



4 Davis Road West, Old Lyme, CT 06371

Ms. Melanie Bachman
Executive Director
CT Siting Council
10 Franklin Square
New Britain, CT 06051

Re: Notice of rescission of Exempt Modification Approval
785 Park Ave., Bloomfield, CT 06002

June 20, 2018

Dear Ms. Bachman:

Sprint Spectrum Realty Company, L.P. ("Sprint"), received CT Siting Council approval for an exempt modification on February 13, 2018; EM-SPRINT- 011-171207. Sprint subsequently found the need to change some equipment from that specified in the approved EM. Sprint, therefore, will not proceed with the EM approval received on that date and will instead resubmit for a new exempt modification with the revised equipment. Please advise if anything else is required to rescind the original approval, and clear the way for the subsequent resubmittal. Thank you.

If you have any questions, please feel free to contact me.

Thank you,

By: *Paul F. Sagristano*

Paul F. Sagristano
Cherundolo Consulting
917.841.0247
psagristano@lrivassoc.com



4 Davis Road West, Suite 5 – Old Lyme, CT 06371

Ms. Melanie Bachman
Executive Director
CT Siting Council
10 Franklin Square
New Britain, CT 06051

Re: Notice of Exempt Modification Application
785 Park Ave., Bloomfield, CT 06002

June 20, 2018

Dear Ms. Bachman:

Sprint Spectrum Realty Company, L.P. (“Sprint”), is submitting to the Connecticut Siting Council for a Notice of Exempt Modification for Proposed Modifications to an Existing Telecommunications Facility located at the above-referenced site. Sprint currently maintains 3 existing panel antenna and 1 parabolic dishes at the 115’ level of the Tower. Sprint proposes to replace the 3 existing antennas and to add 3 new panel antennas (1 per sector) as well as 9 remote radio units (3 per sector) at 115’ tower level as well as 3 new hybrid cables and 48 Antenna-RRH jumper cables, and finally a new ground based growth cabinet and PPC on the existing slab. Sprint will also replace the antenna mounting apparatus.

The Sprint installation was initially approved by Siting Council on 5/27/2010. No Building permit for this construction was found by the Town. The construction and structural documents enclosed reflect the reality of all the current installations on the Tower.

If you have any questions, please feel free to contact me.

Thank you,

By: *Paul F. Sagristano*

Paul F. Sagristano
Cherundolo Consulting
917.841.0247
psagristano@lrvassoc.com



4 Davis Road West, Suite 5 – Old Lyme, CT 06371

Ms. Melanie Bachman
Executive Director
CT Siting Council
10 Franklin Square
New Britain, CT 06051

Re: Notice of Exempt Modification Application
785 Park Ave., Bloomfield, CT 06002

Lat: N 41.8285
Long: W 72.73361

June 20, 2018

Dear Ms. Bachman:

Sprint currently maintains 3 existing panel antenna and 1 parabolic dishes at the 115' level of the Tower. Sprint proposes to replace the 3 existing antennas and to add 3 new panel antennas (1 per sector) as well as 9 remote radio units (3 per sector) at 115' tower level as well as 3 new hybrid cables and 48 Antenna-RRH jumper cables, and finally a new ground based growth cabinet and PPC on the existing slab. Sprint will also replace the antenna mounting apparatus. Sprint is performing a new high-performance upgrade for cellular mobile communications. It is designed to increase the capacity and speed of mobile telephone networks.

The Sprint installation was initially approved by Siting Council on 5/27/2010. No Building permit for this construction was found by the Town.

Please accept this letter as notification to the Council, pursuant to R.C.S.A. Section 16-50j-73, for construction which constitutes an exempt modification pursuant to R.C.S.A. Section 16-50j-72(b)(2). In compliance with R.C.S.A. Section 16-50j-73, a copy of this letter is being sent to and to Phillip K. Schenck Jr. the Town manager for the town of Bloomfield, as well as Jose Giner, P&Z Director for the Town of Bloomfield, and Ray Lemley for Integrated Wireless Services LLC, the tower owner.

Attached is a summary of the planned modifications, including power density calculations reflecting the change in Sprint's operations at the site. Also included is documentation of the structural sufficiency of the tower with proposed modifications to accommodate the revised antenna configuration.

Existing Facility

The Bloomfield facility is located at 785 Park Ave. and is owned by for Integrated Wireless Services LLC, the Site coordinates are: N41.8285, W72.73361. The existing facility consists of a 136' Monnopol. Sprint

currently operates wireless communications equipment on a platform on a concrete slab at the facility and has 3 antennas and 1 Parabolic dish at a centerline of 115' feet on the tower.

Statutory Considerations

The planned modifications to the facility fall within the activities explicitly provided for in R.C.S.A. 16-50j-72(b)(2)

1. The height of the overall structure will be unaffected.
2. The proposed changes will not require an extension of the property boundaries.
3. The proposed additions will not increase the noise level at the existing facility by six decibels or more, or to levels that exceed state and/or local criteria
4. The changes will not increase the calculated “worst case” power density for the combined operations at the site to a level at or above the Federal Communications Commission safety standard.
5. The proposed modifications will not cause a change or alteration in the physical or environmental characteristics of the site.
6. The existing structure and its foundation can support the proposed loading.

For the foregoing reasons, Sprint respectfully submits that the proposed changes at the referenced site constitute exempt modifications under R.C.S.A Section §16-50j-72(b)(2).

Respectfully submitted,

Paul F. Sagristano

Paul F. Sagristano
Charles Cherundolo Consulting
917-841-0247
psagristano@lrvassoc.com

PFS/mtf

Additional Recipients:

Phillip K. Schenck Jr. the Town manager for the town of Bloomfield – Via Fed Ex
Jose Giner, P&Z Director for the Town of Bloomfield – Via Fed Ex
Ray Lemley for Integrated Wireless Services LLC, the tower owner – Via Fed Ex



June 26,2018

Dear Customer:

The following is the proof-of-delivery for tracking number **772514338434**.

Delivery Information:

Status:	Delivered	Delivered to:	Receptionist/Front Desk
Signed for by:	J.PEREZ	Delivery location:	BRANFORD, CT
Service type:	FedEx Express Saver	Delivery date:	Jun 20, 2018 12:01
Special Handling:	Deliver Weekday		
	Direct Signature Required		

Signature image is available. In order to view image and detailed information, the shipper or payor account number of the shipment must be provided.

Shipping Information:

Tracking number:	772514338434	Ship date:	Jun 19, 2018
		Weight:	0.5 lbs/0.2 kg

Recipient:
BRANFORD, CT US

Shipper:
OLD LYME, CT US

Reference

CT52XC024 CSC to Owner

Thank you for choosing FedEx.



June 25, 2018

Dear Customer:

The following is the proof-of-delivery for tracking number **772514252777**.

Delivery Information:

Status:	Delivered	Delivered to:	Receptionist/Front Desk
Signed for by:	D.HELEN	Delivery location:	800 BLOOMFIELD AVE. BLOOMFIELD, CT 06002
Service type:	FedEx Express Saver	Delivery date:	Jun 22, 2018 12:20
Special Handling:	Deliver Weekday Direct Signature Required		



Shipping Information:

Tracking number:	772514252777	Ship date:	Jun 19, 2018
		Weight:	0.5 lbs/0.2 kg

Recipient:
Jose Giner, P&Z Director
Town of Bloomfield
800 Bloomfield Ave.
BLOOMFIELD, CT 06002 US

Shipper:
Paul Sagristano
CCC
4 Davis Road West
Suite 5
OLD LYME, CT 06371 US
CT52XC024 - CSC to P&Z

Reference

Thank you for choosing FedEx.




June 25, 2018

Dear Customer:

The following is the proof-of-delivery for tracking number **772514279660**.

Delivery Information:

Status:	Delivered	Delivered to:	Receptionist/Front Desk
Signed for by:	A.CIOTE	Delivery location:	800 BLOOMFIELD AVE. BLOOMFIELD, CT 06002
Service type:	FedEx Express Saver	Delivery date:	Jun 22, 2018 12:19
Special Handling:	Deliver Weekday Direct Signature Required		



Shipping Information:

Tracking number:	772514279660	Ship date:	Jun 19, 2018
		Weight:	0.5 lbs/0.2 kg

Recipient:
Phillip K. Schenck Jr. Town Manager
Town of Bloomfield
800 Bloomfield Ave.
BLOOMFIELD, CT 06002 US

Shipper:
Paul Sagristano
CCC
4 Davis Road West
Suite 5
OLD LYME, CT 06371 US
CT52XC024 - CSC to Town Mgr.



Reference

Thank you for choosing FedEx.

Town of Bloomfield, Connecticut - Assessment Parcel Map

MBL: 177-3-6

Address: 785 PARK AVE



Approximate Scale:
1 inch = 100 feet

Disclaimer:
This map is for informational purposes only.
All information is subject to verification by any user.
The Town of Bloomfield and its mapping contractors
assume no legal responsibility for the information contained herein.

Map Produced July 2017
Parcels labeled by Unique ID




Property Information

Property Location	785 PARK AVE
Owner	BLOOMFIELD TOWN OF
Co-Owner	POLICE STATION
Mailing Address	800 BLOOMFIELD AVE. BLOOMFIELD CT 06002
Land Use	922 Mun Bldg Com
Land Class	E
Zoning Code	BCD
Census Tract	
Sub Lot	
Neighborhood	
Acreage	2.25
Utilities	
Lot Setting/Desc	
Survey Map	
Foundation	POURED CONC.

Photo



Sketch



Primary Construction Details

Year Built	1991
Stories	1
Building Style	City/Town Hall
Building Use	Commercial
Building Condition	B
Floors	Carpet
Total Rooms	

Bedrooms	
Full Bathrooms	
Half Bathrooms	
Bath Style	
Kitchen Style	
Roof Style	Gable
Roof Cover	Asphalt Shingl

Exterior Walls	Concrete
Interior Walls	Drywall
Heating Type	Forced Air
Heating Fuel	Gas
AC Type	
Gross Bldg Area	20917
Total Living Area	20887



Daniel F. Caruso
Chairman
May 27, 2010

STATE OF CONNECTICUT

CONNECTICUT SITING COUNCIL

Ten Franklin Square, New Britain, CT 06051

Phone: (860) 827-2935 Fax: (860) 827-2950

E-Mail: siting.council@ct.gov

Internet: ct.gov/csc

Thomas F. Flynn III
Site Development Project Manager
Maxton Technology Inc.
1296 Blue Hills Avenue
Bloomfield, CT 06002

RE: **EM-CLEARWIRE-011-100401** – Clearwire Corporation notice of intent to modify an existing telecommunications facility located at 785 Park Avenue, Bloomfield, Connecticut.

Dear Mr. Flynn:

The Connecticut Siting Council (Council) hereby acknowledges your notice to modify this existing telecommunications facility, pursuant to Section 16-50j-73 of the Regulations of Connecticut State Agencies with the following conditions:

- The coax and remote radio heads shall be installed per the structural analysis report dated March 10, 2010 and sealed by Christopher Michael Murphy, P.E.; and
- Not more than 45 days after completion of construction, the Council shall be notified in writing that the coax and remote radio heads were installed as specified.


The proposed modifications are to be implemented as specified here and in your notice dated April 1, 2010, including the placement of all necessary equipment and shelters within the tower compound. The modifications are in compliance with the exception criteria in Section 16-50j-72 (b) of the Regulations of Connecticut State Agencies as changes to an existing facility site that would not increase tower height, extend the boundaries of the tower site, increase noise levels at the tower site boundary by six decibels, and increase the total radio frequencies electromagnetic radiation power density measured at the tower site boundary to or above the standard adopted by the State Department of Environmental Protection pursuant to General Statutes § 22a-162. This facility has also been carefully modeled to ensure that radio frequency emissions are conservatively below State and federal standards applicable to the frequencies now used on this tower.

This decision is under the exclusive jurisdiction of the Council. Please be advised that the validity of this action shall expire one year from the date of this letter. Any additional change to this facility will require explicit notice to this agency pursuant to Regulations of Connecticut State Agencies Section 16-50j-73. Such notice shall include all relevant information regarding the proposed change with cumulative worst-case modeling of radio frequency exposure at the closest point of uncontrolled access to the tower base, consistent with Federal Communications Commission, Office of Engineering and Technology, Bulletin 65. Any deviation from this format may result in the Council implementing enforcement proceedings pursuant to

General Statutes § 16-50u including, without limitation, imposition of expenses resulting from such failure and of civil penalties in an amount not less than one thousand dollars per day for each day of construction or operation in material violation.

Thank you for your attention and cooperation.

Very truly yours,



S/ Derek Phelps
Executive Director

SDP/MP/laf

c: The Honorable Sydney Schulman, Mayor, Town of Bloomfield
Louie Chapman, Jr., Town Manager, Town of Bloomfield
Thomas B. Hooper, Director of Planning, Town of Bloomfield



RADIO FREQUENCY EMISSIONS ANALYSIS REPORT EVALUATION OF HUMAN EXPOSURE POTENTIAL TO NON-IONIZING EMISSIONS

SPRINT Existing Facility

Site ID: CT52XC024

Bloomfield Police Department
785 Park Avenue
Bloomfield, CT 06002

May 21, 2018

EBI Project Number: 6218003637

Site Compliance Summary	
Compliance Status:	COMPLIANT
Site total MPE% of FCC general population allowable limit:	12.17 %



May 21, 2018

SPRINT

Attn: RF Engineering Manager
1 International Boulevard, Suite 800
Mahwah, NJ 07495

Emissions Analysis for Site: **CT52XC024 – Bloomfield Police Department**

EBI Consulting was directed to analyze the proposed SPRINT facility located at **785 Park Avenue, Bloomfield, CT**, for the purpose of determining whether the emissions from the Proposed SPRINT Antenna Installation located on this property are within specified federal limits.

All information used in this report was analyzed as a percentage of current Maximum Permissible Exposure (% MPE) as listed in the FCC OET Bulletin 65 Edition 97-01 and ANSI/IEEE Std C95.1. The FCC regulates Maximum Permissible Exposure in units of microwatts per square centimeter ($\mu\text{W}/\text{cm}^2$). The number of $\mu\text{W}/\text{cm}^2$ calculated at each sample point is called the power density. The exposure limit for power density varies depending upon the frequencies being utilized. Wireless Carriers and Paging Services use different frequency bands each with different exposure limits, therefore it is necessary to report results and limits in terms of percent MPE rather than power density.

All results were compared to the FCC (Federal Communications Commission) radio frequency exposure rules, 47 CFR 1.1307(b)(1) – (b)(3), to determine compliance with the Maximum Permissible Exposure (MPE) limits for General Population/Uncontrolled environments as defined below.

General population/uncontrolled exposure limits apply to situations in which the general population may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Therefore, members of the general population would always be considered under this category when exposure is not employment related, for example, in the case of a telecommunications tower that exposes persons in a nearby residential area.

General population exposure to radio frequencies is regulated and enforced in units of microwatts per square centimeter ($\mu\text{W}/\text{cm}^2$). The general population exposure limits for the 850 MHz Band is approximately $567 \mu\text{W}/\text{cm}^2$. The general population exposure limit for the 1900 MHz (PCS), 2500 MHz (BRS) and 11 GHz microwave bands is $1000 \mu\text{W}/\text{cm}^2$. Because each carrier will be using different frequency bands, and each frequency band has different exposure limits, it is necessary to report percent of MPE rather than power density.



Occupational/controlled exposure limits apply to situations in which persons are exposed as a consequence of their employment and in which those persons who are exposed have been made fully aware of the potential for exposure and can exercise control over their exposure. Occupational/controlled exposure limits also apply where exposure is of a transient nature as a result of incidental passage through a location where exposure levels may be above general population/uncontrolled limits (see below), as long as the exposed person has been made fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Additional details can be found in FCC OET 65.

CALCULATIONS

Calculations were done for the proposed SPRINT Wireless antenna facility located at **785 Park Avenue, Bloomfield, CT**, using the equipment information listed below. All calculations were performed per the specifications under FCC OET 65. Since SPRINT is proposing highly focused directional panel antennas, which project most of the emitted energy out toward the horizon, all calculations were performed assuming a lobe representing the maximum gain of the antenna per the antenna manufactures supplied specifications, minus 10 dB for directional panel antennas and 20 dB for highly focused parabolic microwave dishes, was focused at the base of the tower. For this report the sample point is the top of a 6-foot person standing at the base of the tower.

For all calculations, all equipment was calculated using the following assumptions:

- 1) 1 CDMA channels (850 MHz) were considered for each sector of the proposed installation. This channel has a transmit power of 20 Watts per Channel.
- 2) 2 LTE channels (850 MHz) were considered for each sector of the proposed installation. These Channels have a transmit power of 20 Watts per Channel.
- 3) 5 CDMA channels (1900 MHz (PCS)) were considered for each sector of the proposed installation. These Channels have a transmit power of 16 Watts per Channel.
- 4) 2 LTE channels (1900 MHz (PCS)) were considered for each sector of the proposed installation. These Channels have a transmit power of 40 Watts per Channel.
- 5) 8 LTE channels (2500 MHz (BRS)) were considered for each sector of the proposed installation. These Channels have a transmit power of 20 Watts per Channel.
- 6) 1 microwave backhaul channel (11 GHz) was considered for Sector C. This channel has a transmit power of 1 Watt.



- 7) All radios at the proposed installation were considered to be running at full power and were uncombined in their RF transmissions paths per carrier prescribed configuration. Per FCC OET Bulletin No. 65 - Edition 97-01 recommendations to achieve the maximum anticipated value at each sample point, all power levels emitting from the proposed antenna installation are increased by a factor of 2.56 to account for possible in-phase reflections from the surrounding environment. This is rarely the case, and if so, is never continuous.
- 8) For the following calculations, the sample point was the top of a 6-foot person standing at the base of the tower. The maximum gain of the antenna per the antenna manufactures supplied specifications, minus 10 dB for directional panel antennas and 20 dB for highly focused parabolic microwave dishes, was used in this direction. This value is a very conservative estimate as gain reductions for these particular antennas are typically much higher in this direction.
- 9) The antennas used in this modeling are the **Commscope NNVV-65B-R4** and the **Nokia AAHC** for transmission in the 850 MHz, 1900 MHz (PCS) and 2500 MHz (BRS) frequency bands and one **2-foot parabolic microwave dish** was modeled for the 11 GHz backhaul channels. This is based on feedback from the carrier with regards to anticipated antenna selection. Maximum gain values for all antennas are listed in the Inventory and Power Data table below. The maximum gain of the antenna per the antenna manufactures supplied specifications, minus 10 dB for directional panel antennas and 20 dB for highly focused parabolic microwave dishes, was used for all calculations. This value is a very conservative estimate as gain reductions for these particular antennas are typically much higher in this direction.
- 10) The antenna mounting height centerlines of the proposed antennas and microwave dish are **115 feet** above ground level (AGL) for **Sector A**, **115 feet** above ground level (AGL) for **Sector B** and **115 feet** above ground level (AGL) for Sector C.
- 11) Emissions values for additional carriers were taken from the Connecticut Siting Council active database. Values in this database are provided by the individual carriers themselves.

All calculations were done with respect to uncontrolled / general population threshold limits.



SPRINT Site Inventory and Power Data by Antenna

Sector:	A	Sector:	B	Sector:	C
Antenna #:	1	Antenna #:	1	Antenna #:	1
Make / Model:	Commscope NNVV-65B-R4	Make / Model:	Commscope NNVV-65B-R4	Make / Model:	Commscope NNVV-65B-R4
Gain:	12.75 / 15.05 dBd	Gain:	12.75 / 15.05 dBd	Gain:	12.75 / 15.05 dBd
Height (AGL):	115 feet	Height (AGL):	115 feet	Height (AGL):	115 feet
Frequency Bands	850 MHz / 1900 MHz (PCS)	Frequency Bands	850 MHz / 1900 MHz (PCS)	Frequency Bands	850 MHz / 1900 MHz (PCS)
Channel Count	10	Channel Count	10	Channel Count	10
Total TX Power(W):	220 Watts	Total TX Power(W):	220 Watts	Total TX Power(W):	220 Watts
ERP (W):	6,248.42	ERP (W):	6,248.42	ERP (W):	6,248.42
Antenna A1 MPE%	2.15 %	Antenna B1 MPE%	2.15 %	Antenna C1 MPE%	2.15 %
Antenna #:	2	Antenna #:	2	Antenna #:	2
Make / Model:	Nokia AAHC	Make / Model:	Nokia AAHC	Make / Model:	Nokia AAHC
Gain:	15.05 dBd	Gain:	15.05 dBd	Gain:	15.05 dBd
Height (AGL):	115 feet	Height (AGL):	115 feet	Height (AGL):	115 feet
Frequency Bands	2500 MHz (BRS)	Frequency Bands	2500 MHz (BRS)	Frequency Bands	2500 MHz (BRS)
Channel Count	8	Channel Count	8	Channel Count	8
Total TX Power(W):	160 Watts	Total TX Power(W):	160 Watts	Total TX Power(W):	160 Watts
ERP (W):	5,118.23	ERP (W):	5,118.23	ERP (W):	5,118.23
Antenna A2 MPE%	1.55 %	Antenna B2 MPE%	1.55 %	Antenna C2 MPE%	1.55 %

Microwave Backhaul Data

Antenna Type:	Gain (dBd)	Height (feet AGL):	Frequency Bands	Channel Count	Total TX Power(W)	ERP (W)	MPE %	Sector
2 foot parabolic dish	34 dBd	115	11 GHz	1	1	2511.86	0.08	C

Site Composite MPE%	
Carrier	MPE%
SPRINT – Sector C	3.78 %
Police UHF	0.07 %
Police Back up repeater	0.10 %
Hartford Co. Fire	0.08 %
State Police	0.36 %
NPSAC	0.01 %
RAFS	0.12 %
Verizon Wireless	5.42 %
Nextel	1.10 %
Clearwire	0.16 %
T-Mobile	0.98 %
Site Total MPE %:	12.17 %

SPRINT Sector A Total:	3.70 %
SPRINT Sector B Total:	3.70 %
SPRINT Sector C Total:	3.78 %
Site Total:	12.17 %



Sprint Max Power Values

SPRINT _ Frequency Band / Technology (Sector C)	# Channels	Watts ERP (Per Channel)	Height (feet)	Total Power Density ($\mu\text{W}/\text{cm}^2$)	Frequency (MHz)	Allowable MPE ($\mu\text{W}/\text{cm}^2$)	Calculated % MPE
Sprint 850 MHz CDMA	1	376.73	115	1.14	850 MHz	567	0.20%
Sprint 850 MHz LTE	2	376.73	115	2.28	850 MHz	567	0.40%
Sprint 1900 MHz (PCS) CDMA	5	511.82	115	7.74	1900 MHz (PCS)	1000	0.77%
Sprint 1900 MHz (PCS) LTE	2	1,279.56	115	7.74	1900 MHz (PCS)	1000	0.77%
Sprint 2500 MHz (BRS) LTE	8	639.78	115	15.49	2500 MHz (BRS)	1000	1.55%
Sprint 11 GHz microwave	1	2,511.89	115	0.76	11 GHz	1000	0.08%
						Total:	3.78%



Summary

All calculations performed for this analysis yielded results that were **within** the allowable limits for general population exposure to RF Emissions.

The anticipated maximum composite contributions from the SPRINT facility as well as the site composite emissions value with regards to compliance with FCC's allowable limits for general population exposure to RF Emissions are shown here:

SPRINT Sector	Power Density Value (%)
Sector A:	3.70 %
Sector B:	3.70 %
Sector C:	3.78 %
SPRINT Maximum Total (Sectors A & C):	3.78 %
Site Total:	12.17 %
Site Compliance Status:	COMPLIANT

The anticipated composite MPE value for this site assuming all carriers present is **12.17 %** of the allowable FCC established general population limit sampled at the ground level. This is based upon values listed in the Connecticut Siting Council database for existing carrier emissions.

FCC guidelines state that if a site is found to be out of compliance (over allowable thresholds), that carriers over a 5% contribution to the composite value will require measures to bring the site into compliance. For this facility, the composite values calculated were well within the allowable 100% threshold standard per the federal government.



MASER CONSULTING
— CONNECTICUT —

Tower & Antenna Mount Structural Analysis

FOR
Bloomfield Police Department

Site ID: CT52XC024
785 Park Avenue
Bloomfield, CT 06002

Tower Utilization: 88.5%
Mount Utilization: 36.1%


April 30, 2018

Prepared For

Sprint
201 State Route 17 North
Rutherford, NJ 07070

Prepared By

Maser Consulting Connecticut
331 Newman Springs Road, Suite 203
Red Bank, NJ 07701
732.383.1950



Petros L. Tsoukalas P.E.
Geographic Discipline Leader
Connecticut License No. PEN.32577



Objective:

The objective of this report is to determine the capacity of the existing 136' Monopole tower structure and of the existing antenna support mount at the subject facility for the final wireless telecommunications configuration, per the applicable codes and standards.

Introduction:

Maser Consulting Connecticut has performed limited field observations on August 30, 2017 to visually verify the existing condition of the structure from ground and to locate and quantify the existing wireless appurtenances where possible. Maser Consulting Connecticut has reviewed the following documents in completing this report:

- Previous Antenna Mount Modifications Analysis (17924009A) performed by Maser Consulting P.A., dated January 29, 2018
- RFDS 63853 provided by Sprint, dated March 29, 2018
- Construction Drawings prepared by Maser Consulting P.A. dated April 6, 2018
- Previous Structural Analysis report prepared by Hudson Design Group, dated May 31, 2017.
- Previous Structural Analysis report prepared by CENTEK Engineering, Inc, date July 14, 2015.

The existing structure is an existing 136'-0", three-section, eighteen-sided, tapered Monopole tower originally designed and manufactured by PennSummit Tubular, LLC. The manufacturer's drawings and calculations were unavailable for use in this report. The tower geometry and structure member sizes were all obtained from the referenced report prepared by Hudson Design Group, dated May 31, 2017. The foundation information was obtained from the referenced report prepared by CENTEK Engineering, Inc, date July 14, 2015. The existing **SPRINT** equipment is supported on existing dual stand-off mounts at a centerline of approximately 115'-0" above ground level. This report is based upon this information, as well as the information obtained in the field.

Codes, Standards and Loading:

Maser Consulting Connecticut utilized the following codes and standards:

- 2016 Connecticut State Building Code, Incorporating the 2012 IBC
- Structural Standards for Antenna Supporting Structures and Antennas ANSI/TIA-222-G
 - Basic Wind Speed – 98 mph (3 Second Gust)
 - Exposure Category – B
 - Structural Class – II
 - Topographic Category – 1
 - Ice Wind – 40 mph
 - Ice Thickness – 1"
- Specification for Structural Steel Buildings ANSI/AISC 360-10, American Institute of Steel Construction (AISC)

Loading used in this report is found in Appendix A for the mount analysis and Appendix B for the tower analysis.

Analysis Approach & Assumptions:

The analysis approach used in this structural analysis is based on the premise that if the existing Monopole tower and antenna support mounts are structurally adequate to support the existing and proposed equipment per the aforementioned codes and standards, or if the increase in the forces in the structure are deemed to be negligible or acceptable, then the proposed equipment can be installed as intended.

Tower Numerics, tnx Tower, a tower analysis and design program, designed specifically for the telecommunications industry and for all applicable codes and standards was used for this tower structural analysis.

The existing antenna mount in all sectors has been modeled in RISA-3D, a comprehensive structural analysis program. The program performs design checks of structures under user specified loads. The user specified loads have been calculated separately based on the requirements of the above referenced codes. The program performs an analysis based on the steel code to determine the adequacy of the members, and produces the reactions at the connection points of the mounts to the existing structure. Additional calculations were then prepared to analyze the mount connection points with the proposed loading conditions.

General Site Design Assumption:

- Structural Steel for the monopole sections are assumed to be A607-65 Grade.
- Structural Anchor Bolts are assumed to be A615-75 grade.
- No physical deterioration has occurred in any of the structural components of the monopole and all the tower members have the same capacity as the day they were erected.
- The existing tower foundations are assumed to have been constructed per the original design drawings. As such the calculated foundation capacities are used for comparison to the base reactions of this analysis.
- All engineering services are performed on the basis that the information used is current and correct.
- It is assumed that the telecommunication equipment supports, antenna supports, and existing structure have been designed by a registered licensed professional engineer for the existing loads acting on the structure, as required by all applicable codes, prior to the proposed modifications listed within this report, if any.
- It is assumed that information provided by the client regarding the structure itself, the antenna models, feed lines, and other relevant information is current and correct.
- It is the responsibility of the client to ensure that the information provided to Maser Consulting Connecticut and used in the performance of our engineering services is correct and complete. In the absence of information to the contrary, we assume that the original design, material production, fabrication, and erection of the existing structure was performed in accordance with accepted industry design standards and in accordance with all applicable codes. Further, it is assumed that the existing structure and appurtenances have been properly maintained in accordance with all applicable codes and manufacturer's specifications and no structural defects and/or deterioration to the structural members has occurred.
- It is assumed all other existing appurtenances, antennas, cables, etc. belonging to others have been installed and supported per code and per specifications so as not to damage any existing structural support members, and that any contributing loads from adjacent equipment has been taken into consideration for their design.

- All services are performed, results obtained, and recommendations made in accordance with generally accepted engineering principles and practices. Maser Consulting Connecticut is not responsible for the conclusion, opinions, and recommendations made by others based on the information we supply.

Site Specific Design Parameters:

The following design parameters have been utilized in this report:

- *Structural Steel Pipes are constructed of A53 Grade B Steel*
- *Structural Steel Tubes are constructed of A500 Grade B steel*
- *The Proposed Mount (Site Pro 1 RDS-23096) listed in Previous Antenna mount modifications analysis (17924009A) performed by Maser Consulting P.A., has been installed*

Calculations:

The calculations are found in Appendix A of this report.

Conclusion:

Maser Consulting Connecticut has determined the existing antenna support mount has **ADEQUATE** structural capacity to support the proposed loading. The existing antenna support mount has been determined to be stressed to a maximum of **36.1%** of its structural capacity with the maximum usage occurring at the Pipe Mast.

The existing Monopole tower was analyzed for the loading in the applicable codes and standards. The tower has been determined to be structurally **ADEQUATE** to support the proposed and existing antennas, based upon the aforementioned assumptions. The Monopole tower has been determined to be stressed to a maximum of **88.5%** of its structural capacity with the maximum usage occurring at the base plate.

Additionally, the base reactions have been compared to the previous structural analyses. It is assumed that the foundations and capacities noted in the previous structural analysis by CENTEK Engineering are accurate. Based on the comparison of the capacities to the base reactions of this analysis, the existing concrete foundations have been determined to have **ADEQUATE** structural capacity. Therefore, the proposed **SPRINT** installation **CAN** be placed as intended.

Foundation Reaction Comparison:

	Capacity*	Current Reactions	Pass/Fail
Moment Capacity	4157 ft-k	3359 ft-k	Pass
Axial Capacity	71913.6 kips	316.43 kips	Pass

* Capacities were calculated in the structural analysis by CENTEK Engineering and a reduction factor was applied

It should be noted that due to a lack of information Maser Consulting Connecticut did not perform an analysis on the foundation, but a comparison of the capacities summarized in previous analysis with the current forces has been determined. If information is provided, then this report can be amended. The conclusions reached by Maser Consulting Connecticut in this evaluation are only applicable for the existing structural members supporting the proposed **SPRINT** telecommunications installation described herein.

The conclusions reached by Maser Consulting Connecticut in this evaluation are only applicable for the existing structural members supporting the proposed Sprint telecommunications installation described herein.

Maser Consulting Connecticut reserves the right to amend this report if additional information about the existing members is provided. The conclusions reached by Maser Consulting Connecticut in this report are only valid for the appurtenances listed in this report. Any change to the installation will require a revision to this structural analysis.

We appreciate the opportunity to be of service on this project. If you should have any questions or require any additional information, please do not hesitate to call our office.
Sincerely,

Maser Consulting Connecticut



Petros E. Tsoukalas P.E.
Connecticut Licensed Professional Engineer
License No. PEN.32577



Anthony Bassett
Structural Engineer



APPENDIX A



Client:	Sprint	Computed By:	AB
Site Name:	Bloomfield Police	Date:	4/30/2018
Project No.	179240009A	Verified By:	PET
Title:	Antenna Mount Analysis	Page:	2

ANALYSIS AND DESIGN



Client:	Sprint	Computed By:	AB
Site Name:	Bloomfield Police	Date:	4/30/2018
Project No.:	179240009A	Verified By:	PET
Title:	Antenna Mount Analysis	Page:	3

I. DESIGN INPUTS

Calculations for gravity and lateral loading on equipment and support mounts are determined as per the ANSI/TIA-222-G Code, Addendum 2

Wind Load Inputs Parameters

		Reference	Equation
Antenna Centerline	z 115 ft		
Nomial Wind Speed (3 sec. Gust):	V 98 mph	Ref. 1, Eqn. 16-33	
Nomial Wind Speed with Ice (3 sec. gust):	V_i 40.0 mph	(Figure a5-2a, p. 233)	
Service Wind Speed:	V_s 60.0 mph	(Figure a5-2a, p. 233)	
Design Ice Thickness:	t_i 1.00 in	(Figure A1-2a, p. 233)	
Exposure Category:	B	Ref. 3, Section 2.6.5.1	
Structure Class:	II	Ref. 3, Table 2-1	
Gust Effect Factor:	G_h 1.10	Ref. 3, Section 2.6.7	
Wind Directionality Factor:	K_d 0.85	Ref. 3, Table 2-2	
Topographic Category:	1	Ref. 3, Section 2.6.6.2	

Wind Load Coefficients

Importance Factors:

Non-Iced:	I 1	Ref. 3, Table 2-3
Iced:	I_{ice} 1	(Table 2-3, P. 39)

Exposure Category Coefficients:

3-s Gust-Speed Power Law Exponent:	α 7.0	Ref. 3, Table 2-4	
Nominal Height of the Atmospheric Boundary Layer:	Z_g 1200 ft	Ref. 3, Table 2-4	
Min. Value for k_z :	$K_{z_{min}}$ 0.70	Ref. 3, Table 2-4	
Terrain Constant:	K_e 0.90	Ref. 3, Table 2-4	
Velocity Pressure Exposure Coefficient:	K_z 1.028	Ref. 3, Section 2.6.5.2	$=2.01 \cdot (z/z_g)^{2\alpha}$

Topographic Category Coefficients:

Topographic Constant:	K_t N/A	Ref. 3, Table 2-5	
Height Attenuation Factor:	f N/A	Ref. 3, Table 2-5	
Height Reduction Factor:	K_h N/A	Ref. 3, Section 2.6.6.4	$=e^{(fz/H)}$
Topographic Factor:	K_{zt} 1.00	Ref. 3, Section 2.6.6.4	$=[1+(K_e \cdot K_t/K_h)]^2$

Ice Accumulation:

Ice Velocity Pressure Exposure Coefficient:	K_{iz} 1.13		$=(z/33)^{0.10}$
Factored Ice Thickness:	t_{iz} 2.27 in	(Section 2.6.8, p. 16)	$=2.0 \cdot t_i \cdot I \cdot K_{iz} \cdot K_{zt}$
Ice Density:	ρ_i 56.00 pcf		

Design Wind Pressures:

Velocity Pressure:	q_z 21.49 psf	Ref. 3, Section 2.6.9.6	$=0.00256 \cdot K_z \cdot K_{zt} \cdot K_d \cdot V^2 \cdot I$
Velocity Pressure (With Ice):	q_{zi} 3.58 psf	(Section 2.6.9.6, P. 25)	$=.00256 \cdot K_z \cdot K_{zt} \cdot K_d \cdot V_i^2 \cdot I$
Velocity Pressure (Service):	q_{zs} 8.06 psf	(Section 2.6.9.6, P. 25)	$=.00256 \cdot K_z \cdot K_{zt} \cdot K_d \cdot V_s^2 \cdot I$



Client:	Sprint	Computed By:	AB
Site Name:	Bloomfield Police	Date:	4/30/2018
Project No.	179240009A	Verified By:	PET
Title:	Antenna Mount Analysis	Page:	5

BASIC EQUATIONS

ANSI/TIA-222-G Reference

Importance Factor: $I := \begin{cases} 1.0 & \text{if Class} = \text{"II"} \\ 1.15 & \text{if Class} = \text{"III"} \end{cases}$ Table 2-3, Pg. 39

Force Coefficient:
(Square) $C_{f_square}(h, w) := \begin{cases} 1.2 & \text{if } \frac{h}{w} \leq 2.5 \\ \left[1.2 + \frac{0.2}{4.5} \cdot \left(\frac{h}{w} - 2.5 \right) \right] & \text{if } \frac{h}{w} > 2.5 \wedge \frac{h}{w} \leq 7 \\ \left[1.4 + \frac{0.6}{18} \cdot \left(\frac{h}{w} - 7 \right) \right] & \text{if } \frac{h}{w} > 7 \wedge \frac{h}{w} \leq 25 \\ 2.0 & \text{otherwise} \end{cases}$ Table 2-8, P. 42

Force Coefficient:
(Round) $C_{f_round}(h, w) := \begin{cases} 0.7 & \text{if } \frac{h}{w} \leq 2.5 \\ \left[0.7 + \frac{0.1}{4.5} \cdot \left(\frac{h}{w} - 2.5 \right) \right] & \text{if } \frac{h}{w} > 2.5 \wedge \frac{h}{w} \leq 7 \\ \left[0.8 + \frac{0.4}{18} \cdot \left(\frac{h}{w} - 7 \right) \right] & \text{if } \frac{h}{w} > 7 \wedge \frac{h}{w} \leq 25 \\ 1.2 & \text{otherwise} \end{cases}$ Table 2-8, P. 42

Terrain Exposure Constants: Table 2-4, P. 40

$$\alpha := \begin{cases} 7.0 & \text{if Exp} = \text{"B"} \\ 9.5 & \text{if Exp} = \text{"C"} \\ 11.5 & \text{if Exp} = \text{"D"} \end{cases} \quad Z_g := \begin{cases} 1200\text{ft} & \text{if Exp} = \text{"B"} \\ 900\text{ft} & \text{if Exp} = \text{"C"} \\ 700\text{ft} & \text{if Exp} = \text{"D"} \end{cases} \quad K_{zmin} := \begin{cases} 0.70 & \text{if Exp} = \text{"B"} \\ 0.85 & \text{if Exp} = \text{"C"} \\ 1.03 & \text{if Exp} = \text{"D"} \end{cases}$$



Client:	Sprint	Computed By:	AB
Site Name:	Bloomfield Police	Date:	4/30/2018
Project No.:	179240009A	Verified By:	PET
Title:	Antenna Mount Analysis	Page:	6

BASIC EQUATIONS

ANSI/TIA-222-G Reference

Velocity Pressure Coefficient:

$$K_z(z) := \begin{cases} K_z \leftarrow \max \left[2.01 \cdot \left(\frac{z}{Z_g} \right)^{\frac{2}{\alpha}}, K_{zmin} \right] \\ K_z \leftarrow \min(K_z, 2.01) \end{cases}$$

$$K_z := K_z(z)$$

Section 2.6.5, P. 13

$$K_{zt}(z) := K_{zt} \leftarrow \begin{cases} 1.0 & \text{if Topo} = "1" \\ \text{otherwise} \\ \begin{cases} K_e \leftarrow \begin{cases} 0.90 & \text{if Exp} = "B" \\ 1.00 & \text{if Exp} = "C" \\ 1.10 & \text{if Exp} = "D" \end{cases} \\ K_t \leftarrow \begin{cases} 0.43 & \text{if Topo} = "2" \\ 0.53 & \text{if Topo} = "3" \\ 0.72 & \text{if Topo} = "4" \end{cases} \\ f \leftarrow \begin{cases} 1.25 & \text{if Topo} = "2" \\ 2.00 & \text{if Topo} = "3" \\ 1.50 & \text{if Topo} = "4" \end{cases} \\ K_h \leftarrow e^{\left(\frac{f \cdot z}{CH} \right)} \\ \left(1 + \frac{K_e \cdot K_t}{K_h} \right)^2 \end{cases} \end{cases}$$

Section 2.6.6.4, p. 14

Table 2-4 p. 40

Table 2-5 p. 40

Table 2-5 p. 40

Section 2.6.6.4, P. 14

Section 2.6.6.4, P. 14

$$K_{zt} := K_{zt}(z)$$

Velocity Pressure:

Section 2.6.9.6, P. 25

$$q_z := 0.00256 \cdot K_z \cdot K_{zt} \cdot K_d \cdot V^2 \cdot I \text{ psf}$$



Client:	Sprint	Computed By:	AB
Site Name:	Bloomfield Police	Date:	4/30/2018
Project No.:	179240009A	Verified By:	PET
Title:	Antenna Mount Analysis	Page:	7

LOAD EQUATIONS

WIND LOAD

Area (Normal):	$AN_{area} = H_{ant} \cdot W_{ant}$
Area (Side):	$AT_{area} = H_{ant} \cdot D_{ant}$
Force Coefficient (Normal):	$C_{fn} = C_{fsquare}(H_{ant}, W_{ant})$
Force Coefficient (Side):	$C_{fs} = C_{fsquare}(H_{ant}, D_{ant})$
Pipe Area (Normal):	$AN_p = \max[(L_p - H_{ant}) * D_p, 0]$
Pipe Area (Side):	$AT_p = L_p \cdot D_p$
Force Coefficient (Normal):	$C_{fp} = C_{fround}(L_p, D_p)$
Normal Effective Projected Area:	$E_{pan} = (C_{fn} \cdot AN_{area}) + (C_{fp} \cdot AN_p)$
Side Effective Projected Area:	$E_{pat} = (C_{fs} \cdot AT_{area}) + (C_{fp} \cdot AT_p)$
Effective Projected Area:	$EPA = \max(E_{pan}, E_{pat})$
Wind Force:	$F_{ant} = q_z \cdot Gh \cdot EPA$

ICE DEAD LOAD

Largest Out-to-Out Dimension:	$D_{ant} = \sqrt{D_{ant}^2 + W_{ant}^2}$
Cross Sectional Area of Ice:	$A_{ice_ant} = \pi \cdot t_{iz} \cdot (D_{ant} + t_{iz})$
Total Ice Dead Load:	$DL_{ice_ant} = \rho_i \cdot (A_{ice_ant} \cdot H_{ant})$

ICE WIND LOAD

Dimensions:	$H_{i_ant} = H_{ant} + 2t_{iz}$
	$W_{i_ant} = W_{ant} + 2t_{iz}$
	$D_{i_ant} = D_{ant} + 2t_{iz}$
Area (Normal):	$AIN_{area} = H_{i_ant} \cdot W_{i_ant}$
Area (Side):	$AIT_{area} = H_{i_ant} \cdot D_{i_ant}$
Force Coefficient (Normal):	$Ci_{fn} = C_{fsquare}(H_{i_ant}, W_{i_ant})$
Force Coefficient (Side):	$Ci_{fs} = C_{fsquare}(H_{i_ant}, D_{i_ant})$
Pipe Area (Normal):	$AN_p = \max[(L_{ip} - H_{i_ant}) * D_{ip}, 0]$
Pipe Area (Side):	$AT_p = L_{ip} \cdot D_{ip}$
Force Coefficient (Normal):	$C_{fp} = C_{fround}(L_{ip}, D_{ip})$
Normal Effective Projected Area:	$E_{pain} = (Ci_{fn} \cdot AIN_{area}) + (C_{fp} \cdot AN_p)$
Side Effective Projected Area:	$E_{pait} = (Ci_{fs} \cdot AIT_{area}) + (C_{fp} \cdot AT_p)$
Effective Projected Area:	$EPA_i = \max(E_{pain}, E_{pait})$
Wind Force:	$F_{i_ant} = q_z \cdot Gh \cdot EPA_i$





Client:	Sprint	Computed By:	AB
Site Name:	Bloomfield Police	Date:	4/30/2018
Project No.	179240009A	Verified By:	PET
Title:	Antenna Mount Analysis	Page:	8

III. ATTACHMENTS



Client:	Sprint	Computed By:	AB
Site Name:	Bloomfield Police	Date:	4/30/2018
Project No.:	179240009A	Verified By:	PET
Title:	Antenna Mount Analysis	Page:	9



RISA MODEL





Client:	Sprint	Computed By:	AB
Site Name:	Bloomfield Police	Date:	4/30/2018
Project No.:	179240009A	Verified By:	PET
Title:	Antenna Mount Analysis	Page:	10

RISA WORST CASE LOADING




Loads: LC 8, 1.2D+1.6W7
Envelope Only Solution




Client: Sprint
Site Name: Bloomfield Police
Project No: 179240009A
Title: Antenna Mount Analysis

Computed By: AB
Date: 4/30/2018
Verified By: PET
Page: 11

RISA CODE CHECK



Code Check	
Black	No Calc
Red	> 1.0
Magenta	.90-1.0
Green	.75-.90
Cyan	.50-.75
Blue	0-.50



Member Code Checks Displayed
Envelope Only Solution

DESIGNED APPURTENANCE LOADING


TYPE	ELEVATION	TYPE	ELEVATION
20' Dipole	143	AAHC (Sprint)	115
PTP 400	142	AAHC (Sprint)	115
3"x4.5' Pipe	140	AAHC (Sprint)	115
(2) Ericsson AIR21 with 6' pipe (T-Mobile)	138	BXA-70063-6CF-EDIN-X (Verizon)	106
(2) Ericsson AIR21 with 6' pipe (T-Mobile)	138	BXA-80063-4BF W/ Mount Pipe (Verizon)	106
(2) Ericsson AIR21 with 6' pipe (T-Mobile)	138	BXA-80063-4BF W/ Mount Pipe (Verizon)	106
(2) Ericsson AIR21 with 6' pipe (T-Mobile)	138	SLCP 2x6014 (Verizon)	106
LNX-6515DS-VTM (T-Mobile)	138	SLCP 2x6014 (Verizon)	106
LNX-6515DS-VTM (T-Mobile)	138	SLCP 2x6014 (Verizon)	106
LNX-6515DS-VTM (T-Mobile)	138	B13 RRH4x30 (Verizon)	106
KRY 112 71 (T-Mobile)	138	B13 RRH4x30 (Verizon)	106
KRY 112 71 (T-Mobile)	138	B13 RRH4x30 (Verizon)	106
KRY 112 71 (T-Mobile)	138	B4 RRH 2x60-4R (Verizon)	106
RRUS-11 (T-Mobile)	138	B4 RRH 2x60-4R (Verizon)	106
RRUS-11 (T-Mobile)	138	B4 RRH 2x60-4R (Verizon)	106
RRUS-11 (T-Mobile)	138	B4 RRH 2x60-4R (Verizon)	106
RRUS-11 (T-Mobile)	138	DB-T1-6Z-8ZB-0Z (Verizon)	106
Pirod 13' Platform w/ Handrail	138	DB-T1-6Z-8ZB-0Z (Verizon)	106
Valmont Light Duty Tri-Bracket (Sprint)	115	Pirod 13' Platform w/ Handrail (Verizon)	106
Dual Standoff Mount (Sprint)	115	Pirod 13' Platform w/ Handrail (Verizon)	106
Dual Standoff Mount (Sprint)	115	SBNHH-1D65A (Verizon)	106
Dual Standoff Mount (Sprint)	115	SBNHH-1D65A (Verizon)	106
NNVV-65B-R4 (Sprint)	115	SBNHH-1D65A (Verizon)	106
NNVV-65B-R4 (Sprint)	115	Pirod 13' Platform w/ Handrail	95
NNVV-65B-R4 (Sprint)	115	PTP 400	83
(2) RRH-2X50-800 (Sprint)	115	3"x4.5' Pipe	83
(2) RRH-2X50-800 (Sprint)	115	3"x4.5' Pipe	83
(2) RRH-2X50-800 (Sprint)	115	PTP 400	83
ALU RRH-4X45-1900 (Sprint)	115	3"x4.5' Pipe	83
ALU RRH-4X45-1900 (Sprint)	115	PTP 400	83
ALU RRH-4X45-1900 (Sprint)	115		

MATERIAL STRENGTH

GRADE	Fy	Fu	GRADE	Fy	Fu
A607-65	65 ksi	80 ksi			


TOWER DESIGN NOTES

1. Tower is located in Hartford County, Connecticut.
2. Tower designed for Exposure B to the TIA-222-G Standard.
3. Tower designed for a 98 mph basic wind in accordance with the TIA-222-G Standard.
4. Tower is also designed for a 40 mph basic wind with 1.00 in ice. Ice is considered to increase in thickness with height.
5. Deflections are based upon a 60 mph wind.
6. Tower Structure Class II.
7. Topographic Category 1 with Crest Height of 0.00 ft
8. TOWER RATING: 88.5%






Section	1	2	3
Length (ft)	48.75	45.00	51.00
Number of Sides	18	18	18
Thickness (in)	0.1875	0.3750	0.5000
Socket Length (ft)	4.00	4.75	35.3088
Top Dia (in)	23.0000	29.6932	43.3600
Bot Dia (in)	30.7000	36.8100	11230.2
Grade	A607-65	A607-65	20285.7
Weight (lb)	2763.8	6291.6	

ALL REACTIONS
ARE FACTORED



Maser Consulting PA 400 Valley Road Mt. Arlington, NJ Phone: 973398.3110 FAX: 973.398.3199		Job: 17924009A	
		Project: Bloomfield Police Department	
Client: Sprint	Drawn by: abassett	App'd:	
Code: TIA-222-G	Date: 04/19/18	Scale: NTS	
Path:		Dwg No. E-1	




Maser Consulting PA		Job: 17924009A	
400 Valley Road		Project: Bloomfield Police Department	
Mt. Arlington, NJ		Client: Sprint	Drawn by: abassett
Phone: 973.398.3110		Code: TIA-222-G	Date: 04/19/18
FAX: 973.398.3199		Path:	Scale: NTS
		Dwg No. E-5	

Feed Line Distribution Chart

0' - 136'

— Round
 — Flat
 — App In Face
 — App Out Face
 — Truss Leg



Maser Consulting PA 400 Valley Road Mt. Arlington, NJ Phone: 973398.3110 FAX: 973.398.3199		Job: 17924009A	
		Project: Bloomfield Police Department	
Client: Sprint	Drawn by: abassett	App'd:	
Code: TIA-222-G	Date: 04/19/18	Scale: NTS	
Path:			Dwg No. E-7

tnxTower Maser Consulting PA 400 Valley Road Mt. Arlington, NJ Phone: 973.398.3110 FAX: 973.398.3199	Job 17924009A	Page 1 of 21
	Project Bloomfield Police Department	Date 08:49:01 04/19/18
	Client Sprint	Designed by abassett

Tower Input Data

There is a pole section.

This tower is designed using the TIA-222-G standard.

The following design criteria apply:

Tower is located in Hartford County, Connecticut.

Basic wind speed of 98 mph.

Structure Class II.

Exposure Category B.

Topographic Category 1.

Crest Height 0.00 ft.

Nominal ice thickness of 1.0000 in.

Ice thickness is considered to increase with height.

Ice density of 56 pcf.

A wind speed of 40 mph is used in combination with ice.

Temperature drop of 50 °F.

Deflections calculated using a wind speed of 60 mph.

A non-linear (P-delta) analysis was used.

Pressures are calculated at each section.

Stress ratio used in pole design is 1.

Local bending stresses due to climbing loads, feed line supports, and appurtenance mounts are not considered.

Options

<ul style="list-style-type: none"> Consider Moments - Legs Consider Moments - Horizontals Consider Moments - Diagonals Use Moment Magnification √ Use Code Stress Ratios √ Use Code Safety Factors - Guys Escalate Ice Always Use Max Kz Use Special Wind Profile Include Bolts In Member Capacity Leg Bolts Are At Top Of Section Secondary Horizontal Braces Leg Use Diamond Inner Bracing (4 Sided) SR Members Have Cut Ends SR Members Are Concentric 	<ul style="list-style-type: none"> Distribute Leg Loads As Uniform Assume Legs Pinned Assume Rigid Index Plate Use Clear Spans For Wind Area Use Clear Spans For KL/r Retention Guys To Initial Tension √ Bypass Mast Stability Checks √ Use Azimuth Dish Coefficients Project Wind Area of Appurt. Autocalc Torque Arm Areas Add IBC .6D+W Combination Sort Capacity Reports By Component Triangulate Diamond Inner Bracing Treat Feed Line Bundles As Cylinder 	<ul style="list-style-type: none"> Use ASCE 10 X-Brace Ly Rules Calculate Redundant Bracing Forces Ignore Redundant Members in FEA SR Leg Bolts Resist Compression All Leg Panels Have Same Allowable Offset Girt At Foundation √ Consider Feed Line Torque Include Angle Block Shear Check Use TIA-222-G Bracing Resist. Exemption Use TIA-222-G Tension Splice Exemption <li style="background-color: #e0e0e0;">Poles Include Shear-Torsion Interaction Always Use Sub-Critical Flow Use Top Mounted Sockets
--	--	--

Tapered Pole Section Geometry

Section	Elevation ft	Section Length ft	Splice Length ft	Number of Sides	Top Diameter in	Bottom Diameter in	Wall Thickness in	Bend Radius in	Pole Grade
L1	136.00-87.25	48.75	4.00	18	23.0000	30.7000	0.1875	0.7500	A607-65 (65 ksi)
L2	87.25-46.25	45.00	4.75	18	29.6932	36.8100	0.3750	1.5000	A607-65 (65 ksi)

tnxTower Maser Consulting PA 400 Valley Road Mt. Arlington, NJ Phone: 973.398.3110 FAX: 973.398.3199	Job 17924009A	Page 2 of 21
	Project Bloomfield Police Department	Date 08:49:01 04/19/18
	Client Sprint	Designed by abassett

Section	Elevation ft	Section Length ft	Splice Length ft	Number of Sides	Top Diameter in	Bottom Diameter in	Wall Thickness in	Bend Radius in	Pole Grade (65 ksi)
L3	46.25-0.00	51.00		18	35.3088	43.3600	0.5000	2.0000	A607-65

Tapered Pole Properties

Section	Tip Dia. in	Area in ²	I in ⁴	r in	C in	I/C in ³	J in ⁴	I/Q in ²	w in	w/t
L1	23.3548	13.5763	892.6152	8.0984	11.6840	76.3964	1786.4050	6.7894	3.7180	19.829
	31.1736	18.1588	2135.8907	10.8319	15.5956	136.9547	4274.5918	9.0811	5.0732	27.057
L2	30.7936	34.8960	3789.5512	10.4080	15.0841	251.2274	7584.0888	17.4513	4.5660	12.176
	37.3779	43.3668	7273.3077	12.9344	18.6995	388.9578	14556.1858	21.6875	5.8186	15.516
L3	36.6149	55.2415	8456.3098	12.3571	17.9369	471.4487	16923.7467	27.6260	5.3343	10.669
	44.0289	68.0188	15785.9556	15.2153	22.0269	716.6678	31592.6828	34.0159	6.7514	13.503

Tower Elevation ft	Gusset Area (per face) ft ²	Gusset Thickness in	Gusset Grade	Adjust. Factor A _f	Adjust. Factor A _r	Weight Mult.	Double Angle Stitch Bolt Spacing Diagonals in	Double Angle Stitch Bolt Spacing Horizontals in	Double Angle Stitch Bolt Spacing Redundants in
L1 136.00-87.25				1	1	1.05			
L2 87.25-46.25				1	1	1.05			
L3 46.25-0.00				1	1	1.05			

Monopole Base Plate Data

Base Plate Data	
Base plate is square	√
Base plate is grouted	
Anchor bolt grade	A615-75
Anchor bolt size	2.2500 in
Number of bolts	16
Embedment length	84.0000 in
f _c	4 ksi
Grout space	3.0000 in
Base plate grade	A572-55
Base plate thickness	3.0000 in
Bolt circle diameter	49.7500 in
Outer diameter	54.7500 in
Inner diameter	43.3600 in
Base plate type	Plain Plate

Feed Line/Linear Appurtenances - Entered As Round Or Flat

Description	Sector	Component Type	Placement ft	Total Number	Number Per Row	Start/End Position	Width or Diameter in	Perimeter in	Weight plf
1-5/8 (T-Mobile)	C	Surface Ar (CaAa)	136.00 - 4.00	6	6	0.000 0.000	1.9800		1.04

tnxTower Maser Consulting PA 400 Valley Road Mt. Arlington, NJ Phone: 973.398.3110 FAX: 973.398.3199	Job 17924009A	Page 3 of 21
	Project Bloomfield Police Department	Date 08:49:01 04/19/18
	Client Sprint	Designed by abassett

Description	Sector	Component Type	Placement ft	Total Number	Number Per Row	Start/End Position	Width or Diameter in	Perimeter in	Weight plf
3" Flex Conduit (Sprint)	C	Surface Ar (CaAa)	115.00 - 4.00	2	2	0.000 0.000	3.0100		2.50
1-5/8 Fiber Cable (T-Mobile)	A	Surface Ar (CaAa)	136.00 - 4.00	1	1	0.000 0.000	1.9800		1.04
1-5/8 Fiber Cable (Verizon)	B	Surface Ar (CaAa)	106.00 - 4.00	2	2	0.000 0.000	1.9800		1.04
LDF6-50A (1-1/4 FOAM) (Sprint)	C	Surface Ar (CaAa)	115.00 - 4.00	4	4	0.000 0.000	1.5500		0.66

Feed Line/Linear Appurtenances - Entered As Area

Description	Face or Leg	Allow Shield	Component Type	Placement ft	Total Number		C _{AA} ft ² /ft	Weight plf
1-5/8 (T-Mobile)	A	No	Inside Pole	136.00 - 4.00	12	No Ice	0.00	1.04
						1/2" Ice	0.00	1.04
						1" Ice	0.00	1.04
1-5/8 (Verizon)	B	No	Inside Pole	106.00 - 4.00	12	No Ice	0.00	1.04
						1/2" Ice	0.00	1.04
						1" Ice	0.00	1.04
Category 5e (Town)	C	No	Inside Pole	136.00 - 4.00	1	No Ice	0.00	0.21
						1/2" Ice	0.00	0.21
						1" Ice	0.00	0.21
Category 5e (Town)	A	No	Inside Pole	136.00 - 4.00	1	No Ice	0.00	0.21
						1/2" Ice	0.00	0.21
						1" Ice	0.00	0.21
1-5/8 (Town)	B	No	Inside Pole	136.00 - 4.00	3	No Ice	0.00	1.04
						1/2" Ice	0.00	1.04
						1" Ice	0.00	1.04

Feed Line/Linear Appurtenances Section Areas

Tower Section	Tower Elevation ft	Face	A _R ft ²	A _F ft ²	C _{AA} In Face ft ²	C _{AA} Out Face ft ²	Weight lb
L1	136.00-87.25	A	0.000	0.000	9.652	0.000	669.34
		B	0.000	0.000	7.425	0.000	425.10
		C	0.000	0.000	91.826	0.000	526.45
L2	87.25-46.25	A	0.000	0.000	8.118	0.000	562.93
		B	0.000	0.000	16.236	0.000	724.88
		C	0.000	0.000	98.810	0.000	577.69
L3	46.25-0.00	A	0.000	0.000	8.366	0.000	580.09
		B	0.000	0.000	16.731	0.000	746.98
		C	0.000	0.000	101.823	0.000	595.30

Feed Line/Linear Appurtenances Section Areas - With Ice

Tower Section	Tower Elevation ft	Face or Leg	Ice Thickness in	A _R ft ²	A _F ft ²	C _{AA} In Face ft ²	C _{AA} Out Face ft ²	Weight lb
L1	136.00-87.25	A	2.258	0.000	0.000	31.664	0.000	1239.13
		B		0.000	0.000	19.864	0.000	715.58

tnxTower Maser Consulting PA 400 Valley Road Mt. Arlington, NJ Phone: 973.398.3110 FAX: 973.398.3199	Job	17924009A	Page	4 of 21
	Project	Bloomfield Police Department	Date	08:49:01 04/19/18
	Client	Sprint	Designed by	abassett

Tower Section	Tower Elevation ft	Face or Leg	Ice Thickness in	A _R ft ²	A _F ft ²	C _{AA} In Face ft ²	C _{AA} Out Face ft ²	Weight lb
L2	87.25-46.25	C		0.000	0.000	173.621	0.000	3128.98
		A	2.145	0.000	0.000	26.630	0.000	1042.14
		B		0.000	0.000	43.435	0.000	1360.05
L3	46.25-0.00	C		0.000	0.000	192.934	0.000	3470.10
		A	1.926	0.000	0.000	26.493	0.000	1036.91
		B		0.000	0.000	43.574	0.000	1357.21
		C		0.000	0.000	195.257	0.000	3396.62

Feed Line Center of Pressure

Section	Elevation ft	CP _X in	CP _Z in	CP _X Ice in	CP _Z Ice in
L1	136.00-87.25	-0.0230	1.3990	-0.0696	1.2010
L2	87.25-46.25	0.1304	1.6140	0.1218	1.3286
L3	46.25-0.00	0.1327	1.6420	0.1335	1.4534

Shielding Factor Ka

Tower Section	Feed Line Record No.	Description	Feed Line Segment Elev.	K _a No Ice	K _a Ice
L1	1	1-5/8	87.25 - 136.00	1.0000	1.0000
L1	2	3" Flex Conduit	87.25 - 115.00	1.0000	1.0000
L1	3	1-5/8 Fiber Cable	87.25 - 136.00	1.0000	1.0000
L1	4	1-5/8 Fiber Cable	87.25 - 106.00	1.0000	1.0000
L1	10	LDF6-50A (1-1/4 FOAM)	87.25 - 115.00	1.0000	1.0000
L2	1	1-5/8	46.25 - 87.25	1.0000	1.0000
L2	2	3" Flex Conduit	46.25 - 87.25	1.0000	1.0000
L2	3	1-5/8 Fiber Cable	46.25 - 87.25	1.0000	1.0000
L2	4	1-5/8 Fiber Cable	46.25 - 87.25	1.0000	1.0000
L2	10	LDF6-50A (1-1/4 FOAM)	46.25 - 87.25	1.0000	1.0000

Discrete Tower Loads

Description	Face or Leg	Offset Type	Offsets: Horz Lateral Vert ft ft ft	Azimuth Adjustment °	Placement ft	C _{AA} Front ft ²	C _{AA} Side ft ²	Weight lb	
20' Dipole	C	From Face	1.00	0.0000	143.00	No Ice	7.00	7.00	60.00
			0.00			1/2" Ice	10.04	10.04	115.61
			10.00			1" Ice	13.08	13.08	171.22

tnxTower Maser Consulting PA 400 Valley Road Mt. Arlington, NJ Phone: 973.398.3110 FAX: 973.398.3199	Job						Page		
	17924009A						5 of 21		
	Project						Date		
Bloomfield Police Department						08:49:01 04/19/18			
Client						Designed by			
Sprint						abassett			

Description	Face or Leg	Offset Type	Offsets:		Azimuth Adjustment	Placement	C _{AA}		Weight
			Horz	Vert			Front	Side	
			ft	ft	°	ft	ft ²	ft ²	lb
PTP 400	C	From Face	1.00	0.0000	142.00	No Ice	1.75	0.48	12.10
			0.00			1/2" Ice	1.92	0.58	23.53
			0.00			1" Ice	2.09	0.68	34.96
3"x4.5' Pipe	C	From Face	1.00	0.0000	140.00	No Ice	1.30	1.30	34.00
			0.00			1/2" Ice	1.57	1.57	45.51
			0.00			1" Ice	1.84	1.84	57.02
Pirod 13' Platform w/ Handrail (Verizon)	C	None		0.0000	106.00	No Ice	31.30	31.30	1822.00
						1/2" Ice	40.20	40.20	2452.00
						1" Ice	49.10	49.10	3082.00
SBNHH-1D65A (Verizon)	A	From Face	4.00	0.0000	106.00	No Ice	5.86	3.86	33.50
			0.00			1/2" Ice	6.23	4.22	72.43
			0.00			1" Ice	6.60	4.57	116.35
SBNHH-1D65A (Verizon)	B	From Face	4.00	0.0000	106.00	No Ice	5.86	3.86	33.50
			0.00			1/2" Ice	6.23	4.22	72.43
			0.00			1" Ice	6.60	4.57	116.35
SBNHH-1D65A (Verizon)	C	From Face	4.00	0.0000	106.00	No Ice	5.86	3.86	33.50
			0.00			1/2" Ice	6.23	4.22	72.43
			0.00			1" Ice	6.60	4.57	116.35
BXA-70063-6CF-EDIN-X (Verizon)	A	From Face	4.00	0.0000	106.00	No Ice	14.41	5.72	38.00
			0.00			1/2" Ice	14.92	6.17	120.76
			0.00			1" Ice	15.44	6.63	210.38
BXA-80063-4BF W/ Mount Pipe (Verizon)	B	From Face	4.00	0.0000	106.00	No Ice	4.96	3.44	28.25
			0.00			1/2" Ice	5.34	4.04	69.36
			0.00			1" Ice	5.72	4.64	110.47
BXA-80063-4BF W/ Mount Pipe (Verizon)	C	From Face	4.00	0.0000	106.00	No Ice	4.96	3.44	28.25
			0.00			1/2" Ice	5.34	4.04	69.36
			0.00			1" Ice	5.72	4.64	110.47
SLCP 2x6014 (Verizon)	A	From Face	4.00	0.0000	106.00	No Ice	6.48	5.28	20.00
			0.00			1/2" Ice	6.84	5.62	70.49
			0.00			1" Ice	7.21	5.98	126.23
SLCP 2x6014 (Verizon)	B	From Face	4.00	0.0000	106.00	No Ice	6.48	5.28	20.00
			0.00			1/2" Ice	6.84	5.62	70.49
			0.00			1" Ice	7.21	5.98	126.23
SLCP 2x6014 (Verizon)	C	From Face	4.00	0.0000	106.00	No Ice	6.48	5.28	20.00
			0.00			1/2" Ice	6.84	5.62	70.49
			0.00			1" Ice	7.21	5.98	126.23
B13 RRH4x30 (Verizon)	A	From Face	3.00	0.0000	106.00	No Ice	2.06	1.32	55.60
			0.00			1/2" Ice	2.24	1.48	72.88
			0.00			1" Ice	2.43	1.64	92.95
B13 RRH4x30 (Verizon)	B	From Face	3.00	0.0000	106.00	No Ice	2.06	1.32	55.60
			0.00			1/2" Ice	2.24	1.48	72.88
			0.00			1" Ice	2.43	1.64	92.95
B13 RRH4x30 (Verizon)	C	From Face	3.00	0.0000	106.00	No Ice	2.06	1.32	55.60
			0.00			1/2" Ice	2.24	1.48	72.88
			0.00			1" Ice	2.43	1.64	92.95
B4 RRH 2x60-4R (Verizon)	A	From Face	3.00	0.0000	106.00	No Ice	3.50	2.10	60.00
			0.00			1/2" Ice	3.76	2.34	84.31
			0.00			1" Ice	4.02	2.58	108.62
B4 RRH 2x60-4R (Verizon)	B	From Face	3.00	0.0000	106.00	No Ice	3.50	2.10	60.00
			0.00			1/2" Ice	3.76	2.34	84.31
			0.00			1" Ice	4.02	2.58	108.62
B4 RRH 2x60-4R (Verizon)	C	From Face	3.00	0.0000	106.00	No Ice	3.50	2.10	60.00
			0.00			1/2" Ice	3.76	2.34	84.31
			0.00			1" Ice	4.02	2.58	108.62
DB-T1-6Z-8ZB-0Z (Verizon)	A	From Face	2.00	0.0000	106.00	No Ice	4.80	2.00	44.00
			0.00			1/2" Ice	5.07	2.19	80.13
			0.00			1" Ice	5.34	2.38	116.26

tnxTower Maser Consulting PA 400 Valley Road Mt. Arlington, NJ Phone: 973.398.3110 FAX: 973.398.3199	Job						Page		
	17924009A						6 of 21		
	Project						Date		
Bloomfield Police Department						08:49:01 04/19/18			
Client						Designed by			
Sprint						abassett			

Description	Face or Leg	Offset Type	Offsets:		Azimuth Adjustment	Placement	C _{AA} Front	C _{AA} Side	Weight
			Horz	Vert					
			ft	ft	°	ft	ft ²	ft ²	lb
DB-T1-6Z-8ZB-0Z (Verizon)	B	From Face	2.00	0.0000	106.00	No Ice	4.80	2.00	44.00
			0.00			1/2" Ice	5.07	2.19	80.13
			0.00			1" Ice	5.34	2.38	116.26
Pirod 13' Platform w/ Handrail	A	None		0.0000	95.00	No Ice	31.30	31.30	1822.00
						1/2" Ice	40.20	40.20	2452.00
						1" Ice	49.10	49.10	3082.00
PTP 400	A	From Face	1.00	0.0000	83.00	No Ice	1.75	0.48	12.10
			0.00			1/2" Ice	1.92	0.58	23.53
			0.00			1" Ice	2.09	0.68	34.96
3"x4.5' Pipe	A	From Face	1.00	0.0000	83.00	No Ice	1.30	1.30	34.00
			0.00			1/2" Ice	1.57	1.57	45.51
			0.00			1" Ice	1.84	1.84	57.02
PTP 400	B	From Face	1.00	0.0000	83.00	No Ice	1.75	0.48	12.10
			0.00			1/2" Ice	1.92	0.58	23.53
			0.00			1" Ice	2.09	0.68	34.96
3"x4.5' Pipe	B	From Face	1.00	0.0000	83.00	No Ice	1.30	1.30	34.00
			0.00			1/2" Ice	1.57	1.57	45.51
			0.00			1" Ice	1.84	1.84	57.02
PTP 400	C	From Face	1.00	0.0000	83.00	No Ice	1.75	0.48	12.10
			0.00			1/2" Ice	1.92	0.58	23.53
			0.00			1" Ice	2.09	0.68	34.96
3"x4.5' Pipe	C	From Face	1.00	0.0000	83.00	No Ice	1.30	1.30	34.00
			0.00			1/2" Ice	1.57	1.57	45.51
			0.00			1" Ice	1.84	1.84	57.02
(2) Ericsson AIR21 with 6' pipe (T-Mobile)	A	From Face	4.00	0.0000	138.00	No Ice	6.75	6.08	127.70
			0.00			1/2" Ice	7.23	6.93	188.97
			0.00			1" Ice	7.70	7.66	257.14
(2) Ericsson AIR21 with 6' pipe (T-Mobile)	B	From Face	4.00	0.0000	138.00	No Ice	6.75	6.08	127.70
			0.00			1/2" Ice	7.23	6.93	188.97
			0.00			1" Ice	7.70	7.66	257.14
(2) Ericsson AIR21 with 6' pipe (T-Mobile)	C	From Face	4.00	0.0000	138.00	No Ice	6.75	6.08	127.70
			0.00			1/2" Ice	7.23	6.93	188.97
			0.00			1" Ice	7.70	7.66	257.14
LNX-6515DS-VTM (T-Mobile)	A	From Face	4.00	0.0000	138.00	No Ice	11.45	9.60	79.50
			0.00			1/2" Ice	12.06	11.02	166.47
			0.00			1" Ice	12.69	12.29	263.19
LNX-6515DS-VTM (T-Mobile)	B	From Face	4.00	0.0000	138.00	No Ice	11.45	9.60	79.50
			0.00			1/2" Ice	12.06	11.02	166.47
			0.00			1" Ice	12.69	12.29	263.19
LNX-6515DS-VTM (T-Mobile)	C	From Face	4.00	0.0000	138.00	No Ice	11.45	9.60	79.50
			0.00			1/2" Ice	12.06	11.02	166.47
			0.00			1" Ice	12.69	12.29	263.19
KRY 112 71 (T-Mobile)	A	From Face	4.00	0.0000	138.00	No Ice	0.58	0.40	14.10
			0.00			1/2" Ice	0.69	0.49	19.28
			0.00			1" Ice	0.80	0.59	26.06
KRY 112 71 (T-Mobile)	B	From Face	4.00	0.0000	138.00	No Ice	0.58	0.40	14.10
			0.00			1/2" Ice	0.69	0.49	19.28
			0.00			1" Ice	0.80	0.59	26.06
KRY 112 71 (T-Mobile)	C	From Face	4.00	0.0000	138.00	No Ice	0.58	0.40	14.10
			0.00			1/2" Ice	0.69	0.49	19.28
			0.00			1" Ice	0.80	0.59	26.06
RRUS-11 (T-Mobile)	A	From Face	4.00	0.0000	138.00	No Ice	2.52	1.02	55.00
			0.00			1/2" Ice	2.72	1.16	74.32
			0.00			1" Ice	2.92	1.30	96.56
RRUS-11 (T-Mobile)	B	From Face	4.00	0.0000	138.00	No Ice	2.52	1.02	55.00
			0.00			1/2" Ice	2.72	1.16	74.32
			0.00			1" Ice	2.92	1.30	96.56

tnxTower Maser Consulting PA 400 Valley Road Mt. Arlington, NJ Phone: 973.398.3110 FAX: 973.398.3199	Job		17924009A		Page		7 of 21	
	Project		Bloomfield Police Department		Date		08:49:01 04/19/18	
	Client		Sprint		Designed by		abassett	

Description	Face or Leg	Offset Type	Offsets:		Azimuth Adjustment	Placement	C _{AA}		Weight
			Horz	Vert			Front	Side	
			ft	ft	°	ft	ft ²	ft ²	lb
RRUS-11 (T-Mobile)	C	From Face	4.00	0.0000	138.00	No Ice	2.52	1.02	55.00
			0.00			1/2" Ice	2.72	1.16	74.32
			0.00			1" Ice	2.92	1.30	96.56
Pirod 13' Platform w/ Handrail	A	None		0.0000	138.00	No Ice	31.30	31.30	1822.00
						1/2" Ice	40.20	40.20	2452.00
						1" Ice	49.10	49.10	3082.00
Valmont Light Duty Tri-Bracket (Sprint)	C	None		0.0000	115.00	No Ice	1.76	1.76	54.00
						1/2" Ice	2.08	2.08	70.00
						1" Ice	2.40	2.40	86.00
Dual Standoff Mount (Sprint)	A	From Face	1.50	0.0000	115.00	No Ice	1.40	0.95	130.00
			0.00			1/2" Ice	1.69	1.15	192.44
			0.00			1" Ice	1.98	1.35	254.88
Dual Standoff Mount (Sprint)	B	From Face	1.50	0.0000	115.00	No Ice	1.40	0.95	130.00
			0.00			1/2" Ice	1.69	1.15	192.44
			0.00			1" Ice	1.98	1.35	254.88
Dual Standoff Mount (Sprint)	C	From Face	1.50	0.0000	115.00	No Ice	1.40	0.95	130.00
			0.00			1/2" Ice	1.69	1.15	192.44
			0.00			1" Ice	1.98	1.35	254.88
NNVV-65B-R4 (Sprint)	A	From Face	2.00	0.0000	115.00	No Ice	12.75	7.65	121.60
			0.00			1/2" Ice	13.45	8.94	214.84
			0.00			1" Ice	14.12	10.07	316.80
NNVV-65B-R4 (Sprint)	B	From Face	2.00	0.0000	115.00	No Ice	12.75	7.65	121.60
			0.00			1/2" Ice	13.45	8.94	214.84
			0.00			1" Ice	14.12	10.07	316.80
NNVV-65B-R4 (Sprint)	C	From Face	2.00	0.0000	115.00	No Ice	12.75	7.65	121.60
			0.00			1/2" Ice	13.45	8.94	214.84
			0.00			1" Ice	14.12	10.07	316.80
(2) RRH-2X50-800 (Sprint)	A	From Face	2.00	0.0000	115.00	No Ice	1.73	1.33	69.10
			0.00			1/2" Ice	1.90	1.48	86.54
			0.00			1" Ice	2.07	1.64	106.69
(2) RRH-2X50-800 (Sprint)	B	From Face	2.00	0.0000	115.00	No Ice	1.73	1.33	69.10
			0.00			1/2" Ice	1.90	1.48	86.54
			0.00			1" Ice	2.07	1.64	106.69
(2) RRH-2X50-800 (Sprint)	C	From Face	2.00	0.0000	115.00	No Ice	1.73	1.33	69.10
			0.00			1/2" Ice	1.90	1.48	86.54
			0.00			1" Ice	2.07	1.64	106.69
ALU RRH-4X45-1900 (Sprint)	A	From Face	1.50	0.0000	115.00	No Ice	2.50	2.50	69.50
			0.00			1/2" Ice	2.71	2.71	95.23
			0.00			1" Ice	2.93	2.93	124.33
ALU RRH-4X45-1900 (Sprint)	B	From Face	1.50	0.0000	115.00	No Ice	2.50	2.50	69.50
			0.00			1/2" Ice	2.71	2.71	95.23
			0.00			1" Ice	2.93	2.93	124.33
ALU RRH-4X45-1900 (Sprint)	C	From Face	1.50	0.0000	115.00	No Ice	2.50	2.50	69.50
			0.00			1/2" Ice	2.71	2.71	95.23
			0.00			1" Ice	2.93	2.93	124.33
AAHC (Sprint)	A	From Face	2.00	0.0000	115.00	No Ice	4.20	2.07	103.70
			0.00			1/2" Ice	4.46	2.26	136.02
			0.00			1" Ice	4.72	2.47	172.10
AAHC (Sprint)	B	From Face	2.00	0.0000	115.00	No Ice	4.20	2.07	103.70
			0.00			1/2" Ice	4.46	2.26	136.02
			0.00			1" Ice	4.72	2.47	172.10
AAHC (Sprint)	C	From Face	2.00	0.0000	115.00	No Ice	4.20	2.07	103.70
			0.00			1/2" Ice	4.46	2.26	136.02
			0.00			1" Ice	4.72	2.47	172.10

tnxTower Maser Consulting PA 400 Valley Road Mt. Arlington, NJ Phone: 973.398.3110 FAX: 973.398.3199	Job 17924009A	Page 8 of 21
	Project Bloomfield Police Department	Date 08:49:01 04/19/18
	Client Sprint	Designed by abassett

Tower Pressures - No Ice

$$G_H = 1.100$$

Section Elevation <i>ft</i>	<i>z</i> <i>ft</i>	K_Z	q_z <i>psf</i>	A_G <i>ft</i> ²	F a c e	A_F <i>ft</i> ²	A_R <i>ft</i> ²	A_{leg} <i>ft</i> ²	Leg %	C_{AA} In Face <i>ft</i> ²	C_{AA} Out Face <i>ft</i> ²
L1 136.00-87.25	110.84	1.018	24	110.761	A	0.000	110.761	110.761	100.00	9.652	0.000
					B	0.000	110.761	100.00	7.425	0.000	
					C	0.000	110.761	100.00	91.826	0.000	
L2 87.25-46.25	66.54	0.88	20	116.460	A	0.000	116.460	116.460	100.00	8.118	0.000
					B	0.000	116.460	100.00	16.236	0.000	
					C	0.000	116.460	100.00	98.810	0.000	
L3 46.25-0.00	22.65	0.7	17	155.407	A	0.000	155.407	155.407	100.00	8.366	0.000
					B	0.000	155.407	100.00	16.731	0.000	
					C	0.000	155.407	100.00	101.823	0.000	

Tower Pressure - With Ice

$$G_H = 1.100$$

Section Elevation <i>ft</i>	<i>z</i> <i>ft</i>	K_Z	q_z <i>psf</i>	t_z <i>in</i>	A_G <i>ft</i> ²	F a c e	A_F <i>ft</i> ²	A_R <i>ft</i> ²	A_{leg} <i>ft</i> ²	Leg %	C_{AA} In Face <i>ft</i> ²	C_{AA} Out Face <i>ft</i> ²
L1 136.00-87.25	110.84	1.018	4	2.2576	129.104	A	0.000	129.104	129.104	100.00	31.664	0.000
						B	0.000	129.104	100.00	19.864	0.000	
						C	0.000	129.104	100.00	173.621	0.000	
L2 87.25-46.25	66.54	0.88	3	2.1453	131.887	A	0.000	131.887	131.887	100.00	26.630	0.000
						B	0.000	131.887	100.00	43.435	0.000	
						C	0.000	131.887	100.00	192.934	0.000	
L3 46.25-0.00	22.65	0.7	3	1.9261	171.944	A	0.000	171.944	171.944	100.00	26.493	0.000
						B	0.000	171.944	100.00	43.574	0.000	
						C	0.000	171.944	100.00	195.257	0.000	

Tower Pressure - Service

$$G_H = 1.100$$

Section Elevation <i>ft</i>	<i>z</i> <i>ft</i>	K_Z	q_z <i>psf</i>	A_G <i>ft</i> ²	F a c e	A_F <i>ft</i> ²	A_R <i>ft</i> ²	A_{leg} <i>ft</i> ²	Leg %	C_{AA} In Face <i>ft</i> ²	C_{AA} Out Face <i>ft</i> ²
L1 136.00-87.25	110.84	1.018	8	110.761	A	0.000	110.761	110.761	100.00	9.652	0.000
					B	0.000	110.761	100.00	7.425	0.000	
					C	0.000	110.761	100.00	91.826	0.000	
L2 87.25-46.25	66.54	0.88	7	116.460	A	0.000	116.460	116.460	100.00	8.118	0.000
					B	0.000	116.460	100.00	16.236	0.000	
					C	0.000	116.460	100.00	98.810	0.000	
L3 46.25-0.00	22.65	0.7	6	155.407	A	0.000	155.407	155.407	100.00	8.366	0.000
					B	0.000	155.407	100.00	16.731	0.000	
					C	0.000	155.407	100.00	101.823	0.000	

tnxTower Maser Consulting PA 400 Valley Road Mt. Arlington, NJ Phone: 973.398.3110 FAX: 973.398.3199	Job 17924009A	Page 9 of 21
	Project Bloomfield Police Department	Date 08:49:01 04/19/18
	Client Sprint	Designed by abassett

Section Elevation	z	K _Z	q _z	A _G	F _a	A _F	A _R	A _{leg}	Leg %	C _{AA} In Face	C _{AA} Out Face
ft	ft		psf	ft ²	c	ft ²	ft ²	ft ²		ft ²	ft ²
					C	0.000	155.407		100.00	101.823	0.000

Tower Forces - No Ice - Wind Normal To Face

Section Elevation	Add Weight	Self Weight	F _a	e	C _F	q _z	D _F	D _R	A _E	F	w	Ctrl. Face
ft	lb	lb	c			psf			ft ²	lb	plf	
L1 136.00-87.25	1620.89	2763.81	A	1	0.65	24	1	1	110.761	1878.36	38.53	C
			B	1	0.65		1	1	110.761			
			C	1	0.65		1	1	110.761			
L2 87.25-46.25	1865.50	6291.62	A	1	0.65	20	1	1	116.460	1703.34	41.54	C
			B	1	0.65		1	1	116.460			
			C	1	0.65		1	1	116.460			
L3 46.25-0.00	1922.38	11230.22	A	1	0.65	17	1	1	155.407	1852.81	40.06	C
			B	1	0.65		1	1	155.407			
			C	1	0.65		1	1	155.407			
Sum Weight:	5408.76	20285.65						OTM	363.51 kip-ft	5434.51		

Tower Forces - No Ice - Wind 60 To Face

Section Elevation	Add Weight	Self Weight	F _a	e	C _F	q _z	D _F	D _R	A _E	F	w	Ctrl. Face
ft	lb	lb	c			psf			ft ²	lb	plf	
L1 136.00-87.25	1620.89	2763.81	A	1	0.65	24	1	1	110.761	1878.36	38.53	C
			B	1	0.65		1	1	110.761			
			C	1	0.65		1	1	110.761			
L2 87.25-46.25	1865.50	6291.62	A	1	0.65	20	1	1	116.460	1703.34	41.54	C
			B	1	0.65		1	1	116.460			
			C	1	0.65		1	1	116.460			
L3 46.25-0.00	1922.38	11230.22	A	1	0.65	17	1	1	155.407	1852.81	40.06	C
			B	1	0.65		1	1	155.407			
			C	1	0.65		1	1	155.407			
Sum Weight:	5408.76	20285.65						OTM	363.51 kip-ft	5434.51		

Tower Forces - No Ice - Wind 90 To Face

Section Elevation	Add Weight	Self Weight	F _a	e	C _F	q _z	D _F	D _R	A _E	F	w	Ctrl. Face
ft	lb	lb	c			psf			ft ²	lb	plf	
L1 136.00-87.25	1620.89	2763.81	A	1	0.65	24	1	1	110.761	5863.48	120.28	C
			B	1	0.65		1	1	110.761			

tnxTower Maser Consulting PA 400 Valley Road Mt. Arlington, NJ Phone: 973.398.3110 FAX: 973.398.3199	Job 17924009A	Page 10 of 21
	Project Bloomfield Police Department	Date 08:49:01 04/19/18
	Client Sprint	Designed by abassett

Section Elevation ft	Add Weight lb	Self Weight lb	F a c e	e	C _F	q _z psf	D _F	D _R	A _E ft ²	F lb	w plf	Ctrl. Face
L2 87.25-46.25	1865.50	6291.62	C	1	1.2	20	1	1	110.761	5368.02	130.93	C
			A	1	0.65		1	1	116.460			
			B	1	0.65		1	1	116.460			
L3 46.25-0.00	1922.38	11230.22	C	1	1.2	17	1	1	116.460	5288.21	114.34	C
			A	1	0.65		1	1	155.407			
			B	1	0.65		1	1	155.407			
			C	1	1.2		1	1	155.407			
Sum Weight:	5408.76	20285.65						OTM	1126.90 kip-ft	16519.71		

Tower Forces - With Ice - Wind Normal To Face

Section Elevation ft	Add Weight lb	Self Weight lb	F a c e	e	C _F	q _z psf	D _F	D _R	A _E ft ²	F lb	w plf	Ctrl. Face
L1 136.00-87.25	5083.69	6718.04	A	1	1.2	4	1	1	129.104	1086.46	22.29	B
			B	1	1.2		1	1	129.104			
			C	1	1.2		1	1	129.104			
L2 87.25-46.25	5872.30	10168.96	A	1	1.2	3	1	1	131.887	989.87	24.14	A
			B	1	1.2		1	1	131.887			
			C	1	1.2		1	1	131.887			
L3 46.25-0.00	5790.74	15808.44	A	1	1.2	3	1	1	171.944	943.33	20.40	A
			B	1	1.2		1	1	171.944			
			C	1	1.2		1	1	171.944			
Sum Weight:	16746.73	32695.44						OTM	207.66 kip-ft	3019.65		

Tower Forces - With Ice - Wind 60 To Face

Section Elevation ft	Add Weight lb	Self Weight lb	F a c e	e	C _F	q _z psf	D _F	D _R	A _E ft ²	F lb	w plf	Ctrl. Face
L1 136.00-87.25	5083.69	6718.04	A	1	1.2	4	1	1	129.104	1086.46	22.29	C
			B	1	1.2		1	1	129.104			
			C	1	1.2		1	1	129.104			
L2 87.25-46.25	5872.30	10168.96	A	1	1.2	3	1	1	131.887	989.87	24.14	B
			B	1	1.2		1	1	131.887			
			C	1	1.2		1	1	131.887			
L3 46.25-0.00	5790.74	15808.44	A	1	1.2	3	1	1	171.944	943.33	20.40	B
			B	1	1.2		1	1	171.944			
			C	1	1.2		1	1	171.944			
Sum Weight:	16746.73	32695.44						OTM	207.66 kip-ft	3019.65		

tnxTower Maser Consulting PA 400 Valley Road Mt. Arlington, NJ Phone: 973.398.3110 FAX: 973.398.3199	Job 17924009A	Page 11 of 21
	Project Bloomfield Police Department	Date 08:49:01 04/19/18
	Client Sprint	Designed by abassett

Tower Forces - With Ice - Wind 90 To Face

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	q _z	D _F	D _R	A _E	F	w	Ctrl. Face
ft	lb	lb				psf			ft ²	lb	plf	
L1 136.00-87.25	5083.69	6718.04	A	1	1.2	4	1	1	129.104	1522.92	31.24	C
			B	1	1.2		1	1	129.104			
			C	1	1.2		1	1	129.104			
L2 87.25-46.25	5872.30	10168.96	A	1	1.2	3	1	1	131.887	1380.08	33.66	C
			B	1	1.2		1	1	131.887			
			C	1	1.2		1	1	131.887			
L3 46.25-0.00	5790.74	15808.44	A	1	1.2	3	1	1	171.944	1274.00	27.55	C
			B	1	1.2		1	1	171.944			
			C	1	1.2		1	1	171.944			
Sum Weight:	16746.73	32695.44						OTM	289.49 kip-ft	4177.01		

Tower Forces - Service - Wind Normal To Face

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	q _z	D _F	D _R	A _E	F	w	Ctrl. Face
ft	lb	lb				psf			ft ²	lb	plf	
L1 136.00-87.25	1620.89	2763.81	A	1	0.65	8	1	1	110.761	629.98	12.92	C
			B	1	0.65		1	1	110.761			
			C	1	0.65		1	1	110.761			
L2 87.25-46.25	1865.50	6291.62	A	1	0.65	7	1	1	116.460	571.28	13.93	C
			B	1	0.65		1	1	116.460			
			C	1	0.65		1	1	116.460			
L3 46.25-0.00	1922.38	11230.22	A	1	0.65	6	1	1	155.407	621.41	13.44	C
			B	1	0.65		1	1	155.407			
			C	1	0.65		1	1	155.407			
Sum Weight:	5408.76	20285.65						OTM	121.92 kip-ft	1822.66		

Tower Forces - Service - Wind 60 To Face

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	q _z	D _F	D _R	A _E	F	w	Ctrl. Face
ft	lb	lb				psf			ft ²	lb	plf	
L1 136.00-87.25	1620.89	2763.81	A	1	0.65	8	1	1	110.761	629.98	12.92	C
			B	1	0.65		1	1	110.761			
			C	1	0.65		1	1	110.761			
L2 87.25-46.25	1865.50	6291.62	A	1	0.65	7	1	1	116.460	571.28	13.93	C
			B	1	0.65		1	1	116.460			
			C	1	0.65		1	1	116.460			
L3 46.25-0.00	1922.38	11230.22	A	1	0.65	6	1	1	155.407	621.41	13.44	C
			B	1	0.65		1	1	155.407			
			C	1	0.65		1	1	155.407			

tnxTower Maser Consulting PA 400 Valley Road Mt. Arlington, NJ Phone: 973.398.3110 FAX: 973.398.3199	Job 17924009A	Page 12 of 21
	Project Bloomfield Police Department	Date 08:49:01 04/19/18
	Client Sprint	Designed by abassett

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	q _z psf	D _F	D _R	A _E ft ²	F lb	w plf	Ctrl. Face
Sum Weight:	5408.76	20285.65						OTM	121.92 kip-ft	1822.66		

Tower Forces - Service - Wind 90 To Face

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	q _z psf	D _F	D _R	A _E ft ²	F lb	w plf	Ctrl. Face
L1 136.00-87.25	1620.89	2763.81	A B C	1 1 1	0.65 0.65 1.2	8	1 1 1	1 1 1	110.761 110.761 110.761	1966.53	40.34	C
L2 87.25-46.25	1865.50	6291.62	A B C	1 1 1	0.65 0.65 1.2	7	1 1 1	1 1 1	116.460 116.460 116.460	1800.36	43.91	C
L3 46.25-0.00	1922.38	11230.22	A B C	1 1 1	0.65 0.65 1.2	6	1 1 1	1 1 1	155.407 155.407 155.407	1773.60	38.35	C
Sum Weight:	5408.76	20285.65						OTM	377.95 kip-ft	5540.49		

Force Totals

Load Case	Vertical Forces lb	Sum of Forces X lb	Sum of Forces Z lb	Sum of Overturning Moments, M _x kip-ft	Sum of Overturning Moments, M _z kip-ft	Sum of Torques kip-ft
Leg Weight	20285.65					
Bracing Weight	0.00					
Total Member Self-Weight	20285.65			2.29	-0.07	
Total Weight	35049.61			2.29	-0.07	
Wind 0 deg - No Ice		0.00	-12934.62	-1250.73	-0.07	-0.87
Wind 30 deg - No Ice		6467.31	-11201.71	-1082.86	-626.58	-0.94
Wind 60 deg - No Ice		11201.71	-6467.31	-624.22	-1085.21	-0.76
Wind 90 deg - No Ice		24019.82	0.00	2.29	-2016.47	6.48
Wind 120 deg - No Ice		11201.71	6467.31	628.80	-1085.21	0.11
Wind 150 deg - No Ice		6467.31	11201.71	1087.43	-626.58	0.57
Wind 180 deg - No Ice		0.00	12934.62	1255.30	-0.07	0.87
Wind 210 deg - No Ice		-6467.31	11201.71	1087.43	626.44	0.94
Wind 240 deg - No Ice		-11201.71	6467.31	628.80	1085.08	0.76
Wind 270 deg - No Ice		-24019.82	0.00	2.29	2016.34	-6.48
Wind 300 deg - No Ice		-11201.71	-6467.31	-624.22	1085.08	-0.11
Wind 330 deg - No Ice		-6467.31	-11201.71	-1082.86	626.44	-0.57
Member Ice	12409.79					
Total Weight Ice	79493.29			11.94	0.88	
Wind 0 deg - Ice		0.00	-3930.28	-358.07	0.88	-0.16
Wind 30 deg - Ice		1965.14	-3403.72	-308.50	-184.12	-0.12
Wind 60 deg - Ice		4338.55	-2504.86	-211.67	-386.44	-0.06
Wind 90 deg - Ice		6210.12	0.00	11.94	-530.22	1.41

tnxTower Maser Consulting PA 400 Valley Road Mt. Arlington, NJ Phone: 973.398.3110 FAX: 973.398.3199	Job 17924009A	Page 13 of 21
	Project Bloomfield Police Department	Date 08:49:01 04/19/18
	Client Sprint	Designed by abassett

Load Case	Vertical Forces lb	Sum of Forces X lb	Sum of Forces Z lb	Sum of Overturning Moments, M_x kip-ft	Sum of Overturning Moments, M_z kip-ft	Sum of Torques kip-ft
Wind 120 deg - Ice		4365.57	2520.46	235.92	-387.06	0.10
Wind 150 deg - Ice		1965.14	3403.72	332.38	-184.12	0.15
Wind 180 deg - Ice		0.00	3930.28	381.95	0.88	0.16
Wind 210 deg - Ice		-1965.14	3403.72	332.38	185.89	0.12
Wind 240 deg - Ice		-4338.55	2504.86	235.56	388.20	0.06
Wind 270 deg - Ice		-6210.12	0.00	11.94	531.99	-1.41
Wind 300 deg - Ice		-4365.57	-2520.46	-212.04	388.82	-0.10
Wind 330 deg - Ice		-1965.14	-3403.72	-308.50	185.89	-0.15
Total Weight	35049.61			2.29	-0.07	
Wind 0 deg - Service		0.00	-4338.10	-420.20	0.04	-0.29
Wind 30 deg - Service		2169.05	-3756.90	-363.90	-210.08	-0.32
Wind 60 deg - Service		3756.90	-2169.05	-210.08	-363.90	-0.25
Wind 90 deg - Service		8055.93	0.00	0.04	-676.23	-0.12
Wind 120 deg - Service		3756.90	2169.05	210.17	-363.90	0.04
Wind 150 deg - Service		2169.05	3756.90	363.99	-210.08	0.19
Wind 180 deg - Service		0.00	4338.10	420.29	0.04	0.29
Wind 210 deg - Service		-2169.05	3756.90	363.99	210.17	0.32
Wind 240 deg - Service		-3756.90	2169.05	210.17	363.99	0.25
Wind 270 deg - Service		-8055.93	0.00	0.04	676.32	0.12
Wind 300 deg - Service		-3756.90	-2169.05	-210.08	363.99	-0.04
Wind 330 deg - Service		-2169.05	-3756.90	-363.90	210.17	-0.19

Load Combinations

Comb. No.	Description
1	Dead Only
2	1.2 Dead+1.6 Wind 0 deg - No Ice
3	0.9 Dead+1.6 Wind 0 deg - No Ice
4	1.2 Dead+1.6 Wind 30 deg - No Ice
5	0.9 Dead+1.6 Wind 30 deg - No Ice
6	1.2 Dead+1.6 Wind 60 deg - No Ice
7	0.9 Dead+1.6 Wind 60 deg - No Ice
8	1.2 Dead+1.6 Wind 90 deg - No Ice
9	0.9 Dead+1.6 Wind 90 deg - No Ice
10	1.2 Dead+1.6 Wind 120 deg - No Ice
11	0.9 Dead+1.6 Wind 120 deg - No Ice
12	1.2 Dead+1.6 Wind 150 deg - No Ice
13	0.9 Dead+1.6 Wind 150 deg - No Ice
14	1.2 Dead+1.6 Wind 180 deg - No Ice
15	0.9 Dead+1.6 Wind 180 deg - No Ice
16	1.2 Dead+1.6 Wind 210 deg - No Ice
17	0.9 Dead+1.6 Wind 210 deg - No Ice
18	1.2 Dead+1.6 Wind 240 deg - No Ice
19	0.9 Dead+1.6 Wind 240 deg - No Ice
20	1.2 Dead+1.6 Wind 270 deg - No Ice
21	0.9 Dead+1.6 Wind 270 deg - No Ice
22	1.2 Dead+1.6 Wind 300 deg - No Ice
23	0.9 Dead+1.6 Wind 300 deg - No Ice
24	1.2 Dead+1.6 Wind 330 deg - No Ice
25	0.9 Dead+1.6 Wind 330 deg - No Ice
26	1.2 Dead+1.0 Ice+1.0 Temp
27	1.2 Dead+1.0 Wind 0 deg+1.0 Ice+1.0 Temp
28	1.2 Dead+1.0 Wind 30 deg+1.0 Ice+1.0 Temp
29	1.2 Dead+1.0 Wind 60 deg+1.0 Ice+1.0 Temp
30	1.2 Dead+1.0 Wind 90 deg+1.0 Ice+1.0 Temp

tnxTower Maser Consulting PA 400 Valley Road Mt. Arlington, NJ Phone: 973.398.3110 FAX: 973.398.3199	Job 17924009A	Page 14 of 21
	Project Bloomfield Police Department	Date 08:49:01 04/19/18
	Client Sprint	Designed by abassett

Comb. No.	Description
31	1.2 Dead+1.0 Wind 120 deg+1.0 Ice+1.0 Temp
32	1.2 Dead+1.0 Wind 150 deg+1.0 Ice+1.0 Temp
33	1.2 Dead+1.0 Wind 180 deg+1.0 Ice+1.0 Temp
34	1.2 Dead+1.0 Wind 210 deg+1.0 Ice+1.0 Temp
35	1.2 Dead+1.0 Wind 240 deg+1.0 Ice+1.0 Temp
36	1.2 Dead+1.0 Wind 270 deg+1.0 Ice+1.0 Temp
37	1.2 Dead+1.0 Wind 300 deg+1.0 Ice+1.0 Temp
38	1.2 Dead+1.0 Wind 330 deg+1.0 Ice+1.0 Temp
39	Dead+Wind 0 deg - Service
40	Dead+Wind 30 deg - Service
41	Dead+Wind 60 deg - Service
42	Dead+Wind 90 deg - Service
43	Dead+Wind 120 deg - Service
44	Dead+Wind 150 deg - Service
45	Dead+Wind 180 deg - Service
46	Dead+Wind 210 deg - Service
47	Dead+Wind 240 deg - Service
48	Dead+Wind 270 deg - Service
49	Dead+Wind 300 deg - Service
50	Dead+Wind 330 deg - Service

Maximum Member Forces

Section No.	Elevation ft	Component Type	Condition	Gov. Load Comb.	Axial lb	Major Axis Moment kip-ft	Minor Axis Moment kip-ft
L1	136 - 87.25	Pole	Max Tension	26	0.00	-0.00	0.00
			Max. Compression	26	-43056.61	1.56	-3.33
			Max. Mx	20	-13974.37	552.18	-0.71
			Max. My	14	-14941.04	0.02	-416.62
			Max. Vy	20	-21608.19	552.18	-0.71
			Max. Vx	14	15404.12	0.02	-416.62
			Max. Torque	8			-2.73
L2	87.25 - 46.25	Pole	Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-60604.94	1.46	-8.19
			Max. Mx	20	-23633.77	1599.66	-1.63
			Max. My	14	-24549.69	-0.01	-1099.38
			Max. Vy	8	30193.65	-1599.65	-1.63
			Max. Vx	14	18233.93	-0.01	-1099.38
			Max. Torque	8			-6.26
L3	46.25 - 0	Pole	Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-87351.68	1.16	-14.05
			Max. Mx	8	-42009.88	-3358.53	-2.81
			Max. My	14	-42042.81	-0.09	-2097.87
			Max. Vy	8	38485.98	-3358.53	-2.81
			Max. Vx	14	20729.35	-0.09	-2097.87
			Max. Torque	8			-10.32

Maximum Reactions

Location	Condition	Gov. Load Comb.	Vertical lb	Horizontal, X lb	Horizontal, Z lb
Pole	Max. Vert	36	87351.68	6210.14	-0.00
	Max. H _x	21	31544.65	38431.71	-0.00

tnxTower Maser Consulting PA 400 Valley Road Mt. Arlington, NJ Phone: 973.398.3110 FAX: 973.398.3199	Job	17924009A	Page	15 of 21
	Project	Bloomfield Police Department	Date	08:49:01 04/19/18
	Client	Sprint	Designed by	abassett

Location	Condition	Gov. Load Comb.	Vertical lb	Horizontal, X lb	Horizontal, Z lb
	Max. H _z	2	42059.53	0.00	20695.40
	Max. M _x	2	2092.12	0.00	20695.40
	Max. M _z	8	3358.53	-38431.71	-0.00
	Max. Torsion	20	10.32	38431.71	-0.00
	Min. Vert	5	31544.65	-10347.70	17922.74
	Min. H _x	9	31544.65	-38431.71	-0.00
	Min. H _z	14	42059.53	0.00	-20695.40
	Min. M _x	14	-2097.87	0.00	-20695.40
	Min. M _z	20	-3358.36	38431.71	-0.00
	Min. Torsion	8	-10.32	-38431.71	-0.00

Tower Mast Reaction Summary

Load Combination	Vertical lb	Shear _x lb	Shear _z lb	Overturning Moment, M _x kip-ft	Overturning Moment, M _z kip-ft	Torque kip-ft
Dead Only	35049.61	0.00	0.00	2.30	-0.07	0.00
1.2 Dead+1.6 Wind 0 deg - No Ice	42059.53	-0.00	-20695.40	-2092.12	-0.09	-1.38
0.9 Dead+1.6 Wind 0 deg - No Ice	31544.65	-0.00	-20695.40	-2068.93	-0.07	-1.38
1.2 Dead+1.6 Wind 30 deg - No Ice	42059.53	10347.70	-17922.74	-1811.44	-1047.59	-1.48
0.9 Dead+1.6 Wind 30 deg - No Ice	31544.65	10347.70	-17922.74	-1791.45	-1035.60	-1.49
1.2 Dead+1.6 Wind 60 deg - No Ice	42059.53	17922.74	-10347.70	-1044.61	-1814.41	-1.19
0.9 Dead+1.6 Wind 60 deg - No Ice	31544.65	17922.74	-10347.70	-1033.39	-1793.65	-1.19
1.2 Dead+1.6 Wind 90 deg - No Ice	42059.53	38431.71	0.00	2.81	-3358.53	10.32
0.9 Dead+1.6 Wind 90 deg - No Ice	31544.65	38431.71	0.00	2.08	-3322.70	10.31
1.2 Dead+1.6 Wind 120 deg - No Ice	42059.53	17922.74	10347.70	1050.38	-1814.40	0.20
0.9 Dead+1.6 Wind 120 deg - No Ice	31544.65	17922.74	10347.70	1037.66	-1793.65	0.19
1.2 Dead+1.6 Wind 150 deg - No Ice	42059.53	10347.70	17922.74	1817.19	-1047.58	0.91
0.9 Dead+1.6 Wind 150 deg - No Ice	31544.65	10347.70	17922.74	1795.71	-1035.59	0.91
1.2 Dead+1.6 Wind 180 deg - No Ice	42059.53	-0.00	20695.40	2097.87	-0.09	1.38
0.9 Dead+1.6 Wind 180 deg - No Ice	31544.65	-0.00	20695.40	2073.18	-0.07	1.38
1.2 Dead+1.6 Wind 210 deg - No Ice	42059.53	-10347.70	17922.74	1817.20	1047.40	1.48
0.9 Dead+1.6 Wind 210 deg - No Ice	31544.65	-10347.70	17922.74	1795.72	1035.46	1.49
1.2 Dead+1.6 Wind 240 deg - No Ice	42059.53	-17922.74	10347.70	1050.38	1814.23	1.19
0.9 Dead+1.6 Wind 240 deg - No Ice	31544.65	-17922.74	10347.70	1037.67	1793.52	1.19
1.2 Dead+1.6 Wind 270 deg - No Ice	42059.53	-38431.71	0.00	2.81	3358.36	-10.32
0.9 Dead+1.6 Wind 270 deg - No Ice	31544.65	-38431.71	0.00	2.08	3322.58	-10.31

tnxTower Maser Consulting PA 400 Valley Road Mt. Arlington, NJ Phone: 973.398.3110 FAX: 973.398.3199	Job 17924009A	Page 16 of 21
	Project Bloomfield Police Department	Date 08:49:01 04/19/18
	Client Sprint	Designed by abassett

Load Combination	Vertical lb	Shear _x lb	Shear _z lb	Overturning Moment, M _x kip-ft	Overturning Moment, M _z kip-ft	Torque kip-ft
1.2 Dead+1.6 Wind 300 deg - No Ice	42059.53	-17922.74	-10347.70	-1044.62	1814.24	-0.20
0.9 Dead+1.6 Wind 300 deg - No Ice	31544.65	-17922.74	-10347.70	-1033.40	1793.53	-0.19
1.2 Dead+1.6 Wind 330 deg - No Ice	42059.53	-10347.70	-17922.74	-1811.45	1047.41	-0.91
0.9 Dead+1.6 Wind 330 deg - No Ice	31544.65	-10347.70	-17922.74	-1791.46	1035.46	-0.91
1.2 Dead+1.0 Ice+1.0 Temp	87351.68	-0.01	0.03	14.05	1.16	-0.00
1.2 Dead+1.0 Wind 0 deg+1.0 Ice+1.0 Temp	87351.68	-0.00	-3930.30	-403.18	1.16	-0.15
1.2 Dead+1.0 Wind 30 deg+1.0 Ice+1.0 Temp	87351.68	1965.15	-3403.74	-347.27	-207.50	-0.11
1.2 Dead+1.0 Wind 60 deg+1.0 Ice+1.0 Temp	87351.68	4338.57	-2504.87	-237.26	-434.27	-0.04
1.2 Dead+1.0 Wind 90 deg+1.0 Ice+1.0 Temp	87351.68	6210.14	0.00	14.14	-594.36	1.43
1.2 Dead+1.0 Wind 120 deg+1.0 Ice+1.0 Temp	87351.68	4365.58	2520.47	265.89	-434.87	0.11
1.2 Dead+1.0 Wind 150 deg+1.0 Ice+1.0 Temp	87351.68	1965.15	3403.74	375.55	-207.50	0.15
1.2 Dead+1.0 Wind 180 deg+1.0 Ice+1.0 Temp	87351.68	-0.00	3930.30	431.46	1.16	0.15
1.2 Dead+1.0 Wind 210 deg+1.0 Ice+1.0 Temp	87351.68	-1965.15	3403.74	375.55	209.82	0.11
1.2 Dead+1.0 Wind 240 deg+1.0 Ice+1.0 Temp	87351.68	-4338.57	2504.87	265.54	436.60	0.04
1.2 Dead+1.0 Wind 270 deg+1.0 Ice+1.0 Temp	87351.68	-6210.14	0.00	14.14	596.69	-1.43
1.2 Dead+1.0 Wind 300 deg+1.0 Ice+1.0 Temp	87351.68	-4365.58	-2520.47	-237.61	437.20	-0.11
1.2 Dead+1.0 Wind 330 deg+1.0 Ice+1.0 Temp	87351.68	-1965.15	-3403.74	-347.27	209.82	-0.15
Dead+Wind 0 deg - Service	35049.61	-0.00	-4338.10	-433.80	-0.07	-0.29
Dead+Wind 30 deg - Service	35049.61	2169.05	-3756.90	-375.36	-218.16	-0.31
Dead+Wind 60 deg - Service	35049.61	3756.90	-2169.05	-215.71	-377.82	-0.25
Dead+Wind 90 deg - Service	35049.61	8055.93	-0.00	2.38	-700.28	-0.12
Dead+Wind 120 deg - Service	35049.61	3756.90	2169.05	220.48	-377.82	0.04
Dead+Wind 150 deg - Service	35049.61	2169.05	3756.90	380.13	-218.16	0.19
Dead+Wind 180 deg - Service	35049.61	-0.00	4338.10	438.57	-0.07	0.29
Dead+Wind 210 deg - Service	35049.61	-2169.05	3756.90	380.13	218.02	0.31
Dead+Wind 240 deg - Service	35049.61	-3756.90	2169.05	220.48	377.68	0.25
Dead+Wind 270 deg - Service	35049.61	-8055.93	-0.00	2.38	700.14	0.12
Dead+Wind 300 deg - Service	35049.61	-3756.90	-2169.05	-215.71	377.68	-0.04
Dead+Wind 330 deg - Service	35049.61	-2169.05	-3756.90	-375.37	218.02	-0.19

Solution Summary

Load Comb.	Sum of Applied Forces			Sum of Reactions			% Error
	PX lb	PY lb	PZ lb	PX lb	PY lb	PZ lb	
1	0.00	-35049.61	0.00	0.00	35049.61	-0.00	0.000%
2	0.00	-42059.53	-20695.40	0.00	42059.53	20695.40	0.000%
3	0.00	-31544.65	-20695.40	0.00	31544.65	20695.40	0.000%
4	10347.70	-42059.53	-17922.74	-10347.70	42059.53	17922.74	0.000%
5	10347.70	-31544.65	-17922.74	-10347.70	31544.65	17922.74	0.000%
6	17922.74	-42059.53	-10347.70	-17922.74	42059.53	10347.70	0.000%
7	17922.74	-31544.65	-10347.70	-17922.74	31544.65	10347.70	0.000%

tnxTower Maser Consulting PA 400 Valley Road Mt. Arlington, NJ Phone: 973398.3110 FAX: 973.398.3199	Job	17924009A	Page	17 of 21
	Project	Bloomfield Police Department	Date	08:49:01 04/19/18
	Client	Sprint	Designed by	abassett

Load Comb.	Sum of Applied Forces			Sum of Reactions			% Error
	PX lb	PY lb	PZ lb	PX lb	PY lb	PZ lb	
8	38431.71	-42059.53	0.00	-38431.71	42059.53	-0.00	0.000%
9	38431.71	-31544.65	0.00	-38431.71	31544.65	-0.00	0.000%
10	17922.74	-42059.53	10347.70	-17922.74	42059.53	-10347.70	0.000%
11	17922.74	-31544.65	10347.70	-17922.74	31544.65	-10347.70	0.000%
12	10347.70	-42059.53	17922.74	-10347.70	42059.53	-17922.74	0.000%
13	10347.70	-31544.65	17922.74	-10347.70	31544.65	-17922.74	0.000%
14	0.00	-42059.53	20695.40	0.00	42059.53	-20695.40	0.000%
15	0.00	-31544.65	20695.40	0.00	31544.65	-20695.40	0.000%
16	-10347.70	-42059.53	17922.74	10347.70	42059.53	-17922.74	0.000%
17	-10347.70	-31544.65	17922.74	10347.70	31544.65	-17922.74	0.000%
18	-17922.74	-42059.53	10347.70	17922.74	42059.53	-10347.70	0.000%
19	-17922.74	-31544.65	10347.70	17922.74	31544.65	-10347.70	0.000%
20	-38431.71	-42059.53	0.00	38431.71	42059.53	-0.00	0.000%
21	-38431.71	-31544.65	0.00	38431.71	31544.65	-0.00	0.000%
22	-17922.74	-42059.53	-10347.70	17922.74	42059.53	10347.70	0.000%
23	-17922.74	-31544.65	-10347.70	17922.74	31544.65	10347.70	0.000%
24	-10347.70	-42059.53	-17922.74	10347.70	42059.53	17922.74	0.000%
25	-10347.70	-31544.65	-17922.74	10347.70	31544.65	17922.74	0.000%
26	0.00	-87351.68	0.00	0.01	87351.68	-0.03	0.000%
27	0.00	-87351.68	-3930.28	0.00	87351.68	3930.30	0.000%
28	1965.14	-87351.68	-3403.72	-1965.15	87351.68	3403.74	0.000%
29	4338.55	-87351.68	-2504.86	-4338.57	87351.68	2504.87	0.000%
30	6210.12	-87351.68	0.00	-6210.14	87351.68	-0.00	0.000%
31	4365.57	-87351.68	2520.46	-4365.58	87351.68	-2520.47	0.000%
32	1965.14	-87351.68	3403.72	-1965.15	87351.68	-3403.74	0.000%
33	0.00	-87351.68	3930.28	0.00	87351.68	-3930.30	0.000%
34	-1965.14	-87351.68	3403.72	1965.15	87351.68	-3403.74	0.000%
35	-4338.55	-87351.68	2504.86	4338.57	87351.68	-2504.87	0.000%
36	-6210.12	-87351.68	0.00	6210.14	87351.68	-0.00	0.000%
37	-4365.57	-87351.68	-2520.46	4365.58	87351.68	2520.47	0.000%
38	-1965.14	-87351.68	-3403.72	1965.15	87351.68	3403.74	0.000%
39	0.00	-35049.61	-4338.10	0.00	35049.61	4338.10	0.000%
40	2169.05	-35049.61	-3756.90	-2169.05	35049.61	3756.90	0.000%
41	3756.90	-35049.61	-2169.05	-3756.90	35049.61	2169.05	0.000%
42	8055.93	-35049.61	0.00	-8055.93	35049.61	0.00	0.000%
43	3756.90	-35049.61	2169.05	-3756.90	35049.61	-2169.05	0.000%
44	2169.05	-35049.61	3756.90	-2169.05	35049.61	-3756.90	0.000%
45	0.00	-35049.61	4338.10	0.00	35049.61	-4338.10	0.000%
46	-2169.05	-35049.61	3756.90	2169.05	35049.61	-3756.90	0.000%
47	-3756.90	-35049.61	2169.05	3756.90	35049.61	-2169.05	0.000%
48	-8055.93	-35049.61	0.00	8055.93	35049.61	0.00	0.000%
49	-3756.90	-35049.61	-2169.05	3756.90	35049.61	2169.05	0.000%
50	-2169.05	-35049.61	-3756.90	2169.05	35049.61	3756.90	0.000%

Non-Linear Convergence Results

Load Combination	Converged?	Number of Cycles	Displacement Tolerance	Force Tolerance
1	Yes	4	0.00000001	0.00000001
2	Yes	5	0.00000001	0.00003560
3	Yes	5	0.00000001	0.00001762
4	Yes	6	0.00000001	0.00002440
5	Yes	6	0.00000001	0.00000839
6	Yes	6	0.00000001	0.00002620
7	Yes	6	0.00000001	0.00000908
8	Yes	6	0.00000001	0.00000842

tnxTower Maser Consulting PA 400 Valley Road Mt. Arlington, NJ Phone: 973.398.3110 FAX: 973.398.3199	Job	17924009A	Page	18 of 21
	Project	Bloomfield Police Department	Date	08:49:01 04/19/18
	Client	Sprint	Designed by	abassett

9	Yes	5	0.0000001	0.00007417
10	Yes	6	0.0000001	0.00002574
11	Yes	6	0.0000001	0.00000888
12	Yes	6	0.0000001	0.00002483
13	Yes	6	0.0000001	0.00000854
14	Yes	5	0.0000001	0.00003569
15	Yes	5	0.0000001	0.00001765
16	Yes	6	0.0000001	0.00002662
17	Yes	6	0.0000001	0.00000922
18	Yes	6	0.0000001	0.00002477
19	Yes	6	0.0000001	0.00000851
20	Yes	6	0.0000001	0.00000842
21	Yes	5	0.0000001	0.00007417
22	Yes	6	0.0000001	0.00002515
23	Yes	6	0.0000001	0.00000868
24	Yes	6	0.0000001	0.00002611
25	Yes	6	0.0000001	0.00000904
26	Yes	4	0.0000001	0.00007196
27	Yes	6	0.0000001	0.00004012
28	Yes	6	0.0000001	0.00004407
29	Yes	6	0.0000001	0.00005367
30	Yes	6	0.0000001	0.00005649
31	Yes	6	0.0000001	0.00005677
32	Yes	6	0.0000001	0.00004725
33	Yes	6	0.0000001	0.00004327
34	Yes	6	0.0000001	0.00004787
35	Yes	6	0.0000001	0.00005738
36	Yes	6	0.0000001	0.00005711
37	Yes	6	0.0000001	0.00005418
38	Yes	6	0.0000001	0.00004467
39	Yes	4	0.0000001	0.00003567
40	Yes	4	0.0000001	0.00009244
41	Yes	5	0.0000001	0.00000535
42	Yes	4	0.0000001	0.00003303
43	Yes	5	0.0000001	0.00000502
44	Yes	4	0.0000001	0.00009635
45	Yes	4	0.0000001	0.00003614
46	Yes	5	0.0000001	0.00000570
47	Yes	4	0.0000001	0.00009645
48	Yes	4	0.0000001	0.00003304
49	Yes	4	0.0000001	0.00009873
50	Yes	5	0.0000001	0.00000527

Maximum Tower Deflections - Service Wind

Section No.	Elevation <i>ft</i>	Horz. Deflection <i>in</i>	Gov. Load Comb.	Tilt <i>°</i>	Twist <i>°</i>
L1	136 - 87.25	22.544	48	1.4072	0.0022
L2	91.25 - 46.25	10.489	42	1.0512	0.0014
L3	51 - 0	3.357	42	0.5949	0.0005

Critical Deflections and Radius of Curvature - Service Wind

tnxTower Maser Consulting PA 400 Valley Road Mt. Arlington, NJ Phone: 973.398.3110 FAX: 973.398.3199	Job 17924009A	Page 19 of 21
	Project Bloomfield Police Department	Date 08:49:01 04/19/18
	Client Sprint	Designed by abassett

Elevation	Appurtenance	Gov. Load Comb.	Deflection in	Tilt °	Twist °	Radius of Curvature ft
143.00	20' Dipole	48	22.544	1.4072	0.0022	42667
142.00	PTP 400	48	22.544	1.4072	0.0022	42667
140.00	3"x4.5' Pipe	48	22.544	1.4072	0.0022	42667
138.00	(2) Ericsson AIR21 with 6' pipe	48	22.544	1.4072	0.0022	42667
115.00	Valmont Light Duty Tri-Bracket	48	16.579	1.2552	0.0018	10158
106.00	Pirod 13' Platform w/ Handrail	42	14.152	1.1837	0.0016	7110
95.00	Pirod 13' Platform w/ Handrail	42	11.375	1.0871	0.0014	5203
83.00	PTP 400	42	8.663	0.9665	0.0012	4548

Maximum Tower Deflections - Design Wind

Section No.	Elevation ft	Horz. Deflection in	Gov. Load Comb.	Tilt °	Twist °
L1	136 - 87.25	108.133	20	6.7596	0.0464
L2	91.25 - 46.25	50.333	8	5.0491	0.0246
L3	51 - 0	16.109	8	2.8565	0.0126

Critical Deflections and Radius of Curvature - Design Wind

Elevation	Appurtenance	Gov. Load Comb.	Deflection in	Tilt °	Twist °	Radius of Curvature ft
143.00	20' Dipole	20	108.133	6.7596	0.0464	9092
142.00	PTP 400	20	108.133	6.7596	0.0464	9092
140.00	3"x4.5' Pipe	20	108.133	6.7596	0.0464	9092
138.00	(2) Ericsson AIR21 with 6' pipe	20	108.133	6.7596	0.0464	9092
115.00	Valmont Light Duty Tri-Bracket	20	79.537	6.0293	0.0354	2161
106.00	Pirod 13' Platform w/ Handrail	8	67.900	5.6859	0.0310	1510
95.00	Pirod 13' Platform w/ Handrail	8	54.585	5.2216	0.0262	1103
83.00	PTP 400	8	41.576	4.6422	0.0217	960

Base Plate Design Data

Plate Thickness	Number of Anchor Bolts	Anchor Bolt Size	Actual Allowable Ratio Bolt Tension lb	Actual Allowable Ratio Bolt Compression lb	Actual Allowable Ratio Plate Stress ksi	Actual Allowable Ratio Stiffener Stress ksi	Controlling Condition	Ratio
in		in						
3.0000	16	2.2500	198037.40	203288.63	33.906		Bolt T	0.89
			223654.40	371266.30	49.500			✓
			0.89	0.55	0.68			

tnxTower Maser Consulting PA 400 Valley Road Mt. Arlington, NJ Phone: 973.398.3110 FAX: 973.398.3199	Job 17924009A	Page 20 of 21
	Project Bloomfield Police Department	Date 08:49:01 04/19/18
	Client Sprint	Designed by abassett

Compression Checks

Pole Design Data

Section No.	Elevation ft	Size	L ft	L _u ft	Kl/r	A in ²	P _u lb	φP _n lb	Ratio $\frac{P_u}{\phi P_n}$
L1	136 - 87.25 (1)	TP30.7x23x0.1875	48.75	0.00	0.0	17.7828	-13974.40	1124710.00	0.012
L2	87.25 - 46.25 (2)	TP36.81x29.6932x0.375	45.00	0.00	0.0	42.4726	-23633.80	3155500.00	0.007
L3	46.25 - 0 (3)	TP43.36x35.3088x0.5	51.00	0.00	0.0	68.0188	-42009.90	5053460.00	0.008

Pole Bending Design Data

Section No.	Elevation ft	Size	M _{ux} kip-ft	φM _{ux} kip-ft	Ratio $\frac{M_{ux}}{\phi M_{ux}}$	M _{uy} kip-ft	φM _{uy} kip-ft	Ratio $\frac{M_{uy}}{\phi M_{uy}}$
L1	136 - 87.25 (1)	TP30.7x23x0.1875	552.18	692.16	0.798	0.00	692.16	0.000
L2	87.25 - 46.25 (2)	TP36.81x29.6932x0.375	1599.66	2309.36	0.693	0.00	2309.36	0.000
L3	46.25 - 0 (3)	TP43.36x35.3088x0.5	3358.53	4437.07	0.757	0.00	4437.07	0.000

Pole Shear Design Data

Section No.	Elevation ft	Size	Actual V _u lb	φV _n lb	Ratio $\frac{V_u}{\phi V_n}$	Actual T _u kip-ft	φT _n kip-ft	Ratio $\frac{T_u}{\phi T_n}$
L1	136 - 87.25 (1)	TP30.7x23x0.1875	21608.20	562353.00	0.038	2.69	1386.01	0.002
L2	87.25 - 46.25 (2)	TP36.81x29.6932x0.375	30193.60	1577750.00	0.019	6.26	4624.38	0.001
L3	46.25 - 0 (3)	TP43.36x35.3088x0.5	38486.00	2526730.00	0.015	10.32	8885.00	0.001

Pole Interaction Design Data

Section No.	Elevation ft	Ratio $\frac{P_u}{\phi P_n}$	Ratio $\frac{M_{ux}}{\phi M_{ux}}$	Ratio $\frac{M_{uy}}{\phi M_{uy}}$	Ratio $\frac{V_u}{\phi V_n}$	Ratio $\frac{T_u}{\phi T_n}$	Comb. Stress Ratio	Allow. Stress Ratio	Criteria
L1	136 - 87.25 (1)	0.012	0.798	0.000	0.038	0.002	0.812	1.000	4.8.2 ✓
L2	87.25 - 46.25 (2)	0.007	0.693	0.000	0.019	0.001	0.701	1.000	4.8.2 ✓
L3	46.25 - 0 (3)	0.008	0.757	0.000	0.015	0.001	0.766	1.000	4.8.2 ✓

tnxTower Maser Consulting PA 400 Valley Road Mt. Arlington, NJ Phone: 973398.3110 FAX: 973.398.3199	Job 17924009A	Page 21 of 21
	Project Bloomfield Police Department	Date 08:49:01 04/19/18
	Client Sprint	Designed by abassett

Section Capacity Table

Section No.	Elevation ft	Component Type	Size	Critical Element	P lb	ϕP_{allow} lb	% Capacity	Pass Fail	
L1	136 - 87.25	Pole	TP30.7x23x0.1875	1	-13974.40	1124710.00	81.2	Pass	
L2	87.25 - 46.25	Pole	TP36.81x29.6932x0.375	2	-23633.80	3155500.00	70.1	Pass	
L3	46.25 - 0	Pole	TP43.36x35.3088x0.5	3	-42009.90	5053460.00	76.6	Pass	
							Summary		
							Pole (L1)	81.2	Pass
							Base Plate	88.5	Pass
							RATING =	88.5	Pass

SITE ID: CT52XC024 SITE NAME: BLOOMFIELD POLICE DEPARTMENT

785 PARK AVENUE BLOOMFIELD, CT 06002

DO MACRO PROJECT

SITE INFORMATION

ADDRESS: 785 PARK AVENUE
BLOOMFIELD, CT 06002

JURISDICTION: TOWN OF BLOOMFIELD

COUNTY: HARTFORD

PROPERTY OWNER: TOWN OF BLOOMFIELD POLICE STATION
800 BLOOMFIELD AVENUE
BLOOMFIELD, CT 06002

APPLICANT: SPRINT
201 STATE ROUTE 17 NORTH
RUTHERFORD, NJ 07070

LATITUDE (NAD 83): N 41.8285°

LONGITUDE (NAD 83): W 72.733611°

CURRENT USE: UNMANNED TELECOMMUNICATIONS FACILITY

PROPOSED USE: NO CHANGE

UTILITY COMPANY: CONNECTICUT LIGHT AND POWER
PHONE: 800-266-2000

RF CONFIGURATION

THE CONTRACTOR SHALL OBTAIN THE LATEST RF DATA SHEET AND CONFIRM SAME WITH THE SPRINT CONSTRUCTION MANAGER PRIOR TO START OF CONSTRUCTION.

PROJECT CONTACTS

NAME:	COMPANY:	PHONE #:
ENGINEER: JEREMY MCKEON	MASER CONSULTING P.A.	973.398.3110
CONSTRUCTION: TOM JUPIN	CHERUNDOLO CONSULTING	973.819.9033

STRUCTURAL STATEMENT

THE PROPOSED ANTENNA AND EQUIPMENT INSTALLATION SHALL BE EVALUATED INCLUDING THE NEW LOAD CONDITIONS ON THE SUPPORTING ELEMENTS OF THE EXISTING STRUCTURE. THESE PLANS HAVE BEEN DEVELOPED FOR THE PROPOSED TELECOMMUNICATION FACILITY TO BE OWNED OR LEASED BY SPRINT IN ACCORDANCE WITH THE SCOPE OF WORK PROVIDED BY CHERUNDOLO CONSULTING. MASER HAS INCORPORATED THE SCOPE OF WORK WITHIN THESE PLANS. ELEMENTS OF THE STRUCTURE AFFECTED BY THE SCOPE OF WORK SHALL BE ANALYZED UNDER SEPARATE COVER. MASER ASSUMES NO RESPONSIBILITY FOR ANY ELEMENTS OF THE SITE NOT AFFECTED BY THE SCOPE OR FOR CHANGES TO THE SCOPE OF WORK NOT SPECIFICALLY SHOWN ON THESE DRAWINGS.

APPROVALS


THE FOLLOWING PARTIES HEREBY APPROVE AND ACCEPT THESE DOCUMENTS AND AUTHORIZE THE CONTRACTOR TO PROCEED WITH THE CONSTRUCTION DESCRIBED HEREIN. ALL DOCUMENTS ARE SUBJECT TO REVIEW BY THE LOCAL BUILDING DEPARTMENT AND MAY IMPOSE CHANGES OR MODIFICATIONS.

CONSTRUCTION: _____ DATE: _____

LEASING/SITE ACQUISITION: _____ DATE: _____

RF ENGINEERING: _____ DATE: _____

LANDLORD/PROPERTY OWNER: _____ DATE: _____



DRIVING DIRECTIONS

FROM SPRINT OFFICES, RUTHERFORD, NJ: TAKE VETERANS BLVD AND BOROUGH ST TO NJ-17 N. HEAD SOUTH, SLIGHT LEFT TOWARD VETERANS BLVD. TURN LEFT TOWARD VETERANS BLVD. TURN RIGHT TOWARD VETERANS BLVD. TURN LEFT ONTO VETERANS BLVD. TURN LEFT ONTO BOROUGH ST. FOLLOW NJ-17 N, GARDEN STATE PKWY AND I-87 S TO SAW MILL PKWY N/SAW MILL RIVER PKWY N IN ELMSFORD. TAKE EXIT 8A FROM I-87 S. TURN RIGHT ONTO NJ-17 N. TAKE THE GARDEN STATE PARKWAY N EXIT. MERGE ONTO GARDEN STATE PKWY, ENTERING NEW YORK. USE THE RIGHT 2 LANES TO TAKE EXIT 14-1 TO MERGE ONTO I-287 E/I-87 S. USE THE RIGHT LANE TO KEEP RIGHT AT THE FORK. CONTINUE ON I-87 S AND FOLLOW SIGNS FOR NEW YORK CITY/SAW MILL PKWY S. TAKE EXIT 8A FOR NY-119/SAW MILL PKWY N TOWARD ELMSFORD. KEEP LEFT. FOLLOW SIGNS FOR KATONAH/SAW MILL RIVER PKWY N AND MERGE ONTO SAW MILL PKWY N/SAW MILL RIVER PKWY N. GET ON I-684 N IN BEDFORD. MERGE ONTO SAW MILL PKWY N/SAW MILL RIVER PKWY N. KEEP LEFT, FOLLOW SIGNS FOR I-684/BREWSTER AND MERGE ONTO I-684 N. DRIVE FROM I-84 E TO WEST HARTFORD. TAKE EXIT 43 FROM I-84 E. MERGE ONTO I-684 N. TAKE EXIT 9E FOR INTERSTATE 84 E TOWARD DANBURY. MERGE ONTO I-84 E. ENTERING CONNECTICUT. KEEP RIGHT TO STAY ON I-84 E. KEEP RIGHT AT THE FORK TO STAY ON I-84 E. FOLLOW SIGNS FOR HARTFORD/INTERSTATE 84 E. USE THE LEFT LANE TO TAKE EXIT 43 TOWARD PARK RD/W HARTFORD CENTER. TAKE TROUT BROOK DR AND CT-218 E TO CT-178 W IN BLOOMFIELD. USE THE RIGHT 2 LANES TO TURN RIGHT ONTO PARK RD. USE THE LEFT 2 LANES TO TURN LEFT AT THE 1ST CROSS STREET ONTO TROUT BROOK DR. CONTINUE ONTO KING PHILIP DR. TURN LEFT ONTO MOHAWK DR. TURN RIGHT ONTO CT-218 E/MAIN ST. CONTINUE TO FOLLOW CT-218 E. TURN LEFT ONTO PROSPECT ST. TURN LEFT ONTO CT-178 W. DESTINATION WILL BE ON THE LEFT.

COPYRIGHT © 2017, MASER CONSULTING P.A. ALL RIGHTS RESERVED

THIS DRAWING AND ALL THE INFORMATION CONTAINED HEREIN IS AUTHORIZED FOR USE ONLY BY THE PARTY FOR WHOM THE WORK WAS CONTRACTED OR TO WHOM IT IS CERTIFIED. THIS DRAWING MAY NOT BE COPIED, REUSED, DISCLOSED, DISTRIBUTED OR RELIED UPON FOR ANY OTHER PURPOSE WITHOUT THE EXPRESS WRITTEN CONSENT OF MASER CONSULTING, P.A.

DRAWING INDEX

NYC DOB NUMBER	SHEET TITLE	REV.
T-001.00	TITLE SHEET	4
ANT-001.00	GENERAL NOTES - 1	4
ANT-002.00	GENERAL NOTES - 2	4
ANT-003.00	GENERAL NOTES - 3	4
ANT-004.00	SITE PLAN	4
ANT-005.00	EQUIPMENT PLAN AND ELEVATION	4
ANT-006.00	ANTENNA ORIENTATION PLAN	4
ANT-007.00	DETAILS	4
ANT-008.00	ANTENNA SCHEDULE, WIRING DIAGRAM, BILL OF MATERIALS AND NOTES	4
ANT-009.00	FIBER PLUMBING DIAGRAMS - 1	4
ANT-010.00	FIBER PLUMBING DIAGRAMS - 2	4
ANT-011.00	CABLE COLOR CODING, DC POWER DETAILS & PANEL SCHEDULES	4
ANT-012.00	ELECTRICAL AND GROUNDING NOTES	4
ANT-013.00	GROUNDING SCHEMATIC AND DETAILS	4
S-001.00	STRUCTURAL DETAILS	4

APPLICABLE BUILDING CODES & STANDARDS

ALL WORK AND MATERIALS SHALL BE PERFORMED AND INSTALLED IN ACCORDANCE WITH THE CURRENT EDITIONS OF THE FOLLOWING CODES AS ADOPTED BY THE LOCAL GOVERNING AUTHORITIES. NOTHING IN THESE PLANS IS TO BE CONSTRUED TO PERMIT WORK NOT CONFORMING TO THE LATEST EDITIONS OF THE FOLLOWING CODES.

- 2016 CONNECTICUT STATE BUILDING CODE, INCORPORATING THE 2012 INTERNATIONAL BUILDING CODE
- TIA/EIA-222-G OR LATEST EDITION
- NFPA 780-LIGHTNING PROTECTION CODE 2011
- 2014 NATIONAL ELECTRIC CODE OR LATEST EDITION
- ANY OTHER NATIONAL OR LOCAL APPLICABLE CODES MOST RECENT EDITIONS
- CT BUILDING CODE
- LOCAL BUILDING CODE
- CITY/COUNTY ORDINANCES

SCOPE OF WORK

SPRINT PROPOSED TO MODIFY AN EXISTING UNMANNED TELECOMMUNICATIONS FACILITY.

- INSTALL (3) NEW PANEL ANTENNAS
- REPLACE (3) EXISTING ANTENNAS WITH NEW DUAL BAND ANTENNAS
- INSTALL (9) NEW RRH'S
- INSTALL (48) JUMPER CABLES
- INSTALL (3) HYBRID CABLES (1 PER SECTOR)
- INSTALL (1) ELTEK ECAB GROWTH CABINET
- INSTALL (1) PPC
- INSTALL (1) ANTENNA MOUNTING KIT



Customer Loyalty through Client Satisfaction
www.maserconsulting.com
Engineers ■ Planners ■ Surveyors
Landscape Architects ■ Environmental Scientists

Copyright © 2018, Maser Consulting Connecticut. All Rights Reserved. This drawing and all the information contained herein is authorized for use only by the party for whom the services were contracted or to whom it is certified. This drawing may not be copied, reused, disclosed, distributed or relied upon for any other purpose without the express written consent of Maser Consulting Connecticut.



201 STATE ROUTE 17 NORTH
RUTHERFORD, NJ 07070
PHONE: (201) 684-4000 FAX: (201) 684-4223




Charles Cherundolo Consulting, Inc.
713 Clover Lane
Moscow, PA 18444
Phone: 973-207-4248
Fax: 570-842-5592



SCALE: AS SHOWN JOB NUMBER: 17924009A

REV	DATE	DESCRIPTION	BY	CHECKED BY
4	05/03/18	REVISED PER COMMENTS	JRF	PET
3	04/27/18	REVISED PER COMMENTS	JCM	PET
2	04/11/18	REVISED PER RFDS	JCM	JKM
1	01/29/18	MOUNT MODIFICATION DESIGN	YMA	JKM
0	10/20/17	ISSUED FOR CONSTRUCTION	JRF	PET
A	09/13/17	USED FOR REVIEW	JRF	PET



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF THE RESPONSIBLE LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SITE NAME: BLOOMFIELD POLICE DEPARTMENT
SITE ID: CT52XC024

785 PARK AVENUE
BLOOMFIELD, CT 06002



331 Newmarket Springs Road
Suite 202
Red Bank, NJ 07071-5699
Phone: 732.383.1950
Fax: 732.383.1984

SHEET TITLE: TITLE SHEET

SHEET NUMBER: T-001.00

GENERAL NOTES

1. CONTRACTOR SHALL NOT COMMENCE ANY WORK UNTIL HE OBTAINS, AT HIS OWN EXPENSE, ALL INSURANCE REQUIRED BY SPRINT, THE PROPERTY OWNER AND/OR PROPERTY MANAGEMENT COMPANY.
2. THIS SET OF PLANS HAS BEEN PREPARED FOR THE PURPOSES OF MUNICIPAL AND AGENCY REVIEW AND APPROVAL. THIS SET OF PLANS SHALL NOT BE UTILIZED AS CONSTRUCTION DOCUMENTS UNTIL ALL CONDITIONS OF APPROVAL HAVE BEEN SATISFIED AND EACH OF THE DRAWINGS HAVE BEEN REVISED TO INDICATE "ISSUED FOR CONSTRUCTION".
3. THE CONTRACTOR SHALL COMPLY WITH ALL APPLICABLE CODES, ORDINANCES, LAWS AND REGULATIONS OF ALL MUNICIPALITIES, UTILITIES OR OTHER PUBLIC AUTHORITIES.
4. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL PERMITS AND INSPECTIONS THAT MAY BE REQUIRED BY ANY FEDERAL, STATE, COUNTY OR MUNICIPAL AUTHORITIES.
5. THE CONTRACTOR SHALL NOTIFY THE CONSTRUCTION MANAGER, IN WRITING, OF ANY CONFLICTS, ERRORS OR OMISSIONS PRIOR TO THE SUBMISSION OF BIDS FOR PERFORMANCE OF WORK. MINOR OMISSIONS OR ERRORS IN THE BID DOCUMENTS SHALL NOT EXCUSE SAID CONTRACTOR FROM COMPLETING THIS PROJECT IN ACCORDANCE WITH THE OVERALL INTENT OF THESE DRAWINGS.
6. THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTING ALL EXISTING SITE IMPROVEMENTS PRIOR TO COMMENCING DEMOLITION. THE CONTRACTOR SHALL REPAIR ANY DAMAGE CAUSED AS A RESULT OF REMOVAL OF THIS FACILITY.
7. THE SCOPE OF WORK FOR THIS PROJECT SHALL INCLUDE PROVIDING ALL MATERIALS, EQUIPMENT AND LABOR AS REQUIRED TO COMPLETE THIS PROJECT. ALL EQUIPMENT SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS.
8. THE CONTRACTOR SHALL VISIT THE PROJECT SITE PRIOR TO SUBMITTING A BID TO VERIFY THAT THE PROJECT CAN BE REMOVED IN ACCORDANCE WITH THE CONTRACT DOCUMENTS.
9. THE DEMOLITION CONTRACTOR IS SOLELY RESPONSIBLE FOR DETERMINING ALL REMOVAL MEANS AND METHODS. THE DEMOLITION CONTRACTOR IS ALSO RESPONSIBLE FOR ALL JOB SITE SAFETY.
10. THE CONTRACTOR IS TO REVIEW ALL DRAWINGS AND SPECIFICATIONS IN THE CONTRACT DOCUMENT SET. THE CONTRACTOR SHALL COORDINATE ALL WORK SHOWN IN THE SET OF DRAWINGS. THE CONTRACTOR SHALL PROVIDE A COMPLETE SET OF DRAWINGS TO ALL SUBCONTRACTORS AND RELATED PARTIES. THE SUBCONTRACTOR SHALL EXAMINE ALL THE DRAWINGS AND SPECIFICATIONS FOR THE INFORMATION THAT EFFECTS THEIR WORK.
11. THE CONTRACTOR SHALL MAINTAIN A CURRENT SET OF DRAWINGS AND SPECIFICATIONS ON THE SITE AT ALL TIMES AND INSURE THE DISTRIBUTION OF NEW DRAWINGS TO SUBCONTRACTORS AND OTHER RELEVANT PARTIES AS SOON AS THEY ARE MADE AVAILABLE. OLD DRAWINGS SHALL BE MARKED VOID AND REMOVED FROM THE CONTRACT AREA. CONTRACTOR FURNISH 3 SETS OF REDLINE "AS-REMOVED" DRAWINGS TO SPRINT UPON COMPLETION OF THE WORK.
12. REPAIR MATERIALS INSTALLED SHALL MEET REQUIREMENTS OF CONTRACTORS DOCUMENTS. NO SUBSTITUTIONS ARE ALLOWED.
13. THE CONTRACTOR SHALL RECEIVE CLARIFICATION IN WRITING AND SHALL RECEIVE IN WRITING AUTHORIZATION TO PROCEED BEFORE STARTING WORK ON ANY ITEMS NOT CLEARLY DEFINED OR IDENTIFIED BY THE CONTRACT DOCUMENTS.
14. THE CONTRACTOR SHALL NOTIFY THE CONSTRUCTION MANAGER OF ALL PRODUCTS OR ITEMS NOTED AS EXISTING WHICH ARE NOT FOUND TO BE IN THE FIELD.
15. DEMOLITION SHALL BE DONE IN A WORKMANLIKE MANNER BY COMPETENT EXPERIENCED WORKMEN IN ACCORDANCE WITH APPLICABLE CODES AND THE BEST-ACCEPTED PRACTICE. ALL SURFACES SHALL BE REPAIRED TO MATCH THEIR SURROUNDINGS AND PROVIDE WEATHER TIGHT SEAL ON SAME DAY AS REMOVAL.
16. THE CONTRACTOR SHALL COORDINATE HIS WORK AND SCHEDULE HIS ACTIVITIES AND WORKING HOURS IN ACCORDANCE WITH THE REQUIREMENTS OF THE PROPERTY OWNER AND/OR PROPERTY MANAGEMENT COMPANY.
17. THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING HIS WORK WITH THE WORK OF OTHERS AS IT MAY RELATE TO RADIO EQUIPMENT, ANTENNAS AND ANY OTHER PORTIONS OF THE WORK.
18. THE CONTRACTOR SHALL REPAIR ALL EXISTING SURFACES DAMAGED DURING REMOVAL SUCH THAT THEY MATCH AND BLEND WITH ADJACENT SURFACES.
19. THE CONTRACTOR SHALL KEEP CONTRACT AREA CLEAN, HAZARD FREE AND DISPOSE OF ALL DEBRIS AND RUBBISH. LEAVE PREMISES IN CLEAN CONDITION AND FREE FROM PAINT SPOTS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTAINING ALL ITEMS UNTIL COMPLETION OF CONSTRUCTION.
20. BEFORE FINAL ACCEPTANCE OF THE WORK, THE CONTRACTOR SHALL REMOVE ALL EQUIPMENT, TEMPORARY WORKS, UNUSED AND USELESS MATERIALS, RUBBISH AND TEMPORARY STRUCTURES.



Customer Loyalty through Client Satisfaction
 www.maserconsulting.com
 Engineers ■ Planners ■ Surveyors
 Landscape Architects ■ Environmental Scientists

Copyright © 2018, Maser Consulting Connecticut. All Rights Reserved. This drawing and all the information contained herein is authorized for use only by the party for whom the services were contracted or to whom it is certified. This drawing may not be copied, revised, distributed, distributed or relied upon for any other purpose without the express written consent of Maser Consulting Connecticut.



201 STATE ROUTE 17 NORTH
 RUTHERFORD, NJ 07070
 PHONE: (201) 684-4000 FAX: (201) 684-4223




Charles Cherundolo Consulting, Inc.
 713 Clover Lane
 Moscow, PA 18444
 Phone: 973-207-4248
 Fax: 570-842-5592



PROTECT YOURSELF
 ALL STATES REQUIRE NOTIFICATION OF EXCAVATORS, DESIGNERS OR ANY PERSON PREPARING TO DISTURB THE EARTH'S SURFACE ANYWHERE IN ANY STATE.
 Know what's below.
 Call before you dig.
 FOR STATE SPECIFIC DIRECT PHONE NUMBERS VISIT:
 WWW.CALL811.COM

SCALE: AS SHOWN JOB NUMBER: 17924009A


REV	DATE	DESCRIPTION	BY	CHECKED BY
4	05/03/18	REVISED PER COMMENTS	JRF	PET
3	04/27/18	REVISED PER COMMENTS	JCM	PET
2	04/11/18	REVISED PER RFDS	JCM	JKM
1	01/29/18	MOUNT MODIFICATION DESIGN	YMA	JKM
0	10/20/17	ISSUED FOR CONSTRUCTION	JRF	PET
A	09/13/17	ISSUED FOR REVIEW	JRF	PET



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF THE RESPONSIBLE LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

**SITE NAME: BLOOMFIELD
 POLICE DEPARTMENT
 SITE ID: CT52XC024**

**785 PARK AVENUE
 BLOOMFIELD, CT 06002**



RED BANK OFFICE
 331 Newnam Springs Road
 Suite 203
 Red Bank, NJ 07701-5699
 Phone: 732.383.1950
 Fax: 732.383.1984

SHEET TITLE:
GENERAL NOTES - I

SHEET NUMBER:
ANT-001.00

SECTION 01 100 - SCOPE OF WORK

THE WORK:
THESE STANDARD CONSTRUCTION SPECIFICATIONS IN CONJUNCTION WITH THE CONSTRUCTION DRAWINGS AND ASSOCIATED OUTLINE SPECIFICATIONS AND THE SITE SPECIFIC WORK ORDER, DESCRIBE THE WORK TO BE PERFORMED BY THIS CONSTRUCTION CONTRACTOR (SUPPLIER).

RELATED DOCUMENTS:

- A. THE REQUIREMENTS OF EACH SECTION OF THIS SPECIFICATION APPLY TO ALL SECTIONS, INDIVIDUALLY AND COLLECTIVELY.
- B. RELATED DOCUMENTS: THE CONTRACTOR SHALL COMPLY WITH THE MOST CURRENT VERSION OF THE FOLLOWING SUPPLEMENTAL REQUIREMENTS FOR INSTALLATION AND TESTING.
- 1.EN-2012-001: (FIBER OPTIC, DC CABLE, AND DC CIRCUIT BREAKER TAGGING STANDARDS)
 - 2.TS-0200 - (TRANSMISSION ANTENNA LINE ACCEPTANCE STANDARDS)
 - 3.EL-0568: (FIBER TESTING POLICY)
 - 4.NP-312-201: (EXTERIOR GROUNDING SYSTEM TESTING)
 - 5.NP-760-500: ETHERNET, MICROWAVE, TESTING AND ACCEPTANCE

PRECEDENCE:

SHOULD CONFLICTS OCCUR BETWEEN THE STANDARD CONSTRUCTION SPECIFICATIONS FOR WIRELESS SITES AND THE CONSTRUCTION DRAWINGS, INFORMATION ON THE CONSTRUCTION DRAWINGS SHALL TAKE PRECEDENCE. NOTIFY SPRINT CONSTRUCTION MANAGER IF THIS OCCURS.

NATIONALLY RECOGNIZED CODES AND STANDARDS:

THE WORK SHALL COMPLY WITH APPLICABLE NATIONAL AND LOCAL CODES AND STANDARDS, LATEST EDITION, AND PORTIONS THEREOF, INCLUDED BUT NOT LIMITED TO THE FOLLOWING:

- A. GR-63-CORE NEBS REQUIREMENTS: PHYSICAL PROTECTION
- B. GR-78-CORE GENERIC REQUIREMENTS FOR THE PHYSICAL DESIGN AND MANUFACTURE OF TELECOMMUNICATIONS EQUIPMENT.
- C. GR-1089 CORE, ELECTROMAGNETIC COMPATIBILITY AND ELECTRICAL SAFETY -GENERIC CRITERIA FOR NETWORK TELECOMMUNICATIONS EQUIPMENT.
- D. NATIONAL FIRE PROTECTION ASSOCIATION CODES AND STANDARDS (NFPA) INCLUDING NFPA 70 (NATIONAL ELECTRICAL CODE - "NEC") AND NFPA 101 (LIFE SAFETY CODE).
- E. AMERICAN SOCIETY FOR TESTING OF MATERIALS (ASTM)
- F. INSTITUTE OF ELECTRONIC AND ELECTRICAL ENGINEERS (IEEE)
- G. AMERICAN CONCRETE INSTITUTE (ACI)
- H. AMERICAN WIRE PRODUCERS ASSOCIATION (AWPA)
- I. CONCRETE REINFORCING STEEL INSTITUTE (CRSI)
- J. AMERICAN ASSOCIATION OF STATE HIGHWAY AND TRANSPORTATION OFFICIALS (AASHTO)
- K. PORTLAND CEMENT ASSOCIATION (PCA)
- L. NATIONAL CONCRETE MASONRY ASSOCIATION (NCMA)
- M. BRICK INDUSTRY ASSOCIATION (BIA)
- N. AMERICAN WELDING SOCIETY (AWS)
- O. NATIONAL ROOFING CONTRACTORS ASSOCIATION (NRCA)
- P. SHEET METAL AND AIR CONDITIONING CONTRACTORS' NATIONAL ASSOCIATION (SMACNA)
- Q. DOOR AND HARDWARE INSTITUTE (DHI)
- R. OCCUPATIONAL SAFETY AND HEALTH ACT (OSHA)
- S. APPLICABLE BUILDING CODES INCLUDING UNIFORM BUILDING CODE, SOUTHERN BUILDING CODE, BOCA, AND THE INTERNATIONAL BUILDING CODE.

DEFINITIONS:

- A. WORK: THE SUM OF TASKS AND RESPONSIBILITIES IDENTIFIED IN THE CONTRACT DOCUMENTS.
- B. COMPANY: "SPRINT"; SPRINT NEXTEL CORPORATION AND ITS OPERATING ENTITIES.
- C. ENGINEER: SYNONYMOUS WITH ARCHITECT & ENGINEER AND "A&E". THE DESIGN PROFESSIONAL HAVING PROFESSIONAL RESPONSIBILITY FOR DESIGN OF THE PROJECT.
- D. CONTRACTOR: CONSTRUCTION CONTRACTOR, SUPPLIER, CONSTRUCTION VENDOR; INDIVIDUAL OR ENTITY WHO AFTER EXECUTION OF A CONTRACT IS BOUND TO ACCOMPLISH THE WORK.
- E. THIRD PARTY VENDOR OR AGENCY: A VENDOR OR AGENCY ENGAGED SEPARATELY BY THE COMPANY, A&E, OR CONTRACTOR TO PROVIDE MATERIALS OR TO ACCOMPLISH SPECIFIC TASKS RELATED TO BUT NOT INCLUDED IN THE WORK.
- F. CONSTRUCTION MANAGER - ALL PROJECTS RELATED COMMUNICATION TO FLOW THROUGH SPRINT REPRESENTATIVE IN CHARGE OF PROJECT.

SITE FAMILIARITY:

CONTRACTOR SHALL BE RESPONSIBLE FOR FAMILIARIZING HIMSELF WITH ALL CONTRACT DOCUMENTS, FIELD CONDITIONS AND DIMENSIONS PRIOR TO PROCEEDING WITH CONSTRUCTION. ANY DISCREPANCIES SHALL BE BROUGHT TO THE ATTENTION OF THE SPRINT CONSTRUCTION MANAGER PRIOR TO THE COMMENCEMENT OF WORK. NO COMPENSATION WILL BE AWARDED BASED ON CLAIM OF LACK OF KNOWLEDGE OR FIELD CONDITIONS.

POINT OF CONTACT:

COMMUNICATION BETWEEN SPRINT AND THE CONTRACTOR SHALL FLOW THROUGH THE SINGLE SPRINT CONSTRUCTION MANAGER APPOINTED TO MANAGE THE PROJECT FOR SPRINT.

ON-SITE SUPERVISION:

THE CONTRACTOR SHALL SUPERVISE AND DIRECT THE WORK AND SHALL BE RESPONSIBLE FOR CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES, AND PROCEDURES IN ACCORDANCE WITH THE CONTRACT DOCUMENTS. THE CONTRACTOR SHALL EMPLOY A COMPETENT SUPERINTENDENT WHO SHALL BE IN ATTENDANCE AT THE SITE AT ALL TIMES DURING PERFORMANCE OF THE WORK.

DRAWINGS REQUIRED AT JOBSITE:

THE CONSTRUCTION CONTRACTOR SHALL MAINTAIN A FULL SET OF THE CONSTRUCTION DRAWINGS FOR WIRELESS SITES AND THE STANDARD CONSTRUCTION SPECIFICATIONS FOR WIRELESS SITES AT THE JOBSITE FROM MOBILIZATION THROUGH CONSTRUCTION COMPLETION.

- A. THE JOBSITE DRAWINGS SHALL BE CLEARLY MARKED DAILY IN RED PENCIL WITH ANY CHANGES IN CONSTRUCTION OVER WHAT IS DEPICTED IN THE DOCUMENTS. AT CONSTRUCTION COMPLETION, THIS JOBSITE MARKUP SET SHALL BE DELIVERED TO THE COMPANY OR COMPANY'S DESIGNATED REPRESENTATIVE TO BE FORWARDED TO THE COMPANY'S A&E VENDOR FOR PRODUCTION OF "AS-BUILT" DRAWINGS.
- B. DIMENSIONS SHOWN ARE TO FINISH SURFACES UNLESS NOTED OTHERWISE. SPACING BETWEEN EQUIPMENT IS THE REQUIRED CLEARANCE. SHOULD THERE BE ANY QUESTIONS REGARDING THE CONTRACT DOCUMENTS, EXISTING CONDITIONS AND/OR DESIGN INTENT, THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING A CLARIFICATION FROM THE SPRINT CONSTRUCTION MANAGER PRIOR TO PROCEEDING WITH THE WORK.

USE OF JOB SITE:

THE CONTRACTOR SHALL CONFINED ALL CONSTRUCTION AND RELATED OPERATIONS INCLUDING STAGING AND STORAGE OF MATERIALS AND EQUIPMENT, PARKING, TEMPORARY FACILITIES, AND WASTE STORAGE TO THE LEASE PARCEL UNLESS OTHERWISE PERMITTED BY THE CONTRACT DOCUMENTS.

UTILITY SERVICES:

WHERE NECESSARY TO CUT EXISTING PIPES, ELECTRICAL WIRES, CONDUITS, CABLES, ETC., OF UTILITY SERVICES, OR OF FIRE PROTECTION OR COMMUNICATIONS SYSTEMS, THEY SHALL BE CUT AND CAPPED AT SUITABLE PLACES OR WHERE SHOWN. ALL SUCH ACTIONS SHALL BE COORDINATED WITH THE UTILITY COMPANY INVOLVED:

PERMITS/FEE:

WHEN REQUIRED THAT A PERMIT OR CONNECTION FEE BE PAID TO A PUBLIC UTILITY PROVIDER FOR NEW SERVICE TO THE CONSTRUCTION PROJECT, PAYMENT OF SUCH FEE SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR.

CONTRACTOR:

CONTRACTOR SHALL TAKE ALL MEASURES AND PROVIDE ALL MATERIAL NECESSARY FOR PROTECTING EXISTING EQUIPMENT AND PROPERTY.

USE OF ELECTRONIC PROJECT MANAGEMENT SYSTEMS:

CONTRACTOR WILL UTILIZE ITS BEST EFFORTS TO WORK WITH SPRINT ELECTRONIC PROJECT MANAGEMENT SYSTEMS. CONTRACTOR UNDERSTANDS THAT SUFFICIENT INTERNET ACCESS, EQUIVALENT TO "BROADBAND"

OR BETTER, IS REQUIRED TO TIMELY AND EFFECTIVELY UTILIZE SPRINT DATA AND DOCUMENT MANAGEMENT SYSTEMS AND AGREES TO MAINTAIN APPROPRIATE CONNECTIONS FOR CONTRACTOR'S STAFF AND OFFICES THAT ARE COMPATIBLE WITH SPRINT DATA AND DOCUMENT MANAGEMENT SYSTEMS

TEMPORARY UTILITIES AND FACILITIES:

THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL TEMPORARY UTILITIES AND FACILITIES NECESSARY EXCEPT AS OTHERWISE INDICATED IN THE CONSTRUCTION DOCUMENTS. TEMPORARY UTILITIES AND FACILITIES INCLUDE POTABLE WATER, HEAT, HVAC, ELECTRICITY, SANITARY FACILITIES, WASTE DISPOSAL FACILITIES, AND TELEPHONE/COMMUNICATION SERVICES. PROVIDE TEMPORARY UTILITIES AND FACILITIES IN ACCORDANCE WITH OSHA AND THE AUTHORITY HAVING JURISDICTION. CONTRACTOR MAY UTILIZE THE COMPANY ELECTRICAL SERVICE IN THE COMPLETION OF THE WORK WHEN IT BECOMES AVAILABLE. USE OF THE LESSOR'S OR SITE OWNER'S UTILITIES OR FACILITIES IS EXPRESSLY FORBIDDEN EXCEPT AS OTHERWISE ALLOWED IN THE CONTRACT DOCUMENTS.

ACCESS TO WORK:

THE CONTRACTOR SHALL PROVIDE ACCESS TO THE JOB SITE FOR AUTHORIZED COMPANY PERSONNEL AND AUTHORIZED REPRESENTATIVES OF THE ARCHITECT/ENGINEER DURING ALL PHASES OF THE WORK.

DIMENSIONS:

VERIFY DIMENSIONS INDICATED ON DRAWINGS WITH FIELD DIMENSIONS BEFORE FABRICATION OR ORDERING OF MATERIALS. DO NOT SCALE DRAWINGS.

EXISTING CONDITIONS:

NOTIFY THE SPRINT CONSTRUCTION MANAGER OF EXISTING CONDITIONS DIFFERING FROM THOSE INDICATED ON THE DRAWINGS. DO NOT REMOVE OR ALTER STRUCTURAL COMPONENTS WITHOUT PRIOR WRITTEN APPROVAL FROM THE ARCHITECT AND ENGINEER.

SECTION 01 200 - COMPANY FURNISHED MATERIAL AND EQUIPMENT

FURNISHED MATERIALS:

COMPANY FURNISHED MATERIALS AND EQUIPMENT TO BE INSTALLED BY THE CONTRACTOR (OFIC) IS IDENTIFIED ON THE RF DATA SHEET IN THE CONSTRUCTION DOCUMENTS.

RECEIPT OF MATERIAL AND EQUIPMENT:

- A. THE CONTRACTOR IS RESPONSIBLE FOR SPRINT PROVIDED MATERIAL AND EQUIPMENT AND UPON RECEIPT SHALL:
 1. ACCEPT DELIVERIES AS SHIPPED AND TAKE RECEIPT.
 2. VERIFY COMPLETENESS AND CONDITION OF ALL DELIVERIES.
 3. TAKE RESPONSIBILITY FOR EQUIPMENT AND PROVIDE INSURANCE PROTECTION AS REQUIRED IN AGREEMENT.
- B. RECORD ANY DEFECTS OR DAMAGES AND WITHIN TWENTY-FOUR HOURS AFTER RECEIPT, REPORT TO SPRINT OR ITS DESIGNATED PROJECT REPRESENTATIVE OF SUCH.
- C. PROVIDE SECURE AND NECESSARY WEATHER PROTECTED WAREHOUSING.
- D. COORDINATE SAFE AND SECURE TRANSPORTATION OF MATERIAL AND EQUIPMENT, DELIVERING AND OFF-LOADING FROM CONTRACTOR'S WAREHOUSE TO SITE.

DELIVERABLES:

- A. COMPLETE SHIPPING AND RECEIPT DOCUMENTATION IN ACCORDANCE WITH COMPANY PRACTICE.
- B. IF APPLICABLE, COMPLETE LOST/STOLEN/DAMAGED DOCUMENTATION REPORT AS NECESSARY IN ACCORDANCE WITH COMPANY PRACTICE, AND AS DIRECTED BY COMPANY.

SECTION 01 300 - CELL SITE CONSTRUCTION

NOTICE TO PROCEED:

- A. NO WORK SHALL COMMENCE PRIOR TO COMPANY'S ISSUANCE OF THE WORK ORDER.
- B. UPON RECEIVING NOTICE TO PROCEED, CONTRACTOR SHALL FULLY PERFORM ALL WORK NECESSARY TO PROVIDE SPRINT WITH AN OPERATIONAL WIRELESS FACILITY.

GENERAL REQUIREMENTS FOR CONSTRUCTION:

- A. CONTRACTOR SHALL KEEP THE SITE FREE FROM ACCUMULATING WASTE MATERIAL, DEBRIS, AND TRASH. AT THE COMPLETION OF THE WORK, CONTRACTOR SHALL REMOVE FROM THE SITE ALL REMAINING RUBBISH, IMPLEMENTS, TEMPORARY FACILITIES, AND SURPLUS MATERIALS.
- B. EQUIPMENT ROOMS SHALL AT ALL TIMES BE MAINTAINED "BROOM CLEAN" AND CLEAR OF DEBRIS.
- C. CONTRACTOR SHALL TAKE ALL REASONABLE PRECAUTIONS TO DISCOVER AND LOCATE ANY HAZARDOUS CONDITION.
 1. IN THE EVENT CONTRACTOR ENCOUNTERS ANY HAZARDOUS CONDITION WHICH HAS NOT BEEN ABATED OR OTHERWISE MITIGATED, CONTRACTOR AND ALL OTHER PERSONS SHALL IMMEDIATELY STOP WORK IN THE AFFECTED AREA AND NOTIFY COMPANY IN WRITING. THE WORK IN THE AFFECTED AREA SHALL NOT BE RESUMED EXCEPT BY WRITTEN NOTIFICATION BY COMPANY.
 2. CONTRACTOR AGREES TO USE CARE WHILE ON THE SITE AND SHALL NOT TAKE ANY ACTION THAT WILL OR MAY RESULT IN OR CAUSE THE HAZARDOUS CONDITION TO BE FURTHER RELEASED IN THE ENVIRONMENT, OR TO FURTHER EXPOSE INDIVIDUALS TO THE HAZARD.
- D. CONTRACTOR'S ACTIVITIES SHALL BE RESTRICTED TO THE PROJECT LIMITS. SHOULD AREAS OUTSIDE THE PROJECT LIMITS BE AFFECTED BY CONTRACTOR'S ACTIVITIES, CONTRACTOR SHALL IMMEDIATELY RETURN THEM TO ORIGINAL CONDITION

FUNCTIONAL REQUIREMENTS:

- A. THE ACTIVITIES DESCRIBED IN THIS PARAGRAPH REPRESENT MINIMUM ACTIONS AND PROCESSES REQUIRED TO SUCCESSFULLY COMPLETE THE WORK. CONTRACTOR SHALL TAKE ALL ACTIONS AS NECESSARY TO SUCCESSFULLY COMPLETE THE CONSTRUCTION OF A FULLY FUNCTIONING WIRELESS FACILITY AT THE SITE IN ACCORDANCE WITH COMPANY PROCESSES.
- B. SUBMIT SPECIFIC DOCUMENTATION AS INDICATED HEREIN, AND OBTAIN REQUIRED APPROVALS WHILE THE WORK IS BEING PERFORMED.
- C. MANAGE AND CONDUCT ALL FIELD CONSTRUCTION SERVICE RELATED ACTIVITIES
- D. PROVIDE CONSTRUCTION ACTIVITIES TO THE EXTENT REQUIRED BY THE CONTRACT DOCUMENTS, INCLUDING BUT NOT LIMITED TO THE FOLLOWING:
 1. PERFORM ANY REQUIRED SITE ENVIRONMENTAL MITIGATION.
 2. PREPARE GROUND SITES; PROVIDE DE-GRUBBING; AND ROUGH AND FINAL GRADING, AND COMPOUND SURFACE TREATMENTS.
 3. MANAGE AND CONDUCT ALL ACTIVITIES FOR INSTALLATION OF UTILITIES INCLUDING ELECTRICAL AND BACKHAUL (FIBER, COPPER, OR MICROWAVE).
 4. INSTALL UNDERGROUND FACILITIES INCLUDING UNDERGROUND POWER AND COMMUNICATIONS CONDUITS, AND UNDERGROUND GROUNDING SYSTEM.
 5. INSTALL ABOVE GROUND GROUNDING SYSTEMS, CONDUIT AND BOXES.
 6. PROVIDE NEW HVAC INSTALLATIONS AND MODIFICATIONS.
 7. INSTALL "H-FRAMES", CABINETS AND PADS AND PLATFORMS AS INDICATED.
 8. INSTALL ROADS, ACCESS WAYS, CURBS AND DRAINS AS INDICATED.
 9. ACCOMPLISH REQUIRED MODIFICATION OF EXISTING FACILITIES.
 10. PROVIDE ANTENNA SUPPORT STRUCTURE FOUNDATIONS.
 11. PROVIDE SLABS AND EQUIPMENT PLATFORMS.
 12. INSTALL COMPOUND FENCING, SIGHT SHIELDING, LANDSCAPING AND ACCESS BARRIERS.
 13. PERFORM INSPECTION AND MATERIAL TESTING AS REQUIRED HEREINAFTER.
 14. CONDUCT SITE RESISTANCE TO EARTH TESTING AS REQUIRED HEREINAFTER.
 15. INSTALL FIXED GENERATOR SETS AND OTHER STANDBY POWER SOLUTIONS.
 16. INSTALL TOWERS, ANTENNA SUPPORT STRUCTURES AND PLATFORMS ON EXISTING TOWERS AS REQUIRED.
 17. INSTALL CELL SITE RADIOS, MICROWAVE, GPS, COAXIAL MAINLINE, ANTENNAS, CROSS BAND COUPLERS, TOWER TOP AMPLIFIERS, LOW NOISE AMPLIFIERS AND RELATED EQUIPMENT.
 18. CONDUCT ALL REQUIRED TESTS AND INSPECTIONS
 19. PERFORM, DOCUMENT, AND CLOSE OUT ALL JURISDICTIONAL PERMITTING REQUIREMENTS AND ANY CONSTRUCTION CONTROL DOCUMENTS THAT MAY BE REQUIRED BY GOVERNMENT AGENCIES AND LANDLORDS.
 20. PERFORM ALL ADDITIONAL WORK AS IDENTIFIED IN SCOPE OF SERVICES ATTACHED TO THE SUPPLIER AGREEMENT FOR THIS PROJECT. THIS WORK MAY INCLUDE COMMISSIONING, INTEGRATION, SPECIAL WAREHOUSING, REVERSE LOGISTICS ACTIVITIES, ETC. PERFORM COMMISSIONING AND INTEGRATION ACTIVITIES PER APPLICABLE MOPS.

DELIVERABLES:

- A. THE CONTRACTOR SHALL PROVIDE ALL REQUIRED TEST REPORTS AND DOCUMENTATION INCLUDED BUT NOT LIMITED TO THE FOLLOWING:
 1. PRODUCT SPECIFICATIONS FOR MATERIALS OR SPECIAL CONSTRUCTION IF REQUESTED BY SPRINT
 2. ACTUALIZE ALL CONSTRUCTION RELATED MILESTONES IN SITERRA AND COMPLETE ALL ON-LINE FORMS AND COMPLETE DOCUMENT UP-LOADS. UPLOAD ALL REQUIRED CLOSEOUT DOCUMENTS AND FINAL SITE PHOTOS
 3. SCANABLE BARCODE PHOTOGRAPHS OF TOWER TOP AND INACCESSIBLE SERIALIZED EQUIPMENT LEFT ON SITE INSIDE BASE OF MAIN RF CABINET IN A PROTECTIVE POUCH.
 4. ALL REQUIRED TEST REPORTS.
 5. REQUIRED CLOSEOUT DOCUMENTATION INCLUDING BUT NOT LIMITED TO:
 - a. ALL JURISDICTIONAL PERMITTING AND OCCUPANCY INFORMATION
 - b. PDF SCAN OF REDLINES PRODUCED IN THE FIELD
 - c. ELECTRONIC AS-BUILT DRAWINGS IN AUTOCAD AND PDF FORMATS
 - d. LIEN WAIVERS
 - e. FINAL PAYMENT APPLICATION
 - f. REQUIRED FINAL CONSTRUCTION PHOTOS
 - g. CONSTRUCTION AND COMMISSIONING CHECKLIST COMPLETE WITH NO DEFICIENT ITEMS
 - h. LISTS OF SUBCONTRACTORS
- B. PROVIDE ADDITIONAL DOCUMENTATION INCLUDING, BUT NOT LIMITED TO, THE FOLLOWING. DOCUMENTATION SHALL BE FORWARDED IN ORIGINAL FORMAT AND/OR UPLOADED INTO SMS.
 1. ALL CORRESPONDENCE AND PRELIMINARY CONSTRUCTION REPORTS.
 2. PROJECT PROGRESS REPORTS.
 3. PRE-CONSTRUCTION MEETING NOTES.

SECTION 01 400 - TESTS, INSPECTIONS, SUBMITTALS, AND PROJECT CLOSEOUT

TESTS AND INSPECTIONS:

- A. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL CONSTRUCTION TESTS, INSPECTIONS AND PROJECT DOCUMENTATION.
- B. CONTRACTOR SHALL ACCOMPLISH TESTING INCLUDING BUT NOT LIMITED TO THE FOLLOWING:
 1. COAX SWEEPS AND FIBER TESTS PER TS-0200 (CURRENT VERSION) ANTENNA LINE ACCEPTANCE STANDARDS
 2. POST CONSTRUCTION HEIGHT VERIFICATION, AZIMUTH AND DOWNTILT USING ELECTRONIC COMMERCIAL MADE-FOR-THE-PURPOSE ANTENNA ALIGNMENT TOOL.
 3. CONCRETE BREAK TESTS
 4. SITE RESISTANCE TO EARTH TEST
 5. STRUCTURAL BACKFILL COMPACTION TESTS
 6. CONTRACTOR SHALL BE RESPONSIBLE FOR ANY AND ALL CORRECTIONS TO ANY WORK IDENTIFIED AS UNACCEPTABLE IN SITE INSPECTION ACTIVITIES AND/OR AS A RESULT OF TESTING.
 7. ADDITIONAL TESTING AS REQUIRED ELSEWHERE IN THIS SPECIFICATION.

SUBMITTALS:

- A. THE WORK IN ALL ASPECTS SHALL COMPLY WITH THE CONSTRUCTION DRAWINGS AND THESE SPECIFICATIONS.
- B. UPLOAD THE FOLLOWING TO SITERRA AS APPLICABLE INCLUDING BUT NOT LIMITED TO THE FOLLOWING:
 1. CONCRETE MIX-DESIGNS FOR TOWER FOUNDATIONS, ANCHORS PIERS, AND CONCRETE PAVING.
 2. CONCRETE BREAK TESTS AS SPECIFIED HEREIN.
 3. CHEMICAL GROUNDING SYSTEM.
 4. REINFORCEMENT CERTIFICATIONS
 5. STRUCTURAL BACKFILL TEST RESULTS
 6. SWEEP AND FIBER TESTS
 7. ANTENNA AZIMUTH AND DOWN-TILT VERIFICATION
 8. POST CONSTRUCTION HEIGHT VERIFICATION
 9. ADDITIONAL SUBMITTALS MAY BE REQUIRED FOR SPECIAL CONSTRUCTION OR MINOR MATERIALS
- C. ALTERNATES: AT THE COMPANY'S REQUEST, ANY ALTERNATIVES TO THE MATERIALS OR METHODS SPECIFIED SHALL BE SUBMITTED TO SPRINT'S CONSTRUCTION MANAGER FOR APPROVAL PRIOR TO BEING SHIPPED TO SITE. SPRINT WILL REVIEW AND APPROVE ONLY THOSE REQUESTS MADE IN WRITING. NO VERBAL APPROVALS WILL BE CONSIDERED. SUBMITTAL FOR APPROVAL SHALL INCLUDE A STATEMENT OF COST REDUCTION PROPOSED FOR USE OF ALTERNATE PRODUCT.

TESTING BY THIRD PARTY AGENCY:

- A. EMPLOY AN AGENCY OF ENGINEERS AND SCIENTISTS WHO IS REGULARLY ENGAGED IN FIELD AND LABORATORY TESTING AND ANALYSIS. AGENCY SHALL HAVE BEEN IN BUSINESS A MINIMUM OF FIVE YEARS, AND BE LICENSED AS PROFESSIONAL ENGINEERS IN THE STATE WHERE THE PROJECT IS LOCATED. AGENCY IS SUBJECT TO APPROVAL BY COMPANY.
 1. AGENCY MUST HAVE A THOROUGH UNDERSTANDING OF LOCAL AVAILABLE MATERIALS, INCLUDING THE SOIL, ROCK, AND GROUNDWATER CONDITIONS.
 2. AGENCY IS TO BE FAMILIAR WITH THE APPLICABLE REQUIREMENTS FOR THE TESTS TO BE DONE, EQUIPMENT TO BE USED, AND ASSOCIATED HEALTH AND SAFETY ISSUES.
 3. EXPERIENCE IN SOILS, CONCRETE, MASONRY, AGGREGATE, AND ASPHALT TESTING USING ASTM, AASHTO, AND OTHER METHODS IS NEEDED.
- B. REQUIRED THIRD PARTY TESTS:
 1. SITE RESISTANCE TO EARTH TEST PER NP-312-201
 2. CONCRETE CYLINDER BREAK TESTS FOR TOWER PIER AND ANCHORS PER NATIONALLY RECOGNIZED STANDARDS
 3. STRUCTURAL SOILS COMPACTION TESTS PER NATIONALLY RECOGNIZED STANDARDS
 4. REBAR PLACEMENT VERIFICATION WITH REPORT
 5. TESTING TENSION STUDY FOR ROCK ANCHORS
 6. ALL THIRD PARTY TESTS AS REQUIRED BY LOCAL JURISDICTION
- C. REQUIRED TESTS BY CONTRACTOR
 1. COAX SWEEP TESTS PER SPRINT STANDARD TS-0200
 2. FIBER TESTS PER SPRINT STANDARD EL-0568
 3. MICROWAVE LINK TESTS PER NP-760-500
 4. ANTENNA AZIMUTHS AND DOWN TILT USING ELECTRONIC ALIGNMENT TOOL PER ANTENNA INSTALLATION SPECIFICATION HEREIN.
 5. POST CONSTRUCTION HEIGHT VERIFICATION AS REQUIRED HERewith IN THE TOWER INSTALLATION SPECIFICATIONS.
 6. ASPHALT ROADWAY COMPACTED THICKNESS, SURFACE SMOOTHNESS, AND COMPACTED DENSITY TESTING AS SPECIFIED HERewith IN THE ASPHALT PAVING SPECIFICATIONS.
 7. FIELD QUALITY CONTROL TESTING AS SPECIFIED HERewith IN THE CONCRETE PAVING SPECIFICATIONS.
 8. TESTING REQUIRED HERewith UNDER SPECIFICATIONS FOR AGGREGATE BASE FOR ROADWAYS
 9. ALL OTHER TESTS REQUIRED BY LOCAL JURISDICTION
- D. INSPECTIONS BY COMPANY: THE CONTRACTOR SHALL BE RESPONSIBLE FOR ANY AND ALL CORRECTIONS TO ANY WORK IDENTIFIED AS UNACCEPTABLE IN INSPECTION ACTIVITIES, FINAL ACCEPTANCE / PUNCH WALK REVIEW, AND/OR AS A RESULT OF TESTING
- E. SPRINT RESERVES THE RIGHT TO INSPECT THE CONSTRUCTION SITE AT ANY TIME VIA SITE WALKS AND/OR PHOTO REVIEWS. CONTRACTOR SHALL GIVE SPRINT 24 HOURS NOTICE PRIOR TO THE COMMENCEMENT OF THE FOLLOWING CONSTRUCTION ACTIVITIES AND PHOTOGRAPHS OF THE IN-PROGRESS WORK.
 1. GROUNDING SYSTEM AND BURIED UTILITIES INSTALLATION PRIOR TO EARTH CONCEALMENT DOCUMENTED WITH DIGITAL PHOTOGRAPHS BY CONTRACTOR, APPROVED BY A&E OR SPRINT REPRESENTATIVE.
 2. FORMING FOR CONCRETE AND REBAR PLACEMENT PRIOR TO POUR DOCUMENTED WITH DIGITAL PHOTOGRAPHS BY CONTRACTOR, APPROVED BY A&E OR SPRINT REPRESENTATIVE.
 3. COMPACTION OF BACKFILL MATERIALS, AGGREGATE BASE FOR ROADS, PADS, AND ANCHORS, ASPHALT PAVING, AND SHAFT BACKFILL FOR CONCRETE AND WOOD POLES, BY INDEPENDENT THIRD PARTY AGENCY.
 4. PRE AND POST CONSTRUCTION ROOFTOP AND STRUCTURAL INSPECTIONS ON EXISTING FACILITIES. PRIOR TO CONSTRUCTION ACTIVITIES AND AFTER CONSTRUCTION IS COMPLETE, PROVIDE PHOTOGRAPHIC DOCUMENTATION OF ROOF, FLASHINGS, AND PARAPETS, BOTH BEFORE AND AFTER CONSTRUCTION IS COMPLETE.
 5. TOWER ERECTION SECTION STACKING AND PLATFORM ATTACHMENT DOCUMENTED BY DIGITAL PHOTOGRAPHS BY THIRD PARTY AGENCY.
 6. TOWER TOP AND INACCESSIBLE EQUIPMENT (RRUS, ANTENNAS, AND CABLING): PROVIDE PHOTOS OF THE BACKS OF ALL ANTENNAS, RRUS, COMBINERS, FILTERS, FIBER AND DC CABLING, CABLE COLOR CODING, EQUIPMENT GROUNDING AND CONNECTOR WATER PROOFING INCLUDING NAME PLATE AND SERIAL NUMBER FOR ALL SERIALIZED EQUIPMENT.



Customer Loyalty through Client Satisfaction
www.maserconsulting.com
Engineers ■ Planners ■ Surveyors
Landscape Architects ■ Environmental Scientists

Copyright © 2018, Maser Consulting Connecticut. All Rights Reserved. This drawing and all the information contained herein is authorized for use only by the party for whom the services were rendered or to whom it is certified. This drawing may not be copied, reused, distributed, or filed upon for any other purpose without the express written consent of Maser Consulting Connecticut.



201 STATE ROUTE 17 NORTH
RUTHERFORD, NJ 07070
PHONE: (201) 684-4000 FAX: (201) 684-4223




Charles Cherundolo Consulting, Inc.
713 Clover Lane
Moscow, PA 18444
Phone: 973-207-4248
Fax: 570-842-5592



SCALE: AS SHOWN JOB NUMBER: 17924009A


NO.	DATE	DESCRIPTION	BY	CHECKED BY
4	05/03/18	REVISED PER COMMENTS	JRF	PET
3	04/27/18	REVISED PER COMMENTS	JCM	PET
2	04/11/18	REVISED PER RFDS	JCM	JKM
1	01/29/18	MOUNT MODIFICATION DESIGN	YMA	JKM
0	10/20/17	ISSUED FOR CONSTRUCTION	JRF	PET
A	09/13/17	ISSUED FOR REVIEW	JRF	PET
REV	D	DESCRIPTION	BY	CHECKED BY



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTUALLY UNDER THE DIRECTION OF THE RESPONSIBLE LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SITE NAME: BLOOMFIELD
POLICE DEPARTMENT
SITE ID: CT52XC024

785 PARK AVENUE
BLOOMFIELD, CT 06002



SHEET TITLE:

GENERAL NOTES - 2

SHEET NUMBER:

ANT-002.00

PROJECT CLOSEOUT:

- A. FINAL ACCEPTANCE PUNCH WALK AND INSPECTION: AS IDENTIFIED IN THE SCOPE OF SERVICES, SPRINT WILL CONDUCT A FINAL PUNCH WALK OR FINAL DESK TOP PHOTO REVIEW (SITE MODIFICATIONS). PUNCH WALKS MUST BE SCHEDULED IN ADVANCE AS REQUIRED. AT THE PUNCH WALK / REVIEW, SPRINT MAY IDENTIFY CRITICAL DEFICIENCIES WHICH MUST BE CORRECTED PRIOR TO PUTTING SITE ON AIR. MINOR DEFICIENCIES MUST BE CORRECTED WITHIN 30 DAYS EXCEPT AS OTHERWISE REQUIRED. VERIFICATIONS OF CORRECTIONS MAY BE MADE BY COMPANY DURING A REPEAT SITE WALK OR DESK TOP PHOTO REVIEW AT COMPANY'S SOLE DISCRETION.
- B. CLOSEOUT DOCUMENTATION: ALL CLOSEOUT DOCUMENTATION AND PHOTOGRAPHS SHALL BE UPLOADED PRIOR TO FINAL ACCEPTANCE. SPRINT WILL REVIEW CLOSEOUT DOCUMENTATION FOR PRESENCE AND CONTENT. CLOSEOUT DOCUMENTATION SHALL INCLUDE BUT IS NOT LIMITED TO THE FOLLOWING AS APPLICABLE:
 1. COAX SWEEP TESTS;
 2. FIBER TESTS;
 3. JURISDICTION FINAL INSPECTION DOCUMENTATION
 4. REINFORCEMENT CERTIFICATION (MILL CERTIFICATION)
 5. CONCRETE MIX DESIGN AND PRODUCT DATA (TOWER FOUNDATION)
 6. LIEN WAIVERS AND RELEASES.
 7. POST -CONSTRUCTION HEIGHT VERIFICATION
 8. JURISDICTION CERTIFICATE OF OCCUPANCY
 9. ELECTRONIC ANTENNA AZIMUTH AND DOWN TILT VERIFICATION
 10. STRUCTURAL BACKFILL TEST RESULTS (IF APPLICABLE)
 11. CELL SITE UTILITY SETUP
 12. AS-BUILT REDLINE CONSTRUCTION DRAWINGS (PDF SCAN OF FIELD MARKS)
 13. AS-BUILT CONSTRUCTION DRAWINGS IN DWG AND PDF FORMATS
 14. LIST OF SUB CONTRACTORS
 15. APPROVED PERMITTING DOCUMENTS
 16. FINAL SITE PHOTOS UP-LOADED TO SITERRA. INCLUDE THE FOLLOWING AS APPLICABLE:
 - a. TOWER, ANTENNAS, RRUS, AND MAINLINE. INSPECTION AND PHOTOGRAPHS OF SECTION STACKING; INSPECTION AND PHOTOGRAPHS OF PLATFORM COMPONENT ATTACHMENT POINTS; PHOTOGRAPHS OF TOWER TOP GROUNDING; PHOTOS OF TOWER COAX/CABLE LINE COLOR CODING AT THE TOP AND AT GROUND LEVEL; INSPECTION AND PHOTOGRAPHS OF OPERATIONAL OF TOWER LIGHTING, AND PLACEMENT OF FAA REGISTRATION SIGN; PHOTOGRAPHS SHOWING ADDITIONAL GROUNDING POINTS FOR TOWERS GREATER THAN 200 FEET.; PHOTOS OF ANTENNA GROUND BAR, EQUIPMENT GROUND BAR, AND MASTER GROUND BAR; PHOTOS OF GPS ANTENNA(S); PHOTOS OF EACH SECTOR OF ANTENNAS; ONE PHOTOGRAPH LOOKING AT THE SECTOR AND ONE FROM BEHIND SHOWING THE PROJECTED COVERAGE AREA; PHOTOS OF COAX WEATHERPROOFING - TOP AND BOTTOM; PHOTOS OF COAX GROUNDING--TOP AND BOTTOM; PHOTOS OF ANTENNA AND MAST GROUNDING; PHOTOS OF COAX CABLE ENTRY INTO SHELTER; PHOTOS OF PLATFORM MECHANICAL CONNECTIONS TO TOWER/MONOPOLE.
 - b. ROOF TOPS: PRE-CONSTRUCTION AND POST-CONSTRUCTION VISUAL INSPECTION AND PHOTOGRAPHS OF THE ROOF AND INTERIOR TO DETERMINE AND DOCUMENT CONDITIONS; ROOF TOP CONSTRUCTION INSPECTIONS AS REQUIRED BY THE JURISDICTION; PHOTOGRAPHS OF CABLE TRAY AND/OR ICE BRIDGE; PHOTOGRAPHS OF DOGHOUSE/CABLE EXIT FROM ROOF.
 - c. SITE LAYOUT - PHOTOGRAPHS OF THE OVERALL COMPOUND, INCLUDING EQUIPMENT PLATFORM FROM ALL FOUR CORNERS.
 - d. FINISHED UTILITIES: CLOSE-UP PHOTOGRAPHS OF THE PPC BREAKER PANEL. CLOSE-UP PHOTOGRAPH OF THE INSIDE OF THE TELCO PANEL AND NIU; CLOSE-UP PHOTOGRAPH OF THE POWER METER AND DISCONNECT; PHOTOS OF POWER AND TELCO ENTRANCE TO COMPANY ENCLOSURE; PHOTOGRAPHS AT METER BOX AND/OR FACILITY DISTRIBUTION PANEL.

PROJECT PHOTOGRAPHS:

- A. PROVIDE PROJECT CLOSEOUT GENERAL ARRANGEMENT PHOTOS OF ALL NEW WORK. THE FOLLOWING LIST REPRESENTS MINIMUM REQUIREMENTS AND MINIMUM QUANTITY. ADDITIONAL PHOTOS MAY BE REQUIRED TO ADEQUATELY DOCUMENT THE WORK.
 1. ASR AND RF MPE SIGNAGE (IF NOT IN PLACE, SUPPLIER NOTIFIES EMS FIELD REPRESENTATIVE)
 2. BACK OF ANTENNAS AND RRUS (1 EACH SECTOR)
 3. BACK OF ANTENNAS AND RRUS (1 EACH SECTOR) CLOSE UP SHOWING WEATHERPROOFING AND GROUNDING (AS REQUIRED). CLOSE-UP OF BACK SIDE OF EACH PERMANENT RRU SHOWING SERIAL NUMBER/BAK CODE
 4. VIEW (1 EACH SECTOR) ALONG THE AZIMUTH AND TILT OF THE ANTENNAS
 5. TOP OF TOWER FROM GROUND, 1 EACH SECTOR
 6. MAINLINE HYBRID CABLE ROUTE DOWN TOWER SHOWING FASTENERS AND SUPPORT
 7. MAINLINE/HYBRID CABLE ROUTE ALONG ICE BRIDGE OR IN CABLE TRAY SHOWING FASTENERS AND SUPPORT
 8. GROUND MOUNTED RRU RACKS (FRONT AND BACK)
 9. FRONT, SIDE AND BACK ELEVATIONS OF ALL GROUND CABINETS
 10. VIEW OF COMPOUND FROM A DISTANCE
 11. VIEW OF EACH GROUND CABINET (POWER, RF, FIBER SPOOL, PPC POWER, PPC TELCO WITH DOOR OPEN)
 12. BACK-HAUL FIBER MEET-ME-POINT AND CONDUIT ROUTE (MICROWAVE INSTALLATION IF NOT FIBER)
 13. AAV NETWORK INTERFACE DEVICE OR MICROWAVE RADIO INSTALLATION

DEFICIENCY CORRECTIONS:

CONTRACTOR IS RESPONSIBLE FOR ALL CORRECTIONS TO DEFICIENCIES IDENTIFIED THROUGH TESTING, REVIEW OF SUBMITTALS, INSPECTIONS AND CLOSEOUT REVIEWS.

SECTION 01 500 - PROJECT REPORTING

WEEKLY REPORTS:

- A. CONTRACTOR SHALL REPORT TO SPRINT AT MINIMUM ON A WEEKLY BASIS VIA SITERRA BY UPDATING ALL APPLICABLE POST END KEEPING MILESTONES WITH ACTUAL AND FORECASTED COMPLETION DATES.
- B. ADDITIONAL REQUIREMENTS FOR REPORTING MAY BE IDENTIFIED ELSEWHERE OR REQUIRED BY THE SCOPE OF SERVICES OR SPRINTS LOCAL MARKET CONSTRUCTION MANAGER. THIS INFORMATION WILL PROVIDE A BASIS FOR PROGRESS MONITORING AND PAYMENT.

PROJECT CONFERENCE CALLS:
SPRINT MAY HOLD PERIODIC PROJECT CONFERENCE CALLS. CONTRACTOR WILL BE REQUIRED TO COMMUNICATE SITE STATUS, MILESTONE COMPLETIONS AND UPCOMING MILESTONE PROJECTIONS, AND ANSWER ANY OTHER SITE STATUS QUESTIONS AS NECESSARY.
FINAL PROJECT ACCEPTANCE: PRIOR TO SPRINTS FINAL PROJECT ACCEPTANCE. ALL REQUIRED MILESTONE ACTUALS MUST BE UPDATED IN SITERRA AND ALL REQUIRED REPORTING TASKS MUST BE COMPLETE.

SECTION 11 700 - ANTENNA ASSEMBLY, REMOTE RADIO UNITS AND CABLE INSTALLATION

SUMMARY:

THIS SECTION SPECIFIES INSTALLATION OF ANTENNAS, RRUS, AND CABLE EQUIPMENT, INSTALLATION, AND TESTING OF COAXIAL FIBER CABLE.

ANTENNAS AND RRUS:

THE NUMBER AND TYPE OF ANTENNAS AND RRUS TO BE INSTALLED IS DETAILED ON THE CONSTRUCTION DRAWINGS.

HYBRID CABLE:

HYBRID CABLE WILL BE DC/FIBER AND FURNISHED FOR INSTALLATION AT EACH SITE. CABLE SHALL BE INSTALLED PER THE CONSTRUCTION DRAWINGS AND THE APPLICABLE MANUFACTURER'S REQUIREMENTS.

JUMPERS AND CONNECTORS:

FURNISH AND INSTALL 1/2" COAX JUMPER CABLES BETWEEN THE RRUS AND ANTENNAS. JUMPERS SHALL BE TYPE LDF 4, FLC 12-50, CR 540, OR FXL 540. SUPER-FLEX CABLES ARE NOT ACCEPTABLE. JUMPERS BETWEEN THE RRUS AND ANTENNAS OR TOWER TOP AMPLIFIERS SHALL CONSIST OF 1/2 INCH FOAM DIELECTRIC, OUTDOOR RATED COAXIAL CABLE. MIN. LENGTH FOR JUMPER SHALL BE 10'-0".

REMOTE ELECTRICAL TILT (RET) CABLES:

MISCELLANEOUS:

INSTALL SPLITTERS, COMBINERS, FILTERS PER RF DATA SHEET, FURNISHED BY SPRINT.

ANTENNA INSTALLATION:

THE CONTRACTOR SHALL ASSEMBLE ALL ANTENNAS ONSITE IN ACCORDANCE WITH THE INSTRUCTIONS SUPPLIED BY THE MANUFACTURER. ANTENNA HEIGHT, AZIMUTH, AND FEED ORIENTATION INFORMATION SHALL BE A DESIGNATED ON THE CONSTRUCTION DRAWINGS.

- A. THE CONTRACTOR SHALL POSITION THE ANTENNA ON TOWER PIPE MOUNTS SO THAT THE BOTTOM STRUT IS LEVEL. THE PIPE MOUNTS SHALL BE PLUMB TO WITHIN 1 DEGREE.
- B. ANTENNA MOUNTING REQUIREMENTS: PROVIDE ANTENNA MOUNTING HARDWARE AS INDICATED ON THE DRAWINGS.

HYBRID CABLE INSTALLATION:

- A. THE CONTRACTOR SHALL ROUTE, TEST, AND INSTALL ALL CABLES AS INDICATED ON THE CONSTRUCTION DRAWINGS AND IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS.
- B. THE INSTALLED RADIUS OF THE CABLES SHALL NOT BE LESS THAN THE MANUFACTURER'S SPECIFICATIONS FOR BENDING RADIUS.
- C. EXTREME CARE SHALL BE TAKEN TO AVOID DAMAGE TO THE CABLES DURING HANDLING AND INSTALLATION.
 1. FASTENING MAIN HYBRID CABLES: ALL CABLES SHALL BE INSTALLED INSIDE MONOPOLE WITH CABLE SUPPORT GRIPS AS REQUIRED BY THE MANUFACTURER.
 2. FASTENING INDIVIDUAL FIBER AND DC CABLES ABOVE BREAKOUT ENCLOSURE (MEDUSA), WITHIN THE MMBS CABINET AND ANY INTERMEDIATE DISTRIBUTION BOXES:
 - a. FIBER: SUPPORT FIBER BUNDLES USING 1/2 " VELCRO STRAPS OF THE REQUIRED LENGTH AT 18" O.C. STRAPS SHALL BE UV, OIL AND WATER RESISTANT AND SUITABLE FOR INDUSTRIAL INSTALLATIONS AS MANUFACTURED BY TETOL OR APPROVED EQUAL.
 - b. DC: SUPPORT DC BUNDLES WITH ZIP TIES OF THE ADEQUATE LENGTH. ZIP TIES TO BE UV STABILIZED, BLACK NYLON, WITH TENSILE STRENGTH AT 12,000 PSI AS MANUFACTURED BY NELCO PRODUCTS OR EQUAL.
 3. FASTENING JUMPERS: SECURE JUMPERS TO THE SIDE ARMS OR HEAD FRAMES USING STAINLESS STEEL TIE WRAPS OR STAINLESS STEEL BUTTERFLY CLIPS.
 4. CABLE INSTALLATION:
 - a. INSPECT CABLE PRIOR TO USE FOR SHIPPING DAMAGE, NOTIFY THE CONSTRUCTION MANAGER.
 - b. CABLE ROUTING: CABLE INSTALLATION SHALL BE PLANNED TO ENSURE THAT THE LINES WILL BE PROPERLY ROUTED IN THE CABLE ENVELOP AS INDICATED ON THE DRAWINGS. AVOID TWISTING AND CROSSOVERS.
 - c. HOIST CABLE USING PROPER HOISTING GRIPS. DO NOT EXCEED MANUFACTURER'S RECOMMENDED MAXIMUM BEND RADIUS.
 5. GROUNDING OF TRANSMISSION LINES: ALL TRANSMISSION LINES SHALL BE GROUNDED AS INDICATED ON DRAWINGS.
 6. HYBRID CABLE COLOR CODING: ALL COLOR CODING SHALL BE AS REQUIRED IN TS 0200 (CURRENT VERSION).
 7. HYBRID CABLE LABELING: INDIVIDUAL HYBRID AND DC BUNDLES SHALL BE LABELED ALPHA-NUMERICALLY ACCORDING TO SPRINT CELL SITE ENGINEERING NOTICE - EN 2012-001, REV 1

WEATHERPROOFING EXTERIOR CONNECTORS AND HYBRID CABLE GROUND KITS:

- A. ALL FIBER & COAX CONNECTORS AND GROUND KITS SHALL BE WEATHERPROOFED.
- B. WEATHERPROOFED USING ONE OF THE FOLLOWING METHODS. ALL INSTALLATIONS MUST BE DONE IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS AND INDUSTRY BEST PRACTICES.
 1. COLD SHRINK: ENCOMPASS CONNECTOR IN COLD SHRINK TUBING AND PROVIDE A DOUBLE WRAP OF 2" ELECTRICAL TAPE EXTENDING 2" BEYOND TUBING. PROVIDE 3M COLD SHRINK CXS SERIES OR EQUAL.
 2. SELF-AMALGAMATING TAPE: CLEAN SURFACES. APPLY A DOUBLE WRAP OF SELF-AMALGAMATING TAPE 2" BEYOND CONNECTOR. APPLY A SECOND WRAP OF SELF-AMALGAMATING TAPE IN OPPOSITE DIRECTION, APPLY DOUBLE WRAP OF 2 " WIDE ELECTRICAL TAPE EXTENDING 2 " BEYOND THE SELF-AMALGAMATING TAPE.
 3. 3M SLIM LOCK CLOSURE 716: SUBSTITUTIONS WILL NOT BE ALLOWED.
 4. OPEN FLAME ON JOB SITE IS NOT ACCEPTABLE

SECTION 11 800 - INSTALLATION OF MULTIMODAL BASE STATIONS (MMBS) AND RELATED EQUIPMENT

SUMMARY:

- A. THIS SECTION SPECIFIES MMBS CABINETS, POWER CABINETS, AND INTERNAL EQUIPMENT INCLUDING BY NOT LIMITED TO RECTIFIERS, POWER DISTRIBUTION UNITS, BASE BAND UNITS, SURGE ARRESTORS, BATTERIES, AND SIMILAR EQUIPMENT FURNISHED BY THE COMPANY FOR INSTALLATION BY THE CONTRACTOR (OFCI).
- B. CONTRACTOR SHALL PROVIDE AND INSTALL ALL MISCELLANEOUS MATERIALS AND PROVIDE ALL LABOR REQUIRED FOR INSTALLATION EQUIPMENT IN EXISTING CABINET OR NEW CABINET AS SHOWN ON DRAWINGS AND AS REQUIRED BY THE APPLICABLE INSTALLATION MOPS.
- C. COMPLY WITH MANUFACTURER'S INSTALLATION AND START-UP REQUIREMENTS.

DC CIRCUIT BREAKER LABELING

- A. NEW DC CIRCUIT IS REQUIRED IN MMBS CABINET SHALL BE CLEARLY IDENTIFIED AS TO RRU BEING SERVICED.

SECTION 26 100 - BASIC ELECTRICAL REQUIREMENTS

SUMMARY:

THIS SECTION SPECIFIES BASIC ELECTRICAL REQUIREMENTS FOR SYSTEMS AND COMPONENTS

QUALITY ASSURANCE:

- A. ALL EQUIPMENT FURNISHED UNDER DIVISION 26 SHALL CARRY UL LABELS AND LISTINGS WHERE SUCH LABELS AND LISTINGS ARE AVAILABLE IN THE INDUSTRY.
- B. MANUFACTURERS OF EQUIPMENT SHALL HAVE A MINIMUM OF THREE YEARS EXPERIENCE WITH THEIR EQUIPMENT INSTALLED AND OPERATING IN THE FIELD IN A USE SIMILAR TO THE PROPOSED USE FOR THIS PROJECT.
- C. MATERIALS AND EQUIPMENT: ALL MATERIALS AND EQUIPMENT SPECIFIED IN DIVISION 26 OF THE SAME TYPE SHALL BE OF THE SAME MANUFACTURER AND SHALL BE NEW, OF THE BEST QUALITY AND DESIGN, AND FREE FROM DEFECTS.

SUPPORTING DEVICES:

- A. MANUFACTURED STRUCTURAL SUPPORT MATERIALS: SUBJECT TO COMPLIANCE WITH REQUIREMENTS, PROVIDE PRODUCTS BY THE FOLLOWING:
 1. ALLIED TUBE AND CONDUIT.
 2. B-LINE SYSTEM.
 3. UNISTRUT DIVERSIFIED PRODUCTS.
 4. THOMAS & BETTS.
- B. FASTENERS: TYPES, MATERIALS, AND CONSTRUCTION FEATURES AS FOLLOWS:
 1. EXPANSION ANCHORS: CARBON STEEL WEDGE OR SLEEVE TYPE.
 2. POWER-DRIVEN THREADED STUDS: HEAT-TREATED STEEL, DESIGNED SPECIFICALLY FOR THE INTENDED SERVICE.
 3. FASTEN BY MEANS OF WOOD SCREWS ON WOOD.
 4. TOGGLE BOLTS ON HOLLOW MASONRY UNITS.
 5. CONCRETE INSERTS OR EXPANSION BOLTS ON CONCRETE OR SOLID MASONRY.
 6. MACHINE SCREWS, WELDED THREADED STUDS, OR SPRING-TENSION CLAMPS ON STEEL
 7. EXPLOSIVE DEVICES FOR ATTACHING HANGERS TO STRUCTURE SHALL NOT BE PERMITTED.
 8. DO NOT WELD CONDUIT, PIPE STRAPS, OR ITEMS OTHER THAN THREADED STUDS TO STEEL STRUCTURES.
 9. IN PARTITIONS OF LIGHT STEEL CONSTRUCTION, USE SHEET METAL SCREWS.

SUPPORTING DEVICES:

- A. INSTALL SUPPORTING DEVICES TO FASTEN ELECTRICAL COMPONENTS SECURELY AND PERMANENTLY IN ACCORDANCE WITH NEC.
- B. COORDINATE WITH THE BUILDING STRUCTURAL SYSTEM AND WITH OTHER TRADES.
- C. UNLESS OTHERWISE INDICATED ON THE DRAWINGS, FASTEN ELECTRICAL ITEMS AND THEIR SUPPORTING HARDWARE SECURELY TO THE STRUCTURE IN ACCORDANCE WITH THE FOLLOWING:
 1. ENSURE THAT THE LOAD APPLIED BY ANY FASTENER DOES NOT EXCEED 25 PERCENT OF THE PROOF TEST LOAD.
 2. USE VIBRATION AND SHOCK-RESISTANT FASTENERS FOR ATTACHMENTS TO CONCRETE SLABS.

ELECTRICAL IDENTIFICATION:

- A. UPDATE AND PROVIDE TYPED CIRCUIT BREAKER SCHEDULES IN THE MOUNTING BRACKET, INSIDE DOORS OF AC PANEL BOARDS WITH ANY CHANGES MADE TO THE AC SYSTEM.
- B. BRANCH CIRCUITS FEEDING AVIATION OBSTRUCTION LIGHTING EQUIPMENT SHALL BE CLEARLY IDENTIFIED AS SUCH AT THE BRANCH CIRCUIT PANELBOARD.

SECTION 26 200 - ELECTRICAL MATERIALS AND EQUIPMENT

- A. RIGID GALVANIZED STEEL (RGS) CONDUIT SHALL BE USED FOR EXTERIOR LOCATIONS ABOVE GROUND AND IN UNFINISHED INTERIOR LOCATIONS AND FOR UNDERGROUND RUNS. RIGID CONDUIT AND FITTINGS SHALL BE STEEL, COATED WITH ZINC EXTERIOR AND INTERIOR BY THE HOT DIP GALVANIZING PROCESS. CONDUIT SHALL BE PRODUCED TO ANSI SPECIFICATIONS C80.1, FEDERAL SPECIFICATION WW-C-581 AND SHALL BE LISTED WITH THE UNDERWRITERS' LABORATORIES. FITTINGS SHALL BE THREADED - SET SCREW OR COMPRESSION FITTINGS WILL NOT BE ACCEPTABLE. RGS CONDUITS SHALL BE MANUFACTURED BY ALLIED, REPUBLIC OR WHEATLAND.
- B. UNDERGROUND CONDUIT IN CONCRETE SHALL BE POLYVINYLCHLORIDE (PVC) SUITABLE FOR DIRECT BURIAL AS APPLICABLE. JOINTS SHALL BE BELLED, AND FLUSH SOLVENT WELDED IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS. CONDUIT SHALL BE CARLON ELECTRICAL PRODUCTS OR APPROVED EQUAL.
- C. TRANSITIONS BETWEEN PVC AND RIGID (RGS) SHALL BE MADE WITH PVC COATED METALLIC LONG SWEEP RADIUS ELBOWS.
- D. EMT OR RIGID GALVANIZED STEEL CONDUIT MAY BE USED IN FINISHED SPACES CONGEALED IN WALLS AND CEILINGS. EMT SHALL BE MILD STEEL-ELECTRICALLY WELDED, ELECTRO-GALVANIZED OR HOT-DIPPED GALVANIZED AND PRODUCED TO ANSI SPECIFICATION C80.3, FEDERAL SPECIFICATION WW-C-563, AND SHALL BE UL LISTED. EMT SHALL BE MANUFACTURED BY ALLIED, REPUBLIC OR WHEATLAND, OR APPROVED EQUAL. FITTINGS SHALL BE METALLIC COMPRESSION. SET SCREW CONNECTIONS SHALL NOT BE ACCEPTABLE.
- E. LIQUID TIGHT FLEXIBLE METALLIC CONDUIT SHALL BE USED FOR FINAL CONNECTION TO EQUIPMENT. FITTINGS SHALL BE METALLIC GLAND TYPE COMPRESSION FITTINGS, MAINTAINING THE INTEGRITY OF CONDUIT SYSTEM. SET SCREW CONNECTIONS SHALL NOT BE ACCEPTABLE. MAXIMUM LENGTH OF FLEXIBLE CONDUIT SHALL NOT EXCEED 6-FEET. LFMC SHALL BE PROTECTED AND SUPPORTED AS REQUIRED BY NEC. MANUFACTURERS OF FLEXIBLE CONDUITS SHALL BE CAROL, ANACONDA METAL HOSE OR UNIVERSAL METAL HOSE, OR APPROVED EQUAL.
- F. MINIMUM SIZE CONDUIT SHALL BE 3/4 INCH (21MM).

HUBS AND BOXES:

- A. AT ENTRANCES TO CABINETS OR OTHER EQUIPMENT NOT HAVING INTEGRAL THREADED HUBS PROVIDE METALLIC THREADED HUBS OF THE SIZE AND CONFIGURATION REQUIRED. HUB SHALL INCLUDE LOCKNUT AND NEOPRENE O-RING SEAL. PROVIDE IMPACT RESISTANT 105 DEGREE C PLASTIC BUSHINGS TO PROTECT CABLE INSULATION.
- B. CABLE TERMINATION FITTINGS FOR CONDUIT
 1. CABLE TERMINATORS FOR RGS CONDUITS SHALL BE TYPE CRC BY O-Z/GEDNEY OR EQUAL BY ROXTEC.
 2. CABLE TERMINATORS FOR LFMC SHALL BE ETCO - CL2075; OR MADE FOR THE PURPOSE PRODUCTS BY ROXTEC.
- C. EXTERIOR PULL BOXES AND PULL BOXES IN INTERIOR INDUSTRIAL AREAS SHALL BE PLATED CAST ALLOY, HEAVY DUTY, WEATHERPROOF, DUST PROOF, WITH GASKET, PLATED IRON ALLOY COVER AND STAINLESS STEEL COVER SCREWS, CROUSE-HINDS WAB SERIES OR EQUAL.
- D. CONDUIT OUTLET BODIES SHALL BE PLATED CAST ALLOY WITH SIMILAR GASKET COVERS. OUTLET BODIES SHALL BE OF THE CONFIGURATION AND SIZE SUITABLE FOR THE APPLICATION. PROVIDE CROUSE-HINDS FORM 8 OR EQUAL.
- E. MANUFACTURER FOR BOXES AND COVERS SHALL BE HOFFMAN, SQUARE "D", CROUSE-HINDS, COOPER, ADALET, APPLETON, O-Z GEDNEY, RACO, OR APPROVED EQUAL.

SUPPLEMENTAL GROUNDING SYSTEM:

- A. FURNISH AND INSTALL A SUPPLEMENTAL GROUNDING SYSTEM TO THE EXTENT INDICATED ON THE DRAWINGS. SUPPORT SYSTEM WITH NON-MAGNETIC STAINLESS STEEL CLIPS WITH RUBBER GROMMETS. GROUNDING CONNECTORS SHALL BE TINNED COPPER WIRE, SIZES AS INDICATED ON THE DRAWINGS. PROVIDE STRANDED OR SOLID BARE OR INSULATED CONDUCTORS EXCEPT AS OTHERWISE NOTED.
- B. SUPPLEMENTAL GROUNDING SYSTEM: ALL CONNECTIONS TO BE MADE WITH CAD WELDS, EXCEPT AT EQUIPMENT USE LUGS OR OTHER AVAILABLE GROUNDING MEANS AS REQUIRED BY MANUFACTURER; AT GROUND BARS USE TWO HOLE SPADES WITH NO-OX.
- C. STOLEN GROUND-BARS: IN THE EVENT OF STOLEN GROUND BARS, CONTACT SPRINT CM FOR REPLACEMENT INSTRUCTION USING THREADED ROD KITS.

EXISTING STRUCTURE:

- A. EXISTING EXPOSED WIRING AND ALL EXPOSED OUTLETS, RECEPTACLES, SWITCHES, DEVICES, BOXES, AND OTHER EQUIPMENT THAT ARE NOT TO BE UTILIZED IN THE COMPLETED PROJECT SHALL BE REMOVED OR DE-ENERGIZED AND CAPPED IN THE WALL, CEILING, OR FLOOR SO THAT THEY ARE CONCEALED AND SAFE. WALL, CEILING, OR FLOOR SHALL BE PATCHED TO MATCH THE ADJACENT CONSTRUCTION.

CONDUIT AND CONDUCTOR INSTALLATION:

- A. CONDUITS SHALL BE FASTENED SECURELY IN PLACE WITH APPROVED NON-PERFORATED STRAPS AND HANGERS. EXPLOSIVE DEVICES FOR ATTACHING HANGERS TO STRUCTURE WILL NOT BE PERMITTED. CLOSELY FOLLOW THE LINES OF THE STRUCTURE, MAINTAIN CLOSE PROXIMITY TO THE STRUCTURE AND KEEP CONDUITS IN TIGHT ENVELOPES. CHANGES IN DIRECTION TO ROUTE AROUND OBSTACLES SHALL BE MADE WITH CONDUIT OUTLET BODIES. CONDUIT SHALL BE INSTALLED IN A NEAT AND WORKMANLIKE MANNER, PARALLEL AND PERPENDICULAR TO STRUCTURE WALL AND CEILING LINES. ALL CONDUIT SHALL BE FISHED TO CLEAR OBSTRUCTIONS. ENDS OF CONDUITS SHALL BE TEMPORARILY CAPPED TO PREVENT CONCRETE, PLASTER OR DIRT FROM ENTERING. CONDUITS SHALL BE RIGIDLY CLAMPED TO BOXES BY GALVANIZED MALLEABLE IRON BUSHING ON INSIDE AND GALVANIZED MALLEABLE IRON LOCKNUT ON OUTSIDE AND INSIDE.
- B. CONDUCTORS SHALL BE PULLED IN ACCORDANCE WITH ACCEPTED GOOD PRACTICE.



Customer Loyalty through Client Satisfaction
www.maserconsulting.com
Engineers ■ Planners ■ Surveyors
Landscape Architects ■ Environmental Scientists

Copyright © 2018, Maser Consulting Connecticut. All Rights Reserved. This drawing and all the information contained herein is authorized for use only by the party for whom the services were rendered or to whom it is certified. This drawing may not be copied, reused, disseminated, distributed or relied upon for any other purpose without the express written consent of Maser Consulting Connecticut.



201 STATE ROUTE 17 NORTH
RUTHERFORD, NJ 07070
PHONE: (201) 684-4000 FAX: (201) 684-4223



Charles Cherundolo Consulting, Inc.
713 Clover Lane
Moscow, PA 18444
Phone: 973-207-4248
Fax: 570-842-5592



SCALE: AS SHOWN JOB NUMBER: 17924009A


NO.	DATE	DESCRIPTION	BY	CHECKED BY
4	05/03/18	REVISED PER COMMENTS	JRF	PET
3	04/27/18	REVISED PER COMMENTS	JCM	PET
2	04/11/18	REVISED PER RFDS	JCM	JKM
1	01/29/18	MOUNT MODIFICATION DESIGN	YMA	JKM
0	10/20/17	ISSUED FOR CONSTRUCTION	JRF	PET
A	09/13/17	USED FOR REVIEW	JRF	PET
REV		DESCRIPTION	BY	CHECKED BY



IT IS A VIOLATION OF LAW IN ANY JURISDICTION, UNLESS THEY ARE ACTUALLY UNDER THE DIRECTION OF THE RESPONSIBLE LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SITE NAME: BLOOMFIELD
POLICE DEPARTMENT
SITE ID: CT52XC024

785 PARK AVENUE
BLOOMFIELD, CT 06002



SHEET TITLE:




GENERAL NOTES - 3

SHEET NUMBER:

ANT-003.00

GENERAL NOTES:

1. SITE INFORMATION OBTAINED FROM THE FOLLOWING:
 - A. DRAWINGS ENTITLED, "BLOOMFIELD POLICE DEPARTMENT" PREPARED BY CLEARWIRE TECHNOLOGIES, INC. OF BLOOMFIELD, CONNECTICUT, DATED 06/21/10.
2. CONTRACTOR SHALL VERIFY ALL PLANS AND EXISTING DIMENSIONS AND CONDITIONS ON THE JOB SITE AND SHALL IMMEDIATELY NOTIFY THE ARCHITECT/ENGINEER IN WRITING OF ANY DISCREPANCIES BEFORE PROCEEDING WITH THE WORK OR BE RESPONSIBLE FOR SAME.
3. CONTRACTOR SHALL NOT COMMENCE ANY WORK UNTIL HE OBTAINS, AT HIS OWN EXPENSE, ALL INSURANCE REQUIRED BY SPRINT, THE PROPERTY OWNER AND/OR PROPERTY MANAGEMENT COMPANY.
4. THIS SET OF PLANS HAS BEEN PREPARED FOR THE PURPOSES OF MUNICIPAL AND AGENCY REVIEW AND APPROVAL. THIS SET OF PLANS SHALL NOT BE UTILIZED AS CONSTRUCTION DOCUMENTS UNTIL ALL CONDITIONS OF APPROVAL HAVE BEEN SATISFIED AND EACH OF THE DRAWINGS HAVE BEEN REVISED TO INDICATE "ISSUED FOR CONSTRUCTION."
5. THE CONTRACTOR SHALL COMPLY WITH ALL APPLICABLE CODES, ORDINANCES, LAWS AND REGULATIONS OF ALL MUNICIPALITIES, UTILITIES OR OTHER PUBLIC AUTHORITIES.
6. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL PERMITS AND INSPECTIONS THAT MAY BE REQUIRED BY ANY FEDERAL, STATE, COUNTY OR MUNICIPAL AUTHORITIES.
7. THE CONTRACTOR SHALL NOTIFY THE CONSTRUCTION MANAGER, IN WRITING, OF ANY CONFLICTS, ERRORS OR OMISSIONS PRIOR TO THE SUBMISSION OF BIDS FOR PERFORMANCE OF WORK. MINOR OMISSIONS OR ERRORS IN THE BID DOCUMENTS SHALL NOT EXCLUDE SAID CONTRACTOR FROM COMPLETING THIS PROJECT IN ACCORDANCE WITH THE OVERALL INTENT OF THESE DRAWINGS.
8. THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTING ALL EXISTING SITE IMPROVEMENTS PRIOR TO COMMENCING DEMOLITION. THE CONTRACTOR SHALL REPAIR ANY DAMAGE CAUSED AS A RESULT OF REMOVAL OF THIS FACILITY.
9. THE SCOPE OF WORK FOR THIS PROJECT SHALL INCLUDE PROVIDING ALL MATERIALS, EQUIPMENT AND LABOR AS REQUIRED TO COMPLETE THIS PROJECT. ALL EQUIPMENT SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS.
10. THE CONTRACTOR SHALL VISIT THE PROJECT SITE PRIOR TO SUBMITTING A BID TO VERIFY THAT THE PROJECT CAN BE REMOVED IN ACCORDANCE WITH THE CONTRACT DOCUMENTS.
11. THE DEMOLITION CONTRACTOR IS SOLELY RESPONSIBLE FOR DETERMINING ALL REMOVAL MEANS AND METHODS. THE DEMOLITION CONTRACTOR IS ALSO RESPONSIBLE FOR ALL JOB SITE SAFETY.
12. THE CONTRACTOR IS TO REVIEW ALL DRAWINGS AND SPECIFICATIONS IN THE CONTRACT DOCUMENT SET. THE CONTRACTOR SHALL COORDINATE ALL WORK SHOWN IN THE SET OF DRAWINGS. THE CONTRACTOR SHALL PROVIDE A COMPLETE SET OF DRAWINGS TO ALL SUBCONTRACTORS AND RELATED PARTIES. THE SUBCONTRACTOR SHALL EXAMINE ALL THE DRAWINGS AND SPECIFICATIONS FOR THE INFORMATION THAT EFFECTS THEIR WORK.
13. THE CONTRACTOR SHALL MAINTAIN A CURRENT SET OF DRAWINGS AND SPECIFICATIONS ON THE SITE AT ALL TIMES AND INSURE THE DISTRIBUTION OF NEW DRAWINGS TO SUBCONTRACTORS AND OTHER RELEVANT PARTIES AS SOON AS THEY ARE MADE AVAILABLE. OLD DRAWINGS SHALL BE MARKED VOID AND REMOVED FROM THE CONTRACT AREA. CONTRACTOR FURNISH 3 SETS OF REDLINE "AS-REMOVED" DRAWINGS TO SPRINT UPON COMPLETION OF THE WORK.
14. REPAIR MATERIALS INSTALLED SHALL MEET REQUIREMENTS OF CONTRACTORS DOCUMENTS. NO SUBSTITUTIONS ARE ALLOWED.
15. THE CONTRACTOR SHALL RECEIVE CLARIFICATION IN WRITING AND SHALL RECEIVE IN WRITING AUTHORIZATION TO PROCEED BEFORE STARTING WORK ON ANY ITEMS NOT CLEARLY DEFINED OR IDENTIFIED BY THE CONTRACT DOCUMENTS.
16. THE CONTRACTOR SHALL NOTIFY THE CONSTRUCTION MANAGER OF ALL PRODUCTS OR ITEMS NOTED AS EXISTING WHICH ARE NOT FOUND TO BE IN THE FIELD.
17. DEMOLITION SHALL BE DONE IN A WORKMANLIKE MANNER BY COMPETENT EXPERIENCED WORKMEN IN ACCORDANCE WITH APPLICABLE CODES AND THE BEST-ACCEPTED PRACTICE. ALL SURFACES SHALL BE REPAIRED TO MATCH THEIR SURROUNDINGS AND PROVIDE WEATHER TIGHT SEAL ON SAME DAY AS REMOVAL.
18. THE CONTRACTOR SHALL COORDINATE HIS WORK AND SCHEDULE HIS ACTIVITIES AND WORKING HOURS IN ACCORDANCE WITH THE REQUIREMENTS OF THE PROPERTY OWNER AND/OR PROPERTY MANAGEMENT COMPANY.
19. THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING HIS WORK WITH THE WORK OF OTHERS AS IT MAY RELATE TO RADIO EQUIPMENT, ANTENNAS AND ANY OTHER PORTIONS OF THE WORK.
20. THE CONTRACTOR SHALL REPAIR ALL EXISTING SURFACES DAMAGED DURING REMOVAL SUCH THAT THEY MATCH AND BLEND WITH ADJACENT SURFACES.
21. THE CONTRACTOR SHALL KEEP CONTRACT AREA CLEAN, HAZARD FREE AND DISPOSE OF ALL DEBRIS AND RUBBISH. LEAVE PREMISES IN CLEAN CONDITION AND FREE FROM PAINT SPOTS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTAINING ALL ITEMS UNTIL COMPLETION OF CONSTRUCTION.
22. BEFORE FINAL ACCEPTANCE OF THE WORK, THE CONTRACTOR SHALL REMOVE ALL EQUIPMENT, TEMPORARY WORKS, UNUSED AND USELESS MATERIALS, RUBBISH AND TEMPORARY STRUCTURES.



LEGEND

- LIGHT LINE WORK INDICATES EXISTING OBJECTS
- HEAVY LINE WORK INDICATED PROPOSED OBJECTS



Customer Loyalty through Client Satisfaction
 www.maserconsulting.com
 Engineers ■ Planners ■ Surveyors
 Landscape Architects ■ Environmental Scientists

Copyright © 2018, Maser Consulting Connecticut. All Rights Reserved. This drawing and all the information contained herein is authorized for use only by the party for whom the services were contracted or to whom it is certified. This drawing may not be copied, reused, disseminated, distributed or relied upon for any other purpose without the express written consent of Maser Consulting Connecticut.



201 STATE ROUTE 17 NORTH
 RUTHERFORD, NJ 07070
 PHONE: (201) 684-4000 FAX: (201) 684-4223



Charles Cherundolo Consulting, Inc.
 713 Clover Lane
 Moscow, PA 18444
 Phone: 973-207-4248
 Fax: 570-842-5592



SCALE: AS SHOWN JOB NUMBER: 17924009A

REV	DATE	DESCRIPTION	BY	CHECKED	BY
4	05/03/18	REVISED PER COMMENTS	JRF	PET	
3	04/27/18	REVISED PER COMMENTS	JCM	PET	
2	04/11/18	REVISED PER RFDS	JCM	JKM	
1	01/29/18	MOUNT MODIFICATION DESIGN	YMA	JKM	
0	10/20/17	ISSUED FOR CONSTRUCTION	JRF	PET	
A	09/13/17	USED FOR REVIEW	JRF	PET	
REV	D	DESCRIPTION	BY	CHECKED	BY



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF THE RESPONSIBLE LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SITE NAME: BLOOMFIELD POLICE DEPARTMENT
SITE ID: CT52XC024

785 PARK AVENUE
 BLOOMFIELD, CT 06002



RED BANK OFFICE
 331 Newmarket Springs Road
 Suite 203
 Red Bank, NJ 07701-5699
 Phone: 732.383.1950
 Fax: 732.383.1984

SHEET TITLE: SITE PLAN

SHEET NUMBER: ANT-004.00



201 STATE ROUTE 17 NORTH
RUTHERFORD, NJ 07070
PHONE: (201) 684-4000 FAX: (201) 684-4223




Charles Cherundolo Consulting, Inc.
713 Clover Lane
Moscow, PA 18444
Phone: 973-207-4248
Fax: 570-842-5592



SCALE: AS SHOWN JOB NUMBER: 17924009A

REV	DATE	DESCRIPTION	BY	CHECKED
4	05/03/18	REVISED PER COMMENTS	JRF	PET
3	04/27/18	REVISED PER COMMENTS	JCM	PET
2	04/11/18	REVISED PER RFDS	JCM	JKM
1	01/29/18	MOUNT MODIFICATION DESIGN	YMA	JKM
0	10/20/17	ISSUED FOR CONSTRUCTION	JRF	PET
A	09/13/17	USED FOR REVIEW	JRF	PET



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF THE RESPONSIBLE LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.



SITE NAME: BLOOMFIELD POLICE DEPARTMENT
SITE ID: CT52XC024

785 PARK AVENUE
BLOOMFIELD, CT 06002

RED BANK OFFICE
331 Newnam Springs Road
Suite 203
Red Bank, NJ 07701-5699
Phone: 732.383.1950
Fax: 732.383.1984

SHEET TITLE: EQUIPMENT PLAN AND ELEVATION


SHEET NUMBER: ANT-005.00



EQUIPMENT PLAN



SCALE: 1" = 2'
(DO NOT SCALE 11"X17" DRAWINGS)



ELEVATION (LOOKING SOUTH)



SCALE: 1" = 10'
(DO NOT SCALE 11"X17" DRAWINGS)

LEGEND

- LIGHT LINE WORK INDICATES EXISTING OBJECTS
- HEAVY LINE WORK INDICATED PROPOSED OBJECTS



201 STATE ROUTE 17 NORTH
RUTHERFORD, NJ 07070
PHONE: (201) 684-4000 FAX: (201) 684-4223



Charles Cherundolo Consulting, Inc.
713 Clover Lane
Moscow, PA 18444
Phone: 973-207-4248
Fax: 570-842-5592



SCALE: AS SHOWN JOB NUMBER: 17924009A

NO.	DATE	DESCRIPTION	BY	CHECKED BY
4	05/03/18	REVISED PER COMMENTS	JRF	PET
3	04/27/18	REVISED PER COMMENTS	JCM	PET
2	04/11/18	REVISED PER REFS	JCM	JKM
1	01/29/18	MOUNT MODIFICATION DESIGN	YMA	JKM
0	10/20/17	ISSUED FOR CONSTRUCTION	JRF	PET
A	09/13/17	USED FOR REVIEW	JRF	PET
REV	D	DESCRIPTION	BY	CHECKED BY



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF THE RESPONSIBLE LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.


SITE NAME: BLOOMFIELD
POLICE DEPARTMENT
SITE ID: CT52XC024

785 PARK AVENUE
BLOOMFIELD, CT 06002




SHEET TITLE: ANTENNA ORIENTATION PLAN



SHEET NUMBER: ANT-006.00





NOTE:
PROPOSED ANTENNA INSTALLATION MUST MEET SPRINT GUIDELINES FOR SPACING.
CONTRACTOR TO VERIFY IN FIELD.



EXISTING ANTENNA LAYOUT
SCALE: 1" = 2'
(DO NOT SCALE 11"X17" DRAWINGS)








PROPOSED ANTENNA LAYOUT
SCALE: 1" = 2'
(DO NOT SCALE 11"X17" DRAWINGS)



MODEL	HEIGHT (H)	WIDTH (W)	DEPTH (D)	WEIGHT
ALU RRH-4x45-1900	25"	12"	12"	69.5 LBS
ALU RRH-2x50-800	16"	13"	10"	69.1 LBS

RRH SPECIFICATIONS
NOT TO SCALE



MASER CONSULTING CONNECTICUT
Customer Loyalty through Client Satisfaction
www.maserconsulting.com
Engineers ■ Planners ■ Surveyors
Landscape Architects ■ Environmental Scientists

Copyright © 2018, Maser Consulting Connecticut. All Rights Reserved. This drawing and all the information contained herein is authorized for use only by the party for whom the services were contracted or to whom it is certified. This drawing may not be copied, revised, distributed, distributed or relied upon for any other purpose without the express written consent of Maser Consulting Connecticut.

Sprint
201 STATE ROUTE 17 NORTH
RUTHERFORD, NJ 07070
PHONE: (201) 684-4000 FAX: (201) 684-4223

Cherundolo Consulting
Charles Cherundolo Consulting, Inc.
713 Clover Lane
Moscow, PA 18444
Phone: 973-207-4248
Fax: 570-842-5592

811 PROTECT YOURSELF
ALL STATES REQUIRE NOTIFICATION OF EXCAVATORS, DESIGNERS OR ANY PERSON PREPARING TO DISTURB THE EARTH'S SURFACE ANYWHERE IN ANY STATE
Know what's below. Call before you dig.
FOR STATE SPECIFIC DIRECT PHONE NUMBERS VISIT: WWW.CALL811.COM

SCALE: AS SHOWN JOB NUMBER: 17924009A

NO.	DATE	DESCRIPTION	BY	CHECKED BY
4	05/03/18	REVISED PER COMMENTS	JRF	PET
3	04/27/18	REVISED PER COMMENTS	JCM	PET
2	04/11/18	REVISED PER RFDS	JCM	JKM
1	01/29/18	MOUNT MODIFICATION DESIGN	YMA	JKM
0	10/20/17	ISSUED FOR CONSTRUCTION	JRF	PET
A	09/13/17	USED FOR REVIEW	JRF	PET
REV	D	DESCRIPTION	BY	CHECKED BY

PETROS E. TOUKALAS
CONNECTICUT LICENSED PROFESSIONAL ENGINEER - LICENSE NUMBER: PEN 38575

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF THE RESPONSIBLE LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SITE NAME: BLOOMFIELD POLICE DEPARTMENT
SITE ID: CT52XC024

785 PARK AVENUE
BLOOMFIELD, CT 06002

RED BANK OFFICE
331 Newnam Springs Road
Suite 203
Red Bank, NJ 07701-5699
Phone: 732.383.1950
Fax: 732.383.1984

SHEET TITLE: DETAILS
SHEET NUMBER: ANT-007.00

RF NOTES


- ACTUAL CABLE LENGTHS SHALL BE DETERMINED PER SITE CONDITION BY SUBCONTRACTOR.
- THE DESIGN IS BASED ON RF DATA SHEETS, SIGNED AND APPROVED.
- RADIO SIGNAL CABLE AND RACEWAY SHALL COMPLY WITH THE REQUIREMENTS OF THE NATIONAL ELECTRICAL CODE (NEC, NFPA 70), CHAPTER 8.
- ALL SPECIFIED MATERIAL FOR EACH LOCATION (E.G., OUTDOORS, INDOORS-OCCUPIED, INDOORS-UNOCCUPIED, PLENUMS, RISER SHAFTS, ETC.) SHALL BE APPROVED, LISTED, OR LABELED AS REQUIRED BY THE NEC.
- HARDLINE AND JUMPER CABLES SHALL BE SUPPORTED WITH HANGERS AND AT INTERVALS AS REQUIRED BY THE MANUFACTURER FOR 125 mph WIND SPEED AND EXPECTED ICE CONDITIONS. FOR SITES WITH TOWER HEIGHT OVER 300' OR ARE LOCATED IN THE EXTREME WEATHER/OPERATION AREAS, THE WORST CASE SCENARIO FOR 150 mph WIND SPEED AND 1" ICE CONDITION SHOULD BE APPLIED. ALL CABLES SHOULD BE SUPPORTED AT HALF THE DISTANCE OF THE MAXIMUM HANGER SPACING FROM THE CABLE CONNECTOR LOCATION TO THE 1ST HANGER. MANUFACTURER RECOMMENDED CABLE SUPPORT ACCESSORIES SHALL BE USED. PLASTIC CABLE TIES ARE NOT ACCEPTABLE. HANGER STACKING LIMIT SHOULD ALSO REFER TO VENDOR'S RECOMMENDATION.
- THE OUTDOOR CABLE SUPPORT SYSTEM SHALL BE PROVIDED WITH AN ICE SHIELD TO SUPPORT AND PROTECT ANTENNA CABLE RUNS.
- DRIP LOOPS SHALL BE REQUIRED ON ALL OUTSIDE CABLES. CABLES SHALL BE SLOPED AWAY FROM THE BUILDING OR OUTDOOR BTS CABINETS TO PREVENT WATER FROM ENTERING THROUGH THE COAXIAL CABLE PORT.
- ALL FEEDER LINE AND JUMPER CONNECTORS SHALL BE 7/16 DIN CABLE CONNECTORS THAT MEET IP68 STANDARDS.
- CONNECTORS IN INDOOR APPLICATIONS REQUIRE NO WEATHERPROOFING. OUTDOOR APPLICATIONS REQUIRE WEATHERPROOFING AND THE FOLLOWING PROCEDURES SHOULD BE FOLLOWED:

RE-ENTERABLE AND RE-SEALABLE PLASTIC ENCLOSURE APPROVED BY CABLE MANUFACTURER AND CONTRACTOR IS RECOMMENDED METHOD TO WEATHERPROOF CONNECTORS.

ALSO ACCEPTABLE IS THE USE OF BUTYL RUBBER WEATHERPROOFING KIT APPROVED BY CABLE MANUFACTURER AND CONTRACTOR. START BUTYL RUBBER TAPE APPROXIMATELY 5 INCHES FROM THE CONNECTOR AND WRAP 2 INCHES TOWARD THE CONNECTOR, THEN REVERSE THE TAPE SO THAT THE STICKY SIDE IS UP. TAPE OVER THE CONNECTOR OR SURGE ARRESTOR UNTIL THREE (3) TO FOUR (4) INCHES BEYOND THE CONNECTOR AND REVERSE AGAIN WITH THE STICKY SIDE DOWN FOR ANOTHER TWO INCHES. FINISH WITH TWO LAYERS OF VINYL TAPE. COLD SHRINK IS STRICTLY PROHIBITED. SELF-BONDING, AMALGAMATING TAPE MAYBE USED AS AN ALTERNATIVE TO BUTYL RUBBER TAPE.
- ANTENNAS SHALL BE PAINTED, WHEN REQUIRED, BY THE LANDLORD OR AUTHORITY HAVING JURISDICTION IN ACCORDANCE WITH ANTENNA MANUFACTURERS' SURFACE PREPARATION AND PAINTING REQUIREMENTS.
- CABLE SHIELDS, AND TOWER CONDUITS SHALL BE GROUNDED AT THE TOP OF THE TOWER, WITHIN 10 FEET OF THEIR CONNECTORS, AND AT THE BOTTOM OF THE TOWER ABOUT 6 INCHES BEFORE THEY TURN TOWARD THE FACILITY. THEY SHALL BE GROUNDED AT THE MIDPOINT OF TOWERS THAT ARE BETWEEN 100 FEET AND 200 FEET HIGH, AND AT INTERVALS OF 100 FEET OR LESS ON TOWERS THAT ARE HIGHER THAN 200 FEET.
- APPROVED GROUNDING KITS, WHICH INCLUDE GROUNDING STRAPS, SHALL BE USED TO GROUND THE COAXIAL CABLE SHIELDS, AND CONDUITS. THE GROUND CONDUCTORS FOR THE KITS AT THE TOP OF THE TOWER, AND IN THE MIDDLE SECTION OF THE TOWER, ARE BONDED DIRECTLY TO TOWER STEEL USING BOLTED, OR APPROVED CLAMP CONNECTIONS. EXOTHERMIC WELDS SHALL BE PERMITTED ON TOWERS ONLY WITH THE EXPRESS APPROVAL OF THE TOWER MANUFACTURER OR THE CONTRACTORS STRUCTURAL ENGINEER.
- ALL RADIO SIGNAL CABLE SHALL BE LABELED AND COLOR CODED PER MARKET REQUIREMENTS.
- ANTENNA FEED LINE SYSTEM SWEEP TESTING SHALL BE PERFORMED AND REPORTED IN ACCORDANCE WITH THE REQUIREMENTS OF PROJECT SPECIFICATIONS. CONTRACTOR WILL NOT ACCEPT A RADIO SIGNAL CABLE INSTALLATION WITH UNSATISFACTORY SWEEP TEST RESULTS.
- PIM TESTS SHALL BE PERFORMED ON NEW AND MOVED OR MODIFIED COAXIAL CABLE INSTALLATIONS. TEST SHALL BE PERFORMED AND REPORTED IN ACCORDANCE WITH PROJECT SPECIFICATIONS.
- DC CONNECTORS AT OUTDOOR BIAS-Ts OR DIPLEXER/TRIPLEXER PORTS SHALL BE WEATHERPROOFED PER MANUFACTURER RECOMMENDATIONS.
- AISG CONNECTIONS DO NOT REQUIRE ADDITIONAL WEATHERPROOFING UNLESS RECOMMENDED BY MANUFACTURER OR BY MARKET REQUIREMENTS.
- INSTALL ONLY STANDARD RF JUMPER CABLES (e.g. LDF4 OR LCF12) AT TOWER-TOP APPLICATIONS. FLEXIBLE RF CABLES (e.g. FSJ4 OR SCF12) SHALL NOT BE USED.
- CABLES AND CONNECTORS MUST BE PREPARED AND INSTALLED USING THE TOOLS RECOMMENDED BY THE COAXIAL CABLE MANUFACTURER. IT IS THE CONTRACTOR'S RESPONSIBILITY TO ENSURE THAT THE CORRECT TOOLS ARE USED FOR THE SIZE AND TYPE OF COAX AND CONNECTOR. ALL ASPECTS OF INSTALLATION OF ALL COAXIAL CABLE SHALL FOLLOW THE CABLE MANUFACTURER'S RECOMMENDATIONS, INCLUDING THOSE FOR PULLING, MOUNTING AND GROUNDING.

PROPOSED ANTENNA CONFIGURATION												
SECTOR	PROPOSED ANTENNA	TECH.	ANTENNA	HEIGHT	WIDTH	DEPTH	WEIGHT	ANTENNA	ANT. CL.	ELECTRICAL	MECHANICAL	
			STATUS	(in)	(in)	(in)	(lbs)	AZIMUTH	ELEV (ft.)	DOWNTILT	DOWNTILT	
ALPHA	A1	NOKIA AAHC	2500	REPLACED	25.6	19.7	9.64	103.7	0°	115'	2°	0°
	A2	COMMSCOPE NNVV-65B-R4	800/1900	REPLACED	72	19.6	7.8	84.7	0°	115'	3°	0°
BETA	B1	NOKIA AAHC	2500	REPLACED	25.6	19.7	9.64	103.7	120°	115'	2°	0°
	B2	COMMSCOPE NNVV-65B-R4	800/1900	REPLACED	72	19.6	7.8	84.7	120°	115'	3°	0°
GAMMA	C1	NOKIA AAHC	2500	REPLACED	25.6	19.7	9.64	103.7	240°	115'	2°	0°
	C2	COMMSCOPE NNVV-65B-R4	800/1900	REPLACED	72	19.6	7.8	84.7	240°	115'	3°	0°

BILL OF MATERIALS				
NUMBER	QUANTITY	DESCRIPTION	MANUFACTURER	MODEL NUMBER
1	3	PANEL ANTENNA	NOKIA	AAHC
2	3	PANEL ANTENNA	COMMSCOPE	NNVV-65B-R4
3	6	800MHZ RRH	ALU	RRH-2X50-800
4	3	1900MHZ RRH	ALU	RRH-2X50-1900
5	1280 LF	1-1/4"Ø HYBRID FIBER RISER (4 HYBRID CABLES TOTAL)	ALU	TBD
6	48	1/2"Ø JUMPER CABLE (8' LONG)	TBD	
7	3	0.315"Ø AISG CABLE (8' LONG)	COMMSCOPE	ATCB-B01-006
8	1	GROWTH CABINET	ELTEK	ECAB
9	1	POWER PROTECTION CABINET	ELTEK	581122212
10	1	MONOPOLE DOUBLE SUPPORT ARM KIT	SITEPRO1	RDS-23096



ANTENNA WIRING DIAGRAM
NOT TO SCALE

MASER CONSULTING CONNECTICUT
Customer Loyalty through Client Satisfaction
www.maserconsulting.com
Engineers ■ Planners ■ Surveyors
Landscape Architects ■ Environmental Scientists

Copyright © 2018, Maser Consulting Connecticut. All Rights Reserved. This drawing and all the information contained herein is authorized for use only by the party for whom the services were rendered or to whom it is certified. This drawing may not be copied, revised, distributed, or relied upon for any other purpose without the express written consent of Maser Consulting Connecticut.

Sprint
201 STATE ROUTE 17 NORTH
RUTHERFORD, NJ 07070
PHONE: (201) 684-4000 FAX: (201) 684-4223

Cherundolo Consulting
Charles Cherundolo Consulting, Inc.
713 Clover Lane
Moscow, PA 18444
Phone: 973-207-4248
Fax: 570-842-5592

811 PROTECT YOURSELF
ALL STATES REQUIRE NOTIFICATION OF EXCAVATORS, DESIGNERS OR ANY PERSON PREPARING TO DISTURB THE EARTH'S SURFACE ANYWHERE IN ANY STATE
Know what's below.
Call before you dig.
FOR STATE SPECIFIC DIRECT PHONE NUMBERS VISIT:
WWW.CALL811.COM

SCALE:	AS SHOWN	JOB NUMBER:	17924009A
--------	----------	-------------	-----------

REV	DATE	DESCRIPTION	BY	CHECKED BY
4	05/03/18	REVISED PER COMMENTS	JRF	PET
3	04/27/18	REVISED PER COMMENTS	JCM	PET
2	04/11/18	REVISED PER RFDS	JCM	JKM
1	01/29/18	MOUNT MODIFICATION DESIGN	YMA	JKM
0	10/20/17	ISSUED FOR CONSTRUCTION	JRF	PET
A	09/13/17	USED FOR REVIEW	JRF	PET

PETROS E. TOUKALAS
CONNECTICUT LICENSED PROFESSIONAL ENGINEER - LICENSE NUMBER: PEN 38578

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF THE RESPONSIBLE LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.


SITE NAME: BLOOMFIELD POLICE DEPARTMENT
SITE ID: CT52XC024

785 PARK AVENUE
BLOOMFIELD, CT 06002


RED BANK OFFICE
331 Newnam Springs Road
Suite 203
Red Bank, NJ 07701-5699
Phone: 732.383.1950
Fax: 732.383.1984

SHEET TITLE:
ANTENNA SCHEDULE, WIRING DIAGRAM, BILL OF MATERIALS AND NOTES


SHEET NUMBER:
ANT-008.00




TYPICAL FIBER DISTRIBUTION BOX DETAIL
NOT TO SCALE



RRH TO DISTRIBUTION BOX POWER CONNECTIVITY DETAIL
NOT TO SCALE



BTS TO DISTRIBUTION BOX FIBER CONNECTIVITY DETAIL
NOT TO SCALE



RRH TO DISTRIBUTION BOX FIBER CONNECTIVITY DETAIL
NOT TO SCALE

MASER CONSULTING CONNECTICUT

Customer Loyalty through Client Satisfaction
www.maserconsulting.com

Engineers ■ Planners ■ Surveyors
Landscape Architects ■ Environmental Scientists

Copyright © 2018 Maser Consulting Connecticut. All Rights Reserved. This drawing and all the information contained herein is authorized for use only by the party for whom the services were contracted or to whom it is certified. This drawing may not be copied, revised, discussed, distributed or relied upon for any other purpose without the express written consent of Maser Consulting Connecticut.

Sprint

201 STATE ROUTE 17 NORTH
RUTHERFORD, NJ 07070
PHONE: (201) 684-4000 FAX: (201) 684-4223

Cherundolo Consulting

Charles Cherundolo Consulting, Inc.
713 Clover Lane
Moscow, PA 18444
Phone: 973-207-4248
Fax: 570-842-5592

811 PROTECT YOURSELF

ALL STATES REQUIRE NOTIFICATION OF EXCAVATORS, DESIGNERS OR ANY PERSON PREPARING TO DISTURB THE EARTH'S SURFACE ANYWHERE IN ANY STATE.

Know what's below. Call before you dig.

FOR STATE SPECIFIC DIRECT PHONE NUMBERS VISIT: WWW.CALL811.COM

SCALE:	JOB NUMBER:			
AS SHOWN	17924009A			
4	05/03/18	REVISED PER COMMENTS	JRF	PET
3	04/27/18	REVISED PER COMMENTS	JCM	PET
2	04/11/18	REVISED PER RFDS	JCM	JKM
1	01/29/18	MOUNT MODIFICATION DESIGN	YMA	JKM
0	10/20/17	ISSUED FOR CONSTRUCTION	JRF	PET
A	09/13/17	USED FOR REVIEW	JRF	PET
REV	DATE	DESCRIPTION	BY	CHECKED BY

PETROS E. TOUKALAS

CONNECTICUT LICENSED PROFESSIONAL ENGINEER - LICENSE NUMBER PEN 38578

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF THE RESPONSIBLE LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SITE NAME: BLOOMFIELD POLICE DEPARTMENT
SITE ID: CT52XC024

785 PARK AVENUE
BLOOMFIELD, CT 06002

RED BANK OFFICE

331 Newnam Springs Road
Suite 203
Red Bank, NJ 07701-5699
Phone: 732.383.1950
Fax: 732.383.1984


SHEET TITLE:
FIBER PLUMBING DIAGRAMS - I

SHEET NUMBER:
ANT-009.00

Prepared By Mark Elliott	Revision Date March 13, 2018	Revision Number R1
Approved By RAN Hardware & Antenna Teams	Approval Date Final-Macro Generated	



ALU 21-MIMO NNVV-65B-R4 wo Filters



Not to Scale

ANTENNA WIRING DIAGRAM
NOT TO SCALE



Customer Loyalty through Client Satisfaction
www.maserconsulting.com
Engineers ■ Planners ■ Surveyors
Landscape Architects ■ Environmental Scientists

Copyright © 2018, Maser Consulting Connecticut. All Rights Reserved. This drawing and all the information contained herein is authorized for use only by the party for whom the services were contracted or to whom it is certified. This drawing may not be copied, revised, distributed, distributed or relied upon for any other purpose without the express written consent of Maser Consulting Connecticut.



201 STATE ROUTE 17 NORTH
RUTHERFORD, NJ 07070
PHONE: (201) 684-4000 FAX: (201) 684-4223




Charles Cherundolo Consulting, Inc.
713 Clover Lane
Moscow, PA 18444
Phone: 973-207-4248
Fax: 570-842-5592



PROTECT YOURSELF
ALL STATES REQUIRE NOTIFICATION OF EXCAVATORS, DESIGNERS, OR ANY PERSON PREPARING TO DISTURB THE EARTH'S SURFACE ANYWHERE IN ANY STATE
Know what's below.
Call before you dig.
FOR STATE SPECIFIC DIRECT PHONE NUMBERS VISIT:
WWW.CALL811.COM

SCALE: AS SHOWN JOB NUMBER: 17924009A


REV	DESCRIPTION	DATE	BY	CHECKED BY
4	REVISED PER COMMENTS	05/03/18	JRF	PET
3	REVISED PER COMMENTS	04/27/18	JCM	PET
2	REVISED PER RFDS	04/11/18	JCM	JKM
1	MOUNT MODIFICATION DESIGN	01/29/18	YMA	JKM
0	ISSUED FOR CONSTRUCTION	10/20/17	JRF	PET
A	USED FOR REVIEW	09/13/17	JRF	PET



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF THE RESPONSIBLE LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SITE NAME: BLOOMFIELD
POLICE DEPARTMENT
SITE ID: CT52XC024

785 PARK AVENUE
BLOOMFIELD, CT 06002



RED BANK OFFICE
331 Newnam Springs Road
Suite 203
Red Bank, NJ 07701-5699
Phone: 732.383.1950
Fax: 732.383.1984

SHEET TITLE:

FIBER PLUMBING DIAGRAMS - 2

SHEET NUMBER:

ANT-010.00


CABLE MARKING NOTES

- ALL CABLES SHALL BE MARKED WITH 2" WIDE, UV STABILIZED, UL APPROVED TAPE.
- THE FIRST RING SHALL BE CLOSEST TO THE END OF THE CABLE AND SPACED APPROXIMATELY 2" FROM THE END CONNECTOR, WEATHERPROOFING, OR BREAKOUT UNIT. THERE SHALL BE 1" SPACE BETWEEN EACH RING.
- A 2" GAP SHALL SEPARATE THE CABLE COLOR CODE FROM THE FREQUENCY COLOR CODE. THE 2" COLOR RINGS FOR THE FREQUENCY CODE SHALL BE PLACED NEXT TO EACH OTHER WITH NO SPACES.
- THE 2" COLORED TAPE(S) SHALL BE WRAPPED A MINIMUM OF 3 TIMES AROUND THE INDIVIDUAL CABLES, AND THE TAPE SHALL BE KEPT IN THE SAME LOCATION AS MUCH AS POSSIBLE.
- SITES WITH MORE THAN FOUR (4) SECTORS WILL REQUIRE ADDITIONAL RINGS FOR EACH SECTOR FOLLOWING THE PATTERN. HIGH CAPACITY SITES WILL USE THE SECOND CABLE IDENTIFIED BY BLUE BANDS OF TAPE.
- HYBRID FIBER CABLE SHALL BE SECTOR IDENTIFIED INSIDE THE CABINET ON FREQUENCY BUNDLES, ON THE SEALTITE, ON THE MAIN LINE UPON EXIT OF SEALTITE, AND BEFORE AND AFTER THE BREAKOUT UNIT (MEDUSA), AS WELL AS BEFORE AND AFTER ANY ENTRANCE OR EXIT.
- HFC "MAIN TRUNK" WILL NOT BE MARKED WITH THE FREQUENCY CODES, AS IT CONTAINS ALL FREQUENCIES.
- INDIVIDUAL POWER PAIRS AND FIBER BUNDLES SHALL BE LABEL.


2.5 FREQUENCY	INDICATOR		ID
2500 -1	YEL	WHT	GRN
2500 -2	YEL	WHT	RED
2500 -3	YEL	WHT	BRN
2500 -4	YEL	WHT	BLU
2500 -5	YEL	WHT	SLT
2500 -6	YEL	WHT	ORG
2500 -7	YEL	WHT	WHT
2500 -8	YEL	WHT	PPL

NV FREQUENCY	INDICATOR	ID
800-1	YEL	GRN
1900-1	YEL	RED
1900-2	YEL	BRN
1900-3	YEL	BLU
1900-4	YEL	SLT
800-1	YEL	ORG
RESERVED	YEL	WHT
RESERVED	YEL	PPL


Sector	Cable	First Ring	Second Ring	Third Ring
1 Alpha	1	Green	No Tape	No Tape
	2	Blue	No Tape	No Tape
	3	Brown	No Tape	No Tape
	4	White	No Tape	No Tape
	5	Red	No Tape	No Tape
	6	Grey	No Tape	No Tape
	7	Purple	No Tape	No Tape
	8	Orange	No Tape	No Tape
2 Beta	1	Green	Green	No Tape
	2	Blue	Blue	No Tape
	3	Brown	Brown	No Tape
	4	White	White	No Tape
	5	Red	Red	No Tape
	6	Grey	Grey	No Tape
	7	Purple	Purple	No Tape
	8	Orange	Orange	No Tape
3 Gamma	1	Green	Green	Green
	2	Blue	Blue	Blue
	3	Brown	Brown	Brown
	4	White	White	White
	5	Red	Red	Red
	6	Grey	Grey	Grey
	7	Purple	Purple	Purple
	8	Orange	Orange	Orange



COLOR CODING CHARTS
NOT TO SCALE



DC ONE-LINE DIAGRAM
NOT TO SCALE



- NOTES:
- CIRCUIT BREAKER, NUMBERS 4, 8, AND 12 ARE TO BE USED UNLESS THIRD DC RAIL IS REQUIRED FOR MICROWAVE.
 - USE DC POWER LOOP.
 - ALL UNUSED DC FEEDERS TO BE TERMINATED WITH WIRE NUTS AND TAPED.
 - REMOVE ALL DEBRIS FROM INTERIOR OF FIBER DISTRIBUTION BOX WHEN COMPLETE.

TYPICAL FIBER DISTRIBUTION
NOT TO SCALE



Customer Loyalty through Client Satisfaction
www.maserconsulting.com
Engineers ■ Planners ■ Surveyors
Landscape Architects ■ Environmental Scientists

Copyright © 2018, Maser Consulting Connecticut. All Rights Reserved. This drawing and all the information contained herein is authorized for use only by the party for whom the services were rendered or to whom it is certified. This drawing may not be copied, revised, distributed, reproduced or relied upon for any other purpose without the express written consent of Maser Consulting Connecticut.



201 STATE ROUTE 17 NORTH
RUTHERFORD, NJ 07070
PHONE: (201) 684-4000 FAX: (201) 684-4223



Charles Cherundolo Consulting, Inc.
713 Clover Lane
Moscow, PA 18444
Phone: 973-207-4248
Fax: 570-842-5592



SCALE: AS SHOWN JOB NUMBER: 17924009A

REV	DATE	DESCRIPTION	BY	CHECKED BY
4	05/03/18	REVISED PER COMMENTS	JRF	PET
3	04/27/18	REVISED PER COMMENTS	JCM	PET
2	04/11/18	REVISED PER RFDS	JCM	JKM
1	01/29/18	MOUNT MODIFICATION DESIGN	YMA	JKM
0	10/20/17	ISSUED FOR CONSTRUCTION	JRF	PET
A	09/13/17	USED FOR REVIEW	JRF	PET
REV	D	DESCRIPTION	BY	CHECKED BY



IT IS A VOLUNTARY OF LAW IN ANY JURISDICTION, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF THE RESPONSIBLE LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SITE NAME: BLOOMFIELD POLICE DEPARTMENT
SITE ID: CT52XC024

785 PARK AVENUE
BLOOMFIELD, CT 06002



RED BANK OFFICE
331 Newmar Springs Road
Suite 203
Red Bank, NJ 07701-5699
Phone: 732.383.1950
Fax: 732.383.1984

SHEET TITLE: CABLE COLOR CODING, DC POWER DETAILS & PANEL SCHEDULES

SHEET NUMBER: ANT-011.00

GENERAL REQUIREMENTS:

1. THE WORK TO BE DONE UNDER THIS PROJECT INCLUDES PROVIDING ALL EQUIPMENT, MATERIALS, LABOR AND SERVICES, AND PERFORMING ALL OPERATIONS FOR COMPLETE AND OPERATING SYSTEMS. ANY WORK NOT SPECIFICALLY COVERED BY NECESSARY TO COMPLETE THIS INSTALLATION, SHALL BE PROVIDED. ALL EQUIPMENT AND WIRING TO BE NEW AND PROVIDED UNDER THIS CONTRACT UNLESS OTHERWISE NOTED.
2. ENTIRE INSTALLATION, INCLUDING MATERIALS, EQUIPMENT AND WORKMANSHIP, SHALL CONFORM TO THE 2011 EDITION OF THE NATIONAL ELECTRIC CODE (NEC) AS WELL AS ALL APPLICABLE LAWS AND REGULATIONS AND REGULATORY BODIES HAVING JURISDICTION OVER THIS WORK.
3. THE TERM "FURNISH" SHALL MEAN TO OBTAIN AND SUPPLY THE JOB SITE. THE TERM "INSTALL" SHALL MEAN TO FIX IN POSITION AND CONNECT FOR USE. THE TERM "PROVIDE" SHALL MEAN TO FURNISH AND INSTALL. THE TERM "CONTRACTOR" SHALL MEAN ELECTRICAL CONTRACTOR.
4. ONLY WRITTEN CHANGES AND/OR MODIFICATIONS APPROVED BY THE ENGINEER, CONSULTING ENGINEER OR OWNER'S REPRESENTATIVE WILL BE RECOGNIZED.
5. THE ELECTRICAL CONTRACTOR SHALL SUBMIT, FOR THE ENGINEER'S APPROVAL, DETAILED SHOP DRAWINGS OF ALL EQUIPMENT SPECIFIED.
6. CONTRACTOR SHALL COORDINATE WITH SPECIFICATIONS BY OTHER TRADES.
7. PROVIDE OPERATING AND MAINTENANCE MANUALS, PER SPECIFICATIONS, AND GIVE INSTRUCTIONS TO USER FOR ALL EQUIPMENT AND SYSTEMS PROVIDED UNDER THIS CONTRACT AFTER ALL ARE CLEANED AND OPERATING.
8. KEEP PREMISES FREE FROM RUBBISH. REMOVE ALL ELECTRICAL RUBBISH FROM SITE.
9. ALL WORK SHALL BE INSTALLED CONCEALED UNLESS OTHERWISE NOTED.
10. THE WORK SHALL INCLUDE ALL PANELS, DEVICES, FEEDERS AND BRANCH CIRCUIT WIRING AS REQUIRED FOR THE DISTRIBUTION SYSTEM INDICATED AND CALLED FOR ON THE DRAWINGS. REQUIRED BY SPECIFICATIONS AND AS NECESSARY FOR COMPLETE FUNCTIONAL SYSTEMS PRESENTED AND INTENDED.
11. THE CONTRACTOR SHALL FURNISH ALL MATERIAL, LABOR, TOOLS, EQUIPMENT, CONSUMABLES AND SERVICES REQUIRED FOR OBTAINING, DELIVERY, INSTALLATION, CONNECTION, DISCONNECTION, REMOVAL, RELOCATION, REPAIR, REPLACEMENT, TESTING AND COMMISSIONING OF ALL EQUIPMENT AND DEVICES INCLUDED IN OR NECESSARY FOR THE WORK, AS APPLICABLE. THIS INCLUDES SCAFFOLDING, LADDERS, RIGGING, HOISTING, ETC.
12. ELECTRICAL WORK SHALL INCLUDE ALL REQUIRED CUTTING, PATCHING AND THE FULL RESTORATION OF WALL AND FLOOR STRUCTURE AND SURFACES. ALL EQUIPMENT, WALLS, FLOORS, ETC., DISTURBED OR DAMAGED DURING CONSTRUCTION SHALL BE REPAIRED TO THE SATISFACTION OF THE OWNER, AT THE CONTRACTORS EXPENSE.
13. BEFORE SUBMITTING HIS BID, THE CONTRACTOR SHALL FULLY ACQUAINT HIMSELF/HERSELF WITH THE JOB CONDITIONS AND DIFFICULTIES THAT WILL PERTAIN TO THE EXECUTION OF THIS WORK. SUBMISSION OF A PROPOSAL WILL BE CONSTRUED AS EVIDENCE THAT SUCH AN EXAMINATION HAS BEEN MADE. LATER CLAIMS WILL NOT BE RECOGNIZED FOR EXTRA LABOR, EQUIPMENT OR MATERIALS REQUIRED BECAUSE OF DIFFICULTIES ENCOUNTERED, WHICH COULD NOT HAVE BEEN FORESEEN HAD SUCH AN EXAMINATION BEEN MADE.
14. THE CONTRACTOR SHALL CONFIRM THE LOCATION OF ALL UTILITIES. THE CONTRACTOR IS RESPONSIBLE FOR REPAIRING ANY DAMAGE TO EXISTING UTILITIES.
15. UPON COMPLETION OF THE ELECTRICAL WORK, THE CONTRACTOR SHALL TEST THE COMPLETE ELECTRICAL SYSTEM FOR SHORTS, GROUNDS, AND PROPER OPERATION, IN THE PRESENCE OF THE OWNER'S REPRESENTATIVE.
16. UPON COMPLETION OF WORK, THE CONTRACTOR SHALL CLEAN AND ADJUST ALL EQUIPMENT AND LIGHTING AND TEST SYSTEMS TO THE SATISFACTION OF OWNER AND ENGINEER. RESULTS SHALL BE SUBMITTED TO THE ENGINEER FOR APPROVAL.
17. THE CONTRACTOR SHALL FIELD VERIFY DIMENSIONS OF FINISHED CONSTRUCTION PRIOR TO FABRICATION AND INSTALLATION OF FIXTURES AND EQUIPMENT.
18. EXACT ROUTING OF CONDUITS AND "MC" CABLES SHALL BE DETERMINED IN THE FIELD.
19. IF THE OWNER AND/OR HIS REPRESENTATIVE CONSIDERS ANY WORK TO BE INFERIOR, THE RESPECTIVE CONTRACTOR SHALL REPLACE SAME WITH CONTRACT STANDARD WORK WITHOUT ADDITIONAL CHARGE. ALL WORK SHALL BE DONE IN A NEAT, WORKMANLIKE MANNER. LEFT CLEAN AND FREE FROM DEFECTS, AND COMPLETELY OPERABLE.
20. THE CONTRACTOR SHALL PROVIDE ALL MATERIALS AS SHOWN ON THE DRAWINGS AND/OR AS SPECIFIED. ALL MATERIALS SHALL BE NEW, AND BEAR THE UL LABEL. ALL WORK SHALL BE GUARANTEED BY THE CONTRACTOR FOR A PERIOD OF ONE (1) YEAR FROM THE DATE OF ACCEPTANCE BY THE OWNER.
21. DRAWINGS ARE TO BE CONSIDERED DIAGRAMMATIC, AND SHALL BE FOLLOWED AS CLOSELY AS CONDITIONS ALLOW TO COMPLETE THE INTENT OF THE CONTRACT. THE DRAWINGS AND SPECIFICATIONS COMPLIMENT AND VICE VERSA, IS TO BE INCLUDED IN THE SCOPE OF WORK.
22. ALL EQUIPMENT CONNECTIONS SHALL BE INSTALLED PER APPLICABLE SEISMIC REQUIREMENTS.
23. ENGINEER WILL MAKE A FINAL INSPECTION WITH THE OWNER AND CONTRACTOR AND WILL NOTIFY THE CONTRACTOR IN WRITING OF ALL PARTICULARS IN WHICH THIS INSPECTION REVEALS THAT THE WORK IS INCOMPLETE OR DEFECTIVE. THE CONTRACTOR SHALL IMMEDIATELY TAKE SUCH MEASURES AS ARE NECESSARY TO COMPLETE SUCH WORK OR REMEDY SUCH DEFICIENCIES.
24. THE CONTRACTOR SHALL PERFORM ALL EXCAVATION, TRENCHING, AND BACKFILL AS REQUIRED FOR ELECTRICAL WORK. BACKFILL SHALL BE SUITABLE MATERIAL PROPERLY COMPACTED TO 95% DENSITY IN EACH LAYER OF SIX (6) INCH DEPTH. CONDUIT SHALL BE MINIMUM 36" BELOW FINISHED GRADE.

PROJECT COORDINATION:

1. THE CONTRACTOR SHALL VERIFY FIELD CONDITIONS AT THE SITE AND NOTIFY THE OWNER OF ANY DISCREPANCIES, PRIOR TO COMMENCING WITH THE WORK.
2. THE CONTRACTOR SHALL REVIEW AND COORDINATE WITH THE DOCUMENTS OF ALL TRADES.
3. THE CONTRACTOR SHALL FURNISH A SCHEDULE INDICATING HIS PORTION OF TIME, WITHIN THE OVERALL SCHEDULE, REQUIRED TO COMPLETE THE WORK, IN CONJUNCTION WITH ALL TRADES. ALL WORK THAT MAY AFFECT OPERATION OF BUILDING SYSTEMS SHALL BE COORDINATED WITH THE OWNER'S REPRESENTATIVE.
4. SHUT DOWN OF POWER SHALL BE COORDINATED WITH THE OWNER, ARCHITECT AND PROJECT MANAGER AT LEAST 14 WORKING DAYS PRIOR TO SHUT DOWN. SHUT DOWNS LONGER THAN 2 DAYS SHALL BE COORDINATED WITH THE ABOVE PERSONNEL AT LEAST ONCE A MONTH IN ADVANCE. TEMPORARY POWER FOR CONSTRUCTION SHALL BE PROVIDED BY THE ELECTRICAL CONTRACTOR FOR SHUT DOWNS OVER 2 DAYS.
5. ALL CONDUITS AND DEVICE BOXES SHALL BE PROVIDED BY THE ELECTRICAL CONTRACTOR, INCLUDING ALL TECHNOLOGY CONDUITS AND BOXES.
6. INSTALL NEW WORK AND CONNECT TO EXISTING WORK WITH MINIMUM INTERFERENCE TO EXISTING FACILITIES. ALARM AND EMERGENCY SYSTEMS SHALL NOT BE INTERRUPTED. TEMPORARY SHUT DOWNS OF ANY SYSTEMS SHALL BE COORDINATED WITH AND APPROVED BY THE OWNER AND ARCHITECT.

PROTECTION OF WORK:

1. EFFECTIVELY PROTECT ALL MATERIALS AND EQUIPMENT FROM ENVIRONMENTAL AND PHYSICAL DAMAGE UNTIL FINAL ACCEPTANCE. CLOSE AND PROTECT ALL OPENINGS DURING CONSTRUCTION. PROVIDE NEW MATERIALS AND EQUIPMENT TO REPLACE ITEMS DAMAGED.

WARRANTIES AND BONDS:

1. ALL MATERIALS, EQUIPMENT AND WORKMANSHIP SHALL BE GUARANTEED IN WRITING FOR A MINIMUM OF ONE YEAR AFTER FINAL ACCEPTANCE BY OWNER.
2. OBTAIN AND DELIVER TO THE OWNER'S REPRESENTATIVE ALL GUARANTEES AND CERTIFICATES OF COMPLIANCE.

PERMITS:

1. CONTRACTOR SHALL OBTAIN AND PAY FOR ALL REQUIRED PERMITS AND INSPECTION FEES FOR ELECTRICAL WORK.

RACEWAYS:


1. ALL CONDUIT SHALL BE MINIMUM SIZE OF 3/4" FOR POWER CIRCUITS AND CONTROL CIRCUITS EXCEPT WHERE FLEXIBLE CONDUIT IS CALLED FOR ON PROJECT DOCUMENTS. ALL EXTERIOR EXPOSED CONDUIT SHALL BE GRC (GALVANIZED RIGID METAL CONDUIT). ALL UNDERGROUND, IN SLAB OR UNDER SLAB SHALL BE RNC (RIGID NONMETALLIC CONDUIT). CHANGE RIGID METALLIC CONDUIT FOR INTERMEDIATE METALLIC CONDUIT BEFORE EXITING OUT OF CONCRETE OR PENETRATING A WALL, FLOOR OR ROOF. EMT IS ALLOWED IN INTERIOR DRY LOCATIONS WHERE NOT SUBJECT TO DAMAGE.
2. ALL FLEXIBLE CONDUIT IN WET OR DRY AREAS SHALL BE LIQUID TIGHT CONDUIT. NONMETALLIC FLEXIBLE CONDUIT IS SPECIFICALLY PROHIBITED.
3. CONDUIT SHALL BE RUN AT RIGHT ANGLES AND PARALLEL TO BUILDING LINES, SHALL BE NEATLY RACKED AND SECURELY FASTENED. JUNCTION BOXES SHALL BE PROVIDED WHERE REQUIRED TO FACILITATE INSTALLATION OF WIRES.
4. ALL CONDUIT AND ELECTRICAL EQUIPMENT SHALL BE SUPPORTED FROM THE BUILDING STRUCTURE IN AN APPROVED MANNER.
5. ALL EMPTY RACEWAYS SHALL BE FURNISHED WITH A 200 LB. TEST NYLON DRAG LINE.
6. ARRANGEMENT OF CONDUIT AND EQUIPMENT SHALL BE AS INDICATED, UNLESS MODIFICATION IS REQUIRED TO AVOID INTERFERENCES.
7. FOR CONDUITS CROSSING EXPANSION JOINTS, PROVIDE EXPANSION FITTINGS FOR SIZE 1 1/4" AND LARGER. PROVIDE SECTIONS OF FLEXIBLE CONDUIT WITH GROUNDING JUMPERS FOR SIZES 1" AND SMALLER.
8. THE CONTRACTOR SHALL INSTALL DETECTABLE UNDERGROUND TAPES FOR THE PROTECTION, LOCATION AND IDENTIFICATION OF UNDERGROUND CONDUIT INSTALLATION.
9. EXACT ROUTING OF CONDUITS AND CABLES SHALL BE DETERMINED IN FIELD.

WIRING:

1. ALL WIRE SHALL BE COPPER WITH TYPE THHN/THWN 600 VOLT INSULATION, MINIMUM #12 AWG FOR POWER AND LIGHTING CIRCUITS AND #16 AWG FOR CONTROL CIRCUITS.
2. UNDER NO CIRCUMSTANCES SHALL FEEDERS BE SPLICED.
3. ALL COMPUTER CIRCUITS SHALL HAVE SEPARATE NEUTRAL CONDUCTORS. ALL OTHER CIRCUITS MAY SHARE GROUND AND NEUTRAL CONDUCTORS.
4. WHERE EQUIPMENT, LIGHTING FIXTURES AND WIRING DEVICES ARE SHOWN WITH CIRCUIT NUMBERS ONLY, THE MINIMUM BRANCH CIRCUITING REQUIREMENTS SHALL BE AS FOLLOWS.
5. CONTRACTOR SHALL INCREASE SIZE OF CIRCUIT WIRING/CONDUCTORS TO COMPENSATE FOR VOLTAGE DROP.
6. WIRE SIZES SHALL BE INCREASED TO COMPENSATE FOR VOLTAGE DROP AS FOLLOWS:

GROUNDING:

1. PROVIDE A COMPLETE EQUIPMENT GROUND SYSTEM FOR THE ELECTRICAL SYSTEM AS REQUIRED BY ARTICLE 250, OF THE NEC, AND AS SPECIFIED HEREIN.
2. ALL BRANCH CIRCUITS FOR POWER WIRING SHALL CONTAIN A COPPER GROUND WIRE. NO FLEXIBLE METAL CONDUIT OF ANY KIND OR LENGTH SHALL BE USED AS THE EQUIPMENT GROUNDING CONDUCTOR.
3. THE EQUIPMENT BONDING JUMPER SHALL BE PERMITTED TO BE INSTALLED INSIDE OR OUTSIDE OF A RACEWAY OR ENCLOSURE. WHERE INSTALLED ON OUTSIDE, THE LENGTH OF THE EQUIPMENT BONDING JUMPER SHALL NOT EXCEED 6 FEET AND SHALL BE ROUTED WITH THE RACEWAY OR ENCLOSURE. REFER TO NEC 2011 - 250.102 (E)
4. ALL GROUNDING DEVICES SHALL BE U.L. APPROVED OR LISTED FOR THEIR INTENDED USE.
5. ALL WIRES SHALL BE AWG THHN/THWN COPPER UNLESS NOTED OTHERWISE.
6. GROUNDING CONNECTIONS TO GROUND RODS, GROUND RING WIRE, TOWER BASE AND FENCE POSTS SHALL BE EXOTHERMIC ("CADWELDS") UNLESS NOTED OTHERWISE. CLEAN SURFACES TO SHINY METAL. WHERE GROUND WIRES ARE CADWELDED TO GALVANIZED SURFACES, SPRAY CADWELD WITH GALVANIZING PAINT.
7. GROUNDING CONNECTIONS TO GROUND BARS ARE TO BE TWO-HOLE BRASS MECHANICAL CONNECTORS WITH STAINLESS STEEL HARDWARE (INCLUDE SCREW SET). CLEAN GROUND BAR TO SHINY METAL. AFTER MECHANICAL CONNECTION, TREAT WITH PROTECTIVE ANTIOXIDANT COATING.
8. GROUND COAXIAL CABLE SHIELDS AT BOTH ENDS WITH MANUFACTURERS' GROUNDING KITS.
9. ROUTE GROUNDING CONDUCTORS THE SHORTEST AND STRAIGHTEST PATH POSSIBLE. BEND GROUNDING LEADS WITH A MINIMUM 12" RADIUS.
10. INSTALL #2 AWG GREEN-INSULATED STRANDED WIRE FOR ABOVE GRADE GROUNDING AND #2 BARE TINNED COPPER WIRE FOR BELOW GRADE GROUNDING UNLESS OTHERWISE NOTED.
11. GROUNDING CONNECTIONS SHALL BE EXOTHERMIC TYPE ("CADWELDS") TO GROUND RING. REMAINING GROUNDING CONNECTIONS SHALL BE COMPRESSION FITTINGS. CONNECTIONS TO GROUND BARS SHALL BE MADE WITH TWO-HOLE LUGS.
12. EXOTHERMIC WELDS SHALL BE MADE IN ACCORDANCE WITH ERICO PRODUCTS BULLETIN A-A1.
13. CONSTRUCTION OF GROUND RING AND CONNECTIONS TO EXISTING GROUND RING SYSTEM SHALL BE DOCUMENTED WITH PHOTOGRAPHS PRIOR TO BACKFILLING SITE. PROVIDE PHOTOS TO CARRIER'S CONSTRUCTION MANAGER.
14. ALL GROUND LEADS EXCEPT THOSE TO THE EQUIPMENT ARE TO BE #2/0 TINNED. ALL EXTERIOR GROUND BARS TINNED COPPER.
15. PRIOR TO INSTALLING LUGS ON GROUND WIRES, APPLY THOMAS & BETTS KOPR-SHIELD (TM OF JET LUBE INC.) PRIOR TO BOLTING GROUND WIRE LUGS TO GROUND BARS, APPLY KOPR-SHIELD OR EQUAL.
16. ENGAGE IN INDEPENDENTLY ELECTRICAL TESTING FIRM TO TEST AND VERIFY THAT IMPEDANCE DOES NOT EXCEED FIVE OHMS TO GROUND BY MEANS OF "FALL OF POTENTIAL TEST". TEST SHALL BE WITNESSED BY CARRIER REPRESENTATIVE, AND RECORDED ON CARRIER'S "GROUND RESISTANCE TEST" FORM.
17. WHERE BARE COPPER GROUND WIRES ARE ROUTED FROM ANY CONNECTION ABOVE GRADE TO GROUND RING, INSTALL WIRE IN 3/4" PVC SLEEVE, FROM 1' BELOW GRADE AND SEAL TOP WITH SILICONE MATERIAL.
18. PREPARE ALL BONDING SURFACES FOR GROUNDING CONNECTIONS BY REMOVING ALL PAINT AND CORROSION DOWN TO SHINY METAL FOLLOWING CONNECTION, APPLY APPROPRIATE ANTI-OXIDIZATION PAINT.
19. ANY SITE WHERE THE EQUIPMENT (BTS, CABLE BRIDGE, PPC, GENERATOR, ETC.) IS LOCATED WITHIN 6 FEET OF METAL FENCING THE BGR SHALL BE BONDED TO THE NEAREST FENCE POST USING (2) RUNS OF #2 BARE TINNED COPPER WIRE.




NOTES:

1. SERVICE POWER SHALL BE 240VAC, 200A, 1Ø, 3W OR 208VAC, 200A, 1Ø, 3W.
2. POWER & TELEPHONE CONDUIT INSTALLATION SHALL BE COORDINATED WITH THE UTILITY COMPANIES.
3. CONTRACTOR SHALL INSTALL (1) 100 AMP DUAL POLE BREAKER IN EXISTING PANEL FOR PROPOSED GROWTH CABINET. BREAKER INTERRUPTING RATING SHALL MATCH EXISTING PANEL BOARD.

POWER RISER DIAGRAM

NOT TO SCALE



LEGEND:

1. USE PROPOSED 100A 2 POLE BREAKER IN PROPOSED PPC. INSTALL (3) #3 AWG OR LARGER.
2. CONTRACTOR TO PROVIDE (1) 2\"/>

EQUIPMENT RISER DIAGRAM DETAIL

NOT TO SCALE

**PRELIMINARY ELECTRIC SCHEMATIC SHOWN
PENDING - LOAD STUDY AND VERIFICATION
OF EXISTING SERVICE CAPACITY**



Customer Loyalty through Client Satisfaction
www.maserconsulting.com
Engineers ■ Planners ■ Surveyors
Landscape Architects ■ Environmental Scientists

Copyright © 2018, Maser Consulting Connecticut. All Rights Reserved. This drawing and all the information contained herein is authorized for use only by the party for whom the services were rendered or to whom it is certified. This drawing may not be copied, revised, duplicated, distributed or relied upon for any other purpose without the express written consent of Maser Consulting Connecticut.



201 STATE ROUTE 17 NORTH
RUTHERFORD, NJ 07070
PHONE: (201) 684-4000 FAX: (201) 684-4223




Charles Cherundolo Consulting, Inc.
713 Clover Lane
Moscow, PA 18444
Phone: 973-207-4248
Fax: 570-842-5592



SCALE: AS SHOWN JOB NUMBER: 17924009A

NO.	DATE	DESCRIPTION	BY	CHECKED BY
4	05/03/18	REVISED PER COMMENTS	JRF	PET
3	04/27/18	REVISED PER COMMENTS	JCM	PET
2	04/11/18	REVISED PER RFDS	JCM	JKM
1	01/29/18	MOUNT MODIFICATION DESIGN	YMA	JKM
0	10/20/17	ISSUED FOR CONSTRUCTION	JRF	PET
A	09/13/17	USED FOR REVIEW	JRF	PET
REV	D	DESCRIPTION	BY	CHECKED BY



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF THE RESPONSIBLE LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.


**SITE NAME: BLOOMFIELD
POLICE DEPARTMENT
SITE ID: CT52XC024**

**785 PARK AVENUE
BLOOMFIELD, CT 06002**



SHEET TITLE:
**ELECTRICAL AND
GROUNDING NOTES**


SHEET NUMBER:
ANT-012.00




GROUNDING SCHEMATIC
NOT TO SCALE

ANTENNA GROUNDING NOTES:



1. NEW ANTENNAS (ALL SECTORS).
2. ANTENNA MAST.
3. NEW JUMPER CABLE (TYP. 1 PER NEW ANTENNA).
4. NEW HYBRID CABLE GROUNDING KIT. DO NOT INSTALL ON BENDS.
5. CAD WELD.
6. REMOTE RADIO HEAD/FILTER.
7. NEW HYBRID CABLE TO FIBER MANAGEMENT BOX.
8. ANTENNA GROUND BAR.
9. #2 AWG TINNED SOLID GROUND WIRE CADWELDED TO PIPE MAST, DBL. LUG TO GROUND BAR.
10. SOLID TINNED COPPER CONDUCTOR.
11. GROUND BAR, INTERCONNECT TO ALL ANTENNA GROUND BARS. (NOT PRESENT ON ALL SITES)
12. #2/0 STRANDED GREEN GROUND WIRE INTERCONNECT WITH MASTER GROUND BAR.




ANTENNA GROUNDING SCHEMATIC
NOT TO SCALE



TYPICAL GROUND BAR CONNECTION DETAIL
NOT TO SCALE



CABLE WRAPPING DETAIL
NOT TO SCALE



GROUND BAR DETAIL
NOT TO SCALE

MASER CONSULTING CONNECTICUT
Customer Loyalty through Client Satisfaction
www.maserconsulting.com
Engineers ■ Planners ■ Surveyors
Landscape Architects ■ Environmental Scientists

Copyright © 2018, Maser Consulting Connecticut. All Rights Reserved. This drawing and all the information contained herein is authorized for use only by the party for whom the services were rendered or to whom it is certified. This drawing may not be copied, revised, distributed, reworked or relied upon for any other purpose without the express written consent of Maser Consulting Connecticut.

Sprint
201 STATE ROUTE 17 NORTH
RUTHERFORD, NJ 07070
PHONE: (201) 684-4000 FAX: (201) 684-4223

Cherundolo Consulting
Charles Cherundolo Consulting, Inc.
713 Clover Lane
Moscow, PA 18444
Phone: 973-207-4248
Fax: 570-842-5592

811 PROTECT YOURSELF
ALL STATES REQUIRE NOTIFICATION OF EXCAVATORS, DESIGNERS OR ANY PERSON PREPARING TO DISTURB THE EARTH'S SURFACE ANYWHERE IN ANY STATE
Know what's below. Call before you dig.
FOR STATE SPECIFIC DIRECT PHONE NUMBERS VISIT: WWW.CALL811.COM

SCALE:	JOB NUMBER:			
AS SHOWN	17924009A			
4	05/03/18	REVISED PER COMMENTS	JRF	PET
3	04/27/18	REVISED PER COMMENTS	JCM	PET
2	04/11/18	REVISED PER RFDS	JCM	JKM
1	01/29/18	PROJECT MODIFICATION DESIGN	YMA	JKM
0	10/20/17	ISSUED FOR CONSTRUCTION	JRF	PET
A	09/13/17	USED FOR REVIEW	JRF	PET
REV	DESCRIPTION	DATE	DRAWN BY	CHECKED BY

PETROS E. TOUKALAS
CONNECTICUT LICENSED PROFESSIONAL ENGINEER - LICENSE NUMBER: PEN 3857




IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF THE RESPONSIBLE LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SITE NAME: BLOOMFIELD POLICE DEPARTMENT
SITE ID: CT52XC024

785 PARK AVENUE
BLOOMFIELD, CT 06002

RED BANK OFFICE
331 Newman Springs Road
Suite 203
Red Bank, NJ 07701-5699
Phone: 732.383.1950
Fax: 732.383.1984

SHEET TITLE:
GROUNDING SCHEMATIC AND DETAILS
SHEET NUMBER:
ANT-013.00



ANTENNA AND RRH MOUNTING DETAIL
NOT TO SCALE

PARTS LIST						
ITEM	QTY	PART NO.	PART DESCRIPTION	LENGTH	UNIT WT.	NET WT.
1	3	X-LWRM	RING MOUNT WELDMENT		68.81	206.42
2	9	G58R-48	5/8" x 48" THREADED ROD (HDG.)		0.40	3.59
2	9	G58R-24	5/8" x 24" THREADED ROD (HDG.)		0.40	3.59
3	30	A58FW	5/8" HDG A325 FLATWASHER		0.03	1.02
4	30	G58LW	5/8" HDG LOCKWASHER		0.03	0.78
5	30	A58NUT	5/8" HDG A325 HEX NUT		0.13	3.90
6	3	P348	3-1/2" X 48" SCH 40 GALVANIZED PIPE	48	31.89	95.68
7	3	X-WWM01	8" STAND-OFF ARM / WALL MOUNT		18.12	54.37
8	12	A582112	5/8" x 2-1/2" HDG A325 HEX BOLT	2.5	0.33	4.01
9	12	X-UB1300	1/2" X 3" X 5" X 2" GALV U-BOLT		0.74	8.86
10	12	X-UB1306	1/2" X 3-5/8" X 6" X 3" GALV U-BOLT		0.83	9.94
11	6	X-UB1358	1/2" X 3-5/8" X 5-1/2" X 3" GALV U-BOLT		0.77	4.63
12	60	G12FW	1/2" HDG USS FLATWASHER		0.03	2.04
13	60	G12LW	1/2" HDG LOCKWASHER		0.01	0.83
14	60	G12NUT	1/2" HDG HEAVY 2H HEX NUT		0.07	4.30
15	6	B	C	D	E	F
16	6	X-SP219	SMALL SUPPORT CROSS PLATE	8.250 in	8.61	51.66

2-7/8" MOUNTING PIPES						
ASSEMBLY "A"	PART NO "B"	PART DESCRIPTION "C"	LENGTH "D"	UNIT WEIGHT "	NET WEIGHT "F"	TOTAL WEIGHT
RDS-23072	P3072	2 7/8" O.D. VERTICAL MOUNTING PIPE	72"	70.47#	422.82#	885.61#
RDS-23084	P3084	2 7/8" O.D. VERTICAL MOUNTING PIPE	84"	82.22#	493.32#	956.11#
RDS-23096	P3096	2 7/8" O.D. VERTICAL MOUNTING PIPE	96"	93.96#	563.76#	1026.55#

DOUBLE SUPPORT ARM KIT (SITEPRO PART # RDS-23096)
NOT TO SCALE

MASER CONSULTING CONNECTICUT
 Customer Loyalty through Client Satisfaction
 www.maserconsulting.com
 Engineers ■ Planners ■ Surveyors
 Landscape Architects ■ Environmental Scientists

Copyright © 2018, Maser Consulting Connecticut. All Rights Reserved. This drawing and all the information contained herein is authorized for use only by the party for whom the services were contracted or to whom it is certified. This drawing may not be copied, reused, disseminated, distributed or relied upon for any other purpose without the express written consent of Maser Consulting Connecticut.

Sprint
 201 STATE ROUTE 17 NORTH
 RUTHERFORD, NJ 07070
 PHONE: (201) 684-4000 FAX: (201) 684-4223

Cherundolo Consulting
 Charles Cherundolo Consulting, Inc.
 713 Clover Lane
 Moscow, PA 18444
 Phone: 973-207-4248
 Fax: 570-842-5592

811 PROTECT YOURSELF
 ALL STATES REQUIRE NOTIFICATION OF EXCAVATORS, DESIGNERS OR ANY PERSON PREPARING TO DISTURB THE EARTH'S SURFACE ANYWHERE IN ANY STATE.
 Know what's below. Call before you dig.
 FOR STATE SPECIFIC DIRECT PHONE NUMBERS VISIT: WWW.CALL811.COM

SCALE:	AS SHOWN	JOB NUMBER:	17924009A
REV	DESCRIPTION	DATE	CHECKED BY
4	05/03/18	REVISED PER COMMENTS	JRF PET
3	04/27/18	REVISED PER COMMENTS	JCM PET
2	04/11/18	REVISED PER RFDS	JCM JKJ
1	01/29/18	MOUNT MODIFICATION DESIGN	YMA JKJ
0	10/20/17	ISSUED FOR CONSTRUCTION	JRF PET
A	09/13/17	USED FOR REVIEW	JRF PET

PETROS E. TOUKALAS
 CONNECTICUT LICENSED PROFESSIONAL ENGINEER - LICENSE NUMBER: PEN 38575
 STATE OF CONNECTICUT PROFESSIONAL ENGINEERING REGISTRATION BOARD

SITE NAME: BLOOMFIELD POLICE DEPARTMENT
 SITE ID: CT52XC024
 785 PARK AVENUE
 BLOOMFIELD, CT 06002

MASER CONSULTING
 RED BANK OFFICE
 331 Newnam Springs Road
 Suite 203
 Red Bank, NJ 07701-5699
 Phone: 732.383.1950
 Fax: 732.383.1984

SHEET TITLE:
STRUCTURAL DETAILS
 SHEET NUMBER:
S-001.00