






SPECIFICATION DATA SHEET | MODEL : FCP500



The FuelCube FCP500 is a compact, economic, double-walled fuel tank. Quickly and easily supply fuel where you need it, when you need it.

-  **Mobile.** Forklift pockets allow easy forklift handling when empty.
-  **Stackable.** Easily stackable (2)-high empty to reduce storage space requirements.
-  **Secure.** Pumps, and Equipment enclosed in lockable area – no need for additional pump “Lock-Box”.
-  **Environmentally Safe.** Double-walled, 110% containment eliminates the need for additional spill pans, UL 142 approved.

SPECIFICATIONS	
STANDARD FITTINGS: 1” Pump Feed, Lockable Pump/Equipment Cabinet, Heavy Duty Skid Base with Forklift Pockets, Vent, Fill Cap, UL Plate, Durable Marine Grade Paint Specification, Stacking Brackets.	
OPTIONAL FITTINGS: Direct Reading Float Gauge, 12v, 24v or 110 volt pump kits, Lifting slings, Hoses, Quick Couplers, Filters.	
Capacity (Brim-Fill) Litres: 1893	Outer Tank Material Thickness (in): 1/8”
Capacity (Brim-Fill) Imperial Gallons: 416	Inner Tank Material Thickness (in): 1/8”
Capacity (Brim-Fill) US Gallons: 500	Weight Empty (lbs/kg): 1565 lbs (710kg)
Dimension Length (mm/in): 2185 mm/86”	Weight Full (lbs/kg): 5481 lbs (2650kg)
Dimension Width (mm/in): 1131 mm/44.5”	Approvals: UL142, ULC S-601-07, NFPA
Dimension Height (mm/in): 1169 mm/46”	
Dimension Cabinet Opening (mm/in): 836.6 mm x 533.4 mm/ 34” x 21”	