

State of Connecticut - Department of Public Health

CHILDHOOD LEAD POISONING PREVENTION PROGRAM

REGISTRY OF AUTHORIZED ENCAPSULANT PRODUCTS



Encapsulants are coatings applied in liquid or cementitious form, that are made to be long-lasting barriers over lead paint. Conventional paint is not an encapsulant. Only the products listed on this Registry are authorized for use in Connecticut. Encapsulant use is prohibited on thresholds, window sashes, window parting beads, window stops, window wells, door jambs, door edges, or friction surfaces. Follow manufacturer's instructions/recommendations for product use. Please refer to the Encapsulant Product Fact Sheet and manufacturer's literature for more detailed information on each product.

Product Name	Manufacturer	Not Listed for Use on These Surfaces	Finished Product Thickness	Respiratory Protection Required	Occupancy During Application	Interior Use Exterior Use	Authorization Date
LeadLock™ - (Liquid)/ Your Last Coat™ (Liquid)	GLOBAL Encasement, Inc. 701 E. Santa Clara St. Ventura, CA 93001 Phone: (800) 266-3982 Fax: (800) 520-3291 Email: service@encasement.com www.encasement.com	Friction surfaces, surfaces with chalking or calcimine must be properly prepared.	7 Mils - Interior 16 Mils - Exterior	None required if good ventilation is maintained. During spray application wear suitable respirator (MSHA/NIOSH approved or equivalent).	No - During day of spray application. No - In work area if brush or roller used. Occupancy permitted in other areas if brush or roller used and adequate ventilation is provided for 24 hours after application.	Interior: YES Exterior: YES	04/17/96 Original 12/5/11 revision to Mil thickness
L-B-C® Lead Barrier Compound Type III (Interior/Exterior)/ Child Guard (Interior/Exterior) (Liquid)	Fiberlock Technologies, Inc. 150 Dascomb Road Andover, MA 01810 02139-0802 Phone: (978) 623-9987 Toll Free: (800) 342-3755 Fax: (978) 475-6205 Email: info@fiberlock.com www.fiberlock.com	Friction surfaces, impact surfaces, surfaces with calcimine paint, and radiators where temperature exceeds 212°F. Chalking surfaces must be adequately prepared.	7 Mils	None is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required. For spray application use MSHA/NIOSH	Occupancy in adjacent room(s) permitted during brush or roller application. Occupancy during spray application is not permitted. Occupancy permitted once application has ceased and product	Interior: YES Exterior: YES	3/1/2000

State of Connecticut - Department of Public Health
CHILDHOOD LEAD POISONING PREVENTION PROGRAM
REGISTRY OF AUTHORIZED ENCAPSULANT PRODUCTS



Encapsulants are coatings applied in liquid or cementitious form, that are made to be long-lasting barriers over lead paint. Conventional paint is not an encapsulant. Only the products listed on this Registry are authorized for use in Connecticut. Encapsulant use is prohibited on thresholds, window sashes, window parting beads, window stops, window wells, door jambs, door edges, or friction surfaces. Follow manufacturer’s instructions/recommendations for product use. Please refer to the Encapsulant Product Fact Sheet and manufacturer’s literature for more detailed information on each product.

Product Name	Manufacturer	Not Listed for Use on These Surfaces	Finished Product Thickness	Respiratory Protection Required	Occupancy During Application	Interior Use Exterior Use	Authorization Date
				approved respirator.	is dry to the touch.		
Plaster-In-A-Roll (Cementitious) Gypsum Impregnated Jute Fabric	Flexi-Wall Systems 208 Carolina Drive P.O. Box 89 Liberty, South Carolina 29657-0089 USA Phone: (864) 843-3104 Fax: (864) 843-9318 Email: flexiwall@bellsouth.net www.flexi-wall.com	Not for use on interior surfaces other than walls and ceilings. Not recommended for use in areas where contact with moisture is likely.	35 Mils	Generally not required during normal use and handling of water based adhesive #500.	Occupancy in adjacent room(s) permitted during application. Occupancy permitted 24 hours after application.	Interior: YES Exterior: NO	9/16/96
Faster Plaster Wall Liner (Cementitious) Gypsum Impregnated Jute Fabric	Flexi-Wall Systems 208 Carolina Drive P.O. Box 89 Liberty, South Carolina 29657-0089 USA Phone: (864) 843-3104 Fax: (864) 843-9318 Email: flexiwall@bellsouth.net www.flexi-wall.com	Not for use on interior surfaces other than walls and ceilings. Not recommended for use in areas where contact with moisture is likely.	50 Mils	Generally not required during normal use and handling of water based adhesive #500.	Occupancy in adjacent room(s) permitted during application. Occupancy permitted 24 hours after application.	Interior: YES Exterior: NO	9/16/96

THIS IS VERSION 17-15 OF THE REGISTRY, DATED JUNE 22, 2022. IT WILL BE UPDATED PERIODICALLY. PLEASE CHECK WITH THE DEPARTMENT’S CHILDHOOD LEAD POISONING PREVENTION PROGRAM AT (860) 509-7299 FOR THE MOST RECENT VERSION. THE REGISTRY CAN ALSO BE FOUND ON THE DEPARTMENT’S WEB PAGE.