

STATE OF CONNECTICUT  
CONNECTICUT SITING COUNCIL

IN RE: :  
APPLICATION OF ARX WIRELESS : DOCKET NO. 500  
INFRASTRUCTURE, LLC FOR A :  
CERTIFICATE OF ENVIRONMENTAL :  
COMPATIBILITY AND PUBLIC NEED FOR :  
THE CONSTRUCTION, MAINTENANCE :  
AND OPERATION OF A WIRELESS TELE- :  
COMMUNICATIONS FACILITY LOCATED :  
AT 1061-1063 BOSTON POST ROAD, :  
MILFORD, CONNECTICUT : MAY 9, 2022

**RESPONSES OF CELLCO PARTNERSHIP D/B/A VERIZON WIRELESS TO  
CONNECTICUT SITING COUNCIL REVISED D&M PLAN – INTERROGATORIES**

On April 26, 2022, the Connecticut Siting Council issued Revised D&M Plan – Interrogatories to Cellco Partnership d/b/a Verizon Wireless (“Cellco”) relating to Docket No. 500. Below are Cellco’s responses.

**Question No. 1**

Please provide an updated Radio Frequency Emissions Analysis Report for the revised antenna models shown in the revised Site Plans including the operational frequencies, number of channels and effective radiated power (ERP) values for each proposed antenna.

**Response**

The updated Radio Frequency Emissions Report is attached.

**Question No. 2**

Sheet A-1 of the construction plans show two dimensions for the proposed concrete pad (16-foot by 10-foot & 18-foot by 10-foot). Please clarify.

Response

The correct size of the Verizon equipment pad is 10' by 18'.

**CERTIFICATION OF SERVICE**

I hereby certify that on this 9<sup>th</sup> day of May 2022, a copy of the foregoing was sent, via electronic mail, to the following:

David A. Ball, Esq.  
Philip C. Pires, Esq.  
Cohen & Wolf P.C.  
1115 Broad Street  
Bridgeport, CT 06604  
[dball@cohenandwolf.com](mailto:dball@cohenandwolf.com)  
[ppires@cohenandwolf.com](mailto:ppires@cohenandwolf.com)

Kristen Motel, Esq.  
Lucia Chiocchio, Esq.  
Cuddy & Feder, LLP  
445 Hamilton Avenue, 14<sup>th</sup> Floor  
White Plains, NY 10601  
[kmotel@cuddyfeder.com](mailto:kmotel@cuddyfeder.com)  
[lchiocchio@cuddyfeder.com](mailto:lchiocchio@cuddyfeder.com)

John W. Knuff, Esq.  
Jeffrey P. Nichols, Esq.  
Hurwitz, Sagarin, Slossberg & Knuff, LLC  
147 North Broad Street Milford, CT 06460  
[jknuff@hssklaw.com](mailto:jknuff@hssklaw.com)  
[jnichols@hssklaw.com](mailto:jnichols@hssklaw.com)



---

Kenneth C. Baldwin



C Squared Systems, LLC  
65 Dartmouth Drive  
Auburn, NH 03032  
603-644-2800  
[support@csquaredsystems.com](mailto:support@csquaredsystems.com)

---

## Calculated Radio Frequency Exposure



CT2327

1063 Boston Post Road, Milford, CT 06460

---

May 9, 2022

## Table of Contents

|   |   |
|---|---|
| 1. Introduction.....  | 1 |
| 2. FCC Guidelines for Evaluating RF Radiation Exposure Limits.....    | 1 |
| 3. RF Exposure Calculation Methods.....                               | 2 |
| 4. Calculation Results .....  | 3 |
| 5. Conclusion .....   | 4 |
| 6. Statement of Certification.....                                    | 4 |
| Attachment A: References.....   | 5 |
| Attachment B: FCC Limits for Maximum Permissible Exposure (MPE) ..... | 6 |
| Attachment C: AT&T Antenna Data Sheets and Electrical Patterns.....   | 8 |

## List of Tables

|  |   |
|--|---|
| Table 1: Carrier Information.....                                | 3 |
| Table 2: FCC Limits for Maximum Permissible Exposure (MPE) ..... | 6 |

## List of Figures

|   |   |
|---|---|
| Figure 1: Graph of FCC Limits for Maximum Permissible Exposure (MPE)..... | 7 |
|---|---|

## 1. Introduction

The purpose of this report is to investigate compliance with applicable FCC regulations for the proposed installation of the city of Milford's Public Safety and AT&T antenna arrays on a new monopole tower located at 1063 Boston Post Road in Milford, CT. The coordinates of the tower are 41° 13' 54.32" N, 73° 02' 34.55" W.

AT&T is proposing the following:

- 1) Install six (9) multi-band antennas (three per sector) to support its commercial LTE network and the FirstNet National Public Safety Broadband Network ("NPSBN").

This report considers the planned antenna configuration for AT&T<sup>1</sup> to derive the resulting % Maximum Permissible Exposure of its proposed installation.

## 2. FCC Guidelines for Evaluating RF Radiation Exposure Limits

In 1985, the FCC established rules to regulate radio frequency (RF) exposure from FCC licensed antenna facilities. In 1996, the FCC updated these rules, which were further amended in August 1997 by OET Bulletin 65 Edition 97-01. These new rules include Maximum Permissible Exposure (MPE) limits for transmitters operating between 300 kHz and 100 GHz. The FCC MPE limits are based upon those recommended by the National Council on Radiation Protection and Measurements (NCRP), developed by the Institute of Electrical and Electronics Engineers, Inc., (IEEE) and adopted by the American National Standards Institute (ANSI).

The FCC general population/uncontrolled limits set the maximum exposure to which most people may be subjected. General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Public exposure to radio frequencies is regulated and enforced in units of milliwatts per square centimeter (mW/cm<sup>2</sup>). The general population exposure limits for the various frequency ranges are defined in the attached "FCC Limits for Maximum Permissible Exposure (MPE)" in Attachment B of this report.

Higher exposure limits are permitted under the occupational/controlled exposure category, but only for persons who are exposed as a consequence of their employment and who have been made fully aware of the potential for exposure, and they must be able to exercise control over their exposure. General population/uncontrolled limits are five times more stringent than the levels that are acceptable for occupational, or radio frequency trained individuals. Attachment B contains excerpts from OET Bulletin 65 and defines the Maximum Exposure Limit.

Finally, it should be noted that the MPE limits adopted by the FCC for both general population/uncontrolled exposure and for occupational/controlled exposure incorporate a substantial margin of safety and have been established to be well below levels generally accepted as having the potential to cause adverse health effects.

---

<sup>1</sup> As referenced to AT&T's Radio Frequency Design Sheet updated 9/30/2019.

### 3. RF Exposure Calculation Methods

The power density calculation results were generated using the following formula as outlined in FCC bulletin OET 65, and Connecticut Siting Council recommendations:

$$\text{Power Density} = \left( \frac{1.6^2 \times 1.64 \times \text{ERP}}{4\pi \times R^2} \right) \times \text{Off Beam Loss}$$

Where:

ERP = Effective Radiated Power

R = Radial Distance =  $\sqrt{(H^2 + V^2)}$

H = Horizontal Distance from antenna

V = Vertical Distance from radiation center of antenna

Ground reflection factor of 1.6

Off Beam Loss is determined by the selected antenna pattern

These calculations assume that the antennas are operating at 100 percent capacity and power, and that all antenna channels are transmitting simultaneously. Obstructions (trees, buildings, etc.) that would normally attenuate the signal are not taken into account. The calculations assume even terrain in the area of study and do not consider actual terrain elevations which could attenuate the signal. As a result, the predicted signal levels reported below are much higher than the actual signal levels will be from the final installations.

#### 4. Calculation Results

Table 1 below outlines the cumulative power density information for the AT&T and Verizon equipment at the site. The proposed antennas are directional in nature; therefore, the majority of the RF power is focused out towards the horizon. As a result, there will be less RF power directed below the antennas relative to the horizon, and consequently lower power density levels around the base of the tower. Please refer to Attachment C for the vertical pattern of the proposed AT&T antennas. The calculated results for AT&T in Table 1 include a nominal 10 dB off-beam pattern loss to account for the lower relative gain below the antennas.

| Carrier      | Antenna Height (Feet) | Operating Frequency (MHz) | Number of Trans. | ERP Per Transmitter (Watts) | Power Density (mw/cm <sup>2</sup> ) | Limit        | % MPE         |
|--------------|-----------------------|---------------------------|------------------|-----------------------------|-------------------------------------|--------------|---------------|
| AT&T         | 100                   | 770                       | 1                | 3540                        | 0.0144                              | 0.5133       | 2.81%         |
| AT&T         | 100                   | 770                       | 1                | 3155                        | 0.0128                              | 0.5133       | 2.50%         |
| AT&T         | 100                   | 770                       | 1                | 1730                        | 0.0070                              | 0.5133       | 1.37%         |
| AT&T         | 100                   | 850                       | 1                | 3155                        | 0.0128                              | 0.5667       | 2.27%         |
| AT&T         | 100                   | 1900                      | 1                | 5876                        | 0.0239                              | 1.0000       | 2.39%         |
| AT&T         | 100                   | 2100                      | 1                | 6443                        | 0.0262                              | 1.0000       | 2.62%         |
| AT&T         | 100                   | 2300                      | 1                | 6153                        | 0.0251                              | 1.0000       | 2.51%         |
| Verizon      | 112                   | 770                       | 1                | 623                         | 0.0020                              | 0.5133       | 0.39%         |
| Verizon CDMA | 112                   | 850                       | 1                | 433                         | 0.0014                              | 0.5667       | 0.24%         |
| Verizon LTE  | 112                   | 850                       | 1                | 312                         | 0.0010                              | 0.5667       | 0.18%         |
| Verizon      | 112                   | 1900                      | 1                | 1428                        | 0.0046                              | 1.0000       | 0.46%         |
| Verizon      | 112                   | 2100                      | 1                | 1530                        | 0.0049                              | 1.0000       | 0.49%         |
| Verizon CBRS | 109.5                 | 3500                      | 1                | 42                          | 0.0001                              | 1.0000       | 0.01%         |
| Verizon 5G   | 113.5                 | 3500                      | 1                | 11092                       | 0.0345                              | 1.0000       | 3.45%         |
|              |                       |                           |                  |                             |                                     | <b>Total</b> | <b>21.69%</b> |

Table 1: Carrier Information<sup>2</sup>

<sup>2</sup> Verizon Wireless %MPE based on RFDS dated 2/4/2022

## 5. Conclusion

The above analysis concludes that RF exposure at ground level from the proposed site will be below the maximum power density levels as outlined by the FCC in the OET Bulletin 65 Ed. 97-01. Using conservative calculation methods, the highest expected percent of Maximum Permissible Exposure at ground level is **21.69% of the FCC General Population/Uncontrolled limit.**

As noted previously, the calculated % MPE levels are more conservative (higher) than the actual signal levels will be from the finished modifications.

## **6. Statement of Certification**

I certify to the best of my knowledge that the statements in this report are true and accurate. The calculations follow guidelines set forth in FCC OET Bulletin 65 Edition 97-01, ANSI/IEEE Std. C95.1 and ANSI/IEEE Std. C95.3.

Mark J. Sam

Reviewed/Approved By: Martin Lavin  
Sr. RF Engineer  
C Squared Systems, LLC

May 9, 2022  
Date

### Attachment A: References

OET Bulletin 65 - Edition 97-01 - August 1997 Federal Communications Commission Office of Engineering & Technology

IEEE C95.1-2005, IEEE Standard Safety Levels With Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz IEEE-SA Standards Board

IEEE C95.3-2002 (R2008), IEEE Recommended Practice for Measurements and Computations of Radio Frequency Electromagnetic Fields With Respect to Human Exposure to Such Fields, 100 kHz-300 GHz IEEE-SA Standards Board

## Attachment B: FCC Limits for Maximum Permissible Exposure (MPE)

### **(A) Limits for Occupational/Controlled Exposure<sup>3</sup>**

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (E) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|---|
| 0.3-3.0               | 614                               | 1.63                              | (100)*                                  | 6   |
| 3.0-30                | 1842/f                            | 4.89/f                            | (900/f <sup>2</sup> )*                  | 6   |
| 30-300                | 61.4                              | 0.163                             | 1.0                                     | 6   |
| 300-1500              | -                                 | -                                 | f/300                                   | 6   |
| 1500-100,000          | -                                 | -                                 | 5                                       | 6   |

### **(B) Limits for General Population/Uncontrolled Exposure<sup>4</sup>**

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (E) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|---|
| 0.3-1.34              | 614                               | 1.63                              | (100)*                                  | 30  |
| 1.34-30               | 824/f                             | 2.19/f                            | (180/f <sup>2</sup> )*                  | 30  |
| 30-300                | 27.5                              | 0.073                             | 0.2                                     | 30  |
| 300-1500              | -                                 | -                                 | f/1500                                  | 30  |
| 1500-100,000          | -                                 | -                                 | 1.0                                     | 30  |

f = frequency in MHz \* Plane-wave equivalent power density

**Table 2: FCC Limits for Maximum Permissible Exposure (MPE)**

<sup>3</sup> Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure

<sup>4</sup> General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure








Figure 1: Graph of FCC Limits for Maximum Permissible Exposure (MPE)

### Attachment C: AT&T Antenna Data Sheets and Electrical Patterns

|  |  |
|--|--|
| <p><b>750 MHz</b></p> <p>Manufacturer: CCI Products<br/>         Model #: TPA-65R-BU8D<br/>         Frequency Band: 698-806 MHz<br/>         Gain: 13.45 dBd<br/>         Vertical Beamwidth: 9.5°<br/>         Horizontal Beamwidth: 74°<br/>         Polarization: Dual Linear 45°<br/>         Size L x W x D: 96.0" x 21" x 7.8"</p>     |    |
| <p><b>750 MHz</b></p> <p>Manufacturer: CCI Products<br/>         Model #: DMP-65R-BU8D<br/>         Frequency Band: 698 - 798MHz<br/>         Gain: 12.95 dBd<br/>         Vertical Beamwidth: 9.5°<br/>         Horizontal Beamwidth: 75°<br/>         Polarization: Dual Linear 45°<br/>         Size L x W x D: 96.0" x 20.7" x 7.7"</p>  |   |
| <p><b>750 MHz</b></p> <p>Manufacturer: CCI Products<br/>         Model #: HPA-65R-BU8A<br/>         Frequency Band: 698 - 806 MHz<br/>         Gain: 13.35 dBd<br/>         Vertical Beamwidth: 9.7°<br/>         Horizontal Beamwidth: 67°<br/>         Polarization: Dual Linear 45°<br/>         Size L x W x D: 96.0" x 11.7" x 7.7"</p> |  |


**850 MHz**

Manufacturer: CCI Products  
 Model #: DMP-65R-BU8D  
 Frequency Band: 824-896 MHz  
 Gain: 13.85 dBd  
 Vertical Beamwidth: 8.0°  
 Horizontal Beamwidth: 64°  
 Polarization: Dual Linear 45°  
 Size L x W x D: 96.0" x 20.7" x 7.7"




**1900 MHz**

Manufacturer: CCI Products  
 Model #: DMP-65R-BU8D  
 Frequency Band: 1850-1990 MHz  
 Gain: 15.65 dBd  
 Vertical Beamwidth: 5.1°  
 Horizontal Beamwidth: 68°  
 Polarization: Dual Linear 45°  
 Size L x W x D: 96.0" x 20.7" x 7.7"



**2100 MHz**

Manufacturer: CCI Products  
 Model #: TPA-65R-BU8D  
 Frequency Band: 1920 - 2180 MHz  
 Gain: 16.15 dBd  
 Vertical Beamwidth: 4.7°  
 Horizontal Beamwidth: 67°  
 Polarization: Dual Linear 45°  
 Size L x W x D: 96.0" x 20.7" x 7.7"



**2310 MHz**

Manufacturer: CCI Products

Model #: HPA-65R-BU8A

Frequency Band: 2300 - 2400 MHz

Gain: 15.85 dBd

Vertical Beamwidth: 4.0°

Horizontal Beamwidth: 60°

Polarization: Dual Linear 45°

Size L x W x D: 96.0" x 11.7" x 7.7"

