



C Squared Systems, LLC
65 Dartmouth Drive
Auburn, NH 03032
(603) 644-2800
support@csquaredsystems.com

Calculated Radio Frequency Emissions Report



CT1498

70 Universal Drive, North Haven, CT

June 20, 2025

Table of Contents

1. Introduction	1
2. FCC Guidelines for Evaluating RF Radiation Exposure Limits.....	1
3. RF Exposure Calculation Methods.....	2
4. Antenna Inventory	3
5. Calculated % MPE Results.....	4
6. Conclusion.....	6
7. Statement of Certification.....	6
Attachment A: References	7
Attachment B: FCC Limits for Maximum Permissible Exposure (MPE)	8
Attachment C: AT&T Antenna Model Data Sheets and Electrical Patterns	10

List of Figures

Figure 1: Graph of General Population % MPE vs. Distance.....	4
Figure 2: Graph of FCC Limits for Maximum Permissible Exposure (MPE).....	9

List of Tables

Table 1: AT&T's Proposed Antenna Inventory.....	3
Table 2: Maximum Percent of General Population Exposure Values,,	5
Table 3: FCC Limits for Maximum Permissible Exposure	8

1. Introduction

The purpose of this report is to investigate compliance with applicable FCC regulations for the installation of AT&T's antenna arrays to be mounted at 120' AGL on a proposed monopole located at 70 Universal Drive in North Haven, CT. The coordinates¹ of the proposed facility are 41° 20' 47.09" N, 72° 52' 10.34" W.

AT&T is proposing to install nine (9) directional antennas (three sectors, three antennas per sector) to support its 4G LTE and 5G NR networks.

This report considers the antenna configuration for AT&T's proposed installation to calculate the resulting % Maximum Permissible Exposure (MPE) at ground level around the proposed facility.

2. FCC Guidelines for Evaluating RF Radiation Exposure Limits

In 1985, the FCC established rules to regulate radio frequency (RF) exposure from FCC licensed antenna facilities. In 1996, the FCC updated these rules, which were further amended in August 1997 by OET Bulletin 65 Edition 97-01. These new rules include Maximum Permissible Exposure (MPE) limits for transmitters operating between 300 kHz and 100 GHz. The FCC MPE limits are based upon those recommended by the National Council on Radiation Protection and Measurements (NCRP), developed by the Institute of Electrical and Electronics Engineers, Inc., (IEEE) and adopted by the American National Standards Institute (ANSI).

The FCC general population/uncontrolled limits set the maximum exposure to which most people may be subjected. General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Public exposure to radio frequencies is regulated and enforced in units of milliwatts per square centimeter (mW/cm²). The general population exposure limits for the various frequency ranges are defined in the documents referenced in Attachment A of this report.

Higher exposure limits are permitted under the occupational/controlled exposure category, but only for persons who are exposed as a consequence of their employment and who have been made fully aware of the potential for exposure, and they must be able to exercise control over their exposure. General population/uncontrolled limits are five times more stringent than the levels that are acceptable for occupational, or radio frequency trained individuals. Attachment B contains excerpts from OET Bulletin 65 and defines the Maximum Exposure Limit.

Finally, it should be noted that the MPE limits adopted by the FCC for both general population/uncontrolled exposure and for occupational/controlled exposure incorporate a substantial margin of safety and have been established to be well below levels generally accepted as having the potential to cause adverse health effects.

¹ As defined in Crown Castle's Zoning Drawings prepared by All-Points Technology Corp. (Rev. 2 dated 5/20/2025) for the subject location

3. RF Exposure Calculation Methods

The results displayed in the following figures were generated using the following formula as outlined in FCC bulletin OET 65:

$$\text{Power Density} = \left(\frac{GRF^2 \times \text{EIRP}}{4\pi \times R^2} \right) \times \text{Off Beam Loss}$$

Where:

EIRP = Effective Isotropic Radiated Power

R = Radial Distance = $\sqrt{(H^2 + V^2)}$

H = Horizontal Distance from antenna

V = Vertical Distance from radiation center of antenna

Off Beam Loss is determined by the selected antenna patterns

GRF = Ground reflection factor of 1.6

These calculations assume that the antennas are operating at full power and 100 percent capacity, and that all antenna channels are transmitting simultaneously. Obstructions (trees, buildings, etc.) that would normally attenuate the signal are not considered. The calculations assume level terrain in the area of study and do not account for actual terrain elevations which could attenuate the signal. As a result, the calculated power density and corresponding % MPE levels reported below are much higher than the actual signal levels will be from the final installation.

The percent of MPE values presented in this report reflect levels that one may encounter from one sector of a carrier's antennas. Most carriers use 3 or 4 sectors per site with azimuths approximately 90 or 120 degrees apart, respectively; therefore, one could not be standing in the main beam of all sectors at the same time. In cases where antenna models are not uniform across all sectors, the antenna model with the highest gain was used for the calculations. This results in a conservative or "worst case" assumption for percent of MPE calculations.

4. Antenna Inventory

Table 1 below outlines AT&T’s proposed antenna configuration for the site. The associated data model and antenna patterns for these specific antenna models are included in Attachment C.

Operator	Sector / Azimuth	TX Freq (MHz)	Power at Antenna (Watts)	Ant Gain (dBi)	Power EIRP (Watts)	Antenna Model	Beam Width	Mech. Tilt	Length (ft)	Antenna Centerline Height (ft)
AT&T	Alpha / 40°	722	80	16	3185	NNH4-65C-R6-V4	62	0	8	120
		763	160	16	6370		62	0		
		1900	240	18.6	17386		65	0		
		2100	240	19.1	19508		61	0		
		739	240	16	9555	NNH4-65C-R6-V4	62	0	8	120
		850	240	16.2	10005		60	0		
		3500	200	19.1	16257	AIR6472 B77G B77M	60	0	3	120
		3700	200	18.9	15525		60	0		
	Beta / 160°	722	80	16	3185	NNH4-65C-R6-V4	62	0	8	120
		763	160	16	6370		62	0		
		1900	240	18.6	17386		65	0		
		2100	240	19.1	19508		61	0		
		739	240	16	9555	NNH4-65C-R6-V4	62	0	8	120
		850	240	16.2	10005		60	0		
		3500	200	19.1	16257	AIR6472 B77G B77M	60	0	3	120
		3700	200	18.9	15525		60	0		
	Gamma / 280°	722	80	16	3185	NNH4-65C-R6-V4	62	0	8	120
		763	160	16	6370		62	0		
		1900	240	18.6	17386		65	0		
		2100	240	19.1	19508		61	0		
		739	240	16	9555	NNH4-65C-R6-V4	62	0	8	120
		850	240	16.2	10005		60	0		
		3500	200	19.1	16257	AIR6472 B77G B77M	60	0	3	120
		3700	200	18.9	15525		60	0		

Table 1: AT&T’s Proposed Antenna Inventory^{2,3}

² Antenna configuration is in reference to AT&T’s Radio Frequency Design Sheet last dated 8/6/2024 and the Zoning Drawings prepared by All-Points Technology Corp. (Rev. 2 dated 5/20/2025).

³ Transmit power assumes 0 dB of cable loss.

5. Calculated % MPE Results

The calculated % MPE results for the proposed antenna configuration are shown in Figure 1 below. Each frequency band and technology is calculated as well as the resulting cumulative percent of MPE. For completeness, the calculations for this analysis range from 0 feet horizontal distance (directly below the antennas) to a value of 3,000 feet horizontal distance from the site. In addition to the other worst-case scenario considerations that were previously mentioned, the power density calculations to each horizontal distance point away from the antennas was completed using a local maximum off beam antenna gain (within ± 5 degrees of the true mathematical angle) to incorporate a realistic worst-case scenario.




Figure 1: Graph of General Population % MPE vs. Distance

The highest percent of MPE (3.54% of the General Population limit) is calculated to occur at a horizontal distance of 720 feet away from the site. Please note that the percent of MPE calculations close to the site consider off beam loss, which is determined from the vertical pattern of the antennas used. Therefore, RF power density levels may increase as the distance from the site increases. At distances of approximately 850 feet and beyond, one would now be in the main beam of the antenna patterns and off beam loss is no longer considered. Beyond this point, power density levels vary based on distance from the site and the percent of MPE decreases significantly as distance from the site increases.

Table 2 below lists percent of MPE values as well as the associated parameters that were included in the calculations. As stated in Section 3, all calculations assume that the antennas are operating at 100 percent capacity, and that all antenna channels are transmitting simultaneously. Obstructions (trees, buildings etc.) that would normally attenuate the signal are not taken into account. Additionally, a six-foot height offset was considered in this analysis to account for the height of a person standing at ground level. As a result, the calculated % MPE levels are significantly higher than the actual signal levels will be from the final installation. The results presented in Figure 1 and Table 2 assume level ground elevation from the base of the site out to the horizontal distances calculated.

Carrier	Number of Transmitters	Power out of Base Station Per Transmitter (Watts)	Antenna Height (Feet)	Distance to the Base of Antennas (Feet)	Power Density (mW/cm ²)	Limit (mW/cm ²)	% MPE
AT&T 5G 3500 MHz	1	200.0	120.0	720	0.004656	1.000	0.47%
AT&T 5G 3700 MHz	1	200.0	120.0	720	0.003674	1.000	0.37%
AT&T LTE 1900 MHz	1	240.0	120.0	720	0.004732	1.000	0.47%
AT&T LTE 2100 MHz	1	240.0	120.0	720	0.004519	1.000	0.45%
AT&T LTE 722 MHz	1	80.0	120.0	720	0.000901	0.481	0.19%
AT&T LTE 739 MHz	1	240.0	120.0	720	0.002870	0.493	0.58%
AT&T LTE 763 MHz	1	160.0	120.0	720	0.002237	0.509	0.44%
AT&T LTE 850 MHz	1	240.0	120.0	720	0.003250	0.567	0.57%
						Total	3.54%

Table 2: Maximum Percent of General Population Exposure Values^{4,5,6}

⁴ Frequencies listed are representative of the operating band and are not the specific operating frequency.

⁵ The total % MPE listed is a summation of each unrounded contribution. Therefore, summing each rounded value may not reflect the total value listed in the table.

⁶ Antenna heights are in reference to Crown Castle’s Zoning Drawings prepared by All-Points Technology Corp. (Rev. 2 dated 5/20/2025).

6. Conclusion

The above analysis concludes that RF exposure levels from the proposed site will be well below the maximum permissible levels as outlined by the FCC in the OET Bulletin 65 Ed. 97-01. Using the conservative calculation methods and parameters detailed above, the maximum cumulative percent of MPE is calculated to be **3.54% of the FCC limit (General Population/Uncontrolled)**. This maximum cumulative percent of MPE value is calculated to occur 720 feet away from the site.

7. Statement of Certification

I certify to the best of my knowledge that the statements in this report are true and accurate. The calculations follow guidelines set forth in ANSI/IEEE Std. C95.1, ANSI/IEEE Std. C95.3, and FCC OET Bulletin 65 Edition 97-01.



Report Prepared By: Ram Acharya
RF Engineer
C Squared Systems, LLC

June 20, 2025

Date



Reviewed/Approved By: Martin Lavin
Senior RF Engineer
C Squared Systems, LLC

June 20, 2025

Date

Attachment A: References

OET Bulletin 65 - Edition 97-01 - August 1997 Federal Communications Commission Office of Engineering & Technology

IEEE C95.1-2019, IEEE Standard Safety Levels With Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz IEEE-SA Standards Board

IEEE C95.3-2021, IEEE Recommended Practice for Measurements and Computations of Electric, Magnetic, and Electromagnetic Fields With Respect to Human Exposure to Such Fields, 0 Hz to 300 GHz IEEE-SA Standards Board

Attachment B: FCC Limits for Maximum Permissible Exposure (MPE)

(A) Limits for Occupational/Controlled Exposure⁷

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (E) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	f/300	6
1500-100,000	-	-	5	6

(B) Limits for General Population/Uncontrolled Exposure⁸

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (E) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	f/1500	30
1500-100,000	-	-	1.0	30

f = frequency in MHz * Plane-wave equivalent power density

Table 3: FCC Limits for Maximum Permissible Exposure

⁷ Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

⁸ General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.









Figure 2: Graph of FCC Limits for Maximum Permissible Exposure (MPE)

Attachment C: AT&T Antenna Model Data Sheets and Electrical Patterns

<p>722/763 MHz</p> <p>Manufacturer: COMMSCOPE Model #: NNH4-65C-R6-V4 Frequency Band: 698-806 MHz Gain: 16 dBi Electrical Down-Tilt: 2° Vertical Beamwidth: 9.5° Horizontal Beamwidth: 62° Polarization: ±45° Dimensions (L x W x D): 96" x 19.6" x 7.77"</p>	
<p>739 MHz</p> <p>Manufacturer: COMMSCOPE Model #: NNH4-65C-R6-V4 Frequency Band: 698-806 MHz Gain: 16 dBi Electrical Down-Tilt: 2° Vertical Beamwidth: 9.5° Horizontal Beamwidth: 62° Polarization: ±45° Dimensions (L x W x D): 96" x 19.6" x 7.77"</p>	
<p>850 MHz</p> <p>Manufacturer: COMMSCOPE Model #: NNH4-65C-R6-V4 Frequency Band: 698-806 MHz Gain: 16.2 dBi Electrical Down-Tilt: 2° Vertical Beamwidth: 8.3° Horizontal Beamwidth: 60° Polarization: ±45° Dimensions (L x W x D): 96" x 19.6" x 7.77"</p>	

<p>1900 MHz</p> <p>Manufacturer: COMMSCOPE Model #: NNH4-65C-R6-V4 Frequency Band: 1850-1990 MHz Gain: 18.6 dBi Electrical Down-Tilt: 2° Vertical Beamwidth: 5.3° Horizontal Beamwidth: 65° Polarization: ±45° Dimensions (L x W x D): 96" x 19.6" x 7.77"</p>	
<p>2100 MHz</p> <p>Manufacturer: COMMSCOPE Model #: NNH4-65C-R6-V4 Frequency Band: 1920-2180 MHz Gain: 19.1 dBi Electrical Down-Tilt: 2° Vertical Beamwidth: 5° Horizontal Beamwidth: 61° Polarization: ±45° Dimensions (L x W x D): 96" x 19.6" x 7.77"</p>	
<p>3500/3700 MHz</p> <p>Manufacturer: ERICSSON Model #: AIR6472 B77G B77M Frequency Band: B77G: 3450-3550 MHz B77M: 3840-3980 MHz Gain: 19.1/18.9 dBi Electrical Down-Tilt: 2° Vertical Beamwidth: 87-105° Horizontal Beamwidth: 60° Polarization: -° Dimensions (L x W x D): 36.3" x 15.8" x 7.4"</p>	<p>N/A</p>