

T-Mobile USA Inc. 100 Filley St, Bloomfield, CT 06002-1853 Phone: (860) 692-7100 Fax: (860) 692-7159

## Technical Memo

To: Karina Fournier From: Scott Heffernan - Radio Frequency Engineer cc: Jason Overbey Subject: Power Density Report for CTHA145B Date: October 22, 2008

## 1. Introduction:

This report is the result of an Electromagnetic Field Intensities (EMF - Power Densities) study for the T-Mobile PCS antenna installation on a Monopole at 12 Burr Road, Bloomfield, CT. This study incorporates the most conservative consideration for determining the practical combined worst case power density levels that would be theoretically encountered from locations surrounding the transmitting location.

## 2. Discussion:

The following assumptions were used in the calculations:

- 1) The emissions from T-Mobile transmitters are in the 1935-1945 MHz frequency band.
- 2) The antenna array consists of three sectors, with 3 antennas per sector.
- 3) The model number for each antenna is APXV18-209014-C.
- 4) The antenna center line height is 127 ft.
- 5) The maximum transmit power from any sector is 2067.43 Watts Effective Radiated Power (EiRP) assuming 8 channels per sector.
- 6) All the antennas are simultaneously transmitting and receiving, 24 hours a day.
- 7) Power levels emitting from the antennas are increased by a factor of 2.56 to account for possible in-phase reflections from the surrounding environment. This is rarely the case, and if so, is never continuous.
- 8) The average ground level of the studied area does not change significantly with respect to the transmitting location

Equations given in "FCC OET Bulletin 65, Edition 97-01" were then used with the above information to perform the calculations.

## 3. Conclusion:

Based on the above worst case assumptions, the power density calculation from the T-Mobile PCS antenna installation on a Monopole at 12 Burr Road, Bloomfield, CT, is 0.03098 mW/cm^2. This value represents 3.098% of the Maximum Permissible Exposure (MPE) standard of 1 milliwatt per square centimeter (mW/cm^2) set forth in the FCC/ANSI/IEEE C95.1-1991. Furthermore, the proposed antenna location for T-Mobile will not interfere with existing public safety communications, AM or FM radio broadcasts, TV, Police Communications, HAM Radio communications or any other signals in the area.

| Worst Case Power Density<br>Site:  | T • Mobile *<br>CTHA145B                   |
|--|--|
| -  |  |
| Site:  |  |
|  |  |
| Site Address:  | 12 Burr Road                               |
| Town:  | Bloomfield                                 |
| Tower Height:  | 130 ft.                                    |
| Tower Style:   | Monopole                                   |
| Base Station TX output   | •  |
| Number of channels   | 8  |
| Antenna Model  | APXV18-209014-C                            |
| Cable Size   |  |
| Cable Length   | 160 ft.                                    |
| Antenna Height   |  |
| Ground Reflection  | 1.6<br>1945.0 MHz                          |
| Frequency<br>Jumper & Connector loss   |  |
| Antenna Gain   |  |
| Cable Loss per foot  |  |
| Total Cable Loss   |  |
| Total Attenuation  | 6.3560 dB                                  |
| Total EIRP per Channel   | 54.12 dBm                                  |
| (In Watts)   |  |
| Total EIRP per Sector  |  |
| (In Watts)   | 2067.43 W<br>10.1440                       |
| nsg<br>Power Donsity (S) –   | 0.030980 mW/cm^2                           |
| Power Density (S) =<br>T-Mobile Worst Case % MPE =                           |  |
|  | 0.000070                                   |
| Equation Used :<br>$S = \frac{(1000)(grf)^{2}(Power)^{k}10^{(isg10)}}{4\pi}$ |  |
| $4\pi(\mathbf{R})$   | T) Bulletin 65, Edition 97-01, August 1997 |