GZA
GeoEnvironmental, Inc.

Engineers and
Scientists

September 23, 2011
File No. 44818.02

Mr. Gregory Zupkus
BNE Energy Inc.
Town Center, Suite 200
29 South Main Street
West Hartford, CT 06107

Re: Geotechnical Engineering Report
Proposed Wind Renewable Generating Facility
Colebrook North
Rock Hall Road
Colebrook, Connecticut

655 Winding Brook Drive,
Suite 402
Glastonbury, CT 06033
860-286-8900 (phone)
860-652-8590 (fax)
www.gza.com

Dear Mr. Zupkus:

GZA GeoEnvironmental, Inc. (GZA) is pleased to provide you with our geotechnical engineering report for the subject project, in accordance with our proposal dated July 12, 2011. The subsurface investigation and findings of this report are subject to the Limitations that are included in Appendix A.

GZA appreciates the opportunity to have provided geotechnical engineering services for this project. Please contact the undersigned if you have questions or comments regarding this report or if we may be of further service to you.

Very truly yours
GZA GEOENVIRONMENTAL, INC.

Dan Kinard, P.E.
Senior Project Manager

Mitchell Wurmbrand
Associate Principal

Douglas Roy, P.E.
Associate Principal

GEOTECHNICAL ENGINEERING REPORT
PROPOSED WIND RENEWABLE GENERATING FACILITY
COLEBROOK NORTH
ROCK HALL ROAD
COLEBROOK, CONNECTICUT

PREPARED FOR:
BNE Energy Inc.
Town Center, Suite 200
29 South Main Street
West Hartford, CT 06107

PREPARED BY:
GZA GeoEnvironmental, Inc.
655 Winding Brook Drive, Suite 402
Glastonbury, CT 06033

September 2011
File No. 44818.02

TABLE OF CONTENTS

GEOTECHNICAL ENGINEERING REPORT
Proposed Wind Renewable Generating Facility
Colebrook North
Rock Hall Road
Colebrook, Connecticut

1.00 PROJECT LOCATION & DESCRIPTION

The project site is located east of Rock Hall Road in Colebrook, Connecticut. The proposed project includes installation of three 1.6 MW wind turbines. The undeveloped site is located on Figure 1, Locus Plan and the turbine locations are shown on Figure 2, Exploration Location Plan. The project includes constructing roads, assembly areas, crane pads, surface drainage controls, pads for electrical equipment, and turbine foundations. These major features are shown on Figure 2.

2.00 GEOTECHNICAL OBJECTIVE & SCOPE

The objective of this report is to summarize the results of the subsurface investigations performed to date and provide proposed turbine foundation recommendations based on this information. Laboratory testing on soil and rock samples is currently underway and geophysical testing at turbine locations is planned. The turbine foundation design has been prepared by GZA and is presented on Wind Colebrook North, Foundation Set, Drawings B-201, B-202 and B-203, dated September 23, 2011. The turbine foundation design will be refined and finalized based on the additional information referenced above.

This report provides the exploration locations, boring and test pit logs, an evaluation of the subsurface conditions for the project, and turbine foundation recommendations.

3.00 SUBSURFACE INVESTIGATIONS

A subsurface exploration program, that included five test borings (CNGZ-5 through CNGZ-9) and twenty-seven test pits (CNTP-2 through CNTP-4 and CNTP-6 through CNTP-29), was completed from July 25 through 27, 2011. Test pits CNTP-1 and CNTP-5 were not excavated. The borings were drilled by New Hampshire Borings and the test pits were dug by HTS Construction. A GZA Engineer observed the borings and test pits, classified the subsurface materials and prepared exploration logs.

The soils encountered were classified according to the modified Burmister classification system. Details of the modified Burmister classification system, as well as the boring and test pit logs are presented in Appendix B and C.

The as-built boring exploration locations were located in the field by survey performed by Riordan Land Surveying. The locations of the explorations are indicated on Figure 2. Summaries of the explorations and subsurface conditions encountered are presented on Table 1.

Borings

The borings were drilled to depths ranging from 12 to 32 feet below the existing ground surface. The following borings were drilled:

Boring	Location	Ground Surface Elevations, Feet
CNGZ-5	Turbine 3	1365
CNGZ-6	Turbine 2	1324
CNGZ-7	Turbine 2	1326
CNGZ-8	Turbine 1	1255
CNGZ-9	Turbine 1	1258

Bedrock was encountered in Borings CNGZ-5, CNGZ-6, and CNGZ-8 and about 5 to 10 feet of rock core was obtained in each of these borings. Borings CNGZ-7 and CNGZ-9 were performed as offsets to borings CNGZ-6 and CNGZ-8, and were extended until auger refusal was encountered, possibly indicating the top of bedrock.

Test borings in glacial till were advanced using either augers or steel casing and rotary wash techniques. Standard Penetration Test(s) (SPTs) were performed and split spoon soil samples collected at the ground surface and at five-foot intervals thereafter, in general accordance with ASTM D1586. SPT sampling consists of advancing a 1-3/8 inch inside diameter standard split spoon sampler at least 24 inches with a 140-pound safety hammer dropping from a height of 30 inches. The SPT value, often referred to as the "N" value, is the number of blows per foot of penetration required to drive the sampler from 6 to 18 inches of penetration.

When required, coring was performed using a diamond bit with an NX double tube, ridge-type core barrel in accordance with ASTM D-2113-83. The rock type description, the core recovery for each coring interval, and the rock quality designation (RQD) values expressed in percent for each run are recorded on the test boring logs. The RQD values reflect the quality and fracture spacing of the rock and are calculated as a summation of all unbroken core samples of four inches or more in length divided by the total length of each coring interval. The core recovery percentage and RQD values provide a qualitative understanding of the physical and engineering properties of bedrock.

Upon extraction of each core run, the rock was examined and classified according to rock type, color, weathering, hardness, fracture zones, solution cavities, foliation, and fracture inclination. The rock cores were boxed with the pertinent information transposed onto each core box.

The borings (except for CNGZ-7 and -9) were drilled using rotary wash drilling techniques. Water was introduced into the boring and therefore groundwater levels immediately after drilling are not reported. CNGZ-7 and -9 were drilled with hollow stem augers and no water was introduced. No groundwater was encountered in boring CNGZ-9. Groundwater observation wells were installed in borings CNGZ-7 and CNGZ-8.

Groundwater measurements were taken on August 23, 2011 at CNGZ-7, CNGZ-8 and the open boring at CNGZ-5. Groundwater measurements are presented on the boring logs and summarized in Table 1.

Test Pits

The test pits were generally located at the proposed turbine foundation locations, at crane pad areas, along the proposed access roads, assembly areas, and at surface drainage control areas. The exploration locations were surveyed by Riordan Land Surveying. The test pit locations are shown on Figure 2.

When encountered, depths to groundwater were measured in the excavated test pits. Groundwater measurements are presented on the test pit logs and summarized in Table 1.

4.00 GENERALIZED SUBSURFACE CONDITIONS

A generalized description of subsurface conditions is provided below. Refer to the boring and test pit logs in Appendices B and C for more specific information.

- Approximately three to twelve inches of **topsoil** and forest mat was encountered at the ground surface. In this report this layer is identified as topsoil.

- **Subsoil** was present directly below the topsoil and forest mat, and extended to depths between 1 and 4 feet. The subsoil generally consists of fine to coarse sand, some to little silt. Indications of cobbles and boulders embedded in the subsoil layer were noted during drilling and in test pits. SPT blow counts from borings indicate relative density of the subsoil is loose.

- **Glacial till** was encountered underlying the subsoil. Except in the locations of the proposed turbines, the glacial till typically extends to about 4 to 9 feet below grade. At the proposed turbine locations, the glacial till extends to about 12 to 25 feet below grade. The glacial till consists of generally medium dense to very dense, unsorted gravel and sand, some to little silt. Cobbles and boulders should also be anticipated within the glacial till.

- **Bedrock** is described as typically a hard, slightly weathered, slightly fractured to sound, fine to medium grained, high angle foliation, white and black gneiss. At Turbines 1, 2, and 3, the depth to bedrock is about 12, 15, and 25 feet below ground surface, respectively. Bedrock recovery expressed as a percentage (the length of core recovered divided by the length cored), generally varied between 82 and 100 percent.

  Rock Quality Designation (RQD), also expressed as a percentage, is a measure of how fractured the rock is. It is defined as the sum of the lengths of core pieces that are greater than 4 inches in length, divided by the length of the core run. The RQD values are generally between 69 and 90 percent with one value as low as 35 percent

at CNGZ-5 from 26 to 32 feet below grade (top 6 feet of bedrock). Based on core times, recoveries, RQD, and observations of bedrock core, the upper 5 to 10 feet of bedrock is in generally more weathered and fractured.

- **Groundwater** was observed in Test Pits CNTP-4 and CNGZ-19 and measured in monitoring wells installed in Borings CNGZ-7 and CNGZ-8 and measured in the open boring at CNGZ-5. Groundwater in the test pits was observed from 4.5 to 5 feet below the existing ground surface. The test pits that encountered groundwater are located on the west part of the site near the Turbine 1 location and are at topographic lows which are adjacent to wetlands areas. Monitoring wells installed at Turbine 1 and Turbine 2 and the open hole at borehole CNGZ-5 adjacent to Turbine 3 were read approximately one month after installation. Groundwater was measured at 3.2 feet below ground surface at Turbine 1 (CNGZ-8), at 6.6 feet below ground surface at Turbine 2 (CNGZ-7), and at 4.8 feet below ground surface at Turbine 3 (CNGZ-5).

  Perched groundwater may also be encountered in the glacial till or subsoil above the bedrock, especially in the spring due to the infiltration of snowmelt. The groundwater level in this area is likely controlled by watercourses and wetlands in the vicinity.

  It is anticipated that groundwater levels will vary due to variations in rainfall and other factors different than those prevailing at the time the explorations were performed and the measurements were made. It should be noted that the seasonally lowest groundwater levels typically occur during the late summer and fall months.

5.00 TURBINE FOUNDATION DESIGN DISCUSSION

GZA has prepared the turbine foundation design based on the results of the subsurface explorations completed to date. Laboratory test results and geophysical testing will be provided when they become available and turbine foundation design will be refined and finalized. The current turbine foundation design shown on Drawings B-101, B-102 and B-103 is the largest foundation diameter we currently anticipate.

Our general conclusions are as follows:

- The subsurface conditions encountered at the site are suitable for support of a gravity spread footing foundation. Foundations for the Turbines will be supported on naturally-deposited glacial till. At Turbine 1, bedrock was encountered within three feet of the anticipated bottom of footing elevation. The bedrock surface is anticipated to undulate over short horizontal distance, and limited bedrock removal may therefore be required in some locations.

- Recommended foundations are planned to be octagonally shaped with a dimension of 54 feet between opposing sides. The bottom of foundation is planned to be approximately 9 feet below finished grade.

- Controlled blasting techniques should be used for bedrock removal for cuts in bedrock for foundations, access roads, crane pads and laydown areas.

- The glacial till soils at the site contain elevated percentages of silt. These soils can be disturbed by construction traffic when wet. Excavated surfaces will need subgrade protection that may consist of a concrete mud mat or compacted gravel over a layer of filter fabric.

- The glacial till and bedrock typically have a relatively low permeability and it is not anticipated that significant amounts of groundwater will be encountered during excavations for the foundations. If water is encountered (groundwater or precipitation within excavations), it should be removed from the excavation by pumping from sumps.

TABLES

TABLE 1
SUMMARY OF EXPLORATION DATA
BNE WIND FARM - COLEBROOK NORTH
COLEBROOK, CONNECTICUT

	Test Borings					Test Pits										
	CNGZ-5	CNGZ-6	CNGZ-7 (OW)	CNGZ-8 (OW)	CNGZ-9	CNTP-2	CNTP-3	CNTP-4	CNTP-6	CNTP-7	CNTP-8	CNTP-9	CNTP-10	CNTP-11	CNTP-12	CNTP-13
Depth (ft) to:																
Topsoil/Subsoil	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Glacial Till	3.0	2.5	2.0	3.0	2.0	3.0	2.5	2.0	2.5	2.0	1.5	1.5	1.5	1.8	2.0	2.5
Bedrock or Refusal	25.0	16.0	13.5	12.0	12.0	5.0	4.0	4.5	3.5	NE	NE	NE	NE	NE	NE	NE
Groundwater [2]	4.8	ND	6.6	3.2	NE	NE	NE	4.5	NE	NE	NE	NE	NE	NE	NE	NE
Bottom of Exploration	32.0	21.0	13.5	23.5	12.0	5.0	4.0	4.5	3.5	6.0	6.0	6.0	6.0	7.0	6.0	6.0
Thickness (ft) of:																
Topsoil/Subsoil	3.0	2.5	2.0	3.0	2.0	3.0	2.5	2.0	2.5	2.0	1.5	1.5	1.5	1.8	2.0	2.5
Glacial Till	22.0	13.5	11.5	9.0	10.0	2.0	1.5	2.5	1.0	ND	ND	ND	ND	ND	ND	ND
Elev. of:																
Approx. Ground Surface [3]	1365.0	1324.0	1326.0	1255.0	1258.0	1265.0	1262.0	1248.0	1262.0	1281.0	1308.0	1328.0	1343.0	1356.0	1331.0	1329.0
Top of Topsoil/Subsoil	1365.0	1324.0	1326.0	1255.0	1258.0	1265.0	1262.0	1248.0	1262.0	1281.0	1308.0	1328.0	1343.0	1356.0	1331.0	1329.0
Top of Glacial Till	1362.0	1321.5	1324.0	1252.0	1256.0	1262.0	1259.5	1246.0	1259.5	1279.0	1306.5	1326.5	1341.5	1354.2	1329.0	1326.5
Top of Bedrock/Refusal	1340.0	1308.0	1312.5	1243.0	1246.0	1260.0	1258.0	1243.5	1258.5	NE	NE	NE	NE	NE	NE	NE
Bottom of Exploration	1333.0	1303.0	1312.5	1231.5	1246.0	1260.0	1258.0	1243.5	1258.5	1275.0	1302.0	1322.0	1337.0	1349.0	1325.0	1323.0
Groundwater	1360.2	ND	1319.4	1251.8	NE	NE	NE	1243.5	NE	NE	NE	NE	NE	NE	NE	NE

	Test Pits															
	CNTP-14	CNTP-15	CNTP-16	CNTP-17	CNTP-18	CNTP-19	CNTP-20	CNTP-21	CNTP-22	CNTP-23	CNTP-24	CNTP-25	CNTP-26	CNTP-27	CNTP-28	CNTP-29
Depth (ft) to:																
Topsoil/Subsoil	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Glacial Till	3.0	2.5	2.5	3.0	2.5	2.5	2.5	1.8	2.0	2.5	1.5	2.5	3.0	3.0	1.5	2.0
Bedrock or Refusal	4.0	5.0	4.5	5.0	4.5	NE	NE	NE	6.3	NE	NE	4.0	5.0	8.5	6.0	NE
Groundwater [2]	NE	NE	NE	NE	NE	4.9	NE	NE	NE	NE	NE	NE	NE	NE	NE	NE
Bottom of Exploration	4.0	5.0	4.5	5.0	4.5	6.0	6.0	5.0	6.3	6.0	6.0	4.0	5.0	8.5	6.0	6.0
Thickness (ft) of:																
Topsoil/Subsoil	3.0	2.5	2.5	3.0	2.5	2.5	2.5	1.8	2.0	2.5	1.5	2.5	3.0	3.0	1.5	2.0
Glacial Till	1.0	2.5	2.0	2.0	2.0	ND	ND	ND	4.3	ND	ND	1.5	2.0	5.5	4.5	ND
Elev. of:																
Approx. Ground Surface [3]	1270.0	1263.0	1262.0	1241.0	1273.0	1250.0	1258.0	1246.0	1326.0	1333.0	1365.0	1379.0	1260.0	1315.0	1351.0	1375.0
Top of Topsoil/Subsoil	1270.0	1263.0	1262.0	1241.0	1273.0	1250.0	1258.0	1246.0	1326.0	1333.0	1365.0	1379.0	1260.0	1315.0	1351.0	1375.0
Top of Glacial Till	1267.0	1260.5	1259.5	1238.0	1270.5	1247.5	1255.5	1244.2	1324.0	1330.5	1363.5	1376.5	1257.0	1312.0	1349.5	1373.0
Top of Bedrock/Refusal	1266.0	1258.0	1257.5	1236.0	1268.5	NE	NE	NE	1319.7	NE	NE	1375.0	1255.0	1306.5	1345.0	NE
Bottom of Exploration	1266.0	1258.0	1257.5	1236.0	1268.5	1244.0	1252.0	1241.0	1319.7	1327.0	1359.0	1375.0	1255.0	1306.5	1345.0	1369.0
Groundwater	NE	NE	NE	NE	NE	1245.1	NE	NE	NE	NE	NE	NE	NE	NE	NE	NE

Notes:
1. NE = Not Encountered, ND = Not Determined/Measured
2. Groundwater readings were taken during conditions stated on the boring and test pit logs.
3. Ground surface elevations were interpolated by GZA from a plan provided by the Civil1.
4. Groundwater observation wells were installed in borings CNGZ-7 and CNGZ-8 and represent stabilized water level readings. All other groundwater measurements were made under the conditions stated on the exploration logs.

FIGURES



GZA GeoEnvironmental, Inc.
Engineers and Scientists
655 Winding Brook Drive Suite 402
Glastonbury, Connecticut 06033
(860) 286-8900



USGS 7.5 MINUTE QUADRANGLE BASE MAP
NORFOLK, CONNECTICUT
1997

SITE LOCUS

WIND COLEBROOK NORTH
COLEBROOK, CONNECTICUT

PROJ MGR: DTK	REVIEWED BY: DTK	PROJECT NO. 05.0044818.02
DESIGNED BY: JER	DRAWN BY: MJS	DATE: 08-15-11

THIS MAP HAS BEEN COMPILED FROM OTHER MAPS AND/OR SOURCES OF INFORMATION.
THIS MAP SHOULD NOT BE CONSTRUED AS A PROPERTY SURVEY, NOR USED FOR CONSTRUCTION PURPOSES.

0 1,000 2,000 4,000 6,000 8,000
Scale in Feet

N

FIGURE
1

 J:\Vernon_44,500-44,999\44818.d78\44818-02.mmw\GIS\mxd\SITE LOCUS.mxd, 8/26/2011, 9:07:17 AM, mark.howland



LEGEND

CNGZ-1 LOCATION OF BORING PERFORMED BY GZA

CNTP-1 LOCATION OF TEST PIT PERFORMED BY GZA

NOTES

1. BASE MAP TAKEN FROM AN ELECTRONIC FILE TITLED "3063 TP and Boring locations for GZA.dwg", DATED 9/27/2011, BY CIVIL1.

BNE WIND FARM - COLEBROOK NORTH

EXPLORATION LOCATION PLAN

PREPARED BY: GZA GeoEnvironmental, Inc. Engineers and Scientists www.gza.com	PREPARED FOR: CIVIL1
PROJ MGR: DTK	REVIEWED BY: DTK
DESIGNED BY: JAR	DRAWN BY: JAR
DATE: SEPTEMBER 2011	PROJECT NO.: 44815.20
CHECKED BY: DTK	SCALE: AS SHOWN
REVISION NO.: 0	FIGURE 1
	SHEET NO. 1 OF 2

APPENDIX A
LIMITATIONS

LIMITATIONS

Explorations

1. The analyses and recommendations submitted in this report are based in part upon the data obtained from subsurface explorations. The nature and extent of variations between these explorations may not become evident until construction. If variations then appear evident, it will be necessary to reevaluate the recommendations of this report.

2. The generalized soil profile described in the text is intended to convey trends in subsurface conditions. The boundaries between strata are approximate and idealized and have been developed by interpretations of widely spaced explorations and samples; actual soil transitions are probably more erratic. For specific information, refer to the exploration logs.

3. Water level readings have been made in the explorations at times and under conditions stated on the exploration logs. These data have been reviewed and interpretations have been made in the text of this report. However, it must be noted that fluctuations in the level of the groundwater may occur due to variations in rainfall, temperature, and other factors occurring since the time measurements were made.

Review

4. In the event that any changes in the nature, design or location of the proposed wind turbines are planned, the conclusions and recommendations contained in this report shall not be considered valid unless the changes are reviewed and conclusions of this report modified or verified in writing by GZA. It is recommended that this firm be provided the opportunity for a general review of final design and specifications in order that earthwork and foundation recommendations may be properly interpreted and implemented in the design and specifications.

Construction

5. It is recommended that this firm be retained to provide soil engineering services during construction of the excavation and foundation phases of the work. This is to observe compliance with the design concepts, specifications, and recommendations and to allow design changes in the event that subsurface conditions differ from those anticipated prior to start of construction.

Use of Report

6. This report has been prepared for the exclusive use of Civil1 and their design consultants for specific application to the proposed BNE Wind Farm Development at Colebrook North, in Colebrook, Connecticut in accordance with generally accepted soil and foundation engineering practices. No warranty, express or implied, is made.

7. This soil and foundation engineering report has been prepared for this project by GZA. This report is for design purposes only and is not sufficient to prepare an accurate bid. Contractors wishing a copy of the report may secure it with the understanding that its scope is limited to design considerations only.

8. This report may contain comparative cost estimates for the purpose of evaluating alternative foundation schemes. These estimates may also involve approximate quantity evaluations. It should be noted that quantity estimates may not be accurate enough for construction bids. Since GZA has no control over labor and materials cost and design, the estimates of construction costs have been made on the basis of experience. GZA does not guarantee the accuracy of cost estimates as compared to contractor's bids for construction costs.

APPENDIX B
BORING LOGS

TEST BORING LOG

GZA GeoEnvironmental, Inc.
Engineers and Scientists

BNE WIND FARM NORTH
COLEBROOK, CONNECTICUT

EXPLORATION NO.: CNGZ-5
SHEET: 1 of 2
PROJECT NO: 44818.02
REVIEWED BY: JER

Logged By: T. Bjartmarz
Drilling Co.: New Hampshire Borings
Foreman: Richard Lenard

Type of Rig: ATV
Rig Model: Wildcat
Drilling Method: Casing/Rotary Wash

Boring Location: Turbine 3 North, See Plan
Ground Surface Elev. (ft.): 1365
Final Boring Depth (ft.): 32
Date Start - Finish: 7/27/2011 - 7/27/2011

H. Datum: Project
V. Datum: Project

Hammer Type: Safety Hammer
Hammer Weight (lb.): 140
Hammer Fall (in.): 30
Auger or Casing O.D./I.D Dia (in.): 4" O.D.

Sampler Type: Split Spoon
Sampler O.D. (in.): 2
Sampler Length (in.): 24
Rock Core Size: NX

Groundwater Depth (ft.)

Date	Time	Water Depth	Stab. Time
7/27/11	1800	10'	5 min.
8/23/11	1100	4.8' See Note 2	26 days

Depth (ft)	Casing Blows/ Core Rate	Sample No.	Sample Depth (ft.)	Pen. (in)	Rec. (in)	Blows per 6"	SPT Value	Sample Description Modified Burmister	Remark	Field Test Data	Stratum Depth (ft)	Stratum Description	Stratum Elev. (ft.)	No Equipment Installed
		S-1	0-2	24	13	1 1 1 2	2	Loose, brown, fine to coarse SAND and ORGANIC MATTER, some Silt	1		0.5	TOPSOIL	1364.5	
											3	SUBSOIL	1362.0	
5		S-2	5-7	24	17	6 13 14 16	27	Medium dense, gray, fine to coarse SAND, little fine Gravel, little Silt	2					
10		S-3	10-12	24	13	2 12 6 9	18	Medium dense, gray, fine to coarse SAND, little fine to coarse Gravel, little Silt						
15		S-4	15-17	24	18	11 15 24 32	39	Dense, gray, fine to coarse SAND, some Silt, little fine Gravel				GLACIAL TILL		
20		S-5	20-21.5	18	16	29 53 100/6"	R	Gray, fine to coarse SAND, some fine to coarse Gravel, little Silt						
25		S-6	25-25	0	0	100/0"	R	Spoon Refusal			25		1340.0	
	2	C-1	26-32	72	59			Top 12": Hard, fresh to slightly weathered, slightly fractured, fine to medium grained, high angle, balck and white, GNEISS				BEDROCK		
	1													
	1													
30	1							Bottom 47": Soft to moderately						

REMARKS

1 - Exploration advanced from ground surface to 10 feet belwo grade using 4" solid stem augers. Exploration advanced from 10 feet below grade to end of exploration using casing and rotary wash techniques.
2 - On August 23, 2011, borehole measured to be open to about 7.5 feet below grade. Groundwater level measured in open hole.

Stratification lines represent approximate boundaries between soil and bedrock types. Actual transitions may be gradual. Water level readings have been made at the times and under the conditions stated. Fluctuations of groundwater may occur due to other factors than those present at the times the measurements were made.

Exploration No.: CNGZ-5

GZA TEMPLATE TEST BORING W/ EQUIP.; 8/25/2011; 9:10:31 AM

TEST BORING LOG

GZA GeoEnvironmental, Inc.
Engineers and Scientists

BNE WIND FARM NORTH
COLEBROOK, CONNECTICUT

EXPLORATION NO.: CNGZ-5
SHEET: 2 of 2
PROJECT NO: 44818.02
REVIEWED BY: JER

Logged By: T. Bjartmarz
Drilling Co.: New Hampshire Borings
Foreman: Richard Lenard

Type of Rig: ATV
Rig Model: Wildcat
Drilling Method: Casing/Rotary Wash

Boring Location: Turbine 3 North, See Plan
Ground Surface Elev. (ft.): 1365
Final Boring Depth (ft.): 32
Date Start - Finish: 7/27/2011 - 7/27/2011

H. Datum: Project
V. Datum: Project

Hammer Type: Safety Hammer
Hammer Weight (lb.): 140
Hammer Fall (in.): 30
Auger or Casing O.D./I.D Dia (in.): 4" O.D.

Sampler Type: Split Spoon
Sampler O.D. (in.): 2
Sampler Length (in.): 24
Rock Core Size: NX

Groundwater Depth (ft.)

Date	Time	Water Depth	Stab. Time
7/27/11	1800	10'	5 min.
8/23/11	1100	4.8' See Note 2	26 days

Depth (ft)	Casing Blows/ Core Rate	Sample No.	Sample Depth (ft.)	Sample Pen. (in)	Sample Rec. (in)	Sample Blows per 6"	Sample SPT Value	Sample Description Modified Burmister	Remark	Field Test Data	Stratum Depth (ft.)	Stratum Description	Stratum Elev. (ft.)
	1							hard, slightly weathered, moderately fractured, high angle, black and white, GNEISS					
	1										32	BEDROCK	1333.0
								End of exploration at 32 feet.					
35													
40													
45													
50													
55													
60													

REMARKS

Stratification lines represent approximate boundaries between soil and bedrock types. Actual transitions may be gradual. Water level readings have been made at the times and under the conditions stated. Fluctuations of groundwater may occur due to other factors than those present at the times the measurements were made.

Exploration No.: CNGZ-5

GZA TEMPLATE TEST BORING W/ EQUIP.; 8/25/2011; 9:10:31 AM

TEST BORING LOG

GZA GeoEnvironmental, Inc.
Engineers and Scientists

BNE WIND FARM NORTH
COLEBROOK, CONNECTICUT

EXPLORATION NO.: CNGZ-6
SHEET: 1 of 1
PROJECT NO: 44818.02
REVIEWED BY: JER

Logged By: T. Bjartmarz
Drilling Co.: New Hampshire Borings
Foreman: Richard Lenard

Type of Rig: ATV
Rig Model: Wildcat
Drilling Method: Casing/Rotary Wash

Boring Location: Turbine 2 North, See Plan
Ground Surface Elev. (ft.): 1324
Final Boring Depth (ft.): 21
Date Start - Finish: 7/28/2011 - 7/28/2011

H. Datum: Project
V. Datum: Project

Hammer Type: Safety Hammer
Hammer Weight (lb.): 140
Hammer Fall (in.): 30
Auger or Casing O.D./I.D Dia (In.): 4" O.D.

Sampler Type: Split Spoon
Sampler O.D. (in.): 2
Sampler Length (in.): 24
Rock Core Size: NX

Groundwater Depth (ft.)

Date	Time	Water Depth	Stab. Time
		See Note	

Depth (ft)	Casing Blows/ Core Rate	Sample No.	Sample Depth (ft.)	Pen. (in)	Rec. (in)	Blows per 6"	SPT Value	Sample Description Modified Burmister	Remark	Field Test Data	Stratum Depth (ft)	Stratum Description	Stratum Elev. (ft.)
		S-1	0-2	24	17	1 1 1 3	2	Loose, brown, fine to coarse SAND, some Organic Matter, little fine Gravel, little Silt	1		0.25	TOPSOIL	1323.5
											2.5	SUBSOIL	1321.5
5		S-2	5-7	24	14	20 21 21 21	42	Dense, gray, fine to coarse SAND, some fine to coarse Gravel, little Silt					
10		S-3	10-12	24	13	9 11 36 31	47	Dense, gray, fine to coarse SAND and fine to coarse GRAVEL, little Silt (wet)				GLACIAL TILL	
15	3 2 3 5 5	S-4 C-1	15-15.2 16-21	2 60	2 60	100/2"	R	Gray, fine to coarse GRAVEL and fine to coarse SAND, little Silt Hard, slightly weathered, slightly fractured to sound, fine to medium grained, high angle, white and black, GNEISS RQD = 83%, Recovery = 100%			16		1308.0
20												BEDROCK	
								End of exploration at 21 feet.			21		1303.0
25													
30													

No Equipment Installed

REMARKS

1 - Groundwater not encountered prior to introduction of drilling fluid at 2 feet below grade.

Stratification lines represent approximate boundaries between soil and bedrock types. Actual transitions may be gradual. Water level readings have been made at the times and under the conditions stated. Fluctuations of groundwater may occur due to other factors than those present at the times the measurements were made.

Exploration No.: CNGZ-6

GZA TEMPLATE TEST BORING W/ EQUIP.; 8/25/2011; 9:10:31 AM

TEST BORING LOG

GZA GeoEnvironmental, Inc.
Engineers and Scientists

BNE WIND FARM NORTH
COLEBROOK, CONNECTICUT

EXPLORATION NO.: CNGZ-7
SHEET: 1 of 1
PROJECT NO: 44818.02
REVIEWED BY: JER

Logged By: T. Bjartmarz
Drilling Co.: New Hampshire Borings
Foreman: Richard Lenard

Type of Rig: ATV
Rig Model: Wildcat
Drilling Method: HSA

Boring Location: 30' Northeast of Turbine 2
Ground Surface Elev. (ft.): 1326
Final Boring Depth (ft.): 13.5
Date Start - Finish: 7/28/2011 - 7/28/2011

Northing: Plan
Project
V. Datum:
Project

Hammer Type: Safety Hammer
Hammer Weight (lb.): 140
Hammer Fall (in.): 30
Auger or Casing O.D./I.D Dia (in.): 4-1/4" I.D.

Sampler Type: Split Spoon
Sampler O.D. (in.): 2
Sampler Length (in.): 24
Rock Core Size: NX

Groundwater Depth (ft.)

Date	Time	Water Depth	Stab. Time
7/29/11	715	8.53	1 day
8/23/11	1100	6.6'	25 days

Depth (ft)	Casing Blows/ Core Rate	Sample No.	Sample Depth (ft.)	Pen. (in)	Rec. (in)	Blows per 6"	SPT Value	Sample Description Modified Burmister	Remark	Field Test Data
5		S-1	5-7	24	18.5	13 20 19 13	39	Dense, gray, fine to coarse SAND and fine to coarse GRAVEL, little Silt	1	
15								End of exploration at 13.5 feet.	2 3	

Stratum Description (Depth (ft.) / Elev. (ft.))

- 0.25 TOPSOIL 1325.5
- SUBSOIL
- 2 1324.0
- GLACIAL TILL
- 13.5 1312.5



REMARKS

1 - Stratum descriptions and depths of Forest Mat and Subsoil are based on visual observations of borehole following removal of casing.
2 - Auger refusal at 13.5 feet below ground surface.
3 - 5 feet of 2 inch diameter, Schedule 40, threaded, flush joint, 10-slot PVC well screen set at approximately 13 feet below grade. Well completed to ground surface with a 2 inch diameter, Schedule 40, threaded, flush joint, PVC riser. Filter sand placed in annulus around well from 8 to 13 feet below grade. Remaining annulus filled with drill cuttings from 0 to 8 feet below grade.

Stratification lines represent approximate boundaries between soil and bedrock types. Actual transitions may be gradual. Water level readings have been made at the times and under the conditions stated. Fluctuations of groundwater may occur due to other factors than those present at the times the measurements were made.

Exploration No.: CNGZ-7

GZA TEMPLATE TEST BORING W/ EQUIP.; 8/25/2011; 9:10:32 AM

TEST BORING LOG

GZA GeoEnvironmental, Inc.
Engineers and Scientists

BNE WIND FARM NORTH
COLEBROOK, CONNECTICUT

EXPLORATION NO.: CNGZ-8
SHEET: 1 of 1
PROJECT NO: 44818.02
REVIEWED BY: JER

Logged By: T. Bjartmarz
Drilling Co.: New Hampshire Borings
Foreman: Richard Lenard

Type of Rig: ATV
Rig Model: Wildcat
Drilling Method: Casing/Rotary Wash

Boring Location: Turbine 1 North, See Plan
Ground Surface Elev. (ft.): 1255
Final Boring Depth (ft.): 23.5
Date Start - Finish: 7/28/2011 - 7/28/2011

H. Datum: Project
V. Datum: Project

Hammer Type: Safety Hammer
Hammer Weight (lb.): 140
Hammer Fall (in.): 30
Auger or Casing O.D./I.D Dia (in.): 4" O.D.

Sampler Type: Split Spoon
Sampler O.D. (in.): 2
Sampler Length (in.): 24
Rock Core Size: NX

Groundwater Depth (ft.)

Date	Time	Water Depth	Stab. Time
7/29/11	730	4.28	16 hours
8/23/11	1100	3.2'	25 days

Depth (ft)	Casing Blows/ Core Rate	Sample No.	Sample Depth (ft.)	Pen. (in)	Rec. (in)	Blows per 6"	SPT Value	Sample Description Modified Burmister	Remark	Field Test Data
		S-1	0-2	24	15	1 3 5 1	8	Loose, brown, fine to coarse SAND and ORGANIC MATTER, little Silt, trace fine Gravel	1	
5		S-2	6-8	24	13	12 32 50 48	82	Very dense, brown, fine to coarse SAND and fine to coarse GRAVEL, little Silt (wet)	2	
10		S-3	10-12	10	10	22 100/4"	R	Brown, fine to coarse SAND and fine to coarse GRAVEL, little Silt (wet)		
15		C-1	13.5-18.5	60	58.5			Hard, slightly weathered, slightly fractured, fine to medium grained, high angle, white and black, GNEISS RQD = 69%, Recovery = 98%		
20		C-2	18.5-23.5	60	58			Hard, slightly weathered, sound to slightly fractured, fine to medium grained, white and black, GNEISS RQD = 90%, Recovery = 97%		
25								End of exploration at 23.5 feet.	3	
30										

Depth (ft)	Stratum Description	Elev. (ft.)
0.25	TOPSOIL	1254.5
	SUBSOIL	
3		1252.0
	GLACIAL TILL	
12		1243.0
	BEDROCK	
23.5		1231.5



REMARKS

1 - Borehole advanced from 0 to 10 feet below grade using 4" solid stem augers. Borehole advanced from 10 feet below grade to end of exploration using casing and rotary wash techniques.
2 - Difficulty drilling may indicate rock or cobble from 5 to 6 feet below grade.
3 - 5 feet of 2 inch diameter, Schedule 40, threaded, flush joint, 10-slot PVC well screen set at approximately 12 feet below grade. Well completed to ground surface with a 2 inch diameter, Schedule 40, threaded, flush joint, PVC riser. Filter sand placed below well and in annulus around well from 6 to 23.5 feet below grade. Remaining annulus filled with spoils from 0 to 6 feet below grade.

Stratification lines represent approximate boundaries between soil and bedrock types. Actual transitions may be gradual. Water level readings have been made at the times and under the conditions stated. Fluctuations of groundwater may occur due to other factors than those present at the times the measurements were made.

Exploration No.: CNGZ-8

GZA TEMPLATE TEST BORING W/ EQUIP.; 8/25/2011; 9:10:32 AM

TEST BORING LOG

GZA GeoEnvironmental, Inc.
Engineers and Scientists

BNE WIND FARM NORTH
COLEBROOK, CONNECTICUT

EXPLORATION NO.: CNGZ-9
SHEET: 1 of 1
PROJECT NO: 44818.02
REVIEWED BY: JER

Logged By: T. Bjartmarz
Drilling Co.: New Hampshire Borings
Foreman: Richard Lenard

Type of Rig: ATV
Rig Model: Wildcat
Drilling Method: HSA

Boring Location: See Plan
Ground Surface Elev. (ft.): 1258
Final Boring Depth (ft.): 12
Date Start - Finish: 7/28/2011 - 7/28/2011

H. Datum: Project
V. Datum: Project

Hammer Type: Safety Hammer
Hammer Weight (lb.): 140
Hammer Fall (in.): 30
Auger or Casing O.D./I.D Dia (in.): 4-1/4" I.D.

Sampler Type: Split Spoon
Sampler O.D. (in.): 2
Sampler Length (in.): 24
Rock Core Size: NX

Groundwater Depth (ft.)

Date	Time	Water Depth	Stab. Time
		See Note	

Depth (ft)	Casing Blows/ Core Rate	Sample No.	Sample Depth (ft.)	Pen. (in)	Rec. (in)	Blows per 6"	SPT Value	Sample Description Modified Burmister	Remark	Field Test Data	Stratum Depth (ft)	Stratum Description	Stratum Elev. (ft.)
									1		0.25	TOPSOIL	1257.8
											2	SUBSOIL	1256.0
5		S-1	5-7	24	13	27 37 40 42	77	Very dense, gray, fine to coarse SAND and fine to coarse GRAVEL, little Silt (wet)				GLACIAL TILL	
10		S-2	10-12	8	4	58 100/2"	R	Gray, fine to coarse SAND and fine to coarse GRAVEL, little Silt (wet)			12		1246.0
								End of exploration at 12 feet.	2 3				
15													
20													
25													
30													

No Equipment Installed

REMARKS

1 - Stratum descriptions and depths of Forest Mat and Subsoil are based on visual observations of borehole following removal of casing.
2 - Auger refusal at 12 feet below grade.
3 - Groundwater not encountered.

Stratification lines represent approximate boundaries between soil and bedrock types. Actual transitions may be gradual. Water level readings have been made at the times and under the conditions stated. Fluctuations of groundwater may occur due to other factors than those present at the times the measurements were made.

Exploration No.: CNGZ-9

GZA TEMPLATE TEST BORING W/ EQUIP.; 8/25/2011; 9:10:32 AM

APPENDIX C
TEST PIT LOGS

TEST PIT FIELD LOG

GZA GeoEnvironmental, Inc. Engineers and Scientists	PROJECT *BNE Wind Turbine Project* *Colebrook, CT*	Test Pit No. CNTP-2 File No. 44818.02 Date 7/25/2011
GZA Engineer T. Bjartmarz Weather 70s overcast	EXCAVATION EQUIPMENT Contractor HTS Construction Operator Bruce Remillard Make Volvo Model EC35 Capacity 0.25 cu.yd. Reach 15 ft.	Ground Elevation 1265'± Time Started 809 Time Completed 815

Depth	SOIL DESCRIPTION	Excav. Effort	Boulder Count Qty. Class.	Remark No.
--- 1' ---	0.5' Dark brown, fine to coarse SAND and ORGANIC MATTER, little fine to coarse Gravel, trace Silt Topsoil)	D	3A	
--- 2' ---	Brown, fine to coarse SAND and fine to coarse GRAVEL, little Roots, little Silt (Subsoil)	D	4A, 2B	
--- 3' ---	3'	D	8A, 2B	
--- 4' ---	Gray, fine to coarse SAND and fine to coarse GRAVEL, some Silt (Glacial Till)	D		
--- 5' ---	5'	D		1, 2
--- 6' ---	Excavator Refusal at 5'			
--- 7' ---				
--- 8' ---				
--- 9' ---				
--- 10' ---				
--- 11' ---				
--- 12' ---				
--- 13' ---				
--- 14' ---				

REMARKS:
1. Excavator refusal on bedrock at 5 feet below grade.
2. Groundwater not encountered in test pit.

TEST PIT PLAN



Depth = 5 ft.
Volume = 3 cu.yd.

LEGEND

BOULDER COUNT

Size Range Classification	Letter Designation
6" - 18"	A
18" - 36"	B
36" and Larger	C

PROPORTIONS USED

TRACE (TR)	0-10%
LITTLE (LI)	10-20%
SOME (SO)	20-35%
AND	35-50%

ABBREVIATIONS

F - Fine
M - Medium
C - Coarse
F/M - Fine to Medium
F/C - Fine to Coarse
V - Very
GR - Gray
BN - Brown
YEL - Yellow

EXCAVATION EFFORT

E - Easy
M - Moderate
D - Difficult

GROUNDWATER

Elapsed Time to Reading (hours) NE G.W.L.

TEST PIT FIELD LOG

GZA GeoEnvironmental, Inc. Engineers and Scientists	PROJECT *BNE Wind Turbine Project* *Colebrook, CT*	Test Pit No. CNTP-3 File No. 44818.02 Date 7/25/2011
GZA Engineer T. Bjartmarz Weather 70s overcast	EXCAVATION EQUIPMENT Contractor HTS Construction Operator Bruce Remillard Make Volvo Model EC35 Capacity 0.25 cu.yd. Reach 15 ft.	Ground Elevation 1262'± Time Started 930 Time Completed 945

Depth	SOIL DESCRIPTION	Excav. Effort	Boulder Count Qty. Class.	Remark No.
--- 1' --- 1'	Dark brown, fine to coarse SAND and ORGANIC MATTER, little fine to coarse Gravel, trace Silt (Topsoil)	D	5A, 1B	
--- 2' --- 2.5'	Brown, fine to coarse SAND and fine to coarse GRAVEL, little Roots, little Silt (Subsoil)	D	5A, 1B	
--- 3' --- 4'	Gray, fine to coarse SAND and fine to coarse GRAVEL, some Silt (Glacial Till)	D	3A	
--- 4' ---		D		1. 2
--- 5' ---	Excavator Refusal at 4'			
--- 6' ---				
--- 7' ---				
--- 8' ---				
--- 9' ---				
--- 10' ---				
--- 11' ---				
--- 12' ---				
--- 13' ---				
--- 14' ---				

REMARKS:
1. Excavator refusal on bedrock at 4 feet below grade.
2. Groundwater not encountered in test pit.

TEST PIT PLAN



Depth = 4 ft.
Volume = 2.5 cu.yd.

LEGEND

BOULDER COUNT

Size Range Classification	Letter Designation
6" - 18"	A
18" - 36"	B
36" and Larger	C

PROPORTIONS USED

TRACE (TR)	0-10%
LITTLE (LI)	10-20%
SOME (SO)	20-35%
AND	35-50%

ABBREVIATIONS

F - Fine
M - Medium
C - Coarse
F/M - Fine to Medium
F/C - Fine to Coarse
V - Very
GR - Gray
BN - Brown
YEL - Yellow

EXCAVATION EFFORT

E - Easy
M - Moderate
D - Difficult

GROUNDWATER

Elapsed Time to Reading (hours) NE G.W.L.

TEST PIT FIELD LOG

GZA GeoEnvironmental, Inc. Engineers and Scientists	PROJECT *BNE Wind Turbine Project* *Colebrook, CT*	Test Pit No. CNTP-4 File No. 44818.02 Date 7/25/2011
GZA Engineer T. Bjartmarz Weather 70s overcast	EXCAVATION EQUIPMENT Contractor HTS Construction Operator Bruce Remillard Make Volvo Model EC35 Capacity 0.25 cu.yd. Reach 15 ft.	Ground Elevation 1248'± Time Started 1010 Time Completed 1022

Depth	SOIL DESCRIPTION	Excav. Effort	Boulder Count Qty. Class.	Remark No.
--- 1' ---	1' Dark brown, fine to coarse SAND and ORGANIC MATTER, little fine to coarse Gravel, trace Silt (Topsoil)	M	3A	
--- 2' ---	2' Brown, fine to coarse SAND and fine to coarse GRAVEL, little Roots, little Silt (Subsoil)	D	3A	
--- 3' ---	Gray, fine to coarse SAND and fine to coarse GRAVEL, some Silt (Glacial Till)	D	4A	
--- 4' ---		D		
--- 5' ---	4.5' Excavator Refusal at 4.5'	D		1, 2
--- 6' ---				
--- 7' ---				
--- 8' ---				
--- 9' ---				
--- 10' ---				
--- 11' ---				
--- 12' ---				
--- 13' ---				
--- 14' ---				

REMARKS:
1. Excavator refusal on bedrock at 4.5 feet below grade.
2. Groundwater observed at approximatley 4.5 feet below grade.

TEST PIT PLAN



Depth = 4.5 ft.
Volume = 3 cu.yd.

LEGEND

BOULDER COUNT

Size Range Classification	Letter Designation
6" - 18"	A
18" - 36"	B
36" and Larger	C

PROPORTIONS USED

TRACE (TR)	0-10%
LITTLE (LI)	10-20%
SOME (SO)	20-35%
AND	35-50%

ABBREVIATIONS

F - Fine
M - Medium
C - Coarse
F/M - Fine to Medium
F/C - Fine to Coarse
V - Very
GR - Gray
BN - Brown
YEL - Yellow

EXCAVATION EFFORT

E - Easy
M - Moderate
D - Difficult

GROUNDWATER

Elapsed Time to Reading (hours) 4.5' G.W.L.

TEST PIT FIELD LOG

GZA GeoEnvironmental, Inc. Engineers and Scientists	PROJECT *BNE Wind Turbine Project* *Colebrook, CT*	Test Pit No. CNTP-6 File No. 44818.02 Date 7/25/2011
GZA Engineer J. Davis Weather 70s rain	EXCAVATION EQUIPMENT Contractor HTS Construction Operator Bruce Remillard Make Volvo Model EC35 Capacity 0.25 cu.yd. Reach 15 ft.	Ground Elevation 1262'± Time Started 1240 Time Completed 1245

Depth		SOIL DESCRIPTION	Excav. Effort	Boulder Count Qty. Class.	Remark No.
--- 1' ---	1'	Dark brown, fine to coarse SAND and SILT, little Organics (Topsoil)	D	3A, 1B	
--- 2' ---	2.5'	Light brown, fine to coarse SAND, some fine to coarse Gravel, little Silt, trace Roots (Subsoil)	D	6A, 2B	
--- 3' ---	3.5'	Light brown, fine to coarse SAND and fine to coarse GRAVEL, some Silt (Glacial Till)	D	6A	
--- 4' ---		Excavator Refusal at 3.5'	D	3A	1, 2
--- 5' ---					
--- 6' ---					
--- 7' ---					
--- 8' ---					
--- 9' ---					
--- 10' ---					
--- 11' ---					
--- 12' ---					
--- 13' ---					
--- 14' ---					

REMARKS:
1. Excavator refusal on bedrock at 3.5 feet below grade.
2. Groundwater not encountered in test pit.

TEST PIT PLAN



Depth = 3.5 ft.
Volume = 2 cu.yd.

LEGEND

BOULDER COUNT

Size Range Classification	Letter Designation
6" - 18"	A
18" - 36"	B
36" and Larger	C

PROPORTIONS USED

TRACE (TR)	0-10%
LITTLE (LI)	10-20%
SOME (SO)	20-35%
AND	35-50%

ABBREVIATIONS

F - Fine
M - Medium
C - Coarse
F/M - Fine to Medium
F/C - Fine to Coarse
V - Very
GR - Gray
BN - Brown
YEL - Yellow

EXCAVATION EFFORT

E - Easy
M - Moderate
D - Difficult

GROUNDWATER

Elapsed Time to Reading (hours) NE G.W.L.

TEST PIT FIELD LOG

GZA GeoEnvironmental, Inc. Engineers and Scientists	PROJECT *BNE Wind Turbine Project* *Colebrook, CT*	Test Pit No. CNTP-7 File No. 44818.02 Date 7/25/2011
GZA Engineer J. Davis Weather 70s rain	EXCAVATION EQUIPMENT Contractor HTS Construction Operator Bruce Remillard Make Volvo Model EC35 Capacity 0.25 cu.yd. Reach 15 ft.	Ground Elevation 1281'± Time Started 1305 Time Completed 1315

Depth			SOIL DESCRIPTION	Excav. Effort	Boulder Count Qty. Class.	Remark No.
---	1'	---	1' Dark brown, fine to coarse SAND and SILT, some Roots, little fine to coarse Gravel (Topsoil)	M	3A, 2B	
---	2'	---	2' Light brown, fine to coarse SAND and fine to coarse GRAVEL, some Silt, trace Roots (Subsoil)	M	1A	
---	3'	---	Light brown, fine to coarse SAND and fine to coarse GRAVEL, some Silt, (Glacial Till)	M	2A	
---	4'	---		M		
---	5'	---		M	1A	
---	6'	---	6'	M	1A	1, 2
---	7'	---	End of Exploration at 6'			
---	8'	---				
---	9'	---				
---	10'	---				
---	11'	---				
---	12'	---				
---	13'	---				
---	14'	---				

REMARKS:
1. Exploration terminated within glacial till.
2. Groundwater not encountered in test pit.

TEST PIT PLAN



Depth = 6 ft.
Volume = 5 cu.yd.

LEGEND

BOULDER COUNT

Size Range Classification	Letter Designation
6" - 18"	A
18" - 36"	B
36" and Larger	C

PROPORTIONS USED

TRACE (TR)	0-10%
LITTLE (LI)	10-20%
SOME (SO)	20-35%
AND	35-50%

ABBREVIATIONS

F - Fine
M - Medium
C - Coarse
F/M - Fine to Medium
F/C - Fine to Coarse
V - Very
GR - Gray
BN - Brown
YEL - Yellow

EXCAVATION EFFORT

E - Easy
M - Moderate
D - Difficult

GROUNDWATER

Elapsed Time to Reading (hours) NE G.W.L.

TEST PIT FIELD LOG

GZA GeoEnvironmental, Inc. Engineers and Scientists	PROJECT *BNE Wind Turbine Project* *Colebrook, CT*	Test Pit No. CNTP-8 File No. 44818.02 Date 7/25/2011
GZA Engineer J. Davis Weather 70s rain	EXCAVATION EQUIPMENT Contractor HTS Construction Operator Bruce Remillard Make Volvo Model EC35 Capacity 0.25 cu.yd. Reach 15 ft.	Ground Elevation 1308'± Time Started 1315 Time Completed 1330

Depth	SOIL DESCRIPTION	Excav. Effort	Boulder Count Qty. Class.	Remark No.
0.5'	Dark brown, fine to coarse SAND and SILT, trace Roots (Topsoil)			
--- 1' ---	Tan-brown, fine to coarse SAND, some fine to coarse Gravel, some	E	1A	
1.5'	Silt, trace Roots (Subsoil)			
--- 2' ---	Gray-brown, fine to coarse SAND, some fine to coarse Gravel, little Silt,	M	3A	
--- 3' ---	(Glacial Till)	D	2A	
--- 4' ---		D	1A	
--- 5' ---		D	2A	
--- 6' --- 6'		D	2A	1, 2
--- 7' ---	End of Exploration at 6'			
--- 8' ---				
--- 9' ---				
--- 10' ---				
--- 11' ---				
--- 12' ---				
--- 13' ---				
--- 14' ---				

REMARKS:
1. Exploration terminated within glacial till.
2. Groundwater not encountered in test pit.

TEST PIT PLAN



Depth = 6 ft.
Volume = 4 cu.yd.

LEGEND

BOULDER COUNT

Size Range Classification	Letter Designation
6" - 18"	A
18" - 36"	B
36" and Larger	C

PROPORTIONS USED

TRACE (TR)	0-10%
LITTLE (LI)	10-20%
SOME (SO)	20-35%
AND	35-50%

ABBREVIATIONS

F - Fine
M - Medium
C - Coarse
F/M - Fine to Medium
F/C - Fine to Coarse
V - Very
GR - Gray
BN - Brown
YEL - Yellow

EXCAVATION EFFORT

E - Easy
M - Moderate
D - Difficult

GROUNDWATER

Elapsed Time to Reading (hours) NE G.W.L.

TEST PIT FIELD LOG

GZA GeoEnvironmental, Inc. Engineers and Scientists	PROJECT *BNE Wind Turbine Project* *Colebrook, CT*	Test Pit No. CNTP-9 File No. 44818.02 Date 7/25/2011
GZA Engineer J. Davis Weather 70s Rain	EXCAVATION EQUIPMENT Contractor HTS Construction Operator Bruce Remillard Make Volvo Model EC35 Capacity 0.25 cu.yd. Reach 15 ft.	Ground Elevation 1328'± Time Started 1335 Time Completed 1350

Depth	SOIL DESCRIPTION	Excav. Effort	Boulder Count Qty. Class.	Remark No.
--- 1' ---	0.5' Dark brown, fine to coarse SAND and SILT, some Organics (Topsoil)			
	1.5' Brown, fine to coarse SAND, some Silt, little fine to coarse Gravel, trace Roots (Subsoil)	E		
--- 2' ---	Gray-brown, fine to coarse SAND, some Silt, some fine to coarse Gravel (Glacial Till)	M	2A	
--- 3' ---		D	1A	
--- 4' ---		D	2A	
--- 5' ---		D	1A	
--- 6' ---	6'	D	2A	1, 2
--- 7' ---	End of Exploration at 6'			
--- 8' ---				
--- 9' ---				
--- 10' ---				
--- 11' ---				
--- 12' ---				
--- 13' ---				
--- 14' ---				

REMARKS:
1. End of exploration at 6'±. Exploration terminated within glacial till.
2. Groundwater not encountered in test pit.

TEST PIT PLAN



Depth = 6 ft.
Volume = 4 cu.yd.

LEGEND

BOULDER COUNT

Size Range Classification	Letter Designation
6" - 18"	A
18" - 36"	B
36" and Larger	C

PROPORTIONS USED

TRACE (TR)	0-10%
LITTLE (LI)	10-20%
SOME (SO)	20-35%
AND	35-50%

ABBREVIATIONS

F - Fine
M - Medium
C - Coarse
F/M - Fine to Medium
F/C - Fine to Coarse
V - Very
GR - Gray
BN - Brown
YEL - Yellow

EXCAVATION EFFORT

E - Easy
M - Moderate
D - Difficult

GROUNDWATER

Elapsed Time to Reading (hours) — NE — G.W.L.

TEST PIT FIELD LOG

GZA GeoEnvironmental, Inc. Engineers and Scientists	PROJECT *BNE Wind Turbine Project* *Colebrook, CT*	Test Pit No. CNTP-10 File No. 44818.02 Date 7/25/2011
GZA Engineer J. Davis Weather 70s rain	EXCAVATION EQUIPMENT Contractor HTS Construction Operator Bruce Remillard Make Volvo Model EC35 Capacity 0.25 cu.yd. Reach 15 ft.	Ground Elevation 1343'± Time Started 1400 Time Completed 1420

Depth			SOIL DESCRIPTION	Excav. Effort	Boulder Count Qty. Class.	Remark No.
---	1'	---	0.5' Dark brown, fine to coarse SAND and SILT, little fine Gravel, little Organics (Topsoil)	E	1A	
---	2'	---	1.5' Brown, fine to coarse SAND, some Silt, trace fine to coarse Gravel, trace Roots (Subsoil)	M	1B	
---	3'	---	Light brown-gray, fine to coarse SAND, some Silt, little fine to coarse Gravel (Glacial Till)	D	1A	
---	4'	---		D		
---	5'	---		D	1A	
---	6'	---	6'	D		1, 2
---	7'	---	End of Exploration at 6'			
---	8'	---				
---	9'	---				
---	10'	---				
---	11'	---				
---	12'	---				
---	13'	---				
---	14'	---				

REMARKS:
1. Exploration terminated within glacial till.
2. Groundwater not encountered in test pit.

TEST PIT PLAN



Depth = 6 ft.
Volume = 4 cu.yd.

LEGEND

BOULDER COUNT

Size Range Classification	Letter Designation
6" - 18"	A
18" - 36"	B
36" and Larger	C

PROPORTIONS USED

TRACE (TR)	0-10%
LITTLE (LI)	10-20%
SOME (SO)	20-35%
AND	35-50%

ABBREVIATIONS

F - Fine
M - Medium
C - Coarse
F/M - Fine to Medium
F/C - Fine to Coarse
V - Very
GR - Gray
BN - Brown
YEL - Yellow

EXCAVATION EFFORT

E - Easy
M - Moderate
D - Difficult

GROUNDWATER

Elapsed Time to Reading (hours) ▽NE G.W.L.

TEST PIT FIELD LOG

GZA GeoEnvironmental, Inc. Engineers and Scientists	PROJECT *BNE Wind Turbine Project* *Colebrook, CT*	Test Pit No. CNTP-11 File No. 44818.02 Date 7/25/2011

GZA Engineer J. Davis Weather 70s rain	EXCAVATION EQUIPMENT Contractor HTS Construction Operator Bruce Remillard Make Volvo Model EC35 Capacity 0.25 cu.yd. Reach 15 ft.	Ground Elevation 1356'± Time Started 1500 Time Completed 1505	

Depth			SOIL DESCRIPTION	Excav. Effort	Boulder Count Qty. Class.	Remark No.
		0.6'	Dark brown, fine to coarse SAND and SILT, little Organics (Topsoil)			
---	1'	---	Orange-brown, fine to coarse SAND and SILT, little fine to coarse Gravel,	E		
		1.8'	trace Roots (Subsoil)			
---	2'	---	Light brown-gray, fine to coarse SAND, some Silt, little fine to coarse	M	1A	
---	3'	---	Gravel (Glacial Till)	M		
---	4'	---		D	2A	
---	5'	---		D		
---	6'	---		D	1A	
---	7'	---	7'	D		1, 2
---	8'	---	End of Exploration at 7'			
---	9'	---				
---	10'	---				
---	11'	---				
---	12'	---				
---	13'	---				
---	14'	---				

REMARKS:
1. Exploration terminated within glacial till.
2. Groundwater not encountered in test pit.

TEST PIT PLAN



Depth = 7 ft.
Volume = 4 cu.yd.

LEGEND

BOULDER COUNT

Size Range Classification	Letter Designation
6" - 18"	A
18" - 36"	B
36" and Larger	C

PROPORTIONS USED

TRACE (TR)	0-10%
LITTLE (LI)	10-20%
SOME (SO)	20-35%
AND	35-50%

ABBREVIATIONS

F - Fine
M - Medium
C - Coarse
F/M - Fine to Medium
F/C - Fine to Coarse
V - Very
GR - Gray
BN - Brown
YEL - Yellow

EXCAVATION EFFORT

E - Easy
M - Moderate
D - Difficult

GROUNDWATER

Elapsed Time to Reading (hours) NE G.W.L.

TEST PIT FIELD LOG

GZA GeoEnvironmental, Inc. Engineers and Scientists	PROJECT *BNE Wind Turbine Project* *Colebrook, CT*	Test Pit No. CNTP-12 File No. 44818.02 Date 7/25/2011
GZA Engineer J. Davis Weather 70s rain	EXCAVATION EQUIPMENT Contractor HTS Construction Operator Bruce Remillard Make Volvo Model EC35 Capacity 0.25 cu.yd. Reach 15 ft.	Ground Elevation 1331'± Time Started 1505 Time Completed 1510

Depth		SOIL DESCRIPTION	Excav. Effort	Boulder Count Qty. Class.	Remark No.
	0.7'	Dark brown, fine to coarse SAND and SILT, little Organics (Topsoil)			
--- 1' ---		Orange-brown, fine to coarse SAND and SILT, trace fine to coarse Gravel, trace Roots (Subsoil)	E		
--- 2' ---	2'		M	2A	
--- 3' ---		Light brown, fine to coarse SAND, some Silt, little fine to coarse Gravel (Glacial Till)	D	6A	
--- 4' ---			D	1A	
--- 5' ---			D	3A	
--- 6' ---	6'		D	2A, 1B	1, 2
--- 7' ---		End of Exploration at 6'			
--- 8' ---					
--- 9' ---					
--- 10' ---					
--- 11' ---					
--- 12' ---					
--- 13' ---					
--- 14' ---					

REMARKS:
1. Exploration terminated within glacial till.
2. Groundwater not encountered in test pit.

TEST PIT PLAN



Depth = 6 ft.
Volume = 4 cu.yd.

LEGEND

BOULDER COUNT

Size Range Classification	Letter Designation
6" - 18"	A
18" - 36"	B
36" and Larger	C

PROPORTIONS USED

TRACE (TR)	0-10%
LITTLE (LI)	10-20%
SOME (SO)	20-35%
AND	35-50%

ABBREVIATIONS

F - Fine
M - Medium
C - Coarse
F/M - Fine to Medium
F/C - Fine to Coarse
V - Very
GR - Gray
BN - Brown
YEL - Yellow

EXCAVATION EFFORT

E - Easy
M - Moderate
D - Difficult

GROUNDWATER

Elapsed Time to Reading (hours) NE G.W.L.

TEST PIT FIELD LOG

GZA GeoEnvironmental, Inc. Engineers and Scientists	PROJECT *BNE Wind Turbine Project* *Colebrook, CT*	Test Pit No. CNTP-13 File No. 44818.02 Date 7/25/2011
GZA Engineer J. Davis Weather 70s rain	EXCAVATION EQUIPMENT Contractor HTS Construction Operator Bruce Remillard Make Volvo Model EC35 Capacity 0.25 cu.yd. Reach 15 ft.	Ground Elevation 1329'± Time Started 1520 Time Completed 1525

Depth	SOIL DESCRIPTION	Excav. Effort	Boulder Count Qty. Class.	Remark No.
	0.7' Dark brown, fine to coarse SAND and SILT, little Roots (Topsoil)			
--- 1' ---	Orange-brown, fine to coarse SAND and SILT, trace fine Gravel, trace Roots (Subsoil)	E	1A	
--- 2' ---		M	4A	
	2.5'			
--- 3' ---	Light brown, fine to coarse SAND, some Silt, little fine to coarse Gravel (Glacial Till)	D	2A	
--- 4' ---		D	2A	
--- 5' ---		D	5A, 2B	
--- 6' ---	6'	D	2A, 2B, 1C	1, 2
	End of Exploration at 6'			
--- 7' ---				
--- 8' ---				
--- 9' ---				
--- 10' ---				
--- 11' ---				
--- 12' ---				
--- 13' ---				
--- 14' ---				

REMARKS:
1. Exploration terminated within glacial till.
2. Groundwater not encountered in test pit.

TEST PIT PLAN



Depth = 6 ft.
Volume = 4 cu.yd.

LEGEND

BOULDER COUNT

Size Range Classification	Letter Designation
6" - 18"	A
18" - 36"	B
36" and Larger	C

PROPORTIONS USED

TRACE (TR)	0-10%
LITTLE (LI)	10-20%
SOME (SO)	20-35%
AND	35-50%

ABBREVIATIONS

F - Fine
M - Medium
C - Coarse
F/M - Fine to Medium
F/C - Fine to Coarse
V - Very
GR - Gray
BN - Brown
YEL - Yellow

EXCAVATION EFFORT

E - Easy
M - Moderate
D - Difficult

GROUNDWATER

Elapsed Time to Reading (hours) NE G.W.L.

TEST PIT FIELD LOG

GZA GeoEnvironmental, Inc. Engineers and Scientists	PROJECT *BNE Wind Turbine Project* *Colebrook, CT*	Test Pit No. CNTP-14 File No. 44818.02 Date 7/25/2011
GZA Engineer T. Bjartmarz Weather 80s Sunny	EXCAVATION EQUIPMENT Contractor HTS Construction Operator Bruce Remillard Make Volvo Model EC35 Capacity 0.25 cu.yd. Reach 15 ft.	Ground Elevation 1270'± Time Started 1010 Time Completed 1022

Depth	SOIL DESCRIPTION	Excav. Effort	Boulder Count Qty. Class.	Remark No.
--- 1' ---	0.5' Dark brown, fine to coarse SAND and ORGANIC MATTER, little fine to coarse Gravel, little Silt (Topsoil)	D	5A, 2B	1
--- 2' ---	Brown, fine to coarse SAND and fine to coarse GRAVEL, little Roots, little Silt (Subsoil)	D	3A	
--- 3' ---	3'	D		
--- 4' ---	4' Gray, fine to coarse SAND and fine to coarse GRAVEL, some Silt (Glacial Till)	D		2, 3
--- 5' ---	Excavator Refusal at 4'			
--- 6' ---				
--- 7' ---				
--- 8' ---				
--- 9' ---				
--- 10' ---				
--- 11' ---				
--- 12' ---				
--- 13' ---				
--- 14' ---				

REMARKS:
1. Test pit relocated approximately 6 feet south of originally planned location.
2. Excavator refusal on bedrock at 4 feet below grade.
3. Groundwater not encountered in test pit.

TEST PIT PLAN



Depth = 4 ft.
Volume = 3 cu.yd.

LEGEND

BOULDER COUNT

Size Range Classification	Letter Designation
6" - 18"	A
18" - 36"	B
36" and Larger	C

PROPORTIONS USED

TRACE (TR)	0-10%
LITTLE (LI)	10-20%
SOME (SO)	20-35%
AND	35-50%

ABBREVIATIONS

F - Fine
M - Medium
C - Coarse
F/M - Fine to Medium
F/C - Fine to Coarse
V - Very
GR - Gray
BN - Brown
YEL - Yellow

EXCAVATION EFFORT

E - Easy
M - Moderate
D - Difficult

GROUNDWATER

Elapsed Time to Reading (hours) NE G.W.L.

TEST PIT FIELD LOG

GZA GeoEnvironmental, Inc. Engineers and Scientists	PROJECT *BNE Wind Turbine Project* *Colebrook, CT*	Test Pit No. CNTP-15 File No. 44818.02 Date 7/25/2011
GZA Engineer T. Bjartmarz Weather 80s Sunny	EXCAVATION EQUIPMENT Contractor HTS Construction Operator Bruce Remillard Make Volvo Model EC35 Capacity 0.25 cu.yd. Reach 15 ft.	Ground Elevation 1263'± Time Started 1010 Time Completed 1022

Depth			SOIL DESCRIPTION	Excav. Effort	Boulder Count Qty. Class.	Remark No.
---	1'	---	1' Dark brown, fine to coarse SAND and ORGANIC MATTER, little fine to coarse Gravel, little Silt (Topsoil)	D	4A, 2B, 1C	
---	2'	---	Brown, fine to coarse SAND and fine to coarse GRAVEL, some Silt, little Roots (Subsoil) 2.5'	D	3A, 1B, 1C	
---	3'	---	Gray, fine to coarse SAND and fine to coarse GRAVEL, some Silt (Glacial Till)	D	2A, 1B	
---	4'	---		D		
---	5'	---	5'	D		1, 2
---	6'	---	Excavator Refusal at 5'			
---	7'	---				
---	8'	---				
---	9'	---				
---	10'	---				
---	11'	---				
---	12'	---				
---	13'	---				
---	14'	---				

REMARKS:
1. Excavator refusal on bedrock at 5 feet below grade.
2. Groundwater not encountered in test pit.

TEST PIT PLAN



Depth = 5 ft.
Volume = 3 cu.yd.

LEGEND

BOULDER COUNT

Size Range Classification	Letter Designation
6" - 18"	A
18" - 36"	B
36" and Larger	C

PROPORTIONS USED

TRACE (TR)	0-10%
LITTLE (LI)	10-20%
SOME (SO)	20-35%
AND	35-50%

ABBREVIATIONS

F - Fine
M - Medium
C - Coarse
F/M - Fine to Medium
F/C - Fine to Coarse
V - Very
GR - Gray
BN - Brown
YEL - Yellow

EXCAVATION EFFORT

E - Easy
M - Moderate
D - Difficult

GROUNDWATER

Elapsed Time to Reading (hours) NE G.W.L.

TEST PIT FIELD LOG

GZA GeoEnvironmental, Inc. Engineers and Scientists	PROJECT *BNE Wind Turbine Project* *Colebrook, CT*	Test Pit No. CNTP-16 File No. 44818.02 Date 7/25/2011
GZA Engineer T. Bjartmarz Weather 80s Sunny	EXCAVATION EQUIPMENT Contractor HTS Construction Operator Bruce Remillard Make Volvo Model EC35 Capacity 0.25 cu.yd. Reach 15 ft.	Ground Elevation 1262'± Time Started 750 Time Completed 804

Depth	SOIL DESCRIPTION	Excav. Effort	Boulder Count Qty. Class.	Remark No.
--- 1' ---	0.5' Dark brown, fine to coarse SAND and ORGANIC MATTER, little fine to coarse Gravel, little Silt (Topsoil)	M	4A	
--- 2' ---	Brown, fine to coarse SAND and fine to coarse GRAVEL, little Roots, little Silt (Subsoil)	D	4A	
--- 3' ---	2.5' Gray, fine to coarse SAND and fine to coarse GRAVEL, some Silt (Glacial Till)	D	6A, 2B	
--- 4' ---		D	8A	
--- 5' ---	4.5' Excavator Refusal at 4.5'	D		1, 2
--- 6' ---				
--- 7' ---				
--- 8' ---				
--- 9' ---				
--- 10' ---				
--- 11' ---				
--- 12' ---				
--- 13' ---				
--- 14' ---				

REMARKS:
1. Excavator refusal on bedrock at 4.5 feet below grade.
2. Groundwater not encountered in test pit.

TEST PIT PLAN



Depth = 4.5 ft.
Volume = 3 cu.yd.

LEGEND

BOULDER COUNT

Size Range Classification	Letter Designation
6" - 18"	A
18" - 36"	B
36" and Larger	C

PROPORTIONS USED

TRACE (TR)	0-10%
LITTLE (LI)	10-20%
SOME (SO)	20-35%
AND	35-50%

ABBREVIATIONS

F - Fine
M - Medium
C - Coarse
F/M - Fine to Medium
F/C - Fine to Coarse
V - Very
GR - Gray
BN - Brown
YEL - Yellow

EXCAVATION EFFORT

E - Easy
M - Moderate
D - Difficult

GROUNDWATER

Elapsed Time to Reading (hours) NE G.W.L.

TEST PIT FIELD LOG

GZA GeoEnvironmental, Inc. Engineers and Scientists	PROJECT *BNE Wind Turbine Project* *Colebrook, CT*	Test Pit No. CNTP-17 File No. 44818.02 Date 7/25/2011
GZA Engineer T. Bjartmarz Weather 80s Sunny	EXCAVATION EQUIPMENT Contractor HTS Construction Operator Bruce Remillard Make Volvo Model EC35 Capacity 0.25 cu.yd. Reach 15 ft.	Ground Elevation 1241'± Time Started 1033 Time Completed 1044

Depth	SOIL DESCRIPTION	Excav. Effort	Boulder Count Qty. Class.	Remark No.
--- 1' --- 1'	Dark brown, fine to coarse SAND and ORGANIC MATTER, little fine to coarse Gravel, little Silt (Topsoil)	D	4A, 1B	
--- 2' ---	Brown, fine to coarse SAND and fine to coarse GRAVEL, little Roots, little Silt (Subsoil)	M	5A, 1B	
--- 3' --- 3'		D	3A	
--- 4' ---	Gray, fine to coarse SAND and fine to coarse GRAVEL, little Silt (Glacial Till)	D	4A	
--- 5' --- 5'		D	5A	1, 2
--- 6' ---	Excavator Refusal at 5'			
--- 7' ---				
--- 8' ---				
--- 9' ---				
--- 10' ---				
--- 11' ---				
--- 12' ---				
--- 13' ---				
--- 14' ---				

REMARKS:
1. Excavator refusal on bedrock at 5 feet below grade.
2. Groundwater not encountered in test pit.

TEST PIT PLAN



Depth = 5 ft.
Volume = 3 cu.yd.

LEGEND

BOULDER COUNT

Size Range Classification	Letter Designation
6" - 18"	A
18" - 36"	B
36" and Larger	C

PROPORTIONS USED

TRACE (TR)	0-10%
LITTLE (LI)	10-20%
SOME (SO)	20-35%
AND	35-50%

ABBREVIATIONS

F - Fine
M - Medium
C - Coarse
F/M - Fine to Medium
F/C - Fine to Coarse
V - Very
GR - Gray
BN - Brown
YEL - Yellow

EXCAVATION EFFORT

E - Easy
M - Moderate
D - Difficult

GROUNDWATER

Elapsed Time to Reading (hours) NE G.W.L.

TEST PIT FIELD LOG

GZA GeoEnvironmental, Inc. Engineers and Scientists	PROJECT *BNE Wind Turbine Project* *Colebrook, CT*	Test Pit No. CNTP-18 File No. 44818.02 Date 7/25/2011
GZA Engineer J. Davis Weather 70s rain	EXCAVATION EQUIPMENT Contractor HTS Construction Operator Bruce Remillard Make Volvo Model EC35 Capacity 0.25 cu.yd. Reach 1.5 ft.	Ground Elevation 1273'± Time Started 1250 Time Completed 1300

Depth	SOIL DESCRIPTION	Excav. Effort	Boulder Count Qty. Class.	Remark No.
--- 1' --- 0.8'	Dark brown, fine to coarse SAND and SILT, little Organics, little fine to coarse Gravel (Topsoil)	M		
--- 2' --- 2.5'	Brown, fine to coarse SAND, some fine to coarse Gravel, some Silt, trace Roots (Subsoil)	M	2A	
--- 3' --- 4'	Light brown, fine to coarse SAND and fine to coarse GRAVEL, little Silt (Glacial Till)	D	3A	
--- 4' ---		D	5A	
--- 5' ---	Excavator Refusal at 4.5'	D		1, 2
--- 6' ---				
--- 7' ---				
--- 8' ---				
--- 9' ---				
--- 10' ---				
--- 11' ---				
--- 12' ---				
--- 13' ---				
--- 14' ---				

REMARKS:
1. Excavator refusal on bedrock at about 4 to 4.5 feet below grade.
2. Groundwater not encountered in test pit.

TEST PIT PLAN



Depth = 8.5 ft.
Volume = 3 cu.yd.

LEGEND

BOULDER COUNT

Size Range Classification	Letter Designation
6" - 18"	A
18" - 36"	B
36" and Larger	C

PROPORTIONS USED

TRACE (TR)	0-10%
LITTLE (LI)	10-20%
SOME (SO)	20-35%
AND	35-50%

ABBREVIATIONS

F - Fine
M - Medium
C - Coarse
F/M - Fine to Medium
F/C - Fine to Coarse
V - Very
GR - Gray
BN - Brown
YEL - Yellow

EXCAVATION EFFORT

E - Easy
M - Moderate
D - Difficult

GROUNDWATER

Elapsed Time to Reading (hours) — NE — G.W.L.

TEST PIT FIELD LOG

GZA GeoEnvironmental, Inc. Engineers and Scientists	PROJECT *BNE Wind Turbine Project* *Colebrook, CT*	Test Pit No. CNTP-19 File No. 44818.02 Date 7/25/2011

GZA Engineer J. Davis Weather 70s overcast	EXCAVATION EQUIPMENT Contractor HTS Construction Operator Bruce Remillard Make Volvo Model EC35 Capacity 0.25 cu.yd. Reach 15 ft.	Ground Elevation 1250'± Time Started 1033 Time Completed 1044	

Depth	SOIL DESCRIPTION	Excav. Effort	Boulder Count Qty. Class.	Remark No.
--- 1' ---	0.5' Dark brown, fine to coarse SAND and ORGANIC MATTER, little fine to coarse Gravel, little Silt (Topsoil)	M	1A	
--- 2' ---	Brown, fine to coarse SAND and fine to coarse GRAVEL, little Roots, little Silt (Subsoil) 2.5'	D	3A	
--- 3' ---	Gray, fine to coarse SAND and fine to coarse GRAVEL, little Silt (Glacial Till)	D	6A, 1B	
--- 4' ---		D	5A, 2B	1
--- 5' ---		D	6A, 1B	
--- 6' ---	6'	D	4A	2
--- 7' ---	End of Exploration at 6'			
--- 8' ---				
--- 9' ---				
--- 10' ---				
--- 11' ---				
--- 12' ---				
--- 13' ---				
--- 14' ---				

REMARKS:
1. Groundwater observed at approximately 4.9 feet below grade.
2. Exploration terminated in glacial till.

TEST PIT PLAN



Depth = 6 ft.
Volume = 4 cu.yd.

LEGEND

BOULDER COUNT

Size Range Classification	Letter Designation
6" - 18"	A
18" - 36"	B
36" and Larger	C

PROPORTIONS USED

TRACE (TR)	0-10%
LITTLE (LI)	10-20%
SOME (SO)	20-35%
AND	35-50%

ABBREVIATIONS

F - Fine
M - Medium
C - Coarse
F/M - Fine to Medium
F/C - Fine to Coarse
V - Very
GR - Gray
BN - Brown
YEL - Yellow

EXCAVATION EFFORT

E - Easy
M - Moderate
D - Difficult

GROUNDWATER

Elapsed Time to Reading (hours) 4.9 G.W.L.

TEST PIT FIELD LOG

GZA GeoEnvironmental, Inc. Engineers and Scientists	PROJECT *BNE Wind Turbine Project* *Colebrook, CT*	Test Pit No. CNTP-20 File No. 44818.02 Date 7/25/2011

GZA Engineer J. Davis Weather 70s rain	EXCAVATION EQUIPMENT Contractor HTS Construction Operator Bruce Remillard Make Volvo Model EC35 Capacity 0.25 cu.yd. Reach 15 ft.	Ground Elevation 1258'± Time Started 1230 Time Completed 1240	

Depth	SOIL DESCRIPTION	Excav. Effort	Boulder Count Qty. Class.	Remark No.
--- 1' --- 1'	Dark brown, fine to coarse SAND and SILT, little Organics (Topsoil)	M	4A	
--- 2' --- 2.5'	Brown, fine to coarse SAND and fine to coarse GRAVEL, some Silt, trace Roots (Subsoil)	D	2A, 1B	
--- 3' ---	Light brown, fine to coarse SAND and fine to coarse GRAVEL, little Silt (Glacial Till)	D	4A, 1B	
--- 4' ---		D	5A	
--- 5' ---		D	6A	
--- 6' --- 6'		D	4A	1, 2
--- 7' ---	End of Exploration at 6'			
--- 8' ---				
--- 9' ---				
--- 10' ---				
--- 11' ---				
--- 12' ---				
--- 13' ---				
--- 14' ---				

REMARKS:
1. Exploration terminated within glacial till.
2. Groundwater not encountered in test pit.

TEST PIT PLAN



Depth = 6 ft.
Volume = 3 cu.yd.

LEGEND

BOULDER COUNT

Size Range Classification	Letter Designation
6" - 18"	A
18" - 36"	B
36" and Larger	C

PROPORTIONS USED

TRACE (TR)	0-10%
LITTLE (LI)	10-20%
SOME (SO)	20-35%
AND	35-50%

ABBREVIATIONS

F - Fine
M - Medium
C - Coarse
F/M - Fine to Medium
F/C - Fine to Coarse
V - Very
GR - Gray
BN - Brown
YEL - Yellow

EXCAVATION EFFORT

E - Easy
M - Moderate
D - Difficult

GROUNDWATER

Elapsed Time to Reading (hours) NE G.W.L.

TEST PIT FIELD LOG

GZA GeoEnvironmental, Inc. Engineers and Scientists	PROJECT *BNE Wind Turbine Project* *Colebrook, CT*	Test Pit No. CNTP-21 File No. 44818.02 Date 7/25/2011
GZA Engineer J. Davis Weather 70s rain	EXCAVATION EQUIPMENT Contractor HTS Construction Operator Bruce Remillard Make Volvo Model EC35 Capacity 0.25 cu.yd. Reach 15 ft.	Ground Elevation 1246'± Time Started 1215 Time Completed 1230

Depth			SOIL DESCRIPTION	Excav. Effort	Boulder Count Qty. Class.	Remark No.
---	1'	---	1' Dark brown, fine to coarse SAND and SILT, some Organics (Topsoil)	M		
---	2'	---	1.8' Brown, fine to coarse SAND and fine to coarse GRAVEL, little Silt, trace Roots (Subsoil)	D	4A, 4B	
---	3'	---	Light brown, fine to coarse SAND and fine to coarse GRAVEL, little Silt (Glacial Till)	D	4A, 2B, 1C	
---	4'	---		D	6A, 1B	
---	5'	---	5'	D	5A	1, 2
---	6'	---	End of Exploration at 5'			
---	7'	---				
---	8'	---				
---	9'	---				
---	10'	---				
---	11'	---				
---	12'	---				
---	13'	---				
---	14'	---				

REMARKS:
1. Exploration terminated within glacial till.
2. Groundwater not encountered in test pit.

TEST PIT PLAN



Depth = 6 ft.
Volume = 4 cu.yd.

LEGEND

BOUNDER COUNT

Size Range Classification	Letter Designation
6" - 18"	A
18" - 36"	B
36" and Larger	C

PROPORTIONS USED

TRACE (TR)	0-10%
LITTLE (LI)	10-20%
SOME (SO)	20-35%
AND	35-50%

ABBREVIATIONS

F - Fine
M - Medium
C - Coarse
F/M - Fine to Medium
F/C - Fine to Coarse
V - Very
GR - Gray
BN - Brown
YEL - Yellow

EXCAVATION EFFORT

E - Easy
M - Moderate
D - Difficult

GROUNDWATER

Elapsed Time to Reading (hours) NE G.W.L.

TEST PIT FIELD LOG

GZA GeoEnvironmental, Inc. Engineers and Scientists	PROJECT *BNE Wind Turbine Project* *Colebrook, CT*	Test Pit No. CNTP-22 File No. 44818.02 Date 7/25/2011

GZA Engineer	J. Davis	EXCAVATION EQUIPMENT				Ground Elevation	1326'±
Weather	70s rain	Contractor	HTS Construction			Time Started	1525
		Operator	Bruce Remillard			Time Completed	1530
		Make	Volvo	Model	EC35		
		Capacity	0.25 cu.yd.	Reach	15 ft.		

Depth			SOIL DESCRIPTION		Excav. Effort	Boulder Count Qty. Class.	Remark No.
			0.5'	Dark brown, fine to coarse SAND and SILT, little Roots (Topsoil)			
---	1'	---		Orange-brown, fine to coarse SAND and SILT, trace Roots (Subsoil)	E		
---	2'	---	2'		M	1A	
				Light brown, fine to coarse SAND, some Silt, trace fine to coarse Gravel (Glacial Till)			
---	3'	---			D	5A	
---	4'	---			D	2A	
---	5'	---			D	6A	
---	6'	---	6.3'		D	2A, 2B	1, 2
				Excavator Refusal at 6.3'			
---	7'	---					
---	8'	---					
---	9'	---					
---	10'	---					
---	11'	---					
---	12'	---					
---	13'	---					
---	14'	---					

REMARKS:
1. Excavator refusal on bedrock or very large boulder at 6.3 feet below grade.
2. Groundwater not encountered in test pit.

TEST PIT PLAN



Depth = 6.3 ft.
Volume = 4 cu.yd.

LEGEND

BOULDER COUNT

Size Range Classification	Letter Designation
6" - 18"	A
18" - 36"	B
36" and Larger	C

PROPORTIONS USED

TRACE (TR)	0-10%
LITTLE (LI)	10-20%
SOME (SO)	20-35%
AND	35-50%

ABBREVIATIONS

F - Fine
M - Medium
C - Coarse
F/M - Fine to Medium
F/C - Fine to Coarse
V - Very
GR - Gray
BN - Brown
YEL - Yellow

EXCAVATION EFFORT

E - Easy
M - Moderate
D - Difficult

GROUNDWATER

Elapsed Time to Reading (hours) — NE — G.W.L.

TEST PIT FIELD LOG

GZA GeoEnvironmental, Inc. Engineers and Scientists	PROJECT *BNE Wind Turbine Project* *Colebrook, CT*	Test Pit No. CNTP-23 File No. 44818.02 Date 7/25/2011
GZA Engineer J. Davis Weather 70s rain	EXCAVATION EQUIPMENT Contractor HTS Construction Operator Bruce Remillard Make Volvo Model EC35 Capacity 0.25 cu.yd. Reach 15 ft.	Ground Elevation 1333'± Time Started 1535 Time Completed 1540

Depth	SOIL DESCRIPTION	Excav. Effort	Boulder Count Qty. Class.	Remark No.
--- 1' ---	0.5' Dark brown, fine to coarse SAND and SILT, little Roots (Topsoil)			
--- 2' ---	Orange-brown, fine to coarse SAND and SILT, trace fine to coarse Gravel, trace Roots (Subsoil)	E		
--- 3' ---	2.5' Light brown, fine to coarse SAND, some Silt, little fine to coarse Gravel (Glacial Till)	M	2A	
--- 4' ---		M	1A	
--- 5' ---		D	3A	
--- 6' ---	6' End of Exploration at 6'	D	3A, 1C	
--- 7' ---		D	3A, 1B, 1C	1, 2
--- 8' ---				
--- 9' ---				
--- 10' ---				
--- 11' ---				
--- 12' ---				
--- 13' ---				
--- 14' ---				

REMARKS:
1. Exploration terminated within glacial till.
2. Groundwater not encountered in test pit.

TEST PIT PLAN



Depth = 6 ft.
Volume = 4 cu.yd.

LEGEND

BOULDER COUNT

Size Range Classification	Letter Designation
6" - 18"	A
18" - 36"	B
36" and Larger	C

PROPORTIONS USED

TRACE (TR)	0-10%
LITTLE (LI)	10-20%
SOME (SO)	20-35%
AND	35-50%

ABBREVIATIONS

F - Fine
M - Medium
C - Coarse
F/M - Fine to Medium
F/C - Fine to Coarse
V - Very
GR - Gray
BN - Brown
YEL - Yellow

EXCAVATION EFFORT

E - Easy
M - Moderate
D - Difficult

GROUNDWATER

Elapsed Time to Reading (hours) NE G.W.L.

TEST PIT FIELD LOG

GZA GeoEnvironmental, Inc. Engineers and Scientists	PROJECT *BNE Wind Turbine Project* *Colebrook, CT*	Test Pit No. CNTP-24 File No. 44818.02 Date 7/25/2011
GZA Engineer J. Davis Weather 70s rain	EXCAVATION EQUIPMENT Contractor HTS Construction Operator Bruce Remillard Make Volvo Model EC35 Capacity 0.25 cu.yd. Reach 15 ft.	Ground Elevation 1365'± Time Started 1445 Time Completed 1450

Depth			SOIL DESCRIPTION		Excav. Effort	Boulder Count Qty. Class.	Remark No.
			0.5'	Dark brown, fine to coarse SAND and SILT, little Organics (Topsoil)			
---	1'	---	1.5'	Orange-brown, fine to coarse SAND and SILT, trace fine to coarse Gravel, trace Roots (Subsoil)	E		
---	2'	---		Light brown-gray, fine to coarse SAND, some Silt, trace fine to coarse Gravel (Glacial Till)	M	3A	
---	3'	---			D	1A	
---	4'	---			D		
---	5'	---			D	2A	
---	6'	---	6'		D		1, 2
---	7'	---		End of Exploration at 6'			
---	8'	---					
---	9'	---					
---	10'	---					
---	11'	---					
---	12'	---					
---	13'	---					
---	14'	---					

REMARKS:
1. Exploration terminated within glacial till.
2. Groundwater not encountered in test pit.

TEST PIT PLAN



Depth = 6 ft.
Volume = 4 cu.yd.

LEGEND

BOULDER COUNT

Size Range Classification	Letter Designation
6" - 18"	A
18" - 36"	B
36" and Larger	C

PROPORTIONS USED

TRACE (TR)	0-10%
LITTLE (LI)	10-20%
SOME (SO)	20-35%
AND	35-50%

ABBREVIATIONS

F - Fine
M - Medium
C - Coarse
F/M - Fine to Medium
F/C - Fine to Coarse
V - Very
GR - Gray
BN - Brown
YEL - Yellow

EXCAVATION EFFORT

E - Easy
M - Moderate
D - Difficult

GROUNDWATER

Elapsed Time to Reading (hours) NE G.W.L.

TEST PIT FIELD LOG

GZA GeoEnvironmental, Inc. Engineers and Scientists	PROJECT *BNE Wind Turbine Project* *Colebrook, CT*	Test Pit No. CNTP-25 File No. 44818.02 Date 7/25/2011
GZA Engineer J. Davis Weather 70s rain	EXCAVATION EQUIPMENT Contractor HTS Construction Operator Bruce Remillard Make Volvo Model EC35 Capacity 0.25 cu.yd. Reach 15 ft.	Ground Elevation 1379'± Time Started 1510 Time Completed 1520

Depth	SOIL DESCRIPTION	Excav. Effort	Boulder Count Qty. Class.	Remark No.
	0.5' Dark brown, fine to coarse SAND and SILT, little Organics (Topsoil)			
--- 1' ---	Brown, fine to coarse SAND, some Silt, trace fine to coarse Gravel, trace Roots (Subsoil)	E		
--- 2' ---		M	3A, 1B	
	2.5'			
--- 3' ---	Light brown, fine to coarse SAND, some Silt, little fine to coarse Gravel (Glacial Till) 3.5'	D	4A, 1B, 1C	
--- 4' ---	4'	D	3A, 1B, 1C	1, 2
--- 5' ---	Excavator Refusal at 4'			
--- 6' ---				
--- 7' ---				
--- 8' ---				
--- 9' ---				
--- 10' ---				
--- 11' ---				
--- 12' ---				
--- 13' ---				
--- 14' ---				

REMARKS:
1. Excavator refusal on bedrock at about 3.5 to 4 feet below grade.
2. Groundwater not encountered in test pit.

TEST PIT PLAN



Depth = 6 ft.
Volume = 3 cu.yd.

LEGEND

BOULDER COUNT

Size Range Classification	Letter Designation
6" - 18"	A
18" - 36"	B
36" and Larger	C

PROPORTIONS USED

TRACE (TR)	0-10%
LITTLE (LI)	10-20%
SOME (SO)	20-35%
AND	35-50%

ABBREVIATIONS

F - Fine
M - Medium
C - Coarse
F/M - Fine to Medium
F/C - Fine to Coarse
V - Very
GR - Gray
BN - Brown
YEL - Yellow

EXCAVATION EFFORT

E - Easy
M - Moderate
D - Difficult

GROUNDWATER

Elapsed Time to Reading (hours) NE G.W.L.

TEST PIT FIELD LOG

GZA GeoEnvironmental, Inc. Engineers and Scientists	PROJECT *BNE Wind Turbine Project* *Colebrook, CT*	Test Pit No. CNTP-26 File No. 44818.02 Date 7/25/2011
GZA Engineer T. Bjartmarz Weather 70s overcast	EXCAVATION EQUIPMENT Contractor HTS Construction Operator Bruce Remillard Make Volvo Model EC35 Capacity 0.25 cu.yd. Reach 15 ft.	Ground Elevation 1260'± Time Started 911 Time Completed 920

Depth	SOIL DESCRIPTION	Excav. Effort	Boulder Count Qty. Class.	Remark No.
--- 1' --- 1'	Dark brown, fine to coarse SAND and ORGANIC MATTER, little fine to coarse Gravel, little Silt (Topsoil)	D	3A, 2B	
--- 2' ---	Brown, fine to coarse SAND and fine to coarse GRAVEL, little Roots, little Silt (Subsoil)	D	5A, 1B	
--- 3' --- 3'		D	3A	1
--- 4' ---	Gray, fine to coarse SAND and fine to coarse GRAVEL, little Silt (Glacial Till)	D	3A	
--- 5' --- 5'		D	3A	2
--- 6' ---	Excavator Refusal at 5'			
--- 7' ---				
--- 8' ---				
--- 9' ---				
--- 10' ---				
--- 11' ---				
--- 12' ---				
--- 13' ---				
--- 14' ---				

REMARKS:
1. Mottled soil observed at approximately 3 feet below grade. Groundwater not encountered.
2. Excavator refusal on bedrock at 5 feet below grade.

TEST PIT PLAN



Depth = 5 ft.
Volume = 3 cu.yd.

LEGEND

BOULDER COUNT

Size Range Classification	Letter Designation
6" - 18"	A
18" - 36"	B
36" and Larger	C

PROPORTIONS USED

TRACE (TR)	0-10%
LITTLE (LI)	10-20%
SOME (SO)	20-35%
AND	35-50%

ABBREVIATIONS

F - Fine
M - Medium
C - Coarse
F/M - Fine to Medium
F/C - Fine to Coarse
V - Very
GR - Gray
BN - Brown
YEL - Yellow

EXCAVATION EFFORT

E - Easy
M - Moderate
D - Difficult

GROUNDWATER

Elapsed Time to Reading (hours) NE G.W.L.

TEST PIT FIELD LOG

GZA GeoEnvironmental, Inc. Engineers and Scientists	PROJECT *BNE Wind Turbine Project* *Colebrook, CT*	Test Pit No. CNTP-27 File No. 44818.02 Date 7/25/2011
GZA Engineer J. Davis Weather 70s rain	EXCAVATION EQUIPMENT Contractor HTS Construction Operator Bruce Remillard Make Volvo Model EC35 Capacity 0.25 cu.yd. Reach 15 ft.	Ground Elevation 1315'± Time Started 1535 Time Completed 1545

Depth	SOIL DESCRIPTION	Excav. Effort	Boulder Count Qty. Class.	Remark No.
--- 1' --- 1'	Dark brown, fine to coarse SAND and SILT, little Roots (Topsoil)	E		
--- 2' ---	Orange-brown, fine to coarse SAND and SILT, trace fine to coarse Gravel, trace Roots (Subsoil)	E	1A	
--- 3' --- 3'		E		
--- 4' ---	Light brown, fine to coarse SAND, some Silt, little fine to coarse Gravel (Glacial Till)	M	2A	
--- 5' ---		D	2A	
--- 6' ---		D		
--- 7' ---		D		
--- 8' --- 8.5'		D	1B, 2C	
--- 9' ---	Excavator Refusal at 8.5'	D		1, 2
--- 10' ---				
--- 11' ---				
--- 12' ---				
--- 13' ---				
--- 14' ---				

REMARKS:
1. Excavator refusal on bedrock at 8.5 feet below grade.
2. Groundwater not encountered in test pit.

TEST PIT PLAN



Depth = 8.5 ft.
Volume = 4 cu.yd.

LEGEND

BOULDER COUNT

Size Range Classification	Letter Designation
6" - 18"	A
18" - 36"	B
36" and Larger	C

PROPORTIONS USED

TRACE (TR)	0-10%
LITTLE (LI)	10-20%
SOME (SO)	20-35%
AND	35-50%

ABBREVIATIONS

F - Fine
M - Medium
C - Coarse
F/M - Fine to Medium
F/C - Fine to Coarse
V - Very
GR - Gray
BN - Brown
YEL - Yellow

EXCAVATION EFFORT

E - Easy
M - Moderate
D - Difficult

GROUNDWATER

Elapsed Time to Reading (hours) NE G.W.L.

TEST PIT FIELD LOG

GZA GeoEnvironmental, Inc. Engineers and Scientists	PROJECT *BNE Wind Turbine Project* *Colebrook, CT*	Test Pit No. CNTP-28 File No. 44818.02 Date 7/25/2011

GZA Engineer: J. Davis
Weather: 70s rain

EXCAVATION EQUIPMENT
Contractor: HTS Construction
Operator: Bruce Remillard
Make: Volvo Model: EC35
Capacity: 0.25 cu.yd. Reach: 15 ft.

Ground Elevation: 1351'±
Time Started: 1430
Time Completed: 1445

Depth	SOIL DESCRIPTION	Excav. Effort	Boulder Count Qty. Class.	Remark No.
0.5'	Dark brown, fine to coarse SAND and SILT, little Organics (Topsoil)			
1'	Brown, fine to coarse SAND, some Silt, trace fine to coarse Gravel, trace Roots (Subsoil)	E	1A	
1.5'	Light brown, fine to coarse SAND, some Silt, little fine to coarse Gravel (Glacial Till)	M	1A, 1B	
2'		D	2A	
3'		D	1B	
4'		D		
5'		D	3A	1, 2
6'	Excavator Refusal at 6'			
7'				
8'				
9'				
10'				
11'				
12'				
13'				
14'				

REMARKS:
1. Excavator refusal on bedrock at 6 feet below grade.
2. Groundwater not encountered in test pit.

TEST PIT PLAN



Depth = 6 ft.
Volume = 4 cu.yd.

LEGEND

BOULDER COUNT

Size Range Classification	Letter Designation
6" - 18"	A
18" - 36"	B
36" and Larger	C

PROPORTIONS USED

TRACE (TR)	0-10%
LITTLE (LI)	10-20%
SOME (SO)	20-35%
AND	35-50%

ABBREVIATIONS
F - Fine
M - Medium
C - Coarse
F/M - Fine to Medium
F/C - Fine to Coarse
V - Very
GR - Gray
BN - Brown
YEL - Yellow

EXCAVATION EFFORT
E - Easy
M - Moderate
D - Difficult

GROUNDWATER
Elapsed Time to Reading (hours)
NE
G.W.L.

TEST PIT FIELD LOG

GZA GeoEnvironmental, Inc. Engineers and Scientists	PROJECT *BNE Wind Turbine Project* *Colebrook, CT*	Test Pit No. CNTP-29 File No. 44818.02 Date 7/25/2011
GZA Engineer J. Davis Weather 70s rain	EXCAVATION EQUIPMENT Contractor Operator Bruce Remillard Make Volvo Model EC35 Capacity 0.25 cu.yd. Reach 15 ft.	Ground Elevation 1375'± Time Started 1450 Time Completed 1452

Depth	SOIL DESCRIPTION	Excav. Effort	Boulder Count Qty. Class.	Remark No.
	0.5' Dark brown, fine to coarse SAND and SILT, little Organics (Topsoil)			
--- 1' ---	Orange-brown, fine to coarse SAND, some Silt, trace fine Gravel, trace Roots (Subsoil)	E	1A	
--- 2' --- 2'		M	1A	
--- 3' ---	Light brown-gray, fine to coarse SAND, some Silt, trace fine to coarse Gravel (Glacial Till)	D	1A	
--- 4' ---		D	1A	
--- 5' ---		D	2A	1, 2
--- 6' --- 6'		D		
--- 7' ---	End of Exploration at 6'			
--- 8' ---				
--- 9' ---				
--- 10' ---				
--- 11' ---				
--- 12' ---				
--- 13' ---				
--- 14' ---				

REMARKS:
1. Exploration terminated within glacial till.
2. Groundwater not encountered in test pit.

TEST PIT PLAN



Depth = 6 ft.
Volume = 4 cu.yd.

LEGEND

BOULDER COUNT

Size Range Classification	Letter Designation
6" - 18"	A
18" - 36"	B
36" and Larger	C

PROPORTIONS USED

TRACE (TR)	0-10%
LITTLE (LI)	10-20%
SOME (SO)	20-35%
AND	35-50%

ABBREVIATIONS

F - Fine
M - Medium
C - Coarse
F/M - Fine to Medium
F/C - Fine to Coarse
V - Very
GR - Gray
BN - Brown
YEL - Yellow

EXCAVATION EFFORT

E - Easy
M - Moderate
D - Difficult

GROUNDWATER

Elapsed Time to Reading (hours) — NE — G.W.L.