

October 10, 2023

Melanie A. Bachman
Executive Director/Staff Attorney
Connecticut Siting Council
10 Franklin Square
New Britain, CT 06051

Re: **Notice of Exempt Modification – Facility Modifications
Cellco Partnership d/b/a Verizon Wireless**

P2P Project – 811 Blue Hills Avenue, Bloomfield, Connecticut

Dear Attorney Bachman:

Cellco Partnership d/b/a Verizon Wireless (“Cellco”) currently holds a license, issued by the Federal Communications Commission (“FCC”), to provide wireless communications services in the 28 GHz frequency range. To meet its FCC license requirements for frequency use and deployment, Cellco plans to deploy a new, “Point to Point” (“P2P”) 28 GHz microwave system at numerous cell sites in Connecticut. Initially, these frequencies will help Cellco maintain certain security systems currently used to monitor cell site equipment. This notice pertains to the P2P system that will be deployed at Cellco’s existing cell site at 811 Blue Hills Avenue in Bloomfield, Connecticut (the “Blue Hills Cell Site”).

To establish the referenced P2P system, Cellco will install two (2) point to point microwave dish antennas on the roof of the existing equipment shelter at the Blue Hills Cell Site. Unlike the broadcast antennas on the tower, the P2P dish antennas will communicate only with each other. Shelter-mounted dish antennas will be installed at opposite ends of the shelter roof, approximately 20 feet apart, at a height of approximately twelve (12) feet above grade. The antennas would be attached to a non-penetrating ballast-mounted antenna mast. A copy of the Proposed Shelter View, antenna mount illustration and dish antenna specifications are included in [Attachment 1](#).

Please accept this letter as notification pursuant to R.C.S.A. § 16-50j-73, for construction that constitutes an exempt modification pursuant to R.C.S.A. § 16-50j-72(b)(2). In accordance with R.C.S.A. § 16-50j-73, a copy of this letter is being sent to the Town Manager and Land Use Officer in the Town of Bloomfield. A copy of this filing will also be sent to the property owner of the Blue Hills Cell Site facility location.

28006109-v1

Melanie A. Bachman, Esq.
October 10, 2023
Page 2

The planned modifications to the listed facilities fall squarely within those activities explicitly provided for in R.C.S.A. § 16-50j-72(b)(2).

1. The proposed modifications will not result in an increase in the height of the existing tower. The proposed 28 GHz antennas will be installed on roof of the existing equipment shelter, approximately 12 feet above grade.
2. The proposed modifications will not require the extension of the site boundary.
3. The proposed modifications will not increase noise levels at the facility by six decibels or more, or to levels that exceed state and local criteria.
4. The installation of the 28 GHz antennas will not increase radio frequency (“RF”) emissions at the facility to a level at or above the Federal Communications Commission (FCC) safety standard. Included in Attachment 2 is a Calculated Radio Frequency Emissions Report verifying that RF emissions from the Blue Hills Cell Site with the P2P system installed will comply with the FCC Standards.
5. The proposed modifications will not cause a change or alteration in the physical or environmental characteristics of the site.
6. According to the attached August 14, 2023, letter from Dewberry Engineers Incorporated, Cellco’s existing equipment shelter roof and the proposed ballast sled antenna mounting system can support the proposed 28 GHz antenna installations. A copy of the Dewberry letter is included in Attachment 3.

A Certificate of Mailing verifying that this filing was sent to the municipal officials and the property owner is included in Attachment 4.

For the foregoing reasons, Cellco respectfully submits that the proposed modifications to the above-referenced telecommunications facility constitutes an exempt modification under R.C.S.A. § 16-50j-72(b)(2).

Sincerely,



Kenneth C. Baldwin

Enclosures

Copy to:

Philip Schenk, Acting Town Manager
Justin LaFountain, Director of Building and Land Use
SAMO Realty LLC, Property Owner
Aleksy Tyurin, Verizon Wireless

ATTACHMENT 1

Proposed shelter view



- Rohn Non-Penetrating Roof mount (not quoted HW/Logistics per RFP)
- 30-inch mast
- Quick assembly
- 8 blocks @ 32lbs = 256 lbs of ballast (TBD)
- Cable management will consist of
 - Zip ties
 - Angle adaptors with snap-ins
 - PVC pipe runs across roof top
 - Possible Fiberbond chase (still being reviewed)



- Hatch plate to be used
- Existing grounding points
- No new penetrations
 - Roof or walls
- Indoor
 - Existing rack power
 - 2 x 10amp
 - Existing cable trays



Technical Specifications

WTM 4100

ANSI with A2C+ Operation

General Specifications

General

| | | |
|------------------------------------|---|--|
| Frequency Bands | 5 - 38 GHz | |
| Physical Configurations | 1+0, 2+0 ACCP (via A2C+), 2+0 XPIC (via external OMT) | |
| Modulation and Coding | <i>Fixed or Adaptive</i> | QPSK to 4096 QAM / Hitless AM |
| Channel Sizes | 3.75, 5, 10, 20, 25, 30, 40, 50, 60, 80 and 100 MHz | |
| Capacity (standard single channel) | <i>Airlink Capacity</i> | up to 918 Mbit/s* |
| Capacity (A2C mode) | <i>Airlink Capacity</i> | up to 1836 Mbit/s* |
| Encryption | 256-bit AES Payload Encryption | |
| Design Tools | <i>Recommended</i> <i>Supported</i> | Aviat Design™ on aviatcloud.com (includes MIMO, Multi-band) Pathloss 5 (basic support only) |

Power Supply

| | | |
|-------------|--------------------------------------|---------------------|
| Voltage | <i>DC</i> | ±20 to 57V |
| | <i>PoE</i> | 48Vdc (44 to 58Vdc) |
| Consumption | 50 Watts nominal 65 Watts maximum | |

Physical

| | | |
|--|--|--|
| Size (h-w-d), including antenna interfaces | 11.5in x 10.5in x 4in (295mm x 270mm x 95mm) | |
| Weight, including antenna interfaces | 12lbs (5.5 kg) | |
| Operating Temperature | <i>Guaranteed</i> | -27 to +131°F (-33° to +55°C) |
| | <i>Extended</i> | -49 to +159°F (-45° to +65°C) ^[1] |
| Humidity | <i>Guaranteed</i> | 100% |
| Altitude | <i>Guaranteed</i> | 15,000 ft (4500m) |

Standards Compliance

| | | |
|------------------------------|---|---|
| EMC | FCC CFR 47, Part 15, ICES-003 | |
| Operation | EN 300 019-2-4, Class 4.1 | |
| Safety | UL 60950-1, UL 60950-22, UL 62368-1 | |
| RF Performance | <i>All Federal Frequencies</i> | FCC CFR 47, Part 101 Manual of Regulations for Federal Radio Frequency Management |
| Maximum Permissible Exposure | EN 50385 | |
| Water Ingress | IEC 60529, IP66 | |
| Lightning Protection | Internal, compliant to IEC 61000-4-5, Class 5 | |
| Security | FIPS 197 validated (Certificate A980) | |

Transmitter / Receiver

Transmitter

| | | |
|---|---|-----------------------|
| Transmit Power Tolerance | <i>5-28 GHz</i> | ± 2.0 dB |
| | <i>38 GHz</i> | ± 2.5 dB |
| Transmitter Source | Synthesized | |
| Frequency Stability | ± 5 ppm | |
| Manual Transmitter Power Control Range | Configurable in 0.1 dB steps from min to max power levels | |
| Automatic Transmitter Power Control Range | Configurable over the 20dB attenuation range | |
| | <i>Resolution / Speed</i> | 0.1 dB steps / 50dB/s |
| Synthesizer Resolution | 250 KHz | |
| Transmitter Mute | > 50 dB | |

*[1] See notes in last page

Transmitter / Receiver

Receiver

| | | |
|--------------------------------------|---|---------------------|
| Receiver Source | | Synthesized |
| Frequency Stability | | ± 5 ppm |
| Receiver Overload | <i>BER = 1E-6</i> | -20 dBm |
| Residual (Background) Bit Error Rate | | Better than 1E-13 |
| RSSI Accuracy [4] | -30 to -70 dBm, -27 to +131°F (-33° to +55°C) | Better than ± 2.5dB |
| | -20 to -30 dBm, -27 to +131°F (-33° to +55°C) | Better than ± 3.5dB |
| | -20 to -30 dBm, -49 to +149°F (-45° to +65°C) | Better than ± 4.5dB |

Networking

CE/L2

| | | |
|--------------------------|--|---|
| Switch capability | | 50 Gbps non-blocking |
| Quality of Service (QoS) | | 8 COS, Scheduling, Policing, Storm Control, Shaping |
| QoS Mapping | | PCP (802.1p), DSCP, H-QoS |
| VLANs | | IEEE 802.1Q and IEEE 802.1ad (Q-in-Q) |
| Spanning Tree | | Rapid and multiple protocols (RSTP, MSTP) |
| Ethernet OAM | | IEEE 802.3ah, IEEE 802.1ag, ITU-T Y.1731 |
| Congestion Avoidance | | WRED, per queue |
| | | Packet Buffer – 180 Mbyte |
| Jumbo frames | | Up to 9600 bytes |

Synchronisation

| | | |
|-------------------------|--|----------------------|
| Precision Time Protocol | | IEEE 1588v2 TC or BC |
|-------------------------|--|----------------------|

General Specifications

Interfaces

| | | |
|---------------------|---------------------|--|
| Traffic | 2x fixed RJ45 | 10/100/1000BT Electrical |
| | 2x optional SFP | 1, 2.5 & 10Gbps speeds, both Optical (Single and Multi-mode) and Electrical |
| Power | Direct | 24Vdc or 48Vdc |
| | Power over Ethernet | Via 10/100/1000BT Electrical port |
| USB support | Management | Local setup, sw/fw upgrade, config backup |
| Wireless connection | | via Wifi |
| RSSI | | Dual voltmeter pins |

Management

| | | |
|--------------------|--|---|
| Local Management | | Configuration save & load |
| | | Wireless USB dongle to support Wifi |
| | | Aviat OS software upgrade |
| Event Capture | | Event and Alarm capture, time stamp and logging |
| Statistics | | RMON 1 Ethernet and radio performance statistics |
| Network Management | | SNMPv2c ProVision or MIB interface support |
| | | IPv4 addressing with an In-Band Management VLAN. Telnet or SSH access |
| | | Aviat Cloud – Manage Advanced |
| Clock | | Simple Network Time Protocol (SNTP V4), embedded real time clock |

[1] See notes in last page




Microwave Antenna Specifications

SLA0328S3S49A20 0.3m Ultra High Performance Antenna Flange Type Rectangular



| Electrical Specifications | | | | | |
|---|--------------------------------|-----|-----|-----|-----|
| Frequency (GHz) | 27.5~29.5 | | | | |
| Polarization | Single(V or H) | | | | |
| Gain , Low(dBi) | 37.7 | | | | |
| Gain, Mid(dBi) | 38 | | | | |
| Gain, Top(dBi) | 38.3 | | | | |
| Beam Width | 2.0° | | | | |
| Cross-pol. Discrimination_XPD (dB) | 30 | | | | |
| F/B Ratio (dB) | 64 | | | | |
| VSWR / RL (dB) | 1.3/17.7 | | | | |
| Regulatory Compliance | ETSI EN 302217 Range 4 Class 3 | | | | |
| Mechanical Specifications | | | | | |
| Diameter (m) | 0.3 | | | | |
| Antenna Color | Cool Gray 1C | | | | |
| Radome Options | Foam | | | | |
| Interface Type | UBR320 OR Customized | | | | |
| Side Struts, Included | 0 | | | | |
| Azimuth Adjustment | Coarse : 360 ° Fine : ±15 ° | | | | |
| Elevation Adjustment | Fine : ±15 ° | | | | |
| Diameter of Mounting Pole (mm) | Φ51~Φ114 | | | | |
| Wind Velocity Survival Rating (km/h) | 252 | | | | |
| Wind Velocity Operational (km/h) | 200 | | | | |
| Ice-load (mm) | 25.4 | | | | |
| Operational Temperature (°C) | -45~+60 | | | | |
| Packaging | Carton | | | | |
| LxWxH (mm) | 480*480*267 | | | | |
| Wind Load Specifications | | | | | |
| Axial Force (N) @ survival wind speed | 444 | | | | |
| Side Force (N) @ survival wind speed | 219 | | | | |
| Twisting Moment (N•m) @ survival wind speed | 141 | | | | |
| | Dimensions (mm) | ΦA | B | C | D |
| | | 386 | 318 | 137 | 180 |
| Note: 1. The values of B and C are measured at the pole diameter of 114mm 2. The thickness of the radome is not included in the dimensions of A and C | | | | | |

02YSCH 4X2X0.62/1.5-100 PIMF BK Cat 6A



Design:

Wire

Bare copper wire (22AWG)
Insulation of foamed Polyethylene (PE) with skin

Ø 0.62 mm (0,024 in dia)
Ø 1.50 mm (0,059 in dia)

Screened pair

2 wires twisted to a pair
Alulaminare foil overlapped, applied longitudinally

Core:

4 screened pairs
Sequence of colors: WH/BL, WH/OR, WH/GN, WH/BR
Shield braiding of tinned copper wires
Coverage about 80%

Jacket:

Thermoplastic copolymer (FRNC)BK
Wall thickness about 0.80 mm

Ø (8.8 ± 0.3) mm (0.346 ± 0.012 in dia)

Inkjet -marking: "sequential length in metres" LEONI L * S/FTP CAT 6A SOLID CABLE 22AWG 4PR
"internal lot number"

Electrical data at 20° C

| | | | |
|----------------------------------|---|----------|----------|
| Coductor resistance | ≤ | 65 | Ohm/km |
| Insulation resistance | ≥ | 5 | GOhm*km |
| Capacitance (1kHz) | ≤ | 46 | pF/m |
| Phase delay | | 460 | ns/100 m |
| Skew at 100 MHz | | 10 | ns/100 m |
| Characteristic impedance 100 MHz | | 100 ± 10 | Ohm |
| Operating voltage (peak) | | 125 | V |
| Test voltage | | 1000 | V |

VERTRAULICH: Dieses Dokument und dessen Inhalt sind vertraulich zu behandeln und sind Eigentum der LEONI Cable (China) Co., Ltd.
CONFIDENTIAL: This document and its content must be treated strictly confidentially and are property of LEONI Cable (China) Co., Ltd.
Formular: WI-WWW-PT-TDBL2-A-20 © DV-Werk1 2000

ATTACHMENT 2



C Squared Systems, LLC
65 Dartmouth Drive
Auburn, NH 03032
(603) 644-2800

support@csquaredsystems.com

Calculated Radio Frequency Emissions Report



Bloomfield Blue Hills CT

811 Blue Hills Ave, Bloomfield, CT 06002

October 6, 2023

Table of Contents

1. Introduction..... 1

2. FCC Guidelines for Evaluating RF Radiation Exposure Limits 1

3. RF Exposure Prediction Methods 2

4. Antenna Inventory 3

5. Calculation Results..... 4

6. Conclusion..... 6

7. Statement of Certification..... 6

Attachment A: References 7

Attachment B: FCC Limits for Maximum Permissible Exposure (MPE) 8

Attachment C: Verizon Antenna Model Data Sheets and Electrical Patterns..... 10

Attachment D: Far Field Calculation Sheet..... 12

List of Figures

Figure 1: Graph of General Population % MPE vs. Distance..... 4

Figure 2: Graph of FCC Limits for Maximum Permissible Exposure (MPE)..... 9

List of Tables

Table 1: Proposed Antenna Inventory 3

Table 2: Maximum Percent of General Population Exposure Values 5

Table 3: FCC Limits for Maximum Permissible Exposure 8

1. Introduction

The purpose of this report is to investigate compliance with applicable FCC regulations for the proposed installation of Verizon's 28 GHz microwave antenna to be mounted at 12' AGL on roof of the equipment shelter located at 811 Blue Hills Ave in Bloomfield, CT. The coordinates of the monopole tower are 41° 48' 34.86" N, 72° 41' 47.75" W.

Verizon is proposing the following:

- 1) Install one (1) 28 GHz point-to-point microwave system.

This report considers the planned¹ antenna configuration for Verizon as well as existing antenna configuration for Dish² and Verizon³ to derive the resulting % MPE of its proposed installation.

2. FCC Guidelines for Evaluating RF Radiation Exposure Limits

In 1985, the FCC established rules to regulate radio frequency (RF) exposure from FCC licensed antenna facilities. In 1996, the FCC updated these rules, which were further amended in August 1997 by OET Bulletin 65 Edition 97-01. These new rules include Maximum Permissible Exposure (MPE) limits for transmitters operating between 300 kHz and 100 GHz. The FCC MPE limits are based upon those recommended by the National Council on Radiation Protection and Measurements (NCRP), developed by the Institute of Electrical and Electronics Engineers, Inc., (IEEE) and adopted by the American National Standards Institute (ANSI).

The FCC general population/uncontrolled limits set the maximum exposure to which most people may be subjected. General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Public exposure to radio frequencies is regulated and enforced in units of milliwatts per square centimeter (mW/cm²). The general population exposure limits for the various frequency ranges are defined in the attached "FCC Limits for Maximum Permissible Exposure (MPE)" in Attachment C of this report.

Higher exposure limits are permitted under the occupational/controlled exposure category, but only for persons who are exposed as a consequence of their employment and who have been made fully aware of the potential for exposure, and they must be able to exercise control over their exposure. General population/uncontrolled limits are five times more stringent than the levels that are acceptable for occupational, or radio frequency trained individuals. Attachment C contains excerpts from OET Bulletin 65 and defines the Maximum Exposure Limit.

Finally, it should be noted that the MPE limits adopted by the FCC for both general population/uncontrolled exposure and for occupational/controlled exposure incorporate a substantial margin of safety and have been established to be well below levels generally accepted as having the potential to cause adverse health effects.

¹ As referenced to Verizon's Far Field Calculation sheet updated 06/07/2023 included in Attachment D.

² As referenced to Verizon's Connecticut Siting Council Notice of Exempt Modification – 811 Blue Hills Ave, Bloomfield, Connecticut, dated 10/03/2021

³ As referenced to Verizon's Radio Frequency Design Sheet (RFDS) updated 8/3/2022

3. RF Exposure Prediction Methods

The emission field calculation results displayed in the following figures were generated using the following formula as outlined in FCC bulletin OET 65:

$$\text{Power Density} = \left(\frac{\text{GRF}^2 \times 1.64 \times \text{ERP}}{4\pi \times R^2} \right) \times \text{Off Beam Loss}$$

Where:

EIRP = Effective Isotropic Radiated Power

R = Radial Distance = $\sqrt{H^2 + V^2}$

H = Horizontal Distance from antenna in meters

V = Vertical Distance from radiation center of antenna in meters

Off Beam Loss is determined by the selected antenna patterns

Ground reflection factor (GRF) of 1.6

These calculations assume that the antennas are operating at 100 percent capacity, that all antenna channels are transmitting simultaneously, and that the radio transmitters are operating at full power. Obstructions (trees, buildings, etc.) that would normally attenuate the signal are not taken into account. The calculations assume even terrain in the area of study and do not take into account actual terrain elevations which could attenuate the signal. As a result, the predicted signal levels reported below are much higher than the actual signal levels will be from the final installations.

4. Antenna Inventory

Table 1 below outlines Verizon’s existing antenna configuration for the site. The associated data sheets and antenna patterns for these specific antenna models are included in Attachment C.

| Operator | | TX Freq (MHz) | Power at Antenna (Watts) | Ant Gain (dBi) | Power EIRP (Watts) | Antenna Model | Beam Width | Mech. Tilt | Length (ft) | Antenna Centerline Height (ft) |
|----------|-------|---------------|--------------------------|----------------|--------------------|-----------------|-----------------|------------|-------------|--------------------------------|
| Verizon | Alpha | 700 | 160 | 14.9 | 4944 | NHH-65B-R2B | 65 | 0 | 5.99 | 102 |
| | | 850 | 160 | 15.0 | 5060 | | 60 | | | |
| | | 1900 | 160 | 17.9 | 9866 | | 69 | | | |
| | | 2100 | 240 | 18.0 | 15143 | NHHSS-65B-R2BT4 | 64 | 0 | 5.99 | 102 |
| | | 3500 | 20 | 17.7 | 1178 | | 54 | | | |
| | | 3700 | 200 | 25.5 | 70963 | MT6407-77A | - | 0 | 2.92 | 102 |
| | Beta | 700 | 160 | 14.9 | 4944 | NHH-65B-R2B | 65 | 0 | 5.99 | 102 |
| | | 850 | 160 | 15.0 | 5060 | | 60 | | | |
| | | 1900 | 160 | 17.9 | 9866 | | 69 | | | |
| | | 2100 | 240 | 18.0 | 15143 | NHHSS-65B-R2BT4 | 64 | 0 | 5.99 | 102 |
| | | 3500 | 20 | 17.7 | 1178 | | 54 | | | |
| | | 3700 | 200 | 25.5 | 70963 | MT6407-77A | - | 0 | 2.92 | 102 |
| | Gamma | 700 | 160 | 14.9 | 4944 | NHH-65B-R2B | 65 | 0 | 5.99 | 102 |
| | | 850 | 160 | 15.0 | 5060 | | 60 | | | |
| | | 1900 | 160 | 17.9 | 9866 | | 69 | | | |
| | | 2100 | 240 | 18.0 | 15143 | NHHSS-65B-R2BT4 | 64 | 0 | 5.99 | 102 |
| | | 3500 | 20 | 17.7 | 1178 | | 54 | | | |
| | | 3700 | 200 | 25.5 | 70963 | MT6407-77A | - | 0 | 2.92 | 102 |
| | P2P | | 28000 | 0.2 | 38 | 1287 | SLA0328S3S49A20 | 2 | 0 | 1 |

Table 1: Proposed Antenna Inventory

5. Calculation Results

The calculated power density results are shown in Figure 1 below. For completeness, the calculations for this analysis range from 0 feet horizontal distance (directly below the antennas) to a value of 3,000 feet horizontal distance from the site. In addition to the other worst-case scenario considerations that were previously mentioned, the power density calculations to each horizontal distance point away from the antennas was completed using a local maximum off beam antenna gain (within ± 5 degrees of the true mathematical angle) to incorporate a realistic worst-case scenario.




Figure 1: Graph of General Population % MPE vs. Distance

The highest combined value for % MPE for existing emitters (11.94% of the General Population limit) is calculated to occur at a horizontal distance of 416 feet from antennas. The maximum %MPE generated by the proposed 28 GHz microwave system is 0.12% and occurs at the distance of 344 feet. While the peak % MPE generated by the proposed 28 GHz microwave system does not occur at the same point as the peak cumulative %MPE for all existing emitters, as a very conservative calculation of the total %MPE, we add the 11.94% predicted at 416 feet to the 0.12% predicted for the 28 GHz system at 344 feet to arrive at a total maximum % MPE of 12.06%.

Please note that the percent of MPE calculations close to the site take into account off beam loss, which is determined from the vertical pattern of the antennas used. Therefore, RF power density levels may increase as the distance from the site increases. At distances of approximately 1500 feet and beyond, one would now be in the main beam of the antenna pattern and off beam loss is no longer considered. Beyond this point, RF levels become calculated solely on distance from the site and the percent of MPE decreases significantly as distance from the site increases.

Table 2 below lists percent of MPE values as well as the associated parameters that were included in the calculations. The highest percent of MPE value was calculated to occur at a horizontal distance of 416 feet from the site (reference Figure 1).

As stated in Section 3, all calculations assume that the antennas are operating at 100 percent capacity, that all antenna channels are transmitting simultaneously, and that the radio transmitters are operating at full power. Obstructions (trees, buildings etc.) that would normally attenuate the signal are not taken into account. In addition, a six foot height offset was considered in this analysis to account for average human height. As a result, the predicted signal levels are significantly higher than the actual signal levels will be from the final configuration. The results presented in Figure 1 and Table 2 assume level ground elevation from the base of the tower out to the horizontal distances calculated.

| Carrier | Number of Transmitters | Power out of Base Station Per Transmitter (Watts) | Antenna Height (Feet) | Distance to the Base of Antennas (Feet) | Power Density (mW/cm ²) | Limit (mW/cm ²) | % MPE |
|----------------------|------------------------|---|-----------------------|---|-------------------------------------|-----------------------------|---------------|
| DISH 5G 1900 MHz | 1 | 160.0 | 77.0 | 416 | 0.006263 | 1.000 | 0.63% |
| DISH 5G 2100 MHz | 1 | 160.0 | 77.0 | 416 | 0.006550 | 1.000 | 0.65% |
| DISH 5G 600 MHz | 1 | 120.0 | 77.0 | 416 | 0.002791 | 0.400 | 0.70% |
| Verizon 5G 3500 MHz | 1 | 20.0 | 102.0 | 416 | 0.000448 | 1.000 | 0.04% |
| Verizon 5G 3700 MHz | 1 | 200.0 | 102.0 | 416 | 0.076106 | 1.000 | 7.61% |
| Verizon LTE 1900 MHz | 1 | 160.0 | 102.0 | 416 | 0.004723 | 1.000 | 0.47% |
| Verizon LTE 2100 MHz | 1 | 240.0 | 102.0 | 416 | 0.007468 | 1.000 | 0.75% |
| Verizon LTE 750 MHz | 1 | 160.0 | 102.0 | 416 | 0.003269 | 0.500 | 0.65% |
| Verizon LTE 885 MHz | 1 | 160.0 | 102.0 | 416 | 0.002434 | 0.567 | 0.43% |
| | | | | | | Total | 11.94% |
| Verizon LTE 28GHz | 1 | 0.2 | 12.0 | 344 | 0.001248 | 1.000 | 0.12% |
| | | | | | | Grand Total | 12.06% |


Table 2: Maximum Percent of General Population Exposure Values

6. Conclusion

The above analysis verifies that RF exposure levels from the site with Verizon's proposed 28 GHz microwave antenna will be well below the maximum permissible levels as outlined by the FCC in the OET Bulletin 65 Ed. 97-01. Using the conservative calculation methods and parameters detailed above, the maximum cumulative percent of MPE in consideration of all existing transmitters and the proposed 28 GHz microwave system is calculated to be 12.06% of the FCC limit (General Population/Uncontrolled). This maximum cumulative percent of MPE value is calculated to occur 416 feet away from the site.

7. Statement of Certification

I certify to the best of my knowledge that the statements in this report are true and accurate. The calculations follow guidelines set forth in ANSI/IEEE Std. C95.3, ANSI/IEEE Std. C95.1 and FCC OET Bulletin 65 Edition 97-01.



Report Prepared By: Ram Acharya
RF Engineer 1
C Squared Systems, LLC

October 5, 2023
Date



Reviewed/Approved By: Martin Lavin
Senior RF Engineer
C Squared Systems, LLC

October 6, 2023
Date

Attachment A: References

OET Bulletin 65 - Edition 97-01 - August 1997 Federal Communications Commission Office of Engineering & Technology

IEEE C95.1-2005, IEEE Standard Safety Levels With Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz IEEE-SA Standards Board

IEEE C95.3-2002 (R2008), IEEE Recommended Practice for Measurements and Computations of Radio Frequency Electromagnetic Fields With Respect to Human Exposure to Such Fields, 100 kHz-300 GHz IEEE-SA Standards Board

Verizon's Radio Frequency Design Sheet updated 10/21/2022

AT&T's filing, Connecticut Siting Council Notice of Exempt Modification – Antenna Add - 150 Meriden Waterbury Road (aka 1 Service Road) Bloomfield, CT, dated 9/23/2022

As referenced to Dish Wireless LLC's filing, Connecticut Siting Council Tower Share Application – 150 Meriden Waterbury Road , Bloomfield, CT, dated 11/19/2021

T-Mobile's filing, Connecticut Siting Council Notice of Exempt Modification – 150 Meriden Waterbury Road , Bloomfield, CT, dated 10/1/2020

Attachment B: FCC Limits for Maximum Permissible Exposure (MPE)

(A) Limits for Occupational/Controlled Exposure⁴

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (E) (A/m) | Power Density (S) (mW/cm ²) | Averaging Time E ² , H ² or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|---|
| 0.3-3.0 | 614 | 1.63 | (100)* | 6 |
| 3.0-30 | 1842/f | 4.89/f | (900/f ²)* | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | - | - | f/300 | 6 |
| 1500-100,000 | - | - | 5 | 6 |

(B) Limits for General Population/Uncontrolled Exposure⁵

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (E) (A/m) | Power Density (S) (mW/cm ²) | Averaging Time E ² , H ² or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|---|
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34-30 | 824/f | 2.19/f | (180/f ²)* | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | - | - | f/1500 | 30 |
| 1500-100,000 | - | - | 1.0 | 30 |

f = frequency in MHz * Plane-wave equivalent power density

Table 3: FCC Limits for Maximum Permissible Exposure

⁴ Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

⁵ General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.









Figure 2: Graph of FCC Limits for Maximum Permissible Exposure (MPE)

Attachment C: Verizon Antenna Model Data Sheets and Electrical Patterns

| | |
|--|---|
| <p>LTE 700 MHz</p> <p>Manufacturer: COMMSCOPE Model #: NHH-65B-R2B Frequency Band: 698-806 MHz Gain: 14.5 dBi Vertical Beamwidth: 12.4° Horizontal Beamwidth: 65° Polarization: ±45° Dimensions (L x W x D): 71.97" x 11.85" x 7.09"</p> |  |
| <p>LTE 850 MHz</p> <p>Manufacturer: COMMSCOPE Model #: NHH-65B-R2B Frequency Band: 806-896 MHz Gain: 15.0 dBi Vertical Beamwidth: 11.2° Horizontal Beamwidth: 60° Polarization: ±45° Dimensions (L x W x D): 71.97" x 11.85" x 7.09"</p> |  |

| | |
|--|--|
| <p>LTE 1900 MHz</p> <p>Manufacturer: COMMSCOPE Model #: NHH-65B-R2B Frequency Band: 1850-1990 MHz Gain: 17.9 dBi Vertical Beamwidth: 5.2° Horizontal Beamwidth: 69° Polarization: ±45° Dimensions (L x W x D): 71.97" x 11.85" x 7.09"</p> |  |
| <p>LTE 2100 MHz</p> <p>Manufacturer: COMMSCOPE Model #: NHHSS-65B-R2BT4 Frequency Band: 1920-2200 MHz Gain: 18.0 dBi Vertical Beamwidth: 4.9° Horizontal Beamwidth: 64° Polarization: ±45° Dimensions (L x W x D): 72.97" x 11.85" x 7.13"</p> |  |
| <p>LTE 3500 MHz</p> <p>Manufacturer: COMMSCOPE Model #: NHHSS-65B-R2BT4 Frequency Band: 3550-3700 MHz Gain: 17.7 dBi Vertical Beamwidth: 5.7° Horizontal Beamwidth: 54° Polarization: ±45° Dimensions (L x W x D): 72.97" x 11.85" x 7.13"</p> |  |

Attachment D: Far Field Calculation Sheet

| | |
|---|--------|
| Band | 28 GHz |
| Operating Frequency (MHz) | 27,500 |
| General Population MPE (mW/cm²) | 1.000 |
| ERP Per Transmitter (Watts) | 785 |
| Number of Transmitters | 1 |
| Antenna Centerline (feet) | 12 |
| Total ERP (Watts) | 785 |
| Total ERP (dBm) | 59 |
| Maximum % of General Population Limit | 0.12% |
| Distance to Maximum % of General Population Limit (feet) | 344 |

ATTACHMENT 3



Dewberry Engineers Inc. | 617.695.3400
99 Summer Street, Suite 700 | 617.695.3310 fax
Boston, MA 02110-1200 | www.dewberry.com

August 14, 2023

Alex Tyurin
Verizon Wireless
99 East River Drive
East Hartford, CT 06108

Dear Mr. Tyurin:

Verizon Wireless has proposed to install (2) new Rohn FRM Ballast Sleds, (2) new 0.3m Microwave Antenna, and (2) WTM4000 Radio on the rooftop of an equipment shelter at various locations in Connecticut. The proposed equipment will be mounted on the rooftop of the ground mounted equipment shelter with a maximum height of 15' to the CL of the dish. **This assessment letter is limited to Connecticut sites only.**

Dewberry Engineers Inc. (Dewberry) has reviewed the latest antenna design provided by Verizon Wireless and has determined, based on a maximum ultimate wind speed of 140 mph, exposure D, per ANSI/TIA-222-H and 2022 CT State Building Code, that the proposed ballast sled and equipment shelter roof have adequate capacity to support the proposed equipment configuration. Each proposed ballast sled requires (6) CMU ballast blocks (34 lb . ea.), equaling 204 lbs of ballast to be evenly distributed across both trays. The proposed ballast sled, including ballast blocks, do not exceed the 40 psf minimum allowable roof live load of the existing shelter. **The proposed ballast frame is controlled by overturning moment and the maximum utilization of the proposed mount is 43.0%.** Dewberry assumes that the new antennas and associated equipment are installed per the manufacturer's specifications.

This assessment is based on our assumption that the ground mounted equipment shelter, and proposed ballast mounts are in good condition and were constructed in accordance with ANSI/TIA-222-H standards and the 2022 CT State Building Code. If, during construction, any damage, deterioration, and/or discrepancies are noticed, Dewberry is to be notified to assess any deviation from the assumed condition. Any alteration in equipment loading described above and on the associated plans will void any conclusions expressed herein and will require further analysis and design. No structural qualification is made or implied by this structural letter for existing structural members not supporting the proposed installation.

If you have any questions, please do not hesitate to call me at 617-531-0744.

Sincerely,
Dewberry Engineers Inc.

08/14/2023

Brandon Kelsey, P.E. (CT)
CT License No.: 36967
Structural Project Engineer

ATTACHMENT 4

Certificate of Mailing — Firm



| Name and Address of Sender | TOTAL NO. of Pieces Listed by Sender | TOTAL NO. of Pieces Received at Post Office™ | Affix Stamp Here Postmark with Date of Receipt. |
|--|---|--|--|
| Kenneth C. Baldwin, Esq. Robinson & Cole LLP 280 Trumbull Street Hartford, CT 06103 | 3 | 3 | |
| Postmaster, per (name of receiving employee) | | | |
| USPS® Tracking Number Firm-specific Identifier | Address (Name, Street, City, State, and ZIP Code™) | Postage | Fee |
| 1. | Philip Schenk, Acting Town Manager Town of Bloomfield 800 Bloomfield Avenue Bloomfield, CT 06002 | | Parcel Airlift |
| 2. | Justin LaFountain, Director of Building and Land Use Town of Bloomfield 800 Bloomfield Avenue Bloomfield, CT 06002 | | |
| 3. | SAMO Realty LLC 811 Blue Hills Avenue Bloomfield, CT 06002 | | |
| 4. | | | |
| 5. | | | |
| 6. | | | |