



December 06, 2018

Melanie A. Bachman Acting Executive Director Connecticut Siting Council 10 Franklin Square New Britain, CT 06051

RE: Notice of Exempt Modification for Verizon Macro: 806364

Verizon Site ID: Durham CT 143 R Old Blue Hill Rd., Durham Connecticut 06422 Latitude: 41° 27' 33.67"/ Longitude: 72° 39' 45.83"

Dear Ms. Bachman:

Verizon currently maintains twelve (12) antennas at the 100-foot level of the existing 120-foot monopole tower at 149 R Old Blue Hill Rd., Durham CT. The tower is owned by Crown Castle. The property is owned by Francis E. Behrens Jr. Verizon now intends to install three (3) RRHs, and three (3) diplexers.

The Connecticut Siting Council approved this facility, an email was sent on 12/06/2018 to the Town of Durham Planning and Zoning Office to ascertain the original zoning approval documents and date.

Please accept this letter as notification pursuant to Regulations of Connecticut State Agencies § 16-50j-73, for construction that constitutes an exempt modification pursuant to R.C.S.A. § 16-50j-72(b)(2). In accordance with R.S.C.A. § 16-50j-73, a copy of this letter is being sent to First Selectman Laura L. Francis, Town of Durham, Geoffrey L. Colegrove, Planning & Zoning Officer, Town of Durham, as well as the property owner, and Crown Castle is the tower owner.

- 1. The proposed modifications will not result in an increase in the height of the existing tower.
- 2. The proposed modifications will not require the extension of the site boundary.
- 3. The proposed modification will not increase noise levels at the facility by six decibels or more, or to levels that exceed state and local criteria.
- 4. The operation of the replacement antennas will not increase radio frequency emissions at the facility to a level at or above the Federal Communication Commission safety standard.

The Foundation for a Wireless World.

CrownCastle.com

Melanie A. Bachman September 21, 2018 Page 2

- 5. The proposed modifications will not cause a change or alteration in the physical or environmental characteristics of the site.
- 6. The existing structure and its foundation can support the proposed loading.

For the foregoing reasons, Verizon respectfully submits that the proposed modifications to the above-reference telecommunications facility constitutes an exempt modification under R.C.S.A. § 16-50j-72(b)(2). Please send approval/rejection letter to Attn: Jeffrey Barbadora.

Sincerely, Barb

Jeffrey Barbadora Real Estate Specialist 12 Gill Street, Suite 5800, Woburn, MA 01801 781-729-0053

Jeff.Barbadora@crowncastle.com

Attachments:

Tab 1: Exhibit-1: Compound plan and elevation depicting the planned changes


Tab 2: Exhibit-2: Structural Modification Report

Tab 3: Exhibit-3: General Power Density Table Report (RF Emissions Analysis Report)

cc: The Honorable Laura L. Francis Town Hall, 30 Town House Road P.O. Box 428 Durham, Connecticut 06422

> Geoffrey Colegrove: Planning & Zoning Officer 30 Town House Road P.O. Box 428 Durham, Connecticut 06422

Francis E. Behrens 109 Old Blue Hills Rd. Durham, CT 06422-3005





Parcel ID: 69-12 Account #: B0016900

Owner: BEHRENS FRANCIS E JR Mailing Address: 109 OLD BLUE HILLS RD

DURHAM, CT 06422-3005

General Information	Assessed Value
State Class: 130 Class: R Census-Tract: 5851 District No.: M Neighborhood: 80 Zone: FR Total Acres: 6.31	Land: \$126,400 Buildings: \$0 Total: \$2,030
Sale History	
Book/Page: 100-255 Deed Date: 19840824 Sale Date: Sale Type: 0 Sale Price: 0	
Building Details	
Living Units: 0 Style: 0 Year Built: 0 Effective Year Built: 0 Ture TLA: 0 Stories: 0 Total Rooms: 0 Total Bedrooms: 0 Number Full Baths: 0 Number Half Baths: 0 WB/FP Openings: 0 Heating Type: 0 Heating Fuel Type: 0	Basement: 0 FBLA Size: 0 Attic: 0 Exterior Walls: 0 Basement / Garage: 0







verizon

CROWN
CASTLE

7

VERIZON WIRELESS CM:

VERIZON SITE NAME:

DURHAM CT

CROWN CASTLE SITE NAME:

HRT 106(B) 943202

CROWN CASTLE BU NUMBER:

806364

SITE ADDRESS:

SITE TYPE:

MONOPOLE TOWER

101 OLD BLUE HILL ROAD DURHAM, CT 06422

SITE INFORMATION AREA MAP PROJECT DESCRIPTION DRAWING INDEX VERIZON PROPOSES TO MODIFY AN EXISTING UNMANNED TELECOMMUNICATION FACILITY: APPLICANT: SHEET NO: SHEET TITLE Ü VERIZON 180 WASHINGTON VALLEY ROAD BEDMINSTER, NJ 07921 TITLE SHEET & PROJECT DATA ERIZON EQUIPMENT TO BE INSTALLED: VERIZON SPECIFICATIONS 1 SP-1 INSTALL (3) NOKIA RRU'S P/N: AHCA AIRSCALE RRH 4T4R B5 160W A-1 OVERALL SITE PLAN **CONTACT:** ENLARGED SITE PLAN Α INSTALL (3) RFS DIPLEXERS P/N: FDJ85020Q4-S1 WITHIN EXISTING A-3 TOWER ELEVATION Α **PROPERTY OWNER:** ANTENNA LAYOUT & LOADING CHART A-4 Α INSTALL (3) RFS DIPLEXERS P/N: FDJ85020Q4-S1 ON EXISTING TOWER EQUIPMENT & MOUNTING DETAILS GROUNDING PLAN & DETAILS (68) 110 **TOWER OWNER:** SITE CROWN CASTLE (82) CROWN CASTLE PM: (154) JEFFREY BARBADORA (781) 970-0053 (17) LATITUDE (NAD83): 41° 27° 33.67" N 41.459353° (77) THESE PLANS HAVE BEEN DEVELOPED FOR THE MODIFICATION OF AN EXISTING UNMANNED TELECOMMUNICATIONS FACILITY OWNED OR LEASED BY VERIZON IN ACCORDANCE WITH THE SCOPE OF WORK PROVIDED BY VERIZON. INFINIGY HAS INCORPORATED THIS SCOPE OF WORK IN THE PLANS, THESE PLANS ARE NOT FOR CONSTRUCTION UNLESS ACCOMPANIED BY A PASSING STRUCTURAL STABILITY ANALYSIS PREPARED BY A LICENSED STRUCTURAL. (3) LONGITUDE (NAD83): tii 72' 39' 45.83" W New Haven **COUNTY:** ENGINEER. STRUCTURAL ANALYSIS MUST INCLUDE BOTH TOWER AND MOUNT Guilford 63 MIDDLESEX LOCATION MAP APPLICABLE CODES DRIVING DIRECTIONS **ZONING JURISDICTION:** DM: HARTFORD, CT HEAD SOUTH ON MAIN ST TOWARD TOWER SQUARE ALL WORK SHALL BE PERFORMED AND MATERIALS INSTALL IN ACCORDANCE WITH THE CURRENT EDITIONS OF THE FOLLOWING CODES AS ADOPTED BY THE LOCAL GOVERNING AUTHORITIES. NOTHING IN THESE PLANS IS TO BE CONSTRUED TO PERMIT WORK CONNECTICUT SITING COUNCIL TURN RIGHT ONTO WELLS ST **POWER COMPANY:** AT THE TRAFFIC CIRCLE, TAKE THE 4TH EXIT ONTO WHITEHEAD HWY CL&P (800) 340-9822 HEADING TO INTERSTATE 91/CT-15/SPRINGFIELD/NEW HAVEN/NEW YORK INTERNATIONAL BUILDING CODE (2015 IBC)
TIA-EIA-222-G OR LATEST EDITION
NFPA 780 — LIGHTNING PROTECTION CODE
2017 NATIONAL ELECTRIC CODE OR LATEST EDITION
ANY OTHER NATIONAL OR LOCAL APPLICABLE CODES,
MOST RECENT EDITIONS KEEP RIGHT AT THE FORK, FOLLOW SIGNS FOR I-91 S/NEW HAVEN AND TELCO PROVIDER: FOLLOW I-91 S AND CT-9 S TO CT-17 S IN MIDDLETOWN. TAKE EXIT 13 FROM CT-9 S (17) LIGHTOWER (855) 91-FIBER

79 (77)

- 6. CT BUILDING CODE
- 8. CITY/COUNTY ORDINANCES


Know what's below. Call before you dig.

- MERGE ONTO I-91 S
- USE THE LEFT LANE TO TAKE EXIT 22S TO MERGE ONTO CT-9 S TOWARD
- TAKE EXIT 13 FOR STATE ROUTE 17 S TOWARD NEW HAVEN CONTINUE ON CT-17 S. DRIVE TO OLD BLUE HILLS RD IN DURHAM
- CONTINUE ONTO CT-17 S TURN LEFT ONTO MADISON RD
- 12. TURN LEFT ONTO OLD BLUE HILLS RD
 13. DESTINATION WILL BE ON THE RIGHT



1490 W. 121st. Ave., Suite 101 Westminster, CO 80234 Office # (303) 219-1178 Fax # (303) 242-8636





THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF VERIZON AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS

	_	_
DATE	BY	REV
11/5/18	SKÐ	A
֡		

DURHAM CT

HRT 106(B) 943202

806346

101 OLD BLUE HILL ROAD DURHAM, CT 06422

- SHEET DESCRIPTION:

TITLE SHEET & PROJECT DATA

SHEET NUMBER: -

T-1

ELECTRICAL NOTES:

ON INCLUDE ALL LABOR, MATERIALS, EQUIPMENT, PLANT SERVICES
AND ADMINISTRATIVE TASKS REQUIRED TO COMPLETE AND MAKE
OPERABLE THE ELECTRICAL WORK SHOWN ON THE DRAWNINGS
AND SPECIFIED HERBIN, INCLUDING BUT NOT LIMITED TO THE

FOLLOWING:

A. PREPARE AND SUBMIT SHOP DRAWINGS, DIAGRAMS AND

- ILLUSTRATIONS.
 B. PROCURE ALL NECESSARY PERMITS AND APPROVALS AND PAY ALL REQUIRED FEES AND CHARGES IN CONNECTION WITH THE WORK OF THIS CONTRACT.
- C. SUBMIT AS-BUILT DRAWINGS, OPERATING AND MAINTENANCE INSTRUCTIONS AND MANUALS.

 D. EXECUTE ALL CUTTING, DRILLING, ROUGH AND FINISH
- PATCHING OF EXISTING OR NEWLY INSTALLED CONSTRUCTION REQUIRED FOR THE WORK OF THIS CONTRACT. FOR SLAB PENETRATIONS THROUGH POST TENSION SLABS, X-RAY EXACT AREA OF PENETRATION PRIOR TO PERFORMING WORK.
 COORDINATE ALL X-RAY WORK WITH BUILDING ENGINEER.

PROVIDE HANGERS, SUPPORTS, FOUNDATIONS, STRUCTURAL FRAMING SUPPORTS, AND BASES FOR CONDUIT AND FOUIPMENT PROMOFD OR INSTALLED LINDER THE WORK OF HIS CONTRACT. PROVIDE COUNTER FLASHING, SLEEVES AND SEALS FOR FLOOR AND WALL PENETRATIONS.

- MAINTAIN ALL EXISTING ELECTRICAL SERVICES IN THE BUILDING AREAS NOT AFFECTED BY THE ALTERATION DURING THE PROGRESS OF THE WORK INCLUDING PROVIDING ALL TEMPORARY JUMPERS, CONDUITS, CAPS, PROTECTIVE DEVICES, CONNECTIONS AND EQUIPMENT REQUIRED. PROVIDE TEMPORARY LIGHT AND POWER FOR CONSTRUCTION
- PURPOSES.

 2. IT IS THE INTENT OF THESE DRAWINGS AND SPECIFICATIONS TO CALL FOR AN INSTALLATION THAT IS COMPLETE IN EVERY RESPECT. IT IS NOT THE INTENT TO GIVE EVERY DETAIL ON THE DRAWINGS AND IN THE SPECIFICATIONS. IF AN ITEM OF WORK IS INDICATED IN THE DRAWINGS, IT IS CONSIDERED SUFFICIENT FOR INCLUSION IN THE CONTRACT, FURNISH AND INSTALL ALL MATERIAL AND EQUIPMENT USUALLY FURNISHED OR NEEDED TO MAKE A COMPLETE INSTALLATION WHETHER OR NOT SPECIFICALLY MENTIONED IN THE CONTRACT DOCUMENTS

GENERAL REQUIREMENTS

- . PROVIDE ALL WORK IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE (NEC) AND LOCAL AND STATE ELECTRICAL
- 2. THE ELECTRICAL PLANS ARE DIAGRAMMATIC ONLY, REFER TO THE ARCHITECTURAL PLANS FOR THE EXACT DIMENSIONS OF
- 3. LOAD CALCULATIONS ARE BASED ON EXISTING BUILDING NEGRMATION /DRAWINGS PROVIDED TO ENGINEERING CONTRACTOR IS TO VERIFY ALL EXISTING RATINGS AND LOADS PRIOR TO PURCHASING OF SPECIFIED EQUIPMENT FOR COMPLIANCE TO NEC. CONTRACTOR TO NOTIFY ENGINEER OF ANY DISCREPANCIES AND REQUEST FURTHER DIRECTION BY
- EXISTING BUILDING EQUIPMENT IS NOTED ON THE DRAWINGS. NEW OR RELOCATED EQUIPMENT IS SHOWN WITH SOLID LINES.
 FUTURE EQUIPMENT (NOT IN THIS CONTRACT) IS DEPICTED WITH
 SHADED LINES. REQUEST CLARIFICATION OF DRAWINGS OR OF
 SPECIFICATIONS PRIOR TO PRICING OR INSTALLATION.

- A. AFTER CAREFULLY STUDYING THE DRAWINGS AND SPECIFICATIONS, AND BEFORE SUBMITTING THE PROPOSAL, MAKE A MANDATORY SITE VISIT TO ASCERTAIN CONDITIONS OF THE SITE. AND THE NATURE AND EXACT QUANTITY OF WORK TO BE PERFORMED. NO EXTRA COMPENSATION WILL BE ALLOWED FOR FAILURE TO NOTIFY THE OWNER, IN WRITING, OF ANY DISCREPANCIES THAT MAY HAVE BEEN NOTED BETWEEN THE EXISTING CONDITIONS AND THE DRAWINGS AND SPECIFICATIONS.
- SPECIFICATIONS.

 B. VERIFY ALL MEASUREMENTS AT THE SITE AND BE RESPONSIBLE FOR CORRECTNESS OF SAME.

 6. QUALITY, WORKMANSHIP, MATERIALS AND SAFETY A PROVIDE NEW MATERIALS AND EQUIPMENT OF A DOMESTIC MANUFACTURER BY THOSE REGULARLY ENGAGED IN THE PRODUCTION AND MANUFACTURE OF SPECIFIED MATERIALS
 AND EQUIPMENT. WHERE UL, OR OTHER AGENCY, HAS
 ESTABLISHED STANDARDS FOR MATERIALS, PROVIDE MATERIALS WHICH ARE LISTED AND LABELED ACCORDINGLY. THE COMMERCIALLY STANDARD ITEMS OF EQUIPMENT AND THE SPECIFIC NAMES MENTIONED HEREIN ARE INTENDED FOR THE PROPER FUNCTIONING OF THE WORK.

 WORK SHALL BE PERFORMED BY WORKMEN SKILLED IN THE
- TRADE REQUIRED FOR THE WORK INSTALL MATERIALS AND EQUIPMENT TO PRESENT A NEAT APPEARANCE WHEN COMPLETED AND IN ACCORDANCE WITH THE APPROVED RECOMMENDATIONS OF THE MANUFACTURER AND IN ACCORDANCE WITH CONTRACT DOCUMENTS.
- ACCOMMANCE WITH CONTRACT DOCUMENTS.

 C. PROVIDE LABOR, MATERIALS, APPARATUS AND APPLIANCES
 ESSENTIAL TO THE FUNCTIONING OF THE SYSTEMS DESCRIBED
 OR INDICATED HEREIN, OR WHICH MAY BE REASONABLY
 IMPLED AS ESSENTIAL WHENEVER MENTIONED IN THE
 CONTRACT DOCUMENT OR NOT.
- D. MAKE WRITTEN REQUESTS FOR SUPPLEMENTARY
 INSTRUCTIONS TO ARCHITECT/ENGINEER IN CASE OF DOUBT as to work intended or in event of need for
- E. PERFORMANCE AND MATERIAL REQUIREMENTS SCHEDULED OR SPECIFIED ARE MINIMUM STANDARD ACCEPTABLE. THE RIGHT TO JUDGE THE QUALITY OF EQUIPMENT THAT DEVIATES FROM THE CONTRACT DOCUMENT REMAINS SOLELY WITH ARCHITECT/ENGINEER. CONTRACT DOCUMENT OR NOT.

1. GUARANTEE MATERIALS, PARTS AND LABOR FOR WORK FOR ONE YEAR FROM THE DATE OF ISSUANCE OF OCCUPANCY PERMIT. DURING THAT PERIOD, MAKE GOOD FAULTS OR IMPERFECTIONS THAT MAY ARISE DUE TO DEFECTS OR OMISSIONS IN MATERIALS OR WORKMANSHIP WITH NO ADDITIONAL COMPENSATION AND AS DIRECTED BY ARCHITECT

- 1. REMOVE ALL CONSTRUCTION DEBRIS RESULTING FROM THE
- 2. CLEAN EQUIPMENT AND SYSTEMS FOLLOWING THE COMPLETION OF THE PROJECT TO THE SATISFACTION OF THE ENGINEER.
- COORDINATION AND SUPERVISION

 1. CAREFULLY LAY OUT ALL WORK IN ADVANCE TO AVOID
 UNNECESSARY CUTTING, CHANNELING, CHASING OR DRILLING OF
 FLOORS, WALLS, PARTITIONS, CEILINGS OR OTHER SURFACES. WHERE SUCH WORK IS NECESSARY, HOWEVER, PATCH AND REPAIR THE WORK IN AN APPROVED MANNER BY SKILLED MECHANICS AT NO ADDITIONAL COST TO THE OWNER, RENDER FULL COOPERATION TO OTHER TRADES WHERE WORK WILL BE ASSIST IN WORKING OUT SPACE CONDITIONS, IF WORK IS INSTALLED BEFORE COORDINATION WITH OTHER TRADES, OR CAUSES INTERFERENCE, MAKE CHANGES NECESSARY TO CORRECT CONDITIONS WITHOUT EXTRA CHARGE.

SUBMITTALS

1. AS-BUILT DRAWINGS

- A. UPON COMPLETION OF THE WORK, FURNISH TO THE OWNER "AS-RUILT" DRAWINGS.
- 2. SERVICE MANUALS:
- 2. SERVICE MANUALS:
 A. UPON COMPLETION OF THE WORK, FULLY INSTRUCT VERIZON
 AS TO THE OPERATION AND MAINTENANCE OF ALL MATERIAL,
 EQUIPMENT AND SYSTEMS.
 B. PROVIDE 3 COMPLETE BOUND SETS OF INSTRUCTIONS FOR

CULTING AND PATCHING

- PROVIDE ALL CUTTING, DRILLING, ROUGH AND FINISH PATCHING REQUIRED TO COMPLETE THE WORK.
- OBTAIN OWNER APPROVAL PRIOR TO CUTTING THROUGH FLOORS OR WALLS FOR PIPING OR CONDUIT.

TESTS, INSPECTION AND APPROVAL

- 1. BEFORE ENERGIZING ANY ELECTRICAL INSTALLATION, INSPECT EACH UNIT IN DETAIL TIGHTEN ALL BOLTS AND CONNECTIONS (TORQUE-TIGHTEN WHERE REQUIRED) AND DETERMINE THAT ALL COMPONENTS ARE ALIGNED, AND THE EQUIPMENT IS IN SAFE,
- OPERATIONAL CONDITION.
 2. PROVIDE THE COMPLETE ELECTRICAL SYSTEM FREE OF GROUND FAULTS AND SHORT CIRCUITS SUCH THAT THE SYSTEM WILL OPERATE SATISFACTORILY UNDER FULL LOAD CONDITIONS, WITHOUT EXCESSIVE HEATING AT ANY POINT IN THE SYSTEM

- 1. DO NOT LEAVE ANY WORK INCOMPLETE NOR ANY HAZARDOUS SITUATIONS CREATED WHICH WILL AFFECT THE LIFE OR SAFETY OF THE PUBLIC AND/OR BUILDING OCCUPANTS. DO NOT
- WITHOUT THE OWNER'S WRITTEN PERMISSION.

 2. WHEN NECESSARY TO TEMPORARILY DISCONNECT ANY EXISTING BUILDING UTILITIES AND SERVICE SYSTEMS, INCLUDING FEEDER OR BRANCH CIRCUITING SUPPLYING EXSTING FACILITIES. CONFER WITH THE OWNER AND ARRANGE THE PERIOD OF INTERRUPTION FOR A TIME MUTUALLY AGREED UPON. SHUTDOWN NOTE: SCHEDULE AND NOTIFY OWNER 48 HOURS

- SCHEDULED AT A TIME CONVENIENT TO OWNER. 1. ROUTE ALL GROUNDING CONDUCTORS AS SHOWN ON
- CONDUIT/GROUNDING RISER.

 2. ROUTE 500 KCMIL CU. THIN CONDUCTOR FROM THE MGB 2. ROUTE 500 KOMIL CU. THIN COMBITOR FROM THE MGB LOCATION TO BUILDING STEEL VERIFY BUILDING STEEL IS EFFECTIVELY GROUNDED PER NEC TO THE MAIN SERVICE GROUNDING ELECTROBE CONDUCTOR (GEC).

 3. MAKE ALL GROUND CONNECTIONS FROM MGB TO ELECTRICAL EQUIPMENT WITH 2 HOLE, CRIMP TYPE, BURNDY COMPRESSION TERMINATIONS STEED AS DECIMIED.
- TERMINATIONS, SIZED AS REQUIRED.

 4. USE 1 HOLE, CRIMP TYPE, BURNDY COMPRESSIONS
 TERMINATIONS, SIZED AS REQUIRED, AT EQUIPMENT GROUND
- CONNECTIONS.

 5. HIRE AN INDEPENDENT LAB TO PERFORM THE SPECIFIED OHMS
 TESTING. PROVIDE 4 SETS OF THE CERTIFIED DOCUMENTS TO
 THE OWNER FOR VERIFICATION PRIOR TO THE PROJECT COMPLETION.

- RACEWAYS

 1. ALL WIRING TO BE INSTALLED IN CONDUIT SYSTEMS IN
- ACCORDANCE WITH THE FOLLOWING:
 A. EXTERIOR FEEDERS AND CONTROL, WHERE UNDERGROUND, TO BE IN SCH 40 PVC.
- BE EN SCH 40 PVC.

 B. EXTERIOR, ABOVE GROUND POWER CONDUITS TO BE GALVANIZED RIGID STEEL (RGS).

 C. ALL TELECOMMUNICATION CONDUITS, INTERIOR/EXTERIOR, TO

- E. ALL TELECOM CONDUITS AND PULL BOXES INSTALLED ON THIS PROJECT TO BE LABELED "VERIZON". OWNER WILL PROVIDE LABELS FOR CONTRACTOR TO INSTALL
- F. INTERIOR FEEDERS TO BE INSTALLED IN E.M.T. WITH STEEL
- COMPRESSION FITTINGS.

 G. MINIMUM SIZE CONDUIT TO BE ** TRADE SIZE UNLESS OTHERWISE INDICATED ON THE DRAWNGS.
- H. FINAL CONNECTIONS TO MOTORS AND VIBRATING EQUIPMENT TO BE INSTALLED IN LIQUID—TIGHT FLEXIBLE METAL CONDUIT.
- AREAS OR DRYWALL PARTITIONS, UNLESS OTHERWISE NOTED.
 J. THE ROUTING OF CONDUITS INDICATED ON THE DRAWINGS IS DIAGRAMMATIC. BEFORE INSTALLING ANY WORK, EXAMINE THE WORKING LAYOUTS AND SHOP DRAWINGS OF THE OTHER TRADES TO DETERMINE THE EXACT LOCATIONS AND
- IRADES TO DETAMINE THE EXACT LOCATIONS AND
 CLEARANCES.

 K. ALL EXTERIOR MOUNTING HARDWARE TO BE GALVANIZED
 STEEL COORDINATE WITH BUILDING ENGINEER PRIOR TO
 ATTACHING TO BUILDING STRUCTURE.

RACEWAYS CONT'D

- L. PENETRATIONS OF WALLS, FLOORS AND ROOFS, FOR THE PASSAGE OF ELECTRICAL RACEWAYS, TO BE PROPERLY SEALED AFTER INSTALLATION OF RACEWAYS SO. AS TO MAINTAIN THE STRUCTURAL OR WATERPROOF INTEGRITY OF THE WALL, FLOOR OR ROOF SYSTEM TO BE PENETRATED. SEAL ALL CONDUIT PENETRATIONS THROUGH FIRE OR SMOKE RATED WALLS, CEILINGS OR SMOKE TIGHT CORRIDOR
- M. PROVIDE ALL CONDUIT ENDS WITH INSULATED METALLIC
- GROUNDING BUSHINGS.
 N. CONDUIT TO BE SUPPORTED AT MAXIMUM DISTANCE OF 3'-0", OR AS REQUIRED BY NEC, IN HORIZONTAL AND
- VERTICAL DIRECTIONS. O. PROVIDE STAINLESS STEEL BLANK COVER PLATES FOR ALL JUNCTION BOXES AND/OR OUTLET BOXES NOT USED IN EXPOSED AREAS. PROVIDE ALL OTHER UNUSED BOXES WITH
- STANDARD STEEL COVER PLATES.
 P. WHERE APPLICABLE, PROVIDE ROOFTOP CONDUIT SUPPORT SYSTEM, CONFORMING TO ROOFTOP WARRANTY REQUIREMENTS, PER BUILDING.

- MRES AND CABLES
 1. CONTRACTOR TO COORDINATE WITH EQUIPMENT SUPPLIER AND VENDOR FOR EXACT EQUIPMENT OVER—CURRENT PROTECTION VOLTAGE, WIRE SIZE AND PLUG CONFIGURATION, IF APPLICABLE, PRIOR TO BID.
- 2. ALL EQUIPMENT/DEVICES TO BE PROVIDED WITH INSULATED GROUND CONDUCTOR.

 3. ALL WIRE AND CABLE TO BE 600VOLT, COPPER, WITH THWN/
- 3. ALL MINE AND CABLE TO BE GOVOLT, COPPER, WITH ITHMY THIN INSULATION, EXCEPT AS NOTED.

 4. WIRE FOR POWER AND LIGHTING WILL NOT BE LESS THAN NO. 12AWG. ALL WIRE NO. B AND LARGER TO BE STRANDED.

 5. CONTROL WIRING IS NOT TO BE LESS THAN NO. 14AWG.
- FLEXIBLE IN SINGLE CONDUCTORS OR MULTI-CONDUCTOR
 CABLES. CONTROL WIRING WILL CONSIST OF MULTI-CONDUCTOR
 CABLES WHEREVER POSSIBLE, CABLES TO BE PROVIDED WITH AN OVERALL FLAME-RETARDANT, EXTRUDED JACKET AND RATED FOR PLENUM USE. ALL CONTROL WIRE TO BE 600VOLT RATED.
- 6. WIRE PREVIOUSLY PULLED INTO CONDUIT IS CONSIDERED USED AND IS NOT TO BE RE-PULLED.
 7. HOME RUNS AND BRANCH CIRCUIT WIRING FOR 20A, 120V
- CIRCUITS: LENGTH (FT.) HOME RUN WIRE SIZE 0 TO 50 101 TO 150
- 3. VOLTAGE DROP IS NOT TO EXCEED 3%. D. MAKE ALL CONNECTIONS WITH UL APPROVED, SOLDERLESS, PRESSURE TYPE INSULATED CONNECTORS; SCOTCHLOK OR AND PROVED EQUAL.
- WIRING DEVICES . ALL RECEPTACLES INSTALLED IN THIS PROJECT TO BE GROUNDING TYPE, WITH GROUNDING PIN SLOT CONNECTED TO DEVICE GROUND SCREW FOR GROUND WIRE CONNECTION.
- ISCONNECT SWITCHES AND FUSES

 1. DISCONNECT SWITCHES TO BE VOLTAGE—RATED TO SUIT THE CHARACTERISTICS OF THE SYSTEM FROM WHICH THEY ARE
- 2. PROVIDE HEAVY-DUTY, METAL-ENCLOSED, EXTERNALLY-OPERATED DISCONNECT SWITCHES, FUSED OR UNFUSED, OF SUCH TYPE AND SIZE AS REQUIRED TO PROPERLY PROTECT OR DISCONNECT THE LOAD FOR WHICH THEY ARE INTENDED
- PROVIDE NEMA 1 DISCONNECT SWITCHES FOR INTERIOR INSTALLATION, NEMA 3R FOR EXTERIOR INSTALLATION.
- I, DISCONNECT SWITCHES TO BE MANUFACTURED BY: A, GENERAL ELECTRIC COMPANY
- B. SQUARE-D PROVIDE RK-1 TYPE FUSES, UNLESS NOTED OTHERWISE.
- INSTALLATION 1. INSTALL DISCONNECT SWITCHES WHERE INDICATED ON
- 2. INSTALL FUSES IN FUSIBLE DISCONNECT SWITCHES, FUSES MUST MATCH IN TYPE AND RATING.

 3. FUSES TO BE MOUNTED SO THAT THE LABELS SHOWING THEIR
- RATINGS CAN BE READ WITHOUT REQUIRING FUSE REMOVAL.
 4. FURNISH AND DEPOSIT SPARE FUSES AT THE JOB SITE AS
- FOLLOWS:
- FOLLOWS:
 A. THREE SPARES FOR EACH TYPE AND SIZE, IN EXCESS OF
 60A, USED FOR INITIAL FUSING.
 B. TEN PERCENT SPARES FOR EACH TYPE AND SIZE, UP TO
 AND INCLUDING 60A, USED FOR INITIAL FUSING. IN NO CASE
 WILL LESS THAN THREE FUSES OF ONE PARTICULAR TYPE AND

CONFLICTS

- 1. THE CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFICATIONS
 OF ALL MEASUREMENTS AT THE SITE BEFORE ORDERING ANY
 MATERIALS OR DOING ANY WORK, NO EXTRA CHARGE OR
 COMPENSATION SHALL BE ALLOWED DUE TO DIFFERENCE
 BETWEEN ACTUAL DIMENSIONS AND DIMENSIONS INDICATED ON
 THE CONSTRUCTION DRAWINGS, ANY SUCH DISCREPANCY IN DIMENSION WHICH MAY BE FOUND SHALL BE SUBMITTED TO THE OWNER FOR CONSIDERATION BEFORE THE CONTRACTOR PROCEEDS WITH THE WORK IN THE AFFECTED AREAS.
- THE BIDDER, IF AWARDED THE CONTRACT, WILL NOT BE ALLOWED ANY EXTRA COMPENSATION BY REASON OF ANY MATTER OR THING CONCERNING SUCH BIDDER MIGHT HAVE FULLY INFORMED THEMSELVES PRIOR TO THE BIDDING.

 J. NO PLEA OF IGNORANCE OF CONDITIONS THAT EXIST, OR OF
- DIFFICULTIES OR CONDITIONS THAT MAY BE ENCOUNTERED, OR OF ANY OTHER RELEVANT MATTER CONCERNING THE WORK TO BE PERFORMED IN THE EXECUTION OF THE WORK WILL BE ACCEPTED AS AN EXCUSE FOR ANY FAILURE OR OMISSION ON THE PART OF THE CONTRACTOR TO FULFILL EVERY DETAIL OF ALL THE REQUIREMENTS OF THE CONTRACT DOCUMENTS

- CONTRACTS AND WARRANTIES

 1. CONTRACTOR IS RESPONSIBLE FOR APPLICATION AND PAYMENT OF CONTRACTOR LICENSES AND BONDS.

 2. SEE MASTER CONTRACTION SERVICES AGREEMENT FOR

1. ALL MATERIALS MUST BE STORED IN A LEVEL AND DRY FASHION
AND IN A MANNER THAT DOES NOT NECESSARILY OBSTRUCT THE
FLOW OF OTHER WORK, ANY STORAGE METHOD MUST MEET ALL RECOMMENDATIONS OF THE ASSOCIATED MANUFACTURER.

- 1. THE CONTRACTORS SHALL, AT ALL TIMES, KEEP THE SITE FREE FROM ACCUMULATION OF WASTE MATERIALS OR RUBBISH CAUSED BY THEIR EMPLOYEES AT WORK AND AT THE COMPLETION OF THE WORK, THEY SHALL REMOVE ALL RUBBISH FROM AND ABOUT THE BUILDING AREA, INCLUDING ALL THEIR TOOLS, SCAFFOLDING AND SURPLUS MATERIALS AND SHALL LEAVE THEIR WORK CLEAN AND READY TO USE.
- A. VISUALLY INSPECT EXTERIOR SURFACES AND REMOVE ALL TRACES OF SOIL, WASTE MATERIALS, SMUDGES AND OTHER
- B. REMOVE ALL TRACES OF SPLASHED MATERIALS FROM ADJACENT SURFACES.
 C. IF NECESSARY, TO ACHIEVE A UNIFORM DEGREE OF
- CLEANLINESS, HOSE DOWN THE EXTERIOR OF THE STRUCTURE. A. VISUALLY INSPECT INTERIOR SURFACE AND REMOVE ALL TRACES OF SOIL, WASTE MATERIALS, SMUDGES AND OTHER FOREIGN MATTER FROM WALLS, FLOOR, AND CEILING.
- B. REMOVE ALL TRACES OF SPLASHED MATERIALS FROM ADJACENT SURFACES.
 C. REMOVE PAINT DROPPINGS, SPOTS, STAINS, AND DIRT FROM

FINISHED SURFACES. CHANGE ORDER PROCEDURE:

REFER TO SECTION 17 OF SIGNED MCSA: SEE PROFESSIONAL SERVICE AGREEMENT FOR MCSA.

- RELATED DOCUMENTS AND COORDINATION
 1. GENERAL CARPENTRY, ELECTRICAL AND ANTENNA DRAWINGS ARE INTERRELATED. IN PERFORMANCE OF THE WORK, THE CONTRACTOR MUST REFER TO ALL DRAWINGS. ALL COORDINATION TO BE THE RESPONSIBILITY OF THE CONTRACTOR
- SHOP DRAWNGS

 1. CONTRACTOR SHALL SUBMIT SHOP DRAWNGS AS REQUIRED AND LISTED IN THESE SPECIFICATIONS TO THE OWNER FOR
- 2. ALL SHOP DRAWINGS SHALL BE REVIEWED, CHECKED AND CORRECTED BY CONTRACTOR PRIOR TO SUBMITTAL TO THE

PRODUCTS AND SUBSTITUTIONS

- 1. SUBMIT 3 COPIES OF EACH REQUEST FOR SUBSTITUTION. IN EACH REQUEST, IDENTIFY THE PRODUCT OR FABRICATION OR INSTALLATION METHOD TO BE REPLACED BY THE SUBSTITUTION. INCLUDE RELATED SPECIFICATION SECTION AND DRAWING NUMBERS AND COMPLETE DOCUMENTATION SHOWING COMPLIANCE WITH THE REQUIREMENTS FOR SUBSTITUTIONS.
- . SUBMIT ALL NECESSARY PRODUCT DATA AND CUT SHEETS WHICH PROPERLY INDICATE AND DESCRIBE THE ITEMS, PRODUCTS AND MATERIALS BEING INSTALLED. THE CONTRACTOR SHALL, IF DEEMED NECESSARY BY THE OWNER, SUBMIT ACTUAL SAMPLES TO THE OWNER FOR APPROVAL IN LIEU OF CUT

. ALL WORK SHALL BE IN ACCORDANCE WITH APPLICABLE LOCAL STATE AND FEDERAL REGULATIONS. THESE SHALL INCLUDE, BUT NOT BE LIMITED TO THE APPLICABLE CODES SET FORTH BY THE LOCAL GOVERNING BODY. SEE "CODE COMPLIANCE" T-1.

- 1. BEFORE THE COMMENCEMENT OF ANY WORK, THE CONTRACTOR MILL ASSIGN A PROJECT MANAGER WHO WILL ACT AS A SINGLE POINT OF CONTACT FOR ALL PERSONNEL INVOLVED IN THIS PROJECT. THIS PROJECT MANAGER WILL DEVELOP A MASTER
- THE OWNER PRIOR TO THE COMMENCEMENT OF ANY WORK 2. SUBMIT A BAR TYPE PROGRESS CHART, NOT MORE THAN 3
 DAYS AFTER THE DATE ESTABLISHED FOR COMMENCEMENT OF
 THE WORK ON THE SCHEDULE, INDICATING A TIME BAR FOR EACH MAJOR CATEGORY OR UNIT OF WORK TO BE PERFORMED AT THE SITE, PROPERLY SEQUENCED AND COORDINATED WITH OTHER ELEMENTS OF WORK AND SHOWING COMPLETION OF THE WORK SUFFICIENTLY IN ADVANCE OF THE DATE ESTABLISHED FOR SUBSTANTIAL COMPLETION OF THE WORK
- FOR SUBSTANTIAL COMPLETION OF THE WORK.

 PRIOR TO COMMENCING CONSTRUCTION, THE OWNER SHALL
 SCHEDULE AN ON-SITE MEETING WITH ALL MAJOR PARTIES. THIS
 WOULD INCLUDE, BUT NOT LIMITED TO, THE OWNER, PROJECT
 MANAGER, CONTRACTOR, LAND OWNER REPRESENTATIVE, LOCAL
 TELEPHONE COMPANY, TOWER ERECTION FOREMAN (IF
- 4. CONTRACTOR SHALL BE EQUIPPED WITH SOME MEANS OF CONSTANT COMMUNICATIONS, SUCH AS A MOBILE PHONE OR A BEEPER. THIS EQUIPMENT WILL NOT BE SUPPLIED BY THE OWNER, NOR WILL WIRELESS SERVICE BE ARRANGED.
- 5. DURING CONSTRUCTION, CONTRACTOR MUST ENSURE THAT EMPLOYEES AND SUBCONTRACTORS WEAR HARD HATS AT ALL TIMES, CONTRACTOR WILL COMPLY WITH ALL WPCS SAFETY REQUIREMENTS IN THEIR AGREEMENT.

 6. PROVIDE WRITTEN DAILY UPDATES ON SITE PROGRESS TO THE
- 7. COMPLETE INVENTORY OF CONSTRUCTION MATERIALS AND EQUIPMENT IS REQUIRED PRIOR TO START OF CONSTRUCTION.
- NOTIFY THE OWNER/PROJECT MANAGER IN WRITING NO LESS THAN 48 HOURS IN ADVANCE OF CONCRETE POURS, TOWER FRECTIONS, AND FOUIPMENT CABINET PLACEMENTS

- INSURANCE AND BONDS

 1. CONTRACTOR, AT THEIR OWN EXPENSE, SHALL CARRY AND MAINTAIN, FOR THE DURATION OF THE PROJECT, ALL INSURANCE, AS REQUIRED AND LISTED, AND SHALL NOT COMMENCE WITH THEIR WORK UNTIL THEY HAVE PRESENTED AN ORIGINAL CERTIFICATE OF INSURANCE STATING ALL COVERAGES TO THE OWNER. REFER TO THE MASTER AGREEMENT FOR
- REQUIRED INSURANCE LIMITS.
 THE OWNER SHALL BE NAMED AS AN ADDITIONAL INSURED ON
- ALL POLICIES. 3. CONTRACTOR MUST PROVIDE PROOF OF INSURANCE.

GENERAL NOTES:

AG

APPROX

CLG CONC CONT

FLFC

ELEV

EQUIP

GALV

GC GRND

MAX

MECH

SHT

STL TOC TOM

DIA OR #

- 1. THESE SPECIFICATIONS AND CONSTRUCTION DRAWINGS ACCOMPANYING THEM DESCRIBE THE WORK TO BE DONE AND THE MATERIALS TO BE FURNISHED FOR CONSTRUCTION.
- THE DRAWINGS AND SPECIFICATIONS ARE INTENDED TO BE FULLY EXPLANATORY AND SUPPLEMENTARY, HOWEVER, SHOULD ANYTHING BE SHOWN, INDICATED, OR SPECIFIED ON ONE AND NOT THE OTHER, IT SHALL BE DONE THE SAME AS IF
- SHOWN, INDICATED OR SPECIFIED IN BOTH

 3. THE INTENTION OF THE DOCUMENTS IS TO INCLUDE ALL
 LABOR AND MATERIALS REASONABLY NECESSARY FOR THE PROPER EXECUTION AND COMPLETION OF THE WORK AS STIPULATED IN THE CONTRACT.
- 4. THE PURPOSE OF THE SPECIFICATIONS IS TO INTERPRET THE INTENT OF THE DRAWINGS AND TO DESIGNATE THE METHOD OF THE PROCEDURE, TYPE AND QUALITY OF MATERIALS REQUIRED TO COMPLETE THE WORK.
- 5. MINOR DEVIATIONS FROM THE DESIGN LAYOUT ARE
 ANTICIPATED AND SHALL BE CONSIDERED AS PART OF THE WORK.
 NO CHANGES THAT ALTER THE CHARACTER OF THE WORK WILL
 BE MADE OR PERMITTED BY THE OWNER WITHOUT ISSUING A CHANGE ORDER.

ABBREVIATIONS

APPROXIMATE

CEILING

CONCRETE

DRAWING

FI FCTRICAL

ELEVATION

EQUIPMENT

FXISTING

EXTERIOR

GAUGE GALVANIZED

GROUND

MUMIXAM

MINIMUM

MECHANICAL

MICROWAVE DISH

MANUFACTURER

NOT IN CONTRACT

PERSONAL COMMUNICATION SYSTEM

POWER PROTECTION CARINET

UNLESS OTHERWISE NOTED WELDED WIRE FABRIC

NOT TO SCALE

ON CENTER

OPPOSITE

PROPOSED

SHFFT

STEEL

SQUARE FOOT

STAINLESS STEEL

TOP OF CONCRETE

TOP OF MASONRY

VERIEV IN FIELD

MASTER GROUND BAR

LONG

FINISHED FLOOR

EQUIPMENT GROUND BAR

GENERAL CONTRACTOR

EACH

CONTINUOUS

ABOVE GROUND LINE

BASE TRANSMISSION STATION

verizon^v

PLANS PREPARED FOR

PLANS PREPARED BY

180 WASHINGTON VALLEY ROAD BEDMINSTER, NJ 07921

FROM ZERO TO INFINIGY


the solutions are endless

1490 W. 121st, Ave., Sulte 101 Westminster, CO 80234 Office # (303) 219-1178 Fax # (303) 242-8636 JOB NUMBER: TBD

- MLA PARTNER: -



- ENGINEERING LICENSE: -



DRAWING NOTICE:

THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF VERIZON AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF VERIZON

DESCRIPTION	DATE	BY	RE
SSUED FOR REVIEW	11/5/18	SKÐ	Α

DURHAM CT

- CROWN CASTLE SITE NAME: -HRT 106(B) 943202

CROWN CASTLE BU #: •

SITE ADDRESS:


101 OLD BLUE HILL ROAD DURHAM, CT 06422


806346

- SHEET DESCRIPTION: -

VERIZON SPECIFICATIONS

SHEET NUMBER:





GRAPHIC SCALE





SCALE: 11"x17" SHEET 1"= 4'

SCALE: AS NOTED

180 WASHINGTON VALLEY ROAD BEDMINSTER, NJ 07921

FROM ZERO TO INFINIGY

the solutions are endless

1490 W. 121st, Ave., Sulte 101 Westminster, CO 80234 Office # (303) 219-1178 Fax # (303) 242-8636 JOB NUMBER: TED



ENGINEERING LICENSE: =



THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF VERIZON AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF VERIZON.

REVISIONS: DESCRIPTION	DATE	BV	REV
DESCRIPTION	DATE	Bi	INCV
	-1		
SSUED FOR REVIEW	11/5/18	SKB	A

VERIZON SITE NAME: -

DURHAM CT

- CROWN CASTLE SITE NAME: -

HRT 106(B) 943202

CROWN CASTLE BU #: -

806346

SITE ADDRESS:

101 OLD BLUE HILL ROAD DURHAM, CT 06422


SHEET DESCRIPTION:


ENLARGED SITE PLAN

- SHEET NUMBER: -

A-2

INFORMATION CONTAINED WITHIN DRAWINGS IS BASED ON PROVIDED INFORMATION AND IS NOT THE RESULT OF A FIELD SURVEY. CONTRACTOR TO VERIFY EXISTING FIELD CONDITIONS PRIOR TO ANY CONSTRUCTION





NOTE:
CONTRACTOR TO VERIFY EQUIPMENT &
MOUNTING HARDWARE DOES NOT TRAP
OR INTERFERE WITH SAFETY CLIMB

EXISTING VERIZON PANEL INFINIGY ENGINEERING HAS NOT EVALUATED THE ANTENNAS TO REMAIN (TYP, OF (4) TOWER OR MOUNT FOR THIS SITE AND ASSUMES NO RESPONSIBILITY FOR ITS STRUCTURAL PER SECTOR, (3) SECTORS TOTAL) -INTEGRITY, REFER TO STRUCTURAL ANALYSIS BY EXISTING VERIZON RRH TO OTHERS PRIOR TO ANY CONSTRUCTION. REMAIN (TYP, OF (3) PER THE CONFIGURATION PLAN IS BASED ON PROVIDED INFORMATION AND IS FOR CONCEPTUAL PURPOSES ONLY. SECTOR, (3) SECTORS TOTAL)-PROPOSED VERIZON DIPLEXER, RFS P/N: FDJ85020Q4-S1 MOUNTED (AZ=30')CONTRACTOR TO VERIFY FIELD BELOW NEW RRH (TYP. OF (1) PER ALPHA SECTOR CONDITIONS PRIOR TO CONSTRUCTION. SECTOR, (3) SECTORS TOTAL)-PROPOSED VERIZON RRH, NOKIA P/N: AHCA AIRSCALE RRH 4T4R 85 MOUNTED BEHIND EXISTING PANEL ANTENNA (TYP. OF (1) PER SECTOR, (3) SECTORS TOTAL)-(AZ=290°) GAMMA SECTOR EXISTING VERIZON COVP MOUNTED ON EXISTING (AZ=170°) TOWER (TYP. OF (2) TOTAL) **EXISTING** MONOPOLE TOWER

ENGINEERING LICENSE: =

MLA PARTNER:

I ANS PREPARED FOR:

verizon^v

180 WASHINGTON VALLEY ROAD BEDMINSTER, NJ 07921

FROM ZERO TO INFINIGY

1490 W. 121st. Ave., Sulle 101 Westminster, CO 80234 Office # (303) 219-1178 Fax # (303) 242-8636

JOB NUMBER: TBD

the solutions are endless

NORTH = 0°

NO SCALE

THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF VERIZON AND MAY NOT BE REPRODUCED, DISSEMINATED WRITTEN CONSENT OF VERIZON.

REVISIONS: DESCRIPTION	DATE	BY	REV
SSUED FOR REVIEW	11/5/18	SKB	A

VERIZON SITE NAME:

DURHAM CT

- CROWN CASTLE SITE NAME: -

HRT 106(B) 943202

CROWN CASTLE BU #: *

806346

- SITE ADDRESS:

101 OLD BLUE HILL ROAD DURHAM, CT 06422

- SHEET DESCRIPTION: -

ANTENNA LAYOUT & LOADING CHART

NORTH = 0*

EXISTING ANTENNA LAYOUT

NO SCALE


PROPOSED ANTENNA LAYOUT

SITE LOADING CHART

2

DOWNTILT FEED LINE TYPE/LENGTH SECTOR QTY. QTY. ANTENNA MODEL # VENDOR AZIMUTH RAD CENTER POSITION TECHNOLOGY SECTOR COLOR (REMOVED) (NEW) (QTY/MODEL) MECHANICAL ELECTRICAL (FEET + 20%)EXISTING COAX LPA-80080/6CF DB PRODUCTS ±100' AGL ALPHA A1 RED CDMA UHBA B13 RRH 4x30 (L700) UHIE B66A RRH 4x45 (AWS) 30' 0. 9. ±100' AGL (1) EXISTING HYBRID CABLE (BETA) ALPHA A2 RED L1900 SBNHH-1D65B COMMSCOPE UHFA B25 RRH 4x30 (PCS) 0. ±100' AGL HYBRID SHARED WITH ABOVE (BETA) COMMSCOPE 30° 5° A3 RED SBNHH-1D65B ALPHA L2100 ---(1) AHCA AirScale RRH 4T4R B5 (850 LTE) W/ NEW DIPLEXER 20° 0. 0" ±100' AGL EXISTING COAX DB PRODUCTS LPA-80080/6CF ALPHA Α4 RED CDMA ±100' AGL EXISTING COAX 150" 0* 0* LPA-80080/6CF DB PRODUCTS BETA B1 BLUE CDMA -----UHBA B13 RRH 4x30 (L700) UHIE B66A RRH 4x45 (AWS) (1) EXISTING HYBRID CABLE (BETA) 170° BETA В2 **BLUE** L1900 SBNHH-1D65B COMMSCOPE 0. 0. ±100' AGL UHFA B25 RRH 4x30 (PCS) HYBRID SHARED WITH ABOVE (BETA) LPA-80080/6CF DB PRODUCTS 150° 0. 0. ±100' AGL BETA **B**3 **BLUE** 850 (1) AHCA AirScale RRH 4T4R B5 (850 LTE) W/ NEW DIPLEXER 170° 0* 0, ±100' AGL EXISTING COAX BETA B4 BLUE L2100 SBNHH-1D65B COMMSCOPE 0* 0* ±100' AGL EXISTING COAX G1 WHITE LPA-80080/6CF DB PRODUCTS 270° CDMA GAMMA UHBA B13 RRH 4x30 (L700) HYBRID SHARED WITH ABOVE (BETA) UHIE B66A RRH 4x45 (AWS) 290° ±100' AGL G2 WHITE COMMSCOPE GAMMA L1900 SBNHH-1D65B ---UHFA B25 RRH 4x30 (PCS) 1. 5° ±100' AGL HYBRID SHARED WITH ABOVE (BETA) 270° LPA-80080/6CF DB PRODUCTS GAMMA G3 WHITE CDMA) AHCA AirScale RRH 4T4R B5 (850 LTE) W/ NEW DIPLEXER 290' 0. EXISTING COAX 0. ±100' AGL GAMMA G4 WHITE L2100 SBNHH-1D65B COMMSCOPE

NOTE:
CABLE LENGTHS ARE BASED ON PROVIDED INFORMATION. CONTRACTOR
TO VERIFY REQUIRED CABLE LENGTHS PRIOR TO CONSTRUCTION.




RRH

AHCA AirScale RRH 4T4R B5

WIDTH

11.8"

DEPTH



REMOTE RADIO HEAD SPECIFICATIONS

DETAIL NOT USED

32.6 LBS

NO SCALE RFS DIPLEXER


NO SCALE

3

PART NUMBER:

FDJ85020Q4-S1

6.8"x16.9"x6.3" DIMENSIONS (HxWxD):



DIPLEXER DETAIL

- PLANS PREPARED BY:



180 WASHINGTON VALLEY ROAD BEDMINSTER, NJ 07921

the solutions are endless

1490 W. 121st. Ave., Sulle 101 Westminster, CO 80234 Office # (303) 219-1178 Fax # (303) 242-8636 JOB NUMBER: TBD



ENGINEERING LICENSE: -



NO SCALE

NO SCALE

THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF VERIZON AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF VERIZON.

DESCRIPTION	DATE	BY	RE
SSUED FOR REVIEW	11/5/18	SKB	A

VERIZON SITE NAME: -

DURHAM CT

- CROWN CASTLE SITE NAME: -HRT 106(B) 943202

CROWN CASTLE BU #: -

806346

SITE ADDRESS: -


101 OLD BLUE HILL ROAD DURHAM, CT 06422


SHEET DESCRIPTION:


EQUIPMENT & MOUNTING DETAILS

- SHEET NUMBER:

A-5







TYPICAL CONNECTION OF GROUND WIRES TO GROUNDING BARS @ ANTENNAS

NO SCALE

GENERAL GROUNDING NOTES:

SURFACES SHALL BE TREATED WITH T&B KOPR-SHIELD CP8 ANTI-OXIDATION COMPOUND.

TO ENSURE PROPER BONDING, ALL CONNECTIONS SHALL BE AS FOLLOWS: - #2 BARE TINNED SOLID COPPER CONDUCTOR: EXOTHERMIC WELD TO RODS OR GROUND


NO SCALE


- LUGS AND BUS BAR (UNLESS NOTED OTHERWISE): SANDED CLEAN, COATED WITH OXIDE INHIBITOR AND BOLTED FOR MAXIMUM SURFACE CONTACT. ALL LUGS SHALL BE COPPER (NO ALUMINUM SHALL BE PERMITTED). PROVIDE LOCK WASHERS FOR ALL MECHANICAL CONNECTIONS FOR GROUND CONDUCTORS. USE STAINLESS STEEL HARDWARE THROUGHOUT.

2. ALL GROUNDING CABLE IN CONCRETE OR THROUGH WALLS SHALL BE IN 3/4" PVC CONDUIT. SEAL AROUND CONDUIT THROUGH WALLS. NO METALLIC CONDUIT SHALL BE USED FOR GROUNDING CONDUCTORS

TYPICAL EQUIPMENT GROUND CONNECTION

- 3. OWNER'S REPRESENTATIVE WILL INSPECT EXOTHERMIC WELD AND CONDUCT MEGGER TEST PRIOR TO BURIAL, MAXIMUM 5 OHMS RESISTANCE IS REQUIRED.
- CONTRACTOR TO INSTALL GROUNDING IN CLOSE PROXIMITY TO EQUIPMENT PLATFORM OR PAD.
- 5. MAKE ALL GROUND CONNECTIONS AS SHORT AND DIRECT AS POSSIBLE. AVOID SHARP BENDS. ALL BENDS SHALL BE A MINIMUM 8" RADIUS AND NO GREATER THAN 90 DEGREES.
- 6. ALL CADWELDS TO BURIED GROUND RING SHALL BE THE PARALLEL TYPE, EXCEPT FOR THE GROUND RODS WHICH SHALL BE THE TEE TYPE.
- 7. BOND SERVICE CONDUITS TO GROUND RING AS THEY CROSS. DO NOT EXOTHERMICALLY WELD TO CONDUITS.
- 8. THE CONTRACTOR SHALL NOTIFY THE CONSTRUCTION MANAGER WHEN THE GROUNDING SYSTEM IS COMPLETE. THE CONSTRUCTION MANAGER SHALL INSPECT THE GROUNDING SYSTEM PRIOR TO BACKFILLING.
- 9. THE MINIMUM SPACING BETWEEN GROUND RODS SHALL BE 10'-0" (MAX. 15'-0").
- 10. BOND CIGBE TO EXTERNAL GROUND RING WITH 2 RUNS OF #2 BARE, TINNED, SOLID COPPER CONDUCTOR IN PVC. CONNECT BAR END WITH 2 HOLE LUG, AND "CADWELD" THE OTHER END TO THE EXTERNAL GROUND ROD.
- 1. THE PREFERRED LOCATION FOR COAX GROUNDING IS AT THE BASE OF THE TOWER PRIOR TO THE COAX BEND.
- 12. BONDING OF THE GROUNDED CONDUCTOR (NEUTRAL) AND THE GROUNDING CONDUCTOR SHALL BE AT THE SERVICE DISCONNECTING MEANS. BONDING JUMPER SHALL BE INSTALLED PER N.E.C. ARTICLE 250-30.





GROUND ROD 8

ACCESS WELL \boxtimes GROUND ROD WITH ACCESS

COMPRESSION TYPE CONNECTION

EXOTHERMIC WELD TYPE CONNECTION #2/0 BTS COPPER CONDUCTOR

BURIED GROUND CABLE INDICATES CODED NOTE

ISSUED FOR REVIEW

PLANS PREPARED FOR

180 WASHINGTON VALLEY ROAD BEDMINSTER, NJ 07921

FROM ZERO TO INFINIGY

1490 W. 121st. Ave., Sulle 101 Westminster, CO 80234

Office # (303) 219-1178

JOB NUMBER: TBD

ENGINEERING LICENSE:

the solutions are endless

DURHAM CT

THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF VERIZON AND

MAY NOT BE REPRODUCED. DISSEMINATED

OR REDISTRIBUTED WITHOUT THE EXPRESS

WRITTEN CONSENT OF VERIZON.

DATE BY RE

11/5/18 SKB A

CROWN CASTLE SITE NAME: -

DESCRIPTION

HRT 106(B) 943202

806346

- SITE ADDRESS:

101 OLD BLUE HILL ROAD DURHAM, CT 06422

- SHEET DESCRIPTION: -

GROUNDING PLANS

SHEET NUMBER:

G-1

TYPICAL ANTENNA GROUNDING PLAN

NO SCALE

Date: October 10, 2018



Engineered Tower Solutions, PLLC 8120 Sheridan Blvd, Suite A-311 Westminster, CO 80003 (919) 782-2710

brandon.little@ets-pllc.com

Charles McGuirt
Crown Castle
3530 Toringdon Way, Suite 300
Charlotte, NC 28277
Charles.McGuirt@crowncastle.com

Subject: Mount Structural Analysis

Contractor Designation: Verizon Wireless Co-Locate

Carrier Site Number: 1907
Carrier Site Name: Durham CT

Crown Castle BU Number: 806364

Crown Castle Site Name: HRT 106(B) 943202

Crown Castle JDE Number:528160Crown Castle PO Number:1263868Crown Castle Application Number:457533 Rev. 0

Engineering Firm Designation: ETS Project No.: 184434.14

Site Data: 143 R Old Blue Hill Road, Durham, Middlesex County, CT 06422

Latitude: 41° 27′ 33.67" Longitude: -72° 39′ 45.83"

Structure Information: Tower Height & Type: 120.0-ft Monopole

Mount Elevation: 100.0-ft

Mount Width & Type: 12.0-ft Platform Mount

Dear Charles McGuirt,

Engineered Tower Solutions, PLLC is pleased to submit this "Mount Structural Analysis Report" to determine the structural integrity of *Verizon Wireless's* antenna mounting system with the proposed appurtenance and equipment addition on the abovementioned supporting tower structure. Analysis of the existing supporting tower structure is to be completed by others and therefore is not part of this analysis. Analysis of the antenna mounting system as a tie-off point for fall protection or rigging is not part of this document.

Based upon our analysis, we have determined the adequacy of the antenna mounting system that will support the existing and proposed loading to be for the following Load Case:

Platform Mount Sufficient Capacity

This analysis utilizes an ultimate 3-second gust wind speed of 130 mph as required by the <u>2016 Connecticut State Building Code (2012 IBC)</u>. Applicable Standard references and design criteria are listed in Section 2 – Analysis Criteria.

We at Engineered Tower Solutions, PLLC appreciate the opportunity of providing our continuing professional services to you and Crown Castle. If you have any questions or need further assistance on this or any other projects, please give us a call.

Mount structural analysis prepared by:

Bach S. Tran, El Structural Engineer I

Respectfully Submitted by:

Frederic G. Bost, PE Owner/President




TABLE OF CONTENTS

1) INTRODUCTION

2) ANALYSIS CRITERIA

Table 1 – Proposed Equipment Configuration

3) ANALYSIS PROCEDURE

Table 2 – Documents Provided 3.1) Analysis Method 3.2) Assumptions

4) ANALYSIS RESULTS

Table 3 – Mount Component Stresses vs. Capacity 4.1) Recommendations

5) APPENDIX A)

Wire Frame and Rendered Models

6) APPENDIX B)

Software Input Calculations

7) APPENDIX C)

Software Analysis Output

8) APPENDIX D)

ASCE 7 Hazards Report

1) INTRODUCTION

This mount is an existing 12.0 ft Platform mount installed at the 100.0 ft elevation of the 120.0 ft Monopole. Engineered Tower Solutions, PLLC, did not visit the site. A mapping and/or mount manufacturer drawings were not provided. Therefore, per direction of Crown Castle, photos of the tower were compared with other mounts within our database and a similar and comparable mount was used to perform this mount analysis.

2) ANALYSIS CRITERIA

Building Code: 2012 IBC TIA-222 Revision: TIA-222-H Risk Category: Ultimate Wind Speed: 130 mph **Exposure Category:** В **Topographic Factor:** 1 Ice Thickness: 1.50 in Wind Speed with Ice: 50 mph Seismic Ss: 0.179 Seismic S1: 0.062 Service Wind Speed: 30 mph Man Live Load at Mid/End-Point: 250 lb Man Live Load At Mount Pipes: 500 lb

Table 1 – Proposed Equipment Configuration

Table 1 – Prop Mount	Antenna				
Centerline (ft)	cerline Centerline of Antenna Manufacturer		Antenna Model	Mount / Modification Details	
		6	Andrew	SBNHH-1D65B	
101.0	101.0	6	Antel	LPA-80080/6CF	
	101.0	3	Nokia	AIRSCALE RRH 4T4R B5 160W	
		3	RFS/Celwave	FDJ85020Q4-S1	12.0 ft Platform
	3	Alcatel Lucent	B13 RRH4X30-4R	Mount	
	100.0	3	Alcatel Lucent	B25 RRH4X30	
	100.0	3	Alcatel Lucent	B66A RRH4X45	
		2	Raycap	RXXDC-3315-PF-48	

3) ANALYSIS PROCEDURE

Table 2 - Documents Provided

Document	Remarks	Reference	Source
Carrier Application	App # 457533 Rev. 0	08/21/2018	CCI Sites
Structural Level Drawings (Installed)	Crown Castle	08/31/2018	CCI Sites
Structural Level Drawing (Proposed)	Crown Castle	08/31/2018	CCI Sites
Structural Analysis Report	Jacobs Engineering Group. Inc.	7813699	CCI Sites

3.1) Analysis Method

RISA-3D (version 17.0), a commercially available analysis software package, was used to create a three-dimensional model of the tower and calculate member stresses for various loading cases. Selected output from the analysis is included in Appendix C.

3.2) Assumptions

- 1) Engineered Tower Solutions, PLLC, did not visit the site. A mapping and/or mount manufacturer drawings were not provided. Therefore, per direction of Crown Castle, photos of the tower were compared with other mounts within our database and a similar and comparable mount was used to perform this mount analysis
- 2) The antenna mounting system was properly fabricated, installed and maintained in good condition in accordance with its original design and manufacturer's specification.
- 3) The configuration of antennas, mounts and other appurtenances are as specified in Tables 1 and 2 and the referenced drawings.
- 4) All member connections are assumed to have been designed to meet or exceed the load carrying capacity of the connected member unless otherwise specified in this report.
- 5) This Structural Analysis is not a condition assessment of the mount and is an evaluation of the theoretical structural capacity.
- 6) This analysis is based from the information supplied, and therefore, this report's results are as accurate as the supplied data.
- 7) Engineered Tower Solutions, PLLC makes no warranties, expressed and/or implied, in connection with this report, and disclaims any liability associated with material, fabrication, or erection of the mount. Engineered Tower Solutions, PLLC will not be held responsible from any consequential or incidental damages sustained by any person, firm, or organization as a result of the contents of this report. The maximum liability of Engineered Tower Solutions, PLLC pursuant to this report will be limited to the total fee received for compilation of this report.
- 8) It is the tower owner's responsibility to verify that the mount modeled and analyzed is the correct structure modeled.
- 9) The use of this report shall be limited to the purpose for which it was commissioned and may not be used for any other purposes without the written consent of Engineered Tower Solutions, PLLC.
- 10) Member connections are assumed to have been designed to meet or exceed the theoretical capacity of the connected member.
- 11) Steel grades have been assumed as follows:

a)	Channel, Solid Round, Angle, Plate	ASTM A36 (Gr 36)
b)	HSS (Rectangular)	ASTM 500 (Gr B-46)
c)	HSS (Round)	ASTM 500 (Gr B-42)
d)	Pipe	ASTM A53 (Gr 35)
e)	Connection Bolts	ASTM A325
f)	U-Bolts	SAE 429 Gr.2

This analysis may be affected if any assumptions are not valid or have been made in error. Engineered Tower Solutions, PLLC should be notified to determine the effect on the structural integrity of the tower.

4) ANALYSIS RESULTS

Table 3 – Mount Component Stresses vs. Capacity

Mount Centerline (ft) Component Face Mount – Horizontal		% Capacity	Pass/Fail	Notes
		31.2	PASS	1
100.0	Handrail – Horizontal	53.0	PASS	1
100.0	Mount Pipe – Vertical	56.7	PASS	1
	Sidearm – Horizontal	78.3	PASS	1
	Brace - Horizontal	14.9	PASS	1

Notes:

1) See additional documentation in "Appendix C – Software Analysis Output" for calculations supporting the % capacity consumed.

Rating (max from all components) = 78.3%	Tower Mount Rating (max from all components) = 78.3%
--	--

Verizon Mount Classification	M300R(300)-4[6]
Verizon Mount Classification	M300R(300)-4[6]

4.1) Recommendations

The tower mount has sufficient capacity to carry the existing and proposed load configuration. No modifications are required at this time.

Site Name: DURHAM, CT
Cumulative Power Density

Operator	Operating Frequency	Number of Trans.	ERP Per Trans.	Total ERP	Distance to Target	Calculated Power Density	Maximum Permissable Exposure*	Fraction of MPE
	(MHz)		(watts)	(watts)	(feet)	(mW/cm^2)	(mW/cm^2)	(%)
VZW 700	746	1	1074	1074	100	0.0386	0.4973	7.77%
VZW Cellular	876	3	370	1110	100	0.0399	0.5840	6.84%
VZW 850 LTE	869	1	1059	1059	100	0.0381	0.5793	6.57%
VZW PCS	1970	1	2456	2456	100	0.0883	1.0000	8.83%
VZW AWS	2145	1	3518	3518	100	0.1265	1.0000	12.65%

Total Percentage of Maximum Permissible Exposure

42.66%

MHz = Megahertz mW/cm^2 = milliwatts per square centimeter ERP = Effective Radiated Power

Absolute worst case maximum values used.

^{*}Guidelines adopted by the FCC on August 1, 1996, 47 CFR Part 1 based on NCRP Report 86, 1986 and generally on ANSI/IEEE C95.1-1992

Date: September 11, 2018

Heather Simeone Crown Castle 3530 Toringdon Way, Suite 300 Charlotte, NC 28277 Jacobs Engineering Group. Inc. 5449 Bells Ferry Road Acworth, GA 30102 770-701-2500

Subject: Structural Analysis Report

Carrier Designation: Verizon Wireless Co-Locate

Carrier Site Number: 1907

Carrier Site Name: Durham CT

Crown Castle Designation: Crown Castle BU Number: 806364

Crown Castle Site Name: HRT 106(B) 943202

Crown Castle JDE Job Number: 528160 Crown Castle Work Order Number: 1626719 Crown Castle Application Number: 457533 Rev. 0

Engineering Firm Designation: Jacobs Engineering Group, Inc. Project Number: 1626719

Site Data: 143 R Old Blue Hill Road, DURHAM, Middlesex County, CT

Latitude 41° 27′ 33.67″, Longitude -72° 39′ 45.83″

120 Foot - Monopole Tower

Dear Heather Simeone,

Jacobs Engineering Group, Inc. is pleased to submit this "Structural Analysis Report" to determine the structural integrity of the above mentioned tower.

The purpose of the analysis is to determine acceptability of the tower stress level. Based on our analysis we have determined the tower stress level for the structure and foundation, under the following load case, to be:

LC7: Proposed Equipment Configuration

Sufficient Capacity

The analysis has been performed in accordance with the TIA-222-H Standard. This analysis utilizes an ultimate 3-second gust wind speed of 130 mph as required by the 2016 Connecticut State Building Code. Exposure Category B and Risk Category II were used in this analysis.

Structural analysis prepared by:

Don Martin Serrano Structural Engineer

Respectfully submitted by:

Paul L. Mucci P.E. Senior Project Engineer



TABLE OF CONTENTS

1) INTRODUCTION

2) ANALYSIS CRITERIA

Table 1 - Proposed Equipment Configuration Table 2 - Other Considered Equipment

3) ANALYSIS PROCEDURE

Table 3 - Documents Provided 3.1) Analysis Method 3.2) Assumptions

4) ANALYSIS RESULTS

Table 4 - Section Capacity (Summary)
Table 5 - Tower Component Stresses vs. Capacity
4.1) Recommendations

5) APPENDIX A

tnxTower Output

6) APPENDIX B

Base Level Drawing

7) APPENDIX C

Additional Calculations

1) INTRODUCTION

This tower is a 120 ft Monopole tower designed by Valmont.

2) ANALYSIS CRITERIA

Building Code: 2012 IBC **TIA-222 Revision:** TIA-222-H

Risk Category:

Wind Speed: 130 mph

Exposure Category:
Topographic Factor:
Ice Thickness:
Wind Speed with Ice:
Service Wind Speed:

B
1.5 in
50 mph
60 mph

Table 1 - Proposed Equipment Configuration

Mounting Level (ft)	Center Line Elevation (ft)	Number of Antennas	Antenna Manufacturer	Antenna Model	Number of Feed Lines	Feed Line Size (in)
		6	andrew	SBNHH-1D65B w/ Mount Pipe		
	101.0	6	antel	LPA-80080/6CF w/ Mount Pipe		7/8 1-5/8
		3	nokia	AIRSCALE RRH 4T4R B5 160W	12	
100.0		3	rfs celwave	FDJ85020Q4-S1	2	
		3	alcatel lucent	B13 RRH4X30-4R		
	100.0	3	alcatel lucent	B25 RRH4X30		
		3	alcatel lucent	B66A RRH4X45		
		2	raycap	RXXDC-3315-PF-48		
		1	tower mounts	Platform Mount [LP 713-1]		

Table 2 - Other Considered Equipment

data 1 out of the contract of Equipment							
Mounting Level (ft)	Center Line Elevation (ft)	Number of Antennas	Antenna Manufacturer	Antenna Model	Number of Feed Lines		
	125.0	1	decibel	DB809MT3-XT			
	123.0	1	decibel	DB201-A			
119.0	119.0	1	tower mounts	Side Arm Mount [SO 102-3]	2	7/8	
	119.0	2	tower mounts	Side Arm Mount [SO 701-			

Mounting Level (ft)	Center Line Elevation (ft)	Number of Antennas	Antenna Manufacturer	Antenna Model	Number of Feed Lines	Feed Line Size (in)
		9	andrew	w SBNHH-1D65A w/ Mount Pipe		
	4400	1	tower mounts	Platform Mount [LP 602-1]		
	116.0	3	ericsson	RRUS 11	2	3/8
116.0		3	ericsson	RRUS 32 B2	4	3/4
		3	ericsson	RRUS 32	12	7/8
		3	ericsson	RRUS 32 B2		
	110.0	1	raycap	DC6-48-60-18-8C		
		1	raycap	DC6-48-60-18-8F		
107.0	107.0	1	tower mounts	Pipe Mount [PM 601-1]	1	7/8
107.0	107.0	1	gabriel electronics	GLF6-450	I	1/0
		3	alcatel lucent	PCS 1900MHZ 4X45W- 65MHZ		
	89.0	6	alcatel lucent	RRH2X50-800		
		3	alcatel lucent	TD-RRH8X20-25		4.4/4
87.0		3	commscope	NNVV-65B-R4 w/ Mount Pipe	3	1-1/4 7/8
		3	rfs celwave	APXVTM14-ALU-I20 w/ Mount Pipe		
87.0		1	tower mounts	Platform Mount [LP 713-1]		
79.0		1	decibel	DB636-C		
		1	commscope	SHP2-13		
	73.0	3	ericsson	AIR 21 B2A/B4P		
		3	3 ericsson AIR32 DB B66Aa B2a		1 1	7/8
73.0		3	ericsson	KRY 112 144/1	1	1/2
	7 0.0	3	ericsson	RADIO 4449	4	1-5/8
		3	rfs celwave	APXVAA24_43-U-A20		
		1	tower mounts	Platform Mount [LP 1301- 1]		
	57.0	1	rfs celwave	PD1142-1		
50.0	54.0	1	decibel	ASP-655		
	53.0	1	rfs celwave	PD1121-6	1	1/2
	50.0	2	tower mounts	Side Arm Mount [SO 702-	3	7/8
		1	decibel	DB492A		
40.0	41.0	1	tekelec systemes	EPSILON GPS ANTENNA 35 DB	1	1/2
40.0	40.0	1	tower mounts	Side Arm Mount [SO 701- 1]	1	1/2

3) ANALYSIS PROCEDURE

Table 3 - Documents Provided

Document	Remarks	Reference	Source
4-GEOTECHNICAL REPORTS	Clarence Welti Assoc., Inc.	262150	CCISITES
4-TOWER FOUNDATION DRAWINGS/DESIGN/SPECS	SAC Engineering, Inc.	297341	CCISITES
4-TOWER MANUFACTURER DRAWINGS	Valmont	262153	CCISITES
4-TOWER STRUCTURAL ANALYSIS REPORTS	Valmont	942187	CCISITES

3.1) Analysis Method

tnxTower (version 8.0.4.0), a commercially available analysis software package, was used to create a three-dimensional model of the tower and calculate member stresses for various loading cases. Selected output from the analysis is included in Appendix A.

3.2) Assumptions

- 1) Tower and structures were built and maintained in accordance with the manufacturer's specifications.
- 2) The configuration of antennas, transmission cables, mounts and other appurtenances are as specified in Tables 1 and 2 and the referenced drawings.
- 3) The baseplate grout was not considered in this analysis.

This analysis may be affected if any assumptions are not valid or have been made in error. Jacobs Engineering Group, Inc. should be notified to determine the effect on the structural integrity of the tower.

4) ANALYSIS RESULTS

Table 4 - Section Capacity (Summary)

Section No.	Elevation (ft)	Component Type	Size	Critical Element	P (K)	SF*P_allow (K)	% Capacity	Pass / Fail
L1	120 - 100	Pole	TP20.263x15.403x0.1875	1	-4.12	813.65	32.2	Pass
L2	100 - 47.0833	Pole	TP33.13x20.263x0.2813	2	-20.92	1883.04	94.5	Pass
L3	47.0833 - 0	Pole	TP44x31.372x0.375	3	-34.68	3407.81	88.3	Pass
							Summary	
						Pole (L2)	94.5	Pass
						Rating =	94.5	Pass

Table 5 - Tower Component Stresses vs. Capacity - LC7

Notes	Component	Elevation (ft)	% Capacity	Pass / Fail
1	Anchor Rods	0	84.5	Pass
1	Base Plate	0	43.9	Pass
	Flange Bolts	100	46.8	Pass
1	Top Flange Plate		14.1	Pass
	Bottom Flange Plate		14.1	Pass
1	Base Foundation Structural	0	9.5	Pass
1	Base Foundation Soil Interaction	0	38.9	Pass

Structure Rating (max from all components) =	94.5%
--	-------

Notes:

4.1) Recommendations

The tower and its foundation have sufficient capacity to carry the proposed load configuration. No modifications are required at this time.

¹⁾ See additional documentation in "Appendix C - Additional Calculations" for calculations supporting the % capacity consumed.



December 7,2018

Dear Customer:

The following is the proof-of-delivery for tracking number 773898434862.

Delivery Information:

Status: Signed for by: Delivered

K.GARVIS

Delivered to:

Receptionist/Front Desk

Delivery location:

30 TOWN HOUSE RD DURHAM, CT 06422

Service type: Special Handling: FedEx Priority Overnight

Deliver Weekday

Delivery date:

Dec 7, 2018 10:09



Shipping Information:

Tracking number:

773898434862

Ship date: Weight: Dec 6, 2018

0.5 lbs/0.2 kg

Recipient:

Laura Francis Town of Durham 30 Town House Rd. DURHAM, CT 06422 US

Reference

Shipper:

Kristian McKay 3530 Toringdon Way

STE 300

CHARLOTTE, NC 28277 US

1766.6680

Thank you for choosing FedEx.



December 7,2018

Dear Customer:

The following is the proof-of-delivery for tracking number 773898474064.

Delivery Information:

Status:

Delivered

Delivered to:

Residence

Signed for by:

Signature not required

Delivery location:

109 OLD BLUE HILLS RD

DURHAM, CT 06422

Service type:

FedEx Priority Overnight

Delivery date:

Dec 7, 2018 10:20

Special Handling:

Deliver Weekday

Residential Delivery

NO SIGNATURE REQUIRED

Proof-of-delivery details appear below; however, no signature is available for this FedEx Express shipment because a signature was not required.

Shipping Information:

Tracking number:

773898474064

Ship date:

Dec 6, 2018

Weight:

0.5 lbs/0.2 kg

Recipient:

Francis E. Behrens 109 Old Blue Hills Rd.

DURHAM, CT 06422 US

Reference

Shipper:

Kristian McKay

3530 Toringdon Way

STE 300

CHARLOTTE, NC 28277 US

1766.6680

Thank you for choosing FedEx.



December 7,2018

Dear Customer:

The following is the proof-of-delivery for tracking number 773898449898.

Delivery Information:

Status:

Delivered

Signed for by:

K.GARVIS

Delivered to:

Delivery location:

Receptionist/Front Desk

30 TOWN HOUSE RD

DURHAM, CT 06422

Service type:

Special Handling:

FedEx Priority Overnight

Deliver Weekday

Delivery date:

Dec 7, 2018 10:09



Shipping Information:

Tracking number:

773898449898

Ship date:

Dec 6, 2018

Weight:

0.5 lbs/0.2 kg

Recipient:

Geoffrey Colegrove Town of Durham 30 Town House Rd. DURHAM, CT 06422 US

Reference

Shipper:

Kristian McKay 3530 Toringdon Way

STE 300

CHARLOTTE, NC 28277 US

1766.6680

Thank you for choosing FedEx.