

KENNETH C. BALDWIN

280 Trumbull Street
Hartford, CT 06103-3597
Main (860) 275-8200
Fax (860) 275-8299
kbaldwin@rc.com
Direct (860) 275-8345

Also admitted in Massachusetts
and New York

August 16, 2021

Via Electronic Mail

Melanie A. Bachman, Esq.
Executive Director/Staff Attorney
Connecticut Siting Council
10 Franklin Square
New Britain, CT 06051

Re: **Notice of Exempt Modification – Facility Modification
50 Plantation Road, East Windsor, Connecticut**

Dear Attorney Bachman:

Cellco Partnership d/b/a Verizon Wireless (“Cellco”) currently maintains an existing wireless telecommunications facility at the above-referenced property address (the “Property”). The facility consists of antennas and remote radio heads attached to a water tower and related equipment on the ground, near the base of the water tower. The existing 132.5-foot tower was constructed in 1947 and, according to information presented in TS-CING-047-060405, was first used for telecommunications purposes by Sprint in 1996. On April 12, 2006, the Council, exercising jurisdiction over the existing tower, approved the tower share application filed by New Cingular Wireless PCS, LLC (“Cingular”) (TS-CING-047-060405). A copy of the Council’s approval of the Cingular tower share application is included in Attachment 1. AT&T; Sprint; T-Mobile, Metro PCS and Clearwire currently maintain antennas at various heights on the water tower and maintain radio equipment inside a fenced facility compound near the base of the tower. Cellco’s shared use of the tower was approved by the Council in September of 2020 (TS-VER-047-200827). Copies of the above-referenced approvals are included in Attachment 1.

Cellco now intends to modify its facility by replacing nine (9) existing antennas with three (3) Samsung MT6407-77A antennas; three (3) NHHSS-65B-R2B antennas; and three (3) NHH-65B-R2B antennas and installing three (3) remote radio heads (“RRHs”) all at the same heights on the water tower. A set of project plans showing Cellco’s proposed facility modifications and specifications for Cellco’s new antennas and RRHs are included in

Melanie A. Bachman, Esq.

August 16, 2021

Page 2

Attachment 2. Please note that Cellco refers to its facility as its South Windsor North CT facility.

Please accept this letter as notification pursuant to R.C.S.A. § 16-50j-73, for construction that constitutes an exempt modification pursuant to R.C.S.A. § 16-50j-72(b)(2). In accordance with R.C.S.A. § 16-50j-73, a copy of this letter is being sent to East Windsor's Chief Elected Official and Land Use Officer.

The planned modifications to the facility fall squarely within those activities explicitly provided for in R.C.S.A. § 16-50j-72(b)(2).

1. The proposed modifications will not result in an increase in the height of the existing tower. Cellco's replacement antennas will be installed on its existing antenna mounting structure.

2. The proposed modifications will not involve any change to ground-mounted equipment and, therefore, will not require the extension of the site boundary.

3. The proposed modifications will not increase noise levels at the facility by six decibels or more, or to levels that exceed state and local criteria.

4. The installation of Cellco's new antennas will not increase radio frequency (RF) emissions at the facility to a level at or above the Federal Communications Commission (FCC) safety standard. A cumulative general power density table for Cellco's modified facility is included in Attachment 3. The modified facility will be capable of providing Cellco's 5G wireless service.

5. The proposed modifications will not cause a change or alteration in the physical or environmental characteristics of the site.

6. According to the attached Structural Analysis ("SA") and Mount Analysis ("MA"), the existing water tower, its foundation and antenna mounts can support Cellco's proposed modifications. Copies of the SA and MA are included in Attachment 4.

A copy of the parcel map and Property owner information is included in Attachment 5. A Certificate of Mailing verifying that this filing was sent to municipal officials and the property owner is included in Attachment 6.

Melanie A. Bachman, Esq.

August 16, 2021

Page 3

For the foregoing reasons, Cellco respectfully submits that the proposed modifications to the above-referenced telecommunications facility constitutes an exempt modification under R.C.S.A. § 16-50j-72(b)(2).

Sincerely,



A handwritten signature in black ink, appearing to read "Kenneth C. Baldwin".


Kenneth C. Baldwin

Enclosures

Copy to:

Jason E. Bowsza, First Selectman
Mike D'Amato, Acting Town Planner
Plantation Properties, LLC, Property Owner
Alex Tyurin

ATTACHMENT 1



STATE OF CONNECTICUT

CONNECTICUT SITING COUNCIL

Ten Franklin Square, New Britain, CT 06051

Phone: (860) 827-2935 Fax: (860) 827-2950

E-Mail: siting.council@po.state.ct.us

www.ct.gov/csc

April 13, 2006

Steven L. Levine
Real Estate Consultant
New Cingular Wireless PCS, LLC
500 Enterprise Drive
Rocky Hill, CT 06067-3900

RE: **TS-CING-047-060405** - New Cingular Wireless PCS, LLC request for an order to approve tower sharing at an existing telecommunications facility located at 50 Plantation Road, East Windsor, Connecticut.

Dear Mr. Levine:

At a public meeting held April 12, 2006, the Connecticut Siting Council (Council) ruled that the shared use of this existing tower site is technically, legally, environmentally, and economically feasible and meets public safety concerns, and therefore, in compliance with General Statutes § 16-50aa, the Council has ordered the shared use of this facility to avoid the unnecessary proliferation of tower structures. This facility has also been carefully modeled to ensure that radio frequency emissions are conservatively below State and federal standards applicable to the frequencies now used on this tower.

This decision is under the exclusive jurisdiction of the Council. Any additional change to this facility may require an explicit request to this agency pursuant to General Statutes § 16-50aa or notice pursuant to Regulations of Connecticut State Agencies Section 16-50j-73, as applicable. Such request or notice shall include all relevant information regarding the proposed change with cumulative worst-case modeling of radio frequency exposure at the closest point of uncontrolled access to the tower base, consistent with Federal Communications Commission, Office of Engineering and Technology, Bulletin 65. Any deviation from this format may result in the Council implementing enforcement proceedings pursuant to General Statutes § 16-50u including, without limitation, imposition of expenses resulting from such failure and of civil penalties in an amount not less than one thousand dollars per day for each day of construction or operation in material violation.

This decision applies only to this request for tower sharing and is not applicable to any other request or construction. Please be advised that the validity of this action shall expire one year from the date of this letter.

The proposed shared use is to be implemented as specified in your letter dated April 4, 2006, including the placement of all necessary equipment and shelters within the tower compound.

Thank you for your attention and cooperation.

Very truly yours,


Pamela B. Katz, P.E.

Chairman

PBK/laf

c: The Honorable Linda L. Roberts, First Selectman, Town of East Windsor
Laurie Whitten, Town Planner, Town of East Windsor
Thomas J Regan, Esq., Brown Rudnick Berlack Israels LLP
Christopher B. Fisher, Esq., Cuddy & Feder LLP



STATE OF CONNECTICUT

CONNECTICUT SITING COUNCIL

Ten Franklin Square, New Britain, CT 06051

Phone: (860) 827-2935 Fax: (860) 827-2950

E-Mail: siting.council@ct.gov

Web Site: portal.ct.gov/csc

September 25, 2020

Kenneth C. Baldwin, Esq.
Robinson & Cole LLP
280 Trumbull Street
Hartford, CT 06103-3597

RE: **TS-VER-047-200827** - Cellco Partnership d/b/a Verizon Wireless request for an order to approve tower sharing at an existing telecommunications facility located at 50 Plantation Road, East Windsor, Connecticut.

Dear Attorney Baldwin:

At a public meeting held on September 24, 2020, the Connecticut Siting Council (Council) ruled that the shared use of this existing tower site is technically, legally, environmentally, and economically feasible and meets public safety concerns, and therefore, in compliance with General Statutes § 16-50aa, the Council has ordered the shared use of this facility to avoid the unnecessary proliferation of tower structures with the following conditions:

1. Approval of any changes be delegated to Council staff;
2. Prior to Verizon's antenna installation, the tower modifications shall be installed in accordance with the Structural Analysis prepared by All Points Technology Corporation, dated July 9, 2020 and signed and stamped by Michael S. Trodden;
3. Within 45 days following completion of equipment installation, Verizon shall provide documentation certified by a Professional Engineer that its installation complied with the recommendations of the Structural Analysis;
4. Any deviation from the proposed installation as specified in the original tower share request and supporting materials with the Council shall render this decision invalid;
5. Any material changes to the proposed installation as specified in the original tower share request and supporting materials filed with the Council shall require an explicit request for modification to the Council pursuant to Connecticut General Statutes § 16-50aa, including all relevant information regarding the proposed change with cumulative worst-case modeling of radio frequency exposure at the closest point of uncontrolled access to the tower base, consistent with Federal Communications Commission, Office of Engineering and Technology, Bulletin 65;
6. Not less than 45 days after completion of the proposed installation, the Council shall be notified in writing that the installation has been completed;
7. Any nonfunctioning antenna and associated antenna mounting equipment on this facility owned and operated by Verizon shall be removed within 60 days of the date the antenna ceased to function;
8. The validity of this action shall expire one year from the date of this letter; and

9. The applicant may file a request for an extension of time beyond the one year deadline provided that such request is submitted to the Council not less than 60 days prior to the expiration.

This decision is under the exclusive jurisdiction of the Council and applies only to this request for tower sharing dated August 27, 2020. This facility has been carefully modeled to ensure that radio frequency emissions are conservatively below State and federal standards applicable to the frequencies now used on this tower. Any deviation from the approved tower sharing request is enforceable under the provisions of Connecticut General Statutes § 16-50u.

The proposed shared use is to be implemented as specified in your letter dated August 27, 2020, including the placement of all necessary equipment and shelters within the tower compound.

Please be advised that the validity of this action shall expire one year from the date of this letter.

Thank you for your attention and cooperation.

Sincerely,

s/ Melanie A. Bachman

Melanie Bachman
Executive Director

MAB/IN/emr

c: The Honorable Jason E. Bowsza, First Selectman, Town of East Windsor
jbowsza@eastwindsorct.com)

ATTACHMENT 2

verizon[®]

WIRELESS SERVICES FACILITY

SOUTH WINDSOR NORTH CT 50 PLANTATION ROAD EAST WINDSOR, CT 06016

DRAWING INDEX

T-1 TITLE SHEET

C-1 COMPOUND PLAN, TANK ELEVATION, EQUIPMENT
CONFIGURATION PLANS & ELEVATION.

B-1 RF BILL OF MATERIALS, MECHANICAL SPECIFICATIONS &
EQUIPMENT DETAILS.

N-1 NOTES & SPECIFICATIONS

SITE DIRECTIONS

START: 20 ALEXANDER DRIVE
WALLINGFORD, CONNECTICUT 06492

END: 50 PLANTATION ROAD
EAST WINDSOR, CT 06016

1. FROM ALEXANDER DRIVE TURN RIGHT ONTO BARNES INDUSTRIAL RD S. 0.3 MI
2. TURN LEFT AT THE 1ST CROSS STREET ONTO CT-68W 0.4 MI
3. TURN RIGHT 0.2 MI
4. TURN RIGHT ONTO N COLONY RD 0.3 MI
5. TURN RIGHT TO MERGE ONTO CT-15 TOWARD HARTFORD 0.3 MI
6. MERGE ONTO CT-15 0.3 MI
7. TAKE EXIT 69N E TO MERGE ONTO I-91N 18.3 MI
8. CONTINUE STRAIGHT TO STAY ON I-91N 0.8 MI
9. TAKE EXIT 35A-35B FOR INTERSTATE 291 TOWARD MANCHESTER 0.7 MI
10. MERGE ONTO I-291 E 2.2 MI
11. TAKE EXIT 4 FOR US-5 N TOWARD SOUTH WINDSOR 0.4 MI
12. USE THE LEFT 2 LANES TO TURN LEFT ONTO US-5N 3.9 MI
13. TURN LEFT ONTO CT-194E 0.3 MI
14. TURN LEFT ONTO RYE STREET 2.2 MI
15. TURN RIGHT ONTO PLANTATION RD (DESTINATION ON THE RIGHT) 0.5 MI



SITE INFORMATION

VZ SITE NAME: SOUTH WINDSOR NORTH CT

VZ PROJ FILING ID: 16560063

VZ LOCATION CODE: 469756

VZ PROJECT CODE: 20171645681

LOCATION: 50 PLANTATION ROAD

EAST WINDSOR, CT 06016

PROJECT SCOPE: REFER TO NOTES ON DRAWING C-1 FOR SCOPE OF WORK.

MAP/BLOCK/LOT: 01650/001C

ZONING DISTRICT: "A-1" (AGRICULTURAL/RESIDENTIAL)

LATITUDE: 41° 52' 32.328" N (41.87564654° N)

LONGITUDE: 72° 33' 53.232" W (72.56478672° W)

GROUND ELEVATION: 159.8± AMSL

PROPERTY OWNER: PLANTATION PROPERTIES, LLC
P.O. BOX 542
BROAD BROOK, CT 06106-0542

APPLICANT: CELL CO PARTNERSHIP
a/k/a VERIZON WIRELESS
20 ALEXANDER DRIVE
WALLINGFORD, CT 06492

LEGAL/REGULATORY COUNSEL: ROBINSON & COLE, LLP
KENNETH C. BALDWIN, ESQ.
280 TRUMBULL STREET
HARTFORD, CT 06108

ENGINEER CONTACT: ALL-POINTS TECHNOLOGY CORP., P.C.
567 VAUXHALL STREET EXTENSION - SUITE 311
WATERFORD, CT 06385
(860) 663-1697

VERIZON SMART TOOL PROJECT #: XXXXXXXX

NEW BUILD CONSTRUCTION DRAWING REFERENCE:
THE PROPOSED L-SUB CARRIER ADD EQUIP. SHOWN
HEREIN SUPERSEDES THE EQUIPMENT INDICATED
WITHIN THE NEW BUILD CONSTRUCTION DRAWINGS
PREPARED BY ALL-POINTS TECHNOLOGY
CORPORATION, P.C. MARKED REV1 DATED 11/06/20.
REFER TO NEW BUILD CONSTRUCTION DRAWINGS FOR
ADDITIONAL INFORMATION NOT SHOWN HEREIN.

Cellco Partnership d/b/a

verizon[®]


20 ALEXANDER DRIVE
WALLINGFORD, CT 06492

ALL-POINTS
TECHNOLOGY CORPORATION

567 VAUXHALL STREET EXTENSION - SUITE 311
WATERFORD, CT 06385
PHONE: (860) 663-1697
WWW.ALL-POINTSTECH.COM FAX: (860) 663-1698

CONSTRUCTION DOCUMENTS

NO	DATE	REVISION
0	07/07/21	FOR REVIEW: JRM
1		
2		
3		
4		
5		
6		



DESIGN PROFESSIONALS OF RECORD

PROF. MICHAEL S. TRODDEN, P.E.
COMP: ALL-POINTS TECHNOLOGY
CORPORATION
ADD: 567 VAUXHALL STREET EX-
TENSION, SUITE 311
WATERFORD, CT 06385

OWNER: PLANTATION PROPERTIES, LLC
ADDRESS: P.O. BOX 542
BROAD BROOK, CT 06106-0542



SOUTH WINDSOR NORTH CT

SITE: 50 PLANTATION ROAD
ADDRESS: EAST WINDSOR, CT 06016

APT FILING NUMBER: CT141.12500

DRAWN BY: DRA

DATE: 07/07/21

CHECKED BY: JRM

VZW PROJECT CODE: 20171645681

VZW LOCATION CODE: 469756

VZW FUZE ID: 16560063





SHEET TITLE:

TITLE SHEET
& INDEX

SHEET NUMBER:	T-1
---------------	-----



EQUIPMENT DATA									
EQUIPMENT SPECIFICATIONS									
SECTOR	ANTENNA MAKE/MODEL	QTY	AZIMUTH	EQUIPMENT STATUS	HEIGHT (IN)	WIDTH (IN)	DEPTH (IN)	WEIGHT (LBS)	
ALPHA	700/850/100/CBRS COMMSCOPE NHH-65B-R2B	1	20	NEW	72.0	11.9	7.1	51.0 ²	
	700/850/100/CBRS COMMSCOPE NHH-65B-R2B	1	20	NEW	72.0	11.9	7.1	43.7 ²	
	SAMSUNG MT6407-77A	1	20	NEW	35.7 ³	16.1 ³	5.51 ³	87.1 ³	
BETA	700/850/100/CBRS COMMSCOPE NHH-65B-R2B	1	140	NEW	72.0	11.9	7.1	51.0 ²	
	700/850/100/CBRS COMMSCOPE NHH-65B-R2B	1	140	NEW	72.0	11.9	7.1	43.7 ²	
	SAMSUNG MT6407-77A	1	140	NEW	35.7 ³	16.1 ³	5.51 ³	87.1 ³	
GAMMA	700/850/2100/CBRS COMMSCOPE NHH-65B-R2B	1	260	NEW	72.0	11.9	7.1	51.0 ²	
	700/850/2100/CBRS COMMSCOPE NHH-65B-R2B	1	260	NEW	72.0	11.9	7.1	43.7 ²	
	SAMSUNG MT6407-77A	1	260	NEW	35.7 ³	16.1 ³	5.51 ³	87.1 ³	
APPURTEINANCE MAKE/MODEL									
SAMSUNG B2/B13 RRH-BR049 (RFV01U-D1A)	3	-		NEW	14.9	14.9	10.04	97.5	
SAMSUNG B2/B13 RRH-BR049 (RFV01U-D2A)	3	-		NEW	14.9	14.9	8.14	82.0	
SAMSUNG CBRS RT4401-48 RRH	3	-		NEW	10.6	8.9	3.0	11.0	
RAYCAP RH-SDC-3315-PF-48	3	-		NEW	28.9	15.73	10.25	32.0	

(1) ETR DENOTES EXIST. TO REMAIN.
(2) WEIGHT WITHOUT MOUNTING BRACKET.
(3) ANTENNA DATA BASED ON RFDS DATED 05/06/21.
(4) EQUIPMENT CONFIGURATION INDICATED ABOVE VIEWED FROM THE BEHIND.
NOT TO EXCEED.



2 NEW ANTENNA DETAIL


B-1 SCALE: 1/2 = 1'-0"



NOTE: WEIGHTS INCLUDE SOLAR SHEILD & MOUNTING BRACKET

5 RRH EQUIPMENT DETAILS


B-1 SCALE: 1/2 = 1'-0"



SAMSUNG CBRS RT4401-48 RRH
HxWxD=10.6x8.9x3.0 (11.0 lbs)


3 NEW ANTENNA DETAIL

B-1 SCALE: 1/2 = 1'-0"



4 NEW ANTENNA DETAIL

B-1 SCALE: 1/2 = 1'-0"




OVER VOLTAGE PROTECTION BOX (OVP)

B-1 SCALE: 1/2 = 1'-0"

BILL OF MATERIALS			
	QUANTITY	LENGTH	COMMENTS
① 700/850/1900	3		(COMMSCOPE NHH-65B-R2B)
② 700/850/100/CBRS	3		(COMMSCOPE NHH-65B-R2B)
③ SAMSUNG MT6407-77A	3		
④ 1/2 JUMPER CABLE	48	15 FT	ROUTE FROM RRH TO ANTENNAS
⑤ ANTENNA LINK CABLES	6	15 M	ROUTE FROM UPPER OVP TO ANTENNAS
⑥ ANTENNA POWER CABLES	3	15 M	PROPRIETARY POWER CABLE FROM UPPER OVP TO ANTENNAS
⑦ SAMSUNG CBRS RT4401-48 RRH	3		(COORDINATE WIRING w/ VERIZON EQUIP. ENGINEER)
⑧ CPRI CABLE	6	25 FT	ROUTE FROM UPPER OVP TO RRH
⑨ 10 AWG X2 DC POWER CABLE	3	25 FT	PROPRIETARY POWER CABLE FROM UPPER OVP TO ANTENNA/RRH
⑩ 950/700 DUAL BAND RRH	3		SAMSUNG B2/B13 RRH-BR049 (RFV01U-D1A) MOUNTED TO NEW ANTENNA MOUNT
⑪ PCS/AWS DUAL BAND RRH	3		SAMSUNG B2/B13 RRH-BR049 (RFV01U-D2A) MOUNTED TO NEW ANTENNA MOUNT
⑫ RRH CABLES	6	15M	PROPRIETARY POWER & FIBER CABLES
⑬ UPPER OVP	3		(RH-SDC-3315-PF-48) MOUNTED TO NEW ANTENNA MOUNT
⑭ 6x12 LI. HYBRID CABLE (BETA/GAMMA)	2	140 FT	ROUTE FROM LOWER OVP(s) TO UPPER OVP(s)
⑮ 6x12 LI. HYBRID CABLE (ALPHA)	1	185 FT	ROUTE FROM LOWER OVP(s) TO UPPER OVP(s)

NOTES:
1. INFORMATION SHOWN HEREON IS FOR USE BY VERIZON EQUIPMENT OPERATIONS.
2. INFORMATION IS BASED ON RFDS, MARKED DATED 05/06/21.
3. * DENOTES EQUIPMENT DESIGNATED FOR LEASING ONLY (WHERE APPLICABLE).
4. INSTALL ALARM BOARDS AT ALL OVPS WHERE REQUIRED. COORDINATE w/ VERIZON WIRELESS EQUIPMENT ENGINEERING.
5. INSTALL UP-CONVERTERS LOCATED WITHIN NEW OVP RACK COORDINATE WITH VERIZON EQUIPMENT ENGINEERING.



1 TYPICAL RISER DIAGRAM

B-1 SCALE: N.I.S.


NOTE: ANTENNA CONFIGURATIONS SHOWN WITHIN PLUMBING DIAGRAM ARE VIEWED FROM BEHIND.

Celco Partnership db/a/

verizon

25 ALEXANDER DRIVE
WALLINGFORD, CT 06492

567 VAUXHALL STREET EXT.
WATCHORN, CT 06491-1681
PHONE: (860) 525-7691
WWW.ALL-POINTS.TECH.COM FAX: (860) 525-7693



DESIGN PROFESSIONALS OF RECORD
PROF. MICHAEL S. TRODDEN, P.E.
COMP. ALL-POINTS TECHNOLOGY
CORPORATION
ADD: 567 VAUXHALL STREET EXT.
WATCHORN, CT 06491
WATERBURY, CT 06385

OWNER: PLANTATION PROPERTIES, LLC
ADDRESS: P.O. BOX 542
BROAD BROOK, CT 06016-0542

SOUTH WINDSOR NORTH CT

SITE: 50 PLANTATION ROAD
ADDRESS: EAST WINDSOR, CT 06016

APT FILING NUMBER: CT141.12500

DRAWN BY: DRA
DATE: 07/07/21
CHECKED BY: JRM

VZW PROJECT CODE: 20171645681

VZW LOCATION CODE: 469756

VZW FUZE ID: 16560063

SHEET TITLE:
RF BILL OF MATERIALS,
MECHANICAL
SPECIFICATIONS &
EQUIPMENT DETAILS

SHEET NUMBER:

B-1

SAMSUNG

SAMSUNG C-Band 64T64R

Massive MIMO Radio

for High Capacity and Wide Coverage

Samsung C-Band 64T64R Massive MIMO Radio enables mobile operators to increase coverage range, boost data speeds and ultimately offer enriched 5G experiences to users in the U.S..

Model Code : MT6407-77A




Points of Differentiation

Wide Bandwidth


With capability to support up to 2 CC carrier configuration, Samsung C-Band massive MIMO Radio supports 200 MHz bandwidth in the C-Band spectrum.

Samsung C-Band massive MIMO Radio covers the entire C-Band 280 MHz spectrum, so it can meet the operator's needs in current A block and future B/C blocks



Future Proof Product

Samsung C-Band 64T64R Massive MIMO radio supports not only CPRI but also eCPRI as front-haul interface. It enables operators can cut down on OPEX/CAPEX by reducing front-haul bandwidth through low layer split and using ethernet based higher efficient line.



Enhanced Performance

C-Band massive MIMO Radio creates sharp beams and extends networks' coverage on the critical mid-band spectrum using a large number of antenna elements and high output power to boost data speeds.

This helps operators reduce their CAPEX as they now need less products to cover the same area than before.


Furthermore, as C-Band massive MIMO Radio supports MU-MIMO(Multi-user MIMO), it enables to increase user throughput by minimizing interference.



Well Matched Design

Samsung C-Band Massive MIMO radio utilizes 64 antennas, supports up to 280MHz bandwidth, and delivers a 200W output power. despite the above advanced performance, the Radio has a compact size of 50.9L and 79.4lbs. This makes it easy to install the Radio.

It is designed to look solid and compact, with a low profile appearance so that, when installed, harmonizes well with the surrounding environment..



Technical Specifications

Item	Specification
Tech	NR
Band	n77
Frequency Band	3700 - 3980 MHz
EIRP	78.5dBm (53.0 dBm+25.5 dBi)
IBW/OBW	280 MHz / 200 MHz
Installation	Pole/Wall
Size/Weight	16.06 x 35.06 x 5.51 inch (50.86L)/ 79.4 lbs

About Samsung Electronics Co., Ltd.


Samsung inspires the world and shapes the future with transformative ideas and technologies. The company is redefining the worlds of TVs, smartphones, wearable devices, tablets, digital appliances, network systems, and memory, system LSI, foundry and LED solutions.

129 Samsung-ro, Yeongtong-gu, Suwon-si Gyeonggi-do, Korea

© 2021 Samsung Electronics Co., Ltd.

All rights reserved. Information in this leaflet is proprietary to Samsung Electronics Co., Ltd. and is subject to change without notice. No information contained here may be copied, translated, transcribed or duplicated by any form without the prior written consent of Samsung Electronics.

NHH-65B-R2B



6-port sector antenna, 2x 698–896 and 4x 1695–2360 MHz, 65° HPBW, 2x RET. Both high bands share the same electrical tilt.

- Interleaved dipole technology providing for attractive, low wind load mechanical package
- Internal SBT on low and high band allow remote RET control from the radio over the RF jumper cable
- Separate RS-485 RET input/output for low and high band
- One RET for low band and one RET for both high bands to ensure same tilt level for 4x Rx or 4x MIMO

General Specifications

Antenna Type	Sector
Band	Multiband
Color	Light gray
Effective Projective Area (EPA), frontal	0.26 m ² 2.799 ft ²
Effective Projective Area (EPA), lateral	0.22 m ² 2.368 ft ²
Grounding Type	RF connector body grounded to reflector and mounting bracket
Performance Note	Outdoor usage Wind loading figures are validated by wind tunnel measurements described in white paper WP-112534-EN
Radome Material	Fiberglass, UV resistant
Radiator Material	Low loss circuit board
Reflector Material	Aluminum
RF Connector Interface	7-16 DIN Female
RF Connector Location	Bottom
RF Connector Quantity, high band	4
RF Connector Quantity, low band	2
RF Connector Quantity, total	6

Remote Electrical Tilt (RET) Information, General

RET Interface	8-pin DIN Female 8-pin DIN Male
RET Interface, quantity	2 female 2 male

Dimensions


Width	301 mm 11.85 in
Length	1828 mm 71.969 in

NHH-65B-R2B

Depth

180 mm | 7.087 in

Array Layout



Array	Freq (MHz)	Conns	RET	AISG RET UID
R1	698-896	1-2	1	ANxXXXXXXXXXXXXX1
Y1	1695-2360	3-4	2	ANxXXXXXXXXXXXXX2
Y2	1695-2360	5-6		

View from the front of the antenna

(Sizes of colored boxes are not true
depictions of array sizes)

Electrical Specifications

Impedance	50 ohm
Operating Frequency Band	1695 – 2360 MHz 698 – 896 MHz
Polarization	±45°
Total Input Power, maximum	900 W @ 50 °C

Remote Electrical Tilt (RET) Information, Electrical

Protocol	3GPP/AISG 2.0 (Single RET)
Power Consumption, idle state, maximum	2 W

NHH-65B-R2B

Power Consumption, normal conditions, maximum	13 W
Input Voltage	10–30 Vdc
Internal Bias Tee	Port 1 Port 3
Internal RET	High band (1) Low band (1)

Electrical Specifications

Frequency Band, MHz	698–806	806–896	1695–1880	1850–1990	1920–2200	2300–2360
Gain, dBi	14.9	15	17.7	17.9	18.4	18.7
Beamwidth, Horizontal, degrees	65	60	71	69	64	57
Beamwidth, Vertical, degrees	12.4	11.2	5.7	5.2	4.9	4.6
Beam Tilt, degrees	0–14	0–14	0–7	0–7	0–7	0–7
USLS (First Lobe), dB	13	14	18	18	19	18
Front-to-Back Ratio at 180°, dB	30	29	31	30	29	31
Isolation, Cross Polarization, dB	25	25	25	25	25	25
Isolation, Inter-band, dB	30	30	30	30	30	30
VSWR Return loss, dB	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0
PIM, 3rd Order, 2 x 20 W, dBc	-153	-153	-153	-153	-153	-153
Input Power per Port at 50° C, maximum, watts	300	300	300	300	300	300

Electrical Specifications, BASTA

Frequency Band, MHz	698–806	806–896	1695–1880	1850–1990	1920–2200	2300–2360
Gain by all Beam Tilts, average, dBi	14.5	14.5	17.3	17.7	18.1	18.5
Gain by all Beam Tilts Tolerance, dB	±0.6	±1.1	±0.4	±0.4	±0.5	±0.3
Gain by Beam Tilt, average, dBi	0 ° 14.4 7 ° 14.6 14 ° 14.3	0 ° 14.7 7 ° 14.7 14 ° 14.1	0 ° 17.2 4 ° 17.3 7 ° 17.3	0 ° 17.6 4 ° 17.7 7 ° 17.7	0 ° 18.0 4 ° 18.2 7 ° 18.1	0 ° 18.3 4 ° 18.5 7 ° 18.6
Beamwidth, Horizontal Tolerance, degrees	±2	±2.1	±3	±4.1	±6.5	±2.9
Beamwidth, Vertical Tolerance, degrees	±0.7	±0.7	±0.3	±0.2	±0.3	±0.2
USLS, beampeak to 20° above beampeak, dB	13	14	16	16	17	15
Front-to-Back Total Power at 180° ± 30°, dB	23	22	27	27	25	25
CPR at Boresight, dB	22	21	23	23	22	19

NHH-65B-R2B

CPR at Sector, dB	10	7	16	13	11	4
--------------------------	----	---	----	----	----	---

Mechanical Specifications

Wind Loading at Velocity, frontal	278.0 N @ 150 km/h		63.6 lbf @ 150 km/h
Wind Loading at Velocity, lateral	230.0 N @ 150 km/h		51.7 lbf @ 150 km/h
Wind Loading at Velocity, maximum	120.7 lbf @ 150 km/h		537.0 N @ 150 km/h
Wind Speed, maximum	241 km/h		149.75 mph

Packaging and Weights

Width, packed	409 mm		16.102 in
Depth, packed	299 mm		11.772 in
Length, packed	1952 mm		76.85 in
Net Weight, without mounting kit	19.8 kg		43.651 lb
Weight, gross	32.3 kg		71.209 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant




Included Products

BSAMNT- 3 Wide Profile Antenna Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.

* Footnotes

Performance Note Severe environmental conditions may degrade optimum performance

NHHSS-65B-R2BT2



10-port sector antenna, 2x 698–896, 4x 1695–2200 and 4x 3100–4200 MHz, 65° HPBW, 2x RETs and 2x SBTs. Both high bands share the same electrical tilt.

- Perfect antenna to add 3.5GHz CBRS to macro sites
- Low band and mid band performance mirrors the performance of existing NHH hex port antennas
- Interleaved dipole technology providing for attractive, low wind load mechanical package
- Internal SBT on low and high band allow remote RET control from the radio over the RF jumper cable
- One LB RET and one HB RET. Both high bands are controlled by one RET to ensure same tilt level for 4x MIMO

General Specifications

Antenna Type	Sector
Band	Multiband
Color	Light gray
Grounding Type	RF connector inner conductor and body grounded to reflector and mounting bracket
Performance Note	Outdoor usage
Radome Material	Fiberglass, UV resistant
Radiator Material	Low loss circuit board
Reflector Material	Aluminum
RF Connector Interface	4.3-10 Female
RF Connector Location	Bottom
RF Connector Quantity, high band	4
RF Connector Quantity, mid band	4
RF Connector Quantity, low band	2
RF Connector Quantity, total	10

Remote Electrical Tilt (RET) Information

RET Hardware	CommRET v2
RET Interface	4x 8 pin connector as per IEC 60130-9 Daisy chain in: Male / Daisy chain out: Female Pin3: RS485A(AISG_B), Pin5: RS485B(AISG_A), Pin6: DC 10~30V, Pin7: DC_ Return
RET Interface, quantity	2 female 2 male


NHHSS-65B-R2BT2

Input Voltage	10–30 Vdc
Internal RET	High band (1) Low band (1)
Power Consumption, active state, maximum	10 W
Power Consumption, idle state, maximum	2 W
Protocol	3GPP/AISG 2.0 (Single RET)

Dimensions

Width	301 mm 11.85 in
Depth	181 mm 7.126 in
Length	1828 mm 71.969 in
Net Weight, without mounting kit	23.1 kg 50.927 lb

Array Layout




Array ID	Frequency (MHz)	RF Connector	RET (SRET)	AISG No.	AISG RET UID
R1	698-896	1 - 2	1	AISG1	CPxxxxxxxxxxxxxxR1
B1	1695-2200	3 - 4	2	AISG2	CPxxxxxxxxxxxxxxB1
B2	1695-2200	5 - 6			
P1	3100-4200	7 - 8	N/A	NA	N/A
P2	3100-4200	9 - 10			

(Sizes of colored boxes are not true depictions of array sizes)

Port Configuration

NHHSS-65B-R2BT2



Electrical Specifications

Impedance	50 ohm
Operating Frequency Band	1695 – 2200 MHz 3100 – 4200 MHz 698 – 896 MHz
Polarization	±45°
Total Input Power, maximum	1,000 W @ 50 °C

Electrical Specifications

Frequency Band, MHz	698-806	806-896	1695-1880	1850-1990	1920-2200	3100-3550	3550-3700	3700-4200
Gain, dBi	14.8	15.2	17.4	17.8	18	17.5	17.3	17.6
Beamwidth, Horizontal, degrees	65	62	66	61	64	55	65	61
Beamwidth, Vertical, degrees	13	11.6	5.5	5.2	4.9	5.7	5.4	4.9
Beam Tilt, degrees	0–14	0–14	0–7	0–7	0–7	2	2	2
USLS (First Lobe), dB	15	15	16	18	18	17	17	17
Front-to-Back Ratio at 180°, dB	26	29	31	28	27	30	32	29
Isolation, Cross Polarization, dB	25	25	25	25	25	25	25	25
Isolation, Inter-band, dB	25	25	25	25	25	28	28	28
VSWR Return loss, dB	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0
PIM, 3rd Order, 2 x 20 W, dBc	-153	-153	-153	-153	-153	-140	-140	-140

NHHSS-65B-R2BT2

Input Power per Port at 50°C, maximum, watts 300 300 300 300 300 100 100 100

Electrical Specifications, BASTA

Frequency Band, MHz	698–806	806–896	1695–1880	1850–1990	1920–2200	3100–3550	3550–3700	3700–4200
Gain by all Beam Tilts, average, dBi	14.6	14.8	17	17.5	17.7	17.1	16.9	17.1
Gain by all Beam Tilts Tolerance, dB	±0.4	±0.4	±0.6	±0.3	±0.4	±0.5	±0.7	±0.8
Gain by Beam Tilt, average, dBi	0° 14.6 7° 14.6 14° 14.4	0° 15.0 7° 14.9 14° 14.5	0° 16.9 3° 17.0 7° 16.8	0° 17.4 3° 17.5 7° 17.4	0° 17.5 3° 17.8 7° 17.6			
Beamwidth, Horizontal Tolerance, degrees	±1.7	±1.3	±7.2	±3.1	±6.2	±11.7	±7.4	±10.9
Beamwidth, Vertical Tolerance, degrees	±0.8	±0.8	±0.2	±0.2	±0.4	±0.4	±0.3	±0.4
USLS, beampeak to 20° above beampeak, dB	18	16	14	15	17	14		
Front-to-Back Total Power at 180° ± 30°, dB	22	25	25	25	24	26	25	23
CPR at Boresight, dB	24	17	16	21	19	15	16	14
CPR at Sector, dB	12	6	11	10	8	7	8	7

Mechanical Specifications

Wind Loading at Velocity, frontal	278.0 N @ 150 km/h 62.5 lbf @ 150 km/h
Wind Loading at Velocity, lateral	230.0 N @ 150 km/h 51.7 lbf @ 150 km/h
Wind Loading at Velocity, maximum	120.7 lbf @ 150 km/h 537.0 N @ 150 km/h
Wind Speed, maximum	241 km/h 149.75 mph

Packaging and Weights

Width, packed	1973 mm 77.677 in
Depth, packed	441 mm 17.362 in
Length, packed	337 mm 13.268 in
Weight, gross	35.1 kg 77.382 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance

NHHSS-65B-R2BT2

ROHS



Compliant

Included Products


BSAMNT-3

- Wide Profile Antenna Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members.
Kit contains one scissor top bracket set and one bottom bracket set.



* Footnotes

Performance Note Severe environmental conditions may degrade optimum performance

[CBRS RRH] Spec.



Standard Label



Current Size: 216 x 307 x 105.5 mm (6.99L)
(8.5 x 12.1 x 4.1 inch., excluding Port Guard)

Design is subject to minor change

Item	Specification
Band	Band 48 (3.5 GHz)
Frequency	3550~3700 MHz
IBW	150 MHz
OBW	80 MHz
# of Carriers	5/10/15/20 MHz x 4 carriers
RF Chain	4TX / 4RX
RF Output Power & EIRP	4 path x 5 W (Total: 20 W = 43 dBm) (EIRP: 47 dBm / 10 MHz)
RX Sensitivity	Typical : -101.5 dBm @ 1 Rx (3GPP 36.104, Wide Area)
Modulation	256-QAM support (1024-QAM with 1~2dB power back-off)
Input Power	-48 VDC (-38 to -57 VDC, 1 SKU), with clip-on AC-DC converter (Option)
Power Consumption	About 160 Watt @ 100% RF load, typical conditions
Volume	Under 7L (w/o Antenna), Under 9.6L (with antenna)
Weight	Under 8.0 kg (18.64 lb) (w/o Antenna), Under 10.5 Kg (with ant.)
Operating Temperature	-40°C (-40°F) ~ 55°C (131°F) (W/o solar load)
Cooling	Natural convection
Unwanted Emission	3GPP 36.104 Category A [B48] : FCC 47 CFR 96.41 e)
Optic Interface	20km, 2 ports (9.8Gbps x 2), SFP, single mode, duplex or Bi-Di
CPRI Cascade	Not supported
# of Antenna Port	4
External Alarm (UDA)	4
RET	AISG 2.2
TMA & built-in Bias-T I//F and PIM cancellation	Not supported
Mounting Options	Pole, wall, tower, back to back, side by side (for external ant), 3 RRH with Clip-on Antenna on the pole
Antenna Type	Integrated (Clip-on) antenna (Option), External antenna (Option)
NB-IoT	Not Supported (HW Resource reserved for 1 Guard Band NB-IoT per LTE carrier)
Spectrum Analyzer	TX/RX Support
External Alarm (UDA)	4
5G NR	Support with S/W upgrade
XRAN	Support with S/W upgrade

ATTACHMENT 3

ATTACHMENT 4



July 9, 2021

Verizon Wireless
20 Alexander Drive
Wallingford, CT 06492

Attn: Mr. David Vivian

Re: Structural Analysis Report
Verizon Site I.D.: South Windsor North CT - LSub6 - Carrier Add
50 Plantation Road
East Windsor, CT 06016

Project/Location Code: 20171646071/469756
VZW FUZE I.D.: 16560063
APT Filing No. CT141_12500

Dear Mr. Vivian,

All-Points Technology Corp. (APT), a professional engineering corporation licensed in the State of Connecticut, performed a structural analysis of the above existing 133-ft \pm high elevated water reservoir to support a proposed antenna and appurtenance modification.

Details of the proposed antenna and appurtenance modification are included within the table on the following page. Reference is made to the Construction Drawings prepared by this office, marked Rev 0, dated 07/07/21.

The following information was utilized in the preparation of this assessment:

- Construction Drawings prepared by APT, marked Rev1, dated 11/06/2020
- Tank Reinforcement Drawings, prepared by APT, marked Rev0, dated 07/09/20.
- Structural Modification Design Report, prepared by APT, dated 07/09/20.
- SK-S1 - Foundation Reinforcement Details, marked Rev1, dated 06/08/21.
- SK-S2 - Reinforcement Details, marked Rev1, dated 06/30/21.

The structural analysis has been prepared in accordance with the following design standards:

- ASCE/SEI 7-10 - Minimum Design Loads for Buildings and Other Structures
- AISC - American Institute of Steel Construction Manual of Steel Construction, 14th Ed.
- IBC 2015 - as amended by the 2018 Connecticut State Building Code.
- ANSI/TIA-222-H - Structural Standard for Antenna Supporting Structures, Antennas and Small Wind Turbine Support Structures

Design Criteria:

- Load Case 1: 125 mph (3-sec gust), Ultimate Wind Speed
- Load Case 2: 125 mph (3-sec gust), Ultimate Wind Speed 0.9 x Dead Load
- Structure Class II
- Exposure Category C
- Topographic Category 1

Note: Risk Category II used. (Water tank no longer in service).

The analysis consists was conducted utilizing the following equipment inventory (proposed equipment indicated in **bold** text):

Carrier	Antenna and Appurtenance Make/Model	Elevation	Status	Mount Type	Coax/Feed-Line
Clearwire	(2) 3-ft Dia. Microwave Dishes (Dragonwave A-ANT-23-G-2.5 est.)	125'±	E	(3) Pipe Mounts	(3) 1-1/4" RF Hyrbriflex, (2) 1/2", (2) 2-1/4" Innerduct
Clearwire	(3) Fiber Boxes	124'±	E		
Clearwire	(3) Argus LLPX310R-V4 panel antennas	119'±	E		
Clearwire	(3) Remote Radio Units	116'±	E		
Sprint	(2) RFS APVX9ERR18-C-A20, (1) RFS APVXSPP18-C-A20, (3) ALU 800 MHz 2x50W RRHs & (3) ALU 1900MHz 4x40W RRHs	121'±	E	(3) Pipe Mounts	
Clearwire	(1) Fiber Box	109'±	E	Catwalk Rail	n/a
MetroPCS/ T-Mobile	(3) RFS APXV18-206517S-C panel antennas	119'±	E	(3) Pipe Mounts	(6) 1-5/8
AT&T	(6) Powerwave 7770 panel antennas, (2) Powerwave P65-17-XLH-RR panel antennas, (1) KMW AM-X-CD-16-65-00T-RET panel antenna (12) Powerwave LGP 21401 TMAs, (3) Ericsson RRUS-11, (3) Ericsson RRUS-12 and (3) Raycap DC2 Surge Suppressors (est.)	112 - 113'±	E	(3) Pipe Mounts (shared with Clearwire & MetroPCS/T-Mobile)	(12) 1-5/8", (2) 5/8" & (1) 3/8" fiber/DC cables (est.)
Verizon	(3) Commscope NHSS-65B-R2B, (3) Commscope NHH-65B-R2B panel antennas, (3) Samsung MT6407-77A antennas (3) Samsung B5/B13 RRH-BR04C Remote Radio Heads (RRHs), (3) Samsung B2/B66A RRH-BR049 RRHs, (3) Samsung CBRS RT4401-48A RRHs (3) Raycap RHSDC-3315-PF-48 Over Voltage Protection Boxes (OVPs)	102'94'	P	Custom Pipe Mounts Attached to Exist. Tank Legs	(3) 6x12 Low Inductance Hybrid Fiber Cables (Routed within Southwest Built-Up Lattice Leg Channels)
Clearwire	One (1) Fiber Box	10'±	E	Leg	n/a

Analysis Results:

The analysis was conducted in accordance with the criteria outlined above, with the aforementioned existing and proposed equipment loading. The following table summarizes the results of the analysis:

Component	Usage (%)
New Sway Rods	94%
Reinforced Wing Plates	97%
Anchor Bolts	58%

Notes:

1. ASTM A36 steel grade used for the basis of the new sway rod design.
2. Existing anchor bolts include 1/8" corrosion allowance.
3. Anchor bolt usage includes (1) new 3/4"dia. anchor bolt per leg.
4. Assumes reservoir no longer used for water storage.
5. Reinforced gusset plates (Pin bearing on plate controls).

Base Foundation:

Evaluation of the existing foundation system was limited to a global stability check with the existing and proposed loading. The existing foundation geometry was established through field investigation conducted by APT during May 2017, and during construction of the new build project during June 2021. Subgrade conditions were based on presumptive soil parameters per TIA-222-H Section 9.4, and Table F-1 (Annex F) & IBC 2015.

The calculated leg and base reactions with the above noted loading are as follows:


Load Effect	Calculated Base Reactions	Usage
Axial	74 k	n/a
Shear	70 k	n/a
Overspinning Moment	5291 ft-k	n/a
Leg Uplift	95 k	0.75 < 1.0 (PASS)

1 kip = 1,000lbs

Conclusions:

Successful completion of the reinforcements detailed within the attached drawings, will result in a host structure that meet the requirements of the 2015 International Building Code, as amended by the 2018 Connecticut State Building Code.

Sincerely,
All-Points Technology Corp., P.C.



Michael S. Trodden, P.E.
Sr. Structural Engineer

Prepared by:
All-Points Technology Corp., P.C.



Jason R. Mead
Department Manager –
Structural Services



Limitations:

This report is based on the following:

1. Tower/structure is properly installed and maintained.
2. All members are in a non-deteriorated condition.
3. All required members are in place.
4. All bolts are in place and are properly tightened.
5. Tower/structure is in plumb condition.
6. All tower members were properly designed, detailed, fabricated, and installed and have been properly maintained since erection.

All-Points Technology Corporation, P.C. (APT) is not responsible for any modifications completed prior to or hereafter which APT is not or was not directly involved. Modifications include but are not limited to:

1. Replacing or reinforcing bracing members.
2. Reinforcing members in any manner.
3. Installing antenna mounts.
4. Extending tower/structure.

APT hereby states that this document represents the entire report and that it assumes no liability for any factual changes that may occur after the date of this report. All representations, recommendations, and conclusions are based upon the information contained and set forth herein. If you are aware of any information which is contrary to that which is contained herein, or you are aware of any defects arising from the original design, material, fabrication and erection deficiencies, you should disregard this report and immediately contact APT. APT disclaims all liability for any representation, recommendation, or conclusion not expressly stated herein.

Appendix A

Calculations



(APPENDIX N) MUNICIPALITY - SPECIFIC STRUCTURAL DESIGN PARAMETERS												
Municipality	Ground Snow Load (psf)	MCE Spectral Acceleration s (%g)		Ultimate Design Wind Speeds, V_{ult} (mph)			Nominal Design Wind Speeds, V_{asd} (mph)			Wind-Borne Debris Regions ¹		Hurricane-Prone Regions
		S_s	S_1	Risk Cat.I	Risk Cat.II	Risk Cat. III-IV	Risk Cat. I	Risk Cat. II	Risk Cat. III-IV	Risk Cat. II & III except Occup I-2	Risk Cat III Occup I-2 & Risk Cat. IV	
East Hampton	30	0.177	0.062	120	130	140	93	101	108			Yes
East Hartford	30	0.180	0.064	115	125	135	89	97	105			Yes
East Haven	30	0.182	0.062	120	130	140	93	101	108		Type B	Yes
East Lyme	30	0.164	0.059	125	135	145	97	105	112	Type B	Type A	Yes
Easton	30	0.215	0.066	110	120	130	85	93	101			Yes
East Windsor	35	0.177	0.064	115	125	135	89	97	105			Yes
Ellington	35	0.176	0.064	115	125	135	89	97	105			Yes
Enfield	35	0.176	0.065	110	125	130	85	97	101			Yes
Essex	30	0.168	0.059	120	135	145	93	105	112		Type A	Yes
Fairfield	30	0.215	0.065	115	125	135	89	97	105		Type B	Yes
Farmington	35	0.183	0.064	115	125	135	89	97	105			Yes
Franklin	30	0.171	0.061	120	130	140	93	101	108		Type A	Yes
Glastonbury	30	0.180	0.063	115	125	135	89	97	105			Yes
Goshen	40	0.181	0.065	105	115	125	81	89	97			
Granby	35	0.176	0.065	110	120	130	85	93	101			Yes
Greenwich	30	0.259	0.070	110	120	130	85	93	101			Yes
Griswold	30	0.168	0.060	125	135	145	97	105	112		Type A	Yes
Groton	30	0.160	0.058	125	135	145	97	105	112	Type B	Type A	Yes
Guilford	30	0.176	0.061	120	130	140	93	101	108		Type B	Yes
Haddam	30	0.175	0.061	120	130	140	93	101	108			Yes
Hamden	30	0.185	0.063	115	125	135	89	97	105			Yes
Hampton	35	0.172	0.062	120	130	140	93	101	108			Yes
Hartford	30	0.181	0.064	115	125	135	89	97	105			Yes
Hartland	40	0.175	0.065	110	120	125	85	93	97			Yes
Harwinton	35	0.183	0.065	110	120	130	85	93	101			Yes
Hebron	30	0.177	0.063	120	130	140	93	101	108			Yes
Kent	40	0.188	0.065	105	115	120	81	89	93			
Killingly	40	0.171	0.062	120	130	140	93	101	108			Yes
Killingworth	30	0.173	0.061	120	130	140	93	101	108			Yes
Lebanon	30	0.173	0.062	120	130	140	93	101	108			Yes
Ledyard	30	0.163	0.059	125	135	145	97	105	112		Type A	Yes
Lisbon	30	0.169	0.061	125	135	145	97	105	112		Type A	Yes
Litchfield	40	0.184	0.065	110	120	125	85	93	97			Yes
Lyme	30	0.164	0.059	125	135	145	97	105	112		Type A	Yes
Madison	30	0.173	0.060	120	130	140	93	101	108		Type B	Yes
Manchester	30	0.178	0.064	115	125	135	89	97	105			Yes
Mansfield	35	0.173	0.062	120	130	140	93	101	108			Yes
Marlborough	30	0.177	0.062	120	130	140	93	101	108			Yes
Meriden	30	0.183	0.063	115	125	135	89	97	105			Yes
Middlebury	35	0.191	0.064	110	120	130	85	93	101			Yes
Middlefield	30	0.181	0.063	115	125	135	89	97	105			Yes
Middletown	30	0.180	0.063	115	130	135	89	101	105			Yes
Milford	30	0.194	0.063	115	125	135	89	97	105		Type B	Yes
Monroe	30	0.205	0.065	110	120	130	85	93	101			Yes

ASCE 7 Hazards Report

Address:
50 Plantation Rd
Broad Brook, Connecticut
06016

Standard: ASCE/SEI 7-10
Risk Category: II
Soil Class: D - Stiff Soil

Elevation: 158.08 ft (NAVD 88)
Latitude: 41.87543
Longitude: -72.564799



Wind

Results:

Wind Speed:	122 Vmph
10-year MRI	76 Vmph
25-year MRI	86 Vmph
50-year MRI	93 Vmph
100-year MRI	100 Vmph

Data Sources:

ASCE/SEI 7-10, Fig. 26.5-1A and Figs. CC-1–CC-4, and Section 26.5.2, incorporating errata of March 12, 2014

Value provided is 3-second gust wind speeds at 33 ft above ground for Exposure C Category, based on linear interpolation between contours. Wind speeds are interpolated in accordance with the 7-10 Standard. Wind speeds correspond to approximately a 7% probability of exceedance in 50 years (annual exceedance probability = 0.00143, MRI = 700 years).

Site is in a hurricane-prone region as defined in ASCE/SEI 7-10 Section 26.2. Glazed openings need not be protected against wind-borne debris.



Seismic

Site Soil Class: D - Stiff Soil

Results:

S_s :	0.177	S_{DS} :	0.189
S_1 :	0.064	S_{D1} :	0.103
F_a :	1.6	T_L :	6
F_v :	2.4	PGA :	0.088
S_{MS} :	0.284	PGA _M :	0.141
S_{M1} :	0.154	F_{PGA} :	1.6
		I_e :	1

Seismic Design Category B



Data Accessed:

Wed Jul 14 2021

Date Source:

USGS Seismic Design Maps based on ASCE/SEI 7-10, incorporating Supplement 1 and errata of March 31, 2013, and ASCE/SEI 7-10 Table 1.5-2. Additional data for site-specific ground motion procedures in accordance with ASCE/SEI 7-10 Ch. 21 are available from USGS.

Height		Carrier/Equipment		Antenna and Appearances Area Calculations						
Item	Quantity	H (in)	W (in)	Dimensions	Area (ft ²) (ea)	Item	Dimensions	Area (ft ²) (ea)	Weight (lbs)	Weight (Total)
Prop. Verizon L-Sub6 Antennas	2.00	35.1	16.1	5.5	3.92	2.18	6.0	1.32	5.18	7.25
Prop. Verizon L-Sub6 Antennas	1.00	35.1	16.1	5.5	3.92	2.18	6.0	1.32	5.18	8.71
Prop. Verizon Panel Antennas	4.00	72.0	11.9	7.1	5.95	6.05	6.05	8.24	1.00	32.94
Prop. Verizon Panel Antennas	2.00	72.0	11.9	7.1	5.95	6.05	6.05	8.24	1.00	16.47
Prop. Verizon B2/B6A RRH BR049	2.00	15.0	10.0	1.56	1.00	FLAT	1.38	1.38	1.00	4.06
Prop. Verizon B2/B6A RRH BR049	1.00	15.0	10.0	1.56	1.00	FLAT	1.30	1.30	1.00	2.03
Prop. Verizon B2/B13 RRH BR04C	2.00	15.0	8.1	1.56	1.00	FLAT	1.30	1.30	1.00	4.06
Prop. Verizon B2/B13 RRH BR04C	1.00	15.0	8.1	1.56	1.00	FLAT	1.30	1.30	1.00	2.03
Prop. Verizon Samsung CBS R144001-48A RRH	2.00	10.6	8.9	3.0	0.66	1.19	FLAT	1.30	0.85	8.20
Prop. Verizon Samsung CBS R144001-48A RRH	1.00	10.6	8.9	3.0	0.66	1.19	FLAT	1.30	0.85	8.20
Prop. Verizon B2/P	2.00	29.5	16.5	12.6	3.38	1.79	FLAT	1.31	0.01	11.0
Prop. Verizon B2/P	1.00	29.5	16.5	12.6	3.38	1.79	FLAT	1.31	0.01	11.0
Prop. Verizon B2/P	6.00	180.0	3.5	3.5	4.38	51.43	ROUND	1.20	1.00	6.21
Prop. Verizon B2/P	3.00	180.0	3.5	3.5	4.38	51.43	ROUND	1.20	1.00	6.21
Prop. Verizon Mounts (For Ant + RRHs)	1.00	72.0	11.8	5.9	5.90	6.10	FLAT	1.39	8.17	1.00
Prop. Verizon Mounts	1.00	96.0	12.0	6.0	8.00	8.00	FLAT	1.43	11.47	1.00
Exist. AT&T Panel Antennas (MMW-AM-X-CD-16-65-00T-RET)	1.00	96.0	12.0	6.0	8.00	8.00	FLAT	1.43	11.47	1.00
Exist. AT&T Panel Antennas (Powerwave B165-17-20L-RR)	1.00	55.0	11.0	5.0	4.20	5.00	FLAT	1.37	1.00	1.00
Exist. AT&T Panel Antennas (Powerwave T770)	4.00	55.0	11.0	5.0	4.20	5.00	FLAT	1.37	5.74	1.00
Exist. AT&T TMA8 (Powerwave LGP21401)	4.00	9.2	2.6	0.92	1.57	FLAT	1.31	1.20	1.00	4.82
Exist. AT&T TMA8 (Powerwave LGP21401)	8.00	14.4	9.2	2.6	0.92	1.57	FLAT	1.31	1.20	9.64
Exist. AT&T RRHs (Ericsson RRUS 11)	2.00	19.7	17.0	7.2	2.33	1.16	FLAT	1.30	3.03	1.00
Exist. AT&T RRHs (Ericsson RRUS 11)	1.00	19.7	17.0	7.2	2.33	1.16	FLAT	1.30	3.03	1.00
Exist. AT&T RRHs (Ericsson RRUS 12)	2.00	20.4	18.5	7.5	2.62	1.10	FLAT	1.30	3.41	1.00
Exist. AT&T RRHs (Ericsson RRUS 12)	1.00	20.4	18.5	7.5	2.62	1.10	FLAT	1.30	3.41	1.00
Exist. AT&T RRHs (Ericsson RRUS 12)	2.00	10.4	6.3	10.8	0.46	1.65	ROUND	1.31	0.60	1.00
Exist. AT&T RRHs (Ericsson RRUS 12)	1.00	10.4	6.3	10.8	0.46	1.65	ROUND	1.31	0.60	1.00
Exist. AT&T SA (DC2-48-60-00E, est.)	1.00	72.0	6.8	3.2	3.40	10.59	FLAT	1.52	5.17	1.00
MetroPCST-Mobile Panel Antennas (IRFS APXV18-2065175-C)	2.00	72.0	6.8	3.2	3.40	10.59	FLAT	1.52	5.17	1.00
MetroPCST-Mobile Panel Antennas (IRFS APXV18-2065175-C)	1.00	72.0	6.8	3.2	3.40	10.59	FLAT	1.52	5.17	1.00
Exist. Sprint Panel Antennas (IRFS APXV Series)	2.00	72.0	11.8	7.0	5.90	6.10	FLAT	1.39	8.17	1.00
Exist. Sprint Panel Antennas (IRFS APXV Series)	1.00	72.0	11.8	7.0	5.90	6.10	FLAT	1.39	8.17	1.00
Exist. Sprint RRHs (800 MHz RRH)	2.00	15.7	13.0	9.8	1.42	1.21	FLAT	1.30	1.85	1.00
Exist. Sprint RRHs (800 MHz RRH)	1.00	15.7	13.0	9.8	1.42	1.21	FLAT	1.30	1.85	1.00
Exist. Sprint RRHs (1900 MHz RRH)	2.00	25.0	11.1	11.4	1.93	2.25	FLAT	1.32	2.55	1.00
Exist. Sprint RRHs (1900 MHz RRH)	1.00	25.0	11.1	11.4	1.93	2.25	FLAT	1.32	2.55	1.00
Exist. CW Fiber Box (14x14x8")	1.00	14.0	8.0	17.0	0.78	1.75	FLAT	1.31	1.02	1.00
Exist. CW Fiber Box (14x14x8")	1.00	14.0	8.0	17.0	0.78	1.75	FLAT	1.31	1.02	1.00
Exist. CW Panel Antennas (Aigis LPX310E-V4)	2.00	42.1	11.8	4.5	3.46	3.57	FLAT	1.34	4.64	1.00
Exist. CW Panel Antennas (Aigis LPX310E-V4)	1.00	42.1	11.8	4.5	3.46	3.57	FLAT	1.34	4.64	1.00
Exist. CW RRHs (77x14" Es)	2.00	17.0	14.0	7.0	1.65	1.21	FLAT	1.30	2.15	1.00
Exist. CW RRHs (77x14" Es)	1.00	17.0	14.0	7.0	1.65	1.21	FLAT	1.30	2.15	1.00
Exist. CW Fiber Boxes (12x12x6" est.)	2.00	12.0	6.0	12.0	0.50	2.00	FLAT	1.32	0.66	1.00
Exist. CW Fiber Boxes (12x12x6" est.)	1.00	12.0	6.0	12.0	0.50	2.00	FLAT	1.32	0.66	1.00
Exist. CW MM Dish (A-ANT-23-G-2.5)	1.00	35.0	16.8	8.51	1.00	FLAT	1.30	1.06	1.00	11.06
Exist. CW MM Dish (A-ANT-23-G-2.5)	1.00	35.0	16.8	8.51	1.00	FLAT	1.30	1.06	1.00	11.06
Exist. AT&T Exposed Pipe Mounts (P3x20' est.)	3.00	3.5	86.0	9.8	2.63	0.03	ROUND	0.70	1.84	1.00
Exist. AT&T Exposed Pipe Mounts (P3x20' est.)	3.00	3.5	86.0	9.8	2.63	0.04	ROUND	0.70	1.46	1.00
Exist. AT&T Exposed Pipe Mounts (P3x20' est.)	3.00	3.5	68.0	11.4	1.65	0.05	ROUND	0.99	1.16	1.00
Exist. AT&T Exposed Pipe Mounts (P3x20' est.)	3.00	3.0	46.0	3.0	0.96	0.15	ROUND	1.14	2.83	1.00
Exist. Sprint Exposed Pipe Mounts (P3x20' est.)	3.00	3.5	60.0	3.5	1.46	0.15	ROUND	1.03	1.50	1.00
Exist. Sprint Exposed Pipe Mounts (P3x20' est.)	3.00	3.5	60.0	3.5	1.46	0.15	ROUND	1.03	1.50	1.00
Subtotal										20.69
Total Sum Weight										6313.60

Designer Comments:
 (1) Existing TRAs and RRUs considered not shielded from wind by antennas.

All-Points Technology Corporation

Consulting Engineers
3 Saddlebrook Drive,
Killingworth, CT 06419
Ph. 860-663-1697
Fax. 860-663-0935

Subject: **Sway Bracing & Anchor Bolt Analysis**
Project: **Verizon - South Windsor North CT - LSub6**
Prepared: **07.09.21**

Revised:

APT Job No.

CT141_12500

Sway Rod X - Bracing Analysis at Level 1 (0 to 37-ft ± AGL)

X Bracing Rod Dia. (in)	1.5	New
Rod Yield Stress, Fy (psi)	36,000	ASTM A307 USED
Rod Tensile Stress, Fu (psi)	60,000	ASTM A307 USED
Angle of Sway Rod From Ground Plane (degrees)	50	
Un-threaded Portion Area (in ²)	1.767	(Nominal area, Ag)
Available Tension Strength (Tumbuckle)	52.50	kips (1 1/2" dia. UNC/4UN Class 2B)
Available Tension Strength (Clevis)	52.50	kips (#4, UNC Class 2B)
Available Tension Strength in Un-threaded Rod	57.26	(0.90*Fy*Ag)
Available Tension Strength in Threaded Rod	59.64	(0.75*75*Fu*Ag)
Net Ultimate Shear Force (one side)	63.12	kips
Ultimate Tension Force in Sway Rod	49.10	kips
Usage (Tension)	0.94	<1.0 OK

Assumes only one sway rod is engaged per side.

Sway Rod X - Bracing Analysis at Level 2 (37 to 74-ft ± AGL)

X Bracing Rod Dia. (in)	1.5	New
Rod Yield Stress, Fy (psi)	36,000	ASTM A307 USED
Rod Tensile Stress, Fu (psi)	60,000	ASTM A307 USED
Angle of Sway Rod From Ground Plane (degrees)	59	
Un-threaded Portion Area (in ²)	1.767	(Nominal area, Ag)
Available Tension Strength (Tumbuckle)	52.50	kips (1 1/2" dia. UNC/4UN Class 2B)
Available Tension Strength (Clevis)	52.50	kips (#4, UNC Class 2B)
Available Tension Strength in Un-threaded Rod	57.26	(0.90*Fy*Ag)
Available Tension Strength in Threaded Rod	59.64	(0.75*75*Fu*Ag)
Net Ultimate Shear Force	47.51	kips
Ultimate Tension Force in Sway Rod	46.12	kips
Usage (Tension)	0.88	<1.0 OK

Assumes only one sway rod is engaged per side.

Sway Rod X - Bracing Analysis at Level 3 (74 to 109-ft ± AGL)

X Bracing Rod Dia. (in)	1.375	New
Rod Yield Stress, Fy (psi)	36,000	ASTM A307 USED
Rod Tensile Stress, Fu (psi)	60,000	ASTM A307 USED
Angle of Sway Rod From Ground Plane (degrees)	66	
Un-threaded Portion Area (in ²)	1.485	(Nominal area, Ag)
Available Tension Strength (Tumbuckle)	43.50	kips (1 3/8" dia. UNC/4UN Class 2B)
Available Tension Strength (Clevis)	45.00	kips (#3-1/2, UNC Class 2B)
Available Tension Strength in Un-threaded Rod	48.11	(0.90*Fy*Ag)
Available Tension Strength in Threaded Rod	50.12	(0.75*75*Fu*Ag)
Net Ultimate Shear Force	31.47	kips
Ultimate Tension Force in Sway Rod	38.69	kips
Usage (Tension)	0.89	<1.0 OK

Assumes only one sway rod is engaged per side.

Anchor Bolt Analysis

Anchor Rod Dia. (in)	1.375	1.5" dia. Bolts. 1/8" corrosion allowance used
Number of Exist. Anchor Bolts Per Leg	2	
Number of Legs	4	
Leg Circle Diameter (in)	594	(Assumes central standpipe takes no shell DL)
Bolt Tensile Stress (psi)	60,000	Field verified
Number of Threads per Inch	6	
Bolt Area (in ²)	1.485	(Gross area, Ag)
Net Bolt Area (in ²)	1.155	(Net Area, Ar)
Net Ultimate Uplift Tension Force Per Bolt	45.08	kips. (0.9DL + 1.0WL)
Total Ultimate Base Wind Shear	70.27	kips. (x1.0WL)
Ultimate Shear Per Leg	17.57	kips. (x1.0 WL)
Shear Per Anchor Bolt	8.78	kips. (x1.0 WL)
Available Bolt Tension Strength	50.19	kips
Available Bolt Shear Strength	30.14	kips
Additional Anchor Tension Strength	10.51	kips
Additional Anchor Shear Strength	19.02	kips
Usage	0.58	<1.0 OK

Note: Anchor bolt usage includes installation of (1) new 3/4" dia. anchor bolt per leg.

Sway Rod X - Base Wing Plate Connection Analysis (AISC 14th Ed. Sec D5)

Gusset Plate Thickness	0.375	Existing
Plate Yield Stress, Fy (psi)	33,000	ASTM A7-39 used (tank built circa 1946)
Plate Tensile Stress, Fu (psi)	60,000	ASTM A7-39 used (tank built circa 1946)
beff	1.380	in
b	1.950	in
Asf	2.488	in ²
a	2.380	in
d	1.875	in
Apb	0.703	in ²
Ultimate Force in Direction of Rod	49.10	kips
Available Tension Strength at Pin (Net)	46.58	kips
Available Long Shear Strength at Pin	67.18	kips
Available Bearing Strength at Pin	31.32	kips
Available Tension Strength (Gross area)	84.87	kips
Usage	1.57	>1.0 BEARING CONTROLS. ADD 1/4" THK. REINF. PLATE
Reinf Usage	0.97	<1.0 OK

Sway Rod X - Gusset Plate Connection Analysis (37 ± AGL) (AISC 14th Ed. Sec D5)

Gusset Plate Thickness	0.375	Existing (Assumed, V.I.F.)
Plate Yield Stress, Fy (psi)	33,000	ASTM A7-39 used (tank built circa 1946)
Plate Tensile Stress, Fu (psi)	60,000	ASTM A7-39 used (tank built circa 1946)
beff	1.380	in
b	2.960	in
Asf	2.511	in ²
a	2.410	in
d	1.875	in
Apb	0.703	in ²
Ultimate Force in Direction of Rod	49.10	kips
Available Tension Strength at Pin (Net)	46.58	kips
Available Long Shear Strength at Pin	67.79	kips
Available Bearing Strength at Pin	31.32	kips
Available Tension Strength (Gross area)	95.78	kips
Usage	1.57	>1.0 BEARING CONTROLS. ADD 1/4" THK. REINF. PLATE
Reinf Usage	0.97	<1.0 OK

Sway Rod X - Gusset Plate Connection Analysis (74 ± AGL) (AISC 14th Ed. Sec D5)

Gusset Plate Thickness	0.375	Existing (Assumed, V.I.F.)
Plate Yield Stress, Fy (psi)	33,000	ASTM A7-39 used (tank built circa 1946)
Plate Tensile Stress, Fu (psi)	60,000	ASTM A7-39 used (tank built circa 1946)
beff	1.380	in
b	2.380	in
Asf	2.488	in ²
a	2.380	in
d	1.875	in
Apb	0.703	in ²
Ultimate Force in Direction of Rod	46.12	kips
Available Tension Strength at Pin (Net)	46.58	kips
Available Long Shear Strength at Pin	67.79	kips
Available Bearing Strength at Pin	31.32	kips
Available Tension Strength (Gross area)	80.75	kips
Usage	1.47	>1.0 BEARING CONTROLS. ADD 1/4" THK. REINF. PLATE
Reinf Usage	0.92	<1.0 OK

Sway Rod X - Gusset Plate Connection Analysis (109 ± AGL) (AISC 14th Ed. Sec D5)

Gusset Plate Thickness	0.375	Existing (Assumed, V.I.F.)
Plate Yield Stress, Fy (psi)	33,000	ASTM A7-39 used (tank built circa 1946)
Plate Tensile Stress, Fu (psi)	60,000	ASTM A7-39 used (tank built circa 1946)
beff	1.380	in
b	2.060	in
Asf	2.376	in ²
a	2.230	in
d	1.875	in
Apb	0.703	in ²
Ultimate Force in Direction of Rod	38.69	kips
Available Tension Strength at Pin (Net)	46.58	kips
Available Long Shear Strength at Pin	64.14	kips
Available Bearing Strength at Pin	31.32	kips
Available Tension Strength (Gross area)	90.10	kips
Usage	1.24	>1.0 BEARING CONTROLS. ADD 1/4" THK. REINF. PLATE
Reinf Usage	0.79	<1.0 OK

All-Points Technology Corporation

Consulting Engineers 3 Saddlebrook Drive, Killingworth, CT 06419 Ph. 860-663-1697 Fax. 860-663-0935	Subject: Existing Built-Up Column, Lacing Bar and Girt Analysis		
Project: Verizon - South Windsor North CT - LSub6			
Prepared: 07.09.21	Revised:	APT Job No.	CT141_12500

Lattice Column & Lacing Bar Analysis

Column Steel Yield Strength	33	ksi, ASTM A7-39 (tank built circa 1946)
Column Area	12.095	in ²
Lacing Bar Thickness	0.375	in
Lacing Bar Depth	2.25	in
Column Moment of Inertia, I _{xx}	257.41	in ⁴ (Calculated Externally)
Column Moment of Inertia, I _{yy}	286.94	in ⁴ (Calculated Externally)
Column Radius of Gyration, r _{xx}	4.613	in (Calculated Externally)
Column Radius of Gyration, r _{yy}	4.871	in (Calculated Externally)
Column Unbraced Length	445.200	in
Column Effective Length Factor, K	1.000	(Calculated Externally)
Channel Flange Slenderness Ratio	5.868	(Calculated Externally)
Channel Web Slenderness Ratio	34.57	(Calculated Externally)
Lacing Plate Slenderness Ratio	6.00	(Calculated Externally)
Slenderness Parameters		
b/t ≤ 0.56(E/Fy) ^{1/2}	16.60	Channel Flange - Unstiffened Element
h/tw ≤ 1.49(E/Fy) ^{1/2}	44.17	Channel Web - Stiffened Element
b/t ≤ 0.45(E/Fy) ^{1/2}	13.34	Lacing Plate - Unstiffened Element
Column Slenderness Ratio, KL/r	96.51	if < 200, OK
Column Elastic Buckling Stress, F _e	30.73	ksi
F _c	21.05	ksi
Column Design	229.17	kips
Compressive Strength, ϕP_n		kips, (1.2DL + 1.0WL) Tank Empty
Ultimate Compressive Force, P _u	129.17	No longer used to store water.
Built-Up Column Usage	0.56	if <=1.0, OK
Length of Angle Chord		
Between Lacing Bars, I _a	16.38	in
Channel, r _{yy}	0.797	in (Calculated Externally)
75% of Column KL/r	72.38	
L _a /r _z	20.55	< 75% Column KL/r, OK
Length of Lacing Between Channel Chords, L _b	11.31	in
Radius of Gyration of Bar, r _b	0.108	
I _b /r _b	104.51	if < 140, OK
Bar Elastic Buckling Stress, F _e	26.20	ksi
F _c	19.48	ksi
Lacing Bar Design Compressive Strength, ϕP_n bar	16.44	kips
Required Shearing Strength on Each Face of Latticed Column	2.29	kips, (2% Built-Up Column Compression Strength)
Axial Force in Lacing Bar	3.24	kips, if < Lacing Bar
Lacing Bar Usage	0.20	if <=1.0, OK

Built-Up Girt Analysis - Level 1 - 37-ft+/- (C7x9.8 Toe Up Over C6x8.2 Vert, est.)

Girt Steel Yield Strength	33	ksi, ASTM A7-39 (tank built circa 1946)
Built-Up Girt Area	5.226	in ²
Moment of Inertia, I _{xx}	30.86	in ⁴ (Calculated Externally)
Moment of Inertia, I _{yy}	22.01	in ⁴ (Calculated Externally)
Radius of Gyration, r _{xx}	2.430	in (Calculated Externally)
Radius of Gyration, r _{yy}	2.052	in (Calculated Externally)
Unbraced Length	332.180	in
Effective Length Factor, K	1.000	
Lower Channel Flange Slenderness Ratio	5.598	(Calculated Externally)
Lower Channel Web Slenderness Ratio	21.88	(Calculated Externally)
Upper Channel Flange Slenderness Ratio	5.710	(Calculated Externally)
Upper Channel Web Slenderness Ratio	25.00	(Calculated Externally)
Slenderness Parameters		
b/t ≤ 0.56(E/Fy) ^{1/2}	16.60	Channel Flange - Unstiffened Element
h/tw ≤ 1.49(E/Fy) ^{1/2}	44.17	Channel Web - Stiffened Element
Slenderness Ratio, KL/r	161.88	if < 200, OK
Elastic Buckling Stress, F _e	10.92	ksi
F _c	9.58	ksi
Design	45.05	kips
Compressive Strength, ϕP_n		kips, (1.0WL)/Two Sides - Tank Empty
Ultimate Compressive Force, P _u	31.56	No longer used to store water.
Lower Built-Up Girt Usage	0.70	if <=1.0, OK

Built-Up Girt Analysis - Level 2 - 74-ft+/- (C6x8.2 Toe Up Over C6x8.2 Vert, est.)

Girt Steel Yield Strength	33	ksi, ASTM A7-39 (tank built circa 1946)
Built-Up Girt Area	4.76	in ²
Moment of Inertia, I _{xx}	29.11	in ⁴ (Calculated Externally)
Moment of Inertia, I _{yy}	13.90	in ⁴ (Calculated Externally)
Radius of Gyration, r _{xx}	2.473	in (Calculated Externally)
Radius of Gyration, r _{yy}	1.709	in (Calculated Externally)
Unbraced Length	244.300	in
Effective Length Factor, K	1.000	
Lower Channel Flange Slenderness Ratio	5.710	(Calculated Externally)
Lower Channel Web Slenderness Ratio	25.00	(Calculated Externally)
Upper Channel Flange Slenderness Ratio	5.710	(Calculated Externally)
Upper Channel Web Slenderness Ratio	25.00	(Calculated Externally)
Slenderness Parameters		
b/t ≤ 0.56(E/Fy) ^{1/2}	16.60	Channel Flange - Unstiffened Element
h/tw ≤ 1.49(E/Fy) ^{1/2}	44.17	Channel Web - Stiffened Element
Slenderness Ratio, KL/r	142.95	if < 200, OK
Elastic Buckling Stress, F _e	14.01	ksi
F _c	12.28	ksi
Design	52.62	kips
Compressive Strength, ϕP_n		kips, (1.0WL)/Two Sides - Tank Empty
Ultimate Compressive Force, P _u	23.75	No longer used to store water.
Lower Built-Up Girt Usage	0.45	if <=1.0, OK



Project ID: CT141_12500
Site Name: South Windsor North CT
Date: 07.09.21

Use (1) 3/4" DIA. Threaded Rod set in Hilti RE-500 Epoxy w/ 12" min. embedment

$T_{allow} =$	23070	lbs
$V_{allow} =$	49690	lbs
Anchor Quantity =	1.0	
$f_{AN} =$	0.69	<i><< Spacing Reduction Factor, 10"</i>
$f_{RN} =$	0.66	<i><< Edge Distance Reduction Factor, 18"</i>
$f_{AV} =$	0.58	<i><< Spacing Reduction Factor, 10"</i>
$f_{RV} =$	0.66	<i><< Edge Distance Reduction Factor, 18" (Parallel)</i>
$f_{RV} =$	0.74	<i><< Edge Distance Reduction Factor, 18" (Perpendicular)</i>
$f_{HV} =$	1.00	<i><< Concrete Thickness Reduction Factor</i>
LRFD Factor =	1	

Capacities:

$T_{allow} =$	10506.1	lbs
$V_{allow} =$	19021.3	lbs <i>(Parallel)</i>
$V_{allow} =$	21326.9	lbs <i>(Perpendicular)</i>



Title Block Line 1
You can change this area
using the "Settings" menu item
and then using the "Printing &
Title Block" selection.
Title Block Line 6

Project Title:
Engineer:
Project ID:
Project Descr:

Printed: 9 JUL 2020, 10:23PM

File: Lattice Column & Girt Section Properties.ec6
Software copyright ENERCALC, INC. 1983-2020, Build:12.20.5.31
ALL-POINTS TECHNOLOGY CORP.

General Section Property Calculator


Lic. #: KW-06006315

DESCRIPTION: Built -Up Lattice Column Section Properties

Final Section Properties

Total Area :	12.095 in ²	I _{xx} :	257.406 in ⁴	S _{xx} : -Y	:	42.901 in ³
Calculated final C.G. distance from Datum:		I _{yy} :	286.937 in ⁴	S _{xx} : +Y	:	42.901 in ³
X cg Dist. :	0.0 in	Z _{xx} :	50.929 in ³	S _{yy} : -X	:	41.345 in ³
Y cg Dist. :	0.0 in	Z _{yy} :	57.914 in ³	S _{yy} : +X	:	41.345 in ³
Edge Distances from CG :				r _{xx}	:	4.613 in
+X :	6.940 in	+Y :	6.0 in	r _{yy}	:	4.871 in
-X :	-6.940 in	-Y :	in			

Rotation of All Components @ Angle: 0.00 deg CCW



Rectangular & Circular Shapes

Rectangular Shape : 1	Height =	0.000 in	Width =	0.000 in	Rotation =	0 deg CCW
	Area =	0.000 in ²	X _{cg} =	0.000 in		
			Y _{cg} =	0.000 in		



Title Block Line 1
You can change this area
using the "Settings" menu item
and then using the "Printing &
Title Block" selection.
Title Block Line 6

Project Title:
Engineer:
Project ID:
Project Descr:

Printed: 9 JUL 2020, 10:23PM

File: Lattice Column & Girt Section Properties.ec6
Software copyright ENERCALC, INC. 1983-2020, Build:12.20.5.31
ALL-POINTS TECHNOLOGY CORP.

General Section Property Calculator

Lic. #: KW-06006315

DESCRIPTION: Built -Up Latticed Column Section Properties

Rectangular Shape : 2	Height =	0.000 in	Width =	0.000 in	Rotation =	0 deg CCW
	Area =	0.000 in ²	Xcg =	0.000 in		
			Ycg =	0.000 in		

Steel Shapes

C12x20.7 : 1	Area =	6.047 in ²	Rotation =	180 deg CCW
			Xcg =	-4.698 in
			Ycg =	0.000 in
C12x20.7 : 2	Area =	6.047 in ²	Rotation =	0 deg CCW
			Xcg =	4.698 in
			Ycg =	0.000 in



Title Block Line 1
You can change this area
using the "Settings" menu item
and then using the "Printing &
Title Block" selection.
Title Block Line 6

Project Title:
Engineer:
Project ID:
Project Descr:

Printed: 9 JUL 2020, 10:22PM

File: Lattice Column & Girt Section Properties.ec6
Software copyright ENERCALC, INC. 1983-2020, Build:12.20.5.31
ALL-POINTS TECHNOLOGY CORP.

General Section Property Calculator


Lic. #: KW-06006315

DESCRIPTION: Existing Level 1 Horz Girt Section Properties

Final Section Properties

Total Area :	5.226 in ²	I _{xx} :	30.862 in ⁴	S _{xx} : -Y :	6.234 in ³
Calculated final C.G. distance from Datum:		I _{yy} :	22.007 in ⁴	S _{xx} : +Y :	9.952 in ³
X cg Dist. :	0.02912 in	Z _{xx} :	8.80 in ³	S _{yy} : -X :	6.219 in ³
Y cg Dist. :	1.950 in	Z _{yy} :	8.289 in ³	S _{yy} : +X :	6.323 in ³
Edge Distances from CG :				r _{xx} :	2.430 in
+X :	3.480 in	+Y :	3.101 in	r _{yy} :	2.052 in
-X :	-3.539 in	-Y :	in		

Rotation of All Components @ Angle: 0.00 deg CCW



Steel Shapes

	C6x8.2:1	Area =	2.380 in ²	Rotation =	0 deg CCW
				X _{cg} =	0.000 in
				Y _{cg} =	0.000 in
	C7x9.8:2	Area =	2.846 in ²	Rotation =	90 deg CCW
				X _{cg} =	0.000 in
				Y _{cg} =	3.512 in



Title Block Line 1
You can change this area
using the "Settings" menu item
and then using the "Printing &
Title Block" selection.
Title Block Line 6

Project Title:
Engineer:
Project ID:
Project Descr:

Printed: 9 JUL 2020, 10:23PM

File: Lattice Column & Girt Section Properties.ec6
Software copyright ENERCALC, INC. 1983-2020, Build:12.20.5.31
ALL-POINTS TECHNOLOGY CORP.

General Section Property Calculator


Lic. #: KW-06006315

DESCRIPTION: Existing Level 2 Horz Girt Section Properties

Final Section Properties

Total Area :	4.760 in ²	I _{xx} :	29.111 in ⁴	S _{xx} : -Y :	6.080 in ³
		I _{yy} :	13.899 in ⁴	S _{xx} : +Y :	9.324 in ³
Calculated final C.G. distance from Datum:		Z _{xx} :	8.510 in ³	S _{yy} : -X :	4.570 in ³
X cg Dist. :	0.03198 in	Z _{yy} :	6.288 in ³	S _{yy} : +X :	4.668 in ³
Y cg Dist. :	1.788 in				
Edge Distances from CG :				r _{xx} :	2.473 in
+X :	2.978 in	+Y :	3.122 in	r _{yy} :	1.709 in
-X :	-3.042 in	-Y :	in		

Rotation of All Components @ Angle: 0.00 deg CCW



Steel Shapes

	C6x8.2:1	Area =	2.380 in ²	Rotation =	0 deg CCW
				X _{cg} =	0.000 in
				Y _{cg} =	0.000 in
	C6x8.2:2	Area =	2.380 in ²	Rotation =	90 deg CCW
				X _{cg} =	0.000 in
				Y _{cg} =	3.512 in



Project ID: CT141NB7760
Site Name: South Windsor North CT
Date: 7/10/2020
Sheet: of

Use (1) 3/4" DIA. Threaded Rod set in Hilti RE-500 Epoxy w/ 12" min. embedment

T_{allow} = 23070 lbs
 V_{allow} = 49690 lbs
Anchor Quantity = 1.0

f_{AN} = 0.69 << Spacing Reduction Factor, 10"
 f_{RN} = 0.66 << Edge Distance Reduction Factor, 18"
 f_{AV} = 0.58 << Spacing Reduction Factor, 10"
 f_{RV} = 0.66 << Edge Distance Reduction Factor, 18" (Parallel)
 f_{RV} = 0.74 << Edge Distance Reduction Factor, 18" (Perpendicular)
 f_{HV} = 1.00 << Concrete Thickness Reduction Factor
LRFD Factor 1

Reductions per Table 36 Hilti
Anchor Fastening Technical
Guide (19th edition)

Capacities:

T_{allow} = 10506.1 lbs
 V_{allow} = 19021.3 lbs (Parallel)
 V_{allow} = 21326.9 lbs (Perpendicular)



3 Saddlebrook Drive,
Killingworth, CT 06419
PH: 860-663-1697; FAX: 860-663-0935

Verizon - South Windsor North CT

Foundation Analysis

50 Plantation Road, East Windsor, CT 06016

Prepared by: JRM.

APT FILING No. CT141_12500

Checked by: MST, P.E.

Date/Rev: 07.09.21

Elevated Reservoir Foundation Analysis:

Note: Structure no longer utilized as a water tank and is empty.

Max Reactions:

Un-factored Base Axial Load =	$P := 74.3 \cdot \text{kip}$	(User Input)	(Un-factored Axial Load = Tank Self Weight + Wireless Equip DL - Stand Pipe & 1/2 x Spider Rod DL)
Ultimate Base Shear Load =	$V := 70.3 \cdot \text{kip}$	(User Input)	
Ultimate Base Moment =	$M := 5291 \cdot \text{ft} \cdot \text{kip}$	(User Input)	

Load Factors:

Dead Load Factor =	$DL_{f1} := 0.9$
Dead Load Factor =	$DL_{f2} := 1.2$
Wind Load Factor =	$WL_f := 1.0$

Foundation Data:

		Foundation data obtained by field investigation during June 2017 and June 2021.
Top Width of Frustum Pyramid =	$W_{top} := 67.3 \text{ in}$	(User Input)
Bot Width of Frustum Pyramid =	$W_{bot} := 127.43 \text{ in}$	(User Input)
Top Area of Frustum Pyramid =	$B_{1top} := 4509.5 \text{ in}^2$	(User Input)
Bot Area of Frustum Pyramid =	$B_{2bot} := 16396 \text{ in}^2$	(User Input)
Overall Depth of Pyramid =	$D_f := 74 \text{ in}$	(User Input)
Base Thickness =	$T_{base} := 0.00 \cdot \text{in}$	(User Input)
Base Width =	$W_{base} := 0.00 \cdot \text{in}$	(User Input)
Height of Foundation Above Grade =	$T_{ext} := 4.00 \cdot \text{in}$	(User Input)
Depth to Water Table =	$D_{wt} := 99 \cdot \text{ft}$	(User Input)
Water Tank Leg Circle Diameter =	$D_{circle} := 594.00 \cdot \text{in}$	(User Input)
Number of Legs =	$N_{leg} := 4.00$	(User Input)
Depth to Base of Foundation from Grade =	$D_{base} := D_f + T_{base} - T_{ext} = 5.833 \text{ ft}$	Note: Set Dwt to a value greater than total depth of footing if water table does not affect footing.

Material Data:

Concrete Compressive Strength =	$f_c := 3000 \cdot \text{psi}$	(User Input)
Steel Reinforcement Yield Strength =	$F_y := 40000 \text{ psi}$	(User Input)
Internal Friction Angle of Soil =	$\phi_s := 30 \cdot \text{deg}$	(User Input)
Ultimate Soil Bearing Capacity =	$q_s := 8000 \cdot \text{psf}$	(User Input)
Unit Weight of Soil =	$\gamma_{soil} := 110 \cdot \text{pcf}$	(User Input)
Unit Weight of Concrete =	$\gamma_{concrete} := 150 \cdot \text{pcf}$	(User Input)
Foundation Bouyancy =	$Bouyancy := 0$	(User Input) (Yes=1 / No=0)
Depth to Neglect =	$D_n := 6 \text{ in}$	(User Input)
Cohesion of Clay Type Soil =	$c := 0 \cdot \text{ksf}$	(User Input) (Use 0 for Sandy Soil)
Coefficient of Friction Between Concrete =	$\mu := 0.45$	(User Input)
Coefficient of Lateral Soil Pressure =	$K_p := \frac{1 + \sin(\phi_s)}{1 - \sin(\phi_s)} = 3$	
Adjusted Concrete Unit Weight =	$\gamma_c = 150 \text{ pcf}$	
Adjusted Soil Unit Weight =	$\gamma_s = 110 \text{ pcf}$	

Determine Maximum Uplift and Compression Forces at Leg:

$$\text{Factored Shear Force per Leg} = V_{leg} := \left(\frac{V \cdot WL_f}{N_{leg}} \right) = 17.575 \text{ kip}$$

$$\text{Factored Max Leg Uplift Force} = U_{plift} := \left(\frac{WL_f \cdot (4 \cdot M)}{N_{leg} \cdot D_{circle}} \right) - \left(\frac{DL_{f1} \cdot P}{N_{leg}} \right) = 90.17 \text{ kip}$$

$$\text{Factored Max Leg Compression Force} = C_{compression} := \left(\frac{WL_f \cdot (4 \cdot M)}{N_{leg} \cdot D_{circle}} \right) + \left(\frac{DL_{f2} \cdot P}{N_{leg}} \right) = 129.18 \text{ kip}$$

Calculate Foundation Volume:

$$\text{Volume of Frustum Pyramid Concrete Foundation} = V_{Frustum} := \frac{1}{3} \cdot D_f \cdot (B_{1top} + B_{2bot} + \sqrt{B_{1top} \cdot B_{2bot}}) = 421.16 \text{ ft}^3$$

$$\text{Gross Volume of Conc} = V_{conc} := V_{Frustum} = 421.16 \text{ ft}^3$$

$$\text{Volume of Frustum Pyramid Below Grade (Minus Depth to Neglect)} = V_{FrustumNet} := \frac{1}{3} \cdot (D_{base}) \cdot (B_{1top} + B_{2bot} + \sqrt{B_{1top} \cdot B_{2bot}}) = 398.4 \text{ ft}^3$$

$$\text{Net Volume of Conc} = V_{concrete} := V_{FrustumNet} = 398.4 \text{ ft}^3$$

Stability of Footing:

$$\text{Cross-Sectional Area of Resisting Soil at Base of Foundation} = B_1 := B_{2bot} = 113.861 \text{ ft}^2$$

$$\text{Cross-Sectional Area of Resisting Soil at Top of Foundation (Minus Depth to Neglect)} = B_2 := 302.98 \text{ ft}^2$$

$$\text{Volume of Resisting Soil} = V_{Soil} := \frac{1}{3} \cdot ((D_{base}) \cdot (B_1 + B_2 + \sqrt{B_1 \cdot B_2})) - V_{concrete} = 773.28 \text{ ft}^3$$

$$\text{Weight of Concrete} = Wt_{conc} := V_{conc} \cdot \gamma_c = 63.17 \text{ kip}$$

$$\text{Weight of Resisting Soil} = Wt_{soil} := V_{Soil} \cdot \gamma_s = 85.06 \text{ kip}$$

$$\text{Total Resisting Weight of Soil & Conc} = Wt_{Total} := (DL_{f1} \cdot Wt_{conc} + 0.75 \cdot Wt_{soil}) = 120.65 \text{ kip}$$

$$\text{Uplift Interaction Ratio} = Usage := \left(\frac{U_{plift}}{Wt_{Total}} \right) = 0.75$$

$$UsageCheck := \text{if} \left(\frac{U_{plift}}{Wt_{Total}} \leq 1.05, \text{"Okay"}, \text{"No Good"} \right)$$

UsageCheck = "Okay"

Appendix B

Reference Information



EAST > North East > New England > New England West > SOUTH WINDSOR NORTH CT - water tank

Brauer, Mark - mark.brauer2@verizonwireless.com - 5/6/2021 9:28:39

Project Details

Carrier Aggregation:	false
MPT Id:	
eCIP-0:	false
Project Name:	5G L-Sub6 - Carrier Add
FUZE Project ID:	165600063
Designed Sector Carrier 4G:	15
Designed Sector Carrier 5G:	3
Additional Sector Carrier 4G:	N/A
Additional Sector Carrier 5G:	N/A
SiteTraker Project Id:	
FP Solution Type & Tech Type:	MODIFICATION;5G_L-Sub6-Prep
Suffix:	
RFDS Project Scope:	Sub 6 add CBRS add

Location Information

Site ID:	2578557
E-NodeB ID:	0068554.068554
PSLC:	469756
Switch Name:	
Tower Owner:	
Tower Type:	
Site Type:	MACRO
Street Address:	50 Plantation road
City:	East Windsor
State:	CT
Zip Code:	06016
County:	Hartford
Latitude:	41° 8' 7.56482972" N
Longitude:	72° 56' 48.2972" / 72° 33' 53.387" W

Antenna Summary

Added														
700	850	1900	AWS	CBRS	L-Sub6	Make	Model	Centerline	Tip Height	Azimuth	RET	4xRx	Inst. Type	Quantity
LTE	5G	LTE			COMMSCOPE	NHH-65B-R2B	102	105	140(B) 260(C)	true	true	PHYSICAL	3	
LTE	5G	LTE	5G		COMMSCOPE	NHHSS-65B-R2B	102	105	140(B) 260(C)	true	true	PHYSICAL	3	
				5G	Samsung	MT6407-77A	94	95.5	140(B) 260(C)	false	false	PHYSICAL	3	
 Removed														
700	850	1900	AWS	CBRS	L-Sub6	Make	Model	Centerline	Tip Height	Azimuth	RET	4xRx	Inst. Type	Quantity
LTE	5G	LTE			COMMSCOPE	NNHH-65B-R4	102	105	140(B) 260(C)	false	false	PHYSICAL	3	
		LTE			COMMSCOPE	NNHH-65B-R4	94	97	140(B) 260(C)	false	false	PHYSICAL	3	
 Retained														
700	850	1900	AWS	CBRS	L-Sub6	Make	Model	Centerline	Tip Height	Azimuth	RET	4xRx	Inst. Type	Quantity
													No data available.	
													Added: 9	Removed: 6
														Retained: 0

Equipment Summary

Added									
Equipment Type	Location	700	850	1900	AWS	CBRS	L-Sub6	Make	Model
Mount	Tower					Commscope			BASMINT-SBS-1-2
RRU	Tower				LTE	Samsung			CBRS RRH - RT4401-48A
RRU	Tower				5G	Samsung			MT6407-77A
Removed									
Equipment Type	Location	700	850	1900	AWS	CBRS	L-Sub6	Make	Model

Retained									
Equipment Type	Location	700	850	1900	AWS	CBRS	L-Sub6	Make	Model
RRU	Tower				LTE	LTE		Samsung	B2/B66A RRH-BR049 (RFV01U-D1A)
RRU	Tower				5G			Samsung	B5/B13 RRH-BR04C (RFV01U-D2A)
Hybrid Cable	Tower								
OVP Box	Tower								

No data available.

Service Info

700 MHz LTE		5G		5G	
Sector	01	02	03	01	02
Cell / ENode B ID	068554	140	260	20	140
Antenna Model	NNHH-65B-R4	NNHH-65B-R4	NNHH-65B-R4	NHH-65B-R2B	NHH-65B-R2B
Antenna Centerline(°ft)	102	102	102	102	102
Mechanical Down-Tilt(Deg)	0	0	0	0	0
Electrical Down-Tilt	4	2	4	4	4
Tip Height	105	105	105	105	105
Regulatory Power	68.01	65.85	68.01	73.6	73.6
Total ERP (W)				71.26	
TMA Make					
RUU Model	Samsung B5/B13 RRH-BR04C (RFV01U-D2A)	B5/B13 RRH-BR04C (RFV01U-D2A)	Samsung B5/B13 RRH-BR04C (RFV01U-D2A)	B5/B13 RRH-BR04C (RFV01U-D2A)	Samsung B5/B13 RRH-BR04C (RFV01U-D2A)
Number of Tx, Rx, Lines	4,4	4,4	4,4	4,4	4,4
Position	1967093	1967283	1967288	10225856	10225859
Transmitter Id	ATOLL_AP1	ATOLL_AP1	ATOLL_AP1	ATOLL_AP1	ATOLL_AP1
Source					
350 MHz 5GNR					
Sector	0001	0002	0003	0001	0002
Cell / ENode B ID	068554	140	260	20	140
Antenna Model	NNHH-65B-R4	NNHH-65B-R4	NNHH-65B-R4	NHH-65B-R2B	NHH-65B-R2B
Antenna Centerline(°ft)	20	140	068554	068554	068554
Mechanical Down-Tilt(Deg)	0	0	0	0	0
Electrical Down-Tilt	4	2	4	4	4
Tip Height	105	105	105	105	105
Regulatory Power	324.8	316.68	324.8	306.07	290.63
Total ERP (W)					289.96
TMA Make					
RUU Model	Samsung B5/B13 RRH-BR04C (RFV01U-D2A)	B5/B13 RRH-BR04C (RFV01U-D2A)	Samsung B5/B13 RRH-BR04C (RFV01U-D2A)	B5/B13 RRH-BR04C (RFV01U-D2A)	Samsung B5/B13 RRH-BR04C (RFV01U-D2A)
Number of Tx, Rx, Lines	4,4	4,4	4,4	4,4	4,4
Position	10225644	10225645	10225646	10225853	10225854
Transmitter Id	ATOLL_AP1	ATOLL_AP1	ATOLL_AP1	ATOLL_AP1	ATOLL_AP1
Source					
1900 MHz LTE					
Sector	01	02	03	01	02
Cell / ENode B ID	068554	140	260	20	140
Antenna Model	NNHH-65B-R4	NNHH-65B-R4	NNHH-65B-R4	NHH-65B-R2B	NHH-65B-R2B
Antenna Centerline(°ft)	94	94	94	102	102
Mechanical Down-Tilt(Deg)	0	0	0	0	0
Electrical Down-Tilt	2	2	2	2	2
Tip Height	97	97	97	105	105
Regulatory Power	224.16	224.16	224.16	267.15	267.15
Total ERP (W)					
TMA Make					
RUU Model	Samsung B2/B66A RRH-BR049 (RFV01U-D1A)	B2/B66A RRH-BR049 (RFV01U-D1A)	Samsung B2/B66A RRH-BR049 (RFV01U-D1A)	B2/B66A RRH-BR049 (RFV01U-D1A)	Samsung B2/B66A RRH-BR049 (RFV01U-D1A)
Number of Tx, Rx, Lines	4,4	4,4	4,4	4,4	4,4
Position	1967095	1967285	1967290	10225857	10225860
Transmitter Id	ATOLL_AP1	ATOLL_AP1	ATOLL_AP1	ATOLL_AP1	ATOLL_AP1
Source					


Callsigns Per Antenna

Sector	Antenna M#	Antenna Mc	Ant Cl	Tip Height	Azimuth (T)	Electrical Tilt	Mechanical Tilt	Gain	Beamwidth	Regulatory Power	700	850	1900	2100	28 GHz	31 GHz	39 GHz
No data available.																	

Call/signs

Callsign	Market	Radio Code	Market Number	Block	State	County	Licensee Name	Wholly Owned	Total MHz	Freq Range 1	Freq Range 2	Freq Range 3	Freq Range 4	Regulatory Power	Threshold (W)	POPs/Sq Mi	Status	Action	Approved for Insvc
WQJQ689	Northeast	WU	REA001	C	CT	Hartford	Cellco Partnership	Yes	22.000	746.000-757.000	.000-.000	.000-.000	.000-.000	73.6	1000	1216.19	Active	added	Yes
KNKA404	Hartford-New Britain-Bristol, CT	C.L	CMA032	A	CT	Hartford	Cellco Partnership	Yes	25.000	824.000-835.000	845.000-846.500	869.000-880.000	890.000-891.500	306.07	400	1216.19	Active	added	Yes
WPOJ730	Hartford, CT	CW	BTA184	C	CT	Hartford	Cellco Partnership	Yes	15.000	1895.000-1902.500	1975.000-1982.500	.000-.000	.000-.000	267.15	1640	1216.19	Active	added	Yes
KNLH251	Hartford, CT	CW	BTA184	F	CT	Hartford	Cellco Partnership	Yes	10.000	1890.000-1895.000	1970.000-1975.000	.000-.000	.000-.000	267.15	1640	1216.19	Active	added	Yes
CBRS_CALL	UNLICENSED 3.5 GHz	UNLICENSED	UNLICENSED	CT		Hartford	UNLICENSED	UNLICENSED	UNLICENSED	UNLICENSED	UNLICENSED	UNLICENSED	UNLICENSED	UNLICENSED	12.78	1216.19	Active	added	No
WRLD515	D09003 - Hartford, CT	PL	D09003	0	CT	Hartford	Yes	100.000	350.000-365.000	.000-.000	.000-.000	.000-.000	.000-.000	12.78	.00	Active	added	Yes	
WRLD514	D09003 - Hartford, CT	PL	D09003	0	CT	Hartford	LP	LP	LP	LP	LP	LP	LP	LP	LP	LP	LP	LP	
WRLD513	D09003 - Hartford, CT	PL	D09003	0	CT	Hartford	Yes	100.000	350.000-365.000	.000-.000	.000-.000	.000-.000	.000-.000	12.78	.00	Active	added	Yes	
WQGB276	Hartford-New Britain-Bristol, CT	AW	CMA032	A	CT	Hartford	Cellco Partnership	Yes	20.000	1710.000-1720.000	2110.000-2120.000	.000-.000	.000-.000	143.06	1640	1216.19	Active	added	Yes
WQGA906	New York-No. New Jer.-Long Island, NY-NJ-CT-PA-MA-	AW	BEA010	B	CT	Hartford	Cellco Partnership	Yes	20.000	1720.000-1730.000	.000-.000	.000-.000	.000-.000	143.06	1640	1216.19	Active	added	Yes
WPOH943	Hartford, CT	L.D	BTA184	A	CT	Hartford	Cellco Partnership	Yes	300.000	2910.000-2925.000	3075.000-3125.000	.000-.000	.000-.000	.000-.000	.000-.000	1216.19	Active		No
WPLM398	Hartford, CT	L.D	BTA184	B	CT	Hartford	Cellco Partnership	Yes	150.000	3000.000-3105.000	3225.000-3300.000	.000-.000	.000-.000	.000-.000	.000-.000	1216.19	Active		No
WRBA708	Hartford, CT	UU	BTA184	L1	CT	Hartford	Cellco Partnership	Yes	325.000	2790.000-2795.000	2770.000-2785.000	.000-.000	.000-.000	.000-.000	.000-.000	1216.19	Active		Yes
WRBA709	Hartford, CT	UU	BTA184	L2	CT	Hartford	Cellco Partnership	Yes	325.000	2795.000-2850.000	2850.000-2890.000	.000-.000	.000-.000	.000-.000	.000-.000	1216.19	Active		Yes

WRHD609	New York, NY	UU	PEA001	M1	CT	Hartford	um, LLC	Straight Path	100.000	.000-000	.000-000	.000-000	1216.19	Active	Yes
WRHD610	New York, NY	UU	PEA001	M10	CT	Hartford	um, LLC	Straight Path	100.000	.000-000	.000-000	.000-000	1216.19	Active	Yes
WRHD611	New York, NY	UU	PEA001	M2	CT	Hartford	um, LLC	Straight Path	100.000	.000-000	.000-000	.000-000	1216.19	Active	Yes
WRHD612	New York, NY	UU	PEA001	M3	CT	Hartford	um, LLC	Straight Path	100.000	.000-000	.000-000	.000-000	1216.19	Active	Yes
WRHD613	New York, NY	UU	PEA001	M4	CT	Hartford	um, LLC	Straight Path	100.000	.000-000	.000-000	.000-000	1216.19	Active	Yes
WRHD614	New York, NY	UU	PEA001	M5	CT	Hartford	um, LLC	Straight Path	100.000	.000-000	.000-000	.000-000	1216.19	Active	Yes
WRHD615	New York, NY	UU	PEA001	M6	CT	Hartford	um, LLC	Straight Path	100.000	.000-000	.000-000	.000-000	1216.19	Active	Yes
WRHD616	New York, NY	UU	PEA001	M7	CT	Hartford	um, LLC	Straight Path	100.000	.000-000	.000-000	.000-000	1216.19	Active	Yes
WRHD617	New York, NY	UU	PEA001	M8	CT	Hartford	um, LLC	Straight Path	100.000	.000-000	.000-000	.000-000	1216.19	Active	Yes
WRHD618	New York, NY	UU	PEA001	M9	CT	Hartford	um, LLC	Straight Path	100.000	.000-000	.000-000	.000-000	1216.19	Active	Yes
WRHD619	New York, NY	UU	PEA001	N1	CT	Hartford	um, LLC	Straight Path	100.000	.000-000	.000-000	.000-000	1216.19	Active	No
PEND1050	Northeast	CC	REA001	A	CT	Hartford	Cellco Partnership	Yes	100.000	.000-000	.000-000	.000-000	1216.19	Active	No



Upper level with SBS bracket



Lower level



July 7, 2021

Verizon
20 Alexander Drive
Wallingford, CT 06492

Attn: Mr. David Vivian

Re: Mount Analysis Report – Lsub6
Verizon Wireless Site I.D.: South Windsor North CT
50 Plantation Road
East Windsor, CT 06016

Project/Location Code: 20171645681/469756
VZW FUZE I.D.: 16560063
APT Filing No. CT141_12500

Dear Mr. Vivian,

All-Points Technology Corp. (APT), a professional engineering corporation licensed in the State of Connecticut, has been retained by Verizon to assess the structural adequacy of the mounting assembly and its connection to the existing host structure to support the proposed equipment modification. An evaluation of the existing host structure is to be provided under separate cover.

Details of the proposed antenna and appurtenance installation are included within the table on the following page. Reference is made to the Construction Drawings prepared by this office, marked Rev 0, dated 07/07/21.

The following information was utilized in the preparation of this assessment:

New Build Construction Drawings, prepared by APT, marked Rev1, dated 11/06/20.
Mount Structural Analysis & Design Report, prepared by APT, dated 10/28/20.

The structural review has been prepared in accordance with the following design standards:

ASCE/SEI 7-10 – Minimum Design Loads for Buildings and Other Structures
AISC - American Institute of Steel Construction Manual of Steel Construction, 14th Ed.
IBC 2015 – as amended by the 2018 Connecticut State Building Code.
ANSI/TIA-222-H – Structural Standard for Antenna Supporting Structures, Antennas and Small Wind Turbine Support Structures

The structural review has been prepared utilizing the following design criteria:

125 mph (3-second gust), Ultimate Wind Speed (equivalent to 97mph Nominal).
50 mph (3-second gust), Design Wind Speed with 1.50" Design Ice Thickness
Risk Category II
Exposure Category C
Roof Live Load, LLr = 20 psf
Minimum Roof Snow Load = 30 psf

Mount Analysis Report
 Verizon Wireless Site I.D.: South Windsor North CT
 50 Plantation Road
 East Windsor, CT 06016

July 7, 2021
 Page 2
 APT Project #CT141_12500

The existing and proposed Verizon antenna/appurtenance and mount assembly loading consists of the following equipment (proposed equipment/equipment to be relocated indicated in **bold** text):

Antenna and Appurtenance Make/Model	Quantity	Status	Mount Type	Centerline
Commscope NHH-65B-R2B ² panel antennas	3	P	Three (3) custom mount assemblies attached to existing decommissioned water tank leg.	102.0 ft± AGL
Commscope NHHSS-65B-R2B ² panel antennas	3	P		94.0 ft± AGL
Samsung MT6407-77A panel antennas	3	P		n/a
Samsung B5/B13 RRH-BR04C (RFV01U-D2A) Remote Radio Heads (RRHs)	3	P		
Samsung B2/B66a RRH-BR049 (RFV01U-D1A) Remote Radio Heads (RRHs)	3	P		
Samsung CBRS-RT4401-48A Remote Radio Heads (RRHs)	3	P		
Raycap RHSDC-3315-PF-48 (6OVP)	3	P		
6x12 L.I. Hybrid Fiber Cable	3	P	n/a	n/a

Notes:

1. ETR = Existing to Remain; ERL = Exist to be Relocated; P = Proposed.
2. Mount antennas via Commscope Side-by-Side Mounts (P/N: BSAMNT-SBS-1-2).
3. The above proposed equipment supersedes the equipment indicated within the new build construction drawings prepared by this office, marked Rev1, dated 11/06/20.

The findings of this review are based upon comparative review of the proposed equipment loading, referenced design documentation, a rigorous mount analysis. Under the proposed loading, the maximum usage of the existing mounting assemblies as compared to the mount rating/capacity is 61%. Additionally, the proposed loading is less than the loading utilized in the referenced original new build design documentation. In conclusion, we find that the custom mount assemblies are adequate to support the proposed equipment modification.

Sincerely,
 All-Points Technology Corp. P.C.



Michael S. Trodden, P.E.
 Sr. Structural Engineer



Appendix A

Design Criteria

(APPENDIX N) MUNICIPALITY - SPECIFIC STRUCTURAL DESIGN PARAMETERS													
Municipality	Ground Snow Load (psf)	Wind Design Parameters											Hurricane-Prone Regions
		MCE Spectral Acceleration s (%g)		Ultimate Design Wind Speeds, V_{ult} (mph)			Nominal Design Wind Speeds, V_{asd} (mph)			Wind-Borne Debris Regions ¹			
		S_s	S_1	Risk Cat.I	Risk Cat.II	Risk Cat. III-IV	Risk Cat. I	Risk Cat. II	Risk Cat. III-IV	Risk Cat. II & III except Occup I-2	Risk Cat. III Occup I-2 & Risk Cat. IV		
East Hampton	30	0.177	0.062	120	130	140	93	101	108			Yes	
East Hartford	30	0.180	0.064	115	125	135	89	97	105			Yes	
East Haven	30	0.182	0.062	120	130	140	93	101	108			Type B Yes	
East Lyme	30	0.164	0.059	125	135	145	97	105	112	Type B	Type A	Yes	
Easton	30	0.215	0.066	110	120	130	85	93	101			Yes	
East Windsor	35	0.177	0.064	115	125	135	89	97	105			Yes	
Ellington	35	0.176	0.064	115	125	135	89	97	105			Yes	
Enfield	35	0.176	0.065	110	125	130	85	97	101			Yes	
Essex	30	0.168	0.059	120	135	145	93	105	112			Type A Yes	
Fairfield	30	0.215	0.065	115	125	135	89	97	105			Type B Yes	
Farmington	35	0.183	0.064	115	125	135	89	97	105			Yes	
Franklin	30	0.171	0.061	120	130	140	93	101	108			Type A Yes	
Glastonbury	30	0.180	0.063	115	125	135	89	97	105			Yes	
Goshen	40	0.181	0.065	105	115	125	81	89	97				
Granby	35	0.176	0.065	110	120	130	85	93	101			Yes	
Greenwich	30	0.259	0.070	110	120	130	85	93	101			Yes	
Griswold	30	0.168	0.060	125	135	145	97	105	112			Type A Yes	
Groton	30	0.160	0.058	125	135	145	97	105	112	Type B	Type A	Yes	
Guilford	30	0.176	0.061	120	130	140	93	101	108			Type B Yes	
Haddam	30	0.175	0.061	120	130	140	93	101	108			Yes	
Hamden	30	0.185	0.063	115	125	135	89	97	105			Yes	
Hampton	35	0.172	0.062	120	130	140	93	101	108			Yes	
Hartford	30	0.181	0.064	115	125	135	89	97	105			Yes	
Hartland	40	0.175	0.065	110	120	125	85	93	97			Yes	
Harwinton	35	0.183	0.065	110	120	130	85	93	101			Yes	
Hebron	30	0.177	0.063	120	130	140	93	101	108			Yes	
Kent	40	0.188	0.065	105	115	120	81	89	93				
Killingly	40	0.171	0.062	120	130	140	93	101	108			Yes	
Killingworth	30	0.173	0.061	120	130	140	93	101	108			Yes	
Lebanon	30	0.173	0.062	120	130	140	93	101	108			Yes	
Ledyard	30	0.163	0.059	125	135	145	97	105	112			Type A Yes	
Lisbon	30	0.169	0.061	125	135	145	97	105	112			Type A Yes	
Litchfield	40	0.184	0.065	110	120	125	85	93	97			Yes	
Lyme	30	0.164	0.059	125	135	145	97	105	112			Type A Yes	
Madison	30	0.173	0.060	120	130	140	93	101	108			Type B Yes	
Manchester	30	0.178	0.064	115	125	135	89	97	105			Yes	
Mansfield	35	0.173	0.062	120	130	140	93	101	108			Yes	
Marlborough	30	0.177	0.062	120	130	140	93	101	108			Yes	
Meriden	30	0.183	0.063	115	125	135	89	97	105			Yes	
Middlebury	35	0.191	0.064	110	120	130	85	93	101			Yes	
Middlefield	30	0.181	0.063	115	125	135	89	97	105			Yes	
Middletown	30	0.180	0.063	115	130	135	89	101	105			Yes	
Milford	30	0.194	0.063	115	125	135	89	97	105			Type B Yes	
Monroe	30	0.205	0.065	110	120	130	85	93	101			Yes	

ASCE 7 Hazards Report

Address:



50 Plantation Rd
Broad Brook, Connecticut
06016

Standard: ASCE/SEI 7-16

Risk Category: II

Soil Class:
Elevation: 158.11 ft (NAVD 88)

Latitude: 41.875463

Longitude: -72.564802


Ice

Results:

Ice Thickness: 1.50 in.

Concurrent Temperature: 5 F

Gust Speed: 50 mph

Data Source: Standard ASCE/SEI 7-16, Figs. 10-2 through 10-8

Date Accessed: Tue Jun 08 2021

Ice thicknesses on structures in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.

Values provided are equivalent radial ice thicknesses due to freezing rain with concurrent 3-second gust speeds, for a 500-year mean recurrence interval, and temperatures concurrent with ice thicknesses due to freezing rain. Thicknesses for ice accretions caused by other sources shall be obtained from local meteorological studies. Ice thicknesses in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.

The ASCE 7 Hazard Tool is provided for your convenience, for informational purposes only, and is provided "as is" and without warranties of any kind. The location data included herein has been obtained from information developed, produced, and maintained by third party providers; or has been extrapolated from maps incorporated in the ASCE 7 standard. While ASCE has made every effort to use data obtained from reliable sources or methodologies, ASCE does not make any representations or warranties as to the accuracy, completeness, reliability, currency, or quality of any data provided herein. Any third-party links provided by this Tool should not be construed as an endorsement, affiliation, relationship, or sponsorship of such third-party content by or from ASCE.

ASCE does not intend, nor should anyone interpret, the results provided by this Tool to replace the sound judgment of a competent professional, having knowledge and experience in the appropriate field(s) of practice, nor to substitute for the standard of care required of such professionals in interpreting and applying the contents of this Tool or the ASCE 7 standard.

In using this Tool, you expressly assume all risks associated with your use. Under no circumstances shall ASCE or its officers, directors, employees, members, affiliates, or agents be liable to you or any other person for any direct, indirect, special, incidental, or consequential damages arising from or related to your use of, or reliance on, the Tool or any information obtained therein. To the fullest extent permitted by law, you agree to release and hold harmless ASCE from any and all liability of any nature arising out of or resulting from any use of data provided by the ASCE 7 Hazard Tool.

Appendix B

Existing Mount Analysis



Project ID: CT141_12500
Site Name: South Windsor North CT
Date: 7/14/2021

(Based on ANSI/TIA-222-H-2018)

<u>Site Name:</u>	South Windsor North CT		
<u>Site Address:</u>	50 Plantation Road East Windsor, CT 06016		
<u>Site County:</u>	Hartford		

Design Criteria:

Risk Category =	II		<i>Table 1.5-1</i>
Exposure Category =	C		<i>Section 26.7.3</i>
Ultimate Design Wind Speed, V =	125	mph	<i>2018 CT SBC, Appendix N</i>
Design Wind Speed with Ice, V _i =	50	mph	<i>Fig. B-9</i>
Design Ice Thickness, t _i =	1.50	in	<i>Fig. B-9</i>
Importance Factor, I =	1.00		<i>Table 2-3</i>
Basic Wind Speed, V _m =	30	mph	<i>Section 16.3</i>
Maintenance Load, L _m =	500.0	lbs	<i>Section 16.3</i>
Maintenance Load, L _v =	250.0	lbs	<i>Section 16.3</i>

Building Information:

Antenna Centerline, z =	102.0	ft., +/-	
Host Structure Height, H =	132.5	ft., +/-	
Bulkhead/Parapet Height, H _{pp} =	-	ft., +/-	(max.)
Largest Windward Face of Structure, W _s =	-	ft., +/-	

Wind Pressure Analysis:

$$q_z = 0.00256 K_z K_{zt} K_s K_e K_d V^2 \quad \text{Section 2.6.11.6}$$

K_z : **See Next Sheet**

<u>K_{zt}</u> :	K_{zt} = 1.00	<i>Section 2.6.6</i>
<u>K_s</u> :	K_s = 1.00	<i>Section 2.6.7</i>
<u>K_e</u> :	K_e = 1.00	<i>Section 2.6.8</i>
<u>K_d</u> :	K_d = 0.95	<i>Section 16.6</i>

$$q_z' = 38.00 \text{ psf}$$

$$F = q_z G_h (EPA)_A = q_z G_h K_a [(EPA)_N \cos^2(\Theta) + (EPA)_T \sin^2(\Theta)] \quad \text{Section 2.6.11.2}$$

$$G_h = 1.00 \quad \text{Section 16.6}$$

$$K_a = 0.90 \quad \text{Section 16.6}$$



(Based on ANSI/ETIA-222-H-2018)

Designer Criteria: (From Previous Sheet)

$q_i' = 38.00 \text{ psf}$
 $q_{i\prime} = 6.08 \text{ psf}$
 $q_{iw} = 2.19 \text{ psf}$
 $t_i = 1.50 \text{ in}$

Project ID: CT141_12500
 Site Name: South Windsor North CT
 Date: 7/14/2021

Description	#/Sector	Elev. z, ft	K_c	q_{iw} , psf	Dimensions			Flat Panel Front Coefficient			Flat Panel Side Coefficient								
					Height, in	Width, in	Depth, in	Weight, lbs	Area, ft^2	Aspect Ratio	C_a	C_{Aa}	Front Wind Force, lbs						
MT640-77A NHH-65B-R2B	1.0	94.0	1.249	47.47	35.1	16.1	5.5	87.1	3.92	2.180	1.20	4.71	1.341	6.382	1.37	1.840	202.0	79.0	87.1
NHH-65B-R2B	1.0	102.0	1.271	48.29	72.0	11.9	7.1	56.3	5.92	6.073	1.36	8.05	3.542	10.155	1.51	5.331	350.0	232.0	56.3
NHH-65B-R2B	1.0	102.0	1.271	48.29	72.0	11.9	7.1	63.6	5.92	6.073	1.36	8.05	3.561	10.099	1.50	5.354	350.0	233.0	63.6
B2/B66A RRH-BR049 (RFV01U-D1A)	1.0	94.0	1.249	47.47	14.9	14.9	10.0	97.5	1.54	1.000	1.20	1.85	1.039	1.484	1.20	1.247	80.0	54.0	97.5
B2/B13 RRH-BR04C (RFV01U-D2A)	1.0	94.0	1.249	47.47	14.9	14.9	8.1	82.0	1.54	1.000	1.20	1.85	0.842	1.830	1.20	1.011	80.0	44.0	82.0
CBRS RT4401-48A RRH 60VP	1.0	94.0	1.249	47.47	10.6	8.9	3.0	11.0	0.66	1.191	1.20	0.79	0.221	3.533	1.25	0.275	34.0	12.0	11.0
CBRS RT4401-48A RRH 60VP	1.0	102.0	1.271	48.29	19.2	16.5	12.6	32.0	2.20	1.162	1.20	2.64	1.678	1.522	1.20	2.014	115.0	88.0	32.0

Description	#/Sector	Elev. z, ft	K_c	q_{iw} , psf	Dimensions			Flat Panel Front Coefficient			Flat Panel Side Coefficient								
					Height, in	Width, in	Depth, in	Weight, lbs	Area, ft^2	Aspect Ratio	C_a	C_{Aa}	Front Wind Force, lbs						
MT640-77A NHH-65B-R2B	1.0	94.0	1.249	7.95	1.67	38.43	17.01	121.7	5.19	2.26	0.70	3.630	2.357	2.26	0.70	1.650	25.0	12.0	208.8
NHH-65B-R2B	1.0	102.0	1.271	7.727	1.68	75.33	13.81	139.4	7.96	5.46	0.77	6.091	5.464	5.46	0.77	4.184	43.0	30.0	255.8
NHH-65B-R2B	1.0	102.0	1.271	7.727	1.68	75.33	13.83	139.7	7.96	5.45	0.77	6.090	5.484	5.45	0.77	4.198	43.0	30.0	263.3
B2/B66A RRH-BR049 (RFV01U-D1A)	1.0	94.0	1.249	7.95	1.67	18.23	17.97	60.7	2.31	1.01	0.70	1.616	1.693	1.01	0.70	1.185	12.0	9.0	158.2
B2/B13 RRH-BR04C (RFV01U-D2A)	1.0	94.0	1.249	7.95	1.67	18.23	16.98	57.6	2.31	1.07	0.70	1.616	1.452	1.07	0.70	1.017	12.0	7.0	139.6
CBRS RT4401-48A RRH 60VP	1.0	94.0	1.249	7.95	1.67	13.93	9.39	26.1	1.18	0.70	0.828	0.612	1.48	0.70	0.429	6.0	3.0	37.1	
CBRS RT4401-48A RRH 60VP	1.0	102.0	1.271	7.727	1.68	22.54	20.76	86.5	3.11	1.09	0.70	2.176	2.498	1.09	0.70	1.748	16.0	13.0	118.5

Description	#/Sector	Elev. z, ft	K_c	q_{iw} , psf	Dimensions			Flat Panel Front Coefficient			Flat Panel Side Coefficient								
					Height, in	Width, in	Depth, in	Weight, lbs	Area, ft^2	Aspect Ratio	C_a	C_{Aa}	Front Wind Force, lbs						
MT640-77A NHH-65B-R2B	1.0	94.0	1.249	2.73	35.1	16.1	5.5	87.1	3.92	2.180	1.20	4.71	1.341	6.382	1.37	1.840	12.0	5.0	87.1
NHH-65B-R2B	1.0	102.0	1.271	2.78	72.0	11.9	7.1	63.6	5.92	6.073	1.36	8.05	3.542	10.155	1.51	5.331	21.0	14.0	56.3
NHH-65B-R2B	1.0	102.0	1.271	2.78	72.0	11.9	7.1	63.6	5.92	6.073	1.36	8.05	3.561	10.099	1.50	5.354	21.0	14.0	63.6
B2/B66A RRH-BR049 (RFV01U-D1A)	1.0	94.0	1.249	2.73	14.9	14.9	10.0	97.5	1.54	1.000	1.20	1.85	1.039	1.484	1.20	1.247	5.0	4.0	97.5
B2/B13 RRH-BR04C (RFV01U-D2A)	1.0	94.0	1.249	2.73	14.9	14.9	8.1	82.0	1.54	1.000	1.20	1.85	0.842	1.830	1.20	1.011	5.0	3.0	82.0
CBRS RT4401-48A RRH 60VP	1.0	102.0	1.271	2.78	19.2	16.5	12.6	32.0	2.20	1.162	1.20	2.64	1.678	1.522	1.20	2.014	7.0	6.0	32.0

Notes:

1- Includes mounting bracket weights.



Mounting Assembly Evaluation:

Mounting Assembly Evaluation:

(Based on NSTD-445 "Antenna Mounting System Classification Standard")

Mount Classification:	M	1150 (F)	R	1100 (Fz)	-4[6]
Loading Condition	Normal Direction	lbs	Trans. Direction	lbs	Vert. Direction
Extreme Wind	1.00(F)	1150	1.00(F)	1150	0.50(F)
Extreme Ice	0.25(Fz)	275	0.25(Fz)	275	1.00(Fz)
Maintenance	0.10(F)	115	0.10(F)	115	0.50(F)
Loading Condition	Description	Load, lbs			
L _m	At each mounting location, individual LCs	500			
L _v	At ends of each horizontal mounting members	250			

Since the proposed modification does not exceed the design loading per the previous design report, the existing mounting assembly is adequate to support the proposed equipment modification.

Loading Condition	Normal Direction		Trans. Direction	Vert. Direction		
	lbs	%		lbs	%	
Wind Load	700.0	60.9%	465.0	40.4%	119.9	20.9%
Ice Load	86.0	31.3%	60.0	21.8%	39.1	36.3%
Maintenance	42.0	36.5%	28.0	24.3%	11.9	20.9%

Project ID: CT141_12500
Site Name: South Windsor North CT
Date: 7/14/2021

ATTACHMENT 5



The Assessor's office is responsible for the maintenance of records on the ownership of properties. Assessments are computed at 70% of the estimated market value of real property at the time of the last revaluation which was 2017.



Information on the Property Records for the Municipality of East Windsor was last updated on 7/2/2021.

Property Summary Information

- [Parcel Data And Values](#)
- [Outbuildings](#)
- [Sales](#)

Parcel Information

Location:	50 PLANTATION RD	Property Use:	Vacant Land	Primary Use:	Commercial Vacant Land
Unique ID:	01162500	Map Block Lot:	016 50 001C	Acres:	0.78
490 Acres:	0.00	Zone:	A-1	Volume / Page:	0231/0053
Developers Map / Lot:		Census:	4842000		

Value Information

Appraised Value Assessed Value

Land	245,276	171,690
Buildings	0	0
Detached Outbuildings	21,368	14,960
Total	266,644	186,650

Owner's Information

Owner's Data

PLANTATION PROPERTIES LLC
P O BOX 542
BROAD BROOK CT 06016-0542

Detached Outbuildings

Type: Year Built: Length: Width: Area:

Pump House Utility 1960 154

Owner History - Sales

Owner Name	Volume	Page	Sale Date	Deed Type	Sale Price
PLANTATION PROPERTIES LLC	0231	0053	09/27/2001		\$1

Building Permits

Permit Number Permit Type Date Opened Reason

Google Map

Unique Id:

01162500

Location:

50 PLANTATION

MBL:

016 50 001C

Primary Use:

Commercial Vac

Zone:

A-1

Acres:

0.78

Appraised Value:

\$266,644

Assessed Value:

\$186,650

[Back To Search](#)

[Print View](#)

Information Published With Permission From The Assessor

ATTACHMENT 6



SOUTH WINDSOR NORTH

Certificate of Mailing — Firm

Name and Address of Sender		TOTAL NO. of Pieces Listed by Sender	TOTAL NO. of Pieces Received at Post Office™	Affix Stamp Here <i>Postmark with Date of Receipt.</i>		
Kenneth C. Baldwin, Esq. Robinson & Cole LLP 280 Trumbull Street Hartford, CT 06103		3	3	 08/16/2021 US POSTAGE \$002.89  ZIP 06103 041L12203987		
Postmaster, per (name of receiving employee) 						
USPS® Tracking Number Firm-specific Identifier	Address (Name, Street, City, State, and ZIP Code™)		Postage	Fee	Special Handling	Parcel Airlift
1.	Jason E. Bowsza, First Selectman Town of East Windsor 11 Rye Street Broad Brook, CT 06016					
2.	Mike D'Amato, Acting Planner Town of East Windsor 11 Rye Street Broad Brook, CT 06016					
3.	Plantation Properties, LLC P.O. Box 542 Broad Brook, CT 06016					
4.						
5.						
6.						