

### RACHEL A. SCHWARTZMAN

Please Reply To: Bridgeport
Writer's Direct Dial: (203) 337-4110
E-Mail: rschwartzman@cohenandwolf.com

October 7, 2014

Attorney Melanie Bachman Acting Executive Director Connecticut Siting Council Ten Franklin Square New Britain, CT 06501



RECEIVED OCT 0 8 2011

CONNECTICUT SITING COUNCIL

Re: EM-T-MOBILE-051-130325

T-Mobile Site ID CT11317B

280 Morehouse Drive, Fairfield, CT

Notice of Compliance with Conditions and Construction Completion

Dear Attorney Bachman:

The Connecticut Siting Council ("Council") acknowledged the above referenced T-Mobile Northeast LLC ("T-Mobile") notice of exempt modification on May 1, 2013.

The Council imposed the following condition in its acknowledgment:

- The proposed coax shall be installed in accordance with the recommendation in the Structural Analysis Report prepared by American Tower Corporation, dated November 30, 2012 and stamped by Raphael Mohamed; and
- Not more than 45 days following completion of the antenna installation, T-Mobile shall provide documentation certified by a professional engineer that its installation complied with the recommendation of the structural analysis.

T-Mobile has complied with each of these conditions as evidenced by the PE Close Out Letter, dated September 12, 2014, and the Tower Modification Certification, dated September 11, 2104, attached hereto.

In addition, T-Mobile hereby notifies the Council that construction of the acknowledged modifications were complete as of August 11, 2014.

Please don't hesitate to contact me with any questions.



October 7, 2014 CT11317B Page 2

Sincerely,
Raud Scht

Rachel A. Schwartzman, Esq.

cc: Samuel Simons, T-Mobile Mark Richard, T-Mobile Alex Giannaras, HPC Wireless Julie Kohler, Esq.



Centered on Solutions\*\*

September 11, 2014

Mr. Bill Abbott **HPC Wireless** 22 Shelter Rock Lane Danbury, CT 06810

**Re: Tower Modification Certification** 

Project: T-Mobile CT11317B

280 Morehouse Road, Fairfield, CT

Tower Owner: **Northeast Utilities** 

107 Selden Street, Berlin, CT 06037

Engineer: **Centek Engineering** 

63-2 North Branford Road, Branford, CT

Centek Project No.: 13344.000

Dear Mr. Abbott,

We are providing this "Tower Modification Certification" with regard to the structural components at the above referenced project.


The following are the basis for substantiating compliance with the tower modification documents prepared by this office (Centek Project Number: 12066.CO1):

- Review of the Centek Engineering Structural Analysis dated 10/19/2012 Rev-2.
- Review of the Centek Engineering Reinforcement Drawings S-1 and S-2 dated 02/20/2013.
- Review of the Centek Engineering Letter of Professional Opinion dated 08/28/2014.
- Field observations by Centek Engineering personnel on 03/13/2014 of the completed modifications.

The modification design prepared by this office demonstrates the tower will not exceed 100 percent of the post construction structural rating. The work under this Contract has been reviewed and found, to the Engineer's best knowledge, information and belief, to be completed in general compliance with the documents referenced above.

Carlo F. Centore, PE Senior Project Manager Cc: James Quicksell (Tectonic Engine

Sincerely.





1279 Route 300 Newburgh, NY 12550 (845) 567-6656 FAX: (845) 567-8703 www.tectonicengineering.com

Sam Simons
Engineering Development - Connecticut
T-Mobile
35 Griffin Road South
Bloomfield, CT 06002
sam.simons@t-mobile.com

September 12, 2014

RF.

PE Close Out Letter

EM-T-MOBILE # 051-130325 /T-Mobile Site ID # CT11317B

Dear Mr. Simons:

Tectonic Engineering & Surveying Consultants, P.C. ("Tectonic") has completed its post-construction review of the above-referenced site to determine whether T-Mobile complied with conditions imposed by the Connecticut Siting Council's (the "Council") acknowledgment letter, dated May 1, 2013 ("the Acknowledgment Letter"). Our compliance review included the following: the Acknowledgment Letter, the approved tower structural analysis report by Centek Engineering dated October 19, 2012 (the "Structural Analysis"), the approved design plans by Tectonic dated May 10, 2013, and the tower modification certification letter by Centek Engineering dated September 11, 2014 (the "Certification Letter").

On behalf of Tectonic, based on my review of the information, I, Manojkumar B. Patel, licensed professional engineer number 22038, certify that to the best of my knowledge, T-Mobile work complied with the recommendations of the approved Structural Analysis.

Specifically, as required by the Acknowledgment Letter, T-Mobile work complied with the following structural conditions imposed by the Council as detailed in the Certification Letter:

 A signed letter from a Professional Engineer duly licensed in the State of Connecticut shall be submitted to the Council to certify that the recommended modifications have been completed and the structural and foundation do not exceed 100 percent of the post-construction structural rating.

Should you have any questions regarding the foregoing review, please contact me directly at 845-567-6656 ext. 2808.

Very truly yours,

Manojkumar B. Patel, P.E.

Sr. Project Manager

Cc: Alex Giannaras (HPC Wireless)



### STATE OF CONNECTICUT

### CONNECTICUT SITING COUNCIL

Ten Franklin Square, New Britain, CT 06051 Phone: (860) 827-2935 Fax: (860) 827-2950 E-Mail: siting.council@ct.gov www.ct.gov/csc

May 1, 2013

Julie D. Kohler, Esq. Cohen and Wolf, P.C. 1115 Broad Street Bridgeport, CT 06604

RE: **EM-T-MOBILE-051-130325** – T-Mobile Northeast LLC notice of intent to modify an existing telecommunications facility located at 280 Morehouse Drive, Fairfield, Connecticut.

### Dear Attorney Kohler:

The Connecticut Siting Council (Council) hereby acknowledges your notice to modify this existing telecommunications facility, pursuant to Section 16-50j-73 of the Regulations of Connecticut State Agencies with the following conditions:

- Prior to antenna installation, the foundation reinforcements depicted Section 4 of the Structural Analysis prepared Centek Engineering dated October 19, 2012, and stamped by Carlo Centore shall be implemented;
- Within 45 days following completion of the antenna installation, a signed letter from a Professional Engineer duly licensed in the State of Connecticut shall be submitted to the Council to certify that the recommended modifications have been completed and the structure and foundation do not exceed 100 percent of the post-construction structural rating;
- Any deviation from the proposed modification as specified in this notice and supporting materials with Council shall render this acknowledgement invalid;
- Any material changes to this modification as proposed shall require the filing of a new notice with the Council;
- Within 45 days after completion of construction, the Council shall be notified in writing that construction has been completed;
- The validity of this action shall expire one year from the date of this letter; and
- The applicant may file a request for an extension of time beyond the one year deadline provided that such request is submitted to the Council not less than 60 days prior to the expiration;

The proposed modifications including the placement of all necessary equipment and shelters within the tower compound are to be implemented as specified here and in your notice dated March 22, 2013. The modifications are in compliance with the exception criteria in Section 16-50j-72 (b) of the Regulations of Connecticut State Agencies as changes to an existing facility site that would not increase tower height, extend the boundaries of the tower site, increase noise levels at the tower site boundary by six decibels, and increase the total radio frequencies electromagnetic radiation power density measured at the tower site boundary to or above the standard adopted by the State Department of Environmental Protection pursuant to General Statutes § 22a-162. This facility has also been carefully modeled to ensure that radio frequency emissions are conservatively below State and federal standards applicable to the frequencies now used on this tower.



This decision is under the exclusive jurisdiction of the Council. Please be advised that the validity of this action shall expire one year from the date of this letter. Any additional change to this facility will require explicit notice to this agency pursuant to Regulations of Connecticut State Agencies Section 16-50j-73. Such notice shall include all relevant information regarding the proposed change with cumulative worst-case modeling of radio frequency exposure at the closest point of uncontrolled access to the tower base, consistent with Federal Communications Commission, Office of Engineering and Technology, Bulletin 65. Thank you for your attention and cooperation.

Very truly yours,

Melanie A. Bachman Acting Executive Director

MAB/CDM/jb

c: The Honorable Michael C. Tetreau, First Selectman, Town of Fairfield Joseph E. Devonshuk, Town Planner, Town of Fairfield Robert D. Gray, Program Administrator, Third Party Attachments Transmission Projects, Northeast Utilities Service Company



107 Selden Street, Berlin, CT 06037

Northeast Utilities Service Company P.O. Box 270 Hartford, CT 06141-0270 (203) 665-5000

April 3, 2013

Mr. Mark Richard T-Mobile 35 Griffin Rd. Bloomfield, CT 06002

RE: T-Mobile Antenna Site, CT-11 317, Moorehouse Rd., Fairfield CT, structure 876.

Dear Mr. Richard:

Based on our reviews of the site drawings, the structural analysis provided by Centek Engineering and, and the foundation modification and analyses performed by Centek Engineering, we have reviewed for acceptance this modification

Since there are no outstanding structural or site related issues to resolve at this time, construction at these locations may begin as soon as scheduling allows. You may contact Mr. O'Brien (860-665-6987); once the lease issues are secured you may then contact Mr. John Landry directly (860-665-5425) to begin the construction arrangements

Sincerely

Robert Gray

Transmission Line Engineering

ref:

CT11317B-MDRN-CD-V2.pdf

12066.CO1 - CT11317B - Rev2 10.19.12.pdf



### JULIE D. KOHLER

PLEASE REPLY TO: Bridgeport

WRITER'S DIRECT DIAL: (203) 337-4157
E-Mail Address: jkohler@cohenandwolf.com

EM-T-MOBILE-051-130325

March 22, 2013

Ms. Linda Roberts, Executive Director Connecticut Siting Council Ten Franklin Square New Britain, CT 06051

Re: Notice of Exempt Modification

CL&P/T-Mobile co-location

Site ID CT11317B

280 Morehouse Drive, Fairfield CT

**ORIGINAL** 



CONNECTICUT SITING COUNCIL

Dear Ms. Roberts:

This office represents T-Mobile Northeast LLC ("T-Mobile") and has been retained to file exempt modification filings with the Connecticut Siting Council on its behalf.

In this case, CL&P owns the existing electric transmission tower and related facility at 280 Morehouse Drive, Fairfield Connecticut (latitude 41° 12' 32.4" / longitude -73° 15' 39.5994"). T-Mobile intends to replace six antennas and related equipment at this existing telecommunications facility in Fairfield ("Fairfield Facility"). Please accept this letter as notification, pursuant to R.C.S.A. § 16-50j-73, of construction which constitutes an exempt modification pursuant to R.C.S.A. § 16-50j-72(b)(2). In accordance with R.C.S.A. § 16-50j-73, a copy of this letter is being sent to the First Selectman, Michael C. Tetreau and the property owners, Chijan Zhang and Yuzhi Hu.

The existing Fairfield Facility consists of an 84 foot tall transmission line structure with a power mount that extends to 106' 6". The facility currently supports the antennas of AT&T, Sprint and T-Mobile.

T-Mobile plans to replace six antenna and the platform mounted on the powermount at a centerline of 95 feet. (See the plans revised to March 15, 2013 attached hereto as Exhibit A). T-Mobile will also install 3 equipment cabinets and remove one equipment cabinet within the existing compound area near the base of the tower, as well as install coax cables along existing coax routing. The existing Facility, with foundation modifications, is structurally capable of supporting T-Mobile' proposed use, as indicated in the structural analysis dated October 19, 2012 and attached hereto as Exhibit B. (Section 1-1 of the structural analysis also



March 22, 2013 Site ID CT11317B Page 2

gives provides detail about the proposed equipment revisions and platform replacement.) As referenced by the structural analysis, foundation modification plans dated October 19, 2012 are attached hereto as Exhibit C.

The planned modifications to the Fairfield Facility fall squarely within those activities explicitly provided for in R.C.S.A. § 16-50j-72(b)(2).

- 1. The proposed modification will not increase the height of the tower. T-Mobile's replacement antennas will be installed at the 95 foot level. The enclosed tower drawing confirms that the proposed modification will not increase the height of the tower.
- 2. The installation of the T-Mobile replacement equipment in the existing compound, as reflected on the attached site plan, will not require an extension of the site boundaries. T-Mobile's proposed equipment will be located entirely within the existing compound area.
- 3. The proposed modification to the Facility will not increase the noise levels at the existing facility by six decibels or more.
- 4. The operation of the replacement antennas will not increase the total radio frequency (RF) power density, measured at the base of the tower, to a level at or above the applicable standard. According to a Radio Frequency Emissions Analysis Report prepared by EBI dated March 7, 2013 T-Mobile's operations would add 0.915% of the FCC Standard. Therefore, the calculated "worst case" power density for the planned combined operation at the site including all of the proposed antennas would be 10.955% of the FCC Standard as calculated for a mixed frequency site as evidenced by the engineering exhibit attached hereto as Exhibit D.

For the foregoing reasons, T-Mobile respectfully submits that the proposed replacement antennas and equipment at the Fairfield Facility constitutes an exempt modification under R.C.S.A. § 16-50j-72(b)(2).

Sincerely,


Julie D. Kohler, Esq.


Julie D. Kohler/meb

Town of Fairfield, Michael C. Tetreau Chijan Zhang and Yuzhi Hu Jamie Ford, HPC Wireless

CC:

### **EXHIBIT A**





### EXHIBIT B



Centered on Solutions™

### <u>Structural Analysis of</u> <u>Powermount and CL&P Tower</u>

T-Mobile Site Ref: CT11317B

CL&P Structure No. 876 86' Electric Transmission Lattice Tower


> 280 Morehouse Drive Fairfield, CT

CENTEK Project No. 12066.CO1

Date: July 13, 2012

Rev 1: July 31, 2012

Rev 2: October 19, 2012



Prepared for: T-Mobile Towers 4 Sylvan Way Parsippany, NJ 07054

Structural Analysis – 86-ft CL&P Tower # 876 T-Mobile Antenna Upgrade – CT11317B Fairfield, CT Rev 2 ~ October 19, 2012

### Table of Contents

### SECTION 1 - REPORT

- INTRODUCTION
- PRIMARY ASSUMPTIONS USED IN THE ANALYSIS
- ANALYSIS
- DESIGN BASIS
- RESULTS
- CONCLUSION

### SECTION 2 - CONDITIONS & SOFTWARE

- STANDARD ENGINEERING CONDITIONS
- GENERAL DESCRIPTION OF STRUCTURAL ANALYSIS PROGRAMS
- RISA 3-D
- PLS TOWER

### SECTION 3 - DESIGN CRITERIA

- CRITERIA FOR DESIGN OF PCS FACILITIES ON OR EXTENDING ABOVE METAL ELECTRIC TRANSMISSON TOWERS
- NU DESIGN CRITERIA TABLE
- PCS SHAPE FACTOR CRITERIA
- WIRE LOADS SHEET

### SECTION 4 - DRAWINGS

- EL-1 TOWER ELEVATION
- S-1 FOUNDATION REINFORCEMENT DRAWINGS
- N-1 NOTES
- N-2 NOTES

### <u>SECTION 5 - EIA/TIA-222-F LOAD CALCULATIONS FOR POWERMOUNT ANALYSIS</u>

POWERMOUNT WIND & ICE LOAD

### SECTION 6 - POWERMOUNT ANALYSIS PER EIA/TIA-222F

- LOAD CASES AND COMBINATIONS (TIA/EIA LOADING) POWERMOUNT
- RISA 3-D ANALYSIS REPORT POWERMOUNT
- CONNECTION ANALYSIS

TABLE OF CONTENTS TOC-1

Structural Analysis – 86-ft CL&P Tower # 876 T-Mobile Antenna Upgrade – CT11317B Fairfield, CT Rev 2 ~ October 19, 2012

### SECTION 7 - NECS/NU LOAD CALCULATIONS FOR UTILITY STRUCTURE ANALYSIS

- POWERMOUNT WIND LOAD
- COAX CABLE LOAD ON POWERMOUNT
- AT&T EQUIPMENT WIND LOAD CALCULATION
- COAX CABLE LOAD ON CL&P TOWER

### SECTION 8 - PLS TOWER RESULTS

- PLS REPORT
- FOUNDATION ANALYSIS

### SECTION 9 - REFERENCE MATERIAL

- RFDS SHEET
- EQUIPMENT CUT SHEETS

TABLE OF CONTENTS TOC-2

Structural Analysis – 86-ft CL&P Tower # 876 T-Mobile Antenna Upgrade – CT11317B Fairfield, CT Rev 2 ~ October 19, 2012

### Introduction

The purpose of this report is to analyze the existing powermount and 86' CL&P tower located at 280 Morehouse Dr., in Fairfield, CT for the proposed antenna and equipment upgrade by T-Mobile.

The proposed loads consist of the following:

SPRINT (Existing to Remain):

Antennas: Six (6) Decibel DB980H90 panel antennas mounted on a 14-ft low profile platform to the existing powermount with a RAD center elevation of 104-ft above grade.

Coax Cables: Six (6) 1-5/8" Ø coax cables running on the inside of the existing FWT Powermount.

AT&T (Existing to Remain):

Antennas: Three (3) EMS RR90-17-02DP panel antennas leg mounted to the existing utility tower with a RAD center elevation of 84-ft above grade.

Coax Cables: Six (6) 1-5/8" Ø coax cables running on a leg of the existing utility tower.

■ T-MOBILE (Existing to Remain):

<u>Coax Cables:</u> Twelve (12) 1-1/4"  $\varnothing$  coax cables running on the exterior of the existing FWT Powermount.

T-MOBILE (Existing to Remove):

Antennas: Six (6) panel antennas and one (1) 12-ft low profile platform with a RAD center elevation of 95-ft above grade.

■ T-MOBILE (Proposed):

Antennas: Six (6) RFS APX16DWV-16DWVS panel antennas mounted on a Site Pro WiMAX Monopole T-Arm p/n UDS-NP to the existing powermount with a RAD center elevation of 95-ft above grade.

<u>Coax Cables:</u> Six (6) 1-1/4"  $\varnothing$  coax cables running on the exterior of the existing FWT Powermount.

### Primary assumptions used in the analysis

- Allowable steel stresses are defined by AISC-ASD 9<sup>th</sup> edition for design of the Powermount and antenna supporting elements.
- ASCE Manual No. 10-97, "Design of Latticed Steel Transmission Structures", defines allowable steel stresses for evaluation of the CL&P utility tower.
- All utility tower members are adequately protected to prevent corrosion of steel members.
- All proposed antenna mounts are modeled as listed above.
- All coaxial cable will be installed within the powermount unless specified otherwise.
- Powermount will be properly installed and maintained.
- No residual stresses exist due to incorrect tower erection.
- All bolts are appropriately tightened providing the necessary connection continuity.
- All welds conform to the requirements of AWS D1.1.
- Powermount and utility tower will be in plumb condition.
- Utility tower was properly installed and maintained and all members were properly designed, detailed, fabricated, and installed and have been properly maintained since erection.
- Any deviation from the analyzed loading will require a new analysis for verification of structural adequacy.

Structural Analysis – 86-ft CL&P Tower # 876 T-Mobile Antenna Upgrade – CT11317B Fairfield, CT Rev 2 ~ October 19, 2012

### <u>Analysis</u>

Structural analysis of the existing *Powermount* was independently completed using the current version of RISA-3D computer program licensed to CENTEK Engineering, Inc.

The existing FWT powermount consisting of a 12" Std. pipe conforming to ASTM A500 Grade C (Fy = 50ksi) connected at five points to the existing tower was analyzed for its ability to resist loads prescribed by the TIA/EIA standard. Section 5 of this report details these gravity and lateral wind loads. NESC prescribed loads were also applied to the powermount in order to obtain analyze the CL&P tower structure. These loads are developed in Section 7 of this report.

An envelope solution was first made to determine maximum and minimum forces, stresses, and deflections to confirm the selected section as adequate. Additional analyses were then made to determine the NESC forces to be applied to the CL&P tower structure.

The RISA-3D program contains a library of all AISC shapes and corresponding section properties are computed and applied directly within the program. The program's Steel Code Check option was also utilized. The forces calculated in RISA-3D using NESC guidelines were then applied to the CL&P tower using PLS-Tower. Maximum usage for the tower was calculated considering the additional forces from the mast and associated appurtenances.

### Design Basis

Our analysis was performed in accordance with EIA-222-F-1996, ASCE Manual No. 10-97, "Design of Latticed Steel Transmission Structures", NESC C2-2007 and Northeast Utilities Design Criteria.

The CL&P tower structure, considering existing and future conductor and shield wire loading, with the existing powermount was analyzed under two conditions:

### UTILITY TOWER ANALYSIS

The purpose of this analysis is to determine the adequacy of the existing utility structure to support the proposed antenna loads. The loading and design requirements were analyzed in accordance with the NU Design Criteria Table, NESC C2-2007 ~ Construction Grade B, and ASCE Manual No. 10-97, "Design of Latticed Steel Transmission Structures".

Load cases considered:

| Wind P<br>Radial<br>Vertica<br>Wind C | Pase 1: NESC Heavy Pressure Ice Thickness I Overload Capacity Factor Overload Capacity Factor ension Overload Capacity Factor | 4.0 psf<br>0.5"<br>1.50<br>2.50<br>1.65 |
|---------------------------------------|---|---|
| Wind S                                | ase 2: NESC Extreme peed  | 10 mph <sup>(1)</sup><br>0"             |
| Note 1:                               | NESC C2-2007, Section25, Rule 250C: Extre<br>Loading, 1.25 x Gust Response Factor (wind<br>second gust)                       |   |

REPORT SECTION 1-2

Structural Analysis – 86-ft CL&P Tower # 876 T-Mobile Antenna Upgrade – CT11317B Fairfield, CT Rev 2 ~ October 19, 2012

### POWERMOUNT ANALYSIS

Powermount, appurtenances and connections to the utility tower were analyzed and designed in accordance with the NU Design Criteria Table, TIA/EIA-222-F, and AISC-ASD standards.

Load cases considered:

Load Case 1:

Load Case 2:

Radial Ice Thickness...... 0.5"

Note 2: Per NU Mast Design Criteria Exception 1.

### Results

### POWERMOUNT

The existing powermount was determined to be structurally adequate.

| FWT Powermount | Stress Ratio<br>(% of capacity) | Result |
|----------------|---------------------------------|--------|
| 12" Std. Pipe  | 79.2%                           | PASS   |

### UTILITY TOWER

This analysis finds that the subject utility structure is adequate to support the existing powermount and related appurtenances. The tower stresses meet the requirements set forth by the ASCE Manual No. 10-97, "Design of Latticed Steel Transmission Structures", for the applied NESC Heavy and Hi-Wind load cases. The detailed analysis results are provided in Section 9 of this report. The analysis results are summarized as follows:

A maximum usage of 98.73% occurs in the utility tower under the NESC Extreme Wind loading condition.

### TOWER SECTION:

The utility tower was found to be within allowable limits.

| Tower Member | Stress Ratio<br>(% of capacity) | Result |
|--------------|---------------------------------|--------|
| Angle g11x   | 98.73%                          | PASS   |

### FOUNDATION AND ANCHORS

The existing foundation consists of four (4) 1-ft 8-in square tapering to 2-ft 4-in square x 5.25-ft long reinforced concrete piers and four (4) 5-ft square x 2-ft thick reinforced concrete pads. The base of the tower is connected to the foundation by one (1) anchor stub angle per leg. Foundation information was obtained from Northeast Utilities drawing 01064-60003.

Review of the foundation design consisted of verification of applied loads obtained from the tower design calculations and code checks of allowable stresses:

CENTEK Engineering, Inc. Structural Analysis – 86-ft CL&P Tower # 876 T-Mobile Antenna Upgrade – CT11317B Fairfield, CT Rev 2 ~ October 19, 2012

### **BASE REACTIONS:**

From PLS-Tower analysis of CL&P tower based on NESC/NU prescribed loads.

| Foundation       | Load Case            | Shear      | Uplift     | Compression |
|------------------|----------------------|------------|------------|-------------|
| Single Conc.     | NESC Heavy<br>Wind   | 8.46 kips  | 19.97 kips | 37.33 kips  |
| Pad & Pier       | NESC<br>Extreme Wind | 14.68 kips | 50.80 kips | 60.20 kips  |
| Conc. Pad & Pier | NESC Heavy<br>Wind   | 11.88 kips | 37.90 kips | 61.81 kips  |
| (2) w/ Mat       | NESC<br>Extreme Wind | 28.43 kips | 99.67 kips | 118.12 kips |

Note 1 – 10% increase to be applied to the above tower base reactions for foundation verification per OTRM 051 Note 2 – Reactions used to analysis the reinforced foundation are the combination of the two adjacent tower legs.

### **FOUNDATION:**

The foundation with the proposed reinforcements detailed in section 4 of this report was found to be within allowable limits.

| Foundation                     | Design<br>Limit | Allowable<br>Limit    | Proposed<br>Loading <sup>(2)</sup> | Result |
|--------------------------------|-----------------|-----------------------|------------------------------------|--------|
| Single Conc.<br>Pad & Pier     | Uplift          | 1.0 FS <sup>(1)</sup> | 1.15 FS <sup>(1)</sup>             | PASS   |
| Conc. Pad &<br>Pier (2) w/ Mat | Uplift          | 1.0 FS <sup>(1)</sup> | 1.30 FS <sup>(1)</sup>             | PASS   |

Note 1: FS denotes Factor of Safety

Note 2: 10% increase to PLS base reactions used in foundation analysis per OTRM 051.

### <u>Conclusions and Recommendations</u>

This analysis shows that the subject utility tower with the proposed foundation reinforcements detailed in section 4 of this report is adequate to support the proposed T-Mobile equipment upgrade.

The analysis is based, in part on the information provided to this office by Northeast Utilities and T-Mobile. If the existing conditions are different than the information in this report, CENTEK engineering, Inc. must be contacted for resolution of any potential issues.

Please feel free to-call with any questions or comments.

Respectfully Submitted by

Carlo F. Centore, PE


Principal ~ Structural Engineer

Prepared by:

Timothy J. Lynn, EIT

Structural Engineer

### **EXHIBIT C**



### STRUCTURAL NOTES

DESIGN BASIS

# COVERNING CODE: 2003 INTERNATIONAL BUILDING CODE AS MODIFIED BY THE 2005 CT STATE BUILDING CODE AND 2009 AMENDMENTS.

TA/FAX-222-F-1996, ASCE MANUAL NO. 72 - "DESIGN OF STEEL TRANSMISSION POLE STRUCTURES SECOND EDMON", NESC C2-2007 AND NORTHEAST UTILITIES DESIGN CRITERAL.

MIND LODD: (PCS MAST)

BUSIC MIND SPEED (V) =85 MPH (FASTEST MILE); BASED ON TA/EA-222F

AND NU MAST DESIGN CRITERIA EXCEPTION 1. MIND LAND: (UTILITY POLE & FOLINDATION)
BASIC WIND SPEED (V) = 110 MPH (3-SECOND GUST) BASED ON NESC C2-2007, SECTION 25 RULE 250C.

- ALL CONSTRUCTION SHALL BE IN COMPLIANCE WITH THE GOVERNING BUILDING CODE.
- DOWNINGS INDICATE THE MINIMUM STANDARDS, BUT IF NAY WORK SHOULD BE INDICATED TO BE SUBSTANDARD TO MAY ORDEWANCES, LIMIS, COOKES BULLS OR BECELLATIONS BEFORMS ON THE WORK THE COMPROCEDS SHALL INCLUDES IN HIS SECULATIONS BEFORMS ON THE WORK THE COMPROCEDS SHALL INCLUDES IN HIS SECULATIONS BEFORE THE SHOULD BE INCLUDED. THE WORK THE COMPROCED THE WORK THE CONTROL OF THE WORK THE SHALL SHOULD BE S
- BEFORE BEGINNING THE WORK, THE CONTRACTOR IS RESPONSIBLE FOR MAKING SUCH INVESTIGATIONS CONCERNING PHYSICAL CONDITIONS (SURFACE AND SUBSURFACE) AT OR CONTIGUOUS TO THE SITE WHICH MAY AFFECT PERFORMANCE AND COST OF THE WORK.
- DIMENSIONS AND DETAILS SHALL BE CHECKED AGAINST THE PRE MANUFACTURED EQUIPMENT BUILDING SHOP DRAWINGS.
- ALL DIMENSINS, ELEVATIONS, AND OTHER REFERENCES TO EXISTING STRECTURES.
  SURFACE, AND SUBSILIPACE CONCINIONS AND PREPARAME. TO COLUMNIES OF THE INFORMATIES OF THE INFORMATIES OF THE INFORMATIES AND CONTINUES AND EXPERT AND CONCINUES ALL DESIGNS, ELEVATIONS, AND WITH EXISTING CONCINIONS AND WITH ADDITIONAL AND SITE DAMMICS BETORE PROCEDURG WITH ANY MORE. THE CONTRACTOR SHALL VERIFY AND COORDINATE THE SIZE AND LOCATION OF ALL OPENINGS, SLEEVES AND ANCHOR BOLTS AS REQUIRED BY ALL TRADES.
- AS THE WORK PROGRESSES, THE CONTRACTOR SHALL NOTIFY THE OWNER OF ANY CONDITIONS WHICH ARE IN CONFLICT OR DIFFERENCE NOT CONSISTENT WITH THE CONSTRUCTION DOLUMENTS AND SHALL NOT PROCEED WITH SUCH WORK UNTIL THE CONFLICT IS SATISFACTORLY RESOLVED.
- THE CONTRACTOR IS SOLELY RESPONSIBLE TO DETERMINE CONSTRUCTION PROCEDURE AND STRUCTURES AND TIS COMPONEN, AND TO SHAPE THE SAFFTY OF THE DESTRUCTURES AND TIS COMPONEN PARTS DURING CONSTRUCTION, THIS INCLUDES THE COLDITION OF WINDERTS SHORMED, GROUNDLE, UNDERSMANKE, FET, THAT MAY BE RECESSARY, MARTINE EDSTRIC SITE OPERATIONS, COORDINATE WORK WITH MARTHER STAFF, CONTRACTOR CONTRACTOR OF THE CONTRACTOR OF TH Compagne syml comey with all periodic systy cors my liating dibbne. III phass se corstration in compagner is solicy corsele for produce, and impringence accurate shorter. Because, who touces so law be recursed for any protection of distinct properties, struction workers, and for public systy.
- THE STRUCTURE IS DESCRIED TO BE SOLF-SUPPORTING AND STABLE AFTER TOWNSHING RECLIFICATION WAS IN COMPILET, IT IS THE CONTRICTOR'S RECEIVED PROCEDURE AND SOLECUTE AND TO DESCRIPT TO DETERMINE BECTION PROCEDURE AND SOLECUTED PARTS DURING SOLECUTED FASTE STRUCTURE AND ITS COMPILETY PARTS DURING SOCIEDA, OTHER SPECIFICA, OTHER SPECIFICA, OTHER SPECIFICA, OTHER SPECIFICA, OTHER SPECIFICATION OF MANDRES SPECIFICA, OTHER SPECIFICATION OF MANDRES SPECIFICATION OTHER SPECIFICATION.
- ALL DAMAGE CAUSED TO ANY EXISTING STRUCTURE SHALL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR, THE CONTRACTOR WILL BE HELD LUBLE FOR ALL REPAIRS REQUIRED FOR EXISTING STRUCTURES IF DAMAGED DURING CONSTRUCTION ACTIVITIES. THE COMPACTOR SHALL LIMIT THE DURATION OF ANY FOUNDATION MODIFICATION WORK. THE ENSITING FOUNDATION WITHIN THE SHORM LIMITS IS STRABE FOR WHO SPEEDS LESS THAN SOMEH WITHOUT CIS CLOUNG, IF HIGHER WIND SPEED OR COENTIFIES DEPORTED. THE ENCANATION AREA SHALL BE FILLED WITH COMPACT FILL MATERIAL.
- 14. NO DRILLING WELDING OR TAPING ON CLASP OWNED EQUIPMENT.

  15. REFER TO DRAWING T1 FOR ADDITIONAL NOTES AND REQUIREMENTS.

- THE CONTRACTOR SHALL CALL UTILITIES PRIOR TO THE START OF CONSTRUCTION
- The site shall be graded to cause surface water to flow away from the equipment and tower areas.
- THE AREAS OF THE COMPOUND DISTURBED BY THE WORK SHALL BE RETURNED TO THEIR ORIGINAL CONDITION. CONTRACTOR SHALL MINIMAZE DISTURBANCE TO EXISTING SITE DURING CONSTRUCTION ENGINEN CONTROL WEXISTERS, SHALL BE IN COMPERMANCE WITH THE LOCAL GUIDELINES FOR EROSION AND SEDIMENT CONTROL.

SIEVE DESIGNATION 1 ½\* 1 ½\* No. 4 No. 100 No. 200 CRUSHED STONE TO BE UNIFORMLY GRADED, CLEAN, HARD PROCESS AGGREGATE MEETING THE FOLLOWING GRADATION REQUIREMENTS:

SIEVE DESIGNATION

SELECT BACKFILL FOR FOUNDATION WALLS SHALL BE FREE OF ORGANIC MATERIAL, TOPSOIL, DEBRIS AND BOULDERS LARGER THAN 6".

FOUNDATION CONSTRUCTION NOTES ALL FOOTINGS SHALL BE PLACED ON SUTTABLE, COMPACTED SOIL HANING ADEQUATE BEARING CAPACITY AND TREE OF ORGANIC CONTENT, CLAY, OR OTHER INSUITABLE MATERIAL ADDITIONAL EXCANATION MAY BE REQUIRED BELOW FOOTING ELEXITONS INDICATED IF UNSUITABLE MATERIAL IS ENCOUNTERED.

- Jacobode Perpendinte ir usestindal soli de incoluntera, recore di vicalizada, purtibaci programe della programma della progr

ALL SOIL SURROUNDING AND UNDER ALL FOOTINGS SHALL BE KEPT REASONABLY DRY AND PROTECTED PROM PREEZING AND FROST ACTION DURING THE COURSE OF CONSTRUCTION. MERE GROUNDWATER IS ENCOUNTERED, DEWATERING SMALL BE ACCOMPLISHED CONTINUOUSLY, AND COMPLETELY DURING FOUNDATION CONSTRUCTION, PROVIDE CRUSHED STONE AS REQUIRED TO STABILIZE FOOTING SUBGRADE.

ALL PROMINGS, ARE TO REST ON PIRM SOIL, RECARDLESS OF ELEVATIONS SHOWN ON THE REMAINES, BET IN NO CASE MAY FOOTING ELEVATIONS BE HIGHER THAN MODICATED ON THE FOUNDATION PLAN, UNLESS SPECIFICALLY DIRECTED BY THE DEGINEER.

FOUNDATION WATESPROOFING AND DAMPPROOFING SHALL COMPLY WITH BUILDING CODE REQUIREMENTS UNLESS A MORE SUBSTANTIAL SYSTEM IS INDICATED OR SPECIFIED.

- ALL RUBBISH, STUMPS, DEBRIS, STICKS, STONES AND OTHER REFUSE SHALL BE REMOVED OFF SITE AND BE LECALLY DISPOSED, AT NO ADDITIONAL COST.
- NO FILL OR BUBWINGET WITERW. SHALL BE PLACED ON FROZEN GROUND. FROZEN MATERIALS, SNOW OR ICE SHALL NOT BE PLACED IN ANY FILL OR EMBANGAENT.
- THE SUBGRADE SHALL BE COMPACTED AND BROUGHT TO A SMOOTH UNIFORM GRADE PRIOR TO FINISHED SURFACE APPLICATION.
- IF ANY RELD CONDITIONS EXIST WHICH PRECLUDE COMPLIANCE WITH THE DOMININGS THE CONTRACTOR SYML IMMEDIATELY NOTIFY THE ENGINEER AND SYMLL PROCEED WITH AFFECTED WORK AFTER CONFLICT IS SATISFACTORILY RESOLVED.

### EARTHWORK NOTES

COMPACTED GRAVEL FILL SHALL BE FURNISHED AND PLACED AS A FOUNDATION FOR STRUCTURES, WHERE SHOWN ON THE CONTRACT DRAWNES OR DIRECTED BY THE ENGINEER. CRUSHED STONE FILL SHALL BE PLACED IN 12" MAX. LIFTS AND CONSOLIDATED USING A HAND DEPARTED VIBRATORY PLATE COMPACTOR WITH A MINIMUM OF 2 PAGSSES OF COMPACTOR PER LIFT.

COMPACTED GRAVEL FILL TO BE WELL GRADED BANK RUN GRAVEL MEETING THE FOLLOWING GRADATION REQUIREMENTS: 7. PASSING 100 40-70 5-20 4-8

7. PASSING 100 90-100 0-15 0-5

NON WOVEN GEOTEXTILE FOR SEPARATION PURPOSES SHALL BE MIRAFI 140N, OR ENGINEER APPROVED EQUAL GRAVEL AND GRANULAR FILL SHALL BE INSTALLED IN 10" MAX. LIFTS. COMPACTED TO 95% MIN. AT MAX. DRY DENSITY.

12. SLAB ON GRADE FINISHES: EXTERIOR SLAB: NON-SLIP BROOM FINISH INTERIOR SLAB: STEEL TROWEL FINISH

ILL INSECTION AND TESTING OF CONCRETE WORK SAME, BE PERFORDED BY AN INDEPONDENT TESTING LABOANDEY, "AND BY THE GOMERS, AND APPONDED BY THE DIGHTER THE INSPECTING SHALL OBSERVE CONDITION OF SOLE AND FROMWORK BEFORE FORTHERS ARE PLACED. SZE, SPACING AND LOCATION OF RENFORCEMENT, AND PLACEMENT OF CONCRETE.

. THE TESTING COMPANY SHALL ALSO OBTAIN A MINIMUM OF THREE (3) COMPRESSIVI STRENGTH TEST SPECIMENS FOR EACH CONCRETE MIX DESIGN, ONE SPECIMEN TESTED AT 7 DAYS, ONE AT 28 DAYS, AND ONE HELD IN RESERVE FOR FUTURE TESTING, IF NEEDED. FOUR COPIES OF ALL INSPECTION TEST REPORTS SHALL BE SUBMITTED TO THE ENGINEER WITHIN TEN (10) WORKING DAYS OF THE DATE OF INSPECTION.

3. REINFORCING STEEL SHALL BE 60,000 PSI YIELD STRENGTH.
4. WELDED WIRE FABRIC SHALL CONFORM TO ASTM- A-185.

CONCRETE COVER OVER REINFORCING SHALL CONFORM TO THE FOLLOWING, UNLESS OTHERWISE SHOWN: ALL DEFAUNG, FABRICATION, AND RECTION OF RENFORCING BARS, UNLESS OFFICEMENT ACI CODE MOD LATEST ACI "AWAULA OF STANDARD PRACTICE FOR DETAULING REINFORCED CONCRETE STRUCTURES".

CONCRETE EXPOSED TO EARTH OR WEATHER:

\$6 THROUGH \$18 BARS
\$5 BAR, W31 OR D31 WIRE, AND SMALLER 1-1/2 INCHES CONCRETE CAST AGAINST & PERMANENTLY EXPOSED TO EARTH 3 INCHES

NO STEEL WIRE, METAL FORM TIES, OR ANY OTHER METAL SHALL REMAIN WITHIN THE REQUIRED COVER OF ANY CONCRETE SURFACE. ALL REINFORCEMENT SHALL BE CONTINUOUS UNLESS OTHERWISE NOTED. SPUCES SHALL BE WELL STAGERED, ADDITIONAL BARS AND SPECIAL BENDING DETAILS ARE REQUIRED AT INTERSECTION WALLS HAD AT JOINTS, SUCH DETAILS SHALL COMPLY WITH ACI 315 RECOMMENDATIONS UNLESS OTHERWISE SHOWN. CONCRETE NOT EXPOSED TO WEATHER OR IN CONTACT WITH THE GROUND: \$14 THROUGH \$18 BARS \$11 BAR AND SAMULER

3/4 INCHES

10. NO CALCIUM CHLORIDE OR ADMIXTURES CONTAINING MORE THAN 1% CHLORIDE BY WEIGHT OF ADMIXTURE SHALL BE USED IN THE CONCRETE. USE OF FLY ASH BINDER IS STRICTLY PROHIBITED. NO TACK WELDING OF REINFORCING WILL BE PERMITTED. UNLESS OTHERWISE NOTED, ALL LAP SPLICES SHALL BE 48 BAR DIAMETERS.

## CONCRETE CONSTRUCTION NOTES

1. CONCRETE CONSTRUCTION SHALL CONFORM TO THE FOLLOWING STANDARDS: ACI 211 - STANDARD PRACTICE FOR SELECTING PROPORTIONS FOR NORMAL AND HEAVYWEIGHT CONCRETE. ACI 304 - RECOMMENDED PRACTICE FOR MEASURING, MIXING, TRANSPORTING, PLACING CONCRETE. ACI 302 - GUIDE FOR CONCRETE FLOOR AND SLAB CONSTRUCTION ACI 301 - SPECIFICATIONS FOR STRUCTURAL CONCRETE FOR BUILDINGS.

CONCRETE SHALL DEVELOP COMPRESSIVE STRENGTH IN 28 DAYS AS FOLLOWS: ACI 306.1 STANDARD SPECIFICATION FOR COLD WEATHER CONCRETING SLABS ON GRADE ALL OTHER CONCRETE ACI 318 - BUILDING CODE REQUIREMENTS FOR REINFORCED CONCRETE. 3,000 PSI

REMILIAD CORDIT. SMIL C150, TIPE II. (940 USC)CHSC VWD)
MORRIEDER SMIL CM. MA ST PRO-CLUT ROTO OF JA
MORRIESE SMIL MA SMIL MORRI COMPRIMAN ID SMIL C260 WITH 5 TO
ADMITISES SMIL MA SMILWANION CAPET COMPRIMAN ID SMIL C260 WITH 5 TO
ADMITISES SMIL MA SMILWANION CAPET COMPRIMAN ID SMIL C260 WITH 5 TO
ADMITISES SMIL MA SMILWANION CAPET COMPRIMAN ID SMIL C260 WITH 5 TO
ADMITISES SMIL MA SMILWANION CAPET COMPRIMAN ID SMIL C260 WITH 5 TO
ADMITISES SMILWANION CAPET COMPRIMAN ID SMILWANION CAPET
ADMITISES SMILWA

T · · Mobile CENTEK

S-2

NOTES AND SPECIFICATIONS

T-MOBILE

CT11317B CL&P STRUCT. NO. 876

용물

### **EXHIBIT D**



### RADIO FREQUENCY EMISSIONS ANALYSIS REPORT EVALUATION OF HUMAN EXPOSURE POTENTIAL TO NON-IONIZING EMISSIONS

T-Mobile Existing Facility

Site ID: CT11317B

Fairfield / MP / X44 & X42 280 Morehouse Road Fairfield, CT 06825

March 07, 2013

21 B Street Burlington, MA 01803 Tel: (781) 273.2500 Fax: (781) 273.3311



March 07, 2013

T-Mobile USA Attn: Jason Overbey, RF Manager 35 Griffin Road South Bloomfield, CT 06002

Re: Emissions Values for Site: CT11317B - Fairfield / MP / X44 & X42

EBI Consulting was directed to analyze the proposed T-Mobile facility located at 280 Morehouse Road, Fairfield, CT, for the purpose of determining whether the emissions from the Proposed T-Mobile Antenna Installation located on this property are within specified federal limits.

All information used in this report was analyzed as a percentage of current Maximum Permissible Exposure (% MPE) as listed in the FCC OET Bulletin 65 Edition 97-01 and ANSI/IEEE Std C95.1. The FCC regulates Maximum Permissible Exposure in units of microwatts per square centimeter ( $\mu$ W/cm2). The number of  $\mu$ W/cm2 calculated at each sample point is called the power density. The exposure limit for power density varies depending upon the frequencies being utilized. Wireless Carriers and Paging Services use different frequency bands each with different exposure limits, therefore it is necessary to report results and limits in terms of percent MPE rather than power density.

All results were compared to the FCC (Federal Communications Commission) radio frequency exposure rules, 47 CFR 1.1307(b)(1) - (b)(3), to determine compliance with the Maximum Permissible Exposure (MPE) limits for General Population/Uncontrolled environments as defined below.

General population/uncontrolled exposure limits apply to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Therefore, members of the general public would always be considered under this category when exposure is not employment related, for example, in the case of a telecommunications tower that exposes persons in a nearby residential area.

Public exposure to radio frequencies is regulated and enforced in units of microwatts per square centimeter ( $\mu$ W/cm2). The general population exposure limit for the cellular band is 567  $\mu$ W/cm2, and the general population exposure limit for the PCS band is 1000  $\mu$ W/cm2. Because each carrier will be using different frequency bands, and each frequency band has different exposure limits, it is necessary to report percent of MPE rather than power density.



Occupational/controlled exposure limits apply to situations in which persons are exposed as a consequence of their employment and in which those persons who are exposed have been made fully aware of the potential for exposure and can exercise control over their exposure. Occupational/controlled exposure limits also apply where exposure is of a transient nature as a result of incidental passage through a location where exposure levels may be above general population/uncontrolled limits (see below), as long as the exposed person has been made fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Additional details can be found in FCC OET 65.

### **CALCULATIONS**

Calculations were done for the proposed T-Mobile Wireless antenna facility located at 280 Morehouse Road, Fairfield, CT, using the equipment information listed below. All calculations were performed per the specifications under FCC OET 65. Since T-Mobile is proposing highly focused directional panel antennas, which project most of the emitted energy out toward the horizon, the actual antenna pattern gain value in the direction of the sample area was used. For this report the sample point is a 6 foot person standing at the base of the tower

For all calculations, all equipment was calculated using the following assumptions:

- 1) 2 GSM channels (1940.000 MHz—to 1950.000 MHz) were considered for each sector of the proposed installation.
- 2) 2 UMTS channels (2110.000 MHz to 2120.000 MHz / 2140.000 MHz to 2145.000 MHz) were considered for each sector of the proposed installation
- 3) 2 LTE channels (2110.000 MHz to 2120.000 MHz / 2140.000 MHz to 2145.000 MHz) were considered for each sector of the proposed installation
- 4) All radios at the proposed installation were considered to be running at full power and were uncombined in their RF transmissions paths per carrier prescribed configuration. Per FCC OET Bulletin No. 65 Edition 97-01 recommendations to achieve the maximum anticipated value at each sample point, all power levels emitting from the proposed antenna installation are increased by a factor of 2.56 to account for possible in-phase reflections from the surrounding environment. This is rarely the case, and if so, is never continuous.
- 5) For the following calculations the sample point was the top of a six foot person standing at the base of the tower. The actual gain in this direction was used per the manufactures supplied specifications.
- 6) The antenna used in this modeling is the RFS APX16DWV-16DWVS for LTE, UMTS and GSM. This is based on feedback from the carrier with regards to anticipated antenna selection. This antenna has a 16.3 dBd gain value at its main lobe. Actual antenna gain values were used for all calculations as per the manufacturers specifications



- 7) The antenna mounting height centerline of the proposed antennas is **95 feet** above ground level (AGL)
- 8) Emissions values for additional carriers were taken from the Connecticut Siting Council active database. Values in this database are provided by the individual carriers themselves.

All calculation were done with respect to uncontrolled / general public threshold limits

| Site ID       | CT11317B - Fairfield / MP / X44 & X42   |
|---------------|---|
| site Addresss | 280 Morehouse Road, Fairfield, CT 06825 |
| Site Type     | Transmission Tower                      |

|                 |                                |                 |  |                |            |  | Sector 1   | or 1   |  |                        |  |             |                                   |  |                    |                           |  |
|-----------------|--------------------------------|-----------------|--|----------------|------------|--|--|--|--|------------------------|--|-------------|-----------------------------------|--|--------------------|---------------------------|--|
| Antenna         | Antenna<br>Number Antenna Make | Antenna Model   | Status   | Frequency Band | Technology | Power<br>Out Per<br>Channel<br>(Watts) |  | Number of Composite<br>Channels Power  | Antenna Gain<br>in direction<br>of sample<br>point (dBd)   | Antenna<br>Height (ft) | analysis<br>height   | Cable Size  | Cable Loss Additional             | Additional<br>Loss                       | 8                  | Power<br>Density<br>Value | Power<br>Density<br>Percentage   |
| 1a              | RFS                            | APX16DWV-16DWVS | Passive  | PCS - 1950 MHz | GSM / UMTS | 30                                     | 2  | 09   | -3.95  | 95                     | 68   | 8/ <i>L</i> | 1.2                               | 0  | 18.329527          | 0.831912                  | 0.08319%   |
| 18              | RFS                            | APX16DWV-16DWVS | Passive  | AWS - 2100 MHz | UMTS/LTE   | 40                                     | 4  | 160  | -3.95  | 95                     | 89   | 8/2         | 1.2                               | 0  | 48.878738          | 2.218431                  | 0.22184%   |
|                 |                                |                 |  |                |            |  |  |  |  |                        |  | Sector tota | I Power De                        | Sector total Power Density Value: 0.305% | 0.305%             |                           |  |
|                 |                                |                 |  |                |            |  | Sector 2   | or 2   |  |                        |  |             |                                   |  |                    |                           |  |
|                 |                                |                 |  |                |            | Power<br>Out Per                       |  | y 7  | •  |                        |  |             |                                   |  |                    | Power                     | Power  |
| Antenna         | Antenna<br>Number Antenna Make | Antenna Model   | Status   | Frequency Band | Technology | Channel<br>(Watts)                     |  | Number of Composite<br>Channels Power  | of sample Antenna<br>point (dBd) Height (ft)   | Antenna<br>Height (ft) | analysis<br>height   | Cable Size  | Cable Loss Additional (dB) Loss   | Additional                               | ERP                | Density                   | Density  |
| 1a              | RFS                            | APX16DWV-16DWVS | Passive  | PCS - 1950 MHz | STMU/MSD   | 30                                     | 2  | 09   | -3.95  | 95                     | 68   | 8/ <i>L</i> | 1.2                               | 0  | 18.329527          | 0.831912                  | 0.08319%   |
| 18              | RFS                            | APX16DWV-16DWVS | Passive  | AWS - 2100 MHz | UMTS/LTE   | 40                                     | 4  | 160  | -3.95  | 95                     | 89   | 1-5/8"      | 1.2                               |  | 48.878738 2.218431 | 2.218431                  | 0.22184%   |
|                 |                                |                 |  |                |            |  |  |  |  |                        |  | Sector tota | I Power De                        | Sector total Power Density Value:        | 0.305%             |                           |  |
|                 |                                |                 |  |                |            |  | Sector 3   | or 3   |  |                        |  |             |                                   |  |                    |                           |  |
|                 |                                |                 |  |                |            | Power<br>Out Per                       |  |  |  |                        |  |             |                                   |  |                    | Power                     | Power  |
| Antenna         | Antenna<br>Number Antenna Make | Antenna Model   | Status   | Frequency Band | Technology | Channel<br>(Watts)                     |  | Number of Composite<br>Channels Power  | of sample<br>point (dBd)   | Antenna<br>Height (ft) | analysis   | Cable Size  | Cable Loss Additional             | Additional                               | ERP                | Density                   | Density  |
| 1a              | RFS                            | APX16DWV-16DWVS | Passive  | PCS - 1950 MHz | GSM / UMTS | 30                                     | 2  | 9  | -3.95  | 95                     | 68   | 8/2         | 1.2                               | 0  | 18.329527          | 10                        | 0.08319%   |
| 18              | RFS                            | APX16DWV-16DWVS | Passive  | AWS - 2100 MHz | UMTS/LTE   | 40                                     | 4  | 160  | -3.95  | 95                     | 68   | 1-5/8"      | 1.2                               |  | 48.878738 2.218431 | 2.218431                  | 0.22184%   |
| THE PROPERTY OF |                                |                 | THE CHARGO STREET, STR |                |            | STATE OF STREET                        | SECOND STREET, | CHARLES STATE OF THE PARTY OF T | ALCOHOLD REPORT OF THE PARTY OF | STATISTICS CONTRACTOR  | TO THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN THE PERSON NA | Contactor   | Contact Daniel Daniel Description | ity Volue.                               | 0.0000             | SAGNING STATE CHARGE      | Emphasization Charles Company of the |

| Carrier  | MPE%   |
|----------|--------|
| T-Mobile | 0.915% |
| AT&T     | 5.350% |
| Sprint   | 4.730% |

Sector total Power Density Value



### **Summary**

All calculations performed for this analysis yielded results that were well within the allowable limits for general public exposure to RF Emissions.

The anticipated Maximum Composite contributions from the T-Mobile facility are **0.915%** (**0.305% from each sector**) of the allowable FCC established general public limit considering all three sectors simultaneously.

The anticipated composite MPE value for this site assuming all carriers present is **10.955**% of the allowable FCC established general public limit. This is based upon values listed in the Connecticut Siting Council database for existing carrier emissions

FCC guidelines state that if a site is found to be out of compliance (over allowable thresholds), that carriers over a 5% contribution to the composite value will require measures to bring the site into compliance. For this facility, the composite values calculated were within the allowable 100% threshold standard per the federal government

Scott Heffernan

RF Engineering Director

**EBI Consulting** 

21 B Street

Burlington, MA 01803

21 B Street Burlington, MA 01803 Tel: (781) 273.2500 Fax: (781) 273.3311