



Northeast Site Solutions
Carolyn Seeley
1053 Farmington Ave, Unit G,
Farmington CT 06032
cseeley@northeastsitesolutions.com

January 13, 2022

Members of the Siting Council
Connecticut Siting Council
Ten Franklin Square
New Britain, CT 06051

RE: Tower Share Application
82 Lovely St, Unionville CT
Latitude: 41.7614 N
Longitude: -72.8875 W
Site#: BOBDL00107A

Dear Ms. Bachman:

This letter and attachments are submitted on behalf of Dish Wireless LLC. Dish Wireless LLC plans to install antennas and related equipment to the tower site located at 82 Lovely St, Unionville, Connecticut.

Dish Wireless LLC proposes to install three (3) 600/1900/2100 5G MHz antenna and six (6) RRUs, at the 88-foot level of the existing 100-foot monopole tower, one (1) Fiber cable will also be installed. Dish Wireless LLC equipment cabinets will be placed within 7x5 lease area. Included are plans by Infinigy, dated December 8, 2021, Exhibit C. Also included is a structural analysis prepared by Armor Tower Engineering, dated September 7, 2021, confirming that the existing tower is structurally capable of supporting the proposed equipment. Attached as Exhibit D. This facility was approved by the Town of Farmington, see attached email and decision approval dated July 15, 1953. Please see attached Exhibit A.

Please accept this letter as notification pursuant to Regulations of Connecticut State Agencies 16-50aa, of Dish Wireless LLC intent to share a telecommunications facility pursuant to R.C.S.A. 16-50j-88. In accordance with R.C.S.A., a copy of this letter is being sent to Kathleen A Blonski, Town Manager for the Town of Farmington, Shannon P.E. Rutherford, Town Planner for the Town of Farmington, as well as the property owner Southern New England and EIP Communications LLC, tower owner.

The planned modifications of the facility fall squarely within those activities explicitly provided for in R.C.S.A. 16-50j-89.

1. The proposed modifications will not result in an increase in the height of the existing structure. The top of the tower is 100-feet; Dish Wireless LLC proposed antennas will be located at a center line height of 88-feet.
2. The proposed modification will not result in the increase of the site boundary as depicted on the attached site plan.
3. The proposed modification will not increase the noise levels at the facility by six decibels or more, or to levels that exceed local and state criteria. The incremental effect of the proposed changes will be negligent.



4. The operation of the proposed antennas will not increase radio frequency emissions at the facility to a level at or above the Federal Communications Commission safety standard. As indicated in the attached power density calculations, the combined site operations will result in a total density of 36.76% as evidenced by Exhibit F.

Connecticut General Statutes 16-50-aa indicates that the Council must approve the shared use of a telecommunications facility provided it finds the shared use is technically, legally, environmentally, and economically feasible and meets public safety concerns. As demonstrated in this letter, Dish Wireless LLC respectfully indicates that the shared use of this facility satisfies these criteria.

A. Technical Feasibility. The existing monopole has been deemed structurally capable of supporting Dish Wireless LLC proposed loading. The structural analysis is included in Exhibit D.

B. Legal Feasibility. As referenced above, C.G.S. 16-50aa has been authorized to issue orders approving the shared use of an existing tower such as this monopole in Unionville. Under the authority granted to the Council, an order of the Council approving the requested shared use would permit Dish Wireless LLC to obtain a building permit for the proposed installation. Further, a letter of Authorization is included as Exhibit G, authorizing Dish Wireless LLC to file this application for shared use.

C. Environmental Feasibility. The proposed shared use of this facility would have a minimal environmental impact. The installation of Dish Wireless LLC equipment at the 88-foot level of the existing 100-foot tower would have an insignificant visual impact on the area around the monopole. Dish Wireless LLC ground equipment would be installed within the existing facility compound. Dish Wireless LLC shared use would therefore not cause any significant alteration in the physical or environmental characteristics of the existing site. Additionally, as evidenced by Exhibit F, the proposed antennas would not increase radio frequency emissions to a level at or above the Federal Communications Commission safety standard.

D. Economic Feasibility. Dish Wireless LLC will be entering into an agreement with the owner of this facility to mutually agreeable terms. As previously mentioned, the Letter of Authorization has been provided by the owner to assist Dish Wireless LLC with this tower share application.

E. Public Safety Concerns. As discussed above, the tower is structurally capable of supporting Dish Wireless LLC proposed loading. Dish Wireless LLC is not aware of any public safety concerns relative to the proposed sharing of the existing tower. Dish Wireless LLC intentions of providing new and improved wireless service through the shared use of this facility is expected to enhance the safety and welfare of local residents and individuals traveling through Unionville.

Sincerely,

Carolyn Seeley
Mobile: 978-760-5577
Fax: 413-521-0558
Office: 1053 Farmington Ave, Unit G, Farmington CT 06032
Email: cseeley@northeastsitesolutions.com



Attachments

Cc:

Kathleen A Blonski, Town Manager
Town of Farmington
1 Monteith Drive
Farmington, CT 06032

Shannon P.E. Rutherford
Town Planner
Town of Farmington
1 Monteith Drive
Farmington, CT 06032

Southern New England, Property Owner
401 Merritt 7
Norwalk, CT 06851

EIP Communications LLC, Tower Owner
Two Allegheny Center
Nova Tower 2, Suite 703
Pittsburgh, PA 15212

Exhibit A

Original Facility Approval



Victoria Masse <victoria@northeastitesolutions.com>

Dish Wireless- Request for Original Tower Approval- 82 Lovely St, Farmington CT

Sandra Michaud <michauds@farmington-ct.org>

Wed, Jan 12, 2022 at 11:50 AM

To: Victoria Masse <victoria@northeastitesolutions.com>, Russ Arnold <ArnoldR@farmington-ct.org>, Shannon Rutherford <rutherford@farmington-ct.org>, Bruce Cyr <cyrb@farmington-ct.org>

Cc: Carolyn Seeley <cseeley@northeastitesolutions.com>, Jason Berry <jberry@northeastitesolutions.com>, Chuck Regulbuto <chuck@northeastitesolutions.com>

Good morning Victoria

I have researched the Town Planning & Zoning Office records for the zoning approval of the original build at [82 Lovely Street](#). Although I could not locate the original site plan, I was able to obtain a copy of the 1953 Town Plan & Zoning Commission minutes and decision letter.

In 1964 a Special Exception was granted for an addition and then in 1969 a Special Exception was granted for the installation of a 100-foot radio tower. Those plans are attached to this email.

If you need anything additional from the Planning Office please let me know.

Thank you

Sandy

Sandra Michaud

Land Use Coordinator

Planning Division

Town of Farmington

[1 Monteith Drive](#)

[Farmington, CT 06032](#)





(860) 675-2325


From: Victoria Masse <victoria@northeastsitesolutions.com>
Sent: Tuesday, January 11, 2022 4:39 PM
To: Russ Arnold <ArnoldR@farmington-ct.org>; Shannon Rutherford <rutherfords@farmington-ct.org>; Bruce Cyr <cyrb@farmington-ct.org>; Sandra Michaud <michauds@farmington-ct.org>
Cc: Carolyn Seeley <cseeley@northeastsitesolutions.com>; Jason Berry <jberry@northeastsitesolutions.com>; Chuck Regulbuto <chuck@northeastsitesolutions.com>
Subject: Dish Wireless- Request for Original Tower Approval- 82 Lovely St, Farmington CT

Good Afternoon,


[Quoted text hidden]

4 attachments


-  **1953 Decision Letter.pdf**
126K
-  **TPZ Minutes 07-13-1953 - Utility Company.pdf**
418K
-  **Z6922 - Special Exception for 100 foot radio tower.pdf**
526K
-  **Z6414 - Special Exception for Addition.pdf**
3022K



SOUTH ELEVATION




NORTH ELEVATION




The Southern New England Telephone Co.
FARMINGTON ADD.
 DATE: _____ SCALE: 1/4" = 1'-0"
 DRAWN BY: _____
 REVISIONS: _____

3


26414-2



WEST ELEVATION





PLATFORM & STAIR DETAIL
SCALE 1/2" = 1'-0"



The Southern New England Telephone Co.

FARMINGTON ADD.	
DATE:	SCALE: As Shown.
DRAWN BY:	4
REVISIONS:	

Z-6914-3




THE SOUTHERN NEW ENGLAND TELEPHONE COMPANY - SPACE PLANNING ENGINEER

PARLINGTON-UNIONVILLE CENTRAL OFFICE - ASSIGN AREA - ISSUED 1/2-18-51

82 LOVELLY STREET - GROSS AREA - REVISED 9-26-53

PILOT - FLOOR PLAN - SCALE 1"=30' - ENGR EPP

7-6922



GENERAL NOTES:

1. Detail for Antenna Pole Bases shown on Drawing RA-542-E1, The Union Metal Manufacturing Company, Canton, Ohio.
2. Concrete to have 3500 p.s.i. compressive strength at 28 days. Slump range 2" to 4". Coarse and fine aggregate to conform to ASTM C33. Min. cement content 6.25 sacks per cu. yd. Provide 5% air by use of air-entraining agent.
3. Cement - Type I or Type II. Reinf. bars (including S18 used for anchorage) ASTM A-615, Grade 60.
4. Conform to "Building Code Requirements for Concrete Construction", ACI 318-63, for fabricating, details of construction and erection.
5. Cover for bars - 1-1/2"; 2" for bars over #5 size.
6. Forms - plywood coated with lacquer or non-staining mineral oil; rough lumber may be used below grade.
7. Finish - float finish.
8. Backfill - Well graded run-of-bank gravel or acceptable granular material from excavation. Compact in layers not over 8" thick for full height. Use finer material or sand, if necessary, between foundation and present walls similarly placed and tamped in layers.
9. Excavation depth and foundation bearing to be approved by SNET Co. Engineer before placing concrete. Bearing to be on natural undisturbed material.


GENERAL REQUIREMENTS

THE SOUTHERN NEW ENGLAND
TELEPHONE COMPANY


POLE ANTENNA
FOUNDATION

HENRY A. PFISTERER
AND ASSOCIATES ENGINEERS
424 CHAPEL ST. NEW HAVEN CONN.

DRAWN BY:	DRAWING NO.
CHKD. BY:	608-648
SCALE: AS NOTED	
DATE: 4-1-69	



TYPICAL BASE FOR 100' POLE



TYPICAL BOLT LAYOUT

2692E-3

PUBLIC HEARING, TOWN PLAN AND ZONING COMMISSION, TOWN HALL, UNIONVILLE,
JULY 13, 1953

The Public Hearing was called to order at 8:05 P.M. by Mrs. E. P. Dunne, Chairman. The Notice of Public Hearing was read by Mr. Sturdivant, Secretary, which is to hear the application of The Southern New England Telephone Company for authority to erect a branch office building on a parcel of land owned by Mae Y. Ritchie, located at the Northeast corner of Lovely Street and Sylvan Avenue, Unionville, with a frontage of about 180 feet on Lovely Street and 170 feet on Sylvan Avenue. The Notice was published in the Farmington Valley Herald, issues of July 2 and 9.

Charles F. Maloney, Building Engineer, represented the Telephone Company. He presented a plot plan showing location of the proposed building, keeping to the 40 ft. building line. The building would be 34' x 40' with 11' wing. He said the reason for it is to keep up with telephone growth; the most economical solution is a building in Unionville. It would be residential in character and appearance. They are not asking for a change of zone. The public will not be allowed in the building, just equipment, no business office, no storage, no motor vehicles, no sheds. A small area in back for a truck to come in to maintain the equipment, 2 or 3 trips a week. It will not be a disgrace to the neighborhood but will blend in with it; brick construction, fireproof, look like a large house; there are a number of trees on the property, they will blend it in with the trees.

Donald Lee who owns adjoining property asked if there are 2 lots in the plot. Mr. Maloney said he thinks 3 and this will take in all 3. The building would be put in the middle with good side yard clearance as they don't want anything right next to them that might be a fire hazard, don't want to take a chance on the equipment.

Harold Cromack spoke definitely in favor of the building.

Mr. Lee spoke in favor of it, as closest property owner.

Fred Anderson who also lives next to it favored it.

Ed Marsh, Sylvan Avenue, is in favor of it.

Mrs. Dunne asked if the building will be similar to the one in Farmington. Mr. Maloney said it will not and showed pictures of other buildings of similar size to the one proposed for Unionville.

Miss Martin of Sylvan Avenue asked what protection a property owner has buying in a residential district if the Commission makes these variances, or exceptions. Couldn't anyone come in and be given permission to have some other sort of business? After a bit of discussion Mr. Beach told her this is a permitted use under the zoning regulations after a Public Hearing; it is not a change of zone. Mr. Grouten added the Telephone Company could not sell the building for some other purpose after they have used it for a while.

Mr. Gunther said the area referred to is the only section he knows of where there is no commercial use of property. He wonders if this is the beginning of the end. Mr. Beach repeated his explanation. Mr. Gunther asked why this spot was chosen. Mr. Maloney said in the picking of a location all the lines are brought to a common center

TELEPHONE COMPANY HEARING, JULY 13, 1953-2

and this was it.

Mr. Lee asked if this is the last piece of available frontage from the center to the Avon Line on Lovely Street. Mr. Gunter said there is one more piece, between Parsons' and Hayes' but he thinks the town took it over for drainage.

Mr. Hodge said there was a sewer right of way there but the land has never been purchased by the Town.

Harry Simons asked if there would be any form of overhead service in connection with the building. Mr. Maloney said it will all be underground service into the building entirely, it will have no effect on television, that is guaranteed. He thinks Mr. Simons is thinking of a sub-station. The Telephone Company only uses 48 volts for the operation of the equipment.

The hearing was declared closed at 8:20 P.M.

Frederick Sturman
Secretary

Transcribed by Marion N. Keefe

July 15, 1953

The Southern New England Telephone Company
227 Church Street
New Haven, Connecticut

Att: Charles F. Maloney, Building Engineer

Gentlemen:

Your application for authority to erect a branch office building on a parcel of land located at the northeast corner of Lovely Street and Sylvan Avenue, Unionville, after being properly advertised, was presented at a Public Hearing in the Town Hall, Unionville, July 13, 1953.

Immediately following the Public Hearing, the Town Plan and Zoning Commission met in executive session, when your application was discussed further.

The members of the Commission voted unanimously to grant your application for authority to erect a branch office building on the parcel of land above referred to.

Very truly yours,

gs:mnk

Secretary, Farmington
Town Plan and Zoning Commission

Exhibit B

Property Card



Town of Farmington, CT

Property Listing Report

Map Block Lot

006 1

Building # 1

Unique Identifier

11350082

Property Information

Property Location	82 LOVELY ST
Mailing Address	401 MERRITT 7 - TAX DEPT NORWALK CT 06851
Land Use	Utility Building
Zoning Code	R20
Neighborhood	95

Owner	SOUTHERN NEW ENGLAND
Co-Owner	
Book / Page	0114/0169
Land Class	Commercial
Census Tract	4603
Acreage	0.67


Valuation Summary

(Assessed value = 70% of Appraised Value)

Item	Appraised	Assessed
Buildings	359244	251470
Outbuildings	0	0
Land	243880	170720
Total	603124	422190

Utility Information

Electric	No
Gas	No
Sewer	No
Public Water	No
Well	No



Primary Construction Details

Year Built	1965
Building Desc.	Commercial
Building Style	
Stories	1
Exterior Walls	Brick
Exterior Walls 2	
Interior Walls	Painted Concrete
Interior Walls 2	
Interior Floors 1	Tile
Interior Floors 2	

Heating Fuel	Natural Gas
Heating Type	FHA
AC Type	Central
Bedrooms	0
Full Bathrooms	0
Half Bathrooms	0
Extra Fixtures	0
Total Rooms	0
Bath Style	NA
Kitchen Style	
Occupancy	0

Building Use	Light Industrial
Building Condition	Average
Frame Type	C+
Fireplaces	0
Bsmt Gar	0
Fin Bsmt Area	
Fin Bsmt Quality	
Building Grade	0
Roof Style	
Roof Cover	Arch Shingles

Report Created On

4/9/2020




Exhibit C

Construction Drawings



DISH WIRELESS, LLC. SITE ID:

BOBDL00107A

DISH WIRELESS, LLC. SITE ADDRESS:

**82 LOVELY ST
UNIONVILLE, CT 06085**

SCOPE OF WORK	
THIS IS NOT AN ALL INCLUSIVE LIST. CONTRACTOR SHALL UTILIZE SPECIFIED EQUIPMENT PART OR ENGINEER APPROVED EQUIVALENT. CONTRACTOR SHALL VERIFY ALL NEEDED EQUIPMENT TO PROVIDE A FUNCTIONAL SITE. THE PROJECT GENERALLY CONSISTS OF THE FOLLOWING:	
TOWER SCOPE OF WORK:	
<ul style="list-style-type: none"> • INSTALL (3) PROPOSED PANEL ANTENNAS (1 PER SECTOR) • INSTALL (1) PROPOSED PLATFORM • INSTALL PROPOSED JUMPERS • INSTALL (6) PROPOSED RRUs (2 PER SECTOR) • INSTALL (1) PROPOSED OVER VOLTAGE PROTECTION DEVICE (OVP) • INSTALL (1) PROPOSED HYBRID CABLE 	
GROUND SCOPE OF WORK:	
<ul style="list-style-type: none"> • INSTALL (1) PROPOSED METAL PLATFORM • INSTALL (1) PROPOSED ICE BRIDGE • INSTALL (1) PROPOSED PPC CABINET • INSTALL (1) PROPOSED EQUIPMENT CABINET • INSTALL (1) PROPOSED POWER CONDUIT • INSTALL (1) PROPOSED TELCO CONDUIT • INSTALL (1) PROPOSED TELCO-FIBER BOX • INSTALL (1) PROPOSED GPS UNIT • INSTALL (1) PROPOSED SAFETY SWITCH (IF REQUIRED) • INSTALL (1) PROPOSED CIENA BOX (IF REQUIRED) • INSTALL (1) PROPOSED METER SOCKET 	


SITE INFORMATION	PROJECT DIRECTORY
PROPERTY OWNER: SOUTHERN NEW ENGLAND	APPLICANT: DISH WIRELESS, LLC. 5701 SOUTH SANTA FE DRIVE LITTLETON, CO 80120
ADDRESS: 82 LOVELY STREET FARMINGTON, CT 06085	TOWER OWNER: EIP COMMUNICATIONS I, LLC TWO ALLEGHENY CENTER NOVA TOWER 2, SUITE 703 PITTSBURGH PA 15212
TOWER TYPE: MONOPOLE	SITE DESIGNER: INFINIGY 1033 WATERVLJET SHAKER RD ALBANY, NY 12205 (518) 690-0790
TOWER CO SITE ID: TBD	SITE ACQUISITION: APRIL PARROTT TBD
TOWER APP NUMBER: 550445	CONSTRUCTION MANAGER: JAVIER SOTO TBD
COUNTY: HARTFORD	RF ENGINEER: TBD TBD
LATITUDE (NAD 83): 41° 45' 40.97" N 41.7614 N	
LONGITUDE (NAD 83): 72° 53' 15.18" W -72.8875 W	
ZONING JURISDICTION: R20	
ZONING DISTRICT: 95	
PARCEL NUMBER: 006 1	
OCCUPANCY GROUP: U	
CONSTRUCTION TYPE: V-B	
POWER COMPANY: TBD	
TELEPHONE COMPANY: AT&T	



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



INFINIGY
FROM ZERO TO INFINIGY
the solutions are endless
2500 W. HIGGINS RD. SUITE 500 |
HOFFMAN ESTATES, IL 60169
PHONE: 847-648-4068 | FAX: 518-690-0793
WWW.INFINIGY.COM



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: RCD	CHECKED BY: SS	APPROVED BY: CJW
RFDS REV #: N/A		

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
0	10/25/21	ISSUED FOR PERMIT
1	11/16/21	REVISED PER COMMENTS
2	12/08/21	REVISED PER COMMENTS

A&E PROJECT NUMBER
1197-F0001-C

DISH WIRELESS, LLC.
PROJECT INFORMATION
BOBDL00107A
UNIONVILLE CO
82 LOVELY ST
UNIONVILLE, CT 06085

SHEET TITLE
TITLE SHEET

SHEET NUMBER
T-1

SITE PHOTO



UNDERGROUND SERVICE ALERT CBYD 811
UTILITY NOTIFICATION CENTER OF CONNECTICUT
(800) 922-4455
WWW.CBYD.COM
CALL 2 WORKING DAYS UTILITY NOTIFICATION PRIOR TO CONSTRUCTION

GENERAL NOTES

THE FACILITY IS UNMANNED AND NOT FOR HUMAN HABITATION. A TECHNICIAN WILL VISIT THE SITE AS REQUIRED FOR ROUTINE MAINTENANCE. THE PROJECT WILL NOT RESULT IN ANY SIGNIFICANT DISTURBANCE OR EFFECT ON DRAINAGE. NO SANITARY SEWER SERVICE, POTABLE WATER, OR TRASH DISPOSAL IS REQUIRED AND NO COMMERCIAL SIGNAGE IS PROPOSED.


11"x17" PLOT WILL BE HALF SCALE UNLESS OTHERWISE NOTED

CONTRACTOR SHALL VERIFY ALL PLANS, EXISTING DIMENSIONS, AND CONDITIONS ON THE JOB SITE, AND SHALL IMMEDIATELY NOTIFY THE ENGINEER IN WRITING OF ANY DISCREPANCIES BEFORE PROCEEDING WITH THE WORK.

DIRECTIONS

DIRECTIONS FROM ORLANDO SANFORD INTERNATIONAL AIRPORT:
DEPART AND HEAD TOWARD MASSACO ST, TURN RIGHT ONTO MASSACO ST, TURN RIGHT ONTO US-202 W / CT-10 / HOPMEADOW ST, TURN RIGHT ONTO CT-167 / WEST ST, TURN LEFT TO STAY ON CT-167 / BUSHY HILL RD, TURN RIGHT ONTO HOLLISTER DR, TURN LEFT ONTO CT-177 / LOVELY ST, ARRIVE AT, 82 LOVELY ST, UNIONVILLE, CT 06085

VICINITY MAP



CONNECTICUT CODE COMPLIANCE

ALL WORK SHALL BE PERFORMED AND MATERIALS INSTALLED IN ACCORDANCE WITH THE CURRENT EDITIONS OF THE FOLLOWING CODES AS ADOPTED BY THE LOCAL GOVERNING AUTHORITIES. NOTHING IN THESE PLANS IS TO BE CONSTRUED TO PERMIT WORK NOT CONFORMING TO THESE CODES:



CODE TYPE	CODE
BUILDING	2018 CT STATE BUILDING CODE/2015 IBC W/ CT AMENDMENTS
MECHANICAL	2018 CT STATE BUILDING CODE/2015 IMC W/ CT AMENDMENTS
ELECTRICAL	2018 CT STATE BUILDING CODE/2017 NEC W/ CT AMENDMENTS

SHEET INDEX


SHEET NO.	SHEET TITLE
T-1	TITLE SHEET
A-1	OVERALL AND ENLARGED SITE PLAN
A-2	ELEVATION, ANTENNA LAYOUT AND SCHEDULE
A-3	EQUIPMENT PLATFORM AND H-FRAME DETAILS
A-4	EQUIPMENT DETAILS
A-5	EQUIPMENT DETAILS
A-6	EQUIPMENT DETAILS
E-1	ELECTRICAL ROUTE PLAN AND NOTES
E-2	ELECTRICAL DETAILS
E-3	ELECTRICAL ONE-LINE, FAULT CALCS & PANEL SCHEDULE
G-1	GROUNDING PLANS AND NOTES
G-2	GROUNDING DETAILS
G-3	GROUNDING DETAILS
RF-1	RF CABLE COLOR CODE
RF-2	RF PLUMBING DIAGRAM
GN-1	LEGEND AND ABBREVIATIONS
GN-2	GENERAL NOTES
GN-3	GENERAL NOTES
GN-4	GENERAL NOTES

NOTES


1. CONTRACTOR SHALL FIELD VERIFY ALL DIMENSIONS.
2. ANTENNA AND MW DISH SPECIFICATIONS REFER TO ANTENNA SCHEDULE AND TO FINAL CONSTRUCTION RFDS FOR ALL RF DETAILS
3. EXISTING EQUIPMENT AND FENCE OMITTED FOR CLARITY.
4. BASED ON THE MOUNT ANALYSIS COMPLETED BY INFINIGY DATED 07/30/2021, THE EXISTING ANTENNA MOUNTS ARE CAPABLE OF SUPPORTING THE PROPOSED EQUIPMENT CONFIGURATION
5. FOR ADDITIONAL TOWER STRUCTURAL INFORMATION SEE STRUCTURAL ANALYSIS COMPLETED BY ARMOR TOWER DATED: 09/17/21




PROPOSED WEST ELEVATION



1



ANTENNA LAYOUT



2

SECTOR	POSITION	ANTENNA						TRANSMISSION CABLE
		EXISTING OR PROPOSED	MANUFACTURER - MODEL NUMBER	TECHNOLOGY	SIZE (HxW)	AZMUTH	RAD CENTER	FEED LINE TYPE AND LENGTH
ALPHA	A1	PROPOSED	JMA WIRELESS - MX08FRO665-20	5G	72.0" x 20.0"	0°	88'-0"	(1) HIGH-CAPACITY HYBRID CABLE (TBD)
BETA	B1	PROPOSED	JMA WIRELESS - MX08FRO665-20	5G	72.0" x 20.0"	120°	88'-0"	
GAMMA	C1	PROPOSED	JMA WIRELESS - MX08FRO665-20	5G	72.0" x 20.0"	240°	88'-0"	

NOTES

1. CONTRACTOR TO REFER TO FINAL CONSTRUCTION RFDS FOR ALL RF DETAILS.
2. ANTENNA OR RRH MODELS MAY CHANGE DUE TO EQUIPMENT AVAILABILITY. ALL EQUIPMENT CHANGES MUST BE APPROVED AND REMAIN IN COMPLIANCE WITH THE PROPOSED DESIGN AND STRUCTURAL ANALYSES.

SECTOR	POSITION	RRH		NOTES
		MANUFACTURER - MODEL NUMBER	TECHNOLOGY	
ALPHA	A1	FUJITSU - TA08025-B604	5G	1. CONTRACTOR TO REFER TO FINAL CONSTRUCTION RFDS FOR ALL RF DETAILS. 2. ANTENNA AND RRH MODELS MAY CHANGE DUE TO EQUIPMENT AVAILABILITY. ALL EQUIPMENT CHANGES MUST BE APPROVED AND REMAIN IN COMPLIANCE WITH THE PROPOSED DESIGN AND STRUCTURAL ANALYSES.
	A1	FUJITSU - TA08025-B605	5G	
BETA	B1	FUJITSU - TA08025-B604	5G	
	B1	FUJITSU - TA08025-B605	5G	
GAMMA	C1	FUJITSU - TA08025-B604	5G	
	C1	FUJITSU - TA08025-B605	5G	

ANTENNA SCHEDULE

NO SCALE


3



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



INFINIGY
FROM ZERO TO INFINIGY
the solutions are endless
2500 W. HIGGINS RD., SUITE 500 |
HOFFMAN ESTATES, IL 60169
PHONE: 847-648-4068 | FAX: 518-690-0793
WWW.INFINIGY.COM



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:
RCD SS CJW

RFDS REV #: N/A

CONSTRUCTION DOCUMENTS


SUBMITTALS		
REV	DATE	DESCRIPTION
0	10/25/21	ISSUED FOR PERMIT
1	11/16/21	REVISED PER COMMENTS
2	12/08/21	REVISED PER COMMENTS

A&E PROJECT NUMBER
1197-F0001-C


DISH WIRELESS, LLC.
PROJECT INFORMATION
BOBDL00107A
UNIONVILLE CO
82 LOVELY ST
UNIONVILLE, CT 06085

SHEET TITLE
ELEVATION, ANTENNA
LAYOUT AND SCHEDULE


SHEET NUMBER
A-2



PLATFORM EQUIPMENT PLAN




COMMSCOPE MTC4045LP 5X7 PLATFORM	
DIMENSIONS (HxWxD)	16"x84"x60"
TOTAL WEIGHT	423 LBS



PLATFORM DETAIL

NO SCALE 2

KENWOOD T1701KT5-5S H-FRAME	
UNISTRUT/SUPPORT RAIL	5
WEIGHT/ VOLUME	173.6 LBS



H-FRAME DETAIL

NO SCALE 3




NOT USED


NO SCALE 4

NOTES

- CONTRACTOR TO BURY PLATFORM FEET WITH A MINIMUM OF 2" OF FILL PER EXISTING SITE SURFACE
- WEED BARRIER FABRIC TO BE ADDED AT DISCRETION OF DISH WIRELESS L.L.C. CONSTRUCTION MANAGER AT TIME OF CONSTRUCTION. ONE SHEET 8'x8' INSTALLED UNDER ALL FOUR FEET OF THE PLATFORM (4 MIL BLACK PLASTIC)
- EQUIPMENT CABINET OMITTED FOR CLARITY
- EXISTING GRADE BELOW PROPOSED EQUIPMENT CABINET TO BE LEVEL PRIOR TO INSTALLATION




FRONT ELEVATION



BACK ELEVATION


H-FRAME EQUIPMENT ELEVATION



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



INFINIGY
FROM ZERO TO INFINIGY
the solutions are endless
2500 W. HIGGINS RD., SUITE 500 |
HOFFMAN ESTATES, IL 60169
PHONE: 847-648-4068 | FAX: 518-690-0793
WWW.INFINIGY.COM



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
RCD	SS	CJW
RFDS REV #:	N/A	

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
0	10/25/21	ISSUED FOR PERMIT
1	11/16/21	REVISED PER COMMENTS
2	12/08/21	REVISED PER COMMENTS

A&E PROJECT NUMBER
1197-F0001-C

DISH WIRELESS, LLC.
PROJECT INFORMATION
BOBDL00107A
UNIONVILLE CO
82 LOVELY ST
UNIONVILLE, CT 06085

SHEET TITLE
EQUIPMENT PLATFORM AND
H-FRAME DETAILS

SHEET NUMBER
A-3

CHARLES INDUSTRY HEX CUBE-PM369155N4	
DIMENSIONS (HxWxD):	74"x32"x32"
POWER PLANT:	-48VDC ABB
TOTAL WEIGHT (EMPTY)	394 LBS

PLAN

SIDE BACK SIDE FRONT

CABINET DETAIL NO SCALE 1

RAYCAP RDIAC-6512-P-240-MTS POWER & TELCO PROTECTION CABINET	
DIMENSIONS (HxWxD)	40"x20"x10"
WEIGHT/ VOLUME	124 LBS
MANUAL TRANSFER SWITCH	200A
LOAD CENTER	30 POSITION
MAIN BREAKER	200A, 65KA AIC
GENERATOR RECEPTACLE	CAMLOCK
NEMA RATING	3R POWDER COATED ALUMINUM
SURGE PROTECTION DEVICE	UL 1449 4TH EDITION LISTED

PLAN

SIDE FRONT

POWER PROTECTION CABINET (PPC) DETAIL NO SCALE 2

SQUARE D SAFETY SWITCH D324NRB	
ENCLOSURE DIM (HxWxD)	29.25"x17.25"x8.25"
TOTAL WEIGHT (EMPTY)	45.33 LBS
MAX VOLTAGE/AMPS/WATT	240V/200A/48000W
ENCLOSURE RATING	OUTDOOR NEMA 3R

PLAN

SIDE BACK FRONT

SAFETY SWITCH NO SCALE 3

EATON METER SOCKET UNRRS213BEUSE	
METER SOCKET TYPE	RING
ENCLOSURE DIM (HxWxD)	16"x12"x6"
MAIN AMPERE RATING	200A
WEIGHT	18 LBS

PLAN

SIDE BACK FRONT

METER SOCKET DETAIL NO SCALE 4

CIENA 3931 SERVICE DELIVERY SWITCH	
DIMENSIONS (HxWxD)	17.0"x16.8"x7.0" 431x427x178mm
WEIGHT	28.6 LBS/13.0 KG
POWER INPUT	60W MAX

PLAN

FRONT SIDE BACK

CIENA DETAIL NO SCALE 5

CHARLES FIBER TELCO ENCLOSURE CUBE-MP1818WB-A	
ENCLOSURE DIM (HxWxD)	18.0"x18.0"x9.25"
NEMA RATING	4X
THERMAL	SEALED
MOUNTING BACKBOARD	WOOD

PLAN

SIDE BACK FRONT

FIBER TELCO ENCLOSURE DETAIL NO SCALE 6

COMMSCOPE WB-K110-B WAVEGUIDE BRIDGE KIT		INCLUDED PRODUCTS:	WB-T12-3 TRAPEZE KIT, 3 RUNGS
DIMENSIONS (HxL)	160"x10'	WB-LB12-3 SUPPORT BRACKET	
WEIGHT/ VOLUME	325.0 LBS	MF-130 DIRECT BURIAL PIPE COLUMN, 13'-4"	
CABLE RUN (QTY)	12		

PLAN FRONT SIDE

ICE BRIDGE DETAIL NO SCALE 7

FINISH SLOPE TO DRAIN

A-A

PROPOSED 3.5" DIA. SCH 40 PIPE GALVANIZED

PROPOSED 1'-6" DIA. CONCRETE PIER (TYP)

CONCRETE PIER

3" DIA SCH 40 PIPE

18" DIA DRILLED PIER FOUNDATION

A-A SECTION

TYPICAL ICE BRIDGE CONCRETE PIER DETAIL NO SCALE 8

PROPOSED ICE BRIDGE

PROPOSED X" DIA HYBRID CABLE (OPTION "A")

PROPOSED X" DIA HYBRID CABLE (OPTION "B")

PROPOSED CABLE CLAMP @ 3'-0" O.C.

HYBRID SUPPORT BRACKET AND BANDING @ 10'-0" O.C.

EXISTING ENTRY PORT

EXISTING MONOPOLE

HYBRID CABLE RUN NO SCALE 9

5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120

Turnkey Wireless Development

FROM ZERO TO INFINIGY

the solutions are endless

2500 W. HIGGINS RD., SUITE 500 |
HOFFMAN ESTATES, IL 60169
PHONE: 847-648-4068 | FAX: 518-690-0793
WWW.INFINIGY.COM

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:

RCD SS CJW

RFDS REV #: N/A

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
0	10/25/21	ISSUED FOR PERMIT
1	11/16/21	REVISED PER COMMENTS
2	12/08/21	REVISED PER COMMENTS




A&E PROJECT NUMBER
1197-F0001-C

DISH WIRELESS, LLC.
PROJECT INFORMATION
BOBDL00107A
UNIONVILLE CO
82 LOVELY ST
UNIONVILLE, CT 06085

SHEET TITLE
EQUIPMENT DETAILS

SHEET NUMBER
A-4

ROSENBERGER GPSGLONASS-36-N-S	
DIMENSION (DIA x H)	69mm x 98.5mm
WEIGHT (WITH ACCESSORIES)	515.74g
CONNECTOR	N-FEMALE
FREQUENCY RANGE	1559 MHz ~ 1610.5MHz



GPS ANTENNA DETAIL NO SCALE 1

GPS MINIMUM SKY VIEW REQUIREMENTS NO SCALE 2

NOT USED NO SCALE 3

NOT USED NO SCALE 4

NOT USED NO SCALE 5

NOT USED NO SCALE 6

NOT USED NO SCALE 7

NOT USED NO SCALE 8


NOT USED NO SCALE 9

dish
wireless.

5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



INFINIGY
FROM ZERO TO INFINIGY
the solutions are endless
2500 W. HIGGINS RD., SUITE 500 |
HOFFMAN ESTATES, IL 60169
PHONE: 847-648-4068 | FAX: 518-690-0793
WWW.INFINIGY.COM



IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:
RCD SS CJW
RFDS REV #: N/A

**CONSTRUCTION
DOCUMENTS**

SUBMITTALS		
REV	DATE	DESCRIPTION
0	10/25/21	ISSUED FOR PERMIT
1	11/16/21	REVISED PER COMMENTS
2	12/08/21	REVISED PER COMMENTS

A&E PROJECT NUMBER
1197-F0001-C


DISH WIRELESS, LLC.
PROJECT INFORMATION
BOBDL00107A
UNIONVILLE CO
82 LOVELY ST
UNIONVILLE, CT 06085

SHEET TITLE
EQUIPMENT DETAILS


SHEET NUMBER

A-5


FUJITSU TA08025-B604 RRH	
DIMENSIONS (HxWxD) (KG/IN)	380x400x200/14.9"x15.7"x7.8"
WEIGHT(KG,LB)/ VOLUME	29kg,63.9lb/ 30L
POWER SUPPLY	DC-58~-36V



PLAN



SIDE




FRONT


NOTES

FINAL RRH SPECIFICATIONS TO BE CONFIRMED BY GC


FUJITSU TA08025-B605 RRH	
DIMENSIONS (HxWxD) (KG/IN)	380x400x230/14.9"x15.7"x9.0"
WEIGHT(KG,LB)/ VOLUME	34kg,74.9lb/ 35L
POWER SUPPLY	DC-58~-36V



PLAN



SIDE





FRONT

NOTES

FINAL RRH SPECIFICATIONS TO BE CONFIRMED BY GC

SABRE INDUSTRIES RRU BRACKET MOUNT C10123155	
DIMENSIONS (HxWxD) (1 BRACKET)	5"x20"x1-13/16"
WEIGHT (FULL ASSEMBLY)	35.79 lbs
PACKAGE QUANTITY	4

ITEM#	DESCRIPTION
1	PLATE, CHANNEL BRACKET
2	RRH Z BRACKET, 3/16"
3	THREADED ROD ASSEMBLY 1/2"x12"



REMOTE RADIO MOUNT DETAIL

NO SCALE 3

REMOTE RADIO HEAD DETAIL

NO SCALE 1


REMOTE RADIO HEAD DETAIL

NO SCALE 2


RAYCAP RDIC-9181-PF-48 DC SURGE PROTECTION	
DIMENSIONS (HxWxD)	18.98"x14.39"x8.15"
WEIGHT	21.82 LBS




PLAN



SIDE



BACK




FRONT


SURGE SUPPRESSION DETAIL

NO SCALE 4

JMA WIRELESS MX08FR0665-20 ANTENNA	
DIMENSIONS (HxWxD)	72.0"x20.0"x8.0"
TOTAL WEIGHT	54 LB
RF PORTS, CONNECTOR TYPE	8 x 4.3-10 FEMALE



PLAN



NOTES


FINAL ANTENNA SPECIFICATIONS TO BE CONFIRMED BY GC

ANTENNA DETAIL

NO SCALE 5

JMA MOUNTING BRACKET

WIDTH	5"
DEPTH	2"
HEIGHT	8"
TOTAL WEIGHT	1.5 lbs
HOUSING MATERIAL	ASA/ABS/ALUMINUM
RADOME COLOR	LIGHT GRAY
CONNECTOR	1x8-PIN DAISY CHAIN




NOTE:
OR DISH Wireless L.L.C.
APPROVED EQUIVALENT

ANTENNA MOUNTING DETAIL

NO SCALE 6


COMMSCOPE XP-2040 CROSSOVER PLATE	
DIMENSIONS (HxW)	10"x12"
WEIGHT	11.023 LBS



RRH/OVP MOUNT DETAIL

NO SCALE 7

SITEPRO1 SNP8HR-396 SNUB-NOSE PLATFORM	
FACE SIZE	8'-0"
WEIGHT	1786.28 LB
ANTENNA PIPE MOUNTS	(6) 2-3/8" O.D.



ANTENNA PLATFORM DETAIL

NO SCALE 8

NOT USED


NO SCALE 9



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



INFINIGY
FROM ZERO TO INFINIGY
the solutions are endless
2500 W. HIGGINS RD., SUITE 500 J
HOFFMAN ESTATES, IL 60169
PHONE: 847-648-4068 | FAX: 518-690-0793
WWW.INFINIGY.COM



IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:
RCD SS CJW

RFDS REV #: N/A

**CONSTRUCTION
DOCUMENTS**

SUBMITTALS		
REV	DATE	DESCRIPTION
0	10/25/21	ISSUED FOR PERMIT
1	11/16/21	REVISED PER COMMENTS
2	12/08/21	REVISED PER COMMENTS


A&E PROJECT NUMBER
1197-F0001-C

DISH WIRELESS, LLC.
PROJECT INFORMATION
BOBDL00107A
UNIONVILLE CO
82 LOVELY ST
UNIONVILLE, CT 06085

SHEET TITLE
EQUIPMENT DETAILS

SHEET NUMBER
A-6

EXISTING UTILITY POLE #: 625



LOVELY ST

NOTES


1. CONTRACTOR SHALL FIELD VERIFY ALL PROPOSED UNDERGROUND UTILITY CONDUIT ROUTE.
2. ANTENNAS AND MOUNTS OMITTED FOR CLARITY.

DC POWER WIRING SHALL BE COLOR CODED AT EACH END FOR IDENTIFYING +24V AND -48V CONDUCTORS. RED MARKINGS SHALL IDENTIFY +24V AND BLUE MARKINGS SHALL IDENTIFY -48V.

1. CONTRACTOR SHALL INSPECT THE EXISTING CONDITIONS PRIOR TO SUBMITTING A BID. ANY QUESTIONS ARISING DURING THE BID PERIOD IN REGARDS TO THE CONTRACTOR'S FUNCTIONS, THE SCOPE OF WORK, OR ANY OTHER ISSUE RELATED TO THIS PROJECT SHALL BE BROUGHT UP DURING THE BID PERIOD WITH THE PROJECT MANAGER FOR CLARIFICATION, NOT AFTER THE CONTRACT HAS BEEN AWARDED.
2. ALL ELECTRICAL WORK SHALL BE DONE IN ACCORDANCE WITH CURRENT NATIONAL ELECTRICAL CODES AND ALL STATE AND LOCAL CODES, LAWS, AND ORDINANCES. PROVIDE ALL COMPONENTS AND WIRING SIZES AS REQUIRED TO MEET NEC STANDARDS.
3. LOCATION OF EQUIPMENT, CONDUIT AND DEVICES SHOWN ON THE DRAWINGS ARE APPROXIMATE AND SHALL BE COORDINATED WITH FIELD CONDITIONS PRIOR TO CONSTRUCTION.
4. CONDUIT ROUGH-IN SHALL BE COORDINATED WITH THE MECHANICAL EQUIPMENT TO AVOID LOCATION CONFLICTS. VERIFY WITH THE MECHANICAL EQUIPMENT CONTRACTOR AND COMPLY AS REQUIRED.
5. CONTRACTOR SHALL PROVIDE ALL BREAKERS, CONDUITS AND CIRCUITS AS REQUIRED FOR A COMPLETE SYSTEM.
6. CONTRACTOR SHALL PROVIDE PULL BOXES AND JUNCTION BOXES AS REQUIRED BY THE NEC ARTICLE 314.
7. CONTRACTOR SHALL PROVIDE ALL STRAIN RELIEF AND CABLE SUPPORTS FOR ALL CABLE ASSEMBLIES. INSTALLATION SHALL BE IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS AND RECOMMENDATIONS.
8. ALL DISCONNECTS AND CONTROLLING DEVICES SHALL BE PROVIDED WITH ENGRAVED PHENOLIC NAMEPLATES INDICATING EQUIPMENT CONTROLLED, BRANCH CIRCUITS INSTALLED ON, AND PANEL FIELD LOCATIONS FED FROM.
9. INSTALL AN EQUIPMENT GROUNDING CONDUCTOR IN ALL CONDUITS PER THE SPECIFICATIONS AND NEC 250. THE EQUIPMENT GROUNDING CONDUCTORS SHALL BE BONDED AT ALL JUNCTION BOXES, PULL BOXES, AND ALL DISCONNECT SWITCHES, AND EQUIPMENT CABINETS.
10. ALL NEW MATERIAL SHALL HAVE A U.L. LABEL.
11. PANEL SCHEDULE LOADING AND CIRCUIT ARRANGEMENTS REFLECT POST-CONSTRUCTION EQUIPMENT.
12. CONTRACTOR SHALL BE RESPONSIBLE FOR AS-BUILT PANEL SCHEDULE AND SITE DRAWINGS.
13. FIBER ROUTE IS PRELIMINARY, FINAL FIBER ROUTE TO BE DETERMINED ONCE UCR (UTILITY COORDINATION REPORT) HAS BEEN FINALIZED.



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



12/8/2021

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: RCD | CHECKED BY: SS | APPROVED BY: CJW

RFDS REV #: N/A

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
0	10/25/21	ISSUED FOR PERMIT
1	11/16/21	REVISED PER COMMENTS
2	12/08/21	REVISED PER COMMENTS

A&E PROJECT NUMBER
1197-F0001-C

DISH WIRELESS, LLC.
PROJECT INFORMATION
BOBDL00107A
UNIONVILLE CO
82 LOVELY ST
UNIONVILLE, CT 06085

SHEET TITLE
ELECTRICAL/FIBER ROUTE
PLAN AND NOTES

SHEET NUMBER
E-1

ELECTRICAL NOTES




2

EXISTING FIBER DEMARC NOT LOCATED AT TIME OF SITE VISIT. CONTRACTOR TO INSTALL NEW FIBER CONDUITS TO EXISTING FIBER SOURCE ON NEAREST EXISTING UTILITY POLE OR MEET ME POINT/HAND HOLE, EXACT LOCATION TO BE DETERMINED WITH FIBER PROVIDER PRIOR TO INSTALLATION


EXISTING POWER TO BE TAKEN FROM EXISTING UTILITY POLE. CONTRACTOR TO COORDINATE INSTALLATION OF PROPOSED POWER FEEDERS WITH UTILITY COMPANY AND PROPERTY OWNER PRIOR TO CONSTRUCTION

PROPOSED UNDERGROUND POWER CONDUIT. EXISTING CONDUIT TO BE USED WHERE POSSIBLE AND INTERCEPT WITH PROPOSED CONDUIT AS NEEDED TO ROUTE TO PROPOSED PAD (PENDING POWER DESIGN AND UTILITY COORDINATION REPORT) (LENGTH: 200')

PROPOSED UNDERGROUND FIBER CONDUIT (PENDING FIBER DESIGN AND UTILITY COORDINATION REPORT) (LENGTH: 200')




UTILITY ROUTE PLAN




1

OVERALL UTILITY ROUTE PLAN



3



CARLON EXPANSION FITTINGS				
COUPLING END PART#	MALE TERMINAL ADAPTER END PART#	SIZE	STD CTN QTY.	TRAVEL LENGTH
E945D	E945DX	1/2"	20	4"
E945E	E945EX	3/4"	15	4"
E945F	E945FX	1"	10	4"
E945G	E945GX	1 1/4"	5	4"
E945H	E945HX	1 1/2"	5	4"
E945J	E945JX	2"	15	8"
E945K	E945KX	2 1/2"	10	8"
E945L	E945LX	3"	10	8"
E945M	E945MX	3 1/2"	5	8"
E945N	E945NX	4"	5	8"
E945P	E945PX	5"	1	8"
E945R	E945RX	6"	1	8"



NOTE: CONTRACTOR TO INSTALL EXPANSION FITTING SLIP JOINT AT METER CENTER CONDUIT TERMINATION, AS PER LOCAL UTILITY POLICY, ORDINANCE AND/OR SPECIFIED REQUIREMENT.

TRENCHING NOTES

- CONTRACTOR SHALL RESTORE THE TRENCH TO ITS ORIGINAL CONDITIONS BY EITHER SEEDING OR SODDING GRASS AREAS, OR REPLACING ASPHALT OR CONCRETE AREAS TO ITS ORIGINAL CROSS SECTION.
- TRENCHING SAFETY; INCLUDING, BUT NOT LIMITED TO SOIL CLASSIFICATION, SLOPING, AND SHORING, SHALL BE GOVERNED BY THE CURRENT OSHA TRENCHING AND EXCAVATION SAFETY STANDARDS.
- ALL CONDUITS SHALL BE INSTALLED IN COMPLIANCE WITH THE CURRENT NATIONAL ELECTRIC CODE (NEC) OR AS REQUIRED BY THE LOCAL JURISDICTION, WHICHEVER IS THE MOST STRINGENT.



EXPANSION JOINT DETAIL


NO SCALE 1

TYPICAL UNDERGROUND TRENCH DETAIL

NO SCALE 2

DARK TELCO BOX – INTERIOR WIRING LAYOUT

NO SCALE 3



LIT TELCO BOX – INTERIOR WIRING LAYOUT

NO SCALE 4

NOT USED

NO SCALE 5

NOT USED

NO SCALE 6

NOT USED

NO SCALE 7

NOT USED

NO SCALE 8

NOT USED


NO SCALE 9



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



INFINIGY
FROM ZERO TO INFINIGY
the solutions are endless
2500 W. HIGGINS RD., SUITE 500 |
HOFFMAN ESTATES, IL 60169
PHONE: 847-648-4068 | FAX: 518-690-0793
WWW.INFINIGY.COM



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: RCD CHECKED BY: SS APPROVED BY: CJW

RFDS REV #: N/A

CONSTRUCTION DOCUMENTS


SUBMITTALS		
REV	DATE	DESCRIPTION
0	10/25/21	ISSUED FOR PERMIT
1	11/16/21	REVISED PER COMMENTS
2	12/08/21	REVISED PER COMMENTS

A&E PROJECT NUMBER
1197-F0001-C

DISH WIRELESS, LLC.
PROJECT INFORMATION
BOBDL00107A
UNIONVILLE CO
82 LOVELY ST
UNIONVILLE, CT 06085

SHEET TITLE
ELECTRICAL
DETAILS

SHEET NUMBER
E-2




TYPICAL EQUIPMENT GROUNDING PLAN

NO SCALE 1


NOTES

1. ANTENNAS AND OVP SHOWN ARE GENERIC AND NOT REFERENCING TO A SPECIFIC MANUFACTURER. THIS LAYOUT IS FOR REFERENCE ONLY



TYPICAL ANTENNA GROUNDING PLAN

NO SCALE 2



GROUNDING LEGEND

1. GROUNDING IS SHOWN DIAGRAMMATICALLY ONLY.
2. CONTRACTOR SHALL GROUND ALL EQUIPMENT AS A COMPLETE SYSTEM. GROUNDING SHALL BE IN COMPLIANCE WITH NEC SECTION 250 AND DISH WIRELESS, LLC. GROUNDING AND BONDING REQUIREMENTS AND MANUFACTURER'S SPECIFICATIONS.
3. ALL GROUND CONDUCTORS SHALL BE COPPER; NO ALUMINUM CONDUCTORS SHALL BE USED.

GROUNDING KEY NOTES


- (A) **EXTERIOR GROUND RING:** #2 AWG SOLID COPPER, BURIED AT A DEPTH OF AT LEAST 30 INCHES BELOW GRADE, OR 6 INCHES BELOW THE FROST LINE AND APPROXIMATELY 24 INCHES FROM THE EXTERIOR WALL OR FOOTING.
- (B) **TOWER GROUND RING:** THE GROUND RING SYSTEM SHALL BE INSTALLED AROUND AN ANTENNA TOWER'S LEGS, AND/OR GUY ANCHORS. WHERE SEPARATE SYSTEMS HAVE BEEN PROVIDED FOR THE TOWER AND THE BUILDING, AT LEAST TWO BONDS SHALL BE MADE BETWEEN THE TOWER RING GROUND SYSTEM AND THE BUILDING RING GROUND SYSTEM USING MINIMUM #2 AWG SOLID COPPER CONDUCTORS.
- (C) **INTERIOR GROUND RING:** #2 AWG STRANDED GREEN INSULATED COPPER CONDUCTOR EXTENDED AROUND THE PERIMETER OF THE EQUIPMENT AREA. ALL NON-TELECOMMUNICATIONS RELATED METALLIC OBJECTS FOUND WITHIN A SITE SHALL BE GROUNDED TO THE INTERIOR GROUND RING WITH #6 AWG STRANDED GREEN INSULATED CONDUCTOR.
- (D) **BOND TO INTERIOR GROUND RING:** #2 AWG SOLID TINNED COPPER WIRE PRIMARY BONDS SHALL BE PROVIDED AT LEAST AT FOUR POINTS ON THE INTERIOR GROUND RING, LOCATED AT THE CORNERS OF THE BUILDING.
- (E) **GROUND ROD:** UL LISTED COPPER CLAD STEEL MINIMUM 1/2" DIAMETER BY EIGHT FEET LONG. GROUND RODS SHALL BE INSTALLED WITH INSPECTION SLEEVES. GROUND RODS SHALL BE DRIVEN TO THE DEPTH OF GROUND RING CONDUCTOR.
- (F) **CELL REFERENCE GROUND BAR:** POINT OF GROUND REFERENCE FOR ALL COMMUNICATIONS EQUIPMENT FRAMES. ALL BONDS ARE MADE WITH #2 AWG UNLESS NOTED OTHERWISE STRANDED GREEN INSULATED COPPER CONDUCTORS. BOND TO GROUND RING WITH (2) #2 SOLID TINNED COPPER CONDUCTORS.
- (G) **HATCH PLATE GROUND BAR:** BOND TO THE INTERIOR GROUND RING WITH TWO #2 AWG STRANDED GREEN INSULATED COPPER CONDUCTORS. WHEN A HATCH-PLATE AND A CELL REFERENCE GROUND BAR ARE BOTH PRESENT, THE CRGB MUST BE CONNECTED TO THE HATCH-PLATE AND TO THE INTERIOR GROUND RING USING (2) TWO #2 AWG STRANDED GREEN INSULATED COPPER CONDUCTORS EACH.
- (H) **EXTERIOR CABLE ENTRY PORT GROUND BARS:** LOCATED AT THE ENTRANCE TO THE CELL SITE BUILDING. BOND TO GROUND RING WITH A #2 AWG SOLID TINNED COPPER CONDUCTORS WITH AN EXOTHERMIC WELD AND INSPECTION SLEEVE.
- (J) **TELCO GROUND BAR:** BOND TO BOTH CELL REFERENCE GROUND BAR OR EXTERIOR GROUND RING.
- (K) **FRAME BONDING:** THE BONDING POINT FOR TELECOM EQUIPMENT FRAMES SHALL BE THE GROUND BUS THAT IS NOT ISOLATED FROM THE EQUIPMENTS METAL FRAMEWORK.
- (L) **INTERIOR UNIT BONDS:** METAL FRAMES, CABINETS AND INDIVIDUAL METALLIC UNITS LOCATED WITH THE AREA OF THE INTERIOR GROUND RING REQUIRE A #6 AWG STRANDED GREEN INSULATED COPPER BOND TO THE INTERIOR GROUND RING.
- (M) **FENCE AND GATE GROUNDING:** METAL FENCES WITHIN 7 FEET OF THE EXTERIOR GROUND RING OR OBJECTS BONDED TO THE EXTERIOR GROUND RING SHALL BE BONDED TO THE GROUND RING WITH A #2 AWG SOLID TINNED COPPER CONDUCTOR AT AN INTERVAL NOT EXCEEDING 25 FEET. BONDS SHALL BE MADE AT EACH GATE POST AND ACROSS GATE OPENINGS.
- (N) **EXTERIOR UNIT BONDS:** METALLIC OBJECTS, EXTERNAL TO OR MOUNTED TO THE BUILDING, SHALL BE BONDED TO THE EXTERIOR GROUND RING. USING #2 TINNED SOLID COPPER WIRE
- (P) **ICE BRIDGE SUPPORTS:** EACH ICE BRIDGE LEG SHALL BE BONDED TO THE GROUND RING WITH #2 AWG BARE TINNED COPPER CONDUCTOR. PROVIDE EXOTHERMIC WELDS AT BOTH THE ICE BRIDGE LEG AND BURIED GROUND RING.
- (Q) **DURING ALL DC POWER SYSTEM CHANGES INCLUDING DC SYSTEM CHANGE OUTS, RECTIFIER REPLACEMENTS OR ADDITIONS, BREAKER DISTRIBUTION CHANGES, BATTERY ADDITIONS, BATTERY REPLACEMENTS AND INSTALLATIONS OR CHANGES TO DC CONVERTER SYSTEMS IT SHALL BE REQUIRED THAT SERVICE CONTRACTORS VERIFY ALL DC POWER SYSTEMS ARE EQUIPPED WITH A MASTER DC SYSTEM RETURN GROUND CONDUCTOR FROM THE DC POWER SYSTEM COMMON RETURN BUS DIRECTLY CONNECTED TO THE CELL SITE REFERENCE GROUND BAR**
- (R) **TOWER TOP COLLECTOR BUSS BAR IS TO BE MECHANICALLY BONDED TO PROPOSED ANTENNA MOUNT COLLAR. REFER TO DISH WIRELESS, LLC. GROUNDING NOTES.**

GROUNDING KEY NOTES

NO SCALE 3



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
RCD	SS	CJW

RFDS REV #: N/A

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
0	10/25/21	ISSUED FOR PERMIT
1	11/16/21	REVISED PER COMMENTS
2	12/08/21	REVISED PER COMMENTS


A&E PROJECT NUMBER
1197-F0001-C

DISH WIRELESS, LLC.
PROJECT INFORMATION
BOBDL00107A
UNIONVILLE CO
82 LOVELY ST
UNIONVILLE, CT 06085

SHEET TITLE
GROUNDING PLANS AND NOTES


SHEET NUMBER
G-1

NOTES
EQUIPMENT CABINET OMITTED FOR CLARITY




H-FRAME GROUNDING DETAIL

NO SCALE 1



TRANSITIONING GROUND DETAIL


NO SCALE 4



TYPICAL TEST GROUND ROD WITH INSPECTION SLEEVE


NO SCALE 5

NOTES
CABLE GROUNDING NOT REQUIRED WHEN ANTENNA IS LESS THAN 10' FROM CABINET



TYPICAL GPS UNIT GROUNDING

NO SCALE 2



OUTDOOR CABINET GROUNDING

NO SCALE 3

SUBMITTALS		
REV	DATE	DESCRIPTION
0	10/25/21	ISSUED FOR PERMIT
1	11/16/21	REVISED PER COMMENTS
2	12/08/21	REVISED PER COMMENTS
A&E PROJECT NUMBER 1197-F0001-C		
DISH WIRELESS, LLC. PROJECT INFORMATION BOBDL00107A UNIONVILLE CO 82 LOVELY ST UNIONVILLE, CT 06085		
SHEET TITLE GROUNDING DETAILS		
SHEET NUMBER G-2		

NOT USED

NO SCALE 6

dish wireless.
5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120

NSS NORTHEAST SITE SOLUTIONS
Turnkey Wireless Development

INFINIGY
FROM ZERO TO INFINIGY
the solutions are endless
2500 W. HIGGINS RD., SUITE 500 |
HOFFMAN ESTATES, IL 60169
PHONE: 847-648-4068 | FAX: 518-690-0793
WWW.INFINIGY.COM



STATE OF CONNECTICUT
HUHEI SAKANQUE
34916
LICENSED PROFESSIONAL ENGINEER
12/8/2021

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:
RCD SS CJW
RFDS REV #: N/A

CONSTRUCTION DOCUMENTS

1. EXOTHERMIC WELD (2) TWO, #2 AWG BARE TINNED SOLID COPPER CONDUCTORS TO GROUND BAR. ROUTE CONDUCTORS TO BURIED GROUND RING AND PROVIDE PARALLEL EXOTHERMIC WELD.
2. ALL EXTERIOR GROUNDING HARDWARE SHALL BE STAINLESS STEEL 3/8" DIAMETER OR LARGER. ALL HARDWARE 18-8 STAINLESS STEEL INCLUDING LOCK WASHERS, COAT ALL SURFACES WITH AN ANTI-OXIDANT COMPOUND BEFORE MATING.
3. FOR GROUND BOND TO STEEL ONLY: COAT ALL SURFACES WITH AN ANTI-OXIDANT COMPOUND BEFORE MATING.
4. DO NOT INSTALL CABLE GROUNDING KIT AT A BEND AND ALWAYS DIRECT GROUND CONDUCTOR DOWN TO GROUNDING BUS.
5. NUT & WASHER SHALL BE PLACED ON THE FRONT SIDE OF THE GROUND BAR AND BOLTED ON THE BACK SIDE.
6. ALL GROUNDING PARTS AND EQUIPMENT TO BE SUPPLIED AND INSTALLED BY CONTRACTOR.
7. THE CONTRACTOR SHALL BE RESPONSIBLE FOR INSTALLING ADDITIONAL GROUND BAR AS REQUIRED.
9. ENSURE THE WIRE INSULATION TERMINATION IS WITHIN 1/8" OF THE BARREL (NO SHINERS).



TYPICAL GROUNDING NOTES


NO SCALE 1

TYPICAL EXTERIOR TWO HOLE LUG

NO SCALE 2

TYPICAL INTERIOR TWO HOLE LUG

NO SCALE 3



LUG DETAIL

NO SCALE 4

NOT USED

NO SCALE 5

NOT USED

NO SCALE 6

NOT USED

NO SCALE 7

NOT USED

NO SCALE 8

NOT USED


NO SCALE 9

dish
wireless.

5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120

NSS NORTHEAST
SITE SOLUTIONS
Turnkey Wireless Development

INFINIGY
FROM ZERO TO INFINIGY
the solutions are endless
2500 W. HIGGINS RD., SUITE 500 |
HOFFMAN ESTATES, IL 60169
PHONE: 847-648-4068 | FAX: 518-690-0793
WWW.INFINIGY.COM



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:
RCD SS CJW

RFDS REV #: N/A

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
0	10/25/21	ISSUED FOR PERMIT
1	11/16/21	REVISED PER COMMENTS
2	12/08/21	REVISED PER COMMENTS

A&E PROJECT NUMBER
1197-F0001-C

DISH WIRELESS, LLC.
PROJECT INFORMATION
BOBDL00107A
UNIONVILLE CO
82 LOVELY ST
UNIONVILLE, CT 06085

SHEET TITLE
GROUNDING DETAILS


SHEET NUMBER
G-3

RF JUMPER COLOR CODING

3/4" TAPE WIDTHS WITH 3/4" SPACING


LOW-BAND RRH -
(600MHz N71 BASEBAND) +
(850MHz N26 BAND) +
(700MHz N29 BAND) - OPTIONAL PER MARKET

ADD FREQUENCY COLOR TO SECTOR BAND
(CBRS WILL USE YELLOW BANDS)



MID-BAND RRH -
(AWS BANDS N66+N70)

ADD FREQUENCY COLOR TO SECTOR BAND
(CBRS WILL USE YELLOW BANDS)




HYBRID/DISCREET CABLES

INCLUDE SECTOR BANDS BEING SUPPORTED AMONG WITH FREQUENCY BANDS


EXAMPLE 1 - HYBRID, OR DISCREET, SUPPORTS ALL SECTORS, BOTH LOW-BANDS AND MID-BANDS

EXAMPLE 2 - HYBRID, OR DISCREET, SUPPORTS CBRS ONLY, ALL SECTORS




HYBRID/DISCREET CABLES

LOW-BAND RRH FIBER CABLES HAVE SECTOR STRIPE ONLY




POWER CABLES TO RRHs

LOW-BAND RRH POWER CABLES HAVE SECTOR STRIPE ONLY




RET MOTORS AT ANTENNAS



MICROWAVE RADIO LINKS

LINKS WILL HAVE A 1.5-2 INCH WHITE WRAP WITH THE AZIMUTH COLOR OVERLAPPING IN THE MIDDLE. ADD ADDITIONAL SECTOR COLOR BANDS FOR EACH ADDITIONAL MW RADIO.

MICROWAVE CABINETS WILL REQUIRE P-TOUCH LABELS INSIDE THE CABINET TO IDENTIFY THE LOCAL AND REMOTE SITE ID'S.



RF CABLE COLOR CODES

NO SCALE 1

LOW BANDS (N71-N28) OPTIONAL - (N29)



AWS (N65+N70+H-BLOCK)



CBRS TECH (3 GHz)



NEGATIVE SLANT PORT ON ANTRRH



ALPHA SECTOR



BETA SECTOR



GAMMA SECTOR



COLOR IDENTIFIER

NO SCALE 2

NOT USED

NO SCALE 3

NOT USED


NO SCALE 4



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



INFINIGY
FROM ZERO TO INFINIGY
the solutions are endless
2500 W. HIGGINS RD. SUITE 500 |
HOFFMAN ESTATES, IL 60169
PHONE: 847-648-4068 | FAX: 518-690-0793
WWW.INFINIGY.COM



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: RCD
CHECKED BY: SS
APPROVED BY: CJW

RFDS REV #: N/A

CONSTRUCTION DOCUMENTS


SUBMITTALS		
REV	DATE	DESCRIPTION
0	10/25/21	ISSUED FOR PERMIT
1	11/16/21	REVISED PER COMMENTS
2	12/08/21	REVISED PER COMMENTS

A&E PROJECT NUMBER
1197-F0001-C

DISH WIRELESS, LLC.
PROJECT INFORMATION
BOBDL00107A
UNIONVILLE CO
82 LOVELY ST
UNIONVILLE, CT 06085


SHEET TITLE
RF
CABLE COLOR CODES

SHEET NUMBER
RF-1



Fiber Patch Panel

Bottom Row	Pair 1	Pair 2	Pair 3	Pair 10	Open	Open
Middle Row	Pair 4	Pair 5	Pair 6	Pair 11	Open	Open
Top Row	Pair 7	Pair 8	Pair 9	Pair 12	Open	Open



CSR NCS540


Port	Interface	Description
0	G0/0/0	Stelios
1	G0/0/1	CBRS - Alpha
2	G0/0/2	CBRS - Beta
3	G0/0/3	CBRS - Gamma
4	Te0/0/4	Fujitsu Low-Band RU - Alpha
5	Te0/0/5	Fujitsu Mid-Band RU - Alpha
6	Te0/0/6	Fujitsu Low-Band RU - Beta
7	Te0/0/7	Fujitsu Mid-Band RU - Beta
8	Te0/0/8	Fujitsu Low-Band RU - Gamma
9	Te0/0/9	Fujitsu Mid-Band RU - Gamma
10	Te0/0/10	Fixed W/L
11	Te0/0/11	Fixed W/L
12	Te0/0/12	Fixed W/L
13	Te0/0/13	Fixed W/L
14	Te0/0/14	CBRS1
15	Te0/0/15	CBRS2
16	Te0/0/16	CBRS3
17	G0/0/17	SM1 - BMC
18	G0/0/18	SM2 - BMC
19	Te0/0/19	SM1 - Data 1
20	Te0/0/20	SM1 - Data 2
21	Te0/0/21	SM2 - Data 1
22	Te0/0/22	SM2 - Data 2
23	Te0/0/23	Reserved Uplink (EDC, LDC)
24	Te0/0/24	Blank/Future
25	Te0/0/25	Blank/Future
26	Te0/0/26	Fiber NIU
27	Te0/0/27	Fiber NIU
28	Te0/0/28	Blank/Future
29	Te0/0/29	Blank/Future

top

bottom

Bottom OVP Layout

Circuit 1	Alpha Low Band
Circuit 2	Beta Low Band
Circuit 3	Gamma Low Band
Circuit 4	Alpha Mid Band
Circuit 5	Beta Mid Band
Circuit 6	Gamma Mid Band
Circuit 7	Alpha CBRSS
Circuit 8	Beta CBRSS
Circuit 9	Gamma CBRSS
Circuit 10	Open
Circuit 11	Open
Circuit 12	Open



5G plumbing diagram JMA MX08FRO665-20
2-2-2(LB+MB)


Q	REV	NO	DATE	BY
1	1		5-Jan-2022	



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



INFINIGY
FROM ZERO TO INFINIGY
the solutions are endless
2500 W. HIGGINS RD., SUITE 500
HOFFMAN ESTATES, IL 60169
PHONE: 847-648-4068 | FAX: 518-690-0793
WWW.INFINIGY.COM



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:
RCD SS CJW

RFDS REV #: N/A

CONSTRUCTION DOCUMENTS

SUBMITTALS

REV	DATE	DESCRIPTION
0	10/25/21	ISSUED FOR PERMIT
1	11/16/21	REVISED PER COMMENTS
2	12/08/21	REVISED PER COMMENTS


A&E PROJECT NUMBER
1197-F0001-C

DISH WIRELESS, LLC.
PROJECT INFORMATION
BOBDL00107A
UNIONVILLE CO
82 LOVELY ST
UNIONVILLE, CT 06085


SHEET TITLE
RF
PLUMBING DIAGRAM

SHEET NUMBER
RF-2


EXOTHERMIC CONNECTION
 MECHANICAL CONNECTION
 CHEMICAL ELECTROLYTIC GROUNDING SYSTEM
 TEST CHEMICAL ELECTROLYTIC GROUNDING SYSTEM
 EXOTHERMIC WITH INSPECTION SLEEVE
 GROUNDING BAR
 GROUND ROD
 TEST GROUND ROD WITH INSPECTION SLEEVE
 SINGLE POLE SWITCH
 DUPLEX RECEPTACLE
 DUPLEX GFCI RECEPTACLE
 FLUORESCENT LIGHTING FIXTURE
 (2) TWO LAMPS 48-T8
 SMOKE DETECTION (DC)
 EMERGENCY LIGHTING (DC)
 SECURITY LIGHT W/PHOTOCELL LITHONIA ALXW
 LED-1-25A400/51K-SR4-120-PE-DEBTD



CHAIN LINK FENCE
 WOOD/WROUGHT IRON FENCE
 WALL STRUCTURE
 LEASE AREA
 PROPERTY LINE (PL)
 SETBACKS
 ICE BRIDGE
 CABLE TRAY
 WATER LINE
 UNDERGROUND POWER
 UNDERGROUND TELCO
 OVERHEAD POWER
 OVERHEAD TELCO
 UNDERGROUND TELCO/POWER
 ABOVE GROUND POWER
 ABOVE GROUND TELCO
 ABOVE GROUND TELCO/POWER
 WORKPOINT



SECTION REFERENCE
 DETAIL REFERENCE



AB	ANCHOR BOLT	IN	INCH	INT	INTERIOR
ABV	ABOVE	INT	INTERIOR	LB(S)	POUND(S)
AC	ALTERNATING CURRENT	LF	LINEAR FEET	LTE	LONG TERM EVOLUTION
ADDL	ADDITIONAL	MAS	MASONRY	MAX	MAXIMUM
AFF	ABOVE FINISHED FLOOR	MB	MACHINE BOLT	MECH	MECHANICAL
AFG	ABOVE FINISHED GRADE	MFR	MANUFACTURER	MGB	MASTER GROUND BAR
AGL	ABOVE GROUND LEVEL	MIN	MINIMUM	MISC	MISCELLANEOUS
AIC	AMPERAGE INTERRUPTION CAPACITY	MTL	METAL	MTS	MANUAL TRANSFER SWITCH
ALUM	ALUMINUM	MW	MICROWAVE	NEC	NATIONAL ELECTRIC CODE
ALT	ALTERNATE	NM	NEWTON METERS	NO.	NUMBER
ANT	ANTENNA	#	NUMBER	NTS	NOT TO SCALE
APPROX	APPROXIMATE	OC	ON-CENTER	OSHA	OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
ARCH	ARCHITECTURAL	OPNG	OPENING	P/C	PRECAST CONCRETE
ATS	AUTOMATIC TRANSFER SWITCH	PCS	PERSONAL COMMUNICATION SERVICES	PCU	PRIMARY CONTROL UNIT
AWG	AMERICAN WIRE GAUGE	PRC	PRIMARY RADIO CABINET	PP	POLARIZING PRESERVING
BATT	BATTERY	PSF	POUNDS PER SQUARE FOOT	PSI	POUNDS PER SQUARE INCH
BLDG	BUILDING	PT	PRESSURE TREATED	PWR	POWER CABINET
BLK	BLOCK	QTY	QUANTITY	RAD	RADIUS
BLKG	BLOCKING	RECT	RECTIFIER	REF	REFERENCE
BM	BEAM	REINF	REINFORCEMENT	REQ'D	REQUIRED
BTC	BARE TINNED COPPER CONDUCTOR	RET	REMOTE ELECTRIC TILT	RF	RADIO FREQUENCY
BOF	BOTTOM OF FOOTING	RMC	RIGID METALLIC CONDUIT	RRH	REMOTE RADIO HEAD
CAB	CABINET	RRU	REMOTE RADIO UNIT	RWY	RACEWAY
CANT	CANTILEVERED	SCH	SCHEDULE	SHT	SHEET
CHG	CHARGING	SIAD	SMART INTEGRATED ACCESS DEVICE	SIM	SIMILAR
CLG	CEILING	SPEC	SPECIFICATION	SQ	SQUARE
CLR	CLEAR	SS	STAINLESS STEEL	STD	STANDARD
COL	COLUMN	STL	STEEL	TEMP	TEMPORARY
COMM	COMMON	THK	THICKNESS	TMA	TOWER MOUNTED AMPLIFIER
CONC	CONCRETE	TOA	TOP OF ANTENNA	TN	TOE NAIL
CONSTR	CONSTRUCTION	TOC	TOP OF CURB	TOF	TOP OF FOUNDATION
DBL	DOUBLE	TOP	TOP OF PLATE (PARAPET)	TOS	TOP OF STEEL
DC	DIRECT CURRENT	TOW	TOP OF WALL	TVSS	TRANSIENT VOLTAGE SURGE SUPPRESSION
DEPT	DEPARTMENT	TYP	TYPICAL	UG	UNDERGROUND
DF	DOUGLAS FIR	UL	UNDERWRITERS LABORATORY	UNO	UNLESS NOTED OTHERWISE
DIA	DIAMETER	UMTS	UNIVERSAL MOBILE TELECOMMUNICATIONS SYSTEM	UPS	UNINTERRUPTIBLE POWER SYSTEM (DC POWER PLANT)
DIAG	DIAGONAL	VIF	VERIFIED IN FIELD	W	WIDE
DIM	DIMENSION	W/	WITH	WD	WOOD
DWG	DRAWING	WP	WEATHERPROOF	WT	WEIGHT
DWL	DOWEL				
EA	EACH				
EC	ELECTRICAL CONDUCTOR				
EL	ELEVATION				
ELEC	ELECTRICAL				
EMT	ELECTRICAL METALLIC TUBING				
ENG	ENGINEER				
EQ	EQUAL				
EXP	EXPANSION				
EXT	EXTERIOR				
EW	EACH WAY				
FAB	FABRICATION				
FF	FINISH FLOOR				
FG	FINISH GRADE				
FIF	FACILITY INTERFACE FRAME				
FIN	FINISH(ED)				
FLR	FLOOR				
FDN	FOUNDATION				
FOC	FACE OF CONCRETE				
FOM	FACE OF MASONRY				
FOS	FACE OF STUD				
FOW	FACE OF WALL				
FS	FINISH SURFACE				
FT	FOOT				
FTG	FOOTING				
GA	GAUGE				
GEN	GENERATOR				
GFCI	GROUND FAULT CIRCUIT INTERRUPTER				
GLB	GLUE LAMINATED BEAM				
GLV	GALVANIZED				
GPS	GLOBAL POSITIONING SYSTEM				
GND	GROUND				
GSM	GLOBAL SYSTEM FOR MOBILE				
HDG	HOT DIPPED GALVANIZED				
HDR	HEADER				
HGR	HANGER				
HVAC	HEAT/VENTILATION/AIR CONDITIONING				
HT	HEIGHT				
IGR	INTERIOR GROUND RING				

LEGEND


ABBREVIATIONS



5701 SOUTH SANTA FE DRIVE
 LITTLETON, CO 80120



INFINIGY
 FROM ZERO TO INFINIGY
 the solutions are endless
 2500 W. HIGGINS RD. SUITE 500 |
 HOFFMAN ESTATES, IL 60169
 PHONE: 847-648-4068 | FAX: 518-690-0793
 WWW.INFINIGY.COM



IT IS A VIOLATION OF LAW FOR ANY PERSON,
 UNLESS THEY ARE ACTING UNDER THE DIRECTION
 OF A LICENSED PROFESSIONAL ENGINEER,
 TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
RCD	SS	CJW
RFDS REV #: N/A		

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
0	10/25/21	ISSUED FOR PERMIT
1	11/16/21	REVISED PER COMMENTS
2	12/08/21	REVISED PER COMMENTS

A&E PROJECT NUMBER
 1197-F0001-C

DISH WIRELESS, LLC.
 PROJECT INFORMATION
 BOBDL00107A
 UNIONVILLE CO
 82 LOVELY ST
 UNIONVILLE, CT 06085

SHEET TITLE
 LEGEND AND ABBREVIATIONS

SHEET NUMBER
GN-1

SITE ACTIVITY REQUIREMENTS:

1. NOTICE TO PROCEED – NO WORK SHALL COMMENCE PRIOR TO CONTRACTOR RECEIVING A WRITTEN NOTICE TO PROCEED (NTP) AND THE ISSUANCE OF A PURCHASE ORDER. PRIOR TO ACCESSING/ENTERING THE SITE YOU MUST CONTACT THE DISH WIRELESS, LLC. AND TOWER OWNER NOC & THE DISH WIRELESS, LLC. AND TOWER OWNER CONSTRUCTION MANAGER.
2. "LOOK UP" – DISH WIRELESS, LLC. AND TOWER OWNER SAFETY CLIMB REQUIREMENT:
THE INTEGRITY OF THE SAFETY CLIMB AND ALL COMPONENTS OF THE CLIMBING FACILITY SHALL BE CONSIDERED DURING ALL STAGES OF DESIGN, INSTALLATION, AND INSPECTION. TOWER MODIFICATION, MOUNT REINFORCEMENTS, AND/OR EQUIPMENT INSTALLATIONS SHALL NOT COMPROMISE THE INTEGRITY OR FUNCTIONAL USE OF THE SAFETY CLIMB OR ANY COMPONENTS OF THE CLIMBING FACILITY ON THE STRUCTURE. THIS SHALL INCLUDE, BUT NOT BE LIMITED TO: PINCHING OF THE WIRE ROPE, BENDING OF THE WIRE ROPE FROM ITS SUPPORTS, DIRECT CONTACT OR CLOSE PROXIMITY TO THE WIRE ROPE WHICH MAY CAUSE FRICTIONAL WEAR, IMPACT TO THE ANCHORAGE POINTS IN ANY WAY, OR TO IMPEDE/BLOCK ITS INTENDED USE. ANY COMPROMISED SAFETY CLIMB, INCLUDING EXISTING CONDITIONS MUST BE TAGGED OUT AND REPORTED TO YOUR DISH WIRELESS, LLC. AND DISH WIRELESS, LLC. AND TOWER OWNER POC OR CALL THE NOC TO GENERATE A SAFETY CLIMB MAINTENANCE AND CONTRACTOR NOTICE TICKET.
3. PRIOR TO THE START OF CONSTRUCTION, ALL REQUIRED JURISDICTIONAL PERMITS SHALL BE OBTAINED. THIS INCLUDES, BUT IS NOT LIMITED TO, BUILDING, ELECTRICAL, MECHANICAL, FIRE, FLOOD ZONE, ENVIRONMENTAL, AND ZONING. AFTER ONSITE ACTIVITIES AND CONSTRUCTION ARE COMPLETED, ALL REQUIRED PERMITS SHALL BE SATISFIED AND CLOSED OUT ACCORDING TO LOCAL JURISDICTIONAL REQUIREMENTS.
4. ALL CONSTRUCTION MEANS AND METHODS; INCLUDING BUT NOT LIMITED TO, ERECTION PLANS, RIGGING PLANS, CLIMBING PLANS, AND RESCUE PLANS SHALL BE THE RESPONSIBILITY OF THE GENERAL CONTRACTOR RESPONSIBLE FOR THE EXECUTION OF THE WORK CONTAINED HEREIN, AND SHALL MEET ANSI/ASSE A10.48 (LATEST EDITION); FEDERAL, STATE, AND LOCAL REGULATIONS; AND ANY APPLICABLE INDUSTRY CONSENSUS STANDARDS RELATED TO THE CONSTRUCTION ACTIVITIES BEING PERFORMED. ALL RIGGING PLANS SHALL ADHERE TO ANSI/ASSE A10.48 (LATEST EDITION) AND DISH WIRELESS, LLC. AND TOWER OWNER STANDARDS, INCLUDING THE REQUIRED INVOLVEMENT OF A QUALIFIED ENGINEER FOR CLASS IV CONSTRUCTION, TO CERTIFY THE SUPPORTING STRUCTURE(S) IN ACCORDANCE WITH ANSI/TIA-322 (LATEST EDITION).
5. ALL SITE WORK TO COMPLY WITH DISH WIRELESS, LLC. AND TOWER OWNER INSTALLATION STANDARDS FOR CONSTRUCTION ACTIVITIES ON DISH WIRELESS, LLC. AND TOWER OWNER TOWER SITE AND LATEST VERSION OF ANSI/TIA-1019-A-2012 "STANDARD FOR INSTALLATION, ALTERATION, AND MAINTENANCE OF ANTENNA SUPPORTING STRUCTURES AND ANTENNAS."
6. IF THE SPECIFIED EQUIPMENT CAN NOT BE INSTALLED AS SHOWN ON THESE DRAWINGS, THE CONTRACTOR SHALL PROPOSE AN ALTERNATIVE INSTALLATION FOR APPROVAL BY DISH WIRELESS, LLC. AND TOWER OWNER PRIOR TO PROCEEDING WITH ANY SUCH CHANGE OF INSTALLATION.
7. ALL MATERIALS FURNISHED AND INSTALLED SHALL BE IN STRICT ACCORDANCE WITH ALL APPLICABLE CODES, REGULATIONS AND ORDINANCES. CONTRACTOR SHALL ISSUE ALL APPROPRIATE NOTICES AND COMPLY WITH ALL LAWS, ORDINANCES, RULES, REGULATIONS AND LAWFUL ORDERS OF ANY PUBLIC AUTHORITY REGARDING THE PERFORMANCE OF THE WORK. ALL WORK CARRIED OUT SHALL COMPLY WITH ALL APPLICABLE MUNICIPAL AND UTILITY COMPANY SPECIFICATIONS AND LOCAL JURISDICTIONAL CODES, ORDINANCES AND APPLICABLE REGULATIONS.
8. THE CONTRACTOR SHALL INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS UNLESS SPECIFICALLY STATED OTHERWISE.
9. THE CONTRACTOR SHALL CONTACT UTILITY LOCATING SERVICES INCLUDING PRIVATE LOCATES SERVICES PRIOR TO THE START OF CONSTRUCTION.
10. ALL EXISTING ACTIVE SEWER, WATER, GAS, ELECTRIC AND OTHER UTILITIES WHERE ENCOUNTERED IN THE WORK, SHALL BE PROTECTED AT ALL TIMES AND WHERE REQUIRED FOR THE PROPER EXECUTION OF THE WORK, SHALL BE RELOCATED AS DIRECTED BY CONTRACTOR. EXTREME CAUTION SHOULD BE USED BY THE CONTRACTOR WHEN EXCAVATING OR DRILLING PIERS AROUND OR NEAR UTILITIES. CONTRACTOR SHALL PROVIDE SAFETY TRAINING FOR THE WORKING CREW. THIS WILL INCLUDE BUT NOT BE LIMITED TO A) FALL PROTECTION B) CONFINED SPACE C) ELECTRICAL SAFETY D) TRENCHING AND EXCAVATION E) CONSTRUCTION SAFETY PROCEDURES.
11. ALL SITE WORK SHALL BE AS INDICATED ON THE STAMPED CONSTRUCTION DRAWINGS AND DISH PROJECT SPECIFICATIONS, LATEST APPROVED REVISION.
12. CONTRACTOR SHALL KEEP THE SITE FREE FROM ACCUMULATING WASTE MATERIAL, DEBRIS, AND TRASH AT THE COMPLETION OF THE WORK. IF NECESSARY, RUBBISH, STUMPS, DEBRIS, STICKS, STONES AND OTHER REFUSE SHALL BE REMOVED FROM THE SITE AND DISPOSED OF LEGALLY.
13. ALL EXISTING INACTIVE SEWER, WATER, GAS, ELECTRIC AND OTHER UTILITIES, WHICH INTERFERE WITH THE EXECUTION OF THE WORK, SHALL BE REMOVED AND/OR CAPPED, PLUGGED OR OTHERWISE DISCONTINUED AT POINTS WHICH WILL NOT INTERFERE WITH THE EXECUTION OF THE WORK, SUBJECT TO THE APPROVAL OF DISH WIRELESS, LLC. AND TOWER OWNER, AND/OR LOCAL UTILITIES.
14. THE CONTRACTOR SHALL PROVIDE SITE SIGNAGE IN ACCORDANCE WITH THE TECHNICAL SPECIFICATION FOR SITE SIGNAGE REQUIRED BY LOCAL JURISDICTION AND SIGNAGE REQUIRED ON INDIVIDUAL PIECES OF EQUIPMENT, ROOMS, AND SHELTERS.
15. THE SITE SHALL BE GRADED TO CAUSE SURFACE WATER TO FLOW AWAY FROM THE CARRIER'S EQUIPMENT AND TOWER AREAS.
16. THE SUB GRADE SHALL BE COMPACTED AND BROUGHT TO A SMOOTH UNIFORM GRADE PRIOR TO FINISHED SURFACE APPLICATION.
17. THE AREAS OF THE OWNERS PROPERTY DISTURBED BY THE WORK AND NOT COVERED BY THE TOWER, EQUIPMENT OR DRIVEWAY, SHALL BE GRADED TO A UNIFORM SLOPE, AND STABILIZED TO PREVENT EROSION AS SPECIFIED ON THE CONSTRUCTION DRAWINGS AND/OR PROJECT SPECIFICATIONS.
18. CONTRACTOR SHALL MINIMIZE DISTURBANCE TO EXISTING SITE DURING CONSTRUCTION. EROSION CONTROL MEASURES, IF REQUIRED DURING CONSTRUCTION, SHALL BE IN CONFORMANCE WITH THE LOCAL GUIDELINES FOR EROSION AND SEDIMENT CONTROL.
19. THE CONTRACTOR SHALL PROTECT EXISTING IMPROVEMENTS, PAVEMENTS, CURBS, LANDSCAPING AND STRUCTURES. ANY DAMAGED PART SHALL BE REPAIRED AT CONTRACTOR'S EXPENSE TO THE SATISFACTION OF OWNER.
20. CONTRACTOR SHALL LEGALLY AND PROPERLY DISPOSE OF ALL SCRAP MATERIALS SUCH AS COAXIAL CABLES AND OTHER ITEMS REMOVED FROM THE EXISTING FACILITY. ANTENNAS AND RADIOS REMOVED SHALL BE RETURNED TO THE OWNER'S DESIGNATED LOCATION.
21. CONTRACTOR SHALL LEAVE PREMISES IN CLEAN CONDITION. TRASH AND DEBRIS SHOULD BE REMOVED FROM SITE ON A DAILY BASIS.
22. NO FILL OR EMBANKMENT MATERIAL SHALL BE PLACED ON FROZEN GROUND. FROZEN MATERIALS, SNOW OR ICE SHALL NOT BE PLACED IN ANY FILL OR EMBANKMENT.

GENERAL NOTES:


- 1.FOR THE PURPOSE OF CONSTRUCTION DRAWING, THE FOLLOWING DEFINITIONS SHALL APPLY:
CONTRACTOR:GENERAL CONTRACTOR RESPONSIBLE FOR CONSTRUCTION
CARRIER:DISH WIRELESS, LLC.
TOWER OWNER:TOWER OWNER
2. THESE DRAWINGS HAVE BEEN PREPARED USING STANDARDS OF PROFESSIONAL CARE AND COMPLETENESS NORMALLY EXERCISED UNDER SIMILAR CIRCUMSTANCES BY REPUTABLE ENGINEERS IN THIS OR SIMILAR LOCALITIES. IT IS ASSUMED THAT THE WORK DEPICTED WILL BE PERFORMED BY AN EXPERIENCED CONTRACTOR AND/OR WORKPEOPLE WHO HAVE A WORKING KNOWLEDGE OF THE APPLICABLE CODE STANDARDS AND REQUIREMENTS AND OF INDUSTRY ACCEPTED STANDARD GOOD PRACTICE. AS NOT EVERY CONDITION OR ELEMENT IS (OR CAN BE) EXPLICITLY SHOWN ON THESE DRAWINGS, THE CONTRACTOR SHALL USE INDUSTRY ACCEPTED STANDARD GOOD PRACTICE FOR MISCELLANEOUS WORK NOT EXPLICITLY SHOWN.
3. THESE DRAWINGS REPRESENT THE FINISHED STRUCTURE. THEY DO NOT INDICATE THE MEANS OR METHODS OF CONSTRUCTION. THE CONTRACTOR SHALL BE SOLELY RESPONSIBLE FOR THE CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES, AND PROCEDURES. THE CONTRACTOR SHALL PROVIDE ALL MEASURES NECESSARY FOR PROTECTION OF LIFE AND PROPERTY DURING CONSTRUCTION. SUCH MEASURES SHALL INCLUDE, BUT NOT BE LIMITED TO, BRACING, FORMWORK, SHORING, ETC. SITE VISITS BY THE ENGINEER OR HIS REPRESENTATIVE WILL NOT INCLUDE INSPECTION OF THESE ITEMS AND IS FOR STRUCTURAL OBSERVATION OF THE FINISHED STRUCTURE ONLY.
4. NOTES AND DETAILS IN THE CONSTRUCTION DRAWINGS SHALL TAKE PRECEDENCE OVER GENERAL NOTES AND TYPICAL DETAILS. WHERE NO DETAILS ARE SHOWN, CONSTRUCTION SHALL CONFORM TO SIMILAR WORK ON THE PROJECT, AND/OR AS PROVIDED FOR IN THE CONTRACT DOCUMENTS. WHERE DISCREPANCIES OCCUR BETWEEN PLANS, DETAILS, GENERAL NOTES, AND SPECIFICATIONS, THE GREATER, MORE STRICT REQUIREMENTS, SHALL GOVERN. IF FURTHER CLARIFICATION IS REQUIRED CONTACT THE ENGINEER OF RECORD.
5. SUBSTANTIAL EFFORT HAS BEEN MADE TO PROVIDE ACCURATE DIMENSIONS AND MEASUREMENTS ON THE DRAWINGS TO ASSIST IN THE FABRICATION AND/OR PLACEMENT OF CONSTRUCTION ELEMENTS BUT IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO FIELD VERIFY THE DIMENSIONS, MEASUREMENTS, AND/OR CLEARANCES SHOWN IN THE CONSTRUCTION DRAWINGS PRIOR TO FABRICATION OR CUTTING OF ANY NEW OR EXISTING CONSTRUCTION ELEMENTS. IF IT IS DETERMINED THAT THERE ARE DISCREPANCIES AND/OR CONFLICTS WITH THE CONSTRUCTION DRAWINGS THE ENGINEER OF RECORD IS TO BE NOTIFIED AS SOON AS POSSIBLE.
6. PRIOR TO THE SUBMISSION OF BIDS, THE BIDDING CONTRACTOR SHALL VISIT THE CELL SITE TO FAMILIARIZE WITH THE EXISTING CONDITIONS AND TO CONFIRM THAT THE WORK CAN BE ACCOMPLISHED AS SHOWN ON THE CONSTRUCTION DRAWINGS. ANY DISCREPANCY FOUND SHALL BE BROUGHT TO THE ATTENTION OF CARRIER POC AND TOWER OWNER.
7. ALL MATERIALS FURNISHED AND INSTALLED SHALL BE IN STRICT ACCORDANCE WITH ALL APPLICABLE CODES, REGULATIONS AND ORDINANCES. CONTRACTOR SHALL ISSUE ALL APPROPRIATE NOTICES AND COMPLY WITH ALL LAWS, ORDINANCES, RULES, REGULATIONS AND LAWFUL ORDERS OF ANY PUBLIC AUTHORITY REGARDING THE PERFORMANCE OF THE WORK. ALL WORK CARRIED OUT SHALL COMPLY WITH ALL APPLICABLE MUNICIPAL AND UTILITY COMPANY SPECIFICATIONS AND LOCAL JURISDICTIONAL CODES, ORDINANCES AND APPLICABLE REGULATIONS.
8. UNLESS NOTED OTHERWISE, THE WORK SHALL INCLUDE FURNISHING MATERIALS, EQUIPMENT, APPURTENANCES AND LABOR NECESSARY TO COMPLETE ALL INSTALLATIONS AS INDICATED ON THE DRAWINGS.
9. THE CONTRACTOR SHALL INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS UNLESS SPECIFICALLY STATED OTHERWISE.
10. IF THE SPECIFIED EQUIPMENT CAN NOT BE INSTALLED AS SHOWN ON THESE DRAWINGS, THE CONTRACTOR SHALL PROPOSE AN ALTERNATIVE INSTALLATION FOR APPROVAL BY THE CARRIER AND TOWER OWNER PRIOR TO PROCEEDING WITH ANY SUCH CHANGE OF INSTALLATION.
11. CONTRACTOR IS TO PERFORM A SITE INVESTIGATION, BEFORE SUBMITTING BIDS, TO DETERMINE THE BEST ROUTING OF ALL CONDUITS FOR POWER, AND TELCO AND FOR GROUNDING CABLES AS SHOWN IN THE POWER, TELCO, AND GROUNDING PLAN DRAWINGS.
12. THE CONTRACTOR SHALL PROTECT EXISTING IMPROVEMENTS, PAVEMENTS, CURBS, LANDSCAPING AND STRUCTURES. ANY DAMAGED PART SHALL BE REPAIRED AT CONTRACTOR'S EXPENSE TO THE SATISFACTION OF DISH WIRELESS, LLC. AND TOWER OWNER
13. CONTRACTOR SHALL LEGALLY AND PROPERLY DISPOSE OF ALL SCRAP MATERIALS SUCH AS COAXIAL CABLES AND OTHER ITEMS REMOVED FROM THE EXISTING FACILITY. ANTENNAS REMOVED SHALL BE RETURNED TO THE OWNER'S DESIGNATED LOCATION.
14. CONTRACTOR SHALL LEAVE PREMISES IN CLEAN CONDITION. TRASH AND DEBRIS SHOULD BE REMOVED FROM SITE ON A DAILY BASIS.



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



INFINIGY
FROM ZERO TO INFINIGY
the solutions are endless
2500 W. HIGGINS RD., SUITE 500 |
HOFFMAN ESTATES, IL 60169
PHONE: 847-648-4068 | FAX: 518-690-0793
WWW.INFINIGY.COM



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
RCD	SS	CJW
RFDS REV #: N/A		

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
0	10/25/21	ISSUED FOR PERMIT
1	11/16/21	REVISED PER COMMENTS
2	12/08/21	REVISED PER COMMENTS

A&E PROJECT NUMBER
1197-F0001-C

DISH WIRELESS, LLC.
PROJECT INFORMATION
BOBDL00107A
UNIONVILLE CO
82 LOVELY ST
UNIONVILLE, CT 06085

SHEET TITLE
GENERAL NOTES

SHEET NUMBER
GN-2

CONCRETE, FOUNDATIONS, AND REINFORCING STEEL:

1. ALL CONCRETE WORK SHALL BE IN ACCORDANCE WITH THE ACI 301, ACI 318, ACI 336, ASTM A184, ASTM A185 AND THE DESIGN AND CONSTRUCTION SPECIFICATION FOR CAST-IN-PLACE CONCRETE.
2. UNLESS NOTED OTHERWISE, SOIL BEARING PRESSURE USED FOR DESIGN OF SLABS AND FOUNDATIONS IS ASSUMED TO BE 1000 psf.
3. ALL CONCRETE SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH (f'c) OF 3000 psi AT 28 DAYS, UNLESS NOTED OTHERWISE. NO MORE THAN 90 MINUTES SHALL ELAPSE FROM BATCH TIME TO TIME OF PLACEMENT UNLESS APPROVED BY THE ENGINEER OF RECORD. TEMPERATURE OF CONCRETE SHALL NOT EXCEED 90°f AT TIME OF PLACEMENT.
4. CONCRETE EXPOSED TO FREEZE-THAW CYCLES SHALL CONTAIN AIR ENTRAINING ADMIXTURES. AMOUNT OF AIR ENTRAINMENT TO BE BASED ON SIZE OF AGGREGATE AND F3 CLASS EXPOSURE (VERY SEVERE). CEMENT USED TO BE TYPE II PORTLAND CEMENT WITH A MAXIMUM WATER-TO-CEMENT RATIO (W/C) OF 0.45.
5. ALL STEEL REINFORCING SHALL CONFORM TO ASTM A615. ALL WELDED WIRE FABRIC (WWF) SHALL CONFORM TO ASTM A185. ALL SPLICES SHALL BE CLASS "B" TENSION SPLICES, UNLESS NOTED OTHERWISE. ALL HOOKS SHALL BE STANDARD 90 DEGREE HOOKS, UNLESS NOTED OTHERWISE. YIELD STRENGTH (Fy) OF STANDARD DEFORMED BARS ARE AS FOLLOWS:
 - #4 BARS AND SMALLER 40 ksi
 - #5 BARS AND LARGER 60 ksi
6. THE FOLLOWING MINIMUM CONCRETE COVER SHALL BE PROVIDED FOR REINFORCING STEEL UNLESS SHOWN OTHERWISE ON DRAWINGS:
 - CONCRETE CAST AGAINST AND PERMANENTLY EXPOSED TO EARTH 3"
 - CONCRETE EXPOSED TO EARTH OR WEATHER:
 - #6 BARS AND LARGER 2"
 - #5 BARS AND SMALLER 1-1/2"
 - CONCRETE NOT EXPOSED TO EARTH OR WEATHER:
 - SLAB AND WALLS 3/4"
 - BEAMS AND COLUMNS 1-1/2"
7. A TOOLED EDGE OR A 3/4" CHAMFER SHALL BE PROVIDED AT ALL EXPOSED EDGES OF CONCRETE, UNLESS NOTED OTHERWISE, IN ACCORDANCE WITH ACI 301 SECTION 4.2.4.

ELECTRICAL INSTALLATION NOTES:

1. ALL ELECTRICAL WORK SHALL BE PERFORMED IN ACCORDANCE WITH THE PROJECT SPECIFICATIONS, NEC AND ALL APPLICABLE FEDERAL, STATE, AND LOCAL CODES/ORDINANCES.
2. CONDUIT ROUTINGS ARE SCHEMATIC. CONTRACTOR SHALL INSTALL CONDUITS SO THAT ACCESS TO EQUIPMENT IS NOT BLOCKED AND TRIP HAZARDS ARE ELIMINATED.
3. WIRING, RACEWAY AND SUPPORT METHODS AND MATERIALS SHALL COMPLY WITH THE REQUIREMENTS OF THE NEC.
4. ALL CIRCUITS SHALL BE SEGREGATED AND MAINTAIN MINIMUM CABLE SEPARATION AS REQUIRED BY THE NEC.
- 4.1. ALL EQUIPMENT SHALL BEAR THE UNDERWRITERS LABORATORIES LABEL OF APPROVAL, AND SHALL CONFORM TO REQUIREMENT OF THE NATIONAL ELECTRICAL CODE.
- 4.2. ALL OVERCURRENT DEVICES SHALL HAVE AN INTERRUPTING CURRENT RATING THAT SHALL BE GREATER THAN THE SHORT CIRCUIT CURRENT TO WHICH THEY ARE SUBJECTED, 22,000 AIC MINIMUM. VERIFY AVAILABLE SHORT CIRCUIT CURRENT DOES NOT EXCEED THE RATING OF ELECTRICAL EQUIPMENT IN ACCORDANCE WITH ARTICLE 110.24 NEC OR THE MOST CURRENT ADOPTED CODE PRE THE GOVERNING JURISDICTION.
5. EACH END OF EVERY POWER PHASE CONDUCTOR, GROUNDING CONDUCTOR, AND TELCO CONDUCTOR OR CABLE SHALL BE LABELED WITH COLOR-CODED INSULATION OR ELECTRICAL TAPE (3M BRAND, 1/2" PLASTIC ELECTRICAL TAPE WITH UV PROTECTION, OR EQUAL). THE IDENTIFICATION METHOD SHALL CONFORM WITH NEC AND OSHA.
6. ALL ELECTRICAL COMPONENTS SHALL BE CLEARLY LABELED WITH LAMICOID TAGS SHOWING THEIR RATED VOLTAGE, PHASE CONFIGURATION, WIRE CONFIGURATION, POWER OR AMPACITY RATING AND BRANCH CIRCUIT ID NUMBERS (i.e. PANEL BOARD AND CIRCUIT ID'S).
7. PANEL BOARDS (ID NUMBERS) SHALL BE CLEARLY LABELED WITH PLASTIC LABELS.
8. TIE WRAPS ARE NOT ALLOWED.
9. ALL POWER AND EQUIPMENT GROUND WIRING IN TUBING OR CONDUIT SHALL BE SINGLE COPPER CONDUCTOR (#14 OR LARGER) WITH TYPE THHW, THWN, THWN-2, XHHW, XHHW-2, THW, THW-2, RHW, OR RHW-2 INSULATION UNLESS OTHERWISE SPECIFIED.
10. SUPPLEMENTAL EQUIPMENT GROUND WIRING LOCATED INDOORS SHALL BE SINGLE COPPER CONDUCTOR (#6 OR LARGER) WITH TYPE THHW, THWN, THWN-2, XHHW, XHHW-2, THW, THW-2, RHW, OR RHW-2 INSULATION UNLESS OTHERWISE SPECIFIED.
11. POWER AND CONTROL WIRING IN FLEXIBLE CORD SHALL BE MULTI-CONDUCTOR, TYPE SOOW CORD (#14 OR LARGER) UNLESS OTHERWISE SPECIFIED.
12. POWER AND CONTROL WIRING FOR USE IN CABLE TRAY SHALL BE MULTI-CONDUCTOR, TYPE TC CABLE (#14 OR LARGER), WITH TYPE THHW, THWN, THWN-2, XHHW, XHHW-2, THW, THW-2, RHW, OR RHW-2 INSULATION UNLESS OTHERWISE SPECIFIED.
13. ALL POWER AND GROUNDING CONNECTIONS SHALL BE CRIMP-STYLE, COMPRESSION WIRE LUGS AND WIRE NUTS BY THOMAS AND BETTS (OR EQUAL). LUGS AND WIRE NUTS SHALL BE RATED FOR OPERATION NOT LESS THAN 75° C (90° C IF AVAILABLE).
14. RACEWAY AND CABLE TRAY SHALL BE LISTED OR LABELED FOR ELECTRICAL USE IN ACCORDANCE WITH NEMA, UL, ANSI/IEEE AND NEC.
15. ELECTRICAL METALLIC TUBING (EMT), INTERMEDIATE METAL CONDUIT (IMC), OR RIGID METAL CONDUIT (RMC) SHALL BE USED FOR EXPOSED INDOOR LOCATIONS.


16. ELECTRICAL METALLIC TUBING (EMT) OR METAL-CLAD CABLE (MC) SHALL BE USED FOR CONCEALED INDOOR LOCATIONS.
17. SCHEDULE 40 PVC UNDERGROUND ON STRAIGHTS AND SCHEDULE 80 PVC FOR ALL ELBOWS/90s AND ALL APPROVED ABOVE GRADE PVC CONDUIT.
18. LIQUID-TIGHT FLEXIBLE METALLIC CONDUIT (LIQUID-TITE FLEX) SHALL BE USED INDOORS AND OUTDOORS, WHERE VIBRATION OCCURS OR FLEXIBILITY IS NEEDED.
19. CONDUIT AND TUBING FITTINGS SHALL BE THREADED OR COMPRESSION-TYPE AND APPROVED FOR THE LOCATION USED. SET SCREW FITTINGS ARE NOT ACCEPTABLE.
20. CABINETS, BOXES AND WIRE WAYS SHALL BE LABELED FOR ELECTRICAL USE IN ACCORDANCE WITH NEMA, UL, ANSI/IEEE AND THE NEC.
21. WIREWAYS SHALL BE METAL WITH AN ENAMEL FINISH AND INCLUDE A HINGED COVER, DESIGNED TO SWING OPEN DOWNWARDS (WIREMOLD SPECMATE WIREWAY).
22. SLOTTED WIRING DUCT SHALL BE PVC AND INCLUDE COVER (PANDUIT TYPE E OR EQUAL).
23. CONDUITS SHALL BE FASTENED SECURELY IN PLACE WITH APPROVED NON-PERFORATED STRAPS AND HANGERS. EXPLOSIVE DEVICES (i.e. POWDER-ACTUATED) FOR ATTACHING HANGERS TO STRUCTURE WILL NOT BE PERMITTED. CLOSELY FOLLOW THE LINES OF THE STRUCTURE, MAINTAIN CLOSE PROXIMITY TO THE STRUCTURE AND KEEP CONDUITS IN TIGHT ENVELOPES. CHANGES IN DIRECTION TO ROUTE AROUND OBSTACLES SHALL BE MADE WITH CONDUIT OUTLET BODIES. CONDUIT SHALL BE INSTALLED IN A NEAT AND WORKMANLIKE MANNER. PARALLEL AND PERPENDICULAR TO STRUCTURE WALL AND CEILING LINES. ALL CONDUIT SHALL BE FISHED TO CLEAR OBSTRUCTIONS. ENDS OF CONDUITS SHALL BE TEMPORARILY CAPPED FLUSH TO FINISH GRADE TO PREVENT CONCRETE, PLASTER OR DIRT FROM ENTERING. CONDUITS SHALL BE RIGIDLY CLAMPED TO BOXES BY GALVANIZED MALLEABLE IRON BUSHING ON INSIDE AND GALVANIZED MALLEABLE IRON LOCKNUT ON OUTSIDE AND INSIDE.
24. EQUIPMENT CABINETS, TERMINAL BOXES, JUNCTION BOXES AND PULL BOXES SHALL BE GALVANIZED OR EPOXY-COATED SHEET STEEL. SHALL MEET OR EXCEED UL 50 AND BE RATED NEMA 1 (OR BETTER) FOR INTERIOR LOCATIONS AND NEMA 3 (OR BETTER) FOR EXTERIOR LOCATIONS.
25. METAL RECEPTACLE, SWITCH AND DEVICE BOXES SHALL BE GALVANIZED, EPOXY-COATED OR NON-CORRODING; SHALL MEET OR EXCEED UL 514A AND NEMA OS 1 AND BE RATED NEMA 1 (OR BETTER) FOR INTERIOR LOCATIONS AND WEATHER PROTECTED (WP OR BETTER) FOR EXTERIOR LOCATIONS.
26. NONMETALLIC RECEPTACLE, SWITCH AND DEVICE BOXES SHALL MEET OR EXCEED NEMA OS 2 (NEWEST REVISION) AND BE RATED NEMA 1 (OR BETTER) FOR INTERIOR LOCATIONS AND WEATHER PROTECTED (WP OR BETTER) FOR EXTERIOR LOCATIONS.
27. THE CONTRACTOR SHALL NOTIFY AND OBTAIN NECESSARY AUTHORIZATION FROM THE CARRIER AND/OR DISH WIRELESS, LLC. AND TOWER OWNER BEFORE COMMENCING WORK ON THE AC POWER DISTRIBUTION PANELS.
28. THE CONTRACTOR SHALL PROVIDE NECESSARY TAGGING ON THE BREAKERS, CABLES AND DISTRIBUTION PANELS IN ACCORDANCE WITH THE APPLICABLE CODES AND STANDARDS TO SAFEGUARD LIFE AND PROPERTY.
29. INSTALL LAMICOID LABEL ON THE METER CENTER TO SHOW "DISH WIRELESS, LLC."
30. ALL EMPTY/SPARE CONDUITS THAT ARE INSTALLED ARE TO HAVE A METERED MULE TAPE PULL CORD INSTALLED.



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



INFINIGY
FROM ZERO TO INFINIGY
the solutions are endless
2500 W. HIGGINS RD., SUITE 500 |
HOFFMAN ESTATES, IL 60169
PHONE: 847-648-4068 | FAX: 518-690-0793
WWW.INFINIGY.COM



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
RCD	SS	CJW
RFDS REV #: N/A		

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
0	10/25/21	ISSUED FOR PERMIT
1	11/16/21	REVISED PER COMMENTS
2	12/08/21	REVISED PER COMMENTS

A&E PROJECT NUMBER
1197-F0001-C

DISH WIRELESS, LLC.
PROJECT INFORMATION
BOBDL00107A
UNIONVILLE CO
82 LOVELY ST
UNIONVILLE, CT 06085

SHEET TITLE
GENERAL NOTES

SHEET NUMBER
GN-3

GROUNDING NOTES:


1. ALL GROUND ELECTRODE SYSTEMS (INCLUDING TELECOMMUNICATION, RADIO, LIGHTNING PROTECTION AND AC POWER GES'S) SHALL BE BONDED TOGETHER AT OR BELOW GRADE, BY TWO OR MORE COPPER BONDING CONDUCTORS IN ACCORDANCE WITH THE NEC.
2. THE CONTRACTOR SHALL PERFORM IEEE FALL-OF-POTENTIAL RESISTANCE TO EARTH TESTING (PER IEEE 1100 AND 81) FOR GROUND ELECTRODE SYSTEMS, THE CONTRACTOR SHALL FURNISH AND INSTALL SUPPLEMENTAL GROUND ELECTRODES AS NEEDED TO ACHIEVE A TEST RESULT OF 5 OHMS OR LESS.
3. THE CONTRACTOR IS RESPONSIBLE FOR PROPERLY SEQUENCING GROUNDING AND UNDERGROUND CONDUIT INSTALLATION AS TO PREVENT ANY LOSS OF CONTINUITY IN THE GROUNDING SYSTEM OR DAMAGE TO THE CONDUIT AND PROVIDE TESTING RESULTS.
4. METAL CONDUIT AND TRAY SHALL BE GROUNDED AND MADE ELECTRICALLY CONTINUOUS WITH LISTED BONDING FITTINGS OR BY BONDING ACROSS THE DISCONTINUITY WITH #6 COPPER WIRE UL APPROVED GROUNDING TYPE CONDUIT CLAMPS.
5. METAL RACEWAY SHALL NOT BE USED AS THE NEC REQUIRED EQUIPMENT GROUND CONDUCTOR. STRANDED COPPER CONDUCTORS WITH GREEN INSULATION, SIZED IN ACCORDANCE WITH THE NEC, SHALL BE FURNISHED AND INSTALLED WITH THE POWER CIRCUITS TO BTS EQUIPMENT.
6. EACH CABINET FRAME SHALL BE DIRECTLY CONNECTED TO THE MASTER GROUND BAR WITH GREEN INSULATED SUPPLEMENTAL EQUIPMENT GROUND WIRES, #6 STRANDED COPPER OR LARGER FOR INDOOR BTS; #2 BARE SOLID TINNED COPPER FOR OUTDOOR BTS.
7. CONNECTIONS TO THE GROUND BUS SHALL NOT BE DOUBLED UP OR STACKED BACK TO BACK CONNECTIONS ON OPPOSITE SIDE OF THE GROUND BUS ARE PERMITTED.
8. ALL EXTERIOR GROUND CONDUCTORS BETWEEN EQUIPMENT/GROUND BARS AND THE GROUND RING SHALL BE #2 SOLID TINNED COPPER UNLESS OTHERWISE INDICATED.
9. ALUMINUM CONDUCTOR OR COPPER CLAD STEEL CONDUCTOR SHALL NOT BE USED FOR GROUNDING CONNECTIONS.
10. USE OF 90° BENDS IN THE PROTECTION GROUNDING CONDUCTORS SHALL BE AVOIDED WHEN 45° BENDS CAN BE ADEQUATELY SUPPORTED.
11. EXOTHERMIC WELDS SHALL BE USED FOR ALL GROUNDING CONNECTIONS BELOW GRADE.
12. ALL GROUND CONNECTIONS ABOVE GRADE (INTERIOR AND EXTERIOR) SHALL BE FORMED USING HIGH PRESS CRIMPS.
13. COMPRESSION GROUND CONNECTIONS MAY BE REPLACED BY EXOTHERMIC WELD CONNECTIONS.
14. ICE BRIDGE BONDING CONDUCTORS SHALL BE EXOTHERMICALLY BONDED OR BOLTED TO THE BRIDGE AND THE TOWER GROUND BAR.
15. APPROVED ANTIOXIDANT COATINGS (i.e. CONDUCTIVE GEL OR PASTE) SHALL BE USED ON ALL COMPRESSION AND BOLTED GROUND CONNECTIONS.
16. ALL EXTERIOR GROUND CONNECTIONS SHALL BE COATED WITH A CORROSION RESISTANT MATERIAL.
17. MISCELLANEOUS ELECTRICAL AND NON-ELECTRICAL METAL BOXES, FRAMES AND SUPPORTS SHALL BE BONDED TO THE GROUND RING, IN ACCORDANCE WITH THE NEC.
18. BOND ALL METALLIC OBJECTS WITHIN 6 ft OF MAIN GROUND RING WITH (1) #2 BARE SOLID TINNED COPPER GROUND CONDUCTOR.
19. GROUND CONDUCTORS USED FOR THE FACILITY GROUNDING AND LIGHTNING PROTECTION SYSTEMS SHALL NOT BE ROUTED THROUGH METALLIC OBJECTS THAT FORM A RING AROUND THE CONDUCTOR, SUCH AS METALLIC CONDUITS, METAL SUPPORT CLIPS OR SLEEVES THROUGH WALLS OR FLOORS. WHEN IT IS REQUIRED TO BE HOUSED IN CONDUIT TO MEET CODE REQUIREMENTS OR LOCAL CONDITIONS, NON-METALLIC MATERIAL SUCH AS PVC CONDUIT SHALL BE USED. WHERE USE OF METAL CONDUIT IS UNAVOIDABLE (i.e., NONMETALLIC CONDUIT PROHIBITED BY LOCAL CODE) THE GROUND CONDUCTOR SHALL BE BONDED TO EACH END OF THE METAL CONDUIT.
20. ALL GROUNDS THAT TRANSITION FROM BELOW GRADE TO ABOVE GRADE MUST BE #2 BARE SOLID TINNED COPPER IN 3/4" NON-METALLIC, FLEXIBLE CONDUIT FROM 24" BELOW GRADE TO WITHIN 3" TO 6" OF CAD-WELD TERMINATION POINT. THE EXPOSED END OF THE CONDUIT MUST BE SEALED WITH SILICONE CAULK. (ADD TRANSITIONING GROUND STANDARD DETAIL AS WELL).
21. BUILDINGS WHERE THE MAIN GROUNDING CONDUCTORS ARE REQUIRED TO BE ROUTED TO GRADE, THE CONTRACTOR SHALL ROUTE TWO GROUNDING CONDUCTORS FROM THE ROOFTOP, TOWERS, AND WATER TOWERS GROUNDING RING, TO THE EXISTING GROUNDING SYSTEM, THE GROUNDING CONDUCTORS SHALL NOT BE SMALLER THAN 2/0 COPPER. ROOFTOP GROUNDING RING SHALL BE BONDED TO THE EXISTING GROUNDING SYSTEM, THE BUILDING STEEL COLUMNS, LIGHTNING PROTECTION SYSTEM, AND BUILDING MAIN WATER LINE (FERROUS OR NONFERROUS METAL PIPING ONLY). DO NOT ATTACH GROUNDING TO FIRE SPRINKLER SYSTEM PIPES.



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



INFINIGY
FROM ZERO TO INFINIGY
the solutions are endless
2500 W. HIGGINS RD. SUITE 500 |
HOFFMAN ESTATES, IL 60169
PHONE: 847-648-4068 | FAX: 518-690-0793
WWW.INFINIGY.COM



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
RCD	SS	CJW

RFDS REV #: N/A

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
0	10/25/21	ISSUED FOR PERMIT
1	11/16/21	REVISED PER COMMENTS
2	12/08/21	REVISED PER COMMENTS

A&E PROJECT NUMBER
1197-F0001-C

DISH WIRELESS, LLC.
PROJECT INFORMATION
BOBDL00107A
UNIONVILLE CO
82 LOVELY ST
UNIONVILLE, CT 06085

SHEET TITLE
GENERAL NOTES

SHEET NUMBER
GN-4

Exhibit D

Structural Analysis Report



Structural Analysis of a 100 ft Monopole

Site Number Dish Wireless BOBDL00107A

EIP: 701773

Site Name: Unionville CO

County: Hartford

Location: Unionville, CT

Checked By:

A handwritten signature in cursive script that reads "Patrick Propert".

Patrick Propert
Structural Design Engineer III

A handwritten signature in cursive script that reads "Kenneth Tang".
9/7/2021

Two Allegheny Ctr
Nova Tower 2, Suite 703
Pittsburgh, PA 15212

August 2021

September 7, 2021

Tom Rigg
Everest Infrastructure Partners
Two Allegheny Ctr
Nova Tower 2, Suite 703
Pittsburgh, PA 15212



RE: Dish Wireless – BOBDL00107A
EIP – 701773 – Unionville CO
82 Lovely St, Unionville, CT

Tom:

We have completed the structural analysis of the subject tower and **have found it to be adequate within the scope of this analysis to support the proposed antenna loading.** The tower was analyzed according to the code wind and ice parameters outlined in the *Code Requirements Table* following this letter.

The subject tower is a 100 ft Engineered Endeavors monopole tower consisting of (3) slip-jointed tubular pole sections. Pole dimeters range from 14.5” at the top to 27.5” at the base. Foundation capacities are based on a foundation mapping and geotechnical report by Wilkinson Engineering dated February 2010.

The loading used in the analysis consisted of the existing antennas/lines for AT&T as well as the following for Dish Wireless at 88 ft on a Valmont trisector antenna frame:

- (3) MX08FRO665-20 antennas
- (3) TA08025-B604 RRUs, (3) TA08025-B605 RRUs
- (1) RDIDC-9181-PF-48 fed with (1) 1-5/8” hybrid cable installed inside the pole

The results of the analysis showed all tower and apparent foundation elements to be loaded within allowable limits with a maximum stress rating of 78%. We recommend a post-construction inspection be completed by a structural engineer to document that tower-mounted equipment has been placed in compliance with the requirements of this analysis. For a detailed listing of tower performance, please see page 11 of the calculations.


We appreciate the opportunity to provide our professional services to Everest Infrastructure and Dish Wireless and if you have any questions concerning this analysis, please contact us.

Sincerely,

ARMOR TOWER, INC.

A handwritten signature in blue ink that reads "Patrick Botimer".

Patrick Botimer
Structural Design Engineer V



A handwritten signature in blue ink that reads "Kenneth Tang".

9/7/2021

CODE REQUIREMENTS


Governing code:	2018 CT State Building Code
Code basis/option:	2015 International Building Code
Referenced standard:	ANSI/TIA 222-G-2
Basic wind speed: (3-sec. gust):	V _{ult} : 120 mph with no ice V _{asd} : 93 mph with no ice 50 mph with 1" concurrent ice
County of site location:	Hartford
ASCE 7 Special wind region:	No
Structure/Risk Category:	II
Exposure Category:	B
Topographic Category: (Method 1)	1 - no topographic escalation
Crest Height/Tower Base AMSL Elevation:	0 ft/ 257 ft
Site Spectral Response:	S _s =0.182, S ₁ =0.064

PRIMARY ASSUMPTIONS CONSIDERED IN THIS PROJECT

1. Allowable steel stresses are defined by AISC-LRFD-99/360-16 and all welds conform to AWS D1.1 specification.
2. If reserved antennas/feed lines by other carriers are to be considered in this analysis, it is the responsibility of Everest Infrastructure and its affiliates to provide this information.
3. Any deviation from the analyzed antenna loading will require a re-analysis of the tower for verification of structural integrity. This analysis has considered the proposed hybrid line to be installed inside the tower as shown on drawing E-7.
4. This analysis assumes all tower members are galvanized adequately to prevent corrosion of the steel and that all tower members are in "like new" condition with no physical deterioration. This analysis also assumes the tower has been maintained properly per TIA 222-G Annex J recommended inspection and maintenance procedures for tower owners and is in a plumb condition. Armor Tower has not completed a condition assessment of the tower.
5. No accounting for residual stresses due to incorrect tower erection can be made. This analysis assumes all bolts are appropriately tightened providing necessary connection continuity and that the installation of the tower was performed by a qualified tower erector.
6. Foundation capacities are based on a foundation mapping and geotechnical report by Wilkinson Engineering dated February 2010.
7. No conclusions, expressed or implied, shall indicate that Armor Tower has made an evaluation of the original design, materials, fabrication, or potential installation or erection deficiencies. Any information contrary to that assumed for the purpose of preparing this analysis could alter the findings and conclusions stated herein.
8. Tower member sizes, geometry, and existing antenna loading are based on a tower analysis by MEI dated March 2010. It is our assumption that this data is complete and accurately reflects the existing conditions of the tower and equipment. Armor Tower has not been commissioned to field-validate this data. Armor Tower reserves the right to add to or modify this report as more information becomes available. Proposed equipment was outlined in a ColoApp dated April 15, 2021.

9. The investigation of the load carrying capacities of the antenna supporting frames/mounts is outside the scope of this analysis. Antenna mount certification can be completed under a separate contract.
10. Armor Tower can assist the contractor in providing a Class IV rigging plan for equipment lifting.

Section	1	2	3
Length (ft)	13.15	43.88	48.72
Number of Sides	18	18	18
Thickness (in)	0.1875	0.2500	0.3125
Socket Length (ft)	2.50	3.25	20.7642
Top Dia (in)	14.5000	15.6221	27.5000
Bot Dia (in)	16.3487	21.7155	39.17.2
Grade		A572-65	
Weight (lb)	405.6	2182.3	6505.1



DESIGNED APPURTENANCE LOADING

TYPE	ELEVATION	TYPE	ELEVATION
PwrVw P65-15-XLH-RR w. MtgPipe (ATI-Alpha)	98	Ericsson Radio 8843 B25/B66A (ATI-Gamma)	98
PwrVw P65-15-XLH-RR w. MtgPipe (ATI-Beta)	98	Ericsson Radio 4449 B5/B12 (ATI-Alpha)	98
PwrVw P65-15-XLH-RR w. MtgPipe (ATI-Gamma)	98	Ericsson Radio 4449 B5/B12 (ATI-Beta)	98
HPA-65R-BUU-H8 w. MtgPipe (ATI-Alpha)	98	Ericsson Radio 4449 B5/B12 (ATI-Gamma)	98
HPA-65R-BUU-H8 w. MtgPipe (ATI-Beta)	98	DC6-48-60-18-8F Surge Suppressor (ATI-Alpha)	98
HPA-65R-BUU-H8 w. MtgPipe (ATI-Gamma)	98	DC6-48-60-18-8F Surge Suppressor (ATI-Beta)	98
DMP65R-BU8D w. MtgPipe (ATI-Alpha)	98	Sabre 12' HD MOVE Platform (ATI)	98
DMP65R-BU8D w. MtgPipe (ATI-Beta)	98	MX08FRO665-20 w. Mtg Pipe (P-DW-Alpha)	88
DMP65R-BU8D w. MtgPipe (ATI-Gamma)	98	MX08FRO665-20 w. Mtg Pipe (P-DW-Beta)	88
DPA65R-BU6A w. Mtg Pipe (ATI-Gamma)	98	MX08FRO665-20 w. Mtg Pipe (P-DW-Gamma)	88
PwrVw TT19-08BP111-001 TMA (ATI-Alpha)	98	TA08025-B604 RRU (P-DW-Alpha)	88
PwrVw TT19-08BP111-001 TMA (ATI-Beta)	98	TA08025-B604 RRU (P-DW-Beta)	88
PwrVw TT19-08BP111-001 TMA (ATI-Gamma)	98	TA08025-B604 RRU (P-DW-Gamma)	88
Ericsson Radio 8843 B25/B66A (ATI-Alpha)	98	TA08025-B605 RRU (P-DW-Alpha)	88
Ericsson Radio 8843 B25/B66A (ATI-Beta)	98	TA08025-B605 RRU (P-DW-Beta)	88
Ericsson Radio 8843 B25/B66A (ATI-Gamma)	98	TA08025-B605 RRU (P-DW-Gamma)	88
		RDIDC-9181-PF-48 (P-DW-Alpha)	88
		Valmont SNP8R-396 Platform (P-DW)	88


MATERIAL STRENGTH

GRADE	Fy	Fu	GRADE	Fy	Fu
A572-65	65 ksi	80 ksi			


TOWER DESIGN NOTES

1. Tower designed for Exposure B to the TIA-222-G Standard.
2. Tower designed for a 93 mph basic wind in accordance with the TIA-222-G Standard.
3. Tower is also designed for a 50 mph basic wind with 1.00 in ice. Ice is considered to increase in thickness with height.
4. Deflections are based upon a 60 mph wind.
5. Tower Structure Class II.
6. Topographic Category 1 with Crest Height of 0.00 ft
7. Connections use galvanized A325 bolts, nuts and locking devices. Installation per TIA/EIA-222 and AISC Specifications.
8. Tower members are "hot dipped" galvanized in accordance with ASTM A123 and ASTM A153 Standards.
9. Welds are fabricated with ER-70S-6 electrodes.
10. ASCE7-10:120mph(Vult) => 93 mph (Vasd)
11. TOWER RATING: 78.4%

ALL REACTIONS ARE FACTORED



	Armor Tower Inc 9 North Main Cortland, NY 13045 Phone: 607-591-5381 FAX: 866-870-0840	Job: 100' MONOPOLE ANALYSIS Project: Dish Wireless BOBDL00107A - Unionville CO, CT Client: Everest Infrastructure Partners - 701773 Code: TIA-222-G Path:	Drawn by: PB Date: 09/07/21 Scale: NTS Dwg No. E-1
	<small> C:\Users\jacob@armor.com\AppData\Local\Temp\Folder\090721\Everest_Infrastructure\100107A_100ftMono\100ftMono.dwg </small>		
	<small> Project: 100' MONOPOLE ANALYSIS Client: Everest Infrastructure Partners - 701773 Code: TIA-222-G Path: </small>		
	<small> Drawn by: PB Date: 09/07/21 Scale: NTS Dwg No. E-1 </small>		

 Armor Tower Inc 9 North Main Cortland, NY 13045 Phone: 607-591-5381 FAX: 866-870-0840	Job 100' MONOPOLE ANALYSIS	Page 1 of 11
	Project Dish Wireless BOBDL00107A - Unionville CO, CT	Date 10:58:01 09/07/21
	Client Everest Infrastructure Partners - 701773	Designed by PB

Tower Input Data

The tower is a monopole.

This tower is designed using the TIA-222-G standard.

The following design criteria apply:

ASCE 7-10 Wind Data is used (wind speeds converted to nominal values).

Basic wind speed of 93 mph.

Structure Class II.

Exposure Category B.

Topographic Category 1.

Crest Height 0.00 ft.

Nominal ice thickness of 1.0000 in.

Ice thickness is considered to increase with height.

Ice density of 56 pcf.

A wind speed of 50 mph is used in combination with ice.

Temperature drop of 50 °F.

Deflections calculated using a wind speed of 60 mph.

Connections use galvanized A325 bolts, nuts and locking devices. Installation per TIA/EIA-222 and AISC Specifications.

Tower members are "hot dipped" galvanized in accordance with ASTM A123 and ASTM A153 Standards.

Welds are fabricated with ER-70S-6 electrodes.

ASCE7-10:120mph (Vult) => 93 mph (Vasd).

A non-linear (P-delta) analysis was used.

Pressures are calculated at each section.

Stress ratio used in pole design is 1.

Local bending stresses due to climbing loads, feed line supports, and appurtenance mounts are not considered.

Options

- | | | |
|--|---|--|
| <ul style="list-style-type: none"> Consider Moments - Legs Consider Moments - Horizontals Consider Moments - Diagonals Use Moment Magnification √ Use Code Stress Ratios √ Use Code Safety Factors - Guys Escalate Ice Always Use Max Kz Use Special Wind Profile √ Include Bolts In Member Capacity √ Leg Bolts Are At Top Of Section √ Secondary Horizontal Braces Leg Use Diamond Inner Bracing (4 Sided) SR Members Have Cut Ends SR Members Are Concentric | <ul style="list-style-type: none"> Distribute Leg Loads As Uniform Assume Legs Pinned √ Assume Rigid Index Plate √ Use Clear Spans For Wind Area √ Use Clear Spans For KL/r Retension Guys To Initial Tension Bypass Mast Stability Checks √ Use Azimuth Dish Coefficients √ Project Wind Area of Appurt. Autocalc Torque Arm Areas Add IBC .6D+W Combination Sort Capacity Reports By Component √ Triangulate Diamond Inner Bracing Treat Feed Line Bundles As Cylinder Ignore KL/ry For 60 Deg. Angle Legs | <ul style="list-style-type: none"> Use ASCE 10 X-Brace Ly Rules √ Calculate Redundant Bracing Forces Ignore Redundant Members in FEA SR Leg Bolts Resist Compression √ All Leg Panels Have Same Allowable Offset Girt At Foundation Consider Feed Line Torque Include Angle Block Shear Check Use TIA-222-G Bracing Resist. Exemption Use TIA-222-G Tension Splice Exemption <li style="background-color: #e0e0e0;">Poles Include Shear-Torsion Interaction Always Use Sub-Critical Flow Use Top Mounted Sockets Pole Without Linear Attachments Pole With Shroud Or No Appurtenances Outside and Inside Corner Radii Are Known |
|--|---|--|



Armor Tower Inc
 9 North Main
 Cortland, NY 13045
 Phone: 607-591-5381
 FAX: 866-870-0840

Job	100' MONOPOLE ANALYSIS	Page	2 of 11
Project	Dish Wireless BOBDL00107A - Unionville CO, CT	Date	10:58:01 09/07/21
Client	Everest Infrastructure Partners - 701773	Designed by	PB

Tapered Pole Section Geometry

Section	Elevation ft	Section Length ft	Splice Length ft	Number of Sides	Top Diameter in	Bottom Diameter in	Wall Thickness in	Bend Radius in	Pole Grade
L1	100.00-86.85	13.15	2.50	18	14.5000	16.3487	0.1875	0.7500	A572-65 (65 ksi)
L2	86.85-45.47	43.88	3.25	18	15.6221	21.7155	0.2500	1.0000	A572-65 (65 ksi)
L3	45.47-0.00	48.72		18	20.7642	27.5000	0.3125	1.2500	A572-65 (65 ksi)

Tapered Pole Properties

Section	Tip Dia. in	Area in ²	I in ⁴	r in	C in	I/C in ³	J in ⁴	I/Q in ²	w in	w/t
L1	14.6948	8.5177	220.4409	5.0809	7.3660	29.9268	441.1718	4.2597	2.2220	11.851
	16.5720	9.6179	317.3704	5.7372	8.3051	38.2137	635.1585	4.8099	2.5474	13.586
L2	16.1771	12.1978	364.1548	5.4571	7.9360	45.8862	728.7887	6.1000	2.3095	9.238
	22.0119	17.0329	991.5335	7.6203	11.0315	89.8822	1984.3718	8.5181	3.3819	13.528
L3	21.4925	20.2855	1071.9684	7.2603	10.5482	101.6256	2145.3474	10.1447	3.1045	9.934
	27.8760	26.9666	2518.2696	9.6516	13.9700	180.2627	5039.8527	13.4859	4.2900	13.728

Tower Elevation ft	Gusset Area (per face) ft ²	Gusset Thickness in	Gusset Grade	Adjust. Factor A _f	Adjust. Factor A _r	Weight Mult.	Double Angle Stitch Bolt Spacing Diagonals in	Double Angle Stitch Bolt Spacing Horizontal in	Double Angle Stitch Bolt Spacing Redundants in
L1 100.00-86.85				1	1	1			
L2 86.85-45.47				1	1	1			
L3 45.47-0.00				1	1	1			

Monopole Base Plate Data

Base Plate Data	
Base plate is square	
Base plate is grouted	√
Anchor bolt grade	A615-75
Anchor bolt size	2.2500 in
Number of bolts	6
Embedment length	72.0000 in
f _c	4 ksi
Grout space	4.0000 in
Base plate grade	A871 Gr60
Base plate thickness	2.5000 in
Bolt circle diameter	36.5000 in
Outer diameter	43.0000 in
Inner diameter	17.5000 in
Base plate type	Plain Plate



Armor Tower Inc
 9 North Main
 Cortland, NY 13045
 Phone: 607-591-5381
 FAX: 866-870-0840

Job	100' MONOPOLE ANALYSIS	Page	3 of 11
Project	Dish Wireless BOBDL00107A - Unionville CO, CT	Date	10:58:01 09/07/21
Client	Everest Infrastructure Partners - 701773	Designed by	PB

Feed Line/Linear Appurtenances - Entered As Round Or Flat

Description	Sector	Exclude From Torque Calculation	Component Type	Placement ft	Total Number	Number Per Row	Start/End Position	Width or Diameter in	Perimeter in	Weight plf
Safety Line 3/8	C	Yes	Surface Ar (CaAa)	100.00 - 0.00	1	1	0.000 0.000	0.3750		0.22

Feed Line/Linear Appurtenances - Entered As Area

Description	Face or Leg	Allow Shield	Exclude From Torque Calculation	Component Type	Placement ft	Total Number		C _{AA} ft ² /ft	Weight plf
*									
2.32" Flex Conduit w. Power & Fiber (AT&T)	C	No	Yes	Inside Pole	98.00 - 0.00	2	No Ice 1/2" Ice 1" Ice	0.00 0.00 0.00	2.80 2.80 2.80
LDF6-50A (1-1/4 FOAM) (AT&T)	C	No	Yes	Inside Pole	98.00 - 0.00	12	No Ice 1/2" Ice 1" Ice	0.00 0.00 0.00	0.66 0.66 0.66
* 1-5/8" hybrid (P-DW)	B	No	Yes	Inside Pole	88.00 - 0.00	1	No Ice 1/2" Ice 1" Ice	0.00 0.00 0.00	0.67 0.67 0.67

Feed Line/Linear Appurtenances Section Areas

Tower Section	Tower Elevation ft	Face	A _R ft ²	A _F ft ²	C _{AA} In Face ft ²	C _{AA} Out Face ft ²	Weight lb
L1	100.00-86.85	A	0.000	0.000	0.000	0.000	0.00
		B	0.000	0.000	0.000	0.000	0.77
		C	0.000	0.000	0.493	0.000	153.58
L2	86.85-45.47	A	0.000	0.000	0.000	0.000	0.00
		B	0.000	0.000	0.000	0.000	27.72
		C	0.000	0.000	1.552	0.000	568.56
L3	45.47-0.00	A	0.000	0.000	0.000	0.000	0.00
		B	0.000	0.000	0.000	0.000	30.47
		C	0.000	0.000	1.705	0.000	624.82

Feed Line/Linear Appurtenances Section Areas - With Ice

Tower Section	Tower Elevation ft	Face or Leg	Ice Thickness in	A _R ft ²	A _F ft ²	C _{AA} In Face ft ²	C _{AA} Out Face ft ²	Weight lb
L1	100.00-86.85	A	2.219	0.000	0.000	0.000	0.000	0.00
		B		0.000	0.000	0.000	0.000	0.77
		C		0.000	0.000	6.327	0.000	246.03
L2	86.85-45.47	A	2.142	0.000	0.000	0.000	0.000	0.00



Armor Tower Inc
 9 North Main
 Cortland, NY 13045
 Phone: 607-591-5381
 FAX: 866-870-0840

Job	100' MONOPOLE ANALYSIS	Page	4 of 11
Project	Dish Wireless BOBDL00107A - Unionville CO, CT	Date	10:58:01 09/07/21
Client	Everest Infrastructure Partners - 701773	Designed by	PB

Tower Section	Tower Elevation ft	Face or Leg	Ice Thickness in	A _R ft ²	A _F ft ²	C _{AA} In Face ft ²	C _{AA} Out Face ft ²	Weight lb
L3	45.47-0.00	B	1.920	0.000	0.000	0.000	0.000	27.72
		C		0.000	0.000	19.917	0.000	859.57
		A		0.000	0.000	0.000	0.000	0.00
		B		0.000	0.000	0.000	0.000	30.47
		C		0.000	0.000	21.188	0.000	924.39

Shielding Factor Ka

Tower Section	Feed Line Record No.	Description	Feed Line Segment Elev.	K _a No Ice	K _a Ice
L1	1	Safety Line 3/8	86.85 - 100.00	1.0000	1.0000
L2	1	Safety Line 3/8	45.47 - 86.85	1.0000	1.0000
L3	1	Safety Line 3/8	0.00 - 45.47	1.0000	1.0000

Discrete Tower Loads

Description	Face or Leg	Offset Type	Offsets: Horiz Lateral Vert ft ft ft	Azimuth Adjustment °	Placement ft	C _{AA} Front ft ²	C _{AA} Side ft ²	Weight lb
-------------	-------------	-------------	--------------------------------------	----------------------	--------------	---------------------------------------	--------------------------------------	-----------

*No Lightning Rod
 *

*AT&T Mar2020

PwrWv P65-15-XLH-RR w. MtgPipe (AT&T-Alpha)	A	From Face	3.00 -3.00 0.00	0.0000	98.00	No Ice 5.43 1/2" Ice 5.77 1" Ice 6.12	3.95 4.52 5.11	54.60 99.63 150.60
PwrWv P65-15-XLH-RR w. MtgPipe (AT&T-Beta)	B	From Face	3.00 -3.00 0.00	0.0000	98.00	No Ice 5.43 1/2" Ice 5.77 1" Ice 6.12	3.95 4.52 5.11	54.60 99.63 150.60
PwrWv P65-15-XLH-RR w. MtgPipe (AT&T-Gamma)	C	From Face	3.00 -3.00 0.00	0.0000	98.00	No Ice 5.43 1/2" Ice 5.77 1" Ice 6.12	3.95 4.52 5.11	54.60 99.63 150.60
HPA-65R-BUU-H8 w. MtgPipe (AT&T-Alpha)	A	From Face	3.00 0.00	0.0000	98.00	No Ice 12.83 1/2" Ice 13.44 1" Ice 14.05	9.38 10.78 12.04	82.20 175.71 278.92
HPA-65R-BUU-H8 w. MtgPipe (AT&T-Beta)	B	From Face	3.00 0.00	0.0000	98.00	No Ice 12.83 1/2" Ice 13.44 1" Ice 14.05	9.38 10.78 12.04	82.20 175.71 278.92
HPA-65R-BUU-H8 w. MtgPipe (AT&T-Gamma)	C	From Face	3.00 0.00	0.0000	98.00	No Ice 12.83 1/2" Ice 13.44 1" Ice 14.05	9.38 10.78 12.04	82.20 175.71 278.92
DMP65R-BU8D w. MtgPipe (AT&T-Alpha)	A	From Face	3.00 3.00 0.00	0.0000	98.00	No Ice 17.87 1/2" Ice 18.50 1" Ice 19.14	10.02 11.44 12.72	148.20 266.88 395.91
DMP65R-BU8D w. MtgPipe (AT&T-Beta)	B	From Face	3.00 3.00	0.0000	98.00	No Ice 17.87 1/2" Ice 18.50	10.02 11.44	148.20 266.88



Armor Tower Inc
 9 North Main
 Cortland, NY 13045
 Phone: 607-591-5381
 FAX: 866-870-0840

Job	100' MONOPOLE ANALYSIS	Page	5 of 11
Project	Dish Wireless BOBDL00107A - Unionville CO, CT	Date	10:58:01 09/07/21
Client	Everest Infrastructure Partners - 701773	Designed by	PB

Description	Face or Leg	Offset Type	Offsets:			Azimuth Adjustment	Placement	C _{AA} Front	C _{AA} Side	Weight	
			Horz	Vert	Lateral						ft
DPA65R-BU6A w. Mtg Pipe (AT&T-Gamma)	C	From Face	0.00			0.0000	98.00	1" Ice	19.14	12.72	395.91
			3.00					No Ice	7.88	7.44	69.90
			3.00					1/2" Ice	8.34	8.40	138.34
PwrWv TT19-08BP111-001 TMA (AT&T-Alpha)	A	From Face	0.00			0.0000	98.00	1" Ice	8.80	9.23	214.57
			3.00					No Ice	0.55	0.45	16.00
			0.00					1/2" Ice	0.65	0.53	21.80
PwrWv TT19-08BP111-001 TMA (AT&T-Beta)	B	From Face	0.00			0.0000	98.00	1" Ice	0.75	0.63	29.22
			3.00					No Ice	0.55	0.45	16.00
			0.00					1/2" Ice	0.65	0.53	21.80
PwrWv TT19-08BP111-001 TMA (AT&T-Gamma)	C	From Face	0.00			0.0000	98.00	1" Ice	0.75	0.63	29.22
			3.00					No Ice	0.55	0.45	16.00
			0.00					1/2" Ice	0.65	0.53	21.80
Ericsson Radio 8843 B25/B66A (AT&T-Alpha)	A	From Face	0.00			0.0000	98.00	1" Ice	0.75	0.63	29.22
			3.00					No Ice	1.64	1.36	71.87
			0.00					1/2" Ice	1.80	1.51	89.52
Ericsson Radio 8843 B25/B66A (AT&T-Beta)	B	From Face	0.00			0.0000	98.00	1" Ice	1.97	1.66	109.89
			3.00					No Ice	1.64	1.36	71.87
			0.00					1/2" Ice	1.80	1.51	89.52
Ericsson Radio 8843 B25/B66A (AT&T-Gamma)	C	From Face	0.00			0.0000	98.00	1" Ice	1.97	1.66	109.89
			3.00					No Ice	1.64	1.36	71.87
			0.00					1/2" Ice	1.80	1.51	89.52
Ericsson Radio 4449 B5/B12 (AT&T-Alpha)	A	From Face	0.00			0.0000	98.00	1" Ice	1.97	1.66	109.89
			3.00					No Ice	1.97	1.41	70.50
			0.00					1/2" Ice	2.15	1.57	89.03
Ericsson Radio 4449 B5/B12 (AT&T-Beta)	B	From Face	0.00			0.0000	98.00	1" Ice	2.33	1.73	110.38
			3.00					No Ice	1.97	1.41	70.50
			0.00					1/2" Ice	2.15	1.57	89.03
Ericsson Radio 4449 B5/B12 (AT&T-Gamma)	C	From Face	0.00			0.0000	98.00	1" Ice	2.33	1.73	110.38
			3.00					No Ice	1.97	1.41	70.50
			0.00					1/2" Ice	2.15	1.57	89.03
DC6-48-60-18-8F Surge Suppressor (AT&T-Alpha)	A	From Face	0.00			0.0000	98.00	1" Ice	2.33	1.73	110.38
			2.00					No Ice	0.79	0.79	20.00
			0.00					1/2" Ice	1.27	1.27	35.12
DC6-48-60-18-8F Surge Suppressor (AT&T-Beta)	B	From Face	0.00			0.0000	98.00	1" Ice	1.45	1.45	52.57
			2.00					No Ice	0.79	0.79	20.00
			0.00					1/2" Ice	1.27	1.27	35.12
Sabre 12' HD MOVE Platform (AT&T)	C	None	0.00			0.0000	98.00	1" Ice	1.45	1.45	52.57
								No Ice	28.00	28.00	2959.00
								1/2" Ice	32.00	32.00	3450.00
*											
*DishWireless Aug2021											
MX08FRO665-20 w. Mtg Pipe (P-DW-Alpha)	A	From Face	3.00			0.0000	88.00	No Ice	12.49	7.29	93.90
			0.00					1/2" Ice	12.99	8.25	183.58
			0.00					1" Ice	13.49	9.08	281.61
MX08FRO665-20 w. Mtg Pipe (P-DW-Beta)	B	From Face	3.00			0.0000	88.00	No Ice	12.49	7.29	93.90
			0.00					1/2" Ice	12.99	8.25	183.58
			0.00					1" Ice	13.49	9.08	281.61
MX08FRO665-20 w. Mtg Pipe (P-DW-Gamma)	C	From Face	3.00			0.0000	88.00	No Ice	12.49	7.29	93.90
			0.00					1/2" Ice	12.99	8.25	183.58
			0.00					1" Ice	13.49	9.08	281.61
TA08025-B604 RRU (P-DW-Alpha)	A	From Face	3.00			0.0000	88.00	No Ice	1.98	1.04	64.00
			-2.00					1/2" Ice	2.15	1.18	80.85
			0.00					1" Ice	2.33	1.32	100.41
TA08025-B604 RRU (P-DW-Beta)	B	From Face	3.00			0.0000	88.00	No Ice	1.98	1.04	64.00
			-2.00					1/2" Ice	2.15	1.18	80.85
			0.00					1" Ice	2.33	1.32	100.41




Armor Tower Inc
 9 North Main
 Cortland, NY 13045
 Phone: 607-591-5381
 FAX: 866-870-0840

Job	100' MONOPOLE ANALYSIS	Page	6 of 11
Project	Dish Wireless BOBDL00107A - Unionville CO, CT	Date	10:58:01 09/07/21
Client	Everest Infrastructure Partners - 701773	Designed by	PB

Description	Face or Leg	Offset Type	Offsets:		Azimuth Adjustment	Placement	C _{AA}		Weight
			Horz	Lateral			Front	Side	
			ft	ft	°	ft	ft ²	ft ²	lb
TA08025-B604 RRU (P-DW-Gamma)	C	From Face	3.00	0.0000	88.00	No Ice	1.98	1.04	64.00
			-2.00			1/2" Ice	2.15	1.18	80.85
			0.00			1" Ice	2.33	1.32	100.41
TA08025-B605 RRU (P-DW-Alpha)	A	From Face	3.00	0.0000	88.00	No Ice	1.98	1.20	75.00
			-2.00			1/2" Ice	2.15	1.34	93.09
			0.00			1" Ice	2.33	1.49	113.96
TA08025-B605 RRU (P-DW-Beta)	B	From Face	3.00	0.0000	88.00	No Ice	1.98	1.20	75.00
			-2.00			1/2" Ice	2.15	1.34	93.09
			0.00			1" Ice	2.33	1.49	113.96
TA08025-B605 RRU (P-DW-Gamma)	C	From Face	3.00	0.0000	88.00	No Ice	1.98	1.20	75.00
			-2.00			1/2" Ice	2.15	1.34	93.09
			0.00			1" Ice	2.33	1.49	113.96
RDIDC-9181-PF-48 (P-DW-Alpha)	A	From Face	2.00	0.0000	88.00	No Ice	2.31	1.29	22.00
			0.00			1/2" Ice	2.50	1.45	41.25
			0.00			1" Ice	2.70	1.61	63.41
Valmont SNP8HR-396 Platform (P-DW)	C	None		0.0000	88.00	No Ice	30.70	30.70	1786.00
						1/2" Ice	42.00	42.00	2052.00
						1" Ice	53.30	53.30	2318.00

Load Combinations

Comb. No.	Description
1	Dead Only
2	1.2 Dead+1.6 Wind 0 deg - No Ice
3	0.9 Dead+1.6 Wind 0 deg - No Ice
4	1.2 Dead+1.6 Wind 30 deg - No Ice
5	0.9 Dead+1.6 Wind 30 deg - No Ice
6	1.2 Dead+1.6 Wind 60 deg - No Ice
7	0.9 Dead+1.6 Wind 60 deg - No Ice
8	1.2 Dead+1.6 Wind 90 deg - No Ice
9	0.9 Dead+1.6 Wind 90 deg - No Ice
10	1.2 Dead+1.6 Wind 120 deg - No Ice
11	0.9 Dead+1.6 Wind 120 deg - No Ice
12	1.2 Dead+1.6 Wind 150 deg - No Ice
13	0.9 Dead+1.6 Wind 150 deg - No Ice
14	1.2 Dead+1.6 Wind 180 deg - No Ice
15	0.9 Dead+1.6 Wind 180 deg - No Ice
16	1.2 Dead+1.6 Wind 210 deg - No Ice
17	0.9 Dead+1.6 Wind 210 deg - No Ice
18	1.2 Dead+1.6 Wind 240 deg - No Ice
19	0.9 Dead+1.6 Wind 240 deg - No Ice
20	1.2 Dead+1.6 Wind 270 deg - No Ice
21	0.9 Dead+1.6 Wind 270 deg - No Ice
22	1.2 Dead+1.6 Wind 300 deg - No Ice
23	0.9 Dead+1.6 Wind 300 deg - No Ice
24	1.2 Dead+1.6 Wind 330 deg - No Ice
25	0.9 Dead+1.6 Wind 330 deg - No Ice
26	1.2 Dead+1.0 Ice+1.0 Temp
27	1.2 Dead+1.0 Wind 0 deg+1.0 Ice+1.0 Temp
28	1.2 Dead+1.0 Wind 30 deg+1.0 Ice+1.0 Temp

 Armor Tower Inc 9 North Main Cortland, NY 13045 Phone: 607-591-5381 FAX: 866-870-0840	Job 100' MONOPOLE ANALYSIS	Page 7 of 11
	Project Dish Wireless BOBDL00107A - Unionville CO, CT	Date 10:58:01 09/07/21
	Client Everest Infrastructure Partners - 701773	Designed by PB

Comb. No.	Description
29	1.2 Dead+1.0 Wind 60 deg+1.0 Ice+1.0 Temp
30	1.2 Dead+1.0 Wind 90 deg+1.0 Ice+1.0 Temp
31	1.2 Dead+1.0 Wind 120 deg+1.0 Ice+1.0 Temp
32	1.2 Dead+1.0 Wind 150 deg+1.0 Ice+1.0 Temp
33	1.2 Dead+1.0 Wind 180 deg+1.0 Ice+1.0 Temp
34	1.2 Dead+1.0 Wind 210 deg+1.0 Ice+1.0 Temp
35	1.2 Dead+1.0 Wind 240 deg+1.0 Ice+1.0 Temp
36	1.2 Dead+1.0 Wind 270 deg+1.0 Ice+1.0 Temp
37	1.2 Dead+1.0 Wind 300 deg+1.0 Ice+1.0 Temp
38	1.2 Dead+1.0 Wind 330 deg+1.0 Ice+1.0 Temp
39	Dead+Wind 0 deg - Service
40	Dead+Wind 30 deg - Service
41	Dead+Wind 60 deg - Service
42	Dead+Wind 90 deg - Service
43	Dead+Wind 120 deg - Service
44	Dead+Wind 150 deg - Service
45	Dead+Wind 180 deg - Service
46	Dead+Wind 210 deg - Service
47	Dead+Wind 240 deg - Service
48	Dead+Wind 270 deg - Service
49	Dead+Wind 300 deg - Service
50	Dead+Wind 330 deg - Service

Maximum Reactions

Location	Condition	Gov. Load Comb.	Vertical lb	Horizontal, X lb	Horizontal, Z lb
Pole	Max. Vert	30	34779.17	-3180.35	-3.24
	Max. H _x	21	13201.65	9557.04	15.56
	Max. H _z	2	17602.20	15.56	9323.35
	Max. M _x	2	799907.69	15.56	9323.35
	Max. M _z	8	824779.43	-9557.04	-15.56
	Max. Torsion	12	869.77	-4791.99	-8082.04
	Min. Vert	5	13201.65	-4765.04	8066.48
	Min. H _x	9	13201.65	-9557.04	-15.56
	Min. H _z	14	17602.20	-15.56	-9323.35
	Min. M _x	14	-798870.04	-15.56	-9323.35
	Min. M _z	20	-824254.93	9557.04	15.56
	Min. Torsion	24	-868.37	4791.99	8082.04

Tower Mast Reaction Summary

Load Combination	Vertical lb	Shear _x lb	Shear _z lb	Overturning Moment, M _x lb-ft	Overturning Moment, M _z lb-ft	Torque lb-ft
Dead Only	14668.50	0.00	-0.00	-402.95	-203.40	0.01
1.2 Dead+1.6 Wind 0 deg - No Ice	17602.20	-15.56	-9323.35	-799907.69	1279.70	764.29
0.9 Dead+1.6 Wind 0 deg - No Ice	13201.65	-15.56	-9323.35	-778112.61	1305.25	760.77
1.2 Dead+1.6 Wind 30 deg - No Ice	17602.20	4765.04	-8066.48	-692024.20	-411283.94	454.72
0.9 Dead+1.6 Wind 30 deg - No Ice	13201.65	4765.04	-8066.48	-673150.52	-400054.96	453.79



Armor Tower Inc
 9 North Main
 Cortland, NY 13045
 Phone: 607-591-5381
 FAX: 866-870-0840

Job	100' MONOPOLE ANALYSIS	Page	8 of 11
Project	Dish Wireless BOBDL00107A - Unionville CO, CT	Date	10:58:01 09/07/21
Client	Everest Infrastructure Partners - 701773	Designed by	PB

Load Combination	Vertical lb	Shear _x lb	Shear _y lb	Overturning Moment, M _x lb-ft	Overturning Moment, M _y lb-ft	Torque lb-ft
1.2 Dead+1.6 Wind 60 deg - No Ice	17602.20	8268.86	-4648.20	-398829.16	-713614.33	23.09
0.9 Dead+1.6 Wind 60 deg - No Ice	13201.65	8268.86	-4648.20	-387900.44	-694183.00	25.04
1.2 Dead+1.6 Wind 90 deg - No Ice	17602.20	9557.04	15.56	1005.41	-824779.43	-414.52
0.9 Dead+1.6 Wind 90 deg - No Ice	13201.65	9557.04	15.56	1109.58	-802335.12	-410.25
1.2 Dead+1.6 Wind 120 deg - No Ice	17602.20	8284.41	4675.15	400419.45	-715104.79	-741.35
0.9 Dead+1.6 Wind 120 deg - No Ice	13201.65	8284.41	4675.15	389712.60	-695636.03	-735.87
1.2 Dead+1.6 Wind 150 deg - No Ice	17602.20	4791.99	8082.04	692488.91	-413892.06	-869.77
0.9 Dead+1.6 Wind 150 deg - No Ice	13201.65	4791.99	8082.04	673870.75	-402594.35	-864.51
1.2 Dead+1.6 Wind 180 deg - No Ice	17602.20	15.56	9323.35	798870.04	-1752.16	-764.36
0.9 Dead+1.6 Wind 180 deg - No Ice	13201.65	15.56	9323.35	777371.04	-1643.65	-760.82
1.2 Dead+1.6 Wind 210 deg - No Ice	17602.20	-4765.04	8066.48	690967.14	410791.77	-453.41
0.9 Dead+1.6 Wind 210 deg - No Ice	13201.65	-4765.04	8066.48	672395.56	399702.60	-452.61
1.2 Dead+1.6 Wind 240 deg - No Ice	17602.20	-8268.86	4648.20	397780.88	713096.12	-21.78
0.9 Dead+1.6 Wind 240 deg - No Ice	13201.65	-8268.86	4648.20	387151.80	693812.50	-23.83
1.2 Dead+1.6 Wind 270 deg - No Ice	17602.20	-9557.04	-15.56	-2025.57	824254.93	414.54
0.9 Dead+1.6 Wind 270 deg - No Ice	13201.65	-9557.04	-15.56	-1838.56	801960.45	410.26
1.2 Dead+1.6 Wind 300 deg - No Ice	17602.20	-8284.41	-4675.15	-401420.20	714600.00	740.02
0.9 Dead+1.6 Wind 300 deg - No Ice	13201.65	-8284.41	-4675.15	-390428.16	695275.29	734.63
1.2 Dead+1.6 Wind 330 deg - No Ice	17602.20	-4791.99	-8082.04	-693498.38	413413.32	868.37
0.9 Dead+1.6 Wind 330 deg - No Ice	13201.65	-4791.99	-8082.04	-674592.60	402251.75	863.26
1.2 Dead+1.0 Ice+1.0 Temp	34779.16	0.01	-0.02	-2685.42	-1114.45	0.36
1.2 Dead+1.0 Wind 0 deg+1.0 Ice+1.0 Temp	34779.17	-3.24	-3141.70	-303334.66	-748.09	168.19
1.2 Dead+1.0 Wind 30 deg+1.0 Ice+1.0 Temp	34779.16	1587.23	-2718.95	-262979.84	-153652.49	68.48
1.2 Dead+1.0 Wind 60 deg+1.0 Ice+1.0 Temp	34779.16	2752.42	-1567.91	-152760.04	-265683.17	-49.56
1.2 Dead+1.0 Wind 90 deg+1.0 Ice+1.0 Temp	34779.17	3180.35	3.24	-2332.90	-306699.99	-154.19
1.2 Dead+1.0 Wind 120 deg+1.0 Ice+1.0 Temp	34779.16	2755.66	1573.53	147991.66	-266053.30	-217.49
1.2 Dead+1.0 Wind 150 deg+1.0 Ice+1.0 Temp	34779.16	1592.85	2722.19	257940.92	-154293.86	-222.40
1.2 Dead+1.0 Wind 180 deg+1.0 Ice+1.0 Temp	34779.17	3.25	3141.69	297930.56	-1487.94	-167.52
1.2 Dead+1.0 Wind 210 deg+1.0 Ice+1.0 Temp	34779.16	-1587.23	2718.95	257567.96	151413.93	-67.71
1.2 Dead+1.0 Wind 240 deg+1.0 Ice+1.0 Temp	34779.16	-2752.42	1567.91	147347.52	263440.57	50.33
1.2 Dead+1.0 Wind 270 deg+1.0 Ice+1.0 Temp	34779.17	-3180.34	-3.25	-3072.57	304456.13	154.92



Armor Tower Inc
 9 North Main
 Cortland, NY 13045
 Phone: 607-591-5381
 FAX: 866-870-0840

Job	100' MONOPOLE ANALYSIS	Page	9 of 11
Project	Dish Wireless BOBDL00107A - Unionville CO, CT	Date	10:58:01 09/07/21
Client	Everest Infrastructure Partners - 701773	Designed by	PB

Load Combination	Vertical lb	Shear _x lb	Shear _y lb	Overturning Moment, M _x lb-ft	Overturning Moment, M _y lb-ft	Torque lb-ft
1.2 Dead+1.0 Wind 300 deg+1.0 Ice+1.0 Temp	34779.16	-2755.66	-1573.53	-153396.72	263809.04	218.16
1.2 Dead+1.0 Wind 330 deg+1.0 Ice+1.0 Temp	34779.16	-1592.85	-2722.20	-263345.35	152053.64	223.00
Dead+Wind 0 deg - Service	14668.50	-3.62	-2172.12	-183938.67	132.98	181.69
Dead+Wind 30 deg - Service	14668.50	1110.12	-1879.30	-159179.01	-94573.21	106.91
Dead+Wind 60 deg - Service	14668.50	1926.41	-1082.93	-91881.31	-163995.12	3.48
Dead+Wind 90 deg - Service	14668.50	2226.52	3.62	-79.34	-189531.85	-100.88
Dead+Wind 120 deg - Service	14668.50	1930.03	1089.20	91629.19	-164342.10	-178.21
Dead+Wind 150 deg - Service	14668.50	1116.39	1882.93	158671.99	-95174.68	-207.79
Dead+Wind 180 deg - Service	14668.50	3.62	2172.12	183084.14	-562.06	-181.67
Dead+Wind 210 deg - Service	14668.50	-1110.12	1879.30	158323.64	94143.23	-106.86
Dead+Wind 240 deg - Service	14668.50	-1926.41	1082.93	91026.36	163564.00	-3.43
Dead+Wind 270 deg - Service	14668.50	-2226.52	-3.62	-774.37	189100.49	100.90
Dead+Wind 300 deg - Service	14668.50	-1930.03	-1089.20	-92482.06	163911.62	178.21
Dead+Wind 330 deg - Service	14668.50	-1116.39	-1882.93	-159525.27	94745.35	207.78

Maximum Tower Deflections - Service Wind

Section No.	Elevation ft	Horz. Deflection in	Gov. Load Comb.	Tilt °	Twist °
L1	100 - 86.8542	22.883	42	1.9199	0.0099
L2	89.3542 - 45.4742	18.632	42	1.8750	0.0073
L3	48.7242 - 0	5.554	42	1.0689	0.0022


Critical Deflections and Radius of Curvature - Service Wind

Elevation ft	Appurtenance	Gov. Load Comb.	Deflection in	Tilt °	Twist °	Radius of Curvature ft
98.00	PwrWv P65-15-XLH-RR w. MtgPipe	42	22.078	1.9148	0.0094	13193
88.00	MX08FRO665-20 w. Mtg Pipe	42	18.103	1.8637	0.0070	5807

Maximum Tower Deflections - Design Wind

Section No.	Elevation ft	Horz. Deflection in	Gov. Load Comb.	Tilt °	Twist °
L1	100 - 86.8542	99.647	8	8.3729	0.0423
L2	89.3542 - 45.4742	81.163	8	8.1836	0.0313
L3	48.7242 - 0	24.204	8	4.6645	0.0092

Critical Deflections and Radius of Curvature - Design Wind

 Armor Tower Inc 9 North Main Cortland, NY 13045 Phone: 607-591-5381 FAX: 866-870-0840	Job 100' MONOPOLE ANALYSIS	Page 10 of 11
	Project Dish Wireless BOBDL00107A - Unionville CO, CT	Date 10:58:01 09/07/21
	Client Everest Infrastructure Partners - 701773	Designed by PB

Elevation	Appurtenance	Gov. Load Comb.	Deflection	Tilt	Twist	Radius of Curvature
ft			in	°	°	ft
98.00	PwrWv P65-15-XLH-RR w. MtgPipe	8	96.146	8.3520	0.0401	3188
88.00	MX08FRO665-20 w. Mtg Pipe	8	78.859	8.1350	0.0300	1396

Base Plate Design Data

Plate Thickness	Number of Anchor Bolts	Anchor Bolt Size	Actual Allowable Ratio Bolt Tension	Actual Allowable Ratio Concrete Stress	Actual Allowable Ratio Plate Stress	Actual Allowable Ratio Stiffener Stress	Controlling Condition	Critical Ratio
in		in	lb	ksi	ksi	ksi		
2.5000	6	2.2500	131986.00 223654.40 0.59	2.177 4.080 0.53	41.842 54.000 0.77		Plate	0.77 ✓

Compression Checks

Pole Design Data

Section No.	Elevation	Size	L	L _u	Kl/r	A	P _u	φP _n	Ratio P _u / φP _n
	ft		ft	ft		in ²	lb	lb	
L1	100 - 86.8542 (1)	TP16.3487x14.5x0.1875	13.15	100.00	213.8	9.4087	-13221.20	46495.10	0.284
L2	86.8542 - 45.4742 (2)	TP21.7155x15.6221x0.25	43.88	100.00	160.9	16.6748	-11140.10	145586.00	0.077
L3	45.4742 - 0 (3)	TP27.5x20.7642x0.3125	48.72	100.00	124.3	26.9666	-17583.40	394093.00	0.045

Pole Bending Design Data

Section No.	Elevation	Size	M _{ux}	φM _{ux}	Ratio M _{ux} / φM _{ux}	M _{uy}	φM _{uy}	Ratio M _{uy} / φM _{uy}
	ft		lb-ft	lb-ft		lb-ft	lb-ft	
L1	100 - 86.8542 (1)	TP16.3487x14.5x0.1875	17448.17	226351.67	0.077	0.00	226351.67	0.000
L2	86.8542 - 45.4742 (2)	TP21.7155x15.6221x0.25	374880.00	533197.50	0.703	0.00	533197.50	0.000
L3	45.4742 - 0 (3)	TP27.5x20.7642x0.3125	824780.00	1116050.00	0.739	0.00	1116050.00	0.000

Pole Shear Design Data



Armor Tower Inc
 9 North Main
 Cortland, NY 13045
 Phone: 607-591-5381
 FAX: 866-870-0840

Job	100' MONOPOLE ANALYSIS	Page	11 of 11
Project	Dish Wireless BOBDL00107A - Unionville CO, CT	Date	10:58:01 09/07/21
Client	Everest Infrastructure Partners - 701773	Designed by	PB

Section No.	Elevation ft	Size	Actual V_u lb	ϕV_n lb	Ratio $\frac{V_u}{\phi V_n}$	Actual T_u lb-ft	ϕT_n lb-ft	Ratio $\frac{T_u}{\phi T_n}$
L1	100 - 86.8542 (1)	TP16.3487x14.5x0.1875	1900.13	349510.00	0.005	28.27	454065.00	0.000
L2	86.8542 - 45.4742 (2)	TP21.7155x15.6221x0.25	8798.12	619426.00	0.014	417.62	1069608.33	0.000
L3	45.4742 - 0 (3)	TP27.5x20.7642x0.3125	9591.59	1001740.00	0.010	414.51	2238700.00	0.000

Pole Interaction Design Data

Section No.	Elevation ft	Ratio $\frac{P_u}{\phi P_n}$	Ratio $\frac{M_{ux}}{\phi M_{nx}}$	Ratio $\frac{M_{uy}}{\phi M_{ny}}$	Ratio $\frac{V_u}{\phi V_n}$	Ratio $\frac{T_u}{\phi T_n}$	Comb. Stress Ratio	Allow. Stress Ratio	Criteria
L1	100 - 86.8542 (1)	0.284	0.077	0.000	0.005	0.000	0.361	1.000	4.8.2 ✓
L2	86.8542 - 45.4742 (2)	0.077	0.703	0.000	0.014	0.000	0.780	1.000	4.8.2 ✓
L3	45.4742 - 0 (3)	0.045	0.739	0.000	0.010	0.000	0.784	1.000	4.8.2 ✓

Section Capacity Table

Section No.	Elevation ft	Component Type	Size	Critical Element	P lb	ϕP_{allow} lb	% Capacity	Pass Fail	
L1	100 - 86.8542	Pole	TP16.3487x14.5x0.1875	1	-13221.20	46495.10	36.1	Pass	
L2	86.8542 - 45.4742	Pole	TP21.7155x15.6221x0.25	2	-11140.10	145586.00	78.0	Pass	
L3	45.4742 - 0	Pole	TP27.5x20.7642x0.3125	3	-17583.40	394093.00	78.4	Pass	
							Summary		
							Pole (L3)	78.4	Pass
							Base Plate	77.5	Pass
							RATING =	78.4	Pass

Monopole Pad & Pier Calculations

Client: Dish Wireless
Project: Unionville, CT
09/07/21 11:02

Applied Factored Loads:

OTM: 825 kip-ft
Shear: 9.6 kip
Deadload: 17.6 kip

Specific Gravity: 2.65
Soil Unit Weight: 120 pcf
Submerged Unit Wt: 74.72 pcf
Soil Ang: 34 °
Concrete Unit Wt: 150 pcf
Concrete f'c: 3000 psi
Rebar Fy: 60000 psi

Pad Dimensions:

Width: 17 ft
Thickness: 4.5 ft
OADepth: 9.5 ft
Abolt Circle 36.5 in
ABolt QTY/φ: 6 2.25 in
Pier Diam: 6.5 ft 4.38 ft min
Pier Height: 0.5 ft above Grade
Pier Depth: 5 ft
Total Moment: 878 kip-ft

Concrete Volume: 54.9 cuyd
Depth to Water: 9.5 ft

Soil Resistance:

Soil1: 1473.9 kip-ft
Soil2: 604.1 kip-ft
Soil3: 77.3 kip-ft

Concrete Resistance:

1658 kip-ft

OTM Capacity:

3275 kip-ft

φs: TIA 222G 0.75 26.8% Loaded

Bearing Capacity:

φs: 0.75

Soil Type @ Bearing Location: Sand
SPT-N @ Bearing Location: 50



fb(max): 2387 psf
Fb: 15000 psf per geotech
15.9% Loaded

ASCE 7 Hazards Report

Address:
82 Lovely St
Unionville, Connecticut
06085

Standard: ASCE/SEI 7-10
Risk Category: II
Soil Class: D - Stiff Soil

Elevation: 257.03 ft (NAVD 88)
Latitude: 41.761284
Longitude: -72.887428



Wind

Results:

Wind Speed:	120 Vmph
10-year MRI	76 Vmph
25-year MRI	86 Vmph
50-year MRI	91 Vmph
100-year MRI	98 Vmph

Date Accessed: ~~ASCE/SEI 7-10~~ **ASCE/SEI 7-22** Fig. 26.5-1A and Figs. CC-1–CC-4, and Section 26.5.2, incorporating errata of March 12, 2014

Value provided is 3-second gust wind speeds at 33 ft above ground for Exposure C Category, based on linear interpolation between contours. Wind speeds are interpolated in accordance with the 7-10 Standard. Wind speeds correspond to approximately a 7% probability of exceedance in 50 years (annual exceedance probability = 0.00143, MRI = 700 years).



Site is in a hurricane-prone region as defined in ASCE/SEI 7-10 Section 26.2. Glazed openings need not be protected against wind-borne debris.

Site Soil Class: D - Stiff Soil

Results:

S_s :	0.182	S_{DS} :	0.194
S_1 :	0.064	S_{D1} :	0.103
F_a :	1.6	T_L :	6
F_v :	2.4	PGA :	0.092
S_{MS} :	0.291	PGA _M :	0.147
S_{M1} :	0.154	F _{PGA} :	1.6
		I_e :	1

Seismic Design Category B



Data Accessed:

Mon Aug 30 2021

Date Source:

USGS Seismic Design Maps based on ASCE/SEI 7-10, incorporating Supplement 1 and errata of March 31, 2013, and ASCE/SEI 7-10 Table 1.5-2. Additional data for site-specific ground motion procedures in accordance with ASCE/SEI 7-10 Ch. 21 are available from USGS.

Ice

Results:

Ice Thickness: 1.00 in.
Concurrent Temperature: 5 F
Gust Speed: 50 mph

Data Source: Standard ASCE/SEI 7-10, Figs. 10-2 through 10-8

Date Accessed: Mon Aug 30 2021

Ice thicknesses on structures in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.

Values provided are equivalent radial ice thicknesses due to freezing rain with concurrent 3-second gust speeds, for a 50-year mean recurrence interval, and temperatures concurrent with ice thicknesses due to freezing rain. Thicknesses for ice accretions caused by other sources shall be obtained from local meteorological studies. Ice thicknesses in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.

The ASCE 7 Hazard Tool is provided for your convenience, for informational purposes only, and is provided “as is” and without warranties of any kind. The location data included herein has been obtained from information developed, produced, and maintained by third party providers; or has been extrapolated from maps incorporated in the ASCE 7 standard. While ASCE has made every effort to use data obtained from reliable sources or methodologies, ASCE does not make any representations or warranties as to the accuracy, completeness, reliability, currency, or quality of any data provided herein. Any third-party links provided by this Tool should not be construed as an endorsement, affiliation, relationship, or sponsorship of such third-party content by or from ASCE.

ASCE does not intend, nor should anyone interpret, the results provided by this Tool to replace the sound judgment of a competent professional, having knowledge and experience in the appropriate field(s) of practice, nor to substitute for the standard of care required of such professionals in interpreting and applying the contents of this Tool or the ASCE 7 standard.

In using this Tool, you expressly assume all risks associated with your use. Under no circumstances shall ASCE or its officers, directors, employees, members, affiliates, or agents be liable to you or any other person for any direct, indirect, special, incidental, or consequential damages arising from or related to your use of, or reliance on, the Tool or any information obtained therein. To the fullest extent permitted by law, you agree to release and hold harmless ASCE from any and all liability of any nature arising out of or resulting from any use of data provided by the ASCE 7 Hazard Tool.

Exhibit E

Mount Analysis

INFINIGY

FROM ZERO TO INFINIGY
the solutions are endless

1033 WATERVLIET SHAKER RD ALBANY, NY 12205

Mount Analysis Report

September 27, 2021

Dish Wireless Site Number	BOBDL00107A
Infinigy Job Number	2039-Z5555C
Client	Crown Castle
Carrier	Dish Wireless
Site Location	82 Lovely Street, Unionville, CT 06085 41.7614 N NAD83 72.8875 W NAD83
Mount Centerline EL.	88 ft
Mount Classification	Platform
Structural Usage Ratio	79%
Overall Result	Pass

Upon reviewing the results of this analysis, it is our opinion that the structure meets the specified TIA and ASCE code requirements. The proposed platform for the proposed carrier is therefore deemed **adequate** to support the final loading configuration as listed in this report.



09-27-21

Dmitriy Albul, P.E.
Engineering Consultant to Infinigy

AZ CA CO FL GA MD NC NH NJ NY TX WA

INFINIGY

Contents

Introduction.....	3
Supporting Documentation.....	3
Analysis Code Requirements.....	3
Conclusion.....	3
Final Configuration Loading.....	4
Structure Usages.....	4
Assumptions and Limitations.....	4
Calculations.....	Appended

Introduction

Infinigy Engineering has been requested to perform a mount analysis of proposed antenna mount from the Dish Wireless equipment. All supporting documents have been obtained from the client and are assumed to be accurate and applicable to this site. The mount was analyzed using RISA-3D Version 19.0 analysis software.

Supporting Documentation

Platform Drawings	Site Pro 1 Assembly Drawings No. SNP8HR-3XX
Construction Drawings	Infinigy Engineering PLLC, Job No. 2039-Z5555C, dated June 8, 2021
RF Design Sheet	Dish Wireless, dated February 19, 2021

Analysis Code Requirements

Wind Speed	125 mph (3-second Gust, Vult.)
Wind Speed w/ ice	50 mph (3-Second Gust) w/ 1" ice
TIA Revision	ANSI/TIA-222-G / 2018 Connecticut State Building Code (2015 IBC)
Structure Class	II
Exposure Category	B
Topographic Method	Method 2
Topographic Category	1
Spectral Response	S _s =0.172, S ₁ =0.064
Site Class	D – Stiff Soil
HMSL	264.28 ft.

Conclusion

Upon reviewing the results of this analysis, it is our opinion that the structure meets the specified TIA code requirements. The proposed platform is therefore deemed adequate to support the final loading configuration as listed in this report.

If you have any questions, require additional information, or actual conditions differ from those as detailed in this report please contact me via the information below:

Dmitriy Albul, P.E.
 Professional Engineer | Engineering Consultant to Infinigy
 1033 Watervliet Shaker Road, Albany, NY 12205
 (O) (518) 690-0790 | (M) (518) 699-4428
www.infinigy.com

September 27, 2021

Final Configuration Loading

Mount CL (ft)	Rad. HT (ft)	Vert. O/S (ft)	Horiz. O/S (ft)*	Qty	Appurtenance	Carrier
88.0	88.0	-	4	3	JMA MX08FRO665-20	Dish Wireless
			4	3	Fujitsu TA08025-B605	
			4	3	Fujitsu TA08025-B604	
			-	1	Raycap RDIDC-9181-PF-48	

*Horizontal Offset is defined as the distance from the left most edge of the mount face horizontal when viewed facing the tower.

Structure Usages


Plates	79%	Pass
Mount Pipes	35%	Pass
Arms	33%	Pass
Cross Arms	29%	Pass
Connections	26%	Pass
Frame Rails	12%	Pass
Handrails	11%	Pass
Rating	79%	Pass

Assumptions and Limitations

Our structural calculations are completed assuming all information provided to Infinigy Engineering is accurate and applicable to this site. For the purposes of calculations, we assume an overall structure condition of “like new” and all members and connections to be free of corrosion and/or structural defects. The structure owner and/or contractor shall verify the structure’s condition prior to installation of any proposed equipment. If actual conditions differ from those described in this report Infinigy Engineering should be notified immediately to complete a revised evaluation.

Our evaluation is completed using standard TIA, AISC, ACI, and ASCE methods and procedures. Our structural results are proprietary and should not be used by others as their own. Infinigy Engineering is not responsible for decisions made by others that are or are not based on our supplied assumptions and conclusions.

This report is an evaluation of the proposed carriers mount structure only and does not reflect adequacy of the existing tower, other mounts, or coax mounting attachments. These elements are assumed to be adequate for the purposes of this analysis and are assumed to have been installed per their manufacturer requirements.



Envelope Only Solution

Infinigy Engineering, PLLC

DVA

2039-Z5555C



BOBDL00107A

Proposed Configuration Model

SK-1


Sep 27, 2021

BOBDL00107A.R3D




Loads: LC 109, 1.2DL + 1.5LM3 + 1.6SWL (30 mph) AZI 300
Envelope Only Solution

Infinigy Engineering, PLLC	BOBDL00107A	SK-2
DVA		Sep 27, 2021
2039-Z5555C	Controlling Load Case	BOBDL00107A.R3D






Code Check (Env)

- No Calc
- > 1.0
- .90-1.0
- .75-.90
- .50-.75
- 0-.50



Member Code Checks Displayed (Enveloped)
Envelope Only Solution

Infinigy Engineering, PLLC	BOBDL00107A	SK-3
DVA		Sep 27, 2021
2039-Z5555C	Member Bending Check	BOBDL00107A.R3D



Member Shear Checks Displayed (Enveloped)
Envelope Only Solution

Infinigy Engineering, PLLC
DVA
2039-Z5555C

BOBDL00107A
Member Shear Check

SK-4
Sep 27, 2021
BOBDL00107A.R3D

Model Settings

Solution Members

Number of Reported Sections	5
Number of Internal Sections	100
Member Area Load Mesh Size (in ²)	144
Consider Shear Deformation	Yes
Consider Torsional Warping	Yes

Wall Panels

Approximate Mesh Size (in)	12
Transfer Forces Between Intersecting Wood Walls	Yes
Increase Wood Wall Nailing Capacity for Wind Loads	Yes
Include P-Delta for Walls	Yes
Optimize Masonry and Wood Walls	Yes
Maximum Number of Iterations	3

Processor Core Utilization

Single	No
Multiple (Optimum)	Yes
Maximum	No

Axis

Vertical Global Axis

Global Axis corresponding to vertical direction	Y
Convert Existing Data	Yes

Default Member Orientation

Default Global Plane for z-axis	XZ
---------------------------------	----

Plate Axis

Plate Local Axis Orientation	Nodal
------------------------------	-------

Codes

Hot Rolled Steel	AISC 14th (360-10): LRFD
Stiffness Adjustment	Yes (Iterative)
Notional Annex	None
Connections	AISC 14th (360-10): LRFD
Cold Formed Steel	AISI S100-12: LRFD
Stiffness Adjustment	Yes (Iterative)
Wood	AWC NDS-12: ASD
Temperature	< 100F
Concrete	ACI 318-11
Masonry	ACI 530-11: Strength
Aluminum	AA ADM1-10: LRFD
Structure Type	Building
Stiffness Adjustment	Yes (Iterative)
Stainless	AISC 14th (360-10): LRFD
Stiffness Adjustment	Yes (Iterative)

Concrete

Column Design

Analysis Methodology	Exact Integration Method
Parame Beta Factor	0.65

Compression Stress Block	Rectangular Stress Block
Analyze using Cracked Sections	Yes
Leave room for horizontal rebar splices (2*d bar spacing)	No

Model Settings (Continued)

List forces which were ignored for design in the Detail Report	Yes
--	-----

Rebar

Column Min Steel	1
Column Max Steel	8
Rebar Material Spec	ASTM A615
Warn if beam-column framing arrangement is not understood	No

Shear Reinforcement

Number of Shear Regions	4
Region 2 & 3 Spacing Increase Increment (in)	4

Seismic

RISA-3D Seismic Load Options

Code	ASCE 7-10
Risk Category	I or II
Drift Cat	Other
Base Elevation (ft)	
Include the weight of the structure in base shear calcs	Yes

Site Parameters

S_r (g)	1
SD_1 (g)	1
SD_s (g)	1
T_L (sec)	5

Structure Characteristics

T Z (sec)	
T X (sec)	
$C_p X$	0.02
$C_p \text{Exp. Z}$	0.75
$C_p \text{Exp. X}$	0.75
R Z	3
R X	3
$\Omega_0 Z$	1
$\Omega_0 X$	1
$C_p Z$	4
$C_p X$	4
ρZ	1
ρX	1

Member Primary Data

	Label	I Node	J Node	Rotate(deg)	Section/Shape	Type	Design List	Material	Design Rule
1	M1	N1	N2		Arm	Beam	Tube	A500 Gr.B Rect	Typical
2	M2	N5	N6		Frame Rail	Beam	Pipe	A53 Gr.B	Typical
3	M3	N7	N8		Handrail	HBrace	Pipe	A53 Gr.B	Typical
4	M4	N10	N11		Mount Pipe	Column	Pipe	A53 Gr.B	Typical
5	M5	N4	N3		Arm 2	Beam	Tube	A500 Gr.B Rect	Typical
6	M6	N15	N35	90	Cross Arm	Beam	Single Angle	A36 Gr.36	Typical
7	M7	N33	N13	90	Cross Arm	Beam	Single Angle	A36 Gr.36	Typical
8	M8	N12	N34	90	Cross Arm	Beam	Single Angle	A36 Gr.36	Typical
9	M9	N36	N14	90	Cross Arm	Beam	Single Angle	A36 Gr.36	Typical
10	M10	N18	N20		Plate	Beam	BAR	A36 Gr.36	Typical
11	M11	N17	N19		Plate	Beam	BAR	A36 Gr.36	Typical
12	M12	N21	N22		Plate	Beam	BAR	A36 Gr.36	Typical
13	M13	N23	N24		Plate	Beam	BAR	A36 Gr.36	Typical
14	M14	N28	N25	90	Angle	HBrace	Single Angle	A36 Gr.36	Typical
15	M15	N26	N27		Plate	Beam	BAR	A36 Gr.36	Typical
16	M16	N29	N30		Plate	Beam	BAR	A36 Gr.36	Typical
17	M17	N31	N9		RIGID	None	None	RIGID	Typical
18	M18	N32	N16		RIGID	None	None	RIGID	Typical
19	M19	N4	N35		RIGID	None	None	RIGID	Typical
20	M20	N4	N33		RIGID	None	None	RIGID	Typical
21	M21	N3	N34		RIGID	None	None	RIGID	Typical
22	M22	N36	N3		RIGID	None	None	RIGID	Typical
23	M23	N19	N37		Plate	Beam	BAR	A36 Gr.36	Typical
24	M24	N22	N38		Plate	Beam	BAR	A36 Gr.36	Typical
25	M25	N39	N41		RIGID	None	None	RIGID	Typical
26	M26	N40	N42		RIGID	None	None	RIGID	Typical
27	M27	N27	N43		Plate	Beam	BAR	A36 Gr.36	Typical
28	M28	N44	N45		RIGID	None	None	RIGID	Typical
29	M29	N20	N46		Plate	Beam	BAR	A36 Gr.36	Typical
30	M30	N24	N47		Plate	Beam	BAR	A36 Gr.36	Typical
31	M31	N48	N50		RIGID	None	None	RIGID	Typical
32	M32	N49	N51		RIGID	None	None	RIGID	Typical
33	M33	N30	N52		Plate	Beam	BAR	A36 Gr.36	Typical
34	M34	N53	N54		RIGID	None	None	RIGID	Typical
35	M35	N56	N57		Mount Pipe	Column	Pipe	A53 Gr.B	Typical
36	M36	N59	N55		RIGID	None	None	RIGID	Typical
37	M37	N60	N58		RIGID	None	None	RIGID	Typical
38	M38	N62	N63		Mount Pipe	Column	Pipe	A53 Gr.B	Typical
39	M39	N65	N61		RIGID	None	None	RIGID	Typical
40	M40	N66	N64		RIGID	None	None	RIGID	Typical
41	M41	N67	N68		Arm	Beam	Tube	A500 Gr.B Rect	Typical
42	M42	N72	N73		Mount Pipe	Column	Pipe	A53 Gr.B	Typical
43	M43	N70	N69		Arm 2	Beam	Tube	A500 Gr.B Rect	Typical
44	M44	N77	N97	90	Cross Arm	Beam	Single Angle	A36 Gr.36	Typical
45	M45	N95	N75	90	Cross Arm	Beam	Single Angle	A36 Gr.36	Typical
46	M46	N74	N96	90	Cross Arm	Beam	Single Angle	A36 Gr.36	Typical
47	M47	N98	N76	90	Cross Arm	Beam	Single Angle	A36 Gr.36	Typical
48	M48	N80	N82		Plate	Beam	BAR	A36 Gr.36	Typical
49	M49	N79	N81		Plate	Beam	BAR	A36 Gr.36	Typical
50	M50	N83	N84		Plate	Beam	BAR	A36 Gr.36	Typical
51	M51	N85	N86		Plate	Beam	BAR	A36 Gr.36	Typical
52	M52	N90	N87	90	Angle	HBrace	Single Angle	A36 Gr.36	Typical
53	M53	N88	N89		Plate	Beam	BAR	A36 Gr.36	Typical
54	M54	N91	N92		Plate	Beam	BAR	A36 Gr.36	Typical
55	M55	N93	N71		RIGID	None	None	RIGID	Typical
56	M56	N94	N78		RIGID	None	None	RIGID	Typical
57	M57	N70	N97		RIGID	None	None	RIGID	Typical
58	M58	N70	N95		RIGID	None	None	RIGID	Typical

Member Primary Data (Continued)

	Label	I Node	J Node	Rotate(deg)	Section/Shape	Type	Design List	Material	Design Rule
59	M59	N69	N96		RIGID	None	None	RIGID	Typical
60	M60	N98	N69		RIGID	None	None	RIGID	Typical
61	M61	N81	N99		Plate	Beam	BAR	A36 Gr.36	Typical
62	M62	N84	N100		Plate	Beam	BAR	A36 Gr.36	Typical
63	M63	N101	N103		RIGID	None	None	RIGID	Typical
64	M64	N102	N104		RIGID	None	None	RIGID	Typical
65	M65	N89	N105		Plate	Beam	BAR	A36 Gr.36	Typical
66	M66	N106	N107		RIGID	None	None	RIGID	Typical
67	M67	N82	N108		Plate	Beam	BAR	A36 Gr.36	Typical
68	M68	N86	N109		Plate	Beam	BAR	A36 Gr.36	Typical
69	M69	N110	N112		RIGID	None	None	RIGID	Typical
70	M70	N111	N113		RIGID	None	None	RIGID	Typical
71	M71	N92	N114		Plate	Beam	BAR	A36 Gr.36	Typical
72	M72	N115	N116		RIGID	None	None	RIGID	Typical
73	M73	N117	N118		Arm	Beam	Tube	A500 Gr.B Rect	Typical
74	M74	N122	N123		Mount Pipe	Column	Pipe	A53 Gr.B	Typical
75	M75	N120	N119		Arm 2	Beam	Tube	A500 Gr.B Rect	Typical
76	M76	N127	N147	90	Cross Arm	Beam	Single Angle	A36 Gr.36	Typical
77	M77	N145	N125	90	Cross Arm	Beam	Single Angle	A36 Gr.36	Typical
78	M78	N124	N146	90	Cross Arm	Beam	Single Angle	A36 Gr.36	Typical
79	M79	N148	N126	90	Cross Arm	Beam	Single Angle	A36 Gr.36	Typical
80	M80	N130	N132		Plate	Beam	BAR	A36 Gr.36	Typical
81	M81	N129	N131		Plate	Beam	BAR	A36 Gr.36	Typical
82	M82	N133	N134		Plate	Beam	BAR	A36 Gr.36	Typical
83	M83	N135	N136		Plate	Beam	BAR	A36 Gr.36	Typical
84	M84	N140	N137	90	Angle	HBrace	Single Angle	A36 Gr.36	Typical
85	M85	N138	N139		Plate	Beam	BAR	A36 Gr.36	Typical
86	M86	N141	N142		Plate	Beam	BAR	A36 Gr.36	Typical
87	M87	N143	N121		RIGID	None	None	RIGID	Typical
88	M88	N144	N128		RIGID	None	None	RIGID	Typical
89	M89	N120	N147		RIGID	None	None	RIGID	Typical
90	M90	N120	N145		RIGID	None	None	RIGID	Typical
91	M91	N119	N146		RIGID	None	None	RIGID	Typical
92	M92	N148	N119		RIGID	None	None	RIGID	Typical
93	M93	N131	N149		Plate	Beam	BAR	A36 Gr.36	Typical
94	M94	N134	N150		Plate	Beam	BAR	A36 Gr.36	Typical
95	M95	N151	N153		RIGID	None	None	RIGID	Typical
96	M96	N152	N154		RIGID	None	None	RIGID	Typical
97	M97	N139	N155		Plate	Beam	BAR	A36 Gr.36	Typical
98	M98	N156	N157		RIGID	None	None	RIGID	Typical
99	M99	N132	N158		Plate	Beam	BAR	A36 Gr.36	Typical
100	M100	N136	N159		Plate	Beam	BAR	A36 Gr.36	Typical
101	M101	N160	N162		RIGID	None	None	RIGID	Typical
102	M102	N161	N163		RIGID	None	None	RIGID	Typical
103	M103	N142	N164		Plate	Beam	BAR	A36 Gr.36	Typical
104	M104	N165	N166		RIGID	None	None	RIGID	Typical
105	M105	N167	N168		Frame Rail	Beam	Pipe	A53 Gr.B	Typical
106	M106	N169	N170		Handrail	HBrace	Pipe	A53 Gr.B	Typical
107	M107	N172	N173		Mount Pipe	Column	Pipe	A53 Gr.B	Typical
108	M108	N175	N171		RIGID	None	None	RIGID	Typical
109	M109	N176	N174		RIGID	None	None	RIGID	Typical
110	M110	N178	N179		Mount Pipe	Column	Pipe	A53 Gr.B	Typical
111	M111	N181	N177		RIGID	None	None	RIGID	Typical
112	M112	N182	N180		RIGID	None	None	RIGID	Typical
113	M113	N183	N184		Frame Rail	Beam	Pipe	A53 Gr.B	Typical
114	M114	N185	N186		Handrail	HBrace	Pipe	A53 Gr.B	Typical
115	M115	N188	N189		Mount Pipe	Column	Pipe	A53 Gr.B	Typical
116	M116	N191	N187		RIGID	None	None	RIGID	Typical

Member Primary Data (Continued)

	Label	I Node	J Node	Rotate(deg)	Section/Shape	Type	Design List	Material	Design Rule
117	M117	N192	N190		RIGID	None	None	RIGID	Typical
118	M118	N194	N195		Mount Pipe	Column	Pipe	A53 Gr.B	Typical
119	M119	N197	N193		RIGID	None	None	RIGID	Typical
120	M120	N198	N196		RIGID	None	None	RIGID	Typical
121	M121	N199	N200		RIGID	None	None	RIGID	Typical
122	M122	N201	N199		RIGID	None	None	RIGID	Typical
123	M123	N200	N202		RIGID	None	None	RIGID	Typical
124	M124	N201	N203		RIGID	None	None	RIGID	Typical
125	M125	N204	N205		Mount Pipe	Column	Pipe	A53 Gr.B	Typical

Material Take-Off

	Material	Size	Pieces	Length[in]	Weight[LB]
1	General Members				
2	RIGID		52	123.7	0
3	Total General		52	123.7	0
4					
5	Hot Rolled Steel				
6	A36 Gr.36	6"x0.375" Plate	36	144	91.875
7	A36 Gr.36	L4X4X4	12	363	198.663
8	A36 Gr.36	L2.5x2.5x3	3	165	42.156
9	A500 Gr.B Rect	HSS4.5X4.5X3	3	60	53.615
10	A500 Gr.B Rect	HSS4X4X4	3	115.4	118.563
11	A53 Gr.B	PIPE 2.0	10	912	263.783
12	A53 Gr.B	PIPE 2.5	3	288	131.483
13	A53 Gr.B	PIPE 3.0	3	288	169.05
14	Total HR Steel		73	2335.4	1069.189

Basic Load Cases

	BLC Description	Category	X Gravity	Y Gravity	Z Gravity	Point	Distributed	Area(Member)
1	Self Weight	DL		-1		20		3
2	Wind Load AZI 0	WLX				40	258	
3	Wind Load AZI 30	None				40	258	
4	Wind Load AZI 60	None				40	258	
5	Wind Load AZI 90	WLZ				40	258	
6	Wind Load AZI 120	None				40	258	
7	Wind Load AZI 150	None				40	258	
8	Wind Load AZI 180	None				40	258	
9	Wind Load AZI 210	None				40	258	
10	Wind Load AZI 240	None				40	258	
11	Wind Load AZI 270	None				40	258	
12	Wind Load AZI 300	None				40	258	
13	Wind Load AZI 330	None				40	258	
14	Ice Weight	OL1				20	125	3
15	Ice Wind Load AZI 0	OL2				40	258	
16	Ice Wind Load AZI 30	None				40	258	
17	Ice Wind Load AZI 60	None				40	258	
18	Ice Wind Load AZI 90	OL3				40	258	
19	Ice Wind Load AZI 120	None				40	258	
20	Ice Wind Load AZI 150	None				40	258	
21	Ice Wind Load AZI 180	None				40	258	
22	Ice Wind Load AZI 210	None				40	258	
23	Ice Wind Load AZI 240	None				40	258	
24	Ice Wind Load AZI 270	None				40	258	
25	Ice Wind Load AZI 300	None				40	258	
26	Ice Wind Load AZI 330	None				40	258	
27	Seismic Load X	ELX			-0.097	20		
28	Seismic Load Z	ELZ	-0.097			20		

Basic Load Cases (Continued)

	BLC Description	Category	X Gravity	Y Gravity	Z Gravity	Point	Distributed	Area(Member)
29	Service Live Loads	LL						
30	Maintenance Load 1	LL				1		
31	Maintenance Load 2	LL				1		
32	Maintenance Load 3	LL				1		
33	Maintenance Load 4	LL				1		
34	Maintenance Load 5	LL				1		
35	Maintenance Load 6	LL				1		
36	Maintenance Load 7	LL				1		
37	Maintenance Load 8	LL				1		
38	Maintenance Load 9	LL				1		
39	Maintenance Load 10	LL				1		
40	Maintenance Load 11	LL				1		
41	Maintenance Load 12	LL				1		
42	Maintenance Load 13	LL				1		
43	Maintenance Load 14	LL				1		
44	Maintenance Load 15	LL				1		
45	Maintenance Load 16	LL				1		
46	Maintenance Load 17	LL				1		
47	Maintenance Load 18	LL				1		
52	BLC 1 Transient Area Loads	None					141	
53	BLC 14 Transient Area Loads	None					141	

Load Combinations

	Description	Solve	PDelta	BLC	Factor	BLC	Factor	BLC	Factor
1	1.4DL	Yes	Y	1	1.4				
2	1.2DL + 1.6WL AZI 0	Yes	Y	1	1.2	2	1.6		
3	1.2DL + 1.6WL AZI 30	Yes	Y	1	1.2	3	1.6		
4	1.2DL + 1.6WL AZI 60	Yes	Y	1	1.2	4	1.6		
5	1.2DL + 1.6WL AZI 90	Yes	Y	1	1.2	5	1.6		
6	1.2DL + 1.6WL AZI 120	Yes	Y	1	1.2	6	1.6		
7	1.2DL + 1.6WL AZI 150	Yes	Y	1	1.2	7	1.6		
8	1.2DL + 1.6WL AZI 180	Yes	Y	1	1.2	8	1.6		
9	1.2DL + 1.6WL AZI 210	Yes	Y	1	1.2	9	1.6		
10	1.2DL + 1.6WL AZI 240	Yes	Y	1	1.2	10	1.6		
11	1.2DL + 1.6WL AZI 270	Yes	Y	1	1.2	11	1.6		
12	1.2DL + 1.6WL AZI 300	Yes	Y	1	1.2	12	1.6		
13	1.2DL + 1.6WL AZI 330	Yes	Y	1	1.2	13	1.6		
14	0.9DL + 1.6WL AZI 0	Yes	Y	1	0.9	2	1.6		
15	0.9DL + 1.6WL AZI 30	Yes	Y	1	0.9	3	1.6		
16	0.9DL + 1.6WL AZI 60	Yes	Y	1	0.9	4	1.6		
17	0.9DL + 1.6WL AZI 90	Yes	Y	1	0.9	5	1.6		
18	0.9DL + 1.6WL AZI 120	Yes	Y	1	0.9	6	1.6		
19	0.9DL + 1.6WL AZI 150	Yes	Y	1	0.9	7	1.6		
20	0.9DL + 1.6WL AZI 180	Yes	Y	1	0.9	8	1.6		
21	0.9DL + 1.6WL AZI 210	Yes	Y	1	0.9	9	1.6		
22	0.9DL + 1.6WL AZI 240	Yes	Y	1	0.9	10	1.6		
23	0.9DL + 1.6WL AZI 270	Yes	Y	1	0.9	11	1.6		
24	0.9DL + 1.6WL AZI 300	Yes	Y	1	0.9	12	1.6		
25	0.9DL + 1.6WL AZI 330	Yes	Y	1	0.9	13	1.6		
26	1.2D + 1.0Di	Yes	Y	1	1.2	14	1		
27	1.2D + 1.0Di + 1.0Wi AZI 0	Yes	Y	1	1.2	14	1	15	1
28	1.2D + 1.0Di + 1.0Wi AZI 30	Yes	Y	1	1.2	14	1	16	1
29	1.2D + 1.0Di + 1.0Wi AZI 60	Yes	Y	1	1.2	14	1	17	1
30	1.2D + 1.0Di + 1.0Wi AZI 90	Yes	Y	1	1.2	14	1	18	1
31	1.2D + 1.0Di + 1.0Wi AZI 120	Yes	Y	1	1.2	14	1	19	1
32	1.2D + 1.0Di + 1.0Wi AZI 150	Yes	Y	1	1.2	14	1	20	1
33	1.2D + 1.0Di + 1.0Wi AZI 180	Yes	Y	1	1.2	14	1	21	1
34	1.2D + 1.0Di + 1.0Wi AZI 210	Yes	Y	1	1.2	14	1	22	1

Load Combinations (Continued)

	Description	Solve	PDelta	BLC	Factor	BLC	Factor	BLC	Factor
35	1.2D + 1.0Di + 1.0Wi AZI 240	Yes	Y	1	1.2	14	1	23	1
36	1.2D + 1.0Di + 1.0Wi AZI 270	Yes	Y	1	1.2	14	1	24	1
37	1.2D + 1.0Di + 1.0Wi AZI 300	Yes	Y	1	1.2	14	1	25	1
38	1.2D + 1.0Di + 1.0Wi AZI 330	Yes	Y	1	1.2	14	1	26	1
39	(1.2 + 0.2Sds)DL + 1.0E AZI 0	Yes	Y	1	1.239	27	1	28	
40	(1.2 + 0.2Sds)DL + 1.0E AZI 30	Yes	Y	1	1.239	27	0.866	28	0.5
41	(1.2 + 0.2Sds)DL + 1.0E AZI 60	Yes	Y	1	1.239	27	0.5	28	0.866
42	(1.2 + 0.2Sds)DL + 1.0E AZI 90	Yes	Y	1	1.239	27		28	1
43	(1.2 + 0.2Sds)DL + 1.0E AZI 120	Yes	Y	1	1.239	27	-0.5	28	0.866
44	(1.2 + 0.2Sds)DL + 1.0E AZI 150	Yes	Y	1	1.239	27	-0.866	28	0.5
45	(1.2 + 0.2Sds)DL + 1.0E AZI 180	Yes	Y	1	1.239	27	-1	28	
46	(1.2 + 0.2Sds)DL + 1.0E AZI 210	Yes	Y	1	1.239	27	-0.866	28	-0.5
47	(1.2 + 0.2Sds)DL + 1.0E AZI 240	Yes	Y	1	1.239	27	-0.5	28	-0.866
48	(1.2 + 0.2Sds)DL + 1.0E AZI 270	Yes	Y	1	1.239	27		28	-1
49	(1.2 + 0.2Sds)DL + 1.0E AZI 300	Yes	Y	1	1.239	27	0.5	28	-0.866
50	(1.2 + 0.2Sds)DL + 1.0E AZI 330	Yes	Y	1	1.239	27	0.866	28	-0.5
51	(0.9 - 0.2Sds)DL + 1.0E AZI 0	Yes	Y	1	0.861	27	1	28	
52	(0.9 - 0.2Sds)DL + 1.0E AZI 30	Yes	Y	1	0.861	27	0.866	28	0.5
53	(0.9 - 0.2Sds)DL + 1.0E AZI 60	Yes	Y	1	0.861	27	0.5	28	0.866
54	(0.9 - 0.2Sds)DL + 1.0E AZI 90	Yes	Y	1	0.861	27		28	1
55	(0.9 - 0.2Sds)DL + 1.0E AZI 120	Yes	Y	1	0.861	27	-0.5	28	0.866
56	(0.9 - 0.2Sds)DL + 1.0E AZI 150	Yes	Y	1	0.861	27	-0.866	28	0.5
57	(0.9 - 0.2Sds)DL + 1.0E AZI 180	Yes	Y	1	0.861	27	-1	28	
58	(0.9 - 0.2Sds)DL + 1.0E AZI 210	Yes	Y	1	0.861	27	-0.866	28	-0.5
59	(0.9 - 0.2Sds)DL + 1.0E AZI 240	Yes	Y	1	0.861	27	-0.5	28	-0.866
60	(0.9 - 0.2Sds)DL + 1.0E AZI 270	Yes	Y	1	0.861	27		28	-1
61	(0.9 - 0.2Sds)DL + 1.0E AZI 300	Yes	Y	1	0.861	27	0.5	28	-0.866
62	(0.9 - 0.2Sds)DL + 1.0E AZI 330	Yes	Y	1	0.861	27	0.866	28	-0.5
63	1.0DL + 1.5LL + 1.0SWL (30 mph) AZI 0	Yes	Y	1	1	2	0.096	29	1.5
64	1.0DL + 1.5LL + 1.0SWL (30 mph) AZI 30	Yes	Y	1	1	3	0.096	29	1.5
65	1.0DL + 1.5LL + 1.0SWL (30 mph) AZI 60	Yes	Y	1	1	4	0.096	29	1.5
66	1.0DL + 1.5LL + 1.0SWL (30 mph) AZI 90	Yes	Y	1	1	5	0.096	29	1.5
67	1.0DL + 1.5LL + 1.0SWL (30 mph) AZI 120	Yes	Y	1	1	6	0.096	29	1.5
68	1.0DL + 1.5LL + 1.0SWL (30 mph) AZI 150	Yes	Y	1	1	7	0.096	29	1.5
69	1.0DL + 1.5LL + 1.0SWL (30 mph) AZI 180	Yes	Y	1	1	8	0.096	29	1.5
70	1.0DL + 1.5LL + 1.0SWL (30 mph) AZI 210	Yes	Y	1	1	9	0.096	29	1.5
71	1.0DL + 1.5LL + 1.0SWL (30 mph) AZI 240	Yes	Y	1	1	10	0.096	29	1.5
72	1.0DL + 1.5LL + 1.0SWL (30 mph) AZI 270	Yes	Y	1	1	11	0.096	29	1.5
73	1.0DL + 1.5LL + 1.0SWL (30 mph) AZI 300	Yes	Y	1	1	12	0.096	29	1.5
74	1.0DL + 1.5LL + 1.0SWL (30 mph) AZI 330	Yes	Y	1	1	13	0.096	29	1.5
75	1.2DL + 1.5LM1 + 1.6SWL (30 mph) AZI 0	Yes	Y	1	1.2	34	1.5	2	0.154
76	1.2DL + 1.5LM1 + 1.6SWL (30 mph) AZI 30	Yes	Y	1	1.2	34	1.5	3	0.154
77	1.2DL + 1.5LM1 + 1.6SWL (30 mph) AZI 60	Yes	Y	1	1.2	34	1.5	4	0.154
78	1.2DL + 1.5LM1 + 1.6SWL (30 mph) AZI 90	Yes	Y	1	1.2	34	1.5	5	0.154
79	1.2DL + 1.5LM1 + 1.6SWL (30 mph) AZI 120	Yes	Y	1	1.2	34	1.5	6	0.154
80	1.2DL + 1.5LM1 + 1.6SWL (30 mph) AZI 150	Yes	Y	1	1.2	34	1.5	7	0.154
81	1.2DL + 1.5LM1 + 1.6SWL (30 mph) AZI 180	Yes	Y	1	1.2	34	1.5	8	0.154
82	1.2DL + 1.5LM1 + 1.6SWL (30 mph) AZI 210	Yes	Y	1	1.2	34	1.5	9	0.154
83	1.2DL + 1.5LM1 + 1.6SWL (30 mph) AZI 240	Yes	Y	1	1.2	34	1.5	10	0.154
84	1.2DL + 1.5LM1 + 1.6SWL (30 mph) AZI 270	Yes	Y	1	1.2	34	1.5	11	0.154
85	1.2DL + 1.5LM1 + 1.6SWL (30 mph) AZI 300	Yes	Y	1	1.2	34	1.5	12	0.154
86	1.2DL + 1.5LM1 + 1.6SWL (30 mph) AZI 330	Yes	Y	1	1.2	34	1.5	13	0.154
87	1.2DL + 1.5LM2 + 1.6SWL (30 mph) AZI 0	Yes	Y	1	1.2	35	1.5	2	0.154
88	1.2DL + 1.5LM2 + 1.6SWL (30 mph) AZI 30	Yes	Y	1	1.2	35	1.5	3	0.154
89	1.2DL + 1.5LM2 + 1.6SWL (30 mph) AZI 60	Yes	Y	1	1.2	35	1.5	4	0.154
90	1.2DL + 1.5LM2 + 1.6SWL (30 mph) AZI 90	Yes	Y	1	1.2	35	1.5	5	0.154
91	1.2DL + 1.5LM2 + 1.6SWL (30 mph) AZI 120	Yes	Y	1	1.2	35	1.5	6	0.154
92	1.2DL + 1.5LM2 + 1.6SWL (30 mph) AZI 150	Yes	Y	1	1.2	35	1.5	7	0.154

Load Combinations (Continued)

	Description	Solve	PDelta	BLC	Factor	BLC	Factor	BLC	Factor
93	1.2DL + 1.5LM2 + 1.6SWL (30 mph) AZI 180	Yes	Y	1	1.2	35	1.5	8	0.154
94	1.2DL + 1.5LM2 + 1.6SWL (30 mph) AZI 210	Yes	Y	1	1.2	35	1.5	9	0.154
95	1.2DL + 1.5LM2 + 1.6SWL (30 mph) AZI 240	Yes	Y	1	1.2	35	1.5	10	0.154
96	1.2DL + 1.5LM2 + 1.6SWL (30 mph) AZI 270	Yes	Y	1	1.2	35	1.5	11	0.154
97	1.2DL + 1.5LM2 + 1.6SWL (30 mph) AZI 300	Yes	Y	1	1.2	35	1.5	12	0.154
98	1.2DL + 1.5LM2 + 1.6SWL (30 mph) AZI 330	Yes	Y	1	1.2	35	1.5	13	0.154
99	1.2DL + 1.5LM3 + 1.6SWL (30 mph) AZI 0	Yes	Y	1	1.2	36	1.5	2	0.154
100	1.2DL + 1.5LM3 + 1.6SWL (30 mph) AZI 30	Yes	Y	1	1.2	36	1.5	3	0.154
101	1.2DL + 1.5LM3 + 1.6SWL (30 mph) AZI 60	Yes	Y	1	1.2	36	1.5	4	0.154
102	1.2DL + 1.5LM3 + 1.6SWL (30 mph) AZI 90	Yes	Y	1	1.2	36	1.5	5	0.154
103	1.2DL + 1.5LM3 + 1.6SWL (30 mph) AZI 120	Yes	Y	1	1.2	36	1.5	6	0.154
104	1.2DL + 1.5LM3 + 1.6SWL (30 mph) AZI 150	Yes	Y	1	1.2	36	1.5	7	0.154
105	1.2DL + 1.5LM3 + 1.6SWL (30 mph) AZI 180	Yes	Y	1	1.2	36	1.5	8	0.154
106	1.2DL + 1.5LM3 + 1.6SWL (30 mph) AZI 210	Yes	Y	1	1.2	36	1.5	9	0.154
107	1.2DL + 1.5LM3 + 1.6SWL (30 mph) AZI 240	Yes	Y	1	1.2	36	1.5	10	0.154
108	1.2DL + 1.5LM3 + 1.6SWL (30 mph) AZI 270	Yes	Y	1	1.2	36	1.5	11	0.154
109	1.2DL + 1.5LM3 + 1.6SWL (30 mph) AZI 300	Yes	Y	1	1.2	36	1.5	12	0.154
110	1.2DL + 1.5LM3 + 1.6SWL (30 mph) AZI 330	Yes	Y	1	1.2	36	1.5	13	0.154
111	1.2DL + 1.5LM4 + 1.6SWL (30 mph) AZI 0	Yes	Y	1	1.2	37	1.5	2	0.154
112	1.2DL + 1.5LM4 + 1.6SWL (30 mph) AZI 30	Yes	Y	1	1.2	37	1.5	3	0.154
113	1.2DL + 1.5LM4 + 1.6SWL (30 mph) AZI 60	Yes	Y	1	1.2	37	1.5	4	0.154
114	1.2DL + 1.5LM4 + 1.6SWL (30 mph) AZI 90	Yes	Y	1	1.2	37	1.5	5	0.154
115	1.2DL + 1.5LM4 + 1.6SWL (30 mph) AZI 120	Yes	Y	1	1.2	37	1.5	6	0.154
116	1.2DL + 1.5LM4 + 1.6SWL (30 mph) AZI 150	Yes	Y	1	1.2	37	1.5	7	0.154
117	1.2DL + 1.5LM4 + 1.6SWL (30 mph) AZI 180	Yes	Y	1	1.2	37	1.5	8	0.154
118	1.2DL + 1.5LM4 + 1.6SWL (30 mph) AZI 210	Yes	Y	1	1.2	37	1.5	9	0.154
119	1.2DL + 1.5LM4 + 1.6SWL (30 mph) AZI 240	Yes	Y	1	1.2	37	1.5	10	0.154
120	1.2DL + 1.5LM4 + 1.6SWL (30 mph) AZI 270	Yes	Y	1	1.2	37	1.5	11	0.154
121	1.2DL + 1.5LM4 + 1.6SWL (30 mph) AZI 300	Yes	Y	1	1.2	37	1.5	12	0.154
122	1.2DL + 1.5LM4 + 1.6SWL (30 mph) AZI 330	Yes	Y	1	1.2	37	1.5	13	0.154
123	1.2DL + 1.5LM5 + 1.6SWL (30 mph) AZI 0	Yes	Y	1	1.2	38	1.5	2	0.154
124	1.2DL + 1.5LM5 + 1.6SWL (30 mph) AZI 30	Yes	Y	1	1.2	38	1.5	3	0.154
125	1.2DL + 1.5LM5 + 1.6SWL (30 mph) AZI 60	Yes	Y	1	1.2	38	1.5	4	0.154
126	1.2DL + 1.5LM5 + 1.6SWL (30 mph) AZI 90	Yes	Y	1	1.2	38	1.5	5	0.154
127	1.2DL + 1.5LM5 + 1.6SWL (30 mph) AZI 120	Yes	Y	1	1.2	38	1.5	6	0.154
128	1.2DL + 1.5LM5 + 1.6SWL (30 mph) AZI 150	Yes	Y	1	1.2	38	1.5	7	0.154
129	1.2DL + 1.5LM5 + 1.6SWL (30 mph) AZI 180	Yes	Y	1	1.2	38	1.5	8	0.154
130	1.2DL + 1.5LM5 + 1.6SWL (30 mph) AZI 210	Yes	Y	1	1.2	38	1.5	9	0.154
131	1.2DL + 1.5LM5 + 1.6SWL (30 mph) AZI 240	Yes	Y	1	1.2	38	1.5	10	0.154
132	1.2DL + 1.5LM5 + 1.6SWL (30 mph) AZI 270	Yes	Y	1	1.2	38	1.5	11	0.154
133	1.2DL + 1.5LM5 + 1.6SWL (30 mph) AZI 300	Yes	Y	1	1.2	38	1.5	12	0.154
134	1.2DL + 1.5LM5 + 1.6SWL (30 mph) AZI 330	Yes	Y	1	1.2	38	1.5	13	0.154
135	1.2DL + 1.5LM6 + 1.6SWL (30 mph) AZI 0	Yes	Y	1	1.2	39	1.5	2	0.154
136	1.2DL + 1.5LM6 + 1.6SWL (30 mph) AZI 30	Yes	Y	1	1.2	39	1.5	3	0.154
137	1.2DL + 1.5LM6 + 1.6SWL (30 mph) AZI 60	Yes	Y	1	1.2	39	1.5	4	0.154
138	1.2DL + 1.5LM6 + 1.6SWL (30 mph) AZI 90	Yes	Y	1	1.2	39	1.5	5	0.154
139	1.2DL + 1.5LM6 + 1.6SWL (30 mph) AZI 120	Yes	Y	1	1.2	39	1.5	6	0.154
140	1.2DL + 1.5LM6 + 1.6SWL (30 mph) AZI 150	Yes	Y	1	1.2	39	1.5	7	0.154
141	1.2DL + 1.5LM6 + 1.6SWL (30 mph) AZI 180	Yes	Y	1	1.2	39	1.5	8	0.154
142	1.2DL + 1.5LM6 + 1.6SWL (30 mph) AZI 210	Yes	Y	1	1.2	39	1.5	9	0.154
143	1.2DL + 1.5LM6 + 1.6SWL (30 mph) AZI 240	Yes	Y	1	1.2	39	1.5	10	0.154
144	1.2DL + 1.5LM6 + 1.6SWL (30 mph) AZI 270	Yes	Y	1	1.2	39	1.5	11	0.154
145	1.2DL + 1.5LM6 + 1.6SWL (30 mph) AZI 300	Yes	Y	1	1.2	39	1.5	12	0.154
146	1.2DL + 1.5LM6 + 1.6SWL (30 mph) AZI 330	Yes	Y	1	1.2	39	1.5	13	0.154
147	1.2DL + 1.5LM7 + 1.6SWL (30 mph) AZI 0	Yes	Y	1	1.2	40	1.5	2	0.154
148	1.2DL + 1.5LM7 + 1.6SWL (30 mph) AZI 30	Yes	Y	1	1.2	40	1.5	3	0.154
149	1.2DL + 1.5LM7 + 1.6SWL (30 mph) AZI 60	Yes	Y	1	1.2	40	1.5	4	0.154
150	1.2DL + 1.5LM7 + 1.6SWL (30 mph) AZI 90	Yes	Y	1	1.2	40	1.5	5	0.154

Load Combinations (Continued)

	Description	Solve	PDelta	BLC	Factor	BLC	Factor	BLC	Factor
151	1.2DL + 1.5LM7 + 1.6SWL (30 mph) AZI 120	Yes	Y	1	1.2	40	1.5	6	0.154
152	1.2DL + 1.5LM7 + 1.6SWL (30 mph) AZI 150	Yes	Y	1	1.2	40	1.5	7	0.154
153	1.2DL + 1.5LM7 + 1.6SWL (30 mph) AZI 180	Yes	Y	1	1.2	40	1.5	8	0.154
154	1.2DL + 1.5LM7 + 1.6SWL (30 mph) AZI 210	Yes	Y	1	1.2	40	1.5	9	0.154
155	1.2DL + 1.5LM7 + 1.6SWL (30 mph) AZI 240	Yes	Y	1	1.2	40	1.5	10	0.154
156	1.2DL + 1.5LM7 + 1.6SWL (30 mph) AZI 270	Yes	Y	1	1.2	40	1.5	11	0.154
157	1.2DL + 1.5LM7 + 1.6SWL (30 mph) AZI 300	Yes	Y	1	1.2	40	1.5	12	0.154
158	1.2DL + 1.5LM7 + 1.6SWL (30 mph) AZI 330	Yes	Y	1	1.2	40	1.5	13	0.154
159	1.2DL + 1.5LM8 + 1.6SWL (30 mph) AZI 0	Yes	Y	1	1.2	41	1.5	2	0.154
160	1.2DL + 1.5LM8 + 1.6SWL (30 mph) AZI 30	Yes	Y	1	1.2	41	1.5	3	0.154
161	1.2DL + 1.5LM8 + 1.6SWL (30 mph) AZI 60	Yes	Y	1	1.2	41	1.5	4	0.154
162	1.2DL + 1.5LM8 + 1.6SWL (30 mph) AZI 90	Yes	Y	1	1.2	41	1.5	5	0.154
163	1.2DL + 1.5LM8 + 1.6SWL (30 mph) AZI 120	Yes	Y	1	1.2	41	1.5	6	0.154
164	1.2DL + 1.5LM8 + 1.6SWL (30 mph) AZI 150	Yes	Y	1	1.2	41	1.5	7	0.154
165	1.2DL + 1.5LM8 + 1.6SWL (30 mph) AZI 180	Yes	Y	1	1.2	41	1.5	8	0.154
166	1.2DL + 1.5LM8 + 1.6SWL (30 mph) AZI 210	Yes	Y	1	1.2	41	1.5	9	0.154
167	1.2DL + 1.5LM8 + 1.6SWL (30 mph) AZI 240	Yes	Y	1	1.2	41	1.5	10	0.154
168	1.2DL + 1.5LM8 + 1.6SWL (30 mph) AZI 270	Yes	Y	1	1.2	41	1.5	11	0.154
169	1.2DL + 1.5LM8 + 1.6SWL (30 mph) AZI 300	Yes	Y	1	1.2	41	1.5	12	0.154
170	1.2DL + 1.5LM8 + 1.6SWL (30 mph) AZI 330	Yes	Y	1	1.2	41	1.5	13	0.154
171	1.2DL + 1.5LM9 + 1.6SWL (30 mph) AZI 0	Yes	Y	1	1.2	42	1.5	2	0.154
172	1.2DL + 1.5LM9 + 1.6SWL (30 mph) AZI 30	Yes	Y	1	1.2	42	1.5	3	0.154
173	1.2DL + 1.5LM9 + 1.6SWL (30 mph) AZI 60	Yes	Y	1	1.2	42	1.5	4	0.154
174	1.2DL + 1.5LM9 + 1.6SWL (30 mph) AZI 90	Yes	Y	1	1.2	42	1.5	5	0.154
175	1.2DL + 1.5LM9 + 1.6SWL (30 mph) AZI 120	Yes	Y	1	1.2	42	1.5	6	0.154
176	1.2DL + 1.5LM9 + 1.6SWL (30 mph) AZI 150	Yes	Y	1	1.2	42	1.5	7	0.154
177	1.2DL + 1.5LM9 + 1.6SWL (30 mph) AZI 180	Yes	Y	1	1.2	42	1.5	8	0.154
178	1.2DL + 1.5LM9 + 1.6SWL (30 mph) AZI 210	Yes	Y	1	1.2	42	1.5	9	0.154
179	1.2DL + 1.5LM9 + 1.6SWL (30 mph) AZI 240	Yes	Y	1	1.2	42	1.5	10	0.154
180	1.2DL + 1.5LM9 + 1.6SWL (30 mph) AZI 270	Yes	Y	1	1.2	42	1.5	11	0.154
181	1.2DL + 1.5LM9 + 1.6SWL (30 mph) AZI 300	Yes	Y	1	1.2	42	1.5	12	0.154
182	1.2DL + 1.5LM9 + 1.6SWL (30 mph) AZI 330	Yes	Y	1	1.2	42	1.5	13	0.154
183	1.2DL + 1.5LM10 + 1.6SWL (30 mph) AZI 0	Yes	Y	1	1.2	43	1.5	2	0.154
184	1.2DL + 1.5LM10 + 1.6SWL (30 mph) AZI 30	Yes	Y	1	1.2	43	1.5	3	0.154
185	1.2DL + 1.5LM10 + 1.6SWL (30 mph) AZI 60	Yes	Y	1	1.2	43	1.5	4	0.154
186	1.2DL + 1.5LM10 + 1.6SWL (30 mph) AZI 90	Yes	Y	1	1.2	43	1.5	5	0.154
187	1.2DL + 1.5LM10 + 1.6SWL (30 mph) AZI 120	Yes	Y	1	1.2	43	1.5	6	0.154
188	1.2DL + 1.5LM10 + 1.6SWL (30 mph) AZI 150	Yes	Y	1	1.2	43	1.5	7	0.154
189	1.2DL + 1.5LM10 + 1.6SWL (30 mph) AZI 180	Yes	Y	1	1.2	43	1.5	8	0.154
190	1.2DL + 1.5LM10 + 1.6SWL (30 mph) AZI 210	Yes	Y	1	1.2	43	1.5	9	0.154
191	1.2DL + 1.5LM10 + 1.6SWL (30 mph) AZI 240	Yes	Y	1	1.2	43	1.5	10	0.154
192	1.2DL + 1.5LM10 + 1.6SWL (30 mph) AZI 270	Yes	Y	1	1.2	43	1.5	11	0.154
193	1.2DL + 1.5LM10 + 1.6SWL (30 mph) AZI 300	Yes	Y	1	1.2	43	1.5	12	0.154
194	1.2DL + 1.5LM10 + 1.6SWL (30 mph) AZI 330	Yes	Y	1	1.2	43	1.5	13	0.154
195	1.2DL + 1.5LM11 + 1.6SWL (30 mph) AZI 0	Yes	Y	1	1.2	44	1.5	2	0.154
196	1.2DL + 1.5LM11 + 1.6SWL (30 mph) AZI 30	Yes	Y	1	1.2	44	1.5	3	0.154
197	1.2DL + 1.5LM11 + 1.6SWL (30 mph) AZI 60	Yes	Y	1	1.2	44	1.5	4	0.154
198	1.2DL + 1.5LM11 + 1.6SWL (30 mph) AZI 90	Yes	Y	1	1.2	44	1.5	5	0.154
199	1.2DL + 1.5LM11 + 1.6SWL (30 mph) AZI 120	Yes	Y	1	1.2	44	1.5	6	0.154
200	1.2DL + 1.5LM11 + 1.6SWL (30 mph) AZI 150	Yes	Y	1	1.2	44	1.5	7	0.154
201	1.2DL + 1.5LM11 + 1.6SWL (30 mph) AZI 180	Yes	Y	1	1.2	44	1.5	8	0.154
202	1.2DL + 1.5LM11 + 1.6SWL (30 mph) AZI 210	Yes	Y	1	1.2	44	1.5	9	0.154
203	1.2DL + 1.5LM11 + 1.6SWL (30 mph) AZI 240	Yes	Y	1	1.2	44	1.5	10	0.154
204	1.2DL + 1.5LM11 + 1.6SWL (30 mph) AZI 270	Yes	Y	1	1.2	44	1.5	11	0.154
205	1.2DL + 1.5LM11 + 1.6SWL (30 mph) AZI 300	Yes	Y	1	1.2	44	1.5	12	0.154
206	1.2DL + 1.5LM11 + 1.6SWL (30 mph) AZI 330	Yes	Y	1	1.2	44	1.5	13	0.154
207	1.2DL + 1.5LM12 + 1.6SWL (30 mph) AZI 0	Yes	Y	1	1.2	45	1.5	2	0.154
208	1.2DL + 1.5LM12 + 1.6SWL (30 mph) AZI 30	Yes	Y	1	1.2	45	1.5	3	0.154

Load Combinations (Continued)

	Description	Solve	PDelta	BLC	Factor	BLC	Factor	BLC	Factor
209	1.2DL + 1.5LM12 + 1.6SWL (30 mph) AZI 60	Yes	Y	1	1.2	45	1.5	4	0.154
210	1.2DL + 1.5LM12 + 1.6SWL (30 mph) AZI 90	Yes	Y	1	1.2	45	1.5	5	0.154
211	1.2DL + 1.5LM12 + 1.6SWL (30 mph) AZI 120	Yes	Y	1	1.2	45	1.5	6	0.154
212	1.2DL + 1.5LM12 + 1.6SWL (30 mph) AZI 150	Yes	Y	1	1.2	45	1.5	7	0.154
213	1.2DL + 1.5LM12 + 1.6SWL (30 mph) AZI 180	Yes	Y	1	1.2	45	1.5	8	0.154
214	1.2DL + 1.5LM12 + 1.6SWL (30 mph) AZI 210	Yes	Y	1	1.2	45	1.5	9	0.154
215	1.2DL + 1.5LM12 + 1.6SWL (30 mph) AZI 240	Yes	Y	1	1.2	45	1.5	10	0.154
216	1.2DL + 1.5LM12 + 1.6SWL (30 mph) AZI 270	Yes	Y	1	1.2	45	1.5	11	0.154
217	1.2DL + 1.5LM12 + 1.6SWL (30 mph) AZI 300	Yes	Y	1	1.2	45	1.5	12	0.154
218	1.2DL + 1.5LM12 + 1.6SWL (30 mph) AZI 330	Yes	Y	1	1.2	45	1.5	13	0.154
219	1.2DL + 1.5LM13 + 1.6SWL (30 mph) AZI 0	Yes	Y	1	1.2	46	1.5	2	0.154
220	1.2DL + 1.5LM13 + 1.6SWL (30 mph) AZI 30	Yes	Y	1	1.2	46	1.5	3	0.154
221	1.2DL + 1.5LM13 + 1.6SWL (30 mph) AZI 60	Yes	Y	1	1.2	46	1.5	4	0.154
222	1.2DL + 1.5LM13 + 1.6SWL (30 mph) AZI 90	Yes	Y	1	1.2	46	1.5	5	0.154
223	1.2DL + 1.5LM13 + 1.6SWL (30 mph) AZI 120	Yes	Y	1	1.2	46	1.5	6	0.154
224	1.2DL + 1.5LM13 + 1.6SWL (30 mph) AZI 150	Yes	Y	1	1.2	46	1.5	7	0.154
225	1.2DL + 1.5LM13 + 1.6SWL (30 mph) AZI 180	Yes	Y	1	1.2	46	1.5	8	0.154
226	1.2DL + 1.5LM13 + 1.6SWL (30 mph) AZI 210	Yes	Y	1	1.2	46	1.5	9	0.154
227	1.2DL + 1.5LM13 + 1.6SWL (30 mph) AZI 240	Yes	Y	1	1.2	46	1.5	10	0.154
228	1.2DL + 1.5LM13 + 1.6SWL (30 mph) AZI 270	Yes	Y	1	1.2	46	1.5	11	0.154
229	1.2DL + 1.5LM13 + 1.6SWL (30 mph) AZI 300	Yes	Y	1	1.2	46	1.5	12	0.154
230	1.2DL + 1.5LM13 + 1.6SWL (30 mph) AZI 330	Yes	Y	1	1.2	46	1.5	13	0.154
231	1.2DL + 1.5LM14 + 1.6SWL (30 mph) AZI 0	Yes	Y	1	1.2	47	1.5	2	0.154
232	1.2DL + 1.5LM14 + 1.6SWL (30 mph) AZI 30	Yes	Y	1	1.2	47	1.5	3	0.154
233	1.2DL + 1.5LM14 + 1.6SWL (30 mph) AZI 60	Yes	Y	1	1.2	47	1.5	4	0.154
234	1.2DL + 1.5LM14 + 1.6SWL (30 mph) AZI 90	Yes	Y	1	1.2	47	1.5	5	0.154
235	1.2DL + 1.5LM14 + 1.6SWL (30 mph) AZI 120	Yes	Y	1	1.2	47	1.5	6	0.154
236	1.2DL + 1.5LM14 + 1.6SWL (30 mph) AZI 150	Yes	Y	1	1.2	47	1.5	7	0.154
237	1.2DL + 1.5LM14 + 1.6SWL (30 mph) AZI 180	Yes	Y	1	1.2	47	1.5	8	0.154
238	1.2DL + 1.5LM14 + 1.6SWL (30 mph) AZI 210	Yes	Y	1	1.2	47	1.5	9	0.154
239	1.2DL + 1.5LM14 + 1.6SWL (30 mph) AZI 240	Yes	Y	1	1.2	47	1.5	10	0.154
240	1.2DL + 1.5LM14 + 1.6SWL (30 mph) AZI 270	Yes	Y	1	1.2	47	1.5	11	0.154
241	1.2DL + 1.5LM14 + 1.6SWL (30 mph) AZI 300	Yes	Y	1	1.2	47	1.5	12	0.154
242	1.2DL + 1.5LM14 + 1.6SWL (30 mph) AZI 330	Yes	Y	1	1.2	47	1.5	13	0.154
243	1.2DL + 1.5LM15 + 1.6SWL (30 mph) AZI 0	Yes	Y	1	1.2	48	1.5	2	0.154
244	1.2DL + 1.5LM15 + 1.6SWL (30 mph) AZI 30	Yes	Y	1	1.2	48	1.5	3	0.154
245	1.2DL + 1.5LM15 + 1.6SWL (30 mph) AZI 60	Yes	Y	1	1.2	48	1.5	4	0.154
246	1.2DL + 1.5LM15 + 1.6SWL (30 mph) AZI 90	Yes	Y	1	1.2	48	1.5	5	0.154
247	1.2DL + 1.5LM15 + 1.6SWL (30 mph) AZI 120	Yes	Y	1	1.2	48	1.5	6	0.154
248	1.2DL + 1.5LM15 + 1.6SWL (30 mph) AZI 150	Yes	Y	1	1.2	48	1.5	7	0.154
249	1.2DL + 1.5LM15 + 1.6SWL (30 mph) AZI 180	Yes	Y	1	1.2	48	1.5	8	0.154
250	1.2DL + 1.5LM15 + 1.6SWL (30 mph) AZI 210	Yes	Y	1	1.2	48	1.5	9	0.154
251	1.2DL + 1.5LM15 + 1.6SWL (30 mph) AZI 240	Yes	Y	1	1.2	48	1.5	10	0.154
252	1.2DL + 1.5LM15 + 1.6SWL (30 mph) AZI 270	Yes	Y	1	1.2	48	1.5	11	0.154
253	1.2DL + 1.5LM15 + 1.6SWL (30 mph) AZI 300	Yes	Y	1	1.2	48	1.5	12	0.154
254	1.2DL + 1.5LM15 + 1.6SWL (30 mph) AZI 330	Yes	Y	1	1.2	48	1.5	13	0.154
255	1.2DL + 1.5LM16 + 1.6SWL (30 mph) AZI 0	Yes	Y	1	1.2	49	1.5	2	0.154
256	1.2DL + 1.5LM16 + 1.6SWL (30 mph) AZI 30	Yes	Y	1	1.2	49	1.5	3	0.154
257	1.2DL + 1.5LM16 + 1.6SWL (30 mph) AZI 60	Yes	Y	1	1.2	49	1.5	4	0.154
258	1.2DL + 1.5LM16 + 1.6SWL (30 mph) AZI 90	Yes	Y	1	1.2	49	1.5	5	0.154
259	1.2DL + 1.5LM16 + 1.6SWL (30 mph) AZI 120	Yes	Y	1	1.2	49	1.5	6	0.154
260	1.2DL + 1.5LM16 + 1.6SWL (30 mph) AZI 150	Yes	Y	1	1.2	49	1.5	7	0.154
261	1.2DL + 1.5LM16 + 1.6SWL (30 mph) AZI 180	Yes	Y	1	1.2	49	1.5	8	0.154
262	1.2DL + 1.5LM16 + 1.6SWL (30 mph) AZI 210	Yes	Y	1	1.2	49	1.5	9	0.154
263	1.2DL + 1.5LM16 + 1.6SWL (30 mph) AZI 240	Yes	Y	1	1.2	49	1.5	10	0.154
264	1.2DL + 1.5LM16 + 1.6SWL (30 mph) AZI 270	Yes	Y	1	1.2	49	1.5	11	0.154
265	1.2DL + 1.5LM16 + 1.6SWL (30 mph) AZI 300	Yes	Y	1	1.2	49	1.5	12	0.154
266	1.2DL + 1.5LM16 + 1.6SWL (30 mph) AZI 330	Yes	Y	1	1.2	49	1.5	13	0.154

Load Combinations (Continued)

	Description	Solve	PDelta	BLC	Factor	BLC	Factor	BLC	Factor
267	1.2DL + 1.5LM17 + 1.6SWL (30 mph) AZI 0	Yes	Y	1	1.2	50	1.5	2	0.154
268	1.2DL + 1.5LM17 + 1.6SWL (30 mph) AZI 30	Yes	Y	1	1.2	50	1.5	3	0.154
269	1.2DL + 1.5LM17 + 1.6SWL (30 mph) AZI 60	Yes	Y	1	1.2	50	1.5	4	0.154
270	1.2DL + 1.5LM17 + 1.6SWL (30 mph) AZI 90	Yes	Y	1	1.2	50	1.5	5	0.154
271	1.2DL + 1.5LM17 + 1.6SWL (30 mph) AZI 120	Yes	Y	1	1.2	50	1.5	6	0.154
272	1.2DL + 1.5LM17 + 1.6SWL (30 mph) AZI 150	Yes	Y	1	1.2	50	1.5	7	0.154
273	1.2DL + 1.5LM17 + 1.6SWL (30 mph) AZI 180	Yes	Y	1	1.2	50	1.5	8	0.154
274	1.2DL + 1.5LM17 + 1.6SWL (30 mph) AZI 210	Yes	Y	1	1.2	50	1.5	9	0.154
275	1.2DL + 1.5LM17 + 1.6SWL (30 mph) AZI 240	Yes	Y	1	1.2	50	1.5	10	0.154
276	1.2DL + 1.5LM17 + 1.6SWL (30 mph) AZI 270	Yes	Y	1	1.2	50	1.5	11	0.154
277	1.2DL + 1.5LM17 + 1.6SWL (30 mph) AZI 300	Yes	Y	1	1.2	50	1.5	12	0.154
278	1.2DL + 1.5LM17 + 1.6SWL (30 mph) AZI 330	Yes	Y	1	1.2	50	1.5	13	0.154
279	1.2DL + 1.5LM18 + 1.6SWL (30 mph) AZI 0	Yes	Y	1	1.2	51	1.5	2	0.154
280	1.2DL + 1.5LM18 + 1.6SWL (30 mph) AZI 30	Yes	Y	1	1.2	51	1.5	3	0.154
281	1.2DL + 1.5LM18 + 1.6SWL (30 mph) AZI 60	Yes	Y	1	1.2	51	1.5	4	0.154
282	1.2DL + 1.5LM18 + 1.6SWL (30 mph) AZI 90	Yes	Y	1	1.2	51	1.5	5	0.154
283	1.2DL + 1.5LM18 + 1.6SWL (30 mph) AZI 120	Yes	Y	1	1.2	51	1.5	6	0.154
284	1.2DL + 1.5LM18 + 1.6SWL (30 mph) AZI 150	Yes	Y	1	1.2	51	1.5	7	0.154
285	1.2DL + 1.5LM18 + 1.6SWL (30 mph) AZI 180	Yes	Y	1	1.2	51	1.5	8	0.154
286	1.2DL + 1.5LM18 + 1.6SWL (30 mph) AZI 210	Yes	Y	1	1.2	51	1.5	9	0.154
287	1.2DL + 1.5LM18 + 1.6SWL (30 mph) AZI 240	Yes	Y	1	1.2	51	1.5	10	0.154
288	1.2DL + 1.5LM18 + 1.6SWL (30 mph) AZI 270	Yes	Y	1	1.2	51	1.5	11	0.154
289	1.2DL + 1.5LM18 + 1.6SWL (30 mph) AZI 300	Yes	Y	1	1.2	51	1.5	12	0.154
290	1.2DL + 1.5LM18 + 1.6SWL (30 mph) AZI 330	Yes	Y	1	1.2	51	1.5	13	0.154

Envelope Node Reactions

Node Label		X [lb]	LC	Y [lb]	LC	Z [lb]	LC	MX [lb-in]	LC	MY [lb-in]	LC	MZ [lb-in]	LC	
1	N1	max	905.255	25	1649.562	87	910.801	16	14851.995	108	16870.179	16	2620.082	20
2		min	-1101.221	8	96.024	20	-923.354	24	-14851.1	90	-17200.108	24	-61952.723	87
3	N67	max	1198.642	2	1725.89	35	1115.166	5	2894.363	16	21950.067	25	30206.78	143
4		min	-1090.318	20	129.093	16	-940.67	24	-50085.608	35	-17854.158	18	-1560.157	16
5	N117	max	1128.551	2	1649.791	127	864.19	16	60923.996	127	17217.965	22	29811.578	211
6		min	-1020.402	20	81.453	24	-1106.485	12	-2890.37	24	-17185.582	16	-1668.27	24
7	Totals:	max	3180.168	14	4653.436	35	2787.112	16						
8		min	-3180.168	20	1698.323	52	-2942.973	12						

Envelope AISC 14TH (360-10): LRFD Member Steel Code Checks

Member	Shape	Code Check	Loc[in]	LC	Shear Check	Loc[in]	Dir	LC	phi*Pnc [lb]	phi*Pnt [lb]	phi*Mn y-y [lb-in]	phi*Mn z-z [lb-in]	Cb	Eqn
1	M24	6"x0.375" Plate	0.158	1.125	2	0.791	0	y	10971110.261	72900	6834.391	109350	3	H1-1b
2	M100	6"x0.375" Plate	0.159	1.125	6	0.791	0	y	12971110.261	72900	6834.391	109350	3	H1-1b
3	M30	6"x0.375" Plate	0.158	1.125	2	0.791	0	y	8971110.261	72900	6834.391	109350	3	H1-1b
4	M12	6"x0.375" Plate	0.143	2.036	2	0.751	2.036	y	10962722.329	72900	6834.391	109350	2.484	H1-1b
5	M83	6"x0.375" Plate	0.144	2.036	6	0.75	2.036	y	12962722.329	72900	6834.391	109350	2.49	H1-1b
6	M13	6"x0.375" Plate	0.143	2.036	2	0.75	2.036	y	8962722.329	72900	6834.391	109350	2.492	H1-1b
7	M23	6"x0.375" Plate	0.128	1.125	5	0.623	0	y	10971110.261	72900	6834.391	109350	3	H1-1b
8	M99	6"x0.375" Plate	0.13	1.125	3	0.622	0	y	12971110.261	72900	6834.391	109350	3	H1-1b
9	M29	6"x0.375" Plate	0.128	1.125	11	0.622	0	y	8971110.261	72900	6834.391	109350	3	H1-1b
10	M61	6"x0.375" Plate	0.135	1.125	13	0.615	0	y	3371110.261	72900	6834.391	109350	3	H1-1b
11	M93	6"x0.375" Plate	0.13	1.125	9	0.614	0	y	2971110.261	72900	6834.391	109350	3	H1-1b
12	M67	6"x0.375" Plate	0.134	1.125	25	0.614	0	y	3871110.261	72900	6834.391	109350	3	H1-1b
13	M11	6"x0.375" Plate	0.128	2.036	11	0.587	2.036	y	10962722.329	72900	6834.391	109350	2.23	H1-1b
14	M80	6"x0.375" Plate	0.131	2.036	9	0.586	2.036	y	12962722.329	72900	6834.391	109350	2.216	H1-1b
15	M10	6"x0.375" Plate	0.128	2.036	5	0.586	2.036	y	8962722.329	72900	6834.391	109350	2.229	H1-1b
16	M49	6"x0.375" Plate	0.141	2.036	25	0.577	2.036	y	3362722.329	72900	6834.391	109350	2.006	H1-1b
17	M81	6"x0.375" Plate	0.132	2.036	3	0.576	2.036	y	2962722.329	72900	6834.391	109350	2.216	H1-1b
18	M48	6"x0.375" Plate	0.142	2.036	13	0.576	2.036	y	3862722.329	72900	6834.391	109350	2.178	H1-1b
19	M68	6"x0.375" Plate	0.157	1.125	10	0.519	0	y	14571110.261	72900	6834.391	109350	3	H1-1b

Envelope AISC 14TH (360-10): LRFD Member Steel Code Checks (Continued)

Member	Shape	Code Check	Loc[in]	LC	Shear	Check	Loc[in]	Dir	LC	phi*	Pnc [lb]	phi*	Pnt [lb]	phi*	Mn y-y [lb-in]	phi*	Mn z-z [lb-in]	Cb	Eqn
20	M94	6"x0.375" Plate	0.158	1.125	6	0.518	0	y	209	71110.261	72900	6834.391	109350	3	H1-1b				
21	M62	6"x0.375" Plate	0.159	1.125	10	0.517	0	y	225	71110.261	72900	6834.391	109350	3	H1-1b				
22	M51	6"x0.375" Plate	0.139	2.036	10	0.491	2.036	y	145	62722.329	72900	6834.391	109350	2.492	H1-1b				
23	M82	6"x0.375" Plate	0.139	2.036	6	0.49	2.036	y	209	62722.329	72900	6834.391	109350	2.485	H1-1b				
24	M50	6"x0.375" Plate	0.143	2.036	10	0.489	2.036	y	225	62722.329	72900	6834.391	109350	2.483	H1-1b				
25	M6	L4X4X4	0.284	24.375	89	0.227	24.375	z	98	54411.715	62532	37651.159	80578.632	1.5	H2-1				
26	M7	L4X4X4	0.284	0	109	0.226	0	z	100	54411.715	62532	37651.159	80578.632	1.5	H2-1				
27	M76	L4X4X4	0.284	24.375	129	0.226	24.375	z	126	54411.715	62532	37651.159	80578.632	1.5	H2-1				
28	M77	L4X4X4	0.235	0	25	0.144	0	y	7	54411.715	62532	37651.159	80578.632	1.5	H2-1				
29	M44	L4X4X4	0.216	24.375	16	0.143	24.375	y	9	54411.715	62532	37651.159	80578.632	1.5	H2-1				
30	M45	L4X4X4	0.213	0	16	0.14	0	y	12	54411.715	62532	37651.159	80578.632	1.5	H2-1				
31	M9	L4X4X4	0.294	0	98	0.134	0	z	97	51466.784	62532	37651.159	80578.632	1.5	H2-1				
32	M8	L4X4X4	0.294	36.125	99	0.134	36.125	z	101	51466.784	62532	37651.159	80578.632	1.5	H2-1				
33	M79	L4X4X4	0.294	0	127	0.134	0	z	125	51466.784	62532	37651.159	80578.632	1.5	H2-1				
34	M1	HSS4X4X4	0.325	0	97	0.133	0	y	109	133649.326	139518	194166	194166	1.775	H1-1b				
35	M73	HSS4X4X4	0.325	0	125	0.133	0	y	129	133649.326	139518	194166	194166	1.776	H1-1b				
36	M46	L4X4X4	0.293	36.125	35	0.13	36.125	z	85	51466.784	62532	37651.159	80578.632	1.5	H2-1				
37	M105	PIPE 3.0	0.124	48	122	0.119	93		110	60482.561	65205	68985	68985	1	H1-1b				
38	M113	PIPE 3.0	0.124	48	77	0.119	3		89	60482.561	65205	68985	68985	1	H1-1b				
39	M78	L4X4X4	0.293	36.125	31	0.115	36.125	z	33	51466.784	62532	37651.159	80578.632	1.5	H2-1				
40	M47	L4X4X4	0.292	0	35	0.115	0	z	33	51466.784	62532	37651.159	80578.632	1.5	H2-1				
41	M65	6"x0.375" Plate	0.272	1.125	9	0.111	1.125	y	13	71110.261	72900	6834.391	109350	2.978	H1-1b				
42	M52	L2.5x2.5x3	0.107	27.5	10	0.107	55	z	13	14632.678	29192.4	10470.885	20138.381	1.082	H2-1				
43	M97	6"x0.375" Plate	0.266	1.125	5	0.101	1.125	y	9	71110.261	72900	6834.391	109350	2.986	H1-1b				
44	M103	6"x0.375" Plate	0.272	1.125	7	0.101	1.125	y	3	71110.261	72900	6834.391	109350	2.978	H1-1b				
45	M71	6"x0.375" Plate	0.266	1.125	11	0.101	1.125	y	7	71110.261	72900	6834.391	109350	2.987	H1-1b				
46	M53	6"x0.375" Plate	0.22	5.75	9	0.099	5.75	y	13	62722.329	72900	6834.391	109350	1.458	H1-1b				
47	M33	6"x0.375" Plate	0.272	1.125	3	0.099	1.125	y	11	71110.261	72900	6834.391	109350	2.978	H1-1b				
48	M27	6"x0.375" Plate	0.283	1.125	13	0.098	1.125	y	5	71110.261	72900	6834.391	109350	2.968	H1-1b				
49	M42	PIPE 2.0	0.251	30	13	0.096	38		13	14916.096	32130	22459.5	22459.5	3	H1-1b				
50	M84	L2.5x2.5x3	0.107	27.5	6	0.096	55	z	9	14632.678	29192.4	10470.885	20138.3	1.082	H2-1				
51	M3	PIPE 2.5	0.095	90	6	0.095	90		6	30038.461	50715	43155	43155	1.785	H1-1b				
52	M106	PIPE 2.5	0.106	90	13	0.095	6		6	30038.461	50715	43155	43155	1.767	H1-1b				
53	M114	PIPE 2.5	0.097	48	75	0.094	6		2	30038.461	50715	43155	43155	1.795	H1-1b				
54	M14	L2.5x2.5x3	0.107	27.5	2	0.093	55	y	12	14632.678	29192.4	10470.885	20138.433	1.082	H2-1				
55	M85	6"x0.375" Plate	0.215	5.75	5	0.09	5.75	y	9	62722.329	72900	6834.391	109350	1.469	H1-1b				
56	M86	6"x0.375" Plate	0.22	5.75	7	0.09	5.75	y	3	62722.329	72900	6834.391	109350	1.455	H1-1b				
57	M54	6"x0.375" Plate	0.215	5.75	11	0.09	5.75	y	7	62722.329	72900	6834.391	109350	1.472	H1-1b				
58	M16	6"x0.375" Plate	0.22	5.75	3	0.088	5.75	y	11	62722.329	72900	6834.391	109350	1.454	H1-1b				
59	M15	6"x0.375" Plate	0.228	5.75	13	0.088	5.75	y	5	62722.329	72900	6834.391	109350	1.407	H1-1b				
60	M5	HSS4.5X4.5X3	0.052	20	98	0.088	8.958	y	109	120246.398	121302	194994	194994	1.448	H1-1b				
61	M75	HSS4.5X4.5X3	0.051	20	127	0.088	8.958	y	129	120246.398	121302	194994	194994	1.448	H1-1b				
62	M74	PIPE 2.0	0.244	30	8	0.087	38		3	14916.096	32130	22459.5	22459.5	3	H1-1b				
63	M4	PIPE 2.0	0.249	30	12	0.085	38		12	14916.096	32130	22459.5	22459.5	2.48	H1-1b				
64	M41	HSS4X4X4	0.305	0	37	0.084	0	y	81	133649.326	139518	194166	194166	1.874	H1-1b				
65	M110	PIPE 2.0	0.335	30	8	0.076	30		6	14916.096	32130	22459.5	22459.5	3	H1-1b				
66	M35	PIPE 2.0	0.335	30	4	0.076	30		6	14916.096	32130	22459.5	22459.5	3	H1-1b				
67	M107	PIPE 2.0	0.354	30	13	0.076	30		2	14916.096	32130	22459.5	22459.5	2.65	H1-1b				
68	M38	PIPE 2.0	0.338	30	12	0.076	30		10	14916.096	32130	22459.5	22459.5	3	H1-1b				
69	M118	PIPE 2.0	0.335	30	4	0.076	30		2	14916.096	32130	22459.5	22459.5	2.543	H1-1b				
70	M115	PIPE 2.0	0.335	30	8	0.076	30		10	14916.096	32130	22459.5	22459.5	3	H1-1b				
71	M2	PIPE 3.0	0.1	48	37	0.066	3		12	60482.561	65205	68985	68985	1	H1-1b				
72	M43	HSS4.5X4.5X3	0.044	8.958	12	0.053	8.958	y	225	120246.398	121302	194994	194994	1.455	H1-1b				
73	M125	PIPE 2.0	0.043	18	10	0.008	18		10	26521.424	32130	22459.5	22459.5	2.402	H1-1b				

INFINIGY

FROM ZERO TO INFINIGY
the solutions are endless

BOLT CONNECTION CALCULATION

BOLT PROPERTIES

Date:	9/27/2021
Site:	BOBDL00107A
Engineer:	DVA
Project No:	2039-Z5555C
Connection Location:	Arm to Collar

Bolt Capacity Equation	TIA-222-G	
Connection Type	Steel	
Bolt Size, d	5/8	in
Threads per Inch, n	11	
Steel Grade	A325	
Bolt Ultimate Tensile Stress, F_u	120	ksi
Threads Exclusion	N	
Shear Plane	1	
Net Bolt Cross-Sectional Area, A_n	0.226	in ²
Gross Bolt Cross-Sectional Area, A_g	0.307	in ²
Tensile Steel Strength (per bolt), φR_{nt}	20340	lbs
Shear Steel Strength (per bolt), φR_{nv}	12425	lbs

INFINIGY8

FROM ZERO TO INFINITY
the solutions are endless

BOLT CONNECTION CALCULATION BOLT GROUP CHECK

Date:	9/27/2021
Site:	BOBDL00107A
Engineer:	DVA
Project No.:	2039-Z5555C
Connection Location:	Arm to Collar

Loads Properties	
Controlling LC:	97
Load Point Number:	N1
X-Coordinate (in.)	4.00
Y-Coordinate (in.)	4.00
Z-Coordinate (in.)	0.00
Shear Load, Px (lbs)	0
Shear Load, Py (lbs)	0
Axial Load, Pz (lbs)	0
Moment, Mx (lb-in)	0
Moment, My (lb-in)	0
Moment, Mz (lb-in)	0


Member Properties	
X	Y
0.0	0.0
8.0	8.0

Number of Bolts: 4

No.	Bolt Type	Bolt Coordinates		Bolt Loads			Steel Bolt Usage		Max. Capacity
		Xo (in)	Yo (in)	Axial (lbs)	Shear (lbs)	Tension	Shear	Combined	
1	Main Type	1.0	1.0	4936.25	1151.95	24.3%	9.3%	24.3%	24.3%
2	Main Type	7.0	1.0	5277.08	600.58	25.9%	4.8%	25.9%	25.9%
3	Main Type	1.0	7.0	-5215.58	1175.68	0.0%	9.5%	9.5%	9.5%
4	Main Type	7.0	7.0	-4874.75	644.92	0.0%	5.2%	5.2%	5.2%

Bolt Group Properties:	
Xc =	4.00 in.
Yc =	4.00 in.
Ic,y =	11.04 in.^2
Ic,x =	11.04 in.^2
Ic,xy =	22.09 in.^2






Loads at Center of Gravity of Bolt Group:	
Pz =	123.00 lbs
Px =	93.00 lbs
Py =	1627.00 lbs
Mx =	-60911.00 lb-in
My =	-2045.00 lb-in
Mz =	14254.00 lb-in



Total Capacity of Bolt Group: 25.9%

PARTS LIST

ITEM	QTY	PART NO.	PART DESCRIPTION	LENGTH	UNIT WT.	NET WT.
1	3	X-LWRM	RING MOUNT WELDMENT		68.81	206.42
2	3	X-SNP-ST8	SNB8 TELESCOPING ARM FOR GRATING		60.39	181.16
3	3	X-SNPC	CORNER GRATING WELDMENT		194.33	582.99
4	3	P396	3" SCH. 40 PIPE (3.5" O.D. x 0.216" WALL) A500	96.000 in	60.75	182.25
5	3	P3096	2-7/8" OD X 96" Sch 40 Galvanized Pipe		46.45	139.36
6	3	X-SNP-HRA	CORNER BRACKET FOR SNPX PLATFORMS		25.95	77.86
7	3	X-SNPP1G	CLAMP PLATE	7.250 in	2.03	6.10
8	9	X-SP219	SMALL SUPPORT CROSS PLATE	8.250 in	8.61	77.50
9	9	SCX2	CROSSOVER PLATE	7.000 in	4.80	43.17
10	9	G58R-48	5/8" x 48" THREADED ROD (HDG.)		0.55	4.94
11	9	G58R-24	5/8" x 24" THREADED ROD (HDG.)		0.55	4.94
12	12	A58234	5/8" x 2-3/4" HDG A325 HEX BOLT	2.75	0.36	4.27
13	30	A58FW	5/8" HDG A325 FLATWASHER		0.03	1.02
14	18	A58NUT	5/8" HDG LOCKWASHER		0.03	0.78
15	12	G58NUT	5/8" HDG HEAVY 2H HEX NUT		0.13	2.34
16	12	X-UB1300	1/2" x 3" x 5" x 2" U-BOLT (HDG.)		0.13	1.56
17	24	X-UB1306	1/2" x 3-5/8" x 5-1/2" x 3" U-BOLT (HDG.)		0.73	17.56
18	36	X-UB1212	1/2" x 2-1/2" x 4-1/2" x 2" U-BOLT (HDG.)	7-1/2	0.73	26.34
19	6	G12065	1/2" x 6-1/2" HDG HEX BOLT GR5 FULL THREAD		0.41	2.46
20	18	X-UB1306	1/2" x 3-5/8" x 5" x 3" U-BOLT (HDG.)		0.73	13.17
21	186	G12NUT	1/2" HDG HEAVY 2H HEX NUT		0.07	13.32
22	180	G12FW	1/2" HDG USS FLATWASHER		0.03	6.13
23	186	G12LW	1/2" HDG LOCKWASHER		0.01	2.69
24	9	A	2" SCH. 40 PIPE (2.375" O.D. x 0.154" WALL) A500	B	C	D



2-3/8" O.D. VERTICAL MOUNTING PIPES				
ASSEMBLY NO.	PART NO.	"A" LENGTH "B"	UNIT WEIGHT "C"	TOTAL WEIGHT "D"
SNP8HR-372	P272	6'-0"	2307	1717.07
SNP8HR-384	P284	7'-0"	2691	1751.63
SNP8HR-396	P296	8'-0"	3076	1786.28
SNP8HR-3126	P2126	10'-6"	4075	1876.19

TOLERANCE NOTES

TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE:
 SAWN, SHEARED AND GAS CUT EDGES ($\pm 0.030"$)
 DRILLED AND GAS CUT HOLES ($\pm 0.030"$) - NO CONING OF HOLES
 LASER CUT EDGES AND HOLES ($\pm 0.010"$) - NO CONING OF HOLES
 BENDS ARE $\pm 1/2$ DEGREE
 ALL OTHER MACHINING ($\pm 0.030"$)
 ALL OTHER ASSEMBLY ($\pm 0.060"$)

PROPRIETARY NOTE:
 THE DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT
 INDUSTRIES. ANY REPRODUCTION OR TRANSMISSION OF THIS INFORMATION WITHOUT THE CONSENT OF
 VALMONT INDUSTRIES IS STRICTLY PROHIBITED.

DESCRIPTION
 8" SNUB NOSE PLATFORM WITH HANDRAIL

ENGINEERING
 Support Team:
 Los Angeles, CA
 Plymouth, IN
 Salem, OR
 Dallas, TX



VALMONT
 A valmont COMPANY

PART NO.
 SEE ASSEMBLY NO.
 SNP8HR-3XX


APPROVAL
 DRAWN BY: CEK 11/19/2014
 CHECKED BY: BMC 11/21/2014

CLASS
 SUB: 81 02
 CUSTOMER: BMC




PAGE
 1 OF 2



DETAIL B



DETAIL A



DESCRIPTION		DRAWN BY		ENG. APPROVAL	
8' SNUB NOSE PLATFORM WITH HANDRAIL		CEK 11/19/2014			
GPD NO.		DRAWING USAGE		CHECKED BY	
81 02		CUSTOMER		BMC 11/21/2014	
PART NO.		SEE ASSEMBLY NO.		DWG. NO.	
SNP8HR-3XX					

TOLERANCE NOTES
 TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE:
 SAWED, SHEARED AND GAS CUT EDGES (± 0.030)
 DRILLED AND GAS CUT HOLES (± 0.030) - NO CONING OF HOLES
 LASER CUT EDGES AND HOLES (± 0.010) - NO CONING OF HOLES
 BENDS ARE $\pm 1/2$ DEGREE
 ALL OTHER MACHINING (± 0.030)
 ALL OTHER ASSEMBLY (± 0.060)

PROPRIETARY NOTE:
 THE DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT
 AND SHOULD BE KEPT AS A TRADE SECRET. ANY USE OR DISCLOSURE WITHOUT THE CONSENT OF
 VALMONT IS PROHIBITED AND IS STRICTLY FORBIDDEN.

Locations:
 New York, NY
 Atlanta, GA
 Los Angeles, CA
 Plymouth, IN
 Salem, OR
 Dallas, TX

Engineering
 Support Team:
 1-888-753-7446

SITE PRO
 A valmont COMPANY

PAGE
 2 OF 2

Exhibit F

Power Density/RF Emissions Report



Radio Frequency Emissions Analysis Report



Site ID: BOBDL00107A

BOBDL00107A
82 Lovely Street
Unionville, CT 06085

October 21, 2021

Fox Hill Telecom Project Number: 210615

Site Compliance Summary	
Compliance Status:	COMPLIANT
Site total MPE% of FCC general population allowable limit:	36.76 %



October 21, 2021

Dish Wireless
5701 South Santa Fe Drive
Littleton, CO 80120

Emissions Analysis for Site: **BOBDL00107A – BOBDL00107A**

Fox Hill Telecom, Inc (“Fox Hill”) was directed to analyze the proposed radio installation for **Dish Wireless, LLC (“Dish”)** facility located at **82 Lovely Street, Unionville, CT**, for the purpose of determining whether the emissions from the Proposed Dish radio and antenna installation located on this property are within specified federal limits.

All information used in this report was analyzed as a percentage of current Maximum Permissible Exposure (% MPE) as listed in the FCC OET Bulletin 65 Edition 97-01 and ANSI/IEEE Std C95.1. The FCC regulates Maximum Permissible Exposure in units of microwatts per square centimeter ($\mu\text{W}/\text{cm}^2$). The number of $\mu\text{W}/\text{cm}^2$ calculated at each sample point is called the power density. The exposure limit for power density varies depending upon the frequencies being utilized. Wireless Carriers and Paging Services use different frequency bands each with different exposure limits, therefore it is necessary to report results and limits in terms of percent MPE rather than power density.

All results were compared to the FCC (Federal Communications Commission) radio frequency exposure rules, 47 CFR 1.1307(b)(1) – (b)(3), to determine compliance with the Maximum Permissible Exposure (MPE) limits for General Population/Uncontrolled environments as defined below.

General population/uncontrolled exposure limits apply to situations in which the general population may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Therefore, members of the general population would always be considered under this category when exposure is not employment related, for example, in the case of a telecommunications tower that exposes persons in a nearby residential area.

Population exposure to radio frequencies is regulated and enforced in units of microwatts per square centimeter ($\mu\text{W}/\text{cm}^2$). The general population exposure limits for the 600 MHz & 700 MHz bands are approximately $400 \mu\text{W}/\text{cm}^2$ and $467 \mu\text{W}/\text{cm}^2$ respectively. The general population exposure limit for the 1900 MHz (PCS) and 2100 MHz (AWS) bands is $1000 \mu\text{W}/\text{cm}^2$. Because each carrier will be using different frequency bands, and each frequency band has different exposure limits, it is necessary to report percent of MPE rather than power density.



Occupational/controlled exposure limits apply to situations in which persons are exposed as a consequence of their employment and in which those persons who are exposed have been made fully aware of the potential for exposure and can exercise control over their exposure. Occupational/controlled exposure limits also apply where exposure is of a transient nature as a result of incidental passage through a location where exposure levels may be above general population/uncontrolled limits (see below), as long as the exposed person has been made fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Additional details can be found in FCC OET 65.



CALCULATIONS

Calculations were performed for the proposed radio system installation for **Dish** on the subject site located at **82 Lovely Street, Unionville, CT**, using the equipment information listed below. All calculations were performed per the specifications under FCC OET 65. Since **Dish** is proposing highly focused directional panel antennas, which project most of the emitted energy out toward the horizon, all calculations were performed assuming a lobe representing the maximum gain of the antenna per the antenna manufactures supplied specifications, minus 10 dB for directional panel antennas, was focused toward the base of the tower. For this report the sample point is the top of a 6-foot person standing at the base of the tower.

Per FCC OET Bulletin No. 65 - Edition 97-01 recommendations to achieve the maximum anticipated value at each sample point, all power levels emitting from the proposed antenna installation are increased by a factor of 2.56 to account for possible in-phase reflections from the surrounding environment. All power values expressed and analyzed are maximum power levels expected to be used on all radios.

All emissions values for additional carriers were taken from the Connecticut Siting Council (CSC) active MPE database. Values in this database are provided by the individual carriers themselves

For each sector the following channel counts, frequency bands and power levels were utilized as shown in *Table 1*:

Technology	Frequency Band	Channel Count	Transmit Power per Channel (W)
5G	600 MHz	4	61.5
5G	1900 MHz (PCS)	4	40
5G	2100 MHz (AWS)	4	40

Table 1: Channel Data Table



The following antennas listed in *Table 2* were used in the modeling for transmission in the 600 MHz, 1900 MHz (PCS) and 2100 MHz (AWS) frequency bands. This is based on feedback from the carrier with regards to anticipated antenna selection. Maximum gain values for all antennas are listed in the Inventory and Power Data table below. The maximum gain of the antenna per the antenna manufactures supplied specifications, minus 10 dB for directional panel antennas, was used for all calculations. This value is a very conservative estimate as gain reductions for these particular antennas are typically much higher in this direction.

Sector	Antenna Number	Antenna Make / Model	Antenna Centerline (ft)
A	1	JMA MX08FRO665-21	88
B	1	JMA MX08FRO665-21	88
C	1	JMA MX08FRO665-21	88

Table 2: Antenna Data

All calculations were done with respect to uncontrolled / general population threshold limits.



RESULTS

Per the calculations completed for the proposed **Dish** configurations *Table 3* shows resulting emissions power levels and percentages of the FCC’s allowable general population limit.

Antenna ID	Antenna Make / Model	Frequency Bands	Antenna Gain (dBd)	Channel Count	Total TX Power (W)	ERP (W)	MPE %
Antenna A1	JMA MX08FRO665-21	600 MHz / 1900 MHz (PCS) / 2100 MHz (AWS)	11.45 / 16.15 / 16.65	12	566	17,426.72	12.08
Sector A Composite MPE%							12.08
Antenna B1	JMA MX08FRO665-21	600 MHz / 1900 MHz (PCS) / 2100 MHz (AWS)	11.45 / 16.15 / 16.65	12	566	17,426.72	12.08
Sector B Composite MPE%							12.08
Antenna C1	JMA MX08FRO665-21	600 MHz / 1900 MHz (PCS) / 2100 MHz (AWS)	11.45 / 16.15 / 16.65	12	566	17,426.72	12.08
Sector C Composite MPE%							12.08

Table 3: Dish Emissions Levels



The Following table (*table 4*) shows all additional carriers on site and their MPE% as recorded in the CSC active MPE database for this facility along with the newly calculated maximum **Dish** MPE contributions per this report. FCC OET 65 specifies that for carriers utilizing directional antennas that the highest recorded sector value be used for composite site MPE values due to their greatly reduced emissions contributions in the directions of the adjacent sectors. For this site, all three sectors have the same configuration yielding the same results on all three sectors. *Table 5* below shows a summary for each **Dish** Sector as well as the composite MPE value for the site.

Site Composite MPE%	
Carrier	MPE%
Dish – Max Per Sector Value	12.08 %
AT&T	24.68 %
Site Total MPE %:	36.76 %

Table 4: All Carrier MPE Contributions

Dish Sector A Total:	12.08 %
Dish Sector B Total:	12.08 %
Dish Sector C Total:	12.08 %
Site Total:	36.76 %

Table 5: Site MPE Summary



FCC OET 65 specifies that for carriers utilizing directional antennas that the highest recorded sector value be used for composite site MPE values due to their greatly reduced emissions contributions in the directions of the adjacent sectors. *Table 6* below details a breakdown by frequency band and technology for the MPE power values for the maximum calculated **Dish** sector(s). For this site, all three sectors have the same configuration yielding the same results on all three sectors.

Dish _ Frequency Band / Technology Max Power Values (Per Sector)	# Channels	Watts ERP (Per Channel)	Height (feet)	Total Power Density ($\mu\text{W}/\text{cm}^2$)	Frequency (MHz)	Allowable MPE ($\mu\text{W}/\text{cm}^2$)	Calculated % MPE
Dish 600 MHz 5G	4	858.77	88	18.37	600 MHz	400	4.59%
Dish 1900 MHz (PCS) 5G	4	1,648.39	88	35.25	1900 MHz (PCS)	1000	3.53%
Dish 2100 MHz (AWS) 5G	4	1,849.52	88	39.55	2100 MHz (AWS)	1000	3.96%
						Total:	12.08%

Table 6: Dish Maximum Sector MPE Power Values



Summary

All calculations performed for this analysis yielded results that were **within** the allowable limits for general population exposure to RF Emissions.

The anticipated maximum composite contributions from the Dish facility as well as the site composite emissions value with regards to compliance with FCC's allowable limits for general population exposure to RF Emissions are shown here:

Dish Sector	Power Density Value (%)
Sector A:	12.08 %
Sector B:	12.08 %
Sector C:	12.08 %
Dish Maximum Total (per sector):	12.08 %
Site Total:	36.76 %
Site Compliance Status:	COMPLIANT

The anticipated composite MPE value for this site assuming all carriers present is **36.76 %** of the allowable FCC established general population limit sampled at the ground level. This is based upon values listed in the Connecticut Siting Council database for existing carrier emissions.

FCC guidelines state that if a site is found to be out of compliance (over allowable thresholds), that carriers over a 5% contribution to the composite value will require measures to bring the site into compliance. For this facility, the composite values calculated were well within the allowable 100% threshold standard per the federal government.


Scott Heffernan
Principal RF Engineer
Fox Hill Telecom, Inc
Holden, MA 01520
(978)660-3998

Exhibit G

Letter of Authorization

Exhibit H

Recipient Mailings



USPS TRACKING #

9405 5036 9930 0136 9851 88

Electronic Rate Approved #038555749

SHIP TO: KATHLEEN A BLONSKI
 FARMINGTON TOWN HALL- TOWN MANAGER
 1 MONTIETH DR
 FARMINGTON CT 06032-1082

P

US POSTAGE
 Flat Rate Env
 \$8.95

U.S. POSTAGE PAID
click-n-ship®

Mailed from 01566

PRIORITY MAIL 2-DAY™

Expected Delivery Date: 01/19/22
 Ref#: DD-00107A
0006

R001

DEBORAH CHASE
 NORTHEAST SITE SOLUTIONS
 420 MAIN ST
 STE 1
 STURBRIDGE MA 01566-1359

Click-N-Ship®

usps.com
 9405 5036 9930 0136 9851 88 0089 5000 0010 6032

01/14/2022



Cut on dotted line.

Instructions

1. Each Click-N-Ship® label is unique. Labels are to be used as printed and used only once. DO NOT PHOTO COPY OR ALTER LABEL.
2. Place your label so it does not wrap around the edge of the package.
3. Adhere your label to the package. A self-adhesive label is recommended. If tape or glue is used, DO NOT TAPE OVER BARCODE. Be sure all edges are secure.
4. To mail your package with PC Postage®, you may schedule a Package Pickup online, hand to your letter carrier, take to a Post Office™, or drop in a USPS collection box.
5. Mail your package on the "Ship Date" you selected when creating this label.

Click-N-Ship® Label Record

USPS TRACKING # :
9405 5036 9930 0136 9851 88

Trans. #: 554115270	Priority Mail® Postage: \$8.95
Print Date: 01/14/2022	Total: \$8.95
Ship Date: 01/14/2022	
Expected Delivery Date: 01/19/2022	


From: DEBORAH CHASE Ref#: DD-00107A
 NORTHEAST SITE SOLUTIONS
 420 MAIN ST
 STE 1
 STURBRIDGE MA 01566-1359

To: KATHLEEN A BLONSKI
 FARMINGTON TOWN HALL- TOWN MANAGER
 1 MONTIETH DR
 FARMINGTON CT 06032-1082

* Retail Pricing Priority Mail rates apply. There is no fee for USPS Tracking® service on Priority Mail service with use of this electronic rate shipping label. Refunds for unused postage paid labels can be requested online 30 days from the print date.



Thank you for shipping with the United States Postal Service!
 Check the status of your shipment on the USPS Tracking® page at usps.com



USPS TRACKING #

9405 5036 9930 0136 9851 95

Electronic Rate Approved #038555749

SHIP TO: SHANNON RUTHERFORD
CTING TOWN PLANNER-FARMINGTON
1 MONTIETH DR
FARMINGTON CT 06032-1082

P

PRIORITY MAIL 2-DAY™

Expected Delivery Date: 01/19/22
Ref#: DD-00107A
0006

R001

Click-N-Ship®

U.S. POSTAGE PAID

USPS.com 9405 5036 9930 0136 9851 95 0089 5000 0010 6032
US POSTAGE Flat Rate Env
Mailed from 01566
01/14/2022



Cut on dotted line.

Instructions

1. Each Click-N-Ship® label is unique. Labels are to be used as printed and used only once. DO NOT PHOTO COPY OR ALTER LABEL.
2. Place your label so it does not wrap around the edge of the package.
3. Adhere your label to the package. A self-adhesive label is recommended. If tape or glue is used, DO NOT TAPE OVER BARCODE. Be sure all edges are secure.
4. To mail your package with PC Postage®, you may schedule a Package Pickup online, hand to your letter carrier, take to a Post Office™, or drop in a USPS collection box.
5. Mail your package on the "Ship Date" you selected when creating this label.

Click-N-Ship® Label Record

USPS TRACKING # :
9405 5036 9930 0136 9851 95

Trans. #: 554115270	Priority Mail® Postage: \$8.95
Print Date: 01/14/2022	Total: \$8.95
Ship Date: 01/14/2022	
Expected Delivery Date: 01/19/2022	

From: DEBORAH CHASE
NORTHEAST SITE SOLUTIONS
420 MAIN ST
STE 1
STURBRIDGE MA 01566-1359


Ref#: DD-00107A

To: SHANNON RUTHERFORD
CTING TOWN PLANNER-FARMINGTON
1 MONTIETH DR
FARMINGTON CT 06032-1082

* Retail Pricing Priority Mail rates apply. There is no fee for USPS Tracking® service on Priority Mail service with use of this electronic rate shipping label. Refunds for unused postage paid labels can be requested online 30 days from the print date.



Thank you for shipping with the United States Postal Service!
Check the status of your shipment on the USPS Tracking® page at usps.com



UNITED STATES POSTAL SERVICE®

Click-N-Ship®

P

usps.com 9405 5036 9930 0136 9852 01 0089 5000 0020 6851
US POSTAGE
 Flat Rate Envoy

U.S. POSTAGE PAID
click-n-ship®

01/14/2022 Mailed from 01566

PRIORITY MAIL 2-DAY™


Expected Delivery Date: 01/19/22
 Ref#: DD-00107A
0006

DEBORAH CHASE
 NORTHEAST SITE SOLUTIONS
 420 MAIN ST
 STE 1
 STURBRIDGE MA 01566-1359

C007

SHIP TO:
 SOUTHERN NEW ENGLAND
 401 MERRITT 7
 NORWALK CT 06851-1000

USPS TRACKING #



9405 5036 9930 0136 9852 01

Electronic Rate Approved #038555749



Cut on dotted line.

Instructions

1. Each Click-N-Ship® label is unique. Labels are to be used as printed and used only once. DO NOT PHOTO COPY OR ALTER LABEL.
2. Place your label so it does not wrap around the edge of the package.
3. Adhere your label to the package. A self-adhesive label is recommended. If tape or glue is used, DO NOT TAPE OVER BARCODE. Be sure all edges are secure.
4. To mail your package with PC Postage®, you may schedule a Package Pickup online, hand to your letter carrier, take to a Post Office™, or drop in a USPS collection box.
5. Mail your package on the "Ship Date" you selected when creating this label.

Click-N-Ship® Label Record

USPS TRACKING # :
9405 5036 9930 0136 9852 01

Trans. #: 554115270	Priority Mail® Postage: \$8.95
Print Date: 01/14/2022	Total: \$8.95
Ship Date: 01/14/2022	
Expected Delivery Date: 01/19/2022	


From: DEBORAH CHASE Ref#: DD-00107A
 NORTHEAST SITE SOLUTIONS
 420 MAIN ST
 STE 1
 STURBRIDGE MA 01566-1359

To: SOUTHERN NEW ENGLAND
 401 MERRITT 7
 NORWALK CT 06851-1000

* Retail Pricing Priority Mail rates apply. There is no fee for USPS Tracking® service on Priority Mail service with use of this electronic rate shipping label. Refunds for unused postage paid labels can be requested online 30 days from the print date.



Thank you for shipping with the United States Postal Service!
 Check the status of your shipment on the USPS Tracking® page at usps.com



**UNITED STATES
POSTAL SERVICE®**

Click-N-Ship®

P

usps.com 9405 5036 9930 0136 9852 18 0089 5000 0041 5212
US POSTAGE
 Flat Rate Env
 01/14/2022

U.S. POSTAGE PAID
Click-N-Ship®

Mailed from 01566


PRIORITY MAIL 2-DAY™

Expected Delivery Date: 01/19/22
 Ref#: DD-00107A
0006

C002

SHIP TO: EIP COMMUNICATIONS LLC
 2 ALLEGHENY CTR
 STE 703
 PITTSBURGH PA 15212-5402

USPS TRACKING #



9405 5036 9930 0136 9852 18

Electronic Rate Approved #038555749



Cut on dotted line.

Instructions

1. Each Click-N-Ship® label is unique. Labels are to be used as printed and used only once. DO NOT PHOTO COPY OR ALTER LABEL.
2. Place your label so it does not wrap around the edge of the package.
3. Adhere your label to the package. A self-adhesive label is recommended. If tape or glue is used, DO NOT TAPE OVER BARCODE. Be sure all edges are secure.
4. To mail your package with PC Postage®, you may schedule a Package Pickup online, hand to your letter carrier, take to a Post Office™, or drop in a USPS collection box.
5. Mail your package on the "Ship Date" you selected when creating this label.

Click-N-Ship® Label Record

USPS TRACKING # :
9405 5036 9930 0136 9852 18

Trans. #: 554115270	Priority Mail® Postage: \$8.95
Print Date: 01/14/2022	Total: \$8.95
Ship Date: 01/14/2022	
Expected	
Delivery Date: 01/19/2022	

From: DEBORAH CHASE
 NORTHEAST SITE SOLUTIONS
 420 MAIN ST
 STE 1
 STURBRIDGE MA 01566-1359

Ref#: DD-00107A

To: EIP COMMUNICATIONS LLC
 2 ALLEGHENY CTR
 STE 703
 PITTSBURGH PA 15212-5402

* Retail Pricing Priority Mail rates apply. There is no fee for USPS Tracking® service on Priority Mail service with use of this electronic rate shipping label. Refunds for unused postage paid labels can be requested online 30 days from the print date.



Thank you for shipping with the United States Postal Service!
 Check the status of your shipment on the USPS Tracking® page at usps.com

DOBOL UNITA



UNIONVILLE
24 MILL ST
UNIONVILLE, CT 06085-9998
(800)275-8777

01/18/2022

03:25 PM

Product	Qty	Unit Price	Price
Prepaid Mail Farmington, CT 06032 Weight: 0 lb 7.50 oz Acceptance Date: Tue 01/18/2022 Tracking #: 9405 5036 9930 0136 9851 88	1		\$0.00
Prepaid Mail Pittsburgh, PA 15212 Weight: 0 lb 7.50 oz Acceptance Date: Tue 01/18/2022 Tracking #: 9405 5036 9930 0136 9852 18	1		\$0.00
Prepaid Mail Farmington, CT 06032 Weight: 0 lb 7.40 oz Acceptance Date: Tue 01/18/2022 Tracking #: 9405 5036 9930 0136 9851 95	1		\$0.00
Prepaid Mail Norwalk, CT 06851 Weight: 0 lb 7.50 oz Acceptance Date: Tue 01/18/2022 Tracking #: 9405 5036 9930 0136 9852 01	1		\$0.00
Grand Total:			\$0.00