

PULLMAN & COMLEY, LLC
ATTORNEYS AT LAW

EM-POCKET-054-080930

CARRIE L. LARSON
90 State House Square
Hartford, CT 06103-3702
p (860) 424-4312
f (860) 424-4370


www.pullcom.com

September 29, 2008

Via Federal Express

S. Derek Phelps, Executive Director
Connecticut Siting Council
Ten Franklin Square
New Britain, CT 06051

ORIGINAL



Re: Notice of Exempt Modification
Cox Communications Telecommunications Facility
577 Bell Street, Glastonbury, Connecticut

Dear Mr. Phelps:

Youghiogheny Communications-Northeast, LLC, doing business as Pocket Communications ("Pocket"), intends to install antennas and appurtenant equipment at the existing 90-foot lattice facility owned by Cox Communications and located at 577 Bell Street, Glastonbury, Connecticut ("Facility"). Pocket Communications provides prepaid, flat rate wireless voice and data services to more than a quarter of a million subscribers. Pocket is licensed by the Federal Communications Commission (FCC) to provide PCS wireless telecommunications service in the State of Connecticut, which includes the area to be served by the proposed installation. This installation constitutes an exempt modification pursuant to the Public Utility Environmental Standards Act, Connecticut General Statutes Section 16-50g et. seq. (PUESA), and Section 16-50j-72(b)(2) of the Regulations of the Connecticut State Agencies adopted pursuant to PUESA. In accordance with R.C.S.A. Section 16-50j-73, a copy of this notice has been sent to Richard J. Johnson, Town Manager, Town of Glastonbury.

The existing Facility consists of a 90-foot self-supporting monopole tower capable of supporting multiple carriers within a fenced compound. The coordinates for the Facility are **Lat: 41°-43'-45" and Long: 72°-33'-00"**. The tower is located in the northern portion of Glastonbury, roughly 2,400 feet south of the Manchester town line. The Facility is approximately 200 feet west of Bell Street, and approximately 4,800 feet north of Hebron Avenue (Route 94) (see Site Map, attached as Exhibit A). The tower currently supports AT&T antennas at the eighty eight foot (88') level centerline AGL (above ground level). Cox Communications and the Town of Glastonbury have whip style antennas at multiple elevations, listed in the application materials. Pocket proposes to install three APXV 18-206517S-C panel antennas to the tower legs at the sixty five foot centerline (65') AGL, and a Nortel CDMA Micro BTS 3231 cabinet, mounted on an "H-Frame," contained within a six foot by six foot (6'-0" x 6'-0") lease area. A small GPS antenna will be mounted to an ice bridge which will run from the

Page 2

lease area to the tower. Utilities will be run via a proposed underground conduit from an existing utility pole (SNET 2053) on Bell Street to the east (See Design Drawings and Equipment Specifications, attached as Exhibits B and C respectively).

For the following reasons, the proposed modifications to the Bell Street Facility meet the exempt modification criteria set forth in R.C.S.A. Section 16-50j-72(b)(2):

1. The proposed modification will not increase the height of the tower as Pocket's antennas will be installed at a center line height of approximately 65 feet.
2. The installation of Pocket's equipment and shelter will not require an extension of the site boundaries.
3. The proposed modifications will not increase the noise levels at the existing Facility by six decibels or more.
4. The operation of the additional antennas will not increase the total radio frequency (RF) power density, measured at the site boundary, to a level at or above the standard adopted by the Connecticut Department of Environmental Protection as set forth in Section 22a-162 of the Connecticut General Statutes and MPE limits established by the Federal Communications Commission. The worst-case RF power density calculations for the proposed Pocket antennas would be 44.85% of the FCC standard (see general power density calculations table, attached as Exhibit D).

Also attached, Exhibit E, is a structural analysis confirming that the tower can support the existing and proposed antennas and associated equipment.

For the foregoing reasons, Pocket respectfully submits that the proposed antenna installation and equipment at the Glastonbury Facility constitutes an exempt modification under R.C.S.A. Section 16-50j-72(b)(2)

Respectfully Submitted,



Carrie L. Larson

cc: Richard J. Johnson, Town Manager
John B. Spencer, Trustee, underlying property owner

Exhibit A

Site Map

Pocket Site HFCT1514A

577 Bell Street

Glastonbury, Connecticut




Exhibit B

Design Drawings

Pocket Site HFCT1514A

577 Bell Street

Glastonbury, Connecticut

PROJECT INFORMATION	
TOWER OWNER:	COX COMMUNICATIONS 1400 LAKE MEAD DRIVE ATLANTA, GA 30319
OWNER SITE ID#:	N/A
APPLICANT:	YOUNGROBERTSON COMMUNICATIONS- NORTHEAST LLC 500 ENTERPRISE DRIVE, SUITE 300 SAN ANTONIO, TX 78230
SITE ADDRESS:	577 BELL STREET GLASTONBURY, CT 06033
COUNTY:	HARTFORD
LATITUDE:	41.7336°
LONGITUDE:	-72.5488°
STRUCTURE HEIGHT:	90' AGL
ZONING CLASSIFICATION:	N/A
CONNECTION SITING COUNCIL:	
POWER COMPANY:	CL&P 1-860-947-2121
TELEPHONE COMPANY:	AT&T 1-888-727-8368
DESIGN FIRM:	URS CORPORATION AES 500 ENTERPRISE DRIVE, SUITE 300 SAN ANTONIO, TX 78230 PHONE: 866-529-8882

DRAWING INDEX	
01	TITLE SHEET
02	SITE PLAN, DETAILS AND NOTES
03	TOWER ELEVATION, ANTENNA PLAN AND DETAILS
04	GROUNDING DETAILS
05	GROUNDING PLAN AND DETAILS
06	ELECTRICAL DETAILS


STRUCTURAL REVIEW
A TOWER ANALYSIS HAS NOT BEEN PERFORMED FOR THE PREPARATION OF THESE PLANS. AS OF THE ISSUANCE OF THESE DRAWINGS, THE EXISTING TOWER HAS NOT BEEN EVALUATED FOR REPLACEMENT/ADDITION OF ANOTHER TOWER PRIOR TO THE ISSUANCE OF A PASSING STRUCTURAL TOWER ANALYSIS. A COPY OF THE TOWER ANALYSIS SHALL BE FORWARDED TO URS CORPORATION. ALL REINFORCEMENT (IF REQUIRED) SHALL BE PERFORMED PRIOR TO ANY WORK UNDER THIS CONTRACT BEING PERFORMED.

APPROVALS
REAL ESTATE
RF
OPS/CONSTRUCTION
LEGAL/COMPLIANCE
NET DESIGN

SMART WIRELESS

HFCT1514 **577 BELL STREET** **90' LATTICE TOWER**

LOCATION MAP



DRIVING DIRECTIONS

FROM HARTFORD:
TAKE I-84 EAST TO EXIT #55 FOR CT-2 EAST TOWARD NORWICH/NEW LONDON. TAKE THE HEBRON AVENUE/CT-84 EXIT #8.
TURN SLIGHT LEFT ONTO HEBRON AVENUE/CT-84. TURN LEFT ONTO BELL STREET.

APPLICABLE BUILDING CODES AND STANDARDS

CONTRACTOR'S WORK SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE, AND LOCAL CODES AS ADOPTED BY THE LOCAL AUTHORITY HAVING JURISDICTION (LAW) FOR THE LOCATION. THE CODES OF THE AIA ADOPTED CODES AND STANDARDS IN EFFECT ON THE DATE OF CONTRACT AWARD SHALL GOVERN THE DESIGN.

- BUILDING CODE:
- CONNECTICUT STATE BUILDING CODE
- 2003 INTERNATIONAL PLUMBING CODE
- 2003 INTERNATIONAL MECHANICAL CODE
- 2003 INTERNATIONAL EXISTING BUILDING CODE
- 2003 CONNECTICUT SUPPLEMENT
- ELECTRICAL CODE:
- 2005 NATIONAL ELECTRICAL CODE
- CONNECTICUT STATE FIRE SAFETY CODE
- 2003 INTERNATIONAL FIRE CODE

CONTRACTOR'S WORK SHALL COMPLY WITH THE LATEST APPROVED EDITION OF THE FOLLOWING STANDARDS:

- AMERICAN CONCRETE INSTITUTE (ACI) 318, BUILDING CODE REQUIREMENTS FOR STRUCTURAL
- AMERICAN INSTITUTE OF STEEL CONSTRUCTION (AISC), MANUAL OF STEEL CONSTRUCTION, ASD, NINTH EDITION
- TELECOMMUNICATIONS INDUSTRY ASSOCIATION (TIA) 222-F, STRUCTURAL STANDARD FOR STRUCTURAL ANTENNA TOWER AND ANTENNA SUPPORTING STRUCTURES
- FOR 607 COMMERCIAL BUILDING GROUNDING AND BONDING REQUIREMENTS FOR TELECOMMUNICATIONS
- INSTITUTE FOR ELECTRICAL AND ELECTRONICS ENGINEERS (IEEE) 81, GUIDE FOR MEASURING RESISTIVITY, GROUND IMPEDANCE, AND EARTH SURFACE POTENTIALS OF A GROUND SYSTEM
- IEEE 1100 (1999) RECOMMENDED PRACTICE FOR POWERING AND GROUNDING OF ELECTRONIC EQUIPMENT
- IEEE C92.41, RECOMMENDED PRACTICES ON SURGE VOLTAGES IN LOW VOLTAGE AC POWER CIRCUITS (FOR LOCATION CATEGORY "C3" AND "HIGH SYSTEM EXPOSURE")
- TELECOMORCA GR-1275 GENERAL INSTALLATION REQUIREMENTS
- TELECOMORCA GR-1503 COAXIAL CABLE CONNECTIONS
- ANSI T1.311, FOR TELECOM - DC POWER SYSTEMS - TELECOM ENVIRONMENTAL PROTECTION

FOR ANY CONFLICTS BETWEEN SECTIONS OF LISTED CODES AND STANDARDS REGARDING REQUIREMENT SHALL GOVERN, WHERE THERE IS CONFLICT BETWEEN A GENERAL REQUIREMENT AND A SPECIFIC REQUIREMENT, THE SPECIFIC REQUIREMENT SHALL GOVERN.

SITE NOTES

- THIS SITE IS UNMANNED AND IS RESTRICTED TO OUTDOOR EQUIPMENT. IT WILL BE USED FOR THE TRANSMISSION OF RADIO SIGNALS FOR THE PURPOSE OF PROVIDING PUBLIC CELLULAR SERVICE.
- POCKET COMMUNICATIONS CERTIFIES THAT THIS TELEPHONE EQUIPMENT FACILITY WILL BE SERVICED ONLY BY POCKET COMMUNICATIONS EMPLOYEES AND THE WORK ASSOCIATED WITH THE FACILITY WILL BE PERFORMED ONLY BY SERVICE PERSONNEL FOR REPAIR PURPOSES ONLY. THIS FACILITY IS EXEMPT FROM THE REQUIREMENTS OF THE AMERICANS WITH DISABILITIES ACT (ADA) APPENDIX B, SECTION 4.11.6(B).
- NO POTABLE WATER SUPPLY IS TO BE PROVIDED AT THIS LOCATION.
- NO WASTE WATER WILL BE GENERATED AT THIS LOCATION.
- NO SOLID WASTE WILL BE GENERATED AT THIS LOCATION.
- AVERAGE OF ONE TRIP PER MONTH AT ONE HOUR PER VISIT.

 HFCT1514, 577 BELL STREET		01
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF URS CORPORATION. IT IS TO BE USED ONLY FOR THE PROJECT AND SITE SPECIFICALLY IDENTIFIED HEREIN. IT IS NOT TO BE REPRODUCED WITHOUT THE WRITTEN PERMISSION OF URS CORPORATION.		URS
PROJECT NO. CT-150007 DRAWING NO. CT-150007		DATE: 09/26/08 DESIGNED BY: JCF CHECKED BY: JCF PROJECT NO. CT-150007



1. FIELD VERIFICATION: CONTRACTOR SHALL FIELD VERIFY SCOPE OF WORK, POCKET COMMUNICATIONS ANTENNA MOUNT LOCATION AND ANTENNAS TO BE INSTALLED.
2. COORDINATION OF WORK: CONTRACTOR SHALL COORDINATE RF WORK AND PROCEDURES WITH POCKET COMMUNICATIONS.
3. GRAVEL SURFACES IN AREAS OF COMPOUND THAT ARE DISTURBED DURING CONSTRUCTION SHALL BE REPLACED TO ORIGINAL CONDITION BY CONTRACTOR.


1. FOR THE PURPOSE OF CONSTRUCTION DRAWING, THE FOLLOWING DEFINITIONS SHALL APPLY:
OWNER – PROJECT COMMUNICATIONS
OWNER – ORIGINAL EQUIPMENT MANUFACTURER
GENERAL CONTRACTOR – THE PERSON OR FIRM PRIOR TO THE SUBMISSION OF THIS BID, WHO IS TO BECOME FAMILIAR WITH THE EXISTING CONDITIONS AND TO CONFIRM THAT THE WORK CAN BE ACCOMPLISHED AS SHOWN ON THE DRAWINGS.
DISCREPANCY RESOLUTION SHALL BE BROUGHT TO THE ATTENTION OF THE CONSTRUCTION MANAGER AND THE EMPLOYER.
2. ALL MATERIALS FURNISHED AND INSTALLED SHALL BE IN ACCORDANCE WITH THE SPECIFICATIONS, CODES, REGULATIONS, AND ORDINANCES. CONTRACTOR SHALL ISSUE ALL APPROPRIATE NOTICES AND COMPLY WITH ALL LAWS, ORDINANCES, RULES, REGULATIONS, AND LAWFUL ORDERS OF THE AGENCIES AUTHORIZING THE PERFORMANCE OF THE WORK.
- 3.

THIS SITE PLAN DRAWING WAS COMPILED FROM DATA PROVIDED BY GRAPEVINE SOLUTIONS AND AVAILABLE EXISTING DRAWINGS OF THE SUBJECT AREA.


NOTE:
REFER TO DRAWING 06 FOR
ADDITIONAL UTILITY INFORMATION

8. THE CONTRACTOR SHALL PROTECT EXISTING IMPROVEMENTS, PAVEMENTS, CURBS, LANDSCAPING AND STRUCTURES. ANY DAMAGED PART SHALL BE REPAIRED AT CONTRACTOR'S EXPENSE TO THE SATISFACTION OF OWNER.
9. CONTRACTOR SHALL LEGALLY AND PROPERLY DISPOSE OF ALL SCRAP MATERIALS SUCH AS COAXIAL CABLES AND OTHER ITEMS REMOVED FROM THE EXISTING FACILITY. ANTENNAS REMOVED SHALL BE RETURNED TO THE OWNER'S DESIGNATED LOCATION.
10. CONTRACTOR TO OBTAIN REQUIRED NOTICE TO PROCEED DOCUMENTS FROM THE LOWER OWNER BEFORE COMMENCING CONSTRUCTION.

THIS SITE PLAN DRAWING WAS COMPILED FROM DATA PROVIDED BY GRAPEVINE SOLUTIONS AND AVAILABLE EXISTING DRAWINGS OF THE SUBJECT AREA.



1 COMPOUND PLAN
02 SCALE: 1" = 10'-0"



VERTICAL CABLE LADDER DETAIL



URS

THE COMPARTMENT ACT
800 ENTERPRISE DRIVE
ROCKY HILL, CT. 06067

PC102H/15823848	DATE	09/05/08	PCF
UNIT 1000	DATE IN	PD	

20

pocket.
MANY WIRELESS
HHFCT1514, 677 BELL STREET

THE INFORMATION
CONTAINED IN THIS
DOCUMENT, AND THE
DOCUMENT ITSELF, IS
PROPRIETARY, BELONGING
TO LMS CORPORATION.
THIS DOCUMENT IS NOT
TO BE USED OR
REPRODUCED WITHOUT
WRITTEN PERMISSION OF
LMS CORPORATION.

EXISTING WHIP ANTENNA

TOP OF TOWER = 90'-0"

EXISTING CIRCULAR ANTENNA

EXISTING TOWNS ANTENNAS

ANTENNA CENTERLINE = 65'-0"

POCKET WIRELESS ANTENNAS (TYP. OF 3)

POCKET WIRELESS COAX ROUTED UP EXISTING LATTICE TOWER.


EXISTING 90'-0" LATTICE TOWER

1 TOWER ELEVATION

ANTENNA KEY												
	ANTENNAS PER SECTOR	ANTENNA NUMBER	COAX COLOR CODE	ANTENNA VENDOR	MODEL NUMBER	AZIMUTH	C/L HEIGHT	MECHANICAL DOWNTILT*	ELECTRICAL DOWNTILT*	COAX SIZE	CABLES PER ANTENNA	COAX MANUFACTURER
ALPHA	1	A-1	(1) RED BAND	RFS	APXV18- 2065175-C	30°	120'-0"	0°	0°	1 5/8"	2 @ 80'	RFS
BETA	1	B-1	(1) BLUE BAND	RFS	APXV18- 2065175-C	150°	120'-0"	0°	0°	1 5/8"	2 @ 80'	RFS
GAMMA	1	C-1	(1) GREEN BAND	RFS	APXV18- 2065175-C	270°	120'-0"	0°	0°	1 5/8"	2 @ 80'	RFS


3. PRIOR TO ORDERING ANY ANTENNAS OR CONTACT POCKETS, CONTRACTOR SHALL CONTACT POCKETS CONSTRUCTION MANAGER AND OBTAIN A LIST OF MATERIALS LISTED. CONTRACTOR IS RESPONSIBLE FOR THIS COORDINATION.

2 ANTENNA SECTOR PLAN




*REFER TO RFDS ANTENNA SHEET FOR FINAL TILT AND AZIMUTHS

2 ANTENNA SECTOR PLAN



3	CABINET
07	SCALE: N.T.S.

CABINET SUPPORT FRAME



URS

100 ENTERPRISE DRIVE
ROCKY HILL, CT. 06067

PC1028/38823048	09/05/08	PD	JCF
-----------------	----------	----	-----

03

7/21/1914, 97 BELL STREET

Smart Winkles
Smart Winkles
Smart Winkles

THE INFORMATION
OBTAINED IN THIS
DOCUMENT, AND THE
DOCUMENT ITSELF, IS
PROPRIETARY, BELONGING
TO LRS CORPORATION.
THIS DOCUMENT IS NOT
TO BE USED OR
REPRODUCED WITHOUT
WRITTEN PERMISSION OF
LRS CORPORATION




Exhibit C

Equipment Specifications

Pocket Site HFCT1514A


577 Bell Street

Glastonbury, Connecticut



Product Description

This variable tilt antenna provides exceptional suppression of all upper sidelobes at all downtilt angles. It also features null fill and a wide downtilt range with optional remote tilt.



Features/Benefits

- Variable electrical downtilt - provides enhanced precision in controlling intercell interference. The tilt is infield adjustable 0-10 deg.
- High Suppression of all Upper Sidelobes (Typically <-20dB).
- Optional remote tilt - can be retrofitted.
- Broadband design.
- Dual polarization.
- Low profile for low visual impact.

Technical Features



Frequency Band	3G/UMTS (Single, Broad, Dual and Triple-Band)
Horizontal Pattern	Directional
Antenna Type	Panel Dual Polarized
Electrical Down Tilt Option	Variable




Gain, dBi (dBd)	18.8 (16.7) , 19.0 (16.9)
Frequency Range, MHz	1710-1900, 1900-2170
Connector Type	(2) 7-16 DIN Female
Connector Location	Bottom
Mount Type	Downtilt
Electrical Downtilt, deg	0-10
Horizontal Beamwidth, deg	67 , 63
Mounting Hardware	APM40-2
Rated Wind Speed, km/h (mph)	160 (100)
VSWR	< 1.5:1
Vertical Beamwidth, deg	5.0 , 4.6
Upper Sidelobe Suppression, dB	> 17 , >18 all (Typically >20)
Polarization	Dual pol +/-45°
Front-To-Back Ratio, dB	>30
Maximum Power Input, W	300
Isolation between Ports, dB	>30
Lightning Protection	Direct Ground
3rd Order IMP @ 2 x 43 dBm, dBc	>150
7th Order IMP @ 2x46 dBm, dBc	>170
Impedance, Ohms	50
Overall Length, m (ft)	1.85 (6.06)
Mounting Hardware Weight, kg (lb)	3.4 (7.5)
Dimensions - HxWxD, mm (in)	1850 x 175 x 80 (72.0 x 6.8 x 3.15)
Weight w/o Mtg Hardware, kg (lb)	12 (26.4)
Weight w/ Mtg Hardware, kg (lb)	14.8 (32.5)
Radiating Element Material	Brass
Radome Color	Light Grey RAL7035
Radome Material	Fiberglass
Mounting Hardware Material	Diecasted Aluminum
Reflector Material	Aluminum
Max Wind Loading Area, m ² (ft ²)	0.31 (3.3)
Survival Wind Speed, km/h (mph)	200 (125)
Maximum Thrust @ Rated Wind, N (lbf)	558 (125)
Front Thrust @ Rated Wind, N (lbf)	558 (125)
Shipping Weight, kg (lb)	18.3 (39.8)
Packing Dimensions, HxWxD, mm (in)	2021 x 260 x 200 (79.5 x 10.2 x 7.8)
Packing Dimensions - HxWxD, m (ft)	2.0 x 0.26 x 0.2 (6.6 x 0.85 x 0.65)

Notes

For additional mounting information please click "External Document Link" below.





Pocket/Youghiogheny Communications – Northeast, LLC
 Rack Detail



CDMA BTS 3231 AWS 1.7/2.1 GHz (Outdoor/Indoor)

CDMA BTS 3231

Industry's Highest Capacity AWS Micro BTS

The CDMA BTS 3231 is the latest extension to Nortel Networks BTS (Base Transceiver Station) portfolio providing the ideal solution for urban, sub-urban and rural deployments. The CDMA BTS 3231 is a 3-carrier, 3-sector outdoor/indoor BTS operating at the AWS band of 1.7/2.1 GHz supporting IS-95, 1XRTT and 1xEV-DO simultaneously. BTS 3231 provides flexible deployments solutions including floor, rack, and wall mount options. The power consumption of BTS3231 is industry leading consuming only 630W for 3C3S. The BTS 3231 is also very light at 240lbs making it easy

to transport to hard to reach locations such as the top of a high rise building.




Exhibit D

Power Density Calculations

Pocket Site HFCT1514A

577 Bell Street

Glastonbury, Connecticut



C Squared Systems, LLC
920 Candia Road
Manchester, NH 03109
Phone: (603) 657 9702
E-mail:

support@csquaredsystems.com

Calculated Radio Frequency Emissions



CT-1514

577 Bell Street, Glastonbury, CT

Table of Contents

1. Introduction	1
2. FCC Guidelines for Evaluating RF Radiation Exposure Limits	2
3. RF Exposure Prediction Methods	2
4. Calculation Results	3
5. Conclusion	3
6. Statement of Certification	4
Attachment A: References	5
Attachment B: FCC Limits For Maximum Permissible Exposure (MPE)	6

List of Tables

Table 1: Proposed Carrier Information	3
---	---

1. Introduction

The purpose of this report is to investigate compliance with applicable FCC regulations for the proposed Pocket antennas to be installed on the existing tower at 577 Bell Street, Glastonbury, CT.

These calculations assume that the antennas are operating at 100 percent capacity, that all antenna channels are transmitting simultaneously, and that the radio transmitters are operating at full power. Obstructions (trees, buildings etc.) that would normally attenuate the signal are not taken into account. As a result, the predicted signal levels are much more conservative (higher) than the actual signal levels will be from the finished installation.

Public exposure to radio frequencies is regulated and enforced in units of microwatts per square centimeter (mW/cm^2). The number of mW/cm^2 emitted is called the power density. The general population exposure limit for the cellular band is $0.567\text{--}0.593 \text{ mW}/\text{cm}^2$, and the general population exposure limit for the PCS/AWS band is $1.0 \text{ mW}/\text{cm}^2$. Because each carrier will be using different frequency bands, and each frequency band has different exposure limits, it is necessary to report percent of MPE rather than power density.

The FCC general population / uncontrolled limits set the maximum exposure to which most people may be subjected. General population / uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Higher exposure limits are permitted under the occupational / controlled exposure category, but only for persons who are exposed as a consequence of their employment and who have been made fully aware of the potential for exposure (through training), and they must be able to exercise control over their exposure. General population / uncontrolled limits are five times more stringent than the levels that are acceptable for occupational, or radio frequency trained individuals.”

The FCC describes exposure to radio frequency (RF) energy in terms of percentage of maximum permissible exposure (MPE) with 100% being the maximum allowed. Rather than the FCC presenting the user specification in terms of complex power density figures over a specified surface area, this MPE measure is particularly useful, and even more so when considering that power density limits actually vary by frequency because of the different absorptive properties of the human body at different frequencies.

MPE limits are specified as time-averaged exposure limits. This means that exposure can be averaged over 30 minutes for general population / uncontrolled exposure (or 6 minutes for occupational / controlled exposure). However, for the case of exposure of the general public, time averaging is usually not applied because of uncertainties over exact exposure conditions and difficulty in controlling time of exposure. Therefore, the typical conservative approach is to assume that any RF exposure to the general public will be continuous.

Finally, it should be noted that the MPE limits adopted by the FCC for both general population / uncontrolled exposure and for occupational / controlled exposure incorporate a substantial margin of safety and have been established to be well below levels generally accepted as having the potential to cause adverse health effects.

2. FCC Guidelines for Evaluating RF Radiation Exposure Limits

In 1985, the FCC established rules to regulate radio frequency (RF) exposure from FCC licensed antenna facilities. In 1996, the FCC updated these rules, which were further amended in August 1997 by OET Bulletin 65 Edition 97-01. These new rules include limits for Maximum Permissible Exposure (MPE) for transmitters operating between 300 kHz and 100 GHz. The FCC MPE limits are based on exposure limits recommended by the National Council on Radiation Protection and Measurements (NCRP), the exposure limits developed by the Institute of Electrical and Electronics Engineers, Inc., (IEEE) and adopted by the American National Standards Institute (ANSI).

Attachment B contains excerpts from OET Bulletin 65 and defines the Maximum Exposure Limit. As shown in these excerpts, each frequency band has different exposure limits, requiring power density to be reported as a percent of Maximum Permissible Exposure (MPE) when dealing with carriers transmitting in different frequency bands.

3. RF Exposure Prediction Methods

The emission field calculation results displayed in the following figures were generated using the following formula as outlined in FCC bulletin OET 65:

$$\text{Power Density} = \left(\frac{\text{EIRP}}{\pi \times R^2} \right) \times \text{Off Beam Loss}$$

Where:

EIRP = Effective Isotropic Radiated Power

R = Radial Distance = $\sqrt{H^2 + V^2}$

H = Horizontal Distance from antenna

V = Vertical Distance from bottom of antenna

Off Beam Loss is determined by the selected antenna patterns

4. Calculation Results

Table 1 below outlines the power density information for the site. All information for carriers other than Pocket was obtained from current CSC database.

Carrier	Number of Trans.	Effective Radiated Power (ERP) Per Transmitter (Watts)	Antenna Height (Feet)	Operating Frequency (MHz)	Total ERP (Watts)	Power Density (mw/cm ²)	Limit	%MPE
Town	1	16.829	75	960	17	0.0011	0.6400	0.17%
AT&T GSM	2	296	88	880	592	0.0275	0.5867	4.69%
AT&T GSM	2	427	88	1,930	854	0.0397	1.0000	3.97%
AT&T UMTS	1	500	88	880	500	0.0232	0.5867	3.96%
Cox	1	100	94	451	100	0.0041	0.3007	1.35%
Cox	6	100	70	452	600	0.0440	0.3013	14.61%
Pocket	3	631	65	2130-2133.75	1,893	0.1611	1.0000	16.11%
							Total	44.85%

Table 1: Proposed Carrier Information

5. Conclusion

The above analysis verifies that emissions from the proposed site will be well below the maximum power density levels as outlined by the FCC in the OET Bulletin 65 Ed. 97-01. Even when using conservative methods, the cumulative power density from the proposed transmit antennas at the existing facility is well below the limits for the general public. The highest expected percent of Maximum Permissible Exposure at the base of the tower is 44.85% of the FCC limit.

As noted in the introduction, obstructions (trees, buildings etc.) that would normally attenuate the signal are not taken into account. As a result, the predicted signal levels are more conservative (higher) than the actual signal levels will be from the finished installation.

6. Statement of Certification

I certify to the best of my knowledge that the statements in this report are true and accurate. The calculations follow guidelines set forth in ANSI/IEEE Std. C95.3, ANSI/IEE Std. C95.1 and FCC OET Bulletin 65 Edition 97-01.



Daniel L. Goulet
C Squared Systems, LLC

September 12, 2008
Date

Attachment A: References

OET Bulletin 65 - Edition 97-01 - August 1997 Federal Communications Commission Office of Engineering & Technology

ANSI C95.1-1982, American National Standard Safety Levels With Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 300 kHz to 100 GHz. IEEE-SA Standards Board

IEEE Std C95.3-1991 (Reaff 1997), IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave. IEEE-SA Standards Board

Attachment B: FCC Limits For Maximum Permissible Exposure (MPE)

(A) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (E) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	f/300	6
1500-100,000	-	-	5	6


(B) Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (E) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	f/1500	30
1500-100,000	-	-	1.0	30

f = frequency in MHz * Plane-wave equivalent power density

NOTE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.



• FCC Limits for Maximum Permissible Exposure (MPE)

Exhibit E

Structural Analysis

Pocket Site HFCT1514A

577 Bell Street

Glastonbury, Connecticut

DETAILED STRUCTURAL ANALYSIS AND EVALUATION OF AN EXISTING 92' SELF SUPPORT LATTICE TOWER FOR PROPOSED ANTENNA ARRANGEMENT

Site I.D. HFCT 1514
577 Bell Street
Glastonbury, CT

prepared for



POCKET WIRELESS

2810 NW Loop 410
San Antonio, Texas 06108

prepared by

URS

URS CORPORATION
500 ENTERPRISE DRIVE, SUITE 3B
ROCKY HILL, CT 06067
TEL. 860-529-8882

36923537.00000
PWS-007

September 25, 2008

TABLE OF CONTENTS

- 1. EXECUTIVE SUMMARY**
- 2. INTRODUCTION**
- 3. ANALYSIS METHODOLOGY AND LOADING CONDITIONS**
- 4. FINDINGS AND EVALUATION**
- 5. CONCLUSIONS AND RECOMMENDATIONS**
- 6. DRAWINGS AND DATA**
 - **RISA TOWER INPUT / OUTPUT SUMMARY**
 - **RISA TOWER FEEDLINE DISTRIBUTION**
 - **RISA TOWER FEEDLINE PLAN**
 - **RISA TOWER DETAILED OUTPUT**
 - **ANCHOR BOLT ANALYSIS**

1. EXECUTIVE SUMMARY

This report summarizes the structural analysis of the existing 92' self support ROHN (SSV) lattice tower located at 577 Bell Street in Glastonbury, CT. The analysis was conducted in accordance with the 2005 Connecticut State Building Code and the TIA/EIA-222-F standard for a wind velocity of 80 mph (fastest mile) and 69 mph (fastest mile) concurrent with 1/2" ice. The antenna loading considered in the analysis consists of all existing and proposed antennas, transmission lines, and ancillary items as outlined in the Introduction Section of this report. The proposed Pocket Wireless installation is as follows:

Proposed Antenna and Mount	Carrier	Antenna Center Elevation
Install: (3) RFS APXV18-206517S-C (6) RFS 1-5/8" Coax Cables	Pocket Wireless (Proposed)	@ 65'

The results of the analysis indicate that the tower superstructure steel stresses are within the allowable limits. There was not sufficient information for a foundation analysis. The tower is considered structurally adequate with the wind load classification specified above and the existing and proposed antenna loading.

This analysis is based on:


- 1) The tower structure's theoretical capacity, not including any assessment of the condition of the tower.
- 2) Tower geometry and structural member sizes taken from structural analysis report documents prepared by Paul J. Ford and Company; project number 34804-018, dated 05/14/04 on behalf of Cingular Wireless.
- 3) Field observations noted by URS Corporation conducted during April 2007.
- 4) Antenna and mount configuration as specified on the following page of this report.

This report is only valid as per the assumptions and data utilized in this report for antenna inventory, mounts and associated cables. The user of this report shall field verify the assumption of the antenna and mount configuration as well as the physical condition of the tower and connections. Notify the engineer in writing immediately if any of the information in this report is found to be other than specified.

If you should have any questions, please call.

Sincerely,

URS Corporation


Richard A. Sambor, P.E.
Senior Structural Engineer



RAS/kab

cc: AA, DR, IA, CF/Book - URS

2. INTRODUCTION

The subject tower is located at 577 Bell Street in Glastonbury, CT. The structure is a 92' self support ROHN (SSV) lattice tower.

Tower geometry and structural member sizes taken from structural analysis report documents prepared by Paul J. Ford and Company; project number 34804-018, dated 05/14/04 on behalf of Cingular Wireless.

The inventory is summarized in the table below:

Antenna Type	Carrier	Mount	Antenna Centerline Elevation	Cable
(1) Decibel DB 420 Dipole Quasi - Omni antenna (1) Decibel ASP 705 Omni antenna, (1) Decibel ASPA685 Omni antenna	Unknown (existing)	(3) Leg mounts	* 92'	(3) 7/8" coax cables
(9) CSS DUO1417-8686 antennas and (9) TMA/MHA's	Cingular (existing)	(3) 12' T-frames	88'	(9) 1 5/8" coax cables (bundled in groups of 3 per leg)
(1) Decibel DB806E-XT Omni antenna and (1) Kathrein PR-950 Half Parabolic antenna	Unknown (existing)	(1) 6' Stand-off	73'	(2) 1/2" coax cables
(3) RFS APXV18-206517S-C antenna	Pocket Wireless (proposed)	(3) Leg Mounts	65'	(6) 1-5/8" coax

* Note :Omni-directional antenna elevations taken as base of antenna.

This structural analysis of the communications tower was performed by URS Corporation (URS) for Pocket Wireless. The purpose of this analysis was to investigate the structural integrity of the existing tower with its existing and proposed antenna loads. This analysis was conducted to evaluate stress on the the tower resulting from existing and proposed antenna arrangements.

3. ANALYSIS METHODOLOGY AND LOADING CONDITIONS

The structural analysis was done in accordance with the 2005 Connecticut State Building Code, TIA/EIA-222-F—Structural Standard for Steel Antenna Towers and Antenna Supporting Structures, and the American Institute of Steel Construction (AISC) Manual of Steel Construction—Allowable Stress Design (ASD).

The analysis was conducted using RISA Tower 5.0.2. Two load conditions were evaluated as shown below which were compared to allowable stresses according to AISC and TIA/EIA.

Load Condition 1 = 80 mph (fastest mile) Wind Load (without ice) + Tower Dead Load
Load Condition 2 = 69 mph (fastest mile) Wind Load (with ice) + Ice Load + Tower Dead Load

Please note that wind pressure is a function of velocity squared. Under Load Condition 2, a 25 percent reduction in wind pressure is allowed by code to account for the unlikelihood of the full wind pressure and ice load occurring at the same time. The same results may be achieved by utilizing a lower wind pressure without taking the 25 percent reduction, as shown above.

The TIA/EIA standard permits a one-third increase in allowable stresses for towers and monopoles less than 700 feet tall. For the purposes of this analysis, in computing the load capacity the allowable stresses of the tower members were increased by one-third.

4. FINDINGS AND EVALUATION

Stresses on the tower structure were evaluated to compare with allowable stresses in accordance with AISC. The calculated stresses under the proposed loading were within the allowable stresses. Detailed analysis and calculations for the proposed load conditions are provided in section 6 of this report. No analysis was performed on the foundation since no foundation information was available.

Proposed Tower Base Reactions vs. Paul J. Ford & Co. Design Reactions

Base Reactions	Paul J. Ford & Co. Design Reactions	Proposed Reactions
Axial Load (kips)	-	13
Shear per Leg (kips)	8	8
Total Shear (kips)	-	13
Uplift per Leg (kips)	55	53
Comp. per Leg (kips)	67	62
O.T. Moment (ft-kips)	-	734

Proposed Tower Component Stress vs. Capacity Summary

Component/ (Section No.)	Controlling Component/Elevation	Stress (% capacity)	Pass/Fail	Comments
Tower Leg (T4)	Compression/20'-40'	86.7%	Pass	
Diagonal (T4)	Compression/ 20'-40'	91.6%	Pass	
Top Girt (T1)	Compression/80'-92'	3.4%	Pass	
Anchor Bolts	Min area as req'd per ASCE 10-97	52%	Pass	

5. CONCLUSIONS AND RECOMMENDATIONS

The results of the analysis indicate that the tower superstructure steel stresses within the allowable limits for the proposed loading conditions. The tower is considered structurally adequate with the wind load classification specified above and the existing and proposed antenna loading.

Limitations/Assumptions:

This report is based on the following:

1. Tower inventory as listed in this report.
2. Tower is properly installed and maintained.
3. All members are as specified in the original design documents and are in good condition.
4. All required members are in place.
5. All bolts are in place and are properly tightened.
6. Tower is in plumb condition.
7. All member protective coatings are in good condition.
8. All tower members were properly designed, detailed, fabricated, and installed and have been properly maintained since erection.
9. Foundations were properly constructed to support original design loads as specified in the original design documents.
10. All coaxial cable is installed as specified in Section 6 of this report.

URS is not responsible for any modifications completed prior to or hereafter in which URS is not or was not directly involved. Modifications include but are not limited to:

- A. Adding antennas
- B. Removing/replacing antennas
- C. Adding coaxial cables

URS hereby states that this document represents the entire report and that it assumes no liability for any factual changes that may occur after the date of this report. All representations, recommendations, and conclusions are based upon information contained and set forth herein. If you are aware of any information which conflicts with that which is contained herein, or you are aware of any defects arising from original design, material, fabrication, or erection deficiencies, you should disregard this report and immediately contact URS. URS disclaims all liability for any representation, recommendation, or conclusion not expressly stated herein.

Ongoing and Periodic Inspection and Maintenance:

After the Contractor has successfully completed the installation and the work has been accepted, the owner will be responsible for the ongoing and periodic inspection and maintenance of the tower.

The owner shall refer to TIA/EIA-222-F for recommendations for maintenance and inspection. The frequency of the inspection and maintenance intervals is to be determined by the owner based upon actual site and environmental conditions. It is recommended that a complete and thorough inspection of the entire tower structural system be performed at least yearly and more frequently as conditions warrant. According to TIA/EIA-222-F section 14.1, Note 1: It is recommended that the structure be inspected after severe wind and/or ice storms or other extreme loading conditions.

6. DRAWINGS AND DATA

RISA TOWER INPUT/OUTPUT SUMMARY


Section	T1	T2	T3	T4	T5	T6	T7	T8	T9	T10	T11	T12	T13	T14	T15	T16	T17	T18	T19	T20	T21	T22	T23	T24	T25	T26	T27	T28	T29	T30	T31	T32	T33	T34	T35	T36	T37	T38	T39	T40	T41	T42	T43	T44	T45	T46	T47	T48	T49	T50	T51	T52	T53	T54	T55	T56	T57	T58	T59	T60	T61	T62	T63	T64	T65	T66	T67	T68	T69	T70	T71	T72	T73	T74	T75	T76	T77	T78	T79	T80	T81	T82	T83	T84	T85	T86	T87	T88	T89	T90	T91	T92	T93	T94	T95	T96	T97	T98	T99	T100	T101	T102	T103	T104	T105	T106	T107	T108	T109	T110	T111	T112	T113	T114	T115	T116	T117	T118	T119	T120	T121	T122	T123	T124	T125	T126	T127	T128	T129	T130	T131	T132	T133	T134	T135	T136	T137	T138	T139	T140	T141	T142	T143	T144	T145	T146	T147	T148	T149	T150	T151	T152	T153	T154	T155	T156	T157	T158	T159	T160	T161	T162	T163	T164	T165	T166	T167	T168	T169	T170	T171	T172	T173	T174	T175	T176	T177	T178	T179	T180	T181	T182	T183	T184	T185	T186	T187	T188	T189	T190	T191	T192	T193	T194	T195	T196	T197	T198	T199	T200	T201	T202	T203	T204	T205	T206	T207	T208	T209	T210	T211	T212	T213	T214	T215	T216	T217	T218	T219	T220	T221	T222	T223	T224	T225	T226	T227	T228	T229	T230	T231	T232	T233	T234	T235	T236	T237	T238	T239	T240	T241	T242	T243	T244	T245	T246	T247	T248	T249	T250	T251	T252	T253	T254	T255	T256	T257	T258	T259	T260	T261	T262	T263	T264	T265	T266	T267	T268	T269	T270	T271	T272	T273	T274	T275	T276	T277	T278	T279	T280	T281	T282	T283	T284	T285	T286	T287	T288	T289	T290	T291	T292	T293	T294	T295	T296	T297	T298	T299	T300	T301	T302	T303	T304	T305	T306	T307	T308	T309	T310	T311	T312	T313	T314	T315	T316	T317	T318	T319	T320	T321	T322	T323	T324	T325	T326	T327	T328	T329	T330	T331	T332	T333	T334	T335	T336	T337	T338	T339	T340	T341	T342	T343	T344	T345	T346	T347	T348	T349	T350	T351	T352	T353	T354	T355	T356	T357	T358	T359	T360	T361	T362	T363	T364	T365	T366	T367	T368	T369	T370	T371	T372	T373	T374	T375	T376	T377	T378	T379	T380	T381	T382	T383	T384	T385	T386	T387	T388	T389	T390	T391	T392	T393	T394	T395	T396	T397	T398	T399	T400	T401	T402	T403	T404	T405	T406	T407	T408	T409	T410	T411	T412	T413	T414	T415	T416	T417	T418	T419	T420	T421	T422	T423	T424	T425	T426	T427	T428	T429	T430	T431	T432	T433	T434	T435	T436	T437	T438	T439	T440	T441	T442	T443	T444	T445	T446	T447	T448	T449	T450	T451	T452	T453	T454	T455	T456	T457	T458	T459	T460	T461	T462	T463	T464	T465	T466	T467	T468	T469	T470	T471	T472	T473	T474	T475	T476	T477	T478	T479	T480	T481	T482	T483	T484	T485	T486	T487	T488	T489	T490	T491	T492	T493	T494	T495	T496	T497	T498	T499	T500	T501	T502	T503	T504	T505	T506	T507	T508	T509	T510	T511	T512	T513	T514	T515	T516	T517	T518	T519	T520	T521	T522	T523	T524	T525	T526	T527	T528	T529	T530	T531	T532	T533	T534	T535	T536	T537	T538	T539	T540	T541	T542	T543	T544	T545	T546	T547	T548	T549	T550	T551	T552	T553	T554	T555	T556	T557	T558	T559	T560	T561	T562	T563	T564	T565	T566	T567	T568	T569	T570	T571	T572	T573	T574	T575	T576	T577	T578	T579	T580	T581	T582	T583	T584	T585	T586	T587	T588	T589	T590	T591	T592	T593	T594	T595	T596	T597	T598	T599	T600	T601	T602	T603	T604	T605	T606	T607	T608	T609	T610	T611	T612	T613	T614	T615	T616	T617	T618	T619	T620	T621	T622	T623	T624	T625	T626	T627	T628	T629	T630	T631	T632	T633	T634	T635	T636	T637	T638	T639	T640	T641	T642	T643	T644	T645	T646	T647	T648	T649	T650	T651	T652	T653	T654	T655	T656	T657	T658	T659	T660	T661	T662	T663	T664	T665	T666	T667	T668	T669	T670	T671	T672	T673	T674	T675	T676	T677	T678	T679	T680	T681	T682	T683	T684	T685	T686	T687	T688	T689	T690	T691	T692	T693	T694	T695	T696	T697	T698	T699	T700	T701	T702	T703	T704	T705	T706	T707	T708	T709	T710	T711	T712	T713	T714	T715	T716	T717	T718	T719	T720	T721	T722	T723	T724	T725	T726	T727	T728	T729	T730	T731	T732	T733	T734	T735	T736	T737	T738	T739	T740	T741	T742	T743	T744	T745	T746	T747	T748	T749	T750	T751	T752	T753	T754	T755	T756	T757	T758	T759	T760	T761	T762	T763	T764	T765	T766	T767	T768	T769	T770	T771	T772	T773	T774	T775	T776	T777	T778	T779	T780	T781	T782	T783	T784	T785	T786	T787	T788	T789	T790	T791	T792	T793	T794	T795	T796	T797	T798	T799	T800	T801	T802	T803	T804	T805	T806	T807	T808	T809	T810	T811	T812	T813	T814	T815	T816	T817	T818	T819	T820	T821	T822	T823	T824	T825	T826	T827	T828	T829	T830	T831	T832	T833	T834	T835	T836	T837	T838	T839	T840	T841	T842	T843	T844	T845	T846	T847	T848	T849	T850	T851	T852	T853	T854	T855	T856	T857	T858	T859	T860	T861	T862	T863	T864	T865	T866	T867	T868	T869	T870	T871	T872	T873	T874	T875	T876	T877	T878	T879	T880	T881	T882	T883	T884	T885	T886	T887	T888	T889	T890	T891	T892	T893	T894	T895	T896	T897	T898	T899	T900	T901	T902	T903	T904	T905	T906	T907	T908	T909	T910	T911	T912	T913	T914	T915	T916	T917	T918	T919	T920	T921	T922	T923	T924	T925	T926	T927	T928	T929	T930	T931	T932	T933	T934	T935	T936	T937	T938	T939	T940	T941	T942	T943	T944	T945	T946	T947	T948	T949	T950	T951	T952	T953	T954	T955	T956	T957	T958	T959	T960	T961	T962	T963	T964	T965	T966	T967	T968	T969	T970	T971	T972	T973	T974	T975	T976	T977	T978	T979	T980	T981	T982	T983	T984	T985	T986	T987	T988	T989	T990	T991	T992	T993	T994	T995	T996	T997	T998	T999	T1000	T1001	T1002	T1003	T1004	T1005	T1006	T1007	T1008	T1009	T1010	T1011	T1012	T1013	T1014	T1015	T1016	T1017	T1018	T1019	T1020	T1021	T1022	T1023	T1024	T1025	T1026	T1027	T1028	T1029	T1030	T1031	T1032	T1033	T1034	T1035	T1036	T1037	T1038	T1039	T1040	T1041	T1042	T1043	T1044	T1045	T1046	T1047	T1048	T1049	T1050	T1051	T1052	T1053	T1054	T1055	T1056	T1057	T1058	T1059	T1060	T1061	T1062	T1063	T1064	T1065	T1066	T1067	T1068	T1069	T1070	T1071	T1072	T1073	T1074	T1075	T1076	T1077	T1078	T1079	T1080	T1081	T1082	T1083	T1084	T1085	T1086	T1087	T1088	T1089	T1090	T1091	T1092	T1093	T1094	T1095	T1096	T1097	T1098	T1099	T1100	T1101	T1102	T1103	T1104	T1105	T1106	T1107	T1108	T1109	T1110	T1111	T1112	T1113	T1114	T1115	T1116	T1117	T1118	T1119	T1120	T1121	T1122	T1123	T1124	T1125	T1126	T1127	T1128	T1129	T1130	T1131	T1132	T1133	T1134	T1135	T1136	T1137	T1138	T1139	T1140	T1141	T1142	T1143	T1144	T1145	T1146	T1147	T1148	T1149	T1150	T1151	T1152	T1153	T1154	T1155	T1156	T1157	T1158	T1159	T1160	T1161	T1162	T1163	T1164	T1165	T1166	T1167	T1168	T1169	T1170	T1171	T1172	T1173	T1174	T1175	T1176	T1177	T1178	T1179	T1180	T1181	T1182	T1183	T1184	T1185	T1186	T1187	T1188	T1189	T1190	T1191	T1192	T1193	T1194	T1195	T1196	T1197	T1198	T1199	T1200	T1201	T1202	T1203	T1204	T1205	T1206	T1207	T1208	T1209	T1210	T1211	T1212	T1213	T1214	T1215	T1216	T1217	T1218	T1219	T1220	T1221	T1222	T1223	T1224	T1225	T1226	T1227	T1228	T1229	T1230	T1231	T1232	T1233	T1234	T1235	T1236	T1237	T1238	T1239	T1240	T1241	T1242	T1243	T1244	T1245	T1246	T1247	T1248	T1249	T1250	T1251	T1252	T1253	T1254	T1255	T1256	T1257	T1258	T1259	T1260	T1261	T1262	T1263	T1264	T1265	T1266	T1267	T1268	T1269	T1270	T1271	T1272	T1273	T1274	T1275	T1276	T1277	T1278	T1279	T1280	T1281	T1282	T1283	T1284	T1285	T1286	T1287	T1288	T1289	T1290	T1291	T1292	T1293	T1294	T1295	T1296	T1297	T1298	T1299	T1300	T1301	T1302	T1303	T1304	T1305	T1306	T1307	T1308	T1309	T1310	T1311	T1312	T1313	T1314	T1315	T1316	T1317	T1318	T1319	T1320	T1321	T1322	T1323	T1324	T1325	T1326	T1327	T1328	T1329	T1330	T1331	T1332	T1333	T1334	T1335	T1336	T1337	T1338	T1339	T1340	T1341	T1342	T1343	T1344	T1345	T1346	T1347	T1348	T1349	T1350	T1351	T1352	T1353	T1354	T1355	T1356	T1357	T1358	T1359	T1360	T1361	T1362	T1363	T1364	T1365	T1366	T1367	T1368	T1369	T1370	T1371	T1372	T1373	T1374	T1375	T1376	T1377	T1378	T1379	T1380	T1381	T1382	T1383	T1384	T1385	T1386	T1387	T1388	T1389	T1390	T1391	T1392	T1393	T1394	T1395	T1396	T1397	T1398	T1399	T1400	T1401	T1402	T1403	T1404	T1405	T1406	T1407	T1408	T1409	T1410	T1411	T1412	T1413	T1414	T1415	T1416	T1417	T1418	T1419	T1420	T1421	T1422	T1423	T1424	T1425	T1426	T1427	T1428	T1429	T1430	T1431	T1432	T1433	T1434	T1435	T1436	T1437	T1438	T1439	T1440	T1441	T1442	T1443	T1444	T1445	T1446	T1447	T1448	T1449	T1450	T1451	T1452	T1453	T1454	T1455	T1456	T1457	T1458	T1459	T1460	T1461	T1462	T1463	T1464	T1465	T1466	T1467	T1468	T1469	T1470	T1471	T1472	T1473	T1474	T1475	T1476	T1477	T1478	T1479	T1480	T1481	T1482	T1483	T1484	T1485	T1486	T1487	T1488	T1489	T1490	T1491	T1492	T1493	T1494	T1495
---------	----	----	----	----	----	----	----	----	----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

RISA TOWER FEEDLINE DISTRIBUTION

Feedline Distribution Chart

0' - 92'

Round Flat App In Face App Out Face Truss Leg




URS Corporation		Job: 92' Rohn SSV	
500 Enterprise Drive, Suite 3B		Project: Glastonbury North	
Rocky Hill, CT 06067		Client: Nextel Communications	Drawn by: Kevin Barker
Phone: (860) 529-8882		Code: TIA/EIA-222-F	Date: 09/25/08
FAX: (860) 529-3981		Path: P:\08\ERI\Files\PC1-028 92' Lattice Tower.dwg	Scale: NTS
			Dwg No. E-7

RISA TOWER FEEDLINE PLAN

Feedline Plan

Round Flat App In Face App Out Face



URS Corporation		Job: 92' Rohn SSV	
500 Enterprise Drive, Suite 3B		Project: Glastonbury North	
Rocky Hill, CT 06067		Client: Nextel Communications	Drawn by: Kevin Barker
Phone: (860) 529-8882		Code: TIA/EIA-222-F	Date: 09/25/08
FAX: (860) 529-3991		Path: P:\08BERG Files\PC1-028 92' Lattice Tower.dwg	Scale: NTS
			Dwg No. E-7

RISA TOWER DETAILED OUTPUT

RISATower URS Corporation 500 Enterprise Drive, Suite 3B Rocky Hill, CT 06067 Phone: (860) 529-8882 FAX: (860) 529-3991	Job	92' Rohn SSV	Page	1 of 25
	Project	Glastonbury North	Date	09:32:36 09/25/08
	Client	Nextel Communications	Designed by	Kevin Barker

Tower Input Data

The main tower is a 3x free standing tower with an overall height of 92.00 ft above the ground line.

The base of the tower is set at an elevation of 0.00 ft above the ground line.

The face width of the tower is 6.52 ft at the top and 14.65 ft at the base.

This tower is designed using the TIA/EIA-222-F standard.

The following design criteria apply:

Tower is located in Hartford County, Connecticut.

Basic wind speed of 80 mph.

Nominal ice thickness of 0.5000 in.

Ice density of 56 pcf.

A wind speed of 69 mph is used in combination with ice.

Temperature drop of 50 °F.

Deflections calculated using a wind speed of 50 mph.

A non-linear (P-delta) analysis was used.

Pressures are calculated at each section.


Stress ratio used in tower member design is 1.333.

Local bending stresses due to climbing loads, feedline supports, and appurtenance mounts are not considered.

Options

Consider Moments - Legs	Distribute Leg Loads As Uniform	Treat Feedline Bundles As Cylinder
Consider Moments - Horizontals	Assume Legs Pinned	Use ASCE 10 X-Brace Ly Rules
Consider Moments - Diagonals	✓ Assume Rigid Index Plate	✓ Calculate Redundant Bracing Forces
Use Moment Magnification	✓ Use Clear Spans For Wind Area	Ignore Redundant Members in FEA
✓ Use Code Stress Ratios	✓ Use Clear Spans For KL/r	SR Leg Bolts Resist Compression
✓ Use Code Safety Factors - Guys	Retension Guys To Initial Tension	✓ All Leg Panels Have Same Allowable
Escalate Ice	Bypass Mast Stability Checks	Offset Girt At Foundation
Always Use Max Kz	Use Azimuth Dish Coefficients	✓ Consider Feedline Torque
Use Special Wind Profile	✓ Project Wind Area of Appurt.	Include Angle Block Shear Check
✓ Include Bolts In Member Capacity	Autocalc Torque Arm Areas	***** Poles *****
✓ Leg Bolts Are At Top Of Section	SR Members Have Cut Ends	Include Shear-Torsion Interaction
Secondary Horizontal Braces Leg	✓ Sort Capacity Reports By Component	Always Use Sub-Critical Flow
Use Diamond Inner Bracing (4 Sided)	Triangulate Diamond Inner Bracing	Use Top Mounted Sockets
Add IBC .6D+W Combination		

RISATower URS Corporation 500 Enterprise Drive, Suite 3B Rocky Hill, CT 06067 Phone: (860) 529-8882 FAX: (860) 529-3991	Job	92' Rohn SSV	Page	2 of 25
	Project	Glastonbury North	Date	09:32:36 09/25/08
	Client	Nextel Communications	Designed by	Kevin Barker



Triangular Tower

Tower Section Geometry

Tower Section	Tower Elevation	Assembly Database	Description	Section Width	Number of Sections	Section Length
	ft			ft		ft
T1	92.00-80.00			6.52	1	12.00
T2	80.00-60.00			6.56	1	20.00
T3	60.00-40.00			8.56	1	20.00
T4	40.00-20.00			10.56	1	20.00
T5	20.00-0.00			12.60	1	20.00

Tower Section Geometry (cont'd)

Tower Section	Tower Elevation	Diagonal Spacing	Bracing Type	Has K Brace End Panels	Has Horizontals	Top Girt Offset	Bottom Girt Offset
	ft	ft				in	in
T1	92.00-80.00	6.00	X Bracc	No	No	0.0000	0.0000
T2	80.00-60.00	5.00	X Bracc	No	No	0.0000	0.0000
T3	60.00-40.00	6.67	X Bracc	No	No	0.0000	0.0000
T4	40.00-20.00	6.67	X Bracc	No	No	0.0000	0.0000
T5	20.00-0.00	6.67	X Bracc	No	No	0.0000	0.0000

Tower Section Geometry (cont'd)

RISATower URS Corporation 500 Enterprise Drive, Suite 3B Rocky Hill, CT 06067 Phone: (860) 529-8882 FAX: (860) 529-3991	Job	92' Rohn SSV	Page	3 of 25
	Project	Glastonbury North	Date	09:32:36 09/25/08
	Client	Nextel Communications	Designed by	Kevin Barker

Tower Elevation ft	Leg Type	Leg Size	Leg Grade	Diagonal Type	Diagonal Size	Diagonal Grade
T1 92.00-80.00	Pipe	P2.375x.154	A618-50 (50 ksi)	Single Angle	L1 1/2x1 1/2x3/16	A36 (36 ksi)
T2 80.00-60.00	Pipe	P2.875x.203	A618-50 (50 ksi)	Single Angle	L1 1/2x1 1/2x3/16	A36 (36 ksi)
T3 60.00-40.00	Pipe	P2.875x.203	A618-50 (50 ksi)	Single Angle	L1 3/4x1 3/4x3/16	A36 (36 ksi)
T4 40.00-20.00	Pipe	P2.875x.276	A618-50 (50 ksi)	Single Angle	L2x2x3/16	A36 (36 ksi)
T5 20.00-0.00	Pipe	P3.5x.3	A618-50 (50 ksi)	Single Angle	L2 1/2x2 1/2x3/16	A36 (36 ksi)

Tower Section Geometry (cont'd)

Tower Elevation ft	Top Girt Type	Top Girt Size	Top Girt Grade	Bottom Girt Type	Bottom Girt Size	Bottom Girt Grade
T1 92.00-80.00	Single Angle	L2x2x3/16	A36 (36 ksi)	Single Angle		A36 (36 ksi)

Tower Section Geometry (cont'd)

Tower Elevation ft	Gusset Area (per face) ft ²	Gusset Thickness in	Gusset Grade	Adjust. Factor A _r	Adjust. Factor A _r	Weight Mult.	Double Angle Stitch Bolt Spacing Diagonals in	Double Angle Stitch Bolt Spacing Horizontals in
T1 92.00-80.00	0.00	0.2500	A36 (36 ksi)	1.02	1	1	36.0000	36.0000
T2 80.00-60.00	0.00	0.2500	A36 (36 ksi)	1.02	1	1	36.0000	36.0000
T3 60.00-40.00	0.00	0.2500	A36 (36 ksi)	1.02	1	1	36.0000	36.0000
T4 40.00-20.00	0.00	0.2500	A36 (36 ksi)	1.02	1	1	36.0000	36.0000
T5 20.00-0.00	0.00	0.2500	A36 (36 ksi)	1.02	1	1	36.0000	36.0000

Tower Section Geometry (cont'd)

Tower Elevation ft	Calc K Single Angles	Calc K Solid Rounds	K Factors ¹						
			Legs	X Brace Diags	K Brace Diags	Single Diags	Girts	Horiz.	Sec. Horiz.
				X Y	X Y	X Y	X Y	X Y	X Y
T1 92.00-80.00	Yes	Yes	1	1 1	1 1	1 1	1 1	1 1	1 1

RISATower URS Corporation 500 Enterprise Drive, Suite 3B Rocky Hill, CT 06067 Phone: (860) 529-8882 FAX: (860) 529-3991	Job	92' Rohn SSV	Page	4 of 25
	Project	Glastonbury North	Date	09:32:36 09/25/08
	Client	Nextel Communications	Designed by	Kevin Barker

Tower Elevation ft	Calc K Single Angles	Calc K Solid Rounds	K Factors ¹							
			Legs	X Brace Diags	K Brace Diags	Single Diags	Girts	Horiz.	Sec. Horiz.	Inner Brace
				X Y	X Y	X Y	X Y	X Y	X Y	X Y
T2 80.00-60.00	Yes	Yes	1	1	1	1	1	1	1	1
T3 60.00-40.00	Yes	Yes	1	1	1	1	1	1	1	1
T4 40.00-20.00	Yes	Yes	1	1	1	1	1	1	1	1
T5 20.00-0.00	Yes	Yes	1	1	1	1	1	1	1	1

¹Note: K factors are applied to member segment lengths. K-braces without inner supporting members will have the K factor in the out-of-plane direction applied to the overall length.

Tower Section Geometry (cont'd)

Tower Elevation ft	Leg		Diagonal		Top Girt		Bottom Girt		Mid Girt		Long Horizontal		Short Horizontal	
	Net Width Deduct in	U	Net Width Deduct in	U	Net Width Deduct in	U	Net Width Deduct in	U	Net Width Deduct in	U	Net Width Deduct in	U	Net Width Deduct in	U
T1 92.00-80.00	0.0000	1	0.0000	0.75	0.0000	0.75	0.0000	0.75	0.0000	0.75	0.0000	0.75	0.0000	0.75
T2 80.00-60.00	0.0000	1	0.0000	0.75	0.0000	0.75	0.0000	0.75	0.0000	0.75	0.0000	0.75	0.0000	0.75
T3 60.00-40.00	0.0000	1	0.0000	0.75	0.0000	0.75	0.0000	0.75	0.0000	0.75	0.0000	0.75	0.0000	0.75
T4 40.00-20.00	0.0000	1	0.0000	0.75	0.0000	0.75	0.0000	0.75	0.0000	0.75	0.0000	0.75	0.0000	0.75
T5 20.00-0.00	0.0000	1	0.0000	0.75	0.0000	0.75	0.0000	0.75	0.0000	0.75	0.0000	0.75	0.0000	0.75

Tower Section Geometry (cont'd)

Tower Elevation ft	Leg Connection Type	Leg		Diagonal		Top Girt		Bottom Girt		Mid Girt		Long Horizontal		Short Horizontal	
		Bolt Size in	No.	Bolt Size in	No.	Bolt Size in	No.	Bolt Size in	No.	Bolt Size in	No.	Bolt Size in	No.	Bolt Size in	No.
T1 92.00-80.00	Flange	0.6300	4	0.5000	1	0.5000	1	0.0000	0	0.6250	0	0.0000	0	0.6250	0
		A325N		A325N		A325N		A325N		A325N		A325N		A325N	
T2 80.00-60.00	Flange	0.6300	4	0.5000	1	0.5000	0	0.0000	0	0.6250	0	0.0000	0	0.6250	0
		A325N		A325N		A325N		A325N		A325N		A325N		A325N	
T3 60.00-40.00	Flange	0.6300	4	0.5000	1	0.0000	0	0.0000	0	0.6250	0	0.0000	0	0.6250	0
		A325N		A325N		A325N		A325N		A325N		A325N		A325N	
T4 40.00-20.00	Flange	0.6300	4	0.5000	1	0.0000	0	0.0000	0	0.6250	0	0.0000	0	0.6250	0
		A325N		A325N		A325N		A325N		A325N		A325N		A325N	
T5 20.00-0.00	Flange	0.7500	4	0.5000	1	0.0000	0	0.0000	0	0.6250	0	0.0000	0	0.6250	0
		A325N		A325N		A325N		A325N		A325N		A325N		A325N	

Feed Line/Linear Appurtenances - Entered As Round Or Flat

RISATower URS Corporation 500 Enterprise Drive, Suite 3B Rocky Hill, CT 06067 Phone: (860) 529-8882 FAX: (860) 529-3991	Job	92' Rohn SSV	Page	5 of 25
	Project	Glastonbury North	Date	09:32:36 09/25/08
	Client	Nextel Communications	Designed by	Kevin Barker

Description	Face or Leg	Allow Shield	Component Type	Placement ft	Face Offset in	Lateral Offset (Frac FW)	#	# Per Row	Clear Spacing in	Width or Diameter in	Perimeter in	Weight plf
1/2 (Town)	A	No	Ar (CfAe)	73.00 - 6.00	-12.5000	0.27	1	1	0.5800	0.5800		0.25
1/2 (Town)	A	No	Ar (CfAe)	73.00 - 6.00	-12.0000	0.22	1	1	0.5800	0.5800		0.25
FLC 158-50J (1 5/8 FOAM)	C	No	Ar (CfAe)	65.00 - 6.00	4.0000	0.43	6	6	2.0200	2.0200		0.92
(Pocket Wireless) 7/8 (Unknown)	A	No	Ar (CfAe)	92.00 - 6.00	-4.0000	0.35	3	3	1.1100	1.1100		0.54

Feed Line/Linear Appurtenances - Entered As Area

Description	Face or Leg	Allow Shield	Component Type	Placement ft	Face Offset in	Lateral Offset (Frac FW)	#	C _A A _A ft ² /ft	Weight plf
1 5/8 (Cingular)	A	No	CaAa (In Face)	88.00 - 6.00	-4.0000	0.43	3	No Ice 0.20 1/2" Ice 0.30	1.04 2.55
1 5/8 (Cingular)	B	No	CaAa (In Face)	88.00 - 6.00	-4.0000	0.43	3	No Ice 0.20 1/2" Ice 0.30	1.04 2.55
1 5/8 (Cingular)	C	No	CaAa (In Face)	88.00 - 6.00	-4.0000	0.43	3	No Ice 0.20 1/2" Ice 0.30	1.04 2.55

Feed Line/Linear Appurtenances Section Areas

Tower Section	Tower Elevation ft	Face	A _R ft ²	A _F ft ²	C _A A _A In Face ft ²	C _A A _A Out Face ft ²	Weight lb
T1	92.00-80.00	A	3.330	0.000	4.752	0.000	44.40
		B	0.000	0.000	4.752	0.000	24.96
		C	0.000	0.000	4.752	0.000	24.96
T2	80.00-60.00	A	6.807	0.000	11.880	0.000	101.30
		B	0.000	0.000	11.880	0.000	62.40
		C	5.050	0.000	11.880	0.000	90.00
T3	60.00-40.00	A	7.483	0.000	11.880	0.000	104.80
		B	0.000	0.000	11.880	0.000	62.40
		C	20.200	0.000	11.880	0.000	172.80
T4	40.00-20.00	A	7.483	0.000	11.880	0.000	104.80
		B	0.000	0.000	11.880	0.000	62.40
		C	20.200	0.000	11.880	0.000	172.80
T5	20.00-0.00	A	5.238	0.000	8.316	0.000	73.36
		B	0.000	0.000	8.316	0.000	43.68
		C	14.140	0.000	8.316	0.000	120.96

Feed Line/Linear Appurtenances Section Areas - With Ice

Tower Section	Tower Elevation ft	Face or Leg	Ice Thickness in	A _R ft ²	A _F ft ²	C _A A _A In Face ft ²	C _A A _A Out Face ft ²	Weight lb
T1	92.00-80.00	A	0.500	6.330	0.000	7.152	0.000	116.05
		B		0.000	0.000	7.152	0.000	61.20

RISATower URS Corporation 500 Enterprise Drive, Suite 3B Rocky Hill, CT 06067 Phone: (860) 529-8882 FAX: (860) 529-3991	Job	92' Rohn SSV	Page	6 of 25
	Project	Glastonbury North	Date	09:32:36 09/25/08
	Client	Nextel Communications	Designed by	Kevin Barker

Tower Section	Tower Elevation ft	Face or Leg	Ice Thickness in	A _R ft ²	A _F ft ²	C _A A _A In Face ft ²	C _A A _A Out Face ft ²	Weight lb
T2	80.00-60.00	C		0.000	0.000	7.152	0.000	61.20
		A	0.500	13.973	0.000	17.880	0.000	268.06
		B		0.000	0.000	17.880	0.000	153.00
T3	60.00-40.00	C		7.550	0.000	17.880	0.000	226.78
		A	0.500	15.817	0.000	17.880	0.000	280.80
		B		0.000	0.000	17.880	0.000	153.00
T4	40.00-20.00	C		30.200	0.000	17.880	0.000	448.13
		A	0.500	15.817	0.000	17.880	0.000	280.80
		B		0.000	0.000	17.880	0.000	153.00
T5	20.00-0.00	C		30.200	0.000	17.880	0.000	448.13
		A	0.500	11.072	0.000	12.516	0.000	196.56
		B		0.000	0.000	12.516	0.000	107.10
		C		21.140	0.000	12.516	0.000	313.69

Feed Line Center of Pressure

Section	Elevation ft	CP _x in	CP _z in	CP _x Ice in	CP _z Ice in
T1	92.00-80.00	-0.0710	-1.2017	-0.0884	-1.4956
T2	80.00-60.00	-1.1136	-0.3647	-1.1215	-0.7623
T3	60.00-40.00	-4.4867	1.8780	-4.4936	1.3017
T4	40.00-20.00	-5.2540	2.0720	-5.3163	1.4006
T5	20.00-0.00	-4.8129	1.8269	-5.0463	1.2492

Discrete Tower Loads

Description	Face or Leg	Offset Type	Offsets: Horz Lateral Vert ft ft ft	Azimuth Adjustment °	Placement ft	C _A A _A Front ft ²	C _A A _A Side ft ²	Weight lb
(3) DUO1417-8686 (Cingular)	A	From Leg	4.50 0.00 0.00	0.0000	88.00	No Ice 1/2" Ice 6.53 6.94	4.20 4.57	20.30 62.49
(3) DUO1417-8686 (Cingular)	B	From Leg	4.50 0.00 0.00	0.0000	88.00	No Ice 1/2" Ice 6.53 6.94	4.20 4.57	20.30 62.49
(3) DUO1417-8686 (Cingular)	C	From Leg	4.50 0.00 0.00	0.0000	88.00	No Ice 1/2" Ice 6.53 6.94	4.20 4.57	20.30 62.49
(3) TMA 10"x8"x3" (Cingular)	A	From Leg	4.00 0.00 0.00	0.0000	88.00	No Ice 1/2" Ice 0.78 0.90	0.29 0.38	15.00 20.06
(3) TMA 10"x8"x3" (Cingular)	B	From Leg	4.00 0.00 0.00	0.0000	88.00	No Ice 1/2" Ice 0.78 0.90	0.29 0.38	15.00 20.06
(3) TMA 10"x8"x3" (Cingular)	C	From Leg	4.00 0.00 0.00	0.0000	88.00	No Ice 1/2" Ice 0.78 0.90	0.29 0.38	15.00 20.06

RISATower URS Corporation 500 Enterprise Drive, Suite 3B Rocky Hill, CT 06067 Phone: (860) 529-8882 FAX: (860) 529-3991	Job	92' Rohn SSV	Page	7 of 25
	Project	Glastonbury North	Date	09:32:36 09/25/08
	Client	Nextel Communications	Designed by	Kevin Barker

Description	Face or Leg	Offset Type	Offsets: Horz Lateral Vert ft ft ft	Azimuth Adjustment °	Placement ft		C _A A _A Front ft ²	C _A A _A Side ft ²	Weight lb
12' T-Frame Sector Mount (1) (Cingular)	A	From Leg	4.00 0.00 0.00	0.0000	88.00	No Ice 1/2" Ice	13.60 18.40	13.60 18.40	465.00 600.00
12' T-Frame Sector Mount (1) (Cingular)	B	From Leg	4.00 0.00 0.00	0.0000	88.00	No Ice 1/2" Ice	13.60 18.40	13.60 18.40	465.00 600.00
12' T-Frame Sector Mount (1) (Cingular)	C	From Leg	4.00 0.00 0.00	0.0000	88.00	No Ice 1/2" Ice	13.60 18.40	13.60 18.40	465.00 600.00
DB806-XT (Town)	B	From Leg	4.00 0.00 0.00	0.0000	79.00	No Ice 1/2" Ice	1.14 1.68	1.14 1.68	21.00 29.93
PR-950 (Town)	B	From Leg	4.00 0.00 0.00	0.0000	73.00	No Ice 1/2" Ice	6.35 11.43	6.35 11.43	38.00 49.40
Pired 6' Side Mount Standoff (1) (Town)	B	From Leg	2.00 0.00 0.00	0.0000	73.00	No Ice 1/2" Ice	4.97 6.12	4.97 6.12	70.00 130.00
DB420 (Existing)	A	From Leg	0.25 0.00 0.00	0.0000	102.00	No Ice 1/2" Ice	3.33 5.99	3.33 5.99	34.00 44.20
ASP-705 (Existing)	B	From Leg	0.25 0.00 0.00	0.0000	102.00	No Ice 1/2" Ice	5.88 8.01	5.88 8.01	25.00 67.70
ASPA685 (Existing)	C	From Leg	0.25 0.00 0.00	0.0000	102.00	No Ice 1/2" Ice	5.25 7.38	5.25 7.38	21.50 60.30
APXV18-206517S-C w/ mounting hardware (Pocket Wireless)	A	From Leg	0.25 0.00 0.00	30.0000	65.00	No Ice 1/2" Ice	5.17 5.62	3.62 4.24	43.45 76.89
APXV18-206517S-C w/ mounting hardware (Pocket Wireless)	B	From Leg	0.25 0.00 0.00	30.0000	65.00	No Ice 1/2" Ice	5.17 5.62	3.62 4.24	43.45 76.89
APXV18-206517S-C w/ mounting hardware (Pocket Wireless)	C	From Leg	0.25 0.00 0.00	30.0000	65.00	No Ice 1/2" Ice	5.17 5.62	3.62 4.24	43.45 76.89

Tower Pressures - No Ice

$$G_H = 1.168$$

Section Elevation ft	z ft	K _z	q _z psf	A _G ft ²	F a c e A ft ²	A _F ft ²	A _R ft ²	A _{leg} ft ²	Leg %	C _A A _A In Face ft ²	C _A A _A Out Face ft ²
T1 92.00-80.00	86.00	1.315	22	80.855	A 5.464 B 5.464 C 5.464	5.464 4.750 4.750	8.080 4.750 4.750	4.750	35.07 46.50 46.50	4.752 4.752 4.752	0.000 0.000 0.000
T2 80.00-60.00	70.00	1.24	20	155.998	A 8.965 B 8.965	8.965 16.406 9.599	16.406 9.599	9.599	37.84 51.71	11.880 11.880	0.000 0.000

RISATower URS Corporation 500 Enterprise Drive, Suite 3B Rocky Hill, CT 06067 Phone: (860) 529-8882 FAX: (860) 529-3991	Job	92' Rohn SSV	Page	8 of 25
	Project	Glastonbury North	Date	09:32:36 09/25/08
	Client	Nextel Communications	Designed by	Kevin Barker

Section Elevation	z	K _z	q _z	A _G	F a c e	A _F	A _R	A _{leg}	Leg %	C _{MA} In Face	C _{MA} Out Face
ft	ft		psf	ft ²		ft ²	ft ²	ft ²		ft ²	ft ²
T3 60.00-40.00	50.00	1.126	18	195.998	C	8.965	14.649		40.65	11.880	0.000
					A	10.146	17.083	9.599	35.25	11.880	0.000
					B	10.146	9.599		48.62	11.880	0.000
T4 40.00-20.00	30.00	1	16	236.398	C	10.146	29.799		24.03	11.880	0.000
					A	13.351	17.083	9.600	31.54	11.880	0.000
					B	13.351	9.600		41.83	11.880	0.000
T5 20.00-0.00	10.00	1	16	278.341	C	13.351	29.800		22.25	11.880	0.000
					A	18.942	16.925	11.687	32.58	8.316	0.000
					B	18.942	11.687		38.16	8.316	0.000
					C	18.942	25.827		26.11	8.316	0.000

Tower Pressure - With Ice

$$G_H = 1.168$$

Section Elevation	z	K _z	q _z	I _z	A _G	F a c e	A _F	A _R	A _{leg}	Leg %	C _{MA} In Face	C _{MA} Out Face
ft	ft		psf	in	ft ²		ft ²	ft ²	ft ²		ft ²	ft ²
T1 92.00-80.00	86.00	1.315	16	0.5000	81.855	A	5.464	16.476	6.750	30.77	7.152	0.000
						B	5.464	10.146		43.24	7.152	0.000
						C	5.464	10.146		43.24	7.152	0.000
T2 80.00-60.00	70.00	1.24	15	0.5000	157.666	A	8.965	32.771	12.938	31.00	17.880	0.000
						B	8.965	18.797		46.60	17.880	0.000
						C	8.965	26.347		36.64	17.880	0.000
T3 60.00-40.00	50.00	1.126	14	0.5000	197.666	A	10.146	34.439	12.938	29.02	17.880	0.000
						B	10.146	18.622		44.97	17.880	0.000
						C	10.146	48.822		21.94	17.880	0.000
T4 40.00-20.00	30.00	1	12	0.5000	238.067	A	13.351	35.301	12.939	26.60	17.880	0.000
						B	13.351	19.484		39.41	17.880	0.000
						C	13.351	49.684		20.53	17.880	0.000
T5 20.00-0.00	10.00	1	12	0.5000	280.010	A	18.942	33.526	15.026	28.64	12.516	0.000
						B	18.942	22.455		36.30	12.516	0.000
						C	18.942	43.595		24.03	12.516	0.000

Tower Pressure - Service

$$G_H = 1.168$$

Section Elevation	z	K _z	q _z	A _G	F a c e	A _F	A _R	A _{leg}	Leg %	C _{MA} In Face	C _{MA} Out Face
ft	ft		psf	ft ²		ft ²	ft ²	ft ²		ft ²	ft ²
T1 92.00-80.00	86.00	1.315	8	80.855	A	5.464	8.080	4.750	35.07	4.752	0.000
					B	5.464	4.750		46.50	4.752	0.000
					C	5.464	4.750		46.50	4.752	0.000
T2 80.00-60.00	70.00	1.24	8	155.998	A	8.965	16.406	9.599	37.84	11.880	0.000
					B	8.965	9.599		51.71	11.880	0.000
					C	8.965	14.649		40.65	11.880	0.000
T3 60.00-40.00	50.00	1.126	7	195.998	A	10.146	17.083	9.599	35.25	11.880	0.000
					B	10.146	9.599		48.62	11.880	0.000
					C	10.146	29.799		24.03	11.880	0.000

RISATower URS Corporation 500 Enterprise Drive, Suite 3B Rocky Hill, CT 06067 Phone: (860) 529-8882 FAX: (860) 529-3991	Job	92' Rohn SSV	Page	9 of 25
	Project	Glastonbury North	Date	09:32:36 09/25/08
	Client	Nextel Communications	Designed by	Kevin Barker

Section Elevation	z	K _z	q _z	A _G	F a c e	A _F	A _R	A _{reg}	Leg %	C _{AA} In Face ft ²	C _{AA} Out Face ft ²
ft	ft		psf	ft ²		ft ²	ft ²	ft ²			
T4 40.00-20.00	30.00	1	6	236.398	A	13.351	17.083	9.600	31.54	11.880	0.000
					B	13.351	9.600		41.83	11.880	0.000
					C	13.351	29.800		22.25	11.880	0.000
T5 20.00-0.00	10.00	1	6	278.341	A	18.942	16.925	11.687	32.58	8.316	0.000
					B	18.942	11.687		38.16	8.316	0.000
					C	18.942	25.827		26.11	8.316	0.000

Tower Forces - No Ice - Wind Normal To Face

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	R _R	D _F	D _R	A _E	F	w	Ctrl. Face
ft	lb	lb							ft ²	lb	plf	
T1 92.00-80.00	94.32	370.33	A	0.168	2.708	0.584	1	1	10.185	1052.91	87.74	A
			B	0.126	2.861	0.578	1	1	8.210			
			C	0.126	2.861	0.578	1	1	8.210			
T2 80.00-60.00	253.70	739.12	A	0.163	2.726	0.583	1	1	18.537	2044.53	102.23	A
			B	0.119	2.889	0.577	1	1	14.506			
			C	0.151	2.766	0.582	1	1	17.486			
T3 60.00-40.00	340.00	792.09	A	0.139	2.813	0.58	1	1	20.051	2314.00	115.70	C
			B	0.101	2.961	0.575	1	1	15.667			
			C	0.204	2.583	0.591	1	1	27.763			
T4 40.00-20.00	340.00	1046.25	A	0.129	2.851	0.578	1	1	23.233	2249.82	112.49	C
			B	0.097	2.976	0.575	1	1	18.869			
			C	0.183	2.655	0.587	1	1	30.844			
T5 20.00-0.00	238.00	1455.04	A	0.129	2.851	0.578	1	1	28.733	2255.69	112.78	C
			B	0.11	2.924	0.576	1	1	25.676			
			C	0.161	2.732	0.583	1	1	34.005			
Sum Weight:	1266.02	4402.83						OTM	439418.87 lb-ft	9916.95		

Tower Forces - No Ice - Wind 45 To Face

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	R _R	D _F	D _R	A _E	F	w	Ctrl. Face
ft	lb	lb							ft ²	lb	plf	
T1 92.00-80.00	94.32	370.33	A	0.168	2.708	0.584	0.825	1	9.229	987.74	82.31	A
			B	0.126	2.861	0.578	0.825	1	7.254			
			C	0.126	2.861	0.578	0.825	1	7.254			
T2 80.00-60.00	253.70	739.12	A	0.163	2.726	0.583	0.825	1	16.969	1943.07	97.15	A
			B	0.119	2.889	0.577	0.825	1	12.937			
			C	0.151	2.766	0.582	0.825	1	15.917			
T3 60.00-40.00	340.00	792.09	A	0.139	2.813	0.58	0.825	1	18.276	2215.13	110.76	C
			B	0.101	2.961	0.575	0.825	1	13.892			
			C	0.204	2.583	0.591	0.825	1	25.987			
T4 40.00-20.00	340.00	1046.25	A	0.129	2.851	0.578	0.825	1	20.897	2131.06	106.55	C
			B	0.097	2.976	0.575	0.825	1	16.533			
			C	0.183	2.655	0.587	0.825	1	28.507			
T5 20.00-0.00	238.00	1455.04	A	0.129	2.851	0.578	0.825	1	25.418	2082.35	104.12	C
			B	0.11	2.924	0.576	0.825	1	22.361			
			C	0.161	2.732	0.583	0.825	1	30.690			
Sum Weight:	1266.02	4402.83						OTM	416473.05	9359.36		

RISATower URS Corporation 500 Enterprise Drive, Suite 3B Rocky Hill, CT 06067 Phone: (860) 529-8882 FAX: (860) 529-3991	Job	92' Rohn SSV	Page	10 of 25
	Project	Glastonbury North	Date	09:32:36 09/25/08
	Client	Nextel Communications	Designed by	Kevin Barker

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	R _R	D _F	D _R	A _E	F	w	Ctrl. Face
ft	lb	lb							ft ²	lb	plf	
									lb-ft			

Tower Forces - No Ice - Wind 60 To Face

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	R _R	D _F	D _R	A _E	F	w	Ctrl. Face
ft	lb	lb							ft ²	lb	plf	
T1 92.00- 80.00	94.32	370.33	A	0.168	2.708	0.584	0.8	1	9.093	978.43	81.54	A
			B	0.126	2.861	0.578	0.8	1	7.118			
			C	0.126	2.861	0.578	0.8	1	7.118			
T2 80.00- 60.00	253.70	739.12	A	0.163	2.726	0.583	0.8	1	16.744	1928.58	96.43	A
			B	0.119	2.889	0.577	0.8	1	12.713			
			C	0.151	2.766	0.582	0.8	1	15.693			
T3 60.00- 40.00	340.00	792.09	A	0.139	2.813	0.58	0.8	1	18.022	2201.01	110.05	C
			B	0.101	2.961	0.575	0.8	1	13.638			
			C	0.204	2.583	0.591	0.8	1	25.734			
T4 40.00- 20.00	340.00	1046.25	A	0.129	2.851	0.578	0.8	1	20.563	2114.10	105.70	C
			B	0.097	2.976	0.575	0.8	1	16.199			
			C	0.183	2.655	0.587	0.8	1	28.173			
T5 20.00-0.00	238.00	1455.04	A	0.129	2.851	0.578	0.8	1	24.945	2057.58	102.88	C
			B	0.11	2.924	0.576	0.8	1	21.888			
			C	0.161	2.732	0.583	0.8	1	30.216			
Sum Weight:	1266.02	4402.83						OTM	413195.08 lb-ft	9279.70		

Tower Forces - No Ice - Wind 90 To Face

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	R _R	D _F	D _R	A _E	F	w	Ctrl. Face
ft	lb	lb							ft ²	lb	plf	
T1 92.00- 80.00	94.32	370.33	A	0.168	2.708	0.584	0.85	1	9.366	997.05	83.09	A
			B	0.126	2.861	0.578	0.85	1	7.391			
			C	0.126	2.861	0.578	0.85	1	7.391			
T2 80.00- 60.00	253.70	739.12	A	0.163	2.726	0.583	0.85	1	17.193	1957.57	97.88	A
			B	0.119	2.889	0.577	0.85	1	13.161			
			C	0.151	2.766	0.582	0.85	1	16.141			
T3 60.00- 40.00	340.00	792.09	A	0.139	2.813	0.58	0.85	1	18.529	2229.26	111.46	C
			B	0.101	2.961	0.575	0.85	1	14.146			
			C	0.204	2.583	0.591	0.85	1	26.241			
T4 40.00- 20.00	340.00	1046.25	A	0.129	2.851	0.578	0.85	1	21.231	2148.03	107.40	C
			B	0.097	2.976	0.575	0.85	1	16.867			
			C	0.183	2.655	0.587	0.85	1	28.841			
T5 20.00-0.00	238.00	1455.04	A	0.129	2.851	0.578	0.85	1	25.892	2107.11	105.36	C
			B	0.11	2.924	0.576	0.85	1	22.835			
			C	0.161	2.732	0.583	0.85	1	31.163			
Sum Weight:	1266.02	4402.83						OTM	419751.03 lb-ft	9439.01		

RISATower URS Corporation 500 Enterprise Drive, Suite 3B Rocky Hill, CT 06067 Phone: (860) 529-8882 FAX: (860) 529-3991	Job	92' Rohn SSV	Page	11 of 25
	Project	Glastonbury North	Date	09:32:36 09/25/08
	Client	Nextel Communications	Designed by	Kevin Barker

Tower Forces - With Ice - Wind Normal To Face

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	R _R	D _F	D _R	A _E	F	w	Ctrl. Face
ft	lb	lb							ft ²	lb	plf	
T1 92.00- 80.00	238.45	636.37	A	0.268	2.385	0.607	1	1	15.459	1100.71	91.73	A
			B	0.191	2.627	0.589	1	1	11.435			
			C	0.191	2.627	0.589	1	1	11.435			
T2 80.00- 60.00	647.84	1200.10	A	0.265	2.394	0.606	1	1	28.815	2182.27	109.11	A
			B	0.176	2.678	0.586	1	1	19.976			
			C	0.224	2.518	0.596	1	1	24.657			
T3 60.00- 40.00	881.92	1281.82	A	0.226	2.513	0.596	1	1	30.670	2361.66	118.08	C
			B	0.146	2.788	0.581	1	1	20.962			
			C	0.298	2.3	0.615	1	1	40.191			
T4 40.00- 20.00	881.92	1636.28	A	0.204	2.581	0.591	1	1	34.225	2263.12	113.16	C
			B	0.138	2.816	0.58	1	1	24.646			
			C	0.265	2.394	0.606	1	1	43.448			
T5 20.00-0.00	617.35	2237.18	A	0.187	2.639	0.588	1	1	38.653	2163.25	108.16	C
			B	0.148	2.779	0.581	1	1	31.992			
			C	0.223	2.52	0.595	1	1	44.900			
Sum Weight:	3267.49	6991.75						OTM	455028.92 lb-ft	10071.01		

Tower Forces - With Ice - Wind 45 To Face

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	R _R	D _F	D _R	A _E	F	w	Ctrl. Face
ft	lb	lb							ft ²	lb	plf	
T1 92.00- 80.00	238.45	636.37	A	0.268	2.385	0.607	0.825	1	14.503	1057.67	88.14	A
			B	0.191	2.627	0.589	0.825	1	10.479			
			C	0.191	2.627	0.589	0.825	1	10.479			
T2 80.00- 60.00	647.84	1200.10	A	0.265	2.394	0.606	0.825	1	27.246	2115.43	105.77	A
			B	0.176	2.678	0.586	0.825	1	18.408			
			C	0.224	2.518	0.596	0.825	1	23.088			
T3 60.00- 40.00	881.92	1281.82	A	0.226	2.513	0.596	0.825	1	28.894	2295.63	114.78	C
			B	0.146	2.788	0.581	0.825	1	19.186			
			C	0.298	2.3	0.615	0.825	1	38.415			
T4 40.00- 20.00	881.92	1636.28	A	0.204	2.581	0.591	0.825	1	31.888	2182.83	109.14	C
			B	0.138	2.816	0.58	0.825	1	22.310			
			C	0.265	2.394	0.606	0.825	1	41.111			
T5 20.00-0.00	617.35	2237.18	A	0.187	2.639	0.588	0.825	1	35.338	2043.34	102.17	C
			B	0.148	2.779	0.581	0.825	1	28.677			
			C	0.223	2.52	0.595	0.825	1	41.585			
Sum Weight:	3267.49	6991.75						OTM	439739.53 lb-ft	9694.89		

Tower Forces - With Ice - Wind 60 To Face

RISATower URS Corporation 500 Enterprise Drive, Suite 3B Rocky Hill, CT 06067 Phone: (860) 529-8882 FAX: (860) 529-3991	Job	92' Rohn SSV	Page	12 of 25
	Project	Glastonbury North	Date	09:32:36 09/25/08
	Client	Nextel Communications	Designed by	Kevin Barker

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	R _R	D _F	D _R	A _E	F	w	Ctrl. Face
ft	lb	lb							ft ²	lb	plf	
T1 92.00-80.00	238.45	636.37	A	0.268	2.385	0.607	0.8	1	14.366	1051.52	87.63	A
			B	0.191	2.627	0.589	0.8	1	10.343			
			C	0.191	2.627	0.589	0.8	1	10.343			
T2 80.00-60.00	647.84	1200.10	A	0.265	2.394	0.606	0.8	1	27.022	2105.88	105.29	A
			B	0.176	2.678	0.586	0.8	1	18.183			
			C	0.224	2.518	0.596	0.8	1	22.864			
T3 60.00-40.00	881.92	1281.82	A	0.226	2.513	0.596	0.8	1	28.641	2286.20	114.31	C
			B	0.146	2.788	0.581	0.8	1	18.933			
			C	0.298	2.3	0.615	0.8	1	38.162			
T4 40.00-20.00	881.92	1636.28	A	0.204	2.581	0.591	0.8	1	31.554	2171.35	108.57	C
			B	0.138	2.816	0.58	0.8	1	21.976			
			C	0.265	2.394	0.606	0.8	1	40.777			
T5 20.00-0.00	617.35	2237.18	A	0.187	2.639	0.588	0.8	1	34.864	2026.20	101.31	C
			B	0.148	2.779	0.581	0.8	1	28.203			
			C	0.223	2.52	0.595	0.8	1	41.112			
Sum Weight:	3267.49	6991.75						OTM	437555.33 lb-ft	9641.16		

Tower Forces - With Ice - Wind 90 To Face

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	R _R	D _F	D _R	A _E	F	w	Ctrl. Face
ft	lb	lb							ft ²	lb	plf	
T1 92.00-80.00	238.45	636.37	A	0.268	2.385	0.607	0.85	1	14.639	1063.82	88.65	A
			B	0.191	2.627	0.589	0.85	1	10.616			
			C	0.191	2.627	0.589	0.85	1	10.616			
T2 80.00-60.00	647.84	1200.10	A	0.265	2.394	0.606	0.85	1	27.470	2124.98	106.25	A
			B	0.176	2.678	0.586	0.85	1	18.632			
			C	0.224	2.518	0.596	0.85	1	23.312			
T3 60.00-40.00	881.92	1281.82	A	0.226	2.513	0.596	0.85	1	29.148	2305.07	115.25	C
			B	0.146	2.788	0.581	0.85	1	19.440			
			C	0.298	2.3	0.615	0.85	1	38.669			
T4 40.00-20.00	881.92	1636.28	A	0.204	2.581	0.591	0.85	1	32.222	2194.30	109.71	C
			B	0.138	2.816	0.58	0.85	1	22.643			
			C	0.265	2.394	0.606	0.85	1	41.445			
T5 20.00-0.00	617.35	2237.18	A	0.187	2.639	0.588	0.85	1	35.811	2060.47	103.02	C
			B	0.148	2.779	0.581	0.85	1	29.150			
			C	0.223	2.52	0.595	0.85	1	42.059			
Sum Weight:	3267.49	6991.75						OTM	441923.73 lb-ft	9748.62		

Tower Forces - Service - Wind Normal To Face

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	R _R	D _F	D _R	A _E	F	w	Ctrl. Face
ft	lb	lb							ft ²	lb	plf	
T1 92.00-80.00	94.32	370.33	A	0.168	2.708	0.584	1	1	10.185	411.29	34.27	A
			B	0.126	2.861	0.578	1	1	8.210			
			C	0.126	2.861	0.578	1	1	8.210			

RISATower URS Corporation 500 Enterprise Drive, Suite 3B Rocky Hill, CT 06067 Phone: (860) 529-8882 FAX: (860) 529-3991	Job	92' Rohn SSV	Page	13 of 25
	Project	Glastonbury North	Date	09:32:36 09/25/08
	Client	Nextel Communications	Designed by	Kevin Barker

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	R _R	D _F	D _R	A _E	F	w	Ctrl. Face
ft	lb	lb							ft ²	lb	plf	
T2 80.00- 60.00	253.70	739.12	A	0.163	2.726	0.583	1	1	18.537	798.65	39.93	A
			B	0.119	2.889	0.577	1	1	14.506			
			C	0.151	2.766	0.582	1	1	17.486			
T3 60.00- 40.00	340.00	792.09	A	0.139	2.813	0.58	1	1	20.051	903.90	45.20	C
			B	0.101	2.961	0.575	1	1	15.667			
			C	0.204	2.583	0.591	1	1	27.763			
T4 40.00- 20.00	340.00	1046.25	A	0.129	2.851	0.578	1	1	23.233	878.83	43.94	C
			B	0.097	2.976	0.575	1	1	18.869			
			C	0.183	2.655	0.587	1	1	30.844			
T5 20.00-0.00	238.00	1455.04	A	0.129	2.851	0.578	1	1	28.733	881.13	44.06	C
			B	0.11	2.924	0.576	1	1	25.676			
			C	0.161	2.732	0.583	1	1	34.005			
Sum Weight:	1266.02	4402.83						OTM	171648.00 lb-ft	3873.81		

Tower Forces - Service - Wind 45 To Face

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	R _R	D _F	D _R	A _E	F	w	Ctrl. Face
ft	lb	lb							ft ²	lb	plf	
T1 92.00- 80.00	94.32	370.33	A	0.168	2.708	0.584	0.825	1	9.229	385.84	32.15	A
			B	0.126	2.861	0.578	0.825	1	7.254			
			C	0.126	2.861	0.578	0.825	1	7.254			
T2 80.00- 60.00	253.70	739.12	A	0.163	2.726	0.583	0.825	1	16.969	759.01	37.95	A
			B	0.119	2.889	0.577	0.825	1	12.937			
			C	0.151	2.766	0.582	0.825	1	15.917			
T3 60.00- 40.00	340.00	792.09	A	0.139	2.813	0.58	0.825	1	18.276	865.29	43.26	C
			B	0.101	2.961	0.575	0.825	1	13.892			
			C	0.204	2.583	0.591	0.825	1	25.987			
T4 40.00- 20.00	340.00	1046.25	A	0.129	2.851	0.578	0.825	1	20.897	832.45	41.62	C
			B	0.097	2.976	0.575	0.825	1	16.533			
			C	0.183	2.655	0.587	0.825	1	28.507			
T5 20.00-0.00	238.00	1455.04	A	0.129	2.851	0.578	0.825	1	25.418	813.42	40.67	C
			B	0.11	2.924	0.576	0.825	1	22.361			
			C	0.161	2.732	0.583	0.825	1	30.690			
Sum Weight:	1266.02	4402.83						OTM	162684.79 lb-ft	3656.00		

Tower Forces - Service - Wind 60 To Face

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	R _R	D _F	D _R	A _E	F	w	Ctrl. Face
ft	lb	lb							ft ²	lb	plf	
T1 92.00- 80.00	94.32	370.33	A	0.168	2.708	0.584	0.8	1	9.093	382.20	31.85	A
			B	0.126	2.861	0.578	0.8	1	7.118			
			C	0.126	2.861	0.578	0.8	1	7.118			
T2 80.00- 60.00	253.70	739.12	A	0.163	2.726	0.583	0.8	1	16.744	753.35	37.67	A
			B	0.119	2.889	0.577	0.8	1	12.713			
			C	0.151	2.766	0.582	0.8	1	15.693			

RISATower URS Corporation 500 Enterprise Drive, Suite 3B Rocky Hill, CT 06067 Phone: (860) 529-8882 FAX: (860) 529-3991	Job	92' Rohn SSV	Page	14 of 25
	Project	Glastonbury North	Date	09:32:36 09/25/08
	Client	Nextel Communications	Designed by	Kevin Barker

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	R _R	D _F	D _R	A _E	F	w	Ctrl. Face
ft	lb	lb							ft ²	lb	plf	
T3 60.00-40.00	340.00	792.09	A	0.139	2.813	0.58	0.8	1	18.022	859.77	42.99	C
			B	0.101	2.961	0.575	0.8	1	13.638			
			C	0.204	2.583	0.591	0.8	1	25.734			
T4 40.00-20.00	340.00	1046.25	A	0.129	2.851	0.578	0.8	1	20.563	825.82	41.29	C
			B	0.097	2.976	0.575	0.8	1	16.199			
			C	0.183	2.655	0.587	0.8	1	28.173			
T5 20.00-0.00	238.00	1455.04	A	0.129	2.851	0.578	0.8	1	24.945	803.74	40.19	C
			B	0.11	2.924	0.576	0.8	1	21.888			
			C	0.161	2.732	0.583	0.8	1	30.216			
Sum Weight:	1266.02	4402.83						OTM	161404.33 lb-ft	3624.88		

Tower Forces - Service - Wind 90 To Face

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	R _R	D _F	D _R	A _E	F	w	Ctrl. Face
ft	lb	lb							ft ²	lb	plf	
T1 92.00-80.00	94.32	370.33	A	0.168	2.708	0.584	0.85	1	9.366	389.47	32.46	A
			B	0.126	2.861	0.578	0.85	1	7.391			
			C	0.126	2.861	0.578	0.85	1	7.391			
T2 80.00-60.00	253.70	739.12	A	0.163	2.726	0.583	0.85	1	17.193	764.67	38.23	A
			B	0.119	2.889	0.577	0.85	1	13.161			
			C	0.151	2.766	0.582	0.85	1	16.141			
T3 60.00-40.00	340.00	792.09	A	0.139	2.813	0.58	0.85	1	18.529	870.80	43.54	C
			B	0.101	2.961	0.575	0.85	1	14.146			
			C	0.204	2.583	0.591	0.85	1	26.241			
T4 40.00-20.00	340.00	1046.25	A	0.129	2.851	0.578	0.85	1	21.231	839.07	41.95	C
			B	0.097	2.976	0.575	0.85	1	16.867			
			C	0.183	2.655	0.587	0.85	1	28.841			
T5 20.00-0.00	238.00	1455.04	A	0.129	2.851	0.578	0.85	1	25.892	823.09	41.15	C
			B	0.11	2.924	0.576	0.85	1	22.835			
			C	0.161	2.732	0.583	0.85	1	31.163			
Sum Weight:	1266.02	4402.83						OTM	163965.24 lb-ft	3687.11		

Force Totals

Load Case	Vertical Forces	Sum of Forces X	Sum of Forces Z	Sum of Overturning Moments, M _x	Sum of Overturning Moments, M _z	Sum of Torques
	lb	lb	lb	lb-ft	lb-ft	lb-ft
Leg Weight	1906.34					
Bracing Weight	2496.49					
Total Member Self-Weight	4402.83					
Total Weight	7721.40			893.48	816.17	
Wind 0 deg - No Ice		0.00	-13284.01	-728803.75	816.17	-980.99
Wind 30 deg - No Ice		6403.04	-11090.39	-614010.00	-354198.52	386.45
Wind 45 deg - No Ice		8998.94	-8998.94	-498855.23	-498932.54	991.33
Wind 60 deg - No Ice		10952.42	-6323.38	-350843.24	-608409.69	1517.09
Wind 90 deg - No Ice		12806.07	0.00	893.48	-709213.20	2222.20

RISATower URS Corporation 500 Enterprise Drive, Suite 3B Rocky Hill, CT 06067 Phone: (860) 529-8882 FAX: (860) 529-3991	Job	92' Rohn SSV	Page	15 of 25
	Project	Glastonbury North	Date	09:32:36 09/25/08
	Client	Nextel Communications	Designed by	Kevin Barker

Load Case	Vertical Forces lb	Sum of Forces X lb	Sum of Forces Z lb	Sum of Overturning Moments, M_x lb-ft	Sum of Overturning Moments, M_z lb-ft	Sum of Torques lb-ft
Wind 120 deg - No Ice		11504.29	6642.00	365742.09	-631120.16	2454.14
Wind 135 deg - No Ice		8998.94	8998.94	500642.18	-498932.54	2140.68
Wind 150 deg - No Ice		6403.04	11090.39	615796.95	-354198.52	1835.75
Wind 180 deg - No Ice		0.00	12646.76	704366.90	816.17	788.67
Wind 210 deg - No Ice		-6403.04	11090.39	615796.95	355830.86	-386.45
Wind 225 deg - No Ice		-8998.94	8998.94	500642.18	500564.88	-991.33
Wind 240 deg - No Ice		-11504.29	6642.00	365742.09	632752.50	-1473.15
Wind 270 deg - No Ice		-12806.07	0.00	893.48	710845.55	-2222.20
Wind 300 deg - No Ice		-10952.42	-6323.38	-350843.24	610042.03	-2305.76
Wind 315 deg - No Ice		-8998.94	-8998.94	-498855.23	500564.88	-2140.68
Wind 330 deg - No Ice		-6403.04	-11090.39	-614010.00	355830.86	-1835.75
Member Ice	2588.92					
Total Weight Ice	13414.38			1898.16	3066.02	
Wind 0 deg - Ice		0.00	-13241.76	-727145.36	3066.02	-704.08
Wind 30 deg - Ice		6459.69	-11188.51	-618122.62	-354903.14	424.25
Wind 45 deg - Ice		9097.39	-9097.39	-502802.23	-501634.36	922.29
Wind 60 deg - Ice		11095.44	-6405.96	-353886.81	-613171.61	1350.32
Wind 90 deg - Ice		12919.38	0.00	1898.16	-712872.31	1893.87
Wind 120 deg - Ice		11467.70	6620.88	366419.92	-628304.19	2006.58
Wind 135 deg - Ice		9097.39	9097.39	506598.54	-501634.36	1752.13
Wind 150 deg - Ice		6459.69	11188.51	621918.94	-354903.14	1469.62
Wind 180 deg - Ice		0.00	12811.91	713468.09	3066.02	570.03
Wind 210 deg - Ice		-6459.69	11188.51	621918.94	361035.19	-424.25
Wind 225 deg - Ice		-9097.39	9097.39	507766.41	507766.41	-922.29
Wind 240 deg - Ice		-11467.70	6620.88	366419.92	634436.23	-1302.51
Wind 270 deg - Ice		-12919.38	0.00	1898.16	719004.35	-1893.87
Wind 300 deg - Ice		-11095.44	-6405.96	-353886.81	619303.66	-1920.35
Wind 315 deg - Ice		-9097.39	-9097.39	-502802.23	507766.41	-1752.13
Wind 330 deg - Ice		-6459.69	-11188.51	-618122.62	361035.19	-1469.62
Total Weight	7721.40			893.48		
Wind 0 deg - Service		0.00	-5189.07	-284626.41	-799.76	-383.20
Wind 30 deg - Service		2501.19	-4332.18	-239785.11	-139477.38	150.96
Wind 45 deg - Service		3515.21	-3515.21	-194802.77	-196014.10	387.24
Wind 60 deg - Service		4278.29	-2470.07	-136985.59	-238778.61	592.61
Wind 90 deg - Service		5002.37	0.00	411.56	-278154.99	868.05
Wind 120 deg - Service		4493.86	2594.53	142930.55	-247649.89	958.65
Wind 135 deg - Service		3515.21	3515.21	195625.90	-196014.10	836.20
Wind 150 deg - Service		2501.19	4332.18	240608.24	-139477.38	717.09
Wind 180 deg - Service		0.00	4940.14	275205.87	-799.76	308.07
Wind 210 deg - Service		-2501.19	4332.18	240608.24	137877.85	-150.96
Wind 225 deg - Service		-3515.21	3515.21	195625.90	194414.58	-387.24
Wind 240 deg - Service		-4493.86	2594.53	142930.55	246050.37	-575.45
Wind 270 deg - Service		-5002.37	0.00	411.56	276555.46	-868.05
Wind 300 deg - Service		-4278.29	-2470.07	-136985.59	237179.09	-900.69
Wind 315 deg - Service		-3515.21	-3515.21	-194802.77	194414.58	-836.20
Wind 330 deg - Service		-2501.19	-4332.18	-239785.11	137877.85	-717.09

Load Combinations

Comb. No.	Description
1	Dead Only
2	Dead+ Wind 0 deg - No Ice
3	Dead+ Wind 30 deg - No Ice
4	Dead+ Wind 45 deg - No Ice
5	Dead+ Wind 60 deg - No Ice

RISATower URS Corporation 500 Enterprise Drive, Suite 3B Rocky Hill, CT 06067 Phone: (860) 529-8882 FAX: (860) 529-3991	Job	92' Rohn SSV	Page	16 of 25
	Project	Glastonbury North	Date	09:32:36 09/25/08
	Client	Nextel Communications	Designed by	Kevin Barker

Comb. No.	Description
6	Dead+Wind 90 deg - No Ice
7	Dead+Wind 120 deg - No Ice
8	Dead+Wind 135 deg - No Ice
9	Dead+Wind 150 deg - No Ice
10	Dead+Wind 180 deg - No Ice
11	Dead+Wind 210 deg - No Ice
12	Dead+Wind 225 deg - No Ice
13	Dead+Wind 240 deg - No Ice
14	Dead+Wind 270 deg - No Ice
15	Dead+Wind 300 deg - No Ice
16	Dead+Wind 315 deg - No Ice
17	Dead+Wind 330 deg - No Ice
18	Dead+Ice+Temp
19	Dead+Wind 0 deg+Ice+Temp
20	Dead+Wind 30 deg+Ice+Temp
21	Dead+Wind 45 deg+Ice+Temp
22	Dead+Wind 60 deg+Ice+Temp
23	Dead+Wind 90 deg+Ice+Temp
24	Dead+Wind 120 deg+Ice+Temp
25	Dead+Wind 135 deg+Ice+Temp
26	Dead+Wind 150 deg+Ice+Temp
27	Dead+Wind 180 deg+Ice+Temp
28	Dead+Wind 210 deg+Ice+Temp
29	Dead+Wind 225 deg+Ice+Temp
30	Dead+Wind 240 deg+Ice+Temp
31	Dead+Wind 270 deg+Ice+Temp
32	Dead+Wind 300 deg+Ice+Temp
33	Dead+Wind 315 deg+Ice+Temp
34	Dead+Wind 330 deg+Ice+Temp
35	Dead+Wind 0 deg - Service
36	Dead+Wind 30 deg - Service
37	Dead+Wind 45 deg - Service
38	Dead+Wind 60 deg - Service
39	Dead+Wind 90 deg - Service
40	Dead+Wind 120 deg - Service
41	Dead+Wind 135 deg - Service
42	Dead+Wind 150 deg - Service
43	Dead+Wind 180 deg - Service
44	Dead+Wind 210 deg - Service
45	Dead+Wind 225 deg - Service
46	Dead+Wind 240 deg - Service
47	Dead+Wind 270 deg - Service
48	Dead+Wind 300 deg - Service
49	Dead+Wind 315 deg - Service
50	Dead+Wind 330 deg - Service

Maximum Member Forces

Section No.	Elevation ft	Component Type	Condition	Gov. Load Comb.	Force lb	Major Axis Moment lb-ft	Minor Axis Moment lb-ft
T1	92 - 80	Leg	Max Tension	5	3128.13	-528.65	1.82
			Max. Compression	19	-4861.68	-138.67	5.62
			Max. Mx	7	-1667.63	-749.67	2.65
			Max. My	6	-693.17	-2.38	-769.12
			Max. Vy	2	-649.14	528.09	-0.93
			Max. Vx	6	-646.03	-2.38	501.99
		Diagonal	Max Tension	14	1736.12	0.00	0.00
			Max. Compression	6	-1789.95	0.00	0.00

RISATower

URS Corporation
 500 Enterprise Drive, Suite 3B
 Rocky Hill, CT 06067
 Phone: (860) 529-8882
 FAX: (860) 529-3991

Job	92' Rohn SSV	Page	17 of 25
Project	Glastonbury North	Date	09:32:36 09/25/08
Client	Nextel Communications	Designed by	Kevin Barker

Section No.	Elevation ft	Component Type	Condition	Gov. Load Comb.	Force lb	Major Axis Moment lb-ft	Minor Axis Moment lb-ft
T2	80 - 60	Top Girt	Max. Mx	23	925.16	9.04	0.22
			Max. My	6	-1775.44	2.21	-2.04
			Max. Vy	23	7.53	9.04	0.22
			Max. Vx	6	0.46	0.00	0.00
			Max Tension	10	94.40	0.00	0.00
			Max. Compression	24	-146.90	0.00	0.00
			Max. Mx	18	-63.54	-23.22	0.00
			Max. My	28	-61.53	0.00	0.02
			Max. Vy	18	14.25	0.00	0.00
			Max. Vx	28	-0.01	0.00	0.00
		Leg	Max Tension	5	15345.40	-54.60	12.47
			Max. Compression	24	-18480.94	82.98	-4.05
			Max. Mx	32	5887.59	-167.38	0.07
			Max. My	28	-1662.87	19.49	-231.49
			Max. Vy	10	-137.50	-54.68	-11.63
			Max. Vx	28	192.86	-25.04	134.65
		Diagonal	Max Tension	14	1914.90	0.00	0.00
			Max. Compression	34	-2019.04	0.00	0.00
			Max. Mx	21	1442.36	13.33	0.88
			Max. My	27	-1779.21	9.23	2.86
			Max. Vy	21	9.83	13.33	0.88
			Max. Vx	27	-0.84	0.00	0.00
T3	60 - 40	Leg	Max Tension	10	27198.00	-56.67	-8.69
			Max. Compression	30	-32008.10	-14.76	-2.34
			Max. Mx	22	25954.88	-140.97	1.97
			Max. My	9	-1138.75	-3.90	-97.74
			Max. Vy	22	51.60	-140.97	1.97
			Max. Vx	17	46.20	-3.90	97.54
		Diagonal	Max Tension	23	2527.24	0.00	0.00
			Max. Compression	31	-2439.67	0.00	0.00
			Max. Mx	27	1681.19	22.81	2.07
			Max. My	22	-2130.77	13.43	-3.18
			Max. Vy	27	13.34	22.81	2.07
			Max. Vx	22	0.88	0.00	0.00
		Leg	Max Tension	10	39391.02	-62.76	-8.50
			Max. Compression	30	-45922.07	270.39	-1.76
			Max. Mx	24	-45625.52	272.85	-6.19
			Max. My	9	-2019.68	-5.63	-121.09
			Max. Vy	22	-78.39	-202.52	2.44
			Max. Vx	17	-44.94	-5.63	121.04
T4	40 - 20	Diagonal	Max Tension	23	2774.66	0.00	0.00
			Max. Compression	23	-2979.60	0.00	0.00
			Max. Mx	27	1997.39	40.14	-3.45
			Max. My	22	-2577.51	28.18	-4.15
			Max. Vy	27	19.36	40.14	3.48
			Max. Vx	22	1.05	0.00	0.00
		Leg	Max Tension	10	51123.59	-89.61	-8.04
			Max. Compression	30	-60458.72	0.00	0.01
			Max. Mx	22	46279.88	-423.49	1.74
			Max. My	9	-2522.16	-9.37	-202.59
			Max. Vy	22	-127.78	-423.49	1.74
			Max. Vx	9	-67.16	-9.37	-202.59
		Diagonal	Max Tension	23	3442.56	0.00	0.00
			Max. Compression	23	-3335.41	0.00	0.00
			Max. Mx	33	1509.28	71.58	-4.21
			Max. My	31	-3303.69	47.27	7.90
			Max. Vy	33	28.03	71.58	-4.21
			Max. Vx	31	-1.66	0.00	0.00

RISATower URS Corporation 500 Enterprise Drive, Suite 3B Rocky Hill, CT 06067 Phone: (860) 529-8882 FAX: (860) 529-3991	Job	92' Rohn SSV	Page	18 of 25
	Project	Glastonbury North	Date	09:32:36 09/25/08
	Client	Nextel Communications	Designed by	Kevin Barker

Maximum Reactions

Location	Condition	Gov. Load Comb.	Vertical lb	Horizontal, X lb	Horizontal, Z lb
Leg C	Max. Vert	30	62351.42	6297.39	-3576.64
	Max. H _x	13	60268.99	6834.22	-3878.51
	Max. H _z	21	-49710.20	-6456.00	4021.87
	Min. Vert	5	-52868.97	-6142.02	3476.96
	Min. H _x	22	-51458.96	-6803.75	3866.27
	Min. H _z	13	60268.99	6834.22	-3878.51
Leg B	Max. Vert	24	61932.39	-6306.75	-3545.19
	Max. H _x	32	-51877.88	6819.47	3854.15
	Max. H _z	33	-50129.04	6476.82	4000.66
	Min. Vert	15	-52980.38	6158.79	3451.78
	Min. H _x	7	60157.54	-6852.23	-3843.42
	Min. H _z	7	60157.54	-6852.23	-3843.42
Leg A	Max. Vert	19	61916.91	-31.91	7234.07
	Max. H _x	14	2502.64	1078.88	212.50
	Max. H _z	2	60107.44	-39.39	7855.03
	Min. Vert	10	-53030.48	30.19	-7060.44
	Min. H _x	6	2502.67	-1081.12	212.58
	Min. H _z	27	-51893.37	18.35	-7833.23

Tower Mast Reaction Summary

Load Combination	Vertical lb	Shear _x lb	Shear _y lb	Overturning Moment, M _x lb-ft	Overturning Moment, M _y lb-ft	Torque lb-ft
Dead Only	7721.40	0.00	0.00	893.33	816.43	0.00
Dead+Wind 0 deg - No Ice	7721.40	0.01	-13283.58	-729944.96	814.50	-981.26
Dead+Wind 30 deg - No Ice	7721.40	6402.75	-11089.99	-614971.97	-354754.33	384.66
Dead+Wind 45 deg - No Ice	7721.40	8998.54	-8998.59	-499633.90	-499713.77	992.60
Dead+Wind 60 deg - No Ice	7721.40	10951.95	-6323.10	-351387.49	-609362.95	1519.26
Dead+Wind 90 deg - No Ice	7721.40	12805.59	0.07	902.46	-710325.26	2228.27
Dead+Wind 120 deg - No Ice	7721.40	11503.91	6641.79	366317.13	-632108.44	2456.82
Dead+Wind 135 deg - No Ice	7721.40	8998.66	8998.59	501427.66	-499718.81	2141.27
Dead+Wind 150 deg - No Ice	7721.40	6402.85	11089.93	616759.91	-354757.29	1834.50
Dead+Wind 180 deg - No Ice	7721.40	0.01	12646.22	705466.63	814.79	788.84
Dead+Wind 210 deg - No Ice	7721.40	-6402.84	11089.94	616761.44	356387.64	-384.67
Dead+Wind 225 deg - No Ice	7721.40	-8998.65	8998.60	501429.56	501349.89	-991.57
Dead+Wind 240 deg - No Ice	7721.40	-11503.91	6641.80	366318.76	633740.28	-1475.57
Dead+Wind 270 deg - No Ice	7721.40	-12805.59	0.07	902.80	711957.69	-2228.27
Dead+Wind 300 deg - No Ice	7721.40	-10951.95	-6323.11	-351388.58	610994.40	-2308.10
Dead+Wind 315 deg - No Ice	7721.40	-8998.53	-8998.60	-499635.25	501344.33	-2142.19
Dead+Wind 330 deg - No Ice	7721.40	-6402.74	-11090.00	-614973.19	356384.07	-1834.49
Dead+Ice+Temp	13414.38	0.00	-0.00	1902.46	3069.03	-0.01
Dead+Wind 0 deg+Ice+Temp	13414.38	0.01	-13241.01	-728826.10	3066.36	-708.41
Dead+Wind 30 deg+Ice+Temp	13414.38	6459.24	-11187.84	-619552.15	-355726.80	426.09
Dead+Wind 45 deg+Ice+Temp	13414.38	9096.76	-9096.81	-503962.10	-502798.63	922.18
Dead+Wind 60 deg+Ice+Temp	13414.38	11094.70	-6405.51	-354700.51	-614594.27	1352.56
Dead+Wind 90 deg+Ice+Temp	13414.38	12918.57	0.07	1911.07	-714524.69	1896.53
Dead+Wind 120 deg+Ice+Temp	13414.38	11467.05	6620.50	367268.81	-629759.95	2013.14
Dead+Wind 135 deg+Ice+Temp	13414.38	9096.88	9096.81	507771.54	-502802.59	1759.05
Dead+Wind 150 deg+Ice+Temp	13414.38	6459.35	11187.77	623353.96	-355732.12	1479.07
Dead+Wind 180 deg+Ice+Temp	13414.38	0.01	12811.04	715116.00	3067.38	574.31
Dead+Wind 210 deg+Ice+Temp	13414.38	-6459.33	11187.78	623356.33	361867.83	-426.12
Dead+Wind 225 deg+Ice+Temp	13414.38	-9096.89	9096.81	507773.33	508939.90	-925.76

RISATower URS Corporation 500 Enterprise Drive, Suite 3B Rocky Hill, CT 06067 Phone: (860) 529-8882 FAX: (860) 529-3991	Job	92' Rohn SSV	Page	19 of 25
	Project	Glastonbury North	Date	09:32:36 09/25/08
	Client	Nextel Communications	Designed by	Kevin Barker

Load Combination	Vertical lb	Shear _x lb	Shear _y lb	Overturning Moment, M _x lb-ft	Overturning Moment, M _y lb-ft	Torque lb-ft
Dead+Wind 240 deg+Ice+Temp	13414.38	-11467.04	6620.51	367271.17	635897.34	-1304.82
Dead+Wind 270 deg+Ice+Temp	13414.38	-12918.57	0.07	1911.68	720662.82	-1896.50
Dead+Wind 300 deg+Ice+Temp	13414.38	-11094.69	-6405.52	-354701.81	620730.66	-1926.88
Dead+Wind 315 deg+Ice+Temp	13414.38	-9096.75	-9096.82	-503963.78	508933.71	-1758.14
Dead+Wind 330 deg+Ice+Temp	13414.38	-6459.22	-11187.84	-619553.68	361860.59	-1479.06
Dead+Wind 0 deg - Service	7721.40	0.00	-5188.88	-284589.59	815.88	-383.35
Dead+Wind 30 deg - Service	7721.40	2501.08	-4332.02	-239678.78	-138079.16	149.93
Dead+Wind 45 deg - Service	7721.40	3515.07	-3515.07	-194625.71	-194704.65	386.63
Dead+Wind 60 deg - Service	7721.40	4278.12	-2469.97	-136717.30	-237536.55	593.50
Dead+Wind 90 deg - Service	7721.40	5002.18	0.01	896.09	-276974.47	870.65
Dead+Wind 120 deg - Service	7721.40	4493.70	2594.44	143637.55	-246420.53	959.68
Dead+Wind 135 deg - Service	7721.40	3515.08	3515.07	196416.02	-194705.03	836.27
Dead+Wind 150 deg - Service	7721.40	2501.10	4332.01	241468.46	-138079.48	716.23
Dead+Wind 180 deg - Service	7721.40	0.00	4939.94	276120.61	816.02	308.14
Dead+Wind 210 deg - Service	7721.40	-2501.10	4332.01	241468.75	139711.64	-149.94
Dead+Wind 225 deg - Service	7721.40	-3515.08	3515.08	196416.38	196337.29	-387.18
Dead+Wind 240 deg - Service	7721.40	-4493.70	2594.44	143637.90	248052.89	-576.40
Dead+Wind 270 deg - Service	7721.40	-5002.18	0.01	896.22	278606.89	-870.65
Dead+Wind 300 deg - Service	7721.40	-4278.12	-2469.97	-136717.42	239168.77	-901.67
Dead+Wind 315 deg - Service	7721.40	-3515.07	-3515.08	-194625.87	196336.71	-835.74
Dead+Wind 330 deg - Service	7721.40	-2501.08	-4332.02	-239678.94	139711.07	-716.23

Solution Summary

Load Comb.	Sum of Applied Forces			Sum of Reactions			% Error
	PX lb	PY lb	PZ lb	PX lb	PY lb	PZ lb	
1	0.00	-7721.40	0.00	-0.00	7721.40	-0.00	0.000%
2	-0.00	-7721.40	-13284.01	-0.01	7721.40	13283.58	0.003%
3	6403.04	-7721.40	-11090.39	-6402.75	7721.40	11089.99	0.003%
4	8998.94	-7721.40	-8998.94	-8998.54	7721.40	8998.59	0.004%
5	10952.42	-7721.40	-6323.38	-10951.95	7721.40	6323.10	0.004%
6	12806.07	-7721.40	-0.00	-12805.59	7721.40	-0.07	0.003%
7	11504.29	-7721.40	6642.00	-11503.91	7721.40	-6641.79	0.003%
8	8998.94	-7721.40	8998.94	-8998.66	7721.40	-8998.59	0.003%
9	6403.04	-7721.40	11090.39	-6402.85	7721.40	-11089.93	0.003%
10	0.00	-7721.40	12646.76	-0.01	7721.40	-12646.22	0.004%
11	-6403.04	-7721.40	11090.39	6402.84	7721.40	-11089.94	0.003%
12	-8998.94	-7721.40	8998.94	8998.65	7721.40	-8998.60	0.003%
13	-11504.29	-7721.40	6642.00	11503.91	7721.40	-6641.80	0.003%
14	-12806.07	-7721.40	-0.00	12805.59	7721.40	-0.07	0.003%
15	-10952.42	-7721.40	-6323.38	10951.95	7721.40	6323.11	0.004%
16	-8998.94	-7721.40	-8998.94	8998.53	7721.40	8998.60	0.004%
17	-6403.04	-7721.40	-11090.39	6402.74	7721.40	11090.00	0.003%
18	-0.00	-13414.38	0.00	-0.00	13414.38	0.00	0.000%
19	0.00	-13414.38	-13241.76	-0.01	13414.38	13241.01	0.004%
20	6459.69	-13414.38	-11188.51	-6459.24	13414.38	11187.84	0.004%
21	9097.39	-13414.38	-9097.39	-9096.76	13414.38	9096.81	0.005%
22	11095.44	-13414.38	-6405.96	-11094.70	13414.38	6405.51	0.005%
23	12919.38	-13414.38	-0.00	-12918.57	13414.38	-0.07	0.004%
24	11467.70	-13414.38	6620.88	-11467.05	13414.38	-6620.50	0.004%
25	9097.39	-13414.38	9097.39	-9096.88	13414.38	-9096.81	0.004%
26	6459.69	-13414.38	11188.51	-6459.35	13414.38	-11187.77	0.004%
27	0.00	-13414.38	12811.91	-0.01	13414.38	-12811.04	0.005%
28	-6459.69	-13414.38	11188.51	6459.33	13414.38	-11187.78	0.004%
29	-9097.39	-13414.38	9097.39	9096.89	13414.38	-9096.81	0.004%
30	-11467.70	-13414.38	6620.88	11467.04	13414.38	-6620.51	0.004%
31	-12919.38	-13414.38	-0.00	12918.57	13414.38	-0.07	0.004%

RISATower URS Corporation 500 Enterprise Drive, Suite 3B Rocky Hill, CT 06067 Phone: (860) 529-8882 FAX: (860) 529-3991	Job	92' Rohn SSV	Page	20 of 25
	Project	Glastonbury North	Date	09:32:36 09/25/08
	Client	Nextel Communications	Designed by	Kevin Barker

Load Comb.	Sum of Applied Forces			Sum of Reactions			% Error
	PX lb	PY lb	PZ lb	PX lb	PY lb	PZ lb	
32	-11095.44	-13414.38	-6405.96	11094.69	13414.38	6405.52	0.005%
33	-9097.39	-13414.38	-9097.39	9096.75	13414.38	9096.82	0.005%
34	-6459.69	-13414.38	-11188.51	6459.22	13414.38	11187.84	0.004%
35	-0.00	-7721.40	-5189.07	-0.00	7721.40	5188.88	0.002%
36	2501.19	-7721.40	-4332.18	-2501.08	7721.40	4332.02	0.002%
37	3515.21	-7721.40	-3515.21	-3515.07	7721.40	3515.07	0.002%
38	4278.29	-7721.40	-2470.07	-4278.12	7721.40	2469.97	0.002%
39	5002.37	-7721.40	-0.00	-5002.18	7721.40	-0.01	0.002%
40	4493.86	-7721.40	2594.53	-4493.70	7721.40	-2594.44	0.002%
41	3515.21	-7721.40	3515.21	-3515.08	7721.40	-3515.07	0.002%
42	2501.19	-7721.40	4332.18	-2501.10	7721.40	-4332.01	0.002%
43	-0.00	-7721.40	4940.14	-0.00	7721.40	-4939.94	0.002%
44	-2501.19	-7721.40	4332.18	2501.10	7721.40	-4332.01	0.002%
45	-3515.21	-7721.40	3515.21	3515.08	7721.40	-3515.08	0.002%
46	-4493.86	-7721.40	2594.53	4493.70	7721.40	-2594.44	0.002%
47	-5002.37	-7721.40	-0.00	5002.18	7721.40	-0.01	0.002%
48	-4278.29	-7721.40	-2470.07	4278.12	7721.40	2469.97	0.002%
49	-3515.21	-7721.40	-3515.21	3515.07	7721.40	3515.08	0.002%
50	-2501.19	-7721.40	-4332.18	2501.08	7721.40	4332.02	0.002%

Non-Linear Convergence Results

Load Combination	Converged?	Number of Cycles	Displacement Tolerance	Force Tolerance
1	Yes	4	0.00000001	0.00000001
2	Yes	4	0.00000001	0.00010854
3	Yes	4	0.00000001	0.00012544
4	Yes	4	0.00000001	0.00013614
5	Yes	4	0.00000001	0.00014050
6	Yes	4	0.00000001	0.00012601
7	Yes	4	0.00000001	0.00010854
8	Yes	4	0.00000001	0.00011431
9	Yes	4	0.00000001	0.00012592
10	Yes	4	0.00000001	0.00014044
11	Yes	4	0.00000001	0.00012539
12	Yes	4	0.00000001	0.00011397
13	Yes	4	0.00000001	0.00010851
14	Yes	4	0.00000001	0.00012587
15	Yes	4	0.00000001	0.00014031
16	Yes	4	0.00000001	0.00013625
17	Yes	4	0.00000001	0.00012583
18	Yes	4	0.00000001	0.00000001
19	Yes	4	0.00000001	0.00018831
20	Yes	4	0.00000001	0.00020470
21	Yes	4	0.00000001	0.00021561
22	Yes	4	0.00000001	0.00022008
23	Yes	4	0.00000001	0.00020515
24	Yes	4	0.00000001	0.00018846
25	Yes	4	0.00000001	0.00019391
26	Yes	4	0.00000001	0.00020524
27	Yes	4	0.00000001	0.00021997
28	Yes	4	0.00000001	0.00020459
29	Yes	4	0.00000001	0.00019348
30	Yes	4	0.00000001	0.00018822
31	Yes	4	0.00000001	0.00020476
32	Yes	4	0.00000001	0.00021966

RISATower URS Corporation 500 Enterprise Drive, Suite 3B Rocky Hill, CT 06067 Phone: (860) 529-8882 FAX: (860) 529-3991	Job	92' Rohn SSV	Page	21 of 25
	Project	Glastonbury North	Date	09:32:36 09/25/08
	Client	Nextel Communications	Designed by	Kevin Barker

33	Yes	4	0.00000001	0.00021554
34	Yes	4	0.00000001	0.00020497
35	Yes	4	0.00000001	0.00011755
36	Yes	4	0.00000001	0.00012402
37	Yes	4	0.00000001	0.00012828
38	Yes	4	0.00000001	0.00013001
39	Yes	4	0.00000001	0.00012412
40	Yes	4	0.00000001	0.00011772
41	Yes	4	0.00000001	0.00011980
42	Yes	4	0.00000001	0.00012411
43	Yes	4	0.00000001	0.00012992
44	Yes	4	0.00000001	0.00012393
45	Yes	4	0.00000001	0.00011959
46	Yes	4	0.00000001	0.00011748
47	Yes	4	0.00000001	0.00012377
48	Yes	4	0.00000001	0.00012965
49	Yes	4	0.00000001	0.00012800
50	Yes	4	0.00000001	0.00012385

Maximum Tower Deflections - Service Wind

Section No.	Elevation ft	Horz. Deflection in	Gov. Load Comb.	Tilt °	Twist °
T1	92 - 80	1.640	40	0.1397	0.0090
T2	80 - 60	1.284	40	0.1342	0.0086
T3	60 - 40	0.744	46	0.1106	0.0050
T4	40 - 20	0.337	46	0.0707	0.0026
T5	20 - 0	0.093	46	0.0325	0.0011

Critical Deflections and Radius of Curvature - Service Wind

Elevation ft	Appurtenance	Gov. Load Comb.	Deflection in	Tilt °	Twist °	Radius of Curvature ft
102.00	DB420	40	1.640	0.1397	0.0090	219981
88.00	(3) DUO1417-8686	40	1.521	0.1382	0.0090	219981
79.00	DB806-XT	40	1.255	0.1335	0.0085	84146
73.00	PR-950	40	1.084	0.1283	0.0075	56292
65.00	APXV18-206517S-C w/ mounting hardware	46	0.869	0.1184	0.0060	38959

Maximum Tower Deflections - Design Wind

Section No.	Elevation ft	Horz. Deflection in	Gov. Load Comb.	Tilt °	Twist °
T1	92 - 80	4.190	7	0.3563	0.0240
T2	80 - 60	3.282	7	0.3423	0.0235
T3	60 - 40	1.907	30	0.2824	0.0131
T4	40 - 20	0.864	30	0.1811	0.0065

RISATower

URS Corporation
 500 Enterprise Drive, Suite 3B
 Rocky Hill, CT 06067
 Phone: (860) 529-8882
 FAX: (860) 529-3991

Job

92' Rohn SSV

Page

22 of 25

Project

Glastonbury North

Date

09:32:36 09/25/08

Client

Nextel Communications

Designed by

Kevin Barker

Section No.	Elevation ft	Horz. Deflection in	Gov. Load Comb.	Tilt °	Twist °
T5	20-0	0.238	30	0.0834	0.0028

Critical Deflections and Radius of Curvature - Design Wind

Elevation ft	Appurtenance	Gov. Load Comb.	Deflection in	Tilt °	Twist °	Radius of Curvature ft
102.00	DB420	7	4.190	0.3563	0.0240	86779
88.00	(3) DUO1417-8686	7	3.885	0.3526	0.0242	86779
79.00	DB806-XT	7	3.208	0.3406	0.0232	33145
73.00	PR-950	30	2.773	0.3274	0.0207	22196
65.00	APXV18-206517S-C w/ mounting hardware	30	2.226	0.3024	0.0160	15383

Bolt Design Data

Section No.	Elevation ft	Component Type	Bolt Grade	Bolt Size in	Number Of Bolts	Maximum Load per Bolt lb	Allowable Load lb	Ratio Load Allowable	Allowable Ratio	Criteria
T1	92	Leg	A325N	0.6300	4	221.77	13711.70	0.016 ✓	1.333	Bolt Tension
		Diagonal	A325N	0.5000	1	1789.95	4123.34	0.434 ✓	1.333	Bolt Shear
		Top Girt	A325N	0.5000	1	146.90	4123.34	0.036 ✓	1.333	Bolt Shear
T2	80	Leg	A325N	0.6300	4	1652.17	13715.80	0.120 ✓	1.333	Bolt Tension
		Diagonal	A325N	0.5000	1	2019.04	4123.34	0.490 ✓	1.333	Bolt Shear
T3	60	Leg	A325N	0.6300	4	4735.67	13715.90	0.345 ✓	1.333	Bolt Tension
		Diagonal	A325N	0.5000	1	2527.24	4123.34	0.613 ✓	1.333	Bolt Shear
T4	40	Leg	A325N	0.6300	4	7831.16	13715.90	0.571 ✓	1.333	Bolt Tension
		Diagonal	A325N	0.5000	1	2979.60	4123.34	0.723 ✓	1.333	Bolt Shear
T5	20	Leg	A325N	0.7500	4	10833.50	19438.60	0.557 ✓	1.333	Bolt Tension
		Diagonal	A325N	0.5000	1	3442.56	4123.34	0.835 ✓	1.333	Bolt Shear

Compression Checks**Leg Design Data (Compression)**

Section No.	Elevation ft	Size	L ft	L _n ft	Kl/r	F _a ksi	A in ²	Actual P lb	Allow. P _a lb	Ratio P/P _a
-------------	-----------------	------	---------	----------------------	------	-----------------------	----------------------	----------------	-----------------------------	------------------------

RISATower URS Corporation 500 Enterprise Drive, Suite 3B Rocky Hill, CT 06067 Phone: (860) 529-8882 FAX: (860) 529-3991	Job	92' Rohn SSV	Page	23 of 25
	Project	Glastonbury North	Date	09:32:36 09/25/08
	Client	Nextel Communications	Designed by	Kevin Barker

Section No.	Elevation	Size	L	L _n	Kl/r	F _a	A	Actual P	Allow. P _a	Ratio P
	ft		ft	ft		ksi	in ²	lb	lb	P _a
T1	92 - 80	P2.375x.154	12.00	6.00	91.5 K=1.00	16.619	1.0745	-4861.68	17858.20	0.272 ✓
T2	80 - 60	P2.875x.203	20.03	5.01	63.4 K=1.00	22.122	1.7040	-18480.90	37697.80	0.490 ✓
T3	60 - 40	P2.875x.203	20.03	6.68	84.6 K=1.00	18.081	1.7040	-32008.10	30810.90	1.039 ✓
T4	40 - 20	P2.875x.276	20.03	6.68	86.7 K=1.00	17.634	2.2535	-45922.10	39739.10	1.156 ✓
T5	20 - 0	P3.5x.3	20.03	6.68	70.5 K=1.00	20.840	3.0159	-60458.70	62852.90	0.962 ✓

Diagonal Design Data (Compression)

Section No.	Elevation	Size	L	L _n	Kl/r	F _a	A	Actual P	Allow. P _a	Ratio P
	ft		ft	ft		ksi	in ²	lb	lb	P _a
T1	92 - 80	L1 1/2x1 1/2x3/16	8.88	4.15	169.7 K=1.00	5.188	0.5273	-1789.95	2736.11	0.654 ✓
T2	80 - 60	L1 1/2x1 1/2x3/16	9.70	4.69	191.8 K=1.00	4.059	0.5273	-2019.04	2140.32	0.943 ✓
T3	60 - 40	L1 3/4x1 3/4x3/16	12.21	5.99	209.4 K=1.00	3.405	0.6211	-2408.24	2114.67	1.139 ✓
T4	40 - 20	KL/R > 200 (C) - 49 L2x2x3/16	13.96	6.87	209.2 K=1.00	3.412	0.7150	-2979.60	2439.58	1.221 ✓
T5	20 - 0	KL/R > 200 (C) - 71 L2 1/2x2 1/2x3/16	15.17	7.45	180.5 K=1.00	4.581	0.9020	-3335.41	4132.15	0.807 ✓

Top Girt Design Data (Compression)

Section No.	Elevation	Size	L	L _n	Kl/r	F _a	A	Actual P	Allow. P _a	Ratio P
	ft		ft	ft		ksi	in ²	lb	lb	P _a
T1	92 - 80	L2x2x3/16	6.52	5.99	182.4 K=1.00	4.489	0.7150	-146.90	3209.33	0.046 ✓

Tension Checks

Leg Design Data (Tension)

RISATower URS Corporation 500 Enterprise Drive, Suite 3B Rocky Hill, CT 06067 Phone: (860) 529-8882 FAX: (860) 529-3991	Job	92' Rohn SSV	Page	24 of 25
	Project	Glastonbury North	Date	09:32:36 09/25/08
	Client	Nextel Communications	Designed by	Kevin Barker

Section No.	Elevation ft	Size	L ft	L _u ft	Kl/r	F _a ksi	A in ²	Actual P lb	Allow. P _a lb	Ratio P P _a
T1	92 - 80	P2.375x.154	12.00	6.00	91.5	30.000	1.0745	3128.13	32235.90	0.097 ✓
T2	80 - 60	P2.875x.203	20.03	5.01	63.4	30.000	1.7040	15308.40	51121.50	0.299 ✓
T3	60 - 40	P2.875x.203	20.03	6.68	84.6	30.000	1.7040	27198.00	51121.50	0.532 ✓
T4	40 - 20	P2.875x.276	20.03	6.68	86.7	30.000	2.2535	39391.00	67606.20	0.583 ✓
T5	20 - 0	P3.5x.3	20.03	6.68	70.5	30.000	3.0159	51123.60	90477.90	0.565 ✓

Diagonal Design Data (Tension)

Section No.	Elevation ft	Size	L ft	L _u ft	Kl/r	F _a ksi	A in ²	Actual P lb	Allow. P _a lb	Ratio P P _a
T1	92 - 80	L1 1/2x1 1/2x3/16	8.88	4.15	113.4	29.000	0.3076	1736.12	8920.90	0.195 ✓
T2	80 - 60	L1 1/2x1 1/2x3/16	9.70	4.69	127.6	29.000	0.3076	1914.90	8920.90	0.215 ✓
T3	60 - 40	L1 3/4x1 3/4x3/16	12.21	5.99	137.7	29.000	0.3779	2527.24	10960.00	0.231 ✓
T4	40 - 20	L2x2x3/16	13.36	6.57	131.1	29.000	0.4484	2774.66	13002.40	0.213 ✓
T5	20 - 0	L2 1/2x2 1/2x3/16	15.79	7.75	122.2	29.000	0.5886	3442.56	17069.70	0.202 ✓

Top Girt Design Data (Tension)

Section No.	Elevation ft	Size	L ft	L _u ft	Kl/r	F _a ksi	A in ²	Actual P lb	Allow. P _a lb	Ratio P P _a
T1	92 - 80	L2x2x3/16	6.52	5.99	123.0	29.000	0.4484	94.40	13002.40	0.007 ✓

Section Capacity Table

Section No.	Elevation ft	Component Type	Size	Critical Element	P lb	SF*P _{allow} lb	% Capacity	Pass Fail
T1	92 - 80	Leg	P2.375x.154	3	-4861.68	23804.98	20.4	Pass
T2	80 - 60	Leg	P2.875x.203	20	-18480.90	50251.17	36.8	Pass
T3	60 - 40	Leg	P2.875x.203	46	-32008.10	41070.93	77.9	Pass
T4	40 - 20	Leg	P2.875x.276	67	-45922.10	52972.22	86.7	Pass
T5	20 - 0	Leg	P3.5x.3	88	-60458.70	83782.91	72.2	Pass
T1	92 - 80	Diagonal	L1 1/2x1 1/2x3/16	8	-1789.95	3647.23	49.1	Pass

RISATower URS Corporation 500 Enterprise Drive, Suite 3B Rocky Hill, CT 06067 Phone: (860) 529-8882 FAX: (860) 529-3991	Job	92' Rohn SSV	Page	25 of 25
	Project	Glastonbury North	Date	09:32:36 09/25/08
	Client	Nextel Communications	Designed by	Kevin Barker

Section No.	Elevation ft	Component Type	Size	Critical Element	P lb	SF*P _{allow} lb	% Capacity	Pass Fail
T2	80 - 60	Diagonal	L1 1/2x1 1/2x3/16	25	-2019.04	2853.05	70.8	Pass
T3	60 - 40	Diagonal	L1 3/4x1 3/4x3/16	49	-2408.24	2818.85	85.4	Pass
T4	40 - 20	Diagonal	L2x2x3/16	71	-2979.60	3251.96	91.6	Pass
T5	20 - 0	Diagonal	L2 1/2x2 1/2x3/16	98	-3335.41	5508.16	60.6	Pass
T1	92 - 80	Top Girt	L2x2x3/16	6	-146.90	4278.04	62.6 (b)	Pass
							Summary	
							Lcg (T4)	86.7 Pass
							Diagonal (T4)	91.6 Pass
							Top Girt (T1)	3.4 Pass
							Bolt Checks	62.6 Pass
							RATING =	91.6 Pass

Anchor Bolt Analysis

ANCHOR BOLT ANALYSIS

Input Data

Max Pier Reactions:

Uplift:	Uplift := 53-kips	user input
Shear:	Shear := 8-kips	user input
Compression:	Compression := 62-kips	user input

Anchor Bolt Data:

Use ASTM A354BC

Number of Anchor Bolts = N	$N_b := 4$	user input
Bolt Ultimate Strength:	$F_u := 125\text{-ksi}$	user input
Bolt Yield Strength:	$F_y := 109\text{-ksi}$	user input
Bolt Modulus:	$E := 29000\text{-ksi}$	user input
Thickness of Anchor Bolts	$D := 0.75\text{in}$	user input
Threads per Inch:	$n := 7$	user input
Coefficient of Friction:	$\mu := 0.55$	user input (for baseplate with grout ASCE 10-97)

Anchor Bolt Area:

Gross Area of Bolt:

$$A_g := \frac{\pi}{4} \cdot D^2 \quad A_g = 0.442 \cdot \text{in}^2$$

Net Area of Bolt:

$$A_n := \frac{\pi}{4} \cdot \left(D - \frac{0.9743 \cdot \text{in}}{n} \right)^2 \quad A_n = 0.293 \cdot \text{in}^2$$

Check Tensile Forces:

Maximum Tensile Force (Gross Area):

$$\text{AllowableTension} := 1.333 \cdot (0.33 \cdot A_g \cdot F_u) \quad \text{AllowableTension} = 24.3 \cdot \text{kips}$$

Note: 1.333 increase allowed per TIA/EIA

Maximum Tensile Force (Net Area):

$$F_{\text{net.area}} := 1.333 \cdot (0.60 \cdot A_n \cdot F_y) \quad F_{\text{net.area}} = 25.5 \cdot \text{kips}$$

Note: 1.333 increase allowed per TIA/EIA

Applied Tension:

$$\text{MaxTension} := \frac{\text{Uplift}}{N} \quad \text{MaxTension} = 13.3 \cdot \text{kips}$$

Check Stresses:

$$\frac{\text{MaxTension}}{F_{\text{net.area}}} = 0.52$$

$$\text{Condition1} := \text{if} \left(\frac{\text{MaxTension}}{F_{\text{net.area}}} \leq 1.00, \text{"OK"}, \text{"Overstressed"} \right)$$

$$\boxed{\text{Condition1} = \text{"OK"}}$$

Check Anchor Bolt Area:

Based on the ASCE 10-97 Design of Latticed Steel Transmission Structures

Required Area:

$$A_{s1} := \frac{\text{Uplift}}{F_y} + \frac{\text{Shear}}{\mu \cdot 0.85 \cdot F_y} \quad A_{s1} = 0.6 \cdot \text{in}^2$$

$$A_{s2} := \left\lceil \frac{\text{Shear} - (0.3 \cdot \text{Compression})}{\mu \cdot 0.85 \cdot F_y} \right\rceil \quad A_{s2} = 0.2 \cdot \text{in}^2$$

Provided Area:

$$A_{s\text{provided}} := A_n \cdot N \quad A_{s\text{provided}} = 1.2 \cdot \text{in}^2$$

$$\text{Condition2} := \text{if} \left(\frac{A_{s1}}{A_{s\text{provided}}} \leq 1.00, \text{"OK"}, \text{"Overstressed"} \right) \quad \frac{A_{s1}}{A_{s\text{provided}}} = 0.5$$

Condition2 = "OK"

$$\text{Condition3} := \text{if} \left(\frac{A_{s2}}{A_{s\text{provided}}} \leq 1.00, \text{"OK"}, \text{"Overstressed"} \right) \quad \frac{A_{s2}}{A_{s\text{provided}}} = 0.2$$

Condition3 = "OK"

Units

Angular

$$\text{rad} \equiv 1$$

$$\text{deg} \equiv \pi \cdot \frac{\text{rad}}{180}$$

Weight

$$\text{lb} \equiv \text{lbf}$$

$$\text{kips} \equiv 1000 \cdot \text{lb}$$

$$\text{tons} \equiv 2000 \cdot \text{lb}$$

$$\text{k} \equiv \text{kips}$$

Unit Weight

$$\text{plf} \equiv \frac{\text{lb}}{\text{ft}}$$

$$\text{klf} \equiv \frac{\text{kips}}{\text{ft}}$$

Pressure

$$\text{psf} \equiv \frac{\text{lb}}{\text{ft}^2}$$

$$\text{psi} \equiv \frac{\text{lb}}{\text{in}^2}$$

$$\text{ksf} \equiv \frac{\text{kips}}{\text{ft}^2}$$

$$\text{ksi} \equiv \frac{\text{kips}}{\text{in}^2}$$

Density

$$\text{pcf} \equiv \frac{\text{lb}}{\text{ft}^3}$$