

July 15, 2013

**ORIGINAL** 

David Martin and Members of the Siting Council Connecticut Siting Council Ten Franklin Square New Britain, CT 06051



RE:

Notice of Exempt Modification 2577 Main Street Glastonbury, CT 06033 N 41° 42′ 51.76″ W 72° 36′ 47.03″

Dear Mr. Martin and Members of the Siting Council:

On behalf of Sprint Spectrum, SBA Communications is submitting an exempt modification application to the Connecticut Siting council for modification of existing equipment at a tower facility located at 2577 Main Street, Glastonbury, CT.

The 2577 Main Street facility consists of a 130' LATTICE Tower owned and operated by SBA 2012 TC Assets, LLC. In order to accommodate technological changes and enhance system performance in the State of Connecticut, Sprint Spectrum plans to modify the equipment configurations at many of its existing cell sites. Please accept this letter and attachments as notification, pursuant to R.C.S.A. Section 16-50j-73, of construction which constitutes an exempt modification pursuant to R.C.S.A. Section 16-50j-72(b)(2). In compliance with R.C.S.A. Section 16-50j-73, a copy of this letter and attachments is being sent to the chief elected official of the municipality in which the affected cell site is located.

As part of Sprint's Network Vision modification project, Sprint desires to upgrade their equipment to meet the new standards of 4G technology. The new equipment will allow customers to download files and browse the internet at a high rate of speed while also allowing their phones to be compatible with the latest 4G technology.

Attached is a summary of the planned modifications, including power density calculations reflecting the change in Sprint's operations at the site along with the required fee of \$625.

The changes to the facility do not constitute modifications as defined in Connecticut General Statutes ("C.G.S.") Section 16-50i(d) because the general physical characteristics of the facility will not be



significantly changed or altered. Rather, the planned changes to the facility fall squarely within those activities explicitly provided for in R.C.S.A. Section 16-50j-72(b)(2).

- 1. The overall height of the structure will be unaffected.
- 2. The proposed changes will not extend the site boundaries. There will be no effect on the site compound other than the new equipment cabinets.
- 3. The proposed changes will not increase the noise level at the existing facility by six decibels or more.
- 4. The changes in radio frequency power density will not increase the calculated "worst case" power density for the combined operations at the site to a level at or above the applicable standard for uncontrolled environments as calculated for a mixed frequency site.

For the foregoing reasons, SBA Communications on behalf of Sprint Spectrum, respectfully submits that he proposed changes at the referenced site constitute exempt modifications under R.C.S.A. Section 16-50j-72(b)(2).

Please feel free to call me at (508) 614-0389 with any questions you may have concerning this matter.

Thank you,

Rick Woods

SBA Communications Corporation 33 Boston Post Road West Suite 320

Marlborough, MA 01752 508-251-1691 x 319 + T

508-251-1755 + F

508-614-0389 + C

rwoods@sbasite.com



# Sprint Spectrum Equipment Modification

2577 Main Street, Glastonbury, CT Site number CT43XC822

**Tower Owner:** 

SBA 2012 TC Assets, LLC

**Equipment Configuration:** 

**LATTICE Tower** 

# Current and/or approved:

(3) existing CDMA Antennas and coax

Existing Modcell 4.0 Cabinet

Existing GPS Unit

Existing Local Exchange Carrier landline backhaul facilities

# **Planned Modifications:**

- · Install (1) BBU Cabinet and Fiber Distribution Box within existing lease area
- Retrofit existing Modcell 4.0 Cabinet
- Replace (3) existing CDMA Antennas with (3) Network Vision Antenna and (6) RRHs
- Install (3) Hybriflex cables from fiber distribution box to antenna (remove existing CDMA Coax)
- Replace existing GPS Unit with new GPS Unit
- Replace existing Local Exchange Carrier landline backhaul facilities with proposed Alternative Access Vendor fiber optic facilities including overhead/underground conduits and NID

# Structural Information:

The attached structural analysis demonstrates that the tower and foundation will have adequate structural capacity to accommodate the proposed modifications.

# **Power Density:**

The anticipated Maximum Composite contributions from the Sprint facility are 29.763% of the allowable FCC established general public limit. The anticipated composite MPE value for this site assuming all carriers present is 60.803% of the allowable FCC established general public limit sampled at the ground level.

Carrier	MPE %
Sprint	29.763%
T-Mobile	14.330%
Pocket	6.810%
Clearwire	1.160%
Nextel	3.480%
AT&T	5.260%
Total Site MPE %	60.803%



July 15, 2013

Mr. Richard J. Johnson Town Manager Town of Glastonbury 2155 Main Street Glastonbury, CT 06033



RE: Telecommunications Facility @ 2577 Main Street, Glastonbury, CT

Dear Mr. Johnson,

In order to accommodate technological changes and enhance system performance in the State of Connecticut, Sprint Spectrum will be changing its equipment configuration at certain cell sites.

As required by Regulations of Connecticut State Agencies (R.C.S.A.) Section 16-50j-73, the Connecticut Siting Council has been notified of the changes and will review Sprint's proposal. Please accept this letter as notification under Section 16-50j-73 of construction which constitutes an exempt modification pursuant to R.C.S.A. Section 16-50j-72(b)(2).

The accompanying letter to the Siting Council fully describes Sprint's proposal for the referenced cell site. However, if you have any questions or require any further information on our plans or the Siting Council's procedures, please call me at (508) 614-0389.

Thank you,

Rick Woods

SBA Communications Company
33 Boston Post Road West Suite 320

Marlborough, MA 01752

508-251-1691 x 319 + T

508-251-1755 + F

508-614-0389 + C

rwoods@sbasite.com



FDH Engineering, Inc., 6521 Meridien Drive Raleigh, NC 27616, Ph. 919.755.1012

# Structural Analysis for SBA Network Services, Inc.

130' Self-Support Tower

SBA Site Name: Glastonbury-Main St SBA Site ID: CT46126-A-03 Sprint Site ID: CT43XC822 Sprint Site Name: Glastonbury Nextel

FDH Project Number 1338401400

**Analysis Results** 

Tower Components	95.1%	Sufficient
Foundation	65.0%	Sufficient

Prepared By:

David Zambrano, El Project Engineer Christopher M Murphy, PE President CT PE License No. 25842

FDH Engineering, Inc. 6521 Meridien Drive Raleigh, NC 27616 (919) 755-1012 info@fdh-inc.com



Reviewed By:

Christopher M. Murphy

July 15, 2013

Prepared pursuant to TIA/EIA-222-F Structural Standards for Steel Antenna Towers and Antenna Supporting Structures & 2005 Connecticut Building Code (CTBC)

# TABLE OF CONTENTS EXECUTIVE SUMMARY. 3 Conclusions. 3 Recommendations. 3 APPURTENANCE LISTING 4 RESULTS. 6 GENERAL COMMENTS 9 LIMITATIONS. 9

# **EXECUTIVE SUMMARY**

At the request of SBA Network Services, Inc., FDH Engineering, Inc. performed a structural analysis of the existing self-supported tower located in Glastonbury, CT to determine whether the tower is structurally adequate to support both the existing and proposed loads pursuant to the *Structural Standards for Steel Antenna Towers and Antenna Supporting Structures, TIA/EIA-222-F.* Information pertaining to the existing/proposed antenna loading, current tower geometry, the member sizes, geotechnical data, and foundation dimensions was obtained from:

	Fred A. Nudd Corporation (Project No. 6893) Design of 130' Lattice Tower dated September 12, 1999
	Vertical Solutions, Inc. (Project No. 121081 Rev 0) Rigorous Structural Analysis dated June 4, 2012
	Vertical Solutions, Inc. (Project No. 130126.01 Rev 0) Pre-Modification Installation Letter dated February 14, 2013
	Vertical Solutions, Inc. (Site No. CT46126-A) Modification Drawings for a 130' Self-Support Tower dated December 6, 2012
	Tectonic Engineering Consultants, P.C (W.O No. 1170.C057) Boring Logs and Results of Laboratory Testing dated August 26, 1999
	FDH Engineering, Inc. (Project No. 1338401400) Modification Drawings for a 130' Self-Support Tower dated June 14, 2013
	SBA Network Services, Inc.

The basic design wind speed per the TIA/EIA-222-F standards & 2005 CTBC is 80 mph without ice and 38 mph with 1" radial ice. Ice is considered to increase in thickness with height.

# Conclusions

With the existing and proposed antennas from Sprint in place at 118.5 ft, the tower meets the requirements of the *TIA/EIA-222-F* standards & *2005 CTBC* provided the **Recommendations** listed below are satisfied. Furthermore, provided the foundation was constructed per the original design drawings (see Fred A. Nudd Corporation Project No. 6893), the foundation should have the necessary capacity to support both the proposed and existing loading. For a more detailed description of the analysis of the tower, see the **Results** section of this report.

Our structural analysis has been performed assuming all information provided to FDH Engineering, Inc. is accurate (i.e., the steel data, tower layout, existing antenna loading, and proposed antenna loading) and that the tower has been properly erected and maintained per the original design drawings.

# Recommendations

To ensure the requirements of the *TIA/EIA-222-F* standards & *2005 CTBC* are met with the existing and proposed loading in place, we have the following recommendations:

- 1. Coax lines must be installed as shown in Figure 1.
- RRU/RRH Stipulation: The proposed equipment may be installed in any arrangement as determined by the client.
- 3. Modifications listed in FDH Engineering, Inc. (Project No. 1338401400) Modification Drawings for a 130' Self-Support Tower dated June 14, 2013 must be correctly installed in order for this analysis to be valid.

# APPURTENANCE LISTING

The proposed and existing antennas with their corresponding cables/coax lines are shown in **Table 1**. If the actual layout determined in the field deviates from the layout, FDH Engineering, Inc. should be contacted to perform a revised analysis.

Table 1 - Appurtenance Loading

# **Existing Loading:**

Antenna Elevation (ft)	Description	Coax and Lines	Carrier	Mount Elevation (ft)	Mount Type
128	(12) Decibel DB844H90E-M (2) Argus technologies LLPX310R (1) Kathrein 840 10054 (3) 24"x14"x9" TMAs (1) Motorola TIMING 2000	(12) 1-1/4" (6) 5/16" (4) 1/2"	Sprint/Clearwire	1281	(3) T-Frames
124	(3) IDU Modem (3) Andrew VHLP2.5 Dishes				
118.5	(12) Swedcom ALP 9212-N	(12) 1-5/8"	Sprint	118.5	(3) T-Arms
110	(6) Allgon 7700.00 (2) KMW AM-X-CD-16-65-00T-RET (1) Andrew SBNH-1D6565C (6) Powerwave LGP13519 TMAs (6) Powerwave LGP21401 TMAs (6) Ericsson RRUS-11 1900MHz RRUs (1) Raycap DC6-48-60-18-8F Surge Arrestor	(12) 1-1/4" (1) 3/8"	AT&T	110 <sup>2</sup>	(3) T-Frames
100	(3) RFS APXV18-206517S-C	(6) 1-5/8"	Pocket	100	(3) Standoffs
93	(6) EMS RR65-19-02DP (3) RFS APX16DWV-16WV-S-E-ACU (3) 6.3"x7.7"x3" TMAs	(18) 1-5/8"	T-Mobile	93	(3) T-Frames
55.5	(1) GPS	(1) 1/2"	<u> </u>	55.5	(1) Standoff
50.5	(2) GPS	(2) 1/2"	=	50.5	(2) Standoffs

<sup>1.</sup> Sprint/Clearwire has (6) 5/16" and (3) ½" coax installed inside (2) 2" conduits.

# Proposed Loading:

Antenna Elevation (ft)	Description	Coax and Lines	Carrier	Mount Elevation (ft)	Mount Type
118.5	(2) RFS APXVSPP18-C-A20 (1) Powerwave P40-16-XLPP-RR-A (3) Alcatel Lucent 1900 MHz RRUs (3) Alcatel Lucent 800 MHz RRUs (4) RFS ACU-A20-N RETs (3) Alcatel Lucent 800 MHz Filters	(3) 1-1/4"	Sprint	118.5	(3) T-Arms

<sup>2.</sup> AT&T has (1) 3/8" coax installed inside (1) 3" conduit.




Figure 1 – Assumed Coax Layout

# **RESULTS**

The following yield strength of steel for individual members was used for analysis:

Table 2 - Material Strength

Member Type	Yield Strength
Legs	54 ksi & 45 ksi
Bracing	36 ksi

**Table 3** displays the summary of the ratio (as a percentage) of force in the member to their capacities. Values greater than 100% indicate locations where the maximum force in the member exceeds its capacity. *Note: Capacities up to 100% are considered acceptable.* **Table 4** displays the maximum foundation reactions. **Table 5** displays the maximum antennas rotations at service wind speeds.

If the assumptions outlined in this report differ from actual field conditions, FDH Engineering, Inc. should be contacted to perform a revised analysis. Furthermore, as no information pertaining to the allowable twist and sway requirements for the existing or proposed appurtenances was provided, deflection and rotation were not taken into consideration when performing this analysis.

See the Appendix for detailed modeling information.

Table 3 - Summary of Working Percentage of Structural Components

Section No.	Elevation ft	Component Type	Size	% Capacity	Pass Fail
T1	130 - 120	Leg	1 1/2	26.0	Pass
		Diagonal	1/2	65.0	Pass
L BUT ON		Horizontal	L1 1/4x1 1/4x3/16	7.5	Pass
		Top Girt	L1 1/4x1 1/4x3/16	0.7	Pass
T2	120 - 117.143	Leg	2	19.7	Pass
		Diagonal	3/4	28.1	Pass
		Horizontal	L1 1/4x1 1/4x3/16	3.9	Pass
T3	117.143 - 114.286	Leg	2	27.7	Pass
		Diagonal	3/4	36.2	Pass
		Horizontal	L1 1/4x1 1/4x3/16	5.9	Pass
T4	114.286 - 111.429	Leg	2	36.6	Pass
		Diagonal	3/4	36.0	Pass
		Horizontal	L1 1/4x1 1/4x3/16	13.5	Pass
T5	111.429 - 108.571	Leg	2	47.3	Pass
		Diagonal	3/4	45.5	Pass
		Horizontal	L1 1/4x1 1/4x3/16	12.7	Pass
T6	108.571 - 105.714	Leg	2	59.6	Pass
		Diagonal	3/4	56.4	Pass
		Horizontal	L1 1/4x1 1/4x3/16	17.3	Pass
T7	105.714 - 102.857	Leg	2	73.1	Pass
700770	**************************************	Diagonal	3/4	57.2	Pass
		Horizontal	L1 1/4x1 1/4x3/16	26.7	Pass
Т8	102.857 - 100	Leg	2	70.3	Pass
	360-64	Diagonal	3/4	77.5	Pass

					outy 10, 20
Section No.	Elevation ft	Component Type	Size	% Capacity	Pass Fail
100000		Horizontal	L1 1/4x1 1/4x3/16	31.2	Pass
		Secondary Horizontal	L2x2x1/8	10.5 34.0 (b)	Pass
Т9	100 - 96	Leg	P4x.237 (4.50 OD)	66.9	Pass
		Diagonal	L1 1/2x1 1/2x3/16	40.4 88.5 (b)	Pass
		Top Girt	L1 1/4x1 1/4x3/16	22.7 49.8 (b)	Pass
T10	96 - 92	Leg	P4x.237 (4.50 OD)	77.3	Pass
		Diagonal	L2x2x1/4	22.5 59.9 (b)	Pass
T11	92 - 88	Leg	P4x.237 (4.50 OD)	79.3	Pass
		Diagonal	2L1 1/2x1 1/2x3/16x3/8	34.4 70.0 (b)	Pass
		Secondary Horizontal	3/8x4	22.1 30.9 (b)	Pass
T12	88 - 84	Leg	P4.5x0.237 + P5.5625x0.375	59.4	Pass
		Diagonal	2L1 1/2x1 1/2x3/16x3/8	32.8 67.0 (b)	Pass
		Secondary Horizontal	3/8x4	26.5 32.9 (b)	Pass
T13	84 - 80	Leg	P4.5x0.237 + P5.5625x0.375	65.6	Pass
		Diagonal	2L1 1/2x1 1/2x3/16x3/8	29.4 57.7 (b)	Pass
	11	Secondary Horizontal	3/8x4	28.6 30.6 (b)	Pass
T14	80 - 75	Leg	P6x.28 (6.625 OD)	64.2	Pass
		Diagonal	L2x2x1/4	27.4 62.1 (b)	Pass
T15	75 - 70	Leg	P6x.28 (6.625 OD)	70.4	Pass
		Diagonal	2L1 3/4x1 3/4x3/16x3/8	21.2 50.6 (b)	Pass
T16	70 - 65	Leg	P6x.28 (6.625 OD)	76.2	Pass
		Diagonal	2L1 3/4x1 3/4x3/16x3/8	19.4 45.7 (b)	Pass
T17	65 - 60	Leg	P6x.28 (6.625 OD)	81.5	Pass
		Diagonal	2L1 3/4x1 3/4x3/16x3/8	19.9 46.6 (b)	Pass
T18	60 - 55	Leg	P6x.28 (6.625 OD)	81.7	Pass
		Diagonal	2L1 1/2x1 1/2x3/16x3/8	48.2 63.7 (b)	Pass
		Secondary Horizontal	L2x2x1/8	30.3 90.6 (b)	Pass
T19	55 - 50	Leg	P6.625x0.28 + P7.625x0.301	70.3	Pass
		Diagonal	2L1 1/2x1 1/2x3/16x3/8	38.2 51.6 (b)	Pass
T20	50 - 45	Leg	P6.625x0.28 + P7.625x0.301	73.8	Pass
		Diagonal	2L1 1/2x1 1/2x3/16x3/8	42.3 56.7 (b)	Pass
T21	45 - 40	Leg	P6.625x0.28 + P7.625x0.301	72.3	Pass

Section No.	Elevation ft	Component Type	Size	% Capacity	Pass Fail
		Diagonal Secondary Horizontal	L2x2x1/4	31.7 63.5 (b)	Pass
		Secondary Horizontal	L3x3x5/16	8.8 70.4 (b)	Pass
T22	40 - 20	Leg	P6x.432 (6.625 OD)	82.5	Pass
		Diagonal	2L1 3/4x1 3/4x3/16x3/8	25.4 50.8 (b)	Pass
T23	20 - 13.3333	Leg	P6x.432 (6.625 OD)	86.3	Pass
		Diagonal	L2x2x3/16	64.1 95.1 (b)	Pass
T24	13.3333 - 6.66667	Leg	P6x.432 (6.625 OD)	89.9	Pass
		Diagonal	L2x2x3/16	63.7 89.2 (b)	Pass
T25	6.66667 - 0	Leg	P6.625x0432 + P7.625x0.301	76.6	Pass
	=	Diagonal	2L2x2x3/16x3/8	25.2 58.5 (b)	Pass

Table 4 - Maximum Base Reactions

Load Type	Direction	Current Analysis* (TIA/EIA-222-F)	Original Design (TIA/EIA-222-F)
Individual Foundation	Horizontal	15 k	22 k
	Uplift	283 k	253 k
	Compression	302 k	
Overturning Moment		1,906 k-ft	1,685 k-ft

<sup>\*</sup> Foundation determined to be adequate per independent analysis.

Table 5 - Maximum Antenna Rotations at Service Wind Speeds

Centerline Elevation (ft)	Antenna	Tilt (deg)*	Twist (deg)*
124	(3) Andrew VHLP2.5 Dishes	0.9546	0.0719

<sup>\*</sup>Allowable tilt and twist values to be determined by the carrier.

<sup>\*</sup>Capacities include a 1/3 allowable stress increase for wind per TIA/EIA-222-F Standards.

\*\* Diagonal sizes from 120' to 100' take from Vertical Solutions Rigorous Structural Analysis dated 6/4/12

# **GENERAL COMMENTS**

This engineering analysis is based upon the theoretical capacity of the structure. It is not a condition assessment of the tower and its foundation. It is the responsibility of SBA Network Services, Inc. to verify that the tower modeled and analyzed is the correct structure (with accurate antenna loading information) modeled. If there are substantial modifications to be made or the assumptions made in this analysis are not accurate, FDH Engineering, Inc. should be notified immediately to perform a revised analysis.

# LIMITATIONS

All opinions and conclusions are considered accurate to a reasonable degree of engineering certainty based upon the evidence available at the time of this report. All opinions and conclusions are subject to revision based upon receipt of new or additional/updated information. All services are provided exercising a level of care and diligence equivalent to the standard and care of our profession. No other warranty or guarantee, expressed or implied, is offered. Our services are confidential in nature and we will not release this report to any other party without the client's consent. The use of this engineering work is limited to the express purpose for which it was commissioned and it may not be reused, copied, or distributed for any other purpose without the written consent of FDH Engineering, Inc.

# **APPENDIX**

Leg State         C         A672-60         A672-60         A572-60         A772-60         A772-60         A772-60         A	C   C   Fex.432 (6.625 OD)   Fex.28 (6.625 OD)   A   Fex.28 (6.625 OD)   A   Fex.28 (6.625 OD)   A   Fex.23 (6.625 OD)   A	C	C	C	A572-50	Section		125	124	123	122	121	120	B1T 8tT	T17 8	T16	T15	114	T13 T12	111	110	T9 T8	11		T6 T5	T5 T4	15
A572-50   A772-50   A772	A572-50   A572	A572-50   A572	A572-50	A572-50	NA   NA   NA   NA   NA   NA   NA   NA	Legs		v		Pβ	x.432 (6.625 OD)		В		a.	6x.28 (6.62	(00)		¥	P4x.2	37 (4.50 O	a a			SR 2	SR 2	SR2
F L2x2x316 S 12134x134x316x316 L2x2x14 2L112x112x316x316 L2x2x14 2L112x112x316x316 E D F D F I I I I I I I I I I I I I I I I	F L L L L L L L L L L L L L L L L L L L	NA   NA   NA   NA   NA   NA   NA   NA	NA.  NA.  NA.  NA.  NA.  NA.  NA.  NA.	105.7 translational E 100 of the control of the con	105.7 tr   107.4 tr	Leg Grade	4	572-50			A500M-54		A572-50			A500M-5	4		A572-50	4	500M-54					-075A	A570-45
NA   NA   NA   NA   NA   NA   NA   NA	NA.	NA.  NA.  NA.  NA.  NA.  NA.  NA.  NA.	NA.  NA.  NA.  NA.  NA.  NA.  NA.  NA.	A36 A76 A77 A77 A77 A77 A78 A79 A70 A70 A70 A70 A70 A70 A70 A70	NA.  NA.  NA.  NA.  NA.  NA.  NA.  NA.	Diagonals		L	L2x2x	3/16	2L1 3/4x1 3/4x3/16x3/8	L2x2x1/4	2L1 1/2x1	1/2x3/16x3/6		3/4×1 3/4×2		L2x2x1/4	2L1 1/2x1 1/2	x3/16x3/8	ш	0		SR 3/4		4	4
N.A.         N.A.         N.A.         N.A.         I N.A.         LZXZY18         N.A.         II         N.A. <t< td=""><td>NA. NA. LZXZY18 NA. NA. LZXZY18 NA. NA. NA. NA. NA. NA. NA. NA. NA. NA.</td><td>NA.  NA.  NA.  NA.  NA.  NA.  NA.  NA.</td><td>NA.  NA.  NA.  NA.  NA.  NA.  NA.  NA.</td><td>NA.  NA.  NA.  NA.  NA.  NA.  NA.  NA.</td><td>NA. NA. 1088</td><td>Diagonal Grade</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>A36</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></t<>	NA. NA. LZXZY18 NA. NA. LZXZY18 NA.	NA.  NA.  NA.  NA.  NA.  NA.  NA.  NA.	NA.  NA.  NA.  NA.  NA.  NA.  NA.  NA.	NA.  NA.  NA.  NA.  NA.  NA.  NA.  NA.	NA. NA. 1088	Diagonal Grade										A36											
S N.A. L2x2x18 N.A. 1 N.A. L2x2x18 N.A. 1 N.	NA.	NA.	NA. 1000 tr.	112	NA. NA. L22218  NA. NA. L22218  NA. NA. L22218  NA.	Top Girts							N.A.									9		ď.			
S         NA.         L2x2x18         NA.         L2x2x18         NA.         RA.         L2x2x18         NA.         RA.         <	S     NA.     I NA.     L2A2X18     NA.     I NA.     NA.     NA.     NA.     NA.     NA.     NA.     H       7.5     7.16667     6.83333     6.5     6.66667     5.25     5.25     5     4.75     4.25     4.25     4     3.75     3.75     3.3     3.1     2.9     2.7       11.5     1.0     0.7     0.7     2.4     0.7 <td>NA. NA. NA. NA. NA. NA. NA. NA. NA. NA.</td> <td>H - WY - 100.0ft - 100.0ft</td> <td>NA. NA. 107. NA. NA. 107. NA.</td> <td>H - NA - 1000 t</td> <td>Horizontals</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>N.A.</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>-</td> <td></td> <td>2</td> <td>1 1/4</td> <td>1 1×</td> <td>L1 1/4x1 1/4x3/16</td>	NA.	H - WY - 100.0ft	NA. NA. 107. NA. NA. 107. NA.	H - NA - 1000 t	Horizontals							N.A.									-		2	1 1/4	1 1×	L1 1/4x1 1/4x3/16
7.5 7.16667 6.83333 6.6 6.86667 6.8 6.2 6.2 6.2 6.2 6.4 75 4.7 6.8 6.8 6.8 6.8 6.8 6.8 6.8 6.8 6.8 6.8	7.5 7.16667 6.83333 6.5 6.26667 8.0 6.0 6.0 6.0 6.0 6.0 6.0 6.0 6.0 6.0 6	8 8 0 ft   102.9 ft   103.6 ft   104.0 ft   105.7 ft   107.0 ft	11.4 10.00 ft 105.7 ft 100.0 ft 105.7 ft 100.0 ft 105.7 ft 100.0 ft 105.7 ft 100.0 f	111.4 100.0 th 105.7 th 102.9 th 100.0 th 105.7 th 102.9 th 100.0 th 105.7 th 102.9 th 100.0	111.4 100.6 105.7 ft. 102.9 ft. 100.0 ft. 102.9 ft. 100.0 ft. 102.9 ft. 100.0 ft. 102.9 ft. 100.0 ft	Sec. Horizontals				Ž	.A.	-	N.A.	L2x2>	41/8	_	Ą.		3/8×	_	Z.A.	_				_	N.A.
6@6.66667 5@4	11.5 1.0 0.7 0.6 0.6 0.6 0.5 0.7 0.6 0.6 0.7 0.6 0.7 0.6 0.7 0.7 0.7 0.7 0.7 0.7 0.7 0.7 0.7 0.7	101.4 108.6 105.76 102.96 102.	102.9ft 102.9ft 100.0ft 100.0f	108.6 105.7 R 102.9 R 100.0 R 20.0 R	100.0 ft 100	Face Width (ft)	7.5	7,16667	6.83333	6.5			9	4.75		.25											
	11.5 1.0 0.7 0.7 0.7 0.8 0.6 0.6 0.5 0.4 0.4 0.4 0.4 0.3 0.2 0.7 0.1 0.1 0.1 0.1 0.1	111.4 108.6 105.7 ft 102.9 ft 100.0 ft	5 111.4 108.6 109.6 109.6 109.6 109.6 109.6 109.0 ft 100.0 ft 100.	5 111.4 108.6 105.7 R 5 102.9 R 5 100.0 R 5 10	5 111.4 108.6 105.7 R 5 102.9 ft 5 100.0 ft 5 88.0 ft 7 7 0.0 ft 7 6 5 0.0 ft 7 6 5 0.0 ft 7 6 6 7 0.0 ft 7 6 6 7 0.0 ft 7 6 7 0.0 ft 7 6 6 7 0.0 ft 7 7	# Panels @ (ft)				6@6.	.66667				8@5					5@4		_		7 @ 2.857	714		

# **DESIGNED APPURTENANCE LOADING**

TYPE	ELEVATION	TYPE	ELEVATION
(4) Decibel DB844H90E-M w/ Mount Pipe	128	AM-X-CD-16-65-00T-RET w/ Mount Pipe	110
(4) Decibel DB844H90E-M w/ Mount	128	SBNH-1D6565C w/ Mount Pipe	110
Pipe		(2) LGP13519 TMA	110
(4) Decibel DB844H90E-M w/ Mount	128	(2) LGP13519 TMA	110
Pipe		(2) LGP13519 TMA	110
LLPX310R w/ Mount Pipe	128	(2) LGP21401 TMA	110
LLPX310R w/ Mount Pipe	128	(2) LGP21401 TMA	110
840 10054 w/ Mount Pipe	128	(2) LGP21401 TMA	110
24"x14"x9" TMA	128	(2) RRUS-11 1900MHz	110
24"x14"x9" TMA	128	(2) RRUS-11 1900MHz	110
24"x14"x9" TMA	128	(2) RRUS-11 1900MHz	110
TIMING 2000	128	DC6-48-60-18-8F Surge Arrestor	110
IDU Modem	128	(3) T-Frames	110
IDU Modem	128	(2) 7700.00 w/Mount Pipe	110
IDU Modem	128	(2) 7700.00 w/Mount Pipe	110
(3) T-Frames	128	(2) 7700.00 w/Mount Pipe	110
VHLP2.5 Dish	128	APXV18-206517S-C w/Mount Pipe	100
VHLP2.5 Dish	128	(3) Standoffs	100
VHLP2.5 Dish	128	APXV18-206517S-C w/Mount Pipe	100
APXVSPP18-C-A20 w/Mount Pipe	118.5	APXV18-206517S-C w/Mount Pipe	100
APXVSPP18-C-A20 w/Mount Pipe	118.5	(2) RR65-19-02DP w/Mount Pipe	93
P40-16-XLPP-RR-Aw/ Mount Pipe	118.5	(2) RR65-19-02DP w/Mount Pipe	93
1900 MHz RRH	118.5	RFS APX16DWV-16WV-S-E-ACU	93
1900 MHz RRH	118.5	RFS APX16DWV-16WV-S-E-ACU	93
1900 MHz RRH	118.5	RFS APX16DWV-16WV-S-E-ACU	93
800 MHz RRH	118.5	6.3"x7.7"x3" TMA	93
800 MHz RRH	118.5	6.3"x7.7"x3" TMA	93
800 MHz RRH	118.5	6.3"x7.7"x3" TMA	93
(2) ACU-A20-N RET	118.5		93
ACU-A20-N RET	118.5	(3) T-Frames	93
ACU-A20-N RET	118.5	(2) RR65-19-02DP w/Mount Pipe	55.5
800 MHz Filter	118.5	(1) Standoff	7.7.5
800 MHz Filter	118.5	GPS	55.5
800 MHz Filter	118.5	(1) Standoff	50.5
(3) T-Arms	118.5	GPS	50.5
AM-X-CD-16-65-00T-RET w/ Mount	110	GPS	50.5
Pipe	1.1.5	(1) Standoff	50.5

# SYMBOL LIST

MARK	SIZE	MARK	SIZE
Α	P4.5x0.237 + P5.5625x0.375 (CT)	F	2L2x2x3/16x3/8
В	P6.625x0.28 + P7.625x0.301 (CT)	G	L1 1/4x1 1/4x3/16
С	P6.625x0432 + P7.625x0.301 (CT)	н	L2x2x1/8
D	L1 1/2x1 1/2x3/16	1	L3x3x5/16
Ε	L2x2x1/4		

MATERIAL STRENGTH

	GRADE	Fy	Fu	GRADE	Fy	Fu	
MAX. CORNER RE	A570-45	45 ksi	60 ksi	A500M-54	54 ksi	70 ksi	
	A36	36 ksi	58 ksi	A572-50	50 ksi	65 ksi	
DOTTIV. OUZIN							

SHEAR: 15 K

# **TOWER DESIGN NOTES**

UPLIFT: -283 K1. Tower designed for a 80 mph basic wind in accordance with the TIA/EIA-222-F Standard.

SHEAR: 14 K 2. Tower is also designed for a 38 mph basic wind with 1.25 in ice. Ice is considered to increase in thickness with height.

AXIAL 3. Deflections are based upon a 50 mph wind.

71 K

- Tower is located in Hartford County, Connecticut.
   TOWER RATING: 95.1%

SHEAR MOMENT 761 kip-ft 9 K

TORQUE 2 kip-ft 38 mph WIND - 1.2500 in ICE AXIAL 26 K

SHEAR MOMENT 1906 kip-ft 23 K

TORQUE 6 kip-ft REACTIONS - 80 mph WIND

> FDH Engineering, Inc. 6521 Meridien Drive FDH Raleigh, NC 27616 Phone: 9197551012 FAX: 9197551031

Job: Glastonbury-N	Main St CT46126-A-	03
Project: 1338401400		
Client: SBA	Drawn by: David Zambrano	App'd:
Code: TIA/EIA-222-F	Date: 07/15/13	Scale: NTS
Path:	tean notice as decreased in the Commission of th	Dwg No. E-1

THE MODIFICATIONS DEPICTED ON THESE DRAWINGS ARE BASED ON THE RECOMMENDATIONS OUTLINED IN THE STRUCTURAL ANALYSIS COMPLETED BY FDH ENGINEERING, INC., PROJECT NO. 1320561400 DATED APRIL 15, 2013.

THIS REPORT WAS BASED ON A SPECIFIC ANTENNA AND COAX CONFIGURATION PROVIDED BY THE TOWER OWNER. ANY CHANGE TO THIS INFORMATION MUST BE REVIEWED BY FDH ENGINEERING, INC.

ALL DIMENSIONS, MEASUREMENTS, QUANTITIES, PART NUMBERS AND COAX/ANTENNA PLACEMENTS TO BE FIELD VERIFIED BY CONTRACTOR PRIOR TO MATERIAL ORDERS AND CONSTRUCTION.

FOR INQUIRIES REGARDING THE CONTENT OF THESE
MODIFICATION DRAWINGS, PLEASE CONTACT STEVEN STRICKLAND
WITH THE FDH CONSTRUCTION DEPARTMENT (919) 755-1012

PROJECT DESCRIPTION:

# MODIFICATION DRAWINGS FOR A 130' SELF-SUPPORT TOWER



SITE NAME:

# **GLASTONBURY-MAIN ST**

SITE NUMBER:

CT46126-A-03

SITE ADDRESS:

2577 MAIN STREET GLASTONBURY, CT 06033

COORDINATES:

LATITUDE: 41.7144° LONGITUDE: -72.6130°

_	
	SHEET INDEX
SHT. NO.	DESCRIPTION
T-1	TITLE SHEET
N-1	POST CONSTRUCTION INSPECTION NOTES
N-2	GENERAL NOTES
S-1	MODIFICATION SCHEDULE
S-2	DIAGONAL REPLACEMENT DETAILS

PREPARED BY:	
FDH	6521 MERIDIEN DRIVE RALEIGH, NC 27616 PHONE: 919-755-1012 FAX: 919-755-1031
ENGINEERING	INNOVATION

PREPARED FOR:	
I CDA ME	
SBADI	
5900 BROKEN SOUND PARKWAY, NW	
BOCA RATON, FL 33487 (800) 487-SITE	
(800) 487-SIIE	
(800) 487-SITE	
Wich Chil	_
OF COMME	
1 N. C. O	
S. S. W. 101	
1 5 3 Am	
	=
= * = = = * * * * * * * * * * * * * *	=
	-
No. 25842	
1 32	
S CENSE C	
S 660 - 516 11	
IN SOLONAL ENTITY	
WAS TOWAL ENGINEER	
MALERINIA 06/17/1	13
No. 25842  ACENSE  OF A TOTAL OF THE CONNECTICUT LIC NO. 25842	13

- 1		
	DRAWN BY:	,
	CHECKED BY:	D:
	ENG APPV'D:	СМІ
	PROJECT NO:	133840140

	SUBMITTALS	
DATE	DESCRIPTION	REV
06/17/13	CONSTRUCTION	٥

THE INFORMATION CONTAINED IN THIS SET OF DOCUMENTS IS PROPRIETARY BY NATURE. REPRODUCTION OR CAUSING TO BE REPRODUCED THE WHOLE OR ANY PART OF THESE DRAWINGS WITHOUT THE PERMISSION OF FDH ENGINEERING, INC. IS PROHIBITED.

SITE NAME:
GLASTONBURY-MAIN ST

SITE NUMBER: CT46126-A-03

SITE ADDRESS: 2577 MAIN STREET GLASTONBURY, CT 06033

SHEET TITLE

TITLE SHEET

SHEET NUMBER

T-1

<u> </u>	
CONSTRUCTION/INSTALLATION INSPECTIONS AND TESTING REQUIRED	REPORT ITEM
P	RE-CONSTRUCTION
X	PCI CHECKLIST DRAWING
N/A	EOR APPROVED SHOP DRAWINGS
N/A	FABRICATION INSPECTION
N/A	FABRICATOR CERTIFIED WELD INSPECTION
X	MATERIAL TEST REPORT (MTR)
N/A	FABRICATOR NDE INSPECTION
N/A	NDE REPORT OF MONOPOLE BASE PLATE (AS REQUIRED)
X	PACKING SLIPS
ADDITIONAL TESTING AND INSPEC	CTIONS:
C	ONSTRUCTION
X	CONSTRUCTION INSPECTIONS
N/A	FOUNDATION INSPECTIONS
N/A	CONCRETE COMP. STRENGTH AND SLUMP TESTS
N/A	POST INSTALLED ANCHOR ROD VERIFICATION
N/A	BASE PLATE GROUT VERIFICATION
N/A	CONTRACTOR'S CERTIFIED WELD INSPECTION
N/A	EARTHWORK: LIFT AND DENSITY
X	ON SITE COLD GALVANIZING VERIFICATION
N/A	GUY WIRE TENSION REPORT
X	GC AS-BUILT DOCUMENTS
ADDITIONAL TESTING AND INSPEC	CTIONS:
P	OST-CONSTRUCTION
Х	PCI INSPECTOR REDLINE OR RECORD DRAWING(S)
N/A	POST INSTALLED ANCHOR ROD PULL-OUT TESTING
Х	PHOTOGRAPHS
ADDITIONAL TESTING AND INSPE	CTIONS:
· <del>-</del>	· · · · · · · · · · · · · · · · · · ·

PCI CHECKLIST

NOTE: X DENOTES A DOCUMENT NEEDED FOR THE PCI REPORT N/A DENOTES A DOCUMENT THAT IS NOT REQUIRED FOR THE PCI REPORT

# POST CONSTRUCTION INSPECTION NOTES:

# **GENERAL**

- THE POST CONSTRUCTION INSPECTION (PCI) IS A VISUAL INSPECTION OF TOWER MODIFICATIONS AND A REVIEW OF CONSTRUCTION INSPECTIONS AND OTHER REPORTS TO ENSURE THE INSTALLATION WAS CONSTRUCTED IN ACCORDANCE WITH THE CONTRACT DOCUMENTS, NAMELY THE MODIFICATION DRAWINGS, AS DESIGNED BY THE ENGINEER OF RECORD (EOR).
- 2. THE PCI IS TO CONFIRM INSTALLATION CONFIGURATION AND WORKMANSHIP ONLY AND IS NOT A REVIEW OF THE MODIFICATION DESIGN ITSELF, NOR DOES THE PCI INSPECTOR TAKE OWNERSHIP OF THE MODIFICATION DESIGN. OWNERSHIP OF THE STRUCTURAL MODIFICATION DESIGN EFFECTIVENESS AND INTEGRITY RESIDES WITH THE EOR AT ALL
- 3. ALL PCI'S SHALL BE CONDUCTED BY A PCI INSPECTOR THAT IS APPROVED TO PERFORM ELEVATED WORK FOR FDH ENGINEERING, INC.
- 4. TO ENSURE THAT THE REQUIREMENTS OF THE PCI ARE MET, IT IS VITAL THAT THE GENERAL CONTRACTOR (GC) AND THE PCI INSPECTOR BEGIN COMMUNICATING AND COORDINATING AS SOON AS A PO IS RECEIVED. IT IS EXPECTED THAT EACH PARTY WILL BE PROACTIVE IN REACHING OUT TO THE OTHER PARTY. IF CONTACT INFORMATION IS NOT KNOWN, CONTACT YOUR FDH POINT OF CONTACT (POC).
- 5. REFER TO CCR-01: CONTRACTOR CLOSEOUT REQUIREMENTS FOR FURTHER DETAILS

# **PCI INSPECTOR**

- 1. THE PCI INSPECTOR IS REQUIRED TO CONTACT THE GC AS SOON AS RECEIVING A PO FOR THE PCI TO, AT A MINIMUM:
  - · REVIEW THE REQUIREMENTS OF THE PCI CHECKLIST
  - · WORK WITH THE GC TO DEVELOP A SCHEDULE TO CONDUCT ON-SITE INSPECTIONS, INCLUDING FOUNDATION INSPECTIONS
- 2. THE PCI INSPECTOR IS RESPONSIBLE FOR COLLECTING ALL GENERAL CONTRACTOR (GC) INSPECTION AND TEST REPORTS, REVIEWING THE DOCUMENTS FOR ADHERENCE TO THE CONTRACT DOCUMENTS, CONDUCTING THE IN-FIELD INSPECTIONS, AND SUBMITTING THE PCI REPORT TO FDH.

# CORRECTION OF FAILING PCI'S

- 1. IF THE MODIFICATION INSTALLATION WOULD FAIL THE PCI ("FAILED PCI"), THE GC SHALL WORK WITH FDH TO COORDINATE A REMEDIATION PLAN IN ONE OF TWO WAYS:
  - . CORRECT FAILING ISSUES TO COMPLY WITH THE SPECIFICATIONS CONTAINED IN THE ORIGINAL CONTRACT DOCUMENTS AND COORDINATE A SUPPLEMENT PCI. · OR, WITH FDH'S APPROVAL, THE GC MAY WORK WITH THE EOR TO RE-ANALYZE

# **REQUIRED PHOTOS**


BETWEEN THE GC AND THE PCI INSPECTOR THE FOLLOWING PHOTOGRAPHS, AT A MINIMUM, ARE TO BE TAKEN AND INCLUDED IN THE PCI REPORT:

THE MODIFICATION/REINFORCEMENT USING THE AS-BUILT CONDITION.

- PRE-CONSTRUCTION GENERAL SITE CONDITION
- PHOTOGRAPHS DURING THE REINFORCEMENT MODIFICATION CONSTRUCTION/ERECTION AND INSPECTION
- .. RAW MATERIALS PHOTOS OF ALL CRITICAL DETAILS
- FOUNDATION MODIFICATIONS
- WELD PREPARATION
   BOLT INSTALLATION AND TORQUE
- .. FINAL INSTALLED CONDITION
- .. SURFACE COATING REPAIR
- POST CONSTRUCTION PHOTOGRAPHS .. FINAL INFIELD CONDITION
- PHOTOS OF ELEVATED MODIFICATIONS TAKEN FROM THE GROUND SHALL BE CONSIDERED INADEQUATE.



5900 BROKEN SOUND PARKWAY, NW BOCA RATON, FL 33487 (800) 487-SITE



DRAWN BY: DZ CHECKED BY: ENG APPV'D: CMM 1338401400 PROJECT NO:

	SUBMITTALS	
DATE	DESCRIPTION	REV
06/17/13	CONSTRUCTION	0

THE INFORMATION CONTAINED IN THIS SET OF DOCUMENTS IS PROPRIETARY BY NATURE. REPRODUCTION OR CAUSING TO BE REPRODUCED THE WHOLE OR ANY PART OF THESE DRAWINGS WITHOUT THE PERMISSION OF FOH ENGINEERING, INC. IS PROHIBITED.

SITE NAME: **GLASTONBURY-MAIN ST** 

> SITE NUMBER: CT46126-A-03

SITE ADDRESS: 2577 MAIN STREET GLASTONBURY, CT 06033

> SHEET TITLE POST CONSTRUCTION INSPECTION NOTES

> > SHEET NUMBER

N-1

### **GENERAL NOTES:**

- ALL WORK SHALL BE DONE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL CODES AND ORDINANCES. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN ALL PERMITS NECESSARY TO COMPLETE THE PROJECT AND ABIDE BY ALL CONDITIONS AND REQUIREMENTS OF THE PERMITS.
- 2. THE CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFICATION OF ALL DIMENSIONS, ELEVATIONS AND EXISTING CONDITIONS AT THE SITE BEFORE ORDERING ANY MATERIALS OR DOING ANY WORK. NO EXTRA CHARGE OR COMPENSATION SHALL BE ALLOWED DUE TO DIFFERENCE BETWEEN ACTUAL DIMENSIONS AND DIMENSIONS INDICATED ON THE CONSTRUCTION DRAWINGS. ANY SUCH DISCREPANCY IN DIMENSION WHICH MAY BE FOUND SHALL BE SUBMITTED TO FDH ENGINEERING FOR CONSIDERATION BEFORE THE CONTRACTOR PROCEEDS WITH THE WORK IN THE AFFECTED AREAS.
- INCORRECTLY FABRICATED, DAMAGED, OTHERWISE MISFITTING, OR NON-CONFORMING MATERIALS AND CONDITIONS SHALL BE REPORTED TO FDH ENGINEERING PRIOR TO ANY REMEDIAL OR CORRECTIVE ACTION. ALL ACTIONS SHALL REQUIRE FDH ENGINEERING APPROVAL.
- 4. IT IS THE CONTRACTOR'S SOLE RESPONSIBILITY TO DETERMINE ERECTION PROCEDURE AND SEQUENCE TO ENSURE THE SAFETY OF THE STRUCTURE AND ITS COMPONENT PARTS DURING ERECTION AND/OR FIELD MODIFICATIONS. THIS INCLUDES, BUT IS NOT LIMITED TO, THE ADDITION OF TEMPORARY BRACING, GUYS OR TIE DOWNS THAT MAY BE NECESSARY. SUCH MATERIAL SHALL BE REMOVED AFTER THE COMPLETION OF THE PROJECT.
- 5. CONTRACTOR SHALL PROMPTLY REMOVE ANY & ALL DEBRIS FROM SITE AND RESTORE AS BEST AS POSSIBLE TO PRECONSTRUCTION CONDITION

# CONTRACTOR QUALIFICATION NOTES:

- ALL REPAIRS SHALL BE PERFORMED BY A TOWER CONTRACTOR WITH A MINIMUM 5 YEARS EXPERIENCE IN TOWER ERECTION AND RETROFIT AND WITH WORKING KNOWLEDGE OF THE TIA/EIA 222-F "STRUCTURAL STANDARD FOR STEEL ANTENNA TOWERS AND ANTENNA SUPPORTING STRUCTURES".
- 2. CONTRACTOR IS RESPONSIBLE FOR ALL CONSTRUCTION MEANS AND METHODS. SHOULD THE CONTRACTOR REQUIRE DIRECT CONSULTATION, FDH ENGINEERING, INC. IS WILLING TO OFFER SERVICES BASED UPON AN AGREED FEE FOR THE WORK REQUIRED.
- 3. ALL SUBMITTAL INFORMATION MUST BE SENT TO FDH ENGINEERING, INC. 6521 MERIDIEN DRIVE, RALEIGH NC, 27616, TEL. (919) 755—1012, FAX. (919) 755—1031, E—MAIL INFO@FDH—INC.COM. ANY VARIATION OF THESE SPECIFICATIONS OR DRAWINGS WITHOUT CONSENT FROM FDH ENGINEERING, INC. WILL VOID ANY RESPONSIBILITY OR LIABILITY FOR DAMAGE (MATERIAL OR PHYSICAL) TOWARDS FDH ENGINEERING, INC.
- 4. ALL CONSTRUCTION TO BE IN ACCORDANCE WITH THE TIA-1019-A STANDARD.

# JOB SITE SAFETY & NOTES:

1. NEITHER THE PROFESSIONAL ACTIVITIES OF FDH ENGINEERING, INC. NOR THE PRESENCE OF FDH ENGINEERING, INC. OR EMPLOYEES AND SUB—CONSULTANTS AT THE CONSTRUCTION SITE, SHALL RELIEVE THE GENERAL CONTRACTOR AND OR SUBCONTRACTORS AND ANY OTHER ENTITY OF THEIR OBLIGATIONS, DUTIES AND RESPONSIBILITIES INCLUDING, BUT NOT LIMITED TO, CONSTRUCTION MEANS, METHODS, SEQUENCE, TECHNIQUES OR PROCEDURES NECESSARY FOR PERFORMING, SUPERINTENDING OR COORDINATING ALL PORTIONS OF THE WORK OF CONSTRUCTION IN ACCORDANCE WITH THE CONTRACT DOCUMENTS AND ANY HEALTH OR SAFETY PRECAUTIONS REQUIRED BY ANY REGULATORY AGENCIES. THE GENERAL CONTRACTOR AND OR SUBCONTRACTOR IS SOLELY RESPONSIBLE FOR JOB SAFETY, AND WARRANTS THAT THIS INTENT IS EVIDENT BY ACCEPTING THIS WORK.

### STEEL:

- ALL STRUCTURAL STEEL SHALL BE FABRICATED AND ERECTED IN ACCORDANCE WITH THE LATEST AISC CODE AND ASTM SPECIFICATIONS.
  - \*ALL STEEL ANGLE SHALL BE ASTM A36 (Fy=36KSI) UNLESS OTHERWISE SPECIFIED.
- 2. ALL CONNECTIONS OF STRUCTURAL STEEL MEMBERS SHALL BE MADE USING SPECIFIED WELDS WITH WELDING ELECTRODES E-70XX OR SPECIFIED HIGH STRENGTH BOLTS TO BE ASTM A325X, THREAD INCLUDED WITH SHEAR PLANE (UNLESS OTHERWISE NOTED).
- 3. ALL BOLTED CONNECTIONS TO BE INSTALLED TO A SNUG-TIGHTENED CONDITION IN ACCORDANCE WITH AISC 13 PART 16.2, "SPECIFICATION FOR STRUCTURAL JOINTS USING ASTM A325 OR A490 BOLTS", SECTION 8.1, UNLESS OTHERWISE SPECIFIED. WHEN "X" TYPE BOLTS ARE USED, CONTRACTOR MAY BE REQUIRED TO STACK ADDITIONAL WASHERS TO OBTAIN PROPER SNUG TIGHT INSTALLATION. ALL NUTS SHALL BE HEAVY HEX UNLESS OTHERWISE NOTED.
- 4. ALL STEEL, AFTER FABRICATION, SHALL BE HOT DIPPED GALVANIZED PER ASTM A-123. ALL DAMAGED SURFACES, WELDED AREAS AND AUTHORIZED NON-GALVANIZED MEMBERS OR PARTS (EXISTING OR NEW) SHALL BE PAINTED WITH MULTIPLE COATS OF ZRC COLD GALVANIZING COMPOUND ACHEIVING A MINIMUM OF 4 MILS DRY FILM PER ASTM A 780.
- ALL SHOP AND FIELD WELDING SHALL BE DONE BY WELDERS
  QUALIFIED AS DESCRIBED IN THE "AMERICAN WELDING SOCIETY'S
  STANDARD QUALIFICATION PROCEDURE" TO PERFORM THE TYPE OF
  WORK REQUIRED. CONTRACTOR IS REQUIRED TO PROVIDE FDH
  ENGINEERING, INC. WITH A PASSING CERTIFIED WELDING INSPECTION
  FOR ALL WELDS.
- STRUCTURAL STEEL MAY NOT BE TORCH CUT FOR FABRICATION. ALL STEEL FABRICATION MUST FOLLOW AISC STANDARDS.

### MISC. NOTES:

- ALL MODIFICATIONS ARE ASSUMED TO BE MADE ON AN EMPTY TOWER. CONTRACTOR IS RESPONSIBLE TO MAKE PROVISIONS TO SUPPORT OR WORK AROUND EXISTING ANTENNAS AND TRANSMISSION LINES. MODIFICATIONS MUST BE CONTINUOUS THROUGH ALL AREAS SHOWN.
- CONTRACTOR FIELD VERIFY ALL DIMENSIONS PRIOR TO CONSTRUCTION.

# FABRICATION NOTES:

- ALL DIMENSIONS ARE PRELIMINARY UNTIL FIELD VERIFIED BY CONTRACTOR. ANY CHANGES MUST BE APPROVED BY ENGINEER OF RECORD IN WRITING PRIOR TO FABRICATION AND INSTALLATION.
- NEW STEEL MEMBERS MUST HAVE SINGLE DRILLED HOLES. SLOTTED AND DOUBLE DRILLED HOLES ARE NOT ACCEPTABLE MEANS OF FABRICATION.

## SUBSTITUTES AND/OR EQUALS:

IF CONTRACTOR WISHES TO FURNISH OR USE A SUBSTITUTE ITEM OF MATERIAL OR EQUIPMENT, CONTRACTOR SHALL FIRST MAKE WRITTEN APPLICATION TO ENGINEER OF RECORD FOR ACCEPTANCE THEREOF, CERTIFYING THAT THE PROPOSED SUBSTITUTE WILL PERFORM ADEQUATELY THE FUNCTIONS AND ACHIEVE THE RESULTS CALLED FOR BY THE GENERAL DESIGN, BE SIMILAR IN SUBSTANCE TO THAT SPECIFIED AND SUITED TO THE SAME USE AS THAT SPECIFIED. ALL VARIATIONS OF THE PROPOSED SUBSTITUTE FROM THAT SPECIFIED WILL BE IDENTIFIED IN THE APPLICATION AND AVAILABLE MAINTENANCE, REPAIR AND REPLACEMENT SERVICE WILL BE INDICATED. THE APPLICATION WILL ALSO CONTAIN AN ITEMIZED ESTIMATE OF ALL COSTS OR CREDITS THAT WILL RESULT DIRECTLY OR INDIRECTLY FROM ACCEPTANCE OF SUCH SUBSTITUTE INCLUDING COSTS OF REDESIGN AND CLAIMS OF OTHER CONTRACTORS AFFECTED BY THE RESULTING CHANGE, ALL OF WHICH WILL BE CONSIDERED BY ENGINEER OF RECORD IN EVALUATION OF THE PROPOSED SUBSTITUTE. ENGINEER OF RECORD MAY REQUIRE CONTRACTOR TO FURNISH ADDITIONAL DATA ABOUT THE PROPOSED


### COLD GALVANIZATION/SURFACE PREPARATION NOTES:

- CONTRACTOR TO USE ZINGA OR ZRC COLD GALVANIZATION COMPOUNDS OR APPROVED EQUIVALENT.
- PREPARE RUSTED/CORRODED SURFACE FOR TREATMENT ACCORDING TO MANUFACTURE'S RECOMMENDATIONS.
- 3. CONTRACTOR TO APPLY (2) COATS OF COLD GALYANIZATION COMPOUND PER MANUFACTURER'S RECOMMENDATION. DRYING AND CURING TIMES MUST BE UTILIZED PER MANUFACTURER'S RECOMMENDATION.
- APPLY ALL COATINGS BY BRUSH IN CALM WIND CONDITIONS. THE USE OF AEROSOL IS NOT PERMITTED.
- IF THE TOWER IS PAINTED, BRUSH PAINT ALL TREATED AREAS TO MATCH TOWER AFTER COLD GALVANIZATION COMPOUND IS ALLOWED TO CURE.



REPARED FOR:

SBA SOUND PARKWAY, NW BOCA RATION, FL 33487 (800) 487-SITE



Α	DRAWN BY:
DŽ	CHECKED BY:
CMA	ENG APPV'D:
1338401400	PROJECT NO:

	SUBMITTALS	
DATE	DESCRIPTION	REV
06/17/13	CONSTRUCTION	0
	· · · · · ·	-
		+
		+
		$\dashv$

THE INFORMATION CONTAINED IN THIS SET OF DOCUMENTS IS PROPRIETARY BY NATURE. REPRODUCTION OR CAUSING TO BE REPRODUCED THE WHOLE OR ANY PART OF THESE DRAWINGS WITHOUT THE PERMISSION OF FDH-ENGINEERING, INC. IS PROHIBITED.

SITE NAME:
GLASTONBURY-MAIN ST

SITE NUMBER: CT46126-A-03


SITE ADDRESS: 2577 MAIN STREET GLASTONBURY, CT 06033

SHEET TITLE

GENERAL NOTES

SHEET NUMBER


N-2



1	MEMBER SIZE KEY
MARK	SIZE
Α	L1 1/2X1 1/2X3/16
В	2L1 1/2X1 1/2X3/16X3/8
С	2L1 3/4X1 3/4X3/16X3/8
D	2L2X2X3/16X3/8
E	L1 1/4X1 1/4X3/16
F	L2X2X1/8
G	L3X3X5/16

- APPURTENANCES MAY INTERFERE WITH PROPOSED MODIFICATIONS.
- ALL MODIFICATIONS TO BE INSTALLED CONTINUOUSLY THROUGH EXISTING EQUIPMENT. ALL EXISTING EQUIPMENT NOT TO BE DAMAGED OR TAKEN OFF AIR DURING INSTALLATION.
- ANTENNA GRAPHICS NOT SHOWN FOR CLARITY. SEE STRUCTURAL ANALYSIS REPORT FOR EXISTING ANTENNA LOADING.

	TOWER MODIFICATION SCHEDULE		
NO.	TYPE OF MODIFICATION	BOTTOM ELEV. (FT)	TOP ELEV. (FT)
1	INSTALLATION OF NEW REPLACEMENT DIAGONALS. SEE S-2 FOR DETAILS.	92.0±	96.0±
2	INSTALLATION OF NEW REPLACEMENT DIAGONALS. SEE S-2 FOR DETAILS.	75.0±	80.0±
3	INSTALLATION OF NEW REPLACEMENT DIAGONALS. SEE S-2 FOR DETAILS.	40.0±	45.0±
4	REMOVAL OF EXISTING SUBHORIZONTALS.	10.1±	16.8±




COAX LAYOUT



PREPARED FOR



5900 BROKEN SOUND PARKWAY, NW BOCA RATON, FL 33487 (800) 487-SITE



DRAWN BY:	Α
CHECKED BY:	DZ
ENG APPV'D:	CMM
PROJECT NO:	1338401400

	SUBMITTALS	
DATE	DESCRIPTION	RE
06/17/13	CONSTRUCTION	0
	•	
		.

THE INFORMATION CONTAINED IN THIS SET OF DOCUMENTS IS PROPRIETARY BY NATURE. REPRODUCTION OR CAUSING TO BE REPRODUCED THE WHOLE OR ANY PART OF THESE DRAWINGS WITHOUT THE PERMISSION OF FDH ENGINEERING, INC. IS PROHIBITED.

SITE NAME:
GLASTONBURY-MAIN ST

SITE NUMBER: CT46126-A-03

SITE ADDRESS: 2577 MAIN STREET GLASTONBURY, CT 06033

SHEET TITLE


MODIFICATION SCHEDULE

SHEET NUMBER


S-1

		MK-1 REP	LACEMENT	DIAGONAL SO	CHED	ULE				
ELEVATION	EXISTING MEMBER	PROPOSED MEMBER	ESTIMATED LENGTH, A*	BOLT SIZE	HOLE SIZE	STITCH BOLT SIZE	HOLE SIZE	GAGE LINE**	EDGE DISTANCE***	BOLT GRADE
92.0'± TO 96.0'±	(6) L1 1/2X1 1/2X3/16	(6) L2X2X1/4	7'-4"±	(12) 1/2"ø X 1 1/2"	9/16 <b>°</b> ø	(3) 1/2*ø X 1 3/4*	9/16 <b>"</b> ø	1 1/8"	1"	A325X
75.0'± TO 80.0'±	(6) L1 1/2X1 1/2X3/16	(6) L2X2X1/4	6'-2"±	(12) 1/2"ø X 1 1/2"	9/16"ø	(3) 1/2"ø X 1 3/4"	9/16"ø	1 1/8"	1"	A325X
40.0'± TO 45.0'±	(6) L1 1/2X1 1/2X3/16	(6) L2X2X1/4	4'-11"±	(12) 1/2*ø X 1 1/2*	9/16 <b>"</b> ø	(3) 1/2"ø X 1 3/4"	9/16 <b>"</b> ø	1 1/8"	1"	A325X
	'		3 BAYS REQUIRE D	IAGONAL REPLACEMENT		•	· · · · ·		<u> </u>	

\*CONTRACTOR TO FIELD VERIFY LENGTH PRIOR TO MATERIAL ORDERS.
\*\*DISTANCE FROM HEEL OF ANGLE TO CENTER OF BOLT HOLE.
\*\*\*EDGE DISTANCE FROM CENTER OF BOLT HOLE TO EDGE OF CONNECTED PART.



EXISTING FEEDLINE LADDERS TO BE RE—INSTALLED USING EXISTING HARDWARE TO NEW DIAGONALS WHERE POSSIBLE & REPLACED IN ALL OTHER LOCATIONS AS NECESSARY, CONTRACTOR RESPONSIBLE FOR ALL PARTS ASSOCIATED WITH TEMPORARY & FINAL COAX & CLIMBING LADDER SUPPORT.



- ESTIMATED HOLE LOCATION. CONTRACTOR TO FIELD VERIFY LOCATION OF THIS HOLE PRIOR TO DRILLING HOLE TO ENSURE PROPER FIT. CONTRACTOR TO FIELD CUT EXCESS MATERIAL AFTER HOLE LOCATION IS VERIFIED.
- \*\* "B" WE SUGGEST THE PRELIMINARY CUT LENGTH IS 6" LONGER THAN OUR ESTIMATED LENGTH FOR MEMBERS 10' OR LESS, & 12" FOR MEMBERS GREATER THAN 10'.
- \*\*\* COPING MAY BE REQUIRED; COPING NOT TO EXCEED "TEAR-OUT" PLANE OF BOLT HOLE AS SHOWN,


DIAGONAL FRONT VIEW





PREPARED BY





DRAWN BY:	Al
CHECKED BY:	DZ
ENG APPV'D:	СММ
PROJECT NO:	1338401400

	SUBMITTALS	
DATE	DESCRIPTION	REV
06/17/13	CONSTRUCTION	0
Ì		

THE INFORMATION CONTAINED IN THIS SET OF DOCUMENTS IS PROPRIETARY BY NATURE. REPRODUCTION OR CAUSING TO PART OF THESE DRAWINGS WITHOUT THE PERMISSION OF FDH ENGINEERING, INC. IS PROHIBITED.

SITE NAME:

**GLASTONBURY-MAIN ST** 

SITE NUMBER: CT46126-A-03

SITE ADDRESS: 2577 MAIN STREET GLASTONBURY, CT 06033

SHEET TITLE DIAGONAL REPLACEMENT DETAILS

SHEET NUMBER

S-2



# RADIO FREQUENCY EMISSIONS ANALYSIS REPORT EVALUATION OF HUMAN EXPOSURE POTENTIAL TO NON-IONIZING EMISSIONS

**Sprint Existing Facility** 

Site ID: CT33XC822

Glastonbury Nextel 2577 Main Street Glastonbury, CT 06033

November 3, 2012

Fax: (781) 273.3311



November 3, 2012

Sprint Attn: RF Engineering Manager 1 International Boulevard, Suite 800 Mahwah, NJ 07495

Re: Emissions Values for Site: CT33XC822 - Glastonbury Nextel

EBI Consulting was directed to analyze the proposed upgrades to the existing Sprint facility located at 2577 Main Street, Glastonbury, CT, for the purpose of determining whether the emissions from the proposed Sprint equipment upgrades on this property are within specified federal limits.

All information used in this report was analyzed as a percentage of current Maximum Permissible Exposure (% MPE) as listed in the FCC OET Bulletin 65 Edition 97-01and ANSI/IEEE Std C95.1. The FCC regulates Maximum Permissible Exposure in units of microwatts per square centimeter ( $\mu$ W/cm2). The number of  $\mu$ W/cm2 calculated at each sample point is called the power density. The exposure limit for power density varies depending upon the frequencies being utilized. Wireless Carriers and Paging Services use different frequency bands each with different exposure limits, therefore it is necessary to report results and limits in terms of percent MPE rather than power density.

All results were compared to the FCC (Federal Communications Commission) radio frequency exposure rules, 47 CFR 1.1307(b)(1) - (b)(3), to determine compliance with the Maximum Permissible Exposure (MPE) limits for General Population/Uncontrolled environments as defined below.

General population/uncontrolled exposure limits apply to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Therefore, members of the general public would always be considered under this category when exposure is not employment related, for example, in the case of a telecommunications tower that exposes persons in a nearby residential area.

Public exposure to radio frequencies is regulated and enforced in units of microwatts per square centimeter ( $\mu$ W/cm²). The general population exposure limit for the cellular band is approximately 567  $\mu$ W/cm², and the general population exposure limit for the PCS band is 1000  $\mu$ W/cm². Because each carrier will be using different frequency bands, and each frequency band has different exposure limits, it is necessary to report percent of MPE rather than power density.



Occupational/controlled exposure limits apply to situations in which persons are exposed as a consequence of their employment and in which those persons who are exposed have been made fully aware of the potential for exposure and can exercise control over their exposure. Occupational/controlled exposure limits also apply where exposure is of a transient nature as a result of incidental passage through a location where exposure levels may be above general population/uncontrolled limits (see below), as long as the exposed person has been made fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Additional details can be found in FCC OET 65.

# **CALCULATIONS**

Calculations were done for the proposed upgrades to the existing Sprint Wireless antenna facility located at 2577 Main Street, Glastonbury, CT, using the equipment information listed below. All calculations were performed per the specifications under FCC OET 65. All calculations were performed assuming the main lobe of the antenna was focused at the base of the tower to present a worst case scenario. Actual values seen from this site will be dramatically less than those shown in this report. For this report the sample point is the top of a 6 foot person standing at the base of the tower.

For all calculations, all emissions were calculated using the following assumptions:

- 1) 4 CDMA Carriers (1900 MHz) were considered for each sector of the proposed installation.
- 2) 1 CDMA Carrier (850 MHz ) was considered for each sector of the proposed installation
- 3) All radios at the proposed installation were considered to be running at full power and were uncombined in their RF transmissions paths per carrier prescribed configuration. Per FCC OET Bulletin No. 65 Edition 97-01 recommendations to achieve the maximum anticipated value at each sample point, all power levels emitting from the proposed antenna installation are increased by a factor of 2.56 to account for possible in-phase reflections from the surrounding environment. This is rarely the case, and if so, is never continuous.
- 4) For the following calculations the sample point was the top of a six foot person standing at the base of the tower. The actual gain in this direction was used per the manufactures supplied specifications.
- 5) The antenna used in this modeling is the APXVSPP18-C-A20. This is based on feedback from the carrier with regards to anticipated antenna selection. This antenna has a 15.9 dBd gain value at its main lobe at 1900 MHz and 13.4 dBd at its main lobe for 850 MHz. All calculations were performed assuming the main lobe of the antenna was focused at the base of the tower to present a worst case scenario.



- 6) The antenna mounting height centerline of the proposed antennas is **118 feet** above ground level (AGL)
- 7) Emissions values for additional carriers were taken from the Connecticut Siting Council active database. Values in this database are provided by the individual carriers themselves.

All calculation were done with respect to uncontrolled / general public threshold limits

	Site Addresss	CT33XC 2577 Main S	CT33XC822 - Glastonbury Nextel 577 Main Street, Glastonbury, CT, 06033	ry Nextel													
	Site Type	S. Harter Manual Manual S.	Self Support Tower	er kertigs segments travaile													
							Sector 1	1									
Antenna	Antenna Nimbar Antenna Males	Antenna Model	Bardin Tuna	Francisco Band	Tachnolony	Power Out Per Channel	Number of Composite		Antenna Gain in direction of smaller Antenna analysis oot analysis (FR)	Antenna analysis		5	Cable Loss Additional	Additional	Ē	Power Density	Power Density
13	RFS	APXVSPP18-C-A20	RRH	1900 MHz	CDMA / LTE	20		80 80	15.9	118		1/2"	(ap)	0	2773.8948 79.49868	79.49868	
1a	RFS	APXVSPP18-C-A20	RRH	850 MHz	CDMA / LTE	20	1	07	13.4	118	112	1/5"	0.5	0	389.96892 11.17635	11.17635	1.97114%
												Sector total	Power Den	Sector total Power Density Value: 9.921%	9.921%		
							Sector 2	2									
Antenna		200000000000000			- 11, - 11,	Power Out Per Channel	Number of Composite	Composite	AND RESERVE AND ADDRESS.	Antenna	analysis		Cable Loss Additional	Additional		Power Density	Power Density
Number	Number Antenna Make	Antenn	Radio Type	Frequency Band	Technology	(Watts)	Channels	Power	(p)	Height (ft)	height	Cable Size	(qB)	Loss	ERP	Value	Percentage
e7	RFS	APXVSPP18-C-A20	HARH HARH	1900 MHz	CDMA / LTE	20	1	8 8	13.4	118	112	1/2"	0.5	0	2773.8948	79.49868	1.94987%
							-					Sector total Power Density Value:	Power Der	sity Value:	9.921%		2
							Sector 3	3									
Antenna						Power Out Per Channel	Mumber of	Composite	Antenna Gain in direction of sample	Antenna	analucic		alde Additional	Additional		Power	Power
Number	Ante	000000	Radio Type	Frequency Band	Technology	(Watts)		Power			height	Cable Size	(db)	Loss	ERP	Value	Percentage
3a	RFS	APXVSPP18-C-A20	RRH	1900 MHz	CDMA / LTE	20	3,6524,51Er 1	80	15.9	118	112	1/2	0.5	0	2773.8948	79.49868	7.94987%
3a	RFS	APXVSPP18-C-A20	RRH	850 MHz	CDMA / LTE	20	1	20	13.4	118	112	1/2 "	0.5	0	389.96892	11.17635	1.97114%
												Sector total Power Density Value:	Power Den	isity Value:	9.921%		

Site Co	Site Composite MPE %
Carrier	WPE %
Sprint	29.763%
T-Mobile	14.330%
Pocket	6.810%
Clearwire	1.160%
Nextel	3.480%
AT&T	5.260%
Total Cite MDF %	MEDB U9



# Summary

All calculations performed for this analysis yielded results that were well within the allowable limits for general public exposure to RF Emissions.

The anticipated Maximum Composite contributions from the Sprint facility are 29.763% (9.921% from each sector) of the allowable FCC established general public limit considering all three sectors simultaneously sampled at the ground level.

The anticipated composite MPE value for this site assuming all carriers present is **60.803%** of the allowable FCC established general public limit sampled at the ground level. This is based upon values listed in the Connecticut Siting Council database for existing carrier emissions

FCC guidelines state that if a site is found to be out of compliance (over allowable thresholds), that carriers over a 5% contribution to the composite value will require measures to bring the site into compliance. For this facility, the composite values calculated were well within the allowable 100% threshold standard per the federal government


Scott Heffernan

RF Engineering Director


**EBI Consulting** 

21 B Street


Burlington, MA 01803



332. Sprint, 332.6000. SBAJ322.6011. CT4XXC822. 2577 Main Street\332.6011\_CAD\332.6011\_Construction\332.6011\_A-1.dwg, 6/18/2013 11:34:50 AM, dchadwick



32\_Sprint\_332.6000\_SBA\332.6011\_CT43XCB22\_2577 Main Street\332.6011\_CAD\332.6011\_Construction\332.6011.A-2.dwg, 6/18/2013 11:34:59 AM, dchadwick




A1: (P) EMPTY PIPE

9

T

EXISTING LATTICE TOWER





PROPOSED 800/1900 MHz ANTENNA TO REPLACE

EXISTING CDMA ANTENNA (TYP OF 3, 1 PER SECTOR)

EXISTING LATTICE TOWER



	-911			
$\triangle$				
	06-17-13	REVISED PER CLIENT COMMENTS	DPC	NS
B	05-20-13	REVISED PER CLIENT COMMENTS	кмо	NS
$\triangle$	03-25-13	INITIAL SUBMISSION NOT FOR CONSTRUCTION	cos	NS
REV.	DATE	REVISION DESCRIPTION	DRAWN BY	CHKD. BY



# Stephen A. Bray PROFESSIONAL ENGINEER



CT LICENSE: 26657

332.6011

2577 MAIN STREET GLASTONBURY, CT 06033 HARTFORD COUNTY

CT43XC822

DJECT TYPE:	
1	<b>IETWORK VISION</b>

COS NS 03-18-13

> ANTENNA **PLANS**

HEET NUMBER

6/18/13

SCALE: NTS

EXISTING SPRINT ANTENNA TO BE REMOVED. EMPTY

PIPE MAST TO REMAIN (TYP

FINAL ANTENNA PLAN

OF 6, 2 PER SECTOR)

SCALE: NTS

**EXISTING ANTENNA PHOTO DETAIL**