

STATE OF CONNECTICUT

CONNECTICUT SITING COUNCIL Ten Franklin Square, New Britain, CT 06051

Ten Franklin Square, New Britain, CT 06051 Phone: (860) 827-2935 Fax: (860) 827-2950 E-Mail: siting.council@ct.gov Web Site: portal.ct.gov/csc

VIA ELECTRONIC MAIL

June 29, 2022

Kenneth C. Baldwin, Esq. Robinson & Cole LLP 280 Trumbull Street Hartford, CT 06103 kbaldwin@rc.com

RE: TS-VER-054-220526 – Cellco Partnership d/b/a Verizon Wireless request for an order to approve tower sharing at an existing telecommunications facility located at 63 Woodland Street, Glastonbury, Connecticut.

Dear Attorney Baldwin:

The Connecticut Siting Council (Council) is in receipt of your correspondence of June 27, 2022 submitted in response to the Council's June 24, 2022 notification of an incomplete request for tower sharing with regard to the above-referenced matter.

The submission renders the request for tower sharing complete and the Council will process the request in accordance with the Federal Communications Commission 60-day timeframe.

Thank you for your attention and cooperation.

Sincerely,

Melanie A. Bachman Executive Director

MAB/IN/laf

From: Mayo, Rachel <rmayo@RC.com> Sent: Monday, June 27, 2022 11:48 AM

To: Bachman, Melanie <Melanie.Bachman@ct.gov>; CSC-DL Siting Council <Siting.Council@ct.gov>

Cc: Baldwin, Kenneth < KBALDWIN@RC.com>; Mayo, Rachel < rmayo@RC.com>

Subject: TS-VER-054-220526- Response to incomplete letter

EXTERNAL EMAIL: This email originated from outside of the organization. Do not click any links or open any attachments unless you trust the sender and know the content is safe.

Good morning, please see the attached revised Mount Analysis as requested in the Council's June 24, 2022 letter (also attached)

Please let us know if you have any questions or need additional information.

Thank you

Rachel A. Mayo

Land Use Analyst

Robinson & Cole LLP
280 Trumbull Street
Hartford, CT 06103
Direct 860.275.8213 | Fax 860.275.8299
rmayo@rc.com | Bio | V-Card

Robinson+Cole


Embracing Change for Over 175 Years

Boston | Hartford | New York | Providence | Miami | Stamford Los Angeles | Wilmington | Philadelphia | Albany | www.rc.com



20 Alexander Drive Wallingford, CT 06492

Mount Analysis South Glastonbury 3 CT



Address:

63 WOODLAND STREET
SOUTH GLASTONBURY, CT 06073
LOCATION CODE: 708312

Date:

APRIL 20, 2022 (REV. 2)



Civil • Structural • Land Surveying



April 20, 2022



RE:

Applicant Site Name: South Glastonbury 3 CT

Applicant Location Code: 708312

Site Address: 63 Woodland Street, South Glastonbury, CT 06073

To whom it may concern:

Chappell Engineering Associates, LLC has performed a structural analysis of the proposed Verizon braced low-profile antenna mounting platform being proposed at the existing 150'+/- monopole located at the above-referenced address at approximately 115 ft AGL to analyze the effect of the proposed Verizon antenna installation on the subject platform.

The proposed antenna support structure will consist of one (1) low-profile antenna frame supporting twelve (12) individual antenna pipe mounts. Our analysis has considered the following total major equipment loads indicated on the antenna design summary (included in this report) to be installed on the proposed low-profile antenna frame:

<u>Appurtenance</u>	Size (HxWxD) (in)	<u>Weight</u>	Location	<u>Status</u>
(3) NHH-65B-R2B Panel Antennas	72.0x11.9x7.1	43.7lbs	Face of Mount	Proposed
(3) NHHSS-65B-R2B R2BT4 Panel Antennas	72.0x11.9x7.1	48.1lbs	Face of Mount	Proposed
(3) MT6407-77A Panel Antennas	35.2x16.1x5.6	87lbs	Face of Mount	Proposed
(3) 700/850 mHz RRH	15.0x15.0x9.0	70.3lbs	Face of Mount	Proposed
(3) 1900/2100 mHz RRH	15.0x15.0x10.0	84.4lbs	Face of Mount	Proposed
(3) RT4401-48A RRH	13.9x8.6x4.2	18.6lbs	Face of Mount	Proposed
(1) Fiber Junction Box	29.6x16.5x12.6	32.0lbs	Face of Mount	Proposed

The proposed antennas and ancillary hardware are shown on the enclosed Lease Exhibits and RF Data Sheets.

We have modeled the entire low-profile antenna frame under both wind and wind/ice loads. Our analysis and results are included in this report.

Based upon our analysis of the antenna mounts being proposed, we consider the proposed RMQP-496-HK low-profile mounting frame assembly has adequate capacity to support the proposed antenna configuration as shown on the construction drawings. The maximum percentage stress capacity as determined by our analysis are the antenna mounting pipes supporting the combined dual-mount antennas with a capacity of 51%. Our analysis assumes the mount will be installed and maintained according to the manufacturers' recommendations.

If you have any questions regarding this matter, please do not hesitate to call.

Sincerely,

CHAPPELL ENGINEERING ASSOCIATES) ILLEG

R.K. Executive Centre ■ 201 Boston Post Road West ■ Suite 101 ■ Marlborough, MA 01752

SUPPORTING DOCUMENTS

RADIO FREQUENCY (RF) DESIGN DATE: 12/27/21

ANTENNA MOUNT STRUCTURAL ANALYSIS DATE: 4/15/22

ANTENNA SUPPORT STRUCTURE (150'± MONOPOLE) STRUCTURAL ANALYSIS DATE: 4/12/22



20 ALEXANDER DRIVE, 2nd FLOOR, WALLINGFORD, CT 06492

SOUTH GLASTONBURY 3 CT

63 WOODLAND STREET SOUTH GLASTONBURY, CT 06073

PROJECT TYPE: WIRELESS TELECOMMUNICATIONS COLLOCATION ON EXISTING 150'± MONOPOLE

SITE INFORMATION:

PARENT PARCEL OWNER PAUL J. CAVANNA 80 WOODI AND STREET SOUTH GLASTONBURY, CT 06073

VERTICAL BRIDGE REIT, LLC TOWER OWNER 750 PARK OF COMMERCE DRIVE, SUITE 200

BOCA RATON, FL 33487

CT-5018 (HOPEWELL)

APPLICANT

POWER COMPANY

TELEPHONE COMPANY

CELLCO PARTNERSHIP (dba VERIZON WIRELESS) 20 ALEXANDER DRIVE WALLINGFORD, CT 06492

63 WOODLAND STREET SITE ADDRESS SOUTH GLASTONBURY, CT 06073

HARTFORD COUNTY, CT COUNTY: SITE CONTROL POINT CENTER OF EXISTING MONOPOLE

N 41°-39'-38 85" (41 660792") (NAD '83)

W 72°-34'-26.75" (72.574097°) (NAD '83)

JURISDICTION CONNECTICUT SITING COUNCIL MAP G11 STREET 7800 LOT W0002 TAX ID PARCEL NUMBER

ARCHITECT / ENGINEER: CHAPPELL ENGINEERING ASSOCIATES LLC

201 BOSTON POST ROAD WEST, SUITE 101 MARLBOROUGH, MA 01752

EVERSOURCE ENERGY 247 STATION DRIVE, SE 210

WESTWOOD, MA 02090 (781) 441-3610

VERIZON 185 FRANKLIN STREET BOSTON, MA 02107

(800) 941-9900


GENERAL NOTES

- 1. CONTRACTOR SHALL VERIFY ALL PLANS, EXISTING DIMENSIONS, AND CONDITIONS ON JOB SITE. CONTRACTOR SHALL IMMEDIATELY NOTIFY THE ARCHITECT/ENGINEER IN WRITING OF ANY DISCREPANCIES BEFORE PROCEEDING WITH THE WORK, FAILURE TO NOTIFY THE ARCHITECT/ENGINEER PLACES THE RESPONSIBILITY ON THE CONTRACTOR TO CORRECT THE DISCREPANCIES AT THE CONTRACTOR'S EXPENSE.
- 2. NEW CONSTRUCTION SHALL CONFORM TO ALL APPLICABLE CODES AND ORDINANCES.
 - BUILDING CODE: 2018 CONNECTICUT STATE BUILDING CODE
 - BUILDING CODE: 2017 NATIONAL ELECTRICAL CODE
 ELECTRICAL CODE: 2017 NATIONAL ELECTRICAL CODE
 STRUCTURAL CODE: TIA/EIA-222-G STRUCTURAL STANDARDS FOR ANTENNA
 SUPPORTING STRUCTURES AND ANTENNAS.

AT LEAST 72 HOURS PRIOR TO DIGGING, THE CONTRACTOR IS REQUIRED TO CALL DIG SAFE AT 811



VICINITY MAP



DRIVING DIRECTIONS

FROM WALLINGFORD, TAKE 1-91 NORTH. TAKE THE EXIT ONTO CT-3 NORTH TOWARD GLASTONBURY. TAKE THE EXIT ONTO CT-3 NORTH TOWARD GLASTONBURY. TAKE THE EXIT ONTO CT-2 EAST TOWARD PORTLAND. CONTINUE ONTO CT-17 SGLASTONBURY EXPRESSIVAT. TURN LETF ONTO CHESTING THILL ROAD. TURN INGERT ONTO THE ONTO CHESTING THILL ROAD. TURN INGERT ONTO THE ONTO CHESTING THILL ROAD. TURN INGERT ONTO THE ONTO CHESTING THE ROAD. LEFT ONTO HOPEWELL ROAD. TURN RIGHT ONTO WOODLAND STREET. THE SITE WILL BE ON THE RIGHT HAND SIDE.

SHEET INDEX

DWG.	DESCRIPTION	REV.
T01	TITLE SHEET	3
GN01	GENERAL NOTES	3
C01	PROPERTY PLAN	3
A01	EQUIPMENT COMPOUND PLAN	3
A02	EQUIPMENT AREA PLAN & DETAILS	3
A03	WEST AND NORTH EQUIPMENT COMPOUND ELEVATIONS	3
S01	ICE SHIELD FRAMING PLAN & STRUCTURAL DETAILS	3
RF01	ANTENNA MOUNTING PLAN AND DETAILS	3
RF02	ANTENNA DETAILS AND ANCILLARY EQUIPMENT SPECIFICATIONS	3
RF03	RF BILL OF MATERIALS AND RF CABLE PLUMBING DIAGRAM	3
RF04	RF COLOR CODE SPECIFICATIONS	3
E01	ELECTRICAL SPECIFICATIONS AND NOTES	3
E02	EQUIPMENT COMPOUND UTILITY PLAN & DETAILS	3
E03	ELECTRICAL DIAGRAMS & DETAILS	3
E04	SCHEMATIC GROUNDING PLAN & DETAILS	3
E05	GROUNDING DETAILS	3

DO NOT SCALE DRAWINGS

ALL PLANS, EXISTING DIMENSIONS AND CONDITIONS AT THE PROPOSED PROJECT SITE SHALL BE VERIFIED IN THE FIELD DURING THE CONSTRUCTION PHASE. THE PROJECT OWNERS REPRESENTATIVE SHALL BE NOTIFIED IN WRITING OF ANY DISCREPANCIES IMMEDIATELY HEPHESENTAL IVE SHALL BE NOTIFIED IN WHITING OF ANY DISCHEPANCIES IMMEDIAL ELY PRIOR TO PROCEEDING WITH THE PROPOSED WORK AFFECTED BY SUCH DISCREPANCIES, IN THE EVENT OF LACK OF SUCH NOTIFICATION, SUCH DISCREPANCIES SHALL BECOME THE RESPONSIBILITY OF THE PREVAILING CONTRACTOR RESPONSIBILITY.

PROJECT DESCRIPTION

- THIS IS AN UNMANNED AND RESTRICTED ACCESS EQUIPMENT INSTALLATION AND WILL BE USED FOR THE TRANSMISSION OF RADIO SIGNAL FOR THE PURPOSE OF PROVIDING PUBLIC WIRELESS TELECOMMUNICATIONS SERVICE.
- . THIS FACILITY WILL CONSUME NO UNRECOVERABLE ENERGY NO POTABLE WATER SUPPLY IS TO BE PROVIDED AT THIS LOCATION.
 NO WASTE WATER WILL BE GENERATED AT THIS LOCATION.
- NO SOLID WASTE WILL BE GENERATED AT THIS LOCATION





R.K. EXECUTIVE CENTRE 201 BOSTON POST ROAD WEST SUITE 101 MARLBOROUGH, MA 01752 (508) 481-7400 www.chappellengineering.com



FNGINFER/LAND SURVEYOR

DRAWING SCALE NOTE:

THESE DRIVINGS HIVE BEEN PREPARED IN ARCH D (24'38') FORMT.
AS SLOCI THE INITIES SOLES SHOWN ON ANY REPRODUCTIONS OF A
CONTRIDUCTION SIZE SHALL BE ROLLESS OF INVESTOR
ALL BAY SOLES WAY SE USES PROPALESS OF REPRODUCTION SIZE.
WHERE IN CONTLOT, BAY SOLES SHALL SUPPISEDE WRITTEN SOLES.

IT IS A VIOLATION OF LAW FOR ANY PERSON. NLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER. TO ALTER THIS DOCUMENT

	REVISIONS				
NO.	DESCRIPTION	DATE			
0	ISSUED FOR REVIEW	1/20/22			
1	ISSUED FOR CONSTRUCTION (FINAL)	2/10/22			
2	REVISED TSA REFERENCE DATE	4/13/22			
3	REVISED MSA REFERENCE DATE	4/15/22			
П					

PROJECT NAME:

SOUTH **GLASTONBURY 3 CT**

63 WOODLAND STREET SOUTH GLASTONBURY, CT 06073

DRAWING TITLE;

TITLE SHEET

DRAWING NO:

T01

SCALE:	DESIGNED BY: NWC	VZW PROJECT CODE:
AS SHOWN	DRAWN BY: NWC	20212309233
AS SHOWN	CHECKED BY: QRS	VZW PROJECT NO.:
CEA PROJECT NO.:	ORIGINAL ISSUE DATE:	16085720
96210.404	1/20/22	VZW LOCATION CODE:
	,,,	708312

GENERAL NOTES:

FOR THE PURPOSE OF CONSTRUCTION DRAWINGS, THE FOLLOWING DEFINITIONS SHALL APPLY: CONTRACTOR - VERZON WRELESS SUBCONTRECTOR - CORENT CONTRACTOR (CONSTRUCTION) OWNER - VERZON WRELESS OLE - ORGANIL EDIPIENTS MANUFACTURER

- 2. PRIOR TO THE SUBMISSION OF BIDS, THE BIDDING SUBCONTRACTOR SHALL VISIT THE CELL SITE TO FAMILHARZE WITH THE EXISTING CONDITIONS AND TO CONFIRM THAT THE WORK CAN BE ACCOMPLISHED AS SHOWN ON THE CONSTRUCTION DRAWNINGS. ANY DISCREPANCY FOUND SHALL BE BROUGHT TO THE ATTENTION OF CONTRACTOR.
- 3. ALL MATERIALS FURNISHED AND INSTALLED SHALL BE IN STRICT ACCORDANCE WITH ALL APPLICABLE CODES, REGULATIONS, AND ORDINANCES. SUBCONTRACTOR SHALL ISSUE ALL APPROPRIATE NOTICES AND COMPLY WITH ALL LAWS, ORDINANCES, RULES, REGULATIONS, AND LAWFUL ORDERS OF ANY PUBLIC AUTHORITY REACORDING THE PERFORMANCE OF THE WORK.
- 4. ALL WORK CARRIED OUT SHALL COMPLY WITH ALL APPLICABLE MUNICIPAL AND UTILITY COMPANY SPECIFICATIONS AND LOCAL JURISDICTIONAL CODES, ORDINANCES AND APPLICABLE REGULATIONS.
- 5. DRAWINGS PROVIDED HERE ARE NOT TO BE SCALED AND ARE INTENDED TO SHOW OUTLINE ONLY.
- UNLESS NOTED OTHERWISE, THE WORK SHALL INCLUDE FURNISHING MATERIALS, EQUIPMENT, APPURTENANCES, AND LABOR NECESSARY TO COMPLETE ALL INSTALLATIONS AS INDICATED ON THE DRAWINGS.
- THE SUBCONTRACTOR SHALL INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS UNLESS SPECIFICALLY STATED OTHERWISE.
- IF THE SPECIFIED EQUIPMENT CANNOT BE INSTALLED AS SHOWN ON THESE DRAWINGS, THE SUBCONTRACTOR SHALL PROPOSE AN ALTERNATIVE INSTALLATION FOR APPROVAL BY THE CONTRACTOR.
- 9. SUBCONTRACTOR SHALL DETERMINE ACTUAL ROUTING OF CONDUIT, POWER AND T1 CABLES, GROUNDING CABLES AS SHOWN ON THE POWER, GROUNDING AND TELCO PLAN DRAWING, SUBCONTRACTOR SHALL URLIZE EXISTING TRAYS MOTOR/OR SHALL ADD NEW TRAYS AS NECESSARY, SUBCONTRACTOR SHALL CONFIRM THE ACTUAL ROUTING WITH THE CONTRACTOR.
- 10. THE SUBCONTRACTOR SHALL PROTECT EXISTING IMPROVEMENTS, PAVEMENTS, CURBS, LANDSCAPING AND STRUCTURES, ANY DAMAGED PART SHALL BE REPAIRED AT SUBCONTRACTOR'S EXPENSE TO THE SATISFACTION OF THE OWNER.
- 11. SUBCONTRACTOR SHALL LEGALLY AND PROPERTY DISPOSE OF ALL SOREY MATERIALS SHALL AS COAMAL CARLES AND OTHER TIEMS REMOVED FROM THE DISTING FACULTY. ANTENNAS REMOVED SHALL BE RETURNED TO THE OWNER'S DESIGNATED LOCATION.
- 12. SUBCONTRACTOR SHALL LEAVE PREMISES IN CLEAN CONDITION.
- 13. THE SUBCONTRACTOR SHALL SUPERVISE AND DIRECT THE PROJECT DESCRIBED HEREIN. THE SUBCONTRACTOR SHALL BE SOLEY RESPONSIBLE FOR ALL CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES, AND PROCEDURES FOR COORDINATING ALL PORTIONS OF THE WORK LUBBER THE CONTRACTOR.
- 14. SUBCONTRACTOR SHALL NOTIFY CHAPPELL ENGINEERING ASSOCIATES, LLC. 48 HOURS IN ADVANCE OF POURING CONCRETE OR BACK FILLING TEROHES, SEALING ROOF AND WALL PENETRATIONS & POST DOWNS, FINISHING NEW WALLS OR FINIAL ELECTRICAL CONNECTIONS FOR ENGINEERING REVIEW.
- 15. CONSTRUCTION SHALL COMPLY WITH VERIZON WIRELESS NETWORK STANDARD #NSTD123 TO THE MAXIMUM EXTENT FEASIBLE UNLESS PRECLUDED OR LIMITED BY DESIGN SHOWN ON THESE DRAWINGS.
- 16. SUBCONTRACTOR SHALL VERIFY ALL EXISTING DIMENSIONS AND CONDITIONS PRIOR TO COMMENCING ANY WORK, ALL DIMENSIONS OF EXISTING CONSTRUCTION SHOWN ON THE DRAWINGS MUST BE VERHIFLD. SUBCONTRACTOR SHALL NOTIFY THE CONTRACTOR OF ANY DISCREPANCIES FROM TO ODERING MATERIAL OR PROCEEDING WITH CONSTRUCTION.
- 17. THE EXISTING CELL SITE IS IN FULL COMMERCIAL OPERATION, ANY CONSTRUCTION WORK BY SUBCONTRACTOR SHALL NOT DISRUPT THE EXISTING MORNAL OPERATION, ANY WORK ON EXISTING EQUIPMENT MUST BE COORDINATED WITH CONTRACTOR.
 ALSO, WORK SHOULD BE SCHEDULED FOR AN APPROPRIATE MAINTENANCE WINDOW USUALLY IN LOW TRAFFIC PERIODS AFTER MONORMENT.
- 18. SINCE THE CELL STE IS ACTIVE, ALL SMETTY PRECAUTIONS MUST BE TAKEN WHEN WORKING AROUND HIGH LIVELS OF ELECTROMAGNETIC MUSIANS COURSELY SUPPLY SHOULD DEFOSE THE CHARGE STREET SHOULD DEFOSE THE CHARGE STREET SHOULD DEFOSE THE CHARGE STREET SHOULD SHOULD SHOULD BE SHOULD SH

SITE WORK GENERAL NOTES:

- 1. THE SUBCONTRACTOR SHALL CONTACT UTILITY LOCATING SERVICES PRIOR TO THE START OF CONSTRUCTION.
- 2. ALL EXISTING ACTIVE SEMER, WHITE, CAS, ELECTRIC, AND OTHER UTLIFES WHERE ENCOUNTEED IN THE WROPK, SHALL BE PROTICTED AT LINES, AND WHERE FOURIED FOR THE PROPREP EXCENTION OF THE WORK, SHALL BE RELICATED AS DIRECTED BY ENGINEERS, EXTREME CAUTION SHOULD BE USED BY THE SUBCONTRACTOR WHEN EXCANATION OR DRELING PIERS ADMINIOUS PROPER PROTICES SHALL PROMISE SEMENT SHAME FOR THE WORKING CREW, THIS WILL INCLUDE BUT NOT BE LIMITED TO A) FALL PROTECTION B) CONFINED SPACE C) ELECTRICAL SAFETY D) TRENCHING & EXCAVATION.
- 3. ALL SITE WORK SHALL BE AS INDICATED ON THE DRAWINGS AND PROJECT SPECIFICATIONS.
- 4. IF NECESSARY, RUBBISH, STUMPS, DEBRIS, STICKS, STONES AND OTHER REFUSE SHALL BE REMOVED FROM THE SITE AND DISPOSED OF LECALLY.
- 5. THE SITE SHALL BE GRADED TO CAUSE SURFACE WATER TO FLOW AWAY FROM THE BTS EQUIPMENT AND TOWER AREAS.
- 6. NO FILL OR EMBANKMENT MATERIAL SHALL BE PLACED ON FROZEN GROUND. FROZEN MATERIALS, SNOW OR ICE SHALL NOT BE PLACED IN ANY FILL OR EMBANKMENT.
- THE SUB GRADE SHALL BE COMPACTED AND BROUGHT TO A SMOOTH UNIFORM GRADE PRIOR TO FINISHED SURFACE APPLICATION.
- 8. ALL EXISTING INACTIVE SEWER, WATER, GAS, ELECTRIC AND OTHER UTILITIES, WHICH INTERFERE WITH THE EXECUTION OF THE WORK, SHALL BE REMOVED AND/OR CAPPED, PLUGGED OR OTHERWISE DISCONTINUED AT POINTS WHICH WILL NOT INTERFERE WITH THE EXECUTION OF THE WORK, SUBJECT TO THE APPROVAL OF ENGINEERING, OWNER AND/OR LOCAL UTILITIES.
- 9. THE AREAS OF THE OWNERS PROPERTY DISTURBED BY THE WORK AND NOT COVERED BY THE TOWER, EQUIPMENT OR DRIVEWAY, SHALL BE GRADED TO A UNIFORM SLOPE AND STABILIZED TO PREVENT EROSION AS SPECIFIED IN THE PROJECT SPECIFICATION.
- 10. Subcontractor shall minimize disturbance to existing site during construction. Erosion control, measures, if required during construction, shall be in conformance with the local guidelines for erosion and sediment control.
- 11. THE SUBCONTRACTOR SHALL PROVIDE SITE SIGNAGE IN ACCORDANCE WITH THE VERIZON WIRELESS SPECIFICATION FOR SITE SIGNAGE.

CONCRETE AND REINFORCING STEEL NOTES:

1. ALL CONCRETE WORK SHALL BE IN ACCORDANCE WITH THE ACI 301, ACI 318, ACI 336, ASTM A184, ASTM A185 AND THE DESIGN AND CONSTRUCTION SPECIFICATION FOR CAST—IN-PLACE CONCRETE.

2. ALL CONCRETE SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH OF 3000 PSI AT 28 DAYS, UNLESS NOTED OTHERWISE. A HIGHER STRENGTH (4000PSI) MAY BE USED. ALL CONCRETE WORK SHALL BE IN ACCORDANCE WITH THE ACI 381 CODE

- 3. REINFORCING STEEL SHALL CONFORM TO ASTM A 615, GRADE 60, DEFORMED UNLESS NOTED OTHERWISE, WELDED WIRE FABRIC SHALL CONFORM TO ASTM A 185 WELDED STEEL WIRE FABRIC UNLESS NOTED OTHERWISE. SPLICES SHALL BE CLASS "8" AND ALL
- 4. THE FOLLOWING MINIMUM CONCRETE COVER SHALL BE PROVIDED FOR REINFORCING STEEL UNLESS SHOWN OTHERWISE ON

- 5. A CHAMFER 34" SHALL BE PROVIDED AT ALL EXPOSED EDGES OF CONCRETE, UNO, IN ACCORDANCE WITH ACI 301 SECTION 4.2.4.
- 6. INSTALLATION OF CONCRETE EXPANSION/WEDGE ANCHOR, SHALL BE PER MANUFACTURER'S WRITTEN RECOMMENDED PROCEDURE. THE MOIGH BOLT, DONEL OR ROO SHALL CONFIDEN TO MANUFACTURER'S RECOMMENDATION FOR EMBERGHOT DEPTH OR AS SHOWN ON THE DIMEMBACK, NO ESEMS SHALL BE CONTINUED AND EMBERGHOMPHON, BEND DRILLING MESTES IN CONCRETE SPECIAL INSECTIONS, RECORDS OF OXIGENING COURSE, SHALL BE STIMULES SITEEL OR HOT DIPPED GALVANIZED, EXPANSION BOLDS SHALL BE PROVIDED FOR MANUFACTION OF DAY.
- 7. CONCRETE CYLINDER TEST IS NOT REQUIRED FOR SLAB ON GRADE WHEN CONCRETE IS LESS THAN 50 CUBIC VARUS (BICLIOSIA.2.3) IN THAT CAUSIT THE FOLLOWING RECORDS SHALL BE PROVIDED BY THE CONCRETE SUPPLIER; (A) RESULTS OF CONCRETE CYLINDER TEST PERFORMED AT THE SUPPLIERS PLANT.
 (B) CERTIFICATION OF MINIMAL COMPRESSIVE STRENGTH FOR THE CONCRETE GAUGE SUPPLIED. FOR GRADETE THAN 50 CUBIGS VARIS THE CO-SHALL TENDRIN THE CONCRETE CHADIEST TEST.

8. AS AN ALTERNATIVE TO ITEM 7. TEST CYLINDERS SHALL BE TAKEN INITIALLY AND THEREAFTER FOR EVERY 50 YARDS OF CONCRETE FROM EACH DIFFERENT BATCH PLANT.

EQUIPMENT SHALL NOT BE PLACED ON NEW PADS FOR SEVEN DAYS AFTER PAD IS POURED, UNLESS IT IS VERIFIED BY CYLINDER TESTS THAT COMPRESSIVE STRENGTH HAS BEEN ATTAINED.

STRUCTURAL STEEL NOTES:

1. AL STEEL WORK SHALL BE PANTED OR CALVANCED IN ACCORDANCE WITH THE DRIWINGS AND VERSION WRISESS SPECIFICATION SEQUENCES OF CHAPMEN AND A STRUCTURAL STEEL SALL BE ASTMA-POURSES OF MERSION FORTED ON THE SITE SPECIFIC DRIWINGS. STEEL DESIGN, INSTALLATION AND BOLTING SHALL BE IN ACCORDANCE WITH THE AMERICAN INSTITUTE OF STEEL CONSTRUCTION (ASC) "MANUAL OF STEEL CONSTRUCTION."

- 2. ALL WELDING SHALL BE PERFORMED USING E70XX ELECTRODES AND WELDING SHALL CONFORM TO AISC AND AWS D1.1. FILLET WELD SIZES ARE NOT SHOWN, PROVIDE THE MINIMUM SIZE PER TABLE J2.4 IN THE AISC "MANUAL OF STEEL CONSTI 9TH EDITION, PAINTED SURFACES SHALL BE TOUCHED UP.
- 3. BOLTED CONNECTIONS SHALL USE BEARING TYPE ASTM A325 BOLTS (3(**)) AND SHALL HAVE MINIMUM OF TWO BOLTS UNLESS NOTED OTHERWISE.
- 4. NON-STRUCTURAL CONNECTIONS FOR STEEL GRATING MAY USE %" DIA. ASTM A 307 BOLTS UNLESS NOTED OTHERWISE.
- 5. INSTALLATION OF CONCRETE EXPANSION/WEDGE ANCHORS SHALL BE PER MANUFACTURER'S WRITTEN RECOMMENDED PROFEDURE THE ANCHOR BOLT, DOWEL OR ROD SHALL CONFORM TO THE MANUFACTURERS RECOMMENDATION FOR EMBEDMENT DEPTH OR AS SHOWN ON THE DRAWINGS, NO REBAR SHALL BE CUT WITHOUT PRIOR CONTRACTOR APPROVAL WHEN DRILLING HOLES IN CONCRETE. SPECIAL INSPECTIONS. REQUIRED BY GOVERNING CODES, SHALL BE PERFORMED IN ORDER TO MAINTAIN MANUFACTURER'S MAXIMUM ALLOWABLE LOADS. ALL EXPANSION/WEDGE ANCHORS SHALL BE STAINLESS STEEL OR HOT DIPPED GALVANIZED. EXPANSION BOLTS SHALL BE PROVIDED BY RAMSET/REDHEAD OR APPROVED EQUAL.
- 6. CONTRACTOR SHALL SUBMIT SHOP DRAWINGS FOR ENGINEER REVIEW & APPROVAL ON PROJECTS REQUIRING STRUCTURAL STEEL
- 7. ALL STRUCTURAL STEEL WORK SHALL BE DONE IN ACCORDANCE WITH AISC SPECIFICATIONS.

SOIL COMPACTION NOTES FOR SLAB ON GRADE:

- EXCAVATE AS REQUIRED TO REMOVE VEGETATION AND TOPSOIL TO EXPOSE NATURAL SUBGRADE AND PLACE CRUSHED STONE AS REQUIRED.
- COMPACTION CERTIFICATION: AN INSPECTION AND WRITTEN CERTIFICATION BY A QUALIFIED GEOTECHNICAL TECHNICIAN OR ENGINEER IS ACCEPTABLE.
- 3. AS AN ALTERNATE TO INSPECTION AND WRITTEN CERTIFICATION, THE "UNDISTURBED SOIL" BASE SHALL BE COMPACTED WITH "COMPACTION EQUIPMENT", LISTED BELOW, TO AT LEAST 90% MODIFIED PROCTOR MAXIMUM DENSITY PER ASTM D 1557 METHOD C.
- 4. COMPACTED SUBBASE SHALL BE UNIFORM AND LEVELED, PROVIDE 6" MINIMUM CRUSHED STONE OR GRAVEL COMPACTED IN 3" LIFTS ABOVE COMPACTED SOIL. GRAVEL SHALL BE NATURAL OR CRUSHED WITH 100% PASSING #1 SIEVE.
- 5. AS AM ALTERNATE TO TIEMS 2 AND 3, THE SUBGRACE SOLS WITH 5 PASSES AM AUTERNATE TO TIEMS 2 AND 3, THE SUBGRACE SOLS WITH 5 PASSES AM AUTERNATE TO TIEMS 2 AND 3, THE SUBGRACE SOLS WITH 5 PASSES AM AUTERNATE AND AUTERNATE AND AUTERNATE AND AUTERNATE AND AUTERNATE AND AUTERNATE AND COMPACTED AS STATED ABOVE.

COMPACTION EQUIPMENT:

1. HAND OPERATED DOUBLE DRUM, VIBRATORY ROLLER, VIBRATORY PLATE COMPACTOR OR JUMPING JACK COMPACTOR.

1. FIELD VERIFICATION-

SUBCONTRACTOR SHALL FIELD VERIFY SCOPE OF WORK, VERIZON WIRELESS ANTENNA PLATFORM LOCATION AND ANTENNAS TO BE REPLACED.

2. COORDINATION OF WORK: SUBCONTRACTOR SHALL COORDINATE RF WORK AND PROCEDURES WITH CONTRACTOR.

CABLE LADDER RACK; SUBCONTRACTOR SHALL FURNISH AND INSTALL CABLE LADDER RACK, CABLE TRAY, AND CONDUIT AS REQUIRED TO SUPPORT CABLES TO THE NEW BITS LOCATION.

ELECTRICAL INSTALLATION NOTES:

WIRING, RACEWAY, AND SUPPORT METHODS AND MATERIALS SHALL COMPLY WITH THE REQUIREMENTS OF THE NEC AND TELOPROIA.

SUBCONTRACTOR SHALL MODIFY EXISTING CABLE TRAY SYSTEM AS REQUIRED TO SUPPORT RF AND TRANSPORT CABLING TO THE NEW BTS EQUIPMENT, SUBCONTRACTOR SHALL SUBMIT MODIFICATIONS TO CONTRACTOR FOR APPROVAL.

3. ALL CIRCUITS SHALL BE SEGREGATED AND MAINTAIN MINIMUM CABLE SEPARATION AS REQUIRED BY THE NEC AND TELCORDIA.

4. CABLES SHALL NOT BE ROUTED THROUGH LADDER-STYLE CABLE TRAY RUNGS.

5. EACH END OF EVERY POWER, GROUNDING, AND TI CONDUCTOR AND CABLE SHALL BE LABELED WITH COLOR-CODED INSULATION OR ELECTRICAL TAPE WITH V PROTECTION, OR EQUAL). THE IDENTIFICATION METHOD SHALL CONFORM WITH NEC & GSHA, AND MATCH DISTRICATION INSTALLATION REQUIREMENTS.

6. POWER PHASE CONDUCTORS (I.E., HOTS) SHALL BE LABELED WITH COLOR-CODED INSULATION OR ELECTRICAL TAPE (3M BRAND, ½ INCH PLASTIC ELÈCTRICAL TAPE WITH UV PROTECTION, OR EQUAL). PHASE CONDUCTOR COLOR CODES SHALL CONFORM WITH THE NEC & OSHA AND MATCH EXISTING INSTALLATION REQUIREMENTS

7. ALL ELECTRICAL COMPONENTS SHALL BE CLEARLY LABELED WITH ENGRAVED LAMACOID PLASTIC LABELS. ALL EQUIPMENT SHALL BE LABELED WITH THEIR VOLTAGE RATING, PHASE CONFIGURATION, WIRE CONFIGURATION, POWER OR AMPACITY PARTING, AND BRANCH CRICKIT ID NUMBERS (I.E., PANEL BOARD AND CINCUIT ID'S).

8. PANEL BOARDS (ID NUMBERS) AND INTERNAL CIRCUIT BREAKERS (CIRCUIT ID NUMBERS) SHALL BE CLEARLY LABELED WITH ENGRAVED LAMACOID PLASTIC LABELS.

9. ALL TIE WRAPS SHALL BE CUT FLUSH WITH APPROVED CUTTING TOOL TO REMOVE SHARP EDGES.

10. POWER, CONTROL, AND EQUIPMENT GROUND WIRING IN TUBING OR CONDUIT SHALL BE SINGLE CONDUCTOR (#34 AWG OR LARGER), 600 V. OIL RESISTANT THHIN OR THWN-2. CLASS B STRANDED COPPER CABLE RATED FOR 90 °C (WET AND DRY) OPERATION; LISTED OR LABELED FOR THE LOCATION AND RACEWAY SYSTEM USED, UNLESS OTHERWISE SPECIFIED.

11. SUPPLIBERIUM, EQUIPMENT GROUND WEINE LOCATED INCORES SHALL EC SHALL ECOLOUCTOR (#6 AND OR LAGGED), BOD V, OLL RESSIONT THEN DE THINNEY GREEN INSLINDING, LOSAS OS TREMONDO COPERT DOUBLE RATID TOR ON YOU. (WET AND DRY) OPERATION; LISTED OR LABELED FOR THE LOCATION AND RACEMAY SYSTEM USED, UNLESS OTHERWISE SPECIFIED.

12. SUPPLEMENTAL EQUIPMENT GROUND WIRING LOCATED OUTDOORS, OR BELOW GRADE, SHALL BE SINGLE CONDUCTOR #3 AWG SOLID TINNED COPPER CABLE, UNLESS OTHERWISE SPECIFIED.

13. POWER AND CONTROL WIRING, NOT IN TUBING OR CONDUIT, SHALL BE MULTI-CONDUCTOR, TYPE TO CABLE (§34-AMG OR LAGGER), 600 V, OIL RESISTANT THAN OR THAN-2, CLASS B STRANGED COPPER CABLE RATED FOR 90 °C (WET AND DRY) OPERATION; WITH OUTER JACKET; LISTED OR LABELED FOR THE LOCATION USED, UNILESS OTHERWISE SPECIFIED.

14. ALL POWER AND GROUNDING CONNECTIONS SHALL BE CRIMP STYLE, COMPRESSION WIRE LUGS AND WIRE NUTS BY THOMAS AND BETTS (OR EQUAL). LUGS AND WIRE NUTS SHALL BE RATED FOR OPERATION AT NO LESS THAN 75°C (90°C

- 15. RACEWAY AND CABLE TRAY SHALL BE LISTED OR LABELED FOR ELECTRICAL USE IN ACCORDANCE WITH NEMA, UL, ANSI/IEEE, AND NEC.
- 16. NEW RACEWAY OR CABLE TRAY WILL MATCH THE EXISTING INSTALLATION WHERE POSSIBLE.
- 17. ELECTRICAL METALLIC TUBING (EMT) OR RIGID NONMETALLIC CONDUIT (LE., RIGID PVC SCHEDULE 40, OR RIGID PVC SCHEDULE BO FOR LOCATIONS SUBJECT TO PHYSICAL DAMAGE) SHALL BE LISED FOR EXPOSED INDOOR LOCATIONS
- 18. ELECTRICAL METALLIC TUBING (EMT), ELECTRICAL NONMETALLIC TUBING (ENT), OR RIGID NONMETALLIC CONDUIT (RIGID PVC, SCHEDULE 40) SHALL BE USED FOR CONCEALED INDOOR LOCATIONS.
- 19. GALVANIZED STEEL INTERMEDIATE METALLIC CONDUIT (IMC) SHALL BE USED FOR OUTDOOR LOCATIONS ABOVE GRADE
- 20. RIGID NONMETALLIC CONDUIT (I.E., RIGID PVC SCHEDULE 40 OR RIGID PVC SCHEDULE 80) SHALL BE USED UNDERGROUND; DIRECT BURIED, IN AREAS OF HOAVEN USED IN REINFORCED CONCRETE IN AREAS OF HEAVY VEHICLE TRAFFIC.
- 21. LIQUID-TIGHT FLEXIBLE METALLIC CONDUIT (LIQUID-TITE FLEX) SHALL BE USED INDOORS AND OUTDOORS, WHERE VIBRATION OCCURS OR FLEXIBILITY IS NEEDED.
- 22. CONDUIT AND TUBING FITTINGS SHALL BE THREADED OR COMPRESSION—TYPE AND APPROVED FOR THE LOCATION USED. SET SCREW FITTINGS ARE NOT ACCEPTABLE.
- 23. CABINETS, BOXES, AND WIREWAYS SHALL BE LISTED OR LABELED FOR ELECTRICAL USE IN ACCORDANCE WITH NEMA, UL, ANSI/IEEE, AND NEC.
- 24. CABINETS, BOXES, AND WIREWAYS TO MATCH THE EXISTING INSTALLATION WHERE POSSIBLE
- 25. WIREWAYS SHALL BE EPOXY-COATED (GRAY) AND INCLUDE A HINGED COVER, DESIGNED TO SWING OPEN DOWNWARD: SHALL BE PANDUIT TYPE E (OR EQUAL); AND RATED NEMA 1 (OR BETTER) INDOORS, OR NEMA 3R (OR BETTER) OUTDOORS.
- 26. EQUIPMENT CABINETS, TERMINAL BOXES, JUNCTION BOXES, AND PULL BOXES SHALL BE GALVANIZED OR EPDAY—COATED SHEET STEEL, SHALL MEET OR EXCEED UL 50, AND RATED NEMA 1 (OR BETTER) INDOORS, OR NEMA 36 (OR BETTER) ULTITOORS
- 27, METAL RECEPTACLE, SWITCH, AND DEVICE BOXES SHALL BE GALVANIZED, EPOXY-COATED, OR NON- CORRODING: SHALL MEET OR EXCEED UL 514A AND NEMA OS 1; AND RATED NEMA 1 (OR BETTER) INDOORS, OR WEATHER PROTECTED (WP OR BETTER) OUTDOORS.
- 28. NONMETALLIC RECEPTACLE, SWITCH, AND DEVICE BOXES SHALL MEET OR EXCEED NEMA OS 2; AND RATED NEMA 1 (OR BETTER) INDOORS, OR WEATHER PROTECTED (WP OR BETTER) OUTDOORS.
- 29. THE SUBCONTRACTOR SHALL NOTIFY AND OBTAIN NECESSARY AUTHORIZATION FROM THE CONTRACTOR BEFORE COMMENCING WORK ON THE AC POWER DISTRIBUTION PANELS.
- 31. ALL ELECTRICAL WORK SHALL BE PERFORMED IN ACCORDANCE WITH THE PROJECT SPECIFICATIONS, NEC AND ALL APPLICABLE LOCAL CODES.
- 32. CONDUIT ROUTINGS ARE SCHEMATIC. SUBCONTRACTOR SHALL INSTALL CONDUITS SO THAT ACCESS TO EQUIPMENT IS NOT BLOCKED.



ARCHITECT/ENGINEER:



R.K. EXECUTIVE CENTRE 201 BOSTON POST ROAD WEST SUITE 101 MARLBOROUGH, MA 01752 (508) 481-7400 www.chappellengineering.com





ENGINEER/LAND SURVEYOR DATE

DRAWING SCALE NOTE: These drivings hive been prepared in Arch D (24"\38") format, as such, the written solles skinin on any reproductions of a comprocitory 372. Sall, be reducted mauld.

All bay souls buy be less departededs of perfoluction 322.

Where in conflict, bay solles sault supersede written solles.

IT IS A VIOLATION OF LAW FOR ANY PERSON

	TO ALTER THIS DOCUMENT.					
Ε	REVISIONS					
NO.	DESCRIPTION	DATE				
0	ISSUED FOR REVIEW	1/20/22				
1	ISSUED FOR CONSTRUCTION (FINAL)	2/10/22				
2	REVISED TSA REFERENCE DATE	4/13/22				
3	REVISED MSA REFERENCE DATE	4/15/22				

PROJECT NAME:

SOUTH GLASTONBURY 3 CT


63 WOODLAND STREET SOUTH GLASTONBURY, CT 06073


GENERAL NOTES

DRAWING NO

GN01

SCALE:	DESIGNED BY: NWC	VZW PROJECT CODE:
N/A	DRAWN BY: NWC	20212309233
,	CHECKED BY: GRS	VZW PROJECT NO.:
CEA PROJECT NO.:	ORIGINAL ISSUE DATE:	16065720
96210.404	1/20/22	VZW LOCATION CODE







ARCHITECT/ENGINEER:



R.K. EXECUTIVE CENTRE 201 BOSTON POST ROAD WEST SUITE 101 MARLBOROUGH, MA 01752 (508) 481-7400 www.chappellengineering.com

SEAL:



ENGINEER/LAND SURVEYOR DATE

DRAWING SCALE NOTE: THESE DRIVINGS HIME BEDI REPORTED IN ARCH D (24"-34") FORMUL.
AS SLOV, THE WRITTEN SOLES SHOWN ON ANY REPRODUCTIONS OF A
COMPRISONORY SIZE SHALL BE RECORDED MANUL.
ALL BRY SOLES MAY BE LEED REPRODUCTION SIZE.
WHERE IN CONFLICT, BRY SOZIES SHALL SUPPRISEDE WRITTEN SOZIES.

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

	REVISIONS				
NO.	DESCRIPTION	DATE			
0	ISSUED FOR REVIEW	1/20/22			
1	ISSUED FOR CONSTRUCTION (FINAL)	2/10/22			
2	REVISED TSA REFERENCE DATE	4/13/22			
3	REVISED MSA REFERENCE DATE	4/15/22			
г					

PROJECT NAME:

SOUTH **GLASTONBURY 3 CT**

63 WOODLAND STREET SOUTH GLASTONBURY, CT 06073


DRAWING TITLE:


EQUIPMENT COMPOUND PLAN


DRAWING NO:


A01


ш			
ı	SCALE:	DESIGNED BY: NWC	VZW PROJECT CODE:
ı	K" = 1'-0"	DRAWN BY: NWC	20212309233
ı	A - 1-0	CHECKED BY: GRS	VZW PROJECT NO.:
ı	CEA PROJECT NO.:	ORIGINAL ISSUE DATE:	16065720
ı	96210,404	1/20/22	VZW LOCATION CODE
ı	302 10.101	1,20,22	708312














TYPICAL PROP. PANEL ANTENNA SPECIFICATIONS (1 RF02)







LTE/NR (700/850 MHz) REMOTE RADIO HEAD UNIT 15.0"H x 15.0"W x 9.0"D 70.3 LBS 1 PER SECTOR, TOTAL OF 3 LTE/NR (1900/2100 MHz) REMOTE RADIO HEAD UNIT 15.0°H x 15.0°W x 10.0°D 74.7 LBS 1 PER SECTOR, TOTAL OF 3

(BAND 48 (3.5 GHz)) NR AU RRH DIMENSIONS: WEIGHT: QUANTITY: 13.9"H x 8.6"W x 4.2"D 18.6 LBS EACH 1 PER SECTOR, TOTAL OF 3

TYPICAL REMOTE RADIO HEAD (RRH) UNIT DIMENSIONS 2 RODZ



Oty	Connector Size	Insert P/N	Insert Hole	Cable Type	Purpose	Pos
2	M75	190-0760	42mm	6x12 RL	2 glands fit 1 each 6/12 hyb	8
2	M75	190-0747	2x 24.5mm	2x12 DC	2 glands fit 2 each #6 12 cord DC	- 8
1	MITS	190-0905	2x 10.5mm	2x12 Fiber	1 gland fit 2 x 12 fiber trunk	0
1	MITS	190-0912	2x 9.5mm	2 ETH	1 gland lits 2 ethernet caple	0.

FIBER JUNCTION BOX 29.58"H x 16.5"W x 12.6"D 32.0 LBS TOTAL OF 1

TYPICAL FIBER JUNCTION BOX DIMENSIONS, SCHEMATIC AND MOUNTING PROCEDURE SCALE N.T.S.





CHAPPELL ENGINEERING ASSOCIATES, LLC

R.K. EXECUTIVE CENTRE 201 BOSTON POST ROAD WEST SUITE 101 MARLBOROUGH, MA 01752 (508) 481-7400 (508) 481-7400 www.chappellengineering.com

SEAL:



ENGINEER/LAND SURVEYOR DATE

DRAWING SCALE NOTE; THESE DEWINDS HIVE BEEN PREPARED IN ARCH D (24'536') FORMAT, AS SUCH, THE WRITTEN SCALES SHOWN ON ANY REPRODUCTIONS OF A CONTINUOUS STATES SHALL BE REMETED INAULD. SALES MAY BE USED REDAVELES OF REPORTED STATES HERE IN CONTINUOUS SHALL SHERRIED WRITTEN SOLES.

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

	REVISIONS	
NO.	DESCRIPTION	DATE
0	ISSUED FOR REVIEW	1/20/22
1	ISSUED FOR CONSTRUCTION (FINAL)	2/10/22
2	REVISED TSA REFERENCE DATE	4/13/22
3	REVISED MSA REFERENCE DATE	4/15/22

PROJECT NAME:

SOUTH **GLASTONBURY 3 CT**

63 WOODLAND STREET SOUTH GLASTONBURY, CT 06073


DRAWING TITLE;

ANTENNA DETAILS AND ANCILLARY EQUIPMENT **SPECIFICATIONS**

DRAWING NO:

RF02


- 1			
- 1	SCALE:	DESIGNED BY: NWC	VZW PROJECT CODE:
- 1	AS SHOWN	DRAWN BY: NWC	20212309233
- 1		CHECKED BY: GRS	VZW PROJECT NO.:
- 1	CEA PROJECT NO.:	ORIGINAL ISSUE DATE:	16085720
	96210.404	1/20/22	VZW LOCATION CODE: 708312



THIS RF BILL OF MATERIALS (BOM) HAS BEEN COMPILED FROM ANTENNA RECOMMENDATION DATA SHEET DATED 12/27/2021. CONTRACTOR SHALL CONFIRM ALL FINAL RF MATERIALS/EQUIPMENT TO BE USED WITH VERIZON WIRELESS RF ENGINEER DURING CONSTRUCTION.

RF BILL OF MATERIALS (FINAL CONFIGURATION)

NOTE:
ARRANGEMENT OF ANTENMS, REMOTE RADIO HEAD (RRH) UNITS, FIBER
ARRANGEMENT OF ANTENMS, REMOTE RADIO HEAD (RRH) UNITS, FIBER
EQUIPMENT SHOWN SCHEMITCALLY ON THIS PLUMENING DAGRAM. SEE
PROP. ANTENMA ORBERITATION PLAYS), AND CROSS REFERENCE WITH FEB
BILL OF MATERIALS FOR PROP. ANTENMA/EQUIPMENT PLACEMENT DETAIL.



RF CABLE PLUMBING DIAGRAM (FINAL CONFIGURATION) (2

RADIO FREQUENCY (RF) DESIGN NOTES:) ALL RADIO FREQUENCY (RF) DESIGN INFORMATION CONTAINED ON THIS SHEET IS SHOWN SCHEMATICALLY 2) THE GENERAL CONTRACTOR SHALL CONFIRM ALL RF DESIGN ELEMENTS SHOWN (INCLUDING BUT NOT LIMITED TO PAREL ANTENNA MOBILS & ARRANGEMENT AZUMATHS, REMOTE RADIO HEAD (RRH) UNIT MODELS & ARRANGEMENT AND CARLING UNGRAMS/SCHEMATICS WITH THE VERIZON WIRELESS RF ENGINEER AT THE TIME OF CONSTRUCTION.

LEGEND RED = HYBRID CABLE (MAIN LINE) PURPLE = COAXIAL CABLE (MAIN LINE) BLUE = 1x1 HYBRID CABLE (JUMPER) ORANGE -= 1/2"ø COAXIAL CABLE (JUMPER) GREEN -RET CONTROL CABLE(S) (JUMPER)



ARCHITECT/ENGINEER:



R.K. EXECUTIVE CENTRE
201 BOSTON POST ROAD WEST
SUITE 101
MARLBOROUGH, MA 01752 (508) 481-7400 www.chappellengineering.com

SEAL:



ENGINEER/LAND SURVEYOR DATE

DRAWING SCALE NOTE: THESE DRIVINGS HIME BEDI PREPARED IN ARCH D (24"38") FORMUL.
AS SUCH, THE WRITTEN SCILES SHOWN ON ANY REPRODUCTIONS OF A
COMPRISONORY SIZE SHALL BE REDUCTED MANUE.
ALL BRY SOULES MAY BE LEED REPRODUCTION SIZE.
WHERE IN CONFLICT, BRY SOULES SHALL SUPPRISEDE WRITTEN SCALES.

IT IS A VIOLATION OF LAW FOR ANY PERSON. UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

	REVISIONS				
NO.	DESCRIPTION	DATE			
0	ISSUED FOR REVIEW	1/20/22			
1	ISSUED FOR CONSTRUCTION (FINAL)	2/10/22			
2	REVISED TSA REFERENCE DATE	4/13/22			
3	REVISED MSA REFERENCE DATE	4/15/22			

PROJECT NAME:

SOUTH **GLASTONBURY 3 CT**


63 WOODLAND STREET SOUTH GLASTONBURY, CT 06073


RF BILL OF MATERIALS AND RF CABLE PLUMBING DIAGRAM

DRAWING NO:

RF03

L			
ı	SCALE:	DESIGNED BY: NWC	VZW PROJECT CODE:
ı	AS SHOWN	DRAWN BY: NWC	20212309233
ı		CHECKED BY: GRS	VZW PROJECT NO.:
ı	CEA PROJECT NO.:	ORIGINAL ISSUE DATE:	16085720
ı	96210.404	1/20/22	VZW LOCATION CODE: 708312





HYBRID CABLE COLOR CODE SPECIFICATIONS (2)



ARCHITECT/ENGINEER: CHAPPELL ENGINEERING ASSOCIATES, LLC

> R.K. EXECUTIVE CENTRE 201 BOSTON POST ROAD WEST SUITE 101 MARLBOROUGH, MA 01752 (508) 481-7400 www.chappellengineering.com

SEAL:



ENGINEER/LAND SURVEYOR DATE

DRAWING SCALE NOTE: THESE DRIMINGS HIME BEDI PREPARED IN ARCH D (24",38") FORMUL AS SUCH, THE IMPRIEN SOLES SHOWN ON ANY REPRODUCTIONS OF A CONTROCCIORY SIZE SHALL BE REDICERED IMPULD. ALL BAY SOLES WAY BE USED REPRODUCTION SIZE, WHERE IN CONTRUCT, BAY SOLES SHALL SUPPRISEDE WRITTEN SOLES.

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

	REVISIONS			
NO.	DESCRIPTION	DATE		
0	ISSUED FOR REVIEW	1/20/22		
1	ISSUED FOR CONSTRUCTION (FINAL)	2/10/22		
2	REVISED TSA REFERENCE DATE	4/13/22		
3	REVISED MSA REFERENCE DATE	4/15/22		
г				

PROJECT NAME:

SOUTH **GLASTONBURY 3 CT**

63 WOODLAND STREET SOUTH GLASTONBURY, CT 06073

DRAWING TITLE;

RF COLOR CODE **SPECIFICATIONS**

DRAWING NO:

RF04

ı	SCALE:	DESIGNED BY: NWC	VZW PROJECT CO
ı	N/A	DRAWN BY: NWC	20212309233
ı	,	CHECKED BY: GRS	VZW PROJECT NO
ı	CEA PROJECT NO.:	ORIGINAL ISSUE DATE:	16085720
ı	96210.404	1/20/22	VZW LOCATION CO 708312
ı			700012

LINE COLOR CODE SPECIFICATIONS 1

ELECTRICAL SPECIFICATIONS

- FURNISH ALL LABOR, MATERIALS, EQUIPMENT, TOOLS AND INCIDENTALS REQUIRED TO MAKE READY FOR USE THE COMPLETE ELECTRICAL SYSTEMS AS SHOWN ON THE DRAWINGS. MAKE ALL NECESSARY
- THE ELECTRICAL SYSTEMS SHALL BE SUITABLE IN EVERY WAY FOR THE SERVICE REQUIRED, ALL MATERIAL AND ALL WORK WHICH MAY BE REASONABLY IMPUED AS BEING INCIDENTAL TO THE WORK SHALL BE FUNDISHED AT NO EXTRA COST.
- FURNISH AND INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH THE REQUIREMENTS OF LOCAL, STATE AND NATIONAL CODES AND STANDARDS, INCLUDING BUT NOT LIMITED TO: THE 2018 CONNECTION! STATE BUILDING CODE

 - THE ZOTO CONTROLLOUS SAME BUILDING CODE
 THE MATIONAL ELECTROLL CODE (MPR-70)
 THE CONNECTICUT ELECTROC CODE
 THE CONNECTICUT ELECTROC SAFETY CODE (ANSI C-2)
 THE LIFE SAFETY CODE (MPR-1 tol)
 THE STRUCTURES STANDAMOS FOR AMERINA SUPPORTING STRUCTURE AND ANTENNAS
- MATERIALS AND EQUIPMENT SHALL BE NEW, UNUSED AND UNDERWRITERS' LABORATORIES, INC. LISTED. CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING ALL MATERIALS IN A TIMELY FASHION, INCLUDING RESPONSIBILITY FOR DETERMINION AVAILABILITY/LEAD TIME FOR ALL NECESSARY FOURMENT.
- CONTRACTOR SHALL OBTAIN ALL NECESSARY PERMITS AND PAY ALL FEES for PERMITS AND INSPECTION WHERE NEW COMMERCIAL POWER SERVICE IS PROVIDED TO THE STEL, OR EXISTING SERVICE MUST BE MODIFIED, CONTRACTOR SHALL MAKE JAMPANEADERS WITH THE ELECTRIC CITYL, SHALL PERFORM ALL OF HIS WORK IN ACCORDANCE WITH THE REQUIREMENTS OF THE UTILLITY, AND SHALL PAY ALL UTILITY SERVICE PERFORMANCE WITH THE REQUIREMENTS OF THE UTILLITY, AND SHALL PAY ALL UTILITY SERVICE PERFORMANCE WITH THE REQUIREMENTS OF THE UTILITY, AND SHALL PAY ALL
- ALL WIRING OUTSIDE SHALL BE INSTALLED IN HEAVY-GAUSE, (SCHEDULE 40) RIGID STEEL CONDUIT, HOT-DPPED CALVANIZED INSIDE AND OUTSIDE WITH AN ADDITIONAL FACTORY-APPLIED FINISH INSIDE AND OUTSIDE. CUT ENDES SHALL BE REAMED, THREAGED AND COLD CALVANIZED. NO COMPRESSION FITTING WILL BE ACCEPTED.
- UNDERGROUND CONDUITS SHALL BE PVC SCHEDULE 40 AND INSTALLED NOT LESS THAN 30 INCHES BELOW FINISHED GRADE.
- WIRING INSTALLED IN THE BUILDING THAT IS SHOWN TO BE IN CONDUIT SHALL BE INSTALLED IN EMT. EMT FITTINGS SHALL BE STEEL COMPRESSION TYPE.
- Liquid Tight, flexible metal conduit small be used for all motor terminations and for connections to equipment subject to vibrations. Lexible lexial conduit shall consist of a flexible, consiston resistant value, cope with all detribled, materials, synthetic, oxicet. Conduits smaller than 1-1/2° shall have a continuous ground conductor under the Jacket.
- 10. NO CONDUIT SMALLER THAN 3/4" ELECTRICAL TRADE SIZE SHALL BE USED, EXCEPT AS OTHERWISE SHOWN ON THE DRAWINGS. BOX SIZES SHALL BE 4" SQUARE MINMUM, BUT NOT LESS THAN THAT REQUIRED BY THE CONNECTION ELECTRICAL CODE.
- FITTINGS AND EXPOSED SWITCH, OUTLET AND CONTROL STATION BOXES AND OTHER EXPOSED BOXES 4* SQUARE SHALL BE CAST OR MALLEABLE IRON WITH CADMIUM-ZINC FINISH AND CAST COVERS WITH STANLESS STEEL SCREWS.
- 12. FLUSH SWITCH AND OUTLET BOXES SHALL BE HOT-DIPPED GALVANIZED, PRESSED STEEL WITH NYLON COVER PLATES, COLOR AS DETERMINED BY THE ENGINEER.
- 13. DICCEPT AS OTHERNES SHORM, TERMINA, SANCTION AND PULL BOXES LINGER THAT 4" SQUIME SHALL BE SHEET STEEL STEEL ROSES SHALL BE HOTO-POPED GAVANTICE BOXES AND CORES SHALL BE NOT LESS THAN 14 GAUGE METAL COVERS SHALL BE GASKETED AND FASTENED WITH STAINLESS STEEL HADDWARE.
- FITTINGS USED WITH LIQUID TIGHT, FLEXIBLE CONDUIT SHALL BE OF THE SCREW-IN, COMPRESSION TYPE WITH SEALING RING. FITTINGS LARGER THAN 1-1/4" SHALL BE FURNISHED WITH INTEGRAL GROUND LUGS.
- HANGERS, RODS, BACK PLATES, BEAM CLAMPS, ETC. SHALL BE GALVANIZED IRON OR STEEL. CONDUITS SHALL BE SUPPORTED AT LEAST EVERY 5 FEET.
- EXPOSED CONDUITS SHALL BE RINN PARALLEL TO OR AT RIGHT MAGLES TO WALLS. CONDUIT RINS SHALL BE STRAIGHT AND TIME. CONDUIT SHALL BE STRAIGHT AND THE CHORD THAT SHALL BE WITH SHALL BE WIT THREADED RODS NOT LESS THAN 3/8 INCHES IN DIAMETER. HANGERS SHALL BE ATTACHED TO STRUCTURAL STEEL BY MEANS OF BEAM CLAMPS, SPOT TYPE INSERTS SHALL BE USED IN CONCRETE.
- CONDUIT BENDS SHALL BE CAREFULLY MADE TO PREVENT DISTORTION OF THE CIRCULAR CROSS-SECTION. NO CONDUIT RUN SHALL HAVE MOBE THAN THE COUNLERT OF THESE OD ECROES BENDS BETWEEN PULLING POINTS. CHANGES IN DIRECTION SHALL BE MODE WITH BENDS, STANDARD ELBOWS AND PULLONGES, BENDS IN PRAPALLE RUNS SHALL BE CONCENTRIC.
- CONDUIT SHALL NOT BE SUPPORTED FROM PIPING, PIPING SUPPORTS, DUCTWORK, SUSPENDED CEILING SUPPORTS OR MECHANICAL EQUIPMENT SUBJECT TO VIBRATION OR REMOVAL.
- THE ENDS OF ALL CONDUITS SHALL BE TIGHTLY PLUGGED DURING BUILDING CONSTRUCTION UNTIL WIRES ARE TO BE PULLED, SPARE CONDUITS SHALL BE FURNISHED WITH THREADED CAPS.
- CONDUITS SHALL BE TERMINATED AT UNGASKETED SHEET STEEL BOXES AND ENCLOSURES WITH DOUBLE LOCK NITS AND SUITABLE BUSHNOS. BUSHNOS INSTALLED ON CONDUITS CONTINUNC GROUND WRESS SHALL BE GROUNDING TYPE. CONDUITS SHALL BE TERMINATED AT CASKETED SHEET METAL BOXES AND ENCLOSURES WITH CONDUIT HUBS.
- CONDUCTORS SHALL BE ANNEALED, 98 PERCENT CONDUCTIVITY, SOFT—DRAWN COPPER, NO CONDUCTOR SMALLER THAT NO. 12 AWG SHALL BE USED, EXCEPT AS OTHERWISE NOTED.
- 22. WREF FOR POWER AND LIGHTING BRANCH CIRCUITS SHALL BE 600 VOLT. TYPE THAN WIRE FOR CONTROL CIRCUITS SHALL BE 600 VOLT. TYPE THAN NO. 14 AWG, STANGED. SERVICE CONDUCTORS NO FEDERS SHALL BE TYPE XHHIR. CONDUCTORS NO. 10 AWG AND SMALLER SHALL BE SOLID. NO. 8 AWG AND LARGER SHALL BE STANGED.
- 23. ALL CONDUCTORS SHALL BE CAREFULLY HANDLED TO AVOID KINKS OR DAMAGE TO INSULATION. LUBRICATIONS PAUL BE USED TO FACILITATE WIRE PULLING. LUBRICANTS SHALL BE UL LISTED FOR USE WITH THE INSULATION SPECIFIED.
- ALL EQUIPMENT AND MATERIALS SHALL BE GROUNDED IN STRICT ACCORDANCE WITH THE CONNECTICUT ELECTRICAL CODE. AND THE STANDARD REQUIREMENTS OF VERIZON WIRELESS AND LUCENT.
- DISCONNECT SWITCHES SHALL BE 480 OR 240 VOLT, HEAVY-DUTY, QUICK-MAKE, QUICK BREAK, VISIBLE BLADE, 2 POLE WITH EXTERNAL OPERATING HANDLE AND FULL COVER INTERLOCK. SWITCHES INSTALLED OUTSIDE SHALL BE NEMA TYPE 3R ENCLOSED.
- WALL SWITCHES SHALL BE SINGLE POLE 3-WAY OR 4-WAY, INDICATING, TOGGLE-ACTION, FLUSH, QUIET TYPE, SPECIFICATION GRADE, RATED 20 AMPERE, 120-277 VOLT. COLOR AS DETERMINED BY ENGINEER.
- GENERAL PURPOSE RECEPTACLES SHALL BE DUPLEX, 2 POLE, 3 WIRE, STRAIGHT BLADE, NYLON FACE, GROUNDING TYPE, 20 AMPERE, 125 VOLT, SPECIFICATION GRADE. COLOR AS DETERMINED BY ENGINEER
- 28. PANELS SHALL BE PER DIRECTED BY THESE DRAWINGS WITH TYPED DIRECTORIES.
- 29. CIRCUIT BREAKERS SHALL BE MOLDED CASE, THERMAL-MAGNETIC TYPE WITH RIAS SYMMETRICAL, INTERRIPTING RATING OF NOT LESS THAN 22,000 AMPERE FOR 240 VOLT BREAKERS, DIXLOSED BREAKERS SHALL HAVE PAUGLOONE PROVISIONS AND DETERNAL OPERATING HANDLE WITH FULL COVER INTERLOCK, BREAKERS SHALL BE 1" MODULES MINIMUM.
- 30. NAMEPLATES SHALL BE PROVIDED FOR ALL EQUIPMENT INDICATING VOLTAGE, PHASE, USE AND SOURCE OF ORIGIN. DEVICES SHALL BE LABELED INDICATING VOLTAGE AND BRANCH CIRCUIT. BEARCH CONDUCTORS SHALL BE LABELED INDICATING BRANCH CIRCUIT. FEEDER CONDUCTORS SHALL BE LABELED INDICATING BRANCH CIRCUIT. FEEDER CONDUCTORS SHALL BE LABELED INDICATING BRANCH CIRCUIT. FEEDER CONDUCTORS SHALL INDICATE PHASE.
- 31. ALL EXTERIOR CONDUCTOR/LUG TERMINALS SHALL HAVE AN ANTIOXIDANT APPLIED.
- 32 ALL SPRING TYPE WIRE CONDUCTORS USED IN EXTERIOR BOXES SHALL BE SUICON FILED

- ELECTRICAL CONTRACTOR SHALL AS PART OF HIS WORK INCLUDE ALL FITTINGS, SLEEVES AND MINOR CUTTING REQUIRED FOR HIS WORK, INCLUDING FIRES-STOPPING.
- THE ELECTRICAL CONTRACTOR, AT HIS OWN EXPENSE, SHALL PROVIDE HIS OWN, WHERE DIRECTED, STORAGE AND OFFICE SPACE.
- 35. FIVE COPIES OF SHOP DRAWINGS OF ALL EQUIPMENT SHALL BE PROVIDED TO THE ENGINEER
- ELECTRICAL CONTRACTOR'S WORK SHALL INCLUDE ALL LABOR AND MATERIALS, SCAFFOLDING TOOL AND TRANSPORTATION NECESSARY FOR COMPLETE INSTALLATION.
- 37. ELECTRICAL CONTRACTOR TO FURNISH ENGINEER ONE SET OF MYLARS OF "AS BUILT" DRAWINGS.
- 38. ELECTRICAL CONTRACTOR SHALL PROVIDE TEMPORARY POWER & LIGHTING AS REQ'D.

GENERAL NOTES

- 1. CONTRACTOR SHALL WSIT THE SITE TO MAKE HIMSELF AWARE OF THE EXISTING CONDITIONS.
- 2. BRANCH CIRCUIT RUNS 100 FT AND OVER SHALL BE #10 AWG CONDUCTORS.
- THESE DRAWINGS ARE DIAGRAMMATIC ONLY. THE EXACT LOCATION, MOUNTING HEIGHT, SIZE OF EQUIPMENT AND ROUTING OF RACEWAYS SHALL BE COORDINATED AND DETERMINED IN THE FIELD.
- THE ELECTRICAL CONTRACTOR SHALL COORDINATE WITH THE HAVE AND PLUMBING CONTRACTORS AS TO THE EXACT LOCATION OF THEIR RESPECTIVE FOURMENT, THE POWER WIRING, THE CONTROL WIRING AND ALL ELECTRICAL CONDECTIONS REQUIRED BY THIS CONTRACTOR FOR COMPLETELY OPERATIVE HAVE AND PLUMBING SYSTEMS IN CONFORMANCE WITH THE CONTRACT DOCUMENTS.
- INTERRUPTIONS TO THE EXISTING ELECTRICAL SERVICE FOR SPLICING CONNECTIONS, RENOVATION OF EXISTING DISTRIBUTION, BRANCH CIRCUITS, INSTALLATION OF NEW ELECTRIC SERVICE, AND SHALL BE AS SHORT AS POSSIBLE, AND TO THE CONNEWENCE OF THE OWNER.
- ALL CONDUIT SHALL BE SURFACE MOUNTED UNLESS OTHERWISE NOTED. NO INTERIOR HORIZONTAL CONDUIT BELOW 7'-8" AFF IN FINISHED SPACES.
- 7. ALL WIRING TO BE 3/4°C, 2#12 & 1#12 GROUND, UNLESS OTHERWISE NOTED.
- 8. NO RX OR ROMEX CARLE IS PERMITTED.
- 9. ALL WIRING DEVICES AND EQUIPMENT SHALL BE 20A SPECIFICATION GRADE AND UL LISTED.
- 10. ALL OUTLET AND JUNCTION BOXES SHALL BE SECURELY SURFACE MOUNTED.
- ALL RECEPTACLE AND EQUIPMENT CIRCUITS SHALL BE GROUNDED USING A FULL SIZE EQUIPMENT GROUNDING CONDUCTOR RUN WITH THE CURRENT CONDUCTORS.
- 12. ALL WALL PENETRATIONS FOR TELCO, POWER. AND GROUNDING SHALL REQUIRE PVC SLEEVES.
- 13. ALL SWITCHES SHALL BE FORTY-FIGHT (48) INCHES AFF, UNLESS OTHERWISE NOTED.

EDWART OUTLET - -- 182 (7.2)

- 14. ALL RECEPTACLES SHALL BE EIGHTEEN (18) INCHES AFF, UNLESS OTEHRWISE NOTED.
- 16. ALL WRING SHALL BE IN METAL RACEWAY & NO. 12 AWG COPPER MIN, UNLESS OTHERWISE NOTED.
- 16. WIRE COLOR SHALL BE PER STANDARD CODING BY PHASE.
- 17. FOR UTILITY BILLING, PLEASE SEND TO: VERIZON WIRELESS 20 ALEXANDER DRIVE WALLINGFORD, CT 06492

COOLANT DRAW

SALON SALON

GROUNDING GENERAL NOTES

- ALL EXTERIOR CONDUCTORS SHALL BE #2 AWG, SOLID, BARE, TINNED COPPER, UNLESS OTHERWISE NOTED. MINIMUM BEND RADIUS SHALL BE EIGHT (8) INCHES.
- ALL CONNECTIONS TO HALO GROUND RING AND ALL CABLE TRAY JUMPERS SHALL BE #6 AWG, INSULATED, STRANDED, COPPER WIRE.
- ALL WIRE-TO-WIRE CONNECTIONS SHALL BE THREE-CLAMP, C TAP COMPRESSION (TAB #54740 ORANGE OR EQUIVALENT), ALL GROUND BAR CONNECTIONS SHALL BE TWO-HOLE, LONG-BARREL TYPE COMPRESSION LUSS (TAB OR EQUIVALENT), ALL OTHER CONNECTIONS TO SIEEL SURFACES SHALL USE LUP-TPE CONNECTION.
- 4. MECHANICALLY BOND ANTENNA MOUNTS WITH #2 AWG, BARE, STRANDED CONDUCTORS
- 5 ALL CROLINGING WORK SHALL COMPLY WITH VERITON WIRELESS STANDARDS
- CONNECT GROUND CONDUCTOR TO EXISTING GROUNDING SYSTEM. ATTACH TO WALLS, PARAPET, CABLE TRAY, ETC. WITH A CLAMPS AS NECESSARY. REMOVE PAINT, FIREPROOFING, MILL SCALE, ETC. TO ACHIEVE GOOD CAD WELD GROUND CONNECTION.
- 8. CONNECT TO ENCLOSURES USING BLUE GROUND LUGS.

LEGEND

ELECTRICAL SYMBOLS



METER

 \boxtimes GROUND ROD/TEST (OBSERVATION) WELL

⊗ GROUND ROD

 \blacksquare

CADWELD TYPE CONNECTION COMPRESSION TYPE CONNECTION GROUNDING WIRE



REPRESENTS DETAIL NUMBER



1'X4' SURFACE MTD. FLOURESCENT LIGHTING FIXTURE



0

SELF CONTAINED EMERG, LIGHTING UNIT

20A-120V-1P TOGGLE SWITCH

[6] MAGNETIC DOOR SWITCH (DOOR JAMB TYPE)

20A-120V QUADRAPLEX RECEPTACLE, GROUNDING TYPE,

20A-120V DUPLEX RECEPTACLE, GROUNDING TYPE.
WP = WEATHERPROOF
GFI = GROUND FAULT $\Theta_{\overline{R}}$

SIMPLEX RECEPTACLE, GROUNDING TYPE.
TL = TWIST LOCK

0 JUNCTION BOY

P1 PANELBOARD 'P1'

* @ MOTOR - NUMERAL DENOTES HORSEPOWER N. WEATHER PROOF DISCONNECT SWITCH

Zμ FUSED DISCONNECT SWITCH - '3R' & '1' - NEMA ENCLOSUR

THERMOSTAT * Φ_{H} - HI TEMPERATURE ALARM THERMOSTA * D-HUMIDISTAT *® HALO - HI/LO HUMIDITY ALARM HUMIDISTA * @-

SURGE ARRESTOR - JOSLYN CAT. NO. 1455-85

COMBINATION SMOKE/HEAT DETECTOR WITH MINI HORN SIMPLEX CAT. \$\int 2098-9696 WITH FORM A & C CONTACTS

g1-2 HOMERUN TO PANEL (FURNISH & INSTALLED BY MECHANICAL)

ABOVE FINISHED FLOOR

MOTORIZED DAMPER T_{2#12-3/4°C} EXPOSED CONDUIT 2#12-3/4°C.

TC ALARM TERMINAL CARINET

ABBREVIATIONS

AWG AMERICAN WIRE GAUGE BARE COPPER WIRE GPS GLOBAL POSITIONING SYSTEM PCS PERSONAL COMMUNICATION SYSTEM

RWY RACEWAY TYPICAL TYP

RGS RIGID GALVANIZED STEEL

EMT ELECTRICAL METALLIC TUBING DWG

FMT INTERIOR GROUND RING (HALO)

GEN GENERATOR GR

CGBE COAX GROUND BAR EXTERNAL CIGBE COAX ISOLATED GROUND BAR EXTERNAL

MGB PVC RIGID (SCH. 40) POLYVINYL CHLORIDE CONDUIT

EBH ETHERNET BACK HAUL

CLIENT: verizon

ARCHITECT/ENGINEER:



R.K. EXECUTIVE CENTRE 201 BOSTON POST ROAD WEST SUITE 101 MARLBOROUGH, MA 01752 (508) 481-7400 www.chappellengineering.com

SEAL:



ENGINEER/LAND SURVEYOR DATE

DRAWING SCALE NOTE: THESE DRAWNS HAVE BEEN PREPARED IN ARCH D (241-36") FORMAT, AS SUCH, THE WRITTEN SOLES SHOWN ON JAWN REPRODUCTIONS OF A COMPRISORIES FOR SHOWN ON JAWN REPRODUCTIONS OF A ALL BAY SOLES MAY GE LEED ROWNINGS OF REPRODUCTION SIZE. WHERE IN CONTLOT, BAY SOLES SHALL SUPERSIZE WRITTEN SOLES.

IT IS A VIOLATION OF LAW FOR ANY PERSON INLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER.

	TO ALTER THIS DOCUMENT.				
REVISIONS					
NO.	DESCRIPTION	DATE			
0	ISSUED FOR REVIEW	1/20/22			
1	ISSUED FOR CONSTRUCTION (FINAL)	2/10/22			
2	REVISED TSA REFERENCE DATE	4/13/22			
3	REVISED MSA REFERENCE DATE	4/15/22			

PROJECT NAME: SOUTH GLASTONBURY 3 CT

63 WOODLAND STREET SOUTH GLASTONBURY, CT 06073


DRAWING TITLE:


ELECTRICAL SPECIFICATIONS AND NOTES

DRAWING NO:

F01

SCALE:	DESIGNED BY: NWC	VZW PROJECT CODE:
AS SHOWN	DRAWN BY: NWC	20212309233
	CHECKED BY: GRS	VZW PROJECT NO.:
CEA PROJECT NO.:	ORIGINAL ISSUE DATE:	16085720
96210.404	1/20/22	VZW LOCATION CODE: 708312







KOHLER 50kW DIESEL GENERATOR WITH 283 GA SUB-BASE DIESEL FUEL TANK (PART #50REOZJE) OVERALL GENERATOR (ENCLOSURE) APPROXIMATE OWENDED SENERATION (ENGLOSUE) AFT-NONIMIES

DIMENSIONS: 91.3"1. × 41.2"W x 87.8"H (INCLUDES SUB-BASE DIESEL TANK)


APPROXIMATE MAX. IN-SERVICE WEIGHT: 3,795 lbs








TYPICAL BURIED CONDUIT DETAIL 2



TYPICAL CONDUIT STUB-UP DETAIL 3
SCALE: NONE 602





RAB LIGHTING — BULLET2X12B 24W BLACK

TYPICAL LED FLOOD LIGHT DETAIL (F02)



ARCHITECT/ENGINEER:



R.K. EXECUTIVE CENTRE
201 BOSTON POST ROAD WEST
SUITE 101
MARLBOROUGH, MA 01752
(508) 481-7400
www.chappellengineering.com

SEAL:



ENGINEER/LAND SURVEYOR DATE

DRAWING SCALE NOTE;
THESE DRAWGS HAVE BEEN PREPARED IN ARCH D (24'-38') FORMAT.
AS SLON, THE WRITTEN SOLES SHOWN ON ANY PERFOCUTIONS OF A
CONTRACTION SIZE. SHOW HE RESIDEED INJURIES OF A
ALL ON SOLES ANY ELED NOTIFICIAL OF PREPARED.
HERE IN CONTLOT, BAS SOLES SHALL SHEREDE. WRITTEN SOLES.

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

REVISIONS				
NO.	DESCRIPTION	DATE		
0	ISSUED FOR REVIEW	1/20/22		
1	ISSUED FOR CONSTRUCTION (FINAL)	2/10/22		
2	REVISED TSA REFERENCE DATE	4/13/22		
3	REVISED MSA REFERENCE DATE	4/15/22		

PROJECT NAME:

SOUTH GLASTONBURY 3 CT

63 WOODLAND STREET SOUTH GLASTONBURY, CT 06073


DRAWING TITLE:


EQUIPMENT COMPOUND UTILITY PLAN & DETAILS

DRAWING NO:

E02

SCALE:	DESIGNED BY: NWC	VZW PROJECT CODE
AS SHOWN	DRAWN BY: NWC	20212309233
AS SHOWN	CHECKED BY: QRS	VZW PROJECT NO.:
CEA PROJECT NO.:	ORIGINAL ISSUE DATE:	16085720
96210.404	1/20/22	VZW LOCATION CODE 708312











R.K. EXECUTIVE CENTRE
201 BOSTON POST ROAD WEST
SUITE 101
MARLBOROUGH, MA 01752
(508) 481-7400
www.chappellengineering.com

AL:



ENGINEER/LAND SURVEYOR DATE

DRAWING SCALE NOTE;
THESE DRAWINGS HAVE BEEN PREPARED IN ARCH D (24*38*) FORMAT.
AS SUCH, HE WINTEN SULES SHOWN ON AN "EPPROCURIONS OF A CONTRACTION" SIZE SHALL BE FRENCHED INVOICED. SIZE ALL BY SOLALS MORE BEEN DRAWING SHE SHAPE IN CONTIC. BY SOLALS SHALL SHEPPEDE WINTEN SOLALS.

IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

	REVISIONS			
NO.	DESCRIPTION	DATE		
0	ISSUED FOR REVIEW	1/20/22		
1	ISSUED FOR CONSTRUCTION (FINAL)	2/10/22		
2	REVISED TSA REFERENCE DATE	4/13/22		
3	REVISED MSA REFERENCE DATE	4/15/22		
П				

PROJECT NAME:

SOUTH GLASTONBURY 3 CT

63 WOODLAND STREET SOUTH GLASTONBURY, CT 06073


DRAWING TITLE;


SCHEMATIC GROUNDING PLAN & DETAILS

DRAWING NO:

E04

- 1	SCALE:	DESIGNED BY: NWC	VZW PROJECT CODE:
_	AS SHOWN	DRAWN BY: NWC	20212309233
- 1		CHECKED BY: GRS	VZW PROJECT NO.:
- 1	CEA PROJECT NO.:	ORIGINAL ISSUE DATE:	16085720
	96210.404	1/20/22	VZW LOCATION CODE: 708312





 Page: 1

 Prepared by:
 Date: 2/ 9/22

Load no. 1: Front No Ice (units - kips ft.)
/ JOINT LOADS / BEAM LOADS / JOINT LOADS / BEAM LOADS / JOINT LOADS
/ JOINT LOADS FX2 0.073 FX3 -0.045 N 70 26 FX2 0.025 FX3 -0.045 N 84 54 76 38 FX2 0.047 FX3 -0.023 N 132 FX2 0.047 FX3 -0.023 N 133 135 FX2 0.22 FX3 -0.045 N 28 27
FX2 0.143 FX3 -0.045 N 48 47 64 63 FX2 0.57 FX3 -0.084 N 126 131 127 136 125 134 / END
FORCE SUMMATION
FX1=0. kip FX2=4.819 kip FX3=-1.113 kip

Load no. 2: Side No Ice (units - kips ft.)
/ JOINT LOADS / BEAM LOADS / JOINT LOADS / BEAM LOADS / JOINT LOADS
/ BEAM LOADS / JOINT LOADS / BEAM LOADS / JOINT LOADS / JOINT LOADS / JOINT LOADS
/ JOINT LOADS FX1 0.025 FX3 -0.044 N 70 26 76 38 84 54 FX1 0.047 FX3 -0.023 N 132 135 133 FX1 0.143 FX3 -0.045 N 28 27 48 47 64 63 FX1 0.057 FX3 -0.084 N 126 127 125
FX1 0.057 FX3 -0.084 N 131 136 134 / END
FORCE SUMMATION
FX1=1.491 kip FX2=0. kip FX3=-1.107 kip

 Prepared by:
 Page: 2

 Date: 2/ 9/22
 Date: 2/ 9/22

Load no. 3: Front Ice (units - kips ft.)

/ JOINT LOADS

/ BEAM LOADS

/ JOINT LOADS

/ DEAM LOADS

/ BEAM LOADS

/ JOINT LOADS

/ JOINT LOADS

/ BEAM LOADS

/ JOINT LOADS

/ JOINT LOADS

/ JOINT LOADS

FX2 0.021 FX3 -0.075 N 70 26

FX2 0.01 FX3 -0.075 N 76 38 84 54

FX2 0.016 FX3 -0.049 N 132 135 133

FX2 0.065 FX3 -0.156 N 28 27 48 47 64 63

FX2 0.02 FX3 -0.123 N 126 127 125 134 131 136

/ END

FORCE SUMMATION

FX1=0. kip

FX2=0.64 kip

FX3=-2.271 kip

Load no. 4: Side Ice (units - kips ft.)

/ JOINT LOADS

/ BEAM LOADS

/ JOINT LOADS

/ BEAM LOADS

/ JOINT LOADS

/ BEAM LOADS / JOINT LOADS

/ JOINT LOADS

/ JOINT LOADS

/ JOINT LOADS

FX1 0.01 FX3 -0.075 N 70 26 38 76 84 54

FX1 0.01 FX3 -0.049 N 132 135 133

FX1 0.048 FX3 -0.156 N 28 27 48 47 64 63

FX1 0.014 FX3 -0.123 N 126 127 125 134 131 136

/ END

FORCE SUMMATION

FX1=0.462 kip

FX2=0. kip

FX3=-2.271 kip

 Prepared by:
 Page: 3

 Date: 2/ 9/22

Load no. 5: Selfweight (units - kips ft.)

/ BEAM LOADS

SELF X3 -1. B 1 TO 138 142 TO 150

/ GLOBAL LOADS

/ GLOBAL LOADS

/ GLOBAL LOADS

DIST FX3 -0.003 PLANE -7.25 4.763 0. -1.805 4.763 0. -5.028 -0.818

0. PT -0.5 0.866 BEAMS

DIST FX3 -0.003 PLANE 1.805 4.763 0. 7.25 4.763 0. 7.75 3.897 0. PT

3.223 5.581 BEAMS

DIST FX3 -0.003 PLANE -3.222 -3.945 0. 3.222 -3.945 0. 0.5 -8.66

0. PT 2.722 4.715 BEAMS

/ END

FORCE SUMMATION

FX1=0. kip

FX2=0. kip

FX3=-1.4597 kip

Load no. 6: Front Frame Ice (units - kips ft.)

/ BEAM LOADS

DIST GL FX2 -0.002 B 1 4 5 13 TO 35 BY 2 49 TO 51 55 56 63 64 66 71 TO 74

76 TO 81 83 TO 88 90 TO 115 117 133 TO 135 142 TO 150

/ END

FORCE SUMMATION

FX1=0. kip

FX2=-0.3127 kip

FX3=0. kip

Load no. 7: Side Frame Ice (units - kips ft.)

/ BEAM LOADS

/ BEAM LOADS

DIST GL FX1 -0.002 B 4 5 13 TO 35 BY 2 50 51 63 64 66 71 72 TO 78 BY 2

79 TO 81 83 TO 88 90 91 93 94 TO 100 BY 2 101 TO 115 117 133 TO 135

142 TO 150

/ END

FORCE SUMMATION

FX1=-0.2564 kip

FX2=0. kip

FX3=0. kip

 Prepared by:
 Page: 4

 Date: 2/ 9/22

Load no. 8: Front Frame No Ice (units - kips ft.)

/ BEAM LOADS / BEAM LOADS

DIST GL FX2 -0.005 B 1 4 5 13 TO 35 BY 2 49 TO 51 55 56 63 64 66 71 TO 74

76 TO 81 83 TO 88 90 TO 115 117 133 TO 135 142 TO 150

/ END

FORCE SUMMATION

FX1=0. kip FX2=-0.7817 kip FX3=0. kip

Load no. 9: Side Frame No Ice (units - kips ft.)

/ BEAM LOADS

/ BEAM LOADS

/ BEAM LOADS

DIST GL FX1 -0.005 B 4 5 13 TO 35 BY 2 50 51 63 64 66 71 72 TO 78 BY 2

79 TO 81 83 TO 88 90 91 93 94 TO 100 BY 2 101 TO 115 117 133 TO 135

142 TO 150

/ END STATIC

FORCE SUMMATION


FX1=-0.6411 kip

FX2=0. kip

FX3=0. kip


South Glastonbury 3 CT Mount Analysis X3_N Load 1: Front No Ice


SCALE = 1:30UNITS: kip ft DATE: 2/ 9/22



South Glastonbury 3 CT Mount Analysis X3_N Load 2: Side No Ice

UNITS: kip ft DATE: 2/ 9/22 SCALE = 1:30






DATE: 2/ 9/22

UNITS: kip ft

SCALE = 1:30




South Glastonbury 3 CT Mount Analysis

Load 4: Side Ice

DATE: 2/ 9/22

UNITS: kip ft


SCALE = 1:30



Load 5: Selfweight

SCALE = 1:30 UNITS: kip ft DATE: 2/ 9/22






South Glastonbury 3 CT Mount Analysis	
Load 6: Front Frame Ice	X3 X2 X1

UNITS: kip ft

SCALE = 1:30

DATE: 2/ 9/22






South Glastonbury 3 CT Mount Analysis	
Load 7: Side Frame Ice	X3 X2 X1


UNITS: kip ft

SCALE = 1:30

DATE: 2/ 9/22



South Glastonbury 3 CT Mount Analysis				
Load 8: Front Frame No Ice			X3 X2 X1	
SCALE = 1:30	UNITS: kip ft	DATE: 2/ 9/22	, , , ,	




South Glastonbury 3 C	Mount Analysis	
Load 9: Side Frame No	o Ice	X3 X2 X1

DATE: 2/ 9/22

UNITS: kip ft

SCALE = 1:30



South Glastonbury 3 CT Mount Analysis	
View: Steel Beam Design SCALE = 1:24	X3 →X2 →X1
235 255 275 275 275 275 275 275 275 275 27	28% 28% 28% 28% 28% 28% 28% 28% 27% 2.0% 28% 27% 2.0% 27% 2.0% 27% 2.0% 27% 2.0% 2.0% 2.0% 2.0% 2.0% 2.0% 2.0% 2.0

South Glastonbury 3 CT Mount Analysis

Code: AISC-LRFD

Prepared by: Date: 2/ 9/22

Results				Summary Table							
			Dof			D:		APAC	ITY	Cambina -	
Beam	Section	Com	Defl L/	Slen	Axial	Dir	Shear	Мот	LTB	Combined Axial+Mom	
1	PIPE 3	1	518	150	0.01	MJ		0.13	0.13	0.20	
2	TS 4x4x1/4	1	2962	57	0.02	MI MJ		0.07 0.08	0.00	0.27	
2	TS 4x4x1/4	1	3294	57	0.02	MI		0.20 0.08	0.00 80.0	0.26	
3	13 444 1/4	'	3234	37	0.02		0.03	0.00	0.00	0.20	
6	PIPE 2	1	7444	8	-0.01	MJ MI		0.14 0.04	0.14 0.00	0.18	
7	PIPE 2	1	9999	8	0.00	MJ	0.05	0.14	0.14	0.17	
8	PIPE 2	1	9999	8	0.01	MI MJ		0.03 0.12	0.00 0.12	0.18	
0	TC 4::4::4/4	4	2004	4.5	0.04		0.04	0.13	0.00	0.00	
9	TS 4x4x1/4	4	3861	45	-0.01	MJ MI		0.07 0.03	0.07 0.00	0.08	
	TS 4x4x1/4 TS 4x4x1/4	3	9999 9999	26 26	0.01 0.00	MI MI		0.00 0.00	0.00	0.01 0.00	
	TS 4x4x1/4	1	9999	26	0.00	MI		0.00	0.00	0.00	
49	PIPE 2	1	403	201	-0.06	MJ	0.02	0.16	0.16	0.38	***
52	PIPE 2	1	9999	15	0.00	MI MJ		0.18 0.06	0.00	0.06	
	PIPE 2	1	9999	15	0.00	MJ		0.07	0.07	0.07	
	PIPE 2	2	9999	15	0.00		0.00	0.01	0.01	0.01	
57	PIPE 2	1	6219	8	-0.01	MJ MI		0.15 0.03	0.15 0.00	0.17	
59	TS 4x4x1/4	1	9999	26	0.00	MI		0.00	0.00	0.00	
60	PIPE 2	1	4173	8	-0.01		0.04 0.01	0.26 0.04	0.26 0.00	0.30	
62	TS 4x4x1/4	1	9999	26	0.00	MI		0.00	0.00	0.00	
67	PIPE 2	1	9999	8	0.01	MJ		0.10	0.10	0.16	
69	TS 4x4x1/4	1	9999	26	0.00	MI MI		0.13 0.00	0.00	0.00	
	PIPE 3	4	643	150	0.01	MJ	0.02	0.13	0.13	0.17	
87	PIPE 3	4	645	150	0.01		0.01	0.06 0.13	0.00	0.16	
03	PIPE 2	1	177	88	-0.02	MI MJ		0.04 0.20	0.00 0.20	0.25	***
90		'	'''	00	-0.02	MI		0.20	0.00	0.23	
94	PIPE 2	1	157	88	-0.03	MJ MI	0.01	0.19 0.07	0.19	0.27	***
96	PIPE 2	1	87	69	-0.01	MJ	0.01	0.13	0.13	0.51	***
98	PIPE 2	1	92	91	0.00	MI MJ		0.37 0.14	0.00 0.14	0.45	***
						MI	0.03	0.31	0.00		
101	PIPE 2	1	427	86	-0.01	MJ MI		0.13 0.14	0.13	0.27	
102	PIPE 2	1	193	91	-0.01	MJ	0.01	0.08	0.08	0.28	***
103	PIPE 2	4	680	205	-0.05	MI MJ		0.26 0.16	0.00 0.16	0.23	***
						MI	0.01	0.06	0.00		4.4.
104	PIPE 2	1	225	68	0.00	MJ MI		0.08 0.24	0.08	0.28	***
106	PIPE 2	1	175	68	-0.01	MJ	0.01	0.09	0.09	0.39	***
109	PIPE 2	1	227	91	-0.01	MI MJ		0.33 0.07	0.00 0.07	0.28	***
	PIPE 2	1	411	87	-0.01	MI MJ	0.02	0.25 0.14	0.00 0.14	0.29	
110	FIFLZ	'	411	07	-0.01		0.01	0.14	0.00	0.29	
111	PIPE 2	3	686	209	-0.06	MJ		0.15	0.15	0.21	***
112	PIPE 2	1	195	66	0.00	MI MJ	0.00	0.05 0.05	0.00 0.05	0.35	***
11/	PIPE 2	1	214	74	-0.01	MI MJ	0.03 0.01	0.30 0.12	0.00 0.12	0.31	***
114	<u> </u>	'	۷۱4	, 4	-0.01		0.01	0.12	0.12	0.51	

Chappell Engineering Associates, LLC


Strap 2017.00

South Glastonbury 3 CT Mount Analysis Code: AISC-LRFD

Prepared by: Date: 2/ 9/22

	Results Summary Table										
	CAPACITY										
			Defl			Dir				Combined	ĺ
Beam	Section	Com	L/	Slen	Axial		Shear	Mom	LTB	Axial+Mom	
139	2L 3x3x1/4	4	9999	91	-0.05	MI	0.00	0.00	0.00	0.05	
140	2L 3x3x1/4	4	9999	90	-0.05	MI	0.00	0.00	0.00	0.05	ĺ
141	2L 3x3x1/4	3	9999	90	-0.05	MI	0.00	0.00	0.00	0.05	

South Glastonbury 3 CT Mount	Analysis	
View: Steel Beam Design		X3 X2 X1
SCALE = 1:27	DATE: 2/ 9/22	



Code: AISC-LRFD

South Glastonbury 3 CT Mount Analysis

Date: 2/ 9/22 Prepared by:

Detailed Results Table for Beam 96 - 17

Moments: kips*foot, Forces: kips, Stresses: ksi, Section prop.: inch

X2 (Major axis) 72 30 Beam: 96, 74, 134, 17 6.00

CONSTRAINTS

DESIGN DATA

- Sections : Check -Kx = 1.00- Ky = 1.00

- Steel Grade: A500C - Allow. Slend.: 200 (compr.) 300 (tens.)

- Allowable Deflection : 1/240

- Tension Area Reduction Factor: 1.00

- Building type : Unbraced


Section: PIPE 2

0.67 ly = 0.67 in 4 Zx = 0.76 Zy = 0.76 in 3 Area = 1.07lx =


2.37 t = 0.15inD =1.33 Cw = 0.00 in 6

DESIGN COMBINATION = 1

M2 Moment Diagram



Max. AXIAL Force = 0.09 (tens.), -0.05 (compr.) Max. SHEAR Force = 0.15 M3 Moment Diagram



Max. AXIAL Force = 0.09 (tens.), -0.05 (compr.) Max. SHEAR Force = 0.54

SECTION CLASSIFICATION: *** COMPACT ***

Limiting Ratios: Compact Non-Compact

d/t = 15.4645.0 (Fy= 46.0 R = -0.002)71.7

DESIGN	EQUATION	FACTORS	VALUES	RESULT
V2 Shear (F2-1)	Vu/(.9*Vn)<1.00 Vn=0.6*Fy*Av	Av = 0.64	Vu = 0.54 Vn = 17.81	0.03
M3 Moment (A-F1-1) without LTB	M 0.9Mn < 1.00	Z = 0.76	M = 0.98 Mn = 2.92	0.37
V3 Shear (F2-1)	Vu/(.9*Vn)<1.00 Vn=0.6*Fy*Av	Av = 0.64	Vu = 0.15 Vn = 17.81	0.01

Date: 2/ 9/22 Prepared by:


Detailed Results Table for Beam 96 - 17

Moments: kips*foot, Forces: kips, Stresses: ksi, Section prop.: inch

DESIGN	EQUATION	FACTORS	VALUES	RESULT
M2 Moment (A-F1-1) without LTB	M 0.9Mn < 1.00	Z = 0.76	M = 0.35 Mn = 2.92	0.13
Deflection	defl. L / 240 < 1.00		defl = 0.82553	2.75
Axial Force (D1-1)	Pu < 1.00 0.90AgFy	(kL/r)x =31 (kL/r)y =31	Pu = 0.09 Ag = 1.07 Fy = 46.00	0.00
Combined Forces (compress.) (H1-1b)	Pu + Mux Muy 2φPn φMnx φMny < 1.00	Cmx = 1.00 Cmy = 1.00 Pex = 321.36 Pey = 321.36	Mux = 0.35 Muy = 0.98 B1x = 1.00 B1y = 1.00	0.51

Detailed Results Table for Beam 98 - 19

Moments: kips*foot, Forces: kips, Stresses: ksi, Section prop.: inch



Check - Sections :

-Kx = 1.00- Ky = 1.00

- Steel Grade: A500C - Allow. Slend.: 200 (compr.) 300 (tens.) - Allowable Deflection: 1/240

- Tension Area Reduction Factor: 1.00

- Building type : Unbraced


Section: PIPE 2

$$Ix = 0.67 \ Iy = 0.67 in4 \ Zx = 0.76 \ Zy = 0.76 in3 \ Area = 1.07 \ D = 2.37 \ t = 0.15 in$$

1.33 Cw = 0.00in6

DESIGN COMBINATION = 1

M2 Moment Diagram




Max. AXIAL Force = 0.16 (tens.), 0.00 (compr.) Max. SHEAR Force = 0.16

Prepared by: Date: 2/ 9/22

Detailed Results Table for Beam 98 - 19

Moments: kips*foot , Forces: kips , Stresses: ksi , Section prop.: inch



Max. AXIAL Force = 0.16 (tens.), 0.00 (compr.) Max. SHEAR Force = 0.51

SECTION CLASSIFICATION: *** COMPACT ***

Limiting Ratios: Compact Non-Compact

d/t = 15.46 < 45.0 71.7 (Fy= 46.0 R = -0.003)

DESIGN	EQUATION	FACTORS	VALUES	RESULT
V2 Shear (F2-1)	Vu/(.9*Vn)<1.00 Vn=0.6*Fy*Av	Av = 0.64	Vu = 0.51 Vn = 17.81	0.03
M3 Moment (A-F1-1) without LTB	M 0.9Mn < 1.00	Z = 0.76	M = 0.80 Mn = 2.92	0.31
V3 Shear (F2-1)	Vu/(.9*Vn)<1.00 Vn=0.6*Fy*Av	Av = 0.64	Vu = 0.16 Vn = 17.81	0.01
M2 Moment (A-F1-1) without LTB	M 0.9Mn < 1.00	Z = 0.76	M = 0.37 Mn = 2.92	0.14
Deflection	defl. L / 240 < 1.00		defl = 0.78578	2.62
Axial Force (D1-1)	Pu < 1.00 0.90AgFy	(kL/r)x =91 (kL/r)y =91	Pu = 0.16 Ag = 1.07 Fy = 46.00	0.00
Combined Forces (compress.) (H1-1b)	Pu + Mux Muy 2φPn φMnx φMny < 1.00	Cmx = 1.00 Cmy = 1.00 Pex = 37.29 Pey = 37.29	Mux = 0.37 Muy = 0.80 B1x = 1.00 B1y = 1.00	0.45

Date: 2/ 9/22 Prepared by:

Detailed Results Table for Beam 94 - 15

Moments: kips*foot, Forces: kips, Stresses: ksi, Section prop.: inch

X2 (Major axis) 70 Beam: 26 94, 72, 145, 15 6.00

CONSTRAINTS

DESIGN DATA

- Sections : Check -Kx = 1.00- Ky = 1.00

- Steel Grade: A500C - Allow. Slend.: 200 (compr.) 300 (tens.)

- Allowable Deflection : 1/240

- Tension Area Reduction Factor: 1.00

- Building type : Unbraced


Section: PIPE 2


0.67 ly =0.67in4 Zx = 0.76 Zy = 0.76in3 Area = 1.07lx = 2.37 t = 0.15inD =


1.33 Cw = 0.00 in 6

DESIGN COMBINATION = 1

M2 Moment Diagram







Max. AXIAL Force = 0.00 (tens.), -0.63 (compr.) Max. SHEAR Force =

SECTION CLASSIFICATION: *** COMPACT ***

Limiting Ratios: Compact Non-Compact

d/t = 15.46(Fy= 46.0 R = 0.013)45.0 71.7

DESIGN	EQUATION	FACTORS	VALUES	RESULT
M3 Moment (A-F1-1) without LTB	M 0.9Mn < 1.00	Z = 0.76	M = 0.19 Mn = 2.92	0.07
V3 Shear (F2-1)	Vu/(.9*Vn)<1.00 Vn=0.6*Fy*Av	Av = 0.64	Vu = 0.18 Vn = 17.81	0.01
M2 Moment (A-F1-1) without LTB	M 0.9Mn < 1.00	Z = 0.76	M = 0.47 Mn = 2.92	0.18

Prepared by: Date: 2/ 9/22

Detailed Results Table for Beam 94 - 15

Moments: kips*foot, Forces: kips, Stresses: ksi, Section prop.: inch

DESIGN	EQUATION	FACTORS	VALUES	RESULT
Deflection	defl. L / 240 < 1.00		defl = 0.45714	1.52
Axial Force (E2-1)	Pu < 1.00 0.85AgFcr	(kL/r)x =88 (kL/r)y =88 λc = 1.11	Pu = 0.63 Ag = 1.07 Fcr = 27.37	0.03
Combined Forces (compress.) (H1-1b)	Pu + Mux Muy 2φPn φMnx φMny < 1.00	Cmx = 1.00 Cmy = 1.00 Pex = 39.88 Pey = 39.88	Mux = 0.48 Muy = 0.20 B1x = 1.02 B1y = 1.02	0.27

Detailed Results Table for Beam 2 - 122

Moments: kips*foot, Forces: kips, Stresses: ksi, Section prop.: inch

X2 (Major axis) 3 Beam: 2, 136, 58, 118, 119, 120, -7.16 -121, 122 **DESIGN DATA**

CONSTRAINTS

- Sections : Check

- Steel Grade: A500B -Kx = 1.00- Ky = 1.00

- Allow. Slend.: 200 (compr.) 300 (tens.)

- Allowable Deflection: 1/240

- Tension Area Reduction Factor: 1.00

- Building type : Unbraced

INTERMEDIATE SUPPORTS

L =	1.17	4.71	5.12	5.50	5.92	6.29	6.71
LatTors.							
Compress.	Х	Х	Х	Х	Х	Х	Х

Section: TS 4x4x1/4

Ix = 8.22 Iy = 8.22in4 Zx = 4.97 Zy = 4.97in3 Area = 3.59


h = 4.00 b = 4.00in t = 0.25in

J = 13.50 Cw = 0.00 in 6

Prepared by: Date: 2/ 9/22

Detailed Results Table for Beam 2 - 122

Moments: kips*foot, Forces: kips, Stresses: ksi, Section prop.: inch




Moments at Intermediate Supports:

-1.05

0.17 -0.13 0.07 -0.23 -0.02 0.17

Max. AXIAL Force = 2.51 (tens.) Max. SHEAR Force = 0.92 M3 Moment Diagram



Max. AXIAL Force = 2.51 (tens.) Max. SHEAR Force = 1.29

SECTION CLASSIFICATION: *** COMPACT ***

Limiting Ratios: Compact Non-Compact d/t= 13.13 < 35.2 35.2

b/t= 13.13 < 35.2 35.2 55.2 b/t= 13.13 < 28.1 35.2

(Fy= 46.0 R = -0.015)

DESIGN	EQUATION	FACTORS	VALUES	RESULT
V2 Shear (F2-1)	Vu/(.9*Vn)<1.00 Vn=0.6*Fy*Av	Av = 1.79	Vu = 1.29 Vn = 49.60	0.03
M3 Moment (A-F1-1) without LTB	M 0.9Mn < 1.00	Z = 4.97	M = 3.44 Mn = 19.07	0.20
V3 Shear (F2-1)	Vu/(.9*Vn)<1.00 Vn=0.6*Fy*Av	Av = 1.79	Vu = 0.92 Vn = 49.60	0.02
M2 Moment (A-F1-1) without LTB	M 0.9Mn < 1.00	Z = 4.97	M = 1.06 Mn = 19.07	0.06
Deflection	defl. < 1.00		defl = 0.02900	0.08
Axial Force (D1-1)	Pu < 1.00 0.90AgFy	(kL/r)x =28 (kL/r)y =57	Pu = 2.51 Ag = 3.59 Fy = 46.00	0.02

Prepared by: Date: 2/ 9/22

Detailed Results Table for Beam 2 - 122

Moments: kips*foot, Forces: kips, Stresses: ksi, Section prop.: inch

DESIGN	EQUATION	FACTORS	VALUES	RESULT
Lateral Torsional Buckling	M < 1.00 0.9Mn Critical Segment from Segment End Momen		M = 1.06 Mn = 19.07 ange	0.06
Combined Forces (tension) (H1-1b)	Pu + Mux Muy 2¢Pn + + + + + + + + + + + + + + + + + + +		Mux = 1.06 Muy = 3.44	0.27

Detailed Results Table for Beam 140

Moments: kips*foot , Forces: kips , Stresses: ksi , Section prop.: inch

Beam: 122 X2 (Major axis)
140 6.95

CONSTRAINTS

DESIGN DATA

- Sections : Check - Kx = 1.00 - Ky = 1.00

- Steel Grade: A36 - Allow. Slend. : 200 (compr.) 300 (tens.)

Allowable Deflection : 1/240Tension Area Reduction Factor : 1.00

- Tension Area Reduction Factor . 1.0

- Building type : Unbraced

Connectors spacing = default (= 3.32)(welded)

Section: 2L 3x3x1/4

x = 2.49 ly = 5.56 in 4 Sx = 1.15 Sy = 1.75 in 3 Area = 2.88

 $h = 3.00 \ b = 6.37 in \ t = 0.25 \ ey = 2.16 in$

J = 0.06 Cw = 0.00 in 6

DESIGN COMBINATION = 4

Max. AXIAL Force = -3.12 (compr.) Max. SHEAR Force = 0.00

SECTION CLASSIFICATION: *** COMPACT ***

Limiting Ratios: Compact Non-Compact d/t= 12.10 < 12.8 12.8 b/t= 12.10 < 15.3 12.8

(Fy= 36.0 R = 0.030)

DESIGN	EQUATION	FACTORS	VALUES	RESULT
Axial Force (E2-1)	Pu 	(kL/r)x =90 (kL/r)y =66 λc = 1.01	Pu = 3.12 Ag = 2.88 Fcr = 23.54	0.05

Code: AISC-LRFD

South Glastonbury 3 CT Mount Analysis

Date: 2/ 9/22 Prepared by:

Detailed Results Table for Beam 1 - 73

Moments: kips*foot, Forces: kips, Stresses: ksi, Section prop.: inch



CONSTRAINTS

DESIGN DATA

- Sections : Check -Kx = 1.00- Ky = 1.00

- Steel Grade: A500C - Allow. Slend.: 200 (compr.) 300 (tens.)

- Allowable Deflection : 1/240

- Tension Area Reduction Factor: 1.00

- Building type : Unbraced


Section: PIPE 3


$$Ix = 3.02 Iy = 3.02in4 Zx = 2.33 Zy = 2.33in3 Area = 2.23$$

3.50 t = 0.22inD =6.03 Cw = 0.00 in 6

DESIGN COMBINATION = 1

M2 Moment Diagram





Max. AXIAL Force = 0.50 (tens.), -0.31 (compr.) Max. SHEAR Force = 0.85

SECTION CLASSIFICATION: *** COMPACT ***

Compact Non-Compact Limiting Ratios:

d/t = 16.1645.0 (Fy= 46.0 R = -0.005)

DESIGN	EQUATION	FACTORS	VALUES	RESULT
V2 Shear (F2-1)	Vu/(.9*Vn)<1.00 Vn=0.6*Fy*Av	Av = 1.34	Vu = 0.85 Vn = 36.95	0.03
M3 Moment (A-F1-1) without LTB	M 0.9Mn < 1.00	Z = 2.33	M = 0.56 Mn = 8.95	0.07
V3 Shear (F2-1)	Vu/(.9*Vn)<1.00 Vn=0.6*Fy*Av	Av = 1.34	Vu = 0.73 Vn = 36.95	0.02

Prepared by: Date: 2/ 9/22


Detailed Results Table for Beam 1 - 73

Moments: kips*foot, Forces: kips, Stresses: ksi, Section prop.: inch

DESIGN	EQUATION	FACTORS	VALUES	RESULT
M2 Moment (A-F1-1) without LTB	M 0.9Mn < 1.00	Z = 2.33	M = 1.07 Mn = 8.95	0.13
Deflection	defl. L / 240 < 1.00		defl = 0.33567	0.46
Axial Force (D1-1)	Pu < 1.00 0.90AgFy	(kL/r)x =60 (kL/r)y =60	Pu = 0.50 Ag = 2.23 Fy = 46.00	0.01
Combined Forces (compress.) (H1-1b)	Pu + Mux Muy 2φPn φMnx φMny < 1.00	Cmx = 1.00 Cmy = 1.00 Pex = 178.01 Pey = 178.01	Mux = 1.07 Muy = 0.56 B1x = 1.00 B1y = 1.00	0.20

Detailed Results Table for Beam 49 - 95

Moments: kips*foot, Forces: kips, Stresses: ksi, Section prop.: inch



CONSTRAINTS

DESIGN DATA

- Sections : Check - Kx = 1.00 - Ky = 1.00

- Steel Grade: A500C - Allow. Slend.: 200 (compr.) 300 (tens.)

- Allowable Deflection: 1/240

- Tension Area Reduction Factor: 1.00

- Building type : Unbraced

Section: PIPE 2

$$Ix = 0.67 \ Iy = 0.67 in 4 \ Zx = 0.76 \ Zy = 0.76 in 3 \ Area = 1.07 \ D = 2.37 \ t = 0.15 in$$

J = 1.33 Cw = 0.00 in 6

DESIGN COMBINATION = 1

M2 Moment Diagram




Max. AXIAL Force = 0.08 (tens.), -0.26 (compr.) Max. SHEAR Force = 0.35

Prepared by: Date: 2/ 9/22

Detailed Results Table for Beam 49 - 95

Moments: kips*foot , Forces: kips , Stresses: ksi , Section prop.: inch



Max. AXIAL Force = 0.08 (tens.), -0.26 (compr.) Max. SHEAR Force = 0.16

SECTION CLASSIFICATION: *** COMPACT ***

Limiting Ratios: Compact Non-Compact

d/t=15.46 < 45.0 71.7 (Fy= 46.0 R = 0.005)

DESIGN	EQUATION	FACTORS	VALUES	RESULT
V2 Shear (F2-1)	Vu/(.9*Vn)<1.00 Vn=0.6*Fy*Av	Av = 0.64	Vu = 0.16 Vn = 17.81	0.01
M3 Moment (A-F1-1) without LTB	M 0.9Mn < 1.00	Z = 0.76	M = 0.47 Mn = 2.92	0.18
V3 Shear (F2-1)	Vu/(.9*Vn)<1.00 Vn=0.6*Fy*Av	Av = 0.64	Vu = 0.35 Vn = 17.81	0.02
M2 Moment (A-F1-1) without LTB	M 0.9Mn < 1.00	Z = 0.76	M = 0.43 Mn = 2.92	0.16
Deflection	defl. L / 240 < 1.00		defl = 0.43143	0.60
Axial Force (E2-1)	Pu < 1.00 0.85AgFcr	(kL/r)x =192 (kL/r)y =192 λc = 2.43	Pu = 0.26 Ag = 1.07 Fcr = 6.83	0.04
Combined Forces (compress.) (H1-1b)	Pu + Mux Muy 2 pn pMnx pMny < 1.00	Cmx = 1.00 Cmy = 1.00 Pex = 8.38 Pey = 8.38	Mux = 0.45 Muy = 0.49 B1x = 1.03 B1y = 1.03	0.38