



Northeast Site Solutions  
Denise Sabo  
4 Angela's Way, Burlington CT 06013  
203-435-3640  
denise@northeastsitesolutions.com

February 15, 2023

Members of the Siting Council  
Connecticut Siting Council  
Ten Franklin Square  
New Britain, CT 06051

RE: Tower Share Application  
2172 Glasgo Road, Jewett City CT 06351  
Latitude: 41.537366  
Longitude: -71.873447  
Site #: CT10013-A\_BOBOS00051A\_SBA\_DISH

Dear Ms. Bachman:

This letter and attachments are submitted on behalf of Dish Wireless LLC. Dish Wireless LLC plans to install antennas and related equipment to the tower site located at 2172 Glasgo Road, Jewett City, Connecticut.

Dish Wireless LLC proposes to install three (3) 600/1900 MHz 5G antennas and six (6) RRUs, at the 125-foot level of the existing 195-foot tower, one (1) Fiber cable will also be installed. Dish Wireless LLC equipment cabinets will be placed within a 7' x 5' lease area within the fenced compound. Included are plans by B+T, dated January 26, 2023, Exhibit C. Also included is a structural analysis prepared by TES, stamped February 2, 2023, confirming that the existing tower is structurally capable of supporting the proposed equipment. Attached as Exhibit D. The facility was approved by the Town of Griswold, Zoning Permit approval no. ZP-2-99 received on September 30, 1998. Please see attached Exhibit A.

Please accept this letter as notification pursuant to Regulations of Connecticut State Agencies 16-50aa, of Dish Wireless LLC intent to share a telecommunications facility pursuant to R.C.S.A. 16-50j-88. In accordance with R.C.S.A., a copy of this letter is being sent to Dana Bennet, First Selectman, and Mario Tristany Jr., Town Planner for the Town of Griswold, as well as the property owner and the tower owner.

The planned modifications of the facility fall squarely within those activities explicitly provided for in R.C.S.A. 16-50j-89.

1. The proposed modification will not result in an increase in the height of the existing structure. The top of the existing tower is 195-feet and the Dish Wireless LLC antennas will be located at a center line height of 125-feet.
2. The proposed modifications will not result in an increase of the site boundary as depicted on the attached site plan.



3. The proposed modifications will not increase noise levels at the facility by six decibels or more, or to levels that exceed local and state criteria. The incremental effect of the proposed changes will be negligent.

4. The operation of the proposed antennas will not increase radio frequency emissions at the facility to a level at or above the Federal Communications Commission safety standard. The combined site operations will result in a total power density of 4.19% as evidenced by Exhibit F.

Connecticut General Statutes 16-50aa indicates that the Council must approve the shared use of a telecommunications facility provided it finds the shared use is technically, legally, environmentally, and economically feasible and meets public safety concerns. As demonstrated in this letter, Dish Wireless LLC respectfully submits that the shared use of this facility satisfies these criteria.

A. Technical Feasibility. The existing monopole has been deemed structurally capable of supporting Dish Wireless LLC proposed loading. The structural analysis is included as Exhibit D.

B. Legal Feasibility. As referenced above, C.G.S. 16-50aa has been authorized to issue orders approving the shared use of an existing tower such as this tower in Jewett City. Under the authority granted to the Council, an order of the Council approving the requested shared use would permit Dish Wireless LLC to obtain a building permit for the proposed installation. Further, a Letter of Authorization is included as Exhibit G, authorizing Dish Wireless LLC to file this application for shared use.

C. Environmental Feasibility. The proposed shared use of this facility would have a minimal environmental impact. The installation of Dish Wireless LLC equipment at the 125-foot level of the existing 195-foot tower would have an insignificant visual impact on the area around the tower. Dish Wireless LLC ground equipment would be installed within the existing facility compound. Dish Wireless LLC shared use would therefore not cause any significant alteration in the physical or environmental characteristics of the existing site. Additionally, as evidenced by Exhibit F, the proposed antennas would not increase radio frequency emissions to a level at or above the Federal Communications Commission safety standard.

D. Economic Feasibility. Dish Wireless LLC will be entering into an agreement with the owner of this facility to mutually agreeable terms. As previously mentioned, the Letter of Authorization has been provided by the owner to assist Dish Wireless LLC with this tower sharing application.

E. Public Safety Concerns. As discussed above, the tower is structurally capable of supporting Dish Wireless LLC proposed loading. Dish Wireless LLC is not aware of any public safety concerns relative to the proposed sharing of the existing tower. Dish Wireless LLC intentions of providing new and improved wireless service through the shared use of this facility is expected to enhance the safety and welfare of local residents and individuals traveling through Jewett City.

Sincerely,

*Denise Sabo*

Denise Sabo  
Mobile: 203-435-3640  
Fax: 413-521-0558  
Office: 4 Angela's Way, Burlington CT 06013  
Email: [denise@northeastsitesolutions.com](mailto:denise@northeastsitesolutions.com)



**NSS**

**NORTHEAST**  
SITE SOLUTIONS

*Turnkey Wireless Development*

Attachments

Cc: Dana Bennet, First Selectman  
Griswold Town Hall  
28 Main Street Jewett City, CT 06351

Mario Tristany Jr., Town Planner  
Griswold Town Hall  
28 Main Street Jewett City, CT 06351

Courtland & Bridget Kinnie – Property Owners  
2139 Glasgo Road Griswold, CT 06351

SBA - Tower Owner

# Exhibit A

## **Original Facility Approval**



# Town of Griswold

TOWN HALL, 32 SCHOOL STREET  
JEWETT CITY, CONNECTICUT 06351



070013;  
Griswold  
Glasgo

SELECTMEN	376-7061
ASSESSOR	376-7071
TAX COLLECTOR	376-7068
SOCIAL SERVICES	376-7067
PUBLIC HEALTH NURSES	376-7077

TOWN CLERK	376-7063
BUILDING INSPECTOR	376-7065
PLANNING & ZONING	376-7073
BOOKKEEPING	376-7074
SANITARIAN	376-7065

## PLANNING & ZONING COMMISSION

CERTIFIED MAIL: Z 307 862 713  
RETURN RECEIPT REQUESTED

September 30, 1998

Mr. Kenneth Thomas  
Wireless Solutions, Ltd.  
P.O. Box 284  
Old Lyme, CT 06371

Re: Wireless Solutions, Ltd., Zoning Permit Application (ZP 2-99)  
Gilliver Road, Griswold, CT

Dear Mr. Thomas:

The Griswold Planning & Zoning Commission, at it's Regular Meeting held on August 10, 1998, reviewed the above-referenced Zoning Permit application to construct a 195-foot communication tower off of Gilliver Road on property owned by The Kinnie Family Trust Wheeler.

Following a discussion on the matter, the commission voted unanimously in favor to approve the application as presented with the stipulation that it is approved as a co-location tower.

Should you have any questions regarding the above, please contact Mario at (860)376-7084.

Very truly yours,

*F. Clyde Seaman*  
F. Clyde Seaman  
Chairman

cc: Peter Zvingilas, Z.E.O.  
Cynthia Kata, Assessor

# Exhibit B

## Property Card



## Summary

**ParcelId** 5929  
**Account Number** K0211400  
**Location Address** 2172 GLASGO RD  
**Map-Block-Lot** 91 /162 /3A  
 Dev Lot. 7091  
**Use Class/Description** 4310 TEL REL TW  
**Assessing Neighborhood** 0060A  
**Census Tract** 7091  
**Acreage** 0.02  
**Utilities**



## Owner

KINNIE COURTLAND & BRIDGET  
 2139 GLASGO RD  
 GRISWOLD, CT 06351

## Current Appraised Value

	2017	2015
+ Building Value	\$0	\$0
+ XF Value	\$0	\$0
+ OB Value	\$88,100	\$79,300
+ Land Value	\$150,000	\$150,000
+ Special Land Value		
+ Total Appraised Value	\$238,100	\$229,300
+ Net Appraised Value	\$238,100	\$229,300
+ Current Assessment	\$166,670	\$160,510

## Assessment History

	2017	2015
+ Building Value	\$0	\$0
+ OB/Misc	\$61,670	\$55,510
+ Land	\$105,000	\$105,000
+ Total Assessment	\$166,670	\$160,510

## Land

Use	Class	Zoning	Area	Value
4310 TEL REL TW	I	R80	0.02 AC	\$150,000

## Out Buildings\Extra Features

Description	Sub Description	Area	Year Built	Value
CONC PAD/CELL SITES		100S.F.	2005	\$300
CELL TOWER		195HEIGHT	1999	\$87,800


## Sales History

Sales Date	Type of Document	Grantee	Vacant/Improved	Book/Page	Amount
12-27-1996		KINNIE COURTLAND & BRIDGET	Improved	176/ 903	\$0
12-27-1996		KINNIE ET AL	Improved	176/ 902	\$0
12-27-1996		KINNIE ET AL	Improved	176/ 901	\$0
12-27-1996		KINNIE ET AL	Improved	176/ 900	\$0
12-29-1995		KINNIE FAMILY TRUST II TOWER	Improved	169/ 238	\$0
12-29-1995		KINNIE FAMILY TRUST II	Improved	169/ 238	\$0
01-03-1994		KINNIE BYRON P JR & PAULINE CLAIRE	Improved	156/ 99	\$0
01-17-1964		KINNIE BYRON P JR & PAULINE C	Improved	00049/0085	\$0

**Permit Information**

Permit ID	Issue Date	Type	Description	Amount	Inspection Date	% Complete	Date Complete	Comments
42-19	04-14-2018	MN	MAINTENANCE	\$20,000		0		SWAP 6 EXISTONG CELL ANTENNAS WITH 6 NEWER TECHNOLOGY CELL ANTENNAS AND ASSOC EQUIPMENT AT EXISTING CELL SITE
253-15	05-20-2015	MN	SWAP 3 EXISTING CELL	\$15,000	7/23/2015 12:00:00 AM	100	07-23-2015	87-16 CC
134-06	10-20-2005	AD	CELL ANTENNA	\$40,000		100	12-13-2005	111-06 CC
201-98	02-23-1999	CM	195FT TOWER	\$43,000	8/23/1999 12:00:00 AM	100	08-23-1999	226-07 CC
280-20		MN	MAINTENANCE	\$0	12/13/2020 12:00:00 AM	100	12-13-2020	CC#-124-20. SWAP 6 EXISTING CELL ANTENNAS WITH 6 NEWER TECHNOLOGY CEL ANTENNAS AND ASSOC EQUIPMT AT EXISTING CELL SITE

**Sketch**



**Photos**





**No data available for the following modules:** Building Data, Building Data, Commercial Building.


The Town of Griswold Assessor makes every effort to produce the most accurate information possible. No warranties, expressed or implied are provided for the data herein, its use or interpretation. The assessment information is from the last certified tax roll. All other data is subject to change.

[User Privacy Policy](#)  
[GDPR Privacy Notice](#)


[Last Data Upload: 6/23/2021, 8:22:38 PM](#)

Developed by  
 Schneider  
GEOSPATIAL

Version 2.3.127



Overview



Legend

- Parcels
- Roads
- City Labels

Parcel ID	100013	Alternate ID	K0211401	Owner Address	KINNIE COURTLAND & BRIDGET
Sec/Twp/Rng	91-162-3	Class	S		2139 GLASGO RD
Property Address	2174 GLASGO RD	Acreage	62.7		GRISWOLD CT 06351
District	0050A				
Brief Tax Description	n/a				

(Note: Not to be used on legal documents)

Date created: 6/25/2019

Developed by Schneider GEOSPATIAL

Advised to use  
2174 Glasgo for  
map, per Town  
Assessor

# Exhibit C

## **Construction Drawings**



DISH Wireless L.L.C. SITE ID:

**BOBOS00051A**

DISH Wireless L.L.C. SITE ADDRESS:

**2172 GLASGO ROAD  
JEWETT CITY, CT 06351**

**SBA APPROVED**

**By sroth at 5:14:56 PM, 1/26/2023**

**SCOPE OF WORK**

THIS IS NOT AN ALL INCLUSIVE LIST. CONTRACTOR SHALL UTILIZE SPECIFIED EQUIPMENT PART OR ENGINEER APPROVED EQUIVALENT. CONTRACTOR SHALL VERIFY ALL NEEDED EQUIPMENT TO PROVIDE A FUNCTIONAL SITE. THE PROJECT GENERALLY CONSISTS OF THE FOLLOWING:

- TOWER SCOPE OF WORK:**
- INSTALL (3) PROPOSED PANEL ANTENNAS (1 PER SECTOR)
  - INSTALL (3) PROPOSED ANTENNA SECTOR FRAMES
  - INSTALL PROPOSED JUMPERS
  - INSTALL (6) PROPOSED RRUs (2 PER SECTOR)
  - INSTALL (1) PROPOSED OVER VOLTAGE PROTECTION DEVICE (OVP)
  - INSTALL (1) PROPOSED HYBRID CABLE

- GROUND SCOPE OF WORK:**
- INSTALL (1) PROPOSED METAL PLATFORM
  - INSTALL (1) PROPOSED ICE BRIDGE
  - INSTALL (1) PROPOSED PPC CABINET
  - INSTALL (1) PROPOSED EQUIPMENT CABINET
  - INSTALL (1) PROPOSED POWER CONDUIT
  - INSTALL (1) PROPOSED TELCO CONDUIT
  - INSTALL (1) PROPOSED TELCO-FIBER BOX
  - INSTALL (1) PROPOSED GPS UNIT
  - INSTALL (1) PROPOSED SAFETY SWITCH (IF REQUIRED)
  - INSTALL (1) PROPOSED FIBER NID (IF REQUIRED)
  - INSTALL (1) PROPOSED METER SOCKET

**SITE INFORMATION**

PROPERTY OWNER: KINNIE COURTLAND & BRIDGET  
ADDRESS: 2139 GLASGO RD  
GRISWOLD, CT 06351

TOWER TYPE: GUYED TOWER

TOWER CO SITE ID: CT10013-A

TOWER APP NUMBER: 174044

COUNTY: NEW LONDON

LATITUDE (NAD 83): 41° 32' 14.52" N  
41.53736633

LONGITUDE (NAD 83): 71° 52' 24.41" W  
-71.87344656

ZONING JURISDICTION: NEW LONDON COUNTY

ZONING DISTRICT: R20

PARCEL NUMBER: 100013

OCCUPANCY GROUP: U

CONSTRUCTION TYPE: II-B

POWER COMPANY: EVERSOURCE

TELEPHONE COMPANY: AT&T

**PROJECT DIRECTORY**

APPLICANT: DISH Wireless L.L.C.  
5701 SOUTH SANTA FE DRIVE  
LITTLETON, CO 80120

TOWER OWNER: SBA COMMUNICATAIONS CORP.  
8051 CONGRESS AVENUE  
BOCA RATON, FL 33487  
(800) 487-7483

SITE DESIGNER: B+T GROUP  
1717 S. BOULDER AVE, SUITE 300  
TULSA, OK 74119  
(918) 587-4630

SITE ACQUISITION: APRIL PARROTT  
april.parrott@dish.com

CONST. MANAGER: CHAD WILCOX  
chad.wilcox@dish.com

RF ENGINEER: DIPESH PARIKH  
DIPESH.PARIKH@DISH.COM




5701 SOUTH SANTA FE DRIVE  
LITTLETON, CO 80120



8051 CONGRESS AVENUE  
BOCA RATON, FL 33487



1717 S. BOULDER  
SUITE 300  
TULSA, OK 74119  
PH: (918) 587-4630  
www.btgrp.com



MTS ENGINEERING P.L.L.C.  
BER:2386985  
Expires 3/31/23

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: NGN CHECKED BY: RMC APPROVED BY: RMC

RFDS REV #: 1

**CONSTRUCTION DOCUMENTS**

SUBMITTALS		
REV	DATE	DESCRIPTION
0	2/28/22	ISSUED FOR CONSTRUCTION
1	6/22/22	ISSUED FOR CONSTRUCTION
2	1/26/23	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER  
**149453.001.01**

DISH Wireless L.L.C.  
PROJECT INFORMATION  
**BOBOS00051A**  
**2172 GLASGO ROAD**  
**JEWETT CITY, CT 06351**

SHEET TITLE  
**TITLE SHEET**


SHEET NUMBER  
**T-1**

**CONNECTICUT CODE OF COMPLIANCE**

ALL WORK SHALL BE PERFORMED AND MATERIALS INSTALLED IN ACCORDANCE WITH THE CURRENT EDITIONS OF THE FOLLOWING CODES AS ADOPTED BY THE LOCAL GOVERNING AUTHORITIES. NOTHING IN THESE PLANS IS TO BE CONSTRUED TO PERMIT WORK NOT CONFORMING TO THESE CODES

CODE TYPE	CODE
BUILDING	2022 CT STATE BUILDING CODE/2021 IBC W/ CT AMENDMENTS
MECHANICAL	2022 CT STATE BUILDING CODE/2021 IMC W/ CT AMENDMENTS
ELECTRICAL	2022 CT STATE BUILDING CODE/2020 NEC W/ CT AMENDMENTS

**SITE PHOTO**



**DIRECTIONS**

**DIRECTIONS FROM BRADLEY INTERNATIONAL AIRPORT:**

CONTINUE TO EAST GRANBY, HEAD NORTH TOWARD BRADLEY INTERNATIONAL AIRPORT, SLIGHT LEFT ONTO BRADLEY INTERNATIONAL AIRPORT, CONTINUE STRAIGHT, TAKE I-91 S, CT-2 E AND I-395 N TO GRISWOLD EXPY IN GRISWOLD. TAKE EXIT 22 FROM I-395 N, CONTINUE ONTO BRADLEY INTERNATIONAL AIRPORT CON CONTINUE ONTO CT-20 E/BRADLEY INTERNATIONAL AIRPORT CON, TAKE THE EXIT ONTO I-91 S TOWARD HARTFORD, USE THE LEFT LANE TO TAKE EXIT 30 TO MERGE WITH I-84 E, TAKE EXIT 55 FOR CT-2 E TOWARD NORWICH/NEW LONDON/I-84 E, CONTINUE ONTO CT-2 E, KEEP LEFT AT THE Y JUNCTION TO STAY ON CT-2 E, FOLLOW SIGNS FOR 2 E, TAKE EXIT 28N TO MERGE WITH I-395 N TOWARD PROVIDENCE, TAKE EXIT 22 FOR CT-164 TOWARD CT-138/PRESTON CITY/PACHAUG, FOLLOW CT-138 E AND CT-201 S TO GILLIVER RD, CONTINUE STRAIGHT ONTO GRISWOLD EXPY, TURN RIGHT ONTO CT-138 E, TURN RIGHT ONTO CT-201 S, TURN LEFT ONTO GILLIVER RD AND ARRIVE AT BOBOS00051A.

**VICINITY MAP**



**UNDERGROUND SERVICE ALERT CBYD 811**  
**UTILITY NOTIFICATION CENTER OF CONNECTICUT**  
(800) 922-4455  
**WWW.CBYD.COM**




CALL 2 WORKING DAYS UTILITY NOTIFICATION PRIOR TO CONSTRUCTION

**GENERAL NOTES**


THE FACILITY IS UNMANNED AND NOT FOR HUMAN HABITATION. A TECHNICIAN WILL VISIT THE SITE AS REQUIRED FOR ROUTINE MAINTENANCE. THE PROJECT WILL NOT RESULT IN ANY SIGNIFICANT DISTURBANCE OR EFFECT ON DRAINAGE, NO SANITARY SEWER SERVICE, POTABLE WATER, OR TRASH DISPOSAL IS REQUIRED AND NO COMMERCIAL SIGNAGE IS PROPOSED.

**11"x17" PLOT WILL BE HALF SCALE UNLESS OTHERWISE NOTED**

CONTRACTOR SHALL VERIFY ALL PLANS, EXISTING DIMENSIONS, AND CONDITIONS ON THE JOB SITE, AND SHALL IMMEDIATELY NOTIFY THE ENGINEER IN WRITING OF ANY DISCREPANCIES BEFORE PROCEEDING WITH THE WORK.



VICINITY MAP NOT TO SCALE



**LEGAL DESCRIPTION**

ALL THAT CERTAIN PARCEL OR LAND, WITH THE IMPROVEMENTS THEREON, SITUATED IN THE TOWN OF GRISWOLD, COUNTY OF NEW LONDON AND STATE OF CONNECTICUT, BEING SHOWN ON A CERTAIN SURVEY ENTITLED "PINNACLE TOWERS ACQUISITION SITE NO. 8073-003 TELECOMMUNICATIONS FACILITY 2172 GLASGOW ROAD GRISWOLD, CONNECTICUT" MADE BY JENNIFER MARVIS, L.S. ON FILE IN THE GRISWOLD LAND RECORDS, SAID PREMISES ARE MORE PARTICULARLY BOUNDED AND DESCRIBED AS FOLLOWS:

**LEASE PARCEL:**

BEGINNING AT THE CENTER OF THE EXISTING LATTICE TOWER HAVING CONNECTICUT STATE PLANE COORDINATES (NAD 1983) OF NORTH 757,740.89 EAST 1,230,873.83, SAID CENTER BEING NORTH 17 DEGREES 07 MINUTES 38 SECONDS EAST, AND 676.83 FEET DISTANT FROM A CAPPED IRON PIPE, SAID CENTER BEING THE RADIUS POINT OF A 150.00 FOOT RADIUS LEASE PARCEL;

THENCE PROCEEDING ALONG A RADIUS OF 150.00 FEET, A DELTA ANGLE OF 360 DEGREES 00 MINUTES 00 SECONDS AND AN ARC LENGTH OF 942.48 FEET AROUND SAID POINT OF THE EXISTING LATTICE TOWER;

TOGETHER WITH RIGHTS OF ACCESS OVER THE FOLLOW DESCRIBED PREMISES:

**ACCESS EASEMENT PARCEL 1**

A CERTAIN PIECE OR PARCEL OF LAND SITUATED IN THE TOWN OF GRISWOLD, COUNTY OF NEW LONDON AND STATE OF CONNECTICUT, BEING MORE PARTICULARLY BOUNDED AND DESCRIBED AS FOLLOWS:

BEGINNING AT A POINT ON THE APPROXIMATE SOUTHERLY STREET LINE OF GLASGOW ROAD SAID POINT BEING A POINT ON THE APPROXIMATE SOUTHERLY STREET LINE OF GLASGOW ROAD 150.00 FEET EAST 150.00 FEET FROM THE CENTER POINT OF SAID TOWER; THENCE PROCEEDING SOUTH 89 DEGREES 00 MINUTES 00 SECONDS EAST, 176.21 FEET TO A POINT;

THENCE RUNNING SOUTH 04 DEGREES 45 MINUTES 34 SECONDS WEST, 501.74 FEET TO A POINT;

THENCE RUNNING SOUTH 80 DEGREES 00 MINUTES 26 SECONDS EAST, 176.21 FEET TO A POINT;

THENCE RUNNING NORTH 17 DEGREES 07 MINUTES 38 SECONDS EAST, 501.74 FEET TO A POINT;

THENCE RUNNING SOUTH 49 DEGREES 23 MINUTES 48 SECONDS EAST, 48.22 FEET TO A POINT;

THENCE RUNNING SOUTH 28 DEGREES 45 MINUTES 38 SECONDS EAST, 41.17 FEET TO A POINT;

THENCE RUNNING ALONG SAID LEASE PARCEL ALONG A CURVE TO THE LEFT HAVING A RADIUS OF 150.00 FEET AND AN ARC LENGTH OF 942.48 FEET, A DELTA ANGLE OF 360 DEGREES 00 MINUTES 00 SECONDS AND AN ARC LENGTH OF 942.48 FEET AROUND SAID POINT OF THE EXISTING LATTICE TOWER;

THENCE RUNNING NORTH 08 DEGREES 40 MINUTES 26 SECONDS WEST, 47.86 FEET TO A POINT;

THENCE RUNNING NORTH 46 DEGREES 00 MINUTES 46 SECONDS WEST, 76.26 FEET TO A POINT;

THENCE RUNNING NORTH 17 DEGREES 07 MINUTES 38 SECONDS WEST, 501.74 FEET TO A POINT;

THENCE RUNNING NORTH 08 DEGREES 40 MINUTES 26 SECONDS WEST, 501.74 FEET TO A POINT;

THENCE RUNNING NORTH 04 DEGREES 45 MINUTES 34 SECONDS WEST, 501.74 FEET TO A POINT ON THE APPROXIMATE SOUTHERLY STREET LINE OF GLASGOW ROAD;

THENCE RUNNING NORTH 17 DEGREES 07 MINUTES 38 SECONDS EAST, 501.74 FEET ALONG SAID APPROXIMATE SOUTHERLY STREET LINE OF GLASGOW ROAD TO THE POINT OF BEGINNING.



**GENERAL NOTES**

1. FIELD SURVEY DATE: 04-12-07
2. VERTICAL DATUM: NAVD 83
3. HORIZONTAL DATUM: NAD 83
4. TOWER COORDINATES  
LATITUDE: 41 DEGREES 32 MINUTES 14.82 SECONDS  
LONGITUDE: 73 DEGREES 52 MINUTES 24.41 SECONDS  
ELEVATION: 402 FEET  
HEIGHT OF TOWER: 196.2'
5. PROPERTY OWNERS: BRIDGET KINNE AND COURTLAND KINNE
6. SITE NAME: GRISWOLD GLASGO
7. SITE NUMBER: CT10013-A
8. SITE ADDRESS: 2172 GLASGO ROAD, GRISWOLD, CT
9. JURISDICTION: TOWN OF GRISWOLD, NEW LONDON COUNTY, CT
10. THE MAJOR IMPROVEMENTS ON THIS PROPERTY AREA NOT LOCATED WITHIN THE 100 YEAR FLOOD HAZARD AREA AS SHOWN ON THE FIRM MAP FOR THE TOWN OF GRISWOLD, COUNTY OF NEW LONDON, CT, DATED 01-03-1998.

**ZONE: R-80**

**ADDRESS: 2172 GLASGO ROAD**

**DEED VOL. 196, PG. 238**

**ASSESSORS ID MAP #91, LOT #162**

**AREA OF LEASE PARCEL: 70885 SQUARE FEET**

**AREA OF ACCESS EASEMENT: 8908 SQUARE FEET**

**NOTES**

1. THIS SURVEY HAS BEEN PREPARED PURSUANT TO THE REGULATIONS OF CONNECTICUT STATE AGENCIES SECTION 20-300B-1 THROUGH 20-300B-20 AND THE STANDARDS FOR SURVEYS AND MAPS IN THE STATE OF CONNECTICUT AS ADOPTED BY THE CONNECTICUT ASSOCIATION OF LAND SURVEYORS, INC. ON SEPTEMBER 26, 1996.
- THIS SURVEY CONFORMS TO A CLASS A-2 HORIZONTAL ACCURACY.
- SURVEY TYPE: IMPROVEMENT LOCATION SURVEY AND EASEMENT MAP.
- BOUNDARY DETERMINATION CATEGORY: RESURVEY.
- THE BOUNDARY LINES INDICATED HEREON REFLECT THE INFORMATION CONTAINED IN THE BELOW NAMED MAP REFERENCES. THE BEARINGS INDICATED HEREON ARE BASED ON MAP REFERENCE 1.
- PROPERTY OWNERS: BRIDGET KINNE AND COURTLAND KINNE.
- LEASE PARCEL, ACCESS EASEMENT AND UTILITY EASEMENT ARE A PORTION OF LOT 1 AS SHOWN ON MAP REFERENCE 2.
- MAP REFERENCES:  
1. PINNACLE TOWERS ACQUISITION SITE NO. 8073-003 TELECOMMUNICATIONS FACILITY 2172 GLASGOW ROAD GRISWOLD, CONNECTICUT MADE BY JENNIFER MARVIS, L.S. ON FILE IN THE GRISWOLD LAND RECORDS.  
2. COMPANIONS PLAN MAP SHOWING EASEMENT TO BE GRANTED TO THE CONNECTICUT LIGHT AND POWER COMPANY ACROSS THE PROPERTY OF KINNE FAMILY TRUST CONNECTICUT RITE 201 AND GLASGO ROAD GRISWOLD, CT, PREPARED BY JOHN REDDIP, JR. & ASSOC. DATED MARCH 1998, MAP #1429 G.L.S.  
3. SUBDIVISION MAP OF THE PROPERTY OF MARY SKOLKOWSKI, FRANK DUTIA, CATHERINE BARRY, PREPARED FOR FRANK DUTIA ROAD #201 A.J.K. GLASGO ROAD, GRISWOLD, CONNECTICUT, PREPARED BY FRANK BERNARD F. STONE & ASSOC. DATED OCTOBER 1976, MAP #949 G.L.S.

**FLOTTABLE TITLE EXCEPTIONS LAWYERS TITLE INSURANCE CORPORATION # CRO24837L**

EXCEPTION NO.	INSTRUMENT	COMMENT
3	199-281 210-450	CLAP EASEMENT AS SHOWN ON SURVEY CLAP EASEMENT RELATED INSTRUMENT NOT INCLUDED

I HEREBY CERTIFY TO SBA TOWERS, INC. A FLORIDA LIMITED LIABILITY COMPANY, SEASMAN, PREWITT & OSELLO, PA AND LAWYERS TITLE INSURANCE CORPORATION, THE FOLLOWING:

THIS SURVEYOR HAS RECEIVED AND REVIEWED THAT CERTAIN TITLE COMMITMENT NO. CRO24837L ISSUED BY LAWYERS TITLE INSURANCE CORPORATION WITH AN EFFECTIVE DATE OF 03-13-07, WHICH PROPOSES TO FLOTTA THE LANDS DESCRIBED UNDER ITS SCHEDULE A.

THIS SURVEYOR KNOWS OF HIS OWN KNOWLEDGE THAT THE LANDS DESCRIBED UNDER SAID SCHEDULE A OF THE TITLE COMMITMENT CONTAIN OR INCLUDE THE LANDS DESCRIBED IN AND DEPICTED ON THIS SURVEY.

THIS SURVEYOR FURTHER KNOWS OF HIS OWN KNOWLEDGE THAT THE EASEMENTS OF RECORD AND IDENTIFIED UNDER SCHEDULE B-2 OF SAID TITLE COMMITMENT ENCLURE THE LANDS DESCRIBED ON THIS SURVEY, BUT SAID EASEMENTS WILL NOT INTERFERE WITH THE LOCATION OF THE PROPOSED INSURED LANDS, INCLUDING THE LEASED AREA AND ALL ACCESS, UTILITY AND GUY WIRE EASEMENT PARCELS.

*Paul J. Stowell*

PAUL J. STOWELL REGISTERED LAND SURVEYOR 70218 DATE: 04-12-07

NOT VALID WITHOUT THE ORIGINAL SIGNATURE AND SEAL OF THE STATE LICENSED REGISTERED LAND SURVEYOR.

**LEGEND**

--- CENTERLINE	----- CONCRETE BLOCK WALL	□ MONITORING WELL
--- VOID FENCE	----- CONCRETE BLOCK WALL	□ CHUTE/JUNCTION BOX
--- METAL FENCE	----- CONCRETE BLOCK WALL	□ POWER/LIGHT POLE
--- WOOD FENCE	----- CONCRETE BLOCK WALL	□ WATER METER
--- GUY ANCHOR	----- CONCRETE BLOCK WALL	□ CLAP METER
--- 3.5' GUY ANCHOR	----- CONCRETE BLOCK WALL	□ CLAP PND

I HEREBY CERTIFY THAT THIS SURVEY HAS BEEN PREPARED PURSUANT TO THE REGULATIONS OF CONNECTICUT STATE AGENCIES SECTION 20-300B-1 THROUGH 20-300B-20 AND THE STANDARDS FOR SURVEYS AND MAPS IN THE STATE OF CONNECTICUT AS ADOPTED BY THE CONNECTICUT ASSOCIATION OF LAND SURVEYORS, INC. ON SEPTEMBER 26, 1996.

NOT VALID WITHOUT THE ORIGINAL SIGNATURE AND SEAL OF A CONNECTICUT LICENSED SURVEYOR

*Paul J. Stowell* DATE: 06-01-07

PAUL J. STOWELL PROFESSIONAL LAND SURVEYOR CONNECTICUT LICENSE NO. 70218

**NOTES**

1. DATE OF BEARING OR DISTANCE OR BEARING.
2. LEGAL DESCRIPTION WRITTEN BY THIS SURVEYOR.
3. THE LEGAL DESCRIPTION WRITTEN HEREON IS NOT INTENDED TO BE A SUBSTITUTE FOR THE LEGAL DESCRIPTION OF RECORD.
4. UNLESS OTHERWISE NOTED OTHERWISE, ALL DISTANCES ARE IN FEET AND DECIMALS THEREOF.
5. ALL DISTANCES ARE SHOWN TO THE CENTERLINE UNLESS OTHERWISE NOTED OTHERWISE.
6. POINTS ARE TO BE SHOWN AS TO THE CENTERLINE OF ROAD, WALL OR TO THE FACE OF WALL.
7. IN SOME INSTANCES SURVEY REPRESENTATIONS HAVE BEEN CONSIDERED TO BE NEARLY ALTERNATE TO THE LEGAL DESCRIPTION WRITTEN HEREON. IN ALL CASES SURVEYOR SHALL CORRECT THE LEGAL DESCRIPTION TO REFLECT THE SURVEY REPRESENTATIONS.
8. THE BOUNDARIES AND DISTANCES SHOWN HEREON ARE IN ACCORDANCE WITH RECORD VALUES UNLESS OTHERWISE NOTED.
9. PARTY WALLS ARE SHOWN ON PROPERTY LINE AND ARE 0.7' WIDE UNLESS OTHERWISE NOTED.
10. SHOWN UNLESS OTHERWISE NOTED OTHERWISE.

**PAUL J. STOWELL**  
LAND SURVEYOR

171 WILCOX ROAD  
MILFORD CT, 06460  
PHONE: (203) 882-8995  
FAX: (203) 882-8998  
© 2007 ATLANTIC COAST SURVEYING

**IMPROVEMENT LOCATION SURVEY AND EASEMENT MAP**  
2172 GLASGO ROAD  
GRISWOLD, CT  
PREPARED FOR  
SBA TOWERS II LLC

\*Final CT10013-A; Griswold Glasgo

NOTES

1. CONTRACTOR SHALL FIELD VERIFY ALL PROPOSED UNDERGROUND UTILITY CONDUIT ROUTE.
2. ANTENNAS AND MOUNTS OMITTED FOR CLARITY.

NOTES

1. CONTRACTOR SHALL FIELD VERIFY ALL DIMENSIONS.
2. CONTRACTOR SHALL MAINTAIN A 10'-0" MINIMUM SEPARATION BETWEEN THE PROPOSED GPS UNIT, TRANSMITTING ANTENNAS AND EXISTING GPS UNITS.
3. ANTENNAS AND MOUNTS OMITTED FOR CLARITY.

**dish**  
wireless.

5701 SOUTH SANTA FE DRIVE  
LITTLETON, CO 80120



8051 CONGRESS AVENUE  
BOCA RATON, FL 33487

**B+T GRP**  
1717 S. BOULDER  
SUITE 300  
TULSA, OK 74119  
PH: (918) 587-4630  
www.btgrp.com



1/26/23

MTS ENGINEERING P.L.L.C.  
BER:2386985  
Expires 3/31/23

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: NGN  
CHECKED BY: RMC  
APPROVED BY: RMC

RFDS REV #: 1

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
0	2/28/22	ISSUED FOR CONSTRUCTION
1	6/22/22	ISSUED FOR CONSTRUCTION
2	1/26/23	ISSUED FOR CONSTRUCTION



A&E PROJECT NUMBER  
149453.001.01

DISH Wireless L.L.C.  
PROJECT INFORMATION  
BOBOS00051A  
2172 GLASGO ROAD  
JEWETT CITY, CT 06351


SHEET TITLE  
OVERALL AND ENLARGED  
SITE PLAN

SHEET NUMBER

**A-1**




ENLARGED SITE PLAN



2

OVERALL SITE PLAN



1


NOT USED

NO SCALE


3

**NOTES**


1. CONTRACTOR SHALL FIELD VERIFY ALL DIMENSIONS.
2. ANTENNA AND MW DISH SPECIFICATIONS REFER TO ANTENNA SCHEDULE AND TO FINAL CONSTRUCTION RFDS FOR ALL RF DETAILS
3. EXISTING EQUIPMENT AND FENCE OMITTED FOR CLARITY.




**PROPOSED NORTH ELEVATION**



**1**



**ANTENNA LAYOUT**



**2**

SECTOR	POSITION	ANTENNA						TRANSMISSION CABLE
		EXISTING OR PROPOSED	MANUFACTURER - MODEL NUMBER	TECHNOLOGY	SIZE (HxW)	AZIMUTH	RAD CENTER	FEED LINE TYPE AND LENGTH
ALPHA	A1	PROPOSED	COMMSCOPE - FFV-65B-R2	5G	72.0" x 19.6"	0°	125'-0"	(1) HIGH-CAPACITY HYBRID CABLE (155' LONG)
BETA	B1	PROPOSED	COMMSCOPE - FFV-65B-R2	5G	72.0" x 19.6"	120°	125'-0"	
GAMMA	G1	PROPOSED	COMMSCOPE - FFV-65B-R2	5G	72.0" x 19.6"	240°	125'-0"	

SECTOR	POSITION	RRH		NOTES
		MANUFACTURER - MODEL NUMBER	TECHNOLOGY	
ALPHA	A1	FUJITSU - TA08025-B605	5G	1. CONTRACTOR TO REFER TO FINAL CONSTRUCTION RFDS FOR ALL RF DETAILS. 2. ANTENNA AND RRH MODELS MAY CHANGE DUE TO EQUIPMENT AVAILABILITY. ALL EQUIPMENT CHANGES MUST BE APPROVED AND REMAIN IN COMPLIANCE WITH THE PROPOSED DESIGN AND STRUCTURAL ANALYSES.
	A1	FUJITSU - TA08025-B604	5G	
BETA	B1	FUJITSU - TA08025-B605	5G	
	B1	FUJITSU - TA08025-B604	5G	
GAMMA	G1	FUJITSU - TA08025-B605	5G	
	G1	FUJITSU - TA08025-B604	5G	

**ANTENNA SCHEDULE**

NO SCALE


**3**



5701 SOUTH SANTA FE DRIVE  
LITTLETON, CO 80120



8051 CONGRESS AVENUE  
BOCA RATON, FL 33487



MTS ENGINEERING P.L.L.C.  
BER:2386985  
Expires 3/31/23

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: NGN  
CHECKED BY: RMC  
APPROVED BY: RMC

RFDS REV #: 1

**CONSTRUCTION DOCUMENTS**

SUBMITTALS		
REV	DATE	DESCRIPTION
0	2/28/22	ISSUED FOR CONSTRUCTION
1	6/22/22	ISSUED FOR CONSTRUCTION
2	1/26/23	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER  
**149453.001.01**

DISH Wireless L.L.C. PROJECT INFORMATION  
**BOBOS00051A**  
2172 GLASGO ROAD  
JEWETT CITY, CT 06351

SHEET TITLE  
**ELEVATION, ANTENNA LAYOUT AND SCHEDULE**

SHEET NUMBER  
**A-2**



5701 SOUTH SANTA FE DRIVE  
LITTLETON, CO 80120



8051 CONGRESS AVENUE  
BOCA RATON, FL 33487



1717 S. BOULDER  
SUITE 300  
TULSA, OK 74119  
PH: (918) 587-4630  
www.btgrp.com



MTS ENGINEERING P.L.L.C.  
BER:2386985  
Expires 3/31/23

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: NGN CHECKED BY: RMC APPROVED BY: RMC

RFDS REV #: 1

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
0	2/28/22	ISSUED FOR CONSTRUCTION
1	6/22/22	ISSUED FOR CONSTRUCTION
2	1/26/23	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER  
149453.001.01

DISH Wireless L.L.C.  
PROJECT INFORMATION

BOBOS00051A  
2172 GLASGO ROAD  
JEWETT CITY, CT 06351




SHEET TITLE  
EQUIPMENT PLATFORM AND  
H-FRAME DETAILS

SHEET NUMBER


A-3

NOTES


1. CONTRACTOR TO BURY PLATFORM FEET WITH A MINIMUM OF 2" OF FILL PER EXISTING SITE SURFACE
2. WEED BARRIER FABRIC TO BE ADDED AT DISCRETION OF DISH Wireless L.L.C. CONSTRUCTION MANAGER AT TIME OF CONSTRUCTION. ONE SHEET 8'x8' INSTALLED UNDER ALL FOUR FEET OF THE PLATFORM (4 MIL BLACK PLASTIC)
3. EQUIPMENT CABINET OMITTED FOR CLARITY



5




PLATFORM EQUIPMENT PLAN



1

COMMSCOPE MTC4045LP 5X7 PLATFORM	
DIMENSIONS (HxWxD)	16"x84"x60"
TOTAL WEIGHT	423 LBS

NOTE:  
GC TO PROVIDE EXTENDED  
THREAD FOR PLATFORM IF  
REQUIRED HEIGHT EXCEEDS 17"




PLATFORM DETAIL

NO SCALE

2

COMMSCOPE MTC4045HFLD H-FRAME	
UNISTRUT/SUPPORT RAILS QTY	5
WEIGHT	59.74 lbs

NOTE:  
OR DISH Wireless L.L.C.  
APPROVED EQUIVALENT



H-FRAME DETAIL

NO SCALE

3





NOT USED

NO SCALE

4



ENERSYS HVAC 200005995	
DIMENSIONS (HxWxD)	73"x30"x32"
POWER SYSTEM	-48V ALPHA/600A
HVAC	600W
TOTAL WEIGHT (EMPTY)	371 lbs



BACK

SIDE






FRONT

CABINET DETAIL

NO SCALE

1

RAYCAP PPC RDIAC-2465-P-240-MTS	
ENCLOSURE DIMENSIONS (HxWxD)	39"x22.855"x12.593
WEIGHT:	80 lbs
OPERATING AC VOLTAGE	240/120 1 PHASE 3W+G



BACK

SIDE

FRONT




SIDE

POWER PROTECTION CABINET (PPC) DETAIL

NO SCALE

2

SQUARE D SAFETY SWITCHES D224NRB	
ENCLOSURE DIM (HxWxD)	29.25"x19.00"x8.50"
ENCLOSURE TYPE	NEMA 3R RAINPROOF
UL LISTED	FILE E-2875



SIDE




FRONT

SAFETY SWITCH DETAIL

NO SCALE

3

EATON METER SOCKET UNRRS213BEUSE	
METER SOCKET TYPE	RING
ENCLOSURE DIM (HxWxD)	16"x12"x6"
MAIN AMPERE RATING	200A
WEIGHT	18 LBS



SIDE

BACK





FRONT

METER SOCKET DETAIL

NO SCALE

4

ZAYO 5RU (LEFT SWING DOOR) FIBER NID ENCLOSURE	
DIMENSIONS (HxWxD)	36.1"x29"x12.9"
WEIGHT	85 lbs



BACK

SIDE




FRONT

FIBER NID ENCLOSURE DETAIL

NO SCALE

5

CHARLES CFIT-PF2020DSH1 FIBER TELCO ENCLOSURE	
ENCLOSURE DIMS (HxWxD)	20"x20"x9"
ENCLOSURE WEIGHT	20 lbs
MOUNTING	WALL
COMPLIANCE	TYPE 4



SIDE

BACK

FRONT



FIBER TELCO ENCLOSURE DETAIL

NO SCALE

6

COMMSCOPE WB-K110-B WAVEGUIDE BRIDGE KIT	
DIMENSIONS (HxL)	160"x10"
WEIGHT/ VOLUME	325.0 LBS
CABLE RUN (QTY)	12

INCLUDED PRODUCTS:	WB-T12-3 TRAPEZE KIT, 3 RUNGS
	WB-LB12-3 SUPPORT BRACKET
	MF-130 DIRECT BURIAL PIPE COLUMN, 13'-4"



PLAN


FRONT

SIDE

ICE BRIDGE DETAIL

NO SCALE


7



TYPICAL ICE BRIDGE CONCRETE PIER DETAIL

NO SCALE

8



HYBRID CABLE RUN

NO SCALE

9

**dish**  
wireless.


5701 SOUTH SANTA FE DRIVE  
LITTLETON, CO 80120



8051 CONGRESS AVENUE  
BOCA RATON, FL 33487



1717 S. BOULDER  
SUITE 300  
TULSA, OK 74119  
PH: (918) 587-4630  
www.btgrp.com



1/26/23

MTS ENGINEERING P.L.L.C.  
BER:2386985  
Expires 3/31/23

IT IS A VIOLATION OF LAW FOR ANY PERSON,  
UNLESS THEY ARE ACTING UNDER THE DIRECTION  
OF A LICENSED PROFESSIONAL ENGINEER,  
TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:

NGN RMC RMC

RFDS REV #: 1

### CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
0	2/28/22	ISSUED FOR CONSTRUCTION
1	6/22/22	ISSUED FOR CONSTRUCTION
2	1/26/23	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER  
149453.001.01

DISH Wireless L.L.C.  
PROJECT INFORMATION


BOBOS00051A  
2172 GLASGO ROAD  
JEWETT CITY, CT 06351

SHEET TITLE  
EQUIPMENT DETAILS


SHEET NUMBER

**A-4**


<b>PCTEL</b> <b>GPSGL-TMG-SPI-40NCB</b>	
DIMENSIONS (DIAxH) MM/INCH	81x184mm 3.2"x7.25"
WEIGHT W/ACCESSORIES	075 lbs
CONNECTOR	N-FEMALE
FREQUENCY RANGE	1590 ± 30MHz





TOP



BACK



SIDE



GPS DETAIL

NO SCALE

1

GPS MINIMUM SKY VIEW REQUIREMENTS

NO SCALE

2

CABLES UNLIMITED HYBRID CABLE  
MINIMUM BEND RADIUSES

NO SCALE

3

NOT USED

NO SCALE

4

NOT USED

NO SCALE

5

NOT USED

NO SCALE

6

NOT USED

NO SCALE

7

NOT USED

NO SCALE

8

NOT USED

NO SCALE

9

**dish**  
wireless.

5701 SOUTH SANTA FE DRIVE  
LITTLETON, CO 80120



8051 CONGRESS AVENUE  
BOCA RATON, FL 33487



1717 S. BOULDER  
SUITE 300  
TULSA, OK 74119  
PH: (918) 587-4630  
www.btgrp.com



MTS ENGINEERING P.L.L.C.  
BER:2386985  
Expires 3/31/23

IT IS A VIOLATION OF LAW FOR ANY PERSON,  
UNLESS THEY ARE ACTING UNDER THE DIRECTION  
OF A LICENSED PROFESSIONAL ENGINEER,  
TO ALTER THIS DOCUMENT.

DRAWN BY: NGN CHECKED BY: RMC APPROVED BY: RMC

RFDS REV #: 1

CONSTRUCTION  
DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
0	2/28/22	ISSUED FOR CONSTRUCTION
1	6/22/22	ISSUED FOR CONSTRUCTION
2	1/26/23	ISSUED FOR CONSTRUCTION





A&E PROJECT NUMBER  
149453.001.01

DISH Wireless L.L.C.  
PROJECT INFORMATION  
BOBOS00051A  
2172 GLASGO ROAD  
JEWETT CITY, CT 06351

SHEET TITLE  
EQUIPMENT DETAILS

SHEET NUMBER  
**A-5**

FUJITSU TRIPLE BAND TA08025-B605	
DIMENSIONS (HxWxD)	14.9"x15.7"x9"
WEIGHT	74.95 lbs
CONNECTOR TYPE	4.3-10 RF CONNECTOR
POWER SUPPLY	DC -58~-36V



BACK

SIDE





FRONT

RRH DETAIL

NO SCALE

1

FUJITSU DUAL BAND TA08025-B604	
DIMENSIONS (HxWxD)	14.9"x15.7"x7.8"
WEIGHT	63.9 lbs
CONNECTOR TYPE	4.3-10 RF CONNECTOR
POWER SUPPLY	DC -58~-36V



BACK

SIDE

FRONT



RRH DETAIL

NO SCALE

2

SABRE DOUBLE Z-BRACKET C10123155	
DIMENSIONS (HxWxD) (1 BRACKET)	5"x20"x1-13/16"
WEIGHT (FULL ASSEMBLY)	35.79 lbs
PACKAGE QUANTITY	4

#	DESCRIPTION
1	PLATE, CHANNEL BRACKET
2	RRH Z BRACKET, 3/16"
3	THREADED ROD ASSEMBLY 1/2"x12"





NOTE:  
OR DISH Wireless L.L.C.  
APPROVED EQUIVALENT

RRH MOUNT DETAIL

NO SCALE

3

COMMSCOPE FFVV-65B-R2	
DIMENSIONS (HxWxD)(MM/IN)	1826x498x197 72"x19.6"x7.8"
RF CONNECTOR INTERFACE	4.3-10 FEMALE
WEIGHT	70.8 lbs
WEIGHT WITH BRACKETS	98.1 lbs



BACK

SIDE




FRONT

ANTENNA DETAIL

NO SCALE

4

RAYCAP RDIC-9181-PF-48 DC SURGE PROTECTION (OVP)	
DIMENSIONS (HxWxD)	18.98"x14.39"x8.15"
WEIGHT	21.82 LBS



SIDE

BACK

FRONT

SURGE SUPPRESSION DETAIL (OVP)

NO SCALE

7


NOT USED

NO SCALE

5

JMA ANTENNA MOUNT BRACKET #91900318	
TOTAL WEIGHT (WITH BRACKETS)	18 lbs (8.18 Kg)
POLE DIAMETER RANGE	2.5" TO 4.5"

NOTE:  
KIT #91900318: TOP AND BOTTOM BRACKETS  
FOR 4-, 6-, AND 8-FOOT ANTENNAS  
ANTENNA BRACKET NOT PART OF KIT




NOTE:  
OR DISH Wireless L.L.C.  
APPROVED EQUIVALENT

ANTENNA BRACKET DETAIL

NO SCALE

6



EXISTING HORIZONTAL  
TOWER MEMBER

SITE PRO 1 ANGLE  
ADAPTER PART ADAP

BOLT IN BUTTERFLY HANGER  
SITE PRO 1 PART NO. BUG114  
FOR 1-1/4" Ø RF CABLE  
4'-0" O.C.

NOTE:  
PROVIDED & INSTALLED  
BY CONTRACTOR


HYBRID CABLE TOWER BRACE RUN

NO SCALE

8

COMMSCOPE V-FRAME MTC3975083	
FACE SIZE	8'-0"
WEIGHT	352.136 lbs

NOTE:  
OR DISH Wireless L.L.C.  
APPROVED EQUIVALENT



PLAN

FRONT

ANTENNA FRAME DETAIL

NO SCALE

9

**dish**  
wireless.


5701 SOUTH SANTA FE DRIVE  
LITTLETON, CO 80120



8051 CONGRESS AVENUE  
BOCA RATON, FL 33487



1717 S. BOULDER  
SUITE 300  
TULSA, OK 74119  
PH: (918) 587-4630  
www.btgrp.com



1/26/23

MTS ENGINEERING P.L.L.C.  
BER:2386985  
Expires 3/31/23

IT IS A VIOLATION OF LAW FOR ANY PERSON,  
UNLESS THEY ARE ACTING UNDER THE DIRECTION  
OF A LICENSED PROFESSIONAL ENGINEER,  
TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:  
NGN RMC RMC

RFDS REV #: 1

CONSTRUCTION  
DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
0	2/28/22	ISSUED FOR CONSTRUCTION
1	6/22/22	ISSUED FOR CONSTRUCTION
2	1/26/23	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER  
149453.001.01

DISH Wireless L.L.C.  
PROJECT INFORMATION  
BOBOS00051A  
2172 GLASGO ROAD  
JEWETT CITY, CT 06351

SHEET TITLE  
EQUIPMENT DETAILS

SHEET NUMBER


**A-6**

**NOTES**


1. CONTRACTOR SHALL FIELD VERIFY ALL PROPOSED UNDERGROUND UTILITY CONDUIT ROUTE.
2. ANTENNAS AND MOUNTS OMITTED FOR CLARITY.
3. THE GROUND LEASE PROVIDES BROAD/BLANKET UTILITY RIGHTS. "PWR" AND "FBR" PATH DEPICTED ON A-1 AND E-1 ARE BASED ON BEST AVAILABLE INFORMATION INCLUDING BUT NOT LIMITED TO FIELD VERIFICATION, PRIOR PROJECT DOCUMENTATION AND OTHER REAL PROPERTY RIGHTS DOCUMENTS. WHEN INSTALLING THE UTILITIES PLEASE LOCATE AND FOLLOW EXISTING PATH. IF EXISTING PATH IS NOT AN OPTION, PLEASE NOTIFY TOWER OWNER AS FURTHER COORDINATION MAY BE NEEDED.

DC POWER WIRING SHALL BE COLOR CODED AT EACH END FOR IDENTIFYING +24V AND -48V CONDUCTORS. RED MARKINGS SHALL IDENTIFY +24V AND BLUE MARKINGS SHALL IDENTIFY -48V.

1. CONTRACTOR SHALL INSPECT THE EXISTING CONDITIONS PRIOR TO SUBMITTING A BID. ANY QUESTIONS ARISING DURING THE BID PERIOD IN REGARDS TO THE CONTRACTOR'S FUNCTIONS, THE SCOPE OF WORK, OR ANY OTHER ISSUE RELATED TO THIS PROJECT SHALL BE BROUGHT UP DURING THE BID PERIOD WITH THE PROJECT MANAGER FOR CLARIFICATION, NOT AFTER THE CONTRACT HAS BEEN AWARDED.
2. ALL ELECTRICAL WORK SHALL BE DONE IN ACCORDANCE WITH CURRENT NATIONAL ELECTRICAL CODES AND ALL STATE AND LOCAL CODES, LAWS, AND ORDINANCES. PROVIDE ALL COMPONENTS AND WIRING SIZES AS REQUIRED TO MEET NEC STANDARDS.
3. LOCATION OF EQUIPMENT, CONDUIT AND DEVICES SHOWN ON THE DRAWINGS ARE APPROXIMATE AND SHALL BE COORDINATED WITH FIELD CONDITIONS PRIOR TO CONSTRUCTION.
4. CONDUIT ROUGH-IN SHALL BE COORDINATED WITH THE MECHANICAL EQUIPMENT TO AVOID LOCATION CONFLICTS. VERIFY WITH THE MECHANICAL EQUIPMENT CONTRACTOR AND COMPLY AS REQUIRED.
5. CONTRACTOR SHALL PROVIDE ALL BREAKERS, CONDUITS AND CIRCUITS AS REQUIRED FOR A COMPLETE SYSTEM.
6. CONTRACTOR SHALL PROVIDE PULL BOXES AND JUNCTION BOXES AS REQUIRED BY THE NEC ARTICLE 314.
7. CONTRACTOR SHALL PROVIDE ALL STRAIN RELIEF AND CABLE SUPPORTS FOR ALL CABLE ASSEMBLIES. INSTALLATION SHALL BE IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS AND RECOMMENDATIONS.
8. ALL DISCONNECTS AND CONTROLLING DEVICES SHALL BE PROVIDED WITH ENGRAVED PHENOLIC NAMEPLATES INDICATING EQUIPMENT CONTROLLED, BRANCH CIRCUITS INSTALLED ON, AND PANEL FIELD LOCATIONS FED FROM.
9. INSTALL AN EQUIPMENT GROUNDING CONDUCTOR IN ALL CONDUITS PER THE SPECIFICATIONS AND NEC 250. THE EQUIPMENT GROUNDING CONDUCTORS SHALL BE BONDED AT ALL JUNCTION BOXES, PULL BOXES, AND ALL DISCONNECT SWITCHES, AND EQUIPMENT CABINETS.
10. ALL NEW MATERIAL SHALL HAVE A U.L. LABEL.
11. PANEL SCHEDULE LOADING AND CIRCUIT ARRANGEMENTS REFLECT POST-CONSTRUCTION EQUIPMENT.
12. CONTRACTOR SHALL BE RESPONSIBLE FOR AS-BUILT PANEL SCHEDULE AND SITE DRAWINGS.
13. ALL TRENCHES IN COMPOUND TO BE HAND DUG



UTILITY ROUTE PLAN



1

ELECTRICAL NOTES

NO SCALE

2



5701 SOUTH SANTA FE DRIVE  
LITTLETON, CO 80120



8051 CONGRESS AVENUE  
BOCA RATON, FL 33487



1717 S. BOULDER  
SUITE 300  
TULSA, OK 74119  
PH: (918) 587-4630  
www.btgrp.com



1/26/23

MTS ENGINEERING P.L.L.C.  
BER:2386985  
Expires 3/31/23

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
NGN	RMC	RMC

RFDS REV #: 1

**CONSTRUCTION DOCUMENTS**

SUBMITTALS		
REV	DATE	DESCRIPTION
0	2/28/22	ISSUED FOR CONSTRUCTION
1	6/22/22	ISSUED FOR CONSTRUCTION
2	1/26/23	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER  
149453.001.01


DISH Wireless L.L.C.  
PROJECT INFORMATION

BOBOS00051A  
2172 GLASGO ROAD  
JEWETT CITY, CT 06351

SHEET TITLE  
ELECTRICAL/FIBER ROUTE  
PLAN AND NOTES

SHEET NUMBER  
**E-1**



CARLON EXPANSION FITTINGS				
COUPLING END PART#	MALE TERMINAL ADAPTER END PART#	SIZE	STD CTN QTY.	TRAVEL LENGTH
E945D	E945DX	1/2"	20	4"
E945E	E945EX	3/4"	15	4"
E945F	E945FX	1"	10	4"
E945G	E945GX	1 1/4"	5	4"
E945H	E945HX	1 1/2"	5	4"
E945J	E945JX	2"	15	8"
E945K	E945KX	2 1/2"	10	8"
E945L	E945LX	3"	10	8"
E945M	E945MX	3 1/2"	5	8"
E945N	E945NX	4"	5	8"
E945P	E945PX	5"	1	8"
E945R	E945RX	6"	1	8"



NOTE: CONTRACTOR TO INSTALL EXPANSION FITTING SLIP JOINT AT METER CENTER CONDUIT TERMINATION, AS PER LOCAL UTILITY POLICY, ORDINANCE AND/OR SPECIFIED REQUIREMENT.

**TRENCHING NOTES**

- CONTRACTOR SHALL RESTORE THE TRENCH TO ITS ORIGINAL CONDITIONS BY EITHER SEEDING OR SODDING GRASS AREAS, OR REPLACING ASPHALT OR CONCRETE AREAS TO ITS ORIGINAL CROSS SECTION.
- TRENCHING SAFETY; INCLUDING, BUT NOT LIMITED TO SOIL CLASSIFICATION, SLOPING, AND SHORING, SHALL BE GOVERNED BY THE CURRENT OSHA TRENCHING AND EXCAVATION SAFETY STANDARDS.
- ALL CONDUITS SHALL BE INSTALLED IN COMPLIANCE WITH THE CURRENT NATIONAL ELECTRIC CODE (NEC) OR AS REQUIRED BY THE LOCAL JURISDICTION, WHICHEVER IS THE MOST STRINGENT.



EXPANSION JOINT DETAIL


NO SCALE 1

TYPICAL UNDERGROUND TRENCH DETAIL

NO SCALE 2

DARK TELCO BOX – INTERIOR WIRING LAYOUT

NO SCALE 3



NOTE: FIBER PROVIDER WILL NEED TO PROVIDE AN ADDITIONAL 5FT UNISTRUT, 2 U-BOLTS WITH 4 NUTS, IN THE EVENT THE BRACKET SPACING DOESN'T LINE UP WITH CURRENT SPACING BELOW

LIT TELCO BOX – INTERIOR WIRING LAYOUT (OPTIONAL)

NO SCALE 4

NOT USED

NO SCALE 5

NOT USED

NO SCALE 6

NOT USED

NO SCALE 7

NOT USED

NO SCALE 8

NOT USED

NO SCALE 9



5701 SOUTH SANTA FE DRIVE  
LITTLETON, CO 80120



8051 CONGRESS AVENUE  
BOCA RATON, FL 33487



MTS ENGINEERING P.L.L.C.  
BER:2386985  
Expires 3/31/23

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: NGN CHECKED BY: RMC APPROVED BY: RMC

RFDS REV #: 1

CONSTRUCTION DOCUMENTS



REV	DATE	DESCRIPTION
0	2/28/22	ISSUED FOR CONSTRUCTION
1	6/22/22	ISSUED FOR CONSTRUCTION
2	1/26/23	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER  
149453.001.01

DISH Wireless L.L.C.  
PROJECT INFORMATION  
BOBOS00051A  
2172 GLASGO ROAD  
JEWETT CITY, CT 06351

SHEET TITLE  
ELECTRICAL  
DETAILS

SHEET NUMBER  
E-2



**NOTE:**  
BRANCH CIRCUIT WIRING SUPPLYING RECTIFIERS ARE TO BE RATED UL1015, 105°C, 600V, AND PVC INSULATED, IN THE SIZES SHOWN IN THE ONE-LINE DIAGRAM. CONTRACTOR MAY SUBSTITUTE UL1015 WIRE FOR THWN-2 FOR CONVENIENCE OUTLET BRANCH CIRCUIT.

**BREAKERS REQUIRED:**  
(2) 40A, 2P BREAKER - SQUARE D P/N:Q0240  
(1) 20A, 2P BREAKER - SQUARE D P/N:Q0220  
(1) 20A, 1P BREAKER - SQUARE D P/N:Q0120

**NOTES**

THE ENGINEER OF RECORD HAS PERFORMED ALL REQUIRED SHORT CIRCUIT CALCULATIONS AND THE AIC RATINGS FOR EACH DEVICE IS ADEQUATE TO PROTECT THE EQUIPMENT AND THE ELECTRICAL SYSTEM.

THE ENGINEER OF RECORD HAS PERFORMED ALL REQUIRED VOLTAGE DROP CALCULATIONS AND ALL BRANCH CIRCUIT AND FEEDERS COMPLY WITH THE NEC (LISTED ON T-1) ARTICLE 210.19(A)(1) FPN NO. 4.

CONDUIT SIZING: AT 40% FILL PER NEC CHAPTER 9, TABLE 4, ARTICLE 358.

0.5" CONDUIT - 0.122 SQ. IN AREA  
0.75" CONDUIT - 0.213 SQ. IN AREA  
2.0" CONDUIT - 1.316 SQ. IN AREA  
3.0" CONDUIT - 2.907 SQ. IN AREA

CABINET CONVENIENCE OUTLET CONDUCTORS (1 CONDUIT): USING THWN-2, CU.

#10 - 0.0211 SQ. IN X 2 = 0.0422 SQ. IN  
#10 - 0.0211 SQ. IN X 1 = 0.0211 SQ. IN <GROUND  
TOTAL = 0.0633 SQ. IN

0.5" EMT CONDUIT IS ADEQUATE TO HANDLE THE TOTAL OF (3) WIRES, INCLUDING GROUND WIRE, AS INDICATED ABOVE.

RECTIFIER CONDUCTORS (3 CONDUITS): USING UL1015, CU.

#8 - 0.0552 SQ. IN X 2 = 0.1103 SQ. IN  
#8 - 0.0131 SQ. IN X 1 = 0.0131 SQ. IN <BARE GROUND  
TOTAL = 0.1234 SQ. IN

0.75" EMT CONDUIT IS ADEQUATE TO HANDLE THE TOTAL OF (3) WIRES, INCLUDING GROUND WIRE, AS INDICATED ABOVE.

PPC FEED CONDUCTORS (1 CONDUIT): USING THWN, CU.

3/0 - 0.2679 SQ. IN X 3 = 0.8037 SQ. IN  
#6 - 0.0507 SQ. IN X 1 = 0.0507 SQ. IN <GROUND  
TOTAL = 0.8544 SQ. IN

3.0" SCH 40 PVC CONDUIT IS ADEQUATE TO HANDLE THE TOTAL OF (4) WIRES, INCLUDING GROUND WIRE, AS INDICATED ABOVE.

PPC ONE-LINE DIAGRAM

NO SCALE 1

PROPOSED ENERSYS PANEL SCHEDULE										
LOAD SERVED	VOLT AMPS (WATTS)		TRIP	CKT #	PHASE	CKT #	TRIP	VOLT AMPS (WATTS)		LOAD SERVED
	L1	L2						L1	L2	
PPC GFCI OUTLET	180	180	15A	1	A	2	40A	3840	3840	ENERSYS ALPHA CORDEX RECTIFIERS 1 & 2
ENERSYS GFCI OUTLET			15A	3	B	4				
--SPACE--				5	A	6	40A	3840	3840	ENERSYS ALPHA CORDEX RECTIFIER 3 & 4
--SPACE--				7	B	8				
--SPACE--				9	A	10	20A	1920	1920	ENERSYS ALPHA CORDEX RECTIFIER 5
--SPACE--				11	B	12				
--SPACE--				13	A	14				--SPACE--
--SPACE--				15	B	16				--SPACE--
--SPACE--				17	A	18				--SPACE--
--SPACE--				19	B	20				--SPACE--
--SPACE--				21	A	22				--SPACE--
--SPACE--				23	B	24				--SPACE--
VOLTAGE AMPS	180	180						9500	9500	
200A MCB, 1 $\phi$ , 24 SPACE, 120/240V				L1	L2					
MB RATING: 65,000 AIC				9680	9680					
				81	81					
				81						
				102						

PANEL SCHEDULE

NO SCALE 2

NOT USED


NO SCALE 3



5701 SOUTH SANTA FE DRIVE  
LITTLETON, CO 80120



8051 CONGRESS AVENUE  
BOCA RATON, FL 33487



MTS ENGINEERING P.L.L.C.  
BER:2386985  
Expires 3/31/23

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:  
NGN RMC RMC

RFDS REV #: 1

CONSTRUCTION DOCUMENTS


SUBMITTALS		
REV	DATE	DESCRIPTION
0	2/28/22	ISSUED FOR CONSTRUCTION
1	6/22/22	ISSUED FOR CONSTRUCTION
2	1/26/23	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER  
149453.001.01

DISH Wireless L.L.C.  
PROJECT INFORMATION  
BOBOS00051A  
2172 GLASGO ROAD  
JEWETT CITY, CT 06351


SHEET TITLE  
ELECTRICAL ONE-LINE, FAULT  
CALCS & PANEL SCHEDULE

SHEET NUMBER  
E-3



TYPICAL EQUIPMENT GROUNDING PLAN

NO SCALE 1



TYPICAL ANTENNA GROUNDING PLAN

NO SCALE 2

- EXOTHERMIC CONNECTION
- MECHANICAL CONNECTION
- ▬ GROUND BUS BAR
- GROUND ROD
- TEST GROUND ROD WITH INSPECTION SLEEVE
- #6 AWG STRANDED & INSULATED
- - - #2 AWG SOLID COPPER TINNED
- #2 AWG STRANDED & INSULATED
- ▲ BUSS BAR INSULATOR

GROUNDING LEGEND

1. GROUNDING IS SHOWN DIAGRAMMATICALLY ONLY.
2. CONTRACTOR SHALL GROUND ALL EQUIPMENT AS A COMPLETE SYSTEM. GROUNDING SHALL BE IN COMPLIANCE WITH NEC SECTION 250 AND DISH Wireless L.L.C. GROUNDING AND BONDING REQUIREMENTS AND MANUFACTURER'S SPECIFICATIONS.
3. ALL GROUND CONDUCTORS SHALL BE COPPER; NO ALUMINUM CONDUCTORS SHALL BE USED.

GROUNDING KEY NOTES

- (A) EXTERIOR GROUND RING: #2 AWG SOLID COPPER, BURIED AT A DEPTH OF AT LEAST 30 INCHES BELOW GRADE, OR 6 INCHES BELOW THE FROST LINE AND APPROXIMATELY 24 INCHES FROM THE EXTERIOR WALL OR FOOTING.
  - (B) TOWER GROUND RING: THE GROUND RING SYSTEM SHALL BE INSTALLED AROUND AN ANTENNA TOWER'S LEGS, AND/OR GUY ANCHORS. WHERE SEPARATE SYSTEMS HAVE BEEN PROVIDED FOR THE TOWER AND THE BUILDING, AT LEAST TWO BONDS SHALL BE MADE BETWEEN THE TOWER RING GROUND SYSTEM AND THE BUILDING RING GROUND SYSTEM USING MINIMUM #2 AWG SOLID COPPER CONDUCTORS.
  - (C) INTERIOR GROUND RING: #2 AWG STRANDED GREEN INSULATED COPPER CONDUCTOR EXTENDED AROUND THE PERIMETER OF THE EQUIPMENT AREA. ALL NON-TELECOMMUNICATIONS RELATED METALLIC OBJECTS FOUND WITHIN A SITE SHALL BE GROUNDED TO THE INTERIOR GROUND RING WITH #6 AWG STRANDED GREEN INSULATED CONDUCTOR.
  - (D) BOND TO INTERIOR GROUND RING: #2 AWG SOLID TINNED COPPER WIRE PRIMARY BONDS SHALL BE PROVIDED AT LEAST AT FOUR POINTS ON THE INTERIOR GROUND RING, LOCATED AT THE CORNERS OF THE BUILDING.
  - (E) GROUND ROD: UL LISTED COPPER CLAD STEEL. MINIMUM 1/2" DIAMETER BY EIGHT FEET LONG. GROUND RODS SHALL BE INSTALLED WITH INSPECTION SLEEVES. GROUND RODS SHALL BE DRIVEN TO THE DEPTH OF GROUND RING CONDUCTOR.
  - (F) CELL REFERENCE GROUND BAR: POINT OF GROUND REFERENCE FOR ALL COMMUNICATIONS EQUIPMENT FRAMES. ALL BONDS ARE MADE WITH #2 AWG UNLESS NOTED OTHERWISE STRANDED GREEN INSULATED COPPER CONDUCTORS. BOND TO GROUND RING WITH (2) #2 SOLID TINNED COPPER CONDUCTORS.
  - (G) HATCH PLATE GROUND BAR: BOND TO THE INTERIOR GROUND RING WITH TWO #2 AWG STRANDED GREEN INSULATED COPPER CONDUCTORS. WHEN A HATCH-PLATE AND A CELL REFERENCE GROUND BAR ARE BOTH PRESENT, THE CRGB MUST BE CONNECTED TO THE HATCH-PLATE AND TO THE INTERIOR GROUND RING USING (2) TWO #2 AWG STRANDED GREEN INSULATED COPPER CONDUCTORS EACH.
  - (H) EXTERIOR CABLE ENTRY PORT GROUND BARS: LOCATED AT THE ENTRANCE TO THE CELL SITE BUILDING. BOND TO GROUND RING WITH A #2 AWG SOLID TINNED COPPER CONDUCTORS WITH AN EXOTHERMIC WELD AND INSPECTION SLEEVE.
  - (I) TELCO GROUND BAR: BOND TO BOTH CELL REFERENCE GROUND BAR OR EXTERIOR GROUND RING.
  - (J) FRAME BONDING: THE BONDING POINT FOR TELECOM EQUIPMENT FRAMES SHALL BE THE GROUND BUS THAT IS NOT ISOLATED FROM THE EQUIPMENTS METAL FRAMEWORK.
  - (K) INTERIOR UNIT BONDS: METAL FRAMES, CABINETS AND INDIVIDUAL METALLIC UNITS LOCATED WITH THE AREA OF THE INTERIOR GROUND RING REQUIRE A #6 AWG STRANDED GREEN INSULATED COPPER BOND TO THE INTERIOR GROUND RING.
  - (L) FENCE AND GATE GROUNDING: METAL FENCES WITHIN 7 FEET OF THE EXTERIOR GROUND RING OR OBJECTS BONDED TO THE EXTERIOR GROUND RING SHALL BE BONDED TO THE GROUND RING WITH A #2 AWG SOLID TINNED COPPER CONDUCTOR AT AN INTERVAL NOT EXCEEDING 25 FEET. BONDS SHALL BE MADE AT EACH GATE POST AND ACROSS GATE OPENINGS.
  - (M) EXTERIOR UNIT BONDS: METALLIC OBJECTS, EXTERNAL TO OR MOUNTED TO THE BUILDING, SHALL BE BONDED TO THE EXTERIOR GROUND RING. USING #2 TINNED SOLID COPPER WIRE
  - (N) ICE BRIDGE SUPPORTS: EACH ICE BRIDGE LEG SHALL BE BONDED TO THE GROUND RING WITH #2 AWG BARE TINNED COPPER CONDUCTOR. PROVIDE EXOTHERMIC WELDS AT BOTH THE ICE BRIDGE LEG AND BURIED GROUND RING.
  - (O) DURING ALL DC POWER SYSTEM CHANGES INCLUDING DC SYSTEM CHANGE OUTS, RECTIFIER REPLACEMENTS OR ADDITIONS, BREAKER DISTRIBUTION CHANGES, BATTERY ADDITIONS, BATTERY REPLACEMENTS AND INSTALLATIONS OR CHANGES TO DC CONVERTER SYSTEMS IT SHALL BE REQUIRED THAT SERVICE CONTRACTORS VERIFY ALL DC POWER SYSTEMS ARE EQUIPPED WITH A MASTER DC SYSTEM RETURN GROUND CONDUCTOR FROM THE DC POWER SYSTEM COMMON RETURN BUS DIRECTLY CONNECTED TO THE CELL SITE REFERENCE GROUND BAR
  - (P) TOWER TOP COLLECTOR BUSS BAR IS TO BE MECHANICALLY BONDED TO TOWER STEEL.
- REFER TO DISH Wireless L.L.C. GROUNDING NOTES.

GROUNDING KEY NOTES

NO SCALE 3




5701 SOUTH SANTA FE DRIVE  
LITTLETON, CO 80120



8051 CONGRESS AVENUE  
BOCA RATON, FL 33487



1717 S. BOULDER  
SUITE 300  
TULSA, OK 74119  
PH: (918) 587-4630  
www.btgrp.com



MTS ENGINEERING P.L.L.C.  
BER:2386985  
Expires 3/31/23

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: NGN  
CHECKED BY: RMC  
APPROVED BY: RMC

RFDS REV #: 1

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
0	2/28/22	ISSUED FOR CONSTRUCTION
1	6/22/22	ISSUED FOR CONSTRUCTION
2	1/26/23	ISSUED FOR CONSTRUCTION


A&E PROJECT NUMBER  
149453.001.01

DISH Wireless L.L.C.  
PROJECT INFORMATION  
BOBOS00051A  
2172 GLASGO ROAD  
JEWETT CITY, CT 06351

SHEET TITLE  
GROUNDING PLANS AND NOTES


SHEET NUMBER  
G-1

**NOTES**  
EQUIPMENT CABINET OMITTED FOR CLARITY




**H-FRAME GROUNDING DETAIL**

NO SCALE 1




**TYPICAL GPS UNIT GROUNDING**

NO SCALE 2




**OUTDOOR CABINET GROUNDING**

NO SCALE 3




**TRANSITIONING GROUND DETAIL**

NO SCALE 4



**TYPICAL TEST GROUND ROD WITH INSPECTION SLEEVE**

NO SCALE 5



**TYPICAL GROUND RING TRENCH**


NO SCALE 6



5701 SOUTH SANTA FE DRIVE  
LITTLETON, CO 80120



8051 CONGRESS AVENUE  
BOCA RATON, FL 33487



MTS ENGINEERING P.L.L.C.  
BER:2386985  
Expires 3/31/23

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: NGN CHECKED BY: RMC APPROVED BY: RMC

RFDS REV #: 1

**CONSTRUCTION DOCUMENTS**

SUBMITTALS		
REV	DATE	DESCRIPTION
0	2/28/22	ISSUED FOR CONSTRUCTION
1	6/22/22	ISSUED FOR CONSTRUCTION
2	1/26/23	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER  
**149453.001.01**



DISH Wireless L.L.C.  
PROJECT INFORMATION  
**BOBOS00051A**  
2172 GLASGO ROAD  
JEWETT CITY, CT 06351

SHEET TITLE  
**GROUNDING DETAILS**

SHEET NUMBER  
**G-2**



1. EXOTHERMIC WELD (2) TWO, #2 AWG BARE TINNED SOLID COPPER CONDUCTORS TO GROUND BAR. ROUTE CONDUCTORS TO BURIED GROUND RING AND PROVIDE PARALLEL EXOTHERMIC WELD.
2. ALL EXTERIOR GROUNDING HARDWARE SHALL BE STAINLESS STEEL 3/8" DIAMETER OR LARGER. ALL HARDWARE 18-8 STAINLESS STEEL INCLUDING LOCK WASHERS, COAT ALL SURFACES WITH AN ANTI-OXIDANT COMPOUND BEFORE MATING.
3. FOR GROUND BOND TO STEEL ONLY: COAT ALL SURFACES WITH AN ANTI-OXIDANT COMPOUND BEFORE MATING.
4. DO NOT INSTALL CABLE GROUNDING KIT AT A BEND AND ALWAYS DIRECT GROUND CONDUCTOR DOWN TO GROUNDING BUS.
5. NUT & WASHER SHALL BE PLACED ON THE FRONT SIDE OF THE GROUND BAR AND BOLTED ON THE BACK SIDE.
6. ALL GROUNDING PARTS AND EQUIPMENT TO BE SUPPLIED AND INSTALLED BY CONTRACTOR.
7. THE CONTRACTOR SHALL BE RESPONSIBLE FOR INSTALLING ADDITIONAL GROUND BAR AS REQUIRED.
8. ENSURE THE WIRE INSULATION TERMINATION IS WITHIN 1/8" OF THE BARREL (NO SHINERS).



TYPICAL GROUNDING NOTES


NO SCALE 1

TYPICAL EXTERIOR TWO HOLE LUG

NO SCALE 2

TYPICAL INTERIOR TWO HOLE LUG

NO SCALE 3



LUG DETAIL

NO SCALE 4

NOT USED

NO SCALE 5

NOT USED

NO SCALE 6

NOT USED

NO SCALE 7

NOT USED

NO SCALE 8

NOT USED



NO SCALE 9



5701 SOUTH SANTA FE DRIVE  
LITTLETON, CO 80120



8051 CONGRESS AVENUE  
BOCA RATON, FL 33487



MTS ENGINEERING P.L.L.C.  
BER:2386985  
Expires 3/31/23

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: NGN CHECKED BY: RMC APPROVED BY: RMC

RFDS REV #: 1

CONSTRUCTION DOCUMENTS

REV	DATE	DESCRIPTION
0	2/28/22	ISSUED FOR CONSTRUCTION
1	6/22/22	ISSUED FOR CONSTRUCTION
2	1/26/23	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER  
149453.001.01

DISH Wireless L.L.C.  
PROJECT INFORMATION  
BOBOS00051A  
2172 GLASGO ROAD  
JEWETT CITY, CT 06351

SHEET TITLE  
GROUNDING DETAILS

SHEET NUMBER  
G-3

HYBRID/DISCREET CABLES												3/4" TAPE WIDTHS WITH 3/4" SPACING															
<p>LOW-BAND RRH (600 MHz N71 BASEBAND) + (850 MHz N26 BAND) + (700 MHz N29 BAND) - OPTIONAL PER MARKET</p> <p>ADD FREQUENCY COLOR TO SECTOR BAND (CBRS WILL USE YELLOW BAND)</p>												ALPHA RRH				BETA RRH				GAMMA RRH							
PORT 1 + SLANT		PORT 2 - SLANT		PORT 3 + SLANT		PORT 4 - SLANT		PORT 1 + SLANT		PORT 2 - SLANT		PORT 3 + SLANT		PORT 4 - SLANT		PORT 1 + SLANT		PORT 2 - SLANT		PORT 3 + SLANT		PORT 4 - SLANT					
RED		RED		RED		RED		BLUE		BLUE		BLUE		BLUE		GREEN		GREEN		GREEN		GREEN					
ORANGE		ORANGE		RED		RED		ORANGE		ORANGE		BLUE		BLUE		ORANGE		ORANGE		GREEN		GREEN					
		WHITE (-) PORT		ORANGE		ORANGE				WHITE (-) PORT		ORANGE		ORANGE				WHITE (-) PORT		ORANGE		ORANGE					
				WHITE (-) PORT		WHITE (-) PORT				WHITE (-) PORT		ORANGE		ORANGE				WHITE (-) PORT		ORANGE		ORANGE					
<p>MID-BAND RRH (AWS BANDS N66+N70)</p> <p>ADD FREQUENCY COLOR TO SECTOR BAND (CBRS WILL USE YELLOW BANDS)</p>												RED				BLUE				GREEN							
PURPLE		PURPLE		RED		RED		PURPLE		PURPLE		BLUE		BLUE		PURPLE		PURPLE		GREEN		GREEN					
		WHITE (-) PORT		PURPLE		PURPLE				WHITE (-) PORT		PURPLE		PURPLE				WHITE (-) PORT		PURPLE		PURPLE					
				WHITE (-) PORT		WHITE (-) PORT				WHITE (-) PORT		PURPLE		PURPLE				WHITE (-) PORT		PURPLE		PURPLE					
<p>HYBRID/DISCREET CABLES</p> <p>INCLUDE SECTOR BANDS BEING SUPPORTED ALONG WITH FREQUENCY BANDS.</p> <p>EXAMPLE 1 - HYBRID, OR DISCREET, SUPPORTS ALL SECTORS, BOTH LOW-BANDS AND MID-BANDS.</p> <p>EXAMPLE 2 - HYBRID, OR DISCREET, SUPPORTS CBRS ONLY, ALL SECTORS.</p> <p>EXAMPLE 3 - MAIN COAX WITH GROUND MOUNTED RRHs.</p>												EXAMPLE 1		EXAMPLE 2		EXAMPLE 3 COAX #1 (ALPHA)		EXAMPLE 3 COAX #2 (ALPHA)		CONTRACTOR TO REFER TO FINAL CONSTRUCTION RFDS FOR ALL RD DETAILS. FINAL RFDS IS IN NEXSYSONE.							
RED		RED		RED		RED		RED																			
BLUE		BLUE		GREEN																							
GREEN		GREEN		ORANGE		PURPLE																					
ORANGE		ORANGE		PURPLE																							
PURPLE		PURPLE		YELLOW																							
<p>FIBER JUMPERS TO RRHs</p> <p>LOW-BAND HHR FIBER CABLES HAVE SECTOR STRIPE ONLY.</p>												LOW BAND RRH		MID BAND RRH		LOW BAND RRH		MID BAND RRH		LOW BAND RRH		MID BAND RRH					
RED		RED		RED		BLUE		BLUE		GREEN		GREEN															
ORANGE		ORANGE		PURPLE		ORANGE		PURPLE		ORANGE		PURPLE															
<p>POWER CABLES TO RRHs</p> <p>LOW-BAND RRH POWER CABLES HAVE SECTOR STRIPE ONLY</p>												LOW BAND RRH		MID BAND RRH		LOW BAND RRH		MID BAND RRH		LOW BAND RRH		MID BAND RRH					
RED		RED		RED		BLUE		BLUE		GREEN		GREEN															
ORANGE		ORANGE		PURPLE		ORANGE		PURPLE		ORANGE		PURPLE															
<p>RET MOTORS AT ANTENNAS</p> <p>RET CONTROL IS HANDLED BY THE MID-BAND RRH WHEN ONE SET OF RET PORTS EXIST ON ANTENNA.</p> <p>SEPARATE RET CABLES ARE USED WHEN ANTENNA PORTS PROVIDE INPUTS FOR BOTH LOW AND MID BANDS.</p>												ANTENNA 1 MID BAND		ANTENNA 1 LOW BAND		ANTENNA 1 MID BAND		ANTENNA 1 LOW BAND		ANTENNA 1 MID BAND		ANTENNA 1 LOW BAND					
IN		IN		IN		IN		IN		IN																	
RED		RED		BLUE		BLUE		GREEN		GREEN																	
PURPLE		ORANGE		PURPLE		ORANGE		PURPLE		ORANGE																	
<p>MICROWAVE RADIO LINKS</p> <p>LINKS WILL HAVE A 1.5-2 INCH WHITE WRAP WITH THE AZIMUTH COLOR OVERLAPPING IN THE MIDDLE.</p> <p>ADD ADDITIONAL SECTOR COLOR BANDS FOR EACH ADDITIONAL MW RADIO.</p> <p>MICROWAVE CABLES WILL REQUIRE P-TOUCH LABELS INSIDE THE CABINET TO IDENTIFY THE LOCAL AND REMOTE SITE ID'S.</p>												FORWARD AZIMUTH OF 0-120 DEGREES		FORWARD AZIMUTH OF 120-240 DEGREES		FORWARD AZIMUTH OF 240-359 DEGREES											
PRIMARY		SECONDARY		PRIMARY		SECONDARY		PRIMARY		SECONDARY																	
WHITE		WHITE		WHITE		WHITE		WHITE		WHITE																	
RED		RED		BLUE		BLUE		GREEN		GREEN																	
WHITE		WHITE		WHITE		WHITE		WHITE		WHITE																	
		RED		BLUE		BLUE				GREEN																	
		WHITE		WHITE		WHITE				WHITE																	

RF CABLE COLOR CODES

NO SCALE

1

NOT USED

NO SCALE

4

LOW BANDS (N71+N26)  
OPTIONAL - (N29)

ORANGE

CBRS TECH  
(3 GHz)

YELLOW

AWS  
(N66+N70+H-BLOCK)

PURPLE

NEGATIVE SLANT PORT  
ON ANT/RRH

WHITE

ALPHA SECTOR

RED

BETA SECTOR

BLUE

GAMMA SECTOR

GREEN

COLOR IDENTIFIER

NO SCALE

2

NOT USED

NO SCALE

3

NOT USED

NO SCALE

4

dish  
wireless.


5701 SOUTH SANTA FE DRIVE  
LITTLETON, CO 80120



8051 CONGRESS AVENUE  
BOCA RATON, FL 33487



1717 S. BOULDER  
SUITE 300  
TULSA, OK 74119  
PH: (918) 587-4630  
www.btgrp.com



MTS ENGINEERING P.L.L.C.  
BER:2386985  
Expires 3/31/23

IT IS A VIOLATION OF LAW FOR ANY PERSON,  
UNLESS THEY ARE ACTING UNDER THE DIRECTION  
OF A LICENSED PROFESSIONAL ENGINEER,  
TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:  
NGN RMC RMC

RFDS REV #: 1

CONSTRUCTION  
DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
0	2/28/22	ISSUED FOR CONSTRUCTION
1	6/22/22	ISSUED FOR CONSTRUCTION
2	1/26/23	ISSUED FOR CONSTRUCTION


A&E PROJECT NUMBER  
149453.001.01

DISH Wireless L.L.C.  
PROJECT INFORMATION  
BOBOS00051A  
2172 GLASGO ROAD  
JEWETT CITY, CT 06351


SHEET TITLE  
RF  
CABLE COLOR CODE

SHEET NUMBER  
RF-1

EXOTHERMIC CONNECTION  
 MECHANICAL CONNECTION  
 BUSS BAR INSULATOR  
 CHEMICAL ELECTROLYTIC GROUNDING SYSTEM  
 TEST CHEMICAL ELECTROLYTIC GROUNDING SYSTEM  
 EXOTHERMIC WITH INSPECTION SLEEVE  
 GROUNDING BAR  
 GROUND ROD  
 TEST GROUND ROD WITH INSPECTION SLEEVE  
 SINGLE POLE SWITCH  
 DUPLEX RECEPTACLE  
 DUPLEX GFCI RECEPTACLE  
 FLUORESCENT LIGHTING FIXTURE (2) TWO LAMPS 48-T8  
 SMOKE DETECTION (DC)  
 EMERGENCY LIGHTING (DC)  
 SECURITY LIGHT W/PHOTOCELL LITHONIA ALXW  
 LED-1-25A400/51K-SR4-120-PE-DOBXTD  
 CHAIN LINK FENCE  
 WOOD/WROUGHT IRON FENCE  
 WALL STRUCTURE  
 LEASE AREA  
 PROPERTY LINE (PL)  
 SETBACKS  
 ICE BRIDGE  
 CABLE TRAY  
 WATER LINE  
 UNDERGROUND POWER  
 UNDERGROUND TELCO  
 OVERHEAD POWER  
 OVERHEAD TELCO  
 UNDERGROUND TELCO/POWER  
 ABOVE GROUND POWER  
 ABOVE GROUND TELCO  
 ABOVE GROUND TELCO/POWER  
 WORKPOINT



SECTION REFERENCE  
 DETAIL REFERENCE



**LEGEND**

AB ANCHOR BOLT  
 ABV ABOVE  
 AC ALTERNATING CURRENT  
 ADDL ADDITIONAL  
 AFF ABOVE FINISHED FLOOR  
 AFG ABOVE FINISHED GRADE  
 AGL ABOVE GROUND LEVEL  
 AIC AMPERAGE INTERRUPTION CAPACITY  
 ALUM ALUMINUM  
 ALT ALTERNATE  
 ANT ANTENNA  
 APPROX APPROXIMATE  
 ARCH ARCHITECTURAL  
 ATS AUTOMATIC TRANSFER SWITCH  
 AWG AMERICAN WIRE GAUGE  
 BATT BATTERY  
 BLDG BUILDING  
 BLK BLOCK  
 BLKG BLOCKING  
 BM BEAM  
 BTC BARE TINNED COPPER CONDUCTOR  
 BOF BOTTOM OF FOOTING  
 CAB CABINET  
 CANT CANTILEVERED  
 CHG CHARGING  
 CLG CEILING  
 CLR CLEAR  
 COL COLUMN  
 COMM COMMON  
 CONC CONCRETE  
 CONSTR CONSTRUCTION  
 DBL DOUBLE  
 DC DIRECT CURRENT  
 DEPT DEPARTMENT  
 DF DOUGLAS FIR  
 DIA DIAMETER  
 DIAG DIAGONAL  
 DIM DIMENSION  
 DWG DRAWING  
 DWL DOWEL  
 EA EACH  
 EC ELECTRICAL CONDUCTOR  
 EL ELEVATION  
 ELEC ELECTRICAL  
 EMT ELECTRICAL METALLIC TUBING  
 ENG ENGINEER  
 EQ EQUAL  
 EXP EXPANSION  
 EXT EXTERIOR  
 EW EACH WAY  
 FAB FABRICATION  
 FF FINISH FLOOR  
 FG FINISH GRADE  
 FIF FACILITY INTERFACE FRAME  
 FIN FINISH(ED)  
 FLR FLOOR  
 FDN FOUNDATION  
 FOC FACE OF CONCRETE  
 FOM FACE OF MASONRY  
 FOS FACE OF STUD  
 FOW FACE OF WALL  
 FS FINISH SURFACE  
 FT FOOT  
 FTG FOOTING  
 GA GAUGE  
 GEN GENERATOR  
 GFCI GROUND FAULT CIRCUIT INTERRUPTER  
 GLB GLUE LAMINATED BEAM  
 GLV GALVANIZED  
 GPS GLOBAL POSITIONING SYSTEM  
 GND GROUND  
 GSM GLOBAL SYSTEM FOR MOBILE  
 HDG HOT DIPPED GALVANIZED  
 HDR HEADER  
 HGR HANGER  
 HVAC HEAT/VENTILATION/AIR CONDITIONING  
 HT HEIGHT  
 IGR INTERIOR GROUND RING

IN INCH  
 INT INTERIOR  
 LB(S) POUND(S)  
 LF LINEAR FEET  
 LTE LONG TERM EVOLUTION  
 MAS MASONRY  
 MAX MAXIMUM  
 MB MACHINE BOLT  
 MECH MECHANICAL  
 MFR MANUFACTURER  
 MGB MASTER GROUND BAR  
 MIN MINIMUM  
 MISC MISCELLANEOUS  
 MTL METAL  
 MTS MANUAL TRANSFER SWITCH  
 MW MICROWAVE  
 NEC NATIONAL ELECTRIC CODE  
 NM NEWTON METERS  
 NO. NUMBER  
 # NUMBER  
 NTS NOT TO SCALE  
 OC ON-CENTER  
 OSHA OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION  
 OPNG OPENING  
 P/C PRECAST CONCRETE  
 PCS PERSONAL COMMUNICATION SERVICES  
 PCU PRIMARY CONTROL UNIT  
 PRC PRIMARY RADIO CABINET  
 PP POLARIZING PRESERVING  
 PSF POUNDS PER SQUARE FOOT  
 PSI POUNDS PER SQUARE INCH  
 PT PRESSURE TREATED  
 PWR POWER CABINET  
 QTY QUANTITY  
 RAD RADIUS  
 RECT RECTIFIER  
 REF REFERENCE  
 REINF REINFORCEMENT  
 REQ'D REQUIRED  
 RET REMOTE ELECTRIC TILT  
 RF RADIO FREQUENCY  
 RMC RIGID METALLIC CONDUIT  
 RRH REMOTE RADIO HEAD  
 RRU REMOTE RADIO UNIT  
 RWY RACEWAY  
 SCH SCHEDULE  
 SHT SHEET  
 SIAD SMART INTEGRATED ACCESS DEVICE  
 SIM SIMILAR  
 SPEC SPECIFICATION  
 SQ SQUARE  
 SS STAINLESS STEEL  
 STD STANDARD  
 STL STEEL  
 TEMP TEMPORARY  
 THK THICKNESS  
 TMA TOWER MOUNTED AMPLIFIER  
 TN TOE NAIL  
 TOA TOP OF ANTENNA  
 TOC TOP OF CURB  
 TOF TOP OF FOUNDATION  
 TOP TOP OF PLATE (PARAPET)  
 TOS TOP OF STEEL  
 TOW TOP OF WALL  
 TVSS TRANSIENT VOLTAGE SURGE SUPPRESSION  
 TYP TYPICAL  
 UG UNDERGROUND  
 UL UNDERWRITERS LABORATORY  
 UNO UNLESS NOTED OTHERWISE  
 UMTS UNIVERSAL MOBILE TELECOMMUNICATIONS SYSTEM  
 UPS UNINTERRUPTIBLE POWER SYSTEM (DC POWER PLANT)  
 VIF VERIFIED IN FIELD  
 W WIDE  
 W/ WITH  
 WD WOOD  
 WP WEATHERPROOF  
 WT WEIGHT

**ABBREVIATIONS**



5701 SOUTH SANTA FE DRIVE  
 LITTLETON, CO 80120



8051 CONGRESS AVENUE  
 BOCA RATON, FL 33487



MTS ENGINEERING P.L.L.C.  
 BER:2386985  
 Expires 3/31/23

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: NGN CHECKED BY: RMC APPROVED BY: RMC

RFDS REV #: 1

**CONSTRUCTION DOCUMENTS**

SUBMITTALS		
REV	DATE	DESCRIPTION
0	2/28/22	ISSUED FOR CONSTRUCTION
1	6/22/22	ISSUED FOR CONSTRUCTION
2	1/26/23	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER  
**149453.001.01**

DISH Wireless L.L.C.  
 PROJECT INFORMATION  
**BOBOS00051A**  
 2172 GLASGO ROAD  
 JEWETT CITY, CT 06351

SHEET TITLE  
**LEGEND AND ABBREVIATIONS**

SHEET NUMBER  
**GN-1**

SITE ACTIVITY REQUIREMENTS:

- NOTICE TO PROCEED – NO WORK SHALL COMMENCE PRIOR TO CONTRACTOR RECEIVING A WRITTEN NOTICE TO PROCEED (NTP) AND THE ISSUANCE OF A PURCHASE ORDER. PRIOR TO ACCESSING/ENTERING THE SITE YOU MUST CONTACT THE DISH Wireless L.L.C. AND TOWER OWNER NOC & THE DISH Wireless L.L.C. AND TOWER OWNER CONSTRUCTION MANAGER.
- "LOOK UP" – DISH Wireless L.L.C. AND TOWER OWNER SAFETY CLIMB REQUIREMENT:  
THE INTEGRITY OF THE SAFETY CLIMB AND ALL COMPONENTS OF THE CLIMBING FACILITY SHALL BE CONSIDERED DURING ALL STAGES OF DESIGN, INSTALLATION, AND INSPECTION. TOWER MODIFICATION, MOUNT REINFORCEMENTS, AND/OR EQUIPMENT INSTALLATIONS SHALL NOT COMPROMISE THE INTEGRITY OR FUNCTIONAL USE OF THE SAFETY CLIMB OR ANY COMPONENTS OF THE CLIMBING FACILITY ON THE STRUCTURE. THIS SHALL INCLUDE, BUT NOT BE LIMITED TO: PINCHING OF THE WIRE ROPE, BENDING OF THE WIRE ROPE FROM ITS SUPPORTS, DIRECT CONTACT OR CLOSE PROXIMITY TO THE WIRE ROPE WHICH MAY CAUSE FRICTIONAL WEAR, IMPACT TO THE ANCHORAGE POINTS IN ANY WAY, OR TO IMPEDE/BLOCK ITS INTENDED USE. ANY COMPROMISED SAFETY CLIMB, INCLUDING EXISTING CONDITIONS MUST BE TAGGED OUT AND REPORTED TO YOUR DISH Wireless L.L.C. AND DISH Wireless L.L.C. AND TOWER OWNER POC OR CALL THE NOC TO GENERATE A SAFETY CLIMB MAINTENANCE AND CONTRACTOR NOTICE TICKET.
- PRIOR TO THE START OF CONSTRUCTION, ALL REQUIRED JURISDICTIONAL PERMITS SHALL BE OBTAINED. THIS INCLUDES, BUT IS NOT LIMITED TO, BUILDING, ELECTRICAL, MECHANICAL, FIRE, FLOOD ZONE, ENVIRONMENTAL, AND ZONING. AFTER ONSITE ACTIVITIES AND CONSTRUCTION ARE COMPLETED, ALL REQUIRED PERMITS SHALL BE SATISFIED AND CLOSED OUT ACCORDING TO LOCAL JURISDICTIONAL REQUIREMENTS.
- ALL CONSTRUCTION MEANS AND METHODS; INCLUDING BUT NOT LIMITED TO, ERECTION PLANS, RIGGING PLANS, CLIMBING PLANS, AND RESCUE PLANS SHALL BE THE RESPONSIBILITY OF THE GENERAL CONTRACTOR RESPONSIBLE FOR THE EXECUTION OF THE WORK CONTAINED HEREIN, AND SHALL MEET ANSI/ASSE A10.48 (LATEST EDITION); FEDERAL, STATE, AND LOCAL REGULATIONS; AND ANY APPLICABLE INDUSTRY CONSENSUS STANDARDS RELATED TO THE CONSTRUCTION ACTIVITIES BEING PERFORMED. ALL RIGGING PLANS SHALL ADHERE TO ANSI/ASSE A10.48 (LATEST EDITION) AND DISH Wireless L.L.C. AND TOWER OWNER STANDARDS, INCLUDING THE REQUIRED INVOLVEMENT OF A QUALIFIED ENGINEER FOR CLASS IV CONSTRUCTION, TO CERTIFY THE SUPPORTING STRUCTURE(S) IN ACCORDANCE WITH ANSI/TIA-322 (LATEST EDITION).
- ALL SITE WORK TO COMPLY WITH DISH Wireless L.L.C. AND TOWER OWNER INSTALLATION STANDARDS FOR CONSTRUCTION ACTIVITIES ON DISH Wireless L.L.C. AND TOWER OWNER TOWER SITE AND LATEST VERSION OF ANSI/TIA-1019-A-2012 "STANDARD FOR INSTALLATION, ALTERATION, AND MAINTENANCE OF ANTENNA SUPPORTING STRUCTURES AND ANTENNAS."
- IF THE SPECIFIED EQUIPMENT CAN NOT BE INSTALLED AS SHOWN ON THESE DRAWINGS, THE CONTRACTOR SHALL PROPOSE AN ALTERNATIVE INSTALLATION FOR APPROVAL BY DISH Wireless L.L.C. AND TOWER OWNER PRIOR TO PROCEEDING WITH ANY SUCH CHANGE OF INSTALLATION.
- ALL MATERIALS FURNISHED AND INSTALLED SHALL BE IN STRICT ACCORDANCE WITH ALL APPLICABLE CODES, REGULATIONS AND ORDINANCES. CONTRACTOR SHALL ISSUE ALL APPROPRIATE NOTICES AND COMPLY WITH ALL LAWS, ORDINANCES, RULES, REGULATIONS AND LAWFUL ORDERS OF ANY PUBLIC AUTHORITY REGARDING THE PERFORMANCE OF THE WORK. ALL WORK CARRIED OUT SHALL COMPLY WITH ALL APPLICABLE MUNICIPAL AND UTILITY COMPANY SPECIFICATIONS AND LOCAL JURISDICTIONAL CODES, ORDINANCES AND APPLICABLE REGULATIONS.
- THE CONTRACTOR SHALL INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS UNLESS SPECIFICALLY STATED OTHERWISE.
- THE CONTRACTOR SHALL CONTACT UTILITY LOCATING SERVICES INCLUDING PRIVATE LOCATES SERVICES PRIOR TO THE START OF CONSTRUCTION.
- ALL EXISTING ACTIVE SEWER, WATER, GAS, ELECTRIC AND OTHER UTILITIES WHERE ENCOUNTERED IN THE WORK, SHALL BE PROTECTED AT ALL TIMES AND WHERE REQUIRED FOR THE PROPER EXECUTION OF THE WORK, SHALL BE RELOCATED AS DIRECTED BY CONTRACTOR. EXTREME CAUTION SHOULD BE USED BY THE CONTRACTOR WHEN EXCAVATING OR DRILLING PIERS AROUND OR NEAR UTILITIES. CONTRACTOR SHALL PROVIDE SAFETY TRAINING FOR THE WORKING CREW. THIS WILL INCLUDE BUT NOT BE LIMITED TO A) FALL PROTECTION B) CONFINED SPACE C) ELECTRICAL SAFETY D) TRENCHING AND EXCAVATION E) CONSTRUCTION SAFETY PROCEDURES.
- ALL SITE WORK SHALL BE AS INDICATED ON THE STAMPED CONSTRUCTION DRAWINGS AND DISH PROJECT SPECIFICATIONS, LATEST APPROVED REVISION.
- CONTRACTOR SHALL KEEP THE SITE FREE FROM ACCUMULATING WASTE MATERIAL, DEBRIS, AND TRASH AT THE COMPLETION OF THE WORK. IF NECESSARY, RUBBISH, STUMPS, DEBRIS, STICKS, STONES AND OTHER REFUSE SHALL BE REMOVED FROM THE SITE AND DISPOSED OF LEGALLY.
- ALL EXISTING INACTIVE SEWER, WATER, GAS, ELECTRIC AND OTHER UTILITIES, WHICH INTERFERE WITH THE EXECUTION OF THE WORK, SHALL BE REMOVED AND/OR CAPPED, PLUGGED OR OTHERWISE DISCONTINUED AT POINTS WHICH WILL NOT INTERFERE WITH THE EXECUTION OF THE WORK, SUBJECT TO THE APPROVAL OF DISH Wireless L.L.C. AND TOWER OWNER, AND/OR LOCAL UTILITIES.
- THE CONTRACTOR SHALL PROVIDE SITE SIGNAGE IN ACCORDANCE WITH THE TECHNICAL SPECIFICATION FOR SITE SIGNAGE REQUIRED BY LOCAL JURISDICTION AND SIGNAGE REQUIRED ON INDIVIDUAL PIECES OF EQUIPMENT, ROOMS, AND SHELTERS.
- THE SITE SHALL BE GRADED TO CAUSE SURFACE WATER TO FLOW AWAY FROM THE CARRIER'S EQUIPMENT AND TOWER AREAS.
- THE SUB GRADE SHALL BE COMPACTED AND BROUGHT TO A SMOOTH UNIFORM GRADE PRIOR TO FINISHED SURFACE APPLICATION.
- THE AREAS OF THE OWNERS PROPERTY DISTURBED BY THE WORK AND NOT COVERED BY THE TOWER, EQUIPMENT OR DRIVEWAY, SHALL BE GRADED TO A UNIFORM SLOPE, AND STABILIZED TO PREVENT EROSION AS SPECIFIED ON THE CONSTRUCTION DRAWINGS AND/OR PROJECT SPECIFICATIONS.
- CONTRACTOR SHALL MINIMIZE DISTURBANCE TO EXISTING SITE DURING CONSTRUCTION. EROSION CONTROL MEASURES, IF REQUIRED DURING CONSTRUCTION, SHALL BE IN CONFORMANCE WITH THE LOCAL GUIDELINES FOR EROSION AND SEDIMENT CONTROL.
- THE CONTRACTOR SHALL PROTECT EXISTING IMPROVEMENTS, PAVEMENTS, CURBS, LANDSCAPING AND STRUCTURES. ANY DAMAGED PART SHALL BE REPAIRED AT CONTRACTOR'S EXPENSE TO THE SATISFACTION OF OWNER.
- CONTRACTOR SHALL LEGALLY AND PROPERLY DISPOSE OF ALL SCRAP MATERIALS SUCH AS COAXIAL CABLES AND OTHER ITEMS REMOVED FROM THE EXISTING FACILITY. ANTENNAS AND RADIOS REMOVED SHALL BE RETURNED TO THE OWNER'S DESIGNATED LOCATION.
- CONTRACTOR SHALL LEAVE PREMISES IN CLEAN CONDITION. TRASH AND DEBRIS SHOULD BE REMOVED FROM SITE ON A DAILY BASIS.
- NO FILL OR EMBANKMENT MATERIAL SHALL BE PLACED ON FROZEN GROUND. FROZEN MATERIALS, SNOW OR ICE SHALL NOT BE PLACED IN ANY FILL OR EMBANKMENT.

GENERAL NOTES:

- FOR THE PURPOSE OF CONSTRUCTION DRAWING, THE FOLLOWING DEFINITIONS SHALL APPLY:  
CONTRACTOR:GENERAL CONTRACTOR RESPONSIBLE FOR CONSTRUCTION  
CARRIER:DISH Wireless L.L.C.  
TOWER OWNER:TOWER OWNER
- THESE DRAWINGS HAVE BEEN PREPARED USING STANDARDS OF PROFESSIONAL CARE AND COMPLETENESS NORMALLY EXERCISED UNDER SIMILAR CIRCUMSTANCES BY REPUTABLE ENGINEERS IN THIS OR SIMILAR LOCALITIES. IT IS ASSUMED THAT THE WORK DEPICTED WILL BE PERFORMED BY AN EXPERIENCED CONTRACTOR AND/OR WORKPEOPLE WHO HAVE A WORKING KNOWLEDGE OF THE APPLICABLE CODE STANDARDS AND REQUIREMENTS AND OF INDUSTRY ACCEPTED STANDARD GOOD PRACTICE. AS NOT EVERY CONDITION OR ELEMENT IS (OR CAN BE) EXPLICITLY SHOWN ON THESE DRAWINGS, THE CONTRACTOR SHALL USE INDUSTRY ACCEPTED STANDARD GOOD PRACTICE FOR MISCELLANEOUS WORK NOT EXPLICITLY SHOWN.
- THESE DRAWINGS REPRESENT THE FINISHED STRUCTURE. THEY DO NOT INDICATE THE MEANS OR METHODS OF CONSTRUCTION. THE CONTRACTOR SHALL BE SOLELY RESPONSIBLE FOR THE CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES, AND PROCEDURES. THE CONTRACTOR SHALL PROVIDE ALL MEASURES NECESSARY FOR PROTECTION OF LIFE AND PROPERTY DURING CONSTRUCTION. SUCH MEASURES SHALL INCLUDE, BUT NOT BE LIMITED TO, BRACING, FORMWORK, SHORING, ETC. SITE VISITS BY THE ENGINEER OR HIS REPRESENTATIVE WILL NOT INCLUDE INSPECTION OF THESE ITEMS AND IS FOR STRUCTURAL OBSERVATION OF THE FINISHED STRUCTURE ONLY.
- NOTES AND DETAILS IN THE CONSTRUCTION DRAWINGS SHALL TAKE PRECEDENCE OVER GENERAL NOTES AND TYPICAL DETAILS. WHERE NO DETAILS ARE SHOWN, CONSTRUCTION SHALL CONFORM TO SIMILAR WORK ON THE PROJECT, AND/OR AS PROVIDED FOR IN THE CONTRACT DOCUMENTS. WHERE DISCREPANCIES OCCUR BETWEEN PLANS, DETAILS, GENERAL NOTES, AND SPECIFICATIONS, THE GREATER, MORE STRICT REQUIREMENTS, SHALL GOVERN. IF FURTHER CLARIFICATION IS REQUIRED CONTACT THE ENGINEER OF RECORD.
- SUBSTANTIAL EFFORT HAS BEEN MADE TO PROVIDE ACCURATE DIMENSIONS AND MEASUREMENTS ON THE DRAWINGS TO ASSIST IN THE FABRICATION AND/OR PLACEMENT OF CONSTRUCTION ELEMENTS BUT IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO FIELD VERIFY THE DIMENSIONS, MEASUREMENTS, AND/OR CLEARANCES SHOWN IN THE CONSTRUCTION DRAWINGS PRIOR TO FABRICATION OR CUTTING OF ANY NEW OR EXISTING CONSTRUCTION ELEMENTS. IF IT IS DETERMINED THAT THERE ARE DISCREPANCIES AND/OR CONFLICTS WITH THE CONSTRUCTION DRAWINGS THE ENGINEER OF RECORD IS TO BE NOTIFIED AS SOON AS POSSIBLE.
- PRIOR TO THE SUBMISSION OF BIDS, THE BIDDING CONTRACTOR SHALL VISIT THE CELL SITE TO FAMILIARIZE WITH THE EXISTING CONDITIONS AND TO CONFIRM THAT THE WORK CAN BE ACCOMPLISHED AS SHOWN ON THE CONSTRUCTION DRAWINGS. ANY DISCREPANCY FOUND SHALL BE BROUGHT TO THE ATTENTION OF CARRIER POC AND TOWER OWNER.
- ALL MATERIALS FURNISHED AND INSTALLED SHALL BE IN STRICT ACCORDANCE WITH ALL APPLICABLE CODES, REGULATIONS AND ORDINANCES. CONTRACTOR SHALL ISSUE ALL APPROPRIATE NOTICES AND COMPLY WITH ALL LAWS, ORDINANCES, RULES, REGULATIONS AND LAWFUL ORDERS OF ANY PUBLIC AUTHORITY REGARDING THE PERFORMANCE OF THE WORK. ALL WORK CARRIED OUT SHALL COMPLY WITH ALL APPLICABLE MUNICIPAL AND UTILITY COMPANY SPECIFICATIONS AND LOCAL JURISDICTIONAL CODES, ORDINANCES AND APPLICABLE REGULATIONS.
- UNLESS NOTED OTHERWISE, THE WORK SHALL INCLUDE FURNISHING MATERIALS, EQUIPMENT, APPURTENANCES AND LABOR NECESSARY TO COMPLETE ALL INSTALLATIONS AS INDICATED ON THE DRAWINGS.
- THE CONTRACTOR SHALL INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS UNLESS SPECIFICALLY STATED OTHERWISE.
- IF THE SPECIFIED EQUIPMENT CAN NOT BE INSTALLED AS SHOWN ON THESE DRAWINGS, THE CONTRACTOR SHALL PROPOSE AN ALTERNATIVE INSTALLATION FOR APPROVAL BY THE CARRIER AND TOWER OWNER PRIOR TO PROCEEDING WITH ANY SUCH CHANGE OF INSTALLATION.
- CONTRACTOR IS TO PERFORM A SITE INVESTIGATION, BEFORE SUBMITTING BIDS, TO DETERMINE THE BEST ROUTING OF ALL CONDUITS FOR POWER, AND TELCO AND FOR GROUNDING CABLES AS SHOWN IN THE POWER, TELCO, AND GROUNDING PLAN DRAWINGS.
- THE CONTRACTOR SHALL PROTECT EXISTING IMPROVEMENTS, PAVEMENTS, CURBS, LANDSCAPING AND STRUCTURES. ANY DAMAGED PART SHALL BE REPAIRED AT CONTRACTOR'S EXPENSE TO THE SATISFACTION OF DISH Wireless L.L.C. AND TOWER OWNER
- CONTRACTOR SHALL LEGALLY AND PROPERLY DISPOSE OF ALL SCRAP MATERIALS SUCH AS COAXIAL CABLES AND OTHER ITEMS REMOVED FROM THE EXISTING FACILITY. ANTENNAS REMOVED SHALL BE RETURNED TO THE OWNER'S DESIGNATED LOCATION.
- CONTRACTOR SHALL LEAVE PREMISES IN CLEAN CONDITION. TRASH AND DEBRIS SHOULD BE REMOVED FROM SITE ON A DAILY BASIS.



5701 SOUTH SANTA FE DRIVE  
LITTLETON, CO 80120



8051 CONGRESS AVENUE  
BOCA RATON, FL 33487



MTS ENGINEERING P.L.L.C.  
BER:2386985  
Expires 3/31/23

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
NGN	RMC	RMC

RFDS REV #: 1

**CONSTRUCTION DOCUMENTS**

SUBMITTALS		
REV	DATE	DESCRIPTION
0	2/28/22	ISSUED FOR CONSTRUCTION
1	6/22/22	ISSUED FOR CONSTRUCTION
2	1/26/23	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER  
**149453.001.01**

DISH Wireless L.L.C.  
PROJECT INFORMATION  
**BOBOS00051A**  
2172 GLASGO ROAD  
JEWETT CITY, CT 06351

SHEET TITLE  
**GENERAL NOTES**

SHEET NUMBER  
**GN-2**

CONCRETE, FOUNDATIONS, AND REINFORCING STEEL:

1. ALL CONCRETE WORK SHALL BE IN ACCORDANCE WITH THE ACI 301, ACI 318, ACI 336, ASTM A184, ASTM A185 AND THE DESIGN AND CONSTRUCTION SPECIFICATION FOR CAST-IN-PLACE CONCRETE.
2. UNLESS NOTED OTHERWISE, SOIL BEARING PRESSURE USED FOR DESIGN OF SLABS AND FOUNDATIONS IS ASSUMED TO BE 1000 psf.
3. ALL CONCRETE SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH (f'c) OF 3000 psi AT 28 DAYS, UNLESS NOTED OTHERWISE. NO MORE THAN 90 MINUTES SHALL ELAPSE FROM BATCH TIME TO TIME OF PLACEMENT UNLESS APPROVED BY THE ENGINEER OF RECORD. TEMPERATURE OF CONCRETE SHALL NOT EXCEED 90°f AT TIME OF PLACEMENT.
4. CONCRETE EXPOSED TO FREEZE-THAW CYCLES SHALL CONTAIN AIR ENTRAINING ADMIXTURES. AMOUNT OF AIR ENTRAINMENT TO BE BASED ON SIZE OF AGGREGATE AND F3 CLASS EXPOSURE (VERY SEVERE). CEMENT USED TO BE TYPE II PORTLAND CEMENT WITH A MAXIMUM WATER-TO-CEMENT RATIO (W/C) OF 0.45.
5. ALL STEEL REINFORCING SHALL CONFORM TO ASTM A615. ALL WELDED WIRE FABRIC (WWF) SHALL CONFORM TO ASTM A185. ALL SPLICES SHALL BE CLASS "B" TENSION SPLICES, UNLESS NOTED OTHERWISE. ALL HOOKS SHALL BE STANDARD 90 DEGREE HOOKS, UNLESS NOTED OTHERWISE. YIELD STRENGTH (Fy) OF STANDARD DEFORMED BARS ARE AS FOLLOWS:  
 #4 BARS AND SMALLER 40 ksi  
 #5 BARS AND LARGER 60 ksi
6. THE FOLLOWING MINIMUM CONCRETE COVER SHALL BE PROVIDED FOR REINFORCING STEEL UNLESS SHOWN OTHERWISE ON DRAWINGS:
  - CONCRETE CAST AGAINST AND PERMANENTLY EXPOSED TO EARTH 3"
  - CONCRETE EXPOSED TO EARTH OR WEATHER:
    - #6 BARS AND LARGER 2"
    - #5 BARS AND SMALLER 1-1/2"
  - CONCRETE NOT EXPOSED TO EARTH OR WEATHER:
    - SLAB AND WALLS 3/4"
    - BEAMS AND COLUMNS 1-1/2"
7. A TOOLED EDGE OR A 3/4" CHAMFER SHALL BE PROVIDED AT ALL EXPOSED EDGES OF CONCRETE, UNLESS NOTED OTHERWISE, IN ACCORDANCE WITH ACI 301 SECTION 4.2.4.

ELECTRICAL INSTALLATION NOTES:

1. ALL ELECTRICAL WORK SHALL BE PERFORMED IN ACCORDANCE WITH THE PROJECT SPECIFICATIONS, NEC AND ALL APPLICABLE FEDERAL, STATE, AND LOCAL CODES/ORDINANCES.
2. CONDUIT ROUTINGS ARE SCHEMATIC. CONTRACTOR SHALL INSTALL CONDUITS SO THAT ACCESS TO EQUIPMENT IS NOT BLOCKED AND TRIP HAZARDS ARE ELIMINATED.
3. WIRING, RACEWAY AND SUPPORT METHODS AND MATERIALS SHALL COMPLY WITH THE REQUIREMENTS OF THE NEC.
4. ALL CIRCUITS SHALL BE SEGREGATED AND MAINTAIN MINIMUM CABLE SEPARATION AS REQUIRED BY THE NEC.
- 4.1. ALL EQUIPMENT SHALL BEAR THE UNDERWRITERS LABORATORIES LABEL OF APPROVAL, AND SHALL CONFORM TO REQUIREMENT OF THE NATIONAL ELECTRICAL CODE.
- 4.2. ALL OVERCURRENT DEVICES SHALL HAVE AN INTERRUPTING CURRENT RATING THAT SHALL BE GREATER THAN THE SHORT CIRCUIT CURRENT TO WHICH THEY ARE SUBJECTED, 22,000 AIC MINIMUM. VERIFY AVAILABLE SHORT CIRCUIT CURRENT DOES NOT EXCEED THE RATING OF ELECTRICAL EQUIPMENT IN ACCORDANCE WITH ARTICLE 110.24 NEC OR THE MOST CURRENT ADOPTED CODE PRE THE GOVERNING JURISDICTION.
5. EACH END OF EVERY POWER PHASE CONDUCTOR, GROUNDING CONDUCTOR, AND TELCO CONDUCTOR OR CABLE SHALL BE LABELED WITH COLOR-CODED INSULATION OR ELECTRICAL TAPE (3M BRAND, 1/2" PLASTIC ELECTRICAL TAPE WITH UV PROTECTION, OR EQUAL). THE IDENTIFICATION METHOD SHALL CONFORM WITH NEC AND OSHA.
6. ALL ELECTRICAL COMPONENTS SHALL BE CLEARLY LABELED WITH LAMICOID TAGS SHOWING THEIR RATED VOLTAGE, PHASE CONFIGURATION, WIRE CONFIGURATION, POWER OR AMPACITY RATING AND BRANCH CIRCUIT ID NUMBERS (i.e. PANEL BOARD AND CIRCUIT ID'S).
7. PANEL BOARDS (ID NUMBERS) SHALL BE CLEARLY LABELED WITH PLASTIC LABELS.
8. TIE WRAPS ARE NOT ALLOWED.
9. ALL POWER AND EQUIPMENT GROUND WIRING IN TUBING OR CONDUIT SHALL BE SINGLE COPPER CONDUCTOR (#14 OR LARGER) WITH TYPE THHW, THWN, THWN-2, XHHW, XHHW-2, THW, THW-2, RHW, OR RHW-2 INSULATION UNLESS OTHERWISE SPECIFIED.
10. SUPPLEMENTAL EQUIPMENT GROUND WIRING LOCATED INDOORS SHALL BE SINGLE COPPER CONDUCTOR (#6 OR LARGER) WITH TYPE THHW, THWN, THWN-2, XHHW, XHHW-2, THW, THW-2, RHW, OR RHW-2 INSULATION UNLESS OTHERWISE SPECIFIED.
11. POWER AND CONTROL WIRING IN FLEXIBLE CORD SHALL BE MULTI-CONDUCTOR, TYPE SOOW CORD (#14 OR LARGER) UNLESS OTHERWISE SPECIFIED.
12. POWER AND CONTROL WIRING FOR USE IN CABLE TRAY SHALL BE MULTI-CONDUCTOR, TYPE TC CABLE (#14 OR LARGER), WITH TYPE THHW, THWN, THWN-2, XHHW, XHHW-2, THW, THW-2, RHW, OR RHW-2 INSULATION UNLESS OTHERWISE SPECIFIED.
13. ALL POWER AND GROUNDING CONNECTIONS SHALL BE CRIMP-STYLE, COMPRESSION WIRE LUGS AND WIRE NUTS BY THOMAS AND BETTS (OR EQUAL). LUGS AND WIRE NUTS SHALL BE RATED FOR OPERATION NOT LESS THAN 75° C (90° C IF AVAILABLE).
14. RACEWAY AND CABLE TRAY SHALL BE LISTED OR LABELED FOR ELECTRICAL USE IN ACCORDANCE WITH NEMA, UL, ANSI/IEEE AND NEC.
15. ELECTRICAL METALLIC TUBING (EMT), INTERMEDIATE METAL CONDUIT (IMC), OR RIGID METAL CONDUIT (RMC) SHALL BE USED FOR EXPOSED INDOOR LOCATIONS.

16. ELECTRICAL METALLIC TUBING (EMT) OR METAL-CLAD CABLE (MC) SHALL BE USED FOR CONCEALED INDOOR LOCATIONS.
17. SCHEDULE 40 PVC UNDERGROUND ON STRAIGHTS AND SCHEDULE 80 PVC FOR ALL ELBOWS/90s AND ALL APPROVED ABOVE GRADE PVC CONDUIT.
18. LIQUID-TIGHT FLEXIBLE METALLIC CONDUIT (LIQUID-TITE FLEX) SHALL BE USED INDOORS AND OUTDOORS, WHERE VIBRATION OCCURS OR FLEXIBILITY IS NEEDED.
19. CONDUIT AND TUBING FITTINGS SHALL BE THREADED OR COMPRESSION-TYPE AND APPROVED FOR THE LOCATION USED. SET SCREW FITTINGS ARE NOT ACCEPTABLE.
20. CABINETS, BOXES AND WIRE WAYS SHALL BE LABELED FOR ELECTRICAL USE IN ACCORDANCE WITH NEMA, UL, ANSI/IEEE AND THE NEC.
21. WIREWAYS SHALL BE METAL WITH AN ENAMEL FINISH AND INCLUDE A HINGED COVER, DESIGNED TO SWING OPEN DOWNWARDS (WIREMOLD SPECMATE WIREWAY).
22. SLOTTED WIRING DUCT SHALL BE PVC AND INCLUDE COVER (PANDUIT TYPE E OR EQUAL).
23. CONDUITS SHALL BE FASTENED SECURELY IN PLACE WITH APPROVED NON-PERFORATED STRAPS AND HANGERS. EXPLOSIVE DEVICES (i.e. POWDER-ACTUATED) FOR ATTACHING HANGERS TO STRUCTURE WILL NOT BE PERMITTED. CLOSELY FOLLOW THE LINES OF THE STRUCTURE, MAINTAIN CLOSE PROXIMITY TO THE STRUCTURE AND KEEP CONDUITS IN TIGHT ENVELOPES. CHANGES IN DIRECTION TO ROUTE AROUND OBSTACLES SHALL BE MADE WITH CONDUIT OUTLET BODIES. CONDUIT SHALL BE INSTALLED IN A NEAT AND WORKMANLIKE MANNER. PARALLEL AND PERPENDICULAR TO STRUCTURE WALL AND CEILING LINES. ALL CONDUIT SHALL BE FISHED TO CLEAR OBSTRUCTIONS. ENDS OF CONDUITS SHALL BE TEMPORARILY CAPPED FLUSH TO FINISH GRADE TO PREVENT CONCRETE, PLASTER OR DIRT FROM ENTERING. CONDUITS SHALL BE RIGIDLY CLAMPED TO BOXES BY GALVANIZED MALLEABLE IRON BUSHING ON INSIDE AND GALVANIZED MALLEABLE IRON LOCKNUT ON OUTSIDE AND INSIDE.
24. EQUIPMENT CABINETS, TERMINAL BOXES, JUNCTION BOXES AND PULL BOXES SHALL BE GALVANIZED OR EPOXY-COATED SHEET STEEL. SHALL MEET OR EXCEED UL 50 AND BE RATED NEMA 1 (OR BETTER) FOR INTERIOR LOCATIONS AND NEMA 3 (OR BETTER) FOR EXTERIOR LOCATIONS.
25. METAL RECEPTACLE, SWITCH AND DEVICE BOXES SHALL BE GALVANIZED, EPOXY-COATED OR NON-CORRODING; SHALL MEET OR EXCEED UL 514A AND NEMA OS 1 AND BE RATED NEMA 1 (OR BETTER) FOR INTERIOR LOCATIONS AND WEATHER PROTECTED (WP OR BETTER) FOR EXTERIOR LOCATIONS.
26. NONMETALLIC RECEPTACLE, SWITCH AND DEVICE BOXES SHALL MEET OR EXCEED NEMA OS 2 (NEWEST REVISION) AND BE RATED NEMA 1 (OR BETTER) FOR INTERIOR LOCATIONS AND WEATHER PROTECTED (WP OR BETTER) FOR EXTERIOR LOCATIONS.
27. THE CONTRACTOR SHALL NOTIFY AND OBTAIN NECESSARY AUTHORIZATION FROM THE CARRIER AND/OR DISH Wireless L.L.C. AND TOWER OWNER BEFORE COMMENCING WORK ON THE AC POWER DISTRIBUTION PANELS.
28. THE CONTRACTOR SHALL PROVIDE NECESSARY TAGGING ON THE BREAKERS, CABLES AND DISTRIBUTION PANELS IN ACCORDANCE WITH THE APPLICABLE CODES AND STANDARDS TO SAFEGUARD LIFE AND PROPERTY.
29. INSTALL LAMICOID LABEL ON THE METER CENTER TO SHOW "DISH Wireless L.L.C.".
30. ALL EMPTY/SPARE CONDUITS THAT ARE INSTALLED ARE TO HAVE A METERED MULE TAPE PULL CORD INSTALLED.




5701 SOUTH SANTA FE DRIVE  
LITTLETON, CO 80120



8051 CONGRESS AVENUE  
BOCA RATON, FL 33487



1717 S. BOULDER  
SUITE 300  
TULSA, OK 74119  
PH: (918) 587-4630  
www.btgrp.com



MTS ENGINEERING P.L.L.C.  
BER:2386985  
Expires 3/31/23

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
NGN	RMC	RMC

RFDS REV #: 1

**CONSTRUCTION DOCUMENTS**

SUBMITTALS		
REV	DATE	DESCRIPTION
0	2/28/22	ISSUED FOR CONSTRUCTION
1	6/22/22	ISSUED FOR CONSTRUCTION
2	1/26/23	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER  
**149453.001.01**

DISH Wireless L.L.C.  
PROJECT INFORMATION  
**BOBOS00051A**  
**2172 GLASGO ROAD**  
**JEWETT CITY, CT 06351**

SHEET TITLE  
**GENERAL NOTES**

SHEET NUMBER  
**GN-3**

**GROUNDING NOTES:**

1. ALL GROUND ELECTRODE SYSTEMS (INCLUDING TELECOMMUNICATION, RADIO, LIGHTNING PROTECTION AND AC POWER GES'S) SHALL BE BONDED TOGETHER AT OR BELOW GRADE, BY TWO OR MORE COPPER BONDING CONDUCTORS IN ACCORDANCE WITH THE NEC.
2. THE CONTRACTOR SHALL PERFORM IEEE FALL-OF-POTENTIAL RESISTANCE TO EARTH TESTING (PER IEEE 1100 AND 81) FOR GROUND ELECTRODE SYSTEMS, THE CONTRACTOR SHALL FURNISH AND INSTALL SUPPLEMENTAL GROUND ELECTRODES AS NEEDED TO ACHIEVE A TEST RESULT OF 5 OHMS OR LESS.
3. THE CONTRACTOR IS RESPONSIBLE FOR PROPERLY SEQUENCING GROUNDING AND UNDERGROUND CONDUIT INSTALLATION AS TO PREVENT ANY LOSS OF CONTINUITY IN THE GROUNDING SYSTEM OR DAMAGE TO THE CONDUIT AND PROVIDE TESTING RESULTS.
4. METAL CONDUIT AND TRAY SHALL BE GROUNDED AND MADE ELECTRICALLY CONTINUOUS WITH LISTED BONDING FITTINGS OR BY BONDING ACROSS THE DISCONTINUITY WITH #6 COPPER WIRE UL APPROVED GROUNDING TYPE CONDUIT CLAMPS.
5. METAL RACEWAY SHALL NOT BE USED AS THE NEC REQUIRED EQUIPMENT GROUND CONDUCTOR. STRANDED COPPER CONDUCTORS WITH GREEN INSULATION, SIZED IN ACCORDANCE WITH THE NEC, SHALL BE FURNISHED AND INSTALLED WITH THE POWER CIRCUITS TO BTS EQUIPMENT.
6. EACH CABINET FRAME SHALL BE DIRECTLY CONNECTED TO THE MASTER GROUND BAR WITH GREEN INSULATED SUPPLEMENTAL EQUIPMENT GROUND WIRES, #6 STRANDED COPPER OR LARGER FOR INDOOR BTS; #2 BARE SOLID TINNED COPPER FOR OUTDOOR BTS.
7. CONNECTIONS TO THE GROUND BUS SHALL NOT BE DOUBLED UP OR STACKED BACK TO BACK CONNECTIONS ON OPPOSITE SIDE OF THE GROUND BUS ARE PERMITTED.
8. ALL EXTERIOR GROUND CONDUCTORS BETWEEN EQUIPMENT/GROUND BARS AND THE GROUND RING SHALL BE #2 SOLID TINNED COPPER UNLESS OTHERWISE INDICATED.
9. ALUMINUM CONDUCTOR OR COPPER CLAD STEEL CONDUCTOR SHALL NOT BE USED FOR GROUNDING CONNECTIONS.
10. USE OF 90° BENDS IN THE PROTECTION GROUNDING CONDUCTORS SHALL BE AVOIDED WHEN 45° BENDS CAN BE ADEQUATELY SUPPORTED.
11. EXOTHERMIC WELDS SHALL BE USED FOR ALL GROUNDING CONNECTIONS BELOW GRADE.
12. ALL GROUND CONNECTIONS ABOVE GRADE (INTERIOR AND EXTERIOR) SHALL BE FORMED USING HIGH PRESS CRIMPS.
13. COMPRESSION GROUND CONNECTIONS MAY BE REPLACED BY EXOTHERMIC WELD CONNECTIONS.
14. ICE BRIDGE BONDING CONDUCTORS SHALL BE EXOTHERMICALLY BONDED OR BOLTED TO THE BRIDGE AND THE TOWER GROUND BAR.
15. APPROVED ANTIOXIDANT COATINGS (i.e. CONDUCTIVE GEL OR PASTE) SHALL BE USED ON ALL COMPRESSION AND BOLTED GROUND CONNECTIONS.
16. ALL EXTERIOR GROUND CONNECTIONS SHALL BE COATED WITH A CORROSION RESISTANT MATERIAL.
17. MISCELLANEOUS ELECTRICAL AND NON-ELECTRICAL METAL BOXES, FRAMES AND SUPPORTS SHALL BE BONDED TO THE GROUND RING, IN ACCORDANCE WITH THE NEC.
18. BOND ALL METALLIC OBJECTS WITHIN 6 ft OF MAIN GROUND RING WITH (1) #2 BARE SOLID TINNED COPPER GROUND CONDUCTOR.
19. GROUND CONDUCTORS USED FOR THE FACILITY GROUNDING AND LIGHTNING PROTECTION SYSTEMS SHALL NOT BE ROUTED THROUGH METALLIC OBJECTS THAT FORM A RING AROUND THE CONDUCTOR, SUCH AS METALLIC CONDUITS, METAL SUPPORT CLIPS OR SLEEVES THROUGH WALLS OR FLOORS. WHEN IT IS REQUIRED TO BE HOUSED IN CONDUIT TO MEET CODE REQUIREMENTS OR LOCAL CONDITIONS, NON-METALLIC MATERIAL SUCH AS PVC CONDUIT SHALL BE USED. WHERE USE OF METAL CONDUIT IS UNAVOIDABLE (i.e., NONMETALLIC CONDUIT PROHIBITED BY LOCAL CODE) THE GROUND CONDUCTOR SHALL BE BONDED TO EACH END OF THE METAL CONDUIT.
20. ALL GROUNDS THAT TRANSITION FROM BELOW GRADE TO ABOVE GRADE MUST BE #2 BARE SOLID TINNED COPPER IN 3/4" NON-METALLIC, FLEXIBLE CONDUIT FROM 24" BELOW GRADE TO WITHIN 3" TO 6" OF CAD-WELD TERMINATION POINT. THE EXPOSED END OF THE CONDUIT MUST BE SEALED WITH SILICONE CAULK. (ADD TRANSITIONING GROUND STANDARD DETAIL AS WELL).
21. BUILDINGS WHERE THE MAIN GROUNDING CONDUCTORS ARE REQUIRED TO BE ROUTED TO GRADE, THE CONTRACTOR SHALL ROUTE TWO GROUNDING CONDUCTORS FROM THE ROOFTOP, TOWERS, AND WATER TOWERS GROUNDING RING, TO THE EXISTING GROUNDING SYSTEM, THE GROUNDING CONDUCTORS SHALL NOT BE SMALLER THAN 2/0 COPPER. ROOFTOP GROUNDING RING SHALL BE BONDED TO THE EXISTING GROUNDING SYSTEM, THE BUILDING STEEL COLUMNS, LIGHTNING PROTECTION SYSTEM, AND BUILDING MAIN WATER LINE (FERROUS OR NONFERROUS METAL PIPING ONLY). DO NOT ATTACH GROUNDING TO FIRE SPRINKLER SYSTEM PIPES.



5701 SOUTH SANTA FE DRIVE  
LITTLETON, CO 80120



8051 CONGRESS AVENUE  
BOCA RATON, FL 33487



1717 S. BOULDER  
SUITE 300  
TULSA, OK 74119  
PH: (918) 587-4630  
www.btgrp.com



MTS ENGINEERING P.L.L.C.  
BER:2386985  
Expires 3/31/23

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
NGN	RMC	RMC

RFDS REV #: 1

**CONSTRUCTION DOCUMENTS**

SUBMITTALS		
REV	DATE	DESCRIPTION
0	2/28/22	ISSUED FOR CONSTRUCTION
1	6/22/22	ISSUED FOR CONSTRUCTION
2	1/26/23	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER  
**149453.001.01**

DISH Wireless L.L.C.  
PROJECT INFORMATION  
**BOBOS00051A**  
2172 GLASGO ROAD  
JEWETT CITY, CT 06351

SHEET TITLE  
**GENERAL NOTES**

SHEET NUMBER  
**GN-4**

# Exhibit D

## **Structural Analysis Report**



**Tower Engineering Solutions**

Phone (972) 483-0607, Fax (972) 975-9615  
1320 Greenway Drive, Suite 600, Irving, Texas 75038

---

## **Structural Analysis Report**

**Existing 195 ft PIROD Guyed Tower**

**Customer Name: SBA Communications Corp**

**Customer Site Number: CT10013-A**

**Customer Site Name: Griswold Glasgo**

**Carrier Name: Dish Wireless (App#: 174044-1)**

**Carrier Site ID / Name: BOBOS00051A / 0**

**Site Location: 2172 Glasgo Road**

**Griswold, Connecticut**

**New London County**

**Latitude: 41.537366**

**Longitude: -71.873447**

Exp. 01/31/2024



02/02/2023

### **Analysis Result:**

**Max Structural Usage: 50.0% [Pass]**

**Max Foundation Usage: 23.0% [Pass]**

**Additional Usage Caused by New Mount/Mount Modification: N/A**

**Report Prepared By : Tawfeeq Alajaj**





**Tower Engineering Solutions**

Phone (972) 483-0607, Fax (972) 975-9615  
1320 Greenway Drive, Suite 600, Irving, Texas 75038

---

## **Structural Analysis Report**

**Existing 195 ft PIROD Guyed Tower**

**Customer Name: SBA Communications Corp**

**Customer Site Number: CT10013-A**

**Customer Site Name: Griswold Glasgo**

**Carrier Name: Dish Wireless (App#: 174044-1)**

**Carrier Site ID / Name: BOBOS00051A / 0**

**Site Location: 2172 Glasgo Road**

**Griswold, Connecticut**

**New London County**

**Latitude: 41.537366**

**Longitude: -71.873447**

### **Analysis Result:**

**Max Structural Usage: 50.0% [Pass]**

**Max Foundation Usage: 23.0% [Pass]**

**Additional Usage Caused by New Mount/Mount Modification: N/A**

**Report Prepared By : Tawfeeq Alajaj**

## Introduction

The purpose of this report is to summarize the analysis results on the 195 ft PIROD Guyed Tower to support the proposed antennas and transmission lines in addition to those currently installed. Any modification listed under Sources of Information was assumed completed and was included in this analysis.

## Sources of Information

<b>Tower Drawings</b>	Pirod Inc. (Drawing No. 204648-B) Original Tower Drawings dated February 17, 1999.
<b>Foundation Drawing</b>	Pirod Inc. (Drawing No. 204648-B) Original Tower Drawings dated February 17, 1999.
<b>Geotechnical Report</b>	FDH Engineering, Inc. (Project No. 1207122EG1) Geotechnical Evaluation of Subsurface Conditions dated August 15, 2012.
<b>Modification Drawings</b>	N/A
<b>Mount Analysis</b>	TES MA Job # 127846, dated 04/19/2022.

## Analysis Criteria

The comprehensive analysis was performed in accordance with the requirements and stipulations of the TIA-222-H. In accordance with this standard, the structure was analyzed using **TESTowers**, a proprietary analysis software. The program considers the structure as an elastic 3-D model with second-order effects and temperature effects incorporated in the analysis. The analysis was performed using multiple wind directions.

<b>Wind Speed Used in the Analysis:</b>	130.0 mph (3-Sec. Gust) (Ultimate wind speed)
<b>Wind Speed with Ice:</b>	50 mph (3-Sec. Gust) with 1" radial ice concurrent
<b>Service Load Wind Speed:</b>	60 mph + 0" Radial ice
<b>Standard/Codes:</b>	TIA-222-H / 2021 IBC / 2022 Connecticut State Building Code
<b>Exposure Category:</b>	C
<b>Risk Category:</b>	II
<b>Topographic Category:</b>	1
<b>Crest Height:</b>	0 ft
<b>Seismic Parameters:</b>	$S_5 = 0.191$ , $S_1 = 0.053$

This structural analysis is based upon the tower being classified as a Risk Category II; however, if a different classification is required subsequent to the date hereof, the tower classification will be changed to meet such requirement and a new structural analysis will be run.

**Existing Antennas, Mounts and Transmission Lines**

The table below summarizes the antennas, mounts and transmission lines that were considered in the analysis as existing on the tower.

Items	Elevation (ft)	Qty.	Antenna Descriptions	Mount Type & Qty.	Transmission Lines	Owner
1	185.0	3	Ericsson - AIR6419 B41 - Panel	(3) Sector Frames VFA12-HD	(10) 1 5/8" (6) 1.9" Fiber	T-Mobile
2		3	RFS - APXVAALL24-43-U-NA20 - Panel			
3		3	EMS - RR90-17-XXDP - Panel			
4		3	Ericsson KRY 112 489/2 - TMA/TTA			
5		6	CommScope CBC1923T-DS-43			
6		3	Ericsson 4449 B71 + B85			
7		3	Ericsson 4460 B25 + B66			
8		3	Kathrein 782 11056			
8	165.0	3	CommScope - NNVV-65B-R4 - Panel	(3) Modified Sector Frame with (3) tie-back kit Sitepro SPTB, (3) v- brace kit Sitepro SFR-K- L & (6) new Pipe2.0STD	(4) 1-1/4" Fiber	Sprint Nextel
9		3	RFS - APXVTM14-C-I20 - Panel			
10		3	ALU 1900 Mhz RRU's			
11		6	ALU 800 Mhz RRU's			
12		3	ALU TD-RRH8x20-25 RRU's			

**Proposed Carrier’s Final Configuration of Antennas, Mounts and Transmission Lines**

Information pertaining to the proposed carrier’s final configuration of antennas and transmission lines was provided by SBA Communications Corp. The proposed antennas and lines are listed below.

Items	Elevation (ft)	Qty.	Antenna Descriptions	Mount Type & Qty.	Transmission Lines	Owner
14	125.0	3	CommScope - FFVV-65B-R2 - Panel	(3) MTC3975083	(1) 1.6" Hybrid	Dish Wireless
15		3	Fujitsu TA08025-B605			
16		3	Fujitsu TA08025-B604			
17		1	Raycap RDIDC-9181-PF-48 - OVP			

See the attached coax layout for the line placement considered in the analysis.

## **Analysis Results**

The results of the structural analysis, performed for the wind and ice loading and antenna equipment as defined above, are summarized as the following:

Tower Component	Legs	Diagonals	Horizontals	Guy Wires
Max. Usage:	<b>50.0%</b>	<b>28.1%</b>	<b>28.2%</b>	<b>43.0%</b>
Pass/Fail	<b>Pass</b>	<b>Pass</b>	<b>Pass</b>	<b>Pass</b>

## **Foundations**

Reactions (kips)	Base Reactions		Inner Anchors	
	Axial	Shear	Uplift	Shear
Analysis Reactions	137.8	1.9	50.6	47.0

The foundation has been investigated using the supplied documents and soils report and was found adequate. Therefore, no modification to the foundation will be required.

### **Service Load Condition (Rigidity):**

Operational characteristics of the tower are found to be within the limits prescribed by TIA-222 for the installed antennas. The maximum twist/sway at the elevation of the proposed equipment is 0.0135 degrees under the operational wind speed as specified in the Analysis Criteria.

### **Conclusions**

Based on the analysis results, the existing structure and its foundation were found to be adequate to safely support the existing and proposed equipment and meet the minimum requirements per the TIA-222 Standard under the design basic wind speed as specified in the Analysis Criteria.

## Standard Conditions

1. This analysis was performed based on the information supplied to **(TES) Tower Engineering Solutions, LLC**. Verification of the information provided was not included in the Scope of Work for **TES**. The accuracy of the analysis is dependent on the accuracy of the information provided.
2. The structural analysis was performance based upon the evidence available at the time of this report. All information provided by the client is considered to be accurate.
3. The analyses will be performed based on the codes as specified by the client or based on the best knowledge of the engineering staff of **TES**. In the absence of information to the contrary, all work will be performed in accordance with the latest relevant revision of ANSI/TIA-222. If wind speed and/or ice loads are different from the minimum values recommended by the ANSI/TIA-222 standard or other codes, **TES** should be notified in writing and the applicable minimum values provided by the client.
4. The configuration of the existing mounts, antennas, coax and other appurtenances were supplied by the customer for the current structural analysis. **TES** has not visited the tower site to verify the adequacy of the information provided. If there is any discrepancy found in the report regarding the existing conditions, **TES** should be notified immediately to evaluate the effect of the discrepancy on the analysis results.
5. The client will assume responsibility for rework associated with the differences in initially provided information, including tower and foundation information, existing and/or proposed equipment and transmission lines.
6. If a feasibility analysis was performed, final acceptance of changed conditions shall be based upon a rigorous structural analysis.

## Structure: CT10013-A-SBA

**Site Name:** Griswold Glasgo

**Code:** TIA-222-H

1/30/2023

**Type:** Guyed

**Base Shape:** Triangle

**Basic WS:** 130.00

**Height:** 195.00 (ft)

**Base Width:** 0.00

**Basic Ice WS:** 50.00

**Base Elev:** 0.00 (ft)

**Top Width:** 3.00

**Operational WS:** 60.00

Page: 1



### Section Properties

Sect	Leg Members	Diagonal Members	Horizontal Members
1-8	SOL 2" SOLID	SOL 7/8" SOLID	SOL 7/8" SOLID
9-11	SOL 1 3/4" SOLID	SOL 1" SOLID	SOL 1" SOLID

### Discrete Appurtenances


Attach Elev (ft)	Force Elev (ft)	Qty	Description
185.00	185.00	3	Sector Frames VFA12-HD
185.00	185.00	3	AIR6419 B41
185.00	185.00	3	APXVAALL24-43-U-NA20
185.00	185.00	3	RR90-17-XXDP
185.00	185.00	3	Ericsson KRY 112 489/2
185.00	185.00	6	Commscope CBC1923T-DS-43
185.00	185.00	3	Ericsson 4449 B71 + B85
185.00	185.00	3	Ericsson 4460 B25 + B66
185.00	185.00	3	Kathrein 782 11056
165.00	165.00	3	APXVTM14-C-I20
165.00	165.00	3	ALU 1900 Mhz RRUs
165.00	165.00	6	ALU 800 Mhz RRUs
165.00	165.00	3	ALU TD-RRH8x20-25 RRUs
165.00	165.00	3	Sector Frame
165.00	165.00	3	NNVV-65B-R4
125.00	125.00	3	FFVV-65B-R2
125.00	125.00	3	Fujitsu TA08025-B605
125.00	125.00	3	Fujitsu TA08025-B604
125.00	125.00	1	Raycap RDIDC-9181-PF-48
125.00	125.00	1	(3) MTC3975083

### Linear Appurtenances

Elev From (ft)	Elev To (ft)	Qty	Description
0.00	185.00	10	1 5/8" Coax
0.00	185.00	1	1.60" Hybrid
0.00	185.00	6	1.9" Fiber
0.00	165.00	4	1-1/4" Fiber
0.00	165.00	1	Safety Cable

### Max Guy Wire

43.01% @ 75.1667 ft - 11/16 BS



# Structure: CT10013-A-SBA

**Site Name:** Griswold Glasgo

**Code:** TIA-222-H

1/30/2023

**Type:** Guyed

**Base Shape:** Triangle

**Basic WS:** 130.00

**Height:** 195.00 (ft)

**Base Width:** 0.00


**Basic Ice WS:** 50.00

**Base Elev:** 0.00 (ft)

**Top Width:** 3.00

**Operational WS:** 60.00


Page: 2





## Anchor Drops with Guy Radius - Structure: CT10013-A-SBA

<b>Site Name:</b> Griswold Glasgo	<b>Code:</b> EIA_H	1/30/2023
<b>Type:</b> Guyed	<b>Base Shape:</b> Triangle	<b>Basic WS:</b> 130.00
<b>Height:</b> 195.00 (ft)	<b>Base Width:</b> 0.00	<b>Basic Ice WS:</b> 50.00
<b>Base Elev:</b> 0.00 (ft)	<b>Top Width:</b> 3.00	<b>Operational WS:</b> 60.00




# Structure: CT10013-A-SBA - Coax Line Placement

Type: Guyed  
Site Name: Griswold Glasgo  
Height: 195.00 (ft)

1/30/2023

Page: 4



## Analysis Summary

<b>Structure:</b> CT10013-A-SBA	<b>Code:</b> TIA-222-H	1/30/2023
<b>Site Name:</b> Griswold Glasgo	<b>Exposure:</b> C	
<b>Height:</b> 195.00 (ft)	<b>Crest Height:</b> 0.00	
<b>Base Elev:</b> 0.000 (ft)	<b>Site Class:</b> D - Default	
<b>Gh:</b> 0.85	<b>Topography:</b> 1	<b>Struct Class:</b> II
		<b>Page:</b> 22



### Max Reactions

Base:	137.78 (Vertical)	1.90 (Horizontal)
Anchor 1:	50.62 (Vertical)	47.04 (Horizontal)

### Max Usages

Max Leg: 50.0% (1.2D + 1.0W 60° Wind - Sect 8)  
 Max Diag: 28.1% (1.2D + 1.0Di + 1.0Wi 90° Wind - Sect 1)  
 Max Horiz: 28.2% (1.2D + 1.0Di + 1.0Wi Normal Wind - Sect 1)  
 Max Cable: 43.0% (1.2D + 1.0W 60° Wind) - Elev: 75 ft

### Max Deflection, Twist and Sway

Load Case	Elevation (ft)	Deflection (ft)	Twist (deg)	Sway (deg)
0.9D + 1.0Ev + 1.0Eh - Normal To Face	125.50	0.0146	0.0000	0.0075
	165.50	0.0186	0.0000	0.0179
	184.78	0.0212	0.0001	0.0096
0.9D + 1.0W 130 mph Wind at 60° From Face	125.50	0.4364	0.0019	0.0259
	165.50	0.3998	0.0013	0.1394
	184.78	0.3474	0.0016	0.1657
0.9D + 1.0W 130 mph Wind at 90° From Face	125.50	0.5137	0.0714	0.0295
	165.50	0.4276	0.0641	0.2580
	184.78	0.3517	0.0603	0.2601
0.9D + 1.0W 130 mph Wind at Normal To Face	125.50	0.5526	-0.0023	0.0347
	165.50	0.4438	-0.0020	0.3092
	184.78	0.3458	0.0013	0.3067
1.0D + 1.0W 60 mph Wind at 60° From Face	125.50	0.0709	0.0003	0.0077
	165.50	0.0576	0.0001	0.0382
	184.78	0.0446	0.0003	0.0410
1.0D + 1.0W 60 mph Wind at 90° From Face	125.50	0.0687	0.0031	0.0112
	165.50	0.0529	0.0013	0.0512
	184.78	0.0394	0.0033	0.0444
1.0D + 1.0W 60 mph Wind at Normal To Face	125.50	0.0665	-0.0003	0.0135
	165.50	0.0483	0.0001	0.0573
	184.78	0.0333	-0.0003	0.0471
1.2D + 1.0Di + 1.0Wi 50 mph Wind at 60° From Face	125.50	0.0902	0.0004	0.0192
	165.50	0.0619	0.0002	0.0717
	184.78	0.0376	0.0005	0.0755
1.2D + 1.0Di + 1.0Wi 50 mph Wind at 90° From Face	125.50	0.0809	0.0110	0.0362
	165.50	0.0465	0.0057	0.1054
	184.78	0.0314	0.0131	0.0953
1.2D + 1.0Di + 1.0Wi 50 mph Wind at Normal From Face	125.50	0.0704	0.0004	0.0465
	165.50	0.0191	0.0003	0.1243
	184.78	0.0172	0.0004	0.1115
1.2D + 1.0Ev + 1.0Eh - Normal To Face	125.50	0.0146	0.0000	0.0076
	165.50	0.0187	0.0000	0.0181
	184.78	0.0213	-0.0001	0.0097

1.2D + 1.0W 130 mph Wind at 60° From Face	125.50	0.4383	0.0019	0.0264
	165.50	0.4017	0.0013	0.1395
	184.78	0.3492	0.0016	0.1663
-----				
1.2D + 1.0W 130 mph Wind at 90° From Face	125.50	0.5180	0.0723	0.0299
	165.50	0.4309	0.0650	0.2605
	184.78	0.3544	0.0613	0.2622
-----				
1.2D + 1.0W 130 mph Wind at Normal To Face	125.50	0.5578	0.0023	0.0350
	165.50	0.4481	0.0020	0.3118
	184.78	0.3494	-0.0013	0.3090
-----				



Tower Engineering Solutions

# Guyed Tower Base Design

Date

1/30/2023

<b>Customer Name:</b>	SBA Communications Corp	<b>TIA Standard:</b>	TIA-222-H
<b>Site Name:</b>		<b>Structure Height (Ft.):</b>	195
<b>Site Nmber:</b>	CT10013-A-SBA	<b>Engineer Name:</b>	H. You
<b>Engr. Number:</b>	138175	<b>Engineer Login ID:</b>	

**Foundation Info Obtained from:**

Drawings/Calculations

**Structure Type:**

Guyed Tower

**Analysis or Design?**

Analysis

**Base Reactions (Factored):**


Axial Load (Kips):	137.8	Shear Force (Kips):	1.9
Uplift Force (Kips):	0.0	Moment (Kips-ft):	
Allowable overstress %:	5.0%		

**Foundation Geometries:**

		Mods required -Yes/No ?:	No
Diameter of Pier (ft.):	2.0	Depth of Base BG (ft.):	4.5
Pier Height A. G. (ft.):	0.50	Thickness of Pad (ft):	6.00
Length of Pad (ft.):	6	Width of Pad (ft.):	6
Final Length of pad (ft)	6.0	Final width of pad (ft):	6.0

**Material Properties and Reabr Info:**

Concrete Strength (psi):	4500	Steel Elastic Modulus:	29000	ksi
Vertical bar yield (ksi)	60	Tie steel yield (ksi):	36	
Vertical Rebar Size #:	7	Tie / Stirrup Size #:	3	
Qty. of Vertical Rebars:	10	Tie Spacing (in):	6.0	
Pad Rebar Yield (Ksi):	60	Pad Steel Rebar Size (#):	6	
Concrete Cover (in.):	3	Unit Weight of Concrete:	150.0	pcf
Rebar at the bottom of the concrete pad:				
Qty. of Rebar in Pad (L):	8	Qty. of Rebar in Pad (W):	8	



**Soil Design Parameters:**

Soil Unit Weight (pcf):	115.0	Soil Buoyant Weight:	50.0	Pcf	
Water Table B.G.S. (ft):	99.0	Unit Weight of Water:	62.4	pcf	Angle from Top of Pad: 30
Ultimate Bearing Pressure (psf):	30000	Ultimate Skin Friction:	0	Psf	Angle from Bottm of Pad: 30
					Angle from Bottm of Pad: 25

**Foundation Analysis and Design:**

Uplift Strength Reduction Factor:	0.75	Compression Strength Reduction Factor:	0.6
Total Dry Soil Volume (cu. Ft.):	-49.29	Total Dry Soil Weight (Kips):	-5.67
Total Buoyant Soil Volume (cu. Ft.):	0.00	Total Buoyant Soil Weight (Kips):	0.00
Total Effective Soil Weight (Kips):	-5.67	Weight from the Concrete Block at Top (K):	0.00
Total Dry Concrete Volume (cu. Ft.):	212.86	Total Dry Concrete Weight (Kips):	31.93
Total Buoyant Concrete Volume (cu. Ft.):	0.00	Total Buoyant Concrete Weight (Kips):	0.00
Total Effective Concrete Weight (Kips):	31.93	Total Vertical Load on Base (Kips):	164.04

**Check Soil Capacities:**

Calculated Maxium Net Soil Pressure under the base (psf):	4175.4	<	Allowable Factored Soil Bearing (psf):	18000	0.23	OK!
Calculated Foundation Allowable Axail Capacity (Kips):	648.0	>	Design Factored Axial Load (Kips):	147	0.23	OK!

Load/  
Capacity  
Ratio

**Check the capacities of Reinforcing Concrete:**

Strength reduction factor (Flexure and axial tension):	0.90	Strength reduction factor (Shear):	0.75
Strength reduction factor (Axial compression):	0.65	Wind Load Factor on Concrete Design:	1.00


Load/  
Capacity  
Ratio

(1) Concrete Pier:

Vertical Steel Rebar Area (sq. in./each):	0.60	Tie / Stirrup Area (sq. in./each):	0.11		
Calculated Moment Capacity (Mn,Kips-Ft):	227.0	> Design Factored Moment (Mu, Kips-Ft)	-1.9	-0.01	OK!
Calculated Shear Capacity (Kips):	70.9	> Design Factored Shear (Kips):	1.9	0.03	OK!
Calculated Tension Capacity (Tn, Kips):	324.0	> Design Factored Tension (Tu Kips):	0.0	0.00	OK!
Calculated Compression Capacity (Pn, Kips):	887.9	> Design Factored Axial Load (Pu Kips):	137.8	0.16	OK!
Moment & Axial Strength Combination(Pu/Pn+Mu/Mn):	0.15	OK!			
Pier Reinforcement Ratio:	0.013				

(2).Concrete Pad:

One-Way Design Shear Capacity (L-Dir. Kips);	497.2	> One-Way Factored Shear (L-Dir Kips):	0.0	0.00	OK!
One-Way Design Shear Capacity (W-Dir. Kips):	497.2	> One-Way Factored Shear (W-Dir Kips)	0.0	0.00	OK!
Two-Way Design Shear Capacity (Kips):	4018.7	> Two-Way Factored Shear (Kips):	0.0	0.00	OK!
Lower Steel Pad Reinforcement Ratio (L-Direct. ):	0.0007	OK!	Lower Steel Pad Reinf. Ratio (W-Direc	0.0007	OK!
Lower Steel Pad Moment Capacity (L-Direction. Kips-ft):	1080.8	> Moment at Bottom ( L-Direct. K-Ft):	48.5	0.04	OK!
Lower Steel Pad Moment Capacity (W-Dir. Kips-ft):	1080.8	> Moment at Bottom ( W-Dir. Kips-Ft):	48.5	0.04	OK!

	Guy Anchor Analysis and Design			Date
				1/30/2023
	Customer Name:	SBA Communications Corp	TIA Standard:	EIA-222-H
	Site Name:	0	Structure Height (Ft.):	195
	Site Number:	CT10013-A-SBA	Engineer Name:	H. You
Engr. Number:	138175	Engineer Login ID:		

**Foundation Info Obtained from:** Drawings/Calculations      **Number of Anchors:** 1 Set      Failure model: New

**Soil Design Parameters:**

Soil Unit Weight (pcf):	125.0	Soil Buoyant Weight:	65.0	Pcf	Cohesion of Soils (psf):	2100
		Unit Weight of Water:	62.4	pcf	Internal Angle of Friction (°)	0
Ultimate lateral pressure (psf):	0	Ultimate Skin Friction:	200	Psf	Coefficient of Shear Friction:	0.30
Conical Failure Angle from Top:	30	Failure Angle from Bottom:	20			

**Material Properties:**

Concrete Strength (psi):	3000	Unit Weight of Concrete:	150.0	psf	Horizontal Rebar Yield (psi):	60000
Shear Strength Reduction Factor:	0.75				Flexure Strength Reduction Factor:	0.9

**A. Inner Anchors:**

Radius (ft.): 137

**1. Design Reactions (Factored):**


Uplift (Kips): 50.6      Shear (Kips): 47.0      Angle of force resultant (∅): 47.1

**2. Foundation Geometries:**

Block Base Depth B.G.S. (ft):	13.0	Block with/without toe?	No	Water Table below grade (ft):	99.00
Length of Anchor Block (L, ft.):	14.0	Width of Anchor Block:	4.0 ft.	Thickness of Anchor Block (ft.):	4.0
Concrete Block @ top of Anchor?	No				

**(1). Inner Anchors:**

Radius (ft.):	137
H (ft.):	13.0
L (ft.):	14.0
T (ft.):	4.0
S (ft.):	18.43
Angle (∅):	47.1
Top bars:	4 # 9
Front bars:	4 # 9
Concrete Volume (Cu. Yd.)/Each:	8.30



**3. Foundation Analysis and Design:**

Total Dry Soil Volume (cu. Ft.):	1600.25	Total Dry Soil Weight (Kips):	239.50
Total Buoyant Soil Volume (cu. Ft.):	0.00	Total Buoyant Soil Weight (Kips):	0.00
Total Effective Soil Weight (Kips):	200.03	Weight of the Concrete Block at Top (Kips):	0.00
Total Dry Concrete Volume (cu. Ft.):	224.00	Total Dry Concrete Weight (Kip):	33.60
Total Buoyant Concrete Volume (cu. Ft.):	0.00	Total Buoyant Concrete Weight (Kips):	0.00
Total Effective Concrete Weight (Kips):	33.60	Weight Reduction Factor:	0.9
Soil Uplift Strength Reduction Factor A:	0.75	Shear Strength Reduction Factor:	0.75
Soil Uplift Strength Reduction Factor B:	0.9		

**4. Check Soil and Foundation Capacities:**

Nominal Factored Uplift Resistance:	189.71	Kips > Design Uplift Force (Kips):	50.6	OK!
Ultimate Shear Friction Resistance at base:	20.43	Kips Ultimate Resistance Pressure:	5575.0	Psf
Factored Shear Resistance:	254.27	Kips > Design Shear Force (Kips):	47.0	OK!

**5. Design Concrete Block:**

Rebar Size (#):	9	Wind Load Factor on Concrete Design:	1.00	
Qty. of the Rebar at top of the block:	4	Qty. of the Rebar in the front of the block:	4	
Area of Single Rebar (sq. in.):	1.00	Factor for concrete compression zone:	0.85	
One Way Shear due to Shear Force (Kips):	23.5	One Way Shear Capacity for shear (kips):	173.5	OK!
One Way Shear due to Uplift (Kips):	25.3	One Way Shear Capacity for uplift (kips):	173.5	OK!
Moment due to Shear Load ( Kips-ft):	82.3	Flexural Capacity for Shear Load (Kips-ft):	791.6	OK!
Moment due to uplift Load ( Kips-ft):	88.6	Flexural Capacity for uplift Load (Kips-ft):	791.6	OK!
Ratio of Design Moment/Moment capacity:	0.11	Minimum ratio of rebar (top & front) :	0.27	OK!
Max. Ratio of Shear Force/Shear capacity:	0.15	OK!		

0.0

0.0





# Exhibit E

## **Mount Analysis**



January 23, 2023

Dave Evans  
SBA Network Services, LLC.  
134 Flanders Road, Suite 125  
Westborough, MA 01581  
(508) 251-0720 x 3805

MTS Engineering, P.L.L.C.  
1717 S. Boulder, Suite 300  
Tulsa, OK 74119  
(918) 587- 4630  
btwo@btgrp.com

**Subject:** **Appurtenance Mount Analysis Report**

**Carrier Designation:** **Dish Co-Locate**  
**Site Number:** BOBOS00051A  
**Site Name:** SBA - Glasgo Road

**SBA Network Services Designation:** **Site Number:** CT10013-A  
**Site Name:** Griswold Glasgo  
**Application Number:** 174044, v1

**Engineering Firm Designation:** **Project Number:** 149453.004.01

**Site Data:** **2172 Glasgo Road, Jewett City, CT, 06351, New London County**  
**Latitude 41.53736°, Longitude -71.87344°**  
**Guyed Tower**  
**(3) 8 ft. Sector Mount**

Dear Mr. Evans,

B+T Group is pleased to submit this “**Appurtenance Mount Analysis Report**” to determine the structural integrity of the antenna mount on the above-mentioned structure.

The purpose of the analysis is to determine acceptability of the mount’s stress level. Based on our analysis we have determined the stress level for the mount under the following load case to be:

Proposed Equipment	<b>Sufficient Capacity</b>
Note: See Table 1 for the final loading configuration	<b>(Passing at 48.7%)</b>


This analysis utilizes an ultimate 3-second gust wind speed of 126 mph as required by the 2022 Connecticut State Building Code. Applicable Standard references and design criteria are listed in Section 2 - Analysis Criteria.

All the equipment proposed in this report shall be installed in accordance with the drawings for the determined available structural capacity to be effective.

We at B+T Group appreciate the opportunity of providing our continuing professional services to you and SBA Network Services, LLC. If you have any questions or need further assistance on this or any other projects, please give us a call.

Mount structural analysis prepared by: Erika Ruiz

Respectfully submitted by: B&T Engineering, Inc.  
COA: BER:2386985 Expires: 03/31/2023



Chad E. Tuttle, P.E.

## TABLE OF CONTENTS

### 1) INTRODUCTION

### 2) ANALYSIS CRITERIA

Table 1 – Proposed Equipment Information

Table 2 – Documents Provided

### 3) ANALYSIS PROCEDURE

3.1) Analysis Method

3.2) Assumptions

### 4) ANALYSIS RESULTS

Table 3 – Mount Component Stresses vs. Capacity

### 5) RECOMMENDATIONS

### 6) APPENDIX A

RISA-3D Output

### 7) APPENDIX B

Additional Calculations

## 1) INTRODUCTION

The appurtenance mount consists of sector mount designed by Commscope (Part #MTC3975083) at 125 ft., attached to guyed tower at 2172 Glasgo Road, Jewett City, CT, 06351, New London County. The proposed antenna loading information was obtained from SBA Network Services, LLC. All information provided to B+T Group was assumed accurate and complete.

## 2) ANALYSIS CRITERIA

The structural analysis was performed for this mount in accordance with the ANSI/TIA-222-H-2017 Structural Standard for Antenna Supporting Structures and Antennas and Small Wind Turbine Support Structures using a 3-second gust wind speed of 126 mph with no ice and 50 mph with 1 inch escalated ice thickness. Exposure Category C & Topographic Category 1 and Risk Category II were used in this analysis. In addition, the platform mount has been analyzed for various live loading conditions consisting of a 250-lb man live load applied individually at the midpoint and cantilevered ends of horizontal members as well as a 500-pound man live load applied individually at mount pipe locations using a 3-second gust of 30 mph. The mount was analyzed under 30° increments in the wind direction. The analyzed loading is detailed in Table 1.

**Table 1 – Proposed Equipment Information**

Loading	RAD Center Elev. (ft.)	Position	Qty.	Description	Note
Proposed	125	2	3	Commscope FFVV-65B-R2	1
			3	FUJITSU TA08025-B605	2
			3	FUJITSU TA08025-B604	
		-	1	Raycap RDIDC-9181-PF-48	3

Note:

- (1) Proposed Antenna to be installed on the Proposed Mount Pipe.
- (2) Proposed Equipment to be installed directly behind the Antenna.
- (3) Proposed Equipment to be installed on the mount.

**Table 2 – Documents Provided**

Documents	Remarks	Reference	Source
RFDS	Proposed Loading	Date: 09/27/2021	SBA Network Services, LLC.
Collo App		Date: 11/15/2021	

## 3) ANALYSIS PROCEDURE

### 3.1) Analysis Method

RISA-3D (Version 19.0.4), a commercially available analysis software package, was used to create a three-dimensional model of the mount and calculate member stresses and deflections for various loading cases. Selected output from the analysis is included in Appendix A.

Manufacturers drawing were used to create the model.

### 3.2) Assumptions

1. The mount was built in accordance with the manufacturer's specifications.
2. The mount has been maintained in accordance with the manufacturer's specifications and is free of damage.
3. The configuration of antennas and other appurtenances are as specified in Table 1.
4. All mount components have been assumed to be in sufficient condition to carry their full design capacity for the analysis.
5. Mount area and weights are determined from field measurements, standard material properties, and/or manufacturer product data.

6. Serviceability with respect to antenna twist, tilt, roll, or lateral translation is not checked and is left to the carrier or tower owner to ensure conformance.
7. All prior structural modifications if any are assumed to be correctly installed and fully effective.
8. All member connections are assumed to have been designed to meet or exceed the load carrying capacity of the connected member unless otherwise specified in this report.
9. The following material grades were assumed (Unless Noted Otherwise):
  - a) Connection Bolts : ASTM A325
  - b) Steel Pipe : ASTM A53 (GR. 35)
  - c) HSS (Round) : ASTM 500 (GR. B-42)
  - d) HSS (Rectangular) : ASTM 500 (GR. B-46)
  - e) Channel : ASTM A36 (GR. 36)
  - f) Steel Solid Rod : ASTM A36 (GR. 36)
  - g) Steel Plate : ASTM A36 (GR. 36)
  - h) Steel Angle : ASTM A36 (GR. 36)
  - i) UNISTRUT : ASTM A570 (GR. 33)

This analysis may be affected if any assumptions are not valid or have been made in error. B+T Group should be notified to determine the effect on the structural integrity of the antenna mounting system.

#### 4) ANALYSIS RESULTS

**Table 3 – Mount Component Stresses vs. Capacity**

Notes	Component	Elevation (ft.)	% Capacity	Pass / Fail
-	Face Horizontals	125	10.8	Pass
-	Support Arms	125	24.6	Pass
-	Diagonals	125	26.6	Pass
-	Connection Plates	125	22.0	Pass
-	Verticals	125	48.7	Pass
-	Tiebacks	125	5.8	Pass
-	Mount Pipes	125	19.0	Pass
	Bolt Connection	125	15.3	Pass

#### 5) RECOMMENDATIONS





The Commscope sector mount, Part #MTC3975083 has sufficient capacity to carry the proposed loads and is in compliance with the ANSI/TIA-222-H standard for the proposed loading. (Refer to the RISA output for the specific members).

**Site Soil Class:** D - Default (see Section 11.4.3)

**Results:**

$S_s$ :	0.188	$S_{D1}$ :	0.085
$S_1$ :	0.053	$T_L$ :	6
$F_a$ :	1.6	PGA :	0.103
$F_v$ :	2.4	PGA <sub>M</sub> :	0.164
$S_{MS}$ :	0.3	$F_{PGA}$ :	1.595
$S_{M1}$ :	0.128	$I_e$ :	1
$S_{DS}$ :	0.2	$C_v$ :	0.7

**Seismic Design Category** B



**Data Accessed:**

Wed Nov 17 2021

**Date Source:**

USGS Seismic Design Maps based on ASCE/SEI 7-16 and ASCE/SEI 7-16 Table 1.5-2. Additional data for site-specific ground motion procedures in accordance with ASCE/SEI 7-16 Ch. 21 are available from USGS.

## Ice

---

### Results:

Ice Thickness: 1.00 in.

Concurrent Temperature: 15 F

Gust Speed: 50 mph

**Data Source:** Standard ASCE/SEI 7-16, Figs. 10-2 through 10-8

**Date Accessed:** Wed Nov 17 2021

Ice thicknesses on structures in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.

Values provided are equivalent radial ice thicknesses due to freezing rain with concurrent 3-second gust speeds, for a 500-year mean recurrence interval, and temperatures concurrent with ice thicknesses due to freezing rain. Thicknesses for ice accretions caused by other sources shall be obtained from local meteorological studies. Ice thicknesses in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.

---

The ASCE 7 Hazard Tool is provided for your convenience, for informational purposes only, and is provided “as is” and without warranties of any kind. The location data included herein has been obtained from information developed, produced, and maintained by third party providers; or has been extrapolated from maps incorporated in the ASCE 7 standard. While ASCE has made every effort to use data obtained from reliable sources or methodologies, ASCE does not make any representations or warranties as to the accuracy, completeness, reliability, currency, or quality of any data provided herein. Any third-party links provided by this Tool should not be construed as an endorsement, affiliation, relationship, or sponsorship of such third-party content by or from ASCE.

ASCE does not intend, nor should anyone interpret, the results provided by this Tool to replace the sound judgment of a competent professional, having knowledge and experience in the appropriate field(s) of practice, nor to substitute for the standard of care required of such professionals in interpreting and applying the contents of this Tool or the ASCE 7 standard.

In using this Tool, you expressly assume all risks associated with your use. Under no circumstances shall ASCE or its officers, directors, employees, members, affiliates, or agents be liable to you or any other person for any direct, indirect, special, incidental, or consequential damages arising from or related to your use of, or reliance on, the Tool or any information obtained therein. To the fullest extent permitted by law, you agree to release and hold harmless ASCE from any and all liability of any nature arising out of or resulting from any use of data provided by the ASCE 7 Hazard Tool.

# Exhibit F

## **Power Density/RF Emissions Report**





# Radio Frequency Emissions Analysis Report



**Site ID: BOBOS00051A**

SBA - Glasgo Road  
2172 Glasgo Road  
Jewett City, CT 06351

**January 7, 2023**

**Fox Hill Telecom Project Number: 222141**

Site Compliance Summary	
Compliance Status:	<b>COMPLIANT</b>
Site total MPE% of FCC general population allowable limit:	<b>4.19 %</b>

January 7, 2023

Dish Wireless  
5701 South Santa Fe Drive  
Littleton, CO 80120

### Emissions Analysis for Site: **BOBOS00051A – SBA - Glasgo Road**

Fox Hill Telecom, Inc (“Fox Hill”) was directed to analyze the proposed radio installation for Dish Wireless, LLC (Dish) facility located at **2172 Glasgo Road, Jewett City, CT**, for the purpose of determining whether the emissions from the Proposed Dish radio and antenna installation located on this property are within specified federal limits.

All information used in this report was analyzed as a percentage of current Maximum Permissible Exposure (% MPE) as listed in the FCC OET Bulletin 65 Edition 97-01 and ANSI/IEEE Std C95.1. The FCC regulates Maximum Permissible Exposure in units of microwatts per square centimeter ( $\mu\text{W}/\text{cm}^2$ ). The number of  $\mu\text{W}/\text{cm}^2$  calculated at each sample point is called the power density. The exposure limit for power density varies depending upon the frequencies being utilized. Wireless Carriers and Paging Services use different frequency bands each with different exposure limits, therefore it is necessary to report results and limits in terms of percent MPE rather than power density.

All results were compared to the FCC (Federal Communications Commission) radio frequency exposure rules, 47 CFR 1.1307(b)(1) – (b)(3), to determine compliance with the Maximum Permissible Exposure (MPE) limits for General Population/Uncontrolled environments as defined below.

General population/uncontrolled exposure limits apply to situations in which the general population may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Therefore, members of the general population would always be considered under this category when exposure is not employment related, for example, in the case of a telecommunications tower that exposes persons in a nearby residential area.

Population exposure to radio frequencies is regulated and enforced in units of microwatts per square centimeter ( $\mu\text{W}/\text{cm}^2$ ). The general population exposure limit for the 600 MHz band is approximately  $400 \mu\text{W}/\text{cm}^2$ . The general population exposure limit for the 1900 MHz (PCS) and 2100 MHz (AWS / AWS-4) bands is  $1000 \mu\text{W}/\text{cm}^2$ . Because each carrier will be using different frequency bands, and each frequency band has different exposure limits, it is necessary to report percent of MPE rather than power density.



Occupational/controlled exposure limits apply to situations in which persons are exposed as a consequence of their employment and in which those persons who are exposed have been made fully aware of the potential for exposure and can exercise control over their exposure. Occupational/controlled exposure limits also apply where exposure is of a transient nature as a result of incidental passage through a location where exposure levels may be above general population/uncontrolled limits (see below), as long as the exposed person has been made fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Additional details can be found in FCC OET 65.

## CALCULATIONS

Calculations were performed for the proposed upgrades to the Dish Wireless antenna facility located at **2172 Glasgo Road, Jewett City, CT**, using the equipment information listed below. All calculations were performed per the specifications under FCC OET 65 for far field modeling calculations.

In OET-65, plane wave power densities in the Far Field of an antenna are calculated by considering antenna gain and reflective waves that would contribute to exposure.

Since the radiation pattern of an antenna has developed in the **Far Field** region the power gain in specific directions needs to be considered in exposure predictions to yield an Effective Radiated Power (ERP) in each specific direction from the antenna. Also, since the vertical radiation pattern of the antenna is considered, the exposure calculations would most likely be reduced significantly at ground level, resulting in a more realistic estimate of the actual exposure levels. To determine a worst-case scenario at each point along the calculation radials, each point was calculated using the antenna gain value at each angle of incident and compared against the result using an isotropic radiator at the antenna height with the greater of the two used to yield the more pessimistic far field value for each point along the calculation radial.

Additionally, to model a truly "worst case" prediction of exposure levels at or near a surface, such as at ground-level or on a rooftop, reflection off the surface of antenna radiation power can be assumed, resulting in a potential 1.6 times increase in power density in calculating far field power density values.

With these factors Considered, the worst case **Far Field prediction model** utilized in this analysis is determined by the following equation:

Equation 9 per FCC OET65 for Far Field Modeling

$$S = \frac{33.4 \text{ ERP}}{R^2}$$

S = Power Density (in  $\mu\text{w}/\text{cm}^2$ )

ERP = Effective Radiated Power from antenna (watts)

R = Distance from the antenna (meters)

Predicted far field power density values for all carriers identified in this report were calculated 6 feet above the ground level and are displayed as a percentage of the applicable FCC standards. All emissions values for other carriers were calculated using the same Far Field model outlined above, using industry standard radio configurations and frequency band selection based upon available licenses in this geographic area for emissions contribution estimates.

For each Dish sector the following channel counts, frequency bands and power levels were utilized as shown in *Table 1*:

Technology	Frequency Band	Channel Count	Transmit Power per Channel (W)
5G	n71 (600 MHz)	4	61.5
5G	n70 (AWS-4 / 1995-2020)	4	40
5G	n66 (AWS-4 / 2180-2200)	4	40

*Table 1: Channel Data Table*



The following **Dish** antennas listed in *Table 2* were used in the modeling for transmission in the 600 MHz (n71) frequency band and the 2100 MHz (AWS 4) frequency bands at 1995-2020 MHz (n70) and 2180-2200 MHz (n66). This is based on feedback from Dish regarding anticipated antenna selection. Maximum gain values for all antennas are listed in the Inventory and Power Data table below.

Sector	Antenna Number	Antenna Make / Model	Antenna Centerline (ft)
A	1	Commscope FFVV-65B-R2	125
B	1	Commscope FFVV-65B-R2	125
C	1	Commscope FFVV-65B-R2	125

*Table 2: Antenna Data*

All calculations were done with respect to uncontrolled / general population threshold limits.



## RESULTS

Per the calculations completed for the proposed **Dish** configurations *Table 3* shows resulting emissions power levels and percentages of the FCC’s allowable general population limit.

Antenna ID	Antenna Make / Model	Frequency Bands	Antenna Gain (dBd)	Channel Count	Total TX Power (W)	ERP (W)	MPE %
Antenna A1	Commscope FFVV-65B-R2	n71 (600 MHz) / n70 (AWS-4 / 1995-2020) / n66 (AWS-4 / 2180-2200)	12.15 / 15.95 / 16.25	12	566	17,079.80	2.41
Sector A Composite MPE%							<b>2.41</b>
Antenna B1	Commscope FFVV-65B-R2	n71 (600 MHz) / n70 (AWS-4 / 1995-2020) / n66 (AWS-4 / 2180-2200)	12.15 / 15.95 / 16.25	12	566	17,079.80	2.41
Sector B Composite MPE%							<b>2.41</b>
Antenna C1	Commscope FFVV-65B-R2	n71 (600 MHz) / n70 (AWS-4 / 1995-2020) / n66 (AWS-4 / 2180-2200)	12.15 / 15.95 / 16.25	12	566	17,079.80	2.41
Sector C Composite MPE%							<b>2.41</b>

*Table 3: Dish Emissions Levels*



The Following table (*Table 4*) shows all additional carriers on site and their emissions contribution estimates, along with the newly calculated **Dish** far field emissions contributions per this report. FCC OET 65 specifies that for carriers utilizing directional antennas that the highest recorded sector value be used for composite site emissions values due to their greatly reduced emissions contributions in the directions of the adjacent sectors. For this site, all three sectors have the same configuration yielding the same results on all three sectors. *Table 5* below shows a summary for each **Dish** Sector as well as the composite emissions value for the site.

<b>Site Composite MPE%</b>	
<b>Carrier</b>	<b>MPE%</b>
Dish – Max Per Sector Value	<b>2.41 %</b>
T-Mobile	0.88 %
Sprint	0.90 %
<b>Site Total MPE %:</b>	<b>4.19 %</b>

*Table 4: All Carrier MPE Contributions*

Dish Sector A Total:	2.41 %
Dish Sector B Total:	2.41 %
Dish Sector C Total:	2.41 %
<b>Site Total:</b>	
	4.19 %

*Table 5: Site MPE Summary*





Table 6 below details a breakdown by frequency band and technology for the MPE power values for the maximum calculated **Dish** sector(s). For this site, all three sectors have the same configuration yielding the same results on all three sectors.

Dish _ Frequency Band / Technology Max Power Values (Per Sector)	# Channels	Watts ERP (Per Channel)	Height (feet)	Total Power Density ( $\mu\text{W}/\text{cm}^2$ )	Frequency (MHz)	Allowable MPE ( $\mu\text{W}/\text{cm}^2$ )	Calculated % MPE
Dish n71 (600 MHz) 5G	4	1,008.96	125	6.36	n71 (600 MHz)	400	1.59%
Dish n70 (AWS-4 / 1995-2020) 5G	4	1,574.20	125	4.10	n70 (AWS-4 / 1995-2020)	1000	0.41%
Dish n66 (AWS-4 / 2180-2200) 5G	4	1,686.79	125	4.10	n66 (AWS-4 / 2180-2200)	1000	0.41%
						<b>Total:</b>	<b>2.41 %</b>

Table 6: Dish Maximum Sector MPE Power Values

## Summary

All calculations performed for this analysis yielded results that were **within** the allowable limits for general population exposure to RF Emissions.

The anticipated maximum composite contributions from the Dish facility as well as the site composite emissions value with regards to compliance with FCC's allowable limits for general population exposure to RF Emissions are shown here:

Dish Sector	Power Density Value (%)
Sector A:	2.41 %
Sector B:	2.41 %
Sector C:	2.41 %
Dish Maximum Total (per sector):	2.41 %
Site Total:	4.19 %
Site Compliance Status:	<b>COMPLIANT</b>

The anticipated composite emissions value for this site, assuming all carriers present, is **4.19 %** of the allowable FCC established general population limit sampled at the ground level. This is based upon the far field calculations performed for all carriers identified in this report.

FCC guidelines state that if a site is found to be out of compliance (over allowable thresholds), that carriers over a 5% contribution to the composite value will require measures to bring the site into compliance. For this facility, the composite values calculated were well within the allowable 100% threshold standard per the federal government.



Scott Heffernan  
Principal RF Engineer  
**Fox Hill Telecom, Inc**  
Worcester, MA 01609  
(978)660-3998

# Exhibit G

## **Letter of Authorization**

## SBA Letter of Authorization

CT - CONNECTICUT SITING COUNCIL

Melanie A. Bachman

Executive Director

Connecticut Siting Council

10 Franklin Square

New Britain, CT 06051

Re: Tower Share Application

SBA COMMUNICATIONS CORPORATION hereby authorizes DISH Wireless LLC, including their Agent, to act as our Agent in the processing of all zoning applications, building permits and approvals through the CONNECTICUT SITING COUNCIL for existing wireless communications towers.


SBA COMMUNICATIONS CORPORATION

134 Flanders Road, Suite 125

Westboro, MA 01581

# Exhibit H


## Recipient Mailings



**USPS TRACKING #**

**9405 5036 9930 0482 2527 81**

Electronic Rate Approved #038555749



SBA COMMUNICATIONS CORPORATION  
STE 125  
13 FLANDERS RD  
WESTBOROUGH MA 01581

**P**

USPS.com 9405 5036 9930 0482 2527 81 0096 5000 0010 1581  
**US POSTAGE \$9.65**  
 Flat Rate Env  
**U.S. POSTAGE PAID**  
 Click-N-Ship®

Mailed from 01566 986765594771027

**PRIORITY MAIL®**

DEBORAH CHASE  
NORTHEAST SITE SOLUTIONS  
STE 1  
420 MAIN ST  
STURBRIDGE MA 01566-1359

Expected Delivery Date: 02/17/23  
 Ref#: SBDS-00051  
**0000**

**R005**

✂ ————— Cut on dotted line. —————

### Instructions

1. Each Click-N-Ship® label is unique. Labels are to be used as printed and used only once. DO NOT PHOTO COPY OR ALTER LABEL.
2. Place your label so it does not wrap around the edge of the package.
3. Adhere your label to the package. A self-adhesive label is recommended. If tape or glue is used, DO NOT TAPE OVER BARCODE. Be sure all edges are secure.
4. To mail your package with PC Postage®, you may schedule a Package Pickup online, hand to your letter carrier, take to a Post Office™, or drop in a USPS collection box.
5. Mail your package on the "Ship Date" you selected when creating this label.

### Click-N-Ship® Label Record


**USPS TRACKING # :**  
**9405 5036 9930 0482 2527 81**


Trans. #: 582816277	Priority Mail® Postage: <b>\$9.65</b>
Print Date: 02/16/2023	Total: <b>\$9.65</b>
Ship Date: 02/16/2023	
Expected Delivery Date: 02/17/2023	

**From:** DEBORAH CHASE      Ref#: SBDS-00051  
 NORTHEAST SITE SOLUTIONS  
 STE 1  
 420 MAIN ST  
 STURBRIDGE MA 01566-1359

**To:** SBA COMMUNICATIONS CORPORATION  
 STE 125  
 13 FLANDERS RD  
 WESTBOROUGH MA 01581

\* Retail Pricing Priority Mail rates apply. There is no fee for USPS Tracking® service on Priority Mail service with use of this electronic rate shipping label. Refunds for unused postage paid labels can be requested online 30 days from the print date.



 Thank you for shipping with the United States Postal Service!  
 Check the status of your shipment on the USPS Tracking® page at [usps.com](https://usps.com)



**USPS TRACKING #**

**9405 5036 9930 0482 2528 42**

Electronic Rate Approved #038555749



DANA BENNETT  
FIRST SELECTMAN-JEWETT CITY  
28 MAIN ST  
JEWETT CITY CT 06351-2204

**P**

USPS.com 9405 5036 9930 0482 2528 42 0096 5000 0010 6351  
**US POSTAGE \$9.65**  
 Flat Rate Env  
**U.S. POSTAGE PAID**  
 Click-N-Ship®


02/16/2023 Mailed from 01566 986765594767257

**PRIORITY MAIL®**

DEBORAH CHASE  
NORTHEAST SITE SOLUTIONS  
STE 1  
420 MAIN ST  
STURBRIDGE MA 01566-1359

Expected Delivery Date: 02/18/23  
Ref#: SBDS-00051  
**0000**

**C004**



**UNITED STATES POSTAL SERVICE®**

**Click-N-Ship®**



Cut on dotted line.

### Instructions

1. Each Click-N-Ship® label is unique. Labels are to be used as printed and used only once. DO NOT PHOTO COPY OR ALTER LABEL.
2. Place your label so it does not wrap around the edge of the package.
3. Adhere your label to the package. A self-adhesive label is recommended. If tape or glue is used, DO NOT TAPE OVER BARCODE. Be sure all edges are secure.
4. To mail your package with PC Postage®, you may schedule a Package Pickup online, hand to your letter carrier, take to a Post Office™, or drop in a USPS collection box.
5. Mail your package on the "Ship Date" you selected when creating this label.

### Click-N-Ship® Label Record

**USPS TRACKING # :**  
**9405 5036 9930 0482 2528 42**

Trans. #: 582816277	Priority Mail® Postage: <b>\$9.65</b>
Print Date: 02/16/2023	Total: <b>\$9.65</b>
Ship Date: 02/16/2023	
Expected Delivery Date: 02/18/2023	


**From:** DEBORAH CHASE      Ref#: SBDS-00051  
 NORTHEAST SITE SOLUTIONS  
 STE 1  
 420 MAIN ST  
 STURBRIDGE MA 01566-1359

**To:** DANA BENNETT  
 FIRST SELECTMAN-JEWETT CITY  
 28 MAIN ST  
 JEWETT CITY CT 06351-2204

\* Retail Pricing Priority Mail rates apply. There is no fee for USPS Tracking® service on Priority Mail service with use of this electronic rate shipping label. Refunds for unused postage paid labels can be requested online 30 days from the print date.



Thank you for shipping with the United States Postal Service!  
 Check the status of your shipment on the USPS Tracking® page at usps.com



**USPS TRACKING #**

**9405 5036 9930 0482 2528 80**

**P**

**US POSTAGE**  
Flat Rate Env  
**\$9.65**

**U.S. POSTAGE PAID**  
Click-N-Ship®

Mailed from 01566 986765594764477

**Click-N-Ship®**

**PRIORITY MAIL®**

Expected Delivery Date: 02/18/23  
Ref#: SBDS-00051  
**0000**

**C004**

DEBORAH CHASE  
NORTHEAST SITE SOLUTIONS  
STE 1  
420 MAIN ST  
STURBRIDGE MA 01566-1359

MARIO TRISTANY JR.  
TOWN PLANNER  
28 MAIN ST  
JEWETT CITY CT 06351-2204

Electronic Rate Approved #038555749



Cut on dotted line.

### Instructions

1. Each Click-N-Ship® label is unique. Labels are to be used as printed and used only once. DO NOT PHOTO COPY OR ALTER LABEL.
2. Place your label so it does not wrap around the edge of the package.
3. Adhere your label to the package. A self-adhesive label is recommended. If tape or glue is used, DO NOT TAPE OVER BARCODE. Be sure all edges are secure.
4. To mail your package with PC Postage®, you may schedule a Package Pickup online, hand to your letter carrier, take to a Post Office™, or drop in a USPS collection box.
5. Mail your package on the "Ship Date" you selected when creating this label.

### Click-N-Ship® Label Record

**USPS TRACKING # :**  
**9405 5036 9930 0482 2528 80**

Trans. #: 582816277	Priority Mail® Postage: <b>\$9.65</b>
Print Date: 02/16/2023	Total: <b>\$9.65</b>
Ship Date: 02/16/2023	
Expected Delivery Date: 02/18/2023	

**From:** DEBORAH CHASE      Ref#: SBDS-00051  
NORTHEAST SITE SOLUTIONS  
STE 1  
420 MAIN ST  
STURBRIDGE MA 01566-1359

**To:** MARIO TRISTANY JR.  
TOWN PLANNER  
28 MAIN ST  
JEWETT CITY CT 06351-2204


\* Retail Pricing Priority Mail rates apply. There is no fee for USPS Tracking® service on Priority Mail service with use of this electronic rate shipping label. Refunds for unused postage paid labels can be requested online 30 days from the print date.



Thank you for shipping with the United States Postal Service!

Check the status of your shipment on the USPS Tracking® page at usps.com





**USPS TRACKING #**

**9405 5036 9930 0482 2529 03**

**P**

**US POSTAGE**  
Flat Rate Env

**U.S. POSTAGE PAID**  
Click-N-Ship®

Mailed from 01566 986765594762477

**Click-N-Ship®**

**PRIORITY MAIL®**

Expected Delivery Date: 02/18/23  
Ref#: SBDS-00051  
**0000**

**R007**

DEBORAH CHASE  
NORTHEAST SITE SOLUTIONS  
STE 1  
420 MAIN ST  
STURBRIDGE MA 01566-1359

COURTNEY & BRIDGET KINNIE  
2139 GLASGO RD  
GRISWOLD CT 06351-9114

9405 5036 9930 0482 2529 03

Electronic Rate Approved #038555749



Cut on dotted line.

### Instructions

1. Each Click-N-Ship® label is unique. Labels are to be used as printed and used only once. DO NOT PHOTO COPY OR ALTER LABEL.
2. Place your label so it does not wrap around the edge of the package.
3. Adhere your label to the package. A self-adhesive label is recommended. If tape or glue is used, DO NOT TAPE OVER BARCODE. Be sure all edges are secure.
4. To mail your package with PC Postage®, you may schedule a Package Pickup online, hand to your letter carrier, take to a Post Office™, or drop in a USPS collection box.
5. Mail your package on the "Ship Date" you selected when creating this label.

### Click-N-Ship® Label Record

**USPS TRACKING # :**  
**9405 5036 9930 0482 2529 03**

Trans. #: 582816277	Priority Mail® Postage: <b>\$9.65</b>
Print Date: 02/16/2023	Total: <b>\$9.65</b>
Ship Date: 02/16/2023	
Expected Delivery Date: 02/18/2023	

**From:** DEBORAH CHASE  
NORTHEAST SITE SOLUTIONS  
STE 1  
420 MAIN ST  
STURBRIDGE MA 01566-1359

**To:** COURTNEY & BRIDGET KINNIE  
2139 GLASGO RD  
GRISWOLD CT 06351-9114

Ref#: SBDS-00051

\* Retail Pricing Priority Mail rates apply. There is no fee for USPS Tracking® service on Priority Mail service with use of this electronic rate shipping label. Refunds for unused postage paid labels can be requested online 30 days from the print date.



Thank you for shipping with the United States Postal Service!

Check the status of your shipment on the USPS Tracking® page at [usps.com](https://usps.com)

BOBOSOODSIA SBA  
DISH



LINCOLN MALL  
560 LINCOLN ST STE 8  
WORCESTER, MA 01605-1925  
(800)275-8777

02/17/2023 10:57 AM

Product	Qty	Unit Price	Price
---------	-----	------------	-------

Prepaid Mail	1		\$0.00
--------------	---	--	--------

Jewett City, CT 06351  
Weight: 0 lb 12.70 oz  
Acceptance Date:  
Fri 02/17/2023  
Tracking #:  
9405 5036 9930 0482 2528 80

Prepaid Mail	1		\$0.00
--------------	---	--	--------

Jewett City, CT 06351  
Weight: 0 lb 12.80 oz  
Acceptance Date:  
Fri 02/17/2023  
Tracking #:  
9405 5036 9930 0482 2528 42

Prepaid Mail	1		\$0.00
--------------	---	--	--------

Westborough, MA 01581  
Weight: 0 lb 2.10 oz  
Acceptance Date:  
Fri 02/17/2023  
Tracking #:  
9405 5036 9930 0482 2527 81

Prepaid Mail	1		\$0.00
--------------	---	--	--------

Jewett City, CT 06351  
Weight: 0 lb 12.80 oz  
Acceptance Date:  
Fri 02/17/2023  
Tracking #:  
9405 5036 9930 0482 2529 03

Grand Total:			\$0.00
--------------	--	--	--------