



Crown Castle
3 Corporate Park Drive, Suite 101
Clifton Park, NY 12065

March 18, 2021

Melanie A. Bachman
Executive Director
Connecticut Siting Council
10 Franklin Square
New Britain, CT 06051

**RE: Notice of Exempt Modification for T-Mobile: 806367
65 Maple Avenue West, Haddam, CT 06441
Latitude: 41° 29' 4.54" / Longitude: -72° 34' 20.81"**

Dear Ms. Bachman:

T-Mobile currently maintains six (6) antennas at the 98-foot mount level on the existing 115-foot monopole tower, located at 65 Maple Avenue West, Haddam, CT. The property is owned by D'Amico, Louis W Jr & D'Amico, Enzo. The tower is owned by Crown Castle. T-Mobile now intends to replace three (3) antennas and ancillary equipment at the 98-ft level. T-Mobile also intends to replace the antenna mount at the same level. This modification/proposal includes hardware that is both 4G (LTE) and 5G capable through remote software configuration and either or both services may be turned on or off at various times.

Panned Modification:

Tower:

Installed New:

- (3) RFS/Celwave – APXVAARR24_43-U-NA20
- (3) Ericsson-Radio 4449 B12/B71
- (3) Ericsson-TMA KRY112 489/2
- (3) Ericsson-TMA KRY112 144/1
- (1) HYBRID Cable 1-5/8"

Remove:

- (3) ANTENNAS
- (1) T-Arm Mounts

Ground:

Install New:

- (2) BB 6630
- (6) RUS01 B4

Remove:

- (1) DUS41
- (6) RUS01 B12

The Foundation for a Wireless World.

CrownCastle.com


The facility was approved by the Connecticut Siting Council in Docket No. 170 on November 15, 1995. T-Mobile's proposed modification will not violate the conditions set forth in the Decision and Order.

Please accept this letter as notification pursuant to Regulations of Connecticut State Agencies §16-50j-73, for construction that constitutes an exempt modification pursuant to R.C.S.A. § 16-50j-72(b)(2). In accordance with R.C.S.A. § 16-50j-73, a copy of this letter is being sent to Mr. Robert McGarry, First Selectman, Town of Haddam, Mr. Bill Warner, Town Planner and he property owner, Mr. Louis W. D'Amico, Jr. Crown Castle is the tower owner.

1. The proposed modifications will not result in an increase in the height of the existing tower.
2. The proposed modifications will not require the extension of the site boundary.
3. The proposed modification will not increase noise levels at the facility by six decibels or more, or to levels that exceed state and local criteria.
4. The operation of the replacement antennas will not increase radio frequency emissions at the facility to a level at or above the Federal Communication Commission safety standard.
5. The proposed modifications will not cause a change or alteration in the physical or environmental characteristics of the site.
6. The existing structure and its foundation can support the proposed loading.

For the foregoing reasons, T-Mobile respectfully submits that the proposed modifications to the above-reference telecommunications facility constitutes an exempt modification under R.C.S.A. § 16-50j-72(b)(2). Please send approval/rejection letter to Attn: Jeffrey Barbadora.

Sincerely,



Jeffrey Barbadora
Site Acquisition Specialist
1800 W. Park Drive
Westborough, MA 01581
(781) 970-0053
Jeff.Barbadora@crowncastle.com

Attachments

cc:

First Selectman, Mr. Robert McGarry, 30 Field Park Dr, Haddam, CT 06438 (860)-345-3730
Town Planner, Mr. Bill Warner, 30 Field Park Dr, Haddam, CT 06438 (860)-345-3730
Property Owner, Mr. Louis W D'Amico, Jr., 65 Maple Avenue West, Higganum, CT 06441
Crown Castle, Tower Owner



CONNECTICUT SITING COUNCIL

[Home](#) [About Us](#) [Pending Matters](#) [Decisions](#) [Forms](#) [Contact Us](#)**Filing Guides**[Meetings & Minutes](#)[Public Participation](#)[Audio Link to New Britain Hearing Rooms](#)[Programs & Services](#)[Telecommunications Database](#)[Publications](#)[Other Resources](#)[Statutes & Regulations](#)[Electric Transmission Upgrade Projects](#)[Frequently Asked Questions](#)Melanie Bachman,
Executive Director**NOTICE TO USERS**

The Connecticut Siting Council posts filed documents to this site as a public service. The Council disclaims any liability for the content of submissions made by parties, intervenors, public officials, and the general public. Further, while the Council seeks to be complete in its postings, the Council urges users of this site to confirm with the submitter the completeness of the postings made. The posting of any document does not constitute or imply endorsement by the Connecticut Siting Council. Finally, the Connecticut Siting Council assumes no responsibility for the use of documents posted on this site.

For further information about the proper use of material posted on this site, please see the State of Connecticut [disclaimer](#).

DOCKET NO. 170 - An application of Metro Mobile CTS of Hartford, Inc. for a Certificate of Environmental Compatibility and Public Need for the construction, maintenance, and operation of a cellular telecommunications facility located at 109 Maple Avenue West in the Higganum section of the Town of Haddam, Connecticut.

Connecticut Siting Council

November 15, 1995

DECISION AND ORDER

Pursuant to the foregoing Findings of Fact, and Opinion, the Connecticut Siting Council (Council) finds that the effects associated with the construction, operation, and maintenance of a cellular telecommunications tower and equipment building at the proposed prime site in the Higganum section of Haddam, Connecticut, including effects on the natural environment; ecological integrity and balance; public health and safety; scenic, historic, and recreational values; forests and parks; air and water purity; and fish and wildlife are not disproportionate either alone or cumulatively with other effects when compared to need, are not in conflict with the policies of the State concerning such effects, and are not sufficient reason to deny the application and therefore directs that a Certificate of Environmental Compatibility and Public Need, as provided by General Statutes § 16-50k, be issued to Bell Atlantic NYNEX Mobile, Inc. for the construction, operation, and maintenance of a cellular telecommunications tower, associated equipment, and building at the proposed prime site, located within an 88.85 acre parcel at 109 Maple Avenue West, Haddam, Connecticut. We find the effects on scenic resources and the environment from the alternate site to be more significant than the effects from the prime site, and therefore deny certification of the alternate site without prejudice.

The facility shall be constructed, operated, and maintained as a monopole substantially as specified in the Council's record in this matter, and subject to the following conditions:

1. The tower shall be constructed as a monopole, no taller than necessary to provide the proposed communications service and sufficient to accommodate tower sharing, and not to exceed a total height of 120 feet above ground level.
2. The Certificate Holder shall prepare a Development and Management (D&M) Plan for this site in compliance with Sections 16-50j-75 through 16-50j-77 of the Regulations of Connecticut State Agencies. The D&M Plan shall be submitted to and approved by the Council prior to the commencement of facility construction and shall include plans for the tower and tower foundation; specifications for the placement of all antennas to be attached to this tower; plans for the equipment building, security fence, emergency generator and fuel tank; plans for the access road and utility line installation from 109 Maple Avenue West; plans for site clearing and tree trimming; and plans for water drainage and erosion and sedimentation controls consistent with the Connecticut Guidelines for Soil Erosion and Sedimentation Control, as amended.
3. Upon the establishment of any new State or federal radio frequency power density standards applicable to frequencies of this facility, the facility granted herein shall be brought into compliance with such standards.
4. The Certificate Holder shall provide the Council a recalculated report of electromagnetic radio frequency power density if and when circumstances in operation cause a change in power density above the levels originally calculated and provided in the application.
5. The Certificate Holder shall permit public or private entities to share space on the proposed tower for fair consideration, or shall provide any requesting entity with specific legal, technical, environmental, or economic reasons precluding such tower sharing.
6. If the facility does not initially provide, or permanently ceases to provide, cellular services following completion of construction, this Decision and Order shall be void, and the Certificate Holder shall dismantle the tower and remove all associated equipment or reapplication for any continued or new use shall be made to the Council before any such use is made.
7. Unless otherwise approved by the Council, this Decision and Order shall be void if all construction authorized herein is not completed within three years of the effective date of this Decision and Order or within three years after all appeals to this Decision and Order have been resolved.
8. The Certificate Holder shall notify the Council upon completion of construction and provide the final cost to construct the facility.

Pursuant to General Statutes § 16-50p, we hereby direct that a copy of the Findings of Fact, Opinion, and Decision and Order be served on each person listed below, and notice of issuance shall be published in The

Hartford Courant and the Middletown Press.

By this Decision and Order, the Council disposes of the legal rights, duties, and privileges of each party named or admitted to the proceeding in accordance with Section 16-50j-17 of the Regulations of Connecticut State Agencies.

The parties and intervenors to this proceeding are:

APPLICANT

Bell Atlantic NYNEX Mobile, Inc.

ITS REPRESENTATIVES

Brian C.S. Freeman, Esq.

Kenneth C. Baldwin, Esq.

Robinson & Cole

One Commercial Plaza

Hartford, CT 06103-3597

David S. Malko

General Manager - Engineering

Sandy M. Ranciato

Manager - Regulatory Services

Bell Atlantic NYNEX Mobile, Inc.

20 Alexander Drive

Wallingford, CT 06492

INTERVENOR

Town of Haddam

ITS REPRESENTATIVE

The Honorable Marjorie W. DeBold

First Selectman

Town of Haddam

30 Field Park Drive

Haddam, CT 06438

INTERVENOR

Springwich Cellular Limited Partnership

ITS REPRESENTATIVE

Peter J. Tyrrell, Esq.

General Counsel - Wireless

Springwich Cellular Limited Partnership

500 Enterprise Dr., 4th floor

Rocky Hill, CT 06067


Content Last Modified on 8/9/2002 11:34:46 AM

Ten Franklin Square New Britain, CT 06051 / 860-827-2935

[Home](#) | [CT.gov Home](#) | [Send Feedback](#) | [Login](#) | [Register](#)

State of Connecticut [Disclaimer](#), [Privacy Policy](#), and [Web Site Accessibility Policy](#). Copyright © 2002-2019 State of Connecticut.





3/16/2021 10:43:10 AM

Scale: 1"=33'

Scale is approximate

The information depicted on this map is for planning purposes only.
It is not adequate for legal boundary definition, regulatory
interpretation, or parcel-level analyses.



The Assessor's office is responsible for the maintenance of records on the ownership of properties. Assessments are computed at 70% of the estimated market value of real property at the time of the last revaluation which was 2020.



Information on the Property Records for the Municipality of Haddam was last updated on 3/15/2021.

Parcel Information

| | | | | | |
|--------------------------|-----------------------------|-------------------|-------------|-------------------|------------|
| Location: | 65 MAPLE AVE WEST UNIT C | Property Use: | Vacant Land | Primary Use: | Cell Tower |
| Unique ID: | MT380800 | Map Block Lot: | 23 001 1 C | Acres: | 1.25 |
| 490 Acres: | 0.00 | Zone: | R-2 | Volume / Page: | 0336/0559 |
| Developers Map / Lot: | | Census: | 5901 | | |

Value Information

| | Appraised Value | Assessed Value |
|-----------------------|-----------------|----------------|
| Land | 100,750 | 70,530 |
| Buildings | 0 | 0 |
| Detached Outbuildings | 349,290 | 244,500 |
| Total | 450,040 | 315,030 |

Owner's Information

Owner's Data

DAMICO LOUIS W JR + DAMICO ENZO
C/O CROWN ATLANTIC CO LLC PMB 3
4017 WASHINGTON RD
MCMURRAY, PA 15317

Detached Outbuildings

| Type: | Year Built: | Length: | Width: | Area: |
|------------------|-------------|---------|--------|-------|
| 8 Ft Chain Fence | 2007 | 0.00 | 0.00 | 2,240 |
| Cell Tower | 2007 | 0.00 | 0.00 | 1 |
| Building Utility | 2007 | 0.00 | 0.00 | 580 |

Owner History - Sales

| Owner Name | Volume | Page | Sale Date | Deed Type | Valid Sale | Sale Price |
|--|--------|------|------------|-----------|------------|------------|
| DAMICO LOUIS W JR + DAMICO ENZO | 0336 | 0559 | 04/05/2010 | | No | \$0 |
| DAMICO LOUIS W SR + LOUIS W JR | 0305 | 0805 | 10/10/2006 | | No | \$0 |
| DAMICO LOUIS W & MARJORY C DAMICO FAMILY | 0256 | 0789 | 01/27/2003 | | No | \$0 |
| DAMICO LOUIS W | 0233 | 1040 | 12/21/2000 | | No | \$0 |

Building Permits


| Permit Number | Permit Type | Date Opened | Date Closed | Permit Status | Reason |
|---------------|-------------|-------------|-------------|---------------|--------------------------------|
| 8980 | Unknown | 12/05/2007 | | Closed | MOUNT 2 ANTENNAS ON EXIST TOWE |

ORIGIN ID: BBFA (781) 970-0053
 JEFF BARBADORA
 1800 W. PARK DRIVE
 WESTBOROUGH MA 01581
 UNITED STATES US
 PO BOX
 BILL SENDER
 SHIP DATE: 18MAR21
 ACTWGT: 0.50 LB
 CAD: 108046270/NET4340

TO **ROBERT MCGARRY FIRST SELECTMAN**
 TOWN OF HADDAM
 30 FIELD PARK DRIVE

56DJ3/AC39/FE4A

HADDAM CT 06438
 REF: 7990017680
 (860) 345-3730
 NY
 PO
 DEPT:



FRI - 19 MAR 12:00P
PRIORITY OVERNIGHT
 TRK# 0201
7732 0184 8242
 06438
 BDL
EB RSPA
 CT-US

After printing this label:

1. Use the 'Print' button on this page to print your label to your laser or inkjet printer.
2. Fold the printed page along the horizontal line.
3. Place label in shipping pouch and affix it to your shipment so that the barcode portion of the label can be read and scanned.

Warning: Use only the printed original label for shipping. Using a photocopy of this label for shipping purposes is fraudulent and could result in additional billing charges, along with the cancellation of your FedEx account number.

Use of this system constitutes your agreement to the service conditions in the current FedEx Service Guide, available on fedex.com. FedEx will not be responsible for any claim in excess of \$100 per package, whether the result of loss, damage, delay, non-delivery, misdelivery, or misinformation, unless you declare a higher value, pay an additional charge, document your actual loss and file a timely claim. Limitations found in the current FedEx Service Guide apply. Your right to recover from FedEx for any loss, including intrinsic value of the package, loss of sales, income interest, profit, attorney's fees, costs, and other forms of damage whether direct, incidental, consequential, or special is limited to the greater of \$100 or the authorized declared value. Recovery cannot exceed actual documented loss. Maximum for items of extraordinary value is \$1,000, e.g. jewelry, precious metals, negotiable instruments and other items listed in our Service Guide. Written claims must be filed within strict time limits, see current FedEx Service Guide.


ORIGIN ID:BBFA (781) 970-0053
 JEFF BARBADORA
 1800 W. PARK DRIVE
 WESTBOROUGH MA 01581
 UNITED STATES US

SHIP DATE: 18MAR21
 ACTWGT: 0.50 LB
 CAD: 108046270/NET4340
 BILL SENDER

TO **LOUIS D'AMICO, JR.**
LOUIS D'AMICO, JR.
65 MAPLE AVENUE

HIGGANUM CT 06441

(941) 308-5986
 REF: 7990017680
 INV
 PO
 DEPT:



FRI - 19 MAR 12:00P


PRIORITY OVERNIGHT

TRK# 0201

RES

06441
 BDL

EB RSPA



After printing this label:

1. Use the 'Print' button on this page to print your label to your laser or inkjet printer.
2. Fold the printed page along the horizontal line.
3. Place label in shipping pouch and affix it to your shipment so that the barcode portion of the label can be read and scanned.


Warning: Use only the printed original label for shipping. Using a photocopy of this label for shipping purposes is fraudulent and could result in additional billing charges, along with the cancellation of your FedEx account number.

Use of this system constitutes your agreement to the service conditions in the current FedEx Service Guide, available on fedex.com. FedEx will not be responsible for any claim in excess of \$100 per package, whether the result of loss, damage, delay, non-delivery, misdelivery, or misinformation, unless you declare a higher value, pay an additional charge, document your actual loss and file a timely claim. Limitations found in the current FedEx Service Guide apply. Your right to recover from FedEx for any loss, including intrinsic value of the package, loss of sales, income interest, profit, attorney's fees, costs, and other forms of damage whether direct, incidental, consequential, or special is limited to the greater of \$100 or the authorized declared value. Recovery cannot exceed actual documented loss. Maximum for items of extraordinary value is \$1,000, e.g. jewelry, precious metals, negotiable instruments and other items listed in our Service Guide. Written claims must be filed within strict time limits, see current FedEx Service Guide.

ORIGIN ID:BBFA (781) 970-0053
 JEFF BARBADORA
 1800 W. PARK DRIVE
 WESTBOROUGH MA 01581
 UNITED STATES US
 TO **BILL WARNER TOWN PLANNER**
 TOWN OF HADDAM
 30 FIELD PARK DRIVE
 BILL SENDER

SHIP DATE: 18MAR21
 ACTWGT: 0.50 LB
 CAD: 108046270/NET4340

56DJ3/AC39/FE4A




HADDAM CT 06438
 REF: 7990017680
 (860) 345-3730
 NY
 PO
 DEPT:

FRI - 19 MAR 12:00P
PRIORITY OVERNIGHT

TRK# 7732 0189 3381
 0201

EB RSPA
 06438
 BDL
 CT-US



After printing this label:

1. Use the 'Print' button on this page to print your label to your laser or inkjet printer.
2. Fold the printed page along the horizontal line.
3. Place label in shipping pouch and affix it to your shipment so that the barcode portion of the label can be read and scanned.

Warning: Use only the printed original label for shipping. Using a photocopy of this label for shipping purposes is fraudulent and could result in additional billing charges, along with the cancellation of your FedEx account number.

Use of this system constitutes your agreement to the service conditions in the current FedEx Service Guide, available on fedex.com. FedEx will not be responsible for any claim in excess of \$100 per package, whether the result of loss, damage, delay, non-delivery, misdelivery, or misinformation, unless you declare a higher value, pay an additional charge, document your actual loss and file a timely claim. Limitations found in the current FedEx Service Guide apply. Your right to recover from FedEx for any loss, including intrinsic value of the package, loss of sales, income interest, profit, attorney's fees, costs, and other forms of damage whether direct, incidental, consequential, or special is limited to the greater of \$100 or the authorized declared value. Recovery cannot exceed actual documented loss. Maximum for items of extraordinary value is \$1,000, e.g. jewelry, precious metals, negotiable instruments and other items listed in our Service Guide. Written claims must be filed within strict time limits, see current FedEx Service Guide.



Date: November 30, 2020

Denice Nicholson
Crown Castle
3 Corporate Dr
Clifton Park, NY 12065

Crown Castle
2000 Corporate Drive
Canonsburg, PA 15317
(724) 416-2000

| | | |
|--------------------------------------|---|----------------|
| Subject: | Structural Analysis Report | |
| Carrier Designation: | T-Mobile Co-Locate | |
| | Carrier Site Number: | CT11233A |
| | Carrier Site Name: | Higganum_1 |
| Crown Castle Designation: | Crown Castle BU Number: | 806367 |
| | Crown Castle Site Name: | HRT 046 943209 |
| | Crown Castle JDE Job Number: | 559174 |
| | Crown Castle Work Order Number: | 1901246 |
| | Crown Castle Order Number: | 479816 Rev. 1 |
| Engineering Firm Designation: | Crown Castle Project Number: | 1901246 |
| Site Data: | MAPLE AVE WEST, HADDAM, Middlesex County, CT Latitude 41° 29' 4.54", Longitude -72° 34' 20.81" 115.5 Foot - Monopole Tower | |

Dear Denice Nicholson,

Crown Castle is pleased to submit this "**Structural Analysis Report**" to determine the structural integrity of the above-mentioned tower.

The purpose of the analysis is to determine acceptability of the tower stress level. Based on our analysis we have determined the tower stress level for the structure and foundation, under the following load case, to be:

LC5: Proposed Equipment Configuration

Sufficient Capacity-56.1%

This analysis utilizes an ultimate 3-second gust wind speed of 130 mph as required by the 2018 Connecticut State Building Code. Applicable Standard references and design criteria are listed in Section 2 - "Analysis Criteria".

Structural analysis prepared by: Abigail Ruiz / MAA

Respectfully submitted by:

Maribel Dentinger

Maribel Dentinger, P.E.
Senior Project Engineer

Digitally signed by
Maribel Dentinger
Date: 2020.11.30
10:23:54 -05'00'



TABLE OF CONTENTS

1) INTRODUCTION

2) ANALYSIS CRITERIA

Table 1 - Proposed Equipment Configuration
Table 2 - Other Considered Equipment

3) ANALYSIS PROCEDURE

Table 3 - Documents Provided
3.1) Analysis Method
3.2) Assumptions

4) ANALYSIS RESULTS

Table 4 - Section Capacity (Summary)
Table 5 - Tower Component Stresses vs. Capacity - LC5
4.1) Recommendations

5) APPENDIX A

tnxTower Output

6) APPENDIX B

Base Level Drawing

7) APPENDIX C

Additional Calculations

1) INTRODUCTION

This tower is a 115.5 ft Monopole tower designed by FWT INC.

2) ANALYSIS CRITERIA

| | |
|----------------------|-----------|
| TIA-222 Revision: | TIA-222-H |
| Risk Category: | II |
| Wind Speed: | 130 mph |
| Exposure Category: | B |
| Topographic Factor: | 1 |
| Ice Thickness: | 1.5 in |
| Wind Speed with Ice: | 50 mph |
| Service Wind Speed: | 60 mph |

Table 1 - Proposed Equipment Configuration

| Mounting Level (ft) | Center Line Elevation (ft) | Number of Antennas | Antenna Manufacturer | Antenna Model | Number of Feed Lines | Feed Line Size (in) |
|---------------------|----------------------------|--------------------|----------------------|----------------------|----------------------|---------------------|
| 97.0 | 98.0 | 3 | ems wireless | RR90-17-02DP | 12 | 1-1/4 |
| | | 3 | ericsson | KRY 112 144/1 | | |
| | | 3 | ericsson | KRY 112 489/2 | | |
| | | 3 | ericsson | RADIO 4449 B12/B71 | | |
| | | 3 | rfs celwave | APXVAARR24_43-U-NA20 | | |
| | 97.0 | 1 | SitePro1 | RMQP-SPT | 1 | 1-5/8 |

Table 2 - Other Considered Equipment

| Mounting Level (ft) | Center Line Elevation (ft) | Number of Antennas | Antenna Manufacturer | Antenna Model | Number of Feed Lines | Feed Line Size (in) |
|---------------------|----------------------------|--------------------|------------------------|--------------------------------|----------------------|---------------------|
| 117.0 | 119.0 | 3 | antel | BXA-171063-8BF-2 w/ Mount Pipe | 15 | 1-5/8 |
| | | 3 | antel | BXA-70063/6CF w/ Mount Pipe | | |
| | | 4 | antel | LPA-80063/6CF w/ Mount Pipe | | |
| | | 2 | antel | LPA-80080/6CF w/ Mount Pipe | | |
| | | 6 | rfs celwave | FD9R6004/2C-3L | | |
| | 117.0 | 1 | tower mounts | Platform Mount [LP 1001-1] | | |
| 104.0 | 109.0 | 2 | decibel | DB411-A | 3 | 7/8 |
| | 107.0 | 1 | maxrad | MFB4505 | | |
| | 104.0 | 1 | tower mounts | Side Arm Mount [SO 702-3] | | |
| 87.0 | 89.0 | 4 | cci antennas | HPA65R-BU6A w/ Mount Pipe | 12 | 7/8 |
| | | 2 | cci antennas | HPA65R-BU8A w/ Mount Pipe | | |
| | | 3 | ericsson | RRUS 4415 B25 | | |
| | | 3 | ericsson | RRUS 4449 B5/B12 | | |
| | | 3 | ericsson | RRUS 8843 B2/B66A | 2 | 3/8 |
| | | 2 | kathrein | 80010965 w/ Mount Pipe | 2 | 7/16 |
| | | 1 | kathrein | 80010966 w/ Mount Pipe | 1 | CONDUIT |
| | | 3 | powerwave technologies | 7770.00 w/ Mount Pipe | | |

| Mounting Level (ft) | Center Line Elevation (ft) | Number of Antennas | Antenna Manufacturer | Antenna Model | Number of Feed Lines | Feed Line Size (in) |
|---------------------|----------------------------|--------------------|------------------------|---------------------------|----------------------|---------------------|
| | | 6 | powerwave technologies | LGP21401 | | |
| | | 2 | raycap | DC6-48-60-18-8C-EV | | |
| | | 1 | raycap | DC6-48-60-18-8F | | |
| | 87.0 | 1 | tower mounts | Platform Mount [LP 304-1] | | |
| 75.0 | 77.0 | 3 | kathrein | 742 213 | 6 | 1-5/8 |
| | 75.0 | 1 | tower mounts | Pipe Mount [PM 601-3] | | |

3) ANALYSIS PROCEDURE

Table 3 - Documents Provided

| Document | Remarks | Reference | Source |
|--|---------|-----------|----------|
| 4-GEOTECHNICAL REPORTS | FDH | 2225355 | CCISITES |
| 4-TOWER FOUNDATION DRAWINGS/DESIGN/SPECS | PJF | 2200141 | CCISITES |
| 4-TOWER MANUFACTURER DRAWINGS | PJF | 997499 | CCISITES |

3.1) Analysis Method

tnxTower (version 8.0.7.5), a commercially available analysis software package, was used to create a three-dimensional model of the tower and calculate member stresses for various loading cases. Selected output from the analysis is included in Appendix A. When applicable, Crown Castle has calculated and provided the effective area for panel antennas using approved methods following the intent of the TIA-222 standard.

3.2) Assumptions

- 1) Tower and structures were maintained in accordance with the TIA-222 Standard.
- 2) The configuration of antennas, transmission cables, mounts and other appurtenances are as specified in Tables 1 and 2 and the referenced drawings.

This analysis may be affected if any assumptions are not valid or have been made in error. Crown Castle should be notified to determine the effect on the structural integrity of the tower.

4) ANALYSIS RESULTS

Table 4 - Section Capacity (Summary)

| Section No. | Elevation (ft) | Component Type | Size | Critical Element | P (K) | SF*P_allow (K) | % Capacity | Pass / Fail |
|-------------|----------------|----------------|------------------------|------------------|--------|----------------|------------|-------------|
| L1 | 115.5 - 83.92 | Pole | TP40.829x32.25x0.25 | 1 | -10.83 | 1790.03 | 18.4 | Pass |
| L2 | 83.92 - 41.25 | Pole | TP51.92x38.8811x0.3125 | 2 | -24.66 | 2808.03 | 38.1 | Pass |
| L3 | 41.25 - 0 | Pole | TP62.5x49.4614x0.375 | 3 | -41.53 | 4073.37 | 45.4 | Pass |
| Summary | | | | | | | | |
| | | | | | | Pole (L3) | 45.4 | Pass |
| | | | | | | Rating = | 45.4 | Pass |

Table 5 - Tower Component Stresses vs. Capacity - LC5

| Notes | Component | Elevation (ft) | % Capacity | Pass / Fail |
|-------|------------------------------------|----------------|------------|-------------|
| 1 | Anchor Rods | 0 | 47.0 | Pass |
| 1 | Base Plate | 0 | 47.0 | Pass |
| 1 | Base Foundation (Structure) | 0 | 22.5 | Pass |
| 1 | Base Foundation (Soil Interaction) | 0 | 56.1 | Pass |

| | |
|---|--------------|
| Structure Rating (max from all components) = | 56.1% |
|---|--------------|

Notes:


1) See additional documentation in "Appendix C – Additional Calculations" for calculations supporting the % capacity consumed.

4.1) Recommendations

The tower and its foundation have sufficient capacity to carry the proposed load configuration. No modifications are required at this time.

APPENDIX A

TNXTOWER OUTPUT



MATERIAL STRENGTH

| GRADE | Fy | Fu | GRADE | Fy | Fu |
|---------|--------|--------|-------|----|----|
| A572-65 | 65 ksi | 80 ksi | | | |

TOWER DESIGN NOTES

1. Tower is located in Middlesex County, Connecticut.
2. Tower designed for Exposure B to the TIA-222-H Standard.
3. Tower designed for a 130 mph basic wind in accordance with the TIA-222-H Standard.
4. Tower is also designed for a 50 mph basic wind with 1.50 in ice. Ice is considered to increase in thickness with height.
5. Deflections are based upon a 60 mph wind.
6. Tower Risk Category II.
7. Topographic Category 1 with Crest Height of 0.00 ft
8. TOWER RATING: 45.4%

| | |
|--------------------|---------|
| Section | 1 |
| Length (ft) | 31.58 |
| Number of Sides | 12 |
| Thickness (in) | 0.3750 |
| Socket Length (ft) | 0.3125 |
| Top Dia (in) | 49.4614 |
| Bot Dia (in) | 62.5000 |
| Grade | A572-65 |
| Weight (K) | 11.0 |



115.5 ft

83.9 ft

41.3 ft

0.0 ft

ALL REACTIONS
ARE FACORED



Crown Castle
2000 Corporate Drive
Canonsburg, PA 15317
The Pathway to Possible Phone: (724) 416-2000
FAX:

| | | | |
|----------|---|-----------|----------|
| Job: | BU 806367 | | |
| Project: | | | |
| Client: | Crown Castle | Drawn by: | abruiz |
| Code: | TIA-222-H | Date: | 11/25/20 |
| Path: | C:\Users\AbRuiz\Desktop\WIP\BU806367\WO 1901248 - SAI\Prof\806367_RPA.erf | Scale: | NTS |
| | | Dwg No. | E-1 |

Tower Input Data

The tower is a monopole.

This tower is designed using the TIA-222-H standard.

The following design criteria apply:

- 3) Tower is located in Middlesex County, Connecticut.
- 4) Tower base elevation above sea level: 515.00 ft.
- 5) Basic wind speed of 130 mph.
- 6) Risk Category II.
- 7) Exposure Category B.
- 8) Simplified Topographic Factor Procedure for wind speed-up calculations is used.
- 9) Topographic Category: 1.
- 10) Crest Height: 0.00 ft.
- 11) Nominal ice thickness of 1.5000 in.
- 12) Ice thickness is considered to increase with height.
- 13) Ice density of 56 pcf.
- 14) A wind speed of 50 mph is used in combination with ice.
- 15) Temperature drop of 50 °F.
- 16) Deflections calculated using a wind speed of 60 mph.
- 17) A non-linear (P-delta) analysis was used.
- 18) Pressures are calculated at each section.
- 19) Stress ratio used in pole design is 1.05.
- 20) Tower analysis based on target reliabilities in accordance with Annex S.
- 21) Load Modification Factors used: $K_{es}(F_w) = 0.95$, $K_{es}(t_i) = 0.85$.
- 22) Local bending stresses due to climbing loads, feed line supports, and appurtenance mounts are not considered.

Options

| | | |
|-------------------------------------|--------------------------------------|---|
| Consider Moments - Legs | Distribute Leg Loads As Uniform | Use ASCE 10 X-Brace Ly Rules |
| Consider Moments - Horizontals | Assume Legs Pinned | Calculate Redundant Bracing Forces |
| Consider Moments - Diagonals | ✓ Assume Rigid Index Plate | Ignore Redundant Members in FEA |
| Use Moment Magnification | ✓ Use Clear Spans For Wind Area | SR Leg Bolts Resist Compression |
| Use Code Stress Ratios | Use Clear Spans For KL/r | All Leg Panels Have Same Allowable |
| ✓ Use Code Safety Factors - Guys | Retention Guys To Initial Tension | Offset Girt At Foundation |
| Escalate Ice | ✓ Bypass Mast Stability Checks | ✓ Consider Feed Line Torque |
| Always Use Max Kz | ✓ Use Azimuth Dish Coefficients | Include Angle Block Shear Check |
| Use Special Wind Profile | ✓ Project Wind Area of Appurt. | Use TIA-222-H Bracing Resist. |
| Include Bolts In Member Capacity | Autocalc Torque Arm Areas | Exemption |
| Leg Bolts Are At Top Of Section | Add IBC .6D+W Combination | Use TIA-222-H Tension Splice |
| Secondary Horizontal Braces Leg | ✓ Sort Capacity Reports By Component | Exemption |
| Use Diamond Inner Bracing (4 Sided) | Triangulate Diamond Inner Bracing | Poles |
| SR Members Have Cut Ends | Treat Feed Line Bundles As Cylinder | ✓ Include Shear-Torsion Interaction |
| SR Members Are Concentric | Ignore KL/ry For 60 Deg. Angle Legs | Always Use Sub-Critical Flow |
| | | Use Top Mounted Sockets |
| | | Pole Without Linear Attachments |
| | | Pole With Shroud Or No |
| | | Appurtenances |
| | | Outside and Inside Corner Radii Are Known |

Tapered Pole Section Geometry

| Section | Elevation | Section Length | Splice Length | Number of Sides | Top Diameter | Bottom Diameter | Wall Thickness | Bend Radius | Pole Grade |
|---------|--------------|----------------|---------------|-----------------|--------------|-----------------|----------------|-------------|------------------|
| | ft | ft | ft | | in | in | in | in | |
| L1 | 115.50-83.92 | 31.58 | 5.33 | 12 | 32.2500 | 40.8290 | 0.2500 | 1.0000 | A572-65 (65 ksi) |

| Section | Elevation ft | Section Length ft | Splice Length ft | Number of Sides | Top Diameter in | Bottom Diameter in | Wall Thickness in | Bend Radius in | Pole Grade |
|---------|-----------------|-------------------------|------------------------|-----------------------|-----------------------|--------------------------|-------------------------|----------------------|---------------------|
| L2 | 83.92-41.25 | 48.00 | 6.75 | 12 | 38.8811 | 51.9200 | 0.3125 | 1.2500 | A572-65 (65 ksi) |
| L3 | 41.25-0.00 | 48.00 | | 12 | 49.4614 | 62.5000 | 0.3750 | 1.5000 | A572-65 (65 ksi) |

Tapered Pole Properties

| Section | Tip Dia. in | Area in ² | I in ⁴ | r in | C in | I/C in ³ | J in ⁴ | It/Q in ² | w in | w/t |
|---------|----------------|-------------------------|----------------------|---------|---------|------------------------|----------------------|-------------------------|---------|--------|
| L1 | 33.2995 | 25.7600 | 3366.9120 | 11.4560 | 16.7055 | 201.5451 | 6822.2765 | 12.6783 | 7.9730 | 31.892 |
| | 42.1811 | 32.6661 | 6865.7163 | 14.5273 | 21.1494 | 324.6290 | 13911.802 | 16.0773 | 10.2722 | 41.089 |
| L2 | 41.6413 | 38.8096 | 7368.7188 | 13.8075 | 20.1404 | 365.8678 | 14931.022 | 19.1009 | 9.5826 | 30.664 |
| | 53.6413 | 51.9300 | 17653.479 | 18.4755 | 26.8946 | 656.3959 | 35770.734 | 25.5584 | 13.0771 | 41.847 |
| L3 | 52.9722 | 59.2718 | 18228.737 | 17.5729 | 25.6210 | 711.4763 | 36936.364 | 29.1718 | 12.2507 | 32.668 |
| | 64.5725 | 75.0159 | 36954.922 | 22.2407 | 32.3750 | 1141.4648 | 74880.691 | 36.9206 | 15.7450 | 41.987 |

| Tower Elevation ft | Gusset Area (per face) ft ² | Gusset Thickness in | Gusset Grade | Adjust. Factor A _f | Adjust. Factor A _r | Weight Mult. | Double Angle Stitch Bolt Spacing Diagonals in | Double Angle Stitch Bolt Spacing Horizontals in | Double Angle Stitch Bolt Spacing Redundants in |
|--------------------------|---|---------------------------|--------------|----------------------------------|-------------------------------------|--------------|---|---|--|
| L1 115.50- 83.92 | | | | 1 | 1 | 1 | | | |
| L2 83.92- 41.25 | | | | 1 | 1 | 1 | | | |
| L3 41.25-0.00 | | | | 1 | 1 | 1 | | | |

Feed Line/Linear Appurtenances - Entered As Round Or Flat

| Description | Sector | Exclude From Torque Calculation | Componen t Type | Placement ft | Total Number | Number Per Row | Start/End Position | Width or Diamete r in | Perimete r in | Weight plf |
|-----------------------|--------|--|----------------------|------------------|-----------------|-------------------|-----------------------|--------------------------------|---------------------|---------------|
| LCF78-50J(7/8") | B | No | Surface Ar (CaAa) | 104.00 - 0.00 | 2 | 2 | 0.000 0.042 | 1.1000 | | 0.53 |
| ** | | | | | | | | | | |
| 2" (Nominal) Conduit | A | No | Surface Ar (CaAa) | 87.00 - 0.00 | 1 | 1 | -0.125 -0.125 | 2.3750 | | 0.72 |
| LDF5-50A(7/8") | A | No | Surface Ar (CaAa) | 87.00 - 0.00 | 12 | 6 | 0.000 0.108 | 1.0900 | | 0.33 |
| FB-L98B-034-XXX(3/8") | A | No | Surface Ar (CaAa) | 87.00 - 0.00 | 1 | 1 | -0.108 -0.108 | 0.3937 | | 0.06 |
| WR-VG86ST-BRD(3/4") | A | No | Surface Ar (CaAa) | 87.00 - 0.00 | 4 | 4 | -0.100 0.000 | 0.7950 | | 0.58 |
| ***** | | | | | | | | | | |

Feed Line/Linear Appurtenances - Entered As Area

| Description | Face or Leg | Allow Shield | Exclude From Torque Calculation | Componen t Type | Placement ft | Total Number | CA _A ft ² /ft | Weight plf |
|-------------|-------------------|-----------------|--|--------------------|-----------------|-----------------|--|---------------|
| | | | | | | | | |

| Description | Face or Leg | Allow Shield | Exclude From Torque Calculation | Component Type | Placement ft | Total Number | CAA _A | Weight |
|-------------------------|-------------|--------------|---------------------------------|----------------|---------------|--------------|--|--------|
| | | | | | | | ft ² /ft | plf |
| LDF7-50A(1-5/8") | C | No | No | Inside Pole | 115.50 - 0.00 | 15 | No Ice 0.00 1/2" Ice 0.00 1" Ice 0.00 2" Ice 0.00 | 0.82 |
| | | | | | | | | |
| ** | | | | | | | | |
| LCF78-50J(7/8") | C | No | No | Inside Pole | 104.00 - 0.00 | 1 | No Ice 0.00 1/2" Ice 0.00 1" Ice 0.00 2" Ice 0.00 | 0.53 |
| | | | | | | | | |
| ** | | | | | | | | |
| FLC 114-50J(1-1/4") | C | No | No | Inside Pole | 97.00 - 0.00 | 6 | No Ice 0.00 1/2" Ice 0.00 1" Ice 0.00 2" Ice 0.00 | 0.70 |
| | | | | | | | | |
| AVA6-50(1-1/4") | C | No | No | Inside Pole | 97.00 - 0.00 | 6 | No Ice 0.00 1/2" Ice 0.00 1" Ice 0.00 2" Ice 0.00 | 0.46 |
| | | | | | | | | |
| HCS 6X12 4AWG(1-5/8") | C | No | No | Inside Pole | 97.00 - 0.00 | 1 | No Ice 0.00 1/2" Ice 0.00 1" Ice 0.00 2" Ice 0.00 | 2.40 |
| | | | | | | | | |
| FB-L98B-002-75000(3/8") | C | No | No | Inside Pole | 87.00 - 0.00 | 1 | No Ice 0.00 1/2" Ice 0.00 1" Ice 0.00 2" Ice 0.00 | 0.06 |
| | | | | | | | | |
| WR-VG122ST-BRDA(7/16") | C | No | No | Inside Pole | 87.00 - 0.00 | 2 | No Ice 0.00 1/2" Ice 0.00 1" Ice 0.00 2" Ice 0.00 | 0.14 |
| | | | | | | | | |
| ** | | | | | | | | |
| AVA7-50(1-5/8") | C | No | No | Inside Pole | 75.00 - 0.00 | 6 | No Ice 0.00 1/2" Ice 0.00 1" Ice 0.00 2" Ice 0.00 | 0.70 |
| | | | | | | | | |
| ***** | | | | | | | | |
| **** | | | | | | | | |

Feed Line/Linear Appurtenances Section Areas

| Tower Section | Tower Elevation ft | Face | A _R ft ² | A _F ft ² | CAA _A In Face ft ² | CAA _A Out Face ft ² | Weight K |
|---------------|--------------------|------|-----------------------------------|-----------------------------------|--|---|-------------|
| L1 | 115.50-83.92 | A | 0.000 | 0.000 | 3.847 | 0.000 | 0.02 |
| | | B | 0.000 | 0.000 | 4.418 | 0.000 | 0.02 |
| | | C | 0.000 | 0.000 | 0.000 | 0.000 | 0.52 |
| L2 | 83.92-41.25 | A | 0.000 | 0.000 | 53.289 | 0.000 | 0.30 |
| | | B | 0.000 | 0.000 | 9.387 | 0.000 | 0.05 |
| | | C | 0.000 | 0.000 | 0.000 | 0.000 | 1.10 |
| L3 | 41.25-0.00 | A | 0.000 | 0.000 | 51.516 | 0.000 | 0.29 |
| | | B | 0.000 | 0.000 | 9.075 | 0.000 | 0.04 |
| | | C | 0.000 | 0.000 | 0.000 | 0.000 | 1.10 |

Feed Line/Linear Appurtenances Section Areas - With Ice

| Tower Section | Tower Elevation ft | Face or Leg | Ice Thickness in | A _R ft ² | A _F ft ² | CAA _A In Face ft ² | CAA _A Out Face ft ² | Weight K |
|---------------|--------------------|-------------|------------------|-----------------------------------|-----------------------------------|--|---|-------------|
| L1 | 115.50-83.92 | A | 1.423 | 0.000 | 0.000 | 8.541 | 0.000 | 0.12 |
| | | B | | 0.000 | 0.000 | 12.668 | 0.000 | 0.14 |

| Tower Section | Tower Elevation ft | Face or Leg | Ice Thickness in | A_R ft ² | A_F ft ² | C_{AA} In Face ft ² | C_{AA} Out Face ft ² | Weight K |
|---------------|--------------------|-------------|------------------|--------------------------|--------------------------|-------------------------------------|--------------------------------------|----------|
| L2 | 83.92-41.25 | C | | 0.000 | 0.000 | 0.000 | 0.000 | 0.52 |
| | | A | 1.358 | 0.000 | 0.000 | 118.323 | 0.000 | 1.71 |
| | | B | | 0.000 | 0.000 | 26.919 | 0.000 | 0.29 |
| | | C | | 0.000 | 0.000 | 0.000 | 0.000 | 1.10 |
| L3 | 41.25-0.00 | A | 1.213 | 0.000 | 0.000 | 111.973 | 0.000 | 1.58 |
| | | B | | 0.000 | 0.000 | 25.353 | 0.000 | 0.26 |
| | | C | | 0.000 | 0.000 | 0.000 | 0.000 | 1.10 |

Feed Line Center of Pressure

| Section | Elevation ft | CP_x in | CP_z in | CP_x Ice in | CP_z Ice in |
|---------|-----------------|--------------|--------------|---------------------|---------------------|
| L1 | 115.50-83.92 | 0.0543 | -0.7707 | 0.3730 | -1.2073 |
| L2 | 83.92-41.25 | -4.1245 | -3.2033 | -4.6191 | -3.7209 |
| L3 | 41.25-0.00 | -4.3123 | -3.3519 | -5.0428 | -4.0655 |

Note: For pole sections, center of pressure calculations do not consider feed line shielding.

Shielding Factor Ka

| Tower Section | Feed Line Record No. | Description | Feed Line Segment Elev. | K_a No Ice | K_a Ice |
|---------------|----------------------|----------------------|-------------------------|-----------------|--------------|
| L1 | 4 | LCF78-50J(7/8") | 83.92 - 104.00 | 1.0000 | 1.0000 |
| L1 | 10 | 2" (Nominal) Conduit | 83.92 - 87.00 | 1.0000 | 1.0000 |
| L1 | 11 | LDF5-50A(7/8) | 83.92 - 87.00 | 1.0000 | 1.0000 |
| L1 | 14 | FB-L98B-034-XXX(3/8) | 83.92 - 87.00 | 1.0000 | 1.0000 |
| L1 | 15 | WR-VG86ST-BRD(3/4) | 83.92 - 87.00 | 1.0000 | 1.0000 |
| L2 | 4 | LCF78-50J(7/8") | 41.25 - 83.92 | 1.0000 | 1.0000 |
| L2 | 10 | 2" (Nominal) Conduit | 41.25 - 83.92 | 1.0000 | 1.0000 |
| L2 | 11 | LDF5-50A(7/8) | 41.25 - 83.92 | 1.0000 | 1.0000 |
| L2 | 14 | FB-L98B-034-XXX(3/8) | 41.25 - 83.92 | 1.0000 | 1.0000 |
| L2 | 15 | WR-VG86ST-BRD(3/4) | 41.25 - 83.92 | 1.0000 | 1.0000 |
| L3 | 4 | LCF78-50J(7/8") | 0.00 - 41.25 | 1.0000 | 1.0000 |
| L3 | 10 | 2" (Nominal) Conduit | 0.00 - 41.25 | 1.0000 | 1.0000 |
| L3 | 11 | LDF5-50A(7/8) | 0.00 - 41.25 | 1.0000 | 1.0000 |
| L3 | 14 | FB-L98B-034-XXX(3/8) | 0.00 - 41.25 | 1.0000 | 1.0000 |
| L3 | 15 | WR-VG86ST-BRD(3/4) | 0.00 - 41.25 | 1.0000 | 1.0000 |

Discrete Tower Loads

| Description | Face or Leg | Offset Type | Offsets: Horz Lateral Vert ft ft ft | Azimuth Adjustment ° | Placement | | C _{AA} Front ft ² | C _{AA} Side ft ² | Weight K |
|------------------------------------|-------------|-------------|--|----------------------------|-----------|-----------------|--|---|-------------|
| | | | | | ft | ft ² | | | |
| BXA-171063-8BF-2 w/ Mount Pipe | A | From Leg | 4.00 | 0.0000 | 117.00 | No Ice | 3.18 | 3.35 | 0.03 |
| | | | 0.00 | | | 1/2" | 3.56 | 3.97 | 0.06 |
| | | | 2.00 | | | Ice | 3.93 | 4.60 | 0.10 |
| BXA-171063-8BF-2 w/ Mount Pipe | B | From Leg | 4.00 | 0.0000 | 117.00 | 1" Ice | 4.69 | 5.89 | 0.19 |
| | | | 0.00 | | | 2" Ice | | | |
| | | | 2.00 | | | No Ice | 3.18 | 3.35 | 0.03 |
| BXA-171063-8BF-2 w/ Mount Pipe | C | From Leg | 4.00 | 0.0000 | 117.00 | 1/2" | 3.56 | 3.97 | 0.06 |
| | | | 0.00 | | | Ice | 3.93 | 4.60 | 0.10 |
| | | | 2.00 | | | 1" Ice | 4.69 | 5.89 | 0.19 |
| BXA-70063/6CF w/ Mount Pipe | A | From Leg | 4.00 | 0.0000 | 117.00 | 2" Ice | | | |
| | | | 0.00 | | | No Ice | 7.82 | 5.70 | 0.04 |
| | | | 2.00 | | | 1/2" | 8.37 | 6.85 | 0.10 |
| BXA-70063/6CF w/ Mount Pipe | B | From Leg | 4.00 | 0.0000 | 117.00 | Ice | 8.89 | 7.71 | 0.17 |
| | | | 0.00 | | | 1" Ice | 9.94 | 9.50 | 0.33 |
| | | | 2.00 | | | 2" Ice | | | |
| BXA-70063/6CF w/ Mount Pipe | C | From Leg | 4.00 | 0.0000 | 117.00 | No Ice | 7.82 | 5.70 | 0.04 |
| | | | 0.00 | | | 1/2" | 8.37 | 6.85 | 0.10 |
| | | | 2.00 | | | Ice | 8.89 | 7.71 | 0.17 |
| (2) LPA-80080/6CF w/ Mount Pipe | A | From Leg | 4.00 | 0.0000 | 117.00 | 1" Ice | 9.94 | 9.50 | 0.33 |
| | | | 0.00 | | | 2" Ice | | | |
| | | | 2.00 | | | No Ice | 7.82 | 5.70 | 0.04 |
| (2) LPA-80063/6CF w/ Mount Pipe | B | From Leg | 4.00 | 0.0000 | 117.00 | 1/2" | 8.37 | 6.85 | 0.10 |
| | | | 0.00 | | | Ice | 8.89 | 7.71 | 0.17 |
| | | | 2.00 | | | 1" Ice | 9.94 | 9.50 | 0.33 |
| (2) LPA-80063/6CF w/ Mount Pipe | C | From Leg | 4.00 | 0.0000 | 117.00 | 2" Ice | | | |
| | | | 0.00 | | | No Ice | 7.82 | 5.70 | 0.04 |
| | | | 2.00 | | | 1/2" | 8.37 | 6.85 | 0.10 |
| (2) LPA-80063/6CF w/ Mount Pipe | A | From Leg | 4.00 | 0.0000 | 117.00 | Ice | 8.89 | 7.71 | 0.17 |
| | | | 0.00 | | | 1" Ice | 9.94 | 9.50 | 0.33 |
| | | | 2.00 | | | 2" Ice | | | |
| (2) FD9R6004/2C-3L | A | From Leg | 4.00 | 0.0000 | 117.00 | No Ice | 0.31 | 0.08 | 0.00 |
| | | | 0.00 | | | 1/2" | 0.39 | 0.12 | 0.01 |
| | | | 2.00 | | | Ice | 0.47 | 0.17 | 0.01 |
| (2) FD9R6004/2C-3L | B | From Leg | 4.00 | 0.0000 | 117.00 | 1" Ice | 0.65 | 0.29 | 0.02 |
| | | | 0.00 | | | 2" Ice | | | |
| | | | 2.00 | | | No Ice | 0.31 | 0.08 | 0.00 |
| (2) FD9R6004/2C-3L | C | From Leg | 4.00 | 0.0000 | 117.00 | 1/2" | 0.39 | 0.12 | 0.01 |
| | | | 0.00 | | | Ice | 0.47 | 0.17 | 0.01 |
| | | | 2.00 | | | 1" Ice | 0.65 | 0.29 | 0.02 |
| (2) FD9R6004/2C-3L | A | From Leg | 4.00 | 0.0000 | 117.00 | 2" Ice | | | |
| | | | 0.00 | | | No Ice | 0.31 | 0.08 | 0.00 |
| | | | 2.00 | | | 1/2" | 0.39 | 0.12 | 0.01 |
| (3) 2.375" OD x 4' Mount Pipe | A | From Leg | 4.00 | 0.0000 | 117.00 | Ice | 0.47 | 0.17 | 0.01 |
| | | | 0.00 | | | 1" Ice | 0.65 | 0.29 | 0.02 |
| | | | 0.00 | | | 2" Ice | | | |

| Description | Face or Leg | Offset Type | Offsets: Horz ft | Azimuth Adjustment ° | Placement ft | C _{AA} Front ft ² | C _{AA} Side ft ² | Weight K | |
|-------------------------------|-------------|-------------|----------------------|----------------------|--------------|---|--|--|--|
| | | | | | | | | | |
| (3) 2.375" OD x 4' Mount Pipe | B | From Leg | 4.00 0.00 0.00 | 0.0000 | 117.00 | 2" Ice No Ice 1/2" Ice 1" Ice 2" Ice No Ice 1/2" Ice 1" Ice 2" Ice No Ice 1/2" Ice 1" Ice 2" Ice | 0.87 1.11 1.36 1.90 0.87 1.11 1.36 1.90 44.83 50.34 56.62 73.47 1.50 2.70 3.90 6.30 1.50 2.70 3.90 6.30 0.84 1.50 2.13 2.94 2.53 3.37 4.12 5.76 | 0.87 1.11 1.36 1.90 0.87 1.11 1.36 1.90 44.83 50.34 56.62 73.47 1.50 2.70 3.90 6.30 0.84 1.50 2.13 2.94 2.53 3.37 4.12 5.76 | 0.02 0.03 0.04 0.06 0.02 0.03 0.04 0.06 3.02 3.95 5.04 7.68 0.03 0.03 0.04 0.06 0.03 0.03 0.04 0.06 0.00 0.01 0.02 0.06 0.08 0.13 0.19 0.36 0.15 0.27 0.39 0.66 0.15 0.27 0.39 0.66 0.15 0.27 0.39 0.66 0.01 0.04 0.06 0.13 0.01 0.04 0.06 0.13 0.01 0.04 |
| Platform Mount [LP 1001-1] | C | None | | 0.0000 | 117.00 | | | | |
| ** | | | | | | | | | |
| DB411-A | A | From Leg | 4.00 0.00 5.00 | 0.0000 | 104.00 | No Ice 1/2" Ice 1" Ice 2" Ice No Ice 1/2" Ice 1" Ice 2" Ice No Ice 1/2" Ice 1" Ice 2" Ice | 1.50 2.70 3.90 6.30 1.50 2.70 3.90 6.30 0.84 1.50 2.13 2.94 2.53 3.37 4.12 5.76 | 1.50 2.70 3.90 6.30 1.50 2.70 3.90 6.30 0.84 1.50 2.13 2.94 2.53 3.37 4.12 5.76 | 0.03 0.03 0.04 0.06 0.03 0.03 0.04 0.06 0.00 0.01 0.02 0.06 0.08 0.13 0.19 0.36 |
| DB411-A | C | From Leg | 4.00 0.00 5.00 | 0.0000 | 104.00 | No Ice 1/2" Ice 1" Ice 2" Ice No Ice 1/2" Ice 1" Ice 2" Ice No Ice 1/2" Ice 1" Ice 2" Ice | 1.50 2.70 3.90 6.30 1.50 2.70 3.90 6.30 0.84 1.50 2.13 2.94 2.53 3.37 4.12 5.76 | 1.50 2.70 3.90 6.30 1.50 2.70 3.90 6.30 0.84 1.50 2.13 2.94 2.53 3.37 4.12 5.76 | 0.03 0.03 0.04 0.06 0.03 0.03 0.04 0.06 0.00 0.01 0.02 0.06 0.08 0.13 0.19 0.36 |
| MFB4505 | B | From Leg | 4.00 0.00 3.00 | 0.0000 | 104.00 | No Ice 1/2" Ice 1" Ice 2" Ice No Ice 1/2" Ice 1" Ice 2" Ice No Ice 1/2" Ice 1" Ice 2" Ice | 0.84 1.50 2.13 2.94 0.84 1.50 2.13 2.94 0.84 1.50 2.13 2.94 2.53 3.37 4.12 5.76 | 0.84 1.50 2.13 2.94 0.84 1.50 2.13 2.94 0.84 1.50 2.13 2.94 2.53 3.37 4.12 5.76 | 0.00 0.01 0.02 0.06 0.00 0.01 0.02 0.06 0.08 0.13 0.19 0.36 |
| Side Arm Mount [SO 702-3] | C | None | | 0.0000 | 104.00 | | | | |
| **** | | | | | | | | | |
| APXVAARR24_43-U-NA20 | A | From Leg | 4.00 0.00 1.00 | 0.0000 | 97.00 | No Ice 1/2" Ice 1" Ice 2" Ice No Ice 1/2" Ice 1" Ice 2" Ice No Ice 1/2" Ice 1" Ice 2" Ice | 14.67 15.43 16.21 17.81 14.67 15.43 16.21 17.81 14.67 15.43 16.21 17.81 14.67 15.43 16.21 17.81 | 5.32 5.99 6.68 8.08 5.32 5.99 6.68 8.08 5.32 5.99 6.68 8.08 5.32 5.99 6.68 8.08 | 0.15 0.27 0.39 0.66 0.15 0.27 0.39 0.66 0.15 0.27 0.39 0.66 0.15 0.27 0.39 0.66 |
| APXVAARR24_43-U-NA20 | B | From Leg | 4.00 0.00 1.00 | 0.0000 | 97.00 | No Ice 1/2" Ice 1" Ice 2" Ice No Ice 1/2" Ice 1" Ice 2" Ice No Ice 1/2" Ice 1" Ice 2" Ice | 14.67 15.43 16.21 17.81 14.67 15.43 16.21 17.81 14.67 15.43 16.21 17.81 14.67 15.43 16.21 17.81 | 5.32 5.99 6.68 8.08 5.32 5.99 6.68 8.08 5.32 5.99 6.68 8.08 5.32 5.99 6.68 8.08 | 0.15 0.27 0.39 0.66 0.15 0.27 0.39 0.66 0.15 0.27 0.39 0.66 0.15 0.27 0.39 0.66 |
| APXVAARR24_43-U-NA20 | C | From Leg | 4.00 0.00 1.00 | 0.0000 | 97.00 | No Ice 1/2" Ice 1" Ice 2" Ice No Ice 1/2" Ice 1" Ice 2" Ice No Ice 1/2" Ice 1" Ice 2" Ice | 14.67 15.43 16.21 17.81 14.67 15.43 16.21 17.81 14.67 15.43 16.21 17.81 14.67 15.43 16.21 17.81 | 5.32 5.99 6.68 8.08 5.32 5.99 6.68 8.08 5.32 5.99 6.68 8.08 5.32 5.99 6.68 8.08 | 0.15 0.27 0.39 0.66 0.15 0.27 0.39 0.66 0.15 0.27 0.39 0.66 0.15 0.27 0.39 0.66 |
| RR90-17-02DP | A | From Leg | 4.00 0.00 1.00 | 0.0000 | 97.00 | No Ice 1/2" Ice 1" Ice 2" Ice No Ice 1/2" Ice 1" Ice 2" Ice No Ice 1/2" Ice 1" Ice 2" Ice | 4.52 5.16 5.83 7.22 4.52 5.16 5.83 7.22 4.52 5.16 5.83 7.22 4.52 5.16 5.83 7.22 | 1.54 2.13 2.75 4.03 1.54 2.13 2.75 4.03 1.54 2.13 2.75 4.03 1.54 2.13 2.75 4.03 | 0.01 0.04 0.06 0.13 0.01 0.04 0.06 0.13 0.01 0.04 0.06 0.13 0.01 0.04 0.06 0.13 |
| RR90-17-02DP | B | From Leg | 4.00 0.00 1.00 | 0.0000 | 97.00 | No Ice 1/2" Ice 1" Ice 2" Ice No Ice 1/2" Ice 1" Ice 2" Ice No Ice 1/2" Ice 1" Ice 2" Ice | 4.52 5.16 5.83 7.22 4.52 5.16 5.83 7.22 4.52 5.16 5.83 7.22 4.52 5.16 5.83 7.22 | 1.54 2.13 2.75 4.03 1.54 2.13 2.75 4.03 1.54 2.13 2.75 4.03 1.54 2.13 2.75 4.03 | 0.01 0.04 0.06 0.13 0.01 0.04 0.06 0.13 0.01 0.04 0.06 0.13 0.01 0.04 0.06 0.13 |
| RR90-17-02DP | C | From Leg | 4.00 0.00 | 0.0000 | 97.00 | No Ice 1/2" Ice 1" Ice 2" Ice No Ice 1/2" | 4.52 5.16 5.83 7.22 4.52 5.16 | 1.54 2.13 2.75 4.03 1.54 2.13 | 0.01 0.04 0.06 0.13 0.01 0.04 |

| Description | Face or Leg | Offset Type | Offsets: Horz Vert ft ft ft | Azimuth Adjustmen t ° | Placement ft | CAA | | Weight K |
|-------------------------------|-------------|-------------|---|--------------------------------|-----------------|---|----------------------------------|------------------------------|
| | | | | | | Front | Side | |
| | | | 1.00 | | | Ice 1" Ice 2" Ice | 5.83 7.22 4.03 | 0.06 0.13 |
| RADIO 4449 B12/B71 | A | From Leg | 4.00 0.00 1.00 | 0.0000 | 97.00 | No Ice 1/2" Ice 1" Ice 2" Ice | 1.65 1.81 1.98 2.34 | 1.16 1.30 1.45 1.76 |
| RADIO 4449 B12/B71 | B | From Leg | 4.00 0.00 1.00 | 0.0000 | 97.00 | No Ice 1/2" Ice 1" Ice 2" Ice | 1.65 1.81 1.98 2.34 | 1.16 1.30 1.45 1.76 |
| RADIO 4449 B12/B71 | C | From Leg | 4.00 0.00 1.00 | 0.0000 | 97.00 | No Ice 1/2" Ice 1" Ice 2" Ice | 1.65 1.81 1.98 2.34 | 1.16 1.30 1.45 1.76 |
| (2) KRY 112 489/2 | A | From Leg | 4.00 0.00 1.00 | 0.0000 | 97.00 | No Ice 1/2" Ice 1" Ice 2" Ice | 0.56 0.66 0.76 1.00 | 0.37 0.45 0.54 0.75 |
| KRY 112 489/2 | C | From Leg | 4.00 0.00 1.00 | 0.0000 | 97.00 | No Ice 1/2" Ice 1" Ice 2" Ice | 0.56 0.66 0.76 1.00 | 0.37 0.45 0.54 0.75 |
| (2) KRY 112 144/1 | B | From Leg | 4.00 0.00 1.00 | 0.0000 | 97.00 | No Ice 1/2" Ice 1" Ice 2" Ice | 0.35 0.43 0.51 0.70 | 0.17 0.23 0.30 0.46 |
| KRY 112 144/1 | C | From Leg | 4.00 0.00 1.00 | 0.0000 | 97.00 | No Ice 1/2" Ice 1" Ice 2" Ice | 0.35 0.43 0.51 0.70 | 0.17 0.23 0.30 0.46 |
| Platform Mount [LP 301-1] | C | None | | 0.0000 | 97.00 | No Ice 1/2" Ice 1" Ice 2" Ice | 23.81 30.24 36.33 48.05 | 1.59 2.10 2.73 4.34 |
| ** | | | | | | | | |
| 7770.00 w/ Mount Pipe | A | From Leg | 4.00 0.00 2.00 | 0.0000 | 87.00 | No Ice 1/2" Ice 1" Ice 2" Ice | 5.75 6.18 6.61 7.49 | 4.25 5.01 5.71 7.16 |
| 7770.00 w/ Mount Pipe | B | From Leg | 4.00 0.00 2.00 | 0.0000 | 87.00 | No Ice 1/2" Ice 1" Ice 2" Ice | 5.75 6.18 6.61 7.49 | 4.25 5.01 5.71 7.16 |
| 7770.00 w/ Mount Pipe | C | From Leg | 4.00 0.00 2.00 | 0.0000 | 87.00 | No Ice 1/2" Ice 1" Ice 2" Ice | 5.75 6.18 6.61 7.49 | 4.25 5.01 5.71 7.16 |
| (2) HPA65R-BU6A w/ Mount Pipe | A | From Leg | 4.00 0.00 2.00 | 0.0000 | 87.00 | No Ice 1/2" Ice 1" Ice 2" Ice | 5.83 6.40 6.99 8.19 | 5.00 5.56 6.13 7.32 |
| (2) HPA65R-BU6A w/ | B | From Leg | 4.00 | 0.0000 | 87.00 | No Ice | 5.83 | 5.00 |

| Description | Face or Leg | Offset Type | Offsets: Horz Vert ft ft ft | Azimuth Adjustmen t ° | Placement ft | C _{AA} | | Weight K | |
|-------------------------------|-------------|-------------|---|--------------------------------|---------------------------------|---|----------------------------------|-------------------------------|------------------------------|
| | | | | | | Front | Side | | |
| Mount Pipe | | | 0.00 2.00 | | 1/2" Ice 1" Ice 2" Ice | 6.40 6.99 8.19 | 5.56 6.13 7.32 | 0.14 0.22 0.40 | |
| (2) HPA65R-BU8A w/ Mount Pipe | C | From Leg | 4.00 0.00 2.00 | 0.0000 | 87.00 | No Ice 1/2" Ice 1" Ice 2" Ice | 8.10 8.86 9.64 11.24 | 6.94 7.69 8.45 10.03 | 0.09 0.17 0.27 0.50 |
| 80010965 w/ Mount Pipe | A | From Leg | 4.00 0.00 2.00 | 0.0000 | 87.00 | No Ice 1/2" Ice 1" Ice 2" Ice | 12.26 13.03 13.80 15.41 | 5.79 6.47 7.17 8.60 | 0.14 0.23 0.33 0.57 |
| 80010965 w/ Mount Pipe | B | From Leg | 4.00 0.00 2.00 | 0.0000 | 87.00 | No Ice 1/2" Ice 1" Ice 2" Ice | 12.26 13.03 13.80 15.41 | 5.79 6.47 7.17 8.60 | 0.14 0.23 0.33 0.57 |
| 80010966 w/ Mount Pipe | C | From Leg | 4.00 0.00 2.00 | 0.0000 | 87.00 | No Ice 1/2" Ice 1" Ice 2" Ice | 14.61 15.47 16.35 18.14 | 6.84 7.63 8.42 10.06 | 0.16 0.27 0.39 0.68 |
| (4) LGP21401 | A | From Leg | 4.00 0.00 2.00 | 0.0000 | 87.00 | No Ice 1/2" Ice 1" Ice 2" Ice | 1.10 1.24 1.38 1.69 | 0.21 0.27 0.35 0.52 | 0.01 0.02 0.03 0.05 |
| (2) LGP21401 | B | From Leg | 4.00 0.00 2.00 | 0.0000 | 87.00 | No Ice 1/2" Ice 1" Ice 2" Ice | 1.10 1.24 1.38 1.69 | 0.21 0.27 0.35 0.52 | 0.01 0.02 0.03 0.05 |
| (2) RRUS 4415 B25 | B | From Leg | 4.00 0.00 2.00 | 0.0000 | 87.00 | No Ice 1/2" Ice 1" Ice 2" Ice | 1.64 1.80 1.97 2.33 | 0.68 0.79 0.91 1.18 | 0.04 0.06 0.07 0.11 |
| RRUS 4415 B25 | C | From Leg | 4.00 0.00 2.00 | 0.0000 | 87.00 | No Ice 1/2" Ice 1" Ice 2" Ice | 1.64 1.80 1.97 2.33 | 0.68 0.79 0.91 1.18 | 0.04 0.06 0.07 0.11 |
| (2) DC6-48-60-18-8C-EV | C | From Leg | 4.00 0.00 2.00 | 0.0000 | 87.00 | No Ice 1/2" Ice 1" Ice 2" Ice | 1.14 1.79 2.00 2.45 | 1.14 1.79 2.00 2.45 | 0.03 0.05 0.07 0.13 |
| (2) RRUS 4449 B5/B12 | A | From Leg | 4.00 0.00 2.00 | 0.0000 | 87.00 | No Ice 1/2" Ice 1" Ice 2" Ice | 1.97 2.14 2.33 2.72 | 1.41 1.56 1.73 2.07 | 0.07 0.09 0.11 0.16 |
| RRUS 4449 B5/B12 | B | From Leg | 4.00 0.00 2.00 | 0.0000 | 87.00 | No Ice 1/2" Ice 1" Ice 2" Ice | 1.97 2.14 2.33 2.72 | 1.41 1.56 1.73 2.07 | 0.07 0.09 0.11 0.16 |
| (3) RRUS 8843 B2/B66A | C | From Leg | 4.00 0.00 2.00 | 0.0000 | 87.00 | No Ice 1/2" Ice 1" Ice 2" Ice | 1.64 1.80 1.97 2.32 | 1.35 1.50 1.65 1.99 | 0.07 0.09 0.11 0.16 |
| DC6-48-60-18-8F | B | From Leg | 4.00 | 0.0000 | 87.00 | No Ice | 1.21 | 1.21 | 0.02 |

| Description | Face or Leg | Offset Type | Offsets: Horz ft ft ft | Azimuth Adjustmen t ° | Placement ft | C _{AA} Front | C _{AA} Side | Weight K |
|---------------------------|-------------|-------------|--|--|---|--|--|--|
| | | | | | | | | |
| Platform Mount [LP 304-1] | C | None | 0.00 2.00 0.0000 87.00 No Ice 1/2" Ice 1" Ice 2" Ice 1/2" Ice 25.28 1" Ice 2" Ice | 0.00 2.00 0.0000 87.00 No Ice 1/2" Ice 1" Ice 2" Ice 1/2" Ice 25.28 1" Ice 2" Ice | 1/2" Ice 1" Ice 2" Ice 1/2" Ice 25.28 1" Ice 2" Ice | 1.89 2.11 2.57 21.37 25.28 33.17 | 1.89 2.11 2.57 21.37 25.28 33.17 | 0.04 0.07 0.13 1.71 2.13 3.16 |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| 742 213 | A | From Leg | 1.00 0.00 2.00 0.0000 75.00 No Ice 1/2" Ice 1" Ice 2" Ice 1/2" Ice 4.86 6.21 | 1.00 0.00 2.00 0.0000 75.00 No Ice 1/2" Ice 1" Ice 2" Ice 1/2" Ice 4.86 6.21 | 3.57 4.21 2.83 4.13 3.57 4.21 2.83 4.13 | 1.60 2.21 0.08 0.16 1.60 2.21 0.08 0.16 | 0.02 0.05 0.08 0.16 0.02 0.05 0.08 0.16 | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| 742 213 | B | From Leg | 1.00 0.00 2.00 0.0000 75.00 No Ice 1/2" Ice 1" Ice 2" Ice 1/2" Ice 4.86 6.21 | 1.00 0.00 2.00 0.0000 75.00 No Ice 1/2" Ice 1" Ice 2" Ice 1/2" Ice 4.86 6.21 | 3.57 4.21 2.83 4.13 | 1.60 2.21 0.08 0.16 | 0.02 0.05 0.08 0.16 | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| 742 213 | C | From Leg | 1.00 0.00 2.00 0.0000 75.00 No Ice 1/2" Ice 1" Ice 2" Ice 1/2" Ice 4.86 6.21 | 1.00 0.00 2.00 0.0000 75.00 No Ice 1/2" Ice 1" Ice 2" Ice 1/2" Ice 4.86 6.21 | 3.57 4.21 2.83 4.13 | 1.60 2.21 0.08 0.16 | 0.02 0.05 0.08 0.16 | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| Pipe Mount [PM 601-3] | C | None | 0.0000 75.00 No Ice 1/2" Ice 1" Ice 2" Ice 1/2" Ice 3.17 3.79 4.42 5.76 | 0.0000 75.00 No Ice 1/2" Ice 1" Ice 2" Ice 1/2" Ice 3.17 3.79 4.42 5.76 | 3.17 3.79 4.42 5.76 | 3.17 3.79 4.42 5.76 | 0.20 0.23 0.28 0.40 | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |

Tower Pressures - No Ice

G_H = 1.100

| Section Elevation ft | z ft | K _z | q _z | A _G ft ² | F a c e | A _F ft ² | A _R ft ² | A _{leg} ft ² | Leg % | C _{AA} In Face ft ² | C _{AA} Out Face ft ² |
|-------------------------|---------|----------------|----------------|-----------------------------------|------------------|-----------------------------------|-----------------------------------|-------------------------------------|--------|---|--|
| L1 115.50-83.92 | 99.27 | 0.986 | 38 | 99.320 | A | 0.000 | 99.320 | 99.320 | 100.00 | 3.847 | 0.000 |
| | | | | | B | 0.000 | 99.320 | | 100.00 | 4.418 | 0.000 |
| | | | | | C | 0.000 | 99.320 | | 100.00 | 0.000 | 0.000 |
| L2 83.92-41.25 | 62.21 | 0.863 | 33 | 169.405 | A | 0.000 | 169.405 | 169.405 | 100.00 | 53.289 | 0.000 |
| | | | | | B | 0.000 | 169.405 | | 100.00 | 9.387 | 0.000 |
| L3 41.25-0.00 | 19.99 | 0.7 | 27 | 202.030 | A | 0.000 | 202.030 | 202.030 | 100.00 | 51.516 | 0.000 |
| | | | | | B | 0.000 | 202.030 | | 100.00 | 9.075 | 0.000 |

| Section Elevation | z | K _z | q _z | A _G | F _a c _e | A _F | A _R | A _{leg} | Leg % | C _{AA} A _{In} Face ft ² | C _{AA} A _{Out} Face ft ² |
|-------------------|----|----------------|----------------|-----------------|-------------------------------|-----------------|-----------------|------------------|--------|--|---|
| ft | ft | | psf | ft ² | | ft ² | ft ² | ft ² | | | |
| | | | | C | | 0.000 | 202.030 | | 100.00 | 0.000 | 0.000 |

Tower Pressure - With Ice

G_H = 1.100

| Section Elevation | z | K _z | q _z | t _z | A _G | F _a c _e | A _F | A _R | A _{leg} | Leg % | C _{AA} A _{In} Face ft ² | C _{AA} A _{Out} Face ft ² |
|-------------------|-------|----------------|----------------|----------------|-----------------|-------------------------------|-----------------|-----------------|------------------|--------|--|---|
| ft | ft | | psf | in | ft ² | | ft ² | ft ² | ft ² | | | |
| L1 115.50-83.92 | 99.27 | 0.986 | 6 | 1.4234 | 106.812 | A | 0.000 | 106.812 | 106.812 | 100.00 | 8.541 | 0.000 |
| | | | | | | B | 0.000 | 106.812 | | 100.00 | 12.668 | 0.000 |
| | | | | | | C | 0.000 | 106.812 | | 100.00 | 0.000 | 0.000 |
| L2 83.92-41.25 | 62.21 | 0.863 | 5 | 1.3585 | 179.528 | A | 0.000 | 179.528 | 179.528 | 100.00 | 118.323 | 0.000 |
| | | | | | | B | 0.000 | 179.528 | | 100.00 | 26.919 | 0.000 |
| | | | | | | C | 0.000 | 179.528 | | 100.00 | 0.000 | 0.000 |
| L3 41.25-0.00 | 19.99 | 0.7 | 4 | 1.2126 | 211.369 | A | 0.000 | 211.369 | 211.369 | 100.00 | 111.973 | 0.000 |
| | | | | | | B | 0.000 | 211.369 | | 100.00 | 25.353 | 0.000 |
| | | | | | | C | 0.000 | 211.369 | | 100.00 | 0.000 | 0.000 |

Tower Pressure - Service

G_H = 1.100

| Section Elevation | z | K _z | q _z | A _G | F _a c _e | A _F | A _R | A _{leg} | Leg % | C _{AA} A _{In} Face ft ² | C _{AA} A _{Out} Face ft ² |
|-------------------|-------|----------------|----------------|-----------------|-------------------------------|-----------------|-----------------|------------------|--------|--|---|
| ft | ft | | psf | ft ² | | ft ² | ft ² | ft ² | | | |
| L1 115.50-83.92 | 99.27 | 0.986 | 8 | 99.320 | A | 0.000 | 99.320 | 99.320 | 100.00 | 3.847 | 0.000 |
| | | | | | B | 0.000 | 99.320 | | 100.00 | 4.418 | 0.000 |
| | | | | | C | 0.000 | 99.320 | | 100.00 | 0.000 | 0.000 |
| L2 83.92-41.25 | 62.21 | 0.863 | 7 | 169.40 | A | 0.000 | 169.405 | 169.405 | 100.00 | 53.289 | 0.000 |
| | | | | 5 | B | 0.000 | 169.405 | | 100.00 | 9.387 | 0.000 |
| | | | | | C | 0.000 | 169.405 | | 100.00 | 0.000 | 0.000 |
| L3 41.25-0.00 | 19.99 | 0.7 | 5 | 202.03 | A | 0.000 | 202.030 | 202.030 | 100.00 | 51.516 | 0.000 |
| | | | 0 | | B | 0.000 | 202.030 | | 100.00 | 9.075 | 0.000 |
| | | | | | C | 0.000 | 202.030 | | 100.00 | 0.000 | 0.000 |

Load Combinations

| Comb. No. | Description |
|-----------|------------------------------------|
| 1 | Dead Only |
| 2 | 1.2 Dead+1.0 Wind 0 deg - No Ice |
| 3 | 0.9 Dead+1.0 Wind 0 deg - No Ice |
| 4 | 1.2 Dead+1.0 Wind 30 deg - No Ice |
| 5 | 0.9 Dead+1.0 Wind 30 deg - No Ice |
| 6 | 1.2 Dead+1.0 Wind 60 deg - No Ice |
| 7 | 0.9 Dead+1.0 Wind 60 deg - No Ice |
| 8 | 1.2 Dead+1.0 Wind 90 deg - No Ice |
| 9 | 0.9 Dead+1.0 Wind 90 deg - No Ice |
| 10 | 1.2 Dead+1.0 Wind 120 deg - No Ice |
| 11 | 0.9 Dead+1.0 Wind 120 deg - No Ice |
| 12 | 1.2 Dead+1.0 Wind 150 deg - No Ice |
| 13 | 0.9 Dead+1.0 Wind 150 deg - No Ice |
| 14 | 1.2 Dead+1.0 Wind 180 deg - No Ice |
| 15 | 0.9 Dead+1.0 Wind 180 deg - No Ice |

| Comb. No. | Description |
|--------------|--|
| 16 | 1.2 Dead+1.0 Wind 210 deg - No Ice |
| 17 | 0.9 Dead+1.0 Wind 210 deg - No Ice |
| 18 | 1.2 Dead+1.0 Wind 240 deg - No Ice |
| 19 | 0.9 Dead+1.0 Wind 240 deg - No Ice |
| 20 | 1.2 Dead+1.0 Wind 270 deg - No Ice |
| 21 | 0.9 Dead+1.0 Wind 270 deg - No Ice |
| 22 | 1.2 Dead+1.0 Wind 300 deg - No Ice |
| 23 | 0.9 Dead+1.0 Wind 300 deg - No Ice |
| 24 | 1.2 Dead+1.0 Wind 330 deg - No Ice |
| 25 | 0.9 Dead+1.0 Wind 330 deg - No Ice |
| 26 | 1.2 Dead+1.0 Ice+1.0 Temp |
| 27 | 1.2 Dead+1.0 Wind 0 deg+1.0 Ice+1.0 Temp |
| 28 | 1.2 Dead+1.0 Wind 30 deg+1.0 Ice+1.0 Temp |
| 29 | 1.2 Dead+1.0 Wind 60 deg+1.0 Ice+1.0 Temp |
| 30 | 1.2 Dead+1.0 Wind 90 deg+1.0 Ice+1.0 Temp |
| 31 | 1.2 Dead+1.0 Wind 120 deg+1.0 Ice+1.0 Temp |
| 32 | 1.2 Dead+1.0 Wind 150 deg+1.0 Ice+1.0 Temp |
| 33 | 1.2 Dead+1.0 Wind 180 deg+1.0 Ice+1.0 Temp |
| 34 | 1.2 Dead+1.0 Wind 210 deg+1.0 Ice+1.0 Temp |
| 35 | 1.2 Dead+1.0 Wind 240 deg+1.0 Ice+1.0 Temp |
| 36 | 1.2 Dead+1.0 Wind 270 deg+1.0 Ice+1.0 Temp |
| 37 | 1.2 Dead+1.0 Wind 300 deg+1.0 Ice+1.0 Temp |
| 38 | 1.2 Dead+1.0 Wind 330 deg+1.0 Ice+1.0 Temp |
| 39 | Dead+Wind 0 deg - Service |
| 40 | Dead+Wind 30 deg - Service |
| 41 | Dead+Wind 60 deg - Service |
| 42 | Dead+Wind 90 deg - Service |
| 43 | Dead+Wind 120 deg - Service |
| 44 | Dead+Wind 150 deg - Service |
| 45 | Dead+Wind 180 deg - Service |
| 46 | Dead+Wind 210 deg - Service |
| 47 | Dead+Wind 240 deg - Service |
| 48 | Dead+Wind 270 deg - Service |
| 49 | Dead+Wind 300 deg - Service |
| 50 | Dead+Wind 330 deg - Service |

Maximum Member Forces

| Section No. | Elevation ft | Component Type | Condition | Gov. Load Comb. | Axial K | Major Axis Moment kip-ft | Minor Axis Moment kip-ft |
|----------------|------------------|-------------------|------------------|-----------------------|------------|--------------------------------|--------------------------------|
| L1 | 115.5 - 83.92 | Pole | Max Tension | 1 | 0.00 | 0.00 | 0.00 |
| | | | Max. Compression | 26 | -22.80 | 0.16 | -0.57 |
| | | | Max. Mx | 20 | -10.83 | 253.81 | 0.19 |
| | | | Max. My | 2 | -10.85 | 0.19 | 239.85 |
| | | | Max. Vy | 20 | -12.50 | 253.81 | 0.19 |
| | | | Max. Vx | 14 | 12.03 | 0.19 | -239.44 |
| L2 | 83.92 - 41.25 | Pole | Max Tension | 1 | 0.00 | 0.00 | 0.00 |
| | | | Max. Compression | 26 | -46.99 | 4.51 | -0.34 |
| | | | Max. Mx | 20 | -24.66 | 1059.34 | 0.24 |
| | | | Max. My | 14 | -24.67 | 1.30 | -1025.11 |
| | | | Max. Vy | 20 | -22.46 | 1059.34 | 0.24 |
| | | | Max. Vx | 2 | -22.00 | 1.86 | 1025.04 |
| L3 | 41.25 - 0 | Pole | Max. Torque | 25 | | 1.51 | |
| | | | Max Tension | 1 | 0.00 | 0.00 | 0.00 |
| | | | Max. Compression | 26 | -70.10 | 7.82 | 2.34 |
| | | | Max. Mx | 20 | -41.53 | 2288.63 | 1.13 |
| | | | Max. My | 2 | -41.53 | 2.92 | 2232.66 |
| | | | Max. Vy | 20 | -28.77 | 2288.63 | 1.13 |
| | | | Max. Vx | 2 | -28.33 | 2.92 | 2232.66 |
| | | | Max. Torque | 25 | | 1.51 | |

Maximum Reactions

| Location | Condition | Gov. Load Comb. | Vertical K | Horizontal, X K | Horizontal, Z K |
|----------|---------------------|-----------------|------------|-----------------|-----------------|
| Pole | Max. Vert | 26 | 70.10 | -0.00 | 0.00 |
| | Max. H _x | 21 | 31.15 | 28.76 | 0.01 |
| | Max. H _z | 3 | 31.15 | 0.01 | 28.31 |
| | Max. M _x | 2 | 2232.66 | 0.01 | 28.31 |
| | Max. M _z | 8 | 2283.99 | -28.76 | -0.01 |
| | Max. Torsion | 25 | 1.51 | 14.38 | 24.52 |
| | Min. Vert | 21 | 31.15 | 28.76 | 0.01 |
| | Min. H _x | 9 | 31.15 | -28.76 | -0.01 |
| | Min. H _z | 15 | 31.15 | -0.01 | -28.31 |
| | Min. M _x | 14 | -2231.60 | -0.01 | -28.31 |
| | Min. M _z | 20 | -2288.63 | 28.76 | 0.01 |
| | Min. Torsion | 13 | -1.48 | -14.38 | -24.52 |

Tower Mast Reaction Summary

| Load Combination | Vertical | Shear _x | Shear _z | Overswing Moment, M _x | Overswing Moment, M _z | Torque |
|-----------------------------|----------|--------------------|--------------------|----------------------------------|----------------------------------|--------|
| | K | K | K | kip-ft | kip-ft | kip-ft |
| Dead Only | 34.61 | -0.00 | 0.00 | -0.44 | 1.90 | 0.00 |
| 1.2 Dead+1.0 Wind 0 deg - | 41.54 | -0.01 | -28.31 | -2232.66 | 2.92 | -1.32 |
| No Ice | | | | | | |
| 0.9 Dead+1.0 Wind 0 deg - | 31.15 | -0.01 | -28.31 | -2224.79 | 2.33 | -1.32 |
| No Ice | | | | | | |
| 1.2 Dead+1.0 Wind 30 deg - | 41.54 | 14.49 | -24.73 | -1946.54 | -1147.96 | -0.79 |
| No Ice | | | | | | |
| 0.9 Dead+1.0 Wind 30 deg - | 31.15 | 14.49 | -24.73 | -1939.66 | -1144.54 | -0.79 |
| No Ice | | | | | | |
| 1.2 Dead+1.0 Wind 60 deg - | 41.54 | 24.90 | -14.15 | -1116.09 | -1977.44 | -0.05 |
| No Ice | | | | | | |
| 0.9 Dead+1.0 Wind 60 deg - | 31.15 | 24.90 | -14.15 | -1112.09 | -1971.12 | -0.05 |
| No Ice | | | | | | |
| 1.2 Dead+1.0 Wind 90 deg - | 41.54 | 28.76 | 0.01 | 0.08 | -2283.99 | 0.69 |
| No Ice | | | | | | |
| 0.9 Dead+1.0 Wind 90 deg - | 31.15 | 28.76 | 0.01 | 0.21 | -2276.62 | 0.69 |
| No Ice | | | | | | |
| 1.2 Dead+1.0 Wind 120 deg - | 41.54 | 24.91 | 14.16 | 1116.09 | -1978.05 | 1.24 |
| - No Ice | | | | | | |
| 0.9 Dead+1.0 Wind 120 deg - | 31.15 | 24.91 | 14.16 | 1112.34 | -1971.72 | 1.24 |
| - No Ice | | | | | | |
| 1.2 Dead+1.0 Wind 150 deg - | 41.54 | 14.38 | 24.52 | 1932.91 | -1141.40 | 1.47 |
| - No Ice | | | | | | |
| 0.9 Dead+1.0 Wind 150 deg - | 31.15 | 14.38 | 24.52 | 1926.32 | -1138.00 | 1.48 |
| - No Ice | | | | | | |
| 1.2 Dead+1.0 Wind 180 deg - | 41.54 | 0.01 | 28.31 | 2231.60 | 1.71 | 1.32 |
| - No Ice | | | | | | |
| 0.9 Dead+1.0 Wind 180 deg - | 31.15 | 0.01 | 28.31 | 2224.00 | 1.13 | 1.33 |
| - No Ice | | | | | | |
| 1.2 Dead+1.0 Wind 210 deg - | 41.54 | -14.49 | 24.73 | 1945.49 | 1152.60 | 0.82 |
| - No Ice | | | | | | |
| 0.9 Dead+1.0 Wind 210 deg - | 31.15 | -14.49 | 24.73 | 1938.87 | 1148.01 | 0.82 |
| - No Ice | | | | | | |
| 1.2 Dead+1.0 Wind 240 deg - | 41.54 | -24.90 | 14.15 | 1115.04 | 1982.08 | 0.08 |
| - No Ice | | | | | | |
| 0.9 Dead+1.0 Wind 240 deg - | 31.15 | -24.90 | 14.15 | 1111.30 | 1974.58 | 0.08 |
| - No Ice | | | | | | |
| 1.2 Dead+1.0 Wind 270 deg - | 41.54 | -28.76 | -0.01 | -1.13 | 2288.63 | -0.69 |
| - No Ice | | | | | | |
| 0.9 Dead+1.0 Wind 270 deg - | 31.15 | -28.76 | -0.01 | -1.00 | 2280.08 | -0.69 |
| - No Ice | | | | | | |
| 1.2 Dead+1.0 Wind 300 deg - | 41.54 | -24.91 | -14.16 | -1117.14 | 1982.68 | -1.27 |
| - No Ice | | | | | | |
| 0.9 Dead+1.0 Wind 300 deg | 31.15 | -24.91 | -14.16 | -1113.13 | 1975.19 | -1.27 |

| Load Combination | Vertical | Shear _x | Shear _z | Overshooting Moment, M _x kip-ft | Overshooting Moment, M _z kip-ft | Torque |
|--|----------|--------------------|--------------------|---|---|--------|
| | K | K | K | kip-ft | kip-ft | kip-ft |
| - No Ice | | | | | | |
| 1.2 Dead+1.0 Wind 330 deg | 41.54 | -14.38 | -24.52 | -1933.96 | 1146.04 | -1.50 |
| - No Ice | | | | | | |
| 0.9 Dead+1.0 Wind 330 deg | 31.15 | -14.38 | -24.52 | -1927.11 | 1141.46 | -1.51 |
| - No Ice | | | | | | |
| 1.2 Dead+1.0 Ice+1.0 Temp | 70.10 | 0.00 | -0.00 | -2.34 | 7.82 | 0.00 |
| 1.2 Dead+1.0 Wind 0 deg+1.0 Ice+1.0 Temp | 70.10 | -0.00 | -5.77 | -468.70 | 8.20 | -0.29 |
| 1.2 Dead+1.0 Wind 30 deg+1.0 Ice+1.0 Temp | 70.10 | 2.91 | -4.99 | -406.13 | -229.05 | -0.19 |
| 1.2 Dead+1.0 Wind 60 deg+1.0 Ice+1.0 Temp | 70.10 | 5.05 | -2.88 | -235.37 | -402.77 | -0.03 |
| 1.2 Dead+1.0 Wind 90 deg+1.0 Ice+1.0 Temp | 70.10 | 5.83 | 0.00 | -2.17 | -466.43 | 0.13 |
| 1.2 Dead+1.0 Wind 120 deg+1.0 Ice+1.0 Temp | 70.10 | 5.05 | 2.88 | 230.98 | -402.95 | 0.26 |
| 1.2 Dead+1.0 Wind 150 deg+1.0 Ice+1.0 Temp | 70.10 | 2.92 | 4.99 | 401.60 | -229.36 | 0.32 |
| 1.2 Dead+1.0 Wind 180 deg+1.0 Ice+1.0 Temp | 70.10 | 0.00 | 5.77 | 463.99 | 7.84 | 0.29 |
| 1.2 Dead+1.0 Wind 210 deg+1.0 Ice+1.0 Temp | 70.10 | -2.91 | 4.99 | 401.42 | 245.08 | 0.19 |
| 1.2 Dead+1.0 Wind 240 deg+1.0 Ice+1.0 Temp | 70.10 | -5.05 | 2.88 | 230.66 | 418.81 | 0.03 |
| 1.2 Dead+1.0 Wind 270 deg+1.0 Ice+1.0 Temp | 70.10 | -5.83 | -0.00 | -2.53 | 482.46 | -0.13 |
| 1.2 Dead+1.0 Wind 300 deg+1.0 Ice+1.0 Temp | 70.10 | -5.05 | -2.88 | -235.68 | 418.99 | -0.26 |
| 1.2 Dead+1.0 Wind 330 deg+1.0 Ice+1.0 Temp | 70.10 | -2.92 | -4.99 | -406.31 | 245.40 | -0.32 |
| Dead+Wind 0 deg - Service | 34.61 | -0.00 | -5.68 | -447.22 | 2.05 | -0.27 |
| Dead+Wind 30 deg - Service | 34.61 | 2.91 | -4.96 | -389.95 | -228.31 | -0.16 |
| Dead+Wind 60 deg - Service | 34.61 | 5.00 | -2.84 | -223.73 | -394.33 | -0.01 |
| Dead+Wind 90 deg - Service | 34.61 | 5.77 | 0.00 | -0.32 | -455.70 | 0.14 |
| Dead+Wind 120 deg - Service | 34.61 | 5.00 | 2.84 | 223.06 | -394.45 | 0.25 |
| Dead+Wind 150 deg - Service | 34.61 | 2.89 | 4.92 | 386.55 | -226.99 | 0.30 |
| Dead+Wind 180 deg - Service | 34.61 | 0.00 | 5.68 | 446.34 | 1.81 | 0.27 |
| Dead+Wind 210 deg - Service | 34.61 | -2.91 | 4.96 | 389.07 | 232.16 | 0.16 |
| Dead+Wind 240 deg - Service | 34.61 | -5.00 | 2.84 | 222.85 | 398.18 | 0.01 |
| Dead+Wind 270 deg - Service | 34.61 | -5.77 | -0.00 | -0.56 | 459.55 | -0.14 |
| Dead+Wind 300 deg - Service | 34.61 | -5.00 | -2.84 | -223.94 | 398.30 | -0.25 |
| Dead+Wind 330 deg - Service | 34.61 | -2.89 | -4.92 | -387.43 | 230.85 | -0.30 |

Solution Summary

| Load Comb. | Sum of Applied Forces | | | Sum of Reactions | | | % Error |
|------------|-----------------------|--------|--------|------------------|-------|--------|---------|
| | PX K | PY K | PZ K | PX K | PY K | PZ K | |
| 1 | 0.00 | -34.61 | 0.00 | 0.00 | 34.61 | 0.00 | 0.000% |
| 2 | -0.01 | -41.54 | -28.31 | 0.01 | 41.54 | 28.31 | 0.001% |
| 3 | -0.01 | -31.15 | -28.31 | 0.01 | 31.15 | 28.31 | 0.001% |
| 4 | 14.49 | -41.54 | -24.73 | -14.49 | 41.54 | 24.73 | 0.000% |
| 5 | 14.49 | -31.15 | -24.73 | -14.49 | 31.15 | 24.73 | 0.000% |
| 6 | 24.90 | -41.54 | -14.15 | -24.90 | 41.54 | 14.15 | 0.000% |
| 7 | 24.90 | -31.15 | -14.15 | -24.90 | 31.15 | 14.15 | 0.000% |
| 8 | 28.76 | -41.54 | 0.01 | -28.76 | 41.54 | -0.01 | 0.002% |
| 9 | 28.76 | -31.15 | 0.01 | -28.76 | 31.15 | -0.01 | 0.001% |
| 10 | 24.91 | -41.54 | 14.16 | -24.91 | 41.54 | -14.16 | 0.000% |

| Load Comb. | Sum of Applied Forces | | | Sum of Reactions | | | % Error |
|------------|-----------------------|--------|--------|------------------|-------|--------|---------|
| | PX K | PY K | PZ K | PX K | PY K | PZ K | |
| 11 | 24.91 | -31.15 | 14.16 | -24.91 | 31.15 | -14.16 | 0.000% |
| 12 | 14.38 | -41.54 | 24.52 | -14.38 | 41.54 | -24.52 | 0.000% |
| 13 | 14.38 | -31.15 | 24.52 | -14.38 | 31.15 | -24.52 | 0.000% |
| 14 | 0.01 | -41.54 | 28.31 | -0.01 | 41.54 | -28.31 | 0.001% |
| 15 | 0.01 | -31.15 | 28.31 | -0.01 | 31.15 | -28.31 | 0.001% |
| 16 | -14.49 | -41.54 | 24.73 | 14.49 | 41.54 | -24.73 | 0.000% |
| 17 | -14.49 | -31.15 | 24.73 | 14.49 | 31.15 | -24.73 | 0.000% |
| 18 | -24.90 | -41.54 | 14.15 | 24.90 | 41.54 | -14.15 | 0.000% |
| 19 | -24.90 | -31.15 | 14.15 | 24.90 | 31.15 | -14.15 | 0.000% |
| 20 | -28.76 | -41.54 | -0.01 | 28.76 | 41.54 | 0.01 | 0.002% |
| 21 | -28.76 | -31.15 | -0.01 | 28.76 | 31.15 | 0.01 | 0.001% |
| 22 | -24.91 | -41.54 | -14.16 | 24.91 | 41.54 | 14.16 | 0.000% |
| 23 | -24.91 | -31.15 | -14.16 | 24.91 | 31.15 | 14.16 | 0.000% |
| 24 | -14.38 | -41.54 | -24.52 | 14.38 | 41.54 | 24.52 | 0.000% |
| 25 | -14.38 | -31.15 | -24.52 | 14.38 | 31.15 | 24.52 | 0.000% |
| 26 | 0.00 | -70.10 | 0.00 | -0.00 | 70.10 | 0.00 | 0.000% |
| 27 | -0.00 | -70.10 | -5.77 | 0.00 | 70.10 | 5.77 | 0.000% |
| 28 | 2.91 | -70.10 | -4.99 | -2.91 | 70.10 | 4.99 | 0.000% |
| 29 | 5.05 | -70.10 | -2.88 | -5.05 | 70.10 | 2.88 | 0.000% |
| 30 | 5.83 | -70.10 | 0.00 | -5.83 | 70.10 | -0.00 | 0.000% |
| 31 | 5.05 | -70.10 | 2.89 | -5.05 | 70.10 | -2.88 | 0.000% |
| 32 | 2.92 | -70.10 | 4.99 | -2.92 | 70.10 | -4.99 | 0.000% |
| 33 | 0.00 | -70.10 | 5.77 | -0.00 | 70.10 | -5.77 | 0.000% |
| 34 | -2.91 | -70.10 | 4.99 | 2.91 | 70.10 | -4.99 | 0.000% |
| 35 | -5.05 | -70.10 | 2.88 | 5.05 | 70.10 | -2.88 | 0.000% |
| 36 | -5.83 | -70.10 | -0.00 | 5.83 | 70.10 | 0.00 | 0.000% |
| 37 | -5.05 | -70.10 | -2.89 | 5.05 | 70.10 | 2.88 | 0.000% |
| 38 | -2.92 | -70.10 | -4.99 | 2.92 | 70.10 | -4.99 | 0.000% |
| 39 | -0.00 | -34.61 | -5.68 | 0.00 | 34.61 | 5.68 | 0.002% |
| 40 | 2.91 | -34.61 | -4.96 | -2.91 | 34.61 | 4.96 | 0.002% |
| 41 | 5.00 | -34.61 | -2.84 | -5.00 | 34.61 | 2.84 | 0.002% |
| 42 | 5.77 | -34.61 | 0.00 | -5.77 | 34.61 | -0.00 | 0.002% |
| 43 | 5.00 | -34.61 | 2.84 | -5.00 | 34.61 | -2.84 | 0.002% |
| 44 | 2.89 | -34.61 | 4.92 | -2.89 | 34.61 | -4.92 | 0.002% |
| 45 | 0.00 | -34.61 | 5.68 | -0.00 | 34.61 | -5.68 | 0.002% |
| 46 | -2.91 | -34.61 | 4.96 | 2.91 | 34.61 | -4.96 | 0.002% |
| 47 | -5.00 | -34.61 | 2.84 | 5.00 | 34.61 | -2.84 | 0.002% |
| 48 | -5.77 | -34.61 | -0.00 | 5.77 | 34.61 | 0.00 | 0.002% |
| 49 | -5.00 | -34.61 | -2.84 | 5.00 | 34.61 | 2.84 | 0.002% |
| 50 | -2.89 | -34.61 | -4.92 | 2.89 | 34.61 | 4.92 | 0.002% |

Non-Linear Convergence Results

| Load Combination | Converged? | Number of Cycles | Displacement Tolerance | Force Tolerance |
|------------------|------------|------------------|------------------------|-----------------|
| 1 | Yes | 6 | 0.00000001 | 0.00000001 |
| 2 | Yes | 9 | 0.00000001 | 0.00008609 |
| 3 | Yes | 9 | 0.00000001 | 0.00007618 |
| 4 | Yes | 10 | 0.00000001 | 0.00008841 |
| 5 | Yes | 10 | 0.00000001 | 0.00007336 |
| 6 | Yes | 10 | 0.00000001 | 0.00009406 |
| 7 | Yes | 10 | 0.00000001 | 0.00007815 |
| 8 | Yes | 9 | 0.00000001 | 0.00007104 |
| 9 | Yes | 9 | 0.00000001 | 0.00006375 |
| 10 | Yes | 10 | 0.00000001 | 0.00010184 |
| 11 | Yes | 10 | 0.00000001 | 0.00008480 |
| 12 | Yes | 10 | 0.00000001 | 0.00008493 |
| 13 | Yes | 10 | 0.00000001 | 0.00007050 |
| 14 | Yes | 9 | 0.00000001 | 0.00008582 |
| 15 | Yes | 9 | 0.00000001 | 0.00007595 |
| 16 | Yes | 10 | 0.00000001 | 0.00009855 |
| 17 | Yes | 10 | 0.00000001 | 0.00008188 |
| 18 | Yes | 10 | 0.00000001 | 0.00009319 |
| 19 | Yes | 10 | 0.00000001 | 0.00007728 |
| 20 | Yes | 9 | 0.00000001 | 0.00007106 |

| | | | | |
|----|-----|----|------------|------------|
| 21 | Yes | 9 | 0.00000001 | 0.00006375 |
| 22 | Yes | 10 | 0.00000001 | 0.00008716 |
| 23 | Yes | 10 | 0.00000001 | 0.00007213 |
| 24 | Yes | 10 | 0.00000001 | 0.00010213 |
| 25 | Yes | 10 | 0.00000001 | 0.00008504 |
| 26 | Yes | 6 | 0.00000001 | 0.00000292 |
| 27 | Yes | 10 | 0.00000001 | 0.00004495 |
| 28 | Yes | 10 | 0.00000001 | 0.00004574 |
| 29 | Yes | 10 | 0.00000001 | 0.00004595 |
| 30 | Yes | 10 | 0.00000001 | 0.00004502 |
| 31 | Yes | 10 | 0.00000001 | 0.00004604 |
| 32 | Yes | 10 | 0.00000001 | 0.00004584 |
| 33 | Yes | 10 | 0.00000001 | 0.00004501 |
| 34 | Yes | 10 | 0.00000001 | 0.00004690 |
| 35 | Yes | 10 | 0.00000001 | 0.00004762 |
| 36 | Yes | 10 | 0.00000001 | 0.00004683 |
| 37 | Yes | 10 | 0.00000001 | 0.00004761 |
| 38 | Yes | 10 | 0.00000001 | 0.00004688 |
| 39 | Yes | 8 | 0.00000001 | 0.00007106 |
| 40 | Yes | 8 | 0.00000001 | 0.00006733 |
| 41 | Yes | 8 | 0.00000001 | 0.00006821 |
| 42 | Yes | 8 | 0.00000001 | 0.00007238 |
| 43 | Yes | 8 | 0.00000001 | 0.00006910 |
| 44 | Yes | 8 | 0.00000001 | 0.00006719 |
| 45 | Yes | 8 | 0.00000001 | 0.00007103 |
| 46 | Yes | 8 | 0.00000001 | 0.00006829 |
| 47 | Yes | 8 | 0.00000001 | 0.00006878 |
| 48 | Yes | 8 | 0.00000001 | 0.00007321 |
| 49 | Yes | 8 | 0.00000001 | 0.00006868 |
| 50 | Yes | 8 | 0.00000001 | 0.00006869 |

Maximum Tower Deflections - Service Wind

| Section No. | Elevation ft | Horz. Deflection in | Gov. Load Comb. | Tilt ° | Twist ° |
|-------------|---------------|---------------------|-----------------|--------|---------|
| L1 | 115.5 - 83.92 | 4.476 | 48 | 0.3168 | 0.0006 |
| L2 | 89.25 - 41.25 | 2.810 | 48 | 0.2807 | 0.0006 |
| L3 | 48 - 0 | 0.844 | 48 | 0.1573 | 0.0002 |

Critical Deflections and Radius of Curvature - Service Wind

| Elevation ft | Appurtenance | Gov. Load Comb. | Deflection in | Tilt ° | Twist ° | Radius of Curvature ft |
|--------------|--------------------------------|-----------------|---------------|--------|---------|------------------------|
| 117.00 | BXA-171063-8BF-2 w/ Mount Pipe | 48 | 4.476 | 0.3168 | 0.0006 | 148178 |
| 104.00 | DB411-A | 48 | 3.729 | 0.3040 | 0.0006 | 64425 |
| 97.00 | APXVAARR24_43-U-NA20 | 48 | 3.285 | 0.2944 | 0.0006 | 40048 |
| 87.00 | 7770.00 w/ Mount Pipe | 48 | 2.677 | 0.2760 | 0.0005 | 26600 |
| 75.00 | 742 213 | 48 | 2.007 | 0.2453 | 0.0005 | 20222 |

Maximum Tower Deflections - Design Wind

| Section No. | Elevation ft | Horz. Deflection in | Gov. Load Comb. | Tilt ° | Twist ° |
|-------------|---------------|---------------------|-----------------|--------|---------|
| L1 | 115.5 - 83.92 | 22.276 | 20 | 1.5761 | 0.0029 |
| L2 | 89.25 - 41.25 | 13.986 | 20 | 1.3965 | 0.0028 |
| L3 | 48 - 0 | 4.204 | 20 | 0.7831 | 0.0009 |

| Section No. | Elevation ft | Horz. Deflection in | Gov. Load Comb. | Tilt ° | Twist ° |
|-------------|-----------------|---------------------------|-----------------------|-----------|------------|
| | | | | | |

Critical Deflections and Radius of Curvature - Design Wind

| Elevation ft | Appurtenance | Gov. Load Comb. | Deflection in | Tilt ° | Twist ° | Radius of Curvature ft |
|-----------------|--------------------------------|-----------------------|------------------|-----------|------------|------------------------------|
| 117.00 | BXA-171063-8BF-2 w/ Mount Pipe | 20 | 22.276 | 1.5761 | 0.0029 | 29877 |
| 104.00 | DB411-A | 20 | 18.559 | 1.5124 | 0.0029 | 12990 |
| 97.00 | APXVAARR24_43-U-NA20 | 20 | 16.348 | 1.4645 | 0.0029 | 8074 |
| 87.00 | 7770.00 w/ Mount Pipe | 20 | 13.322 | 1.3729 | 0.0027 | 5361 |
| 75.00 | 742 213 | 20 | 9.991 | 1.2205 | 0.0023 | 4071 |

Compression Checks

Pole Design Data

| Section No. | Elevation ft | Size | L ft | L _u ft | Kl/r | A in ² | P _u K | ϕP _n K | Ratio P _u ϕP _n |
|-------------|----------------------|------------------------|---------|----------------------|------|----------------------|---------------------|----------------------|--|
| L1 | 115.5 - 83.92 (1) | TP40.829x32.25x0.25 | 31.58 | 0.00 | 0.0 | 31.500 5 | -10.83 | 1704.79 | 0.006 |
| L2 | 83.92 - 41.25 (2) | TP51.92x38.8811x0.3125 | 48.00 | 0.00 | 0.0 | 50.085 0 | -24.66 | 2674.31 | 0.009 |
| L3 | 41.25 - 0 (3) | TP62.5x49.4614x0.375 | 48.00 | 0.00 | 0.0 | 75.015 9 | -41.53 | 3879.40 | 0.011 |

Pole Bending Design Data

| Section No. | Elevation ft | Size | M _{ux} kip-ft | ϕM _{nx} kip-ft | Ratio M _{ux} ϕM _{nx} | M _{uy} kip-ft | ϕM _{ny} kip-ft | Ratio M _{uy} ϕM _{ny} |
|-------------|----------------------|------------------------|---------------------------|----------------------------|--|---------------------------|----------------------------|--|
| L1 | 115.5 - 83.92 (1) | TP40.829x32.25x0.25 | 253.81 | 1361.13 | 0.186 | 0.00 | 1361.13 | 0.000 |
| L2 | 83.92 - 41.25 (2) | TP51.92x38.8811x0.3125 | 1059.34 | 2716.25 | 0.390 | 0.00 | 2716.25 | 0.000 |
| L3 | 41.25 - 0 (3) | TP62.5x49.4614x0.375 | 2288.63 | 4919.18 | 0.465 | 0.00 | 4919.18 | 0.000 |

Pole Shear Design Data

| Section No. | Elevation ft | Size | Actual V _u K | ϕV _n K | Ratio V _u ϕV _n | Actual T _u kip-ft | ϕT _n kip-ft | Ratio T _u ϕT _n |
|-------------|----------------------|------------------------|-------------------------------|----------------------|--|------------------------------------|---------------------------|--|
| L1 | 115.5 - 83.92 (1) | TP40.829x32.25x0.25 | 12.50 | 552.83 | 0.023 | 0.13 | 1902.90 | 0.000 |
| L2 | 83.92 - 41.25 (2) | TP51.92x38.8811x0.3125 | 22.46 | 878.99 | 0.026 | 0.69 | 3848.45 | 0.000 |
| L3 | 41.25 - 0 (3) | TP62.5x49.4614x0.375 | 28.77 | 1316.53 | 0.022 | 0.69 | 7194.44 | 0.000 |

Pole Interaction Design Data


| Section No. | Elevation ft | Ratio P_u ϕP_n | Ratio M_{ux} ϕM_{nx} | Ratio M_{uy} ϕM_{ny} | Ratio V_u ϕV_n | Ratio T_u ϕT_n | Comb. Stress Ratio | Allow. Stress Ratio | Criteria |
|-------------|----------------------|---------------------------|---------------------------------|---------------------------------|---------------------------|---------------------------|--------------------|---------------------|----------|
| L1 | 115.5 - 83.92 | 0.006 | 0.186 | 0.000 | 0.023 | 0.000 | 0.193 | 1.050 | 4.8.2 |
| L2 | 83.92 - 41.25 (1) | 0.009 | 0.390 | 0.000 | 0.026 | 0.000 | 0.400 | 1.050 | 4.8.2 |
| L3 | 41.25 - 0 (3) (2) | 0.011 | 0.465 | 0.000 | 0.022 | 0.000 | 0.476 | 1.050 | 4.8.2 |

Section Capacity Table

| Section No. | Elevation ft | Component Type | Size | Critical Element | P K | ϕP_{allow} K | % Capacity | Pass Fail |
|-------------|---------------|----------------|------------------------|------------------|--------|--------------------|-------------|-------------|
| L1 | 115.5 - 83.92 | Pole | TP40.829x32.25x0.25 | 1 | -10.83 | 1790.03 | 18.4 | Pass |
| L2 | 83.92 - 41.25 | Pole | TP51.92x38.8811x0.3125 | 2 | -24.66 | 2808.03 | 38.1 | Pass |
| L3 | 41.25 - 0 | Pole | TP62.5x49.4614x0.375 | 3 | -41.53 | 4073.37 | 45.4 | Pass |
| | | | | | | Summary | | |
| | | | | | | Pole (L3) | 45.4 | Pass |
| | | | | | | RATING = | 45.4 | Pass |

APPENDIX B

BASE LEVEL DRAWING



APPENDIX C
ADDITIONAL CALCULATIONS

Monopole Base Plate Connection




| Site Info | |
|-----------|----------------|
| BU # | 806367 |
| Site Name | HRT 046 943209 |
| Order # | 479816 REV.1 |

| Analysis Considerations | |
|-------------------------|------|
| TIA-222 Revision | H |
| Grout Considered: | No |
| l_{ar} (in) | 1.75 |

| Applied Loads | |
|--------------------|---------|
| Moment (kip-ft) | 2288.63 |
| Axial Force (kips) | 41.53 |
| Shear Force (kips) | 28.77 |

*TIA-222-H Section 15.5 Applied



Connection Properties

Anchor Rod Data

(12) 2-1/4" ϕ bolts (A615-75 N; $F_y=75$ ksi, $F_u=100$ ksi) on 71" BC

Anchor Spacing: 6 in

Base Plate Data

71" W x 2.5" Plate (A572-60; $F_y=60$ ksi, $F_u=75$ ksi); Clip: 6 in

Stiffener Data

N/A

Pole Data

62.5" x 0.375" 12-sided pole (A572-65; $F_y=65$ ksi, $F_u=80$ ksi)

Analysis Results

Anchor Rod Summary

| (units of kips, kip-in) | | |
|-------------------------|-----------------------|---------------|
| $P_u_c = 132.34$ | $\phi P_n_c = 268.39$ | Stress Rating |
| $V_u = 2.4$ | $\phi V_n = 120.77$ | 47.0% |
| $M_u = n/a$ | $\phi M_n = n/a$ | Pass |

Base Plate Summary

| | | |
|-------------------------|-------|------------|
| Max Stress (ksi): | 26.66 | (Flexural) |
| Allowable Stress (ksi): | 54 | |
| Stress Rating: | 47.0% | Pass |

Pier and Pad Foundation



| | |
|--------------|----------------|
| BU # : | 806367 |
| Site Name: | HRT 046 943209 |
| App. Number: | 479816, Rev1 |

| | |
|-------------------|----------|
| TIA-222 Revision: | H |
| Tower Type: | Monopole |

| | |
|----------------------------------|-------------------------------------|
| Top & Bot. Pad Rein. Different?: | <input type="checkbox"/> |
| Block Foundation?: | <input checked="" type="checkbox"/> |
| Rectangular Pad?: | <input type="checkbox"/> |

| Superstructure Analysis Reactions | | |
|---|-------|---------|
| Compression, P_{comp} : | 42 | kips |
| Base Shear, V_{u_comp} : | 29 | kips |
| | | |
| Moment, M_u : | 2289 | ft-kips |
| Tower Height, H : | 115.5 | ft |
| | | |
| BP Dist. Above Fdn, bp_{dist} : | 6 | in |
| Bolt Circle / Bearing Plate Width, BC : | 71 | in |

| Foundation Analysis Checks | | | | |
|--------------------------------|----------|---------|---------|-------|
| | Capacity | Demand | Rating* | Check |
| Lateral (Sliding) (kips) | 115.73 | 29.00 | 23.9% | Pass |
| Bearing Pressure (ksf) | 9.00 | 1.51 | 16.8% | Pass |
| Overturning (kip*ft) | 4310.34 | 2419.50 | 56.1% | Pass |
| | | | | |
| | | | | |
| Pad Flexure (kip*ft) | 3946.25 | 933.59 | 22.5% | Pass |
| Pad Shear - 1-way (kips) | 1072.17 | 124.40 | 11.0% | Pass |
| Pad Shear - 2-way (Comp) (ksi) | 0.164 | 0.002 | 1.3% | Pass |
| Flexural 2-way (Comp) (kip*ft) | 3730.81 | 0.00 | 0.0% | Pass |

*Rating per TIA-222-H Section 15.5

| | |
|---------------------|--------------|
| Soil Rating*: | 56.1% |
| Structural Rating*: | 22.5% |

| Pad Properties | | |
|--|-----|----|
| Depth, D : | 3.5 | ft |
| Pad Width, W_1 : | 25 | ft |
| Pad Thickness, T : | 4 | ft |
| Pad Rebar Size (Bottom dir. 2), Sp_2 : | 8 | |
| Pad Rebar Quantity (Bottom dir. 2), mp_2 : | 26 | |
| Pad Clear Cover, cc_{pad} : | 3 | in |

| Material Properties | | |
|--|-----|-----|
| Rebar Grade, F_y : | 60 | ksi |
| Concrete Compressive Strength, F_c : | 3 | ksi |
| Dry Concrete Density, δ_c : | 150 | pcf |

| Soil Properties | | |
|-------------------------------------|--------|---------|
| Total Soil Unit Weight, γ : | 120 | pcf |
| Ultimate Gross Bearing, Q_{ult} : | 12.000 | ksf |
| Cohesion, C_u : | | ksf |
| Friction Angle, φ : | 36 | degrees |
| SPT Blow Count, N_{blows} : | 33 | |
| Base Friction, μ : | 0.4 | |
| Neglected Depth, N : | 3.33 | ft |
| Foundation Bearing on Rock?: | No | |
| Groundwater Depth, gw : | 8 | ft |


--Toggle between Gross and Net

ASCE 7 Hazards Report

Address:
No Address at This Location

Standard: ASCE/SEI 7-10
Risk Category: II
Soil Class: D - Stiff Soil

Elevation: 514.59 ft (NAVD 88)
Latitude: 41.484594
Longitude: -72.572447





Seismic

Site Soil Class: D - Stiff Soil

Results:

| | | | |
|------------|-------|--------------------|-------|
| S_s : | 0.177 | S_{DS} : | 0.189 |
| S_1 : | 0.062 | S_{D1} : | 0.099 |
| F_a : | 1.6 | T_L : | 6 |
| F_v : | 2.4 | PGA : | 0.09 |
| S_{MS} : | 0.283 | PGA _M : | 0.144 |
| S_{M1} : | 0.148 | F_{PGA} : | 1.6 |
| | | I_e : | 1 |

Seismic Design Category B



Data Accessed:

Wed Nov 18 2020

Date Source:

USGS Seismic Design Maps based on ASCE/SEI 7-10, incorporating Supplement 1 and errata of March 31, 2013, and ASCE/SEI 7-10 Table 1.5-2. Additional data for site-specific ground motion procedures in accordance with ASCE/SEI 7-10 Ch. 21 are available from USGS.

Results:

Ice Thickness: 0.75 in.

Concurrent Temperature: 15 F

Gust Speed: 50 mph

Data Source: Standard ASCE/SEI 7-10, Figs. 10-2 through 10-8

Date Accessed: Wed Nov 18 2020

Ice thicknesses on structures in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.

Values provided are equivalent radial ice thicknesses due to freezing rain with concurrent 3-second gust speeds, for a 50-year mean recurrence interval, and temperatures concurrent with ice thicknesses due to freezing rain. Thicknesses for ice accretions caused by other sources shall be obtained from local meteorological studies. Ice thicknesses in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.

The ASCE 7 Hazard Tool is provided for your convenience, for informational purposes only, and is provided "as is" and without warranties of any kind. The location data included herein has been obtained from information developed, produced, and maintained by third party providers; or has been extrapolated from maps incorporated in the ASCE 7 standard. While ASCE has made every effort to use data obtained from reliable sources or methodologies, ASCE does not make any representations or warranties as to the accuracy, completeness, reliability, currency, or quality of any data provided herein. Any third-party links provided by this Tool should not be construed as an endorsement, affiliation, relationship, or sponsorship of such third-party content by or from ASCE.

ASCE does not intend, nor should anyone interpret, the results provided by this Tool to replace the sound judgment of a competent professional, having knowledge and experience in the appropriate field(s) of practice, nor to substitute for the standard of care required of such professionals in interpreting and applying the contents of this Tool or the ASCE 7 standard.

In using this Tool, you expressly assume all risks associated with your use. Under no circumstances shall ASCE or its officers, directors, employees, members, affiliates, or agents be liable to you or any other person for any direct, indirect, special, incidental, or consequential damages arising from or related to your use of, or reliance on, the Tool or any information obtained therein. To the fullest extent permitted by law, you agree to release and hold harmless ASCE from any and all liability of any nature arising out of or resulting from any use of data provided by the ASCE 7 Hazard Tool.

Date: November 17, 2020

Darcy Tarr
Crown Castle
6325 Ardrey Kell Road
Charlotte, NC 28277

Paul J Ford and Company
250 E. Broad Street, Suite 600
Columbus, OH 43215
614.221.6679

| | | |
|--------------------------------------|---|------------------------|
| Subject: | Mount Replacement Report | |
| Carrier Designation: | T-Mobile Equipment Change-out | |
| | Carrier Site Number: | CT11233A |
| | Carrier Site Name: | Higginum_1 |
| Crown Castle Designation: | Crown Castle BU Number: | 806367 |
| | Crown Castle Site Name: | HRT 046 943209 |
| | Crown Castle JDE Job Number: | 559174 |
| | Crown Castle Order Number: | 479816 Rev. 1 |
| Engineering Firm Designation: | Paul J Ford and Company Project Number: | A37520-2305.001.7190 |
| Site Data: | Maple Ave West, Haddam, Middlesex County, CT 06441 Latitude 41.484594°, Longitude -72.572447° | |
| Structure Information: | Tower Height & Type: | 115.5 Foot Monopole |
| | Mount Elevation: | 97 Foot |
| | Mount Type: | (1) 12.5 Foot Platform |

Dear Darcy Tarr,

Paul J Ford and Company is pleased to submit this "Mount Replacement Report" to determine the structural integrity of the T-Mobile antenna mounting system with the proposed appurtenance and equipment addition on the abovementioned supporting tower structure. Analysis of the existing supporting tower structure is to be completed by others and therefore is not part of this analysis. Analysis of the antenna mounting system as a tie-off point is not part of this document.

The purpose of the analysis is to determine acceptability of the mount stress level. Based on our analysis we have determined the mount stress level to be:

12.5' Platform

SUFFICIENT*

*The mount has sufficient capacity once the modifications, as described in Section 4.1 Recommendations of this report, are completed.


The analysis utilizes an ultimate 3-second gust wind speed of 130 mph as required by the 2018 Connecticut State Building Code and Appendix N. Applicable Standard references and design criteria are listed in Section 2 - Analysis Criteria.

Respectfully submitted by:



Ibrahim O. Huthman, E.I.
Structural Designer
IHuthman@pauljford.com

D.S.



11/17/2020

TABLE OF CONTENTS

1) INTRODUCTION

2) ANALYSIS CRITERIA

Table 1 - Proposed Equipment Configuration

3) ANALYSIS PROCEDURE

Table 2 - Documents Provided

3.1) Analysis Method

3.2) Assumptions

4) ANALYSIS RESULTS

Table 3 - Mount Component Capacity

4.1) Recommendations

5) APPENDIX A

SOFTWARE INPUT CALCULATIONS

6) APPENDIX B

SOFTWARE ANALYSIS OUTPUT

7) APPENDIX C

ADDITIONAL CALCULATIONS

8) APPENDIX D

MANUFACTURER DRAWINGS (FOR REFERENCE ONLY)

1) INTRODUCTION

The proposed mount under consideration is a (1) 12.5' Platform mount, designed by SitePro1.

2) ANALYSIS CRITERIA

| | |
|--|-----------|
| TIA-222 Revision: | TIA-222-H |
| Risk Category: | II |
| Ultimate Wind Speed: | 130 mph |
| Exposure Category: | B |
| Topographic Factor at Base: | 1.00 |
| Topographic Factor at Mount: | 1.00 |
| Ice Thickness: | 1.5 in |
| Wind Speed with Ice: | 50 mph |
| Seismic S_s: | 0.177 |
| Seismic S_1: | 0.062 |
| Maintenance Loading Wind Speed: | 30 mph |
| Maintenance Load at Mid/End-Points, L_v: | 250 lb |
| Maintenance Load at Mount Pipes, L_m: | 500 lb |

Table 1 - Proposed Equipment Configuration

| Mount Centerline (ft) | Antenna Centerline (ft) | Number of Antennas | Antenna Manufacturer | Antenna Model | Mount / Modification Details |
|-----------------------|-------------------------|--------------------|----------------------|----------------------|------------------------------|
| 97 | 98 | 3 | RFS CELWAVE | APXVAARR24_43-U-NA20 | (1) PLATFORM (12.5') |
| | | 3 | EMS WIRELESS | RR90-17-02DP | |
| | | 3 | ERICSSON | KRY 112 144/1 | |
| | | 3 | ERICSSON | KRY 112 489/2 | |
| | | 3 | ERICSSON | RADIO 4449 B12/B71 | |

3) ANALYSIS PROCEDURE

Table 2 - Documents Provided

| Document | Remarks | Reference | Source |
|-----------------------------|---|-----------|--------------|
| Mount Manufacturer Drawings | Model #:RMQP-SPT Dated: 06/28/2018 | - | SitePro1 |
| Order | ID: 479816 Rev. 1 Dated: 04/17/2019 | - | CCISites |
| Radio Frequency Data Sheet | RFDS ID #: CT11233A Version 2.1, Dated: 03/29/2019 | - | Crown Castle |

3.1) Analysis Method

RISA-3D (version 17.0.3), a commercially available analysis software package, was used to create a three-dimensional model of the tower and calculate member stresses for various loading cases.

A tool internally developed, using Microsoft Excel, by Paul J. Ford and Company was used to calculate wind loading on all appurtenances, dishes, and mount members for various load cases. Selected output from the analysis is included in Appendix B.

This analysis was performed in accordance with Crown Castle's ENG-SOW-10208 *Tower Mount Analysis* (Revision C).

3.2) Assumptions

- 1) The analysis of the existing tower or the effect of the mount attachment to the tower is not within the current scope of work.
- 2) The antenna mounting system was properly fabricated, installed and maintained in good condition, twist free and plumb in accordance with its original design and manufacturer's specifications and all bolts are tightened as specified by the manufacturer and AISC requirements.
- 3) The configuration of antennas, mounts, and other appurtenances are as specified in Table 1.
- 4) All member connections have been designed to meet or exceed the load carrying capacity of the connected member unless otherwise specified in this report. All U-Bolt connections have been properly tightened. This analysis will be required to be revised if the existing conditions in the field differ from those shown in the above referenced documents or assumed in this analysis. No allowance was made for any damaged, missing, or rusted members.
- 5) Steel grades are as follows, unless noted otherwise:
 - a) Channel, Solid Round, Angle, Unistrut ASTM A53 (GR 35)
 - b) Pipe ASTM A53 (GR 35)
 - c) HSS (Rectangular), Plate Q235 Gr B (Fy = 34 ksi, Fu = 58 ksi)
 - d) HSS (Round) ASTM A53 (GR 35)
 - e) Connection Bolts ASTM A325
 - f) Threaded Rods SAE J429 (GR2)
 - g) U-Bolts SAE J429 (GR2)
- 6) Proposed equipment is to be installed in the locations specified in Appendix A. Any changes to the proposed equipment locations will render this report invalid.

This analysis may be affected if any assumptions are not valid or have been made in error. Paul J Ford and Company should be notified to determine the effect on the structural integrity of the mount.

4) ANALYSIS RESULTS

Table 3- Mount Component Capacity

| Notes | Component | Critical Member | Elevation (ft) | % Capacity | Pass / Fail |
|-------|---------------------------|-----------------|----------------|------------|-------------|
| 1,2 | Face Horizontals | CBB1 | 97 | 19.0 | Pass |
| 1,2 | Bracing Members | M17 | | 23.8 | Pass |
| 1,2 | Support Rails | CBB2 | | 57.1 | Pass |
| 1,2 | Grating Support Members | M5 | | 13.3 | Pass |
| 1,2 | Standoff Members | M38 | | 55.2 | Pass |
| 1,2 | Corner Plates | M12 | | 14.3 | Pass |
| 1,2 | Mount Pipes | C1 | | 56.2 | Pass |
| 1,2 | Mount to Tower Connection | - | | 32.4 | Pass |

| | |
|---|--------------|
| Mount Rating (max from all components) = | 57.1% |
|---|--------------|

Notes:

- 1) See additional documentation in "Appendix B – Software Analysis Output" and "Appendix C – Additional Calculations" for calculations supporting the % capacity consumed.
- 2) Rating per TIA-222-H, Section 15.5

4.1) Recommendations

The proposed mount has sufficient capacity to support the proposed loading configuration. In order for the results of this analysis to be considered valid, the mount listed below shall be installed.



- Mount Replacement, SitePro1 and RMQP-SPT

Beyond the mount replacement, no structural modifications are required at this time, provided that the above-listed changes are implemented.

APPENDIX A

SOFTWARE INPUT CALCULATION

Sector A



| Ref ID | Type | Manufacturer | Model | Height (in) | Width (in) | Depth (in) | Center Line (ft) | Mount Pipe | Tangential Offset (in) | Normal Offset (in) |
|--------|---------|--------------|----------------------|-------------|------------|------------|------------------|------------|------------------------|--------------------|
| #1 | Antenna | RFS CELWAVE | APXVAARR24_43-U-NA20 | 95.90 | 24.00 | 8.70 | 98.00 | A1 | 0.00 | 3.00 |
| #2 | Antenna | EMS WIRELESS | RR90-17-02DP | 56.00 | 8.00 | 2.75 | 98.00 | A4 | 0.00 | 3.00 |
| #3 | TME/RRH | ERICSSON | KRY 112 144/1 | 7.00 | 6.00 | 3.00 | 100.00 | A1 | 0.00 | -3.00 |
| #4 | TME/RRH | ERICSSON | KRY 112 489/2 | 11.00 | 6.10 | 3.94 | 98.00 | A1 | 0.00 | -3.00 |
| #5 | TME/RRH | ERICSSON | RADIO 4449 B12/B71 | 14.95 | 13.19 | 9.25 | 96.00 | A1 | 0.00 | -3.00 |


1. A 6" tolerance for proposed equipment is acceptable.

2. Contractor to verify location of existing equipment prior to installation of proposed equipment. Notify for any deviations.


3. Install shall not cause harm to the structure, climbing facility, safety climb, or any system installed on the structure

Sector B

Profile View



Plan View



| Ref ID | Type | Manufacturer | Model | Height (in) | Width (in) | Depth (in) | Center Line (ft) | Mount Pipe | Tangential Offset (in) | Normal Offset (in) |
|--------|---------|--------------|----------------------|-------------|------------|------------|------------------|------------|------------------------|--------------------|
| #1 | Antenna | RFS CELWAVE | APXVAARR24_43-U-NA20 | 95.90 | 24.00 | 8.70 | 98.00 | B1 | 0.00 | 3.00 |
| #2 | Antenna | EMS WIRELESS | RR90-17-02DP | 56.00 | 8.00 | 2.75 | 98.00 | B4 | 0.00 | 3.00 |
| #3 | TME/RRH | ERICSSON | KRY 112 144/1 | 7.00 | 6.00 | 3.00 | 100.00 | B1 | 0.00 | -3.00 |
| #4 | TME/RRH | ERICSSON | KRY 112 489/2 | 11.00 | 6.10 | 3.94 | 98.00 | B1 | 0.00 | -3.00 |
| #5 | TME/RRH | ERICSSON | RADIO 4449 B12/B71 | 14.95 | 13.19 | 9.25 | 96.00 | B1 | 0.00 | -3.00 |


1. A 6" tolerance for proposed equipment is acceptable.

2. Contractor to verify location of existing equipment prior to installation of proposed equipment. Notify for any deviations.


3. Install shall not cause harm to the structure, climbing facility, safety climb, or any system installed on the structure

Sector C

Profile View



Plan View




| Ref ID | Type | Manufacturer | Model | Height (in) | Width (in) | Depth (in) | Center Line (ft) | Mount Pipe | Tangential Offset (in) | Normal Offset (in) |
|--------|---------|--------------|----------------------|-------------|------------|------------|------------------|------------|------------------------|--------------------|
| #1 | Antenna | RFS CELWAVE | APXVAARR24_43-U-NA20 | 95.90 | 24.00 | 8.70 | 98.00 | C1 | 0.00 | 3.00 |
| #2 | Antenna | EMS WIRELESS | RR90-17-02DP | 56.00 | 8.00 | 2.75 | 98.00 | C4 | 0.00 | 3.00 |
| #3 | TME/RRH | ERICSSON | KRY 112 144/1 | 7.00 | 6.00 | 3.00 | 100.00 | C1 | 0.00 | -3.00 |
| #4 | TME/RRH | ERICSSON | KRY 112 489/2 | 11.00 | 6.10 | 3.94 | 98.00 | C1 | 0.00 | -3.00 |
| #5 | TME/RRH | ERICSSON | RADIO 4449 B12/B71 | 14.95 | 13.19 | 9.25 | 96.00 | C1 | 0.00 | -3.00 |

1. A 6" tolerance for proposed equipment is acceptable.

2. Contractor to verify location of existing equipment prior to installation of proposed equipment. Notify for any deviations.

3. Install shall not cause harm to the structure, climbing facility, safety climb, or any system installed on the structure



(c) Copyright 2020 by Paul J. Ford and Company, all rights reserved.

Project Number: 37520-2305.001.7190
 Date: 11/17/2020
 Engineer: IOH

Mount Loading per TIA-222-H (Version v3.3 - Effective 10/22/2020)



| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--|--|--|--|---------------------------------|--|--|--|--|---|--|--|--|--|--|--|--|--|--|--|--|--|--|--|---|--|--|--|--|----------------------|--|--|--|--|--|--|--|--|--|
| Structure & Wind Speed | | | | | | | | | | Topography | | | | | | | | | | Velocity Pressure Coefficients | | | | | | | | | | Ice Loading | | | | | | | | | |
| Structure Type = Mount | | | | | Ultimate Wind Speed = 130 mph | | | | | Risk Category = II | | | | | z _g = 1200 ft (Table 2-4) | | | | | h = 1.00 in (Bar Grating Height) | | | | | | | | | | | | | | | | | | | |
| Mount Type = 3 Sectors | | | | | Ice Wind Speed = 50 mph | | | | | Exposure Category = B | | | | | α' = 7.00 (Table 2-4) | | | | | l _i = 1.00 (Table 2-3) | | | | | | | | | | | | | | | | | | | |
| Mount Centerline (z) = 97.00 ft | | | | | Maintenance Wind Speed = 30 mph | | | | | Topographic Category = 1 | | | | | K _z = 0.98 (Section 2.6.5.2) | | | | | K _{es} = 1.0 (Annex S - Ice) | | | | | | | | | | | | | | | | | | | |
| Risa 3D Y-Coordinate = 30.00 in | | | | | Non-Op Wind Speed = - mph | | | | | Structure Base Height (Z _s) = 514.59 ft | | | | | K _{zmin} = 0.70 | | | | | q _a = 5.96 psf (Section 2.6.11.6) | | | | | | | | | | | | | | | | | | | |
| | | | | | Op Wind Speed = - mph | | | | | Crest Height (H) = | | | | | K _{zcalc} = 0.98 | | | | | K _{iz} = 1.11 (Section 2.6.10) | | | | | | | | | | | | | | | | | | | |
| | | | | | Ice Thickness = 1.5 in | | | | | | | | | | K _{zmax} = 2.01 | | | | | t _{iz} = 1.67 in (Section 2.6.10) | | | | | | | | | | | | | | | | | | | |
| Analysis Settings | | | | | | | | | | Maintenance Point Loads | | | | | | | | | | Override | | | | | | | | | | Wind Pressure | | | | | | | | | |
| Analysis Scope = Client | | | | | File Suffix = .Client.r3d | | | | | L _{m1} = 500 lbs N110 110 | | | | | L _{v1} = 250 lbs N14 14 | | | | | K _{zt} = 1.00 (Section 2.6.6.2.1) | | | | | K _a = 0.9 (on all Appurt. / Member Forces) | | | | | | | | | | | | | | |
| Analysis Wind Direction Increment = 30° | | | | | EPA Calculation Method = TIA | | | | | L _{m2} = 500 lbs N104 104 | | | | | L _{v2} = 250 lbs N173 167 | | | | | K _d = 0.95 (Section 16.6) | | | | | q _z (G _h) (K _{es}) = 39.52 psf (Ice) | | | | | | | | | | | | | | |
| Construction Duration = | | | | | | | | | | L _{m3} = 500 lbs N98 98 | | | | | L _{v3} = 250 lbs N13 13 | | | | | K _e = 0.98 (Section 2.6.8) | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | L _{m4} = 500 lbs N152 152 | | | | | L _{v4} = 250 lbs N2 2 | | | | | G _h = 1.00 (Section 16.6) | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | K _{es} = 1.0 (Annex S - Wind Force) | | | | | q _z (G _h) (K _{es}) = 39.52 psf (Section 2.6.11.6) | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Risa3D Source: G:\TOWER\375_Crown_Castle\2020\37520-2305_806367_HRT 046 943209\37520-2305.001.7190_MA\RISA\37520-2305.001.7190.r3d | | | | | | | | | | | | | | | | | | | | (57 Total Populated Members) | | | | | | | | | | | | | | | | | | | |

Antennas

| Item | Include Loading | Status | Mounting Location | Manufacturer | Antenna | Height (in) | Width (in) | Depth (in) | Flat or Round | Weight (lbs) | Sector / Face | Position | Quantity | Orientation | Use tnxTower C _a A _s (CFD) | Top/Bottom Mounting Point Spacing | Override Spacing (in) | Max Antenna C/L (ft) | Min Antenna C/L (ft) | Antenna C/L (ft) | Antenna Top Mount Location from Mount Pipe Bottom (in) | Antenna Bottom Mount Location from Mount Pipe Bottom (in) | Override Top Antenna Mounting Location (in) | Override Bottom Antenna Mounting Location (in) | Normal Wind Force per Antenna (lbs) | Transverse Wind Force per Antenna (lbs) |
|------|-----------------|----------|-------------------|--------------|----------------------|-------------|------------|------------|---------------|--------------|---------------|----------|----------|-------------|--|-----------------------------------|-----------------------|----------------------|----------------------|------------------|--|---|---|--|-------------------------------------|---|
| 1 | Yes | Proposed | Mount | RFS CELWAVE | APXVAARR24_43-U-NA20 | 95.9 | 24 | 8.7 | Flat | 128 | A | 1 | 1 | Normal | Yes | 89.90 | 78 | 98.083 | 96.583 | 98 | 95.00 | 17.00 | | | 521.809 | 189.231 |
| 2 | Yes | Existing | Mount | EMS WIRELESS | RR90-17-02DP | 56 | 8 | 2.75 | Flat | 13.5 | A | 4 | 1 | Normal | Yes | 50.00 | | 99.250 | 95.417 | 98 | 81.00 | 31.00 | | | 160.776 | 54.778 |
| 3 | Yes | Existing | Mount | ERICSSON | KRY 112 144/1 | 7 | 6 | 3 | Flat | 11 | A | 1 | 1 | Normal | No | 1.00 | | 101.292 | 93.375 | 100 | 80.50 | 79.50 | | | 12.449 | 6.225 |
| 4 | Yes | Proposed | Mount | ERICSSON | KRY 112 489/2 | 11 | 6.1 | 3.94 | Flat | 15.4 | A | 1 | 1 | Normal | No | 5.00 | | 101.125 | 93.542 | 98 | 58.50 | 53.50 | | | 19.889 | 12.986 |
| 5 | Yes | Proposed | Mount | ERICSSON | RADIO 4449 B12/B71 | 14.95 | 13.19 | 9.25 | Flat | 75 | A | 1 | 1 | Normal | No | 8.95 | | 100.960 | 93.706 | 96 | 36.48 | 27.53 | | | 58.450 | 40.991 |
| 6 | Yes | Proposed | Mount | RFS CELWAVE | APXVAARR24_43-U-NA20 | 95.9 | 24 | 8.7 | Flat | 128 | B | 1 | 1 | Normal | Yes | 89.90 | 78 | 98.083 | 96.583 | 98 | 95.00 | 17.00 | | | 521.809 | 189.231 |
| 7 | Yes | Existing | Mount | EMS WIRELESS | RR90-17-02DP | 56 | 8 | 2.75 | Flat | 13.5 | B | 4 | 1 | Normal | Yes | 50.00 | | 99.250 | 95.417 | 98 | 81.00 | 31.00 | | | 160.776 | 54.778 |
| 8 | Yes | Existing | Mount | ERICSSON | KRY 112 144/1 | 7 | 6 | 3 | Flat | 11 | B | 1 | 1 | Normal | No | 1.00 | | 101.292 | 93.375 | 100 | 80.50 | 79.50 | | | 12.449 | 6.225 |
| 9 | Yes | Proposed | Mount | ERICSSON | KRY 112 489/2 | 11 | 6.1 | 3.94 | Flat | 15.4 | B | 1 | 1 | Normal | No | 5.00 | | 101.125 | 93.542 | 98 | 58.50 | 53.50 | | | 19.889 | 12.986 |
| 10 | Yes | Proposed | Mount | ERICSSON | RADIO 4449 B12/B71 | 14.95 | 13.19 | 9.25 | Flat | 75 | B | 1 | 1 | Normal | No | 8.95 | | 100.960 | 93.706 | 96 | 36.48 | 27.53 | | | 58.450 | 40.991 |
| 11 | Yes | Proposed | Mount | RFS CELWAVE | APXVAARR24_43-U-NA20 | 95.9 | 24 | 8.7 | Flat | 128 | C | 1 | 1 | Normal | Yes | 89.90 | 78 | 98.083 | 96.583 | 98 | 95.00 | 17.00 | | | 521.809 | 189.231 |
| 12 | Yes | Existing | Mount | EMS WIRELESS | RR90-17-02DP | 56 | 8 | 2.75 | Flat | 13.5 | C | 4 | 1 | Normal | Yes | 50.00 | | 99.250 | 95.417 | 98 | 81.00 | 31.00 | | | 160.776 | 54.778 |
| 13 | Yes | Existing | Mount | ERICSSON | KRY 112 144/1 | 7 | 6 | 3 | Flat | 11 | C | 1 | 1 | Normal | No | 1.00 | | 101.292 | 93.375 | 100 | 80.50 | 79.50 | | | 12.449 | 6.225 |
| 14 | Yes | Proposed | Mount | ERICSSON | KRY 112 489/2 | 11 | 6.1 | 3.94 | Flat | 15.4 | C | 1 | 1 | Normal | No | 5.00 | | 101.125 | 93.542 | 98 | 58.50 | 53.50 | | | 19.889 | 12.986 |
| 15 | Yes | Proposed | Mount | ERICSSON | RADIO 4449 B12/B71 | 14.95 | 13.19 | 9.25 | Flat | 75 | C | 1 | 1 | Normal | No | 8.95 | | 100.960 | 93.706 | 96 | 36.48 | 27.53 | | | 58.450 | 40.991 |

Dishes

| Item | Include Loading | Status | Mounting Location | Manufacturer | Microwave Dish | Dia (in) | Dish Type | Weight (lbs) | Sector / Face | Position | Top/Bottom Mounting Point Spacing | Override Spacing (in) | Max Dish C/L (ft) | Min Dish C/L (ft) | Dish C/L (ft) | Dish Top Mount Location from Mount Pipe Bottom | Dish Bottom Mount Location from Mount Pipe Bottom | Override Top Dish Mounting Location (in) | Override Bottom Dish Mounting Location (in) |
|------|-----------------|--------|-------------------|--------------|----------------|----------|-----------|--------------|---------------|----------|-----------------------------------|-----------------------|-------------------|-------------------|---------------|--|---|--|---|
|------|-----------------|--------|-------------------|--------------|----------------|----------|-----------|--------------|---------------|----------|-----------------------------------|-----------------------|-------------------|-------------------|---------------|--|---|--|---|



Envelope Only Solution

Paul J. Ford and Company

IOH



37520-2305.001.7190

SK - 1

Nov 17, 2020 at 2:04 PM

37520-2305.001.7190_Client.r3d

879532 / HRT 046 943209



Envelope Only Solution

Paul J. Ford and Company
IOH
37520-2305.001.7190

879532 / HRT 046 943209

SK - 2
Nov 17, 2020 at 2:06 PM
37520-2305.001.7190_Client.r3d



ASCE 7 Hazards Report

Address:

No Address at This Location

Standard:

ASCE/SEI 7-10

Elevation: 514.59 ft (NAVD 88)

Risk Category:



II

Latitude: 41.484594

Soil Class:

D - Stiff Soil

Longitude: -72.572447



Wind

Results:

| | |
|--------------|----------|
| Wind Speed: | 127 Vmph |
| 10-year MRI | 78 Vmph |
| 25-year MRI | 88 Vmph |
| 50-year MRI | 95 Vmph |
| 100-year MRI | 104 Vmph |

130 Vmph REQUIRED BY JURISDICTION

Data Source:

ASCE/SEI 7-10, Fig. 26.5-1A and Figs. CC-1–CC-4, incorporating errata of March 12, 2014


Date Accessed:

Fri May 03 2019

Value provided is 3-second gust wind speeds at 33 ft above ground for Exposure C Category, based on linear interpolation between contours. Wind speeds are interpolated in accordance with the 7-10 Standard. Wind speeds correspond to approximately a 7% probability of exceedance in 50 years (annual exceedance probability = 0.00143, MRI = 700 years).

Site is in a hurricane-prone region as defined in ASCE/SEI 7-10 Section 26.2. Glazed openings need not be protected against wind-borne debris.

Mountainous terrain, gorges, ocean promontories, and special wind regions should be examined for unusual wind conditions.





Seismic

Site Soil Class: D - Stiff Soil

Results:


| | | | |
|------------|-------|--------------------|-------|
| S_s : | 0.177 | S_{DS} : | 0.189 |
| S_1 : | 0.062 | S_{D1} : | 0.099 |
| F_a : | 1.6 | T_L : | 6 |
| F_v : | 2.4 | PGA : | 0.09 |
| S_{MS} : | 0.283 | PGA _M : | 0.144 |
| S_{M1} : | 0.148 | F_{PGA} : | 1.6 |
| | | I_e : | 1 |

Seismic Design Category B



Data Accessed: Fri May 03 2019

Date Source: USGS Seismic Design Maps based on ASCE/SEI 7-10, incorporating Supplement 1 and errata of March 31, 2013, and ASCE/SEI 7-10 Table 1.5-2. Additional data for site-specific ground motion procedures in accordance with ASCE/SEI 7-10 Ch. 21 are available from USGS.



Ice

Results:

Ice Thickness: 0.75 in.

Concurrent Temperature: 15 F

Gust Speed: 50 mph

Data Source: Standard ASCE/SEI 7-10, Figs. 10-2 through 10-8

Date Accessed: Fri May 03 2019

Ice thicknesses on structures in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.

Values provided are equivalent radial ice thicknesses due to freezing rain with concurrent 3-second gust speeds, for a 50-year mean recurrence interval, and temperatures concurrent with ice thicknesses due to freezing rain. Thicknesses for ice accretions caused by other sources shall be obtained from local meteorological studies. Ice thicknesses in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.


The ASCE 7 Hazard Tool is provided for your convenience, for informational purposes only, and is provided "as is" and without warranties of any kind. The location data included herein has been obtained from information developed, produced, and maintained by third party providers; or has been extrapolated from maps incorporated in the ASCE 7 standard. While ASCE has made every effort to use data obtained from reliable sources or methodologies, ASCE does not make any representations or warranties as to the accuracy, completeness, reliability, currency, or quality of any data provided herein. Any third-party links provided by this Tool should not be construed as an endorsement, affiliation, relationship, or sponsorship of such third-party content by or from ASCE.

ASCE does not intend, nor should anyone interpret, the results provided by this Tool to replace the sound judgment of a competent professional, having knowledge and experience in the appropriate field(s) of practice, nor to substitute for the standard of care required of such professionals in interpreting and applying the contents of this Tool or the ASCE 7 standard.


In using this Tool, you expressly assume all risks associated with your use. Under no circumstances shall ASCE or its officers, directors, employees, members, affiliates, or agents be liable to you or any other person for any direct, indirect, special, incidental, or consequential damages arising from or related to your use of, or reliance on, the Tool or any information obtained therein. To the fullest extent permitted by law, you agree to release and hold harmless ASCE from any and all liability of any nature arising out of or resulting from any use of data provided by the ASCE 7 Hazard Tool.

APPENDIX B

SOFTWARE ANALYSIS OUTPUT



| Code Check (Env) | |
|-----------------------|--|
| No Calc | |
| > 1.0 | |
| .90-1.0 | |
| .75-.90 | |
| .50-.75 | |
| 0.-.50 | |



Member Code Checks Displayed (Enveloped)
Envelope Only Solution

Paul J. Ford and Company

IOH




37520-2305.001.7190

SK - 3

Nov 17, 2020 at 2:06 PM

37520-2305.001.7190_Client.r3d

879532 / HRT 046 943209



Member Shear Checks Displayed (Enveloped) Envelope Only Solution

Paul J. Ford and Company

SK - 4

101

Nov 17, 2020 at 2:06 PM

37520 2305 001 7100

(Global) Model Settings

| | |
|---|--------------------|
| Display Sections for Member Calcs | 5 |
| Max Internal Sections for Member Calcs | 97 |
| Include Shear Deformation? | Yes |
| Increase Nailing Capacity for Wind? | Yes |
| Include Warping? | Yes |
| Trans Load Btwn Intersecting Wood Wall? | Yes |
| Area Load Mesh (in ²) | 144 |
| Merge Tolerance (in) | .12 |
| P-Delta Analysis Tolerance | 0.50% |
| Include P-Delta for Walls? | Yes |
| Automatically Iterate Stiffness for Walls? | Yes |
| Max Iterations for Wall Stiffness | 3 |
| Gravity Acceleration (in/sec ²) | 386.4 |
| Wall Mesh Size (in) | 24 |
| Eigensolution Convergence Tol. (1.E-) | 4 |
| Vertical Axis | Y |
| Global Member Orientation Plane | XZ |
| Static Solver | Sparse Accelerated |
| Dynamic Solver | Accelerated Solver |

| | |
|------------------------|-------------------------|
| Hot Rolled Steel Code | AISC 15th(360-16): LRFD |
| Adjust Stiffness? | Yes(Iterative) |
| RISAConnection Code | None |
| Cold Formed Steel Code | None |
| Wood Code | None |
| Wood Temperature | < 100F |
| Concrete Code | None |
| Masonry Code | None |
| Aluminum Code | None - Building |
| Stainless Steel Code | None |

| | |
|-------------------------------|--------------------|
| Number of Shear Regions | 4 |
| Region Spacing Increment (in) | 4 |
| Biaxial Column Method | Exact Integration |
| Parmer Beta Factor (PCA) | .65 |
| Concrete Stress Block | Rectangular |
| Use Cracked Sections? | Yes |
| Use Cracked Sections Slab? | Yes |
| Bad Framing Warnings? | No |
| Unused Force Warnings? | Yes |
| Min 1 Bar Diam. Spacing? | No |
| Concrete Rebar Set | REBAR_SET_ASTMA615 |
| Min % Steel for Column | 1 |
| Max % Steel for Column | 8 |

(Global) Model Settings, Continued

| | |
|-----------------------------|-------------|
| Seismic Code | ASCE 7-10 |
| Seismic Base Elevation (in) | Not Entered |
| Add Base Weight? | Yes |
| Ct X | .02 |
| Ct Z | .02 |
| T X (sec) | Not Entered |
| T Z (sec) | Not Entered |
| R X | 3 |
| R Z | 3 |
| Ct Exp. X | .75 |
| Ct Exp. Z | .75 |
| SD1 | 1 |
| SDS | 1 |
| S1 | 1 |
| TL (sec) | 5 |
| Risk Cat | I or II |
| Drift Cat | Other |
| Om Z | 1 |
| Om X | 1 |
| Cd Z | 4 |
| Cd X | 4 |
| Rho Z | 1 |
| Rho X | 1 |

Hot Rolled Steel Properties

| Label | E [ksi] | G [ksi] | Nu | Therm ... | Density[k/ft^3] | Yield[ksi] | Ry | Fu[ksi] | Rt |
|-------------|---------|---------|----|-----------|-----------------|------------|-----|---------|-----|
| 1 A36 Gr.36 | 29000 | 11154 | .3 | .65 | .49 | 36 | 1.5 | 58 | 1.2 |
| 2 A53 Gr.B | 29000 | 11154 | .3 | .65 | .49 | 35 | 1.6 | 60 | 1.2 |
| 3 Q235 Gr B | 29000 | 11154 | .3 | .65 | .527 | 34 | 1.4 | 58 | 1.3 |

Member Primary Data

| Label | I Joint | J Joint | K Joint | Rotate(...) | Section/Shape | Type | Design List | Material | Design ... |
|---------|---------|---------|---------|-------------|---------------|------|-------------|----------|------------|
| 1 M10 | N11 | N12 | | | RIGID | None | None | RIGID | Typical |
| 2 M14 | N18 | N19 | | | RIGID | None | None | RIGID | Typical |
| 3 M21 | N29 | N30 | | | RIGID | None | None | RIGID | Typical |
| 4 M22 | N32 | N31 | | | RIGID | None | None | RIGID | Typical |
| 5 M25 | N35 | N36 | | | RIGID | None | None | RIGID | Typical |
| 6 M29 | N42 | N43 | | | RIGID | None | None | RIGID | Typical |
| 7 M36 | N54 | N53 | | | RIGID | None | None | RIGID | Typical |
| 8 M37 | N56 | N55 | | | RIGID | None | None | RIGID | Typical |
| 9 M40 | N60 | N61 | | | RIGID | None | None | RIGID | Typical |
| 10 M43 | N65 | N66 | | | RIGID | None | None | RIGID | Typical |
| 11 M50 | N77 | N76 | | | RIGID | None | None | RIGID | Typical |
| 12 M51 | N78 | N79 | | | RIGID | None | None | RIGID | Typical |
| 13 M52 | N81 | N80 | | | RIGID | None | None | RIGID | Typical |
| 14 M76 | N95 | N94 | | | RIGID | None | None | RIGID | Typical |
| 15 M64 | N99 | N98 | | | RIGID | None | None | RIGID | Typical |
| 16 M65 | N101 | N100 | | | RIGID | None | None | RIGID | Typical |
| 17 M67 | N105 | N104 | | | RIGID | None | None | RIGID | Typical |
| 18 M68 | N107 | N106 | | | RIGID | None | None | RIGID | Typical |
| 19 M70A | N111 | N110 | | | RIGID | None | None | RIGID | Typical |
| 20 M71A | N113 | N112 | | | RIGID | None | None | RIGID | Typical |
| 21 M73A | N117 | N116 | | | RIGID | None | None | RIGID | Typical |
| 22 M74A | N119 | N118 | | | RIGID | None | None | RIGID | Typical |
| 23 M76A | N123 | N122 | | | RIGID | None | None | RIGID | Typical |

Member Primary Data (Continued)

| Label | I Joint | J Joint | K Joint | Rotate(...) | Section/Shape | Type | Design List | Material | Design ... |
|-------|---------|---------|---------|-------------|---------------|------|-------------|-----------|------------|
| 24 | M77 | N125 | N124 | | RIGID | None | None | RIGID | Typical |
| 25 | M79 | N129 | N128 | | RIGID | None | None | RIGID | Typical |
| 26 | M80 | N131 | N130 | | RIGID | None | None | RIGID | Typical |
| 27 | M82 | N135 | N134 | | RIGID | None | None | RIGID | Typical |
| 28 | M83 | N137 | N136 | | RIGID | None | None | RIGID | Typical |
| 29 | M85A | N141 | N140 | | RIGID | None | None | RIGID | Typical |
| 30 | M86A | N143 | N142 | | RIGID | None | None | RIGID | Typical |
| 31 | M88 | N147 | N146 | | RIGID | None | None | RIGID | Typical |
| 32 | M89 | N149 | N148 | | RIGID | None | None | RIGID | Typical |
| 33 | M91 | N153 | N152 | | RIGID | None | None | RIGID | Typical |
| 34 | M92 | N155 | N154 | | RIGID | None | None | RIGID | Typical |
| 35 | M94 | N159 | N158 | | RIGID | None | None | RIGID | Typical |
| 36 | M95 | N161 | N160 | | RIGID | None | None | RIGID | Typical |
| 37 | M15 | N22 | N20 | | PL6x0.375 | None | None | Q235 Gr B | Typical |
| 38 | M16 | N21 | N22 | | PL6x0.375 | None | None | Q235 Gr B | Typical |
| 39 | M18 | N26 | N24 | | PL6x0.375 | None | None | Q235 Gr B | Typical |
| 40 | M19 | N25 | N26 | | PL6x0.375 | None | None | Q235 Gr B | Typical |
| 41 | M30 | N46 | N44 | | PL6x0.375 | None | None | Q235 Gr B | Typical |
| 42 | M31 | N45 | N46 | | PL6x0.375 | None | None | Q235 Gr B | Typical |
| 43 | M33 | N50 | N48 | | PL6x0.375 | None | None | Q235 Gr B | Typical |
| 44 | M34 | N49 | N50 | | PL6x0.375 | None | None | Q235 Gr B | Typical |
| 45 | M44 | N69 | N67 | | PL6x0.375 | None | None | Q235 Gr B | Typical |
| 46 | M45 | N68 | N69 | | PL6x0.375 | None | None | Q235 Gr B | Typical |
| 47 | M47 | N73 | N71 | | PL6x0.375 | None | None | Q235 Gr B | Typical |
| 48 | M48 | N72 | N73 | | PL6x0.375 | None | None | Q235 Gr B | Typical |
| 49 | M9 | N10 | N15 | | PL 6" x 1/2" | None | None | Q235 Gr B | Typical |
| 50 | M12 | N17 | N15 | | PL 6" x 1/2" | None | None | Q235 Gr B | Typical |
| 51 | M13 | N16 | N17 | | PL 6" x 1/2" | None | None | Q235 Gr B | Typical |
| 52 | M24 | N34 | N39 | | PL 6" x 1/2" | None | None | Q235 Gr B | Typical |
| 53 | M27 | N41 | N39 | | PL 6" x 1/2" | None | None | Q235 Gr B | Typical |
| 54 | M28 | N40 | N41 | | PL 6" x 1/2" | None | None | Q235 Gr B | Typical |
| 55 | M39 | N59 | N62 | | PL 6" x 1/2" | None | None | Q235 Gr B | Typical |
| 56 | M41 | N64 | N62 | | PL 6" x 1/2" | None | None | Q235 Gr B | Typical |
| 57 | M42 | N63 | N64 | | PL 6" x 1/2" | None | None | Q235 Gr B | Typical |
| 58 | CBA1 | N1 | N2 | | PIPE_3.0 | None | None | A53 Gr.B | Typical |
| 59 | CBC1 | N13 | N14 | | PIPE_3.0 | None | None | A53 Gr.B | Typical |
| 60 | CBB1 | N37 | N38 | | PIPE_3.0 | None | None | A53 Gr.B | Typical |
| 61 | CBA2 | N82 | N83 | | PIPE_2.0 | None | None | A53 Gr.B | Typical |
| 62 | CBC2 | N84 | N85 | | PIPE_2.0 | None | None | A53 Gr.B | Typical |
| 63 | CBB2 | N86 | N87 | | PIPE_2.0 | None | None | A53 Gr.B | Typical |
| 64 | C4 | N96 | N97 | | PIPE_2.0 | None | None | A53 Gr.B | Typical |
| 65 | C3 | N102 | N103 | | PIPE_2.0 | None | None | A53 Gr.B | Typical |
| 66 | C2 | N108 | N109 | | PIPE_2.0 | None | None | A53 Gr.B | Typical |
| 67 | C1 | N114 | N115 | | PIPE_2.0 | None | None | A53 Gr.B | Typical |
| 68 | B4 | N120 | N121 | | PIPE_2.0 | None | None | A53 Gr.B | Typical |
| 69 | B3 | N126 | N127 | | PIPE_2.0 | None | None | A53 Gr.B | Typical |
| 70 | B2 | N132 | N133 | | PIPE_2.0 | None | None | A53 Gr.B | Typical |
| 71 | B1 | N138 | N139 | | PIPE_2.0 | None | None | A53 Gr.B | Typical |
| 72 | A4 | N144 | N145 | | PIPE_2.0 | None | None | A53 Gr.B | Typical |
| 73 | A3 | N150 | N151 | | PIPE_2.0 | None | None | A53 Gr.B | Typical |
| 74 | A2 | N156 | N157 | | PIPE_2.0 | None | None | A53 Gr.B | Typical |
| 75 | A1 | N162 | N163 | | PIPE_2.0 | None | None | A53 Gr.B | Typical |
| 76 | M2 | N9 | N3 | 270 | L2x2x3 | None | None | A53 Gr.B | Typical |
| 77 | M3 | N9 | N4 | | L2x2x3 | None | None | A53 Gr.B | Typical |
| 78 | M4 | N33 | N5 | 270 | L2x2x3 | None | None | A53 Gr.B | Typical |
| 79 | M5 | N33 | N6 | | L2x2x3 | None | None | A53 Gr.B | Typical |
| 80 | M6 | N58 | N7 | 270 | L2x2x3 | None | None | A53 Gr.B | Typical |

Member Primary Data (Continued)

| Label | I Joint | J Joint | K Joint | Rotate(...) | Section/Shape | Type | Design List | Material | Design ... |
|-------|---------|---------|---------|-------------|---------------|------|-------------|-----------|------------|
| 81 | M7 | N58 | N8 | | L2x2x3 | None | None | A53 Gr.B | Typical |
| 82 | M73 | N89 | N88 | 90 | L2.5x2.5x4 | None | None | A53 Gr.B | Typical |
| 83 | M74 | N91 | N90 | 90 | L2.5x2.5x4 | None | None | A53 Gr.B | Typical |
| 84 | M75 | N93 | N92 | 90 | L2.5x2.5x4 | None | None | A53 Gr.B | Typical |
| 85 | M17 | N23 | N28 | | HSS4X4X4 | None | None | Q235 Gr B | Typical |
| 86 | M20 | N27 | N28 | | HSS4X4X4 | None | None | Q235 Gr B | Typical |
| 87 | M32 | N47 | N52 | | HSS4X4X4 | None | None | Q235 Gr B | Typical |
| 88 | M35 | N51 | N52 | | HSS4X4X4 | None | None | Q235 Gr B | Typical |
| 89 | M38 | N57 | N58 | | HSS4X4X4 | None | None | Q235 Gr B | Typical |
| 90 | M46 | N70 | N75 | | HSS4X4X4 | None | None | Q235 Gr B | Typical |
| 91 | M49 | N74 | N75 | | HSS4X4X4 | None | None | Q235 Gr B | Typical |
| 92 | M93 | N164 | N9 | | HSS4X4X4 | None | None | Q235 Gr B | Typical |
| 93 | M95A | N165 | N33 | | HSS4X4X4 | None | None | Q235 Gr B | Typical |

Member Advanced Data

| Label | I Release | J Release | I Offset[in] | J Offset[in] | T/C Only | Physical | Defl Rat... | Analysis ... | Inactive | Seismic... |
|-------|-----------|-----------|--------------|--------------|----------|----------|-------------|--------------|----------|------------|
| 1 | M10 | BenPIN | | | | Yes | ** NA ** | | | None |
| 2 | M14 | BenPIN | | | | Yes | ** NA ** | | | None |
| 3 | M21 | | BenPIN | | | Yes | ** NA ** | | | None |
| 4 | M22 | BenPIN | | | | Yes | ** NA ** | | | None |
| 5 | M25 | BenPIN | | | | Yes | ** NA ** | | | None |
| 6 | M29 | BenPIN | | | | Yes | ** NA ** | | | None |
| 7 | M36 | BenPIN | | | | Yes | ** NA ** | | | None |
| 8 | M37 | BenPIN | | | | Yes | ** NA ** | | | None |
| 9 | M40 | BenPIN | | | | Yes | ** NA ** | | | None |
| 10 | M43 | BenPIN | | | | Yes | ** NA ** | | | None |
| 11 | M50 | BenPIN | | | | Yes | ** NA ** | | | None |
| 12 | M51 | | BenPIN | | | Yes | ** NA ** | | | None |
| 13 | M52 | | | | | Yes | ** NA ** | | | None |
| 14 | M76 | | | | | Yes | ** NA ** | | | None |
| 15 | M64 | | | | | Yes | ** NA ** | | | None |
| 16 | M65 | | | | | Yes | ** NA ** | | | None |
| 17 | M67 | | | | | Yes | ** NA ** | | | None |
| 18 | M68 | | | | | Yes | ** NA ** | | | None |
| 19 | M70A | | | | | Yes | ** NA ** | | | None |
| 20 | M71A | | | | | Yes | ** NA ** | | | None |
| 21 | M73A | | | | | Yes | ** NA ** | | | None |
| 22 | M74A | | | | | Yes | ** NA ** | | | None |
| 23 | M76A | | | | | Yes | ** NA ** | | | None |
| 24 | M77 | | | | | Yes | ** NA ** | | | None |
| 25 | M79 | | | | | Yes | ** NA ** | | | None |
| 26 | M80 | | | | | Yes | ** NA ** | | | None |
| 27 | M82 | | | | | Yes | ** NA ** | | | None |
| 28 | M83 | | | | | Yes | ** NA ** | | | None |
| 29 | M85A | | | | | Yes | ** NA ** | | | None |
| 30 | M86A | | | | | Yes | ** NA ** | | | None |
| 31 | M88 | | | | | Yes | ** NA ** | | | None |
| 32 | M89 | | | | | Yes | ** NA ** | | | None |
| 33 | M91 | | | | | Yes | ** NA ** | | | None |
| 34 | M92 | | | | | Yes | ** NA ** | | | None |
| 35 | M94 | | | | | Yes | ** NA ** | | | None |
| 36 | M95 | | | | | Yes | ** NA ** | | | None |
| 37 | M15 | | | | | Yes | ** NA ** | | | None |
| 38 | M16 | | | | | Yes | ** NA ** | | | None |
| 39 | M18 | | | | | Yes | ** NA ** | | | None |

Member Advanced Data (Continued)

| Label | I Release | J Release | I Offset[in] | J Offset[in] | T/C Only | Physical | Defl Rat... | Analysis ... | Inactive | Seismic... |
|-------|-----------|-----------|--------------|--------------|----------|----------|-------------|--------------|----------|------------|
| 40 | M19 | | | | | Yes | ** NA ** | | | None |
| 41 | M30 | | | | | Yes | ** NA ** | | | None |
| 42 | M31 | | | | | Yes | ** NA ** | | | None |
| 43 | M33 | | | | | Yes | ** NA ** | | | None |
| 44 | M34 | | | | | Yes | ** NA ** | | | None |
| 45 | M44 | | | | | Yes | ** NA ** | | | None |
| 46 | M45 | | | | | Yes | ** NA ** | | | None |
| 47 | M47 | | | | | Yes | ** NA ** | | | None |
| 48 | M48 | | | | | Yes | ** NA ** | | | None |
| 49 | M9 | | | | | Yes | ** NA ** | | | None |
| 50 | M12 | | | | | Yes | ** NA ** | | | None |
| 51 | M13 | | | | | Yes | ** NA ** | | | None |
| 52 | M24 | | | | | Yes | ** NA ** | | | None |
| 53 | M27 | | | | | Yes | ** NA ** | | | None |
| 54 | M28 | | | | | Yes | ** NA ** | | | None |
| 55 | M39 | | | | | Yes | ** NA ** | | | None |
| 56 | M41 | | | | | Yes | ** NA ** | | | None |
| 57 | M42 | | | | | Yes | ** NA ** | | | None |
| 58 | CBA1 | | | | | Yes | ** NA ** | | | None |
| 59 | CBC1 | | | | | Yes | ** NA ** | | | None |
| 60 | CBB1 | | | | | Yes | ** NA ** | | | None |
| 61 | CBA2 | | | | | Yes | ** NA ** | | | None |
| 62 | CBC2 | | | | | Yes | ** NA ** | | | None |
| 63 | CBB2 | | | | | Yes | ** NA ** | | | None |
| 64 | C4 | | | | | Yes | ** NA ** | | | None |
| 65 | C3 | | | | | Yes | ** NA ** | | | None |
| 66 | C2 | | | | | Yes | ** NA ** | | | None |
| 67 | C1 | | | | | Yes | ** NA ** | | | None |
| 68 | B4 | | | | | Yes | ** NA ** | | | None |
| 69 | B3 | | | | | Yes | ** NA ** | | | None |
| 70 | B2 | | | | | Yes | ** NA ** | | | None |
| 71 | B1 | | | | | Yes | ** NA ** | | | None |
| 72 | A4 | | | | | Yes | ** NA ** | | | None |
| 73 | A3 | | | | | Yes | ** NA ** | | | None |
| 74 | A2 | | | | | Yes | ** NA ** | | | None |
| 75 | A1 | | | | | Yes | ** NA ** | | | None |
| 76 | M2 | BenPIN | BenPIN | | | Yes | ** NA ** | | | None |
| 77 | M3 | BenPIN | BenPIN | | | Yes | ** NA ** | | | None |
| 78 | M4 | BenPIN | BenPIN | | | Yes | ** NA ** | | | None |
| 79 | M5 | BenPIN | BenPIN | | | Yes | ** NA ** | | | None |
| 80 | M6 | BenPIN | BenPIN | | | Yes | ** NA ** | | | None |
| 81 | M7 | BenPIN | BenPIN | | | Yes | ** NA ** | | | None |
| 82 | M73 | | | | | Yes | ** NA ** | | | None |
| 83 | M74 | | | | | Yes | ** NA ** | | | None |
| 84 | M75 | | | | | Yes | ** NA ** | | | None |
| 85 | M17 | | | | | Yes | ** NA ** | | | None |
| 86 | M20 | | | | | Yes | ** NA ** | | | None |
| 87 | M32 | | | | | Yes | ** NA ** | | | None |
| 88 | M35 | | | | | Yes | ** NA ** | | | None |
| 89 | M38 | | | | | Yes | ** NA ** | | | None |
| 90 | M46 | | | | | Yes | ** NA ** | | | None |
| 91 | M49 | | | | | Yes | ** NA ** | | | None |
| 92 | M93 | | | | | Yes | ** NA ** | | | None |
| 93 | M95A | | | | | Yes | ** NA ** | | | None |

Hot Rolled Steel Design Parameters

| Label | Shape | Length[in] | Lbyy[in] | Lbzz[in] | Lcomp top[i..Lcomp bot[i..L-torq... | Kyy | Kzz | Cb | Function |
|-------|-------|--------------|----------|----------|-------------------------------------|-----|-----|----|----------|
| 1 | M15 | PL6x0.375 | 5.363 | | Lbyy | | | | Lateral |
| 2 | M16 | PL6x0.375 | 3.499 | | Lbyy | | | | Lateral |
| 3 | M18 | PL6x0.375 | 5.363 | | Lbyy | | | | Lateral |
| 4 | M19 | PL6x0.375 | 3.499 | | Lbyy | | | | Lateral |
| 5 | M30 | PL6x0.375 | 5.363 | | Lbyy | | | | Lateral |
| 6 | M31 | PL6x0.375 | 3.499 | | Lbyy | | | | Lateral |
| 7 | M33 | PL6x0.375 | 5.363 | | Lbyy | | | | Lateral |
| 8 | M34 | PL6x0.375 | 3.499 | | Lbyy | | | | Lateral |
| 9 | M44 | PL6x0.375 | 5.363 | | Lbyy | | | | Lateral |
| 10 | M45 | PL6x0.375 | 3.499 | | Lbyy | | | | Lateral |
| 11 | M47 | PL6x0.375 | 5.363 | | Lbyy | | | | Lateral |
| 12 | M48 | PL6x0.375 | 3.499 | | Lbyy | | | | Lateral |
| 13 | M9 | PL 6" x 1/2" | 3.184 | | Lbyy | | | | Lateral |
| 14 | M12 | PL 6" x 1/2" | 12.707 | | Lbyy | | | | Lateral |
| 15 | M13 | PL 6" x 1/2" | 3.184 | | Lbyy | | | | Lateral |
| 16 | M24 | PL 6" x 1/2" | 3.184 | | Lbyy | | | | Lateral |
| 17 | M27 | PL 6" x 1/2" | 12.707 | | Lbyy | | | | Lateral |
| 18 | M28 | PL 6" x 1/2" | 3.184 | | Lbyy | | | | Lateral |
| 19 | M39 | PL 6" x 1/2" | 3.184 | | Lbyy | | | | Lateral |
| 20 | M41 | PL 6" x 1/2" | 12.707 | | Lbyy | | | | Lateral |
| 21 | M42 | PL 6" x 1/2" | 3.184 | | Lbyy | | | | Lateral |
| 22 | CBA1 | PIPE 3.0 | 150 | | Lbyy | | | | Lateral |
| 23 | CBC1 | PIPE 3.0 | 150 | | Lbyy | | | | Lateral |
| 24 | CBB1 | PIPE 3.0 | 150 | | Lbyy | | | | Lateral |
| 25 | CBA2 | PIPE 2.0 | 150 | | Lbyy | | | | Lateral |
| 26 | CBC2 | PIPE 2.0 | 150 | | Lbyy | | | | Lateral |
| 27 | CBB2 | PIPE 2.0 | 150 | | Lbyy | | | | Lateral |
| 28 | C4 | PIPE 2.0 | 96 | | | | | | Lateral |
| 29 | C3 | PIPE 2.0 | 96 | | | | | | Lateral |
| 30 | C2 | PIPE 2.0 | 96 | | | | | | Lateral |
| 31 | C1 | PIPE 2.0 | 96 | | | | | | Lateral |
| 32 | B4 | PIPE 2.0 | 96 | | | | | | Lateral |
| 33 | B3 | PIPE 2.0 | 96 | | | | | | Lateral |
| 34 | B2 | PIPE 2.0 | 96 | | | | | | Lateral |
| 35 | B1 | PIPE 2.0 | 96 | | | | | | Lateral |
| 36 | A4 | PIPE 2.0 | 96 | | | | | | Lateral |
| 37 | A3 | PIPE 2.0 | 96 | | | | | | Lateral |
| 38 | A2 | PIPE 2.0 | 96 | | | | | | Lateral |
| 39 | A1 | PIPE 2.0 | 96 | | | | | | Lateral |
| 40 | M2 | L2x2x3 | 51.837 | | Lbyy | | | | Lateral |
| 41 | M3 | L2x2x3 | 51.837 | | Lbyy | | | | Lateral |
| 42 | M4 | L2x2x3 | 51.837 | | Lbyy | | | | Lateral |
| 43 | M5 | L2x2x3 | 51.837 | | Lbyy | | | | Lateral |
| 44 | M6 | L2x2x3 | 51.837 | | Lbyy | | | | Lateral |
| 45 | M7 | L2x2x3 | 51.837 | | Lbyy | | | | Lateral |
| 46 | M73 | L2.5x2.5x4 | 19.173 | | | | | | Lateral |
| 47 | M74 | L2.5x2.5x4 | 19.173 | | | | | | Lateral |
| 48 | M75 | L2.5x2.5x4 | 19.173 | | | | | | Lateral |
| 49 | M17 | HSS4X4X4 | 30.71 | | Lbyy | | | | Lateral |
| 50 | M20 | HSS4X4X4 | 30.71 | | Lbyy | | | | Lateral |
| 51 | M32 | HSS4X4X4 | 30.71 | | Lbyy | | | | Lateral |
| 52 | M35 | HSS4X4X4 | 30.71 | | Lbyy | | | | Lateral |
| 53 | M38 | HSS4X4X4 | 68.014 | | Lbyy | | | | Lateral |
| 54 | M46 | HSS4X4X4 | 30.71 | | Lbyy | | | | Lateral |
| 55 | M49 | HSS4X4X4 | 30.71 | | Lbyy | | | | Lateral |
| 56 | M93 | HSS4X4X4 | 68.014 | | Lbyy | | | | Lateral |

Hot Rolled Steel Design Parameters (Continued)

| Label | Shape | Length[in] | Lbyy[in] | Lbzz[in] | Lcomp top[i..Lcomp bot[i..L-torq... | Kyy | Kzz | Cb | Function |
|-------|-------|------------|----------|----------|-------------------------------------|-----|-----|----|----------|
| 57 | M95A | HSS4X4X4 | 68.014 | | Lbyy | | | | Lateral |

Basic Load Cases

| BLC Description | | Category | X Gravity | Y Gravity | Z Gravity | Joint | Point | Distrib... | Area(M...) | Surfac... |
|-----------------|----------------------------|----------|-----------|-----------|-----------|-------|-------|------------|------------|-----------|
| 1 | Dead | None | | -1.1 | | | 30 | | 3 | |
| 2 | Wind 0 | None | | | | | 60 | 114 | | |
| 3 | Wind 30 | None | | | | | 60 | 114 | | |
| 4 | Wind 60 | None | | | | | 60 | 114 | | |
| 5 | Wind 90 | None | | | | | 60 | 114 | | |
| 6 | Wind 120 | None | | | | | 60 | 114 | | |
| 7 | Wind 150 | None | | | | | 60 | 114 | | |
| 8 | Ice Load | None | | | | | 30 | 57 | 3 | |
| 9 | Ice 0 | None | | | | | 60 | 114 | | |
| 10 | Ice 30 | None | | | | | 60 | 114 | | |
| 11 | Ice 60 | None | | | | | 60 | 114 | | |
| 12 | Ice 90 | None | | | | | 60 | 114 | | |
| 13 | Ice 120 | None | | | | | 60 | 114 | | |
| 14 | Ice 150 | None | | | | | 60 | 114 | | |
| 15 | Lm1 | None | | | | 1 | | | | |
| 16 | Lm2 | None | | | | 1 | | | | |
| 17 | Lm3 | None | | | | 1 | | | | |
| 18 | Lm4 | None | | | | 1 | | | | |
| 19 | Lv1 | None | | | | 1 | | | | |
| 20 | Lv2 | None | | | | 1 | | | | |
| 21 | Lv3 | None | | | | 1 | | | | |
| 22 | Lv4 | None | | | | 1 | | | | |
| 23 | BLC 1 Transient Area Loads | None | | | | | | 75 | | |
| 24 | BLC 8 Transient Area Loads | None | | | | | | 75 | | |

Load Combinations

Load Combinations (Continued)

Envelope Joint Reactions

| Joint | | X [lb] | LC | Y [lb] | LC | Z [lb] | LC | MX [k-ft] | LC | MY [k-ft] | LC | MZ [k-ft] | LC | |
|-------|---------|--------|-----------|--------|----------|--------|-----------|-----------|--------|-----------|--------|-----------|--------|----|
| 1 | N57 | max | 1738.504 | 11 | 2689.512 | 17 | 638.527 | 2 | .607 | 2 | 1.296 | 8 | 6.928 | 17 |
| 2 | | min | -1679.141 | 5 | -75.157 | 11 | -632.839 | 8 | -.763 | 8 | -1.278 | 2 | -1.24 | 11 |
| 3 | N164 | max | 858.068 | 13 | 2689.513 | 25 | 1443.415 | 13 | 6.104 | 25 | 1.297 | 4 | .709 | 6 |
| 4 | | min | -882.027 | 7 | -75.101 | 7 | -1498.129 | 7 | -1.04 | 7 | -1.278 | 10 | -3.291 | 24 |
| 5 | N165 | max | 917.997 | 11 | 2689.54 | 21 | 1512.937 | 3 | 1.108 | 3 | 1.296 | 12 | .634 | 4 |
| 6 | | min | -952.838 | 5 | -75.085 | 3 | -1464.834 | 9 | -5.896 | 21 | -1.278 | 6 | -3.658 | 22 |
| 7 | Totals: | max | 3355.995 | 11 | 7301.745 | 22 | 3355.77 | 2 | | | | | | |
| 8 | | min | -3355.993 | 5 | 2281.999 | 78 | -3355.774 | 8 | | | | | | |

Envelope AISC 15th(360-16): LRFD Steel Code Checks

| Member | Shape | Code Check | Loc... | LC | Shear Check Loc..... | LC | phi*P... | phi*P... | phi*M... | phi*M..... | Eqn | | | |
|--------|-------|--------------|--------|--------|----------------------|------|----------|----------|----------|------------|--------|-------|--------|-------|
| 1 | CBC2 | PIPE 2.0 | .598 | 135... | 6 | .373 | 143... | 6 | 6295... | 32130 | 1.872 | 1.872 | H3-6 | |
| 2 | CBA2 | PIPE 2.0 | .598 | 135... | 10 | .373 | 143... | 10 | 6295... | 32130 | 1.872 | 1.872 | H3-6 | |
| 3 | CBB2 | PIPE 2.0 | .598 | 135... | 2 | .373 | 143... | 2 | 6295... | 32130 | 1.872 | 1.872 | H3-6 | |
| 4 | C1 | PIPE 2.0 | .592 | 56 | 11 | .232 | 56 | 11 | 14916... | 32130 | 1.872 | 1.872 | H1-1b | |
| 5 | B1 | PIPE 2.0 | .590 | 56 | 7 | .232 | 56 | 7 | 14916... | 32130 | 1.872 | 1.872 | H1-1b | |
| 6 | M95A | HSS4X4X4 | .582 | 0 | 21 | .126 | 0 | y | 44 | 93367... | 103122 | 11.96 | 11.96 | H1-1b |
| 7 | M93 | HSS4X4X4 | .582 | 0 | 25 | .130 | 0 | y | 63 | 93367... | 103122 | 11.96 | 11.96 | H1-1b |
| 8 | M38 | HSS4X4X4 | .582 | 0 | 17 | .126 | 0 | y | 19 | 93367... | 103122 | 11.96 | 11.96 | H1-1b |
| 9 | A1 | PIPE 2.0 | .515 | 56 | 3 | .232 | 56 | 3 | 14916... | 32130 | 1.872 | 1.872 | H1-1b | |
| 10 | M73 | L2.5x2.5x4 | .443 | 19.... | 10 | .157 | 19.... | z | 5 | 34569... | 37485 | 1.083 | 2.467 | H2-1 |
| 11 | M74 | L2.5x2.5x4 | .443 | 19.... | 6 | .157 | 19.... | z | 13 | 34569... | 37485 | 1.083 | 2.467 | H2-1 |
| 12 | M75 | L2.5x2.5x4 | .443 | 19.... | 2 | .157 | 19.... | z | 9 | 34569... | 37485 | 1.083 | 2.467 | H2-1 |
| 13 | A2 | PIPE 2.0 | .429 | 14 | 6 | .089 | 14 | 7 | 14916... | 32130 | 1.872 | 1.872 | H1-1b | |
| 14 | B2 | PIPE 2.0 | .429 | 14 | 10 | .089 | 14 | 11 | 14916... | 32130 | 1.872 | 1.872 | H1-1b | |
| 15 | C2 | PIPE 2.0 | .429 | 14 | 2 | .089 | 14 | 3 | 14916... | 32130 | 1.872 | 1.872 | H1-1b | |
| 16 | B4 | PIPE 2.0 | .413 | 14 | 5 | .190 | 56 | 7 | 14916... | 32130 | 1.872 | 1.872 | H1-1b | |
| 17 | A4 | PIPE 2.0 | .413 | 14 | 13 | .190 | 56 | 3 | 14916... | 32130 | 1.872 | 1.872 | H1-1b | |
| 18 | C4 | PIPE 2.0 | .413 | 14 | 9 | .190 | 56 | 11 | 14916... | 32130 | 1.872 | 1.872 | H1-1b | |
| 19 | B3 | PIPE 2.0 | .404 | 14 | 5 | .088 | 14 | 8 | 14916... | 32130 | 1.872 | 1.872 | H1-1b | |
| 20 | A3 | PIPE 2.0 | .404 | 14 | 13 | .088 | 14 | 4 | 14916... | 32130 | 1.872 | 1.872 | H1-1b | |
| 21 | C3 | PIPE 2.0 | .404 | 14 | 9 | .088 | 14 | 12 | 14916... | 32130 | 1.872 | 1.872 | H1-1b | |
| 22 | M17 | HSS4X4X4 | .247 | 30.... | 24 | .070 | 30.... | y | 24 | 10105... | 103122 | 11.96 | 11.96 | H1-1b |
| 23 | M32 | HSS4X4X4 | .247 | 30.... | 20 | .070 | 30.... | y | 20 | 10105... | 103122 | 11.96 | 11.96 | H1-1b |
| 24 | M46 | HSS4X4X4 | .247 | 30.... | 16 | .070 | 30.... | y | 16 | 10105... | 103122 | 11.96 | 11.96 | H1-1b |
| 25 | M35 | HSS4X4X4 | .237 | 30.... | 22 | .078 | 30.... | y | 22 | 10105... | 103122 | 11.96 | 11.96 | H1-1b |
| 26 | M49 | HSS4X4X4 | .237 | 30.... | 18 | .078 | 30.... | y | 18 | 10105... | 103122 | 11.96 | 11.96 | H1-1b |
| 27 | M20 | HSS4X4X4 | .237 | 30.... | 14 | .078 | 30.... | y | 14 | 10105... | 103122 | 11.96 | 11.96 | H1-1b |
| 28 | M44 | PL6x0.375 | .232 | 2.8... | 4 | .379 | 2.8... | y | 18 | 60835... | 68850 | .538 | 8.606 | H1-1b |
| 29 | M30 | PL6x0.375 | .232 | 2.8... | 8 | .379 | 2.8... | y | 22 | 60835... | 68850 | .538 | 8.606 | H1-1b |
| 30 | M15 | PL6x0.375 | .232 | 2.8... | 12 | .379 | 2.8... | y | 14 | 60835... | 68850 | .538 | 8.606 | H1-1b |
| 31 | M48 | PL6x0.375 | .218 | 1.4... | 12 | .408 | 3.4... | y | 17 | 65316... | 68850 | .538 | 8.606 | H1-1b |
| 32 | M34 | PL6x0.375 | .218 | 1.4... | 4 | .408 | 3.4... | y | 21 | 65316... | 68850 | .538 | 8.606 | H1-1b |
| 33 | M19 | PL6x0.375 | .218 | 1.4... | 8 | .408 | 3.4... | y | 25 | 65316... | 68850 | .538 | 8.606 | H1-1b |
| 34 | M18 | PL6x0.375 | .207 | 2.8... | 13 | .246 | 2.8... | y | 24 | 60835... | 68850 | .538 | 8.606 | H1-1b |
| 35 | M33 | PL6x0.375 | .207 | 2.8... | 9 | .246 | 2.8... | y | 20 | 60835... | 68850 | .538 | 8.606 | H1-1b |
| 36 | M47 | PL6x0.375 | .207 | 2.8... | 5 | .246 | 2.8... | y | 16 | 60835... | 68850 | .538 | 8.606 | H1-1b |
| 37 | M45 | PL6x0.375 | .202 | 1.4... | 10 | .415 | 3.4... | y | 17 | 65316... | 68850 | .538 | 8.606 | H1-1b |
| 38 | M16 | PL6x0.375 | .202 | 1.4... | 6 | .415 | 3.4... | y | 25 | 65316... | 68850 | .538 | 8.606 | H1-1b |
| 39 | M31 | PL6x0.375 | .202 | 1.4... | 2 | .415 | 3.4... | y | 21 | 65316... | 68850 | .538 | 8.606 | H1-1b |
| 40 | CBB1 | PIPE 3.0 | .196 | 50 | 19 | .079 | 50 | 8 | 28250... | 65205 | 5.749 | 5.749 | H1-1b | |
| 41 | CBC1 | PIPE 3.0 | .196 | 50 | 23 | .079 | 50 | 12 | 28250... | 65205 | 5.749 | 5.749 | H1-1b | |
| 42 | CBA1 | PIPE 3.0 | .196 | 50 | 15 | .079 | 50 | 4 | 28250... | 65205 | 5.749 | 5.749 | H1-1b | |
| 43 | M41 | PL 6" x 1/2" | .148 | 6.3... | 10 | .124 | 6.3... | y | 16 | 62633... | 91800 | .956 | 11.475 | H1-1b |

Envelope AISC 15th(360-16): LRFD Steel Code Checks (Continued)

| Member | Shape | Code Check | Loc... | LC | Shear Check Loc.... | LC | phi*P... | phi*P... | phi*M... | phi*M..... | Eqn |
|--------|-------|--------------|--------|--------|---------------------|------|----------|----------|----------|------------|-----------------------|
| 44 | M12 | PL 6" x 1/2" | .148 | 6.3... | 6 | .124 | 6.3...y | 24 | 62633.. | 91800 | .956 11.475 ... H1-1b |
| 45 | M27 | PL 6" x 1/2" | .148 | 6.3... | 2 | .124 | 6.3...y | 20 | 62633.. | 91800 | .956 11.475 ... H1-1b |
| 46 | M7 | L2x2x3 | .139 | 25.... | 6 | .009 | 51....y | 25 | 9165.... | 22743 | .542 1.039 ... H2-1 |
| 47 | M5 | L2x2x3 | .139 | 25.... | 10 | .009 | 51....y | 17 | 9165.... | 22743 | .542 1.039 ... H2-1 |
| 48 | M3 | L2x2x3 | .139 | 25.... | 2 | .009 | 51....y | 21 | 9165.... | 22743 | .542 1.039 ... H2-1 |
| 49 | M6 | L2x2x3 | .134 | 25.... | 4 | .012 | 51....z | 19 | 9165.... | 22743 | .542 1.038 ... H2-1 |
| 50 | M2 | L2x2x3 | .134 | 25.... | 12 | .012 | 51....z | 15 | 9165.... | 22743 | .542 1.038 ... H2-1 |
| 51 | M4 | L2x2x3 | .134 | 25.... | 8 | .012 | 51....z | 23 | 9165.... | 22743 | .542 1.038 ... H2-1 |
| 52 | M42 | PL 6" x 1/2" | .068 | 1.6... | 5 | .103 | 3.1...y | 6 | 89622.. | 91800 | .956 11.475 ... H1-1b |
| 53 | M28 | PL 6" x 1/2" | .068 | 1.6... | 9 | .127 | 3.1...y | 37 | 89622.. | 91800 | .956 11.475 ... H1-1b |
| 54 | M13 | PL 6" x 1/2" | .068 | 1.6... | 13 | .103 | 3.1...y | 2 | 89622.. | 91800 | .956 11.475 ... H1-1b |
| 55 | M39 | PL 6" x 1/2" | .067 | 1.6... | 5 | .079 | 1.6...y | 9 | 89622.. | 91800 | .956 11.475 ... H1-1b |
| 56 | M24 | PL 6" x 1/2" | .067 | 1.6... | 9 | .079 | 1.6...y | 13 | 89622.. | 91800 | .956 11.475 ... H1-1b |
| 57 | M9 | PL 6" x 1/2" | .067 | 1.6... | 13 | .079 | 1.6...y | 5 | 89622.. | 91800 | .956 11.475 ... H1-1b |

APPENDIX C

ADDITIONAL CALCULATIONS

| | |
|---------------|---------------------|
| Job Number: | 37520-2305.001.7190 |
| Engineer: | IOH |
| Date: | 11/17/2020 |
| Site Name: | HRT 046 943209 |
| Site Number: | 806367 |
| Order Number: | 479816 Rev 1 |

Mount to Tower Connection Checks (Version v4.6 - Effective Date 11/11/2020)

Risa File Path: G:\TOWER\375_Crown_Castle\2020\37520-2305_806367_HRT 046 943209\37520-2305.001.7190_MA\RISA\37520-2305.001.7190_Client.r3d

Total Populated Members: 93
Total Populated Nodes: 168

Settings Apply Capacity Normalization Per Section 15.5

Code: **TIA-222-H**
Check(s) Performed: **Bolts & Welds**

Risa-3D Member Reactions Input Forces Manually

Consider Tie-Backs: **No**
Consider Kickers: **No**
Consider Horizontal Members Only: **Yes**

Controlling Load Case: **17**
Controlling Member: **M38**
Member Orientation: **Horizontal** (in global Risa coordinate system)
Member Local Rotation: **0** (about its longitudinal axis)

Shear (kip) **Moment (kip-ft)**

| | | |
|-----------------------------------|-----------------|-------|
| Local Z Axis (Global Horizontal): | 0.012 | 6.928 |
| Local Y Axis (Global Vertical): | 2.688 | 0.013 |
| Axial (kip) | Torque (kip-ft) | |
| Local X Axis (Global Horizontal): | 0.404 | 0.304 |

Note: Forces are relative to member local axis

Bolt Information

Type: **A325N**
Diameter: **0.625** in
Quantity: **4**

Vertical Spacing (S_{VERT}): **6.00** in
Horizontal Spacing (S_{HORZ}): **6.00** in


Standoff Member Information

Type: **Rectangular**
Width (B): **4** in
Depth (D): **4** in
Thickness: **0.25** in

Weld Size: **0.375** in
Weld Size Assumed: **Yes**

Stiffener Information

Present: **No**



Analysis Results

32.4% Pass

Bolt Capacity

32.4%

Tension: Applied Load: 7.04 kip Capacity: 20.71 kip

Shear: Applied Load: 0.89 kip Capacity: 12.43 kip

Tension-Shear Interaction: Applied Load: - Capacity: -

Weld Capacity

30.4%

Applied Resultant Load: 2.67 kip/in

30.4%

Capacity: 8.35 kip/in



(Bolts Controls)

Notes:


1. Connection is considered fixed.
2. Allowable capacity limit is 100%. Values have been normalized by dividing by 1.05 per TIA-222-H Section 15.5
3. Calculations are in accordance with TIA-222-H and AISC 15th Ed.
4. Bolt tension reduction not required as tension and/or shear capacity is below 30%.

APPENDIX D

MANUFACTURER DRAWINGS (FOR REFERENCE ONLY)



| PARTS LIST | | | | | | |
|------------|-----|----------|--|-----------|----------|---------------------|
| ITEM | QTY | PART NO. | PART DESCRIPTION | LENGTH | UNIT WT. | NET WT. |
| 1 | 3 | X-SV196 | LOW PROFILE PLATFORM CORNER | | 212.10 | 636.31 |
| 2 | 3 | X-LWRM | RING MOUNT WELDMENT | | 68.81 | 206.42 |
| 3 | 3 | X-AHCP | ANGLE HANDRAIL CORNER PLATE | | 12.92 | 38.76 |
| 4 | 3 | P3150 | 3-1/2" X 150" (3" SCH 40) GALVANIZED PIPE | 150 in | 94.80 | 284.40 |
| 5 | 3 | P2150 | 2-3/8" O.D. X 150" SCH 40 GALVANIZED PIPE | 150 in | 45.77 | 137.31 |
| 6 | 30 | G58LW | 5/8" HDG LOCKWASHER | | 0.03 | 0.78 |
| 7 | 30 | A58NUT | 5/8" HDG A325 HEX NUT | | 0.13 | 3.90 |
| 8 | 9 | G58R-24 | 5/8" x 24" THREADED ROD (HDG.) | 24 in | 0.40 | 3.59 |
| 9 | 9 | G58R-48 | 5/8" x 48" THREADED ROD (HDG.) | 48 in | 0.40 | 3.59 |
| 10 | 12 | A58234 | 5/8" x 2-3/4" HDG A325 HEX BOLT | 2 3/4 in | 0.36 | 4.27 |
| 11 | 12 | A58FW | 5/8" HDG A325 FLATWASHER | | 0.03 | 0.41 |
| 12 | 12 | X-UB1212 | 1/2" X 2" X 3" X 1-1/4" U-BOLT (HDG.) | | 0.60 | 7.17 |
| 13 | 12 | X-UB1306 | 1/2" X 3-5/8" X 6" X 3" U-BOLT (HDG.) | | 0.83 | 9.94 |
| 14 | 192 | G12065 | 1/2" x 6-1/2" HDG HEX BOLT GR5 FULL THREAD | 5 1/2 in | 0.41 | 78.62 |
| 15 | 96 | G12045 | 1/2" x 4.5" HDG HEX BOLT GR5 FULL THREAD | 4 1/2 in | 0.30 | 28.61 |
| 16 | 432 | G12FW | 1/2" HDG USS FLATWASHER | 3/32 in | 0.03 | 14.72 |
| 17 | 240 | G12LW | 1/2" HDG LOCKWASHER | 1/8 in | 0.01 | 3.34 |
| 18 | 240 | G12NUT | 1/2" HDG HEAVY 2H HEX NUT | | 0.07 | 17.19 |
| 19 | 24 | SCX7 | CROSSOVER PLATE | 8 in | 7.55 | 181.17 |
| 20 | 48 | X-100064 | CLAMP (4" V-CLAMP) GALVANIZED | | 0.92 | 44.24 |
| 21 | 48 | X-115765 | 5" V-CLAMP | 7 1/16 in | 1.03 | 49.23 |
| | | | | | | TOTAL WT. # 1803.22 |



TOLERANCE NOTES

TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE:
SAWED, SHEARED AND GAS CUT EDGES ($\pm 0.030"$)
DRILLED AND GAS CUT HOLES ($\pm 0.030"$) - NO CONING OF HOLES
LASER CUT EDGES AND HOLES ($\pm 0.010"$) - NO CONING OF HOLES
BENDS ARE $\pm 1/2$ DEGREE
ALL OTHER MACHINING ($\pm 0.030"$)
ALL OTHER ASSEMBLY ($\pm 0.060"$)

DETAIL A
PROPRIETARY NOTE:
THE DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT INDUSTRIES AND CONSIDERED A TRADE SECRET. ANY USE OR DISCLOSURE WITHOUT THE CONSENT OF VALMONT INDUSTRIES IS STRICTLY PROHIBITED.

DESCRIPTION
12' 6" LOW PROFILE PLATFORM
WITH TWELVE 2-3/8" ANTENNA MOUNTING
PIPES, AND HANDRAIL

CPD NO. 4488 DRAWN BY CEK 7/14/2014 ENG. APPROVAL

CLASS 81 SUB 02 DRAWING USAGE CUSTOMER CHECKED BY BMC 6/28/2018






Engineering
Support Team:
1-888-753-7446

Locations:
New York, NY
Atlanta, GA
Los Angeles, CA
Plymouth, IN
Salem, OR
Dallas, TX

RMQP-SPT

RMQP-SPT



TOLERANCE NOTES

TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE:
 SAWED, SHEARED AND GAS CUT EDGES ($\pm 0.030"$)
 DRILLED AND GAS CUT HOLES ($\pm 0.030"$) - NO CONING OF HOLES
 LASER CUT EDGES AND HOLES ($\pm 0.010"$) - NO CONING OF HOLES
 BENDS ARE $\pm 1/2$ DEGREE
 ALL OTHER MACHINING ($\pm 0.030"$)
 ALL OTHER ASSEMBLY ($\pm 0.060"$)

PROPRIETARY NOTE:
 THE DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT INDUSTRIES AND CONSIDERED A TRADE SECRET. ANY USE OR DISCLOSURE WITHOUT THE CONSENT OF VALMONT INDUSTRIES IS STRICTLY PROHIBITED.

DESCRIPTION
 12' 6" LOW PROFILE PLATFORM
 WITH TWELVE 2-3/8" ANTENNA MOUNTING
 PIPES, AND HANDRAIL

CPD NO. 4488 DRAWN BY CEK 7/14/2014 ENG. APPROVAL

CLASS 81 SUB 02 DRAWING USAGE CUSTOMER CHECKED BY BMC 6/28/2018



Engineering
 Support Team:
 1-888-753-7446
 Locations:
 New York, NY
 Atlanta, GA
 Los Angeles, CA
 Plymouth, IN
 Salem, OR
 Dallas, TX

PART NO. RMQP-SPT

DWG. NO. RMQP-SPT

Transcom Engineering, Inc.

Wireless Network Design and Deployment

Radio Frequency Emissions Analysis Report

T-MOBILE Existing Facility

Site ID: CT11233A

Higginum_1
65 Maple Avenue West
Haddam, CT 06441

May 23, 2019

Transcom Engineering Project Number: 737001-0050

| Site Compliance Summary | |
|--|------------------|
| Compliance Status: | COMPLIANT |
| Site total MPE% of FCC general population allowable limit: | 13.70 % |

Transcom Engineering, Inc.

Wireless Network Design and Deployment

May 23, 2019

T-MOBILE
Attn: Jason Overbey, RF Manager
35 Griffin Road South
Bloomfield, CT 6009

Emissions Analysis for Site: **CT11233A – Higganum_1**

Transcom Engineering, Inc (“Transcom”) was directed to analyze the proposed upgrades to the T-MOBILE facility located at **65 Maple Avenue West, Haddam, CT**, for the purpose of determining whether the emissions from the Proposed T-MOBILE Antenna Installation located on this property are within specified federal limits.

All information used in this report was analyzed as a percentage of current Maximum Permissible Exposure (% MPE) as listed in the FCC OET Bulletin 65 Edition 97-01 and ANSI/IEEE Std C95.1. The FCC regulates Maximum Permissible Exposure in units of microwatts per square centimeter ($\mu\text{W}/\text{cm}^2$). The number of $\mu\text{W}/\text{cm}^2$ calculated at each sample point is called the power density. The exposure limit for power density varies depending upon the frequencies being utilized. Wireless Carriers and Paging Services use different frequency bands each with different exposure limits, therefore it is necessary to report results and limits in terms of percent MPE rather than power density.

All results were compared to the FCC (Federal Communications Commission) radio frequency exposure rules, 47 CFR 1.1307(b)(1) – (b)(3), to determine compliance with the Maximum Permissible Exposure (MPE) limits for General Population/Uncontrolled environments as defined below.

General population/uncontrolled exposure limits apply to situations in which the general population may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Therefore, members of the general population would always be considered under this category when exposure is not employment related, for example, in the case of a telecommunications tower that exposes persons in a nearby residential area.

Population exposure to radio frequencies is regulated and enforced in units of microwatts per square centimeter ($\mu\text{W}/\text{cm}^2$). The general population exposure limits for the 600 & 700 MHz bands are approximately 400 $\mu\text{W}/\text{cm}^2$ and 467 $\mu\text{W}/\text{cm}^2$ respectively. The general population exposure limit for the 1900 MHz (PCS) and 2100 MHz (AWS) bands is 1000 $\mu\text{W}/\text{cm}^2$. Because each carrier will be using different frequency bands, and each frequency band has different exposure limits, it is necessary to report percent of MPE rather than power density.

Transcom Engineering, Inc.

Wireless Network Design and Deployment

Occupational/controlled exposure limits apply to situations in which persons are exposed as a consequence of their employment and in which those persons who are exposed have been made fully aware of the potential for exposure and can exercise control over their exposure. Occupational/controlled exposure limits also apply where exposure is of a transient nature as a result of incidental passage through a location where exposure levels may be above general population/uncontrolled limits (see below), as long as the exposed person has been made fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Additional details can be found in FCC OET 65.

Transcom Engineering, Inc.

Wireless Network Design and Deployment

CALCULATIONS

Calculations were performed for the proposed upgrades to the T-MOBILE antenna facility located at **65 Maple Avenue West, Haddam, CT**, using the equipment information listed below. All calculations were performed per the specifications under FCC OET 65. Since T-MOBILE is proposing highly focused directional panel antennas, which project most of the emitted energy out toward the horizon, all calculations were performed assuming a lobe representing the maximum gain of the antenna per the antenna manufacturer's supplied specifications, minus 10 dB for directional panel antennas, was focused at the base of the tower. For this report the sample point is the top of a 6-foot person standing at the base of the tower.

Per FCC OET Bulletin No. 65 - Edition 97-01 recommendations to achieve the maximum anticipated value at each sample point, all power levels emitting from the proposed antenna installation are increased by a factor of 2.56 to account for possible in-phase reflections from the surrounding environment. All power values expressed and analyzed are maximum power levels expected to be used on all radios.

All emissions values for additional carriers were taken from the Connecticut Siting Council (CSC) active MPE database. Values in this database are provided by the individual carriers themselves.

For each sector the following channel counts, frequency bands and power levels were utilized as shown in *Table 1*:

| Technology | Frequency Band | Channel Count | Transmit Power per Channel (W) |
|-------------|----------------|---------------|--------------------------------|
| LTE / 5G NR | 600 MHz | 2 | 40 |
| LTE | 700 MHz | 2 | 20 |
| LTE | 1900 MHz (PCS) | 4 | 40 |
| GSM | 1900 MHz (PCS) | 1 | 15 |
| LTE | 2100 MHz (AWS) | 2 | 60 |

Table 1: Channel Data Table

Transcom Engineering, Inc.

Wireless Network Design and Deployment

The following antennas listed in *Table 2* were used in the modeling for transmission in the 600, 700 MHz, 1900 MHz (PCS) and 2100 MHz (AWS) frequency bands. This is based on feedback from the carrier with regards to anticipated antenna selection. Maximum gain values for all antennas are listed in the Inventory and Power Data table below. The maximum gain of the antenna per the antenna manufacturers supplied specifications, minus 10 dB for directional panel antennas, was used for all calculations. This value is a very conservative estimate as gain reductions for these particular antennas are typically much higher in this direction.

| Sector | Antenna Number | Antenna Make / Model | Antenna Centerline (ft) |
|--------|----------------|----------------------------|-------------------------|
| A | 1 | RFS APXVAARR24_43-U-NA20 | 120 |
| A | 2 | EMS RR90-17-XXDP (Dormant) | 120 |
| B | 1 | RFS APXVAARR24_43-U-NA20 | 120 |
| B | 2 | EMS RR90-17-XXDP (Dormant) | 120 |
| C | 1 | RFS APXVAARR24_43-U-NA20 | 120 |
| C | 2 | EMS RR90-17-XXDP (Dormant) | 120 |

Table 2: Antenna Data

All calculations were done with respect to uncontrolled / general population threshold limits.

Cable losses were factored in the calculations for this site. Since all **1900 MHz (PCS) and 2100 MHz (AWS)** radios are ground mounted the following cable loss values were used. For each ground mounted **1900 MHz (PCS)** radio there was **1.95 dB** of cable loss calculated into the system gains / losses for this site. For each ground mounted **2100 MHz (AWS)** radio there was **2.06 dB** of cable loss calculated into the system gains / losses for this site. These values were calculated based upon the manufacturers specifications for **160** feet of **1-1/4"** coax.

Transcom Engineering, Inc.

Wireless Network Design and Deployment

RESULTS

Per the calculations completed for the proposed T-MOBILE configurations *Table 3* shows resulting emissions power levels and percentages of the FCC's allowable general population limit.

| Antenna ID | Antenna Make / Model | Frequency Bands | Antenna Gain (dBd) | Channel Count | Total TX Power (W) | ERP (W) | MPE % |
|-------------------------|--------------------------|---|-------------------------------|---------------|--------------------|----------|-------------|
| Antenna A1 | RFS APXVAARR24_43-U-NA20 | 600 MHz / 700 MHz / 1900 MHz (PCS) / 2100 MHz (AWS) | 12.95 / 13.35 / 15.65 / 16.35 | 11 | 415 | 9,767.84 | 3.63 |
| Antenna A2 | EMS RR90-17-XXDP | Dormant | N/A | 0 | 0 | 0.00 | 0.00 |
| Sector A Composite MPE% | | | | | | | 3.63 |
| Antenna B1 | RFS APXVAARR24_43-U-NA20 | 600 MHz / 700 MHz / 1900 MHz (PCS) / 2100 MHz (AWS) | 12.95 / 13.35 / 15.65 / 16.35 | 11 | 415 | 9,767.84 | 3.63 |
| Antenna B2 | EMS RR90-17-XXDP | Dormant | N/A | 0 | 0 | 0.00 | 0.00 |
| Sector B Composite MPE% | | | | | | | 3.63 |
| Antenna C1 | RFS APXVAARR24_43-U-NA20 | 600 MHz / 700 MHz / 1900 MHz (PCS) / 2100 MHz (AWS) | 12.95 / 13.35 / 15.65 / 16.35 | 11 | 415 | 9,767.84 | 3.63 |
| Antenna C2 | EMS RR90-17-XXDP | Dormant | N/A | 0 | 0 | 0.00 | 0.00 |
| Sector C Composite MPE% | | | | | | | 3.63 |

Table 3: T-MOBILE Emissions Levels

Transcom Engineering, Inc.

Wireless Network Design and Deployment

The Following table (*table 4*) shows all additional carriers on site and their MPE% as recorded in the CSC active MPE database for this facility along with the newly calculated maximum T-MOBILE MPE contributions per this report. FCC OET 65 specifies that for carriers utilizing directional antennas that the highest recorded sector value be used for composite site MPE values due to their greatly reduced emissions contributions in the directions of the adjacent sectors. For this site, all three sectors have the same configuration yielding the same results on all three sectors. *Table 5* below shows a summary for each T-MOBILE Sector as well as the composite MPE value for the site.

| Site Composite MPE% | |
|---------------------------------|----------------|
| Carrier | MPE% |
| T-MOBILE – Max Per Sector Value | 3.63 % |
| Town | 0.89 % |
| AT&T | 4.99 % |
| MetroPCS | 1.09 % |
| Verizon Wireless | 3.04 % |
| Haddam VFD | 0.06 % |
| Site Total MPE %: | 13.70 % |

Table 4: All Carrier MPE Contributions

| | |
|--------------------------|----------------|
| T-MOBILE Sector A Total: | 3.63 % |
| T-MOBILE Sector B Total: | 3.63 % |
| T-MOBILE Sector C Total: | 3.63 % |
| Site Total: | 13.70 % |

Table 5: Site MPE Summary

Transcom Engineering, Inc.

Wireless Network Design and Deployment

FCC OET 65 specifies that for carriers utilizing directional antennas that the highest recorded sector value be used for composite site MPE values due to their greatly reduced emissions contributions in the directions of the adjacent sectors. *Table 6* below details a breakdown by frequency band and technology for the MPE power values for the maximum calculated T-MOBILE sector(s). For this site, all three sectors have the same configuration yielding the same results on all three sectors.

| T-MOBILE _ Frequency Band / Technology Max Power Values (Per Sector) | # Channels | Watts ERP (Per Channel) | Height (feet) | Total Power Density ($\mu\text{W}/\text{cm}^2$) | Frequency (MHz) | Allowable MPE ($\mu\text{W}/\text{cm}^2$) | Calculated % MPE |
|---|------------|-------------------------|---------------|---|-----------------|---|---------------------|
| T-Mobile 600 MHz LTE / 5G NR | 2 | 788.97 | 120 | 4.37 | 600 MHz | 400 | 1.09% |
| T-Mobile 700 MHz LTE | 2 | 432.54 | 120 | 2.39 | 700 MHz | 467 | 0.51% |
| T-Mobile 1900 MHz (PCS) LTE | 4 | 937.69 | 120 | 10.38 | 1900 MHz (PCS) | 1000 | 1.04% |
| T-Mobile 1900 MHz (PCS) GSM | 1 | 351.63 | 120 | 0.97 | 1900 MHz (PCS) | 1000 | 0.10% |
| T-Mobile 2100 MHz (AWS) LTE | 2 | 1,611.21 | 120 | 8.91 | 2100 MHz (AWS) | 1000 | 0.89% |
| | | | | | | | Total: 3.63% |

Table 6: T-MOBILE Maximum Sector MPE Power Values

Transcom Engineering, Inc.

Wireless Network Design and Deployment

Summary

All calculations performed for this analysis yielded results that were **within** the allowable limits for general population exposure to RF Emissions.

The anticipated maximum composite contributions from the T-MOBILE facility as well as the site composite emissions value with regards to compliance with FCC's allowable limits for general population exposure to RF Emissions are shown here:

| T-MOBILE Sector | Power Density Value (%) |
|--------------------------------------|-------------------------|
| Sector A: | 3.63 % |
| Sector B: | 3.63 % |
| Sector C: | 3.63 % |
| T-MOBILE Maximum Total (per sector): | 3.63 % |
| Site Total: | 13.70 % |
| Site Compliance Status: | COMPLIANT |

The anticipated composite MPE value for this site assuming all carriers present is **13.70 %** of the allowable FCC established general population limit sampled at the ground level. This is based upon values listed in the Connecticut Siting Council database for existing carrier emissions.

FCC guidelines state that if a site is found to be out of compliance (over allowable thresholds), that carriers over a 5% contribution to the composite value will require measures to bring the site into compliance. For this facility, the composite values calculated were well within the allowable 100% threshold standard per the federal government.



Scott Heffernan
RF Engineering Director
Transcom Engineering, Inc.
PO Box 1048
Sterling, MA 01564



T-MOBILE SITE NUMBER:CT11233A
T-MOBILE SITE NAME: HIGGANUM_1
SITE TYPE: MONOPOLE
TOWER HEIGHT: 115'-6"

BUSINESS UNIT #: 806367
SITE ADDRESS: MAPLE AVE WEST
HADDAM, CT 06441
COUNTY: MIDDLESEX
JURISDICTION: TOWN OF HADDAM

T-MOBILE L600 SITE CONFIGURATION: 67D94AR V2 Outdoor

SITE INFORMATION

| | |
|---------------------------|--|
| CROWN CASTLE USA INC. | |
| SITE NAME: | HRT 046 943209 |
| SITE ADDRESS: | MAPLE AVE WEST HADDAM, CT 06411 |
| COUNTY: | MIDDLESEX |
| MAP/PARCEL #: | HADD-000023-000001-000001 |
| AREA OF CONSTRUCTION: | EXISTING |
| LATITUDE: | 41° 29' 04.54" |
| LONGITUDE: | -72° 34' 20.81" |
| LAT/LONG TYPE: | NAD83 |
| GROUND ELEVATION: | 509 FT. |
| CURRENT ZONING: | NOT REQUIRED |
| JURISDICTION: | TOWN OF HADDAM |
| OCCUPANCY CLASSIFICATION: | U |
| TYPE OF CONSTRUCTION: | IIB |
| A.D.A. COMPLIANCE: | FACILITY IS UNMANNED AND NOT FOR HUMAN HABITATION |
| PROPERTY OWNER: | GLOBAL SIGNAL ACQUISITIONS IV LLC PO BOX 277455 ATLANTA, GA 30384-7455 |
| TOWER OWNER: | CROWN ATLANTIC COMPANY LLC 2000 CORPORATE DRIVE CANONSBURG, PA 15317 |
| CARRIER/APPLICANT: | T-MOBILE 35 GRIFFIN ROAD BLOOMFIELD, CT 06002 |
| CROWN CASTLE USA INC. | |
| APPLICATION ID: | 479816 |
| ELECTRIC PROVIDER: | CONNECTICUT LIGHT & POWER CO (800) 286-2000 |
| TELCO PROVIDER: | AT&T (866) 620-6900 |

DRAWING INDEX

A map showing the location of The Spirit of 76 House B&B. The property is located on Candlewood Hill Rd, just off Route 85. The map also shows the Higganum Reservoir State Park and several local businesses: Pizzeria De Vinci, Brewed Awakening, and AJ's Pizza. The map includes labels for Nod Hill Rd, Spencer Rd, Remond Hill Rd, Main Ave W, and Main Ave. A location marker is placed at the coordinates 41.484596, -72.572449.



APPROVALS

| <u>APPROVAL</u> | <u>SIGNATURE</u> | <u>DATE</u> |
|------------------------|------------------|-------------|
| PROPERTY OWNER OR REP. | _____ | _____ |
| LAND USE PLANNER | _____ | _____ |
| T-MOBILE | _____ | _____ |
| OPERATIONS | _____ | _____ |
| RF | _____ | _____ |
| NETWORK | _____ | _____ |
| BACKHAUL | _____ | _____ |
| CONSTRUCTION MANAGER | _____ | _____ |

THE PARTIES ABOVE HEREBY APPROVE AND ACCEPT THESE DOCUMENTS AND AUTHORIZE THE CONTRACTOR TO PROCEED WITH THE CONSTRUCTION DESCRIBED HEREIN. ALL CONSTRUCTION DOCUMENTS ARE SUBJECT TO REVIEW BY THE LOCAL BUILDING DEPARTMENT AND ANY CHANGES AND MODIFICATIONS THEY MAY IMPOSE.

| APPLICABLE CODES/REFERENCE DOCUMENTS | |
|--|---|
| ALL WORK SHALL BE PERFORMED AND MATERIALS INSTALLED IN ACCORDANCE WITH THE CURRENT EDITIONS OF THE FOLLOWING CODES AS ADOPTED BY THE LOCAL GOVERNING AUTHORITIES. NOTHING IN THESE PLANS IS TO BE CONSTRUED TO PERMIT WORK NOT CONFORMING TO THESE CODES: | |
| <u>CODE TYPE</u> | <u>CODE</u> |
| BUILDING | 2018 CT STATE BUILDING CODE/2015 IBC W/ CT AMENDMENTS |
| MECHANICAL | 2018 CT STATE BUILDING CODE/2015 IMC W/ CT AMENDMENTS |
| ELECTRICAL | 2018 CT STATE BUILDING CODE/2017 NEC W/ CT AMENDMENTS |
| REFERENCE DOCUMENTS: | |
| STRUCTURAL ANALYSIS: CROWN CASTLE DATED NOVEMBER 30, 2020 | |
| MOUNT ANALYSIS: PAUL J FORD AND COMPANY DATED NOVEMBER 17, 2020 | |
| <div style="border: 1px solid black; padding: 10px; text-align: center;"> <u>INSTALLER NOTE:</u> NO PROPOSED LOADING TO BE ADDED UNTIL MOUNT MODIFICATIONS ARE INSTALLED PER MOUNT ANALYSIS DESIGNED BY PAUL J FORD AND COMPANY DATED NOVEMBER 17, 2020. </div> | |

PROJECT DESCRIPTION



SITE WORK GENERAL NOTES:

1. THE SUBCONTRACTOR SHALL CONTACT UTILITY LOCATING SERVICES PRIOR TO THE START OF CONSTRUCTION.
2. ALL EXISTING ACTIVE SEWER, WATER, GAS, ELECTRIC AND OTHER UTILITIES WHERE ENCOUNTERED IN THE WORK, SHALL BE PROTECTED AT ALL TIMES AND WHERE REQUIRED FOR THE PROPER EXECUTION OF THE WORK, SHALL BE RELOCATED AS DIRECTED BY CONTRACTOR. EXTREME CAUTION SHOULD BE USED BY THE SUBCONTRACTOR WHEN EXCAVATING OR DRILLING PIERS AROUND OR NEAR UTILITIES. SUBCONTRACTOR SHALL PROVIDE SAFETY TRAINING FOR THE WORKING CREW. THIS WILL INCLUDE BUT NOT BE LIMITED TO A) FALL PROTECTION B) CONFINED SPACE C) ELECTRICAL SAFETY D) TRENCHING AND EXCAVATION.
3. ALL SITE WORK TO COMPLY WITH QAS-STD-10068 "INSTALLATION STANDARDS FOR CONSTRUCTION ACTIVITIES ON CROWN CASTLE USA INC. TOWER SITE" AND LATEST VERSION OF TIA 109 "STANDARD FOR INSTALLATION, ALTERATION, AND MAINTENANCE OF ANTENNA SUPPORTING STRUCTURES AND ANTENNAS."
4. ALL SITE WORK SHALL BE AS INDICATED ON THE STAMPED CONSTRUCTION DRAWINGS AND PROJECT SPECIFICATIONS.
5. IF NECESSARY, RUBBISH, STUMPS, DEBRIS, STICKS, STONES AND OTHER REFUSE SHALL BE REMOVED FROM THE SITE AND DISPOSED OF LEGALLY.
6. ALL EXISTING INACTIVE SEWER, WATER, GAS, ELECTRIC AND OTHER UTILITIES, WHICH INTERFERE WITH THE EXECUTION OF THE WORK, SHALL BE REMOVED AND/OR CAPPED, PLUGGED OR OTHERWISE DISCONTINUED AT POINTS WHICH WILL NOT INTERFERE WITH THE EXECUTION OF THE WORK, SUBJECT TO THE APPROVAL OF CONTRACTOR, OWNER AND/OR LOCAL UTILITIES.
7. THE SUBCONTRACTOR SHALL PROVIDE SITE SIGNAGE IN ACCORDANCE WITH THE TECHNICAL SPECIFICATION FOR SITE SIGNAGE.
8. THE SITE SHALL BE GRADED TO CAUSE SURFACE WATER TO FLOW AWAY FROM THE BTS EQUIPMENT AND TOWER AREAS.
9. NO FILL OR EMBANKMENT MATERIAL SHALL BE PLACED ON FROZEN GROUND. FROZEN MATERIALS, SNOW OR ICE SHALL NOT BE PLACED IN ANY FILL OR EMBANKMENT.
10. THE SUB GRADE SHALL BE COMPAKTED AND BROUGHT TO A SMOOTH UNIFORM GRADE PRIOR TO FINISHED SURFACE APPLICATION.
11. THE AREAS OF THE OWNERS PROPERTY DISTURBED BY THE WORK AND NOT COVERED BY THE TOWER, EQUIPMENT OR DRIVEWAY, SHALL BE GRADED TO A UNIFORM SLOPE, AND STABILIZED TO PREVENT EROSION AS SPECIFIED ON THE PROJECT SPECIFICATIONS.
12. SUBCONTRACTOR SHALL MINIMIZE DISTURBANCE TO EXISTING SITE DURING CONSTRUCTION. EROSION CONTROL MEASURES, IF REQUIRED DURING CONSTRUCTION, SHALL BE IN CONFORMANCE WITH THE LOCAL GUIDELINES FOR EROSION AND SEDIMENT CONTROL.
13. NOTICE TO PROCEED- NO WORK TO COMMENCE PRIOR TO COMPANY'S WRITTEN NOTICE TO PROCEED AND THE ISSUANCE OF A PURCHASE ORDER.
14. ALL CONSTRUCTION MEANS AND METHODS; INCLUDING BUT NOT LIMITED TO, ERECTION PLANS, RIGGING PLANS, CLIMBING PLANS, AND RESCUE PLANS SHALL BE THE RESPONSIBILITY OF THE GENERAL CONTRACTOR FOR THE EXECUTION OF THE WORK CONTAINED HEREIN AND SHALL MEET ANSI/ASSE A10.48 (LATEST EDITION); FEDERAL, STATE, AND LOCAL REGULATIONS; AND ANY APPLICABLE INDUSTRY CONSENSUS STANDARDS RELATED TO THE CONSTRUCTION ACTIVITIES BEING PERFORMED. ALL RIGGING PLANS SHALL ADHERE TO ANSI/ASSE A10.48 (LATEST EDITION) AND CROWN CASTLE USA INC. STANDARD STANDARD CED-STD-10253 INCLUDING THE REQUIRED INVOLVEMENT OF A QUALIFIED ENGINEER FOR CLASS IV CONSTRUCTION TO CERTIFY THE SUPPORTING STRUCTURE(S) IN ACCORDANCE WITH THE ANSI/TIA-322 (LATEST EDITION).

STRUCTURAL STEEL NOTES:

1. ALL STEEL WORK SHALL BE PAINTED IN ACCORDANCE WITH THE PROJECT SPECIFICATIONS AND IN ACCORDANCE WITH ASTM A36 UNLESS OTHERWISE NOTED.
2. BOLTED CONNECTIONS SHALL BE ASTM A325 BEARING TYPE (3/4") CONNECTIONS AND SHALL HAVE MINIMUM OF TWO BOLTS UNLESS NOTED OTHERWISE.
3. NON-STRUCTURAL CONNECTIONS FOR STEEL GRATING MAY USE 5/8" ASTM A307 BOLTS UNLESS NOTED OTHERWISE.
4. INSTALLATION OF CONCRETE EXPANSION/WEDGE ANCHOR, SHALL BE PER MANUFACTURER'S RECOMMENDED PROCEDURE. THE ANCHOR BOLT, DOWEL OR ROD SHALL CONFORM TO MANUFACTURER'S RECOMMENDATION FOR EMBEDMENT DEPTH OR AS SHOWN ON THE DRAWINGS. NO REBAR SHALL BE CUT WITHOUT PRIOR CONTRACTOR APPROVAL WHEN DRILLING HOLES IN CONCRETE. SPECIAL INSPECTIONS, REQUIRED BY GOVERNING CODES, SHALL BE PERFORMED IN ORDER TO MAINTAIN MANUFACTURER'S MAXIMUM ALLOWABLE LOADS.

CONCRETE AND REINFORCING STEEL NOTES:

1. ALL CONCRETE WORK SHALL BE IN ACCORDANCE WITH THE ACI 301, ACI 318, ACI 336, ASTM A184, ASTM A185 AND THE DESIGN AND CONSTRUCTION SPECIFICATION FOR CAST-IN-PLACE CONCRETE.
2. ALL CONCRETE SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH OF 3000 PSI AT 28 DAYS, UNLESS NOTED OTHERWISE. SLAB FOUNDATION DESIGN ASSUMING ALLOWABLE SOIL BEARING PRESSURE OF 2000 PSF.
3. REINFORCING STEEL SHALL CONFORM TO ASTM A615, GRADE 60, DEFORMED UNLESS NOTED OTHERWISE. WELDED WIRE FABRIC SHALL CONFORM TO ASTM A185 WELDED STEEL WIRE FABRIC UNLESS NOTED OTHERWISE. SPLICES SHALL BE CLASS "B" AND ALL HOOKS SHALL BE STANDARD, UNO.
4. THE FOLLOWING MINIMUM CONCRETE COVER SHALL BE PROVIDED FOR REINFORCING STEEL UNLESS SHOWN OTHERWISE ON DRAWINGS:

CONCRETE CAST AGAINST EARTH.....3 IN.
CONCRETE EXPOSED TO EARTH OR WEATHER:
#6 AND LARGER.....2 IN.
#5 AND SMALLER & WWF.....1 1/2 IN.
CONCRETE NOT EXPOSED TO EARTH OR WEATHER OR NOT CAST AGAINST THE GROUND:
SLAB AND WALLS.....3/4 IN.
BEAMS AND COLUMNS.....1 1/2 IN.
5. A CHAMFER 3/4" SHALL BE PROVIDED AT ALL EXPOSED EDGES OF CONCRETE, UNLESS NOTED OTHERWISE. IN ACCORDANCE WITH ACI 301 SECTION 4.2.4.

MASONRY NOTES:

1. HOLLOW CONCRETE MASONRY UNITS SHALL MEET A.S.T.M. SPECIFICATION C90, GRADE N, TYPE 1. THE SPECIFIED DESIGN COMPRESSIVE STRENGTH OF CONCRETE MASONRY ("f'm") SHALL BE 1500 PSI.
2. MORTAR SHALL MEET THE PROPERTY SPECIFICATION OF A.S.T.M. C270 TYP. "S" MORTAR AND SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH OF 2000 PSI.
3. GROUT SHALL MEET A.S.T.M. SPECIFICATION C475 AND HAVE A MINIMUM 28 DAY COMPRESSIVE STRENGTH OF 2000 PSI.
4. CONCRETE MASONRY SHALL BE LAID IN RUNNING (COMMON) BOND.
5. WALL SHALL RECEIVE TEMPORARY BRACING. TEMPORARY BRACING SHALL NOT BE REMOVED UNTIL GROUT IS FULLY CURED.

GENERAL NOTES:

1. FOR THE PURPOSE OF CONSTRUCTION DRAWING, THE FOLLOWING DEFINITIONS SHALL APPLY:

CONTRACTOR-
SUBCONTRACTOR- GENERAL CONTRACTOR (CONSTRUCTION)
CARRIER- T-MOBILE
TOWER OWNER- CROWN CASTLE USA INC.
OEM- ORIGINAL EQUIPMENT MANUFACTURER
2. PRIOR TO THE SUBMISSION OF BIDS, THE BIDDING SUBCONTRACTOR SHALL VISIT THE CELL SITE TO FAMILIARIZE WITH THE EXISTING CONDITIONS AND TO CONFIRM THAT THE WORK CAN BE ACCOMPLISHED AS SHOWN ON THE CONSTRUCTION DRAWINGS. ANY DISCREPANCY FOUND SHALL BE BROUGHT TO THE ATTENTION OF CONTRACTOR AND CROWN CASTLE USA INC.
3. ALL MATERIALS FURNISHED AND INSTALLED SHALL BE IN STRICT ACCORDANCE WITH ALL APPLICABLE CODES, REGULATIONS AND ORDINANCES. SUBCONTRACTOR SHALL ISSUE ALL APPROPRIATE NOTICES AND COMPLY WITH ALL LAWS, ORDINANCES, RULES, REGULATIONS AND LAWFUL ORDERS OF ANY PUBLIC AUTHORITY REGARDING THE PERFORMANCE OF THE WORK. ALL WORK CARRIED OUT SHALL COMPLY WITH ALL APPLICABLE MUNICIPAL AND UTILITY COMPANY SPECIFICATIONS AND LOCAL JURISDICTIONAL CODES, ORDINANCES AND APPLICABLE REGULATIONS.
4. DRAWINGS PROVIDED HERE ARE NOT TO SCALE AND ARE INTENDED TO SHOW OUTLINE ONLY.
5. UNLESS NOTED OTHERWISE, THE WORK SHALL INCLUDE FURNISHING MATERIALS, EQUIPMENT, APPURTENANCES AND LABOR NECESSARY TO COMPLETE ALL INSTALLATIONS AS INDICATED ON THE DRAWINGS.
6. "KITTING LIST" SUPPLIED WITH THE BID PACKAGE IDENTIFIES ITEMS THAT WILL BE SUPPLIED BY CONTRACTOR. ITEMS NOT INCLUDED IN THE BILL OF MATERIALS AND KITTING LIST SHALL BE SUPPLIED BY THE SUBCONTRACTOR.
7. THE SUBCONTRACTOR SHALL INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS UNLESS SPECIFICALLY STATED OTHERWISE.
8. IF THE SPECIFIED EQUIPMENT CAN NOT BE INSTALLED AS SHOWN ON THESE DRAWINGS, THE SUBCONTRACTOR SHALL PROPOSE AN ALTERNATIVE INSTALLATION FOR APPROVAL BY THE CONTRACTOR AND CROWN CASTLE USA INC. PRIOR TO PROCEEDING WITH ANY SUCH CHANGE OF INSTALLATION.
9. SUBCONTRACTOR SHALL DETERMINE ACTUAL ROUTING OF CONDUIT, POWER AND T1 CABLES, GROUNDING CABLES AS SHOWN ON THE POWER, GROUNDING AND TELCO PLAN DRAWINGS.
10. THE SUBCONTRACTOR SHALL PROTECT EXISTING IMPROVEMENTS, PAVEMENTS, CURBS, LANDSCAPING AND STRUCTURES. ANY DAMAGED PART SHALL BE REPAIRED AT SUBCONTRACTOR'S EXPENSE TO THE SATISFACTION OF OWNER.
11. SUBCONTRACTOR SHALL LEGALLY AND PROPERLY DISPOSE OF ALL SCRAP MATERIALS SUCH AS COAXIAL CABLES AND OTHER ITEMS REMOVED FROM THE EXISTING FACILITY. ANTENNAS REMOVED SHALL BE RETURNED TO THE OWNER'S DESIGNATED LOCATION.
12. SUBCONTRACTOR SHALL LEAVE PREMISES IN CLEAN CONDITION. TRASH AND DEBRIS SHOULD BE REMOVED FROM SITE ON A DAILY BASIS.

ABBREVIATIONS AND SYMBOLS:

ABBREVIATIONS:

| | |
|--------|--------------------------------|
| AGL | ABOVE GRADE LEVEL |
| BTS | BASE TRANSCEIVER STATION |
| (C) | EXISTING |
| MIN. | MINIMUM |
| REF. | REFERENCE |
| RF | RADIO FREQUENCY |
| T.B.D. | TO BE DETERMINED |
| T.B.R. | TO BE RESOLVED |
| TYP. | TYPICAL |
| REQ. | REQUIRED |
| EGR | EQUIPMENT GROUND RING |
| AWG | AMERICAN WIRE GAUGE |
| MGB | MASTER GROUND BAR |
| EG | EQUIPMENT GROUND |
| BCW | BARE COPPER WIRE |
| SIAD | SMART INTEGRATED ACCESS DEVICE |
| GEN | GENERATOR |
| IGR | INTERIOR GROUND RING (HALO) |
| RBS | RADIO BASE STATION |

SYMBOLS:

| | |
|--|---|
| | SOLID GROUND BUS BAR |
| | SOLID NEUTRAL BUS BAR |
| | SUPPLEMENTAL GROUND CONDUCTOR |
| | 2-POLE THERMAL-MAGNETIC CIRCUIT BREAKER |
| | SINGLE-POLE THERMAL-MAGNETIC CIRCUIT BREAKER |
| | CHEMICAL GROUND ROD |
| | TEST WELL |
| | DISCONNECT SWITCH |
| | METER |
| | EXOTHERMIC WELD (CADWELD) (UNLESS OTHERWISE NOTED) |
| | MECHANICAL CONNECTION |
| | GROUNDING WIRE |

ELECTRICAL INSTALLATION NOTES:

1. ALL ELECTRICAL WORK SHALL BE PERFORMED IN ACCORDANCE WITH THE PROJECT SPECIFICATIONS, NEC AND ALL APPLICABLE FEDERAL, STATE, AND LOCAL CODES/ORDINANCES.
2. CONDUIT ROUTINGS ARE SCHEMATIC. SUBCONTRACTOR SHALL INSTALL CONDUITS SO THAT ACCESS TO EQUIPMENT IS NOT BLOCKED AND TRIP HAZARDS ARE ELIMINATED.
3. WIRING, RACEWAY AND SUPPORT METHODS AND MATERIALS SHALL COMPLY WITH THE REQUIREMENTS OF THE NEC. HILTI EPOXY ANCHORS ARE REQUIRED BY CROWN CASTLE USA INC.
4. ALL CIRCUITS SHALL BE SEGREGATED AND MAINTAIN MINIMUM CABLE SEPARATION AS REQUIRED BY THE NEC.
5. CABLES SHALL NOT BE ROUTED THROUGH LADDER-STYLE CABLE TRAY RUNGS.
6. EACH END OF EVERY POWER, POWER PHASE CONDUCTOR (I.E., HOTS), GROUNDING AND T1 CONDUCTOR AND CABLE SHALL BE LABELED WITH COLOR-CODED INSULATION OR ELECTRICAL TAPE (3M BRAND, 1/2" PLASTIC ELECTRICAL TAPE WITH UV PROTECTION, OR EQUAL). THE IDENTIFICATION METHOD SHALL CONFORM WITH NEC AND OSHA.
7. ALL ELECTRICAL COMPONENTS SHALL BE CLEARLY LABELED WITH PLASTIC TAPE PER COLOR SCHEDULE. ALL EQUIPMENT SHALL BE LABELED WITH THEIR VOLTAGE RATING, PHASE CONFIGURATION, WIRE CONFIGURATION, POWER OR AMPACITY RATING AND BRANCH CIRCUIT ID NUMBERS (I.E. PANEL BOARD AND CIRCUIT ID'S).
8. PANEL BOARDS (ID NUMBERS) AND INTERNAL CIRCUIT BREAKERS (CIRCUIT ID NUMBERS) SHALL BE CLEARLY LABELED WITH PLASTIC LABELS.
9. ALL TIE WRAPS SHALL BE CUT FLUSH WITH APPROVED CUTTING TOOL TO REMOVE SHARP EDGES.
10. POWER, CONTROL AND EQUIPMENT GROUND WIRING IN TUBING OR CONDUIT SHALL BE SINGLE CONDUCTOR (#14 AWG OR LARGER), 600 V, OIL RESISTANT THHN OR THWN-2, CLASS B STRANDED COPPER CABLE RATED FOR 90° C (WET & DRY) OPERATION LISTED OR LABELED FOR THE LOCATION AND RACEWAY SYSTEM USED UNLESS OTHERWISE SPECIFIED.
11. SUPPLEMENTAL EQUIPMENT GROUND WIRING LOCATED INDOORS SHALL BE SINGLE CONDUCTOR (#6 AWG OR LARGER), 600V, OIL RESISTANT THHN OR THWN-2 GREEN INSULATION CLASS B STRANDED COPPER CABLE RATED FOR 90° C (WET AND DRY) OPERATION LISTED OR LABELED FOR THE LOCATION AND RACEWAY SYSTEM USED UNLESS OTHERWISE SPECIFIED.
12. POWER AND CONTROL WIRING, NOT IN TUBING OR CONDUIT, SHALL BE MULTI-CONDUCTOR, TYPE TC CABLE (#14 AWG OR LARGER), 600 V, OIL RESISTANT THHN OR THWN-2, CLASS B STRANDED COPPER CABLE RATED FOR 90° C (WET AND DRY) OPERATION WITH OUTER JACKET LISTED OR LABELED FOR THE LOCATION USED UNLESS OTHERWISE SPECIFIED.
13. ALL POWER AND GROUNDING CONNECTIONS SHALL BE CRIMP-STYLE, COMPRESSION WIRE LUGS AND WIRE NUTS BY THOMAS AND BETTS (OR EQUAL). LUGS AND WIRE NUTS SHALL BE RATED FOR OPERATION AT NO LESS THAN 75° C (90° C IF AVAILABLE).
14. RACEWAY AND CABLE TRAY SHALL BE LISTED OR LABELED FOR ELECTRICAL USE IN ACCORDANCE WITH NEMA, UL, ANSI/IEEE AND NEC.
15. ELECTRICAL METALLIC TUBING (EMT) OR RIGID NONMETALLIC CONDUIT (I.E. RIGID PVC SCHEDULE 40 OR RIGID PVC SCHEDULE 80 FOR LOCATIONS SUBJECT TO PHYSICAL DAMAGE) SHALL BE USED FOR EXPOSED INDOOR LOCATIONS.
16. ELECTRICAL METALLIC TUBING (EMT), ELECTRICAL NONMETALLIC TUBING (ENT) OR RIGID NONMETALLIC CONDUIT (RIGID PVC, SCHEDULE 40) SHALL BE USED FOR CONCEALED INDOOR LOCATIONS.
17. SCHEDULE 40 PVC UNDERGROUND ON STRAIGHTS AND SCHEDULE 80 PVC FOR ALL ELBOWS/90s AND ALL APPROVED ABOVE GRADE PVC CONDUIT.
18. LIQUID-TIGHT FLEXIBLE METALLIC CONDUIT (LIQUID-TITE FLEX) SHALL BE USED INDOORS AND OUTDOORS, WHERE VIBRATION OCCURS OR FLEXIBILITY IS NEEDED.
19. CONDUIT AND TUBING FITTINGS SHALL BE THREADED OR COMPRESSION-TYPE AND APPROVED FOR THE LOCATION USED. SET SCREW FITTINGS ARE NOT ACCEPTABLE.
20. CABINETS, BOXES AND WIRE WAYS SHALL BE LABELED FOR ELECTRICAL USE IN ACCORDANCE WITH NEMA, UL, ANSI/IEEE AND NEC.
21. WIREWAYS SHALL BE EPOXY-COATED (GRAY) AND INCLUDE A HINGED COVER, DESIGNED TO SWING OPEN DOWNWARDS; SHALL BE PANDUIT TYPE E (OR EQUAL); AND RATED NEMA 1 (OR BETTER).
22. CONDUITS SHALL BE FASTENED SECURELY IN PLACE WITH APPROVED NON-PERFORATED STRAPS AND HANGERS. EXPLOSIVE DEVICES FOR ATTACHING HANGERS TO STRUCTURE WILL NOT BE PERMITTED. CLOSELY FOLLOW THE LINES OF THE STRUCTURE, MAINTAIN CLOSE PROXIMITY TO THE STRUCTURE AND KEEP CONDUITS IN TIGHT ENVELOPES. CHANGES IN DIRECTION TO ROUTE AROUND OBSTACLES SHALL BE MADE WITH CONDUIT OUTLET BODIES. CONDUIT SHALL BE INSTALLED IN A NEAT AND WORKMANLIKE MANNER, PARALLEL AND PERPENDICULAR TO STRUCTURE WALL AND CEILING LINES. ALL CONDUIT SHALL BE FISHED TO CLEAR OBSTRUCTIONS. ENDS OF CONDUITS SHALL BE TEMPORARILY CAPPED FLUSH TO FINISH GRADE TO PREVENT CONCRETE, PLASTER OR DIRT FROM ENTERING. CONDUITS SHALL BE RIGIDLY CLAMPED TO BOXES BY GALVANIZED MALLEABLE IRON BUSHIN ON INSIDE AND GALVANIZED MALLEABLE IRON LOCKNUT ON OUTSIDE AND INSIDE.
23. EQUIPMENT CABINETS, TERMINAL BOXES, JUNCTION BOXES AND PULL BOXES SHALL BE GALVANIZED OR EPOXY-COATED SHEET STEEL; SHALL MEET OR EXCEED UL 50 AND RATED NEMA 1 (OR BETTER) INDOORS OR NEMA 3R (OR BETTER) OUTDOORS.
24. METAL RECEPTACLE, SWITCH AND DEVICE BOXES SHALL BE GALVANIZED, EPOXY-COATED OR NON-CORRODING; SHALL MEET OR EXCEED UL 514A AND NEMA OS-1; AND RATED NEMA 1 (OR BETTER) INDOORS OR WEATHER PROTECTED (WP OR BETTER) OUTDOORS.
25. NONMETALLIC RECEPTACLE, SWITCH AND DEVICE BOXES SHALL MEET OR EXCEED NEMA OS-2; AND RATED NEMA 1 (OR BETTER) INDOORS OR WEATHER PROTECTED (WP OR BETTER) OUTDOORS.
26. THE SUBCONTRACTOR SHALL NOTIFY AND OBTAIN NECESSARY AUTHORIZATION FROM THE CONTRACTOR BEFORE COMMENCING WORK ON THE AC POWER DISTRIBUTION PANELS.
27. THE SUBCONTRACTOR SHALL PROVIDE NECESSARY TAGGING ON THE BREAKERS, CABLES AND DISTRIBUTION PANELS IN ACCORDANCE WITH THE APPLICABLE CODES AND STANDARDS TO SAFEGUARD LIFE AND PROPERTY.
28. INSTALL PLASTIC LABEL ON THE METER CENTER TO SHOW "T-MOBILE".
29. ALL CONDUITS THAT ARE INSTALLED ARE TO HAVE A METERED MULE TAPE PULL CORD INSTALLED.

GREENFIELD GROUNDING NOTES:

1. ALL GROUND ELECTRODE SYSTEMS (INCLUDING TELECOMMUNICATION, RADIO, LIGHTNING PROTECTION AND AC POWER GES') SHALL BE BONDED TOGETHER AT OR BELOW GRADE, BY TWO OR MORE COPPER BONDING CONDUCTORS IN ACCORDANCE WITH THE NEC.
2. THE SUBCONTRACTOR SHALL PERFORM IEEE FALL-OF-POTENTIAL RESISTANCE TO EARTH TESTING (PER IEEE 1100 AND 81) FOR GROUND ELECTRODE SYSTEMS. THE SUBCONTRACTOR SHALL FURNISH AND INSTALL SUPPLEMENTAL GROUND ELECTRODES AS NEEDED TO ACHIEVE A TEST RESULT OF 5 OHMS OR LESS.
3. THE SUBCONTRACTOR IS RESPONSIBLE FOR PROPERLY SEQUENCING GROUNDING AND UNDERGROUND CONDUIT INSTALLATION AS TO PREVENT ANY LOSS OF CONTINUITY IN THE GROUNDING SYSTEM OR DAMAGE TO THE CONDUIT AND PROVIDE TESTING RESULTS.
4. METAL CONDUIT AND TRAY SHALL BE GROUNDED AND MADE ELECTRICALLY CONTINUOUS WITH LISTED BONDING FITTINGS OR BY BONDING ACROSS THE DISCONTINUITY WITH #6 AWG COPPER WIRE UL APPROVED GROUNDING TYPE CONDUIT CLAMPS.
5. METAL RACEWAY SHALL NOT BE USED AS THE NEC REQUIRED EQUIPMENT GROUND CONDUCTOR. STRANDED COPPER CONDUCTORS WITH GREEN INSULATION, SIZED IN ACCORDANCE WITH THE NEC, SHALL BE FURNISHED AND INSTALLED WITH THE POWER CIRCUITS TO BTS EQUIPMENT.
6. EACH CABINET FRAME SHALL BE DIRECTLY CONNECTED TO THE MASTER GROUND BAR WITH GREEN INSULATED SUPPLEMENTAL EQUIPMENT GROUND WIRES, 6 AWG STRANDED COPPER OR LARGER FOR INDOOR BTS; #2 AWG SOLID TINNED COPPER FOR OUTDOOR BTS.
7. CONNECTIONS TO THE GROUND BUS SHALL NOT BE DOUBLED UP OR STACKED BACK TO BACK CONNECTIONS ON OPPOSITE SIDE OF THE GROUND BUS ARE PERMITTED.
8. ALL EXTERIOR GROUND CONDUCTORS BETWEEN EQUIPMENT/GROUND BARS AND THE GROUND RING SHALL BE #2 AWG SOLID TINNED COPPER UNLESS OTHERWISE INDICATED.
9. ALUMINUM CONDUCTOR OR COPPER CLAD STEEL CONDUCTOR SHALL NOT BE USED FOR GROUNDING CONNECTIONS.
10. USE OF 90° BENDS IN THE PROTECTION GROUNDING CONDUCTORS SHALL BE AVOIDED WHEN 45° BENDS CAN BE ADEQUATELY SUPPORTED.
11. EXOTHERMIC WELDS SHALL BE USED FOR ALL GROUNDING CONNECTIONS BELOW GRADE.
12. ALL GROUND CONNECTIONS ABOVE GRADE (INTERIOR AND EXTERIOR) SHALL BE FORMED USING HIGH PRESS CRIMPS.
13. COMPRESSION GROUND CONNECTIONS MAY BE REPLACED BY EXOTHERMIC WELD CONNECTIONS.
14. ICE BRIDGE BONDING CONDUCTORS SHALL BE EXOTHERMICALLY BONDED OR BOLTED TO THE BRIDGE AND THE TOWER GROUND BAR.
15. APPROVED ANTI-OXIDANT COATINGS (I.E. CONDUCTIVE GEL OR PASTE) SHALL BE USED ON ALL COMPRESSION AND BOLTED GROUND CONNECTIONS.
16. ALL EXTERIOR GROUND CONNECTIONS SHALL BE COATED WITH A CORROSION RESISTANT MATERIAL.
17. MISCELLANEOUS ELECTRICAL AND NON-ELECTRICAL METAL BOXES, FRAMES AND SUPPORTS SHALL BE BONDED TO THE GROUND RING, IN ACCORDANCE WITH THE NEC.
18. BOND ALL METALLIC OBJECTS WITHIN 6 FT. OF MAIN GROUND WIRES WITH 1-#2 AWG TIN-PLATED COPPER GROUND CONDUCTOR.
19. GROUND CONDUCTORS USED IN THE FACILITY GROUND AND LIGHTNING PROTECTION SYSTEMS SHALL NOT BE ROUTED THROUGH METALLIC OBJECTS THAT FORM A RING AROUND THE CONDUCTOR, SUCH AS METALLIC CONDUITS, METAL SUPPORT CLIPS OR SLEEVES THROUGH WALLS OR FLOORS, WHEN IT IS REQUIRED TO BE HOUSED IN CONDUIT TO MEET CODE REQUIREMENTS OR LOCAL CONDITIONS, NON-METALLIC MATERIAL SUCH AS PVC PLASTIC CONDUIT SHALL BE USED, WHERE USE OF METAL CONDUIT IS UNAVOIDABLE (E.G., NONMETALLIC CONDUIT PROHIBITED BY LOCAL CODE) THE GROUND CONDUCTOR SHALL BE BONDED TO EACH END OF THE METAL CONDUIT.
20. ALL GROUNDS THAT TRANSITION FROM BELOW GRADE TO ABOVE GRADE MUST BE #2 TINNED SOLID IN 3/4" LIQUID TIGHT CONDUIT FROM 24" BELOW GRADE TO WITHIN 3" TO 6" OF CAD-WELD TERMINATION POINT. THE EXPOSED END OF THE LIQUID TIGHT CONDUIT MUST BE SEALED WITH SILICONE CAULK. (ADD TRANSITIONING GROUND STANDARD DETAIL AS WELL).



T-Mobile

35 GRIFFIN ROAD
BLOOMFIELD, CT 06002

CROWN CASTLE

3 CORPORATE PARK DRIVE, SUITE 101
CLIFTON PARK, NY 12065

T-MOBILE SITE NUMBER:
CT11233A


BU #: 806367
HRT 046 943209

MAPLE AVE WEST
HADDAM, CT 06441

EXISTING 115'-6" MONOPOLE

ISSUED FOR:


| REV | DATE | DRWN | DESCRIPTION | DES./QA |
|-----|----------|------|--------------------|---------|
| 0 | 08/13/19 | JAS | CONSTRUCTION | JL |
| 1 | 12/14/20 | DMW | REVISED PER CLIENT | MCK |
| 2 | 01/26/21 | DMW | REVISED PER CLIENT | MCK |
| 3 | 02/26/21 | DMW | REVISED PER CLIENT | MCK |
| 4 | 03/18/21 | DMW | REVISED PER CLIENT | MCK |



03/18/21
Exp. 01/31/22


IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

SHEET NUMBER: **C-1** REVISION: **4**



1 SITE PLAN

SCALE: 4' 2' 0' 4' 3/16"=1'-0" (FULL SIZE)
3/32"=1'-0" (11x17)



2 ENLARGED SITE PLAN

SCALE: 1' 6' 0' 1' 1"=1'-0" (FULL SIZE)
1/2"=1'-0" (11x17)



4

T-Mobile

35 GRIFFIN ROAD
BLOOMFIELD, CT 06002

CROWN CASTLE


3 CORPORATE PARK DRIVE, SUITE 101
CLIFTON PARK, NY 12065

T-MOBILE SITE NUMBER:
CT11233A


BU #: 806367
HRT 046 943209

MAPLE AVE WEST
HADDAM, CT 06441


EXISTING 115'-6" MONOPOLE



1 FINAL ELEVATION
SCALE: NOT TO SCALE



2 EXISTING ANTENNA LAYOUT
SCALE: NOT TO SCALE



3 FINAL ANTENNA LAYOUT
SCALE: NOT TO SCALE

ISSUED FOR:

| REV | DATE | DRWN | DESCRIPTION | DES./QA |
|-----|----------|------|--------------------|---------|
| 0 | 08/13/19 | JAS | CONSTRUCTION | JL |
| 1 | 12/14/20 | DMW | REVISED PER CLIENT | MCK |
| 2 | 01/26/21 | DMW | REVISED PER CLIENT | MCK |
| 3 | 02/26/21 | DMW | REVISED PER CLIENT | MCK |
| 4 | 03/18/21 | DMW | REVISED PER CLIENT | MCK |



03/18/21
Exp. 01/31/22

IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

SHEET NUMBER: **C-2** REVISION: **4**

T-Mobile

35 GRIFFIN ROAD
BLOOMFIELD, CT 06002

CROWN CASTLE

3 CORPORATE PARK DRIVE, SUITE 101
CLIFTON PARK, NY 12065

T-MOBILE SITE NUMBER:
CT11233A

BU #: 806367
HRT 046 943209

MAPLE AVE WEST
HADDAM, CT 06441

EXISTING 115'-6" MONOPOLE

1 ANTENNA AND CABLE SCHEDULE


SCALE: NOT TO SCALE

INSTALLER NOTES:

1. COMPLY WITH MANUFACTURERS INSTRUCTIONS TO ENSURE THAT ALL RRHs RECEIVE ELECTRICAL POWER WITHIN 24 HOURS OF BEING REMOVED FROM THE MANUFACTURER'S PACKAGING.
2. DO NOT OPEN RRH PACKAGES IN THE RAIN.
3. ALL PIPES, BRACKETS, AND MISCELLANEOUS HARDWARE TO BE GALVANIZED UNLESS NOTED OTHERWISE.

NOTE:

ANTENNA NOT SHOWN FOR CLARITY




2 ANTENNA WITH RRH MOUNTING DETAIL

SCALE: NOT TO SCALE

ISSUED FOR:

| REV | DATE | DRWN | DESCRIPTION | DES./QA |
|-----|----------|------|--------------------|---------|
| 0 | 08/13/19 | JAS | CONSTRUCTION | JL |
| 1 | 12/14/20 | DMW | REVISED PER CLIENT | MCK |
| 2 | 01/26/21 | DMW | REVISED PER CLIENT | MCK |
| 3 | 02/26/21 | DMW | REVISED PER CLIENT | MCK |
| 4 | 03/18/21 | DMW | REVISED PER CLIENT | MCK |



03/18/21
Exp. 01/31/22

IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

SHEET NUMBER: **C-3** **REVISION:** **4**

T-Mobile

35 GRIFFIN ROAD
BLOOMFIELD, CT 06002

CROWN CASTLE


3 CORPORATE PARK DRIVE, SUITE 101
CLIFTON PARK, NY 12065

T-MOBILE SITE NUMBER:
CT11233A

BU #: **806367**
HRT 046 943209


MAPLE AVE WEST
HADDAM, CT 06441

EXISTING 115'-6" MONOPOLE




RFS/CELWAVE - APXVAA24_43-U-NA20
WEIGHT (WITHOUT MOUNTING HARDWARE): 101.4 LBS
SIZE (HxWxD): 96.0x24.0x8.5 IN.

1 RFS/CELWAVE - APXVAA24_43-U-NA20
SCALE: NOT TO SCALE



ERICSSON - RADIO 4449 B12/B71
WEIGHT: 70.0 LBS
SIZE (HxWxD): 18.0x13.2x9.4 IN.

2 ERICSSON - RADIO 4449 B12/B71
SCALE: NOT TO SCALE



ERICSSON - KRY 112 489/2
WEIGHT: 15.4 LBS
SIZE (HxWxD): 11.0x6.1x3.9 IN.

3 ERICSSON - KRY 112 489/2
SCALE: NOT TO SCALE

ISSUED FOR:

| REV | DATE | DRWN | DESCRIPTION | DES./QA |
|-----|----------|------|--------------------|---------|
| 0 | 08/13/19 | JAS | CONSTRUCTION | JL |
| 1 | 12/14/20 | DMW | REVISED PER CLIENT | MCK |
| 2 | 01/26/21 | DMW | REVISED PER CLIENT | MCK |
| 3 | 02/26/21 | DMW | REVISED PER CLIENT | MCK |
| 4 | 03/18/21 | DMW | REVISED PER CLIENT | MCK |



03/18/21
Exp. 01/31/22

IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

SHEET NUMBER: **C-4** REVISION: **4**

4 NOT USED
SCALE: NOT TO SCALE

5 NOT USED
SCALE: NOT TO SCALE

6 NOT USED
SCALE: NOT TO SCALE



35 GRIFFIN ROAD
BLOOMFIELD, CT 06002

35 GRIFFIN ROAD
BLOOMFIELD, CT 06002

The logo for Crown Castle, featuring a stylized 'CC' monogram to the left of the company name 'CROWN CASTLE' in a bold, sans-serif font.

CLAYTON PARK, NY 12055


—
—

T-MOBILE SITE NUMBER:
CT11233A

BU #: 806367
HRT 046 943209

MAPLE AVE WEST
HADDAM, CT 06441

EXISTING 115'-6" MONOPOLE



ISSUED FOR:

| REV | DATE | DRWN | DESCRIPTION | DES./QA |
|-----|----------|------|--------------------|---------|
| 0 | 08/13/19 | JAS | CONSTRUCTION | JL |
| 1 | 12/14/20 | DMW | REVISED PER CLIENT | MCK |
| 2 | 01/26/21 | DMW | REVISED PER CLIENT | MCK |
| 3 | 02/26/21 | DMW | REVISED PER CLIENT | MCK |
| 4 | 03/18/21 | DMW | REVISED PER CLIENT | MCK |

The seal is circular with a decorative border. The outer ring contains the text "STATE OF CONNECTICUT" at the top and "PROFESSIONAL ENGINEER" at the bottom. The inner circle features a central emblem with a bridge, a river, and a factory, surrounded by the words "BRAVE & BRAZED BREWER". Below the emblem, the year "1951" is inscribed. The entire seal is signed "John J. Brewster" in blue ink across the center.

03/18/21

IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

SHEET NUMBER: E-1 REVISION: 4

NOTE:
GROUND CREW TO VERIFY
EXISTING 100AMP SERVICE
DISCONNECT

1 AC PANEL SCHEDULE
SCALE: NOT TO SCALE

2 ONE-LINE DIAGRAM

T-Mobile

35 GRIFFIN ROAD
BLOOMFIELD, CT 06002

CC CROWN CASTLE


3 CORPORATE PARK DRIVE, SUITE 101
CLIFTON PARK, NY 12065

T-MOBILE SITE NUMBER:
CT11233A

BU #: **806367**
HRT 046 943209


MAPLE AVE WEST
HADDAM, CT 06441

EXISTING 115'-6" MONPOLE



ISSUED FOR:

| REV | DATE | DRWN | DESCRIPTION | DES./QA |
|-----|----------|------|--------------------|---------|
| 0 | 08/13/19 | JAS | CONSTRUCTION | JL |
| 1 | 12/14/20 | DMW | REVISED PER CLIENT | MCK |
| 2 | 01/26/21 | DMW | REVISED PER CLIENT | MCK |
| 3 | 02/26/21 | DMW | REVISED PER CLIENT | MCK |
| 4 | 03/18/21 | DMW | REVISED PER CLIENT | MCK |



03/18/21
Exp. 01/31/22

IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

SHEET NUMBER: **G-1** REVISION: **4**

1 ANTENNA GROUNDING DIAGRAM
SCALE: NOT TO SCALE

T-Mobile

35 GRIFFIN ROAD
BLOOMFIELD, CT 06002

CROWN CASTLE

3 CORPORATE PARK DRIVE, SUITE 101
CLIFTON PARK, NY 12065

T-MOBILE SITE NUMBER:
CT11233A

BU #: 806367
HRT 046 943209

MAPLE AVE WEST
HADDAM, CT 06441

EXISTING 115'-6" MONPOLE

ISSUED FOR:


| REV | DATE | DRWN | DESCRIPTION | DES./QA |
|-----|----------|------|--------------------|---------|
| 0 | 08/13/19 | JAS | CONSTRUCTION | JL |
| 1 | 12/14/20 | DMW | REVISED PER CLIENT | MCK |
| 2 | 01/26/21 | DMW | REVISED PER CLIENT | MCK |
| 3 | 02/26/21 | DMW | REVISED PER CLIENT | MCK |
| 4 | 03/18/21 | DMW | REVISED PER CLIENT | MCK |



03/18/21
Exp. 01/31/22

IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

SHEET NUMBER: **G-2** REVISION: **4**




NOTES:

1. DOUBLING UP "OR STACKING" OF CONNECTIONS IS NOT PERMITTED.
2. EXTERIOR ANTIOXIDANT JOINT COMPOUND TO BE USED ON ALL EXTERIOR CONNECTIONS.
3. GROUND BAR SHALL NOT BE ISOLATED FROM TOWER. MOUNT DIRECTLY TO TOWER STEEL.

1 ANTENNA GROUND BAR DETAIL

SCALE: NOT TO SCALE




NOTES:

1. EXTERIOR ANTIOXIDANT JOINT COMPOUND TO BE USED ON ALL EXTERIOR CONNECTIONS.
2. GROUND BAR SHALL NOT BE ISOLATED FROM TOWER. MOUNT DIRECTLY TO TOWER STEEL (TOWER ONLY).
3. GROUND BAR SHALL BE ISOLATED FROM BUILDING OR SHELTER.

2 TOWER/SHELTER GROUND BAR DETAIL

SCALE: NOT TO SCALE




SEE DESIGN NOTE 2

NOTES:

1. GROUND ROD SHALL BE DRIVEN VERTICALLY, NOT TO EXCEED 45 DEGREES FROM THE VERTICAL.
2. GROUND WIRE SHALL BE MIN. 30" BELOW GRADE OR 6" BELOW FROST LINE. (WHICH EVER IS GREATER) AS PER N.E.C. ARTICLE 250-50(D).

3 INSPECTION WELL DETAIL

SCALE: NOT TO SCALE




NOTES:

1. NUMBER OF GROUNDING BARS MAY VARY DEPENDING ON THE TYPE OF TOWER, ANTENNA LOCATIONS AND CONNECTION ORIENTATION. COAXIAL CABLES EXCEEDING 200 FEET ON THE TOWER SHALL HAVE GROUND KITS AT THE MIDPOINT. PROVIDE AS REQUIRED.
2. ONLY MECHANICAL CONNECTIONS ARE ALLOWED TO BE MADE TO CROWN CASTLE USA INC. TOWERS. ALL MECHANICAL CONNECTIONS SHALL BE TREATED WITH AN ANTI-OXIDANT COATING.
3. ALL TOWER GROUNDING SYSTEMS SHALL COMPLY WITH THE REQUIREMENTS OF THE RECOGNIZED EDITION OF ANSI/TIA 222 AND NFPA 780.


4 TYPICAL ANTENNA CABLE GROUNDING

SCALE: NOT TO SCALE



5 HARDWARE DETAIL FOR EXTERIOR CONNECTIONS

SCALE: NOT TO SCALE




SEE DESIGN NOTE 2

NOTES:

1. GROUND ROD SHALL BE DRIVEN VERTICALLY, NOT TO EXCEED 45 DEGREES FROM THE VERTICAL.
2. GROUND WIRE SHALL BE MIN. 30" BELOW GRADE OR 6" BELOW FROST LINE. (WHICH EVER IS GREATER) AS PER N.E.C. ARTICLE 250-50(D).

6 GROUND ROD DETAIL

SCALE: NOT TO SCALE




NOTE:

1. ERICO EXOTHERMIC "MOLD TYPES" SHOWN HERE ARE EXAMPLES. CONSULT WITH CONSTRUCTION MANAGER FOR SPECIFIC MOLDS TO BE USED FOR THIS PROJECT.
2. MOLD TYPE ONLY TO BE USED BELOW GRADE WHEN CONNECTING GROUND RING TO GROUND ROD.

1 CADWELD GROUNDING CONNECTIONS
SCALE: NOT TO SCALE

WEATHERPROOFING KIT
(SEE NOTE 3)

ANTENNA CABLE



#6 AWG STRANDED COPPER GROUND WIRE
(GROUNDED TO GROUND BAR). SEE NOTE 1 & 2


CABLE GROUND KIT

CABLE CONNECTOR

NOTES:

1. DO NOT INSTALL CABLE GROUND KIT AT A BEND AND ALWAYS DIRECT GROUND WIRE DOWN TO GROUND BAR.
2. GROUNDING KIT SHALL BE TYPE AND PART NUMBER AS SUPPLIED OR RECOMMENDED BY CABLE MANUFACTURER.
3. WEATHER PROOFING SHALL BE TWO-PART TAPE KIT, COLD SHRINK SHALL NOT BE USED.

3 CABLE GROUND KIT CONNECTION
SCALE: NOT TO SCALE



NOTES:

1. DOWN LEAD (HOME RUN) CONDUCTORS ARE NOT TO BE INSTALLED ON CROWN CASTLE USA INC. TOWER, PER THE GROUNDING DOWN CONDUCTOR POLICY QAS-STD-10091. NO MODIFICATION OR DRILLING INTO TOWER STEEL IS ALLOWED IN ANY FORM OR FASHION, CAD-WELDING ON THE TOWER AND/OR IN THE AIR ARE NOT PERMITTED.
2. OMIT INSULATOR WHEN MOUNTING TO TOWER STEEL OR PLATFORM STEEL. USE INSULATORS WHEN ATTACHING TO BUILDING OR SHELTERS.

6 GROUND BAR DETAIL
SCALE: NOT TO SCALE

| WIRE SIZE | BURNDY LUG | BOLT SIZE |
|------------------------|------------|-----------------------|
| #6 AWG GREEN INSULATED | YA6C-2TC38 | 3/8" - 16 NC S 2 BOLT |
| #2 AWG SOLID TINNED | YA3C-2TC38 | 3/8" - 16 NC S 2 BOLT |
| #2 AWG STRANDED | YA2C-2TC38 | 3/8" - 16 NC S 2 BOLT |
| #2/0 AWG STRANDED | YA26-2TC38 | 3/8" - 16 NC S 2 BOLT |
| #4/0 AWG STRANDED | YA28-2N | 1/2" - 16 NC S 2 BOLT |

BURNDY GROUND LUG W/
LONG BARREL
(SEE CHART)

HEAT SHRINK
(CLEAR)

NUT
(TYP)
LOCK WASHER
(TYP)

GROUNDING
CONDUCTOR

GROUND BAR
BOLT
(SEE CHART)
(TYP)

BURNDY TWO HOLE LUG W/
LONG BARREL
(SEE CHART)

GROUNDING
CONDUCTOR


BARE WIRE TO BE
NO-OX AT BOTH ENDS

STRANDED (GREEN INSULATED) ONLY FOR #6 AWG
(SEE CHART)


NOTES:

1. ALL GROUNDING LUGS ARE TO BE INSTALLED PER MANUFACTURER'S SPECIFICATIONS. ALL HARDWARE BOLTS, NUTS, LOCK WASHERS SHALL BE STAINLESS STEEL. ALL HARDWARE ARE TO BE AS FOLLOWS: BOLT, FLAT WASHER, GROUND BAR, GROUND LUG, FLAT WASHER AND NUT.

2 MECHANICAL LUG CONNECTION
SCALE: NOT TO SCALE



5 GROUNDWIRE INSTALLATION
SCALE: NOT TO SCALE



8 TRANSITIONING GROUND DETAIL
SCALE: NOT TO SCALE

T-Mobile

35 GRIFFIN ROAD
BLOOMFIELD, CT 06002

CROWN
CASTLE

3 CORPORATE PARK DRIVE, SUITE 101
CLIFTON PARK, NY 12065

T-MOBILE SITE NUMBER:
CT11233A


BU #: 806367
HRT 046 943209

MAPLE AVE WEST
HADDAM, CT 06441

EXISTING 115'-6" MONPOLE

ISSUED FOR:

| REV | DATE | DRWN | DESCRIPTION | DES./QA |
|-----|----------|------|--------------------|---------|
| 0 | 08/13/19 | JAS | CONSTRUCTION | JL |
| 1 | 12/14/20 | DMW | REVISED PER CLIENT | MCK |
| 2 | 01/26/21 | DMW | REVISED PER CLIENT | MCK |
| 3 | 02/26/21 | DMW | REVISED PER CLIENT | MCK |
| 4 | 03/18/21 | DMW | REVISED PER CLIENT | MCK |



03/18/21
Exp. 01/31/22

IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

SHEET NUMBER: G-3
REVISION: 4

7 LUG DETAIL
SCALE: NOT TO SCALE