




ORIGINAL

35 Griffin Road South
Bloomfield, CT 06002

November 21, 2007

BY HAND

Daniel F. Caruso, Chairman and
Members of the Siting Council
Connecticut Siting Council
Ten Franklin Square
New Britain, CT 06051



EM-T-MOBILE-074-070928 REVISED

RE: **Notice of Exempt Modification**
383 Torrington Road Litchfield, CT
Latitude: 41 45 58.62 / Longitude: 73 10 42.7

Dear Chairman Caruso and Members of the Siting Council:

Omnipoint Communications, Inc. a.k.a. T-Mobile (formerly Voicestream Wireless Corp.) hereby requests an order from the Connecticut Siting Council ("Council") to approve the proposed ("Litchfield"), in Litchfield, CT owned by Sprint.

Please accept this letter as notification pursuant to R.C.S.A. §16-50j-73, for construction that constitutes an exempt modification pursuant to R.C.S.A. §16-50j-72(b) (2).

Litchfield

The Litchfield facility consists of a one hundred forty (140') foot monopole ("Tower") owned and operated by Sprint. T-Mobile proposes to locate antennas at a centerline mounting height of one hundred eight (108') feet. T-Mobile's equipment will be located within the compound at the base of the tower.

Litchfield

As shown on the enclosed plans prepared by including a site plan and tower elevation of the November 13, 2007, annexed hereto as Exhibit 1, T-Mobile proposes a shared use of the Facility by placing antennas on the tower and equipment needed to provide personal communications services ("PCS") within the existing site plan. T-Mobile will install nine (9) panel antennas at the one hundred eight (108') foot level of the Tower. Three (3) associated unmanned equipment cabinets will be located at the base of the tower.

The proposed modification is structurally feasible. A structural analysis of the tower is attached as Exhibit 2. The structural analysis shows that the tower can safely accommodate the proposed T-Mobile installation.

The planned modifications to this facility fall within the activities explicitly provided for in R.C.S.A. §16-50j-72(b)(2).

1. The proposed modification will not result in any increase in the overall height of the existing structure.
2. The proposed modification will not affect ground-mounted equipment and will not require the extension of the site boundaries.
3. The proposed modification will not increase noise levels at the facility by six decibels or more.
4. Operation of T-Mobile's antennas at this site would not exceed the total radio frequency electromagnetic radiation power density level adopted by the FCC and Connecticut Department of Health. The "worst case" exposure calculated for the operation of this facility for T-Mobile would be approximately 11.829% of the standard. See Radio Frequency Memo annexed hereto as Exhibit 3.

Conclusion

For the foregoing reasons, T-Mobile respectfully submits that the proposed modification to the above referenced telecommunication facility constitute an exempt modification under R.C.S.A §16-50j-72(b)(2).

Respectfully submitted,



H. Karina Fournier
Zoning Department
35 Griffin Road South
Bloomfield, CT 06002

cc: First Selectman, Leo Paul, Jr.
Land Use/Zoning Enforcement Director, Matthew Speck
Property Owner, Angela Bolus


Exhibit 1

LITCHFIELD
383 TORRINGTON ROAD
LITCHFIELD, CT 06759
SITE NO.: CTNH375E
SITE TYPE: MONOPOLE

GENERAL NOTES

1. THE CONTRACTOR SHALL GIVE ALL NOTICES AND COMPLY WITH ALL LAWS, ORDINANCES, RULES, REGULATIONS AND LAWFUL ORDERS OF ANY PUBLIC AUTHORITY, MUNICIPAL AND UTILITY COMPANY SPECIFICATIONS, AND LOCAL AND STATE JURISDICTIONAL CODES BEARING ON THE PERFORMANCE OF THE WORK. THE WORK PERFORMED ON THE PROJECT AND THE MATERIALS INSTALLED SHALL BE IN STRICT ACCORDANCE WITH ALL APPLICABLE CODES, REGULATIONS, AND ORDINANCES.
2. THE ARCHITECT/ENGINEER HAVE MADE EVERY EFFORT TO SET FORTH IN THE CONSTRUCTION AND CONTRACT DOCUMENTS THE COMPLETE SCOPE OF WORK. THE CONTRACTOR BIDDING THE JOB IS NEVERTHELESS CAUTIONED THAT MINOR OMISSIONS OR ERRORS IN THE DRAWINGS OR SPECIFICATIONS SHALL NOT EXCUSE SAID CONTRACTOR FROM COMPLETING THE PROJECT AND IMPROVEMENTS IN ACCORDANCE WITH THE INTENT OF THESE DOCUMENTS.
3. THE CONTRACTOR OR BIDDER SHALL BEAR THE RESPONSIBILITY OF NOTIFYING (IN WRITING) THE PROJECT OWNER'S REPRESENTATIVE OF ANY CONFLICTS, ERRORS, OR OMISSIONS PRIOR TO THE SUBMISSION OF CONTRACTOR'S PROPOSAL OR PERFORMANCE OF WORK. IN THE EVENT OF DISCREPANCIES THE CONTRACTOR SHALL PRICE THE MORE COSTLY OR EXTENSIVE WORK, UNLESS DIRECTED IN WRITING OTHERWISE.
4. THE SCOPE OF WORK SHALL INCLUDE FURNISHING ALL MATERIALS, EQUIPMENT, LABOR AND ALL OTHER MATERIALS AND LABOR DEEMED NECESSARY TO COMPLETE THE WORK/PROJECT AS DESCRIBED HEREIN.
5. THE CONTRACTOR SHALL VISIT THE JOB SITE PRIOR TO THE SUBMISSION OF BIDS OR PERFORMING WORK TO FAMILIARIZE HIMSELF WITH THE FIELD CONDITIONS AND TO VERIFY THAT THE PROJECT CAN BE CONSTRUCTED IN ACCORDANCE WITH THE CONTRACT DOCUMENTS.
6. THE CONTRACTOR SHALL OBTAIN AUTHORIZATION FROM THE PROJECT OWNER'S REPRESENTATIVE TO PROCEED WITH CONSTRUCTION PRIOR TO STARTING WORK ON ANY ITEM NOT CLEARLY DEFINED BY THE CONSTRUCTION DRAWINGS / CONTRACT DOCUMENTS.
7. THE CONTRACTOR SHALL INSTALL ALL EQUIPMENT AND MATERIALS ACCORDING TO THE MANUFACTURER'S / VENDOR'S SPECIFICATIONS UNLESS NOTED OTHERWISE OR WHERE LOCAL CODES OR ORDINANCES TAKE PRECEDENCE.
8. THE CONTRACTOR SHALL PROVIDE A FULL SET OF CONSTRUCTION DOCUMENTS AT THE SITE UPDATED WITH THE LATEST REVISIONS AND ADDENDUMS OR CLARIFICATIONS AVAILABLE FOR THE USE BY ALL PERSONNEL INVOLVED WITH THE PROJECT.
9. THE CONTRACTOR SHALL SUPERVISE AND DIRECT THE PROJECT DESCRIBED HEREIN. THE CONTRACTOR SHALL BE SOLELY RESPONSIBLE FOR ALL CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES AND PROCEDURES AND FOR COORDINATING ALL PORTIONS OF THE WORK UNDER THE CONTRACT.
10. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY CONSTRUCTION CONTROL SURVEYS, ESTABLISHING AND MAINTAINING ALL LINES AND GRADES REQUIRED TO CONSTRUCT ALL IMPROVEMENTS AS SHOWN HEREIN.
11. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL PERMITS AND INSPECTIONS WHICH MAY BE REQUIRED FOR THE WORK BY THE ARCHITECT/ENGINEER, THE STATE, COUNTY OR LOCAL GOVERNMENT AUTHORITY.
12. THE CONTRACTOR SHALL MAKE NECESSARY PROVISIONS TO PROTECT EXISTING IMPROVEMENTS, EASEMENTS, PAVING, CURBING, ETC. DURING CONSTRUCTION. UPON COMPLETION OF WORK, THE CONTRACTOR SHALL REPAIR ANY DAMAGE THAT MAY HAVE OCCURRED DUE TO CONSTRUCTION ON OR ABOUT THE PROPERTY.
13. THE CONTRACTOR SHALL KEEP THE GENERAL WORK AREA CLEAN AND HAZARD FREE DURING CONSTRUCTION AND DISPOSE OF ALL DIRT, DEBRIS, RUBBISH AND REMOVE EQUIPMENT NOT SPECIFIED AS REMAINING ON THE PROPERTY. PREMISES SHALL BE LEFT IN CLEAN CONDITION AND FREE FROM PAINT SPOTS, DUST, OR SMUDGES OF ANY NATURE.
14. THE CONTRACTOR SHALL COMPLY WITH ALL OSHA REQUIREMENTS AS THEY APPLY TO THIS PROJECT.
15. THE CONTRACTOR SHALL NOTIFY THE PROJECT OWNER'S REPRESENTATIVE WHERE A CONFLICT OCCURS ON ANY OF THE CONTRACT DOCUMENTS. THE CONTRACTOR IS NOT TO ORDER MATERIAL OR CONSTRUCT ANY PORTION OF THE WORK THAT IS IN CONFLICT UNTIL CONFLICT IS RESOLVED BY THE PROJECT OWNER'S REPRESENTATIVE.
16. THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS, ELEVATIONS, PROPERTY LINES, ETC. ON THE JOB.
17. ALL UNDERGROUND UTILITY INFORMATION WAS DETERMINED FROM SURFACE INVESTIGATIONS AND EXISTING PLANS OR RECORD. THE CONTRACTOR SHALL LOCATE ALL UNDERGROUND UTILITIES IN THE FIELD PRIOR TO ANY SITE WORK. CALL THE FOLLOWING FOR ALL PRE-CONSTRUCTION NOTIFICATION 72-HOURS PRIOR TO ANY EXCAVATION ACTIVITY: DIG SAFE SYSTEM (MA, ME, NH, RI, VT): 1-888-344-7233 CALL BEFORE YOU DIG (CT): 1-800-922-4455

VICINITY MAP



SHEET INDEX

PROJECT SUMMARY

SITE NUMBER: CTNH375E
 SITE NAME: LITCHFIELD
 SITE ADDRESS: 353 TORRINGTON ROAD
 LITCHFIELD, CT 06759
 ASSESSOR'S PARCEL NO.: MAP: 126, BLOCK: 36, LOT: 91
 DEED BOOK/PAGE: 234/333
 SITE TYPE: MONOPOLE
 PROPERTY OWNER: SPRINT SITES USA
 APPLICANT: OMNIPOINT COMMUNICATIONS INC.
 35 GRIFFIN ROAD SOUTH
 SLOOMFIELD, CT 06002

PPROVAJ S

NDLORD _____
ASING _____
F. _____
ONDING _____
NSTRUCTION _____
VE _____

PROJECT NO: 2806.035

CHECKED BY: RS

SUBMITTALS

11/13/07	FINAL CONSTRUCTION
10/25/07	ANTENNA HEIGHT REVISED
09/25/07	FINAL CONSTRUCTION
09/18/07	CONSTRUCTION

THIS DOCUMENT IS THE CREATION, DESIGN,
PROPERTY AND COPYRIGHTED WORK OF
OMNIPONT COMMUNICATIONS, INC. ANY
DUPLICATION OR USE WITHOUT EXPRESS
WRITTEN CONSENT IS STRICTLY PROHIBITED.
DUPLICATION AND USE BY GOVERNMENT
AGENCIES FOR THE PURPOSES OF
CONDUCTING THEIR LAWFULLY AUTHORIZED
REGULATORY AND ADMINISTRATIVE FUNCTIONS
IS SPECIFICALLY ALLOWED.
THIS DRAWING IS NOT 24"X36", IT IS NOT
TO SCALE.

SITE
CTNH375E

REFERENCES

TITLE SHEET

SHEET NUMBER


DO NOT SCALE DRAWINGS

CONTRACTOR SHALL VERIFY ALL PLANS AND EXISTING DIMENSIONS AND CONDITIONS ON THE JOB SITE AND SHALL IMMEDIATELY NOTIFY THE PROJECT OWNER'S REPRESENTATIVE IN WRITING OF DISCREPANCIES BEFORE PROCEEDING WITH THE WORK OR BE RESPONSIBLE FOR SAME.

REFER TO SPRINT PCS DWG
FOR SITE CT33XC607
BY DEWBERRY DT. 04/05/07

NOTES:

- THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL NECESSARY CONSTRUCTION CONTROL SURVEYS AND MAINTAINING ALL LINES AND GRADES REQUIRED TO CONSTRUCT ALL IMPROVEMENTS SHOWN HEREIN.
- ALL DIMENSIONS SHOWN THUS \pm ARE APPROXIMATE. THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS AND ELEVATIONS WHICH EFFECT THE CONTRACTOR'S WORK. CONTRACTOR TO VERIFY ALL DIMENSIONS WITH PROJECT OWNER PRIOR TO CONSTRUCTION.
- NORTH ARROW SHOWN ON PLANS REFERS TO APPROXIMATE TRUE NORTH. CONTRACTOR SHALL RETAIN THE SERVICES OF A PROFESSIONAL SURVEYOR TO VERIFY TRUE NORTH AND PROVIDE AS-BUILT ANTELLA AZIMUTH, ANTELLA MECHANICAL DOWN-tilt AND ANTELLA RADIATION CENTER HEIGHT (AGL) CERTIFICATIONS FOR ANTELLA AZIMUTHS MUST BE WITHIN 3 DEGREES OF THE SPECIFIED SECTOR ORIENTATION ON THE RF BUILD SHEET.
- THE CONTRACTOR AND OR HIS SUB CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL PERMITS AND INSPECTIONS WHICH MAY BE REQUIRED FOR THE WORK BY THE ARCHITECT/ENGINEER, THE STATE, COUNTY OR LOCAL GOVERNMENT AUTHORITY.
- ANTENNA INSTALLATION SHALL BE CONDUCTED BY FIELD CREWS EXPERIENCED IN THE ASSEMBLY AND ERECTION OF RADIO ANTENNAS, TRANSMISSION LINES AND SUPPORT STRUCTURES.
- COAXIAL CABLE CONNECTORS AND TRANSMITTER EQUIPMENT SHALL BE PROVIDED BY THE PROJECT OWNER AND IS NOT INCLUDED IN THESE CONSTRUCTION DOCUMENTS. A SCHEDULE OF PROJECT OWNER SUPPLIED MATERIALS IS ATTACHED TO THE BID DOCUMENTS (SEE EXHIBIT 3). ALL OTHER HARDWARE TO BE PROVIDED BY THE CONTRACTOR, CONNECTION HARDWARE SHALL BE STAINLESS STEEL.
- WHEN "PAINT TO MATCH" IS SPECIFIED FOR ANTELLA CONCEALMENT, PAINT PRODUCT FOR ANTELLA RADOME SHALL BE SHERWIN WILLIAMS COROTHANE II. SURFACE PREPARATION AND APPLICATION SHALL BE IN ACCORDANCE WITH THE MANUFACTURER'S SPECIFICATIONS AND PROJECT OWNER'S GUIDELINES.
- COORDINATION, LAYOUT, AND FURNISHING OF CONDUIT, CABLE AND ALL APPURTENANCES REQUIRED FOR PROPER INSTALLATION OF ELECTRICAL AND TELECOMMUNICATION SERVICE SHALL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR.




ABBREVIATIONS

ADJ	ADJUSTABLE	NTS	NOT TO SCALE
APPROX	APPROXIMATE	OC	ON CENTER
BTS	BASE TRANSMISSION STATION	OPP	OPPOSITE
C	CONDUIT	(P)	PROPOSED
CMU	CONCRETE MASONRY UNIT	SF	SQUARE FOOT
CONC	CONCRETE	SHT	SHEET
CONT	CONTINUOUS	SIM	SIMILAR
CJ	CONSTRUCTION JOINT	STL	STEEL
DIA	DIAMETER	TOC	TOP OF CONCRETE
DWG	DRAWING	TOP	TOP OF MASONRY
EGB	EQUIPMENT GROUND BAR	TYP	TYPICAL
EA	EACH	VIF	VERIFY IN FIELD
ELEC	ELECTRICAL	UON	UNLESS OTHERWISE NOTED
EL	ELEVATION	WWF	WELDED WIRE FABRIC
EQ	EQUAL	W/	WITH
EQUIP	EQUIPMENT	PCS	PERSONAL COMMUNICATIONS SERVICES
(E)	EXISTING		
EXT	EXTERIOR		
FF	FINISHED FLOOR	A-1	ANTENNA MARK NO.
FG	FINISHED GRADE	C	CENTERLINE
GA	GAUGE	P	PLATE
GALV	GALVANIZED	&	AND
GC	GENERAL CONTRACTOR	•	AT
GWB	GYPSUM WALLBOARD		
LG	LONG		
LNA	LOW NOISE AMPLIFIER		
MAX	MAXIMUM		
MECH	MECHANICAL		
MFR	MANUFACTURER		
MGB	MASTER GROUND BAR		
MIN	MINIMUM		
MTL	METAL		
NIC	NOT IN CONTRACT		

SYMBOLS AND MATERIALS


W	NEW ANTENNA	GROUT OR PLASTER
•	EXISTING ANTENNAS	GWB
Wavy lines	ASPHALT	(E)CONSTRUCTION
Box	NEW ACCESS EASEMENT	CONCRETE
Concrete	CONCRETE	EARTH
Electric box	ELECTRIC BOX	GRAVEL
Light pole	LIGHT POLE	PLYWOOD
Circle	FND. MONUMENT	SAND
Diamond	SPOT ELEVATION	WOOD CONT.
Triangle	SET POINT	WOOD BLOCKING
Circle with dot	REVISION	STEEL
Grid reference	GRID REFERENCE	CENTER LINE
Detail reference	DET# SH#	PROPERTY LINE
Detail reference	DET# SH#	STEPPED FOOTING
SH# D	ELEVATION	MATCH LINE
SH# D	ELEVATION	WORK POINT
SH# D	ELEVATION	G GROUND WIRE
SH# D	ELEVATION	COAXIAL CABLE
Work item note	WORK ITEM NOTE	CHAIN LINK FENCE
		WATER MAIN

ANTENNA ORIENTATION KEY



OMNIPOINT COMMUNICATIONS INC.
A WHOLLY-OWNED SUBSIDIARY
OF T-MOBILE USA, INC.
35 GRIFFIN ROAD SOUTH
BLOOMFIELD, CT 06002
OFFICE: (860)-692-7100
FAX: (860)-692-7159

MAXTON
50 EASTMAN ST.
SOUTH EASTON, MA 02375
PHONE: (508) 936-6393
FAX: (508) 936-6395



APPROVALS

LANDLORD _____
LEASING _____

R.F. _____

ZONING _____

CONSTRUCTION _____

A/E _____

PROJECT NO: 2806.035

DRAWN BY: PT

CHECKED BY: RS

SUBMITTALS

3	11/13/07	FINAL CONSTRUCTION
2	10/25/07	ANTENNA HEIGHT REVISED
1	09/25/07	FINAL CONSTRUCTION
0	09/18/07	CONSTRUCTION

THIS DOCUMENT IS THE CREATION, DESIGN, PROPERTY AND COPYRIGHTED WORK OF OMNIPOINT COMMUNICATIONS, INC. ANY DUPLICATION OR USE WITHOUT EXPRESS WRITTEN CONSENT IS STRICTLY PROHIBITED. DUPLICATION AND USE BY GOVERNMENT AGENCIES FOR THE PURPOSES OF CONDUCTING THEIR LAWFULLY AUTHORIZED REGULATORY AND ADMINISTRATIVE FUNCTIONS IS SPECIFICALLY ALLOWED. IF THIS DRAWING IS NOT 24"X36", IT IS NOT TO SCALE.

SITE

CTNH375E

LITCHFIELD

383 TORRINGTON ROAD
LITCHFIELD, CT 06759

SHEET TITLE

PLAN
&
NOTES


SHEET NUMBER

A-1

OMNIPOINT COMMUNICATIONS INC.
A WHOLLY-OWNED SUBSIDIARY
OF T-MOBILE USA, INC.
35 GRIFFIN ROAD SOUTH
BLOOMFIELD, CT 06002
OFFICE: (860)-692-7100
FAX: (860)-692-7159

MAXTON

50 EASTMAN ST.
SOUTH EASTON, MA 02375
PHONE: (508) 936-6393
FAX: (508) 936-6395



APPROVALS

LANDLORD _____
LEASING _____
R.F. _____
ZONING _____
CONSTRUCTION _____
A/E _____

PROJECT NO: 2806.035

DRAWN BY: PT

CHECKED BY: RS

SUBMITTALS

3 11/13/07 FINAL CONSTRUCTION
2 10/25/07 ANTENNA HEIGHT REVISED
1 09/25/07 FINAL CONSTRUCTION
0 09/18/07 CONSTRUCTION

THIS DOCUMENT IS THE CREATION, DESIGN, PROPERTY AND COPYRIGHTED WORK OF OMNIPOINT COMMUNICATIONS, INC. ANY DUPLICATION OR USE WITHOUT EXPRESS WRITTEN CONSENT IS STRICTLY PROHIBITED. DUPLICATION AND USE BY GOVERNMENT AGENCIES FOR THE PURPOSE OF CONDUCTING THEIR LAWFULLY AUTHORIZED REGULATORY AND ADMINISTRATIVE FUNCTIONS IS SPECIFICALLY ALLOWED. IF THIS DRAWING IS NOT 24"X36", IT IS NOT TO SCALE.

SITE


CTNH375E

LITCHFIELD

383 TORRINGTON ROAD
LITCHFIELD, CT 06759

SHEET TITLE
ELEVATION
&
DETAILS


SHEET NUMBER
A-2



EQUIPMENT LAYOUT

SCALE: 1/2" = 1'-0"


2



ELEVATION
AT EQUIPMENT PAD

SCALE: 1/2" = 1'-0"

3



WEST ELEVATION


SCALE: 1/8" = 1'-0"

1

NOTE:
MONPOLE AND FOUNDATION
ANALYSIS BY OTHERS

OMNIPOINT COMMUNICATIONS INC.
A WHOLLY-OWNED SUBSIDIARY
OF T-MOBILE USA, INC.
35 GRIFFIN ROAD SOUTH
BLOOMFIELD, CT 06002
OFFICE: (860)-692-7100
FAX: (860)-692-7159

MAXTON
50 EASTMAN ST.
SOUTH EASTON, MA 02375
PHONE: (508) 936-6393
FAX: (508) 936-6395



APPROVALS

LANDLORD _____
LEASING _____
R.F. _____
ZONING _____
CONSTRUCTION _____
A/E _____

PROJECT NO: 2806.035

DRAWN BY: PT
CHECKED BY: RS

SUBMITTALS

3	11/13/07	FINAL CONSTRUCTION
2	10/25/07	ANTENNA HEIGHT REVISED
1	09/25/07	FINAL CONSTRUCTION
0	09/18/07	CONSTRUCTION

THIS DOCUMENT IS THE CREATION, DESIGN, PROPERTY AND COPYRIGHTED WORK OF OMNIPOINT COMMUNICATIONS, INC. ANY DUPLICATION OR USE WITHOUT EXPRESS WRITTEN CONSENT IS STRICTLY PROHIBITED. DUPLICATION AND USE BY GOVERNMENT AGENCIES FOR THE PURPOSES OF CONDUCTING THEIR LAWFULLY AUTHORIZED REGULATORY AND ADMINISTRATIVE FUNCTIONS IS SPECIFICALLY ALLOWED. IF THIS DRAWING IS NOT 24"X36", IT IS NOT TO SCALE.

SITE

CTNH375E

LITCHFIELD


383 TORRINGTON ROAD
LITCHFIELD, CT 06759

SHEET TITLE


DETAILS

SHEET NUMBER

A-3




GPS ANTENNA DETAIL



AMPLIFIER & PANEL
ANTENNA DETAIL

SCALE: N.T.S.


1



BTS EQUIPMENT DETAIL

SCALE: N.T.S.


4



SECTION AT CABLE BRIDGE


SCALE: 3/4"=1'-0"

2



MASTER GND. BAR (MGB) 6

SCALE: N.T.S.




GROUNDING - STANDARD DETAIL GROUND ROD 7

SCALE: N.T.S.


COAX CABLE CONNECTION AND GROUNDING DETAIL 4

SCALE: N.T.S.




ONE LINE DIAGRAM 5

SCALE: N.T.S.



POWER/TELCO RISER DIAGRAM 1

SCALE: N.T.S.



SECTION "A-A"


NOTE:

1. "DOUBLING UP" OR "STACKING" OF CONNECTION IS NOT PERMITTED.

2. OXIDE INHIBITING COMPOUND TO BE USED AT ALL LOCATIONS.

TYPICAL GROUND BAR CONNECTIONS DETAIL 2

SCALE: N.T.S.



EQUIPMENT GND. BAR (EGB) 3

SCALE: N.T.S.

GROUNDING RISER DIAGRAM 8

SCALE: N.T.S.


ELECTRICAL LEGEND

—	NEW PANEL BOARD, SURFACE MOUNTED
—	EXISTING PANEL BOARD, SURFACE MOUNTED
—	DRY TYPE TRANSFORMER
—	METER
—	CIRCUIT BREAKER
—	NON-FUSIBLE DISCONNECT SWITCH, MOUNTED 54" A.F.F.
—	FUSIBLE DISCONNECT SWITCH, MOUNTED 54" A.F.F.
—	TRANSIENT VOLTAGE SURGE SUPPRESSER WITH BUILT-IN FUSES, SURFACE MOUNTED
—	DUPLEX OUTLET, SURFACE MOUNTED, 20 AMPS, 125 VOLTS, SINGLE PHASE
—	JUNCTION BOX, SURFACE MOUNTED 18" A.F.F.
—	EXPOSED WIRING
—	HOME RUNS, MINIMUM 2#10 + 1#10G IN 3/4" CONDUIT U.O.N.
—	ABOVE FINISHED FLOOR
—	UNLESS OTHERWISE NOTED
—	WEATHERPROOF
—	GROUND FAULT INTERRUPTER
—	AMPERE
—	VOLT
—	KILOWATT - HOUR
—	CONDUIT
—	GROUND
—	GROUND
—	MASTER GND. BAR <small>MECHANICAL CONNECTION</small>
—	— CADWELD CONNECTION
—	EQUIPMENT GND. BAR <small>MECHANICAL CONNECTION</small>
—	— CADWELD CONNECTION
—	GROUND COPPER WIRE, SIZE AS NOTED
—	EXPOSED WIRING
—	COAXIAL CABLE
—	5/8" x 10' COPPER CLAD STEEL GROUND ROD
—	EXOTHERMIC (CADWELD) OR MECHANICAL (COMPRESSION TYPE) CONNECTION
—	POWER PROTECTION CABINET

OMNIPOINT COMMUNICATIONS INC.

A WHOLLY-OWNED SUBSIDIARY
OF T-MOBILE USA, INC.
35 GRIFFIN ROAD SOUTH
BLOOMFIELD, CT 06002
OFFICE: (860)-692-7100
FAX: (860)-692-7159

MAXTON
50 EASTMAN ST.
SOUTH EASTON, MA 02375
PHONE: (508) 936-6393
FAX: (508) 936-6395



APPROVALS

LANDLORD _____

LEASING _____

R.F. _____

ZONING _____

CONSTRUCTION _____

A/E _____

PROJECT NO: 2806.035

DRAWN BY: PT

CHECKED BY: RS

SUBMITTALS

3	11/13/07	FINAL CONSTRUCTION
2	10/25/07	ANTENNA HEIGHT REVISED
1	09/25/07	FINAL CONSTRUCTION
0	09/18/07	CONSTRUCTION

THIS DOCUMENT IS THE CREATION, DESIGN, PROPERTY AND COPYRIGHTED WORK OF OMNIPOINT COMMUNICATIONS, INC. ANY DUPLICATION OR USE WITHOUT EXPRESS WRITTEN CONSENT IS STRICTLY PROHIBITED. DUPLICATION AND USE BY GOVERNMENT AGENCIES FOR THE PURPOSES OF CONDUCTING THEIR LAWFULLY AUTHORIZED REGULATORY AND ADMINISTRATIVE FUNCTIONS IS SPECIFICALLY ALLOWED. IF THIS DRAWING IS NOT 24" x 36", IT IS NOT TO SCALE.

SITE

CTNH375E

LITCHFIELD

383 TORRINGTON ROAD
LITCHFIELD, CT 06759

SHEET TITLE
ELECTRICAL RISERS,
DETAILS & NOTES

SHEET NUMBER
E-1

Exhibit 2

**Sprint PCS
Structure & Foundation
Design Calculations
140' Monopole
Site: Litchfield/CT33XC607
EEI Job #: 14854-E01**

1522 MONTELLA, LUDWIG, & CLOUTIER


MATERIAL REC'D. PER ASSEMBLY



**ENGINEERED
ENDEAVORS
INCORPORATED**

The Experienced Point of View

Customer: SPRINT PCS
Description: 140' MONOPOLE
EEI Job Number: 14854-0




SITE INFORMATION

Location: LITCHFIELD,
LITCHFIELD COUNTY, CT
Site Name: LITCHFIELD
Site Number: CT33XC607

DESIGN INFORMATION


Designed By: P. SCHWARTZ
Design Date: 04 / 13 / 2007
Status: REVISION 0

ANTENNA LOADING



- (12) 48" x 10" x 6" PANEL ANTENNAS MOUNTED ON A 12' T-ARM ARRAY AT 138' (CELCO PARTNERSHIP - FUTURE)
- (12) 96" x 12" x 6" PANEL ANTENNAS MOUNTED ON A 12' T-ARM ARRAY AT 128' (SPRINT PCS)
- (12) 48" x 10" x 6" PANEL ANTENNAS MOUNTED ON A 12' T-ARM ARRAY AT 118' (CINGULAR - FUTURE)
- (12) 48" x 10" x 6" PANEL ANTENNAS MOUNTED ON A 12' T-ARM ARRAY AT 108' (FUTURE)
- (1) GPS ANTENNA MOUNTED AT 65' (SPRINT PCS)

DESIGN CRITERIA



ENGINEERED ENDEAVORS, INC.

7610 Jenthal Drive • Mentor, Ohio 44060-4872
Phone: (440) 918-1101 • Phone: (888) 270-3855
Fax: (440) 918-1108 • www.engend.com

IT IS THE RESPONSIBILITY OF THE PURCHASER TO VERIFY THAT THE WIND LOADS AND DESIGN CRITERIA SPECIFIED MEET THE REQUIREMENTS OF ALL LOCAL BUILDING CODES.

APPURTENANCES

DESCRIPTION	NUM.	ELEV.	Kz	AREA	WGT	Ca	< WITHOUT ICE >		< WITH ICE >		FACTOR
							AREA	WGT	Ca	AREA	
8'x1' PANEL ANTENNAS	12	127.	1.470	8.00	50.	1.4300	8.76	112.	1.4200	0.96	
4'x10in PANEL ANTENN	12	137.	1.502	3.33	25.	1.4000	3.74	54.	1.4000	1.01	
T-ARM W/12' SEPARATI	3	137.	1.502	5.00	400.	0.7000	6.00	600.	0.7000	1.00	
4'x10in PANEL ANTENN	12	117.	1.436	3.33	25.	1.4000	3.74	54.	1.4000	1.01	
T-ARM W/12' SEPARATI	3	117.	1.436	5.00	400.	2.0000	6.00	600.	2.0000	1.00	
4'x10in PANEL ANTENN	12	107.	1.399	3.33	25.	1.4000	3.74	54.	1.4000	1.01	
T-ARM W/12' SEPARATI	3	107.	1.399	5.00	400.	0.7000	6.00	600.	0.7000	1.00	
T-ARM W/12' SEPARATI	3	127.	1.470	5.00	400.	0.7000	6.00	600.	0.7000	1.00	
GPS	1	64.	1.208	2.00	25.	0.8000	2.26	45.	0.8000	1.00	

LOAD CASE 2

BASIC LOADING

DEAD LOAD FACTOR 1.00, WIND PSF REDUCTION 1.00, RADIAL ICE 0.00 IN.

WIND VELOCITY 90 BOTTOM 20.91 PSF TOP 31.47 PSF
MAX BASE ROTATION 0.00 DEG

APPLIED APPURTENANCE FORCES

	ELEVATION	WEIGHT	WIND
	FT	KIPS	KIPS
8'x1' PANEL ANTENNAS	127.00	0.600	6.788
4'x10in PANEL ANTENNAS	137.00	0.300	2.974
T-ARM W/12' SEPARATION	137.00	1.200	0.553
4'x10in PANEL ANTENNAS	117.00	0.300	2.843
T-ARM W/12' SEPARATION	117.00	1.200	1.509
4'x10in PANEL ANTENNAS	107.00	0.300	2.771
T-ARM W/12' SEPARATION	107.00	1.200	0.515
T-ARM W/12' SEPARATION	127.00	1.200	0.541
GPS	64.00	0.025	0.068

TUBE PROPERTIES	MEMBER FORCES	STRESSES	STRESS	TOTAL
ELEV/IDIAM	WALL	SHEAR	AXIAL	AXIAL BEND
FT/IN	IN	K-FT	K-FT	KSI

36.00	44.38	0.3750	26.07	2021.02	18.69	0.36	42.88	48.56	0.89	5.6	1.49
24.00	47.34	0.3750	26.96	2344.41	20.94	0.38	43.66	47.80	0.92	2.4	0.97
12.00	50.29	0.3750	27.79	2677.82	23.21	0.39	44.11	47.13	0.94	0.6	0.47
0.00	53.25	0.3750	29.19	3021.64	26.86	0.43	44.35	46.53	0.96	0.0	0.00

REACTION COMPONENTS (KIPS AND FT-KIPS)

TRANSVERSE	VERTICAL	WIND	MOMENT ABOUT	MOMENT ABOUT	MOMENT ABOUT
TRANSVERSE	VERTICAL	WIND	TRANSVERSE	VERTICAL	WIND
0.000	26.862	29.193	3021.636	0.000	0.000

Pole 140' - MONOPOLE 14854-0

SUMMARY TABLE

ELEV	STRESS RATIO	AXIAL	BENDING	LOADING	COMPARISON
139.00	0.00	0.00	0.05	0.10	3. BASIC LOADING PLUS ICE
137.00	0.01	0.54	0.1	0.1	2. BASIC LOADING
127.00	0.09	1.54	40.4	2	2. BASIC LOADING
117.00	0.30	3.26	161.5	2	2. BASIC LOADING
107.00	0.53	5.08	333.9	2	2. BASIC LOADING
96.75	0.76	7.16	552.9	2	2. BASIC LOADING
84.00	0.61	9.04	836.7	2	2. BASIC LOADING
74.00	0.68	10.69	1068.1	2	2. BASIC LOADING
64.00	0.74	12.26	1307.3	2	2. BASIC LOADING
49.50	0.84	18.69	1669.2	2	2. BASIC LOADING
36.00	0.89	18.69	2021.0	2	2. BASIC LOADING
24.00	0.92	20.94	2344.4	2	2. BASIC LOADING
12.00	0.94	23.21	2677.8	2	2. BASIC LOADING
0.00	0.96	26.86	3021.6	2	2. BASIC LOADING

MAXIMUM SUPPORT MOMENT K-FT

CORRESPONDING AXIAL FORCE KIPS

CORRESPONDING SHEAR FORCE KIPS



**ENGINEERED
ENDEAVORS
INCORPORATED**

The Experienced Point of View



DESIGN CALCULATIONS

FOR A

DRILLED PIER FOUNDATION

April 17, 2007

7610 Jenthal Drive • Mentor, Ohio 44060-4872
Phone: (440) 918-1101 • Phone: (888) 270-3855
Fax: (440) 918-1108 • www.engend.com

ULTIMATE STRENGTH DESIGN OF FOOTING

CONCRETE, psi
STEEL, KSI

SHEAR IN FOOTING

1. CASE I - DEAD LOAD, TWO-WAY SHEAR

Ultimate Vertical Load, kips	775.97
Ultimate Pressure, ksf	1.29
Ultimate shear V, kips	659.30
Design shear V_d , kips	2547.57

$$U = 1.47D$$

2. CASE II - WIND LOAD, ONE-WAY SHEAR

Ultimate Moment, kip-ft	5208.32
Ultimate Vertical Load, kips	498.84
Eccentricity, ft	10.44
Ultimate Pressure, ksf	7.50
Dist. from edge to critical sect., ft	6.25
Pressure distance, ft	5.43
Pressure @ critical section, ksf	0.00
Ultimate Shear, kips	498.84
Design Shear, kips	821.26

$$U = 0.9D + 1.6W$$

REINFORCING STEEL

FLEXURE STRENGTH DESIGN

Ultimate Moment, kip-ft

Case I 1212.45

Case II 3462.39 $q_1 = 0.00$

$R_n =$	174.5
$r =$	0.00301
i_{min}	0.00180
A_1	26.59
#	8
$A_b, in^2 =$	0.79
	33.66
	36.00
	28.44
	0.00322
	193.45

Design Moment, kip-ft	3839.03
Horizontal Spacing, in	shor= 8.23
Min. Steel Area, sq.in	15.88
Min. Number of Bars	20.10
Actual Number of Bars	23.00
Top Steel Area, sq.in	18.17
Horizontal Spacing, in	shor= 13.09

TOP

Bending about the diagonal

No.	Angle, deg		Coord., in	Edge Dist., in	No.	Angle, deg		Coord., in	Edge Dist., in
	phi	c1				phi	c1		
1	0	37.50		21.90	7	180	-37.50		96.90
2	30	32.48		26.92	8	210	-32.48		91.87
3	60	18.75		40.65	9	240	-18.75		78.15
4	90	0.00		59.40	10	270	0.00		59.40
5	120	-18.75		78.15	11	300	18.75		40.65
6	150	-32.48		91.87	12	330	32.48		26.92

Location of neutral axis $c =$, in
Compression zone, $a =$

	No.	e	Force kips	Tension zone	No.	e	Force kips
eu=	1	0.000558773	36.93		2	0.0000	0.01
	0.003	2			3	0.0015	119.74
		12		ey= 0.00207	4	0.0036	161.95
					5	0.0057	161.95
					6	0.0072	161.95
					7	0.0078	161.95
					8	0.0072	161.95
					9	0.0057	161.95
					10	0.0036	161.95
	Concrete, kips		1335.14		11	0.0015	119.74
	Total compression		1372.08		12	0.0000	0.01
				Total tension, kips			1373.15

Moment due to compression

Moment due to Compressor			
Rebars	Force	Mom. Arm.	Moment
	- kips	in	k-ft
1	36.93	37.50	115.42
2	0.00	32.48	0.00
12	0.00	32.48	0.00
Concrete	1335.14	51.77	5759.99
Total in compressor		5875.41	

Moment due to tension

Rebars	Force	Mom.	Arm.	Moment
3	119.74	18.75		-187.10
4	161.95	18.75		-253.05
5	161.95	0.00		0.00
6	161.95	-18.75		253.05
7	161.95	-37.50		506.09
8	161.95	-32.48		438.29
9	161.95	-18.75		253.05
10	161.95	0.00		0.00
11	119.74	18.75		-187.10

Total in compressor 5875.41

Total in tension 823.24

Design Moment, kip-ft 6028.78



Pedestal Design Moment, kip-ft 5498.85

MATERIAL LIST	
ITEM	DESCRIPTION
1	7 INCH x 8'-0" (ASTM A415-G50) ANCHOR BOLTS
2	46 #6 REBAR x 20'-0" (ASTM A415-G50)
3	76 #6 REBAR x 20'-0" (ASTM A415-G50)
4	41 #6 REBAR x 10'-3" (ASTM A415-G50)
5	10 #6 REBAR x 21'-0" (ASTM A415-G50)

VOL. CONCRETE @ 4000 cu. ft. CEMENT 75.6 yd ³
STEEL (ASTM A415-G50) 11500 lb

GENERAL NOTES:

1. FOUNDATION DESIGN BASED ON THE POLYGRAPHIC REPORT NO. 1084, DRAWDOWN IS AS EMAILED BY THE CONTRACTOR.
2. FOUNDATION DESIGN IS SHOWN FROM THE ACTUAL SOIL INVESTIGATION AS DEFINED IN THE SOIL REPORT. SHOWN ARE THE ACTUAL SOIL CONDITIONS, SUPERFICIAL SOIL CONDITIONS, AND DEPTH TO BEDROCK. NO FOUNDATION DESIGNER SHOULD BE NOTIFIED IN WRITING IF THESE CONDITIONS ARE NOT AS SHOWN IN THE SOIL REPORT.
3. THE CONTRACTOR SHOULD BE CONSULTED PRIOR TO CONSTRUCTION. SITE CHANGES OR LURKING CONDITIONS WHICH ARE NOT SHOWN IN THE SOIL REPORT SHOULD BE NOTIFIED IN WRITING. CONSTRUCTION DRAWINGS, CONTRACTOR'S CONSTRUCTION METHODS, AND CONSTRUCTION SEQUENCES SHOULD BE APPROVED PRIOR TO CONSTRUCTION. CONTRACTOR'S CONSTRUCTION METHODS AND CONSTRUCTION SEQUENCES SHOULD BE APPROVED PRIOR TO CONSTRUCTION.
4. FOUNDATION DRAWDOWN SHALL BE INFERRED PRIOR TO PLACEMENT OF REINFORCEMENT AND ANCHOR BOLTS.
5. SPECIAL INSPECTION OF REINFORCEMENT, ANCHOR BOLTS, PLACEMENT, AND CONCRETE IS REQUIRED PER 2010 MC. FOR CONCRETE, USE TYPE 4 CONCRETE AS SHOWN IN THE DRAWINGS. CONCRETE SHOULD NOT EXCEED 3000 psi COMPRESSIVE STRENGTH.
6. REINFORCING STEEL SHALL CONFORM TO THE STANDARDS: FERROUS AND NONFERROUS SHALL BE ASSEMBLED VIBRATING, WELDING, OR BY MEANS OF OTHER MEANS AS SHOWN IN THE DRAWINGS. FOR NO. 8 BARS AND THICKER, AS A DIA. OF 10 MM AND LONGER AS THE HORIZONTAL TIES, SHALL BE STaggerED WITH NO MORE THAN 5% OF SPACES IN ONE PLACE.
7. CONCRETE MAX DESIGN AND CONSTRUCTION PROCEDURES SHALL BE IN COMPLIANCE WITH ACI 318-12, ACI 315, AND ACI 348, AS WELL AS APPROPRIATE STATE AND LOCAL CODES.
8. ANCHOR BOLTS REQUIRED TO STRENGTHEN FOUNDATIONS SHALL BE PLACED AS SHOWN IN THE DRAWINGS.
9. CONCRETE MAX SHOULD HAVE A SLUMP OF 7'-0" (1.75 M) FOR DRILLED TIEH AND 2'-0" (0.6 M) FOR Poured CONCRETE.
10. FOR DRILLED PILES ONLY, THE CONCRETE OVER THE ENTIRE LENGTH OF ANCHOR BOLTS IS SMALL. CONCRETE MAX FOUNDATION SHALL BE VIBRATED FOR MAX FOUNDATIONS. ALL CONCRETE SHOULD BE VIBRATED FOR MAX FOUNDATIONS.
11. ANCHOR BOLT CONSTRUCTION REQUIRED PRIOR TO CONCRETE PLACEMENT. THE CONTRACTOR SHOULD CONSULT THE SITE PLAN AND APPROVAL DRAWING FOR PROPER ACCESS POINT ORIENTATION.



140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

140'-0" MONOPOLE
LITCHFIELD, LITCHFIELD COUNTY CT

14

Exhibit 3



T-Mobile USA Inc.
100 Filley St, Bloomfield, CT 06002-1853
Phone: (860) 692-7100
Fax: (860) 692-7159

Technical Memo

To: Karina Fournier
From: Alex Murillo - Radio Frequency Engineer
cc: Jason Overbey
Subject: Power Density Report for CTNH375E
Date: November 6, 2007

1. Introduction:

This report is the result of an Electromagnetic Field Intensities (EMF - Power Densities) study for the T-Mobile PCS antenna installation on a Monopole at 383 Torrington Rd, Litchfield, CT. This study incorporates the most conservative consideration for determining the practical combined worst case power density levels that would be theoretically encountered from locations surrounding the transmitting location.

2. Discussion:

The following assumptions were used in the calculations:

- 1) The emissions from T-Mobile transmitters are in the 1935-1945 MHz frequency band.
- 2) The antenna array consists of three sectors, with 3 antennas per sector.
- 3) The model number for each antenna is APXV18-209014-C.
- 4) The antenna center line height is 108 ft.
- 5) The maximum transmit power from any sector is 1653.94 Watts Effective Radiated Power (EiRP) assuming 8 channels per sector.
- 6) All the antennas are simultaneously transmitting and receiving, 24 hours a day.
- 7) Power levels emitting from the antennas are increased by a factor of 2.56 to account for possible in-phase reflections from the surrounding environment. This is rarely the case, and if so, is never continuous.
- 8) The average ground level of the studied area does not change significantly with respect to the transmitting location

Equations given in "FCC OET Bulletin 65, Edition 97-01" were then used with the above information to perform the calculations.

3. Conclusion:

Based on the above worst case assumptions, the power density calculation from the T-Mobile PCS antenna installation on a Monopole at 383 Torrington Rd, Litchfield, CT, is 0.03488 mW/cm². This value represents 3.488% of the Maximum Permissible Exposure (MPE) standard of 1 milliwatt per square centimeter (mW/cm²) set forth in the FCC/ANSI/IEEE C95.1-1991. Furthermore, the proposed antenna location for T-Mobile will not interfere with existing public safety communications, AM or FM radio broadcasts, TV, Police Communications, HAM Radio communications or any other signals in the area.

The combined Power Density from other carriers is 8.341%. The combined Power Density for the site is 11.829% of the M.P.E. standard.

New England Market

T-Mobile

Worst Case Power Density

Site:	CTNH375E
Site Address:	383 Torrington Rd
Town:	Litchfield
Tower Height:	140 ft.
Tower Style:	Monopole
Base Station TX output	20 W
Number of channels	8
Antenna Model	APXV18-209014-C
Cable Size	15/8
Cable Length	160 ft.
Antenna Height	108.0 ft.
Ground Reflection	1.6
Frequency	1945.0 MHz
Jumper & Connector loss	4.50 dB
Antenna Gain	16.5 dBi
Cable Loss per foot	0.0116 dB
Total Cable Loss	1.8560 dB
Total Attenuation	6.3560 dB
Total EIRP per Channel (In Watts)	53.15 dBm 206.74 W
Total EIRP per Sector (In Watts)	62.19 dBm 1653.94 W
nsg	10.1440
Power Density (S) =	0.034877 mW/cm^2
T-Mobile Worst Case % MPE =	3.4877%

Equation Used :

$$S = \frac{(1000(\pi r)^2 (Power) \cdot 10^{(mW/10)})}{4 \pi (R)^2}$$

Office of Engineering and Technology (OET) Bulletin 65, Edition 97-01, August 1997

Co-Location Total

Carrier	% of Standard
Sprint PCS	8.3410 %
Total Excluding T-Mobile	8.3410 %
T-Mobile	3.4877
Total % MPE for Site	11.8287%