

January 13, 2025

Members of the Siting Council Connecticut Siting Council Ten Franklin Square New Britain, CT 06051

RE: Notice of Exempt Modification

864 Opening Hill Road, Madison CT

Latitude: 41.3573381 Longitude: -72.638773

T-Mobile Site#: CT11394A Equipment Upgrade

Dear Ms. Bachman:

T-Mobile currently maintains (6) antenna at the 130-foot level of the existing 180-foot self-support tower located at 864 Opening Hill Road, Madison CT. The property and tower are both owned by North Madison Volunteer Fire Co. T-Mobile now intends to remove (3) existing antenna and replace with (3) new 600/700/1900/2100 MHz antenna. The new antennas would be installed at the 130-foot level of the existing tower. This modification includes B2, B5 hardware that is both 4G (LTE), and 5G capable.

T-Mobile Planned Modifications:

Remove: NONE

Remove and Replace:

- (3) RR90 Antenna (Remove) (3) HBXX-9014DS-A2M Antenna 1900/2100 MHz (Replace)
- (3) Hybrid 6x12 Fiber lines (Remove) (3) Hybrid 6x24 Hybrid line (Replace)

Install New:

(3) RRU 4460

Existing to Remain:

- (6) 1-5/8" Coax Lines
- (3) APXVAARR24 43-U-NA20 600/700 MHZ Antenna
- (3) RRU 4449



This facility was approved by the Town of Madison Planning and Zoning Commission April 17, 1997. Please see attached.

Please accept this letter as notification pursuant to Regulations of Connecticut State Agencies §16-50j-73, for construction that constitutes an exempt modification pursuant to R.C.S.A. § 16-50j-72(b)(2). In accordance with R.C.S.A. § 16-50j-73, a copy of this letter is being sent to Peggy Lyons, First Selectwoman and Erin Mannix, Town Planner for the Town of Madison, as well as the property owner and the tower owner.

- 1. The proposed modifications will not result in an increase in the height of the existing structure.
- 2. The proposed modifications will not require the extension of the site boundary.
- 3. The proposed modifications will not increase noise levels at the facility by six decibels or more, or to levels that exceed state and local criteria.
- 4. The operation of the replacement antennas will not increase radio frequency emissions at the facility to a level at or above the Federal Communications Commission safety standard.
- 5. The proposed modifications will not cause a change or alteration in the physical or environmental characteristics of the site.
- 6. The existing structure and its foundation can support the proposed loading.

For the foregoing reasons, T-Mobile respectfully submits that the proposed modifications to the above referenced telecommunications facility constitute an exempt modification under R.C.S.A. § 16-50j-72(b)(2).

Sincerely,

Denise Sabo

Mobile: 203-435-3640 Fax: 413-521-0558

Office: 4 Angelas Way, Burlington CT 06013 Email: denise@northeastsitesolutions.com



Attachments:

cc:

Peggy Lyons, First Selectwoman Town of Madison 8 Campus Drive, Madison CT 06443

Erin Mannix., Town Planner Town of Madison 8 Campus Drive, Madison CT 06443

Madison Volunteer Fire Co, Tower and property owner 864 Opening Hill Road, Madison CT 06443

Exhibit A

Original Facility Approval



8 CAMPUS DRIVE MADISON, CONNECTICUT 06443-2563 (203) 245-5632

FAX (203) 245-5613

TOWN OF MADISON

CONNECTICUT LAND USE OFFICE

MADISON PLANNING AND ZONING COMMISSION

CERTIFICATION OF SPECIAL EXCEPTION PERMIT OR MODIFICATION OF SPECIAL EXCEPTION PERMIT

APPL. NO.: 97-5D

DATE OF APPROVAL: April 17, 1997

This certifies that on the above date a MODIFICATION OF SPECIAL EXCEPTION PERMIT was granted by the Madison Planning and Zoning Commission to:

OWNER OF RECORD: North Madison Volunteer Fire Department

under the provisions of Sec. 4.7 of the Zoning Regulations of the Town of Madison on property located at:

STREET ADDRESS OR LOCATION: 864 OPENING HILL ROAD

TO ALLOW: Construction of a 180 ft. communications tower to replace existing tower, installation of equipment building and emergency back-up generator waiving requirements of 1) a traffic study; 2) a waste water report and engineering study; and 3) final floor plans for the equipment building. The temporary installation of the "Cell on Wheels" was also approved. This approval is conditioned on plastic slats being placed in the chain link fence to obscure the view of the materials enclosed.

In accordance with Section 4.6 of said Regulations, this approval and permit are conditioned upon completion of all proposed improvements in accordance with approved plans within five years from date of approval, and shall become null and void in the event of failure to complete such improvements within said five year period or any extension thereof granted by the Commission

period or any extension thereof	f granted by the Commission.	
Appl.: Owner		
9	William B. Bilcheck	~
4	Chairman, Planning and Zoning Commission	
Received for Record	19	
at	hm 29i	
Signature of Town Cl	3 / 11 11 1	*
× "	FRM. SEPERMIT	6/91



TOWN OF MADISON

CONNECTICUT LAND USE OFFICE

8 CAMPUS DRIVE MADISON, CONNECTICUT 06443-2563 (203) 245-5632 FAX (203) 245-5613

May 24, 1999

CERTIFIED MAIL

North Madison Volunteer Fire Company, Inc. 864 Opening Hill Road Madison, CT 06443

Re: Application #99-26D: 864 OPENING HILL ROAD. Request for Modification of Special Exception Permit to allow relocation of the site for emergency generator, enlarge the fenced coumpound, change the style of the fence, add landscaping and permit Nextel Communications ands Sprint PCS to install radio equipment shelters inside the enlarged compound.

Gentlemen:

At their regular meeting on May 20, 1999, the Planning and Zoning Commission approved the application above referenced as presented at the meeting.

Before this Modification of Special Exception Permit will become effective, it is necessary to file a Certificate in the Land Records of the Town for which there is a \$10.00 filing fee. At your earliest convenience, please forward this amount to our office so that we may file this Certificate in your behalf. Your check should be made payable to the Town of Madison.

When this Certificate is filed at the end of the appeal period, you may apply for building permits through normal Building Department procedures.

Very truly yours,

William McMinn

Planning and Zoning Administrator

: drk

Copy to: Ronald C. Clark, Nextel Communications

M. 4 mm



STATE OF CONNECTICUT

CONNECTICUT SITING COUNCIL

10 Franklin Square New Britain, Connecticut 06051 Phone: (860) 827-2935 Fax: (860) 827-2950

July 1, 1997

Kenneth C. Baldwin Robinson & Cole One Commercial Plaza 280 Trumbull Street Hartford, CT 06103-3597

Cellco Partnership d/b/a Bell Atlantic NYNEX Mobile notice of intent to modify an existing Re: telecommunications facility located at 864 Opening Hill Road in Madison, Connecticut. Dear Mr. Baldwin:

At a public meeting held on June 30, 1997, the Connecticut Siting Council (Council) acknowledged your notice of intent to modify an existing telecommunications site in Madison, Connecticut, pursuant to Section

The proposed modifications are to be implemented as specified in your notice dated June 16, 1997. The modifications are in compliance with the exception criteria in Section 16-50j-72 (c)(1) of the Regulations of Connecticut State Agencies as changes to an existing non-facility site that would not cause a significant change or alteration in the physical and environmental characteristics of the site. This site has been carefully modeled to ensure that radio frequency emissions are conservatively below State and federal standards applicable to the frequency now used on this tower. Any additional change to this site will require explicit notice to this agency pursuant to Regulations of Connecticut State Agencies Section 16-50j-73. Such notice shall include all relevant information regarding the proposed change with cumulative worst-case modeling of radio frequency exposure at the closest point of uncontrolled access to the tower base, consistent with Federal Communications Commission, Office of Science and Technology, Bulletin No. 65. Any deviation from this format may result in the Council implementing enforcement proceedings pursuant to General Statutes \$ 16-50u including, without limitation, imposition of expenses resulting from such failure and of civil penalties in an amount not less than one thousand dollars per day for each day of

Thank you for your attention and cooperation.

Very truly yours,

Mortier de Gelelogen

Chairman

MAG/RKE/ss

c: Honorable Thomas Rylander, First Selectman, Town of Madison

Exhibit B

Property Card

864 OPENING HILL RD

Location 864 OPENING HILL RD

MBLU 134/17///

Unique ID# 00665700 Owner NORTH MADISON VOLUNTEER

FIRE COMPANY INC

Assessment \$938,700

Appraisal \$1,341,000

PID 7027 **Building Count** 1

Dev. Map

Current Value

Appraisal					
Valuation Year Building Extra Features Outbuildings Land Total					
2021	\$1,211,400	\$0	\$7,000	\$122,600	\$1,341,000
	Assessment				
Valuation Year	Building	Extra Features	Outbuildings	Land	Total
2021	\$848,000	\$0	\$4,900	\$85,800	\$938,700

Owner of Record

Owner Co-Owner NORTH MADISON VOLUNTEER FIRE COMPANY INC

Sale Price \$0

Care Of

Book & Page 0044/0130

Sale Date

Ownership History

Ownership History				
Owner	Sale Price	Book & Page	Sale Date	
NORTH MADISON VOLUNTEER FIRE COMPANY INC	\$0	0044/0130		

Building Information

Building 1: Section 1

Year Built:

1971

Living Area:

10,480

Building Attributes	
Field	Description

Style:	Fire Station
Model	Commercial
Grade	Average
Stories:	2
Occupancy	1.00
Exterior Wall 1	Brick Veneer
Exterior Wall 2	Vinyl Siding
Roof Structure	Gambrel
Roof Cover	Asphalt Shngl.
Interior Wall 1	Minim/Masonry
Interior Wall 2	Plywood Panel
Interior Floor 1	Concr-Finished
Interior Floor 2	Carpet
Heating Fuel	Oil
Heating Type	Hot Water
AC Type	None
Struct Class	
Bldg Use	Municipal Fire
Total Rooms	
Total Bedrms	00
Total Baths	0
Fireplace	
Xtra Fireplaces	
1st Floor Use:	903L
Heat/AC	None
Frame Type	Masonary
Baths/Plumbing	Average
Ceiling/Wall	None
Rooms/Prtns	Average
Wall Height	10.00
% Comn Wall	0.00

Building Photo



(https://images.vgsi.com/photos/MadisonCTPhotos/\01\01\79\69.jpg)

Building Sub-Areas (sq ft)				
Code	Description	Gross Area	Living Area	
FUS	Finished Upper Story	6,000	6,000	
BAS	First Floor	4,480	4,480	
FGR	Garage	1,520	0	
UGR	Basement Garage	1,520	0	
		13,520	10,480	

Extra Features

Extra Features
No Data for Extra Features

Land

Land Use Land Line Valuation

Use Code 903L **Size (Acres)** 0.38


Description Municipal Fire IblIndfront

Zone RU-1

Outbuildings

Outbuildings						
Code	Description	Sub Code	Sub Description	Size	Value	Bldg #
PAV1	Paving Asphalt			10000.00 S.F.	\$7,000	1

(c) 2022 Vision Government Solutions, Inc. All rights reserved.



864 Opening Hill Rd, Madison, CT 06443

Exhibit C

Construction Drawings

CONSTRUCTION DRAWINGS

ALL SCALES RELATIVE TO 24"X36" PAGE SIZE

ELEVATED **ENGINEERING**

35 GRIFFIN ROAD SOUTH BLOOMFIELD, CT 06002

BOONTON, NEW JERSEY 07005

Documents prepared by Elevated Engineering including this document, are to be used only for the specific project and specific use for which they were intended. Any extension of use to any other projects, by owner or by any other party, without the expressed written consent of Elevated Engineering, is done unlawfully and at the users own risk. If used in a way other than that specifically intended, user will hold Elevated Engineering, harmless from all claims and losses.

SCHEDULE OF REVISIONS REVISED PER CLIENT COMMENTS 12/09/24 REVISED PER SA 11/27/24 ISSUED AS FINALS 11/22/24 INITIAL SUBMISSION

DESCRIPTION OF CHANGES

DRAWN BY: CJT **CHECKED BY:** NDB

SCALE: AS NOTED 24045-NSS

INFORMATION ON THIS SET OF DRAWINGS IS NOT FOR OFFICIAL USE UNLESS ACCOMPANIED BY THE STAMPED SEAL & SIGNATURE OF A PROFESSIONAL ENGINEER



NICHOLAS D. BARILE

PROFESSIONAL ENGINEER, CT LIC. No. 28643

SITE ID: CT11394A NORTH MADISON 864 OPENING HILL RD MADISON, CT 06443 **NEW HAVEN COUNTY**

DRAWING TITLE:

TITLE SHEET

DRAWING SHEET:

T-MOBILE NORTHEAST LLC

RADIO UPGRADE 4460

SITE #: CT11394A SITE NAME: NORTH MADISON 864 OPENING HILL ROAD MADISON, CT 06443 **NEW HAVEN COUNTY**

RAN CONFIGURATION: 67E998E 6160 (GSM ON 6630)

A&L CONFIGURATION: N/A

DATE

DATE

DATE

DATE

DATE

DATE

THIS DOCUMENT IS THE CREATION, DESIGN, PROPERTY, AND COPYRIGHTED WORK OF T-MOBILE. ANY DUPLICATION OR USE WITHOUT EXPRESS WRITTEN CONSENT IS STRICTLY PROHIBITED. DUPLICATION AND USE BY GOVERNMENT AGENCIES FOR THE PURPOSES OF CONDUCTING THEIR LAWFULLY AUTHORIZED REGULATORY AND ADMINISTRATIVE FUNCTIONS IS SPECIFICALLY ALLOWED.

GENERAL NOTES

THE FACILITY IS AN UNMANNED, PRIVATE, AND SECURED EQUIPMENT INSTALLATION. IT IS ONLY ACCESSED BY TRAINED TECHNICIANS FOR PERIODIC ROUTINE MAINTENANCE AND, THEREFORE, DOES NOT REQUIRE ANY WATER OR SANITARY SEWER SERVICE. THE FACILITY IS NOT GOVERNED BY REGULATIONS REQUIRING PUBLIC ACCESS PER ADA REQUIREMENTS.

CONTRACTOR SHALL VERIFY ALL PLANS AND EXISTING DIMENSIONS AND CONDITIONS ON THE JOB SITE AND SHALL IMMEDIATELY NOTIFY THE T-MOBILE NORTHEAST, LLC REPRESENTATIVE IN WRITING OF DISCREPANCIES BEFORE PROCEEDING WITH THE WORK OR BE RESPONSIBLE FOR

SPECIAL STRUCTURAL NOTES

STRUCTURE OWNER SHALL BE RESPONSIBLE FOR GLOBAL STRUCTURAL STABILITY ANALYSIS OF EXISTING SUPPORT STRUCTURE. GENERAL CONTRACTOR SCOPE OF WORK SHALL INCLUDE ALL REQUIRED STRUCTURAL MODIFICATIONS, RE-BUNDLING OF COAXIAL CABLES OR OTHER SPECIAL MODIFICATIONS AS OUTLINED THEREIN.

STRUCTURAL DESIGNS AND DETAILS FOR ANTENNA MOUNTS COMPLETED BY ELEVATED ENGINEERING, PLLC ON BEHALF OF T-MOBILE ARE INCLUSIVE OF THE ENTIRE ANTENNA SUPPORT STRUCTURE (GLOBAL STRUCTURAL STABILITY ANALYSIS BY OTHERS), EXISTING PLATFORM, EXISTING ANTENNA MOUNTS, AND ALL OTHER ASPECTS OF THE STRUCTURE THAT WILL SUPPORT THE T-MOBILE EQUIPMENT DEPLOYMENT AS DEPICTED HEREIN.

ELEVATED ENGINEERING, PLLC ASSUMES THAT THE STRUCTURE IS PROPERLY CONSTRUCTED AND MAINTAINED. ALL STRUCTURAL MEMBERS AND THEIR CONNECTIONS ARE ASSUMED TO BE IN GOOD CONDITION AND ARE FREE FROM DEFECTS WITH NOT DETERIORATION TO IT'S MEMBER CAPACITIES.

APPROVALS

PROJECT MANAGER

CONSTRUCTION

RF ENGINEERING

OPERATIONS

OWNER

ZONING / SITE ACQUISITION



KEY MAP



UNDERGROUND SERVICE ALERT

Know what's **below.** Call before you dig.

CALL TOLL FREE: 800-922-4455

SITE CHARACTERISTICS

SITE LOCATION INFORMATION

864 OPENING HILL ROAD

NORTH MADISON VOLUNTARY

T-MOBILE NORTHEAST LLC

35 GRIFFIN ROAD SOUTH

BLOOMFIELD, CT 06002

AMERICAN TOWER CORPORATION (SITE ID: 383660)

MADISON, CT 06443

TOWN OF MADISON

1255 DURHAM RD.

MADISON, CT 06443

CT11394A

NEW HAVEN

-72.638773° LONGITUDE: SELF SUPPORT TOWER STRUCTURE TYPE:

SITE NUMBER:

SITE ADDRESS:

JURISDICTION:

TOWER OWNER:

APPLICANT:

LATITUDE:

SHEET

TITLE SHEET

ELEVATION

GENERAL NOTES

COMPOUND PLAN

GROUNDING DETAILS & NOTES

PROPERTY OWNER:

COUNTY:

LOCATION OF EQUIPMENT: CONCRETE PAD (AT GRADE)

±197'-0" AGL (TOP OF HIGHEST APPURTENANCE) STRUCTURE HEIGHT:

41.357381°

ANTENNA (RAD CENTER) ALPHA $-\pm 130'-0"$ AGL BETA $-\pm 130'-0''$ AGL

 $GAMMA - \pm 130' - 0" AGL$

SHEET INDEX

SHEET DESCRIPTION

EXISTING/FINAL EQUIPMENT PLAN & EXISTING/FINAL ANTENNA PLANS

GENERAL NOTES

1. FOR THE PURPOSE OF THE CONSTRUCTION DRAWING, THE FOLLOWING DEFINITIONS SHALL APPLY:

CONTRACTORS — TO BE DETERMINED SUBCONTRACTOR — GENERAL CONTRACTOR (CONSTRUCTION) OWNER — T-MOBILE

- 2. PRIOR TO THE SUBMISSION OF BIDS, THE BIDDING SUBCONTRACTOR SHALL VISIT THE CELL SITE TO FAMILIARIZE WITH THE EXISTING CONDITIONS AND TO CONFIRM THAT THE WORK CAN BE ACCOMPLISHED AS SHOWN ON THE CONSTRUCTION DRAWINGS. ANY DISCREPANCY FOUND SHALL BE BROUGHT TO THE ATTENTION OF THE CONTRACTOR.
- 3. ALL MATERIALS FURNISHED AND INSTALLED SHALL BE IN STRICT ACCORDANCE WITH ALL APPLICABLE CODES, REGULATIONS AND ORDINANCES. SUBCONTRACTOR SHALL ISSUE ALL APPROPRIATE NOTICES AND COMPLY WITH ALL LAWS, ORDINANCES, RULES, REGULATIONS AND LAWFUL ORDERS OF ANY PUBLIC AUTHORITY REGARDING THE PERFORMANCE OF THE WORK. ALL WORK CARRIED OUT SHALL COMPLY WITH ALL APPLICABLE MUNICIPAL AND UTILITY COMPANY SPECIFICATIONS AND LOCAL JURISDICTIONAL CODES, ORDINANCES AND APPLICABLE REGULATIONS.
- 4. DRAWINGS PROVIDED HERE ARE NOT TO BE SCALED AND ARE INTENDED TO SHOW OUTLINE ONLY.
- 5. UNLESS NOTED OTHERWISE, THE WORK SHALL INCLUDE FURNISHING MATERIALS, EQUIPMENT APPURTENANCES, AND LABOR NECESSARY TO COMPLETE ALL INSTALLATIONS AS INDICATED ON THE DRAWINGS.
- 6. "KITTING LIST" SUPPLIED WITH THE BID PACKAGE IDENTIFIES ITEMS THAT WILL BE SUPPLIED BY CONTRACTOR. ITEMS NOT INCLUDED IN THE BILL OF MATERIALS AND KITTING LIST SHALL BE PROVIDED BY THE SUBCONTRACTOR.
- 7. THE SUBCONTRACTOR SHALL INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURERS RECOMMENDATIONS UNLESS SPECIFICALLY STATED OTHERWISE.
- 8. IF THE SPECIFIED EQUIPMENT CANNOT BE INSTALLED AS SHOWN ON THESE DRAWINGS, THE SUBCONTRACTOR SHALL PROPOSED AND ALTERNATIVE INSTALLATION SPACE FOR APPROVAL BY CONTRACTOR.

- 9. SUBCONTRACTOR SHALL DETERMINE ACTUAL ROUTING OF CONDUIT, POWER AND T1 CABLES, GROUNDING CABLES AS SHOWN ON THE POWER, GROUNDING AND TELCO PLAN DRAWING. SUBCONTRACTOR SHALL UTILIZE EXISTING TRAYS AND/OR SHALL ADD NEW TRAYS AS NECESSARY. SUBCONTRACTOR SHALL CONFIRM THE ACTUAL ROUTING WITH THE CONTRACTOR.
- 10. THE SUBCONTRACTOR SHALL PROTECT THE EXISTING IMPROVEMENTS, PAVEMENTS, CURBS, LANDSCAPING AND STRUCTURES. ANY DAMAGED PART SHALL BE REPAIRED AT SUBCONTRACTORS EXPENSE TO THE SATISFACTION OF OWNER.
- 11. SUBCONTRACTOR SHALL LEGALLY AND PROPERLY DISPOSE OF ALL SCRAP MATERIAL SUCH AS COAXIAL CABLE AND OTHER ITEMS REMOVED FROM THE EXISTING FACILITY. ANTENNAS REMOVED SHALL BE RETURNED TO THE OWNERS DESIGNATED LOCATION.
- 12. SUBCONTRACTOR SHALL LEAVE PREMISES IN CLEAN CONDITION.
- 13. ALL CONCRETE REPAIR WORK SHALL BE DONE IN ACCORDANCE WITH AMERICAN CONCRETE INSTITUTE (ACI) 301.
- 14. ANY NEW CONCRETE NEEDED FOR THE CONSTRUCTION SHALL BE AIR—ENTRAINED AND SHALL HAVE 4000 PSI STRENGTH AT 28 DAYS. ALL CONCRETE WORK SHALL BE DONE IN ACCORDANCE WITH ACI 318 CODE REQUIREMENTS.
- 15. ALL STRUCTURAL STEEL WORK SHALL BE DETAILED, FABRICATED AND ERECTED IN ACCORDANCE WITH AISC SPECIFICATIONS. ALL STRUCTURAL STEEL SHALL BE ASTM A36 (Fy = 36 ksi) UNLESS OTHERWISE NOTED. PIPES SHALL BE ASTM A53 TYPE E (Fy = 36 ksi). ALL STEEL EXPOSED TO WEATHER SHALL BE HOT DIPPED GALVANIZED. TOUCH UP ALL SCRATCHED AND OTHER MARKS IN THE FIELD AFTER STEEL IS ERECTED USING A COMPATIBLE ZINC RICH PAINT.
- 16. CONSTRUCTION SHALL COMPLY WITH UMTS SPECIFICATIONS AND "GENERAL CONSTRUCTION SERVICES FOR CONSTRUCTION OF T-MOBILE SITES."
- 17. SUBCONTRACTORS SHALL VERIFY ALL EXISTING DIMENSIONS AND CONDITIONS PRIOR TO COMMENCING ANY WORK. ALL DIMENSIONS OF EXISTING CONSTRUCTION SHOWN ON THE DRAWINGS MUST BE VERIFIED. SUBCONTRACTOR SHALL NOTIFY THE CONTRACTOR OF ANY DISCREPANCIES PRIOR TO ORDERING MATERIAL OR PROCEEDING WITH CONSTRUCTION.

- 18. THE EXISTING CELL SITE IS ACTIVE, ALL SAFETY PRECAUTIONS MUST BE TAKEN WHEN WORKING AROUND HIGH LEVELS OF ELECTROMAGNETIC RADIATION. EQUIPMENT SHOULD BE SHUTDOWN PRIOR TO PERFORMING ANY WORK THAT COULD EXPOSE THE WORKERS TO DANGER. PERSONAL RF EXPOSURE MONITORS ARE ADVISED TO BE WORN TO ALERT OF ANY DANGEROUS EXPOSURE LEVELS.
- 19. APPLICABLE BUILDING CODES:

SUBCONTRACTORS WORK SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE AND LOCAL CODES AS ADOPTED BY THE LOCAL AUTHORITY HAVING JURISDICTION (AHJ) FOR THE LOCATION. THE EDITION OF THE AHJ ADOPTED CODES AND STANDARDS IN EFFECT ON THE DATE OF CONTRACT AWARD SHALL GOVERN THE DESIGN.

- BUILDING CODE: 2022 CONNECTICUT STATE BUILDING CODE
- ELECTRICAL CODE: NFPA 70 NATIONAL ELECTRICAL CODE, 2017 EDITION
 LIGHTNING CODE: NFPA 780—2014 LIGHTNING PROTECTION CODE
- LIGHTNING CODE: NFPA 780-2014 LIGHTNING PROTECTION CODE

SUBCONTRACTORS WORK SHALL COMPLY WITH THE LATEST EDITION OF THE FOLLOWING STANDARDS:

- AMERICAN CONCRETE INSTITUTE (ACI) 318; BUILDING CODE REQUIREMENT FOR STRUCTURAL CONCRETE
- AMERICAN INSTITUTE FOR STEEL CONSTRUCTION (AISC)
- MANUAL OF STEEL CONSTRUCTION, ASD, NINTH EDITION
- TELECOMMUNICATIONS INDUSTRY ASSOCIATION (TIA) 222-H, STRUCTURAL STANDARDS FOR STEEL
- ANTENNA TOWER AND ANTENNA SUPPORTING STRUCTURES; REFER TO ELECTRICAL DRAWINGS FOR SPECIFIC ELECTRICAL STANDARDS.

FOR ANY CONFLICTS BETWEEN SECTIONS OF LISTED CODES AND STANDARDS REGARDING MATERIAL, METHODS OF CONSTRUCTION, OR OTHER REQUIREMENTS, THE MOST RESTRICTIVE REQUIREMENT SHALL GOVERN. WHERE THERE IS A CONFLICT BETWEEN A GENERAL REQUIREMENT, THE SPECIFIC REQUIREMENT SHALL GOVERN.

ELECTRICAL & GROUNDING NOTES

- 1. THE SUBCONTRACTOR SHALL REVIEW AND INSPECT THE EXISTING FACILITY GROUNDING SYSTEM AND LIGHTNING PROTECTION SYSTEM (AS DESIGNED AND INSTALLED) FOR STRICT COMPLIANCE WITH THE NEC (AS ADOPTED BY THE AHJ), THE SITE SPECIFIC (UL, LPI, OR NFPA) LIGHTNING PROTECTION CODE, AND GENERAL COMPLIANCE WITH TELCORDIA AND TIA GROUNDING STANDARDS. THE SUBCONTRACTOR SHALL REPORT ANY VIOLATIONS OR ADVERSE FINDINGS TO THE CONTRACTOR FOR RESOLUTION.
- 2. ALL GROUND ELECTRODE SYSTEMS (INCLUDING TELECOMMUNICATION, RADIO LIGHTNING PROTECTION AND AS POWER GES'S) SHALL BE BONDED TOGETHER, AT OR BELOW GRADE, BY TWO OR MORE COPPER BONDING CONDUCTORS IN ACCORDANCE WITH THE NEC
- 3. THE SUBCONTRACTOR SHALL PERFORM IEEE FALL—OF—POTENTIAL RESISTANCE TO EARTH TESTING (PER IEEE 1100 AND 81) FOR NEW GROUND ELECTRODE SYSTEMS. THE SUBCONTRACTOR SHALL FURNISH AND INSTALL SUPPLEMENTAL GROUND ELECTRODES AS NEEDED TO ACHIEVE A TEST RESULT OF 5 OHMS OR LESS.
- 4. METAL RACEWAY SHALL NOT BE USED AS THE NEC REQUIRED EQUIPMENT GROUND CONDUCTOR. STRANDED COPPER CONDUCTORS WITH GREEN INSULATION, SIZED IN ACCORDANCE WITH THE NEC, SHALL BE FURNISHED AND INSTALLED WITH THE POWER CIRCUITS TO THE BTS EQUIPMENT.
- 5. EACH BTS CABINET FRAME SHALL BE DIRECTLY CONNECTED TO THE MASTER GROUND BAR WITH GREEN INSULATED SUPPLEMENTAL EQUIPMENT GROUND WIRES, 6 AWG STRANDED COPPER OR LARGER FOR INDOOR BTS 2 AWG STRANDED COPPER FOR OUTDOOR BTS.
- 6. EXOTHERMIC WELDS SHALL BE USED FOR ALL GROUNDING CONNECTIONS BELOW GRADE.
- 7. APPROVED ANTIOXIDANT COATING (I.E. CONDUCTIVE GEL OR PASTE) SHALL BE USED ON ALL COMPRESSION AND BOLTED GROUND CONNECTIONS.
- 8. ICE BRIDGE BONDING CONDUCTORS SHALL BE EXOTHERMICALLY BONDED OR BOLTED TO THE BRIDGE AND THE TOWER GROUND BAR.
- 9. ALUMINUM CONDUCTOR OR COPPER CLAD STEEL CONDUCTOR SHALL NOT BE USED FOR GROUNDING CONNECTIONS.
- 10. MISCELLANEOUS ELECTRICAL AND NON-ELECTRICAL METAL BOXES, FRAMES AND SUPPORTS SHALL BE BONDED TO THE GROUND RING, IN ACCORDANCE WITH THE NEC.

- 11. METAL CONDUIT SHALL BE MADE ELECTRICALLY CONTINUOUS WITH LISTED BONDING FITTINGS OR BY BONDING ACROSS THE DISCONTINUITY WITH 6 AWS COPPER WIRE UL APPROVED GROUNDING TYPE CONDUIT CLAMPS.
- 12. ALL NEW STRUCTURE WITH A FOUNDATION AND/OR FOOTING HAVING 20 FT. OR MORE OF 1/2 IN. OR GREATER ELECTRICALLY CONDUCTIVE REINFORCING RING USING AN EXOTHERMIC WELD CONNECTION USING #2 AWG SOLID BARE TINNED COPPER GROUND WIRE, PER NEC 250.50.
- 13. ALL ELECTRICAL WORK SHALL CONFORM TO THE REQUIREMENTS OF THE NATIONAL ELECTRICAL CODE (NEC) AS WELL AS APPLICABLE STATE AND LOCAL CODES.
- 14. ALL ELECTRICAL ITEMS SHALL BE U.L. APPROVED OR LISTED AND PROCURED PER SPECIFICATION REQUIREMENTS.
- 15. THE ELECTRICAL WORK INCLUDES ALL LABOR AND MATERIAL DESCRIBED BY DRAWINGS AND SPECIFICATIONS INCLUDING INCIDENTAL WORK TO PROVIDE COMPLETE OPERATING AND APPROVED ELECTRICAL SYSTEM.
- 16. GENERAL CONTRACTOR SHALL PAY FEES FOR PERMITS, AND IS RESPONSIBLE FOR OBTAINING SAID PERMITS AND COORDINATION OF INSPECTIONS.
- 17. ELECTRICAL AND TELCO WIRING OUTSIDE A BUILDING AND EXPOSED TO WEATHER SHALL BE IN WATER TIGHT GALVANIZED RIGID STEEL CONDUITS OR SCHEDULE 80 PVC (AS PERMITTED BY CODE) AND WHERE REQUIRED IN LIQUID TIGHT FLEXIBLE METAL OR NONMETALLIC CONDUITS.
- 18. RIGID STEEL CONDUITS SHALL BE GROUNDED AT BOTH ENDS.
- 19. ELECTRICAL WIRING SHALL BE COPPER WITH TYPE XHHW, THWN OR THIN INSULATION.
- 20. RUN ELECTRICAL CONDUIT OR CABLE BETWEEN ELECTRICAL ROOM AND PROPOSED CELL SITE POWER PEDESTAL AS INDICATED ON THIS DRAWING. PROVIDE FULL LENGTH PULL ROPE. COORDINATE INSTALLATION WITH UTILITY COMPANY.
- 21. RUN TELCO CONDUIT OR CABLE BETWEEN TELEPHONE UTILITY DEMARCATION POINT AND PROPOSED CELL SITE TELCO CABINET AND BTS CABINET AS INDICATED ON DRAWING A-1. PROVIDE FULL LENGTH PULL ROPE IN INSTALLED TELCO CONDUIT. PROVIDE GREENLEE CONDUIT MEASURING TAPE AT EACH END.
- 22. ALL EQUIPMENT LOCATED OUTSIDE SHALL HAVE NEMA 3R ENCLOSURE.

- 23. GROUNDING SHALL COMPLY WITH NEW ART. 250.
- 24. GROUND COAXIAL CABLE SHIELDS MINIMUM AT BOTH ENDS USING MANUFACTURERS COAX CABLE GROUNDING KITS SUPPLIED BY PROJECT OWNER.
- 25. USE #6 COPPER STRANDED WIRE WITH GREEN COLOR INSULATION FOR ABOVE GRADE GROUNDING (UNLESS OTHERWISE SPECIFIED) AND #2 SOLID TINNED BARE COPPER WIRE FOR BELOW GRADE GROUNDING AS INDICATED ON DRAWING.
- 26. ALL GROUND CONNECTIONS TO BE BURNDY HYGROUND COMPRESSION TYPE CONNECTORS OR CADWELD EXOTHERMIC WELD. DO NOT ALLOW BARE COPPER WIRE TO BE IN CONTACT WITH GALVANIZED STEEL.
- 27. ROUTE GROUNDING CONDUCTORS ALONG THE SHORTEST AND STRAIGHTEST PATH POSSIBLE EXCEPT AS OTHERWISE INDICATED. GROUNDING LEADS SHOULD NEVER BE BENT AT RIGHT ANGLE. ALWAYS MAKE AT LEAST 12" RADIUS BENDS. #6 WIRE CAN BE BENT AT 6" RADIUS WHEN NECESSARY. BOND ANY METAL OBJECTS WITHIN 7 FEET OF PROPOSED EQUIPMENT OR CABINET TO MASTER GROUND BAR.
- 28. CONNECTIONS TO MGB SHALL BE ARRANGED IN THREE MAIN GROUPS: SURGE PRODUCERS (COAXIAL CABLE GROUND KITS, TELCO AND POWER PANEL GROUND); (GROUNDING ELECTRODE RING OR BUILDING STEEL); NON-SURGING OBJECTS (EGB GROUND IN BTS UNIT)
- 29. CONNECTIONS TO GROUND BARS SHALL BE MADE WITH TWO HOLE COMPRESSION TYPE COPPER LUGS. APPLY OXIDE INHIBITING COMPOUND TO ALL LOCATIONS.
- 30. BOND ANTENNA MOUNTING BRACKETS. COAXIAL CABLE GROUND KITS AND ALNA TO EGB PLACES NEAR THE ANTENNA LOCATION.
- 31. BOND ANTENNA EGB'S AND MGB TO WATER MAIN.
- 32. TEST COMPLETED GROUND SYSTEM AND RECORD RESULTS FOR PROJECT CLOSE—OUT DOCUMENTATION.
- 33. BOND ANY METAL OBJECTS WITHIN 7 FEET OF PROPOSED EQUIPMENT OR CABINET TO MASTER GROUND BAR.
- 34. VERIFY PROPOSED SERVICE UPGRADE WITH LOCAL UTILITY COMPANY PRIOR TO CONSTRUCTION.

ABBREVIATIONS ABOVE GRADE LEVEL G.C. GENERAL CONTRACTOR RADIO FREQUENCY AMERICAN WIRE GAUGE MGB MASTER GROUND BUS BARE COPPER WIRE TO BE DETERMINED MIN MINIMUM TBD PROPOSED BASE TRANSCEIVER STATION TO BE REMOVED TBRR TO BE REMOVED EXISTING EXISTING N.T.S. NOT TO SCALE AND REPLACED EQUIPMENT GROUND REFERENCE REF TYP TYPICAL EQUIPMENT GROUND RING REQ REQUIRED



35 GRIFFIN ROAD SOUTH BLOOMFIELD, CT 06002

ELEVATED ENGINEERING

99 FANNY ROAD

BOONTON, NEW JERSEY 07005

862-242-8050

Documents prepared by Elevated Engineering, including this document, are to be used only for the specific project and specific use for which they were intended. Any extension of use to any other projects, by owner or by any other party, without the expressed written consent of Elevated Engineering, is done unlawfully and at the users own risk. If used in a way other than that specifically intended, user will hold Elevated Engineering, harmless from all claims and losses.

REV. NO.	DATE	DESCRIPTION OF CHANGES
0	11/22/24	INITIAL SUBMISSION
1	11/27/24	ISSUED AS FINALS
2	12/09/24	REVISED PER SA
3	12/24/24	REVISED PER CLIENT COMMENT
4		
5		
6		
7		
SCHEDULE OF REVISIONS		

DRAWN BY: CJT

CHECKED BY: NDB


SCALE: AS NOTED

JOB NO: 24045-NSS

INFORMATION ON THIS SET OF DRAWINGS IS

NOT FOR OFFICIAL USE UNLESS

ACCOMPANIED BY THE STAMPED SEAL &
SIGNATURE OF A PROFESSIONAL ENGINEER



NICHOLAS D. BARILE
PROFESSIONAL ENGINEER, CT LIC. No. 28643


SITE ID: CT11394A
NORTH MADISON
864 OPENING HILL RD
MADISON, CT 06443
NEW HAVEN COUNTY

DRAWING TITLE:

GENERAL NOTES

DRAWING SHEET:

GN-1



T-MODILE NORTHEAST LLC

35 GRIFFIN ROAD SOUTH BLOOMFIELD, CT 06002

ELEVATED

ENGINEERING

99 FANNY ROAD
BOONTON, NEW JERSEY 07005
862-242-8050

Documents prepared by Elevated Engineering, including this document, are to be used only for the specific project and specific use for which they were intended. Any extension of use to any other projects, by owner or by any other party, without the expressed written consent of Elevated Engineering, is done unlawfully and at the users own risk. If used in a way other than that specifically intended, user will hold Elevated Engineering, harmless from all claims and losses.

	SCI	HEDULE OF REVISIONS
7		
6		
5		
4		
3	12/24/24	REVISED PER CLIENT COMMEN
2	12/09/24	REVISED PER SA
1	11/27/24	ISSUED AS FINALS
0	11/22/24	INITIAL SUBMISSION
REV. NO.	DATE	DESCRIPTION OF CHANGES

DRAWN BY:	CJT
CHECKED BY:	NDB
SCALE:	AS NOTED
JOB NO:	24045-NSS

INFORMATION ON THIS SET OF DRAWINGS IS NOT FOR OFFICIAL USE UNLESS ACCOMPANIED BY THE STAMPED SEAL & SIGNATURE OF A PROFESSIONAL ENGINEER



NICHOLAS D. BARILE

PROFESSIONAL ENGINEER, CT LIC. No. 28643

SITE ID: CT11394A
NORTH MADISON
864 OPENING HILL RD
MADISON, CT 06443
NEW HAVEN COUNTY


DRAWING TITLE:

COMPOUND PLAN

DRAWING SHEET:

A-1

LOADING SHOWN WITHIN THIS SET OF DRAWINGS IS BASED ON THE STRUCTURAL ANALYSIS PERFORMED BY ELEVATED ENGINEERING, DATED DECEMBER 9, 2024. CONTRACTOR TO NOTIFY ENGINEER AND CARRIER IN THE EVENT SITE CONDITIONS DIFFER FROM WHAT IS REPRESENTED IN THE ANALYSIS. NO SUBSTITUTIONS ARE PERMITTED WITHOUT ADDITIONAL ANALYSIS.



T - Mobile

T-MOBILE NORTHEAST LLC

35 GRIFFIN ROAD SOUTH BLOOMFIELD, CT 06002

ELEVATED ENGINEERING

99 FANNY ROAD BOONTON, NEW JERSEY 07005 862-242-8050

Documents prepared by Elevated Engineering, including this document, are to be used only for the specific project and specific use for which they were intended. Any extension of use to any other projects, by owner or by any other party, without the expressed written consent of Elevated Engineering, is done unlawfully and at the users own risk. If used in a way other than that specifically intended, user will hold Elevated Engineering, harmless from all claims and losses.

SCHEDULE OF REVISIONS		
7		
6		
5		
4		
3	12/24/24	REVISED PER CLIENT COMMENT
2	12/09/24	REVISED PER SA
1	11/27/24	ISSUED AS FINALS
0	11/22/24	INITIAL SUBMISSION
REV. NO.	DATE	DESCRIPTION OF CHANGES
DRA	WN BY:	CJT

INFORMATION ON THIS SET OF DRAWINGS IS

NOT FOR OFFICIAL USE UNLESS

ACCOMPANIED BY THE STAMPED SEAL &
SIGNATURE OF A PROFESSIONAL ENGINEER

NDB

AS NOTED

24045-NSS

CHECKED BY:

SCALE:

JOB NO:



NICHOLAS D. BARILE
PROFESSIONAL ENGINEER, CT LIC. No. 28643

SITE ID: CT11394A

NORTH MADISON

864 OPENING HILL RD

MADISON, CT 06443

NEW HAVEN COUNTY


DRAWING TITLE:

ELEVATION

DRAWING SHEET:

A-2

LOADING SHOWN WITHIN THIS SET OF DRAWINGS IS
BASED ON THE STRUCTURAL ANALYSIS PERFORMED BY
ELEVATED ENGINEERING, DATED DECEMBER 9, 2024.
CONTRACTOR TO NOTIFY ENGINEER AND CARRIER IN THE
EVENT SITE CONDITIONS DIFFER FROM WHAT IS
REPRESENTED IN THE ANALYSIS. NO SUBSTITUTIONS ARE
PERMITTED WITHOUT ADDITIONAL ANALYSIS.



LOADING SHOWN WITHIN THIS SET OF DRAWINGS IS BASED ON THE STRUCTURAL ANALYSIS PERFORMED BY

ELEVATED ENGINEERING, DATED DECEMBER 9, 2024.
CONTRACTOR TO NOTIFY ENGINEER AND CARRIER IN THE
EVENT SITE CONDITIONS DIFFER FROM WHAT IS
REPRESENTED IN THE ANALYSIS. NO SUBSTITUTIONS ARE
PERMITTED WITHOUT ADDITIONAL ANALYSIS.

FINAL ANTENNA PLAN

<u>EXISTING ANTENNA PLAN</u>

T-Mobile Northeast LLC

35 GRIFFIN ROAD SOUTH BLOOMFIELD, CT 06002

ELEVATED
ENGINEERING
99 FANNY ROAD

BOONTON, NEW JERSEY 07005 862-242-8050

Documents prepared by Elevated Engineering, including this document, are to be used only for the specific project and specific use for which they were intended. Any extension of use to any other projects, by owner or by any other party, without the expressed written consent of Elevated Engineering, is done unlawfully and at the users own risk. If used in a way other than that specifically intended, user will hold Elevated Engineering, harmless from all claims and losses.

	SCHEDULE OF REVISIONS								
7									
6									
5									
4									
3	12/24/24	REVISED PER CLIENT COMMENTS							
2	12/09/24	REVISED PER SA							
1	11/27/24	ISSUED AS FINALS							
0	11/22/24	INITIAL SUBMISSION							
REV.	DATE	DESCRIPTION OF CHANGES							

DRAWN BY:	CJT
CHECKED BY:	NDB
SCALE:	AS NOTED
JOB NO:	24045-NSS

INFORMATION ON THIS SET OF DRAWINGS IS

NOT FOR OFFICIAL USE UNLESS

ACCOMPANIED BY THE STAMPED SEAL &
SIGNATURE OF A PROFESSIONAL ENGINEER



NICHOLAS D. BARILE

PROFESSIONAL ENGINEER, CT LIC. No. 28643


SITE ID: CT11394A
NORTH MADISON
864 OPENING HILL RD
MADISON, CT 06443
NEW HAVEN COUNTY

DRAWING TITLE:

EXISTING/FINAL EQUIPMENT PLAN & EXISTING/FINAL ANTENNA PLANS


DRAWING SHEET:

A-3




COMMSCOPE: HBXX-9014DS-A2M A-4 | SCALE: N.T.S.

DETAIL NOT USED A-4 SCALE: N.T.S.



TYPICAL ANTENNA INSTALLATION DETAIL A-4 SCALE: N.T.S.



<u>RRH</u>	<u>HEIGHT</u>	<u>WIDTH</u>	<u>DEPTH</u>	<u>WEIGHT</u>
RADIO 4460 B25+B66	17.0"	15.1"	11.9"	104 LBS.

4 RRU DETAILS A-4 SCALE: N.T.S.

T-MOBILE NORTHEAST LLC

35 GRIFFIN ROAD SOUTH BLOOMFIELD, CT 06002

ELEVATED ENGINEERING 99 FANNY ROAD BOONTON, NEW JERSEY 07005 862-242-8050

Documents prepared by Elevated Engineering, including this document, are to be used only for the specific project and specific use for which they were intended. Any extension of use to any other projects, by owner or by any other party, without the expressed written consent of Elevated Engineering, is done unlawfully and at the users own risk. If used in a way other than that specifically intended, user will hold Elevated Engineering, harmless from all claims and losses.

SCHEDULE OF REVISIONS

REV.	DATE	DESCRIPTION OF CHANGES
0	11/22/24	INITIAL SUBMISSION
1	11/27/24	ISSUED AS FINALS
2	12/09/24	REVISED PER SA
3	12/24/24	REVISED PER CLIENT COMMENTS
4		
5		
6		
7		

DRAWN BY:	CJT
CHECKED BY:	NDB
SCALE:	AS NOTED
JOB NO:	24045-NSS

INFORMATION ON THIS SET OF DRAWINGS IS NOT FOR OFFICIAL USE UNLESS ACCOMPANIED BY THE STAMPED SEAL & SIGNATURE OF A PROFESSIONAL ENGINEER




NICHOLAS D. BARILE PROFESSIONAL ENGINEER, CT LIC. No. 28643


SITE ID: CT11394A **NORTH MADISON** 864 OPENING HILL RD MADISON, CT 06443 **NEW HAVEN COUNTY**

DRAWING TITLE:

DETAILS

DRAWING SHEET:






ERICSSON: B160 CABINET A-4 SCALE: N.T.S.

				-	NTENN	IA INFORM	ATION							
	POSITION				PROPOSED									
SECTOR	(FROM REAR LEFT TO RIGHT)	MODEL	QTY.	MODEL	ANT. C.L.	SECTOR MARK	QTY.	E-TILT	M-TILT	RRU MODEL/QUANTITY	COAX/ FIBER QUANTITY	COAX/ FIBER	COAX/ FIBER LENGTH	HCS QTY / SIZE / LENGTH
	R1	_	_	-	_	_	_	-	_	-	_	-	_	_
ALPHA	R2	APXVAARR24_43-U-NA20	1	APXVAARR24_43-U-NA20	130'-0"	N600/L700/ L1900/G1900	1	2/2/2/2	0	(1) 4449 B71+B85	4 2	COAX JUMPER FIBER JUMPER	15' 15'	-
40°	R3	_	_	_	_	_	-	_	_	_	_	-	_	-
	R4	RR90-17-00DPL2	1	HBXX-9014DS-A2M	130'-0"	N1900/L1900/ L2100	1	0/0	0	(1) 4460 B25+B66	4 2	COAX JUMPER FIBER JUMPER	15' 15'	(1) 6x24 HCS (200')
	W1	_	_	-	_	_	-	-	_	I	_	-	_	-
BETA	W2	APXVAARR24_43-U-NA20	1	APXVAARR24_43-U-NA20	130'-0"	N600/L700/ L1900/G1900	1	2/2/2/2	0	(1) 4449 B71+B85	4 2	COAX JUMPER FIBER JUMPER	15' 15'	-
150°	W3	_	_	-	_	_	_	_	_	П	_	_	-	_
	W4	RR90-17-00DPL2	1	HBXX-9014DS-A2M	130'-0"	N1900/L1900/ L2100	1	0/0	0	(1) 4460 B25+B66	4 2	COAX JUMPER FIBER JUMPER	15' 15'	(1) 6x24 HCS (200')
GAMMA 270°	B1	_	_	-	_	_	_	_	_	_	_	-	_	-
	B2	APXVAARR24_43-U-NA20	1	APXVAARR24_43-U-NA20	130'-0"	N600/L700/ L1900/G1900	1	2/2/2/2	0	(1) 4449 B71+B85	4 2	COAX JUMPER FIBER JUMPER	15 ' 15'	-
	В3	_	_	_	_	_	_	_	_	П	_	_	_	_
	B4	RR90-17-00DPL2	1	HBXX-9014DS-A2M	130'-0"	N1900/L1900/ L2100	1	0/0	0	(1) 4460 B25+B66	4 2	COAX JUMPER FIBER JUMPER	15' 15'	(1) 6x24 HCS (200')

AT TIME OF CONSTRUCTION, CONTRACTOR TO VERIFY AZIMUTHS OF EXISTING ANTENNAS. IF DIFFERENT FROM RFDS, PLEASE NOTIFY THE RF ENGINEER AND CONSTRUCTION MANAGER WITH ACTUAL AZIMUTH TO ENSURE T-MOBILE'S DATABASE IS ACCURATE AND UP-TO-DATE.

ANTENNA LOCATIONS TO BE VERIFIED IN FIELD. RFDS TO BE REDLINED ACCORDINGLY.

INFORMATION SHOWN PROVIDED ON T-MOBILE RFDS DATED 10/31/24.




NOTE:

1. "DOUBLING UP" OR "STACKING" OF CONNECTIONS IS NOT


PERMITTED.

2. OXIDE INHIBITING COMPOUND TO BE USED AT ALL LOCATIONS.




TYPICAL GROUND BAR CONNECTION DETAIL


1 SCALE: N.T.S.



GROUNDING RISER DIAGRAM
E-1) SCALE: N.T.S.




GROUND WIRE TO GROUND BAR CONNECTION DETAIL scale: n.t.s.




EXISTING ELECTRIC FEEDERS AND CONDUIT TO BE UPGRADED AS REQUIRED, CONDUIT AND WIRE LENGTH/SIZE TO BE VERIFIED BY LICENSED ELECTRICIAN

ONE LINE DIAGRAM

E-1 SCALE: 1/4"=1'-0"





5 ANTENNA CABLE GROUNDING E-1) SCALE: N.T.S. T-Mobile Northeast LLC

ELEVATED

35 GRIFFIN ROAD SOUTH

BLOOMFIELD, CT 06002

ENGINEERING

99 FANNY ROAD
BOONTON, NEW JERSEY 07005
862-242-8050

Documents prepared by Elevated Engineering, including this document, are to be used only for the specific project and specific use for which they were intended. Any extension of use to any other projects, by owner or by any other party, without the expressed written consent of Elevated Engineering, is done unlawfully and at the users own risk. If used in a way other than that specifically intended, user will hold Elevated Engineering, harmless from all claims and losses.

	SCHEDULE OF REVISIONS							
7								
6								
5								
4	1							
3	12/24/24	REVISED PER CLIENT COMMENTS						
2	12/09/24	REVISED PER SA						
1	11/27/24	ISSUED AS FINALS						
0	11/22/24	INITIAL SUBMISSION						
REV. NO.	DATE	DESCRIPTION OF CHANGES						

DRAWN BY:	CJT
CHECKED BY:	NDB
SCALE:	AS NOTED
JOB NO:	24045-NSS

INFORMATION ON THIS SET OF DRAWINGS IS
NOT FOR OFFICIAL USE UNLESS
ACCOMPANIED BY THE STAMPED SEAL &
SIGNATURE OF A PROFESSIONAL ENGINEER



NICHOLAS D. BARILE
PROFESSIONAL ENGINEER, CT LIC. No. 28643

SITE ID: CT11394A
NORTH MADISON
864 OPENING HILL RD
MADISON, CT 06443
NEW HAVEN COUNTY

DRAWING TITLE:

GROUNDING DETAILS & NOTES

DRAWING SHEET:

E-1

Exhibit D

Structural Analysis Report




CT11394A - NORTH MADISON

864 Opening Hill Road, Madison, CT 06443 (New Haven County)

Structural Analysis

December 9, 2024

Item	Pass/Fail	Capacity
Tower - Leg	Pass	30.6%
Tower - Diagonal	Pass	52.9%
Tower - Horizontal	Pass	51.6%
Anchor Bolts	Pass	23.4%
Concrete Pier	Pass	1.4%
Soil	Pass	26.8%



Nicholas D. Barile, PE CT PE License No.: 28643

Elevated Engineering Project No.: 24045-NSS



Summary

At the request of T-Mobile, Elevated Engineering has performed a structural analysis of the self-support tower for the equipment loading under the 2022 Connecticut Building Code, ASCE 7, ANSI/TIA-222-H, and AISC (LRFD14). Information pertaining to the tower, and its foundation was obtained from:

- Mount analysis by CLS Engineering dated 07/03/2019.
- Structural report by Matec Network Solution dated 10/18/2023.
- RFDS Version-7 last modified 10/331/2024.
- Design visit notes by Elevated Engineering dated 11/27/2024.
- Construction drawings by Elevated Engineering dated 11/27/2024.

Loading Criteria

Ment Fratan			
Wind Factors			
Basic Wind Sp	eed; Vult	131	mph
Risk Cate	gory	II	
Exposui	·e	В	
Flat Terra	ain		
Ground Elevation t	o Sea Level	316	ft
Ice Thickn	ess	1"	
Wi		50	mph
Seismic Factors			
Ss:		0.209	
S1:		0.054	
Loading Combinations at (12	2) 30° Intervals		

Conclusions

Per our analysis, the self-support tower can support proposed loading under the 2022 Connecticut Building Code.

General Comments

If there are substantial modifications to be made or the assumptions made in this analysis are not accurate, ELEVATED ENGINEERING should be notified immediately to perform a revised analysis. This report is not a condition assessment and assumes good workmanship will be used and systems will be properly maintained.

Limitations

All opinions and conclusions are considered accurate to a reasonable degree of engineering certainty based upon the evidence available at the time of this report. All opinions and conclusions are subject to revision based upon receipt of new or additional/updated information. All services are provided exercising a level of care and diligence equivalent to the standard and care of our profession. No other warranty or guarantee, expressed or implied, is offered. Our services are confidential in nature, and we will not release this report to any other party without the client's consent. The use of this engineering work is limited to the express purpose for which it was commissioned, and it may not be reused, copied, or distributed for any other purpose without the written consent of ELEVATED ENGINEERING.



Attachment A Final Equipment Configuration

Final Alpha Sector Antenna Configuration

Rad Center 130'-0"

- (1) RFS APXVAARR24 43-C-NA20 Antenna
- (1) CommScope HBXX-9014DS-A2M Antenna
- (1) Ericsson Radio 4449 B71+B85 RRU
- (1) Ericsson Radio 4460 B25+B66 RRU

Final Beta Sector Antenna Configuration


Rad Center 130'-0"

- (1) RFS APXVAARR24 43-C-NA20 Antenna
- (1) CommScope HBXX-9014DS-A2M Antenna
- (1) Ericsson Radio 4449 B71+B85 RRU
- (1) Ericsson Radio 4460 B25+B66 RRU

Final Gamma Sector Antenna Configuration

Rad Center 130'-0"

- (1) RFS APXVAARR24 43-C-NA20 Antenna
- (1) CommScope HBXX-9014DS-A2M Antenna
- (1) Ericsson Radio 4449 B71+B85 RRU
- (1) Ericsson Radio 4460 B25+B66 RRU



MATERIAL STRENGTH

GRADE	Fy	Fu	GRADE	Fy	Fu	
A618-50	50 ksi	70 ksi				

TOWER DESIGN NOTES

- Tower is located in New Haven County, Connecticut.
 Tower designed for Exposure B to the TIA-222-H Standard.
- Tower designed for a 131 mph basic wind in accordance with the TIA-222-H Standard.
- 4. Tower is also designed for a 50 mph basic wind with 1.00 in ice. Ice is considered to increase

MAX. CORNER REACTIONS AT BASE:

MOMENT 1182 kip-ft

MOMENT 4268 kip-ft

	^{Job:} 24045-NSS		
	Project: Self-Standing Tower		
	^{Client:} Elevated Engineering	Drawn by:	App'd:
Phone:	^{Code:} TIA-222-H	Date: 12/09/24	Scale: NTS
FAX:	Path:	TA - TOMER TOMER GONES NAS Seef Standing Tower Order	Dwg No. E-1

4Tornor	Job		Page
tnxTower		24045-NSS	1 of 41
	Project		Date
		Self-Standing Tower	10:20:05 12/09/24
	Client		Designed by
Phone: FAX:		Elevated Engineering	

Tower Input Data

The main tower is a 3x free standing tower with an overall height of 180.000 ft above the ground line.

The base of the tower is set at an elevation of 0.000 ft above the ground line.

The face width of the tower is 8.540 ft at the top and 25.230 ft at the base.

This tower is designed using the TIA-222-H standard.

The following design criteria apply:

Tower is located in New Haven County, Connecticut.

Tower base elevation above sea level: 316.000 ft.

Basic wind speed of 131 mph.

Risk Category III.

Exposure Category B.

Simplified Topographic Factor Procedure for wind speed-up calculations is used.

Topographic Category: 1.

Crest Height: 0.000 ft.

Nominal ice thickness of 1.000 in.

Ice thickness is considered to increase with height.

Ice density of 57 pcf.

A wind speed of 50 mph is used in combination with ice.

Temperature drop of 15 °F.


Deflections calculated using a wind speed of 60 mph.

A non-linear (P-delta) analysis was used.

Pressures are calculated at each section.

Stress ratio used in tower member design is 1.

Local bending stresses due to climbing loads, feed line supports, and appurtenance mounts are not considered.



Triangular Tower



Address:

864 Opening Hill Rd Madison, Connecticut


06443

ASCE Hazards Report

Standard: ASCE/SEI 7-16 Latitude: 41.357564
Risk Category: III Longitude: -72.638304

Soil Class: D - Stiff Soil **Elevation:** 316.05428670822505 ft

(NAVD 88)





Wind

Results:

Wind Speed 131 Vmph
10-year MRI 75 Vmph
25-year MRI 85 Vmph
50-year MRI 93 Vmph
100-year MRI 100 Vmph

Data Source: ASCE/SEI 7-16, Fig. 26.5-1C and Figs. CC.2-1–CC.2-4, and Section 26.5.2

Date Accessed: Tue Nov 26 2024


Value provided is 3-second gust wind speeds at 33 ft above ground for Exposure C Category, based on linear interpolation between contours. Wind speeds are interpolated in accordance with the 7-16 Standard. Wind speeds correspond to approximately a 3% probability of exceedance in 50 years (annual exceedance probability = 0.000588, MRI = 1,700 years).


Site is in a hurricane-prone region as defined in ASCE/SEI 7-16 Section 26.2. Glazed openings need not be protected against wind-borne debris.





Seismic

Site Soil Class: Results:	D - Stiff Soil			
S _s :	0.209	S _{D1} :	0.087	
S_1 :	0.054	T _L :	6	
F _a :	1.6	PGA:	0.117	
F_v :	2.4	PGA _M :	0.184	
S _{MS} :	0.335	F _{PGA} :	1.565	
S _{M1} :	0.131	l _e :	1.25	
S _{DS} :	0.223	C_v :	0.718	









Data Accessed: Tue Nov 26 2024

Date Source:

USGS Seismic Design Maps based on ASCE/SEI 7-16 and ASCE/SEI 7-16 Table 1.5-2. Additional data for site-specific ground motion procedures in accordance with ASCE/SEI 7-16 Ch. 21 are available from USGS.



Ice

Results:

Ice Thickness: 1.00 in.

Concurrent Temperature: 15 F

Gust Speed 50 mph

Data Source: Standard ASCE/SEI 7-16, Figs. 10-2 through 10-8

Date Accessed: Tue Nov 26 2024

Ice thicknesses on structures in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.

Values provided are equivalent radial ice thicknesses due to freezing rain with concurrent 3-second gust speeds, for a 500-year mean recurrence interval, and temperatures concurrent with ice thicknesses due to freezing rain. Thicknesses for ice accretions caused by other sources shall be obtained from local meteorological studies. Ice thicknesses in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.

The ASCE Hazard Tool is provided for your convenience, for informational purposes only, and is provided "as is" and without warranties of any kind. The location data included herein has been obtained from information developed, produced, and maintained by third party providers; or has been extrapolated from maps incorporated in the ASCE standard. While ASCE has made every effort to use data obtained from reliable sources or methodologies, ASCE does not make any representations or warranties as to the accuracy, completeness, reliability, currency, or quality of any data provided herein. Any third-party links provided by this Tool should not be construed as an endorsement, affiliation, relationship, or sponsorship of such third-party content by or from ASCE.

ASCE does not intend, nor should anyone interpret, the results provided by this Tool to replace the sound judgment of a competent professional, having knowledge and experience in the appropriate field(s) of practice, nor to substitute for the standard of care required of such professionals in interpreting and applying the contents of this Tool or the ASCE standard.

In using this Tool, you expressly assume all risks associated with your use. Under no circumstances shall ASCE or its officers, directors, employees, members, affiliates, or agents be liable to you or any other person for any direct, indirect, special, incidental, or consequential damages arising from or related to your use of, or reliance on, the Tool or any information obtained therein. To the fullest extent permitted by law, you agree to release and hold harmless ASCE from any and all liability of any nature arising out of or resulting from any use of data provided by the ASCE Hazard Tool.

Exhibit E

Mount Analysis




CT11394A - NORTH MADISON

864 Opening Hill Road, Madison, CT 06443 (New Haven County)

Mount Analysis

November 27, 2024

Item	Pass/Fail	Capacity		
Antenna Mount	Pass	28.2%		
Antenna Pipes	Pass	31.9%		



Nicholas D. Barile, PE CT PE License No.: 28643

Elevated Engineering Project No.: 24045-NSS



Summary

At the request of T-Mobile, Elevated Engineering has performed a structural analysis of the antenna mounting system for the antenna equipment loading under the 2022 Connecticut Building Code, ASCE 7, ANSI/TIA-222-H, and AISC (LRFD14). Information pertaining to the antenna mounts was obtained from:

- Mount analysis by CLS Engineering dated 07/03/2019.
- Structural report by Matec Network Solution dated 10/18/2023.
- RFDS Version-7 last modified 10/331/2024.
- Design visit notes by Elevated Engineering dated 11/27/2024.
- Construction drawings by Elevated Engineering dated 11/27/2024.

Loading Criteria

 9		
Wind Factors		
Basic Wind Speed; Vult	131	mph
Risk Category	III	
Exposure	В	
Flat Terrain		
Ground Elevation to Sea Level	316	ft
Ice Thickness	1"	
Wi	50	mph
Seismic Factors		
Ss:	0.209	
S1:	0.054	
Loading Combinations at (12) 30° Intervals		

Conclusions

Per our analysis, the antenna mounting system can support proposed loading under the 2022 Connecticut Building Code; however, steel grating needs structural reinforcement.

General Comments

If there are substantial modifications to be made or the assumptions made in this analysis are not accurate, ELEVATED ENGINEERING should be notified immediately to perform a revised analysis. This report is not a condition assessment and assumes good workmanship will be used and systems will be properly maintained.

Limitations

All opinions and conclusions are considered accurate to a reasonable degree of engineering certainty based upon the evidence available at the time of this report. All opinions and conclusions are subject to revision based upon receipt of new or additional/updated information. All services are provided exercising a level of care and diligence equivalent to the standard and care of our profession. No other warranty or guarantee, expressed or implied, is offered. Our services are confidential in nature, and we will not release this report to any other party without the client's consent. The use of this engineering work is limited to the express purpose for which it was commissioned, and it may not be reused, copied, or distributed for any other purpose without the written consent of ELEVATED ENGINEERING.



Attachment A Final Equipment Configuration

Final Alpha Sector Antenna Configuration

Rad Center 130'-0"

- (1) RFS APXVAARR24 43-C-NA20 Antenna
- (1) CommScope HBXX-9014DS-A2M Antenna
- (1) Ericsson Radio 4449 B71+B85 RRU
- (1) Ericsson Radio 4460 B25+B66 RRU

Final Beta Sector Antenna Configuration

Rad Center 130'-0"

- (1) RFS APXVAARR24 43-C-NA20 Antenna
- (1) CommScope HBXX-9014DS-A2M Antenna
- (1) Ericsson Radio 4449 B71+B85 RRU
- (1) Ericsson Radio 4460 B25+B66 RRU

Final Gamma Sector Antenna Configuration

Rad Center 130'-0"

- (1) RFS APXVAARR24_43-C-NA20 Antenna
- (1) CommScope HBXX-9014DS-A2M Antenna
- (1) Ericsson Radio 4449 B71+B85 RRU
- (1) Ericsson Radio 4460 B25+B66 RRU

Wind Analysis $F = qz \times Gh \times (EPA)$ per TIA-222-H

 $Kz=2.01 (Z/Zg)^{(2/\alpha)} = 1.065$ Zg = 1200 Table 2-4 Exposure B

Alpha (α) = 7 Table 2-4

Z= 130 ft

Terrain Category I

 $Kzt = (1+KcKt/Kh)^2$ 1.00 for Category I

Kc= 1.00 Table 2-4

Kt= 0.53 Table 2-5

 $Kh=e^{(f*z/H)} = 0.000$ for H=0

f= 2.00 Table 2-5

H =Height of Crest Surrounding Terrain 0.00 ft

Kz = 1.065

Kzt = 1.0

Kd = 0.95

Importance Factor Table 2-3 = I = 1.0 Use Class III

Zs = **316** ft

 $Ke = e^{(-0.0000362xZs)} = 0.99$

Vult = 131 mph

 $qz=0.00256xKzxKztxKdxKsxKexV^2xI = 43.9$ psf

Gh = 1.00

qz Gh = 43.9 psf

	42 On -	73.5	рэт			
	Equipment Loading	CaAa	Wind	.,	Wind Load	Weight
		(sf or sf/lf)	(psf)	Ka	(lb)	(lb)
F _N 1	APXVAARR24_43-C-NA20	17.140	43.9	0.9	678.0	114.7
F _{N2}	HBXX-9014DS-A2M	5.44	43.9	0.9	215.2	38.4
F _{N3}	4460 B71+B85 RRU	2.140	43.9	0.9	84.6	104
F _N 4	4449 B25+B66 RRU	1.97	43.9	0.9	77.9	75
	2"Ф Pipe	0.238	43.9	0.9	9.4	
	2-1/2"Ф Ріре	0.288	43.9	0.9	11.4	
	SR-5/8	0.063	43.9	0.9	2.5	
	SR-3/4	0.075	43.9	0.9	3.0	
FT1	APXVAARR24_43-C-NA20	8.740	43.9	0.9	345.7	114.7
FT2	HBXX-9014DS-A2M	3.29	43.9	0.9	130.1	38.4
F т3	4460 RRU	1.690	43.9	0.9	66.8	104
FT4	4449 RRU	1.60	43.9	0.9	63.3	75
-						

1" Ice 50mph - Wind Analysis F = qz x Gh x (EPA) per TIA-222-H

 $Kz=2.01 (Z/Zg)^{(2/\alpha)} =$ Zg = 1200 Table 2-4 Exposure B 7 Alpha $(\alpha) =$ Table 2-4 Z= 130 ft **Terrain Category** 1 $Kzt = (1+KcKt/Kh)^2$ 1.00 for Category I 1.00 Table 2-4 Kc= Kt= 0.53 Table 2-5 $Kh=e^{(f * Z/H)} =$ 0.000 for H=0 2.00 Table 2-5 H =Height of Crest Surrounding Terrain 0.00 ft Kz = 1.065 1.0 Kzt = Kd = 0.95 Importance Factor Table 2-3 = I = 1.0 Use Class III

316 ft Zs =

 $Ke= e^{(-0.0000362xZs)} =$ 0.99

> Vult = 50 mph

qz=0.00256xKzxKztxKdxKsxKexV^2xI = 6.4 psf

> 1.00 Gh =

az Gh = 64 nsf

	qz Gh =	6.4	pst			
	Equipment Loading	CaAa	Wind		Wind Load	Weight
		(sf or sf/lf)	(psf)	Ka	(lb)	(lb)
F _{N1}	APXVAARR24_43-C-NA20	19.280	6.4	0.9	111.1	317.4
F _{N2}	HBXX-9014DS-A2M	6.60	6.4	0.9	38.0	114
F _{N3}	4460 B25+B66 RRU	2.710	6.4	0.9	15.6	148.4
FN4	4449 B71+B85 RRU	2.51	6.4	0.9	14.5	114.6
	2"Ф Pipe	0.438	6.4	0.9	2.5	
	2-1/2"Φ Pipe	0.488	6.4	0.9	2.8	
	SR-5/8	0.263	6.4	0.9	1.5	
	SR-3/4	0.275	6.4	0.9	1.6	
FT1	APXVAARR24_43-C-NA20	11.030	6.4	0.9	63.6	317.4
FT2	HBXX-9014DS-A2M	4.47	6.4	0.9	25.8	114
F т3	4460 B25+B66 RRU	2.190	6.4	0.9	12.6	148.4
FT4	4449 B71+B85 RRU	2.08	6.4	0.9	12.0	114.6



Address:

864 Opening Hill Rd Madison, Connecticut


06443


ASCE Hazards Report

Standard: ASCE/SEI 7-16 Latitude: 41.357564
Risk Category: III Longitude: -72.638304

Soil Class: D - Stiff Soil **Elevation:** 316.05428670822505 ft

(NAVD 88)





Wind

Results:

Wind Speed 131 Vmph
10-year MRI 75 Vmph
25-year MRI 85 Vmph
50-year MRI 93 Vmph
100-year MRI 100 Vmph

Data Source: ASCE/SEI 7-16, Fig. 26.5-1C and Figs. CC.2-1–CC.2-4, and Section 26.5.2

Date Accessed: Tue Nov 26 2024


Value provided is 3-second gust wind speeds at 33 ft above ground for Exposure C Category, based on linear interpolation between contours. Wind speeds are interpolated in accordance with the 7-16 Standard. Wind speeds correspond to approximately a 3% probability of exceedance in 50 years (annual exceedance probability = 0.000588, MRI = 1,700 years).


Site is in a hurricane-prone region as defined in ASCE/SEI 7-16 Section 26.2. Glazed openings need not be protected against wind-borne debris.





Seismic

Site Soil Class: Results:	D - Stiff Soil			
S _s :	0.209	S _{D1} :	0.087	
S_1 :	0.054	T _L :	6	
F _a :	1.6	PGA:	0.117	
F_v :	2.4	PGA _M :	0.184	
S _{MS} :	0.335	F _{PGA} :	1.565	
S _{M1} :	0.131	l _e :	1.25	
S _{DS} :	0.223	C_v :	0.718	









Data Accessed: Tue Nov 26 2024

Date Source:

USGS Seismic Design Maps based on ASCE/SEI 7-16 and ASCE/SEI 7-16 Table 1.5-2. Additional data for site-specific ground motion procedures in accordance with ASCE/SEI 7-16 Ch. 21 are available from USGS.



Ice

Results:

Ice Thickness: 1.00 in.

Concurrent Temperature: 15 F

Gust Speed 50 mph

Data Source: Standard ASCE/SEI 7-16, Figs. 10-2 through 10-8

Date Accessed: Tue Nov 26 2024

Ice thicknesses on structures in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.

Values provided are equivalent radial ice thicknesses due to freezing rain with concurrent 3-second gust speeds, for a 500-year mean recurrence interval, and temperatures concurrent with ice thicknesses due to freezing rain. Thicknesses for ice accretions caused by other sources shall be obtained from local meteorological studies. Ice thicknesses in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.

The ASCE Hazard Tool is provided for your convenience, for informational purposes only, and is provided "as is" and without warranties of any kind. The location data included herein has been obtained from information developed, produced, and maintained by third party providers; or has been extrapolated from maps incorporated in the ASCE standard. While ASCE has made every effort to use data obtained from reliable sources or methodologies, ASCE does not make any representations or warranties as to the accuracy, completeness, reliability, currency, or quality of any data provided herein. Any third-party links provided by this Tool should not be construed as an endorsement, affiliation, relationship, or sponsorship of such third-party content by or from ASCE.

ASCE does not intend, nor should anyone interpret, the results provided by this Tool to replace the sound judgment of a competent professional, having knowledge and experience in the appropriate field(s) of practice, nor to substitute for the standard of care required of such professionals in interpreting and applying the contents of this Tool or the ASCE standard.

In using this Tool, you expressly assume all risks associated with your use. Under no circumstances shall ASCE or its officers, directors, employees, members, affiliates, or agents be liable to you or any other person for any direct, indirect, special, incidental, or consequential damages arising from or related to your use of, or reliance on, the Tool or any information obtained therein. To the fullest extent permitted by law, you agree to release and hold harmless ASCE from any and all liability of any nature arising out of or resulting from any use of data provided by the ASCE Hazard Tool.

Exhibit F

Power Density/RF Emissions Report



Radio Frequency Emissions Analysis Report

T Mobile

Site ID: CT11394A

North Madison 864 Opening Hill Road Madison, CT 06443

December 4, 2024

Fox Hill Telecom Project Number: 240275

Site Compliance Summary				
Compliance Status:	COMPLIANT			
Site total MPE% of FCC				
general population	14.16 %			
allowable limit:				



December 4, 2024

T-MOBILE Attn: RF Manager 35 Griffin Road South Bloomfield, CT 06009

Emissions Analysis for Site: CT11394A – North Madison

Fox Hill Telecom, Inc ("Fox Hill") was directed to analyze the proposed upgrades to the T-MOBILE facility located at **864 Opening Hill Road, Madison, CT**, for the purpose of determining whether the emissions from the Proposed T-MOBILE Antenna Installation located on this property are within specified federal limits.

All information used in this report was analyzed as a percentage of current Maximum Permissible Exposure (% MPE) as listed in the FCC OET Bulletin 65 Edition 97-01and ANSI/IEEE Std C95.1. The FCC regulates Maximum Permissible Exposure in units of microwatts per square centimeter (μ W/cm2). The number of μ W/cm² calculated at each sample point is called the power density. The exposure limit for power density varies depending upon the frequencies being utilized. Wireless Carriers and Paging Services use different frequency bands each with different exposure limits, therefore it is necessary to report results and limits in terms of percent MPE rather than power density.

All results were compared to the FCC (Federal Communications Commission) radio frequency exposure rules, 47 CFR 1.1307(b)(1) - (b)(3), to determine compliance with the Maximum Permissible Exposure (MPE) limits for General Population/Uncontrolled environments as defined below.

General population/uncontrolled exposure limits apply to situations in which the general population may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Therefore, members of the general population would always be considered under this category when exposure is not employment related, for example, in the case of a telecommunications tower that exposes persons in a nearby residential area.

General population exposure to radio frequencies is regulated and enforced in units of microwatts per square centimeter (μ W/cm²). The general population exposure limits for the 600 MHz & 700 MHz bands are approximately 400 μ W/cm² and 467 μ W/cm² respectively. The general population exposure limit for the 1900 MHz (PCS) and 2100 MHz (AWS) bands is 1000 μ W/cm². Because each carrier will be using different frequency bands, and each frequency band has different exposure limits, it is necessary to report the percentage of MPE rather than power density.



Occupational/controlled exposure limits apply to situations in which persons are exposed as a consequence of their employment and in which those persons who are exposed have been made fully aware of the potential for exposure and can exercise control over their exposure. Occupational/controlled exposure limits also apply where exposure is of a transient nature as a result of incidental passage through a location where exposure levels may be above general population/uncontrolled limits (see below), as long as the exposed person has been made fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Additional details can be found in FCC OET 65.



CALCULATIONS

Calculations were performed for the proposed upgrades to the T-MOBILE antenna facility located at **864 Opening Hill Road, Madison, CT**, using the equipment information listed below. All calculations were performed per the specifications under FCC OET 65 for far field modeling calculations.

In OET-65, plane wave power densities in the Far Field of an antenna are calculated by considering antenna gain and reflective waves that would contribute to exposure.

Since the radiation pattern of an antenna has developed in the **Far Field** region the power gain in specific directions needs to be considered in exposure predictions to yield an Effective Radiated Power (ERP) in each specific direction from the antenna. Also, since the vertical radiation pattern of the antenna is considered, the exposure calculations would most likely be reduced significantly at ground level, resulting in a more realistic estimate of the actual exposure levels. To determine a worst-case scenario at each point along the calculation radials, each point was calculated using the antenna gain value at each angle of incident and compared against the result using an isotropic radiator at the antenna height with the greater of the two used to yield the more pessimistic far field value for each point along the calculation radial.

Additionally, to model a truly "worst case" prediction of exposure levels at or near a surface, such as at ground-level or on a rooftop, reflection off the surface of antenna radiation power can be assumed, resulting in a potential 1.6 times increase in power density in calculating far field power density values.

With these factors Considered, the worst case **Far Field prediction model** utilized in this analysis is determined by the following equation:

Equation 9 per FCC OET65 for Far Field Modeling

$$S = \frac{33.4 \ ERP}{R^2}$$

S = Power Density (in μ w/cm²) ERP = Effective Radiated Power from antenna (watts) R = Distance from the antenna (meters)

Predicted far field power density values for all carriers identified in this report were calculated 6 feet above the ground level and are displayed as a percentage of the applicable FCC standards. All emissions values for other carriers were calculated using the same Far Field model outlined above, using industry standard radio configurations and frequency band selection based upon available licenses in this geographic area for emissions contribution estimates.



For each T-Mobile sector the following channel counts, frequency bands and power levels were utilized as shown in *Table 1*:

Technology	Frequency Band	Channel Count	Transmit Power per Channel (W)
LTE / 5G NR	600 MHz	4	40
LTE	700 MHz	2	20
GSM	1900 MHz (PCS)	2	10
LTE	1900 MHz (PCS)	4	35
5G	1900 MHz (PCS)	4	40
LTE	2100 MHz (AWS)	4	60

Table 1: Channel Data Table



The following T-Mobile antennas listed in *Table 2* were used in the modeling for transmission in the 600 MHz, 700 MHz, 1900 MHz (PCS) and 2100 MHz (AWS) frequency bands. This is based on feedback from the carrier with regards to anticipated antenna selection. Maximum gain values for all antennas are listed in the Inventory and Power Data table below.

			Antenna
	Antenna		Centerline
Sector	Number	Antenna Make / Model	(ft)
A	1	RFS APXVAARR24_43-U-NA20	130
A	2	Commscope HBXX-9014DS-A2M	130
В	1	RFS APXVAARR24_43-U-NA20	130
В	2	Commscope HBXX-9014DS-A2M	130
C	1	RFS APXVAARR24_43-U-NA20	130
C	2	Commscope HBXX-9014DS-A2M	130

Table 2: Antenna Data

All calculations were done with respect to uncontrolled / general population threshold limits.



RESULTS

Per the calculations completed for the proposed T-MOBILE configurations *Table 3* shows resulting emissions power levels and percentages of the FCC's allowable general population limit.

					Total TX		
Antenna			Antenna Gain	Channel	Power		
ID	Antenna Make / Model	Frequency Bands	(dBd)	Count	(W)	ERP (W)	MPE %
Antenna	RFS						
A1	APXVAARR24_43-U-NA20	600 MHz / 700 MHz	12.95 / 13.35	6	200	4,020.96	1.14
Antenna	Commscope	1900 MHz (PCS) /					
A2	HBXX-9014DS-A2M	2100 MHz (AWS)	13.85 / 14.05	14	556	13,766.42	1.31
	Sector A Composite MPE%				osite MPE%	2.45	
Antenna	RFS						
B1	APXVAARR24_43-U-NA20	600 MHz / 700 MHz	12.95 / 13.35	6	200	4,020.96	1.14
Antenna	Commscope	1900 MHz (PCS) /					
B2	HBXX-9014DS-A2M	2100 MHz (AWS)	13.85 / 14.05	14	556	13,766.42	1.31
				Se	ector B Comp	osite MPE%	2.45
Antenna	RFS						
C1	APXVAARR24_43-U-NA20	600 MHz / 700 MHz	12.95 / 13.35	6	200	4,020.96	1.14
Antenna	Commscope	1900 MHz (PCS) /					
C2	HBXX-9014DS-A2M	2100 MHz (AWS)	13.85 / 14.05	14	556	13,766.42	1.31
Sector C Composite MPE%					2.45		

Table 3: T-MOBILE Emissions Levels

The Following table (*table 4*) shows all additional identified carriers on site and their emissions contribution estimates, along with the newly calculated maximum T-MOBILE MPE contributions per this report. FCC OET 65 specifies that for carriers utilizing directional antennas that the highest recorded sector value be used for composite site MPE values due to their greatly reduced emissions contributions in the directions of the adjacent sectors. For this site, all three T-Mobile sectors have the same configuration yielding the same results on all three sectors. *Table 5* below shows a summary for each T-MOBILE Sector as well as the composite estimated MPE value for the site.

Site Composite MPE%				
Carrier	MPE%			
T-MOBILE – Max Per Sector Value	2.45 %			
Verizon Wireless	2.54 %			
AT&T	5.03 %			
Dish Wireless	3.14 %			
Town Fire (180')	0.06 %			
Town Police (180')	0.04 %			
Unknown Omni Antennas (90')	0.90 %			
Site Total MPE %:	14.16 %			

Table 4: All Carrier MPE Contributions

T-MOBILE Sector A Total:	2.45 %
T-MOBILE Sector B Total:	2.45 %
T-MOBILE Sector C Total:	2.45 %
Site Total:	14.16 %

Table 5: Site MPE Summary



Table 6 below details a breakdown by frequency band and technology for the MPE power values for the maximum calculated T-MOBILE sector(s). For this site, all three T-Mobile sectors have the same configuration yielding the same results on all three sectors.

T-MOBILE _ Frequency Band / Technology Max Power Values (Per Sector)	# Channels	Watts ERP (Per Channel)	Height (feet)	Total Power Density (µW/cm²)	Frequency (MHz)	Allowable MPE (µW/cm²)	Calculated % MPE
T-Mobile 600 MHz LTE / 5G NR	4	788.97	130	3.76	600 MHz	400	0.94%
T-Mobile 700 MHz LTE	2	432.54	130	0.93	700 MHz	467	0.20%
T-Mobile 1900 MHz (PCS) GSM	2	242.66	130	0.50	1900 MHz (PCS)	1000	0.05%
T-Mobile 1900 MHz (PCS) LTE	4	825.05	130	3.30	1900 MHz (PCS)	1000	0.33%
T-Mobile 1900 MHz (PCS) 5G	4	970.64	130	3.70	1900 MHz (PCS)	1000	0.37%
T-Mobile 2100 MHz (AWS) LTE	4	1,524.58	130	5.60	2100 MHz (AWS)	1000	0.56%
						Total:	2.45 %

Table 6: T-MOBILE Maximum Sector MPE Power Values



Summary

All calculations performed for this analysis yielded results that were **within** the allowable limits for general population exposure to RF Emissions.

The anticipated maximum composite contributions from the T-MOBILE facility as well as the site composite emissions estimates value with regards to compliance with FCC's allowable limits for general population exposure to RF Emissions are shown here:

T-MOBILE Sector	Power Density Value (%)		
Sector A:	2.45 %		
Sector B:	2.45 %		
Sector C:	2.45 %		
T-MOBILE Maximum	2.45.0/		
Total (per sector):	2.45 %		
Site Total:	14.16 %		
Site Compliance Status:	COMPLIANT		

The estimated composite MPE value for this site assuming all carriers present is **14.16** % of the allowable FCC established general population limit sampled at the ground level. This is based upon the far field calculations performed for all carriers identified in this report.

FCC guidelines state that if a site is found to be out of compliance (over allowable thresholds), that carriers over a 5% contribution to the composite value will require measures to bring the site into compliance. For this facility, the composite estimated values calculated were well within the allowable 100% threshold standard per the federal government.

Scott Heffernan Principal RF Engineer


Fox Hill Telecom, Inc

Worcester, MA 01609

(978)660-3998

Exhibit G

Recipient Mailings





Cut on dotted line.

Instructions

- 1. Each Click-N-Ship® label is unique. Labels are to be used as printed and used only once. DO NOT PHOTO **COPY OR ALTER LABEL.**
- 2. Place your label so it does not wrap around the edge of the package.
- 3. Adhere your label to the package. A self-adhesive label is recommended. If tape or glue is used, DO NOT TAPE OVER BARCODE. Be sure all edges are secure.
- 4. To mail your package with PC Postage®, you may schedule a Package Pickup online, hand to your letter carrier, take to a Post Office™, or drop in a USPS collection box.
- 5. Mail your package on the "Ship Date" you selected when creating this label.

Click-N-Ship® Label Record

USPS TRACKING #: 9405 5036 9930 0738 9358 64

Trans. #: 607496241 Print Date: 01/13/2025 01/13/2025 01/15/2025 Delivery Date:

Priority Mail® Postage: Total:

\$10.45 \$10.45

Ref#: CT11394A

From: DEBORAH A CHASE

NORTHEAST SITE SOLUTIONS

46 HUNTINGTON AVE WORCESTER MA 01606-3543

PEGGY LYONS


FIRST SELECTWOMAN 8 CAMPUS DR

MADISON CT 06443-2562

* Retail Pricing Priority Mail rates apply. There is no fee for USPS Tracking® service on Priority Mail service with use of this electronic rate shipping label. Refunds for unused postage paid labels can be requested online 30 days from the print date.



Thank you for shipping with the United States Postal Service! Check the status of your shipment on the USPS Tracking® page at usps.com





Cut on dotted line.

Instructions

- 1. Each Click-N-Ship® label is unique. Labels are to be used as printed and used only once. DO NOT PHOTO **COPY OR ALTER LABEL.**
- 2. Place your label so it does not wrap around the edge of the package.
- 3. Adhere your label to the package. A self-adhesive label is recommended. If tape or glue is used, DO NOT TAPE OVER BARCODE. Be sure all edges are secure.
- 4. To mail your package with PC Postage®, you may schedule a Package Pickup online, hand to your letter carrier, take to a Post Office™, or drop in a USPS collection box.
- 5. Mail your package on the "Ship Date" you selected when creating this label.

Click-N-Ship® Label Record

USPS TRACKING #: 9405 5036 9930 0738 9358 88

Trans. #: 607496241 Print Date: 01/13/2025 01/13/2025 01/15/2025 Delivery Date:

Priority Mail® Postage: Total:

\$10.45 \$10.45

Ref#: CT11394A

From: DEBORAH A CHASE

NORTHEAST SITE SOLUTIONS


46 HUNTINGTON AVE WORCESTER MA 01606-3543

ERIN MANNIX

TOWN PLANNER 8 CAMPUS DR

MADISON CT 06443-2562

* Retail Pricing Priority Mail rates apply. There is no fee for USPS Tracking® service on Priority Mail service with use of this electronic rate shipping label. Refunds for unused postage paid labels can be requested online 30 days from the print date.





Cut on dotted line.

Instructions

- 1. Each Click-N-Ship® label is unique. Labels are to be used as printed and used only once. DO NOT PHOTO **COPY OR ALTER LABEL.**
- 2. Place your label so it does not wrap around the edge of the package.
- 3. Adhere your label to the package. A self-adhesive label is recommended. If tape or glue is used, DO NOT TAPE OVER BARCODE. Be sure all edges are secure.
- 4. To mail your package with PC Postage®, you may schedule a Package Pickup online, hand to your letter carrier, take to a Post Office™, or drop in a USPS collection box.
- 5. Mail your package on the "Ship Date" you selected when creating this label.

Click-N-Ship® Label Record

USPS TRACKING #: 9405 5036 9930 0738 9359 18

Trans. #: 607496241 Print Date: 01/13/2025 01/13/2025 01/15/2025 Delivery Date:

Priority Mail® Postage: Total:

\$10.45 \$10.45

Ref#: CT-394A

From: DEBORAH A CHASE

NORTHEAST SITE SOLUTIONS

46 HUNTINGTON AVE WORCESTER MA 01606-3543

NORTH MADISON VOLUNTEER FIRE DEPARTMENT

864 OPENING HILL RD MADISON CT 06443-8202

* Retail Pricing Priority Mail rates apply. There is no fee for USPS Tracking® service on Priority Mail service with use of this electronic rate shipping label. Refunds for unused postage paid labels can be requested online 30 days from the print date.

(T11394A - updated



GREENDALE
290 W BOYLSTON ST
WORCESTER, MA 01606-2378
(800)275-8777

	(800) 275-8	777 - (02:39 PM
01/13/2025			Doi oo
Product	Qty	Unit Price	Price
Prepaid Mail Madison, CT Weight: 0 lk Acceptance E Mon 01/ Tracking #: 9405 50) 9.90 02)ate:	38 9359 1	\$0.00
Prepaid Mail Madison, CT Weight: O l Acceptance Mon O1.	1 06443 b 9.30 o Date: /13/2025	2	\$0.00
Prepaid Mail Madison, C Weight: O Acceptance Mon Of Tracking	1 T 06443 1b 9.40 o Date: 1/13/2025 #: 5036 9930	o z 0738 9358	\$0.00 88
and had not the the			30.00