



Crown Castle
3 Corporate Park Drive, Suite 101
Clifton Park, NY 12065

October 3, 2022

Melanie A. Bachman
Executive Director
Connecticut Siting Council
10 Franklin Square
New Britain, CT 06051

RE: **Notice of Exempt Modification for ATT
Crown #825983; ATT Site ID CTL01044
90 Industrial Park Road, Middletown, CT 06457
Latitude: 41° 35' 8.30" / Longitude: -72° 42' 50.49"**

Dear Ms. Bachman:

AT&T currently maintains twelve (12) antennas at the 174-foot level of the existing 185-foot monopole tower at 90 Industrial Park Road, Middletown, CT. The tower is owned by Crown Castle USA Inc. and the property is owned by Airline Avenue Realty LLC. AT&T now intends to replace nine (9) antennas, install nine (9) new antennas and ancillary equipment at the 174-foot level. This modification may include B2, B5, B17, B14, B29, B30, B66 & n77 hardware that is 4G(LTE) and/or 5GNR capable through remote software configuration and either or both services may be turned on or off at various times.

Panned Modification:

Tower:

Installed New:

- (3) QUINTEL-QD6616-7 Antennas
- (6) Ericsson-AIR6449 B77D + AIR6419 B77G Stacked Antennas
- (3) Ericsson-4415 B25 Radios
- (3) Dual Radio Mounts
- (3) Y CABLES
- (3) 2-1/2" SCH 40x6'-0" long mount pipes w/crossover hardware
- (1) New Sabre-C10899050 pipe mount assembly
- (3) New Valmont-VFA14-WLL-30120 Sector Mounts
- (6) 2-1/2" SCH 40x9'-0" long mount pipes w/crossover hardware

Remove:

- (3) POWERWAVE-7770 Antennas
- (3) QUINTEL-QS66512-2 Antennas
- (3) CCI-OPA65R-BU6DA-K Antennas
- (6) POWERWAVE-LGP21401TMAs
- (6) ERICSSON-RRUS-32 B2 Radios
- (6) KATHREIN-782-10250 Diplexers
- (6) KAELUS-DBC0061F1V51-2 Diplexers

The Foundation for a Wireless World.

CrownCastle.com

Ground:

Install New:

- (4) GE Rectifiers in existing power plant
- (2) Battery Strings

New -48V Battery Rack next to power plant & additional (8) 170AH batteries in Battery Rack
(1) 6648 w/XCEDE

Remove:

Replace existing batteries with (12) 170AH Batteries


The facility was approved by the City of Middletown Planning & Zoning Commission on January 28, 1998.

Please accept this letter as notification pursuant to Regulations of Connecticut State Agencies §16-50j-73, for construction that constitutes an exempt modification pursuant to R.C.S.A. § 16-50j-72(b)(2). In accordance with R.C.S.A. § 16-50j-73, a copy of this letter is being sent to Mayor Ben Florsheim and Marek Kozikowski, Director of Land Use for the City of Middletown, Airline Avenue Realty LLC as the property owner and Crown Castle is the tower owner.

1. The proposed modifications will not result in an increase in the height of the existing tower.
2. The proposed modifications will not require the extension of the site boundary.
3. The proposed modification will not increase noise levels at the facility by six decibels or more, or to levels that exceed state and local criteria.
4. The operation of the replacement antennas will not increase radio frequency emissions at the facility to a level at or above the Federal Communication Commission safety standard.
5. The proposed modifications will not cause a change or alteration in the physical or environmental characteristics of the site.
6. The existing structure and its foundation can support the proposed loading.

For the foregoing reasons, ATT respectfully submits that the proposed modifications to the above-reference telecommunications facility constitutes an exempt modification under R.C.S.A. § 16-50j-72(b)(2). Please send approval/rejection letter to Attn: Domenica Tatasciore.

Sincerely,



Domenica Tatasciore
Site Acquisition Specialist
1800 W. Park Drive
Westborough, MA 01581
(508) 621-9161/ Domenica.Tatasciore@crowncastle.com

Attachments

cc:

Mayor Ben Florsheim
Middletown City Hall
245 deKoven Drive
Middletown, CT 06457
860-638-4801

Marek Kozikowski, Director of Land Use
Middletown City Hall
245 deKoven Drive
Middletown, CT 06457
860-638-4590

Airline Avenue Realty LLC – Property Owner
15 Mullen Road
Enfield, CT 06082
860-749-3801

Crown Castle, Tower Owner

From: TrackingUpdates@fedex.com
To: [Tatasclore, Domenica](#)
Subject: FedEx Shipment 770056289204: Your package has been delivered
Date: Tuesday, October 4, 2022 9:48:19 AM

CAUTION: This email originated from outside of the organization. Do not click links or open attachments unless you recognize the sender and know the content is safe.

A large redacted area containing the FedEx logo.

FedEx

Hi. Your package was
delivered Tue, 10/04/2022 at
9:34am.



Delivered to 245 DEKOVEN DR, MIDDLETOWN, CT 06457
Received by F.FLYNN

OBTAI^N PROOF OF DELIVERY

TRACKING NUMBER [770056289204](#)

FROM Domenica Tatasclore
 1800 West Park Drive

Suite 200
WESTBOROUGH, MA, US, 01581

TO Middletown City Hall
Mayor Ben Florsheim
245 deKoven Drive
MIDDLETOWN, CT, US, 06457

REFERENCE 799001.7680

SHIPPER REFERENCE 799001.7680

SHIP DATE Mon 10/03/2022 05:29 PM

DELIVERED TO Receptionist/Front Desk

PACKAGING TYPE FedEx Envelope

ORIGIN WESTBOROUGH, MA, US, 01581

DESTINATION MIDDLETOWN, CT, US, 06457

SPECIAL HANDLING Deliver Weekday

NUMBER OF PIECES 1

TOTAL SHIPMENT WEIGHT 1.00 LB

SERVICE TYPE FedEx Priority Overnight

Get the FedEx® Mobile app

Create shipments, receive tracking alerts, redirect packages to a FedEx retail location for pickup, and more from the palm of your hand
- Download now.



From: TrackingUpdates@fedex.com
To: [Tatasciore, Domenica](#)
Subject: FedEx Shipment 770056309596: Your package has been delivered
Date: Tuesday, October 4, 2022 9:47:19 AM

CAUTION: This email originated from outside of the organization. Do not click links or open attachments unless you recognize the sender and know the content is safe.

FedEx



Hi. Your package was
delivered Tue, 10/04/2022 at
9:34am.



Delivered to 245 DEKOVEN DR, MIDDLETOWN, CT 06457
Received by F.FLYNN

OBTAI N PROOF OF DELIVERY

TRACKING NUMBER [770056309596](#)

FROM Domenica Tatasciore
1800 West Park Drive

Suite 200
WESTBOROUGH, MA, US, 01581

TO Middletown City Hall
Marek Kozikowski, Land Use Director
245 deKoven Drive
MIDDLETOWN, CT, US, 06457

REFERENCE 7990017680

SHIPPER REFERENCE 7990017680

SHIP DATE Mon 10/03/2022 05:29 PM

DELIVERED TO Receptionist/Front Desk

PACKAGING TYPE FedEx Envelope

ORIGIN WESTBOROUGH, MA, US, 01581

DESTINATION MIDDLETOWN, CT, US, 06457

SPECIAL HANDLING Deliver Weekday

NUMBER OF PIECES 1

TOTAL SHIPMENT WEIGHT 1.00 LB

SERVICE TYPE FedEx Priority Overnight

Get the FedEx® Mobile app

Create shipments, receive tracking alerts, redirect packages to a FedEx retail location for pickup, and more from the palm of your hand
- Download now.



From: TrackingUpdates@fedex.com
To: [Tatasciore, Domenica](#)
Subject: FedEx Shipment 770056337450: Your package has been delivered
Date: Tuesday, October 4, 2022 9:29:16 AM

CAUTION: This email originated from outside of the organization. Do not click links or open attachments unless you recognize the sender and know the content is safe.



Hi. Your package was
delivered Tue, 10/04/2022 at
9:21am.



Delivered to 15 MULLEN RD, ENFIELD, CT 06082
Received by D.FRIEDMAN

OBTAI^N PROOF OF DELIVERY

TRACKING NUMBER [770056337450](#)

FROM Domenica Tatasciore
1800 West Park Drive

Suite 200
WESTBOROUGH, MA, US, 01581

TO Airline Avenue Realty LLC
15 Mullen Road
ENFIELD, CT, US, 06082

REFERENCE 799001.7680

SHIPPER REFERENCE 799001.7680

SHIP DATE Mon 10/03/2022 05:29 PM

DELIVERED TO Receptionist/Front Desk

PACKAGING TYPE FedEx Envelope

ORIGIN WESTBOROUGH, MA, US, 01581

DESTINATION ENFIELD, CT, US, 06082

SPECIAL HANDLING Deliver Weekday

NUMBER OF PIECES 1

TOTAL SHIPMENT WEIGHT 1.00 LB

SERVICE TYPE FedEx Priority Overnight

Get the FedEx® Mobile app

Create shipments, receive tracking alerts, redirect packages to a FedEx retail location for pickup, and more from the palm of your hand

- **Download now.**



LEGAL NOTICE

NOTICE OF DECISION BY THE MIDDLETON PLANNING AND ZONING COMMISSION at its meeting of January 28, 1998

1. Denied without prejudice a request for release of the cash bond for Wesleyan Hills PRD, Red Area Section III. Applicant/agent Larsen, St. John & Johnson, P.C./Atty. Frank St. John PRD
2. Denied without prejudice a request for release of the cash bond for Longhill Meadows Subdivision located off South Main Street. Applicant/agent Krasow, Garlick & Hadley, LLC/Atty. Herbert A. Krasow S87-32
3. Denied without prejudice a request for release of the cash bond for Richards Brook Subdivision, Lots #2 and #3, located on Kenneth Dooley Drive. Applicant/agent Tyler Cooper & Alcorn, LLP/Atty. Barry M. Winnick S89-6
4. Granted Final Approval of a portion of Pond Place in Section 3 of The Meadows at Riverbend Subdivision located off East Street with the condition that all departmental comments be addressed and that a cash bond in the amount of \$45,000 be posted. Applicant/agent Tuttle Road Associates/Robert C. Fusari, President S93-3
5. Granted a one (1) year extension of the Special Exception approval for the Connecticut Beverage Mart Plaza located at 955 Washington Street. Applicant/agent 3127 Berlin Turnpike Associates/Brigham S. Metcalfe SE95-6
6. Denied without prejudice a proposed Zoning Code text amendment to modify Section 42 Protection of Water Sources. Applicant/agent City of Middletown Water and Sewer Department/Guy P. Russo, Director Z97-7
7. Granted a Special Exception for construction of a 185 foot monopole and installation of associated antennae and equipment for up to three (3) wireless communication providers at the Dainty Rubbish facility at 90 Industrial Park Road with the condition that all staff comments and conditions be addressed and adhered to. Applicant/agent Omnipoint Communications, Inc./Thomas M. Gilligan SE97-18
8. Granted a Special Exception to convert a former insurance business to a new use as a home for the aged and a rest home at 26 Silver Street with the following conditions: 1) there be no nurse on the premises; 2) no residents are to be older than fifty-five (55) years of age; 3) all residents are to administer their own medication; and 4) any modification to the structure are to be approved by the Design Preservation Board. Applicant/agent Deonarine and Neeta Dhanraj/Atty. Owen P. Eagan SE97-19

9. Adopted a Zoning Map amendment to rezone a portion of a piece of property located behind Middlesex Schools Federal Credit Union on South Main Street from RPZ Residential Pre Zoning to the B-2 General Business Zone with an effective date of February 15, 1998. A copy of the adopted map change is on file in the Office of the Town Clerk. Applicant/agent Middlesex Schools Federal Credit Union/Attorney Philip F. Karpel Z97-12

W. Lee Osborne, Chairman
Planning and Zoning Commission



P. O. No. 061920, Account No. 067419

The above legal notice to appear in the Hartford Courant ONCE

Thursday, February 5, 1998

THE MUNICIPAL BUILDING IS WHEELCHAIR ACCESSIBLE

P 348 778 241
US Postal Service

SENDER: ■ Complete items 1 and/or 2 for additional services. ■ Complete items 3, 4a, and 4b. ■ Print your name and address on the reverse of this form so that we can return this card to you. ■ Attach this form to the front of the mailpiece, or on the back if space does not permit. ■ Write "Return Receipt Requested" on the mailpiece below the article number. ■ The Return Receipt will show to whom the article was delivered and the date delivered.		I also wish to receive the following services (for an extra fee): 1. <input type="checkbox"/> Addressee's Address 2. <input type="checkbox"/> Restricted Delivery Consult postmaster for fee.
3. Article Addressed to: Omnipoint Communications, Inc. 25 Van Zant St. 4th fl/oor Norwalk, CT 06855		4a. Article Number P348 778 241
		4b. Service Type <input type="checkbox"/> Registered <input checked="" type="checkbox"/> Certified <input type="checkbox"/> Express Mail <input type="checkbox"/> Insured <input type="checkbox"/> Return Receipt for Merchandise <input type="checkbox"/> COD
		7. Date of Delivery 2/3/98
5. Received By: (Print Name) 		8. Addressee's Address (Only if requested and fee is paid) 102595-97-B-0179
6. Signature: (Addressee or Agent) 		PS Form 3811, December 1994 102595-97-B-0179 Domestic Return Receipt

Is your RETURN ADDRESS completed on the reverse side?

Thank you for using Return Receipt Service.

SE 97-18

INITIAL APPLICATION FOR LAND-USE IN MIDDLETON, CT

Please fill out this application so we will know who you are, what you are applying to do, and how to contact you. With this basic information we will evaluate your project as it relates to City regulations as quickly as possible. Thank you for your cooperation.

GENERAL INFORMATION ABOUT THE PEOPLE INVOLVED

Applicant: OMNIPONT Communications, INC.
 Address: 1515 Summer St City STAMFORD
 Agent: Thomas M. Gilligan
 Address: 1515 Summer St City STAMFORD

Date 11-6-97

Phone#(203) 359-1280

State CT Zip 06905

Phone#(203) 359-1280

State CT Zip 06905

WHAT ARE YOU APPLYING TO DO? (CHECK ONE OR MORE)

- Add an addition to a single/two family dwelling to be used for _____
- Construct a single family dwelling (A-2 survey required)
- Add an addition to a multi-family or non-residential building to be used for (A-2 survey required)
- Convert an existing building from present use as _____ to a new use as _____
- Construct one or more new buildings to be used for (A-2 survey required)
- Subdivide land into building lots (A-2 survey required)
- Change the text of the Zoning Code or amend the Zoning Map
- Install a sign
- Start a Residential Unit Business Pursuit
- Application for Zoning Board of Appeals
- Extract Natural Resources like sand or gravel or fill an area
- Other WIRELESS COMMUNICATIONS MASTPOLE, ASSOCIATED ANTENNAE AND EQUIPMENT DESIGNED FOR UP TO THREE CARRIERS

FACTS ABOUT LAND PROPOSED FOR USE

Landowner: PHILIP ARMETTA Location: 90 INDUSTRIAL PARK ROAD
 Zone IT Lot Area 2.54A Tax Assessor's Map 6 Block 22 Lot 6B1
 Is this project within 500' of a Municipal Boundary? Yes Yes No No
 Is this project located in a FEMA 100 or 500 year flood plain? Yes Yes No No
 Utilities Available: City Water (✓); Private Well (); City Sewer (✓); Private Septic ()

DEPT. PLANNING & ZONING

97 NOV - 6 PM 4:28

SIGNATURE OF I.W.A. STAFF

DATE APPLIED _____

- PERMIT REQUIRED
- PERMIT NOT REQUIRED
- IWA REVIEW REQUIRED

Meets Zoning Requirements

Wayne J. Bell
 ZONING ENFORCEMENT OFFICER
MARCH 6, 1998

DATE

9/17/97

DATE OF APPROVED PLANS

Thomas M. Gilligan
 SIGNATURE OF APPLICANT/AGENT**

Philip C. Armetta
 SIGNATURE OF OWNER**

**Both signatures required. I certify that the above information and plans submitted are true and correct, and that, if required, an application for an Inland/Wetlands permit has been filed before or on the same day as the filing of this application with the P&Z Commission.

Pd. \$110.00
 CK # 1846
 11/7/97

ALL DOCUMENTS WHICH MAKE UP THE RECORD OF THIS APPLICATION MUST BE LISTED BELOW. THIS INCLUDES ALL MAPS AND TEXT MATERIAL.

PROJECT: Construction of a 185' Monopole and Installation of Associated Antennae and Equipment designed for up to 3 Carriers

- 1.) Cover Letter 2.) Special Exception Form 3.) List of Abutting Owners 4.) Deed 5.) Executed Lease Signature Page 6.) General Information 7.) 8.5 x 11 Architectural Plans 8.) Site Plan 9.) Architectural Plans

IN THE EVENT A PUBLIC HEARING IS REQUIRED FOR THIS APPLICATION, ALL PERSONS MAKING VERBAL PRESENTATIONS AT THE PUBLIC HEARING FOR THIS PROJECT AND THE APPROXIMATE TIME EACH WILL REQUIRE MUST BE LISTED BELOW.

- ELENI SOTIRIOU, DIR. OF ZONING & LEASE MNGMT - 10-15 MINUTES
JONATHON LINDEMTHALER, PROJECT COORDINATOR - 10-15 MINUTES
THOMAS GILLIGAN, ZONING SPECIALIST/PLANNER - 10-15 MINUTES
MOHAN KUPPASWAMY, RF ENGINEER - 10-15 MINUTES
LOU CORNACCHIA, RF HEALTH PROFESSIONAL - 10-15 MINUTES

SPECIAL EXCEPTION FORM
MIDDLETOWN, CONNECTICUT
PLANNING & ZONING COMMISSION

A. GENERAL INFORMATION ABOUT APPLICANT (Please type or print clearly)

Name OmniPoint Communications, INC Date 11-6-97
 Address 1515 Summer Street Phone 203-359-1280
 Agent Thomas M. Gilligan Phone 203-359-1280

B. DESCRIPTION OF PREMISES

Owner of Record Philip Armetta
 Location 90 Industrial Park Road
 Deed Filed in Town Clerk's Office on _____
 Map File# Vol. & Page# 505 : 134
 Zone F-T Current Use OFFICE & BULKY WASTE TRANSFER STA.
 Relevant Zoning Code Provision SECTION 61
 NOTE: A legal description of the premises to be affected by the Special Exception must be attached to this form.

C. NATURE OF SPECIAL EXCEPTION

CONSTRUCTION OF A 185 FOOT MONOPOLE AND INSTALLATION OF ASSOCIATED ANTENNAE AND EQUIPMENT FOR UP TO 3 WIRELESS COMMUNICATION PROVIDERS

Philip M. Gilligan
 Signature of Applicant or Agent

Philip C. Armetta
 Signature of Owner
 *Both Signatures Required

NOTE: An approved Special Exception will not be effective until a copy of this certification is recorded in the Middletown Town Clerk's Office.

The owner, applicant and\or other authorized agent hereby grant the Middletown Planning and Zoning Commission and\or its agents permission to enter upon the property for which the Special Exception application has been filed for the purpose of inspection and enforcement of the Regulations of the City of Middletown.

Staff Comments _____

D. CERTIFICATION OF COMMISSION RESPONSE

Dates Legal Notices Published 1/16/98 ; 1/23/98
 Date of Public Hearing 1/28/98
 Final Action: Disapproved Approved X
 Zoning Regulation to which Special Exception is granted Sec. 61
 Date Notice of Decision Published 2/5/98
 Effective Date Upon filing this form

E. MATERIAL FILED IN TOWN CLERK'S OFFICE

This Form Site Plan
 Other Legal description ; Date 1/29/98

F. This is to certify that a Special Exception, as depicted on this form, was granted by the Middletown Planning and Zoning Commission.

W. Lee Malone
 Chairman

90 INDUSTRIAL PARK RD

Location 90 INDUSTRIAL PARK RD

Map-Lot 06 / 0018 /

Acct# R00347

Owner AIRLINE AVENUE REALTY LLC

Municipality

Assessment \$1,324,110

Appraisal \$1,891,590

PID 396

Building Count 1

Assessing District

Current Value

Appraisal			
Valuation Year	Improvements	Land	Total
2021	\$1,255,960	\$635,630	\$1,891,590
Assessment			
Valuation Year	Improvements	Land	Total
2021	\$879,170	\$444,940	\$1,324,110

Parcel Addresses

Additional Addresses

No Additional Addresses available for this parcel

Owner of Record

Owner AIRLINE AVENUE REALTY LLC

Sale Price \$1,000,000

Co-Owner

Certificate

Address 15 MULLEN RD

Book & Page 1956/943

ENFIELD, CT 06082

Sale Date 11/15/2019

Instrument 25

Ownership History

Ownership History

Owner	Sale Price	Certificate	Book & Page	Instrument	Sale Date
AIRLINE AVENUE REALTY LLC	\$1,000,000		1956/943	25	11/15/2019
90 INDUSTRIAL PARK ROAD LLC	\$0		1843/0205	29	06/11/2015
ARMETTA PHILIP C	\$0		0505/0134	29	02/22/1978

Building Information

Building 1 : Section 1

Year Built: 1986
Living Area: 28,684
Replacement Cost: \$1,523,694
Building Percent Good: 77
Replacement Cost
Less Depreciation: \$1,173,240


Building Attributes	
Field	Description
Style	Office/Warehs
Model	Industrial
Grade	C
Stories	1
Occupancy	2.00
Exterior Wall 1	Pre-finsh Metl
Exterior Wall 2	Concrete
Roof Structure	Flat
Roof Cover	Tar and Gravel
Interior Wall 1	Drywall
Interior Wall 2	
Interior Floor 1	Concrete
Interior Floor 2	Carpet
Heating Fuel	Gas
Heating Type	Forced Air
AC Type	Partial
Struct Class	
Bldg Use	Industrial
Cov Parking	0
Uncov Parking	0
Percent Fin	100
1st Floor Use	
Heat/AC	Heat/AC Pkg
Frame Type	Steel
Baths/Plumbing	Average
Ceiling/Walls	Typical
Rooms/Prtns	Average
Wall Height	25.00

Building Photo



(<https://images.vgsi.com/photos/MiddletownCTPhotos/10010211186.jpg>)

Building Layout



([ParcelSketch.ashx?pid=396&bid=396](#))

Building Sub-Areas (sq ft)		Legend	
Code	Description	Gross Area	Living Area
BAS	First Floor	24,104	24,104
FUS	Finished Upper Story	4,580	4,580
		28,684	28,684

Extra Features

Extra Features					<u>Legend</u>
Code	Description	Size	Value	Bldg #	
A/C	Air Condition	8896.00 UNITS	\$23,290		1

Land

Land Use

Use Code 301
Description Industrial
Zone IT
Neighborhood 3100
Alt Land Appr No
Category

Land Line Valuation

Size (Acres) 2.61
Assessed Value \$444,940
Appraised Value \$635,630


Outbuildings

Outbuildings					<u>Legend</u>	
Code	Description	Sub Code	Sub Description	Size	Value	Bldg #
LT1	Lights-In W/PI			4.00 UNITS	\$210	1
PAV1	Paving	AS	Asphalt	51134.00 UNITS	\$57,530	1
PAV2	Paving	CN	Concrete LD	2100.00 UNITS	\$3,830	1
CSHD	Cell Shed			288.00 UNITS	\$34,200	1

Valuation History

Appraisal			
Valuation Year	Improvements	Land	Total
2020	\$1,255,960	\$635,630	\$1,891,590
2019	\$1,255,960	\$635,630	\$1,891,590
2018	\$1,255,960	\$635,630	\$1,891,590

Assessment			
Valuation Year	Improvements	Land	Total
2020	\$879,170	\$444,940	\$1,324,110
2019	\$879,170	\$444,940	\$1,324,110
2018	\$879,170	\$444,940	\$1,324,110



90 Industrial Park Road

Map generated 9/20/2022



Map Legend: [<vision link>](http://gis.cityofmiddletown.com/middletownct/legend.pdf)


0 0.005 0.01 0.02 0.03 0.04 mi

1 in = 100 ft



MAP FOR REFERENCE ONLY - NOT A LEGAL DOCUMENT

Because of different update schedules, current property assessments may not reflect recent changes to property boundaries. Check with the Board of Assessors to confirm boundaries uses at the time of assessment.



RADIO FREQUENCY EMISSIONS ANALYSIS REPORT

EVALUATION OF HUMAN EXPOSURE POTENTIAL TO NON-IONIZING EMISSIONS



Site Name: CROMWELL EAST
Crown Castle Site# 825983
Site ID: CTL01044
Project Name: 5G NR 1SR C-BAND
Address: 90 INDUSTRIAL PARK ROAD,
 MIDDLETOWN, CT 06457
County: MIDDLESEX
Latitude: 41.5856311
Longitude: -72.7139711
Structure Type: MONOPOLE
Property Owner: AIRLINE AVENUE REALTY LLC
Property Contact: PAUL PEDICONE

AT&T Existing Facility

Report Information

Report Writer:

Sushil Dogra

Report Generated Date:

09-19-2022

Site Compliance Statement

Compliance Status	Compliant
Cumulative General Population % MPE (Ground Level)	25.62%

September 19, 2022

Emissions Analysis for Site: CTL01044– CROMWELL EAST

MobileComm Professionals, Inc was directed to analyze the proposed AT&T facility located at **90 INDUSTRIAL PARK ROAD, MIDDLETON, CT 06457**, for the purpose of determining whether the emissions from the Proposed AT&T Antenna Installation located on this property are within specified federal limits.

All information used in this report was analyzed as a percentage of current Maximum Permissible Exposure (% MPE) as listed in the FCC OET Bulletin 65 Edition 97-01 and ANSI/IEEE Std C95.1. The FCC regulates Maximum Permissible Exposure in units of milliwatts per square centimeter (mW/cm^2). The number of mW/cm^2 calculated at each sample point is called the power density. The exposure limit for power density varies depending upon the frequencies being utilized. Wireless Carriers and Paging Services use different frequency bands each with different exposure limits, therefore it is necessary to report results and limits in terms of percent MPE rather than power density.

All results were compared to the FCC (Federal Communications Commission) radio frequency exposure rules, 47 CFR 1.1307(b)(1) – (b)(3), to determine compliance with the Maximum Permissible Exposure (MPE) limits for General Population/Uncontrolled environments as defined below.

General population/uncontrolled exposure limits apply to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Therefore, members of the general public would always be considered under this category when exposure is not employment related, for example, in the case of a telecommunications tower that exposes persons in a nearby residential area.

Public exposure to radio frequencies is regulated and enforced in units of milliwatts per square centimeter (mW/cm^2). The general population exposure limits for the 700 and 850 MHz Bands are approximately 0.467 mW/cm^2 and 0.567 mW/cm^2 respectively. The general population exposure limit for the 1900 MHz (PCS), 2100 MHz (AWS), 2300 MHz (WCS), 3450 MHz (DoD Band) and 3840 MHz (C Band) bands is 1 mW/cm^2 . Because each carrier will be using different frequency bands, and each frequency band has different exposure limits, it is necessary to report percent of MPE rather than power density.

Occupational/controlled exposure limits apply to situations in which persons are exposed as a consequence of their employment and in which those persons who are exposed have been made fully aware of the potential for exposure and can exercise control over their exposure. Occupational/controlled exposure limits also apply where exposure is of a transient nature as a result of incidental passage through a location where exposure levels may be above general population/uncontrolled limits (see below), as long as the exposed person has been made fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Additional details can be found in FCC OET 65.

1. Theoretical Calculations

Calculations were done for the proposed AT&T Wireless antenna facility located at **90 INDUSTRIAL PARK ROAD, MIDDLETOWN, CT 06457** using the equipment information listed below. All calculations were performed per the specifications under FCC OET 65. Since AT&T is proposing highly focused directional panel antennas, which project most of the emitted energy out toward the horizon, all calculations were performed assuming a lobe representing the maximum gain of the antenna per the antenna manufacturer's supplied specifications, minus 10 dB for directional panel antennas and 20 dB for highly focused parabolic microwave dishes, was focused at the base of the tower. For this report, the sample point is the top of a 6-foot person standing at the base of the tower.

For all calculations, all equipment was calculated using the following assumptions:

- 1) 4 LTE channels (700 MHz Band 14) were considered for each sector of the proposed installation. These Channels have a transmit power of 40 Watts per Channel.
- 2) 2 LTE channels (700 MHz Band 29) were considered for each sector of the proposed installation. These Channels have a transmit power of 40 Watts per Channel.
- 3) 4 LTE/5G channels (1900 MHz) were considered for each sector of the proposed installation. These Channels have a transmit power of 40 Watts per Channel.
- 4) 4 LTE/5G channels (2100 MHz) were considered for each sector of the proposed installation. These Channels have a transmit power of 40 Watts per Channel.
- 5) 1 NR channel (DoD Band - 3450 MHz) was considered for each sector of the proposed installation. This Channel has a transmit power of 108.44 Watts per Channel.
- 6) 1 NR channel (C Band - 3840 MHz) was considered for each sector of the proposed installation. This Channel has a transmit power of 108.44 Watts per Channel.
- 7) 4 LTE channels (700 MHz Band 12) were considered for each sector of the proposed installation. These Channels have a transmit power of 40 Watts per Channel.
- 8) 4 5G channels (850 MHz Band) were considered for each sector of the proposed installation. These Channels have a transmit power of 40 Watts per Channel.
- 9) 4 LTE channels (WCS Band – 2300 MHz) were considered for each sector of the proposed installation. These Channels have a transmit power of 25 Watts per Channel.

- 10) All radios at the proposed installation were considered to be running at full power and were uncombined in their RF transmissions paths per carrier prescribed configuration. Per FCC OET Bulletin No. 65 - Edition 97-01 recommendations to achieve the maximum anticipated value at each sample point, all power levels emitting from the proposed antenna installation are increased by a factor of 2.56 to account for possible in-phase reflections from the surrounding environment. This is rarely the case, and if so, is never continuous.
- 11) For the following calculations, the sample point was the top of a 6-foot person standing at the base of the tower. The maximum gain of the antenna per the antenna manufacturer's supplied specifications, minus 10 dB for directional panel antennas and 20 dB for highly focused parabolic microwave dishes, was used in this direction. This value is a very conservative estimate as gain reductions for these particular antennas are typically much higher in this direction.
- 12) The antennas used in this modeling are the Quintel QD6616-7 for the 700 MHz(Band 14) / 700 MHz(Band 29) / 1900 MHz / 2100 MHz channel(s), the Ericsson AIR6419 for the DoD Band (3450 MHz) channel(s), the Ericsson AIR6449 for the C Band (3840 MHz) channel(s), the CCI DMP65R-BU6D for the 700 MHz(B12) / 850 MHz / WCS Band (2300 MHz) channel(s) in Sector A, Quintel QD6616-7 for the 700 MHz(Band 14) / 700 MHz(Band 29) / 1900 MHz / 2100 MHz channel(s), the Ericsson AIR6419 for the DoD Band (3450 MHz) channel(s), the Ericsson AIR6449 for the C Band (3840 MHz) channel(s), the CCI DMP65R-BU6D for the 700 MHz(B12) / 850 MHz / WCS Band (2300 MHz) channel(s) in Sector B, Quintel QD6616-7 for the 700 MHz(Band 14) / 700 MHz(Band 29) / 1900 MHz / 2100 MHz channel(s), the Ericsson AIR6419 for the DoD Band (3450 MHz) channel(s), the Ericsson AIR6449 for the C Band (3840 MHz) channel(s), the CCI DMP65R-BU6D for the 700 MHz(B12) / 850 MHz / WCS Band (2300 MHz) channel(s) in Sector C. This is based on feedback from the carrier with regard to anticipated antenna selection. All Antenna gain values and associated transmit power levels are shown in the Site Inventory and Power Data table below. The maximum gain of the antenna per the antenna manufacturer's supplied specifications, minus 10 dB for directional panel antennas and 20 dB for highly focused parabolic microwave dishes, was used for all calculations. This value is a very conservative estimate as gain reductions for these particular antennas are typically much higher in this direction.
- 13) The antenna mounting height centerline of the proposed antennas is 174 feet above ground level (AGL).
- 14) Emissions values for additional carriers were taken from the Connecticut Siting Council active database. Values in this database are provided by the individual carriers themselves.
- 15) All calculations were done with respect to uncontrolled / general population threshold limits.

2. Antenna Inventory & Power Data

Sector	Ant ID	Operator	Antenna Mfg	Antenna Model	Antenna Type	FREQ. (MHz)	TECH.	AZ. (°)	H B W (°)	Antenna Gain (dBd)	Antenna Aperture (ft)	#of Channels	Transmitter Power (Watts)	Total ERP (Watts)	Total EIRP (Watts)	Total Ant Transmitter Power (Watts)	Total Ant ERP(Watts)	Ant MPE%
A	1	AT&T	Quintel	QD6616-7	Panel	700	LTE(B14)	40	71	12.05	6	4	160.00	2566.12	4208.43	560	14714.06	2.27%
A	1	AT&T	Quintel	QD6616-7	Panel	700	LTE(B29)	40	71	12.05	6	2	80.00	1283.06	2104.21			
A	1	AT&T	Quintel	QD6616-7	Panel	1900	LTE/5G	40	67	15.05	6	4	160.00	5120.07	8396.92			
A	1	AT&T	Quintel	QD6616-7	Panel	2100	LTE/5G	40	62	15.55	6	4	160.00	5744.82	9421.50			
A	2-1	AT&T	Ericsson	AIR 6419 B77G	Panel	3450	5G	40	11	23.5	2.55	1	108.44	24277.05	39828.68	108.44	24277.05	2.83%
A	2-2	AT&T	Ericsson	AIR 6449 B77D	Panel	3840	5G	40	11	23.5	2.55	1	108.44	24277.05	39828.68	108.44	24277.05	2.94%
A	3	AT&T	CCI	DMP65R-BU6D	Panel	700	LTE(B12)	40	74	11.85	6	4	160.00	2450.62	4019.02	420	9482.79	1.72%
A	3	AT&T	CCI	DMP65R-BU6D	Panel	850	5G	40	63	12.45	6	4	160.00	2813.69	4614.45			
A	3	AT&T	CCI	DMP65R-BU6D	Panel	2300	LTE	40	54	16.25	6	4	100.00	4218.48	6918.31			
B	4	AT&T	Quintel	QD6616-7	Panel	700	LTE(B14)	150	71	12.05	6	4	160.00	2566.12	4208.43			
B	4	AT&T	Quintel	QD6616-7	Panel	700	LTE(B29)	150	71	12.05	6	2	80.00	1283.06	2104.21	560	14714.06	2.27%
B	4	AT&T	Quintel	QD6616-7	Panel	1900	LTE/5G	150	67	15.05	6	4	160.00	5120.07	8396.92			
B	4	AT&T	Quintel	QD6616-7	Panel	2100	LTE/5G	150	62	15.55	6	4	160.00	5744.82	9421.50			
B	5-1	AT&T	Ericsson	AIR 6419 B77G	Panel	3450	5G	150	11	23.5	2.55	1	108.44	24277.05	39828.68	108.44	24277.05	2.83%
B	5-2	AT&T	Ericsson	AIR 6449 B77D	Panel	3840	5G	150	11	23.5	2.55	1	108.44	24277.05	39828.68	108.44	24277.05	2.94%
B	6	AT&T	CCI	DMP65R-BU6D	Panel	700	LTE(B12)	150	74	11.85	6	4	160.00	2450.62	4019.02	420	9482.79	1.72%
B	6	AT&T	CCI	DMP65R-BU6D	Panel	850	5G	150	63	12.45	6	4	160.00	2813.69	4614.45			
B	6	AT&T	CCI	DMP65R-BU6D	Panel	2300	LTE	150	54	16.25	6	4	100.00	4218.48	6918.31			
C	7	AT&T	Quintel	QD6616-7	Panel	700	LTE(B14)	270	71	12.05	6	4	160.00	2566.12	4208.43	560	14714.06	2.27%
C	7	AT&T	Quintel	QD6616-7	Panel	700	LTE(B29)	270	71	12.05	6	2	80.00	1283.06	2104.21			
C	7	AT&T	Quintel	QD6616-7	Panel	1900	LTE/5G	270	67	15.05	6	4	160.00	5120.07	8396.92			
C	7	AT&T	Quintel	QD6616-7	Panel	2100	LTE/5G	270	62	15.55	6	4	160.00	5744.82	9421.50			
C	8-1	AT&T	Ericsson	AIR 6419 B77G	Panel	3450	5G	270	11	23.5	2.55	1	108.44	24277.05	39828.68	108.44	24277.05	2.83%
C	8-2	AT&T	Ericsson	AIR 6449 B77D	Panel	3840	5G	270	11	23.5	2.55	1	108.44	24277.05	39828.68	108.44	24277.05	2.94%
C	9	AT&T	CCI	DMP65R-BU6D	Panel	700	LTE(B12)	270	74	11.85	6	4	160.00	2450.62	4019.02	420	9482.79	1.72%
C	9	AT&T	CCI	DMP65R-BU6D	Panel	850	5G	270	63	12.45	6	4	160.00	2813.69	4614.45			
C	9	AT&T	CCI	DMP65R-BU6D	Panel	2300	LTE	270	54	16.25	6	4	100.00	4218.48	6918.31			

Table 2.1: Antenna Inventory & Power Data

*NOTE: 75% Duty Cycle and adjusted power reduction factor of 0.32 was applied to the AIR6449 & AIR6419 antennas per guidance from AT&T.

Specifications were not available for the Ericsson AIR 6419 antenna. Per AT&T, specifications for the AIR 6449 antenna were used to model the 6419 due to its similarity.

Cumulative Site MPE%	
Carrier	MPE%
AT&T (Max MPE% at Sector A)	9.76%
T-Mobile	7.19%
Verizon	8.19%
MetroPCS	0.48%
Site Total MPE%	25.62%

Table 2.2: Cumulative Site MPE%

AT&T Max MPE% Per Sector	
AT&T Sector A Total	9.76%
AT&T Sector B Total	9.76%
AT&T Sector C Total	9.76%
Site Total MPE%	25.62%

Table 2.3: AT&T MPE% Per Sector

Sector	Ant ID	Operator	Antenna Mfg	Antenna Model	FREQ. (MHz)	TECH.	#of Channels	Transmitter Power (Watts)	Total ERP (Watts)	Total EIRP (Watts)	Height (ft)	Total Power Density (mW/cm ²)	Allowable MPE (mW/cm ²)	Calculated MPE%
A	1	AT&T	Quintel	QD6616-7	700	LTE(B14)	4	160.00	2566.12	4208.43	174.00	0.003049	0.467	0.65%
A	1	AT&T	Quintel	QD6616-7	700	LTE(B29)	2	80.00	1283.06	2104.21	174.00	0.001525	0.467	0.33%
A	1	AT&T	Quintel	QD6616-7	1900	LTE/5G	4	160.00	5120.07	8396.92	174.00	0.006084	1.000	0.61%
A	1	AT&T	Quintel	QD6616-7	2100	LTE/5G	4	160.00	5744.82	9421.50	174.00	0.006826	1.000	0.68%
A	2-1	AT&T	Ericsson	AIR 6419 B77G	3450	5G	1	108.44	24277.05	39828.68	175.75	0.028286	1.000	2.83%
A	2-2	AT&T	Ericsson	AIR 6449 B77D	3840	5G	1	108.44	24277.05	39828.68	172.25	0.029447	1.000	2.94%
A	3	AT&T	CCI	DMP65R-BU6D	700	LTE(B12)	4	160.00	2450.62	4019.02	174.00	0.002912	0.467	0.62%
A	3	AT&T	CCI	DMP65R-BU6D	850	5G	4	160.00	2813.69	4614.45	174.00	0.003343	0.567	0.59%
A	3	AT&T	CCI	DMP65R-BU6D	2300	LTE	4	100.00	4218.48	6918.31	174.00	0.005013	1.000	0.50%
													Total	9.76%

Table 2.4: Detailed MPE% at AT&T Sector A

3. Compliance Summary

All calculations performed for this analysis yielded results that were **within** the allowable limits for general public exposure to RF Emissions.

The anticipated maximum composite contributions from the AT&T facility as well as the site composite emissions value with regards to compliance with FCC's allowable limits for general public exposure to RF Emissions are shown here:

AT&T Sector	Power Density Value (%)
Sector A	9.76%
Sector B	9.76%
Sector C	9.76%
AT&T Maximum Total (per sector)	9.76%
Site Total MPE%	25.62%
Site Compliance Status	COMPLIANT

The anticipated composite MPE value for this site assuming all carriers present is 25.62% of the allowable FCC established general public limit sampled at the ground level. This is based upon values listed in the Connecticut Siting Council database for existing carrier emissions.

FCC guidelines state that if a site is found to be out of compliance (over allowable thresholds), that carriers over a 5% contribution to the composite value will require measures to bring the site into compliance. For this facility, the composite values calculated were within the allowable 100% threshold standard per the federal government.



Date: May 24, 2022

MTS Engineering, P.L.L.C.
1717 S. Boulder, Suite 300
Tulsa, OK 74119
(918) 587-4630
towersupport@btgrp.com

Subject:	Mount Replacement Analysis Report	
Carrier Designation:	AT&T Mobility Equipment Change-Out	
	Carrier Site Number:	CTL01044
	Carrier Site Name:	Cromwell East
	Carrier FA Number:	10035130
Crown Castle Designation:	BU Number:	825983
	Site Name:	Middletown_1
	JDE Job Number:	716731
	Order Number:	616581, Rev.0
Engineering Firm Designation:	Report Designation:	136918.010.01
Site Data:	90 Industrial Park Road, Middletown, CT, Middlesex County, 06457 Latitude 41° 35' 8.30" Longitude -72° 42' 50.49"	
Structure Information:	Tower Height & Type:	185 ft. Monopole
	Mount Elevation:	174 ft.
	Mount Type:	14.5 ft. Sector Mount

We are pleased to submit this “**Mount Replacement Analysis Report**” to determine the structural integrity of AT&T Mobility’s antenna mounting system with the proposed appurtenance and equipment addition on the abovementioned supporting tower structure. Analysis of the existing supporting tower structure is to be completed by others and therefore is not part of this analysis. Analysis of the antenna mounting system as a tie-off point for fall protection or rigging is not part of this document.

The purpose of the analysis is to determine acceptability of the mount’s stress level. Based on our analysis we have determined the stress level to be:

Sector Mount


Sufficient

*Sufficient upon completion of the changes listed in the ‘Recommendations’ section of this report.

This analysis has been performed in accordance with the 2018 International Building Code based upon an ultimate 3-second gust wind speed of 119 mph. Applicable Standard references and design criteria are listed in Section 2 - Analysis Criteria.

Mount structural analysis prepared by: Erika Ruiz

Respectfully submitted by: MTS Engineering, P.L.L.C.
COA: BER: 2386985 Expires: 02/01/2023



Chad E. Tuttle, P.E.

TABLE OF CONTENTS

1) INTRODUCTION

2) ANALYSIS CRITERIA

Table 1 - Proposed Equipment Configuration
Table 2 - Documents Provided

3) ANALYSIS PROCEDURE

3.1) Analysis Method
3.2) Assumptions

4) ANALYSIS RESULTS

Table 3 - Mount Component Stresses vs. Capacity
4.1) Recommendations

5) APPENDIX A

Wire Frame and Rendered Models

6) APPENDIX B

Software Input Calculations

7) APPENDIX C

Software Analysis Output

8) APPENDIX D

Additional Calculations

9) APPENDIX E

Supplemental Drawings

1) INTRODUCTION

This is a proposed 3 - Sector 14.5' Sector Mount, designed by SitePro1 (Part #VFA14-WLL-30120 w/ Sabre Part # C10-899-050).

2) ANALYSIS CRITERIA

Building Code:	2018 IBC
TIA-222 Revision:	TIA-222-H
Risk Category:	II
Ultimate Wind Speed:	119 mph
Exposure Category:	C
Topographic Factor at Base:	1
Topographic Factor at Mount:	1
Ice Thickness:	1.0 in
Wind Speed with Ice:	50 mph
Seismic S _a :	0.205
Seismic S ₁ :	0.055
Live Loading Wind Speed:	30 mph
Man Live Load at Mid/End-Points:	250 lb.
Man Live Load at Mount Pipes:	500 lb.

Table 1 – Proposed Equipment Configuration

Mount Centerline (ft.)	Antenna Centerline (ft.)	Number of Antennas	Manufacturer	Model / Type	Mount / Modification Details
174	174	176	Ericsson	AIR 6419 B77G	14.5' Sector Mount
		3	CCI Antennas	DMP65R-BU6D	
		3	Quintel	QD6616-7	
		3	Ericsson	RRUS 32 B66A	
		3	Ericsson	RRUS 4449 B5/B12	
		3	Ericsson	RRUS 4478 B14_CCIV2	
		3	Ericsson	RRUS-32 B30	
		2	Raycap	DC6-48-60-18-8F	
		1	Raycap	DC9-48-60-24-8C-EV	
		3	Ericsson	RRUS 4415 B25 CCIV2	
		3	Ericsson	RRUS E2 B29	
		172	Ericsson	AIR 6449 B77D	

Table 2 – Documents Provided

Document	Remarks	Reference	Source
CCI Order	Existing Loading Proposed Loading	Date: 05/04/2022	Crown Castle
RFDS		Date: 03/15/2022	
CD's		Date: 04/12/2022	
Previous MA	MTS Engineering, P.L.L.C.	Date: 12/24/2021	On File
Mount Manufacturer Drawing	SitePro1 (Part #VFA14-WLL-30120)	Date: 09/21/2020	SitePro1

3) ANALYSIS PROCEDURE

3.1) Analysis Method

RISA-3D (Version 20.0.1), a commercially available analysis software package, was used to create a three-dimensional model of the antenna mounting system and calculate member stresses for various loading cases.

A tool internally developed by MTS Engineering, P.L.L.C., was used to calculate wind loading on all appurtenances, dishes and mount members for various loading cases. Selected output from the analysis is included in Appendix B.

This analysis was performed in accordance with Crown Castle's ENG-SOW-10208 *Mount Analysis* (Revision E). In addition, this analysis is in accordance with AT&T's *Mount Technical Directive – R21.0*.

Manufacturers drawing were used to create the model.

3.2) Assumptions

1. The antenna mounting system was properly fabricated, installed and maintained in good condition in accordance with its original design, TIA Standards, and/or manufacturer's specifications.
2. The configuration of antennas, mounts, and other appurtenances are as specified in Table-1.
3. All member connections are assumed to have been designed to meet or exceed the load carrying capacity of the connected members unless otherwise specified in this report.
4. Mount areas and weights are determined from field measurements, standard material properties, and/or manufacturer product data.
5. Serviceability with respect to antenna twist, tilt, roll or lateral translation is not checked and is left to the carrier or tower owner to ensure conformance.
6. Prior structural modifications to the tower mounting system are assumed to be installed as shown per available data.
7. The analysis will be required to be revised if the existing conditions in the field differ from those shown in the above-referenced documents or assumed in this analysis. No allowance was made for any damaged, missing, or rusted members.
8. The following material grades were assumed (Unless Noted Otherwise):
 - (a) Connection Bolts : ASTM A325
 - (b) Steel Pipe : ASTM A53 (GR. 35)
 - (c) HSS (Round) : ASTM 500 (GR. B-42)
 - (d) HSS (Rectangular) : ASTM 500 (GR. B-46)
 - (e) Channel : ASTM A36 (GR. 36)
 - (f) Steel Solid Rod : ASTM A36 (GR. 36)
 - (g) Steel Plate : ASTM A36 (GR. 36)
 - (h) Steel Angle : ASTM A36 (GR. 36)
 - (i) UNISTRUT : ASTM A570 (GR. 33)

This analysis may be affected if any assumptions are not valid or have been made in error. MTS Engineering, P.L.L.C. should be notified to determine the effect on the structural integrity of the antenna mounting system.

4) ANALYSIS RESULTS

Table 3 - Mount Component Stresses vs. Capacity (Sector Mount)

Notes	Component	Centerline (ft.)	Critical Member	% Capacity	Pass / Fail
1	Face Horizontals	174	1	37.6	Pass
	Support Arms		21	28.4	Pass
	Connection Plates		6	40.6	Pass
	Verticals		31	60.0	Pass
	Diagonals		35	19.5	Pass
	Mount Pipes		39	57.0	Pass
	Tiebacks		181	13.2	Pass
	Connection Pipes		146	43.2	Pass
2	Mount to Tower Connection		-	45.6	Pass

Structure Rating with Recommendations (max from all components) =	60.0%
--	--------------

Notes:

- 1) See additional documentation in "Appendix C - Software Analysis Output" for calculations supporting the % capacity consumed.
- 2) See additional documentation in "Appendix D - Additional Calculations" for calculations supporting the % capacity reported.



4.1) Recommendations

The proposed mount has sufficient capacity to support the proposed loading configuration. In order for the results of this analysis to be considered valid, the mount listed below shall be installed.

1. Mount replacement, SitePro1 Part #VFA14-WLL-30120 (P/N: CEQ.53332) w/ Sabre Part # C10-899-050 (P/N: ANT.46131).
2. Install (2) 2" Std. x 6'-0" long pipes "or equivalent approved Conmat item" on V-Booms per sector to install RRUS on all sectors.

Beyond the mount replacement, no structural modifications are required at this time, provided that the above-listed changes are implemented.

APPENDIX A
WIRE FRAME AND RENDERED MODELS



Envelope Only Solution

MTS Engineering, P.L.L.C.

GRG



136918.010.01

825983 - Middletown_1

GRG-1

May 24, 2022

136918_010_01_Middletown_1_C...



Envelope Only Solution

MTS Engineering, P.L.L.C.

GRG



136918.010.01

825983 - Middletown_1

GRG-2




May 24, 2022

136918_010_01_Middletown_1_C...



Envelope Only Solution

MTS Engineering, P.L.L.C.	825983 - Middletown_1	GRG-3
GRG		May 24, 2022
136918.010.01		136918_010_01_Middletown_1_C...



Member Code Checks Displayed (Enveloped)
Envelope Only Solution

MTS Engineering, P.L.L.C.

GRG




136918.010.01

825983 - Middletown_1

GRG-4

May 24, 2022

136918_010_01_Middletown_1_C...



Member Shear Checks Displayed (Enveloped)
Envelope Only Solution

MTS Engineering, P.L.L.C.

GRG

136918.010.01

825983 - Middletown_1

GRG-5

May 24, 2022

136918_010_01_Middletown_1_C...



APPENDIX B
SOFTWARE INPUT CALCULATIONS

ASCE 7 Hazards Report

Address:
No Address at This Location

Standard: ASCE/SEI 7-16
Risk Category: II
Soil Class: D - Default (see Section 11.4.3)

Elevation: 89.45 ft (NAVD 88)
Latitude: 41.585639
Longitude: -72.714025



Wind

Results:

Wind Speed	119 Vmph
10-year MRI	75 Vmph
25-year MRI	84 Vmph
50-year MRI	90 Vmph
100-year MRI	98 Vmph

Data Source: ASCE/SEI 7-16, Fig. 26.5-1B and Figs. CC.2-1–CC.2-4, and Section 26.5.2

Date Accessed: Fri May 06 2022

Value provided is 3-second gust wind speeds at 33 ft above ground for Exposure C Category, based on linear interpolation between contours. Wind speeds are interpolated in accordance with the 7-16 Standard. Wind speeds correspond to approximately a 7% probability of exceedance in 50 years (annual exceedance probability = 0.00143, MRI = 700 years).

Site is in a hurricane-prone region as defined in ASCE/SEI 7-16 Section 26.2. Glazed openings need not be protected against wind-borne debris.





Seismic

Site Soil Class: D - Default (see Section 11.4.3)

Results:

S_s :	0.205	S_{D1} :	0.089
S_1 :	0.055	T_L :	6
F_a :	1.6	PGA :	0.113
F_v :	2.4	PGA_M :	0.178
S_{MS} :	0.328	F_{PGA} :	1.573
S_{M1} :	0.133	I_e :	1
S_{DS} :	0.219	C_v :	0.71

Seismic Design Category B



Data Accessed: Fri May 06 2022

Date Source:

USGS Seismic Design Maps based on ASCE/SEI 7-16 and ASCE/SEI 7-16 Table 1.5-2. Additional data for site-specific ground motion procedures in accordance with ASCE/SEI 7-16 Ch. 21 are available from USGS.

Ice

Results:

Ice Thickness: 1.00 in.

Concurrent Temperature: 15 F

Gust Speed 50 mph

Data Source: Standard ASCE/SEI 7-16, Figs. 10-2 through 10-8

Date Accessed: Fri May 06 2022

Ice thicknesses on structures in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.

Values provided are equivalent radial ice thicknesses due to freezing rain with concurrent 3-second gust speeds, for a 500-year mean recurrence interval, and temperatures concurrent with ice thicknesses due to freezing rain. Thicknesses for ice accretions caused by other sources shall be obtained from local meteorological studies. Ice thicknesses in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.

The ASCE 7 Hazard Tool is provided for your convenience, for informational purposes only, and is provided "as is" and without warranties of any kind. The location data included herein has been obtained from information developed, produced, and maintained by third party providers; or has been extrapolated from maps incorporated in the ASCE 7 standard. While ASCE has made every effort to use data obtained from reliable sources or methodologies, ASCE does not make any representations or warranties as to the accuracy, completeness, reliability, currency, or quality of any data provided herein. Any third-party links provided by this Tool should not be construed as an endorsement, affiliation, relationship, or sponsorship of such third-party content by or from ASCE.

ASCE does not intend, nor should anyone interpret, the results provided by this Tool to replace the sound judgment of a competent professional, having knowledge and experience in the appropriate field(s) of practice, nor to substitute for the standard of care required of such professionals in interpreting and applying the contents of this Tool or the ASCE 7 standard.

In using this Tool, you expressly assume all risks associated with your use. Under no circumstances shall ASCE or its officers, directors, employees, members, affiliates, or agents be liable to you or any other person for any direct, indirect, special, incidental, or consequential damages arising from or related to your use of, or reliance on, the Tool or any information obtained therein. To the fullest extent permitted by law, you agree to release and hold harmless ASCE from any and all liability of any nature arising out of or resulting from any use of data provided by the ASCE 7 Hazard Tool.

PROJECT	136918.010.01 - Middletown_1, CT	KSC
SUBJECT	Sector Mount Analysis	
DATE	05/24/22	



B+T Group
 1717 S. Boulder, Suite 300
 Tulsa, OK 74119
 (918) 587-4630

B+T GRP

Tower Type	:	Monopole	
Ground Elevation	z_s	: 89 ft	[ASCE7 Hazard Tool]
Tower Height	:	185.00 ft	
Mount Elevation	:	174.00 ft	
Antenna Elevation	:	176.00 ft	
Crest Height	:	0 ft	
Risk Category	:	II	[Table 2-1]
Exposure Category	:	C	[Sec. 2.6.5.1.2]
Topography Category	:	1.00	[Sec. 2.6.6.2]
Wind Velocity	V	: 119 mph	[ASCE7 Hazard Tool]
Ice wind Velocity	V_i	: 50 mph	[ASCE7 Hazard Tool]
Service Velocity	V_s	: 30 mph	[ASCE7 Hazard Tool]
Base Ice thickness	t_i	: 1.00 in	[ASCE7 Hazard Tool]
Seismic Design Cat.	:	B	[ASCE7 Hazard Tool]
	S_s	: 0.21	
	S_1	: 0.06	
	S_{DS}	: 0.22	
	S_{D1}	: 0.09	
Gust Factor	G_h	: 1.00	[Sec. 16.6]
Pressure Coefficient	K_z	: 1.43	[Sec. 2.6.5.2]
Topography Facto	K_{zt}	: 1.00	[Sec. 2.6.6]
Elevation Factor	K_e	: 1.00	[Sec. 2.6.8]
Directionality Factor	K_d	: 0.95	[Sec. 16.6]
Shielding Factor	K_a	: 0.90	[Sec. 16.6]
Design Ice Thickness	t_{iz}	: 1.18 in	[Sec. 2.6.10]
Importance Factor	I_e	: 1	[Table 2-3]
Response Coefficient	C_s	: 0.110	[Sec. 2.7.7.1]
Amplification	A_s	: 2.762162	[Sec. 16.7]
	q_z	: 48.82 psf	

PROJECT	136918.010.01 - Middletown_1, CT			KSC
SUBJECT	Sector Mount Analysis			
DATE	05/24/22			



B+T Group
 1717 S. Boulder, Suite 300
 Tulsa, OK 74119
 (918) 587-4630

B+T GRP

Manufacturer	Model	Qty	Height (in ²)	Width (in ²)	Depth (in ²)	Weight (lbs)	C _a A _a (N) (ft ²)	C _a A _a (T) (ft ²)	C _a A _a (N) Ice (ft ²)	C _a A _a (T) Ice (ft ²)	F _A (N) (k)	F _A (T) (k)	F _A (N) Ice (k)	F _A (T) Ice (k)
INTEL TECHNOLOGIES	QD6616-7	0.5	72.0	22.0	9.6	130.0	6.80	2.96	7.62	3.68	0.33	0.14	0.07	0.03
INTEL TECHNOLOGIES	QD6616-7	0.5					6.80	2.96	7.62	3.68	0.33	0.14	0.07	0.03
ERICSSON	AIR 6419 B77G	0.5	28.0	15.8	6.7	66.2	2.32	0.94	2.80	1.31	0.11	0.05	0.02	0.01
ERICSSON	AIR 6419 B77G	0.5					2.32	0.94	2.80	1.31	0.11	0.05	0.02	0.01
ERICSSON	AIR 6449 B77D	0.5	30.4	15.9	8.1	81.6	1.82	0.86	2.19	1.17	0.09	0.04	0.02	0.01
ERICSSON	AIR 6449 B77D	0.5	30.4	15.9	8.1	81.6	1.82	0.86	2.19	1.17	0.09	0.04	0.02	0.01
CCI ANTENNAS	DMP65R-BU6D	0.5	71.2	20.7	7.7	89.3	5.97	2.24	6.73	2.89	0.29	0.11	0.06	0.02
CCI ANTENNAS	DMP65R-BU6D	0.5					5.97	2.24	6.73	2.89	0.29	0.11	0.06	0.02
INTEL TECHNOLOGIES	QD6616-7	0.5	72.0	22.0	9.6	130.0	6.80	2.96	7.62	3.68	0.33	0.14	0.07	0.03
INTEL TECHNOLOGIES	QD6616-7	0.5					6.80	2.96	7.62	3.68	0.33	0.14	0.07	0.03
ERICSSON	AIR 6419 B77G	0.5	28.0	15.8	6.7	66.2	2.32	0.94	2.80	1.31	0.11	0.05	0.02	0.01
ERICSSON	AIR 6419 B77G	0.5					2.32	0.94	2.80	1.31	0.11	0.05	0.02	0.01
ERICSSON	AIR 6449 B77D	0.5	30.4	15.9	8.1	81.6	1.82	0.86	2.19	1.17	0.09	0.04	0.02	0.01
ERICSSON	AIR 6449 B77D	0.5	30.4	15.9	8.1	81.6	1.82	0.86	2.19	1.17	0.09	0.04	0.02	0.01
CCI ANTENNAS	DMP65R-BU6D	0.5	71.2	20.7	7.7	89.3	5.97	2.24	6.73	2.89	0.29	0.11	0.06	0.02
CCI ANTENNAS	DMP65R-BU6D	0.5					5.97	2.24	6.73	2.89	0.29	0.11	0.06	0.02
INTEL TECHNOLOGIES	QD6616-7	0.5	72.0	22.0	9.6	130.0	6.80	2.96	7.62	3.68	0.33	0.14	0.07	0.03
INTEL TECHNOLOGIES	QD6616-7	0.5					6.80	2.96	7.62	3.68	0.33	0.14	0.07	0.03
ERICSSON	AIR 6419 B77G	0.5	28.0	15.8	6.7	66.2	2.32	0.94	2.80	1.31	0.11	0.05	0.02	0.01
ERICSSON	AIR 6419 B77G	0.5					2.32	0.94	2.80	1.31	0.11	0.05	0.02	0.01
ERICSSON	AIR 6449 B77D	0.5	30.4	15.9	8.1	81.6	1.82	0.86	2.19	1.17	0.09	0.04	0.02	0.01
ERICSSON	AIR 6449 B77D	0.5	30.4	15.9	8.1	81.6	1.82	0.86	2.19	1.17	0.09	0.04	0.02	0.01

PROJECT	136918.010.01 - Middletown_1, CT	KSC
SUBJECT	Sector Mount Analysis	
DATE	05/24/22	



B+T Group

1717 S. Boulder, Suite 300
Tulsa, OK 74119
(918) 587-4630

B+T GRP

APPENDIX C
SOFTWARE ANALYSIS OUTPUT

Node Coordinates

Label	X [ft]	Y [ft]	Z [ft]	Detach From Diaphragm
1	1	7.25	-0.739585	5.166666
2	2	-7.25	-0.739585	5.166666
3	3	7.25	-4.072918	5.166666
4	4	-7.25	-4.072918	5.166666
5	5	-2.458333	-0.739585	5.166666
6	6	-2.458333	-4.072918	5.166666
7	7	2.458333	-4.072918	5.166666
8	8	2.458333	-0.739585	5.166666
9	9	0	-0.885418	2.416666
10	10	-2.458333	-0.885418	5.166666
11	11	-2.458333	-4.218752	5.166666
12	12	2.458333	-4.218752	5.166666
13	13	2.458333	-0.885418	5.166666
14	14	-2.458333	-0.885418	5.401041
15	15	-2.458333	-4.218752	5.401041
16	16	2.458333	-4.218752	5.401041
17	17	2.458333	-0.885418	5.401041
18	18	-2.458333	-0.885418	4.942708
19	19	-2.458333	-4.218752	4.942708
20	20	2.458333	-4.218752	4.942708
21	21	2.458333	-0.885418	4.942708
22	22	0	-4.218752	2.416666
23	23	0	-0.885418	3.333333
24	24	0	-4.218752	3.333333
25	25	0	-0.885418	3.187499
26	26	0	-4.218752	3.187499
27	27	0.458333	-0.885418	3.187499
28	28	0.458333	-4.218752	3.187499
29	29	-0.458333	-0.885418	3.187499
30	30	-0.458333	-4.218752	3.187499
31	31	-0.518814	-0.885418	3.240578
32	32	-2.397829	-0.885418	4.889609
33	33	-0.518814	-4.218752	3.240578
34	34	-2.397829	-4.218752	4.889609
35	35	0.518814	-0.885418	3.240578
36	36	2.397829	-0.885418	4.889609
37	37	0.518814	-4.218752	3.240578
38	38	2.397829	-4.218752	4.889609
39	39	-2.272561	-0.885418	4.779673
40	40	-2.272561	-4.218752	4.779673
41	41	-0.644082	-0.885418	3.350513
42	42	-0.644082	-4.218752	3.350513
43	43	2.272561	-0.885418	4.779673
44	44	2.272561	-4.218752	4.779673
45	45	0.644082	-0.885418	3.350513
46	46	0.644082	-4.218752	3.350513
47	47	6.95833	-0.739585	5.166666
48	48	6.95833	-4.072918	5.166666
49	49	6.95833	-0.739585	5.416666
50	50	6.95833	-4.072918	5.416666
51	51	6.95833	-7.656252	5.416666
52	52	6.95833	2.843748	5.416666
53	53	3.375	-0.739585	5.166666
54	54	0	-0.885418	1.354166
55	55	0	-4.218752	1.354166

Node Coordinates (Continued)

Label		X [ft]	Y [ft]	Z [ft]	Detach From Diaphragm
56	56	-3.375	-0.739585	5.166666	
57	57	0	0.947917	1.354166	
58	58	0	-6.052087	1.354166	
59	59	0	-5.052085	1.354166	
60	60	0	-0.052085	1.354166	
61	61	0	-5.052085	1.166666	
62	62	0	-0.052085	1.166666	
63	63	0	-0.468418	1.354166	
64	64	0	-1.302418	1.354166	
65	65	2.23	-0.739585	5.166666	
66	66	2.23	-4.072918	5.166666	
67	67	2.3	-0.739585	5.416666	
68	68	2.3	-4.072918	5.416666	
69	69	2.3	-7.656252	5.416666	
70	70	2.3	2.843748	5.416666	
71	71	0	0	0	
72	72	-2.3	-0.739585	5.166666	
73	73	-2.3	-4.072918	5.166666	
74	74	-2.3	-0.739585	5.416666	
75	75	-2.3	-4.072918	5.416666	
76	76	-2.3	-7.656252	5.416666	
77	77	-2.3	2.843748	5.416666	
78	78	1.458322	-0.885418	4.065093	
79	79	1.585594	-0.885418	3.913416	
80	80	1.458322	-4.218752	4.065093	
81	81	1.585594	-4.218418	3.913416	
82	82	1.585594	0.448082	3.913416	
83	83	1.585594	-5.551918	3.913416	
84	84	-1.458322	-0.885418	4.065093	
85	85	-1.585594	-0.885418	3.913416	
86	86	-1.458322	-4.218752	4.065093	
87	87	-1.585594	-4.218418	3.913416	
88	88	-1.585594	0.448082	3.913416	
89	89	-1.585594	-5.551918	3.913416	
90	137	1.172742	-0.885418	-0.677083	
91	138	1.172742	-4.218752	-0.677083	
92	140	1.172742	0.947917	-0.677083	
93	141	1.172742	-6.052087	-0.677083	
94	142	1.172742	-5.052085	-0.677083	
95	143	1.172742	-0.052085	-0.677083	
96	146	1.172742	-0.468418	-0.677083	
97	147	1.172742	-1.302418	-0.677083	
98	205	-1.172742	-0.885418	-0.677083	
99	206	-1.172742	-4.218752	-0.677083	
100	208	-1.172742	0.947917	-0.677083	
101	209	-1.172742	-6.052087	-0.677083	
102	210	-1.172742	-5.052085	-0.677083	
103	211	-1.172742	-0.052085	-0.677083	
104	214	-1.172742	-0.468418	-0.677083	
105	215	-1.172742	-1.302418	-0.677083	
106	114	0.849464	-0.739585	-8.862017	
107	115	5.275599	-0.885418	-0.421741	
108	116	2.547015	-4.218752	-2.069595	
109	117	5.703631	-4.072918	-0.454354	
110	118	8.099464	-0.739585	3.695351	

Node Coordinates (Continued)

Label		X [ft]	Y [ft]	Z [ft]	Detach From Diaphragm
111	119	0.849464	-4.072918	-8.862017	
112	120	3.245297	-4.072918	-4.712312	
113	121	8.099464	-4.072918	3.695351	
114	122	2.989622	-4.218752	-1.196821	
115	123	2.886751	-4.218752	-1.666666	
116	124	5.703631	-0.885418	-0.454354	
117	125	3.245297	-0.739585	-4.712312	
118	126	5.703631	-0.739585	-0.454354	
119	127	3.06583	-0.885418	-1.170982	
120	128	2.092894	-0.885418	-1.208333	
121	129	5.703631	-4.218752	-0.454354	
122	130	1.010362	-5.052085	-0.583333	
123	131	5.509677	-4.218752	-0.342375	
124	132	3.245297	-0.885418	-4.712312	
125	133	3.245297	-4.218752	-4.712312	
126	134	5.906605	-0.885418	-0.571541	
127	135	5.906605	-4.218752	-0.571541	
128	136	3.448272	-4.218752	-4.8295	
129	139	2.579588	-4.218752	-2.233048	
130	144	3.448272	-0.885418	-4.8295	
131	145	1.211805	2.843748	-8.734424	
132	148	5.509677	-0.885418	-0.342375	
133	149	0.995299	-4.072918	-8.609424	
134	150	3.051344	-4.218752	-4.600333	
135	151	3.003038	-0.885418	-4.357933	
136	152	3.051344	-0.885418	-4.600333	
137	153	2.092894	-4.218752	-1.208333	
138	154	1.010362	-5.052085	-0.583333	
139	155	2.547015	-0.885418	-2.069595	
140	156	2.531289	-4.218752	-1.990678	
141	158	2.886751	-0.885418	-1.666666	
142	159	5.43344	-4.218752	-0.368224	
143	160	2.760455	-0.885418	-1.59375	
144	161	3.035611	-0.885418	-4.521385	
145	162	2.760455	-4.218752	-1.59375	
146	163	3.22367	-0.885418	-1.117465	
147	164	2.531289	-0.885418	-1.990678	
148	165	2.989622	-0.885418	-1.196821	
149	166	5.43344	-0.885418	-0.368224	
150	167	3.06583	-4.218752	-1.170982	
151	168	3.035611	-4.218752	-4.521385	
152	169	4.181915	-4.218418	-0.583544	
153	170	5.275599	-4.218752	-0.421741	
154	171	6.161964	-0.739585	0.339503	
155	172	3.22367	-4.218752	-1.117465	
156	173	3.003038	-4.218752	-4.357933	
157	174	2.579588	-0.885418	-2.233048	
158	175	0.995299	-0.739585	-8.609424	
159	176	1.211805	-0.739585	-8.734424	
160	177	1.211805	-4.072918	-8.734424	
161	178	1.211805	-7.656252	-8.734424	
162	179	2.791313	-0.885418	-3.29549	
163	180	2.786964	-0.739585	-5.506169	
164	181	3.54097	-0.739585	-4.700191	
165	182	3.54097	2.843748	-4.700191	

Node Coordinates (Continued)

Label		X [ft]	Y [ft]	Z [ft]	Detach From Diaphragm
166	183	5.624464	-4.072918	-0.591475	
167	185	5.84097	2.843748	-0.716475	
168	186	2.596321	-0.885418	-3.329873	
169	187	2.791313	-4.218752	-3.29549	
170	188	2.596321	-4.218418	-3.329873	
171	189	2.596321	0.448082	-3.329873	
172	190	2.596321	-5.551918	-3.329873	
173	191	4.249635	-0.885418	-0.769603	
174	192	4.181915	-0.885418	-0.583544	
175	193	4.249635	-4.218752	-0.769603	
176	194	4.181915	0.448082	-0.583544	
177	195	4.181915	-5.551918	-0.583544	
178	199	7.953629	-4.072918	3.442758	
179	200	7.953629	-0.739585	3.442758	
180	202	3.359464	-0.739585	-4.51457	
181	203	3.359464	-4.072918	-4.51457	
182	204	5.624464	-0.739585	-0.591475	
183	207	5.84097	-0.739585	-0.716475	
184	212	5.84097	-4.072918	-0.716475	
185	213	5.84097	-7.656252	-0.716475	
186	216	3.54097	-4.072918	-4.700191	
187	217	3.54097	-7.656252	-4.700191	
188	218	-8.099464	-0.739585	3.695351	
189	219	-3.003038	-0.885418	-4.357933	
190	220	-3.06583	-4.218752	-1.170982	
191	221	-3.245297	-4.072918	-4.712312	
192	222	-0.849464	-0.739585	-8.862017	
193	223	-8.099464	-4.072918	3.695351	
194	224	-5.703631	-4.072918	-0.454354	
195	225	-0.849464	-4.072918	-8.862017	
196	226	-2.531289	-4.218752	-1.990678	
197	227	-2.886751	-4.218752	-1.666666	
198	228	-3.245297	-0.885418	-4.712312	
199	229	-5.703631	-0.739585	-0.454354	
200	230	-3.245297	-0.739585	-4.712312	
201	231	-2.547015	-0.885418	-2.069595	
202	232	-2.092894	-0.885418	-1.208333	
203	233	-3.245297	-4.218752	-4.712312	
204	234	-1.010362	-5.052085	-0.583333	
205	235	-3.051344	-4.218752	-4.600333	
206	236	-5.703631	-0.885418	-0.454354	
207	237	-5.703631	-4.218752	-0.454354	
208	238	-3.448272	-0.885418	-4.8295	
209	239	-3.448272	-4.218752	-4.8295	
210	240	-5.906605	-4.218752	-0.571541	
211	241	-3.22367	-4.218752	-1.117465	
212	242	-5.906605	-0.885418	-0.571541	
213	243	-8.170135	2.843748	3.317758	
214	244	-3.051344	-0.885418	-4.600333	
215	245	-7.953629	-4.072918	3.442758	
216	246	-5.509677	-4.218752	-0.342375	
217	247	-5.275599	-0.885418	-0.421741	
218	248	-5.509677	-0.885418	-0.342375	
219	249	-2.092894	-4.218752	-1.208333	
220	250	-1.010362	-0.052085	-0.583333	

Node Coordinates (Continued)

Label	X [ft]	Y [ft]	Z [ft]	Detach From Diaphragm
221	251	-3.06583	-0.885418	-1.170982
222	252	-2.989622	-4.218752	-1.196821
223	254	-2.886751	-0.885418	-1.666666
224	255	-3.035611	-4.218752	-4.521385
225	256	-2.760455	-0.885418	-1.59375
226	257	-5.43344	-0.885418	-0.368224
227	258	-2.760455	-4.218752	-1.59375
228	259	-2.579588	-0.885418	-2.233048
229	260	-2.989622	-0.885418	-1.196821
230	261	-2.531289	-0.885418	-1.990678
231	262	-3.035611	-0.885418	-4.521385
232	263	-2.547015	-4.218752	-2.069595
233	264	-5.43344	-4.218752	-0.368224
234	265	-2.596321	-4.218418	-3.329873
235	266	-3.003038	-4.218752	-4.357933
236	267	-2.786964	-0.739585	-5.506169
237	268	-2.579588	-4.218752	-2.233048
238	269	-5.275599	-4.218752	-0.421741
239	272	-3.22367	-0.885418	-1.117465
240	273	-7.953629	-0.739585	3.442758
241	274	-8.170135	-0.739585	3.317758
242	275	-8.170135	-4.072918	3.317758
243	282	-8.170135	-7.656252	3.317758
244	283	-4.249635	-0.885418	-0.769603
245	284	-6.161964	-0.739585	0.339503
246	285	-5.84097	-0.739585	-0.716475
247	286	-5.84097	2.843748	-0.716475
248	287	-3.324464	-4.072918	-4.575191
249	289	-3.54097	2.843748	-4.700191
250	290	-4.181915	-0.885418	-0.583544
251	291	-4.249635	-4.218752	-0.769603
252	292	-4.181915	-4.218418	-0.583544
253	293	-4.181915	0.448082	-0.583544
254	294	-4.181915	-5.551918	-0.583544
255	295	-2.791313	-0.885418	-3.29549
256	296	-2.596321	-0.885418	-3.329873
257	297	-2.791313	-4.218752	-3.29549
258	298	-2.596321	0.448082	-3.329873
259	299	-2.596321	-5.551918	-3.329873
260	303	-0.995299	-4.072918	-8.609424
261	306	-5.589464	-0.739585	-0.652096
262	307	-5.589464	-4.072918	-0.652096
263	308	-3.324464	-0.739585	-4.575191
264	309	-3.54097	-0.739585	-4.700191
265	310	-3.54097	-4.072918	-4.700191
266	311	-3.54097	-7.656252	-4.700191
267	312	-5.84097	-4.072918	-0.716475
268	313	-5.84097	-7.656252	-0.716475

Node Boundary Conditions

Node Label	X [k/in]	Y [k/in]	Z [k/in]	X Rot [k-ft/rad]	Y Rot [k-ft/rad]	Z Rot [k-ft/rad]
1	22					
2	9					
3	54					
4	55					

Node Boundary Conditions (Continued)

Node Label	X [k/in]	Y [k/in]	Z [k/in]	X Rot [k-ft/rad]	Y Rot [k-ft/rad]	Z Rot [k-ft/rad]
5 57						
6 58						
7 59						
8 60						
9 61	Reaction	Reaction	Reaction	Reaction	Reaction	Reaction
10 62	Reaction	Reaction	Reaction	Reaction	Reaction	Reaction
11 63						
12 64						
13 71						
14 137						
15 138						
16 140						
17 141						
18 142						
19 143						
20 146						
21 147						
22 205						
23 206						
24 208						
25 209						
26 210						
27 211						
28 214						
29 215						
30 128						
31 130	Reaction	Reaction	Reaction	Reaction	Reaction	Reaction
32 153						
33 154	Reaction	Reaction	Reaction	Reaction	Reaction	Reaction
34 232						
35 234	Reaction	Reaction	Reaction	Reaction	Reaction	Reaction
36 249						
37 250	Reaction	Reaction	Reaction	Reaction	Reaction	Reaction

Hot Rolled Steel Properties

Label	E [ksi]	G [ksi]	Nu	Therm. Coeff. [1e ⁶ °F ⁻¹]	Density [k/ft ³]	Yield [ksi]	Ry	Fu [ksi]	Rt
1 A992	29000	11154	0.3	0.65	0.49	50	1.1	65	1.1
2 A36 Gr.36	29000	11154	0.3	0.65	0.49	36	1.5	58	1.2
3 A572 Gr.50	29000	11154	0.3	0.65	0.49	50	1.1	65	1.1
4 A500 Gr.B RND	29000	11154	0.3	0.65	0.527	42	1.4	58	1.3
5 A500 Gr.B Rect	29000	11154	0.3	0.65	0.527	46	1.4	58	1.3
6 A53 Gr.B	29000	11154	0.3	0.65	0.49	35	1.6	60	1.2
7 A1085	29000	11154	0.3	0.65	0.49	50	1.4	65	1.3
8 A53 Gr.B 50	29000	11154	0.3	0.65	0.49	50	1.5	58	1.2

Hot Rolled Steel Section Sets

Label	Shape	Type	Design List	Material	Design Rule	Area [in ²]	Iyy [in ⁴]	Izz [in ⁴]	J [in ⁴]
1 MF-H1	PIPE_2.875X0.276"	Beam	Pipe	A500 Gr.B RND	Typical	2.254	1.924	1.924	3.848
2 SF-H1	PIPE_2.0	Beam	Pipe	A53 Gr.B	Typical	1.02	0.627	0.627	1.25
3 MF-CP1	PL5/8X3.5	Beam	RECT	A36 Gr.36	Typical	2.188	0.071	2.233	0.253
4 MF-CP2	PL1.25"X3.5"	Beam	RECT	A36 Gr.36	Typical	4.375	0.57	4.466	1.767
5 SF-V1	5/8"SR	Column	BAR	A36 Gr.36	Typical	0.307	0.007	0.007	0.015
6 SF-D1	SR_3/4"	VBrace	BAR	A36 Gr.36	Typical	0.442	0.016	0.016	0.031

Hot Rolled Steel Section Sets (Continued)

	Label	Shape	Type	Design List	Material	Design Rule	Area [in ²]	Iyy [in ⁴]	Izz [in ⁴]	J [in ⁴]
7	MF-P1	PIPE_2.0	Column	Pipe	A53 Gr.B	Typical	1.02	0.627	0.627	1.25
8	Tieback	PIPE_2.0	Beam	Pipe	A53 Gr.B	Typical	1.02	0.627	0.627	1.25
9	C-P1	HSS4.500X0.237	Column	Pipe	A53 Gr.B 50	Typical	2.96	6.79	6.79	13.6

Member Primary Data

	Label	I Node	J Node	Rotate(deg)	Section/Shape	Type	Design List	Material	Design Rule
1	1	1	2		MF-H1	Beam	Pipe	A500 Gr.B RND	Typical
2	2	3	4		MF-H1	Beam	Pipe	A500 Gr.B RND	Typical
3	3	14	18	90	MF-CP1	Beam	RECT	A36 Gr.36	Typical
4	4	15	19	90	MF-CP1	Beam	RECT	A36 Gr.36	Typical
5	5	16	20	90	MF-CP1	Beam	RECT	A36 Gr.36	Typical
6	6	17	21	90	MF-CP1	Beam	RECT	A36 Gr.36	Typical
7	7	11	6		RIGID	None	None	RIGID	Typical
8	8	10	5		RIGID	None	None	RIGID	Typical
9	9	18	32	90	MF-CP1	Beam	RECT	A36 Gr.36	Typical
10	10	31	29	90	MF-CP1	Beam	RECT	A36 Gr.36	Typical
11	11	32	31		SF-H1	Beam	Pipe	A53 Gr.B	Typical
12	12	29	25	90	MF-CP2	Beam	RECT	A36 Gr.36	Typical
13	13	25	27	90	MF-CP2	Beam	RECT	A36 Gr.36	Typical
14	14	30	26	90	MF-CP2	Beam	RECT	A36 Gr.36	Typical
15	15	26	28	90	MF-CP2	Beam	RECT	A36 Gr.36	Typical
16	16	19	34	90	MF-CP1	Beam	RECT	A36 Gr.36	Typical
17	17	33	30	90	MF-CP1	Beam	RECT	A36 Gr.36	Typical
18	18	34	33		SF-H1	Beam	Pipe	A53 Gr.B	Typical
19	19	21	36	90	MF-CP1	Beam	RECT	A36 Gr.36	Typical
20	20	35	27	90	MF-CP1	Beam	RECT	A36 Gr.36	Typical
21	21	36	35		SF-H1	Beam	Pipe	A53 Gr.B	Typical
22	22	20	38	90	MF-CP1	Beam	RECT	A36 Gr.36	Typical
23	23	37	28	90	MF-CP1	Beam	RECT	A36 Gr.36	Typical
24	24	38	37		SF-H1	Beam	Pipe	A53 Gr.B	Typical
25	25	12	7		RIGID	None	None	RIGID	Typical
26	26	13	8		RIGID	None	None	RIGID	Typical
27	27	23	9		RIGID	None	None	RIGID	Typical
28	28	24	22		RIGID	None	None	RIGID	Typical
29	29	40	39		SF-V1	Column	BAR	A36 Gr.36	Typical
30	30	42	41		SF-V1	Column	BAR	A36 Gr.36	Typical
31	31	44	43		SF-V1	Column	BAR	A36 Gr.36	Typical
32	32	46	45		SF-V1	Column	BAR	A36 Gr.36	Typical
33	33	40	41		SF-D1	VBrace	BAR	A36 Gr.36	Typical
34	34	39	42		SF-D1	VBrace	BAR	A36 Gr.36	Typical
35	35	45	44		SF-D1	VBrace	BAR	A36 Gr.36	Typical
36	36	46	43		SF-D1	VBrace	BAR	A36 Gr.36	Typical
37	37	50	48		RIGID	None	None	RIGID	Typical
38	38	49	47		RIGID	None	None	RIGID	Typical
39	39	52	51		MF-P1	Column	Pipe	A53 Gr.B	Typical
40	40	53	146		Tieback	Beam	Pipe	A53 Gr.B	Typical
41	41	9	54		RIGID	None	None	RIGID	Typical
42	42	22	55		RIGID	None	None	RIGID	Typical
43	43	56	215		Tieback	Beam	Pipe	A53 Gr.B	Typical
44	44	57	58		C-P1	Column	Pipe	A53 Gr.B 50	Typical
45	45	60	62		RIGID	None	None	RIGID	Typical
46	46	59	61		RIGID	None	None	RIGID	Typical
47	47	68	66		RIGID	None	None	RIGID	Typical
48	48	67	65		RIGID	None	None	RIGID	Typical
49	49	70	69		MF-P1	Column	Pipe	A53 Gr.B	Typical

Member Primary Data (Continued)

Label	I Node	J Node	Rotate(deg)	Section/Shape	Type	Design List	Material	Design Rule
50	50	75	73	RIGID	None	None	RIGID	Typical
51	51	74	72	RIGID	None	None	RIGID	Typical
52	52	77	76	MF-P1	Column	Pipe	A53 Gr.B	Typical
53	53	78	79	RIGID	None	None	RIGID	Typical
54	54	80	81	RIGID	None	None	RIGID	Typical
55	55	82	83	MF-P1	Column	Pipe	A53 Gr.B	Typical
56	56	84	85	RIGID	None	None	RIGID	Typical
57	57	86	87	RIGID	None	None	RIGID	Typical
58	58	88	89	MF-P1	Column	Pipe	A53 Gr.B	Typical
59	99	140	141	C-P1	Column	Pipe	A53 Gr.B 50	Typical
60	146	208	209	C-P1	Column	Pipe	A53 Gr.B 50	Typical
61	64	131	159	90	MF-CP1	Beam	RECT	A36 Gr.36
62	65	148	166	90	MF-CP1	Beam	RECT	A36 Gr.36
63	66	119	121	MF-H1	Beam	Pipe	A500 Gr.B RND	Typical
64	67	161	155	SF-H1	Beam	Pipe	A53 Gr.B	Typical
65	68	129	117	RIGID	None	None	RIGID	Typical
66	70	136	150	90	MF-CP1	Beam	RECT	A36 Gr.36
67	71	124	126	RIGID	None	None	RIGID	Typical
68	72	166	127	SF-H1	Beam	Pipe	A53 Gr.B	Typical
69	73	193	169	RIGID	None	None	RIGID	Typical
70	74	165	160	90	MF-CP2	Beam	RECT	A36 Gr.36
71	75	142	130	RIGID	None	None	RIGID	Typical
72	76	160	164	90	MF-CP2	Beam	RECT	A36 Gr.36
73	77	162	156	90	MF-CP2	Beam	RECT	A36 Gr.36
74	78	133	120	RIGID	None	None	RIGID	Typical
75	79	132	125	RIGID	None	None	RIGID	Typical
76	80	158	128	RIGID	None	None	RIGID	Typical
77	81	123	153	RIGID	None	None	RIGID	Typical
78	82	173	151	SF-V1	Column	BAR	A36 Gr.36	Typical
79	83	174	173	SF-D1	VBrace	BAR	A36 Gr.36	Typical
80	84	177	149	RIGID	None	None	RIGID	Typical
81	85	176	175	RIGID	None	None	RIGID	Typical
82	86	143	154	RIGID	None	None	RIGID	Typical
83	87	128	137	RIGID	None	None	RIGID	Typical
84	88	153	138	RIGID	None	None	RIGID	Typical
85	89	187	188	RIGID	None	None	RIGID	Typical
86	90	181	202	RIGID	None	None	RIGID	Typical
87	91	179	186	RIGID	None	None	RIGID	Typical
88	92	191	192	RIGID	None	None	RIGID	Typical
89	93	114	118	MF-H1	Beam	Pipe	A500 Gr.B RND	Typical
90	94	134	148	90	MF-CP1	Beam	RECT	A36 Gr.36
91	95	135	131	90	MF-CP1	Beam	RECT	A36 Gr.36
92	96	144	152	90	MF-CP1	Beam	RECT	A36 Gr.36
93	97	127	165	90	MF-CP1	Beam	RECT	A36 Gr.36
94	98	122	162	90	MF-CP2	Beam	RECT	A36 Gr.36
95	100	167	122	90	MF-CP1	Beam	RECT	A36 Gr.36
96	101	159	167	SF-H1	Beam	Pipe	A53 Gr.B	Typical
97	102	152	161	90	MF-CP1	Beam	RECT	A36 Gr.36
98	103	155	164	90	MF-CP1	Beam	RECT	A36 Gr.36
99	104	150	168	90	MF-CP1	Beam	RECT	A36 Gr.36
100	105	116	156	90	MF-CP1	Beam	RECT	A36 Gr.36
101	106	168	116	SF-H1	Beam	Pipe	A53 Gr.B	Typical
102	107	170	115	SF-V1	Column	BAR	A36 Gr.36	Typical
103	108	172	163	SF-V1	Column	BAR	A36 Gr.36	Typical
104	109	139	174	SF-V1	Column	BAR	A36 Gr.36	Typical

Member Primary Data (Continued)

Label	I Node	J Node	Rotate(deg)	Section/Shape	Type	Design List	Material	Design Rule
105	110	170	163	SF-D1	VBrace	BAR	A36 Gr.36	Typical
106	111	115	172	SF-D1	VBrace	BAR	A36 Gr.36	Typical
107	112	139	151	SF-D1	VBrace	BAR	A36 Gr.36	Typical
108	113	145	178	MF-P1	Column	Pipe	A53 Gr.B	Typical
109	114	180	214	Tieback	Beam	Pipe	A53 Gr.B	Typical
110	115	171	64	Tieback	Beam	Pipe	A53 Gr.B	Typical
111	117	189	190	MF-P1	Column	Pipe	A53 Gr.B	Typical
112	118	194	195	MF-P1	Column	Pipe	A53 Gr.B	Typical
113	123	207	204	RIGID	None	None	RIGID	Typical
114	124	212	183	RIGID	None	None	RIGID	Typical
115	125	185	213	MF-P1	Column	Pipe	A53 Gr.B	Typical
116	126	216	203	RIGID	None	None	RIGID	Typical
117	127	182	217	MF-P1	Column	Pipe	A53 Gr.B	Typical
118	128	235	255	90	MF-CP1	Beam	RECT	A36 Gr.36
119	129	244	262	90	MF-CP1	Beam	RECT	A36 Gr.36
120	130	223	225	MF-H1	Beam	Pipe	A500 Gr.B RND	Typical
121	131	257	251	SF-H1	Beam	Pipe	A53 Gr.B	Typical
122	132	233	221	RIGID	None	None	RIGID	Typical
123	134	240	246	90	MF-CP1	Beam	RECT	A36 Gr.36
124	135	228	230	RIGID	None	None	RIGID	Typical
125	136	262	231	SF-H1	Beam	Pipe	A53 Gr.B	Typical
126	137	297	265	RIGID	None	None	RIGID	Typical
127	138	261	256	90	MF-CP2	Beam	RECT	A36 Gr.36
128	139	210	234	RIGID	None	None	RIGID	Typical
129	140	256	260	90	MF-CP2	Beam	RECT	A36 Gr.36
130	141	258	252	90	MF-CP2	Beam	RECT	A36 Gr.36
131	142	237	224	RIGID	None	None	RIGID	Typical
132	143	236	229	RIGID	None	None	RIGID	Typical
133	144	254	232	RIGID	None	None	RIGID	Typical
134	145	227	249	RIGID	None	None	RIGID	Typical
135	147	269	247	SF-V1	Column	BAR	A36 Gr.36	Typical
136	148	272	269	SF-D1	VBrace	BAR	A36 Gr.36	Typical
137	149	275	245	RIGID	None	None	RIGID	Typical
138	150	274	273	RIGID	None	None	RIGID	Typical
139	151	211	250	RIGID	None	None	RIGID	Typical
140	152	232	205	RIGID	None	None	RIGID	Typical
141	153	249	206	RIGID	None	None	RIGID	Typical
142	154	291	292	RIGID	None	None	RIGID	Typical
143	155	285	306	RIGID	None	None	RIGID	Typical
144	156	283	290	RIGID	None	None	RIGID	Typical
145	157	295	296	RIGID	None	None	RIGID	Typical
146	158	218	222	MF-H1	Beam	Pipe	A500 Gr.B RND	Typical
147	159	238	244	90	MF-CP1	Beam	RECT	A36 Gr.36
148	160	239	235	90	MF-CP1	Beam	RECT	A36 Gr.36
149	161	242	248	90	MF-CP1	Beam	RECT	A36 Gr.36
150	162	231	261	90	MF-CP1	Beam	RECT	A36 Gr.36
151	163	226	258	90	MF-CP2	Beam	RECT	A36 Gr.36
152	164	263	226	90	MF-CP1	Beam	RECT	A36 Gr.36
153	165	255	263	SF-H1	Beam	Pipe	A53 Gr.B	Typical
154	166	248	257	90	MF-CP1	Beam	RECT	A36 Gr.36
155	167	251	260	90	MF-CP1	Beam	RECT	A36 Gr.36
156	168	246	264	90	MF-CP1	Beam	RECT	A36 Gr.36
157	169	220	252	90	MF-CP1	Beam	RECT	A36 Gr.36
158	170	264	220	SF-H1	Beam	Pipe	A53 Gr.B	Typical
159	171	266	219	SF-V1	Column	BAR	A36 Gr.36	Typical

Member Primary Data (Continued)

Label	I Node	J Node	Rotate(deg)	Section/Shape	Type	Design List	Material	Design Rule
160	172	268	259	SF-V1	Column	BAR	A36 Gr.36	Typical
161	176	241	272	SF-V1	Column	BAR	A36 Gr.36	Typical
162	177	266	259	SF-D1	VBrace	BAR	A36 Gr.36	Typical
163	178	219	268	SF-D1	VBrace	BAR	A36 Gr.36	Typical
164	179	241	247	SF-D1	VBrace	BAR	A36 Gr.36	Typical
165	180	243	282	MF-P1	Column	Pipe	A53 Gr.B	Typical
166	181	284	63	Tieback	Beam	Pipe	A53 Gr.B	Typical
167	182	267	147	Tieback	Beam	Pipe	A53 Gr.B	Typical
168	184	293	294	MF-P1	Column	Pipe	A53 Gr.B	Typical
169	185	298	299	MF-P1	Column	Pipe	A53 Gr.B	Typical
170	190	309	308	RIGID	None	None	RIGID	Typical
171	191	310	287	RIGID	None	None	RIGID	Typical
172	192	289	311	MF-P1	Column	Pipe	A53 Gr.B	Typical
173	193	312	307	RIGID	None	None	RIGID	Typical
174	194	286	313	MF-P1	Column	Pipe	A53 Gr.B	Typical

Member Advanced Data

Label	I Release	J Release	T/C Only	Physical	Deflection Ratio Options	Seismic DR
1	1			Yes	N/A	None
2	2			Yes	N/A	None
3	3			Yes	N/A	None
4	4			Yes	N/A	None
5	5			Yes	N/A	None
6	6			Yes	N/A	None
7	7	OOOOXO		Yes	** NA **	None
8	8	OOOOXO		Yes	** NA **	None
9	9			Yes	N/A	None
10	10			Yes	N/A	None
11	11			Yes	N/A	None
12	12			Yes	N/A	None
13	13			Yes	N/A	None
14	14			Yes	N/A	None
15	15			Yes	N/A	None
16	16			Yes	N/A	None
17	17			Yes	N/A	None
18	18			Yes	Default	None
19	19			Yes	N/A	None
20	20			Yes	N/A	None
21	21			Yes	N/A	None
22	22			Yes	N/A	None
23	23			Yes	N/A	None
24	24			Yes	N/A	None
25	25	OOOOXO		Yes	** NA **	None
26	26	OOOOXO		Yes	** NA **	None
27	27			Yes	** NA **	None
28	28			Yes	** NA **	None
29	29			Yes	** NA **	None
30	30			Yes	** NA **	None
31	31			Yes	** NA **	None
32	32			Yes	** NA **	None
33	33			Yes	** NA **	None
34	34		Euler Buckling	Yes	** NA **	None
35	35			Yes	** NA **	None
36	36		Euler Buckling	Yes	** NA **	None
37	37			Yes	** NA **	None

Member Advanced Data (Continued)

Label	I Release	J Release	T/C Only	Physical	Deflection Ratio Options	Seismic DR
38	38			Yes	** NA **	None
39	39			Yes	** NA **	None
40	40	BenPIN	BenPIN	Yes	Default	None
41	41			Yes	** NA **	None
42	42			Yes	** NA **	None
43	43	BenPIN	BenPIN	Yes	Default	None
44	44			Yes	** NA **	None
45	45			Yes	** NA **	None
46	46			Yes	** NA **	None
47	47			Yes	** NA **	None
48	48			Yes	** NA **	None
49	49			Yes	** NA **	None
50	50			Yes	** NA **	None
51	51			Yes	** NA **	None
52	52			Yes	** NA **	None
53	53			Yes	** NA **	None
54	54			Yes	** NA **	None
55	55			Yes	** NA **	None
56	56			Yes	** NA **	None
57	57			Yes	** NA **	None
58	58			Yes	** NA **	None
59	99			Yes	** NA **	None
60	146			Yes	** NA **	None
61	64			Yes	N/A	None
62	65			Yes	N/A	None
63	66			Yes	N/A	None
64	67			Yes	N/A	None
65	68	OOOOXO		Yes	** NA **	None
66	70			Yes	N/A	None
67	71	OOOOXO		Yes	** NA **	None
68	72			Yes	N/A	None
69	73			Yes	** NA **	None
70	74			Yes	N/A	None
71	75			Yes	** NA **	None
72	76			Yes	N/A	None
73	77			Yes	N/A	None
74	78	OOOOXO		Yes	** NA **	None
75	79	OOOOXO		Yes	** NA **	None
76	80			Yes	** NA **	None
77	81			Yes	** NA **	None
78	82			Yes	** NA **	None
79	83			Yes	** NA **	None
80	84			Yes	** NA **	None
81	85			Yes	** NA **	None
82	86			Yes	** NA **	None
83	87			Yes	** NA **	None
84	88			Yes	** NA **	None
85	89			Yes	** NA **	None
86	90			Yes	** NA **	None
87	91			Yes	** NA **	None
88	92			Yes	** NA **	None
89	93			Yes	N/A	None
90	94			Yes	N/A	None
91	95			Yes	N/A	None
92	96			Yes	N/A	None

Member Advanced Data (Continued)

Label	I Release	J Release	T/C Only	Physical	Deflection Ratio Options	Seismic DR
93	97			Yes	N/A	None
94	98			Yes	N/A	None
95	100			Yes	N/A	None
96	101			Yes	Default	None
97	102			Yes	N/A	None
98	103			Yes	N/A	None
99	104			Yes	N/A	None
100	105			Yes	N/A	None
101	106			Yes	N/A	None
102	107			Yes	** NA **	None
103	108			Yes	** NA **	None
104	109			Yes	** NA **	None
105	110			Yes	** NA **	None
106	111		Euler Buckling	Yes	** NA **	None
107	112		Euler Buckling	Yes	** NA **	None
108	113			Yes	** NA **	None
109	114	BenPIN	BenPIN	Yes	Default	None
110	115	BenPIN	BenPIN	Yes	Default	None
111	117			Yes	** NA **	None
112	118			Yes	** NA **	None
113	123			Yes	** NA **	None
114	124			Yes	** NA **	None
115	125			Yes	** NA **	None
116	126			Yes	** NA **	None
117	127			Yes	** NA **	None
118	128			Yes	N/A	None
119	129			Yes	N/A	None
120	130			Yes	N/A	None
121	131			Yes	N/A	None
122	132		OOOOXO	Yes	** NA **	None
123	134			Yes	N/A	None
124	135		OOOOXO	Yes	** NA **	None
125	136			Yes	N/A	None
126	137			Yes	** NA **	None
127	138			Yes	N/A	None
128	139			Yes	** NA **	None
129	140			Yes	N/A	None
130	141			Yes	N/A	None
131	142		OOOOXO	Yes	** NA **	None
132	143		OOOOXO	Yes	** NA **	None
133	144			Yes	** NA **	None
134	145			Yes	** NA **	None
135	147			Yes	** NA **	None
136	148			Yes	** NA **	None
137	149			Yes	** NA **	None
138	150			Yes	** NA **	None
139	151			Yes	** NA **	None
140	152			Yes	** NA **	None
141	153			Yes	** NA **	None
142	154			Yes	** NA **	None
143	155			Yes	** NA **	None
144	156			Yes	** NA **	None
145	157			Yes	** NA **	None
146	158			Yes	N/A	None
147	159			Yes	N/A	None

Member Advanced Data (Continued)

Label	I Release	J Release	T/C Only	Physical	Deflection Ratio Options	Seismic DR
148	160			Yes	N/A	None
149	161			Yes	N/A	None
150	162			Yes	N/A	None
151	163			Yes	N/A	None
152	164			Yes	N/A	None
153	165			Yes	Default	None
154	166			Yes	N/A	None
155	167			Yes	N/A	None
156	168			Yes	N/A	None
157	169			Yes	N/A	None
158	170			Yes	N/A	None
159	171			Yes	** NA **	None
160	172			Yes	** NA **	None
161	176			Yes	** NA **	None
162	177			Yes	** NA **	None
163	178		Euler Buckling	Yes	** NA **	None
164	179		Euler Buckling	Yes	** NA **	None
165	180			Yes	** NA **	None
166	181	BenPIN	BenPIN	Yes	Default	None
167	182	BenPIN	BenPIN	Yes	Default	None
168	184			Yes	** NA **	None
169	185			Yes	** NA **	None
170	190			Yes	** NA **	None
171	191			Yes	** NA **	None
172	192			Yes	** NA **	None
173	193			Yes	** NA **	None
174	194			Yes	** NA **	None

Hot Rolled Steel Design Parameters

Label	Shape	Length [ft]	Lb y-y [ft]	Lb z-z [ft]	Lcomp top [ft]	Channel Conn.	a [ft]	Function
1	1	MF-H1	14.5		Lbyy	N/A	N/A	Lateral
2	2	MF-H1	14.5		Lbyy	N/A	N/A	Lateral
3	3	MF-CP1	0.458		Lbyy	N/A	N/A	Lateral
4	4	MF-CP1	0.458		Lbyy	N/A	N/A	Lateral
5	5	MF-CP1	0.458		Lbyy	N/A	N/A	Lateral
6	6	MF-CP1	0.458		Lbyy	N/A	N/A	Lateral
7	9	MF-CP1	0.08		Lbyy	N/A	N/A	Lateral
8	10	MF-CP1	0.08		Lbyy	N/A	N/A	Lateral
9	11	SF-H1	2.5		Lbyy	N/A	N/A	Lateral
10	12	MF-CP2	0.458		Lbyy	N/A	N/A	Lateral
11	13	MF-CP2	0.458		Lbyy	N/A	N/A	Lateral
12	14	MF-CP2	0.458		Lbyy	N/A	N/A	Lateral
13	15	MF-CP2	0.458		Lbyy	N/A	N/A	Lateral
14	16	MF-CP1	0.08		Lbyy	N/A	N/A	Lateral
15	17	MF-CP1	0.08		Lbyy	N/A	N/A	Lateral
16	18	SF-H1	2.5		Lbyy	N/A	N/A	Lateral
17	19	MF-CP1	0.08		Lbyy	N/A	N/A	Lateral
18	20	MF-CP1	0.08		Lbyy	N/A	N/A	Lateral
19	21	SF-H1	2.5		Lbyy	N/A	N/A	Lateral
20	22	MF-CP1	0.08		Lbyy	N/A	N/A	Lateral
21	23	MF-CP1	0.08		Lbyy	N/A	N/A	Lateral
22	24	SF-H1	2.5		Lbyy	N/A	N/A	Lateral
23	29	SF-V1	3.333	2.5	2.5	Lbyy	N/A	Lateral
24	30	SF-V1	3.333	2.5	2.5	Lbyy	N/A	Lateral
25	31	SF-V1	3.333	2.5	2.5	Lbyy	N/A	Lateral

Hot Rolled Steel Design Parameters (Continued)

Label	Shape	Length [ft]	Lb y-y [ft]	Lb z-z [ft]	Lcomp top [ft]	Channel Conn.	a [ft]	Function
26	32	SF-V1	3.333	2.5	2.5	Lbyy	N/A	Lateral
27	33	SF-D1	3.976			Lbyy	N/A	Lateral
28	34	SF-D1	3.976			Lbyy	N/A	Lateral
29	35	SF-D1	3.976			Lbyy	N/A	Lateral
30	36	SF-D1	3.976			Lbyy	N/A	Lateral
31	39	MF-P1	10.5			Lbyy	N/A	Lateral
32	40	Tieback	6.251			Lbyy	N/A	Lateral
33	43	Tieback	6.27			Lbyy	N/A	Lateral
34	44	C-P1	7			Lbyy	N/A	Lateral
35	49	MF-P1	10.5			Lbyy	N/A	Lateral
36	52	MF-P1	10.5			Lbyy	N/A	Lateral
37	55	MF-P1	6			Lbyy	N/A	Lateral
38	58	MF-P1	6			Lbyy	N/A	Lateral
39	99	C-P1	7			Lbyy	N/A	Lateral
40	146	C-P1	7			Lbyy	N/A	Lateral
41	64	MF-CP1	0.08			Lbyy	N/A	Lateral
42	65	MF-CP1	0.08			Lbyy	N/A	Lateral
43	66	MF-H1	14.5			Lbyy	N/A	Lateral
44	67	SF-H1	2.5			Lbyy	N/A	Lateral
45	70	MF-CP1	0.458			Lbyy	N/A	Lateral
46	72	SF-H1	2.5			Lbyy	N/A	Lateral
47	74	MF-CP2	0.458			Lbyy	N/A	Lateral
48	76	MF-CP2	0.458			Lbyy	N/A	Lateral
49	77	MF-CP2	0.458			Lbyy	N/A	Lateral
50	82	SF-V1	3.333	2.5	2.5	Lbyy	N/A	Lateral
51	83	SF-D1	3.976			Lbyy	N/A	Lateral
52	93	MF-H1	14.5			Lbyy	N/A	Lateral
53	94	MF-CP1	0.458			Lbyy	N/A	Lateral
54	95	MF-CP1	0.458			Lbyy	N/A	Lateral
55	96	MF-CP1	0.458			Lbyy	N/A	Lateral
56	97	MF-CP1	0.08			Lbyy	N/A	Lateral
57	98	MF-CP2	0.458			Lbyy	N/A	Lateral
58	100	MF-CP1	0.08			Lbyy	N/A	Lateral
59	101	SF-H1	2.5			Lbyy	N/A	Lateral
60	102	MF-CP1	0.08			Lbyy	N/A	Lateral
61	103	MF-CP1	0.08			Lbyy	N/A	Lateral
62	104	MF-CP1	0.08			Lbyy	N/A	Lateral
63	105	MF-CP1	0.08			Lbyy	N/A	Lateral
64	106	SF-H1	2.5			Lbyy	N/A	Lateral
65	107	SF-V1	3.333	2.5	2.5	Lbyy	N/A	Lateral
66	108	SF-V1	3.333	2.5	2.5	Lbyy	N/A	Lateral
67	109	SF-V1	3.333	2.5	2.5	Lbyy	N/A	Lateral
68	110	SF-D1	3.976			Lbyy	N/A	Lateral
69	111	SF-D1	3.976			Lbyy	N/A	Lateral
70	112	SF-D1	3.976			Lbyy	N/A	Lateral
71	113	MF-P1	10.5			Lbyy	N/A	Lateral
72	114	Tieback	6.251			Lbyy	N/A	Lateral
73	115	Tieback	6.27			Lbyy	N/A	Lateral
74	117	MF-P1	6			Lbyy	N/A	Lateral
75	118	MF-P1	6			Lbyy	N/A	Lateral
76	125	MF-P1	10.5			Lbyy	N/A	Lateral
77	127	MF-P1	10.5			Lbyy	N/A	Lateral
78	128	MF-CP1	0.08			Lbyy	N/A	Lateral
79	129	MF-CP1	0.08			Lbyy	N/A	Lateral
80	130	MF-H1	14.5			Lbyy	N/A	Lateral

Hot Rolled Steel Design Parameters (Continued)

Label	Shape	Length [ft]	Lb y-y [ft]	Lb z-z [ft]	Lcomp top [ft]	Channel Conn.	a [ft]	Function
81	131	SF-H1	2.5		Lbyy	N/A	N/A	Lateral
82	134	MF-CP1	0.458		Lbyy	N/A	N/A	Lateral
83	136	SF-H1	2.5		Lbyy	N/A	N/A	Lateral
84	138	MF-CP2	0.458		Lbyy	N/A	N/A	Lateral
85	140	MF-CP2	0.458		Lbyy	N/A	N/A	Lateral
86	141	MF-CP2	0.458		Lbyy	N/A	N/A	Lateral
87	147	SF-V1	3.333	2.5	2.5	Lbyy	N/A	Lateral
88	148	SF-D1	3.976			Lbyy	N/A	Lateral
89	158	MF-H1	14.5			Lbyy	N/A	Lateral
90	159	MF-CP1	0.458			Lbyy	N/A	Lateral
91	160	MF-CP1	0.458			Lbyy	N/A	Lateral
92	161	MF-CP1	0.458			Lbyy	N/A	Lateral
93	162	MF-CP1	0.08			Lbyy	N/A	Lateral
94	163	MF-CP2	0.458			Lbyy	N/A	Lateral
95	164	MF-CP1	0.08			Lbyy	N/A	Lateral
96	165	SF-H1	2.5			Lbyy	N/A	Lateral
97	166	MF-CP1	0.08			Lbyy	N/A	Lateral
98	167	MF-CP1	0.08			Lbyy	N/A	Lateral
99	168	MF-CP1	0.08			Lbyy	N/A	Lateral
100	169	MF-CP1	0.08			Lbyy	N/A	Lateral
101	170	SF-H1	2.5			Lbyy	N/A	Lateral
102	171	SF-V1	3.333	2.5	2.5	Lbyy	N/A	Lateral
103	172	SF-V1	3.333	2.5	2.5	Lbyy	N/A	Lateral
104	176	SF-V1	3.333	2.5	2.5	Lbyy	N/A	Lateral
105	177	SF-D1	3.976			Lbyy	N/A	Lateral
106	178	SF-D1	3.976			Lbyy	N/A	Lateral
107	179	SF-D1	3.976			Lbyy	N/A	Lateral
108	180	MF-P1	10.5			Lbyy	N/A	Lateral
109	181	Tieback	6.251			Lbyy	N/A	Lateral
110	182	Tieback	6.27			Lbyy	N/A	Lateral
111	184	MF-P1	6			Lbyy	N/A	Lateral
112	185	MF-P1	6			Lbyy	N/A	Lateral
113	192	MF-P1	10.5			Lbyy	N/A	Lateral
114	194	MF-P1	10.5			Lbyy	N/A	Lateral

Member Point Loads (BLC 1 : Dead)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
1	39	Y	-0.065 %5
2	39	Y	-0.065 %65
3	39	Y	0 0
4	39	Y	0 0
5	39	Y	0 0
6	49	Y	-0.033 %5
7	49	Y	-0.033 %25
8	49	Y	-0.041 %75
9	49	Y	-0.041 %95
10	49	Y	0 0
11	52	Y	-0.045 %5
12	52	Y	-0.045 %65
13	52	Y	0 0
14	52	Y	0 0
15	52	Y	0 0
16	180	Y	-0.065 %5
17	180	Y	-0.065 %65
18	180	Y	0 0

Member Point Loads (BLC 1 : Dead) (Continued)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
19	180	Y	0
20	180	Y	0
21	194	Y	-0.033
22	194	Y	-0.033
23	194	Y	-0.041
24	194	Y	-0.041
25	194	Y	0
26	192	Y	-0.045
27	192	Y	-0.045
28	192	Y	0
29	192	Y	0
30	192	Y	0
31	113	Y	-0.065
32	113	Y	-0.065
33	113	Y	0
34	113	Y	0
35	113	Y	0
36	127	Y	-0.033
37	127	Y	-0.033
38	127	Y	-0.041
39	127	Y	-0.041
40	127	Y	0
41	125	Y	-0.045
42	125	Y	-0.045
43	125	Y	0
44	125	Y	0
45	125	Y	0
46	55	Y	-0.055
47	55	Y	-0.059
48	55	Y	-0.046
49	55	Y	0
50	55	Y	0
51	58	Y	-0.077
52	58	Y	-0.071
53	58	Y	-0.019
54	58	Y	0
55	58	Y	0
56	184	Y	-0.055
57	184	Y	-0.059
58	184	Y	-0.046
59	184	Y	0
60	184	Y	0
61	185	Y	-0.077
62	185	Y	-0.071
63	185	Y	-0.019
64	185	Y	0
65	185	Y	0
66	117	Y	-0.055
67	117	Y	-0.059
68	117	Y	-0.046
69	117	Y	0
70	117	Y	0
71	118	Y	-0.077
72	118	Y	-0.071
73	118	Y	-0.026

Member Point Loads (BLC 1 : Dead) (Continued)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
74 118	Y	0	0
75 118	Y	0	0

Member Point Loads (BLC 2 : 0 Wind - No Ice)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
1 39	Z	-0.333	%5
2 39	Z	-0.333	%65
3 39	Z	0	0
4 39	Z	0	0
5 39	Z	0	0
6 49	Z	-0.114	%5
7 49	Z	-0.114	%25
8 49	Z	-0.089	%75
9 49	Z	-0.089	%95
10 49	Z	0	0
11 52	Z	-0.292	%5
12 52	Z	-0.292	%65
13 52	Z	0	0
14 52	Z	0	0
15 52	Z	0	0
16 180	Z	-0.333	%5
17 180	Z	-0.333	%65
18 180	Z	0	0
19 180	Z	0	0
20 180	Z	0	0
21 194	Z	-0.114	%5
22 194	Z	-0.114	%25
23 194	Z	-0.089	%75
24 194	Z	-0.089	%95
25 194	Z	0	0
26 192	Z	-0.292	%5
27 192	Z	-0.292	%65
28 192	Z	0	0
29 192	Z	0	0
30 192	Z	0	0
31 113	Z	-0.333	%5
32 113	Z	-0.333	%65
33 113	Z	0	0
34 113	Z	0	0
35 113	Z	0	0
36 127	Z	-0.114	%5
37 127	Z	-0.114	%25
38 127	Z	-0.089	%75
39 127	Z	-0.089	%95
40 127	Z	0	0
41 125	Z	-0.292	%5
42 125	Z	-0.292	%65
43 125	Z	0	0
44 125	Z	0	0
45 125	Z	0	0
46 55	Z	-0.079	%10
47 55	Z	-0.055	%10
48 55	Z	-0.036	%75
49 55	Z	0	0
50 55	Z	0	0

Member Point Loads (BLC 2 : 0 Wind - No Ice) (Continued)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
51	58	Z	-0.107 %55
52	58	Z	-0.062 %55
53	58	Z	-0.037 %10
54	58	Z	0 0
55	58	Z	0 0
56	184	Z	-0.079 %10
57	184	Z	-0.055 %10
58	184	Z	-0.036 %75
59	184	Z	0 0
60	184	Z	0 0
61	185	Z	-0.107 %55
62	185	Z	-0.062 %55
63	185	Z	-0.037 %10
64	185	Z	0 0
65	185	Z	0 0
66	117	Z	-0.079 %10
67	117	Z	-0.055 %10
68	117	Z	-0.036 %75
69	117	Z	0 0
70	117	Z	0 0
71	118	Z	-0.107 %55
72	118	Z	-0.062 %55
73	118	Z	-0.121 %10
74	118	Z	0 0
75	118	Z	0 0

Member Point Loads (BLC 3 : 90 Wind - No Ice)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
1	39	X	-0.145 %5
2	39	X	-0.145 %65
3	39	X	0 0
4	39	X	0 0
5	39	X	0 0
6	49	X	-0.046 %5
7	49	X	-0.046 %25
8	49	X	-0.042 %75
9	49	X	-0.042 %95
10	49	X	0 0
11	52	X	-0.11 %5
12	52	X	-0.11 %65
13	52	X	0 0
14	52	X	0 0
15	52	X	0 0
16	180	X	-0.145 %5
17	180	X	-0.145 %65
18	180	X	0 0
19	180	X	0 0
20	180	X	0 0
21	194	X	-0.046 %5
22	194	X	-0.046 %25
23	194	X	-0.042 %75
24	194	X	-0.042 %95
25	194	X	0 0
26	192	X	-0.11 %5
27	192	X	-0.11 %65

Member Point Loads (BLC 3 : 90 Wind - No Ice) (Continued)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
28	192	X	0
29	192	X	0
30	192	X	0
31	113	X	-0.145
32	113	X	-0.145
33	113	X	0
34	113	X	0
35	113	X	0
36	127	X	-0.046
37	127	X	-0.046
38	127	X	-0.042
39	127	X	-0.042
40	127	X	0
41	125	X	-0.11
42	125	X	-0.11
43	125	X	0
44	125	X	0
45	125	X	0
46	55	X	-0.132
47	55	X	-0.089
48	55	X	-0.082
49	55	X	0
50	55	X	0
51	58	X	-0.15
52	58	X	-0.087
53	58	X	-0.037
54	58	X	0
55	58	X	0
56	184	X	-0.132
57	184	X	-0.089
58	184	X	-0.082
59	184	X	0
60	184	X	0
61	185	X	-0.15
62	185	X	-0.087
63	185	X	-0.037
64	185	X	0
65	185	X	0
66	117	X	-0.132
67	117	X	-0.089
68	117	X	-0.082
69	117	X	0
70	117	X	0
71	118	X	-0.15
72	118	X	-0.087
73	118	X	-0.215
74	118	X	0
75	118	X	0

Member Point Loads (BLC 4 : 0 Wind - Ice)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
1	39	Z	-0.066
2	39	Z	-0.066
3	39	Z	0
4	39	Z	0

Member Point Loads (BLC 4 : 0 Wind - Ice) (Continued)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
5	39	Z	0
6	49	Z	-0.024
7	49	Z	-0.024
8	49	Z	-0.019
9	49	Z	-0.019
10	49	Z	0
11	52	Z	-0.058
12	52	Z	-0.058
13	52	Z	0
14	52	Z	0
15	52	Z	0
16	180	Z	-0.066
17	180	Z	-0.066
18	180	Z	0
19	180	Z	0
20	180	Z	0
21	194	Z	-0.024
22	194	Z	-0.024
23	194	Z	-0.019
24	194	Z	-0.019
25	194	Z	0
26	192	Z	-0.058
27	192	Z	-0.058
28	192	Z	0
29	192	Z	0
30	192	Z	0
31	113	Z	-0.066
32	113	Z	-0.066
33	113	Z	0
34	113	Z	0
35	113	Z	0
36	127	Z	-0.024
37	127	Z	-0.024
38	127	Z	-0.019
39	127	Z	-0.019
40	127	Z	0
41	125	Z	-0.058
42	125	Z	-0.058
43	125	Z	0
44	125	Z	0
45	125	Z	0
46	55	Z	-0.014
47	55	Z	-0.01
48	55	Z	-0.006
49	55	Z	0
50	55	Z	0
51	58	Z	-0.019
52	58	Z	-0.011
53	58	Z	-0.007
54	58	Z	0
55	58	Z	0
56	184	Z	-0.014
57	184	Z	-0.01
58	184	Z	-0.006
59	184	Z	0

Member Point Loads (BLC 4 : 0 Wind - Ice) (Continued)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
60	184	Z	0
61	185	Z	-0.019
62	185	Z	-0.011
63	185	Z	-0.007
64	185	Z	0
65	185	Z	0
66	117	Z	-0.014
67	117	Z	-0.01
68	117	Z	-0.006
69	117	Z	0
70	117	Z	0
71	118	Z	-0.019
72	118	Z	-0.011
73	118	Z	-0.021
74	118	Z	0
75	118	Z	0

Member Point Loads (BLC 5 : 90 Wind - Ice)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
1	39	X	-0.032
2	39	X	-0.032
3	39	X	0
4	39	X	0
5	39	X	0
6	49	X	-0.011
7	49	X	-0.011
8	49	X	-0.01
9	49	X	-0.01
10	49	X	0
11	52	X	-0.025
12	52	X	-0.025
13	52	X	0
14	52	X	0
15	52	X	0
16	180	X	-0.032
17	180	X	-0.032
18	180	X	0
19	180	X	0
20	180	X	0
21	194	X	-0.011
22	194	X	-0.011
23	194	X	-0.01
24	194	X	-0.01
25	194	X	0
26	192	X	-0.025
27	192	X	-0.025
28	192	X	0
29	192	X	0
30	192	X	0
31	113	X	-0.032
32	113	X	-0.032
33	113	X	0
34	113	X	0
35	113	X	0
36	127	X	-0.011

Member Point Loads (BLC 5 : 90 Wind - Ice) (Continued)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
37	127	X	-0.011
38	127	X	-0.01
39	127	X	-0.01
40	127	X	0
41	125	X	-0.025
42	125	X	-0.025
43	125	X	0
44	125	X	0
45	125	X	0
46	55	X	-0.023
47	55	X	-0.016
48	55	X	-0.015
49	55	X	0
50	55	X	0
51	58	X	-0.026
52	58	X	-0.015
53	58	X	-0.007
54	58	X	0
55	58	X	0
56	184	X	-0.023
57	184	X	-0.016
58	184	X	-0.015
59	184	X	0
60	184	X	0
61	185	X	-0.026
62	185	X	-0.015
63	185	X	-0.007
64	185	X	0
65	185	X	0
66	117	X	-0.023
67	117	X	-0.016
68	117	X	-0.015
69	117	X	0
70	117	X	0
71	118	X	-0.026
72	118	X	-0.015
73	118	X	-0.038
74	118	X	0
75	118	X	0

Member Point Loads (BLC 6 : 0 Wind - Service)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
1	39	Z	-0.021
2	39	Z	-0.021
3	39	Z	0
4	39	Z	0
5	39	Z	0
6	49	Z	-0.007
7	49	Z	-0.007
8	49	Z	-0.006
9	49	Z	-0.006
10	49	Z	0
11	52	Z	-0.019
12	52	Z	-0.019
13	52	Z	0

Member Point Loads (BLC 6 : 0 Wind - Service) (Continued)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
14	52	Z	0
15	52	Z	0
16	180	Z	-0.021
17	180	Z	-0.021
18	180	Z	0
19	180	Z	0
20	180	Z	0
21	194	Z	-0.007
22	194	Z	-0.007
23	194	Z	-0.006
24	194	Z	-0.006
25	194	Z	0
26	192	Z	-0.019
27	192	Z	-0.019
28	192	Z	0
29	192	Z	0
30	192	Z	0
31	113	Z	-0.021
32	113	Z	-0.021
33	113	Z	0
34	113	Z	0
35	113	Z	0
36	127	Z	-0.007
37	127	Z	-0.007
38	127	Z	-0.006
39	127	Z	-0.006
40	127	Z	0
41	125	Z	-0.019
42	125	Z	-0.019
43	125	Z	0
44	125	Z	0
45	125	Z	0
46	55	Z	-0.005
47	55	Z	-0.004
48	55	Z	-0.002
49	55	Z	0
50	55	Z	0
51	58	Z	-0.007
52	58	Z	-0.004
53	58	Z	-0.002
54	58	Z	0
55	58	Z	0
56	184	Z	-0.005
57	184	Z	-0.004
58	184	Z	-0.002
59	184	Z	0
60	184	Z	0
61	185	Z	-0.007
62	185	Z	-0.004
63	185	Z	-0.002
64	185	Z	0
65	185	Z	0
66	117	Z	-0.005
67	117	Z	-0.004
68	117	Z	-0.002

Member Point Loads (BLC 6 : 0 Wind - Service) (Continued)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
69 117	Z	0	0
70 117	Z	0	0
71 118	Z	-0.007	%55
72 118	Z	-0.004	%55
73 118	Z	-0.008	%10
74 118	Z	0	0
75 118	Z	0	0

Member Point Loads (BLC 7 : 90 Wind - Service)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
1 39	X	-0.009	%5
2 39	X	-0.009	%65
3 39	X	0	0
4 39	X	0	0
5 39	X	0	0
6 49	X	-0.003	%5
7 49	X	-0.003	%25
8 49	X	-0.003	%75
9 49	X	-0.003	%95
10 49	X	0	0
11 52	X	-0.007	%5
12 52	X	-0.007	%65
13 52	X	0	0
14 52	X	0	0
15 52	X	0	0
16 180	X	-0.009	%5
17 180	X	-0.009	%65
18 180	X	0	0
19 180	X	0	0
20 180	X	0	0
21 194	X	-0.003	%5
22 194	X	-0.003	%25
23 194	X	-0.003	%75
24 194	X	-0.003	%95
25 194	X	0	0
26 192	X	-0.007	%5
27 192	X	-0.007	%65
28 192	X	0	0
29 192	X	0	0
30 192	X	0	0
31 113	X	-0.009	%5
32 113	X	-0.009	%65
33 113	X	0	0
34 113	X	0	0
35 113	X	0	0
36 127	X	-0.003	%5
37 127	X	-0.003	%25
38 127	X	-0.003	%75
39 127	X	-0.003	%95
40 127	X	0	0
41 125	X	-0.007	%5
42 125	X	-0.007	%65
43 125	X	0	0
44 125	X	0	0
45 125	X	0	0

Member Point Loads (BLC 7 : 90 Wind - Service) (Continued)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
46	55	X	-0.008 %10
47	55	X	-0.006 %10
48	55	X	-0.005 %75
49	55	X	0 0
50	55	X	0 0
51	58	X	-0.01 %55
52	58	X	-0.006 %55
53	58	X	-0.002 %10
54	58	X	0 0
55	58	X	0 0
56	184	X	-0.008 %10
57	184	X	-0.006 %10
58	184	X	-0.005 %75
59	184	X	0 0
60	184	X	0 0
61	185	X	-0.01 %55
62	185	X	-0.006 %55
63	185	X	-0.002 %10
64	185	X	0 0
65	185	X	0 0
66	117	X	-0.008 %10
67	117	X	-0.006 %10
68	117	X	-0.005 %75
69	117	X	0 0
70	117	X	0 0
71	118	X	-0.01 %55
72	118	X	-0.006 %55
73	118	X	-0.014 %10
74	118	X	0 0
75	118	X	0 0

Member Point Loads (BLC 8 : Ice)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
1	39	Y	-0.152 %5
2	39	Y	-0.152 %65
3	39	Y	0 0
4	39	Y	0 0
5	39	Y	0 0
6	49	Y	-0.06 %5
7	49	Y	-0.06 %25
8	49	Y	-0.072 %75
9	49	Y	-0.072 %95
10	49	Y	0 0
11	52	Y	-0.122 %5
12	52	Y	-0.122 %65
13	52	Y	0 0
14	52	Y	0 0
15	52	Y	0 0
16	180	Y	-0.152 %5
17	180	Y	-0.152 %65
18	180	Y	0 0
19	180	Y	0 0
20	180	Y	0 0
21	194	Y	-0.06 %5
22	194	Y	-0.06 %25

Member Point Loads (BLC 8 : Ice) (Continued)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
23	194	Y	-0.072 %75
24	194	Y	-0.072 %95
25	194	Y	0 0
26	192	Y	-0.122 %5
27	192	Y	-0.122 %65
28	192	Y	0 0
29	192	Y	0 0
30	192	Y	0 0
31	113	Y	-0.152 %5
32	113	Y	-0.152 %65
33	113	Y	0 0
34	113	Y	0 0
35	113	Y	0 0
36	127	Y	-0.06 %5
37	127	Y	-0.06 %25
38	127	Y	-0.072 %75
39	127	Y	-0.072 %95
40	127	Y	0 0
41	125	Y	-0.122 %5
42	125	Y	-0.122 %65
43	125	Y	0 0
44	125	Y	0 0
45	125	Y	0 0
46	55	Y	-0.052 %10
47	55	Y	-0.037 %10
48	55	Y	-0.031 %75
49	55	Y	0 0
50	55	Y	0 0
51	58	Y	-0.063 %55
52	58	Y	-0.038 %55
53	58	Y	-0.033 %10
54	58	Y	0 0
55	58	Y	0 0
56	184	Y	-0.052 %10
57	184	Y	-0.037 %10
58	184	Y	-0.031 %75
59	184	Y	0 0
60	184	Y	0 0
61	185	Y	-0.063 %55
62	185	Y	-0.038 %55
63	185	Y	-0.033 %10
64	185	Y	0 0
65	185	Y	0 0
66	117	Y	-0.052 %10
67	117	Y	-0.037 %10
68	117	Y	-0.031 %75
69	117	Y	0 0
70	117	Y	0 0
71	118	Y	-0.063 %55
72	118	Y	-0.038 %55
73	118	Y	-0.084 %10
74	118	Y	0 0
75	118	Y	0 0

Member Point Loads (BLC 9 : 0 Seismic)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
1 39	Z	-0.039	%5
2 39	Z	-0.039	%65
3 39	Z	0	0
4 39	Z	0	0
5 39	Z	0	0
6 49	Z	-0.02	%5
7 49	Z	-0.02	%25
8 49	Z	-0.025	%75
9 49	Z	-0.025	%95
10 49	Z	0	0
11 52	Z	-0.027	%5
12 52	Z	-0.027	%65
13 52	Z	0	0
14 52	Z	0	0
15 52	Z	0	0
16 180	Z	-0.039	%5
17 180	Z	-0.039	%65
18 180	Z	0	0
19 180	Z	0	0
20 180	Z	0	0
21 194	Z	-0.02	%5
22 194	Z	-0.02	%25
23 194	Z	-0.025	%75
24 194	Z	-0.025	%95
25 194	Z	0	0
26 192	Z	-0.027	%5
27 192	Z	-0.027	%65
28 192	Z	0	0
29 192	Z	0	0
30 192	Z	0	0
31 113	Z	-0.039	%5
32 113	Z	-0.039	%65
33 113	Z	0	0
34 113	Z	0	0
35 113	Z	0	0
36 127	Z	-0.02	%5
37 127	Z	-0.02	%25
38 127	Z	-0.025	%75
39 127	Z	-0.025	%95
40 127	Z	0	0
41 125	Z	-0.027	%5
42 125	Z	-0.027	%65
43 125	Z	0	0
44 125	Z	0	0
45 125	Z	0	0
46 55	Z	-0.017	%10
47 55	Z	-0.018	%10
48 55	Z	-0.014	%75
49 55	Z	0	0
50 55	Z	0	0
51 58	Z	-0.023	%55
52 58	Z	-0.022	%55
53 58	Z	-0.006	%10
54 58	Z	0	0
55 58	Z	0	0

Member Point Loads (BLC 9 : 0 Seismic) (Continued)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
56	184	Z	-0.017
57	184	Z	-0.018
58	184	Z	-0.014
59	184	Z	0
60	184	Z	0
61	185	Z	-0.023
62	185	Z	-0.022
63	185	Z	-0.006
64	185	Z	0
65	185	Z	0
66	117	Z	-0.017
67	117	Z	-0.018
68	117	Z	-0.014
69	117	Z	0
70	117	Z	0
71	118	Z	-0.023
72	118	Z	-0.022
73	118	Z	-0.008
74	118	Z	0
75	118	Z	0

Member Point Loads (BLC 10 : 90 Seismic)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
1	39	X	-0.039
2	39	X	-0.039
3	39	X	0
4	39	X	0
5	39	X	0
6	49	X	-0.02
7	49	X	-0.02
8	49	X	-0.025
9	49	X	-0.025
10	49	X	0
11	52	X	-0.027
12	52	X	-0.027
13	52	X	0
14	52	X	0
15	52	X	0
16	180	X	-0.039
17	180	X	-0.039
18	180	X	0
19	180	X	0
20	180	X	0
21	194	X	-0.02
22	194	X	-0.02
23	194	X	-0.025
24	194	X	-0.025
25	194	X	0
26	192	X	-0.027
27	192	X	-0.027
28	192	X	0
29	192	X	0
30	192	X	0
31	113	X	-0.039
32	113	X	-0.039

Member Point Loads (BLC 10 : 90 Seismic) (Continued)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
33	113	X	0
34	113	X	0
35	113	X	0
36	127	X	-0.02
37	127	X	-0.02
38	127	X	-0.025
39	127	X	-0.025
40	127	X	0
41	125	X	-0.027
42	125	X	-0.027
43	125	X	0
44	125	X	0
45	125	X	0
46	55	X	-0.017
47	55	X	-0.018
48	55	X	-0.014
49	55	X	0
50	55	X	0
51	58	X	-0.023
52	58	X	-0.022
53	58	X	-0.006
54	58	X	0
55	58	X	0
56	184	X	-0.017
57	184	X	-0.018
58	184	X	-0.014
59	184	X	0
60	184	X	0
61	185	X	-0.023
62	185	X	-0.022
63	185	X	-0.006
64	185	X	0
65	185	X	0
66	117	X	-0.017
67	117	X	-0.018
68	117	X	-0.014
69	117	X	0
70	117	X	0
71	118	X	-0.023
72	118	X	-0.022
73	118	X	-0.008
74	118	X	0
75	118	X	0

Member Point Loads (BLC 15 : Maint LL 1)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
1	11	Y	-0.25

Member Point Loads (BLC 16 : Maint LL 2)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
1	18	Y	-0.25

Member Point Loads (BLC 17 : Maint LL 3)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
21	Y	-0.25	%50

Member Point Loads (BLC 18 : Maint LL 4)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
24	Y	-0.25	%50

Member Point Loads (BLC 19 : Maint LL 5)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
136	Y	-0.25	%50

Member Point Loads (BLC 20 : Maint LL 6)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
165	Y	-0.25	%50

Member Point Loads (BLC 21 : Maint LL 7)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
131	Y	-0.25	%50

Member Point Loads (BLC 22 : Maint LL 8)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
170	Y	-0.25	%50

Member Point Loads (BLC 23 : Maint LL 9)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
72	Y	-0.25	%50

Member Point Loads (BLC 24 : Maint LL 10)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
101	Y	-0.25	%50

Member Point Loads (BLC 25 : Maint LL 11)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
67	Y	-0.25	%50

Member Point Loads (BLC 26 : Maint LL 12)

Member Label	Direction	Magnitude [k, k-ft]	Location [(ft, %)]
106	Y	-0.25	%50

Member Distributed Loads (BLC 2 : 0 Wind - No Ice)

Member Label	Direction	Start Magnitude [k/ft, F, ksf, k-ft/ft]	End Magnitude [k/ft, F, ksf, k-ft/ft]	Start Location [(ft, %)]	End Location [(ft, %)]
1	1	Z	-0.013	-0.013	0 %100
2	2	Z	-0.013	-0.013	0 %100
3	3	Z	-0.003	-0.003	0 %100
4	4	Z	-0.003	-0.003	0 %100
5	5	Z	-0.003	-0.003	0 %100
6	6	Z	-0.003	-0.003	0 %100
7	9	Z	-0.003	-0.003	0 %100
8	10	Z	-0.003	-0.003	0 %100
9	11	Z	-0.008	-0.008	0 %100
10	12	Z	-0.006	-0.006	0 %100
11	13	Z	-0.006	-0.006	0 %100
12	14	Z	-0.006	-0.006	0 %100
13	15	Z	-0.006	-0.006	0 %100
14	16	Z	-0.003	-0.003	0 %100
15	17	Z	-0.003	-0.003	0 %100
16	18	Z	-0.008	-0.008	0 %100
17	19	Z	-0.003	-0.003	0 %100
18	20	Z	-0.003	-0.003	0 %100
19	21	Z	-0.008	-0.008	0 %100
20	22	Z	-0.003	-0.003	0 %100
21	23	Z	-0.003	-0.003	0 %100
22	24	Z	-0.008	-0.008	0 %100
23	29	Z	-0.003	-0.003	0 %100
24	30	Z	-0.003	-0.003	0 %100
25	31	Z	-0.003	-0.003	0 %100
26	32	Z	-0.003	-0.003	0 %100
27	33	Z	-0.003	-0.003	0 %100
28	34	Z	-0.003	-0.003	0 %100
29	35	Z	-0.003	-0.003	0 %100
30	36	Z	-0.003	-0.003	0 %100
31	39	Z	-0.011	-0.011	0 %100
32	40	Z	-0.011	-0.011	0 %100
33	43	Z	-0.011	-0.011	0 %100
34	44	Z	-0.009	-0.009	0 %100
35	49	Z	-0.011	-0.011	0 %100
36	52	Z	-0.011	-0.011	0 %100
37	55	Z	-0.011	-0.011	0 %100
38	58	Z	-0.011	-0.011	0 %100
39	99	Z	-0.009	-0.009	0 %100
40	146	Z	-0.009	-0.009	0 %100
41	64	Z	-0.003	-0.003	0 %100
42	65	Z	-0.003	-0.003	0 %100
43	66	Z	-0.013	-0.013	0 %100
44	67	Z	-0.008	-0.008	0 %100
45	70	Z	-0.003	-0.003	0 %100
46	72	Z	-0.008	-0.008	0 %100
47	74	Z	-0.006	-0.006	0 %100
48	76	Z	-0.006	-0.006	0 %100
49	77	Z	-0.006	-0.006	0 %100
50	82	Z	-0.003	-0.003	0 %100
51	83	Z	-0.003	-0.003	0 %100
52	93	Z	-0.013	-0.013	0 %100
53	94	Z	-0.003	-0.003	0 %100
54	95	Z	-0.003	-0.003	0 %100
55	96	Z	-0.003	-0.003	0 %100

Member Distributed Loads (BLC 2 : 0 Wind - No Ice) (Continued)

Member Label	Direction	Start Magnitude [k/ft, F, ksf, k-ft/ft]	End Magnitude [k/ft, F, ksf, k-ft/ft]	Start Location [(ft, %)]	End Location [(ft, %)]
56	97	Z	-0.003	-0.003	0 %100
57	98	Z	-0.006	-0.006	0 %100
58	100	Z	-0.003	-0.003	0 %100
59	101	Z	-0.008	-0.008	0 %100
60	102	Z	-0.003	-0.003	0 %100
61	103	Z	-0.003	-0.003	0 %100
62	104	Z	-0.003	-0.003	0 %100
63	105	Z	-0.003	-0.003	0 %100
64	106	Z	-0.008	-0.008	0 %100
65	107	Z	-0.003	-0.003	0 %100
66	108	Z	-0.003	-0.003	0 %100
67	109	Z	-0.003	-0.003	0 %100
68	110	Z	-0.003	-0.003	0 %100
69	111	Z	-0.003	-0.003	0 %100
70	112	Z	-0.003	-0.003	0 %100
71	113	Z	-0.011	-0.011	0 %100
72	114	Z	-0.011	-0.011	0 %100
73	115	Z	-0.011	-0.011	0 %100
74	117	Z	-0.011	-0.011	0 %100
75	118	Z	-0.011	-0.011	0 %100
76	125	Z	-0.011	-0.011	0 %100
77	127	Z	-0.011	-0.011	0 %100
78	128	Z	-0.003	-0.003	0 %100
79	129	Z	-0.003	-0.003	0 %100
80	130	Z	-0.013	-0.013	0 %100
81	131	Z	-0.008	-0.008	0 %100
82	134	Z	-0.003	-0.003	0 %100
83	136	Z	-0.008	-0.008	0 %100
84	138	Z	-0.006	-0.006	0 %100
85	140	Z	-0.006	-0.006	0 %100
86	141	Z	-0.006	-0.006	0 %100
87	147	Z	-0.003	-0.003	0 %100
88	148	Z	-0.003	-0.003	0 %100
89	158	Z	-0.013	-0.013	0 %100
90	159	Z	-0.003	-0.003	0 %100
91	160	Z	-0.003	-0.003	0 %100
92	161	Z	-0.003	-0.003	0 %100
93	162	Z	-0.003	-0.003	0 %100
94	163	Z	-0.006	-0.006	0 %100
95	164	Z	-0.003	-0.003	0 %100
96	165	Z	-0.008	-0.008	0 %100
97	166	Z	-0.003	-0.003	0 %100
98	167	Z	-0.003	-0.003	0 %100
99	168	Z	-0.003	-0.003	0 %100
100	169	Z	-0.003	-0.003	0 %100
101	170	Z	-0.008	-0.008	0 %100
102	171	Z	-0.003	-0.003	0 %100
103	172	Z	-0.003	-0.003	0 %100
104	176	Z	-0.003	-0.003	0 %100
105	177	Z	-0.003	-0.003	0 %100
106	178	Z	-0.003	-0.003	0 %100
107	179	Z	-0.003	-0.003	0 %100
108	180	Z	-0.011	-0.011	0 %100
109	181	Z	-0.011	-0.011	0 %100
110	182	Z	-0.011	-0.011	0 %100

Member Distributed Loads (BLC 2 : 0 Wind - No Ice) (Continued)

Member Label	Direction	Start Magnitude [k/ft, F, ksf, k-ft/ft]	End Magnitude [k/ft, F, ksf, k-ft/ft]	Start Location [(ft, %)]	End Location [(ft, %)]
111	184	Z	-0.011	-0.011	0 %100
112	185	Z	-0.011	-0.011	0 %100
113	192	Z	-0.011	-0.011	0 %100
114	194	Z	-0.011	-0.011	0 %100

Member Distributed Loads (BLC 3 : 90 Wind - No Ice)

Member Label	Direction	Start Magnitude [k/ft, F, ksf, k-ft/ft]	End Magnitude [k/ft, F, ksf, k-ft/ft]	Start Location [(ft, %)]	End Location [(ft, %)]
1	1	X	-0.013	-0.013	0 %100
2	2	X	-0.013	-0.013	0 %100
3	3	X	-0.003	-0.003	0 %100
4	4	X	-0.003	-0.003	0 %100
5	5	X	-0.003	-0.003	0 %100
6	6	X	-0.003	-0.003	0 %100
7	9	X	-0.003	-0.003	0 %100
8	10	X	-0.003	-0.003	0 %100
9	11	X	-0.008	-0.008	0 %100
10	12	X	-0.006	-0.006	0 %100
11	13	X	-0.006	-0.006	0 %100
12	14	X	-0.006	-0.006	0 %100
13	15	X	-0.006	-0.006	0 %100
14	16	X	-0.003	-0.003	0 %100
15	17	X	-0.003	-0.003	0 %100
16	18	X	-0.008	-0.008	0 %100
17	19	X	-0.003	-0.003	0 %100
18	20	X	-0.003	-0.003	0 %100
19	21	X	-0.008	-0.008	0 %100
20	22	X	-0.003	-0.003	0 %100
21	23	X	-0.003	-0.003	0 %100
22	24	X	-0.008	-0.008	0 %100
23	29	X	-0.003	-0.003	0 %100
24	30	X	-0.003	-0.003	0 %100
25	31	X	-0.003	-0.003	0 %100
26	32	X	-0.003	-0.003	0 %100
27	33	X	-0.003	-0.003	0 %100
28	34	X	-0.003	-0.003	0 %100
29	35	X	-0.003	-0.003	0 %100
30	36	X	-0.003	-0.003	0 %100
31	39	X	-0.011	-0.011	0 %100
32	40	X	-0.011	-0.011	0 %100
33	43	X	-0.011	-0.011	0 %100
34	44	X	-0.009	-0.009	0 %100
35	49	X	-0.011	-0.011	0 %100
36	52	X	-0.011	-0.011	0 %100
37	55	X	-0.011	-0.011	0 %100
38	58	X	-0.011	-0.011	0 %100
39	99	X	-0.009	-0.009	0 %100
40	146	X	-0.009	-0.009	0 %100
41	64	X	-0.003	-0.003	0 %100
42	65	X	-0.003	-0.003	0 %100
43	66	X	-0.013	-0.013	0 %100
44	67	X	-0.008	-0.008	0 %100
45	70	X	-0.003	-0.003	0 %100
46	72	X	-0.008	-0.008	0 %100
47	74	X	-0.006	-0.006	0 %100
48	76	X	-0.006	-0.006	0 %100

Member Distributed Loads (BLC 3 : 90 Wind - No Ice) (Continued)

Member Label	Direction	Start Magnitude [k/ft, F, ksf, k-ft/ft]	End Magnitude [k/ft, F, ksf, k-ft/ft]	Start Location [(ft, %)]	End Location [(ft, %)]
49	77	X	-0.006	-0.006	0 %100
50	82	X	-0.003	-0.003	0 %100
51	83	X	-0.003	-0.003	0 %100
52	93	X	-0.013	-0.013	0 %100
53	94	X	-0.003	-0.003	0 %100
54	95	X	-0.003	-0.003	0 %100
55	96	X	-0.003	-0.003	0 %100
56	97	X	-0.003	-0.003	0 %100
57	98	X	-0.006	-0.006	0 %100
58	100	X	-0.003	-0.003	0 %100
59	101	X	-0.008	-0.008	0 %100
60	102	X	-0.003	-0.003	0 %100
61	103	X	-0.003	-0.003	0 %100
62	104	X	-0.003	-0.003	0 %100
63	105	X	-0.003	-0.003	0 %100
64	106	X	-0.008	-0.008	0 %100
65	107	X	-0.003	-0.003	0 %100
66	108	X	-0.003	-0.003	0 %100
67	109	X	-0.003	-0.003	0 %100
68	110	X	-0.003	-0.003	0 %100
69	111	X	-0.003	-0.003	0 %100
70	112	X	-0.003	-0.003	0 %100
71	113	X	-0.011	-0.011	0 %100
72	114	X	-0.011	-0.011	0 %100
73	115	X	-0.011	-0.011	0 %100
74	117	X	-0.011	-0.011	0 %100
75	118	X	-0.011	-0.011	0 %100
76	125	X	-0.011	-0.011	0 %100
77	127	X	-0.011	-0.011	0 %100
78	128	X	-0.003	-0.003	0 %100
79	129	X	-0.003	-0.003	0 %100
80	130	X	-0.013	-0.013	0 %100
81	131	X	-0.008	-0.008	0 %100
82	134	X	-0.003	-0.003	0 %100
83	136	X	-0.008	-0.008	0 %100
84	138	X	-0.006	-0.006	0 %100
85	140	X	-0.006	-0.006	0 %100
86	141	X	-0.006	-0.006	0 %100
87	147	X	-0.003	-0.003	0 %100
88	148	X	-0.003	-0.003	0 %100
89	158	X	-0.013	-0.013	0 %100
90	159	X	-0.003	-0.003	0 %100
91	160	X	-0.003	-0.003	0 %100
92	161	X	-0.003	-0.003	0 %100
93	162	X	-0.003	-0.003	0 %100
94	163	X	-0.006	-0.006	0 %100
95	164	X	-0.003	-0.003	0 %100
96	165	X	-0.008	-0.008	0 %100
97	166	X	-0.003	-0.003	0 %100
98	167	X	-0.003	-0.003	0 %100
99	168	X	-0.003	-0.003	0 %100
100	169	X	-0.003	-0.003	0 %100
101	170	X	-0.008	-0.008	0 %100
102	171	X	-0.003	-0.003	0 %100
103	172	X	-0.003	-0.003	0 %100

Member Distributed Loads (BLC 3 : 90 Wind - No Ice) (Continued)

Member Label	Direction	Start Magnitude [k/ft, F, ksf, k-ft/ft]	End Magnitude [k/ft, F, ksf, k-ft/ft]	Start Location [(ft, %)]	End Location [(ft, %)]
104	176	X	-0.003	-0.003	0 %100
105	177	X	-0.003	-0.003	0 %100
106	178	X	-0.003	-0.003	0 %100
107	179	X	-0.003	-0.003	0 %100
108	180	X	-0.011	-0.011	0 %100
109	181	X	-0.011	-0.011	0 %100
110	182	X	-0.011	-0.011	0 %100
111	184	X	-0.011	-0.011	0 %100
112	185	X	-0.011	-0.011	0 %100
113	192	X	-0.011	-0.011	0 %100
114	194	X	-0.011	-0.011	0 %100

Member Distributed Loads (BLC 4 : 0 Wind - Ice)

Member Label	Direction	Start Magnitude [k/ft, F, ksf, k-ft/ft]	End Magnitude [k/ft, F, ksf, k-ft/ft]	Start Location [(ft, %)]	End Location [(ft, %)]
1	1	Z	-0.002	-0.002	0 %100
2	2	Z	-0.002	-0.002	0 %100
3	3	Z	-0.004	-0.004	0 %100
4	4	Z	-0.004	-0.004	0 %100
5	5	Z	-0.004	-0.004	0 %100
6	6	Z	-0.004	-0.004	0 %100
7	9	Z	-0.008	-0.008	0 %100
8	10	Z	-0.008	-0.008	0 %100
9	11	Z	-0.002	-0.002	0 %100
10	12	Z	-0.004	-0.004	0 %100
11	13	Z	-0.004	-0.004	0 %100
12	14	Z	-0.004	-0.004	0 %100
13	15	Z	-0.004	-0.004	0 %100
14	16	Z	-0.008	-0.008	0 %100
15	17	Z	-0.008	-0.008	0 %100
16	18	Z	-0.002	-0.002	0 %100
17	19	Z	-0.008	-0.008	0 %100
18	20	Z	-0.008	-0.008	0 %100
19	21	Z	-0.002	-0.002	0 %100
20	22	Z	-0.008	-0.008	0 %100
21	23	Z	-0.008	-0.008	0 %100
22	24	Z	-0.002	-0.002	0 %100
23	29	Z	-0.002	-0.002	0 %100
24	30	Z	-0.002	-0.002	0 %100
25	31	Z	-0.002	-0.002	0 %100
26	32	Z	-0.002	-0.002	0 %100
27	33	Z	-0.002	-0.002	0 %100
28	34	Z	-0.002	-0.002	0 %100
29	35	Z	-0.002	-0.002	0 %100
30	36	Z	-0.002	-0.002	0 %100
31	39	Z	-0.002	-0.002	0 %100
32	40	Z	-0.002	-0.002	0 %100
33	43	Z	-0.002	-0.002	0 %100
34	44	Z	-0.003	-0.003	0 %100
35	49	Z	-0.002	-0.002	0 %100
36	52	Z	-0.002	-0.002	0 %100
37	55	Z	-0.002	-0.002	0 %100
38	58	Z	-0.002	-0.002	0 %100
39	99	Z	-0.003	-0.003	0 %100
40	146	Z	-0.003	-0.003	0 %100
41	64	Z	-0.008	-0.008	0 %100

Member Distributed Loads (BLC 4 : 0 Wind - Ice) (Continued)

Member Label	Direction	Start Magnitude [k/ft, F, ksf, k-ft/ft]	End Magnitude [k/ft, F, ksf, k-ft/ft]	Start Location [(ft, %)]	End Location [(ft, %)]
42	65	Z	-0.008	-0.008	0 %100
43	66	Z	-0.002	-0.002	0 %100
44	67	Z	-0.002	-0.002	0 %100
45	70	Z	-0.004	-0.004	0 %100
46	72	Z	-0.002	-0.002	0 %100
47	74	Z	-0.004	-0.004	0 %100
48	76	Z	-0.004	-0.004	0 %100
49	77	Z	-0.004	-0.004	0 %100
50	82	Z	-0.002	-0.002	0 %100
51	83	Z	-0.002	-0.002	0 %100
52	93	Z	-0.002	-0.002	0 %100
53	94	Z	-0.004	-0.004	0 %100
54	95	Z	-0.004	-0.004	0 %100
55	96	Z	-0.004	-0.004	0 %100
56	97	Z	-0.008	-0.008	0 %100
57	98	Z	-0.004	-0.004	0 %100
58	100	Z	-0.008	-0.008	0 %100
59	101	Z	-0.002	-0.002	0 %100
60	102	Z	-0.008	-0.008	0 %100
61	103	Z	-0.008	-0.008	0 %100
62	104	Z	-0.008	-0.008	0 %100
63	105	Z	-0.008	-0.008	0 %100
64	106	Z	-0.002	-0.002	0 %100
65	107	Z	-0.002	-0.002	0 %100
66	108	Z	-0.002	-0.002	0 %100
67	109	Z	-0.002	-0.002	0 %100
68	110	Z	-0.002	-0.002	0 %100
69	111	Z	-0.002	-0.002	0 %100
70	112	Z	-0.002	-0.002	0 %100
71	113	Z	-0.002	-0.002	0 %100
72	114	Z	-0.002	-0.002	0 %100
73	115	Z	-0.002	-0.002	0 %100
74	117	Z	-0.002	-0.002	0 %100
75	118	Z	-0.002	-0.002	0 %100
76	125	Z	-0.002	-0.002	0 %100
77	127	Z	-0.002	-0.002	0 %100
78	128	Z	-0.008	-0.008	0 %100
79	129	Z	-0.008	-0.008	0 %100
80	130	Z	-0.002	-0.002	0 %100
81	131	Z	-0.002	-0.002	0 %100
82	134	Z	-0.004	-0.004	0 %100
83	136	Z	-0.002	-0.002	0 %100
84	138	Z	-0.004	-0.004	0 %100
85	140	Z	-0.004	-0.004	0 %100
86	141	Z	-0.004	-0.004	0 %100
87	147	Z	-0.002	-0.002	0 %100
88	148	Z	-0.002	-0.002	0 %100
89	158	Z	-0.002	-0.002	0 %100
90	159	Z	-0.004	-0.004	0 %100
91	160	Z	-0.004	-0.004	0 %100
92	161	Z	-0.004	-0.004	0 %100
93	162	Z	-0.008	-0.008	0 %100
94	163	Z	-0.004	-0.004	0 %100
95	164	Z	-0.008	-0.008	0 %100
96	165	Z	-0.002	-0.002	0 %100

Member Distributed Loads (BLC 4 : 0 Wind - Ice) (Continued)

Member Label	Direction	Start Magnitude [k/ft, F, ksf, k-ft/ft]	End Magnitude [k/ft, F, ksf, k-ft/ft]	Start Location [(ft, %)]	End Location [(ft, %)]
97	166	Z	-0.008	-0.008	0 %100
98	167	Z	-0.008	-0.008	0 %100
99	168	Z	-0.008	-0.008	0 %100
100	169	Z	-0.008	-0.008	0 %100
101	170	Z	-0.002	-0.002	0 %100
102	171	Z	-0.002	-0.002	0 %100
103	172	Z	-0.002	-0.002	0 %100
104	176	Z	-0.002	-0.002	0 %100
105	177	Z	-0.002	-0.002	0 %100
106	178	Z	-0.002	-0.002	0 %100
107	179	Z	-0.002	-0.002	0 %100
108	180	Z	-0.002	-0.002	0 %100
109	181	Z	-0.002	-0.002	0 %100
110	182	Z	-0.002	-0.002	0 %100
111	184	Z	-0.002	-0.002	0 %100
112	185	Z	-0.002	-0.002	0 %100
113	192	Z	-0.002	-0.002	0 %100
114	194	Z	-0.002	-0.002	0 %100

Member Distributed Loads (BLC 5 : 90 Wind - Ice)

Member Label	Direction	Start Magnitude [k/ft, F, ksf, k-ft/ft]	End Magnitude [k/ft, F, ksf, k-ft/ft]	Start Location [(ft, %)]	End Location [(ft, %)]
1	1	X	-0.002	-0.002	0 %100
2	2	X	-0.002	-0.002	0 %100
3	3	X	-0.004	-0.004	0 %100
4	4	X	-0.004	-0.004	0 %100
5	5	X	-0.004	-0.004	0 %100
6	6	X	-0.004	-0.004	0 %100
7	9	X	-0.008	-0.008	0 %100
8	10	X	-0.008	-0.008	0 %100
9	11	X	-0.002	-0.002	0 %100
10	12	X	-0.004	-0.004	0 %100
11	13	X	-0.004	-0.004	0 %100
12	14	X	-0.004	-0.004	0 %100
13	15	X	-0.004	-0.004	0 %100
14	16	X	-0.008	-0.008	0 %100
15	17	X	-0.008	-0.008	0 %100
16	18	X	-0.002	-0.002	0 %100
17	19	X	-0.008	-0.008	0 %100
18	20	X	-0.008	-0.008	0 %100
19	21	X	-0.002	-0.002	0 %100
20	22	X	-0.008	-0.008	0 %100
21	23	X	-0.008	-0.008	0 %100
22	24	X	-0.002	-0.002	0 %100
23	29	X	-0.002	-0.002	0 %100
24	30	X	-0.002	-0.002	0 %100
25	31	X	-0.002	-0.002	0 %100
26	32	X	-0.002	-0.002	0 %100
27	33	X	-0.002	-0.002	0 %100
28	34	X	-0.002	-0.002	0 %100
29	35	X	-0.002	-0.002	0 %100
30	36	X	-0.002	-0.002	0 %100
31	39	X	-0.002	-0.002	0 %100
32	40	X	-0.002	-0.002	0 %100
33	43	X	-0.002	-0.002	0 %100
34	44	X	-0.003	-0.003	0 %100

Member Distributed Loads (BLC 5 : 90 Wind - Ice) (Continued)

Member Label	Direction	Start Magnitude [k/ft, F, ksf, k-ft/ft]	End Magnitude [k/ft, F, ksf, k-ft/ft]	Start Location [(ft, %)]	End Location [(ft, %)]
35	49	X	-0.002	-0.002	0 %100
36	52	X	-0.002	-0.002	0 %100
37	55	X	-0.002	-0.002	0 %100
38	58	X	-0.002	-0.002	0 %100
39	99	X	-0.003	-0.003	0 %100
40	146	X	-0.003	-0.003	0 %100
41	64	X	-0.008	-0.008	0 %100
42	65	X	-0.008	-0.008	0 %100
43	66	X	-0.002	-0.002	0 %100
44	67	X	-0.002	-0.002	0 %100
45	70	X	-0.004	-0.004	0 %100
46	72	X	-0.002	-0.002	0 %100
47	74	X	-0.004	-0.004	0 %100
48	76	X	-0.004	-0.004	0 %100
49	77	X	-0.004	-0.004	0 %100
50	82	X	-0.002	-0.002	0 %100
51	83	X	-0.002	-0.002	0 %100
52	93	X	-0.002	-0.002	0 %100
53	94	X	-0.004	-0.004	0 %100
54	95	X	-0.004	-0.004	0 %100
55	96	X	-0.004	-0.004	0 %100
56	97	X	-0.008	-0.008	0 %100
57	98	X	-0.004	-0.004	0 %100
58	100	X	-0.008	-0.008	0 %100
59	101	X	-0.002	-0.002	0 %100
60	102	X	-0.008	-0.008	0 %100
61	103	X	-0.008	-0.008	0 %100
62	104	X	-0.008	-0.008	0 %100
63	105	X	-0.008	-0.008	0 %100
64	106	X	-0.002	-0.002	0 %100
65	107	X	-0.002	-0.002	0 %100
66	108	X	-0.002	-0.002	0 %100
67	109	X	-0.002	-0.002	0 %100
68	110	X	-0.002	-0.002	0 %100
69	111	X	-0.002	-0.002	0 %100
70	112	X	-0.002	-0.002	0 %100
71	113	X	-0.002	-0.002	0 %100
72	114	X	-0.002	-0.002	0 %100
73	115	X	-0.002	-0.002	0 %100
74	117	X	-0.002	-0.002	0 %100
75	118	X	-0.002	-0.002	0 %100
76	125	X	-0.002	-0.002	0 %100
77	127	X	-0.002	-0.002	0 %100
78	128	X	-0.008	-0.008	0 %100
79	129	X	-0.008	-0.008	0 %100
80	130	X	-0.002	-0.002	0 %100
81	131	X	-0.002	-0.002	0 %100
82	134	X	-0.004	-0.004	0 %100
83	136	X	-0.002	-0.002	0 %100
84	138	X	-0.004	-0.004	0 %100
85	140	X	-0.004	-0.004	0 %100
86	141	X	-0.004	-0.004	0 %100
87	147	X	-0.002	-0.002	0 %100
88	148	X	-0.002	-0.002	0 %100
89	158	X	-0.002	-0.002	0 %100

Member Distributed Loads (BLC 5 : 90 Wind - Ice) (Continued)

Member Label	Direction	Start Magnitude [k/ft, F, ksf, k-ft/ft]	End Magnitude [k/ft, F, ksf, k-ft/ft]	Start Location [(ft, %)]	End Location [(ft, %)]
90	159	X	-0.004	-0.004	0 %100
91	160	X	-0.004	-0.004	0 %100
92	161	X	-0.004	-0.004	0 %100
93	162	X	-0.008	-0.008	0 %100
94	163	X	-0.004	-0.004	0 %100
95	164	X	-0.008	-0.008	0 %100
96	165	X	-0.002	-0.002	0 %100
97	166	X	-0.008	-0.008	0 %100
98	167	X	-0.008	-0.008	0 %100
99	168	X	-0.008	-0.008	0 %100
100	169	X	-0.008	-0.008	0 %100
101	170	X	-0.002	-0.002	0 %100
102	171	X	-0.002	-0.002	0 %100
103	172	X	-0.002	-0.002	0 %100
104	176	X	-0.002	-0.002	0 %100
105	177	X	-0.002	-0.002	0 %100
106	178	X	-0.002	-0.002	0 %100
107	179	X	-0.002	-0.002	0 %100
108	180	X	-0.002	-0.002	0 %100
109	181	X	-0.002	-0.002	0 %100
110	182	X	-0.002	-0.002	0 %100
111	184	X	-0.002	-0.002	0 %100
112	185	X	-0.002	-0.002	0 %100
113	192	X	-0.002	-0.002	0 %100
114	194	X	-0.002	-0.002	0 %100

Member Distributed Loads (BLC 6 : 0 Wind - Service)

Member Label	Direction	Start Magnitude [k/ft, F, ksf, k-ft/ft]	End Magnitude [k/ft, F, ksf, k-ft/ft]	Start Location [(ft, %)]	End Location [(ft, %)]
1	1	Z	-0.0004	-0.0004	0 %100
2	2	Z	-0.0004	-0.0004	0 %100
3	3	Z	-0.0002	-0.0002	0 %100
4	4	Z	-0.0002	-0.0002	0 %100
5	5	Z	-0.0002	-0.0002	0 %100
6	6	Z	-0.0002	-0.0002	0 %100
7	9	Z	-0.0002	-0.0002	0 %100
8	10	Z	-0.0002	-0.0002	0 %100
9	11	Z	-0.0003	-0.0003	0 %100
10	12	Z	-0.0004	-0.0004	0 %100
11	13	Z	-0.0004	-0.0004	0 %100
12	14	Z	-0.0004	-0.0004	0 %100
13	15	Z	-0.0004	-0.0004	0 %100
14	16	Z	-0.0002	-0.0002	0 %100
15	17	Z	-0.0002	-0.0002	0 %100
16	18	Z	-0.0003	-0.0003	0 %100
17	19	Z	-0.0002	-0.0002	0 %100
18	20	Z	-0.0002	-0.0002	0 %100
19	21	Z	-0.0003	-0.0003	0 %100
20	22	Z	-0.0002	-0.0002	0 %100
21	23	Z	-0.0002	-0.0002	0 %100
22	24	Z	-0.0003	-0.0003	0 %100
23	29	Z	-0.0002	-0.0002	0 %100
24	30	Z	-0.0002	-0.0002	0 %100
25	31	Z	-0.0002	-0.0002	0 %100
26	32	Z	-0.0002	-0.0002	0 %100
27	33	Z	-0.0002	-0.0002	0 %100

Member Distributed Loads (BLC 6 : 0 Wind - Service) (Continued)

Member Label	Direction	Start Magnitude [k/ft, F, ksf, k-ft/ft]	End Magnitude [k/ft, F, ksf, k-ft/ft]	Start Location [(ft, %)]	End Location [(ft, %)]
28	34	Z	-0.0002	-0.0002	0 %100
29	35	Z	-0.0002	-0.0002	0 %100
30	36	Z	-0.0002	-0.0002	0 %100
31	39	Z	-0.0003	-0.0003	0 %100
32	40	Z	-0.0003	-0.0003	0 %100
33	43	Z	-0.0003	-0.0003	0 %100
34	44	Z	-0.0006	-0.0006	0 %100
35	49	Z	-0.0003	-0.0003	0 %100
36	52	Z	-0.0003	-0.0003	0 %100
37	55	Z	-0.0003	-0.0003	0 %100
38	58	Z	-0.0003	-0.0003	0 %100
39	99	Z	-0.0006	-0.0006	0 %100
40	146	Z	-0.0006	-0.0006	0 %100
41	64	Z	-0.0002	-0.0002	0 %100
42	65	Z	-0.0002	-0.0002	0 %100
43	66	Z	-0.0004	-0.0004	0 %100
44	67	Z	-0.0003	-0.0003	0 %100
45	70	Z	-0.0002	-0.0002	0 %100
46	72	Z	-0.0003	-0.0003	0 %100
47	74	Z	-0.0004	-0.0004	0 %100
48	76	Z	-0.0004	-0.0004	0 %100
49	77	Z	-0.0004	-0.0004	0 %100
50	82	Z	-0.0002	-0.0002	0 %100
51	83	Z	-0.0002	-0.0002	0 %100
52	93	Z	-0.0004	-0.0004	0 %100
53	94	Z	-0.0002	-0.0002	0 %100
54	95	Z	-0.0002	-0.0002	0 %100
55	96	Z	-0.0002	-0.0002	0 %100
56	97	Z	-0.0002	-0.0002	0 %100
57	98	Z	-0.0004	-0.0004	0 %100
58	100	Z	-0.0002	-0.0002	0 %100
59	101	Z	-0.0003	-0.0003	0 %100
60	102	Z	-0.0002	-0.0002	0 %100
61	103	Z	-0.0002	-0.0002	0 %100
62	104	Z	-0.0002	-0.0002	0 %100
63	105	Z	-0.0002	-0.0002	0 %100
64	106	Z	-0.0003	-0.0003	0 %100
65	107	Z	-0.0002	-0.0002	0 %100
66	108	Z	-0.0002	-0.0002	0 %100
67	109	Z	-0.0002	-0.0002	0 %100
68	110	Z	-0.0002	-0.0002	0 %100
69	111	Z	-0.0002	-0.0002	0 %100
70	112	Z	-0.0002	-0.0002	0 %100
71	113	Z	-0.0003	-0.0003	0 %100
72	114	Z	-0.0003	-0.0003	0 %100
73	115	Z	-0.0003	-0.0003	0 %100
74	117	Z	-0.0003	-0.0003	0 %100
75	118	Z	-0.0003	-0.0003	0 %100
76	125	Z	-0.0003	-0.0003	0 %100
77	127	Z	-0.0003	-0.0003	0 %100
78	128	Z	-0.0002	-0.0002	0 %100
79	129	Z	-0.0002	-0.0002	0 %100
80	130	Z	-0.0004	-0.0004	0 %100
81	131	Z	-0.0003	-0.0003	0 %100
82	134	Z	-0.0002	-0.0002	0 %100

Member Distributed Loads (BLC 6 : 0 Wind - Service) (Continued)

Member Label	Direction	Start Magnitude [k/ft, F, ksf, k-ft/ft]	End Magnitude [k/ft, F, ksf, k-ft/ft]	Start Location [(ft, %)]	End Location [(ft, %)]
83	136	Z	-0.0003	-0.0003	0 %100
84	138	Z	-0.0004	-0.0004	0 %100
85	140	Z	-0.0004	-0.0004	0 %100
86	141	Z	-0.0004	-0.0004	0 %100
87	147	Z	-0.0002	-0.0002	0 %100
88	148	Z	-0.0002	-0.0002	0 %100
89	158	Z	-0.0004	-0.0004	0 %100
90	159	Z	-0.0002	-0.0002	0 %100
91	160	Z	-0.0002	-0.0002	0 %100
92	161	Z	-0.0002	-0.0002	0 %100
93	162	Z	-0.0002	-0.0002	0 %100
94	163	Z	-0.0004	-0.0004	0 %100
95	164	Z	-0.0002	-0.0002	0 %100
96	165	Z	-0.0003	-0.0003	0 %100
97	166	Z	-0.0002	-0.0002	0 %100
98	167	Z	-0.0002	-0.0002	0 %100
99	168	Z	-0.0002	-0.0002	0 %100
100	169	Z	-0.0002	-0.0002	0 %100
101	170	Z	-0.0003	-0.0003	0 %100
102	171	Z	-0.0002	-0.0002	0 %100
103	172	Z	-0.0002	-0.0002	0 %100
104	176	Z	-0.0002	-0.0002	0 %100
105	177	Z	-0.0002	-0.0002	0 %100
106	178	Z	-0.0002	-0.0002	0 %100
107	179	Z	-0.0002	-0.0002	0 %100
108	180	Z	-0.0003	-0.0003	0 %100
109	181	Z	-0.0003	-0.0003	0 %100
110	182	Z	-0.0003	-0.0003	0 %100
111	184	Z	-0.0003	-0.0003	0 %100
112	185	Z	-0.0003	-0.0003	0 %100
113	192	Z	-0.0003	-0.0003	0 %100
114	194	Z	-0.0003	-0.0003	0 %100

Member Distributed Loads (BLC 7 : 90 Wind - Service)

Member Label	Direction	Start Magnitude [k/ft, F, ksf, k-ft/ft]	End Magnitude [k/ft, F, ksf, k-ft/ft]	Start Location [(ft, %)]	End Location [(ft, %)]
1	1	X	-0.0004	-0.0004	0 %100
2	2	X	-0.0004	-0.0004	0 %100
3	3	X	-0.0002	-0.0002	0 %100
4	4	X	-0.0002	-0.0002	0 %100
5	5	X	-0.0002	-0.0002	0 %100
6	6	X	-0.0002	-0.0002	0 %100
7	9	X	-0.0002	-0.0002	0 %100
8	10	X	-0.0002	-0.0002	0 %100
9	11	X	-0.0003	-0.0003	0 %100
10	12	X	-0.0004	-0.0004	0 %100
11	13	X	-0.0004	-0.0004	0 %100
12	14	X	-0.0004	-0.0004	0 %100
13	15	X	-0.0004	-0.0004	0 %100
14	16	X	-0.0002	-0.0002	0 %100
15	17	X	-0.0002	-0.0002	0 %100
16	18	X	-0.0003	-0.0003	0 %100
17	19	X	-0.0002	-0.0002	0 %100
18	20	X	-0.0002	-0.0002	0 %100
19	21	X	-0.0003	-0.0003	0 %100
20	22	X	-0.0002	-0.0002	0 %100

Member Distributed Loads (BLC 7 : 90 Wind - Service) (Continued)

Member Label	Direction	Start Magnitude [k/ft, F, ksf, k-ft/ft]	End Magnitude [k/ft, F, ksf, k-ft/ft]	Start Location [(ft, %)]	End Location [(ft, %)]
21	23	X	-0.0002	-0.0002	0 %100
22	24	X	-0.0003	-0.0003	0 %100
23	29	X	-0.0002	-0.0002	0 %100
24	30	X	-0.0002	-0.0002	0 %100
25	31	X	-0.0002	-0.0002	0 %100
26	32	X	-0.0002	-0.0002	0 %100
27	33	X	-0.0002	-0.0002	0 %100
28	34	X	-0.0002	-0.0002	0 %100
29	35	X	-0.0002	-0.0002	0 %100
30	36	X	-0.0002	-0.0002	0 %100
31	39	X	-0.0003	-0.0003	0 %100
32	40	X	-0.0003	-0.0003	0 %100
33	43	X	-0.0003	-0.0003	0 %100
34	44	X	-0.0006	-0.0006	0 %100
35	49	X	-0.0003	-0.0003	0 %100
36	52	X	-0.0003	-0.0003	0 %100
37	55	X	-0.0003	-0.0003	0 %100
38	58	X	-0.0003	-0.0003	0 %100
39	99	X	-0.0006	-0.0006	0 %100
40	146	X	-0.0006	-0.0006	0 %100
41	64	X	-0.0002	-0.0002	0 %100
42	65	X	-0.0002	-0.0002	0 %100
43	66	X	-0.0004	-0.0004	0 %100
44	67	X	-0.0003	-0.0003	0 %100
45	70	X	-0.0002	-0.0002	0 %100
46	72	X	-0.0003	-0.0003	0 %100
47	74	X	-0.0004	-0.0004	0 %100
48	76	X	-0.0004	-0.0004	0 %100
49	77	X	-0.0004	-0.0004	0 %100
50	82	X	-0.0002	-0.0002	0 %100
51	83	X	-0.0002	-0.0002	0 %100
52	93	X	-0.0004	-0.0004	0 %100
53	94	X	-0.0002	-0.0002	0 %100
54	95	X	-0.0002	-0.0002	0 %100
55	96	X	-0.0002	-0.0002	0 %100
56	97	X	-0.0002	-0.0002	0 %100
57	98	X	-0.0004	-0.0004	0 %100
58	100	X	-0.0002	-0.0002	0 %100
59	101	X	-0.0003	-0.0003	0 %100
60	102	X	-0.0002	-0.0002	0 %100
61	103	X	-0.0002	-0.0002	0 %100
62	104	X	-0.0002	-0.0002	0 %100
63	105	X	-0.0002	-0.0002	0 %100
64	106	X	-0.0003	-0.0003	0 %100
65	107	X	-0.0002	-0.0002	0 %100
66	108	X	-0.0002	-0.0002	0 %100
67	109	X	-0.0002	-0.0002	0 %100
68	110	X	-0.0002	-0.0002	0 %100
69	111	X	-0.0002	-0.0002	0 %100
70	112	X	-0.0002	-0.0002	0 %100
71	113	X	-0.0003	-0.0003	0 %100
72	114	X	-0.0003	-0.0003	0 %100
73	115	X	-0.0003	-0.0003	0 %100
74	117	X	-0.0003	-0.0003	0 %100
75	118	X	-0.0003	-0.0003	0 %100

Member Distributed Loads (BLC 7 : 90 Wind - Service) (Continued)

Member Label	Direction	Start Magnitude [k/ft, F, ksf, k-ft/ft]	End Magnitude [k/ft, F, ksf, k-ft/ft]	Start Location [(ft, %)]	End Location [(ft, %)]
76	125	X	-0.0003	-0.0003	0 %100
77	127	X	-0.0003	-0.0003	0 %100
78	128	X	-0.0002	-0.0002	0 %100
79	129	X	-0.0002	-0.0002	0 %100
80	130	X	-0.0004	-0.0004	0 %100
81	131	X	-0.0003	-0.0003	0 %100
82	134	X	-0.0002	-0.0002	0 %100
83	136	X	-0.0003	-0.0003	0 %100
84	138	X	-0.0004	-0.0004	0 %100
85	140	X	-0.0004	-0.0004	0 %100
86	141	X	-0.0004	-0.0004	0 %100
87	147	X	-0.0002	-0.0002	0 %100
88	148	X	-0.0002	-0.0002	0 %100
89	158	X	-0.0004	-0.0004	0 %100
90	159	X	-0.0002	-0.0002	0 %100
91	160	X	-0.0002	-0.0002	0 %100
92	161	X	-0.0002	-0.0002	0 %100
93	162	X	-0.0002	-0.0002	0 %100
94	163	X	-0.0004	-0.0004	0 %100
95	164	X	-0.0002	-0.0002	0 %100
96	165	X	-0.0003	-0.0003	0 %100
97	166	X	-0.0002	-0.0002	0 %100
98	167	X	-0.0002	-0.0002	0 %100
99	168	X	-0.0002	-0.0002	0 %100
100	169	X	-0.0002	-0.0002	0 %100
101	170	X	-0.0003	-0.0003	0 %100
102	171	X	-0.0002	-0.0002	0 %100
103	172	X	-0.0002	-0.0002	0 %100
104	176	X	-0.0002	-0.0002	0 %100
105	177	X	-0.0002	-0.0002	0 %100
106	178	X	-0.0002	-0.0002	0 %100
107	179	X	-0.0002	-0.0002	0 %100
108	180	X	-0.0003	-0.0003	0 %100
109	181	X	-0.0003	-0.0003	0 %100
110	182	X	-0.0003	-0.0003	0 %100
111	184	X	-0.0003	-0.0003	0 %100
112	185	X	-0.0003	-0.0003	0 %100
113	192	X	-0.0003	-0.0003	0 %100
114	194	X	-0.0003	-0.0003	0 %100

Member Distributed Loads (BLC 8 : Ice)

Member Label	Direction	Start Magnitude [k/ft, F, ksf, k-ft/ft]	End Magnitude [k/ft, F, ksf, k-ft/ft]	Start Location [(ft, %)]	End Location [(ft, %)]
1	1	Y	-0.006	-0.006	0 %100
2	2	Y	-0.006	-0.006	0 %100
3	3	Y	-0.012	-0.012	0 %100
4	4	Y	-0.012	-0.012	0 %100
5	5	Y	-0.012	-0.012	0 %100
6	6	Y	-0.012	-0.012	0 %100
7	9	Y	-0.012	-0.012	0 %100
8	10	Y	-0.012	-0.012	0 %100
9	11	Y	-0.005	-0.005	0 %100
10	12	Y	-0.007	-0.007	0 %100
11	13	Y	-0.007	-0.007	0 %100
12	14	Y	-0.007	-0.007	0 %100
13	15	Y	-0.007	-0.007	0 %100

Member Distributed Loads (BLC 8 : Ice) (Continued)

Member Label	Direction	Start Magnitude [k/ft, F, ksf, k-ft/ft]	End Magnitude [k/ft, F, ksf, k-ft/ft]	Start Location [(ft, %)]	End Location [(ft, %)]
14	16	Y	-0.012	-0.012	0 %100
15	17	Y	-0.012	-0.012	0 %100
16	18	Y	-0.005	-0.005	0 %100
17	19	Y	-0.012	-0.012	0 %100
18	20	Y	-0.012	-0.012	0 %100
19	21	Y	-0.005	-0.005	0 %100
20	22	Y	-0.012	-0.012	0 %100
21	23	Y	-0.012	-0.012	0 %100
22	24	Y	-0.005	-0.005	0 %100
23	29	Y	-0.003	-0.003	0 %100
24	30	Y	-0.003	-0.003	0 %100
25	31	Y	-0.003	-0.003	0 %100
26	32	Y	-0.003	-0.003	0 %100
27	33	Y	-0.003	-0.003	0 %100
28	34	Y	-0.003	-0.003	0 %100
29	35	Y	-0.003	-0.003	0 %100
30	36	Y	-0.003	-0.003	0 %100
31	39	Y	-0.005	-0.005	0 %100
32	40	Y	-0.005	-0.005	0 %100
33	43	Y	-0.005	-0.005	0 %100
34	44	Y	-0.008	-0.008	0 %100
35	49	Y	-0.005	-0.005	0 %100
36	52	Y	-0.005	-0.005	0 %100
37	55	Y	-0.005	-0.005	0 %100
38	58	Y	-0.005	-0.005	0 %100
39	99	Y	-0.008	-0.008	0 %100
40	146	Y	-0.008	-0.008	0 %100
41	64	Y	-0.012	-0.012	0 %100
42	65	Y	-0.012	-0.012	0 %100
43	66	Y	-0.006	-0.006	0 %100
44	67	Y	-0.005	-0.005	0 %100
45	70	Y	-0.012	-0.012	0 %100
46	72	Y	-0.005	-0.005	0 %100
47	74	Y	-0.007	-0.007	0 %100
48	76	Y	-0.007	-0.007	0 %100
49	77	Y	-0.007	-0.007	0 %100
50	82	Y	-0.003	-0.003	0 %100
51	83	Y	-0.003	-0.003	0 %100
52	93	Y	-0.006	-0.006	0 %100
53	94	Y	-0.012	-0.012	0 %100
54	95	Y	-0.012	-0.012	0 %100
55	96	Y	-0.012	-0.012	0 %100
56	97	Y	-0.012	-0.012	0 %100
57	98	Y	-0.007	-0.007	0 %100
58	100	Y	-0.012	-0.012	0 %100
59	101	Y	-0.005	-0.005	0 %100
60	102	Y	-0.012	-0.012	0 %100
61	103	Y	-0.012	-0.012	0 %100
62	104	Y	-0.012	-0.012	0 %100
63	105	Y	-0.012	-0.012	0 %100
64	106	Y	-0.005	-0.005	0 %100
65	107	Y	-0.003	-0.003	0 %100
66	108	Y	-0.003	-0.003	0 %100
67	109	Y	-0.003	-0.003	0 %100
68	110	Y	-0.003	-0.003	0 %100

Member Distributed Loads (BLC 8 : Ice) (Continued)

Member Label	Direction	Start Magnitude [k/ft, F, ksf, k-ft/ft]	End Magnitude [k/ft, F, ksf, k-ft/ft]	Start Location [(ft, %)]	End Location [(ft, %)]
69	111	Y	-0.003	-0.003	0 %100
70	112	Y	-0.003	-0.003	0 %100
71	113	Y	-0.005	-0.005	0 %100
72	114	Y	-0.005	-0.005	0 %100
73	115	Y	-0.005	-0.005	0 %100
74	117	Y	-0.005	-0.005	0 %100
75	118	Y	-0.005	-0.005	0 %100
76	125	Y	-0.005	-0.005	0 %100
77	127	Y	-0.005	-0.005	0 %100
78	128	Y	-0.012	-0.012	0 %100
79	129	Y	-0.012	-0.012	0 %100
80	130	Y	-0.006	-0.006	0 %100
81	131	Y	-0.005	-0.005	0 %100
82	134	Y	-0.012	-0.012	0 %100
83	136	Y	-0.005	-0.005	0 %100
84	138	Y	-0.007	-0.007	0 %100
85	140	Y	-0.007	-0.007	0 %100
86	141	Y	-0.007	-0.007	0 %100
87	147	Y	-0.003	-0.003	0 %100
88	148	Y	-0.003	-0.003	0 %100
89	158	Y	-0.006	-0.006	0 %100
90	159	Y	-0.012	-0.012	0 %100
91	160	Y	-0.012	-0.012	0 %100
92	161	Y	-0.012	-0.012	0 %100
93	162	Y	-0.012	-0.012	0 %100
94	163	Y	-0.007	-0.007	0 %100
95	164	Y	-0.012	-0.012	0 %100
96	165	Y	-0.005	-0.005	0 %100
97	166	Y	-0.012	-0.012	0 %100
98	167	Y	-0.012	-0.012	0 %100
99	168	Y	-0.012	-0.012	0 %100
100	169	Y	-0.012	-0.012	0 %100
101	170	Y	-0.005	-0.005	0 %100
102	171	Y	-0.003	-0.003	0 %100
103	172	Y	-0.003	-0.003	0 %100
104	176	Y	-0.003	-0.003	0 %100
105	177	Y	-0.003	-0.003	0 %100
106	178	Y	-0.003	-0.003	0 %100
107	179	Y	-0.003	-0.003	0 %100
108	180	Y	-0.005	-0.005	0 %100
109	181	Y	-0.005	-0.005	0 %100
110	182	Y	-0.005	-0.005	0 %100
111	184	Y	-0.005	-0.005	0 %100
112	185	Y	-0.005	-0.005	0 %100
113	192	Y	-0.005	-0.005	0 %100
114	194	Y	-0.005	-0.005	0 %100

Member Distributed Loads (BLC 9 : 0 Seismic)

Member Label	Direction	Start Magnitude [k/ft, F, ksf, k-ft/ft]	End Magnitude [k/ft, F, ksf, k-ft/ft]	Start Location [(ft, %)]	End Location [(ft, %)]
1	1	Z	-0.002	-0.002	0 %100
2	2	Z	-0.002	-0.002	0 %100
3	3	Z	-0.002	-0.002	0 %100
4	4	Z	-0.002	-0.002	0 %100
5	5	Z	-0.002	-0.002	0 %100
6	6	Z	-0.002	-0.002	0 %100

Member Distributed Loads (BLC 9 : 0 Seismic) (Continued)

Member Label	Direction	Start Magnitude [k/ft, F, ksf, k-ft/ft]	End Magnitude [k/ft, F, ksf, k-ft/ft]	Start Location [(ft, %)]	End Location [(ft, %)]
7	9	Z	-0.002	-0.002	0 %100
8	10	Z	-0.002	-0.002	0 %100
9	11	Z	-0.001	-0.001	0 %100
10	12	Z	-0.004	-0.004	0 %100
11	13	Z	-0.004	-0.004	0 %100
12	14	Z	-0.004	-0.004	0 %100
13	15	Z	-0.004	-0.004	0 %100
14	16	Z	-0.002	-0.002	0 %100
15	17	Z	-0.002	-0.002	0 %100
16	18	Z	-0.001	-0.001	0 %100
17	19	Z	-0.002	-0.002	0 %100
18	20	Z	-0.002	-0.002	0 %100
19	21	Z	-0.001	-0.001	0 %100
20	22	Z	-0.002	-0.002	0 %100
21	23	Z	-0.002	-0.002	0 %100
22	24	Z	-0.001	-0.001	0 %100
23	29	Z	-0.0006	-0.0006	0 %100
24	30	Z	-0.0006	-0.0006	0 %100
25	31	Z	-0.0006	-0.0006	0 %100
26	32	Z	-0.0006	-0.0006	0 %100
27	33	Z	-0.0007	-0.0007	0 %100
28	34	Z	-0.0007	-0.0007	0 %100
29	35	Z	-0.0007	-0.0007	0 %100
30	36	Z	-0.0007	-0.0007	0 %100
31	39	Z	-0.001	-0.001	0 %100
32	40	Z	-0.001	-0.001	0 %100
33	43	Z	-0.001	-0.001	0 %100
34	44	Z	-0.003	-0.003	0 %100
35	49	Z	-0.001	-0.001	0 %100
36	52	Z	-0.001	-0.001	0 %100
37	55	Z	-0.001	-0.001	0 %100
38	58	Z	-0.001	-0.001	0 %100
39	99	Z	-0.003	-0.003	0 %100
40	146	Z	-0.003	-0.003	0 %100
41	64	Z	-0.002	-0.002	0 %100
42	65	Z	-0.002	-0.002	0 %100
43	66	Z	-0.002	-0.002	0 %100
44	67	Z	-0.001	-0.001	0 %100
45	70	Z	-0.002	-0.002	0 %100
46	72	Z	-0.001	-0.001	0 %100
47	74	Z	-0.004	-0.004	0 %100
48	76	Z	-0.004	-0.004	0 %100
49	77	Z	-0.004	-0.004	0 %100
50	82	Z	-0.0006	-0.0006	0 %100
51	83	Z	-0.0007	-0.0007	0 %100
52	93	Z	-0.002	-0.002	0 %100
53	94	Z	-0.002	-0.002	0 %100
54	95	Z	-0.002	-0.002	0 %100
55	96	Z	-0.002	-0.002	0 %100
56	97	Z	-0.002	-0.002	0 %100
57	98	Z	-0.004	-0.004	0 %100
58	100	Z	-0.002	-0.002	0 %100
59	101	Z	-0.001	-0.001	0 %100
60	102	Z	-0.002	-0.002	0 %100
61	103	Z	-0.002	-0.002	0 %100

Member Distributed Loads (BLC 9 : 0 Seismic) (Continued)

Member Label	Direction	Start Magnitude [k/ft, F, ksf, k-ft/ft]	End Magnitude [k/ft, F, ksf, k-ft/ft]	Start Location [(ft, %)]	End Location [(ft, %)]
62	104	Z	-0.002	-0.002	0 %100
63	105	Z	-0.002	-0.002	0 %100
64	106	Z	-0.001	-0.001	0 %100
65	107	Z	-0.0006	-0.0006	0 %100
66	108	Z	-0.0006	-0.0006	0 %100
67	109	Z	-0.0006	-0.0006	0 %100
68	110	Z	-0.0007	-0.0007	0 %100
69	111	Z	-0.0007	-0.0007	0 %100
70	112	Z	-0.0007	-0.0007	0 %100
71	113	Z	-0.001	-0.001	0 %100
72	114	Z	-0.001	-0.001	0 %100
73	115	Z	-0.001	-0.001	0 %100
74	117	Z	-0.001	-0.001	0 %100
75	118	Z	-0.001	-0.001	0 %100
76	125	Z	-0.001	-0.001	0 %100
77	127	Z	-0.001	-0.001	0 %100
78	128	Z	-0.002	-0.002	0 %100
79	129	Z	-0.002	-0.002	0 %100
80	130	Z	-0.002	-0.002	0 %100
81	131	Z	-0.001	-0.001	0 %100
82	134	Z	-0.002	-0.002	0 %100
83	136	Z	-0.001	-0.001	0 %100
84	138	Z	-0.004	-0.004	0 %100
85	140	Z	-0.004	-0.004	0 %100
86	141	Z	-0.004	-0.004	0 %100
87	147	Z	-0.0006	-0.0006	0 %100
88	148	Z	-0.0007	-0.0007	0 %100
89	158	Z	-0.002	-0.002	0 %100
90	159	Z	-0.002	-0.002	0 %100
91	160	Z	-0.002	-0.002	0 %100
92	161	Z	-0.002	-0.002	0 %100
93	162	Z	-0.002	-0.002	0 %100
94	163	Z	-0.004	-0.004	0 %100
95	164	Z	-0.002	-0.002	0 %100
96	165	Z	-0.001	-0.001	0 %100
97	166	Z	-0.002	-0.002	0 %100
98	167	Z	-0.002	-0.002	0 %100
99	168	Z	-0.002	-0.002	0 %100
100	169	Z	-0.002	-0.002	0 %100
101	170	Z	-0.001	-0.001	0 %100
102	171	Z	-0.0006	-0.0006	0 %100
103	172	Z	-0.0006	-0.0006	0 %100
104	176	Z	-0.0006	-0.0006	0 %100
105	177	Z	-0.0007	-0.0007	0 %100
106	178	Z	-0.0007	-0.0007	0 %100
107	179	Z	-0.0007	-0.0007	0 %100
108	180	Z	-0.001	-0.001	0 %100
109	181	Z	-0.001	-0.001	0 %100
110	182	Z	-0.001	-0.001	0 %100
111	184	Z	-0.001	-0.001	0 %100
112	185	Z	-0.001	-0.001	0 %100
113	192	Z	-0.001	-0.001	0 %100
114	194	Z	-0.001	-0.001	0 %100

Member Distributed Loads (BLC 10 : 90 Seismic)

Member Label	Direction	Start Magnitude [k/ft, F, ksf, k-ft/ft]	End Magnitude [k/ft, F, ksf, k-ft/ft]	Start Location [(ft, %)]	End Location [(ft, %)]
1	1	X	-0.002	-0.002	0 %100
2	2	X	-0.002	-0.002	0 %100
3	3	X	-0.002	-0.002	0 %100
4	4	X	-0.002	-0.002	0 %100
5	5	X	-0.002	-0.002	0 %100
6	6	X	-0.002	-0.002	0 %100
7	9	X	-0.002	-0.002	0 %100
8	10	X	-0.002	-0.002	0 %100
9	11	X	-0.001	-0.001	0 %100
10	12	X	-0.004	-0.004	0 %100
11	13	X	-0.004	-0.004	0 %100
12	14	X	-0.004	-0.004	0 %100
13	15	X	-0.004	-0.004	0 %100
14	16	X	-0.002	-0.002	0 %100
15	17	X	-0.002	-0.002	0 %100
16	18	X	-0.001	-0.001	0 %100
17	19	X	-0.002	-0.002	0 %100
18	20	X	-0.002	-0.002	0 %100
19	21	X	-0.001	-0.001	0 %100
20	22	X	-0.002	-0.002	0 %100
21	23	X	-0.002	-0.002	0 %100
22	24	X	-0.001	-0.001	0 %100
23	29	X	-0.0006	-0.0006	0 %100
24	30	X	-0.0006	-0.0006	0 %100
25	31	X	-0.0006	-0.0006	0 %100
26	32	X	-0.0006	-0.0006	0 %100
27	33	X	-0.0007	-0.0007	0 %100
28	34	X	-0.0007	-0.0007	0 %100
29	35	X	-0.0007	-0.0007	0 %100
30	36	X	-0.0007	-0.0007	0 %100
31	39	X	-0.001	-0.001	0 %100
32	40	X	-0.001	-0.001	0 %100
33	43	X	-0.001	-0.001	0 %100
34	44	X	-0.003	-0.003	0 %100
35	49	X	-0.001	-0.001	0 %100
36	52	X	-0.001	-0.001	0 %100
37	55	X	-0.001	-0.001	0 %100
38	58	X	-0.001	-0.001	0 %100
39	99	X	-0.003	-0.003	0 %100
40	146	X	-0.003	-0.003	0 %100
41	64	X	-0.002	-0.002	0 %100
42	65	X	-0.002	-0.002	0 %100
43	66	X	-0.002	-0.002	0 %100
44	67	X	-0.001	-0.001	0 %100
45	70	X	-0.002	-0.002	0 %100
46	72	X	-0.001	-0.001	0 %100
47	74	X	-0.004	-0.004	0 %100
48	76	X	-0.004	-0.004	0 %100
49	77	X	-0.004	-0.004	0 %100
50	82	X	-0.0006	-0.0006	0 %100
51	83	X	-0.0007	-0.0007	0 %100
52	93	X	-0.002	-0.002	0 %100
53	94	X	-0.002	-0.002	0 %100
54	95	X	-0.002	-0.002	0 %100
55	96	X	-0.002	-0.002	0 %100

Member Distributed Loads (BLC 10 : 90 Seismic) (Continued)

Member Label	Direction	Start Magnitude [k/ft, F, ksf, k-ft/ft]	End Magnitude [k/ft, F, ksf, k-ft/ft]	Start Location [(ft, %)]	End Location [(ft, %)]
56	97	X	-0.002	-0.002	0 %100
57	98	X	-0.004	-0.004	0 %100
58	100	X	-0.002	-0.002	0 %100
59	101	X	-0.001	-0.001	0 %100
60	102	X	-0.002	-0.002	0 %100
61	103	X	-0.002	-0.002	0 %100
62	104	X	-0.002	-0.002	0 %100
63	105	X	-0.002	-0.002	0 %100
64	106	X	-0.001	-0.001	0 %100
65	107	X	-0.0006	-0.0006	0 %100
66	108	X	-0.0006	-0.0006	0 %100
67	109	X	-0.0006	-0.0006	0 %100
68	110	X	-0.0007	-0.0007	0 %100
69	111	X	-0.0007	-0.0007	0 %100
70	112	X	-0.0007	-0.0007	0 %100
71	113	X	-0.001	-0.001	0 %100
72	114	X	-0.001	-0.001	0 %100
73	115	X	-0.001	-0.001	0 %100
74	117	X	-0.001	-0.001	0 %100
75	118	X	-0.001	-0.001	0 %100
76	125	X	-0.001	-0.001	0 %100
77	127	X	-0.001	-0.001	0 %100
78	128	X	-0.002	-0.002	0 %100
79	129	X	-0.002	-0.002	0 %100
80	130	X	-0.002	-0.002	0 %100
81	131	X	-0.001	-0.001	0 %100
82	134	X	-0.002	-0.002	0 %100
83	136	X	-0.001	-0.001	0 %100
84	138	X	-0.004	-0.004	0 %100
85	140	X	-0.004	-0.004	0 %100
86	141	X	-0.004	-0.004	0 %100
87	147	X	-0.0006	-0.0006	0 %100
88	148	X	-0.0007	-0.0007	0 %100
89	158	X	-0.002	-0.002	0 %100
90	159	X	-0.002	-0.002	0 %100
91	160	X	-0.002	-0.002	0 %100
92	161	X	-0.002	-0.002	0 %100
93	162	X	-0.002	-0.002	0 %100
94	163	X	-0.004	-0.004	0 %100
95	164	X	-0.002	-0.002	0 %100
96	165	X	-0.001	-0.001	0 %100
97	166	X	-0.002	-0.002	0 %100
98	167	X	-0.002	-0.002	0 %100
99	168	X	-0.002	-0.002	0 %100
100	169	X	-0.002	-0.002	0 %100
101	170	X	-0.001	-0.001	0 %100
102	171	X	-0.0006	-0.0006	0 %100
103	172	X	-0.0006	-0.0006	0 %100
104	176	X	-0.0006	-0.0006	0 %100
105	177	X	-0.0007	-0.0007	0 %100
106	178	X	-0.0007	-0.0007	0 %100
107	179	X	-0.0007	-0.0007	0 %100
108	180	X	-0.001	-0.001	0 %100
109	181	X	-0.001	-0.001	0 %100
110	182	X	-0.001	-0.001	0 %100

Member Distributed Loads (BLC 10 : 90 Seismic) (Continued)

Member Label		Direction	Start Magnitude [k/ft, F, ksf, k-ft/ft]	End Magnitude [k/ft, F, ksf, k-ft/ft]	Start Location [(ft, %)]	End Location [(ft, %)]
111	184	X	-0.001	-0.001	0	%100
112	185	X	-0.001	-0.001	0	%100
113	192	X	-0.001	-0.001	0	%100
114	194	X	-0.001	-0.001	0	%100

Member Area Loads

No Data to Print...

Node Loads and Enforced Displacements (BLC 11 : Live Load a)

Node Label		L, D, M	Direction	Magnitude [(k, k-ft), (in, rad), (k*s^2/ft, k*s^2*ft)]
1	48	L	Y	-0.5
2	149	L	Y	-0.5
3	245	L	Y	-0.5

Node Loads and Enforced Displacements (BLC 12 : Live Load b)

Node Label		L, D, M	Direction	Magnitude [(k, k-ft), (in, rad), (k*s^2/ft, k*s^2*ft)]
1	66	L	Y	-0.5
2	203	L	Y	-0.5
3	307	L	Y	-0.5

Node Loads and Enforced Displacements (BLC 13 : Live Load c)

Node Label		L, D, M	Direction	Magnitude [(k, k-ft), (in, rad), (k*s^2/ft, k*s^2*ft)]
1	73	L	Y	-0.5
2	183	L	Y	-0.5
3	287	L	Y	-0.5

Basic Load Cases

BLC Description		Category	Y Gravity	Nodal	Point	Distributed
1	Dead	DL	-1		75	
2	0 Wind - No Ice	WLZ			75	114
3	90 Wind - No Ice	WLX			75	114
4	0 Wind - Ice	WLZ			75	114
5	90 Wind - Ice	WLX			75	114
6	0 Wind - Service	WLZ			75	114
7	90 Wind - Service	WLX			75	114
8	Ice	OL1			75	114
9	0 Seismic	ELZ			75	114
10	90 Seismic	ELX			75	114
11	Live Load a	LL	3			
12	Live Load b	LL	3			
13	Live Load c	LL	3			
14	Live Load d	LL				
15	Maint LL 1	LL			1	
16	Maint LL 2	LL			1	
17	Maint LL 3	LL			1	
18	Maint LL 4	LL			1	
19	Maint LL 5	LL			1	
20	Maint LL 6	LL			1	
21	Maint LL 7	LL			1	
22	Maint LL 8	LL			1	

Basic Load Cases (Continued)

	BLC Description	Category	Y Gravity	Nodal	Point	Distributed
23	Maint LL 9	LL			1	
24	Maint LL 10	LL			1	
25	Maint LL 11	LL			1	
26	Maint LL 12	LL			1	
27	Maint LL 13	LL				
28	Maint LL 14	LL				
29	Maint LL 15	LL				

Load Combinations

	Description	Solve	P-Delta	BLC	Factor	BLC	Factor	BLC	Factor	BLC	Factor
1	1.4 Dead	Yes	Y	1	1.4						
2	1.2 D + 1.0 - 0 W	Yes	Y	1	1.2	2	1				
3	1.2 D + 1.0 - 30 W	Yes	Y	1	1.2	2	0.866	3	0.5		
4	1.2 D + 1.0 - 60 W	Yes	Y	1	1.2	3	0.866	2	0.5		
5	1.2 D + 1.0 - 90 W	Yes	Y	1	1.2	3	1				
6	1.2 D + 1.0 - 120 W	Yes	Y	1	1.2	3	0.866	2	-0.5		
7	1.2 D + 1.0 - 150 W	Yes	Y	1	1.2	2	-0.866	3	0.5		
8	1.2 D + 1.0 - 180 W	Yes	Y	1	1.2	2	-1				
9	1.2 D + 1.0 - 210 W	Yes	Y	1	1.2	2	-0.866	3	-0.5		
10	1.2 D + 1.0 - 240 W	Yes	Y	1	1.2	3	-0.866	2	-0.5		
11	1.2 D + 1.0 - 270 W	Yes	Y	1	1.2	3	-1				
12	1.2 D + 1.0 - 300 W	Yes	Y	1	1.2	3	-0.866	2	0.5		
13	1.2 D + 1.0 - 330 W	Yes	Y	1	1.2	2	0.866	3	-0.5		
14	1.2 D + 1.0 - 0 W/Ice	Yes	Y	1	1.2	4	1			8	1
15	1.2 D + 1.0 - 30 W/Ice	Yes	Y	1	1.2	4	0.866	5	0.5	8	1
16	1.2 D + 1.0 - 60 W/Ice	Yes	Y	1	1.2	5	0.866	4	0.5	8	1
17	1.2 D + 1.0 - 90 W/Ice	Yes	Y	1	1.2	5	1			8	1
18	1.2 D + 1.0 - 120 W/Ice	Yes	Y	1	1.2	5	0.866	4	-0.5	8	1
19	1.2 D + 1.0 - 150 W/Ice	Yes	Y	1	1.2	4	-0.866	5	0.5	8	1
20	1.2 D + 1.0 - 180 W/Ice	Yes	Y	1	1.2	4	-1			8	1
21	1.2 D + 1.0 - 210 W/Ice	Yes	Y	1	1.2	4	-0.866	5	-0.5	8	1
22	1.2 D + 1.0 - 240 W/Ice	Yes	Y	1	1.2	5	-0.866	4	-0.5	8	1
23	1.2 D + 1.0 - 270 W/Ice	Yes	Y	1	1.2	5	-1			8	1
24	1.2 D + 1.0 - 300 W/Ice	Yes	Y	1	1.2	5	-0.866	4	0.5	8	1
25	1.2 D + 1.0 - 330 W/Ice	Yes	Y	1	1.2	4	0.866	5	-0.5	8	1
26	1.2 D + 1.0 E - 0	Yes	Y	1	1.2	9	1				
27	1.2 D + 1.0 E - 30	Yes	Y	1	1.2	9	0.866	10	0.5		
28	1.2 D + 1.0 E - 60	Yes	Y	1	1.2	10	0.866	9	0.5		
29	1.2 D + 1.0 E - 90	Yes	Y	1	1.2	10	1				
30	1.2 D + 1.0 E - 120	Yes	Y	1	1.2	10	0.866	9	-0.5		
31	1.2 D + 1.0 E - 150	Yes	Y	1	1.2	9	-0.866	10	0.5		
32	1.2 D + 1.0 E - 180	Yes	Y	1	1.2	9	-1				
33	1.2 D + 1.0 E - 210	Yes	Y	1	1.2	9	-0.866	10	-0.5		
34	1.2 D + 1.0 E - 240	Yes	Y	1	1.2	10	-0.866	9	-0.5		
35	1.2 D + 1.0 E - 270	Yes	Y	1	1.2	10	-1				
36	1.2 D + 1.0 E - 300	Yes	Y	1	1.2	10	-0.866	9	0.5		
37	1.2 D + 1.0 E - 330	Yes	Y	1	1.2	9	0.866	10	-0.5		
38	1.2 D + 1.5 LL a + Service - 0 W	Yes	Y	1	1.2	6	1			11	1.5
39	1.2 D + 1.5 LL a + Service - 30 W	Yes	Y	1	1.2	6	0.866	7	0.5	11	1.5
40	1.2 D + 1.5 LL a + Service - 60 W	Yes	Y	1	1.2	7	0.866	6	0.5	11	1.5
41	1.2 D + 1.5 LL a + Service - 90 W	Yes	Y	1	1.2	7	1			11	1.5
42	1.2 D + 1.5 LL a + Service - 120 W	Yes	Y	1	1.2	7	0.866	6	-0.5	11	1.5
43	1.2 D + 1.5 LL a + Service - 150 W	Yes	Y	1	1.2	6	-0.866	7	0.5	11	1.5
44	1.2 D + 1.5 LL a + Service - 180 W	Yes	Y	1	1.2	6	-1			11	1.5
45	1.2 D + 1.5 LL a + Service - 210 W	Yes	Y	1	1.2	6	-0.866	7	-0.5	11	1.5

Load Combinations (Continued)

	Description	Solve	P-Delta	BLC	Factor	BLC	Factor	BLC	Factor	BLC	Factor
46	1.2 D + 1.5 LL a + Service - 240 W	Yes	Y	1	1.2	7	-0.866	6	-0.5	11	1.5
47	1.2 D + 1.5 LL a + Service - 270 W	Yes	Y	1	1.2	7	-1			11	1.5
48	1.2 D + 1.5 LL a + Service - 300 W	Yes	Y	1	1.2	7	-0.866	6	0.5	11	1.5
49	1.2 D + 1.5 LL a + Service - 330 W	Yes	Y	1	1.2	6	0.866	7	-0.5	11	1.5
50	1.2 D + 1.5 LL b + Service - 0 W	Yes	Y	1	1.2	6	1			12	1.5
51	1.2 D + 1.5 LL b + Service - 30 W	Yes	Y	1	1.2	6	0.866	7	0.5	12	1.5
52	1.2 D + 1.5 LL b + Service - 60 W	Yes	Y	1	1.2	7	0.866	6	0.5	12	1.5
53	1.2 D + 1.5 LL b + Service - 90 W	Yes	Y	1	1.2	7	1			12	1.5
54	1.2 D + 1.5 LL b + Service - 120 W	Yes	Y	1	1.2	7	0.866	6	-0.5	12	1.5
55	1.2 D + 1.5 LL b + Service - 150 W	Yes	Y	1	1.2	6	-0.866	7	0.5	12	1.5
56	1.2 D + 1.5 LL b + Service - 180 W	Yes	Y	1	1.2	6	-1			12	1.5
57	1.2 D + 1.5 LL b + Service - 210 W	Yes	Y	1	1.2	6	-0.866	7	-0.5	12	1.5
58	1.2 D + 1.5 LL b + Service - 240 W	Yes	Y	1	1.2	7	-0.866	6	-0.5	12	1.5
59	1.2 D + 1.5 LL b + Service - 270 W	Yes	Y	1	1.2	7	-1			12	1.5
60	1.2 D + 1.5 LL b + Service - 300 W	Yes	Y	1	1.2	7	-0.866	6	0.5	12	1.5
61	1.2 D + 1.5 LL b + Service - 330 W	Yes	Y	1	1.2	6	0.866	7	-0.5	12	1.5
62	1.2 D + 1.5 LL c + Service - 0 W	Yes	Y	1	1.2	6	1			13	1.5
63	1.2 D + 1.5 LL c + Service - 30 W	Yes	Y	1	1.2	6	0.866	7	0.5	13	1.5
64	1.2 D + 1.5 LL c + Service - 60 W	Yes	Y	1	1.2	7	0.866	6	0.5	13	1.5
65	1.2 D + 1.5 LL c + Service - 90 W	Yes	Y	1	1.2	7	1			13	1.5
66	1.2 D + 1.5 LL c + Service - 120 W	Yes	Y	1	1.2	7	0.866	6	-0.5	13	1.5
67	1.2 D + 1.5 LL c + Service - 150 W	Yes	Y	1	1.2	6	-0.866	7	0.5	13	1.5
68	1.2 D + 1.5 LL c + Service - 180 W	Yes	Y	1	1.2	6	-1			13	1.5
69	1.2 D + 1.5 LL c + Service - 210 W	Yes	Y	1	1.2	6	-0.866	7	-0.5	13	1.5
70	1.2 D + 1.5 LL c + Service - 240 W	Yes	Y	1	1.2	7	-0.866	6	-0.5	13	1.5
71	1.2 D + 1.5 LL c + Service - 270 W	Yes	Y	1	1.2	7	-1			13	1.5
72	1.2 D + 1.5 LL c + Service - 300 W	Yes	Y	1	1.2	7	-0.866	6	0.5	13	1.5
73	1.2 D + 1.5 LL c + Service - 330 W	Yes	Y	1	1.2	6	0.866	7	-0.5	13	1.5
74	1.2 D + 1.5 LL d + Service - 0 W	Yes	Y	1	1.2	6	1			14	1.5
75	1.2 D + 1.5 LL d + Service - 30 W	Yes	Y	1	1.2	6	0.866	7	0.5	14	1.5
76	1.2 D + 1.5 LL d + Service - 60 W	Yes	Y	1	1.2	7	0.866	6	0.5	14	1.5
77	1.2 D + 1.5 LL d + Service - 90 W	Yes	Y	1	1.2	7	1			14	1.5
78	1.2 D + 1.5 LL d + Service - 120 W	Yes	Y	1	1.2	7	0.866	6	-0.5	14	1.5
79	1.2 D + 1.5 LL d + Service - 150 W	Yes	Y	1	1.2	6	-0.866	7	0.5	14	1.5
80	1.2 D + 1.5 LL d + Service - 180 W	Yes	Y	1	1.2	6	-1			14	1.5
81	1.2 D + 1.5 LL d + Service - 210 W	Yes	Y	1	1.2	6	-0.866	7	-0.5	14	1.5
82	1.2 D + 1.5 LL d + Service - 240 W	Yes	Y	1	1.2	7	-0.866	6	-0.5	14	1.5
83	1.2 D + 1.5 LL d + Service - 270 W	Yes	Y	1	1.2	7	-1			14	1.5
84	1.2 D + 1.5 LL d + Service - 300 W	Yes	Y	1	1.2	7	-0.866	6	0.5	14	1.5
85	1.2 D + 1.5 LL d + Service - 330 W	Yes	Y	1	1.2	6	0.866	7	-0.5	14	1.5
86	1.2 D + 1.5 LL Maint (1)	Yes	Y	1	1.2					15	1.5
87	1.2 D + 1.5 LL Maint (2)	Yes	Y	1	1.2					16	1.5
88	1.2 D + 1.5 LL Maint (3)	Yes	Y	1	1.2					17	1.5
89	1.2 D + 1.5 LL Maint (4)	Yes	Y	1	1.2					18	1.5
90	1.2 D + 1.5 LL Maint (5)	Yes	Y	1	1.2					19	1.5
91	1.2 D + 1.5 LL Maint (6)	Yes	Y	1	1.2					20	1.5
92	1.2 D + 1.5 LL Maint (7)	Yes	Y	1	1.2					21	1.5
93	1.2 D + 1.5 LL Maint (8)	Yes	Y	1	1.2					22	1.5
94	1.2 D + 1.5 LL Maint (9)	Yes	Y	1	1.2					23	1.5
95	1.2 D + 1.5 LL Maint (10)	Yes	Y	1	1.2					24	1.5
96	1.2 D + 1.5 LL Maint (11)	Yes	Y	1	1.2					25	1.5
97	1.2 D + 1.5 LL Maint (12)	Yes	Y	1	1.2					26	1.5
98	1.2 D + 1.5 LL Maint (13)	Yes	Y	1	1.2					27	1.5
99	1.2 D + 1.5 LL Maint (14)	Yes	Y	1	1.2					28	1.5
100	1.2 D + 1.5 LL Maint (15)	Yes	Y	1	1.2					29	1.5



Company : MTS Engineering, P.L.L.C.
Designer : GRG
Job Number : 136918.010.01
Model Name : 825983 - Middletown_1

5/24/2022
7:53:15 PM
Checked By : _____

Load Combinations (Continued)

Description	Solve	P-Delta	BLC	Factor	BLC	Factor	BLC	Factor	BLC	Factor
-------------	-------	---------	-----	--------	-----	--------	-----	--------	-----	--------

Envelope Node Reactions

Node Label	X [k]	LC	Y [k]	LC	Z [k]	LC	MX [k-ft]	LC	MY [k-ft]	LC	MZ [k-ft]	LC
1 61	max 1.51	41	1.686	14	2.52	14	0.226	2	2.565	5	0.438	12
2	min -0.499	11	0.655	8	0.165	8	-0.442	8	-1.773	11	-0.687	6
3 62	max 2.309	5	1.705	22	0.1	3	0.056	9	3.074	5	1.217	6
4	min -3.041	11	0.69	4	-1.829	21	-0.711	15	-3.901	11	-1.567	12
5 130	max 1.777	17	1.699	17	0.025	2	0.516	3	2.942	9	0.584	10
6	min -0.125	11	0.687	11	-2.187	44	-0.635	9	-2.123	3	-0.263	4
7 154	max 1.278	3	1.755	25	4.407	2	1.661	9	4.302	9	1.256	3
8	min -2.513	9	0.727	7	-3.089	8	-1.678	3	-5.069	3	-0.776	9
9 234	max -0.297	5	1.651	21	0.694	2	0.778	2	2.927	13	0.353	12
10	min -2.601	23	0.687	3	-1.152	8	-0.466	8	-2.124	7	-0.423	6
11 250	max 3.648	7	1.723	18	2.893	13	1.836	8	4.286	13	1.221	7
12	min -1.689	13	0.662	13	-2.672	7	-1.306	2	-5.108	7	-1.339	13
13 Totals:	max 7.596	5	10.073	25	9.807	2						
14	min -7.596	11	4.75	7	-9.807	8						

Envelope AISC 15TH (360-16): LRFD Member Steel Code Checks

Member	Shape	Code Check Loc [ft]	Loc [ft]	LC	Shear Check Loc [ft]	Loc [ft]	Dir L	Cphi * Pnc [k]	Pnt [k]	phi * Mn y-y [k-ft]	phi * Mn z-z [k-ft]	Cb	Eqn
1 31	5/8"SR	0.6	0	14	0.017	3.333	7	1.88	9.94	0.104	0.104	1	H1-1a
2 39	PIPE 2.0	0.57	3.5	2	0.107	3.609	8	8.922	32.13	1.872	1.872	1	H1-1b
3 113	PIPE 2.0	0.57	3.5	2	0.076	3.609	13	8.922	32.13	1.872	1.872	1	H1-1b
4 180	PIPE 2.0	0.57	3.5	8	0.086	3.609	9	8.922	32.13	1.872	1.872	1	H1-1b
5 147	5/8"SR	0.557	0	21	0.022	3.333	2	1.88	9.94	0.104	0.104	1	H1-1a
6 82	5/8"SR	0.528	0	19	0.017	3.333	10	1.88	9.94	0.104	0.104	1	H1-1a
7 32	5/8"SR	0.515	0	16	0.01	3.333	45	1.88	9.94	0.104	0.104	1	H1-1a
8 52	PIPE 2.0	0.503	3.5	8	0.072	3.609	6	8.922	32.13	1.872	1.872	1	H1-1b
9 192	PIPE 2.0	0.503	3.5	2	0.088	3.609	2	8.922	32.13	1.872	1.872	1	H1-1b
10 125	PIPE 2.0	0.503	3.5	2	0.084	3.609	9	8.922	32.13	1.872	1.872	1	H1-1b
11 109	5/8"SR	0.5	0	21	0.01	3.333	38	1.88	9.94	0.104	0.104	1	H1-1a
12 176	5/8"SR	0.49	0	25	0.01	3.333	41	1.88	9.94	0.104	0.104	1	H1-1a
13 49	PIPE 2.0	0.444	3.609	8	0.077	3.609	7	8.922	32.13	1.872	1.872	1	H1-1b
14 6	PL5/8X3.5	0.406	0.458	13	0.142	0.458	y 44	67.491	70.875	0.923	5.168	2.599	H1-1b
15 29	5/8"SR	0.389	1.667	2	0.016	3.333	6	1.88	9.94	0.104	0.104	1	H1-1a
16 19	PL5/8X3.5	0.377	0.08	13	0.322	0	y 13	70.768	70.875	0.923	5.168	1.033	H1-1b
17 1	PIPE_2.875X0.276"	0.376	3.927	8	0.109	3.927	8	14.358	85.184	5.895	5.895	1	H1-1b
18 22	PL5/8X3.5	0.348	0.08	44	0.23	0	y 9	70.768	70.875	0.923	5.168	1.048	H1-1b
19 104	PL5/8X3.5	0.329	0.08	13	0.088	0	y 6	70.768	70.875	0.923	5.168	1.022	H1-1b
20 146	HSS4.500X0.237	0.318	1.021	7	0.432	1.021	7	106.372	133.2	15.113	15.113	1	H3-6
21 158	PIPE_2.875X0.276"	0.311	3.927	3	0.121	3.927	3	14.358	85.184	5.895	5.895	1	H1-1b
22 99	HSS4.500X0.237	0.306	1.021	3	0.424	1.021	3	106.372	133.2	15.113	15.113	1	H3-6
23 5	PL5/8X3.5	0.306	0.458	9	0.151	0.458	y 41	67.491	70.875	0.923	5.168	2.482	H1-1b
24 102	PL5/8X3.5	0.299	0.08	4	0.076	0	y 11	70.768	70.875	0.923	5.168	1.058	H1-1b
25 107	5/8"SR	0.298	3.333	7	0.017	3.333	9	1.88	9.94	0.104	0.104	1	H1-1a
26 96	PL5/8X3.5	0.294	0.239	8	0.308	0.458	y 4	67.491	70.875	0.923	5.168	2.661	H1-1b
27 21	PIPE 2.0	0.284	0.182	2	0.204	0.156	2	29.81	32.13	1.872	1.872	1	H1-1b
28 24	PIPE 2.0	0.282	0.182	45	0.185	0.156	21	29.81	32.13	1.872	1.872	1	H1-1b
29 127	PIPE 2.0	0.274	3.5	2	0.059	3.609	47	8.922	32.13	1.872	1.872	1	H1-1b
30 194	PIPE 2.0	0.274	3.5	8	0.079	3.609	2	8.922	32.13	1.872	1.872	1	H1-1b
31 159	PL5/8X3.5	0.269	0.239	8	0.292	0.458	y 7	67.491	70.875	0.923	5.168	3	H1-1b
32 140	PL1.25"X3.5"	0.261	0	20	0.054	0.458	y 8	140.027	141.75	3.691	10.336	1.58	H1-1b
33 16	PL5/8X3.5	0.258	0.08	8	0.202	0	y 7	70.768	70.875	0.923	5.168	1.038	H1-1b
34 70	PL5/8X3.5	0.257	0.239	44	0.265	0.458	y 13	67.491	70.875	0.923	5.168	2.577	H1-1b
35 106	PIPE 2.0	0.247	0.156	13	0.136	2.5	48	29.81	32.13	1.872	1.872	1	H1-1b
36 4	PL5/8X3.5	0.244	0.458	8	0.083	0.239	y 46	67.491	70.875	0.923	5.168	2.484	H1-1b
37 76	PL1.25"X3.5"	0.243	0	15	0.038	0	y 14	140.027	141.75	3.691	10.336	1.57	H1-1b

Envelope AISC 15TH (360-16): LRFD Member Steel Code Checks (Continued)

Member	Shape	Code Check Loc[ft]	LC Shear Check Loc[ft]	DirLcphi*Pnc [k]	phi*Mn y-y [k-ft]	phi*Mn z-z [k-ft]	Cb	Eqn
38	3	PL5/8X3.5	0.24	0.239	12 0.149 0.458 y 6 67.491	70.875 0.923	5.168	2.803 H1-1b
39	66	PIPE 2.875X0.276"	0.238	4.682	39 0.055 4.833 y 2 14.358	85.184 5.895	5.895	5.895 1 H1-1b
40	2	PIPE 2.875X0.276"	0.236	4.682	49 0.053 5.135 y 7 14.358	85.184 5.895	5.895	5.895 1 H1-1b
41	130	PIPE 2.875X0.276"	0.236	4.833	43 0.059 4.833 y 4 14.358	85.184 5.895	5.895	5.895 1 H1-1b
42	93	PIPE 2.875X0.276"	0.235	3.927	12 0.075 9.667 y 7 14.358	85.184 5.895	5.895	5.895 1 H1-1b
43	13	PL1.25"X3.5"	0.233	0	24 0.044 0.458 y 13 140.027	141.75 3.691	10.336	1.53 H1-1b
44	128	PL5/8X3.5	0.23	0.08	3 0.055 0 y 11 70.768	70.875 0.923	5.168	1.043 H1-1b
45	161	PL5/8X3.5	0.229	0.239	9 0.209 0.458 y 12 67.491	70.875 0.923	5.168	5.168 3 H1-1b
46	134	PL5/8X3.5	0.221	0.239	4 0.2 0.458 y 38 67.491	70.875 0.923	5.168	2.56 H1-1b
47	165	PIPE 2.0	0.207	2.5	8 0.101 2.5 y 19 29.81	32.13 1.872	1.872	1.872 1 H1-1b
48	129	PL5/8X3.5	0.205	0	13 0.108 0 y 6 70.768	70.875 0.923	5.168	1.173 H1-1b
49	44	HSS4.500X0.237	0.204	1.021	11 0.326 1.021 y 11 106.372	133.2 15.113	15.113	1 H3-6
50	67	PIPE 2.0	0.203	0.182	5 0.158 2.5 y 40 29.81	32.13 1.872	1.872	1 H1-1b
51	141	PL1.25"X3.5"	0.203	0	21 0.053 0 y 22 140.027	141.75 3.691	10.336	1.599 H1-1b
52	94	PL5/8X3.5	0.202	0.239	13 0.241 0.458 y 4 67.491	70.875 0.923	5.168	2.759 H1-1b
53	18	PIPE 2.0	0.199	0.156	8 0.156 0.156 y 8 29.81	32.13 1.872	1.872	1 H1-1b
54	77	PL1.25"X3.5"	0.199	0	17 0.044 0 y 19 140.027	141.75 3.691	10.336	1.675 H1-1b
55	35	SR 3/4"	0.195	0	47 0.019 0 y 8 1.542	14.314 0.179	0.179	0.179 1 H1-1b*
56	15	PL1.25"X3.5"	0.194	0	14 0.041 0.458 y 17 140.027	141.75 3.691	10.336	1.754 H1-1b
57	83	SR 3/4"	0.188	0	38 0.007 3.976 y 47 1.542	14.314 0.179	0.179	0.179 1 H1-1b*
58	131	PIPE 2.0	0.187	0.182	9 0.153 2.5 y 44 29.81	32.13 1.872	1.872	1 H1-1b
59	148	SR 3/4"	0.185	0	43 0.014 3.976 y 38 1.542	14.314 0.179	0.179	0.179 1 H1-1b*
60	170	PIPE 2.0	0.182	2.5	8 0.227 0.156 y 39 29.81	32.13 1.872	1.872	1 H1-1b
61	9	PL5/8X3.5	0.18	0.08	3 0.148 0 y 2 70.768	70.875 0.923	5.168	1.064 H1-1b
62	171	5/8"SR	0.179	0	9 0.02 3.333 y 2 1.88	9.94 0.104	0.104	0.104 1 H1-1b*
63	169	PL5/8X3.5	0.166	0.08	49 0.057 0.08 z 43 70.768	70.875 0.923	5.168	1.024 H1-1b
64	105	PL5/8X3.5	0.166	0.08	44 0.12 0.08 y 49 70.768	70.875 0.923	5.168	1.031 H1-1b
65	166	PL5/8X3.5	0.164	0.08	8 0.157 0 y 12 70.768	70.875 0.923	5.168	1.053 H1-1b
66	95	PL5/8X3.5	0.164	0.239	6 0.08 0.458 y 44 67.491	70.875 0.923	5.168	2.521 H1-1b
67	11	PIPE 2.0	0.164	0.156	2 0.149 0.156 y 2 29.81	32.13 1.872	1.872	1 H1-1b
68	167	PL5/8X3.5	0.155	0.08	8 0.071 0.08 z 44 70.768	70.875 0.923	5.168	1.01 H1-1b
69	101	PIPE 2.0	0.155	2.5	4 0.11 0.156 y 73 29.81	32.13 1.872	1.872	1 H1-1b
70	23	PL5/8X3.5	0.147	0.08	17 0.094 0.002 y 38 70.768	70.875 0.923	5.168	1.029 H1-1b
71	72	PIPE 2.0	0.139	1.25	3 0.12 0.156 y 5 29.81	32.13 1.872	1.872	1 H1-1b
72	138	PL1.25"X3.5"	0.137	0.458	2 0.037 0.458 y 2 140.027	141.75 3.691	10.336	1.442 H1-1b
73	74	PL1.25"X3.5"	0.135	0.458	10 0.036 0.458 y 9 140.027	141.75 3.691	10.336	1.566 H1-1b
74	65	PL5/8X3.5	0.134	0	10 0.154 0.08 y 4 70.768	70.875 0.923	5.168	1.017 H1-1b
75	136	PIPE 2.0	0.133	1.25	7 0.077 0.156 y 8 29.81	32.13 1.872	1.872	1 H1-1b
76	181	PIPE 2.0	0.132	6.251	9 0.079 6.251 y 45 20.112	32.13 1.872	1.872	1 H1-1b*
77	103	PL5/8X3.5	0.131	0.08	39 0.124 0.08 y 5 70.768	70.875 0.923	5.168	1.014 H1-1b
78	160	PL5/8X3.5	0.131	0.458	3 0.185 0.458 y 3 67.491	70.875 0.923	5.168	2.503 H1-1b
79	20	PL5/8X3.5	0.129	0.08	13 0.074 0.08 z 46 70.768	70.875 0.923	5.168	1.019 H1-1b
80	12	PL1.25"X3.5"	0.12	0.458	7 0.034 0.458 y 6 140.027	141.75 3.691	10.336	1.436 H1-1b
81	168	PL5/8X3.5	0.117	0.08	6 0.265 0.08 y 38 70.768	70.875 0.923	5.168	1.031 H1-1b
82	98	PL1.25"X3.5"	0.117	0.458	66 0.031 0 y 14 140.027	141.75 3.691	10.336	1.572 H1-1b
83	40	PIPE 2.0	0.116	6.251	13 0.078 6.251 y 38 20.112	32.13 1.872	1.872	1 H1-1b*
84	164	PL5/8X3.5	0.116	0.08	8 0.1 0.001 y 42 70.768	70.875 0.923	5.168	1.024 H1-1b
85	163	PL1.25"X3.5"	0.114	0.458	71 0.03 0.458 y 19 140.027	141.75 3.691	10.336	1.596 H1-1b
86	14	PL1.25"X3.5"	0.114	0.458	62 0.031 0 y 22 140.027	141.75 3.691	10.336	1.632 H1-1b
87	17	PL5/8X3.5	0.102	0	13 0.107 0.08 y 45 70.768	70.875 0.923	5.168	1.024 H1-1b
88	64	PL5/8X3.5	0.094	0.08	12 0.111 0.001 y 62 70.768	70.875 0.923	5.168	1.041 H1-1b
89	162	PL5/8X3.5	0.093	0.08	2 0.095 0.08 y 45 70.768	70.875 0.923	5.168	1.016 H1-1b
90	117	PIPE 2.0	0.092	1.312	5 0.054 4.625 y 10 20.867	32.13 1.872	1.872	1 H1-1b
91	55	PIPE 2.0	0.092	1.312	11 0.055 4.625 y 6 20.867	32.13 1.872	1.872	1 H1-1b
92	184	PIPE 2.0	0.092	1.312	5 0.068 1.375 y 2 20.867	32.13 1.872	1.872	1 H1-1b

Envelope AISC 15TH (360-16): LRFD Member Steel Code Checks (Continued)

Member	Shape	Code Check Loc[ft]	LC Shear Check Loc[ft]	DirLc	phi*iPnc [k]	phi*Mn y-y [k-ft]	phi*Mn z-z [k-ft]	Cb	Eqn
93 118	PIPE 2.0	0.088	1.312	5	0.058	4.625	10	20.867	32.13
94 108	5/8"SR	0.086	0	15	0.011	0	38	1.88	9.94
95 172	5/8"SR	0.084	0	20	0.011	0	43	1.88	9.94
96 100	PL5/8X3.5	0.082	0	4	0.1	0.08	y 2	70.768	70.875
97 30	5/8"SR	0.081	0	24	0.011	0	45	1.88	9.94
98 97	PL5/8X3.5	0.079	0.08	8	0.103	0.08	y 38	70.768	70.875
99 58	PIPE 2.0	0.075	3.312	9	0.067	4.625	7	20.867	32.13
100 114	PIPE 2.0	0.075	6.251	5	0.074	6.251	42	20.112	32.13
101 185	PIPE 2.0	0.073	4.625	3	0.076	4.625	2	20.867	32.13
102 10	PL5/8X3.5	0.072	0.08	6	0.069	0.001	y 39	70.768	70.875
103 177	SR 3/4"	0.067	0	45	0.01	3.976	38	1.542	14.314
104 115	PIPE 2.0	0.063	6.27	8	0.026	6.27	8	20.053	32.13
105 33	SR 3/4"	0.061	3.976	68	0.011	3.976	39	1.542	14.314
106 110	SR 3/4"	0.06	3.976	71	0.009	0	45	1.542	14.314
107 182	PIPE 2.0	0.05	3.135	13	0.014	6.27	12	20.053	32.13
108 43	PIPE 2.0	0.045	3.135	5	0.026	6.27	9	20.053	32.13
109 34	SR 3/4"	0.008	3.976	7	0.012	3.976	7	1.542	14.314
110 179	SR 3/4"	0	3.976	100	0.013	3.976	13	1.542	14.314
111 112	SR 3/4"	0	3.976	100	0.012	3.976	10	1.542	14.314
112 36	SR 3/4"	0	3.976	100	0.012	0	3	1.542	14.314
113 178	SR 3/4"	0	3.976	100	0.011	0	13	1.542	14.314
114 111	SR 3/4"	0	3.976	100	0.01	0	9	1.542	14.314

APPENDIX D
ADDITIONAL CALCULATIONS

PROJECT	136918.010.01 - Middletown_1, CT	KSC
SUBJECT	Sector Mount Analysis	
DATE	05/24/22	PAGE 1 OF 1



B+T Group
1717 S. Boulder, Suite 300
Tulsa, OK 74119
(918) 587-4630

[REF: AISC 360-05]

Reactions at Bolted Connection

Tension	:	4.41	k
Vertical Shear	:	1.755	k
Horizontal Shear	:	2.51	k
Torsion	:	1.253	k.ft
Moment from Horizontal Forces	:	5.068	k.ft
Moment from Vertical Forces	:	1.679	k.ft

Bolt Parameters

Bolt Grade	:	A325	
Bolt Diameter	:	0.625	in
Nominal Bolt Area	:	0.307	in ²
Bolt spacing, Horizontal	:	6	in
Bolt spacing, Vertical	:	6	in
Bolt edge distance, plate height	:	1.5	in
Bolt edge distance, plate width	:	1.5	in
Total Number of Bolts	:	4	bolts


Summary of Forces

Shear Resultant Force	:	3.06	k
Force from Horz. Moment	:	9.18	k
Force from Vert. Moment	:	3.04	k
Shear Load / Bolt	:	0.77	k
Tension Load / Bolt	:	1.10	k
Resultant from Moments / Bolt	:	4.84	k

Bolt Checks

Nominal Tensile Stress, F_{nt}	:	90.00	ksi	[AISC Table J3.2]
Available Tensile Stress, ΦR_{nt}	:	20.72	k/bolt	[Eq. J3-1]
Unity Check, Bolt Tension	:	28.65%		OKAY
Nominal Shear Stress, F_{nv}	:	48.00	ksi	[AISC Table J3.2]
Available Shear Stress, ΦR_{nv}	:	11.05	k/bolt	[Eq. J3-1]
Unity Check, Bolt Shear	:	16.90%		OKAY
Unity Check, Combined	:	45.56%		OKAY
Available Bearing Strength, ΦR_n	:	34.66	k/bolt	
Unity Check, Bolt Bearing	:	2.21%		OKAY


APPENDIX E
SUPPLEMENTAL DRAWINGS



PARTS LIST							
ITEM	QTY	PART NO.	PART DESCRIPTION	LENGTH	UNIT WT.	NET WT.	
1	2	X-VFAW	SUPPORT ARM		71.41	142.81	
2	2	X-HDPMW	HEAVY DUTY PIPE MOUNT WELDMENT		18.61	37.21	
3	2	X-HDPMBP	HEAVY DUTY PIPE MOUNT BACKING PLATE	12 in	13.44	26.89	
4	2	X-VFAPL3	VFA-HD PIVOT PLATE	24 in	9.69	19.38	
5	1	X-LPB	LOWER PIVOT BRACKET		8.84	8.84	
6	1	X-UPB	UPPER PIVOT BRACKET		8.84	8.84	
7	4	X-SPTB	SLIDING PIPE TIE BACK PLATE	5 1/2 in	5.87	23.49	
8	4	X-TBCA	TIE BACK CLIP ANGLE		2.01	8.02	
9	8	SCX2	CROSSOVER PLATE	7 in	4.80	38.37	
10	4	MCP	CLAMP HALF 1/2" THICK, 11-5/8" LONG	12 1/16 in	3.59	14.37	
11	8	DCP	1/2" THICK, 5-3/4" CNTER TO CENTER CLAMP HALF	8 1/8 in	2.42	19.36	
13	2	P2126	2-3/8" X 126" (2" SCH. 40) GALVANIZED PIPE	126 in	40.75	81.50	
12	2	P30174	2-7/8" O.D. x 174" SCH. 40 PIPE	174 in	84.20	168.39	
14	6	A34212	3/4" x 2-1/2" UNC HEX BOLT (A325)	2 1/2 in	0.48	2.87	
15	6	G34LW	3/4" HDG LOCKWASHER		0.04	0.26	
16	6	G34NUT	3/4" HDG HEAVY 2H HEX NUT		0.21	1.27	
19	8	G58R-18	5/8" x 18" THREADED ROD (HDG.)	18 in	0.40	3.19	
20	4	G58R-12	5/8" x 12" THREADED ROD (HDG.)		1.05	4.18	
21	8	G58R-8	5/8" x 8" THREADED ROD (HDG.)		0.70	5.58	
17	4	X-UB5300	5/8" X 3" X 5-1/4" X 2-1/2" U-BOLT (HDG.)		1.15	4.60	
18	8	X-UB5258	5/8" X 2-5/8" X 4-1/2" X 2" U-BOLT (HDG.)		1.00	8.00	
23	8	A582114	5/8" x 2-1/4" HDG A325 HEX BOLT	2 1/4 in	0.31	2.50	
22	8	G5804	5/8" x 4" HDG HEX BOLT GR5		0.44	3.55	
24	4	G5802	5/8" x 2" HDG HEX BOLT GR5		0.27	1.08	
25	20	G58FW	5/8" HDG USS FLATWASHER	1/8 in	0.07	1.41	
26	66	G58LW	5/8" HDG LOCKWASHER		0.03	1.72	
27	70	G58NUT	5/8" HDG HEAVY 2H HEX NUT		0.13	9.09	
28	32	X-UB1300	1/2" X 3" X 5" X 2" GALV U-BOLT		0.74	23.64	
29	16	X-UB1212	1/2" X 2-1/2" X 4-1/2" X 2" U-BOLT (HDG.)		0.63	10.00	
30	64	G12FW	1/2" HDG USS FLATWASHER	3/32 in	0.03	2.18	
31	64	G12LW	1/2" HDG LOCKWASHER	1/8 in	0.01	0.89	
32	64	G12NUT	1/2" HDG HEAVY 2H HEX NUT		0.07	4.58	
							TOTAL WT. # 700.78

				TOLERANCE NOTES		DESCRIPTION			Locations:				
				TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE: SAWN, SHEARED AND GAS CUT EDGES ($\pm 0.030"$) DRILLED AND GAS CUT HOLES ($\pm 0.030"$) - NO CONING OF HOLES LASER CUT EDGES AND HOLES ($\pm 0.010"$) - NO CONING OF HOLES BENDS ARE $\pm 1/2$ DEGREE		14' 6" HEAVY DUTY V-FRAME ASSEMBLY WITH TWO STIFF ARMS			New York, NY Atlanta, GA Los Angeles, CA Plymouth, IN Salem, OR Dallas, TX				
				ALL OTHER MACHINING ($\pm 0.030"$) ALL OTHER ASSEMBLY ($\pm 0.060"$)		CPD NO.	DRAWN BY		Engineering Support Team: 1-888-753-7446				
				CEK 7/31/2017		CEK 1/25/2017			A valmont  COMPANY				
B	CHANGED TIE-BACK BACK CONNECTION			CEK 7/31/2017		ENG. APPROVAL			PART NO.				
A	CHANGED TIE-BACK FRONT CONNECTION			CEK 2/2/2017					VFA14-HD				
REV	DESCRIPTION OF REVISIONS			CPD	BY	DATE	CLASS	SUB	DRAWING USAGE	CHECKED BY	DWG. NO.		
REVISION HISTORY				81		02	CUSTOMER		BMC 8/4/2017		VFA14-HD		

TIE-BACK POSITIONS



TOLERANCE NOTES

TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE:
 SAWED, SHEARED AND GAS CUT EDGES ($\pm 0.030"$)
 DRILLED AND GAS CUT HOLES ($\pm 0.030"$) - NO CONING OF HOLES
 LASER CUT EDGES AND HOLES ($\pm 0.010"$) - NO CONING OF HOLES
 BENDS ARE $\pm 1/2$ DEGREE
 ALL OTHER MACHINING ($\pm 0.030"$)
 ALL OTHER ASSEMBLY ($\pm 0.060"$)

DESCRIPTION

14' 6" HEAVY DUTY
V-FRAME ASSEMBLY
WITH TWO STIFF ARMS

CPD NO.

DRAWN BY
CEK 1/25/2017

ENG. APPROVAL

PART NO.

VFA14-HD



Engineering
Support Team:
1-888-753-7446
Locations:
New York, NY
Atlanta, GA
Los Angeles, CA
Plymouth, IN
Salem, OR
Dallas, TX




B	CHANGED TIE-BACK BACK CONNECTION	CEK	7/31/2017
A	CHANGED TIE-BACK FRONT CONNECTION	CEK	2/2/2017
REV	DESCRIPTION OF REVISIONS	CPD	BY DATE

PROPRIETARY NOTE:
THE DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT INDUSTRIES AND CONSIDERED A TRADE SECRET. ANY USE OR DISCLOSURE WITHOUT THE CONSENT OF VALMONT INDUSTRIES IS STRICTLY PROHIBITED.

CLASS 81 SUB 02 DRAWING USAGE CUSTOMER CHECKED BY BMC 8/4/2017



DWG. NO.

VFA14-HD



NOTES:

1. USE HOLE "A" IN UPPER AND LOWER BRACKETS FOR STRAIGHT LEGS.
2. USE HOLE "A" IN UPPER BRACKET AND HOLE "C" IN LOWER BRACKET FOR 2" IN 20' TAPER LEGS (3.309")
3. USE HOLE "B" IN UPPER BRACKET AND HOLE "C" IN LOWER BRACKET FOR 6" IN 20' TAPER LEGS. (0.827")



TOLERANCE NOTES

TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE:
SAWED, SHEARED AND GAS CUT EDGES ($\pm 0.030"$)
DRILLED AND GAS CUT HOLES ($\pm 0.030"$) - NO CONING OF HOLES
LASER CUT EDGES AND HOLES ($\pm 0.010"$) - NO CONING OF HOLES
BENDS ARE $\pm 1/2$ DEGREE
ALL OTHER MACHINING ($\pm 0.030"$)
ALL OTHER ASSEMBLY ($\pm 0.060"$)

PROPRIETARY NOTE:
 THE DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT INDUSTRIES AND CONSIDERED A TRADE SECRET. ANY USE OR DISCLOSURE WITHOUT THE CONSENT OF VALMONT INDUSTRIES IS STRICTLY PROHIBITED.

DESCRIPTION

**14' 6" HEAVY DUTY
V-FRAME ASSEMBLY
WITH TWO STIFF ARMS**

CPD NO.

DRAWN BY

CEK

1/25/2017

ENG. APPROVAL

PART NO.

VFA14-HD



Engineering
Support Team:
1-888-753-7446
Locations:
New York, NY
Atlanta, GA
Los Angeles, CA
Plymouth, IN
Salem, OR
Dallas, TX


B	CHANGED TIE-BACK BACK CONNECTION	CEK	7/31/2017
A	CHANGED TIE-BACK FRONT CONNECTION	CEK	2/2/2017
REV	DESCRIPTION OF REVISIONS	CPD	BY DATE

REVISION HISTORY

CLASS	SUB	DRAWING USAGE	CHECKED BY
81	02	CUSTOMER	BMC 8/4/2017

DWG. NO.

VFA14-HD




			TOLERANCE NOTES			DESCRIPTION					
			TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE: SAWED, SHEARED AND GAS CUT EDGES ($\pm 0.030"$) DRILLED AND GAS CUT HOLES ($\pm 0.030"$) - NO CONING OF HOLES LASER CUT EDGES AND HOLES ($\pm 0.010"$) - NO CONING OF HOLES BENDS ARE $\pm 1/2$ DEGREE ALL OTHER MACHINING ($\pm 0.030"$) ALL OTHER ASSEMBLY ($\pm 0.060"$)						14' 6" HEAVY DUTY V-FRAME ASSEMBLY WITH TWO STIFF ARMS		
B	CHANGED TIE-BACK BACK CONNECTION	CEK	7/31/2017	CPD NO.	DRAWN BY	ENG. APPROVAL	PART NO.	VFA14-HD			
A	CHANGED TIE-BACK FRONT CONNECTION	CEK	2/2/2017	CLASS	SUB	DRAWING USAGE	CHECKED BY				
REV	DESCRIPTION OF REVISIONS	CPD	BY	DATE				DWG. NO.	VFA14-HD		
	REVISION HISTORY										

PROPRIETARY NOTE:
THE DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT INDUSTRIES AND CONSIDERED A TRADE SECRET. ANY USE OR DISCLOSURE WITHOUT THE CONSENT OF VALMONT INDUSTRIES IS STRICTLY PROHIBITED.




Engineering Support Team:
1-888-753-7446
A valmont company

Locations:
New York, NY
Atlanta, GA
Los Angeles, CA
Plymouth, IN
Salem, OR
Dallas, TX



UNISTRUT AND HARDWARE
SOLD SEPARATELY.

REQUIRES 3/8" HARDWARE



EQUIPMENT PIPE AND HARDWARE
SOLD SEPARATELY.


REQUIRES 1/2" HARDWARE
AND 2-3/8" TO 4-1/2" O.D. PIPE

				TOLERANCE NOTES		DESCRIPTION						
				TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE: SAWED, SHEARED AND GAS CUT EDGES ($\pm 0.030"$) DRILLED AND GAS CUT HOLES ($\pm 0.030"$) - NO CONING OF HOLES LASER CUT EDGES AND HOLES ($\pm 0.010"$) - NO CONING OF HOLES BENDS ARE $\pm 1/2$ DEGREE ALL OTHER MACHINING ($\pm 0.030"$) ALL OTHER ASSEMBLY ($\pm 0.060"$)		14' 6" HEAVY DUTY V-FRAME ASSEMBLY WITH TWO STIFF ARMS			CPD NO.	DRAWN BY	ENG. APPROVAL	PART NO.
B	CHANGED TIE-BACK BACK CONNECTION	CEK	7/31/2017						CEK	1/25/2017		SITE PRO
A	CHANGED TIE-BACK FRONT CONNECTION	CEK	2/2/2017									Engineering Support Team: 1-888-753-7446
REV	DESCRIPTION OF REVISIONS	CPD	BY	DATE	PROPRIETARY NOTE: THE DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT INDUSTRIES AND CONSIDERED A TRADE SECRET. ANY USE OR DISCLOSURE WITHOUT THE CONSENT OF VALMONT INDUSTRIES IS STRICTLY PROHIBITED.	CLASS	SUB	DRAWING USAGE	CHECKED BY	DWG. NO.	VFA14-HD	Locations: New York, NY Atlanta, GA Los Angeles, CA Plymouth, IN Salem, OR Dallas, TX
	REVISION HISTORY					81	02	CUSTOMER	BMC	8/4/2017	VFA14-HD	PAGE 5




NOTE:

SEE DRAWING C10112377 FOR INSTALLATION OF TRI-COLLAR BRACKET ASSEMBLY



ISOMETRIC VIEW

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS INCLUDE FINISHES AND ARE IN INCHES	MATERIAL:
TOLERANCES: FRACTIONS $\pm 1/16$ " ANGLES $\pm 1/2$ DEG. DECIMALS $\pm .010$ "	TOLERANCES DO NOT APPLY TO RAW MATERIAL
1 02/03/17 WRF KLE COLLAR WAS C10112300	
REV DATE DRW CHK	DESCRIPTION



VIEW A-A




CONFIDENTIAL
 This document and the information contained herein is the confidential trade secret property of Sabre Communications Corporation ("Sabre") and must not be reproduced, copied or used, in whole or in part, for any purpose without the prior written consent of Sabre.
 © 2016 Sabre Communications Corporation.
 All rights reserved.

C10899050 4 1/2" O.D. PIPE MOUNT ASSEMBLY

ITEM	QTY.	PART NO.	DESCRIPTION	WEIGHT
1.	2	C10112377	TRI-COLLAR BRACKET ASSEMBLY	416
2.	3	C10901407	PIPE, 4 1/2 O.D. X .237 X 7'-0	236
3.	12	C40034032	U-BOLT ASSEMBLY, 5/8 ϕ X 5 3/16 C-C	26
TOTAL WEIGHT				678

A →

A →



PLAN VIEW


4 1/2" O.D. PIPE MOUNT ASSEMBLY
 FOR MONOPOLIES
 (FITS 10" TO 40" DIAMETER)

SIZE	DRAWING NO.	REV
B	C10899050	1
DATE	01/26/16	
DRAWN BY	WRF	
CHECKED BY	DLW	
	SCALE None	PAGE 1 OF 1



C10112377 TRI-COLLAR ASSEMBLY (10"-40" MONPOLE)

ITEM	QTY.	PART. NO.	DESCRIPTION	WEIGHT
1.	3	CW01324	WELDMENT, TRI-COLLAR (10"-40" MONPOLE)	166
2.	6	C40094012	THREADED ROD ASSEMBLY 5/8 X 2'-9"	25
3.	6	C40094002	THREADED ROD ASSEMBLY 5/8 X 1'-6"	17
TOTAL WEIGHT				208



ISOMETRIC VIEW

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS INCLUDE
FINISHES AND ARE IN INCHES
TOLERANCES: FRACTIONS $\pm 1/16"$
ANGLES $\pm 1/2$ DEG.
DECIMALS $\pm .010"$

MATERIAL:
TOLERANCES DO NOT APPLY
TO RAW MATERIAL

REV	DATE	DRW	CHK	DESCRIPTION



CONFIDENTIAL

This document and the information contained herein is the confidential trade secret property of Sabre Communications Corporation ("Sabre") and must not be reproduced, copied or used, in whole or in part, for any purpose without the prior written consent of Sabre.
© 2016 Sabre Communications Corporation.
All rights reserved.

TRI-COLLAR BRACKET ASSEMBLY
FOR MONPOLES (10"-40" DIA.)
(CIRCUMFERENCE 31.4" TO 125.7")

SIZE	DRAWING NO.	REV
B	C10112377	0
	SCALE	PAGE
	None	1 OF 1



QC CHECK

PREWELD _____



WELD _____

MAG _____

SWO NO. _____

PROJECT _____

QUANTITY _____

ISO VIEW

FINISH: HOT DIP GALV. PER ASTM A123 OR EQUAL.

LIST OF MATERIAL

ITEM	QTY.	PART. NO.	DESCRIPTION	WEIGHT
1.	1	CWS01831	PLATE, COLLAR MOUNTING	20.5#
2.	2	CWS01832	PLATE, COLLAR BEARING	32.6#
				TOTAL WEIGHT BLACK 53.1#
				TOTAL WEIGHT GALV. 55.2#

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS INCLUDE FINISHES AND ARE IN INCHES	MATERIAL:
TOLERANCES: FRACTIONS \pm 1/16" ANGLES \pm 1/2 DEG. DECIMALS \pm .010"	TOLERANCES DO NOT APPLY TO RAW MATERIAL

REV	DATE	DRW	CHK	DESCRIPTION



WELDMENT, TRI-COLLAR
(10"-40" MONOPOLE)

CONFIDENTIAL
This document and the information contained herein is the confidential trade secret property of Sabre Communications Corporation ("Sabre") and must not be reproduced, copied or used, in whole or in part, for any purpose without the prior written consent of Sabre.
© 2016 Sabre Communications Corporation.
All rights reserved.

SIZE	DRAWING NO.	REV
B	CW01324	0
	SCALE	PAGE
	None	1 OF 1



SWO NO. _____
PROJECT _____
QUANTITY _____



FORMED VIEW

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS INCLUDE FINISHES AND ARE IN INCHES	MATERIAL: PLATE, 3/8 X 11 1/2 X 2'-0 3/4 ASTM A572 GR 65 OR EQUAL
TOLERANCES: FRACTIONS \pm 1/16" ANGLES \pm 1/2 DEG. READING TO .005"	TOLERANCES DO NOT APPLY TO THIS DRAWING

CONFIDENTIAL

This document and the information contained herein is the confidential trade secret property of Sabre Communications Corporation ("Sabre") and must not be reproduced, copied or used, in whole or in part, for any purpose without the prior written consent of Sabre.

© 2016 Sabre Communications Corporation.
All rights reserved.

NOTES:


1. ALL SHADED HOLES ARE 11/16"Ø (4 REQ'D)
 2. ALL SLOTTED HOLES ARE 11/16" X 1 3/4"
SLOTS (4 REQ'D)
 3. ALL UNSHADED HOLES ARE 4"Ø (3 REQ'D)
 4. MATERIAL CUT LENGTH MAY VARY DUE TO SHOP
PROCEDURES
 5. BLACK STEEL WEIGHT = 20.5#

PLATE, COLLAR MOUNTING


		SIZE B	DRAWING NO. CWS01831		REV 0
DATE 04/15/16	DRAWN BY WRF			SCALE None	
CHECKED BY KLE					PAGE 1 OF 1



SWO NO. _____
 PROJECT _____
 QUANTITY _____



FORMED VIEW



FLAT LAYOUT

NOTES:

- ALL HOLES ARE 11/16"Ø (2 REQ'D)
- MATERIAL CUT LENGTH MAY VARY DUE TO SHOP PROCEDURES
- BLACK STEEL WEIGHT = 16.3#

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS INCLUDE FINISHES AND ARE IN INCHES MATERIAL: PLATE, $3/8 \times 10\frac{1}{2} \times 1'-3$ ASTM A572 GR 65 OR EQUAL TOLERANCES: FRACTIONS $\pm 1/16"$ ANGLES $\pm 1/2$ DEG. DECIMALS $\pm .010"$ TOLERANCES DO NOT APPLY TO RAW MATERIAL				Sabre Industries™ Towers and Poles CONFIDENTIAL This document and the information contained herein is the confidential trade secret property of Sabre Communications Corporation ("Sabre") and must not be reproduced, copied or used, in whole or in part, for any purpose without the prior written consent of Sabre. © 2016 Sabre Communications Corporation. All rights reserved.				PLATE, COLLAR BEARING			
								SIZE B			
				DRAWING NO. CWS01832				REV 0			
								DATE 04/15/16			
				DRAWN BY WRF							
				CHECKED BY KLE				SCALE None			
								PAGE 1 OF 1			



4 1/2"
O.D.

ITEM #	DESCRIPTION	BLACK WEIGHT	APPROX GALV WT
C10901401	4 1/2" O.D. X .237 X 1'-0	10.8#	11.2#
C10901402	4 1/2" O.D. X .237 X 2'-0	21.6#	22.4#
C10901403	4 1/2" O.D. X .237 X 3'-0	32.4#	33.7#
C10901404	4 1/2" O.D. X .237 X 4'-0	43.2#	44.9#
C10901405	4 1/2" O.D. X .237 X 5'-3	56.6#	58.9#
C10901406	4 1/2" O.D. X .237 X 6'-0	64.8#	67.3#
C10901407	4 1/2" O.D. X .237 X 7'-0	75.5#	78.6#
C10901408	4 1/2" O.D. X .237 X 8'-6	91.7#	95.4#
C10901409	4 1/2" O.D. X .237 X 9'-0	97.1#	101.0#
C10901410	4 1/2" O.D. X .237 X 10'-6	113.3#	117.8#
C10901411	4 1/2" O.D. X .237 X 11'-0	118.7#	123.4#
C10901412	4 1/2" O.D. X .237 X 12'-0	129.5#	134.7#
C10901413	4 1/2" O.D. X .237 X 13'-0	140.3#	145.9#
C10901414	4 1/2" O.D. X .237 X 14'-0	151.1#	157.1#
C10901415	4 1/2" O.D. X .237 X 15'-0	161.9#	168.3#
C10901416	4 1/2" O.D. X .237 X 16'-0	172.6#	179.5#
C10901417	4 1/2" O.D. X .237 X 17'-0	183.4#	190.8#
C10901418	4 1/2" O.D. X .237 X 18'-0	194.2#	202.0#
C10901419	4 1/2" O.D. X .237 X 19'-0	205.0#	213.2#
C10901420	4 1/2" O.D. X .237 X 20'-0	215.8#	224.4#
C10901421	4 1/2" O.D. X .237 X 21'-0	226.6#	235.7#
C10901422	4 1/2" O.D. X .237 X 5'-0	54.0#	56.1#
C10901423	4 1/2" O.D. X .237 X 12'-6	134.9#	140.3#
C10901424	4 1/2" O.D. X .237 X 28'-0	302.1#	314.2#
C10901425	4 1/2" O.D. X .237 X 10'-0	107.9#	112.2#
C10901426	4 1/2" O.D. X .237 X 8'-0	86.3#	89.8#
C10901427	4 1/2" O.D. X .237 X 26'-0	280.5#	291.7#
C10901428			
C10901429			
C10901430			

ITEM #	DESCRIPTION	BLACK WEIGHT	APPROX GALV WT
C10901457	4 1/2" O.D. X .337 X 7'-0	104.9#	109.1#
C10901458	4 1/2" O.D. X .337 X 21'-0	314.6#	327.2#

FINISH: HOT DIP GALV. PER ASTM A123

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS INCLUDE FINISHES AND ARE IN INCHES	MATERIAL: PIPE 4 1/2 O.D. X SEE CHARTS ABOVE ASTM A53 GRADE B OR EQUAL
TOLERANCES: FRACTIONS \pm 1/16"	TOLERANCES DO NOT APPLY
ANGLES \pm 1/2 DEG.	TO RAW MATERIAL
DECIMALS \pm .010"	
10 12/16/14 KLE EK ADDED C10901427	
9 6/10/13 KLE EK ADDED C109011458	
8 6/14/07 KLE EK ADDED C109011425 & C10901426	
7 2/15/06 MLC MC REVISED TO "B" SIZE & ADDED .218 WALL PIPE	
6 7/28/05 KLE DLW REVISED MATERIAL DESCRIPTION (WAS Fy = 50 ksi)	
5 5/17/04 KLE DLW ADDED MATERIAL GRADE NOTE	
4 4/29/03 CHHZAK ADDED C109011424	
3 4/3/02 KLE DLW ADDED C109011423	
2 3/26/02 KLE DLW ADDED C10901422	
1 10/2/00 KLE BCT ADDED WALL THICKNESS	
REV DATE DRW CHK	DESCRIPTION



CONFIDENTIAL
This document and the information contained herein is the confidential trade secret property of Sabre Communications Corporation ("Sabre") and must not be reproduced, copied or used, in whole or in part, for any purpose without the prior written consent of Sabre.
© 2006 Sabre Communications Corporation.
All rights reserved.

4 1/2" O.D. PLAIN PIPE CUT LIST
.237" & .337" WALL

DATE	5/9/00	SIZE	DRAWING NO.	REV
DRAWN BY	KLE	B	C109014	10
CHECKED BY	BCT		SCALE	PAGE
			None	1 OF 1



MORRISON HERSHFIELD

Date: July 20, 2022

Morrison Hershfield
1455 Lincoln Parkway, Suite 500
Atlanta, GA 30346
(770) 379-8500

Subject:	Structural Analysis Report	
Carrier Designation:	AT&T Mobility Co-Locate	
Site Number:	CTL01044	
Site Name:	Cromwell East	
Site FA Number:	10035130	
Crown Castle Designation:	BU Number:	825983
	Site Name:	Middletown_1
	JDE Job Number:	716731
	Work Order Number:	2112605
	Order Number:	616581 Rev. 0
Engineering Firm Designation:	Morrison Hershfield Project Number: CN9-327R4 / 2200039	
Site Data:	90 Industrial Park Road, Middletown, Middlesex County, CT 06457 Latitude 41° 35' 8.3", Longitude -72° 42' 50.49" 185 Foot – Fred A. Nudd Monopole Tower	

Morrison Hershfield is pleased to submit this “**Structural Analysis Report**” to determine the structural integrity of the above-mentioned tower.

The purpose of the analysis is to determine acceptability of the tower stress level. Based on our analysis we have determined the tower stress level for the structure and foundation, under the following load case, to be:

LC7: Proposed Equipment Configuration

Sufficient Capacity – 88.5%

This analysis has been performed in accordance with the 2022 Connecticut State Building Code and the 2021 International Building Code based upon an ultimate 3-second gust wind speed of 120 mph. Applicable Standard references and design criteria are listed in Section 2 - Analysis Criteria.

Respectfully submitted by:

G. Lance Cooke, P.E. (CT License No. 28133)
Senior Engineer



TABLE OF CONTENTS

1) INTRODUCTION

2) ANALYSIS CRITERIA

Table 1 - Proposed Equipment Configuration
Table 2 - Other Considered Equipment

3) ANALYSIS PROCEDURE

Table 3 - Documents Provided
3.1) Analysis Method
3.2) Assumptions

4) ANALYSIS RESULTS

Table 4 - Section Capacity (Summary)
Table 5 – Tower Component Stresses vs. Capacity – LC7
4.1) Recommendations

5) APPENDIX A

tnxTower Output

6) APPENDIX B

Base Level Drawing

7) APPENDIX C

Additional Calculations

1) INTRODUCTION

This tower is a 185 ft Monopole tower designed by Fred A. Nudd Corporation.

The tower was modified multiple times in the past to accommodate additional loading.

2) ANALYSIS CRITERIA

TIA-222 Revision:	TIA-222-H
Risk Category:	II
Wind Speed:	120 mph
Exposure Category:	C
Topographic Factor:	1
Ice Thickness:	1 in
Wind Speed with Ice:	50 mph
Service Wind Speed:	60 mph

Table 1 - Proposed Equipment Configuration

Mounting Level (ft)	Center Line Elevation (ft)	Number of Antennas	Antenna Manufacturer	Antenna Model	Number of Feed Lines	Feed Line Size (in)
174.0	174.0	176.0	3	ericsson	AIR 6419 B77G	12 1 2 2
		3	cci antennas	DMP65R-BU6D	1-1/4	
		3	quintel technology	QD6616-7	7/8	
		3	ericsson	RRUS 32 B66A	13/16	
		3	ericsson	RRUS 4415 B25_CCIV2	3/8	
		3	ericsson	RRUS 4449 B5/B12		
		3	ericsson	RRUS 4478 B14_CCIV2		
		3	ericsson	RRUS E2 B29		
		3	ericsson	RRUS-32 B30		
		2	raycap	DC6-48-60-18-8F		
		1	raycap	DC9-48-60-24-8C-EV		
		3	-	Site Pro 1 VFA14-WLL-30120		
	172.0	3	ericsson	Sabre C10899050		
	172.0	3	ericsson	AIR 6449 B77D		

Table 2 - Other Considered Equipment

Mounting Level (ft)	Center Line Elevation (ft)	Number of Antennas	Antenna Manufacturer	Antenna Model	Number of Feed Lines	Feed Line Size (in)
183.0	183.0	3	ericsson	AIR6449 B41_T-MOBILE	4	1-5/8
		3	rfs celwave	APXVAARR24_43-U-NA20		
		3	ericsson	RADIO 4449 B12/B71		
		3	ericsson	RADIO 4460 B2/B25 B66_TMO		
		1	-	Site Pro 1 RMQP-496-HK		
165.0	165.0	3	jma wireless	MX08FRO665-20 w/ Mount Pipe	1	1-3/4
		3	fujitsu	TA08025-B604		
		3	fujitsu	TA08025-B605		
		1	raycap	RDIDC-9181-PF-48		
		1	-	Commscope MC-PK8-DSH		

Mounting Level (ft)	Center Line Elevation (ft)	Number of Antennas	Antenna Manufacturer	Antenna Model	Number of Feed Lines	Feed Line Size (in)
155.0	155.0	6	andrew	SBNHH-1D65B	2	1-5/8
		3	andrew	SBNHH-1D65B w/ Mount Pipe		
		3	samsung telecommunications	MT6407-77A		
		3	samsung telecommunications	RFV01U-D1A		
		3	samsung telecommunications	RFV01U-D2A		
		2	rfs celwave	DB-T1-6Z-8AB-0Z		
		3	-	Commscope BSAMNT-SBS-1-2		
		1	-	Platform Mount [LP 403-1]		

3) ANALYSIS PROCEDURE

Table 3 - Documents Provided

Document	Reference	Source
4-GEOTECHNICAL REPORTS	3473514	CCISITES
4-TOWER FOUNDATION DRAWINGS/DESIGN/SPECS	3880469	CCISITES
4-TOWER MANUFACTURER DRAWINGS	3473517	CCISITES
4-TOWER REINFORCEMENT DESIGN/DRAWINGS/DATA	3879955	CCISITES
4-POST-MODIFICATION INSPECTION	3945944	CCISITES
4-TOWER REINFORCEMENT DESIGN/DRAWINGS/DATA	3990532	CCISITES
4-POST-MODIFICATION INSPECTION	5512978	CCISITES
4-TOWER REINFORCEMENT DESIGN/DRAWINGS/DATA	3954032	CCISITES
4-POST-MODIFICATION INSPECTION	5650784	CCISITES

3.1) Analysis Method

tnxTower (version 8.1.1.0), a commercially available analysis software package, was used to create a three-dimensional model of the tower and calculate member stresses for various loading cases. Selected output from the analysis is included in Appendix A. When applicable, Crown Castle has calculated and provided the effective area for panel antennas using approved methods following the intent of the TIA-222 standard.

tnxTower was used to determine the loads on the modified structure. Additional calculations were performed to determine the stresses in the pole and in the reinforcing elements. These calculations are presented in Appendix C.

3.2) Assumptions

- 1) Tower and structures were maintained in accordance with the TIA-222 Standard.
- 2) The configuration of antennas, transmission cables, mounts and other appurtenances are as specified in Tables 1 and 2 and the referenced drawings.

This analysis may be affected if any assumptions are not valid or have been made in error. Morrison Hershfield should be notified to determine the effect on the structural integrity of the tower.

4) ANALYSIS RESULTS

Table 4 - Section Capacity (Summary)

Section No.	Elevation (ft)	Component Type	Size	Critical Element	% Capacity	Pass / Fail
L1	185 - 180	Pole	TP18x18x0.1875	Pole	9.5%	Pass
L2	180 - 175	Pole	TP19.631x18x0.25	Pole	15.1%	Pass
L3	175 - 170	Pole	TP21.263x19.631x0.25	Pole	32.2%	Pass
L4	170 - 165	Pole	TP22.894x21.263x0.25	Pole	45.8%	Pass
L5	165 - 160	Pole	TP24.525x22.894x0.25	Pole	61.1%	Pass
L6	160 - 155	Pole	TP26.156x24.525x0.25	Pole	73.4%	Pass
L7	155 - 154	Pole	TP26.483x26.156x0.25	Pole	76.2%	Pass
L8	154 - 153.75	Pole + Reinf.	TP26.564x26.483x0.3688	Reinf. 8 Tension Rupture	59.3%	Pass
L9	153.75 - 152.5	Pole + Reinf.	TP26.972x26.564x0.3625	Reinf. 8 Tension Rupture	61.9%	Pass
L10	152.5 - 152.25	Pole + Reinf.	TP27.053x26.972x0.55	Reinf. 8 Tension Rupture	42.4%	Pass
L11	152.25 - 151.5	Pole + Reinf.	TP27.298x27.053x0.55	Reinf. 8 Tension Rupture	43.5%	Pass
L12	151.5 - 151.25	Pole + Reinf.	TP27.38x27.298x0.425	Reinf. 3 Tension Rupture	53.3%	Pass
L13	151.25 - 146.25	Pole + Reinf.	TP29.011x27.38x0.4125	Reinf. 3 Tension Rupture	61.1%	Pass
L14	146.25 - 141.25	Pole + Reinf.	TP30.642x29.011x0.4	Reinf. 3 Tension Rupture	67.6%	Pass
L15	141.25 - 136.25	Pole + Reinf.	TP32.273x30.642x0.3938	Reinf. 3 Tension Rupture	73.2%	Pass
L16	136.25 - 135	Pole + Reinf.	TP34.313x32.273x0.3938	Reinf. 3 Tension Rupture	74.4%	Pass
L17	135 - 129	Pole + Reinf.	TP34.133x32.181x0.475	Reinf. 7 Tension Rupture	69.5%	Pass
L18	129 - 124	Pole + Reinf.	TP35.76x34.133x0.4625	Reinf. 7 Tension Rupture	73.2%	Pass
L19	124 - 121.42	Pole + Reinf.	TP36.599x35.76x0.4625	Pole	75.4%	Pass
L20	121.42 - 121.17	Pole + Reinf.	TP36.68x36.599x0.5	Pole	69.3%	Pass
L21	121.17 - 116.17	Pole + Reinf.	TP38.307x36.68x0.4875	Pole	73.9%	Pass
L22	116.17 - 115	Pole + Reinf.	TP38.688x38.307x0.4875	Pole	75.0%	Pass
L23	115 - 113.75	Pole + Reinf.	TP39.094x38.688x0.55	Reinf. 7 Tension Rupture	64.8%	Pass
L24	113.75 - 113.5	Pole + Reinf.	TP39.175x39.094x0.4688	Pole	71.1%	Pass
L25	113.5 - 108.5	Pole + Reinf.	TP40.8x39.175x0.4625	Pole	74.3%	Pass
L26	108.5 - 103.5	Pole + Reinf.	TP42.425x40.8x0.4563	Pole	77.3%	Pass
L27	103.5 - 101	Pole + Reinf.	TP45.188x42.425x0.45	Pole	78.7%	Pass
L28	101 - 94	Pole + Reinf.	TP44.853x42.613x0.5875	Pole	65.0%	Pass
L29	94 - 91.4	Pole + Reinf.	TP45.685x44.853x0.575	Pole	66.4%	Pass
L30	91.4 - 91.15	Pole + Reinf.	TP45.765x45.685x0.4438	Pole	85.9%	Pass
L31	91.15 - 91	Pole + Reinf.	TP45.813x45.765x0.4438	Pole	86.0%	Pass
L32	91 - 86	Pole + Reinf.	TP47.445x45.813x0.5	Pole	71.8%	Pass
L33	86 - 81	Pole + Reinf.	TP49.078x47.445x0.5	Pole	73.6%	Pass
L34	81 - 76	Pole + Reinf.	TP50.711x49.078x0.4938	Pole	75.3%	Pass
L35	76 - 71	Pole + Reinf.	TP52.344x50.711x0.4875	Pole	77.0%	Pass
L36	71 - 66	Pole + Reinf.	TP53.977x52.344x0.4875	Pole	78.6%	Pass
L37	66 - 63.75	Pole + Reinf.	TP54.711x53.977x0.4875	Pole	79.3%	Pass
L38	63.75 - 63.5	Pole + Reinf.	TP54.793x54.711x0.4875	Pole	79.4%	Pass
L39	63.5 - 58.5	Pole + Reinf.	TP56.426x54.793x0.4813	Pole	81.0%	Pass
L40	58.5 - 58	Pole + Reinf.	TP58.875x56.426x0.4813	Pole	81.2%	Pass
L41	58 - 50	Pole + Reinf.	TP58.438x55.839x0.55	Pole	73.7%	Pass

Section No.	Elevation (ft)	Component Type	Size	Critical Element	% Capacity	Pass / Fail
L42	50 - 45	Pole + Reinf.	TP60.063x58.438x0.55	Pole	75.3%	Pass
L43	45 - 40.42	Pole + Reinf.	TP61.551x60.063x0.5438	Pole	76.8%	Pass
L44	40.42 - 40.17	Pole + Reinf.	TP61.632x61.551x0.475	Pole	88.5%	Pass
L45	40.17 - 40	Pole + Reinf.	TP61.688x61.632x0.475	Pole	88.5%	Pass
L46	40 - 35	Pole + Reinf.	TP63.31x61.688x0.5313	Pole	73.5%	Pass
L47	35 - 33	Pole + Reinf.	TP63.958x63.31x0.525	Pole	74.0%	Pass
L48	33 - 32.75	Pole + Reinf.	TP64.039x63.958x0.6	Pole	66.7%	Pass
L49	32.75 - 28	Pole + Reinf.	TP68.5x64.039x0.6	Pole	67.8%	Pass
L50	28 - 18	Pole + Reinf.	TP67.958x64.705x0.6	Pole	71.2%	Pass
L51	18 - 13	Pole + Reinf.	TP69.584x67.958x0.5875	Pole	72.3%	Pass
L52	13 - 8	Pole + Reinf.	TP71.21x69.584x0.5875	Pole	73.4%	Pass
L53	8 - 6.42	Pole + Reinf.	TP71.724x71.21x0.5875	Pole	73.8%	Pass
L54	6.42 - 6.17	Pole + Reinf.	TP71.806x71.724x0.9375	Reinf. 9 Tension Rupture	79.4%	Pass
L55	6.17 - 1.17	Pole + Reinf.	TP73.432x71.806x0.9125	Reinf. 9 Tension Rupture	80.1%	Pass
L56	1.17 - 0	Pole + Reinf.	TP73.813x73.432x0.9	Reinf. 9 Tension Rupture	80.2%	Pass
				Summary		
				Pole	88.5%	Pass
				Reinforcement	80.2%	Pass
				Overall	88.5%	Pass

Table 5 - Tower Component Stresses vs. Capacity – LC7

Notes	Component	Elevation (ft)	% Capacity	Pass / Fail
1	Anchor Rods	0	67.9	Pass
1	Base Plate		37.4	Pass
1	Base Foundation (Structure)	0	72.3	Pass
1	Base Foundation (Soil Interaction)		80.1	Pass

Structure Rating (max from all components) =	88.5%*
---	---------------

Notes:


- 1) See additional documentation in "Appendix C – Additional Calculations" for calculations supporting the % capacity consumed.
- 2) *Rating Per TIA-222-H, Section 15.5.

4.1) Recommendations

The tower and its foundation have sufficient capacity to carry the proposed load configuration. No modifications are required at this time.

APPENDIX A

TNXTOWER OUTPUT



MATERIAL STRENGTH

GRADE	Fy	Fu	GRADE	Fy	Fu
A36M-42	42 ksi	60 ksi			

TOWER DESIGN NOTES

1. Tower is located in Middlesex County, Connecticut.
2. Tower designed for Exposure C to the TIA-222-H Standard.
3. Tower designed for a 120 mph basic wind in accordance with the TIA-222-H Standard.
4. Tower is also designed for a 50 mph basic wind with 1.00 in ice. Ice is considered to increase in thickness with height.
5. Deflections are based upon a 60 mph wind.
6. Tower Risk Category II.
7. Topographic Category 1 with Crest Height of 0.00 ft
8. TOWER RATING: 88.5%

Tower Input Data

The tower is a monopole.

This tower is designed using the TIA-222-H standard.

The following design criteria apply:

- Tower is located in Middlesex County, Connecticut.
- Tower base elevation above sea level: 90.00 ft.
- Basic wind speed of 120 mph.
- Risk Category II.
- Exposure Category C.
- Simplified Topographic Factor Procedure for wind speed-up calculations is used.
- Topographic Category: 1.
- Crest Height: 0.00 ft.
- Nominal ice thickness of 1.0000 in.
- Ice thickness is considered to increase with height.
- Ice density of 56 pcf.
- A wind speed of 50 mph is used in combination with ice.
- Temperature drop of 50 °F.
- Deflections calculated using a wind speed of 60 mph.
- A non-linear (P-delta) analysis was used.
- Pressures are calculated at each section.
- Stress ratio used in pole design is 1.
- Tower analysis based on target reliabilities in accordance with Annex S.
- Load Modification Factors used: $K_{es}(F_w) = 0.95$, $K_{es}(t_i) = 0.85$.
- Maximum demand-capacity ratio is: 1.05.
- Local bending stresses due to climbing loads, feed line supports, and appurtenance mounts are not considered.

Options

Consider Moments - Legs	Distribute Leg Loads As Uniform	Use ASCE 10 X-Brace Ly Rules
Consider Moments - Horizontals	Assume Legs Pinned	Calculate Redundant Bracing Forces
Consider Moments - Diagonals	✓ Assume Rigid Index Plate	Ignore Redundant Members in FEA
Use Moment Magnification	✓ Use Clear Spans For Wind Area	SR Leg Bolts Resist Compression
✓ Use Code Stress Ratios	Use Clear Spans For KL/r	All Leg Panels Have Same Allowable
✓ Use Code Safety Factors - Guys	Retention Guys To Initial Tension	Offset Girt At Foundation
Escalate Ice	✓ Bypass Mast Stability Checks	✓ Consider Feed Line Torque
Always Use Max Kz	✓ Use Azimuth Dish Coefficients	Include Angle Block Shear Check
Use Special Wind Profile	✓ Project Wind Area of Appurt.	Use TIA-222-H Bracing Resist.
Include Bolts In Member Capacity	Autocalc Torque Arm Areas	Exemption
Leg Bolts Are At Top Of Section	Add IBC .6D+W Combination	Use TIA-222-H Tension Splice
Secondary Horizontal Braces Leg	Sort Capacity Reports By Component	Exemption
Use Diamond Inner Bracing (4 Sided)	Triangulate Diamond Inner Bracing	Poles
SR Members Have Cut Ends	Treat Feed Line Bundles As Cylinder	✓ Include Shear-Torsion Interaction
SR Members Are Concentric	Ignore KL/ry For 60 Deg. Angle Legs	Always Use Sub-Critical Flow
		Use Top Mounted Sockets
		Pole Without Linear Attachments
		Pole With Shroud Or No
		Appurtenances
		Outside and Inside Corner Radii Are Known

Tapered Pole Section Geometry									
Section	Elevation ft	Section Length ft	Splice Length ft	Number of Sides	Top Diameter in	Bottom Diameter in	Wall Thickness in	Bend Radius in	Pole Grade
L1	185.00-180.00	5.00	0.00	12	18.0000	18.0000	0.1875	0.7500	A36M-42 (42 ksi)
L2	180.00-175.00	5.00	0.00	12	18.0000	19.6313	0.2500	1.0000	A36M-42 (42 ksi)
L3	175.00-170.00	5.00	0.00	12	19.6313	21.2625	0.2500	1.0000	A36M-42 (42 ksi)
L4	170.00-165.00	5.00	0.00	12	21.2625	22.8938	0.2500	1.0000	A36M-42 (42 ksi)
L5	165.00-160.00	5.00	0.00	12	22.8938	24.5250	0.2500	1.0000	A36M-42 (42 ksi)
L6	160.00-155.00	5.00	0.00	12	24.5250	26.1563	0.2500	1.0000	A36M-42 (42 ksi)
L7	155.00-154.00	1.00	0.00	12	26.1563	26.4825	0.2500	1.0000	A36M-42 (42 ksi)
L8	154.00-153.75	0.25	0.00	12	26.4825	26.5641	0.3688	1.4750	A36M-42 (42 ksi)
L9	153.75-152.50	1.25	0.00	12	26.5641	26.9719	0.3625	1.4500	A36M-42 (42 ksi)
L10	152.50-152.25	0.25	0.00	12	26.9719	27.0534	0.5500	2.2000	A36M-42 (42 ksi)
L11	152.25-151.50	0.75	0.00	12	27.0534	27.2981	0.5500	2.2000	A36M-42 (42 ksi)
L12	151.50-151.25	0.25	0.00	12	27.2981	27.3797	0.4250	1.7000	A36M-42 (42 ksi)
L13	151.25-146.25	5.00	0.00	12	27.3797	29.0109	0.4125	1.6500	A36M-42 (42 ksi)
L14	146.25-141.25	5.00	0.00	12	29.0109	30.6422	0.4000	1.6000	A36M-42 (42 ksi)
L15	141.25-136.25	5.00	0.00	12	30.6422	32.2734	0.3937	1.5750	A36M-42 (42 ksi)
L16	136.25-130.00	6.25	5.00	12	32.2734	34.3125	0.3937	1.5750	A36M-42 (42 ksi)
L17	130.00-129.00	6.00	0.00	12	32.1812	34.1331	0.4750	1.9000	A36M-42 (42 ksi)
L18	129.00-124.00	5.00	0.00	12	34.1331	35.7597	0.4625	1.8500	A36M-42 (42 ksi)
L19	124.00-121.42	2.58	0.00	12	35.7597	36.5990	0.4625	1.8500	A36M-42 (42 ksi)
L20	121.42-121.17	0.25	0.00	12	36.5990	36.6803	0.5000	2.0000	A36M-42 (42 ksi)
L21	121.17-116.17	5.00	0.00	12	36.6803	38.3069	0.4875	1.9500	A36M-42 (42 ksi)
L22	116.17-115.00	1.17	0.00	12	38.3069	38.6875	0.4875	1.9500	A36M-42 (42 ksi)
L23	115.00-113.75	1.25	0.00	12	38.6875	39.0938	0.5500	2.2000	A36M-42 (42 ksi)
L24	113.75-113.50	0.25	0.00	12	39.0938	39.1750	0.4688	1.8750	A36M-42 (42 ksi)
L25	113.50-108.50	5.00	0.00	12	39.1750	40.8000	0.4625	1.8500	A36M-42 (42 ksi)
L26	108.50-103.50	5.00	0.00	12	40.8000	42.4250	0.4562	1.8250	A36M-42 (42 ksi)
L27	103.50-95.00	8.50	6.00	12	42.4250	45.1875	0.4500	1.8000	A36M-42 (42 ksi)
L28	95.00-94.00	7.00	0.00	12	42.6125	44.8525	0.5875	2.3500	A36M-42 (42 ksi)
L29	94.00-91.40	2.60	0.00	12	44.8525	45.6845	0.5750	2.3000	A36M-42 (42 ksi)
L30	91.40-91.15	0.25	0.00	12	45.6845	45.7645	0.4437	1.7750	A36M-42 (42 ksi)
L31	91.15-91.00	0.15	0.00	12	45.7645	45.8125	0.4437	1.7750	A36M-42 (42 ksi)
L32	91.00-86.00	5.00	0.00	12	45.8125	47.4453	0.5000	2.0000	A36M-42 (42 ksi)
L33	86.00-81.00	5.00	0.00	12	47.4453	49.0781	0.5000	2.0000	A36M-42 (42 ksi)

Section	Elevation ft	Section Length ft	Splice Length ft	Number of Sides	Top Diameter in	Bottom Diameter in	Wall Thickness in	Bend Radius in	Pole Grade
L34	81.00-76.00	5.00	0.00	12	49.0781	50.7109	0.4938	1.9750	A36M-42 (42 ksi)
L35	76.00-71.00	5.00	0.00	12	50.7109	52.3438	0.4875	1.9500	A36M-42 (42 ksi)
L36	71.00-66.00	5.00	0.00	12	52.3438	53.9766	0.4875	1.9500	A36M-42 (42 ksi)
L37	66.00-63.75	2.25	0.00	12	53.9766	54.7113	0.4875	1.9500	A36M-42 (42 ksi)
L38	63.75-63.50	0.25	0.00	12	54.7113	54.7930	0.4875	1.9500	A36M-42 (42 ksi)
L39	63.50-58.50	5.00	0.00	12	54.7930	56.4258	0.4813	1.9250	A36M-42 (42 ksi)
L40	58.50-51.00	7.50	7.00	12	56.4258	58.8750	0.4813	1.9250	A36M-42 (42 ksi)
L41	51.00-50.00	8.00	0.00	12	55.8391	58.4384	0.5500	2.2000	A36M-42 (42 ksi)
L42	50.00-45.00	5.00	0.00	12	58.4384	60.0629	0.5500	2.2000	A36M-42 (42 ksi)
L43	45.00-40.42	4.58	0.00	12	60.0629	61.5510	0.5437	2.1750	A36M-42 (42 ksi)
L44	40.42-40.17	0.25	0.00	12	61.5510	61.6323	0.4750	1.9000	A36M-42 (42 ksi)
L45	40.17-40.00	0.17	0.00	12	61.6323	61.6875	0.4750	1.9000	A36M-42 (42 ksi)
L46	40.00-35.00	5.00	0.00	12	61.6875	63.3095	0.5313	2.1250	A36M-42 (42 ksi)
L47	35.00-33.00	2.00	0.00	12	63.3095	63.9583	0.5250	2.1000	A36M-42 (42 ksi)
L48	33.00-32.75	0.25	0.00	12	63.9583	64.0394	0.6000	2.4000	A36M-42 (42 ksi)
L49	32.75-19.00	13.75	9.00	12	64.0394	68.5000	0.6000	2.4000	A36M-42 (42 ksi)
L50	19.00-18.00	10.00	0.00	12	64.7054	67.9579	0.6000	2.4000	A36M-42 (42 ksi)
L51	18.00-13.00	5.00	0.00	12	67.9579	69.5842	0.5875	2.3500	A36M-42 (42 ksi)
L52	13.00-8.00	5.00	0.00	12	69.5842	71.2105	0.5875	2.3500	A36M-42 (42 ksi)
L53	8.00-6.42	1.58	0.00	12	71.2105	71.7244	0.5875	2.3500	A36M-42 (42 ksi)
L54	6.42-6.17	0.25	0.00	12	71.7244	71.8057	0.9375	3.7500	A36M-42 (42 ksi)
L55	6.17-1.17	5.00	0.00	12	71.8057	73.4320	0.9125	3.6500	A36M-42 (42 ksi)
L56	1.17-0.00	1.17		12	73.4320	73.8125	0.9000	3.6000	A36M-42 (42 ksi)

Tapered Pole Properties

Section	Tip Dia. in	Area in ²	I in ⁴	r in	C in	I/C in ³	J in ⁴	It/Q in ²	w in	w/t
L1	18.5688	10.7543	435.5296	6.3769	9.3240	46.7106	882.5011	5.2929	4.3215	23.048
	18.5688	10.7543	435.5296	6.3769	9.3240	46.7106	882.5011	5.2929	4.3215	23.048
L2	18.5468	14.2888	574.6149	6.3545	9.3240	61.6275	1164.3256	7.0325	4.1540	16.616
	20.2356	15.6019	748.0441	6.9385	10.1690	73.5613	1515.7401	7.6788	4.5912	18.365
L3	20.2356	15.6019	748.0441	6.9385	10.1690	73.5613	1515.7401	7.6788	4.5912	18.365
	21.9244	16.9151	953.2680	7.5225	11.0140	86.5508	1931.5794	8.3251	5.0283	20.113
L4	21.9244	16.9151	953.2680	7.5225	11.0140	86.5508	1931.5794	8.3251	5.0283	20.113
	23.6132	18.2282	1192.9628	8.1065	11.8590	100.5959	2417.2660	8.9714	5.4655	21.862
L5	23.6132	18.2282	1192.9628	8.1065	11.8590	100.5959	2417.2660	8.9714	5.4655	21.862
	25.3020	19.5414	1469.8044	8.6905	12.7039	115.6966	2978.2222	9.6177	5.9027	23.611
L6	25.3020	19.5414	1469.8044	8.6905	12.7039	115.6966	2978.2222	9.6177	5.9027	23.611
	26.9908	20.8545	1786.4690	9.2744	13.5489	131.8531	3619.8706	10.2640	6.3399	25.36
L7	26.9908	20.8545	1786.4690	9.2744	13.5489	131.8531	3619.8706	10.2640	6.3399	25.36
	27.3285	21.1172	1854.8162	9.3912	13.7179	135.2110	3758.3604	10.3932	6.4273	25.709
L8	27.2866	31.0068	2698.8676	9.3487	13.7179	196.7401	5468.6374	15.2606	6.1091	16.567

185 Ft Monopole Tower Structural Analysis
Project Number CN9-327R4 / 2200039, Order 616581, Revision 0

Section	Tip Dia. in	Area in ²	I in ⁴	r in	C in	I/C in ³	J in ⁴	I/t/Q in ²	w in	w/t
	27.3711	31.1037	2724.2352	9.3779	13.7602	197.9796	5520.0391	15.3083	6.1309	16.626
L9	27.3733	30.5838	2679.9791	9.3802	13.7602	194.7633	5430.3642	15.0524	6.1477	16.959
	27.7955	31.0598	2807.0740	9.5262	13.9714	200.9153	5687.8929	15.2867	6.2570	17.261
L10	27.7293	46.7931	4169.6098	9.4590	13.9714	298.4383	8448.7598	23.0302	5.7545	10.463
	27.8138	46.9376	4208.3430	9.4882	14.0137	300.3025	8527.2438	23.1013	5.7763	10.502
L11	27.8138	46.9376	4208.3430	9.4882	14.0137	300.3025	8527.2438	23.1013	5.7763	10.502
	28.0671	47.3709	4325.9804	9.5758	14.1404	305.9299	8765.6090	23.3145	5.8419	10.622
L12	28.1112	36.7759	3389.8874	9.6206	14.1404	239.7302	6868.8309	18.1000	6.1769	14.534
	28.1956	36.8875	3420.8470	9.6498	14.1827	241.1989	6931.5635	18.1549	6.1988	14.585
L13	28.2000	35.8192	3324.8552	9.6543	14.1827	234.4307	6737.0581	17.6291	6.2323	15.109
	29.8888	37.9859	3965.4520	10.2382	15.0277	263.8768	8035.0807	18.6955	6.6694	16.168
L14	29.8932	36.8509	3850.3311	10.2427	15.0277	256.2162	7801.8147	18.1369	6.7029	16.757
	31.5820	38.9519	4547.1724	10.8267	15.8727	286.4784	9213.8040	19.1710	7.1401	17.85
L15	31.5842	38.3512	4478.8986	10.8289	15.8727	282.1771	9075.4628	18.8753	7.1569	18.176
	33.2730	40.4195	5243.2982	11.4129	16.7176	313.6386	10624.3436	19.8932	7.5940	19.286
L16	33.2730	40.4195	5243.2982	11.4129	16.7176	313.6386	10624.3436	19.8932	7.5940	19.286
	35.3840	43.0047	6315.1243	12.1429	17.7739	355.3037	12796.1540	21.1656	8.1405	20.674
L17	34.8329	48.4947	6222.5740	11.3508	16.6699	373.2823	12608.6220	23.8676	7.3516	15.477
	35.1696	51.4801	7443.9798	12.0496	17.6810	421.0168	15083.5213	25.3369	7.8747	16.578
L18	35.1741	50.1440	7256.1640	12.0541	17.6810	410.3943	14702.9556	24.6793	7.9082	17.099
	36.8580	52.5663	8359.3761	12.6364	18.5235	451.2845	16938.3623	25.8716	8.3441	18.041
L19	36.8580	52.5663	8359.3761	12.6364	18.5235	451.2845	16938.3623	25.8716	8.3441	18.041
	37.7269	53.8163	8969.9825	12.9369	18.9583	473.1433	18175.6163	26.4867	8.5690	18.528
L20	37.7137	58.1194	9667.1201	12.9234	18.9583	509.9155	19588.2062	28.6046	8.4685	16.937
	37.7979	58.2503	9732.6052	12.9526	19.0004	512.2314	19720.8967	28.6690	8.4903	16.981
L21	37.8023	56.8137	9499.1288	12.9570	19.0004	499.9434	19247.8104	27.9620	8.5238	17.485
	39.4862	59.3670	10838.2660	13.5393	19.8430	546.2019	21961.2654	29.2186	8.9597	18.379
L22	39.4862	59.3670	10838.2660	13.5393	19.8430	546.2019	21961.2654	29.2186	8.9597	18.379
	39.8803	59.9644	11168.8004	13.6756	20.0401	557.3219	22631.0177	29.5127	9.0618	18.588
L23	39.8582	67.5415	12538.9501	13.6532	20.0401	625.6922	25407.3123	33.2419	8.8942	16.171
	40.2788	68.2610	12943.9375	13.7987	20.2506	639.1890	26227.9267	33.5960	9.0031	16.369
L24	40.3075	58.2996	11101.6768	13.8278	20.2506	548.2157	22495.0070	28.6933	9.2209	19.671
	40.3916	58.4222	11171.8834	13.8568	20.2926	550.5384	22637.2646	28.7537	9.2426	19.718
L25	40.3938	57.6526	11028.2655	13.8591	20.2926	543.4611	22346.2559	28.3749	9.2594	20.02
	42.0761	60.0726	12476.1473	14.4408	21.1344	590.3242	25280.0569	29.5659	9.6949	20.962
L26	42.0783	59.2700	12313.2725	14.4431	21.1344	582.6176	24950.0284	29.1709	9.7117	21.286
	43.7606	61.6573	13861.9013	15.0248	21.9762	630.7702	28087.9702	30.3459	10.1472	22.24
L27	43.7628	60.8218	13678.1213	15.0270	21.9762	622.4075	27715.5820	29.9346	10.1639	22.586
	46.6228	64.8246	16560.3484	16.0160	23.4071	707.4918	33555.7556	31.9047	10.9042	24.232
L28	45.8962	79.5008	17921.4382	15.0450	22.0733	811.9066	36313.6926	39.1279	9.8456	16.759
	46.2275	83.7383	20942.6241	15.8469	23.2336	901.3940	42435.4343	41.2135	10.4460	17.78
L29	46.2319	81.9798	20514.4058	15.8513	23.2336	882.9630	41567.7478	40.3480	10.4795	18.225
	47.0932	83.5202	21692.7048	16.1492	23.6646	916.6743	43955.3011	41.1061	10.7024	18.613
L30	47.1395	64.6434	16887.6639	16.1962	23.6646	713.6265	34218.9855	31.8155	11.0542	24.911
	47.2224	64.7577	16977.4106	16.2248	23.7060	716.1648	34400.8367	31.8718	11.0756	24.959
L31	47.2224	64.7577	16977.4106	16.2248	23.7060	716.1648	34400.8367	31.8718	11.0756	24.959
	47.2721	64.8263	17031.4110	16.2420	23.7309	717.6900	34510.2561	31.9055	11.0885	24.988
L32	47.2522	72.9531	19119.0319	16.2219	23.7309	805.6606	38740.3421	35.9053	10.9377	21.876
	48.9426	75.5820	21261.2370	16.8064	24.5767	865.0983	43081.0304	37.1991	11.3753	22.751
L33	48.9426	75.5820	21261.2370	16.8064	24.5767	865.0983	43081.0304	37.1991	11.3753	22.751
	50.6330	78.2108	23557.7642	17.3910	25.4225	926.6513	47734.4171	38.4930	11.8129	23.626
L34	50.6352	77.2431	23272.2724	17.3932	25.4225	915.4214	47155.9333	38.0167	11.8297	23.959
	52.3256	79.8391	25698.4002	17.9778	26.2683	978.3059	52071.9259	39.2944	12.2673	24.845
L35	52.3279	78.8382	25382.5789	17.9800	26.2683	966.2830	51431.9864	38.8018	12.2840	25.198
	54.0183	81.4013	27939.5730	18.5645	27.1141	1030.4458	56613.1497	40.0633	12.7216	26.096
L36	54.0183	81.4013	27939.5730	18.5645	27.1141	1030.4458	56613.1497	40.0633	12.7216	26.096
	55.7087	83.9645	30662.7710	19.1491	27.9599	1096.6711	62131.0872	41.3248	13.1592	26.993
L37	55.7087	83.9645	30662.7710	19.1491	27.9599	1096.6711	62131.0872	41.3248	13.1592	26.993
	56.4694	85.1179	31943.8286	19.4121	28.3405	1127.1454	64726.8571	41.8924	13.3561	27.397
L38	56.4694	85.1179	31943.8286	19.4121	28.3405	1127.1454	64726.8571	41.8924	13.3561	27.397
	56.5539	85.2460	32088.3320	19.4414	28.3828	1130.5572	65019.6602	41.9555	13.3780	27.442
L39	56.5561	84.1628	31687.8814	19.4436	28.3828	1116.4483	64208.2388	41.4224	13.3948	27.833
	58.2465	86.6930	34632.6307	20.0281	29.2286	1184.8903	70175.0992	42.6677	13.8324	28.743
L40	58.2465	86.6930	34632.6307	20.0281	29.2286	1184.8903	70175.0992	42.6677	13.8324	28.743
	60.7821	90.4884	39383.2600	20.9050	30.4973	1291.3709	79801.1622	44.5356	14.4888	30.106
L41	59.9695	97.9169	38205.1746	19.7935	28.9246	1320.8525	77414.0418	48.1917	13.4909	24.529
	60.3058	102.5203	43850.8919	20.7240	30.2711	1448.6070	88853.7955	50.4574	14.1875	25.795
L42	60.3058	102.5203	43850.8919	20.7240	30.2711	1448.6070	88853.7955	50.4574	14.1875	25.795
	61.9877	105.3974	47647.3330	21.3056	31.1126	1531.4481	96546.4145	51.8734	14.6229	26.587
L43	61.9899	104.2107	47120.7287	21.3079	31.1126	1514.5224	95479.3714	51.2893	14.6396	26.923

Section	Tip Dia. in	Area in ²	I in ⁴	r in	C in	I/C in ³	J in ⁴	I/t/Q in ²	w in	w/t
	63.5305	106.8161	50744.1775	21.8406	31.8834	1591.5529	102821.4610	52.5717	15.0384	27.657
L44	63.5548	93.4158	44478.2784	21.8652	31.8834	1395.0277	90125.0506	45.9764	15.2227	32.048
	63.6389	93.5400	44655.9766	21.8943	31.9255	1398.7552	90485.1155	46.0376	15.2444	32.094
L45	63.6389	93.5400	44655.9766	21.8943	31.9255	1398.7552	90485.1155	46.0376	15.2444	32.094
	63.6960	93.6245	44777.0814	21.9141	31.9541	1401.2927	90730.5066	46.0791	15.2593	32.125
L46	63.6762	104.6154	49941.6983	21.8939	31.9541	1562.9187	101195.4207	51.4885	15.1085	28.44
	65.3554	107.3901	54021.7781	22.4746	32.7943	1647.2900	109462.7685	52.8541	15.5432	29.258
L47	65.3576	106.1372	53402.1742	22.4769	32.7943	1628.3964	108207.2830	52.2375	15.5600	29.638
	66.0293	107.2341	55074.9011	22.7091	33.1304	1662.3667	111596.6812	52.7773	15.7338	29.969
L48	66.0029	122.4083	62719.7481	22.6823	33.1304	1893.1168	127087.2139	60.2456	15.5328	25.888
	66.0868	122.5650	62960.9079	22.7113	33.1724	1897.9892	127575.8689	60.3228	15.5546	25.924
L49	66.0868	122.5650	62960.9079	22.7113	33.1724	1897.9892	127575.8689	60.3228	15.5546	25.924
	70.7048	131.1828	77197.3505	24.3082	35.4830	2175.6151	156422.7614	64.5642	16.7500	27.917
L50	69.8068	123.8516	64964.4917	22.9497	33.5174	1938.2333	131635.6728	60.9560	15.7330	26.222
	70.1435	130.1355	75363.1160	24.1141	35.2022	2140.8640	152706.1049	64.0487	16.6047	27.675
L51	70.1480	127.4480	73834.1413	24.1186	35.2022	2097.4300	149607.9877	62.7260	16.6382	28.32
	71.8316	130.5245	79311.1676	24.7008	36.0446	2200.3615	160705.9279	64.2402	17.0741	29.062
L52	71.8316	130.5245	79311.1676	24.7008	36.0446	2200.3615	160705.9279	64.2402	17.0741	29.062
	73.5152	133.6010	85052.5670	25.2830	36.8870	2305.7588	172339.5597	65.7543	17.5099	29.804
L53	73.5152	133.6010	85052.5670	25.2830	36.8870	2305.7588	172339.5597	65.7543	17.5099	29.804
	74.0473	134.5732	86922.8201	25.4670	37.1532	2339.5771	176129.1995	66.2328	17.6476	30.039
L54	73.9238	213.6878	136669.3358	25.3417	37.1532	3678.5328	276929.1273	105.1707	16.7096	17.824
	74.0080	213.9333	137140.8585	25.3708	37.1953	3687.0441	277884.5601	105.2915	16.7314	17.847
L55	74.0168	208.3019	133625.0851	25.3798	37.1953	3592.5222	270760.6499	102.5198	16.7984	18.409
	75.7005	213.0803	143033.6520	25.9620	38.0378	3760.3078	289824.9574	104.8716	17.2343	18.887
L56	75.7049	210.1976	141147.2494	25.9664	38.0378	3710.7149	286002.5942	103.4529	17.2678	19.186
	76.0988	211.3004	143380.5690	26.1027	38.2349	3749.9944	290527.9053	103.9956	17.3698	19.3

Tower Elevation	Gusset Area (per face)	Gusset Thickness	Gusset Grade	Adjust. Factor A _f	Adjust. Factor A _r	Weight Mult.	Double Angle Stitch Bolt Spacing Diagonals	Double Angle Stitch Bolt Spacing Horizontals	Double Angle Stitch Bolt Spacing Redundants
ft	ft ²	in					in	in	in
L1 185.00-				1	1	1			
180.00									
L2 180.00-				1	1	1			
175.00									
L3 175.00-				1	1	1			
170.00									
L4 170.00-				1	1	1			
165.00									
L5 165.00-				1	1	1			
160.00									
L6 160.00-				1	1	1			
155.00									
L7 155.00-				1	1	1			
154.00									
L8 154.00-				1	1	0.970809			
153.75									
L9 153.75-				1	1	0.98275			
152.50									
L10 152.50-				1	1	0.939738			
152.25									
L11 152.25-				1	1	0.935299			
151.50									
L12 151.50-				1	1	0.958557			
151.25									
L13 151.25-				1	1	0.965409			
146.25									
L14 146.25-				1	1	0.975178			
141.25									
L15 141.25-				1	1	0.97226			
136.25									
L16 136.25-				1	1	0.967999			
130.00									
L17 130.00-				1	1	0.967523			
129.00									
L18 129.00-				1	1	0.972439			
124.00									

Tower Elevation	Gusset Area (per face)	Gusset Thickness	Gusset Grade	Adjust. Factor A_f	Adjust. Factor A_r	Weight Mult.	Double Angle Stitch Bolt Spacing Diagonals in	Double Angle Stitch Bolt Spacing Horizontals in	Double Angle Stitch Bolt Spacing Redundants in
ft	ft ²	in							
L19 124.00-121.42				1	1	0.962408			
L20 121.42-121.17				1	1	0.967636			
L21 121.17-116.17				1	1	0.971491			
L22 116.17-115.00				1	1	0.966921			
L23 115.00-113.75				1	1	0.967791			
L24 113.75-113.50				1	1	0.977901			
L25 113.50-108.50				1	1	0.978255			
L26 108.50-103.50				1	1	0.979632			
L27 103.50-95.00				1	1	0.987419			
L28 95.00-94.00				1	1	0.965747			
L29 94.00-91.40				1	1	0.978292			
L30 91.40-91.15				1	1	0.984623			
L31 91.15-91.00				1	1	0.984326			
L32 91.00-86.00				1	1	0.990491			
L33 86.00-81.00				1	1	0.982407			
L34 81.00-76.00				1	1	0.987066			
L35 76.00-71.00				1	1	0.992343			
L36 71.00-66.00				1	1	0.985532			
L37 66.00-63.75				1	1	0.982601			
L38 63.75-63.50				1	1	0.982281			
L39 63.50-58.50				1	1	0.988627			
L40 58.50-51.00				1	1	0.988018			
L41 51.00-50.00				1	1	0.991576			
L42 50.00-45.00				1	1	0.98312			
L43 45.00-40.42				1	1	0.986885			
L44 40.42-40.17				1	1	0.983471			
L45 40.17-40.00				1	1	0.983296			
L46 40.00-35.00				1	1	0.992613			
L47 35.00-33.00				1	1	1.00258			
L48 33.00-32.75				1	1	1.07829			
L49 32.75-19.00				1	1	1.07001			
L50 19.00-18.00				1	1	1.05798			
L51 18.00-13.00				1	1	1.07238			
L52 13.00-				1	1	1.06483			

Tower Elevation	Gusset Area (per face)	Gusset Thickness	Gusset Grade	Adjust. Factor A _f	Adjust. Factor A _r	Weight Mult.	Double Angle Stitch Bolt Spacing Diagonals	Double Angle Stitch Bolt Spacing Horizontals	Double Angle Stitch Bolt Spacing Redundants
ft	ft ²	in					in	in	in
8.00									
L53 8.00-6.42				1	1	1.06252			
L54 6.42-6.17				1	1	0.582868			
L55 6.17-1.17				1	1	0.595953			
L56 1.17-0.00				1	1	0.60351			

Feed Line/Linear Appurtenances - Entered As Round Or Flat

Description	Sector	Exclude From Torque Calculation	Component Type	Placement ft	Total Number	Number Per Row	Start/End Position	Width or Diamete r in	Perimeter in	Weight plf

Safety Line 3/8"	C	No	Surface Ar (CaAa)	185.00 - 0.00	1	1	-0.300	0.3750		0.22
Step Pegs	C	No	Surface Ar (CaAa)	185.00 - 0.00	1	1	-0.350	0.3500		0.45
HCS 6X12 4AWG(1-5/8)	C	No	Surface Ar (CaAa)	183.00 - 0.00	3	3	-0.470	1.6600		2.40
HB158-21U6S24-xxM_TMO(1-5/8)	C	No	Surface Ar (CaAa)	183.00 - 0.00	1	1	-0.500	1.9960		2.50
CU12PSM6P4XXX(1-3/4)	B	No	Surface Ar (CaAa)	165.00 - 0.00	1	1	-0.450	1.7500		2.72

CCI-045100 (L)	C	No	Surface Af (CaAa)	53.92 - 38.92	1	1	-0.318	4.5000	11.0000	0.00
CCI-045100 (L)	B	No	Surface Af (CaAa)	53.92 - 38.92	1	1	-0.318	4.5000	11.0000	0.00
CCI-045100 (L)	A	No	Surface Af (CaAa)	53.92 - 38.92	1	1	-0.318	4.5000	11.0000	0.00
*										
CCI-060100 (L)	C	No	Surface Af (CaAa)	123.92 - 88.89	1	1	-0.318	6.0000	14.0000	0.00
CCI-060100 (L)	B	No	Surface Af (CaAa)	123.92 - 88.89	1	1	-0.318	6.0000	14.0000	0.00
CCI-060100 (L)	A	No	Surface Af (CaAa)	123.92 - 88.89	1	1	-0.318	6.0000	14.0000	0.00
*										
CCI-045100 (L)	B	No	Surface Af (CaAa)	154.50 - 119.50	1	1	0.432	4.5000	11.0000	0.00
CCI-045100 (L)	A	No	Surface Af (CaAa)	154.50 - 119.50	1	1	0.432	4.5000	11.0000	0.00
CCI-045100 (L)	C	No	Surface Af (CaAa)	154.50 - 119.50	1	1	0.432	4.5000	11.0000	0.00

CCI-085125 (L)	B	No	Surface Af (CaAa)	37.42 - 0.00	1	1	0.182	8.5000	19.5000	0.00
CCI-085125 (L)	A	No	Surface Af (CaAa)	37.42 - 0.00	1	1	0.432	8.5000	19.5000	0.00
CCI-085125 (L)	A	No	Surface Af (CaAa)	37.42 - 0.00	1	1	-0.318	8.5000	19.5000	0.00
CCI-085125 (L)	C	No	Surface Af (CaAa)	37.42 - 0.00	1	1	0.182	8.5000	19.5000	0.00
*										
CCI-060100 (L)	B	No	Surface Af (CaAa)	65.50 - 30.50	1	1	-0.068	6.0000	14.0000	0.00
CCI-060100 (L)	A	No	Surface Af (CaAa)	65.50 - 30.50	1	1	-0.068	6.0000	14.0000	0.00
CCI-060100 (L)	C	No	Surface Af (CaAa)	65.50 - 30.50	1	1	-0.068	6.0000	14.0000	0.00
*										
CCI-060100 (L)	B	No	Surface Af (CaAa)	101.67 -	1	1	0.182	6.0000	14.0000	0.00

Description	Sector	Exclude From Torque Calculation	Component Type	Placement ft	Total Number	Number Per Row	Start/End Position	Width or Diameter in	Perimeter in	Weight plf
CCI-060100 (L)	A	No	(CaAa) Surface Af	61.67 101.67 - (CaAa) 61.67	1	1	0.182 0.182 0.182	6.0000	14.0000	0.00
CCI-060100 (L)	C	No	Surface Af	101.67 - (CaAa) 61.67	1	1	0.182 0.182	6.0000	14.0000	0.00

CCI-040075 (W)	B	No	Surface Af	132.50 - (CaAa) 112.50	1	1	0.182 0.182	4.0000	9.5000	0.00
CCI-040075 (W)	A	No	Surface Af	132.50 - (CaAa) 112.50	1	1	0.182 0.182	4.0000	9.5000	0.00
CCI-040075 (W)	C	No	Surface Af	132.50 - (CaAa) 112.50	1	1	0.182 0.182	4.0000	9.5000	0.00
*										
CCI-040075 (W)	B	No	Surface Af	155.25 - (CaAa) 150.25	1	1	0.182 0.182	4.0000	9.5000	0.00
CCI-040075 (W)	A	No	Surface Af	155.25 - (CaAa) 150.25	1	1	0.182 0.182	4.0000	9.5000	0.00
CCI-040075 (W)	C	No	Surface Af	155.25 - (CaAa) 150.25	1	1	0.182 0.182	4.0000	9.5000	0.00

Feed Line/Linear Appurtenances - Entered As Area

Description	Face or Leg	Allow Shield	Exclude From Torque Calculation	Component Type	Placement ft	Total Number	$C_A A_A$	Weight
							ft^2/ft	plf

LDF6-50A(1-1/4)	A	No	No	Inside Pole	174.00 - 0.00	12	No Ice 1/2" Ice 1" Ice	0.00 0.00 0.00
FB-L98B-034-XXXXXX(3/8)	A	No	No	Inside Pole	174.00 - 0.00	1	No Ice 1/2" Ice 1" Ice	0.00 0.00 0.00
PWRT-606-S(7/8)	A	No	No	Inside Pole	174.00 - 0.00	1	No Ice 1/2" Ice 1" Ice	0.00 0.00 0.00
PWRT-608-S(13/16)	A	No	No	Inside Pole	174.00 - 0.00	2	No Ice 1/2" Ice 1" Ice	0.00 0.00 0.00
FB-L98B-235-XXX(3/8)	A	No	No	Inside Pole	174.00 - 0.00	1	No Ice 1/2" Ice 1" Ice	0.00 0.00 0.00

HB158-1-08U8-S8J18(1-5/8)	B	No	No	Inside Pole	155.00 - 0.00	2	No Ice 1/2" Ice 1" Ice	0.00 0.00 0.00

Feed Line/Linear Appurtenances Section Areas

Tower Section	Tower Elevation ft	Face	A_R	A_F	$C_A A_A$ In Face ft^2	$C_A A_A$ Out Face ft^2	Weight
			ft^2	ft^2	ft^2	K	
L1	185.00-180.00	A	0.000	0.000	0.000	0.000	0.00
		B	0.000	0.000	0.000	0.000	0.00
		C	0.000	0.000	2.455	0.000	0.03
L2	180.00-175.00	A	0.000	0.000	0.000	0.000	0.00
		B	0.000	0.000	0.000	0.000	0.00

Tower Section	Tower Elevation ft	Face	A_R ft^2	A_F ft^2	$C_A A_A$ In Face ft^2	$C_A A_A$ Out Face ft^2	Weight
							K
L3	175.00-170.00	C	0.000	0.000	3.850	0.000	0.05
		A	0.000	0.000	0.000	0.000	0.04
		B	0.000	0.000	0.000	0.000	0.00
		C	0.000	0.000	3.850	0.000	0.05
L4	170.00-165.00	A	0.000	0.000	0.000	0.000	0.05
		B	0.000	0.000	0.000	0.000	0.00
		C	0.000	0.000	3.850	0.000	0.05
L5	165.00-160.00	A	0.000	0.000	0.000	0.000	0.05
		B	0.000	0.000	0.875	0.000	0.01
		C	0.000	0.000	3.850	0.000	0.05
L6	160.00-155.00	A	0.000	0.000	0.138	0.000	0.05
		B	0.000	0.000	1.013	0.000	0.01
		C	0.000	0.000	3.989	0.000	0.05
L7	155.00-154.00	A	0.000	0.000	0.928	0.000	0.01
		B	0.000	0.000	1.103	0.000	0.01
		C	0.000	0.000	1.698	0.000	0.01
L8	154.00-153.75	A	0.000	0.000	0.326	0.000	0.00
		B	0.000	0.000	0.369	0.000	0.00
		C	0.000	0.000	0.518	0.000	0.00
L9	153.75-152.50	A	0.000	0.000	1.628	0.000	0.01
		B	0.000	0.000	1.847	0.000	0.01
		C	0.000	0.000	2.591	0.000	0.01
L10	152.50-152.25	A	0.000	0.000	0.326	0.000	0.00
		B	0.000	0.000	0.369	0.000	0.00
		C	0.000	0.000	0.518	0.000	0.00
L11	152.25-151.50	A	0.000	0.000	0.977	0.000	0.01
		B	0.000	0.000	1.108	0.000	0.00
		C	0.000	0.000	1.555	0.000	0.01
L12	151.50-151.25	A	0.000	0.000	0.326	0.000	0.00
		B	0.000	0.000	0.369	0.000	0.00
		C	0.000	0.000	0.518	0.000	0.00
L13	151.25-146.25	A	0.000	0.000	4.303	0.000	0.05
		B	0.000	0.000	5.178	0.000	0.03
		C	0.000	0.000	8.153	0.000	0.05
L14	146.25-141.25	A	0.000	0.000	3.750	0.000	0.05
		B	0.000	0.000	4.625	0.000	0.03
		C	0.000	0.000	7.601	0.000	0.05
L15	141.25-136.25	A	0.000	0.000	3.750	0.000	0.05
		B	0.000	0.000	4.625	0.000	0.03
		C	0.000	0.000	7.601	0.000	0.05
L16	136.25-130.00	A	0.000	0.000	6.354	0.000	0.06
		B	0.000	0.000	7.448	0.000	0.03
		C	0.000	0.000	11.167	0.000	0.06
L17	130.00-129.00	A	0.000	0.000	1.417	0.000	0.01
		B	0.000	0.000	1.592	0.000	0.01
		C	0.000	0.000	2.187	0.000	0.01
L18	129.00-124.00	A	0.000	0.000	7.083	0.000	0.05
		B	0.000	0.000	7.958	0.000	0.03
		C	0.000	0.000	10.934	0.000	0.05
L19	124.00-121.42	A	0.000	0.000	6.155	0.000	0.02
		B	0.000	0.000	6.606	0.000	0.01
		C	0.000	0.000	8.142	0.000	0.03
L20	121.42-121.17	A	0.000	0.000	0.604	0.000	0.00
		B	0.000	0.000	0.648	0.000	0.00
		C	0.000	0.000	0.797	0.000	0.00
L21	121.17-116.17	A	0.000	0.000	9.586	0.000	0.05
		B	0.000	0.000	10.461	0.000	0.03
		C	0.000	0.000	13.436	0.000	0.05
L22	116.17-115.00	A	0.000	0.000	1.950	0.000	0.01
		B	0.000	0.000	2.155	0.000	0.01
		C	0.000	0.000	2.851	0.000	0.01
L23	115.00-113.75	A	0.000	0.000	2.083	0.000	0.01
		B	0.000	0.000	2.302	0.000	0.01
		C	0.000	0.000	3.046	0.000	0.01
L24	113.75-113.50	A	0.000	0.000	0.417	0.000	0.00
		B	0.000	0.000	0.460	0.000	0.00
		C	0.000	0.000	0.609	0.000	0.00
L25	113.50-108.50	A	0.000	0.000	5.667	0.000	0.05
		B	0.000	0.000	6.542	0.000	0.03

Tower Section	Tower Elevation ft	Face	A_R ft^2	A_F ft^2	$C_A A_A$ In Face ft^2	$C_A A_A$ Out Face ft^2	Weight K
L26	108.50-103.50	C	0.000	0.000	9.517	0.000	0.05
		A	0.000	0.000	5.000	0.000	0.05
		B	0.000	0.000	5.875	0.000	0.03
L27	103.50-95.00	C	0.000	0.000	8.851	0.000	0.05
		A	0.000	0.000	15.170	0.000	0.08
		B	0.000	0.000	16.657	0.000	0.05
L28	95.00-94.00	C	0.000	0.000	21.716	0.000	0.09
		A	0.000	0.000	2.000	0.000	0.01
		B	0.000	0.000	2.175	0.000	0.01
L29	94.00-91.40	C	0.000	0.000	2.770	0.000	0.01
		A	0.000	0.000	5.200	0.000	0.02
		B	0.000	0.000	5.655	0.000	0.01
L30	91.40-91.15	C	0.000	0.000	7.202	0.000	0.03
		A	0.000	0.000	0.500	0.000	0.00
		B	0.000	0.000	0.544	0.000	0.00
L31	91.15-91.00	C	0.000	0.000	0.693	0.000	0.00
		A	0.000	0.000	0.300	0.000	0.00
		B	0.000	0.000	0.326	0.000	0.00
L32	91.00-86.00	C	0.000	0.000	0.416	0.000	0.00
		A	0.000	0.000	7.110	0.000	0.05
		B	0.000	0.000	7.985	0.000	0.03
L33	86.00-81.00	C	0.000	0.000	10.961	0.000	0.05
		A	0.000	0.000	5.000	0.000	0.05
		B	0.000	0.000	5.875	0.000	0.03
L34	81.00-76.00	C	0.000	0.000	8.851	0.000	0.05
		A	0.000	0.000	5.000	0.000	0.05
		B	0.000	0.000	5.875	0.000	0.03
L35	76.00-71.00	C	0.000	0.000	8.851	0.000	0.05
		A	0.000	0.000	5.000	0.000	0.05
		B	0.000	0.000	5.875	0.000	0.03
L36	71.00-66.00	C	0.000	0.000	8.851	0.000	0.05
		A	0.000	0.000	5.000	0.000	0.05
		B	0.000	0.000	5.875	0.000	0.03
L37	66.00-63.75	C	0.000	0.000	8.851	0.000	0.05
		A	0.000	0.000	4.000	0.000	0.02
		B	0.000	0.000	4.394	0.000	0.01
L38	63.75-63.50	C	0.000	0.000	5.733	0.000	0.02
		A	0.000	0.000	0.500	0.000	0.00
		B	0.000	0.000	0.544	0.000	0.00
L39	63.50-58.50	C	0.000	0.000	0.693	0.000	0.00
		A	0.000	0.000	6.830	0.000	0.05
		B	0.000	0.000	7.705	0.000	0.03
L40	58.50-51.00	C	0.000	0.000	10.681	0.000	0.05
		A	0.000	0.000	9.690	0.000	0.07
		B	0.000	0.000	11.003	0.000	0.04
L41	51.00-50.00	C	0.000	0.000	15.466	0.000	0.08
		A	0.000	0.000	1.750	0.000	0.01
		B	0.000	0.000	1.925	0.000	0.01
L42	50.00-45.00	C	0.000	0.000	2.520	0.000	0.01
		A	0.000	0.000	8.750	0.000	0.05
		B	0.000	0.000	9.625	0.000	0.03
L43	45.00-40.42	C	0.000	0.000	12.601	0.000	0.05
		A	0.000	0.000	8.015	0.000	0.04
		B	0.000	0.000	8.816	0.000	0.02
L44	40.42-40.17	C	0.000	0.000	11.542	0.000	0.05
		A	0.000	0.000	0.438	0.000	0.00
		B	0.000	0.000	0.481	0.000	0.00
L45	40.17-40.00	C	0.000	0.000	0.630	0.000	0.00
		A	0.000	0.000	0.297	0.000	0.00
		B	0.000	0.000	0.327	0.000	0.00
L46	40.00-35.00	C	0.000	0.000	0.428	0.000	0.00
		A	0.000	0.000	12.667	0.000	0.05
		B	0.000	0.000	10.113	0.000	0.03
L47	35.00-33.00	C	0.000	0.000	13.089	0.000	0.05
		A	0.000	0.000	7.667	0.000	0.02
		B	0.000	0.000	5.183	0.000	0.01
L48	33.00-32.75	C	0.000	0.000	6.374	0.000	0.02
		A	0.000	0.000	0.958	0.000	0.00
		B	0.000	0.000	0.648	0.000	0.00

Tower Section	Tower Elevation ft	Face	A_R ft^2	A_F ft^2	$C_A A_A$ In Face ft^2	$C_A A_A$ Out Face ft^2	Weight
							K
L49	32.75-19.00	C	0.000	0.000	0.797	0.000	0.00
		A	0.000	0.000	41.208	0.000	0.13
		B	0.000	0.000	24.135	0.000	0.07
L50	19.00-18.00	C	0.000	0.000	32.318	0.000	0.14
		A	0.000	0.000	2.833	0.000	0.01
		B	0.000	0.000	1.592	0.000	0.01
L51	18.00-13.00	C	0.000	0.000	2.187	0.000	0.01
		A	0.000	0.000	14.167	0.000	0.05
		B	0.000	0.000	7.958	0.000	0.03
L52	13.00-8.00	C	0.000	0.000	10.934	0.000	0.05
		A	0.000	0.000	14.167	0.000	0.05
		B	0.000	0.000	7.958	0.000	0.03
L53	8.00-6.42	C	0.000	0.000	10.934	0.000	0.05
		A	0.000	0.000	4.477	0.000	0.01
		B	0.000	0.000	2.515	0.000	0.01
L54	6.42-6.17	C	0.000	0.000	3.455	0.000	0.02
		A	0.000	0.000	0.708	0.000	0.00
		B	0.000	0.000	0.398	0.000	0.00
L55	6.17-1.17	C	0.000	0.000	0.547	0.000	0.00
		A	0.000	0.000	14.167	0.000	0.05
		B	0.000	0.000	7.958	0.000	0.03
L56	1.17-0.00	C	0.000	0.000	10.934	0.000	0.05
		A	0.000	0.000	3.315	0.000	0.01
		B	0.000	0.000	1.862	0.000	0.01
		C	0.000	0.000	2.559	0.000	0.01

Feed Line/Linear Appurtenances Section Areas - With Ice

Tower Section	Tower Elevation ft	Face or Leg	Ice Thickness in	A_R ft^2	A_F ft^2	$C_A A_A$ In Face ft^2	$C_A A_A$ Out Face ft^2	Weight
								K
L1	185.00-180.00	A	1.009	0.000	0.000	0.000	0.000	0.00
		B		0.000	0.000	0.000	0.000	0.00
		C		0.000	0.000	6.207	0.000	0.08
L2	180.00-175.00	A	1.006	0.000	0.000	0.000	0.000	0.00
		B		0.000	0.000	0.000	0.000	0.00
		C		0.000	0.000	8.747	0.000	0.12
L3	175.00-170.00	A	1.003	0.000	0.000	0.000	0.000	0.04
		B		0.000	0.000	0.000	0.000	0.00
		C		0.000	0.000	8.735	0.000	0.12
L4	170.00-165.00	A	1.000	0.000	0.000	0.000	0.000	0.05
		B		0.000	0.000	0.000	0.000	0.00
		C		0.000	0.000	8.723	0.000	0.12
L5	165.00-160.00	A	0.997	0.000	0.000	0.000	0.000	0.05
		B		0.000	0.000	1.872	0.000	0.03
		C		0.000	0.000	8.710	0.000	0.12
L6	160.00-155.00	A	0.994	0.000	0.000	0.165	0.000	0.05
		B		0.000	0.000	2.034	0.000	0.03
		C		0.000	0.000	8.861	0.000	0.12
L7	155.00-154.00	A	0.992	0.000	0.000	1.134	0.000	0.02
		B		0.000	0.000	1.507	0.000	0.02
		C		0.000	0.000	2.871	0.000	0.03
L8	154.00-153.75	A	0.991	0.000	0.000	0.402	0.000	0.01
		B		0.000	0.000	0.495	0.000	0.00
		C		0.000	0.000	0.836	0.000	0.01
L9	153.75-152.50	A	0.991	0.000	0.000	2.009	0.000	0.03
		B		0.000	0.000	2.476	0.000	0.02
		C		0.000	0.000	4.181	0.000	0.04
L10	152.50-152.25	A	0.991	0.000	0.000	0.402	0.000	0.01
		B		0.000	0.000	0.495	0.000	0.00
		C		0.000	0.000	0.836	0.000	0.01
L11	152.25-151.50	A	0.990	0.000	0.000	1.205	0.000	0.02
		B		0.000	0.000	1.485	0.000	0.01
		C		0.000	0.000	2.508	0.000	0.03
L12	151.50-151.25	A	0.990	0.000	0.000	0.402	0.000	0.01
		B		0.000	0.000	0.495	0.000	0.00

Tower Section	Tower Elevation ft	Face or Leg	Ice Thickness in	A_R ft^2	A_F ft^2	C_{AA} In Face ft^2	C_{AA} Out Face ft^2	Weight K
L13	151.25-146.25	C		0.000	0.000	0.836	0.000	0.01
		A	0.988	0.000	0.000	5.397	0.000	0.08
		B		0.000	0.000	7.260	0.000	0.08
		C		0.000	0.000	14.070	0.000	0.15
L14	146.25-141.25	A	0.985	0.000	0.000	4.735	0.000	0.08
		B		0.000	0.000	6.594	0.000	0.07
		C		0.000	0.000	13.393	0.000	0.15
L15	141.25-136.25	A	0.981	0.000	0.000	4.731	0.000	0.08
		B		0.000	0.000	6.588	0.000	0.07
		C		0.000	0.000	13.375	0.000	0.14
L16	136.25-130.00	A	0.977	0.000	0.000	8.064	0.000	0.11
		B		0.000	0.000	10.380	0.000	0.10
		C		0.000	0.000	18.847	0.000	0.19
L17	130.00-129.00	A	0.975	0.000	0.000	1.808	0.000	0.02
		B		0.000	0.000	2.178	0.000	0.02
		C		0.000	0.000	3.533	0.000	0.03
L18	129.00-124.00	A	0.972	0.000	0.000	9.028	0.000	0.10
		B		0.000	0.000	10.875	0.000	0.10
		C		0.000	0.000	17.633	0.000	0.17
L19	124.00-121.42	A	0.969	0.000	0.000	7.640	0.000	0.07
		B		0.000	0.000	8.592	0.000	0.07
		C		0.000	0.000	12.074	0.000	0.10
L20	121.42-121.17	A	0.968	0.000	0.000	0.749	0.000	0.01
		B		0.000	0.000	0.842	0.000	0.01
		C		0.000	0.000	1.179	0.000	0.01
L21	121.17-116.17	A	0.966	0.000	0.000	11.841	0.000	0.11
		B		0.000	0.000	13.682	0.000	0.11
		C		0.000	0.000	20.419	0.000	0.18
L22	116.17-115.00	A	0.964	0.000	0.000	2.401	0.000	0.02
		B		0.000	0.000	2.831	0.000	0.02
		C		0.000	0.000	4.406	0.000	0.04
L23	115.00-113.75	A	0.962	0.000	0.000	2.565	0.000	0.03
		B		0.000	0.000	3.024	0.000	0.03
		C		0.000	0.000	4.705	0.000	0.04
L24	113.75-113.50	A	0.962	0.000	0.000	0.513	0.000	0.01
		B		0.000	0.000	0.605	0.000	0.01
		C		0.000	0.000	0.941	0.000	0.01
L25	113.50-108.50	A	0.960	0.000	0.000	6.818	0.000	0.09
		B		0.000	0.000	8.653	0.000	0.08
		C		0.000	0.000	15.370	0.000	0.15
L26	108.50-103.50	A	0.955	0.000	0.000	5.955	0.000	0.08
		B		0.000	0.000	7.785	0.000	0.08
		C		0.000	0.000	14.488	0.000	0.15
L27	103.50-95.00	A	0.949	0.000	0.000	18.049	0.000	0.18
		B		0.000	0.000	21.150	0.000	0.17
		C		0.000	0.000	32.509	0.000	0.29
L28	95.00-94.00	A	0.944	0.000	0.000	2.380	0.000	0.02
		B		0.000	0.000	2.744	0.000	0.02
		C		0.000	0.000	4.081	0.000	0.04
L29	94.00-91.40	A	0.942	0.000	0.000	6.180	0.000	0.06
		B		0.000	0.000	7.125	0.000	0.06
		C		0.000	0.000	10.589	0.000	0.09
L30	91.40-91.15	A	0.941	0.000	0.000	0.594	0.000	0.01
		B		0.000	0.000	0.685	0.000	0.01
		C		0.000	0.000	1.018	0.000	0.01
L31	91.15-91.00	A	0.941	0.000	0.000	0.356	0.000	0.00
		B		0.000	0.000	0.411	0.000	0.00
		C		0.000	0.000	0.611	0.000	0.01
L32	91.00-86.00	A	0.938	0.000	0.000	8.444	0.000	0.09
		B		0.000	0.000	10.257	0.000	0.09
		C		0.000	0.000	16.904	0.000	0.16
L33	86.00-81.00	A	0.933	0.000	0.000	5.933	0.000	0.08
		B		0.000	0.000	7.740	0.000	0.07
		C		0.000	0.000	14.370	0.000	0.14
L34	81.00-76.00	A	0.927	0.000	0.000	5.927	0.000	0.08
		B		0.000	0.000	7.729	0.000	0.07
		C		0.000	0.000	14.339	0.000	0.14
L35	76.00-71.00	A	0.921	0.000	0.000	5.921	0.000	0.08
		B		0.000	0.000	7.717	0.000	0.07

Tower Section	Tower Elevation ft	Face or Leg	Ice Thickness in	A_R ft^2	A_F ft^2	C_{AA} In Face ft^2	C_{AA} Out Face ft^2	Weight K
L36	71.00-66.00	C		0.000	0.000	14.307	0.000	0.14
		A	0.914	0.000	0.000	5.914	0.000	0.08
		B		0.000	0.000	7.704	0.000	0.07
		C		0.000	0.000	14.274	0.000	0.14
L37	66.00-63.75	A	0.909	0.000	0.000	4.728	0.000	0.05
		B		0.000	0.000	5.531	0.000	0.04
		C		0.000	0.000	8.480	0.000	0.07
L38	63.75-63.50	A	0.908	0.000	0.000	0.591	0.000	0.01
		B		0.000	0.000	0.680	0.000	0.01
		C		0.000	0.000	1.007	0.000	0.01
L39	63.50-58.50	A	0.904	0.000	0.000	8.065	0.000	0.09
		B		0.000	0.000	9.843	0.000	0.08
		C		0.000	0.000	16.379	0.000	0.15
L40	58.50-51.00	A	0.894	0.000	0.000	11.553	0.000	0.13
		B		0.000	0.000	14.207	0.000	0.12
		C		0.000	0.000	23.963	0.000	0.22
L41	51.00-50.00	A	0.887	0.000	0.000	2.108	0.000	0.02
		B		0.000	0.000	2.461	0.000	0.02
		C		0.000	0.000	3.762	0.000	0.03
L42	50.00-45.00	A	0.882	0.000	0.000	10.513	0.000	0.10
		B		0.000	0.000	12.270	0.000	0.10
		C		0.000	0.000	18.732	0.000	0.16
L43	45.00-40.42	A	0.872	0.000	0.000	9.613	0.000	0.09
		B		0.000	0.000	11.213	0.000	0.09
		C		0.000	0.000	17.106	0.000	0.15
L44	40.42-40.17	A	0.867	0.000	0.000	0.524	0.000	0.01
		B		0.000	0.000	0.611	0.000	0.00
		C		0.000	0.000	0.932	0.000	0.01
L45	40.17-40.00	A	0.867	0.000	0.000	0.356	0.000	0.00
		B		0.000	0.000	0.416	0.000	0.00
		C		0.000	0.000	0.634	0.000	0.01
L46	40.00-35.00	A	0.861	0.000	0.000	14.547	0.000	0.12
		B		0.000	0.000	12.438	0.000	0.09
		C		0.000	0.000	18.834	0.000	0.16
L47	35.00-33.00	A	0.853	0.000	0.000	8.690	0.000	0.06
		B		0.000	0.000	6.206	0.000	0.04
		C		0.000	0.000	8.754	0.000	0.07
L48	33.00-32.75	A	0.850	0.000	0.000	1.086	0.000	0.01
		B		0.000	0.000	0.775	0.000	0.01
		C		0.000	0.000	1.093	0.000	0.01
L49	32.75-19.00	A	0.829	0.000	0.000	46.143	0.000	0.34
		B		0.000	0.000	29.070	0.000	0.22
		C		0.000	0.000	46.377	0.000	0.40
L50	19.00-18.00	A	0.802	0.000	0.000	3.165	0.000	0.02
		B		0.000	0.000	1.923	0.000	0.02
		C		0.000	0.000	3.182	0.000	0.03
L51	18.00-13.00	A	0.788	0.000	0.000	15.743	0.000	0.12
		B		0.000	0.000	9.535	0.000	0.07
		C		0.000	0.000	15.694	0.000	0.14
L52	13.00-8.00	A	0.758	0.000	0.000	15.683	0.000	0.11
		B		0.000	0.000	9.474	0.000	0.07
		C		0.000	0.000	15.536	0.000	0.13
L53	8.00-6.42	A	0.730	0.000	0.000	4.938	0.000	0.03
		B		0.000	0.000	2.976	0.000	0.02
		C		0.000	0.000	4.863	0.000	0.04
L54	6.42-6.17	A	0.720	0.000	0.000	0.780	0.000	0.01
		B		0.000	0.000	0.470	0.000	0.00
		C		0.000	0.000	0.767	0.000	0.01
L55	6.17-1.17	A	0.682	0.000	0.000	15.531	0.000	0.11
		B		0.000	0.000	9.323	0.000	0.07
		C		0.000	0.000	15.138	0.000	0.12
L56	1.17-0.00	A	0.568	0.000	0.000	3.581	0.000	0.02
		B		0.000	0.000	2.128	0.000	0.01
		C		0.000	0.000	3.402	0.000	0.03

Feed Line Center of Pressure

Section	Elevation	CP _x	CP _z	CP _x Ice	CP _z Ice
	ft	in	in	in	in
L1	185.00-180.00	1.8724	1.5510	2.4020	2.2629
L2	180.00-175.00	2.6471	2.1285	3.0157	2.6638
L3	175.00-170.00	2.7013	2.1728	3.1349	2.7705
L4	170.00-165.00	2.7499	2.2125	3.2450	2.8691
L5	165.00-160.00	2.7048	1.3428	3.2023	1.8397
L6	160.00-155.00	2.6774	1.3298	3.2413	1.8638
L7	155.00-154.00	1.4621	0.7264	2.0716	1.1917
L8	154.00-153.75	1.2339	0.6130	1.7956	1.0330
L9	153.75-152.50	1.2410	0.6166	1.8066	1.0395
L10	152.50-152.25	1.2490	0.6206	1.8187	1.0466
L11	152.25-151.50	1.2538	0.6230	1.8260	1.0509
L12	151.50-151.25	1.2579	0.6250	1.8325	1.0547
L13	151.25-146.25	1.5742	0.7823	2.2025	1.2681
L14	146.25-141.25	1.7184	0.8543	2.3823	1.3725
L15	141.25-136.25	1.7655	0.8780	2.4565	1.4160
L16	136.25-130.00	1.5995	0.7957	2.2752	1.3121
L17	130.00-129.00	1.3739	0.6835	1.9977	1.1524
L18	129.00-124.00	1.3975	0.6954	2.0325	1.1726
L19	124.00-121.42	1.0515	0.5233	1.6074	0.9276
L20	121.42-121.17	1.0519	0.5235	1.6101	0.9292
L21	121.17-116.17	1.2328	0.6136	1.8609	1.0742
L22	116.17-115.00	1.3575	0.6758	2.0324	1.1734
L23	115.00-113.75	1.3662	0.6801	2.0458	1.1812
L24	113.75-113.50	1.3711	0.6826	2.0533	1.1856
L25	113.50-108.50	1.6812	0.8370	2.4732	1.4282
L26	108.50-103.50	1.8102	0.9014	2.6511	1.5312
L27	103.50-95.00	1.4140	0.7043	2.1615	1.2487
L28	95.00-94.00	1.3443	0.6696	2.0734	1.1981
L29	94.00-91.40	1.3549	0.6749	2.0866	1.2055
L30	91.40-91.15	1.3628	0.6789	2.0985	1.2125
L31	91.15-91.00	1.3640	0.6795	2.1003	1.2135
L32	91.00-86.00	1.6446	0.8194	2.4717	1.4282
L33	86.00-81.00	1.9443	0.9688	2.8548	1.6497
L34	81.00-76.00	1.9744	0.9839	2.8998	1.6757
L35	76.00-71.00	2.0034	0.9985	2.9427	1.7006
L36	71.00-66.00	2.0316	1.0126	2.9837	1.7242
L37	66.00-63.75	1.6049	0.8000	2.4414	1.4108
L38	63.75-63.50	1.5174	0.7564	2.3252	1.3437
L39	63.50-58.50	1.8348	0.9147	2.7428	1.5849
L40	58.50-51.00	1.9111	0.9528	2.8319	1.6361
L41	51.00-50.00	1.6803	0.8378	2.5245	1.4587
L42	50.00-45.00	1.6953	0.8453	2.5383	1.4661
L43	45.00-40.42	1.7187	0.8570	2.5682	1.4830
L44	40.42-40.17	1.7301	0.8627	2.5821	1.4909
L45	40.17-40.00	1.7311	0.8632	2.5833	1.4916
L46	40.00-35.00	1.8424	1.9754	2.6550	2.4147
L47	35.00-33.00	1.7663	2.7113	2.4832	3.0050
L48	33.00-32.75	1.7731	2.7217	2.4906	3.0153
L49	32.75-19.00	2.1766	3.3408	2.9868	3.6275
L50	19.00-18.00	2.2937	3.5203	3.1359	3.8088
L51	18.00-13.00	2.3113	3.5473	3.1195	3.8133
L52	13.00-8.00	2.3404	3.5917	3.1291	3.8438
L53	8.00-6.42	2.3591	3.6204	3.1262	3.8577
L54	6.42-6.17	2.3662	3.6312	3.1254	3.8631
L55	6.17-1.17	2.3808	3.6535	3.1053	3.8629
L56	1.17-0.00	2.3978	3.6796	3.0049	3.8153

Note: For pole sections, center of pressure calculations do not consider feed line shielding.

Shielding Factor Ka

Tower Section	Feed Line Record No.	Description	Feed Line Segment Elev.	K _a No Ice	K _a Ice
L1	2	Safety Line 3/8"	180.00 - 185.00	1.0000	1.0000
L1	3	Step Pegs	180.00 - 185.00	1.0000	1.0000
L1	6	HCS 6X12 4AWG(1-5/8)	180.00 - 183.00	1.0000	1.0000
L1	8	HB158-21U6S24-xxM_TMO(1-5/8)	180.00 - 183.00	1.0000	1.0000
L2	2	Safety Line 3/8"	175.00 - 180.00	1.0000	1.0000
L2	3	Step Pegs	175.00 - 180.00	1.0000	1.0000
L2	6	HCS 6X12 4AWG(1-5/8)	175.00 - 180.00	1.0000	1.0000
L2	8	HB158-21U6S24-xxM_TMO(1-5/8)	175.00 - 180.00	1.0000	1.0000
L3	2	Safety Line 3/8"	170.00 - 175.00	1.0000	1.0000
L3	3	Step Pegs	170.00 - 175.00	1.0000	1.0000
L3	6	HCS 6X12 4AWG(1-5/8)	170.00 - 175.00	1.0000	1.0000
L3	8	HB158-21U6S24-xxM_TMO(1-5/8)	170.00 - 175.00	1.0000	1.0000
L4	2	Safety Line 3/8"	165.00 - 170.00	1.0000	1.0000
L4	3	Step Pegs	165.00 - 170.00	1.0000	1.0000
L4	6	HCS 6X12 4AWG(1-5/8)	165.00 - 170.00	1.0000	1.0000
L4	8	HB158-21U6S24-xxM_TMO(1-5/8)	165.00 - 170.00	1.0000	1.0000
L5	2	Safety Line 3/8"	160.00 - 165.00	1.0000	1.0000
L5	3	Step Pegs	160.00 - 165.00	1.0000	1.0000
L5	6	HCS 6X12 4AWG(1-5/8)	160.00 - 165.00	1.0000	1.0000
L5	8	HB158-21U6S24-xxM_TMO(1-5/8)	160.00 - 165.00	1.0000	1.0000
L5	23	CU12PSM6P4XXX(1-3/4)	160.00 - 165.00	1.0000	1.0000
L6	2	Safety Line 3/8"	155.00 - 160.00	1.0000	1.0000
L6	3	Step Pegs	155.00 - 160.00	1.0000	1.0000
L6	6	HCS 6X12 4AWG(1-5/8)	155.00 - 160.00	1.0000	1.0000
L6	8	HB158-21U6S24-xxM_TMO(1-5/8)	155.00 - 160.00	1.0000	1.0000
L6	23	CU12PSM6P4XXX(1-3/4)	155.00 - 160.00	1.0000	1.0000
L6	56	CCI-040075 (W)	155.00 - 155.25	1.0000	1.0000
L6	57	CCI-040075 (W)	155.00 - 155.25	1.0000	1.0000
L6	58	CCI-040075 (W)	155.00 - 155.25	1.0000	1.0000
L7	2	Safety Line 3/8"	154.00 - 155.00	1.0000	1.0000
L7	3	Step Pegs	154.00 - 155.00	1.0000	1.0000
L7	6	HCS 6X12 4AWG(1-5/8)	154.00 - 155.00	1.0000	1.0000
L7	8	HB158-21U6S24-xxM_TMO(1-5/8)	154.00 - 155.00	1.0000	1.0000

Tower Section	Feed Line Record No.	Description	Feed Line Segment Elev.	K_a No Ice	K_a Ice
L7	23	CU12PSM6P4XXX(1-3/4)	154.00 - 155.00	1.0000	1.0000
L7	35	CCI-045100 (L)	154.00 - 154.50	1.0000	1.0000
L7	36	CCI-045100 (L)	154.00 - 154.50	1.0000	1.0000
L7	37	CCI-045100 (L)	154.00 - 154.50	1.0000	1.0000
L7	56	CCI-040075 (W)	154.00 - 155.00	1.0000	1.0000
L7	57	CCI-040075 (W)	154.00 - 155.00	1.0000	1.0000
L7	58	CCI-040075 (W)	154.00 - 155.00	1.0000	1.0000
L8	2	Safety Line 3/8"	153.75 - 154.00	1.0000	1.0000
L8	3	Step Pegs	153.75 - 154.00	1.0000	1.0000
L8	6	HCS 6X12 4AWG(1-5/8)	153.75 - 154.00	1.0000	1.0000
L8	8	HB158-21U6S24- xxM_TMO(1-5/8)	153.75 - 154.00	1.0000	1.0000
L8	23	CU12PSM6P4XXX(1-3/4)	153.75 - 154.00	1.0000	1.0000
L8	35	CCI-045100 (L)	153.75 - 154.00	1.0000	1.0000
L8	36	CCI-045100 (L)	153.75 - 154.00	1.0000	1.0000
L8	37	CCI-045100 (L)	153.75 - 154.00	1.0000	1.0000
L8	56	CCI-040075 (W)	153.75 - 154.00	1.0000	1.0000
L8	57	CCI-040075 (W)	153.75 - 154.00	1.0000	1.0000
L8	58	CCI-040075 (W)	153.75 - 154.00	1.0000	1.0000
L9	2	Safety Line 3/8"	152.50 - 153.75	1.0000	1.0000
L9	3	Step Pegs	152.50 - 153.75	1.0000	1.0000
L9	6	HCS 6X12 4AWG(1-5/8)	152.50 - 153.75	1.0000	1.0000
L9	8	HB158-21U6S24- xxM_TMO(1-5/8)	152.50 - 153.75	1.0000	1.0000
L9	23	CU12PSM6P4XXX(1-3/4)	152.50 - 153.75	1.0000	1.0000
L9	35	CCI-045100 (L)	152.50 - 153.75	1.0000	1.0000
L9	36	CCI-045100 (L)	152.50 - 153.75	1.0000	1.0000
L9	37	CCI-045100 (L)	152.50 - 153.75	1.0000	1.0000
L9	56	CCI-040075 (W)	152.50 - 153.75	1.0000	1.0000
L9	57	CCI-040075 (W)	152.50 - 153.75	1.0000	1.0000
L9	58	CCI-040075 (W)	152.50 - 153.75	1.0000	1.0000
L10	2	Safety Line 3/8"	152.25 - 152.50	1.0000	1.0000
L10	3	Step Pegs	152.25 - 152.50	1.0000	1.0000
L10	6	HCS 6X12 4AWG(1-5/8)	152.25 - 152.50	1.0000	1.0000
L10	8	HB158-21U6S24- xxM_TMO(1-5/8)	152.25 - 152.50	1.0000	1.0000
L10	23	CU12PSM6P4XXX(1-3/4)	152.25 - 152.50	1.0000	1.0000
L10	35	CCI-045100 (L)	152.25 -	1.0000	1.0000

Tower Section	Feed Line Record No.	Description	Feed Line Segment Elev.	K_a No Ice	K_a Ice
L10	36	CCI-045100 (L)	152.50 152.25 - 152.50	1.0000	1.0000
L10	37	CCI-045100 (L)	152.25 - 152.50	1.0000	1.0000
L10	56	CCI-040075 (W)	152.25 - 152.50	1.0000	1.0000
L10	57	CCI-040075 (W)	152.25 - 152.50	1.0000	1.0000
L10	58	CCI-040075 (W)	152.25 - 152.50	1.0000	1.0000
L11	2	Safety Line 3/8"	151.50 - 152.25	1.0000	1.0000
L11	3	Step Pegs	151.50 - 152.25	1.0000	1.0000
L11	6	HCS 6X12 4AWG(1-5/8)	151.50 - 152.25	1.0000	1.0000
L11	8	HB158-21U6S24-xxM_TMO(1-5/8)	151.50 - 152.25	1.0000	1.0000
L11	23	CU12PSM6P4XXX(1-3/4)	151.50 - 152.25	1.0000	1.0000
L11	35	CCI-045100 (L)	151.50 - 152.25	1.0000	1.0000
L11	36	CCI-045100 (L)	151.50 - 152.25	1.0000	1.0000
L11	37	CCI-045100 (L)	151.50 - 152.25	1.0000	1.0000
L11	56	CCI-040075 (W)	151.50 - 152.25	1.0000	1.0000
L11	57	CCI-040075 (W)	151.50 - 152.25	1.0000	1.0000
L11	58	CCI-040075 (W)	151.50 - 152.25	1.0000	1.0000
L12	2	Safety Line 3/8"	151.25 - 151.50	1.0000	1.0000
L12	3	Step Pegs	151.25 - 151.50	1.0000	1.0000
L12	6	HCS 6X12 4AWG(1-5/8)	151.25 - 151.50	1.0000	1.0000
L12	8	HB158-21U6S24-xxM_TMO(1-5/8)	151.25 - 151.50	1.0000	1.0000
L12	23	CU12PSM6P4XXX(1-3/4)	151.25 - 151.50	1.0000	1.0000
L12	35	CCI-045100 (L)	151.25 - 151.50	1.0000	1.0000
L12	36	CCI-045100 (L)	151.25 - 151.50	1.0000	1.0000
L12	37	CCI-045100 (L)	151.25 - 151.50	1.0000	1.0000
L12	56	CCI-040075 (W)	151.25 - 151.50	1.0000	1.0000
L12	57	CCI-040075 (W)	151.25 - 151.50	1.0000	1.0000
L12	58	CCI-040075 (W)	151.25 - 151.50	1.0000	1.0000
L13	2	Safety Line 3/8"	146.25 - 151.25	1.0000	1.0000
L13	3	Step Pegs	146.25 - 151.25	1.0000	1.0000
L13	6	HCS 6X12 4AWG(1-5/8)	146.25 - 151.25	1.0000	1.0000
L13	8	HB158-21U6S24-xxM_TMO(1-5/8)	146.25 - 151.25	1.0000	1.0000
L13	23	CU12PSM6P4XXX(1-3/4)	146.25 - 151.25	1.0000	1.0000
L13	35	CCI-045100 (L)	146.25 - 151.25	1.0000	1.0000
L13	36	CCI-045100 (L)	146.25 - 151.25	1.0000	1.0000

Tower Section	Feed Line Record No.	Description	Feed Line Segment Elev.	K_a No Ice	K_a Ice
L13	37	CCI-045100 (L)	146.25 - 151.25	1.0000	1.0000
L13	56	CCI-040075 (W)	150.25 - 151.25	1.0000	1.0000
L13	57	CCI-040075 (W)	150.25 - 151.25	1.0000	1.0000
L13	58	CCI-040075 (W)	150.25 - 151.25	1.0000	1.0000
L14	2	Safety Line 3/8"	141.25 - 146.25	1.0000	1.0000
L14	3	Step Pegs	141.25 - 146.25	1.0000	1.0000
L14	6	HCS 6X12 4AWG(1-5/8)	141.25 - 146.25	1.0000	1.0000
L14	8	HB158-21U6S24-xxM_TMO(1-5/8)	141.25 - 146.25	1.0000	1.0000
L14	23	CU12PSM6P4XXX(1-3/4)	141.25 - 146.25	1.0000	1.0000
L14	35	CCI-045100 (L)	141.25 - 146.25	1.0000	1.0000
L14	36	CCI-045100 (L)	141.25 - 146.25	1.0000	1.0000
L14	37	CCI-045100 (L)	141.25 - 146.25	1.0000	1.0000
L15	2	Safety Line 3/8"	136.25 - 141.25	1.0000	1.0000
L15	3	Step Pegs	136.25 - 141.25	1.0000	1.0000
L15	6	HCS 6X12 4AWG(1-5/8)	136.25 - 141.25	1.0000	1.0000
L15	8	HB158-21U6S24-xxM_TMO(1-5/8)	136.25 - 141.25	1.0000	1.0000
L15	23	CU12PSM6P4XXX(1-3/4)	136.25 - 141.25	1.0000	1.0000
L15	35	CCI-045100 (L)	136.25 - 141.25	1.0000	1.0000
L15	36	CCI-045100 (L)	136.25 - 141.25	1.0000	1.0000
L15	37	CCI-045100 (L)	136.25 - 141.25	1.0000	1.0000
L16	2	Safety Line 3/8"	130.00 - 136.25	1.0000	1.0000
L16	3	Step Pegs	130.00 - 136.25	1.0000	1.0000
L16	6	HCS 6X12 4AWG(1-5/8)	130.00 - 136.25	1.0000	1.0000
L16	8	HB158-21U6S24-xxM_TMO(1-5/8)	130.00 - 136.25	1.0000	1.0000
L16	23	CU12PSM6P4XXX(1-3/4)	130.00 - 136.25	1.0000	1.0000
L16	35	CCI-045100 (L)	130.00 - 136.25	1.0000	1.0000
L16	36	CCI-045100 (L)	130.00 - 136.25	1.0000	1.0000
L16	37	CCI-045100 (L)	130.00 - 136.25	1.0000	1.0000
L16	52	CCI-040075 (W)	130.00 - 132.50	1.0000	1.0000
L16	53	CCI-040075 (W)	130.00 - 132.50	1.0000	1.0000
L16	54	CCI-040075 (W)	130.00 - 132.50	1.0000	1.0000
L17	2	Safety Line 3/8"	129.00 - 130.00	1.0000	1.0000
L17	3	Step Pegs	129.00 - 130.00	1.0000	1.0000
L17	6	HCS 6X12 4AWG(1-5/8)	129.00 - 130.00	1.0000	1.0000
L17	8	HB158-21U6S24-	129.00 -	1.0000	1.0000

Tower Section	Feed Line Record No.	Description	Feed Line Segment Elev.	K_a No Ice	K_a Ice
L17	23	xxM_TMO(1-5/8) CU12PSM6P4XXX(1-3/4)	130.00 129.00 - 130.00	1.0000	1.0000
L17	35	CCI-045100 (L)	129.00 - 130.00	1.0000	1.0000
L17	36	CCI-045100 (L)	129.00 - 130.00	1.0000	1.0000
L17	37	CCI-045100 (L)	129.00 - 130.00	1.0000	1.0000
L17	52	CCI-040075 (W)	129.00 - 130.00	1.0000	1.0000
L17	53	CCI-040075 (W)	129.00 - 130.00	1.0000	1.0000
L17	54	CCI-040075 (W)	129.00 - 130.00	1.0000	1.0000
L18	2	Safety Line 3/8"	124.00 - 129.00	1.0000	1.0000
L18	3	Step Pegs	124.00 - 129.00	1.0000	1.0000
L18	6	HCS 6X12 4AWG(1-5/8)	124.00 - 129.00	1.0000	1.0000
L18	8	HB158-21U6S24- xxM_TMO(1-5/8)	124.00 - 129.00	1.0000	1.0000
L18	23	CU12PSM6P4XXX(1-3/4)	124.00 - 129.00	1.0000	1.0000
L18	35	CCI-045100 (L)	124.00 - 129.00	1.0000	1.0000
L18	36	CCI-045100 (L)	124.00 - 129.00	1.0000	1.0000
L18	37	CCI-045100 (L)	124.00 - 129.00	1.0000	1.0000
L18	52	CCI-040075 (W)	124.00 - 129.00	1.0000	1.0000
L18	53	CCI-040075 (W)	124.00 - 129.00	1.0000	1.0000
L18	54	CCI-040075 (W)	124.00 - 129.00	1.0000	1.0000
L19	2	Safety Line 3/8"	121.42 - 124.00	1.0000	1.0000
L19	3	Step Pegs	121.42 - 124.00	1.0000	1.0000
L19	6	HCS 6X12 4AWG(1-5/8)	121.42 - 124.00	1.0000	1.0000
L19	8	HB158-21U6S24- xxM_TMO(1-5/8)	121.42 - 124.00	1.0000	1.0000
L19	23	CU12PSM6P4XXX(1-3/4)	121.42 - 124.00	1.0000	1.0000
L19	31	CCI-060100 (L)	121.42 - 123.92	1.0000	1.0000
L19	32	CCI-060100 (L)	121.42 - 123.92	1.0000	1.0000
L19	33	CCI-060100 (L)	121.42 - 123.92	1.0000	1.0000
L19	35	CCI-045100 (L)	121.42 - 124.00	1.0000	1.0000
L19	36	CCI-045100 (L)	121.42 - 124.00	1.0000	1.0000
L19	37	CCI-045100 (L)	121.42 - 124.00	1.0000	1.0000
L19	52	CCI-040075 (W)	121.42 - 124.00	1.0000	1.0000
L19	53	CCI-040075 (W)	121.42 - 124.00	1.0000	1.0000
L19	54	CCI-040075 (W)	121.42 - 124.00	1.0000	1.0000
L20	2	Safety Line 3/8"	121.17 - 121.42	1.0000	1.0000
L20	3	Step Pegs	121.17 - 121.42	1.0000	1.0000

Tower Section	Feed Line Record No.	Description	Feed Line Segment Elev.	K_a No Ice	K_a Ice
L20	6	HCS 6X12 4AWG(1-5/8)	121.17 - 121.42	1.0000	1.0000
L20	8	HB158-21U6S24- xxM_TMO(1-5/8)	121.17 - 121.42	1.0000	1.0000
L20	23	CU12PSM6P4XXX(1-3/4)	121.17 - 121.42	1.0000	1.0000
L20	31	CCI-060100 (L)	121.17 - 121.42	1.0000	1.0000
L20	32	CCI-060100 (L)	121.17 - 121.42	1.0000	1.0000
L20	33	CCI-060100 (L)	121.17 - 121.42	1.0000	1.0000
L20	35	CCI-045100 (L)	121.17 - 121.42	1.0000	1.0000
L20	36	CCI-045100 (L)	121.17 - 121.42	1.0000	1.0000
L20	37	CCI-045100 (L)	121.17 - 121.42	1.0000	1.0000
L20	52	CCI-040075 (W)	121.17 - 121.42	1.0000	1.0000
L20	53	CCI-040075 (W)	121.17 - 121.42	1.0000	1.0000
L20	54	CCI-040075 (W)	121.17 - 121.42	1.0000	1.0000
L21	2	Safety Line 3/8"	116.17 - 121.17	1.0000	1.0000
L21	3	Step Pegs	116.17 - 121.17	1.0000	1.0000
L21	6	HCS 6X12 4AWG(1-5/8)	116.17 - 121.17	1.0000	1.0000
L21	8	HB158-21U6S24- xxM_TMO(1-5/8)	116.17 - 121.17	1.0000	1.0000
L21	23	CU12PSM6P4XXX(1-3/4)	116.17 - 121.17	1.0000	1.0000
L21	31	CCI-060100 (L)	116.17 - 121.17	1.0000	1.0000
L21	32	CCI-060100 (L)	116.17 - 121.17	1.0000	1.0000
L21	33	CCI-060100 (L)	116.17 - 121.17	1.0000	1.0000
L21	35	CCI-045100 (L)	119.50 - 121.17	1.0000	1.0000
L21	36	CCI-045100 (L)	119.50 - 121.17	1.0000	1.0000
L21	37	CCI-045100 (L)	119.50 - 121.17	1.0000	1.0000
L21	52	CCI-040075 (W)	116.17 - 121.17	1.0000	1.0000
L21	53	CCI-040075 (W)	116.17 - 121.17	1.0000	1.0000
L21	54	CCI-040075 (W)	116.17 - 121.17	1.0000	1.0000
L22	2	Safety Line 3/8"	115.00 - 116.17	1.0000	1.0000
L22	3	Step Pegs	115.00 - 116.17	1.0000	1.0000
L22	6	HCS 6X12 4AWG(1-5/8)	115.00 - 116.17	1.0000	1.0000
L22	8	HB158-21U6S24- xxM_TMO(1-5/8)	115.00 - 116.17	1.0000	1.0000
L22	23	CU12PSM6P4XXX(1-3/4)	115.00 - 116.17	1.0000	1.0000
L22	31	CCI-060100 (L)	115.00 - 116.17	1.0000	1.0000
L22	32	CCI-060100 (L)	115.00 - 116.17	1.0000	1.0000
L22	33	CCI-060100 (L)	115.00 - 116.17	1.0000	1.0000
L22	52	CCI-040075 (W)	115.00 -	1.0000	1.0000

Tower Section	Feed Line Record No.	Description	Feed Line Segment Elev.	K_a No Ice	K_a Ice
L22	53	CCI-040075 (W)	116.17 115.00 - 116.17	1.0000	1.0000
L22	54	CCI-040075 (W)	115.00 - 116.17	1.0000	1.0000
L23	2	Safety Line 3/8"	113.75 - 115.00	1.0000	1.0000
L23	3	Step Pegs	113.75 - 115.00	1.0000	1.0000
L23	6	HCS 6X12 4AWG(1-5/8)	113.75 - 115.00	1.0000	1.0000
L23	8	HB158-21U6S24- xxM_TMO(1-5/8)	113.75 - 115.00	1.0000	1.0000
L23	23	CU12PSM6P4XXX(1-3/4)	113.75 - 115.00	1.0000	1.0000
L23	31	CCI-060100 (L)	113.75 - 115.00	1.0000	1.0000
L23	32	CCI-060100 (L)	113.75 - 115.00	1.0000	1.0000
L23	33	CCI-060100 (L)	113.75 - 115.00	1.0000	1.0000
L23	52	CCI-040075 (W)	113.75 - 115.00	1.0000	1.0000
L23	53	CCI-040075 (W)	113.75 - 115.00	1.0000	1.0000
L23	54	CCI-040075 (W)	113.75 - 115.00	1.0000	1.0000
L24	2	Safety Line 3/8"	113.50 - 113.75	1.0000	1.0000
L24	3	Step Pegs	113.50 - 113.75	1.0000	1.0000
L24	6	HCS 6X12 4AWG(1-5/8)	113.50 - 113.75	1.0000	1.0000
L24	8	HB158-21U6S24- xxM_TMO(1-5/8)	113.50 - 113.75	1.0000	1.0000
L24	23	CU12PSM6P4XXX(1-3/4)	113.50 - 113.75	1.0000	1.0000
L24	31	CCI-060100 (L)	113.50 - 113.75	1.0000	1.0000
L24	32	CCI-060100 (L)	113.50 - 113.75	1.0000	1.0000
L24	33	CCI-060100 (L)	113.50 - 113.75	1.0000	1.0000
L24	52	CCI-040075 (W)	113.50 - 113.75	1.0000	1.0000
L24	53	CCI-040075 (W)	113.50 - 113.75	1.0000	1.0000
L24	54	CCI-040075 (W)	113.50 - 113.75	1.0000	1.0000
L25	2	Safety Line 3/8"	108.50 - 113.50	1.0000	1.0000
L25	3	Step Pegs	108.50 - 113.50	1.0000	1.0000
L25	6	HCS 6X12 4AWG(1-5/8)	108.50 - 113.50	1.0000	1.0000
L25	8	HB158-21U6S24- xxM_TMO(1-5/8)	108.50 - 113.50	1.0000	1.0000
L25	23	CU12PSM6P4XXX(1-3/4)	108.50 - 113.50	1.0000	1.0000
L25	31	CCI-060100 (L)	108.50 - 113.50	1.0000	1.0000
L25	32	CCI-060100 (L)	108.50 - 113.50	1.0000	1.0000
L25	33	CCI-060100 (L)	108.50 - 113.50	1.0000	1.0000
L25	52	CCI-040075 (W)	112.50 - 113.50	1.0000	1.0000
L25	53	CCI-040075 (W)	112.50 - 113.50	1.0000	1.0000

Tower Section	Feed Line Record No.	Description	Feed Line Segment Elev.	K_a No Ice	K_a Ice
L25	54	CCI-040075 (W)	112.50 - 113.50	1.0000	1.0000
L26	2	Safety Line 3/8"	103.50 - 108.50	1.0000	1.0000
L26	3	Step Pegs	103.50 - 108.50	1.0000	1.0000
L26	6	HCS 6X12 4AWG(1-5/8)	103.50 - 108.50	1.0000	1.0000
L26	8	HB158-21U6S24-xxM_TMO(1-5/8)	103.50 - 108.50	1.0000	1.0000
L26	23	CU12PSM6P4XXX(1-3/4)	103.50 - 108.50	1.0000	1.0000
L26	31	CCI-060100 (L)	103.50 - 108.50	1.0000	1.0000
L26	32	CCI-060100 (L)	103.50 - 108.50	1.0000	1.0000
L26	33	CCI-060100 (L)	103.50 - 108.50	1.0000	1.0000
L27	2	Safety Line 3/8"	95.00 - 103.50	1.0000	1.0000
L27	3	Step Pegs	95.00 - 103.50	1.0000	1.0000
L27	6	HCS 6X12 4AWG(1-5/8)	95.00 - 103.50	1.0000	1.0000
L27	8	HB158-21U6S24-xxM_TMO(1-5/8)	95.00 - 103.50	1.0000	1.0000
L27	23	CU12PSM6P4XXX(1-3/4)	95.00 - 103.50	1.0000	1.0000
L27	31	CCI-060100 (L)	95.00 - 103.50	1.0000	1.0000
L27	32	CCI-060100 (L)	95.00 - 103.50	1.0000	1.0000
L27	33	CCI-060100 (L)	95.00 - 103.50	1.0000	1.0000
L27	48	CCI-060100 (L)	95.00 - 101.67	1.0000	1.0000
L27	49	CCI-060100 (L)	95.00 - 101.67	1.0000	1.0000
L27	50	CCI-060100 (L)	95.00 - 101.67	1.0000	1.0000
L28	2	Safety Line 3/8"	94.00 - 95.00	1.0000	1.0000
L28	3	Step Pegs	94.00 - 95.00	1.0000	1.0000
L28	6	HCS 6X12 4AWG(1-5/8)	94.00 - 95.00	1.0000	1.0000
L28	8	HB158-21U6S24-xxM_TMO(1-5/8)	94.00 - 95.00	1.0000	1.0000
L28	23	CU12PSM6P4XXX(1-3/4)	94.00 - 95.00	1.0000	1.0000
L28	31	CCI-060100 (L)	94.00 - 95.00	1.0000	1.0000
L28	32	CCI-060100 (L)	94.00 - 95.00	1.0000	1.0000
L28	33	CCI-060100 (L)	94.00 - 95.00	1.0000	1.0000
L28	48	CCI-060100 (L)	94.00 - 95.00	1.0000	1.0000
L28	49	CCI-060100 (L)	94.00 - 95.00	1.0000	1.0000
L28	50	CCI-060100 (L)	94.00 - 95.00	1.0000	1.0000
L29	2	Safety Line 3/8"	91.40 - 94.00	1.0000	1.0000
L29	3	Step Pegs	91.40 - 94.00	1.0000	1.0000
L29	6	HCS 6X12 4AWG(1-5/8)	91.40 - 94.00	1.0000	1.0000
L29	8	HB158-21U6S24-	91.40 -	1.0000	1.0000

Tower Section	Feed Line Record No.	Description	Feed Line Segment Elev.	K_a No Ice	K_a Ice
L29	23	xxM_TMO(1-5/8) CU12PSM6P4XXX(1-3/4)	94.00 91.40 - 94.00	1.0000	1.0000
L29	31	CCI-060100 (L)	91.40 - 94.00	1.0000	1.0000
L29	32	CCI-060100 (L)	91.40 - 94.00	1.0000	1.0000
L29	33	CCI-060100 (L)	91.40 - 94.00	1.0000	1.0000
L29	48	CCI-060100 (L)	91.40 - 94.00	1.0000	1.0000
L29	49	CCI-060100 (L)	91.40 - 94.00	1.0000	1.0000
L29	50	CCI-060100 (L)	91.40 - 94.00	1.0000	1.0000
L30	2	Safety Line 3/8"	91.15 - 91.40	1.0000	1.0000
L30	3	Step Pegs	91.15 - 91.40	1.0000	1.0000
L30	6	HCS 6X12 4AWG(1-5/8)	91.15 - 91.40	1.0000	1.0000
L30	8	HB158-21U6S24- xxM_TMO(1-5/8)	91.15 - 91.40	1.0000	1.0000
L30	23	CU12PSM6P4XXX(1-3/4)	91.15 - 91.40	1.0000	1.0000
L30	31	CCI-060100 (L)	91.15 - 91.40	1.0000	1.0000
L30	32	CCI-060100 (L)	91.15 - 91.40	1.0000	1.0000
L30	33	CCI-060100 (L)	91.15 - 91.40	1.0000	1.0000
L30	48	CCI-060100 (L)	91.15 - 91.40	1.0000	1.0000
L30	49	CCI-060100 (L)	91.15 - 91.40	1.0000	1.0000
L30	50	CCI-060100 (L)	91.15 - 91.40	1.0000	1.0000
L31	2	Safety Line 3/8"	91.00 - 91.15	1.0000	1.0000
L31	3	Step Pegs	91.00 - 91.15	1.0000	1.0000
L31	6	HCS 6X12 4AWG(1-5/8)	91.00 - 91.15	1.0000	1.0000
L31	8	HB158-21U6S24- xxM_TMO(1-5/8)	91.00 - 91.15	1.0000	1.0000
L31	23	CU12PSM6P4XXX(1-3/4)	91.00 - 91.15	1.0000	1.0000
L31	31	CCI-060100 (L)	91.00 - 91.15	1.0000	1.0000
L31	32	CCI-060100 (L)	91.00 - 91.15	1.0000	1.0000
L31	33	CCI-060100 (L)	91.00 - 91.15	1.0000	1.0000
L31	48	CCI-060100 (L)	91.00 - 91.15	1.0000	1.0000
L31	49	CCI-060100 (L)	91.00 - 91.15	1.0000	1.0000
L31	50	CCI-060100 (L)	91.00 - 91.15	1.0000	1.0000
L32	2	Safety Line 3/8"	86.00 - 91.00	1.0000	1.0000
L32	3	Step Pegs	86.00 - 91.00	1.0000	1.0000
L32	6	HCS 6X12 4AWG(1-5/8)	86.00 - 91.00	1.0000	1.0000
L32	8	HB158-21U6S24- xxM_TMO(1-5/8)	86.00 - 91.00	1.0000	1.0000
L32	23	CU12PSM6P4XXX(1-3/4)	86.00 - 91.00	1.0000	1.0000

Tower Section	Feed Line Record No.	Description	Feed Line Segment Elev.	K_a No Ice	K_a Ice
L32	31	CCI-060100 (L)	88.89 - 91.00	1.0000	1.0000
L32	32	CCI-060100 (L)	88.89 - 91.00	1.0000	1.0000
L32	33	CCI-060100 (L)	88.89 - 91.00	1.0000	1.0000
L32	48	CCI-060100 (L)	86.00 - 91.00	1.0000	1.0000
L32	49	CCI-060100 (L)	86.00 - 91.00	1.0000	1.0000
L32	50	CCI-060100 (L)	86.00 - 91.00	1.0000	1.0000
L33	2	Safety Line 3/8"	81.00 - 86.00	1.0000	1.0000
L33	3	Step Pegs	81.00 - 86.00	1.0000	1.0000
L33	6	HCS 6X12 4AWG(1-5/8)	81.00 - 86.00	1.0000	1.0000
L33	8	HB158-21U6S24-xxM_TMO(1-5/8)	81.00 - 86.00	1.0000	1.0000
L33	23	CU12PSM6P4XXX(1-3/4)	81.00 - 86.00	1.0000	1.0000
L33	48	CCI-060100 (L)	81.00 - 86.00	1.0000	1.0000
L33	49	CCI-060100 (L)	81.00 - 86.00	1.0000	1.0000
L33	50	CCI-060100 (L)	81.00 - 86.00	1.0000	1.0000
L34	2	Safety Line 3/8"	76.00 - 81.00	1.0000	1.0000
L34	3	Step Pegs	76.00 - 81.00	1.0000	1.0000
L34	6	HCS 6X12 4AWG(1-5/8)	76.00 - 81.00	1.0000	1.0000
L34	8	HB158-21U6S24-xxM_TMO(1-5/8)	76.00 - 81.00	1.0000	1.0000
L34	23	CU12PSM6P4XXX(1-3/4)	76.00 - 81.00	1.0000	1.0000
L34	48	CCI-060100 (L)	76.00 - 81.00	1.0000	1.0000
L34	49	CCI-060100 (L)	76.00 - 81.00	1.0000	1.0000
L34	50	CCI-060100 (L)	76.00 - 81.00	1.0000	1.0000
L35	2	Safety Line 3/8"	71.00 - 76.00	1.0000	1.0000
L35	3	Step Pegs	71.00 - 76.00	1.0000	1.0000
L35	6	HCS 6X12 4AWG(1-5/8)	71.00 - 76.00	1.0000	1.0000
L35	8	HB158-21U6S24-xxM_TMO(1-5/8)	71.00 - 76.00	1.0000	1.0000
L35	23	CU12PSM6P4XXX(1-3/4)	71.00 - 76.00	1.0000	1.0000
L35	48	CCI-060100 (L)	71.00 - 76.00	1.0000	1.0000
L35	49	CCI-060100 (L)	71.00 - 76.00	1.0000	1.0000
L35	50	CCI-060100 (L)	71.00 - 76.00	1.0000	1.0000
L36	2	Safety Line 3/8"	66.00 - 71.00	1.0000	1.0000
L36	3	Step Pegs	66.00 - 71.00	1.0000	1.0000
L36	6	HCS 6X12 4AWG(1-5/8)	66.00 - 71.00	1.0000	1.0000
L36	8	HB158-21U6S24-xxM_TMO(1-5/8)	66.00 - 71.00	1.0000	1.0000
L36	23	CU12PSM6P4XXX(1-3/4)	66.00 - 71.00	1.0000	1.0000

Tower Section	Feed Line Record No.	Description	Feed Line Segment Elev.	K_a No Ice	K_a Ice
L36	48	CCI-060100 (L)	71.00 66.00 - 71.00	1.0000	1.0000
L36	49	CCI-060100 (L)	66.00 - 71.00	1.0000	1.0000
L36	50	CCI-060100 (L)	66.00 - 71.00	1.0000	1.0000
L37	2	Safety Line 3/8"	63.75 - 66.00	1.0000	1.0000
L37	3	Step Pegs	63.75 - 66.00	1.0000	1.0000
L37	6	HCS 6X12 4AWG(1-5/8)	63.75 - 66.00	1.0000	1.0000
L37	8	HB158-21U6S24- xxM_TMO(1-5/8)	63.75 - 66.00	1.0000	1.0000
L37	23	CU12PSM6P4XXX(1-3/4)	63.75 - 66.00	1.0000	1.0000
L37	44	CCI-060100 (L)	63.75 - 65.50	1.0000	1.0000
L37	45	CCI-060100 (L)	63.75 - 65.50	1.0000	1.0000
L37	46	CCI-060100 (L)	63.75 - 65.50	1.0000	1.0000
L37	48	CCI-060100 (L)	63.75 - 66.00	1.0000	1.0000
L37	49	CCI-060100 (L)	63.75 - 66.00	1.0000	1.0000
L37	50	CCI-060100 (L)	63.75 - 66.00	1.0000	1.0000
L38	2	Safety Line 3/8"	63.50 - 63.75	1.0000	1.0000
L38	3	Step Pegs	63.50 - 63.75	1.0000	1.0000
L38	6	HCS 6X12 4AWG(1-5/8)	63.50 - 63.75	1.0000	1.0000
L38	8	HB158-21U6S24- xxM_TMO(1-5/8)	63.50 - 63.75	1.0000	1.0000
L38	23	CU12PSM6P4XXX(1-3/4)	63.50 - 63.75	1.0000	1.0000
L38	44	CCI-060100 (L)	63.50 - 63.75	1.0000	1.0000
L38	45	CCI-060100 (L)	63.50 - 63.75	1.0000	1.0000
L38	46	CCI-060100 (L)	63.50 - 63.75	1.0000	1.0000
L38	48	CCI-060100 (L)	63.50 - 63.75	1.0000	1.0000
L38	49	CCI-060100 (L)	63.50 - 63.75	1.0000	1.0000
L38	50	CCI-060100 (L)	63.50 - 63.75	1.0000	1.0000
L39	2	Safety Line 3/8"	58.50 - 63.50	1.0000	1.0000
L39	3	Step Pegs	58.50 - 63.50	1.0000	1.0000
L39	6	HCS 6X12 4AWG(1-5/8)	58.50 - 63.50	1.0000	1.0000
L39	8	HB158-21U6S24- xxM_TMO(1-5/8)	58.50 - 63.50	1.0000	1.0000
L39	23	CU12PSM6P4XXX(1-3/4)	58.50 - 63.50	1.0000	1.0000
L39	44	CCI-060100 (L)	58.50 - 63.50	1.0000	1.0000
L39	45	CCI-060100 (L)	58.50 - 63.50	1.0000	1.0000
L39	46	CCI-060100 (L)	58.50 - 63.50	1.0000	1.0000
L39	48	CCI-060100 (L)	61.67 - 63.50	1.0000	1.0000

Tower Section	Feed Line Record No.	Description	Feed Line Segment Elev.	K_a No Ice	K_a Ice
L39	49	CCI-060100 (L)	61.67 - 63.50	1.0000	1.0000
L39	50	CCI-060100 (L)	61.67 - 63.50	1.0000	1.0000
L40	2	Safety Line 3/8"	51.00 - 58.50	1.0000	1.0000
L40	3	Step Pegs	51.00 - 58.50	1.0000	1.0000
L40	6	HCS 6X12 4AWG(1-5/8)	51.00 - 58.50	1.0000	1.0000
L40	8	HB158-21U6S24-xxM_TMO(1-5/8)	51.00 - 58.50	1.0000	1.0000
L40	23	CU12PSM6P4XXX(1-3/4)	51.00 - 58.50	1.0000	1.0000
L40	27	CCI-045100 (L)	51.00 - 53.92	1.0000	1.0000
L40	28	CCI-045100 (L)	51.00 - 53.92	1.0000	1.0000
L40	29	CCI-045100 (L)	51.00 - 53.92	1.0000	1.0000
L40	44	CCI-060100 (L)	51.00 - 58.50	1.0000	1.0000
L40	45	CCI-060100 (L)	51.00 - 58.50	1.0000	1.0000
L40	46	CCI-060100 (L)	51.00 - 58.50	1.0000	1.0000
L41	2	Safety Line 3/8"	50.00 - 51.00	1.0000	1.0000
L41	3	Step Pegs	50.00 - 51.00	1.0000	1.0000
L41	6	HCS 6X12 4AWG(1-5/8)	50.00 - 51.00	1.0000	1.0000
L41	8	HB158-21U6S24-xxM_TMO(1-5/8)	50.00 - 51.00	1.0000	1.0000
L41	23	CU12PSM6P4XXX(1-3/4)	50.00 - 51.00	1.0000	1.0000
L41	27	CCI-045100 (L)	50.00 - 51.00	1.0000	1.0000
L41	28	CCI-045100 (L)	50.00 - 51.00	1.0000	1.0000
L41	29	CCI-045100 (L)	50.00 - 51.00	1.0000	1.0000
L41	44	CCI-060100 (L)	50.00 - 51.00	1.0000	1.0000
L41	45	CCI-060100 (L)	50.00 - 51.00	1.0000	1.0000
L41	46	CCI-060100 (L)	50.00 - 51.00	1.0000	1.0000
L42	2	Safety Line 3/8"	45.00 - 50.00	1.0000	1.0000
L42	3	Step Pegs	45.00 - 50.00	1.0000	1.0000
L42	6	HCS 6X12 4AWG(1-5/8)	45.00 - 50.00	1.0000	1.0000
L42	8	HB158-21U6S24-xxM_TMO(1-5/8)	45.00 - 50.00	1.0000	1.0000
L42	23	CU12PSM6P4XXX(1-3/4)	45.00 - 50.00	1.0000	1.0000
L42	27	CCI-045100 (L)	45.00 - 50.00	1.0000	1.0000
L42	28	CCI-045100 (L)	45.00 - 50.00	1.0000	1.0000
L42	29	CCI-045100 (L)	45.00 - 50.00	1.0000	1.0000
L42	44	CCI-060100 (L)	45.00 - 50.00	1.0000	1.0000
L42	45	CCI-060100 (L)	45.00 - 50.00	1.0000	1.0000
L42	46	CCI-060100 (L)	45.00 - 50.00	1.0000	1.0000

Tower Section	Feed Line Record No.	Description	Feed Line Segment Elev.	K_a No Ice	K_a Ice
L43	2	Safety Line 3/8"	50.00 40.42 - 45.00	1.0000	1.0000
L43	3	Step Pegs	40.42 - 45.00	1.0000	1.0000
L43	6	HCS 6X12 4AWG(1-5/8)	40.42 - 45.00	1.0000	1.0000
L43	8	HB158-21U6S24-xxM_TMO(1-5/8)	40.42 - 45.00	1.0000	1.0000
L43	23	CU12PSM6P4XXX(1-3/4)	40.42 - 45.00	1.0000	1.0000
L43	27	CCI-045100 (L)	40.42 - 45.00	1.0000	1.0000
L43	28	CCI-045100 (L)	40.42 - 45.00	1.0000	1.0000
L43	29	CCI-045100 (L)	40.42 - 45.00	1.0000	1.0000
L43	44	CCI-060100 (L)	40.42 - 45.00	1.0000	1.0000
L43	45	CCI-060100 (L)	40.42 - 45.00	1.0000	1.0000
L43	46	CCI-060100 (L)	40.42 - 45.00	1.0000	1.0000
L44	2	Safety Line 3/8"	40.17 - 40.42	1.0000	1.0000
L44	3	Step Pegs	40.17 - 40.42	1.0000	1.0000
L44	6	HCS 6X12 4AWG(1-5/8)	40.17 - 40.42	1.0000	1.0000
L44	8	HB158-21U6S24-xxM_TMO(1-5/8)	40.17 - 40.42	1.0000	1.0000
L44	23	CU12PSM6P4XXX(1-3/4)	40.17 - 40.42	1.0000	1.0000
L44	27	CCI-045100 (L)	40.17 - 40.42	1.0000	1.0000
L44	28	CCI-045100 (L)	40.17 - 40.42	1.0000	1.0000
L44	29	CCI-045100 (L)	40.17 - 40.42	1.0000	1.0000
L44	44	CCI-060100 (L)	40.17 - 40.42	1.0000	1.0000
L44	45	CCI-060100 (L)	40.17 - 40.42	1.0000	1.0000
L44	46	CCI-060100 (L)	40.17 - 40.42	1.0000	1.0000
L45	2	Safety Line 3/8"	40.00 - 40.17	1.0000	1.0000
L45	3	Step Pegs	40.00 - 40.17	1.0000	1.0000
L45	6	HCS 6X12 4AWG(1-5/8)	40.00 - 40.17	1.0000	1.0000
L45	8	HB158-21U6S24-xxM_TMO(1-5/8)	40.00 - 40.17	1.0000	1.0000
L45	23	CU12PSM6P4XXX(1-3/4)	40.00 - 40.17	1.0000	1.0000
L45	27	CCI-045100 (L)	40.00 - 40.17	1.0000	1.0000
L45	28	CCI-045100 (L)	40.00 - 40.17	1.0000	1.0000
L45	29	CCI-045100 (L)	40.00 - 40.17	1.0000	1.0000
L45	44	CCI-060100 (L)	40.00 - 40.17	1.0000	1.0000
L45	45	CCI-060100 (L)	40.00 - 40.17	1.0000	1.0000
L45	46	CCI-060100 (L)	40.00 - 40.17	1.0000	1.0000
L46	2	Safety Line 3/8"	35.00 - 40.00	1.0000	1.0000

Tower Section	Feed Line Record No.	Description	Feed Line Segment Elev.	K_a No Ice	K_a Ice
L46	3	Step Pegs	35.00 - 40.00	1.0000	1.0000
L46	6	HCS 6X12 4AWG(1-5/8)	35.00 - 40.00	1.0000	1.0000
L46	8	HB158-21U6S24-xxM_TMO(1-5/8)	35.00 - 40.00	1.0000	1.0000
L46	23	CU12PSM6P4XXX(1-3/4)	35.00 - 40.00	1.0000	1.0000
L46	27	CCI-045100 (L)	38.92 - 40.00	1.0000	1.0000
L46	28	CCI-045100 (L)	38.92 - 40.00	1.0000	1.0000
L46	29	CCI-045100 (L)	38.92 - 40.00	1.0000	1.0000
L46	39	CCI-085125 (L)	35.00 - 37.42	1.0000	1.0000
L46	40	CCI-085125 (L)	35.00 - 37.42	1.0000	1.0000
L46	41	CCI-085125 (L)	35.00 - 37.42	1.0000	1.0000
L46	42	CCI-085125 (L)	35.00 - 37.42	1.0000	1.0000
L46	44	CCI-060100 (L)	35.00 - 40.00	1.0000	1.0000
L46	45	CCI-060100 (L)	35.00 - 40.00	1.0000	1.0000
L46	46	CCI-060100 (L)	35.00 - 40.00	1.0000	1.0000
L47	2	Safety Line 3/8"	33.00 - 35.00	1.0000	1.0000
L47	3	Step Pegs	33.00 - 35.00	1.0000	1.0000
L47	6	HCS 6X12 4AWG(1-5/8)	33.00 - 35.00	1.0000	1.0000
L47	8	HB158-21U6S24-xxM_TMO(1-5/8)	33.00 - 35.00	1.0000	1.0000
L47	23	CU12PSM6P4XXX(1-3/4)	33.00 - 35.00	1.0000	1.0000
L47	39	CCI-085125 (L)	33.00 - 35.00	1.0000	1.0000
L47	40	CCI-085125 (L)	33.00 - 35.00	1.0000	1.0000
L47	41	CCI-085125 (L)	33.00 - 35.00	1.0000	1.0000
L47	42	CCI-085125 (L)	33.00 - 35.00	1.0000	1.0000
L47	44	CCI-060100 (L)	33.00 - 35.00	1.0000	1.0000
L47	45	CCI-060100 (L)	33.00 - 35.00	1.0000	1.0000
L47	46	CCI-060100 (L)	33.00 - 35.00	1.0000	1.0000
L48	2	Safety Line 3/8"	32.75 - 33.00	1.0000	1.0000
L48	3	Step Pegs	32.75 - 33.00	1.0000	1.0000
L48	6	HCS 6X12 4AWG(1-5/8)	32.75 - 33.00	1.0000	1.0000
L48	8	HB158-21U6S24-xxM_TMO(1-5/8)	32.75 - 33.00	1.0000	1.0000
L48	23	CU12PSM6P4XXX(1-3/4)	32.75 - 33.00	1.0000	1.0000
L48	39	CCI-085125 (L)	32.75 - 33.00	1.0000	1.0000
L48	40	CCI-085125 (L)	32.75 - 33.00	1.0000	1.0000
L48	41	CCI-085125 (L)	32.75 - 33.00	1.0000	1.0000
L48	42	CCI-085125 (L)	32.75 -	1.0000	1.0000

Tower Section	Feed Line Record No.	Description	Feed Line Segment Elev.	K_a No Ice	K_a Ice
L48	44	CCI-060100 (L)	33.00 32.75 - 33.00	1.0000	1.0000
L48	45	CCI-060100 (L)	32.75 - 33.00	1.0000	1.0000
L48	46	CCI-060100 (L)	32.75 - 33.00	1.0000	1.0000
L49	2	Safety Line 3/8"	19.00 - 32.75	1.0000	1.0000
L49	3	Step Pegs	19.00 - 32.75	1.0000	1.0000
L49	6	HCS 6X12 4AWG(1-5/8)	19.00 - 32.75	1.0000	1.0000
L49	8	HB158-21U6S24- xxM_TMO(1-5/8)	19.00 - 32.75	1.0000	1.0000
L49	23	CU12PSM6P4XXX(1-3/4)	19.00 - 32.75	1.0000	1.0000
L49	39	CCI-085125 (L)	19.00 - 32.75	1.0000	1.0000
L49	40	CCI-085125 (L)	19.00 - 32.75	1.0000	1.0000
L49	41	CCI-085125 (L)	19.00 - 32.75	1.0000	1.0000
L49	42	CCI-085125 (L)	19.00 - 32.75	1.0000	1.0000
L49	44	CCI-060100 (L)	30.50 - 32.75	1.0000	1.0000
L49	45	CCI-060100 (L)	30.50 - 32.75	1.0000	1.0000
L49	46	CCI-060100 (L)	30.50 - 32.75	1.0000	1.0000
L50	2	Safety Line 3/8"	18.00 - 19.00	1.0000	1.0000
L50	3	Step Pegs	18.00 - 19.00	1.0000	1.0000
L50	6	HCS 6X12 4AWG(1-5/8)	18.00 - 19.00	1.0000	1.0000
L50	8	HB158-21U6S24- xxM_TMO(1-5/8)	18.00 - 19.00	1.0000	1.0000
L50	23	CU12PSM6P4XXX(1-3/4)	18.00 - 19.00	1.0000	1.0000
L50	39	CCI-085125 (L)	18.00 - 19.00	1.0000	1.0000
L50	40	CCI-085125 (L)	18.00 - 19.00	1.0000	1.0000
L50	41	CCI-085125 (L)	18.00 - 19.00	1.0000	1.0000
L50	42	CCI-085125 (L)	18.00 - 19.00	1.0000	1.0000
L51	2	Safety Line 3/8"	13.00 - 18.00	1.0000	1.0000
L51	3	Step Pegs	13.00 - 18.00	1.0000	1.0000
L51	6	HCS 6X12 4AWG(1-5/8)	13.00 - 18.00	1.0000	1.0000
L51	8	HB158-21U6S24- xxM_TMO(1-5/8)	13.00 - 18.00	1.0000	1.0000
L51	23	CU12PSM6P4XXX(1-3/4)	13.00 - 18.00	1.0000	1.0000
L51	39	CCI-085125 (L)	13.00 - 18.00	1.0000	1.0000
L51	40	CCI-085125 (L)	13.00 - 18.00	1.0000	1.0000
L51	41	CCI-085125 (L)	13.00 - 18.00	1.0000	1.0000
L51	42	CCI-085125 (L)	13.00 - 18.00	1.0000	1.0000
L52	2	Safety Line 3/8"	8.00 - 13.00	1.0000	1.0000
L52	3	Step Pegs	8.00 - 13.00	1.0000	1.0000

Tower Section	Feed Line Record No.	Description	Feed Line Segment Elev.	K_a No Ice	K_a Ice
L52	6	HCS 6X12 4AWG(1-5/8)	8.00 - 13.00	1.0000	1.0000
L52	8	HB158-21U6S24-xxM_TMO(1-5/8)	8.00 - 13.00	1.0000	1.0000
L52	23	CU12PSM6P4XXXX(1-3/4)	8.00 - 13.00	1.0000	1.0000
L52	39	CCI-085125 (L)	8.00 - 13.00	1.0000	1.0000
L52	40	CCI-085125 (L)	8.00 - 13.00	1.0000	1.0000
L52	41	CCI-085125 (L)	8.00 - 13.00	1.0000	1.0000
L52	42	CCI-085125 (L)	8.00 - 13.00	1.0000	1.0000
L53	2	Safety Line 3/8"	6.42 - 8.00	1.0000	1.0000
L53	3	Step Pegs	6.42 - 8.00	1.0000	1.0000
L53	6	HCS 6X12 4AWG(1-5/8)	6.42 - 8.00	1.0000	1.0000
L53	8	HB158-21U6S24-xxM_TMO(1-5/8)	6.42 - 8.00	1.0000	1.0000
L53	23	CU12PSM6P4XXXX(1-3/4)	6.42 - 8.00	1.0000	1.0000
L53	39	CCI-085125 (L)	6.42 - 8.00	1.0000	1.0000
L53	40	CCI-085125 (L)	6.42 - 8.00	1.0000	1.0000
L53	41	CCI-085125 (L)	6.42 - 8.00	1.0000	1.0000
L53	42	CCI-085125 (L)	6.42 - 8.00	1.0000	1.0000
L54	2	Safety Line 3/8"	6.17 - 6.42	1.0000	1.0000
L54	3	Step Pegs	6.17 - 6.42	1.0000	1.0000
L54	6	HCS 6X12 4AWG(1-5/8)	6.17 - 6.42	1.0000	1.0000
L54	8	HB158-21U6S24-xxM_TMO(1-5/8)	6.17 - 6.42	1.0000	1.0000
L54	23	CU12PSM6P4XXXX(1-3/4)	6.17 - 6.42	1.0000	1.0000
L54	39	CCI-085125 (L)	6.17 - 6.42	1.0000	1.0000
L54	40	CCI-085125 (L)	6.17 - 6.42	1.0000	1.0000
L54	41	CCI-085125 (L)	6.17 - 6.42	1.0000	1.0000
L54	42	CCI-085125 (L)	6.17 - 6.42	1.0000	1.0000
L55	2	Safety Line 3/8"	1.17 - 6.17	1.0000	1.0000
L55	3	Step Pegs	1.17 - 6.17	1.0000	1.0000
L55	6	HCS 6X12 4AWG(1-5/8)	1.17 - 6.17	1.0000	1.0000
L55	8	HB158-21U6S24-xxM_TMO(1-5/8)	1.17 - 6.17	1.0000	1.0000
L55	23	CU12PSM6P4XXXX(1-3/4)	1.17 - 6.17	1.0000	1.0000
L55	39	CCI-085125 (L)	1.17 - 6.17	1.0000	1.0000
L55	40	CCI-085125 (L)	1.17 - 6.17	1.0000	1.0000
L55	41	CCI-085125 (L)	1.17 - 6.17	1.0000	1.0000
L55	42	CCI-085125 (L)	1.17 - 6.17	1.0000	1.0000
L56	2	Safety Line 3/8"	0.00 - 1.17	1.0000	1.0000
L56	3	Step Pegs	0.00 - 1.17	1.0000	1.0000
L56	6	HCS 6X12 4AWG(1-5/8)	0.00 - 1.17	1.0000	1.0000
L56	8	HB158-21U6S24-xxM_TMO(1-5/8)	0.00 - 1.17	1.0000	1.0000
L56	23	CU12PSM6P4XXXX(1-3/4)	0.00 - 1.17	1.0000	1.0000
L56	39	CCI-085125 (L)	0.00 - 1.17	1.0000	1.0000
L56	40	CCI-085125 (L)	0.00 - 1.17	1.0000	1.0000
L56	41	CCI-085125 (L)	0.00 - 1.17	1.0000	1.0000
L56	42	CCI-085125 (L)	0.00 - 1.17	1.0000	1.0000

Effective Width of Flat Linear Attachments / Feed Lines

Tower Section	Attachment Record No.	Description	Attachment Segment Elev.	Ratio Calculation Method	Effective Width Ratio
L6	56	CCI-040075 (W)	155.00 - 155.25	Auto	0.0000
L6	57	CCI-040075 (W)	155.00 - 155.25	Auto	0.0000
L6	58	CCI-040075 (W)	155.00 - 155.25	Auto	0.0000
L7	35	CCI-045100 (L)	154.00 - 154.50	Auto	0.0000
L7	36	CCI-045100 (L)	154.00 - 154.50	Auto	0.0000
L7	37	CCI-045100 (L)	154.00 -	Auto	0.0000

Tower Section	Attachment Record No.	Description	Attachment Segment Elev.	Ratio Calculation Method	Effective Width Ratio
L7	56	CCI-040075 (W)	154.00 - 155.00	Auto	0.0000
L7	57	CCI-040075 (W)	154.00 - 155.00	Auto	0.0000
L7	58	CCI-040075 (W)	154.00 - 155.00	Auto	0.0000
L8	35	CCI-045100 (L)	153.75 - 154.00	Auto	0.0000
L8	36	CCI-045100 (L)	153.75 - 154.00	Auto	0.0000
L8	37	CCI-045100 (L)	153.75 - 154.00	Auto	0.0000
L8	56	CCI-040075 (W)	153.75 - 154.00	Auto	0.0000
L8	57	CCI-040075 (W)	153.75 - 154.00	Auto	0.0000
L8	58	CCI-040075 (W)	153.75 - 154.00	Auto	0.0000
L9	35	CCI-045100 (L)	152.50 - 153.75	Auto	0.0000
L9	36	CCI-045100 (L)	152.50 - 153.75	Auto	0.0000
L9	37	CCI-045100 (L)	152.50 - 153.75	Auto	0.0000
L9	56	CCI-040075 (W)	152.50 - 153.75	Auto	0.0000
L9	57	CCI-040075 (W)	152.50 - 153.75	Auto	0.0000
L9	58	CCI-040075 (W)	152.50 - 153.75	Auto	0.0000
L10	35	CCI-045100 (L)	152.25 - 152.50	Auto	0.0000
L10	36	CCI-045100 (L)	152.25 - 152.50	Auto	0.0000
L10	37	CCI-045100 (L)	152.25 - 152.50	Auto	0.0000
L10	56	CCI-040075 (W)	152.25 - 152.50	Auto	0.0000
L10	57	CCI-040075 (W)	152.25 - 152.50	Auto	0.0000
L10	58	CCI-040075 (W)	152.25 - 152.50	Auto	0.0000
L11	35	CCI-045100 (L)	151.50 - 152.25	Auto	0.0000
L11	36	CCI-045100 (L)	151.50 - 152.25	Auto	0.0000
L11	37	CCI-045100 (L)	151.50 - 152.25	Auto	0.0000
L11	56	CCI-040075 (W)	151.50 - 152.25	Auto	0.0000
L11	57	CCI-040075 (W)	151.50 - 152.25	Auto	0.0000
L11	58	CCI-040075 (W)	151.50 - 152.25	Auto	0.0000
L12	35	CCI-045100 (L)	151.25 - 151.50	Auto	0.0000
L12	36	CCI-045100 (L)	151.25 - 151.50	Auto	0.0000
L12	37	CCI-045100 (L)	151.25 - 151.50	Auto	0.0000
L12	56	CCI-040075 (W)	151.25 - 151.50	Auto	0.0000
L12	57	CCI-040075 (W)	151.25 - 151.50	Auto	0.0000
L12	58	CCI-040075 (W)	151.25 - 151.50	Auto	0.0000
L13	35	CCI-045100 (L)	146.25 -	Auto	0.0000

Tower Section	Attachment Record No.	Description	Attachment Segment Elev.	Ratio Calculation Method	Effective Width Ratio
L13	36	CCI-045100 (L)	146.25 - 151.25	Auto	0.0000
L13	37	CCI-045100 (L)	146.25 - 151.25	Auto	0.0000
L13	56	CCI-040075 (W)	150.25 - 151.25	Auto	0.0000
L13	57	CCI-040075 (W)	150.25 - 151.25	Auto	0.0000
L13	58	CCI-040075 (W)	150.25 - 151.25	Auto	0.0000
L14	35	CCI-045100 (L)	141.25 - 146.25	Auto	0.0000
L14	36	CCI-045100 (L)	141.25 - 146.25	Auto	0.0000
L14	37	CCI-045100 (L)	141.25 - 146.25	Auto	0.0000
L15	35	CCI-045100 (L)	136.25 - 141.25	Auto	0.0000
L15	36	CCI-045100 (L)	136.25 - 141.25	Auto	0.0000
L15	37	CCI-045100 (L)	136.25 - 141.25	Auto	0.0000
L16	35	CCI-045100 (L)	130.00 - 136.25	Auto	0.0000
L16	36	CCI-045100 (L)	130.00 - 136.25	Auto	0.0000
L16	37	CCI-045100 (L)	130.00 - 136.25	Auto	0.0000
L16	52	CCI-040075 (W)	130.00 - 132.50	Auto	0.0000
L16	53	CCI-040075 (W)	130.00 - 132.50	Auto	0.0000
L16	54	CCI-040075 (W)	130.00 - 132.50	Auto	0.0000
L17	35	CCI-045100 (L)	129.00 - 130.00	Auto	0.0000
L17	36	CCI-045100 (L)	129.00 - 130.00	Auto	0.0000
L17	37	CCI-045100 (L)	129.00 - 130.00	Auto	0.0000
L17	52	CCI-040075 (W)	129.00 - 130.00	Auto	0.0000
L17	53	CCI-040075 (W)	129.00 - 130.00	Auto	0.0000
L17	54	CCI-040075 (W)	129.00 - 130.00	Auto	0.0000
L18	35	CCI-045100 (L)	124.00 - 129.00	Auto	0.0000
L18	36	CCI-045100 (L)	124.00 - 129.00	Auto	0.0000
L18	37	CCI-045100 (L)	124.00 - 129.00	Auto	0.0000
L18	52	CCI-040075 (W)	124.00 - 129.00	Auto	0.0000
L18	53	CCI-040075 (W)	124.00 - 129.00	Auto	0.0000
L18	54	CCI-040075 (W)	124.00 - 129.00	Auto	0.0000
L19	31	CCI-060100 (L)	121.42 - 123.92	Auto	0.0000
L19	32	CCI-060100 (L)	121.42 - 123.92	Auto	0.0000
L19	33	CCI-060100 (L)	121.42 - 123.92	Auto	0.0000
L19	35	CCI-045100 (L)	121.42 - 124.00	Auto	0.0000
L19	36	CCI-045100 (L)	121.42 -	Auto	0.0000

Tower Section	Attachment Record No.	Description	Attachment Segment Elev.	Ratio Calculation Method	Effective Width Ratio
L19	37	CCI-045100 (L)	124.00 121.42 - 124.00	Auto	0.0000
L19	52	CCI-040075 (W)	124.00 121.42 - 124.00	Auto	0.0000
L19	53	CCI-040075 (W)	124.00 121.42 - 124.00	Auto	0.0000
L19	54	CCI-040075 (W)	124.00 121.42 - 124.00	Auto	0.0000
L20	31	CCI-060100 (L)	121.42 121.17 - 121.42	Auto	0.0000
L20	32	CCI-060100 (L)	121.42 121.17 - 121.42	Auto	0.0000
L20	33	CCI-060100 (L)	121.42 121.17 - 121.42	Auto	0.0000
L20	35	CCI-045100 (L)	121.42 121.17 - 121.42	Auto	0.0000
L20	36	CCI-045100 (L)	121.42 121.17 - 121.42	Auto	0.0000
L20	37	CCI-045100 (L)	121.42 121.17 - 121.42	Auto	0.0000
L20	52	CCI-040075 (W)	121.42 121.17 - 121.42	Auto	0.0000
L20	53	CCI-040075 (W)	121.42 121.17 - 121.42	Auto	0.0000
L20	54	CCI-040075 (W)	121.42 121.17 - 121.42	Auto	0.0000
L21	31	CCI-060100 (L)	121.17 116.17 - 121.17	Auto	0.0000
L21	32	CCI-060100 (L)	121.17 116.17 - 121.17	Auto	0.0000
L21	33	CCI-060100 (L)	121.17 116.17 - 121.17	Auto	0.0000
L21	35	CCI-045100 (L)	121.17 119.50 - 121.17	Auto	0.0000
L21	36	CCI-045100 (L)	121.17 119.50 - 121.17	Auto	0.0000
L21	37	CCI-045100 (L)	121.17 119.50 - 121.17	Auto	0.0000
L21	52	CCI-040075 (W)	121.17 116.17 - 121.17	Auto	0.0000
L21	53	CCI-040075 (W)	121.17 116.17 - 121.17	Auto	0.0000
L21	54	CCI-040075 (W)	121.17 116.17 - 121.17	Auto	0.0000
L22	31	CCI-060100 (L)	116.17 115.00 - 116.17	Auto	0.0000
L22	32	CCI-060100 (L)	116.17 115.00 - 116.17	Auto	0.0000
L22	33	CCI-060100 (L)	116.17 115.00 - 116.17	Auto	0.0000
L22	52	CCI-040075 (W)	116.17 115.00 - 116.17	Auto	0.0000
L22	53	CCI-040075 (W)	116.17 115.00 - 116.17	Auto	0.0000
L22	54	CCI-040075 (W)	116.17 115.00 - 116.17	Auto	0.0000
L23	31	CCI-060100 (L)	115.00 113.75 - 115.00	Auto	0.0000
L23	32	CCI-060100 (L)	115.00 113.75 - 115.00	Auto	0.0000
L23	33	CCI-060100 (L)	115.00 113.75 - 115.00	Auto	0.0000
L23	52	CCI-040075 (W)	115.00 113.75 - 115.00	Auto	0.0000
L23	53	CCI-040075 (W)	115.00 113.75 - 115.00	Auto	0.0000
L23	54	CCI-040075 (W)	115.00 113.75 - 115.00	Auto	0.0000

Tower Section	Attachment Record No.	Description	Attachment Segment Elev.	Ratio Calculation Method	Effective Width Ratio
L24	31	CCI-060100 (L)	115.00 - 113.50 - 113.75	Auto	0.0000
L24	32	CCI-060100 (L)	113.50 - 113.75	Auto	0.0000
L24	33	CCI-060100 (L)	113.50 - 113.75	Auto	0.0000
L24	52	CCI-040075 (W)	113.50 - 113.75	Auto	0.0000
L24	53	CCI-040075 (W)	113.50 - 113.75	Auto	0.0000
L24	54	CCI-040075 (W)	113.50 - 113.75	Auto	0.0000
L25	31	CCI-060100 (L)	108.50 - 113.50	Auto	0.0000
L25	32	CCI-060100 (L)	108.50 - 113.50	Auto	0.0000
L25	33	CCI-060100 (L)	108.50 - 113.50	Auto	0.0000
L25	52	CCI-040075 (W)	112.50 - 113.50	Auto	0.0000
L25	53	CCI-040075 (W)	112.50 - 113.50	Auto	0.0000
L25	54	CCI-040075 (W)	112.50 - 113.50	Auto	0.0000
L26	31	CCI-060100 (L)	103.50 - 108.50	Auto	0.0000
L26	32	CCI-060100 (L)	103.50 - 108.50	Auto	0.0000
L26	33	CCI-060100 (L)	103.50 - 108.50	Auto	0.0000
L27	31	CCI-060100 (L)	95.00 - 103.50	Auto	0.0000
L27	32	CCI-060100 (L)	95.00 - 103.50	Auto	0.0000
L27	33	CCI-060100 (L)	95.00 - 103.50	Auto	0.0000
L27	48	CCI-060100 (L)	95.00 - 101.67	Auto	0.0000
L27	49	CCI-060100 (L)	95.00 - 101.67	Auto	0.0000
L27	50	CCI-060100 (L)	95.00 - 101.67	Auto	0.0000
L28	31	CCI-060100 (L)	94.00 - 95.00	Auto	0.0000
L28	32	CCI-060100 (L)	94.00 - 95.00	Auto	0.0000
L28	33	CCI-060100 (L)	94.00 - 95.00	Auto	0.0000
L28	48	CCI-060100 (L)	94.00 - 95.00	Auto	0.0000
L28	49	CCI-060100 (L)	94.00 - 95.00	Auto	0.0000
L28	50	CCI-060100 (L)	94.00 - 95.00	Auto	0.0000
L29	31	CCI-060100 (L)	91.40 - 94.00	Auto	0.0000
L29	32	CCI-060100 (L)	91.40 - 94.00	Auto	0.0000
L29	33	CCI-060100 (L)	91.40 - 94.00	Auto	0.0000
L29	48	CCI-060100 (L)	91.40 - 94.00	Auto	0.0000
L29	49	CCI-060100 (L)	91.40 - 94.00	Auto	0.0000
L29	50	CCI-060100 (L)	91.40 - 94.00	Auto	0.0000
L30	31	CCI-060100 (L)	91.15 -	Auto	0.0000

Tower Section	Attachment Record No.	Description	Attachment Segment Elev.	Ratio Calculation Method	Effective Width Ratio
L30	32	CCI-060100 (L)	91.40	Auto	0.0000
L30	33	CCI-060100 (L)	91.15 - 91.40	Auto	0.0000
L30	48	CCI-060100 (L)	91.15 - 91.40	Auto	0.0000
L30	49	CCI-060100 (L)	91.15 - 91.40	Auto	0.0000
L30	50	CCI-060100 (L)	91.15 - 91.40	Auto	0.0000
L31	31	CCI-060100 (L)	91.00 - 91.15	Auto	0.0000
L31	32	CCI-060100 (L)	91.00 - 91.15	Auto	0.0000
L31	33	CCI-060100 (L)	91.00 - 91.15	Auto	0.0000
L31	48	CCI-060100 (L)	91.00 - 91.15	Auto	0.0000
L31	49	CCI-060100 (L)	91.00 - 91.15	Auto	0.0000
L31	50	CCI-060100 (L)	91.00 - 91.15	Auto	0.0000
L32	31	CCI-060100 (L)	88.89 - 91.00	Auto	0.0000
L32	32	CCI-060100 (L)	88.89 - 91.00	Auto	0.0000
L32	33	CCI-060100 (L)	88.89 - 91.00	Auto	0.0000
L32	48	CCI-060100 (L)	86.00 - 91.00	Auto	0.0000
L32	49	CCI-060100 (L)	86.00 - 91.00	Auto	0.0000
L32	50	CCI-060100 (L)	86.00 - 91.00	Auto	0.0000
L33	48	CCI-060100 (L)	81.00 - 86.00	Auto	0.0000
L33	49	CCI-060100 (L)	81.00 - 86.00	Auto	0.0000
L33	50	CCI-060100 (L)	81.00 - 86.00	Auto	0.0000
L34	48	CCI-060100 (L)	76.00 - 81.00	Auto	0.0000
L34	49	CCI-060100 (L)	76.00 - 81.00	Auto	0.0000
L34	50	CCI-060100 (L)	76.00 - 81.00	Auto	0.0000
L35	48	CCI-060100 (L)	71.00 - 76.00	Auto	0.0000
L35	49	CCI-060100 (L)	71.00 - 76.00	Auto	0.0000
L35	50	CCI-060100 (L)	71.00 - 76.00	Auto	0.0000
L36	48	CCI-060100 (L)	66.00 - 71.00	Auto	0.0000
L36	49	CCI-060100 (L)	66.00 - 71.00	Auto	0.0000
L36	50	CCI-060100 (L)	66.00 - 71.00	Auto	0.0000
L37	44	CCI-060100 (L)	63.75 - 65.50	Auto	0.0000
L37	45	CCI-060100 (L)	63.75 - 65.50	Auto	0.0000
L37	46	CCI-060100 (L)	63.75 - 65.50	Auto	0.0000
L37	48	CCI-060100 (L)	63.75 - 66.00	Auto	0.0000
L37	49	CCI-060100 (L)	63.75 -	Auto	0.0000

Tower Section	Attachment Record No.	Description	Attachment Segment Elev.	Ratio Calculation Method	Effective Width Ratio
L37	50	CCI-060100 (L)	66.00 63.75 - 66.00	Auto	0.0000
L38	44	CCI-060100 (L)	63.50 - 63.75	Auto	0.0000
L38	45	CCI-060100 (L)	63.50 - 63.75	Auto	0.0000
L38	46	CCI-060100 (L)	63.50 - 63.75	Auto	0.0000
L38	48	CCI-060100 (L)	63.50 - 63.75	Auto	0.0000
L38	49	CCI-060100 (L)	63.50 - 63.75	Auto	0.0000
L38	50	CCI-060100 (L)	63.50 - 63.75	Auto	0.0000
L39	44	CCI-060100 (L)	58.50 - 63.50	Auto	0.0000
L39	45	CCI-060100 (L)	58.50 - 63.50	Auto	0.0000
L39	46	CCI-060100 (L)	58.50 - 63.50	Auto	0.0000
L39	48	CCI-060100 (L)	61.67 - 63.50	Auto	0.0000
L39	49	CCI-060100 (L)	61.67 - 63.50	Auto	0.0000
L39	50	CCI-060100 (L)	61.67 - 63.50	Auto	0.0000
L40	27	CCI-045100 (L)	51.00 - 53.92	Auto	0.0000
L40	28	CCI-045100 (L)	51.00 - 53.92	Auto	0.0000
L40	29	CCI-045100 (L)	51.00 - 53.92	Auto	0.0000
L40	44	CCI-060100 (L)	51.00 - 58.50	Auto	0.0000
L40	45	CCI-060100 (L)	51.00 - 58.50	Auto	0.0000
L40	46	CCI-060100 (L)	51.00 - 58.50	Auto	0.0000
L41	27	CCI-045100 (L)	50.00 - 51.00	Auto	0.0000
L41	28	CCI-045100 (L)	50.00 - 51.00	Auto	0.0000
L41	29	CCI-045100 (L)	50.00 - 51.00	Auto	0.0000
L41	44	CCI-060100 (L)	50.00 - 51.00	Auto	0.0000
L41	45	CCI-060100 (L)	50.00 - 51.00	Auto	0.0000
L41	46	CCI-060100 (L)	50.00 - 51.00	Auto	0.0000
L42	27	CCI-045100 (L)	45.00 - 50.00	Auto	0.0000
L42	28	CCI-045100 (L)	45.00 - 50.00	Auto	0.0000
L42	29	CCI-045100 (L)	45.00 - 50.00	Auto	0.0000
L42	44	CCI-060100 (L)	45.00 - 50.00	Auto	0.0000
L42	45	CCI-060100 (L)	45.00 - 50.00	Auto	0.0000
L42	46	CCI-060100 (L)	45.00 - 50.00	Auto	0.0000
L43	27	CCI-045100 (L)	40.42 - 45.00	Auto	0.0000
L43	28	CCI-045100 (L)	40.42 - 45.00	Auto	0.0000
L43	29	CCI-045100 (L)	40.42 -	Auto	0.0000

Tower Section	Attachment Record No.	Description	Attachment Segment Elev.	Ratio Calculation Method	Effective Width Ratio
L43	44	CCI-060100 (L)	45.00 40.42 - 45.00	Auto	0.0000
L43	45	CCI-060100 (L)	45.00 40.42 - 45.00	Auto	0.0000
L43	46	CCI-060100 (L)	45.00 40.42 - 45.00	Auto	0.0000
L44	27	CCI-045100 (L)	40.42 40.17 - 40.42	Auto	0.0000
L44	28	CCI-045100 (L)	40.42 40.17 - 40.42	Auto	0.0000
L44	29	CCI-045100 (L)	40.42 40.17 - 40.42	Auto	0.0000
L44	44	CCI-060100 (L)	40.42 40.17 - 40.42	Auto	0.0000
L44	45	CCI-060100 (L)	40.42 40.17 - 40.42	Auto	0.0000
L44	46	CCI-060100 (L)	40.42 40.17 - 40.42	Auto	0.0000
L45	27	CCI-045100 (L)	40.00 - 40.17	Auto	0.0000
L45	28	CCI-045100 (L)	40.00 - 40.17	Auto	0.0000
L45	29	CCI-045100 (L)	40.00 - 40.17	Auto	0.0000
L45	44	CCI-060100 (L)	40.00 - 40.17	Auto	0.0000
L45	45	CCI-060100 (L)	40.00 - 40.17	Auto	0.0000
L45	46	CCI-060100 (L)	40.00 - 40.17	Auto	0.0000
L46	27	CCI-045100 (L)	40.00 38.92 - 40.00	Auto	0.0000
L46	28	CCI-045100 (L)	40.00 38.92 - 40.00	Auto	0.0000
L46	29	CCI-045100 (L)	40.00 38.92 - 40.00	Auto	0.0000
L46	39	CCI-085125 (L)	37.42 35.00 -	Auto	0.0000
L46	40	CCI-085125 (L)	37.42 35.00 -	Auto	0.0000
L46	41	CCI-085125 (L)	37.42 35.00 -	Auto	0.0000
L46	42	CCI-085125 (L)	37.42 35.00 -	Auto	0.0000
L46	44	CCI-060100 (L)	37.42 35.00 -	Auto	0.0000
L46	45	CCI-060100 (L)	37.42 35.00 -	Auto	0.0000
L46	46	CCI-060100 (L)	37.42 35.00 -	Auto	0.0000
L47	39	CCI-085125 (L)	35.00 33.00 -	Auto	0.0000
L47	40	CCI-085125 (L)	35.00 33.00 -	Auto	0.0000
L47	41	CCI-085125 (L)	35.00 33.00 -	Auto	0.0000
L47	42	CCI-085125 (L)	35.00 33.00 -	Auto	0.0000
L47	44	CCI-060100 (L)	35.00 33.00 -	Auto	0.0000
L47	45	CCI-060100 (L)	35.00 33.00 -	Auto	0.0000
L47	46	CCI-060100 (L)	35.00 33.00 -	Auto	0.0000
L48	39	CCI-085125 (L)	33.00 32.75 -	Auto	0.0000
L48	40	CCI-085125 (L)	33.00 32.75 -	Auto	0.0000

Tower Section	Attachment Record No.	Description	Attachment Segment Elev.	Ratio Calculation Method	Effective Width Ratio
L48	41	CCI-085125 (L)	33.00 32.75 - 33.00	Auto	0.0000
L48	42	CCI-085125 (L)	32.75 - 33.00	Auto	0.0000
L48	44	CCI-060100 (L)	32.75 - 33.00	Auto	0.0000
L48	45	CCI-060100 (L)	32.75 - 33.00	Auto	0.0000
L48	46	CCI-060100 (L)	32.75 - 33.00	Auto	0.0000
L49	39	CCI-085125 (L)	19.00 - 32.75	Auto	0.0000
L49	40	CCI-085125 (L)	19.00 - 32.75	Auto	0.0000
L49	41	CCI-085125 (L)	19.00 - 32.75	Auto	0.0000
L49	42	CCI-085125 (L)	19.00 - 32.75	Auto	0.0000
L49	44	CCI-060100 (L)	30.50 - 32.75	Auto	0.0000
L49	45	CCI-060100 (L)	30.50 - 32.75	Auto	0.0000
L49	46	CCI-060100 (L)	30.50 - 32.75	Auto	0.0000
L50	39	CCI-085125 (L)	18.00 - 19.00	Auto	0.0000
L50	40	CCI-085125 (L)	18.00 - 19.00	Auto	0.0000
L50	41	CCI-085125 (L)	18.00 - 19.00	Auto	0.0000
L50	42	CCI-085125 (L)	18.00 - 19.00	Auto	0.0000
L51	39	CCI-085125 (L)	13.00 - 18.00	Auto	0.0000
L51	40	CCI-085125 (L)	13.00 - 18.00	Auto	0.0000
L51	41	CCI-085125 (L)	13.00 - 18.00	Auto	0.0000
L51	42	CCI-085125 (L)	13.00 - 18.00	Auto	0.0000
L52	39	CCI-085125 (L)	8.00 - 13.00	Auto	0.0000
L52	40	CCI-085125 (L)	8.00 - 13.00	Auto	0.0000
L52	41	CCI-085125 (L)	8.00 - 13.00	Auto	0.0000
L52	42	CCI-085125 (L)	8.00 - 13.00	Auto	0.0000
L53	39	CCI-085125 (L)	6.42 - 8.00	Auto	0.0000
L53	40	CCI-085125 (L)	6.42 - 8.00	Auto	0.0000
L53	41	CCI-085125 (L)	6.42 - 8.00	Auto	0.0000
L53	42	CCI-085125 (L)	6.42 - 8.00	Auto	0.0000
L54	39	CCI-085125 (L)	6.17 - 6.42	Auto	0.0000
L54	40	CCI-085125 (L)	6.17 - 6.42	Auto	0.0000
L54	41	CCI-085125 (L)	6.17 - 6.42	Auto	0.0000
L54	42	CCI-085125 (L)	6.17 - 6.42	Auto	0.0000
L55	39	CCI-085125 (L)	1.17 - 6.17	Auto	0.0000
L55	40	CCI-085125 (L)	1.17 - 6.17	Auto	0.0000
L55	41	CCI-085125 (L)	1.17 - 6.17	Auto	0.0000
L55	42	CCI-085125 (L)	1.17 - 6.17	Auto	0.0000
L56	39	CCI-085125 (L)	0.00 - 1.17	Auto	0.0000
L56	40	CCI-085125 (L)	0.00 - 1.17	Auto	0.0000
L56	41	CCI-085125 (L)	0.00 - 1.17	Auto	0.0000
L56	42	CCI-085125 (L)	0.00 - 1.17	Auto	0.0000

Discrete Tower Loads

Description	Face or Leg	Offset Type	Offsets: Horz Lateral Vert ft ft ft	Azimuth Adjustment °	Placement ft	C _A A _A		Weight K
						Front	Side	

3' x 2" Pipe Mount	A	From Leg	3.00 0.00 0.00	0.0000	185.00	No Ice 1/2" Ice 1" Ice	0.58 0.77 0.97	0.58 0.77 0.97
3' x 2" Pipe Mount	B	From Leg	3.00 0.00 0.00	0.0000	185.00	No Ice 1/2" Ice 1" Ice	0.58 0.77 0.97	0.58 0.77 0.97
3' x 2" Pipe Mount	C	From Leg	3.00 0.00 0.00	0.0000	185.00	No Ice 1/2" Ice 1" Ice	0.58 0.77 0.97	0.58 0.77 0.97
Side Arm Mount [SO 701-3]	A	None		0.0000	185.00	No Ice 1/2" Ice 1" Ice	3.02 4.18 5.33	3.02 4.18 5.33

APXVAARR24_43-U-NA20	A	From Leg	4.00 0.00 0.00	0.0000	183.00	No Ice 1/2" Ice 1" Ice	14.67 15.43 16.21	5.32 5.99 6.68
APXVAARR24_43-U-NA20	B	From Leg	4.00 0.00 0.00	0.0000	183.00	No Ice 1/2" Ice 1" Ice	14.67 15.43 16.21	5.32 5.99 6.68
APXVAARR24_43-U-NA20	C	From Leg	4.00 0.00 0.00	0.0000	183.00	No Ice 1/2" Ice 1" Ice	14.67 15.43 16.21	5.32 5.99 6.68
RADIO 4449 B12/B71	A	From Leg	4.00 0.00 0.00	0.0000	183.00	No Ice 1/2" Ice 1" Ice	1.65 1.81 1.98	1.16 1.30 1.45
RADIO 4449 B12/B71	B	From Leg	4.00 0.00 0.00	0.0000	183.00	No Ice 1/2" Ice 1" Ice	1.65 1.81 1.98	1.16 1.30 1.45
RADIO 4449 B12/B71	C	From Leg	4.00 0.00 0.00	0.0000	183.00	No Ice 1/2" Ice 1" Ice	1.65 1.81 1.98	1.16 1.30 1.45
Site Pro 1 RMQP-496-HK	A	None		0.0000	183.00	No Ice 1/2" Ice 1" Ice	38.42 50.04 61.66	38.42 50.04 61.66
*								
AIR6449 B41_T-MOBILE	A	From Leg	4.00 0.00 0.00	0.0000	183.00	No Ice 1/2" Ice 1" Ice	5.27 5.70 6.14	2.03 2.36 2.70
AIR6449 B41_T-MOBILE	B	From Leg	4.00 0.00 0.00	0.0000	183.00	No Ice 1/2" Ice 1" Ice	5.27 5.70 6.14	2.03 2.36 2.70
AIR6449 B41_T-MOBILE	C	From Leg	4.00 0.00 0.00	0.0000	183.00	No Ice 1/2" Ice 1" Ice	5.27 5.70 6.14	2.03 2.36 2.70
RADIO 4460 B2/B25 B66_TMO	A	From Leg	4.00 0.00 0.00	0.0000	183.00	No Ice 1/2" Ice 1" Ice	2.14 2.32 2.51	1.69 1.85 2.02
RADIO 4460 B2/B25 B66_TMO	B	From Leg	4.00 0.00 0.00	0.0000	183.00	No Ice 1/2" Ice 1" Ice	2.14 2.32 2.51	1.69 1.85 2.02
RADIO 4460 B2/B25 B66_TMO	C	From Leg	4.00 0.00 0.00	0.0000	183.00	No Ice 1/2" Ice 1" Ice	2.14 2.32 2.51	1.69 1.85 2.02

DMP65R-BU6D	A	From Leg	4.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	11.93 12.68 13.45	4.48 5.12 5.78
DMP65R-BU6D	B	From Leg	4.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	11.93 12.68 13.45	4.48 5.12 5.78
DMP65R-BU6D	C	From Leg	4.00 0.00 0.00	0.0000	174.00	No Ice	11.93	4.48

Description	Face or Leg	Offset Type	Offsets: Horz Lateral Vert ft ft ft	Azimuth Adjustment °	Placement ft	C _{AA} Front ft ²	C _{AA} Side ft ²	Weight K
RRUS-32 B30	A	From Leg	0.00 0.00 2.00 0.00 0.00	0.0000	174.00	1/2" Ice 1" Ice No Ice 1/2" Ice 1" Ice	12.68 13.45 3.31 3.56 3.81	5.12 5.78 2.42 2.64 2.86
RRUS-32 B30	B	From Leg	0.00 0.00 2.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice No Ice 1/2" Ice	3.31 3.56 3.81 3.31 3.56	0.08 0.10 0.14 0.08 0.10
RRUS-32 B30	C	From Leg	0.00 0.00 2.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice No Ice 1/2" Ice	3.31 3.81 3.81 3.31 3.56	0.08 0.14 0.14 0.08 0.10
RRUS 4449 B5/B12	A	From Leg	2.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	1.97 2.14 2.33	1.41 1.56 1.73
RRUS 4449 B5/B12	B	From Leg	2.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	1.97 2.14 2.33	0.07 0.09 0.11
RRUS 4449 B5/B12	C	From Leg	2.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	1.97 2.14 2.33	0.07 0.09 0.11
RRUS 4478 B14_CCIV2	A	From Leg	2.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	2.02 2.20 2.39	1.25 1.40 1.55
RRUS 4478 B14_CCIV2	B	From Leg	2.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	2.02 2.20 2.39	0.06 0.09 0.10
RRUS 4478 B14_CCIV2	C	From Leg	2.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	2.02 2.20 2.39	0.06 0.08 0.10
DC6-48-60-18-8F	A	From Leg	1.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	0.92 1.46 1.64	0.92 1.46 1.64
DC6-48-60-18-8F	B	From Leg	1.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	0.92 1.46 1.64	0.02 0.04 0.06
DC9-48-60-24-8C-EV	C	From Leg	1.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	2.74 2.96 3.20	4.78 5.06 5.35
*								
AIR 6419 B77G	A	From Leg	4.00 0.00 2.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	4.64 5.11 5.59	1.87 2.23 2.62
AIR 6419 B77G	B	From Leg	4.00 0.00 2.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	4.64 5.11 5.59	1.87 2.23 2.62
AIR 6419 B77G	C	From Leg	4.00 0.00 2.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	4.64 5.11 5.59	1.87 2.23 0.09
AIR 6449 B77D	A	From Leg	4.00 0.00 -2.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	3.64 4.00 4.37	1.72 2.02 2.33
AIR 6449 B77D	B	From Leg	4.00 0.00 -2.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	3.64 4.00 4.37	0.08 0.11 0.14
AIR 6449 B77D	C	From Leg	4.00 0.00 -2.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	3.64 4.00 4.37	1.72 2.02 2.33
QD6616-7	A	From Leg	4.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	13.59 14.40 15.24	5.92 6.63 7.36
QD6616-7	B	From Leg	4.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	13.59 14.40 15.24	0.13 0.21 0.30
QD6616-7	C	From Leg	4.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice	13.59 14.40	5.92 6.63
								0.13 0.21 0.30

Description	Face or Leg	Offset Type	Offsets: Horz Lateral Vert ft ft ft	Azimuth Adjustment °	Placement ft	C _{AA} Front	C _{AA} Side	Weight K
RRUS 32 B66A	A	From Leg	0.00 2.00 0.00 0.00	0.0000	174.00	1" Ice No Ice 1/2" Ice 1" Ice	15.24 2.86 3.09 3.32	7.36 1.78 1.97 2.17
RRUS 32 B66A	B	From Leg	2.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	2.86 3.09 3.32	1.78 1.97 2.17
RRUS 32 B66A	C	From Leg	2.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	2.86 3.09 3.32	1.78 1.97 2.17
RRUS 4415 B25_CCIV2	A	From Leg	2.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	1.84 2.01 2.19	0.82 0.94 1.07
RRUS 4415 B25_CCIV2	B	From Leg	2.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	1.84 2.01 2.19	0.82 0.94 1.07
RRUS 4415 B25_CCIV2	C	From Leg	2.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	1.84 2.01 2.19	0.82 0.94 1.07
RRUS E2 B29	A	From Leg	2.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	3.15 3.36 3.59	1.29 1.44 1.60
RRUS E2 B29	B	From Leg	2.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	3.15 3.36 3.59	1.29 1.44 1.60
RRUS E2 B29	C	From Leg	2.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	3.15 3.36 3.59	1.29 1.44 1.60
(2) 6' x 2" Mount Pipe	A	From Leg	2.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	1.43 1.92 2.29	1.43 1.92 2.29
(2) 6' x 2" Mount Pipe	B	From Leg	2.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	1.43 1.92 2.29	1.43 1.92 2.29
(2) 6' x 2" Mount Pipe	C	From Leg	2.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	1.43 1.92 2.29	1.43 1.92 2.29
Site Pro 1 VFA14-WLL-30120	A	From Leg	2.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	28.80 42.80 55.40	12.10 18.50 24.46
Site Pro 1 VFA14-WLL-30120	B	From Leg	2.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	28.80 42.80 55.40	12.10 18.50 24.46
Site Pro 1 VFA14-WLL-30120	C	From Leg	2.00 0.00 0.00	0.0000	174.00	No Ice 1/2" Ice 1" Ice	28.80 42.80 55.40	12.10 18.50 24.46
Sabre C10899050	A	None		0.0000	174.00	No Ice 1/2" Ice 1" Ice	6.67 7.70 8.74	0.68 0.88 1.08

*								
MX08FRO665-20 w/ Mount Pipe	A	From Leg	4.00 0.00 0.00	0.0000	165.00	No Ice 1/2" Ice 1" Ice	8.01 8.52 9.04	4.23 4.69 5.16
MX08FRO665-20 w/ Mount Pipe	B	From Leg	4.00 0.00 0.00	0.0000	165.00	No Ice 1/2" Ice 1" Ice	8.01 8.52 9.04	4.23 4.69 5.16
MX08FRO665-20 w/ Mount Pipe	C	From Leg	4.00 0.00 0.00	0.0000	165.00	No Ice 1/2" Ice 1" Ice	8.01 8.52 9.04	4.23 4.69 5.16
TA08025-B604	A	From Leg	4.00 0.00 0.00	0.0000	165.00	No Ice 1/2" Ice 1" Ice	1.96 2.14 2.32	0.98 1.11 1.25
TA08025-B604	B	From Leg	4.00 0.00	0.0000	165.00	No Ice 1/2" Ice	1.96 2.14	0.98 1.11

Description	Face or Leg	Offset Type	Offsets: Horz Lateral Vert ft ft ft	Azimuth Adjustment °	Placement ft	C _{AA} _{Front}	C _{AA} _{Side}	Weight K
TA08025-B604	C	From Leg	0.00 4.00 0.00 0.00	0.0000	165.00	1" Ice No Ice 1/2" Ice 1" Ice	2.32 1.96 2.14 2.32	1.25 0.98 1.11 1.25
TA08025-B605	A	From Leg	4.00 0.00 0.00	0.0000	165.00	No Ice 1/2" Ice 1" Ice	1.96 2.14 2.32	0.08 1.13 1.25
TA08025-B605	B	From Leg	4.00 0.00 0.00	0.0000	165.00	No Ice 1/2" Ice 1" Ice	1.96 2.14 2.32	0.08 1.27 1.41
TA08025-B605	C	From Leg	4.00 0.00 0.00	0.0000	165.00	No Ice 1/2" Ice 1" Ice	1.96 2.14 2.32	0.08 1.13 1.41
RDIDC-9181-PF-48	A	From Leg	4.00 0.00 0.00	0.0000	165.00	No Ice 1/2" Ice 1" Ice	2.01 2.19 2.37	0.02 1.31 1.46
(2) 8' x 2" Mount Pipe	A	From Leg	4.00 0.00 0.00	0.0000	165.00	No Ice 1/2" Ice 1" Ice	1.90 2.73 3.40	0.03 2.73 3.40
(2) 8' x 2" Mount Pipe	B	From Leg	4.00 0.00 0.00	0.0000	165.00	No Ice 1/2" Ice 1" Ice	1.90 2.73 3.40	0.03 2.73 3.40
(2) 8' x 2" Mount Pipe	C	From Leg	4.00 0.00 0.00	0.0000	165.00	No Ice 1/2" Ice 1" Ice	1.90 2.73 3.40	0.03 2.73 3.40
Commscope MC-PK8-DSH	A	None		0.0000	165.00	No Ice 1/2" Ice 1" Ice	34.24 62.95 91.66	34.24 62.95 91.66

SBNHH-1D65B w/ Mount Pipe	A	From Leg	4.00 0.00 0.00	0.0000	155.00	No Ice 1/2" Ice 1" Ice	4.09 4.49 4.89	3.30 3.68 4.07
SBNHH-1D65B w/ Mount Pipe	B	From Leg	4.00 0.00 0.00	0.0000	155.00	No Ice 1/2" Ice 1" Ice	4.09 4.49 4.89	3.30 3.68 4.07
SBNHH-1D65B w/ Mount Pipe	C	From Leg	4.00 0.00 0.00	0.0000	155.00	No Ice 1/2" Ice 1" Ice	4.09 4.49 4.89	3.30 3.68 4.07
(2) SBNHH-1D65B	A	From Leg	4.00 0.00 0.00	0.0000	155.00	No Ice 1/2" Ice 1" Ice	4.16 4.57 4.99	2.49 2.88 3.27
(2) SBNHH-1D65B	B	From Leg	4.00 0.00 0.00	0.0000	155.00	No Ice 1/2" Ice 1" Ice	4.16 4.57 4.99	2.49 2.88 3.27
(2) SBNHH-1D65B	C	From Leg	4.00 0.00 0.00	0.0000	155.00	No Ice 1/2" Ice 1" Ice	4.16 4.57 4.99	2.49 2.88 3.27
DB-T1-6Z-8AB-0Z	B	From Leg	1.00 0.00 0.00	0.0000	155.00	No Ice 1/2" Ice 1" Ice	4.80 5.07 5.35	2.00 2.19 2.39
DB-T1-6Z-8AB-0Z	C	From Leg	1.00 0.00 0.00	0.0000	155.00	No Ice 1/2" Ice 1" Ice	4.80 5.07 5.35	2.00 2.19 2.39
Commscope BSAMNT-SBS-1-2	A	From Leg	4.00 0.00 0.00	0.0000	155.00	No Ice 1/2" Ice 1" Ice	1.32 1.58 1.84	1.32 1.58 1.84
Commscope BSAMNT-SBS-1-2	B	From Leg	4.00 0.00 0.00	0.0000	155.00	No Ice 1/2" Ice 1" Ice	1.32 1.58 1.84	1.32 1.58 1.84
Commscope BSAMNT-SBS-1-2	C	From Leg	4.00 0.00 0.00	0.0000	155.00	No Ice 1/2" Ice 1" Ice	1.32 1.58 1.84	1.32 1.58 1.84
4' x 2" Pipe Mount	A	From Leg	1.00 0.00 0.00	0.0000	165.00	No Ice 1/2" Ice 1" Ice	0.79 1.03 1.28	0.03 0.04 0.04

Description	Face or Leg	Offset Type	Offsets: Horz Lateral Vert ft ft ft	Azimuth Adjustment °	Placement ft	C _{AA} _{Front}	C _{AA} _{Side}	Weight K
4' x 2" Pipe Mount	B	From Leg	1.00 0.00 0.00	0.0000	165.00	No Ice 1/2" Ice 1" Ice	0.79 1.03 1.28	0.79 1.03 0.04
(2) 6' x 2" Mount Pipe	A	From Leg	4.00 0.00 0.00	0.0000	165.00	No Ice 1/2" Ice 1" Ice	1.43 1.92 2.29	1.43 1.92 0.02
(2) 6' x 2" Mount Pipe	B	From Leg	4.00 0.00 0.00	0.0000	165.00	No Ice 1/2" Ice 1" Ice	1.43 1.92 2.29	1.43 1.92 0.05
(2) 6' x 2" Mount Pipe	C	From Leg	4.00 0.00 0.00	0.0000	165.00	No Ice 1/2" Ice 1" Ice	1.43 1.92 2.29	1.43 1.92 0.05
Platform Mount [LP 403-1]	A	None		0.0000	155.00	No Ice 1/2" Ice 1" Ice	18.94 23.31 27.74	18.94 23.31 1.50 1.90 2.37
*								
MT6407-77A	A	From Leg	4.00 0.00 0.00	0.0000	155.00	No Ice 1/2" Ice 1" Ice	4.69 4.98 5.28	1.84 2.06 2.29
MT6407-77A	B	From Leg	4.00 0.00 0.00	0.0000	155.00	No Ice 1/2" Ice 1" Ice	4.69 4.98 5.28	1.84 2.06 0.11
MT6407-77A	C	From Leg	4.00 0.00 0.00	0.0000	155.00	No Ice 1/2" Ice 1" Ice	4.69 4.98 5.28	1.84 2.06 0.14
RFV01U-D1A	A	From Leg	4.00 0.00 0.00	0.0000	155.00	No Ice 1/2" Ice 1" Ice	1.88 2.05 2.22	1.25 1.39 1.54
RFV01U-D1A	B	From Leg	4.00 0.00 0.00	0.0000	155.00	No Ice 1/2" Ice 1" Ice	1.88 2.05 2.22	0.08 0.10 0.12
RFV01U-D1A	C	From Leg	4.00 0.00 0.00	0.0000	155.00	No Ice 1/2" Ice 1" Ice	1.88 2.05 2.22	1.25 1.39 1.54
RFV01U-D2A	A	From Leg	4.00 0.00 0.00	0.0000	155.00	No Ice 1/2" Ice 1" Ice	1.88 2.05 2.22	1.01 1.14 1.28
RFV01U-D2A	B	From Leg	4.00 0.00 0.00	0.0000	155.00	No Ice 1/2" Ice 1" Ice	1.88 2.05 2.22	0.07 0.09 0.11
RFV01U-D2A	C	From Leg	4.00 0.00 0.00	0.0000	155.00	No Ice 1/2" Ice 1" Ice	1.88 2.05 2.22	1.01 1.14 1.28

Load Combinations

Comb. No.	Description
1	Dead Only
2	1.2 Dead+1.0 Wind 0 deg - No Ice
3	0.9 Dead+1.0 Wind 0 deg - No Ice
4	1.2 Dead+1.0 Wind 30 deg - No Ice
5	0.9 Dead+1.0 Wind 30 deg - No Ice
6	1.2 Dead+1.0 Wind 60 deg - No Ice
7	0.9 Dead+1.0 Wind 60 deg - No Ice
8	1.2 Dead+1.0 Wind 90 deg - No Ice
9	0.9 Dead+1.0 Wind 90 deg - No Ice
10	1.2 Dead+1.0 Wind 120 deg - No Ice
11	0.9 Dead+1.0 Wind 120 deg - No Ice
12	1.2 Dead+1.0 Wind 150 deg - No Ice
13	0.9 Dead+1.0 Wind 150 deg - No Ice

Comb. No.	Description
14	1.2 Dead+1.0 Wind 180 deg - No Ice
15	0.9 Dead+1.0 Wind 180 deg - No Ice
16	1.2 Dead+1.0 Wind 210 deg - No Ice
17	0.9 Dead+1.0 Wind 210 deg - No Ice
18	1.2 Dead+1.0 Wind 240 deg - No Ice
19	0.9 Dead+1.0 Wind 240 deg - No Ice
20	1.2 Dead+1.0 Wind 270 deg - No Ice
21	0.9 Dead+1.0 Wind 270 deg - No Ice
22	1.2 Dead+1.0 Wind 300 deg - No Ice
23	0.9 Dead+1.0 Wind 300 deg - No Ice
24	1.2 Dead+1.0 Wind 330 deg - No Ice
25	0.9 Dead+1.0 Wind 330 deg - No Ice
26	1.2 Dead+1.0 Ice+1.0 Temp
27	1.2 Dead+1.0 Wind 0 deg+1.0 Ice+1.0 Temp
28	1.2 Dead+1.0 Wind 30 deg+1.0 Ice+1.0 Temp
29	1.2 Dead+1.0 Wind 60 deg+1.0 Ice+1.0 Temp
30	1.2 Dead+1.0 Wind 90 deg+1.0 Ice+1.0 Temp
31	1.2 Dead+1.0 Wind 120 deg+1.0 Ice+1.0 Temp
32	1.2 Dead+1.0 Wind 150 deg+1.0 Ice+1.0 Temp
33	1.2 Dead+1.0 Wind 180 deg+1.0 Ice+1.0 Temp
34	1.2 Dead+1.0 Wind 210 deg+1.0 Ice+1.0 Temp
35	1.2 Dead+1.0 Wind 240 deg+1.0 Ice+1.0 Temp
36	1.2 Dead+1.0 Wind 270 deg+1.0 Ice+1.0 Temp
37	1.2 Dead+1.0 Wind 300 deg+1.0 Ice+1.0 Temp
38	1.2 Dead+1.0 Wind 330 deg+1.0 Ice+1.0 Temp
39	Dead+Wind 0 deg - Service
40	Dead+Wind 30 deg - Service
41	Dead+Wind 60 deg - Service
42	Dead+Wind 90 deg - Service
43	Dead+Wind 120 deg - Service
44	Dead+Wind 150 deg - Service
45	Dead+Wind 180 deg - Service
46	Dead+Wind 210 deg - Service
47	Dead+Wind 240 deg - Service
48	Dead+Wind 270 deg - Service
49	Dead+Wind 300 deg - Service
50	Dead+Wind 330 deg - Service

Maximum Member Forces

Section No.	Elevation ft	Component Type	Condition	Gov. Load Comb.	Axial	Major Axis Moment kip-ft	Minor Axis Moment kip-ft
L1	185 - 180	Pole	Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-8.08	-0.00	-0.07
			Max. Mx	8	-4.63	-15.96	-0.03
			Max. My	14	-4.63	-0.00	-15.99
			Max. Vy	8	5.21	-15.96	-0.03
			Max. Vx	14	5.21	-0.00	-15.99
L2	180 - 175	Pole	Max. Torque	22			-0.00
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-8.64	-0.00	-0.19
			Max. Mx	8	-4.96	-43.07	-0.09
			Max. My	14	-4.96	-0.00	-43.15
			Max. Vy	8	5.64	-43.07	-0.09
L3	175 - 170	Pole	Max. Vx	14	5.64	-0.00	-43.15
			Max. Torque	2			-0.00
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-21.08	0.08	-0.36
			Max. Mx	20	-12.51	106.27	0.01
			Max. My	14	-12.50	-0.16	-106.58
L4	170 - 165	Pole	Max. Vy	8	14.52	-106.23	-0.31
			Max. Vx	14	14.56	-0.16	-106.58
			Max. Torque	12			-0.29
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-21.77	0.07	-0.50
			Max. Mx	20	-12.99	180.00	0.14

Section No.	Elevation ft	Component Type	Condition	Gov. Load Comb.	Axial K	Major Axis Moment kip-ft	Minor Axis Moment kip-ft
L5	165 - 160	Pole	Max. My	14	-12.99	-0.35	-180.59
			Max. Vy	8	14.98	-179.97	-0.57
			Max. Vx	14	15.03	-0.35	-180.59
			Max. Torque	12		-0.29	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-27.85	-0.05	-0.27
			Max. Mx	8	-16.63	-276.51	-0.69
			Max. My	14	-16.62	-0.62	-277.35
			Max. Vy	8	19.54	-276.51	-0.69
			Max. Vx	14	19.61	-0.62	-277.35
L6	160 - 155	Pole	Max. Torque	12		-0.29	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-28.64	-0.08	-0.41
			Max. Mx	8	-17.23	-375.36	-0.95
			Max. My	14	-17.23	-0.83	-376.63
			Max. Vy	8	20.02	-375.36	-0.95
			Max. Vx	14	20.10	-0.83	-376.63
			Max. Torque	4		0.24	
L7	155 - 154	Pole	Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-34.91	-0.09	-0.70
			Max. Mx	8	-20.59	-399.14	-1.09
			Max. My	14	-20.59	-0.87	-400.49
			Max. Vy	8	23.84	-399.14	-1.09
			Max. Vx	14	23.80	-0.87	-400.49
L8	154 - 153.75	Pole	Max. Torque	15		-0.20	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-34.97	-0.09	-0.71
			Max. Mx	8	-20.64	-405.10	-1.11
			Max. My	14	-20.64	-0.88	-406.44
			Max. Vy	8	23.85	-405.10	-1.11
L9	153.75 - 152.5	Pole	Max. Vx	14	23.82	-0.88	-406.44
			Max. Torque	15		-0.20	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-35.26	-0.10	-0.75
			Max. Mx	8	-20.83	-435.00	-1.17
L10	152.5 - 152.25	Pole	Max. My	14	-20.83	-0.94	-436.31
			Max. Vy	8	23.99	-435.00	-1.17
			Max. Vx	14	23.96	-0.94	-436.31
			Max. Torque	15		-0.20	
			Max Tension	1	0.00	0.00	0.00
L11	152.25 - 151.5	Pole	Max. Compression	26	-35.34	-0.10	-0.76
			Max. Mx	8	-20.89	-441.00	-1.18
			Max. My	14	-20.90	-0.95	-442.30
			Max. Vy	8	24.01	-441.00	-1.18
			Max. Vx	14	23.98	-0.95	-442.30
			Max. Torque	15		-0.20	
L12	151.5 - 151.25	Pole	Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-35.56	-0.11	-0.78
			Max. Mx	8	-21.05	-459.05	-1.22
			Max. My	14	-21.05	-0.98	-460.33
			Max. Vy	8	24.10	-459.05	-1.22
L13	151.25 - 146.25	Pole	Max. Vx	14	24.07	-0.98	-460.33
			Max. Torque	15		-0.20	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-35.62	-0.11	-0.79
			Max. Mx	8	-21.10	-465.08	-1.24
			Max. My	14	-21.10	-0.99	-466.35
			Max. Vy	8	24.13	-465.08	-1.24
			Max. Vx	14	24.09	-0.99	-466.35
			Max. Torque	15		-0.20	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-36.86	-0.14	-0.92
			Max. Mx	8	-22.02	-587.11	-1.51
			Max. My	14	-22.02	-1.20	-588.25

Sectio n No.	Elevation ft	Component Type	Condition	Gov. Load Comb.	Axial K	Major Axis Moment kip-ft	Minor Axis Moment kip-ft
L14	146.25 - 141.25	Pole	Max. Vy	8	24.69	-587.11	-1.51
			Max. Vx	14	24.66	-1.20	-588.25
			Max. Torque	15		-0.20	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-38.12	-0.18	-1.07
			Max. Mx	8	-22.98	-711.99	-1.78
			Max. My	14	-22.98	-1.42	-713.00
			Max. Vy	8	25.27	-711.99	-1.78
			Max. Vx	14	25.24	-1.42	-713.00
			Max. Torque	15		-0.20	
L15	141.25 - 136.25	Pole	Max Tension	1	0.00	0.00	0.00
L16	136.25 - 130	Pole	Max. Compression	26	-39.42	-0.22	-1.22
			Max. Mx	8	-23.97	-839.80	-2.05
			Max. My	14	-23.97	-1.63	-840.70
			Max. Vy	8	25.87	-839.80	-2.05
			Max. Vx	14	25.83	-1.63	-840.70
			Max. Torque	3		0.20	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-39.76	-0.23	-1.26
			Max. Mx	8	-24.22	-872.23	-2.12
			Max. My	14	-24.22	-1.69	-873.09
L17	130 - 129	Pole	Max. Vy	8	26.03	-872.23	-2.12
			Max. Vx	14	25.99	-1.69	-873.09
			Max. Torque	3		0.20	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-42.66	-0.28	-1.45
			Max. Mx	8	-26.44	-1030.97	-2.46
			Max. My	14	-26.44	-1.95	-1031.68
			Max. Vy	8	26.89	-1030.97	-2.46
			Max. Vx	14	26.85	-1.95	-1031.68
			Max. Torque	3		0.20	
L18	129 - 124	Pole	Max Tension	1	0.00	0.00	0.00
L19	124 - 121.42	Pole	Max. Compression	26	-44.29	-0.32	-1.62
			Max. Mx	8	-27.66	-1167.02	-2.74
			Max. My	14	-27.66	-2.17	-1167.62
			Max. Vy	8	27.55	-1167.02	-2.74
			Max. Vx	14	27.51	-2.17	-1167.62
			Max. Torque	3		0.20	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-45.20	-0.35	-1.71
			Max. Mx	8	-28.31	-1238.53	-2.89
			Max. My	14	-28.31	-2.28	-1239.07
L20	121.42 - 121.17	Pole	Max. Vy	8	27.90	-1238.53	-2.89
			Max. Vx	14	27.86	-2.28	-1239.07
			Max. Torque	3		0.20	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-45.29	-0.35	-1.72
			Max. Mx	8	-28.38	-1245.51	-2.90
			Max. My	14	-28.39	-2.29	-1246.04
			Max. Vy	8	27.93	-1245.51	-2.90
			Max. Vx	14	27.89	-2.29	-1246.04
			Max. Torque	3		0.20	
L21	121.17 - 116.17	Pole	Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-47.11	-0.39	-1.90
			Max. Mx	8	-29.73	-1386.89	-3.19
			Max. My	14	-29.74	-2.51	-1387.30
			Max. Vy	8	28.63	-1386.89	-3.19
			Max. Vx	14	28.60	-2.51	-1387.30
			Max. Torque	3		0.20	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-47.53	-0.41	-1.94
			Max. Mx	8	-30.06	-1420.48	-3.26
L22	116.17 - 115	Pole	Max. My	14	-30.06	-2.56	-1420.86
			Max. Vy	8	28.80	-1420.48	-3.26
			Max. Vx	14	28.77	-2.56	-1420.86

Sectio n No.	Elevation ft	Component Type	Condition	Gov. Load Comb.	Axial K	Major Axis Moment kip-ft	Minor Axis Moment kip-ft
L23	115 - 113.75	Pole	Max. Torque	3		0.20	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-48.03	-0.42	-1.99
			Max. Mx	8	-30.44	-1456.59	-3.33
			Max. My	14	-30.44	-2.61	-1456.95
			Max. Vy	8	28.99	-1456.59	-3.33
			Max. Vx	14	28.95	-2.61	-1456.95
L24	113.75 - 113.5	Pole	Max. Torque	3		0.20	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-48.12	-0.42	-1.99
			Max. Mx	8	-30.52	-1463.84	-3.34
			Max. My	14	-30.52	-2.62	-1464.19
			Max. Vy	8	29.02	-1463.84	-3.34
			Max. Vx	14	28.98	-2.62	-1464.19
L25	113.5 - 108.5	Pole	Max. Torque	3		0.20	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-49.88	-0.47	-2.18
			Max. Mx	8	-31.90	-1610.74	-3.64
			Max. My	14	-31.90	-2.84	-1610.97
			Max. Vy	8	29.75	-1610.74	-3.64
			Max. Vx	14	29.71	-2.84	-1610.97
L26	108.5 - 103.5	Pole	Max. Torque	3		0.20	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-51.67	-0.52	-2.38
			Max. Mx	8	-33.32	-1761.31	-3.93
			Max. My	14	-33.32	-3.06	-1761.43
			Max. Vy	8	30.49	-1761.31	-3.93
			Max. Vx	14	30.46	-3.06	-1761.43
L27	103.5 - 95	Pole	Max. Torque	3		0.20	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-52.63	-0.54	-2.48
			Max. Mx	8	-34.04	-1838.00	-4.08
			Max. My	14	-34.04	-3.17	-1838.07
			Max. Vy	8	30.87	-1838.00	-4.08
			Max. Vx	14	30.84	-3.17	-1838.07
L28	95 - 94	Pole	Max. Torque	3		0.20	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-57.68	-0.62	-2.77
			Max. Mx	8	-38.07	-2058.42	-4.50
			Max. My	14	-38.07	-3.48	-2058.34
			Max. Vy	8	32.10	-2058.42	-4.50
			Max. Vx	14	32.07	-3.48	-2058.34
L29	94 - 91.4	Pole	Max. Torque	3		0.20	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-58.90	-0.65	-2.88
			Max. Mx	8	-39.03	-2142.42	-4.66
			Max. My	14	-39.03	-3.60	-2142.29
			Max. Vy	8	32.53	-2142.42	-4.66
			Max. Vx	14	32.49	-3.60	-2142.29
L30	91.4 - 91.15	Pole	Max. Torque	3		0.20	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-59.00	-0.65	-2.89
			Max. Mx	8	-39.11	-2150.56	-4.68
			Max. My	14	-39.11	-3.61	-2150.42
			Max. Vy	8	32.56	-2150.56	-4.68
			Max. Vx	14	32.52	-3.61	-2150.42
L31	91.15 - 91	Pole	Max. Torque	3		0.20	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-59.06	-0.65	-2.89
			Max. Mx	8	-39.16	-2155.44	-4.68
			Max. My	14	-39.16	-3.62	-2155.30
			Max. Vy	8	32.59	-2155.44	-4.68
			Max. Vx	14	32.55	-3.62	-2155.30
L32	91 - 86	Pole	Max. Torque	3		0.20	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-61.20	-0.71	-3.11

Sectio n No.	Elevation ft	Component Type	Condition	Gov. Load Comb.	Axial K	Major Axis Moment kip-ft	Minor Axis Moment kip-ft
L33	86 - 81	Pole	Max. Mx	8	-40.87	-2320.34	-4.99
			Max. My	14	-40.87	-3.84	-2320.09
			Max. Vy	8	33.39	-2320.34	-4.99
			Max. Vx	14	33.35	-3.84	-2320.09
			Max. Torque	3		0.20	
			Max. Tension	1	0.00	0.00	0.00
			Max. Compression	26	-63.36	-0.76	-3.33
			Max. Mx	8	-42.62	-2489.28	-5.30
			Max. My	14	-42.62	-4.06	-2488.93
			Max. Vy	8	34.20	-2489.28	-5.30
			Max. Vx	14	34.17	-4.06	-2488.93
L34	81 - 76	Pole	Max. Torque	3		0.20	
			Max. Tension	1	0.00	0.00	0.00
			Max. Compression	26	-65.55	-0.82	-3.56
			Max. Mx	8	-44.42	-2662.32	-5.61
			Max. My	14	-44.42	-4.28	-2661.88
			Max. Vy	8	35.03	-2662.32	-5.61
			Max. Vx	14	34.99	-4.28	-2661.88
			Max. Torque	3		0.20	
			Max. Tension	1	0.00	0.00	0.00
			Max. Compression	26	-67.80	-0.88	-3.79
L35	76 - 71	Pole	Max. Mx	8	-46.26	-2839.53	-5.93
			Max. My	14	-46.26	-4.51	-2838.99
			Max. Vy	8	35.87	-2839.53	-5.93
			Max. Vx	14	35.83	-4.51	-2838.99
			Max. Torque	3		0.20	
			Max. Tension	1	0.00	0.00	0.00
			Max. Compression	26	-70.09	-0.94	-4.03
			Max. Mx	8	-48.15	-3020.96	-6.25
			Max. My	14	-48.15	-4.73	-3020.33
			Max. Vy	8	36.72	-3020.96	-6.25
L36	71 - 66	Pole	Max. Vx	14	36.68	-4.73	-3020.33
			Max. Torque	3		0.20	
			Max. Tension	1	0.00	0.00	0.00
			Max. Compression	26	-71.17	-0.97	-4.14
			Max. Mx	8	-49.01	-3104.00	-6.39
			Max. My	14	-49.01	-4.83	-3103.33
			Max. Vy	8	37.10	-3104.00	-6.39
			Max. Vx	14	37.07	-4.83	-3103.33
			Max. Torque	3		0.20	
			Max. Tension	1	0.00	0.00	0.00
L37	66 - 63.75	Pole	Max. Compression	26	-71.17	-0.97	-4.14
			Max. Mx	8	-49.01	-3104.00	-6.39
			Max. My	14	-49.01	-4.83	-3103.33
			Max. Vy	8	37.10	-3104.00	-6.39
			Max. Vx	14	37.07	-4.83	-3103.33
			Max. Torque	3		0.20	
			Max. Tension	1	0.00	0.00	0.00
			Max. Compression	26	-71.29	-0.98	-4.16
			Max. Mx	8	-49.11	-3113.28	-6.41
			Max. My	14	-49.11	-4.84	-3112.60
L38	63.75 - 63.5	Pole	Max. Vy	8	37.14	-3113.28	-6.41
			Max. Vx	14	37.10	-4.84	-3112.60
			Max. Torque	3		0.20	
			Max. Tension	1	0.00	0.00	0.00
			Max. Compression	26	-71.29	-0.98	-4.16
			Max. Mx	8	-49.11	-3113.28	-6.41
			Max. My	14	-49.11	-4.84	-3112.60
			Max. Vy	8	37.14	-3113.28	-6.41
			Max. Vx	14	37.10	-4.84	-3112.60
			Max. Torque	3		0.20	
L39	63.5 - 58.5	Pole	Max. Tension	1	0.00	0.00	0.00
			Max. Compression	26	-73.68	-1.04	-4.41
			Max. Mx	8	-51.05	-3301.12	-6.73
			Max. My	14	-51.05	-5.07	-3300.36
			Max. Vy	8	38.01	-3301.12	-6.73
			Max. Vx	14	37.97	-5.07	-3300.36
			Max. Torque	3		0.20	
			Max. Tension	1	0.00	0.00	0.00
			Max. Compression	26	-73.93	-1.05	-4.43
			Max. Mx	8	-51.25	-3320.14	-6.76
L40	58.5 - 51	Pole	Max. My	14	-51.25	-5.09	-3319.37
			Max. Vy	8	38.09	-3320.14	-6.76
			Max. Vx	14	38.05	-5.09	-3319.37
			Max. Torque	3		0.20	
			Max. Tension	1	0.00	0.00	0.00
			Max. Compression	26	-73.93	-1.05	-4.43
			Max. Mx	8	-51.25	-3320.14	-6.76
			Max. My	14	-51.25	-5.09	-3319.37
			Max. Vy	8	38.09	-3320.14	-6.76
			Max. Vx	14	38.05	-5.09	-3319.37
L41	51 - 50	Pole	Max. Torque	3		0.20	
			Max. Tension	1	0.00	0.00	0.00
			Max. Compression	26	-81.22	-1.15	-4.84
			Max. Mx	8	-57.29	-3630.99	-7.28
			Max. My	14	-57.29	-5.45	-3630.08
			Max. Vy	8	39.62	-3630.99	-7.28
			Max. Vx	14	39.58	-5.45	-3630.08
			Max. Torque	3		0.20	
			Max. Tension	1	0.00	0.00	0.00
			Max. Compression	26	-81.22	-1.15	-4.84
L42	50 - 45	Pole	Max. Mx	8	-57.29	-3630.99	-7.28
			Max. My	14	-57.29	-5.45	-3630.08

Sectio n No.	Elevation ft	Component Type	Condition	Gov. Load Comb.	Axial K	Major Axis Moment kip-ft	Minor Axis Moment kip-ft
L43	45 - 40.42	Pole	Max. Compression	26	-84.02	-1.22	-5.10
			Max. Mx	8	-59.60	-3831.21	-7.61
			Max. My	14	-59.60	-5.68	-3830.22
			Max. Vy	8	40.49	-3831.21	-7.61
			Max. Vx	14	40.45	-5.68	-3830.22
			Max. Torque	3		0.20	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-86.63	-1.28	-5.35
			Max. Mx	8	-61.75	-4018.42	-7.92
			Max. My	14	-61.75	-5.88	-4017.36
L44	40.42 - 40.17	Pole	Max. Vy	8	41.28	-4018.42	-7.92
			Max. Vx	14	41.24	-5.88	-4017.36
			Max. Torque	3		0.20	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-86.76	-1.29	-5.36
L45	40.17 - 40	Pole	Max. Mx	8	-61.86	-4028.74	-7.93
			Max. My	14	-61.86	-5.90	-4027.68
			Max. Vy	8	41.31	-4028.74	-7.93
			Max. Vx	14	41.28	-5.90	-4027.68
			Max. Torque	3		0.20	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-86.85	-1.29	-5.37
			Max. Mx	8	-61.93	-4035.77	-7.94
			Max. My	14	-61.93	-5.90	-4034.70
			Max. Vy	8	41.34	-4035.77	-7.94
L46	40 - 35	Pole	Max. Vx	14	41.31	-5.90	-4034.70
			Max. Torque	3		0.20	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-89.73	-1.31	-5.62
			Max. Mx	8	-64.30	-4244.63	-8.28
L47	35 - 33	Pole	Max. My	14	-64.30	-6.13	-4243.49
			Max. Vy	8	42.21	-4244.63	-8.28
			Max. Vx	14	42.17	-6.13	-4243.49
			Max. Torque	3		0.20	
			Max Tension	1	0.00	0.00	0.00
L48	33 - 32.75	Pole	Max. Compression	26	-90.92	-1.30	-5.72
			Max. Mx	8	-65.26	-4329.37	-8.41
			Max. My	14	-65.26	-6.22	-4328.20
			Max. Vy	8	42.55	-4329.37	-8.41
			Max. Vx	14	42.51	-6.22	-4328.20
			Max. Torque	3		0.20	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-91.10	-1.30	-5.73
			Max. Mx	8	-65.41	-4340.01	-8.43
			Max. My	14	-65.41	-6.23	-4338.84
L49	32.75 - 19	Pole	Max. Vy	8	42.58	-4340.01	-8.43
			Max. Vx	14	42.55	-6.23	-4338.84
			Max. Torque	3		0.20	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-94.36	-1.28	-5.96
L50	19 - 18	Pole	Max. Mx	8	-68.18	-4544.16	-8.76
			Max. My	14	-68.18	-6.45	-4542.93
			Max. Vy	8	43.38	-4544.16	-8.76
			Max. Vx	14	43.34	-6.45	-4542.93
			Max. Torque	3		0.20	
L51	18 - 13	Pole	Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-106.96	-1.23	-6.44
			Max. Mx	8	-79.09	-4987.12	-9.44
			Max. My	14	-79.09	-6.90	-4985.74
			Max. Vy	8	45.20	-4987.12	-9.44
			Max. Vx	14	45.16	-6.90	-4985.74
			Max. Torque	3		0.20	
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-110.48	-1.21	-6.69
			Max. Mx	8	-82.14	-5214.97	-9.78

Section No.	Elevation ft	Component Type	Condition	Gov. Load Comb.	Axial K	Major Axis Moment kip-ft	Minor Axis Moment kip-ft
L52	13 - 8	Pole	Max. Torque	3	0.00	0.00	0.20
			Max Tension	1	-114.02	-1.19	0.00
			Max. Compression	26	-85.23	-5446.63	-6.93
			Max. Mx	8	-85.23	-10.13	
			Max. My	14	46.72	-5446.63	-10.13
			Max. Vy	8	46.68	-7.36	-5445.13
			Max. Vx	14	46.68	-7.36	-5445.13
			Max. Torque	3	0.00	0.00	0.20
			Max Tension	1	-115.15	-1.18	0.00
L53	8 - 6.42	Pole	Max. Compression	26	-86.22	-5520.63	-7.01
			Max. Mx	8	-86.22	-10.24	
			Max. My	14	46.97	-5520.63	-10.24
			Max. Vy	8	46.94	-7.43	-5519.11
			Max. Vx	14	46.94	-7.43	-5519.11
			Max. Torque	3	0.00	0.00	0.20
			Max Tension	1	-115.31	-1.18	0.00
			Max. Compression	26	-86.36	-5532.38	-10.26
			Max. Mx	8	-86.36	-7.44	-5530.85
L54	6.42 - 6.17	Pole	Max. My	14	47.00	-5532.38	-10.26
			Max. Vy	8	46.96	-7.44	-5530.85
			Max. Vx	14	46.96	-7.44	-5530.85
			Max. Torque	3	0.00	0.00	0.20
			Max Tension	1	-118.51	-1.17	0.00
			Max. Compression	26	-89.12	-5769.46	-7.27
			Max. Mx	8	-89.12	-10.61	
			Max. My	14	47.83	-5769.46	-10.61
			Max. Vy	8	47.80	-7.67	-5767.88
L55	6.17 - 1.17	Pole	Max. Vx	14	47.80	-7.67	-5767.88
			Max. Torque	3	0.00	0.00	0.20
			Max Tension	1	-119.25	-1.17	0.00
			Max. Compression	26	-89.77	-5825.54	-7.32
			Max. Mx	8	-89.77	-10.70	
			Max. My	14	48.03	-5825.54	-10.70
			Max. Vy	8	48.00	-7.72	-5823.94
			Max. Vx	14	48.00	-7.72	-5823.94
			Max. Torque	3	0.00	0.00	0.20
<hr/>							

Maximum Reactions

Location	Condition	Gov. Load Comb.	Vertical K	Horizontal, X K	Horizontal, Z K
Pole	Max. Vert	26	119.25	-0.00	-0.00
	Max. H _x	20	89.78	48.02	0.04
	Max. H _z	2	89.78	0.04	47.99
	Max. M _x	2	5815.90	0.04	47.99
	Max. M _z	8	5825.54	-48.02	-0.04
	Max. Torsion	3	0.20	0.04	47.99
	Min. Vert	19	67.34	41.57	-23.96
	Min. H _x	8	89.78	-48.02	-0.04
	Min. H _z	14	89.78	-0.04	-47.99
	Min. M _x	14	-5823.94	-0.04	-47.99
	Min. M _z	20	-5823.43	48.02	0.04
	Min. Torsion	15	-0.20	-0.04	-47.99

Tower Mast Reaction Summary

Load Combination	Vertical	Shear _x	Shear _z	Overswinging Moment, M _x	Overswinging Moment, M _z	Torque
	K	K	K	kip-ft	kip-ft	kip-ft
Dead Only	74.82	0.00	0.00	3.25	-0.85	0.00
1.2 Dead+1.0 Wind 0 deg -	89.78	-0.04	-47.99	-5815.90	5.61	-0.19
No Ice						
0.9 Dead+1.0 Wind 0 deg -	67.34	-0.04	-47.99	-5766.88	5.81	-0.20
No Ice						
1.2 Dead+1.0 Wind 30 deg -	89.78	24.43	-42.31	-5156.37	-2978.85	-0.15
No Ice						
0.9 Dead+1.0 Wind 30 deg -	67.34	24.43	-42.31	-5112.98	-2952.96	-0.15
No Ice						
1.2 Dead+1.0 Wind 60 deg -	89.78	41.57	-23.96	-2900.16	-5041.89	-0.06
No Ice						
0.9 Dead+1.0 Wind 60 deg -	67.34	41.57	-23.96	-2876.23	-4998.29	-0.06
No Ice						
1.2 Dead+1.0 Wind 90 deg -	89.78	48.02	0.04	10.70	-5825.54	0.04
No Ice						
0.9 Dead+1.0 Wind 90 deg -	67.34	48.02	0.04	9.59	-5775.20	0.04
No Ice						
1.2 Dead+1.0 Wind 120 deg - No Ice	89.78	41.61	24.02	2919.75	-5048.53	0.13
0.9 Dead+1.0 Wind 120 deg - No Ice	67.34	41.61	24.02	2893.64	-5004.86	0.14
1.2 Dead+1.0 Wind 150 deg - No Ice	89.78	24.04	41.58	5047.55	-2919.07	0.19
0.9 Dead+1.0 Wind 150 deg - No Ice	67.34	24.04	41.58	5003.14	-2893.70	0.19
1.2 Dead+1.0 Wind 180 deg - No Ice	89.78	0.04	47.99	5823.94	-7.72	0.19
0.9 Dead+1.0 Wind 180 deg - No Ice	67.34	0.04	47.99	5772.87	-7.38	0.20
1.2 Dead+1.0 Wind 210 deg - No Ice	89.78	-24.43	42.31	5164.42	2976.73	0.15
0.9 Dead+1.0 Wind 210 deg - No Ice	67.34	-24.43	42.31	5118.97	2951.38	0.15
1.2 Dead+1.0 Wind 240 deg - No Ice	89.78	-41.57	23.96	2908.22	5039.77	0.06
0.9 Dead+1.0 Wind 240 deg - No Ice	67.34	-41.57	23.96	2882.22	4996.71	0.06
1.2 Dead+1.0 Wind 270 deg - No Ice	89.78	-48.02	-0.04	-2.64	5823.43	-0.04
0.9 Dead+1.0 Wind 270 deg - No Ice	67.34	-48.02	-0.04	-3.60	5773.63	-0.04
1.2 Dead+1.0 Wind 300 deg - No Ice	89.78	-41.61	-24.02	-2911.70	5046.43	-0.13
0.9 Dead+1.0 Wind 300 deg - No Ice	67.34	-41.61	-24.02	-2887.65	5003.30	-0.14
1.2 Dead+1.0 Wind 330 deg - No Ice	89.78	-24.04	-41.58	-5039.50	2916.96	-0.19
0.9 Dead+1.0 Wind 330 deg - No Ice	67.34	-24.04	-41.58	-4997.16	2892.13	-0.19
1.2 Dead+1.0 Ice+1.0 Temp	119.25	0.00	0.00	7.32	-1.17	-0.00
1.2 Dead+1.0 Wind 0 deg+1.0 Ice+1.0 Temp	119.25	0.00	-11.64	-1475.29	-0.00	-0.03
1.2 Dead+1.0 Wind 30 deg+1.0 Ice+1.0 Temp	119.25	5.82	-10.08	-1275.99	-742.04	-0.02
1.2 Dead+1.0 Wind 60 deg+1.0 Ice+1.0 Temp	119.25	10.08	-5.82	-732.74	-1285.59	-0.02
1.2 Dead+1.0 Wind 90 deg+1.0 Ice+1.0 Temp	119.25	11.65	0.01	8.90	-1485.00	-0.00
1.2 Dead+1.0 Wind 120 deg+1.0 Ice+1.0 Temp	119.25	10.09	5.83	750.20	-1286.84	0.01
1.2 Dead+1.0 Wind 150 deg+1.0 Ice+1.0 Temp	119.25	5.83	10.09	1292.54	-744.20	0.02
1.2 Dead+1.0 Wind 180 deg+1.0 Ice+1.0 Temp	119.25	0.01	11.64	1490.59	-2.49	0.03
1.2 Dead+1.0 Wind 210 deg+1.0 Ice+1.0 Temp	119.25	-5.82	10.08	1291.29	739.56	0.02

Load Combination	Vertical	Shear _x	Shear _z	Overspinning Moment, M _x kip-ft	Overspinning Moment, M _z kip-ft	Torque
	K	K	K			kip-ft
1.2 Dead+1.0 Wind 240 deg+1.0 Ice+1.0 Temp	119.25	-10.08	5.82	748.04	1283.11	0.02
1.2 Dead+1.0 Wind 270 deg+1.0 Ice+1.0 Temp	119.25	-11.65	-0.01	6.41	1482.52	0.00
1.2 Dead+1.0 Wind 300 deg+1.0 Ice+1.0 Temp	119.25	-10.09	-5.83	-734.89	1284.36	-0.01
1.2 Dead+1.0 Wind 330 deg+1.0 Ice+1.0 Temp	119.25	-5.83	-10.09	-1277.23	741.72	-0.02
Dead+Wind 0 deg - Service	74.82	-0.01	-11.30	-1360.33	0.69	-0.05
Dead+Wind 30 deg - Service	74.82	5.75	-9.96	-1205.82	-698.62	-0.03
Dead+Wind 60 deg - Service	74.82	9.79	-5.64	-677.14	-1181.99	-0.01
Dead+Wind 90 deg - Service	74.82	11.31	0.01	4.90	-1365.61	0.01
Dead+Wind 120 deg - Service	74.82	9.80	5.66	686.53	-1183.55	0.03
Dead+Wind 150 deg - Service	74.82	5.66	9.79	1185.09	-684.60	0.04
Dead+Wind 180 deg - Service	74.82	0.01	11.30	1367.01	-2.44	0.05
Dead+Wind 210 deg - Service	74.82	-5.75	9.96	1212.50	696.87	0.03
Dead+Wind 240 deg - Service	74.82	-9.79	5.64	683.82	1180.24	0.01
Dead+Wind 270 deg - Service	74.82	-11.31	-0.01	1.78	1363.87	-0.01
Dead+Wind 300 deg - Service	74.82	-9.80	-5.66	-679.84	1181.80	-0.03
Dead+Wind 330 deg - Service	74.82	-5.66	-9.79	-1178.41	682.85	-0.04

Solution Summary

Load Comb.	Sum of Applied Forces			Sum of Reactions			% Error
	PX K	PY K	PZ K	PX K	PY K	PZ K	
1	0.00	-74.82	0.00	0.00	74.82	0.00	0.000%
2	-0.04	-89.78	-47.99	0.04	89.78	47.99	0.000%
3	-0.04	-67.34	-47.99	0.04	67.34	47.99	0.000%
4	24.43	-89.78	-42.31	-24.43	89.78	42.31	0.000%
5	24.43	-67.34	-42.31	-24.43	67.34	42.31	0.000%
6	41.57	-89.78	-23.96	-41.57	89.78	23.96	0.000%
7	41.57	-67.34	-23.96	-41.57	67.34	23.96	0.000%
8	48.02	-89.78	0.04	-48.02	89.78	-0.04	0.000%
9	48.02	-67.34	0.04	-48.02	67.34	-0.04	0.000%
10	41.61	-89.78	24.02	-41.61	89.78	-24.02	0.000%
11	41.61	-67.34	24.02	-41.61	67.34	-24.02	0.000%
12	24.04	-89.78	41.58	-24.04	89.78	-41.58	0.000%
13	24.04	-67.34	41.58	-24.04	67.34	-41.58	0.000%
14	0.04	-89.78	47.99	-0.04	89.78	-47.99	0.000%
15	0.04	-67.34	47.99	-0.04	67.34	-47.99	0.000%
16	-24.43	-89.78	42.31	24.43	89.78	-42.31	0.000%
17	-24.43	-67.34	42.31	24.43	67.34	-42.31	0.000%
18	-41.57	-89.78	23.96	41.57	89.78	-23.96	0.000%
19	-41.57	-67.34	23.96	41.57	67.34	-23.96	0.000%
20	-48.02	-89.78	-0.04	48.02	89.78	0.04	0.000%
21	-48.02	-67.34	-0.04	48.02	67.34	0.04	0.000%
22	-41.61	-89.78	-24.02	41.61	89.78	24.02	0.000%
23	-41.61	-67.34	-24.02	41.61	67.34	24.02	0.000%
24	-24.04	-89.78	-41.58	24.04	89.78	-41.58	0.000%
25	-24.04	-67.34	-41.58	24.04	67.34	-41.58	0.000%
26	0.00	-119.25	0.00	-0.00	119.25	-0.00	0.000%
27	-0.01	-119.25	-11.64	-0.00	119.25	11.64	0.009%
28	5.82	-119.25	-10.08	-5.82	119.25	10.08	0.000%
29	10.08	-119.25	-5.82	-10.08	119.25	5.82	0.000%
30	11.65	-119.25	0.01	-11.65	119.25	-0.01	0.000%
31	10.09	-119.25	5.83	-10.09	119.25	-5.83	0.000%
32	5.83	-119.25	10.09	-5.83	119.25	-10.09	0.000%

Load Comb.	Sum of Applied Forces			Sum of Reactions			% Error
	PX K	PY K	PZ K	PX K	PY K	PZ K	
33	0.01	-119.25	11.64	-0.01	119.25	-11.64	0.000%
34	-5.82	-119.25	10.08	5.82	119.25	-10.08	0.000%
35	-10.08	-119.25	5.82	10.08	119.25	-5.82	0.000%
36	-11.65	-119.25	-0.01	11.65	119.25	0.01	0.000%
37	-10.09	-119.25	-5.83	10.09	119.25	5.83	0.000%
38	-5.83	-119.25	-10.09	5.83	119.25	10.09	0.000%
39	-0.01	-74.82	-11.30	0.01	74.82	11.30	0.000%
40	5.75	-74.82	9.96	-5.75	74.82	9.96	0.000%
41	9.79	-74.82	-5.64	-9.79	74.82	5.64	0.000%
42	11.31	-74.82	0.01	-11.31	74.82	-0.01	0.000%
43	9.80	-74.82	5.66	-9.80	74.82	-5.66	0.000%
44	5.66	-74.82	9.79	-5.66	74.82	-9.79	0.000%
45	0.01	-74.82	11.30	-0.01	74.82	-11.30	0.000%
46	-5.75	-74.82	9.96	5.75	74.82	-9.96	0.000%
47	-9.79	-74.82	5.64	9.79	74.82	-5.64	0.000%
48	-11.31	-74.82	-0.01	11.31	74.82	0.01	0.000%
49	-9.80	-74.82	-5.66	9.80	74.82	5.66	0.000%
50	-5.66	-74.82	-9.79	5.66	74.82	9.79	0.000%

Non-Linear Convergence Results

Load Combination	Converged?	Number of Cycles	Displacement Tolerance	Force Tolerance
1	Yes	4	0.00000001	0.00000001
2	Yes	5	0.00000001	0.00028577
3	Yes	5	0.00000001	0.00010793
4	Yes	6	0.00000001	0.00050870
5	Yes	6	0.00000001	0.00017139
6	Yes	6	0.00000001	0.00048305
7	Yes	6	0.00000001	0.00016406
8	Yes	5	0.00000001	0.00028093
9	Yes	5	0.00000001	0.00010399
10	Yes	6	0.00000001	0.00048809
11	Yes	6	0.00000001	0.00016552
12	Yes	6	0.00000001	0.00048566
13	Yes	6	0.00000001	0.00016462
14	Yes	5	0.00000001	0.00027527
15	Yes	5	0.00000001	0.00010104
16	Yes	6	0.00000001	0.00051162
17	Yes	6	0.00000001	0.00017239
18	Yes	6	0.00000001	0.00048318
19	Yes	6	0.00000001	0.00016397
20	Yes	5	0.00000001	0.00027454
21	Yes	5	0.00000001	0.00010058
22	Yes	6	0.00000001	0.00048449
23	Yes	6	0.00000001	0.00016439
24	Yes	6	0.00000001	0.00048709
25	Yes	6	0.00000001	0.00016536
26	Yes	4	0.00000001	0.00012427
27	Yes	6	0.00000001	0.00054799
28	Yes	6	0.00000001	0.00035891
29	Yes	6	0.00000001	0.00035937
30	Yes	6	0.00000001	0.00032903
31	Yes	6	0.00000001	0.00036316
32	Yes	6	0.00000001	0.00036334
33	Yes	6	0.00000001	0.00033036
34	Yes	6	0.00000001	0.00036195
35	Yes	6	0.00000001	0.00036155
36	Yes	6	0.00000001	0.00032831
37	Yes	6	0.00000001	0.00035942
38	Yes	6	0.00000001	0.00035918
39	Yes	5	0.00000001	0.00005123
40	Yes	5	0.00000001	0.00016626
41	Yes	5	0.00000001	0.00015700
42	Yes	5	0.00000001	0.00005134
43	Yes	5	0.00000001	0.00016019

44	Yes	5	0.00000001	0.00015836
45	Yes	5	0.00000001	0.00005143
46	Yes	5	0.00000001	0.00016873
47	Yes	5	0.00000001	0.00015764
48	Yes	5	0.00000001	0.00005126
49	Yes	5	0.00000001	0.00015684
50	Yes	5	0.00000001	0.00015869

Maximum Tower Deflections - Service Wind

Section No.	Elevation	Horz. Deflection	Gov. Load Comb.	Tilt	Twist
	ft	in		°	°
L1	185 - 180	20.753	46	1.2317	0.0005
L2	180 - 175	19.465	46	1.2278	0.0005
L3	175 - 170	18.186	46	1.2130	0.0005
L4	170 - 165	16.929	46	1.1851	0.0004
L5	165 - 160	15.710	46	1.1403	0.0003
L6	160 - 155	14.545	46	1.0826	0.0002
L7	155 - 154	13.446	46	1.0150	0.0002
L8	154 - 153.75	13.235	46	1.0009	0.0002
L9	153.75 - 152.5	13.183	46	0.9984	0.0002
L10	152.5 - 152.25	12.923	46	0.9857	0.0002
L11	152.25 - 151.5	12.872	46	0.9840	0.0002
L12	151.5 - 151.25	12.718	46	0.9787	0.0002
L13	151.25 - 146.25	12.666	46	0.9764	0.0002
L14	146.25 - 141.25	11.669	46	0.9275	0.0001
L15	141.25 - 136.25	10.725	46	0.8751	0.0001
L16	136.25 - 130	9.837	46	0.8209	0.0001
L17	135 - 129	9.624	46	0.8073	0.0001
L18	129 - 124	8.629	46	0.7726	0.0001
L19	124 - 121.42	7.845	46	0.7247	0.0001
L20	121.42 - 121.17	7.460	46	0.7003	0.0001
L21	121.17 - 116.17	7.424	46	0.6981	0.0001
L22	116.17 - 115	6.716	46	0.6540	0.0001
L23	115 - 113.75	6.557	46	0.6440	0.0001
L24	113.75 - 113.5	6.389	46	0.6345	0.0001
L25	113.5 - 108.5	6.356	46	0.6323	0.0001
L26	108.5 - 103.5	5.718	46	0.5877	0.0000
L27	103.5 - 95	5.125	46	0.5437	0.0000
L28	101 - 94	4.846	46	0.5219	0.0000
L29	94 - 91.4	4.101	46	0.4924	0.0000
L30	91.4 - 91.15	3.837	46	0.4747	0.0000
L31	91.15 - 91	3.813	46	0.4726	0.0000
L32	91 - 86	3.798	46	0.4713	0.0000
L33	86 - 81	3.324	46	0.4334	0.0000
L34	81 - 76	2.890	46	0.3967	0.0000
L35	76 - 71	2.493	46	0.3608	0.0000
L36	71 - 66	2.134	46	0.3255	0.0000
L37	66 - 63.75	1.811	46	0.2914	0.0000
L38	63.75 - 63.5	1.677	46	0.2763	0.0000
L39	63.5 - 58.5	1.663	46	0.2747	0.0000
L40	58.5 - 51	1.392	46	0.2416	0.0000
L41	58 - 50	1.367	46	0.2384	0.0000
L42	50 - 45	0.988	46	0.2115	0.0000
L43	45 - 40.42	0.781	46	0.1836	0.0000
L44	40.42 - 40.17	0.617	46	0.1585	0.0000
L45	40.17 - 40	0.609	46	0.1570	0.0000
L46	40 - 35	0.604	46	0.1559	0.0000
L47	35 - 33	0.455	46	0.1287	0.0000
L48	33 - 32.75	0.403	46	0.1179	0.0000
L49	32.75 - 19	0.397	46	0.1167	0.0000
L50	28 - 18	0.292	46	0.0947	0.0000
L51	18 - 13	0.117	46	0.0696	0.0000
L52	13 - 8	0.056	46	0.0468	0.0000
L53	8 - 6.42	0.019	46	0.0247	0.0000
L54	6.42 - 6.17	0.012	46	0.0179	0.0000
L55	6.17 - 1.17	0.011	46	0.0172	0.0000
L56	1.17 - 0	0.000	46	0.0000	0.0000

Critical Deflections and Radius of Curvature - Service Wind

Elevation ft	Appurtenance	Gov. Load Comb.	Deflection in	Tilt °	Twist °	Radius of Curvature ft
185.00	3' x 2" Pipe Mount	46	20.753	1.2317	0.0005	29958
183.00	APXVAARR24_43-U-NA20	46	20.237	1.2309	0.0005	29958
174.00	DMP65R-BU6D	46	17.932	1.2086	0.0005	12210
165.00	MX08FRO665-20 w/ Mount Pipe	46	15.710	1.1403	0.0003	5588
155.00	SBNHH-1D65B w/ Mount Pipe	46	13.446	1.0150	0.0002	4631

Maximum Tower Deflections - Design Wind

Section No.	Elevation ft	Horz. Deflection in	Gov. Load Comb.	Tilt °	Twist °
L1	185 - 180	88.594	16	5.2684	0.0022
L2	180 - 175	83.094	16	5.2517	0.0022
L3	175 - 170	77.637	16	5.1886	0.0022
L4	170 - 165	72.271	16	5.0693	0.0018
L5	165 - 160	67.070	16	4.8773	0.0013
L6	160 - 155	62.097	16	4.6300	0.0010
L7	155 - 154	57.406	16	4.3401	0.0008
L8	154 - 153.75	56.505	16	4.2796	0.0008
L9	153.75 - 152.5	56.281	16	4.2689	0.0008
L10	152.5 - 152.25	55.172	16	4.2147	0.0007
L11	152.25 - 151.5	54.952	16	4.2072	0.0007
L12	151.5 - 151.25	54.294	16	4.1845	0.0007
L13	151.25 - 146.25	54.076	16	4.1747	0.0007
L14	146.25 - 141.25	49.819	16	3.9654	0.0006
L15	141.25 - 136.25	45.788	16	3.7408	0.0005
L16	136.25 - 130	41.997	16	3.5088	0.0004
L17	135 - 129	41.087	16	3.4507	0.0004
L18	129 - 124	36.837	16	3.3021	0.0004
L19	124 - 121.42	33.490	16	3.0971	0.0003
L20	121.42 - 121.17	31.846	16	2.9927	0.0003
L21	121.17 - 116.17	31.689	16	2.9834	0.0003
L22	116.17 - 115	28.667	16	2.7946	0.0003
L23	115 - 113.75	27.988	16	2.7517	0.0003
L24	113.75 - 113.5	27.273	16	2.7112	0.0003
L25	113.5 - 108.5	27.131	16	2.7017	0.0003
L26	108.5 - 103.5	24.404	16	2.5107	0.0002
L27	103.5 - 95	21.875	16	2.3226	0.0002
L28	101 - 94	20.684	16	2.2293	0.0002
L29	94 - 91.4	17.501	16	2.1031	0.0002
L30	91.4 - 91.15	16.376	16	2.0276	0.0002
L31	91.15 - 91	16.271	16	2.0183	0.0002
L32	91 - 86	16.207	16	2.0128	0.0002
L33	86 - 81	14.185	16	1.8509	0.0001
L34	81 - 76	12.330	16	1.6941	0.0001
L35	76 - 71	10.637	16	1.5405	0.0001
L36	71 - 66	9.104	16	1.3897	0.0001
L37	66 - 63.75	7.725	16	1.2437	0.0001
L38	63.75 - 63.5	7.155	16	1.1795	0.0001
L39	63.5 - 58.5	7.093	16	1.1724	0.0001
L40	58.5 - 51	5.940	16	1.0312	0.0001
L41	58 - 50	5.832	16	1.0173	0.0001
L42	50 - 45	4.215	16	0.9024	0.0000
L43	45 - 40.42	3.333	16	0.7834	0.0000
L44	40.42 - 40.17	2.633	16	0.6762	0.0000
L45	40.17 - 40	2.598	16	0.6696	0.0000
L46	40 - 35	2.574	16	0.6652	0.0000
L47	35 - 33	1.939	16	0.5490	0.0000
L48	33 - 32.75	1.718	16	0.5029	0.0000
L49	32.75 - 19	1.692	16	0.4979	0.0000
L50	28 - 18	1.244	16	0.4037	0.0000
L51	18 - 13	0.500	16	0.2968	0.0000

Section No.	Elevation ft	Horz. Deflection in	Gov. Load Comb.	Tilt °	Twist °
L52	13 - 8	0.241	16	0.1997	0.0000
L53	8 - 6.42	0.081	16	0.1052	0.0000
L54	6.42 - 6.17	0.051	16	0.0762	0.0000
L55	6.17 - 1.17	0.047	16	0.0733	0.0000
L56	1.17 - 0	0.002	16	0.0138	0.0000

Critical Deflections and Radius of Curvature - Design Wind

Elevation ft	Appurtenance	Gov. Load Comb.	Deflection in	Tilt °	Twist °	Radius of Curvature ft
185.00	3' x 2" Pipe Mount	16	88.594	5.2684	0.0022	7138
183.00	APXVAARR24_43-U-NA20	16	86.392	5.2649	0.0022	7138
174.00	DMP65R-BU6D	16	76.555	5.1698	0.0021	2907
165.00	MX08FRO665-20 w/ Mount Pipe	16	67.070	4.8773	0.0013	1325
155.00	SBNHH-1D65B w/ Mount Pipe	16	57.406	4.3401	0.0008	1095

Compression Checks

Pole Design Data

Section No.	Elevation ft	Size	L ft	L _u ft	Kl/r	A in ²	P _u K	ϕP _n K	Ratio ϕP _n /P _u
L1	185 - 180 (1)	TP18x18x0.1875	5.00	0.00	0.0	10.7543	-4.62	406.51	0.011
L2	180 - 175 (2)	TP19.6313x18x0.25	5.00	0.00	0.0	15.6019	-4.94	589.75	0.008
L3	175 - 170 (3)	TP21.2625x19.6313x0.25	5.00	0.00	0.0	16.9151	-12.46	639.39	0.019
L4	170 - 165 (4)	TP22.8938x21.2625x0.25	5.00	0.00	0.0	18.2282	-12.94	689.03	0.019
L5	165 - 160 (5)	TP24.525x22.8938x0.25	5.00	0.00	0.0	19.5414	-16.56	738.66	0.022
L6	160 - 155 (6)	TP26.1563x24.525x0.25	5.00	0.00	0.0	20.8545	-17.16	788.30	0.022
L7	155 - 154 (7)	TP26.4825x26.1563x0.25	1.00	0.00	0.0	21.1172	-20.52	798.23	0.026
L8	154 - 153.75 (8)	TP26.5641x26.4825x0.36	0.25	0.00	0.0	31.1037	-20.57	1175.72	0.017
L9	153.75 - 152.5 (9)	TP26.9719x26.5641x0.36	1.25	0.00	0.0	31.0598	-20.76	1174.06	0.018
L10	152.5 - 152.25 (10)	TP27.0534x26.9719x0.55	0.25	0.00	0.0	46.9376	-20.82	1774.24	0.012
L11	152.25 - 151.5 (11)	TP27.2981x27.0534x0.55	0.75	0.00	0.0	47.3709	-20.98	1790.62	0.012
L12	151.5 - 151.25 (12)	TP27.3797x27.2981x0.42	0.25	0.00	0.0	36.8875	-21.03	1394.35	0.015
L13	151.25 - 146.25 (13)	TP29.0109x27.3797x0.41	5.00	0.00	0.0	37.9859	-21.94	1435.87	0.015
L14	146.25 - 141.25 (14)	TP30.6422x29.0109x0.4	5.00	0.00	0.0	38.9519	-22.90	1472.38	0.016
L15	141.25 - 136.25 (15)	TP32.2734x30.6422x0.39	5.00	0.00	0.0	40.4195	-23.89	1527.86	0.016
L16	136.25 - 130 (16)	TP34.3125x32.2734x0.39	6.25	0.00	0.0	40.9365	-24.14	1547.40	0.016
L17	130 - 129 (17)	TP34.1331x32.1813x0.47	6.00	0.00	0.0	51.4801	-26.35	1945.95	0.014
L18	129 - 124 (18)	TP35.7597x34.1331x0.46	5.00	0.00	0.0	52.5663	-27.58	1987.01	0.014
L19	124 - 121.42 (19)	TP36.599x35.7597x0.462	2.58	0.00	0.0	53.8163	-28.23	2034.26	0.014
L20	121.42 - 121.17 (20)	TP36.6803x36.599x0.5	0.25	0.00	0.0	58.2503	-28.30	2201.86	0.013
L21	121.17 - 116.17 (21)	TP38.3069x36.6803x0.48	5.00	0.00	0.0	59.3670	-29.66	2244.07	0.013
L22	116.17 - 115	TP38.6875x38.3069x0.48	1.17	0.00	0.0	59.9645	-29.98	2266.66	0.013

Section No.	Elevation ft	Size	L ft	L _u ft	Kl/r	A in ²	P _u K	ϕP _n K	Ratio
									P _u ϕP _n
L23	(22) 115 - 113.75	TP39.0938x38.6875x0.55 75 (23)	1.25	0.00	0.0	68.2610	-30.37	2580.27	0.012
L24	113.75 - 113.5 (24)	TP39.175x39.0938x0.468 8	0.25	0.00	0.0	58.4222	-30.44	2208.36	0.014
L25	113.5 - 108.5 (25)	TP40.8x39.175x0.4625	5.00	0.00	0.0	60.0726	-31.83	2270.75	0.014
L26	108.5 - 103.5 (26)	TP42.425x40.8x0.4563	5.00	0.00	0.0	61.6573	-33.25	2330.65	0.014
L27	103.5 - 95 (27)	TP45.1875x42.425x0.45	8.50	0.00	0.0	61.9991	-33.98	2343.57	0.014
L28	95 - 94 (28)	TP44.8525x42.6125x0.58 75	7.00	0.00	0.0	83.7383	-38.01	3165.31	0.012
L29	94 - 91.4 (29)	TP45.6845x44.8525x0.57 5	2.60	0.00	0.0	83.5202	-38.97	3157.07	0.012
L30	91.4 - 91.15 (30)	TP45.7645x45.6845x0.44 38	0.25	0.00	0.0	64.7577	-39.05	2447.84	0.016
L31	91.15 - 91 (31)	TP45.8125x45.7645x0.44 38	0.15	0.00	0.0	64.8263	-39.10	2450.43	0.016
L32	91 - 86 (32)	TP47.4453x45.8125x0.5	5.00	0.00	0.0	75.5820	-40.81	2857.00	0.014
L33	86 - 81 (33)	TP49.0781x47.4453x0.5	5.00	0.00	0.0	78.2108	-42.57	2956.37	0.014
L34	81 - 76 (34)	TP50.7109x49.0781x0.49 38	5.00	0.00	0.0	79.8391	-44.37	3017.92	0.015
L35	76 - 71 (35)	TP52.3438x50.7109x0.48 75	5.00	0.00	0.0	81.4014	-46.22	3076.97	0.015
L36	71 - 66 (36)	TP53.9766x52.3438x0.48 75	5.00	0.00	0.0	83.9645	-48.11	3173.86	0.015
L37	66 - 63.75 (37)	TP54.7113x53.9766x0.48 75	2.25	0.00	0.0	85.1179	-48.97	3217.46	0.015
L38	63.75 - 63.5 (38)	TP54.793x54.7113x0.487 5	0.25	0.00	0.0	85.2460	-49.08	3222.30	0.015
L39	63.5 - 58.5 (39)	TP56.4258x54.793x0.481 3	5.00	0.00	0.0	86.6930	-51.02	3277.00	0.016
L40	58.5 - 51 (40)	TP58.875x56.4258x0.481 3	7.50	0.00	0.0	86.9461	-51.22	3286.56	0.016
L41	51 - 50 (41)	TP58.4384x55.8391x0.55	8.00	0.00	0.0	102.5200	-57.26	3875.27	0.015
L42	50 - 45 (42)	TP60.0629x58.4384x0.55	5.00	0.00	0.0	105.3970	-59.57	3984.02	0.015
L43	45 - 40.42 (43)	TP61.551x60.0629x0.543 8	4.58	0.00	0.0	106.8160	-61.72	4037.65	0.015
L44	40.42 - 40.17 (44)	TP61.6323x61.551x0.475	0.25	0.00	0.0	93.5400	-61.84	3535.81	0.017
L45	40.17 - 40 (45)	TP61.6875x61.6323x0.47	0.17	0.00	0.0	93.6245	-61.91	3539.01	0.017
L46	40 - 35 (46)	TP63.3095x61.6875x0.53 13	5.00	0.00	0.0	107.3900	-64.28	4059.35	0.016
L47	35 - 33 (47)	TP63.9583x63.3095x0.52 5	2.00	0.00	0.0	107.2340	-65.24	4053.45	0.016
L48	33 - 32.75 (48)	TP64.0394x63.9583x0.6	0.25	0.00	0.0	122.5650	-65.39	4632.96	0.014
L49	32.75 - 19 (49)	TP68.5x64.0394x0.6	13.75	0.00	0.0	125.5420	-68.17	4745.49	0.014
L50	19 - 18 (50)	TP67.9579x64.7054x0.6	10.00	0.00	0.0	130.1350	-79.08	4919.12	0.016
L51	18 - 13 (51)	TP69.5842x67.9579x0.58 75	5.00	0.00	0.0	130.5240	-82.13	4933.83	0.017
L52	13 - 8 (52)	TP71.2105x69.5842x0.58 75	5.00	0.00	0.0	133.6010	-85.23	5050.12	0.017
L53	8 - 6.42 (53)	TP71.7244x71.2105x0.58 75	1.58	0.00	0.0	134.5730	-86.21	5086.87	0.017
L54	6.42 - 6.17 (54)	TP71.8057x71.7244x0.93 75	0.25	0.00	0.0	213.6880	-86.23	8077.40	0.011
L55	6.17 - 1.17 (55)	TP73.432x71.8057x0.912 5	5.00	0.00	0.0	208.3020	-86.37	7873.81	0.011
L56	1.17 - 0 (56)	TP73.8125x73.432x0.9	1.17	0.00	0.0	210.1980	-89.13	7945.47	0.011

Pole Bending Design Data

Section No.	Elevation ft	Size	M_{ux} kip-ft	ϕM_{nx} kip-ft	Ratio M_{ux} ϕM_{nx}	M_{uy} kip-ft	ϕM_{ny} kip-ft	Ratio M_{uy} ϕM_{ny}
L1	185 - 180 (1)	TP18x18x0.1875	16.07	185.39	0.087	0.00	185.39	0.000
L2	180 - 175 (2)	TP19.6313x18x0.25	43.61	291.96	0.149	0.00	291.96	0.000
L3	175 - 170 (3)	TP21.2625x19.6313x0.25	107.81	343.52	0.314	0.00	343.52	0.000
L4	170 - 165 (4)	TP22.8938x21.2625x0.25	182.99	399.26	0.458	0.00	399.26	0.000
L5	165 - 160 (5)	TP24.525x22.8938x0.25	281.27	459.20	0.613	0.00	459.20	0.000
L6	160 - 155 (6)	TP26.1563x24.525x0.25	382.41	519.54	0.736	0.00	519.54	0.000
L7	155 - 154 (7)	TP26.4825x26.1563x0.25	406.69	530.76	0.766	0.00	530.76	0.000
L8	154 - 153.75 (8) 88	TP26.5641x26.4825x0.36	412.76	785.78	0.525	0.00	785.78	0.000
L9	153.75 - 152.5 (9) 25	TP26.9719x26.5641x0.36	443.21	797.43	0.556	0.00	797.43	0.000
L10	152.5 - 152.25 (10)	TP27.0534x26.9719x0.55	449.33	1191.90	0.377	0.00	1191.90	0.000
L11	152.25 - 151.5 (11)	TP27.2981x27.0534x0.55	467.72	1214.23	0.385	0.00	1214.23	0.000
L12	151.5 - 151.25 (12) 5	TP27.3797x27.2981x0.42	473.87	957.32	0.495	0.00	957.32	0.000
L13	151.25 - 146.25 (13) 25	TP29.0109x27.3797x0.41	598.52	1047.33	0.571	0.00	1047.33	0.000
L14	146.25 - 141.25 (14)	TP30.6422x29.0109x0.4	726.46	1137.03	0.639	0.00	1137.03	0.000
L15	141.25 - 136.25 (15) 38	TP32.2734x30.6422x0.39	857.70	1244.83	0.689	0.00	1244.83	0.000
L16	136.25 - 130 (16) 38	TP34.3125x32.2734x0.39	891.04	1277.08	0.698	0.00	1277.08	0.000
L17	130 - 129 (17) 5	TP34.1331x32.1813x0.47	1054.41	1671.02	0.631	0.00	1671.02	0.000
L18	129 - 124 (18) 25	TP35.7597x34.1331x0.46	1194.62	1791.15	0.667	0.00	1791.15	0.000
L19	124 - 121.42 (19) 5	TP36.599x35.7597x0.462	1268.36	1877.91	0.675	0.00	1877.91	0.000
L20	121.42 - 121.17 (20) 121.17	TP36.6803x36.599x0.5	1275.55	2033.05	0.627	0.00	2033.05	0.000
L21	121.17 - 116.17 (21) 75	TP38.3069x36.6803x0.48	1421.32	2167.88	0.656	0.00	2167.88	0.000
L22	116.17 - 115 (22) 75	TP38.6875x38.3069x0.48	1455.94	2212.01	0.658	0.00	2212.01	0.000
L23	115 - 113.75 (23) 23)	TP39.0938x38.6875x0.55	1493.15	2536.94	0.589	0.00	2536.94	0.000
L24	113.75 - 113.5 (24) 8	TP39.175x39.0938x0.468	1500.62	2185.08	0.687	0.00	2185.08	0.000
L25	113.5 - 108.5 (25) 25)	TP40.8x39.175x0.4625	1651.90	2343.00	0.705	0.00	2343.00	0.000
L26	108.5 - 103.5 (26) 26)	TP42.425x40.8x0.4563	1806.86	2503.53	0.722	0.00	2503.53	0.000
L27	103.5 - 95 (27)	TP45.1875x42.425x0.45	1885.75	2567.42	0.734	0.00	2567.42	0.000
L28	95 - 94 (28) 75	TP44.8525x42.6125x0.58	2112.31	3577.63	0.590	0.00	3577.63	0.000
L29	94 - 91.4 (29) 5	TP45.6845x44.8525x0.57	2198.60	3638.28	0.604	0.00	3638.28	0.000
L30	91.4 - 91.15 (30) 38	TP45.7645x45.6845x0.44	2206.95	2834.07	0.779	0.00	2834.07	0.000
L31	91.15 - 91 (31) 38	TP45.8125x45.7645x0.44	2211.97	2839.22	0.779	0.00	2839.22	0.000
L32	91 - 86 (32)	TP47.4453x45.8125x0.5	2381.26	3433.57	0.694	0.00	3433.57	0.000
L33	86 - 81 (33)	TP49.0781x47.4453x0.5	2554.57	3677.88	0.695	0.00	3677.88	0.000
L34	81 - 76 (34) 38	TP50.7109x49.0781x0.49	2732.00	3876.18	0.705	0.00	3876.18	0.000
L35	76 - 71 (35) 75	TP52.3438x50.7109x0.48	2913.58	4028.01	0.723	0.00	4028.01	0.000
L36	71 - 66 (36) 75	TP53.9766x52.3438x0.48	3099.38	4245.06	0.730	0.00	4245.06	0.000
L37	66 - 63.75 (37) 75	TP54.7113x53.9766x0.48	3184.38	4343.68	0.733	0.00	4343.68	0.000
L38	63.75 - 63.5	TP54.793x54.7113x0.487	3193.88	4354.67	0.733	0.00	4354.67	0.000

Section No.	Elevation ft	Size	M_{ux} kip-ft	ϕM_{nx} kip-ft	Ratio $\frac{M_{ux}}{\phi M_{nx}}$	M_{uy} kip-ft	ϕM_{ny} kip-ft	Ratio $\frac{M_{uy}}{\phi M_{ny}}$
L39	63.5 - 58.5 (38)	TP56.4258x54.793x0.481 5	3386.07	4498.48	0.753	0.00	4498.48	0.000
L40	58.5 - 51 (40) (39)	TP58.875x56.4258x0.481 3	3405.53	4520.28	0.753	0.00	4520.28	0.000
L41	51 - 50 (41)	TP58.4384x55.8391x0.55	3723.32	5681.07	0.655	0.00	5681.07	0.000
L42	50 - 45 (42)	TP60.0629x58.4384x0.55	3927.88	5954.45	0.660	0.00	5954.45	0.000
L43	45 - 40.42 (43)	TP61.551x60.0629x0.543 8	4119.06	6115.80	0.674	0.00	6115.80	0.000
L44	40.42 - 40.17 (44)	TP61.6323x61.551x0.475	4129.60	5111.28	0.808	0.00	5111.28	0.000
L45	40.17 - 40 (45)	TP61.6875x61.6323x0.47 5	4136.77	5118.70	0.808	0.00	5118.70	0.000
L46	40 - 35 (46) 13	TP63.3095x61.6875x0.53	4349.96	6217.93	0.700	0.00	6217.93	0.000
L47	35 - 33 (47) 5	TP63.9583x63.3095x0.52	4436.43	6224.60	0.713	0.00	6224.60	0.000
L48	33 - 32.75 (48)	TP64.0394x63.9583x0.6	4447.28	7433.05	0.598	0.00	7433.05	0.000
L49	32.75 - 19 (49)	TP68.5x64.0394x0.6	4655.52	7742.02	0.601	0.00	7742.02	0.000
L50	19 - 18 (50)	TP67.9579x64.7054x0.6	5107.07	8225.02	0.621	0.00	8225.02	0.000
L51	18 - 13 (51) 75	TP69.5842x67.9579x0.58	5339.23	8323.87	0.641	0.00	8323.87	0.000
L52	13 - 8 (52) 75	TP71.2105x69.5842x0.58	5575.16	8649.92	0.645	0.00	8649.92	0.000
L53	8 - 6.42 (53) 75	TP71.7244x71.2105x0.58	5650.51	8753.50	0.646	0.00	8753.50	0.000
L54	6.42 - 6.17 (54)	TP71.8057x71.7244x0.93 75	5650.51	14600.08	0.387	0.00	14600.08	0.000
L55	6.17 - 1.17 (55)	TP73.432x71.8057x0.912 5	5662.47	14258.75	0.397	0.00	14258.75	0.000
L56	1.17 - 0 (56)	TP73.8125x73.432x0.9	5903.81	14727.83	0.401	0.00	14727.83	0.000

Pole Shear Design Data

Section No.	Elevation ft	Size	$Actual V_u$ K	ϕV_n K	Ratio $\frac{V_u}{\phi V_n}$	$Actual T_u$ kip-ft	ϕT_n kip-ft	Ratio $\frac{T_u}{\phi T_n}$
L1	185 - 180 (1)	TP18x18x0.1875	5.24	121.95	0.043	0.00	191.08	0.000
L2	180 - 175 (2)	TP19.6313x18x0.25	5.77	176.93	0.033	0.00	301.63	0.000
L3	175 - 170 (3)	TP21.2625x19.6313x0.25	14.76	191.82	0.077	0.15	354.54	0.000
L4	170 - 165 (4)	TP22.8938x21.2625x0.25	15.30	206.71	0.074	0.15	411.72	0.000
L5	165 - 160 (5)	TP24.525x22.8938x0.25	19.96	221.60	0.090	0.24	473.18	0.000
L6	160 - 155 (6)	TP26.1563x24.525x0.25	20.50	236.49	0.087	0.24	538.91	0.000
L7	155 - 154 (7)	TP26.4825x26.1563x0.25	24.25	239.47	0.101	0.15	552.57	0.000
L8	154 - 153.75 (8)	TP26.5641x26.4825x0.36 88	24.28	352.72	0.069	0.15	812.73	0.000
L9	153.75 - 152.5 (9) 25	TP26.9719x26.5641x0.36	24.44	352.22	0.069	0.15	824.42	0.000
L10	152.5 - 152.25 (10)	TP27.0534x26.9719x0.55	24.47	532.27	0.046	0.15	1240.90	0.000
L11	152.25 - 151.5 (11)	TP27.2981x27.0534x0.55	24.57	537.19	0.046	0.15	1263.92	0.000
L12	151.5 - 151.25 (12) 5	TP27.3797x27.2981x0.42	24.61	418.30	0.059	0.15	991.81	0.000
L13	151.25 - 146.25 (13) 25	TP29.0109x27.3797x0.41	25.26	430.76	0.059	0.15	1083.63	0.000
L14	146.25 - 141.25 (14)	TP30.6422x29.0109x0.4	25.92	441.71	0.059	0.15	1175.05	0.000
L15	141.25 - 136.25 (15) 38	TP32.2734x30.6422x0.39	26.59	458.36	0.058	0.15	1285.34	0.000
L16	136.25 - 130 (16) 38	TP34.3125x32.2734x0.39	26.75	464.22	0.058	0.15	1318.43	0.000
L17	130 - 129 (17)	TP34.1331x32.1813x0.47	27.69	583.78	0.047	0.15	1728.39	0.000

Section No.	Elevation ft	Size	Actual Vu K	ϕV_n K	$\frac{\text{Ratio } V_u}{\phi V_n}$	Actual T_u kip-ft	ϕT_n kip-ft	$\frac{\text{Ratio } T_u}{\phi T_n}$
		5	25					
L18	129 - 124 (18)	TP35.7597x34.1331x0.46	28.40	596.10	0.048	0.15	1850.81	0.000
L19	124 - 121.42 (19)	TP36.599x35.7597x0.462	28.77	610.28	0.047	0.15	1939.87	0.000
L20	121.42 - 121.17 (20)	TP36.6803x36.599x0.5	28.80	660.56	0.044	0.15	2102.25	0.000
L21	121.17 - 116.17 (21)	TP38.3069x36.6803x0.48	29.50	673.22	0.044	0.15	2239.61	0.000
L22	116.17 - 115 (22)	TP38.6875x38.3069x0.48	29.67	680.00	0.044	0.15	2284.92	0.000
L23	115 - 113.75 (23)	TP39.0938x38.6875x0.55	29.86	774.08	0.039	0.15	2624.46	0.000
L24	113.75 - 113.5 (24)	TP39.175x39.0938x0.468	29.89	662.51	0.045	0.15	2255.65	0.000
L25	113.5 - 108.5 (25)	TP40.8x39.175x0.4625	30.62	681.22	0.045	0.15	2417.13	0.000
L26	108.5 - 103.5 (26)	TP42.425x40.8x0.4563	31.36	699.19	0.045	0.15	2581.21	0.000
L27	103.5 - 95 (27)	TP45.1875x42.425x0.45	31.74	703.07	0.045	0.15	2646.15	0.000
L28	95 - 94 (28)	TP44.8525x42.6125x0.58	32.97	949.59	0.035	0.15	3697.41	0.000
L29	94 - 91.4 (29)	TP45.6845x44.8525x0.57	33.40	947.12	0.035	0.15	3758.13	0.000
L30	91.4 - 91.15 (30)	TP45.7645x45.6845x0.44	33.43	734.35	0.046	0.15	2927.53	0.000
L31	91.15 - 91 (31)	TP45.8125x45.7645x0.44	33.45	735.13	0.046	0.15	2933.73	0.000
L32	91 - 86 (32)	TP47.4453x45.8125x0.5	34.25	857.10	0.040	0.15	3539.35	0.000
L33	86 - 81 (33)	TP49.0781x47.4453x0.5	35.07	886.91	0.040	0.15	3789.83	0.000
L34	81 - 76 (34)	TP50.7109x49.0781x0.49	35.89	905.38	0.040	0.15	3999.27	0.000
L35	76 - 71 (35)	TP52.3438x50.7109x0.48	36.73	923.09	0.040	0.15	4210.62	0.000
L36	71 - 66 (36)	TP53.9766x52.3438x0.48	37.58	952.16	0.039	0.15	4479.95	0.000
L37	66 - 63.75 (37)	TP54.7113x53.9766x0.48	37.96	965.24	0.039	0.15	4603.88	0.000
L38	63.75 - 63.5 (38)	TP54.793x54.7113x0.487	38.00	966.69	0.039	0.15	4617.75	0.000
L39	63.5 - 58.5 (39)	TP56.4258x54.793x0.481	38.86	983.10	0.040	0.15	4837.88	0.000
L40	58.5 - 51 (40)	TP58.875x56.4258x0.481	38.94	985.97	0.039	0.15	4866.16	0.000
L41	51 - 50 (41)	TP58.4384x55.8391x0.55	40.47	1162.58	0.035	0.15	5919.90	0.000
L42	50 - 45 (42)	TP60.0629x58.4384x0.55	41.34	1195.21	0.035	0.15	6256.82	0.000
L43	45 - 40.42 (43)	TP61.551x60.0629x0.543	42.13	1211.30	0.035	0.15	6500.27	0.000
L44	40.42 - 40.17 (44)	TP61.6323x61.551x0.475	42.16	1060.74	0.040	0.15	5706.35	0.000
L45	40.17 - 40 (45)	TP61.6875x61.6323x0.47	42.19	1061.70	0.040	0.15	5716.67	0.000
L46	40 - 35 (46)	TP63.3095x61.6875x0.53	43.06	1217.80	0.035	0.15	6724.91	0.000
L47	35 - 33 (47)	TP63.9583x63.3095x0.52	43.40	1216.03	0.036	0.15	6785.21	0.000
L48	33 - 32.75 (48)	TP64.0394x63.9583x0.6	43.43	1389.89	0.031	0.15	7756.02	0.000
L49	32.75 - 19 (49)	TP68.5x64.0394x0.6	44.23	1423.65	0.031	0.15	8137.37	0.000
L50	19 - 18 (50)	TP67.9579x64.7054x0.6	46.04	1475.74	0.031	0.15	8743.75	0.000
L51	18 - 13 (51)	TP69.5842x67.9579x0.58	46.80	1480.15	0.032	0.15	8983.25	0.000
L52	13 - 8 (52)	TP71.2105x69.5842x0.58	47.56	1515.04	0.031	0.15	9411.75	0.000
L53	8 - 6.42 (53)	TP71.7244x71.2105x0.58	47.81	1526.06	0.031	0.15	9549.17	0.000
L54	6.42 - 6.17	TP71.8057x71.7244x0.93	47.83	2426.00	0.020	0.15	15088.50	0.000

Section No.	Elevation ft	Size	Actual V_u K	ϕV_n K	$\frac{\text{Ratio } V_u}{\phi V_n}$	Actual T_u kip-ft	ϕT_n kip-ft	$\frac{\text{Ratio } T_u}{\phi T_n}$
L55	6.17 - 1.17 (54)	TP73.432x71.8057x0.912	48.00	2372.98	0.020	0.15	14730.25	0.000
L56	1.17 - 0 (55) (56)	TP73.8125x73.432x0.9	48.87	2396.15	0.020	0.15	15207.92	0.000

Pole Interaction Design Data

Section No.	Elevation ft	$\frac{\text{Ratio } P_u}{\phi P_n}$	$\frac{\text{Ratio } M_{ux}}{\phi M_{nx}}$	$\frac{\text{Ratio } M_{uy}}{\phi M_{ny}}$	$\frac{\text{Ratio } V_u}{\phi V_n}$	$\frac{\text{Ratio } T_u}{\phi T_n}$	Comb. Stress Ratio	Allow. Stress Ratio	Criteria
L1	185 - 180 (1)	0.011	0.087	0.000	0.043	0.000	0.100	1.050	4.8.2
L2	180 - 175 (2)	0.008	0.149	0.000	0.033	0.000	0.159	1.050	4.8.2
L3	175 - 170 (3)	0.019	0.314	0.000	0.077	0.000	0.339	1.050	4.8.2
L4	170 - 165 (4)	0.019	0.458	0.000	0.074	0.000	0.483	1.050	4.8.2
L5	165 - 160 (5)	0.022	0.613	0.000	0.090	0.000	0.643	1.050	4.8.2
L6	160 - 155 (6)	0.022	0.736	0.000	0.087	0.000	0.765	1.050	4.8.2
L7	155 - 154 (7)	0.026	0.766	0.000	0.101	0.000	0.802	1.050	4.8.2
L8	154 - 153.75 (8)	0.017	0.525	0.000	0.069	0.000	0.548	1.050	4.8.2
L9	153.75 - 152.5 (9)	0.018	0.556	0.000	0.069	0.000	0.578	1.050	4.8.2
L10	152.5 - 152.25 (10)	0.012	0.377	0.000	0.046	0.000	0.391	1.050	4.8.2
L11	152.25 - 151.5 (11)	0.012	0.385	0.000	0.046	0.000	0.399	1.050	4.8.2
L12	151.5 - 151.25 (12)	0.015	0.495	0.000	0.059	0.000	0.514	1.050	4.8.2
L13	151.25 - 146.25 (13)	0.015	0.571	0.000	0.059	0.000	0.590	1.050	4.8.2
L14	146.25 - 141.25 (14)	0.016	0.639	0.000	0.059	0.000	0.658	1.050	4.8.2
L15	141.25 - 136.25 (15)	0.016	0.689	0.000	0.058	0.000	0.708	1.050	4.8.2
L16	136.25 - 130 (16)	0.016	0.698	0.000	0.058	0.000	0.717	1.050	4.8.2
L17	130 - 129 (17)	0.014	0.631	0.000	0.047	0.000	0.647	1.050	4.8.2
L18	129 - 124 (18)	0.014	0.667	0.000	0.048	0.000	0.683	1.050	4.8.2
L19	124 - 121.42 (19)	0.014	0.675	0.000	0.047	0.000	0.692	1.050	4.8.2
L20	121.42 - 121.17 (20)	0.013	0.627	0.000	0.044	0.000	0.642	1.050	4.8.2
L21	121.17 - 116.17 (21)	0.013	0.656	0.000	0.044	0.000	0.671	1.050	4.8.2
L22	116.17 - 115 (22)	0.013	0.658	0.000	0.044	0.000	0.673	1.050	4.8.2
L23	115 - 113.75 (23)	0.012	0.589	0.000	0.039	0.000	0.602	1.050	4.8.2
L24	113.75 - 113.5 (24)	0.014	0.687	0.000	0.045	0.000	0.703	1.050	4.8.2
L25	113.5 - 108.5 (25)	0.014	0.705	0.000	0.045	0.000	0.721	1.050	4.8.2
L26	108.5 - 103.5 (26)	0.014	0.722	0.000	0.045	0.000	0.738	1.050	4.8.2
L27	103.5 - 95 (27)	0.014	0.734	0.000	0.045	0.000	0.751	1.050	4.8.2
L28	95 - 94 (28)	0.012	0.590	0.000	0.035	0.000	0.604	1.050	4.8.2
L29	94 - 91.4 (29)	0.012	0.604	0.000	0.035	0.000	0.618	1.050	4.8.2
L30	91.4 - 91.15 (30)	0.016	0.779	0.000	0.046	0.000	0.797	1.050	4.8.2
L31	91.15 - 91 (31)	0.016	0.779	0.000	0.046	0.000	0.797	1.050	4.8.2
L32	91 - 86 (32)	0.014	0.694	0.000	0.040	0.000	0.709	1.050	4.8.2
L33	86 - 81 (33)	0.014	0.695	0.000	0.040	0.000	0.711	1.050	4.8.2
L34	81 - 76 (34)	0.015	0.705	0.000	0.040	0.000	0.721	1.050	4.8.2
L35	76 - 71 (35)	0.015	0.723	0.000	0.040	0.000	0.740	1.050	4.8.2

Section No.	Elevation	Ratio P_u	Ratio M_{ux}	Ratio M_{uy}	Ratio V_u	Ratio T_u	Comb. Stress Ratio	Allow. Stress Ratio	Criteria
	ft	ϕP_n	ϕM_{nx}	ϕM_{ny}	ϕV_n	ϕT_n			
L36	71 - 66 (36)	0.015	0.730	0.000	0.039	0.000	0.747	1.050	4.8.2
L37	66 - 63.75 (37)	0.015	0.733	0.000	0.039	0.000	0.750	1.050	4.8.2
L38	63.75 - 63.5 (38)	0.015	0.733	0.000	0.039	0.000	0.750	1.050	4.8.2
L39	63.5 - 58.5 (39)	0.016	0.753	0.000	0.040	0.000	0.770	1.050	4.8.2
L40	58.5 - 51 (40)	0.016	0.753	0.000	0.039	0.000	0.771	1.050	4.8.2
L41	51 - 50 (41)	0.015	0.655	0.000	0.035	0.000	0.671	1.050	4.8.2
L42	50 - 45 (42)	0.015	0.660	0.000	0.035	0.000	0.676	1.050	4.8.2
L43	45 - 40.42 (43)	0.015	0.674	0.000	0.035	0.000	0.690	1.050	4.8.2
L44	40.42 - 40.17 (44)	0.017	0.808	0.000	0.040	0.000	0.827	1.050	4.8.2
L45	40.17 - 40 (45)	0.017	0.808	0.000	0.040	0.000	0.827	1.050	4.8.2
L46	40 - 35 (46)	0.016	0.700	0.000	0.035	0.000	0.717	1.050	4.8.2
L47	35 - 33 (47)	0.016	0.713	0.000	0.036	0.000	0.730	1.050	4.8.2
L48	33 - 32.75 (48)	0.014	0.598	0.000	0.031	0.000	0.613	1.050	4.8.2
L49	32.75 - 19 (49)	0.014	0.601	0.000	0.031	0.000	0.617	1.050	4.8.2
L50	19 - 18 (50)	0.016	0.621	0.000	0.031	0.000	0.638	1.050	4.8.2
L51	18 - 13 (51)	0.017	0.641	0.000	0.032	0.000	0.659	1.050	4.8.2
L52	13 - 8 (52)	0.017	0.645	0.000	0.031	0.000	0.662	1.050	4.8.2
L53	8 - 6.42 (53)	0.017	0.646	0.000	0.031	0.000	0.663	1.050	4.8.2
L54	6.42 - 6.17 (54)	0.011	0.387	0.000	0.020	0.000	0.398	1.050	4.8.2
L55	6.17 - 1.17 (55)	0.011	0.397	0.000	0.020	0.000	0.409	1.050	4.8.2
L56	1.17 - 0 (56)	0.011	0.401	0.000	0.020	0.000	0.412	1.050	4.8.2

Section Capacity Table

Section No.	Elevation ft	Component Type	Size	Critical Element	P K	ϕP_{allow} K	% Capacity	Pass Fail
L1	185 - 180	Pole	TP18x18x0.1875	1	-4.62	426.84	9.5	Pass
L2	180 - 175	Pole	TP19.6313x18x0.25	2	-4.94	619.24	15.1	Pass
L3	175 - 170	Pole	TP21.2625x19.6313x0.25	3	-12.46	671.36	32.3	Pass
L4	170 - 165	Pole	TP22.8938x21.2625x0.25	4	-12.94	723.48	46.0	Pass
L5	165 - 160	Pole	TP24.525x22.8938x0.25	5	-16.56	775.60	61.3	Pass
L6	160 - 155	Pole	TP26.1563x24.525x0.25	6	-17.16	827.72	72.9	Pass
L7	155 - 154	Pole	TP26.4825x26.1563x0.25	7	-20.52	838.14	76.4	Pass
L8	154 - 153.75	Pole	TP26.5641x26.4825x0.3688	8	-20.57	1234.51	52.1	Pass
L9	153.75 - 152.5	Pole	TP26.9719x26.5641x0.3625	9	-20.76	1232.76	55.1	Pass
L10	152.5 - 152.25	Pole	TP27.0534x26.9719x0.55	10	-20.82	1862.95	37.2	Pass
L11	152.25 - 151.5	Pole	TP27.2981x27.0534x0.55	11	-20.98	1880.15	38.0	Pass
L12	151.5 - 151.25	Pole	TP27.3797x27.2981x0.425	12	-21.03	1464.07	48.9	Pass
L13	151.25 - 146.25	Pole	TP29.0109x27.3797x0.4125	13	-21.94	1507.66	56.2	Pass
L14	146.25 - 141.25	Pole	TP30.6422x29.0109x0.4	14	-22.90	1546.00	62.7	Pass
L15	141.25 - 136.25	Pole	TP32.2734x30.6422x0.3938	15	-23.89	1604.25	67.4	Pass
L16	136.25 - 130	Pole	TP34.3125x32.2734x0.3938	16	-24.14	1624.77	68.3	Pass
L17	130 - 129	Pole	TP34.1331x32.1813x0.475	17	-26.35	2043.25	61.6	Pass
L18	129 - 124	Pole	TP35.7597x34.1331x0.4625	18	-27.58	2086.36	65.1	Pass
L19	124 - 121.42	Pole	TP36.599x35.7597x0.4625	19	-28.23	2135.97	65.9	Pass
L20	121.42 - 121.17	Pole	TP36.6803x36.599x0.5	20	-28.30	2311.95	61.2	Pass
L21	121.17 - 116.17	Pole	TP38.3069x36.6803x0.4875	21	-29.66	2356.27	63.9	Pass
L22	116.17 - 115	Pole	TP38.6875x38.3069x0.4875	22	-29.98	2379.99	64.1	Pass
L23	115 - 113.75	Pole	TP39.0938x38.6875x0.55	23	-30.37	2709.28	57.3	Pass
L24	113.75 - 113.5	Pole	TP39.175x39.0938x0.4688	24	-30.44	2318.78	66.9	Pass
L25	113.5 - 108.5	Pole	TP40.8x39.175x0.4625	25	-31.83	2384.29	68.7	Pass
L26	108.5 - 103.5	Pole	TP42.425x40.8x0.4563	26	-33.25	2447.18	70.3	Pass
L27	103.5 - 95	Pole	TP45.1875x42.425x0.45	27	-33.98	2460.75	71.5	Pass
L28	95 - 94	Pole	TP44.8525x42.6125x0.5875	28	-38.01	3323.58	57.5	Pass
L29	94 - 91.4	Pole	TP45.6845x44.8525x0.575	29	-38.97	3314.92	58.8	Pass

Section No.	Elevation ft	Component Type	Size	Critical Element	P K	σP_{allow} K	% Capacity	Pass Fail
L30	91.4 - 91.15	Pole	TP45.7645x45.6845x0.4438	30	-39.05	2570.23	75.9	Pass
L31	91.15 - 91	Pole	TP45.8125x45.7645x0.4438	31	-39.10	2572.95	75.9	Pass
L32	91 - 86	Pole	TP47.4453x45.8125x0.5	32	-40.81	2999.85	67.6	Pass
L33	86 - 81	Pole	TP49.0781x47.4453x0.5	33	-42.57	3104.19	67.7	Pass
L34	81 - 76	Pole	TP50.7109x49.0781x0.4938	34	-44.37	3168.82	68.7	Pass
L35	76 - 71	Pole	TP52.3438x50.7109x0.4875	35	-46.22	3230.82	70.5	Pass
L36	71 - 66	Pole	TP53.9766x52.3438x0.4875	36	-48.11	3332.55	71.1	Pass
L37	66 - 63.75	Pole	TP54.7113x53.9766x0.4875	37	-48.97	3378.33	71.4	Pass
L38	63.75 - 63.5	Pole	TP54.793x54.7113x0.4875	38	-49.08	3383.41	71.4	Pass
L39	63.5 - 58.5	Pole	TP56.4258x54.793x0.4813	39	-51.02	3440.85	73.3	Pass
L40	58.5 - 51	Pole	TP58.875x56.4258x0.4813	40	-51.22	3450.89	73.4	Pass
L41	51 - 50	Pole	TP58.4384x55.8391x0.55	41	-57.26	4069.03	63.9	Pass
L42	50 - 45	Pole	TP60.0629x58.4384x0.55	42	-59.57	4183.22	64.4	Pass
L43	45 - 40.42	Pole	TP61.551x60.0629x0.5438	43	-61.72	4239.53	65.7	Pass
L44	40.42 - 40.17	Pole	TP61.6323x61.551x0.475	44	-61.84	3712.60	78.8	Pass
L45	40.17 - 40	Pole	TP61.6875x61.6323x0.475	45	-61.91	3715.96	78.8	Pass
L46	40 - 35	Pole	TP63.3095x61.6875x0.5313	46	-64.28	4262.32	68.3	Pass
L47	35 - 33	Pole	TP63.9583x63.3095x0.525	47	-65.24	4256.12	69.5	Pass
L48	33 - 32.75	Pole	TP64.0394x63.9583x0.6	48	-65.39	4864.61	58.4	Pass
L49	32.75 - 19	Pole	TP68.5x64.0394x0.6	49	-68.17	4982.76	58.7	Pass
L50	19 - 18	Pole	TP67.9579x64.7054x0.6	50	-79.08	5165.08	60.8	Pass
L51	18 - 13	Pole	TP69.5842x67.9579x0.5875	51	-82.13	5180.52	62.8	Pass
L52	13 - 8	Pole	TP71.2105x69.5842x0.5875	52	-85.23	5302.63	63.1	Pass
L53	8 - 6.42	Pole	TP71.7244x71.2105x0.5875	53	-86.21	5341.21	63.2	Pass
L54	6.42 - 6.17	Pole	TP71.8057x71.7244x0.9375	54	-86.23	8481.27	37.9	Pass
L55	6.17 - 1.17	Pole	TP73.432x71.8057x0.9125	55	-86.37	8267.50	38.9	Pass
L56	1.17 - 0	Pole	TP73.8125x73.432x0.9	56	-89.13	8342.74	39.3	Pass
Summary								
Pole (L45) 78.8								Pass
RATING = 78.8								Pass


*NOTE: Above stress ratios for reinforced sections are approximate. More exact calculations are presented in Appendix C.

APPENDIX B

BASE LEVEL DRAWING



(PROPOSED EQUIPMENT CONFIGURATION)
(2) 3/8" TO 174 FT LEVEL
(2) 13/16" TO 174 FT LEVEL
(1) 7/8" TO 174 FT LEVEL
(12) 1-1/4" TO 174 FT LEVEL



APPENDIX C
ADDITIONAL CALCULATIONS

Pole Geometry

	Pole Height Above Base (ft)	Section Length (ft)	Lap Splice Length (ft)	Number of Sides	Top Diameter (in)	Bottom Diameter (in)	Wall Thickness (in)	Bend Radius (in)	Pole Material
1	185	5	0	12	18	18	0.1875	Auto	A36M-42
2	180	50	5	12	18.00	34.3125	0.25	Auto	A36M-42
3	135	20	0	12	32.18	38.6875	0.25	Auto	A36M-42
4	115	20	6	12	38.69	45.1875	0.3125	Auto	A36M-42
5	101	10	0	12	42.61	45.8125	0.3125	Auto	A36M-42
6	91	40	7	12	45.81	58.875	0.375	Auto	A36M-42
7	58	18	0	12	55.84	61.6875	0.375	Auto	A36M-42
8	40	21	9	12	61.69	68.5	0.4375	Auto	A36M-42
9	28	28	0	12	64.71	73.8125	0.4375	Auto	A36M-42

Reinforcement Configuration

	Bottom Effective Elevation (ft)	Top Effective Elevation (ft)	Type	Model	Number	1	2	3	4	5	6	7	8	9	10	11	12
1	40.42	52.42	plate	CCI-045100_1	3	x			x			x					
2	91.4	121.42	plate	CCI-060100_1	3	x			x			x					
3	121.42	152.5	plate	CCI-045100_2	3		x			x			x		x		
4	6.42	33	plate	CCI-085125_1	4			x		x		x		x		x	
5	33	63.75	plate	CCI-060100_2	3				x			x				x	
6	63.75	99.42	plate	CCI-060100_2	3			x			x				x		
7	113.75	131	plate	CCI-040075_1	3			x			x		x		x		
8	151.5	154	plate	CCI-040075_2	3			x			x		x		x		
9	0	6.42	plate	Titan 73/45_1	6	x	x	x		x	x	x	x			x	
10																	

Reinforcement Details

	B (in)	H (in)	Gross Area (in ²)	Pole Face to Centroid (in)	Bottom Termination Type	Bottom Termination Length (in)	Top Termination Type	Top Termination Length (in)	Lu (in)	Net Area (in ²)	Bolt Hole Size (in)	Reinforcement Material
1	4.5	1	4.5	0.5	PC 8.8 - M20 (100)	18	PC 8.8 - M20 (100)	18.000	20.000	3.250	1.1875	A572-65
2	6	1	6	0.5	PC 8.8 - M20 (100)	30	PC 8.8 - M20 (100)	30.000	16.000	4.750	1.1875	A572-65
3	4.5	1	4.5	0.5	PC 8.8 - M20 (100)	24	PC 8.8 - M20 (100)	24.000	20.000	3.250	1.1875	A572-65
4	8.5	1.25	10.625	0.625	PC 8.8 - M20 (100)	48	PC 8.8 - M20 (100)	51.000	17.000	9.063	1.1875	A572-65
5	6	1	6	0.5	PC 8.8 - M20 (100)	27	PC 8.8 - M20 (100)	27.000	16.000	4.750	1.1875	A572-65
6	6	1	6	0.5	PC 8.8 - M20 (100)	27	PC 8.8 - M20 (100)	27.000	16.000	4.750	1.1875	A572-65
7	4	0.75	3	0.375	PC 8.8 - M20 (100)	15	PC 8.8 - M20 (100)	18.000	16.000	2.063	1.1875	A572-65
8	4	0.75	3	0.375	PC 8.8 - M20 (100)	15	PC 8.8 - M20 (100)	15.000	16.000	2.063	1.1875	A572-65
9	11.6978	0.34366	4.02007	48.00075	Capacity Input	0	Capacity Input	0.000	0.000	3.500	0.0000	A572-65

Connection Details for Custom Reinforcements

Reinforcement	End	# Bolts	N or X	Bolt Spacing (in)	Edge Dist (in)	Weld Grade (ksi)	Transverse (Horiz.) Weld Type	Horiz. Weld Length (in)	Horiz. Groove Depth (in)	Horiz. Groove Angle (deg)	Horiz. Fillet Size (in)	Vertical Weld Length (in)	Vertical Fillet Size (in)	Rev H Connection Capacity (kip)
CCI-045100_1	Top	6	N	3	3	-	-	-	-	-	-	-	-	-
	Bottom	6	N	3	3	-	-	-	-	-	-	-	-	-
CCI-060100_1	Top	10	N	3	3	-	-	-	-	-	-	-	-	-
	Bottom	10	N	3	3	-	-	-	-	-	-	-	-	-
CCI-045100_2	Top	8	N	3	3	-	-	-	-	-	-	-	-	-
	Bottom	8	N	3	3	-	-	-	-	-	-	-	-	-
CCI-085125_1	Top	17	N	3	3	-	-	-	-	-	-	-	-	-
	Bottom	16	N	3	3	-	-	-	-	-	-	-	-	-
CCI-060100_2	Top	9	N	3	3	-	-	-	-	-	-	-	-	-
	Bottom	9	N	3	3	-	-	-	-	-	-	-	-	-
CCI-040075_1	Top	6	N	3	3	-	-	-	-	-	-	-	-	-
	Bottom	5	N	3	3	-	-	-	-	-	-	-	-	-
CCI-040075_2	Top	5	N	3	3	-	-	-	-	-	-	-	-	-
	Bottom	5	N	3	3	-	-	-	-	-	-	-	-	-
Titan 73/45_1	Top	0	-	0	0	0	None	-	-	-	-	-	-	285.12
	Bottom	0	-	0	0	0	None	-	-	-	-	-	-	285.12

TNX Geometry Input

Increment (ft): 5 [Export to TNX](#)

	Section Height (ft)	Section Length (ft)	Lap Splice Length (ft)	Number of Sides	Top Diameter (in)	Bottom Diameter (in)	Wall Thickness (in)	Tapered Pole Grade	Weight Multiplier
1	185 - 180	5	0	12	18.000	18.000	0.1875	A36M-42	1.000
2	180 - 175	5		12	18.000	19.631	0.25	A36M-42	1.000
3	175 - 170	5		12	19.631	21.263	0.25	A36M-42	1.000
4	170 - 165	5		12	21.263	22.894	0.25	A36M-42	1.000
5	165 - 160	5		12	22.894	24.525	0.25	A36M-42	1.000
6	160 - 155	5		12	24.525	26.156	0.25	A36M-42	1.000
7	155 - 154	1		12	26.156	26.483	0.25	A36M-42	1.000
8	154 - 153.75	0.25		12	26.483	26.564	0.36875	A36M-42	0.971
9	153.75 - 152.5	1.25		12	26.564	26.972	0.3625	A36M-42	0.983
10	152.5 - 152.25	0.25		12	26.972	27.053	0.55	A36M-42	0.940
11	152.25 - 151.5	0.75		12	27.053	27.298	0.55	A36M-42	0.935
12	151.5 - 151.25	0.25		12	27.298	27.380	0.425	A36M-42	0.959
13	151.25 - 146.25	5		12	27.380	29.011	0.4125	A36M-42	0.965
14	146.25 - 141.25	5		12	29.011	30.642	0.4	A36M-42	0.975
15	141.25 - 136.25	5		12	30.642	32.273	0.39375	A36M-42	0.972
16	136.25 - 135	6.25	5	12	32.273	34.313	0.39375	A36M-42	0.968
17	135 - 129	6		12	32.181	34.133	0.475	A36M-42	0.968
18	129 - 124	5		12	34.133	35.760	0.4625	A36M-42	0.972
19	124 - 121.42	2.58		12	35.760	36.599	0.4625	A36M-42	0.962
20	121.42 - 121.17	0.25		12	36.599	36.680	0.5	A36M-42	0.968
21	121.17 - 116.17	5		12	36.680	38.307	0.4875	A36M-42	0.971
22	116.17 - 115	1.17	0	12	38.307	38.688	0.4875	A36M-42	0.967
23	115 - 113.75	1.25		12	38.688	39.094	0.55	A36M-42	0.968
24	113.75 - 113.5	0.25		12	39.094	39.175	0.46875	A36M-42	0.978
25	113.5 - 108.5	5		12	39.175	40.800	0.4625	A36M-42	0.978
26	108.5 - 103.5	5		12	40.800	42.425	0.45625	A36M-42	0.980
27	103.5 - 101	8.5	6	12	42.425	45.188	0.45	A36M-42	0.987
28	101 - 94	7		12	42.613	44.853	0.5875	A36M-42	0.966
29	94 - 91.4	2.6		12	44.853	45.685	0.575	A36M-42	0.978
30	91.4 - 91.15	0.25		12	45.685	45.765	0.44375	A36M-42	0.985
31	91.15 - 91	0.15	0	12	45.765	45.813	0.44375	A36M-42	0.984
32	91 - 86	5		12	45.813	47.445	0.5	A36M-42	0.990
33	86 - 81	5		12	47.445	49.078	0.5	A36M-42	0.982
34	81 - 76	5		12	49.078	50.711	0.49375	A36M-42	0.987
35	76 - 71	5		12	50.711	52.344	0.4875	A36M-42	0.992
36	71 - 66	5		12	52.344	53.977	0.4875	A36M-42	0.986
37	66 - 63.75	2.25		12	53.977	54.711	0.4875	A36M-42	0.983
38	63.75 - 63.5	0.25		12	54.711	54.793	0.4875	A36M-42	0.982
39	63.5 - 58.5	5		12	54.793	56.426	0.48125	A36M-42	0.989
40	58.5 - 58	7.5	7	12	56.426	58.875	0.48125	A36M-42	0.988
41	58 - 50	8		12	55.839	58.438	0.55	A36M-42	0.992
42	50 - 45	5		12	58.438	60.063	0.55	A36M-42	0.983
43	45 - 40.42	4.58		12	60.063	61.551	0.54375	A36M-42	0.987
44	40.42 - 40.17	0.25		12	61.551	61.632	0.475	A36M-42	0.983
45	40.17 - 40	0.17	0	12	61.632	61.688	0.475	A36M-42	0.983
46	40 - 35	5		12	61.688	63.310	0.53125	A36M-42	0.993
47	35 - 33	2		12	63.310	63.958	0.525	A36M-42	1.003
48	33 - 32.75	0.25		12	63.958	64.039	0.6	A36M-42	1.078
49	32.75 - 28	13.75	9	12	64.039	68.500	0.6	A36M-42	1.070
50	28 - 18	10		12	64.705	67.958	0.6	A36M-42	1.058
51	18 - 13	5		12	67.958	69.584	0.5875	A36M-42	1.072
52	13 - 8	5		12	69.584	71.210	0.5875	A36M-42	1.065
53	8 - 6.42	1.58		12	71.210	71.724	0.5875	A36M-42	1.063
54	6.42 - 6.17	0.25		12	71.724	71.806	0.9375	A36M-42	0.583
55	6.17 - 1.17	5		12	71.806	73.432	0.9125	A36M-42	0.596
56	1.17 - 0	1.17		12	73.432	73.813	0.9	A36M-42	0.604

TNX Section Forces

Increment (ft):		5	TNX Output		
	Section Height (ft)	P _u (K)	M _{ux} (kip-ft)	V _u (K)	
1	185 - 180	4.62	16.07	5.24	
2	180 - 175	4.94	43.61	5.77	
3	175 - 170	12.46	107.81	14.76	
4	170 - 165	12.94	182.99	15.30	
5	165 - 160	16.56	281.27	19.96	
6	160 - 155	20.67	382.50	23.87	
7	155 - 154	20.51	406.69	24.25	
8	154 - 153.75	20.57	412.76	24.28	
9	153.75 - 152.5	20.76	443.21	24.44	
10	152.5 - 152.25	20.82	449.33	24.47	
11	152.25 - 151.5	20.98	467.72	24.57	
12	151.5 - 151.25	21.03	473.87	24.61	
13	151.25 - 146.25	21.94	598.53	25.26	
14	146.25 - 141.25	22.90	726.46	25.92	
15	141.25 - 136.25	23.89	857.70	26.58	
16	136.25 - 135	24.14	891.04	26.75	
17	135 - 129	26.35	1054.41	27.69	
18	129 - 124	27.58	1194.61	28.40	
19	124 - 121.42	28.23	1268.36	28.77	
20	121.42 - 121.17	28.30	1275.55	28.80	
21	121.17 - 116.17	29.66	1421.32	29.50	
22	116.17 - 115	29.98	1455.94	29.67	
23	115 - 113.75	30.37	1493.15	29.86	
24	113.75 - 113.5	30.44	1500.62	29.89	
25	113.5 - 108.5	31.83	1651.90	30.62	
26	108.5 - 103.5	33.25	1806.86	31.36	
27	103.5 - 101	33.98	1885.75	31.74	
28	101 - 94	38.01	2112.31	32.97	
29	94 - 91.4	38.97	2198.60	33.40	
30	91.4 - 91.15	39.05	2206.95	33.43	
31	91.15 - 91	39.10	2211.97	33.45	
32	91 - 86	40.81	2381.26	34.25	
33	86 - 81	42.57	2554.58	35.07	
34	81 - 76	44.37	2732.00	35.89	
35	76 - 71	46.22	2913.58	36.73	
36	71 - 66	48.11	3099.38	37.58	
37	66 - 63.75	48.97	3184.37	37.96	
38	63.75 - 63.5	49.08	3193.87	38.00	
39	63.5 - 58.5	51.02	3386.07	38.86	
40	58.5 - 58	51.22	3405.52	38.94	
41	58 - 50	57.26	3723.32	40.47	
42	50 - 45	59.57	3927.88	41.34	
43	45 - 40.42	61.72	4119.06	42.13	
44	40.42 - 40.17	61.84	4129.60	42.16	
45	40.17 - 40	61.91	4136.77	42.19	
46	40 - 35	64.28	4349.96	43.06	
47	35 - 33	65.24	4436.43	43.40	
48	33 - 32.75	65.39	4447.28	43.43	
49	32.75 - 28	68.17	4655.53	44.23	
50	28 - 18	79.08	5107.08	46.04	
51	18 - 13	82.13	5339.22	46.80	
52	13 - 8	85.23	5575.16	47.56	
53	8 - 6.42	86.21	5650.51	47.81	
54	6.42 - 6.17	86.36	5662.47	47.83	
55	6.17 - 1.17	89.12	5903.81	48.67	
56	1.17 - 0	89.77	5960.89	48.87	

Analysis Results

Elevation (ft)	Component Type	Size	Critical Element	% Capacity	Pass / Fail
185 - 180	Pole	TP18x18x0.1875	Pole	9.5%	Pass
180 - 175	Pole	TP19.631x18x0.25	Pole	15.1%	Pass
175 - 170	Pole	TP21.263x19.631x0.25	Pole	32.2%	Pass
170 - 165	Pole	TP22.894x21.263x0.25	Pole	45.8%	Pass
165 - 160	Pole	TP24.525x22.894x0.25	Pole	61.1%	Pass
160 - 155	Pole	TP26.156x24.525x0.25	Pole	73.4%	Pass
155 - 154	Pole	TP26.483x26.156x0.25	Pole	76.2%	Pass
154 - 153.75	Pole + Reinf.	TP26.564x26.483x0.3688	Reinf. 8 Tension Rupture	59.3%	Pass
153.75 - 152.5	Pole + Reinf.	TP26.972x26.564x0.3625	Reinf. 8 Tension Rupture	61.9%	Pass
152.5 - 152.25	Pole + Reinf.	TP27.053x26.972x0.55	Reinf. 8 Tension Rupture	42.4%	Pass
152.25 - 151.5	Pole + Reinf.	TP27.298x27.053x0.55	Reinf. 8 Tension Rupture	43.5%	Pass
151.5 - 151.25	Pole + Reinf.	TP27.38x27.298x0.425	Reinf. 3 Tension Rupture	53.3%	Pass
151.25 - 146.25	Pole + Reinf.	TP29.011x27.38x0.4125	Reinf. 3 Tension Rupture	61.1%	Pass
146.25 - 141.25	Pole + Reinf.	TP30.642x29.011x0.4	Reinf. 3 Tension Rupture	67.6%	Pass
141.25 - 136.25	Pole + Reinf.	TP32.273x30.642x0.3938	Reinf. 3 Tension Rupture	73.2%	Pass
136.25 - 135	Pole + Reinf.	TP34.313x32.273x0.3938	Reinf. 3 Tension Rupture	74.4%	Pass
135 - 129	Pole + Reinf.	TP34.133x32.181x0.475	Reinf. 7 Tension Rupture	69.5%	Pass
129 - 124	Pole + Reinf.	TP35.76x34.133x0.4625	Reinf. 7 Tension Rupture	73.2%	Pass
124 - 121.42	Pole + Reinf.	TP36.599x35.76x0.4625	Pole	75.4%	Pass
121.42 - 121.17	Pole + Reinf.	TP36.68x36.599x0.5	Pole	69.3%	Pass
121.17 - 116.17	Pole + Reinf.	TP38.307x36.68x0.4875	Pole	73.9%	Pass
116.17 - 115	Pole + Reinf.	TP38.688x38.307x0.4875	Pole	75.0%	Pass
115 - 113.75	Pole + Reinf.	TP39.094x38.688x0.55	Reinf. 7 Tension Rupture	64.8%	Pass
113.75 - 113.5	Pole + Reinf.	TP39.175x39.094x0.4688	Pole	71.1%	Pass
113.5 - 108.5	Pole + Reinf.	TP40.8x39.175x0.4625	Pole	74.3%	Pass
108.5 - 103.5	Pole + Reinf.	TP42.425x40.8x0.4563	Pole	77.3%	Pass
103.5 - 101	Pole + Reinf.	TP45.188x42.425x0.45	Pole	78.7%	Pass
101 - 94	Pole + Reinf.	TP44.853x42.613x0.5875	Pole	65.0%	Pass
94 - 91.4	Pole + Reinf.	TP45.685x44.853x0.575	Pole	66.4%	Pass
91.4 - 91.15	Pole + Reinf.	TP45.765x45.685x0.4438	Pole	85.9%	Pass
91.15 - 91	Pole + Reinf.	TP45.813x45.765x0.4438	Pole	86.0%	Pass
91 - 86	Pole + Reinf.	TP47.445x45.813x0.5	Pole	71.8%	Pass
86 - 81	Pole + Reinf.	TP49.078x47.445x0.5	Pole	73.6%	Pass
81 - 76	Pole + Reinf.	TP50.711x49.078x0.4938	Pole	75.3%	Pass
76 - 71	Pole + Reinf.	TP52.344x50.711x0.4875	Pole	77.0%	Pass
71 - 66	Pole + Reinf.	TP53.977x52.344x0.4875	Pole	78.6%	Pass
66 - 63.75	Pole + Reinf.	TP54.711x53.977x0.4875	Pole	79.3%	Pass
63.75 - 63.5	Pole + Reinf.	TP54.793x54.711x0.4875	Pole	79.4%	Pass
63.5 - 58.5	Pole + Reinf.	TP56.426x54.793x0.4813	Pole	81.0%	Pass
58.5 - 58	Pole + Reinf.	TP58.875x56.426x0.4813	Pole	81.2%	Pass
58 - 50	Pole + Reinf.	TP58.438x55.839x0.55	Pole	73.7%	Pass
50 - 45	Pole + Reinf.	TP60.063x58.438x0.55	Pole	75.3%	Pass
45 - 40.42	Pole + Reinf.	TP61.551x60.063x0.5438	Pole	76.8%	Pass
40.42 - 40.17	Pole + Reinf.	TP61.632x61.551x0.475	Pole	88.5%	Pass
40.17 - 40	Pole + Reinf.	TP61.688x61.632x0.475	Pole	88.5%	Pass
40 - 35	Pole + Reinf.	TP63.31x61.688x0.5313	Pole	73.5%	Pass
35 - 33	Pole + Reinf.	TP63.958x63.31x0.525	Pole	74.0%	Pass
33 - 32.75	Pole + Reinf.	TP64.039x63.958x0.6	Pole	66.7%	Pass
32.75 - 28	Pole + Reinf.	TP68.5x64.039x0.6	Pole	67.8%	Pass
28 - 18	Pole + Reinf.	TP67.958x64.705x0.6	Pole	71.2%	Pass
18 - 13	Pole + Reinf.	TP69.584x67.958x0.5875	Pole	72.3%	Pass
13 - 8	Pole + Reinf.	TP71.21x69.584x0.5875	Pole	73.4%	Pass
8 - 6.42	Pole + Reinf.	TP71.724x71.21x0.5875	Pole	73.8%	Pass
6.42 - 6.17	Pole + Reinf.	TP71.806x71.724x0.9375	Reinf. 9 Tension Rupture	79.4%	Pass
6.17 - 1.17	Pole + Reinf.	TP73.432x71.806x0.9125	Reinf. 9 Tension Rupture	80.1%	Pass
1.17 - 0	Pole + Reinf.	TP73.813x73.432x0.9	Reinf. 9 Tension Rupture	80.2%	Pass
			Summary		
			Pole	88.5%	Pass
			Reinforcement	80.2%	Pass
			Overall	88.5%	Pass

Additional Calculations

Section Elevation (ft)	Moment of Inertia (in ⁴)			Area (in ²)			% Capacity* (100% Max. Allowable)									
	Pole	Reinf.	Total	Pole	Reinf.	Total	Pole	R1	R2	R3	R4	R5	R6	R7	R8	R9
185 - 180	436	n/a	436	10.74	n/a	10.74	9.5%									
180 - 175	749	n/a	749	15.58	n/a	15.58	15.1%									
175 - 170	955	n/a	955	16.89	n/a	16.89	32.2%									
170 - 165	1195	n/a	1195	18.20	n/a	18.20	45.8%									
165 - 160	1472	n/a	1472	19.51	n/a	19.51	61.1%									
160 - 155	1789	n/a	1789	20.82	n/a	20.82	73.4%									
155 - 154	1857	n/a	1857	21.09	n/a	21.09	76.2%									
154 - 153.75	1875	846	2720	21.15	9.00	30.15	50.8%									59.3%
153.75 - 152.5	1963	871	2834	21.48	9.00	30.48	53.3%									61.9%
152.5 - 152.25	1981	2216	4197	21.55	22.50	44.05	36.5%									42.4%
152.25 - 151.5	2036	2255	4291	21.74	22.50	44.24	37.6%									43.5%
151.5 - 151.25	2054	1371	3426	21.81	13.50	35.31	48.0%									
151.25 - 146.25	2448	1532	3980	23.12	13.50	36.62	56.1%									
146.25 - 141.25	2888	1702	4590	24.43	13.50	37.93	63.4%									
141.25 - 136.25	3379	1880	5259	25.74	13.50	39.24	70.0%									
136.25 - 135	3510	1926	5436	26.07	13.50	39.57	71.6%									
135 - 129	4002	3470	7472	27.24	22.50	49.74	65.4%									69.5%
129 - 124	4607	3798	8405	28.54	22.50	51.04	70.5%									73.2%
124 - 121.42	4941	3973	8914	29.22	22.50	51.72	75.4%									75.0%
121.42 - 121.17	4975	4805	9779	29.28	27.00	56.28	69.3%									68.8%
121.17 - 116.17	5671	5226	10897	30.59	27.00	57.59	73.9%									71.8%
116.17 - 115	5843	5328	11171	30.90	27.00	57.90	75.0%									72.5%
115 - 113.75	7501	5437	12938	38.97	27.00	65.97	59.1%									64.8%
113.75 - 113.5	7549	3659	11208	39.05	18.00	57.05	71.1%									
113.5 - 108.5	8536	3959	12495	40.68	18.00	58.68	74.3%									
108.5 - 103.5	9605	4271	13876	42.32	18.00	60.32	77.3%									
103.5 - 101	10172	4431	14603	43.13	18.00	61.13	78.7%									
101 - 94	11364	9517	20880	44.75	36.00	80.75	65.0%									56.9%
94 - 91.4	12013	9863	21876	45.59	36.00	81.59	66.4%									57.6%
91.4 - 91.15	12076	4948	17025	45.67	18.00	63.67	85.9%									74.5%
91.15 - 91	12115	4958	17073	45.72	18.00	63.72	86.0%									74.5%
91 - 86	16095	5308	21404	56.76	18.00	74.76	71.8%									66.2%
86 - 81	17829	5670	23499	58.72	18.00	76.72	73.6%									66.9%
81 - 76	19683	6044	25727	60.69	18.00	78.69	75.3%									67.5%
76 - 71	21661	6430	28091	62.66	18.00	80.66	77.0%									68.0%
71 - 66	23768	6828	30596	64.63	18.00	82.63	78.6%									68.5%
66 - 63.75	24758	7011	31770	65.52	18.00	83.52	79.3%									68.7%
63.75 - 63.5	24870	7032	31902	65.62	18.00	83.62	79.4%									68.7%
63.5 - 58.5	27177	7448	34624	67.58	18.00	85.58	81.0%									69.1%
58.5 - 58	27415	7490	34905	67.78	18.00	85.78	81.2%									69.1%
58 - 50	30211	13951	44161	70.01	31.50	101.51	73.7%	67.5%								61.7%
50 - 45	32818	14721	47539	71.97	31.50	103.47	75.3%	67.9%								62.1%
45 - 40.42	35334	15446	50780	73.76	31.50	105.26	76.8%	68.3%								62.5%
40.42 - 40.17	35475	8854	44329	73.86	18.00	91.86	88.5%									71.9%
40.17 - 40	35571	8870	44441	73.93	18.00	91.93	88.5%									71.9%
40 - 35	44748	9333	54081	88.44	18.00	106.44	73.5%									63.8%
35 - 33	46148	9522	55669	89.36	18.00	107.36	74.0%									63.8%
33 - 32.75	46436	17211	63646	89.47	42.50	131.97	66.7%									49.9%
32.75 - 28	49889	18029	67918	91.64	42.50	134.14	67.8%									50.1%
28 - 18	55547	19329	74876	94.98	42.50	137.48	71.2%									51.8%
18 - 13	59654	20245	79898	97.27	42.50	139.77	72.3%									52.0%
13 - 8	63958	21182	85140	99.56	42.50	142.06	73.4%									52.2%
8 - 6.42	65360	21482	86842	100.28	42.50	142.78	73.8%									52.3%
6.42 - 6.17	65549	70691	136240	100.40	24.12	124.52	47.0%									79.4%
6.17 - 1.17	70127	72068	142195	102.68	24.12	126.80	48.5%									80.1%
1.17 - 0	71228	72392	143620	103.22	24.12	127.34	48.9%									80.2%

Note: Section

Monopole Base Plate Connection




Site Info	
BU #	825983
Site Name	Middletown_1
Order #	616581 Rev. 0

Analysis Considerations	
TIA-222 Revision	H
Grout Considered:	See Custom Sheet
I_{ar} (in)	See Custom Sheet

Applied Loads	
Moment (kip-ft)	5960.89
Axial Force (kips)	89.77
Shear Force (kips)	48.87

*TIA-222-H Section 15.5 Applied



Connection Properties		Analysis Results	
Anchor Rod Data		Anchor Rod Summary	(units of kips, kip-in)
GROUP 1: (24) 2" ø bolts (A36 N; Fy=36 ksi, Fu=58 ksi) on 68" BC		GROUP 1: Pu_c = 62.88 Vu = 2.04 Mu = n/a	φPn_c = 101.79 φVn = 45.8 φMn = n/a
GROUP 2: (6) 2-3/4" ø bolts (Titan 73/45 N; Fy=90.51429 ksi, Fu=108.6171 ksi) on 169" pos. (deg): 45, 115, 165, 240, 285, 345		Stress Rating 59.0% Pass	
Base Plate Data		GROUP 2: Pu_t = 203.32 Vu = 0 Mu = n/a	φPn_t = 285.12 φVn = 142.56 φMn = n/a
62" ID x 2" Plate (A36; Fy=36 ksi, Fu=58 ksi)		Stress Rating 67.9% Pass	
Stiffener Data		Base Plate Summary	
(24) 18"H x 5"W x 1"T, Notch: 1" plate: Fy= 50 ksi ; weld: Fy= 70 ksi horiz. weld: 0.75" fillet vert. weld: 0.375" fillet		Max Stress (ksi): 12.71 Allowable Stress (ksi): 32.4 Stress Rating: 37.4%	(Roark's Flexural) Pass
Pole Data		Stiffener Summary	
73.8125" x 0.4375" 12-sided pole (A36M-42; Fy=42 ksi, Fu=60 ksi)		Horizontal Weld: 19.9% Vertical Weld: 10.1% Plate Flexure+Shear: 1.9% Plate Tension+Shear: 14.6% Plate Compression: 13.2%	Pass Pass Pass Pass Pass
		Pole Summary	
		Punching Shear: 3.3%	Pass

CCplate

Elevation (ft) 0 (Base)

note: Bending interaction not considered when Grout Considered = "Yes"

Bolt Group	Resist Axial	Resist Shear	Induce Plate Bending	Grout Considered	Apply at BARB Elevation	BARB CL Elevation (ft)
1	Yes	Yes	Yes	No	No	
2	No	No	No	No	No	


Custom Bolt Connection

Bolt	Bolt Group ID	Location (deg.)	Diameter (in)	Material	Bolt Circle (in)	Eta Factor, n:	I _{ar} (in):	Thread Type	Area Override, in ²	Tension Only
1	1	0	2	A36	68	0.5	1.75	N-Included		No
2	1	15	2	A36	68	0.5	1.75	N-Included		No
3	1	30	2	A36	68	0.5	1.75	N-Included		No
4	1	45	2	A36	68	0.5	1.75	N-Included		No
5	1	60	2	A36	68	0.5	1.75	N-Included		No
6	1	75	2	A36	68	0.5	1.75	N-Included		No
7	1	90	2	A36	68	0.5	1.75	N-Included		No
8	1	105	2	A36	68	0.5	1.75	N-Included		No
9	1	120	2	A36	68	0.5	1.75	N-Included		No
10	1	135	2	A36	68	0.5	1.75	N-Included		No
11	1	150	2	A36	68	0.5	1.75	N-Included		No
12	1	165	2	A36	68	0.5	1.75	N-Included		No
13	1	180	2	A36	68	0.5	1.75	N-Included		No
14	1	195	2	A36	68	0.5	1.75	N-Included		No
15	1	210	2	A36	68	0.5	1.75	N-Included		No
16	1	225	2	A36	68	0.5	1.75	N-Included		No
17	1	240	2	A36	68	0.5	1.75	N-Included		No
18	1	255	2	A36	68	0.5	1.75	N-Included		No
19	1	270	2	A36	68	0.5	1.75	N-Included		No
20	1	285	2	A36	68	0.5	1.75	N-Included		No
21	1	300	2	A36	68	0.5	1.75	N-Included		No
22	1	315	2	A36	68	0.5	1.75	N-Included		No
23	1	330	2	A36	68	0.5	1.75	N-Included		No
24	1	345	2	A36	68	0.5	1.75	N-Included		No
25	2	45	2.75	Titan 73/45	169	0.5	0	N-Included	3.5	No
26	2	115	2.75	Titan 73/45	169	0.5	0	N-Included	3.5	No
27	2	165	2.75	Titan 73/45	169	0.5	0	N-Included	3.5	No
28	2	240	2.75	Titan 73/45	169	0.5	0	N-Included	3.5	No
29	2	285	2.75	Titan 73/45	169	0.5	0	N-Included	3.5	No
30	2	345	2.75	Titan 73/45	169	0.5	0	N-Included	3.5	No

Custom Stiffener Connection

Stiffener	Stiffener Group ID	Location (deg.)	Width (in)	Height (in)	Thickness (in)	H. Notch (in)	V. Notch (in)	Grade (ksi)	Weld Type	Groove Depth (in)	Groove Angle (deg.)	H. Fillet Weld Size (in)	V. Fillet Weld Size (in)	Weld Strength (ksi)
1	1	7.5	5	18	1	1	1	50	Fillet			0.75	0.375	70
2	1	22.5	5	18	1	1	1	50	Fillet			0.75	0.375	70
3	1	37.5	5	18	1	1	1	50	Fillet			0.75	0.375	70
4	1	52.5	5	18	1	1	1	50	Fillet			0.75	0.375	70
5	1	67.5	5	18	1	1	1	50	Fillet			0.75	0.375	70
6	1	82.5	5	18	1	1	1	50	Fillet			0.75	0.375	70
7	1	97.5	5	18	1	1	1	50	Fillet			0.75	0.375	70
8	1	112.5	5	18	1	1	1	50	Fillet			0.75	0.375	70
9	1	127.5	5	18	1	1	1	50	Fillet			0.75	0.375	70
10	1	142.5	5	18	1	1	1	50	Fillet			0.75	0.375	70
11	1	157.5	5	18	1	1	1	50	Fillet			0.75	0.375	70
12	1	172.5	5	18	1	1	1	50	Fillet			0.75	0.375	70
13	1	187.5	5	18	1	1	1	50	Fillet			0.75	0.375	70
14	1	202.5	5	18	1	1	1	50	Fillet			0.75	0.375	70
15	1	217.5	5	18	1	1	1	50	Fillet			0.75	0.375	70
16	1	232.5	5	18	1	1	1	50	Fillet			0.75	0.375	70
17	1	247.5	5	18	1	1	1	50	Fillet			0.75	0.375	70
18	1	262.5	5	18	1	1	1	50	Fillet			0.75	0.375	70
19	1	277.5	5	18	1	1	1	50	Fillet			0.75	0.375	70
20	1	292.5	5	18	1	1	1	50	Fillet			0.75	0.375	70
21	1	307.5	5	18	1	1	1	50	Fillet			0.75	0.375	70
22	1	322.5	5	18	1	1	1	50	Fillet			0.75	0.375	70
23	1	337.5	5	18	1	1	1	50	Fillet			0.75	0.375	70
24	1	352.5	5	18	1	1	1	50	Fillet			0.75	0.375	70

Plot Graphic



Pier and Pad Foundation

BU # :	825983
Site Name:	Middletown_1
App. Number:	586243 Rev. 0



TIA-222 Revision: H
Tower Type: Monopole

Top & Bot. Pad Rein. Different?:	<input type="checkbox"/>
Block Foundation?:	<input type="checkbox"/>
Rectangular Pad?:	<input type="checkbox"/>

Superstructure Analysis Reactions		
Compression, P_{comp} :	89.78	kips
Base Shear, V_u comp:	48.86	kips
Moment, M_u :	5960.89	ft-kips
Tower Height, H :	185	ft
BP Dist. Above Fdn, bp_{dist} :	4	in

Foundation Analysis Checks				
	Capacity	Demand	Rating*	Check
Lateral (Sliding) (kips)	402.28	48.86	11.6%	Pass
Bearing Pressure (ksf)	5.82	3.70	63.6%	Pass
Overturning (kip*ft)	8112.94	6502.42	80.1%	Pass
Pier Flexure (Comp.) (kip*ft)	8837.66	6339.56	68.3%	Pass
Pier Compression (kip)	28118.83	151.41	0.5%	Pass
Pad Flexure (kip*ft)	3818.20	2536.33	63.3%	Pass
Pad Shear - 1-way (kips)	896.51	397.45	42.2%	Pass
Pad Shear - 2-way (Comp) (ksi)	0.190	0.059	29.8%	Pass
Flexural 2-way (Comp) (kip*ft)	5013.71	3803.73	72.3%	Pass

*Rating per TIA-222-H Section
15.5

Structural Rating*:	72.3%
Soil Rating*:	80.1%

Pier Properties		
Pier Shape:	Circular	
Pier Diameter, d_{pier} :	7.5	ft
Ext. Above Grade, E :	0.25	ft
Pier Rebar Size, S_c :	8	
Pier Rebar Quantity, m_c :	65	
Pier Tie/Spiral Size, S_t :	4	
Pier Tie/Spiral Quantity, m_t :	8	
Pier Reinforcement Type:	Tie	
Pier Clear Cover, cc_{pier} :	3	in

Pad Properties		
Depth, D :	10.5	ft
Pad Width, W_1 :	25	ft
Pad Thickness, T :	3	ft
Pad Rebar Size (Bottom dir. 2), S_{p2} :	8	
Pad Rebar Quantity (Bottom dir. 2), m_{p2} :	35	
Pad Clear Cover, cc_{pad} :	3	in

Material Properties		
Rebar Grade, F_y :	60	ksi
Concrete Compressive Strength, F'_c :	4	ksi
Dry Concrete Density, δ_c :	150	pcf

Soil Properties		
Total Soil Unit Weight, γ :	110	pcf
Ultimate Net Bearing, Q_{net} :	6.600	ksf
Cohesion, C_u :	1.000	ksf
Friction Angle, φ :	0	degrees
SPT Blow Count, N_{blows} :	13	
Base Friction, μ :	0.3	
Neglected Depth, N :	3.80	ft
Foundation Bearing on Rock?	No	
Groundwater Depth, gw :	16	ft



<--Toggle between Gross and Net

ASCE 7 Hazards Report

Address:
No Address at This Location

Standard: ASCE/SEI 7-16
Risk Category: II
Soil Class: D - Default (see Section 11.4.3)

Elevation: 89.45 ft (NAVD 88)
Latitude: 41.585639
Longitude: -72.714025



Wind

Results:

Wind Speed	*120 Vmph per local jurisdiction requirements
10-year MRI	75 Vmph
25-year MRI	84 Vmph
50-year MRI	90 Vmph
100-year MRI	98 Vmph

Data Source: ASCE/SEI 7-16, Fig. 26.5-1B and Figs. CC.2-1–CC.2-4, and Section 26.5.2

Date Accessed: Wed Jul 20 2022

Value provided is 3-second gust wind speeds at 33 ft above ground for Exposure C Category, based on linear interpolation between contours. Wind speeds are interpolated in accordance with the 7-16 Standard. Wind speeds correspond to approximately a 7% probability of exceedance in 50 years (annual exceedance probability = 0.00143, MRI = 700 years).

Site is in a hurricane-prone region as defined in ASCE/SEI 7-16 Section 26.2. Glazed openings need not be protected against wind-borne debris.





Seismic

Site Soil Class: D - Default (see Section 11.4.3)

Results:

S_s :	0.205	S_{D1} :	0.089
S_1 :	0.055	T_L :	6
F_a :	1.6	PGA :	0.113
F_v :	2.4	PGA_M :	0.178
S_{MS} :	0.328	F_{PGA} :	1.573
S_{M1} :	0.133	I_e :	1
S_{DS} :	0.219	C_v :	0.71

Seismic Design Category B



Data Accessed: Wed Jul 20 2022

Date Source:

USGS Seismic Design Maps based on ASCE/SEI 7-16 and ASCE/SEI 7-16 Table 1.5-2. Additional data for site-specific ground motion procedures in accordance with ASCE/SEI 7-16 Ch. 21 are available from USGS.

Ice

Results:

Ice Thickness: 1.00 in.

Concurrent Temperature: 15 F

Gust Speed 50 mph

Data Source: Standard ASCE/SEI 7-16, Figs. 10-2 through 10-8

Date Accessed: Wed Jul 20 2022

Ice thicknesses on structures in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.

Values provided are equivalent radial ice thicknesses due to freezing rain with concurrent 3-second gust speeds, for a 500-year mean recurrence interval, and temperatures concurrent with ice thicknesses due to freezing rain. Thicknesses for ice accretions caused by other sources shall be obtained from local meteorological studies. Ice thicknesses in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.

The ASCE 7 Hazard Tool is provided for your convenience, for informational purposes only, and is provided "as is" and without warranties of any kind. The location data included herein has been obtained from information developed, produced, and maintained by third party providers; or has been extrapolated from maps incorporated in the ASCE 7 standard. While ASCE has made every effort to use data obtained from reliable sources or methodologies, ASCE does not make any representations or warranties as to the accuracy, completeness, reliability, currency, or quality of any data provided herein. Any third-party links provided by this Tool should not be construed as an endorsement, affiliation, relationship, or sponsorship of such third-party content by or from ASCE.

ASCE does not intend, nor should anyone interpret, the results provided by this Tool to replace the sound judgment of a competent professional, having knowledge and experience in the appropriate field(s) of practice, nor to substitute for the standard of care required of such professionals in interpreting and applying the contents of this Tool or the ASCE 7 standard.

In using this Tool, you expressly assume all risks associated with your use. Under no circumstances shall ASCE or its officers, directors, employees, members, affiliates, or agents be liable to you or any other person for any direct, indirect, special, incidental, or consequential damages arising from or related to your use of, or reliance on, the Tool or any information obtained therein. To the fullest extent permitted by law, you agree to release and hold harmless ASCE from any and all liability of any nature arising out of or resulting from any use of data provided by the ASCE 7 Hazard Tool.



AT&T SITE NUMBER: CTL01044
AT&T SITE NAME: CROMWELL EAST
AT&T FA CODE: 10035130
AT&T PACE NUMBER: MRCTB056281, MRCTB053774, MRCTB055493, MRCTB055102
AT&T PROJECT: 5G NR 1SR CBAND, 5G NR ACTIVATION, 5G NR 1SR

BUSINESS UNIT #: 825983
SITE ADDRESS: 90 INDUSTRIAL PARK ROAD
COUNTY: MIDDLETON, CT 06457
SITE TYPE: MIDDLESEX
MONOPOLE
TOWER HEIGHT: 185'-0"



AT&T SITE NUMBER: **CTL01044**

BU #: **825983**
MIDDLETON_1



90 INDUSTRIAL PARK ROAD
MIDDLETON, CT 06457
EXISTING
185'-0" MONOPOLE

SITE INFORMATION	
CROWN CASTLE USA INC.	MIDDLETON_1
SITE NAME:	
SITE ADDRESS:	90 INDUSTRIAL PARK ROAD MIDDLETON, CT 06457
COUNTY:	MIDDLESEX
MAP/PARCEL #:	06-0018
AREA OF CONSTRUCTION:	EXISTING
LATITUDE:	41° 35' 8.30" N
LONGITUDE:	72° 42' 50.49" W
LAT/LONG TYPE:	NAD83
GROUND ELEVATION:	98'
CURRENT ZONING:	IT - INTERSTATE TRADE
JURISDICTION:	CONNECTICUT SITING COUNCIL
OCCUPANCY CLASSIFICATION:	U
TYPE OF CONSTRUCTION:	IIB
A.D.A. COMPLIANCE:	FACILITY IS UNMANNED AND NOT FOR HUMAN HABITATION
PROPERTY OWNER:	AIRLINE AVENUE REALTY LLC 15 MULLEN RD ENFIELD, CT 06082
TOWER OWNER:	CROWN CASTLE USA INC 2000 CORPORATE DRIVE CANONSBURG, PA 15317
CARRIER/APPLICANT:	AT&T TOWER ASSET GROUP 575 MOROSGO DRIVE ATLANTA, GA 30324-3300
ELECTRIC PROVIDER:	NORTHEAST UTILITIES 800.286-2000
TELCO PROVIDER:	AT&T 800.288.2020

DRAWING INDEX	
SHEET #	SHEET DESCRIPTION
T-1	TITLE SHEET
T-2	GENERAL NOTES
C-1.1	SITE PLAN
C-1.2	EXISTING & FINAL EQUIPMENT PLANS
C-2	FINAL ELEVATION & ANTENNA PLANS
C-3	FINAL EQUIPMENT SCHEDULE
C-4	EQUIPMENT MOUNTING DETAILS
C-5	EQUIPMENT SPECS
G-1	GROUNDING SCHEMATIC
G-2	GROUNDING DETAILS
ATTACHED	PLUMBING DIAGRAM
ATTACHED	MOUNT SPECIFICATIONS

ALL DRAWINGS CONTAINED HEREIN ARE FORMATTED FOR FULL SIZE. CONTRACTOR SHALL VERIFY ALL PLANS AND EXISTING DIMENSIONS AND CONDITIONS ON THE JOB SITE AND SHALL IMMEDIATELY NOTIFY THE ENGINEER IN WRITING OF ANY DISCREPANCIES BEFORE PROCEEDING WITH THE WORK OR BE RESPONSIBLE FOR SAME.

CALL CONNECTICUT ONE CALL
(800) 922-4455 CBYD.COM
CALL 2 WORKING DAYS
BEFORE YOU DIG!



PROJECT TEAM	
A&E FIRM:	B+T GROUP 1717 S. BOULDER AVE. TULSA, OK 74119 MARVIN PHILLIPS marvin.phillips@btgrp.com
CROWN CASTLE USA INC. DISTRICT CONTACTS:	3530 TORINGDON WAY, SUITE 300 CHARLOTTE, NC 28277
	PAUL PEDICONE - PROJECT MANAGER PAUL.PEDICONE@CROWNCastle.COM
	JASON D'AMICO - CONSTRUCTION MANAGER JASON.DAMICO@CROWNCastle.COM

NOTE:
PRIOR TO ACCESSING/ENTERING THE SITE YOU MUST CONTACT THE CROWN NOC AT (800) 788-7011 & CROWN CONSTRUCTION MANAGER.

PROJECT DESCRIPTION	
THE PURPOSE OF THIS PROJECT IS TO ENHANCE BROADBAND CONNECTIVITY AND CAPACITY TO THE EXISTING ELIGIBLE WIRELESS FACILITY.	<ul style="list-style-type: none"> REMOVE (6) KAELES - DBC0061F1V51-2 DIPLEXERS INSTALL (3) QUINTEL - QD6616-7 ANTENNAS INSTALL (6) ERICSSON - AIR 6449 B77D+AIR 6419 B77G STACKED ANTENNAS INSTALL (3) ERICSON - 4415 B25 RADIOS INSTALL (3) DUAL RADIO MOUNTS INSTALL (3) Y CABLES INSTALL (3) 2-1/2" SCH 40 x 6'-0" LONG MOUNT PIPES W/ CROSSOVER HARDWARE INSTALL (1) NEW SABRE - C10899050 PIPE MOUNT ASSEMBLY INSTALL (3) NEW VALMONT - VFA14-WLL-30120 SECTOR MOUNTS INSTALL (6) 2-1/2" SCH 40 x 9'-0" LONG MOUNT PIPES W/ CROSSOVER HARDWARE
TOWER SCOPE OF WORK:	<ul style="list-style-type: none"> RELOCATE (3) ERICSSON - RRUS-32 B30 RADIOS RELOCATE (3) ERICSSON - 4478 B14 RADIOS RELOCATE (3) ERICSSON - RRUS-B6A B2 REMOVE (3) POWERWAVE - 7770 ANTENNAS REMOVE (3) QUINTEL - QS66512-2 ANTENNAS REMOVE (3) CCI - OPA65R-BU6DA-K ANTENNAS REMOVE (6) POWERWAVE - LGP21401 TMAS REMOVE (6) ERICSSON - RRUS-32 B2 RADIOS REMOVE (6) KATHREIN - 782-10250 DIPLEXERS
GROUND SCOPE OF WORK:	<ul style="list-style-type: none"> REPLACE EXISTING BATTERIES WITH (12) 170AH BATTERIES INSTALL (4) GE RECTIFIERS TO EXISTING POWER PLANT INSTALL (2) BATTERY STRINGS INSTALL NEW -48V BATTERY RACK NEXT TO POWER PLANT AND ADDITIONAL (8) 170AH BATTERIES IN BATTERY RACK INSTALL (1) 6648 W/ XCEDE

APPLICABLE CODES/REFERENCE DOCUMENTS	
ALL WORK SHALL BE PERFORMED AND MATERIALS INSTALLED IN ACCORDANCE WITH THE CURRENT EDITIONS OF THE FOLLOWING CODES AS ADOPTED BY THE LOCAL GOVERNING AUTHORITIES. NOTHING IN THESE PLANS IS TO BE CONSTRUED TO PERMIT WORK NOT CONFORMING TO THESE CODES:	
CODE TYPE	CODE
BUILDING	2015 IBC
MECHANICAL	2015 IMC
ELECTRICAL	2017 NEC
REFERENCE DOCUMENTS:	
STRUCTURAL ANALYSIS:	MORRISON HERSHFIELD DATED: 2/1/22
MOUNT ANALYSIS:	B+T GRP DATED: 5/24/2022
RFDS REVISION:	FINAL DATED: 3/15/22
ORDER ID:	586243
REVISION:	0



MTS ENGINEERING P.L.L.C.
BER:2386985
Expires 3/31/23

IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

SHEET NUMBER: **T-1** REVISION: **1**

CROWN CASTLE USA INC. SITE ACTIVITY REQUIREMENTS:

- NOTICE TO PROCEED - NO WORK SHALL COMMENCE PRIOR TO CROWN CASTLE USA INC. WRITTEN NOTICE TO PROCEED (NTP) AND THE ISSUANCE OF A PURCHASE ORDER. PRIOR TO ACCESSING/ENTERING THE SITE YOU MUST CONTACT THE CROWN CASTLE USA INC. NOC AT 800-788-7011 & THE CROWN CASTLE USA INC. CONSTRUCTION MANAGER.
- "LOOK UP" - CROWN CASTLE USA INC. SAFETY CLIMB REQUIREMENT:
THE INTEGRITY OF THE SAFETY CLIMB AND ALL COMPONENTS OF THE CLIMBING FACILITY SHALL BE CONSIDERED DURING ALL STAGES OF DESIGN, INSTALLATION, AND INSPECTION. TOWER MODIFICATION, MOUNT REINFORCEMENTS, AND/OR EQUIPMENT INSTALLATIONS SHALL NOT COMPROMISE THE INTEGRITY OR FUNCTIONAL USE OF THE SAFETY CLIMB OR ANY COMPONENTS OF THE CLIMBING FACILITY ON THE STRUCTURE. THIS SHALL INCLUDE, BUT NOT BE LIMITED TO: PINCHING OF THE WIRE ROPE, BENDING OF THE WIRE ROPE FROM ITS SUPPORTS, DIRECT CONTACT OR CLOSE PROXIMITY TO THE WIRE ROPE WHICH MAY CAUSE FRICTIONAL WEAR, IMPACT TO THE ANCHORAGE POINTS IN ANY WAY, OR TO IMPEDE/BLOCK ITS INTENDED USE. ANY COMPROMISED SAFETY CLIMB, INCLUDING EXISTING CONDITIONS MUST BE TAGGED OUT AND REPORTED TO YOUR CROWN CASTLE USA INC. POC OR CALL THE NOC TO GENERATE A SAFETY CLIMB MAINTENANCE AND CONTRACTOR NOTICE TICKET.
- PRIOR TO THE START OF CONSTRUCTION, ALL REQUIRED JURISDICTIONAL PERMITS SHALL BE OBTAINED. THIS INCLUDES, BUT IS NOT LIMITED TO, BUILDING, ELECTRICAL, MECHANICAL, FIRE, FLOOD ZONE, ENVIRONMENTAL, AND ZONING. AFTER ONSITE ACTIVITIES AND CONSTRUCTION ARE COMPLETED, ALL REQUIRED PERMITS SHALL BE SATISFIED AND CLOSED OUT ACCORDING TO LOCAL JURISDICTIONAL REQUIREMENTS.
- ALL CONSTRUCTION MEANS AND METHODS; INCLUDING BUT NOT LIMITED TO, ERECTION PLANS, RIGGING PLANS, CLIMBING PLANS, AND RESCUE PLANS SHALL BE THE RESPONSIBILITY OF THE GENERAL CONTRACTOR RESPONSIBLE FOR THE EXECUTION OF THE WORK CONTAINED HEREIN, AND SHALL MEET ANSI/ASSE A10.48 (LATEST EDITION); FEDERAL, STATE, AND LOCAL REGULATIONS; AND ANY APPLICABLE INDUSTRY CONSENSUS STANDARDS RELATED TO THE CONSTRUCTION ACTIVITIES BEING PERFORMED. ALL RIGGING PLANS SHALL ADHERE TO ANSI/ASSE A10.48 (LATEST EDITION) AND CROWN CASTLE USA INC. STANDARD CED-STD-10253, INCLUDING THE REQUIRED INVOLVEMENT OF A QUALIFIED ENGINEER FOR CLASS IV CONSTRUCTION, TO CERTIFY THE SUPPORTING STRUCTURE(S) IN ACCORDANCE WITH ANSI/TIA-322 (LATEST EDITION).
- ALL SITE WORK TO COMPLY WITH QAS-STD-10068 "INSTALLATION STANDARDS FOR CONSTRUCTION ACTIVITIES ON CROWN CASTLE USA INC. TOWER SITE," CED-STD-10294 "STANDARD FOR INSTALLATION OF MOUNTS AND APPURTENANCES," AND LATEST VERSION OF ANSI/TIA-1019-A-2012 "STANDARD FOR INSTALLATION, ALTERATION, AND MAINTENANCE OF ANTENNA SUPPORTING STRUCTURES AND ANTENNAS."
- IF THE SPECIFIED EQUIPMENT CAN NOT BE INSTALLED AS SHOWN ON THESE DRAWINGS, THE CONTRACTOR SHALL PROPOSE AN ALTERNATIVE INSTALLATION FOR APPROVAL BY CROWN CASTLE USA INC. PRIOR TO PROCEEDING WITH ANY SUCH CHANGE OF INSTALLATION.
- ALL MATERIALS FURNISHED AND INSTALLED SHALL BE IN STRICT ACCORDANCE WITH ALL APPLICABLE CODES, REGULATIONS AND ORDINANCES. CONTRACTOR SHALL ISSUE ALL APPROPRIATE NOTICES AND COMPLY WITH ALL LAWS, ORDINANCES, RULES, REGULATIONS AND LAWFUL ORDERS OF ANY PUBLIC AUTHORITY REGARDING THE PERFORMANCE OF THE WORK. ALL WORK CARRIED OUT SHALL COMPLY WITH ALL APPLICABLE MUNICIPAL AND UTILITY COMPANY SPECIFICATIONS AND LOCAL JURISDICTIONAL CODES, ORDINANCES AND APPLICABLE REGULATIONS.
- THE CONTRACTOR SHALL INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS UNLESS SPECIFICALLY STATED OTHERWISE.
- THE CONTRACTOR SHALL CONTACT UTILITY LOCATING SERVICES PRIOR TO THE START OF CONSTRUCTION.
- ALL EXISTING ACTIVE SEWER, WATER, GAS, ELECTRIC AND OTHER UTILITIES WHERE ENCOUNTERED IN THE WORK, SHALL BE PROTECTED AT ALL TIMES AND WHERE REQUIRED FOR THE PROPER EXECUTION OF THE WORK, SHALL BE RELOCATED AS DIRECTED BY CONTRACTOR. EXTREME CAUTION SHOULD BE USED BY THE CONTRACTOR WHEN EXCAVATING OR DRILLING PIERS AROUND OR NEAR UTILITIES. CONTRACTOR SHALL PROVIDE SAFETY TRAINING FOR THE WORKING CREW. THIS WILL INCLUDE BUT NOT BE LIMITED TO A) FALL PROTECTION B) CONFINED SPACE C) ELECTRICAL SAFETY D) TRENCHING AND EXCAVATION E) CONSTRUCTION SAFETY PROCEDURES.
- ALL SITE WORK SHALL BE AS INDICATED ON THE STAMPED CONSTRUCTION DRAWINGS AND PROJECT SPECIFICATIONS, LATEST APPROVED REVISION.
- CONTRACTOR SHALL KEEP THE SITE FREE FROM ACCUMULATING WASTE MATERIAL, DEBRIS, AND TRASH AT THE COMPLETION OF THE WORK. IF NECESSARY, RUBBISH, STUMPS, DEBRIS, STICKS, STONES AND OTHER REFUSE SHALL BE REMOVED FROM THE SITE AND DISPOSED OF LEGALLY.
- ALL EXISTING INACTIVE SEWER, WATER, GAS, ELECTRIC AND OTHER UTILITIES, WHICH INTERFERE WITH THE EXECUTION OF THE WORK, SHALL BE REMOVED AND/OR CAPPED, PLUGGED OR OTHERWISE DISCONTINUED AT POINTS WHICH WILL NOT INTERFERE WITH THE EXECUTION OF THE WORK, SUBJECT TO THE APPROVAL OF CONTRACTOR, TOWER OWNER, CROWN CASTLE USA INC., AND/OR LOCAL UTILITIES.
- THE CONTRACTOR SHALL PROVIDE SITE SIGNAGE IN ACCORDANCE WITH THE TECHNICAL SPECIFICATION FOR SITE SIGNAGE REQUIRED BY LOCAL JURISDICTION AND SIGNAGE REQUIRED ON INDIVIDUAL PIECES OF EQUIPMENT, ROOMS, AND SHELTERS.
- THE SITE SHALL BE GRADED TO CAUSE SURFACE WATER TO FLOW AWAY FROM THE CARRIER'S EQUIPMENT AND TOWER AREAS.
- THE SUB GRADE SHALL BE COMPACTED AND BROUGHT TO A SMOOTH UNIFORM GRADE PRIOR TO FINISHED SURFACE APPLICATION.
- THE AREAS OF THE OWNERS PROPERTY DISTURBED BY THE WORK AND NOT COVERED BY THE TOWER, EQUIPMENT OR DRIVEWAY, SHALL BE GRADED TO A UNIFORM SLOPE, AND STABILIZED TO PREVENT EROSION AS SPECIFIED ON THE CONSTRUCTION DRAWINGS AND/OR PROJECT SPECIFICATIONS.
- CONTRACTOR SHALL MINIMIZE DISTURBANCE TO EXISTING SITE DURING CONSTRUCTION. EROSION CONTROL MEASURES, IF REQUIRED DURING CONSTRUCTION, SHALL BE IN CONFORMANCE WITH THE LOCAL GUIDELINES FOR EROSION AND SEDIMENT CONTROL.
- THE CONTRACTOR SHALL PROTECT EXISTING IMPROVEMENTS, PAVEMENTS, CURBS, LANDSCAPING AND STRUCTURES. ANY DAMAGED PART SHALL BE REPAIRED AT CONTRACTOR'S EXPENSE TO THE SATISFACTION OF OWNER.
- CONTRACTOR SHALL LEGALLY AND PROPERLY DISPOSE OF ALL SCRAP MATERIALS SUCH AS COAXIAL CABLES AND OTHER ITEMS REMOVED FROM THE EXISTING FACILITY. ANTENNAS REMOVED SHALL BE RETURNED TO THE OWNER'S DESIGNATED LOCATION.
- CONTRACTOR SHALL LEAVE PREMISES IN CLEAN CONDITION. TRASH AND DEBRIS SHOULD BE REMOVED FROM SITE ON A DAILY BASIS.
- NO FILL OR EMBANKMENT MATERIAL SHALL BE PLACED ON FROZEN GROUND. FROZEN MATERIALS, SNOW OR ICE SHALL NOT BE PLACED IN ANY FILL OR EMBANKMENT.

GREENFIELD GROUNDING NOTES:

- ALL GROUND ELECTRODE SYSTEMS (INCLUDING TELECOMMUNICATION, RADIO, LIGHTNING PROTECTION AND AC POWER GES'S) SHALL BE BONDED TOGETHER AT OR BELOW GRADE, BY TWO OR MORE COPPER BONDING CONDUCTORS IN ACCORDANCE WITH THE NEC.
- THE CONTRACTOR SHALL PERFORM IEEE FALL-OF-POTENTIAL RESISTANCE TO EARTH TESTING (PER IEEE 1100 AND 81) FOR GROUND ELECTRODE SYSTEMS, THE CONTRACTOR SHALL FURNISH AND INSTALL SUPPLEMENTAL GROUND ELECTRODES AS NEEDED TO ACHIEVE A TEST RESULT OF 5 OHMS OR LESS.
- THE CONTRACTOR IS RESPONSIBLE FOR PROPERLY SEQUENCING GROUNDING AND UNDERGROUND CONDUIT INSTALLATION AS TO PREVENT ANY LOSS OF CONTINUITY IN THE GROUNDING SYSTEM OR DAMAGE TO THE CONDUIT AND PROVIDE TESTING RESULTS.
- METAL CONDUIT AND TRAY SHALL BE GROUNDED AND MADE ELECTRICALLY CONTINUOUS WITH LISTED BONDING FITTINGS OR BY BONDING ACROSS THE DISCONTINUITY WITH #6 COPPER WIRE UL APPROVED GROUNDING TYPE CONDUIT CLAMPS.
- METAL RACEWAY SHALL NOT BE USED AS THE NEC REQUIRED EQUIPMENT GROUND CONDUCTOR. STRANDED COPPER CONDUCTORS WITH GREEN INSULATION, SIZED IN ACCORDANCE WITH THE NEC, SHALL BE FURNISHED AND INSTALLED WITH THE POWER CIRCUITS TO BTS EQUIPMENT.
- EACH CABINET FRAME SHALL BE DIRECTLY CONNECTED TO THE MASTER GROUND BAR WITH GREEN INSULATED SUPPLEMENTAL EQUIPMENT GROUND WIRES, #6 STRANDED COPPER OR LARGER FOR INDOOR BTS; #2 BARE SOLID TINNED COPPER FOR OUTDOOR BTS.
- CONNECTIONS TO THE GROUND BUS SHALL NOT BE DOUBLED UP OR STACKED BACK TO BACK CONNECTIONS ON OPPOSITE SIDE OF THE GROUND BUS ARE PERMITTED.
- ALL EXTERIOR GROUND CONDUCTORS BETWEEN EQUIPMENT/GROUND BARS AND THE GROUND RING SHALL BE #2 SOLID TINNED COPPER UNLESS OTHERWISE INDICATED.
- ALUMINUM CONDUCTOR OR COPPER CLAD STEEL CONDUCTOR SHALL NOT BE USED FOR GROUNDING CONNECTIONS.
- USE OF 90° BENDS IN THE PROTECTION GROUNDING CONDUCTORS SHALL BE AVOIDED WHEN 45° BENDS CAN BE ADEQUATELY SUPPORTED.
- EXOTHERMIC WELDS SHALL BE USED FOR ALL GROUNDING CONNECTIONS BELOW GRADE.
- ALL GROUND CONNECTIONS ABOVE GRADE (INTERIOR AND EXTERIOR) SHALL BE FORMED USING HIGH PRESS CRIMPS.
- COMPRESSION GROUND CONNECTIONS MAY BE REPLACED BY EXOTHERMIC WELD CONNECTIONS.
- ICE BRIDGE BONDING CONDUCTORS SHALL BE EXOTHERMICALLY BONDED OR BOLTED TO THE BRIDGE AND THE TOWER GROUND BAR.
- APPROVED ANTIODANT COATINGS (i.e. CONDUCTIVE GEL OR PASTE) SHALL BE USED ON ALL COMPRESSION AND BOLTED GROUND CONNECTIONS.
- ALL EXTERIOR GROUND CONNECTIONS SHALL BE COATED WITH A CORROSION RESISTANT MATERIAL.
- MISCELLANEOUS ELECTRICAL AND NON-ELECTRICAL METAL BOXES, FRAMES AND SUPPORTS SHALL BE BONDED TO THE GROUND RING IN ACCORDANCE WITH THE NEC.
- BOND ALL METALLIC OBJECTS WITHIN 6' FT OF MAIN GROUND RING WITH (1) #2 BARE SOLID TINNED COPPER GROUND CONDUCTOR.
- GROUND CONDUCTORS USED FOR THE FACILITY GROUNDING AND LIGHTNING PROTECTION SYSTEMS SHALL NOT BE ROUTED THROUGH METALLIC OBJECTS THAT FORM A RING AROUND THE CONDUCTOR, SUCH AS METALLIC CONDUITS, METAL SUPPORT CLIPS OR SLEEVES THROUGH WALLS OR FLOORS. WHEN IT IS REQUIRED TO BE HOUSED IN CONDUIT TO MEET CODE REQUIREMENTS OR LOCAL CONDITIONS, NON-METALLIC MATERIAL SUCH AS PVC CONDUIT SHALL BE USED. WHERE USE OF METAL CONDUIT IS UNAVOIDABLE (i.e., NONMETALLIC CONDUIT PROHIBITED BY LOCAL CODE) THE GROUND CONDUCTOR SHALL BE BONDED TO EACH END OF THE METAL CONDUIT.
- ALL GROUNDS THAT TRANSITION FROM BELOW GRADE TO ABOVE GRADE MUST BE #2 BARE SOLID TINNED COPPER IN 3/4" NON-METALLIC, FLEXIBLE CONDUIT FROM 24" BELOW GRADE TO WITHIN 3" TO 6" OF CAD-WELD TERMINATION POINT, THE EXPOSED END OF THE CONDUIT MUST BE SEALED WITH SILICONE CAULK. (ADD TRANSITIONING GROUND STANDARD DETAIL AS WELL).
- BUILDINGS WHERE THE MAIN GROUNDING CONDUCTORS ARE REQUIRED TO BE ROUTED TO GRADE, THE CONTRACTOR SHALL ROUTE TWO GROUNDING CONDUCTORS FROM THE ROOFTOP, TOWERS, AND WATER TOWERS GROUNDING RING, TO THE EXISTING GROUNDING SYSTEM, THE GROUNDING CONDUCTORS SHALL NOT BE SMALLER THAN 2/0 COPPER. ROOFTOP GROUNDING RING SHALL BE BONDED TO THE EXISTING GROUNDING SYSTEM, THE BUILDING STEEL COLUMNS, LIGHTNING PROTECTION SYSTEM, AND BUILDING MAIN WATER LINE (FERROUS OR NONFERROUS METAL PIPING ONLY).

GENERAL NOTES:

- FOR THE PURPOSE OF CONSTRUCTION DRAWING, THE FOLLOWING DEFINITIONS SHALL APPLY:
CONTRACTOR: GENERAL CONTRACTOR RESPONSIBLE FOR CONSTRUCTION
CARRIER: AT&T
TOWER OWNER: CROWN CASTLE USA INC.
- THESE DRAWINGS HAVE BEEN PREPARED USING STANDARDS OF PROFESSIONAL CARE AND COMPLETENESS NORMALLY EXERCISED UNDER SIMILAR CIRCUMSTANCES BY REPUTABLE ENGINEERS IN THIS OR SIMILAR LOCALITIES. IT IS ASSUMED THAT THE WORK DEPICTED WILL BE PERFORMED BY AN EXPERIENCED CONTRACTOR AND/OR WORKPEOPLE WHO HAVE A WORKING KNOWLEDGE OF THE APPLICABLE CODE STANDARDS AND REQUIREMENTS AND OF INDUSTRY ACCEPTED STANDARD GOOD PRACTICE. AS NOT EVERY CONDITION OR ELEMENT IS (OR CAN BE) EXPLICITLY SHOWN ON THESE DRAWINGS, THE CONTRACTOR SHALL USE INDUSTRY ACCEPTED STANDARD GOOD PRACTICE FOR MISCELLANEOUS WORK NOT EXPLICITLY SHOWN.
- THESE DRAWINGS REPRESENT THE FINISHED STRUCTURE. THEY DO NOT INDICATE THE MEANS OR METHODS OF CONSTRUCTION. THE CONTRACTOR SHALL BE SOLELY RESPONSIBLE FOR THE CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES, AND PROCEDURES. THE CONTRACTOR SHALL PROVIDE ALL MEASURES NECESSARY FOR PROTECTION OF LIFE AND PROPERTY DURING CONSTRUCTION. SUCH MEASURES SHALL INCLUDE, BUT NOT BE LIMITED TO, BRACING, FORMWORK-SHORING, ETC. SITE VISITS BY THE ENGINEER OR HIS REPRESENTATIVE WILL NOT INCLUDE INSPECTION OF THESE ITEMS AND IS FOR CONSTRUCTIONAL OBSERVATION OF THE FINISHED STRUCTURE ONLY.
- NOTES AND DETAILS IN THE CONSTRUCTION DRAWINGS SHALL TAKE PRECEDENCE OVER GENERAL NOTES AND TYPICAL DETAILS. WHERE NO DETAILS ARE SHOWN, CONSTRUCTION SHALL CONFORM TO SIMILAR WORK ON THE PROJECT, AND/OR AS PROVIDED IN THE CONTRACT DOCUMENTS. WHERE DISCREPANCIES OCCUR BETWEEN PLANS, DETAILS, GENERAL NOTES, AND SPECIFICATIONS, THE GREATER, MORE STRICT REQUIREMENTS, SHALL GOVERN. IF FURTHER CLARIFICATION IS REQUIRED CONTACT THE ENGINEER OF RECORD.
- SUBSTANTIAL EFFORT HAS BEEN MADE TO PROVIDE ACCURATE DIMENSIONS AND MEASUREMENTS ON THE DRAWINGS TO ASSIST IN THE FABRICATION AND/OR PLACEMENT OF CONSTRUCTION ELEMENTS BUT IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO FIELD VERIFY THE DIMENSIONS, MEASUREMENTS, AND/OR CLEARANCES SHOWN IN THE CONSTRUCTION DRAWINGS PRIOR TO FABRICATION OR CUTTING OF ANY NEW OR EXISTING CONSTRUCTION ELEMENTS. IF IT IS DETERMINED THAT THERE ARE DISCREPANCIES AND/OR CONFLICTS WITH THE CONSTRUCTION DRAWINGS THE ENGINEER OF RECORD IS TO BE NOTIFIED AS SOON AS POSSIBLE.
- PRIOR TO THE SUBMISSION OF BIDS, THE BIDDING CONTRACTOR SHALL VISIT THE CELL SITE TO FAMILIARIZE WITH THE EXISTING CONDITIONS AND TO CONFIRM THAT THE WORK CAN BE ACCOMPLISHED AS SHOWN ON THE CONSTRUCTION DRAWINGS. ANY DISCREPANCY FOUND SHALL BE BROUGHT TO THE ATTENTION OF CROWN CASTLE.
- ALL MATERIALS FURNISHED AND INSTALLED SHALL BE IN STRICT ACCORDANCE WITH ALL APPLICABLE CODES, REGULATIONS AND ORDINANCES. CONTRACTOR SHALL ISSUE ALL APPROPRIATE NOTICES AND COMPLY WITH ALL LAWS, ORDINANCES, RULES, REGULATIONS AND LAWFUL ORDERS OF ANY PUBLIC AUTHORITY REGARDING THE PERFORMANCE OF THE WORK. ALL WORK CARRIED OUT SHALL COMPLY WITH ALL APPLICABLE MUNICIPAL AND UTILITY COMPANY SPECIFICATIONS AND LOCAL JURISDICTIONAL CODES, ORDINANCES AND APPLICABLE REGULATIONS.
- THE CONTRACTOR SHALL INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS UNLESS SPECIFICALLY STATED OTHERWISE.
- IF THE SPECIFIED EQUIPMENT CAN NOT BE INSTALLED AS SHOWN ON THESE DRAWINGS, THE CONTRACTOR SHALL PROPOSE AN ALTERNATIVE INSTALLATION FOR APPROVAL BY THE CARRIER AND CROWN CASTLE PRIOR TO PROCEEDING WITH ANY SUCH CHANGE OF INSTALLATION.
- CONTRACTOR IS TO PERFORM A SITE INVESTIGATION AND IS TO DETERMINE THE BEST ROUTING OF ALL CONDUITS FOR POWER, AND TELCO AND FOR GROUNDING CABLES AS SHOWN IN THE POWER, TELCO, AND GROUNDING PLAN DRAWINGS.
- THE CONTRACTOR SHALL PROTECT EXISTING IMPROVEMENTS, PAVEMENTS, CURBS, LANDSCAPING AND STRUCTURES. ANY DAMAGED PART SHALL BE REPAIRED AT CONTRACTOR'S EXPENSE TO THE SATISFACTION OF CROWN CASTLE USA INC.
- CONTRACTOR SHALL LEGALLY AND PROPERLY DISPOSE OF ALL SCRAP MATERIALS SUCH AS COAXIAL CABLES AND OTHER ITEMS REMOVED FROM THE EXISTING FACILITY. ANTENNAS REMOVED SHALL BE RETURNED TO THE OWNER'S DESIGNATED LOCATION.
- CONTRACTOR SHALL LEAVE PREMISES IN CLEAN CONDITION. TRASH AND DEBRIS SHOULD BE REMOVED FROM SITE ON A DAILY BASIS.

ELECTRICAL INSTALLATION NOTES:

- ALL ELECTRICAL WORK SHALL BE PERFORMED IN ACCORDANCE WITH THE PROJECT SPECIFICATIONS, NEC AND ALL APPLICABLE FEDERAL, STATE, AND LOCAL CODES/ORDINANCES.
- CONDUIT ROUTINGS ARE SCHEMATIC. CONTRACTOR SHALL INSTALL CONDUITS SO THAT ACCESS TO EQUIPMENT IS NOT BLOCKED AND TRIP HAZARDS ARE ELIMINATED.
- WIRING, RACEWAY AND SUPPORT METHODS AND MATERIALS SHALL COMPLY WITH THE REQUIREMENTS OF THE NEC.
- ALL CIRCUITS SHALL BE SEGREGATED AND MAINTAIN MINIMUM CABLE SEPARATION AS REQUIRED BY THE NEC.
- ALL EQUIPMENT SHALL BEAR THE UNDERWRITERS LABORATORIES LABEL OF APPROVAL, AND SHALL CONFORM TO REQUIREMENT OF THE NATIONAL ELECTRICAL CODE.
- ALL OVERCURRENT DEVICES SHALL HAVE AN INTERRUPTING CURRENT RATING THAT SHALL BE GREATER THAN THE SHORT CIRCUIT CURRENT TO WHICH THEY ARE SUBJECTED, 22,000 AIC MINIMUM. VERIFY AVAILABLE SHORT CIRCUIT CURRENT DOES NOT EXCEED THE RATING OF ELECTRICAL EQUIPMENT IN ACCORDANCE WITH ARTICLE 110.24 NEC OR THE MOST CURRENT ADOPTED CODE PRE THE GOVERNING JURISDICTION.
- Each END OF EVERY POWER PHASE CONDUCTOR, GROUNDING CONDUCTOR, AND TELCO CONDUCTOR OR CABLE SHALL BE LABELED WITH COLOR-CODED INSULATION OR ELECTRICAL TAPE (3M BRAND, 1/2" PLASTIC ELECTRICAL TAPE WITH UV PROTECTION, OR EQUAL). THE IDENTIFICATION METHOD SHALL CONFORM WITH NEC AND OSHA.
- ALL ELECTRICAL COMPONENTS SHALL BE CLEARLY LABELED WITH LAMICOID TAGS SHOWING THEIR RATED VOLTAGE, PHASE CONFIGURATION, WIRE CONFIGURATION, POWER OR AMPACITY RATING AND BRANCH CIRCUIT ID NUMBERS (i.e. PANEL BOARD AND CIRCUIT ID'S).
- PANEL BOARDS (ID NUMBERS) SHALL BE CLEARLY LABELED WITH PLASTIC LABELS.
- ALL TIE WRAPS SHALL BE CUT FLUSH WITH APPROVED CUTTING TOOL TO REMOVE SHARP EDGES.
- ALL POWER AND EQUIPMENT GROUND WIRING IN TUBING OR CONDUIT SHALL BE SINGLE COPPER CONDUCTOR (#14 OR LARGER) WITH TYPE THHW, THWN, THHN-2, XHHW-2, THW, THW-2, RHW, OR RHW-2 INSULATION UNLESS OTHERWISE SPECIFIED.
- SUPPLEMENTAL EQUIPMENT GROUND WIRING LOCATED INDOORS SHALL BE SINGLE COPPER CONDUCTOR (#6 OR LARGER) WITH TYPE THHW, THWN, THHN-2, XHHW-2, THW, THW-2, RHW, OR RHW-2 INSULATION UNLESS OTHERWISE SPECIFIED.
- POWER AND CONTROL WIRING IN FLEXIBLE CORD SHALL BE MULTI-CONDUCTOR, TYPE SOOW CORD (#14 OR LARGER) UNLESS OTHERWISE SPECIFIED.
- POWER AND CONTROL WIRING FOR USE IN CABLE TRAY SHALL BE MULTI-CONDUCTOR, TYPE TC CABLE (#14 OR LARGER), WITH TYPE THHW, THWN, THHN-2, XHHW-2, THW, THW-2, RHW, OR RHW-2 INSULATION UNLESS OTHERWISE SPECIFIED.
- ALL POWER AND GROUNDING CONNECTIONS SHALL BE CRIMP-STYLE, COMPRESSION WIRE LUGS AND WIRE NUTS BY THOMAS AND BETTS (OR EQUAL).
- RACEWAY AND CABLE TRAY SHALL BE LISTED OR LABELED FOR ELECTRICAL USE IN ACCORDANCE WITH NEMA, UL, ANSI/IEEE AND NEC.
- ELECTRICAL METALLIC TUBING (EMT), INTERMEDIATE METAL CONDUIT (IMC), OR RIGID METAL CONDUIT (RMC) SHALL BE USED FOR EXPOSED INDOOR LOCATIONS.
- ELECTRICAL METALLIC TUBING (EMT) OR METAL-CLAD CABLE (MC) SHALL BE USED FOR CONCEALED INDOOR LOCATIONS.
- SCHEDULE 40 PVC UNDERGROUND ON STRAIGHTS AND SCHEDULE 80 PVC FOR ALL ELBOWS/90s AND ALL APPROVED ABOVE GRADE PVC CONDUIT.
- LIQUID-TIGHT FLEXIBLE METAL CONDUIT (LIQUID-TITE FLEX) SHALL BE USED INDOORS AND OUTDOORS, WHERE VIBRATION OCCURS OR FLEXIBILITY IS NEEDED.
- CONDUIT AND TUBING FITTINGS SHALL BE THREADED OR COMPRESSION-TYPE AND APPROVED FOR THE LOCATION USED. SET SCREW FITTINGS ARE NOT ACCEPTABLE.
- CABINETS, BOXES AND WIRE WAYS SHALL BE LABELED FOR ELECTRICAL USE IN ACCORDANCE WITH NEMA, UL, ANSI/IEEE AND THE NEC.
- WIREWAYS SHALL BE METAL WITH AN ENAMEL FINISH AND INCLUDE A HINGED COVER, DESIGNED TO SWING OPEN DOWNWARDS (WIREMOLD SPECMATE WIREWAY).
- SLOTTED WIRING DUCT SHALL BE PVC AND INCLUDE COVER (PANDUIT TYPE E OR EQUAL).
- CONDUITS SHALL BE FASTENED SECURELY IN PLACE WITH APPROVED NON-PERFORATED STRAPS AND HANGERS. EXPLOSIVE DEVICES (i.e. POWDER-ACTUATED) FOR ATTACHING HANGERS TO STRUCTURE WILL NOT BE PERMITTED. CLOSELY FOLLOW THE LINES OF THE STRUCTURE, MAINTAIN CLOSE PROXIMITY TO THE STRUCTURE AND KEEP CONDUITS IN TIGHT ENVELOPES. CHANGES IN DIRECTION TO ROUTE AROUND OBSTACLES SHALL BE MADE WITH CONDUIT OUTLET BODIES. CONDUITS SHALL BE INSTALLED IN A NEAT AND WORKMANLIKE MANNER. PARALLEL AND PERPENDICULAR TO STRUCTURE, WALL AND CEILING LINES. ALL CONDUITS SHALL BE FISHED TO CLEAR OBSTRUCTIONS. ENDS OF CONDUITS SHALL BE TEMPORARILY CAPPED FLUSH TO FINISH GRADE TO PREVENT CONCRETE, PLASTER OR DIRT FROM ENTERING. CONDUITS SHALL BE RIGIDLY CLAMPED TO BOXES BY GALVANIZED MALLEABLE IRON BUSHING ON INSIDE AND GALVANIZED MALLEABLE IRON LOCKNUT ON OUTSIDE AND INSIDE.
- EQUIPMENT CABINETS, TERMINAL BOXES, JUNCTION BOXES AND PULL BOXES SHALL BE GALVANIZED OR EPOXY-COATED SHEET STEEL. SHALL MEET OR EXCEED UL 50 AND BE RATED NEMA 1 (OR BETTER) FOR INTERIOR LOCATIONS AND NEMA 3R (OR BETTER) FOR EXTERIOR LOCATIONS.
- METAL RECEPTACLE, SWITCH AND DEVICE BOXES SHALL BE GALVANIZED, EPOXY-COATED OR NON-CORRODING; SHALL MEET OR EXCEED UL 514A AND NEMA 03 1 AND BE RATED NEMA 1 (OR BETTER) FOR INTERIOR LOCATIONS AND WEATHER PROTECTED (WP OR BETTER) FOR EXTERIOR LOCATIONS.
- NONMETALLIC RECEPTACLE, SWITCH AND DEVICE BOXES SHALL MEET OR EXCEED NEMA OS 2 (NEWEST REVISION) AND BE RATED NEMA 1 (OR BETTER) FOR INTERIOR LOCATIONS AND WEATHER PROTECTED (WP OR BETTER) FOR EXTERIOR LOCATIONS.
- THE CONTRACTOR SHALL NOTIFY AND OBTAIN NECESSARY AUTHORIZATION FROM THE CARRIER AND/OR CROWN CASTLE USA INC. BEFORE COMMENCING WORK ON THE AC POWER DISTRIBUTION PANELS.
- THE CONTRACTOR SHALL PROVIDE NECESSARY TAGGING ON THE BREAKERS, CABLES AND DISTRIBUTION PANELS IN ACCORDANCE WITH THE APPLICABLE CODES AND STANDARDS TO SAFEGUARD LIFE AND PROPERTY.
- INSTALL LAMICOID LABEL ON THE METER CENTER TO SHOW "AT&T".
- ALL EMPTY/SPARE CONDUITS THAT ARE INSTALLED ARE TO HAVE A METERED MULE TAPE PULL CORD INSTALLED.

CONDUCTOR COLOR CODE		
SYSTEM	CONDUCTOR	COLOR
120/240V, 1Ø	A PHASE	BLACK
	B PHASE	RED
	NEUTRAL	WHITE
	GROUND	GREEN
120/208V, 3Ø	A PHASE	BLACK
	B PHASE	RED
	C PHASE	BLUE
	NEUTRAL	WHITE
	GROUND	GREEN
277/480V, 3Ø	A PHASE	BROWN
	B PHASE	ORANGE OR PURPLE
	C PHASE	YELLOW
	NEUTRAL	GREY
	GROUND	GREEN
	POS (+)	RED**
	NEG (-)	BLACK**

* SEE NEC 210.5(C)(1) AND (2)

** POLARITY MARKED AT TERMINATION

APWA UNIFORM COLOR CODE:

WHITE	PROPOSED EXCAVATION
PINK	TEMPORARY SURVEY MARKINGS
RED	ELECTRIC POWER LINES, CABLES, CONDUIT, AND LIGHTING CABLES
YELLOW	GAS, OIL, STE

AT&T SITE NUMBER: CTL01044

BU #: 825983

MIDDLETOWN_1


 90 INDUSTRIAL PARK ROAD
 MIDDLETOWN, CT 06457

 EXISTING
 185'-0" MONOPOLE

ISSUED FOR:

REV	DATE	DRWN	DESCRIPTION	DES/QA
A	1/5/22	YX	PRELIMINARY REVIEW	KT
B	2/22/22	YX	PRELIMINARY REVIEW	KT
C	4/12/22	YX	PRELIMINARY REVIEW	KT
0	5/31/22	ANP	CONSTRUCTION	KT
1	8/15/22	BEH	CONSTRUCTION	ANP


 MTS ENGINEERING P.L.L.C.
 BER:2386985
 Expires 3/31/23

 IT IS A VIOLATION OF LAW FOR ANY PERSON,
 UNLESS THEY ARE ACTING UNDER THE DIRECTION
 OF A LICENSED PROFESSIONAL ENGINEER,
 TO ALTER THIS DOCUMENT.


AT&T SITE NUMBER: CTL01044



BU #: 825983
MIDDLETON_1

90 INDUSTRIAL PARK ROAD
MIDDLETON, CT 06457

EXISTING
185'-0" MONPOLE

1 EXISTING EQUIPMENT PLAN

SCALE: 2' 1' 0 2' 1/2"=1'-0" (FULL SIZE)
1/4"=1'-0" (11x17)



GROUND SCOPE OF WORK:

- REPLACE EXISTING BATTERIES WITH (12) 170AH BATTERIES
- INSTALL (3) GE RECTIFIERS TO EXISTING POWER PLANT
- INSTALL NEW -48V BATTERY RACK NEXT TO POWER PLANT AND ADDITIONAL (8) 170AH BATTERIES IN BATTERY RACK
- INSTALL 6648(+XCEDE)

NOTE:

THE POWER DESIGN FOR ANY AC ELECTRICAL POWER CHANGES IS TO BE PERFORMED BY OTHERS AND IS SHOWN HERE FOR REFERENCE PURPOSES ONLY. AT&T IS SOLELY RESPONSIBLE FOR THE ELECTRICAL POWER DESIGN.

ISSUED FOR:


REV	DATE	DRWN	DESCRIPTION	DES/QA
A	1/5/22	YX	PRELIMINARY REVIEW	KT
B	2/22/22	YX	PRELIMINARY REVIEW	KT
C	4/12/22	YX	PRELIMINARY REVIEW	KT
0	5/31/22	ANP	CONSTRUCTION	KT
1	8/15/22	BEH	CONSTRUCTION	ANP



MTS ENGINEERING P.L.L.C.
BER:2386985
Expires 3/31/23

IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

SHEET NUMBER: C-1.2 | REVISION: 1





575 MORSGO DRIVE
ATLANTA, GA 30324-3300



3530 TORINGDON WAY, SUITE 300
CHARLOTTE, NC 28277







1717 S. BOULDER
SUITE 300
TULSA, OK 74119
PH: (918) 587-4630
www.btgrp.com

AT&T SITE NUMBER: CTL01044

BU #: 825983
MIDDLETON_1

90 INDUSTRIAL PARK ROAD
MIDDLETON, CT 06457

EXISTING
185'-0" MONPOLE



"LOOK UP" - CROWN CASTLE USA INC.
SAFETY CLIMB REQUIREMENT:

THE INTEGRITY OF THE SAFETY CLIMB AND ALL COMPONENTS OF THE CLIMBING FACILITY SHALL BE CONSIDERED DURING ALL STAGES OF DESIGN, INSTALLATION, AND INSPECTION. TOWER MODIFICATION, MOUNT REINFORCEMENTS, AND/OR EQUIPMENT INSTALLATIONS SHALL NOT COMPROMISE THE INTEGRITY OR FUNCTIONAL USE OF THE SAFETY CLIMB OR ANY COMPONENTS OF THE CLIMBING FACILITY ON THE STRUCTURE. THIS SHALL INCLUDE, BUT NOT BE LIMITED TO: PINCHING OF THE WIRE ROPE, BENDING OF THE WIRE ROPE FROM ITS SUPPORTS, DIRECT CONTACT OR CLOSE PROXIMITY TO THE WIRE ROPE WHICH MAY CAUSE FRICTIONAL WEAR, IMPACT TO THE ANCHORAGE POINTS IN ANY WAY, OR TO IMPEDE/BLOCK ITS INTENDED USE. ANY COMPROMISED SAFETY CLIMB, INCLUDING EXISTING CONDITIONS MUST BE TAGGED OUT AND REPORTED TO YOUR CROWN CASTLE USA INC. POC OR CALL THE NOC TO GENERATE A SAFETY CLIMB MAINTENANCE AND CONTRACTOR NOTICE TICKET.

INSTALLER NOTES:

1. REFERENCE C-3 FOR FINAL EQUIPMENT SCHEDULE.
2. REFERENCE C-4 FOR NEW EQUIPMENT SPECIFICATIONS.
3. CONTRACTOR TO VERIFY ALL ANTENNA TIP HEIGHTS DO NOT EXCEED BEACON BASE HEIGHT.
4. 3'-0" MINIMUM DISTANCE REQUIRED BETWEEN LTE ANTENNAS ON SAME SECTOR.
5. 6'-0" MINIMUM DISTANCE REQUIRED BETWEEN 700BC & 700DE ANTENNAS ON SAME SECTOR.
6. 4'-0" MINIMUM DISTANCE REQUIRED BETWEEN LTE 700 ANTENNAS ON OPPOSING SECTORS.
7. ALL ANTENNA MEASUREMENT DISTANCES MUST BE EDGE TO EDGE (RELOCATE ANTENNAS AS NEEDED).
8. 8" MINIMUM DISTANCE REQUIRED BETWEEN ANTENNA & RADIO SEE GENERIC EXAMPLE DETAIL ON SHEET C-4.



MTS ENGINEERING P.L.L.C.
BER:2386985
Expires 3/31/23

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SHEET NUMBER: **C-2** REVISION: **1**

NOTE: RFDS BEING USED
DATED 3/15/22 V FINAL



FINAL ANTENNA AND FEEDLINE SCHEDULE																		
POS.	TECH	STATUS	AZIMUTH	ANTENNA TYPE	ANTENNA RAD CENTER	MECHANICAL DOWNTILT	ELECTRICAL DOWNTILT	MAIN COAX SIZE	MAIN COAX LENGTH	COAX QTY	TMA QTY AND MODEL	SURGE PROTECTION	DC/FIBER CABLES	RRHs QTY & MODEL ON TOWER	LOCATION	DIPLEXER ON TOWER	DIPLEXER ON GROUND	RET CABLE
ALPHA SECTOR																		
A1	LTE 700/LTE 1900/LTE AWS/5G 1900/5G AWS	NEW	40°	QUINTEL - QD6616-7	174'-0"	0°	3°/3°/3°/3°/3°/5°/5°/5°	1-1/4"	224'-0"	1	-	DC6-48-60-18-8F	(1) ERICSSON - 4478 B14 (1) ERICSSON - RRUS-32 B66A (1) ERICSSON - 4415 B25 (1) ERICSSON - RRUS-E2 B29 - -	TOWER TOWER TOWER GROUND	N	N	N	
A2	-	-	-	-	-	-	-	-	-	-	-	DC6-48-60-18-8F	(2) 8AWG DC TRUNK 13/16" (1) 12 PAIR FIBER TRUNK 3/8"	SHELTER	N	N	N	
A3	5G CBAND	NEW	40°	ERICSSON - AIR6449 B77D ERICSSON - AIR6419 B77G	172'-3" 175'-9"	0° 0°	0°/0° 0°/0°	-	-	-	-	DC6-48-60-18-8F	INTEGRATED RADIO	TOWER	N	N	N	
A4	-	-	-	-	-	-	-	-	-	-	-	DC6-48-60-18-8F	-	-	-	-	-	
A5	LTE 700/LTE WCS/5G 850	EXISTING	40°	CCI - DMP65R-BU6DA	174'-0"	0°	8°/3°/4°	-	-	-	-	DC6-48-60-18-8F	(1) ERICSSON - 4449 B5/B12 (1) ERICSSON - RRUS-32 B30 (1) Y CABLE - ON 4449	TOWER	N	N	N	
BETA SECTOR																		
B1	LTE 700/LTE 1900/LTE AWS/5G 1900/5G AWS	NEW	150°	QUINTEL - QD6616-7	174'-0"	0°	3°/3°/3°/3°/3°/5°/5°/5°	1-1/4"	224'-0"	1	-	DC6-48-60-18-8F	(1) ERICSSON - 4478 B14 (1) ERICSSON - RRUS-32 B66A (1) ERICSSON - 4415 B25 (1) ERICSSON - RRUS-E2 B29 - -	TOWER TOWER TOWER GROUND	N	N	N	
B2	-	-	-	-	-	-	-	-	-	-	-	DC6-48-60-18-8F	(2) 8AWG DC TRUNK 13/16" (1) 18 PAIR FIBER TRUNK 3/8"	SHELTER	N	N	N	
B3	5G CBAND	NEW	150°	ERICSSON - AIR6449 B77D ERICSSON - AIR6419 B77G	172'-3" 175'-9"	0° 0°	0°/0° 0°/0°	-	-	-	-	DC6-48-60-18-8F	INTEGRATED RADIO	TOWER	N	N	N	
B4	-	-	-	-	-	-	-	-	-	-	-	DC6-48-60-18-8F	-	-	-	-	-	
B5	LTE 700/LTE WCS/5G 850	EXISTING	150°	CCI - DMP65R-BU6DA	174'-0"	0°	8°/3°/4°	-	-	-	-	DC6-48-60-18-8F	(1) ERICSSON - 4449 B5/B12 (1) ERICSSON - RRUS-32 B30 (1) Y CABLE - ON 4449	TOWER	N	N	N	
GAMMA SECTOR																		
C1	LTE 700/LTE 1900/LTE AWS/5G 1900/5G AWS	NEW	270°	QUINTEL - QD6616-7	174'-0"	0°	3°/3°/3°/3°/3°/5°/5°/5°	1-1/4"	224'-0"	1	-	DC9-48-60-24-8C -EV	(1) ERICSSON - 4478 B14 (1) ERICSSON - RRUS-32 B66A (1) ERICSSON - 4415 B25 (1) ERICSSON - RRUS-E2 B29 - -	TOWER TOWER TOWER GROUND	N	N	N	
C2	-	-	-	-	-	-	-	-	-	-	-	DC9-48-60-24-8C -EV	(3) 6AWG DC TRUNK 7/8" (1) 24 PAIR FIBER TRUNK 3/8"	SHELTER	N	N	N	
C3	5G CBAND	NEW	270°	ERICSSON - AIR6449 B77D ERICSSON - AIR6419 B77G	172'-3" 175'-9"	0° 0°	0°/0° 0°/0°	-	-	-	-	DC9-48-60-24-8C -EV	INTEGRATED RADIO	TOWER	N	N	N	
C4	-	-	-	-	-	-	-	-	-	-	-	DC9-48-60-24-8C -EV	-	-	-	-	-	
C5	LTE 700/LTE WCS/5G 850	EXISTING	270°	CCI - DMP65R-BU6DA	174'-0"	0°	8°/3°/4°	-	-	-	-	DC9-48-60-24-8C -EV	(1) ERICSSON - 4449 B5/B12 (1) ERICSSON - RRUS-32 B30 (1) Y CABLE - ON 4449	TOWER	N	N	N	

NOTE: BOLD DENOTES NEW EQUIPMENT



AT&T SITE NUMBER: CTL01044

BU #: 825983

MIDDLETOWN_1

90 INDUSTRIAL PARK ROAD
MIDDLETOWN, CT 06457
EXISTING
185'-0" MONOPOLE

ISSUED FOR:

REV	DATE	DRWN	DESCRIPTION	DES/QA
A	1/5/22	YX	PRELIMINARY REVIEW	KT
B	2/22/22	YX	PRELIMINARY REVIEW	KT
C	4/12/22	YX	PRELIMINARY REVIEW	KT
0	5/31/22	ANP	CONSTRUCTION	KT
1	8/15/22	BEH	CONSTRUCTION	ANP



MTS ENGINEERING P.L.L.C.
BER:2386985
Expires 3/31/23

IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

SHEET NUMBER: C-3
REVISION: 1

AT&T SITE NUMBER: CTL01044

BU #: 825983
MIDDLETOWN_1


90 INDUSTRIAL PARK ROAD
MIDDLETOWN, CT 06457

EXISTING
185'-0" MONOPOLE

1 NOT USED
SCALE: NOT TO SCALE


2 DUAL RRH MOUNT
SCALE: NOT TO SCALE

3 NOT USED
SCALE: NOT TO SCALE



INSTALLER NOTES:


1. COMPLY WITH MANUFACTURERS INSTRUCTIONS TO ENSURE THAT ALL RRHs RECEIVE ELECTRICAL POWER WITHIN 24 HOURS OF BEING REMOVED FROM THE MANUFACTURER'S PACKAGING.
2. DO NOT OPEN RRH PACKAGES IN THE RAIN.
3. ALL PIPES, BRACKETS, AND MISCELLANEOUS HARDWARE TO BE GALVANIZED UNLESS NOTED OTHERWISE.
4. RRHs SHALL NOT BE INSTALLED CLOSER THAN 8" TO ANTENNAS.



4 DUAL RRH MOUNTING DETAIL
SCALE: NOT TO SCALE

INSTALLER NOTE:


1. ALL PIPES, BRACKETS, AND MISCELLANEOUS HARDWARE TO BE GALVANIZED UNLESS NOTED OTHERWISE.



5 ANTENNA MOUNTING DETAIL
SCALE: NOT TO SCALE

INSTALLER NOTES:

1. COMPLY WITH MANUFACTURERS INSTRUCTIONS TO ENSURE THAT ALL RRHs RECEIVE ELECTRICAL POWER WITHIN 24 HOURS OF BEING REMOVED FROM THE MANUFACTURER'S PACKAGING.
2. DO NOT OPEN RRH PACKAGES IN THE RAIN.
3. ALL PIPES, BRACKETS, AND MISCELLANEOUS HARDWARE TO BE GALVANIZED UNLESS NOTED OTHERWISE.



6 STACKED ANTENNA MOUNTING DETAIL
SCALE: NOT TO SCALE

ISSUED FOR:

REV	DATE	DRWN	DESCRIPTION	DES/QA
A	1/5/22	YX	PRELIMINARY REVIEW	KT
B	2/22/22	YX	PRELIMINARY REVIEW	KT
C	4/12/22	YX	PRELIMINARY REVIEW	KT
0	5/31/22	ANP	CONSTRUCTION	KT
1	8/15/22	BEH	CONSTRUCTION	ANP



MTS ENGINEERING P.L.L.C.
BER:2386985
Expires 3/31/23

IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

SHEET NUMBER: C-4
REVISION: 1




AT&T SITE NUMBER: CTL01044

BU #: 825983


MIDDLETOWN_1

90 INDUSTRIAL PARK ROAD
MIDDLETOWN, CT 06457


EXISTING
185'-0" MONOPOLE






1 ANTENNA DETAIL
SCALE: NOT TO SCALE



2 ANTENNA DETAIL
SCALE: NOT TO SCALE



3 ANTENNA DETAIL
SCALE: NOT TO SCALE



ERICSSON - RRUS 4415 B25
WEIGHT: 60.0 LBS
SIZE (HxWxD): 15.0x13.0x8.0 IN.

4 ERICSSON - RRUS 4415 B25
SCALE: NOT TO SCALE

5 NOT USED
SCALE: NOT TO SCALE

6 NOT USED
SCALE: NOT TO SCALE

ISSUED FOR:


REV	DATE	DRWN	DESCRIPTION	DES/QA
A	1/5/22	YX	PRELIMINARY REVIEW	KT
B	2/22/22	YX	PRELIMINARY REVIEW	KT
C	4/12/22	YX	PRELIMINARY REVIEW	KT
0	5/31/22	ANP	CONSTRUCTION	KT
1	8/15/22	BEH	CONSTRUCTION	ANP



MTS ENGINEERING P.L.L.C.
BER:2386985
Expires 3/31/23

IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

SHEET NUMBER: C-5
REVISION: 1



1 GROUNDING SCHEMATIC
SCALE: NOT TO SCALE

GROUNDING PLAN LEGEND:	
---	GROUND WIRE
■	EXOTHERMIC WELD
●	MECHANICAL CONNECTION



AT&T SITE NUMBER: CTL01044

BU #: 825983
MIDDLETON_1

90 INDUSTRIAL PARK ROAD
MIDDLETON, CT 06457

EXISTING
185'-0" MONOPOLE

ISSUED FOR:

REV	DATE	DRWN	DESCRIPTION	DES/QA
A	1/5/22	YX	PRELIMINARY REVIEW	KT
B	2/22/22	YX	PRELIMINARY REVIEW	KT
C	4/12/22	YX	PRELIMINARY REVIEW	KT
0	5/31/22	ANP	CONSTRUCTION	KT
1	8/15/22	BEH	CONSTRUCTION	ANP



MTS ENGINEERING P.L.L.C.
BER:2386985
Expires 3/31/23

IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

SHEET NUMBER: G-1
REVISION: 1

AT&T SITE NUMBER: CTL01044

BU #: 825983
MIDDLETOWN_1

90 INDUSTRIAL PARK ROAD
MIDDLETOWN, CT 06457

EXISTING
185'-0" MONOPOLE


ISSUED FOR:

REV	DATE	DRWN	DESCRIPTION	DES/QA
A	1/5/22	YX	PRELIMINARY REVIEW	KT
B	2/22/22	YX	PRELIMINARY REVIEW	KT
C	4/12/22	YX	PRELIMINARY REVIEW	KT
0	5/31/22	ANP	CONSTRUCTION	KT
1	8/15/22	BEH	CONSTRUCTION	ANP



MTS ENGINEERING P.L.L.C.
BER:2386985
Expires 3/31/23


IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.




NOTES:

1. DOUBLING UP "OR STACKING" OF CONNECTIONS IS NOT PERMITTED.
2. EXTERIOR ANTIOXIDANT JOINT COMPOUND TO BE USED ON ALL EXTERIOR CONNECTIONS.
3. GROUND BAR SHALL NOT BE ISOLATED FROM TOWER. MOUNT DIRECTLY TO TOWER STEEL.

1 ANTENNA SECTOR GROUND BAR DETAIL
SCALE: NOT TO SCALE



4 GROUNDWIRE INSTALLATION
SCALE: NOT TO SCALE




NOTES:

1. DO NOT INSTALL CABLE GROUND KIT AT A BEND AND ALWAYS DIRECT GROUND WIRE DOWN TO GROUND BAR.
2. GROUNDING KIT SHALL BE TYPE AND PART NUMBER AS SUPPLIED OR RECOMMENDED BY CABLE MANUFACTURER.
3. WEATHER PROOFING SHALL BE TWO-PART TAPE KIT, COLD SHRINK SHALL NOT BE USED.

6 CABLE GROUND KIT CONNECTION
SCALE: NOT TO SCALE




7 LUG DETAIL
SCALE: NOT TO SCALE



NOTES:

1. EXTERIOR ANTIOXIDANT JOINT COMPOUND TO BE USED ON ALL EXTERIOR CONNECTIONS.
2. GROUND BAR SHALL NOT BE ISOLATED FROM TOWER. MOUNT DIRECTLY TO TOWER STEEL (TOWER ONLY).
3. GROUND BAR SHALL BE ISOLATED FROM BUILDING OR SHELTER.



2 TOWER/SHELTER GROUND BAR DETAIL
SCALE: NOT TO SCALE



NOTES:


1. DOWN LEAD (HOME RUN) CONDUCTORS ARE NOT TO BE INSTALLED ON CROWN CASTLE USA INC. TOWER. PER THE GROUNDING DOWN CONDUCTOR POLICY QAS-STD-10091, NO MODIFICATION OR DRILLING TO TOWER STEEL IS ALLOWED IN ANY FORM OR FASHION, CAD-WELDING ON THE TOWER AND/OR IN THE AIR ARE NOT PERMITTED.
2. OMIT INSULATOR WHEN MOUNTING TO TOWER STEEL OR PLATFORM STEEL USE INSULATORS WHEN ATTACHING TO BUILDING OR SHELTERS.

3 MECHANICAL LUG CONNECTION
SCALE: NOT TO SCALE






8 HARDWARE DETAIL FOR EXTERIOR CONNECTIONS
SCALE: NOT TO SCALE


WIRE SIZE	BURNDY LUG	BOLT SIZE
#6 GREEN INSULATED	YA6C-2TC38	3/8" - 16 NC SS 2 BOLT
#2 SOLID TINNED	YA3C-2TC38	3/8" - 16 NC SS 2 BOLT
#2 STRANDED	YA2C-2TC38	3/8" - 16 NC SS 2 BOLT
#2/0 STRANDED	YA26-2TC38	3/8" - 16 NC SS 2 BOLT
#4/0 STRANDED	YA28-2N	1/2" - 16 NC SS 2 BOLT





NOTE:
ALL GROUNDING LUGS ARE TO BE INSTALLED PER MANUFACTURER'S SPECIFICATIONS. ALL HARDWARE BOLTS, NUTS, LOCK WASHERS SHALL BE STAINLESS STEEL. ALL HARDWARE ARE TO BE AS FOLLOWS: BOLT, FLAT WASHER, GROUND BAR, GROUND LUG, FLAT WASHER AND NUT.




8 HARDWARE DETAIL FOR EXTERIOR CONNECTIONS
SCALE: NOT TO SCALE









PARTS LIST						
ITEM	QTY	PART NO.	PART DESCRIPTION	LENGTH	UNIT WT.	NET WT.
1	2	X-VFAW	SUPPORT ARM		71.41	142.81
2	1	X-HDCAMTBW	CLAMP WELDMENT FOR BCAM-HD		33.86	33.86
3	1	X-MHTPHD	MULTI-HOLE TAPER PLATE WELDMENT		36.24	36.24
4	1	X-HDCAMSS	ANGLE ADJUSTMENT WELDMENT FOR BCAM-HD		16.39	16.39
5	2	X-VFAPL4	VFA-HD PIVOT PLATE	12 in	15.88	31.77
6	2	X-LCBP4	BENT BACKING PLATE	13 in	20.04	40.09
7	4	X-SPTB	SLIDING PIPE TIE BACK PLATE	5 1/2 in	5.87	23.49
8	1	X-HDCAMSP	POSITIONING PLATE WELDMENT FOR BCAM-HD		2.58	2.58
9	4	X-TBCA	TIE BACK CLIP ANGLE		2.01	8.02
10	10	SCX2	CROSSOVER PLATE	7 in	4.80	47.96
11	4	MCP	CLAMP HALF 1/2" THICK, 11-5/8" LONG	12 1/16 in	3.59	14.37
12	8	DCP	1/2" THICK, 5-3/4" CENTER TO CENTER CLAMP HALF	8 1/8 in	2.36	18.90
13	2	P2126	2-3/8" X 126" (2" SCH. 40) GALVANIZED PIPE	126 in	40.75	81.50
14	2	SCH80-P30174	2-1/2" SCH. 80 PIPE (2.875" O.D. x 0.276" WALL) A500	174 in	118.03	236.05
15	4	A34212	3/4" x 2-1/2" UNC HEX BOLT (A325)	2 1/2 in	0.48	1.92
16	4	G34FW	3/4" HDG USS FLATWASHER		0.06	0.24
17	4	G34LW	3/4" HDG LOCKWASHER		0.04	0.17
18	4	G34NUT	3/4" HDG HEAVY 2H HEX NUT		0.21	0.85
19	8	G58R-18	5/8" x 18" THREADED ROD (HDG.)		1.57	12.54
20	4	G58R-12	5/8" x 12" THREADED ROD (HDG.)		1.05	4.18
21	4	G58R-8	5/8" x 8" THREADED ROD (HDG.)		0.70	2.79
22	4	X-UB5300	5/8" X 3" X 5-1/4" X 2-1/2" U-BOLT (HDG.)		1.15	4.60
23	8	X-UB5258	5/8" X 2-5/8" X 4-1/2" X 2" U-BOLT (HDG.)		1.00	8.00
24	2	G5807	5/8" x 7" HDG HEX BOLT GR5 FULL THREAD	7 in	0.70	1.41
25	1	G5806	5/8" x 6" HDG HEX BOLT GR5 FULL THREAD	6 in	0.62	0.62
26	8	G5804	5/8" x 4" HDG HEX BOLT GR5		0.44	3.55
27	4	G5802	5/8" x 2" HDG HEX BOLT GR5		0.27	1.08
28	8	A582114	5/8" x 2-1/4" HDG A325 HEX BOLT	2 1/4 in	0.31	2.50
29	25	G58FW	5/8" HDG USS FLATWASHER	1/8 in	0.07	1.76
30	66	G58LW	5/8" HDG LOCKWASHER		0.03	1.72
31	71	G58NUT	5/8" HDG HEAVY 2H HEX NUT		0.13	9.22
32	48	X-UB1300	1/2" X 3" X 5" X 2" GALV U-BOLT		0.74	35.45
33	20	X-UB1212	1/2" X 2-1/2" X 4-1/2" X 2" GALV. U-BOLT		0.66	13.25
34	80	G12FW	1/2" HDG USS FLATWASHER	3/32 in	0.03	2.73
35	80	G12LW	1/2" HDG LOCKWASHER	1/8 in	0.01	1.11
36	80	G12NUT	1/2" HDG HEAVY 2H HEX NUT		0.07	5.73
37	5	P30120	2-7/8" x 120" (2-1/2" SCH. 40) GALVANIZED PIPE	120 in	58.07	290.33
						TOTAL WT. # 1139.79

TOLERANCE NOTES

TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE:
SAWED, SHEARED AND GAS CUT EDGES ($\pm 0.030"$)
DRILLED AND GAS CUT HOLES ($\pm 0.030"$) - NO CONING OF HOLES
LASER CUT EDGES AND HOLES ($\pm 0.010"$) - NO CONING OF HOLES
BENDS ARE $\pm 1/2$ DEGREE
ALL OTHER MACHINING ($\pm 0.030"$)
ALL OTHER ASSEMBLY ($\pm 0.060"$)

PROPRIETARY NOTE:
THE DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT INDUSTRIES AND CONSIDERED A TRADE SECRET. ANY USE OR DISCLOSURE WITHOUT THE CONSENT OF VALMONT INDUSTRIES IS STRICTLY PROHIBITED.

DESCRIPTION
14' 6" HEAVY DUTY
V-FRAME ASSEMBLY
W/ 2 STIFF ARMS
& MOUNT PIPES

CPD NO.
SP1

DRAWN BY
CMFL 9/21/2020

ENG. APPROVAL




Engineering
Support Team:
1-888-753-7446

Locations:
New York, NY
Atlanta, GA
Los Angeles, CA
Plymouth, IN
Salem, OR
Dallas, TX


PART NO.
VFA14-WLL-30120

DWG. NO.
VFA14-WLL-30120


TIE-BACK POSITIONS






TIE-BACK POSITION 1
-20° / +20° TOP PARALLEL



TIE-BACK POSITION 2
-20° / -20° TOP CROSS



TIE-BACK POSITION 3
-20° SAME SIDE STACKED



TOLERANCE NOTES

TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE:
 SAWED, SHEARED AND GAS CUT EDGES ($\pm 0.030"$)
 DRILLED AND GAS CUT HOLES ($\pm 0.030"$) - NO CONING OF HOLES
 LASER CUT EDGES AND HOLES ($\pm 0.010"$) - NO CONING OF HOLES
 BENDS ARE $\pm 1/2$ DEGREE
 ALL OTHER MACHINING ($\pm 0.030"$)
 ALL OTHER ASSEMBLY ($\pm 0.060"$)

PROPRIETARY NOTE:
 THE DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT INDUSTRIES AND CONSIDERED A TRADE SECRET. ANY USE OR DISCLOSURE WITHOUT THE CONSENT OF VALMONT INDUSTRIES IS STRICTLY PROHIBITED.

DESCRIPTION

14' 6" HEAVY DUTY
V-FRAME ASSEMBLY
W/ 2 STIFF ARMS
& MOUNT PIPES

CPD NO.
SP1

DRAWN BY
CMFL 9/21/2020

ENG. APPROVAL

PART NO.

**SITE
PRO** 1

Engineering
Support Team:
1-888-753-7446

Locations:
 New York, NY
 Atlanta, GA
 Los Angeles, CA
 Plymouth, IN
 Salem, OR
 Dallas, TX

VFA14-WLL-30120

CLASS
87

SUB
02

DRAWING USAGE
CUSTOMER






CHECKED BY

DWG. NO.

VFA14-WLL-30120

ANGLE CALIBRATING PROCEDURE:

1. MEASURE TOWER TAPER AND PICK LOWER BRACKET HOLE:
 - HOLE A = -2.6° TO 2.6°
 - HOLE B = 1.6° TO 6.8°
2. USE CALIBRATING BOLT TO ADJUST FRAME TO DESIRED TAPER
3. TORQUE LOCKING BOLTS TO 100 ft.-lbs.
4. ADVANCE LOCKING NUT TO POSITIONING PLATE, THEN TIGHTEN.



TOLERANCE NOTES

TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE:
 SAWED, SHEARED AND GAS CUT EDGES ($\pm 0.030"$)
 DRILLED AND GAS CUT HOLES ($\pm 0.030"$) - NO CONING OF HOLES
 LASER CUT EDGES AND HOLES ($\pm 0.010"$) - NO CONING OF HOLES
 BENDS ARE $\pm 1/2$ DEGREE
 ALL OTHER MACHINING ($\pm 0.030"$)
 ALL OTHER ASSEMBLY ($\pm 0.060"$)

PROPRIETARY NOTE:
 THE DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT INDUSTRIES AND CONSIDERED A TRADE SECRET. ANY USE OR DISCLOSURE WITHOUT THE CONSENT OF VALMONT INDUSTRIES IS STRICTLY PROHIBITED.

DESCRIPTION

14' 6" HEAVY DUTY
V-FRAME ASSEMBLY
W/ 2 STIFF ARMS
& MOUNT PIPES

CPD NO.
SP1

DRAWN BY
CMFL 9/21/2020

ENG. APPROVAL




Engineering
Support Team:
1-888-753-7446

Locations:
New York, NY
Atlanta, GA
Los Angeles, CA
Plymouth, IN
Salem, OR
Dallas, TX

VFA14-WLL-30120

VFA14-WLL-30120



DETAIL G

TOLERANCE NOTES

TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE:
 SAWED, SHEARED AND GAS CUT EDGES ($\pm 0.030"$)
 DRILLED AND GAS CUT HOLES ($\pm 0.030"$) - NO CONING OF HOLES
 LASER CUT EDGES AND HOLES ($\pm 0.010"$) - NO CONING OF HOLES
 BENDS ARE $\pm 1/2$ DEGREE
 ALL OTHER MACHINING ($\pm 0.030"$)
 ALL OTHER ASSEMBLY ($\pm 0.060"$)

PROPRIETARY NOTE:
 THE DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT INDUSTRIES AND CONSIDERED A TRADE SECRET. ANY USE OR DISCLOSURE WITHOUT THE CONSENT OF VALMONT INDUSTRIES IS STRICTLY PROHIBITED.

DESCRIPTION

14' 6" HEAVY DUTY
 V-FRAME ASSEMBLY
 W/ 2 STIFF ARMS
 & MOUNT PIPES

CPD NO.
SP1

DRAWN BY
CMFL 9/21/2020


ENG. APPROVAL



Locations:
 New York, NY
 Atlanta, GA
 Los Angeles, CA
 Plymouth, IN
 Salem, OR
 Dallas, TX
 Engineering Support Team:
 1-888-753-7446


VFA14-WLL-30120

VFA14-WLL-30120



**UNISTRUT AND HARDWARE
SOLD SEPARATELY.**

REQUIRES 3/8" HARDWARE



**EQUIPMENT PIPE AND HARDWARE
SOLD SEPARATELY.**

**REQUIRES 1/2" HARDWARE
AND 2-3/8" TO 4-1/2" O.D. PIPE**

TOLERANCE NOTES

TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE:
 SAWED, SHEARED AND GAS CUT EDGES ($\pm 0.030"$)
 DRILLED AND GAS CUT HOLES ($\pm 0.030"$) - NO CONING OF HOLES
 LASER CUT EDGES AND HOLES ($\pm 0.010"$) - NO CONING OF HOLES
 BENDS ARE $\pm 1/2$ DEGREE
 ALL OTHER MACHINING ($\pm 0.030"$)
 ALL OTHER ASSEMBLY ($\pm 0.060"$)

PROPRIETARY NOTE:
 THE DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT INDUSTRIES AND CONSIDERED A TRADE SECRET. ANY USE OR DISCLOSURE WITHOUT THE CONSENT OF VALMONT INDUSTRIES IS STRICTLY PROHIBITED.

DESCRIPTION

**14' 6" HEAVY DUTY
V-FRAME ASSEMBLY
W/ 2 STIFF ARMS
& MOUNT PIPES**

CPD NO.
SP1

DRAWN BY
CMFL 9/21/2020

ENG. APPROVAL



Engineering
Support Team:
1-888-753-7446

Locations:
 New York, NY
 Atlanta, GA
 Los Angeles, CA
 Plymouth, IN
 Salem, OR
 Dallas, TX

VFA14-WLL-30120

CLASS
87

SUB
02

DRAWING USAGE
CUSTOMER

CHECKED BY

PART NO.

VFA14-WLL-30120