



December 06, 2018

Melanie A. Bachman Acting Executive Director Connecticut Siting Council 10 Franklin Square New Britain, CT 06051

RE: Notice of Exempt Modification for Verizon DO Macro:

876370 Verizon Site ID: Chesterfield CT 41 Beckwith Rd. Montville, CT 06370

Latitude: 41° 26′ 7.66′′/ Longitude: 72° 13′ 15.07′′

Dear Ms. Bachman:

Verizon currently maintains twelve (12) antennas at the 160-foot level of the existing 180-foot monopole tower at 41 Beckwith Rd. Montville, CT 06370. The tower is owned by Crown Castle. The Gladys J. Bond Trustees own the property. Verizon now intends to install three (3) RRH's, side-by-side antennas mounts, and three (3) stabilizer kits.

This facility was approved by the Town of Montville Planning and Zoning Commission on September 6th 2000. This approval was made with conditions that were met.

. D1

Please accept this letter as notification pursuant to Regulations of Connecticut State Agencies § 16-50j-73, for construction that constitutes an exempt modification pursuant to R.C.S.A. § 16-50j-72(b)(2). In accordance with R.S.C.A. § 16-50j-73, a copy of this letter is being sent to Mayor Ronald McDaniel, Town of Montville, Vernon D Vesey II, Building Official, Town of Montville, the property owner, and Crown Castle is the tower owner.

- 1. The proposed modifications will not result in an increase in the height of the existing tower.
- 2. The proposed modifications will not require the extension of the site boundary.
- 3. The proposed modification will not increase noise levels at the facility by six decibels or more, or to levels that exceed state and local criteria.

- 4. The operation of the replacement antennas will not increase radio frequency emissions at the facility to a level at or above the Federal Communication Commission safety standard.
- 5. The proposed modifications will not cause a change or alteration in the physical or environmental characteristics of the site.
- 6. The existing structure and its foundation can support the proposed loading.

For the foregoing reasons, Verizon respectfully submits that the proposed modifications to the above-reference telecommunications facility constitutes an exempt modification under R.C.S.A. § 16-50j-72(b)(2). Please send approval/rejection letter to Attn: Jeffrey Barbadora.

Sincerely,

Jeffrey Barbadora Real Estate Specialist 12 Gill Street, Suite 5800, Woburn, MA 01801 781-729-0053 Jeff.Barbadora@crowncastle.com

Attachments:

Tab 1: Exhibit-1: Compound plan and elevation depicting the planned changes

Tab 2: Exhibit-2: Structural Modification Report


Tab 3: Exhibit-3: General Power Density Table Report (RF Emissions Analysis Report)

cc: The Honorable Ronald

McDaniel Town Hall 310 Norwich-New London Tpke. Uncasville, CT 06382

Vernon D. Vesey II, Building Official Town Hall 310 Norwich-New London Tpke. Uncasville, CT 06382

Gladys J Bond Trustee 41 Beckwith Rd. Oakdale, CT 06370



	D 507	RENT OWNER	,		# B004		TILITIE	c	STRT		0	1 LOCAT	TON		ec# 1	of 1		Card #	SMENT	_		-			9:48:35 AM
OND		J TRUSTEE	1	1 L	vel	7 Ele			Paved			Murphy :		Des	cription				aised	Т	Assess	ed	4	00	00
OND	GLADIS	JIRUSTEE				We			1			Chesterf		Res La		1-			60,80	_		2,56	<u>ज</u>	608	86
							otic							Res Ex	ces	1-	2		155,83	0	10	9,08	0	MONTVI	LLE CT
1 BEC	KWITH F	RD		A11 E	1110			<u>EMEN</u>	TAL DA	1TA				Dwelling		1-			172,74			0,92	0		
				Cen		012/001-0 695202	000							Res OF		1-			185,59			9,91			
		1920	020000000	Dou		033202								Util Lan		4-			185,40		12	9,78			
AKDA	VLE.	CT	06370	Sub										Farm La	ano	6-			22,500 377,500		2	88 5,37			
				Мар				C	Callback					lolest		0	۱ '		377,300	١.	2	3,31	١		
				Zoni	ng Notes	WRP-160)																		
				Gis	D	012/001-0	000	Α	SSOC	PID#					<u> </u>		otal	- 1	.160.36	n	55	8.50	ᆔ		
	RECO	RD OF OWN	ERSHIP	5	BK-VC	L/PAGE	SALE	DATE	Q/U	V/I	SALE	PRICE	IVC						SSESS						and the L
OND		J TRUSTEE			0606			9-2015		1	-		0 10	Year	Code	Asses		Year	Code		ssesse		Year	Code	Assesse
		EALY EST			0576			0-2012		i I			0 29	2016	1-1	4:	2,560	2015	1-1		53,7	60	2014	1-1	53,76
OND	LOUIS HE	EALY			0101	0472	08-0	1-1968		1			0	100000000000000000000000000000000000000	1-2		080,		1-2		196,3			1-2	196,3
															1-3		,920		1-3		108,3			1-3	108,3
						1									1-4	12	9,910		1-4		5,6	70		1-4	18,0
															Total		8,500		Total		508,2	200		Total	520,5
			EMPTIC									SSESS					s signat	ure ackn	owledges	a visit	t by a Da	ıta Co	ollector c	or Assessor	
'ear	Code		escriptio	on		Amount	Co	de	Descrip	tion	Nun	nber	Am	ount	Com	m Int									
																			APPR	AISE	DVAL	UE S	SUMM	ARY	
		<u> </u>			Total	0	00									Ar	praise	d Bldg.	Value (C.	ard)					172,7
	77.77					ESSING		BORH	OOD							Ar	oraise	XF (B) Value (I	Blda)			- 1		
	NBHD		NBH	ID Name		Street In				Trac	cing			Bat	ch) Value (185.5
	0001															1 .					,				
							IOTES		-	-			_			Ar	praise	d Land \	Value (Bl	dg)					802,0
ELL S	ITE						V58	0 P1 1/	/29/13 E	ASEM	ENT S	ALE/AS	SIGN O	F		Sp	ecial L	and Val	ue						26,2
2000 N	MONTH X	(12 = \$24,000	ì				ΙFΑ	SE VS	80 P1 10	000 E	ASEM	ENT W	/20' RO	W		To	tal App	raised l	Parcel Va	alue					1,160,3
									00111	0,000 L	J (OLIV		20 110			V	luation	Method	i						
		1% = \$185,40					\$40	5,000								١,٠	iuation	Wellio	•				- 1		
C12: N	NEW FOR	RESTRY REP	ORT, FO	OREST A	CRES		VC1	5: SHE	EDS & B	ARNS	REMO	VED													
ROM ·	187 AC T	O 151 AC. O\	/ERALL	ACREA	SE.		201	6 ADD	ED CELI	L TOW	ER FR	ROM PIE	10133	7		Ad	justme	nt							
ORRE	CTION F	ROM 237 AC	TO 226	6 AC												Т	ntal And	oraised	Parcel V	alue			1	,160,360	
	.0110111	TOW ZOT TO	. 10 220	571O.	RII	ILDING F	PERMIT	RECC	ORD								nai Ap	pruiscu			CHANG	FH		*	
ermit	ID I Iss	sue Date	Туре	T	escription		mount		p Date	1 % (Comp	Date	Comp	C	omments	6	Date	T	Туре				Cd		st/Result
017-0	036 02	-28-2017 00					8,80				100		1-2017	CA-INS	TALL N	EW 2 0	3-20-20)15			L	В	06 Pr	ermit Insp	
017-0		-28-2017 79					15,000				100		7-2017		RIZON R		1-13-20	011			K	(N	00 In	terior + Ex	terior Insp
016-0		-30-2016 CN					43,50		0015		100	05-17	7-2017		L TOW										
/O 2013-0		-22-2015 79 -06-2013 13		Misc	nk New		50		20-2015		100 100	00.00	9-2013		DNGS F NK & LIN										
013-0		-28-2013 00		Electr			6,00				100		9-2013		NDBY (1	- 1			
002-2		-12-2002 00			TRICAL FO	OR	7.00			1	100	00 0	2010	ELECTION	RICAL F	OR									
_								_	LA	ND Lī	NE VA	LUATIO	ON SEC	TION											
Use	co De	escription	Zone	D Front	a Depti	h	Units	Uni	t Price	I. Fact	S.A.	Ac Di	C. Fac	t St. Idx	Adj	Note	S		Use S			S Ad	j Adj	Unit Pric	Land Val
	10 Singl	le Family	WRP			160	0.0001 S	F	0.38	1.000	5	1.000	1.00	016	1.00			Opec	0	T		1.00	0		60.8
10		le Family	WRP			100	62 A		500.00		ő	1.000	1.00	016	1.00				0			0.00			155,8
10			WRP				1 W	/F 185	5,400.0	1.000	0	1.000	1.00	1000000	1.00				0			0.00	00		185,
10° 434	40 Cell																	1	440	- 1					
10° 434 60	40 Cell 5	n Pasture	WRP				9 A			1.000	0	1.000	1.00	016	1.00			490	140			0.00		j	22,5
10° 434	40 Cell 5	n Pasture					9 A 151 A		500.00		0	1.000	1.00	016	1.00			490	240			0.00			377,5
10° 434 60	40 Cell 5	n Pasture	WRP																						

Bldg Name SFR & TOWER SITE Sec # 1 of 1 Card # 1 Account # B0046400 Bldg # Card # 1 of 1 Print Date 9/11/2017 9:48:35 AM **CONSTRUCTION DETAIL** CONSTRUCTION DETAIL (CONTINUED) Element Description Split Level Style Model 01 09 Residential C+ Grade: Stories: MIXED USE Occupancy Exterior Wall A Exterior Wall B 26 Aluminum Sidng Description Percentage BAS Single Family 1010 100 URB Roof Structure: 03 Gable Roof Cover Asphalt 03 FGR BAS Interior Wall A 05 Drywall COST / MARKET VALUATION CRL Base Rate Interior Wall B Interior FIr A 12 Hardwood RCN Net Other Adj Year Built Interior FIr B 02 Oil 1963 Heat Fuel Forced Air None Effective Year Built Depreciation Code Heat Type: 04 01 AC Type: Total Bedrooms 03 3 Bedrooms Remodel Rating Total Bthrms: Year Remodeled Total Half Baths Depreciation % 36 FOP Total Xtra Fixtrs 0 Functional Obsol Total Rooms: 6 02 Economic Obsol Bath Style: Average Cost Trend Factor Kitchen Style: 02 Condition Average Whirlpool Tub % Complete Fireplaces 64 172,740 700 Fin Bsmnt RCNLD Fin Bsmnt Qual R 04 Rec Room 4 Dep % Ovr Attic Access Scuttle Dep Ovr Comment Basement Gara Misc Imp Ovr Misc Imp Ovr Comment Cost to Cure Ovr MH Basement MHP/Complex Cost to Cure Ovr Comment


OB - OUTBUILDING & YARD ITEMS(L) / XF - BUILDING EXTRA FEATURE

Code Description Su Sub Type Lan Units Unit Price Year Pct Depre Conditio Qu
SPL2 Pool-Ingroun B 1,00 23.00 1963 30 0.00 F A Conditio Qu Apprais Va 1.00 6,900 4.00 2011 12.00 2011 30 50 08 08 1.00 PAT1 Patio-Ave 600 0.00 720 SHD1 Shed AV В 80 12.00 0.00 480 IMP Implement S В 2,40 6.00 1977 10 0.00 07 1.00 CELL 163600.0 AV 163 600 Cell Tower 100 0.00 08 0.00 CELS Cell Shed 100.00 75 0.00 G 08 1.00 12,000 160 FN8 6' Top Rail F 360 7.00 75 0.00 08 1.00 1,890 BUILDING SUB-AREA SUMMARY SECTION Living 2,054 Subarea Gross 2,054 Description Eff Area Unit Cost Undeprec Value First Floor BAS 102.05 209,604 CRL Crawl Space 988 0.00 Garage Open Porch 20,613 **FGR** 0 672 30.67 FOF 228 15.22 3.470 URB Raised Basement 1,014 35.73 36,227 Ttl Gross Liv / Lease Area 2,054 4.956

Map ID 012/ 001/ 000/ /

State Use 1010

Property Location 41 BECKWITH RD



verizon

CROWN

VERIZON SITE NAME:

CHESTERFIELD CT

CROWN CASTLE SITE NAME:

MAYBROOK/BOND

CROWN CASTLE BU NUMBER:

876370

SITE ADDRESS:

41 BECKWITH ROAD OAKDALE, CT 06370

SITE TYPE:

MONOPOLE TOWER

MALL / SPEEDBOWL / WATERFORD


PASS SHELL IN 3.2 KM

Know what's below.

Call before you dig.

12. MODERATE CONGESTION
13. TURN RIGHT ONTO BECKWITH RD

10. TURN RIGHT ONTO CT-85 / HARTFORD RD / HARTFORD TPKE



6. RI BUILDING CODE
7. LOCAL BUILDING CODE

8. CITY/COUNTY ORDINANCES

verizon

180 WASHINGTON VALLEY ROAD
BEDMINSTER N.I 07921

INFINIGY8


ROM ZERO TO INFINIGY

the solutions are endless

1490 W. 121st, Ave., Suite 101 Westminster, CO 80234 Office # (303) 219-1178 Fax # (303) 242-8636

MI A PARTNER





- DRAWING NOTIC

THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF VERIZON AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF VERIZON.

	_	
DATE	BY	REV
	_	_
11/30/18	RCD	A
	_	_
֡	DATE	

CHESTERFIELD CT

CROWN CASTLE SITE NAME: -

MAYBROOK/BOND

CROWN CASTLE

876370

SITE ADDRESS:

41 BECKWITH ROAD OAKDALE, CT 06370

SHEET DESCRIPTIO

TITLE SHEET & PROJECT DATA

SHEET NUMBE

T-1

- WORK INCLUDED

 1. INCLUDE ALL LABOR, MATERIALS, EQUIPMENT, PLANT SERVICES

 1. INCLUDE ALL LABOR, MATERIALS, EQUIPMENT, PLANT S AND ADMINISTRATIVE TASKS REQUIRED TO COMPLETE AND MAKE OPERABLE THE ELECTRICAL WORK SHOWN ON THE DRAWINGS AND SPECIFIED HEREIN, INCLUDING BUT NOT LIMITED TO THE
- A. PREPARE AND SUBMIT SHOP DRAWINGS, DIAGRAMS AND
- B. PROCURE ALL NECESSARY PERMITS AND APPROVALS AND PAY ALL REQUIRED FEES AND CHARGES IN CONNECTION WITH THE WORK OF THIS CONTRACT.

C. SUBMIT AS-BUILT DRAWINGS, OPERATING AND MAINTENANCE INSTRUCTIONS AND MANUALS.

- EXECUTE ALL CUTTING, DRILLING, ROUGH AND FINISH
 PATCHING OF EXISTING OR NEWLY INSTALLED CONSTRUCTION REQUIRED FOR THE WORK OF THIS CONTRACT. FOR SLAB PENETRATIONS THROUGH POST TENSION SLABS, X-RAY EXACT AREA OF PENETRATION PRIOR TO PERFORMING WORK.
 COORDINATE ALL X-RAY WORK WITH BUILDING ENGINEER
- PROVIDE HANGERS, SUPPORTS, FOUNDATIONS, STRUCTURAL EQUIPMENT PROVIDED OR INSTALLED LINDER THE WORK OF IIS CONTRACT. PROVIDE COUNTER FLASHING, SLEEVES AND SEALS FOR FLOOR AND WALL PENETRATIONS.
- F. MAINTAIN ALL EXISTING ELECTRICAL SERVICES IN THE BUILDING AREAS NOT AFFECTED BY THE ALTERATION DURING THE PROGRESS OF THE WORK INCLUDING PROVIDING ALL TEMPORARY JUMPERS, CONDUITS, CAPS, PROTECTIVE DEVICES, CONNECTIONS AND EQUIPMENT REQUIRED, PROVIDE TEMPORARY LIGHT AND POWER FOR CONSTRUCTION
- IS THE INTENT OF THESE DRAWINGS AND SPECIFICATIONS TO CALL FOR AN INSTALLATION THAT IS COMPLETE IN EVERY RESPECT. IT IS NOT THE INTENT TO GIVE EVERY DETAIL ON THE DRAWINGS AND IN THE SPECIFICATIONS. IF AN ITEM OF WORK IS INDICATED IN THE DRAWINGS, IT IS CONSIDERED SUFFICIENT FOR INCLUSION IN THE CONTRACT, FURNISH AND INSTALL ALL MATERIAL AND EQUIPMENT USUALLY FURNISHED OR NEEDED TO MAKE A COMPLETE INSTALLATION WHETHER OR NOT SPECIFICALLY MENTIONED IN THE CONTRACT DOCUMENTS.

- 1. PROVIDE ALL WORK IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE (NEC) AND LOCAL AND STATE ELECTRICAL
- 2. THE FLECTRICAL PLANS ARE DIAGRAMMATIC ONLY, REFER TO THE ARCHITECTURAL PLANS FOR THE EXACT DIMENSIONS OF THE BUILDING
- . LOAD CALCULATIONS ARE BASED ON EXISTING BUILDING INFORMATION/DRAWINGS PROVIDED TO ENGINEERING. CONTRACTOR IS TO VERIFY ALL EXISTING RATINGS AND LOADS PRIOR TO PURCHASING OF SPECIFIED EQUIPMENT FOR COMPLIANCE TO NEC. CONTRACTOR TO NOTIFY ENGINEER OF ANY DISCREPANCIES AND REQUEST FURTHER DIRECTION BY
- . EXISTING BUILDING EQUIPMENT IS NOTED ON THE DRAWINGS. NEW OR RELOCATED EQUIPMENT IS SHOWN WITH SOLID LINES.
 FUTURE EQUIPMENT (NOT IN THIS CONTRACT) IS DEPICTED WITH
 SHADED LINES. REQUEST CLARIFICATION OF DRAWINGS OR OF
 SPECIFICATIONS PRIOR TO PRICING OR INSTALLATION.
- A. AFTER CAREFULLY STUDYING THE DRAWINGS AND SPECIFICATIONS, AND BEFORE SUBMITTING THE PROPOSAL, MAKE A MANDATORY SITE VISIT TO ASCERTAIN CONDITIONS OF THE SITE, AND THE NATURE AND EXACT QUANTITY OF WORK TO BE PERFORMED. NO EXTRA COMPENSATION WILL BE ALLOWED FOR FAILURE TO NOTIFY THE OWNER. IN WRITING. OF ANY DISCREPANCIES THAT MAY HAVE BEEN NOTED BETWEEN THE EXISTING CONDITIONS AND THE DRAWINGS AND SPECIFICATIONS

B. VERIFY ALL MEASUREMENTS AT THE SITE AND BE

- RESPONSIBLE FOR CORRECTNESS OF SAME.
 QUALITY, WORKMANSHIP, MATERIALS AND SAFETY
 A. PROVIDE NEW MATERIALS AND EQUIPMENT OF A DOMESTIC MANUFACTURER BY THOSE REGULARLY ENGAGED IN THE PRODUCTION AND MANUFACTURE OF SPECIFIED MATERIALS AND EQUIPMENT, WHERE UL, OR OTHER AGENCY, HAS
 ESTABLISHED STANDARDS FOR MATERIALS, PROVIDE MATERIALS WHICH ARE LISTED AND LABELED ACCORDINGLY. THE COMMERCIALLY STANDARD ITEMS OF EQUIPMENT AND THE SPECIFIC NAMES MENTIONED HEREIN ARE INTENDED FOR PROPER FUNCTIONING OF THE WORK.
- WORK SHALL BE PERFORMED BY WORKMEN SKILLED IN THE TRADE REQUIRED FOR THE WORK. INSTALL MATERIALS AND EQUIPMENT TO PRESENT A NEAT APPEARANCE WHEN COMPLETED AND IN ACCORDANCE WITH THE APPROVED RECOMMENDATIONS OF THE MANUFACTURER AND IN ACCORDANCE WITH CONTRACT DOCUMENTS.
- C. PROVIDE LABOR, MATERIALS, APPARATUS AND APPLIANCES ESSENTIAL TO THE FUNCTIONING OF THE SYSTEMS DESCRIBED OR INDICATED HEREIN, OR WHICH MAY BE REASONABLY IMPLIED AS ESSENTIAL WHENEVER MENTIONED IN THE CONTRACT DOCUMENT OR NOT.
- D. MAKE WRITTEN REQUESTS FOR SUPPLEMENTARY
 INSTRUCTIONS TO ARCHITECT/ENGINEER IN CASE OF DOUBT AS TO WORK INTENDED OR IN EVENT OF NEED FOR EXPLANATION THEREOF.
- EXPLANATION INERCOR.

 E. PERFORMANCE AND MATERIAL REQUIREMENTS SCHEDULED OR SPECIFIED ARE MINIMUM STANDARD ACCEPTABLE. THE RIGHT TO JUDGE THE QUALITY OF EQUIPMENT THAT DEVIATES FROM THE CONTRACT DOCUMENT REMAINS SOLELY WITH ARCHITECT/ENGINEER. CONTRACT DOCUMENT OR NOT.
- 1. GUARANTEE MATERIALS, PARTS AND LABOR FOR WORK FOR ONE YEAR FROM THE DATE OF ISSUANCE OF OCCUPANCY PERMIT.
 DURING THAT PERIOD, MAKE GOOD FAULTS OR IMPERFECTIONS THAT MAY ARISE DUE TO DEFECTS OR OMISSIONS IN MATERIALS OR WORKMANSHIP WITH NO ADDITIONAL COMPENSATION AND AS DIRECTED BY ARCHITECT.

CI FANING

- 1. REMOVE ALL CONSTRUCTION DEBRIS RESULTING FROM THE
- 2. CLEAN EQUIPMENT AND SYSTEMS FOLLOWING THE COMPLETION OF THE PROJECT TO THE SATISFACTION OF THE ENGINEER. COORDINATION AND SUPERVISION
- UNNECESSARY CUTTING, CHANNELING, CHASING OR DRILLING OF FLOORS, WALLS, PARTITIONS, CEILINGS OR OTHER SURFACES. WHERE SUCH WORK IS NECESSARY, HOWEVER, PATCH AND REPAIR THE WORK IN AN APPROVED MANNER BY SKILLED
 MECHANICS AT NO ADDITIONAL COST TO THE OWNER, RENDER FULL COOPERATION TO OTHER TRADES WHERE WORK WILL BE INSTALLED IN CLOSE PROXIMITY TO WORK OF OTHER TRADES. ASSIST IN WORKING OUT SPACE CONDITIONS. IF WORK IS INSTALLED BEFORE COORDINATION WITH OTHER TRADES, OR CAUSES INTERFERENCE, MAKE CHANGES NECESSARY TO CORRECT CONDITIONS WITHOUT EXTRA CHARGE.

- 1. AS-BUILT DRAWINGS:
- A. UPON COMPLETION OF THE WORK, FURNISH TO THE OWNER
 "AS—BUILT" DRAWINGS.
- A. UPON COMPLETION OF THE WORK, FULLY INSTRUCT VERIZON
- AS TO THE OPERATION AND MAINTENANCE OF ALL MATERIAL, EQUIPMENT AND SYSTEMS. B. PROVIDE 3 COMPLETE BOUND SETS OF INSTRUCTIONS FOR OPERATING AND MAINTAINING ALL SYSTEMS AND EQUIPMENT.

CUTTING AND PATCHING

- THING AND FAIGHING.

 1. PROVIDE ALL CUTTING, DRILLING, ROUGH AND FINISH PATCHING REQUIRED TO COMPLETE THE WORK.

 2. OBTAIN OWNER APPROVAL PRIOR TO CUTTING THROUGH FLOORS OR WALLS FOR PIPING OR COMDUIT.

TESTS, INSPECTION AND APPROVAL

- 2313, INSPECTION AND AFFROVAL

 1. BEFORE ENERGIZING ANY ELECTRICAL INSTALLATION, INSPECT
 EACH UNIT IN DETAIL TIGHTEN ALL BOLTS AND CONNECTIONS
 (TORQUE—TIGHTEN WHERE REQUIRED) AND DETERMINE THAT ALL COMPONENTS ARE ALIGNED, AND THE EQUIPMENT IS IN SAFE, OPERATIONAL CONDITION.
- 2. PROVIDE THE COMPILETE ELECTRICAL SYSTEM FREE OF GROUND FAULTS AND SHORT CIRCUITS SUCH THAT THE SYSTEM WILL OPERATE SATISFACTORILY UNDER FULL LOAD CONDITIONS, WITHOUT EXCESSIVE HEATING AT ANY POINT IN THE SYSTEM.

SPECIAL REQUIREMENTS

- 1. DO NOT LEAVE ANY WORK INCOMPLETE NOR ANY HAZARDOUS STUATIONS CREATED WHICH WILL AFFECT THE LIFE OR SAFETY
 OF THE PUBLIC AND/OR BUILDING OCCUPANTS, DO NOT NTERFERE WITH OR CUTOFF ANY OF THE EXISTING SERVICES WITHOUT THE OWNER'S WRITTEN PERMISSION.
- WHEN NECESSARY TO TEMPORARILY DISCONNECT ANY EXISTING BUILDING UTILITIES AND SERVICE SYSTEMS, INCLUDING FEFDER OR BRANCH CIRCUITING SUPPLYING EXISTING FACILITIES CONFER WITH THE OWNER AND ARRANGE THE PERIOD OF INTERRUPTION FOR A TIME MUTUALLY AGREED UPON, SHUTDOWN NOTE: SCHEDULE AND NOTIFY OWNER 48 HOURS PRIOR TO SHUTDOWN, ALL SHUTDOWN WORK TO BE SCHEDULED AT A TIME CONVENIENT TO OWNER.

- 1. ROUTE ALL GROUNDING CONDUCTORS AS SHOWN ON
- CONDUIT/GROUNDING RISER.

 2. ROUTE 500 KCMIL CU. THIN CONDUCTOR FROM THE MGB LOCATION TO BUILDING STEEL VERIFY BUILDING STEEL IS EFFECTIVELY GROUNDED PER NEC TO THE MAIN SERVICE
- GROUNDING ELECTRODE CONDUCTOR (GEC).

 3. MAKE ALL GROUND CONNECTIONS FROM MGB TO ELECTRICAL EQUIPMENT WITH 2 HOLE, CRIMP TYPE, BURNDY COMPRESSION TERMINATIONS, SIZED AS REQUIRED.

 4. USE 1 HOLE, CRIMP TYPE, BURNDY COMPRESSIONS
- TERMINATIONS, SIZED AS REQUIRED, AT EQUIPMENT GROUND CONNECTIONS
- 5. HIRE AN INDEPENDENT LAB TO PERFORM THE SPECIFIED OHMS TESTING, PROVIDE 4 SETS OF THE CERTIFIED DOCUMENTS TO THE OWNER FOR VERIFICATION PRIOR TO THE PROJECT COMPLETION.

- . ALL WIRING TO BE INSTALLED IN CONDUIT SYSTEMS IN ACCORDANCE WITH THE FOLLOWING:

 A. EXTERIOR FEEDERS AND CONTROL, WHERE UNDERGROUND, TO
- BE IN SCH 40 PVC. B. EXTERIOR, ABOVE GROUND POWER CONDUITS TO BE GALVANIZED RIGID STEEL (RGS).
 C. ALL TELECOMMUNICATION CONDUITS, INTERIOR/EXTERIOR, TO

ON THIS PROJECT.

- E. ALL TELECOM CONDUITS AND PULL BOXES INSTALLED ON THIS PROJECT TO BE LABELED "VERIZON". OWNER WILL PROVIDE LABELS FOR CONTRACTOR TO INSTALL
- F. INTERIOR FEEDERS TO BE INSTALLED IN E.M.T. WITH STEEL
- NIMUM SIZE CONDUIT TO BE 3/4" TRADE SIZE UNLESS OTHERWISE INDICATED ON THE DRAWINGS.
 H. FINAL CONNECTIONS TO MOTORS AND VIBRATING EQUIPMENT
- TO BE INSTALLED IN LIQUID-TIGHT FLEXIBLE METAL CONDUIT. AREAS OR DRYWALL PARTITIONS, UNLESS OTHERWISE NOTED. J. THE ROUTING OF CONDUITS INDICATED ON THE DRAWINGS IS DIAGRAMMATIC. BEFORE INSTALLING ANY WORK, EXAMINE THE WORKING LAYOUTS AND SHOP DRAWINGS OF THE OTHER
- TRADES TO DETERMINE THE EXACT LOCATIONS AND K. ALL EXTERIOR MOUNTING HARDWARE TO BE GALVANIZED STEEL COORDINATE WITH BUILDING ENGINEER PRIOR TO ATTACHING TO BUILDING STRUCTURE.

RACEWAYS CONT'D

- L PENETRATIONS OF WALLS, FLOORS AND ROOFS, FOR THE PASSAGE OF ELECTRICAL RACEWAYS, TO BE PROPERLY SEALED AFTER INSTALLATION OF RACEWAYS SO AS TO MAINTAIN THE STRUCTURAL OR WATERPROOF INTEGRITY OF THE WALL, FLOOR OR ROOF SYSTEM TO BE PENETRATED.
 SEAL ALL CONDUIT PENETRATIONS THROUGH FIRE OR SMOKE RATED WALLS, CEILINGS OR SMOKE TIGHT CORRIDOR PARTITIONS TO MAINTAIN PROPER RATING OF WALL OR
- M. PROVIDE ALL CONDUIT ENDS WITH INSULATED METALLIC
- GROUNDING BUSHINGS.

 N. CONDUIT TO BE SUPPORTED AT MAXIMUM DISTANCE OF B'-O", OR AS REQUIRED BY NEC, IN HORIZONTAL AND
- VERTICAL DIRECTIONS.

 O. PROVIDE STAINLESS STEEL BLANK COVER PLATES FOR ALL JUNCTION BOXES AND/OR OUTLET BOXES NOT USED IN EXPOSED AREAS, PROVIDE ALL OTHER UNUSED BOXES WITH STANDARD STEEL COVER PLATES.
 P. WHERE APPLICABLE, PROVIDE ROOFTOP CONDUIT SUPPORT
- SYSTEM, CONFORMING TO ROOFTOP WARRANTY REQUIREMENTS.

WIRES AND CABLES

- CONTRACTOR TO COORDINATE WITH EQUIPMENT SUPPLIER AND VENDOR FOR EXACT EQUIPMENT OVER-CURRENT PROTECTION VOLTAGE, WIRE SIZE AND PLUG CONFIGURATION, IF APPLICABLE
- PRIOR TO BID.

 2. ALL EQUIPMENT/DEVICES TO BE PROVIDED WITH INSULATED GROUND CONDUCTOR.

 3. ALL WIRE AND CABLE TO BE 600VOLT, COPPER, WITH THWN/
- THHN INSULATION, EXCEPT AS NOTED.
- 4. WIRE FOR POWER AND LIGHTING WILL NOT BE LESS THAN NO. 12AWG. ALL WIRE NO. 8 AND LARGER TO BE STRANDED.
 5. CONTROL WIRING IS NOT TO BE LESS THAN NO. 14AWG.
- FLEXIBLE IN SINGLE CONDUCTORS OR MULTI-CONDUCTOR CABLES. CONTROL WIRING WILL CONSIST OF MULTI-CONDUCTOR CABLES WHEREVER POSSIBLE. CABLES TO BE PROVIDED WITH AN OVERALL FLAME-RETARDANT, EXTRUDED JACKET AND RATED FOR PLENUM USE, ALL CONTROL WIRE TO BE 600VOLT RATED.
 WIRE PREVIOUSLY PULLED INTO CONDUIT IS CONSIDERED USED
- AND IS NOT TO BE RE-PULLED.
- HOME RUNS AND BRANCH CIRCUIT WIRING FOR 20A, 120V

CIRCUITS: LENGTH_(FT.) HOME RUN WIRE SIZE NO. 12 NO. 10 O TO 50 51 TO 100 101 TO 150

- 8. VOLTAGE DROP IS NOT TO EXCEED 3%.
 9. MAKE ALL CONNECTIONS WITH UL APPROVED, SOLDERLESS, PRESSURE TYPE INSULATED CONNECTORS: SCOTCHLOK OR AND APPROVED EQUAL.
- WRING DEVICES 1. ALL RECEPTACLES INSTALLED IN THIS PROJECT TO BE GROUNDING TYPE, WITH GROUNDING PIN SLOT CONNECTED TO DEVICE GROUND SCREW FOR GROUND WIRE CONNECTION.
- DISCONNECT SWITCHES AND FUSES DISCONNECT SWITCHES TO BE VOLTAGE—RATED TO SUIT THE CHARACTERISTICS OF THE SYSTEM FROM WHICH THEY ARE
- SUPPLIED.
 2. PROVIDE HEAVY-DUTY, METAL-ENCLOSED, EXTERNALLY-OPERATED DISCONNECT SWITCHES, FUSED OR UNFUSED, OF SUCH TYPE AND SIZE AS REQUIRED TO PROPERLY PROTECT OR DISCONNECT
- THE LOAD FOR WHICH THEY ARE INTENDED.

 3. PROVIDE NEMA 1 DISCONNECT SWITCHES FOR INTERIOR INSTALLATION, NEMA 3R FOR EXTERIOR INSTALLATION
- 4. DISCONNECT SWITCHES TO BE MANUFACTURED BY: A. GENERAL ELECTRIC COMPANY
- 5. PROVIDE RK-1 TYPE FUSES, UNLESS NOTED OTHERWISE.
- 1. INSTALL DISCONNECT SWITCHES WHERE INDICATED ON DRAWINGS
- 2. INSTALL FUSES IN FUSIBLE DISCONNECT SWITCHES, FUSES
- MUST MATCH IN TYPE AND RATING.

 3. FUSES TO BE MOUNTED SO THAT THE LABELS SHOWING THEIR RATINGS CAN BE READ WITHOUT REQUIRING FUSE REMOVAL

 4. FURNISH AND DEPOSIT SPARE FUSES AT THE JOB SITE AS FOLLOWS:
- A. THREE SPARES FOR EACH TYPE AND SIZE, IN EXCESS OF 60A. USED FOR INITIAL FUSING.
- B. TEN PERCENT SPARES FOR EACH TYPE AND SIZE, UP TO AND INCLUDING 60A, USED FOR INITIAL FUSING. IN NO CASE WILL LESS THAN THREE FUSES OF ONE PARTICULAR TYPE AND SIZE BE FURNISHED.

CONFLICTS

- 1. THE CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFICATIONS
 OF ALL MEASUREMENTS AT THE SITE BEFORE ORDERING ANY
 MATERIALS OR DOING ANY WORK, NO EXTRA CHARGE OR
 COMPENSATION SHALL BE ALLOWED DUE TO DIFFERENCE
 BETWEEN ACTUAL DIMENSIONS AND DIMENSIONS INDICATED ON
 THE CONSTRUCTION DRAWINGS, ANY SUCH DISCREPANCY IN DIMENSION WHICH MAY BE FOUND SHALL BE SUBMITTED TO THE OWNER FOR CONSIDERATION BEFORE THE CONTRACTOR PROCEEDS WITH THE WORK IN THE AFFECTED AREAS.
 THE BIDDER, IF AWARDED THE CONTRACT, WILL NOT BE
- ALLOWED ANY EXTRA COMPENSATION BY REASON OF ANY MATTER OR THING CONCERNING SUCH BIDDER MIGHT HAVE FULLY INFORMED THEMSELVES PRIOR TO THE BIDDING.
- NO PLEA OF IGNORANCE OF CONDITIONS THAT EXIST, OR OF DIFFICULTIES OR CONDITIONS THAT MAY BE ENCOUNTERED. OR OF ANY OTHER RELEVANT MATTER CONCERNING THE WORK TO BE PERFORMED IN THE EXECUTION OF THE WORK WILL BE ACCEPTED AS AN EXCUSE FOR ANY FAILURE OR OMISSION ON THE PART OF THE CONTRACTOR TO FULFILL EVERY DETAIL OF ALL THE REQUIREMENTS OF THE CONTRACT DOCUMENTS

- CONTRACTS AND WARRANTIES
 1. CONTRACTOR IS RESPONSIBLE FOR APPLICATION AND PAYMENT
- OF CONTRACTOR LICENSES AND BONDS.

 2. SEE MASTER CONTRACTION SERVICES AGREEMENT FOR ADDITIONAL DETAILS.

ATAIGE.

1. ALL MATERIALS MUST BE STORED IN A LEVEL AND DRY FASHION
AND IN A MANNER THAT DOES NOT NECESSARILY OBSTRUCT THE
FLOW OF OTHER WORK. ANY STORAGE METHOD MUST MEET ALL
RECOMMENDATIONS OF THE ASSOCIATED MANUFACTURER.

CLEANUP

- THE CONTRACTORS SHALL, AT ALL TIMES, KEEP THE SITE FREE
 FROM ACCUMULATION OF WASTE MATERIALS OR RUBBISH CAUSED BY THEIR EMPLOYEES AT WORK AND AT THE COMPLETION OF THE WORK, THEY SHALL REMOVE ALL RUBBISH FROM AND ABOUT THE BUILDING AREA, INCLUDING ALL THEIR TOOLS, SCAFFOLDING AND SURPLUS MATERIALS AND SHALL LEAVE THEIR WORK CLEAN AND READY TO USE.
- A. VISUALLY INSPECT EXTERIOR SURFACES AND REMOVE ALL TRACES OF SOIL, WASTE MATERIALS, SMUDGES AND OTHER FOREIGN MATTER. B. REMOVE ALL TRACES OF SPLASHED MATERIALS FROM
- ADJACENT SURFACES. ADJACENT SURFACES.

 C. IF NECESSARY, TO ACHIEVE A UNIFORM DEGREE OF CLEANLINESS, HOSE DOWN THE EXTERIOR OF THE STRUCTURE.
- 3 INTERIOR A. VISUALLY INSPECT INTERIOR SURFACE AND REMOVE ALL TRACES OF SOIL, WASTE MATERIALS, SMUDGES AND OTHER FOREIGN MATTER FROM WALLS, FLOOR, AND CEILING.
- B. REMOVE ALL TRACES OF SPLASHED MATERIALS FROM ADJACENT SURFACES.
 C. REMOVE PAINT DROPPINGS, SPOTS, STAINS, AND DIRT FROM

CHANGE ORDER PROCEDURE:
1. REFER TO SECTION 17 OF SIGNED MCSA: SEE PROFESSIONAL

SERVICE AGREEMENT FOR MCSA.

- RELATED DOCUMENTS AND COORDINATION
 1. GENERAL CARPENTRY, ELECTRICAL AND ANTENNA DRAWINGS ARE INTERRELATED, IN PERFORMANCE OF THE WORK, THE CONTRACTOR MUST REFER TO ALL DRAWINGS, ALL COORDINATION TO BE THE RESPONSIBILITY OF THE CONTRACTOR.
- 1. CONTRACTOR SHALL SUBMIT SHOP DRAWINGS AS REQUIRED AND LISTED IN THESE SPECIFICATIONS TO THE OWNER FOR
- 2. ALL SHOP DRAWINGS SHALL BE REVIEWED, CHECKED AND CORRECTED BY CONTRACTOR PRIOR TO SUBMITTAL TO THE

- PRODUCTS AND SUBSTITUTIONS
 1. SUBMIT 3 COPIES OF EACH REQUEST FOR SUBSTITUTION. IN EACH REQUEST, IDENTIFY THE PRODUCT OR FABRICATION OR INSTALLATION METHOD TO BE REPLACED BY THE SUBSTITUTION. INCLUDE RELATED SPECIFICATION SECTION AND DRAWING NUMBERS AND COMPLETE DOCUMENTATION SHOWING COMPLIANCE WITH THE REQUIREMENTS FOR SUBSTITUTIONS.
- 2. SUBMIT ALL NECESSARY PRODUCT DATA AND CUT SHEETS WHICH PROPERLY INDICATE AND DESCRIBE THE ITEMS. PRODUCTS AND MATERIALS BEING INSTALLED. THE CONTRACTOR SHALL, IF DEEMED NECESSARY BY THE OWNER, SUBMIT ACTUAL SAMPLES TO THE OWNER FOR APPROVAL IN LIEU OF CUT

 ALL WORK SHALL BE IN ACCORDANCE WITH APPLICABLE LOCAL STATE AND FEDERAL REGULATIONS. THESE SHALL INCLUDE, BUT NOT BE LIMITED TO THE APPLICABLE CODES SET FORTH BY THE LOCAL GOVERNING BODY. SEE "CODE COMPLIANCE" T-1.

- DIMINISTRATION

 1. BEFORE THE COMMENCEMENT OF ANY WORK, THE CONTRACTOR
 WILL ASSICN A PROJECT MANAGER WHO WILL ACT AS A SINGLE
 POINT OF CONTACT FOR ALL PERSONNEL INVOLVED IN THIS PROJECT. THIS PROJECT MANAGER WILL DEVELOP A MASTER SCHEDULE FOR THE PROJECT WHICH WILL BE SUBMITTED TO
- THE OWNER PRIOR TO THE COMMENCEMENT OF ANY WORK.

 2. SUBMIT A BAR TYPE PROGRESS CHART, NOT MORE THAN 3
 DAYS AFTER THE DATE ESTABLISHED FOR COMMENCEMENT OF
 THE WORK ON THE SCHEDULE, INDICATING A TIME BAR FOR EACH MAJOR CATEGORY OR UNIT OF WORK TO BE PERFORMED AT THE SITE, PROPERLY SEQUENCED AND COORDINATED WITH OTHER ELEMENTS OF WORK AND SHOWING COMPLETION OF THE WORK SUFFICIENTLY IN ADVANCE OF THE DATE ESTABLISHED FOR SUBSTANTIAL COMPLETION OF THE WORK.

S. PRIOR TO COMMENCING CONSTRUCTION, THE OWNER SHALL SCHEDULE AN ON-SITE MEETING WITH ALL MAJOR PARTIES. THIS WOULD INCLUDE, BUT NOT LIMITED TO, THE OWNER, PROJECT MANAGER, CONTRACTOR, LAND OWNER REPRESENTATIVE, LOCAL TELEPHONE COMPANY, TOWER ERECTION FOREMAN (IF

- 4. CONTRACTOR SHALL BE EQUIPPED WITH SOME MEANS OF CONSTANT COMMUNICATIONS, SUCH AS A MOBILE PHONE OR A BEEPER. THIS EQUIPMENT WILL NOT BE SUPPLIED BY THE OWNER, NOR WILL WIRELESS SERVICE BE ARRANGED.
- 5. DURING CONSTRUCTION, CONTRACTOR MUST ENSURE THAT EMPLOYEES AND SUBCONTRACTORS WEAR HARD HATS AT ALL TIMES. CONTRACTOR WILL COMPLY WITH ALL WPCS SAFETY REQUIREMENTS IN THEIR AGREEMENT.
- 6. PROVIDE WRITTEN DAILY UPDATES ON SITE PROGRESS TO THE 7. COMPLETE INVENTORY OF CONSTRUCTION MATERIALS AND
- EQUIPMENT IS REQUIRED PRIOR TO START OF CONSTRUCTION.

 NOTIFY THE OWNER/PROJECT MANAGER IN WRITING NO LESS THAN 48 HOURS IN ADVANCE OF CONCRETE POURS, TOWER ERECTIONS, AND EQUIPMENT CABINET PLACEMENTS.

- INSURANCE AND BONDS

 1. CONTRACTOR, AT THEIR OWN EXPENSE, SHALL CARRY AND MAINTAIN, FOR THE DURATION OF THE PROJECT, ALL INSURANCE AS REQUIRED AND LISTED AND SHALL NOT COMMENCE WITH THEIR WORK UNTIL THEY HAVE PRESENTED AN ORIGINAL CERTIFICATE OF INSURANCE STATING ALL COVERAGES TO THE OWNER. REFER TO THE MASTER AGREEMENT FOR REQUIRED INSURANCE LIMITS.
- 2. THE OWNER SHALL BE NAMED AS AN ADDITIONAL INSURED ON
- 3. CONTRACTOR MUST PROVIDE PROOF OF INSURANCE.

GENERAL NOTES:

INTENT

AGI

BTS

APPROX

DIA OR ø

EQUIP

GALV

GRND

(N) NIC NTS

PCS PPC

SS STL

TOC

TOM TYP

VIF

1. THESE SPECIFICATIONS AND CONSTRUCTION DRAWINGS ACCOMPANYING THEM DESCRIBE THE WORK TO BE DONE AND THE MATERIALS TO BE FURNISHED FOR CONSTRUCTION. 2. THE DRAWINGS AND SPECIFICATIONS ARE INTENDED TO BE

FULLY EXPLANATORY AND SUPPLEMENTARY. HOWEVER, SHOULD ANYTHING BE SHOWN, INDICATED, OR SPECIFIED ON ONE AND NOT THE OTHER, IT SHALL BE DONE THE SAME AS IF SHOWN INDICATED OR SPECIFIED IN BOTH

3. THE INTENTION OF THE DOCUMENTS IS TO INCLUDE ALL LABOR AND MATERIALS REASONABLY NECESSARY FOR THE PROPER EXECUTION AND COMPLETION OF THE WORK AS STIPULATED IN THE CONTRACT.

4. THE PURPOSE OF THE SPECIFICATIONS IS TO INTERPRET THE INTENT OF THE DRAWINGS AND TO DESIGNATE THE METHOD OF THE PROCEDURE, TYPE AND QUALITY OF MATERIALS REQUIRED TO COMPLETE THE WORK

5. MINOR DEVIATIONS FROM THE DESIGN LAYOUT ARE ANTICIPATED AND SHALL BE CONSIDERED AS PART OF THE WORK.
NO CHANGES THAT ALTER THE CHARACTER OF THE WORK WILL BE MADE OR PERMITTED BY THE OWNER WITHOUT ISSUING A

ABBREVIATIONS

ADJUSTABLE

APPROXIMATE

AND

CELLING

CONCRETE

DIAMETER

DRAWING

EACH ELECTRICAL

ELEVATION

FOUIPMENT

EXISTING

EXTERIOR

GAUGE

GROUND

MAXIMUM

MINIMUM

METAL

NEW

MECHANICAL

MICROWAVE DISH

MANUFACTURER

NOT IN CONTRACT

PERSONAL COMMUNICATION SYSTEM

POWER PROTECTION CABINET

NOT TO SCALE

ON CENTER

OPPOSITE

PROPOSED

SHEET

SIMILAR

STEEL

TYPICAL

SQUARE FOOT

STAINLESS STEEL

TOP OF CONCRETE

TOP OF MASONRY

VERIFY IN FIELD

UNLESS OTHERWISE NOTED

WELDED WIRE FABRIC

MASTER GROUND BAR

LONG

FINISHED FLOOR

GALVANIZED

EQUIPMENT GROUND BAR

GENERAL CONTRACTOR

CONTINUOUS

ABOVE GROUND LINE

BASE TRANSMISSION STATION

PLANS PREPARED FOR:

180 WASHINGTON VALLEY ROAD

FROM ZERO TO INFINIGY

the solutions are endless 1490 W. 121st. Ave., Suite 101 Westminster, CO 80234 Office # (303) 219-1178

Fax # (303) 242-8636

JOB NUMBER: TBD

MI A PARTNER

ENGINEERING LICENSE:



MINIOF CONNECTION OF CONNEC S. STE MONAL ENGIN

DRAWING NOTICE:

THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF VERIZON AND MAY NOT BE REPRODUCED DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF VERIZON.

DATE	BY	RE
	_	
	-	-
11/30/18	RCD	Α
	11/30/18	11/30/18 RCD

CHESTERFIELD CT

MAYBROOK/BOND

- CROWN CASTLE SITE NAME: -


- CROWN CASTLE BU #: -876370

SITE ADDRESS:

41 BECKWITH ROAD OAKDALE, CT 06370

SHEET DESCRIPTION: -

VERIZON SPECIFICATIONS



OVERALL SITE PLAN

- PLANS PREPARED FOR:



180 WASHINGTON VALLEY ROAD BEDMINSTER, NJ 07921

FROM ZERO TO INFINIGY

the solutions are endless

1490 W. 121st. Ave., Suite 101 Westminster, CO 80234 Office # (303) 219-1178 Fax # (303) 242-8636 JOB NUMBER: TBD

MLA PARTNER:



- ENGINEERING LICENSE: -



THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF VERIZON AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF VERIZON.

DE ADIONO.				
REVISIONS: DESCRIPTION	DATE	BY	REV	
		_		
ISSUED FOR REVIEW	11/30/18	RCD	A	

VERIZON SITE NAME: -

CHESTERFIELD CT

CROWN CASTLE SITE NAME: -

MAYBROOK/BOND

876370


41 BECKWITH ROAD OAKDALE, CT 06370

OVERALL SITE PLAN

SHEET NUMBER: -

SCALE: AS NOTED

A-1





FROM ZERO TO INFINIGY

the solutions are endless

1490 W. 121st. Ave., Suite 101 Westminster, CO 80234 Office # (303) 219-1178 Fax # (303) 242-8636 JOB NUMBER: TBD





THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF VERIZON AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS
WRITTEN CONSENT OF VERIZON.

BY	REV
_	
RCD	A

CHESTERFIELD CT

MAYBROOK/BOND

41 BECKWITH ROAD OAKDALE, CT 06370

> **TOWER ELEVATION**

THE CONFIGURATION PLAN IS BASED ON PROVIDED INFORMATION AND IS FOR CONCEPTUAL PURPOSES ONLY. CONTRACTOR TO VERIFY FIELD CONDITIONS PRIOR TO CONSTRUCTION.

ALPHA SECTOR

 $(AZ=30^{\circ})$ ALPHA SECTOR

 $(AZ=150^{\circ})$

BETA SECTOR

(AZ=30°) ALPHA SECTOR

PROPOSED REINFORCEMENT (SITE

(AZ=270')

GAMMA SECTOR

PROPOSED VERIZON RRH P/N:

UHFA B25 RRH 4X30 RRH (TYP.

OF (1) PER SECTOR, (3) SECTORS

PRO1 PART# SFS-V-L OR

SECTOR) -

APPROVED EQUAL) (TYP PER

INFINIGY ENGINEERING HAS NOT EVALUATED THE TOWER OR MOUNT FOR THIS SITE AND ASSUMES NO RESPONSIBILITY FOR ITS STRUCTURAL INTEGRITY. REFER TO STRUCTURAL ANALYSIS BY OTHERS PRIOR TO ANY CONSTRUCTION.

-EXISTING VERIZON RRH TO

REMAIN (TYP, OF (3) PER

EXISTING MONOPOLE TOWER

SECTOR, (9) SECTORS TOTAL)

PROPOSED VERIZON SIDE BY SIDE ANTENNA MOUNT (COMMSCOPE PART# BSAMNT-SBS-2-2 OR

APPROVED EQUAL) (TYP. OF (1)

PER SECTOR, (3) SECTORS TOTAL)

-RELOCATED EXISTING VERIZON PANEL

ATNENNA P/N: JAHH-65BR3B (TYP,

NO SCALE

OF (2) PER SECTOR, (3) SECTORS

RELOCATED EXISTING VERIZON PANEL ATNENNA P/N: LPA-80080-4CF-EDIN-0 (TYP, OF (2) PER SECTOR, (3) SECTORS

BEDMINSTER, NJ 07921


FROM ZERO TO INFINIGY the solutions are endless

1490 W. 121st, Ave., Suite 101 Westminster, CO 80234 Office # (303) 219-1178 Fax # (303) 242-8636 JOB NUMBER: TBD

MLA PARTNER



ENGINEERING LICENSE:



THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF VERIZON AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF VERIZON.

REVISIONS: DESCRIPTION	DATE	BY	RE
	-		
SSUED FOR REVIEW	11/30/18	RCD	A

- VERIZON SITE NAME: -

CHESTERFIELD CT

- CROWN CASTLE SITE NAME: -

CROWN CASTLE BU #:

MAYBROOK/BOND

876370


41 BECKWITH ROAD OAKDALE, CT 06370

- SHEET DESCRIPTION: -

ANTENNA LAYOUT & LOADING CHART

- SHEET NUMBER:

A-3



EXISTING ANTENNA LAYOUT

NOTE: CONTRACTOR TO VERIFY EQUIPMENT &

MOUNTING HARDWARE DOES NOT TRAP OR INTERFERE WITH SAFETY CLIMB

NORTH = 0PROPOSED ANTENNA LAYOUT NO SCALE 2


TOTAL)

SITE LOADING CHART DOWNTILT SECTOR QTY. QTY FEED LINE TYPE/LENGTH ANTENNA MODEL # SECTOR POSITION TECHNOLOGY VENDOR AZIMUTH RAD CENTER COLOR (REMOVED) (NEW) (QTY/MODEL) MECHANICAL ELECTRICAL (FEET + 20%)±167' AGL LPA-80080-4CF-EDIN-0 ANTEL 30° AI PHA A1 RED CDMA EXISTING COAX UHBA B13 RRH 4X30/ ALPHA A2 RED LTE 700/850 JAHH-65BR3B_2DT **ANDREW** -0° 0. ±167' AGL (2) EXISTING HYBRID CABLES RRH 4T4R B5 160W UHIE B66 RRH 4X45/ JAHH-65BR3B_1DT SHARED EXISTING HYBRID CABLE ALPHA A3 RED LTE 850 **ANDREW** 0. ±167' AGL UHFA B25 RRH 4X30 ALPHA A4 RED LPA-80080-4CF-FDIN-0 ANTFI 30° 0* ±167' AGL CDMA EXISTING COAX 0. BETA B1 **BLUE** CDMA LPA-80080-4CF-EDIN-0 ANTEL 150* 0* ±167' AGL EXISTING COAX UHBA B13 RRH 4X30/ **BETA** B2 BLUE JAHH-65BR3B_2DT ANDREW ±167' AGL SHARED EXISTING HYBRID CABLE LTE 700/850 150' 0. 2. RRH 4T4R B5 160W UHIE B66 RRH 4X45/ **B3** BETA BLUE JAHH-65BR3B_1DT ANDREW LTE 850 ±167' AGL SHARED EXISTING HYBRID CABLE UHFA B25 RRH 4X30 BETA В4 BLUE LPA-80080-4CF-EDIN-0 ANTEL 0. ±167' AGL CDMA 150' EXISTING COAX GAMMA G1 WHITE CDMA LPA-80080-4CF-EDIN-0 ANTEL 270° 0, ±167' AGL EXISTING COAX UHBA B13 RRH 4X30/ GAMMA G2 WHITE LTE 700/850 JAHH-65BR3B_2DT **ANDREW** 270° ±167' AGL SHARED EXISTING HYBRID CABLE RRH 4T4R B5 160W UHIF B66 RRH 4X45/ GAMMA G3 WHITE JAHH-65BR3B_1DT ANDREW SHARED EXISTING HYBRID CABLE LTE 850 ±167' AGL 270° UHFA B25 RRH 4X30 LPA-80080-4CF-EDIN-0 GAMMA G4 WHITE ANTEL. 0. 0. ±167' AGL CDMA 270° EXISTING COAX

NOTE:
CABLE LENGTHS ARE BASED ON PROVIDED INFORMATION. CONTRACTOR
TO VERIFY REQUIRED CABLE LENGTHS PRIOR TO CONSTRUCTION.

SITE LOADING CHART


NO SCALE



NO SCALE

3

NOT USED



verizon

180 WASHINGTON VALLEY ROAD BEDMINSTER, NJ 07921

NFINIGY8

FROM ZERO TO INFINIGY

1490 W. 121st. Ave., Suite 101 Westminster, CO 80234 Office # (303) 219-1178 Fax # (303) 242-8636 JOB NUMBER: TBD

the solutions are endless

- MLA PARTNER: •



CONN S. STE No. 24705 No. 24705

- DRAWING NOTICE: -

THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF VERIZON AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF VERIZON.

REVISIONS: DESCRIPTION	DATE	ву	RE
ISSUED FOR REVIEW	11/30/18	RCD	A

VERIZON SITE NAME:

CHESTERFIELD CT

ROWN CASTLE SITE NAME

MAYBROOK/BOND

CROWN CASTLE BU #: -

876370

- SITE ADDRESS: -


41 BECKWITH ROAD OAKDALE, CT 06370

SHEET DESCRIP

MOUNTING DETAILS

SHEET NUMBER

A-4





180 WASHINGTON VALLEY ROAD BEDMINSTER, NJ 07921

the solutions are endless

1490 W. 121st. Ave., Suite 101 Westminster, CO 80234 Office # (303) 219-1178 Fax # (303) 242-8636 JOB NUMBER: TBD

UNIT WT.

1.37

14.21

12.72

4.53

1.84

0.55

0.55

0.33

0.41

0.15

0.03

0.01

0.07

NET WT.

5.49

28.42

12.72

4.53

3.68

2,20

2.20

0.33

1.64

0.59

0.54


0.25

1.43

65.66



ENGINEERING LICENSE:



THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF VERIZON AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF VERIZON.

REVISIONS:	_	r -	_
DESCRIPTION	DATE	BY	REV
			_
ISSUED FOR REVIEW	11/30/18	RCD	Α

- VERIZON SITE NAME: -

CHESTERFIELD CT


MAYBROOK/BOND


CROWN CASTLE BU#:-

876370

41 BECKWITH ROAD OAKDALE, CT 06370

EQUIPMENT DETAILS





DO NOT INSTALL CABLE GROUND KIT AT A BEND AND ALWAYS DIRECT GROUND WIRE DOWN TO GROUND BAR.

JUMPER REQUIRED ONLY WHEN
7/8" AND LARGER (TYP.)

WEATHERPROOFING KIT (USE
SITEPRO1 OR APPROVED EQUAL)

STANDARD GROUND KIT (USE
SITEPRO1 OR APPROVED EQUAL)

ANTENNA CABLE (TYP.)

NOTE: DO NOT INSTALL CABLE GROUND
KIT AT A BEND ALWAYS DIRECT
GROUND WIRE DOWN TO CIGBE

GROUND BAR
(CONTRACTOR SUPPLIED)

#2/O AWG GREEN INSULATED TO
GROUND BAR AS APPROPRIATE

TYPICAL CABLE GROUND KIT CONNECTION NO SCALE 2 TYPICAL CONNECTION OF GROUND WIRES TO GROUNDING BARS • ANTENNAS

NO SCALE

GENERAL GROUNDING NOTES:

ALL MECHANICAL EXTERNAL TERMINATION SURFACES SHALL BE TREATED WITH T&B KOPR-SHIELD CP8 ANTI-OXIDATION COMPOUND.

TO ENSURE PROPER BONDING, ALL CONNECTIONS SHALL BE AS FOLLOWS:


 #2 BARE TINNED SOLID COPPER CONDUCTOR: EXOTHERMIC WELD TO RODS OR GROUND RING


NO SCALE

- LUGS AND BUS BAR (UNLESS NOTED OTHERWISE): SANDED CLEAN, COATED WITH OXIDE INHIBITOR AND BOLTED FOR MAXIMUM SURFACE CONTACT. ALL LUGS SHALL BE COPPER (NO ALUMINUM SHALL BE PERMITTED). PROVIDE LOCK WASHERS FOR ALL MECHANICAL CONNECTIONS FOR GROUND CONDUCTORS. USE STAINLESS STEEL HARDWARE THROUGHOUT.
- ALL GROUNDING CABLE IN CONCRETE OR THROUGH WALLS SHALL BE IN 3/4" PVC CONDUIT. SEAL AROUND CONDUIT THROUGH WALLS. NO METALLIC CONDUIT SHALL BE USED FOR GROUNDING CONDUCTORS.

TYPICAL EQUIPMENT GROUND CONNECTION

- 3. OWNER'S REPRESENTATIVE WILL INSPECT EXOTHERMIC WELD AND CONDUCT MEGGER TEST PRIOR TO BURIAL. MAXIMUM 5 OHMS RESISTANCE IS REQUIRED.
- 4. CONTRACTOR TO INSTALL GROUNDING IN CLOSE PROXIMITY TO EQUIPMENT PLATFORM OR PAD.
- 5. MAKE ALL GROUND CONNECTIONS AS SHORT AND DIRECT AS POSSIBLE. AVOID SHARP BENDS. ALL BENDS SHALL BE A MINIMUM 8" RADIUS AND NO GREATER THAN 90 DEGREES.
- 6. ALL CADWELDS TO BURIED GROUND RING SHALL BE THE PARALLEL TYPE, EXCEPT FOR THE GROUND RODS WHICH SHALL BE THE TEE TYPE.
- 7. BOND SERVICE CONDUITS TO GROUND RING AS THEY CROSS. DO NOT EXOTHERMICALLY WELD TO CONDUITS.
- 8. THE CONTRACTOR SHALL NOTIFY THE CONSTRUCTION MANAGER WHEN THE GROUNDING SYSTEM IS COMPLETE. THE CONSTRUCTION MANAGER SHALL INSPECT THE GROUNDING SYSTEM PRIOR TO BACKFILLING.
- 9. THE MINIMUM SPACING BETWEEN GROUND RODS SHALL BE 10'-0" (MAX. 15'-0").
- BOND CIGBE TO EXTERNAL GROUND RING WITH 2 RUNS OF #2 BARE, TINNED, SOLID COPPER CONDUCTOR IN PVC. CONNECT BAR END WITH 2 HOLE LUG, AND "CADWELD" THE OTHER END TO THE EXTERNAL GROUND ROD.
- 11. THE PREFERRED LOCATION FOR COAX GROUNDING IS AT THE BASE OF THE TOWER PRIOR TO THE COAX BEND.
- BONDING OF THE GROUNDED CONDUCTOR (NEUTRAL) AND THE GROUNDING CONDUCTOR SHALL BE AT THE SERVICE DISCONNECTING MEANS. BONDING JUMPER SHALL BE INSTALLED PER N.E.C. ARTICLE 250-30.





⊗ GROUND ROD△ ACCESS WELL

GROUND ROD WITH ACCESS

COMPRESSION TYPE CONNECTION

EXOTHERMIC WELD TYPE CONNECTION

#2/0 BTS COPPER CONDUCTOR BURIED GROUND CABLE

INDICATES CODED NOTE

verizon

180 WASHINGTON VALLEY ROAD BEDMINSTER, NJ 07921

- PLANS PREPARED BY: -

PLANS PREPARED FOR:

INFINIGY&

A ZERO TO INFINIGY

the solutions are endless

1490 W. 121st, Ave., Suite 101 Westminster, CO 80234 Office # (303) 219-1178 Fax # (303) 242-8636 JOB NUMBER: TRD

MLA PARTNER:



ENGINEERING LICENSE: •



P DRAWING NOTICE

THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF VERIZON AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF VERIZON.

REVISIONS:			12
DESCRIPTION	DATE	BY	REV
		H	-
ISSUED FOR REVIEW	11/30/18	RCD	A
ISSUED FOR REVIEW	11/30/18	RCD	A

VERIZON SITE NAME:

CHESTERFIELD CT

CROWN CASTLE SITE NAME: -

MAYBROOK/BOND

CROWN CASTLE BU #:

876370

SITE ADDRESS:

41 BECKWITH ROAD OAKDALE, CT 06370

SHEET DESCRIPTION: -

GROUNDING PLANS

SHEET NUMBER:

G-1

NORTH = 0°

TYPICAL ANTENNA GROUNDING PLAN

NO SCAL

SCALE

PAGE 2/3 TEL: 848-8549 FAX: 848-2354

VOL. 342 PAGE 391

TOWN OF MONTVILLE PLANNING & ZONING COMMISSION

310 NORWICH-NEW LONDON TPKE. UNCASVILLE, CONNECTICUT 06382-2599

CERTIFICATE OF NOTICE OF DECISION

APPROVAL: APPROVED WICONDITIONS

LOCATION/DESCRIPTION: 41 BECKWITH ROAD

NATURE OF PROJECT: TELECOMMUNICATIONS TOWER

APPLICABLE ZONING REGULATION:

REGULATION

OWNER OF RECORD:

SPRINT PCS/BOND

PLANNING DIRECTOR

CLERICAL ASSISTANT

REMARKS:

Received for Record SEP 0 6 2000

At 11 h 58 m A. M. and recorded by

Bia Simons Town Clerk

AFTER RECORDING, PLEASE RETURN TO: Thomas J. Regan, Esquire Brown Rudnick Freed & Gesmer 185 Asylum Street, 38th Floor Hartford, CT 06103-3402

recorded in MONTVILLE Lend Records TOWH CLERK

Date: November 27, 2018

Charles McGuirt Crown Castle 3530 Toringdon Way, Suite 300 Charlotte, NC 28277

Charles.McGuirt@crowncastle.com

ETS
ENGINEERED TOWER
SOLUTIONS, PLIC

Engineered Tower Solutions, PLLC 8120 Sheridan Blvd, Suite A-311 Westminster, CO 80003 (919) 782-2710

brandon.little@ets-pllc.com

Subject: Mount Modification Report

Contractor Designation: Verizon Wireless Equipment Change-Out

Carrier Site Number: 38210

Carrier Site Name: CHESTERFIELD CT

Crown Castle Designation: Crown Castle BU Number: 876370

Crown Castle Site Name: MAYBROOK / BOND

Crown Castle JDE Number: 534513 **Crown Castle Order Number:** 461179 Rev. 2

Engineering Firm Designation: ETS Project No.: 184419.17

Site Data: 41 Beckwith Rd., Montville, New London County, CT 06370

Latitude: 41° 26' 7.66" Longitude: -72° 13' 15.07"

Structure Information: Tower Height & Type: 180.0-ft Monopole

Mount Elevation: 167.0-ft

Mount Width & Type: 14.5-ft T-Arm Mount

Dear Charles McGuirt,

Engineered Tower Solutions, PLLC is pleased to submit this "Mount Modification Report" to determine the structural integrity of *Verizon Wireless's* antenna mounting system with the proposed appurtenance and equipment addition on the abovementioned supporting tower structure. Analysis of the existing supporting tower structure is to be completed by others and therefore is not part of this analysis. Analysis of the antenna mounting system as a tie-off point for fall protection or rigging is not part of this document.

The purpose of the analysis is to determine acceptability of the mount stress level. Based on our analysis we have determined the mount stress level to be:

T-Arm Mount (Multiple)

Sufficient*

*Sufficient upon completion of the changes listed in the "Recommendations" section of this report.

This analysis utilizes an ultimate 3-second gust wind speed of 135 mph as required by the 2018 Connecticut State Building Code. Applicable Standard references and design criteria are listed in Section 2 – Analysis Criteria.

Mount Modification Report prepared by:

Brandon R. Little, El Structural Engineer I

Respectfully Submitted by:

Frederic G. Bost, PE Owner/President



TABLE OF CONTENTS

1) INTRODUCTION

2) ANALYSIS CRITERIA

Table 1 – Proposed Equipment Configuration

3) ANALYSIS PROCEDURE

Table 2 – Documents Provided 3.1) Analysis Method 3.2) Assumptions

4) ANALYSIS RESULTS

Table 3 – Mount Component Stresses vs. Capacity 4.1) Recommendations

5) APPENDIX A)

Wire Frame and Rendered Models

6) APPENDIX B)

Software Input Calculations

7) APPENDIX C)

Software Analysis Output

8) APPENDIX D)

Mount Modification Design Drawings (MDD)

1) INTRODUCTION

This mount is an existing 14.5 ft T-Arm mount mapped by Engineered Tower Solutions, PLLC. This mount is installed at the 167.0 ft elevation on 3 sectors of the 180.0 ft Monopole.

2) ANALYSIS CRITERIA

Building Code: 2015 IBC
TIA-222 Revision: TIA-222-H
Risk Category: II
Wind Speed: 135 mph
Exposure Category: B
Topographic Factor: 1
Ice Thickness: 2.00 in
Wind Speed with Ice: 50 mph

Seismic S_s: 0.201
Seismic S₁: 0.054
Live Loading Wind Speed: 30 mph
Man Live Load at Mid/End-Points: 250 lb
Man Live Load at Mount Pipes: 500 lb

Table 1 – Proposed Equipment Configuration

Mount Centerline (ft)	Antenna Centerline (ft)	Number of Antennas	Antenna Manufacturer	Antenna Model	Mount / Modification Details
		6	ANTEL	LPA-80080/4CF	
		6	COMMSCOPE	JAHH-65B-R3B	
		3	ALCATEL LUCENT	B66A RRH4X45-4R	
167.0	167.0	6	NOKIA	B25 RRH4X30 (UHFA)	(3) 14.5 ft T-Arm Mounts
	2 NOKIA		NOKIA	B5 4T4R RRH4X40	
		3	NOKIA	AIRSCALE	
		2	RAYCAP	RC3DC-3315-PF-48	

3) ANALYSIS PROCEDURE

Table 2 - Documents Provided

Document	Remarks	Reference	Source
Structural Level Drawings (Installed)	Crown Castle	10/01/2018	CCI Sites
Structural Level Drawing (Proposed)	Crown Castle	10/01/2018	CCI Sites
Carrier Application	App # 461179 Rev. 2	09/24/2018	CCI Sites
4-Structural Analysis Report	Crown Castle	7704136	CCI Sites
Verizon Mount Mapping	Engineered Tower Solutions, PLLC	11/20/2018	ETS, PLLC

3.1) Analysis Method

RISA-3D (version 16.0), a commercially available analysis software package, was used to create a three-dimensional model of the tower and calculate member stresses for various loading cases. Selected output from the analysis is included in Appendix C.

This analysis was performed in accordance with Crown Castle's ENG-SOW-10208 Tower Mount Analysis (Revision B).

3.2) Assumptions

- 1) The antenna mounting system was properly fabricated, installed and maintained in good condition in accordance with its original design and manufacturer's specification.
- 2) The configuration of antennas, mounts and other appurtenances are as specified in Tables 1 and 2 and the referenced drawings.
- 3) All member connections are assumed to have been designed to meet or exceed the load carrying capacity of the connected member unless otherwise specified in this report.
- 4) This Structural Analysis is not a condition assessment of the mount and is an evaluation of the theoretical structural capacity.
- 5) This analysis is based from the information supplied, and therefore, this report's results are as accurate as the supplied data.
- 6) Engineered Tower Solutions, PLLC makes no warranties, expressed and/or implied, in connection with this report, and disclaims any liability associated with material, fabrication, or erection of the mount. Engineered Tower Solutions, PLLC will not be held responsible from any consequential or incidental damages sustained by any person, firm, or organization as a result of the contents of this report. The maximum liability of Engineered Tower Solutions, PLLC pursuant to this report will be limited to the total fee received for compilation of this report.
- 7) It is the tower owner's responsibility to verify that the mount modeled and analyzed is the correct structure modeled.
- 8) The use of this report shall be limited to the purpose for which it was commissioned and may not be used for any other purposes without the written consent of Engineered Tower Solutions, PLLC.
- 9) Steel grades have been assumed as follows:

a)	Channel, Solid Round, Angle, Plate	ASTM A36 (Gr 36)
b)	HSS (Rectangular)	ASTM 500 (Gr B-46)
c)	HSS (Round)	ASTM 500 (Gr B-42)
d)	Pipe	ASTM A53 (Gr 35)
e)	Connection Bolts	ASTM A325
f)	U-Bolts	SAE 429 Gr.2

This analysis may be affected if any assumptions are not valid or have been made in error. Engineered Tower Solutions, PLLC should be notified to determine the effect on the structural integrity of the tower.

4) ANALYSIS RESULTS

Table 3(a) - Mount Component Stresses vs. Capacity (T-Arm Mount, All Sectors) - Without Modifications

Notes	Component	Critical Member	Centerline (ft)	% Capacity	Pass / Fail
1	Sidearm	SA		146.8	FAIL
1	Face Mount	FM	167.0	123.8	FAIL
1	Mount Pipe	MP3	167.0	29.2	PASS
1	Grate Support	SUP2		23.0	PASS

Table 3(b) - Mount Component Stresses vs. Capacity (T-Arm Mount, All Sectors) - With Modifications

Notes	Component	Critical Member	Centerline (ft)	% Capacity	Pass / Fail
1	Sidearm	SA		74.3	PASS
1	Face Mount	FM	167.0	68.4	PASS
1	Mount Pipe	MP3	167.0	29.2	PASS
1	Grate Support	SUP2		73.8	PASS

Notes:

1) See additional documentation in "Appendix C – Software Analysis Output" for calculations supporting the % capacity consumed.

Tower Mount Rating (max from all components) =	74.3%
--	-------

4.1) Recommendations

The tower mount has sufficient capacity to carry the existing and proposed load configuration. In order for the results of this analysis to be considered valid, the following modifications must be performed:

1) Add (1) SFS-V-L stabilizer kit per sector (see drawings in Appendix D for additional details).



Tel: 519-885-3806 Fax: 519-884-3806 www.p-sec.ca



October 5, 2018

Amanda D Brown, Tower Structural Analyst Crown Castle 3530 Toringdon Way Suite 300 Charlotte, NC 28277

Subject: Structural Analysis Report

Carrier Designation: Carrier Co-Locate: Verizon Wireless

Carrier Site Number: 38210

Carrier Site Name: CHESTERFIELD CT

Crown Castle Designation: Crown Castle BU Number: 876370

Crown Castle Site Name: MAYBROOK / BOND

Crown Castle JDE Job Number: 534513 Crown Castle WO Number: 1641866 Crown Castle Order Number: 461179 Rev. 2

Engineering Firm Designation: P-SEC Project Number: 18724

Site Data: 41 Beckwith Rd., MONTVILLE, New London County, CT

Latitude 41° 26' 7.66", Longitude -72° 13' 15.07"

180-ft Monopole Tower

Dear Amanda D Brown,

Pier Structural Engineering Corp. (P-SEC) is pleased to submit this "Structural Analysis Report" to determine the structural integrity of the above mentioned tower. This analysis has been performed in accordance with the Crown Castle Structural 'Statement of Work' and the terms of Crown Castle Purchase Order Number 1265167, in accordance with order 461179, revision 2.

The purpose of the analysis is to determine acceptability of the tower stress level. Based on our analysis we have determined the tower stress level for the structure and foundation, under the following load case, to be:

LC7: Proposed Equipment Configuration

Sufficient Capacity

No. 31228
No. 31228
No. 31228
No. 31228
No. 31228

This analysis utilizes an ultimate 3-second gust wind speed of 135 mph as required by the 2016 Connecticut State Building Code. Applicable Standard references and design criteria are listed in Section 2 - Analysis Criteria.

We at P-SEC appreciate the opportunity of providing our continuing professional services to you and Crown Castle. If you have any questions or need further assistance on this or any other projects please give us a call.

Structural analysis prepared by: Joseph Andre, E.I.T.

Respectfully submitted by:

Shawn Hoffmeyer, P.E., P.Eng.

CT PE# 31228

tnxTower Report - version 8.0.4.0



Pier Structural Engineering Corp.

55 Northfield Drive E, Suite 198 Waterloo, ON N2K 3T6 Tel: 519-885-3806 Fax: 519-884-3806

www.p-sec.ca

October 5, 2018

Amanda D Brown, Tower Structural Analyst Crown Castle 3530 Toringdon Way Suite 300 Charlotte, NC 28277

Subject: Structural Analysis Report

Carrier Designation: Carrier Co-Locate: Verizon Wireless

Carrier Site Number: 38210

Carrier Site Name: CHESTERFIELD CT

Crown Castle Designation: Crown Castle BU Number: 876370

Crown Castle Site Name: MAYBROOK / BOND

Crown Castle JDE Job Number: 534513 Crown Castle WO Number: 1641866 Crown Castle Order Number: 461179 Rev. 2

Engineering Firm Designation: P-SEC Project Number: 18724

Site Data: 41 Beckwith Rd., MONTVILLE, New London County, CT

Latitude 41° 26′ 7.66″, Longitude -72° 13′ 15.07″

180-ft Monopole Tower

Dear Amanda D Brown,

Pier Structural Engineering Corp. (P-SEC) is pleased to submit this "Structural Analysis Report" to determine the structural integrity of the above mentioned tower. This analysis has been performed in accordance with the Crown Castle Structural 'Statement of Work' and the terms of Crown Castle Purchase Order Number 1265167, in accordance with order 461179, revision 2.

The purpose of the analysis is to determine acceptability of the tower stress level. Based on our analysis we have determined the tower stress level for the structure and foundation, under the following load case, to be:

LC7: Proposed Equipment Configuration

Sufficient Capacity

This analysis utilizes an ultimate 3-second gust wind speed of 135 mph as required by the 2016 Connecticut State Building Code. Applicable Standard references and design criteria are listed in Section 2 - Analysis Criteria.

We at P-SEC appreciate the opportunity of providing our continuing professional services to you and Crown Castle. If you have any questions or need further assistance on this or any other projects please give us a call.

Structural analysis prepared by: Joseph Andre, E.I.T.

Respectfully submitted by:

TABLE OF CONTENTS

1) INTRODUCTION

2) ANALYSIS CRITERIA

Table 1 - Proposed Equipment Configuration
Table 2 - Other Considered Equipment

3) ANALYSIS PROCEDURE

Table 3 - Documents Provided 3.1) Analysis Method 3.2) Assumptions

4) ANALYSIS RESULTS

Table 4 - Section Capacity (Summary)
Table 5 - Tower Component Stresses vs. Capacity
4.1) Recommendations

5) APPENDIX A

tnxTower Output

6) APPENDIX B

Base Level Drawing

7) APPENDIX C

Additional Calculations

1) INTRODUCTION

This tower is a 180-ft Monopole tower originally designed by ENGINEERED ENDEAVORS, INC. in September of 2000 for a wind speed of 90 mph per TIA/EIA-222-F.

2) ANALYSIS CRITERIA

The following design parameters have been used in our analysis:

Design Standard: TIA-222-H Standard and local code requirements

County/State: New London County, CT Wind Speeds: CASE 1 135 mph (3-second gust)

CASE 2 50 mph (3-second gust) with 1.5" radial solid ice

CASE 3 60 mph (3-second gust) for serviceability

Exposure Category: B
Topographic Category: 1
Risk Category: II

Table 1 - Proposed Equipment Configuration

Mounting Level (ft)	Line Elev.	Number of Antennas	Antenna Manufacturer	Antenna Model	Number of Feed Lines	Feed Line Size (in)
		6	antel	LPA-80080/4CF		
		6	commscope	JAHH-65B-R3B		
		3	alcatel lucent	B66A RRH4X45-4R		
167	167	6	nokia	B25 RRH4X30 (UHFA)	12	1-5/8
		3	nokia	B5 4T4R RRH4X40 AIRSCALE		
		2	raycap	RC3DC-3315-PF-48		
		1		RMQP-496-HK (Mount)		

Table 2 - Other Considered Equipment

Mounting Level (ft)	Center Line Elev. (ft)	Number of Antennas	Antenna Manufacturer	Antenna Model	Number of Feed Lines	Feed Line Size (in)
		3	commscope	NNVV-65B-R4		
		3	rfs celwave	APXVTM14-ALU-I20		
180	180	3	alcatel lucent	PCS 1900MHZ 4X45W-65MHZ	4	1-1/4
100	100	6	alcatel lucent	RRH2X50-800	4	1-1/4
		3	alcatel lucent	TD-RRH8X20-25		
		1		RMQP-496 (Mount)		
		3	commscope	LNX-6515DS-A1M		
		1	fastback	IBR 1300		
175	175	3	rfs celwave	APX16DWV-16DWV-S-E-A20	1	1-5/8
175	175	3	ericsson	RRUS 11 B12	3	1/4
		6	ericsson	RRUS 11 B4		
		1		Platform Mount [LP 301-1]		
75	76	1	lucent	KS24019-L112A	1	1/2
15	75	1		Side Arm Mount [SO 701-1]	1	1/2

3) ANALYSIS PROCEDURE

Table 3 - Documents Provided

Document	Remarks	Reference	Source
4-GEOTECHNICAL REPORTS	CSA, Proj. No. 2000.905 dated 3/16/2000	1533478	CCISITES
4-TOWER MANUFACTURER DRAWINGS	EEI, Proj. No. 7776 dated 9/7/2000	1532099	CCISITES
APPLICATION	Verizon Wireless, Revision #2 dated 9/24/2018	461179	CCISITES

3.1) Analysis Method

tnxTower (8.0.4.0), a commercially available analysis software package, was used to create a threedimensional model of the tower and calculate member stresses for various loading cases. Selected output from the analysis is included in Appendix A.

3.2) Assumptions

- 1) Tower and structures were built in accordance with the manufacturer's specifications.
- 2) The tower\structures have been maintained in accordance with the manufacturer's specification.
- 3) The configuration of antennas, transmission cables, mounts and other appurtenances are as specified in Tables 1 and 2 and the referenced drawings.
- 4) P-SEC did not analyze antenna supporting mounts as part of this analysis report and assumed they are structurally sufficient. It is the carrier's responsibility to ensure structural compliance of their existing and/or proposed antenna supporting mounts.
- 5) All equipment model numbers, quantities, and centerline elevations are as provided in the CCI CAD package dated 10/1/2018.

This analysis may be affected if any assumptions are not valid or have been made in error. P-SEC should be notified to determine the effect on the structural integrity of the tower.

4) ANALYSIS RESULTS

Table 4 - Section Capacity (Summary)

Section No.	Elevation (ft)	Component Type	Size	Critical Element	P (K)	SF*P_allow (K)	% Capacity	Pass / Fail
L1	180 - 133	Pole	TP27.51x15.5x0.25	1	-11.28	1583.86	80.8	Pass
L2	133 - 87.3333	Pole	TP38.56x25.9879x0.375	2	-20.04	3393.02	65.3	Pass
L3	87.3333 - 42.6667	Pole	TP49.1x36.46x0.4375	3	-32.90	4931.72	59.4	Pass
L4	42.6667 - 0	Pole	TP59x46.5397x0.4375	4	-51.28	5726.71	63.3	Pass
							Summary	
						Pole (L1)	80.8	Pass
						Rating =	80.8	Pass

Table 5 - Tower Component Stresses vs. Capacity

Notes	Component	Elevation (ft)	% Capacity	Pass / Fail
2	Anchor Rods		63	Pass
2	Base Plate		79.6	Pass
2	Base Foundation (Compared w/ Design Loads)		73.8	Pass

Structure Rating (max from all components) = 80.8%
--

Notes:

- 1) See full member breakdown and section capacities in Appendix A.
- 2) See additional documentation in Appendix C for supporting calculations.
- 3) Rating per TIA-222-H Section 15.5

4.1) Recommendations

The tower and its foundation have sufficient capacity to carry the proposed loading configuration.

No modifications are required at this time.

Should you have any questions, please call us anytime at 519-885-3806.

encl.

BU876370_461179 SA Report_20181005.doc

Site Name: Newtown CT SC6
Cumulative Power Density

Operator	Operating Frequency	Number of Trans.	ERP Per Trans.	Total ERP	Distance to Target	Calculated Power Density	Maximum Permissible Exposure*	Fraction of MPE
	(MHz)		(watts)	(watts)	(feet)	(mW/cm^2)	(mW/cm^2)	(%)
VZW PCS	1970	1	5062.17	5062.17	173	0.0608	1.0	6.08%
VZW Cellular	869	1	3709.2	3709.2	173	0.0446	0.579333333	7.69%
VZW AWS	2145	1	7770.14	7770.14	173	0.0934	1.0	9.34%
VZW 700	746	1	2062.23	2062.23	173	0.0248	0.497333333	4.98%

Total Percentage of Maximum Permissible Exposure

28.09%

*Guidelines adopted by the FCC on August 1, 1996, 47 CFR Part 1 based on NCRP Report 86, 1986 and generally on ANSI/IEEE C95.1-1992

MHz = Megahertz mW/cm^2 = milliwatts per square centimeter ERP = Effective Radiated Power

Absolute worst case maximum values used, including the following assumptions:

- 1. closest accessible point is distance from antenna to base of pole;
- 2. continuous transmission from all available channels at full power for indefinite time period; and,
- 3. all RF energy is assumed to be directed solely to the base of the pole.



December 7,2018

Dear Customer:

The following is the proof-of-delivery for tracking number 773904536570.

Delivery Information:

Status:

Delivered

Signed for by:

T.HART

Delivered to:

Delivery location:

Receptionist/Front Desk

TOWN OF MONTVILLE UNCASVILLE, CT 06382

Service type:

Special Handling:

FedEx Priority Overnight

Deliver Weekday

Delivery date:

Dec 7, 2018 10:12



Shipping Information:

Tracking number:

773904536570

Ship date:

Dec 6, 2018

Weight:

0.5 lbs/0.2 kg

Recipient:

Ronald McDaniel
Town of Montville

UNCASVILLE, CT 06382 US

Shipper:

Kristian McKay 3530 Toringdon Way

STE 300

CHARLOTTE, NC 28277 US

Reference

1766.6680

Thank you for choosing FedEx.



December 7,2018

Dear Customer:

The following is the proof-of-delivery for tracking number 773904544729.

Delivery Information:

Status: Signed for by: Delivered

C.ARMEN KNEILAND

Delivered to:

Delivery location:

Receptionist/Front Desk TOWN OF MONTVILLE

UNCASVILLE, CT 06382

Service type:

Special Handling:

FedEx Priority Overnight

Deliver Weekday

Delivery date:

Dec 7, 2018 10:11



Shipping Information:

Tracking number:

773904544729

Ship date:

Dec 6, 2018 0.5 lbs/0.2 kg

Weight:

Recipient:

Vernon D. Vesey Town of Montville

UNCASVILLE, CT 06382 US

Shipper:

Kristian McKay 3530 Toringdon Way

STE 300

CHARLOTTE, NC 28277 US

1766.6680

Reference

Thank you for choosing FedEx.



December 7,2018

Dear Customer:

The following is the proof-of-delivery for tracking number **773904567112**.

Delivery Information:

Status:

Delivered

Delivered to:

Residence

Signed for by:

Signature not required

Delivery location:

41 BECKWITH RD

OAKDALE, CT 06370

Service type:

FedEx Priority Overnight

Delivery date:

Special Handling:

Deliver Weekday

Residential Delivery

Dec 7, 2018 11:58

NO SIGNATURE REQUIRED

Proof-of-delivery details appear below; however, no signature is available for this FedEx Express shipment because a signature was not required.

Shipping Information:

Tracking number:

773904567112

Ship date:

Dec 6, 2018

Weight:

0.5 lbs/0.2 kg

Recipient:

Gladys J. Bond Trustee

41 Beckwith Rd.

OAKDALE, CT 06370 US

Shipper:

Kristian McKay

3530 Toringdon Way

STE 300

CHARLOTTE, NC 28277 US

Reference

1766.6680

Thank you for choosing FedEx.