



Northeast Site Solutions
Victoria Masse
5 Melrose Drive
Farmington, CT 06032
victoria@northeastitesolutions.com

December 5, 2023

Members of the Siting Council
Connecticut Siting Council
Ten Franklin Square
New Britain, CT 06051

RE: Tower Share Application
227 Boombridge Road, North Stonington CT 06359
Latitude: 41.42879694
Longitude: -71.80907720
Site#: BOBOS01171A

Dear Ms. Bachman:

This letter and attachments are submitted on behalf of Dish Wireless LLC. Dish Wireless LLC plans to install antennas and related equipment to the guyed lattice tower site located at 227 Boombridge Road, North Stonington, Connecticut.

Dish Wireless LLC proposes to install three (3) 600/1900/2100 5G MHz antenna and six (6) RRUs, at the 153-foot level of the existing 180-foot guyed lattice tower, one (1) hybrid cable will also be installed. Dish Wireless LLC equipment cabinets will be placed within 8"x11" lease area. Included are plans by Centek, dated December 1, 2023, Exhibit C. Also included is a structural analysis prepared by Centek, dated September 19, 2023 confirming that the existing guyed tower is structurally capable of supporting the proposed equipment. Attached as Exhibit D. This facility was originally approved by the Town of North Stonington Zoning and Building Official in 1997 (Building Permit No. 97-012). Please see attached Exhibit A.

Please accept this letter as notification pursuant to Regulations of Connecticut State Agencies 16-50aa, of Dish Wireless LLC intent to share a telecommunications facility pursuant to R.C.S.A. 16-50j-88. In accordance with R.C.S.A., a copy of this letter is being sent to First Selectman Bob Carlson, Cheryl Konsavitch, Land Use Assistant, for the Town of North Stonington, as well as the property owner and the tower owner.

The planned modifications of the facility fall squarely within those activities explicitly provided for in R.C.S.A. 16-50j-89.

1. The proposed modifications will not result in an increase in the height of the existing structure. The top of the guyed lattice tower is 180-feet; Dish Wireless LLC proposed antennas will be located at a center line height of 153-feet.
2. The proposed modification will not result in the increase of the site boundary as depicted on the attached site plan.
3. The proposed modification will not increase the noise levels at the facility by six decibels or more, or to levels that exceed local and state criteria. The incremental effect of the proposed changes will be negligent.

5 Melrose Drive, Farmington CT 06032



4. The operation of the proposed antennas will not increase radio frequency emissions at the facility to a level at or above the Federal Communications Commission safety standard. As indicated in the attached power density calculations, the combined site operations will result in a total density of 11.75% as evidenced by Exhibit F.

Connecticut General Statutes 16-50-aa indicates that the Council must approve the shared use of a telecommunications facility provided it finds the shared use is technically, legally, environmentally, and economically feasible and meets public safety concerns. As demonstrated in this letter, Dish Wireless LLC respectfully indicates that the shared use of this facility satisfies these criteria.

A. Technical Feasibility. The existing guyed lattice tower has been deemed structurally capable of supporting Dish Wireless LLC proposed loading. The structural analysis is included in Exhibit D.

B. Legal Feasibility. As referenced above, C.G.S. 16-50aa has been authorized to issue orders approving the shared use of an existing guyed lattice tower such as this guyed lattice tower in North Stonington. Under the authority granted to the Council, an order of the Council approving the requested shared use would permit Dish Wireless LLC to obtain a building permit for the proposed installation. Further, a letter of Authorization is included as Exhibit G, authorizing Dish Wireless LLC to file this application for shared use.

C. Environmental Feasibility. The proposed shared use of this facility would have a minimal environmental impact. The installation of Dish Wireless LLC equipment at the 153-foot level of the existing 180-foot guyed lattice tower would have an insignificant visual impact on the area around the guyed lattice tower. Dish Wireless LLC ground equipment would be installed within the existing facility compound. Dish Wireless LLC shared use would therefore not cause any significant alteration in the physical or environmental characteristics of the existing site. Additionally, as evidenced by Exhibit F, the proposed antennas would not increase radio frequency emissions to a level at or above the Federal Communications Commission safety standard.

D. Economic Feasibility. Dish Wireless LLC will be entering into an agreement with the owner of this facility to mutually agreeable terms. As previously mentioned, the Letter of Authorization has been provided by the owner to assist Dish Wireless LLC with this tower share application.

E. Public Safety Concerns. As discussed above, the guyed lattice tower is structurally capable of supporting Dish Wireless LLC proposed loading. Dish Wireless LLC is not aware of any public safety concerns relative to the proposed sharing of the existing guyed lattice tower. Dish Wireless LLC intentions of providing new and improved wireless service through the shared use of this facility is expected to enhance the safety and welfare of local residents and individuals traveling through North Stonington.

Sincerely,

Victoria Masse
Mobile: 860-306-2326
Fax: 413-521-0558
Office: 5 Melrose Drive, Farmington CT 06032
Email: victoria@northeastsitesolutions.com



Attachments

Cc:

Bob Carlson, First Selectman
Town of North Stonington
40 Main Street
North Stonington, CT 06359

Cheryl Konsavitch, Land Use Assistant
Town of North Stonington
40 Main Street
North Stonington, CT 06359

LEWIS DAVID BABCOCK LLC, Property Owner
273 BOOMBRIDGE RD
NORTH STONINGTON, CT 06359

Ken Thomas, Tower Owners
Wireless Solutions LLC
PO BOX 284
Old Lyme, CT 06371

Exhibit A

Original Facility Approval

Town of North Starington

Building Permit

Date: Feb 5, 1997

Permit Number: 7402

Expiration Date of Permit: Feb 5, 1998

Number of Stories: 0

CU
(Residential Use)

Location: 227 Down Bridge Rd

Zoning District: R-80

Subdivision: _____ Lot _____ Map _____

I HEREBY CERTIFY THAT THE PROPOSED WORK IS AUTHORIZED BY THE OWNER OF RECORD AND I HAVE BEEN AUTHORIZED BY THE OWNER TO MAKE THIS APPLICATION AS HIS OR HER AUTHORIZED AGENT.

Signature of Authorized Agent _____

Address: _____

License Number: _____

Area in Square Feet: N/A

Estimated Cost of Construction: \$0.00 Permit Fee: \$656

Owner: David Lewis

Address: 227 Down Bridge Rd

Building Official: _____ Date: 2/5/97

White - Applicant

Copy Distribution

Canary - File

Pink - Assessor

Exhibit B

Property Card

Town of North Stonington, CT

Property Listing Report

Map Block Lot

119 6314

Building #

Unique Identifier

L9857560

Property Information

Property Location	227 BOOMBRIDGE RD
Mailing Address	273 BOOMBRIDGE RD NORTH STONINGTON CT 06359
Land Use	Cell Tower
Zoning Code	R60
Neighborhood	C120

Owner	LEWIS DAVID BABCOCK LLC
Co-Owner	
Book / Page	0140/0513
Land Class	Vacant Land
Census Tract	7071
Acreage	1.38

Valuation Summary

(Assessed value = 70% of Appraised Value)


Item	Appraised	Assessed
Buildings	0	0
Outbuildings	0	0
	444000	310800
	444000	310800

Utility Information

Electric	No
Gas	No
Sewer	No



No Photo Available



No Photo Available

Primary Construction Details

Year Built	
Building Desc.	
Building Style	
Stories	
Exterior Walls	
Exterior Walls 2	
Interior Walls	
Interior Walls 2	
Interior Floors 1	
Interior Floors 2	

Heating Fuel	
Heating Type	
AC Type	
Bedrooms	
Full Bathrooms	
Half Bathrooms	
Extra Fixtures	
Total Rooms	
Bath Style	
Kitchen Style	
Occupancy	

Building Use	
Building Condition	
Frame Type	
Fireplaces	
Bsmt Gar	
Fin Bsmt Area	
Fin Bsmt Quality	
Building Grade	
Roof Style	
Roof Cover	

Report Created On

12/6/2023

Town of North Stonington, CT

Property Listing Report

Map Block Lot **119 6314**

Building #

Unique Identifier

L9857560

Detached Outbuildings

Type	Description	Area (sq ft)	Condition	Year Built

Attached Extra Features

Type	Description	Area (sq ft)	Condition	Year Built


Sales History

Owner of Record	Book/ Page	Sale Date	Sale Price
LEWIS DAVID BABCOCK LLC	0140_0513	12/28/2001	0
LEWIS ROSALIND M	0126_0960	8/5/1999	0
LEWIS DAVID B EST & ROSALIND M	0116_0313	10/15/1997	0
LEWIS DAVID B & ROSALIND M	0032_0296	6/9/1964	0

Town of North Stonington, Connecticut - Assessment Parcel Map

Parcel: 119-6314

Address: 227 BOOMBRIDGE RD



Approximate Scale: 1:200

0 3.757.5 15 22.5 30

Feet

Map Produced
April 2023

Disclaimer: This map is for informational purposes only.
All information is subject to verification by any user.
The Town of North Stonington and its mapping contractors assume
no legal responsibility for the information contained herein.



Exhibit C

Construction Drawings



DISH Wireless L.L.C. SITE ID:
BOBOS01171A

DISH Wireless L.L.C. SITE ADDRESS:
**227 BOOMBRIDGE ROAD
NORTH STONINGTON, CT 06359**

CODE COMPLIANCE

ALL WORK SHALL BE PERFORMED AND MATERIALS INSTALLED IN ACCORDANCE WITH THE CURRENT EDITIONS OF THE FOLLOWING CODES AS ADOPTED BY THE LOCAL GOVERNING AUTHORITIES. NOTHING IN THESE PLANS IS TO BE CONSTRUED TO PERMIT WORK NOT CONFORMING TO THESE CODES:

CODE TYPE	CODE
BUILDING	2022 CT STATE BUILDING CODE/2021 IBC W/ CT AMENDMENTS
ELECTRICAL	2022 CT STATE BUILDING CODE/2020 NEC W/ CT AMENDMENTS

SHEET INDEX

SHEET NO.	SHEET TITLE
T-1	TITLE SHEET
C-1	OVERALL SITE PLAN
C-2	ELEVATION, ANT. LAYOUT AND SCHEDULE
C-3	EQUIPMENT PLATFORM AND H-FRAME DETAILS
C-4	TYPICAL EQUIPMENT DETAILS
C-5	TYPICAL EQUIPMENT DETAILS
E-1	ELECTRICAL AND FIBER ROUTING PLAN WITH NOTES
E-2	TELCO CABINET DETAILS
E-3	ELECTRICAL RISER, PANEL SCHEDULE, AND SCHEMATIC
G-1	COMPOUND/ANTENNA GROUNDING PLAN AND NOTES
G-2	TYPICAL GROUNDING DETAILS
G-3	TYPICAL GROUNDING DETAILS
G-4	ELECTRICAL SPECIFICATIONS
GN-1	CENTEK NOTES AND SPECIFICATIONS
GN-1.1	LEGENDS AND ABBREVIATIONS
GN-1.2	DISH RF SIGNAGE
GN-1.3	DISH GENERAL NOTES
GN-1.4	DISH GENERAL NOTES
GN-1.5	DISH GENERAL NOTES
RF-1	RF CABLE COLOR CODES


SCOPE OF WORK

THIS IS NOT AN ALL INCLUSIVE LIST. CONTRACTOR SHALL UTILIZE SPECIFIED EQUIPMENT PART OR ENGINEER APPROVED EQUIVALENT. CONTRACTOR SHALL VERIFY ALL NEEDED EQUIPMENT TO PROVIDE A FUNCTIONAL SITE. THE PROJECT GENERALLY CONSISTS OF THE FOLLOWING:

- TOWER SCOPE OF WORK:**
- INSTALL (3) PROPOSED PANEL ANTENNAS (1 PER SECTOR)
 - INSTALL (3) PROPOSED ANTENNA MOUNT FRAMES (1 PER SECTOR)
 - INSTALL PROPOSED JUMPERS
 - INSTALL (6) PROPOSED RRUs (2 PER SECTOR)
 - INSTALL (1) PROPOSED OVER VOLTAGE PROTECTION DEVICE (OVP)
 - INSTALL (1) PROPOSED HYBRID CABLE

- GROUND SCOPE OF WORK:**
- INSTALL (1) PROPOSED 5' x 7' STEEL EQUIPMENT PLATFORM ATOP AN EXISTING CONCRETE PAD
 - INSTALL (1) PROPOSED PPC CABINET
 - INSTALL (1) PROPOSED EQUIPMENT CABINET
 - INSTALL (1) PROPOSED POWER CONDUIT
 - INSTALL (1) PROPOSED TELCO CONDUIT
 - INSTALL (1) PROPOSED TELCO-FIBER BOX
 - INSTALL (1) PROPOSED GPS UNIT
 - INSTALL (1) PROPOSED SAFETY SWITCH (IF REQUIRED)
 - INSTALL (1) PROPOSED FIBER NID (IF REQUIRED)
 - INSTALL (1) PROPOSED 200A RATED UTILITY METER

SITE PHOTO



UNDERGROUND SERVICE ALERT
UTILITY NOTIFICATION CENTER OF (CT)
1-800-922-4455



CALL 2 WORKING DAYS UTILITY NOTIFICATION PRIOR TO CONSTRUCTION

GENERAL NOTES

THE FACILITY IS UNMANNED AND NOT FOR HUMAN HABITATION. A TECHNICIAN WILL VISIT THE SITE AS REQUIRED FOR ROUTINE MAINTENANCE. THE PROJECT WILL NOT RESULT IN ANY SIGNIFICANT DISTURBANCE OR EFFECT ON DRAINAGE. NO SANITARY SEWER SERVICE, POTABLE WATER, OR TRASH DISPOSAL IS REQUIRED AND NO COMMERCIAL SIGNAGE IS PROPOSED.

11"x17" PLOT WILL BE HALF SCALE UNLESS OTHERWISE NOTED

CONTRACTOR SHALL VERIFY ALL PLANS, EXISTING DIMENSIONS, AND CONDITIONS ON THE JOB SITE, AND SHALL IMMEDIATELY NOTIFY THE ENGINEER IN WRITING OF ANY DISCREPANCIES BEFORE PROCEEDING WITH THE WORK.

SITE INFORMATION

PROPERTY OWNER:	LEWIS DAVID BABCOCK LLC
ADDRESS:	227 BOOMBRIDGE RD NORTH STONINGTON, CT 06359
SITE TYPE:	TOWER
COUNTY:	NEW LONDON
LATITUDE (NAD 83):	41° 25' 43.71" N
LONGITUDE (NAD 83):	71° 48' 32.75" W
ZONING JURISDICTION:	CONNECTICUT SITING COUNCIL
ZONING CODE:	R60
PARCEL NUMBER:	119 6314
OCCUPANCY GROUP:	N/A
CONSTRUCTION TYPE:	N/A
POWER COMPANY:	EVERSOURCE
TELEPHONE COMPANY:	TBD

PROJECT DIRECTORY

APPLICANT:	DISH Wireless L.L.C. 5701 SOUTH SANTA FE DRIVE LITTLETON, CO 80120
SITE DESIGNER:	CENTEK ENGINEERING, INC. 63-2 NORTH BRANFORD ROAD BRANFORD, CT. 06405 (203) 488-0580
SITE ACQUISITION:	DAVID GOODFELLOW (860) 305-3841
CONSTRUCTION MANAGER:	CHAD WILCOX (860) 573-2758
RF ENGINEER:	IRENE RANGEL (312) 929-9086

DIRECTIONS

DIRECTIONS FROM BRADLEY AIRPORT TO 277 BOOMBRIDGE ROAD, NORTH STONINGTON

1. HEAD NORTHWEST FROM BRADLEY INTL AIRPORT. GO FOR 0.03 MI.
2. KEEP LEFT TOWARD TERMINAL PARKING A/B/ARRIVALS A/B. GO FOR 0.4 MI.
3. CONTINUE STRAIGHT AHEAD. GO FOR 0.3 MI.
4. KEEP RIGHT TOWARD CT-20/I-91. GO FOR 0.1 MI.
5. CONTINUE ON BRADLEY FIELD CONN. GO FOR 0.5 MI.
6. CONTINUE ON CT-20 E (BRADLEY FIELD CONN). GO FOR 3.2 MI.
7. TAKE THE EXIT TOWARD HARTFORD ONTO I-91 S (RICHARD P HORAN MEMORIAL HWY). GO FOR 1.3 MI.
8. KEEP RIGHT ONTO I-91 S (RICHARD P HORAN MEMORIAL HWY) TOWARD I-91. GO FOR 8.5 MI.
9. TAKE THE LEFT EXIT ONTO I-84 E (BULKELEY BRG). GO FOR 0.6 MI.
10. TAKE EXIT 55 TOWARD NORWICH/NEW LONDON ONTO CT-2 E. GO FOR 37.5 MI
11. TURN RIGHT ONTO WASHINGTON ST (CT-2 E/CT-32 S). GO FOR 0.2 MI.
12. CONTINUE ON WASHINGTON ST (CT-2/CT-32). GO FOR 0.4 MI.
13. TURN LEFT ONTO BROADWAY. GO FOR 0.6 MI.
14. CONTINUE ON UNION ST. GO FOR 0.4 MI.
15. KEEP RIGHT ONTO BROADWAY. GO FOR 0.1 MI.
16. TURN LEFT ONTO MAIN ST. GO FOR 0.05 MI.
17. TAKE THE 1ST EXIT FROM ROUNDABOUT ONTO MAIN ST. GO FOR 0.2 MI.
18. CONTINUE ON CT-2. GO FOR 14.1 MI.
19. TAKE THE 3RD EXIT IN ROUNDABOUT ONTO PROVIDENCE NEW LONDON TPKE (CT-184 E). GO FOR 2.8 MI.
20. TURN RIGHT ONTO BOOMBRIDGE RD. GO FOR 0.5 MI.
21. 227 BOOMBRIDGE RD NORTH STONINGTON, CT 06359-1704 ACCESS ROAD WILL BE ON THE LEFT.

VICINITY MAP



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



CENTEKengineering
Centered on Solutions™

(203) 488-0580
(203) 488-8587 Fax
63-2 North Branford Road
Branford, CT 06405

www.CentekEng.com



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
BSP	TJR	

RFDS REV #: 0 - 08/17/2023

CONSTRUCTION DOCUMENTS

SUBMITTALS



REV	DATE	DESCRIPTION
A	10/05/23	ISSUED FOR CLIENT REVIEW
B	10/17/23	REVISED PER CLIENT COMMENTS
0	12/01/23	ISSUED FOR CONSTRUCTION

CENTEK PROJECT NUMBER
23009.09

DISH Wireless L.L.C.
PROJECT INFORMATION
**BOBOS01171A
227 BOOMBRIDGE RD
NORTH STONINGTON CT,
06359**

SHEET TITLE
TITLE SHEET



SHEET NUMBER
T-1



1



NO SCALE 2



3

dish
wireless.


5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



CEN TEK engineering
Centered on Solutions™

(203) 488-0580
(203) 488-8587 Fax
63-2 North Branford Road
Branford, CT 06405

www.CentekEng.com



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
BSP	TJR	

RFDS REV #: 0 - 08/17/2023

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/05/23	ISSUED FOR CLIENT REVIEW
B	10/17/23	REVISED PER CLIENT COMMENTS
0	12/01/23	ISSUED FOR CONSTRUCTION


CEN TEK PROJECT NUMBER
23009.09

DISH Wireless L.L.C.
PROJECT INFORMATION

BOBOS0171A
227 BOOMBRIDGE RD
NORTH STONINGTON CT,
06359

SHEET TITLE
OVERALL SITE PLAN

SHEET NUMBER
C-1



STRUCTURAL COMPLIANCE



ANTENNA MOUNTS
 A STRUCTURAL ANALYSIS OF THE ANTENNA MOUNTS WAS PERFORMED FOR THE PROPOSED EQUIPMENT INSTALLATION AND THEY WERE FOUND TO BE STRUCTURALLY SUFFICIENT TO ACCOMMODATE THE PROPOSED LOADING.
 REFER TO THE ANTENNA MOUNT ANALYSIS REPORT PREPARED BY CENTEK ENGINEERING (PROJECT # 23009.09) DATED 09/19/23 FOR ADDITIONAL INFORMATION AND REQUIREMENTS.

TOWER AND TOWER FOUNDATION
 A STRUCTURAL ANALYSIS OF THE TOWER AND TOWER FOUNDATION WAS PERFORMED FOR THE PROPOSED EQUIPMENT INSTALLATION AND THEY WERE FOUND TO BE STRUCTURALLY SUFFICIENT TO ACCOMMODATE THE PROPOSED LOADING.
 REFER TO THE STRUCTURAL ANALYSIS REPORT PREPARED BY CENTEK ENGINEERING (PROJECT # 23009.09) DATED 09/19/23 FOR ADDITIONAL INFORMATION AND REQUIREMENTS.


NOTE: NO EQUIPMENT SHALL BE INSTALLED ON THE HOSTING STRUCTURE WITHOUT A PASSING STRUCTURAL ANALYSIS REPORT AND CONTRACTOR PRIOR CONFIRMATION THAT ANY AND ALL REQUISITE MODIFICATIONS HAVE BEEN COMPLETED.

NOTE:
 GROUND EQUIPMENT BY OTHERS, NOT SHOWN FOR CLARITY


TOWER ELEVATION



ALPHA/BETA/GAMMA SECTOR TYP.




ANTENNA CONFIGURATION PLAN



SECTOR	POSITION	ANTENNA						TRANSMISSION CABLE
		EXISTING OR PROPOSED	MANUFACTURER - MODEL NUMBER	TECHNOLOGY	SIZE (HxW)	AZIMUTH	RAD CENTER	FEED LINE TYPE AND LENGTH
ALPHA	A2	PROPOSED	COMMSCOPE - FFV-65B-R2	n70, n71, n66	72.0" x 19.6"	30°	153'-0"	CU12PSM6P4XXX_4AWG APPROX. 250FT
BETA	B2	PROPOSED	COMMSCOPE - FFV-65B-R2	n70, n71, n66	72.0" x 19.6"	150°	153'-0"	SHARED WITH ALPHA
GAMMA	C2	PROPOSED	COMMSCOPE - FFV-65B-R2	n70, n71, n66	72.0" x 19.6"	270°	153'-0"	SHARED WITH ALPHA

SECTOR	POSITION	RRH		NOTES
		MANUFACTURER - MODEL NUMBER	TECHNOLOGY	
ALPHA	A2	SAMSUNG - RF4450t-71A / SFG-ARR3J601DI	n71	1. CONTRACTOR TO REFER TO FINAL CONSTRUCTION RFDS FOR ALL RF DETAILS. 2. ANTENNA AND RRH MODELS MAY CHANGE DUE TO EQUIPMENT AVAILABILITY. ALL EQUIPMENT CHANGES MUST BE APPROVED AND REMAIN IN COMPLIANCE WITH THE PROPOSED DESIGN AND STRUCTURAL ANALYSES. 3. ALL HYBRID/COAX LENGTHS TO BE MEASURED AND VERIFIED IN FIELD BEFORE ORDERING.
	A2	SAMSUNG - RF4451d-70A / SFG-ARR3KM01DI	n70 n66	
BETA	B2	SAMSUNG - RF4450t-71A / SFG-ARR3J601DI	n71	
	B2	SAMSUNG - RF4451d-70A / SFG-ARR3KM01DI	n70 n66	
GAMMA	C2	SAMSUNG - RF4450t-71A / SFG-ARR3J601DI	n71	
	C2	SAMSUNG - RF4451d-70A / SFG-ARR3KM01DI	n70 n66	
ALPHA		RAYCAP - RDIDC-9181-PF-48 (OVP BOX)		

ANTENNA SCHEDULE



5701 SOUTH SANTA FE DRIVE
 LITTLETON, CO 80120



CEN TEK engineering
 Centered on Solutions™

(203) 488-0580
 (203) 488-8587 Fax
 63-2 North Branford Road
 Branford, CT 06405

www.CentekEng.com



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
BSP	TJR	

RFDS REV #: 0 - 08/17/2023

CONSTRUCTION DOCUMENTS

SUBMITTALS


REV	DATE	DESCRIPTION
A	10/05/23	ISSUED FOR CLIENT REVIEW
B	10/17/23	REVISED PER CLIENT COMMENTS
0	12/01/23	ISSUED FOR CONSTRUCTION

CEN TEK PROJECT NUMBER
23009.09


DISH Wireless L.L.C.
 PROJECT INFORMATION
BOBOS01171A
227 BOOMBRIDGE RD
NORTH STONINGTON CT,
06359

SHEET TITLE
 ELEVATION, ANT. LAYOUT
 AND SCHEDULE


SHEET NUMBER



PROPOSED EQUIPMENT PLAN




1



NOTE:
FIELD CREW TO CONSULT WITH DISH CM FOR CABINET, H-FRAME POST AND UNISTRUT PLACEMENTS


EQUIPMENT ELEVATION



2

COMMSCOPE MTC4045LP 5X7 PLATFORM	
DIMENSIONS (HxWxL)	16"x84"x60"
WEIGHT/ VOLUME	423 LBS

NOTE:
GC TO PROVIDE EXTENDED THREAD FOR PLATFORM IF REQUIRED HEIGHT EXCEEDS 17"




PLATFORM DETAIL

NO SCALE 3

COMMSCOPE MTC4045HFLD H-FRAME	
UNISTRUT/SUPPORT RAILS QTY	5
WEIGHT	59.74 LBS

NOTE:
OR DISH Wireless L.L.C. APPROVED EQUIVALENT



H-FRAME DETAIL


NO SCALE 4



CEN TEK engineering
Centered on Solutions™

(203) 488-0580
(203) 488-8587 Fax
63-2 North Branford Road
Branford, CT 06405

www.CentekEng.com



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
BSP	TJR	

RFDS REV #: 0 - 08/17/2023

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/05/23	ISSUED FOR CLIENT REVIEW
B	10/17/23	REVISED PER CLIENT COMMENTS
0	12/01/23	ISSUED FOR CONSTRUCTION

CEN TEK PROJECT NUMBER
23009.09

DISH Wireless L.L.C.
PROJECT INFORMATION

BOBOS0171A
227 BOOMBRIDGE RD
NORTH STONINGTON CT,
06359

SHEET TITLE
EQUIPMENT PLATFORM
AND H-FRAME DETAILS

SHEET NUMBER
C-3

SQUARE D SAFETY SWITCHES D224NRB	
ENCLOSURE DIM (HxWxD)	29.25"x19.00"x8.50"
ENCLOSURE TYPE	NEMA 3R RAINPROOF
UL LISTED	FILE E-2875

TOP

SIDE

FRONT

RAYCAP PPC RDIAC-2465-P-240-MTS	
ENCLOSURE DIMENSIONS (HxWxD):	39"x22.855"x12.593
WEIGHT:	80 lbs
OPERATING AC VOLTAGE	240/120 1 PHASE 3W+G

TOP

BACK

SIDE

FRONT

SIDE

CHARLES INDUSTRY HEX CUBE-PM639155N4	
DIMENSIONS (HxWxD):	74"x32"x32"
POWER PLANT:	-48VDC ABB/600W
TOTAL WEIGHT (EMPTY)	408 LBS

PLAN

SIDE

BACK

SIDE

FRONT

SAFETY SWITCH DETAIL NO SCALE 1

POWER PROTECTIVE CABINET DETAIL NO SCALE 2

CABINET DETAIL NO SCALE 3

ZAYO 5RU CABINET LEFT SWING DOOR ('LIT' SITES)	
DIMENSIONS (HxWxD)	36.115"x29"x12.9"
WEIGHT	85 LBS
POWER INPUT	20A, -48VDC

PLAN

FRONT

SIDE

BACK

ROSENBERGER GPSGLONASS-36-N-S	
DIMENSION (DIA x H)	69mm x 98.5mm
WEIGHT (WITH ACCESSORIES)	515.74g
CONNECTOR	N-FEMALE
FREQUENCY RANGE	1559 MHz ~ 1610.5MHz

TOP

SIDE

BACK

GPS UNIT

GROUNDING KIT

MOUNTING BRACKET

MINIMUM OF 75% OR 270° IN ANY DIRECTION

GPS

GPS UNIT

OBSTRUCTIONS MUST BE BELOW 10°

FIBER NID ENCLOSURE DETAIL NO SCALE 4

GPS DETAIL NO SCALE 5

GPS MINIMUM SKY VIEW REQUIREMENTS NO SCALE 6

CHARLES CFT-PF2020D5H1 FIBER TELCO ENCLOSURE	
ENCLOSURE DIMS (HxWxD)	20"x20"x9"
ENCLOSURE WEIGHT	20 lbs
MOUNTING	WALL
COMPLIANCE	TYPE 4

FRONT

SIDE

BACK

FRONT

1.75"φ

27" MIN BEND RADIUS

CU12PSM6P4XXX (4 AWG CONDUCTORS)

1.60"φ

24" MIN BEND RADIUS

CU12PSM9P6XXX (6 AWG CONDUCTORS)

1.41"φ

22" MIN BEND RADIUS

CU12PSM9P8XXX (8 AWG CONDUCTORS)

SITEPROF CABLE LADDER	
DIMENSIONS (LxW) (PER CABLE LADDER SECTION)	237.5" x 29.5"
WEIGHT/ VOLUME	81.5 LBS
CABLE RUN (QTY)	9
MODEL	WCL9

FIBER TELCO ENCLOSURE DETAIL NO SCALE 7

CABLES UNLIMITED HYBRID CABLE MINIMUM BEND RADIUS NO SCALE 8

CABLE LADDER DETAIL NO SCALE 9

5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120

NSS
NORTHEAST
SITE SOLUTIONS
Turnkey Wireless Development

CEN TEK engineering
Centered on Solutions™

(203) 488-0580
(203) 488-8587 Fax
63-2 North Branford Road
Branford, CT 06405

www.CentekEng.com

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
BSP	TJR	

RFDS REV #: 0 - 08/17/2023

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/05/23	ISSUED FOR CLIENT REVIEW
B	10/17/23	REVISED PER CLIENT COMMENTS
0	12/01/23	ISSUED FOR CONSTRUCTION

CEN TEK PROJECT NUMBER
23009.09


DISH Wireless L.L.C.
PROJECT INFORMATION

BOBOS01171A
227 BOOMBRIDGE RD
NORTH STONINGTON CT,
06359

SHEET TITLE
TYPICAL EQUIPMENT
DETAILS


SHEET NUMBER
C-4

SAMSUNG RF4450t-71A / SFG-ARR3J601DI	
DIMENSIONS (HxWxD)	16.5"x15.0"x11.0"
WEIGHT	94.58 lbs



PLAN


NOTE:
ALL VISIBLE RRH'S SHALL BE WRAPPED IN CONCEALFAB MMW VINYL FILM WRAP (PART #900864-99 OR APPROVED EQUAL)




BACKSIDEFRONT

SAMSUNG RF4451d-70A / SFG-ARR3KM01DI	
DIMENSIONS (HxWxD)	15.0"x15.0"x8.9"
WEIGHT	61.3 lbs

NOTE:
ALL VISIBLE RRH'S SHALL BE WRAPPED IN CONCEALFAB MMW VINYL FILM WRAP (PART #900864-99 OR APPROVED EQUAL)




PLAN



BACKSIDEFRONT

SABRE DOUBLE Z-BRACKET C10123155	
DIMENSIONS (HxWxD) (1 BRACKET)	5"x20"x1-13/16"
WEIGHT (FULL ASSEMBLY)	35.79 lbs
PACKAGE QUANTITY	4

#	DESCRIPTION
1	PLATE, CHANNEL BRACKET
2	RRH Z BRACKET, 3/16"
3	THREADED ROD ASSEMBLY 1/2"x12"




NOTE:
OR DISH Wireless L.L.C. APPROVED EQUIVALENT

RRH DETAIL NO SCALE 1


RRH DETAIL NO SCALE 2

RRH MOUNT DETAIL NO SCALE 3

RAYCAP RDIDC-9181-PF-48 SURGE PROTECTION DEVICE (OVP)	
DIMENSIONS (HxWxD)	18.97"x16.21"x9.64"
WEIGHT	21 lbs




PLAN




BACKSIDEFRONT

COMMSCOPE FFV-65B-R2	
DIMENSIONS (HxWxD)(MM/IN)	1828x498x197 72"x19.6"x7.8"
RF CONNECTOR INTERFACE	4.3-10 FEMALE
WEIGHT	70.8 lbs
WEIGHT WITH BRACKETS	98.1 lbs

NOTE:
ALL VISIBLE ANTENNAS SHALL BE WRAPPED IN CONCEALFAB MMW VINYL FILM WRAP (PART #900864-99 OR APPROVED EQUAL)




PLAN



BACKSIDEFRONT

JMA ANTENNA MOUNT BRACKET #91900318	
TOTAL WEIGHT (WITH BRACKETS)	18 lbs (8.18 Kg)
POLE DIAMETER RANGE	2.5" TO 4.5"

NOTE:
KIT #91900318: TOP AND BOTTOM BRACKETS FOR 4-, 6-, AND 8-FOOT ANTENNAS
ANTENNA BRACKET NOT PART OF KIT




NOTE:
OR DISH Wireless L.L.C. APPROVED EQUIVALENT


SURGE PROTECTION DEVICE DETAIL (OVP) NO SCALE 4

ANTENNA DETAIL NO SCALE 5

ANTENNA BRACKET DETAIL NO SCALE 6



ANTENNA SECTOR FRAME SITEPRO P/N: VFA8-HD	
DIMENSION	8" HORIZONTAL FACE, 40" SEPARATION



ANTENNA FRAME DETAIL

NOT USED

ANTENNA FRAME DETAIL NO SCALE 7


NOT USED NO SCALE 8



CEN TEK engineering
Centered on Solutions™

(203) 488-0580
(203) 488-8587 Fax
63-2 North Branford Road
Branford, CT 06405

www.CentekEng.com



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
BSP	TJR	

RFDS REV #: 0 - 08/17/2023

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/05/23	ISSUED FOR CLIENT REVIEW
B	10/17/23	REVISED PER CLIENT COMMENTS
0	12/01/23	ISSUED FOR CONSTRUCTION

CENTEK PROJECT NUMBER
23009.09

DISH Wireless L.L.C.
PROJECT INFORMATION

BOBOS01171A
227 BOOMBRIDGE RD
NORTH STONINGTON CT,
06359

SHEET TITLE
TYPICAL EQUIPMENT
DETAILS


SHEET NUMBER
C-5

NOTES


1. CONTRACTOR SHALL FIELD VERIFY ALL PROPOSED UNDERGROUND UTILITY CONDUIT ROUTES. (EXISTING CONDUITS MAY BE REUSED PROVIDED THEY MEET THE SPECIFICATIONS IN THESE DOCUMENTS AND ARE IN PROPER WORKING CONDITION)
2. THE GROUND LEASE PROVIDES BROAD/BLANKET UTILITY RIGHTS. "PWR" AND "FBR" PATH DEPICTED ON C-2 AND E-1 ARE BASED ON BEST AVAILABLE INFORMATION INCLUDING BUT NOT LIMITED TO FIELD VERIFICATION, PRIOR PROJECT DOCUMENTATION AND OTHER REAL PROPERTY RIGHTS DOCUMENTS. WHEN INSTALLING THE UTILITIES PLEASE LOCATE AND FOLLOW EXISTING PATH. IF EXISTING PATH IS NOT AN OPTION, PLEASE NOTIFY TOWER OWNER AS FURTHER COORDINATION MAY BE NEEDED.

NOTE

CONTRACTOR IS RESPONSIBLE TO VERIFY FINAL CONDUIT ROUTING, LENGTH OF RUN, AND FEASIBILITY.



ENLARGED SITE PLAN



1



AERIAL VIEW PLAN

NO SCALE

2



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120




NSS
NORTHEAST
SITE SOLUTIONS
Turnkey Wireless Development

CEN TEK engineering
Centered on Solutions™

(203) 488-0580
(203) 488-8587 Fax
63-2 North Branford Road
Branford, CT 06405

www.CentekEng.com



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
BSP	TJR	

RFDS REV #: 0 - 08/17/2023

CONSTRUCTION DOCUMENTS

SUBMITTALS

REV	DATE	DESCRIPTION
A	10/05/23	ISSUED FOR CLIENT REVIEW
B	10/17/23	REVISED PER CLIENT COMMENTS
0	12/01/23	ISSUED FOR CONSTRUCTION

CEN TEK PROJECT NUMBER
23009.09

DISH Wireless L.L.C.
PROJECT INFORMATION
BOBOS01171A
227 BOOMBRIDGE RD
NORTH STONINGTON CT,
06359


SHEET TITLE
ELECTRICAL AND FIBER
ROUTING PLAN WITH NOTES

SHEET NUMBER

E-1

DC POWER WIRING SHALL BE COLOR CODED AT EACH END FOR IDENTIFYING +24V AND -48V CONDUCTORS. RED MARKINGS SHALL IDENTIFY +24V AND BLUE MARKINGS SHALL IDENTIFY -48V.


- CONTRACTOR SHALL INSPECT THE EXISTING CONDITIONS PRIOR TO SUBMITTING A BID. ANY QUESTIONS ARISING DURING THE BID PERIOD IN REGARDS TO THE CONTRACTOR'S FUNCTIONS, THE SCOPE OF WORK, OR ANY OTHER ISSUE RELATED TO THIS PROJECT SHALL BE BROUGHT UP DURING THE BID PERIOD WITH THE PROJECT MANAGER FOR CLARIFICATION, NOT AFTER THE CONTRACT HAS BEEN AWARDED.
- ALL ELECTRICAL WORK SHALL BE DONE IN ACCORDANCE WITH CURRENT NATIONAL ELECTRICAL CODES AND ALL STATE AND LOCAL CODES, LAWS, AND ORDINANCES. PROVIDE ALL COMPONENTS AND WIRING SIZES AS REQUIRED TO MEET NEC STANDARDS.
- LOCATION OF EQUIPMENT, CONDUIT AND DEVICES SHOWN ON THE DRAWINGS ARE APPROXIMATE AND SHALL BE COORDINATED WITH FIELD CONDITIONS PRIOR TO CONSTRUCTION.
- CONDUIT ROUGH-IN SHALL BE COORDINATED WITH THE MECHANICAL EQUIPMENT CONTRACTOR AND COMPLY AS REQUIRED.
- CONTRACTOR SHALL PROVIDE ALL BREAKERS, CONDUITS AND CIRCUITS AS REQUIRED FOR A COMPLETE SYSTEM.
- CONTRACTOR SHALL PROVIDE PULL BOXES AND JUNCTION BOXES AS REQUIRED BY THE NEC ARTICLE 314.
- CONTRACTOR SHALL PROVIDE ALL STRAIN RELIEF AND CABLE SUPPORTS FOR ALL CABLE ASSEMBLIES. INSTALLATION SHALL BE IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS AND RECOMMENDATIONS.
- ALL DISCONNECTS AND CONTROLLING DEVICES SHALL BE PROVIDED WITH ENGRAVED PHENOLIC NAMEPLATES INDICATING EQUIPMENT CONTROLLED, BRANCH CIRCUITS INSTALLED ON, AND PANEL FIELD LOCATIONS FED FROM.
- INSTALL AN EQUIPMENT GROUNDING CONDUCTOR IN ALL CONDUITS PER THE SPECIFICATIONS AND NEC 250. THE EQUIPMENT GROUNDING CONDUCTORS SHALL BE BONDED AT ALL JUNCTION BOXES, PULL BOXES, AND ALL DISCONNECT SWITCHES, AND EQUIPMENT CABINETS.
- ALL NEW MATERIAL SHALL HAVE A U.L. LABEL.
- PANEL SCHEDULE LOADING AND CIRCUIT ARRANGEMENTS REFLECT POST-CONSTRUCTION EQUIPMENT.
- CONTRACTOR SHALL BE RESPONSIBLE FOR AS-BUILT PANEL SCHEDULE AND SITE DRAWINGS.



DARK TELCO BOX - INTERIOR WIRING LAYOUT

NO SCALE

2



LIT TELCO BOX - INTERIOR WIRING LAYOUT (OPTIONAL)

NO SCALE

3

ELECTRICAL NOTES

NO SCALE

1

NOT USED

NO SCALE

4

NOT USED

NO SCALE

5

NOT USED

NO SCALE

6

NOT USED

NO SCALE

7

NOT USED

NO SCALE

8




5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



CENTEKengineering
Centered on Solutions™

(203) 488-0580
(203) 488-8587 Fax
63-2 North Branford Road
Branford, CT 06405

www.CentekEng.com



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
BSP	TJR	

RFDS REV #: 0 - 08/17/2023

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/05/23	ISSUED FOR CLIENT REVIEW
B	10/17/23	REVISED PER CLIENT COMMENTS
0	12/01/23	ISSUED FOR CONSTRUCTION

CENTEK PROJECT NUMBER
23009.09


DISH Wireless L.L.C.
PROJECT INFORMATION

BOBOS01171A
227 BOOMBRIDGE RD
NORTH STONINGTON CT,
06359

SHEET TITLE
TELCO CABINET
DETAILS

SHEET NUMBER

E-2



RISER NOTES

- ① EXISTING 800A, TWO GANG MULTIMETER CENTER TO REMAIN. INSTALL NEW 200A, SINGLE PHASE, 240V RATED UTILITY METER WITH 200A/2P CIRCUIT BREAKER IN POSITION PREVIOUSLY SERVING SPRINT. ALL EQUIPMENT TO BE UTILITY APPROVED.
- ② ROUTED TO EXISTING FIBER DEMARC. CONTRACTOR TO VERIFY LOCATION IN FIELD.
- ③ (3) 3/0 AWG, (1) #6 AWG GROUND, 2" CONDUIT.
- ④ (1) 4" CONDUIT WITH PULL ROPES FOR TELEPHONE COMPANY CONDUCTORS. CONDUCTORS PROVIDED BY TELEPHONE COMPANY FROM EXISTING DEMARC TO EQUIPMENT PLATFORM. PROVIDE ALL COUPLINGS, ADAPTERS, SWEEPS, AND ASSOCIATED HARDWARE. MATERIAL SHALL BE PER TELEPHONE COMPANY SPECIFICATIONS.
- ⑤ NEW HEAVY DUTY NEMA-3R, 200A/240V, NON FUSED DISCONNECT.
- ⑥ EXPANSION COUPLING TYP.
- ⑦ NEW DISH Wireless L.L.C. TELCO/FIBER CABINET.
- ⑧ CONDUITS AND CONDUCTORS FOR TELCO CONNECTION TO EQUIPMENT CABINET AS REQUIRED BY MANUFACTURER AND CONSTRUCTION MANAGER FOR PROPER OPERATION OF EQUIPMENT
- ⑨ NEW 120/240V, 200A, SINGLE PHASE PPC CABINET.
- ⑩ 4 SETS OF (3) #10 AWG, (1) #10 AWG GROUND, 3/4" CONDUIT.
- ⑪ (2) #12 AWG, (1) #12 AWG GROUND, 3/4" CONDUIT. FOR CONVENIENCE OUTLET.
- ⑫ NEW DISH Wireless L.L.C. EQUIPMENT CABINET.

ELECTRICAL RISER DIAGRAM


NO SCALE 1

VOLTAGE:		120/240		PHASE:	1	WIRE:	3	PANEL NO.	MDP		
MAIN BUS:	200	AMPS		A FRAME	200	A TRIP		TOTAL WATTS, L1	11,700	LOC:	EQUIPMENT FRAME
MAIN BREAKER:	200							TOTAL WATTS, L2	11,700		
MOUNTING:	SURFACE							TOTAL WATTS	23,400		

DIRECTORY	WIRE & CONDUIT	WATTS LOAD		CKT.	AMPS	L1		AMPS	CKT.	WATTS LOAD		DIRECTORY
		L1	L2			L1	L2					
RECTIFIER #1	3/4" C, 2 #10, #10GND	2,880	2,880	1	30/2P			20	2	180	3/4" C, 2 #12, #12GND	CONVENIENCE GFCI OUTLET
RECTIFIER #2	3/4" C, 2 #10, #10GND	2,880	2,880	3	30/2P			20	4	180	3/4" C, 2 #12, #12GND	PPC GFCI OUTLET
RECTIFIER #3	3/4" C, 2 #10, #10GND	2,880	2,880	5	30/2P			20	6	180	-	SPACE
RECTIFIER #4	3/4" C, 2 #10, #10GND	2,880	2,880	7	30/2P			20	8	180	-	SPACE
SPACE	-	2,880	2,880	9	30/2P			20	10	180	-	SPACE
SPACE	-	2,880	2,880	11	30/2P			20	12	180	-	SPACE
SPACE	-	2,880	2,880	13	30/2P			20	14	180	-	SPACE
SPACE	-	2,880	2,880	15	30/2P			20	16	180	-	SPACE
SPACE	-	-	-	17				20	18	-	-	SPACE
SPACE	-	-	-	19				20	20	-	-	SPACE
SPACE	-	-	-	21				20	22	-	-	SPACE
SPACE	-	-	-	23				20	24	-	-	SPACE

ELECTRICAL PANEL SCHEDULE

NO SCALE 2



GROUNDING SCHEMATIC NOTES

- ① GROUND RING, #2 AWG BCW
 - ② #2/0 GREEN INSULATED
 - ③ #6 AWG
- GENERAL NOTES:
1. ALL SURGE SUPPRESSION EQUIPMENT SHALL BE BONDED TO GROUND PER MANUFACTURER'S SPECIFICATIONS
 2. UNLESS OTHERWISE NOTED OR REQUIRED BY CODE, GROUND CONDUCTORS SHOWN SHALL BE #2 AWG (SOLID TINNED BCW - EXTERIOR; STRANDED GREEN INSULATED - INTERIOR).
 3. BOND CABLE TRAY AND ICE BRIDGE SECTIONS TOGETHER WITH #6 AWG STRANDED GREEN INSULATED JUMPERS.
 4. ALL SECTOR GROUND BARS SHALL BE BONDED TOGETHER WITH #2 AWG SOLID TINNED BCW.
 5. BOND ALL EQUIPMENT CABINETS AND BATTERY CABINETS TO GROUND PER MANUFACTURER'S SPECIFICATIONS.
 6. ALL BONDS TO TOWER SHALL BE MADE IN STRICT ACCORDANCE WITH SPECIFICATIONS OF TOWER MANUFACTURER OR STRUCTURAL ENGINEER.
 7. REFER TO GROUNDING PLAN FOR LOCATION OF GROUNDING DEVICES.
 8. REFER TO ALL ELECTRICAL AND GROUNDING DETAILS.
 9. COORDINATE ALL TOWER MOUNTED EQUIPMENT WITH OWNER.
 10. ALL TOWER MOUNTED AMPLIFIERS AND ASSOCIATED EQUIPMENT SHALL BE BONDED TO THE SECTOR GROUND BAR PER MANUFACTURER'S SPECIFICATIONS.
 11. ALL GROUNDING SHALL BE IN ACCORDANCE WITH NEC AND OWNER'S REQUIREMENTS.
 12. COORDINATE WITH TOWER OWNER BEFORE INSTALLING ANY GROUNDING ELEMENTS ON TOWER OR BONDING TO EXISTING TOWER GROUND RING.

ELECTRICAL SCHEMATIC DIAGRAM

NO SCALE 3




5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



CENTEK engineering
Centered on Solutions™

(203) 488-0580
(203) 488-8587 Fax
63-2 North Branford Road
Branford, CT 06405

www.CentekEng.com



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
BSP	TJR	

RFDS REV #: 0 - 08/17/2023

CONSTRUCTION DOCUMENTS

SUBMITTALS

REV	DATE	DESCRIPTION
A	10/05/23	ISSUED FOR CLIENT REVIEW
B	10/17/23	REVISED PER CLIENT COMMENTS
0	12/01/23	ISSUED FOR CONSTRUCTION


CENTEK PROJECT NUMBER
23009.09

DISH Wireless L.L.C.
PROJECT INFORMATION
BOBOS0171A
227 BOOMBRIDGE RD
NORTH STONINGTON CT,
06359

SHEET TITLE
ELECTRICAL RISER, PANEL
SCHEDULE, AND SCHEMATIC

SHEET NUMBER

E-3



COMPOUND GROUNDING PLAN


NO SCALE 1

GROUNDING PLAN NOTES:

- ① LOWER TOWER MOUNTED GROUND BAR.
- ② UPPER TOWER MOUNTED GROUND BAR.
- ③ BOND LOWER TOWER MOUNTED GROUND BAR TO UPPER TOWER MOUNTED GROUND BAR TYP. 2 LEADS.
- ④ ALL SECTOR GROUND BARS SHALL BE BONDED TOGETHER WITH #2 AWG SOLID TINNED BCW.
- ⑤ BOND LOWER TOWER MOUNTED GROUND BAR TO ICE-BRIDGE POST.
- ⑥ CONNECT LOWER TOWER MOUNTED GROUND BAR TO EXISTING TOWER GROUND RING TYP. 2 LEADS.
- ⑦ BOND ANTENNA AND ANTENNA APPURTENANCES MOUNTING PIPES TO SECTOR GROUND BAR. (TYPICAL).
- ⑧ BOND SECTOR GROUND BAR TO TOWER. (TYP)
- ⑨ #2 SOLID TINNED BCW GROUND RING (2'-0" FROM OUTSIDE EDGE OF EQUIPMENT PLATFORM FOUNDATION WHEN ROUTED ALONG PLATFORM PERIMETER.) (TYP.).
- ⑩ GROUNDING ROD WITH ACCESS (TYP.).
- ⑪ GROUNDING ROD (TYP.).
- ⑫ MAIN EQUIPMENT GROUND BAR.
- ⑬ BOND MAIN GROUND BAR TO GROUND RING.
- ⑭ CONNECT PLATFORM TO GROUNDING RING (TYP. EACH CORNER OF GROUND RING).
- ⑮ BOND EQUIPMENT CABINETS TO GROUND BAR PER NEC AND MANUFACTURER REQUIREMENTS
- ⑯ BOND EQUIPMENT TO GROUND BAR PER NEC AND MANUFACTURER REQUIREMENTS
- ⑰ BOND GROUND BAR TO EQUIPMENT PLATFORM STEEL TYP.
- ⑱ CONNECT EQUIPMENT GROUND RING TO EXISTING COMPOUND GROUND RING- CONTRACTOR TO VERIFY LOCATION COMPOUND GROUND RING IN FIELD.
- ⑲ CONNECT UPPER TOWER MOUNTED GROUND BAR TO SECTOR GROUND BAR TYP.
- ⑳ SECTOR GROUND BAR TYP.
- ㉑ GROUND BAR MOUNTED TO EXISTING ICE BRIDGE.
- ㉒ BOND GROUND BAR TO GROUND RING.
- ㉓ BOND GROUND BAR TO EXISTING ICE BRIDGE.
- ㉔ BOND FENCE AND FENCE GATE TO GROUND RING PER DETAILS.
- ㉕ BOND NEW FENCE TO EXISTING FENCE.

GROUNDING PLAN NOTES

NO SCALE 2



ANTENNA GROUNDING PLAN

NO SCALE 3




5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



CEN TEK engineering
Centered on Solutions™

(203) 488-0580
(203) 488-8587 Fax
63-2 North Branford Road
Branford, CT 06405

www.CentekEng.com



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
BSP	TJR	

RFDS REV #: 0 - 08/17/2023

CONSTRUCTION DOCUMENTS


SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/05/23	ISSUED FOR CLIENT REVIEW
B	10/17/23	REVISED PER CLIENT COMMENTS
0	12/01/23	ISSUED FOR CONSTRUCTION

CEN TEK PROJECT NUMBER
23009.09


DISH Wireless L.L.C.
PROJECT INFORMATION
BOBOS0171A
227 BOOMBRIDGE RD
NORTH STONINGTON CT,
06359

SHEET TITLE
COMPOUND/ANTENNA
GROUNDING PLAN AND NOTES


SHEET NUMBER
G-1



- NOTES**
- HIGH CONDUCTIVITY TINNED COPPER BAR 1'-8"Lx4"Wx1/4"D.
 - RED COLORED STANDOFF INSULATOR PLASTIC #1872-1A.
 - STAINLESS STEEL TRUSS SPANNER MACHINE SCREWS, SPLIT LOCKWASHER AND FLAT WASHER.
 - 1"Wx1/8" STAINLESS STEEL TYPE 304 BRACKET.
 - STAINLESS STEEL TYPE 304 HARDWARE - 3/8" EXPANSION BOLT FOR CONCRETE.









- NOTES:**
- DO NOT INSTALL CABLE GROUND KIT AT A BEND AND ALWAYS DIRECT GROUND WIRE DOWN TO CIGBE



BILL OF MATERIALS


ITEM	DESCRIPTION	QUANTITY
1	2-1/2" SCH. 40 x 8'-0" LG. MAX SS OR GALV. PIPE	1
2	UNIVERSAL CLAMP SET.	2



CENTEK engineering
Centered on Solutions™

(203) 488-0580
(203) 488-8587 Fax
63-2 North Branford Road
Branford, CT 06405

www.CentekEng.com



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: BSP
CHECKED BY: TJR
APPROVED BY:

RFDS REV #: 0 - 08/17/2023

CONSTRUCTION DOCUMENTS

SUBMITTALS

REV	DATE	DESCRIPTION
A	10/05/23	ISSUED FOR CLIENT REVIEW
B	10/17/23	REVISED PER CLIENT COMMENTS
0	12/01/23	ISSUED FOR CONSTRUCTION

CENTEK PROJECT NUMBER
23009.09

DISH Wireless L.L.C.
PROJECT INFORMATION


BOBOS0171A
227 BOOMBRIDGE RD
NORTH STONINGTON CT,
06359

SHEET TITLE
TYPICAL GROUNDING
DETAILS

SHEET NUMBER
G-2

NOTES:

1. USE GROUND PLATE DETAIL IF 10 FT. GROUND ROD DEPTH CANNOT BE ACHIEVED DUE TO LEDGE CONDITION OR IF EXISTING TOWER FOUNDATION IS ENCOUNTERED.




GROUND ROD DETAIL

NO SCALE 1


NOTES:

1. INSPECTION HAND HOLE MAY BE CONCRETE OR PVC AND SHALL BE A MINIMUM OF 12" DIA x 18" DEEP.




GROUND ROD WITH ACCESS DETAIL

NO SCALE 2



ICE-BRIDGE GROUNDING DETAIL

NO SCALE 3



OUTDOOR CABINET GROUNDING

NO SCALE 4

NOT USED

NO SCALE 7

NOT USED

NO SCALE 8

NOT USED

NO SCALE 9




5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



CEN TEK engineering
Centered on Solutions™

(203) 488-0580
(203) 488-8587 Fax
63-2 North Branford Road
Branford, CT 06405

www.CentekEng.com



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
BSP	TJR	

RFDS REV #: 0 - 08/17/2023

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/05/23	ISSUED FOR CLIENT REVIEW
B	10/17/23	REVISED PER CLIENT COMMENTS
0	12/01/23	ISSUED FOR CONSTRUCTION

CEN TEK PROJECT NUMBER
23009.09

DISH Wireless L.L.C.
PROJECT INFORMATION
BOBOS0171A
227 BOOMBRIDGE RD
NORTH STONINGTON CT,
06359

SHEET TITLE
TYPICAL GROUNDING
DETAILS

SHEET NUMBER
G-3

ELECTRICAL SPECIFICATIONS

SECTION 16010

- 1.01. SCOPE OF WORK
- A. WORK SHALL INCLUDE ALL LABOR, EQUIPMENT AND SERVICES REQUIRED TO COMPLETE (MAKE READY FOR OPERATION) ALL THE ELECTRICAL WORK INCLUDING, BUT NOT LIMITED TO, THE FOLLOWING:
- 200A, 240/120V, 1P, 3 WIRE ELECTRIC SERVICE METER FOR OWNER AND ASSOCIATED DISTRIBUTION EQUIPMENT. (AS REQUIRED BY UTILITY CO.)
 - NEW SITE TELEPHONE SERVICE AS SPECIFIED BY TELEPHONE COMPANY.
 - CELLULAR GROUNDING SYSTEMS, CONSISTING OF ANTENNA GROUNDING, GROUND RING, GROUND BARS, ETC.
 - FIELD MEASURE EXISTING ELECTRICAL SERVICES TO CONFIRM AVAILABLE EXISTING POWER.
 - COORDINATE ALL WORK SHOWN, ON THESE PLANS WITH LOCAL UTILITY COMPANIES.
- B. LOCAL UTILITY COMPANIES SHALL PROVIDE THE FOLLOWING:
- TELEPHONE CABLES.
 - SHUTDOWN OF SERVICE (COORDINATE WITH OWNER).
- C. CONTRACTOR SHALL CONFER WITH LOCAL UTILITY COMPANIES TO ASCERTAIN THE LIMITS OF THEIR WORK AND SHALL INCLUDE IN BID ANY CHARGES OR FEES MADE BY THE UTILITY COMPANIES FOR THEIR PORTION OF THE WORK AND SHALL PROVIDE AND INSTALL ALL ITEMS REQUIRED, BUT NOT PROVIDED BY UTILITY COMPANY.
- D. ELECTRICAL CONTRACTOR SHALL COORDINATE ELECTRICAL INSTALLATION WITH ELECTRIC UTILITY CO. PRIOR TO INSTALLATION.
- E. CONTRACTOR SHALL COORDINATE WITH TELEPHONE UTILITY COMPANY FOR LOCATION OF TELEPHONE SERVICE AND TO DETERMINE ANY REQUIRED EQUIPMENT TO BE INSTALLED BY CONTRACTOR.

1.02. GENERAL REQUIREMENTS

- A. THE ENTIRE ELECTRICAL INSTALLATION SHALL BE MADE IN STRICT ACCORDANCE WITH ALL LOCAL, STATE AND NATIONAL CODES AND REGULATIONS WHICH MAY APPLY AND NOTHING IN THE DRAWINGS OR SPECIFICATIONS SHALL BE INTERPRETED AS AN INFRINGEMENT OF SUCH CODES OR REGULATIONS.
- B. THE ELECTRICAL CONTRACTOR IS TO BE RESPONSIBLE FOR THE COMPLETE INSTALLATION AND COORDINATION OF THE ENTIRE ELECTRICAL SERVICE. ALL ACTIVITIES TO BE COORDINATED THROUGH OWNERS REPRESENTATIVE, DESIGN ENGINEER AND OTHER AUTHORITIES HAVING JURISDICTION OF TRADES.
- C. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL PERMITS AND PAY ALL FEES THAT MAY BE REQUIRED FOR THE ELECTRICAL WORK AND FOR SCHEDULING OF ALL INSPECTIONS THAT MAY BE REQUIRED BY THE LOCAL AUTHORITY.
- D. THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATION WITH THE BUILDING OWNER FOR NEW AND/OR DEMOLITION WORK INVOLVED.
- E. THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATION WITH LOCAL TELEPHONE COMPANY THAT MAY BE REQUIRED FOR THE INSTALLATION OF TELEPHONE SERVICE TO THE PROPOSED CELLULAR SITE.
- F. NO MATERIAL OTHER THAN THAT CONTAINED IN THE "LATEST LIST OF ELECTRICAL FITTINGS" APPROVED BY THE UNDERWRITERS' LABORATORIES, SHALL BE USED IN ANY PART OF THE WORK. ALL MATERIAL FOR WHICH LABEL SERVICE HAS BEEN ESTABLISHED SHALL BEAR THE U.L. LABEL.
- G. THE CONTRACTOR SHALL GUARANTEE ALL NEW WORK FOR A PERIOD OF ONE YEAR FROM THE ACCEPTANCE DATE BY THE OWNER. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING WARRANTIES FROM ALL EQUIPMENT MANUFACTURERS FOR SUBMISSION TO THE OWNER.
- H. DRAWINGS INDICATE GENERAL ARRANGEMENT OF WORK INCLUDED IN CONTRACT. CONTRACTOR SHALL, WITHOUT EXTRA CHARGE, MAKE MODIFICATIONS TO THE LAYOUT OF THE WORK TO PREVENT CONFLICT WITH WORK OF OTHER TRADES AND FOR THE PROPER INSTALLATION OF WORK. CHECK ALL DRAWINGS AND VISIT JOB SITE TO VERIFY SPACE AND TYPE OF EXISTING CONDITIONS IN WHICH WORK WILL BE DONE, PRIOR TO SUBMITTAL OF BID.
- I. THE ELECTRICAL CONTRACTOR SHALL SUPPLY THREE (3) COMPLETE SETS OF APPROVED DRAWINGS, ENGINEERING DATA SHEETS, MAINTENANCE AND OPERATING INSTRUCTION MANUALS FOR ALL SYSTEMS AND THEIR RESPECTIVE EQUIPMENT. THESE MANUALS SHALL BE INSERTED IN VINYL COVERED 3-RING BINDERS AND TURNED OVER TO OWNER'S REPRESENTATIVE ONE (1) WEEK PRIOR TO FINAL PUNCH LIST.
- J. ALL WORK SHALL BE INSTALLED IN A NEAT AND WORKMAN LIKE MANNER AND WILL BE SUBJECT TO THE APPROVAL OF THE OWNER'S REPRESENTATIVE.
- K. ALL EQUIPMENT AND MATERIALS TO BE INSTALLED SHALL BE NEW, UNLESS OTHERWISE NOTED.
- L. BEFORE FINAL PAYMENT, THE CONTRACTOR SHALL PROVIDE A COMPLETE SET OF PRINTS (AS-BUILTS), LEGIBLY MARKED IN RED PENCIL TO SHOW ALL CHANGES FROM THE ORIGINAL PLANS.
- M. PROVIDE TEMPORARY POWER AND LIGHTING IN WORK AREAS AS REQUIRED.
- N. SHOP DRAWINGS:

- CONTRACTOR SHALL SUBMIT SIX (6) COPIES OF SHOP DRAWINGS ON ALL EQUIPMENT AND MATERIALS PROPOSED FOR USE ON THIS PROJECT, GIVING ALL DETAILS, WHICH INCLUDE DIMENSIONS, CAPACITIES, ETC.
- CONTRACTOR SHALL SUBMIT SIX (6) COPIES OF ALL TEST REPORTS CALLED FOR IN THE SPECIFICATIONS AND DRAWINGS.

- O. ENTIRE ELECTRICAL INSTALLATION SHALL BE IN ACCORDANCE WITH OWNER'S SPECIFICATIONS, AND REQUIREMENTS OF ALL LOCAL AUTHORITIES HAVING JURISDICTION. IT IS THE CONTRACTOR'S RESPONSIBILITY TO COORDINATE WITH APPROPRIATE INDIVIDUALS TO OBTAIN ALL SUCH SPECIFICATIONS AND REQUIREMENTS. NOTHING CONTAINED IN, OR OMITTED FROM, THESE DOCUMENTS SHALL RELIEVE CONTRACTOR FROM THIS OBLIGATION.

SECTION 16111

- 1.01. CONDUIT
- A. MINIMUM CONDUIT SIZE FOR BRANCH CIRCUITS, LOW VOLTAGE CONTROL AND ALARM CIRCUITS SHALL BE 3/4". CONDUITS SHALL BE PROPERLY FASTENED AS REQUIRED BY THE N.E.C.
- B. THE INTERIOR OF RACEWAYS/ ENCLOSURES INSTALLED UNDERGROUND SHALL BE CONSIDERED TO BE WET LOCATION, INSULATED CONDUCTORS SHALL BE LISTED FOR USE IN WET LOCATIONS. PROVIDE WEATHERPROOF CONSTRUCTION IN WET LOCATIONS.
- C. CONDUIT INSTALLED UNDERGROUND SHALL BE INSTALLED TO MEET MINIMUM COVER REQUIREMENTS OF TABLE 300.5.
- D. PROVIDE RIGID GALVANIZED STEEL CONDUIT (RMC) FOR THE FIRST 10 FOOT SECTION WHEN LEAVING A BUILDING OR SECTIONS PASSING THROUGH FLOOR SLABS
- E. ONLY LISTED PVC CONDUIT AND FITTINGS ARE PERMITTED FOR THE INSTALLATION OF ELECTRICAL CONDUCTORS, SUITABLE FOR UNDERGROUND APPLICATIONS.

CONDUIT SCHEDULE SECTION 16111			
CONDUIT TYPE	NEC REFERENCE	APPLICATION	MIN. BURIAL DEPTH (PER NEC TABLE 300.5) ^{2,3}
EMT	ARTICLE 358	INTERIOR CIRCUITING, EQUIPMENT ROOMS, SHELTERS	N/A
RMC, RIGID GALV. STEEL	ARTICLE 344, 300.5, 300.50	ALL INTERIOR/ EXTERIOR CIRCUITING, ALL UNDERGROUND INSTALLATIONS.	6 INCHES
PVC, SCHEDULE 40	ARTICLE 352, 300.5, 300.50	INTERIOR/ EXTERIOR CIRCUITING AND GROUNDING SYSTEMS, UNDERGROUND INSTALLATIONS, WHERE NOT SUBJECT TO PHYSICAL DAMAGE. ¹	18 INCHES
PVC, SCHEDULE 80	ARTICLE 352, 300.5, 300.50	INTERIOR/ EXTERIOR CIRCUITING AND GROUNDING SYSTEMS, UNDERGROUND INSTALLATIONS, WHERE SUBJECT TO PHYSICAL DAMAGE. ¹	18 INCHES
LIQUID TIGHT FLEX. METAL	ARTICLE 350	SHORT LENGTHS (MAX. 3FT.) WIRING TO VIBRATING EQUIPMENT IN WET LOCATIONS.	N/A
FLEX. METAL	ARTICLE 348	SHORT LENGTHS (MAX. 3FT.) WIRING TO VIBRATING EQUIPMENT IN WET LOCATIONS.	N/A

¹ PHYSICAL DAMAGE IS SUBJECT TO THE AUTHORITY HAVING JURISDICTION.
² UNDERGROUND CONDUIT INSTALLED UNDER ROADS, HIGHWAYS, DRIVEWAYS, PARKING LOTS SHALL HAVE MINIMUM DEPTH OF 24".
³ WHERE SOLID ROCK PREVENTS COMPLIANCE WITH MINIMUM COVER DEPTHS, WIRING SHALL BE INSTALLED IN PERMITTED RACEWAY FOR DIRECT BURIAL. THE RACEWAY SHALL BE COVERED BY A MINIMUM OF 2" OF CONCRETE EXTENDING DOWN TO ROCK.

SECTION 16123

- 1.01. CONDUCTORS
- A. ALL CONDUCTORS SHALL BE TYPE THWN (INT. APPLICATION) AND XHHW (EXT. APPLICATION), 75 DEGREE C, 600 VOLT INSULATION, SOFT ANNEALED STRANDED COPPER, #10 AWG AND SMALLER SHALL BE SPLICED USING ACCEPTABLE SOLDERLESS PRESSURE CONNECTORS. #8 AWG AND LARGER SHALL BE SPLICED USING COMPRESSION SPLIT-BOLT TYPE CONNECTORS. #12 AWG SHALL BE THE MINIMUM SIZE CONDUCTOR FOR LINE VOLTAGE BRANCH CIRCUITS. REFER TO PANEL SCHEDULE FOR BRANCH CIRCUIT CONDUCTOR SIZE(S). CONDUCTORS SHALL BE COLOR CODED FOR CONSISTENT PHASE IDENTIFICATION:
- | | | |
|------|------------------|--------------------------|
| LINE | 120/208/240V | 277/480V |
| A | BLACK | BROWN |
| B | RED | ORANGE |
| C | BLUE | YELLOW |
| N | CONTINUOUS WHITE | GREY |
| G | CONTINUOUS GREEN | GREEN WITH YELLOW STRIPE |
- B. MINIMUM BENDING RADIUS FOR CONDUCTORS SHALL BE 12 TIMES THE LARGEST DIAMETER OF BRANCH CIRCUIT CONDUCTOR.

SECTION 16130

- 1.01. BOXES
- A. FURNISH AND INSTALL OUTLET BOXES FOR ALL DEVICES, SWITCHES, RECEPTACLES, ETC.. BOXES TO BE ZINC COATED STEEL.
- B. FURNISH AND INSTALL PULL BOXES IN MAIN FEEDERS RUNS WHERE REQUIRED. PULL BOXES SHALL BE GALVANIZED STEEL WITH SCREW REMOVABLE COVERS, SIZE AND QUANTITY AS REQUIRED. PROVIDE WEATHERPROOF CONSTRUCTION IN WET LOCATIONS.

SECTION 16140

- 1.01. WIRING DEVICES
- A. THE FOLLOWING LIST IS PROVIDED TO CONVEY THE QUALITY AND RATING OF WIRING DEVICES WHICH ARE TO BE INSTALLED. A COMPLETE LIST OF ALL DEVICES MUST BE SUBMITTED BEFORE INSTALLATION FOR APPROVAL.
- 15 MINUTE TIMER SWITCH - INTERMATIC #FF15M (INTERIOR LIGHTS)
 - DUPLEX RECEPTACLE - P&S #2095 (GFCI) SPECIFICATION GRADE
 - SINGLE POLE SWITCH - P&S #CSB20AC2 (20A-120V HARD USE) SPECIFICATION GRADE
 - DUPLEX RECEPTACLE - P&S #5362 (20A-120V HARD USE) SPECIFICATION GRADE
- B. PLATES - ALL PLATES USED SHALL BE CORROSION RESISTANT TYPE 304 STAINLESS STEEL. PLATES SHALL BE FROM SAME MANUFACTURER AS SWITCHES AND RECEPTACLES. PROVIDE WEATHERPROOF HOUSING FOR DEVICES LOCATED IN WET LOCATIONS.
- C. OTHER MANUFACTURERS OF THE SWITCHES, RECEPTACLES AND PLATES MAY BE SUBMITTED FOR APPROVAL BY THE ENGINEER.

SECTION 16170

- 1.01. DISCONNECT SWITCHES
- A. FUSIBLE AND NON-FUSIBLE, 600V, HEAVY DUTY DISCONNECT SWITCHES SHALL BE AS MANUFACTURED BY SQUARE "D". PROVIDE FUSES AS CALLED FOR ON THE CONTRACT DRAWINGS. AMPERE RATING SHALL BE CONSISTENT WITH LOAD BEING SERVED. DISCONNECT SWITCH COVER SHALL BE MECHANICALLY INTERLOCKED TO PREVENT COVER FROM OPENING WHEN THE SWITCH IS IN THE "ON" POSITION. EXTERIOR APPLICATIONS SHALL BE NEMA 3R CONSTRUCTION WITH PADLOCK FEATURE.

SECTION 16190

- 1.01. SEISMIC RESTRAINT
- A. ALL DEVICES SHALL BE INSTALLED IN ACCORDANCE WITH ZONE 2 SEISMIC REQUIREMENTS.

SECTION 16195

- 1.01. LABELING AND IDENTIFICATION NOMENCLATURE FOR ELECTRICAL EQUIPMENT
- A. CONTRACTOR SHALL FURNISH AND INSTALL NON-METALLIC ENGRAVED BACK-LIT NAMEPLATES ON ALL PANELS AND MAJOR ITEMS OF ELECTRICAL EQUIPMENT.
- B. LETTERS TO BE WHITE ON BLACK BACKGROUND WITH LETTERS 1-1/2 INCH HIGH WITH 1/4 INCH MARGIN.
- C. IDENTIFICATION NOMENCLATURE SHALL BE IN ACCORDANCE WITH OWNER'S STANDARDS.

SECTION 16450

- 1.01. GROUNDING
- A. ALL NON-CURRENT CARRYING PARTS OF THE ELECTRICAL AND TELEPHONE CONDUIT SYSTEMS SHALL BE MECHANICALLY AND ELECTRICALLY CONNECTED TO PROVIDE AN INDEPENDENT RETURN PATH TO THE EQUIPMENT GROUNDING SOURCES.
- B. GROUNDING SYSTEM WILL BE IN ACCORDANCE WITH THE LATEST ACCEPTABLE EDITION OF THE NATIONAL ELECTRICAL CODE AND REQUIREMENTS PER LOCAL INSPECTOR HAVING JURISDICTION.

C. GROUNDING OF PANELBOARDS:

- PANELBOARD SHALL BE GROUNDED BY TERMINATING THE PANELBOARD FEEDER'S EQUIPMENT GROUND CONDUCTOR TO THE EQUIPMENT GROUND BAR KIT(S) LUGGED TO THE CABINET. ENSURE THAT THE SURFACE BETWEEN THE KIT AND CABINET ARE BARE METAL TO BARE METAL. PRIME AND PAINT OVER TO PREVENT CORROSION.
 - CONDUIT(S) TERMINATING INTO THE PANELBOARD SHALL HAVE GROUNDING TYPE BUSHINGS. THE BUSHINGS SHALL BE BONDED TOGETHER WITH BARE #10 AWG COPPER CONDUCTOR WHICH IN TURN IS TERMINATED INTO THE PANELBOARD'S EQUIPMENT GROUND BAR KIT(S).
- D. EQUIPMENT GROUNDING CONDUCTOR:
- EACH EQUIPMENT GROUND CONDUCTOR SHALL BE SIZED IN ACCORDANCE WITH THE N.E.C. ARTICLE 250.
 - THE MINIMUM SIZE OF EQUIPMENT GROUND CONDUCTOR SHALL BE #12 AWG COPPER.
 - EACH FEEDER OR BRANCH CIRCUIT SHALL HAVE EQUIPMENT GROUND CONDUCTOR(S) INSTALLED IN THE SAME RACEWAY(S).
- E. CELLULAR GROUNDING SYSTEM:
- CONTRACTOR SHALL PROVIDE A CELLULAR GROUNDING SYSTEM WITH THE MAXIMUM AC RESISTANCE TO GROUND OF 10 OHM BETWEEN ANY POINT ON THE GROUNDING SYSTEM AS MEASURED BY 3-POINT GROUNDING TEST. (REFER TO SECTION 16960).

PROVIDE THE CELLULAR GROUNDING SYSTEM AS SPECIFIED ON DRAWINGS, INCLUDING, BUT NOT LIMITED TO:

- GROUND BARS
 - INTERIOR GROUND RING
 - EXTERIOR GROUNDING (WHERE REQUIRED DUE TO MEASURED AC RESISTANCE GREATER THAN SPECIFIED).
 - ANTENNA GROUND CONNECTIONS AND PLATES.
- F. CONTRACTOR, AFTER COMPLETION OF THE COMPLETE GROUNDING SYSTEM BUT PRIOR TO CONCEALMENT/BURIAL OF SAME, SHALL NOTIFY OWNER'S PROJECT ENGINEER WHO WILL HAVE A DESIGN ENGINEER VISIT SITE AND MAKE A VISUAL INSPECTION OF THE GROUNDING GRID AND CONNECTIONS OF THE SYSTEM.
- G. ALL EQUIPMENT SHALL BE BONDED TO GROUND AS REQUIRED BY N.E.C., MFG. SPECIFICATIONS, AND OWNER'S SPECIFICATIONS.

SECTION 16470

- 1.01. DISTRIBUTION EQUIPMENT
- A. REFER TO CONTRACT DRAWINGS FOR DETAILS AND SCHEDULES.

SECTION 16477

- 1.01. FUSES
- A. FUSES SHALL BE NONRENEWABLE TYPE AS MANUFACTURED BY "BUSSMAN" OR APPROVED EQUAL. FUSES RATED TO 1/10 AMPERE UP TO 600 AMPERES SHALL BE EQUIVALENT TO BUSSMAN TYPE LPN-RK (250V) UL CLASS RK1, LOW PEAK, DUAL ELEMENT, TIME-DELAY FUSES. FUSES SHALL HAVE SEPARATE SHORT CIRCUIT AND OVERLOAD ELEMENTS AND HAVE AN INTERRUPTING RATING OF 200 KAIC. UPON COMPLETION OF WORK, PROVIDE ONE SPARE SET OF FUSES FOR EACH TYPE INSTALLED.

SECTION 16960

- 1.01. TESTS BY INDEPENDENT ELECTRICAL TESTING FIRM
- A. CONTRACTOR SHALL RETAIN THE SERVICES OF A LOCAL INDEPENDENT ELECTRICAL TESTING FIRM (WITH MINIMUM 5 YEARS COMMERCIAL EXPERIENCE IN THE ELECTRICAL TESTING INDUSTRY) AS SPECIFIED BY OWNER TO PERFORM:
- TEST 1: THERMAL OVERLOAD AND MAGNETIC TRIP TEST, AND CABLE INSULATION TEST FOR ALL CIRCUIT BREAKERS RATED 100 AMPS OR GREATER.
- TEST 2: RESISTANCE TO GROUND TEST ON THE CELLULAR GROUNDING SYSTEM.
- THE TESTING FIRM SHALL INCLUDE THE FOLLOWING INFORMATION WITH THE REPORT:
- TESTING PROCEDURE INCLUDING THE MAKE AND MODEL OF TEST EQUIPMENT.
 - CERTIFICATION OF TESTING EQUIPMENT CALIBRATION WITHIN SIX (6) MONTHS OF DATE OF TESTING. INCLUDE CERTIFICATION LAB ADDRESS AND TELEPHONE NUMBER.
 - GRAPHICAL DESCRIPTION OF TESTING METHOD ACTUALLY IMPLEMENTED.
- B. THESE TESTS SHALL BE PERFORMED IN THE PRESENCE AND TO THE SATISFACTION OF OWNER'S CONSTRUCTION REPRESENTATIVE. TESTING DATA SHALL BE INITIALED AND DATED BY THE CONSTRUCTION REPRESENTATIVE AND INCLUDED WITH THE WRITTEN REPORT/ANALYSIS.
- C. THE CONTRACTOR SHALL FORWARD SIX (6) COPIES OF THE INDEPENDENT ELECTRICAL TESTING FIRM'S REPORT/ANALYSIS TO ENGINEER A MINIMUM OF TEN (10) WORKING DAYS PRIOR TO THE JOB TURNOVER.
- D. CONTRACTOR TO PROVIDE A MINIMUM OF ONE (1) WEEK NOTICE TO OWNER AND ENGINEER FOR ALL TESTS REQUIRING WITNESSING.

SECTION 16961

- 1.01. TESTS BY CONTRACTOR
- A. ALL TESTS AS REQUIRED UPON COMPLETION OF WORK, SHALL BE MADE BY THIS CONTRACTOR. THESE SHALL BE CONTINUITY AND INSULATION TESTS; TEST TO DETERMINE THE QUALITY OF MATERIALS, ETC. AND SHALL BE MADE IN ACCORDANCE WITH N.E.C. RECOMMENDATIONS. ALL FEEDERS AND BRANCH CIRCUIT WIRING (EXCEPT CLASS 2 SIGNAL CIRCUITS) MUST BE TESTED FREE FROM SHORT CIRCUIT AND GROUND FAULT CONDITIONS AT 500V IN A REASONABLY DRY AMBIENT OF APPROXIMATELY 70 DEGREES F.
- B. CONTRACTOR SHALL PERFORM LOAD PHASE BALANCING TESTS. CIRCUITS SHALL BE SO CONNECTED TO THE PANELBOARDS SUCH THAT THE NEW LOAD IS DISTRIBUTED AS EQUALLY AS POSSIBLE BETWEEN EACH LOAD AND NEUTRAL. 10% SHALL BE CONSIDERED AS A REASONABLE AND ACCEPTABLE ALLOWANCE. BRANCH CIRCUITS SHALL BE BALANCED ON THEIR OWN PANELBOARDS; FEEDER LOADS SHALL, IN TURN, BE BALANCED ON THE SERVICE EQUIPMENT. REASONABLE LOAD TEST SHALL BE ARRANGED TO VERIFY LOAD BALANCE IF REQUESTED BY THE ENGINEER.
- C. ALL TESTS, UPON REQUEST, SHALL BE REPEATED IN THE PRESENCE OF OWNER'S REPRESENTATIVE. ALL TESTS SHALL BE DOCUMENTED AND TURNED OVER TO OWNER. OWNER SHALL HAVE THE AUTHORITY TO STOP ANY OF THE WORK NOT BEING PROPERLY INSTALLED. ALL SUCH DETECTED WORK SHALL BE REPAIRED OR REPLACED AT NO ADDITIONAL EXPENSE TO THE OWNER AND THE TESTS SHALL BE REPEATED.




5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



CENTEK engineering
Centered on Solutions™

(203) 488-0580
(203) 488-8587 Fax
63-2 North Branford Road
Branford, CT 06405

www.CentekEng.com



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
BSP	TJR	

RFDS REV #: 0 - 08/17/2023

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/05/23	ISSUED FOR CLIENT REVIEW
B	10/17/23	REVISED PER CLIENT COMMENTS
0	12/01/23	ISSUED FOR CONSTRUCTION

CENTEK PROJECT NUMBER
23009.09

DISH Wireless L.L.C.
PROJECT INFORMATION

BOBOS0171A
227 BOOMBRIDGE RD
NORTH STONINGTON CT,
06359

SHEET TITLE
ELECTRICAL
SPECIFICATIONS

SHEET NUMBER

G-4

CEN TEK NOTES AND SPECIFICATIONS:

DESIGN BASIS:

GOVERNING CODE: 2021 INTERNATIONAL BUILDING (IBC) AS MODIFIED BY THE 2022 CONNECTICUT STATE BUILDING CODE.

1. DESIGN CRITERIA:

- RISK CATEGORY II (BASED ON IBC TABLE 1604.5)
- NOMINAL DESIGN SPEED: 105 MPH (Vasd) (EXPOSURE C/ IMPORTANCE FACTOR 1.0 BASED ON ASCE 7-16).

SITE NOTES

1. THE CONTRACTOR SHALL CALL UTILITIES PRIOR TO THE START OF CONSTRUCTION.
2. ACTIVE EXISTING UTILITIES, WHERE ENCOUNTERED IN THE WORK, SHALL BE PROTECTED AT ALL TIMES. THE ENGINEER SHALL BE NOTIFIED IMMEDIATELY, PRIOR TO PROCEEDING, SHOULD ANY UNCOVERED EXISTING UTILITY PRECLUDE COMPLETION OF THE WORK IN ACCORDANCE WITH THE CONTRACT DOCUMENTS.
3. THE AREAS OF THE COMPOUND DISTURBED BY THE WORK SHALL BE RETURNED TO THEIR ORIGINAL CONDITION.
4. CONTRACTOR SHALL MINIMIZE DISTURBANCE TO EXISTING SITE DURING CONSTRUCTION. EROSION CONTROL MEASURES, SHALL BE IN CONFORMANCE WITH THE LOCAL GUIDELINES FOR EROSION AND SEDIMENT CONTROL.
5. IF ANY FIELD CONDITIONS EXIST WHICH PRECLUDE COMPLIANCE WITH THE DRAWINGS, THE CONTRACTOR SHALL IMMEDIATELY NOTIFY THE ENGINEER AND SHALL PROCEED WITH AFFECTED WORK AFTER CONFLICT IS SATISFACTORILY RESOLVED.

GENERAL NOTES

1. ALL WORK SHALL BE IN ACCORDANCE WITH THE 2021 INTERNATIONAL BUILDING CODE AS MODIFIED BY THE 2022 CONNECTICUT SUPPLEMENT, INCLUDING THE TIA/EIA-222 REVISION "H" "STRUCTURAL STANDARDS FOR STEEL ANTENNA TOWERS AND SUPPORTING STRUCTURES." 2022 CONNECTICUT FIRE SAFETY CODE, NATIONAL ELECTRICAL CODE AND LOCAL CODES.
2. SHOULD ANY FIELD CONDITIONS PRECLUDE COMPLIANCE WITH THE DRAWINGS, THE CONTRACTOR SHALL IMMEDIATELY NOTIFY THE ENGINEER AND SHALL NOT PROCEED WITH ANY AFFECTED WORK.
3. CONTRACTOR SHALL REVIEW ALL DRAWINGS AND SPECIFICATIONS IN THE CONTRACT DOCUMENT SET. CONTRACTOR SHALL COORDINATE ALL WORK SHOWN IN THE SET OF DRAWINGS. THE CONTRACTOR SHALL PROVIDE A COMPLETE SET OF DRAWINGS TO ALL SUBCONTRACTORS AND ALL RELATED PARTIES. THE SUBCONTRACTORS SHALL EXAMINE ALL THE DRAWINGS AND SPECIFICATIONS FOR THE INFORMATION THAT AFFECTS THEIR WORK.
4. BEFORE BEGINNING THE WORK, THE CONTRACTOR IS RESPONSIBLE FOR MAKING SUCH INVESTIGATIONS CONCERNING PHYSICAL CONDITIONS (SURFACE AND SUBSURFACE) AT OR CONTIGUOUS TO THE SITE, WHICH MAY AFFECT PERFORMANCE AND COST OF THE WORK.
5. ALL DIMENSIONS, ELEVATIONS, AND OTHER REFERENCES TO EXISTING STRUCTURES, SURFACE, AND SUBSURFACE CONDITIONS ARE APPROXIMATE. NO GUARANTEE IS MADE FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION SHOWN. THE CONTRACTOR SHALL VERIFY AND COORDINATE ALL DIMENSIONS, ELEVATIONS AND ANGLES WITH EXISTING CONDITIONS AND WITH ARCHITECTURAL AND SITE DRAWINGS BEFORE PROCEEDING WITH ANY WORK.
6. AS THE WORK PROGRESSES, THE CONTRACTOR SHALL NOTIFY THE OWNER OF ANY CONDITIONS WHICH ARE IN CONFLICT OR OTHERWISE NOT CONSISTENT WITH THE CONSTRUCTION DOCUMENTS, AND SHALL NOT PROCEED WITH SUCH WORK UNTIL THE CONFLICT IS SATISFACTORILY RESOLVED.
7. CONTRACTOR SHALL PROVIDE A COMPLETE BUILD-OUT WITH ALL FINISHES, STRUCTURAL, MECHANICAL, AND ELECTRICAL COMPONENTS AND PROVIDE ALL ITEMS AS SHOWN OR INDICATED ON THE DRAWINGS OR IN THE WRITTEN SPECIFICATIONS.
8. CONTRACTOR SHALL FURNISH ALL MATERIAL, LABOR AND EQUIPMENT TO COMPLETE THE WORK AND FURNISH A COMPLETED JOB ALL IN ACCORDANCE WITH LOCAL AND STATE GOVERNING AUTHORITIES AND OTHER AUTHORITIES HAVING LAWFUL JURISDICTION OVER THE WORK.
9. CONTRACTOR SHALL SECURE AND PAY FOR ALL PERMITS AND ALL INSPECTIONS REQUIRED AND SHALL ALSO PAY FEES REQUIRED FOR THE GENERAL CONSTRUCTION, PLUMBING, ELECTRICAL, AND HVAC. PERMITS SHALL BE PAID FOR BY THE RESPECTIVE SUBCONTRACTORS.
10. CONTRACTOR SHALL MAINTAIN A CURRENT SET OF DRAWINGS AND SPECIFICATIONS ON SITE AT ALL TIMES AND INSURE DISTRIBUTION OF NEW DRAWINGS TO SUBCONTRACTORS AND OTHER RELEVANT PARTIES AS SOON AS THEY ARE MADE AVAILABLE. ALL OLD DRAWINGS SHALL BE MARKED VOID AND REMOVED FROM THE CONTRACT AREA. THE CONTRACTOR SHALL FURNISH AN 'AS-BUILT' SET OF DRAWINGS TO OWNER UPON COMPLETION OF PROJECT.
11. LOCATION OF EQUIPMENT AND WORK SUPPLIED BY OTHERS THAT IS DIAGRAMMATICALLY INDICATED ON THE DRAWINGS, SHALL BE DETERMINED BY THE CONTRACTOR. THE CONTRACTOR SHALL DETERMINE LOCATIONS AND DIMENSIONS SUBJECT TO STRUCTURAL CONDITIONS AND WORK OF THE SUBCONTRACTORS.
12. THE CONTRACTOR IS SOLELY RESPONSIBLE TO DETERMINE CONSTRUCTION PROCEDURE AND SEQUENCE AND TO ENSURE THE SAFETY OF THE EXISTING STRUCTURES AND ITS COMPONENT PARTS DURING CONSTRUCTION. THIS INCLUDES THE ADDITION OF WHATEVER SHORING, BRACING, UNDERPINNING, ETC. THAT MAY BE NECESSARY.
13. ALL EQUIPMENT AND PRODUCTS PURCHASED ARE TO BE REVIEWED BY CONTRACTOR AND ALL APPLICABLE SUB-CONTRACTORS FOR ANY CONDITION PER THE MANUFACTURER'S RECOMMENDATIONS. CONTRACTOR TO SUPPLY THESE ITEMS AT NO COST TO OWNER OR CONSTRUCTION MANAGER.

14. DRAWINGS INDICATE THE MINIMUM STANDARDS, BUT IF ANY WORK SHOULD BE INDICATED TO BE SUBSTANDARD TO ANY ORDINANCES, LAWS, CODES, RULES, OR REGULATIONS BEARING ON THE WORK, THE CONTRACTOR SHALL INCLUDE IN HIS WORK AND SHALL EXECUTE THE WORK CORRECTLY IN ACCORDANCE WITH SUCH ORDINANCES, LAWS, CODES, RULES OR REGULATIONS WITH NO INCREASE IN COSTS.
15. ALL UTILITY WORK SHALL BE IN ACCORDANCE WITH LOCAL UTILITY COMPANY REQUIREMENTS AND SPECIFICATIONS.
16. ALL EQUIPMENT AND PRODUCTS PURCHASED ARE TO BE REVIEWED BY CONTRACTOR AND ALL APPLICABLE SUBCONTRACTORS FOR ANY CONDITION PER MANUFACTURER'S RECOMMENDATIONS. CONTRACTOR TO SUPPLY THESE ITEMS AT NO COST TO OWNER OR CONSTRUCTION MANAGER.
17. ANY AND ALL ERRORS, DISCREPANCIES, AND 'MISSED' ITEMS ARE TO BE BROUGHT TO THE ATTENTION OF THE DISH Wireless L.L.C. CONSTRUCTION MANAGER DURING THE BIDDING PROCESS BY THE CONTRACTOR. ALL THESE ITEMS ARE TO BE INCLUDED IN THE BID. NO 'EXTRA' WILL BE ALLOWED FOR MISSED ITEMS.
18. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL ON-SITE SAFETY FROM THE TIME THE JOB IS AWARDED UNTIL ALL WORK IS COMPLETE AND ACCEPTED BY THE OWNER.
19. CONTRACTOR TO REVIEW ALL SHOP DRAWINGS AND SUBMIT COPY TO ENGINEER FOR APPROVAL. DRAWINGS MUST BEAR THE CHECKER'S INITIALS BEFORE SUBMITTING TO THE CONSTRUCTION MANAGER FOR REVIEW.
20. THE CONTRACTOR SHALL FIELD VERIFY ALL DIMENSIONS, ELEVATIONS, ANGLES AND EXISTING CONDITIONS AT THE SITE, PRIOR TO FABRICATION AND/OR INSTALLATION OF ANY WORK IN THE CONTRACT AREA.
21. COORDINATION, LAYOUT, FURNISHING AND INSTALLATION OF CONDUITS AND ALL APPURTENANCES REQUIRED FOR PROPER INSTALLATION OF ELECTRICAL AND TELECOMMUNICATION SERVICE SHALL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR AND CONFIRMED WITH THE PROJECT MANAGER AND OWNER PRIOR TO THE COMMENCEMENT OF ANY WORK.
22. ALL DAMAGE CAUSED TO ANY EXISTING STRUCTURE SHALL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR. THE CONTRACTOR WILL BE HELD LIABLE FOR ALL REPAIRS REQUIRED FOR EXISTING STRUCTURES IF DAMAGED DURING CONSTRUCTION ACTIVITIES.
23. THE CONTRACTOR SHALL CONTACT 'CALL BEFORE YOU DIG' AT LEAST 48 HOURS PRIOR TO ANY EXCAVATIONS AT 1-800-922-4455. ALL UTILITIES SHALL BE IDENTIFIED AND CLEARLY MARKED. CONTRACTOR SHALL MAINTAIN AND PROTECT MARKED UTILITIES THROUGHOUT PROJECT COMPLETION.
24. CONTRACTOR SHALL COMPLY WITH THE OWNER'S ENVIRONMENTAL ENGINEER ON ALL METHODS AND PROVISIONS FOR ALL EXCAVATION ACTIVITIES INCLUDING SOIL DISPOSAL. ALL BACKFILL MATERIALS TO BE PROVIDED BY THE CONTRACTOR.
25. THE COUNTY/CITY/TOWN MAY MAKE PERIODIC FIELD INSPECTIONS TO ENSURE COMPLIANCE WITH THE DESIGN PLANS, SPECIFICATIONS, AND CONTRACT DOCUMENTS.
26. THE COUNTY/CITY/TOWN MUST BE NOTIFIED (2) WORKING DAYS PRIOR TO CONCEALMENT/BURIAL OF ANY SYSTEM OR MATERIAL THAT WILL PREVENT THE DIRECT INSPECTION OF MATERIALS, METHODS OR WORKMANSHIP. EXAMPLES OF THESE PROCESSES ARE BACKFILLING A GROUND RING OR TOWER FOUNDATION, POURING TOWER FOUNDATIONS, BURYING GROUND RODS, PLATES OR GRIDS, ETC. THE CONTRACTOR MAY PROCEED WITH THE SCHEDULED PROCESS (2) WORKING DAYS AFTER PROVIDING NOTICE UNLESS NOTIFIED OTHERWISE BY THE COUNTY/CITY/TOWN.
27. PRIOR TO THE SUBMISSION OF BIDS, THE CONTRACTOR SHALL VISIT THE SITE TO FAMILIARIZE WITH THE EXISTING CONDITIONS AND TO CONFIRM THAT THE WORK CAN BE ACCOMPLISHED AS SHOWN ON THE CONSTRUCTION DRAWINGS. ANY DISCREPANCY FOUND SHALL BE BROUGHT TO THE ATTENTION OF ENGINEER ON RECORD, PRIOR TO THE COMMENCEMENT OF ANY WORK.




5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



CEN TEKengineering
Centered on Solutions™

(203) 488-0580
(203) 488-8587 Fax
63-2 North Branford Road
Branford, CT 06405

www.CentekEng.com



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
BSP	TJR	

RFDS REV #: 0 - 08/17/2023

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/05/23	ISSUED FOR CLIENT REVIEW
B	10/17/23	REVISED PER CLIENT COMMENTS
0	12/01/23	ISSUED FOR CONSTRUCTION


CEN TEK PROJECT NUMBER
23009.09

DISH Wireless L.L.C.
PROJECT INFORMATION
BOBOS01171A
227 BOOMBRIDGE RD
NORTH STONINGTON CT,
06359


SHEET TITLE
CEN TEK NOTES/SPECIFICATIONS

SHEET NUMBER
GN-1


EXOTHERMIC CONNECTION
 MECHANICAL CONNECTION
 BUSS BAR INSULATOR
 CHEMICAL ELECTROLYTIC GROUNDING SYSTEM
 TEST CHEMICAL ELECTROLYTIC GROUNDING SYSTEM
 EXOTHERMIC WITH INSPECTION SLEEVE
 GROUNDING BAR
 GROUND ROD
 TEST GROUND ROD WITH INSPECTION SLEEVE
 SINGLE POLE SWITCH
 DUPLEX RECEPTACLE
 DUPLEX GFCI RECEPTACLE
 FLUORESCENT LIGHTING FIXTURE (2) TWO LAMPS 48-T8
 SMOKE DETECTION (DC)
 EMERGENCY LIGHTING (DC)
 SECURITY LIGHT W/PHOTOCELL LITHONIA ALXW
 LED-1-25A400/51K-SR4-120-PE-DDBTXD




CHAIN LINK FENCE
 WOOD/WROUGHT IRON FENCE
 WALL STRUCTURE
 LEASE AREA
 PROPERTY LINE (PL)
 SETBACKS
 ICE BRIDGE
 CABLE TRAY
 WATER LINE
 UNDERGROUND POWER
 UNDERGROUND TELCO
 OVERHEAD POWER
 OVERHEAD TELCO
 UNDERGROUND TELCO/POWER
 ABOVE GROUND POWER
 ABOVE GROUND TELCO
 ABOVE GROUND TELCO/POWER
 WORKPOINT



SECTION REFERENCE



DETAIL REFERENCE



LEGEND

AB ANCHOR BOLT
 ABV ABOVE
 AC ALTERNATING CURRENT
 ADDL ADDITIONAL
 AFF ABOVE FINISHED FLOOR
 AFG ABOVE FINISHED GRADE
 AGL ABOVE GROUND LEVEL
 AIC AMPERAGE INTERRUPTION CAPACITY
 ALUM ALUMINUM
 ALT ALTERNATE
 ANT ANTENNA
 APPROX APPROXIMATE
 ARCH ARCHITECTURAL
 ATS AUTOMATIC TRANSFER SWITCH
 AWG AMERICAN WIRE GAUGE
 BATT BATTERY
 BLDG BUILDING
 BLK BLOCK
 BLKG BLOCKING
 BM BEAM
 BTC BARE TINNED COPPER CONDUCTOR
 BOF BOTTOM OF FOOTING
 CAB CABINET
 CANT CANTILEVERED
 CHG CHARGING
 CLG CEILING
 CLR CLEAR
 COL COLUMN
 COMM COMMON
 CONC CONCRETE
 CONSTR CONSTRUCTION
 DBL DOUBLE
 DC DIRECT CURRENT
 DEPT DEPARTMENT
 DF DOUGLAS FIR
 DIA DIAMETER
 DIAG DIAGONAL
 DIM DIMENSION
 DWG DRAWING
 DWL DOWEL
 EA EACH
 EC ELECTRICAL CONDUCTOR
 EL ELEVATION
 ELEC ELECTRICAL
 EMT ELECTRICAL METALLIC TUBING
 ENG ENGINEER
 EQ EQUAL
 EXP EXPANSION
 EXT EXTERIOR
 EW EACH WAY
 FAB FABRICATION
 FF FINISH FLOOR
 FG FINISH GRADE
 FIF FACILITY INTERFACE FRAME
 FIN FINISH(ED)
 FLR FLOOR
 FDN FOUNDATION
 FOC FACE OF CONCRETE
 FOM FACE OF MASONRY
 FOS FACE OF STUD
 FOW FACE OF WALL
 FS FINISH SURFACE
 FT FOOT
 FTG FOOTING
 GA GAUGE
 GEN GENERATOR
 GFCI GROUND FAULT CIRCUIT INTERRUPTER
 GLB GLUE LAMINATED BEAM
 GLV GALVANIZED
 GPS GLOBAL POSITIONING SYSTEM
 GND GROUND
 GSM GLOBAL SYSTEM FOR MOBILE
 HDG HOT DIPPED GALVANIZED
 HDR HEADER
 HGR HANGER
 HVAC HEAT/VENTILATION/AIR CONDITIONING
 HT HEIGHT
 IGR INTERIOR GROUND RING

IN INCH
 INT INTERIOR
 LB(S) POUND(S)
 LF LINEAR FEET
 LTE LONG TERM EVOLUTION
 MAS MASONRY
 MAX MAXIMUM
 MB MACHINE BOLT
 MECH MECHANICAL
 MFR MANUFACTURER
 MGB MASTER GROUND BAR
 MIN MINIMUM
 MISC MISCELLANEOUS
 MTL METAL
 MTS MANUAL TRANSFER SWITCH
 MW MICROWAVE
 NEC NATIONAL ELECTRIC CODE
 NM NEWTON METERS
 NO. NUMBER
 # NUMBER
 NTS NOT TO SCALE
 OC ON-CENTER
 OSHA OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
 OPNG OPENING
 P/C PRECAST CONCRETE
 PCS PERSONAL COMMUNICATION SERVICES
 PCU PRIMARY CONTROL UNIT
 PRC PRIMARY RADIO CABINET
 PP POLARIZING PRESERVING
 PSF POUNDS PER SQUARE FOOT
 PSI POUNDS PER SQUARE INCH
 PT PRESSURE TREATED
 PWR POWER CABINET
 QTY QUANTITY
 RAD RADIUS
 RECT RECTIFIER
 REF REFERENCE
 REINF REINFORCEMENT
 REQ'D REQUIRED
 RET REMOTE ELECTRIC TILT
 RF RADIO FREQUENCY
 RMC RIGID METALLIC CONDUIT
 RRR REMOTE RADIO HEAD
 RRU REMOTE RADIO UNIT
 RWY RACEWAY
 SCH SCHEDULE
 SHT SHEET
 SIAD SMART INTEGRATED ACCESS DEVICE
 SIM SIMILAR
 SPEC SPECIFICATION
 SQ SQUARE
 SS STAINLESS STEEL
 STD STANDARD
 STL STEEL
 TEMP TEMPORARY
 THK THICKNESS
 TMA TOWER MOUNTED AMPLIFIER
 TN TOE NAIL
 TOA TOP OF ANTENNA
 TOC TOP OF CURB
 TOF TOP OF FOUNDATION
 TOP TOP OF PLATE (PARAPET)
 TOS TOP OF STEEL
 TOW TOP OF WALL
 TVSS TRANSIENT VOLTAGE SURGE SUPPRESSION
 TYP TYPICAL
 UG UNDERGROUND
 UL UNDERWRITERS LABORATORY
 UNO UNLESS NOTED OTHERWISE
 UMS UNIVERSAL MOBILE TELECOMMUNICATIONS SYSTEM
 UPS UNINTERRUPTIBLE POWER SYSTEM (DC POWER PLANT)
 VIF VERIFIED IN FIELD
 W WIDE
 W/ WITH
 WD WOOD
 WP WEATHERPROOF
 WT WEIGHT

ABBREVIATIONS




5701 SOUTH SANTA FE DRIVE
 LITTLETON, CO 80120



CEN TEK engineering
 Centered on Solutions™

(203) 488-0580
 (203) 488-8587 Fax
 63-2 North Branford Road
 Branford, CT 06405

www.CentekEng.com



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
BSP	TJR	

RFDS REV #: 0 - 08/17/2023

CONSTRUCTION DOCUMENTS

SUBMITTALS

REV	DATE	DESCRIPTION
A	10/05/23	ISSUED FOR CLIENT REVIEW
B	10/17/23	REVISED PER CLIENT COMMENTS
0	12/01/23	ISSUED FOR CONSTRUCTION

CEN TEK PROJECT NUMBER
23009.09

DISH Wireless L.L.C.
 PROJECT INFORMATION
BOBOS01171A
227 BOOMBRIDGE RD
NORTH STONINGTON CT,
06359

SHEET TITLE
LEGEND AND ABBREVIATIONS

SHEET NUMBER

GN-1.1

SIGN TYPES		
TYPE	COLOR	COLOR CODE PURPOSE
INFORMATION	GREEN	"INFORMATIONAL SIGN" TO NOTIFY OTHERS OF SITE OWNERSHIP & CONTACT NUMBER AND POTENTIAL RF EXPOSURE.
NOTICE	BLUE	"NOTICE BEYOND THIS POINT" RF FIELDS BEYOND THIS POINT MAY EXCEED THE FCC GENERAL PUBLIC EXPOSURE LIMIT. OBEY ALL POSTED SIGNS AND SITE GUIDELINES FOR WORKING IN RF ENVIRONMENTS. IN ACCORDANCE WITH FEDERAL COMMUNICATIONS COMMISSION RULES ON RADIO FREQUENCY EMISSIONS 47 CFR-1.1307(b)
CAUTION	YELLOW	"CAUTION BEYOND THIS POINT" RF FIELDS BEYOND THIS POINT MAY EXCEED THE FCC GENERAL PUBLIC EXPOSURE LIMIT. OBEY ALL POSTED SIGNS AND SITE GUIDELINES FOR WORKING IN RF ENVIRONMENTS. IN ACCORDANCE WITH FEDERAL COMMUNICATIONS COMMISSION RULES ON RADIO FREQUENCY EMISSIONS 47 CFR-1.1307(b)
WARNING	ORANGE/RED	"WARNING BEYOND THIS POINT" RF FIELDS AT THIS SITE EXCEED FCC RULES FOR HUMAN EXPOSURE. FAILURE TO OBEY ALL POSTED SIGNS AND SITE GUIDELINES FOR WORKING IN RF ENVIRONMENTS COULD RESULT IN SERIOUS INJURY. IN ACCORDANCE WITH FEDERAL COMMUNICATIONS COMMISSION RULES ON RADIO FREQUENCY EMISSIONS 47 CFR-1.1307(b)

SIGN PLACEMENT:

- RF SIGNAGE PLACEMENT SHALL FOLLOW THE RECOMMENDATIONS OF AN EXISTING EME REPORT, CREATED BY A THIRD PARTY PREVIOUSLY AUTHORIZED BY DISH Wireless L.L.C.
- INFORMATION SIGN (GREEN) SHALL BE LOCATED ON EXISTING DISH Wireless L.L.C EQUIPMENT.
A) IF THE INFORMATION SIGN IS A STICKER, IT SHALL BE PLACED ON EXISTING DISH Wireless L.L.C EQUIPMENT CABINET.
B) IF THE INFORMATION SIGN IS A METAL SIGN IT SHALL BE PLACED ON EXISTING DISH Wireless L.L.C H-FRAME WITH A SECURE ATTACH METHOD.
- IF EME REPORT IS NOT AVAILABLE AT THE TIME OF CREATION OF CONSTRUCTION DOCUMENTS; PLEASE CONTACT DISH Wireless L.L.C. CONSTRUCTION MANAGER FOR FURTHER INSTRUCTION ON HOW TO PROCEED.

NOTES:


1. FOR DISH Wireless L.L.C. LOGO, SEE DISH Wireless L.L.C. DESIGN SPECIFICATIONS (PROVIDED BY DISH Wireless L.L.C.)
2. SITE ID SHALL BE APPLIED TO SIGNS USING "LASER ENGRAVING" OR ANY OTHER WEATHER RESISTANT METHOD (DISH Wireless L.L.C. APPROVAL REQUIRED)
3. TEXT FOR SIGNAGE SHALL INDICATE CORRECT SITE NAME AND NUMBER AS PER DISH Wireless L.L.C. CONSTRUCTION MANAGER RECOMMENDATIONS.
4. CABINET/SHELTER MOUNTING APPLICATION REQUIRES ANOTHER PLATE APPLIED TO THE FACE OF THE CABINET WITH WATER PROOF POLYURETHANE ADHESIVE
5. ALL SIGNS WILL BE SECURED WITH EITHER STAINLESS STEEL ZIP TIES OR STAINLESS STEEL TECH SCREWS
6. ALL SIGNS TO BE 8.5"x11" AND MADE WITH 0.04" OF ALUMINUM MATERIAL

INFORMATION

This is an access point to an area with transmitting antennas.

Obey all signs and barriers beyond this point.
Call the DISH Wireless L.L.C. NOC at 1-866-624-6874

Site ID: _____



THIS SIGN IS FOR REFERENCE PURPOSES ONLY

NOTICE

Transmitting Antenna(s)

Radio frequency fields beyond this point MAY EXCEED the FCC Occupational exposure limit.

Obey all posted signs and site guidelines for working in radio frequency environments.

Call the DISH Wireless L.L.C. NOC at 1-866-624-6874 prior to working beyond this point.

Site ID: _____

THIS SIGN IS FOR REFERENCE PURPOSES ONLY

CAUTION

Transmitting Antenna(s)

Radio frequency fields beyond this point MAY EXCEED the FCC Occupational exposure limit.

Obey all posted signs and site guidelines for working in radio frequency environments.

Call the DISH Wireless L.L.C. NOC at 1-866-624-6874 prior to working beyond this point.

Site ID: _____

THIS SIGN IS FOR REFERENCE PURPOSES ONLY

WARNING

Transmitting Antenna(s)

Radio frequency fields beyond this point EXCEED the FCC Occupational exposure limit.

Obey all posted signs and site guidelines for working in radio frequency environments.

Call the DISH Wireless L.L.C. NOC at 1-866-624-6874 prior to working beyond this point.

Site ID: _____

THIS SIGN IS FOR REFERENCE PURPOSES ONLY



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



CENTEKengineering
Centered on Solutions™

(203) 488-0580
(203) 488-8587 Fax
63-2 North Branford Road
Branford, CT 06405

www.CentekEng.com



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
BSP	TJR	

RFDS REV #: 0 - 08/17/2023

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/05/23	ISSUED FOR CLIENT REVIEW
B	10/17/23	REVISED PER CLIENT COMMENTS
0	12/01/23	ISSUED FOR CONSTRUCTION

CENTEK PROJECT NUMBER
23009.09

DISH Wireless L.L.C.
PROJECT INFORMATION

BOBOS0171A
227 BOOMBRIDGE RD
NORTH STONINGTON CT,
06359

SHEET TITLE
DISH RF SIGNAGE

SHEET NUMBER
GN-1.2

SITE ACTIVITY REQUIREMENTS:

1. NOTICE TO PROCEED – NO WORK SHALL COMMENCE PRIOR TO CONTRACTOR RECEIVING A WRITTEN NOTICE TO PROCEED (NTP) AND THE ISSUANCE OF A PURCHASE ORDER. PRIOR TO ACCESSING/ENTERING THE SITE YOU MUST CONTACT THE DISH Wireless L.L.C. AND TOWER OWNER NOC & THE DISH Wireless L.L.C. AND TOWER OWNER CONSTRUCTION MANAGER.
2. "LOOK UP" – DISH Wireless L.L.C. AND TOWER OWNER SAFETY CLIMB REQUIREMENT:
THE INTEGRITY OF THE SAFETY CLIMB AND ALL COMPONENTS OF THE CLIMBING FACILITY SHALL BE CONSIDERED DURING ALL STAGES OF DESIGN, INSTALLATION, AND INSPECTION. TOWER MODIFICATION, MOUNT REINFORCEMENTS, AND/OR EQUIPMENT INSTALLATIONS SHALL NOT COMPROMISE THE INTEGRITY OR FUNCTIONAL USE OF THE SAFETY CLIMB OR ANY COMPONENTS OF THE CLIMBING FACILITY ON THE STRUCTURE. THIS SHALL INCLUDE, BUT NOT BE LIMITED TO: PINCHING OF THE WIRE ROPE, BENDING OF THE WIRE ROPE FROM ITS SUPPORTS, DIRECT CONTACT OR CLOSE PROXIMITY TO THE WIRE ROPE WHICH MAY CAUSE FRICTIONAL WEAR, IMPACT TO THE ANCHORAGE POINTS IN ANY WAY, OR TO IMPEDE/BLOCK ITS INTENDED USE. ANY COMPROMISED SAFETY CLIMB, INCLUDING EXISTING CONDITIONS MUST BE TAGGED OUT AND REPORTED TO YOUR DISH Wireless L.L.C. AND DISH Wireless L.L.C. AND TOWER OWNER POC OR CALL THE NOC TO GENERATE A SAFETY CLIMB MAINTENANCE AND CONTRACTOR NOTICE TICKET.
3. PRIOR TO THE START OF CONSTRUCTION, ALL REQUIRED JURISDICTIONAL PERMITS SHALL BE OBTAINED. THIS INCLUDES, BUT IS NOT LIMITED TO, BUILDING, ELECTRICAL, MECHANICAL, FIRE, FLOOD ZONE, ENVIRONMENTAL, AND ZONING. AFTER ONSITE ACTIVITIES AND CONSTRUCTION ARE COMPLETED, ALL REQUIRED PERMITS SHALL BE SATISFIED AND CLOSED OUT ACCORDING TO LOCAL JURISDICTIONAL REQUIREMENTS.
4. ALL CONSTRUCTION MEANS AND METHODS; INCLUDING BUT NOT LIMITED TO, ERECTION PLANS, RIGGING PLANS, CLIMBING PLANS, AND RESCUE PLANS SHALL BE THE RESPONSIBILITY OF THE GENERAL CONTRACTOR RESPONSIBLE FOR THE EXECUTION OF THE WORK CONTAINED HEREIN, AND SHALL MEET ANSI/ASSE A10.48 (LATEST EDITION); FEDERAL, STATE, AND LOCAL REGULATIONS; AND ANY APPLICABLE INDUSTRY CONSENSUS STANDARDS RELATED TO THE CONSTRUCTION ACTIVITIES BEING PERFORMED. ALL RIGGING PLANS SHALL ADHERE TO ANSI/ASSE A10.48 (LATEST EDITION) AND DISH Wireless L.L.C. AND TOWER OWNER STANDARDS, INCLUDING THE REQUIRED INVOLVEMENT OF A QUALIFIED ENGINEER FOR CLASS IV CONSTRUCTION, TO CERTIFY THE SUPPORTING STRUCTURE(S) IN ACCORDANCE WITH ANSI/TIA-322 (LATEST EDITION).
5. ALL SITE WORK TO COMPLY WITH DISH Wireless L.L.C. AND TOWER OWNER INSTALLATION STANDARDS FOR CONSTRUCTION ACTIVITIES ON DISH Wireless L.L.C. AND TOWER OWNER TOWER SITE AND LATEST VERSION OF ANSI/TIA-1019-A-2012 "STANDARD FOR INSTALLATION, ALTERATION, AND MAINTENANCE OF ANTENNA SUPPORTING STRUCTURES AND ANTENNAS."
6. IF THE SPECIFIED EQUIPMENT CAN NOT BE INSTALLED AS SHOWN ON THESE DRAWINGS, THE CONTRACTOR SHALL PROPOSE AN ALTERNATIVE INSTALLATION FOR APPROVAL BY DISH Wireless L.L.C. AND TOWER OWNER PRIOR TO PROCEEDING WITH ANY SUCH CHANGE OF INSTALLATION.
7. ALL MATERIALS FURNISHED AND INSTALLED SHALL BE IN STRICT ACCORDANCE WITH ALL APPLICABLE CODES, REGULATIONS AND ORDINANCES. CONTRACTOR SHALL ISSUE ALL APPROPRIATE NOTICES AND COMPLY WITH ALL LAWS, ORDINANCES, RULES, REGULATIONS AND LAWFUL ORDERS OF ANY PUBLIC AUTHORITY REGARDING THE PERFORMANCE OF THE WORK. ALL WORK CARRIED OUT SHALL COMPLY WITH ALL APPLICABLE MUNICIPAL AND UTILITY COMPANY SPECIFICATIONS AND LOCAL JURISDICTIONAL CODES, ORDINANCES AND APPLICABLE REGULATIONS.
8. THE CONTRACTOR SHALL INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS UNLESS SPECIFICALLY STATED OTHERWISE.
9. THE CONTRACTOR SHALL CONTACT UTILITY LOCATING SERVICES INCLUDING PRIVATE LOCATES SERVICES PRIOR TO THE START OF CONSTRUCTION.
10. ALL EXISTING ACTIVE SEWER, WATER, GAS, ELECTRIC AND OTHER UTILITIES WHERE ENCOUNTERED IN THE WORK, SHALL BE PROTECTED AT ALL TIMES AND WHERE REQUIRED FOR THE PROPER EXECUTION OF THE WORK, SHALL BE RELOCATED AS DIRECTED BY CONTRACTOR. EXTREME CAUTION SHOULD BE USED BY THE CONTRACTOR WHEN EXCAVATING OR DRILLING PIERS AROUND OR NEAR UTILITIES. CONTRACTOR SHALL PROVIDE SAFETY TRAINING FOR THE WORKING CREW. THIS WILL INCLUDE BUT NOT BE LIMITED TO A) FALL PROTECTION B) CONFINED SPACE C) ELECTRICAL SAFETY D) TRENCHING AND EXCAVATION E) CONSTRUCTION SAFETY PROCEDURES.
11. ALL SITE WORK SHALL BE AS INDICATED ON THE STAMPED CONSTRUCTION DRAWINGS AND DISH PROJECT SPECIFICATIONS, LATEST APPROVED REVISION.
12. CONTRACTOR SHALL KEEP THE SITE FREE FROM ACCUMULATING WASTE MATERIAL, DEBRIS, AND TRASH AT THE COMPLETION OF THE WORK. IF NECESSARY, RUBBISH, STUMPS, DEBRIS, STICKS, STONES AND OTHER REFUSE SHALL BE REMOVED FROM THE SITE AND DISPOSED OF LEGALLY.
13. ALL EXISTING INACTIVE SEWER, WATER, GAS, ELECTRIC AND OTHER UTILITIES, WHICH INTERFERE WITH THE EXECUTION OF THE WORK, SHALL BE REMOVED AND/OR CAPPED, PLUGGED OR OTHERWISE DISCONTINUED AT POINTS WHICH WILL NOT INTERFERE WITH THE EXECUTION OF THE WORK, SUBJECT TO THE APPROVAL OF DISH Wireless L.L.C. AND TOWER OWNER, AND/OR LOCAL UTILITIES.
14. THE CONTRACTOR SHALL PROVIDE SITE SIGNAGE IN ACCORDANCE WITH THE TECHNICAL SPECIFICATION FOR SITE SIGNAGE REQUIRED BY LOCAL JURISDICTION AND SIGNAGE REQUIRED ON INDIVIDUAL PIECES OF EQUIPMENT, ROOMS, AND SHELTERS.
15. THE SITE SHALL BE GRADED TO CAUSE SURFACE WATER TO FLOW AWAY FROM THE CARRIER'S EQUIPMENT AND TOWER AREAS.
16. THE SUB GRADE SHALL BE COMPACTED AND BROUGHT TO A SMOOTH UNIFORM GRADE PRIOR TO FINISHED SURFACE APPLICATION.
17. THE AREAS OF THE OWNERS PROPERTY DISTURBED BY THE WORK AND NOT COVERED BY THE TOWER, EQUIPMENT OR DRIVEWAY, SHALL BE GRADED TO A UNIFORM SLOPE, AND STABILIZED TO PREVENT EROSION AS SPECIFIED ON THE CONSTRUCTION DRAWINGS AND/OR PROJECT SPECIFICATIONS.
18. CONTRACTOR SHALL MINIMIZE DISTURBANCE TO EXISTING SITE DURING CONSTRUCTION. EROSION CONTROL MEASURES, IF REQUIRED DURING CONSTRUCTION, SHALL BE IN CONFORMANCE WITH THE LOCAL GUIDELINES FOR EROSION AND SEDIMENT CONTROL.
19. THE CONTRACTOR SHALL PROTECT EXISTING IMPROVEMENTS, PAVEMENTS, CURBS, LANDSCAPING AND STRUCTURES. ANY DAMAGED PART SHALL BE REPAIRED AT CONTRACTOR'S EXPENSE TO THE SATISFACTION OF OWNER.
20. CONTRACTOR SHALL LEGALLY AND PROPERLY DISPOSE OF ALL SCRAP MATERIALS SUCH AS COAXIAL CABLES AND OTHER ITEMS REMOVED FROM THE EXISTING FACILITY. ANTENNAS AND RADIOS REMOVED SHALL BE RETURNED TO THE OWNER'S DESIGNATED LOCATION.
21. CONTRACTOR SHALL LEAVE PREMISES IN CLEAN CONDITION. TRASH AND DEBRIS SHOULD BE REMOVED FROM SITE ON A DAILY BASIS.
22. NO FILL OR EMBANKMENT MATERIAL SHALL BE PLACED ON FROZEN GROUND. FROZEN MATERIALS, SNOW OR ICE SHALL NOT BE PLACED IN ANY FILL OR EMBANKMENT.

GENERAL NOTES:

1. FOR THE PURPOSE OF CONSTRUCTION DRAWING, THE FOLLOWING DEFINITIONS SHALL APPLY:
CONTRACTOR: GENERAL CONTRACTOR RESPONSIBLE FOR CONSTRUCTION
CARRIER: DISH Wireless L.L.C.
TOWER OWNER: TOWER OWNER
2. THESE DRAWINGS HAVE BEEN PREPARED USING STANDARDS OF PROFESSIONAL CARE AND COMPLETENESS NORMALLY EXERCISED UNDER SIMILAR CIRCUMSTANCES BY REPUTABLE ENGINEERS IN THIS OR SIMILAR LOCALITIES. IT IS ASSUMED THAT THE WORK DEPICTED WILL BE PERFORMED BY AN EXPERIENCED CONTRACTOR AND/OR WORKPEOPLE WHO HAVE A WORKING KNOWLEDGE OF THE APPLICABLE CODE STANDARDS AND REQUIREMENTS AND OF INDUSTRY ACCEPTED STANDARD GOOD PRACTICE. AS NOT EVERY CONDITION OR ELEMENT IS (OR CAN BE) EXPLICITLY SHOWN ON THESE DRAWINGS, THE CONTRACTOR SHALL USE INDUSTRY ACCEPTED STANDARD GOOD PRACTICE FOR MISCELLANEOUS WORK NOT EXPLICITLY SHOWN.
3. THESE DRAWINGS REPRESENT THE FINISHED STRUCTURE. THEY DO NOT INDICATE THE MEANS OR METHODS OF CONSTRUCTION. THE CONTRACTOR SHALL BE SOLELY RESPONSIBLE FOR THE CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES, AND PROCEDURES. THE CONTRACTOR SHALL PROVIDE ALL MEASURES NECESSARY FOR PROTECTION OF LIFE AND PROPERTY DURING CONSTRUCTION. SUCH MEASURES SHALL INCLUDE, BUT NOT BE LIMITED TO, BRACING, FORMWORK, SHORING, ETC. SITE VISITS BY THE ENGINEER OR HIS REPRESENTATIVE WILL NOT INCLUDE INSPECTION OF THESE ITEMS AND IS FOR STRUCTURAL OBSERVATION OF THE FINISHED STRUCTURE ONLY.
4. NOTES AND DETAILS IN THE CONSTRUCTION DRAWINGS SHALL TAKE PRECEDENCE OVER GENERAL NOTES AND TYPICAL DETAILS. WHERE NO DETAILS ARE SHOWN, CONSTRUCTION SHALL CONFORM TO SIMILAR WORK ON THE PROJECT, AND/OR AS PROVIDED FOR IN THE CONTRACT DOCUMENTS. WHERE DISCREPANCIES OCCUR BETWEEN PLANS, DETAILS, GENERAL NOTES, AND SPECIFICATIONS, THE GREATER, MORE STRICT REQUIREMENTS, SHALL GOVERN. IF FURTHER CLARIFICATION IS REQUIRED CONTACT THE ENGINEER OF RECORD.
5. SUBSTANTIAL EFFORT HAS BEEN MADE TO PROVIDE ACCURATE DIMENSIONS AND MEASUREMENTS ON THE DRAWINGS TO ASSIST IN THE FABRICATION AND/OR PLACEMENT OF CONSTRUCTION ELEMENTS BUT IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO FIELD VERIFY THE DIMENSIONS, MEASUREMENTS, AND/OR CLEARANCES SHOWN IN THE CONSTRUCTION DRAWINGS PRIOR TO FABRICATION OR CUTTING OF ANY NEW OR EXISTING CONSTRUCTION ELEMENTS. IF IT IS DETERMINED THAT THERE ARE DISCREPANCIES AND/OR CONFLICTS WITH THE CONSTRUCTION DRAWINGS THE ENGINEER OF RECORD IS TO BE NOTIFIED AS SOON AS POSSIBLE.
6. PRIOR TO THE SUBMISSION OF BIDS, THE BIDDING CONTRACTOR SHALL VISIT THE CELL SITE TO FAMILIARIZE WITH THE EXISTING CONDITIONS AND TO CONFIRM THAT THE WORK CAN BE ACCOMPLISHED AS SHOWN ON THE CONSTRUCTION DRAWINGS. ANY DISCREPANCY FOUND SHALL BE BROUGHT TO THE ATTENTION OF CARRIER POC AND TOWER OWNER.
7. ALL MATERIALS FURNISHED AND INSTALLED SHALL BE IN STRICT ACCORDANCE WITH ALL APPLICABLE CODES, REGULATIONS AND ORDINANCES. CONTRACTOR SHALL ISSUE ALL APPROPRIATE NOTICES AND COMPLY WITH ALL LAWS, ORDINANCES, RULES, REGULATIONS AND LAWFUL ORDERS OF ANY PUBLIC AUTHORITY REGARDING THE PERFORMANCE OF THE WORK. ALL WORK CARRIED OUT SHALL COMPLY WITH ALL APPLICABLE MUNICIPAL AND UTILITY COMPANY SPECIFICATIONS AND LOCAL JURISDICTIONAL CODES, ORDINANCES AND APPLICABLE REGULATIONS.
8. UNLESS NOTED OTHERWISE, THE WORK SHALL INCLUDE FURNISHING MATERIALS, EQUIPMENT, APPURTENANCES AND LABOR NECESSARY TO COMPLETE ALL INSTALLATIONS AS INDICATED ON THE DRAWINGS.
9. THE CONTRACTOR SHALL INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS UNLESS SPECIFICALLY STATED OTHERWISE.
10. IF THE SPECIFIED EQUIPMENT CAN NOT BE INSTALLED AS SHOWN ON THESE DRAWINGS, THE CONTRACTOR SHALL PROPOSE AN ALTERNATIVE INSTALLATION FOR APPROVAL BY THE CARRIER AND TOWER OWNER PRIOR TO PROCEEDING WITH ANY SUCH CHANGE OF INSTALLATION.
11. CONTRACTOR IS TO PERFORM A SITE INVESTIGATION, BEFORE SUBMITTING BIDS, TO DETERMINE THE BEST ROUTING OF ALL CONDUITS FOR POWER, AND TELCO AND FOR GROUNDING CABLES AS SHOWN IN THE POWER, TELCO, AND GROUNDING PLAN DRAWINGS.
12. THE CONTRACTOR SHALL PROTECT EXISTING IMPROVEMENTS, PAVEMENTS, CURBS, LANDSCAPING AND STRUCTURES. ANY DAMAGED PART SHALL BE REPAIRED AT CONTRACTOR'S EXPENSE TO THE SATISFACTION OF DISH Wireless L.L.C. AND TOWER OWNER
13. CONTRACTOR SHALL LEGALLY AND PROPERLY DISPOSE OF ALL SCRAP MATERIALS SUCH AS COAXIAL CABLES AND OTHER ITEMS REMOVED FROM THE EXISTING FACILITY. ANTENNAS REMOVED SHALL BE RETURNED TO THE OWNER'S DESIGNATED LOCATION.
14. CONTRACTOR SHALL LEAVE PREMISES IN CLEAN CONDITION. TRASH AND DEBRIS SHOULD BE REMOVED FROM SITE ON A DAILY BASIS.




5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



CENTEK engineering
Centered on Solutions™

(203) 488-0580
(203) 488-8587 Fax
63-2 North Branford Road
Branford, CT 06405

www.CentekEng.com



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
BSP	TJR	

RFDS REV #: 0 - 08/17/2023

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/05/23	ISSUED FOR CLIENT REVIEW
B	10/17/23	REVISED PER CLIENT COMMENTS
0	12/01/23	ISSUED FOR CONSTRUCTION

CENTEK PROJECT NUMBER
23009.09

DISH Wireless L.L.C.
PROJECT INFORMATION
BOBOS0171A
227 BOOMBRIDGE RD
NORTH STONINGTON CT,
06359

SHEET TITLE
DISH GENERAL NOTES

SHEET NUMBER
GN-1.3

CONCRETE, FOUNDATIONS, AND REINFORCING STEEL:

1. ALL CONCRETE WORK SHALL BE IN ACCORDANCE WITH THE ACI 301, ACI 318, ACI 336, ASTM A184, ASTM A185 AND THE DESIGN AND CONSTRUCTION SPECIFICATION FOR CAST-IN-PLACE CONCRETE.
2. UNLESS NOTED OTHERWISE, SOIL BEARING PRESSURE USED FOR DESIGN OF SLABS AND FOUNDATIONS IS ASSUMED TO BE 1000 psf.
3. ALL CONCRETE SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH (f'c) OF 3000 psi AT 28 DAYS, UNLESS NOTED OTHERWISE. NO MORE THAN 90 MINUTES SHALL ELAPSE FROM BATCH TIME TO TIME OF PLACEMENT UNLESS APPROVED BY THE ENGINEER OF RECORD. TEMPERATURE OF CONCRETE SHALL NOT EXCEED 90°F AT TIME OF PLACEMENT.
4. CONCRETE EXPOSED TO FREEZE-THAW CYCLES SHALL CONTAIN AIR ENTRAINING ADMIXTURES. AMOUNT OF AIR ENTRAINMENT TO BE BASED ON SIZE OF AGGREGATE AND F3 CLASS EXPOSURE (VERY SEVERE). CEMENT USED TO BE TYPE II PORTLAND CEMENT WITH A MAXIMUM WATER-TO-CEMENT RATIO (W/C) OF 0.45.
5. ALL STEEL REINFORCING SHALL CONFORM TO ASTM A615. ALL WELDED WIRE FABRIC (WWF) SHALL CONFORM TO ASTM A185. ALL SPLICES SHALL BE CLASS "B" TENSION SPLICES, UNLESS NOTED OTHERWISE. ALL HOOKS SHALL BE STANDARD 90 DEGREE HOOKS, UNLESS NOTED OTHERWISE. YIELD STRENGTH (Fy) OF STANDARD DEFORMED BARS ARE AS FOLLOWS:

#4 BARS AND SMALLER 40 ksi

#5 BARS AND LARGER 60 ksi

6. THE FOLLOWING MINIMUM CONCRETE COVER SHALL BE PROVIDED FOR REINFORCING STEEL UNLESS SHOWN OTHERWISE ON DRAWINGS:

- CONCRETE CAST AGAINST AND PERMANENTLY EXPOSED TO EARTH 3"
- CONCRETE EXPOSED TO EARTH OR WEATHER:
 - #6 BARS AND LARGER 2"
 - #5 BARS AND SMALLER 1-1/2"
- CONCRETE NOT EXPOSED TO EARTH OR WEATHER:
 - SLAB AND WALLS 3/4"
 - BEAMS AND COLUMNS 1-1/2"

7. A TOOLED EDGE OR A 3/4" CHAMFER SHALL BE PROVIDED AT ALL EXPOSED EDGES OF CONCRETE, UNLESS NOTED OTHERWISE, IN ACCORDANCE WITH ACI 301 SECTION 4.2.4.

ELECTRICAL INSTALLATION NOTES:

1. ALL ELECTRICAL WORK SHALL BE PERFORMED IN ACCORDANCE WITH THE PROJECT SPECIFICATIONS, NEC AND ALL APPLICABLE FEDERAL, STATE, AND LOCAL CODES/ORDINANCES.
2. CONDUIT ROUTINGS ARE SCHEMATIC. CONTRACTOR SHALL INSTALL CONDUITS SO THAT ACCESS TO EQUIPMENT IS NOT BLOCKED AND TRIP HAZARDS ARE ELIMINATED.
3. WIRING, RACEWAY AND SUPPORT METHODS AND MATERIALS SHALL COMPLY WITH THE REQUIREMENTS OF THE NEC.
4. ALL CIRCUITS SHALL BE SEGREGATED AND MAINTAIN MINIMUM CABLE SEPARATION AS REQUIRED BY THE NEC.
- 4.1. ALL EQUIPMENT SHALL BEAR THE UNDERWRITERS LABORATORIES LABEL OF APPROVAL, AND SHALL CONFORM TO REQUIREMENT OF THE NATIONAL ELECTRICAL CODE.
- 4.2. ALL OVERCURRENT DEVICES SHALL HAVE AN INTERRUPTING CURRENT RATING THAT SHALL BE GREATER THAN THE SHORT CIRCUIT CURRENT TO WHICH THEY ARE SUBJECTED, 22,000 AIC MINIMUM. VERIFY AVAILABLE SHORT CIRCUIT CURRENT DOES NOT EXCEED THE RATING OF ELECTRICAL EQUIPMENT IN ACCORDANCE WITH ARTICLE 110.24 NEC OR THE MOST CURRENT ADOPTED CODE PRE THE GOVERNING JURISDICTION.
5. EACH END OF EVERY POWER PHASE CONDUCTOR, GROUNDING CONDUCTOR, AND TELCO CONDUCTOR OR CABLE SHALL BE LABELED WITH COLOR-CODED INSULATION OR ELECTRICAL TAPE (3M BRAND, 1/2" PLASTIC ELECTRICAL TAPE WITH UV PROTECTION, OR EQUAL). THE IDENTIFICATION METHOD SHALL CONFORM WITH NEC AND OSHA.
6. ALL ELECTRICAL COMPONENTS SHALL BE CLEARLY LABELED WITH LAMICOID TAGS SHOWING THEIR RATED VOLTAGE, PHASE CONFIGURATION, WIRE CONFIGURATION, POWER OR AMPACITY RATING AND BRANCH CIRCUIT ID NUMBERS (i.e. PANEL BOARD AND CIRCUIT ID'S).
7. PANEL BOARDS (ID NUMBERS) SHALL BE CLEARLY LABELED WITH PLASTIC LABELS.
8. TIE WRAPS ARE NOT ALLOWED.
9. ALL POWER AND EQUIPMENT GROUND WIRING IN TUBING OR CONDUIT SHALL BE SINGLE COPPER CONDUCTOR (#14 OR LARGER) WITH TYPE THHW, THWN, THWN-2, XHHW, XHHW-2, THW, THW-2, RHW, OR RHW-2 INSULATION UNLESS OTHERWISE SPECIFIED.
10. SUPPLEMENTAL EQUIPMENT GROUND WIRING LOCATED INDOORS SHALL BE SINGLE COPPER CONDUCTOR (#6 OR LARGER) WITH TYPE THHW, THWN, THWN-2, XHHW, XHHW-2, THW, THW-2, RHW, OR RHW-2 INSULATION UNLESS OTHERWISE SPECIFIED.
11. POWER AND CONTROL WIRING IN FLEXIBLE CORD SHALL BE MULTI-CONDUCTOR, TYPE SOOW CORD (#14 OR LARGER) UNLESS OTHERWISE SPECIFIED.
12. POWER AND CONTROL WIRING FOR USE IN CABLE TRAY SHALL BE MULTI-CONDUCTOR, TYPE TC CABLE (#14 OR LARGER), WITH TYPE THHW, THWN, THWN-2, XHHW, XHHW-2, THW, THW-2, RHW, OR RHW-2 INSULATION UNLESS OTHERWISE SPECIFIED.
13. ALL POWER AND GROUNDING CONNECTIONS SHALL BE CRIMP-STYLE, COMPRESSION WIRE LUGS AND WIRE NUTS BY THOMAS AND BETTS (OR EQUAL). LUGS AND WIRE NUTS SHALL BE RATED FOR OPERATION NOT LESS THAN 75° C (90° C IF AVAILABLE).
14. RACEWAY AND CABLE TRAY SHALL BE LISTED OR LABELED FOR ELECTRICAL USE IN ACCORDANCE WITH NEMA, UL, ANSI/IEEE AND NEC.
15. ELECTRICAL METALLIC TUBING (EMT), INTERMEDIATE METAL CONDUIT (IMC), OR RIGID METAL CONDUIT (RMC) SHALL BE USED FOR EXPOSED INDOOR LOCATIONS.
16. ELECTRICAL METALLIC TUBING (EMT) OR METAL-CLAD CABLE (MC) SHALL BE USED FOR CONCEALED INDOOR LOCATIONS.
17. SCHEDULE 40 PVC UNDERGROUND ON STRAIGHTS AND SCHEDULE 80 PVC FOR ALL ELBOWS/90s AND ALL APPROVED ABOVE GRADE PVC CONDUIT.
18. LIQUID-TIGHT FLEXIBLE METALLIC CONDUIT (LIQUID-TITE FLEX) SHALL BE USED INDOORS AND OUTDOORS, WHERE VIBRATION OCCURS OR FLEXIBILITY IS NEEDED.
19. CONDUIT AND TUBING FITTINGS SHALL BE THREADED OR COMPRESSION-TYPE AND APPROVED FOR THE LOCATION USED. SET SCREW FITTINGS ARE NOT ACCEPTABLE.
20. CABINETS, BOXES AND WIRE WAYS SHALL BE LABELED FOR ELECTRICAL USE IN ACCORDANCE WITH NEMA, UL, ANSI/IEEE AND THE NEC.
21. WIREWAYS SHALL BE METAL WITH AN ENAMEL FINISH AND INCLUDE A HINGED COVER, DESIGNED TO SWING OPEN DOWNWARDS (WIREMOLD SPECIMATE WIREWAY).
22. SLOTTED WIRING DUCT SHALL BE PVC AND INCLUDE COVER (PANDUIT TYPE E OR EQUAL).
23. CONDUITS SHALL BE FASTENED SECURELY IN PLACE WITH APPROVED NON-PERFORATED STRAPS AND HANGERS. EXPLOSIVE DEVICES (i.e. POWDER-ACTUATED) FOR ATTACHING HANGERS TO STRUCTURE WILL NOT BE PERMITTED. CLOSELY FOLLOW THE LINES OF THE STRUCTURE, MAINTAIN CLOSE PROXIMITY TO THE STRUCTURE AND KEEP CONDUITS IN TIGHT ENVELOPES. CHANGES IN DIRECTION TO ROUTE AROUND OBSTACLES SHALL BE MADE WITH CONDUIT OUTLET BODIES. CONDUIT SHALL BE INSTALLED IN A NEAT AND WORKMANLIKE MANNER. PARALLEL AND PERPENDICULAR TO STRUCTURE WALL AND CEILING LINES. ALL CONDUIT SHALL BE FISHED TO CLEAR OBSTRUCTIONS. ENDS OF CONDUITS SHALL BE TEMPORARILY CAPPED FLUSH TO FINISH GRADE TO PREVENT CONCRETE, PLASTER OR DIRT FROM ENTERING. CONDUITS SHALL BE RIGIDLY CLAMPED TO BOXES BY GALVANIZED MALLEABLE IRON BUSHING ON INSIDE AND GALVANIZED MALLEABLE IRON LOCKNUT ON OUTSIDE AND INSIDE.
24. EQUIPMENT CABINETS, TERMINAL BOXES, JUNCTION BOXES AND PULL BOXES SHALL BE GALVANIZED OR EPOXY-COATED SHEET STEEL. SHALL MEET OR EXCEED UL 50 AND BE RATED NEMA 1 (OR BETTER) FOR INTERIOR LOCATIONS AND NEMA 3 (OR BETTER) FOR EXTERIOR LOCATIONS.
25. METAL RECEPTACLE, SWITCH AND DEVICE BOXES SHALL BE GALVANIZED, EPOXY-COATED OR NON-CORRODING; SHALL MEET OR EXCEED UL 514A AND NEMA OS 1 AND BE RATED NEMA 1 (OR BETTER) FOR INTERIOR LOCATIONS AND WEATHER PROTECTED (WP OR BETTER) FOR EXTERIOR LOCATIONS.
26. NONMETALLIC RECEPTACLE, SWITCH AND DEVICE BOXES SHALL MEET OR EXCEED NEMA OS 2 (NEWEST REVISION) AND BE RATED NEMA 1 (OR BETTER) FOR INTERIOR LOCATIONS AND WEATHER PROTECTED (WP OR BETTER) FOR EXTERIOR LOCATIONS.
27. THE CONTRACTOR SHALL NOTIFY AND OBTAIN NECESSARY AUTHORIZATION FROM THE CARRIER AND/OR DISH Wireless L.L.C. AND TOWER OWNER BEFORE COMMENCING WORK ON THE AC POWER DISTRIBUTION PANELS.
28. THE CONTRACTOR SHALL PROVIDE NECESSARY TAGGING ON THE BREAKERS, CABLES AND DISTRIBUTION PANELS IN ACCORDANCE WITH THE APPLICABLE CODES AND STANDARDS TO SAFEGUARD LIFE AND PROPERTY.
29. INSTALL LAMICOID LABEL ON THE METER CENTER TO SHOW "DISH Wireless L.L.C."
30. ALL EMPTY/SPARE CONDUITS THAT ARE INSTALLED ARE TO HAVE A METERED MULE TAPE PULL CORD INSTALLED.




5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



CEN TEK engineering
Centered on Solutions™

(203) 488-0580
(203) 488-8587 Fax
63-2 North Branford Road
Branford, CT 06405

www.CentekEng.com



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
BSP	TJR	

RFDS REV #: 0 - 08/17/2023

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/05/23	ISSUED FOR CLIENT REVIEW
B	10/17/23	REVISED PER CLIENT COMMENTS
0	12/01/23	ISSUED FOR CONSTRUCTION

CEN TEK PROJECT NUMBER
23009.09

DISH Wireless L.L.C.
PROJECT INFORMATION
BOBOS01171A
227 BOOMBRIDGE RD
NORTH STONINGTON CT,
06359

SHEET TITLE
DISH GENERAL NOTES

SHEET NUMBER
GN-1.4

GROUNDING NOTES:

1. ALL GROUND ELECTRODE SYSTEMS (INCLUDING TELECOMMUNICATION, RADIO, LIGHTNING PROTECTION AND AC POWER GES'S) SHALL BE BONDED TOGETHER AT OR BELOW GRADE, BY TWO OR MORE COPPER BONDING CONDUCTORS IN ACCORDANCE WITH THE NEC.
2. THE CONTRACTOR SHALL PERFORM IEEE FALL-OF-POTENTIAL RESISTANCE TO EARTH TESTING (PER IEEE 1100 AND 81) FOR GROUND ELECTRODE SYSTEMS, THE CONTRACTOR SHALL FURNISH AND INSTALL SUPPLEMENTAL GROUND ELECTRODES AS NEEDED TO ACHIEVE A TEST RESULT OF 5 OHMS OR LESS.
3. THE CONTRACTOR IS RESPONSIBLE FOR PROPERLY SEQUENCING GROUNDING AND UNDERGROUND CONDUIT INSTALLATION AS TO PREVENT ANY LOSS OF CONTINUITY IN THE GROUNDING SYSTEM OR DAMAGE TO THE CONDUIT AND PROVIDE TESTING RESULTS.
4. METAL CONDUIT AND TRAY SHALL BE GROUNDED AND MADE ELECTRICALLY CONTINUOUS WITH LISTED BONDING FITTINGS OR BY BONDING ACROSS THE DISCONTINUITY WITH #6 COPPER WIRE UL APPROVED GROUNDING TYPE CONDUIT CLAMPS.
5. METAL RACEWAY SHALL NOT BE USED AS THE NEC REQUIRED EQUIPMENT GROUND CONDUCTOR. STRANDED COPPER CONDUCTORS WITH GREEN INSULATION, SIZED IN ACCORDANCE WITH THE NEC, SHALL BE FURNISHED AND INSTALLED WITH THE POWER CIRCUITS TO BTS EQUIPMENT.
6. EACH CABINET FRAME SHALL BE DIRECTLY CONNECTED TO THE MASTER GROUND BAR WITH GREEN INSULATED SUPPLEMENTAL EQUIPMENT GROUND WIRES, #6 STRANDED COPPER OR LARGER FOR INDOOR BTS; #2 BARE SOLID TINNED COPPER FOR OUTDOOR BTS.
7. CONNECTIONS TO THE GROUND BUS SHALL NOT BE DOUBLED UP OR STACKED BACK TO BACK CONNECTIONS ON OPPOSITE SIDE OF THE GROUND BUS ARE PERMITTED.
8. ALL EXTERIOR GROUND CONDUCTORS BETWEEN EQUIPMENT/GROUND BARS AND THE GROUND RING SHALL BE #2 SOLID TINNED COPPER UNLESS OTHERWISE INDICATED.
9. ALUMINUM CONDUCTOR OR COPPER CLAD STEEL CONDUCTOR SHALL NOT BE USED FOR GROUNDING CONNECTIONS.
10. USE OF 90° BENDS IN THE PROTECTION GROUNDING CONDUCTORS SHALL BE AVOIDED WHEN 45° BENDS CAN BE ADEQUATELY SUPPORTED.
11. EXOTHERMIC WELDS SHALL BE USED FOR ALL GROUNDING CONNECTIONS BELOW GRADE.
12. ALL GROUND CONNECTIONS ABOVE GRADE (INTERIOR AND EXTERIOR) SHALL BE FORMED USING HIGH PRESS CRIMPS.
13. COMPRESSION GROUND CONNECTIONS MAY BE REPLACED BY EXOTHERMIC WELD CONNECTIONS.
14. ICE BRIDGE BONDING CONDUCTORS SHALL BE EXOTHERMICALLY BONDED OR BOLTED TO THE BRIDGE AND THE TOWER GROUND BAR.
15. APPROVED ANTIOXIDANT COATINGS (i.e. CONDUCTIVE GEL OR PASTE) SHALL BE USED ON ALL COMPRESSION AND BOLTED GROUND CONNECTIONS.
16. ALL EXTERIOR GROUND CONNECTIONS SHALL BE COATED WITH A CORROSION RESISTANT MATERIAL.
17. MISCELLANEOUS ELECTRICAL AND NON-ELECTRICAL METAL BOXES, FRAMES AND SUPPORTS SHALL BE BONDED TO THE GROUND RING, IN ACCORDANCE WITH THE NEC.
18. BOND ALL METALLIC OBJECTS WITHIN 6 ft OF MAIN GROUND RING WITH (1) #2 BARE SOLID TINNED COPPER GROUND CONDUCTOR.
19. GROUND CONDUCTORS USED FOR THE FACILITY GROUNDING AND LIGHTNING PROTECTION SYSTEMS SHALL NOT BE ROUTED THROUGH METALLIC OBJECTS THAT FORM A RING AROUND THE CONDUCTOR, SUCH AS METALLIC CONDUITS, METAL SUPPORT CLIPS OR SLEEVES THROUGH WALLS OR FLOORS. WHEN IT IS REQUIRED TO BE HOUSED IN CONDUIT TO MEET CODE REQUIREMENTS OR LOCAL CONDITIONS, NON-METALLIC MATERIAL SUCH AS PVC CONDUIT SHALL BE USED. WHERE USE OF METAL CONDUIT IS UNAVOIDABLE (i.e., NONMETALLIC CONDUIT PROHIBITED BY LOCAL CODE) THE GROUND CONDUCTOR SHALL BE BONDED TO EACH END OF THE METAL CONDUIT.
20. ALL GROUNDS THAT TRANSITION FROM BELOW GRADE TO ABOVE GRADE MUST BE #2 BARE SOLID TINNED COPPER IN 3/4" NON-METALLIC, FLEXIBLE CONDUIT FROM 24" BELOW GRADE TO WITHIN 3" TO 6" OF CAD-WELD TERMINATION POINT. THE EXPOSED END OF THE CONDUIT MUST BE SEALED WITH SILICONE CAULK. (ADD TRANSITIONING GROUND STANDARD DETAIL AS WELL).
21. BUILDINGS WHERE THE MAIN GROUNDING CONDUCTORS ARE REQUIRED TO BE ROUTED TO GRADE, THE CONTRACTOR SHALL ROUTE TWO GROUNDING CONDUCTORS FROM THE ROOFTOP, TOWERS, AND WATER TOWERS GROUNDING RING, TO THE EXISTING GROUNDING SYSTEM, THE GROUNDING CONDUCTORS SHALL NOT BE SMALLER THAN 2/0 COPPER. ROOFTOP GROUNDING RING SHALL BE BONDED TO THE EXISTING GROUNDING SYSTEM, THE BUILDING STEEL COLUMNS, LIGHTNING PROTECTION SYSTEM, AND BUILDING MAIN WATER LINE (FERROUS OR NONFERROUS METAL PIPING ONLY). DO NOT ATTACH GROUNDING TO FIRE SPRINKLER SYSTEM PIPES.



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



CEN TEK engineering
Centered on Solutions™

(203) 488-0580
(203) 488-8587 Fax
63-2 North Branford Road
Branford, CT 06405

www.CentekEng.com



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
BSP	TJR	

RFDS REV #: 0 - 08/17/2023

CONSTRUCTION DOCUMENTS

SUBMITTALS

REV	DATE	DESCRIPTION
A	10/05/23	ISSUED FOR CLIENT REVIEW
B	10/17/23	REVISED PER CLIENT COMMENTS
0	12/01/23	ISSUED FOR CONSTRUCTION

CEN TEK PROJECT NUMBER
23009.09

DISH Wireless L.L.C.
PROJECT INFORMATION

BOBOS01171A
227 BOOMBRIDGE RD
NORTH STONINGTON CT,
06359

SHEET TITLE
DISH GENERAL NOTES

SHEET NUMBER

GN-1.5

RF COLOR CODING

RF Cable Color Codes

	Low Bands (N71-N26) Colors - (N26)	Mid Bands (N27-N40) Colors - (N40)	High Bands (N41-N54) Colors - (N54)	CBRS Bands (N55-N68) Colors - (N68)	Negative Band Port on Ant/RRH
<p>RF Jumper Color Coding 3/4" tape widths with 3/4" spacing</p>					
<p>Low-Band RRH - (500MHz N71 baseband) + (700MHz N26 band) + (700MHz N29 band) - optional per market</p> <p>Add Frequency Color to Sector Band (CBRS will use Yellow bands)</p>					
<p>Mid-band RRH - (AWS bands N42-N70)</p> <p>Add Frequency Color to Sector Band (CBRS will use Yellow bands)</p>					
<p>Hybrid/Discret Cables</p> <p>Example 1 - Hybrid, no CBRS, sequential all ports with low-band and mid-band</p> <p>Example 2 - Hybrid, no CBRS, sequential all ports with low-band and mid-band</p> <p>Example 3 - Hybrid, no CBRS, sequential all ports with low-band and mid-band</p> <p>Example 4 - Main Core with ground mounted RRHs</p>					
<p>Fiber Jumpers to RRHs</p> <p>Low Band RRH fiber cables have sector stripe only</p>					
<p>Power Cables to RRHs</p> <p>Low Band RRH power cables have sector stripe only</p>					
<p>RET colors at Antennas</p> <p>RET control is handled by the Mid-band RRH when one set of RET ports exist on antenna</p> <p>Separate RET cables are used when antenna ports provide inputs for both Low and Mid bands</p>					
<p>Microwave Radio Links</p> <p>Links will have a 1/2 inch white wrap with the primary color overlapping to the middle. Add additional sector color bands to each additional RRH radio</p> <p>Microwave cables will require P1 (sector) labels. Bands for control to identify the tool will provide 50% ID's</p>	<p>Forward azimuth of 0-120 degrees</p>	<p>Forward azimuth of 120-240 degrees</p>	<p>Forward azimuth of 240-360 degrees</p>		



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



CENTEK engineering
Centered on Solutions™

(203) 488-0580
(203) 488-5587 Fax
63-2 North Branford Road
Branford, CT 06405

www.CentekEng.com



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
BSP	TJR	

RFDS REV #: 0 - 08/17/2023

CONSTRUCTION DOCUMENTS

SUBMITTALS

REV	DATE	DESCRIPTION
A	10/05/23	ISSUED FOR CLIENT REVIEW
B	10/17/23	REVISED PER CLIENT COMMENTS
0	12/01/23	ISSUED FOR CONSTRUCTION

CENTEK PROJECT NUMBER
23009.09

DISH Wireless L.L.C.
PROJECT INFORMATION

BOBOS0171A
227 BOOMBRIDGE RD
NORTH STONINGTON CT,
06359

SHEET TITLE
RF CABLE
COLOR CODES

SHEET NUMBER

RF-1

Exhibit D

Structural Analysis Report

Structural Analysis Report

180-ft Existing Guyed Lattice Tower

*Proposed Dish
Antenna Installation*


Dish Site Ref: BOBOS01171A

*227 Boombridge Road,
North Stonington, CT*

Centek Project No. 23009.09

Date: September 19, 2023

Max Stress Ratio = 70.2%



Prepared for:
Northeast Site Solutions
5 Melrose Road
Farmington, CT 06032

Table of Contents

SECTION 1 – REPORT

- INTRODUCTION
- ANTENNA AND APPURTENANCE SUMMARY
- PRIMARY ASSUMPTIONS USED IN THE ANALYSIS
- ANALYSIS
- TOWER LOADING
- TOWER CAPACITY
- FOUNDATION AND ANCHORS
- CONCLUSION

SECTION 2 – CONDITIONS & SOFTWARE

- STANDARD ENGINEERING CONDITIONS.
- GENERAL DESCRIPTION OF STRUCTURAL ANALYSIS PROGRAM.

SECTION 3 – CALCULATIONS – (with Proposed Verizon Wireless Reinforcements)

- tnxTower INPUT/OUTPUT SUMMARY
- tnxTower FEED LINE PLAN
- tnxTower FEED LINE DISTRIBUTION
- tnxTower GUY TENSION AND ANCHOR REACTIONS
- tnxTower DETAILED OUTPUT
- TOWER BASE AND GUY FOUNDATION ANALYSIS

SECTION 4 – REFERENCE MATERIALS

- DISH RFDS.

I n t r o d u c t i o n

The purpose of this report is to summarize the results of the non-linear, P- Δ structural analysis of the antenna installation proposed by Dish on the existing guyed lattice tower located in North Stonington, CT.

The host tower is a 180-ft, three face, guyed steel lattice tower originally manufactured by UNR ROHN circa 1997; job no. 33353PH. The tower geometry and structure member information was obtained from UNR-ROHN assembly drawing D951097, file no. 33353PH dated November 10, 1997. Subsequent tower reinforcement design information was obtained from a structural analysis and reinforcement design report prepared for Verizon Wireless by Centek Engineering, dated December 1, 2011. Guy anchor foundation information was obtained from the standard UNR-ROHN foundation drawing no. C620643, dated August 18, 1977.

Antenna and appurtenance information were obtained from a structural analysis report prepared by Centek Engineering; job no. 22022.04 dated May 6, 2022 and an RF data sheet provided by Dish dated August 17, 2023.

The tower consists of ten (10) vertical sections constructed of steel pipe legs conforming to ASTM A572-50. Diagonal and horizontal lateral support bracing consists of a combination of steel angle and steel pipe construction conforming to ASTM A36 and ASTM A53-B-42. The vertical tower sections are connected by bolted flange plates with the diagonal and horizontal bracing to pipe legs consisting of bolted connections. The width of the tower face is 3.42-ft throughout its length with the exception of a 5'-0" high tapered base section.

A n t e n n a a n d A p p u r t e n a n c e S u m m a r y

- AT&T (Existing):
Antennas: Three (3) Powerwave 7770, three (3) CCI TPA-65RLCUUUU-H8, two (2) Powerwave P65-17-XLH-RR, one (1) Commscope SBNH-1D6565C, three (3) Ericsson RRUS-11, three (3) Ericsson 4415 B25, six (6) Kaelus DBC0061F1V51-2 and three (3) TMAs mounted on three (3) existing 15-ft ROHN boom gates with a RAD center elevation of ± 180 -ft above grade.
Coax Cables: Twelve (12) 1-5/8" \varnothing coax, one (1) fiber trunk and two (2) DC trunk cables running on the leg/face(s) of the existing tower as specified within Section 3 of this report.
- VERIZON (Existing):
Antennas: Six (6) Antel LPA 80080/4CF, six (6) Qunitel QS6656-5D, three (3) Samsung B2/B66A, three (3) Samsung B5/B13 and one (1) OVP mounted on three (3) SitePro VFA12-HD 12-ft V-Frames with a RAD center elevation of ± 136 -ft above grade.
Coax Cables: Six (6) 1-5/8" \varnothing coax and two (2) 1-5/8" \varnothing hybriflex cables running on a leg/face of the existing tower as specified within Section 3 of this report.
- T-MOBILE (Existing):
Antennas: Three (3) RFS APXVAALL24-43-U-NA20 panel antenna, three (3) Ericsson AIR6419 B41 panel antennas, three (3) Commscope VV-65A-R1 panel antennas, three (3) Ericsson 4460 B25+B66 remote radio heads and three (3) Ericsson 4449 B71+B12 remote radio heads with a RAD center elevation of ± 120 -ft above grade.
Coax Cables: Three (3) 6x12 and one (1) 6x24 hybrid cables running on a leg/face of the existing tower as specified within Section 3 of this report.

CEN TEK Engineering, Inc.

Structural Analysis - 180-ft Guyed Lattice Tower

Dish Antenna Installation ~ BOBOS01171A

North Stonington, CT

September 19, 2023

- Unknown (Existing):

Antennas: One (1) GPS antenna mounted on a 1-ft stand-off frame with a RAD center elevation of ±98-ft above grade.

Coax Cables: One (1) 1/2" Ø coax cable running on the face of the existing tower as specified within Section 3 of this report.

- **DISH (PROPOSED):**

Antennas: Three (3) Commscope FFVV-65B-R2 panel antennas, three (3) Samsung RF4450t-71A remote radio heads, three (3) Samsung RF4451d-70A remote radio heads and one (1) Raycap RD1DC-9181-PF-48 OVP box mounted on three (3) existing 8-ft V-Frames (Sitepro p/n VFA8-HD) with a RAD center elevation of ±153-ft above grade.

Coax Cables: One (1) 1-1/4"Ø Hybriflex cable running on the face of the existing tower as specified in Section 3 of this report.

Primary Assumptions Used in the Analysis

- The tower structure's theoretical capacity not including any assessment of the condition of the tower.
- The tower carries the horizontal and vertical loads due to the weight of antennas, ice load and wind.
- Tower is properly installed and maintained.
- Tower is in plumb condition.
- Tower loading for antennas and mounts as listed in this report.
- All bolts are appropriately tightened providing the necessary connection continuity.
- All welds are fabricated with ER-70S-6 electrodes.
- All members are assumed to be as specified in the original tower design documents or reinforcement drawings.
- All members are "hot dipped" galvanized in accordance with ASTM A123 and ASTM A153 Standards.
- All member protective coatings are in good condition.
- All tower members were properly designed, detailed, fabricated, installed and have been properly maintained since erection.
- Any deviation from the analyzed antenna loading will require a new analysis for verification of structural adequacy.
- All coax cables to be installed as indicated in this report.

A n a l y s i s

The existing tower was analyzed using a comprehensive computer program entitled tnxTower. The program analyzes the tower, considering the worst case loading condition. The tower is considered as loaded by concentric forces along the tower, and the model assumes that the tower members are subjected to bending, axial, and shear forces.

The existing tower was analyzed for the controlling basic wind speed (3-second gust) with no ice and the applicable wind and ice combination to determine stresses in members as per guidelines of TIA-222-H entitled "Structural Standard for Antenna Support Structures and Antennas", the American Institute of Steel Construction (AISC) and the Manual of Steel Construction; Load and Resistance Factor Design (LRFD).

The controlling wind speed is determined by evaluating the local available wind speed data as provided in Appendix P of the CSBC¹ and the wind speed data available in the TIA-222-H Standard.

T o w e r L o a d i n g

Tower loading was determined by the basic wind speed as applied to projected surface areas with modification factors per TIA-222-H, gravity loads of the tower structure and its components, and the application of 1.0" radial ice on the tower structure and its components.

Load Cases:	<u>Load Case 1</u> ; 130 mph (Ultimate) wind speed w/ no ice plus gravity load – used in calculation of tower stresses and rotation.	<i>[Appendix P of the 2022 CT Building Code]</i>
	<u>Load Case 2</u> ; 50 mph wind speed w/ 1.0" radial ice plus gravity load – used in calculation of tower stresses.	<i>[Annex B of TIA-222-H]</i>
	<u>Load Case 3</u> ; 60 mph (Nominal) wind speed used for deflection calculation.	

¹ The 2021 International Building Code as amended by the 2022 Connecticut State Building Code (CSBC).

Tower Capacity

- Calculated stresses were found to be within allowable limits. This tower was found to be at **70.2%** of its total capacity.

Tower Section	Elevation	Stress Ratio (percentage of capacity)	Result
Leg (T4)	20' - 40'	70.2%	PASS
Diagonal (T5)	80' - 100'	64.2%	PASS
Bottom Girt (T9)	5' - 20'	61.2%	PASS
Guy A (T3)	132.159'	61.6%	PASS
Bolt Check	-	63.1%	PASS

Foundations and Anchorage

The existing tower base foundation, type CB No. 9, consists of a 2-ft square pedestal with a 6-ft square reinforced concrete pad bearing directly on the existing sub grade, obtained from the standard ROHN 'Concrete Base Foundation Schedule', drawing No. C610621, dated January 9, 1985. The reinforced concrete anchor support blocks at the 142-ft guy radius were based on the typical ROHN 10a foundation and the reinforced concrete anchor support blocks at the 162-ft radius were based on the ROHN 10e foundation. The guy anchor foundation information was obtained from ROHN drawing No. C620643, dated August 18, 1977. Three (3) additional guy anchor foundations consistent of 12'x6'x4' reinforced concrete blocks were installed at a 100-ft guy radius. Reinforcement information was attained from construction drawings prepared by Centek Engineering, job no. 11079, dated December 13, 2011.

The worst case tower base and guy anchor reactions developed from the governing Load Case were used in the verification of the anchorage foundations:

Tower Guy Reactions			
Vector	Inner (100' Rad.)	Center (142' Rad.)	Outer (162' Rad.)
Horizontal (In Plane of GW)	22 kips	24 kips	11 kips
Horizontal (Out of Plane of GW)	0 kips	1 kips	0 kips
Vertical	16 kips	25 kips	11 kips
Resultant Force at end of Guy Wire	27 kips	34 kips	16 kips
Tower Base Reactions			
Vector	Proposed Reaction		
Horizontal Shear	2 kips		
Axial Compression	138 kips		

CENTEK Engineering, Inc.
 Structural Analysis - 180-ft Guyed Lattice Tower
 Dish Antenna Installation ~ BOBOS01171A
 North Stonington, CT
 September 19, 2023

Foundation	Design Limit	TIA-222-H (FS) ⁽¹⁾	Proposed Loading (FS) ⁽¹⁾	Result
Reinf. Conc. Anchor Block (C) at 142-ft radius.	Uplift	1.0	2.4	PASS
	Sliding	1.0	1.4	PASS
		Ultimate Bearing	Proposed	
Base Foundation	Bearing	12.0 ksf	4.0 ksf	PASS

Conclusion


This analysis shows that the subject tower **is adequate** to support the proposed antenna configuration.

The analysis is based, in part, on the information provided to this office by Dish. If the existing conditions are different than the information in this report, Centek Engineering, Inc. must be contacted for resolution of any potential issues.

Please feel free to call with any questions or comments.

Respectfully Submitted by:

Timothy J. Lynn, PE
 Structural Engineer



*Standard Conditions for Furnishing of
Professional Engineering Services on
Existing Structures*

All engineering services are performed on the basis that the information used is current and correct. This information may consist of, but is not necessarily limited to:

- Information supplied by the client regarding the structure itself, its foundations, the soil conditions, the antenna and feed line loading on the structure and its components, or other relevant information.
- Information from the field and/or drawings in the possession of Centek Engineering, Inc. or generated by field inspections or measurements of the structure.
- It is the responsibility of the client to ensure that the information provided to Centek Engineering, Inc. and used in the performance of our engineering services is correct and complete. In the absence of information to the contrary, we assume that all structures were constructed in accordance with the drawings and specifications and are in an uncorroded condition and have not deteriorated. It is therefore assumed that its capacity has not significantly changed from the “as new” condition.
- All services will be performed to the codes specified by the client, and we do not imply to meet any other codes or requirements unless explicitly agreed in writing. If wind and ice loads or other relevant parameters are to be different from the minimum values recommended by the codes, the client shall specify the exact requirement. In the absence of information to the contrary, all work will be performed in accordance with the latest revision of ANSI/ASCE10 & ANSI/EIA-222
- All services performed, results obtained, and recommendations made are in accordance with generally accepted engineering principles and practices. Centek Engineering, Inc. is not responsible for the conclusions, opinions and recommendations made by others based on the information we supply.

GENERAL DESCRIPTION OF STRUCTURAL ANALYSIS PROGRAM

tnxTower, is an integrated structural analysis and design software package for Designed specifically for the telecommunications industry, tnxTower, formerly RISA Tower, automates much of the tower analysis and design required by the TIA/EIA 222 Standard.

tnxTower Features:

- tnxTower can analyze and design 3- and 4-sided guyed towers, 3- and 4-sided self-supporting towers and either round or tapered ground mounted poles with or without guys.
- The program analyzes towers using the TIA-222-H standard or any of the previous TIA/EIA standards back to RS-222 (1959). Steel design is checked using the AISC ASD or the AISC LRFD specifications.
- Linear and non-linear (P-delta) analyses can be used in determining displacements and forces in the structure. Wind pressures and forces are automatically calculated.
- Extensive graphics plots include material take-off, shear-moment, leg compression, displacement, twist, feed line, guy anchor and stress plots.
- tnxTower contains unique features such as True Cable behavior, hog rod take-up, foundation stiffness and much more.
- such as True Cable behavior, hog rod take-up, foundation stiffness and much more.



RF DESIGN SHEET

Issue Date	8/17/2023
Revision	0

RFDS Status	Preliminary
Created By	Rangel, Irene

SITE INFORMATION	
DISH Site Number	BOBOS01171A
DISH Site Name	
Prequal Asset ID	
AOI	BOS
PEA	7
Latitude	41.428796
Longitude	-71.809077
Address	227 Boombridge Rd
City	North Stonington
State	CT
ZIP Code	06359
County	New London
Rad Center (ft)	153
RAD Confirmed	No Confirmed RAD
Structure Type	Guyed

PROJECT ASSIGNMENTS	
Market Manager	Bradford Rainey
Site Development Mgr.	David Goodfellow
RF Engineer	Irene Rangel
Site Acq Specialist/Develop. Cord.	David Goodfellow /
SAQ Vendor/A&E Vendor	NORTHEAST SITE SOLUTIONS LLC / NORTHEAST SITE SOLUTIONS LLC
Asset Owner/Asset #	/
Construction Mgr. (Lead/Field)	/
Contractor (General/Tower/Civil)	/ /
Power Company / Transport Provider	EVERSOURCE ELECTRIC /

EMERGENCY CONTACT INFORMATION	
Name	Temporary Emergency Line
Phone	866-624-6874

LEASE AREA	
Dimensions (ft.)	5x7
Type	Steel Platform
Baseband Cabinet	Charles(Ampheno)-H/EX
Dimensions (in)	32" x 32.1" x 74"
Baseband	gNB-CU
Generator Required	
Make/Model	

DESIGN COMMENTS
Preliminary RFDS version, not to be used for construction. To be updated as needed








RF EQUIPMENT INFORMATION

Issue Date/Revision: 8/17/2023 Revision: 0
 Site ID: BOBOS01171A
 Site Address: 227 Boombridge Rd, North Stonington CT 06359
 Structure Type: Guyed
 sectors >20' apart? No Confirmed RAD? No Confirmed RAD 153

Latitude: 41.428796 Longitude: -71.809077
 Prequal Asset ID: 0
 SOW / RF: Dish proposes to place 3 antennas, 6 RRU's, 1 junction box(s), and 1 (power/hybrid) cable(s), at the 153 foot RAD. Dish will require a 5x7 lease area for ground equipment. Preliminary RFDS version, not to be used for construction. To be updated as needed
 Comments:

	Sector 1 (alpha)			Sector 2 (beta)			Sector 3 (gamma)		
ANTENNA									
Antenna Mount Position	1	2	3	1	2	3	1	2	3
Antenna ID		1			2			3	
Manufacturer		Commscope			Commscope			Commscope	
Model Number		FFVV-65B-R2			FFVV-65B-R2			FFVV-65B-R2	
Dimensions H x W x D (in)		72.0" x 19.6" x 7.8"			72.0" x 19.6" x 7.8"			72.0" x 19.6" x 7.8"	
Weight (lbs.)		70.8			70.8			70.8	
TX Power Output (watts)		40000			40000			40000	
ERP (dBm)		76.02			76.02			76.02	
RAD Centerline Height (ft.)		153			153			153	
Azimuths (True North)		30°			150°			270°	
Mech Down Tilt		0°			0°			0°	
Default Mount		Generic							
LOW BAND/RADIO #1									
Manufacturer		Samsung			Samsung			Samsung	
Model Number		RF4450t-71A			RF4450t-71A			RF4450t-71A	
Dimensions H x W x D (in.)		16.5" x 15.0" x 11.0"			16.5" x 15.0" x 11.0"			16.5" x 15.0" x 11.0"	
Weight (lbs.)		94.58			94.58			94.58	
Location		Antenna			Antenna			Antenna	
Band		n71			n71			n71	
Quantity		1			1			1	
Port Assignment		Port 1-4			Port 1-4			Port 1-4	
Elec Down Tilt		2°			2°			2°	
MID BAND/RADIO #2									
Manufacturer		Samsung			Samsung			Samsung	
Model Number		RF4451d-70A			RF4451d-70A			RF4451d-70A	
Dimensions H x W x D (in)		15.0" x 15.0" x 8.9"			15.0" x 15.0" x 8.9"			15.0" x 15.0" x 8.9"	
Weight (lbs.)		61.3			61.3			61.3	
Location		Antenna			Antenna			Antenna	
Quantity		1			1			1	
Band		n70 n66			n70 n66			n70 n66	
Port Assignment		Port 5-8			Port 5-8			Port 5-8	
Elec Down Tilt		2°			2°			2°	
OVP (Junction Box)									
Manufacturer		Raycap							
Model Number		RDIDC-9181-PF-48							
Dimensions H x W x D (in.)		16" x 14" x 8"							
Weight (lbs.)		21							
Quantity		1							
LINE DETAILS									
Line Type		Hybrid							
Manufacturer		Cables Unlimited							
Model Number		CU12PSM6P4XXX_4AWG							
Diameter (O.D. in.)		1.75"							
Weight (lbs. per ft.)		2.716 lbs/ft							
Quantity		1							
Approx. Cable Length		183							
OTHER EQUIPMENT									
Type of Equipment									
Manufacturer									
Model Number									
Dimensions H x W x D (in)									
Weight (lbs.)									
Equipment Location									
Quantity									
Frequencies									
Downlink (TX)		n29		n66		n70		n71	
Uplink (RX)		-		[2160 - 2165] [2180 - 2200]		[1995 - 2020]		[632 - 652]	
		-		[1760 - 1765]		[1695 - 1710]		[678 - 698]	

PLUMBING DIAGRAM ANTENNA








<p>Wireless Engineering</p>	ALPHA SECTOR (1 Antenna) RRU AND ANTENNA RF CABLING CONFIGURATION			
	Commscope FFV-65B-R2 - 8 Port - 6ft LOW/MID Radios LOW Band RET cable			
Chuck Iversen 20 - Sept - 2022	SIZE 50HD6	CAGE CODE None	DWG NAME FFV-65B-R2-Commscope-8P-ALPHA	REV 1 SHEET 1 OF 1

Dimensions Length 1828 mm 72.0 in Width 498 mm 19.6 in Depth 197 mm 7.8 in	Mechanical Specifications Ret Loading @ Velocity, Normal 680 N @ 150 km/h 154.0 lbf @ 150 km/h Ret Loading @ Velocity, Max 232 N @ 150 km/h 52.3 lbf @ 150 km/h Ret Loading @ Velocity, Min 164 N @ 150 km/h 36.8 lbf @ 150 km/h Ret Loading @ Velocity, Maximum 680 N @ 150 km/h 154.0 lbf @ 150 km/h Ret Speed, Maximum 241 km/h 150 mph Packaging and Weights Length, packed 2010 mm 79.1 in Width, packed 400 mm 15.7 in Depth, packed 352 mm 13.9 in Net Weight, without mounting kit 22.1 kg 48.8 lb Weight, gross 44.3 kg 97.6 lb
--	---

- Refer to the color coding chart for RF Cables
- Check RRH SFFs are "Temp" rated, (industrial-temp range)
- RF Connector recommended torque: 50 inch-lbs.
- RET connector recommended torque: 4.3-8.6 inch-lbs.
- Weatherproof boots required on all RF Jumpers.
- RET cables require self-sealing tape.
- Protect unused ports with weather-sealing caps.
- When OOB filters are used, provide straight-through connectivity (Ant port 1 --> RU port A) with each port and each set of RF jumpers color-coded accordingly.

Sector Color Bands ALPHA SECTOR (RED) BETA SECTOR (ORANGE) GAMMA SECTOR (WHITE)	Frequency Color Bands LOW BAND (LB) (ORANGE) MID BAND (MB) (PURPLE) FUTURE (YELLOW)	Main Coax RET Cable (BLACK) RF Jumper - Low Band (ORANGE) RF Jumper - Mid Band (PURPLE)
---	---	---

PLUMBING DIAGRAM ANTENNA








	BETA SECTOR (1 Antenna) RRU AND ANTENNA RF CABLING CONFIGURATION			
	Commscope FFVV-65B-R2 - 8 Port - 6ft LOW/MID Radios LOW Band RET cable			
Chuck Iversen	SIZE 50HD6	CAGE CODE 50HD6	DWG NAME FFVV-65B-R2-Commscope-6ft_BETA	REV 1
20 - Sept - 2022	SCALE None	SHEET 1 OF 1		

Dimensions	Length 1828 mm 72.0 in	Mechanical Specifications	Init Loading at Velocity, frontal 485 N @ 150 km/h 108.0 lbf @ 150 km/h
	Width 496 mm 19.5 in		Init Loading at Velocity, lateral 232 N @ 150 km/h 52.2 lbf @ 150 km/h
Depth 197 mm 7.8 in		Init Loading at Velocity, rear 564 N @ 150 km/h 126.0 lbf @ 150 km/h	Init Loading at Velocity, maximum 693 N @ 150 km/h 155.8 lbf @ 150 km/h
		Init Speed, maximum 241 km/h 150 mph	
		Packaging and Weights	
		Length, packed 2200 mm 86.9 in	
		Width, packed 608 mm 23.9 in	
		Depth, packed 351 mm 13.8 in	
		Net Weight, without mounting kit 32.1 kg 70.8 lb	
		Weight, gross 46.5 kg 103.1 lb	

- Refer to the color coding chart for RF Cables
- Check RRH SFPs are 'temp' rated, (industrial-temp range)
- RF Connector recommended torque: 50 inch-lbs.
- RET connector recommended torque: 4.3-8.6 inch-lbs.
- Weatherproof boots required on all RF jumpers.
- RET cables require self-sealing tape.
- Protect unused ports with weather-sealing caps.
- When OOB filters are used, provide straight-through connectivity (Ant port 1 -> RU port A) with each port and each set of RF jumpers color-coded accordingly.

Sector Color Bands ALPHA SECTOR BETA SECTOR GAMMA SECTOR	Frequency Color Bands LOW BAND (LB) MID BAND (MB) FUTURE	Main Coax RET Cable RF Jumper - Low Band RF Jumper - Mid Band
--	--	---


PLUMBING DIAGRAM ANTENNA




	GAMMA SECTOR (1 Antenna) RRU AND ANTENNA RF CABLING CONFIGURATION		
	Commscope FFVV-65B-R2 - 8 Port - 6ft LOW/MID Radios LOW Band RET cable		
Chuck Iversen	CASE CODE 50HD6	DWS NAME FFVV-65B-R2-Commscope-6ft_GAMMA	REV 1
20 - Sept - 2022	SCALE None	SHEET 1 OF 1	

Dimensions	Mechanical Specifications	Packaging and Weights
Length 1828 mm 72.0 in Width 498 mm 19.6 in Depth 197 mm 7.8 in	Ant Loading at Velocity, frontal 685 N @ 150 km/h; 154.0 lbf @ 150 km/h Ant Loading at Velocity, lateral 232 N @ 150 km/h; 52.2 lbf @ 150 km/h Ant Loading at Velocity, rear 565 N @ 150 km/h; 126.8 lbf @ 150 km/h Ant Loading at Velocity, maximum 889 N @ 150 km/h; 199.8 lbf @ 150 km/h Ant Speed, maximum 241 km/h 150 mph	Length, packed 2010 mm 79.1 in Width, packed 608 mm 23.9 in Depth, packed 192 mm 7.5 in Net Weight, without mounting kit 32.1 kg 70.8 lb Weight, gross 44.1 kg 97.1 lb

- Refer to the color coding chart for RF Cables
- Check RRH SFPs are 'Temp' rated, (industrial-temp range)
- RF Connector recommended torque: 50 inch-lbs.
- RET connector recommended torque: 4.3-8.6 inch-lbs.
- Weatherproof boots required on all RF jumpers.
- RET cables require self-sealing tape.
- Protect unused ports with weather-sealing caps.
- When OOB filters are used, provide straight-through connectivity (Ant port 1 -> RU port A) with each port and each set of RF jumpers color-coded accordingly.




PLUMBING DIAGRAM OVP



	5G Macro Site Communications Diagram			
	Raycap 9303 (3 x 3 Circuits) No Booster Raycap 9181 (TOWER) Top OVP			
Chuck Iversen	SIZE	CAGE CODE	DWG NAME	REV
20 - Nov - 2022	SCALE	None	9303-NoBoost-Tower OVP	1
			SHEET	1 OF 1

DC Circuit pair #	
RF Color Coding Sector color bands	RF Color Coding Frequency color bands
ALPHA SECTOR	LOW BAND (LB)
BETA SECTOR	MID BAND (MB)
GAMMA SECTOR	UNUSED

PLUMBING DIAGRAM NETWORK



<p>Wireless Engineering</p>	<p>5G Macro Site Communications Diagram</p> <p>Cisco CSR – NCS-540 Lit Fiber-Dell XR11 DU</p>			
	<p>SIZE</p> <p>50HD6</p>	<p>CAGE CODE</p> <p>50HD6</p>	<p>DWG NAME</p> <p>CSR-DU-Good CSR-Dell</p>	<p>REV</p> <p>2</p>
<p>1 - July - 2022</p>	<p>SCALE</p> <p>None</p>	<p>SHEET</p> <p>1 OF 1</p>	<p>Author</p> <p>Chuck Iversen</p>	

CSR Port	Cable Labels	Label Type	Color Band 1	Color Band 2	Media/Adapter	Cable Part
CSR - Port 0	SiteBoss/ETH port CSR Port 0/16	Tag or Flag	NONE/GREY RIBBON CABLE		Native RJ45	CAT 5
CSR - Port 2	BMC/IDRAC CSR Port 2/17 DU IDRAC port	Tag or Flag	PURPLE		Native RJ46	CAT 5
CSR - Port 4	Alpha Low	Tag or Flag	RED	ORANGE	SFP-10G-LR-S	Hybrid Fiber Pair
CSR - Port 5	Alpha Mid	Tag or Flag	RED	PURPLE	SFP-10G-LR-S	Hybrid Fiber Pair
CSR - Port 6	Beta Low	Tag or Flag	BLUE	ORANGE	SFP-10G-LR-S	Hybrid Fiber Pair
CSR - Port 7	Beta Mid	Tag or Flag	BLUE	PURPLE	SFP-10G-LR-S	Hybrid Fiber Pair
CSR - Port 8	Gamma Low	Tag or Flag	GREEN	ORANGE	SFP-10G-LR-S	Hybrid Fiber Pair
CSR - Port 9	Gamma Mid	Tag or Flag	GREEN	PURPLE	SFP-10G-LR-S	Hybrid Fiber Pair
CSR - Port 13	PTP CSR PORT 13 DU PORT 1	Flag	BLUE		DAC/10G	SFP-H10GB-CU3M
CSR - Port 14	VMWARE-MGMT CSR PORT 14 DU PORT 3	Flag	RED		DAC/10G	SFP-H10GB-CU3M
CSR - Port 15	MIDHAUL CSR PORT 15 DU PORT 4	Flag	GREEN		DAC/10G	SFP-H10GB-CU3M
CSR - Port 18	ESXI CSR PORT 18 DU ESXI MGMT PORT	Flag	YELLOW		DAC/10G	SFP-H10GB-CU3M
CSR - Port 19	To XHAUL NID (CKT ID) CSR PORT 19	Flag	LABEL ONLY		SFP-10G-LR-S (Typically)	SM Fiber
CSR - Port 24	FRONTHAUL CSR PORT 24 DU PORT 2	Flag	LABEL ONLY		SFP-25G-SR-S	G3232002M2A901M

RF COLOR CODING

RF Cable Color Codes

Low Bands (N71+N26)
Optional - (N29)

AWS
(N66+N70+H-block)

CBRS Tech
(3 GHz)

Negative Slant Port
on Ant/RRH



RF Jumper Color Coding

3/4" tape widths with 3/4" spacing

Alpha RRH

Port 1 + slant	Port 2 - slant	Port 3 + slant	Port 4 - slant
RED	RED	RED	RED
ORANGE	ORANGE	RED	RED
	WHITE (-) Port	ORANGE	ORANGE
			WHITE (-) Port

Beta RRH

Port 1 + slant	Port 2 - slant	Port 3 + slant	Port 4 - slant
BLUE	BLUE	BLUE	BLUE
ORANGE	ORANGE	BLUE	BLUE
	WHITE (-) Port	ORANGE	ORANGE
			WHITE (-) Port

Gamma RRH

Port 1 + slant	Port 2 - slant	Port 3 + slant	Port 4 - slant
GREEN	GREEN	GREEN	GREEN
ORANGE	ORANGE	GREEN	GREEN
	WHITE (-) Port	ORANGE	ORANGE
			WHITE (-) Port

Low-Band RRH - (600MHz N71 baseband) + (850MHz N26 band) + (700MHz N29 band) - optional per market

Add Frequency Color to Sector Band (CBRS will use Yellow bands)

Mid-band RRH - (AWS bands N66+N70)

Port 1 + slant	Port 2 - slant	Port 3 + slant	Port 4 - slant
RED	RED	RED	RED
PURPLE	PURPLE	RED	RED
	WHITE (-) Port	PURPLE	PURPLE
			WHITE (-) Port

Add Frequency Color to Sector Band (CBRS will use Yellow bands)

Hybrid/Discreet Cables

Example 1: RED, BLUE, GREEN, ORANGE, PURPLE

Example 2 (3rd Tech added): RED, BLUE, GREEN, YELLOW, PURPLE

Example 3 (canister) COAX #1 (Alpha): RED, RED

Example 3 (canister) COAX #2 (Alpha): RED, RED

Include sector bands being supported along with frequency bands

Example 1 - Hybrid, or discreet, supports all sectors, both low-bands and mid-bands

Example 2 - Hybrid, or discreet, supports CBRS only, all sectors

Example 3 - Main Coax with ground mounted RRUs

Fiber Jumpers to RRHs

Low Band RRH fiber cables have sector stripe only

Low Band RRH	Mid Band RRH	Low Band RRH	Mid Band RRH	Low Band RRH	Mid Band RRH
RED, ORANGE	RED, PURPLE	BLUE, ORANGE	BLUE, PURPLE	GREEN, ORANGE	GREEN, PURPLE

Power Cables to RRHs

Low Band RRH power cables have sector stripe only

Low Band RRH	Mid Band RRH	Low Band RRH	Mid Band RRH	Low Band RRH	Mid Band RRH
RED, ORANGE	RED, PURPLE	BLUE, ORANGE	BLUE, PURPLE	GREEN, ORANGE	GREEN, PURPLE

RET motors at Antennas

Antenna 1 Mid Band / Low Band / IN

Antenna 1 Mid Band / IN	Antenna 1 Low Band / IN	Antenna 1 Mid Band / IN	Antenna 1 Low Band / IN	Antenna 1 Mid Band / IN	Antenna 1 Low Band / IN
RED, PURPLE	RED, ORANGE	BLUE, PURPLE	BLUE, ORANGE	GREEN, PURPLE	GREEN, ORANGE

RET control is handled by the MID-band RRU when one set of RET ports exist on antenna.

Separate RET cables are used when antenna ports provide inputs for both LOW and MID bands.

Microwave Radio Links

Links will have a 1.5-2 inch white wrap with the azimuth color overlapping in the middle. Add additional sector color bands for each additional MW radio.

Microwave cables will require P-touch labels inside the cabinet to identify the local and remote Site ID's.

Forward azimuth of 0-120 degrees		Forward azimuth of 120-240 degrees		Forward azimuth of 240-359 degrees	
Primary	Secondary	Primary	Secondary	Primary	Secondary
WHITE, RED, WHITE	WHITE, RED, WHITE	WHITE, BLUE, WHITE	WHITE, BLUE, WHITE	WHITE, GREEN, WHITE	WHITE, GREEN, WHITE
	RED		BLUE		GREEN
	WHITE		WHITE		WHITE

Exhibit E

Mount Analysis

Structural Analysis Report

Antenna Mount Analysis


Dish Site #: BOBOS01171A

*227 Boombridge Road
North Stonington, CT*

Centek Project No. 23009.09

Date: September 19, 2023

Max Stress Ratio = 25%



Prepared for:

*Northeast Site Solutions
5 Melrose Road
Farmington, CT 06032*

CENTEK Engineering, Inc.
Structural Analysis – Mount Analysis
Dish Site Ref. ~ BOBOS01171A
North Stonington, CT
September 19, 2023

Table of Contents

SECTION 1 – REPORT

- ANTENNA AND APPURTENANCE SUMMARY
- STRUCTURE LOADING
- CONCLUSION

SECTION 2 – CALCULATIONS

- WIND LOAD ON APPURTENANCES
- RISA3D OUTPUT REPORT
- MOUNT CONNECTION

September 19, 2023

Mr. Chuck Regulbuto
Northeast Site Solutions
5 Melrose Road
Farmington, CT 06032

Re: *Structural Letter ~ Antenna Mount*
Dish – Site Ref: BOBOS01171A
227 Boombridge Road
North Stonington, CT

Centek Project No. 23009.09

Dear Mr. Regulbuto,

Centek Engineering, Inc. has reviewed the Dish antenna installation at the above referenced site. The purpose of the review is to determine the structural adequacy of the **proposed mounts, consisting of three (3) V-frame sector mounts (SitePro P/N: VFA8-HD)** to support the proposed equipment configuration. The review considered the effects of wind load, dead load and ice load in accordance with the 2021 International Building Code as modified by the 2022 Connecticut State Building Code (CTBC) including ASCE 7-16 and ANSI/TIA-222-H *Structural Standard for Antenna Supporting Structures, Antennas and Small Wind Turbine Support Structures*.

The loads considered in this analysis consist of the following:


- **Dish:**
V-Frames: Three (3) Commscope FFVV-65B-R2 panel antennas, three (3) Samsung RF4450t-71A remote radio heads, three (3) Samsung RF4451d-70A remote radio heads and one (1) Raycap OVP box mounted on three (3) V-Frame mounts with a RAD center elevation of 153-ft +/- AGL.

The antenna mounts were analyzed per the requirements of the 2021 International Building Code as modified by the 2022 Connecticut State Building Code considering a Ultimate design wind speed of 130 mph for North Stonington as required in Appendix P of the 2022 Connecticut State Building Code.

A structural analysis of tower and foundation needs to be completed prior to any work.

Based on our review of the installation, it is our opinion that the **subject antenna mounts have sufficient capacity** to support the aforementioned antenna configurations. If there are any questions regarding this matter, please feel free to call.

Respectfully Submitted by:



Timothy J. Lynn, PE
Structural Engineer




Exhibit F

Power Density/RF Emissions Report



FOX HILL TELECOM

Radio Frequency Emissions Analysis Report



Site ID: BOBOS01171A

227 Boombridge Road
North Stonington, CT 06359

October 19, 2023

Fox Hill Telecom Project Number: 231030

Site Compliance Summary	
Compliance Status:	COMPLIANT
Site total MPE% of FCC general population allowable limit:	11.75 %



October 19, 2023

Dish Wireless
5701 South Santa Fe Drive
Littleton, CO 80120

Emissions Analysis for Site: **BOBOS01171A**

Fox Hill Telecom, Inc (“Fox Hill”) was directed to analyze the proposed radio installation for Dish Wireless, LLC (Dish) facility located at **227 Boombridge Road, North Stonington, CT**, for the purpose of determining whether the emissions from the Proposed Dish radio and antenna installation located on this property are within specified federal limits.

All information used in this report was analyzed as a percentage of current Maximum Permissible Exposure (% MPE) as listed in the FCC OET Bulletin 65 Edition 97-01 and ANSI/IEEE Std C95.1. The FCC regulates Maximum Permissible Exposure in units of microwatts per square centimeter ($\mu\text{W}/\text{cm}^2$). The number of $\mu\text{W}/\text{cm}^2$ calculated at each sample point is called the power density. The exposure limit for power density varies depending upon the frequencies being utilized. Wireless Carriers and Paging Services use different frequency bands each with different exposure limits, therefore it is necessary to report results and limits in terms of percent MPE rather than power density.

All results were compared to the FCC (Federal Communications Commission) radio frequency exposure rules, 47 CFR 1.1307(b)(1) – (b)(3), to determine compliance with the Maximum Permissible Exposure (MPE) limits for General Population/Uncontrolled environments as defined below.

General population/uncontrolled exposure limits apply to situations in which the general population may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Therefore, members of the general population would always be considered under this category when exposure is not employment related, for example, in the case of a telecommunications tower that exposes persons in a nearby residential area.

Population exposure to radio frequencies is regulated and enforced in units of microwatts per square centimeter ($\mu\text{W}/\text{cm}^2$). The general population exposure limit for the 600 MHz band is approximately $400 \mu\text{W}/\text{cm}^2$. The general population exposure limit for the 1900 MHz (PCS) and 2100 MHz (AWS / AWS-4) bands is $1000 \mu\text{W}/\text{cm}^2$. Because each carrier will be using different frequency bands, and each frequency band has different exposure limits, it is necessary to report the percentage of MPE rather than power density.



FOX HILL TELECOM

Occupational/controlled exposure limits apply to situations in which persons are exposed as a consequence of their employment and in which those persons who are exposed have been made fully aware of the potential for exposure and can exercise control over their exposure. Occupational/controlled exposure limits also apply where exposure is of a transient nature as a result of incidental passage through a location where exposure levels may be above general population/uncontrolled limits (see below), as long as the exposed person has been made fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Additional details can be found in FCC OET 65.



CALCULATIONS

Calculations were performed for the proposed upgrades to the Dish Wireless antenna facility located at **227 Boombridge Road, North Stonington, CT**, using the equipment information listed below. All calculations were performed per the specifications under FCC OET 65 for far field modeling calculations.

In OET-65, plane wave power densities in the Far Field of an antenna are calculated by considering antenna gain and reflective waves that would contribute to exposure.

Since the radiation pattern of an antenna has developed in the **Far Field** region the power gain in specific directions needs to be considered in exposure predictions to yield an Effective Radiated Power (ERP) in each specific direction from the antenna. Also, since the vertical radiation pattern of the antenna is considered, the exposure calculations would most likely be reduced significantly at ground level, resulting in a more realistic estimate of the actual exposure levels. To determine a worst-case scenario at each point along the calculation radials, each point was calculated using the antenna gain value at each angle of incident and compared against the result using an isotropic radiator at the antenna height with the greater of the two used to yield the more pessimistic far field value for each point along the calculation radial.

Additionally, to model a truly "worst case" prediction of exposure levels at or near a surface, such as at ground-level or on a rooftop, reflection off the surface of antenna radiation power can be assumed, resulting in a potential 1.6 times increase in power density in calculating far field power density values.

With these factors Considered, the worst case **Far Field prediction model** utilized in this analysis is determined by the following equation:

Equation 9 per FCC OET65 for Far Field Modeling

$$S = \frac{33.4 ERP}{R^2}$$

S = Power Density (in $\mu\text{w}/\text{cm}^2$)

ERP = Effective Radiated Power from antenna (watts)

R = Distance from the antenna (meters)

Predicted far field power density values for all carriers identified in this report were calculated 6 feet above the ground level and are displayed as a percentage of the applicable FCC standards. All emissions values for other carriers were calculated using the same Far Field model outlined above, using industry standard radio configurations and frequency band selection based upon available licenses in this geographic area for emissions contribution estimates.



For each Dish sector the following channel counts, frequency bands and power levels were utilized as shown in *Table 1*:

Technology	Frequency Band	Channel Count	Transmit Power per Channel (W)
5G	n71 (600 MHz)	4	61.5
5G	n70 (AWS-4 / 1995-2020)	4	40
5G	n66 (AWS-4 / 2180-2200)	4	40

Table 1: Channel Data Table



The following **Dish** antennas listed in *Table 2* were used in the modeling for transmission in the 600 MHz (n71) frequency band and the 2100 MHz (AWS 4) frequency bands at 1995-2020 MHz (n70) and 2180-2200 MHz (n66). This is based on feedback from Dish regarding anticipated antenna selection. Maximum gain values for all antennas are listed in the Inventory and Power Data table below.

Sector	Antenna Number	Antenna Make / Model	Antenna Centerline (ft)
A	1	Commscope FFVV-65B-R2	153
B	1	Commscope FFVV-65B-R2	153
C	1	Commscope FFVV-65B-R2	153

Table 2: Antenna Data

All calculations were done with respect to uncontrolled / general population threshold limits.



RESULTS

Per the calculations completed for the proposed **Dish** configurations *Table 3* shows resulting emissions power levels and percentages of the FCC’s allowable general population limit.

Antenna ID	Antenna Make / Model	Frequency Bands	Antenna Gain (dBd)	Channel Count	Total TX Power (W)	ERP (W)	MPE %
Antenna A1	Commscope FFVV-65B-R2	n71 (600 MHz) / n70 (AWS-4 / 1995-2020) / n66 (AWS-4 / 2180-2200)	12.15 / 15.95 / 16.25	12	566	17,079.80	1.58
Sector A Composite MPE%							1.58
Antenna B1	Commscope FFVV-65B-R2	n71 (600 MHz) / n70 (AWS-4 / 1995-2020) / n66 (AWS-4 / 2180-2200)	12.15 / 15.95 / 16.25	12	566	17,079.80	1.58
Sector B Composite MPE%							1.58
Antenna C1	Commscope FFVV-65B-R2	n71 (600 MHz) / n70 (AWS-4 / 1995-2020) / n66 (AWS-4 / 2180-2200)	12.15 / 15.95 / 16.25	12	566	17,079.80	1.58
Sector C Composite MPE%							1.58

Table 3: Dish Emissions Levels



The Following table (*Table 4*) shows all additional carriers on site and their emissions contribution estimates, along with the newly calculated **Dish** far field emissions contributions per this report. FCC OET 65 specifies that for carriers utilizing directional antennas the highest recorded sector value be used for composite site emissions values due to their greatly reduced emissions contributions in the directions of the adjacent sectors. For this site, all three sectors have the same configuration yielding the same results for all three sectors. *Table 5* below shows a summary for each **Dish** Sector as well as the composite emissions value for the site.

Site Composite MPE%	
Carrier	MPE%
Dish – Max Per Sector Value	1.58 %
AT&T	2.99 %
Verizon Wireless	3.70 %
T-Mobile	3.48 %
Site Total MPE %:	11.75 %

Table 4: All Carrier MPE Contributions

Dish Sector A Total:	1.58 %
Dish Sector B Total:	1.58 %
Dish Sector C Total:	1.58 %
Site Total:	11.75 %

Table 5: Site MPE Summary



Table 6 below details a breakdown by frequency band and technology for the MPE power values for the maximum calculated **Dish** sector(s). For this site, all three sectors have the same configuration yielding the same results for all three sectors.

Dish _ Frequency Band / Technology Max Power Values (Per Sector)	# Channels	Watts ERP (Per Channel)	Height (feet)	Total Power Density ($\mu\text{W}/\text{cm}^2$)	Frequency (MHz)	Allowable MPE ($\mu\text{W}/\text{cm}^2$)	Calculated % MPE
Dish n71 (600 MHz) 5G	4	1,008.96	153	4.16	n71 (600 MHz)	400	1.04%
Dish n70 (AWS-4 / 1995-2020) 5G	4	1,574.20	153	2.70	n70 (AWS-4 / 1995-2020)	1000	0.27%
Dish n66 (AWS-4 / 2180-2200) 5G	4	1,686.79	153	2.70	n66 (AWS-4 / 2180-2200)	1000	0.27%
						Total:	1.58 %

Table 6: Dish Maximum Sector MPE Power Values



Summary

All calculations performed for this analysis yielded results that were **within** the allowable limits for general population exposure to RF Emissions.

The anticipated maximum composite contributions from the Dish facility as well as the site composite emissions value with regards to compliance with FCC's allowable limits for general population exposure to RF Emissions are shown here:

Dish Sector	Power Density Value (%)
Sector A:	1.58 %
Sector B:	1.58 %
Sector C:	1.58 %
Dish Maximum Total (per sector):	1.58 %
Site Total:	11.75 %
Site Compliance Status:	COMPLIANT

The anticipated composite emissions value for this site, assuming all carriers present, is **11.75 %** of the allowable FCC established general population limit sampled at the ground level. This is based upon the far field calculations performed for all carriers identified in this report.

FCC guidelines state that if a site is found to be out of compliance (over allowable thresholds), that carriers over a 5% contribution to the composite value will require measures to bring the site into compliance. For this facility, the composite values calculated were well within the allowable 100% threshold standard per the federal government.

Scott Heffernan
Principal RF Engineer
Fox Hill Telecom, Inc
Worcester, MA 01609
(978)660-3998

Exhibit G

Letter of Authorization

**Wireless Solutions, LLC Letter of
Authorization**

CT - CONNECTICUT SITING COUNCIL

Melanie A. Bachman
Executive Director
Connecticut Siting Council
10 Franklin Square
New Britain, CT 06051

**Re: Tower Share Application
Wireless Solutions, LLC Telecommunications Site at:
227 Boombridge Road, North Stonington CT**

Wireless Solutions, LLC hereby authorizes DISH Wireless LLC, including their Agent, to act as our Agent in the processing of all zoning applications, building permits and approvals through the CT - CONNECTICUT SITING COUNCIL for the existing wireless communications site described below:

Customer Site ID: BOBDL01171A

Site Address: 227 Boombridge Road, North Stonington CT

Wireless Solutions, LLC

By: _____

Ken Thomas


Wireless Solutions, LLC

Date: _____

10-17-2023


Exhibit H

Recipient Mailings



KEN THOMAS
WIRELESS SOLUTIONS, LLC
PO BOX 284
OLD LYME CT 06371-0284

USPS TRACKING #




9405 5036 9930 0633 2582 11

DEBORAH CHASE
NORTHEAST SITE SOLUTIONS
STE 1
5 MELROSE DR
FARMINGTON CT 06032-2251

PRIORITY MAIL®


Expected Delivery Date: 12/08/23
Ref#: DD-01171A
0003

B004




Click-N-Ship®

usps.com 9405 5036 9930 0633 2582 11 0096 5000 0010 6371
\$9.65
US POSTAGE
 Flat Rate Env
U.S. POSTAGE PAID
 Click-N-Ship®
 Mailed from 06032 986743639274658
 12/05/2023



Electronic Rate Approved #038555749





Cut on dotted line.

Instructions

1. Each Click-N-Ship® label is unique. Labels are to be used as printed and used only once. DO NOT PHOTO COPY OR ALTER LABEL.
2. Place your label so it does not wrap around the edge of the package.
3. Adhere your label to the package. A self-adhesive label is recommended. If tape or glue is used, DO NOT TAPE OVER BARCODE. Be sure all edges are secure.
4. To mail your package with PC Postage®, you may schedule a Package Pickup online, hand to your letter carrier, take to a Post Office™, or drop in a USPS collection box.
5. Mail your package on the "Ship Date" you selected when creating this label.

Click-N-Ship® Label Record

USPS TRACKING # :
9405 5036 9930 0633 2582 11

Trans. #:	597524603	Priority Mail® Postage:	\$9.65
Print Date:	12/05/2023	Total:	\$9.65
Ship Date:	12/05/2023		
Expected			
Delivery Date:	12/08/2023		

From: DEBORAH CHASE
 NORTHEAST SITE SOLUTIONS
 STE 1
 5 MELROSE DR
 FARMINGTON CT 06032-2251


To: KEN THOMAS
 WIRELESS SOLUTIONS, LLC
 PO BOX 284
 OLD LYME CT 06371-0284

Ref#: DD-01171A

* Retail Pricing Priority Mail rates apply. There is no fee for USPS Tracking® service on Priority Mail service with use of this electronic rate shipping label. Refunds for unused postage paid labels can be requested online 30 days from the print date.




Thank you for shipping with the United States Postal Service!
 Check the status of your shipment on the USPS Tracking® page at usps.com



CHERYL KONSAVITCH
LAND USE ASSISTANT- TOWN OF NORTH
40 MAIN ST
N STONINGTON CT 06359-1612

USPS TRACKING #



9405 5036 9930 0633 2582 35

P

usps.com 9405 5036 9930 0633 2582 35 0096 5000 0010 6359
US POSTAGE
 Flat Rate Env
U.S. POSTAGE PAID
 Click-N-Ship®

12/05/2023 Mailed from 06032 986743639273326


PRIORITY MAIL®

DEBORAH CHASE
NORTHEAST SITE SOLUTIONS
5 MELROSE DR
FARMINGTON CT 06032-2251

Expected Delivery Date: 12/08/23
 Ref#: DD-01171A
0003

R005

Electronic Rate Approved #038555749



✂ ————— Cut on dotted line. —————

Instructions

1. Each Click-N-Ship® label is unique. Labels are to be used as printed and used only once. **DO NOT PHOTO COPY OR ALTER LABEL.**
2. Place your label so it does not wrap around the edge of the package.
3. Adhere your label to the package. A self-adhesive label is recommended. If tape or glue is used, **DO NOT TAPE OVER BARCODE.** Be sure all edges are secure.
4. To mail your package with PC Postage®, you may schedule a Package Pickup online, hand to your letter carrier, take to a Post Office™, or drop in a USPS collection box.
5. Mail your package on the "Ship Date" you selected when creating this label.

Click-N-Ship® Label Record

USPS TRACKING # :
9405 5036 9930 0633 2582 35

Trans. #: 597524603	Priority Mail® Postage: \$9.65
Print Date: 12/05/2023	Total: \$9.65
Ship Date: 12/05/2023	
Expected Delivery Date: 12/08/2023	

From: DEBORAH CHASE
 NORTHEAST SITE SOLUTIONS
 5 MELROSE DR
 FARMINGTON CT 06032-2251


Ref#: DD-01171A

To: CHERYL KONSAVITCH
 LAND USE ASSISTANT- TOWN OF NORTH
 STONINGTON
 40 MAIN ST
 N STONINGTON CT 06359-1612

* Retail Pricing Priority Mail rates apply. There is no fee for USPS Tracking® service on Priority Mail service with use of this electronic rate shipping label. Refunds for unused postage paid labels can be requested online 30 days from the print date.




Thank you for shipping with the United States Postal Service!
 Check the status of your shipment on the USPS Tracking® page at usps.com



BOB CARLSON
FIRST SELECTMAN- TOWN OF NORTH
40 MAIN ST
N STONINGTON CT 06359-1612

USPS TRACKING #



9405 5036 9930 0633 2582 59

DEBORAH CHASE
NORTHEAST SITE SOLUTIONS
5 MELROSE DR
FARMINGTON CT 06032-2251

Expected Delivery Date: 12/08/23
Ref#: DD-01171A
0003


P

USPS.com 9405 5036 9930 0633 2582 59 0096 5000 0010 6359
\$9.65
 US POSTAGE
 Flat Rate Env
 U.S. POSTAGE PAID
 Click-N-Ship®

12/05/2023

Mailed from 06032 986743639272237

Click-N-Ship®



PRIORITY MAIL®



Cut on dotted line.

Instructions

1. Each Click-N-Ship® label is unique. Labels are to be used as printed and used only once. DO NOT PHOTO COPY OR ALTER LABEL.
2. Place your label so it does not wrap around the edge of the package.
3. Adhere your label to the package. A self-adhesive label is recommended. If tape or glue is used, DO NOT TAPE OVER BARCODE. Be sure all edges are secure.
4. To mail your package with PC Postage®, you may schedule a Package Pickup online, hand to your letter carrier, take to a Post Office™, or drop in a USPS collection box.
5. Mail your package on the "Ship Date" you selected when creating this label.

Click-N-Ship® Label Record

USPS TRACKING # :
9405 5036 9930 0633 2582 59

Trans. #: 597524603	Priority Mail® Postage: \$9.65
Print Date: 12/05/2023	Total: \$9.65
Ship Date: 12/05/2023	
Expected Delivery Date: 12/08/2023	


From: DEBORAH CHASE Ref#: DD-01171A
 NORTHEAST SITE SOLUTIONS
 5 MELROSE DR
 FARMINGTON CT 06032-2251

To: BOB CARLSON
 FIRST SELECTMAN- TOWN OF NORTH STONINGTON
 40 MAIN ST
 N STONINGTON CT 06359-1612

* Retail Pricing Priority Mail rates apply. There is no fee for USPS Tracking® service on Priority Mail service with use of this electronic rate shipping label. Refunds for unused postage paid labels can be requested online 30 days from the print date.




Thank you for shipping with the United States Postal Service!
 Check the status of your shipment on the USPS Tracking® page at usps.com



USPS TRACKING #

9405 5036 9930 0633 2582 73

Electronic Rate Approved #038555749



LEWIS DAVID BABCOCK
LEWIS DAVID BABCOCK LLC
273 BOOMBRIDGE RD
N STONINGTON CT 06359-1705

P

usps.com 9405 5036 9930 0633 2582 73 0096 5000 0010 6359
\$9.65
US POSTAGE
Flat Rate Env
U.S. POSTAGE PAID
Click-N-Ship®


12/05/2023 Mailed from 06032 986743639271543

PRIORITY MAIL®

DEBORAH CHASE
NORTHEAST SITE SOLUTIONS
5 MELROSE DR
FARMINGTON CT 06032-2251

Expected Delivery Date: 12/08/23
Ref#: DD-01171A
0003

R001



Click-N-Ship®



Cut on dotted line.

Instructions

- Each Click-N-Ship® label is unique. Labels are to be used as printed and used only once. DO NOT PHOTO COPY OR ALTER LABEL.
- Place your label so it does not wrap around the edge of the package.
- Adhere your label to the package. A self-adhesive label is recommended. If tape or glue is used, DO NOT TAPE OVER BARCODE. Be sure all edges are secure.
- To mail your package with PC Postage®, you may schedule a Package Pickup online, hand to your letter carrier, take to a Post Office™, or drop in a USPS collection box.
- Mail your package on the "Ship Date" you selected when creating this label.

Click-N-Ship® Label Record

USPS TRACKING # :
9405 5036 9930 0633 2582 73

Trans. #:	597524603	Priority Mail® Postage:	\$9.65
Print Date:	12/05/2023	Total:	\$9.65
Ship Date:	12/05/2023		
Expected			
Delivery Date:	12/08/2023		

From: DEBORAH CHASE
NORTHEAST SITE SOLUTIONS
5 MELROSE DR
FARMINGTON CT 06032-2251

Ref#: DD-01171A

To: LEWIS DAVID BABCOCK
LEWIS DAVID BABCOCK LLC
273 BOOMBRIDGE RD
N STONINGTON CT 06359-1705

* Retail Pricing Priority Mail rates apply. There is no fee for USPS Tracking® service on Priority Mail service with use of this electronic rate shipping label. Refunds for unused postage paid labels can be requested online 30 days from the print date.



Thank you for shipping with the United States Postal Service!
Check the status of your shipment on the USPS Tracking® page at usps.com

BOBOS 9/1171A - North
Stonington



GREENDA_E
290 W BOY_STON ST
WORCESTER, MA 01606-2378
(800)275-8777

12/07/2023 12:55 PM

Product	Qty	Unit Price	Price
---------	-----	------------	-------

Prepaid Mail	1		\$0.00
--------------	---	--	--------

North Stonington, CT 06359

Weight: 0 lb 12.30 oz

Acceptance Date:

Thu 12/07/2023

Tracking #:

9405 5036 9930 0633 2582 59

Prepaid Mail	1		\$0.00
--------------	---	--	--------

North Stonington, CT 06359

Weight: 0 lb 12.20 oz

Acceptance Date:

Thu 12/07/2023

Tracking #:

9405 5036 9930 0633 2582 35

Prepaid Mail	1		\$0.00
--------------	---	--	--------

North Stonington, CT 06359

Weight: 0 lb 12.30 oz

Acceptance Date:

Thu 12/07/2023

Tracking #:

9405 5036 9930 0633 2582 73

Prepaid Mail	1		\$0.00
--------------	---	--	--------

Old Lyme, CT 06371

Weight: 0 lb 12.30 oz

Acceptance Date:

Thu 12/07/2023

Tracking #:

9405 5036 9930 0633 2582 11

Grand Total:			\$0.00
--------------	--	--	--------