



STATE OF CONNECTICUT
CONNECTICUT SITING COUNCIL

Ten Franklin Square, New Britain, CT 06051

Phone: (860) 827-2935 Fax: (860) 827-2950

E-Mail: siting.council@ct.gov

Web Site: portal.ct.gov/csc

VIA ELECTRONIC MAIL

January 11, 2023

Michael Jones
President
M+K Development
140 Beach 137th Street
Rockaway Beach, NY 11694
mjones@mandkdevelopment.com

RE: TS-DISH-103-221206 – Dish Wireless, LLC request for an order to approve tower sharing at an existing telecommunications facility located at 284 New Canaan Avenue, Norwalk, Connecticut.

Dear Michael Jones:

The Connecticut Siting Council (Council) is in receipt of your correspondence of January 6, 2023 submitted in response to the Council's December 20, 2022 notification of an incomplete request for tower sharing with regard to the above-referenced matter.

The submission renders the request for tower sharing complete and the Council will process the request in accordance with the Federal Communications Commission 60-day timeframe.

Thank you for your attention and cooperation.

Sincerely,

Melanie A. Bachman
Executive Director

MAB/IN/lm

L 70



January 6, 2023

Melanie A. Bachman
Zoning Officer
Connecticut Siting Council
10 Franklin Square
New Britain, CT 06051

RE: Request of DISH Wireless LLC for an Order to Approve the Shared Use of an Existing Tower- NJJER02030A- **TS-DISH-103-221206**
284 New Canaan Avenue, Norwalk, CT 06605

Dear Ms. Bachman:

In response to your letter dated 12/20/22 related to the incomplete application submitted and pursuant to Connecticut General Statutes ("C.G.S.") §16-50aa, as amended, DISH Wireless LLC ("DISH") hereby requests an approval from the Connecticut Siting Council ("Council") to approve the shared use by DISH of an existing telecommunication tower at 284 New Canaan Avenue in Norwalk. We have attached the following updated documents as requested to amend our original application:

- An updated set of Construction Drawings (CD) citing the 2022 Connecticut State Building Code (CSBC).
- An updated Structural Analysis (SA) citing the 2022 CSBC or 2021 IBC.

Please review and advise if there is any other required documentation required to deem this application complete.

Sincerely,

A handwritten signature in black ink, appearing to read 'Michael Jones', is written over a light green background.

Michael Jones
President, M+K Development
140 Beach 137th St
Rockaway Beach, NY 11694
732-677-8881



Amended EXHIBIT C

Construction Drawings



DISH Wireless L.L.C. SITE ID:

NJJER02030A

DISH Wireless L.L.C. SITE ADDRESS:

**284 NEW CANAAN AVE
NORWALK, CT 06850**

SCOPE OF WORK

THIS IS NOT AN ALL INCLUSIVE LIST. CONTRACTOR SHALL UTILIZE SPECIFIED EQUIPMENT PART OR ENGINEER APPROVED EQUIVALENT. CONTRACTOR SHALL VERIFY ALL NEEDED EQUIPMENT TO PROVIDE A FUNCTIONAL SITE. THE PROJECT GENERALLY CONSISTS OF THE FOLLOWING:

- TOWER SCOPE OF WORK:**
- INSTALL (3) PROPOSED PANEL ANTENNAS (1 PER SECTOR)
 - INSTALL PROPOSED JUMPERS
 - INSTALL (6) PROPOSED RRU's (3 PER SECTOR)
 - INSTALL (12) PROPOSED 7/8" COAX LINES
 - INSTALL (3) PROPOSED COMMSCOPE CDX623T-DS DIPLEXERS
 - INSTALL (1) PROPOSED CABLE CLAMP

- GROUND SCOPE OF WORK:**
- INSTALL (1) PROPOSED METAL PLATFORM
 - INSTALL (1) PROPOSED ICE BRIDGE
 - INSTALL (1) PROPOSED PPC CABINET
 - INSTALL (1) PROPOSED EQUIPMENT CABINET
 - INSTALL (1) PROPOSED POWER CONDUIT
 - INSTALL (1) PROPOSED TELCO CONDUIT
 - INSTALL (1) PROPOSED TELCO-FIBER BOX
 - INSTALL (1) PROPOSED GPS UNIT
 - INSTALL (1) PROPOSED SAFETY SWITCH (IF REQUIRED)
 - INSTALL (1) PROPOSED FIBER NID (IF REQUIRED)
 - INSTALL (1) PROPOSED METER SOCKET
 - INSTALL (3) PROPOSED COMMSCOPE CDX623T-DS DIPLEXERS

SITE INFORMATION

PROPERTY OWNER: INDIAN HILL RE, L.L.C.
ADDRESS: 46 INDIAN HILL ROAD
WESTPORT, CT 06880

TOWER TYPE: CANISTER

TOWER CO SITE ID: FA 10113256

TOWER APP NUMBER: TBD

COUNTY: FAIRFIELD COUNTY

LATITUDE (NAD 83): 41° 08' 09.8" N
41.136045 N

LONGITUDE (NAD 83): 73° 27' 22.6" W
73.456285 W

ZONING JURISDICTION: CT SITING COUNCIL

ZONING DISTRICT: TBD

PARCEL NUMBER: 5-46-76-0

OCCUPANCY GROUP: U

CONSTRUCTION TYPE: II-B

POWER COMPANY: TBD

TELEPHONE COMPANY: TBD

PROJECT DIRECTORY

APPLICANT: DISH Wireless L.L.C.
5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120

TOWER OWNER: NEW CINGULAR Wireless PCS, L.L.C.

SITE DESIGNER: M+K DEVELOPMENT
140 BEACH 137TH STREET
ROCKAWAY, NY 11694

SITE ACQUISITION: ALEXIS ELAGMI
ALEXIS.ELAGMI@DISH.COM

CONSTRUCTION MANAGER: ARNALDO ARROYO
ARNALDO.ARROYO@DISH.COM

RF ENGINEER: SRI RAM GOTTUMUKKALA
SRIRAM.GOTTUMUKKALA@DISH.COM



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



140 BEACH 137TH STREET
ROCKAWAY, NY 11694



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: GIN
CHECKED BY: ---
APPROVED BY: ---

RFDS REV #: ---

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/21/2022	ISSUED FOR REVIEW
0	12/22/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER
FA 10113256

DISH Wireless L.L.C.
PROJECT INFORMATION
NJJER02030A
284 NEW CANAAN AVE
NORWALK, CT 06850

SHEET TITLE
TITLE SHEET

SHEET NUMBER
T-1

CONNECTICUT CODE OF COMPLIANCE

ALL WORK SHALL BE PERFORMED AND MATERIALS INSTALLED IN ACCORDANCE WITH THE CURRENT EDITIONS OF THE FOLLOWING CODES AS ADOPTED BY THE LOCAL GOVERNING AUTHORITIES. NOTHING IN THESE PLANS IS TO BE CONSTRUED TO PERMIT WORK NOT CONFORMING TO THESE CODES

CODE TYPE	CODE
BUILDING	2022 CT STATE BUILDING CODE/2015 IBC W/ CT AMENDMENTS
MECHANICAL	2022 CT STATE BUILDING CODE/2015 IMC W/ CT AMENDMENTS
ELECTRICAL	2022 CT STATE BUILDING CODE/2017 NEC W/ CT AMENDMENTS

SHEET INDEX

SHEET NO.	SHEET TITLE
T-1	TITLE SHEET
A-1	OVERALL AND ENLARGED SITE PLAN
A-2	ELEVATION, ANTENNA LAYOUT AND SCHEDULE
A-3	EQUIPMENT PLATFORM AND H-FRAME DETAILS
A-4	EQUIPMENT DETAILS
A-5	EQUIPMENT DETAILS
A-6	EQUIPMENT DETAILS
E-1	ELECTRICAL/FIBER ROUTE PLAN AND NOTES
E-2	ELECTRICAL DETAILS
E-3	ELECTRICAL ONE-LINE, FAULT CALCS & PANEL SCHEDULE
G-1	GROUNDING PLANS AND NOTES
G-2	GROUNDING DETAILS
G-3	GROUNDING DETAILS
RF-1	RF CABLE COLOR CODE
GN-1	LEGEND AND ABBREVIATIONS
GN-2	RF SIGNAGE
GN-3	GENERAL NOTES
GN-4	GENERAL NOTES
GN-5	GENERAL NOTES

SITE PHOTO



UNDERGROUND SERVICE ALERT CBYD 811
UTILITY NOTIFICATION CENTER OF CONNECTICUT
(800) 922-4455
WWW.CBYD.COM
CALL 2 WORKING DAYS UTILITY NOTIFICATION PRIOR TO CONSTRUCTION



GENERAL NOTES

THE FACILITY IS UNMANNED AND NOT FOR HUMAN HABITATION. A TECHNICIAN WILL VISIT THE SITE AS REQUIRED FOR ROUTINE MAINTENANCE. THE PROJECT WILL NOT RESULT IN ANY SIGNIFICANT DISTURBANCE OR EFFECT ON DRAINAGE, NO SANITARY SEWER SERVICE, POTABLE WATER, OR TRASH DISPOSAL IS REQUIRED AND NO COMMERCIAL SIGNAGE IS PROPOSED.

11"x17" PLOT WILL BE HALF SCALE UNLESS OTHERWISE NOTED

CONTRACTOR SHALL VERIFY ALL PLANS, EXISTING DIMENSIONS, AND CONDITIONS ON THE JOB SITE, AND SHALL IMMEDIATELY NOTIFY THE ENGINEER IN WRITING OF ANY DISCREPANCIES BEFORE PROCEEDING WITH THE WORK.

DIRECTIONS

DIRECTIONS FROM 3 ADP:
GET ON I-280 E FROM LIVINGSTON AVE, HEAD NORTHEAST TOWARD ADP BLVD, TURN LEFT, TURN LEFT TOWARD ADP BLVD, TURN LEFT TOWARD ADP BLVD, TURN LEFT ONTO ADP BLVD, TURN RIGHT TOWARD CHOCTAW WAY, SLIGHT RIGHT ONTO CHOCTAW WAY, USE THE LEFT LANE TO TURN RIGHT ONTO LIVINGSTON AVE, USE THE RIGHT LANE TO TAKE THE RAMP ONTO I-280 E, CONTINUE ON I-280 E, TAKE GARDEN STATE PKWY AND I-287 E TO CT-15 S IN NORWALK, MERGE ONTO I-280 E, TAKE EXIT 12 FOR GARDEN STATE PKWY N, KEEP LEFT, FOLLOW SIGNS FOR GARDEN STATE PARKWAY AND MERGE ONTO GARDEN STATE PKWY, CONTINUE ONTO NJ-444 N/GARDEN STATE PKWY, CONTINUE ONTO GARDEN STATE PARKWAY CONNECTOR, TAKE EXIT 14-1 TO MERGE ONTO I-287 E/I-87 S, KEEP LEFT AT THE FORK TO CONTINUE ON I-287 E, FOLLOW SIGNS FOR WHITE PLAINS/RYE, TAKE EXIT 9 S-N TOWARD HUTCHINSON PKWY/MERRITT PKWY, MERGE ONTO WESTCHESTER AVE, USE THE RIGHT LANE TO TAKE THE RAMP TO WESTCHESTER AVE/NORTH HUTCHINSON PKWY/MERRITT PKWY, MERGE ONTO HUTCHINSON RIVER PKWY N, KEEP RIGHT AT THE FORK TO STAY ON HUTCHINSON RIVER PKWY N, CONTINUE ONTO CT-15 N, USE THE LEFT 2 LANES TO TURN SHARPLY RIGHT TO STAY ON CT-15 N, TAKE EXIT 308 FOR US-7 N TOWARD DANBURY, KEEP RIGHT AT THE FORK TO CONTINUE ON EXIT 3, FOLLOW SIGNS FOR CT-15 S/N.Y. CITY AND MERGE ONTO CT-15 S.

VICINITY MAP



NO SCALE

NOTES

1. CONTRACTOR SHALL FIELD VERIFY ALL DIMENSIONS.
2. ANTENNAS AND MOUNTS OMITTED FOR CLARITY.


NOTES

1. CONTRACTOR SHALL FIELD VERIFY ALL DIMENSIONS.
2. CONTRACTOR SHALL MAINTAIN A 10'-0" MINIMUM SEPARATION BETWEEN THE PROPOSED GPS UNIT, TRANSMITTING ANTENNAS AND EXISTING GPS UNITS.
3. ANTENNAS AND MOUNTS OMITTED FOR CLARITY.

dish
wireless.

5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120

MK
DEVELOPMENT
140 BEACH 137TH STREET
ROCKAWAY, NY 11694



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:

GIN --- ---

RFDS REV #: ---

CONSTRUCTION DOCUMENTS


SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/21/2022	ISSUED FOR REVIEW
0	12/22/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER
FA 10113256


DISH Wireless L.L.C.
PROJECT INFORMATION
NJJER02030A
284 NEW CANAAN AVE
NORWALK, CT 06850

SHEET TITLE
OVERALL AND ENLARGED
SITE PLAN


SHEET NUMBER
A-1



ENLARGED SITE PLAN



2




SITE LOCATION


AERIAL VIEW

NO SCALE


3



OVERALL SITE PLAN







1




NOTES

1. CONTRACTOR SHALL FIELD VERIFY ALL DIMENSIONS.
2. ANTENNA AND MW DISH SPECIFICATIONS REFER TO ANTENNA SCHEDULE AND TO FINAL CONSTRUCTION RFDS FOR ALL RF DETAILS
3. EXISTING EQUIPMENT AND FENCE OMITTED FOR CLARITY.



ANTENNA LAYOUT




2

SECTOR POS.	ANTENNA					TRANSMISSION CABLE	RRH			OVP
	EXISTING OR PROPOSED	MANUFACTURER - MODEL NUMBER	TECH	AZIMUTH	RAD CENTER	FEED LINE TYPE AND LENGTH	MANUFACTURER - MODEL NUMBER	TECH	POS.	MANUFACTURER MODEL
A1	PROPOSED	COMMSCOPE - FW-65B-R3	5G	60°	117'-0"	(4) 7/8"-D06C04-4AWG COAX CABLES (145'-0" LONG)	FUJITSU - TA08025-B604	5G	C1	-
							FUJITSU - TA08025-B605	5G	C1	
B1	PROPOSED	COMMSCOPE - FW-65B-R3	5G	180°	117'-0"	(4) 7/8"-D06C04-4AWG COAX CABLES (145'-0" LONG)	FUJITSU - TA08025-B604	5G	C1	-
							FUJITSU - TA08025-B605	5G	C1	
C1	PROPOSED	COMMSCOPE - FW-65B-R3	5G	300°	117'-0"	(4) 7/8"-D06C04-4AWG COAX CABLES (145'-0" LONG)	FUJITSU - TA08025-B604	5G	C1	-
							FUJITSU - TA08025-B605	5G	C1	

NOTES

1. CONTRACTOR TO REFER TO FINAL CONSTRUCTION RFDS FOR ALL RF DETAILS.
2. ANTENNA AND RRH MODELS MAY CHANGE DUE TO EQUIPMENT AVAILABILITY. ALL EQUIPMENT CHANGES MUST BE APPROVED AND REMAIN IN COMPLIANCE WITH THE PROPOSED DESIGN AND STRUCTURAL ANALYSES.

PROPOSED NORTHWEST ELEVATION



1

ANTENNA SCHEDULE

NO SCALE

3



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: GIN
CHECKED BY: ---
APPROVED BY: ---

RFDS REV #: ---

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/21/2022	ISSUED FOR REVIEW
0	12/22/2022	ISSUED FOR CONSTRUCTION




A&E PROJECT NUMBER
FA 10113256

DISH Wireless L.L.C.
PROJECT INFORMATION
NJJER02030A
284 NEW CANAAN AVE
NORWALK, CT 06850

SHEET TITLE
ELEVATION, ANTENNA
LAYOUT AND SCHEDULE

SHEET NUMBER

A-2



- NOTES**
1. CONTRACTOR TO BURY PLATFORM FEET WITH A MINIMUM OF 2" OF FILL PER EXISTING SITE SURFACE
 2. WEED BARRIER FABRIC TO BE ADDED AT DISCRETION OF DISH Wireless L.L.C. CONSTRUCTION MANAGER AT TIME OF CONSTRUCTION. ONE SHEET 8'x8' INSTALLED UNDER ALL FOUR FEET OF THE PLATFORM (4 MIL BLACK PLASTIC)
 3. EQUIPMENT CABINET OMITTED FOR CLARITY.

dish wireless.

5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120

MK DEVELOPMENT

140 BEACH 137TH STREET
ROCKAWAY, NY 11694

STATE OF CONNECTICUT
J. MAGUIRE
12/27/2022
33678
LICENSED PROFESSIONAL ENGINEER

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
GIN	---	---
RFDS REV #:	---	

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/21/2022	ISSUED FOR REVIEW
0	12/22/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER
FA 10113256



DISH Wireless L.L.C. PROJECT INFORMATION
NJER02030A
284 NEW CANAAN AVE
NORWALK, CT 06850

SHEET TITLE
EQUIPMENT PLATFORM AND H-FRAME DETAILS

SHEET NUMBER
A-3

PLATFORM EQUIPMENT PLAN NO SCALE 1



H-FRAME EQUIPMENT ELEVATION NO SCALE 2



PLATFORM DETAIL NO SCALE 3

H-FRAME DETAIL NO SCALE 4



DELTA ELECTRONICS, INC. ESOA600-HCB04 (HEX)	
DIMENSIONS (HxWxD)	75"x32"x32"
WEIGHT (EMPTY)	625 lbs (approx.)



CABINET DETAIL

NO SCALE 1



RAYCAP PPC RDIAC-2465-P-240-MTS	
ENCLOSURE DIMENSIONS (HxWxD):	39"x22.855"x12.593
WEIGHT:	80 lbs
OPERATING AC VOLTAGE	240/120 1 PHASE 3W+G



POWER PROTECTION CABINET (PPC) DETAIL

NO SCALE 2



SQUARE D SAFETY SWITCHES D224NRB	
ENCLOSURE DIM (HxWxD)	29.25"x19.00"x8.50"
ENCLOSURE TYPE	NEMA 3R RAINPROOF
UL LISTED	FILE E-2875



SAFETY SWITCH DETAIL

NO SCALE 3



ZAYO 5RU (LEFT SWING DOOR) FIBER NID ENCLOSURE	
DIMENSIONS (HxWxD)	36.1"x29"x12.9"
WEIGHT	85 lbs



FIBER NID ENCLOSURE DETAIL

NO SCALE 5

CHARLES CFIT-PF2020DSH1 FIBER TELCO ENCLOSURE	
ENCLOSURE DIMS (HxWxD)	20"x20"x9"
ENCLOSURE WEIGHT	20 lbs
MOUNTING	WALL
COMPLIANCE	TYPE 4



FIBER TELCO ENCLOSURE DETAIL


NO SCALE 6

NOT USED

NO SCALE 4


COMMSCOPE WB-K110-B WAVEGUIDE BRIDGE KIT	
DIMENSIONS (HxL)	160"x10"
WEIGHT/ VOLUME	325.0 LBS
CABLE RUN (QTY)	12

INCLUDED PRODUCTS:	WB-T12-3 TRAPEZE KIT, 3 RUNGS
	WB-LB12-3 SUPPORT BRACKET
	MF-130 DIRECT BURIAL PIPE COLUMN, 13'-4"




ICE BRIDGE DETAIL

NO SCALE 7



TYPICAL ICE BRIDGE CONCRETE PIER DETAIL

NO SCALE 8



HYBRID CABLE RUN

NO SCALE 9



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: GIN
CHECKED BY: ---
APPROVED BY: ---

RFDS REV #: ---

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/21/2022	ISSUED FOR REVIEW
0	12/22/2022	ISSUED FOR CONSTRUCTION


A&E PROJECT NUMBER
FA 10113256

DISH Wireless L.L.C.
PROJECT INFORMATION
NJJER02030A
284 NEW CANAAN AVE
NORWALK, CT 06850


SHEET TITLE
EQUIPMENT DETAILS

SHEET NUMBER
A-4


PCTEL GPSGL-TMG-SPI-40NCB	
DIMENSIONS (DIAxH) MM/INCH	81x184mm 3.2"x7.25"
WEIGHT W/ACCESSORIES	075 lbs
CONNECTOR	N-FEMALE
FREQUENCY RANGE	1590 ± 30MHz



TOP



BACK




SIDE

GPS DETAIL

NO SCALE


1



GPS MINIMUM SKY VIEW REQUIREMENTS

NO SCALE

2




CABLES UNLIMITED DC AND FIBER
MINIMUM BEND RADIUS

NO SCALE

3

COMMSCOPE MTC4045HFLD H-FRAME	
UNISTRUT/SUPPORT RAILS QTY	5
WEIGHT	±59.74 lbs

NOTE:
OR DISH Wireless L.L.C.
APPROVED EQUIVALENT



H-FRAME DETAIL

NO SCALE

5

NOT USED

NO SCALE

4

NOT USED

NO SCALE

6

dish
wireless.

5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120

MK

DEVELOPMENT
140 BEACH 137TH STREET
ROCKAWAY, NY 11694



IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:

GIN --- ---

RFDS REV #: ---

**CONSTRUCTION
DOCUMENTS**

SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/21/2022	ISSUED FOR REVIEW
0	12/22/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER

FA 10113256

DISH Wireless L.L.C.
PROJECT INFORMATION

NJERO2030A
284 NEW CANAAN AVE
NORWALK, CT 06850

SHEET TITLE
EQUIPMENT DETAILS

SHEET NUMBER

A-5

NOT USED

NO SCALE

7

NOT USED

NO SCALE


8

NOT USED


NO SCALE

9


FUJITSU DUAL BAND TA08025-B604	
DIMENSIONS (HxWxD)	14.9"x15.7"x7.8"
WEIGHT	63.9 lbs
CONNECTOR TYPE	4.3-10 RF CONNECTOR
POWER SUPPLY	DC -58~-36V




PLAN



BACK



SIDE




FRONT

RRH DETAIL


NO SCALE

1


FUJITSU TRIPLE BAND TA08025-B605	
DIMENSIONS (HxWxD)	14.9"x15.7"x9"
WEIGHT	74.95 lbs
CONNECTOR TYPE	4.3-10 RF CONNECTOR
POWER SUPPLY	DC -58~-36V




PLAN



BACK



SIDE




FRONT

RRH DETAIL

NO SCALE

2

EEI FPS-AB TRIAD FLUH MOUNT	
DESCRIPTION	PART # - QTY
TRIAD-FPS - 1/4" BRACKET ASSEMBLY	PART 1 - QTY: 6
TRIAD-AB - 1/4" HRPO GUSSET ASSEMBLY	PART 2 - QTY: 6
3/8"x5-1/2" A36 THREADED ROD	PART 3 - QTY: 6
3/8"x1-1/4" A307 BOLT	PART 4 - QTY: 6
3/8" HEX NUT	PART 5 - QTY: 6
3/8" FLAT WASHER	PART 6 - QTY: 6
3/8" LOCK WASHER	PART 7 - QTY: 6
TOTAL WEIGHT	±8 lbs




NOTE:
OR DISH Wireless L.L.C.
APPROVED EQUIVALENT

MAST MOUNT DETAIL

NO SCALE

3

COMMSCOPE FVV-65B-R3	
DIMENSIONS (HxWxD)(MM/IN)	1828x300x181 71.9"x11.8"x7.1"
RF CONNECTOR INTERFACE	4.3-10 FEMALE
WEIGHT	43.8 lbs
WEIGHT WITH BRACKETS	70.9 lbs



ANTENNA DETAIL

NO SCALE

4

CDX623T-DS-T | E15V95P63



Twin Diplexer, 555-894 MHz/1695-2360 MHz, dc sense, LOC-top

- Automatic dc sensing with dc sense
- dc redundancy with dummy current sink
- Integrated layer one converter (MSO modem)
- Convertible mounting brackets
- Stackable to single unit with included hardware
- Stackable in multiples with included hardware
- Feeder-to-antenna application

OBSELETE
Replaced by:
CDX623T-DS-T-43
E16V95P63

Product Classification

Product Type Diplexer

General Specifications

Product Family CDX623

Color Gray

Common Part Label Common

Modularity 2 Slot

Mounting Frame | Pole | Rack | Rod | Wall

Mounting Pipe Hardware Band Clamps (2)

RF Connector Interface 7-16 DIN Female

RF Connector Interface Body Style Medium rack

Dimensions

Height 225 mm | 8.858 in

Width 126 mm | 4.961 in

Depth 115 mm | 4.528 in

Ground Screw Diameter 8 mm | 0.315 in

Mounting Pipe Diameter Range 40-160 mm

DIPLEXER DETAIL

NO SCALE


5

NOT USED


NO SCALE

6

RAYCAP STEALTH SMOOTH MULTI-PART	
RADOME OUTSIDE DIAMETERS	24"-60" DIA.
APPROX. MATERIAL THICKNESS	3/16"
MAX. HEIGHT	12'-0"
CONNECTION	BOLTS OR STRAPS



PLAN



ISOMETRIC

RADOME CANISTER DETAIL

NO SCALE

8

NOT USED

NO SCALE


9



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



140 BEACH 137TH STREET
ROCKAWAY, NY 11694



IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
GIN	---	---

RFDS REV #: ---

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/21/2022	ISSUED FOR REVIEW
0	12/22/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER
FA 10113256

DISH Wireless L.L.C.
PROJECT INFORMATION
NJJER02030A
284 NEW CANAAN AVE
NORWALK, CT 06850

SHEET TITLE
EQUIPMENT DETAILS



SHEET NUMBER
A-6

NOTES


1. CONTRACTOR SHALL FIELD VERIFY ALL PROPOSED UNDERGROUND UTILITY CONDUIT ROUTE.
2. ANTENNAS AND MOUNTS OMITTED FOR CLARITY.
3. THE GROUND LEASE PROVIDES BROAD/BLANKET UTILITY RIGHTS. "PWR" AND "FBR" PATH DEPICTED ON A-1 AND E-1 ARE BASED ON BEST AVAILABLE INFORMATION INCLUDING BUT NOT LIMITED TO FIELD VERIFICATION, PRIOR PROJECT DOCUMENTATION AND OTHER REAL PROPERTY RIGHTS DOCUMENTS. WHEN INSTALLING THE UTILITIES PLEASE LOCATE AND FOLLOW EXISTING PATH. IF EXISTING PATH IS NOT AN OPTION, PLEASE NOTIFY TOWER OWNER AS FURTHER COORDINATION MAY BE NEEDED.

DC POWER WIRING SHALL BE COLOR CODED AT EACH END FOR IDENTIFYING +24V AND -48V CONDUCTORS. RED MARKINGS SHALL IDENTIFY +24V AND BLUE MARKINGS SHALL IDENTIFY -48V.

1. CONTRACTOR SHALL INSPECT THE EXISTING CONDITIONS PRIOR TO SUBMITTING A BID. ANY QUESTIONS ARISING DURING THE BID PERIOD IN REGARDS TO THE CONTRACTOR'S FUNCTIONS, THE SCOPE OF WORK, OR ANY OTHER ISSUE RELATED TO THIS PROJECT SHALL BE BROUGHT UP DURING THE BID PERIOD WITH THE PROJECT MANAGER FOR CLARIFICATION, NOT AFTER THE CONTRACT HAS BEEN AWARDED.
2. ALL ELECTRICAL WORK SHALL BE DONE IN ACCORDANCE WITH CURRENT NATIONAL ELECTRICAL CODES AND ALL STATE AND LOCAL CODES, LAWS, AND ORDINANCES. PROVIDE ALL COMPONENTS AND WIRING SIZES AS REQUIRED TO MEET NEC STANDARDS.
3. LOCATION OF EQUIPMENT, CONDUIT AND DEVICES SHOWN ON THE DRAWINGS ARE APPROXIMATE AND SHALL BE COORDINATED WITH FIELD CONDITIONS PRIOR TO CONSTRUCTION.
4. CONDUIT ROUGH-IN SHALL BE COORDINATED WITH THE MECHANICAL EQUIPMENT TO AVOID LOCATION CONFLICTS. VERIFY WITH THE MECHANICAL EQUIPMENT CONTRACTOR AND COMPLY AS REQUIRED.
5. CONTRACTOR SHALL PROVIDE ALL BREAKERS, CONDUITS AND CIRCUITS AS REQUIRED FOR A COMPLETE SYSTEM.
6. CONTRACTOR SHALL PROVIDE PULL BOXES AND JUNCTION BOXES AS REQUIRED BY THE NEC ARTICLE 314.
7. CONTRACTOR SHALL PROVIDE ALL STRAIN RELIEF AND CABLE SUPPORTS FOR ALL CABLE ASSEMBLIES. INSTALLATION SHALL BE IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS AND RECOMMENDATIONS.
8. ALL DISCONNECTS AND CONTROLLING DEVICES SHALL BE PROVIDED WITH ENGRAVED PHENOLIC NAMEPLATES INDICATING EQUIPMENT CONTROLLED, BRANCH CIRCUITS INSTALLED ON, AND PANEL FIELD LOCATIONS FED FROM.
9. INSTALL AN EQUIPMENT GROUNDING CONDUCTOR IN ALL CONDUITS PER THE SPECIFICATIONS AND NEC 250. THE EQUIPMENT GROUNDING CONDUCTORS SHALL BE BONDED AT ALL JUNCTION BOXES, PULL BOXES, AND ALL DISCONNECT SWITCHES, AND EQUIPMENT CABINETS.
10. ALL NEW MATERIAL SHALL HAVE A U.L. LABEL.
11. PANEL SCHEDULE LOADING AND CIRCUIT ARRANGEMENTS REFLECT POST-CONSTRUCTION EQUIPMENT.
12. CONTRACTOR SHALL BE RESPONSIBLE FOR AS-BUILT PANEL SCHEDULE AND SITE DRAWINGS.
13. ALL TRENCHES IN COMPOUND TO BE HAND DUG



UTILITY ROUTE PLAN



1

ELECTRICAL NOTES

NO SCALE

2



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
GIN	---	---

RFDS REV #: ---

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/21/2022	ISSUED FOR REVIEW
0	12/22/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER
FA 10113256


DISH Wireless L.L.C.
PROJECT INFORMATION
NJJER02030A
284 NEW CANAAN AVE
NORWALK, CT 06850

SHEET TITLE
ELECTRICAL/FIBER ROUTE
PLAN AND NOTES

SHEET NUMBER
E-1

CARLON EXPANSION FITTINGS



COUPLING END PART#	MALE TERMINAL ADAPTER END PART#	SIZE	STD CTN QTY.	TRAVEL LENGTH
E945D	E945DX	1/2"	20	4"
E945E	E945EX	3/4"	15	4"
E945F	E945FX	1"	10	4"
E945G	E945GX	1 1/4"	5	4"
E945H	E945HX	1 1/2"	5	4"
E945J	E945JX	2"	15	8"
E945K	E945KX	2 1/2"	10	8"
E945L	E945LX	3"	10	8"
E945M	E945MX	3 1/2"	5	8"
E945N	E945NX	4"	5	8"
E945P	E945PX	5"	1	8"
E945R	E945RX	6"	1	8"



NOTE: CONTRACTOR TO INSTALL EXPANSION FITTING SLIP JOINT AT METER CENTER CONDUIT TERMINATION, AS PER LOCAL UTILITY POLICY, ORDINANCE AND/OR SPECIFIED REQUIREMENT.

TRENCHING NOTES

- CONTRACTOR SHALL RESTORE THE TRENCH TO ITS ORIGINAL CONDITIONS BY EITHER SEEDING OR SODDING GRASS AREAS, OR REPLACING ASPHALT OR CONCRETE AREAS TO ITS ORIGINAL CROSS SECTION.
- TRENCHING SAFETY; INCLUDING, BUT NOT LIMITED TO SOIL CLASSIFICATION, SLOPING, AND SHORING, SHALL BE GOVERNED BY THE CURRENT OSHA TRENCHING AND EXCAVATION SAFETY STANDARDS.
- ALL CONDUITS SHALL BE INSTALLED IN COMPLIANCE WITH THE CURRENT NATIONAL ELECTRIC CODE (NEC) OR AS REQUIRED BY THE LOCAL JURISDICTION, WHICHEVER IS THE MOST STRINGENT.



EXPANSION JOINT DETAIL


NO SCALE 1

TYPICAL UNDERGROUND TRENCH DETAIL

NO SCALE 2

DARK TELCO BOX – INTERIOR WIRING LAYOUT

NO SCALE 3



LIT TELCO BOX – INTERIOR WIRING LAYOUT (OPTIONAL)

NO SCALE 4

NOT USED

NO SCALE 5

NOT USED

NO SCALE 6

NOT USED

NO SCALE 7

NOT USED

NO SCALE 8

NOT USED

NO SCALE 9



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



140 BEACH 137TH STREET
ROCKAWAY, NY 11694



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: GIN CHECKED BY: --- APPROVED BY: ---
RFDS REV #: ---

CONSTRUCTION DOCUMENTS



SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/21/2022	ISSUED FOR REVIEW
0	12/22/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER
FA 10113256

DISH Wireless L.L.C.
PROJECT INFORMATION
NJJER02030A
284 NEW CANAAN AVE
NORWALK, CT 06850

SHEET TITLE
ELECTRICAL
DETAILS

SHEET NUMBER
E-2



NOTES

THE (2) CONDUITS WITH (4) CURRENT CARRYING CONDUCTORS EACH, SHALL APPLY THE ADJUSTMENT FACTOR OF 80% PER 2020 NEC TABLE 310.15(C)(1) FOR UL1015 WIRE. (ALL WIRE AND TERMINATION HARDWARE TO BE RATED 75°C)

#12 FOR 20A OCPD WIRE DERATING: 0.8 x 25A = 20.0A
#8 FOR 40A OCPD WIRE DERATING: 0.8 x 50A = 40.0A

CONDUIT SIZING: AT 40% FILL PER NEC CHAPTER 9, TABLE 4, ARTICLE 358.

1.0" CONDUIT - .3460 SQ. IN AREA
3.0" CONDUIT - 3.538 SQ. IN AREA

(2 CONDUIT): USING THWN-2, CU.
RECTIFIER CONDUCTORS
#8 - 0.0366 SQ. IN X 4 = 0.1464 SQ. IN
#8 - 0.0366 SQ. IN X 1 = 0.0366 SQ. IN <GROUND
TOTAL = 0.1830 SQ. IN

RECTIFIER & GFCI CONDUCTORS
#12 - 0.0133 SQ. IN X 2 = 0.0266 SQ. IN
#8 - 0.0366 SQ. IN X 2 = 0.0732 SQ. IN
#8 - 0.0366 SQ. IN X 1 = 0.0366 SQ. IN <GROUND
TOTAL = 0.1364 SQ. IN

1.0" EMT CONDUIT IS ADEQUATE TO HANDLE THE TOTAL OF (5) WIRES, INCLUDING GROUND WIRE, AS INDICATED ABOVE.

PPC FEED CONDUCTORS (1 CONDUIT): USING THWN, CU.
3/0 - 0.2679 SQ. IN X 3 = 0.8037 SQ. IN
#6 - 0.0507 SQ. IN X 1 = 0.0507 SQ. IN <GROUND
TOTAL = 0.8544 SQ. IN

3.0" SCH 40 PVC CONDUIT IS ADEQUATE TO HANDLE THE TOTAL OF (4) WIRES, INCLUDING GROUND WIRE, AS INDICATED ABOVE.

1 OPTIONAL ALUMINUM SERVICE CONDUCTOR:
• 4/0 AL + #2 GRD MAY BE USED INSTEAD OF 3/0 CU + #6 GRD IF THE TOTAL LENGTH OF THE CONDUCTOR IS LESS THAN 300 FT FROM THE TRANSFORMER.
• ALUMINUM CONDUCTORS MUST BE 90°C TO CARRY THE FULL 200A LOAD REQUIRED
• ALUMINUM TO COPPER BUSS CONNECTIONS MUST MEET AND CONFORM TO ANSI AND BE UL LISTED. USE ANTI CORROSION CONDUCTIVE LUBRICANT ON CONNECTIONS

PPC ONE-LINE DIAGRAM

NO SCALE 1

PANEL NAME		LOCATION		VOLTAGE: 240/120 1ϕ MAIN C/B: 200 AMPS BUS RATING: 200 AMPS				MOUNTING/ENCLOSURE: SURFACE/NEMA 3R					
DELTA		EQUIPMENT PLATFORM						AVAIL. FAULT CURRENT: SHORT CIRCUIT RATING: 65,000 / 10,000 SERIES RATED					
AMPS POLES	WIRE & CONDUIT	TYPE	DESCRIPTION	KVA	CKT	A	B	CKT	KVA	DESCRIPTION	TYPE	WIRE & CONDUIT	AMPS POLES
15/1	2 #12, 1 #12G	R	INTERNAL GFCI	0.18	1	1.68		2	1.50	RECTIFIER	EQ	SEE ONE LINE	40/2
15/1	SEE ONE LINE	R	CONVENIENCE OUTLET	0.18	3		1.68	4	1.50	EQ	EQ	SEE ONE LINE	
			SPACE		5	1.50		6	1.50	RECTIFIER	EQ	SEE ONE LINE	40/2
			SPACE		7		1.50	8	1.50	EQ	EQ	SEE ONE LINE	
			SPACE		9	1.50		10	1.50	RECTIFIER	EQ	SEE ONE LINE	40/2
			SPACE		11		1.50	12	1.50	EQ	EQ	SEE ONE LINE	
			SPACE		13			14		SPACE			
			SPACE		15			16		SPACE			
			SPACE		17			18		SPACE			
			SPACE		19			20		SPACE			
			SPACE		21			22		SPACE			
			SPACE		23			24		SPACE			
				PHASED LOAD	4.7		4.7	KVA					
				TOTAL CONNECTED LOAD					9.4 KVA			39 A	
				TOTAL DEMAND LOAD					9.4 KVA			39 A	

LOAD TYPE	DESCRIPTION	CONN. LOAD KVA	AMPS	DEMAND FACTOR	DESIGN LOAD KVA	AMPS
L	LIGHTING	0.0	0.0	1.25	0.0	0.0
R	RECEPTACLE	0.4	1.5	NEC	0.4	1.5
M	MOTOR	0.0	0.0	NEC	0.0	0.0
H	HEATING	0.0	0.0	1.00	0.0	0.0
AC	HVAC	0.0	0.0	1.00	0.0	0.0
EQ	EQUIPMENT	9.0	37.5	1.00	9.0	37.5
E	EXISTING	0.0	0.0	1.25	0.0	0.0

*ALL EQUIPMENT LOADS CONSIDERED CONTINUOUS LOADS

PANEL SCHEDULE

NO SCALE 2

SHORT CIRCUIT CALCULATIONS

NO SCALE 3



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: GIN
CHECKED BY: ---
APPROVED BY: ---

RFDS REV #: ---

CONSTRUCTION DOCUMENTS


SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/21/2022	ISSUED FOR REVIEW
0	12/22/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER
FA 10113256

DISH Wireless L.L.C.
PROJECT INFORMATION
NJJER02030A
284 NEW CANAAN AVE
NORWALK, CT 06850


SHEET TITLE
ELECTRICAL ONE-LINE, FAULT
CALCS & PANEL SCHEDULE

SHEET NUMBER
E-3




TYPICAL EQUIPMENT GROUNDING PLAN

NO SCALE 1



TYPICAL ANTENNA GROUNDING DETAIL

NO SCALE 2



GROUNDING LEGEND

- GROUNDING IS SHOWN DIAGRAMMATICALLY ONLY.
- CONTRACTOR SHALL GROUND ALL EQUIPMENT AS A COMPLETE SYSTEM. GROUNDING SHALL BE IN COMPLIANCE WITH NEC SECTION 250 AND DISH Wireless L.L.C. GROUNDING AND BONDING REQUIREMENTS AND MANUFACTURER'S SPECIFICATIONS.
- ALL GROUND CONDUCTORS SHALL BE COPPER; NO ALUMINUM CONDUCTORS SHALL BE USED.

GROUNDING KEY NOTES

- (A) **EXTERIOR GROUND RING:** #2 AWG SOLID COPPER, BURIED AT A DEPTH OF AT LEAST 30 INCHES BELOW GRADE, OR 6 INCHES BELOW THE FROST LINE AND APPROXIMATELY 24 INCHES FROM THE EXTERIOR WALL OR FOOTING.
- (B) **TOWER GROUND RING:** THE GROUND RING SYSTEM SHALL BE INSTALLED AROUND AN ANTENNA TOWER'S LEGS, AND/OR GUY ANCHORS. WHERE SEPARATE SYSTEMS HAVE BEEN PROVIDED FOR THE TOWER AND THE BUILDING, AT LEAST TWO BONDS SHALL BE MADE BETWEEN THE TOWER RING GROUND SYSTEM AND THE BUILDING RING GROUND SYSTEM USING MINIMUM #2 AWG SOLID COPPER CONDUCTORS.
- (C) **INTERIOR GROUND RING:** #2 AWG STRANDED GREEN INSULATED COPPER CONDUCTOR EXTENDED AROUND THE PERIMETER OF THE EQUIPMENT AREA. ALL NON-TELECOMMUNICATIONS RELATED METALLIC OBJECTS FOUND WITHIN A SITE SHALL BE GROUNDED TO THE INTERIOR GROUND RING WITH #6 AWG STRANDED GREEN INSULATED CONDUCTOR.
- (D) **BOND TO INTERIOR GROUND RING:** #2 AWG SOLID TINNED COPPER WIRE PRIMARY BONDS SHALL BE PROVIDED AT LEAST AT FOUR POINTS ON THE INTERIOR GROUND RING, LOCATED AT THE CORNERS OF THE BUILDING.
- (E) **GROUND ROD:** UL LISTED COPPER CLAD STEEL. MINIMUM 1/2" DIAMETER BY EIGHT FEET LONG. GROUND RODS SHALL BE INSTALLED WITH INSPECTION SLEEVES. GROUND RODS SHALL BE DRIVEN TO THE DEPTH OF GROUND RING CONDUCTOR.
- (F) **CELL REFERENCE GROUND BAR:** POINT OF GROUND REFERENCE FOR ALL COMMUNICATIONS EQUIPMENT FRAMES. ALL BONDS ARE MADE WITH #2 AWG UNLESS NOTED OTHERWISE STRANDED GREEN INSULATED COPPER CONDUCTORS. BOND TO GROUND RING WITH (2) #2 SOLID TINNED COPPER CONDUCTORS.
- (G) **HATCH PLATE GROUND BAR:** BOND TO THE INTERIOR GROUND RING WITH TWO #2 AWG STRANDED GREEN INSULATED COPPER CONDUCTORS. WHEN A HATCH-PLATE AND A CELL REFERENCE GROUND BAR ARE BOTH PRESENT, THE CRGB MUST BE CONNECTED TO THE HATCH-PLATE AND TO THE INTERIOR GROUND RING USING (2) TWO #2 AWG STRANDED GREEN INSULATED COPPER CONDUCTORS EACH.
- (H) **EXTERIOR CABLE ENTRY PORT GROUND BARS:** LOCATED AT THE ENTRANCE TO THE CELL SITE BUILDING. BOND TO GROUND RING WITH A #2 AWG SOLID TINNED COPPER CONDUCTORS WITH AN EXOTHERMIC WELD AND INSPECTION SLEEVE.
- (I) **TELCO GROUND BAR:** BOND TO BOTH CELL REFERENCE GROUND BAR AND EXTERIOR GROUND RING.
- (J) **FRAME BONDING:** THE BONDING POINT FOR TELECOM EQUIPMENT FRAMES SHALL BE THE GROUND BUS THAT IS NOT ISOLATED FROM THE EQUIPMENTS METAL FRAMEWORK.
- (K) **INTERIOR UNIT BONDS:** METAL FRAMES, CABINETS AND INDIVIDUAL METALLIC UNITS LOCATED WITH THE AREA OF THE INTERIOR GROUND RING REQUIRE A #6 AWG STRANDED GREEN INSULATED COPPER BOND TO THE INTERIOR GROUND RING.
- (L) **FENCE AND GATE GROUNDING:** METAL FENCES WITHIN 7 FEET OF THE EXTERIOR GROUND RING OR OBJECTS BONDED TO THE EXTERIOR GROUND RING SHALL BE BONDED TO THE GROUND RING WITH A #2 AWG SOLID TINNED COPPER CONDUCTOR AT AN INTERVAL NOT EXCEEDING 25 FEET. BONDS SHALL BE MADE AT EACH GATE POST AND ACROSS GATE OPENINGS.
- (M) **EXTERIOR UNIT BONDS:** METALLIC OBJECTS, EXTERNAL TO OR MOUNTED TO THE BUILDING, SHALL BE BONDED TO THE EXTERIOR GROUND RING. USING #2 TINNED SOLID COPPER WIRE
- (N) **ICE BRIDGE SUPPORTS:** EACH ICE BRIDGE LEG SHALL BE BONDED TO THE GROUND RING WITH #2 AWG BARE TINNED COPPER CONDUCTOR. PROVIDE EXOTHERMIC WELDS AT BOTH THE ICE BRIDGE LEG AND BURIED GROUND RING.
- (O) DURING ALL DC POWER SYSTEM CHANGES INCLUDING DC SYSTEM CHANGE OUTS, RECTIFIER REPLACEMENTS OR ADDITIONS, BREAKER DISTRIBUTION CHANGES, BATTERY ADDITIONS, BATTERY REPLACEMENTS AND INSTALLATIONS OR CHANGES TO DC CONVERTER SYSTEMS IT SHALL BE REQUIRED THAT SERVICE CONTRACTORS VERIFY ALL DC POWER SYSTEMS ARE EQUIPPED WITH A MASTER DC SYSTEM RETURN GROUND CONDUCTOR FROM THE DC POWER SYSTEM COMMON RETURN BUS DIRECTLY CONNECTED TO THE CELL SITE REFERENCE GROUND BAR
- (P) TOWER TOP COLLECTOR BUSS BAR IS TO BE MECHANICALLY BONDED TO PROPOSED ANTENNA MOUNT.

REFER TO DISH Wireless L.L.C. GROUNDING NOTES.

GROUNDING KEY NOTES

NO SCALE 3



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



140 BEACH 137TH STREET
ROCKAWAY, NY 11694



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
GIN	---	---
RFDS REV #:	---	

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/21/2022	ISSUED FOR REVIEW
0	12/22/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER
FA 10113256


DISH Wireless L.L.C.
PROJECT INFORMATION
NJJER02030A
284 NEW CANAAN AVE
NORWALK, CT 06850

SHEET TITLE
GROUNDING PLANS
AND NOTES

SHEET NUMBER
G-1

NOTES

EQUIPMENT CABINET OMITTED FOR CLARITY



FRONT ELEVATION

SIDE ELEVATION



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
GIN	---	---
RFDS REV #:	---	

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/21/2022	ISSUED FOR REVIEW
0	12/22/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER
FA 10113256


DISH Wireless L.L.C.
PROJECT INFORMATION
NJJER02030A
284 NEW CANAAN AVE
NORWALK, CT 06850

SHEET TITLE
GROUNDING DETAILS

SHEET NUMBER
G-2

NOT USED

NO SCALE 1




TRANSITIONING GROUND DETAIL

NO SCALE 5

H-FRAME GROUNDING DETAIL

NO SCALE 4




TYPICAL GPS UNIT GROUNDING



NO SCALE 6

OUTDOOR CABINET GROUNDING

NO SCALE 7



1. EXOTHERMIC WELD (2) TWO, #2 AWG BARE TINNED SOLID COPPER CONDUCTORS TO GROUND BAR. ROUTE CONDUCTORS TO BURIED GROUND RING AND PROVIDE PARALLEL EXOTHERMIC WELD.
2. ALL EXTERIOR GROUNDING HARDWARE SHALL BE STAINLESS STEEL 3/8" DIAMETER OR LARGER. ALL HARDWARE 18-8 STAINLESS STEEL INCLUDING LOCK WASHERS, COAT ALL SURFACES WITH AN ANTI-OXIDANT COMPOUND BEFORE MATING.
3. FOR GROUND BOND TO STEEL ONLY: COAT ALL SURFACES WITH AN ANTI-OXIDANT COMPOUND BEFORE MATING.
4. DO NOT INSTALL CABLE GROUNDING KIT AT A BEND AND ALWAYS DIRECT GROUND CONDUCTOR DOWN TO GROUNDING BUS.
5. NUT & WASHER SHALL BE PLACED ON THE FRONT SIDE OF THE GROUND BAR AND BOLTED ON THE BACK SIDE.
6. ALL GROUNDING PARTS AND EQUIPMENT TO BE SUPPLIED AND INSTALLED BY CONTRACTOR.
7. THE CONTRACTOR SHALL BE RESPONSIBLE FOR INSTALLING ADDITIONAL GROUND BAR AS REQUIRED.
8. ENSURE THE WIRE INSULATION TERMINATION IS WITHIN 1/8" OF THE BARREL (NO SHINERS).



TYPICAL GROUNDING NOTES


NO SCALE 1

TYPICAL EXTERIOR TWO HOLE LUG

NO SCALE 2


TYPICAL INTERIOR TWO HOLE LUG

NO SCALE 3



LUG DETAIL

NO SCALE 4



TYPICAL TEST GROUND ROD WITH INSPECTION SLEEVE

NO SCALE 5

NOT USED

NO SCALE 6

NOT USED

NO SCALE 7

NOT USED

NO SCALE 8

NOT USED


NO SCALE 9



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



140 BEACH 137TH STREET
ROCKAWAY, NY 11694



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:

GIN --- ---

RFDS REV #: ---

CONSTRUCTION DOCUMENTS

SUBMITTALS

REV	DATE	DESCRIPTION
A	10/21/2022	ISSUED FOR REVIEW
0	12/22/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER

FA 10113256

DISH Wireless L.L.C.
PROJECT INFORMATION

NJJER02030A
284 NEW CANAAN AVE
NORWALK, CT 06850

SHEET TITLE
GROUNDING DETAILS

SHEET NUMBER

G-3

HYBRID/DISCREET CABLES												3/4" TAPE WIDTHS WITH 3/4" SPACING																					
<p>LOW-BAND RRH (600 MHz N71 BASEBAND) + (850 MHz N26 BAND) + (700 MHz N29 BAND) - OPTIONAL PER MARKET</p> <p>ADD FREQUENCY COLOR TO SECTOR BAND (CBRS WILL USE YELLOW BAND)</p>												ALPHA RRH				BETA RRH				GAMMA RRH													
PORT 1 + SLANT				PORT 2 - SLANT				PORT 3 + SLANT				PORT 4 - SLANT				PORT 1 + SLANT				PORT 2 - SLANT				PORT 3 + SLANT				PORT 4 - SLANT					
RED				RED				BLUE				BLUE				GREEN				GREEN				GREEN				GREEN					
ORANGE				ORANGE				ORANGE				ORANGE				ORANGE				ORANGE				ORANGE				ORANGE					
WHITE (-) PORT				WHITE (-) PORT				WHITE (-) PORT				WHITE (-) PORT				WHITE (-) PORT				WHITE (-) PORT				WHITE (-) PORT									
<p>MID-BAND RRH (AWS BANDS N66+N70)</p> <p>ADD FREQUENCY COLOR TO SECTOR BAND (CBRS WILL USE YELLOW BANDS)</p>												RED				BLUE				GREEN				GREEN				GREEN					
PURPLE				PURPLE				PURPLE				PURPLE				PURPLE				PURPLE				PURPLE									
WHITE (-) PORT				WHITE (-) PORT				WHITE (-) PORT				WHITE (-) PORT				WHITE (-) PORT				WHITE (-) PORT													
<p>HYBRID/DISCREET CABLES</p> <p>INCLUDE SECTOR BANDS BEING SUPPORTED ALONG WITH FREQUENCY BANDS.</p> <p>EXAMPLE 1 - HYBRID, OR DISCREET, SUPPORTS ALL SECTORS, BOTH LOW-BANDS AND MID-BANDS.</p> <p>EXAMPLE 2 - HYBRID, OR DISCREET, SUPPORTS CBRS ONLY, ALL SECTORS.</p> <p>EXAMPLE 3 - MAIN COAX WITH GROUND MOUNTED RRHS.</p>												EXAMPLE 1		EXAMPLE 2		EXAMPLE 3		CANISTER COAX #1 (ALPHA)		CANISTER COAX #2 (ALPHA)													
RED		RED		RED		RED		RED		RED																							
BLUE		BLUE		GREEN		ORANGE		PURPLE		ORANGE																							
ORANGE		ORANGE		YELLOW		PURPLE		PURPLE		PURPLE																							
<p>FIBER JUMPERS TO RRHS</p> <p>LOW-BAND HHR FIBER CABLES HAVE SECTOR STRIPE ONLY.</p>												LOW BAND RRH		MID BAND RRH		LOW BAND RRH		MID BAND RRH		LOW BAND RRH		MID BAND RRH											
RED		RED		RED		RED		RED		RED		RED																					
ORANGE		ORANGE		PURPLE		PURPLE		BLUE		BLUE		BLUE		GREEN		GREEN		ORANGE		ORANGE		PURPLE											
<p>POWER CABLES TO RRHS</p> <p>LOW-BAND RRH POWER CABLES HAVE SECTOR STRIPE ONLY.</p>												LOW BAND RRH		MID BAND RRH		LOW BAND RRH		MID BAND RRH		LOW BAND RRH		MID BAND RRH											
RED		RED		RED		RED		RED		RED		RED																					
ORANGE		ORANGE		PURPLE		PURPLE		BLUE		BLUE		BLUE		GREEN		GREEN		ORANGE		ORANGE		PURPLE											
<p>RET MOTORS AT ANTENNAS</p> <p>RET CONTROL IS HANDLED BY THE MID-BAND RRH WHEN ONE SET OF RET PORTS EXIST ON ANTENNA.</p> <p>SEPARATE RET CABLES ARE USED WHEN ANTENNA PORTS PROVIDE INPUTS FOR BOTH LOW AND MID BANDS.</p>												ANTENNA 1 MID BAND		ANTENNA 1 LOW BAND		ANTENNA 1 MID BAND		ANTENNA 1 LOW BAND		ANTENNA 1 MID BAND		ANTENNA 1 LOW BAND											
IN		IN		IN		IN		IN		IN		IN																					
RED		RED		RED		RED		RED		RED		RED																					
PURPLE		PURPLE		ORANGE		ORANGE		ORANGE		ORANGE		ORANGE																					
<p>MICROWAVE RADIO LINKS</p> <p>LINKS WILL HAVE A 1.5-2 INCH WHITE WRAP WITH THE AZIMUTH COLOR OVERLAPPING IN THE MIDDLE.</p> <p>ADD ADDITIONAL SECTOR COLOR BANDS FOR EACH ADDITIONAL MW RADIO.</p> <p>MICROWAVE CABLES WILL REQUIRE P-TOUCH LABELS INSIDE THE CABINET TO IDENTIFY THE LOCAL AND REMOTE SITE ID'S.</p>												FORWARD AZIMUTH OF 0-120 DEGREES PRIMARY		FORWARD AZIMUTH OF 0-120 DEGREES SECONDARY		FORWARD AZIMUTH OF 120-240 DEGREES PRIMARY		FORWARD AZIMUTH OF 120-240 DEGREES SECONDARY		FORWARD AZIMUTH OF 240-359 DEGREES PRIMARY		FORWARD AZIMUTH OF 240-359 DEGREES SECONDARY											
WHITE		WHITE		WHITE		WHITE		WHITE		WHITE		WHITE																					
RED		RED		RED		RED		RED		RED		RED																					
WHITE		WHITE		WHITE		WHITE		WHITE		WHITE		WHITE																					
RED		RED		BLUE		BLUE		BLUE		BLUE		BLUE																					
WHITE		WHITE		ORANGE		ORANGE		ORANGE		ORANGE		ORANGE																					
WHITE		WHITE		GREEN		GREEN		GREEN		GREEN		GREEN																					
WHITE		WHITE		PURPLE		PURPLE		PURPLE		PURPLE		PURPLE																					
WHITE		WHITE		YELLOW		YELLOW		YELLOW		YELLOW		YELLOW																					

RF CABLE COLOR CODES

NO SCALE

1

NOT USED

NO SCALE

4


LOW BANDS (N71+N26) OPTIONAL - (N29)



AWS (N66+N70+H-BLOCK)



CBRS TECH (3 GHz)



NEGATIVE SLANT PORT ON ANT/RRH



ALPHA SECTOR



BETA SECTOR



GAMMA SECTOR



COLOR IDENTIFIER

NO SCALE

2

NOT USED

NO SCALE

3

NOT USED

NO SCALE


4



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



140 BEACH 137TH STREET
ROCKAWAY, NY 11694



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:

GIN --- ---

RFDS REV #: ---

CONSTRUCTION DOCUMENTS

SUBMITTALS

REV	DATE	DESCRIPTION
A	10/21/2022	ISSUED FOR REVIEW
0	12/22/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER

FA 10113256

DISH Wireless L.L.C.
PROJECT INFORMATION




NJ02030A
284 NEW CANAAN AVE
NORWALK, CT 06850

SHEET TITLE
RF
CABLE COLOR CODE

SHEET NUMBER

RF-1

EXOTHERMIC CONNECTION
 MECHANICAL CONNECTION
 BUSS BAR INSULATOR
 CHEMICAL ELECTROLYTIC GROUNDING SYSTEM
 TEST CHEMICAL ELECTROLYTIC GROUNDING SYSTEM
 EXOTHERMIC WITH INSPECTION SLEEVE
 GROUNDING BAR
 GROUND ROD
 TEST GROUND ROD WITH INSPECTION SLEEVE
 SINGLE POLE SWITCH
 DUPLEX RECEPTACLE
 DUPLEX GFCI RECEPTACLE
 FLUORESCENT LIGHTING FIXTURE (2) TWO LAMPS 48-T8
 SMOKE DETECTION (DC)
 EMERGENCY LIGHTING (DC)
 SECURITY LIGHT W/PHOTOCELL LITHONIA ALXW
 LED-1-25A400/51K-SR4-120-PE-DOBTD
 CHAIN LINK FENCE
 WOOD/WROUGHT IRON FENCE
 WALL STRUCTURE
 LEASE AREA
 PROPERTY LINE (PL)
 SETBACKS
 ICE BRIDGE
 CABLE TRAY
 WATER LINE
 UNDERGROUND POWER
 UNDERGROUND TELCO
 OVERHEAD POWER
 OVERHEAD TELCO
 UNDERGROUND TELCO/POWER
 ABOVE GROUND POWER
 ABOVE GROUND TELCO
 ABOVE GROUND TELCO/POWER
 WORKPOINT



SECTION REFERENCE
 DETAIL REFERENCE

LEGEND

AB ANCHOR BOLT	IN INCH
ABV ABOVE	INT INTERIOR
AC ALTERNATING CURRENT	LB(S) POUND(S)
ADDL ADDITIONAL	LF LINEAR FEET
AFF ABOVE FINISHED FLOOR	LTE LONG TERM EVOLUTION
AFG ABOVE FINISHED GRADE	MAS MASONRY
AGL ABOVE GROUND LEVEL	MAX MAXIMUM
AIC AMPERAGE INTERRUPTION CAPACITY	MB MACHINE BOLT
ALUM ALUMINUM	MECH MECHANICAL
ALT ALTERNATE	MFR MANUFACTURER
ANT ANTENNA	MGB MASTER GROUND BAR
APPROX APPROXIMATE	MIN MINIMUM
ARCH ARCHITECTURAL	MISC MISCELLANEOUS
ATS AUTOMATIC TRANSFER SWITCH	MTL METAL
AWG AMERICAN WIRE GAUGE	MTS MANUAL TRANSFER SWITCH
BATT BATTERY	MW MICROWAVE
BLDG BUILDING	NEC NATIONAL ELECTRIC CODE
BLK BLOCK	NM NEWTON METERS
BLKG BLOCKING	NO. NUMBER
BM BEAM	# NUMBER
BTC BARE TINNED COPPER CONDUCTOR	NTS NOT TO SCALE
BOF BOTTOM OF FOOTING	OC ON-CENTER
CAB CABINET	OSHA OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
CANT CANTILEVERED	OPNG OPENING
CHG CHARGING	P/C PRECAST CONCRETE
CLG CEILING	PCS PERSONAL COMMUNICATION SERVICES
CLR CLEAR	PCU PRIMARY CONTROL UNIT
COL COLUMN	PRC PRIMARY RADIO CABINET
COMM COMMON	PP POLARIZING PRESERVING
CONC CONCRETE	PSF POUNDS PER SQUARE FOOT
CONSTR CONSTRUCTION	PSI POUNDS PER SQUARE INCH
DBL DOUBLE	PT PRESSURE TREATED
DC DIRECT CURRENT	PWR POWER CABINET
DEPT DEPARTMENT	QTY QUANTITY
DF DOUGLAS FIR	RAD RADIUS
DIA DIAMETER	RECT RECTIFIER
DIAG DIAGONAL	REF REFERENCE
DIM DIMENSION	REINF REINFORCEMENT
DWG DRAWING	REQ'D REQUIRED
DWL DOWEL	RET REMOTE ELECTRIC TILT
EA EACH	RF RADIO FREQUENCY
EC ELECTRICAL CONDUCTOR	RMC RIGID METALLIC CONDUIT
EL ELEVATION	RRH REMOTE RADIO HEAD
ELEC ELECTRICAL	RRU REMOTE RADIO UNIT
EMT ELECTRICAL METALLIC TUBING	RWY RACEWAY
ENG ENGINEER	SCH SCHEDULE
EQ EQUAL	SHT SHEET
EXP EXPANSION	SIAD SMART INTEGRATED ACCESS DEVICE
EXT EXTERIOR	SIM SIMILAR
EW EACH WAY	SPEC SPECIFICATION
FAB FABRICATION	SQ SQUARE
FF FINISH FLOOR	SS STAINLESS STEEL
FG FINISH GRADE	STD STANDARD
FIF FACILITY INTERFACE FRAME	STL STEEL
FIN FINISH(ED)	TEMP TEMPORARY
FLR FLOOR	THK THICKNESS
FDN FOUNDATION	TMA TOWER MOUNTED AMPLIFIER
FOC FACE OF CONCRETE	TN TOE NAIL
FOM FACE OF MASONRY	TOA TOP OF ANTENNA
FOS FACE OF STUD	TOC TOP OF CURB
FOW FACE OF WALL	TOF TOP OF FOUNDATION
FS FINISH SURFACE	TOP TOP OF PLATE (PARAPET)
FT FOOT	TOS TOP OF STEEL
FTG FOOTING	TOW TOP OF WALL
GA GAUGE	TVSS TRANSIENT VOLTAGE SURGE SUPPRESSION
GEN GENERATOR	TYP TYPICAL
GFCI GROUND FAULT CIRCUIT INTERRUPTER	UG UNDERGROUND
GLB GLUE LAMINATED BEAM	UL UNDERWRITERS LABORATORY
GLV GALVANIZED	UNO UNLESS NOTED OTHERWISE
GPS GLOBAL POSITIONING SYSTEM	UMTS UNIVERSAL MOBILE TELECOMMUNICATIONS SYSTEM
GND GROUND	UPS UNINTERRUPTIBLE POWER SYSTEM (DC POWER PLANT)
GSM GLOBAL SYSTEM FOR MOBILE	VIF VERIFIED IN FIELD
HDG HOT DIPPED GALVANIZED	W WIDE
HDR HEADER	W/ WITH
HGR HANGER	WD WOOD
HVAC HEAT/VENTILATION/AIR CONDITIONING	WP WEATHERPROOF
HT HEIGHT	WT WEIGHT
IGR INTERIOR GROUND RING	

ABBREVIATIONS



5701 SOUTH SANTA FE DRIVE
 LITTLETON, CO 80120



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
GIN	---	---
RFDS REV #:	---	

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/21/2022	ISSUED FOR REVIEW
0	12/22/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER
 FA 10113256

DISH Wireless L.L.C.
 PROJECT INFORMATION
 NJJER02030A
 284 NEW CANAAN AVE
 NORWALK, CT 06850

SHEET TITLE
 LEGEND AND ABBREVIATIONS

SHEET NUMBER
GN-1

SIGN TYPES		
TYPE	COLOR	COLOR CODE PURPOSE
INFORMATION	GREEN	"INFORMATIONAL SIGN" TO NOTIFY OTHERS OF SITE OWNERSHIP & CONTACT NUMBER AND POTENTIAL RF EXPOSURE.
NOTICE	BLUE	"NOTICE BEYOND THIS POINT" RF FIELDS BEYOND THIS POINT MAY EXCEED THE FCC GENERAL PUBLIC EXPOSURE LIMIT. OBEY ALL POSTED SIGNS AND SITE GUIDELINES FOR WORKING IN RF ENVIRONMENTS. IN ACCORDANCE WITH FEDERAL COMMUNICATIONS COMMISSION RULES ON RADIO FREQUENCY EMISSIONS 47 CFR-1.1307(b)
CAUTION	YELLOW	"CAUTION BEYOND THIS POINT" RF FIELDS BEYOND THIS POINT MAY EXCEED THE FCC GENERAL PUBLIC EXPOSURE LIMIT. OBEY ALL POSTED SIGNS AND SITE GUIDELINES FOR WORKING IN RF ENVIRONMENTS. IN ACCORDANCE WITH FEDERAL COMMUNICATIONS COMMISSION RULES ON RADIO FREQUENCY EMISSIONS 47 CFR-1.1307(b)
WARNING	ORANGE/RED	"WARNING BEYOND THIS POINT" RF FIELDS AT THIS SITE EXCEED FCC RULES FOR HUMAN EXPOSURE. FAILURE TO OBEY ALL POSTED SIGNS AND SITE GUIDELINES FOR WORKING IN RF ENVIRONMENTS COULD RESULT IN SERIOUS INJURY. IN ACCORDANCE WITH FEDERAL COMMUNICATIONS COMMISSION RULES ON RADIO FREQUENCY EMISSIONS 47 CFR-1.1307(b)

SIGN PLACEMENT:

- RF SIGNAGE PLACEMENT SHALL FOLLOW THE RECOMMENDATIONS OF AN EXISTING EME REPORT, CREATED BY A THIRD PARTY PREVIOUSLY AUTHORIZED BY DISH Wireless L.L.C.
- INFORMATION SIGN (GREEN) SHALL BE LOCATED ON EXISTING DISH Wireless L.L.C. EQUIPMENT.
 - A) IF THE INFORMATION SIGN IS A STICKER, IT SHALL BE PLACED ON EXISTING DISH Wireless L.L.C. EQUIPMENT CABINET.
 - B) IF THE INFORMATION SIGN IS A METAL SIGN IT SHALL BE PLACED ON EXISTING DISH Wireless L.L.C. H-FRAME WITH A SECURE ATTACH METHOD.
- IF EME REPORT IS NOT AVAILABLE AT THE TIME OF CREATION OF CONSTRUCTION DOCUMENTS; PLEASE CONTACT DISH Wireless L.L.C. CONSTRUCTION MANAGER FOR FURTHER INSTRUCTION ON HOW TO PROCEED.

NOTES:


1. FOR DISH Wireless L.L.C. LOGO, SEE DISH Wireless L.L.C. DESIGN SPECIFICATIONS (PROVIDED BY DISH Wireless L.L.C.)
2. SITE ID SHALL BE APPLIED TO SIGNS USING "LASER ENGRAVING" OR ANY OTHER WEATHER RESISTANT METHOD (DISH Wireless L.L.C. APPROVAL REQUIRED)
3. TEXT FOR SIGNAGE SHALL INDICATE CORRECT SITE NAME AND NUMBER AS PER DISH Wireless L.L.C. CONSTRUCTION MANAGER RECOMMENDATIONS.
4. CABINET/SHELTER MOUNTING APPLICATION REQUIRES ANOTHER PLATE APPLIED TO THE FACE OF THE CABINET WITH WATER PROOF POLYURETHANE ADHESIVE
5. ALL SIGNS WILL BE SECURED WITH EITHER STAINLESS STEEL ZIP TIES OR STAINLESS STEEL TECH SCREWS
6. ALL SIGNS TO BE 8.5"x11" AND MADE WITH 0.04" OF ALUMINUM MATERIAL

INFORMATION

This is an access point to an area with transmitting antennas.

Obey all signs and barriers beyond this point.
Call the DISH Wireless L.L.C. NOC at 1-866-624-6874

Site ID: _____




THIS SIGN IS FOR REFERENCE PURPOSES ONLY



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



140 BEACH 137TH STREET
ROCKAWAY, NY 11694



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: GIN
CHECKED BY: ---
APPROVED BY: ---

RFDS REV #: ---

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/21/2022	ISSUED FOR REVIEW
0	12/22/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER
FA 10113256

DISH Wireless L.L.C.
PROJECT INFORMATION
NJJER02030A
284 NEW CANAAN AVE
NORWALK, CT 06850

SHEET TITLE
RF
SIGNAGE

SHEET NUMBER
GN-2

NOTICE



Transmitting Antenna(s)

Radio frequency fields beyond this point **MAY EXCEED** the FCC Occupational exposure limit.

Obey all posted signs and site guidelines for working in radio frequency environments.

Call the DISH Wireless L.L.C. NOC at 1-866-624-6874 prior to working beyond this point.

Site ID: _____



THIS SIGN IS FOR REFERENCE PURPOSES ONLY

CAUTION



Transmitting Antenna(s)

Radio frequency fields beyond this point **MAY EXCEED** the FCC Occupational exposure limit.

Obey all posted signs and site guidelines for working in radio frequency environments.

Call the DISH Wireless L.L.C. NOC at 1-866-624-6874 prior to working beyond this point.

Site ID: _____



THIS SIGN IS FOR REFERENCE PURPOSES ONLY

WARNING



Transmitting Antenna(s)

Radio frequency fields beyond this point **EXCEED** the FCC Occupational exposure limit.

Obey all posted signs and site guidelines for working in radio frequency environments.

Call the DISH Wireless L.L.C. NOC at 1-866-624-6874 prior to working beyond this point.

Site ID: _____



THIS SIGN IS FOR REFERENCE PURPOSES ONLY

RF SIGNAGE

SITE ACTIVITY REQUIREMENTS:

1. NOTICE TO PROCEED – NO WORK SHALL COMMENCE PRIOR TO CONTRACTOR RECEIVING A WRITTEN NOTICE TO PROCEED (NTP) AND THE ISSUANCE OF A PURCHASE ORDER. PRIOR TO ACCESSING/ENTERING THE SITE YOU MUST CONTACT THE DISH Wireless L.L.C. AND TOWER OWNER NOC & THE DISH Wireless L.L.C. AND TOWER OWNER CONSTRUCTION MANAGER.
2. "LOOK UP" – DISH Wireless L.L.C. AND TOWER OWNER SAFETY CLIMB REQUIREMENT:
THE INTEGRITY OF THE SAFETY CLIMB AND ALL COMPONENTS OF THE CLIMBING FACILITY SHALL BE CONSIDERED DURING ALL STAGES OF DESIGN, INSTALLATION, AND INSPECTION. TOWER MODIFICATION, MOUNT REINFORCEMENTS, AND/OR EQUIPMENT INSTALLATIONS SHALL NOT COMPROMISE THE INTEGRITY OR FUNCTIONAL USE OF THE SAFETY CLIMB OR ANY COMPONENTS OF THE CLIMBING FACILITY ON THE STRUCTURE. THIS SHALL INCLUDE, BUT NOT BE LIMITED TO: PINCHING OF THE WIRE ROPE, BENDING OF THE WIRE ROPE FROM ITS SUPPORTS, DIRECT CONTACT OR CLOSE PROXIMITY TO THE WIRE ROPE WHICH MAY CAUSE FRICTIONAL WEAR, IMPACT TO THE ANCHORAGE POINTS IN ANY WAY, OR TO IMPEDE/BLOCK ITS INTENDED USE. ANY COMPROMISED SAFETY CLIMB, INCLUDING EXISTING CONDITIONS MUST BE TAGGED OUT AND REPORTED TO YOUR DISH Wireless L.L.C. AND DISH Wireless L.L.C. AND TOWER OWNER POC OR CALL THE NOC TO GENERATE A SAFETY CLIMB MAINTENANCE AND CONTRACTOR NOTICE TICKET.
3. PRIOR TO THE START OF CONSTRUCTION, ALL REQUIRED JURISDICTIONAL PERMITS SHALL BE OBTAINED. THIS INCLUDES, BUT IS NOT LIMITED TO, BUILDING, ELECTRICAL, MECHANICAL, FIRE, FLOOD ZONE, ENVIRONMENTAL, AND ZONING. AFTER ONSITE ACTIVITIES AND CONSTRUCTION ARE COMPLETED, ALL REQUIRED PERMITS SHALL BE SATISFIED AND CLOSED OUT ACCORDING TO LOCAL JURISDICTIONAL REQUIREMENTS.
4. ALL CONSTRUCTION MEANS AND METHODS; INCLUDING BUT NOT LIMITED TO, ERECTION PLANS, RIGGING PLANS, CLIMBING PLANS, AND RESCUE PLANS SHALL BE THE RESPONSIBILITY OF THE GENERAL CONTRACTOR RESPONSIBLE FOR THE EXECUTION OF THE WORK CONTAINED HEREIN, AND SHALL MEET ANSI/ASSE A10.48 (LATEST EDITION); FEDERAL, STATE, AND LOCAL REGULATIONS; AND ANY APPLICABLE INDUSTRY CONSENSUS STANDARDS RELATED TO THE CONSTRUCTION ACTIVITIES BEING PERFORMED. ALL RIGGING PLANS SHALL ADHERE TO ANSI/ASSE A10.48 (LATEST EDITION) AND DISH Wireless L.L.C. AND TOWER OWNER STANDARDS, INCLUDING THE REQUIRED INVOLVEMENT OF A QUALIFIED ENGINEER FOR CLASS IV CONSTRUCTION, TO CERTIFY THE SUPPORTING STRUCTURE(S) IN ACCORDANCE WITH ANSI/TIA-322 (LATEST EDITION).
5. ALL SITE WORK TO COMPLY WITH DISH Wireless L.L.C. AND TOWER OWNER INSTALLATION STANDARDS FOR CONSTRUCTION ACTIVITIES ON DISH Wireless L.L.C. AND TOWER OWNER TOWER SITE AND LATEST VERSION OF ANSI/TIA-1019-A-2012 "STANDARD FOR INSTALLATION, ALTERATION, AND MAINTENANCE OF ANTENNA SUPPORTING STRUCTURES AND ANTENNAS."
6. IF THE SPECIFIED EQUIPMENT CAN NOT BE INSTALLED AS SHOWN ON THESE DRAWINGS, THE CONTRACTOR SHALL PROPOSE AN ALTERNATIVE INSTALLATION FOR APPROVAL BY DISH Wireless L.L.C. AND TOWER OWNER PRIOR TO PROCEEDING WITH ANY SUCH CHANGE OF INSTALLATION.
7. ALL MATERIALS FURNISHED AND INSTALLED SHALL BE IN STRICT ACCORDANCE WITH ALL APPLICABLE CODES, REGULATIONS AND ORDINANCES. CONTRACTOR SHALL ISSUE ALL APPROPRIATE NOTICES AND COMPLY WITH ALL LAWS, ORDINANCES, RULES, REGULATIONS AND LAWFUL ORDERS OF ANY PUBLIC AUTHORITY REGARDING THE PERFORMANCE OF THE WORK. ALL WORK CARRIED OUT SHALL COMPLY WITH ALL APPLICABLE MUNICIPAL AND UTILITY COMPANY SPECIFICATIONS AND LOCAL JURISDICTIONAL CODES, ORDINANCES AND APPLICABLE REGULATIONS.
8. THE CONTRACTOR SHALL INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS UNLESS SPECIFICALLY STATED OTHERWISE.
9. THE CONTRACTOR SHALL CONTACT UTILITY LOCATING SERVICES INCLUDING PRIVATE LOCATES SERVICES PRIOR TO THE START OF CONSTRUCTION.
10. ALL EXISTING ACTIVE SEWER, WATER, GAS, ELECTRIC AND OTHER UTILITIES WHERE ENCOUNTERED IN THE WORK, SHALL BE PROTECTED AT ALL TIMES AND WHERE REQUIRED FOR THE PROPER EXECUTION OF THE WORK, SHALL BE RELOCATED AS DIRECTED BY CONTRACTOR. EXTREME CAUTION SHOULD BE USED BY THE CONTRACTOR WHEN EXCAVATING OR DRILLING PIERS AROUND OR NEAR UTILITIES. CONTRACTOR SHALL PROVIDE SAFETY TRAINING FOR THE WORKING CREW. THIS WILL INCLUDE BUT NOT BE LIMITED TO A) FALL PROTECTION B) CONFINED SPACE C) ELECTRICAL SAFETY D) TRENCHING AND EXCAVATION E) CONSTRUCTION SAFETY PROCEDURES.
11. ALL SITE WORK SHALL BE AS INDICATED ON THE STAMPED CONSTRUCTION DRAWINGS AND DISH PROJECT SPECIFICATIONS, LATEST APPROVED REVISION.
12. CONTRACTOR SHALL KEEP THE SITE FREE FROM ACCUMULATING WASTE MATERIAL, DEBRIS, AND TRASH AT THE COMPLETION OF THE WORK. IF NECESSARY, RUBBISH, STUMPS, DEBRIS, STICKS, STONES AND OTHER REFUSE SHALL BE REMOVED FROM THE SITE AND DISPOSED OF LEGALLY.
13. ALL EXISTING INACTIVE SEWER, WATER, GAS, ELECTRIC AND OTHER UTILITIES, WHICH INTERFERE WITH THE EXECUTION OF THE WORK, SHALL BE REMOVED AND/OR CAPPED, PLUGGED OR OTHERWISE DISCONTINUED AT POINTS WHICH WILL NOT INTERFERE WITH THE EXECUTION OF THE WORK, SUBJECT TO THE APPROVAL OF DISH Wireless L.L.C. AND TOWER OWNER, AND/OR LOCAL UTILITIES.
14. THE CONTRACTOR SHALL PROVIDE SITE SIGNAGE IN ACCORDANCE WITH THE TECHNICAL SPECIFICATION FOR SITE SIGNAGE REQUIRED BY LOCAL JURISDICTION AND SIGNAGE REQUIRED ON INDIVIDUAL PIECES OF EQUIPMENT, ROOMS, AND SHELTERS.
15. THE SITE SHALL BE GRADED TO CAUSE SURFACE WATER TO FLOW AWAY FROM THE CARRIER'S EQUIPMENT AND TOWER AREAS.
16. THE SUB GRADE SHALL BE COMPACTED AND BROUGHT TO A SMOOTH UNIFORM GRADE PRIOR TO FINISHED SURFACE APPLICATION.
17. THE AREAS OF THE OWNERS PROPERTY DISTURBED BY THE WORK AND NOT COVERED BY THE TOWER, EQUIPMENT OR DRIVEWAY, SHALL BE GRADED TO A UNIFORM SLOPE, AND STABILIZED TO PREVENT EROSION AS SPECIFIED ON THE CONSTRUCTION DRAWINGS AND/OR PROJECT SPECIFICATIONS.
18. CONTRACTOR SHALL MINIMIZE DISTURBANCE TO EXISTING SITE DURING CONSTRUCTION. EROSION CONTROL MEASURES, IF REQUIRED DURING CONSTRUCTION, SHALL BE IN CONFORMANCE WITH THE LOCAL GUIDELINES FOR EROSION AND SEDIMENT CONTROL.
19. THE CONTRACTOR SHALL PROTECT EXISTING IMPROVEMENTS, PAVEMENTS, CURBS, LANDSCAPING AND STRUCTURES. ANY DAMAGED PART SHALL BE REPAIRED AT CONTRACTOR'S EXPENSE TO THE SATISFACTION OF OWNER.
20. CONTRACTOR SHALL LEGALLY AND PROPERLY DISPOSE OF ALL SCRAP MATERIALS SUCH AS COAXIAL CABLES AND OTHER ITEMS REMOVED FROM THE EXISTING FACILITY. ANTENNAS AND RADIOS REMOVED SHALL BE RETURNED TO THE OWNER'S DESIGNATED LOCATION.
21. CONTRACTOR SHALL LEAVE PREMISES IN CLEAN CONDITION. TRASH AND DEBRIS SHOULD BE REMOVED FROM SITE ON A DAILY BASIS.
22. NO FILL OR EMBANKMENT MATERIAL SHALL BE PLACED ON FROZEN GROUND. FROZEN MATERIALS, SNOW OR ICE SHALL NOT BE PLACED IN ANY FILL OR EMBANKMENT.

GENERAL NOTES:

1. FOR THE PURPOSE OF CONSTRUCTION DRAWING, THE FOLLOWING DEFINITIONS SHALL APPLY:
CONTRACTOR: GENERAL CONTRACTOR RESPONSIBLE FOR CONSTRUCTION
CARRIER: DISH Wireless L.L.C.
TOWER OWNER: TOWER OWNER
2. THESE DRAWINGS HAVE BEEN PREPARED USING STANDARDS OF PROFESSIONAL CARE AND COMPLETENESS NORMALLY EXERCISED UNDER SIMILAR CIRCUMSTANCES BY REPUTABLE ENGINEERS IN THIS OR SIMILAR LOCALITIES. IT IS ASSUMED THAT THE WORK DEPICTED WILL BE PERFORMED BY AN EXPERIENCED CONTRACTOR AND/OR WORKPEOPLE WHO HAVE A WORKING KNOWLEDGE OF THE APPLICABLE CODE STANDARDS AND REQUIREMENTS AND OF INDUSTRY ACCEPTED STANDARD GOOD PRACTICE. AS NOT EVERY CONDITION OR ELEMENT IS (OR CAN BE) EXPLICITLY SHOWN ON THESE DRAWINGS, THE CONTRACTOR SHALL USE INDUSTRY ACCEPTED STANDARD GOOD PRACTICE FOR MISCELLANEOUS WORK NOT EXPLICITLY SHOWN.
3. THESE DRAWINGS REPRESENT THE FINISHED STRUCTURE. THEY DO NOT INDICATE THE MEANS OR METHODS OF CONSTRUCTION. THE CONTRACTOR SHALL BE SOLELY RESPONSIBLE FOR THE CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES, AND PROCEDURES. THE CONTRACTOR SHALL PROVIDE ALL MEASURES NECESSARY FOR PROTECTION OF LIFE AND PROPERTY DURING CONSTRUCTION. SUCH MEASURES SHALL INCLUDE, BUT NOT BE LIMITED TO, BRACING, FORMWORK, SHORING, ETC. SITE VISITS BY THE ENGINEER OR HIS REPRESENTATIVE WILL NOT INCLUDE INSPECTION OF THESE ITEMS AND IS FOR STRUCTURAL OBSERVATION OF THE FINISHED STRUCTURE ONLY.
4. NOTES AND DETAILS IN THE CONSTRUCTION DRAWINGS SHALL TAKE PRECEDENCE OVER GENERAL NOTES AND TYPICAL DETAILS. WHERE NO DETAILS ARE SHOWN, CONSTRUCTION SHALL CONFORM TO SIMILAR WORK ON THE PROJECT, AND/OR AS PROVIDED FOR IN THE CONTRACT DOCUMENTS. WHERE DISCREPANCIES OCCUR BETWEEN PLANS, DETAILS, GENERAL NOTES, AND SPECIFICATIONS, THE GREATER, MORE STRICT REQUIREMENTS, SHALL GOVERN. IF FURTHER CLARIFICATION IS REQUIRED CONTACT THE ENGINEER OF RECORD.
5. SUBSTANTIAL EFFORT HAS BEEN MADE TO PROVIDE ACCURATE DIMENSIONS AND MEASUREMENTS ON THE DRAWINGS TO ASSIST IN THE FABRICATION AND/OR PLACEMENT OF CONSTRUCTION ELEMENTS BUT IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO FIELD VERIFY THE DIMENSIONS, MEASUREMENTS, AND/OR CLEARANCES SHOWN IN THE CONSTRUCTION DRAWINGS PRIOR TO FABRICATION OR CUTTING OF ANY NEW OR EXISTING CONSTRUCTION ELEMENTS. IF IT IS DETERMINED THAT THERE ARE DISCREPANCIES AND/OR CONFLICTS WITH THE CONSTRUCTION DRAWINGS THE ENGINEER OF RECORD IS TO BE NOTIFIED AS SOON AS POSSIBLE.
6. PRIOR TO THE SUBMISSION OF BIDS, THE BIDDING CONTRACTOR SHALL VISIT THE CELL SITE TO FAMILIARIZE WITH THE EXISTING CONDITIONS AND TO CONFIRM THAT THE WORK CAN BE ACCOMPLISHED AS SHOWN ON THE CONSTRUCTION DRAWINGS. ANY DISCREPANCY FOUND SHALL BE BROUGHT TO THE ATTENTION OF CARRIER POC AND TOWER OWNER.
7. ALL MATERIALS FURNISHED AND INSTALLED SHALL BE IN STRICT ACCORDANCE WITH ALL APPLICABLE CODES, REGULATIONS AND ORDINANCES. CONTRACTOR SHALL ISSUE ALL APPROPRIATE NOTICES AND COMPLY WITH ALL LAWS, ORDINANCES, RULES, REGULATIONS AND LAWFUL ORDERS OF ANY PUBLIC AUTHORITY REGARDING THE PERFORMANCE OF THE WORK. ALL WORK CARRIED OUT SHALL COMPLY WITH ALL APPLICABLE MUNICIPAL AND UTILITY COMPANY SPECIFICATIONS AND LOCAL JURISDICTIONAL CODES, ORDINANCES AND APPLICABLE REGULATIONS.
8. UNLESS NOTED OTHERWISE, THE WORK SHALL INCLUDE FURNISHING MATERIALS, EQUIPMENT, APPURTENANCES AND LABOR NECESSARY TO COMPLETE ALL INSTALLATIONS AS INDICATED ON THE DRAWINGS.
9. THE CONTRACTOR SHALL INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS UNLESS SPECIFICALLY STATED OTHERWISE.
10. IF THE SPECIFIED EQUIPMENT CAN NOT BE INSTALLED AS SHOWN ON THESE DRAWINGS, THE CONTRACTOR SHALL PROPOSE AN ALTERNATIVE INSTALLATION FOR APPROVAL BY THE CARRIER AND TOWER OWNER PRIOR TO PROCEEDING WITH ANY SUCH CHANGE OF INSTALLATION.
11. CONTRACTOR IS TO PERFORM A SITE INVESTIGATION, BEFORE SUBMITTING BIDS, TO DETERMINE THE BEST ROUTING OF ALL CONDUITS FOR POWER, AND TELCO AND FOR GROUNDING CABLES AS SHOWN IN THE POWER, TELCO, AND GROUNDING PLAN DRAWINGS.
12. THE CONTRACTOR SHALL PROTECT EXISTING IMPROVEMENTS, PAVEMENTS, CURBS, LANDSCAPING AND STRUCTURES. ANY DAMAGED PART SHALL BE REPAIRED AT CONTRACTOR'S EXPENSE TO THE SATISFACTION OF DISH Wireless L.L.C. AND TOWER OWNER
13. CONTRACTOR SHALL LEGALLY AND PROPERLY DISPOSE OF ALL SCRAP MATERIALS SUCH AS COAXIAL CABLES AND OTHER ITEMS REMOVED FROM THE EXISTING FACILITY. ANTENNAS REMOVED SHALL BE RETURNED TO THE OWNER'S DESIGNATED LOCATION.
14. CONTRACTOR SHALL LEAVE PREMISES IN CLEAN CONDITION. TRASH AND DEBRIS SHOULD BE REMOVED FROM SITE ON A DAILY BASIS.



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
GIN	---	---
RFDS REV #:	---	

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/21/2022	ISSUED FOR REVIEW
0	12/22/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER
FA 10113256

DISH Wireless L.L.C.
PROJECT INFORMATION
NJJER02030A
284 NEW CANAAN AVE
NORWALK, CT 06850

SHEET TITLE
GENERAL NOTES

SHEET NUMBER
GN-3

CONCRETE, FOUNDATIONS, AND REINFORCING STEEL:

- ALL CONCRETE WORK SHALL BE IN ACCORDANCE WITH THE ACI 301, ACI 318, ACI 336, ASTM A184, ASTM A185 AND THE DESIGN AND CONSTRUCTION SPECIFICATION FOR CAST-IN-PLACE CONCRETE.
- UNLESS NOTED OTHERWISE, SOIL BEARING PRESSURE USED FOR DESIGN OF SLABS AND FOUNDATIONS IS ASSUMED TO BE 1000 psf.
- ALL CONCRETE SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH (f'c) OF 3000 psi AT 28 DAYS, UNLESS NOTED OTHERWISE. NO MORE THAN 90 MINUTES SHALL ELAPSE FROM BATCH TIME TO TIME OF PLACEMENT UNLESS APPROVED BY THE ENGINEER OF RECORD. TEMPERATURE OF CONCRETE SHALL NOT EXCEED 90°F AT TIME OF PLACEMENT.
- CONCRETE EXPOSED TO FREEZE-THAW CYCLES SHALL CONTAIN AIR ENTRAINING ADMIXTURES. AMOUNT OF AIR ENTRAINMENT TO BE BASED ON SIZE OF AGGREGATE AND F3 CLASS EXPOSURE (VERY SEVERE). CEMENT USED TO BE TYPE II PORTLAND CEMENT WITH A MAXIMUM WATER-TO-CEMENT RATIO (W/C) OF 0.45.
- ALL STEEL REINFORCING SHALL CONFORM TO ASTM A615. ALL WELDED WIRE FABRIC (WWF) SHALL CONFORM TO ASTM A185. ALL SPLICES SHALL BE CLASS "B" TENSION SPLICES, UNLESS NOTED OTHERWISE. ALL HOOKS SHALL BE STANDARD 90 DEGREE HOOKS, UNLESS NOTED OTHERWISE. YIELD STRENGTH (Fy) OF STANDARD DEFORMED BARS ARE AS FOLLOWS:
 #4 BARS AND SMALLER 40 ksi
 #5 BARS AND LARGER 60 ksi
- THE FOLLOWING MINIMUM CONCRETE COVER SHALL BE PROVIDED FOR REINFORCING STEEL UNLESS SHOWN OTHERWISE ON DRAWINGS:
 - CONCRETE CAST AGAINST AND PERMANENTLY EXPOSED TO EARTH 3"
 - CONCRETE EXPOSED TO EARTH OR WEATHER:
 - #6 BARS AND LARGER 2"
 - #5 BARS AND SMALLER 1-1/2"
 - CONCRETE NOT EXPOSED TO EARTH OR WEATHER:
 - SLAB AND WALLS 3/4"
 - BEAMS AND COLUMNS 1-1/2"
- A TOOLED EDGE OR A 3/4" CHAMFER SHALL BE PROVIDED AT ALL EXPOSED EDGES OF CONCRETE, UNLESS NOTED OTHERWISE, IN ACCORDANCE WITH ACI 301 SECTION 4.2.4.

ELECTRICAL INSTALLATION NOTES:

- ALL ELECTRICAL WORK SHALL BE PERFORMED IN ACCORDANCE WITH THE PROJECT SPECIFICATIONS, NEC AND ALL APPLICABLE FEDERAL, STATE, AND LOCAL CODES/ORDINANCES.
- CONDUIT ROUTINGS ARE SCHEMATIC. CONTRACTOR SHALL INSTALL CONDUITS SO THAT ACCESS TO EQUIPMENT IS NOT BLOCKED AND TRIP HAZARDS ARE ELIMINATED.
- WIRING, RACEWAY AND SUPPORT METHODS AND MATERIALS SHALL COMPLY WITH THE REQUIREMENTS OF THE NEC.
- ALL CIRCUITS SHALL BE SEGREGATED AND MAINTAIN MINIMUM CABLE SEPARATION AS REQUIRED BY THE NEC.
 - ALL EQUIPMENT SHALL BEAR THE UNDERWRITERS LABORATORIES LABEL OF APPROVAL, AND SHALL CONFORM TO REQUIREMENT OF THE NATIONAL ELECTRICAL CODE.
 - ALL OVERCURRENT DEVICES SHALL HAVE AN INTERRUPTING CURRENT RATING THAT SHALL BE GREATER THAN THE SHORT CIRCUIT CURRENT TO WHICH THEY ARE SUBJECTED, 22,000 AIC MINIMUM. VERIFY AVAILABLE SHORT CIRCUIT CURRENT DOES NOT EXCEED THE RATING OF ELECTRICAL EQUIPMENT IN ACCORDANCE WITH ARTICLE 110.24 NEC OR THE MOST CURRENT ADOPTED CODE PRE THE GOVERNING JURISDICTION.
- EACH END OF EVERY POWER PHASE CONDUCTOR, GROUNDING CONDUCTOR, AND TELCO CONDUCTOR OR CABLE SHALL BE LABELED WITH COLOR-CODED INSULATION OR ELECTRICAL TAPE (3M BRAND, 1/2" PLASTIC ELECTRICAL TAPE WITH UV PROTECTION, OR EQUAL). THE IDENTIFICATION METHOD SHALL CONFORM WITH NEC AND OSHA.
- ALL ELECTRICAL COMPONENTS SHALL BE CLEARLY LABELED WITH LAMICOID TAGS SHOWING THEIR RATED VOLTAGE, PHASE CONFIGURATION, WIRE CONFIGURATION, POWER OR AMPACITY RATING AND BRANCH CIRCUIT ID NUMBERS (i.e. PANEL BOARD AND CIRCUIT ID'S).
- PANEL BOARDS (ID NUMBERS) SHALL BE CLEARLY LABELED WITH PLASTIC LABELS.
- TIE WRAPS ARE NOT ALLOWED.
- ALL POWER AND EQUIPMENT GROUND WIRING IN TUBING OR CONDUIT SHALL BE SINGLE COPPER CONDUCTOR (#14 OR LARGER) WITH TYPE THHW, THWN, THWN-2, XHHW, XHHW-2, THW, THW-2, RHW, OR RHW-2 INSULATION UNLESS OTHERWISE SPECIFIED.
- SUPPLEMENTAL EQUIPMENT GROUND WIRING LOCATED INDOORS SHALL BE SINGLE COPPER CONDUCTOR (#6 OR LARGER) WITH TYPE THHW, THWN, THWN-2, XHHW, XHHW-2, THW, THW-2, RHW, OR RHW-2 INSULATION UNLESS OTHERWISE SPECIFIED.
- POWER AND CONTROL WIRING IN FLEXIBLE CORD SHALL BE MULTI-CONDUCTOR, TYPE SOOW CORD (#14 OR LARGER) UNLESS OTHERWISE SPECIFIED.
- POWER AND CONTROL WIRING FOR USE IN CABLE TRAY SHALL BE MULTI-CONDUCTOR, TYPE TC CABLE (#14 OR LARGER), WITH TYPE THHW, THWN, THWN-2, XHHW, XHHW-2, THW, THW-2, RHW, OR RHW-2 INSULATION UNLESS OTHERWISE SPECIFIED.
- ALL POWER AND GROUNDING CONNECTIONS SHALL BE CRIMP-STYLE, COMPRESSION WIRE LUGS AND WIRE NUTS BY THOMAS AND BETTS (OR EQUAL). LUGS AND WIRE NUTS SHALL BE RATED FOR OPERATION NOT LESS THAN 75° C (90° C IF AVAILABLE).
- RACEWAY AND CABLE TRAY SHALL BE LISTED OR LABELED FOR ELECTRICAL USE IN ACCORDANCE WITH NEMA, UL, ANSI/IEEE AND NEC.
- ELECTRICAL METALLIC TUBING (EMT), INTERMEDIATE METAL CONDUIT (IMC), OR RIGID METAL CONDUIT (RMC) SHALL BE USED FOR EXPOSED INDOOR LOCATIONS.

- ELECTRICAL METALLIC TUBING (EMT) OR METAL-CLAD CABLE (MC) SHALL BE USED FOR CONCEALED INDOOR LOCATIONS.
- SCHEDULE 40 PVC UNDERGROUND ON STRAIGHTS AND SCHEDULE 80 PVC FOR ALL ELBOWS/90s AND ALL APPROVED ABOVE GRADE PVC CONDUIT.
- LIQUID-TIGHT FLEXIBLE METALLIC CONDUIT (LIQUID-TITE FLEX) SHALL BE USED INDOORS AND OUTDOORS, WHERE VIBRATION OCCURS OR FLEXIBILITY IS NEEDED.
- CONDUIT AND TUBING FITTINGS SHALL BE THREADED OR COMPRESSION-TYPE AND APPROVED FOR THE LOCATION USED. SET SCREW FITTINGS ARE NOT ACCEPTABLE.
- CABINETS, BOXES AND WIRE WAYS SHALL BE LABELED FOR ELECTRICAL USE IN ACCORDANCE WITH NEMA, UL, ANSI/IEEE AND THE NEC.
- WIREWAYS SHALL BE METAL WITH AN ENAMEL FINISH AND INCLUDE A HINGED COVER, DESIGNED TO SWING OPEN DOWNWARDS (WIREMOLD SPECMATE WIREWAY).
- SLOTTED WIRING DUCT SHALL BE PVC AND INCLUDE COVER (PANDUIT TYPE E OR EQUAL).
- CONDUITS SHALL BE FASTENED SECURELY IN PLACE WITH APPROVED NON-PERFORATED STRAPS AND HANGERS. EXPLOSIVE DEVICES (i.e. POWDER-ACTUATED) FOR ATTACHING HANGERS TO STRUCTURE WILL NOT BE PERMITTED. CLOSELY FOLLOW THE LINES OF THE STRUCTURE, MAINTAIN CLOSE PROXIMITY TO THE STRUCTURE AND KEEP CONDUITS IN TIGHT ENVELOPES. CHANGES IN DIRECTION TO ROUTE AROUND OBSTACLES SHALL BE MADE WITH CONDUIT OUTLET BODIES. CONDUIT SHALL BE INSTALLED IN A NEAT AND WORKMANLIKE MANNER. PARALLEL AND PERPENDICULAR TO STRUCTURE WALL AND CEILING LINES. ALL CONDUIT SHALL BE FISHED TO CLEAR OBSTRUCTIONS. ENDS OF CONDUITS SHALL BE TEMPORARILY CAPPED FLUSH TO FINISH GRADE TO PREVENT CONCRETE, PLASTER OR DIRT FROM ENTERING. CONDUITS SHALL BE RIGIDLY CLAMPED TO BOXES BY GALVANIZED MALLEABLE IRON BUSHING ON INSIDE AND GALVANIZED MALLEABLE IRON LOCKNUT ON OUTSIDE AND INSIDE.
- EQUIPMENT CABINETS, TERMINAL BOXES, JUNCTION BOXES AND PULL BOXES SHALL BE GALVANIZED OR EPOXY-COATED SHEET STEEL. SHALL MEET OR EXCEED UL 50 AND BE RATED NEMA 1 (OR BETTER) FOR INTERIOR LOCATIONS AND NEMA 3 (OR BETTER) FOR EXTERIOR LOCATIONS.
- METAL RECEPTACLE, SWITCH AND DEVICE BOXES SHALL BE GALVANIZED, EPOXY-COATED OR NON-CORRODING; SHALL MEET OR EXCEED UL 514A AND NEMA OS 1 AND BE RATED NEMA 1 (OR BETTER) FOR INTERIOR LOCATIONS AND WEATHER PROTECTED (WP OR BETTER) FOR EXTERIOR LOCATIONS.
- NONMETALLIC RECEPTACLE, SWITCH AND DEVICE BOXES SHALL MEET OR EXCEED NEMA OS 2 (NEWEST REVISION) AND BE RATED NEMA 1 (OR BETTER) FOR INTERIOR LOCATIONS AND WEATHER PROTECTED (WP OR BETTER) FOR EXTERIOR LOCATIONS.
- THE CONTRACTOR SHALL NOTIFY AND OBTAIN NECESSARY AUTHORIZATION FROM THE CARRIER AND/OR DISH Wireless L.L.C. AND TOWER OWNER BEFORE COMMENCING WORK ON THE AC POWER DISTRIBUTION PANELS.
- THE CONTRACTOR SHALL PROVIDE NECESSARY TAGGING ON THE BREAKERS, CABLES AND DISTRIBUTION PANELS IN ACCORDANCE WITH THE APPLICABLE CODES AND STANDARDS TO SAFEGUARD LIFE AND PROPERTY.
- INSTALL LAMICOID LABEL ON THE METER CENTER TO SHOW "DISH Wireless L.L.C."
- ALL EMPTY/SPARE CONDUITS THAT ARE INSTALLED ARE TO HAVE A METERED MULE TAPE PULL CORD INSTALLED.



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY:	CHECKED BY:	APPROVED BY:
GIN	---	---
RFDS REV #:	---	

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/21/2022	ISSUED FOR REVIEW
0	12/22/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER
FA 10113256

DISH Wireless L.L.C.
PROJECT INFORMATION
NJJER02030A
284 NEW CANAAN AVE
NORWALK, CT 06850

SHEET TITLE
GENERAL NOTES

SHEET NUMBER
GN-4

GROUNDING NOTES:


1. ALL GROUND ELECTRODE SYSTEMS (INCLUDING TELECOMMUNICATION, RADIO, LIGHTNING PROTECTION AND AC POWER GES'S) SHALL BE BONDED TOGETHER AT OR BELOW GRADE, BY TWO OR MORE COPPER BONDING CONDUCTORS IN ACCORDANCE WITH THE NEC.
2. THE CONTRACTOR SHALL PERFORM IEEE FALL-OF-POTENTIAL RESISTANCE TO EARTH TESTING (PER IEEE 1100 AND 81) FOR GROUND ELECTRODE SYSTEMS, THE CONTRACTOR SHALL FURNISH AND INSTALL SUPPLEMENTAL GROUND ELECTRODES AS NEEDED TO ACHIEVE A TEST RESULT OF 5 OHMS OR LESS.
3. THE CONTRACTOR IS RESPONSIBLE FOR PROPERLY SEQUENCING GROUNDING AND UNDERGROUND CONDUIT INSTALLATION AS TO PREVENT ANY LOSS OF CONTINUITY IN THE GROUNDING SYSTEM OR DAMAGE TO THE CONDUIT AND PROVIDE TESTING RESULTS.
4. METAL CONDUIT AND TRAY SHALL BE GROUNDED AND MADE ELECTRICALLY CONTINUOUS WITH LISTED BONDING FITTINGS OR BY BONDING ACROSS THE DISCONTINUITY WITH #6 COPPER WIRE UL APPROVED GROUNDING TYPE CONDUIT CLAMPS.
5. METAL RACEWAY SHALL NOT BE USED AS THE NEC REQUIRED EQUIPMENT GROUND CONDUCTOR. STRANDED COPPER CONDUCTORS WITH GREEN INSULATION, SIZED IN ACCORDANCE WITH THE NEC, SHALL BE FURNISHED AND INSTALLED WITH THE POWER CIRCUITS TO BTS EQUIPMENT.
6. EACH CABINET FRAME SHALL BE DIRECTLY CONNECTED TO THE MASTER GROUND BAR WITH GREEN INSULATED SUPPLEMENTAL EQUIPMENT GROUND WIRES, #6 STRANDED COPPER OR LARGER FOR INDOOR BTS; #2 BARE SOLID TINNED COPPER FOR OUTDOOR BTS.
7. CONNECTIONS TO THE GROUND BUS SHALL NOT BE DOUBLED UP OR STACKED BACK TO BACK CONNECTIONS ON OPPOSITE SIDE OF THE GROUND BUS ARE PERMITTED.
8. ALL EXTERIOR GROUND CONDUCTORS BETWEEN EQUIPMENT/GROUND BARS AND THE GROUND RING SHALL BE #2 SOLID TINNED COPPER UNLESS OTHERWISE INDICATED.
9. ALUMINUM CONDUCTOR OR COPPER CLAD STEEL CONDUCTOR SHALL NOT BE USED FOR GROUNDING CONNECTIONS.
10. USE OF 90° BENDS IN THE PROTECTION GROUNDING CONDUCTORS SHALL BE AVOIDED WHEN 45° BENDS CAN BE ADEQUATELY SUPPORTED.
11. EXOTHERMIC WELDS SHALL BE USED FOR ALL GROUNDING CONNECTIONS BELOW GRADE.
12. ALL GROUND CONNECTIONS ABOVE GRADE (INTERIOR AND EXTERIOR) SHALL BE FORMED USING HIGH PRESS CRIMPS.
13. COMPRESSION GROUND CONNECTIONS MAY BE REPLACED BY EXOTHERMIC WELD CONNECTIONS.
14. ICE BRIDGE BONDING CONDUCTORS SHALL BE EXOTHERMICALLY BONDED OR BOLTED TO THE BRIDGE AND THE TOWER GROUND BAR.
15. APPROVED ANTIOXIDANT COATINGS (i.e. CONDUCTIVE GEL OR PASTE) SHALL BE USED ON ALL COMPRESSION AND BOLTED GROUND CONNECTIONS.
16. ALL EXTERIOR GROUND CONNECTIONS SHALL BE COATED WITH A CORROSION RESISTANT MATERIAL.
17. MISCELLANEOUS ELECTRICAL AND NON-ELECTRICAL METAL BOXES, FRAMES AND SUPPORTS SHALL BE BONDED TO THE GROUND RING, IN ACCORDANCE WITH THE NEC.
18. BOND ALL METALLIC OBJECTS WITHIN 6 ft OF MAIN GROUND RING WITH (1) #2 BARE SOLID TINNED COPPER GROUND CONDUCTOR.
19. GROUND CONDUCTORS USED FOR THE FACILITY GROUNDING AND LIGHTNING PROTECTION SYSTEMS SHALL NOT BE ROUTED THROUGH METALLIC OBJECTS THAT FORM A RING AROUND THE CONDUCTOR, SUCH AS METALLIC CONDUITS, METAL SUPPORT CLIPS OR SLEEVES THROUGH WALLS OR FLOORS. WHEN IT IS REQUIRED TO BE HOUSED IN CONDUIT TO MEET CODE REQUIREMENTS OR LOCAL CONDITIONS, NON-METALLIC MATERIAL SUCH AS PVC CONDUIT SHALL BE USED. WHERE USE OF METAL CONDUIT IS UNAVOIDABLE (i.e., NONMETALLIC CONDUIT PROHIBITED BY LOCAL CODE) THE GROUND CONDUCTOR SHALL BE BONDED TO EACH END OF THE METAL CONDUIT.
20. ALL GROUNDS THAT TRANSITION FROM BELOW GRADE TO ABOVE GRADE MUST BE #2 BARE SOLID TINNED COPPER IN 3/4" NON-METALLIC, FLEXIBLE CONDUIT FROM 24" BELOW GRADE TO WITHIN 3" TO 6" OF CAD-WELD TERMINATION POINT. THE EXPOSED END OF THE CONDUIT MUST BE SEALED WITH SILICONE CAULK. (ADD TRANSITIONING GROUND STANDARD DETAIL AS WELL).
21. BUILDINGS WHERE THE MAIN GROUNDING CONDUCTORS ARE REQUIRED TO BE ROUTED TO GRADE, THE CONTRACTOR SHALL ROUTE TWO GROUNDING CONDUCTORS FROM THE ROOFTOP, TOWERS, AND WATER TOWERS GROUNDING RING, TO THE EXISTING GROUNDING SYSTEM, THE GROUNDING CONDUCTORS SHALL NOT BE SMALLER THAN 2/0 COPPER. ROOFTOP GROUNDING RING SHALL BE BONDED TO THE EXISTING GROUNDING SYSTEM, THE BUILDING STEEL COLUMNS, LIGHTNING PROTECTION SYSTEM, AND BUILDING MAIN WATER LINE (FERROUS OR NONFERROUS METAL PIPING ONLY). DO NOT ATTACH GROUNDING TO FIRE SPRINKLER SYSTEM PIPES.



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



140 BEACH 137TH STREET
ROCKAWAY, NY 11694



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:

GIN --- ---

RFDS REV #: ---

CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV	DATE	DESCRIPTION
A	10/21/2022	ISSUED FOR REVIEW
0	12/22/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER
FA 10113256

DISH Wireless L.L.C.
PROJECT INFORMATION
NJJERO2030A
284 NEW CANAAN AVE
NORWALK, CT 06850

SHEET TITLE
GENERAL NOTES

SHEET NUMBER
GN-5



Amended EXHIBIT E

Structural Analysis



AT&T
2180 Lake Blvd, 5th Floor (5B13)
Brookhaven, GA 30319



GPD Engineering and Architecture
Professional Corporation

Mac Risley
520 South Main Street, Suite 2531
Akron, OH 44311
(678) 781-5067
mrisley@gpdgroup.com

GPD# 2022723.01.105046.01 Rev. 1
January 3, 2023

COMPREHENSIVE STRUCTURAL ANALYSIS REPORT

SITE DESIGNATION: Dish Applicant Site #: **NJJER02030A**
AT&T USID #: **105046**
AT&T Site FA #: **10113256**
AT&T Site Name: **NORWALK CT NEW CANAAN AVE**

ANALYSIS CRITERIA: Codes: **TIA-222-H, 2021 IBC & 2022 CSBC**
117 mph (3-second gust) w/ 0" ice
50 mph (3-second gust) w/ 1" ice
Ss = 0.246, S1 = 0.057

SITE DATA: **284 New Canaan Avenue, Norwalk, CT 6850, Fairfield County**
Latitude 41° 08' 10.10" N, Longitude 73° 27' 23.10" W
Market: NEW ENGLAND
140' Stealth Monopole

To whom it may concern,

GPD is pleased to submit this Comprehensive Structural Analysis Report to determine the structural integrity of the aforementioned tower. The purpose of the analysis is to determine the suitability of the tower with the existing and proposed loading configuration detailed in the analysis report.

Analysis Results

Tower Stress Level with Proposed Equipment:	39.1%	Pass
Foundation Ratio with Proposed Equipment:	23.1%	Pass

We at GPD appreciate the opportunity of providing our continuing professional services to you and AT&T. If you have any questions or need further assistance on this or any other projects, please do not hesitate to call.

Respectfully submitted,




Christopher J. Scheks, P.E.
Connecticut #: 0030026

1/3/2023

SUMMARY & RESULTS

The purpose of this analysis was to verify whether the existing structure is capable of carrying the proposed loading configuration as specified by AT&T Mobility and commissioned by AT&T.

This analysis has been performed in accordance with the 2021 IBC based upon a 3-second gust wind speed of 117 mph. Applicable Standard references and design criteria are listed in Appendices A & B.

The proposed feedlines shall be installed as shown in Appendices A & B for the analysis results to be valid.

TOWER SUMMARY AND RESULTS

Member	Capacity	Results
Monopole	28.5%	Pass
Anchor Rods	24.3%	Pass
Base Plate	39.1%	Pass
Foundation	23.1%	Pass

RECOMMENDATIONS

The tower and its foundation(s) have sufficient capacity to carry the proposed loading configuration. No modifications are required at this time.

ANALYSIS METHOD

tnxTower (Version 8.1.1.0), a commercially available software program, was used to create a three-dimensional model of the tower and calculate primary member stresses for various load cases. Selected output from the analysis is included the report appendices. The following table details the information provided to complete this structural analysis. This analysis is solely based on this information.

DOCUMENTS PROVIDED

Document	Remarks	Source
RF Data Sheet	RFDS Name: CT2200 Rev. 1, updated 5/27/2022	AT&T
AT&T Site Lease Application	Dish Applicant Site #: NJJER02030A, dated 9/29/2021	AT&T
Tower Design	Engineering Endeavors Project #: 17340, dated 10/13/2014	AT&T
Foundation Design	Engineering Endeavors Project #: 17340, dated 10/13/2014	AT&T
Geotechnical Report	Dewberry Site: National Guard Armory-SR1038, dated 4/7/2014	AT&T
Previous Tower Analysis	Not Provided	N/A
Tower Mapping	Not Provided	N/A

ASSUMPTIONS

This structural analysis is based on the theoretical capacity of the members and is not a condition assessment of the tower. This analysis is from information supplied, and therefore, its results are based on and are as accurate as that supplied data. GPD has made no independent determination, nor is it required to, of its accuracy. The following assumptions were made for this structural analysis.

1. The tower member sizes and shapes are considered accurate as supplied. The material grade is as per data supplied and/or as assumed and as stated in the materials section.
2. The appurtenance configuration is as supplied, determined from available photos, and/or as modeled in the analysis. It is assumed to be complete and accurate. All antennas, mounts, coax and waveguides are assumed to be properly installed and supported as per manufacturer requirements.
3. All mounts, if applicable, are considered adequate to support the loading. No actual analysis of the mount(s) is performed. This analysis is limited to analyzing the tower only.
4. The soil parameters are as per data supplied or as assumed and stated in the calculations.
5. Foundations are properly designed and constructed to resist the original design loads indicated in the documents provided.
6. The tower and structures have been properly maintained in accordance with TIA Standards and/or with manufacturer's specifications.
7. All welds and connections are assumed to develop at least the member capacity unless determined otherwise and explicitly stated in this report.
8. All prior structural modifications, if applicable, are assumed to be as per data supplied/available and to have been properly installed.
9. Loading interpreted from photos is accurate to $\pm 5'$ AGL, antenna size accurate to ± 3.3 sf, and coax equal to the number of existing antennas without reserve.
10. All existing and proposed loading has been taken from the available site photos as well as documents supplied to GPD at the time of generating this report. All such documents are listed in the Documents Provided Table and are assumed to be accurate. GPD is not responsible for loading scenarios outside those conveyed in the supplied documentation.

If any of these assumptions are not valid or have been made in error, this analysis may be affected, and GPD should be allowed to review any new information to determine its effect on the structural integrity of the tower.

DISCLAIMER OF WARRANTIES

GPD has not performed a site visit to the tower to verify the member sizes or antenna/coax loading. If the existing conditions are not as represented on the tower elevation contained in this report, we should be contacted immediately to evaluate the significance of the discrepancy. This is not a condition assessment of the tower or foundation. This report does not replace a full tower inspection. The tower and foundations are assumed to have been properly fabricated, erected, maintained, in good condition, twist free, and plumb.

The engineering services rendered by GPD in connection with this Comprehensive Structural Analysis are limited to a computer analysis of the tower structure and theoretical capacity of its main structural members. No allowance was made for any damaged, bent, missing, loose, or rusted members (above and below ground). No allowance was made for loose bolts or cracked welds.

This analysis is limited to the designated maximum wind and seismic conditions per the governing tower standards and code. Wind forces resulting in tower vibrations near the structure's resonant frequencies were not considered in this analysis and are outside the scope of this analysis. Lateral loading from any dynamic response was not evaluated under a time-domain based fatigue analysis.

GPD does not analyze the fabrication of the structure (including welding). It is not possible to have all the very detailed information needed to perform a thorough analysis of every structural sub-component and connection of an existing tower. GPD provides a limited scope of service in that we cannot verify the adequacy of every weld, plate connection detail, etc. The purpose of this report is to assess the capability of adding appurtenances usually accompanied by transmission lines to the structure.

It is the owner's responsibility to determine the amount of ice accumulation in excess of the code specified amount, if any, that should be considered in the structural analysis.

The attached sketches are a schematic representation of the analyzed tower. If any material is fabricated from these sketches, the contractor shall be responsible for field verifying the existing conditions, proper fit, and clearance in the field. Any mentions of structural modifications are reasonable estimates and should not be used as a precise construction document. Precise modification drawings are obtainable from GPD, but are beyond the scope of this report.

Miscellaneous items such as antenna mounts, etc., have not been designed or detailed as a part of our work. We recommend that material of adequate size and strength be purchased from a reputable tower manufacturer.

Towers are designed to carry gravity, wind, and ice loads. All members, legs, diagonals, struts, and redundant members provide structural stability to the tower with little redundancy. Absence or removal of a member can trigger catastrophic failure unless a substitute is provided before any removal. Legs carry axial loads and derive their strength from shorter unbraced lengths by the presence of redundant members and their connection to the diagonals with bolts or welds. If the bolts or welds are removed without providing any substitute to the frame, the leg is subjected to a higher unbraced length that immediately reduces its load carrying capacity. If a diagonal is also removed in addition to the connection, the unbraced length of the leg is greatly increased, jeopardizing its load carrying capacity. Failure of one leg can result in a tower collapse because there is no redundancy. Redundant members and diagonals are critical to the stability of the tower.

GPD makes no warranties, expressed and/or implied, in connection with this report and disclaims any liability arising from material, fabrication, and erection of this tower. GPD will not be responsible whatsoever for, or on account of, consequential or incidental damages sustained by any person, firm, or organization as a result of any data or conclusions contained in this report. The maximum liability of GPD pursuant to this report will be limited to the total fee received for preparation of this report.

APPENDIX A

Tower Analysis Summary Form

Tower Analysis Summary Form

General Info

Site Name	NORWALK CT NEW CANAAN AVE
Site Number	105046
FA Number	10113256
Date of Analysis	1/3/2023
Company Performing Analysis	GPD

The information contained in this summary report is not to be used independently from the PE stamped tower analysis.

Tower Info	Description	Date
Tower Type (G, SST, MP)	MP	
Tower Height (top of steel AGL)	140'	
Tower Manufacturer	n/a	
Tower Model	Stealth	
Tower Design	Engineering Endeavors Project #: 17340	10/13/2014
Foundation Design	Engineering Endeavors Project #: 17340	10/13/2014
Geotechnical Report	National Guard armory-SR1038	4/7/2014
Previous Tower Analysis	n/a	
Tower Mapping	n/a	

Design Parameters	
Design Code Used	TIA-222-H, 2021 IBC, 2022 CSBC
Location of Tower (County, State)	Fairfield, CT
Wind Speed (mph)	117 (3-second gust)
Ice Thickness (in)	1
Risk Category (I, II, III)	II
Exposure Category (B, C, D)	B
Topographic Category (1 to 5)	1

Analysis Results (% Maximum Usage)	
Existing/Reserved + Future + Proposed Condition	
Tower (%)	28.5%
Tower Base (%)	39.1%
Foundation (%)	23.1%
Foundation Adequate?	Yes

Existing / Reserved Loading

Antenna								Mount			Transmission Line			
Antenna Owner	Mount Height (ft)	Antenna CL (ft)	Quantity	Type	Manufacturer	Model	Azimuth	Quantity	Manufacturer	Type	Quantity	Model	Size	Attachment Int/Ext
AT&T Mobility	134	134	3*	Panel	CCI	OPA-65R-LCUU-H8	30/150/270			Inside Canister	12	Unknown	7/8"	Internal
AT&T Mobility	134	134	12*	Diplexer	Kaelus	DBC2055F1V1-2				Inside Canister				
AT&T Mobility	134	134	6	TMA	CCI	TMABPD7823VG12A				Inside Canister				
AT&T Mobility	124	124	3*	Panel	CCI	OPA-65R-LCUU-H8	30/150/270			Inside Canister	12	Unknown	7/8"	Internal
AT&T Mobility	124	124	6*	Diplexer	Kaelus	DBC2055F1V1-2				Inside Canister				
AT&T Mobility	124	124	6	Diplexer	Kaelus	DBC2055F1V1-2				Inside Canister				
AT&T Mobility	124	124	6*	TMA	CCI	TMABPD7823VG12A				Inside Canister				

*Indicates equipment/feedline quantity to be removed.

Proposed Loading

Antenna								Mount			Transmission Line			
Antenna Owner	Mount Height (ft)	Antenna CL (ft)	Quantity	Type	Manufacturer	Model	Azimuth	Quantity	Manufacturer	Type	Quantity	Model	Size	Attachment Int/Ext
Dish Wireless	117	117	3	Panel	Commscope	FFVV-65B-R3	80/200/300			Inside Canister	12	Unknown	7/8"	Internal
Dish Wireless	117	117	3	TMA	Kaelus	SBT0003F1V2				Inside Canister	1	Hybrid	1.411"	Internal
Dish Wireless	117	177	3	Diplexer	Commscope	CDX623T-DS-T E15V95P63				Inside Canister				

Note: The proposed loading shall be in addition to the remaining existing equipment at the same elevation.

Note: The proposed coax shall be installed inside the monopole in order for this analysis to be valid.


Future Loading

Antenna								Mount			Transmission Line			
Antenna Owner	Mount Height (ft)	Antenna CL (ft)	Quantity	Type	Manufacturer	Model	Azimuth	Quantity	Manufacturer	Type	Quantity	Model	Size	Attachment Int/Ext
AT&T Mobility	134	134	3	Panel	Commscope	NNHHS4-65A-R5	30/150/270			on the existing mounts				
AT&T Mobility	124	124	3	Panel	CCI	TPA65R-BU8DA-K	30/150/270			on the existing mounts				
AT&T Mobility	124	124	6	TMA	Commscope	TMAT192123B68-31				on the existing mounts				


APPENDIX B

Tower Analysis Output File


Section	5	4	3	2	1
Length (ft)	52.83	41.84	20.00	20.00	10.00
Number of Sides	18	18	0	0	0
Thickness (in)	0.2500	0.1875	4.0000	3.0000	0.3150
Socket Length (ft)	40.2082	5.67			
Top Dia (in)	47.5000	35.5000	8.0000	6.0000	4.5000
Bot Dia (in)		41.3800	8.0000	6.0000	4.5000
Grade		A572-65	A572-50	A53-B-35	
Weight (K)	6.2	3.2	3.4	1.9	0.1



ALL REACTIONS ARE FACTORED



50 mph WIND - 1.0000 in ICE



REACTIONS - 117 mph WIND

DESIGNED APPURTENANCE LOADING

TYPE	ELEVATION	TYPE	ELEVATION
Canister Load1	140	(2) TMA192123B68-31	124
NNHHS4-65A-R5 w/ Mount Pipe	134	TPA-65R-BU8DA-K w/ Mount Pipe	124
NNHHS4-65A-R5 w/ Mount Pipe	134	TPA-65R-BU8DA-K w/ Mount Pipe	124
(2) TMABPD7823VG12A	134	FFVV-65B-R3-V1 w/ Mount Pipe	117
(2) TMABPD7823VG12A	134	SBT0003F1V2	117
(2) TMABPD7823VG12A	134	SBT0003F1V2	117
NNHHS4-65A-R5 w/ Mount Pipe	134	SBT0003F1V2	117
Canister Load2	130	CDX623T-DS-T E15V95P63	117
TPA-65R-BU8DA-K w/ Mount Pipe	124	CDX623T-DS-T E15V95P63	117
(2) DBC2055F1V1-2	124	CDX623T-DS-T E15V95P63	117
(2) DBC2055F1V1-2	124	FFVV-65B-R3-V1 w/ Mount Pipe	117
(2) DBC2055F1V1-2	124	FFVV-65B-R3-V1 w/ Mount Pipe	117
(2) TMA192123B68-31	124	Canister Load3	110
(2) TMA192123B68-31	124	Canister Load4	90

MATERIAL STRENGTH

GRADE	Fy	Fu	GRADE	Fy	Fu
A53-B-35	35 ksi	63 ksi	A572-65	65 ksi	80 ksi
A572-50	50 ksi	65 ksi			

TOWER DESIGN NOTES



1. Tower is located in Fairfield County, Connecticut.
2. Tower designed for Exposure B to the TIA-222-H Standard.
3. Tower designed for a 117 mph basic wind in accordance with the TIA-222-H Standard.
4. Tower is also designed for a 50 mph basic wind with 1.00 in ice. Ice is considered to increase in thickness with height.
5. Deflections are based upon a 60 mph wind.
6. Tower Risk Category II.
7. Topographic Category 1 with Crest Height of 0.00 ft
8. TOWER RATING: 28.5%

GPD
 520 South Main Street Suite 2531
 Akron, Ohio 44311
 Phone: (330) 572-2100
 FAX: (330) 572-2101

Job: **Dish Applicant Site #: NJJER02030A**
 Project: **2022723.01.105046.01**
 Client: AT&T
 Code: TIA-222-H
 Path:
 Drawn by: jdross
 Date: 08/04/22
 App'd:
 Scale: NTS
 Dwg No. E-1

Feed Line Plan

Round Flat App In Face App Out Face



GPD
520 South Main Street Suite 2531
Akron, Ohio 44311
Phone: (330) 572-2100
FAX: (330) 572-2101

Job: Dish Applicant Site #: NJJER02030A		
Project: 2022723.01.105046.01		
Client: AT&T	Drawn by: jdross	App'd:
Code: TIA-222-H	Date: 08/04/22	Scale: NTS
Path:		Dwg No. E-7

T:\AT&T\105046\01_2022723_01_105046_01_AT&T_Dish_S&S_Structure\00_Structure\00_Rev_003_Modeling\105046_FigP08.dwg

tnxTower GPD 520 South Main Street Suite 2531 Akron, Ohio 44311 Phone: (330) 572-2100 FAX: (330) 572-2101	Job Dish Applicant Site #: NJJER02030A	Page 1 of 9
	Project 2022723.01.105046.01	Date 08:33:59 08/04/22
	Client AT&T	Designed by jdross

Tower Input Data

The tower is a monopole.

This tower is designed using the TIA-222-H standard.

The following design criteria apply:

Tower is located in Fairfield County, Connecticut.

Tower base elevation above sea level: 197.00 ft.

Basic wind speed of 117 mph.

Risk Category II.

Exposure Category B.

Simplified Topographic Factor Procedure for wind speed-up calculations is used.

Topographic Category: 1.

Crest Height: 0.00 ft.

Nominal ice thickness of 1.0000 in.

Ice thickness is considered to increase with height.

Ice density of 56 pcf.

A wind speed of 50 mph is used in combination with ice.

Temperature drop of 50 °F.

Deflections calculated using a wind speed of 60 mph.

A non-linear (P-delta) analysis was used.

Pressures are calculated at each section.

Stress ratio used in pole design is 1.

Local bending stresses due to climbing loads, feed line supports, and appurtenance mounts are not considered.

Options

Consider Moments - Legs	Distribute Leg Loads As Uniform	Use ASCE 10 X-Brace Ly Rules
Consider Moments - Horizontals	Assume Legs Pinned	Calculate Redundant Bracing Forces
Consider Moments - Diagonals	√ Assume Rigid Index Plate	Ignore Redundant Members in FEA
Use Moment Magnification	√ Use Clear Spans For Wind Area	SR Leg Bolts Resist Compression
√ Use Code Stress Ratios	√ Use Clear Spans For KL/r	All Leg Panels Have Same Allowable
√ Use Code Safety Factors - Guys	Retension Guys To Initial Tension	Offset Girt At Foundation
Escalate Ice	√ Bypass Mast Stability Checks	√ Consider Feed Line Torque
Always Use Max Kz	√ Use Azimuth Dish Coefficients	Include Angle Block Shear Check
Use Special Wind Profile	√ Project Wind Area of Appurt.	Use TIA-222-H Bracing Resist. Exemption
Include Bolts In Member Capacity	Autocalc Torque Arm Areas	Use TIA-222-H Tension Splice Exemption
Leg Bolts Are At Top Of Section	Add IBC .6D+W Combination	Poles
Secondary Horizontal Braces Leg	Sort Capacity Reports By Component	√ Include Shear-Torsion Interaction
Use Diamond Inner Bracing (4 Sided)	Triangulate Diamond Inner Bracing	Always Use Sub-Critical Flow
SR Members Have Cut Ends	Treat Feed Line Bundles As Cylinder	Use Top Mounted Sockets
SR Members Are Concentric	Ignore KL/ry For 60 Deg. Angle Legs	√ Pole Without Linear Attachments
		Pole With Shroud Or No Appurtenances
		Outside and Inside Corner Radii Are
		Known

Tapered Pole Section Geometry

Section	Elevation	Section Length	Splice Length	Number of Sides	Top Diameter	Bottom Diameter	Wall Thickness	Bend Radius	Pole Grade
	ft	ft	ft		in	in	in	in	

tnxTower GPD 520 South Main Street Suite 2531 Akron, Ohio 44311 Phone: (330) 572-2100 FAX: (330) 572-2101	Job Dish Applicant Site #: NJJER02030A	Page 2 of 9
	Project 2022723.01.105046.01	Date 08:33:59 08/04/22
	Client AT&T	Designed by jdross

Section	Elevation ft	Section Length ft	Splice Length ft	Number of Sides	Top Diameter in	Bottom Diameter in	Wall Thickness in	Bend Radius in	Pole Grade
L1	140.00-130.00	10.00	0.00	Round	4.5000	4.5000	0.3150		A53-B-35 (35 ksi)
L2	130.00-110.00	20.00	0.00	Round	6.0000	6.0000	3.0000		A572-50 (50 ksi)
L3	110.00-90.00	20.00	0.00	Round	8.0000	8.0000	4.0000		A572-65 (65 ksi)
L4	90.00-48.16	41.84	5.67	18	35.5000	41.3800	0.1875	0.7500	A572-65 (65 ksi)
L5	48.16-1.00	52.83		18	40.2082	47.5000	0.2500	1.0000	A572-65 (65 ksi)

Tapered Pole Properties

Section	Tip Dia. in	Area in ²	I in ⁴	r in	C in	I/C in ³	J in ⁴	It/Q in ²	w in	w/t
L1	4.5000	4.1415	9.1182	1.4838	2.2500	4.0525	18.2365	2.0695	0.0000	0
	4.5000	4.1415	9.1182	1.4838	2.2500	4.0525	18.2365	2.0695	0.0000	0
L2	6.0000	28.2743	63.6173	1.5000	3.0000	21.2058	127.2345	14.1287	0.0000	0
	6.0000	28.2743	63.6173	1.5000	3.0000	21.2058	127.2345	14.1287	0.0000	0
L3	8.0000	50.2655	201.0619	2.0000	4.0000	50.2655	402.1239	25.1177	0.0000	0
	8.0000	50.2655	201.0619	2.0000	4.0000	50.2655	402.1239	25.1177	0.0000	0
L4	36.0187	21.0154	3310.7855	12.5359	18.0340	183.5858	6625.9274	10.5097	5.9180	31.563
	41.9894	24.5147	5255.3313	14.6233	21.0210	250.0034	10517.5776	12.2597	6.9529	37.082
L5	41.5845	31.7068	6395.8896	14.1851	20.4257	313.1288	12800.1950	15.8564	6.6366	26.547
	48.1942	37.4929	10575.2300	16.7738	24.1300	438.2607	21164.3751	18.7500	7.9200	31.68

Tower Elevation	Gusset Area (per face)	Gusset Thickness	Gusset Grade	Adjust. Factor A _f	Adjust. Factor A _r	Weight Mult.	Double Angle Stitch Bolt Spacing Diagonals	Double Angle Stitch Bolt Spacing Horizontals	Double Angle Stitch Bolt Spacing Redundants
ft	ft ²	in					in	in	in
L1 140.00-130.00				1	0	1			
L2 130.00-110.00				1	0	1			
L3 110.00-90.00				1	0	1			
L4 90.00-48.16				1	1	1			
L5 48.16-1.00				1	1	1			

Feed Line/Linear Appurtenances - Entered As Area

Description	Face or Leg	Allow Shield	Exclude From Torque Calculation	Component Type	Placement ft	Total Number		C _A A _A ft ² /ft	Weight plf
LDF5-50A(7/8")	C	No	No	Inside Pole	134.00 - 8.00	12	No Ice	0.00	0.33
							1/2" Ice	0.00	0.33
							1" Ice	0.00	0.33
LDF5-50A(7/8")	C	No	No	Inside Pole	117.00 - 8.00	12	No Ice	0.00	0.33
							1/2" Ice	0.00	0.33
							1" Ice	0.00	0.33

tnxTower GPD 520 South Main Street Suite 2531 Akron, Ohio 44311 Phone: (330) 572-2100 FAX: (330) 572-2101	Job	Dish Applicant Site #: NJJER02030A	Page	3 of 9
	Project	2022723.01.105046.01	Date	08:33:59 08/04/22
	Client	AT&T	Designed by	jdross

Description	Face or Leg	Allow Shield	Exclude From Torque Calculation	Component Type	Placement ft	Total Number	C _{AA}	Weight
							ft ² /ft	plf
1.411" Hybrid Cable	C	No	No	Inside Pole	117.00 - 8.00	1	No Ice 1/2" Ice 1" Ice	1.00 1.00 1.00
LDF5-50A(7/8")	C	No	No	Inside Pole	124.00 - 8.00	12	No Ice 1/2" Ice 1" Ice	0.33 0.33 0.33

Feed Line/Linear Appurtenances Section Areas

Tower Section	Tower Elevation ft	Face	A _R ft ²	A _F ft ²	C _{AA} In Face ft ²	C _{AA} Out Face ft ²	Weight K
L1	140.00-130.00	A	0.000	0.000	0.000	0.000	0.00
		B	0.000	0.000	0.000	0.000	0.00
		C	0.000	0.000	0.000	0.000	0.02
L2	130.00-110.00	A	0.000	0.000	0.000	0.000	0.00
		B	0.000	0.000	0.000	0.000	0.00
		C	0.000	0.000	0.000	0.000	0.17
L3	110.00-90.00	A	0.000	0.000	0.000	0.000	0.00
		B	0.000	0.000	0.000	0.000	0.00
		C	0.000	0.000	0.000	0.000	0.26
L4	90.00-48.16	A	0.000	0.000	0.000	0.000	0.00
		B	0.000	0.000	0.000	0.000	0.00
		C	0.000	0.000	0.000	0.000	0.54
L5	48.16-1.00	A	0.000	0.000	0.000	0.000	0.00
		B	0.000	0.000	0.000	0.000	0.00
		C	0.000	0.000	0.000	0.000	0.52

Feed Line/Linear Appurtenances Section Areas - With Ice

Tower Section	Tower Elevation ft	Face or Leg	Ice Thickness in	A _R ft ²	A _F ft ²	C _{AA} In Face ft ²	C _{AA} Out Face ft ²	Weight K
L1	140.00-130.00	A	1.151	0.000	0.000	0.000	0.000	0.00
		B		0.000	0.000	0.000	0.000	0.00
		C		0.000	0.000	0.000	0.000	0.02
L2	130.00-110.00	A	1.138	0.000	0.000	0.000	0.000	0.00
		B		0.000	0.000	0.000	0.000	0.00
		C		0.000	0.000	0.000	0.000	0.17
L3	110.00-90.00	A	1.117	0.000	0.000	0.000	0.000	0.00
		B		0.000	0.000	0.000	0.000	0.00
		C		0.000	0.000	0.000	0.000	0.26
L4	90.00-48.16	A	1.077	0.000	0.000	0.000	0.000	0.00
		B		0.000	0.000	0.000	0.000	0.00
		C		0.000	0.000	0.000	0.000	0.54
L5	48.16-1.00	A	0.970	0.000	0.000	0.000	0.000	0.00
		B		0.000	0.000	0.000	0.000	0.00
		C		0.000	0.000	0.000	0.000	0.52

tnxTower GPD 520 South Main Street Suite 2531 Akron, Ohio 44311 Phone: (330) 572-2100 FAX: (330) 572-2101	Job	Dish Applicant Site #: NJJER02030A	Page	4 of 9
	Project	2022723.01.105046.01	Date	08:33:59 08/04/22
	Client	AT&T	Designed by	jdross

Feed Line Center of Pressure

Section	Elevation	CP _x	CP _z	CP _x Ice	CP _z Ice
	ft	in	in	in	in
L1	140.00-130.00	0.0000	0.0000	0.0000	0.0000
L2	130.00-110.00	0.0000	0.0000	0.0000	0.0000
L3	110.00-90.00	0.0000	0.0000	0.0000	0.0000
L4	90.00-48.16	0.0000	0.0000	0.0000	0.0000
L5	48.16-1.00	0.0000	0.0000	0.0000	0.0000

Note: For pole sections, center of pressure calculations do not consider feed line shielding.

Discrete Tower Loads

Description	Face or Leg	Offset Type	Offsets: Horz Lateral Vert ft ft ft	Azimuth Adjustment °	Placement ft	C _{AA} Front ft ²	C _{AA} Side ft ²	Weight K
NNHHS4-65A-R5 w/ Mount Pipe	A	None		0.0000	134.00	No Ice	0.00	0.13
						1/2" Ice	0.00	0.21
						1" Ice	0.00	0.29
NNHHS4-65A-R5 w/ Mount Pipe	B	None		0.0000	134.00	No Ice	0.00	0.13
						1/2" Ice	0.00	0.21
						1" Ice	0.00	0.29
NNHHS4-65A-R5 w/ Mount Pipe	C	None		0.0000	134.00	No Ice	0.00	0.13
						1/2" Ice	0.00	0.21
						1" Ice	0.00	0.29
(2) TMABPD7823VG12A	A	None		0.0000	134.00	No Ice	0.00	0.03
						1/2" Ice	0.00	0.04
						1" Ice	0.00	0.05
(2) TMABPD7823VG12A	B	None		0.0000	134.00	No Ice	0.00	0.03
						1/2" Ice	0.00	0.04
						1" Ice	0.00	0.05
(2) TMABPD7823VG12A	C	None		0.0000	134.00	No Ice	0.00	0.03
						1/2" Ice	0.00	0.04
						1" Ice	0.00	0.05
TPA-65R-BU8DA-K w/ Mount Pipe	A	None		0.0000	124.00	No Ice	0.00	0.12
						1/2" Ice	0.00	0.23
						1" Ice	0.00	0.36
TPA-65R-BU8DA-K w/ Mount Pipe	B	None		0.0000	124.00	No Ice	0.00	0.12
						1/2" Ice	0.00	0.23
						1" Ice	0.00	0.36
TPA-65R-BU8DA-K w/ Mount Pipe	C	None		0.0000	124.00	No Ice	0.00	0.12
						1/2" Ice	0.00	0.23
						1" Ice	0.00	0.36
(2) DBC2055F1V1-2	A	None		0.0000	124.00	No Ice	0.00	0.01
						1/2" Ice	0.00	0.01
						1" Ice	0.00	0.02
(2) DBC2055F1V1-2	B	None		0.0000	124.00	No Ice	0.00	0.01
						1/2" Ice	0.00	0.01
						1" Ice	0.00	0.02
(2) DBC2055F1V1-2	C	None		0.0000	124.00	No Ice	0.00	0.01

tnxTower GPD 520 South Main Street Suite 2531 Akron, Ohio 44311 Phone: (330) 572-2100 FAX: (330) 572-2101	Job	Dish Applicant Site #: NJJER02030A	Page	5 of 9
	Project	2022723.01.105046.01	Date	08:33:59 08/04/22
	Client	AT&T	Designed by	jdross

Description	Face or Leg	Offset Type	Offsets:			Azimuth Adjustment	Placement	C _{AA} Front	C _{AA} Side	Weight
			Horz	Lateral	Vert					
							1/2" Ice	0.00	0.00	0.01
							1" Ice	0.00	0.00	0.02
(2) TMAT192123B68-31	A	None			0.0000	124.00	No Ice	0.00	0.00	0.02
							1/2" Ice	0.00	0.00	0.03
							1" Ice	0.00	0.00	0.04
(2) TMAT192123B68-31	B	None			0.0000	124.00	No Ice	0.00	0.00	0.02
							1/2" Ice	0.00	0.00	0.03
							1" Ice	0.00	0.00	0.04
(2) TMAT192123B68-31	C	None			0.0000	124.00	No Ice	0.00	0.00	0.02
							1/2" Ice	0.00	0.00	0.03
							1" Ice	0.00	0.00	0.04
FFVV-65B-R3-V1 w/ Mount Pipe	A	None			0.0000	117.00	No Ice	0.00	0.00	0.13
							1/2" Ice	0.00	0.00	0.24
							1" Ice	0.00	0.00	0.36
FFVV-65B-R3-V1 w/ Mount Pipe	B	None			0.0000	117.00	No Ice	0.00	0.00	0.13
							1/2" Ice	0.00	0.00	0.24
							1" Ice	0.00	0.00	0.36
FFVV-65B-R3-V1 w/ Mount Pipe	C	None			0.0000	117.00	No Ice	0.00	0.00	0.13
							1/2" Ice	0.00	0.00	0.24
							1" Ice	0.00	0.00	0.36
SBT0003F1V2	A	None			0.0000	117.00	No Ice	0.00	0.00	0.00
							1/2" Ice	0.00	0.00	0.00
							1" Ice	0.00	0.00	0.00
SBT0003F1V2	B	None			0.0000	117.00	No Ice	0.00	0.00	0.00
							1/2" Ice	0.00	0.00	0.00
							1" Ice	0.00	0.00	0.00
SBT0003F1V2	C	None			0.0000	117.00	No Ice	0.00	0.00	0.00
							1/2" Ice	0.00	0.00	0.00
							1" Ice	0.00	0.00	0.00
CDX623T-DS-T1 E15V95P63	A	None			0.0000	117.00	No Ice	0.00	0.00	0.01
							1/2" Ice	0.00	0.00	0.01
							1" Ice	0.00	0.00	0.02
CDX623T-DS-T1 E15V95P63	B	None			0.0000	117.00	No Ice	0.00	0.00	0.01
							1/2" Ice	0.00	0.00	0.01
							1" Ice	0.00	0.00	0.02
CDX623T-DS-T1 E15V95P63	C	None			0.0000	117.00	No Ice	0.00	0.00	0.01
							1/2" Ice	0.00	0.00	0.01
							1" Ice	0.00	0.00	0.02
Canister Load1	C	None			0.0000	140.00	No Ice	6.75	6.75	0.09
							1/2" Ice	16.96	16.96	0.21
							1" Ice	17.42	17.42	0.32
Canister Load2	C	None			0.0000	130.00	No Ice	20.25	20.25	0.76
							1/2" Ice	50.88	50.88	1.10
							1" Ice	52.25	52.25	1.44
Canister Load3	C	None			0.0000	110.00	No Ice	27.00	27.00	0.86
							1/2" Ice	67.83	67.83	1.30
							1" Ice	69.67	69.67	1.76
Canister Load4	C	None			0.0000	90.00	No Ice	13.50	13.50	0.67
							1/2" Ice	33.92	33.92	0.89
							1" Ice	34.83	34.83	1.12

<p>tnxTower</p> <p>GPD</p> <p>520 South Main Street Suite 2531 Akron, Ohio 44311 Phone: (330) 572-2100 FAX: (330) 572-2101</p>	Job	Dish Applicant Site #: NJJER02030A	Page	6 of 9
	Project	2022723.01.105046.01	Date	08:33:59 08/04/22
	Client	AT&T	Designed by	jdross

Load Combinations

Comb. No.	Description
1	Dead Only
2	1.2 Dead+1.0 Wind 0 deg - No Ice
3	0.9 Dead+1.0 Wind 0 deg - No Ice
4	1.2 Dead+1.0 Wind 30 deg - No Ice
5	0.9 Dead+1.0 Wind 30 deg - No Ice
6	1.2 Dead+1.0 Wind 60 deg - No Ice
7	0.9 Dead+1.0 Wind 60 deg - No Ice
8	1.2 Dead+1.0 Wind 90 deg - No Ice
9	0.9 Dead+1.0 Wind 90 deg - No Ice
10	1.2 Dead+1.0 Wind 120 deg - No Ice
11	0.9 Dead+1.0 Wind 120 deg - No Ice
12	1.2 Dead+1.0 Wind 150 deg - No Ice
13	0.9 Dead+1.0 Wind 150 deg - No Ice
14	1.2 Dead+1.0 Wind 180 deg - No Ice
15	0.9 Dead+1.0 Wind 180 deg - No Ice
16	1.2 Dead+1.0 Wind 210 deg - No Ice
17	0.9 Dead+1.0 Wind 210 deg - No Ice
18	1.2 Dead+1.0 Wind 240 deg - No Ice
19	0.9 Dead+1.0 Wind 240 deg - No Ice
20	1.2 Dead+1.0 Wind 270 deg - No Ice
21	0.9 Dead+1.0 Wind 270 deg - No Ice
22	1.2 Dead+1.0 Wind 300 deg - No Ice
23	0.9 Dead+1.0 Wind 300 deg - No Ice
24	1.2 Dead+1.0 Wind 330 deg - No Ice
25	0.9 Dead+1.0 Wind 330 deg - No Ice
26	1.2 Dead+1.0 Ice+1.0 Temp
27	1.2 Dead+1.0 Wind 0 deg+1.0 Ice+1.0 Temp
28	1.2 Dead+1.0 Wind 30 deg+1.0 Ice+1.0 Temp
29	1.2 Dead+1.0 Wind 60 deg+1.0 Ice+1.0 Temp
30	1.2 Dead+1.0 Wind 90 deg+1.0 Ice+1.0 Temp
31	1.2 Dead+1.0 Wind 120 deg+1.0 Ice+1.0 Temp
32	1.2 Dead+1.0 Wind 150 deg+1.0 Ice+1.0 Temp
33	1.2 Dead+1.0 Wind 180 deg+1.0 Ice+1.0 Temp
34	1.2 Dead+1.0 Wind 210 deg+1.0 Ice+1.0 Temp
35	1.2 Dead+1.0 Wind 240 deg+1.0 Ice+1.0 Temp
36	1.2 Dead+1.0 Wind 270 deg+1.0 Ice+1.0 Temp
37	1.2 Dead+1.0 Wind 300 deg+1.0 Ice+1.0 Temp
38	1.2 Dead+1.0 Wind 330 deg+1.0 Ice+1.0 Temp
39	Dead+Wind 0 deg - Service
40	Dead+Wind 30 deg - Service
41	Dead+Wind 60 deg - Service
42	Dead+Wind 90 deg - Service
43	Dead+Wind 120 deg - Service
44	Dead+Wind 150 deg - Service
45	Dead+Wind 180 deg - Service
46	Dead+Wind 210 deg - Service
47	Dead+Wind 240 deg - Service
48	Dead+Wind 270 deg - Service
49	Dead+Wind 300 deg - Service
50	Dead+Wind 330 deg - Service

Maximum Tower Deflections - Service Wind

Section No.	Elevation ft	Horz. Deflection in	Gov. Load Comb.	Tilt °	Twist °

tnxTower GPD 520 South Main Street Suite 2531 Akron, Ohio 44311 Phone: (330) 572-2100 FAX: (330) 572-2101	Job	Dish Applicant Site #: NJJER02030A	Page	7 of 9
	Project	2022723.01.105046.01	Date	08:33:59 08/04/22
	Client	AT&T	Designed by	jdross

Section No.	Elevation ft	Horz. Deflection in	Gov. Load Comb.	Tilt °	Twist °
L1	140 - 130	9.320	42	0.9812	0.0000
L2	130 - 110	7.336	42	0.8772	0.0000
L3	110 - 90	4.142	39	0.5620	0.0000
L4	90 - 48.16	2.382	39	0.2279	0.0000
L5	53.83 - 1	0.920	39	0.1495	0.0000

Critical Deflections and Radius of Curvature - Service Wind

Elevation ft	Appurtenance	Gov. Load Comb.	Deflection in	Tilt °	Twist °	Radius of Curvature ft
140.00	Canister Load1	42	9.320	0.9812	0.0000	9979
134.00	NNHHS4-65A-R5 w/ Mount Pipe	42	8.114	0.9219	0.0000	8321
130.00	Canister Load2	42	7.336	0.8772	0.0000	5248
124.00	TPA-65R-BU8DA-K w/ Mount Pipe	39	6.241	0.7971	0.0000	4007
117.00	FFVV-65B-R3-V1 w/ Mount Pipe	39	5.101	0.6863	0.0000	3258
110.00	Canister Load3	39	4.142	0.5620	0.0000	2874
90.00	Canister Load4	39	2.382	0.2279	0.0000	7028

Maximum Tower Deflections - Design Wind

Section No.	Elevation ft	Horz. Deflection in	Gov. Load Comb.	Tilt °	Twist °
L1	140 - 130	40.325	8	4.2591	0.0000
L2	130 - 110	31.719	8	3.8118	0.0000
L3	110 - 90	17.847	8	2.4378	0.0000
L4	90 - 48.16	10.230	8	0.9808	0.0000
L5	53.83 - 1	3.948	8	0.6415	0.0000

Critical Deflections and Radius of Curvature - Design Wind

Elevation ft	Appurtenance	Gov. Load Comb.	Deflection in	Tilt °	Twist °	Radius of Curvature ft
140.00	Canister Load1	8	40.325	4.2591	0.0000	2339
134.00	NNHHS4-65A-R5 w/ Mount Pipe	8	35.095	4.0045	0.0000	1950
130.00	Canister Load2	8	31.719	3.8118	0.0000	1228
124.00	TPA-65R-BU8DA-K w/ Mount Pipe	8	26.963	3.4641	0.0000	931
117.00	FFVV-65B-R3-V1 w/ Mount Pipe	8	22.012	2.9809	0.0000	752
110.00	Canister Load3	8	17.847	2.4378	0.0000	660
90.00	Canister Load4	8	10.230	0.9808	0.0000	1615

Compression Checks

tnxTower GPD 520 South Main Street Suite 2531 Akron, Ohio 44311 Phone: (330) 572-2100 FAX: (330) 572-2101	Job Dish Applicant Site #: NJJER02030A	Page 8 of 9
	Project 2022723.01.105046.01	Date 08:33:59 08/04/22
	Client AT&T	Designed by jdross

Pole Design Data

Section No.	Elevation ft	Size	L ft	L _u ft	Kl/r	A in ²	P _u K	φP _n K	Ratio $\frac{P_u}{\phi P_n}$
L1	140 - 130 (1)	TP4.5x4.5x0.315	10.00	0.00	0.0	4.1415	-0.97	130.46	0.007
L2	130 - 110 (2)	TP6x6x3	20.00	0.00	0.0	28.2743	-5.50	1272.35	0.004
L3	110 - 90 (3)	TP8x8x4	20.00	0.00	0.0	50.2655	-10.95	2940.53	0.004
L4	90 - 48.16 (4)	TP41.38x35.5x0.1875	41.84	0.00	0.0	24.0405	-15.62	1246.92	0.013
L5	48.16 - 1 (5)	TP47.5x40.2082x0.25	52.83	0.00	0.0	37.4929	-24.41	2129.38	0.011

Pole Bending Design Data

Section No.	Elevation ft	Size	M _{ux} kip-ft	φM _{ux} kip-ft	Ratio $\frac{M_{ux}}{\phi M_{ux}}$	M _{uy} kip-ft	φM _{uy} kip-ft	Ratio $\frac{M_{uy}}{\phi M_{uy}}$
L1	140 - 130 (1)	TP4.5x4.5x0.315	3.00	14.51	0.207	0.00	14.51	0.000
L2	130 - 110 (2)	TP6x6x3	28.18	135.00	0.209	0.00	135.00	0.000
L3	110 - 90 (3)	TP8x8x4	74.49	416.00	0.179	0.00	416.00	0.000
L4	90 - 48.16 (4)	TP41.38x35.5x0.1875	215.56	1039.10	0.207	0.00	1039.10	0.000
L5	48.16 - 1 (5)	TP47.5x40.2082x0.25	567.15	2074.22	0.273	0.00	2074.22	0.000

Pole Shear Design Data

Section No.	Elevation ft	Size	Actual V _u K	φV _n K	Ratio $\frac{V_u}{\phi V_n}$	Actual T _u kip-ft	φT _n kip-ft	Ratio $\frac{T_u}{\phi T_n}$
L1	140 - 130 (1)	TP4.5x4.5x0.315	0.33	39.14	0.009	0.00	14.40	0.000
L2	130 - 110 (2)	TP6x6x3	1.29	381.70	0.003	0.00	100.68	0.000
L3	110 - 90 (3)	TP8x8x4	2.25	882.16	0.003	0.00	310.23	0.000
L4	90 - 48.16 (4)	TP41.38x35.5x0.1875	5.08	421.91	0.012	0.00	1492.57	0.000
L5	48.16 - 1 (5)	TP47.5x40.2082x0.25	8.19	658.00	0.012	0.00	2722.75	0.000

Pole Interaction Design Data

Section No.	Elevation ft	Ratio $\frac{P_u}{\phi P_n}$	Ratio $\frac{M_{ux}}{\phi M_{ux}}$	Ratio $\frac{M_{uy}}{\phi M_{uy}}$	Ratio $\frac{V_u}{\phi V_n}$	Ratio $\frac{T_u}{\phi T_n}$	Comb. Stress Ratio	Allow. Stress Ratio	Criteria
L1	140 - 130 (1)	0.007	0.207	0.000	0.009	0.000	0.214	1.000	4.8.2 ✓
L2	130 - 110 (2)	0.004	0.209	0.000	0.003	0.000	0.213	1.000	4.8.2 ✓
L3	110 - 90 (3)	0.004	0.179	0.000	0.003	0.000	0.183	1.000	4.8.2 ✓
L4	90 - 48.16 (4)	0.013	0.207	0.000	0.012	0.000	0.220	1.000	4.8.2 ✓

tnxTower GPD 520 South Main Street Suite 2531 Akron, Ohio 44311 Phone: (330) 572-2100 FAX: (330) 572-2101	Job	Dish Applicant Site #: NJJER02030A	Page	9 of 9
	Project	2022723.01.105046.01	Date	08:33:59 08/04/22
	Client	AT&T	Designed by	jdross

Section No.	Elevation ft	Ratio P_u ϕP_n	Ratio M_{ux} ϕM_{nx}	Ratio M_{uy} ϕM_{ny}	Ratio V_u ϕV_n	Ratio T_u ϕT_n	Comb. Stress Ratio	Allow. Stress Ratio	Criteria
L5	48.16 - 1 (5)	0.011	0.273	0.000	0.012	0.000	0.285 ✓ ✓	1.000	4.8.2 ✓

Section Capacity Table


Section No.	Elevation ft	Component Type	Size	Critical Element	P K	ϕP_{allow} K	% Capacity	Pass Fail
L1	140 - 130	Pole	TP4.5x4.5x0.315	1	-0.97	130.46	21.4	Pass
L2	130 - 110	Pole	TP6x6x3	2	-5.50	1272.35	21.3	Pass
L3	110 - 90	Pole	TP8x8x4	3	-10.95	2940.53	18.3	Pass
L4	90 - 48.16	Pole	TP41.38x35.5x0.1875	4	-15.62	1246.92	22.0	Pass
L5	48.16 - 1	Pole	TP47.5x40.2082x0.25	5	-24.41	2129.38	28.5	Pass
Summary							ELC:	E+P
Pole (L5)							28.5	Pass
Rating =							28.5	Pass

APPENDIX C

Additional Calculations

Code	
Code:	TIA-222-H
Ice Thickness:	1 in
Windspeed (V):	117 mph
Ice Wind Speed (V):	50 mph
Exposure Category:	B
Topographic Feature:	N/A
Risk Category:	II

Tower Information	
Total Tower Height:	139 ft
Base Tower Height:	89 ft
Total Canister Length:	50 ft
Number of Canister Assembly Sections:	3



Canister Section Number ¹ :	Canister Assembly Length (ft):	Canister Assembly Diameter (in):	Ventilated Canister:	Manufacturer ² :	Number of Sides Canister Section	Plate Type:	Mating Flange Plate Thickness (in) ³ :	Mating Flange Plate Diameter (in):	Solidity Ratio	Plate Weight (Kip):	Canister Weight (Kip)	Vent Length (ft):
1	10	36	No		Round	1	1.75	37	0.45	0.480	0.188	0-0
2	20	36	No		Round	1	1.75	37	0.45	0.480	0.377	0-0
3	20	36	No		Round	1	1.75	37	0.45	0.480	0.377	0-0

¹ Sections are numbered from the top of the tower down

² Select manufacturer if available for vented canister. Leave blank to autocalculate Cf values.

³ Mating Flange Plate Thickness at the bottom of canister section

Flag on Tower:	No
----------------	----

Truck Ball on Tower:	No
----------------------	----

Geometry : Base Tower + Spine				105046.eri (last saved 08/02 10:17 am)					
Pole Height Above Base (ft)	Section Length (ft)	Lap Splice Length (ft)	Number of Sides	Top Diameter (in)	Bottom Diameter (in)	Wall Thickness (in)	Bend Radius (in)	Pole Material	Delete
139	10	0	Round	4.5	4.5	0.315	1.26	A53-B-35	[x]
129	20	0	Round	6	6	3	12	A572-50	[x]
109	20	0	Round	8	8	4	16	A572-65	[x]
89	41.84	5.67	18	35.5	41.38	0.1875	0.75	A572-65	[x]
52.83	52.83	0	18	40.208164	47.5	0.25	1	A572-65	[x]

Discrete Loads : $C_r A_F$ for Canister Assembly								
Canister Loading	Apply $C_r A_F$ at Elevation(z) (ft)	$C_r A_F$ No Ice (ft ²)	$C_r A_F$ 1/2" Ice (ft ²)	$C_r A_F$ 1" Ice (ft ²)	$C_r A_F$ 2" Ice (ft ²)	$C_r A_F$ 4" Ice (ft ²)	Canister Assembly Weight No Ice (Kip)	Canister Assembly Weight 1/2" Ice (Kip)
Canister Load 1	139	6.750	16.958	17.417	18.333	20.167	0.094	0.206
Canister Load 2	129	20.250	50.875	52.250	55.000	60.500	0.763	1.097
Canister Load 3	109	27.000	67.833	69.667	73.333	80.667	0.857	1.303
Canister Load 4	89	13.500	33.917	34.833	36.667	40.333	0.669	0.892

Deflection Check Required:	Yes	Import Deflection Results
3% Spine Deflection Check		
Allowable (3%) Horizontal Spine Deflection (inches)	Actual Deflection ¹ (inches)	Sufficient/ Insufficient
18.000		

¹ Relative deflection under service level wind speed



Anchor Rod and Base Plate Stresses, TIA-222-H-1
NJJER02030A
 2022723.01.105046.01

Overturning Moment =	567.00	k*ft
Axial Force =	24.00	k
Shear Force =	8.00	k

Maximum Capacity	105%
Apply TIA-222-H Section 15.5?	No

Anchor Rods		
Number of Rods =	8	
Rod Yield Strength, F_y =	75	ksi
Rod Ultimate Strength, F_u =	100	ksi
Rod Circle =	54.75	in
Rod Diameter =	2.25	in
Rod Projection, l_{ar} =	2.25	in
Is grout present?	No	
Max Tension on Rod, P_{ut} =	59.08	k
Max Compression on Rod, P_{uc} =	65.08	k
Shear on Rod, V_u =	1.00	k
Moment on Rod, M_u =	0.00	k-in
Tension Interaction =	5.9%	OK
Compression Interaction =	24.3%	OK

Base Plate		
Location =	External	
Plate Strength, F_y =	50	ksi
ϕ =	0.9	
Outside Diameter =	60.75	in
Plate Thickness =	1.75	in
wcalc =	27.23	in
wmax =	17.50	in
w =	17.50	in
Z =	13.40	in ³
M_u =	235.93	k-in
ϕM_n =	602.93	k-in
BP Capacity =	39.1%	OK

Stiffeners		
Configuration =	None	

Pole		
Pole Diameter =	47.5	in
Number of Sides =	18	
Thickness =	0.25	in
Pole Yield Strength =	65	ksi

Drilled Pier Foundation

TIA-222 Revision:	H
Tower Type:	Monopole

Report File:

Applied Loads		
	Comp.	Uplift
Moment (kip-ft)	567	
Axial Force (kips)	24	
Shear Force (kips)	8	

Material Properties	
Concrete Strength, f _c :	4 ksi
Rebar Strength, F _y :	60 ksi
Tie Yield Strength, F _{yt} :	60 ksi

Pier Design Data	
Depth	20 ft
Ext. Above Grade	1 ft
Pier Section 1	
<i>From 1' above grade to 20' below grade</i>	
Pier Diameter	6.5 ft
Rebar Quantity	20
Rebar Size	11
Clear Cover to Ties	3 in
Tie Size	5
Tie Spacing	12 in

[Rebar & Pier Options](#)

[Embedded Pole Inputs](#)

[Belled Pier Inputs](#)

Analysis Results

Soil Lateral Check	Compression	Uplift
D _{ve0} (ft from TOC)	5.01	-
Soil Safety Factor	7.34	-
Max Moment (kip-ft)	600.22	-
Rating	18.1%	-

Soil Vertical Check	Compression	Uplift
Skin Friction (kips)	160.65	-
End Bearing (kips)	336.64	-
Weight of Concrete (kips)	90.63	-
Total Capacity (kips)	497.29	-
Axial (kips)	114.63	-
Rating	23.1%	-

Reinforced Concrete Flexure	Compression	Uplift
Critical Depth (ft from TOC)	4.88	-
Critical Moment (kip-ft)	600.18	-
Critical Moment Capacity	4660.28	-
Rating	12.9%	-

Reinforced Concrete Shear	Compression	Uplift
Critical Depth (ft from TOC)	13.82	-
Critical Shear (kip)	74.07	-
Critical Shear Capacity	649.83	-
Rating	11.4%	-

Structural Foundation Rating	12.9%
Soil Interaction Rating	23.1%

Check Limitation	
Apply TIA-222-H Section 15.5:	<input type="checkbox"/>
N/A	<input type="checkbox"/>
Additional Longitudinal Rebar	
Input Effective Depths (else Actual):	<input type="checkbox"/>
Shear Design Options	
Check Shear along Depth of Pier:	<input checked="" type="checkbox"/>
Utilize Shear-Friction Methodology:	<input type="checkbox"/>
Override Critical Depth:	<input type="checkbox"/>

[Go to Soil Calculations](#)

Soil Profile													
Groundwater Depth	6			# of Layers	4								

Layer	Top (ft)	Bottom (ft)	Thickness (ft)	γ _{soil} (pcf)	γ _{concrete} (pcf)	Cohesion (ksf)	Angle of Friction (degrees)	Calculated Ultimate Skin Friction Comp (ksf)	Calculated Ultimate Skin Friction Uplift (ksf)	Ultimate Skin Friction Comp Override (ksf)	Ultimate Skin Friction Uplift Override (ksf)	Ult. Net Bearing Capacity (ksf)	SPT Blow Count	Soil Type
1	0	2	2	125	150			0.000	0.000					Cohesionless
2	2	6	4	125	150		37	0.615	0.615				26	Cohesionless
3	6	10	4	62.6	87.6		37	0.979	0.979				22	Cohesionless
4	10	20	10	52.6	87.6		30	0.412	0.412			12	5	Cohesionless