



Crown Castle
3 Corporate Park Drive, Suite 101
Clifton Park, NY 12065

October 25, 2018

Melanie A. Bachman
Acting Executive Director
Connecticut Siting Council
10 Franklin Square
New Britain, CT 06051

RE: Notice of Exempt Modification for Sprint DO Macro: 806382
Sprint Site ID: CT03XC166
74 Goodrich Ln. Portland, CT 06480
Latitude: 41° 36' 29.90"/ Longitude: -72° 35' 29.56"

Dear Ms. Bachman:

Sprint currently maintains six (6) antennas at the 152-foot level of the existing 160-foot monopole tower at 74 Goodrich Ln. Portland, CT 06480. The tower is owned by Crown Castle. The property is owned by Joan J Hale. Sprint now intends to replace three (3) antennas with three (3) new antennas. These antennas would be installed at the 152-foot level of the tower. Sprint also intends to install three (3) RRHs, one (1) junction box, mount modifications, and replace two (2) coax cables with one (1) hybrid cable.

Please note that although mount modifications are listed in the project description on the construction drawings that within the Structural analysis it is the required materials for those modifications that are listed.

This facility was approved by the Connecticut Siting Council on July 11th 1986. This approval was given without conditions.

Please accept this letter as notification pursuant to Regulations of Connecticut State Agencies § 16-50j-73, for construction that constitutes an exempt modification pursuant to R.C.S.A. § 16-50j-72(b)(2). In accordance with R.S.C.A. § 16-50j-73, a copy of this letter is being sent to First Selectwoman Susan Bransfield, Town of Portland, Building official Lincoln White, Town of Portland, as well as the property owner, and Crown Castle is the tower owner.

1. The proposed modifications will not result in an increase in the height of the existing tower.
2. The proposed modifications will not require the extension of the site boundary.
3. The proposed modification will not increase noise levels at the facility by six decibels or more, or to levels that exceed state and local criteria.
4. The operation of the replacement antennas will not increase radio frequency emissions at the facility to a level at or above the Federal Communication Commission safety standard.

The Foundation for a Wireless World.

CrownCastle.com

Melanie A. Bachman

September 11, 2018

Page 2

5. The proposed modifications will not cause a change or alteration in the physical or environmental characteristics of the site.
6. The existing structure and its foundation can support the proposed loading.

For the foregoing reasons, Sprint respectfully submits that the proposed modifications to the above-reference telecommunications facility constitutes an exempt modification under R.C.S.A. § 16-50j-72(b)(2). Please send approval/rejection letter to Attn: Jeffrey Barbadora.

Sincerely,

Jeffrey Barbadora
Real Estate Specialist
12 Gill Street, Suite 5800, Woburn, MA 01801
781-729-0053
Jeff.Barbadora@crowncastle.com

Attachments:

Tab 1: Exhibit-1: Compound plan and elevation depicting the planned changes

Tab 2: Exhibit-2: Structural Modification Report

Tab 3: Exhibit-3: General Power Density Table Report (RF Emissions Analysis Report)


cc: The Honorable Susan Bransfield
33 East Main St.
Portland, CT 06480

Building Official Lincoln White
33 East Main St.
Portland, CT 06480

Joan J Hale
3060 N Atlantic Ave. APT 301
Cocoa Beach, FL32931



Sign in



Satellite

Google



Portland, CT : Assessor Database

Property Search:

Parcel ID:	Alternate ID:	Owner 1 Name:	Street Number:	Street Name:
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text" value="74"/>	<input style="border-bottom: none; border-right: none; border-top: none; border-left: none; padding: 2px 5px;" type="text" value="GOODRICH LANE"/> ▼
<input type="button" value="Search"/>		<input type="button" value="Reset"/>		

Property Detail:

Parcel ID:	Alternate ID/Map Block Lot:	Card:	Card:	Street Name:	Street Number:	Zoning:	LUC:	Acres:
084-0009	00354100			GOODRICH LANE	74	R25	Communication Towers	0.08

Owner Information:

Owner 1 Name:	HALE JOAN J
Owner 2 Name:	CROWN ATLANTIC LLC
Street 1:	PMB 353
Street 2:	4017 WASHINGTON RD
City:	MCMURRAY
State:	PA
Zip:	15317
Volume:	284
Page:	47

Property Images:

Picture:	There is no picture available.
Sketch:	There is no sketch available.

Valuation:

Appraised Land:	\$74,900.00
Appraised Bldg:	\$139,200.00
Appraised Total:	\$214,100.00
Total Assessment:	\$149,870.00

Out-Buildings:

Code:	Description:	Units:	Year Built:	Size1:	Size2:	Area:	Grade:	Condition:
FN1	FENCE CHAIN	3	1996	8	260	0	2	
TT4	TOWER CELLULAR	4	1978	1	160	0	1	
SH1	FRAME MACHINERY SHED	4	1978	1	200	0	2	
SH1	FRAME MACHINERY SHED	4	2000	1	96	0	9	
PC3	PAVING CONCRETE MAT/SLAB	3	1996	1	2640	0	2	

The information delivered through this on-line database is provided in the spirit of open access to government information and is intended as an enhanced service and convenience for citizens of Portland, CT. The providers of this database: Tyler CLT, Big Room Studios, and Portland, CT assume no liability for any error or omission in the information provided here.

Comments regarding this service should be directed to: assessor@portlandct.org

Thu. October 25, 2018 : 09:50 AM : 0.07s : 10mb





SPRINT SITE NUMBER:
SPRINT SITE NAME:
SITE TYPE:
TOWER HEIGHT:

CT03XC166
CT03XC166
MONOPOLE
160'-0"

CROWN CASTLE BU #: 806382
SITE ADDRESS:
COUNTY:
JURISDICTION:

74 GOODRICH LANE
PORTLAND, CT 06480
MIDDLESEX
TOWN OF PORTLAND

SPRINT DO MACRO UPGRADE



SPRINT SITE NUMBER:
CT03XC166

BU #: 806382
HRT 082 943274

74 GOODRICH LANE
PORTLAND, CT 06480

EXISTING 160'-0" MONOPOLE

SITE INFORMATION

CROWN CASTLE SITE NAME: HRT 082 943274
SITE ADDRESS: 74 GOODRICH LANE, PORTLAND, CT 06480
COUNTY: MIDDLESEX
MAP/PARCEL #: PORT-000084-000000-000009
AREA OF CONSTRUCTION: EXISTING
LATITUDE: 41° 36' 29.90"
LONGITUDE: -72° 35' 29.56"
LAT/LONG TYPE: NAD83
GROUND ELEVATION: 315 FT.
CURRENT ZONING: R-25
JURISDICTION: TOWN OF PORTLAND
OCCUPANCY CLASSIFICATION: U
TYPE OF CONSTRUCTION: VB
A.D.A. COMPLIANCE: FACILITY IS UNMANNED AND NOT FOR HUMAN HABITATION
PROPERTY OWNER: RIVERA, WAYNE, 58 GOODRICH LN, PORTLAND, CT 06480
TOWER OWNER: CROWN ATLANTIC COMPANY LLC, 2000 CORPORATE DRIVE, CANONSBURG, PA 15317
CARRIER/APPLICANT: SPRINT, 6391 SPRINT PARKWAY, OVERLAND PARK, KS 66251-2650
CROWN CASTLE APPLICATION ID: 396861
ELECTRIC PROVIDER: CONNECTICUT LIGHT & POWER CO, (800) 286-2000
TELCO PROVIDER: FRONTIER, (877) 650-6012

DRAWING INDEX

SHEET #	SHEET DESCRIPTION
T-1	TITLE SHEET
T-2	GENERAL NOTES
C-1	OVERALL AND ENLARGED SITE PLAN
C-2	FINAL ELEVATION AND ANTENNA PLANS
C-3	ANTENNA AND CABLE SCHEDULE
C-4	EQUIPMENT SPECIFICATIONS
C-5	PLUMBING DIAGRAM
G-1	GROUNDING DETAILS
G-2	GROUNDING DETAILS

ALL DRAWINGS CONTAINED HEREIN ARE FORMATTED FOR 11X17. CONTRACTOR SHALL VERIFY ALL PLANS AND EXISTING DIMENSIONS AND CONDITIONS ON THE JOB SITE AND SHALL IMMEDIATELY NOTIFY THE ENGINEER IN WRITING OF ANY DISCREPANCIES BEFORE PROCEEDING WITH THE WORK OR BE RESPONSIBLE FOR SAME.

PROJECT DESCRIPTION

THE PURPOSE OF THIS PROJECT IS TO ENHANCE BROADBAND CONNECTIVITY AND CAPACITY TO THE EXISTING ELIGIBLE WIRELESS FACILITY.


- TOWER SCOPE OF WORK**
- REMOVE (3) ANTENNAS
 - REMOVE (2) 1" COAX CABLES
 - REMOVE (3) RRHs
 - REMOVE (1) JUNCTION BOX
 - INSTALL (3) ANTENNAS
 - INSTALL (6) RRHs
 - INSTALL (1) 1-1/4" HYBRID CABLE
 - INSTALL MOUNT MODIFICATIONS PER CONDITIONAL PASSING MOUNT ANALYSIS DESIGN BY HUDSON DESIGN GROUP LLC DATED JUNE 20, 2018

- GROUND SCOPE OF WORK**
- NONE

INSTALLER NOTE:
 NO ADDITIONAL LOADING TO BE ADDED UNTIL MOUNT MODIFICATIONS ARE INSTALLED PER MOUNT MODIFICATION DESIGNED BY HUDSON DESIGN GROUP LLC DATED JUNE 20, 2018.

DESIGN PACKAGE BASED ON THE APPLICATION
 ID: 396861
 REVISION: 4

LOCATION MAP



NO SCALE

APPLICABLE CODES/REFERENCE DOCUMENTS

ALL WORK SHALL BE PERFORMED AND MATERIALS INSTALLED IN ACCORDANCE WITH THE CURRENT EDITIONS OF THE FOLLOWING CODES AS ADOPTED BY THE LOCAL GOVERNING AUTHORITIES. NOTHING IN THESE PLANS IS TO BE CONSTRUED TO PERMIT WORK NOT CONFORMING TO THESE CODES:

CODE TYPE	CODE
BUILDING	2016 CT STATE BUILDING CODE/2012 IBC W/ CT AMENDMENTS
MECHANICAL	2016 CT STATE BUILDING CODE/2012 IMC W/ CT AMENDMENTS
ELECTRICAL	2016 CT STATE BUILDING CODE/2014 NEC W/ CT AMENDMENTS

REFERENCE DOCUMENTS:


STRUCTURAL ANALYSIS:	B+T GROUP DATED JULY 3, 2018
MOUNT ANALYSIS: (CONDITIONAL PASS)	HUDSON DESIGN GROUP LLC DATED JUNE 20, 2018

PROJECT TEAM

CROWN CASTLE A&E FIRM: CROWN CASTLE, 2000 CORPORATE DRIVE, CANONSBURG, PA 15317, CROWN.AE.APPROVAL@CROWNCastle.COM
CROWN CASTLE CONTACTS: 3 CORPORATE PARK DRIVE, SUITE 101, CLIFTON PARK, NY 12065
 TRICIA PELON - PROJECT MANAGER (518) 373-3507
 JASON D'AMICO - CONSTRUCTION MANAGER (860) 209-0104
 DASHANNA HANLON - A&E PROJECT MANAGER, DASHANNA.HANLON@CROWNCastle.COM (781) 970-0067

ISSUED FOR:


REV	DATE	DRWN	DESCRIPTION	DES/QA
A	01/03/18	TDG	PRELIMINARY	LMR
0	07/18/18	JHW	CONSTRUCTION	AJF
1	10/03/18	LMR	CONSTRUCTION	JPL



Crown Castle USA Inc. Certificate of Registration #PEC.0001101

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SHEET NUMBER: T-1
REVISION: 1



CROWN CASTLE SITE WORK GENERAL NOTES:

1. THE SUBCONTRACTOR SHALL CONTACT UTILITY LOCATING SERVICES PRIOR TO THE START OF CONSTRUCTION.
2. ALL EXISTING ACTIVE SEWER, WATER, GAS, ELECTRIC AND OTHER UTILITIES WHERE ENCOUNTERED IN THE WORK, SHALL BE PROTECTED AT ALL TIMES AND WHERE REQUIRED FOR THE PROPER EXECUTION OF THE WORK, SHALL BE RELOCATED AS DIRECTED BY CONTRACTOR. EXTREME CAUTION SHOULD BE USED BY THE SUBCONTRACTOR WHEN EXCAVATING OR DRILLING PIERS AROUND OR NEAR UTILITIES, SUBCONTRACTOR SHALL PROVIDE SAFETY TRAINING FOR THE WORKING CREW. THIS WILL INCLUDE BUT NOT BE LIMITED TO A) FALL PROTECTION B) CONFINED SPACE C) ELECTRICAL SAFETY D) TRENCHING AND EXCAVATION.
3. ALL SITE WORK TO COMPLY WITH QAS-STD-10068 "INSTALLATION STANDARDS FOR CONSTRUCTION ACTIVITIES ON CROWN CASTLE TOWER SITE" AND LATEST VERSION OF TIA 1019 "STANDARD FOR INSTALLATION, ALTERATION, AND MAINTENANCE OF ANTENNA SUPPORTING STRUCTURES AND ANTENNAS."
4. ALL SITE WORK SHALL BE AS INDICATED ON THE STAMPED CONSTRUCTION DRAWINGS AND PROJECT SPECIFICATIONS.
5. IF NECESSARY, RUBBISH, STUMPS, DEBRIS, STICKS, STONES AND OTHER REFUSE SHALL BE REMOVED FROM THE SITE AND DISPOSED OF LEGALLY.
6. ALL EXISTING INACTIVE SEWER, WATER, GAS, ELECTRIC AND OTHER UTILITIES, WHICH INTERFERE WITH THE EXECUTION OF THE WORK, SHALL BE REMOVED AND/OR CAPPED, PLUGGED OR OTHERWISE DISCONTINUED AT POINTS WHICH WILL NOT INTERFERE WITH THE EXECUTION OF THE WORK, SUBJECT TO THE APPROVAL OF CONTRACTOR, OWNER AND/OR LOCAL UTILITIES.
7. THE SUBCONTRACTOR SHALL PROVIDE SITE SIGNAGE IN ACCORDANCE WITH THE TECHNICAL SPECIFICATION FOR SITE SIGNAGE.
8. THE SITE SHALL BE GRADED TO CAUSE SURFACE WATER TO FLOW AWAY FROM THE BTS EQUIPMENT AND TOWER AREAS.
9. NO FILL OR EMBANKMENT MATERIAL SHALL BE PLACED ON FROZEN GROUND. FROZEN MATERIALS, SNOW OR ICE SHALL NOT BE PLACED IN ANY FILL OR EMBANKMENT.
10. THE SUB GRADE SHALL BE COMPACTED AND BROUGHT TO A SMOOTH UNIFORM GRADE PRIOR TO FINISHED SURFACE APPLICATION.
11. THE AREAS OF THE OWNERS PROPERTY DISTURBED BY THE WORK AND NOT COVERED BY THE TOWER, EQUIPMENT OR DRIVEWAY, SHALL BE GRADED TO A UNIFORM SLOPE, AND STABILIZED TO PREVENT EROSION AS SPECIFIED ON THE PROJECT SPECIFICATIONS.
12. SUBCONTRACTOR SHALL MINIMIZE DISTURBANCE TO EXISTING SITE DURING CONSTRUCTION. EROSION CONTROL MEASURES, IF REQUIRED DURING CONSTRUCTION, SHALL BE IN CONFORMANCE WITH THE LOCAL GUIDELINES FOR EROSION AND SEDIMENT CONTROL.
13. NOTICE TO PROCEED- NO WORK TO COMMENCE PRIOR TO COMPANY'S WRITTEN NOTICE TO PROCEED AND THE ISSUANCE OF A PURCHASE ORDER.
14. ALL CONSTRUCTION MEANS AND METHODS; INCLUDING BUT NOT LIMITED TO, ERECTION PLANS, RIGGING PLANS, CLIMBING PLANS, AND RESCUE PLANS SHALL BE THE RESPONSIBILITY OF THE GENERAL CONTRACTOR RESPONSIBLE FOR THE EXECUTION OF THE WORK CONTAINED HEREIN AND SHALL MEET ANSI/TIA 1019 (LATEST EDITION), OSHA, AND GENERAL INDUSTRY STANDARDS. ALL RIGGING PLANS SHALL ADHERE TO ANSI/TIA-1019 (LATEST EDITION) INCLUDING THE REQUIRED INVOLVEMENT OF A QUALIFIED ENGINEER FOR CLASS IV CONSTRUCTION.

SPRINT CONSTRUCTION NOTES

SECTION 01 100 - SCOPE OF WORK

THE WORK:

MUST COMPLY WITH ALL APPLICABLE ADOPTED CODES AND STANDARDS, AND PORTIONS THEREOF. SPRINT METHOD OF PROCEDURE (MOP) AND SPRINT STANDARDS AT THE TIME OF CONSTRUCTION START.

PRECEDENCE:

SHOULD CONFLICTS OCCUR BETWEEN THE STANDARD CONSTRUCTION SPECIFICATIONS FOR WIRELESS SITES INCLUDING THE STANDARD DETAILS FOR WIRELESS SITES AND THE CONSTRUCTION DRAWINGS, INFORMATION ON THE CONSTRUCTION DRAWINGS SHALL TAKE PRECEDENCE. ALONG WITH SPRINT CONSTRUCTION MANAGER APPROVAL.

SITE FAMILIARITY:

CONTRACTOR SHALL BE RESPONSIBLE FOR FAMILIARIZING THEMSELVES WITH ALL CONTRACT DOCUMENTS, FIELD CONDITIONS AND DIMENSIONS PRIOR TO PROCEEDING WITH CONSTRUCTION.

ON-SITE SUPERVISION:

THE CONTRACTOR SHALL SUPERVISE AND DIRECT THE WORK AND SHALL BE RESPONSIBLE FOR CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES, AND PROCEDURES IN ACCORDANCE WITH THE CONTRACT DOCUMENTS.

DRAWINGS, SPECIFICATIONS AND DETAILS REQUIRED AT JOBSITE:

THE CONSTRUCTION CONTRACTOR SHALL MAINTAIN A FULL SET OF THE CONSTRUCTION DRAWINGS AT THE JOBSITE FROM MOBILIZATION THROUGH CONSTRUCTION COMPLETION.

A. DETAILS ARE INTENDED TO SHOW DESIGN INTENT. PROVIDE ALL MATERIALS AND LABOR AS REQUIRED TO PROVIDE A COMPLETE FUNCTIONING SYSTEM. MODIFICATIONS MAY BE REQUIRED TO SUITE JOB DIMENSIONS OR CONDITIONS, AND SUCH MODIFICATIONS SHALL BE INCLUDED AS PART OF THE WORK.

B. CONTRACTOR SHALL NOTIFY SPRINT CONSTRUCTION MANAGER OF ANY VARIATIONS PRIOR TO PROCEEDING WITH THE WORK. DIMENSIONS SHOWN ARE TO FINISH SURFACES UNLESS NOTED OTHERWISE. MODIFICATIONS MAY BE REQUIRED TO SUIT JOB DIMENSIONS OR CONDITIONS, AND SUCH MODIFICATIONS SHALL BE INCLUDED AS PART OF THE WORK.

C. MARK THE FIELD SET OF DRAWINGS IN RED, DOCUMENTING ANY CHANGES FROM THE CONSTRUCTION DOCUMENTS.

METHODS OF PROCEDURE (MOPS) FOR CONSTRUCTION:

CONTRACTOR SHALL PERFORM WORK AS DESCRIBED IN THE FOLLOWING INSTALLATION AND COMMISSIONING MOPS. CONTRACTOR IS RESPONSIBLE FOR DISTRIBUTION OF LATEST MOPS.

- A. TOP HAT
- B. HOW TO INSTALL A NEW CABINET
- C. BASE BAND UNIT IN EXISTING UNIT
- D. INSTALLATION OF BATTERIES
- E. INSTALLATION OF FIBER CABLE
- F. INSTALLATION OF RRU'S
- G. CABLING
- H. TS-0200 REV 5 - ANTENNA LINE ACCEPTANCE STANDARDS
- I. SPRINT CELL SITE ENGINEERING NOTICE - EN 2012-001, REV 1.
- J. COMMISSIONING MOPS

SECTION 01 200 - COMPANY FURNISHED MATERIAL AND EQUIPMENT

- A. COMPANY FURNISHED MATERIAL AND EQUIPMENT IS IDENTIFIED ON THE RF DATA SHEET IN THE CONSTRUCTION DRAWINGS.
- B. CONTRACTOR IS RESPONSIBLE FOR SPRINT PROVIDED MATERIAL AND EQUIPMENT TO ENSURE IT IS PROTECTED AND HANDLED PROPERLY THROUGHOUT THE CONSTRUCTION DURATION.
- C. CONTRACTOR IS RESPONSIBLE FOR RECEIPT OF SPRINT FURNISHED EQUIPMENT AT CELL SITE OR CONTRACTORS LOCATION. CONTRACTOR TO COMPLETE SHIPPING AND RECEIPT DOCUMENTATION

IN ACCORDANCE WITH COMPANY PRACTICE. CONTRACTOR MAY BE REQUIRED TO PICK UP MATERIAL AT LOCATION PRESCRIBED BY SPRINT.

SECTION 01 300 - CELL SITE CONSTRUCTION

NOTICE TO PROCEED:

NO WORK SHALL COMMENCE PRIOR TO COMPANY'S WRITTEN NOTICE TO PROCEED AND THE ISSUANCE OF WORK ORDER.

SITE CLEANLINESS:

CONTRACTOR SHALL KEEP THE SITE FREE FROM ACCUMULATING WASTE MATERIAL, DEBRIS, AND TRASH AT THE COMPLETION OF THE WORK, CONTRACTOR SHALL REMOVE FROM THE SITE ALL REMAINING RUBBISH, IMPLEMENTS, TEMPORARY FACILITIES, AND SURPLUS MATERIALS.

SECTION 01 400 - SUBMITTALS AND TESTS

ALTERNATIVES:

AT THE COMPANY'S REQUEST, ANY ALTERNATIVES TO THE MATERIALS OR METHODS SPECIFIED SHALL BE SUBMITTED TO SPRINT'S CONSTRUCTION MANAGER FOR APPROVAL. SPRINT WILL REVIEW AND APPROVE ONLY THOSE REQUESTS MADE IN WRITING. NO VERBAL APPROVALS WILL BE CONSIDERED.

TESTS AND INSPECTIONS:

A. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL CONSTRUCTION TESTS, INSPECTIONS AND PROJECT DOCUMENTATION.

B. CONTRACTOR SHALL ACCOMPLISH TESTING INCLUDING BUT NOT LIMITED TO THE FOLLOWING:

1. COAX SWEEPS AND FIBER TESTS PER TS-200 REV 5 ANTENNA LINE ACCEPTANCE STANDARDS.
2. AZIMUTH AND DOWNTILT: PROVIDE AN AUTOMATED REPORT UPLOADED TO SITERRA USING A COMMERCIAL MADE-FOR PURPOSE ELECTRONIC ANTENNA ALIGNMENT TOOL (AAT). INSTALLED AZIMUTH, CENTERLINE AND DOWNTILT MUST CONFORM WITH RF CONFIGURATION DATA.
3. CONTRACTOR SHALL BE RESPONSIBLE FOR ANY AND ALL CORRECTIONS TO ANY WORK IDENTIFIED AS UNACCEPTABLE IN SITE INSPECTION ACTIVITIES AND/OR AS A RESULT OF TESTING.
4. ALL TESTING REQUIRED BY APPLICABLE INSTALLATION MOPS.

C. REQUIRED CLOSEOUT DOCUMENTATION INCLUDES, BUT IS NOT LIMITED TO THE FOLLOWING:

1. AZIMUTH, DOWNTILT, AGL FROM SUNSIGHT INSTRUMENTS - ANTENNA ALIGNMENT TOOL (AAT)
2. SWEEP AND FIBER TESTS.
3. SCANABLE BARCODE PHOTOGRAPHS OF TOWER TOP AND INACCESSIBLE SERIALIZED EQUIPMENT.
4. ALL AVAILABLE JURISDICTIONAL PERMIT AND OCCUPANCY INFORMATION.
5. PDF SCAN OF REDLINES PRODUCED IN FIELD.
6. A PDF SCAN OF REDLINE MARK-UPS SUITABLE FOR USE IN ELECTRONIC AS-BUILT DRAWING PRODUCTION.
7. LIEN WAIVERS.
8. FINAL PAYMENT APPLICATION.
9. REQUIRED FINAL CONSTRUCTION PHOTOS.
10. CONSTRUCTION AND COMMISSIONING CHECKLIST COMPLETE WITH NO DEFICIENT ITEMS.
11. APPLICABLE POST NTP TASKS INCLUDING DOCUMENT UPLOADS COMPLETED IN SITERRA (SPRINT'S DOCUMENT REPOSITORY OF RECORD).
12. CLOSEOUT PHOTOGRAPHS AND CLOSEOUT CHECKLIST: SPRINT WILL PROVIDE SEPARATE GUIDANCE.

a. PROVIDE PHOTOGRAPHS OF FINAL PROJECT PER THE FOLLOWING LIST. ADDITIONAL PHOTOS MAY BE REQUIRED TO SUPPORT ACCEPTANCE PROCESSES

- (i) BACK MAIN FIBER CABLE ROUTE (MINIMUM TWO PHOTOS)
 - (ii) OF EACH ANTENNA AND RRU
 - (iii) MANUFACTURERS NAME TAG FOR ALL SERIALIZED EQUIPMENT
 - (iv) PULL AND DISTRIBUTION BOXES INTERMEDIATE BETWEEN RRU'S AND RBS (DOOR OPEN)
 - (v) RBS CABINET WITH DOOR OPEN SHOWING MODIFICATIONS
 - (vi) POWER CABINET, DOORS OPEN, BATTERIES INSTALLED
 - (vii) BREAK OUT CYLINDERS
 - (viii) ASR SIGNAGE FOR SPRINT OWNED TOWERS
 - (ix) RADIATION EXPOSURE WARNING SIGNS
 - (x) PHOTOGRAPH FROM EACH SECTOR FROM APPROXIMATELY RAD CENTER OF ANY NEW ANTENNA AT HORIZON.
- b. LOAD PHOTOS TO SITERRA PROJECT LIBRARY 15. IN 15 CREATE NEW CATEGORY: 2.5 DEPLOYMENT, AND SECTION: PERMANENT CONSTRUCTION. LABEL PHOTOS WITH SITE CASCADE AND VIEW BEING DEPICTED. CAMERAS USED TO TAKE PHOTOS SHALL BE GPS ENABLED SUCH THAT THE GPS COORDINATES ARE INCLUDED IN THE PHOTO MEDIA-FILE INFORMATION.

COMMISSIONING:

PERFORM ALL COMMISSIONING AS REQUIRED BY APPLICABLE MOPS

INTEGRATION:

PERFORM ALL INTEGRATION ACTIVITIES AS REQUIRED BY APPLICABLE MOPS

SECTION 09 900 - PAINTING

QUALITY ASSURANCE:

A. COMPLY WITH GOVERNING CODES AND REGULATIONS. PROVIDE PRODUCTS OF ACCEPTABLE MANUFACTURERS WHICH HAVE BEEN IN SATISFACTORY USE IN SIMILAR SERVICE FOR THREE YEARS. USE EXPERIENCED INSTALLERS. DELIVER, HANDLE, AND STORE MATERIALS IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.

B. COMPLY WITH ALL ENVIRONMENTAL REGULATIONS FOR VOLATILE ORGANIC COMPOUNDS.

MATERIALS:

A. MANUFACTURERS: BENJAMIN MOORE, ICI DEVOE COATINGS, PPG, SHERWIN WILLIAMS OR APPROVED PROVIDE PREMIUM GRADE, PROFESSIONAL-QUALITY PRODUCTS FOR COATING SYSTEMS.

PAINT SCHEDULE:

A. EXTERIOR ANTENNAE AND ANTENNA MOUNTING HARDWARE: ONE COAT OF PRIMER AND TWO FINISH COATS. PAINT FOR ANTENNAE SHALL BE NON-METALLIC BASED AND CONTAIN NO METALLIC PARTICLES. PROVIDE COLORS AND PATTERNS AS REQUIRED TO MASK APPEARANCE OF ANTENNAE ON ADJACENT BUILDING SURFACES AND AS ACCEPTABLE TO THE OWNER. REFER TO ANTENNA MANUFACTURER'S INSTRUCTION WHENEVER POSSIBLE.

B. WATER TANKS: TOUCH UP - PREPARE SURFACES TO BE REPAIRED. FOLLOW INDUSTRY STANDARDS AND REQUIREMENTS OF OWNER TO MATCH EXISTING COATING AND FINISH.

PAINTING APPLICATION:

1. INSPECT SURFACES, REPORT UNSATISFACTORY CONDITIONS IN WRITING; BEGINNING WORK MEANS ACCEPTANCE OF SUBSTRATE.
2. COMPLY WITH MANUFACTURER'S INSTRUCTIONS AND RECOMMENDATIONS FOR PREPARATION, PRIMING AND COATING WORK. COORDINATE WITH WORK OF OTHER SECTIONS.
3. MATCH APPROVED MOCK-UPS FOR COLOR, TEXTURE, AND PATTERN. RE-COAT OR REMOVE AND REPLACE WORK WHICH DOES NOT MATCH OR SHOWS LOSS OF ADHESION.
4. CLEAN UP, TOUCH UP AND PROTECT WORK.

TOUCHUP PAINTING:

1. GALVANIZING DAMAGE AND ALL BOLTS AND NUTS SHALL BE TOUCHED UP AFTER TOWER ERECTION WITH "GALVANOX," "DRY GALV," OR "ZINC-IT."
2. FIELD TOUCHUP PAINT SHALL BE DONE IN ACCORDANCE WITH THE MANUFACTURER'S WRITTEN INSTRUCTIONS.
3. ALL METAL COMPONENTS SHALL BE HANDLED WITH CARE TO PREVENT DAMAGE TO THE COMPONENTS, THEIR PRESERVATIVE TREATMENT, OR THEIR PROTECTIVE COATINGS.

SECTION 11 700 - ANTENNA ASSEMBLY, REMOTE RADIO UNITS AND CABLE INSTALLATION

SUMMARY:

THIS SECTION SPECIFIES INSTALLATION OF ANTENNAS, RRU'S, AND CABLE EQUIPMENT, INSTALLATION, AND TESTING OF COAXIAL FIBER CABLE.

ANTENNAS AND RRU'S:

THE NUMBER AND TYPE OF ANTENNAS AND RRU'S TO BE INSTALLED IS DETAILED ON THE CONSTRUCTION DRAWINGS.

NV FIBER CABLE:

EXISTING NV FIBER CABLE WILL BE USED AT EACH SITE. CABLE SHALL BE USED PER THE CONSTRUCTION DRAWINGS AND THE APPLICABLE MANUFACTURER'S REQUIREMENTS.

JUMPERS AND CONNECTIONS:

FURNISH AND INSTALL 1/2" COAX JUMPER CABLES BETWEEN THE RRU'S AND ANTENNAS. JUMPERS SHALL BE TYPE LDF 4, FLC 12-50, CR 540, OR FXL 540. SUPER-FLEX CABLES ARE NOT ACCEPTABLE JUMPERS BETWEEN THE RRU'S AND ANTENNAS OR TOWER TOP AMPLIFIERS SHALL CONSIST OF 1/2" FOAM DIELECTRIC, OUTDOOR RATED COAXIAL CABLE. MINIMUM LENGTH FOR JUMPER SHALL BE SO AS TO ALLOW FOR THE PROPER BEND RADIUS PER MANUFACTURER OR SPRINT SPECIFICATIONS.

REMOTE ELECTRICAL TILT (RET) CABLES:

MISCELLANEOUS:

INSTALL SPLITTERS, COMBINERS, FILTERS PER RF DATA SHEET, FURNISHED BY SPRINT.

ANTENNA INSTALLATION:

THE CONTRACTOR SHALL ASSEMBLE ALL ANTENNAS ONSITE IN ACCORDANCE WITH THE INSTRUCTIONS SUPPLIED BY THE MANUFACTURER. ANTENNA HEIGHT, AZIMUTH AND FEED ORIENTATION INFORMATION SHALL BE AS DESIGNATED ON THE CONSTRUCTION DRAWINGS.

A. THE CONTRACTOR SHALL POSITION THE ANTENNA ON TOWER PIPE MOUNTS SO THAT THE BOTTOM STRUT IS LEVEL. THE PIPE MOUNTS SHALL BE PLUMB TO WITHIN 1 DEGREE.

B. ANTENNA MOUNTING REQUIREMENTS: PROVIDE ANTENNA MOUNTING HARDWARE AS INDICATED ON THE CONSTRUCTION DRAWINGS.

FIBER CABLE INSTALLATION:

A. THE CONTRACTOR SHALL ROUTE, TEST AND INSTALL ALL CABLES AS INDICATED ON THE CONSTRUCTION DRAWINGS AND IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS.

B. THE INSTALLED RADIUS OF THE CABLES SHALL NOT BE LESS THAT THE MANUFACTURER'S SPECIFICATIONS FOR BENDING RADI.

C. EXTREME CARE SHALL BE TAKEN TO AVOID DAMAGE TO THE CABLES DURING HANDLING AND INSTALLATION.

1. FASTENING MAIN FIBER CABLES:

a. LATTICE AND GUYED TOWERS:

ALL CABLES SHALL BE PERMANENTLY FASTENED TO THE COAX LADDER AT 4'-0" OC USING NON-MAGNETIC STAINLESS STEEL CLIPS. HOISTING GRIPS SHOULD BE INSTALLED AT MID-POINT IF CABLE RUN EXCEEDS 200' AS WELL AS TOP SIDE.

a. MONOPOLE:

ALL CABLES SHALL BE PERMANENTLY SUPPORTED WITH HOISTING GRIPS AT INTERVALS OF NO MORE THAN 200' (ONE HOISTING GRIP PER COAX).

1. FASTENING INDIVIDUAL FIBER AND DC CABLES ABOVE BREAKOUT ENCLOSURE (MEDUSA). WITHIN THE MMBS CABINET AND ANY INTERMEDIATE DISTRIBUTION BOXES.

a. FIBER: SUPPORT FIBER BUNDLES USING 1/2" VELCRO STRAPS OF THE REQUIRED LENGTH AT 18" O.C. STRAPS SHALL BE UV, OIL AND WATER RESISTANT AND SUITABLE FOR INDUSTRIAL INSTALLATIONS AS MANUFACTURED BY TEXTOL OR APPROVED EQUAL.

b. DC: SUPPORT DC BUNDLES WITH ZIP TIES OF THE ADEQUATE LENGTH. ZIP TIES TO BE UV STABILIZED, BLACK NYLON, WITH TENSILE STRENGTH AT 12,000 PSI AS MANUFACTURED BY NELCO PRODUCTS OR EQUAL.

2. FASTENING OR SECURING JUMPERS SHOULD CONSIST OF STAINLESS STEEL CLIPS, 18" FROM REAR OF CONNECTOR AND 24" THEREAFTER AND AT NO TIME SHALL THEY CONTACT TOWER OR STRUCTURAL STEEL.

3. CABLE INSTALLATION:

a. INSPECT CABLE PRIOR TO USE FOR SHIPPING DAMAGE. NOTIFY THE CONSTRUCTION MANAGER.

b. CABLE ROUTING CABLE INSTALLATION SHALL BE PLANNED TO ENSURE THAT THE LINES WILL BE PROPERLY ROUTED IN THE CABLE ENVELOPE AS INDICATED ON THE DRAWINGS. AVOID TWISTING AND CROSSOVERS.

c. HOIST CABLE USING PROPER HOISTING GRIPS. DO NOT EXCEED MANUFACTURER'S RECOMMENDED MAXIMUM BEND RADIUS.

5. GROUNDING OF TRANSMISSION LINES: ALL TRANSMISSION LINES SHALL BE GROUNDED AS INDICATED ON DRAWINGS.

6. HYBRID CABLE COLOR CODING: ALL COLOR CODING SHALL BE AS REQUIRED IN TS 0200 REV 5.

7. HYBRID CABLE LABELING: INDIVIDUAL HYBRID AND DC BUNDLES SHALL BE LABELED ALPHA-NUMERICALLY A ACCORDING TO SPRINT CELL SITE ENGINEERING NOTICE - EN 2012-001, REV 1.



SPRINT SITE NUMBER:
CT03XC166


BU #: **806382**
HRT **082 943274**

74 GOODRICH LANE
PORTLAND, CT 06480

EXISTING 160'-0" MONOPOLE

ISSUED FOR:

REV	DATE	DRWN	DESCRIPTION	DES./QA
A	01/03/18	TDG	PRELIMINARY	LMR
0	07/18/18	JHW	CONSTRUCTION	AJF
1	10/03/18	LMR	CONSTRUCTION	JPL



Crown Castle USA Inc. Certificate of Registration #PEC.0001101

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SHEET NUMBER: **T-2** REVISION: **1**

WEATHERPROOFING EXTERIOR CONNECTORS AND HYBRID CABLE GROUND KITS:

- A. ALL FIBER AND COAX CONNECTORS AND GROUND KITS SHALL BE WEATHERPROOFED.
- B. WEATHERPROOFED USING ONE OF THE FOLLOWING METHODS. ALL INSTALLATIONS MUST BE IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS AND INDUSTRY BEST PRACTICES.

1. SELF-AMALGAMATING TAPE: CLEAN SURFACES. APPLY A DOUBLE WRAP OF SELF AMALGAMATING TAPE 2" BEYOND CONNECTOR. APPLY A SECOND WRAP OF SELF-AMALGAMATING TAPE IN OPPOSITE DIRECTION. APPLY DOUBLE WRAP OF 2" WIDE ELECTRICAL TAPE EXTENDING 2" BEYOND THE SELF AMALGAMATING TAPE.
2. 3M SLIM LOCK CLOSURE 716: SUBSTITUTIONS WILL NOT BE ALLOWED.
3. JMA-WPS SERIES ENCLOSURE.
4. BUTYL AND TAPE, 1 COMPLETE WRAP OF 3/4" PRE-TAPE, BUTYL WRAPPED IN HALF INCH LAP LAYERS, ENDED WITH SHINGLED DOWNWARD 3 WRAPS OF 2" TAPE, 3 WRAPS OF 3/4" TAPE SHINGLED DOWNWARD, FREE OF WRINKLES, BUCKLES AND FLAGGING.
5. OPEN FLAME ON JOB SITE IS NOT ACCEPTABLE

- C. ANTENNA MOUNTING REQUIREMENTS: PROVIDE ANTENNA MOUNTING HARDWARE AS INDICATED ON THE CONSTRUCTION DRAWINGS.

FIBER CABLE INSTALLATION:

- A. THE CONTRACTOR SHALL ROUTE, TEST AND INSTALL ALL CABLES AS INDICATED ON THE CONSTRUCTION DRAWINGS AND IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS.

- B. THE INSTALLED RADIUS OF THE CABLES SHALL NOT BE LESS THAT THE MANUFACTURER'S SPECIFICATIONS FOR BENDING RADII.

- C. EXTREME CARE SHALL BE TAKEN TO AVOID DAMAGE TO THE CABLES DURING HANDLING AND INSTALLATION.

- 1. FASTENING MAIN FIBER CABLES:

a. LATTICE AND GUYED TOWERS:

ALL CABLES SHALL BE PERMANENTLY FASTENED TO THE COAX LADDER AT 4'-0" OC USING NON-MAGNETIC STAINLESS STEEL CLIPS. HOISTING GRIPS SHOULD BE INSTALLED AT MID-POINT IF CABLE RUN EXCEEDS 200' AS WELL AS TOP SIDE.

b. MONOPOLE:

ALL CABLES SHALL BE PERMANENTLY SUPPORTED WITH HOISTING GRIPS AT INTERVALS OF NO MORE THAN 200' (ONE HOISTING GRIP PER COAX).

- 2. FASTENING INDIVIDUAL FIBER AND DC CABLES ABOVE BREAKOUT ENCLOSURE (MEDUSA). WITHIN THE MMBS CABINET AND ANY INTERMEDIATE DISTRIBUTION BOXES.

a. FIBER: SUPPORT FIBER BUNDLES USING 1/2" VELCRO STRAPS OF THE REQUIRED LENGTH AT 18" O.C. STRAPS SHALL BE UV, OIL AND WATER RESISTANT AND SUITABLE FOR INDUSTRIAL INSTALLATIONS AS MANUFACTURED BY TEXTOL OR APPROVED EQUAL.

b. DC: SUPPORT DC BUNDLES WITH ZIP TIES OF THE ADEQUATE LENGTH. ZIP TIES TO BE UV STABILIZED, BLACK NYLON, WITH TENSILE STRENGTH AT 12,000 PSI AS MANUFACTURED BY NELCO PRODUCTS OR EQUAL.

- 3. FASTENING OR SECURING JUMPERS SHOULD CONSIST OF STAINLESS STEEL CLIPS, 18" FROM REAR OF CONNECTOR AND 24" THEREAFTER AND AT NO TIME SHALL THEY CONTACT TOWER OR STRUCTURAL STEEL.

- 4. CABLE INSTALLATION:

a. INSPECT CABLE PRIOR TO USE FOR SHIPPING DAMAGE. NOTIFY THE CONSTRUCTION MANAGER.

b. CABLE ROUTING CABLE INSTALLATION SHALL BE PLANNED TO ENSURE THAT THE LINES WILL BE PROPERLY ROUTED IN THE CABLE ENVELOPE AS INDICATED ON THE DRAWINGS. AVOID TWISTING AND CROSSOVERS.

c. HOIST CABLE USING PROPER HOISTING GRIPS. DO NOT EXCEED MANUFACTURER'S RECOMMENDED MAXIMUM BEND RADIUS.

- 5. GROUNDING OF TRANSMISSION LINES: ALL TRANSMISSION LINES SHALL BE GROUNDED AS INDICATED ON DRAWINGS.

- 6. HYBRID CABLE COLOR CODING: ALL COLOR CODING SHALL BE AS REQUIRED IN TS 0200 REV 5.

- 7. HYBRID CABLE LABELING: INDIVIDUAL HYBRID AND DC BUNDLES SHALL BE LABELED ALPHA-NUMERICALLY ACCORDING TO SPRINT CELL SITE ENGINEERING NOTICE - EN 2012-001, REV 1.

WEATHERPROOFING EXTERIOR CONNECTORS AND HYBRID CABLE GROUND KITS:

- A. ALL FIBER AND COAX CONNECTORS AND GROUND KITS SHALL BE WEATHERPROOFED.

- B. WEATHERPROOFED USING ONE OF THE FOLLOWING METHODS. ALL INSTALLATIONS MUST BE IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS AND INDUSTRY BEST PRACTICES.

1. SELF-AMALGAMATING TAPE: CLEAN SURFACES. APPLY A DOUBLE WRAP OF SELF AMALGAMATING TAPE 2" BEYOND CONNECTOR. APPLY A SECOND WRAP OF SELF-AMALGAMATING TAPE IN OPPOSITE DIRECTION. APPLY DOUBLE WRAP OF 2" WIDE ELECTRICAL TAPE EXTENDING 2" BEYOND THE SELF AMALGAMATING TAPE.
2. 3M SLIM LOCK CLOSURE 716: SUBSTITUTIONS WILL NOT BE ALLOWED.
3. JMA-WPS SERIES ENCLOSURE.
4. BUTYL AND TAPE, 1 COMPLETE WRAP OF 3/4" PRE-TAPE, BUTYL WRAPPED IN HALF INCH LAP LAYERS, ENDED WITH SHINGLED DOWNWARD 3 WRAPS OF 2" TAPE, 3 WRAPS OF 3/4" TAPE SHINGLED DOWNWARD, FREE OF WRINKLES, BUCKLES AND FLAGGING.
5. OPEN FLAME ON JOB SITE IS NOT ACCEPTABLE

SECTION 11 800 - INSTALLATION OF MULTIMODAL BASE STATIONS (MMBS) AND RELATED EQUIPMENT

SUMMARY:

A. THIS SECTION SPECIFIES MMBS CABINETS, POWER CABINETS, AND INTERNAL EQUIPMENT INCLUDING BUT NOT LIMITED TO RECTIFIERS, POWER DISTRIBUTION UNITS, BASE BAND UNITS, SURGE ARRESTORS, BATTERIES, AND SIMILAR EQUIPMENT FURNISHED BY THE COMPANY FOR INSTALLATION BY THE CONTRACTOR (OFC).

B. CONTRACTOR SHALL PROVIDE AND INSTALL ALL MISCELLANEOUS MATERIALS AND PROVIDE ALL LABOR REQUIRED FOR INSTALLATION EQUIPMENT IN EXISTING CABINET OR NEW CABINET AS SHOWN ON DRAWINGS AND AS REQUIRED

BY THE APPLICABLE INSTALLATION MOPS.

- C. COMPLY WITH MANUFACTURER'S INSTALLATION AND START-UP REQUIREMENTS.

DC CIRCUIT BREAKER LABELING:

- A. LABEL CIRCUIT BREAKERS ACCORDING TO SPRINT CELL SITE ENGINEERING NOTICE - EN 2012-001, REV 1. SECTION 26 100 - BASIC ELECTRICAL REQUIREMENTS

SUMMARY:

THIS SECTION SPECIFIES BASIC ELECTRICAL REQUIREMENTS FOR SYSTEMS AND COMPONENTS.

QUALITY ASSURANCE:

A. ALL EQUIPMENT FURNISHED UNDER DIVISION 26 SHALL CARRY UL LABELS AND LISTINGS WHERE SUCH LABELS AND LISTING ARE AVAILABLE IN THE INDUSTRY.

B. MANUFACTURERS OF EQUIPMENT SHALL HAVE A MINIMUM OF THREE YEARS EXPERIENCE WITH THEIR EQUIPMENT INSTALLED AND OPERATING IN THE FIELD IN A USE SIMILAR TO THE NEW USE FOR THIS PROJECT.

C. MATERIALS AND EQUIPMENT: ALL MATERIALS AND EQUIPMENT SPECIFIED IN DIVISION 26 OF THE SAME TYPE SHALL BE OF THE SAME MANUFACTURER AND SHALL BE NEW, OF THE BEST QUALITY AND DESIGN, AND FREE FROM DEFECTS.

SUPPORTING DEVICES:

A. MANUFACTURED STRUCTURAL SUPPORT MATERIALS: SUBJECT TO COMPLIANCE WITH REQUIREMENTS. PROVIDE PRODUCTS BY THE FOLLOWING:

1. ALLIED TUBE AND CONDUIT.
2. B-LINE SYSTEM.
3. UNISTRUT DIVERSIFIED PRODUCTS.
4. THOMAS & BETTS

B. FASTENERS: TYPES, MATERIALS AND CONSTRUCTION FEATURES AS FOLLOWS:

1. EXPANSION ANCHORS: CARBON STEEL WEDGE OR SLEEVE TYPE.
2. POWER-DRIVEN THREADED STUDS: HEAT-TREATED STEEL. DESIGNED SPECIFICALLY FOR THE INTENDED SERVICE.
3. FASTEN BY MEANS OF WOOD SCREWS IN WOOD.
4. TOGGLE BOLTS ON HOLLOW MASONRY UNITS.
5. CONCRETE INSERTS OR EXPANSION BOLTS ON CONCRETE OR SOLID MASONRY.
6. MACHINE SCREWS, WELDED THREADED STUDS, OR SPRING-TENSION CLAMPS ON STEEL.
7. EXPLOSIVE DEVICES FOR ATTACHING HANGERS TO STRUCTURE SHALL NOT BE PERMITTED.
8. DO NOT WELD CONDUIT, PIPE STRAPS, OR ITEMS OTHER THAN THREADED STUDS TO STEEL STRUCTURES.
9. IN PARTITIONS OF LIGHT STEEL CONSTRUCTION, USE SHEET METAL SCREWS.

SUPPORTING DEVICES:

A. INSTALL SUPPORTING DEVICES TO FASTEN ELECTRICAL COMPONENTS SECURELY AND PERMANENTLY IN ACCORDANCE WITH NEC.

B. COORDINATE WITH THE BUILDING STRUCTURAL SYSTEM AND WITH OTHER TRADES.

C. UNLESS OTHERWISE INDICATED ON THE DRAWINGS, FASTEN ELECTRICAL ITEMS AND THEIR SUPPORTING HARDWARE SECURELY TO THE STRUCTURE IN ACCORDANCE WITH THE FOLLOWING:

1. ENSURE THAT THE LOAD APPLIED BY ANY FASTENER DOES NOT EXCEED 25 PERCENT OF THE PROOF TEST LOAD.
2. USE VIBRATION AND SHOCK-RESISTANT FASTNERS FOR ATTACHMENTS TO CONCRETE SLABS.

ELECTRICAL IDENTIFICATION:

A. UPDATE AND PROVIDE TYPED CIRCUIT BREAKER SCHEDULES IN THE MOUNTING BRACKET, INSIDE DOORS OF AC PANEL BOARDS WITH ANY CHANGES MADE TO THE AC SYSTEM.

B. BRANCH CIRCUITS FEEDING AVIATION OBSTRUCTION LIGHTING EQUIPMENT SHALL BE CLEARLY IDENTIFIED AS SUCH AT THE BRANCH CIRCUIT PANELBOARD.

SECTION 26 200 - ELECTRICAL MATERIALS AND EQUIPMENT

CONDUIT:

A. RIGID GALVANIZED STEEL (RGS) CONDUIT SHALL BE USED FOR EXTERIOR LOCATIONS ABOVE GROUND AND IN UNFINISHED INTERIOR LOCATIONS AND FOR UNDERGROUND RUNS. RIGID CONDUIT AND FITTINGS SHALL BE STEEL, COATED WITH ZINC EXTERIOR AND INTERIOR BY THE HOT DIP GALVANIZING PROCESS. CONDUIT SHALL BE PRODUCED TO ANSI SPECIFICATIONS C80.1, FEDERAL SPECIFICATION WW-C-581 AND SHALL BE LISTED WITH THE UNDERWRITERS' LABORATORIES. FITTINGS SHALL BE THREADED - SET SCREW OR COMPRESSION FITTINGS WILL NOT BE ACCEPTABLE. RGS CONDUITS SHALL BE MANUFACTURED BY ALLIED, REPUBLIC OR WHEATLAND.

B. UNDERGROUND CONDUIT IN CONCRETE SHALL BE POLYVINYLCHLORIDE (PVC) SUITABLE FOR DIRECT BURIAL AS APPLICABLE. JOINTS SHALL BE BELLED, AND FLUSH SOLVENT WELDED IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS. CONDUIT SHALL BE CARLON ELECTRICAL PRODUCTS OR APPROVED EQUAL.

C. TRANSITIONS BETWEEN PVC AND RIGID (RGS) SHALL BE MADE WITH PVC COATED METALLIC LONG SWEEP RADIUS ELBOWS.

D. ALL UNDERGROUND CONDUIT OR CONDUIT IN CONCRETE SHOULD BE PVC. EMT OR RIGID GALVANIZED STEEL CONDUIT MAY BE USED IN FINISHED SPACES CONCEALED IN WALLS AND CEILINGS. EMT SHALL BE MILD STEEL, ELECTRICALLY WELDED, ELECTRO-GALVANIZED OR HOT-DIPPED GALVANIZED AND PRODUCED TO ANSI SPECIFICATIONS C80.3, FEDERAL SPECIFICATION WW-C-563, AND SHALL BE UL LISTED. EMT SHALL BE MANUFACTURED BY ALLIED, REPUBLIC OR WHEATLAND, OR APPROVED EQUAL. FITTINGS SHALL BE METALLIC COMPRESSION. SET SCREW CONNECTIONS SHALL NOT BE ACCEPTABLE.

E. LIQUID TIGHT FLEXIBLE METALLIC CONDUIT SHALL BE USED FOR FINAL CONNECTION TO EQUIPMENT FITTINGS SHALL BE METALLIC GLAND TYPE COMPRESSION FITTINGS, MAINTAINING THE INTEGRITY OF CONDUIT SYSTEM. SET SCREW CONNECTIONS SHALL NOT BE ACCEPTABLE. MAXIMUM LENGTH OF FLEXIBLE CONDUIT SHALL NOT EXCEED 6- FEET. LFMC SHALL BE PROTECTED AND SUPPORTED AS REQUIRED BY NEC. MANUFACTURERS OF FLEXIBLE CONDUITS SHALL BE CAROL, ANACONDA METAL HOSE OR UNIVERSAL METAL HOSE, OR APPROVED EQUAL.

F. MINIMUM SIZE CONDUIT SHALL BE 3/4 INCH (21MM).

HUBS AND BOXES:

A. AT ENTRANCES TO CABINETS OR OTHER EQUIPMENT NOT HAVING INTEGRAL THREADED HUBS PROVIDE METALLIC THREADED HUBS OF THE SIZE AND CONFIGURATION REQUIRED HUB SHALL INCLUDE LOCK NUT AND NEOPRENE O-RING SEAL. PROVIDE IMPACT RESISTANT 105 DEGREE C PLASTIC BUSHINGS TO PROTECT CABLE INSULATION

- B. CABLE TERMINATION FITTINGS FOR CONDUIT

- 1. CABLE TERMINATORS FOR RGS CONDUITS SHALL BE TYPE CRC BY O-Z/GEDNEY OR EQUAL BY ROXTEC.

- 2. CABLE TERMINATORS FOR LFMC SHALL BE ETCO - CL2075, OR MADE FOR THE PURPOSE PRODUCTS BY ROXTEC.

C. EXTERIOR PULL BOXES AND PULL BOXES IN INTERIOR INDUSTRIAL AREAS SHALL BE PLATED CAST ALLOY, HEAVY DUTY, WEATHERPROOF, DUST PROOF, WITH GASKET, PLATED IRON ALLOY COVER AND STAINLESS STEEL COVER SCREWS, CROUSE-HINDS WAB SERIES OR EQUAL.

D. CONDUIT OUTLET BODIES SHALL BE PLATED CAST ALLOY WITH SIMILAR GASKET COVERS. OUTLET BODIES SHALL BE OF THE CONFIGURATION AND SIZE SUITABLE FOR THE APPLICATION, PROVIDE CROUSE-HINDS FORM 8 OR EQUAL.

E. MANUFACTURER FOR BOXES AND COVERS SHALL BE HOFFMAN, SQUARE "D", CROUSE-HINDS, COOPER, ADALET, APPLETON, O-Z GEDNEY, RACO, OR APPROVED EQUAL.

SUPPLEMENTAL GROUNDING SYSTEM:

A. FURNISH AND INSTALL A SUPPLEMENTAL GROUNDING SYSTEM TO THE EXTENT INDICATED ON THE DRAWINGS. SUPPORT SYSTEM WITH NON-MAGNETIC STAINLESS STEEL CLIPS WITH RUBBER GROMMET. GROUNDING CONNECTORS SHALL BE TINNED COPPER WIRE, SIZES AS INDICATED ON THE DRAWINGS. PROVIDE STRANDED OR SOLID BARE OR INSULATED CONDUCTORS EXCEPT AS OTHERWISE NOTED.

B. SUPPLEMENTAL GROUNDING SYSTEM: ALL CONNECTIONS TO BE MADE WITH CAD WELDS, EXCEPT AT EQUIPMENT USE LUGS OR OTHER AVAILABLE GROUNDING MEANS AS REQUIRED BY MANUFACTURER; AT GROUND BARS USE TWO-HOLE SPADES WITH NO-OX.

C. STOLEN GROUND-BARS: IN THE EVENT OF STOLEN GROUND BARS, CONTACT SPRINT CONSTRUCTION MANAGER FOR REPLACEMENT INSTRUCTION USING THREADED ROD KITS.

EXISTING STRUCTURE:

A. EXISTING EXPOSED WIRING AND ALL EXPOSED OUTLETS, RECEPTACLES, SWITCHES, DEVICES, BOXES, AND OTHER EQUIPMENT THAT ARE NOT TO BE UTILIZED IN THE COMPLETED PROJECT SHALL BE REMOVED OR DE-ENERGIZED AND CAPPED IN THE WALL, CEILING, OR FLOOR SO THAT THEY ARE CONCEALED AND SAFE. WALL, CEILING, OR FLOOR SHALL BE PATCHED TO MATCH THE ADJACENT CONSTRUCTION.

CONDUIT AND CONDUCTOR INSTALLATION:

A. CONDUITS SHALL BE FASTENED SECURELY IN PLACE WITH APPROVED NON-PERFORATED STRAPS AND HANGERS. EXPLOSIVE DEVICES FOR ATTACHING HANGERS TO STRUCTURE WILL NOT BE PERMITTED. CLOSELY FOLLOW THE LINES OF THE STRUCTURE, MAINTAIN CLOSE PROXIMITY TO THE STRUCTURE AND KEEP CONDUITS IN TIGHT ENVELOPES. CHANGES IN DIRECTION TO ROUTE AROUND OBSTACLES SHALL BE MADE WITH CONDUIT OUTLET BODIES. CONDUIT SHALL BE INSTALLED IN A NEAT AND WORKMANLIKE MANNER, PARALLEL AND PERPENDICULAR TO STRUCTURE WALL AND CEILING LINES. ALL CONDUIT SHALL BE FISHED TO CLEAR OBSTRUCTIONS. ENDS OF CONDUITS SHALL BE TEMPORARILY CAPPED TO PREVENT CONCRETE, PLASTER OR DIRT FROM ENTERING. CONDUITS SHALL BE RIGIDLY CLAMPED TO BOXES BY GALVANIZED MALLEABLE IRON BUSHING ON INSIDE AND GALVANIZED MALLEABLE IRON LOCKNUT ON OUTSIDE AND INSIDE.

B. CONDUCTORS SHALL BE PULLED IN ACCORDANCE WITH ACCEPTED GOOD PRACTICE.

ADDITIONAL REQUIRED NOTES:

- GC IS RESPONSIBLE FOR HIRING ALL 3RD PARTY SPECIAL INSPECTIONS AS REQUIRED PER MUNICIPALITY
- GC IS RESPONSIBLE FOR VERIFYING ALL FIELD MEASUREMENTS PRIOR TO STARTING CONSTRUCTION
- DO NOT OPEN RRU PACKAGES IN THE RAIN
- NO OPEN FLAME ON SITE
- GC TO ENSURE HYBRIDS ARE SUPPORTED EVERY 3'-0" ON HORIZONTAL AND 4'-0" ON VERTICAL RUNS



6391 SPRINT PARKWAY
OVERLAND PARK, KS 66251-2650



3 CORPORATE PARK DRIVE, SUITE 101
CLIFTON PARK, NY 12065

SPRINT SITE NUMBER:
CT03XC166


BU #: **806382**
HRT **082 943274**

74 GOODRICH LANE
PORTLAND, CT 06480

EXISTING 160'-0" MONOPOLE

ISSUED FOR:

REV	DATE	DRWN	DESCRIPTION	DES./QA
A	01/03/18	TDG	PRELIMINARY	LMR
0	07/18/18	JHW	CONSTRUCTION	AJF
1	10/03/18	LMR	CONSTRUCTION	JPL



10/31/2018 10:52:32 AM EDT

Crown Castle USA Inc. Certificate of
Registration #PEC.0001101


IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

SHEET NUMBER:

T-3


REVISION:

1




1 OVERALL SITE PLAN

SCALE: 1/4"=1'-0" (FULL SIZE)
1/8"=1'-0" (11x17)



2 ENLARGED SITE PLAN

SCALE: 1"=1'-0" (FULL SIZE)
1/2"=1'-0" (11x17)



SPRINT SITE NUMBER:
CT03XC166


BU #: 806382
HRT 082 943274

74 GOODRICH LANE
PORTLAND, CT 06480

EXISTING 160'-0" MONOPOLE


ISSUED FOR:

REV	DATE	DRWN	DESCRIPTION	DES./QA
A	01/03/18	TDG	PRELIMINARY	LMR
0	07/18/18	JHW	CONSTRUCTION	AJF
1	10/03/18	LMR	CONSTRUCTION	JPL




IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SHEET NUMBER: **C-1** REVISION: **1**




SPRINT EQUIPMENT
ANTENNA CL: 152'-0"
MOUNT CL: 150'-0"

1 FINAL ELEVATION
SCALE: NOT TO SCALE



INSTALLER NOTE:
NO ADDITIONAL LOADING TO BE ADDED UNTIL MOUNT MODIFICATIONS ARE INSTALLED PER MOUNT MODIFICATION DESIGNED BY HUDSON DESIGN GROUP LLC DATED JUNE 20, 2018.



SPRINT SITE NUMBER:
CT03XC166


BU #: 806382
HRT 082 943274

74 GOODRICH LANE
PORTLAND, CT 06480

EXISTING 160'-0" MONOPOLE


ISSUED FOR:

REV	DATE	DRWN	DESCRIPTION	DES./QA
A	01/03/18	TDG	PRELIMINARY	LMR
0	07/18/18	JHW	CONSTRUCTION	AJF
1	10/03/18	LMR	CONSTRUCTION	JPL




IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SHEET NUMBER: **C-2** REVISION: **1**



1 ANTENNA MOUNTING ELEVATION
SCALE: NOT TO SCALE

2 NOT USED
SCALE: NOT TO SCALE



3 EQUIPMENT ELEVATION DETAIL
SCALE: NOT TO SCALE



6391 SPRINT PARKWAY
OVERLAND PARK, KS 66251-2650



3 CORPORATE PARK DRIVE, SUITE 101
CLIFTON PARK, NY 12065

SPRINT SITE NUMBER:
CT03XC166


BU #: 806382
HRT 082 943274

74 GOODRICH LANE
PORTLAND, CT 06480

EXISTING 160'-0" MONOPOLE

ISSUED FOR:

REV	DATE	DRWN	DESCRIPTION	DES./QA
A	01/03/18	TDG	PRELIMINARY	LMR
0	07/18/18	JHW	CONSTRUCTION	AJF
1	10/03/18	LMR	CONSTRUCTION	JPL



10/3/2018 10:52:32 AM EDT

Crown Castle USA Inc. Certificate of
Registration #PEC.0001101

IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

SHEET NUMBER: **C-3** REVISION: **1**

FIBER ONLY (EXISTING DC POWER)	HYBRID CABLE MN: HB058-M12-050F 12X MULTI-MODE FIBER PAIRS, TOP: OUTDOOR PROTECTED CONNECTORS, BOTTOM: LC CONNECTORS, 5/8" CABLE, 50 FT	50 FT
	MN: HB058-M12-075F	75 FT
	MN: HB058-M12-100F	100 FT
	MN: HB058-M12-125F	125 FT
	MN: HB058-M12-150F	150 FT
	MN: HB058-M12-175F	175 FT
	MN: HB058-M12-200F	200 FT

8 AWG POWER	HYBRID CABLE MN: HB114-08U3M12-050F 3X8 AWG POWER PAIRS, 12X MULTI-MODE FIBER PAIRS, OUTDOOR RATED CONNECTORS & LC CONNECTORS, 1-1/4" CABLE, 50 FT	50 FT
	MN: HB114-08U3M12-075F	75 FT
	MN: HB114-08U3M12-100F	100 FT
	MN: HB114-08U3M12-125F	125 FT
	MN: HB114-08U3M12-150F	150 FT
	MN: HB114-08U3M12-175F	175 FT
	MN: HB114-08U3M12-200F	200 FT

6 AWG POWER	HYBRID CABLE MN: HB114-13U3M12-225F 3X6 AWG POWER PAIRS, 12X MULTI-MODE FIBER PAIRS, OUTDOOR RATED CONNECTORS & LC CONNECTORS, 1-1/4" CABLE, 225 FT	225 FT
	MN: HB114-13U3M12-250F	250 FT
	MN: HB114-13U3M12-275F	275 FT
	MN: HB114-13U3M12-300F	300 FT

4 AWG POWER	HYBRID CABLE MN: HB114-21U3M12-325F 3X6 AWG POWER PAIRS, 12X MULTI-MODE FIBER PAIRS, OUTDOOR RATED CONNECTORS & LC CONNECTORS, 1-1/4" CABLE, 325 FT	325 FT
	MN: HB114-21U3M12-350F	350 FT
	MN: HB114-21U3M12-375F	375 FT

RFS HYBRIFLEX JUMPER CABLE SCHEDULE

FIBER ONLY	HYBRID JUMPER CABLE MN: HBFO12-M3-5F1 5 FT, 3X MULTI-MODE FIBER PAIRS, OUTDOOR & LC CONNECTORS, 1/2" CABLE	5 FT
	MN: HBFO12-M3-10F1	10 FT
	MN: HBFO12-M3-15F1	15 FT
SPECIAL INSTALLATION NOTE: JUMPERS FROM 2.5 RRH TO 2.5 ANTENNA SHALL NOT EXCEED 15' NOTIFY SPRINT CM OF ANY DISCREPANCY		




8 AWG POWER	HYBRID JUMPER CABLE MN: HBFO58-08U1M3-5F1 5 FT, 1X8 AWG POWER PAIR, 3X MULTI-MODE FIBER PAIRS, OUTDOOR & LC CONNECTORS, 5/8" CABLE	5 FT
	MN: HBFO58-08U1M3-10F1	10 FT
	MN: HBFO58-08U1M3-15F1	15 FT
SPECIAL INSTALLATION NOTE: JUMPERS FROM 2.5 RRH TO 2.5 ANTENNA SHALL NOT EXCEED 15' NOTIFY SPRINT CM OF ANY DISCREPANCY		

6 AWG POWER	HYBRID JUMPER CABLE MN: HBFO58-13U1M3-5F1 5 FT, 1X6 AWG POWER PAIR, 3X MULTI-MODE FIBER PAIRS, OUTDOOR & LC CONNECTORS, 5/8" CABLE	5 FT
	MN: HBFO58-13U1M3-10F1	10 FT
	MN: HBFO58-13U1M3-15F1	15 FT
SPECIAL INSTALLATION NOTE: JUMPERS FROM 2.5 RRH TO 2.5 ANTENNA SHALL NOT EXCEED 15' NOTIFY SPRINT CM OF ANY DISCREPANCY		

4 AWG POWER	HYBRID JUMPER CABLE MN: HBFO78-21U1M3-5F1 5 FT, 1X4 AWG POWER PAIR, 3X MULTI-MODE FIBER PAIRS, OUTDOOR & LC CONNECTORS, 7/8" CABLE	5 FT
	MN: HBFO78-21U1M3-10F1	10 FT
	MN: HBFO78-21U1M3-15F1	15 FT
SPECIAL INSTALLATION NOTE: JUMPERS FROM 2.5 RRH TO 2.5 ANTENNA SHALL NOT EXCEED 15' NOTIFY SPRINT CM OF ANY DISCREPANCY		


HYBRID CABLE DC CONDUCTOR SIZE GUIDELINE
MANUF: RFS/CELWAVE

CABLE	LENGTH	DC CONDUCTOR	CABLE DIAMETER
FIBER ONLY	VARIES	USE NV HYBRIFLEX	5/8"
HYBRIFLEX	<200'	8 AWG	1-1/4"
HYBRIFLEX	225-300'	6 AWG	1-1/4"
HYBRIFLEX	325-375'	4 AWG	1-1/4"




INSTALLER NOTE:
SPRINT CM TO CONFIRM HYBRID/FIBER
RISER CABLE & HYBRID/FIBER JUMPER
CABLE MODEL NUMBERS BEFORE
PREPARING BOM.

1 HYBRID CABLE CROSS SECTION & DATA
SCALE: NOT TO SCALE




COMMSCOPE - DT465B-2XR
WEIGHT (WITHOUT MOUNTING HARDWARE): 58.0 LBS
SIZE (HxWxD): 71.9x13.8x8.2 IN.
MOUNTING HARDWARE P/N: BSAMNT-1
RATED WIND VELOCITY: 150.0 MPH

2 COMMSCOPE - DT465B-2XR
SCALE: NOT TO SCALE



ALCATEL LUCENT - RRH2x50-800
WEIGHT (WITHOUT BRACKETS): 53.0 LBS
SIZE (WITHOUT BRACKET): 19.70x13.00x10.80 IN.

4 ALCATEL LUCENT - RRH2x50-800
SCALE: NOT TO SCALE



ALCATEL LUCENT - TD-RRH8x20-25
WEIGHT (WITHOUT MOUNTING HARDWARE): 66.0 LBS
SIZE (HxWxD): 25.4x17.5x5.7 IN.

3 ALCATEL LUCENT - TD-RRH8x20-25
SCALE: NOT TO SCALE

5 NOT USED
SCALE: NOT TO SCALE



SPRINT SITE NUMBER:
CT03XC166


BU #: 806382
HRT 082 943274

74 GOODRICH LANE
PORTLAND, CT 06480

EXISTING 160'-0" MONOPOLE

ISSUED FOR:

REV	DATE	DRWN	DESCRIPTION	DES./QA
A	01/03/18	TDG	PRELIMINARY	LMR
0	07/18/18	JHW	CONSTRUCTION	AJF
1	10/03/18	LMR	CONSTRUCTION	JPL



Crown Castle USA Inc. Certificate of
Registration #PEC.0001101


IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

SHEET NUMBER: **C-4** REVISION: **1**

Prepared By Mark Elliott	Revision Date October 25, 2017	Revision Number R7
Approved By RAN Hardware & Antenna Teams	Approval Date Final-Macro Generated	



ALU 211 DT465B-2XR-V2 & APXVSP18-C-A20 wo Filters



Not to Scale

1 PLUMBING DIAGRAM
SCALE: NOT TO SCALE



SPRINT SITE NUMBER:
CT03XC166


BU #: **806382**
HRT **082 943274**

74 GOODRICH LANE
PORTLAND, CT 06480

EXISTING 160'-0" MONOPOLE

ISSUED FOR:


REV	DATE	DRWN	DESCRIPTION	DES./QA
A	01/03/18	TDG	PRELIMINARY	LMR
0	07/18/18	JHW	CONSTRUCTION	AJF
1	10/03/18	LMR	CONSTRUCTION	JPL



Crown Castle USA Inc. Certificate of Registration #PEC.0001101


IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SHEET NUMBER: **C-5** REVISION: **1**




- NOTES:**
1. DOUBLING UP "OR STACKING" OF CONNECTIONS IS NOT PERMITTED.
 2. EXTERIOR ANTIOXIDANT JOINT COMPOUND TO BE USED ON ALL EXTERIOR CONNECTIONS.
 3. GROUND BAR SHALL NOT BE ISOLATED FROM TOWER. MOUNT DIRECTLY TO TOWER STEEL.

1 ANTENNA GROUND BAR DETAIL
SCALE: NOT TO SCALE




- NOTES:**
1. EXTERIOR ANTIOXIDANT JOINT COMPOUND TO BE USED ON ALL EXTERIOR CONNECTIONS.
 2. GROUND BAR SHALL NOT BE ISOLATED FROM TOWER. MOUNT DIRECTLY TO TOWER STEEL (TOWER ONLY).
 3. GROUND BAR SHALL BE ISOLATED FROM BUILDING OR SHELTER.

2 TOWER/SHELTER GROUND BAR DETAIL
SCALE: NOT TO SCALE




- NOTES:**
1. GROUND ROD SHALL BE DRIVEN VERTICALLY, NOT TO EXCEED 45 DEGREES FROM THE VERTICAL.
 2. GROUND WIRE SHALL BE MIN. 30" BELOW GRADE OR 6" BELOW FROST LINE. (WHICH EVER IS GREATER) AS PER N.E.C. ARTICLE 250-50(D).

3 INSPECTION WELL DETAIL
SCALE: NOT TO SCALE




- NOTES:**
1. NUMBER OF GROUNDING BARS MAY VARY DEPENDING ON THE TYPE OF TOWER, ANTENNA LOCATIONS AND CONNECTION ORIENTATION. COAXIAL CABLES EXCEEDING 200 FEET ON THE TOWER SHALL HAVE GROUND KITS AT THE MIDPOINT. PROVIDE AS REQUIRED.
 2. ONLY MECHANICAL CONNECTIONS ARE ALLOWED TO BE MADE TO CROWN CASTLE TOWERS. ALL MECHANICAL CONNECTIONS SHALL BE TREATED WITH AN ANTI-OXIDANT COATING.
 3. ALL TOWER GROUNDING SYSTEMS SHALL COMPLY WITH THE REQUIREMENTS OF THE RECOGNIZED EDITION OF ANSI/TIA 222 AND NFPA 780.

4 TYPICAL ANTENNA CABLE GROUNDING
SCALE: NOT TO SCALE



5 HARDWARE DETAIL FOR EXTERIOR CONNECTIONS
SCALE: NOT TO SCALE



- NOTES:**
1. GROUND ROD SHALL BE DRIVEN VERTICALLY, NOT TO EXCEED 45 DEGREES FROM THE VERTICAL.
 2. GROUND WIRE SHALL BE MIN. 30" BELOW GRADE OR 6" BELOW FROST LINE. (WHICH EVER IS GREATER) AS PER N.E.C. ARTICLE 250-50(D).

6 GROUND ROD DETAIL
SCALE: NOT TO SCALE



SPRINT SITE NUMBER:
CT03XC166


BU #: **806382**
HRT **082 943274**

74 GOODRICH LANE
PORTLAND, CT 06480

EXISTING 160'-0" MONOPOLE


ISSUED FOR:

REV	DATE	DRWN	DESCRIPTION	DES./QA
A	01/03/18	TDG	PRELIMINARY	LMR
0	07/18/18	JHW	CONSTRUCTION	AJF
1	10/03/18	LMR	CONSTRUCTION	JPL



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.


SHEET NUMBER: **G-1** REVISION: **1**



NOTE:

1. ERICO EXOTHERMIC "MOLD TYPES" SHOWN HERE ARE EXAMPLES. CONSULT WITH CONSTRUCTION MANAGER FOR SPECIFIC MOLDS TO BE USED FOR THIS PROJECT.
2. MOLD TYPE ONLY TO BE USED BELOW GRADE WHEN CONNECTING GROUND RING TO GROUND ROD.


1 CADWELD GROUNDING CONNECTIONS
SCALE: NOT TO SCALE



NOTES:

1. DO NOT INSTALL CABLE GROUND KIT AT A BEND AND ALWAYS DIRECT GROUND WIRE DOWN TO GROUND BAR.
2. GROUNDING KIT SHALL BE TYPE AND PART NUMBER AS SUPPLIED OR RECOMMENDED BY CABLE MANUFACTURER.
3. WEATHER PROOFING SHALL BE TWO-PART TAPE KIT. COLD SHRINK SHALL NOT BE USED.


3 CABLE GROUND KIT CONNECTION
SCALE: NOT TO SCALE



NOTES:

1. DO NOT INSTALL CABLE GROUND KIT AT A BEND AND ALWAYS DIRECT GROUND WIRE DOWN TO ANTENNA GROUND BAR.
2. WEATHER PROOFING SHALL BE TWO-PART TAPE KIT. COLD SHRINK SHALL NOT BE USED.


4 GROUND CABLE CONNECTION
SCALE: NOT TO SCALE



NOTES:


1. DOWN LEAD (HOME RUN) CONDUCTORS ARE NOT TO BE INSTALLED ON CROWN CASTLE USA INC. TOWER, PER THE GROUNDING DOWN CONDUCTOR POLICY GAS-STD-10091. NO MODIFICATION OR DRILLING TO TOWER STEEL IS ALLOWED IN ANY FORM OR FASHION. CAD-WELDING ON THE TOWER AND/OR IN THE AIR ARE NOT PERMITTED.
2. OMIT INSULATOR WHEN MOUNTING TO TOWER STEEL OR PLATFORM STEEL. USE INSULATORS WHEN ATTACHING TO BUILDING OR SHELTERS.

6 GROUND BAR DETAIL
SCALE: NOT TO SCALE



7 LUG DETAIL
SCALE: NOT TO SCALE


WIRE SIZE	BURNDY LUG	BOLT SIZE
#6 AWG GREEN INSULATED	YA6C-2TC38	3/8" - 16 NC S 2 BOLT
#2 AWG SOLID TINNED	YA3C-2TC38	3/8" - 16 NC S 2 BOLT
#2 AWG STRANDED	YA2C-2TC38	3/8" - 16 NC S 2 BOLT
#2/0 AWG STRANDED	YA26-2TC38	3/8" - 16 NC S 2 BOLT
#4/0 AWG STRANDED	YA28-2N	1/2" - 16 NC S 2 BOLT




NOTES:

1. ALL GROUNDING LUGS ARE TO BE INSTALLED PER MANUFACTURER'S SPECIFICATIONS. ALL HARDWARE BOLTS, NUTS, LOCK WASHERS SHALL BE STAINLESS STEEL. ALL HARDWARE ARE TO BE AS FOLLOWS: BOLT, FLAT WASHER, GROUND BAR, GROUND LUG, FLAT WASHER AND NUT.

2 MECHANICAL LUG CONNECTION
SCALE: NOT TO SCALE



5 GROUNDWIRE INSTALLATION
SCALE: NOT TO SCALE



8 TRANSITIONING GROUND DETAIL
SCALE: NOT TO SCALE



SPRINT SITE NUMBER:
CT03XC166


BU #: 806382
HRT 082 943274

74 GOODRICH LANE
PORTLAND, CT 06480

EXISTING 160'-0" MONOPOLE

ISSUED FOR:

REV	DATE	DRWN	DESCRIPTION	DES./QA
A	01/03/18	TDG	PRELIMINARY	LMR
0	07/18/18	JHW	CONSTRUCTION	AJF
1	10/03/18	LMR	CONSTRUCTION	JPL



10/31/2018 10:52:32 AM EDT

Crown Castle USA Inc. Certificate of Registration #PEC.0001101

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SHEET NUMBER: **G-2** REVISION: **1**

Certificate Of Completion

Envelope Id: 94ADFE9D1CFB4B84A66C381F4D96D6F8	Status: Completed
Subject: Please DocuSign: CT03XC166_806382_HRT 082 943274_Sprint DO Macro Upgrade FCD REV 1_10.03.2018.pdf	
Source Envelope:	
Document Pages: 10	Signatures: 10
Certificate Pages: 3	Initials: 0
AutoNav: Enabled	Envelope Originator:
Envelopeld Stamping: Enabled	Whitney Flavion
Time Zone: (UTC-05:00) Eastern Time (US & Canada)	2000 Corporate Drive
	Canonsburg, PA 15317
	Whitney.Flavion.Contractor@crowncastle.com
	IP Address: 50.197.38.250

Record Tracking

Status: Original 10/3/2018 10:36:19 AM	Holder: Whitney Flavion Whitney.Flavion.Contractor@crowncastle.com	Location: DocuSign
---	---	--------------------

Signer Events

Justin Linette
justin.linette@crowncastle.com
Crown Castle International Corp.
Security Level: Email, Account Authentication (None)

Signature

DocuSigned by:

1B4005B2547C41D...

Signature Adoption: Pre-selected Style
Using IP Address: 50.197.38.250

Timestamp

Sent: 10/3/2018 10:38:46 AM
Viewed: 10/3/2018 10:51:44 AM
Signed: 10/3/2018 10:52:32 AM

Electronic Record and Signature Disclosure:
Accepted: 9/20/2018 7:12:49 AM
ID: 5006cfc0-7b26-47be-9523-588826283226

In Person Signer Events	Signature	Timestamp
Editor Delivery Events	Status	Timestamp
Agent Delivery Events	Status	Timestamp
Intermediary Delivery Events	Status	Timestamp
Certified Delivery Events	Status	Timestamp
Carbon Copy Events	Status	Timestamp
Notary Events	Signature	Timestamp
Envelope Summary Events	Status	Timestamps
Envelope Sent	Hashed/Encrypted	10/3/2018 10:38:46 AM
Certified Delivered	Security Checked	10/3/2018 10:51:44 AM
Signing Complete	Security Checked	10/3/2018 10:52:32 AM
Completed	Security Checked	10/3/2018 10:52:32 AM
Payment Events	Status	Timestamps
Electronic Record and Signature Disclosure		

Parties agreed to: Justin Linette

ELECTRONIC RECORD AND SIGNATURE DISCLOSURE

In order to provide more efficient and faster service, Crown Castle (“we”, “us” or “company”) is pleased to announce the use of DocuSign, Inc. (“DocuSign”) electronic signing system. The terms for providing such documents for execution and various other documents and records to you electronically through DocuSign are set forth below. Please read the information below carefully and if you can satisfactorily access this information electronically and agree to these terms, please confirm your agreement by clicking the “I agree” button at the bottom of this document.

Getting paper copies

At any time, you may request from us a paper copy of any document for execution or other document or record provided or made available electronically to you by us. You will be able to download and print documents we send to you through the DocuSign system during and immediately after each signing session and, if you elect to create a DocuSign signer account, you may access them for a limited period of time thereafter. To request paper copies of documents previously provided by us to you electronically, send an e-mail to esignature@CrownCastle.com, requesting the subject paper copies and stating your e-mail address, name, US Postal address and telephone number.

Withdrawing your consent to receive and/or execute documents electronically

If you elect to receive documents for execution and various other documents and records from us electronically, you may at any time change your mind and tell us that thereafter you want to receive such documents only in paper format. To withdraw your consent to electronic delivery and execution of documents, use the DocuSign 'Withdraw Consent' form on the signing page of a DocuSign envelope, instead of signing it. Thereafter, you will no longer be able to use the DocuSign system to electronically receive and execute documents or other records from us. You may also send an e-mail to esignature@CrownCastle.com stating that you are withdrawing your consent to electronic delivery and execution of documents through the DocuSign system and stating your e-mail address, name, US Postal Address, and telephone number.

Consequences of withdrawing consent to receive and/or execute documents electronically

If you elect to receive documents for execution and various other documents and other records only in paper format, it will slow the speed at which we can complete the subject transactions because of the increased delivery time.

Documents for execution, and other documents and records may be sent to you electronically

Unless you tell us otherwise in accordance with the procedures described herein, we may provide documents for execution, and other documents and records electronically to you through the DocuSign system during the course of our relationship with you. To reduce the chance of you inadvertently not receiving any document for execution or other document or record, we prefer to provide all documents for execution, and other documents and records by the same method and to the same address that you have given us. If you do not agree with this process, please let us know as described below.

How to contact Crown Castle

You may contact us to let us know of any changes related to contacting you electronically, to request paper copies of documents for execution and other documents and records from us, and to withdraw your prior consent to receive documents for execution and other documents and records electronically as follows:

To contact us by phone call: 724-416-2000

To contact us by email, send messages to: esignature@CrownCastle.com

To contact us by paper mail, send correspondence to

Crown Castle
2000 Corporate Drive
Canonsburg, PA 15317

To advise Crown Castle and DocuSign of your new e-mail address

To let us know of a change to the e-mail address where we should send documents for execution and other documents and records to you, you must send an email message to esignature@CrownCastle.com and state your previous e-mail address and your new e-mail address.

In addition, you must notify DocuSign, Inc. to arrange for your new email address to be reflected in your DocuSign account by following the process for changing e-mail in the DocuSign system.

Required hardware and software

Browsers:	Internet Explorer® 11 (Windows only); Windows Edge Current Version; Mozilla Firefox Current Version; Safari™ (Mac OS only) 6.2 or above; Google Chrome Current Version; Note : Pre-release (e.g., beta) versions of operating systems and browsers are not supported.
Mobile Signing:	Apple iOS 7.0 or above; Android 4.0 or above
PDF Reader:	Acrobat® Reader or similar software may be required to view and print PDF files
Screen Resolution:	1024 x 768

Enabled Security Settings:	Allow per session cookies
----------------------------------	---------------------------

These minimum requirements are subject to change. If these requirements change, you will be asked to re-accept the disclosure. Pre-release (e.g. beta) versions of operating systems and browsers are not supported.

Acknowledging your access and consent to receive documents electronically

Please confirm that you were able to access this disclosure electronically (which is similar to the manner in which we will deliver documents for execution and other documents and records) and that you were able to print this disclosure on paper or electronically save it for your future reference and access or that you were able to e-mail this disclosure to an address where you will be able to print it on paper or save it for your future reference and access. Further, if you consent to receiving documents for execution and other documents and records in electronic format on the terms described above, please let us know by clicking the "I agree" button below.

By checking the 'I agree' box, I confirm that:

- You can access and read this Electronic Record and Signature Disclosure; and
- As a recipient, you can read, electronically sign and act upon this message, and you agree not to forward it or any other DocuSign e-mail communications. In the event another party needs to be added to the DocuSign communication, you must make a request to the e-mail originator.

DOCKET NO. 58

AN APPLICATION OF HARTFORD CELLULAR
COMPANY FOR A CERTIFICATE OF
ENVIRONMENTAL COMPATIBILITY AND PUBLIC
NEED FOR THE CONSTRUCTION, MAINTENANCE,
AND OPERATION OF FACILITIES TO PROVIDE
CELLULAR SERVICE IN HARTFORD, TOLLAND AND
MIDDLESEX COUNTIES.

CONNECTICUT SITING
COUNCIL

July 11, 1986.

D E C I S I O N A N D O R D E R

Pursuant to the foregoing opinion, the Connecticut Siting Council (Council) hereby directs that a Certificate of Environmental Compatibility and Public Need as provided by Section 16-50k of the General Statutes of Connecticut (CGS) be issued to the Hartford Cellular Company for the construction, maintenance, and operation of cellular mobile phone telecommunication towers and associated equipment in the towns of Glastonbury, Haddam, Hartford, Portland, Rocky Hill, Somers, Vernon, Windsor, and Willington subject to the conditions below.

- 1) The proposed Bloomfield and Middlefield sites are rejected without prejudice. ^{TALCOTT} 9A ^{BESSEK} 7
- 2) The antennas on the Glastonbury tower shall be mounted no higher than the 180' level of this existing tower.
- 3) The Portland and Rocky Hill towers shall be monopoles.
- 4) The towers shall be no taller than necessary to provide the proposed service, and in no event shall exceed total heights, including antennas, of
 - a) 193' at the Haddam site;
 - b) 173' at the Portland site;



July 3rd, 2018

Charles McGuirt
Crown Castle
3530 Toringdon Way Suite 300
Charlotte, NC 28277
(704) 405-6607

B+T Group
1717 S. Boulder, Suite 300
Tulsa, OK 74119
(918) 587-4630
btwo@btgrp.com

Subject: **Structural Analysis Report**

Carrier Designation: **Sprint PCS Co-Locate**
Carrier Site Number: CT03XC166
Carrier Site Name: CT03XC166

Crown Castle Designation: **Crown Castle BU Number:** 806382
Crown Castle Site Name: HRT 082 943274
Crown Castle JDE Job Number: 447440
Crown Castle Work Order Number: 1595859
Crown Castle Order Number: 396861 Rev. 4

Engineering Firm Designation: **B+T Group Project Number:** 81363.016.01

Site Data: **74 Goodrich Lane, Portland, Middlesex County, CT**
Latitude 41° 36' 29.9", Longitude -72° 35' 29.56"
160 Foot - Monopole Tower

Dear Charles McGuirt,

B+T Group is pleased to submit this “**Structural Analysis Report**” to determine the structural integrity of the above-mentioned tower. This analysis has been performed in accordance with the Crown Castle Structural ‘Statement of Work’ and the terms of Crown Castle Purchase Order Number 1211957, in accordance with order 396861, revision 4.

The purpose of the analysis is to determine acceptability of the tower stress level. Based on our analysis we have determined the tower stress level for the structure and foundation, under the following load case, to be:

LC5: Existing + Proposed Equipment **Sufficient Capacity**
Note: See Table 1 and Table 2 for the proposed and existing loading, respectively.

This analysis has been performed in accordance with the 2016 Connecticut State Building Code based upon an ultimate 3-second gust wind speed of 130 mph converted to a nominal 3-second gust wind speed of 101 mph per Section 1609.3 and Appendix N as required for use in the TIA-222-G Standard per Exception #5 of Section 1609.1.1. Exposure Category B and Risk Category II were used in this analysis.

All equipment proposed in this report shall be installed in accordance with the attached drawings for the determined available structural capacity to be effective.

We at B+T Group appreciate the opportunity of providing our continuing professional services to you and Crown Castle. If you have any questions or need further assistance on this or any other projects, please give us a call.

Structural analysis prepared by: Tharun Cheriyan, E.I.T.

Respectfully submitted by: B+T Engineering, Inc.
COA: PEC.0001564 Expires: 02/10/2019

Scott S. Vance, P.E.

tnxTower Report - version 7.0.5.1




TABLE OF CONTENTS

1) INTRODUCTION

2) ANALYSIS CRITERIA

Table 1 - Proposed Antenna and Cable Information

Table 2 - Existing Antenna and Cable Information

Table 3 - Design Antenna and Cable Information

3) ANALYSIS PROCEDURE

Table 4 - Documents Provided

3.1) Analysis Method

3.2) Assumptions

4) ANALYSIS RESULTS

Table 5 - Section Capacity (Summary)

Table 6 – Tower Components vs. Capacity

4.1) Recommendations

5) APPENDIX A

tnxTower Output

6) APPENDIX B

Base Level Drawing

7) APPENDIX C

Additional Calculations

1) INTRODUCTION

This tower is a 160 ft. Monopole designed by Valmont in January of 1998. The tower was originally designed for a wind speed of 85 mph per TIA/EIA-222-F. This tower has been modified by B+T Group in May of 2013.

2) ANALYSIS CRITERIA

The structural analysis was performed for this tower in accordance with the requirements of TIA-222-G Structural Standards for Steel Antenna Towers and Antenna Supporting Structures using a 3-second gust wind speed of 101 mph with no ice, 50 mph with 0.75-inch ice thickness and 60 mph under service loads, exposure category B with topographic category 1 and crest height of 0 feet.

Table 1 - Proposed Antenna and Cable Information

Mounting Level (ft)	Center Line Elevation (ft)	Number of Antennas	Antenna Manufacturer	Antenna Model	Number of Feed Lines	Feed Line Size (in)	Note
150.0	152.0	3	Alcatel Lucent	1900MHZ RRH	4	1-1/4	--
		3	Alcatel Lucent	800MHZ RRH			
		3	Alcatel Lucent	RRH2X50-800			
		3	Alcatel Lucent	TD-RRH8X20-25			
		3	Commscope	DT465B-2XR			
		3	Rfs Celwave	APXVSP18-C-A20			
	150.0	3	--	L 2-1/2x2-1/2x1/4			
		3	--	2.88" O.D Steel Pipe Mast			

Table 2 - Existing Antenna and Cable Information

Mounting Level (ft)	Center Line Elevation (ft)	Number of Antennas	Antenna Manufacturer	Antenna Model	Number of Feed Lines	Feed Line Size (in)	Note
158.0	160.0	3	Alcatel Lucent	B13 RRH 4X30	12	1-5/8	1
		3	Alcatel Lucent	B25 RRH4X30			
		3	Alcatel Lucent	B4 RRH2x60-4R			
		6	Andrew	SBNHH-1D65B			
		2	Decibel	DB846F65ZAXY			
		4	Decibel	DB846H80E-6X			
	1	Raycap	RRFDC-3315-PF-48				
158.0	1	--	Platform Mount [LP 713-1]				
150.0	152.0	6	Decibel	DB980H90E-M	6	1-5/8	3
	150.0	1	--	Platform Mount [LP 713-1]	--	--	1
142.0	144.0	2	Radiowaves	HP3-11	2	1/2	1
	142.0	1	--	Side Arm Mount [SO 101-3]			
136.0	137.0	3	Commscope	SBNH-1D65C-SR	7	1-5/8	1
		3	Commscope	TMAT1921B78-21A			
		3	Ericsson	ERICSSON AIR 21 B4A B2P			
		3	Ericsson	RRUS 11 B12			
		3	Ericsson	RRUS 11 B2			
	136.0	1	--	T-Arm Mount [TA 602-3]			

Mounting Level (ft)	Center Line Elevation (ft)	Number of Antennas	Antenna Manufacturer	Antenna Model	Number of Feed Lines	Feed Line Size (in)	Note
118.0	120.0	3	Ericsson	RRUS 11 B12	12 2 1	1-1/4 3/4 3/8	1
		3	Ericsson	RRUS 12 B2			
		3	Kmw Comm.	AM-X-CD-16-65-00T-RET			
		6	Powerwave Technologies	7770.00			
		3	Powerwave Tech.	LGP21401			
		3	Powerwave Tech.	LGP21901			
	1	Raycap	DC6-48-60-18-8F				
	118.0	1	--	Platform Mount [LP 303-1]			
61.0	61.0	1	Lucent	KS24019-L112A	1	1/2	1
		1	--	Side Arm Mount [SO 701-1]			
50.0	50.0	2	--	Side Arm Mount [SO 701-1]	--	--	2

Notes:

- 1) Existing Equipment
- 2) Empty Mount; Considered in This Analysis
- 3) Equipment to Be Removed; Not Considered in This Analysis

Table 3 - Design Antenna and Cable Information

Mounting Level (ft)	Center Line Elevation (ft)	Number of Antennas	Antenna Manufacturer	Antenna Model	Number of Feed Lines	Feed Line Size (in)
157	157	12	Swedcom	ALP 9212-N	--	--
		1	Valmont	Cellular Platform		
148	148	12	Swedcom	ALP 9212-N	--	--
		1	Valmont	Cellular Platform		
138	138	12	Swedcom	ALP 9212-N	--	--
		1	Valmont	Cellular Platform		
128	128	12	Swedcom	ALP 9212-N	--	--
		1	Valmont	Cellular Platform		
60	60	2	Generic	GPS	--	--
		2	Generic	Short Straight Arm		
50	50	2	Generic	GPS	--	--
		2	Generic	Short Straight Arm		

3) ANALYSIS PROCEDURE

Table 4 - Documents Provided

Document	Remarks	Reference	Source
Online Order	Sprint Co-locate, Rev# 4	396861	CCI Sites
Tower Manufacturer Drawing	Valmont, Order No: 16750-98	255193	CCI Sites
Mount Analysis Report	Hudson Design Group LLC, Project No. 48681917	Date: 06/20/2018	--
Tower Modification Drawing	B+T Group, Date: 05/29/2013	3865159	CCI Sites
Post Modification Inspection	TEP, Date: 09/17/2013	3996803	CCI Sites
Foundation Drawing	Valmont, Order No: 16750-98	301226	CCI Sites
Geotech Report	TGG, Project No. 067058	1041653	CCI Sites
Antenna Configuration	Crown CAD Package	Date: 06/26/2018	CCI Sites

3.1) Analysis Method

tnxTower (version 7.0.5.1), a commercially available analysis software package, was used to create a three-dimensional model of the tower and calculate member stresses for various loading cases. Selected output from the analysis is included in Appendix A.

3.2) Assumptions

- 1) Tower and structures were built in accordance with the manufacturer's specifications.
- 2) The tower and structures have been maintained in accordance with the manufacturer's specification.
- 3) The configuration of antennas, transmission cables, mounts and other appurtenances are as specified in Tables 1 and 2 and the referenced drawings.
- 4) Mount areas and weights are assumed based on photographs provided.

This analysis may be affected if any assumptions are not valid or have been made in error. B+T Group should be notified to determine the effect on the structural integrity of the tower.

4) ANALYSIS RESULTS

Table 5 - Section Capacity (Summary)

Section No.	Elevation (ft)	Component Type	Size	Critical Element	P (K)	SF*P_allow (K)	% Capacity	Pass / Fail
L1	160 - 123.667	Pole	TP29.05x18.87x0.188	1	-10.499	965.169	84.5	Pass
L2	123.667 - 76.25	Pole	TP41.95x27.461x0.313	2	-22.567	2534.090	81.5	Pass
L3	76.25 - 37	Pole	TP52.32x39.715x0.344	3	-34.824	3229.470	89.3	Pass
L4	37 - 0	Pole	TP62x49.672x0.406	4	-52.948	4570.550	80.9	Pass
							Summary	
						Pole (L3)	89.3	Pass
						Rating =	89.3	Pass

Table 6 - Tower Component Stresses vs. Capacity – LC5

Notes	Component	Elevation	% Capacity	Pass / Fail
1	Anchor Rods	Base	78.0	Pass
1	Base Plate	Base	42.2	Pass
1	Base Foundation	Structure	50.4	Pass
		Soil	69.1	Pass
Structure Rating (max from all components) =				89.3%

Notes:

- 1) See additional documentation in "Appendix C – Additional Calculations" for calculations supporting the % capacity consumed.

4.1) Recommendations

The tower and its foundation have sufficient capacity to carry the proposed load configuration. No modifications are required at this time.



RADIO FREQUENCY EMISSIONS ANALYSIS REPORT EVALUATION OF HUMAN EXPOSURE POTENTIAL TO NON-IONIZING EMISSIONS

SPRINT Existing Facility

Site ID: CT03XC166

Crown Castle 806382 Portland
74 Goodrich Lane
Portland, CT 06480

October 17, 2018

EBI Project Number: 6218006581

Site Compliance Summary	
Compliance Status:	COMPLIANT
Site total MPE% of FCC general population allowable limit:	11.90 %



October 17, 2018

SPRINT

Attn: RF Engineering Manager
1 International Boulevard, Suite 800
Mahwah, NJ 07495

Emissions Analysis for Site: **CT03XC166 – Crown Castle 806382 Portland**

EBI Consulting was directed to analyze the proposed SPRINT facility located at **74 Goodrich Lane, Portland, CT**, for the purpose of determining whether the emissions from the Proposed SPRINT Antenna Installation located on this property are within specified federal limits.

All information used in this report was analyzed as a percentage of current Maximum Permissible Exposure (% MPE) as listed in the FCC OET Bulletin 65 Edition 97-01 and ANSI/IEEE Std C95.1. The FCC regulates Maximum Permissible Exposure in units of microwatts per square centimeter ($\mu\text{W}/\text{cm}^2$). The number of $\mu\text{W}/\text{cm}^2$ calculated at each sample point is called the power density. The exposure limit for power density varies depending upon the frequencies being utilized. Wireless Carriers and Paging Services use different frequency bands each with different exposure limits, therefore it is necessary to report results and limits in terms of percent MPE rather than power density.

All results were compared to the FCC (Federal Communications Commission) radio frequency exposure rules, 47 CFR 1.1307(b)(1) – (b)(3), to determine compliance with the Maximum Permissible Exposure (MPE) limits for General Population/Uncontrolled environments as defined below.

General population/uncontrolled exposure limits apply to situations in which the general population may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Therefore, members of the general population would always be considered under this category when exposure is not employment related, for example, in the case of a telecommunications tower that exposes persons in a nearby residential area.

General population exposure to radio frequencies is regulated and enforced in units of microwatts per square centimeter ($\mu\text{W}/\text{cm}^2$). The general population exposure limits for the 850 MHz Band is approximately $567 \mu\text{W}/\text{cm}^2$. The general population exposure limit for the 1900 MHz (PCS) and 2500 MHz (BRS) bands is $1000 \mu\text{W}/\text{cm}^2$. Because each carrier will be using different frequency bands, and each frequency band has different exposure limits, it is necessary to report percent of MPE rather than power density.



Occupational/controlled exposure limits apply to situations in which persons are exposed as a consequence of their employment and in which those persons who are exposed have been made fully aware of the potential for exposure and can exercise control over their exposure. Occupational/controlled exposure limits also apply where exposure is of a transient nature as a result of incidental passage through a location where exposure levels may be above general population/uncontrolled limits (see below), as long as the exposed person has been made fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Additional details can be found in FCC OET 65.

CALCULATIONS

Calculations were done for the proposed SPRINT Wireless antenna facility located at **74 Goodrich Lane, Portland, CT**, using the equipment information listed below. All calculations were performed per the specifications under FCC OET 65. Since SPRINT is proposing highly focused directional panel antennas, which project most of the emitted energy out toward the horizon, all calculations were performed assuming a lobe representing the maximum gain of the antenna per the antenna manufactures supplied specifications, minus 10 dB for directional panel antennas, was focused at the base of the tower. For this report the sample point is the top of a 6-foot person standing at the base of the tower.

For all calculations, all equipment was calculated using the following assumptions:

- 1) 1 CDMA channels (850 MHz) were considered for each sector of the proposed installation. These Channels have a transmit power of 20 Watts per Channel.
- 2) 2 LTE channels (850 MHz) were considered for each sector of the proposed installation. These Channels have a transmit power of 50 Watts per Channel.
- 3) 5 CDMA channels (1900 MHz (PCS)) were considered for each sector of the proposed installation. These Channels have a transmit power of 16 Watts per Channel.
- 4) 2 LTE channels (1900 MHz (PCS)) were considered for each sector of the proposed installation. These Channels have a transmit power of 40 Watts per Channel.
- 5) 8 LTE channels (2500 MHz (BRS)) were considered for each sector of the proposed installation. These Channels have a transmit power of 20 Watts per Channel.



- 6) All radios at the proposed installation were considered to be running at full power and were uncombined in their RF transmissions paths per carrier prescribed configuration. Per FCC OET Bulletin No. 65 - Edition 97-01 recommendations to achieve the maximum anticipated value at each sample point, all power levels emitting from the proposed antenna installation are increased by a factor of 2.56 to account for possible in-phase reflections from the surrounding environment. This is rarely the case, and if so, is never continuous.
- 7) For the following calculations, the sample point was the top of a 6-foot person standing at the base of the tower. The maximum gain of the antenna per the antenna manufactures supplied specifications, minus 10 dB for directional panel antennas, was used in this direction. This value is a very conservative estimate as gain reductions for these particular antennas are typically much higher in this direction.
- 8) The antennas used in this modeling are the **RFS APXVSP18-C-A20 and the Commscope DT465B-2XR** for transmission in the 850 MHz, 1900 MHz (PCS) and 2500 MHz (BRS) frequency bands. This is based on feedback from the carrier with regards to anticipated antenna selection. Maximum gain values for all antennas are listed in the Inventory and Power Data table below. The maximum gain of the antenna per the antenna manufactures supplied specifications, minus 10 dB for directional panel antennas, was used for all calculations. This value is a very conservative estimate as gain reductions for these particular antennas are typically much higher in this direction.
- 9) The antenna mounting height centerlines of the proposed panel antennas are **152 feet** above ground level (AGL) for **Sector A**, **152 feet** above ground level (AGL) for **Sector B** and **152 feet** above ground level (AGL) for Sector C.
- 10) Emissions values for additional carriers were taken from the Connecticut Siting Council active database. Values in this database are provided by the individual carriers themselves.

All calculations were done with respect to uncontrolled / general population threshold limits.



SPRINT Site Inventory and Power Data by Antenna

Sector:	A	Sector:	B	Sector:	C
Antenna #:	1	Antenna #:	1	Antenna #:	1
Make / Model:	RFS APXVSP18-C-A20	Make / Model:	RFS APXVSP18-C-A20	Make / Model:	RFS APXVSP18-C-A20
Gain:	13.4 / 15.9 dBd	Gain:	13.4 / 15.9 dBd	Gain:	13.4 / 15.9 dBd
Height (AGL):	152 feet	Height (AGL):	152 feet	Height (AGL):	152 feet
Frequency Bands	850 MHz / 1900 MHz (PCS)	Frequency Bands	850 MHz / 1900 MHz (PCS)	Frequency Bands	850 MHz / 1900 MHz (PCS)
Channel Count	10	Channel Count	10	Channel Count	10
Total TX Power(W):	280 Watts	Total TX Power(W):	280 Watts	Total TX Power(W):	280 Watts
ERP (W):	8,850.04	ERP (W):	8,850.04	ERP (W):	8,850.04
Antenna A1 MPE%	1.83 %	Antenna B1 MPE%	1.83 %	Antenna C1 MPE%	1.83 %
Antenna #:	2	Antenna #:	2	Antenna #:	2
Make / Model:	Commscope DT465B-2XR	Make / Model:	Commscope DT465B-2XR	Make / Model:	Commscope DT465B-2XR
Gain:	15.05 dBd	Gain:	15.05 dBd	Gain:	15.05 dBd
Height (AGL):	152 feet	Height (AGL):	152 feet	Height (AGL):	152 feet
Frequency Bands	2500 MHz (BRS)	Frequency Bands	2500 MHz (BRS)	Frequency Bands	2500 MHz (BRS)
Channel Count	8	Channel Count	8	Channel Count	8
Total TX Power(W):	160 Watts	Total TX Power(W):	160 Watts	Total TX Power(W):	160 Watts
ERP (W):	5,118.23	ERP (W):	5,118.23	ERP (W):	5,118.23
Antenna A2 MPE%	0.86 %	Antenna B2 MPE%	0.86 %	Antenna C2 MPE%	0.86 %

Site Composite MPE%	
Carrier	MPE%
SPRINT – Max per sector	2.69 %
AT&T	4.19 %
Verizon Wireless	1.94 %
Clearwire	0.10 %
T-Mobile	2.98 %
Site Total MPE %:	11.90 %

SPRINT Sector A Total:	2.69 %
SPRINT Sector B Total:	2.69 %
SPRINT Sector C Total:	2.69 %
Site Total:	11.90 %

SPRINT _ Frequency Band / Technology (Per Sector)	# Channels	Watts ERP (Per Channel)	Height (feet)	Total Power Density ($\mu\text{W}/\text{cm}^2$)	Frequency (MHz)	Allowable MPE ($\mu\text{W}/\text{cm}^2$)	Calculated % MPE
Sprint 850 MHz CDMA	1	437.55	152	0.74	850 MHz	567	0.14%
Sprint 850 MHz LTE	2	1,093.88	152	3.69	850 MHz	567	0.65%
Sprint 1900 MHz (PCS) CDMA	5	622.47	152	5.25	1900 MHz (PCS)	1000	0.52%
Sprint 1900 MHz (PCS) LTE	2	1,556.18	152	5.25	1900 MHz (PCS)	1000	0.52%
Sprint 2500 MHz (BRS) LTE	8	639.78	152	8.63	2500 MHz (BRS)	1000	0.86%
						Total:	2.69%



Summary

All calculations performed for this analysis yielded results that were **within** the allowable limits for general population exposure to RF Emissions.

The anticipated maximum composite contributions from the SPRINT facility as well as the site composite emissions value with regards to compliance with FCC's allowable limits for general population exposure to RF Emissions are shown here:

SPRINT Sector	Power Density Value (%)
Sector A:	2.69 %
Sector B:	2.69 %
Sector C:	2.69 %
SPRINT Maximum MPE % (per sector):	2.69 %
Site Total:	11.90 %
Site Compliance Status:	COMPLIANT

The anticipated composite MPE value for this site assuming all carriers present is **11.90 %** of the allowable FCC established general population limit sampled at the ground level. This is based upon values listed in the Connecticut Siting Council database for existing carrier emissions.

FCC guidelines state that if a site is found to be out of compliance (over allowable thresholds), that carriers over a 5% contribution to the composite value will require measures to bring the site into compliance. For this facility, the composite values calculated were well within the allowable 100% threshold standard per the federal government.

Date: May 10, 2018
June 20, 2018 (Rev.1)



Charles McGuirt
Crown Castle
2000 Corporate Drive
Canonsburg, PA 15317
(724) 416-2000

Hudson Design Group LLC
45 Beechwood Drive
N. Andover, MA 01845
(978) 557-5553

Subject: Mount Structural Analysis

Carrier Designation: Sprint Equipment Change-Out
Carrier Site Number: CT03XC166
Carrier Site Name: CT03XC166

Crown Castle Designation: Crown Castle BU Number: 806382
Crown Castle Site Name: HRT 082 943274
Crown Castle JDE Number: 447440
Crown Castle PO Number: 1206297
Crown Castle Application Number: 396861 Rev. 3

Engineering Firm Designation: Crown Castle Report Designation: 3876013

Site Data: 74 Goodrich Lane, Portland, CT, 06480
Latitude: 41° 36' 29.90" Longitude: -72° 35' 29.56"

Structure Information: Tower Height & Type: 160 ft Monopole
Mount Elevation: 152 ft
Mount Width & Type: 12 ft Platform

Dear Charles McGuirt,

Hudson Design Group LLC (HDG) is pleased to submit this "Mount Structural Analysis Report" to determine the structural integrity of Sprint's antenna mounting system with the proposed appurtenance and equipment addition on the abovementioned supporting tower structure. Analysis of the existing supporting tower structure is to be completed by others and therefore is not part of this analysis. Analysis of the antenna mounting system as a tie-off point for fall protection or rigging is not part of this document.

Based upon our analysis, we have determined the adequacy of the antenna mounting system that will support the existing and proposed loading to be:

Platform Mount (Single)

Conditional

This analysis has been performed in accordance with the 2012 International Building Code and the TIA-222-G based on a basic wind speed of 120 mph as required for use in the TIA-222-G Standard Annex B. Exposure Category B with a maximum topographic factor, K_{zt} , of 1.0 and Risk Category II were used in this analysis.

We at HDG appreciate the opportunity of providing our continuing professional services to you and Crown Castle. If you have any questions or need further assistance on this or any other projects, please give us a call.

Mount structural analysis prepared by: HDG
Respectfully Submitted by:

Michael Cabral
Structural Dept. Head



Daniel P. Hamm, P.E.
Principal

TABLE OF CONTENTS

1) INTRODUCTION

2) ANALYSIS CRITERIA

Table 1 - Proposed Equipment Loading Information

Table 2 - Existing and Reserved Equipment Loading Information

3) ANALYSIS PROCEDURE

Table 3 - Documents Provided

3.1) Analysis Method

3.2) Assumptions

4) ANALYSIS RESULTS

Table 4 - Mount Component Stresses vs. Capacity

4.1) Recommendations

5) APPENDIX A

Wire Frame and Rendered Models

6) APPENDIX B

RAM Elements Input Calculations

7) APPENDIX C

RAM Elements Analysis Output

8) APPENDIX D

Additional Calculations

1) INTRODUCTION

This mount is a 12' low profile platform. No original structural design documents or fabrication drawings were available for the existing mounts. A mount mapping was not performed at this site. HDG performed a visual assessment using field photographs and mount mapping data from similar mounts to perform this analysis. The mount is installed at an elevation of 152 ft on the 160 ft Monopole.

2) ANALYSIS CRITERIA

The mount structural analysis was conducted in accordance with the requirements of TIA-222-G, Structural Standards for Steel Antenna Towers and Antenna Supporting Structures using a basic wind speed of 120 mph with no ice, 50 mph with a 1.75 inch escalated ice thickness, Exposure Category B and Topographic category 1 with a crest height of 0 ft. In addition, the mounts have been analyzed for various live loading conditions consisting of a 250 pound man live load applied individually at the midpoint and cantilevered ends of horizontal members as well as a 500 pound man live load applied individually at mount pipe locations using a 3-second gust wind speed of 30 mph.

Table 1 - Proposed Equipment Loading Information

Mount Centerline (ft)	Antenna Centerline (ft)	Number of Antennas	Antenna Manufacturer	Antenna Model	Proposed Mount Type	Note
152	152	3	CommScope	DT465B-2XR	-	1,2
	152	3	RFS/Celwave	APXVSPP18-C-A20	-	1,2
	152	3	Alcatel Lucent	TD-RRH 8x20-25	-	1,2
	152	6	Alcatel Lucent	800MHz 2x50W RRH	-	1,2
	152	3	Alcatel Lucent	PCS 1900MHZ 4X45W-65MHZ	-	1,2

Notes:

- 1) Proposed Equipment
- 2) Existing Mount to Remain

Table 2 - Existing and Reserved Equipment Loading Information

Mount Centerline (ft)	Antenna Centerline (ft)	Number of Antennas	Antenna Manufacturer	Antenna Model	Existing Mount Type	Note
152	-	-	-	-	12' Platform	1

Notes:

- 1) Existing Equipment

3) ANALYSIS PROCEDURE

Table 3 - Documents Provided

Document	Remarks	Reference	Source
RFDS	SPRINT	-	ON FILE

3.1) Analysis Method

RAM Elements (Version 14.0.1), a commercially available analysis software package, was used to create a three-dimensional model of the antenna mounting system and calculate member stresses for various loading cases.

3.2) Assumptions

- 1) The antenna mounting system was properly fabricated, installed and maintained in good condition in accordance with its original design and manufacturer's specifications.
- 2) The configuration of antennas, mounts, and other appurtenances are as specified in Table 1 and 2 and the referenced drawings.
- 3) All member connections are assumed to have been designed to meet or exceed the load carrying capacity of the connected member unless otherwise specified in this report.
- 4) Steel grades have been assumed as follows, unless noted otherwise:

Channel, Solid Round, Angle, Plate	ASTM A36 (GR 36)
HSS (Square, Rectangular)	ASTM A500 (GR B)
Pipe	ASTM A53 (GR 53)
Connection Bolts	ASTM A325

This analysis may be affected if any assumptions are not valid or have been made in error. Crown Castle should be notified to determine the effect on the structural integrity of the antenna mounting system.

4) ANALYSIS RESULTS

Table 4(a) - Mount Component Stresses vs. Capacity (Platform Mount, Alpha Sector)

Notes	Component	Member No.	Centerline (ft)	% Capacity	Pass / Fail
1	Face Horizontal	210	152	50	Pass
1	Standoff Members	308	152	85	Pass
2	Mount-to-Tower Connection	-	152	67	Pass

Table 4(b) - Mount Component Stresses vs. Capacity (Platform Mount, Beta Sector)

Notes	Component	Beam No.	Centerline (ft)	% Capacity	Pass / Fail
1	Face Horizontal	210	152	50	Pass
1	Standoff Members	308	152	85	Pass
2	Mount-to-Tower Connection	-	152	67	Pass

Table 4(c) - Mount Component Stresses vs. Capacity (Platform Mount, Gamma Sector)

Notes	Component	Beam No.	Centerline (ft)	% Capacity	Pass / Fail
1	Face Horizontal	210	152	50	Pass
1	Standoff Members	308	152	85	Pass
2	Mount-to-Tower Connection	-	152	67	Pass

Structure Rating (max from all components) =	85%
---	------------

Notes:

- 1) See additional documentation in "Appendix C – Analysis Output" for calculations supporting the % Capacity consumed.
- 2) See additional documentation in "Appendix D – Additional Calculations" for calculations supporting the % capacity consumed.

4.1) Recommendations

The Mount has sufficient capacity to support the proposed loading with the following modifications:

- Reinforce existing L2-1/2x2-1/2x1/4 steel angle handrail with new L2-1/2x2-1/2x1/4 steel angle secured to the existing mount (typ. of 1 per sector, total of 3).
- Install new 2-1/2" x-strong (2.88" O.D.) steel pipe masts secured to the existing mount (typ. of 1 per sector, total of 3).



October 30,2018

Dear Customer:

The following is the proof-of-delivery for tracking number **773569318387**.

Delivery Information:

Status:	Delivered	Delivered to:	Receptionist/Front Desk
Signed for by:	P.LEE	Delivery location:	33 E MAIN ST PORTLAND, CT 06480
Service type:	FedEx Standard Overnight	Delivery date:	Oct 29, 2018 11:25
Special Handling:	Deliver Weekday		



Shipping Information:

Tracking number:	773569318387	Ship date:	Oct 26, 2018
		Weight:	1.0 lbs/0.5 kg

Recipient:
Lincoln White
Town of Portland
33 East Main St.
PORTLAND, CT 06480 US

Shipper:
Kristian McKay
3530 Toringdon Way
STE 300
CHARLOTTE, NC 28277 US

Reference 1766.6680

Thank you for choosing FedEx.



October 30, 2018

Dear Customer:

The following is the proof-of-delivery for tracking number **773569310011**.

Delivery Information:

Status:	Delivered	Delivered to:	Receptionist/Front Desk
Signed for by:	P.LEE	Delivery location:	33 E MAIN ST PORTLAND, CT 06480
Service type:	FedEx Standard Overnight	Delivery date:	Oct 29, 2018 11:25
Special Handling:	Deliver Weekday		



Shipping Information:

Tracking number:	773569310011	Ship date:	Oct 26, 2018
		Weight:	1.0 lbs/0.5 kg

Recipient:
Susan Bransfield
Town of Portland
33 East Main St.
PORTLAND, CT 06480 US

Shipper:
Kristian McKay
3530 Toringdon Way
STE 300
CHARLOTTE, NC 28277 US

Reference 1766.6680

Thank you for choosing FedEx.



October 30, 2018

Dear Customer:

The following is the proof-of-delivery for tracking number **773569336765**.

Delivery Information:

Status:	Delivered	Delivered to:	Residence
Signed for by:	Signature not required	Delivery location:	3060 N ATLANTIC AVE 301 COCOA BEACH, FL 32931
Service type:	FedEx Standard Overnight	Delivery date:	Oct 29, 2018 11:06
Special Handling:	Deliver Weekday Residential Delivery		

NO SIGNATURE REQUIRED

Proof-of-delivery details appear below; however, no signature is available for this FedEx Express shipment because a signature was not required.

Shipping Information:

Tracking number:	773569336765	Ship date:	Oct 26, 2018
		Weight:	1.0 lbs/0.5 kg

Recipient:

Joan J Hale
3060 N Atlantic Ave. Apt. 301
COCOA BEACH, FL 32931 US

Shipper:

Kristian McKay
3530 Toringdon Way
STE 300
CHARLOTTE, NC 28277 US

Reference

1766.6680

Thank you for choosing FedEx.