



January 8, 2021

Melanie A. Bachman Executive Director Connecticut Siting Council 10 Franklin Square New Britain, CT 06051

Re: Notice of Exempt Modifications – AT&T Site CT2546 AT&T Telecommunications Facility @ 28 Great Oak Lane, Redding, CT 06896

Dear Ms. Bachman,

New Cingular Wireless, PCS, LLC ("AT&T") currently maintains a wireless telecommunications facility on an existing +/- 180' monopole tower at the above referenced address, latitude 41.3068333, longitude - 73.3863056. Said monopole tower is owned by Octagon Towers, LLC and managed by SRR Towers, LLC (an Octagon Towers subsidiary).

AT&T desires to modify its existing telecommunications facility by replacing (6) antennas, replacing (6) TMAs and adding (6) additional TMAs, adding (12) coax cables on the tower, replacing (3) RRUs, adding (3) RRUs, adding (2) surge arrestors within the equipment lease space as more particularly detailed and described on the enclosed Construction Drawings prepared by Hudson Design Engineering last revised on October 19, 2020. The centerline height of the existing antennas is and will remain at 165 and 175 feet.

Please accept this letter as notification pursuant to R.C.S.A §16-50j-73 for construction that constitutes an exempt modification pursuant to R.C.S.A §16-50j-72(b)(2). In accordance with R.C.S.A §16-50j-73, a copy of this letter is being sent to the following individuals: Julia Pemberton First Selectman of the Town of Redding, and as property owner: Toby S. Welles Planning Commission Chairman of Town of Redding: James Burgess Project Manager on behalf of SRR Towers LLC.

The planned modifications to the facility fall squarely within those activities explicitly provided for in R.C.S.A. §16-50j-72(b)(2). Specifically:

- 1. The proposed modifications will not result in an increase in the height of the existing structure.
- 2. The proposed modifications will not require an extension of the site boundary.
- 3. The proposed modifications will not increase noise levels at the facility by six decibels or more, or to levels that exceed state and local criteria.
- 4. The operation of the modified facility will not increase radio frequency emissions at the facility to a level at or above the Federal Communications Commission's safety standard. *Please see the RF emissions calculation for AT&T's modified facility enclosed herewith*.
- 5. The proposed modifications will not cause an ineligible change or alternation in the physical or environmental characteristics of the site.

6. The existing structure and its foundation can support the proposed loading. Please see the structural analysis dated January 5, 2021 and prepared BlueSky Tower Partners LLC enclosed herewith.

For the foregoing reasons, AT&T respectfully submits that the proposed modifications to the above referenced telecommunications facility constitute an exempt modification under R.C.S.A §16-50j-72(b)(2).

Best Regards,

Allison Hebel

Site Acquisition Consultant – Agent for AT&T Centerline Communications LLC 750 West Center St. Ste 301 West Bridgewater, MA 02379 215-588-7035 ahebel@clinellc.com

Enclosures: Exhibit 1 – Construction Drawings

Exhibit 2 – Property Card and GIS Exhibit 3 – Structural Analysis

Exhibit 4 – RF Emissions Analysis Report Evaluation

Exhibit 5 – Available Town of Redding Original Tower Approval Records

Exhibit 6 – Notice Deliver Confirmations

Cc: Julia Pemberton First Selectman of the Town of Redding, and as property owner

Toby S. Welles Planning Commission Chairman of Town of Redding

James Burgess Project Manager on behalf of SRR Towers LLC, tower owner

EXHIBIT 1

PROJECT INFORMATION

SCOPE OF WORK: ITEMS TO BE MOUNTED ON THE EXISTING FLAGPOLE:

• NEW AT&T ANTENNAS: 840370966 (TYP. OF 2 PER SECTOR, TOTAL OF 6). • NEW AT&T TMAS: TMABPD7823VG12A (TYP. OF 4 PER SECTOR, TOTAL OF 12)

ITEMS TO BE MOUNTED AT EQUIPMENT LOCATION:

- NEW AT&T RRUS: B5/B12 4449 (850/700) (TYP. OF 1 PER SECTOR, TOTAL OF 3). NEW AT&T RRUS: B2/B66A 8843 (PCS/AWS) (TYP. OF 1 PER SECTOR, TOTAL OF 3).
- NEW AT&T TRIPLEXERS: TPX-070821 (TYP. OF 8 PER SECTOR, TOTAL OF 24)
- NEW AT&T SURGE ARRESTORS: TSXDC-4310FM (TYP. OF 12 PER SECTOR,
- ADD (1) IDLe. • ADD (1) 6630.
- •ADD (12) 1-5/8" COAX.

ITEMS TO BE REMOVED:

- EXISTING AT&T ANTENNAS: SBNH-1D6565C (TYP. OF 2 PER SECTOR, TOTAL OF 6).
 EXISTING AT&T RRUS: RRUS-11 B12 (TYP. OF 1 PER SECTOR, TOTAL OF 3).
- EXISTING AT&T RRUS: RRUS-11 B2 (TYP. OF 1 PER SECTOR, TOTAL OF 3).
- EXISTING AT&T RRUS: RRUS-11 B5 (TYP. OF 1 PER SECTOR, TOTAL OF 3).

ITEMS TO REMAIN:

• (12) 1-5/8" COAX CABLES

2051A0V4QH, 2051A0V49D, 2051A0V4D2, 2051A0V52J

SITE ADDRESS: 28 GREAT OAK LANE REDDING, CT 06896

LATITUDE: 41.306833° N, 41° 18' 24.59" N LONGITUDE: 73.386305° W, 73° 23' 10.70" W

FLAGPOLE / INDOOR TYPE OF SITE:

STRUCTURE HEIGHT:

RAD CENTER: 175'-0"± & 165'-0"± CURRENT USE: TELECOMMUNICATIONS FACILITY

PROPOSED USE: TELECOMMUNICATIONS FACILITY



SITE NUMBER: CT2546

SITE NAME: REDDING GREAT OAK LANE

FA CODE: 10050764

PACE ID: MRCTB046960, MRCTB046944, MRCTB046797, MRCTB046655

PROJECT: LTE 2C_3C_5G NR_RETRO 2021 UPGRADE

	DRAWING INDEX				
SHEET NO.	DESCRIPTION	REV.			
T-1	TITLE SHEET	В			
GN-1	GENERAL NOTES	В			
A-1	COMPOUND & EQUIPMENT PLANS	В			
A-2	ANTENNA LAYOUTS & ELEVATION	В			
A-3	DETAILS	В			
G-1	GROUNDING DETAILS	В			
RF-1	RF PLUMBING DIAGRAM	В			

VICINITY MAP DIRECTIONS TO SITE:

TURN LEFT ONTO CAPITAL BLVD (.2 MI)TURN LEFT ONTO STATE HWY 411 THEN LEFT TO MERGE ONTO -91 S (8.8 MI). TAKE EXIT 18 FOR I-691 W TOWARD MERIDEN/WATERBURY (.3 MI). CONTINUE ONTO I-691 W (7.7 MI). TAKE EXIT 1 FOR I-84 W (1.0 MI) MERGE ONTO I-84 (23.3 MI). TAKE EXIT 11 TOWARD CT-34/DERBY-NEW HAVEN (.9 MI). TURN LEFT ONTO WASSERMAN WAY (1.0 MI), CONTINUE ONTO MILE HILL RD (.5 MI), TURN RÌGHT ÓNTO CT-25 N/S MAIN ST (.7 MI). TURN LEFT ONTO CT-302 W/SUGAR ST (2.5 MI). TURN LEFT ONTO KEY ROCK RD (.9 MI), CONTINUE ONTO POVERTY HOLLOW RD (3.7 MI), SLIGHT RIGHT ONTO CHURCH HILL RD (.6 MI), CONTINUE ONTO CROSS WAY (1.9 MI), SLIĞHT LEFT ONTO CT-107 A (.1 MI) TURN RIGHT ÖNTO GRAT OAK LN, DESTINATION ON THE RIGHT.



GENERAL NOTES

- THIS DOCUMENT IS THE CREATION, DESIGN, PROPERTY AND COPYRIGHTED WORK OF AT&T. ANY DUPLICATION OR USE WITHOUT EXPRESS WRITTEN CONSENT IS STRICTLY PROHIBITED. DUPLICATION AND USE BY GOVERNMENT AGENCIES FOR THE PURPOSES OF CONDUCTING THEIR LAWFULLY AUTHORIZED REGULATORY AND ADMINISTRATIVE FUNCTIONS IS SPECIFICALLY ALLOWED.
- 2. THE FACILITY IS AN UNMANNED PRIVATE AND SECURED EQUIPMENT INSTALLATION. IT IS ONLY ACCESSED BY TRAINED TECHNICIANS FOR PERIODIC ROUTINE MAINTENANCE AND THEREFORE DOES NOT REQUIRE ANY WATER OR SANITARY SEWER SERVICE. THE FACILITY IS NOT GOVERNED BY REGULATIONS REQUIRING PUBLIC ACCESS PER ADA REQUIREMENTS.
- 3. CONTRACTOR SHALL VERIFY ALL PLANS AND EXISTING DIMENSIONS AND CONDITIONS ON THE JOB SITE AND SHALL IMMEDIATELY NOTIFY THE AT&T MOBILITY REPRESENTATIVE IN WRITING OF DISCREPANCIES BEFORE PROCEEDING WITH THE WORK OR BE RESPONSIBLE FOR SAME.
- 4. CONSTRUCTION DRAWINGS ARE VALID FOR SIX MONTHS AFTER ENGINEER OF RECORD'S STAMPED AND SIGNED SUBMITTAL DATE LISTED HEREIN.

72 HOURS



BEFORE YOU DIG

CALL TOLL FREE 1 - 800 - 922 - 4455

or call 811

UNDERGROUND SERVICE ALERT

HUDSON Design Group LLC

45 BEECHWOOD DRIVE NORTH ANDOVER, MA 01845

TEL: (978) 557-5553 FAX: (978) 336-5586

CENTERLINE

750 WEST CENTER STREET, SUITE #301

WEST BRIDGEWATER, MA 02379"

SITE NUMBER: CT2546 SITE NAME: REDDING GREAT OAK LANE

28 GREAT OAK LANE REDDING, CT 06896 FAIRFIELD COUNTY



							ΖŪ		4
							V	V	2
						,			1
В	10/19/20	ISSUED FO	OR PERMITTIN	IG			SG	AT	DPH.
Α	08/10/20	ISSUED FO	ISSUED FOR REVIEW				TR	AT	DPH
NO.	DATE	REVISIONS BY CHK APP'D							
SCALE: AS SHOWN DESIGNED BY: AT DRAWN BY: TR									

AT&T TITLE SHEET LTE 2C_3C_5G NR_RETRO 2021 UPGRADE CT2546

GROUNDING NOTES

- 1. THE SUBCONTRACTOR SHALL REVIEW AND INSPECT THE EXISTING FACILITY GROUNDING SYSTEM AND LIGHTNING PROTECTION SYSTEM (AS DESIGNED AND INSTALLED) FOR STRICT COMPLIANCE WITH THE NEC (AS ADOPTED BY THE AHJ), THE SITE—SPECIFIC (UL, LPI, OR NFPA) LIGHTING PROTECTION CODE, AND GENERAL COMPLIANCE WITH TELCORDIA AND TIA GROUNDING STANDARDS. THE SUBCONTRACTOR SHALL REPORT ANY VIOLATIONS OR ADVERSE FINDINGS TO THE CONTRACTOR FOR RESOLUTION.
- 2. ALL GROUND ELECTRODE SYSTEMS (INCLUDING TELECOMMUNICATION, RADIO, LIGHTNING PROTECTION, AND AC POWER GES'S) SHALL BE BONDED TOGETHER, AT OR BELOW GRADE, BY TWO OR MORE COPPER BONDING CONDUCTORS IN ACCORDANCE WITH THE NEC.
- 3. THE SUBCONTRACTOR SHALL PERFORM IEEE FALL-OF-POTENTIAL RESISTANCE TO EARTH TESTING (PER IEEE 1100 AND 81 STANDARDS) FOR NEW GROUND ELECTRODE SYSTEMS. THE SUBCONTRACTOR SHALL FURNISH AND INSTALL SUPPLEMENTAL GROUND ELECTRODES AS NEEDED TO ACHIEVE A TEST RESULT OF 5 OHMS OR LESS.
- 4. METAL RACEWAY SHALL NOT BE USED AS THE NEC REQUIRED EQUIPMENT GROUND CONDUCTOR. STRANDED COPPER CONDUCTORS WITH GREEN INSULATION, SIZED IN ACCORDANCE WITH THE NEC, SHALL BE FURNISHED AND INSTALLED WITH THE POWER CIRCUITS TO BTS EQUIPMENT.
- 5. EACH BTS CABINET FRAME SHALL BE DIRECTLY CONNECTED TO THE MASTER GROUND BAR WITH GREEN INSULATED SUPPLEMENTAL EQUIPMENT GROUND WIRES, #6 AWG STRANDED COPPER OR LARGER FOR INDOOR BTS AND #2 AWG STRANDED COPPER FOR OUTDOOR BTS.
- 6. EXOTHERMIC WELDS SHALL BE USED FOR ALL GROUNDING CONNECTIONS BELOW GRADE.
- 7. APPROVED ANTIOXIDANT COATINGS (I.E., CONDUCTIVE GEL OR PASTE) SHALL BE USED ON ALL COMPRESSION AND BOLTED GROUND CONNECTIONS.
- 8. ICE BRIDGE BONDING CONDUCTORS SHALL BE EXOTHERMICALLY BONDED OR BOLTED TO GROUND BAR
- ALUMINUM CONDUCTOR OR COPPER CLAD STEEL CONDUCTOR SHALL NOT BE USED FOR GROUNDING CONNECTIONS.
- 10. MISCELLANEOUS ELECTRICAL AND NON-ELECTRICAL METAL BOXES, FRAMES AND SUPPORTS SHALL BE BONDED TO THE GROUND RING, IN ACCORDANCE WITH THE NEC.
- 11. METAL CONDUIT SHALL BE MADE ELECTRICALLY CONTINUOUS WITH LISTED BONDING FITTINGS OR BY BONDING ACROSS THE DISCONTINUITY WITH #6 AWG COPPER WIRE UL APPROVED GROUNDING TYPE CONDUIT CLAMPS.
- 12. ALL NEW STRUCTURES WITH A FOUNDATION AND/OR FOOTING HAVING 20 FT. OR MORE OF 1/2 IN. OR GREATER ELECTRICALLY CONDUCTIVE REINFORCING STEEL MUST HAVE IT BONDED TO THE GROUND RING USING AN EXOTHERMIC WELD CONNECTION USING #2 AWG SOLID BARE TINNED COPPER GROUND WIRE, PER NEC 250.50

GENERAL NOTES

1. FOR THE PURPOSE OF CONSTRUCTION DRAWING, THE FOLLOWING DEFINITIONS SHALL APPLY:

CONTRACTOR - CENTERLINE SUBCONTRACTOR - GENERAL CONTRACTOR (CONSTRUCTION) OWNER - AT&T MOBILITY

- PRIOR TO THE SUBMISSION OF BIDS, THE BIDDING SUBCONTRACTOR SHALL VISIT THE CELL SITE TO FAMILIARIZE WITH THE EXISTING CONDITIONS AND TO CONFIRM THAT THE WORK CAN BE ACCOMPLISHED AS SHOWN ON THE CONSTRUCTION DRAWINGS. ANY DISCREPANCY FOUND SHALL BE BROUGHT TO THE ATTENTION OF CONTRACTOR.
- 3. ALL MATERIALS FURNISHED AND INSTALLED SHALL BE IN STRICT ACCORDANCE WITH ALL APPLICABLE CODES, REGULATIONS, AND ORDINANCES. SUBCONTRACTOR SHALL ISSUE ALL APPROPRIATE NOTICES AND COMPLY WITH ALL LAWS, ORDINANCES, RULES, REGULATIONS, AND LAWFUL ORDERS OF ANY PUBLIC AUTHORITY REGARDING THE PERFORMANCE OF THE WORK. ALL WORK CARRIED OUT SHALL COMPLY WITH ALL APPLICABLE MUNICIPAL AND UTILITY COMPANY SPECIFICATIONS AND LOCAL JURISDICTIONAL CODES, ORDINANCES AND APPLICABLE REGULATIONS.
- 4. DRAWINGS PROVIDED HERE ARE NOT TO BE SCALED AND ARE INTENDED TO SHOW OUTLINE ONLY.
- 5. UNLESS NOTED OTHERWISE, THE WORK SHALL INCLUDE FURNISHING MATERIALS, EQUIPMENT, APPURTENANCES, AND LABOR NECESSARY TO COMPLETE ALL INSTALLATIONS AS INDICATED ON THE DRAWINGS
- 6. "KITTING LIST" SUPPLIED WITH THE BID PACKAGE IDENTIFIES ITEMS THAT WILL BE SUPPLIED BY CONTRACTOR. ITEMS NOT INCLUDED IN THE BILL OF MATERIALS AND KITTING LIST SHALL BE SUPPLIED BY THE SUBCONTRACTOR.
- 7. THE SUBCONTRACTOR SHALL INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS UNLESS SPECIFICALLY STATED OTHERWISE.
- 8. IF THE SPECIFIED EQUIPMENT CANNOT BE INSTALLED AS SHOWN ON THESE DRAWINGS, THE SUBCONTRACTOR SHALL PROPOSE AN ALTERNATIVE INSTALLATION SPACE FOR APPROVAL BY THE CONTRACTOR.
- 9. SUBCONTRACTOR SHALL DETERMINE ACTUAL ROUTING OF CONDUIT, POWER AND T1 CABLES, GROUNDING CABLES AS SHOWN ON THE POWER, GROUNDING AND TELCO PLAN DRAWING. SUBCONTRACTOR SHALL UTILIZE EXISTING TRAYS AND/OR SHALL ADD NEW TRAYS AS NECESSARY. SUBCONTRACTOR SHALL CONFIRM THE ACTUAL ROUTING WITH THE CONTRACTOR.
- 10. THE SUBCONTRACTOR SHALL PROTECT EXISTING IMPROVEMENTS, PAVEMENTS, CURBS, LANDSCAPING AND STRUCTURES. ANY DAMAGED PART SHALL BE REPAIRED AT SUBCONTRACTOR'S EXPENSE TO THE SATISFACTION OF OWNER.
- 11. SUBCONTRACTOR SHALL LEGALLY AND PROPERLY DISPOSE OF ALL SCRAP MATERIALS SUCH AS COAXIAL CABLES AND OTHER ITEMS REMOVED FROM THE EXISTING FACILITY. ANTENNAS REMOVED SHALL BE RETURNED TO THE OWNER'S DESIGNATED LOCATION.
- 12. SUBCONTRACTOR SHALL LEAVE PREMISES IN CLEAN CONDITION.
- 13. ALL CONCRETE REPAIR WORK SHALL BE DONE IN ACCORDANCE WITH AMERICAN CONCRETE INSTITUTE (ACI) 301.

- 14. ANY NEW CONCRETE NEEDED FOR THE CONSTRUCTION SHALL BE AIR—ENTRAINED AND SHALL HAVE 4000 PSI STRENGTH AT 28 DAYS. ALL CONCRETE WORK SHALL BE DONE IN ACCORDANCE WITH ACI 318 CODE REQUIREMENTS.
- 15. ALL STRUCTURAL STEEL WORK SHALL BE DETAILED, FABRICATED AND ERECTED IN ACCORDANCE WITH AISC SPECIFICATIONS. ALL STRUCTURAL STEEL SHALL BE ASTM A36 (Fy = 36 ksi) UNLESS OTHERWISE NOTED. PIPES SHALL BE ASTM A53 TYPE E (Fy = 36 ksi). ALL STEEL EXPOSED TO WEATHER SHALL BE HOT DIPPED GALVANIZED. TOUCH UP ALL SCRATCHES AND OTHER MARKS IN THE FIELD AFTER STEEL IS ERECTED USING A COMPATIBLE ZINC RICH PAINT.
- 16. CONSTRUCTION SHALL COMPLY WITH SPECIFICATIONS AND "GENERAL CONSTRUCTION SERVICES FOR CONSTRUCTION OF AT&T SITES."
- 17. SUBCONTRACTOR SHALL VERIFY ALL EXISTING DIMENSIONS AND CONDITIONS PRIOR TO COMMENCING ANY WORK. ALL DIMENSIONS OF EXISTING CONSTRUCTION SHOWN ON THE DRAWINGS MUST BE VERIFIED. SUBCONTRACTOR SHALL NOTIFY THE CONTRACTOR OF ANY DISCREPANCIES PRIOR TO ORDERING MATERIAL OR PROCEEDING WITH CONSTRUCTION.
- 18. THE EXISTING CELL SITE IS IN FULL COMMERCIAL OPERATION. ANY CONSTRUCTION WORK BY SUBCONTRACTOR SHALL NOT DISRUPT THE EXISTING NORMAL OPERATION. ANY WORK ON EXISTING EQUIPMENT MUST BE COORDINATED WITH CONTRACTOR. ALSO, WORK SHOULD BE SCHEDULED FOR AN APPROPRIATE MAINTENANCE WINDOW USUALLY IN LOW TRAFFIC PERIODS AFTER MIDNIGHT.
- 19. SINCE THE CELL SITE IS ACTIVE, ALL SAFETY PRECAUTIONS MUST BE TAKEN WHEN WORKING AROUND HIGH LEVELS OF ELECTROMAGNETIC RADIATION. EQUIPMENT SHOULD BE SHUTDOWN PRIOR TO PERFORMING ANY WORK THAT COULD EXPOSE THE WORKERS TO DANGER. PERSONAL RF EXPOSURE MONITORS ARE ADVISED TO BE WORN TO ALERT OF ANY DANGEROUS EXPOSURE LEVELS.

20. APPLICABLE BUILDING CODES:

SUBCONTRACTOR'S WORK SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE, AND LOCAL CODES AS ADOPTED BY THE LOCAL AUTHORITY HAVING JURISDICTION (AHJ) FOR THE LOCATION. THE EDITION OF THE AHJ ADOPTED CODES AND STANDARDS IN EFFECT ON THE DATE OF CONTRACT AWARD SHALL GOVERN THE DESIGN.

BUILDING CODE: IBC 2015 WITH 2018 CT STATE BUILDING CODE AMENDMENTS ELECTRICAL CODE: 2017 NATIONAL ELECTRICAL CODE (NFPA 70-2017)

SUBCONTRACTOR'S WORK SHALL COMPLY WITH THE LATEST EDITION OF THE FOLLOWING STANDARDS:

AMERICAN CONCRETE INSTITUTE (ACI) 318; BUILDING CODE REQUIREMENTS FOR STRUCTURAL CONCRETE;

AMERICAN INSTITUTE OF STEEL CONSTRUCTION (AISC) MANUAL OF STEEL CONSTRUCTION. ASD. FOURTEENTH EDITION:

TELECOMMUNICATIONS INDUSTRY ASSOCIATION (TIA) 222-H, STRUCTURAL STANDARDS FOR STEEL

FOR ANY CONFLICTS BETWEEN SECTIONS OF LISTED CODES AND STANDARDS REGARDING MATERIAL, METHODS OF CONSTRUCTION, OR OTHER REQUIREMENTS, THE MOST RESTRICTIVE REQUIREMENT SHALL GOVERN. WHERE THERE IS CONFLICT BETWEEN A GENERAL REQUIREMENT AND A SPECIFIC REQUIREMENT, THE SPECIFIC REQUIREMENT SHALL GOVERN.

			ABBREVIATIONS		
AGL	ABOVE GRADE LEVEL	EQ	EQUAL	REQ	REQUIRED
AWG	AMERICAN WIRE GAUGE	GC	GENERAL CONTRACTOR	RF	RADIO FREQUENCY
BBU	BATTERY BACKUP UNIT	GRC	GALVANIZED RIGID CONDUIT	TBD	TO BE DETERMINED
BTCW	BARE TINNED SOLID COPPER WIRE	MGB	MASTER GROUND BAR	TBR	TO BE REMOVED
BGR	BURIED GROUND RING	MIN	MINIMUM	TBRR	TO BE REMOVED AND REPLACED
BTS	BASE TRANSCEIVER STATION	Р	PROPOSED	TYP	TYPICAL
E	EXISTING	NTS	MOT TO SCALE	UG	UNDER GROUND
EGB	EQUIPMENT GROUND BAR	RAD	RADIATION CENTER LINE (ANTENNA)	VIF	VERIFY IN FIELD
EGR	EQUIPMENT GROUND RING	REF			



FAX: (978) 336-5586

NORTH ANDOVER, MA 01845




750 WEST CENTER STREET, SUITE #301

WEST BRIDGEWATER, MA 02379

SITE NUMBER: CT2546 SITE NAME: REDDING GREAT OAK LANE

> 28 GREAT OAK LANE REDDING, CT 06896 FAIRFIELD COUNTY







GENERAL NOTES


LTE 2C_3C_5G NR_RETRO 2021 UPGRADE

ONAL ENGINEER DRAWING NUMBER F

CT2546 GN-1







FINAL ANTENNA SCHEDULE SCALE: N.T.S (A-3)

RRU CHART					
QUANTITY MODEL SIZE (L x W x D)					
3(P)	4449 (850/700)	17.9"x13.2"x10.4"			
3(P) 8843 (PCS/AWS) 14.9"x13.2"x10.9"					
NOTE:					

MOUNT PER MANUFACTURER'S SPECIFICATIONS

NOTE: SEE RFDS FOR RRH FREQUENCY AND MODEL NUMBER

PROPOSED RRU REFER TO THE -FINAL RFDS AND CHART FOR QUANTITY, MODEL AND DIMENSIONS

MOUNT PER MANUFACTURER'S SPECIFICATIONS.

PROPOSED RRUS DETAIL SCALE: N.T.S

- EXISTING UNISTRUT (TYP.) -PROPOSED AT&T RRUS 8843 B2/B66A (PCS/AWS) (TYP. OF 1 PER SECTOR, TOTAL OF 3) PROPOSED AT&T RRUS 4449 -B5/B12 (850/700) (TYP. OF TOTAL OF 3)

PROPOSED RRUS MOUNTING DETAIL 22x34 SCALE: 1/2"=1'-0'

(A-3

11x17 SCALE: 1/4"=1'-0"

SITE NUMBER: CT2546 SITE NAME: REDDING GREAT OAK LANE

> 28 GREAT OAK LANE FAIRFIELD COUNTY



ROCKY HILL, CT 06067

						/(<u>) </u>		/`/
						\mathcal{N}		П F	
						\triangleright	N	7	P/
									У
В	10/19/20	ISSUED FOR	PERMITTING			SG	ΑT	DPH.	8/
Α	08/10/20	ISSUED FOR	REVIEW			TR	AT	DPH	700
NO.	DATE		REVIS	SIONS		BY	СНК	APP'D	115
SCA	LE: AS SI	HOWN	DESIGNED BY	: AT	DRAW	N BY:	TR		'//

TOP OF TOWER

ELEV. = 180'-0" ± A.G.L

© OF PROPOSED AT&T ANTENNAS ELEV. 175'-0"± (AGL)

PROPOSED AT&T LTE

TOTAL OF 6)

ANTENNA (840370966)

MOUNTED INSIDE FLAGPOLE

(TYP. OF 2 PER SECTOR,

FRP CONNECTION
ELEV. = 170'-0" ± A.G.L

© OF PROPOSED AT&T ANTENNAS ELEV. 165'-0"± (AGL)

PROPOSED 48"ø (10' LONG)-FRP SHROUD (TOTAL OF 2)

FRP CONNECTION
ELEV. = 160'-0" ± A.G.L

PROPOSED AT&T TMAS -

TMABPD7823VG12A (TYP. OF 4

PROPOSED LTE ANTENNA

MOUNTING DETAIL

22x34 SCALE: 1/2"=1'-0"

11x17 SCALE: 1/4"=1"-0"

PER SECTOR, TOTAL OF 12)

(BY OTHERS)

AT&T **DETAILS** LTE 2C_3C_5G NR_RETRO 2021 UPGRADE CT2546

NOTE:

NOTE:

CONSTRUCTION.

4'-0"±

3'-3"±

REFER TO THE FINAL RF DATA SHEET

AN ANALYSIS FOR THE CAPACITY OF

SUPPORT THE PROPOSED EQUIPMENT

- EXISTING FRP SHROUD (TO BE REPLACED)

> PROPOSED AT&T (12) 1-5/8" COAX CABLE (TO TERMINATE PRIOR TO LOWEST ANTENNA LEVEL AND TO RUN TO AT&T

LOCATION VIA 1/2"ø

JUMPER CABLES)

EXISTING 1'-6"ø FLAGPOLE SPINE

SHALL BE DETERMINED PRIOR TO

FOR FINAL ANTENNA SETTINGS.

THE EXISTING STRUCTURES TO



NORTH ANDOVER, MA 01845


TEL: (978) 557-5553 FAX: (978) 336-5586

CENTERLINE


750 WEST CENTER STREET, SUITE #301


WEST BRIDGEWATER, MA 02379

REDDING, CT 06896



1. DO NOT INSTALL CABLE GROUND KIT AT A BEND AND ALWAYS DIRECT GROUND WIRE DOWN TO CIGBE.





NOTES:

STAINLESS:

- "DOUBLING UP" OR "STACKING" OF CONNECTION IS NOT PERMITTED.
- OX STACKING OF CONSISTING IS NOT LEADING.
 OXIDE INHIBITING COMPOUND TO BE USED AT ALL LOCATION.
 CADWELD DOWNLEADS FROM UPPER EGB, LOWER EGB, AND MGB.

TYPICAL GROUND BAR CONNECTION DETAIL SCALE: N.T.S




EACH GROUND CONDUCTOR TERMINATING ON ANY GROUND BAR SHALL HAVE AN IDENTIFICATION TAG ATTACHED AT EACH END THAT WILL IDENTIFY ITS ORIGIN AND DESTINATION.

SECTION "P" - SURGE PRODUCERS

CABLE ENTRY PORTS (HATCH PLATES) (#2 AWG) GENERATOR FRAMEWORK (IF AVAILABLE) "(#2 AWG) TELCO GROUND BAR COMMERCIAL POWER COMMON NEUTRAL/GROUND BOND (#2 AWG) +24V POWER SUPPLY RETURN BAR (#2 AWG) -48V POWER SUPPLY RETURN BAR (#2 AWG) RECTIFIER FRAMES.

SECTION "A" - SURGE ABSORBERS

INTERIOR GROUND RING (#2 AWG) EXTERNAL EARTH GROUND FIELD (BURIED GROUND RING) (#2 AWG)
METALLIC COLD WATER PIPE (IF AVAILABLE) (#2 AWG) BUILDING STEEL (IF AVAILABLE) (#2 AWG)



GROUND BAR - DETAIL (AS REQUIRED)

SCALE: N.T.S



45 BEECHWOOD DRIVE NORTH ANDOVER, MA 01845

TEL: (978) 557-5553 FAX: (978) 336-5586



750 WEST CENTER STREET, SUITE #301 WEST BRIDGEWATER, MA 02379

SITE NUMBER: CT2546 SITE NAME: REDDING GREAT OAK LANE

> 28 GREAT OAK LANE REDDING, CT 06896 FAIRFIELD COUNTY



							/	1		<u>/ </u>
							\mathcal{I}	/_	17 F	
							∇	N		1
-										V
-	В	10/19/20	ISSUED FOR	PERMITTING			SG	ΑT	DPH.	
	Α	08/10/20	ISSUED FOR	REVIEW			TR	AT	DP₩	70x7
	NO.	DATE		REVIS	IONS		BY	СНК	APP'D	115
	SCA	LE: AS SI	HOWN	DESIGNED BY	: AT	DRAWN	N BY:	TR		. /

AT&T GROUNDING DETAILS LTE 2C_3C_5G NR_RETRO 2021 UPGRADE CT2546





EXHIBIT 2





28 GREAT OAK LN

Location 28 GREAT OAK LN Mblu 21//108//

Acct# 00140200 Owner REDDING TOWN OF

Assessment \$1,437,100 **Appraisal** \$2,052,700

PID 1393 Building Count 2

Current Value

Appraisal Appraisal					
Valuation Year	Improvements	Land	Total		
2017	\$602,200	\$1,450,500	\$2,052,700		
	Assessment				
Valuation Year	Improvements	Land	Total		
2017	\$421,700	\$1,015,400	\$1,437,100		

Owner of Record

 Owner
 REDDING TOWN OF
 Sale Price
 \$0

 Co-Owner
 TOWN GARAGE
 Certificate
 1

 Address
 PO BOX 1028
 Book & Page
 0065

PO BOX 1028 Book & Page 0065/0343
REDDING, CT 06875- Sale Date 05/17/1963

Instrument XX

Ownership History

Ownership History					
Owner Sale Price Certificate Book & Pag		Book & Page	Instrument	Sale Date	
REDDING TOWN OF	\$0	1	0065/0343	xx	05/17/1963

Building Information

Building 1: Section 1

Year Built: 1964
Living Area: 7,488
Replacement Cost: \$445,425
Building Percent Good: 69

Replacement Cost

Less Depreciation: \$307,300

Building Attributes


Field	Description
STYLE	Comm Garage
MODEL	Comm/Ind
Grade	С
Stories	1
Occupancy	1.00
Exterior Wall 1	Brick/Masonry
Exterior Wall 2	
Roof Structure	Gable
Roof Cover	Asphalt Shingl
Interior Wall 1	Minimum
Interior Wall 2	
Interior Floor 1	Linoleum
Interior Floor 2	
Heating Fuel	Oil
Heating Type	Forced Air
AC Type	None
Struct Class	
Bldg Use	Mun Bldg Com
Usrfld 215	
Bedrooms	
Full Bths	
Half Bths	
Usrfld 219	
1st Floor Use:	
Heat/AC	None
Frame Type	Masonry
Baths/Plumbing	Average
Ceiling/Walls	Ceil and Min W
Rooms/Prtns	Average
Wall Height	14.00
% Comn Wall	

Building Photo



(http://images.vgsi.com/photos/ReddingCTPhotos/\00\01\16\62.jpg)

Building Layout



Building Sub-Areas (sq ft) <u>Legen</u>					
Code	Description	Gross Area	Living Area		
BAS	First Floor	6,208	6,208		
AOF	Office Area	1,280	1,280		
CAN	Canopy	240	0		
SLB	Slab	6,208	0		
		13,936	7,488		

Building 2 : Section 1

Year Built: 1964
Living Area: 5,640
Replacement Cost: \$329,560
Building Percent Good: 69

Replacement Cost

Less Depreciation: \$227,400

Building Attributes : Bldg 2 of 2			
Field	Description		

STYLE	Comm Garage
MODEL	Comm/Ind
Grade	С
Stories	1
Occupancy	1.00
Exterior Wall 1	Pre-finsh Metl
Exterior Wall 2	
Roof Structure	Gable
Roof Cover	Metal/Tin
Interior Wall 1	Minimum
Interior Wall 2	
Interior Floor 1	Minimum/Plywd
Interior Floor 2	
Heating Fuel	Oil
Heating Type	Forced Air
AC Type	None
Struct Class	
Bldg Use	Mun Bldg Com
Usrfld 215	
Bedrooms	
Full Bths	
Half Bths	
Usrfld 219	
1st Floor Use:	
Heat/AC	None
Frame Type	Steel
Baths/Plumbing	Average
Ceiling/Walls	Ceil & Wall
Rooms/Prtns	Average
Wall Height	16.00
% Comn Wall	

Building Photo



(http://images.vgsi.com/photos/ReddingCTPhotos//default.jpg)

Building Layout



Building Sub-Areas (sq ft)			Legend
Code	Description	Gross Area	Living Area
BAS	First Floor	5,640	5,640
BSM	Basement Area	1,040	0
SLB	Slab	4,600	0
		11,280	5,640

Extra Features

Extra Features Legend				
Code	Description	Size	Value	Bldg #
LFT2	Lift Heavy	1.00 Units	\$2,800	2
MEZ1	Mezzanine Unf.	180.00 S.F.	\$2,500	2

Land

Land	Use
------	-----

Use Code 922

Description Mun Bldg Com

Zone R-2

Neighborhood 1400 Alt Land Appr No

Category

Size (Acres) 6.50

Frontage Depth

Assessed Value \$1,015,400 **Appraised Value** \$1,450,500

Outbuildings

	Outbuildings <u>Legen</u>					
Code	Description	Sub Code	Sub Description	Size	Value	Bldg #
PAV1	Paving Asph.			29060.00 S.F.	\$47,100	1
SHD2	Salt Shed			6300.00 S.F.	\$15,100	1

Valuation History

Appraisal					
Valuation Year	Improvements	Land	Total		
2018	\$602,200	\$1,450,500	\$2,052,700		
2017	\$602,200	\$1,450,500	\$2,052,700		
2016	\$525,200	\$1,450,500	\$1,975,700		

Assessment					
Valuation Year	Improvements	Land	Total		
2018	\$421,700	\$1,015,400	\$1,437,100		
2017	\$421,700	\$1,015,400	\$1,437,100		
2016	\$367,800	\$1,015,400	\$1,383,200		

(c) 2016 Vision Government Solutions, Inc. All rights reserved.

EXHIBIT 3



Structural Analysis Report

Structure : 180ft Stealth Pole

BlueSky Site Name : S. Yale Ave

BlueSky Site # : CT-1420

Proposed Carrier : AT&T

Carrier Site Name : Redding Great Oak Lane

Carrier Site Number : 10050764 / CT2546

Site Location : 28 Great Oak Lane

Redding, CT 06896 (Fairfield County)

41.3068333, -73.3863056

Date : January 5, 2021

Max Member Stress Level: 40.4% (Tower)

Unknown (Slimline Steel Pipe) – more info required

89.0% (Baseplate)

87.6% (Caisson Foundation)

54.9% (Mat and Pier Foundation)

Result : PASS

Prepared by:
Bennett & Pless, Inc.
B&P Job No.: 20.03.017.006





Table of Contents

Introduction	1
Existing Structural Information	1
Final Proposed Equipment Loading for AT&T	1
Design Criteria	2
Analysis Results	2
Assumptions	
Conclusions	3
Standard Conditions	
Disclaimer of Warranties	4
Calculations	Attached
Collocation Application	Attached

Introduction

We have completed our structural analysis of the proposed equipment installation on the foregoing tower to determine its ability to support the new loads proposed by AT&T. The objective of the analysis was to determine if the tower meets the current structural codes and standards with the proposed equipment installation.

Existing Structural Information

The following documents for the existing structure were made available for our structural analysis.

Tower Information	Sabre tower drawings Job No.: 41261 dated March 2, 2011.	
Foundation Information	Sabre tower drawings Job No.: 41261 dated March 2, 2011.	
Geotechnical Information	Sabre tower drawings Job No.: 41261 dated March 2, 2011.	
Existing Equipment Information	BlueSky Collocation Application dated October 16, 2020.	
Tower Reinforcement Information	Tower has not been previously reinforced.	

Final Proposed Equipment Loading for AT&T

The following proposed loading was obtained from the BlueSky Collocation Application:

Antenna/Equipment					Coax	
Mount	RAD	Qty.	Antenna	Type	Qty.	Size/Type
177.0	175.0	3	Kathrein 840370966	Panel	12	1 5/8" Coax
177.0 175.0	6	CCI TMABPD7823VG12A	TMA	12	1 5/6" Coax	
165.0	165.0 165.0		Kathrein 840370966	Panel	——————————————————————————————————————	1 5/8" Coax
165.0 165.0	165.0	165.0 6 CCI TMABPD7823VG12A	TMA			

Note: Proposed equipment shown in bold.

Note: Other existing loading can be found on the tower profile attached.

Design Criteria

The tower was analyzed using tnxTower (Version 8.0.7.4) tower analysis software using the following design criteria.

State/County	Connecticut/Fairfield County		
State Building Code	Connecticut State Building Code 2018 (IBC 2015)		
TIA/EIA Standard Code	Code TIA-222-G		
Basic Wind Speed	118 MPH (Vult) / 92 MPH (Vasd)		
Basic Wind Speed w/ Ice	50 MPH/ 0.75" Ice		
Exposure	Centered between B and C		
	See Bennett & Pless Wind Exposure Letter dated		
	January 5, 2021		
Steel Grade	See attached tower profile and output for steel		
	grade		



Analysis Results

Based on the foregoing information, our structural analysis determined that the existing main tower from 0'-0" to 126'-0" AGL is structurally capable of supporting the proposed equipment loads without modification. The existing foundations and baseplate have also been evaluated and are structurally capable of supporting the proposed equipment loads.

Note: The top 20'-0" of the canister from 160'-0" AGL to 180'-0" AGL is being replaced from 36" diameter to a new shroud that is 48" diameter. No information was provided for the slimline steel pipe section from 126'-0" AGL to 160'-0" AGL and the base plate connecting to the top portion of the main steel pole. We recommend obtaining information on these structural elements before installation.

Assumptions

- 1. The existing tower has been maintained to manufacturer's specifications and is in good condition.
- 2. Foundations are considered to have been properly designed for the original design loads.
- 3. All member connections are considered to have been designed to meet the load carrying capacity of the connected member.
- 4. Antenna mount loads have been estimated based on generally accepted industry standards.
- 5. The mounts for the proposed antennas have been analyzed and designed by others.
- 6. See additional assumptions contained in the report attached.

Conclusions

The existing main tower described above **has sufficient capacity** to support the proposed loading based on the governing Building Code. The foundation is also acceptable. As noted in the Analysis Results section of this report more information is needed to determine the capacity of the slimline steel pipe section.

We appreciate the opportunity of providing our continuing professional services to you. If you have any questions or need further assistance, please call us anytime at 678-990-8700.

Sincerely,

Analysis by:

Cory Blake, P.E. Project Engineer

1/5/2021

Reviewed by:

Thomas F. Ireland, PE Principal



Standard Conditions

All engineering services are performed on the basis that the information used is current and correct. This information may consist of, but not necessarily limited, to:

- Information supplied by the client regarding the structure itself, the antenna and transmission line loading on the structure and its components, or relevant information.
- Information from drawings in possession of Bennett & Pless or generated by field inspections or measurements of the structure.

It is the responsibility of the client to ensure that the information provided to Bennett & Pless and used in the performance of our engineering services is correct and complete. In the absence of information contrary, we consider that all structures were constructed in accordance with the drawings and specifications and are in a un- corroded condition and have not deteriorated; and we, therefore consider that their capacity has not significantly changed from the original design condition.

All services will be performed to the codes and standards specified by the client, and we do not imply to meet any other code and standard requirements unless explicitly agreed to in writing. If wind and ice loads or other relevant parameters are to be different from the minimum values recommended by the codes and standards, the client shall specify the exact requirements. In the absence of information to the contrary, all work will be performed in accordance with the revision of ANSI/TIA/EIA-222 requested.

All services are performed, results obtained, and recommendations made in accordance with the generally accepted engineering principles and practices. Bennett & Pless is not responsible for the conclusions, opinions and recommendations made by others based on the information we supply.

Disclaimer of Warranties

Bennett & Pless Inc. makes no warranties, expressed or implied, in connection with this report, and disclaims any liability arising from the ability of the existing structure to support the design loads for which it was originally designed. Bennett & Pless Inc. will not be responsible whatsoever for or on account of, consequential or incidental damages sustained by any person, firm, or organization as a result of any data or conclusions contained in this report. The maximum liability of Bennett & Pless pursuant to this report will be limited to the total fee received for preparation of this report.



EXHIBIT 4



Radio Frequency Emissions Analysis Report

AT&T

Site Name: REDDING GREAT OAK LANE

28 Great Oaks Lane Redding, CT 06896 October 22, 2020

Site Compliance Summary				
Compliance Status:	Compliant			
Site total MPE% of FCC general population allowable limit:	0.127702%			



October 22, 2020 AT&T Mobility – New England Attn: John Benedetto, RF Manager 550 Cochituate Road Suite 550 – 13&14 Framingham, MA 01701

Emissions Analysis for Site: REDDING GREAT OAK LANE

Centerline Communications, LLC ("Centerline") was directed to analyze the proposed AT&T facility to be located on **Utility Pole #10050764** near **28 Great Oaks Lane, Redding CT 06896** for the purpose of determining whether the emissions from the proposed facility are within specified federal limits.

All information used in this report was analyzed as a percentage of current Maximum Permissible Exposure (% MPE) as listed in the FCC OET Bulletin 65 Edition 97-01and ANSI/IEEE Std C95.1. The FCC regulates Maximum Permissible Exposure in units of microwatts per square centimeter (μ W/cm2). The number of μ W/cm² calculated at each sample point is called the power density. The exposure limit for power density varies depending upon the frequencies being utilized. Wireless Carriers and Paging Services use different frequency bands each with different exposure limits, therefore it is necessary to report results and limits in terms of percent MPE rather than power density.

All results were compared to the FCC (Federal Communications Commission) radio frequency exposure rules, 47 CFR 1.1307(b)(1) - (b)(3), to determine compliance with the Maximum Permissible Exposure (MPE) limits for General Population/Uncontrolled environments as defined below.

General population/uncontrolled exposure limits apply to situations in which the general population may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Therefore, members of the general population would always be considered under this category when exposure is not employment related, for example, in the case of a telecommunications tower that exposes persons in a nearby residential area.

Population exposure to radio frequencies is regulated and enforced in units of microwatts per square centimeter (μ W/cm²). The general population exposure limits for the 1900 MHz (PCS) and 5 GHz (B46) bands is 1000 μ W/cm².

Occupational/controlled exposure limits apply to situations in which persons are exposed as a consequence of their employment and in which those persons who are exposed have been made fully aware of the potential for exposure and can exercise control over their exposure. Occupational/controlled exposure limits also apply where exposure is of a transient nature as a result of incidental passage through a location where exposure levels may be above general population/uncontrolled limits, as long as the exposed person has been made fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Additional details can be found in FCC OET 65.



CALCULATION FORMULAS

MODELING

RoofMasterTM employs several power density prediction models based on the computational approaches set forth in the Federal Communications Commission's Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields, OET Bulletin 65. This guideline utilizes several antenna and operational parameters in calculating the power density contributions from each emitter at specified points throughout the study space. RoofMasterTM enables antennas to be fully defined in site-specific aspects as well as through the use of a library of manufacturer data. The parameters include:

- Antenna model
- Radiation patterns
- Aperture length
- Gain
- Beam width
- Antenna radiation center
- Azimuth
- Mechanical downtilt
- Location Frequency
- Power into antenna

THE CYLINDRICAL MODEL IMPLEMENTATION (Sula9)

In OET-65, the Cylindrical Model is presented as an approach to determine the spatially averaged power density in the near field directly in front of an antenna. In order to implement this model in all directions, RoofMasterTM utilizes the antenna manufacturer horizontal pattern data. Additionally, RoofMasterTM incorporates factors that reduce the power density by the inverse square of horizontal and vertical distance beyond the near field region.

Power density is calculated as follows:

$$S = \left(\left(\frac{360}{Beamwidth} \right) \frac{P_{in}G_{H}H_{r}V_{r}}{2\pi Rh} \right) \frac{\mu W}{cm^{2}}$$

- S is the spatially averaged power density value
- R is the horizontal distance meters to the study point
- h is the aperture length in meters
- Pin is power into the antenna input port in Watts
- RoofMasterTM Implementation:
 - o GH is gain offset to study point as specified in manufacturer horizontal pattern
 - o Pin is adjusted by the portion of the antenna aperture in the 0-6 ft vertical study zone
 - o Hr accounts for 1/R2 Far Field roll off which starts at 2xh
 - O Vr accounts for 1/ (vertical distance)2 roll off from antenna bottom to the top of the 0-6ft study zone (or antenna top to bottom of 0-6ft study zone)



For each sector the following channel counts, frequency bands and power levels were utilized as shown in *Table 1*:

RRH#	Technology	Frequency Band	Channel Count	Transmit Power Per Channel (W)
1	UMTS	850	4	40
1	LTE	2100	4	40
2	LTE	700	4	40
2	LTE	850	4	40
2	LTE	1900	4	40
3	UMTS	850	4	40
3	LTE	2100	4	40
4	LTE	700	4	40
4	LTE	850	4	40
4	LTE	1900	4	40
5	UMTS	850	4	40
5	LTE	2100	4	40
6	LTE	700	4	40
6	LTE	850	4	40
6	LTE	1900	4	40

Table 1: Channel Data Table



Sector	Antenna Number	Frequency	Antenna Make / Model	Antenna Centerline (ft)
A	1	850	KATHREIN 840370966	175
A	1	2100	KATHREIN 840370966	175
A	2	700	KATHREIN 840370966	165
A	2	850	KATHREIN 840370966	165
A	2	1900	KATHREIN 840370966	165
В	3	850	KATHREIN 840370966	175
В	3	2100	KATHREIN 840370966	175
В	4	700	KATHREIN 840370966	165
В	4	850	KATHREIN 840370966	165
В	4	1900	KATHREIN 840370966	165
С	5	850	KATHREIN 840370966	175
C	5	2100	KATHREIN 840370966	175
C	6	700	KATHREIN 840370966	165
С	6	850	KATHREIN 840370966	165
C	6	1900	KATHREIN 840370966	165

Table 2: Antenna Data

All calculations were done with respect to uncontrolled / general population threshold limits.



RESULTS

Per the calculations completed for the proposed AT&T configurations *Table 3* shows resulting emissions power levels and percentages of the FCC's allowable general population limit.

Antenna ID	Antenna Make / Model	Frequency Bands	Antenna Gain (dBd)	Antenna Centerline (ft)	Channel Count	TX Power (W)	ERP (W)	MPE %
AT&T 1	KATHREIN 840370966	850	13.55	171.1	4	40	3623.4	0.009595957
AT&T 1	KATHREIN 840370966	2100	16.54	171.1	4	40	7213.0	0.004777873
AT&T 2	KATHREIN 840370966	700	11.93	161.1	4	40	2495.2	0.012338200
AT&T 2	KATHREIN 840370966	850	13.55	161.1	4	40	3623.4	0.010849707
AT&T 2	KATHREIN 840370966	1900	15.85	161.1	4	40	6153.4	0.005035206
AT&T 3	KATHREIN 840370966	850	13.55	171.1	4	40	3623.4	0.009595815
AT&T 3	KATHREIN 840370966	2100	16.54	171.1	4	40	7213.0	0.004777640
AT&T 4	KATHREIN 840370966	700			4	40		
			11.93	161.1			2495.2	0.012338004
AT&T 4	KATHREIN 840370966	850	13.55	161.1	4	40	3623.4	0.010849535
AT&T 4	KATHREIN 840370966	1900	15.85	161.1	4	40	6153.4	0.005034944
AT&T 5	KATHREIN 840370966	850	13.55	171.1	4	40	3623.4	0.009464302
AT&T 5	KATHREIN 840370966	2100	16.54	171.1	4	40	7213.0	0.004889075
AT&T 6	KATHREIN 840370966	700	11.93	161.1	4	40	2495.2	0.012338202
AT&T 6	KATHREIN 840370966	850	13.55	161.1	4	40	3623.4	0.010700845
AT&T 6	KATHREIN 840370966	1900	15.85	161.1	4	40	6153.4	0.005116920
	Site Total Composite MPE%							0.127702 %

Table 3: Antenna Inventory & Power Levels



FCC OET 65 specifies that for carriers utilizing directional antennas that the highest recorded sector value be used for composite site MPE values due to their greatly reduced emissions contributions in the directions of the adjacent sectors. *Table 4* below details a breakdown by frequency band and technology for the MPE power values for the maximum calculated AT&T sector(s).

Frequency Band	# of Channels	TPO W (Per Channel)	Height (feet)	Total Power Density (μW/cm²)	Technology	Allowable MPE (μW/cm²)	Calculated % MPE
850	4	40	171.1	0.0543771	UMTS	567	0.00959596
2100	4	40	171.1	0.0477787	LTE	1000	0.00477787
700	4	40	161.1	0.0575783	LTE	467	0.01233820
850	4	40	161.1	0.0614817	LTE	567	0.01084971
1900	4	40	161.1	0.0503521	LTE	1000	0.00503521
850	4	40	171.1	0.0543763	UMTS	567	0.00959581
2100	4	40	171.1	0.0477764	LTE	1000	0.00477764
700	4	40	161.1	0.0575774	LTE	467	0.01233800
850	4	40	161.1	0.0614807	LTE	567	0.01084954
1900	4	40	161.1	0.0503494	LTE	1000	0.00503494
850	4	40	171.1	0.0536310	UMTS	567	0.00946430
2100	4	40	171.1	0.0488908	LTE	1000	0.00488908
700	4	40	161.1	0.0575783	LTE	467	0.01233820
850	4	40	161.1	0.0606381	LTE	567	0.01070085
1900	4	40	161.1	0.0511692	LTE	1000	0.00511692
						AT&T Total:	0.127702

Table 4: AT&T Maximum MPE Power Values



Summary

All calculations performed for this analysis yielded results that were **within** the allowable limits for general population exposure to RF Emissions.

The anticipated maximum composite contributions from the AT&T facility as well as the site composite emissions value with regards to compliance with FCC's allowable limits for general population exposure to RF Emissions are shown here:

Carrier	MPE Contribution Value
AT&T:	0.127702%

Site Total:	0.127702%
Site Compliance Status:	Compliant

The anticipated composite MPE value for this site assuming all carriers present is **0.127702%** of the allowable FCC established general population limit sampled at the ground level.

FCC guidelines state that if a site is found to be out of compliance (over allowable thresholds), that carriers over a 5% contribution to the composite value will require measures to bring the site into compliance. For this facility, the composite values calculated were well within the allowable 100% threshold standard per the federal government.

Samuel Cosgrove

RF Compliance Consultant

Centerline Communications, LLC

750 West Center St. Suite 301 West Bridgewater, MA 02379

EXHIBIT 5

BUILDING OFFICE

REDDING, CONNECTICUT 06875 TEL. (203) 938-2558

CERTIFICATE OF OCCUPANCY

DATE CERTIFICATE ISSUED 1/2/5

AUTHORIZED BY: BUIL	DAMMO DI LDING OFFICIAL	DATE PERMIT	April 18, 2011				
1. PROPERTY OWNER TOWN OF REDDING (TOWN GARAGE)	OWNERS ADDR	RESS 28 Great Oa	k Lane				
2. PROJECT ADDRESS 28 Great Oak LAne	al and the second						
2A. OWNERS TEL. 203-938-2801	CONTRACTOR'S TEL.	860-877-3565					
3. PERMIT FOR Cell Tower		PROPOSED USE	Cell Tower				
4. ASSESSOR'S MAP#	LOT# P-18	_# STORIES	# DWELLING UNITS				
5. APPLICANT_SAI Communications/DavidVivian	LIC# 0901834	PHONE 41	3-218-5042				
6. ADDRESS 500 Enterprise Drive	Rocky Hill	CT	06067				
(NO.) (STREET)	(CITY)	(STATE)	(ZIP CODE)				
7. BUILDING IS TO BE FEET WIDE BY FEET LONG	AREA OR VOLUME						
8. CONSTRUCTION TYPE IBC-2003			hin fenced				
9. REMARKS Construct a 180' cell tower and equipment shelter (10' X 20') within fenced 10. (33' X 73') compound.							
11. OWNER Town of Redding (Town Gagage) 12. ADDRESS 28 Great Oak Lane Redding, CT 06896	<u> </u>	STO	ING DEPARTMENT OF REDDING JILDING DEEICIAL				

DEPT. FILE COPY



STATE OF CONNECTICUT

CONNECTICUT SITING COUNCIL

Ten Franklin Square, New Britain, CT 06051
Phone: (860) 827-2935 Fax: (860) 827-2950
E-Mail: siting.council@ct.gov
Internet: ct.gov/csc

January 24, 2011

Christopher B Fisher, Esq. Daniel M. Laub, Esq. Cuddy & Feder LLP 445 Hamilton Avenue, 14th Floor White Plains, NY 10601

RE: **DOCKET NO. 404** - New Cingular Wireless PCS, LLC application for a Certificate of Environmental Compatibility and Public Need for the construction, maintenance and operation of a telecommunications facility located at 28 Great Oak Lane, Redding, Connecticut.

Dear Attorney Fisher and Attorney Laub:

By its Decision and Order dated January 20, 2011, the Connecticut Siting Council (Council) granted a Certificate of Environmental Compatibility and Public Need (Certificate) for the construction, maintenance and operation of a telecommunications facility located at 28 Great Oak Lane, Redding, Connecticut.

Enclosed are the Council's Certificate, Findings of Fact, Opinion, and Decision and Order.

Very truly yours,

Linda Roberts
Executive Director

LR/RDM/laf

Enclosures (4)

c: Michele Briggs, AT&T



EXHIBIT 6