CC CROWN CASTLE

Crown Castle 3 Corporate Park Drive, Suite 101 Clifton Park, NY 12065

September 18, 2017

Melanie A. Bachman Acting Executive Director Connecticut Siting Council 10 Franklin Square New Britain, CT 06051

RE: Notice of Exempt Modification for Sprint/ Crown Site BU: 806953 Sprint PCS Site ID: CT03XC344 69 Guinea Road (Camp Rocky Craig), Stamford, CT 06903 Latitude: 41° 6' 6.35''/ Longitude: -73° 35' 41.45''

Dear Ms. Bachman:

Sprint currently maintains three (3) antennas at the 158-foot level of the existing 160-foot monopole tower at 69 Guinea Road (Camp Rocky Craig) in Stamford, Connecticut. The tower is owned by Crown Castle. The property is owned by the Girl Scouts of Connecticut Inc. Sprint intends to install (6) antennas and (3) RRUs, a junction box, and (3) mini-macro radios.

This facility was approved by the Connecticut Siting Council on April 2, 1998, Docket No. 180. This approval included the following conditions:

- 1. The tower shall be constructed as a monopole, no taller than necessary to provide the proposed telecommunications services and not exceed a height of 160 ft.
- 2. The Certificate Holder shall prepare a Development and Management (D&M) Plan for this site in compliance with Sections 16-50j-75 of the Regulations of CT State Agencies.
- 3. Upon the establishment of any new State or federal radio frequency standards applicable to frequencies of this facility, the facility granted herein shall be brought into compliance with such standards.
- 4. The Certificate Holder shall provide the council a recalculated report of electromagnetic radio frequency power density if and when circumstances in operation cause a change in power density above the levels originally calculated and provided in the application.
- 5. The Certificate Holder shall permit public or private entities to share space on the proposed tower for fair consideration, or shall provide any requesting entity with specific legal, technical, environmental, or economic reasons precluding such tower sharing.

Melanie A. Bachman September 18, 2017 Page 2

- 6. If the facility does not initially provide, or permanently ceases to provide cellular services following completion of construction, this Decision and Order shall be void, and the Certificate Holder shall dismantle the tower and remove all associated equipment or reapplication for any continued or new use shall be made to the Council before any such use is made.
- 7. Any antenna that becomes obsolete and ceases to function shall be removed within 60 days after such antennas become obsolete and cease to function.
- 8. Unless otherwise approved by the Council, this Decision and Order shall be void if all construction authorized herein is not completed within three years of the effective date of this Decision and Order or within three years after all appeals to this Decision and Order have been resolved.

This modification complies with the aforementioned condition(s).

Please accept this letter as notification pursuant to Regulations of Connecticut State Agencies § 16-50j-73, for construction that constitutes an exempt modification pursuant to R.C.S.A. § 16-50j-72(b)(2). In accordance with R.S.C.A. § 16-50j-73, a copy of this letter is being sent to The Honorable David Martin, Mayor of the City of Stamford, the City Principal Planner David W. Woods PhD, AICP , and to the land owner the Girl Scouts of Connecticut Inc. Crown Castle is the tower owner.

- 1. The proposed modifications will not result in an increase in the height of the existing tower.
- 2. The proposed modifications will not require the extension of the site boundary.
- 3. The proposed modification will not increase noise levels at the facility by six decibels or more, or to levels that exceed state and local criteria.
- 4. The operation of the replacement antennas will not increase radio frequency emissions at the facility to a level at or above the Federal Communication Commission safety standard.
- 5. The proposed modifications will not cause a change or alteration in the physical or environmental characteristics of the site.
- 6. The existing structure and its foundation can support the proposed loading.

For the foregoing reasons, Sprint respectfully submits that the proposed modifications to the above-reference telecommunications facility constitutes an exempt modification under R.C.S.A. § 16-50j-72(b)(2). Please send approval/rejection letter to Attn: Jeffrey Barbadora.

Melanie A. Bachman September 18, 2017 Page 3

Sincerely,


Jeffrey Barbadora Real Estate Specialist 12 Gill Street, Suite 5800, Woburn, MA 01801 781-729-0053 Jeff.Barbadora@crowncastle.com

Attachments:

- Tab 1: Exhibit-1: Compound plan and elevation depicting the planned changes
- Tab 2: Exhibit-2: Structural Modification Report
- Tab 3: Exhibit-3: General Power Density Table Report (RF Emissions Analysis Report)
- cc: The Honorable David Martin, Mayor for the City of Stamford Stamford Government Center 888 Washington Boulevard Stamford, CT 06901

David W. Woods, PhD, AICP, Principal Planner Stamford Government Center 888 Washington Boulevard 7th Floor Stamford, CT 06901

Girl Scouts of Connecticut Inc. 340 Washington Street Hartford, CT 06106



Legend

Crown Internal Sites Layer

Tower C DAS NODE DAS HUB DAS SYSTEM Land Under Alternative Crown Sites

Alternative Crown Sites

69 GUINEA ROAD

| Location | 69 GUINEA ROAD | Mblu | 002/ 6848/ / / |
|------------|----------------|----------------|-----------------------------------|
| Acct# | 002-6848 | Owner | GIRL SCOUTS OF CONNECTICUT INC |
| Assessment | \$1,003,970 | Appraisal | \$1,434,230 |
| PID | 24323 | Building Count | 1 |

Current Value

| Appraisal | | | | |
|----------------|--------------|-----------|-------------|--|
| Valuation Year | Improvements | Land | Total | |
| 2016 | \$438,650 | \$995,580 | \$1,434,230 | |
| | Assessment | | | |
| Valuation Year | Improvements | Land | Total | |
| 2016 | \$307,060 | \$696,910 | \$1,003,970 | |

Owner of Record

| Owner | GIRL SCOUTS OF CONNECTICUT INC | Sale Price | \$0 |
|----------|--------------------------------|-------------|------------|
| Co-Owner | | Book & Page | 9322/ 308 |
| Address | 340 WASHINGTON STREET | Sale Date | 04/16/2008 |
| | HARTFORD, CT 06106-3317 | Instrument | 25 |

Ownership History

| Ownership History | | | | | |
|--------------------------------|------------|-------------|------------|------------|--|
| Owner | Sale Price | Book & Page | Instrument | Sale Date | |
| GIRL SCOUTS OF CONNECTICUT INC | \$0 | 9322/ 308 | 25 | 04/16/2008 | |
| GIRL SCOUT COUNCIL SW CT INC | \$0 | 4405/ 321 | | 05/12/1995 | |
| SOUTHWESTERN CT GIRL SCT | \$0 | 1035/ 131 | 25 | 12/29/1964 | |

Building Information

Building 1 : Section 1

| Year Built: | 1963 | |
|--------------|------------|-------------|
| Living Area: | 1,960 | |
| | Building A | ttributes |
| Field | | Description |
| Style | | Ranch |
| Stories: | | 1 Story |
| Occupancy | | 1 |


Building Photo

| Exterior Wall 1 | Cement fiberbd |
|--------------------|----------------|
| Exterior Wall 2 | |
| Roof Structure: | Gable/Hip |
| Roof Cover | Asph/F Gls/Cmp |
| Interior Wall 1 | Drywall |
| Interior Wall 2 | |
| Interior Flr 1 | Hardwood |
| Interior Flr 2 | |
| Heat Fuel | Electric |
| Heat Type: | Electr Basebrd |
| АС Туре: | Central |
| Total Bedrooms: | 00 |
| Total Bthrms: | 1 |
| Total Half Baths: | 0 |
| Total Xtra Fixtrs: | 3 |
| Total Rooms: | 4 |
| Fireplace Msnry. | |
| Fpl. Gas/Prefab | 1 |
| Fpl. Outdoor | |
| Fpl. Addnl. Open | |
| Bsmt. Garage | |



(http://images.vgsi.com/photos/StamfordCTPhotos//\00\11 \94/79.jpg)

Building Layout



| Building Sub-Areas (sq ft) | | | | |
|----------------------------|----------------------|-------|----------------|--|
| Code | Description Gro | | Living Area | |
| BAS | First Floor | 1,960 | 1,960 | |
| RP2 | Porch Covered | 392 | 0 | |
| UBM | Basement, Unfinished | 1,960 | 0 | |
| WD1 | Deck, Wood | 252 | 0 | |
| | | 4,564 | 1,960 | |

Extra Features

| Extra Features | | | | Legend |
|----------------|--------------|----------|----------|--------|
| Code | Description | Size | Value | Bldg # |
| RP2 | Porch Coverd | 1056 S.F | \$26,290 | 1 |
| RP2 | Porch Coverd | 756 S.F | \$18,820 | 1 |
| RP2 | Porch Coverd | 672 S.F | \$16,730 | 1 |
| RP2 | Porch Coverd | 216 S.F | \$5,380 | 1 |
| RP2 | Porch Coverd | 176 S.F | \$4,380 | 1 |

Land

Land Use

Land Line Valuation

| Use Code | 901 | Size (Acres) | 16.86 |
|---------------|------------------|-----------------|-----------|
| Description | Exmpt Res MDL-01 | Depth | |
| Zone | RA3 | Assessed Value | \$696,910 |
| Neighborhood | 1100 | Appraised Value | \$995,580 |
| Alt Land Appr | No | | |

Outbuildings

Category

| | Outbuildings | | | | | <u>Legend</u> |
|------|----------------|----------|-----------------|----------|-----------|---------------|
| Code | Description | Sub Code | Sub Description | Size | Value | Bldg # |
| FC1 | Shed Wood | | | 240 S.F. | \$2,700 | 1 |
| MS1 | Misc Structure | | | 528 S.F. | \$3,050 | 1 |
| WD1 | Wood Deck | | | 252 S.F. | \$5,290 | 1 |
| CEL1 | Cell Tower | | | 1 SITES | \$139,880 | 1 |

Valuation History

| Appraisal | | | | | | |
|----------------|--------------|-----------|-------------|--|--|--|
| Valuation Year | Improvements | Land | Total | | | |
| 2016 | \$438,650 | \$995,580 | \$1,434,230 | | | |
| 2015 | \$438,650 | \$995,580 | \$1,434,230 | | | |
| 2014 | \$438,650 | \$995,580 | \$1,434,230 | | | |

| Assessment | | | | | |
|----------------|--------------|-----------|-------------|--|--|
| Valuation Year | Improvements | Land | Total | | |
| 2016 | \$307,060 | \$696,910 | \$1,003,970 | | |
| 2015 | \$307,060 | \$696,910 | \$1,003,970 | | |
| 2014 | \$307,060 | \$696,910 | \$1,003,970 | | |

(c) 2016 Vision Government Solutions, Inc. All rights reserved.

DOCKET NO. 180 - Cellco Partnership d/b/a Bell Atlantic MobileConnecticutapplication for a Certificate of Environmental Compatibility andSitingPublic Need for the construction, maintenance, and operation of aSitingcellular telecommunications tower and associated equipment locatedCounciland alternate one sites), or 141 Den Road (alternate two site) inCouncilStamford, Connecticut.April 2, 1998

Decision and Order

Pursuant to the foregoing Findings of Fact and Opinion, the Connecticut Siting Council (Council) finds that the effects associated with the construction, operation, and maintenance of a telecommunications tower and equipment buildings at the proposed prime site in Stamford, Connecticut, including effects on the natural environment; ecological integrity and balance; public health and safety; scenic, historic, and recreational values; forests and parks; air and water purity; and fish and wildlife are not disproportionate either alone or cumulatively with other effects when compared to need, are not in conflict with the policies of the State concerning such effects, and are not sufficient reason to deny the application and therefore directs that a Certificate of Environmental Compatibility and Public Need, as provided by General Statutes § 16-50k, be issued to Bell Atlantic Mobile (BAM) for the construction, operation, and maintenance of a telecommunications tower, associated equipment, and buildings at the proposed prime site, located within a 28-acre parcel at Guinea Road, Stamford, Connecticut. We find the effects on scenic resources and adjacent land uses of the first alternate site and second alternate site to be significant, and therefore deny certification of these sites.

The facility shall be constructed, operated, and maintained substantially as specified in the Council's record in this matter, and subject to the following conditions:

- 1. The tower shall be constructed as a monopole, no taller than necessary to provide the proposed telecommunications services, sufficient to accommodate the antennas of BAM, Springwich Cellular Limited Partnership (Springwich), Sprint PCS (Sprint), and Nextel Communications of the Mid-Atlantic, Inc. (Nextel); and such tower shall not exceed a height of 160 feet above ground level (AGL).
- 2. The Certificate Holder shall prepare a Development and Management (D&M) Plan for this site in compliance with Sections 16-50j-75 through 16-50j-77 of the Regulations of Connecticut State Agencies. The D&M Plan shall be submitted to and approved by the Council prior to the commencement of facility construction and shall include: adjustment of the tower location within the leased parcel to protect a nearby stream and minimize grade; a final site plan(s) for site development to include the location and specifications for the tower foundation, antennas, equipment buildings, emergency generator and fuel tank, security fence, access road, and utility line; construction plans for site clearing, tree trimming, water drainage, and erosion and sedimentation controls consistent with the <u>Connecticut Guidelines for Soil Erosion and Sediment Control</u>, as amended; provisions for the tower finish that may include painting; and provisions for the prevention and containment of spills and/or other discharge into surface water and ground water bodies.
- 3. Upon the establishment of any new State or federal radio frequency standards applicable to frequencies of this facility, the facility granted herein shall be brought into compliance with such standards.

. . ~ ~

۰.

.

Docket No. 180 Decision and Order Page 2

- 4. The Certificate Holder shall provide the Council a recalculated report of electromagnetic radio frequency power density if and when circumstances in operation cause a change in power density above the levels originally calculated and provided in the application.
- 5. The Certificate Holder shall permit public or private entities to share space on the proposed tower for fair consideration, or shall provide any requesting entity with specific legal, technical, environmental, or economic reasons precluding such tower sharing.
- 6. If the facility does not initially provide, or permanently ceases to provide cellular services following completion of construction, this Decision and Order shall be void, and the Certificate Holder shall dismantle the tower and remove all associated equipment or reapplication for any continued or new use shall be made to the Council before any such use is made.
- 7. Any antenna that becomes obsolete and ceases to function shall be removed within 60 days after such antennas become obsolete and cease to function.
- 8. Unless otherwise approved by the Council, this Decision and Order shall be void if all construction authorized herein is not completed within three years of the effective date of this Decision and Order or within three years after all appeals to this Decision and Order have been resolved.

Pursuant to General Statutes § 16-50p, we hereby direct that a copy of the Findings of Fact, Opinion, and Decision and Order be served on each person listed below, and notice of issuance shall be published in <u>The Hartford Courant</u> and <u>Stamford Advocate</u>.

By this Decision and Order, the Council disposes of the legal rights, duties, and privileges of each party named or admitted to the proceeding in accordance with Section 16-50j-17 of the Regulations of Connecticut State Agencies.

The parties and intervenors to this proceeding are:

APPLICANT

Bell Atlantic Mobile

ITS REPRESENTATIVE

Kenneth C. Baldwin, Esq. Brian C. S. Freeman, Esq. Robinson & Cole One Commercial Plaza Hartford, CT 06103-3597

Mr. David S. Malko, P.E. Jennifer Young Gaudet Bell Atlantic Mobile 20 Alexander Drive Wallingford, CT 06492 Docket No. 180 Decision and Order Page 3

INTERVENORS

Sprint Spectrum, L.P. d/b/a Sprint PCS

ITS REPRESENTATIVE

Elias A. Alexiades John W. Knuff Harris, Beach & Wilcox, LLP 147 North Broad Street Milford, CT 06460

Nextel Communications of the Mid-Atlantic, Inc. d/b/a Nextel Communications Christopher B. Fisher, Esq. Cuddy, Feder & Worby, Esq. 90 Maple Avenue White Plains, NY 10601

Peter J. Tyrrell, Esq. General Counsel 500 Enterprise Drive Rocky Hill, CT 06067-3900

PARTIES

Charles H. Nobs, Maurice Lucas, and Ben and Myrna Raphan

Springwich Cellular Limited Partnership

ITS REPRESENTATIVE

Jeffrey J. Mirman, Esq. Levy & Droney, P.C. P.O. Box 887 Farmington, CT 06034

Evening dock at A 18044 + 400

CERTIFICATION

The undersigned members of the Connecticut Siting Council (Council) hereby certify that they have heard this case, or read the record thereof, in Docket No. 180 - an application of Cellco Partnership d/b/a Bell Atlantic Mobile for a Certificate of Environmental Compatibility and Public Need for the construction, maintenance, and operation of a telecommunications tower and associated equipment located immediately north of the Merritt Parkway off Guinea Road (prime and alternate one sites) or 141 Den Road (alternate two site) in Stamford, Connecticut, and voted as follows to approve the proposed prime site and deny the first and second alternate sites:

Council Members

Mortimer A. Gelston, Chairman

Commissioner Donald W. Downes Designee: Gerald J. Neffernan

Commissioner Arthur J. Rocque, Jr. Designee: Brian J. Emerick

Albert E. Gary

Pamela B. Katz Daniel P. Lynch, Jr. illfam H. Smith

Colin C. Tait

Abstain

Absent

Edward S. Wilensky

Dated at New Britain, Connecticut April 2, 1998.

Vote Cast

Yes

Yes

Yes

Absent

No

Yes

Yes

STATE OF CONNECTICUT

ss. New Britain, Connecticut

COUNTY OF HARTFORD

I hereby certify that the foregoing is a true and correct copy of the Findings of Fact, Opinion, and Decision and Order issued by the Connecticut Siting Council, State of Connecticut.

)

:

)

ATTEST:


Joel M. Rinebold

Executive Director Connecticut Siting Council

I certify that a copy of the Findings of Fact, Opinion, and Decision and Order in Docket No. 180 have been forwarded by Certified First Class Return Receipt Requested mail on April 6, 1998, to all parties and intervenors of record as listed on the attached service list, dated December 10, 1997.

ATTEST;

Sharon L. Gdovin Secretary II Connecticut Siting Council



PROJECT:2.5 MM OVERLAY ON NSITE NAME:MERRIT 4 - ROXBURY (SITE CASCADE:CT03XC344CROWN BUN:806953SITE ADDRESS:69 GUINEA ROAD
STAMFORD, CT 06903SITE TYPE:MONOPOLE TOWERMARKET:SOUTHERN CONNECTION

SITE INFORMATION

TOWER OWNER: CROWN ATLANTIC COMPANY LLC 2000 CORPORATE DRIVE CANNONSBURG, PA 15317 (704) 405-6555

PROJECT MANAGER: TRICIA PELON (781) 970-0067

LATITUDE (NAD83): 41' 6' 6.48" N


LONGITUDE (NAD83): 73' 35' 39.84" W

COUNTY: FAIRFIELD

ZONING DISTRICT:

POWER COMPANY: EVERSOURCE (800) 286-2000

SPRINT CM: NICHOLAS WLEKLINSKI



| NETWORK VISIO (CROWN) | N | PLANS PREPARED FOR: Sprint 3 Enterprise Drive Albany, New York 12204 MLA PARTNER: |
|--------------------------|-----|--|
| | | CC CROWN CASTLE |
| | | INFINIGY INSTITUTE I |
| CUT | | JOB NUMBER 353-000 |
| | | OF CONNE |
| NG INDEX | | STELLS STEL |
| ET TITLE | REV | |
| | | K BBB |
| | 0 | Kon Kan Koens |
| | 0 | No. 24705 |
| E PLAN | 0 | CENSE |
| BLE PLAN | 0 | NONAL ENTIT |
| AT PLAN | 0 | in the second |
| | 0 | DRAWING NOTICE: |
| | 0 | |
| | 0 | THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF SPRINT AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPRINT. |
| | | REVISIONS: DESCRIPTION DATE BY REV |
| | | DESCRIPTION DATE BY REV |
| | | |
| | | |
| | | ISSUED FOR PERMIT 9/1/17 JUN 0 |
| | | |
| | - | SITE NAME: |
| | | MERIT 4 - ROXBURY (CROWN) |
| | | SITE CASCADE: |
| | | CT03XC344 |
| | | SITE ADDRESS: |
| | | 69 GUINEA ROAD |
| | | 69 GUINEA ROAD STAMFORD, CT 06903 |
| | - | |
| | | STAMFORD, CT 06903 |
| | | STAMFORD, CT 06903 |
| | | STAMFORD, CT 06903 |

SPRINT CONSTRUCTION SPECIFICATIONS MINI-MACRO CELL SITES REV. 0 7/25/16

1) BASIC REQUIREMENTS

a) MEET ALL REQUIREMENTS OF JURISDICTIONS.

b) IF EQUIPMENT FURNISHED BY COMPANY DOES NOT MATCH THE EQUIPMENT LISTED ON THE RFDS AND SHOWN ON THE PERMITTING DRAWINGS, RESOLVE DISCREPANCY THROUGH INSTALLER'S CONSTRUCTION MANAGER AND COMPANY'S POINT OF CONTACT.

c) CABLE INSTALLATIONS

I) ALL CABLES MUST BE OUTDOOR RATED AND HAVE UV RESISTANT OUTER JACKETS.

II) CABLE BENDS MUST NOT EXCEED MANUFACTURER'S ALLOWABLE CABLE BEND RADII.

III) AT RADIOS INSTALL SERVICE LOOPS FOR POWER, FIBER AND ETHERNET SECURED AT LEAST TWICE AT 180 TO THE STRUCTURE.

IV) SPARE FIBERS MUST BE ENCASED IN A LOW PROFILE WEATHERTIGHT ASSEMBLY

d) FIBERS MUST BE FIELD-TERMINATED WITH LC-TYPE CONNECTORS.

e) CONDUITS IN EARTH: PROVIDE PVC. CONDUITS EXPOSED AND IN FACILITIES: PROVIDE RGS. HAND DIG TRENCHES IN COMPOUNDS.

f) SECURE AND SUPPORT CONDUITS AND CABLES ON NO MORE THAN 48" INTERVALS.

g) on tower sites RGS conduits may be surface mounted away from Walkways and access/Egress Paths. IF installations in Walkways and access/Egress Paths cannot be avoided, identify the conduit envelope / TRIP hazard by alternating yellow and black stripes painted on concrete and conduit.

2)SPRINT-FURNISHED EQUIPMENT

a) INSTALL THE FOLLOWING EQUIPMENT AT LOCATIONS AND AZIMUTHS SHOWN ON THE CONSTRUCTION DRAWINGS.

i) PANEL ANTENNAS

II) RADIOS

III) GPS ANTENNAS

Iv) FILTERS

v) 120 VOLT DIN-RAIL CIRCUIT BREAKER ASSEMBLY

3) TOWER INSTALLATIONS

a) MEET ALL REQUIREMENTS OF THE TOWER OWNER.

b) INSTALL CORRUGATED FLEXIBLE CONDUIT UP THE TOWER TO COMPANY'S RAD CENTER.

c) PROVIDE HANGING GRIPS OR CONDUIT CLAMPS AND ENSURE CONDUITS AS WELL AS INNER CABLES ARE SUPPORTED.

d) CONDUIT RISERS: AT TOP OF TOWER TURN CONDUIT DOWN AND PROVIDE CABLE TERMINATION FITTINGS. EXTEND CABLES TO RADIOS EXPOSED AND SECURED TO STRUCTURE. AT CONDUIT EXIT FROM TOWER, PROVIDE DRIP LOOPS AND WEEP HOLES.

e) AT ICE BRIDGE RUN CABLES IN RGS CONDUIT. UTILIZE CONDULETS TO MAKE COMPACT 90 DEGREE TURNS.

4) AC POWER TIE-IN

a) INSTALL SPRINT'S 120 VOLT DIN-RAIL CIRCUIT BREAKER ASSEMBLY IN THE EXISTING POWER PROTECTION CABINET TELCO SECTION.

b) INSTALL A 20 AMPERE MOLDED CASE CIRCUIT BREAKER IN AVAILABLE SPACE IN THE ADJACENT PPC POWER SECTION LOAD CENTER.

5) GROUNDING

a) 120 VOLT CIRCUITS: POWER CABLES MUST BE 3-WIRE WITH EQUIPMENT GROUNDING CONDUCTOR.

b) SUPPLEMENTAL GROUNDING: ALL GROUNDING HARDWARE MUST BE UL STAMPED AS SUITABLE FOR GROUNDING HARDWARE.

C) RADIOS: BOND RADIO TO THE TOWER TOP OR SECTOR GROUND BAR WITH #8 BARE TINNED COPPER WIRE (GREEN INSULATED ON ROOFTOPS).

d) DIN-RAIL CIRCUIT BREAKER ASSEMBLY: BOND SURGE ARRESTOR TO PPC TELCO BOARD GROUND BAR.

6)MINOR MATERIALS

a) CONDUIT

i) RIGID GALVANIZED STEEL CONDUIT (RGS): UL LISTED, COMPLIANT WITH ANSI STANDARD C80, HOT-DIP GALVANIZED, WITH THREADED FITTINGS. MANUFACTURERS: ALLIED, REPUBLIC, WHEATLAND, OR EQUAL.

ii) CORRUGATED FLEXIBLE CONDUIT: DURALINE OR EQUAL.

III) LIQUID-TIGHT FLEXIBLE METALLIC CONDUIT (LFMC): UL LABELED, UV RESISTANT, FLAME RETARDANT PVC JACKET, HOT-DIP GALVANIZED, GREY. MANUFACTURERS: AFC, ANACONDA, SOUTHWIRE OR EQUAL.

IV) PVC CONDUIT: SCHEDULE 40. CARLON OR EQUAL.

v) CABINET HUBS AND CABLE TERMINATION FITTINGS: OZ GEDNEY OR ROXTEC

b) COAXIAL CABLE JUMPERS: 1/2" LDF-4. MANUFACTURERS: COMMSCOPE, RFS OR FCT.

c) FASTENERS AND HARDWARE

I) TO SECURE RACEWAYS, UTILIZE NON CORRODING NON-MAGNETIC METALLIC FASTENERS AND HARDW.

d) POWER CABLES - 3/C @12 SOOW BY SOUTHWIRE OR EQUAL

e) ETHERNET CABLES AND CONNECTORS: OUTDOOR RATED, CAT 5E, BELDEN OR EQUAL.

f) FIBER CABLES: CORNING 'FREEDOM FAN OUT" OUTDOOR RISER CABLE, 4F, SINGLE MODE, OR EQUA

g) RF TRANSPARENT PAINT FOR ANTENNA CONCEALMENT: SELECT NO/LOW CARBON PAINTS, WITH NO SUSPENDED METAL PARTICLES (ALUMINUM, ZINC, COPPER, ETC.)

7)COLOR CODING

a) COLOR CODE CABLES AND CONDUITS AS REQUIRED BY SPRINT STANDARD TS-0200.

8) TESTING AND CONSTRUCTION COMPLETE


a) SWEEP ALL COAXIAL CABLES ACCORDING TO SPRINT STANDARD TS-0200.


b) PANEL ANTENNA ALIGNMENT - USING ELECTRONIC ALIGNMENT TOOL. AZIMUTH/DOWNTILT +/- 1


c) LEAVE EQUIPMENT DE-ENERGIZED UNTIL INSTRUCTED BY THE COMMISSIONING AND INTEGRATION TEAM

d) OTHER REQUIREMENTS AND DELIVERABLES MAY BE REQUIRED BEFORE THE CONSTRUCTION COMPLETE SITERRA (SPRINT'S DATABASE-OF-RECORD).


| | PLANS PREPARED FOR: | | | | |
|--|--|------------|--|--|--|
| ARE SUITABLE FOR THE PURPOSE. | Sprint 3 Enterprise Drive Albany, New York 12200 | 4 | | | |
| IL /Low Titanium dioxide, and without | | WN TLE | | | |
| DEGREE. M TO ENERGIZE, MILESTONE CAN BE ACTUALIZED IN | PLANS PREPARED BY: INFING 1033 Watervliet Shaker R Albany, NY 12205 Office # (518) 680-0790 Fax # (518) 690-0793 JOB NUMBER 353-000 | | | | |
| | ENGINEERING LICENSE: | | | | |
| * | DRAWING NOTICE: THESE DOCUMENTS ARE CONFIDENTI THE SOLE PROPERTY OF SPRINT AND N REPRODUCED, DISSEMINATED OR RED WITHOUT THE EXPRESS WRITTEN CO SPRINT. | VAY NOT BE | | | |
| | REVISIONS: DESCRIPTION DAT | E BY REV | | | |
| | | | | | |
| | ISSUED FOR PERMIT 9/1/17 | JLM D | | | |
| а 1910 — 1910 — 1910 — 1910 — 1910 — 1910 — 1910 — 1910 — 1910 — 1910 — 1910 — 1910 — 1910 — 1910 — 1910 — 1910 — | MERIT 4 - ROXBU (CROWN) | JRY | | | |
| | SITE CASCADE CT03XC344 | | | | |
| | SITE ADDRESS: 69 GUINEA ROAD STAMFORD, CT 0690 SHEET DESCRIPTION: | 03 | | | |
| | SPRINT SPECIFICATION | S | | | |
| SCALE: AS NOTED 1 | - SHEET NUMBER: | - | | | |
| | | | | | |










| 1" RGS (GROUND)/CORRUGATED (TOWER) 1" CORRUGATED PVC CONDUIT SOOW CABLE | PLANS PREPARED FOR: Sprint 3 Enterprise Drive Albany, New York 12204 MLA PARTNER: |
|---|--|
| | CC CROWN CASTLE |
| | PLANS PREPARED BY: INFINICY & 1033 Watervliet Shaker Rd Albany, NY 12205 Office # (518) 690-0790 Fax # (518) 690-0793 JOB NUMBER 353-000 |
| 5 | ENGINEERING LICENSE: |
| | DRAWING NOTICE: THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF SPRINT AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPRINT. REVISIONS: DESCRIPTION DATE BY REV |
| | ISSUED FOR PERMIT SITE NAME: MERIT 4 - ROXBURY |
| | CT03XC344 |
| | SITE ADDRESS: 69 GUINEA ROAD STAMFORD, CT 06903 SHEET DESCRIPTION: |
| L | TOWER ELEVATION & CABLE PLAN |
| SCALE: NTS 1 | A-2 |








| <u>19</u> | | PLANS PREPARED FOR: |
|-----------|-----|---|
| | | Sprint ³ Enterprise Drive Albany, New York 12204 MLA PARTNER: CCC CROWN |
| | | PLANS PREPARED BY: INFINICY & State of the |
| NO SCALE | 1 | No. 24705 |
| | | DRAWING NOTICE: THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF SPRINT AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPRINT. REVISIONS: |
| | | DESCRIPTION DATE BY REV |
| | | |
| | | ISSUED FOR PERMIT 9/1/17 JLM 0 |
| | | SITE NAME: |
| | | MERIT 4 - ROXBURY (CROWN) |
| | | CT03XC344 |
| | | SHEET DESCRIPTION: |
| | | |
| NO SCALE | 2 | A-5 |
| | الت | |



NOKIA MM SYSTEM WIRING DIAGRAM


NOTE: 1. AC POWER GROUND LEVEL NOTES AND NOKIA MM SYSTEM WIRING DIAGRAM REFERENCED FROM DOCUMENT ENTITLED "MINI-MACRO ON NV MACRO SITE INSTALLATION MOP" DATED NOVEMBER 2, 2016, PAGES 11-12 AND 14, RESPECTIVELY.



THE PREFERRED AC POWER CONNECTION TO THE DIN RAIL ASSEMBLY IS HARD WIRED FROM A DEDICATED 20A PANEL BREAKER TO THE DIN RAIL (DIN RAIL MUST BE IN AN ENCLOSURE) HOWEVER IF THE PROVIDED POWER CORD IS CHOSEN THE DIN RAIL ASSEMBLY RECEPTACLE MUST NOT BE GFCI AS THEY WILL TRIP, REPLACE WITH STANDARD RECEPTACLE AS REQUIRED. WHEN USING THE SUPPLIED POWER PLUG, THE CORD AND OUTLET MUST BE LABELED "DO NOT DISCONNECT" AND "DO NOT UNPLUG" IF PPC TELCO SECTION IS LESS THAN 50' FROM TOWER AND THE CONDUIT RUN IS 100% ABOVEGROUND INSTALL 9 OR 10/C SOOW IN 1.5" RGS (EXPOSED) ON ICE BRIDGE, SOOW EXPOSED UP THROUGH TOWER TO TERMINAL BOX AT THE RAD CENTER. IF PPC TELCO SECTION IS MORE THAN 50' FROM TOWER, OR THE CONDUIT RUN AT ANY POINT IS UNDERGROUND ROUTE 1.5" RGS (EXPOSED) OR PCC (UNDERGROUND) WITH 9 EA. THHN/THWN CONDUCTORS. INSTALL A TERMINAL BOX WITH TERMINAL BLOCK ON ICE BRIDGE NEAREST TOWER AND TRANISTION TO SOOW. AT TELCO SECTION INDIVIDUAL CONDUCTORS ROUTE ACROSS PLYWOOD BACKBOARD TO THE DIN RAIL CIRCUIT BREAKER ASSEMBLY. SOME JURISDICTIONS MAY NOT ALLOW INDIVIDUAL CONDUCTORS TO ROUTE ACROSS BACKBOARD THEREFORE INSTALL ANOTHER TERMINAL BOX INSIDE OR OUTSIDE AND TRANSITION BACK TO SOW.

AC POWER GROUND LEVEL:

POWER CIRCUITS/CABLES MUST BE 3 WIRE EQUIPMENT GROUNDING CONDUCTOR. SUPPLEMENTAL GROUNDING HARDWARE MUST BE UL STAMPED AS SUITABLE FOR GROUNDING HARDWARE.



NO SCALE



Date: July 11, 2017

Cheryl Schultz Crown Castle 3530 Toringdon Way, Suite 300 Charlotte, NC 28277

Paul J. Ford and Company 250 E. Broad Street, Suite 600 Columbus, OH 43215 mscroggy@pjfweb.com

Subject: Structural Analysis Report

| Carrier Designation: | Sprint PCS Co-Locate | |
|-------------------------------|---|---------------------|
| | Carrier Site Number: | CT03XC344 |
| | Carrier Site Name: | CT03XC344 |
| Crown Castle Designation: | Crown Castle BU Number: | 806953 |
| - | Crown Castle Site Name: | BRG 2044 (A) 943097 |
| , | Crown Castle JDE Job Number: | 443988 |
| | Crown Castle Work Order Number: | 1418980 |
| | Crown Castle Application Number: | 394844 Rev. 3 |
| Engineering Firm Designation: | Paul J. Ford and Company Project Number: | 37517-0206.002.7805 |
| Site Data: | 69 Guinea RD(Camp Rocky Craig), Stamford Latitude <i>41° 6' 6.35"</i> , Longitude -73° 35' 41.4 160 Foot - Monopole Tower | |
| Deen Ohemil Celuiter | • | |

Dear Cheryl Schultz,

Paul J. Ford and Company is pleased to submit this **"Structural Analysis Report"** to determine the structural integrity of the above mentioned tower. This analysis has been performed in accordance with the Crown Castle Structural 'Statement of Work' and the terms of Crown Castle Purchase Order Number 1047734, in accordance with application 394844, revision 3.

The purpose of the analysis is to determine acceptability of the tower stress level. Based on our analysis we have determined the tower stress level for the structure and foundation, under the following load case, to be:

LC7: Existing + Reserved + Proposed Equipment Note: See Table I and Table II for the proposed and existing/reserved loading, respectively. Sufficient Capacity

JUL 1 2 2017

This analysis has been performed in accordance with the 2016 Connecticut State Building Code based upon an ultimate 3-second gust wind speed of 120 mph converted to a nominal 3-second gust wind speed of 93 mph per Section 1609.3 and Appendix N as required for use in the ANSI/TIA-222-G-2005 Standard, "Structural Standard for Antenna Supporting Structures and Antennas", with ANSI/TIA-222-G-1-2007 and ANSI/TIA-222-G-2-2009 Addenda per Exception #5 of Section 1609.1.1. Risk Category II, Exposure Category B and Topographic Category 1 with a maximum Topographic Factor, Kzt, of 1.0 were used in this analysis.

We at *Paul J. Ford and Company* appreciate the opportunity of providing our continuing professional services to you and Crown Castle. If you have any questions or need further assistance on this or any other projects please give us a call.

Respectfully submitted by:

INAN

Morgan Scroggy, P.E. Project Engineer



Date: July 11, 2017

Cheryl Schultz Crown Castle 3530 Toringdon Way, Suite 300 Charlotte, NC 28277 Paul J. Ford and Company 250 E. Broad Street, Suite 600 Columbus, OH 43215 mscroggy@pjfweb.com

Subject: Structural Analysis Report

| Carrier Designation: | Sprint PCS Co-Locate | |
|-------------------------------|--|---------------------|
| | Carrier Site Number: | CT03XC344 |
| | Carrier Site Name: | CT03XC344 |
| Crown Castle Designation: | Crown Castle BU Number: | 806953 |
| - | Crown Castle Site Name: | BRG 2044 (A) 943097 |
| | Crown Castle JDE Job Number: | 443988 |
| | Crown Castle Work Order Number: | 1418980 |
| | Crown Castle Application Number: | 394844 Rev. 3 |
| Engineering Firm Designation: | Paul J. Ford and Company Project Number: | 37517-0206.002.7805 |
| Site Data: | 69 Guinea RD(Camp Rocky Craig), Stamford Latitude <i>41° 6' 6.35''</i> , Longitude -73° 35' 41.4 160 Foot - Monopole Tower | |
| Dear Charyl Schultz | | |

Dear Cheryl Schultz,

Paul J. Ford and Company is pleased to submit this **"Structural Analysis Report"** to determine the structural integrity of the above mentioned tower. This analysis has been performed in accordance with the Crown Castle Structural 'Statement of Work' and the terms of Crown Castle Purchase Order Number 1047734, in accordance with application 394844, revision 3.

The purpose of the analysis is to determine acceptability of the tower stress level. Based on our analysis we have determined the tower stress level for the structure and foundation, under the following load case, to be:

LC7: Existing + Reserved + Proposed Equipment Note: See Table I and Table II for the proposed and existing/reserved loading, respectively.

Sufficient Capacity

This analysis has been performed in accordance with the 2016 Connecticut State Building Code based upon an ultimate 3-second gust wind speed of 120 mph converted to a nominal 3-second gust wind speed of 93 mph per Section 1609.3 and Appendix N as required for use in the ANSI/TIA-222-G-2005 Standard, "Structural Standard for Antenna Supporting Structures and Antennas", with ANSI/TIA-222-G-1-2007 and ANSI/TIA-222-G-2-2009 Addenda per Exception #5 of Section 1609.1.1. Risk Category II, Exposure Category B and Topographic Category 1 with a maximum Topographic Factor, Kzt, of 1.0 were used in this analysis.

We at *Paul J. Ford and Company* appreciate the opportunity of providing our continuing professional services to you and Crown Castle. If you have any questions or need further assistance on this or any other projects please give us a call.

Respectfully submitted by:

Morgan Scroggy, P.E. Project Engineer

TABLE OF CONTENTS

1) INTRODUCTION

2) ANALYSIS CRITERIA

- Table 1 Proposed Antenna and Cable Information
- Table 2 Existing and Reserved Antenna and Cable Information
- Table 3 Design Antenna and Cable Information

3) ANALYSIS PROCEDURE

Table 4 - Documents Provided

- 3.1) Analysis Method
- 3.2) Assumptions

4) ANALYSIS RESULTS

Table 5 - Section Capacity (Summary) Table 6 – Tower Components vs. Capacity 4.1) Recommendations

5) APPENDIX A

tnxTower Output

6) APPENDIX B

Base Level Drawing

7) APPENDIX C

Additional Calculations

1) INTRODUCTION

This tower is a 160 ft Monopole tower designed by VALMONT in August of 1999. The tower was originally designed for a wind speed of 85 mph per TIA/EIA-222-F.

2) ANALYSIS CRITERIA

This analysis has been performed in accordance with the 2016 Connecticut State Building Code based upon an ultimate 3-second gust wind speed of 120 mph converted to a nominal 3-second gust wind speed of 93 mph per Section 1609.3 and Appendix N as required for use in the ANSI/TIA-222-G-2005 Standard, "Structural Standard for Antenna Supporting Structures and Antennas", with ANSI/TIA-222-G-1-2007 and ANSI/TIA-222-G-2-2009 Addenda per Exception #5 of Section 1609.1.1. Risk Category II, Exposure Category B and Topographic Category 1 with a maximum Topographic Factor, Kzt, of 1.0 were used in this analysis.

| Mounting Level (ft) | Center Line Elevation (ft) | Number of Antennas | Antenna Manufacturer | | Number of Feed Lines | IINA | |
|------------------------|-------------------------------------|--------------------------|--------------------------------|---------------------------|----------------------------|---------------------|---|
| | | 3 | alcatel lucent | TD-RRH8x20-25 | | | |
| | | 3 | argus technologies | LLPX310R-V1 w/ Mount Pipe | 1 | | |
| 157.0 | 158.0 | 158.0 1 | box enclosures and assembly | BEN-92P | | 1/8 17/64 5/8 | - |
| | | 3 | nokia | FWHR | 1 | 7/8 | |
| | | 3 | rfs celwave | APXVTM14-ALU-I20 w/ Pipe | _ | | |
| | 157.0 | 1 | - | L3"x3"x1/4" Bracing | | | |
| 40.0 | 40.0 | - | - | - | 1 | 1/2 | - |

Table 1 - Proposed Antenna and Cable Information

| Mounting Level (ft) | Center Line Elevation (ft) | Number of Antennas | Antenna Manufacturer | Antenna Model | Number of Feed Lines | Feed Line Size (in) | Note |
|------------------------|-------------------------------------|--------------------------|-------------------------|------------------------------|----------------------------|------------------------------|------|
| | 158.0 | 3 | rfs celwave | APXVSPP18-C-A20 w/ Pipe | | | |
| 157.0 | 157.0 | 9 | rfs celwave | ACU-A20-N | 3 | 1-1/4 | 1 |
| | 157.0 | 1 | tower mounts | Platform Mount [LP 602-1] | | | |
| | 155.0 | 3 | alcatel lucent | 800 EXTERNAL NOTCH FILTER | _ | - | 1 |
| 154.0 | 155.0 | 3 | alcatel lucent | 800MHZ RRH | | | |
| 154.0 | 153.0 | 3 | alcatel lucent | 1900MHz RRH (65MHz) | - | | ' |
| | 154.0 | 2 | tower mounts | Pipe Mount [PM 601-3] | | | |
| | | 3 | cci antennas | HPA-65R-BUU-H6 w/ Mount Pipe | - | - | |
| | | 3 | ericsson | RRUS 12 B2/RRUS A2 | | | 2 |
| | | 3 | | 1001983 | | | |
| | 151.0 | 6 | powerwave | 7770.00 w/ Mount Pipe | | | |
| 149.0 | 151.0 | 6 | technologies | LGP21401 | _ | | |
| | | 6 | | LGP21901 | 1 2 | 3/8 5/8 | 1 |
| | | 3 | ericsson | RRUS-11 | 12 | 5/6 1-5/8 | |
| | | 1 | raycap | DC6-48-60-18-8F | | , . | |
| | 149.0 | 1 | tower mounts | Platform Mount [LP 602-1] | | | |

| Mounting Level (ft) | Center Line Elevation (ft) | Number of Antennas | Antenna Manufacturer | Antenna Model | Number of Feed Lines | Feed Line Size (in) | Note | | |
|------------------------|-------------------------------------|---------------------------|---------------------------|--|----------------------------|--|------|--|--|
| | | 3 | alcatel lucent | RRH2X40-AWS | | | | | |
| | | 6 | andrew | DB846F65ZAXY w/ Mount Pipe | | | | | |
| | 140.0 | 3 | powerwave technologies | P65.16.XL.2 w/ Mount Pipe | 1 | 1/2 | | | |
| 139.0 | 142.0 | 1 | rfs celwave | DB-T1-6Z-8AB-0Z | 1 | 1-1/4 | 1 | | |
| | | 6 | rfs celwave | FD9R6004/2C-3L | 12 | 1-5/8 | | | |
| | | 3 | rymsa wireless | MG D3-800TV w/ Mount Pipe | _ | | | | |
| | | 3 | rymsa wireless | MG D3-800Tx w/ Mount Pipe | | | | | |
| | 139.0 | 1 | tower mounts | Platform Mount [LP 602-1] | | | | | |
| | 118.0 | 3 | commscope | LNX-6515DS-VTM w/ Mount Pipe | | | | | |
| | | | | 3 | ericsson | ERICSSON AIR 21 B2A B4P w/ Mount Pipe | - | | |
| 116.0 | | 3 | ericsson | ERICSSON AIR 21 B4A B2P w/ Mount Pipe | 1 12 | 1-1/4 1-5/8 | 1 | | |
| | | 3 | ericsson | KRY 112 144/1 | - | | | | |
| | | 3 | ericsson | RRUS 11 B12 | | | | | |
| | 116.0 | 1 | tower mounts | Platform Mount [LP 713-1] | | | | | |
| 94.0 | 94.0 | 1 | gps | GPS_A | | | 4 | | |
| 04.0 | 84.0 84.0 | | tower mounts | Side Arm Mount [SO 701-1] | - | - | 1 | | |
| 45.0 | 45.0 | 1 | tower mounts | Pipe Mount [PM 601-1] | | | 1 | | |
| 43.0 | 45.0 | 45.0 1 trimble BULLET III | | BULLET III | - | | | | |
| 40.0 | 40.0 | 1 | andrew | GPS-QBW-20N | | | 1 | | |
| 40.0 | 40.0 | 1 | tower mounts | Pipe Mount [PM 601-1] | - | - | | | |

Notes:

1) 2) 3)

Existing Equipment Reserved Equipment Equipment to be Removed, Not Considered in this SA

 Table 3 - Design Antenna and Cable Information

| Mounting Level (ft) | Line | Number of Antennas | Antenna Manufacturer | | Number of Feed Lines | Feed Line Size (in) |
|------------------------|------|--------------------------|-------------------------|---|----------------------------|---------------------------|
| - | - | - | - | - | - | - |

3) ANALYSIS PROCEDURE

Table 4 - Documents Provided

| Document | Remarks | Reference | Source |
|---|----------------------------|-----------|--------------|
| 4-GEOTECHNICAL REPORTS | FDH, 15BRBK1600, 6/15/2015 | 5749621 | CCISITES |
| 4-TOWER FOUNDATION DRAWINGS/DESIGN/SPECS | Towerkraft, 2622, 7/30/98 | 1104113 | CCISITES |
| 4-TOWER MANUFACTURER DRAWINGS | Valmont, 18917-69, 8/5/99 | 823122 | CCISITES |
| 4-POST-MODIFICATION INSPECTION | TEP, 1210025, 8/10/2013 | 4015064 | CCISITES |
| 4-POST-MODIFICATION INSPECTION | SGS, 140526, 8/13/2014 | 5577141 | CCISITES |
| 4-TOWER REINFORCEMENT DESIGN/DRAWINGS/DATA | PJF, 41705-162, 8/30/2009 | 1251715 | CCISITES |
| Mount Analysis | Infinigy, 7/5/2017 | - | Crown Castle |

3.1) Analysis Method

tnxTower (version 7.0.5.1), a commercially available analysis software package, was used to create a three-dimensional model of the tower and calculate member stresses for various loading cases. Selected output from the analysis is included in Appendix A.

3.2) Assumptions

- 1) Monopole was fabricated and installed in accordance with the manufacturer's specifications.
- 2) Monopole has been properly maintained in accordance with manufacturer's specifications.
- 3) The configuration of antennas, transmission cables, mounts and other appurtenances are as specified in Tables 1 and 2 and the referenced drawings.
- 4) Monopole was modified in conformance with the referenced modification drawings.
- 5) The existing monopole shaft has been reinforced using a Crown-approved system in accordance with the above referenced documents. However, in this analysis we found that the existing pole shaft without modifications has adequate capacity according to TIA-222-G-2 (addendum 2) and therefore, we did not consider the existing reinforcing elements in the strength calculations.

This analysis may be affected if any assumptions are not valid or have been made in error. Paul J. Ford and Company should be notified to determine the effect on the structural integrity of the tower.

4) ANALYSIS RESULTS

| Section No. | Elevation (ft) | Component Type | Size | Critical Element | Р (К) | SF*P_allow (K) | % Capacity | Pass / Fail |
|----------------|-------------------|-------------------|-------------------------|---------------------|--------|-------------------|---------------|-------------|
| L1 | 160 - 111.33 | Pole | TP31.29x19.6x0.25 | 1 | -12.51 | 1568.58 | 64.5 | Pass |
| L2 | 111.33 - 73.25 | Pole | TP39.912x29.6683x0.3438 | 2 | -23.42 | 2848.48 | 71.0 | Pass |
| L3 | 73.25 - 36.33 | Pole | TP48.088x37.8467x0.4063 | 3 | -34.66 | 4024.95 | 70.2 | Pass |
| L4 | 36.33 - 0 | Pole | TP56x45.6746x0.4375 | 4 | -51.53 | 4947.02 | 73.8 | Pass |
| | | | | | | | Summary | |
| | | | | | | Pole (L4) | 73.8 | Pass |
| | | | | | | RATING = | 73.8 | Pass |

Table 5 - Section Capacity (Summary)

Table 6 - Tower Component Stresses vs. Capacity

| Notes | Component | Elevation (ft) | % Capacity | Pass / Fail | |
|-------|----------------------------------|-------------------|------------|-------------|--|
| 1 | Anchor Rods | 0 | 60.7 | Pass | |
| 1 | Base Plate | 0 | 53.2 | Pass | |
| 1 | Base Foundation – Steel | 0 | 59.0 | Pass | |
| 1 | Base Foundation Soil Interaction | 0 | 66.0 | Pass | |

| Structure Rating (max from all components) = | 73.8% |
|--|-------|
|--|-------|

Notes:

1) See additional documentation in "Appendix C – Additional Calculations" for calculations supporting the % capacity consumed.

4.1) Recommendations

The monopole and its foundation have sufficient capacity to carry the proposed loading configuration. No modifications are required at this time.



RADIO FREQUENCY EMISSIONS ANALYSIS REPORT EVALUATION OF HUMAN EXPOSURE POTENTIAL TO NON-IONIZING EMISSIONS

SPRINT Existing Facility

Site ID: CT03XC344

Merrit 4 - Roxbury (Crown) 69 Guinea Road Stamford, CT 06903

August 21, 2017

EBI Project Number: 6217003717

| Site Compliance Summary | | | | | | |
|-------------------------|-----------|--|--|--|--|--|
| Compliance Status: | COMPLIANT | | | | | |
| Site total MPE% of | | | | | | |
| FCC general | 10.82 % | | | | | |
| population | 10.02 70 | | | | | |
| allowable limit: | | | | | | |



August 21, 2017

SPRINT Attn: RF Engineering Manager 1 International Boulevard, Suite 800 Mahwah, NJ 07495

Emissions Analysis for Site: CT03XC344 - Merrit 4 - Roxbury (Crown)

EBI Consulting was directed to analyze the proposed SPRINT facility located at **69 Guinea Road**, **Stamford**, **CT**, for the purpose of determining whether the emissions from the Proposed SPRINT Antenna Installation located on this property are within specified federal limits.

All information used in this report was analyzed as a percentage of current Maximum Permissible Exposure (% MPE) as listed in the FCC OET Bulletin 65 Edition 97-01and ANSI/IEEE Std C95.1. The FCC regulates Maximum Permissible Exposure in units of microwatts per square centimeter (μ W/cm2). The number of μ W/cm² calculated at each sample point is called the power density. The exposure limit for power density varies depending upon the frequencies being utilized. Wireless Carriers and Paging Services use different frequency bands each with different exposure limits, therefore it is necessary to report results and limits in terms of percent MPE rather than power density.

All results were compared to the FCC (Federal Communications Commission) radio frequency exposure rules, 47 CFR 1.1307(b)(1) - (b)(3), to determine compliance with the Maximum Permissible Exposure (MPE) limits for General Population/Uncontrolled environments as defined below.

<u>General population/uncontrolled exposure</u> limits apply to situations in which the general population may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Therefore, members of the general population would always be considered under this category when exposure is not employment related, for example, in the case of a telecommunications tower that exposes persons in a nearby residential area.

Population exposure to radio frequencies is regulated and enforced in units of microwatts per square centimeter (μ W/cm²). The general population exposure limits for the 850 MHz Band is approximately 567 μ W/cm². The general population exposure limit for the 1900 MHz (PCS) and 2500 MHz (BRS) bands is 1000 μ W/cm². Because each carrier will be using different frequency bands, and each frequency band has different exposure limits, it is necessary to report percent of MPE rather than power density.



<u>Occupational/controlled exposure</u> limits apply to situations in which persons are exposed as a consequence of their employment and in which those persons who are exposed have been made fully aware of the potential for exposure and can exercise control over their exposure. Occupational/controlled exposure limits also apply where exposure is of a transient nature as a result of incidental passage through a location where exposure levels may be above general population/uncontrolled limits (see below), as long as the exposed person has been made fully aware of the potential for exposure and can exercise control over their exposure and can exercise control over the potential for exposure and can exercise control over the potentia

Additional details can be found in FCC OET 65.

CALCULATIONS

Calculations were done for the proposed SPRINT Wireless antenna facility located at **69 Guinea Road**, **Stamford, CT**, using the equipment information listed below. All calculations were performed per the specifications under FCC OET 65. Since SPRINT is proposing highly focused directional panel antennas, which project most of the emitted energy out toward the horizon, all calculations were performed assuming a lobe representing the maximum gain of the antenna per the antenna manufactures supplied specifications, minus 10 dB, was focused at the base of the tower. For this report the sample point is the top of a 6-foot person standing at the base of the tower.

For all calculations, all equipment was calculated using the following assumptions:

- 1) 1 CDMA channels (850 MHz) were considered for each sector of the proposed installation. These Channels have a transmit power of 20 Watts per Channel.
- 2) 2 LTE channels (850 MHz) were considered for each sector of the proposed installation. These Channels have a transmit power of 20 Watts per Channel.
- 3) 5 CDMA channels (1900 MHz (PCS)) were considered for each sector of the proposed installation. These Channels have a transmit power of 16 Watts per Channel.
- 4) 2 LTE channels (1900 MHz (PCS)) were considered for each sector of the proposed installation. These Channels have a transmit power of 40 Watts per Channel.
- 5) 8 LTE channels (2500 MHz (BRS)) were considered for each sector of the proposed installation. These Channels have a transmit power of 20 Watts per Channel.



- 6) All radios at the proposed installation were considered to be running at full power and were uncombined in their RF transmissions paths per carrier prescribed configuration. Per FCC OET Bulletin No. 65 Edition 97-01 recommendations to achieve the maximum anticipated value at each sample point, all power levels emitting from the proposed antenna installation are increased by a factor of 2.56 to account for possible in-phase reflections from the surrounding environment. This is rarely the case, and if so, is never continuous.
- 7) For the following calculations, the sample point was the top of a 6-foot person standing at the base of the tower. The maximum gain of the antenna per the antenna manufactures supplied specifications minus 10 dB was used in this direction. This value is a very conservative estimate as gain reductions for these particular antennas are typically much higher in this direction.
- 8) The antennas used in this modeling are the RFS APXVSPP18-C-A20, RFS APXVTM14-C-I20 and Argus LLPX310R-V1 for transmission in the 850 MHz, 1900 MHz (PCS) and 2500 MHz (BRS) frequency bands. This is based on feedback from the carrier with regards to anticipated antenna selection. Maximum gain values for all antennas are listed in the Inventory and Power Data table below. The maximum gain of the antenna per the antenna manufactures supplied specifications, minus 10 dB, was used for all calculations. This value is a very conservative estimate as gain reductions for these particular antennas are typically much higher in this direction.
- 9) The antenna mounting height centerlines of the proposed antennas are **158 feet** above ground level (AGL) for **Sector A**, **158 feet** above ground level (AGL) for **Sector B** and **158 feet** above ground level (AGL) for **Sector C**.
- 10) Emissions values for additional carriers were taken from the Connecticut Siting Council active database. Values in this database are provided by the individual carriers themselves.

All calculations were done with respect to uncontrolled / general population threshold limits.



SPRINT Site Inventory and Power Data by Antenna

| Sector: | | | Sector: | В | | Sector: | С | |
|--|-----------------|---------------------------------------|-----------------------|-----------------------|---------------------|---------------------------|-----------------|--|
| Antenna #: | 1 | Ant | tenna #: | 1 | | Antenna #: | 1 | |
| Make / Model: | RFS | B-C-A20 Make / Model: APXVSPP18-C-A20 | | | Make / Model: | RFS | | |
| | APXVSPP18-C-A20 | | | | | | APXVSPP18-C-A20 | |
| Gain: | 13.4 / 15.9 dBd | | Gain: 13.4 / 15.9 dBo | | lBd | Gain: | 13.4 / 15.9 dBd | |
| Height (AGL): | 158 feet | Height (AGL) | | 158 feet 850 MHz / | | Height (AGL): | 158 feet | |
| Frequency Bands | 850 MHz / | Frequency | Frequency Bands | | - | Frequency Bands | 850 MHz / | |
| 1 5 | 1900 MHz (PCS) | 1. | · | 1900 MHz (PCS) | | 1 5 | 1900 MHz (PCS) | |
| Channel Count | 10 | Channel Count | | 10 | | Channel Count | 10 | |
| Total TX | 220 Watts | | otal TX | 220 Watts | | Total TX | 220 Watts | |
| Power(W): | | | wer(W): | | | Power(W): | | |
| ERP (W): | 7,537.38 | | RP (W): | 7,537.38 | | ERP (W): | 7,537.38 | |
| Antenna A1 MPE% | 1.33 % | Antenna B1 | MPE% | 1.33 % | | Antenna C1 MPE% | 1.33 % | |
| Antenna #: | 2 | Ant | tenna #: | 2 | | Antenna #: | 2 | |
| Make / Model: | RFS | Make / | Model: | RFS | | Make / Model: | RFS | |
| | APXVTM14-C-I20 | | | APXVTM14-C-I20 | | | APXVTM14-C-I20 | |
| Gain: | 15.9 dBd | | Gain: | | | Gain: | 15.9 dBd | |
| Height (AGL): | | | (AGL): | 158 feet | | Height (AGL): | 158 feet | |
| Frequency Bands | | | 2500 MHz (BRS) | | Frequency Bands | 2500 MHz (BRS) | | |
| Channel Count | 4 | Channel Count | | 4 | | Channel Count | 4 | |
| Total TX | 80 Watts | | otal TX | 80 Watts | | Total TX | 80 Watts | |
| Power(W): | | Power(W): | | 2.112.24 | | Power(W): | 2 112 20 | |
| ERP (W): | | | 3,112.36 | | ERP (W): | 3,112.36 | | |
| Antenna A2 MPE% | 0.48 % | | | 0.48 % | | Antenna C2 MPE% | 0.48 % | |
| Antenna #: | 3 | Ant | tenna #: | 3 | | Antenna #: | 3 | |
| Make / Model: | Argus | Make / | lake / Model: | Argus | | Make / Model: | Argus | |
| | LLPX310R-V1 | | | LLPX310R- | | | LLPX310R-V1 | |
| Gain: | 15.85 dBd | TT 1 1. | Gain: | 15.85 dBd | | Gain: | 15.85 dBd | |
| Height (AGL): | 158 feet | 0 | (AGL): | 158 feet | | | 158 feet | |
| Frequency Bands | 2500 MHz (BRS) | Frequency | / | 2500 MHz (BRS) | | Frequency Bands | 2500 MHz (BRS) | |
| Channel Count Total TX | 4 | | el Count otal TX | 4 | | Channel Count Total TX | 4 | |
| | 80 Watts | | | 80 Watts | | | 80 Watts | |
| Power(W): | 3.076.73 | | Power(W): ERP (W): | | | Power(W): | 3.076.73 | |
| ERP (W): | -) | | <u> </u> | | | ERP (W): | -) | |
| Antenna A3 MPE% 0.48 % Antenna B3 MPE% 0.48 % Antenna C3 MPE% 0.48 % | | | | | | 0.48 % | | |
| Site Co | | | | SPR | INT Sector A Total: | 2.29 % | | |
| Carrier | MPI | Ξ% | | | SPR | INT Sector B Total: | 2.29 % | |
| SPRINT – Max per | sector 2.29 | % | | | SPR | INT Sector C Total: | 2.29 % | |
| T-Mobile | 3.21 | % | | | | | | |
| AT&T | 2.11 | % | | | | Site Total: | 10.82 % | |
| Verizon Wirele | | | | • | | | | |
| Metricom | 0.00 | % | | | | | | |
| | | | | | | | | |

| SPRINT _ Max Values per Frequency Band / Technology Per Sector | # Channels | Watts ERP (Per Channel) | Height (feet) | Total Power Density (µW/cm ²) | Frequency (MHz) | Allowable MPE (µW/cm ²) | Calculated % MPE |
|--|---------------|----------------------------|------------------|---|--------------------|---|---------------------|
| Sprint 850 MHz CDMA | 1 | 437.55 | 158 | 0.68 | 850 MHz | 567 | 0.12% |
| Sprint 850 MHz LTE | 2 | 437.55 | 158 | 1.36 | 850 MHz | 567 | 0.24% |
| Sprint 1900 MHz (PCS) CDMA | 5 | 622.47 | 158 | 4.84 | 1900 MHz (PCS) | 1000 | 0.48% |
| Sprint 1900 MHz (PCS) LTE | 2 | 1,556.18 | 158 | 4.84 | 1900 MHz (PCS) | 1000 | 0.48% |
| Sprint 2500 MHz (BRS) LTE (ANT2) | 4 | 778.09 | 158 | 4.84 | 2500 MHz (BRS) | 1000 | 0.48% |
| Sprint 2500 MHz (BRS) LTE (ANT3) | 4 | 769.18 | 158 | 4.79 | 2500 MHz (BRS) | 1000 | 0.48% |
| | | | | | | Total*: | 2.29% |

*NOTE: Totals may vary by 0.01% due to summing of remainders

Nextel

Site Total MPE %:

0.19 %

10.82 %



Summary

All calculations performed for this analysis yielded results that were **within** the allowable limits for general population exposure to RF Emissions.

The anticipated maximum composite contributions from the SPRINT facility as well as the site composite emissions value with regards to compliance with FCC's allowable limits for general population exposure to RF Emissions are shown here:

| SPRINT Sector | Power Density Value (%) |
|-------------------------|-------------------------|
| Sector A: | 2.29 % |
| Sector B: | 2.29 % |
| Sector C: | 2.29 % |
| SPRINT Maximum | 2.29 % |
| Total (per sector): | |
| | |
| Site Total: | 10.82 % |
| | |
| Site Compliance Status: | COMPLIANT |

The anticipated composite MPE value for this site assuming all carriers present is **10.82** % of the allowable FCC established general population limit sampled at the ground level. This is based upon values listed in the Connecticut Siting Council database for existing carrier emissions.

FCC guidelines state that if a site is found to be out of compliance (over allowable thresholds), that carriers over a 5% contribution to the composite value will require measures to bring the site into compliance. For this facility, the composite values calculated were well within the allowable 100% threshold standard per the federal government.