

STATE OF CONNECTICUT CONNECTICUT SITING COUNCIL

Ten Franklin Square, New Britain, CT 06051 Phone: (860) 827-2935 Fax: (860) 827-2950 E-Mail: siting.council@ct.gov

Web Site: portal.ct.gov/csc

VIA ELECTRONIC MAIL

April 19, 2023

Kenneth C. Baldwin, Esq. Robinson & Cole LLP 280 Trumbull Street Hartford, CT 06103-3597 kbaldwin@rc.com

RE: **EM-VER-137-230209** – Cellco Partnership d/b/a Verizon Wireless notice of intent to modify an existing telecommunications facility located at 212 Deans Mill Road, Stonington, Connecticut.

Dear Attorney Baldwin:

The Connecticut Siting Council (Council) is in receipt of your April 17, 2023 correspondence notifying the Council of a change to the model of the remote radio head (RRH) to RF4440d-13A due to the unavailability of the approved RRH model.

Pursuant to Regulations of Connecticut State Agencies §16-50j-73, the Council hereby acknowledges notification of the change in the RRH model. This acknowledgment applies only to the changes described in the April 17, 2023 correspondence.

The RRH installation is to be implemented as specified in the revised Structural Analysis prepared by Centek Engineering, dated April 10, 2023, associated Tower Modification Drawings and project plans for the above-referenced facility attached to the April 17, 2023 correspondence.

Thank you for your attention and cooperation.

Sincerely,

Melanie A. Bachman Executive Director

Mulin Bul

MAB/ANM/laf

c: The Honorable Danielle Chesebrough, First Selectperson, Town of Stonington (selectmen@stonington-ct.gov)

Robinson+Cole

KENNETH C. BALDWIN

280 Trumbull Street Hartford, CT 06103-3597 Main (860) 275-8200 Fax (860) 275-8299 kbaldwin@rc.com Direct (860) 275-8345

Also admitted in Massachusetts and New York

April 17, 2023

Melanie A. Bachman, Esq. Executive Director/Staff Attorney Connecticut Siting Council 10 Franklin Square New Britain, CT 06051

Re: EM-VER-137-230209 – Cellco Partnership d/b/a Verizon Wireless – 212 Deans Mill Road, Stonington, Connecticut

Dear Attorney Bachman:

On March 13, 2023 the Siting Council approved the above referenced Exempt Modification filing permitting the modification of an existing telecommunications facility located at 212 Deans Mill Road in Stonington. Cellco recently learned that the remote radio head ("RRH") it intended to install at this site was no longer available. The new RRH, model number RF4440d-13A will be installed in its place.

Enclosed is a revised Structural Analysis and updated set of project plans showing the new RRH that Cellco intends to install.

Please contact me if you have any questions regarding this proposal.

Sincerely,

Kenneth C. Baldwin

Attachments



Centered on Solutions[™]

Structural Analysis Report

Antenna Mount

Proposed Verizon Antenna Upgrade

Site Ref: Mystic SC1

212 Deans Mill Road Stonington, CT

CENTEK Project No. 22105.05

Date: September 13, 2022

Rev 2: April 10, 2023



Prepared for:

Verizon Wireless 20 Alexander Drive Wallingford, CT 06492

Structural Analysis – Antenna Mounts Verizon Antenna Upgrade – Mystic SC1 Stonington, CT Rev 2 ~ April 10, 2023

Table of Contents

SECTION 1 - REPORT

- INTRODUCTION
- PRIMARY ASSUMPTIONS USED IN THE ANALYSIS
- ANTENNA AND EQUIPMENT INSTALLATION SUMMARY
- ANALYSIS
- DESIGN LOADING
- RESULTS
- CONCLUSION

SECTION 2 - CONDITIONS & SOFTWARE

- STANDARD ENGINEERING CONDITIONS
- GENERAL DESCRIPTION OF STRUCTURAL ANALYSIS PROGRAM

SECTION 3 - CALCULATIONS

RISA 3D OUTPUT REPORT – ANTENNA MOUNT

SECTION 4 - REFERENCE MATERIAL

RF DATA SHEET

TABLE OF CONTENTS TOC-1

Structural Analysis – Antenna Mounts Verizon Antenna Upgrade – Mystic SC1 Stonington, CT Rev 2 ~ April 10, 2023

Introduction

The purpose of this structural analysis report (SAR) is to summarize the results, of the impacted structural components, by the equipment upgrade proposed by Verizon Wireless on the existing host building located in Stonington, CT.

The antenna is mounted on a structural steel pipe mast with steel base frame attached to the host building roof framing. The antenna mast/base frame is located within a RF transparent cupola. The mounts member sizes information were obtained from the original design documents prepared by Centek Engineering, dated February 2, 2016. Proposed/existing antenna and appurtenance information was taken from a RF data sheet dated 3/30/2023 provided by Verizon Wireless.

Primary Assumptions Used in the Analysis

- The host structure's theoretical capacity not including any assessment of the condition of the host structure.
- The existing steel antenna frames carry the horizontal and vertical loads due to the weight of equipment, and wind and transfers into host structure.
- Structure is in plumb condition.
- Loading for equipment and enclosure as listed in this report.
- All bolts are appropriately tightened providing the necessary connection continuity.
- All welds are fabricated with ER-70S-6 electrodes.
- All members are assumed to be as observed during roof framing mapping.
- All members are "hot dipped" galvanized in accordance with ASTM A123 and ASTM A153 Standards.
- All member protective coatings are in good condition.

REPORT SECTION 1-1

Structural Analysis – Antenna Mounts Verizon Antenna Upgrade – Mystic SC1 Stonington, CT Rev 2 ~ April 10, 2023

Antenna and Equipment Summary

Location	Appurtenance / Equipment	Rad Center Elevation (AGL)	Mount Type
Alpha Sector	(1) Andrew HBX-6513DS Antenna (1) Amphenol HTXCWW63111414F00 Antenna (1) Nokia B4 RRH 2x60-4R RRH (1) Samsung RF4440d-13A (B5/B13) RRH	±24.9-ft	Pipe mast with steel base frame attached to roof deck located within cupola

Equipment – Indicates equipment to be removed. Equipment – Indicates equipment to be installed.

Analysis

The existing antenna frame was analyzed using a comprehensive computer program titled Risa3D. The program analyzes the antenna mounts considering the worst case code prescribed loading condition. The structures were considered to be loaded by concentric forces, and the model assumes that the members are subjected to bending, axial, and shear forces.

<u>Design Loading</u>

Loading was determined per the requirements of the 2021 International Building Code amended by the 2022 CSBC and ASCE 7-16 "Minimum Design Loads for Buildings and Other Structures".

Wind Speed:	V _{ult} = 130 mph	Appendix P of the 2022 CT State Building Code				
Risk Category:	II	2021 IBC; Table 1604.05				
Exposure Category:	Surface Roughness C	ASCE 7-16; Section 26.7.2				
Dead Load	Equipment and framing self- weight	Identified within SAR design calculations				

REPORT SECTION 1-2

Structural Analysis – Antenna Mounts Verizon Antenna Upgrade – Mystic SC1 Stonington, CT Rev 2 ~ April 10, 2023

Reference Standards

2021 International Building Code:

- 1. ACI 318-19, Building Code Requirements for Structural Concrete.
- 2. ACI 402/602-16, Building Code Requirements for Masonry Structures.
- 3. AISC 360-16, Specification for Structural Steel Buildings
- 4. AWS D1.4-18, Structural Welding Code Steel.

Results

Structure stresses were calculated utilizing the structural analysis software RISA 3D. The stresses were determined based on the AISC standard.

Calculated stresses for the antenna frame were found to be within allowable limits.

Sector	Component	Stress Ratio (percentage of capacity)	Result
All Sectors	Antenna Frame	4%	PASS

Conclusion

This analysis shows that the subject antenna mounts and host building **HAVE SUFFICIENT CAPACITY** to support the proposed modified antenna configuration.

The analysis is based, in part, on the information provided to this office by Verizon. If the existing conditions are different than the information in this report, Centek Engineering, Inc. must be contacted for resolution of any potential issues.

Please feel free to call with any questions or comments.

Respectfully Submitted by:

Timothy J. Lynn, PĒ Structural Engineer

REPORT SECTION 1-3


Structural Analysis – Antenna Mounts Verizon Antenna Upgrade – Mystic SC1 Stonington, CT Rev 2 ~ April 10, 2023


Standard Conditions for Furnishing of Professional Engineering Services on Existing Structures

All engineering services are performed on the basis that the information used is current and correct. This information may consist of, but is not necessarily limited to:

- Information supplied by the client regarding the structure itself, its foundations, the soil
 conditions, the antenna and feed line loading on the structure and its components, or
 other relevant information.
- Information from the field and/or drawings in the possession of Centek Engineering, Inc. or generated by field inspections or measurements of the structure.
- It is the responsibility of the client to ensure that the information provided to Centek Engineering, Inc. and used in the performance of our engineering services is correct and complete. In the absence of information to the contrary, we assume that all structures were constructed in accordance with the drawings and specifications and are in an uncorroded condition and have not deteriorated. It is therefore assumed that its capacity has not significantly changed from the "as new" condition.
- All services will be performed to the codes specified by the client, and we do not imply to
 meet any other codes or requirements unless explicitly agreed in writing. If wind and ice
 loads or other relevant parameters are to be different from the minimum values
 recommended by the codes, the client shall specify the exact requirement. In the
 absence of information to the contrary, all work will be performed in accordance with the
 latest revision of ANSI/ASCE10 & ANSI/EIA-222
- All services performed, results obtained, and recommendations made are in accordance
 with generally accepted engineering principles and practices. Centek Engineering, Inc.
 is not responsible for the conclusions, opinions and recommendations made by others
 based on the information we supply.

REPORT SECTION 2-1





Envelope Only Solution

Centek Engineering		
TJL	Mystic SC1	Sept 13, 2022 at 2:52 PM
22105.05	Member Framing	Mount.r3d



: Centek Engineering: TJL

Company : Centek Engi Designer : TJL Job Number : 22105.05 Model Name : Mystic SC1

Sept 13, 2022 2:51 PM Checked By: CFC

(Global) Model Settings

Display Sections for Member Calcs	5
Max Internal Sections for Member Calcs	97
Include Shear Deformation?	Yes
Increase Nailing Capacity for Wind?	Yes
Include Warping?	Yes
Trans Load Btwn Intersecting Wood Wall?	Yes
Area Load Mesh (in^2)	144
Merge Tolerance (in)	.12
P-Delta Analysis Tolerance	0.50%
Include P-Delta for Walls?	Yes
Automatically Iterate Stiffness for Walls?	Yes
Max Iterations for Wall Stiffness	3
Gravity Acceleration (ft/sec^2)	32.2
Wall Mesh Size (in)	12
Eigensolution Convergence Tol. (1.E-)	4
Vertical Axis	Υ
Global Member Orientation Plane	XZ
Static Solver	Sparse Accelerated
Dynamic Solver	Accelerated Solver

Hot Rolled Steel Code	AISC 15th(360-16): ASD
Adjust Stiffness?	Yes(Iterative)
RISAConnection Code	AISC 14th(360-10): ASD
Cold Formed Steel Code	AISI S100-10: ASD
Wood Code	AWC NDS-12: ASD
Wood Temperature	< 100F
Concrete Code	ACI 318-11
Masonry Code	ACI 530-11: ASD
Aluminum Code	AA ADM1-10: ASD - Building
Stainless Steel Code	AISC 14th(360-10): ASD
Adjust Stiffness?	Yes(Iterative)

Number of Shear Regions	4
Region Spacing Increment (in)	4
Biaxial Column Method	Exact Integration
Parme Beta Factor (PCA)	.65
Concrete Stress Block	Rectangular
Use Cracked Sections?	Yes
Use Cracked Sections Slab?	No
Bad Framing Warnings?	No
Unused Force Warnings?	Yes
Min 1 Bar Diam. Spacing?	No
Concrete Rebar Set	REBAR_SET_ASTMA615
Min % Steel for Column	1
Max % Steel for Column	8



: Centek Engineering

Company Designer Job Number : 22105.05 Model Name : Mystic SC1

Sept 13, 2022 2:51 PM Checked By: CFC

(Global) Model Settings, Continued

Seismic Base Elevation (ft)	Seismic Code	ASCE 7-10
Ct X .02 Ct Z .02 T X (sec) Not Entered T Z (sec) Not Entered R X 3 R Z 3 Ct Exp. X .75 Ct Exp. Z .75 SD1 1 SDS 1 S1 1 TL (sec) 5 Risk Cat I or II Drift Cat Other Om Z 1 Om X 1 Cd Z 4 Cd X 4 Rho Z 1 Rho X 1 Rho X 1 Pooting Overturning Safety Factor 1 Optimize for OTM/Sliding No Check Concrete Bearing No Footing Concrete Weight (k/ft/3) 150.001 Footing Concrete Ec (ksi) 3644 Lambda 1 Footing Steel fy (ksi) 60 Minimum Steel 0.0018 Maximum Steel 0.00075	Seismic Base Elevation (ft)	Not Entered
Ct Z .02 T X (sec) Not Entered T Z (sec) Not Entered R X 3 R Z 3 Ct Exp. X .75 Ct Exp. Z .75 SDD 1 SDS 1 S1 1 TL (sec) 5 Risk Cat I or II Drift Cat Other Om Z 1 Om X 1 Cd Z 4 Cd X 4 Rho Z 1 Rho X 1 Footing Overturning Safety Factor 1 Optimize for OTM/Sliding No Check Concrete Bearing No Footing Concrete Weight (k/ft^3) 150.001 Footing Concrete Ec (ksi) 3644 Lambda 1 Footing Steel fy (ksi) 60 Minimum Steel 0.0018 Maximum Steel 0.0075 Footing Top Bar #3 Footing Bottom Bar (rin)	Add Base Weight?	Yes
Ct Z .02 T X (sec) Not Entered T Z (sec) Not Entered R X 3 R Z 3 Ct Exp. X .75 Ct Exp. Z .75 SDS 1 S1 1 TL (sec) 5 Risk Cat lor II Drift Cat Other Om Z 1 Om X 1 Cd Z 4 Cd X 4 Rho Z 1 Rho X 1 Footing Overturning Safety Factor 1 Optimize for OTM/Sliding No Check Concrete Bearing No Footing Concrete Weight (k/ft^3) 150.001 Footing Concrete Fc (ksi) 3644 Lambda 1 Footing Steel fy (ksi) 60 Minimum Steel 0.0018 Maximum Steel 0.0075 Footing Bottom Bar #3 Footing Bottom Bar Cover (in) 2 Fo	Ct X	.02
T Z (sec) Not Entered R X 3 R Z 3 Ct Exp. X .75 Ct Exp. Z .75 SD1 1 SDS 1 S1 1 TL (sec) 5 Risk Cat I or II Drift Cat Other Om Z 1 Om X 1 Cd Z 4 Cd X 4 Rho Z 1 Rho X 1 Footing Overturning Safety Factor 1 Optimize for OTM/Sliding No Check Concrete Bearing No Footing Concrete Weight (k/ft^3) 150.001 Footing Concrete Weight (k/ft/3) 150.001 Footing Concrete Ec (ksi) 3644 Lambda 1 Footing Steel fy (ksi) 60 Minimum Steel 0.0018 Maximum Steel 0.0075 Footing Top Bar Cover (in) 2 Footing Bottom Bar Cover (in) 3.5 <td></td> <td>.02</td>		.02
T Z (sec) Not Entered R X 3 R Z 3 Ct Exp. X .75 Ct Exp. Z .75 SD1 1 SDS 1 S1 1 TL (sec) 5 Risk Cat I or II Drift Cat Other Om Z 1 Om X 1 Cd Z 4 Cd X 4 Rho Z 1 Rho X 1 Footing Overturning Safety Factor 1 Optimize for OTM/Sliding No Check Concrete Bearing No Footing Concrete Weight (k/ft^3) 150.001 Footing Concrete Weight (k/ft/3) 150.001 Footing Concrete Ec (ksi) 3644 Lambda 1 Footing Steel fy (ksi) 60 Minimum Steel 0.0018 Maximum Steel 0.0075 Footing Top Bar Cover (in) 2 Footing Bottom Bar Cover (in) 3.5 <td>T X (sec)</td> <td>Not Entered</td>	T X (sec)	Not Entered
R Z Ct Exp. X .75 Ct Exp. Z .75 SD1 SD1 1 SDS 1 SS1 TL (sec) Sisk Cat I or II Drift Cat Other Om Z 1 Om X 1 Cd Z 4 Cd X Rho Z Rho X 1 The South Safety Factor Optimize for OTM/Sliding Check Concrete Bearing Footing Concrete Weight (k/ft^3) Footing Concrete Fic (ksi) Lambda Footing Steel fy (ksi) Minimum Steel Maximum Steel Footing Top Bar Footing Bottom Bar Footing Bar Foo		Not Entered
Ct Exp. Z .75 Ct Exp. Z .75 SD1 1 SDS 1 St 1 TL (sec) 5 Risk Cat I or II Drift Cat Other Om Z 1 Om X 1 Cd Z 4 Cd X 4 Rho Z 1 Rho X 1 Footing Overturning Safety Factor 1 Optimize for OTM/Sliding No Check Concrete Bearing No Footing Concrete Weight (k/ft^3) 150.001 Footing Concrete Fic (ksi) 4 Footing Concrete Ec (ksi) 3644 Lambda 1 Footing Steel fy (ksi) 60 Minimum Steel 0.0018 Maximum Steel 0.0075 Footing Top Bar #3 Footing Bottom Bar Cover (in) 2 Footing Bottom Bar Cover (in) 3.5 Pedestal Bar #3 Pedestal Bar Cover (in) 1.5	RX	3
Ct Exp. Z .75 SD1 1 SDS 1 S1 1 TL (sec) 5 Risk Cat I or II Drift Cat Other Om Z 1 Om X 1 Cd Z 4 Cd X 4 Rho Z 1 Rho X 1 Footing Overturning Safety Factor 1 Optimize for OTM/Sliding No Check Concrete Bearing No Footing Concrete Weight (k/ft^3) 150.001 Footing Concrete Ec (ksi) 3644 Lambda 1 Footing Steel fy (ksi) 60 Minimum Steel 0.0018 Maximum Steel 0.0018 Maximum Top Bar #3 Footing Bottom Bar Cover (in) 2 Footing Bottom Bar Cover (in) 3.5 Pedestal Bar #3 Pedestal Bar Cover (in) 1.5	R Z	3
SD1 1 SDS 1 S1 1 TL (sec) 5 Risk Cat I or II Drift Cat Other Om Z 1 Om X 1 Cd Z 4 Cd X 4 Rho Z 1 Rho X 1 Footing Overturning Safety Factor 1 Optimize for OTM/Sliding No Check Concrete Bearing No Footing Concrete Weight (k/ft^3) 150.001 Footing Concrete Fic (ksi) 4 Footing Concrete Ec (ksi) 3644 Lambda 1 Footing Steel fy (ksi) 60 Minimum Steel 0.0018 Maximum Steel 0.0075 Footing Top Bar #3 Footing Bottom Bar #3 Footing Bottom Bar Cover (in) 3.5 Pedestal Bar #3 Pedestal Bar Cover (in) 1.5	Ct Exp. X	.75
SD1 1 SDS 1 S1 1 TL (sec) 5 Risk Cat I or II Drift Cat Other Om Z 1 Om X 1 Cd Z 4 Cd X 4 Rho Z 1 Rho X 1 Footing Overturning Safety Factor 1 Optimize for OTM/Sliding No Check Concrete Bearing No Footing Concrete Weight (k/ft^3) 150.001 Footing Concrete Fic (ksi) 4 Footing Concrete Ec (ksi) 3644 Lambda 1 Footing Steel fy (ksi) 60 Minimum Steel 0.0018 Maximum Steel 0.0075 Footing Top Bar #3 Footing Bottom Bar #3 Footing Bottom Bar Cover (in) 3.5 Pedestal Bar #3 Pedestal Bar Cover (in) 1.5	Ct Exp. Z	.75
S1 1 TL (sec) 5 Risk Cat I or II Drift Cat Other Om Z 1 Om X 1 Cd Z 4 Cd X 4 Rho Z 1 Rho X 1 Footing Overturning Safety Factor 1 Optimize for OTM/Sliding No Check Concrete Bearing No Footing Concrete Weight (k/ft^3) 150.001 Footing Concrete Weight (k/ft^3) 4 Footing Concrete Ec (ksi) 3644 Lambda 1 Footing Steel fy (ksi) 60 Minimum Steel 0.0018 Maximum Steel 0.0075 Footing Top Bar Cover (in) 2 Footing Bottom Bar #3 Footing Bottom Bar Cover (in) 3.5 Pedestal Bar Cover (in) 1.5		1
TL (sec) 5 Risk Cat I or II Drift Cat Other Om Z 1 Om X 1 Cd Z 4 Cd X 4 Rho Z 1 Rho X 1 Footing Overturning Safety Factor 1 Optimize for OTM/Sliding No Check Concrete Bearing No Footing Concrete Weight (k/ft^3) 150.001 Footing Concrete Fic (ksi) 4 Footing Concrete Ec (ksi) 3644 Lambda 1 Footing Steel fy (ksi) 60 Minimum Steel 0.0018 Maximum Steel 0.0075 Footing Top Bar #3 Footing Bottom Bar #3 Footing Bottom Bar Cover (in) 3.5 Pedestal Bar #3 Pedestal Bar Cover (in) 1.5	SDS	1
Risk Cat I or II Drift Cat Other Om Z 1 Om X 1 Cd Z 4 Cd X 4 Rho Z 1 Footing Overturning Safety Factor 1 Optimize for OTM/Sliding No Check Concrete Bearing No Footing Concrete Weight (k/ft^3) 150.001 Footing Concrete Fic (ksi) 4 Footing Concrete Ec (ksi) 3644 Lambda 1 Footing Steel fy (ksi) 60 Minimum Steel 0.0018 Maximum Steel 0.0075 Footing Top Bar #3 Footing Bottom Bar #3 Footing Bottom Bar Cover (in) Pedestal Bar #3 Pedestal Bar Footing Bot Cover (in) Pedestal Bar Cover (in) 1.5	S1	1
Risk Cat I or II Drift Cat Other Om Z 1 Om X 1 Cd Z 4 Cd X 4 Rho Z 1 Footing Overturning Safety Factor 1 Optimize for OTM/Sliding No Check Concrete Bearing No Footing Concrete Weight (k/ft^3) 150.001 Footing Concrete Fic (ksi) 4 Footing Concrete Ec (ksi) 3644 Lambda 1 Footing Steel fy (ksi) 60 Minimum Steel 0.0018 Maximum Steel 0.0075 Footing Top Bar #3 Footing Bottom Bar #3 Footing Bottom Bar Cover (in) Pedestal Bar #3 Pedestal Bar Footing Bot Cover (in) Pedestal Bar Cover (in) 1.5	TL (sec)	5
Om Z 1 Om X 1 Cd Z 4 Cd X 4 Rho Z 1 Rho X 1 Footing Overturning Safety Factor 1 Optimize for OTM/Sliding No Check Concrete Bearing No Footing Concrete Weight (k/ft^3) 150.001 Footing Concrete F'c (ksi) 4 Footing Concrete Ec (ksi) 3644 Lambda 1 Footing Steel fy (ksi) 60 Minimum Steel 0.0018 Maximum Steel 0.0075 Footing Top Bar #3 Footing Top Bar Cover (in) 2 Footing Bottom Bar #3 Footing Bottom Bar Cover (in) 3.5 Pedestal Bar #3 Pedestal Bar Cover (in) 1.5		I or II
Om X Cd Z Cd X Rho Z Rho X Footing Overturning Safety Factor Optimize for OTM/Sliding Check Concrete Bearing Footing Concrete Weight (k/ft^3) Footing Concrete Wight (k/ft^3) Footing Concrete Ec (ksi) Footing Concrete Ec (ksi) Footing Steel fy (ksi) Footing Steel fy (ksi) Footing Steel fy (ksi) Footing Top Bar Footing Top Bar Footing Top Bar Cover (in) Footing Bottom Bar Footing Bottom Bar #3 Footing Bottom Bar Cover (in) Pedestal Bar Foedstal Bar Cover (in) 1 1 1 1 1 1 1 1 1 1 1 1 1	Drift Cat	Other
Cd Z Cd X Rho Z Rho X 1 Footing Overturning Safety Factor Optimize for OTM/Sliding Check Concrete Bearing Footing Concrete Weight (k/ft^3) Footing Concrete Weight (k/ft^3) Footing Concrete Ec (ksi) Footing Concrete Ec (ksi) Footing Steel fy (ksi) Footing Steel fy (ksi) Footing Steel fy (ksi) Footing Top Bar Footing Top Bar Footing Top Bar Cover (in) Footing Bottom Bar #3 Footing Bottom Bar Cover (in) Pedestal Bar Foedestal Bar Footore Top Sate #3 Footing Bottom Bar Cover (in) Pedestal Bar #3 Footing Bottom Bar Footing Bottom Bar #3	Om Z	1
Cd X Rho Z Rho X 1 Footing Overturning Safety Factor Optimize for OTM/Sliding Check Concrete Bearing No Footing Concrete Weight (k/ft^3) Footing Concrete Fic (ksi) Footing Concrete Ec (ksi) Footing Concrete Ec (ksi) Footing Steel fy (ksi) Footing Steel fy (ksi) Minimum Steel Maximum Steel Maximum Steel O.0075 Footing Top Bar Footing Top Bar #3 Footing Bottom Bar Footing Bottom Bar Cover (in) Pedestal Bar Pedestal Bar Cover (in) 1.5		1
Rho Z Rho X 1 Footing Overturning Safety Factor Optimize for OTM/Sliding Check Concrete Bearing No Footing Concrete Weight (k/ft^3) Footing Concrete f'c (ksi) Footing Concrete Ec (ksi) Footing Concrete Ec (ksi) Sooting Steel fy (ksi) Footing Steel fy (ksi) Minimum Steel Maximum Steel Maximum Steel No.0075 Footing Top Bar Footing Top Bar #3 Footing Bottom Bar Footing Bottom Bar Cover (in) Pedestal Bar Pedestal Bar Cover (in) 1.5	Cd Z	4
Rho X Footing Overturning Safety Factor Optimize for OTM/Sliding Check Concrete Bearing Footing Concrete Weight (k/ft^3) Footing Concrete f'c (ksi) Footing Concrete Ec (ksi) Footing Concrete Ec (ksi) Footing Steel fy (ksi) Minimum Steel Maximum Steel Maximum Steel Footing Top Bar Footing Top Bar Cover (in) Footing Bottom Bar Footing Bottom Bar Cover (in) Pedestal Bar Pedestal Bar Cover (in) 1 Control Description Safety Factor 1 Control Description Safety 1 Control Description Safety Control Description Sa	Cd X	4
Footing Overturning Safety Factor Optimize for OTM/Sliding Check Concrete Bearing Footing Concrete Weight (k/ft^3) Footing Concrete f'c (ksi) Footing Concrete Ec (ksi) Footing Concrete Ec (ksi) Footing Steel fy (ksi) Minimum Steel Maximum Steel Maximum Steel O.0075 Footing Top Bar Footing Top Bar Cover (in) Footing Bottom Bar Footing Bottom Bar #3 Footing Bottom Bar Cover (in) Pedestal Bar Pedestal Bar Cover (in) 1.5	Rho Z	1
Optimize for OTM/Sliding Check Concrete Bearing No Footing Concrete Weight (k/ft^3) Footing Concrete f'c (ksi) Footing Concrete Ec (ksi) Footing Concrete Ec (ksi) Lambda 1 Footing Steel fy (ksi) 60 Minimum Steel 0.0018 Maximum Steel 0.0075 Footing Top Bar Footing Top Bar #3 Footing Bottom Bar #3 Footing Bottom Bar Cover (in) Pedestal Bar Pedestal Bar Cover (in) 1.5	Rho X	1
Optimize for OTM/Sliding Check Concrete Bearing No Footing Concrete Weight (k/ft^3) Footing Concrete f'c (ksi) Footing Concrete Ec (ksi) Footing Concrete Ec (ksi) Lambda 1 Footing Steel fy (ksi) 60 Minimum Steel 0.0018 Maximum Steel 0.0075 Footing Top Bar Footing Top Bar #3 Footing Bottom Bar #3 Footing Bottom Bar Cover (in) Pedestal Bar Pedestal Bar Cover (in) 1.5		
Optimize for OTM/Sliding Check Concrete Bearing No Footing Concrete Weight (k/ft^3) Footing Concrete f'c (ksi) Footing Concrete Ec (ksi) Footing Concrete Ec (ksi) Lambda 1 Footing Steel fy (ksi) 60 Minimum Steel 0.0018 Maximum Steel 0.0075 Footing Top Bar Footing Top Bar #3 Footing Bottom Bar #3 Footing Bottom Bar Cover (in) Pedestal Bar Pedestal Bar Cover (in) 1.5	Footing Overturning Safety Factor	1
Footing Concrete Weight (k/ft^3) Footing Concrete f'c (ksi) Footing Concrete Ec (ksi) Lambda Footing Steel fy (ksi) Minimum Steel Maximum Steel Footing Top Bar Footing Top Bar #3 Footing Bottom Bar Footing Bottom Bar Cover (in) Pedestal Bar Pedestal Bar Cover (in) 150.001 4 0.001 0.0018 0.0075 #3 Footing Top Bar #3 Footing Top Bar Cover (in) 3.5 Pedestal Bar #3 Pedestal Bar Cover (in) 1.5		No
Footing Concrete f'c (ksi) 4 Footing Concrete Ec (ksi) 3644 Lambda 1 Footing Steel fy (ksi) 60 Minimum Steel 0.0018 Maximum Steel 0.0075 Footing Top Bar #3 Footing Top Bar Cover (in) 2 Footing Bottom Bar #3 Footing Bottom Bar Cover (in) 3.5 Pedestal Bar #3 Pedestal Bar Cover (in) 1.5	Check Concrete Bearing	No
Footing Concrete Ec (ksi) 3644 Lambda 1 Footing Steel fy (ksi) 60 Minimum Steel 0.0018 Maximum Steel 0.0075 Footing Top Bar #3 Footing Top Bar Cover (in) 2 Footing Bottom Bar #3 Footing Bottom Bar Cover (in) 3.5 Pedestal Bar #3 Pedestal Bar Cover (in) 1.5	Footing Concrete Weight (k/ft^3)	150.001
Lambda 1 Footing Steel fy (ksi) 60 Minimum Steel 0.0018 Maximum Steel 0.0075 Footing Top Bar #3 Footing Top Bar Cover (in) 2 Footing Bottom Bar #3 Footing Bottom Bar Cover (in) 3.5 Pedestal Bar #3 Pedestal Bar Cover (in) 1.5	Footing Concrete f'c (ksi)	4
Footing Steel fy (ksi) 60 Minimum Steel 0.0018 Maximum Steel 0.0075 Footing Top Bar #3 Footing Top Bar Cover (in) 2 Footing Bottom Bar #3 Footing Bottom Bar Cover (in) 3.5 Pedestal Bar #3 Pedestal Bar Cover (in) 1.5	Footing Concrete Ec (ksi)	3644
Minimum Steel 0.0018 Maximum Steel 0.0075 Footing Top Bar #3 Footing Bottom Bar #3 Footing Bottom Bar Cover (in) 3.5 Pedestal Bar #3 Pedestal Bar Cover (in) 1.5	Lambda	1
Maximum Steel 0.0075 Footing Top Bar #3 Footing Top Bar Cover (in) 2 Footing Bottom Bar #3 Footing Bottom Bar Cover (in) 3.5 Pedestal Bar #3 Pedestal Bar Cover (in) 1.5	Footing Steel fy (ksi)	60
Footing Top Bar #3 Footing Top Bar Cover (in) 2 Footing Bottom Bar #3 Footing Bottom Bar Cover (in) 3.5 Pedestal Bar #3 Pedestal Bar Cover (in) 1.5	Minimum Steel	0.0018
Footing Top Bar Cover (in) Footing Bottom Bar Footing Bottom Bar Cover (in) Pedestal Bar Pedestal Bar Cover (in) 1.5	Maximum Steel	0.0075
Footing Bottom Bar #3 Footing Bottom Bar Cover (in) 3.5 Pedestal Bar #3 Pedestal Bar Cover (in) 1.5	Footing Top Bar	#3
Footing Bottom Bar Cover (in) 3.5 Pedestal Bar #3 Pedestal Bar Cover (in) 1.5	Footing Top Bar Cover (in)	2
Pedestal Bar #3 Pedestal Bar Cover (in) 1.5		
Pedestal Bar Cover (in) 1.5	Footing Bottom Bar Cover (in)	3.5
		#3
	Pedestal Bar Cover (in)	1.5
r cucsiai i ics	Pedestal Ties	#3

Hot Rolled Steel Properties

	Label	E [ksi]	G [ksi]	Nu	Therm (\	Density[k/ft^3]	Yield[ksi]	Ry	Fu[ksi]	Rt
1	A36 Gr.36	29000	11154	.3	.65	.49	36	1.5	58	1.2
2	A572 Gr.50	29000	11154	.3	.65	.49	50	1.1	58	1.2
3	A992	29000	11154	.3	.65	.49	50	1.1	58	1.2
4	A500 Gr.42	29000	11154	.3	.65	.49	42	1.3	58	1.1
5	A500 Gr.46	29000	11154	.3	.65	.49	46	1.2	58	1.1
6	A53 Grade B	29000	11154	.3	.65	.49	35	1.5	58	1.2



Company Designer Job Number

: Centek Engineering

: 22105.05 Model Name : Mystic SC1 Sept 13, 2022 2:51 PM Checked By: CFC

Hot Rolled Steel Section Sets

	Label	Shape	Type	Design List	Material	Design Ru	. A [in2]	lyy [in4]	Izz [in4]	J [in4]
1	Antenna Mast	PIPE_3.0	Column	Pipe	A53 Grade B	Typical	2.07	2.85	2.85	5.69
2	Post	PIPE_2.5X	Column	Pipe	A53 Grade B	Typical	2.1	1.83	1.83	3.66
3	C10	C10X15.3	Beam	Channel	A36 Gr.36	Typical	4.48	2.27	67.3	.209
4	C4	C4X7.25	Beam	Channel	A36 Gr.36	Typical	2.13	.425	4.58	.082

Hot Rolled Steel Design Parameters

	Label	Shape	Length[ft]	Lbyy[ft]	Lbzz[ft]	Lcomp top[.Lcomp bot[.L-torq	Куу	Kzz	Cb	Functi
1	M1	Post	2.5				-					Lateral
2	M2	Post	2.5									Lateral
3	M3	Post	2.5									Lateral
4	M4	Post	2.5									Lateral
5	M5	C10	3			Lbyy						Lateral
6	M6	C10	3			Lbyy						Lateral
7	M7	C10	3			Lbyy						Lateral
8	M8	C10	3			Lbyy						Lateral
9	M9	C4	3			Lbyy						Lateral
10	M10	C4	1.5			Lbyy						Lateral
11	M11	C4	1.5			Lbyy						Lateral
12	M12	Antenna Mast	4									Lateral

Member Primary Data

	Label	I Joint	J Joint	K Joint Rotate(.	Section/Shape	Type	Design List	Material	Design
1	M1	N5	N1		Post	Column	Pipe	A53 Grade B	Typical
2	M2	N6	N2		Post	Column	Pipe	A53 Grade B	Typical
3	M3	N7	N3		Post	Column	Pipe	A53 Grade B	Typical
4	M4	N8	N4		Post	Column	Pipe	A53 Grade B	Typical
5	M5	N7	N8	90	C10	Beam	Channel	A36 Gr.36	Typical
6	M6	N8	N6	90	C10	Beam	Channel	A36 Gr.36	Typical
7	M7	N6	N5	90	C10	Beam	Channel	A36 Gr.36	Typical
8	M8	N5	N7	90	C10	Beam	Channel	A36 Gr.36	Typical
9	M9	N11	N12	90	C4	Beam	Channel	A36 Gr.36	Typical
10	M10	N10	N13	90	C4	Beam	Channel	A36 Gr.36	Typical
11	M11	N13	N9	90	C4	Beam	Channel	A36 Gr.36	Typical
12	M12	N13	N14		Antenna Mast	Column	Pipe	A53 Grade B	Typical

Joint Coordinates and Temperatures

	Label	X [ft]	Y [ft]	Z [ft]	Temp [F]	Detach From Diap
1	N1	0	0	0	0	
2	N2	3	0	0	0	
3	N3	0	0	3	0	
4	N4	3	0	3	0	
5	N5	0	2.5	0	0	
6	N6	3	2.5	0	0	
7	N7	0	2.5	3	0	
8	N8	3	2.5	3	0	
9	N9	1.5	2.5	0	0	



: Centek Engineering

Company Designer Job Number

: 22105.05 Model Name : Mystic SC1 Sept 13, 2022 2:51 PM Checked By: CFC

Joint Coordinates and Temperatures (Continued)

	Label	X [ft]	Y [ft]	Z [ft]	Temp [F]	Detach From Diap
10	N10	1.5	2.5	3	0	
11	N11	0	2.5	1.5	0	
12	N12	3	2.5	1.5	0	
13	N13	1.5	2.5	1.5	0	
14	N14	1.5	6.5	1.5	0	

Joint Boundary Conditions

	Joint Label	X [k/in]	Y [k/in]	Z [k/in]	X Rot.[k-ft/rad]	Y Rot.[k-ft/rad]	Z Rot.[k-ft/rad]
1	N3	Reaction	Reaction	Reaction		Reaction	
2	N4	Reaction	Reaction	Reaction		Reaction	
3	N1	Reaction	Reaction	Reaction		Reaction	
4	N2	Reaction	Reaction	Reaction		Reaction	

Member Point Loads (BLC 2 : Weight of Equipment)

	Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]
1	M12	Υ	03	4
2	M12	Υ	075	2

Member Distributed Loads

Member Label	Direction	Start Magnitude[k/ft,F,ksf]	End Magnitude[k/ft,F,kStart Location[ftEnd Location[ft,
		No Data to Print	

Basic Load Cases

	BLC Description	Category	X Gra	Y Gra	Z Gra	Joint	Point	Distrib.	.Area(Surfa
1	Self Weight	DL		-1						
2	Weight of Equipment	DL					2			
3	Wind X-Direction	WLX								
4	Wind Z-Direction	WLZ								

Load Combinations

	Description	So	P	S I	BLC	Fac	.BLC	Fac	BLC	Fac	BLC	Fac	BLC	Fac	.BLC	Fac	BLC	Fac	.BLC	Fac	.BLC	Fac	BLC	Fac
1	IBC 16-8	Yes	Υ		DL	1																		
2	IBC 16-9	Yes	Υ		DL	1	LL	1	LLS	1														
3	IBC 16-12 (a) (a)	Yes	Υ		DL	1	W	.6																
4	IBC 16-12 (a) (b)	Yes	Υ		DL	1	W	.6																
5	IBC 16-12 (a) (c)	Yes	Υ		DL	1	W	6																
6	IBC 16-12 (a) (d)	Yes	Υ		DL	1	W	6																
7	IBC 16-13 (a) (a)	Yes	Υ		DL	1	W	.45	LL	.75	LLS	.75												
8	IBC 16-13 (a) (b)	Yes	Υ		DL	1	W	.45	LL	.75	LLS	.75												
9	IBC 16-13 (a) (c)	Yes	Υ		DL	1	W	45	LL	.75	LLS	.75												
10	IBC 16-13 (a) (d)	Yes	Υ		DL	1	W	45	LL	.75	LLS	.75												
11	IBC 16-15 (a)	Yes	Υ		DL	.6	W	.6																
12	IBC 16-15 (b)	Yes	Υ		DL	.6	W	.6																
13	IBC 16-15 (c)	Yes	Υ		DL	.6	W	6																



: Centek Engineering

Company Designer Job Number

: 22105.05 Model Name : Mystic SC1 Sept 13, 2022 2:51 PM Checked By: CFC

Load Combinations (Continued)

Description	So	P	S B	BLC F	acB	LC Fa	acBLC	Fac	.BLC	Fac	.BLC	Fac	BLC	Fac	BLC	Fac	.BLC	Fac	.BLC	Fac	BLC	Fac
14 IBC 16-15 (d)	Yes	Υ		DL	.6 ۷	V	.6															

Envelope Joint Reactions

	Joint		X [k]	LC	Y [k]	LC	Z [k]	LC	MX [k-ft]	LC	MY [k-ft]	LC	MZ [k-ft]	LC
1	N3	max	.009	10	.108	10	005	14	0	14	0	14	0	14
2		min	.005	11	.065	11	009	1	0	1	0	1	0	1
3	N4	max	005	14	.108	10	005	14	0	14	0	14	0	14
4		min	009	1	.065	11	009	1	0	1	0	1	0	1
5	N1	max	.009	10	.108	10	.009	10	0	14	0	14	0	14
6		min	.005	11	.065	11	.005	11	0	1	0	1	0	1
7	N2	max	005	14	.108	10	.009	10	0	14	0	14	0	14
8		min	009	1	.065	11	.005	11	0	1	0	1	0	1
9	Totals:	max	0	14	.431	10	0	14						
10		min	0	1	.259	11	0	1						

Envelope Joint Displacements

	Joint		X [in]	LC	Y [in]	LC	Z [in]	LC	X Rotation [rad]	LC	Y Rotation [rad]	LC	Z Rotation [rad]	LC
1	N1	max	0	14	0	14	0	14	-1.869e-05	14	0	14	3.115e-05	10
2		min	0	1	0	1	0	1	-3.115e-05	1	0	1	1.869e-05	11
3	N2	max	0	14	0	14	0	14	-1.869e-05	14	0	14	-1.869e-05	14
4		min	0	1	0	1	0	1	-3.115e-05	1	0	1	-3.115e-05	1
5	N3	max	0	14	0	14	0	14	3.115e-05	10	0	14	3.115e-05	10
6		min	0	1	0	1	0	1	1.869e-05	11	0	1	1.869e-05	11
7	N4	max	0	14	0	14	0	14	3.115e-05	10	0	14	-1.869e-05	14
8		min	0	1	0	1	0	1	1.869e-05	11	0	1	-3.115e-05	1
9	N5	max	0	10	0	14	0	10	6.459e-05	10	0	14	-3.875e-05	14
10		min	0	11	0	1	0	11	3.875e-05	11	0	1	-6.459e-05	1
11	N6	max	0	14	0	14	0	10	6.459e-05	10	0	14	6.459e-05	10
12		min	0	1	0	1	0	11	3.875e-05	11	0	1	3.875e-05	11
13	N7	max	0	10	0	14	0	14	-3.875e-05	14	0	14	-3.875e-05	14
14		min	0	11	0	1	0	1	-6.459e-05	1	0	1	-6.459e-05	1
15	N8	max	0	14	0	14	0	14	-3.875e-05	14	0	14	6.459e-05	10
16		min	0	1	0	1	0	1	-6.459e-05	1	0	1	3.875e-05	11
17	N9	max	0	14	0	14	0	10	2.133e-04	10	0	14	0	14
18		min	0	1	0	1	0	11	1.28e-04	11	0	1	0	1
19	N10	max	0	14	0	14	0	14	-1.28e-04	14	0	14	0	14
20		min	0	1	0	1	0	1	-2.133e-04	1	0	1	0	1
21	N11	max	0	10	0	14	0	14	0	14	0	14	-1.28e-04	14
22		min	0	11	0	1	0	1	0	1	0	1	-2.133e-04	1
23	N12	max	0	14	0	14	0	14	0	14	0	14	2.133e-04	10
24		min	0	1	0	1	0	1	0	1	0	1	1.28e-04	11
25	N13	max	0	14	003	14	0	14	0	14	0	14	0	14
26		min	0	1	005	1	0	1	0	1	0	1	0	1
27	N14	max	0	14	003	14	0	14	0	14	0	14	0	14
28		min	0	1	005	1	0	1	0	1	0	1	0	1




Company Designer Job Number

: Centek Engineering

: 22105.05 Model Name : Mystic SC1 Sept 13, 2022 2:51 PM Checked By: CFC

Envelope AISC 15th(360-16): ASD Steel Code Checks

	Memb	Shape	Code Check	L	LC	ShL	Dir	Pnc/o	Pnt/o	Mnyy/om [k-ft]	Mn	Cb	Eqn
1	M1	PIPE_2.5X	.011	0	10	.001 0		41.746	44.012	3.091	3.091	1	.H1
2	M2	PIPE_2.5X	.011	0	10	.001 0		41.746	44.012	3.091	3.091	1	.H1
3	M3	PIPE_2.5X	.011	0	10	.001 0		41.746	44.012	3.091	3.091	1	.H1
4	M4	PIPE_2.5X	.011	0	10	.001 0		41.746	44.012	3.091	3.091	1	.H1
5	M5	C10X15.3	.013	0	10	.006 1	Z	84.408	96.575	3.319	28	1	.H1
6	M6	C10X15.3	.013	0	10	.006 1	Z	84.408	96.575	3.319	28	1	.H1
7	M7	C10X15.3	.013	0	10	.006 1	Z	84.408	96.575	3.319	28	1	.H1
8	M8	C10X15.3	.013	3	10	.006 1	Z	84.408	96.575	3.319	28	1	.H1
9	M9	C4X7.25	.039	1.5	10	.003 3	Z	32.618	45.916	.969	4.913	1	H1
10	M10	C4X7.25	.039	1.5	10	.003 0	Z	42.154	45.916	.969	5.102	1	H1
11	M11	C4X7.25	.039	0	10	.003 1.5	Z	42.154	45.916	.969	5.102	1	H1
12	M12	PIPE_3.0	.003	0	10	.000 0		39.822	43.383	3.825	3.825	1	H1





EAST > North East > New England > New England West > MYSTIC SC1CT

RF Submit by: Stevens, Wesley - wesley.stevens@verizonwireless.com - 3/30/2023, 7:38:58 AM

EE Submit by: Driscoll, Janet - janet.driscoll@verizonwireless.com - 7/19/2022, 8:23:55 AM

Project Details
FUZE Project ID: 16774002
Project Name: Radio Swap
Project Alt Name: MYSTIC SC 1 CT - NENG_SC_ESNAP
Project Type: Modification
Modification Type: RF
Designed Sector Carrier 4G: 2
Designed Sector Carrier 5G: N/A
Additional Sector Carrier 4G: N/A
Additional Sector Carrier 5G: N/A
FP Solution Type & Tech Type: MODIFICATION;4G_700,4G_850,4G_Radio Swap
Carrier Aggregation: false
MPT Id:
eCIP-0: false
Suffix: Rev1_20230330

Location Information	
Site ID: 3400790	
E-NodeB ID: 064405,064439	
PSLC: 467653	
Switch Name: Wallingford 1	
Tower Owner:	
Tower Type: Rooftop	
Site Type: SMALL-CELL	
Site Sub Type: SPOKE	
Street Address: 212 Deans Mill Rd	
City: Stonington	
State: CT	
Zip Code: 06378	
County: New London	
Latitude: 41.37148056 / 41° 22' 17.33" N	
Longitude: -71.92881611 / 71° 55' 43.738" W	

RFDS Project Scope: Per ESNAP direction, changing to 700/850

Swap antenna to HTXCWW63111414F Swap RRH to SS dual-band (700/850)

Rev1_20230330: updated RRH to ORAN

Rev0_20220223: initial design

Antenna Summary

Added													
700	850	AWS	Make	Model	Centerline	Tip Height	Azimuth	RET	4xRx	Inst. Type	Quantity	Item ID	
LTE	LTE		AMPHENOL	HTXCWW63111414F	24.9	25.9	295(04)	false	false	PHYSICAL	1		
Remove	d												
700	850	AWS	Make	Model	Centerline	Tip Height	Azimuth	RET	4xRx	Inst. Type	Quantity	Item ID	
		LTE	ANDREW	HBX-6513DS-A1M	26.6	27.7	295(04)	false	false	PHYSICAL	1		
Retaine	d												
700	850	AWS	Make	Model	Centerline	Tip Height	Azimuth	RET	4xRx	Inst. Type	Quantity	Item ID	
								No data	available.				

Added: 1	Removed: 1	Retained: 0

Equipment Summary

Added											
Equipment Type	Location	700	850	AWS	Make	Model	Cable Length	Cable Size	Install Type	Quantity	Item ID
Kit	Tower				GEMINI	1600131299A			PHYSICAL	1	00000001900078
Kit	Tower				GEMINI	1600270671A			PHYSICAL	1	00000001900057
Kit	Tower				QUADELECTRIC	F113CGRS0101FLF025			PHYSICAL	2	00000001900038
Kit	Tower				QUADELECTRIC	FLI0020T010046M010			PHYSICAL	2	00000001900038
Kit	Tower				QUADELECTRIC	SAM-CBRS-BRT-NID			PHYSICAL	1	00000001900005
Kit	Tower				QUADELECTRIC	TRAT303H1B1J00F050			PHYSICAL	8	00000001900028
Kit	Tower				QUADELECTRIC	UXP-4MT-12S			PHYSICAL	8	00000001900167
Kit	Tower				QUADELECTRIC	WPS-4F			PHYSICAL	8	00000001900166
Kit	Tower				QUADELECTRIC	WPS-N-4S			PHYSICAL	8	00000001900166
Kit	Tower				QUADELELECTRIC	V3000			PHYSICAL	1	00000001900059
Other	Tower				SAMSUNGELE- 001	SLS-BB1150EDEX			PHYSICAL	1	00000001900167
RRU	Tower	LTE	LTE		Samsung	B5/B13 RRH ORAN (RF4440d-13A)			PHYSICAL	1	
Removed											
Equipment Type	Location	700	850	AWS	Make	Model	Cable Length	Cable Size	Install Type	Quantity	Item ID
RRU	Tower			LTE	Nokia	UHIC B4 RRH 2x60-4R			PHYSICAL	1	
Retained											
Equipment Type	Location	700	850	AWS	Make	Model	Cable Length	Cable Size	Install Type	Quantity	Item ID
								No data avail	able.		

Service Info

Sector O4	700 MHz LTE	0001	
Admental Model 1975			
Col. Pixode B ID		295	
Antenna Model Antenna Model Antenna CanterlinaMen Antenna CanterlinaMen Antenna CanterlinaMen Antenna CanterlinaMen Medanical Down-Till. Ceal Republicary Power Republicary Power Republicary Power Republicary Power Republicary Republic			
Antenna Make Antenna Center InterF1 Mechanical Down Till Deal Below Till Height Below Till Height Below Till Height Till Height Till Height Till Height Total ERP (W) Total ERP (W) The Mill Make Brill Make Brill Make Brill Model Brill Make Brill Model Brill Fine Brill Antenna Model Antenna Model Brill Mod			
Antenna Centerins(FB) Mechanical Down-Till (Deba) Description (Down-Till (Dow			
Antenna Centerins(FB) Mechanical Down-Till (Deba) Description (Down-Till (Dow	Antenna Make	AMPHENOL	
Mechanical Down-Titt(Degs)			
Electrical Down-Till	Mechanical Down-Tilt(Deg.)	0	
Tip Height 25,9	Electrical Down-Tilt	5	
Regulatory Power 1,22	Tip Height		
DLEARECN 5230		4.22	
Total ERP (W) TMA Make TMA Model RRU Model RRU Model RRU Model RRU Sector Fosition Transmitter id Sector Azimuth Azimuth Antenna Model Antenna	DLEARFCN	5230	
Total ERP (W) TMA Make TMA Model RRU Model RRU Model RRU Model RRU Sector Fosition Transmitter id Sector Azimuth Azimuth Antenna Model Antenna	Channel Randwidth(MHz)	10	
TMA Made			
TMA Model		55,62	
RRU Make RRU Model B5/B13 RRU FAAN (RF4440d-13A) B5/B13 RRU FAAN (RF4440d-13A) RRU Model B5/B13 RRU FAAN (RF4440d-13A) RRU FAAN (RF444			
RRU Model Number of Tx, Rx Lines 2.2	RRU Make	Samsung	
Number of Tx, Rx Lines		B5/B13 RRH ORAN (RF4440d-13A)	
Position Tansmitter Id			
Transmitter Id Source ATOLL API \$50 MHz LTE \$50 MHz L			
Source Source Sector S		12436008	
Sector Azimuth Sector Azimuth Sector Azimuth Sector			
Sector	OFO MULTITE		
Azimuth 295 Cell / ENode B ID 064439 Antenna Model HTXCWW63111414F Antenna Genterline(Ft) 24,9 Mechanical Down-Tilt (Deg.) 0 Electrical Down-Tilt 5 Tip Height 25,9 Regulatory Power 8.45 DLEARFCN 2450 Channel Bandwidth(MHz) 10 Total ERP (W) 38.02 TMA Make Samsung RRU Make Samsung RRU Model 85/B13 RRH ORAN (RF4440d-13A) Number of 1x, Rx Lines 2,2 Position 12436009		0001	
Cell / ENode B ID 064439 Antenna Model HTXCWW63111414F Antenna Make AMPHENOL Antenna Center-line(Ft) 24,9 Mechanical Down-Tilt (Deg.) 0 Electrical Down-Tilt 5 Tip Height 25,9 Regulatory Power 8,45 DLEARFCN 2450 Channel Bandwidth(MHz) 10 Total ERP (W) 38.02 TMA Make 38.02 TMA Model Samsung RRU Make B5/B13 RRH ORAN (RF4440d-13A) RRU Model 85/B13 RRH ORAN (RF4440d-13A) Number of Tx, Rx Lines 2,2 Position 12436009			
Antenna Make Antenna Make Antenna Centerline(Ft) Antenna Centerline(Ft) Mechanical Down-Tilt 0 Electrical Down-Til	Sector	04	
Antenna Make Antenna Centerline(Ft) Antenna Centerline(Ft) Mechanical Down-Tilt(Deg.) Electrical Down-Tilt Tip Height Segulatory Power Begulatory Power Begulatory Power Begulatory Power Begulatory Fower Begul	Sector Azimuth	04 295	
Antenna Centerline(Ft) Mechanical Down-Tilt(Deg.) Electrical Down-Tilt Electrical Dow	Sector Azimuth Cell / ENode B ID	04 295 064439	
Antenna Centerline(Ft) Mechanical Down-Tilt(Deg.) Electrical Down-Tilt Electrical Dow	Sector Azimuth Cell / ENode B ID	04 295 064439	
Mechanical Down-Tilt(Deg.) 0 Electrical Down-Tilt 5 Tip Height 25.9 Regulatory Power 8.45 DLEARFCN 2450 Channel Bandwidth (MHz) 10 Total ERP (W) 38.02 TMA Make 5 TMA Model Samsung RRU Model B5/B13 RRH ORAN (RF4440d-13A) Number of Tx, Rx Lines 2,2 Position 12436009	Sector Azimuth Cell / ENode B ID Antenna Model	04 295 064439 HTXCWW63111414F	
Flectrical Down-Tilt	Sector Azimuth Cell / ENode B ID Antenna Model Antenna Make	04 295 064439 HTXCWW63111414F	
Tip Height	Sector Azimuth Cell / ENode B ID Antenna Model Antenna Make Antenna Centerline(Ft)	04 295 064439 HTXCWW63111414F AMPHENOL 24.9	
Regulatory Power 8.45 DLEARFCN 2450 Channel Bandwidth(MHz) 10 Total ERP (W) 38.02 TMA Make Samsung RRU Make Samsung RRU Model B5/B13 RRH ORAN (RF4440d-13A) Number of Tx, Rx Lines 2,2 Position 12436009	Sector Azimuth Cell / ENode B ID Antenna Model Antenna Make Antenna Centerline(Ft) Mechanical Down-Tilt(Deg.)	04 295 064439 HTXCWW63111414F AMPHENOL 24.9 0	
DLEARFCN	Sector Azimuth Cell / ENode B ID Antenna Model Antenna Make Antenna Centerline(Ft) Mechanical Down-Tilt(Deg.) Electrical Down-Tilt Tip Height	04 295 064439 HTXCWW63111414F AMPHENOL 24.9 0 5	
Total ERP (W) TMA Make TMA Model RRU Make RRU Model RRU Model Number of Tx, Rx Lines Position Transmitter Id 12436009	Sector Azimuth Cell / ENode B ID Antenna Model Antenna Make Antenna Centerline(Ft) Mechanical Down-Tilt(Deg.) Electrical Down-Tilt Tip Height	04 295 064439 HTXCWW63111414F AMPHENOL 24.9 0 5 25.9	
Total ERP (W) TMA Make TMA Model RRU Make RRU Model RRU Model Number of Tx, Rx Lines Position Transmitter Id 12436009	Sector Azimuth Cell / ENode B ID Antenna Model Antenna Make Antenna Centerline(Ft) Mechanical Down-Tilt(Deg.) Electrical Down-Tilt Tip Height Regulatory Power	04 295 064439 HTXCWW63111414F AMPHENOL 24.9 0 5 25.9 8.45	
TMA Make TMA Model RRU Make RRU Model B5/B13 RRH ORAN (RF4440d-13A) Number of Tx, Rx Lines Position Transmitter Id 12436009	Sector Azimuth Cell / ENode B ID Antenna Model Antenna Make Antenna Centerline(Ft) Mechanical Down-Tilt(Deg.) Electrical Down-Tilt Tip Height Regulatory Power DLEARFCN	295 064439 HTXCWW63111414F AMPHENOL 24.9 0 5 25.9 8.45 2450	
## TMA Model ## RRU Make ## RRU Model ## RRU Model ## B5/B13 RRH ORAN (RF4440d-13A) ## Number of Tx, Rx Lines ## Position ## Transmitter Id ## 12436009	Sector Azimuth Cell / ENode B ID Antenna Model Antenna Make Antenna Centerline(Ft) Mechanical Down-Tilt(Deg.) Electrical Down-Tilt Tip Height Regulatory Power DLEARFCN Channel Bandwidth(MHz)	295 064439 HTXCWW63111414F AMPHENOL 24.9 0 5 25.9 8.45 2450	
RRU Make Samsung RRU Model B5/B13 RRH ORAN (RF4440d-13A) Number of Tx, Rx Lines 2,2 Position Transmitter Id 12436009	Sector Azimuth Cell / ENode B ID Antenna Model Antenna Make Antenna Centerline(Ft) Mechanical Down-Tilt(Deg.) Electrical Down-Tilt Tip Height Regulatory Power DLEARFCN Channel Bandwidth(MHz) Total ERP (W)	295 064439 HTXCWW63111414F AMPHENOL 24.9 0 5 25.9 8.45 2450	
RRU Model B5/B13 RRH ORAN (RF4440d-13A) Number of Tx, Rx Lines 2,2 Position Transmitter Id 12436009 12436009	Sector Azimuth Cell / ENode B ID Antenna Model Antenna Make Antenna Centerline(Ft) Mechanical Down-Tilt(Deg.) Electrical Down-Tilt Tip Height Regulatory Power DLEARFCN Channel Bandwidth(MHz) Total ERP (W) TMA Make	295 064439 HTXCWW63111414F AMPHENOL 24.9 0 5 25.9 8.45 2450	
Number of Tx, Rx Lines Position Transmitter Id 12436009	Sector Azimuth Cell / ENode B ID Antenna Model Antenna Make Antenna Centerline(Ft) Mechanical Down-Tilt(Deg.) Electrical Down-Tilt Tip Height Regulatory Power DLEARFCN Channel Bandwidth(MHz) Total ERP (W) TMA Make TMA Model	04 295 064439 HTXCWW63111414F AMPHENOL 24.9 0 5 25.9 8.45 2450 10 38.02	
Position Transmitter Id 12436009	Sector Azimuth Cell / ENode B ID Antenna Model Antenna Make Antenna Centerline(Ft) Mechanical Down-Tilt(Deg.) Electrical Down-Tilt Tip Height Regulatory Power DLEARFCN Channel Bandwidth(MHz) Total ERP (W) TMA Make TMA Model RRU Make	04 295 064439 HTXCWW63111414F AMPHENOL 24.9 0 5 25.9 8.45 2450 10 38.02	
Transmitter Id	Sector Azimuth Cell / ENode B ID Antenna Model Antenna Make Antenna Centerline(Ft) Mechanical Down-Tilt(Deg.) Electrical Down-Tilt Tip Height Regulatory Power DLEARFCN Channel Bandwidth(MHz) Total ERP (W) TMA Make TMA Model RRU Make RRU Model	04 295 064439 HTXCWW63111414F AMPHENOL 24.9 0 5 25.9 8.45 2450 10 38.02 Samsung B5/B13 RRH ORAN (RF4440d-13A)	
	Sector Azimuth Cell / ENode B ID Antenna Model Antenna Make Antenna Centerline(Ft) Mechanical Down-Tilt(Deg.) Electrical Down-Tilt Tip Height Regulatory Power DLEARFCN Channel Bandwidth(MHz) Total ERP (W) TMA Make TMA Model RRU Make RRU Model Number of Tx, Rx Lines	04 295 064439 HTXCWW63111414F AMPHENOL 24.9 0 5 25.9 8.45 2450 10 38.02 Samsung B5/B13 RRH ORAN (RF4440d-13A)	
	Sector Azimuth Cell / ENode B ID Antenna Model Antenna Make Antenna Centerline(Ft) Mechanical Down-Tilt(Deg.) Electrical Down-Tilt Tip Height Regulatory Power DLEARFCN Channel Bandwidth(MHz) Total ERP (W) TMA Make TMA Model RRU Model Number of Tx, Rx Lines Position	04 295 064439 HTXCWW63111414F AMPHENOL 24.9 0 5 25.9 8.45 2450 10 38.02 Samsung B5/B13 RRH ORAN (RF4440d-13A) 2,2	

2100 MHz LTE Sector Azimuth Cell / ENode B ID Antenna Model Antenna Make Antenna Centerline(Ft) Mechanical Down-Tilt(Deg.) Electrical Down-Tilt	04 295 064439 HBX-6513DS-A1M ANDREW 26.6 0
Azimuth Cell / ENode B ID Antenna Model Antenna Make Antenna Centerline(Ft) Mechanical Down-Tilt(Deg.)	295 064439 HBX-6513DS-A1M ANDREW 26.6 0
Cell / ENode B ID Antenna Model Antenna Make Antenna Centerline(Ft) Mechanical Down-Tilt(Deg.)	064439 HBX-6513DS-A1M ANDREW 26.6 0
Antenna Model Antenna Make Antenna Centerline(Ft) Mechanical Down-Tilt(Deg.)	HBX-6513DS-A1M ANDREW 26.6 0
Antenna Centerline(Ft) Mechanical Down-Tilt(Deg.)	ANDREW 26.6 0
Antenna Centerline(Ft) Mechanical Down-Tilt(Deg.)	26.6 0
Mechanical Down-Tilt(Deg.)	0
	0
Electrical Down-Tilt	•
	0
Tip Height	27.7
Regulatory Power	111.33
DLEARFCN	2050
Channel Bandwidth(MHz)	20
Total ERP (W)	1221.52
TMA Make	
TMA Model	
RRU Make	Nokia
RRU Model	UHIC B4 RRH 2x60-4R
Number of Tx, Rx Lines	2,2
Position	
Transmitter Id	1962387
Source	ATOLL_API


Callsigns Per Antenna

Sector	Antenna Make	Antenna Model		Tip			Mech	Gain		Regulatory	Callsigns							
			Height AGL	Height	(TN)	Tilt	Tilt		Width	Power	700	850	1900	2100	28 GHz	31 GHz	39 GHz	
						No	data availa	ble.										

Callsigns

Callsign	Market	Radio Code	Market Number	Block	State	County	Licensee Name	Wholly Owned	Total MHZ	Freq Range 1	Freq Range 2	Freq Range 3	Freq Range 4	Regulatory Power	Threshold (W)	POPs /Sq Mi	Status	Action	Approved for Insvc
WQJQ689	Northeast	wu	REA001	с	СТ	New London	Cellco Partnership	Yes	22.000	746.000- 757.000	776.000- 787.000	.000000	.000000	4.22	1000	403.90	Active	added	Yes
KNKA745	New London- Norwich, CT	CL	CMA154	A	СТ	New London	Cellco Partnership	Yes	25.000	824.000- 835.000	869.000- 880.000	845.000- 846.500	890.000- 891.500	8.45 - PSD	400	403.90	Active	added	Yes
WQGD494	New London- Norwich, CT	AW	CMA154	A	ст	New London	Cellco Partnership	Yes	20.000	1710.000- 1720.000	2110.000- 2120.000	.000000	.000000		1640	403.90	Active	removed	Yes
WQGA906	New York-No. New JerLong Island, NY-NJ-CT-PA-MA-	AW	BEA010	В	СТ	New London	Cellco Partnership	Yes	20.000	1720.000- 1730.000	2120.000- 2130.000	.000000	.000000		1640	403.90	Active	removed	Yes
WQDU931	New London- Norwich, CT	cw	BTA319	С	СТ	New London	Cellco Partnership	Yes	10.000	1900.000- 1905.000	1980.000- 1985.000	.000000	.000000		1640	403.90	Active		Yes
WQEM954	New London- Norwich, CT	cw	BTA319	С	СТ	New London	Cellco Partnership	Yes	10.000	1895.000- 1900.000	1975.000- 1980.000	.000000	.000000		1640	403.90	Active		Yes
KNLH263	New London- Norwich, CT	cw	BTA319	F	СТ	New London	Cellco Partnership	Yes	10.000	1890.000- 1895.000	1970.000- 1975.000	.000000	.000000		1640	403.90	Active		Yes
WREE835	C09011 - New London, CT	UU	C09011	L1	СТ	New London	Cellco Partnership	Yes	425.000	27500.000- 27925.000	.000000	.000000	.000000			403.90	Active		Yes
WREE836	C09011 - New London, CT	UU	C09011	L2	СТ	New London	Cellco Partnership	Yes	425.000	27925.000- 28350.000	.000000	.000000	.000000			403.90	Active		Yes
WRHD609	New York, NY	UU	PEA001	M1	СТ	New London	Cellco Partnership	Yes	100.000	37600.000- 37700.000	.000000	.000000	.000000			403.90	Active		Yes
WRHD610	New York, NY	UU	PEA001	M10	СТ	New London	Cellco Partnership	Yes	100.000	38500.000- 38600.000	.000000	.000000	.000000			403.90	Active		Yes
WRHD611	New York, NY	UU	PEA001	M2	СТ	New London	Cellco Partnership	Yes	100.000	37700.000- 37800.000	.000000	.000000	.000000			403.90	Active		Yes
WRHD612	New York, NY	UU	PEA001	МЗ	СТ	New London	Cellco Partnership	Yes	100.000	37800.000- 37900.000	.000000	.000000	.000000			403.90	Active		Yes
WRHD613	New York, NY	UU	PEA001	M4	СТ	New London	Cellco Partnership	Yes	100.000	37900.000- 38000.000	.000000	.000000	.000000			403.90	Active		Yes
WRHD614	New York, NY	UU	PEA001	M5	СТ	New London	Cellco Partnership	Yes	100.000	38000.000- 38100.000	.000000	.000000	.000000			403.90	Active		Yes
WRHD615	New York, NY	UU	PEA001	M6	СТ	New London	Cellco Partnership	Yes	100.000	38100.000- 38200.000	.000000	.000000	.000000			403.90	Active		Yes
WRHD616	New York, NY	UU	PEA001	M7	СТ	New London	Cellco Partnership	Yes	100.000	38200.000- 38300.000	.000000	.000000	.000000			403.90	Active		Yes
WRHD617	New York, NY	UU	PEA001	M8	СТ	New London	Cellco Partnership	Yes	100.000	38300.000- 38400.000	.000000	.000000	.000000			403.90	Active		Yes
WRHD618	New York, NY	UU	PEA001	М9	СТ	New London	Cellco Partnership	Yes	100.000	38400.000- 38500.000	.000000	.000000	.000000			403.90	Active		Yes
WRHD619	New York, NY	UU	PEA001	N1	СТ	New London	Cellco Partnership	Yes	100.000	38600.000- 38700.000	.000000	.000000	.000000			403.90	Active		Yes
WRNE581	New York, NY	РМ	PEA001	A1	СТ	New London	Cellco Partnership	Yes	20.000	3700.000- 3720.000	.000000	.000000	.000000		1640	403.90	Active		Yes

WRNE582	New York, NY	PM	PEA001	A2	СТ	New London	Cellco Partnership	Yes	20.000	3720.000- 3740.000	.000000	.000000	.000000	1640	403.90	Active	Yes
WRNE583	New York, NY	PM	PEA001	АЗ	СТ	New London	Cellco Partnership	Yes	20.000	3740.000- 3760.000	.000000	.000000	.000000	1640	403.90	Active	Yes
WRNE584	New York, NY	PM	PEA001	A 4	СТ	New London	Cellco Partnership	Yes	20.000	3760.000- 3780.000	.000000	.000000	.000000	1640	403.90	Active	No
WRNE585	New York, NY	PM	PEA001	A5	СТ	New London	Cellco Partnership	Yes	20.000	3780.000- 3800.000	.000000	.000000	.000000	1640	403.90	Active	No
WRNE586	New York, NY	PM	PEA001	B1	СТ	New London	Cellco Partnership	Yes	20.000	3800.000- 3820.000	.000000	.000000	.000000	1640	403.90	Active	No
WRNE587	New York, NY	PM	PEA001	B2	СТ	New London	Cellco Partnership	Yes	20.000	3820.000- 3840.000	.000000	.000000	.000000	1640	403.90	Active	No
WRNE588	New York, NY	PM	PEA001	В3	СТ	New London	Cellco Partnership	Yes	20.000	3840.000- 3860.000	.000000	.000000	.000000	1640	403.90	Active	No



A R R R വ ∪ മ ∢ ഉ




verizon

(203) 488-0580 (203) 488-8587 Fax 63-2 North Branford I Branford, CT 06405

212 DEANS MILL ROAD STONINGTON, CT 06378 MYSTIC SC1

09/12/2022 AS SHOWN



TJR DMD DMD A R R R _ O O B ▼ 2

verizon

(203) 488-0580 (203) 488-8587 Fax 63-2 North Branford I Branford, CT 06405

212 DEANS MILL ROAD STONINGTON, CT 06378 MYSTIC SC1

09/12/2022 SCALE: AS SHOWN