



**STATE OF CONNECTICUT
CONNECTICUT SITING COUNCIL**

Ten Franklin Square, New Britain, CT 06051
Phone: (860) 827-2935 Fax: (860) 827-2950
E-Mail: siting.council@ct.gov
Web Site: portal.ct.gov/csc

VIA ELECTRONIC MAIL

January 11, 2023

Michael Jones
President
M+K Development
140 Beach 137th Street
Rockaway Beach, NY 11694
mjones@mandkdevelopment.com

RE: TS-DISH-138-221206 – Dish Wireless, LLC request for an order to approve tower sharing at an existing telecommunications facility located at 200 Oronoque Lane, Stratford, Connecticut.

Dear Michael Jones:

The Connecticut Siting Council (Council) is in receipt of your correspondence of January 10, 2023 submitted in response to the Council's December 20, 2022 notification of an incomplete request for tower sharing with regard to the above-referenced matter.

The submission renders the request for tower sharing complete and the Council will process the request in accordance with the Federal Communications Commission 60-day timeframe.

Thank you for your attention and cooperation.

Sincerely,

Melanie A. Bachman
Executive Director

MAB/IN/lm

L.M.



January 6, 2023

Melanie A. Bachman
Zoning Officer
Connecticut Siting Council
10 Franklin Square
New Britain, CT 06051

RE: Request of DISH Wireless LLC for an Order to Approve the Shared Use of an Existing Tower – NJJER02052B - **TS-DISH-138-221206**
200 Oronoque Lane, Stratford, CT 06614

Dear Ms. Bachman:

In response to your letter dated 12/20/2022 related to the incomplete application submitted and pursuant to Connecticut General Statutes (“C.G.S.”) §16-50aa, as amended, DISH Wireless LLC (“DISH”) hereby requests an approval from the Connecticut Siting Council (“Council”) to approve the shared use by DISH of an existing telecommunication tower at 200 Oronoque Lane in Stratford. We have attached the following updated documents as requested to amend our original application:

- An updated set of Construction Drawings (CD) citing the 2022 Connecticut State Building Code (CSBC).
- An updated Structural Analysis (SA) citing the 2022 CSBC or 2021 IBC.
- An updated Mount Analysis (MA) citing the 2022 CSBC or 2021 IBC.

Please review and advise if there is any other required documentation required to deem this application complete.

Sincerely,

A handwritten signature in black ink, appearing to read "Michael Jones".
Michael Jones
President, M+K Development
140 Beach 137th St
Rockaway Beach, NY 11694
732-677-8881



Amended EXHIBIT C

Construction Drawings



DISH Wireless L.L.C. SITE ID:

NJJER02052B

DISH Wireless L.L.C. SITE ADDRESS:

**200 ORONOQUE LANE
STRATFORD, CT 06614**

CONNECTICUT CODE OF COMPLIANCE

ALL WORK SHALL BE PERFORMED AND MATERIALS INSTALLED IN ACCORDANCE WITH THE CURRENT EDITIONS OF THE FOLLOWING CODES AS ADOPTED BY THE LOCAL GOVERNING AUTHORITIES. NOTHING IN THESE PLANS IS TO BE CONSTRUED TO PERMIT WORK NOT CONFORMING TO THESE CODES

CODE TYPE	CODE
BUILDING	2022 CT STATE BUILDING CODE/2015 IBC W/ CT AMENDMENTS
MECHANICAL	2022 CT STATE BUILDING CODE/2015 IMC W/ CT AMENDMENTS
ELECTRICAL	2022 CT STATE BUILDING CODE/2017 NEC W/ CT AMENDMENTS

SHEET INDEX

SHEET NO.	SHEET TITLE
T-1	TITLE SHEET
A-1	OVERALL AND ENLARGED SITE PLAN
A-2	ELEVATION, ANTENNA LAYOUT AND SCHEDULE
A-3	EQUIPMENT PLATFORM AND H-FRAME DETAILS
A-4	EQUIPMENT DETAILS
A-5	EQUIPMENT DETAILS
A-6	EQUIPMENT DETAILS
E-1	ELECTRICAL/FIBER ROUTE PLAN AND NOTES
E-2	ELECTRICAL DETAILS
E-3	ELECTRICAL ONE-LINE, FAULT CALCS & PANEL SCHEDULE
G-1	GROUNDING PLANS AND NOTES
G-2	GROUNDING DETAILS
G-3	GROUNDING DETAILS
RF-1	RF CABLE COLOR CODE
GN-1	LEGEND AND ABBREVIATIONS
GN-2	RF SIGNAGE
GN-3	GENERAL NOTES
GN-4	GENERAL NOTES
GN-5	GENERAL NOTES

SCOPE OF WORK

THIS IS NOT AN ALL INCLUSIVE LIST. CONTRACTOR SHALL UTILIZE SPECIFIED EQUIPMENT PART OR ENGINEER APPROVED EQUIVALENT. CONTRACTOR SHALL VERIFY ALL NEEDED EQUIPMENT TO PROVIDE A FUNCTIONAL SITE. THE PROJECT GENERALLY CONSISTS OF THE FOLLOWING:

TOWER SCOPE OF WORK:

- INSTALL (3) PROPOSED PANEL ANTENNAS (1 PER SECTOR)
- INSTALL (1) PROPOSED ANTENNA PLATFORM MOUNT
- INSTALL PROPOSED JUMPERS
- INSTALL (6) PROPOSED RRUs (2 PER SECTOR)
- INSTALL (1) PROPOSED OVER VOLTAGE PROTECTION DEVICE (OVP)
- INSTALL (1) PROPOSED HYBRID CABLE

GROUND SCOPE OF WORK:

- INSTALL (1) PROPOSED METAL PLATFORM
- INSTALL (1) PROPOSED ICE BRIDGE
- INSTALL (1) PROPOSED PPC CABINET
- INSTALL (1) PROPOSED EQUIPMENT CABINET
- INSTALL (1) PROPOSED POWER CONDUIT
- INSTALL (1) PROPOSED TELCO CONDUIT
- INSTALL (1) PROPOSED TELCO-FIBER BOX
- INSTALL (1) PROPOSED GPS UNIT
- INSTALL (1) PROPOSED FIBER NID (IF REQUIRED)

SITE INFORMATION

PROJECT DIRECTORY

PROPERTY OWNER:	TOWN OF STRATFORD 2725 MAIN STREET STRATFORD, CT 06615	APPLICANT:	DISH Wireless L.L.C. 5701 SOUTH SANTA FE DRIVE LITTLETON, CO 80120 (303) 706-5008
TOWER TYPE:	MONPOLE	TOWER OWNER:	TOWN OF STRATFORD 2725 MAIN STREET STRATFORD, CT 06615
TOWER CO SITE ID:	N/A	SITE DESIGNER:	M+K DEVELOPMENT 140 BEACH 137TH STREET ROCKAWAY, NY 11694
TOWER APP NUMBER:	N/A	SITE ACQUISITION:	AUSTIN PAPPAS AUSTIN.PAPPAS@DISH.COM
COUNTY:	FAIRFIELD COUNTY	ZONING DISTRICT:	RS-1
LATITUDE (NAD 83):	41° 15' 5.28" N 41.251475	LONGITUDE (NAD 83):	73° 07' 1.63" W -73.117119
ZONING JURISDICTION:	CT SITING COUNCIL	CONSTRUCTION MANAGER:	OMAR ZEERBAN OMAR.ZEERBAN@DISH.COM
PARCEL NUMBER:	6020020001	OCCUPANCY GROUP:	U
RF ENGINEER:	PAWN MADAHAR PAWN.MADAHAR@DISH.COM	CONSTRUCTION TYPE:	V-B
POWER COMPANY:	UNITED ILLUMINATING	TELEPHONE COMPANY:	TBD

SITE PHOTO



UNDERGROUND SERVICE ALERT CBYD 811
UTILITY NOTIFICATION CENTER OF CONNECTICUT
(800) 922-4455
WWW.CBYD.COM

CALL 2 WORKING DAYS UTILITY NOTIFICATION PRIOR TO CONSTRUCTION

DIRECTIONS

DIRECTIONS FROM 3 ADP BLVD, NJ 07068, USA:
HEAD NORTHEAST TOWARD ADP BLVD, TURN RIGHT TOWARD CHOCATE WAY, SLIGHT RIGHT ONTO LIVINGSTON AVE, USE THE RIGHT LANE TO TAKE THE RAMP ONTO I-280 E, MERGE ONTO I-280 E, TAKE EXIT 15X AND 16E TOWARD LINCOLN TUNNEL, MERGE ONTO I-95 N TOLL ROAD, KEEP RIGHT TO STAY ON I-95 N, FOLLOW SIGNS FOR GEORGE WASHINGTON BRG/FORT LEE, KEEP RIGHT TO STAY ON I-95 N, FOLLOW SIGNS FOR US-1 W/US-9 N/GEORGE WASHINGTON BRIDGE CONTINUE ONTO US-9 N, CONTINUE ONTO I-95 LOWER LEVEL N/US-1 LOWER LEVEL N, TOLL ROAD, KEEP RIGHT TO CONTINUE ON I-95 LOWER LEVEL N/TRANS-MANHATTAN EXPWY/US-1 LOWER LEVEL N, CONTINUE STRAIGHT TO STAY ON I-95 LOWER LEVEL N/TRANS-MANHATTAN EXPWY/US-1 LOWER LEVEL N, I-95 LOWER LEVEL N/TRANS-MANHATTAN EXPWY/US-1 LOWER LEVEL N TURNS SLIGHTLY RIGHT AND BECOMES I-95 N, KEEP LEFT AT THE FORK TO STAY ON I-95 N, FOLLOW SIGNS FOR INTERSTATE 95 N/New Haven, KEEP LEFT TO STAY ON I-95 N, TAKE EXIT 27A FOR CT-25/CT-8 TOWARD TRUMBULL/WATERBURY, CONTINUE ONTO CT-25 N/CT-8 N, USE THE RIGHT 2 LANES TO TAKE THE CT-8 N EXIT TOWARD CT-15 N/SHELTON/WATERBURY, CONTINUE ONTO CT-8 N, TAKE EXIT 9 TO MERGE ONTO CT-15 N/MERRITT PKWY TOWARD CT-15, TAKE EXIT 53 FOR STATE ROUTE 110 TOWARD STRATFORD/SHELTON, USE THE LEFT LANE TO KEEP LEFT AT THE FORK AND FOLLOW SIGNS FOR SHELTON, TURN LEFT ONTO MAIN ST, TURN LEFT ONTO ORONOQUE LN, DESTINATION WILL BE ON THE RIGHT.

VICINITY MAP



GENERAL NOTES

THE FACILITY IS UNMANNED AND NOT FOR HUMAN HABITATION. A TECHNICIAN WILL VISIT THE SITE AS REQUIRED FOR ROUTINE MAINTENANCE. THE PROJECT WILL NOT RESULT IN ANY SIGNIFICANT DISTURBANCE OR EFFECT ON DRAINAGE, NO SANITARY SEWER SERVICE, POTABLE WATER, OR TRASH DISPOSAL IS REQUIRED AND NO COMMERCIAL SIGNAGE IS PROPOSED.

11"x17" PLOT WILL BE HALF SCALE UNLESS OTHERWISE NOTED

CONTRACTOR SHALL VERIFY ALL PLANS, EXISTING DIMENSIONS, AND CONDITIONS ON THE JOB SITE, AND SHALL IMMEDIATELY NOTIFY THE ENGINEER IN WRITING OF ANY DISCREPANCIES BEFORE PROCEEDING WITH THE WORK.



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



140 BEACH 137TH STREET
ROCKAWAY, NY 11694



IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:
GIN --- ---

RFDS REV #: ---

CONSTRUCTION DOCUMENTS



SUBMITTALS		
REV	DATE	DESCRIPTION
A	09/13/2022	ISSUED FOR REVIEW
0	12/21/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER
NJJER02052B

DISH Wireless L.L.C.
PROJECT INFORMATION
NJJER02052B
200 ORONOQUE LANE
STRATFORD, CT 06614

SHEET TITLE
TITLE SHEET


SHEET NUMBER
T-1



OVERALL SITE PLAN

12' 8' 4' 0 10' 20'
3/32"=1'-0"

1



AERIAL PHOTO

NO SCALE

3

dish
wireless.
5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120

MK
DEVELOPMENT
140 BEACH 137TH STREET
ROCKAWAY, NY 11694



IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:
GIN --- ---

RFDS REV #: ---

CONSTRUCTION DOCUMENTS

SUBMITTALS

REV	DATE	DESCRIPTION
A	09/13/2022	ISSUED FOR REVIEW
O	12/21/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER
NJER02052B

DISH Wireless LLC.
PROJECT INFORMATION

NJER02052B
200 ORONOQUE LANE
STRATFORD, CT 06614


SHEET TITLE
OVERALL AND ENLARGED
SITE PLAN

SHEET NUMBER

A-1

NOTES


1. CONTRACTOR SHALL FIELD VERIFY ALL DIMENSIONS.
2. ANTENNA AND MW DISH SPECIFICATIONS REFER TO ANTENNA SCHEDULE AND TO FINAL CONSTRUCTION RFDS FOR ALL RF DETAILS
3. EXISTING EQUIPMENT AND FENCE OMITTED FOR CLARITY.



PROPOSED NORTH ELEVATION

12' 8' 4' 0' 10' 20'
3/32"=1'-0"

1



ANTENNA LAYOUT

12"	6"	0	1'	2'	3'
3/4"=1'-0"					

2

SECTOR POS.	ANTENNA					TRANSMISSION CABLE	RRH			OVP
	EXISTING OR PROPOSED	MANUFACTURER - MODEL NUMBER	TECH	AZIMUTH	RAD CENTER		MANUFACTURER - MODEL NUMBER	TECH	POS.	
A1	--	--	--	--	--	(1) HIGH-CAPACITY HYBRID CABLE (141' LONG)	FUJITSU - TA08025-B605	5G	A2	RAYCAP RDIDC-9181-PF-48
A2	PROPOSED	COMMSCOPE - FFVW-65B-R2	5G	20°	110'-0"		FUJITSU - TA08025-B604	5G	A2	
A3	--	--	--	--	--		--	--	--	
B1	--	--	--	--	--	SHARED W/ALPHA	FUJITSU - TA08025-B605	5G	B2	SHARED W/ALPHA
B2	PROPOSED	COMMSCOPE - FFVW-65B-R2	5G	120°	110'-0"		FUJITSU - TA08025-B604	5G	B2	
B3	--	--	--	--	--		--	--	--	
C1	--	--	--	--	--	SHARED W/ALPHA	FUJITSU - TA08025-B605	5G	C2	SHARED W/ALPHA
C2	PROPOSED	COMMSCOPE - FFVW-65B-R2	5G	240°	110'-0"		FUJITSU - TA08025-B604	5G	C2	
C3	--	--	--	--	--		--	--	--	


NOTES

1. CONTRACTOR TO REFER TO FINAL CONSTRUCTION RFDS FOR ALL RF DETAILS.
2. ANTENNA AND RRH MODELS MAY CHANGE DUE TO EQUIPMENT AVAILABILITY. ALL EQUIPMENT CHANGES MUST BE APPROVED AND REMAIN IN COMPLIANCE WITH THE PROPOSED DESIGN AND STRUCTURAL ANALYSES.

ANTENNA SCHEDULE

NO SCALE

3



IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:
GIN --- ---

RFDS REV #: ---

CONSTRUCTION DOCUMENTS


SUBMITTALS

REV	DATE	DESCRIPTION
A	09/13/2022	ISSUED FOR REVIEW
0	12/21/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER
NJJER02052BDISH Wireless LLC.
PROJECT INFORMATION
NJJER02052B
200 ORONOQUE LANE
STRATFORD, CT 06614SHEET TITLE
ELEVATION, ANTENNA LAYOUT AND SCHEDULE

SHEET NUMBER

A-2




NOTES

1. CONTRACTOR TO BURY PLATFORM FEET WITH A MINIMUM OF 2" OF FILL PER EXISTING SITE SURFACE
2. WEED BARRIER FABRIC TO BE ADDED AT DISCRETION OF DISH Wireless LLC. CONSTRUCTION MANAGER AT TIME OF CONSTRUCTION. ONE SHEET 8'x8' INSTALLED UNDER ALL FOUR FEET OF THE PLATFORM (4 MIL BLACK PLASTIC)
3. EQUIPMENT CABINET OMITTED FOR CLARITY



dish wireless.
5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120

MK DEVELOPMENT
140 BEACH 137TH STREET
ROCKAWAY, NY 11694



COMMSCOPE MTC4045LP
5X7 PLATFORM
DIMENSIONS (HxWxD) 16"x84"x60"
TOTAL WEIGHT 423 LBS

NOTE:
GC TO PROVIDE EXTENDED
THREAD FOR PLATFORM IF
REQUIRED HEIGHT EXCEEDS 17"



12' 9" 6" 3" 0" 1' 2'
1"=1'-0"


1

PLATFORM DETAIL

NO SCALE 2

COMMSCOPE MTC4045HFLD
H-FRAME
UNISTRUT/SUPPORT RAILS QTY 5
WEIGHT 59.74 lbs

NOTE:
OR DISH Wireless LLC.
APPROVED EQUIVALENT



H-FRAME DETAIL

NO SCALE 3


NOT USED

NO SCALE 4


H-FRAME EQUIPMENT ELEVATION

12' 9" 6" 3" 0" 1' 2'
1"=1'-0"

5



FRONT ELEVATION



BACK ELEVATION

IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING IN THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.


DRAWN BY: CHECKED BY: APPROVED BY:
GIN --- ---

RFDS REV #: ---


CONSTRUCTION DOCUMENTS

SUBMITTALS		
REV A	DATE 09/13/2022	DESCRIPTION ISSUED FOR REVIEW
0	12/21/2022	ISSUED FOR CONSTRUCTION
A&E PROJECT NUMBER		
NJIER02052B		
DISH Wireless LLC. PROJECT INFORMATION		
NJIER02052B 200 ORONOQUE LANE STRATFORD, CT 06614		
SHEET TITLE		
EQUIPMENT PLATFORM AND H-FRAME DETAILS		
SHEET NUMBER		
A-3		

DELTA ELECTRONICS, INC. ESOA600-HCB04 (HEX)	
DIMENSIONS (HxWxD)	75"x32"x32"
WEIGHT (EMPTY)	625 lbs (approx.)



RAYCAP PPC RDIAC-2465-P-240-MTS	
ENCLOSURE DIMENSIONS (HxWxD):	39"x22.855"x12.593
WEIGHT:	80 lbs
OPERATING AC VOLTAGE	240/120 1 PHASE 3W+G



CABINET DETAIL

NO SCALE

1

POWER PROTECTION CABINET (PPC) DETAIL

NO SCALE


2

NOT USED


NO SCALE

3

ZAYO 5RU (LEFT SWING DOOR) FIBER NID ENCLOSURE	
DIMENSIONS (HxWxD)	36.1"x29"x12.9"
WEIGHT	85 lbs



CHARLES CFIT-PF2020DSH1 FIBER TELCO ENCLOSURE	
ENCLOSURE DIMS (HxWxD)	20"x20"x9"
ENCLOSURE WEIGHT	20 lbs
MOUNTING	WALL



NOT USED

NO SCALE

4

FIBER NID ENCLOSURE DETAIL

NO SCALE




5

FIBER TELCO ENCLOSURE DETAIL

NO SCALE

6

COMMSCOPE WB-K110-B WAVEGUIDE BRIDGE KIT	
DIMENSIONS (HxL)	160"x10'
WEIGHT/ VOLUME	325.0 LBS
CABLE RUN (QTY)	12



ICE BRIDGE DETAIL

NO SCALE

7

TYPICAL ICE BRIDGE CONCRETE PIER DETAIL

NO SCALE

8

HYBRID CABLE RUN

NO SCALE

9



5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



STATE OF CONNECTICUT
CHARLES MAGRATH
12/27/2022
33678
LICENSED
PROFESSIONAL ENGINEER

IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:

GIN --- ---

RFDS REV #: ---

CONSTRUCTION DOCUMENTS

SUBMITTALS

REV	DATE	DESCRIPTION
A	09/13/2022	ISSUED FOR REVIEW
O	12/21/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER

NJJER02052B

DISH Wireless L.L.C.
PROJECT INFORMATION
NJJER02052B
200 ORONOQUE LANE
STRATFORD, CT 06614





SHEET TITLE

EQUIPMENT DETAILS

SHEET NUMBER

A-4

PCTEL GPSGL-TMG-SPI-40NCF	
DIMENSIONS (DIAxH) MM/INCH	81x184mm 3.2"x7.25"
WEIGHT W/ACCESSORIES	075 lbs
CONNECTOR	N-FEMALE
FREQUENCY RANGE	1590 ± 30MHz



dish
wireless.
5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120

MK
DEVELOPMENT
140 BEACH 137TH STREET
ROCKAWAY, NY 11694



IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:

GIN --- ---

RFDS REV #: ---

CONSTRUCTION DOCUMENTS

SUBMITTALS

REV	DATE	DESCRIPTION
A	09/13/2022	ISSUED FOR REVIEW
O	12/21/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER
NJJER02052B

DISH Wireless L.L.C.
PROJECT INFORMATION

NJJER02052B
200 ORONOQUE LANE
STRATFORD, CT 06614

SHEET TITLE
EQUIPMENT DETAILS





SHEET NUMBER

A-5

<u>GPS DETAIL</u>	NO SCALE	1	<u>GPS MINIMUM SKY VIEW REQUIREMENTS</u>	NO SCALE	2	<u>CABLES UNLIMITED HYBRID CABLE MINIMUM BEND RADIIUSES</u>	NO SCALE	3
COMMSCOPE MTC4045HFLD H-FRAME UNISTRUT/SUPPORT RAILS QTY 5 WEIGHT ±59.74 lbs			NOTE: OR DISH Wireless LLC. APPROVED EQUIVALENT					
			SEE DETAIL 1 SHEET A-3 					
<u>H-FRAME DETAIL</u>	NO SCALE	4	<u>NOT USED</u>	NO SCALE	5	<u>NOT USED</u>	NO SCALE	6

<u>NOT USED</u>	NO SCALE	7	<u>NOT USED</u>	NO SCALE	8	<u>NOT USED</u>	NO SCALE	9
-----------------	----------	---	-----------------	----------	---	-----------------	----------	---

FUJITSU TRIPLE BAND TA08025-B605	
DIMENSIONS (HxWxD)	14.9" x 15.7" x 9"
WEIGHT	74.95 lbs
CONNECTOR TYPE	4.3-10 RF CONNECTOR
POWER SUPPLY	DC -58~36V





BACK


SIDE

FRONT


FUJITSU DUAL BAND TA08025-B604	
DIMENSIONS (HxWxD)	14.9" x 15.7" x 7.8"
WEIGHT	63.9 lbs
CONNECTOR TYPE	4.3-10 RF CONNECTOR
POWER SUPPLY	DC -58~36V



BACK





SIDE



FRONT

SABRE DOUBLE Z-BRACKET C10123155	
DIMENSIONS (HxWxD) (1 BRACKET)	5" x 20" x 1-13/16"
WEIGHT (FULL ASSEMBLY)	35.79 lbs
PACKAGE QUANTITY	4

#	DESCRIPTION
1	PLATE, CHANNEL BRACKET
2	RRH Z BRACKET, 3/16"
3	THREADED ROD ASSEMBLY 1/2" x 12"



NOTE:
OR DISH Wireless L.L.C.
APPROVED EQUIVALENT

RRH DETAIL

NO SCALE

1

RRH DETAIL

NO SCALE


2

RRH MOUNT DETAIL

NO SCALE

3

COMMSCOPE FFVV-65B-R2	
DIMENSIONS (HxWxD)(MM/IN)	1828x498x197 72" x 19.6" x 7.8"
RF CONNECTOR INTERFACE	4.3-10 FEMALE
WEIGHT	70.8 lbs
WEIGHT WITH BRACKETS	98.1 lbs





BACK

SIDE

FRONT

COMMSCOPE ANTENNA BRACKET BSAMNT-3	
DIAMETER COMPATIBILITY	2.362" - 4.528"
NET WEIGHT	13.669 lbs

NOTE:
OR DISH Wireless L.L.C.
APPROVED EQUIVALENT



IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:

GIN --- ---

RFDS REV #: ---

CONSTRUCTION DOCUMENTS**SUBMITTALS**

REV	DATE	DESCRIPTION
A	09/13/2022	ISSUED FOR REVIEW
O	12/21/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER

NJJER02052B

DISH Wireless L.L.C.
PROJECT INFORMATION
NJJER02052B
200 ORONOQUE LANE
STRATFORD, CT 06614

SHEET TITLE

EQUIPMENT DETAILS


SHEET NUMBER

A-6

RAYCAP RDIDC-9181-PF-48 DC SURGE PROTECTION (OVP)	
DIMENSIONS (HxWxD)	18.98" x 14.39" x 8.15"
WEIGHT	21.82 LBS




PLAN




SIDE

BACK



FRONT

COMMSCOPE XP-2040 CROSSOVER PLATE	
DIMENSIONS (HxW)	10" x 12"
WEIGHT	11 lbs



PLAN


PLATE

U-BOLT

SIDE

PLATE

U-BOLT



NO SCALE

5



ANTENNA BRACKET DETAIL

NO SCALE

6

COMMSCOPE MC-PK8-DSH	
FACE WIDTH	96"
WEIGHT	1373.08 lbs
NOTE: 15" TO 38" O.D.	

NOTE:
OR DISH Wireless L.L.C.
APPROVED EQUIVALENT

ANTENNA PLATFORM DETAIL

NO SCALE

9

SURGE SUPPRESSION DETAIL (OVP)

NO SCALE

7

RRH/OVP MOUNT DETAIL

NO SCALE

8

ANTENNA PLATFORM DETAIL

NO SCALE


9

NOTES

1. CONTRACTOR SHALL FIELD VERIFY ALL PROPOSED UNDERGROUND UTILITY CONDUIT ROUTE.
2. ANTENNAS AND MOUNTS OMITTED FOR CLARITY.
3. THE GROUND LEASE DOES NOT SPECIFY OUR UTILITY RIGHTS. "PWR" AND "FBR" PATH DEPICTED ON A-1 AND E-1 ARE BASED ON BEST AVAILABLE INFORMATION INCLUDING BUT NOT LIMITED TO FIELD VERIFICATION, PRIOR PROJECT DOCUMENTATION AND OTHER REAL PROPERTY RIGHTS DOCUMENTS. WHEN INSTALLING THE UTILITIES PLEASE LOCATE AND FOLLOW EXISTING PATH. IF EXISTING PATH IS NOT AN OPTION PLEASE NOTIFY TOWER OWNER AS FURTHER COORDINATION MAY BE NEEDED.

DC POWER WIRING SHALL BE COLOR CODED AT EACH END FOR IDENTIFYING +24V AND -48V CONDUCTORS. RED MARKINGS SHALL IDENTIFY +24V AND BLUE MARKINGS SHALL IDENTIFY -48V.

1. CONTRACTOR SHALL INSPECT THE EXISTING CONDITIONS PRIOR TO SUBMITTING A BID. ANY QUESTIONS ARISING DURING THE BID PERIOD IN REGARDS TO THE CONTRACTOR'S FUNCTIONS, THE SCOPE OF WORK, OR ANY OTHER ISSUE RELATED TO THIS PROJECT SHALL BE BROUGHT UP DURING THE BID PERIOD WITH THE PROJECT MANAGER FOR CLARIFICATION, NOT AFTER THE CONTRACT HAS BEEN AWARDED.
2. ALL ELECTRICAL WORK SHALL BE DONE IN ACCORDANCE WITH CURRENT NATIONAL ELECTRICAL CODES AND ALL STATE AND LOCAL CODES, LAWS, AND ORDINANCES. PROVIDE ALL COMPONENTS AND WIRING SIZES AS REQUIRED TO MEET NEC STANDARDS.
3. LOCATION OF EQUIPMENT, CONDUIT AND DEVICES SHOWN ON THE DRAWINGS ARE APPROXIMATE AND SHALL BE COORDINATED WITH FIELD CONDITIONS PRIOR TO CONSTRUCTION.
4. CONDUIT ROUGH-IN SHALL BE COORDINATED WITH THE MECHANICAL EQUIPMENT TO AVOID LOCATION CONFLICTS. VERIFY WITH THE MECHANICAL EQUIPMENT CONTRACTOR AND COMPLY AS REQUIRED.
5. CONTRACTOR SHALL PROVIDE ALL BREAKERS, CONDUITS AND CIRCUITS AS REQUIRED FOR A COMPLETE SYSTEM.
6. CONTRACTOR SHALL PROVIDE PULL BOXES AND JUNCTION BOXES AS REQUIRED BY THE NEC ARTICLE 314.
7. CONTRACTOR SHALL PROVIDE ALL STRAIN RELIEF AND CABLE SUPPORTS FOR ALL CABLE ASSEMBLIES. INSTALLATION SHALL BE IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS AND RECOMMENDATIONS.
8. ALL DISCONNECTS AND CONTROLLING DEVICES SHALL BE PROVIDED WITH ENGRAVED PHENOLIC NAMEPLATES INDICATING EQUIPMENT CONTROLLED, BRANCH CIRCUITS INSTALLED ON, AND PANEL FIELD LOCATIONS FED FROM.
9. INSTALL AN EQUIPMENT GROUNDING CONDUCTOR IN ALL CONDUITS PER THE SPECIFICATIONS AND NEC 250. THE EQUIPMENT GROUNDING CONDUCTORS SHALL BE BONDED AT ALL JUNCTION BOXES, PULL BOXES, AND ALL DISCONNECT SWITCHES, AND EQUIPMENT CABINETS.
10. ALL NEW MATERIAL SHALL HAVE A U.L. LABEL.
11. PANEL SCHEDULE LOADING AND CIRCUIT ARRANGEMENTS REFLECT POST-CONSTRUCTION EQUIPMENT.
12. CONTRACTOR SHALL BE RESPONSIBLE FOR AS-BUILT PANEL SCHEDULE AND SITE DRAWINGS.
13. ALL TRENCHES IN COMPOUND TO BE HAND DUG



UTILITY ROUTE PLAN

12' 6" 0' 1' 2' 3' 4' 5' 6' 7'
3/8"=1'-0"

dish
wireless.

5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120

MK
DEVELOPMENT
140 BEACH 137TH STREET
ROCKAWAY, NY 11694



IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:
GIN --- ---

RFDS REV #: ---

CONSTRUCTION DOCUMENTS

SUBMITTALS

REV	DATE	DESCRIPTION
A	09/13/2022	ISSUED FOR REVIEW
O	12/21/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER
NJER02052B


DISH Wireless L.L.C.
PROJECT INFORMATION
NJER02052B
200 ORONOQUE LANE
STRATFORD, CT 06614

SHEET TITLE
ELECTRICAL/FIBER ROUTE
PLAN AND NOTES

SHEET NUMBER



CARLON EXPANSION FITTINGS				
COUPLING END PART#	MALE TERMINAL ADAPTER END PART#	SIZE	STD CNT QTY.	TRAVEL LENGTH
E945D	E945DX	1/2"	20	4"
E945E	E945EX	3/4"	15	4"
E945F	E945FX	1"	10	4"
E945G	E945GX	1 1/4"	5	4"
E945H	E945HX	1 1/2"	5	4"
E945J	E945JX	2"	15	8"
E945K	E945KX	2 1/2"	10	8"
E945L	E945LX	3"	10	8"
E945M	E945MX	3 1/2"	5	8"
E945N	E945NX	4"	5	8"
E945P	E945PX	5"	1	8"
E945R	E945RX	6"	1	8"

NOTE:
CONTRACTOR TO INSTALL EXPANSION FITTING
SLIP JOINT AT METER CENTER CONDUIT
TERMINATION, AS PER LOCAL UTILITY POLICY,
ORDINANCE AND/OR SPECIFIED REQUIREMENT.




TRENCHING NOTES

1. CONTRACTOR SHALL RESTORE THE TRENCH TO ITS ORIGINAL CONDITIONS BY EITHER SEEDING OR SODDING GRASS AREAS, OR REPLACING ASPHALT OR CONCRETE AREAS TO ITS ORIGINAL CROSS SECTION.
2. TRENCHING SAFETY; INCLUDING, BUT NOT LIMITED TO SOIL CLASSIFICATION, SLOPING, AND SHORING, SHALL BE GOVERNED BY THE CURRENT OSHA TRENCHING AND EXCAVATION SAFETY STANDARDS.
3. ALL CONDUITS SHALL BE INSTALLED IN COMPLIANCE WITH THE CURRENT NATIONAL ELECTRIC CODE (NEC) OR AS REQUIRED BY THE LOCAL JURISDICTION, WHICHEVER IS THE MOST STRINGENT.



dish
wireless.
5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120

MK
DEVELOPMENT
140 BEACH 137TH STREET
ROCKAWAY, NY 11694



IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:

GIN --- ---

RFDS REV #: ---

CONSTRUCTION DOCUMENTS

SUBMITTALS

REV	DATE	DESCRIPTION
A	09/13/2022	ISSUED FOR REVIEW
O	12/21/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER
NJJER02052B

DISH Wireless LLC.
PROJECT INFORMATION
NJJER02052B
200 ORONOQUE LANE
STRATFORD, CT 06614

SHEET TITLE
ELECTRICAL
DETAILS

SHEET NUMBER

E-2

EXPANSION JOINT DETAIL

NO SCALE

1

TYPICAL UNDERGROUND TRENCH DETAIL

NO SCALE

2

DARK TELCO BOX - INTERIOR WIRING LAYOUT

NO SCALE

3

LIT TELCO BOX - INTERIOR WIRING LAYOUT (OPTIONAL)

NO SCALE

4

NOT USED

NO SCALE

5

NOT USED

NO SCALE

6

NOT USED

NO SCALE

7

NOT USED



NO SCALE

8

NOT USED

NO SCALE

9



NOTES	
THE (2) CONDUITS WITH (4) CURRENT CARRYING CONDUCTORS EACH, SHALL APPLY THE ADJUSTMENT FACTOR OF 80% PER 2020 NEC TABLE 310.15(C)(1) FOR UL1015 WIRE. (ALL WIRE AND TERMINATION HARDWARE TO BE RATED 75°C)	
#12 FOR 20A OCPD WIRE DERATING: 0.8 x 25A = 20.0A #8 FOR 40A OCPD WIRE DERATING: 0.8 x 50A = 40.0A	
CONDUIT SIZING: AT 40% FILL PER NEC CHAPTER 9, TABLE 4, ARTICLE 358.	
1.0" CONDUIT - .3460 SQ. IN AREA 3.0" CONDUIT - 3.538 SQ. IN AREA	
(2 CONDUIT): USING THWN-2, CU. RECTIFIER CONDUCTORS	
#8 - 0.0366 SQ. IN X 4 = 0.1464 SQ. IN #8 - 0.0366 SQ. IN X 1 = 0.0366 SQ. IN <GROUND TOTAL = 0.1830 SQ. IN	
RECTIFIER & GFCI CONDUCTORS	
#12 - 0.0133 SQ. IN X 2 = 0.0266 SQ. IN #8 - 0.0366 SQ. IN X 2 = 0.0732 SQ. IN #8 - 0.0366 SQ. IN X 1 = 0.0366 SQ. IN <GROUND TOTAL = 0.1364 SQ. IN	
1.0" EMT CONDUIT IS ADEQUATE TO HANDLE THE TOTAL OF (5) WIRES, INCLUDING GROUND WIRE, AS INDICATED ABOVE.	
PPC FEED CONDUCTORS (1 CONDUIT): USING THWN, CU.	
3/0 - 0.2679 SQ. IN X 3 = 0.8037 SQ. IN #6 - 0.0507 SQ. IN X 1 = 0.0507 SQ. IN <GROUND TOTAL = 0.8544 SQ. IN	
3.0" SCH 40 PVC CONDUIT IS ADEQUATE TO HANDLE THE TOTAL OF (4) WIRES, INCLUDING GROUND WIRE, AS INDICATED ABOVE.	
1 PPC FEED CONDUCTORS (1 CONDUIT): USING THWN, AL	
250kcmil AL - 0.3970 SQ. IN X 3 = 1.191 SQ. IN #4 AL - 0.0824 SQ. IN X 1 = 0.0824 SQ. IN <GROUND TOTAL = 1.2734 SQ. IN	
3.0" SCH 40 PVC CONDUIT IS ADEQUATE TO HANDLE THE TOTAL OF (4) WIRES, INCLUDING GROUND WIRE, AS INDICATED ABOVE.	

NOTE:
BRANCH CIRCUIT WIRING SUPPLYING RECTIFIERS ARE TO BE RATED UL1015, 105°C, 600V, AND PVC INSULATED, IN THE SIZES SHOWN IN THE ONE-LINE DIAGRAM. CONTRACTOR MAY SUBSTITUTE UL1015 WIRE FOR THWN-2 FOR CONVENIENCE OUTLET BRANCH CIRCUIT.

BREAKERS REQUIRED:
(3) 40A, 2P BREAKER - SQUARE D P/N:Q00240
(2) 15A, 1P BREAKER - SQUARE D P/N:Q0115

SERVICE/FEEDER CONDUCTOR LENGTH TABLE (BASED ON INDUSTRY STANDARD 3% VOLTAGE DROP AND 5% NEC ALLOWABLE LIMIT)						
	CONDUCTOR SIZES					
DESIGN LOADS	250 kcmil AL	300 kcmil AL	3/0 CU	4/0 CU	250 kcmil CU	300 kcmil CU
DISH Wireless LLC. MAXIMUM CONTINUOUS LOAD (160A) (NEC ARTICLE 220 & 230 3% VOLTAGE DROP)	130'	155'	145'	180'	215'	255'
DISH Wireless LLC. MAXIMUM CONTINUOUS LOAD (160A) (NEC ARTICLE 220 & 230 5% VOLTAGE DROP)	220'	260'	240'	300'	360'	425'

NOTES:

1. 250 MCM/KCMIL AL + #2 AL GRD MAY BE USED AS A REPLACEMENT FOR 3/0 CU + #6 CU GRD SERVICE CONDUCTOR FROM THE DISH Wireless LLC. FIRST MEANS OF DISCONNECT/UTILITY COMPANY MEET-ME POINT. REFER TO VALUES ABOVE TO LIMIT VOLTAGE DROP TO 3%.
2. ALUMINUM/COPPER CONDUCTORS MUST BE RATED 75°C.
3. ALUMINUM TO COPPER BUSS CONNECTIONS MUST MEET AND CONFORM TO ANSI AND BE UL LISTED. USE ANTI CORROSION CONDUCTIVE LUBRICANT ON CONNECTIONS
4. PPC MAIN DISCONNECT CIRCUIT BREAKERS ACCEPT #4 - 300KCMIL AL OR CU CONDUCTORS.
5. VOLTAGE DROP FOR SINGLE METER ENCLOSURE FED FROM TRANSFORMER WITH MULTIPLE CUSTOMERS IS CALCULATED FROM THE TRANSFORMER TO PPC. (SERVICE AND FEEDER CONDUCTOR LENGTH)
6. VOLTAGE DROP FOR MULTI-METER ENCLOSURE IS CALCULATED FROM THE METER TO PPC. (FEEDER CONDUCTOR LENGTH)
7. VOLTAGE DROP CALCULATIONS ARE BASED ON A POWER FACTOR OF 1, A LINE TO GROUND VOLTAGE PER CONDUCTOR OF 120V, NO CORRECTION FACTOR FOR AMBIENT TEMPERATURE OR ADJUSTMENT FACTOR FOR MORE THAN THREE CURRENT-CARRYING CONDUCTORS IN A SINGLE CONDUCTOR RACEWAY. A POWER FACTOR LESS THAN 1 OR VOLTAGE LESS THAN 120 WILL RESULT IN SHORTER DISTANCES THAN SHOWN IN TABLE.


PPC ONE-LINE DIAGRAM

PANEL NAME		LOCATION		VOLTAGE: 240/120 1Ø				MOUNTING/ENCLOSURE: SURFACE/NEMA 3R					
DELTA		EQUIPMENT PLATFORM		MAIN C/B: 200 AMPS				AVAIL. FAULT CURRENT:					
AMPS POLES	WIRE & CONDUIT	TYPE	DESCRIPTION	KVA	CKT	A	B	CKT	KVA	DESCRIPTION	TYPE	WIRE & CONDUIT	AMPS POLES
15/1	2 #12, 1 #12G SEE ONE LINE	R	INTERNAL GFCI	0.18	1	1.68	1.68	4	1.50	RECTIFIER	EQ	SEE ONE LINE	40/2
		R	CONVENIENCE OUTLET	0.18	3	1.50		6	1.50	RECTIFIER	EQ	SEE ONE LINE	40/2
			SPACE			7		8	1.50	RECTIFIER	EQ	SEE ONE LINE	40/2
			SPACE	9	1.50		10	1.50	RECTIFIER	EQ	SEE ONE LINE	40/2	
			SPACE	11			12	1.50	RECTIFIER	EQ	SEE ONE LINE	40/2	
			SPACE	13			14		SPACE				
			SPACE	15			16		SPACE				
			SPACE	17			18		SPACE				
			SPACE	19			20		SPACE				
			SPACE	21			22		SPACE				
			SPACE	23			24		SPACE				
PHASED LOAD				4.7			4.7		KVA	TOTAL CONNECTED LOAD 9.4 KVA 39 A			
										TOTAL DEMAND LOAD 9.4 KVA 39 A			
LOAD TYPE	DESCRIPTION	CONN. LOAD KVA	DEMAND FACTOR	KVA	AMPS								
I	LIGHTING	0.0	0.0	1.25									
R	RECEPTACLE	0.4	1.5	NEC	0.4	1.5							
M	MOTOR	0.0	0.0	NEC	0.0	0.0							
H	HEATING	0.0	0.0	1.00									
AC	HVAC	0.0	0.0	1.00									
EQ	EQUIPMENT	9.0	37.5	1.00	9.0	37.5							
E	EXISTING	0.0	0.0	1.25									

*ALL EQUIPMENT LOADS CONSIDERED CONTINUOUS LOADS



DRAWN BY:	CHECKED BY:	APPROVED BY:
GIN	---	---
RFDS REV #:	---	
CONSTRUCTION DOCUMENTS		
SUBMITTALS		
REV	DATE	DESCRIPTION
A	09/13/2022	ISSUED FOR REVIEW
O	12/21/2022	ISSUED FOR CONSTRUCTION
A&E PROJECT NUMBER		
NJJER02052B		
DISH Wireless L.L.C. PROJECT INFORMATION		
NJJER02052B 200 ORONOQUE LANE STRATFORD, CT 06614		
SHEET TITLE		
ELECTRICAL ONE-LINE, FAULT CALCS & PANEL SCHEDULE		
SHEET NUMBER		
E-3		




TYPICAL EQUIPMENT GROUNDING PLAN

NO SCALE

1

NOTES

ANTENNAS AND OVP SHOWN ARE GENERIC AND NOT REFERENCING TO A SPECIFIC MANUFACTURER. THIS LAYOUT IS FOR REFERENCE PURPOSES ONLY



TYPICAL ANTENNA GROUNDING PLAN

NO SCALE

2

GROUNDING KEY NOTES

- EXOTHERMIC CONNECTION
- MECHANICAL CONNECTION
- GROUND BUS BAR
- GROUND ROD

- TEST GROUND ROD WITH INSPECTION SLEEVE
- #6 AWG STRANDED & INSULATED
- #2 AWG SOLID COPPER TINNED
- #2 AWG STRANDED & INSULATED
- ▲ BUSS BAR INSULATOR

GROUNDING LEGEND

1. GROUNDING IS SHOWN DIAGRAMMATICALLY ONLY.
2. CONTRACTOR SHALL GROUND ALL EQUIPMENT AS A COMPLETE SYSTEM. GROUNDING SHALL BE IN COMPLIANCE WITH NEC SECTION 250 AND DISH Wireless LLC. GROUNDING AND BONDING REQUIREMENTS AND MANUFACTURER'S SPECIFICATIONS.
3. ALL GROUND CONDUCTORS SHALL BE COPPER; NO ALUMINUM CONDUCTORS SHALL BE USED.

GROUNDING KEY NOTES

- (A) EXTERIOR GROUND RING: #2 AWG SOLID COPPER, BURIED AT A DEPTH OF AT LEAST 30 INCHES BELOW GRADE, OR 6 INCHES BELOW THE FROST LINE AND APPROXIMATELY 24 INCHES FROM THE EXTERIOR WALL OR FOOTING.
- (B) TOWER GROUND RING: THE GROUND RING SYSTEM SHALL BE INSTALLED AROUND AN ANTENNA TOWER'S LEGS, AND/OR GUY ANCHORS. WHERE SEPARATE SYSTEMS HAVE BEEN PROVIDED FOR THE TOWER AND THE BUILDING, AT LEAST TWO BONDS SHALL BE MADE BETWEEN THE TOWER RING GROUND SYSTEM AND THE BUILDING RING GROUND SYSTEM USING MINIMUM #2 AWG SOLID COPPER CONDUCTORS.
- (C) INTERIOR GROUND RING: #2 AWG STRANDED GREEN INSULATED COPPER CONDUCTOR EXTENDED AROUND THE PERIMETER OF THE EQUIPMENT AREA. ALL NON-TELECOMMUNICATIONS RELATED METALLIC OBJECTS FOUND WITHIN A SITE SHALL BE GROUNDED TO THE INTERIOR GROUND RING WITH #6 AWG STRANDED GREEN INSULATED CONDUCTOR.
- (D) BOND TO INTERIOR GROUND RING: #2 AWG SOLID TINNED COPPER WIRE PRIMARY BONDS SHALL BE PROVIDED AT LEAST AT FOUR POINTS ON THE INTERIOR GROUND RING, LOCATED AT THE CORNERS OF THE BUILDING.
- (E) GROUND ROD: UL LISTED COPPER CLAD STEEL. MINIMUM 1/2" DIAMETER BY EIGHT FEET LONG, GROUND RODS SHALL BE INSTALLED WITH INSPECTION SLEEVES. GROUND RODS SHALL BE DRIVEN TO THE DEPTH OF GROUND RING CONDUCTOR.
- (F) CELL REFERENCE GROUND BAR: POINT OF GROUND REFERENCE FOR ALL COMMUNICATIONS EQUIPMENT FRAMES. ALL BONDS ARE MADE WITH #2 AWG UNLESS NOTED OTHERWISE STRANDED GREEN INSULATED COPPER CONDUCTORS. BOND TO GROUND RING WITH (2) #2 SOLID TINNED COPPER CONDUCTORS.
- (G) HATCH PLATE GROUND BAR: BOND TO THE INTERIOR GROUND RING WITH TWO #2 AWG STRANDED GREEN INSULATED COPPER CONDUCTORS. WHEN A HATCH-PLATE AND A CELL REFERENCE GROUND BAR ARE BOTH PRESENT, THE CRGB MUST BE CONNECTED TO THE HATCH-PLATE AND TO THE INTERIOR GROUND RING USING (2) TWO #2 AWG STRANDED GREEN INSULATED COPPER CONDUCTORS EACH.
- (H) EXTERIOR CABLE ENTRY PORT GROUND BARS: LOCATED AT THE ENTRANCE TO THE CELL SITE BUILDING. BOND TO GROUND RING WITH A #2 AWG SOLID TINNED COPPER CONDUCTORS WITH AN EXOTHERMIC WELD AND INSPECTION SLEEVE.
- (I) TELCO GROUND BAR: BOND TO BOTH CELL REFERENCE GROUND BAR OR EXTERIOR GROUND RING.
- (J) FRAME BONDING: THE BONDING POINT FOR TELECOM EQUIPMENT FRAMES SHALL BE THE GROUND BUS THAT IS NOT ISOLATED FROM THE EQUIPMENT'S METAL FRAMEWORK.
- (K) INTERIOR UNIT BONDS: METAL FRAMES, CABINETS AND INDIVIDUAL METALLIC UNITS LOCATED WITHIN THE AREA OF THE INTERIOR GROUND RING REQUIRE A #6 AWG STRANDED GREEN INSULATED COPPER BOND TO THE INTERIOR GROUND RING.
- (L) FENCE AND GATE GROUNDING: METAL FENCES WITHIN 7 FEET OF THE EXTERIOR GROUND RING OR OBJECTS BONDED TO THE EXTERIOR GROUND RING SHALL BE BONDED TO THE GROUND RING WITH A #2 AWG SOLID TINNED COPPER CONDUCTOR AT AN INTERVAL NOT EXCEEDING 25 FEET. BONDS SHALL BE MADE AT EACH GATE POST AND ACROSS GATE OPENINGS.
- (M) EXTERIOR UNIT BONDS: METALLIC OBJECTS, EXTERNAL TO OR MOUNTED TO THE BUILDING, SHALL BE BONDED TO THE EXTERIOR GROUND RING. USING #2 TINNED SOLID COPPER WIRE
- (N) ICE BRIDGE SUPPORTS: EACH ICE BRIDGE LEG SHALL BE BONDED TO THE GROUND RING WITH #2 AWG BARE TINNED COPPER CONDUCTOR. PROVIDE EXOTHERMIC WELDS AT BOTH THE ICE BRIDGE LEG AND BURIED GROUND RING.
- (O) DURING ALL DC POWER SYSTEM CHANGES INCLUDING DC SYSTEM CHANGE OUTS, RECTIFIER REPLACEMENTS OR ADDITIONS, BREAKER DISTRIBUTION CHANGES, BATTERY ADDITIONS, BATTERY REPLACEMENTS AND INSTALLATIONS OR CHANGES TO DC CONVERTER SYSTEMS IT SHALL BE REQUIRED THAT SERVICE CONTRACTORS VERIFY ALL DC POWER SYSTEMS ARE EQUIPPED WITH A MASTER DC SYSTEM RETURN GROUND CONDUCTOR FROM THE DC POWER SYSTEM COMMON RETURN BUS DIRECTLY CONNECTED TO THE CELL SITE REFERENCE GROUND BAR.
- (P) TOWER TOP COLLECTOR BUSS BAR IS TO BE MECHANICALLY BONDED TO PROPOSED ANTENNA MOUNT COLLAR. REFER TO DISH Wireless LLC. GROUNDING NOTES.

5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120

M-K
DEVELOPMENT
140 BEACH 137TH STREET
ROCKAWAY, NY 11694



IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:
GIN --- ---

RFDS REV #:

CONSTRUCTION DOCUMENTS

SUBMITTALS

REV	DATE	DESCRIPTION
A	09/13/2022	ISSUED FOR REVIEW
O	12/21/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER
NJER02052B

DISH Wireless LLC.
PROJECT INFORMATION
NJER02052B
200 ORONOQUE LANE
STRATFORD, CT 06614

SHEET TITLE
GROUNDING PLANS
AND NOTES

SHEET NUMBER


G-1

dish
wireless.

5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120

MK
DEVELOPMENT

140 BEACH, 137TH STREET
ROCKAWAY, NY 11694



IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:

GIN --- ---

RFDS REV #: ---

CONSTRUCTION DOCUMENTS

SUBMITTALS







REV	DATE	DESCRIPTION
A	09/13/2022	ISSUED FOR REVIEW
O	12/21/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER
NJER02052B



DISH Wireless L.L.C.
PROJECT INFORMATION
NJER02052B
200 ORONOQUE LANE
STRATFORD, CT 06614

SHEET TITLE
GROUNDING DETAILS
SHEET NUMBER

G-2



1. EXOTHERMIC WELD (2) TWO, #2 AWG BARE TINNED SOLID COPPER CONDUCTORS TO GROUND BAR. ROUTE CONDUCTORS TO BURIED GROUND RING AND PROVIDE PARALLEL EXOTHERMIC WELD.
2. ALL EXTERIOR GROUNDING HARDWARE SHALL BE STAINLESS STEEL 3/8" DIAMETER OR LARGER. ALL HARDWARE 18-8 STAINLESS STEEL INCLUDING LOCK WASHERS, COAT ALL SURFACES WITH AN ANTI-OXIDANT COMPOUND BEFORE MATING.
3. FOR GROUND BOND TO STEEL ONLY: COAT ALL SURFACES WITH AN ANTI-OXIDANT COMPOUND BEFORE MATING.
4. DO NOT INSTALL CABLE GROUNDING KIT AT A BEND AND ALWAYS DIRECT GROUND CONDUCTOR DOWN TO GROUNDING BUS.
5. NUT & WASHER SHALL BE PLACED ON THE FRONT SIDE OF THE GROUND BAR AND BOLTED ON THE BACK SIDE.
6. ALL GROUNDING PARTS AND EQUIPMENT TO BE SUPPLIED AND INSTALLED BY CONTRACTOR.
7. THE CONTRACTOR SHALL BE RESPONSIBLE FOR INSTALLING ADDITIONAL GROUND BAR AS REQUIRED.
8. ENSURE THE WIRE INSULATION TERMINATION IS WITHIN 1/8" OF THE BARREL (NO SHINERS).



dish
wireless.
5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120

MK
DEVELOPMENT
140 BEACH 137TH STREET
ROCKAWAY, NY 11694



IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:
GIN --- ---

RFDS REV #: ---

CONSTRUCTION DOCUMENTS

SUBMITTALS

REV	DATE	DESCRIPTION
A	09/13/2022	ISSUED FOR REVIEW
O	12/21/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER
NJJER02052B

DISH Wireless L.L.C.
PROJECT INFORMATION

NJJER02052B
200 ORONOQUE LANE
STRATFORD, CT 06614

SHEET TITLE
GROUNDING DETAILS

SHEET NUMBER

G-3

TYPICAL GROUNDING NOTES


NO SCALE 1

TYPICAL EXTERIOR TWO HOLE LUG

NO SCALE 2

TYPICAL INTERIOR TWO HOLE LUG

NO SCALE 3



LUG DETAIL

NO SCALE 4

NOT USED

NO SCALE 5

NOT USED

NO SCALE 6

NOT USED

NO SCALE 7


NOT USED

NO SCALE 8

NOT USED

NO SCALE 9

HYBRID/DISCREET CABLES	3/4" TAPE WIDTHS WITH 3/4" SPACING																					
LOW-BAND RRH (600 MHz N71 BASEBAND) + (850 MHz N26 BAND) + (700 MHz N29 BAND) - OPTIONAL PER MARKET ADD FREQUENCY COLOR TO SECTOR BAND (CBRS WILL USE YELLOW BAND)																						
ALPHA RRH				BETA RRH				GAMMA RRH														
PORT 1 + SLANT	PORT 2 - SLANT	PORT 3 + SLANT	PORT 4 - SLANT	PORT 1 + SLANT	PORT 2 - SLANT	PORT 3 + SLANT	PORT 4 - SLANT	PORT 1 + SLANT	PORT 2 - SLANT	PORT 3 + SLANT	PORT 4 - SLANT											
RED	RED	RED	RED	BLUE	BLUE	BLUE	BLUE	GREEN	GREEN	GREEN	GREEN											
ORANGE	ORANGE	RED	RED	ORANGE	ORANGE	BLUE	BLUE	ORANGE	ORANGE	GREEN	GREEN											
WHITE (-) PORT	ORANGE	ORANGE	WHITE (-) PORT	WHITE (-) PORT	ORANGE	ORANGE	WHITE (-) PORT	WHITE (-) PORT	WHITE (-) PORT	ORANGE	ORANGE	WHITE (-) PORT										
MID-BAND RRH (AWS BANDS N66+N70) ADD FREQUENCY COLOR TO SECTOR BAND (CBRS WILL USE YELLOW BAND)																						
HYBRID/DISCREET CABLES				EXAMPLE 1		EXAMPLE 2		EXAMPLE 3 CANISTER COAX #1 (ALPHA)		CANISTER COAX #2 (ALPHA)												
INCLUDE SECTOR BANDS BEING SUPPORTED ALONG WITH FREQUENCY BANDS.																						
EXAMPLE 1 - HYBRID, OR DISCREET, SUPPORTS ALL SECTORS, BOTH LOW-BANDS AND MID-BANDS.																						
EXAMPLE 2 - HYBRID, OR DISCREET, SUPPORTS CBRS ONLY, ALL SECTORS.																						
EXAMPLE 3 - MAIN COAX WITH GROUND MOUNTED RRHs.																						
FIBER JUMPERS TO RRHs																						
LOW-BAND HHR FIBER CABLES HAVE SECTOR STRIPE ONLY.																						
LOW BAND RRH		MID BAND RRH		LOW BAND RRH		MID BAND RRH		LOW BAND RRH		MID BAND RRH												
RED		RED		BLUE		BLUE		GREEN		GREEN												
ORANGE		PURPLE		ORANGE		PURPLE		ORANGE		PURPLE												
POWER CABLES TO RRHs																						
LOW-BAND RRH POWER CABLES HAVE SECTOR STRIPE ONLY																						
LOW BAND RRH		MID BAND RRH		LOW BAND RRH		MID BAND RRH		LOW BAND RRH		MID BAND RRH												
RED		RED		BLUE		BLUE		GREEN		GREEN												
ORANGE		PURPLE		ORANGE		PURPLE		ORANGE		PURPLE												
RET MOTORS AT ANTENNAS																						
RET CONTROL IS HANDLED BY THE MID-BAND RRH WHEN ONE SET OF RET PORTS EXIST ON ANTENNA.																						
SEPARATE RET CABLES ARE USED WHEN ANTENNA PORTS PROVIDE INPUTS FOR BOTH LOW AND MID BANDS.																						
MICROWAVE RADIO LINKS																						
LINKS WILL HAVE A 1.5-2 INCH WHITE WRAP WITH THE AZIMUTH COLOR OVERLAPPING IN THE MIDDLE. ADD ADDITIONAL SECTOR COLOR BANDS FOR EACH ADDITIONAL MW RADIO.																						
MICROWAVE CABLES WILL REQUIRE P-TOUCH LABELS INSIDE THE CABINET TO IDENTIFY THE LOCAL AND REMOTE SITE ID's.																						
FORWARD AZIMUTH OF 0-120 DEGREES PRIMARY SECONDARY				FORWARD AZIMUTH OF 120-240 DEGREES PRIMARY SECONDARY				FORWARD AZIMUTH OF 240-359 DEGREES PRIMARY SECONDARY														
WHITE	WHITE	WHITE	WHITE	WHITE	WHITE	WHITE	WHITE	WHITE	WHITE	WHITE	WHITE											
RED	RED	WHITE	RED	PURPLE	BLUE	WHITE	WHITE	WHITE	WHITE	WHITE	WHITE											
WHITE	WHITE	RED	WHITE	ORANGE	PURPLE	WHITE	WHITE	WHITE	WHITE	WHITE	WHITE											






5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120



140 BEACH 137TH STREET
ROCKAWAY, NY 11694



12/27/2022
33678
LICENSED
PROFESSIONAL ENGINEER

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:
GIN --- ---

RFDS REV #: ---

CONSTRUCTION DOCUMENTS

SUBMITTALS

REV	DATE	DESCRIPTION
A	09/13/2022	ISSUED FOR REVIEW
O	12/21/2022	ISSUED FOR CONSTRUCTION


A&E PROJECT NUMBER
NJJER02052B

DISH Wireless L.L.C.
PROJECT INFORMATION
NJJER02052B
200 ORONOQUE LANE
STRATFORD, CT 06614

SHEET TITLE
RF
CABLE COLOR CODES

SHEET NUMBER
RF-1

EXOTHERMIC CONNECTION
 MECHANICAL CONNECTION
 BUSS BAR INSULATOR
 CHEMICAL ELECTROLYTIC GROUNDING SYSTEM
 TEST CHEMICAL ELECTROLYTIC GROUNDING SYSTEM
 EXOTHERMIC WITH INSPECTION SLEEVE
 GROUNDING BAR
 GROUND ROD
 TEST GROUND ROD WITH INSPECTION SLEEVE



SECURITY LIGHT W/PHOTOCELL LITHONIA ALXW
 LED-1-25A400/51K-SR4-120-PE-DDBTXD

CHAIN LINK FENCE

WOOD/WROUGHT IRON FENCE

WALL STRUCTURE

LEASE AREA

PROPERTY LINE (PL)

SETBACKS

ICE BRIDGE

CABLE TRAY

WATER LINE

UNDERGROUND POWER

UNDERGROUND TELCO

OVERHEAD POWER

OVERHEAD TELCO

UNDERGROUND TELCO/POWER




ABOVE GROUND POWER

ABOVE GROUND TELCO


ABOVE GROUND TELCO/POWER

WORKPOINT

SECTION REFERENCE



DETAIL REFERENCE



AB	ANCHOR BOLT	IN	INCH
ABV	ABOVE	INT	INTERIOR
AC	ALTERNATING CURRENT	LB(S)	POUND(S)
ADDL	ADDITIONAL	LF	LINEAR FEET
AFF	ABOVE FINISHED FLOOR	LTE	LONG TERM EVOLUTION
AFG	ABOVE FINISHED GRADE	MAS	MASONRY
AGL	ABOVE GROUND LEVEL	MAX	MAXIMUM
AIC	AMPERAGE INTERRUPTION CAPACITY	MB	MACHINE BOLT
ALUM	ALUMINUM	MECH	MECHANICAL
ALT	ALTERNATE	MFR	MANUFACTURER
ANT	ANTENNA	MGB	MASTER GROUND BAR
APPROX	APPROXIMATE	MIN	MINIMUM
ARCH	ARCHITECTURAL	MISC	MISCELLANEOUS
ATS	AUTOMATIC TRANSFER SWITCH	MTL	METAL
AWG	AMERICAN WIRE GAUGE	MTS	MANUAL TRANSFER SWITCH
BATT	BATTERY	MW	MICROWAVE
BLDG	BUILDING	NEC	NATIONAL ELECTRIC CODE
BLK	BLOCK	NM	NEWTON METERS
BLKG	BLOCKING	NO.	NUMBER
BM	BEAM	#	NUMBER
BTC	BARE TINNED COPPER CONDUCTOR	NTS	NOT TO SCALE
BOF	BOTTOM OF FOOTING	OC	ON-CENTER
CAB	CABINET	OSHA	OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
CANT	CANTILEVERED	OPNG	OPENING
CHG	CHARGING	P/C	PRECAST CONCRETE
CLG	CEILING	PCS	PERSONAL COMMUNICATION SERVICES
CLR	CLEAR	PCU	PRIMARY CONTROL UNIT
COL	COLUMN	PRC	PRIMARY RADIO CABINET
COMM	COMMON	PP	POLARIZING PRESERVING
CONC	CONCRETE	PSF	POUNDS PER SQUARE FOOT
CONSTR	CONSTRUCTION	PSI	POUNDS PER SQUARE INCH
DBL	DOUBLE	PT	PRESSURE TREATED
DC	DIRECT CURRENT	PWR	POWER CABINET
DEPT	DEPARTMENT	QTY	QUANTITY
DF	DOUGLAS FIR	RAD	RADIUS
DIA	DIAMETER	RECT	RECTIFIER
DIAG	DIAGONAL	REF	REFERENCE
DIM	DIMENSION	REINF	REINFORCEMENT
DWG	DRAWING	REQ'D	REQUIRED
DWL	DOWEL	RET	REMOTE ELECTRIC TILT
EA	EACH	RF	RADIO FREQUENCY
EC	ELECTRICAL CONDUCTOR	RMC	RIGID METALLIC CONDUIT
EL	ELEVATION	RRH	REMOTE RADIO HEAD
ELEC	ELECTRICAL	RRU	REMOTE RADIO UNIT
EMT	ELECTRICAL METALLIC TUBING	RWY	RACEWAY
ENG	ENGINEER	SCH	SCHEDULE
EQ	EQUAL	SHT	SHEET
EXP	EXPANSION	SIAD	SMART INTEGRATED ACCESS DEVICE
EXT	EXTERIOR	SIM	SIMILAR
EW	EACH WAY	SPEC	SPECIFICATION
FAB	FABRICATION	SQ	SQUARE
FF	FINISH FLOOR	SS	STAINLESS STEEL
FG	FINISH GRADE	STD	STANDARD
FIF	FACILITY INTERFACE FRAME	STL	STEEL
FIN	FINISH(ED)	TEMP	TEMPORARY
FLR	FLOOR	THK	THICKNESS
FDN	FOUNDATION	TMA	TOWER MOUNTED AMPLIFIER
FOC	FACE OF CONCRETE	TN	TOE NAIL
FOM	FACE OF MASONRY	TOA	TOP OF ANTENNA
FOS	FACE OF STUD	TOC	TOP OF CURB
FOW	FACE OF WALL	TOF	TOP OF FOUNDATION
FS	FINISH SURFACE	TOP	TOP OF PLATE (PARAPET)
FT	FOOT	TOS	TOP OF STEEL
FTG	FOOTING	TOW	TOP OF WALL
GA	GAUGE	TVSS	TRANSIENT VOLTAGE SURGE SUPPRESSION
GEN	GENERATOR	TYP	TYPICAL
GFCI	GROUND FAULT CIRCUIT INTERRUPTER	UG	UNDERGROUND
GLB	GLUE LAMINATED BEAM	UL	UNDERWRITERS LABORATORY
GLV	GALVANIZED	UNO	UNLESS NOTED OTHERWISE
GPS	GLOBAL POSITIONING SYSTEM	UMTS	UNIVERSAL MOBILE TELECOMMUNICATIONS SYSTEM
GND	GROUND	UPS	UNINTERRUPTIBLE POWER SYSTEM (DC POWER PLANT)
GSM	GLOBAL SYSTEM FOR MOBILE	VIF	VERIFIED IN FIELD
HDG	HOT DIPPED GALVANIZED	W	WIDE
HDR	HEADER	W/	WITH
HGR	HANGER	WD	WOOD
HVAC	HEAT/VENTILATION/AIR CONDITIONING	WP	WEATHERPROOF
HT	HEIGHT	WT	WEIGHT
IGR	INTERIOR GROUND RING		

LEGEND

ABBREVIATIONS

dish
 wireless.
 5701 SOUTH SANTA FE DRIVE
 LITTLETON, CO 80120

MK
 DEVELOPMENT
 140 BEACH 137TH STREET
 ROCKAWAY, NY 11694



IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:
 GIN --- ---

RFDS REV #: ---

CONSTRUCTION DOCUMENTS

SUBMITTALS

REV	DATE	DESCRIPTION
A	09/13/2022	ISSUED FOR REVIEW
0	12/21/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER

NJJER02052B

DISH Wireless L.L.C.
 PROJECT INFORMATION
 NJJER02052B
 200 ORONOQUE LANE
 STRATFORD, CT 06614

SHEET TITLE

LEGEND AND
 ABBREVIATIONS

SHEET NUMBER

GN-1





SIGN TYPES		
TYPE	COLOR	COLOR CODE PURPOSE
INFORMATION	GREEN	"INFORMATIONAL SIGN" TO NOTIFY OTHERS OF SITE OWNERSHIP & CONTACT NUMBER AND POTENTIAL RF EXPOSURE.
NOTICE	BLUE	"NOTICE BEYOND THIS POINT" RF FIELDS BEYOND THIS POINT MAY EXCEED THE FCC GENERAL PUBLIC EXPOSURE LIMIT. OBEY ALL POSTED SIGNS AND SITE GUIDELINES FOR WORKING IN RF ENVIRONMENTS. IN ACCORDANCE WITH FEDERAL COMMUNICATIONS COMMISSION RULES ON RADIO FREQUENCY EMISSIONS 47 CFR-1.1307(b)
CAUTION	YELLOW	"CAUTION BEYOND THIS POINT" RF FIELDS BEYOND THIS POINT MAY EXCEED THE FCC GENERAL PUBLIC EXPOSURE LIMIT. OBEY ALL POSTED SIGNS AND SITE GUIDELINES FOR WORKING IN RF ENVIRONMENTS. IN ACCORDANCE WITH FEDERAL COMMUNICATIONS COMMISSION RULES ON RADIO FREQUENCY EMISSIONS 47 CFR-1.1307(b)
WARNING	ORANGE/RED	"WARNING BEYOND THIS POINT" RF FIELDS AT THIS SITE EXCEED FCC RULES FOR HUMAN EXPOSURE. FAILURE TO OBEY ALL POSTED SIGNS AND SITE GUIDELINES FOR WORKING IN RF ENVIRONMENTS COULD RESULT IN SERIOUS INJURY. IN ACCORDANCE WITH FEDERAL COMMUNICATIONS COMMISSION RULES ON RADIO FREQUENCY EMISSIONS 47 CFR-1.1307(b)

SIGN PLACEMENT:

- RF SIGNAGE PLACEMENT SHALL FOLLOW THE RECOMMENDATIONS OF AN EXISTING EME REPORT, CREATED BY A THIRD PARTY PREVIOUSLY AUTHORIZED BY DISH Wireless L.L.C.
- INFORMATION SIGN (GREEN) SHALL BE LOCATED ON EXISTING DISH Wireless L.L.C EQUIPMENT.
 - A) IF THE INFORMATION SIGN IS A STICKER, IT SHALL BE PLACED ON EXISTING DISH Wireless L.L.C EQUIPMENT CABINET.
 - B) IF THE INFORMATION SIGH IS A METAL SIGN IT SHALL BE PLACED ON EXISTING DISH Wireless L.L.C H-FRAME WITH A SECURE ATTACH METHOD.
- IF EME REPORT IS NOT AVAILABLE AT THE TIME OF CREATION OF CONSTRUCTION DOCUMENTS; PLEASE CONTACT DISH Wireless L.L.C. CONSTRUCTION MANAGER FOR FURTHER INSTRUCTION ON HOW TO PROCEED.


NOTES:

1. FOR DISH Wireless L.L.C. LOGO, SEE DISH Wireless L.L.C. DESIGN SPECIFICATIONS (PROVIDED BY DISH Wireless L.L.C.)
2. SITE ID SHALL BE APPLIED TO SIGNS USING "LASER ENGRAVING" OR ANY OTHER WEATHER RESISTANT METHOD (DISH Wireless L.L.C. APPROVAL REQUIRED)
3. TEXT FOR SIGNAGE SHALL INDICATE CORRECT SITE NAME AND NUMBER AS PER DISH Wireless L.L.C. CONSTRUCTION MANAGER RECOMMENDATIONS.
4. CABINET/SHELTER MOUNTING APPLICATION REQUIRES ANOTHER PLATE APPLIED TO THE FACE OF THE CABINET WITH WATER PROOF POLYURETHANE ADHESIVE
5. ALL SIGNS WILL BE SECURED WITH EITHER STAINLESS STEEL ZIP TIES OR STAINLESS STEEL TECH SCREWS
6. ALL SIGNS TO BE 8.5"x11" AND MADE WITH 0.04" OF ALUMINUM MATERIAL



dish wireless.
5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120

MK DEVELOPMENT
140 BEACH 137TH STREET
ROCKAWAY, NY 11694


12/27/2022
33678
LICENSED
PROFESSIONAL ENGINEER

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:
GIN --- ---

RFDS REV #: ---

CONSTRUCTION DOCUMENTS

SUBMITTALS

REV	DATE	DESCRIPTION
A	09/13/2022	ISSUED FOR REVIEW
O	12/21/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER
NJER02052B

DISH Wireless L.L.C.
PROJECT INFORMATION
NJER02052B
200 ORONOQUE LANE
STRATFORD, CT 06614

SHEET TITLE
RF
SIGNAGE

SHEET NUMBER
GN-2

SITE ACTIVITY REQUIREMENTS:

1. NOTICE TO PROCEED – NO WORK SHALL COMMENCE PRIOR TO CONTRACTOR RECEIVING A WRITTEN NOTICE TO PROCEED (NTP) AND THE ISSUANCE OF A PURCHASE ORDER. PRIOR TO ACCESSING/ENTERING THE SITE YOU MUST CONTACT THE DISH Wireless L.L.C. AND TOWER OWNER NOC & THE DISH Wireless L.L.C. AND TOWER OWNER CONSTRUCTION MANAGER.
2. "LOOK UP" – DISH Wireless L.L.C. AND TOWER OWNER SAFETY CLIMB REQUIREMENT:
THE INTEGRITY OF THE SAFETY CLIMB AND ALL COMPONENTS OF THE CLIMBING FACILITY SHALL BE CONSIDERED DURING ALL STAGES OF DESIGN, INSTALLATION, AND INSPECTION. TOWER MODIFICATION, MOUNT REINFORCEMENTS, AND/OR EQUIPMENT INSTALLATIONS SHALL NOT COMPROMISE THE INTEGRITY OR FUNCTIONAL USE OF THE SAFETY CLIMB OR ANY COMPONENTS OF THE CLIMBING FACILITY ON THE STRUCTURE. THIS SHALL INCLUDE, BUT NOT BE LIMITED TO: PINCHING OF THE WIRE ROPE, BENDING OF THE WIRE ROPE FROM ITS SUPPORTS, DIRECT CONTACT OR CLOSE PROXIMITY TO THE WIRE ROPE WHICH MAY CAUSE FRICTIONAL WEAR, IMPACT TO THE ANCHORAGE POINTS IN ANY WAY, OR TO IMPEDE/BLOCK ITS INTENDED USE. ANY COMPROMISED SAFETY CLIMB, INCLUDING EXISTING CONDITIONS MUST BE TAGGED OUT AND REPORTED TO YOUR DISH Wireless L.L.C. AND DISH Wireless L.L.C. AND TOWER OWNER POC OR CALL THE NOC TO GENERATE A SAFETY CLIMB MAINTENANCE AND CONTRACTOR NOTICE TICKET.
3. PRIOR TO THE START OF CONSTRUCTION, ALL REQUIRED JURISDICTIONAL PERMITS SHALL BE OBTAINED. THIS INCLUDES, BUT IS NOT LIMITED TO, BUILDING, ELECTRICAL, MECHANICAL, FIRE, FLOOD ZONE, ENVIRONMENTAL, AND ZONING. AFTER ONSITE ACTIVITIES AND CONSTRUCTION ARE COMPLETED, ALL REQUIRED PERMITS SHALL BE SATISFIED AND CLOSED OUT ACCORDING TO LOCAL JURISDICTIONAL REQUIREMENTS.
4. ALL CONSTRUCTION MEANS AND METHODS; INCLUDING BUT NOT LIMITED TO, ERECTION PLANS, RIGGING PLANS, CLIMBING PLANS, AND RESCUE PLANS SHALL BE THE RESPONSIBILITY OF THE GENERAL CONTRACTOR RESPONSIBLE FOR THE EXECUTION OF THE WORK CONTAINED HEREIN, AND SHALL MEET ANSI/ASSE A10.48 (LATEST EDITION); FEDERAL, STATE, AND LOCAL REGULATIONS; AND ANY APPLICABLE INDUSTRY CONSENSUS STANDARDS RELATED TO THE CONSTRUCTION ACTIVITIES BEING PERFORMED. ALL RIGGING PLANS SHALL ADHERE TO ANSI/ASSE A10.48 (LATEST EDITION) AND DISH Wireless L.L.C. AND TOWER OWNER STANDARDS, INCLUDING THE REQUIRED INVOLVEMENT OF A QUALIFIED ENGINEER FOR CLASS IV CONSTRUCTION, TO CERTIFY THE SUPPORTING STRUCTURE(S) IN ACCORDANCE WITH ANSI/TIA-322 (LATEST EDITION).
5. ALL SITE WORK TO COMPLY WITH DISH Wireless L.L.C. AND TOWER OWNER INSTALLATION STANDARDS FOR CONSTRUCTION ACTIVITIES ON DISH Wireless L.L.C. AND TOWER OWNER TOWER SITE AND LATEST VERSION OF ANSI/TIA-1019-A-2012 "STANDARD FOR INSTALLATION, ALTERATION, AND MAINTENANCE OF ANTENNA SUPPORTING STRUCTURES AND ANTENNAS."
6. IF THE SPECIFIED EQUIPMENT CAN NOT BE INSTALLED AS SHOWN ON THESE DRAWINGS, THE CONTRACTOR SHALL PROPOSE AN ALTERNATIVE INSTALLATION FOR APPROVAL BY DISH Wireless L.L.C. AND TOWER OWNER PRIOR TO PROCEEDING WITH ANY SUCH CHANGE OF INSTALLATION.
7. ALL MATERIALS FURNISHED AND INSTALLED SHALL BE IN STRICT ACCORDANCE WITH ALL APPLICABLE CODES, REGULATIONS AND ORDINANCES. CONTRACTOR SHALL ISSUE ALL APPROPRIATE NOTICES AND COMPLY WITH ALL LAWS, ORDINANCES, RULES, REGULATIONS AND LAWFUL ORDERS OF ANY PUBLIC AUTHORITY REGARDING THE PERFORMANCE OF THE WORK. ALL WORK CARRIED OUT SHALL COMPLY WITH ALL APPLICABLE MUNICIPAL AND UTILITY COMPANY SPECIFICATIONS AND LOCAL JURISDICTIONAL CODES, ORDINANCES AND APPLICABLE REGULATIONS.
8. THE CONTRACTOR SHALL INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS UNLESS SPECIFICALLY STATED OTHERWISE.
9. THE CONTRACTOR SHALL CONTACT UTILITY LOCATING SERVICES INCLUDING PRIVATE LOCATES SERVICES PRIOR TO THE START OF CONSTRUCTION.
10. ALL EXISTING ACTIVE SEWER, WATER, GAS, ELECTRIC AND OTHER UTILITIES WHERE ENCOUNTERED IN THE WORK, SHALL BE PROTECTED AT ALL TIMES AND WHERE REQUIRED FOR THE PROPER EXECUTION OF THE WORK, SHALL BE RELOCATED AS DIRECTED BY CONTRACTOR. EXTREME CAUTION SHOULD BE USED BY THE CONTRACTOR WHEN EXCAVATING OR DRILLING PIERS AROUND OR NEAR UTILITIES. CONTRACTOR SHALL PROVIDE SAFETY TRAINING FOR THE WORKING CREW. THIS WILL INCLUDE BUT NOT BE LIMITED TO A) FALL PROTECTION B) CONFINED SPACE C) ELECTRICAL SAFETY D) TRENCHING AND EXCAVATION E) CONSTRUCTION SAFETY PROCEDURES.
11. ALL SITE WORK SHALL BE AS INDICATED ON THE STAMPED CONSTRUCTION DRAWINGS AND DISH PROJECT SPECIFICATIONS, LATEST APPROVED REVISION.
12. CONTRACTOR SHALL KEEP THE SITE FREE FROM ACCUMULATING WASTE MATERIAL, DEBRIS, AND TRASH AT THE COMPLETION OF THE WORK. IF NECESSARY, RUBBISH, STUMPS, DEBRIS, STICKS, STONES AND OTHER REFUSE SHALL BE REMOVED FROM THE SITE AND DISPOSED OF LEGALLY.
13. ALL EXISTING INACTIVE SEWER, WATER, GAS, ELECTRIC AND OTHER UTILITIES, WHICH INTERFERE WITH THE EXECUTION OF THE WORK, SHALL BE REMOVED AND/OR CAPPED, PLUGGED OR OTHERWISE DISCONTINUED AT POINTS WHICH WILL NOT INTERFERE WITH THE EXECUTION OF THE WORK, SUBJECT TO THE APPROVAL OF DISH Wireless L.L.C. AND TOWER OWNER, AND/OR LOCAL UTILITIES.
14. THE CONTRACTOR SHALL PROVIDE SITE SIGNAGE IN ACCORDANCE WITH THE TECHNICAL SPECIFICATION FOR SITE SIGNAGE REQUIRED BY LOCAL JURISDICTION AND SIGNAGE REQUIRED ON INDIVIDUAL PIECES OF EQUIPMENT, ROOMS, AND SHELTERS.
15. THE SITE SHALL BE GRADED TO CAUSE SURFACE WATER TO FLOW AWAY FROM THE CARRIER'S EQUIPMENT AND TOWER AREAS.
16. THE SUB GRADE SHALL BE COMPACTED AND BROUGHT TO A SMOOTH UNIFORM GRADE PRIOR TO FINISHED SURFACE APPLICATION.
17. THE AREAS OF THE OWNERS PROPERTY DISTurbed BY THE WORK AND NOT COVERED BY THE TOWER, EQUIPMENT OR DRIVEWAY, SHALL BE GRADED TO A UNIFORM SLOPE, AND STABILIZED TO PREVENT EROSION AS SPECIFIED ON THE CONSTRUCTION DRAWINGS AND/OR PROJECT SPECIFICATIONS.
18. CONTRACTOR SHALL MINIMIZE DISTURBANCE TO EXISTING SITE DURING CONSTRUCTION. EROSION CONTROL MEASURES, IF REQUIRED DURING CONSTRUCTION, SHALL BE IN CONFORMANCE WITH THE LOCAL GUIDELINES FOR EROSION AND SEDIMENT CONTROL.
19. THE CONTRACTOR SHALL PROTECT EXISTING IMPROVEMENTS, PAVEMENTS, CURBS, LANDSCAPING AND STRUCTURES. ANY DAMAGED PART SHALL BE REPAIRED AT CONTRACTOR'S EXPENSE TO THE SATISFACTION OF OWNER.
20. CONTRACTOR SHALL LEGALLY AND PROPERLY DISPOSE OF ALL SCRAP MATERIALS SUCH AS COAXIAL CABLES AND OTHER ITEMS REMOVED FROM THE EXISTING FACILITY. ANTENNAS AND RADIOS REMOVED SHALL BE RETURNED TO THE OWNER'S DESIGNATED LOCATION.
21. CONTRACTOR SHALL LEAVE PREMISES IN CLEAN CONDITION. TRASH AND DEBRIS SHOULD BE REMOVED FROM SITE ON A DAILY BASIS.
22. NO FILL OR EMBANKMENT MATERIAL SHALL BE PLACED ON FROZEN GROUND. FROZEN MATERIALS, SNOW OR ICE SHALL NOT BE PLACED IN ANY FILL OR EMBANKMENT.

GENERAL NOTES:

1. FOR THE PURPOSE OF CONSTRUCTION DRAWING, THE FOLLOWING DEFINITIONS SHALL APPLY:
CONTRACTOR:GENERAL CONTRACTOR RESPONSIBLE FOR CONSTRUCTION
CARRIER:DISH Wireless L.L.C.
TOWER OWNER:TOWER OWNER
2. THESE DRAWINGS HAVE BEEN PREPARED USING STANDARDS OF PROFESSIONAL CARE AND COMPLETENESS NORMALLY EXERCISED UNDER SIMILAR CIRCUMSTANCES BY REPUTABLE ENGINEERS IN THIS OR SIMILAR LOCALITIES. IT IS ASSUMED THAT THE WORK DEPICTED WILL BE PERFORMED BY AN EXPERIENCED CONTRACTOR AND/OR WORKPEOPLE WHO HAVE A WORKING KNOWLEDGE OF THE APPLICABLE CODE STANDARDS AND REQUIREMENTS AND OF INDUSTRY ACCEPTED STANDARD GOOD PRACTICE. AS NOT EVERY CONDITION OR ELEMENT IS (OR CAN BE) EXPLICITLY SHOWN ON THESE DRAWINGS, THE CONTRACTOR SHALL USE INDUSTRY ACCEPTED STANDARD GOOD PRACTICE FOR MISCELLANEOUS WORK NOT EXPLICITLY SHOWN.
3. THESE DRAWINGS REPRESENT THE FINISHED STRUCTURE. THEY DO NOT INDICATE THE MEANS OR METHODS OF CONSTRUCTION. THE CONTRACTOR SHALL BE SOLELY RESPONSIBLE FOR THE CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES, AND PROCEDURES. THE CONTRACTOR SHALL PROVIDE ALL MEASURES NECESSARY FOR PROTECTION OF LIFE AND PROPERTY DURING CONSTRUCTION. SUCH MEASURES SHALL INCLUDE, BUT NOT BE LIMITED TO, BRACING, FORMWORK, SHORING, ETC. SITE VISITS BY THE ENGINEER OR HIS REPRESENTATIVE WILL NOT INCLUDE INSPECTION OF THESE ITEMS AND IS FOR STRUCTURAL OBSERVATION OF THE FINISHED STRUCTURE ONLY.
4. NOTES AND DETAILS IN THE CONSTRUCTION DRAWINGS SHALL TAKE PRECEDENCE OVER GENERAL NOTES AND TYPICAL DETAILS. WHERE NO DETAILS ARE SHOWN, CONSTRUCTION SHALL CONFORM TO SIMILAR WORK ON THE PROJECT, AND/OR AS PROVIDED FOR IN THE CONTRACT DOCUMENTS. WHERE DISCREPANCIES OCCUR BETWEEN PLANS, DETAILS, GENERAL NOTES, AND SPECIFICATIONS, THE GREATER, MORE STRICT REQUIREMENTS, SHALL GOVERN. IF FURTHER CLARIFICATION IS REQUIRED CONTACT THE ENGINEER OF RECORD.
5. SUBSTANTIAL EFFORT HAS BEEN MADE TO PROVIDE ACCURATE DIMENSIONS AND MEASUREMENTS ON THE DRAWINGS TO ASSIST IN THE FABRICATION AND/OR PLACEMENT OF CONSTRUCTION ELEMENTS BUT IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO FIELD VERIFY THE DIMENSIONS, MEASUREMENTS, AND/OR CLEARANCES SHOWN IN THE CONSTRUCTION DRAWINGS PRIOR TO FABRICATION OR CUTTING OF ANY NEW OR EXISTING CONSTRUCTION ELEMENTS. IF IT IS DETERMINED THAT THERE ARE DISCREPANCIES AND/OR CONFLICTS WITH THE CONSTRUCTION DRAWINGS THE ENGINEER OF RECORD IS TO BE NOTIFIED AS SOON AS POSSIBLE.
6. PRIOR TO THE SUBMISSION OF BIDS, THE BIDDING CONTRACTOR SHALL VISIT THE CELL SITE TO FAMILIARIZE WITH THE EXISTING CONDITIONS AND TO CONFIRM THAT THE WORK CAN BE ACCOMPLISHED AS SHOWN ON THE CONSTRUCTION DRAWINGS. ANY DISCREPANCY FOUND SHALL BE BROUGHT TO THE ATTENTION OF CARRIER POC AND TOWER OWNER.
7. ALL MATERIALS FURNISHED AND INSTALLED SHALL BE IN STRICT ACCORDANCE WITH ALL APPLICABLE CODES, REGULATIONS AND ORDINANCES. CONTRACTOR SHALL ISSUE ALL APPROPRIATE NOTICES AND COMPLY WITH ALL LAWS, ORDINANCES, RULES, REGULATIONS AND LAWFUL ORDERS OF ANY PUBLIC AUTHORITY REGARDING THE PERFORMANCE OF THE WORK. ALL WORK CARRIED OUT SHALL COMPLY WITH ALL APPLICABLE MUNICIPAL AND UTILITY COMPANY SPECIFICATIONS AND LOCAL JURISDICTIONAL CODES, ORDINANCES AND APPLICABLE REGULATIONS.
8. UNLESS NOTED OTHERWISE, THE WORK SHALL INCLUDE FURNISHING MATERIALS, EQUIPMENT, APPURTENANCES AND LABOR NECESSARY TO COMPLETE ALL INSTALLATIONS AS INDICATED ON THE DRAWINGS.
9. THE CONTRACTOR SHALL INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS UNLESS SPECIFICALLY STATED OTHERWISE.
10. IF THE SPECIFIED EQUIPMENT CAN NOT BE INSTALLED AS SHOWN ON THESE DRAWINGS, THE CONTRACTOR SHALL PROPOSE AN ALTERNATIVE INSTALLATION FOR APPROVAL BY THE CARRIER AND TOWER OWNER PRIOR TO PROCEEDING WITH ANY SUCH CHANGE OF INSTALLATION.
11. CONTRACTOR IS TO PERFORM A SITE INVESTIGATION, BEFORE SUBMITTING BIDS, TO DETERMINE THE BEST ROUTING OF ALL CONDUITS FOR POWER, AND TELCO AND FOR GROUNDING CABLES AS SHOWN IN THE POWER, TELCO, AND GROUNDING PLAN DRAWINGS.
12. THE CONTRACTOR SHALL PROTECT EXISTING IMPROVEMENTS, PAVEMENTS, CURBS, LANDSCAPING AND STRUCTURES. ANY DAMAGED PART SHALL BE REPAIRED AT CONTRACTOR'S EXPENSE TO THE SATISFACTION OF DISH Wireless L.L.C. AND TOWER OWNER
13. CONTRACTOR SHALL LEGALLY AND PROPERLY DISPOSE OF ALL SCRAP MATERIALS SUCH AS COAXIAL CABLES AND OTHER ITEMS REMOVED FROM THE EXISTING FACILITY. ANTENNAS REMOVED SHALL BE RETURNED TO THE OWNER'S DESIGNATED LOCATION.
14. CONTRACTOR SHALL LEAVE PREMISES IN CLEAN CONDITION. TRASH AND DEBRIS SHOULD BE REMOVED FROM SITE ON A DAILY BASIS.



IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:
GIN --- ---

RFDS REV #: ---

CONSTRUCTION DOCUMENTS

SUBMITTALS

REV	DATE	DESCRIPTION
A	09/13/2022	ISSUED FOR REVIEW
O	12/21/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER
NJJER02052B

DISH Wireless L.L.C.
PROJECT INFORMATION
NJJER02052B
200 ORONOQUE LANE
STRATFORD, CT 06614

SHEET TITLE
GENERAL NOTES

SHEET NUMBER

GN-3

CONCRETE, FOUNDATIONS, AND REINFORCING STEEL:

1. ALL CONCRETE WORK SHALL BE IN ACCORDANCE WITH THE ACI 301, ACI 318, ACI 336, ASTM A184, ASTM A185 AND THE DESIGN AND CONSTRUCTION SPECIFICATION FOR CAST-IN-PLACE CONCRETE.
2. UNLESS NOTED OTHERWISE, SOIL BEARING PRESSURE USED FOR DESIGN OF SLABS AND FOUNDATIONS IS ASSUMED TO BE 1000 psf.
3. ALL CONCRETE SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH (f'_c) OF 3000 psi AT 28 DAYS, UNLESS NOTED OTHERWISE. NO MORE THAN 90 MINUTES SHALL ELAPSE FROM BATCH TIME TO TIME OF PLACEMENT UNLESS APPROVED BY THE ENGINEER OF RECORD. TEMPERATURE OF CONCRETE SHALL NOT EXCEED 90°f AT TIME OF PLACEMENT.
4. CONCRETE EXPOSED TO FREEZE-THAW CYCLES SHALL CONTAIN AIR ENTRAINING ADMIXTURES. AMOUNT OF AIR ENTRAINMENT TO BE BASED ON SIZE OF AGGREGATE AND F3 CLASS EXPOSURE (VERY SEVERE). CEMENT USED TO BE TYPE II PORTLAND CEMENT WITH A MAXIMUM WATER-TO-CEMENT RATIO (W/C) OF 0.45.
5. ALL STEEL REINFORCING SHALL CONFORM TO ASTM A615. ALL WELDED WIRE FABRIC (WWF) SHALL CONFORM TO ASTM A185. ALL SPLICES SHALL BE CLASS "B" TENSION SPLICES, UNLESS NOTED OTHERWISE. ALL HOOKS SHALL BE STANDARD 90 DEGREE HOOKS, UNLESS NOTED OTHERWISE. YIELD STRENGTH (F_y) OF STANDARD DEFORMED BARS ARE AS FOLLOWS:
 #4 BARS AND SMALLER 40 ksi
 #5 BARS AND LARGER 60 ksi
6. THE FOLLOWING MINIMUM CONCRETE COVER SHALL BE PROVIDED FOR REINFORCING STEEL UNLESS SHOWN OTHERWISE ON DRAWINGS:
 - CONCRETE CAST AGAINST AND PERMANENTLY EXPOSED TO EARTH 3"
 - CONCRETE EXPOSED TO EARTH OR WEATHER:
 - #6 BARS AND LARGER 2"
 - #5 BARS AND SMALLER 1-1/2"
 - CONCRETE NOT EXPOSED TO EARTH OR WEATHER:
 - SLAB AND WALLS 3/4"
 - BEAMS AND COLUMNS 1-1/2"
7. A TOOLED EDGE OR A 3/4" CHAMFER SHALL BE PROVIDED AT ALL EXPOSED EDGES OF CONCRETE, UNLESS NOTED OTHERWISE, IN ACCORDANCE WITH ACI 301 SECTION 4.2.4.

ELECTRICAL INSTALLATION NOTES:

1. ALL ELECTRICAL WORK SHALL BE PERFORMED IN ACCORDANCE WITH THE PROJECT SPECIFICATIONS, NEC AND ALL APPLICABLE FEDERAL, STATE, AND LOCAL CODES/ORDINANCES.
2. CONDUIT ROUTINGS ARE SCHEMATIC. CONTRACTOR SHALL INSTALL CONDUITS SO THAT ACCESS TO EQUIPMENT IS NOT BLOCKED AND TRIP HAZARDS ARE ELIMINATED.
3. WIRING, RACEWAY AND SUPPORT METHODS AND MATERIALS SHALL COMPLY WITH THE REQUIREMENTS OF THE NEC.
4. ALL CIRCUITS SHALL BE SEGREGATED AND MAINTAIN MINIMUM CABLE SEPARATION AS REQUIRED BY THE NEC.
 - 4.1. ALL EQUIPMENT SHALL BEAR THE UNDERWRITERS LABORATORIES LABEL OF APPROVAL, AND SHALL CONFORM TO REQUIREMENT OF THE NATIONAL ELECTRICAL CODE.
 - 4.2. ALL OVERCURRENT DEVICES SHALL HAVE AN INTERRUPTING CURRENT RATING THAT SHALL BE GREATER THAN THE SHORT CIRCUIT CURRENT TO WHICH THEY ARE SUBJECTED, 22,000 AIC MINIMUM. VERIFY AVAILABLE SHORT CIRCUIT CURRENT DOES NOT EXCEED THE RATING OF ELECTRICAL EQUIPMENT IN ACCORDANCE WITH ARTICLE 110.24 NEC OR THE MOST CURRENT ADOPTED CODE PRE THE GOVERNING JURISDICTION.
5. EACH END OF EVERY POWER PHASE CONDUCTOR, GROUNDING CONDUCTOR, AND TELCO CONDUCTOR OR CABLE SHALL BE LABELED WITH COLOR-CODED INSULATION OR ELECTRICAL TAPE (3M BRAND, 1/2" PLASTIC ELECTRICAL TAPE WITH UV PROTECTION, OR EQUAL). THE IDENTIFICATION METHOD SHALL CONFORM WITH NEC AND OSHA.
6. ALL ELECTRICAL COMPONENTS SHALL BE CLEARLY LABELED WITH LAMICOID TAGS SHOWING THEIR RATED VOLTAGE, PHASE CONFIGURATION, WIRE CONFIGURATION, POWER OR AMPACITY RATING AND BRANCH CIRCUIT ID NUMBERS (i.e. PANEL BOARD AND CIRCUIT ID'S).
7. PANEL BOARDS (ID NUMBERS) SHALL BE CLEARLY LABELED WITH PLASTIC LABELS.
8. TIE WRAPS ARE NOT ALLOWED.
9. ALL POWER AND EQUIPMENT GROUND WIRING IN TUBING OR CONDUIT SHALL BE SINGLE COPPER CONDUCTOR (#14 OR LARGER) WITH TYPE THHW, THWN, THWN-2, XHHW, XHHW-2, THW, THW-2, RHW, OR RHW-2 INSULATION UNLESS OTHERWISE SPECIFIED.
10. SUPPLEMENTAL EQUIPMENT GROUND WIRING LOCATED INDOORS SHALL BE SINGLE COPPER CONDUCTOR (#6 OR LARGER) WITH TYPE THHW, THWN, THWN-2, XHHW, XHHW-2, THW, THW-2, RHW, OR RHW-2 INSULATION UNLESS OTHERWISE SPECIFIED.
11. POWER AND CONTROL WIRING IN FLEXIBLE CORD SHALL BE MULTI-CONDUCTOR, TYPE SOOW CORD (#14 OR LARGER) UNLESS OTHERWISE SPECIFIED.
12. POWER AND CONTROL WIRING FOR USE IN CABLE TRAY SHALL BE MULTI-CONDUCTOR, TYPE TC CABLE (#14 OR LARGER), WITH TYPE THHW, THWN, THWN-2, XHHW, XHHW-2, THW, THW-2, RHW, OR RHW-2 INSULATION UNLESS OTHERWISE SPECIFIED.
13. ALL POWER AND GROUNDING CONNECTIONS SHALL BE CRIMP-STYLE, COMPRESSION WIRE LUGS AND WIRE NUTS BY THOMAS AND BETTS (OR EQUAL). LUGS AND WIRE NUTS SHALL BE RATED FOR OPERATION NOT LESS THAN 75° C (90° C IF AVAILABLE).
14. RACEWAY AND CABLE TRAY SHALL BE LISTED OR LABELED FOR ELECTRICAL USE IN ACCORDANCE WITH NEMA, UL, ANSI/IEEE AND NEC.
15. ELECTRICAL METALLIC TUBING (EMT), INTERMEDIATE METAL CONDUIT (IMC), OR RIGID METAL CONDUIT (RMC) SHALL BE USED FOR EXPOSED INDOOR LOCATIONS.

16. ELECTRICAL METALLIC TUBING (EMT) OR METAL-CLAD CABLE (MC) SHALL BE USED FOR CONCEALED INDOOR LOCATIONS.
17. SCHEDULE 40 PVC UNDERGROUND ON STRAIGHTS AND SCHEDULE 80 PVC FOR ALL ELBOWS/90s AND ALL APPROVED ABOVE GRADE PVC CONDUIT.
18. LIQUID-TIGHT FLEXIBLE METALLIC CONDUIT (LIQUID-TITE FLEX) SHALL BE USED INDOORS AND OUTDOORS, WHERE VIBRATION OCCURS OR FLEXIBILITY IS NEEDED.
19. CONDUIT AND TUBING FITTINGS SHALL BE THREADED OR COMPRESSION-TYPE AND APPROVED FOR THE LOCATION USED. SET SCREW FITTINGS ARE NOT ACCEPTABLE.
20. CABINETS, BOXES AND WIREWAYS SHALL BE LABELED FOR ELECTRICAL USE IN ACCORDANCE WITH NEMA, UL, ANSI/IEEE AND THE NEC.
21. WIREWAYS SHALL BE METAL WITH AN ENAMEL FINISH AND INCLUDE A HINGED COVER, DESIGNED TO SWING OPEN DOWNTOWARDS (WIREMOLD SPECMATE WIREWAY).
22. SLOTTED WIRING DUCT SHALL BE PVC AND INCLUDE COVER (PANDUIT TYPE E OR EQUAL).
23. CONDUITS SHALL BE FASTENED SECURELY IN PLACE WITH APPROVED NON-PERFORATED STRAPS AND HANGERS. EXPLOSIVE DEVICES (i.e. POWDER-ACTUATED) FOR ATTACHING HANGERS TO STRUCTURE WILL NOT BE PERMITTED. CLOSELY FOLLOW THE LINES OF THE STRUCTURE, MAINTAIN CLOSE PROXIMITY TO THE STRUCTURE AND KEEP CONDUITS IN TIGHT ENVELOPES. CHANGES IN DIRECTION TO ROUTE AROUND OBSTACLES SHALL BE MADE WITH CONDUIT OUTLET BODIES. CONDUIT SHALL BE INSTALLED IN A NEAT AND WORKMANLIKE MANNER. PARALLEL AND PERPENDICULAR TO STRUCTURE WALL AND CEILING LINES. ALL CONDUIT SHALL BE FISHED TO CLEAR OBSTRUCTIONS. ENDS OF CONDUITS SHALL BE TEMPORARILY CAPPED FLUSH TO FINISH GRADE TO PREVENT CONCRETE, PLASTER OR DIRT FROM ENTERING. CONDUITS SHALL BE RIDIGLY CLAMPED TO BOXES BY GALVANIZED MALLEABLE IRON BUSHING ON INSIDE AND GALVANIZED MALLEABLE IRON LOCKNUT ON OUTSIDE AND INSIDE.
24. EQUIPMENT CABINETS, TERMINAL BOXES, JUNCTION BOXES AND PULL BOXES SHALL BE GALVANIZED OR EPOXY-COATED SHEET STEEL. SHALL MEET OR EXCEED UL 50 AND BE RATED NEMA 1 (OR BETTER) FOR INTERIOR LOCATIONS AND NEMA 3 (OR BETTER) FOR EXTERIOR LOCATIONS.
25. METAL RECEPTACLE, SWITCH AND DEVICE BOXES SHALL BE GALVANIZED, EPOXY-COATED OR NON-CORRODING; SHALL MEET OR EXCEED UL 514A AND NEMA OS 1 AND BE RATED NEMA 1 (OR BETTER) FOR INTERIOR LOCATIONS AND WEATHER PROTECTED (WP OR BETTER) FOR EXTERIOR LOCATIONS.
26. NONMETALLIC RECEPTACLE, SWITCH AND DEVICE BOXES SHALL MEET OR EXCEED NEMA OS 2 (NEWEST REVISION) AND BE RATED NEMA 1 (OR BETTER) FOR INTERIOR LOCATIONS AND WEATHER PROTECTED (WP OR BETTER) FOR EXTERIOR LOCATIONS.
27. THE CONTRACTOR SHALL NOTIFY AND OBTAIN NECESSARY AUTHORIZATION FROM THE CARRIER AND/OR DISH Wireless L.L.C. AND TOWER OWNER BEFORE COMMENCING WORK ON THE AC POWER DISTRIBUTION PANELS.
28. THE CONTRACTOR SHALL PROVIDE NECESSARY TAGGING ON THE BREAKERS, CABLES AND DISTRIBUTION PANELS IN ACCORDANCE WITH THE APPLICABLE CODES AND STANDARDS TO SAFEGUARD LIFE AND PROPERTY.
29. INSTALL LAMICOID LABEL ON THE METER CENTER TO SHOW "DISH Wireless L.L.C."
30. ALL EMPTY/SPARE CONDUITS THAT ARE INSTALLED ARE TO HAVE A METERED MULE TAPE PULL CORD INSTALLED.

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:

GIN --- ---

RFDS REV #: ---

CONSTRUCTION DOCUMENTS

SUBMITTALS

REV	DATE	DESCRIPTION
A	09/13/2022	ISSUED FOR REVIEW
O	12/21/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER

NJJER02052B

DISH Wireless L.L.C. PROJECT INFORMATION


NJJER02052B
200 ORONOQUE LANE
STRATFORD, CT 06614

SHEET TITLE

GENERAL NOTES

SHEET NUMBER

GN-4



GROUNDING NOTES:

1. ALL GROUND ELECTRODE SYSTEMS (INCLUDING TELECOMMUNICATION, RADIO, LIGHTNING PROTECTION AND AC POWER GES'S) SHALL BE BONDED TOGETHER AT OR BELOW GRADE, BY TWO OR MORE COPPER BONDING CONDUCTORS IN ACCORDANCE WITH THE NEC.
2. THE CONTRACTOR SHALL PERFORM IEEE FALL-OF-POTENTIAL RESISTANCE TO EARTH TESTING (PER IEEE 1100 AND 81) FOR GROUND ELECTRODE SYSTEMS, THE CONTRACTOR SHALL FURNISH AND INSTALL SUPPLEMENTAL GROUND ELECTRODES AS NEEDED TO ACHIEVE A TEST RESULT OF 5 OHMS OR LESS.
3. THE CONTRACTOR IS RESPONSIBLE FOR PROPERLY SEQUENCING GROUNDING AND UNDERGROUND CONDUIT INSTALLATION AS TO PREVENT ANY LOSS OF CONTINUITY IN THE GROUNDING SYSTEM OR DAMAGE TO THE CONDUIT AND PROVIDE TESTING RESULTS.
4. METAL CONDUIT AND TRAY SHALL BE GROUNDED AND MADE ELECTRICALLY CONTINUOUS WITH LISTED BONDING FITTINGS OR BY BONDING ACROSS THE DISCONTINUITY WITH #6 COPPER WIRE UL APPROVED GROUNDING TYPE CONDUIT CLAMPS.
5. METAL RACEWAY SHALL NOT BE USED AS THE NEC REQUIRED EQUIPMENT GROUND CONDUCTOR. STRANDED COPPER CONDUCTORS WITH GREEN INSULATION, SIZED IN ACCORDANCE WITH THE NEC, SHALL BE FURNISHED AND INSTALLED WITH THE POWER CIRCUITS TO BTS EQUIPMENT.
6. EACH CABINET FRAME SHALL BE DIRECTLY CONNECTED TO THE MASTER GROUND BAR WITH GREEN INSULATED SUPPLEMENTAL EQUIPMENT GROUND WIRES, #6 STRANDED COPPER OR LARGER FOR INDOOR BTS; #2 BARE SOLID TINNED COPPER FOR OUTDOOR BTS.
7. CONNECTIONS TO THE GROUND BUS SHALL NOT BE DOUBLED UP OR STACKED BACK TO BACK CONNECTIONS ON OPPOSITE SIDE OF THE GROUND BUS ARE PERMITTED.
8. ALL EXTERIOR GROUND CONDUCTORS BETWEEN EQUIPMENT/GROUND BARS AND THE GROUND RING SHALL BE #2 SOLID TINNED COPPER UNLESS OTHERWISE INDICATED.
9. ALUMINUM CONDUCTOR OR COPPER CLAD STEEL CONDUCTOR SHALL NOT BE USED FOR GROUNDING CONNECTIONS.
10. USE OF 90° BENDS IN THE PROTECTION GROUNDING CONDUCTORS SHALL BE AVOIDED WHEN 45° BENDS CAN BE ADEQUATELY SUPPORTED.
11. EXOTHERMIC WELDS SHALL BE USED FOR ALL GROUNDING CONNECTIONS BELOW GRADE.
12. ALL GROUND CONNECTIONS ABOVE GRADE (INTERIOR AND EXTERIOR) SHALL BE FORMED USING HIGH PRESS CRIMPS.
13. COMPRESSION GROUND CONNECTIONS MAY BE REPLACED BY EXOTHERMIC WELD CONNECTIONS.
14. ICE BRIDGE BONDING CONDUCTORS SHALL BE EXOTHERMICALY BONDED OR BOLTED TO THE BRIDGE AND THE TOWER GROUND BAR.
15. APPROVED ANTIOXIDANT COATINGS (i.e. CONDUCTIVE GEL OR PASTE) SHALL BE USED ON ALL COMPRESSION AND BOLTED GROUND CONNECTIONS.
16. ALL EXTERIOR GROUND CONNECTIONS SHALL BE COATED WITH A CORROSION RESISTANT MATERIAL.
17. MISCELLANEOUS ELECTRICAL AND NON-ELECTRICAL METAL BOXES, FRAMES AND SUPPORTS SHALL BE BONDED TO THE GROUND RING, IN ACCORDANCE WITH THE NEC.
18. BOND ALL METALLIC OBJECTS WITHIN 6 ft OF MAIN GROUND RING WITH (1) #2 BARE SOLID TINNED COPPER GROUND CONDUCTOR.
19. GROUND CONDUCTORS USED FOR THE FACILITY GROUNDING AND LIGHTNING PROTECTION SYSTEMS SHALL NOT BE ROUTED THROUGH METALLIC OBJECTS THAT FORM A RING AROUND THE CONDUCTOR, SUCH AS METALLIC CONDUITS, METAL SUPPORT CLIPS OR SLEEVES THROUGH WALLS OR FLOORS. WHEN IT IS REQUIRED TO BE HOUSED IN CONDUIT TO MEET CODE REQUIREMENTS OR LOCAL CONDITIONS, NON-METALLIC MATERIAL SUCH AS PVC CONDUIT SHALL BE USED. WHERE USE OF METAL CONDUIT IS UNAVOIDABLE (i.e., NONMETALLIC CONDUIT PROHIBITED BY LOCAL CODE) THE GROUND CONDUCTOR SHALL BE BONDED TO EACH END OF THE METAL CONDUIT.
20. ALL GROUNDS THAT TRANSITION FROM BELOW GRADE TO ABOVE GRADE MUST BE #2 BARE SOLID TINNED COPPER IN 3/4" NON-METALLIC, FLEXIBLE CONDUIT FROM 24" BELOW GRADE TO WITHIN 3" TO 6" OF CAD-WELD TERMINATION POINT. THE EXPOSED END OF THE CONDUIT MUST BE SEALED WITH SILICONE CAULK. (ADD TRANSITIONING GROUND STANDARD DETAIL AS WELL).
21. BUILDINGS WHERE THE MAIN GROUNDING CONDUCTORS ARE REQUIRED TO BE ROUTED TO GRADE, THE CONTRACTOR SHALL ROUTE TWO GROUNDING CONDUCTORS FROM THE ROOFTOP, TOWERS, AND WATER TOWERS GROUNDING RING, TO THE EXISTING GROUNDING SYSTEM, THE GROUNDING CONDUCTORS SHALL NOT BE SMALLER THAN 2/0 COPPER. ROOFTOP GROUNDING RING SHALL BE BONDED TO THE EXISTING GROUNDING SYSTEM, THE BUILDING STEEL COLUMNS, LIGHTNING PROTECTION SYSTEM, AND BUILDING MAIN WATER LINE (FERROUS OR NONFERROUS METAL PIPING ONLY). DO NOT ATTACH GROUNDING TO FIRE SPRINKLER SYSTEM PIPES.

dish
wireless.
5701 SOUTH SANTA FE DRIVE
LITTLETON, CO 80120

MK
DEVELOPMENT
140 BEACH 137TH STREET
ROCKAWAY, NY 11694



IT IS A VIOLATION OF LAW FOR ANY PERSON,
UNLESS THEY ARE ACTING UNDER THE DIRECTION
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

DRAWN BY: CHECKED BY: APPROVED BY:
GIN --- ---

RFDS REV #: ---

CONSTRUCTION DOCUMENTS**SUBMITTALS**

REV	DATE	DESCRIPTION
A	09/13/2022	ISSUED FOR REVIEW
O	12/21/2022	ISSUED FOR CONSTRUCTION

A&E PROJECT NUMBER
NJJER02052B

DISH Wireless L.L.C.
PROJECT INFORMATION
NJJER02052B
200 ORONOQUE LANE
STRATFORD, CT 06614

SHEET TITLE
GENERAL NOTES

SHEET NUMBER
GN-5



Amended EXHIBIT D

Structural Analysis



August 9, 2022

PASS

RE: Structural Analysis for Tower

Location: 200 Oronoque lane Stratford, CT 06614

Site ID: NJJER02052B

Dish Wireless LLC,

Per your request, we have performed a structural analysis of the existing tower. This site consists of an existing monopole that has multiple carriers co-located on the tower. This review determines if the tower can support the existing and proposed loads.

1.0 Assumptions:

CATEGORY	DATA	CODE
Structure Type	Monopole	
Top of Tower	150'-0"	
Structure Class	IV	ASCE 7-16
Exposure Class	C	ASCE 7-16
Kzt Factor	1.0	ASCE 7-16
Basic Wind Speed	135	2022 Connecticut SBC
Ice Thickness	1"	ASCE 7-16
Ice Windspeed	50 MPH	ASCE 7-16
Seismic Design Category	C	ASCE 7-16
S _{DS}	.218	ASCE 7-16

2.0 Existing Documents:

DOCUMENT	COMPANY	DATE
Proposed Drawings	M&K Development	12/16/2021
Site Visit Photos	M&K Development	8/2/2021
Structural Analysis	Fullerton Engineering	5/31/2022



3.0 Proposed Equipment:

MANUFACTURER	EQUIPMENT	WEIGHTS
CommScope	(1) MC-PK8-DSH	1802 lbs
CommScope	(3) FFVV-65B-R2	70.54 lbs
Fujitsu	(3) TA08025-B604	63.9 lbs
Fujitsu	(3) TA08025-B605	74.9 lbs
RayCap	(1) OVP RDIDC-9181-PF-48	32 lbs
CommScope	(1) HYBRID CABLE	N.A.

Bold represents equipment to be added

It is assumed that all information from the previous analysis performed by Fullerton Engineering on May 31, 2022 is still accurate and correct. If this assumption is not true, please contact our office for an amended report.

We are installing (1) proposed MC-PK8-DSH mount on the existing monopole that will support all the proposed equipment. After performing an analysis on the tower in TNxTower, it has been determined that the tower is **ADEQUATE** for the existing and proposed loads on the structure which passes at 89.1% of its capacity.

This report does not address the structural stability of any other mounts, or portion of the structure, nor does it provide any warranty either express or implied, for any portion of the proposed mount or structure.

Please note that we have not had a professional engineer perform an independent visit to confirm existing structural conditions and the outcome of this analysis is based solely on the information provided in the previous structural analysis, photos and drawing details. If the existing conditions are modified, in disrepair or not properly represented, contact our office immediately for an amended report since this analysis may be inaccurate.



If you have any questions, feel free to contact us at any time.

Sincerely,

Magaram Engineering





Brett Magaram
Connecticut License # 33678
Brett@MagaramEngineering.com
Phone: 914-450-8416

ASCE 7 Hazards Report

Address:
200 Oronoque Ln
Stratford, Connecticut
06614

Standard: ASCE/SEI 7-16
Risk Category: IV
Soil Class: D - Default (see
Section 11.4.3)

Elevation: 256.3 ft (NAVD 88)
Latitude: 41.251254
Longitude: -73.11699







Seismic

Site Soil Class: D - Default (see Section 11.4.3)

Results:

S_s :	0.205	S_{D1} :	0.086
S_1 :	0.054	T_L :	6
F_a :	1.6	PGA :	0.115
F_v :	2.4	PGA_M :	0.181
S_{MS} :	0.327	F_{PGA} :	1.569
S_{M1} :	0.129	I_e :	1.5
S_{DS} :	0.218	C_v :	0.709

Seismic Design Category C



Data Accessed:

Tue Aug 09 2022

Date Source:

USGS Seismic Design Maps based on ASCE/SEI 7-16 and ASCE/SEI 7-16 Table 1.5-2. Additional data for site-specific ground motion procedures in accordance with ASCE/SEI 7-16 Ch. 21 are available from USGS.

Ice

Results:

Ice Thickness: 1.00 in.

Concurrent Temperature: 15 F

Gust Speed 50 mph

Data Source: Standard ASCE/SEI 7-16, Figs. 10-2 through 10-8

Date Accessed: Tue Aug 09 2022

Ice thicknesses on structures in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.

Values provided are equivalent radial ice thicknesses due to freezing rain with concurrent 3-second gust speeds, for a 500-year mean recurrence interval, and temperatures concurrent with ice thicknesses due to freezing rain. Thicknesses for ice accretions caused by other sources shall be obtained from local meteorological studies. Ice thicknesses in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.

The ASCE 7 Hazard Tool is provided for your convenience, for informational purposes only, and is provided "as is" and without warranties of any kind. The location data included herein has been obtained from information developed, produced, and maintained by third party providers; or has been extrapolated from maps incorporated in the ASCE 7 standard. While ASCE has made every effort to use data obtained from reliable sources or methodologies, ASCE does not make any representations or warranties as to the accuracy, completeness, reliability, currency, or quality of any data provided herein. Any third-party links provided by this Tool should not be construed as an endorsement, affiliation, relationship, or sponsorship of such third-party content by or from ASCE.

ASCE does not intend, nor should anyone interpret, the results provided by this Tool to replace the sound judgment of a competent professional, having knowledge and experience in the appropriate field(s) of practice, nor to substitute for the standard of care required of such professionals in interpreting and applying the contents of this Tool or the ASCE 7 standard.

In using this Tool, you expressly assume all risks associated with your use. Under no circumstances shall ASCE or its officers, directors, employees, members, affiliates, or agents be liable to you or any other person for any direct, indirect, special, incidental, or consequential damages arising from or related to your use of, or reliance on, the Tool or any information obtained therein. To the fullest extent permitted by law, you agree to release and hold harmless ASCE from any and all liability of any nature arising out of or resulting from any use of data provided by the ASCE 7 Hazard Tool.

Municipality	Basic Design Wind Speeds, V (mph)				Allowable Stress Design Wind Speeds, V_{asd} (mph)				Ground Snow Load p_g (psf)	MCE Ground Accelerations		Wind-Borne Debris Region ¹		Hurricane- Prone Region
	Risk Cat. I	Risk Cat. II	Risk Cat. III	Risk Cat. IV	Risk Cat. I	Risk Cat. II	Risk Cat. III	Risk Cat. IV		S_s (g)	S_I (g)	Risk Cat. III Occup. I-2	Risk Cat. IV	
Sherman	110	115	125	130	85	89	97	101	35	0.203	0.055			
Simsbury	110	120	125	130	85	93	97	101	35	0.177	0.054			Yes
Somers	110	120	130	135	85	93	101	105	35	0.174	0.055			Yes
South Windsor	110	120	130	135	85	93	101	105	30	0.183	0.055			Yes
Southbury	110	120	130	130	85	93	101	101	35	0.199	0.054			Yes
Southington	110	120	130	135	85	93	101	105	30	0.196	0.055			Yes
Sprague	115	125	135	140	89	97	105	108	30	0.191	0.054			Yes
Stafford	110	120	130	135	85	93	101	105	35	0.176	0.055			Yes
Stamford	110	120	130	135	85	93	101	105	30	0.261	0.058		Type B	Yes
Sterling	115	125	135	140	89	97	105	108	35	0.187	0.054			Yes
Stonington	120	130	140	145	93	101	108	112	30	0.182	0.051	Type B	Type A	Yes
Stratford	110	120	130	135	85	93	101	105	30	0.206	0.054		Type B	Yes
Suffield	110	120	125	130	85	93	97	101	35	0.170	0.054			Yes
Thomaston	110	120	125	130	85	93	97	101	35	0.184	0.054			Yes
Thompson	110	120	130	135	85	93	101	105	40	0.185	0.056			Yes
Tolland	110	120	130	135	85	93	101	105	35	0.182	0.055			Yes
Torrington	110	115	125	130	85	89	97	101	40	0.175	0.054			
Trumbull	110	120	130	135	85	93	101	105	30	0.210	0.054			Yes
Union	110	120	130	135	85	93	101	105	40	0.178	0.055			Yes
Vernon	110	120	130	135	85	93	101	105	30	0.186	0.055			Yes
Voluntown	120	130	135	140	93	101	105	108	30	0.188	0.053			Yes
Wallingford	110	120	130	135	85	93	101	105	30	0.205	0.055			Yes
Warren	110	115	125	130	85	89	97	101	40	0.179	0.054			
Washington	110	115	125	130	85	89	97	101	35	0.189	0.054			
Waterbury	110	120	130	135	85	93	101	105	35	0.193	0.054			Yes
Waterford	120	130	140	140	93	101	108	108	30	0.194	0.053	Type B	Type B	Yes
Watertown	110	120	130	130	85	93	101	101	35	0.189	0.054			Yes
West Hartford	110	120	130	135	85	93	101	105	30	0.187	0.055			Yes
West Haven	110	125	130	135	85	97	101	105	30	0.200	0.053	Type B	Type B	Yes
Westbrook	115	125	135	140	89	97	105	108	30	0.204	0.054	Type B	Type B	Yes
Weston	110	120	130	135	85	93	101	105	30	0.233	0.056			Yes
Westport	110	120	130	135	85	93	101	105	30	0.232	0.056		Type B	Yes

DESIGNED APPURTEINANCE LOADING

TYPE	ELEVATION	TYPE	ELEVATION
20' Omni (Town)	150	RRUS32 (ATI)	123
20' Omni (Town)	150	Radio 4478 (ATI)	123
8' Dipole (Town)	150	RRU 8843 (ATI)	123
8' Dipole (Town)	150	TPA65R-BU6D (ATI)	123
Pirod 4' Side Mount Standoff (1) (Town)	150	AIR6449 (ATI)	123
Pirod 4' Side Mount Standoff (1) (Town)	150	AIR6419 (ATI)	123
Pirod 4' Side Mount Standoff (1) (Town)	150	DMP65R-BU8DA-K (ATI)	123
Pirod 4' Side Mount Standoff (1) (Town)	150	Radio 4449 (ATI)	123
Andrew HP6	142	RRUS32 (ATI)	123
10' Omni (Town)	134	Radio 4478 (ATI)	123
8' Dipole (Town)	134	RRU 8843 (ATI)	123
8' Dipole (Town)	134	RMQP-NP (12' Platform) (ATI)	123
Pirod 4' Side Mount Standoff (1) (Town)	134	RDIDC-9181-PF-48 (ATI)	123
Pirod 4' Side Mount Standoff (1) (Town)	134	RDIDC-9181-PF-48 (ATI)	123
Pirod 4' Side Mount Standoff (1) (Town)	134	TPA65R-BU6D (ATI)	123
10' Omni (Town)	134	FFVV-65B-R2 (DISH)	111
AIR6449 (ATI)	123	TA08025-B604 (DISH)	111
AIR6419 (ATI)	123	TA08025-B604 (DISH)	111
DMP65R-BU8DA-K (ATI)	123	RDIDC-9181-PF-48 (DISH)	111
Radio 4449 (ATI)	123	FFVV-65B-R2 (DISH)	111
RRUS32 (ATI)	123	TA08025-B604 (DISH)	111
Radio 4478 (ATI)	123	TA08025-B604 (DISH)	111
RRU 8843 (ATI)	123	RDIDC-9181-PF-48 (DISH)	111
TPA65R-BU6D (ATI)	123	MC-PK8-DSH (DISH)	111
AIR6449 (ATI)	123	FFVV-65B-R2 (DISH)	111
AIR6419 (ATI)	123	TA08025-B604 (DISH)	111
DMP65R-BU8DA-K (ATI)	123	TA08025-B604 (DISH)	111
Radio 4449 (ATI)	123	RDIDC-9181-PF-48 (DISH)	111


MATERIAL STRENGTH

GRADE	Fy	Fu	GRADE	Fy	Fu
A572-65	65 ksi	80 ksi			

TOWER DESIGN NOTES

1. Tower designed for Exposure C to the TIA-222-H Standard.
2. Tower designed for a 135 mph basic wind in accordance with the TIA-222-H Standard.
3. Tower is also designed for a 50 mph basic wind with 1.00 in ice. Ice is considered to increase in thickness with height.
4. Deflections are based upon a 60 mph wind.
5. Tower Risk Category IV.
6. Topographic Category 1 with Crest Height of 0.00 ft
7. Weld together tower sections have flange connections.
8. Connections use galvanized A325 bolts, nuts and locking devices. Installation per TIA/EIA-222 and AISC Specifications.
9. Tower members are "hot dipped" galvanized in accordance with ASTM A123 and ASTM A153 Standards.
10. Welds are fabricated with ER-70S-6 electrodes.
11. TOWER RATING: 88%

ALL REACTIONS
ARE FACTORED



Section	1	2	3
Length (ft)	52.75	53.50	53.25
Number of Sides	18	18	18
Thickness (in)	0.3125	0.3125	0.3750
Socket Length (ft)	6.00	6.00	6.00
Top Dia (in)	42.1900	30.2568	40.2267
Bot Dia (in)	52.1000	52.1000	40.2267
Grade	A572-65	A572-65	A572-65
Weight (lb)	9875.3	9875.3	20010.2

Magaram Engineering

13705 Stone Shadow

Clifton VA

Phone: 914-450-8416

FAX:

Job: **NJJER02052B**

Project:

Client: Dish Wireless LLC

Drawn by:

App'd:

Code: TIA-222-H

Date: 09/20/22

Scale: NTS

Path: C:\Users\Brett Laptop 2019\Desktop\Tower Analysis\NJJER02052B Tower Model.xls

Dwg No. E-1

Feed Line Distribution Chart

1' - 150'

Round

Flat

App In Face


App Out Face

Truss Leg

Face A

Face B



Face C



Magaram Engineering
13705 Stone Shadow
Clifton VA
Phone: 914-450-8416
FAX:

Job: **NJJER02052B**

Project:	
Client: Dish Wireless LLC	Drawn by:
Code: TIA-222-H	Date: 08/09/22
Scale: NTS	
Path: C:\Users\Brett Laptop 2019\Desktop\Magaram Engineering\MK Development\NJJER02052B\Tower Analysis\NJJER02052B Tower Model.dwg	
Dwg No. E-7	



FOUNDATION NOTES

1. Plate thickness is 2.5000 in.
2. Plate grade is A572-50.
3. Anchor bolt grade is A325X.
4. f_c is 3 ksi.

Magaram Engineering
13705 Stone Shadow
Clifton VA
Phone: 914-450-8416
FAX:

Job:	NJJER02052B		
Project:			
Client:	Dish Wireless LLC	Drawn by:	App'd:
Code:	TIA-222-H	Date: 08/09/22	Scale: NTS
Path:	C:\Users\Brett Laptop 2019\Desktop\Magaram Engineering\MK Development\NJJER02052B\Tower Analysis\NJJER02052B Tower Model.dwg		

tnxTower	Job NJJER02052B	Page 1 of 21
Magaram Engineering 13705 Stone Shadow Clifton VA Phone: 914-450-8416 FAX:	Project	Date 09:15:26 09/20/22
	Client Dish Wireless LLC	Designed by

Tower Input Data

The tower is a monopole.

This tower is designed using the TIA-222-H standard.

The following design criteria apply:

Tower base elevation above sea level: 1.00 ft.

Basic wind speed of 135 mph.

Risk Category IV.

Exposure Category C.

Simplified Topographic Factor Procedure for wind speed-up calculations is used.

Topographic Category: 1.

Crest Height: 0.00 ft.

Nominal ice thickness of 1.0000 in.

Ice thickness is considered to increase with height.

Ice density of 56 pcf.

A wind speed of 50 mph is used in combination with ice.

Temperature drop of 50 °F.

Deflections calculated using a wind speed of 60 mph.

Weld together tower sections have flange connections..

Connections use galvanized A325 bolts, nuts and locking devices. Installation per TIA/EIA-222 and AISC Specifications..

Tower members are "hot dipped" galvanized in accordance with ASTM A123 and ASTM A153 Standards..

Welds are fabricated with ER-70S-6 electrodes..

A non-linear (P-delta) analysis was used.

Pressures are calculated at each section.

Stress ratio used in pole design is 1.

Local bending stresses due to climbing loads, feed line supports, and appurtenance mounts are not considered.

Options

Consider Moments - Legs	Distribute Leg Loads As Uniform	Use ASCE 10 X-Brace Ly Rules
Consider Moments - Horizontals	Assume Legs Pinned	✓ Calculate Redundant Bracing Forces
Consider Moments - Diagonals	✓ Assume Rigid Index Plate	Ignore Redundant Members in FEA
Use Moment Magnification	✓ Use Clear Spans For Wind Area	SR Leg Bolts Resist Compression
✓ Use Code Stress Ratios	✓ Use Clear Spans For KL/r	✓ All Leg Panels Have Same Allowable
✓ Use Code Safety Factors - Guys	✓ Retension Guys To Initial Tension	Offset Girt At Foundation
Escalate Ice	Bypass Mast Stability Checks	✓ Consider Feed Line Torque
Always Use Max Kz	✓ Use Azimuth Dish Coefficients	✓ Include Angle Block Shear Check
Use Special Wind Profile	✓ Project Wind Area of Appurt.	Use TIA-222-H Bracing Resist. Exemption
✓ Include Bolts In Member Capacity	✓ Autocalc Torque Arm Areas	Use TIA-222-H Tension Splice Exemption
✓ Leg Bolts Are At Top Of Section	Add IBC .6D+W Combination	Poles
✓ Secondary Horizontal Braces Leg	Sort Capacity Reports By Component	Include Shear-Torsion Interaction
Use Diamond Inner Bracing (4 Sided)	Triangulate Diamond Inner Bracing	Always Use Sub-Critical Flow
SR Members Have Cut Ends	Treat Feed Line Bundles As Cylinder	Use Top Mounted Sockets
SR Members Are Concentric	Ignore KL/ry For 60 Deg. Angle Legs	Pole Without Linear Attachments
		Pole With Shroud Or No Appurtenances
		Outside and Inside Corner Radii Are Known

tnxTower Magaram Engineering 13705 Stone Shadow Clifton VA Phone: 914-450-8416 FAX:	Job	NJJER02052B	Page
	Project		Date 09:15:26 09/20/22
	Client	Dish Wireless LLC	Designed by

Tapered Pole Section Geometry

Section	Elevation	Section Length	Splice Length	Number of Sides	Top Diameter	Bottom Diameter	Wall Thickness	Bend Radius	Pole Grade
	ft	ft	ft		in	in	in	in	
L1	150.00-97.25	52.75	4.50	18	20.0000	31.7600	0.2500	1.0000	A572-65 (65 ksi)
L2	97.25-48.25	53.50	6.00	18	30.2568	42.1900	0.3125	1.2500	A572-65 (65 ksi)
L3	48.25-1.00	53.25		18	40.2267	52.1000	0.3750	1.5000	A572-65 (65 ksi)

Tapered Pole Properties

Section	Tip Dia.	Area	I	r	C	I/C	J	It/Q	w	w/t
	in	in ²	in ⁴	in	in	in ³	in ⁴	in ²	in	
L1	20.2700	15.6716	772.2994	7.0112	10.1600	76.0137	1545.6150	7.8373	3.0800	12.32
	32.2114	25.0032	3136.3866	11.1861	16.1341	194.3951	6276.9002	12.5040	5.1498	20.599
L2	31.6945	29.7010	3364.6190	10.6302	15.3704	218.9019	6733.6652	14.8533	4.7752	15.281
	42.7926	41.5372	9203.1529	14.8665	21.4325	429.4013	18418.4155	20.7726	6.8754	22.001
L3	42.1479	47.4335	9517.3498	14.1474	20.4352	465.7340	19047.2229	23.7212	6.4199	17.12
	52.8459	61.5657	20810.2424	18.3624	26.4668	786.2772	41647.8674	30.7887	8.5096	22.692

Tower Elevation	Gusset Area (per face)	Gusset Thickness	Gusset Grade	Adjust. Factor <i>A_f</i>	Adjust. Factor <i>A_r</i>	Weight Mult.	Double Angle Stitch Bolt Spacing Diagonals	Double Angle Stitch Bolt Spacing Horizontals	Double Angle Stitch Bolt Spacing Redundants
ft	ft ²	in					in	in	in
L1				1	1	1			
150.00-97.25									
L2 97.25-48.25				1	1	1			
L3 48.25-1.00				1	1	1			

Monopole Base Plate Data

Base Plate Data

Base plate is square	
Base plate is grouted	
Anchor bolt grade	A325X
Anchor bolt size	2.2500 in
Number of bolts	14
Embedment length	84.0000 in
<i>f_c</i>	3 ksi
Grout space	2.0000 in
Base plate grade	A572-50
Base plate thickness	2.5000 in
Bolt circle diameter	58.5000 in
Outer diameter	64.5000 in
Inner diameter	50.5000 in
Base plate type	Plain Plate

tnxTower Magaram Engineering 13705 Stone Shadow Clifton VA Phone: 914-450-8416 FAX:	Job	NJJER02052B	Page 3 of 21
	Project		Date 09:15:26 09/20/22
	Client	Dish Wireless LLC	Designed by

Feed Line/Linear Appurtenances - Entered As Round Or Flat

Description	Sector	Exclude From Torque Calculation	Component Type	Placement ft	Total Number	Number Per Row	Start/End Position	Width or Diameter in	Perimeter in	Weight plf
Step Bolts	C	No	Surface Ar (CaAa)	150.00 - 1.00	1	1	0.000	0.7500		0.48
Safety Line 3/8	C	No	Surface Ar (CaAa)	150.00 - 1.00	1	1	0.000	0.3750		0.22

Feed Line/Linear Appurtenances - Entered As Area

Description	Face or Leg	Allow Shield	Exclude From Torque Calculation	Component Type	Placement ft	Total Number	CAAA	Weight
							ft ² /ft	plf

Generic Hybrid	C	No	No	Inside Pole	150.00 - 1.00	6	No Ice 1/2" Ice 1" Ice	0.00 0.00 0.00
								1.90 1.90 1.90
*								
3/4 Power (TMO)	C	No	No	Inside Pole	123.00 - 9.00	6	No Ice 1/2" Ice 1" Ice	0.00 0.00 0.00
								0.40 0.40 0.40
1/2 Fiber (TMO)								
RET Cable (TMO)	C	No	No	Inside Pole	123.00 - 9.00	3	No Ice 1/2" Ice 1" Ice	0.00 0.00 0.00
								0.15 0.15 0.15
* Generic Hybrid (DISH)								
Generic Hybrid (DISH)	C	No	No	Inside Pole	111.00 - 9.00	1	No Ice 1/2" Ice 1" Ice	0.00 0.00 0.00
								1.90 1.90 1.90

Feed Line/Linear Appurtenances Section Areas

Tower Section	Tower Elevation ft	Face	Ar ft ²	Af ft ²	CAA In Face ft ²	CAA Out Face ft ²	Weight lb
L1	150.00-97.25	A	0.000	0.000	0.000	0.000	0.00
		B	0.000	0.000	0.000	0.000	0.00
		C	0.000	0.000	5.934	0.000	757.10
L2	97.25-48.25	A	0.000	0.000	0.000	0.000	0.00
		B	0.000	0.000	0.000	0.000	0.00
		C	0.000	0.000	5.513	0.000	862.40
L3	48.25-1.00	A	0.000	0.000	0.000	0.000	0.00
		B	0.000	0.000	0.000	0.000	0.00
		C	0.000	0.000	5.316	0.000	787.60

Feed Line/Linear Appurtenances Section Areas - With Ice

tnxTower Magaram Engineering 13705 Stone Shadow Clifton VA Phone: 914-450-8416 FAX:	Job	NJJER02052B	Page
	Project		Date 09:15:26 09/20/22
	Client	Dish Wireless LLC	Designed by

Tower Section	Tower Elevation ft	Face or Leg	Ice Thickness in	A_R ft ²	A_F ft ²	C_{AA} In Face ft ²	C_{AA} Out Face ft ²	Weight lb
L1	150.00-97.25	A	1.425	0.000	0.000	0.000	0.000	0.00
		B		0.000	0.000	0.000	0.000	0.00
		C		0.000	0.000	35.992	0.000	1121.93
L2	97.25-48.25	A	1.351	0.000	0.000	0.000	0.000	0.00
		B		0.000	0.000	0.000	0.000	0.00
		C		0.000	0.000	33.433	0.000	1201.30
L3	48.25-1.00	A	1.215	0.000	0.000	0.000	0.000	0.00
		B		0.000	0.000	0.000	0.000	0.00
		C		0.000	0.000	30.857	0.000	1086.20

Feed Line Center of Pressure

Section	Elevation ft	CP_x in	CP_z in	CP_x Ice in	CP_z Ice in
L1	150.00-97.25	0.0000	0.8725	0.0000	2.5129
L2	97.25-48.25	0.0000	0.8834	0.0000	2.7206
L3	48.25-1.00	0.0000	0.8893	0.0000	2.7417

Note: For pole sections, center of pressure calculations do not consider feed line shielding.

Shielding Factor Ka

Tower Section	Feed Line Record No.	Description	Feed Line Segment Elev.	K_a No Ice	K_a Ice
L1	1	Step Bolts	97.25 - 150.00	1.0000	1.0000
L1	2	Safety Line 3/8	97.25 - 150.00	1.0000	1.0000
L2	1	Step Bolts	48.25 - 97.25	1.0000	1.0000
L2	2	Safety Line 3/8	48.25 - 97.25	1.0000	1.0000
L3	1	Step Bolts	1.00 - 48.25	1.0000	1.0000
L3	2	Safety Line 3/8	1.00 - 48.25	1.0000	1.0000

Discrete Tower Loads

Description	Face or Leg	Offset Type	Offsets: Horz Lateral Vert ft ft ft	Azimuth Adjustment °	Placement ft	C_{AA} Front	C_{AA} Side	Weight lb	
20' Omni	A	From Face	4.00	90.0000	150.00	No Ice	6.70	6.70	150.00

tnxTower Magaram Engineering 13705 Stone Shadow Clifton VA Phone: 914-450-8416 FAX:	Job NJJER02052B							Page 5 of 21
	Project							Date 09:15:26 09/20/22
	Client Dish Wireless LLC							Designed by

Description	Face or Leg	Offset Type	Offsets: Horz Lateral Vert ft ft ft	Azimuth Adjustment °	Placement ft	CAA _A Front ft ²	CAA _A Side ft ²	Weight lb
(Town)			0.00 10.00		1/2" Ice 1" Ice	9.04 11.09	9.04 11.09	199.38 261.50
20' Omni (Town)	C	From Face	4.00 0.00 10.00	30.0000	150.00	No Ice 1/2" Ice 1" Ice	6.70 9.04 11.09	150.00 199.38 261.50
8' Dipole (Town)	B	From Face	4.00 0.00 4.00	90.0000	150.00	No Ice 1/2" Ice 1" Ice	1.60 2.42 3.24	20.00 32.45 50.41
8' Dipole (Town)	B	From Face	4.00 0.00 4.00	-90.0000	150.00	No Ice 1/2" Ice 1" Ice	1.60 2.42 3.24	20.00 32.45 50.41
10' Omni (Town)	A	From Face	4.00 0.00 5.00	90.0000	134.00	No Ice 1/2" Ice 1" Ice	3.39 4.54 5.30	75.00 99.95 131.52
10' Omni (Town)	C	From Face	4.00 0.00 5.00	30.0000	134.00	No Ice 1/2" Ice 1" Ice	3.39 4.54 5.30	75.00 99.95 131.52
8' Dipole (Town)	B	From Face	4.00 0.00 4.00	90.0000	134.00	No Ice 1/2" Ice 1" Ice	1.60 2.42 3.24	20.00 32.45 50.41
8' Dipole (Town)	B	From Face	4.00 0.00 4.00	-90.0000	134.00	No Ice 1/2" Ice 1" Ice	1.60 2.42 3.24	20.00 32.45 50.41
Pirod 4' Side Mount Standoff (1) (Town)	A	From Face	2.00 0.00 0.00	0.0000	150.00	No Ice 1/2" Ice 1" Ice	2.72 4.91 7.10	50.00 89.00 128.00
Pirod 4' Side Mount Standoff (1) (Town)	B	From Face	2.00 0.00 0.00	0.0000	150.00	No Ice 1/2" Ice 1" Ice	2.72 4.91 7.10	50.00 89.00 128.00
Pirod 4' Side Mount Standoff (1) (Town)	C	From Face	2.00 0.00 0.00	0.0000	150.00	No Ice 1/2" Ice 1" Ice	2.72 4.91 7.10	50.00 89.00 128.00
Pirod 4' Side Mount Standoff (1) (Town)	C	From Face	2.00 0.00 0.00	30.0000	150.00	No Ice 1/2" Ice 1" Ice	2.72 4.91 7.10	50.00 89.00 128.00
Pirod 4' Side Mount Standoff (1) (Town)	A	From Face	2.00 0.00 0.00	0.0000	134.00	No Ice 1/2" Ice 1" Ice	2.72 4.91 7.10	50.00 89.00 128.00
Pirod 4' Side Mount Standoff (1) (Town)	B	From Face	2.00 0.00 0.00	0.0000	134.00	No Ice 1/2" Ice 1" Ice	2.72 4.91 7.10	50.00 89.00 128.00
Pirod 4' Side Mount Standoff (1) (Town)	C	From Face	2.00 0.00 0.00	0.0000	134.00	No Ice 1/2" Ice 1" Ice	2.72 4.91 7.10	50.00 89.00 128.00
TPA65R-BU6D (AT&T)	A	From Face	4.00 0.00 0.00	0.0000	123.00	No Ice 1/2" Ice 1" Ice	13.20 13.91 14.59	97.50 192.55 296.34
AIR6449 (AT&T)	A	From Face	4.00 0.00 0.00	0.0000	123.00	No Ice 1/2" Ice 1" Ice	5.65 5.96 6.26	100.00 140.00 180.00
AIR6419 (AT&T)	A	From Face	4.00 0.00 0.00	0.0000	123.00	No Ice 1/2" Ice 1" Ice	3.80 4.05 4.31	77.00 104.86 136.30

tnxTower Magaram Engineering 13705 Stone Shadow Clifton VA Phone: 914-450-8416 FAX:	Job NJJER02052B							Page 6 of 21
	Project							Date 09:15:26 09/20/22
	Client Dish Wireless LLC							Designed by

Description	Face or Leg	Offset Type	Offsets: Horz Lateral Vert ft ft ft	Azimuth Adjustment °	Placement ft	CAA Front ft ²	CAA Side ft ²	Weight lb
DMP65R-BU8DA-K (AT&T)	A	From Face	4.00 0.00 0.00	0.0000	123.00	No Ice 1/2" Ice 1" Ice	17.87 18.50 19.14	10.02 11.44 12.72
Radio 4449 (AT&T)	A	From Face	4.00 0.00 0.00	0.0000	123.00	No Ice 1/2" Ice 1" Ice	1.64 1.80 1.97	1.29 1.44 1.59
RRUS32 (AT&T)	A	From Face	4.00 0.00 0.00	0.0000	123.00	No Ice 1/2" Ice 1" Ice	3.31 3.56 3.81	2.42 2.64 2.86
Radio 4478 (AT&T)	A	From Face	4.00 0.00 0.00	0.0000	123.00	No Ice 1/2" Ice 1" Ice	1.84 2.01 2.19	1.06 1.20 1.34
RRU 8843 (AT&T)	A	From Face	4.00 0.00 0.00	0.0000	123.00	No Ice 1/2" Ice 1" Ice	1.64 1.80 1.97	1.35 1.50 1.65
*								
TPA65R-BU6D (AT&T)	B	From Face	4.00 0.00 0.00	0.0000	123.00	No Ice 1/2" Ice 1" Ice	13.20 13.91 14.59	7.52 8.80 9.93
AIR6449 (AT&T)	B	From Face	4.00 0.00 0.00	0.0000	123.00	No Ice 1/2" Ice 1" Ice	5.65 5.96 6.26	2.42 2.64 2.87
AIR6419 (AT&T)	B	From Face	4.00 0.00 0.00	0.0000	123.00	No Ice 1/2" Ice 1" Ice	3.80 4.05 4.31	1.94 2.14 2.34
DMP65R-BU8DA-K (AT&T)	B	From Face	4.00 0.00 0.00	0.0000	123.00	No Ice 1/2" Ice 1" Ice	17.87 18.50 19.14	10.02 11.44 12.72
Radio 4449 (AT&T)	B	From Face	4.00 0.00 0.00	0.0000	123.00	No Ice 1/2" Ice 1" Ice	1.64 1.80 1.97	1.29 1.44 1.59
RRUS32 (AT&T)	B	From Face	4.00 0.00 0.00	0.0000	123.00	No Ice 1/2" Ice 1" Ice	3.31 3.56 3.81	2.42 2.64 2.86
Radio 4478 (AT&T)	B	From Face	4.00 0.00 0.00	0.0000	123.00	No Ice 1/2" Ice 1" Ice	1.84 2.01 2.19	1.06 1.20 1.34
RRU 8843 (AT&T)	B	From Face	4.00 0.00 0.00	0.0000	123.00	No Ice 1/2" Ice 1" Ice	1.64 1.80 1.97	1.35 1.50 1.65
*								
TPA65R-BU6D (AT&T)	C	From Face	4.00 0.00 0.00	0.0000	123.00	No Ice 1/2" Ice 1" Ice	13.20 13.91 14.59	7.52 8.80 9.93
AIR6449 (AT&T)	C	From Face	4.00 0.00 0.00	0.0000	123.00	No Ice 1/2" Ice 1" Ice	5.65 5.96 6.26	2.42 2.64 2.87
AIR6419 (AT&T)	C	From Face	4.00 0.00 0.00	0.0000	123.00	No Ice 1/2" Ice 1" Ice	3.80 4.05 4.31	1.94 2.14 2.34
DMP65R-BU8DA-K (AT&T)	C	From Face	4.00 0.00 0.00	0.0000	123.00	No Ice 1/2" Ice 1" Ice	17.87 18.50 19.14	10.02 11.44 12.72
Radio 4449 (AT&T)	C	From Face	4.00 0.00 0.00	0.0000	123.00	No Ice 1/2" Ice 1" Ice	1.64 1.80 1.97	1.29 1.44 1.59
RRUS32	C	From Face	4.00	0.0000	123.00	No Ice	3.31	2.42

tnxTower Magaram Engineering 13705 Stone Shadow Clifton VA Phone: 914-450-8416 FAX:	Job NJJER02052B							Page 7 of 21
	Project							Date 09:15:26 09/20/22
	Client Dish Wireless LLC							Designed by

Description	Face or Leg	Offset Type	Offsets: Horz Lateral Vert ft ft ft	Azimuth Adjustment	Placement	CAA Front	CAA Side	Weight	
				°	ft	ft ²	ft ²	lb	
(AT&T)			0.00 0.00 0.00		1/2" Ice 1" Ice No Ice	3.56 3.81 1.84	2.64 2.86 1.06	100.00 140.00 60.00	
Radio 4478 (AT&T)	C	From Face	4.00 0.00 0.00	0.0000	123.00	1/2" Ice 1" Ice No Ice	2.01 2.19 1.64	80.00 90.00 72.00	
RRU 8843 (AT&T)	C	From Face	4.00 0.00 0.00	0.0000	123.00	1/2" Ice 1" Ice No Ice	1.50 1.80 1.97	89.60 109.91 1.65	
*						1/2" Ice 1" Ice No Ice	25.04 29.39 34.02	1205.00 1475.00 1815.00	
RMQP-NP (12' Platform) (AT&T)	C	None		0.0000	123.00	1/2" Ice 1" Ice No Ice	25.04 29.39 25.04	1205.00 1475.00 1205.00	
***						1/2" Ice 1" Ice No Ice	34.02 34.02 29.39	1815.00	
FFVV-65B-R2 (DISH)	A	From Face	4.00 0.00 0.00	0.0000	111.00	No Ice 1/2" Ice 1" Ice	12.75 13.45 14.12	100.00 193.24 295.20	
TA08025-B604 (DISH)	A	From Face	4.00 0.00 0.00	0.0000	111.00	No Ice 1/2" Ice 1" Ice	0.98 2.14 2.32	60.00 80.00 100.00	
TA08025-B604 (DISH)	A	From Face	4.00 0.00 0.00	0.0000	111.00	No Ice 1/2" Ice 1" Ice	0.98 2.14 2.32	60.00 80.00 100.00	
RDIDC-9181-PF-48 (DISH)	A	From Face	4.00 0.00 0.00	0.0000	111.00	No Ice 1/2" Ice 1" Ice	2.01 2.19 2.38	20.00 40.00 60.00	
*						No Ice 1/2" Ice 1" Ice	12.75 13.45 14.12	100.00 193.24 295.20	
FFVV-65B-R2 (DISH)	B	From Face	4.00 0.00 0.00	0.0000	111.00	No Ice 1/2" Ice 1" Ice	7.65 8.94 10.07	100.00 193.24 295.20	
TA08025-B604 (DISH)	B	From Face	4.00 0.00 0.00	0.0000	111.00	No Ice 1/2" Ice 1" Ice	0.98 2.14 2.32	60.00 80.00 100.00	
TA08025-B604 (DISH)	B	From Face	4.00 0.00 0.00	0.0000	111.00	No Ice 1/2" Ice 1" Ice	0.98 2.14 2.32	60.00 80.00 100.00	
RDIDC-9181-PF-48 (DISH)	B	From Face	4.00 0.00 0.00	0.0000	111.00	No Ice 1/2" Ice 1" Ice	2.01 2.19 2.38	20.00 40.00 60.00	
*						No Ice 1/2" Ice 1" Ice	12.75 13.45 14.12	100.00 193.24 295.20	
FFVV-65B-R2 (DISH)	C	From Face	4.00 0.00 0.00	0.0000	111.00	No Ice 1/2" Ice 1" Ice	7.65 8.94 10.07	100.00 193.24 295.20	
TA08025-B604 (DISH)	C	From Face	4.00 0.00 0.00	0.0000	111.00	No Ice 1/2" Ice 1" Ice	0.98 2.14 2.32	60.00 80.00 100.00	
TA08025-B604 (DISH)	C	From Face	4.00 0.00 0.00	0.0000	111.00	No Ice 1/2" Ice 1" Ice	0.98 2.14 2.32	60.00 80.00 100.00	
RDIDC-9181-PF-48 (DISH)	C	From Face	4.00 0.00 0.00	0.0000	111.00	No Ice 1/2" Ice 1" Ice	2.01 2.19 2.38	20.00 40.00 60.00	
*						No Ice 1/2" Ice 1" Ice	12.75 13.45 14.12	100.00 193.24 295.20	
MC-PK8-DSH (DISH)	C	None		0.0000	111.00	No Ice 1/2" Ice 1" Ice	32.24 62.95 91.66	1750.00 2100.00 2450.00	
*						No Ice 1/2" Ice 1" Ice	32.24 62.95 91.66	1750.00 2100.00 2450.00	
RDIDC-9181-PF-48	A	From Face	4.00	0.0000	123.00	No Ice	2.01	1.17	20.00

tnxTower Magaram Engineering 13705 Stone Shadow Clifton VA Phone: 914-450-8416 FAX:	Job NJJER02052B							Page 8 of 21
	Project							Date 09:15:26 09/20/22
	Client Dish Wireless LLC							Designed by

Description	Face or Leg	Offset Type	Offsets: Horz Lateral Vert ft ft ft	Azimuth Adjustment	Placement	C _{AA} Front	C _{AA} Side	Weight
(AT&T)			0.00		1/2" Ice	2.19	1.31	40.00
			0.00		1" Ice	2.38	1.46	60.00
RDIDC-9181-PF-48 (AT&T)	B	From Face	4.00	0.0000	123.00	No Ice	2.01	1.17
			0.00		1/2" Ice	2.19	1.31	40.00
			0.00		1" Ice	2.38	1.46	60.00
RDIDC-9181-PF-48 (AT&T)	C	From Face	4.00	0.0000	123.00	No Ice	2.01	1.17
			0.00		1/2" Ice	2.19	1.31	40.00
			0.00		1" Ice	2.38	1.46	60.00

Dishes

Description	Face or Leg	Dish Type	Offset Type	Offsets: Horz Lateral Vert ft	Azimuth Adjustment	3 dB Beam Width	Elevation	Outside Diameter	Aperture Area	Weight
Andrew HP6		Paraboloid w/Shroud (HP)	None		0.0000		142.00	6.00	No Ice	28.27
									1/2" Ice	29.07
									1" Ice	29.87
										860.00

Tower Pressures - No Ice

$$G_H = 1.100$$

Section Elevation ft	z ft	K _Z	q _z psf	A _G ft ²	F a c e	A _F ft ²	A _R ft ²	A _{leg} ft ²	Leg %	C _{AA} In Face ft ²	C _{AA} Out Face ft ²
L1 150.00-97.25	121.92	1.32	58	115.350	A B C	0.000 0.000 0.000	115.350 115.350 115.350	115.350	100.00 100.00 100.00	0.000 0.000 5.934	0.000 0.000 0.000
L2 97.25-48.25	71.97	1.181	52	152.078	A B C	0.000 0.000 0.000	152.078 152.078 152.078	152.078	100.00 100.00 100.00	0.000 0.000 5.513	0.000 0.000 0.000
L3 48.25-1.00	24.82	0.944	41	187.019	A B C	0.000 0.000 0.000	187.019 187.019 187.019	187.019	100.00 100.00 100.00	0.000 0.000 5.316	0.000 0.000 0.000

Tower Pressure - With Ice

$$G_H = 1.100$$

tnxTower Magaram Engineering 13705 Stone Shadow Clifton VA Phone: 914-450-8416 FAX:	Job NJJER02052B											Page 9 of 21
	Project											Date 09:15:26 09/20/22
	Client Dish Wireless LLC											Designed by

Section Elevation	z	Kz	qz	tz	AG	Fa ce	A _F	A _R	A _{leg}	Leg %	C _{AA} In Face ft ²	C _{AA} Out Face ft ²
ft	ft		psf	in	ft ²		ft ²	ft ²	ft ²			
L1 150.00-97.25	121.92	1.32	8	1.4245	127.873	A	0.000	127.873	127.873	100.00	0.000	0.000
						B	0.000	127.873		100.00	0.000	0.000
						C	0.000	127.873		100.00	35.992	0.000
L2 97.25-48.25	71.97	1.181	7	1.3514	163.711	A	0.000	163.711	163.711	100.00	0.000	0.000
						B	0.000	163.711		100.00	0.000	0.000
						C	0.000	163.711		100.00	33.433	0.000
L3 48.25-1.00	24.82	0.944	6	1.2149	197.661	A	0.000	197.661	197.661	100.00	0.000	0.000
						B	0.000	197.661		100.00	0.000	0.000
						C	0.000	197.661		100.00	30.857	0.000

Tower Pressure - Service

$$G_H = 1.100$$

Section Elevation	z	Kz	qz	AG	Fa ce	A _F	A _R	A _{leg}	Leg %	C _{AA} In Face ft ²	C _{AA} Out Face ft ²
ft	ft		psf	ft ²		ft ²	ft ²	ft ²			
L1 150.00-97.25	121.92	1.32	10	115.350	A	0.000	115.350	115.350	100.00	0.000	0.000
					B	0.000	115.350		100.00	0.000	0.000
					C	0.000	115.350		100.00	5.934	0.000
L2 97.25-48.25	71.97	1.181	9	152.078	A	0.000	152.078	152.078	100.00	0.000	0.000
					B	0.000	152.078		100.00	0.000	0.000
					C	0.000	152.078		100.00	5.513	0.000
L3 48.25-1.00	24.82	0.944	7	187.019	A	0.000	187.019	187.019	100.00	0.000	0.000
					B	0.000	187.019		100.00	0.000	0.000
					C	0.000	187.019		100.00	5.316	0.000

Tower Forces - No Ice - Wind Normal To Face

Section Elevation	Add Weight	Self Weight	Fa ce	e	C _F	qz	D _F	D _R	A _E	F	w	Ctrl. Face
ft	lb	lb				psf			ft ²	lb	plf	
L1 150.00-97.25	757.10	3650.51	A	1	0.73	58	1	1	115.350	5409.46	102.55	C
			B	1	0.73		1	1	115.350			
			C	1	0.73		1	1	115.350			
L2 97.25-48.25	862.40	6484.44	A	1	0.73	52	1	1	152.078	6368.53	129.97	C
			B	1	0.73		1	1	152.078			
			C	1	0.73		1	1	152.078			
L3 48.25-1.00	787.60	9875.25	A	1	0.73	41	1	1	187.019	6197.72	131.17	C
			B	1	0.73		1	1	187.019			
			C	1	0.73		1	1	187.019			
Sum Weight:	2407.10	20010.20						OTM	1253728.6 0 lb-ft	17975.71		

Tower Forces - No Ice - Wind 60 To Face

tnxTower Magaram Engineering 13705 Stone Shadow Clifton VA Phone: 914-450-8416 FAX:	Job NJJER02052B										Page 10 of 21
	Project										Date 09:15:26 09/20/22
	Client Dish Wireless LLC										Designed by

Section Elevation ft	Add Weight lb	Self Weight lb	F a c e	e	C _F	q _z psf	D _F	D _R	A _E ft ²	F lb	w plf	Ctrl. Face
L1 150.00-97.25	757.10	3650.51	A B C	1 1 1	0.73 0.73 0.73	58	1	1	115.350	5409.46	102.55	C
L2 97.25-48.25	862.40	6484.44	A B C	1 1 1	0.73 0.73 0.73	52	1	1	152.078	6368.53	129.97	C
L3 48.25-1.00	787.60	9875.25	A B C	1 1 1	0.73 0.73 0.73	41	1	1	187.019	6197.72	131.17	C
Sum Weight:	2407.10	20010.20						OTM	1253728.6 0 lb-ft	17975.71		

Tower Forces - No Ice - Wind 90 To Face

Section Elevation ft	Add Weight lb	Self Weight lb	F a c e	e	C _F	q _z psf	D _F	D _R	A _E ft ²	F lb	w plf	Ctrl. Face
L1 150.00-97.25	757.10	3650.51	A B C	1 1 1	0.73 0.73 0.73	58	1	1	115.350	5409.46	102.55	C
L2 97.25-48.25	862.40	6484.44	A B C	1 1 1	0.73 0.73 0.73	52	1	1	152.078	6368.53	129.97	C
L3 48.25-1.00	787.60	9875.25	A B C	1 1 1	0.73 0.73 0.73	41	1	1	187.019	6197.72	131.17	C
Sum Weight:	2407.10	20010.20						OTM	1253728.6 0 lb-ft	17975.71		

Tower Forces - With Ice - Wind Normal To Face

Section Elevation ft	Add Weight lb	Self Weight lb	F a c e	e	C _F	q _z psf	D _F	D _R	A _E ft ²	F lb	w plf	Ctrl. Face
L1 150.00-97.25	1121.93	6183.04	A B C	1 1 1	1.2 1.2 1.2	8	1	1	127.873	1352.22	25.63	C
L2 97.25-48.25	1201.30	9596.59	A B C	1 1 1	1.2 1.2 1.2	7	1	1	127.873	1540.27	31.43	C
L3 48.25-1.00	1086.20	13279.71	A B C	1 1 1	1.2 1.2 1.2	6	1	1	163.114	1469.03	31.09	C
Sum Weight:	3409.43	29059.34						OTM	307818.68 lb-ft	4361.52		

<i>tnxTower</i> Magaram Engineering 13705 Stone Shadow Clifton VA Phone: 914-450-8416 FAX:	Job NJJER02052B										Page 11 of 21
	Project										Date 09:15:26 09/20/22
	Client Dish Wireless LLC										Designed by

Tower Forces - With Ice - Wind 60 To Face

Section Elevation ft	Add Weight lb	Self Weight lb	F a c e	e	C _F	q _z psf	D _F	D _R	A _E ft ²	F lb	w plf	Ctrl. Face
L1 150.00-97.25	1121.93	6183.04	A	1	1.2	8	1	1	127.873	1352.22	25.63	C
			B	1	1.2		1	1	127.873			
			C	1	1.2		1	1	127.873			
L2 97.25-48.25	1201.30	9596.59	A	1	1.2	7	1	1	163.114	1540.27	31.43	C
			B	1	1.2		1	1	163.114			
			C	1	1.2		1	1	163.114			
L3 48.25-1.00	1086.20	13279.71	A	1	1.2	6	1	1	196.586	1469.03	31.09	C
			B	1	1.2		1	1	196.586			
			C	1	1.2		1	1	196.586			
Sum Weight:	3409.43	29059.34					OTM		307818.68 lb-ft	4361.52		

Tower Forces - With Ice - Wind 90 To Face

Section Elevation ft	Add Weight lb	Self Weight lb	F a c e	e	C _F	q _z psf	D _F	D _R	A _E ft ²	F lb	w plf	Ctrl. Face
L1 150.00-97.25	1121.93	6183.04	A	1	1.2	8	1	1	127.873	1352.22	25.63	C
			B	1	1.2		1	1	127.873			
			C	1	1.2		1	1	127.873			
L2 97.25-48.25	1201.30	9596.59	A	1	1.2	7	1	1	163.114	1540.27	31.43	C
			B	1	1.2		1	1	163.114			
			C	1	1.2		1	1	163.114			
L3 48.25-1.00	1086.20	13279.71	A	1	1.2	6	1	1	196.586	1469.03	31.09	C
			B	1	1.2		1	1	196.586			
			C	1	1.2		1	1	196.586			
Sum Weight:	3409.43	29059.34					OTM		307818.68 lb-ft	4361.52		

Tower Forces - Service - Wind Normal To Face

Section Elevation ft	Add Weight lb	Self Weight lb	F a c e	e	C _F	q _z psf	D _F	D _R	A _E ft ²	F lb	w plf	Ctrl. Face
L1 150.00-97.25	757.10	3650.51	A	1	0.73	10	1	1	115.350	956.06	18.12	C
			B	1	0.73		1	1	115.350			
			C	1	0.73		1	1	115.350			
L2 97.25-48.25	862.40	6484.44	A	1	0.73	9	1	1	152.078	1125.56	22.97	C
			B	1	0.73		1	1	152.078			
			C	1	0.73		1	1	152.078			

tnxTower Magaram Engineering 13705 Stone Shadow Clifton VA Phone: 914-450-8416 FAX:	Job NJJER02052B										Page 12 of 21	
	Project										Date 09:15:26 09/20/22	
	Client Dish Wireless LLC										Designed by	

Section Elevation ft	Add Weight lb	Self Weight lb	F a c e	e	C _F	q _z psf	D _F	D _R	A _E	F	w	Ctrl. Face
L3 48.25-1.00	787.60	9875.25	A B C	1 1 1	0.73 0.73 0.73	7	1 1 1	1 1 1	187.019 187.019 187.019	1095.37	23.18	C
Sum Weight:	2407.10	20010.20						OTM	221581.66 lb-ft	3176.99		

Tower Forces - Service - Wind 60 To Face

Section Elevation ft	Add Weight lb	Self Weight lb	F a c e	e	C _F	q _z psf	D _F	D _R	A _E	F	w	Ctrl. Face
L1 150.00-97.25	757.10	3650.51	A B C	1 1 1	0.73 0.73 0.73	10	1 1 1	1 1 1	115.350 115.350 115.350	956.06	18.12	C
L2 97.25-48.25	862.40	6484.44	A B C	1 1 1	0.73 0.73 0.73	9	1 1 1	1 1 1	152.078 152.078 152.078	1125.56	22.97	C
L3 48.25-1.00	787.60	9875.25	A B C	1 1 1	0.73 0.73 0.73	7	1 1 1	1 1 1	187.019 187.019 187.019	1095.37	23.18	C
Sum Weight:	2407.10	20010.20						OTM	221581.66 lb-ft	3176.99		

Tower Forces - Service - Wind 90 To Face

Section Elevation ft	Add Weight lb	Self Weight lb	F a c e	e	C _F	q _z psf	D _F	D _R	A _E	F	w	Ctrl. Face
L1 150.00-97.25	757.10	3650.51	A B C	1 1 1	0.73 0.73 0.73	10	1 1 1	1 1 1	115.350 115.350 115.350	956.06	18.12	C
L2 97.25-48.25	862.40	6484.44	A B C	1 1 1	0.73 0.73 0.73	9	1 1 1	1 1 1	152.078 152.078 152.078	1125.56	22.97	C
L3 48.25-1.00	787.60	9875.25	A B C	1 1 1	0.73 0.73 0.73	7	1 1 1	1 1 1	187.019 187.019 187.019	1095.37	23.18	C
Sum Weight:	2407.10	20010.20						OTM	221581.66 lb-ft	3176.99		

Force Totals

tnxTower Magaram Engineering 13705 Stone Shadow Clifton VA Phone: 914-450-8416 FAX:	Job	NJJER02052B	Page
	Project		Date 09:15:26 09/20/22
	Client	Dish Wireless LLC	Designed by

Load Case	Vertical Forces lb	Sum of Forces X lb	Sum of Forces Z lb	Sum of Overturning Moments, M_x lb-ft	Sum of Overturning Moments, M_z lb-ft	Sum of Torques lb-ft
Leg Weight	20010.20					
Bracing Weight	0.00					
Total Member Self-Weight	20010.20			803.37	611.44	
Total Weight	29576.40			803.37	611.44	
Wind 0 deg - No Ice		0.00	-36560.91	-3593983.76	611.44	-1062.84
Wind 30 deg - No Ice		18280.46	-31662.68	-3112373.61	-1796782.12	-88.52
Wind 60 deg - No Ice		31662.68	-18280.46	-1796590.19	-3112565.54	909.52
Wind 90 deg - No Ice		36560.91	0.00	803.37	-3594175.69	1663.85
Wind 120 deg - No Ice		31662.68	18280.46	1798196.94	-3112565.54	1972.36
Wind 150 deg - No Ice		18280.46	31662.68	3113980.36	-1796782.12	1752.37
Wind 180 deg - No Ice		0.00	36560.91	3595590.51	611.44	1062.84
Wind 210 deg - No Ice		-18280.46	31662.68	3113980.36	1798005.01	88.52
Wind 240 deg - No Ice		-31662.68	18280.46	1798196.94	3113788.43	-909.52
Wind 270 deg - No Ice		-36560.91	0.00	803.37	3595398.58	-1663.85
Wind 300 deg - No Ice		-31662.68	-18280.46	-1796590.19	3113788.43	-1972.36
Wind 330 deg - No Ice		-18280.46	-31662.68	-3112373.61	1798005.01	-1752.37
Member Ice	9049.14					
Total Weight Ice	48445.11			3279.27	1132.97	
Wind 0 deg - Ice		0.00	-8543.83	-834238.79	1132.97	-118.47
Wind 30 deg - Ice		4271.91	-7399.17	-722032.65	-417626.07	171.37
Wind 60 deg - Ice		7399.17	-4271.91	-415479.76	-724178.95	415.29
Wind 90 deg - Ice		8543.83	0.00	3279.27	-836385.10	547.93
Wind 120 deg - Ice		7399.17	4271.91	422038.30	-724178.95	533.75
Wind 150 deg - Ice		4271.91	7399.17	728591.19	-417626.07	376.56
Wind 180 deg - Ice		0.00	8543.83	840797.34	1132.97	118.47
Wind 210 deg - Ice		-4271.91	7399.17	728591.19	419892.00	-171.37
Wind 240 deg - Ice		-7399.17	4271.91	422038.30	726444.88	-415.29
Wind 270 deg - Ice		-8543.83	0.00	3279.27	838651.03	-547.93
Wind 300 deg - Ice		-7399.17	-4271.91	-415479.76	726444.88	-533.75
Wind 330 deg - Ice		-4271.91	-7399.17	-722032.65	419892.00	-376.56
Total Weight	29576.40			803.37	611.44	
Wind 0 deg - Service		0.00	-6461.71	-634692.22	611.44	-187.84
Wind 30 deg - Service		3230.85	-5596.00	-549573.33	-317056.55	-15.64
Wind 60 deg - Service		5596.00	-3230.85	-317024.22	-549605.67	160.75
Wind 90 deg - Service		6461.71	0.00	643.78	-634724.55	294.07
Wind 120 deg - Service		5596.00	3230.85	318311.78	-549605.67	348.59
Wind 150 deg - Service		3230.85	5596.00	550860.90	-317056.55	309.71
Wind 180 deg - Service		0.00	6461.71	635979.78	611.44	187.84
Wind 210 deg - Service		-3230.85	5596.00	550860.90	318279.44	15.64
Wind 240 deg - Service		-5596.00	3230.85	318311.78	550828.56	-160.75
Wind 270 deg - Service		-6461.71	0.00	643.78	635947.44	-294.07
Wind 300 deg - Service		-5596.00	-3230.85	-317024.22	550828.56	-348.59
Wind 330 deg - Service		-3230.85	-5596.00	-549573.33	318279.44	-309.71

Load Combinations

Comb. No.	Description
1	Dead Only
2	1.2 Dead+1.0 Wind 0 deg - No Ice
3	0.9 Dead+1.0 Wind 0 deg - No Ice
4	1.2 Dead+1.0 Wind 30 deg - No Ice
5	0.9 Dead+1.0 Wind 30 deg - No Ice
6	1.2 Dead+1.0 Wind 60 deg - No Ice
7	0.9 Dead+1.0 Wind 60 deg - No Ice
8	1.2 Dead+1.0 Wind 90 deg - No Ice

tnxTower	Job NJJER02052B	Page 14 of 21
Magaram Engineering 13705 Stone Shadow Clifton VA Phone: 914-450-8416 FAX:	Project	Date 09:15:26 09/20/22
	Client Dish Wireless LLC	Designed by

<i>Comb. No.</i>	<i>Description</i>
9	0.9 Dead+1.0 Wind 90 deg - No Ice
10	1.2 Dead+1.0 Wind 120 deg - No Ice
11	0.9 Dead+1.0 Wind 120 deg - No Ice
12	1.2 Dead+1.0 Wind 150 deg - No Ice
13	0.9 Dead+1.0 Wind 150 deg - No Ice
14	1.2 Dead+1.0 Wind 180 deg - No Ice
15	0.9 Dead+1.0 Wind 180 deg - No Ice
16	1.2 Dead+1.0 Wind 210 deg - No Ice
17	0.9 Dead+1.0 Wind 210 deg - No Ice
18	1.2 Dead+1.0 Wind 240 deg - No Ice
19	0.9 Dead+1.0 Wind 240 deg - No Ice
20	1.2 Dead+1.0 Wind 270 deg - No Ice
21	0.9 Dead+1.0 Wind 270 deg - No Ice
22	1.2 Dead+1.0 Wind 300 deg - No Ice
23	0.9 Dead+1.0 Wind 300 deg - No Ice
24	1.2 Dead+1.0 Wind 330 deg - No Ice
25	0.9 Dead+1.0 Wind 330 deg - No Ice
26	1.2 Dead+1.0 Ice+1.0 Temp
27	1.2 Dead+1.0 Wind 0 deg+1.0 Ice+1.0 Temp
28	1.2 Dead+1.0 Wind 30 deg+1.0 Ice+1.0 Temp
29	1.2 Dead+1.0 Wind 60 deg+1.0 Ice+1.0 Temp
30	1.2 Dead+1.0 Wind 90 deg+1.0 Ice+1.0 Temp
31	1.2 Dead+1.0 Wind 120 deg+1.0 Ice+1.0 Temp
32	1.2 Dead+1.0 Wind 150 deg+1.0 Ice+1.0 Temp
33	1.2 Dead+1.0 Wind 180 deg+1.0 Ice+1.0 Temp
34	1.2 Dead+1.0 Wind 210 deg+1.0 Ice+1.0 Temp
35	1.2 Dead+1.0 Wind 240 deg+1.0 Ice+1.0 Temp
36	1.2 Dead+1.0 Wind 270 deg+1.0 Ice+1.0 Temp
37	1.2 Dead+1.0 Wind 300 deg+1.0 Ice+1.0 Temp
38	1.2 Dead+1.0 Wind 330 deg+1.0 Ice+1.0 Temp
39	Dead+Wind 0 deg - Service
40	Dead+Wind 30 deg - Service
41	Dead+Wind 60 deg - Service
42	Dead+Wind 90 deg - Service
43	Dead+Wind 120 deg - Service
44	Dead+Wind 150 deg - Service
45	Dead+Wind 180 deg - Service
46	Dead+Wind 210 deg - Service
47	Dead+Wind 240 deg - Service
48	Dead+Wind 270 deg - Service
49	Dead+Wind 300 deg - Service
50	Dead+Wind 330 deg - Service

Maximum Member Forces

<i>Section No.</i>	<i>Elevation ft</i>	<i>Component Type</i>	<i>Condition</i>	<i>Gov. Load Comb.</i>	<i>Axial</i>	<i>Major Axis Moment</i>	<i>Minor Axis Moment</i>
L1	150 - 97.25	Pole	Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-24817.86	1312.69	-2249.85
			Max. Mx	20	-10976.50	607198.30	-747.92
			Max. My	14	-10976.29	693.93	-607282.95
			Max. Vy	20	-24650.29	607198.30	-747.92
			Max. Vx	14	24650.38	693.93	-607282.95
			Max. Torque	10			-2030.66
L2	97.25 - 48.25	Pole	Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-36596.93	1338.68	-2865.92
			Max. Mx	20	-20089.90	1917564.41	-904.19
			Max. My	14	-20089.80	761.20	-1917713.2

tnxTower Magaram Engineering 13705 Stone Shadow Clifton VA Phone: 914-450-8416 FAX:	Job	NJJER02052B	Page
	Project		Date 09:15:26 09/20/22
	Client	Dish Wireless LLC	Designed by

Section No.	Elevation ft	Component Type	Condition	Gov. Load Comb.	Axial lb	Major Axis Moment lb-ft	Minor Axis Moment lb-ft
L3	48.25 - 1	Pole	Max. Vy	20	-30541.38	1917564.41	-904.19
			Max. Vx	14	30541.45	761.20	-1917713.2
			Max. Torque	10			9
			Max Tension	1	0.00	0.00	0.00
			Max. Compression	26	-55078.51	1310.00	-3550.17
			Max. Mx	20	-35450.89	3713477.78	-1006.76
			Max. My	14	-35450.89	773.34	-3713715.2
			Max. Vy	20	-36597.92	3713477.78	-1006.76
			Max. Vx	14	36597.92	773.34	-3713715.2
			Max. Torque	10			0
							-2012.51

Maximum Reactions

Location	Condition	Gov. Load Comb.	Vertical lb	Horizontal, X lb	Horizontal, Z lb
Pole	Max. Vert	26	55078.51	-0.50	0.98
	Max. H _x	21	26618.65	36559.29	-0.01
	Max. H _z	3	26618.65	0.00	36559.29
	Max. M _x	2	3711689.69	0.00	36558.53
	Max. M _z	8	3711927.13	-36558.53	-0.01
	Max. Torsion	22	2008.10	31662.59	18280.41
	Min. Vert	15	26618.65	0.00	-36559.29
	Min. H _x	9	26618.65	-36559.29	-0.01
	Min. H _z	15	26618.65	0.00	-36559.29
	Min. M _x	14	-3713715.20	0.00	-36558.53
	Min. M _z	20	-3713477.78	36558.53	-0.01
	Min. Torsion	10	-2008.23	-31662.59	-18280.41

Tower Mast Reaction Summary

Load Combination	Vertical	Shear _x	Shear _z	Overshielding Moment, M _x	Overshielding Moment, M _z	Torque
	lb	lb	lb	lb-ft	lb-ft	lb-ft
Dead Only	29576.40	0.04	-0.05	803.28	611.35	0.01
1.2 Dead+1.0 Wind 0 deg - No Ice	35491.51	-0.00	-36558.53	-3711689.69	772.99	-1102.77
0.9 Dead+1.0 Wind 0 deg - No Ice	26618.65	-0.00	-36559.29	-3679733.22	570.11	-1087.89
1.2 Dead+1.0 Wind 30 deg - No Ice	35491.67	18280.41	-31662.59	-3214529.13	-1855717.69	-113.83
0.9 Dead+1.0 Wind 30 deg - No Ice	26618.75	18280.43	-31662.62	-3186806.74	-1839763.10	-106.88
1.2 Dead+1.0 Wind 60 deg - No Ice	35491.67	31662.59	-18280.41	-1855485.58	-3214763.49	905.46
0.9 Dead+1.0 Wind 60 deg - No Ice	26618.75	31662.62	-18280.43	-1839590.81	-3186980.69	902.64
1.2 Dead+1.0 Wind 90 deg - No Ice	35491.51	36558.53	0.01	1006.22	-3711927.13	1682.32

tnxTower Magaram Engineering 13705 Stone Shadow Clifton VA Phone: 914-450-8416 FAX:	Job	NJJER02052B			Page
	Project				Date 09:15:26 09/20/22
	Client	Dish Wireless LLC			Designed by

Load Combination	Vertical	Shear _x	Shear _z	Overturning Moment, M _x	Overturning Moment, M _z	Torque
	lb	lb	lb	lb-ft	lb-ft	lb-ft
0.9 Dead+1.0 Wind 90 deg - No Ice	26618.65	36559.29	0.01	743.26	-3679909.45	1670.44
1.2 Dead+1.0 Wind 120 deg - No Ice	35491.67	31662.59	18280.41	1857500.18	-3214769.96	2008.23
0.9 Dead+1.0 Wind 120 deg - No Ice	26618.75	31662.62	18280.43	1841078.68	-3186985.47	1990.51
1.2 Dead+1.0 Wind 150 deg - No Ice	35491.67	18280.41	31662.59	3216551.17	-1855724.18	1796.02
0.9 Dead+1.0 Wind 150 deg - No Ice	26618.75	18280.43	31662.62	3188300.11	-1839767.88	1777.22
1.2 Dead+1.0 Wind 180 deg - No Ice	35491.51	-0.00	36558.53	3713715.20	772.97	1102.75
0.9 Dead+1.0 Wind 180 deg - No Ice	26618.65	-0.00	36559.29	3681229.23	570.10	1087.87
1.2 Dead+1.0 Wind 210 deg - No Ice	35491.67	-18280.41	31662.59	3216553.71	1857270.61	113.94
0.9 Dead+1.0 Wind 210 deg - No Ice	26618.75	-18280.43	31662.62	3188301.99	1840908.28	106.96
1.2 Dead+1.0 Wind 240 deg - No Ice	35491.67	-31662.59	18280.41	1857502.71	3216319.36	-905.46
0.9 Dead+1.0 Wind 240 deg - No Ice	26618.75	-31662.62	18280.43	1841080.55	3188128.05	-902.64
1.2 Dead+1.0 Wind 270 deg - No Ice	35491.51	-36558.53	0.01	1006.19	3713477.78	-1682.22
0.9 Dead+1.0 Wind 270 deg - No Ice	26618.65	-36559.29	0.01	743.25	3681053.01	-1670.38
1.2 Dead+1.0 Wind 300 deg - No Ice	35491.67	-31662.59	-18280.41	-1855488.16	3216312.90	-2008.10
0.9 Dead+1.0 Wind 300 deg - No Ice	26618.75	-31662.62	-18280.43	-1839592.71	3188123.28	-1990.43
1.2 Dead+1.0 Wind 330 deg - No Ice	35491.67	-18280.41	-31662.59	-3214531.69	1857264.17	-1796.11
0.9 Dead+1.0 Wind 330 deg - No Ice	26618.75	-18280.43	-31662.62	-3186808.63	1840903.51	-1777.30
1.2 Dead+1.0 Ice+1.0 Temp	55078.51	0.50	-0.98	3550.17	1310.00	0.13
1.2 Dead+1.0 Wind 0 deg+1.0 Ice+1.0 Temp	55078.49	0.00	-8542.62	-887641.51	1422.01	-145.71
1.2 Dead+1.0 Wind 30 deg+1.0 Ice+1.0 Temp	55078.50	4271.69	-7398.78	-768317.41	-444354.67	160.51
1.2 Dead+1.0 Wind 60 deg+1.0 Ice+1.0 Temp	55078.49	7398.13	-4271.32	-441926.28	-770581.21	423.77
1.2 Dead+1.0 Wind 90 deg+1.0 Ice+1.0 Temp	55078.49	8542.62	-0.01	3790.18	-890010.75	573.51
1.2 Dead+1.0 Wind 120 deg+1.0 Ice+1.0 Temp	55078.50	7398.78	4271.68	449568.68	-770687.10	569.64
1.2 Dead+1.0 Wind 150 deg+1.0 Ice+1.0 Temp	55078.50	4271.69	7398.77	775900.64	-444355.44	413.16
1.2 Dead+1.0 Wind 180 deg+1.0 Ice+1.0 Temp	55078.48	0.00	8542.60	895223.40	1421.99	146.01
1.2 Dead+1.0 Wind 210 deg+1.0 Ice+1.0 Temp	55078.50	-4271.68	7398.77	775900.41	447200.12	-160.19
1.2 Dead+1.0 Wind 240 deg+1.0 Ice+1.0 Temp	55078.50	-7398.77	4271.68	449568.44	773531.54	-423.45
1.2 Dead+1.0 Wind 270 deg+1.0 Ice+1.0 Temp	55078.49	-8542.61	-0.01	3790.15	892854.21	-573.20
1.2 Dead+1.0 Wind 300 deg+1.0 Ice+1.0 Temp	55078.49	-7398.12	-4271.32	-441926.09	773424.81	-569.31
1.2 Dead+1.0 Wind 330 deg+1.0 Ice+1.0 Temp	55078.50	-4271.68	-7398.78	-768317.22	447199.38	-412.86
Dead+Wind 0 deg - Service	29576.39	0.00	-6460.72	-652794.78	646.48	-196.50
Dead+Wind 30 deg - Service	29576.39	3230.36	-5595.15	-565223.73	-326173.59	-19.63

tnxTower Magaram Engineering 13705 Stone Shadow Clifton VA Phone: 914-450-8416 FAX:	Job	NJJER02052B	Page
	Project		Date 09:15:26 09/20/22
	Client	Dish Wireless LLC	Designed by

Load Combination	Vertical	Shear _x	Shear _z	Overswing Moment, M _x	Overswing Moment, M _z	Torque
	lb	lb	lb	lb-ft	lb-ft	lb-ft
Dead+Wind 60 deg - Service	29576.39	5595.15	-3230.36	-325975.01	-565422.36	162.49
Dead+Wind 90 deg - Service	29576.39	6460.72	-0.00	845.09	-652993.48	301.09
Dead+Wind 120 deg - Service	29576.39	5595.15	3230.36	327665.24	-565422.47	359.01
Dead+Wind 150 deg - Service	29576.39	3230.36	5595.15	566914.09	-326173.71	320.73
Dead+Wind 180 deg - Service	29576.39	0.00	6460.72	654485.20	646.48	196.52
Dead+Wind 210 deg - Service	29576.39	-3230.36	5595.15	566914.12	327466.68	19.66
Dead+Wind 240 deg - Service	29576.39	-5595.15	3230.36	327665.27	566715.48	-162.47
Dead+Wind 270 deg - Service	29576.39	-6460.72	-0.00	845.09	654286.51	-301.06
Dead+Wind 300 deg - Service	29576.39	-5595.15	-3230.36	-325975.04	566715.37	-358.98
Dead+Wind 330 deg - Service	29576.39	-3230.36	-5595.15	-565223.76	327466.58	-320.71

Solution Summary

Load Comb.	Sum of Applied Forces			Sum of Reactions			% Error
	PX lb	PY lb	PZ lb	PX lb	PY lb	PZ lb	
1	0.00	-29576.40	0.00	-0.04	29576.40	0.05	0.000%
2	0.00	-35491.68	-36560.91	0.00	35491.51	36558.53	0.005%
3	0.00	-26618.76	-36560.91	0.00	26618.65	36559.29	0.004%
4	18280.46	-35491.68	-31662.68	-18280.41	35491.67	31662.59	0.000%
5	18280.46	-26618.76	-31662.68	-18280.43	26618.75	31662.62	0.000%
6	31662.68	-35491.68	-18280.46	-31662.59	35491.67	18280.41	0.000%
7	31662.68	-26618.76	-18280.46	-31662.62	26618.75	18280.43	0.000%
8	36560.91	-35491.68	0.00	-36558.53	35491.51	-0.01	0.005%
9	36560.91	-26618.76	0.00	-36559.29	26618.65	-0.01	0.004%
10	31662.68	-35491.68	18280.46	-31662.59	35491.67	-18280.41	0.000%
11	31662.68	-26618.76	18280.46	-31662.62	26618.75	-18280.43	0.000%
12	18280.46	-35491.68	31662.68	-18280.41	35491.67	-31662.59	0.000%
13	18280.46	-26618.76	31662.68	-18280.43	26618.75	-31662.62	0.000%
14	0.00	-35491.68	36560.91	0.00	35491.51	-36558.53	0.005%
15	0.00	-26618.76	36560.91	0.00	26618.65	-36559.29	0.004%
16	-18280.46	-35491.68	31662.68	18280.41	35491.67	-31662.59	0.000%
17	-18280.46	-26618.76	31662.68	18280.43	26618.75	-31662.62	0.000%
18	-31662.68	-35491.68	18280.46	31662.59	35491.67	-18280.41	0.000%
19	-31662.68	-26618.76	18280.46	31662.62	26618.75	-18280.43	0.000%
20	-36560.91	-35491.68	0.00	36558.53	35491.51	-0.01	0.005%
21	-36560.91	-26618.76	0.00	36559.29	26618.65	-0.01	0.004%
22	-31662.68	-35491.68	-18280.46	31662.59	35491.67	18280.41	0.000%
23	-31662.68	-26618.76	-18280.46	31662.62	26618.75	18280.43	0.000%
24	-18280.46	-35491.68	-31662.68	18280.41	35491.67	31662.59	0.000%
25	-18280.46	-26618.76	-31662.68	18280.43	26618.75	31662.62	0.000%
26	0.00	-55078.51	0.00	-0.50	55078.51	0.98	0.002%
27	0.00	-55078.51	-8543.83	-0.00	55078.49	8542.62	0.002%
28	4271.91	-55078.51	-7399.17	-4271.69	55078.50	7398.78	0.001%
29	7399.17	-55078.51	-4271.91	-7398.13	55078.49	4271.32	0.002%
30	8543.83	-55078.51	0.00	-8542.62	55078.49	0.01	0.002%
31	7399.17	-55078.51	4271.91	-7398.78	55078.50	-4271.68	0.001%
32	4271.91	-55078.51	7399.17	-4271.69	55078.50	-7398.77	0.001%
33	0.00	-55078.51	8543.83	-0.00	55078.48	-8542.60	0.002%
34	-4271.91	-55078.51	7399.17	4271.68	55078.50	-7398.77	0.001%
35	-7399.17	-55078.51	4271.91	7398.77	55078.50	-4271.68	0.001%
36	-8543.83	-55078.51	0.00	8542.61	55078.49	0.01	0.002%
37	-7399.17	-55078.51	-4271.91	7398.12	55078.49	4271.32	0.002%
38	-4271.91	-55078.51	-7399.17	4271.68	55078.50	7398.78	0.001%
39	0.00	-29576.40	-6461.71	-0.00	29576.39	6460.72	0.003%
40	3230.85	-29576.40	-5596.00	-3230.36	29576.39	5595.15	0.003%
41	5596.00	-29576.40	-3230.85	-5595.15	29576.39	3230.36	0.003%
42	6461.71	-29576.40	0.00	-6460.72	29576.39	0.00	0.003%

<i>tnxTower</i> Magaram Engineering 13705 Stone Shadow Clifton VA Phone: 914-450-8416 FAX:	Job	NJJER02052B	Page
	Project		Date 09:15:26 09/20/22
	Client	Dish Wireless LLC	Designed by

Load Comb.	Sum of Applied Forces			Sum of Reactions			% Error
	PX lb	PY lb	PZ lb	PX lb	PY lb	PZ lb	
43	5596.00	-29576.40	3230.85	-5595.15	29576.39	-3230.36	0.003%
44	3230.85	-29576.40	5596.00	-3230.36	29576.39	-5595.15	0.003%
45	0.00	-29576.40	6461.71	-0.00	29576.39	-6460.72	0.003%
46	-3230.85	-29576.40	5596.00	3230.36	29576.39	-5595.15	0.003%
47	-5596.00	-29576.40	3230.85	5595.15	29576.39	-3230.36	0.003%
48	-6461.71	-29576.40	0.00	6460.72	29576.39	0.00	0.003%
49	-5596.00	-29576.40	-3230.85	5595.15	29576.39	3230.36	0.003%
50	-3230.85	-29576.40	-5596.00	3230.36	29576.39	5595.15	0.003%

Non-Linear Convergence Results

Load Combination	Converged?	Number of Cycles	Displacement Tolerance	Force Tolerance
1	Yes	6	0.00000001	0.00000001
2	Yes	13	0.00005403	0.00011183
3	Yes	13	0.00003643	0.00008605
4	Yes	16	0.00000001	0.00011505
5	Yes	16	0.00000001	0.00008073
6	Yes	16	0.00000001	0.00011392
7	Yes	16	0.00000001	0.00007991
8	Yes	13	0.00005403	0.00012782
9	Yes	13	0.00003643	0.00009811
10	Yes	16	0.00000001	0.00011858
11	Yes	16	0.00000001	0.00008323
12	Yes	16	0.00000001	0.00011295
13	Yes	16	0.00000001	0.00007916
14	Yes	13	0.00005402	0.00011193
15	Yes	13	0.00003642	0.00008611
16	Yes	16	0.00000001	0.00011592
17	Yes	16	0.00000001	0.00008124
18	Yes	16	0.00000001	0.00011710
19	Yes	16	0.00000001	0.00008211
20	Yes	13	0.00005402	0.00012792
21	Yes	13	0.00003642	0.00009817
22	Yes	16	0.00000001	0.00011263
23	Yes	16	0.00000001	0.00007893
24	Yes	16	0.00000001	0.00011821
25	Yes	16	0.00000001	0.00008297
26	Yes	7	0.00000001	0.00001658
27	Yes	13	0.00014620	0.00009728
28	Yes	14	0.00000001	0.00006748
29	Yes	13	0.00014594	0.00014731
30	Yes	13	0.00014621	0.00009876
31	Yes	14	0.00000001	0.00007000
32	Yes	14	0.00000001	0.00006745
33	Yes	13	0.00014626	0.00009869
34	Yes	14	0.00000001	0.00006864
35	Yes	14	0.00000001	0.00007017
36	Yes	13	0.00014625	0.00009947
37	Yes	13	0.00014597	0.00014806
38	Yes	14	0.00000001	0.00006885
39	Yes	12	0.00000001	0.00007103
40	Yes	12	0.00000001	0.00005633
41	Yes	12	0.00000001	0.00005496
42	Yes	12	0.00000001	0.00007142
43	Yes	12	0.00000001	0.00006149

tnxTower Magaram Engineering 13705 Stone Shadow Clifton VA Phone: 914-450-8416 FAX:	Job	NJJER02052B	Page
	Project		Date 09:15:26 09/20/22
	Client	Dish Wireless LLC	Designed by

44	Yes	12	0.00000001	0.00005407
45	Yes	12	0.00000001	0.00007141
46	Yes	12	0.00000001	0.00005720
47	Yes	12	0.00000001	0.00005896
48	Yes	12	0.00000001	0.00007173
49	Yes	12	0.00000001	0.00005382
50	Yes	12	0.00000001	0.00006087

Maximum Tower Deflections - Service Wind

Section No.	Elevation	Horz. Deflection	Gov. Load Comb.	Tilt	Twist
	ft	in		°	°
L1	150 - 97.25	21.857	46	1.2298	0.0053
L2	101.75 - 48.25	10.248	46	0.9840	0.0016
L3	54.25 - 1	2.777	46	0.4833	0.0005

Critical Deflections and Radius of Curvature - Service Wind

Elevation	Appurtenance	Gov. Load Comb.	Deflection	Tilt	Twist	Radius of Curvature
ft			in	°	°	ft
150.00	20' Omni	46	21.857	1.2298	0.0053	59530
142.00	Andrew HP6	46	19.810	1.2011	0.0046	37206
134.00	10' Omni	46	17.784	1.1703	0.0039	18603
123.00	TPA65R-BU6D	46	15.070	1.1210	0.0030	11023
111.00	FFVV-65B-R2	46	12.262	1.0520	0.0021	7631

Maximum Tower Deflections - Design Wind

Section No.	Elevation	Horz. Deflection	Gov. Load Comb.	Tilt	Twist
	ft	in		°	°
L1	150 - 97.25	123.573	14	6.9388	0.0299
L2	101.75 - 48.25	58.072	14	5.5766	0.0088
L3	54.25 - 1	15.749	14	2.7421	0.0026

Critical Deflections and Radius of Curvature - Design Wind

Elevation	Appurtenance	Gov. Load Comb.	Deflection	Tilt	Twist	Radius of Curvature
ft			in	°	°	ft
150.00	20' Omni	14	123.573	6.9388	0.0299	10899
142.00	Andrew HP6	14	112.033	6.7824	0.0258	6811
134.00	10' Omni	14	100.609	6.6143	0.0218	3403
123.00	TPA65R-BU6D	14	85.300	6.3422	0.0167	2014
111.00	FFVV-65B-R2	14	69.449	5.9585	0.0118	1391

tnxTower Magaram Engineering 13705 Stone Shadow Clifton VA Phone: 914-450-8416 FAX:	Job	NJJER02052B	Page
	Project		Date 09:15:26 09/20/22
	Client	Dish Wireless LLC	Designed by

Base Plate Design Data

Plate Thickness	Number of Anchor Bolts	Anchor Bolt Size	Actual Allowable Ratio	Actual Allowable Ratio	Actual Allowable Ratio	Actual Allowable Ratio	Controlling Condition	Ratio
			Bolt Tension lb	Bolt Compression lb	Plate Stress ksi	Stiffener Stress ksi		
2.5000	14	2.2500	209695.09	214759.53	37.620		Plate	0.84
			292291.37	485203.68	45.000			
			0.72	0.44	0.84			

Compression Checks

Pole Design Data

Section No.	Elevation ft	Size	L ft	L _u ft	Kl/r	A in ²	P _u lb	ϕP _n lb	Ratio P _u / ϕP _n
L1	150 - 97.25 (1)	TP31.76x20x0.25	52.75	149.00	165.1	24.2071	-10975.50	200631.00	0.055
L2	97.25 - 48.25 (2)	TP42.19x30.2568x0.3125	53.50	149.00	124.2	40.2098	-20089.50	588496.00	0.034
L3	48.25 - 1 (3)	TP52.1x40.2267x0.375	53.25	149.00	97.4	61.5657	-35451.00	1462480.00	0.024

Pole Bending Design Data

Section No.	Elevation ft	Size	M _{ux} lb-ft	ϕM _{nx} lb-ft	Ratio M _{ux} / ϕM _{nx}	M _{uy} lb-ft	ϕM _{ny} lb-ft	Ratio M _{uy} / ϕM _{ny}
L1	150 - 97.25 (1)	TP31.76x20x0.25	607568.33	1051575.00	0.578	0.00	1051575.00	0.000
L2	97.25 - 48.25 (2)	TP42.19x30.2568x0.3125	1918075.00	2274216.67	0.843	0.00	2274216.67	0.000
L3	48.25 - 1 (3)	TP52.1x40.2267x0.375	3714250.00	4344708.33	0.855	0.00	4344708.33	0.000

Pole Shear Design Data

Section No.	Elevation ft	Size	Actual V _u lb	ϕV _n lb	Ratio V _u / ϕV _n	Actual T _u lb-ft	ϕT _n lb-ft	Ratio T _u / ϕT _n
L1	150 - 97.25 (1)	TP31.76x20x0.25	24654.50	424835.00	0.058	913.51	1135000.00	0.001
L2	97.25 - 48.25 (2)	TP42.19x30.2568x0.3125	30544.50	705682.00	0.043	907.88	2505325.00	0.000
L3	48.25 - 1 (3)	TP52.1x40.2267x0.375	36600.20	1080480.00	0.034	113.94	4894366.67	0.000

tnxTower Magaram Engineering 13705 Stone Shadow Clifton VA Phone: 914-450-8416 FAX:	Job	NJJER02052B	Page
	Project		Date 09:15:26 09/20/22
	Client	Dish Wireless LLC	Designed by

Section No.	Elevation ft	Size	Actual V_u lb	ϕV_n lb	Ratio $\frac{V_u}{\phi V_n}$	Actual T_u lb-ft	ϕT_n lb-ft	Ratio $\frac{T_u}{\phi T_n}$

Pole Interaction Design Data

Section No.	Elevation ft	Ratio P_u ϕP_n	Ratio M_{ux} ϕM_{nx}	Ratio M_{uy} ϕM_{ny}	Ratio V_u ϕV_n	Ratio T_u ϕT_n	Comb. Stress Ratio	Allow. Stress Ratio	Criteria
L1	150 - 97.25 (1)	0.055	0.578	0.000	0.058	0.001	0.636	1.000	4.8.2 ✓
L2	97.25 - 48.25 (2)	0.034	0.843	0.000	0.043	0.000	0.879	1.000	4.8.2 ✓
L3	48.25 - 1 (3)	0.024	0.855	0.000	0.034	0.000	0.880	1.000	4.8.2 ✓

Section Capacity Table

Section No.	Elevation ft	Component Type	Size	Critical Element	P lb	ϕP_{allow} lb	% Capacity	Pass Fail
L1	150 - 97.25	Pole	TP31.76x20x0.25	1	-10975.50	200631.00	63.6	Pass
L2	97.25 - 48.25	Pole	TP42.19x30.2568x0.3125	2	-20089.50	588496.00	87.9	Pass
L3	48.25 - 1	Pole	TP52.1x40.2267x0.375	3	-35451.00	1462480.00	88.0	Pass
						Summary		
						Pole (L3)	88.0	Pass
						Base Plate	83.6	Pass
						RATING =	88.0	Pass



Amended EXHIBIT E

Mount Analysis



August 10, 2022

PASS

RE: Mount Analysis

Location: 200 Oronoque lane Stratford, CT 06614

Site ID: NJJER02052B

Dish Wireless LLC,

Per your request, we have performed a mount analysis of the proposed mount. This site consists of an existing monopole that has multiple carriers co-located on the tower. This review determines if the proposed mount can support the proposed loads.

1.0 Assumptions:

CATEGORY	DATA	CODE
Structure Type	Monopole	
Rad Center	110'-0"	
Structure Class	IV	ASCE 7-16
Exposure Class	C	ASCE 7-16
Kzt Factor	1.0	ASCE 7-16
Basic Wind Speed	135	2022 Connecticut SBC
Ice Thickness	1"	ASCE 7-16
Ice Windspeed	50 MPH	ASCE 7-16
Seismic Design Category	C	ASCE 7-16
S _{DS}	.218	ASCE 7-16

2.0 Existing Documents:

DOCUMENT	COMPANY	DATE
Proposed Drawings	M&K Development	12/16/2021
Site Visit Photos	M&K Development	8/2/2021



3.0 Proposed Equipment:

MANUFACTURER	EQUIPMENT	WEIGHTS
CommScope	(1) MC-PK8-DSH	1802 lbs
CommScope	(3) FFVV-65B-R2	70.54 lbs
Fujitsu	(3) TA08025-B604	63.9 lbs
Fujitsu	(3) TA08025-B605	74.9 lbs
RayCap	(1) OVP RDIDC-9181-PF-48	32 lbs
CommScope	(1) HYBRID CABLE	N.A.

Bold represents equipment to be added

We are installing (1) proposed MC-PK8-DSH mount on the existing monopole that will support all the proposed equipment. After performing an analysis on the mount in RISA-3D, it has been determined that the mount is **ADEQUATE** for the proposed loads.

This report does not address the structural stability of any other mounts, or portion of the structure, nor does it provide any warranty either express or implied, for any portion of the proposed mount or structure.

Please note that we have not had a professional engineer perform an independent visit to confirm existing structural conditions and the outcome of this analysis is based solely on the information provided in the previous structural analysis, photos and drawing details. If the existing conditions are modified, in disrepair or not properly represented, contact our office immediately for an amended report since this analysis may be inaccurate.

If you have any questions, feel free to contact us at any time.

Sincerely,

Magaram Engineering

Brett Magaram
Connecticut License # 33678
Brett@MagaramEngineering.com
Phone: 914-450-8416





ASCE 7 Hazards Report

Address:
200 Oronoque Ln
Stratford, Connecticut
06614

Standard: ASCE/SEI 7-16
Risk Category: IV
Soil Class: D - Default (see
Section 11.4.3)

Elevation: 256.3 ft (NAVD 88)
Latitude: 41.251254
Longitude: -73.11699







Seismic

Site Soil Class: D - Default (see Section 11.4.3)

Results:

S_s :	0.205	S_{D1} :	0.086
S_1 :	0.054	T_L :	6
F_a :	1.6	PGA :	0.115
F_v :	2.4	PGA_M :	0.181
S_{MS} :	0.327	F_{PGA} :	1.569
S_{M1} :	0.129	I_e :	1.5
S_{DS} :	0.218	C_v :	0.709

Seismic Design Category C



Data Accessed:

Tue Aug 09 2022

Date Source:

USGS Seismic Design Maps based on ASCE/SEI 7-16 and ASCE/SEI 7-16 Table 1.5-2. Additional data for site-specific ground motion procedures in accordance with ASCE/SEI 7-16 Ch. 21 are available from USGS.

Ice

Results:

Ice Thickness: 1.00 in.

Concurrent Temperature: 15 F

Gust Speed 50 mph

Data Source: Standard ASCE/SEI 7-16, Figs. 10-2 through 10-8

Date Accessed: Tue Aug 09 2022

Ice thicknesses on structures in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.



Values provided are equivalent radial ice thicknesses due to freezing rain with concurrent 3-second gust speeds, for a 500-year mean recurrence interval, and temperatures concurrent with ice thicknesses due to freezing rain. Thicknesses for ice accretions caused by other sources shall be obtained from local meteorological studies. Ice thicknesses in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.

The ASCE 7 Hazard Tool is provided for your convenience, for informational purposes only, and is provided "as is" and without warranties of any kind. The location data included herein has been obtained from information developed, produced, and maintained by third party providers; or has been extrapolated from maps incorporated in the ASCE 7 standard. While ASCE has made every effort to use data obtained from reliable sources or methodologies, ASCE does not make any representations or warranties as to the accuracy, completeness, reliability, currency, or quality of any data provided herein. Any third-party links provided by this Tool should not be construed as an endorsement, affiliation, relationship, or sponsorship of such third-party content by or from ASCE.

ASCE does not intend, nor should anyone interpret, the results provided by this Tool to replace the sound judgment of a competent professional, having knowledge and experience in the appropriate field(s) of practice, nor to substitute for the standard of care required of such professionals in interpreting and applying the contents of this Tool or the ASCE 7 standard.

In using this Tool, you expressly assume all risks associated with your use. Under no circumstances shall ASCE or its officers, directors, employees, members, affiliates, or agents be liable to you or any other person for any direct, indirect, special, incidental, or consequential damages arising from or related to your use of, or reliance on, the Tool or any information obtained therein. To the fullest extent permitted by law, you agree to release and hold harmless ASCE from any and all liability of any nature arising out of or resulting from any use of data provided by the ASCE 7 Hazard Tool.

Municipality	Basic Design Wind Speeds, V (mph)				Allowable Stress Design Wind Speeds, V_{asd} (mph)				Ground Snow Load p_g (psf)	MCE Ground Accelerations		Wind-Borne Debris Region ¹		Hurricane- Prone Region
	Risk Cat. I	Risk Cat. II	Risk Cat. III	Risk Cat. IV	Risk Cat. I	Risk Cat. II	Risk Cat. III	Risk Cat. IV		S_s (g)	S_I (g)	Risk Cat. III Occup. I-2	Risk Cat. IV	
Sherman	110	115	125	130	85	89	97	101	35	0.203	0.055			
Simsbury	110	120	125	130	85	93	97	101	35	0.177	0.054			Yes
Somers	110	120	130	135	85	93	101	105	35	0.174	0.055			Yes
South Windsor	110	120	130	135	85	93	101	105	30	0.183	0.055			Yes
Southbury	110	120	130	130	85	93	101	101	35	0.199	0.054			Yes
Southington	110	120	130	135	85	93	101	105	30	0.196	0.055			Yes
Sprague	115	125	135	140	89	97	105	108	30	0.191	0.054			Yes
Stafford	110	120	130	135	85	93	101	105	35	0.176	0.055			Yes
Stamford	110	120	130	135	85	93	101	105	30	0.261	0.058		Type B	Yes
Sterling	115	125	135	140	89	97	105	108	35	0.187	0.054			Yes
Stonington	120	130	140	145	93	101	108	112	30	0.182	0.051	Type B	Type A	Yes
Stratford	110	120	130	135	85	93	101	105	30	0.206	0.054		Type B	Yes
Suffield	110	120	125	130	85	93	97	101	35	0.170	0.054			Yes
Thomaston	110	120	125	130	85	93	97	101	35	0.184	0.054			Yes
Thompson	110	120	130	135	85	93	101	105	40	0.185	0.056			Yes
Tolland	110	120	130	135	85	93	101	105	35	0.182	0.055			Yes
Torrington	110	115	125	130	85	89	97	101	40	0.175	0.054			
Trumbull	110	120	130	135	85	93	101	105	30	0.210	0.054			Yes
Union	110	120	130	135	85	93	101	105	40	0.178	0.055			Yes
Vernon	110	120	130	135	85	93	101	105	30	0.186	0.055			Yes
Voluntown	120	130	135	140	93	101	105	108	30	0.188	0.053			Yes
Wallingford	110	120	130	135	85	93	101	105	30	0.205	0.055			Yes
Warren	110	115	125	130	85	89	97	101	40	0.179	0.054			
Washington	110	115	125	130	85	89	97	101	35	0.189	0.054			
Waterbury	110	120	130	135	85	93	101	105	35	0.193	0.054			Yes
Waterford	120	130	140	140	93	101	108	108	30	0.194	0.053	Type B	Type B	Yes
Watertown	110	120	130	130	85	93	101	101	35	0.189	0.054			Yes
West Hartford	110	120	130	135	85	93	101	105	30	0.187	0.055			Yes
West Haven	110	125	130	135	85	97	101	105	30	0.200	0.053	Type B	Type B	Yes
Westbrook	115	125	135	140	89	97	105	108	30	0.204	0.054	Type B	Type B	Yes
Weston	110	120	130	135	85	93	101	105	30	0.233	0.056			Yes
Westport	110	120	130	135	85	93	101	105	30	0.232	0.056		Type B	Yes



Envelope Only Solution

Magaram Engineering



BJM

NJJER02052B

SK-2



Aug 10, 2022

NJJER02052B - MA Model.r3d






Loads: BLC 3, Telco Wx
Envelope Only Solution

Magaram Engineering	NJJER02052B	SK-3
BJM		Aug 10, 2022
		NJJER02052B - MA Model.r3d



Loads: BLC 12, Mount Wx
Envelope Only Solution

Magaram Engineering	NJJER02052B	SK-4
BJM		Aug 10, 2022
		NJJER02052B - MA Model.r3d



Member Code Checks Displayed (Enveloped)
Envelope Only Solution

Magaram Engineering

BJM

NJJER02052B

SK-1

Aug 10, 2022

NJJER02052B - MA Model.r3d

Hot Rolled Steel Properties

Label	E [ksi]	G [ksi]	Nu	Therm. Coeff. [1e ⁵ °F ⁻¹]	Density [k/ft ³]	Yield [ksi]	Ry	Fu [ksi]	Rt
1 A992	29000	11154	0.3	0.65	0.49	50	1.1	65	1.1
2 A36 Gr.36	29000	11154	0.3	0.65	0.49	36	1.5	58	1.2
3 A572 Gr.50	29000	11154	0.3	0.65	0.49	50	1.1	65	1.1
4 A500 Gr.B RND	29000	11154	0.3	0.65	0.527	42	1.4	58	1.3
5 A500 Gr.B Rect	29000	11154	0.3	0.65	0.527	46	1.4	58	1.3
6 A53 Gr.B	29000	11154	0.3	0.65	0.49	35	1.6	60	1.2
7 A1085	29000	11154	0.3	0.65	0.49	50	1.4	65	1.3
8 A913 Gr.65	29000	11154	0.3	0.65	0.49	65	1.1	80	1.1
9 A500 GR.C	29000	11154	0.3	0.65	0.49	46	1.6	60	1.2
10 A529 Gr. 50	29000	11154	0.3	0.65	0.49	50	1.1	65	1.1
11 A1011-33Ksi	29000	11154	0.3	0.65	0.49	33	1.5	58	1.2
12 A1011 36 ksi	29000	11154	0.3	0.65	0.49	36	1.5	58	1.2
13 A1018 50 ksi	29000	11154	0.3	0.65	0.49	50	1.5	65	1.2

General Materials Properties

Label	E [ksi]	G [ksi]	Nu	Therm. Coeff. [1e ⁵ °F ⁻¹]	Density [k/ft ³]	Plate Methodology
1 gen_Conc3NW	3155	1372	0.15	0.6	0.145	Isotropic
2 gen_Conc4NW	3644	1584	0.15	0.6	0.145	Isotropic
3 gen_Conc3LW	2085	906	0.15	0.6	0.11	Isotropic
4 gen_Conc4LW	2408	1047	0.15	0.6	0.11	Isotropic
5 gen_Alum	10100	4077	0.3	1.29	0.173	Isotropic
6 gen_Steel	29000	11154	0.3	0.65	0.49	Isotropic
7 gen_Plywood	1800	38	0	0.3	0.035	Isotropic
8 RIGID	1e+6		0.3	0	0	Isotropic

Hot Rolled Steel Section Sets

Label	Shape	Type	Design List	Material	Design Rule	Area [in ²]	Iyy [in ⁴]	Izz [in ⁴]	J [in ⁴]
1 6.5"x0.37" Plate	PL6.5x0.375	Beam	None	A1011 36 ksi	Typical	2.438	0.029	8.582	0.11
2 6"x0.37" Plate	Plate 6x.37	Beam	None	A1011 36 ksi	Typical	2.22	0.025	6.66	0.097
3 L 2"x2"x1/4"	L2x2x4	Beam	None	A529 Gr. 50	Typical	0.944	0.346	0.346	0.021
4 Face Pipes(3.5x.16)	Pipe3.5x0.165	Beam	None	A500 GR.C	Typical	1.729	2.409	2.409	4.819
5 Antenna Pipes	PIPE_2.5	Beam	None	A500 GR.C	Typical	1.61	1.45	1.45	2.89
6 Channel(3.38x2.06)	C3.38x2.06x0.25	Beam	None	A1011 36 ksi	Typical	1.75	0.715	3.026	0.034
7 Square Tubing	HSS4X4X6	Beam	None	A500 GR.C	Typical	4.78	10.3	10.3	17.5
8 Handrail Connector	L6.6x4.46x0.25	Beam	None	A1011 36 ksi	Typical	2.703	4.759	12.473	0.055
9 Handrail	PIPE_2.5	Beam	None	A500 GR.C	Typical	1.61	1.45	1.45	2.89

General Section Sets

Label	Shape	Type	Material	Area [in ²]	Iyy [in ⁴]	Izz [in ⁴]	J [in ⁴]
1 GEN1	RE4X4	Beam	gen_Conc3NW	16	21.333	21.333	31.573
2 RIGID		None	RIGID	1e+06	1e+06	1e+06	1e+06

Member Primary Data

Label	I Node	J Node	Rotate(deg)	Section/Shape	Type	Design List	Material	Design Rule
1 M2	P3	P1		Square Tubing	Beam	None	A500 GR.C	Typical
2 M3	P9	P12	270	L 2"x2"x1/4"	Beam	None	A529 Gr. 50	Typical
3 M4	P10	P11		L 2"x2"x1/4"	Beam	None	A529 Gr. 50	Typical
4 M5	P7	P8		6.5"x0.37" Plate	Beam	None	A1011 36 ksi	Typical
5 M7	P14	P13		Square Tubing	Beam	None	A500 GR.C	Typical

Member Primary Data (Continued)

Label	I Node	J Node	Rotate(deg)	Section/Shape	Type	Design List	Material	Design Rule
6	M8	P20	P23	270	L 2"x2"x1/4"	Beam	None	A529 Gr. 50
7	M9	P21	P22		L 2"x2"x1/4"	Beam	None	A529 Gr. 50
8	M10	P18	P19		6.5"x0.37" Plate	Beam	None	A1011 36 ksi
9	M12	P25	P24		Square Tubing	Beam	None	A500 GR.C
10	M13	P31	P34	270	L 2"x2"x1/4"	Beam	None	A529 Gr. 50
11	M14	P32	P33		L 2"x2"x1/4"	Beam	None	A529 Gr. 50
12	M15	P29	P30		6.5"x0.37" Plate	Beam	None	A1011 36 ksi
13	M18	N43	N44		Face Pipes(3.5x.16)	Beam	None	A500 GR.C
14	MP9	N60	N66		Antenna Pipes	Beam	None	A500 GR.C
15	MP7	N57	N63		Antenna Pipes	Beam	None	A500 GR.C
16	M25	N67	N68		Handrail	Beam	None	A500 GR.C
17	M28	N114A	N113A	180	Handrail Connector	Beam	None	A1011 36 ksi
18	M29	N112A	N111A	180	Handrail Connector	Beam	None	A1011 36 ksi
19	M30	N116A	N115A	180	Handrail Connector	Beam	None	A1011 36 ksi
20	M32	N48A	N70A		RIGID	None	None	RIGID
21	M35	N45	N69A		RIGID	None	None	RIGID
22	M36	N51	N71A		RIGID	None	None	RIGID
23	M39A	N54	N72A		RIGID	None	None	RIGID
24	M61A	P4	N122A		Channel(3.38x2.06)	Beam	None	A1011 36 ksi
25	M63A	P4	N124B		Channel(3.38x2.06)	Beam	None	A1011 36 ksi
26	M60A	P15	N122B		Channel(3.38x2.06)	Beam	None	A1011 36 ksi
27	M61B	P15	N123A		Channel(3.38x2.06)	Beam	None	A1011 36 ksi
28	M62A	P26	N125		Channel(3.38x2.06)	Beam	None	A1011 36 ksi
29	M63B	P26	N126		Channel(3.38x2.06)	Beam	None	A1011 36 ksi
30	M64	N126A	N125A		RIGID	None	None	RIGID
31	M65	N126	N125A		RIGID	None	None	RIGID
32	M66	N129	N128		RIGID	None	None	RIGID
33	M67	N124B	N128		RIGID	None	None	RIGID
34	M68	N132	N131		RIGID	None	None	RIGID
35	M69	N123A	N131		RIGID	None	None	RIGID
36	M70	N133	N132A		RIGID	None	None	RIGID
37	M71	N122B	N132A		RIGID	None	None	RIGID
38	M72	N135	N134		RIGID	None	None	RIGID
39	M73	N125	N134		RIGID	None	None	RIGID
40	M74	N138	N137		RIGID	None	None	RIGID
41	M75	N122A	N137		PL 2.375X0.5	None	None	A36 Gr.36
42	MP8	N74	N75		Antenna Pipes	Beam	None	A500 GR.C
43	M43	N72B	N76		RIGID	None	None	RIGID
44	M44	N73	N77		RIGID	None	None	RIGID
45	M48	N81A	N82A		Face Pipes(3.5x.16)	Beam	None	A500 GR.C
46	MP3	N88	N90		Antenna Pipes	Beam	None	A500 GR.C
47	MP1	N87	N89		Antenna Pipes	Beam	None	A500 GR.C
48	M51	N91	N92		Handrail	Beam	None	A500 GR.C
49	M52	N84	N94		RIGID	None	None	RIGID
50	M53	N83A	N93		RIGID	None	None	RIGID
51	M54	N85	N95		RIGID	None	None	RIGID
52	M55	N86	N96		RIGID	None	None	RIGID
53	M62	N109	N110		Face Pipes(3.5x.16)	Beam	None	A500 GR.C
54	MP6	N116	N118		Antenna Pipes	Beam	None	A500 GR.C
55	MP4	N115	N117		Antenna Pipes	Beam	None	A500 GR.C
56	M65A	N119	N120		Handrail	Beam	None	A500 GR.C
57	M66A	N112	N122		RIGID	None	None	RIGID
58	M67A	N111	N121		RIGID	None	None	RIGID
59	M68A	N113	N123		RIGID	None	None	RIGID
60	M69A	N114	N124		RIGID	None	None	RIGID

Member Primary Data (Continued)

Label	I Node	J Node	Rotate(deg)	Section/Shape	Type	Design List	Material	Design Rule
61	MP2	N131A	N132B		Antenna Pipes	Beam	None	A500 GR.C
62	M68B	N129B	N133B		RIGID	None	None	RIGID
63	M69B	N130A	N134A		RIGID	None	None	RIGID
64	MP5	N137A	N138A		Antenna Pipes	Beam	None	A500 GR.C
65	M71B	N135A	N139		RIGID	None	None	RIGID
66	M72B	N136	N140		RIGID	None	None	RIGID

Member Advanced Data

Label	I Release	J Release	Physical	Deflection Ratio Options	Analysis Offset [in]	Seismic DR
1	M2		Yes	N/A		None
2	M3		Yes	N/A		None
3	M4		Yes	N/A		None
4	M5	BenPIN	BenPIN	Yes	Default	None
5	M7			Yes	N/A	None
6	M8			Yes	N/A	None
7	M9			Yes	N/A	None
8	M10	BenPIN	BenPIN	Yes	Default	None
9	M12			Yes	Default	None
10	M13			Yes	N/A	None
11	M14			Yes	N/A	None
12	M15	BenPIN	BenPIN	Yes	Default	None
13	M18			Yes	N/A	None
14	MP9			Yes	N/A	+y+3
15	MP7			Yes	N/A	+y+3
16	M25			Yes	N/A	None
17	M28	OOOOOX	OOOOOX	Yes	N/A	None
18	M29	OOOOOX	OOOOOX	Yes	N/A	None
19	M30	OOOOOX	OOOOOX	Yes	Default	None
20	M32			Yes	** NA **	None
21	M35			Yes	** NA **	None
22	M36			Yes	** NA **	None
23	M39A			Yes	** NA **	None
24	M61A			Yes	Default	None
25	M63A			Yes	Default	None
26	M60A			Yes	Default	None
27	M61B			Yes	Default	None
28	M62A			Yes	Default	None
29	M63B			Yes	Default	None
30	M64	BenPIN		Yes	** NA **	None
31	M65			Yes	** NA **	None
32	M66	BenPIN		Yes	** NA **	None
33	M67			Yes	** NA **	None
34	M68	BenPIN		Yes	** NA **	None
35	M69			Yes	** NA **	None
36	M70	BenPIN		Yes	** NA **	None
37	M71			Yes	** NA **	None
38	M72	BenPIN		Yes	** NA **	None
39	M73			Yes	** NA **	None
40	M74	BenPIN		Yes	** NA **	None
41	M75			Yes	** NA **	None
42	MP8			Yes	N/A	+y+3
43	M43			Yes	** NA **	None
44	M44			Yes	** NA **	None
45	M48			Yes	N/A	None
46	MP3			Yes	N/A	+y+3

Member Advanced Data (Continued)

Label	I Release	J Release	Physical	Deflection Ratio Options	Analysis Offset [in]	Seismic DR
47 MP1			Yes	N/A	+y+3	None
48 M51			Yes	N/A		None
49 M52			Yes	** NA **		None
50 M53			Yes	** NA **		None
51 M54			Yes	** NA **		None
52 M55			Yes	** NA **		None
53 M62			Yes	N/A		None
54 MP6			Yes	N/A	+y+3	None
55 MP4			Yes	N/A	+y+3	None
56 M65A			Yes	N/A		None
57 M66A			Yes	** NA **		None
58 M67A			Yes	** NA **		None
59 M68A			Yes	** NA **		None
60 M69A			Yes	** NA **		None
61 MP2			Yes	N/A	+y+3	None
62 M68B			Yes	** NA **		None
63 M69B			Yes	** NA **		None
64 MP5			Yes	N/A	+y+3	None
65 M71B			Yes	** NA **		None
66 M72B			Yes	** NA **		None

Hot Rolled Steel Design Parameters

Label	Shape	Length [in]	Lcomp top [in]	Function
1 M2	Square Tubing	40	Lbyy	Lateral
2 M3	L 2"x2"x1/4"	27.295	Lbyy	Lateral
3 M4	L 2"x2"x1/4"	27.295	Lbyy	Lateral
4 M5	6.5"x0.37" Plate	42	Lbyy	Lateral
5 M7	Square Tubing	40	Lbyy	Lateral
6 M8	L 2"x2"x1/4"	27.295	Lbyy	Lateral
7 M9	L 2"x2"x1/4"	27.295	Lbyy	Lateral
8 M10	6.5"x0.37" Plate	42	Lbyy	Lateral
9 M12	Square Tubing	40	Lbyy	Lateral
10 M13	L 2"x2"x1/4"	27.295	Lbyy	Lateral
11 M14	L 2"x2"x1/4"	27.295	Lbyy	Lateral
12 M15	6.5"x0.37" Plate	42	Lbyy	Lateral
13 M18	Face Pipes(3.5x.16)	96	Lbyy	Lateral
14 MP9	Antenna Pipes	96	Lbyy	Lateral
15 MP7	Antenna Pipes	96	Lbyy	Lateral
16 M25	Handrail	96	Lbyy	Lateral
17 M28	Handrail Connector	42	Lbyy	Lateral
18 M29	Handrail Connector	42	Lbyy	Lateral
19 M30	Handrail Connector	42	Lbyy	Lateral
20 M61A	Channel(3.38x2.06)	33	Lbyy	Lateral
21 M63A	Channel(3.38x2.06)	33	Lbyy	Lateral
22 M60A	Channel(3.38x2.06)	33	Lbyy	Lateral
23 M61B	Channel(3.38x2.06)	33	Lbyy	Lateral
24 M62A	Channel(3.38x2.06)	33	Lbyy	Lateral
25 M63B	Channel(3.38x2.06)	33	Lbyy	Lateral
26 M75	PL 2.375X0.5	1.5		Lateral
27 MP8	Antenna Pipes	96	Lbyy	Lateral
28 M48	Face Pipes(3.5x.16)	96	Lbyy	Lateral
29 MP3	Antenna Pipes	96	Lbyy	Lateral
30 MP1	Antenna Pipes	96	Lbyy	Lateral
31 M51	Handrail	96	Lbyy	Lateral
32 M62	Face Pipes(3.5x.16)	96	Lbyy	Lateral

Hot Rolled Steel Design Parameters (Continued)

Label	Shape	Length [in]	Lcomp top [in]	Function
33 MP6	Antenna Pipes	96	Lbby	Lateral
34 MP4	Antenna Pipes	96	Lbby	Lateral
35 M65A	Handrail	96	Lbby	Lateral
36 MP2	Antenna Pipes	96	Lbby	Lateral
37 MP5	Antenna Pipes	96	Lbby	Lateral

Member RISAConnection Properties

Label	Shape	Start Conn	End Conn	Start Release	End Release
1 M2	HSS4X4X6	None	None	Fixed	Fixed
2 M3	L2x2x4	None	None	Fixed	Fixed
3 M4	L2x2x4	None	None	Fixed	Fixed
4 M5	PL6.5x0.375	None	None	Pinned	Pinned
5 M7	HSS4X4X6	None	None	Fixed	Fixed
6 M8	L2x2x4	None	None	Fixed	Fixed
7 M9	L2x2x4	None	None	Fixed	Fixed
8 M10	PL6.5x0.375	None	None	Pinned	Pinned
9 M12	HSS4X4X6	None	None	Fixed	Fixed
10 M13	L2x2x4	None	None	Fixed	Fixed
11 M14	L2x2x4	None	None	Fixed	Fixed
12 M15	PL6.5x0.375	None	None	Pinned	Pinned
13 M18	Pipe3.5x0.165	None	None	Fixed	Fixed
14 MP9	PIPE 2.5	None	None	Fixed	Fixed
15 MP7	PIPE 2.5	None	None	Fixed	Fixed
16 M25	PIPE 2.5	None	None	Fixed	Fixed
17 M28	L6.6x4.46x0.25	None	None	Fixed	Fixed
18 M29	L6.6x4.46x0.25	None	None	Fixed	Fixed
19 M30	L6.6x4.46x0.25	None	None	Fixed	Fixed
20 M61A	C3.38x2.06x0.25	None	None	Fixed	Fixed
21 M63A	C3.38x2.06x0.25	None	None	Fixed	Fixed
22 M60A	C3.38x2.06x0.25	None	None	Fixed	Fixed
23 M61B	C3.38x2.06x0.25	None	None	Fixed	Fixed
24 M62A	C3.38x2.06x0.25	None	None	Fixed	Fixed
25 M63B	C3.38x2.06x0.25	None	None	Fixed	Fixed
26 M75	PL 2.375X0.5	None	None	Fixed	Fixed
27 MP8	PIPE 2.5	None	None	Fixed	Fixed
28 M48	Pipe3.5x0.165	None	None	Fixed	Fixed
29 MP3	PIPE 2.5	None	None	Fixed	Fixed
30 MP1	PIPE 2.5	None	None	Fixed	Fixed
31 M51	PIPE 2.5	None	None	Fixed	Fixed
32 M62	Pipe3.5x0.165	None	None	Fixed	Fixed
33 MP6	PIPE 2.5	None	None	Fixed	Fixed
34 MP4	PIPE 2.5	None	None	Fixed	Fixed
35 M65A	PIPE 2.5	None	None	Fixed	Fixed
36 MP2	PIPE 2.5	None	None	Fixed	Fixed
37 MP5	PIPE 2.5	None	None	Fixed	Fixed

Design Size and Code Check Parameters

Label	Max Axial/Bending Chk	Max Shear Chk
1 Typical	1	1

Concrete Rebar Parameters

Label Optimize Rebar ?Min Flex Bar Max Flex Bar Shear Bar Legs per Stirrup Top (Column) Cover [in] Bottom Cover [in] Side Cover [in] Top/Bottom Bars Add'l Side Bars Shear Bar Spacing [in]												
1	Typical	Optimize	#6	#10	#4	2	1.5	1.5	1.5	2	1	12

Deflection Design

Label	LC	Ratio	LC	Ratio	LC	Ratio
1	Typical	None	N/A	None	N/A	None

Wall Panel U.C. Parameters

Label	Max Bending Chk	Max Shear Chk
1	1	1

Frame / HR Column Seismic Design Rule

Label	Frame Ductility	Overstrength Reqd
1 OCBF	Minimal	Yes
2 SCBF	High	Yes
3 OMF	Minimal	Yes
4 IMF	Moderate	Yes
5 SMF-RBS	High	Yes
6 SMF-Kaiser	High	Yes

HR Beam Seismic Design Rule

Label	Connection	Overstrength Reqd	Z Factor	Hinge Location [in]
1 OCBF	Other/None			
2 SCBF	Other/None	Yes		
3 OMF	BUEEP			12
4 IMF	BFP			12
5 SMF-RBS	RBS		0.685	14.625
6 SMF-Kaiser	KBB-B			12

HR Brace Seismic Design Rule

Label	Overstrength Reqd	KL/r
1 OCBF		
2 SCBF		Yes
3 OMF		
4 IMF		
5 SMF-RBS		
6 SMF-Kaiser		

Connection Design Rules

Label	Conn Type	Type	Beam Conn	Col/Girder Conn	Eccentricity
1 Col/Bm Single Angle Shear	Shear	Column/Beam Clip Single Angle Shear	Bolted	Bolted	1.5
2 Col/Bm Double Angle Shear	Shear	Column/Beam Clip Double Angle Shear	Bolted	Bolted	0
3 Col/Bm Two Side Clip Angle Shear	Shear	Column/Beam Clip Double Angle (Both Side) Shear	Bolted	Bolted	N/A
4 Col/Bm End Plate Shear	Shear	Column/Beam End-Plate Shear	N/A	Bolted	N/A
5 Col/Bm Shear Tab Shear	Shear	Column/Beam Shear Tab Shear	Bolted	N/A	0
6 Girder/Bm Single Angle Shear	Shear	Girder/Beam Clip Single Angle Shear	Bolted	Bolted	N/A
7 Girder/Bm Double Angle Shear	Shear	Girder/Beam Clip Double Angle Shear	Bolted	Bolted	N/A

Connection Design Rules (Continued)

Label	Conn Type	Type	Beam Conn	Col/Girder Conn	Eccentricity
8 Grd/Bm Two Side Clip Angle Shear	Shear	Girder/Beam Clip Double Angle (Both Side) Shear	Bolted	Bolted	N/A
9 Girder/Bm End Plate Shear	Shear	Girder/Beam End-Plate Shear	N/A	Bolted	N/A
10 Girder/Bm Shear Tab Shear	Shear	Girder/Beam Shear Tab Shear	Bolted	N/A	N/A
11 Beam Shear Splice	Shear	Beam Shear Tab Splice	Bolted	N/A	N/A
12 Column Shear Splice	Shear	Column Shear Tab Splice	N/A	Bolted	N/A
13 Col/Bm Ext. End Plate Moment	Moment	Column/Beam Extended End-Plate Moment	N/A	N/A	N/A
14 Col/Bm PartExt. End Plate Moment	Moment	Column/Beam Partially Extended End-Plate Moment (Tension side)	N/A	N/A	N/A
15 Col/Bm Flush End Plate Moment	Moment	Column/Beam Flush End-Plate Moment	N/A	N/A	N/A
16 Col/Bm Flange Plate Moment	Moment	Column/Beam Flange Plate Moment	Bolted	N/A	N/A
17 Col/Bm Direct Weld Moment	Moment	Column/Beam Direct Weld Moment	Bolted	N/A	N/A
18 Col/Bm Seismic Moment	Moment	Column/Beam Seismic Moment	N/A	N/A	N/A
19 Beam Moment Plate Splice	Moment	Beam Moment Plate Splice	Bolted	N/A	N/A
20 Column Moment Plate Splice	Moment	Column Moment Plate Splice	N/A	N/A	N/A
21 Beam Direct Weld Moment Splice	Moment	Beam Direct Weld Splice	Bolted	N/A	N/A
22 Col Direct Weld Moment Splice	Moment	Column Direct Weld Splice	N/A	Bolted	N/A
23 Bm Ext. End Plate Moment Splice	Moment	Beam Extended End Plate Splice	Bolted	N/A	N/A
24 Col Ext. End Plate Moment Splice	Moment	Column Extended End Plate Splice	N/A	Bolted	N/A
25 Diagonal Vertical Brace	Brace	Diagonal Vertical Brace	N/A	N/A	N/A
26 Chevron Vertical Brace	Brace	Chevron Vertical Brace	N/A	N/A	N/A
27 Seismic Diagonal Brace	Brace	Diagonal Brace Seismic	N/A	N/A	N/A
28 Seismic Chevron Brace	Brace	Chevron Brace Seismic	N/A	N/A	N/A
29 Knee Brace	Brace	Knee Brace	N/A	N/A	N/A
30 Single Column Base Plate	Baseplate	Single Column Baseplate	N/A	N/A	N/A
31 Base Plate with Vertical Brace	Baseplate	Brace to Column Base Plate	N/A	N/A	N/A
32 HSS Truss Connection	Truss	HSS T-Connection	N/A	N/A	N/A

Node Loads and Enforced Displacements (BLC 1 : Telco DL)

Node Label	L, D, M	Direction	Magnitude [(lb, k-ft), (in, rad), (lb*s^2/in, lb*s^2*in)]
1 N127	L	Y	-35.25
2 N130	L	Y	-35.25
3 N143	L	Y	-35.25
4 N144	L	Y	-35.25
5 N147	L	Y	-35.25
6 N149	L	Y	-35.25
7 N142	L	Y	-76
8 N146	L	Y	-76
9 N151	L	Y	-76
10 N141	L	Y	-63.9
11 N145	L	Y	-63.9
12 N150	L	Y	-63.9
13 N130B	L	Y	-21.8
14 N131B	L	Y	-21.8
15 N132C	L	Y	-21.8

Node Loads and Enforced Displacements (BLC 2 : Telco DLi)

Node Label	L, D, M	Direction	Magnitude [(lb, k-ft), (in, rad), (lb*s^2/in, lb*s^2*in)]
1 N127	L	Y	-106.35
2 N130	L	Y	-106.35
3 N143	L	Y	-106.35
4 N144	L	Y	-106.35
5 N147	L	Y	-106.35
6 N149	L	Y	-106.35
7 N142	L	Y	-38.2

Node Loads and Enforced Displacements (BLC 2 : Telco DLi) (Continued)

	Node Label	L, D, M	Direction	Magnitude [(lb, k-ft), (in, rad), (lb*s^2/in, lb*s^2*in)]
8	N146	L	Y	-38.2
9	N151	L	Y	-38.2
10	N141	L	Y	-37
11	N145	L	Y	-37
12	N150	L	Y	-37
13	N130B	L	Y	-44.7
14	N131B	L	Y	-44.7
15	N132C	L	Y	-44.7

Node Loads and Enforced Displacements (BLC 3 : Telco Wx)

	Node Label	L, D, M	Direction	Magnitude [(lb, k-ft), (in, rad), (lb*s^2/in, lb*s^2*in)]
1	N127	L	X	319.7
2	N130	L	X	319.7
3	N143	L	X	319.7
4	N144	L	X	319.7
5	N147	L	X	319.7
6	N149	L	X	319.7
7	N142	L	X	100.4
8	N146	L	X	100.4
9	N151	L	X	100.4
10	N141	L	X	100.4
11	N145	L	X	100.4
12	N150	L	X	100.4
13	N130B	L	X	117.2
14	N131B	L	X	117.2
15	N132C	L	X	117.2

Node Loads and Enforced Displacements (BLC 4 : Telco Wz)

	Node Label	L, D, M	Direction	Magnitude [(lb, k-ft), (in, rad), (lb*s^2/in, lb*s^2*in)]
1	N127	L	Z	319.7
2	N130	L	Z	319.7
3	N143	L	Z	319.7
4	N144	L	Z	319.7
5	N147	L	Z	319.7
6	N149	L	Z	319.7
7	N142	L	Z	100.4
8	N146	L	Z	100.4
9	N151	L	Z	100.4
10	N141	L	Z	100.4
11	N145	L	Z	100.4
12	N150	L	Z	100.4
13	N130B	L	Z	117.2
14	N131B	L	Z	117.2
15	N132C	L	Z	117.2

Node Loads and Enforced Displacements (BLC 5 : Telco Wxi)

	Node Label	L, D, M	Direction	Magnitude [(lb, k-ft), (in, rad), (lb*s^2/in, lb*s^2*in)]
1	N127	L	X	26.85
2	N130	L	X	26.85
3	N143	L	X	26.85
4	N144	L	X	26.85
5	N147	L	X	26.85

Node Loads and Enforced Displacements (BLC 5 : Telco Wxi) (Continued)

	Node Label	L, D, M	Direction	Magnitude [(lb, k-ft), (in, rad), (lb*s^2/in, lb*s^2*in)]
6	N149	L	X	26.85
7	N142	L	X	8.7
8	N146	L	X	8.7
9	N151	L	X	8.7
10	N141	L	X	8.7
11	N145	L	X	8.7
12	N150	L	X	8.7
13	N130B	L	X	10.2
14	N131B	L	X	10.2
15	N132C	L	X	10.2

Node Loads and Enforced Displacements (BLC 6 : Telco Wzi)

	Node Label	L, D, M	Direction	Magnitude [(lb, k-ft), (in, rad), (lb*s^2/in, lb*s^2*in)]
1	N127	L	Z	26.85
2	N130	L	Z	26.85
3	N143	L	Z	26.85
4	N144	L	Z	26.85
5	N147	L	Z	26.85
6	N149	L	Z	26.85
7	N142	L	Z	8.7
8	N146	L	Z	8.7
9	N151	L	Z	8.7
10	N141	L	Z	8.7
11	N145	L	Z	8.7
12	N150	L	Z	8.7
13	N130B	L	Z	10.2
14	N131B	L	Z	10.2
15	N132C	L	Z	10.2

Node Loads and Enforced Displacements (BLC 7 : Telco Wxm)

	Node Label	L, D, M	Direction	Magnitude [(lb, k-ft), (in, rad), (lb*s^2/in, lb*s^2*in)]
1	N127	L	X	15.8
2	N130	L	X	15.8
3	N143	L	X	15.8
4	N144	L	X	15.8
5	N147	L	X	15.8
6	N149	L	X	15.8
7	N142	L	X	5
8	N146	L	X	5
9	N151	L	X	5
10	N141	L	X	5
11	N145	L	X	5
12	N150	L	X	5
13	N130B	L	X	5.8
14	N131B	L	X	5.8
15	N132C	L	X	5.8

Node Loads and Enforced Displacements (BLC 8 : Telco Wzm)

	Node Label	L, D, M	Direction	Magnitude [(lb, k-ft), (in, rad), (lb*s^2/in, lb*s^2*in)]
1	N127	L	Z	15.8
2	N130	L	Z	15.8
3	N143	L	Z	15.8

Node Loads and Enforced Displacements (BLC 8 : Telco Wzm) (Continued)

	Node Label	L, D, M	Direction	Magnitude [(lb, k-ft), (in, rad), (lb*s^2/in, lb*s^2*in)]
4	N144	L	Z	15.8
5	N147	L	Z	15.8
6	N149	L	Z	15.8
7	N142	L	Z	5
8	N146	L	Z	5
9	N151	L	Z	5
10	N141	L	Z	5
11	N145	L	Z	5
12	N150	L	Z	5
13	N130B	L	Z	5.8
14	N131B	L	Z	5.8
15	N132C	L	Z	5.8

Node Loads and Enforced Displacements (BLC 19 : Lm)

	Node Label	L, D, M	Direction	Magnitude [(lb, k-ft), (in, rad), (lb*s^2/in, lb*s^2*in)]
1	N132B	L	Y	-500
2	N138A	L	Y	-500
3	N75	L	Y	-500

Node Loads and Enforced Displacements (BLC 20 : Lv)

	Node Label	L, D, M	Direction	Magnitude [(lb, k-ft), (in, rad), (lb*s^2/in, lb*s^2*in)]
1	N82A	L	Y	-250
2	N92	L	Y	-250
3	N120	L	Y	-250
4	N110	L	Y	-250
5	N68	L	Y	-250
6	N44	L	Y	-250

Member Point Loads

No Data to Print...

Basic Load Cases

	BLC Description	Category	Y Gravity	Nodal	Distributed	Area(Member)
1	Telco DL	DL		15		
2	Telco DLi	OL1		15		
3	Telco Wx	WLX		15		
4	Telco Wz	WLZ		15		
5	Telco Wxi	WLXP1		15		
6	Telco Wzi	WLZP1		15		
7	Telco Wxm	WLXP2		15		
8	Telco Wzm	WLZP2		15		
9	-	None				
10	Mount DL	DL	-1.1			3
11	Mount DLi	OL1			36	3
12	Mount Wx	WLX			36	
13	Mount Wz	WLZ			36	
14	Mount Wxi	WLXP1			36	
15	Mount Wzi	WLZP1			36	
16	Mount Wxm	WLXP2			36	
17	Mount Wzm	WLZP2			36	
18	-	None				

Basic Load Cases (Continued)

	BLC Description	Category	Y Gravity	Nodal	Distributed	Area(Member)
19	Lm	None		3		
20	Lv	None		6		
21	BLC 10 Transient Area Loads	None			9	
22	BLC 11 Transient Area Loads	None			9	

Load Combinations

	Description	Solve P-Delta	BLC	Factor	BLC	Factor	BLC	Factor	BLC	Factor
1	1.4D	Yes	Y	DL	1.4					
2	Wind LCs (Case 1)									
3	1.2D + 1.0W (0)	Yes	Y	DL	1.2		WLX	1	WLZ	
4	1.2D + 1.0W (30)	Yes	Y	DL	1.2		WLX	0.866	WLZ	0.5
5	1.2D + 1.0W (45)	Yes	Y	DL	1.2		WLX	0.707	WLZ	0.707
6	1.2D + 1.0W (60)	Yes	Y	DL	1.2		WLX	0.5	WLZ	0.866
7	1.2D + 1.0W (90)	Yes	Y	DL	1.2		WLX		WLZ	1
8	1.2D + 1.0W (120)	Yes	Y	DL	1.2		WLX	-0.5	WLZ	0.866
9	1.2D + 1.0W (135)	Yes	Y	DL	1.2		WLX	-0.707	WLZ	0.707
10	1.2D + 1.0W (150)	Yes	Y	DL	1.2		WLX	-0.866	WLZ	0.5
11	1.2D + 1.0W (180)	Yes	Y	DL	1.2		WLX	-1	WLZ	
12	1.2D + 1.0W (210)	Yes	Y	DL	1.2		WLX	-0.866	WLZ	-0.5
13	1.2D + 1.0W (225)	Yes	Y	DL	1.2		WLX	-0.707	WLZ	-0.707
14	1.2D + 1.0W (240)	Yes	Y	DL	1.2		WLX	-0.5	WLZ	-0.866
15	1.2D + 1.0W (270)	Yes	Y	DL	1.2		WLX		WLZ	-1
16	1.2D + 1.0W (300)	Yes	Y	DL	1.2		WLX	0.5	WLZ	-0.866
17	1.2D + 1.0W (315)	Yes	Y	DL	1.2		WLX	0.707	WLZ	-0.707
18	1.2D + 1.0W (330)	Yes	Y	DL	1.2		WLX	0.866	WLZ	-0.5
19	Uplift LCs (Case 2)									
20	1.2D + 1.0W (0)	Yes	Y	DL	0.9		WLX	1	WLZ	
21	1.2D + 1.0W (30)	Yes	Y	DL	0.9		WLX	0.866	WLZ	0.5
22	1.2D + 1.0W (45)	Yes	Y	DL	0.9		WLX	0.707	WLZ	0.707
23	1.2D + 1.0W (60)	Yes	Y	DL	0.9		WLX	0.5	WLZ	0.866
24	1.2D + 1.0W (90)	Yes	Y	DL	0.9		WLX		WLZ	1
25	1.2D + 1.0W (120)	Yes	Y	DL	0.9		WLX	-0.5	WLZ	0.866
26	1.2D + 1.0W (135)	Yes	Y	DL	0.9		WLX	-0.707	WLZ	0.707
27	1.2D + 1.0W (150)	Yes	Y	DL	0.9		WLX	-0.866	WLZ	0.5
28	1.2D + 1.0W (180)	Yes	Y	DL	0.9		WLX	-1	WLZ	
29	1.2D + 1.0W (210)	Yes	Y	DL	0.9		WLX	-0.866	WLZ	-0.5
30	1.2D + 1.0W (225)	Yes	Y	DL	0.9		WLX	-0.707	WLZ	-0.707
31	1.2D + 1.0W (240)	Yes	Y	DL	0.9		WLX	-0.5	WLZ	-0.866
32	1.2D + 1.0W (270)	Yes	Y	DL	0.9		WLX		WLZ	-1
33	1.2D + 1.0W (300)	Yes	Y	DL	0.9		WLX	0.5	WLZ	-0.866
34	1.2D + 1.0W (315)	Yes	Y	DL	0.9		WLX	0.707	WLZ	-0.707
35	1.2D + 1.0W (330)	Yes	Y	DL	0.9		WLX	0.866	WLZ	-0.5
36	Ice LCs (Case 3)									
37	1.2D + 1.0Di + 1.0Wi (0)	Yes	Y	DL	1.2	OL1	1	WLXP1	1	WLZP1
38	1.2D + 1.0W (30)	Yes	Y	DL	1.2	OL1	1	WLXP1	0.866	WLZP1
39	1.2D + 1.0W (45)	Yes	Y	DL	1.2	OL1	1	WLXP1	0.707	WLZP1
40	1.2D + 1.0W (60)	Yes	Y	DL	1.2	OL1	1	WLXP1	0.5	WLZP1
41	1.2D + 1.0W (90)	Yes	Y	DL	1.2	OL1	1	WLXP1		WLZP1
42	1.2D + 1.0W (120)	Yes	Y	DL	1.2	OL1	1	WLXP1	-0.5	WLZP1
43	1.2D + 1.0W (135)	Yes	Y	DL	1.2	OL1	1	WLXP1	-0.707	WLZP1
44	1.2D + 1.0W (150)	Yes	Y	DL	1.2	OL1	1	WLXP1	-0.866	WLZP1
45	1.2D + 1.0W (180)	Yes	Y	DL	1.2	OL1	1	WLXP1	-1	WLZP1
46	1.2D + 1.0W (210)	Yes	Y	DL	1.2	OL1	1	WLXP1	-0.866	WLZP1
47	1.2D + 1.0W (225)	Yes	Y	DL	1.2	OL1	1	WLXP1	-0.707	WLZP1
48	1.2D + 1.0W (240)	Yes	Y	DL	1.2	OL1	1	WLXP1	-0.5	WLZP1

Load Combinations (Continued)

	Description	SolveP-Delta	BLC	Factor	BLC	Factor	BLC	Factor	BLC	Factor
49	1.2D + 1.0W (270)	Yes	Y	DL	1.2	OL1	1	WLXP1	WLZP1	-1
50	1.2D + 1.0W (300)	Yes	Y	DL	1.2	OL1	1	WLXP1	0.5	WLZP1 -0.866
51	1.2D + 1.0W (315)	Yes	Y	DL	1.2	OL1	1	WLXP1	0.707	WLZP1 -0.707
52	1.2D + 1.0W (330)	Yes	Y	DL	1.2	OL1	1	WLXP1	0.866	WLZP1 -0.5
53	Maintenance LCs (Case 3)									
54	1.2D + 1.0Di + 1.0Wi (0)	Yes	Y	DL	1.2	19	1.5	WLXP2	1	WLZP2
55	1.2D + 1.0W (30)	Yes	Y	DL	1.2	19	1.5	WLXP2	0.866	WLZP2 0.5
56	1.2D + 1.0W (45)	Yes	Y	DL	1.2	19	1.5	WLXP2	0.707	WLZP2 0.707
57	1.2D + 1.0W (60)	Yes	Y	DL	1.2	19	1.5	WLXP2	0.5	WLZP2 0.866
58	1.2D + 1.0W (90)	Yes	Y	DL	1.2	19	1.5	WLXP2		WLZP2 1
59	1.2D + 1.0W (120)	Yes	Y	DL	1.2	19	1.5	WLXP2	-0.5	WLZP2 0.866
60	1.2D + 1.0W (135)	Yes	Y	DL	1.2	19	1.5	WLXP2	-0.707	WLZP2 0.707
61	1.2D + 1.0W (150)	Yes	Y	DL	1.2	19	1.5	WLXP2	-0.866	WLZP2 0.5
62	1.2D + 1.0W (180)	Yes	Y	DL	1.2	19	1.5	WLXP2	-1	WLZP2
63	1.2D + 1.0W (210)	Yes	Y	DL	1.2	19	1.5	WLXP2	-0.866	WLZP2 -0.5
64	1.2D + 1.0W (225)	Yes	Y	DL	1.2	19	1.5	WLXP2	-0.707	WLZP2 -0.707
65	1.2D + 1.0W (240)	Yes	Y	DL	1.2	19	1.5	WLXP2	-0.5	WLZP2 -0.866
66	1.2D + 1.0W (270)	Yes	Y	DL	1.2	19	1.5	WLXP2		WLZP2 -1
67	1.2D + 1.0W (300)	Yes	Y	DL	1.2	19	1.5	WLXP2	0.5	WLZP2 -0.866
68	1.2D + 1.0W (315)	Yes	Y	DL	1.2	19	1.5	WLXP2	0.707	WLZP2 -0.707
69	1.2D + 1.0W (330)	Yes	Y	DL	1.2	19	1.5	WLXP2	0.866	WLZP2 -0.5
70	1.2D + 1.5Lv	Yes	Y	DL	1.2	20	1.5			

Load Combination Design

	Description	Service	Hot Rolled	Cold Formed	Wood	Concrete	Masonry	Aluminum	Stainless	Connection
1	1.4D		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
2	Wind LCs (Case 1)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
3	1.2D + 1.0W (0)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
4	1.2D + 1.0W (30)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
5	1.2D + 1.0W (45)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
6	1.2D + 1.0W (60)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
7	1.2D + 1.0W (90)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
8	1.2D + 1.0W (120)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
9	1.2D + 1.0W (135)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
10	1.2D + 1.0W (150)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
11	1.2D + 1.0W (180)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
12	1.2D + 1.0W (210)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
13	1.2D + 1.0W (225)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
14	1.2D + 1.0W (240)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
15	1.2D + 1.0W (270)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
16	1.2D + 1.0W (300)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
17	1.2D + 1.0W (315)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
18	1.2D + 1.0W (330)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
19	Uplift LCs (Case 2)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
20	1.2D + 1.0W (0)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
21	1.2D + 1.0W (30)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
22	1.2D + 1.0W (45)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
23	1.2D + 1.0W (60)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
24	1.2D + 1.0W (90)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
25	1.2D + 1.0W (120)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
26	1.2D + 1.0W (135)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
27	1.2D + 1.0W (150)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
28	1.2D + 1.0W (180)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
29	1.2D + 1.0W (210)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
30	1.2D + 1.0W (225)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes

Load Combination Design (Continued)

	Description	Service	Hot Rolled	Cold Formed	Wood	Concrete	Masonry	Aluminum	Stainless	Connection
31	1.2D + 1.0W (240)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
32	1.2D + 1.0W (270)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
33	1.2D + 1.0W (300)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
34	1.2D + 1.0W (315)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
35	1.2D + 1.0W (330)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
36	Ice LCs (Case 3)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
37	1.2D + 1.0Di +1.0Wi (0)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
38	1.2D + 1.0W (30)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
39	1.2D + 1.0W (45)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
40	1.2D + 1.0W (60)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
41	1.2D + 1.0W (90)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
42	1.2D + 1.0W (120)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
43	1.2D + 1.0W (135)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
44	1.2D + 1.0W (150)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
45	1.2D + 1.0W (180)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
46	1.2D + 1.0W (210)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
47	1.2D + 1.0W (225)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
48	1.2D + 1.0W (240)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
49	1.2D + 1.0W (270)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
50	1.2D + 1.0W (300)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
51	1.2D + 1.0W (315)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
52	1.2D + 1.0W (330)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
53	Maintenance LCs (Case 3)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
54	1.2D + 1.0Di +1.0Wi (0)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
55	1.2D + 1.0W (30)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
56	1.2D + 1.0W (45)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
57	1.2D + 1.0W (60)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
58	1.2D + 1.0W (90)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
59	1.2D + 1.0W (120)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
60	1.2D + 1.0W (135)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
61	1.2D + 1.0W (150)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
62	1.2D + 1.0W (180)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
63	1.2D + 1.0W (210)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
64	1.2D + 1.0W (225)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
65	1.2D + 1.0W (240)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
66	1.2D + 1.0W (270)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
67	1.2D + 1.0W (300)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
68	1.2D + 1.0W (315)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
69	1.2D + 1.0W (330)		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
70	1.2D + 1.5Lv		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes

AISC 15TH (360-16): LRFD Member Steel Code Checks

No Data to Print...

Envelope Node Reactions

Node Label		X [lb]	LC	Y [lb]	LC	Z [lb]	LC	MX [k-ft]	LC	MY [k-ft]	LC	MZ [k-ft]	LC
1	P24	max	2491.767	29	1808.754	42	1689.388	31	0.548	33	3.26	29	0.344
2		min	-2496.001	4	12.932	33	-1688.197	6	-3.508	8	-3.284	4	-2.942
3	P13	max	2472.435	27	1810.662	48	1732.208	16	3.983	70	3.288	18	0.35
4		min	-2478.269	18	13.186	23	-1732.919	25	-0.538	23	-3.264	27	-2.002
5	P1	max	1090.15	11	1737.751	37	2611.208	32	0.274	24	2.898	24	4.03
6		min	-1072.942	20	-44.009	28	-2611.52	24	-1.193	70	-2.899	32	-0.811
7	Totals:	max	5892.223	11	5128.665	45	5689.786	15					
8		min	-5892.223	20	2003.57	20	-5689.785	24					

Envelope Node Displacements

	Node Label	X [in]	LC	Y [in]	LC	Z [in]	LC	X Rotation [rad]	LC	Y Rotation [rad]	LC	Z Rotation [rad]	LC
1	P1	max	0	20	0	28	0	24	0	70	0	32	0
2		min	0	11	0	37	0	32	0	24	0	24	0
3	P3	max	0	20	0.028	28	0.027	24	3.261e-3	70	4.908e-4	32	1.09e-3
4		min	0	11	-0.1	3	-0.027	32	-9.693e-4	24	-4.886e-4	24	-3.576e-3
5	P4	max	0	20	0.005	28	0.013	24	1.173e-3	70	9.391e-4	32	6.241e-4
6		min	0	11	-0.022	3	-0.013	32	-2.693e-4	24	-9.381e-4	24	-2.413e-3
7	P7	max	0.114	21	0.036	29	0.027	24	5.056e-3	24	1.181e-3	13	3.422e-3
8		min	-0.114	12	-0.108	4	-0.027	32	-5.133e-3	15	-1.172e-3	22	-2.941e-3
9	P8	max	0.113	35	0.034	27	0.027	24	5.275e-3	7	1.179e-3	34	3.614e-3
10		min	-0.114	10	-0.17	70	-0.027	32	-5.274e-3	15	-1.182e-3	9	-3.235e-3
11	P9	max	0.091	35	-0.012	28	0.014	24	3.58e-3	70	3.573e-3	35	-5.262e-4
12		min	-0.092	10	-0.096	70	-0.014	32	9.251e-4	28	-3.603e-3	10	-4.435e-3
13	P10	max	0.09	21	-0.011	28	0.014	24	-8.978e-4	28	3.495e-3	12	-5.171e-4
14		min	-0.09	12	-0.078	54	-0.014	32	-3.346e-3	54	-3.475e-3	21	-2.074e-3
15	P11	max	0.086	21	0.031	29	0.027	24	3.287e-3	70	1.607e-3	30	1.497e-3
16		min	-0.087	12	-0.103	4	-0.027	32	-1.224e-3	7	-1.645e-3	5	-1.688e-3
17	P12	max	0.088	35	0.03	28	0.027	24	4.048e-3	70	1.503e-3	17	1.546e-3
18		min	-0.089	10	-0.145	70	-0.027	32	-1.037e-3	25	-1.447e-3	26	-3.273e-3
19	P13	max	0	18	0	23	0	25	0	23	0	27	0
20		min	0	27	0	48	0	16	0	70	0	18	0
21	P14	max	0.03	18	0.023	23	0.017	26	8.485e-4	22	7.234e-4	26	1.962e-3
22		min	-0.03	27	-0.102	14	-0.017	18	-4.497e-3	70	-7.524e-4	17	-1.249e-3
23	P15	max	0.013	18	0.004	23	0.007	27	4.378e-4	22	1.096e-3	27	1.213e-3
24		min	-0.013	27	-0.023	14	-0.007	18	-2.543e-3	70	-1.112e-3	18	-3.183e-4
25	P18	max	0.045	5	0.031	24	0.097	24	2.467e-3	7	1.619e-3	25	6.534e-3
26		min	-0.044	30	-0.108	15	-0.097	15	-2.195e-3	32	-1.668e-3	16	-5.507e-3
27	P19	max	0.069	4	0.029	22	0.098	22	4.829e-3	8	1.383e-3	28	4.078e-3
28		min	-0.069	29	-0.176	70	-0.099	13	-4.574e-3	33	-1.407e-3	3	-3.84e-3
29	P20	max	0.053	21	-0.014	22	0.076	22	-9.732e-4	34	3.672e-3	13	-1.327e-4
30		min	-0.053	12	-0.095	70	-0.077	13	-5.711e-3	70	-3.658e-3	22	-2.098e-3
31	P21	max	0.035	6	-0.012	23	0.077	24	4.878e-4	70	3.252e-3	7	3.893e-3
32		min	-0.035	31	-0.08	65	-0.077	15	-5.606e-4	3	-3.25e-3	32	1.094e-3
33	P22	max	0.036	4	0.026	23	0.077	24	1.234e-3	22	1.529e-3	25	1.627e-3
34		min	-0.035	29	-0.104	14	-0.077	15	-1.629e-3	13	-1.538e-3	16	-3.475e-3
35	P23	max	0.058	3	0.027	22	0.076	23	1.426e-3	21	1.582e-3	11	8.926e-4
36		min	-0.058	28	-0.151	70	-0.077	14	-5.24e-3	70	-1.525e-3	20	-1.775e-3
37	P24	max	0	4	0	33	0	6	0	8	0	4	0
38		min	0	29	0	42	0	31	0	33	0	29	0
39	P25	max	0.03	4	0.024	33	0.017	4	3.157e-3	9	7.351e-4	4	4.421e-3
40		min	-0.029	29	-0.102	8	-0.017	29	-8.733e-4	34	-7.032e-4	30	-7.783e-4
41	P26	max	0.013	4	0.004	33	0.007	4	2.1e-3	9	1.111e-3	4	2.104e-3
42		min	-0.013	29	-0.023	8	-0.007	29	-4.501e-4	34	-1.093e-3	29	-3.024e-4
43	P29	max	0.069	3	0.03	35	0.095	9	4.246e-3	23	1.45e-3	3	3.892e-3
44		min	-0.069	28	-0.111	10	-0.094	34	-4.569e-3	14	-1.425e-3	28	-3.821e-3
45	P30	max	0.049	17	0.03	32	0.097	7	2.39e-3	24	1.62e-3	6	6.903e-3
46		min	-0.048	26	-0.173	70	-0.097	15	-2.518e-3	15	-1.568e-3	31	-5.821e-3
47	P31	max	0.037	16	-0.012	33	0.077	7	2.096e-3	70	3.259e-3	24	5.256e-3
48		min	-0.037	25	-0.095	70	-0.077	15	-2.708e-4	28	-3.267e-3	15	1.145e-3
49	P32	max	0.052	35	-0.014	34	0.075	10	3.498e-3	47	3.567e-3	35	-2.261e-4
50		min	-0.052	10	-0.082	60	-0.074	35	9.43e-4	22	-3.596e-3	10	-2.116e-3
51	P33	max	0.059	3	0.027	34	0.073	9	1.9e-3	10	1.564e-3	20	2.191e-3
52		min	-0.059	28	-0.107	9	-0.072	34	-2.701e-3	70	-1.598e-3	11	-9.692e-4
53	P34	max	0.039	18	0.026	33	0.077	7	1.674e-3	9	1.508e-3	6	5.361e-3
54		min	-0.038	27	-0.148	70	-0.077	32	-1.26e-3	34	-1.477e-3	31	-1.349e-3
55	N43	max	0.043	5	0.038	24	0.097	24	2.467e-3	7	1.619e-3	25	6.534e-3

Envelope Node Displacements (Continued)

	Node Label	X [in]	LC	Y [in]	LC	Z [in]	LC	X Rotation [rad]	LC	Y Rotation [rad]	LC	Z Rotation [rad]	LC	
56		min	-0.041	30	-0.115	15	-0.097	15	-2.196e-3	32	-1.668e-3	16	-5.507e-3	20
57	N44	max	0.047	17	0.038	32	0.097	7	2.39e-3	24	1.62e-3	6	6.903e-3	11
58		min	-0.045	26	-0.179	70	-0.097	15	-2.518e-3	15	-1.568e-3	31	-5.821e-3	20
59	N45	max	0.047	5	0.024	24	0.097	24	2.486e-3	7	1.588e-3	25	6.547e-3	11
60		min	-0.046	30	-0.102	15	-0.097	15	-2.228e-3	32	-1.638e-3	16	-5.521e-3	20
61	N48A	max	0.051	17	0.023	32	0.097	7	2.425e-3	24	1.595e-3	6	6.917e-3	11
62		min	-0.05	26	-0.168	70	-0.097	15	-2.537e-3	15	-1.542e-3	31	-5.836e-3	20
63	N51	max	0.306	20	0.024	24	0.278	7	2.715e-3	7	2.842e-3	20	6.529e-3	28
64		min	-0.319	11	-0.109	15	-0.275	32	-2.448e-3	32	-2.908e-3	11	-6.754e-3	3
65	N54	max	0.314	20	0.023	32	0.278	7	2.528e-3	25	2.902e-3	11	6.311e-3	28
66		min	-0.326	11	-0.182	70	-0.275	32	-2.609e-3	16	-2.811e-3	20	-6.567e-3	3
67	N57	max	0.233	10	0.025	23	0.013	26	2.033e-3	7	1.588e-3	25	6.092e-3	11
68		min	-0.19	35	-0.104	14	-0.057	70	-1.775e-3	32	-1.638e-3	16	-5.067e-3	20
69	N60	max	0.244	11	0.024	33	0.02	56	1.971e-3	24	1.595e-3	6	6.462e-3	11
70		min	-0.198	20	-0.169	70	-0.08	70	-2.083e-3	15	-1.542e-3	31	-5.382e-3	20
71	N63	max	0.373	20	0.023	24	0.305	7	2.721e-3	7	2.842e-3	20	6.535e-3	28
72		min	-0.384	11	-0.108	15	-0.299	32	-2.455e-3	32	-2.908e-3	11	-6.76e-3	3
73	N66	max	0.379	20	0.023	33	0.303	7	2.533e-3	25	2.902e-3	11	6.317e-3	28
74		min	-0.389	11	-0.181	70	-0.3	32	-2.614e-3	16	-2.811e-3	20	-6.573e-3	3
75	N67	max	0.288	20	0.039	24	0.278	7	2.663e-3	6	3.074e-3	35	6.437e-3	28
76		min	-0.3	11	-0.123	15	-0.275	32	-2.408e-3	31	-3.144e-3	10	-6.664e-3	3
77	N68	max	0.296	20	0.038	32	0.278	7	2.517e-3	25	3.148e-3	11	6.209e-3	28
78		min	-0.307	11	-0.197	70	-0.275	32	-2.59e-3	16	-3.045e-3	20	-6.468e-3	3
79	N111A	max	0.284	20	0.039	29	0.278	24	5.721e-3	24	2.818e-3	8	4.266e-3	10
80		min	-0.292	11	-0.114	4	-0.28	15	-5.872e-3	15	-2.804e-3	33	-4.09e-3	35
81	N112A	max	0.293	20	0.036	27	0.278	24	5.57e-3	7	2.813e-3	6	4.127e-3	12
82		min	-0.295	11	-0.179	70	-0.28	15	-5.524e-3	32	-2.778e-3	31	-4.097e-3	21
83	N113A	max	0.297	20	0.031	24	0.278	7	2.663e-3	6	3.074e-3	35	6.437e-3	28
84		min	-0.31	11	-0.116	15	-0.275	32	-2.408e-3	31	-3.144e-3	10	-6.664e-3	3
85	N114A	max	0.292	20	0.03	22	0.29	7	5.103e-3	8	2.808e-3	17	3.718e-3	27
86		min	-0.304	11	-0.178	70	-0.286	32	-4.971e-3	33	-2.808e-3	9	-3.775e-3	18
87	N115A	max	0.298	20	0.031	34	0.272	24	5.079e-3	23	2.87e-3	13	3.798e-3	29
88		min	-0.303	11	-0.112	9	-0.279	15	-5.281e-3	14	-2.844e-3	22	-4.03e-3	4
89	N116A	max	0.305	20	0.03	32	0.278	7	2.517e-3	25	3.148e-3	11	6.209e-3	28
90		min	-0.317	11	-0.19	70	-0.275	32	-2.59e-3	16	-3.045e-3	20	-6.468e-3	3
91	N69A	max	0.047	5	0.024	23	0.098	24	2.486e-3	7	1.588e-3	25	6.547e-3	11
92		min	-0.046	30	-0.103	14	-0.098	15	-2.228e-3	32	-1.638e-3	16	-5.521e-3	20
93	N70A	max	0.051	17	0.023	33	0.098	7	2.425e-3	24	1.595e-3	6	6.917e-3	11
94		min	-0.05	26	-0.169	70	-0.098	15	-2.537e-3	15	-1.542e-3	31	-5.836e-3	20
95	N71A	max	0.306	20	0.023	24	0.278	7	2.715e-3	7	2.842e-3	20	6.529e-3	28
96		min	-0.319	11	-0.108	15	-0.274	32	-2.448e-3	32	-2.908e-3	11	-6.754e-3	3
97	N72A	max	0.314	20	0.023	33	0.278	7	2.528e-3	25	2.902e-3	11	6.311e-3	28
98		min	-0.326	11	-0.181	70	-0.274	32	-2.609e-3	16	-2.811e-3	20	-6.567e-3	3
99	N122A	max	0.108	21	-0.016	28	0.014	24	-9.317e-4	28	3.522e-3	12	1.006e-3	29
100		min	-0.108	12	-0.095	54	-0.014	32	-3.471e-3	54	-3.507e-3	21	-1.998e-3	4
101	N124B	max	0.109	35	-0.017	28	0.014	24	3.661e-3	70	3.636e-3	35	9.142e-4	27
102		min	-0.11	10	-0.115	70	-0.014	32	9.596e-4	28	-3.66e-3	10	-4.185e-3	70
103	N122B	max	0.043	6	-0.017	23	0.091	24	1.619e-3	70	3.286e-3	7	3.58e-3	66
104		min	-0.043	31	-0.098	65	-0.091	15	-8.802e-4	32	-3.283e-3	32	3.725e-4	24
105	N123A	max	0.062	21	-0.019	22	0.093	22	8.193e-5	22	3.795e-3	13	-3.298e-4	29
106		min	-0.062	12	-0.113	70	-0.093	13	-5.331e-3	70	-3.772e-3	22	-2.658e-3	55
107	N125	max	0.062	35	-0.019	34	0.091	10	2.78e-3	43	3.643e-3	34	-3.419e-4	27
108		min	-0.062	10	-0.1	60	-0.09	35	-1.625e-4	34	-3.675e-3	9	-2.693e-3	69
109	N126	max	0.045	16	-0.017	33	0.091	7	1.786e-3	70	3.3e-3	24	5.171e-3	70
110		min	-0.044	25	-0.113	70	-0.091	15	-1.272e-3	15	-3.308e-3	15	4.465e-4	33

Envelope Node Displacements (Continued)

Node Label	X [in]	LC	Y [in]	LC	Z [in]	LC	X Rotation [rad]	LC	Y Rotation [rad]	LC	Z Rotation [rad]	LC
111 N125A	max 0.05	16	-0.019	33	0.091	7	1.786e-3	70	3.3e-3	24	5.171e-3	70
112	min -0.049	25	-0.11	70	-0.091	15	-1.272e-3	15	-3.308e-3	15	4.465e-4	33
113 N126A	max 0.05	16	-0.02	33	0.096	7	1.786e-3	70	1.678e-3	15	6.633e-3	11
114	min -0.049	25	-0.119	70	-0.096	15	-1.272e-3	15	-1.674e-3	24	-5.5e-3	20
115 N128	max 0.112	35	-0.018	28	0.013	23	3.661e-3	70	3.636e-3	35	9.142e-4	27
116	min -0.113	10	-0.112	70	-0.013	14	9.596e-4	28	-3.66e-3	10	-4.185e-3	70
117 N129	max 0.117	35	-0.019	28	0.013	24	4.507e-3	6	1.865e-3	10	3.209e-3	13
118	min -0.118	10	-0.12	70	-0.013	15	-4.51e-3	14	-1.855e-3	35	-2.773e-3	22
119 N131	max 0.059	21	-0.021	22	0.098	22	8.193e-5	22	3.795e-3	13	-3.298e-4	29
120	min -0.059	12	-0.11	70	-0.098	13	-5.331e-3	70	-3.772e-3	22	-2.658e-3	55
121 N132	max 0.064	21	-0.022	22	0.101	22	4.766e-3	8	1.881e-3	22	2.732e-3	27
122	min -0.065	12	-0.118	70	-0.101	13	-4.376e-3	33	-1.912e-3	13	-2.832e-3	18
123 N132A	max 0.048	6	-0.019	23	0.091	24	1.619e-3	70	3.286e-3	7	3.58e-3	66
124	min -0.047	31	-0.099	65	-0.091	15	-8.802e-4	32	-3.283e-3	32	3.725e-4	24
125 N133	max 0.048	6	-0.019	23	0.096	7	1.619e-3	70	1.635e-3	32	6.486e-3	11
126	min -0.047	31	-0.105	65	-0.096	15	-8.802e-4	32	-1.635e-3	7	-5.375e-3	20
127 N134	max 0.059	35	-0.021	34	0.096	10	2.78e-3	43	3.643e-3	34	-3.419e-4	27
128	min -0.059	10	-0.101	60	-0.095	35	-1.625e-4	34	-3.675e-3	9	-2.693e-3	69
129 N135	max 0.064	35	-0.022	34	0.099	10	4.209e-3	23	1.877e-3	10	2.675e-3	29
130	min -0.064	10	-0.107	60	-0.098	35	-4.681e-3	14	-1.835e-3	35	-2.946e-3	4
131 N137	max 0.11	21	-0.018	28	0.012	25	-1.119e-3	27	5.176e-3	12	8.874e-4	29
132	min -0.111	12	-0.097	54	-0.012	33	-4.331e-3	69	-5.182e-3	21	-2.245e-3	4
133 N138	max 0.118	21	-0.019	28	0.014	24	4.38e-3	25	1.839e-3	21	3.185e-3	9
134	min -0.118	12	-0.104	54	-0.014	32	-4.475e-3	16	-1.842e-3	12	-2.59e-3	34
135 N72B	max 0.018	3	-0.035	20	0.097	7	1.784e-3	70	3.066e-3	15	6.446e-3	11
136	min -0.018	28	-0.116	62	-0.097	15	-1.154e-3	32	-3.064e-3	7	-5.278e-3	20
137 N73	max 0.385	20	-0.035	28	0.278	7	2.493e-3	7	3.167e-4	16	8.352e-3	28
138	min -0.399	11	-0.133	54	-0.275	32	-2.404e-3	32	-3.087e-4	25	-8.415e-3	3
139 N74	max 0.096	11	-0.009	20	0.2	24	3.584e-3	15	4.386e-3	15	1.609e-3	62
140	min -0.055	20	-0.12	62	-0.204	15	-3.495e-3	24	-4.383e-3	24	-6.734e-4	20
141 N75	max 0.469	20	-0.042	31	0.303	7	2.5e-3	7	3.167e-4	16	8.358e-3	28
142	min -0.483	11	-0.136	56	-0.298	32	-2.41e-3	32	-3.087e-4	25	-8.421e-3	3
143 N76	max 0.018	3	-0.03	20	0.094	7	1.784e-3	70	3.066e-3	15	6.446e-3	11
144	min -0.018	28	-0.118	62	-0.094	15	-1.154e-3	32	-3.064e-3	7	-5.278e-3	20
145 N77	max 0.385	20	-0.042	31	0.278	7	2.493e-3	7	3.167e-4	16	8.352e-3	28
146	min -0.399	11	-0.131	57	-0.274	32	-2.404e-3	32	-3.087e-4	25	-8.415e-3	3
147 N81A	max 0.072	3	0.039	35	0.093	9	4.246e-3	23	1.45e-3	3	3.892e-3	11
148	min -0.072	28	-0.118	10	-0.091	34	-4.569e-3	14	-1.425e-3	28	-3.821e-3	20
149 N82A	max 0.112	35	0.042	27	0.03	24	5.275e-3	7	1.179e-3	34	3.614e-3	12
150	min -0.112	10	-0.175	70	-0.03	32	-5.274e-3	15	-1.182e-3	9	-3.235e-3	21
151 N83A	max 0.067	18	0.023	34	0.098	9	4.266e-3	23	1.414e-3	3	3.913e-3	11
152	min -0.067	27	-0.103	9	-0.096	34	-4.587e-3	14	-1.389e-3	28	-3.83e-3	20
153 N84	max 0.115	35	0.026	27	0.025	24	5.277e-3	7	1.144e-3	34	3.644e-3	12
154	min -0.116	10	-0.166	70	-0.025	15	-5.286e-3	15	-1.148e-3	9	-3.272e-3	21
155 N85	max 0.3	20	0.023	34	0.278	24	5.137e-3	23	2.547e-3	13	3.958e-3	29
156	min -0.306	11	-0.105	9	-0.284	15	-5.349e-3	14	-2.552e-3	5	-4.183e-3	4
157 N86	max 0.295	20	0.028	27	0.284	24	5.705e-3	7	2.628e-3	6	4.128e-3	12
158	min -0.297	11	-0.171	70	-0.286	15	-5.651e-3	32	-2.606e-3	14	-4.094e-3	21
159 N87	max 0.095	12	0.024	34	0.184	12	3.873e-3	23	1.414e-3	3	3.459e-3	11
160	min -0.092	21	-0.105	9	-0.168	21	-4.193e-3	14	-1.388e-3	28	-3.377e-3	20
161 N88	max 0.122	15	0.024	28	0.182	15	4.823e-3	7	1.145e-3	34	3.251e-3	12
162	min -0.107	24	-0.165	70	-0.182	7	-4.832e-3	15	-1.149e-3	9	-2.879e-3	21
163 N89	max 0.339	20	0.024	34	0.326	24	5.142e-3	23	2.547e-3	13	3.963e-3	29
164	min -0.342	11	-0.106	9	-0.335	15	-5.354e-3	14	-2.552e-3	5	-4.188e-3	4
165 N90	max 0.332	20	0.029	28	0.34	24	5.711e-3	7	2.628e-3	6	4.134e-3	12

Envelope Node Displacements (Continued)

Node Label		X [in]	LC	Y [in]	LC	Z [in]	LC	X Rotation [rad]	LC	Y Rotation [rad]	LC	Z Rotation [rad]	LC	
166		min	-0.335	11	-0.171	70	-0.342	15	-5.657e-3	32	-2.606e-3	14	-4.099e-3	21
167	N91	max	0.295	20	0.04	35	0.267	24	5.079e-3	23	2.87e-3	13	3.798e-3	29
168		min	-0.3	11	-0.12	10	-0.274	15	-5.281e-3	14	-2.844e-3	22	-4.03e-3	4
169	N92	max	0.291	20	0.045	27	0.271	24	5.57e-3	7	2.813e-3	6	4.127e-3	12
170		min	-0.294	11	-0.188	70	-0.273	15	-5.524e-3	32	-2.778e-3	31	-4.097e-3	21
171	N93	max	0.068	18	0.023	34	0.098	9	4.266e-3	23	1.414e-3	3	3.913e-3	11
172		min	-0.068	28	-0.103	9	-0.097	34	-4.587e-3	14	-1.389e-3	28	-3.83e-3	20
173	N94	max	0.116	35	0.026	28	0.025	24	5.277e-3	7	1.144e-3	34	3.644e-3	12
174		min	-0.117	10	-0.165	70	-0.026	15	-5.286e-3	15	-1.148e-3	9	-3.272e-3	21
175	N95	max	0.299	20	0.024	34	0.279	24	5.137e-3	23	2.547e-3	13	3.958e-3	29
176		min	-0.304	11	-0.106	9	-0.285	15	-5.349e-3	14	-2.552e-3	5	-4.183e-3	4
177	N96	max	0.296	20	0.029	28	0.283	24	5.705e-3	7	2.628e-3	6	4.128e-3	12
178		min	-0.298	11	-0.171	70	-0.285	15	-5.651e-3	32	-2.606e-3	14	-4.094e-3	21
179	N109	max	0.112	21	0.044	29	0.03	24	5.056e-3	24	1.181e-3	13	3.422e-3	10
180		min	-0.113	12	-0.115	4	-0.03	15	-5.133e-3	15	-1.172e-3	22	-2.941e-3	35
181	N110	max	0.071	4	0.037	21	0.096	23	4.829e-3	8	1.383e-3	28	4.078e-3	11
182		min	-0.071	29	-0.183	70	-0.097	13	-4.574e-3	33	-1.407e-3	3	-3.84e-3	20
183	N111	max	0.116	21	0.028	29	0.025	24	5.066e-3	24	1.144e-3	13	3.451e-3	10
184		min	-0.116	12	-0.102	4	-0.025	32	-5.136e-3	15	-1.135e-3	22	-2.975e-3	35
185	N112	max	0.067	4	0.022	22	0.101	22	4.849e-3	8	1.351e-3	28	4.1e-3	11
186		min	-0.067	29	-0.17	70	-0.102	13	-4.596e-3	33	-1.375e-3	3	-3.848e-3	20
187	N113	max	0.285	20	0.03	29	0.284	24	5.846e-3	24	2.672e-3	8	4.268e-3	10
188		min	-0.293	11	-0.105	4	-0.287	15	-6.002e-3	15	-2.652e-3	33	-4.087e-3	35
189	N114	max	0.294	20	0.022	22	0.295	7	5.175e-3	8	2.527e-3	16	3.878e-3	27
190		min	-0.306	11	-0.172	70	-0.291	32	-5.034e-3	33	-2.497e-3	25	-3.929e-3	18
191	N115	max	0.128	7	0.025	29	0.176	15	4.612e-3	24	1.145e-3	13	3.058e-3	10
192		min	-0.108	32	-0.099	4	-0.173	24	-4.682e-3	15	-1.135e-3	22	-2.582e-3	35
193	N116	max	0.106	10	0.023	22	0.173	35	4.455e-3	8	1.351e-3	28	3.647e-3	11
194		min	-0.096	35	-0.169	70	-0.186	10	-4.203e-3	33	-1.375e-3	3	-3.395e-3	20
195	N117	max	0.323	20	0.031	28	0.342	24	5.852e-3	24	2.672e-3	8	4.274e-3	10
196		min	-0.333	11	-0.106	3	-0.345	15	-6.008e-3	15	-2.652e-3	33	-4.092e-3	35
197	N118	max	0.332	20	0.023	22	0.344	7	5.181e-3	8	2.527e-3	16	3.883e-3	27
198		min	-0.343	11	-0.172	70	-0.339	32	-5.04e-3	33	-2.497e-3	25	-3.934e-3	18
199	N119	max	0.283	20	0.049	29	0.27	24	5.721e-3	24	2.818e-3	8	4.266e-3	10
200		min	-0.291	11	-0.122	4	-0.273	15	-5.872e-3	15	-2.804e-3	33	-4.09e-3	35
201	N120	max	0.289	20	0.038	22	0.284	7	5.103e-3	8	2.808e-3	17	3.718e-3	27
202		min	-0.301	11	-0.185	70	-0.28	32	-4.971e-3	33	-2.808e-3	9	-3.775e-3	18
203	N121	max	0.116	21	0.027	29	0.025	24	5.066e-3	24	1.144e-3	13	3.451e-3	10
204		min	-0.117	12	-0.101	4	-0.025	32	-5.136e-3	15	-1.135e-3	22	-2.975e-3	35
205	N122	max	0.068	4	0.022	22	0.101	22	4.849e-3	8	1.351e-3	28	4.1e-3	11
206		min	-0.068	29	-0.169	70	-0.102	13	-4.596e-3	33	-1.375e-3	3	-3.848e-3	20
207	N123	max	0.286	20	0.031	28	0.283	24	5.846e-3	24	2.672e-3	8	4.268e-3	10
208		min	-0.294	11	-0.106	3	-0.285	15	-6.002e-3	15	-2.652e-3	33	-4.087e-3	35
209	N124	max	0.293	20	0.023	22	0.296	7	5.175e-3	8	2.527e-3	16	3.878e-3	27
210		min	-0.305	11	-0.172	70	-0.292	32	-5.034e-3	33	-2.497e-3	25	-3.929e-3	18
211	N129B	max	0.091	35	-0.035	31	0.054	9	4.224e-3	23	3.667e-3	10	2.927e-3	12
212		min	-0.091	10	-0.117	57	-0.054	34	-4.415e-3	14	-3.639e-3	35	-2.757e-3	21
213	N130A	max	0.315	20	-0.031	29	0.333	24	6.858e-3	23	1.026e-4	70	4.598e-3	12
214		min	-0.318	11	-0.121	55	-0.337	15	-6.876e-3	14	-1.83e-4	7	-4.532e-3	21
215	N131A	max	0.169	35	-0.024	35	0.131	10	2.197e-3	35	3.16e-3	11	2.854e-3	35
216		min	-0.17	10	-0.118	61	-0.122	35	-2.411e-3	10	-3.121e-3	20	-2.965e-3	10
217	N132B	max	0.353	20	-0.023	30	0.395	24	6.863e-3	23	1.026e-4	70	4.603e-3	12
218		min	-0.358	11	-0.127	56	-0.399	15	-6.881e-3	14	-1.83e-4	7	-4.537e-3	21
219	N133B	max	0.088	35	-0.03	31	0.052	9	4.224e-3	23	3.667e-3	10	2.927e-3	12
220		min	-0.088	10	-0.117	57	-0.052	34	-4.415e-3	14	-3.639e-3	35	-2.757e-3	21

Envelope Node Displacements (Continued)

Node Label	X [in]	LC	Y [in]	LC	Z [in]	LC	X Rotation [rad]	LC	Y Rotation [rad]	LC	Z Rotation [rad]	LC
221 N134A	max 0.315	20	-0.023	30	0.333	24	6.858e-3	23	1.026e-4	70	4.598e-3	12
222	min -0.319	11	-0.122	56	-0.337	15	-6.876e-3	14	-1.83e-4	7	-4.532e-3	21
223 N135A	max 0.091	21	-0.035	25	0.056	22	4.393e-3	8	3.646e-3	21	2.946e-3	10
224	min -0.092	12	-0.117	67	-0.056	13	-4.29e-3	33	-3.664e-3	12	-2.609e-3	35
225 N136	max 0.306	20	-0.031	27	0.343	7	6.854e-3	25	3.615e-4	70	4.622e-3	10
226	min -0.316	11	-0.121	69	-0.343	15	-6.924e-3	16	-1.324e-4	35	-4.402e-3	35
227 N137A	max 0.177	5	-0.023	21	0.118	21	2.205e-3	12	3.024e-3	20	3.006e-3	4
228	min -0.171	30	-0.118	63	-0.124	12	-2.076e-3	21	-3.053e-3	11	-2.957e-3	29
229 N138A	max 0.343	20	-0.023	26	0.406	7	6.859e-3	25	3.615e-4	70	4.628e-3	10
230	min -0.355	11	-0.127	68	-0.407	15	-6.929e-3	16	-1.324e-4	35	-4.407e-3	35
231 N139	max 0.088	21	-0.03	25	0.054	22	4.393e-3	8	3.646e-3	21	2.946e-3	10
232	min -0.089	12	-0.117	67	-0.054	13	-4.29e-3	33	-3.664e-3	12	-2.609e-3	35
233 N140	max 0.306	20	-0.023	26	0.343	7	6.854e-3	25	3.615e-4	70	4.622e-3	10
234	min -0.316	11	-0.122	68	-0.343	15	-6.924e-3	16	-1.324e-4	35	-4.402e-3	35
235 N127	max 0.135	34	-0.024	35	0.103	11	2.192e-3	35	3.16e-3	11	2.845e-3	35
236	min -0.135	26	-0.118	61	-0.096	20	-2.406e-3	10	-3.121e-3	20	-2.956e-3	10
237 N130	max 0.307	20	-0.022	29	0.32	24	6.983e-3	23	1.489e-4	30	4.908e-3	12
238	min -0.31	11	-0.122	55	-0.324	15	-7.006e-3	14	-2.355e-4	5	-4.852e-3	21
239 N141	max 0.101	20	-0.024	29	0.071	25	5.491e-3	23	3.082e-3	10	4.412e-3	12
240	min -0.103	11	-0.118	55	-0.072	16	-5.65e-3	14	-3.07e-3	35	-4.356e-3	21
241 N142	max 0.166	20	-0.017	29	0.145	24	6.968e-3	24	1.997e-3	27	6.19e-3	11
242	min -0.168	11	-0.12	55	-0.147	15	-7.076e-3	15	-2.018e-3	18	-6.214e-3	3
243 N143	max 0.298	20	-0.022	26	0.33	7	6.987e-3	25	3.478e-4	70	4.924e-3	10
244	min -0.307	11	-0.122	68	-0.33	15	-7.051e-3	16	-4.157e-5	32	-4.716e-3	35
245 N144	max 0.142	5	-0.023	21	0.093	21	2.199e-3	12	3.024e-3	20	2.997e-3	4
246	min -0.136	30	-0.118	63	-0.097	12	-2.071e-3	21	-3.053e-3	11	-2.948e-3	29
247 N145	max 0.1	21	-0.025	27	0.075	6	5.638e-3	8	3.077e-3	4	4.411e-3	10
248	min -0.102	12	-0.118	69	-0.074	31	-5.561e-3	33	-3.078e-3	12	-4.197e-3	35
249 N146	max 0.162	20	-0.018	27	0.152	7	7.166e-3	7	2.025e-3	4	6.153e-3	11
250	min -0.166	11	-0.12	69	-0.151	32	-7.133e-3	32	-1.994e-3	29	-6.022e-3	20
251 N147	max 0.368	20	-0.042	29	0.273	7	3.046e-3	7	5.167e-4	15	8.537e-3	28
252	min -0.383	11	-0.131	55	-0.27	32	-2.958e-3	32	-5.053e-4	24	-8.597e-3	3
253 N149	max 0.077	11	-0.009	20	0.158	24	3.574e-3	15	4.386e-3	15	1.609e-3	62
254	min -0.047	20	-0.12	62	-0.161	15	-3.484e-3	24	-4.384e-3	24	-6.84e-4	20
255 N150	max 0.055	20	-0.037	20	0.107	7	3.352e-3	7	2.821e-3	15	7.692e-3	11
256	min -0.061	11	-0.12	62	-0.107	32	-3.263e-3	32	-2.817e-3	24	-6.891e-3	20
257 N151	max 0.151	20	-0.04	28	0.161	7	5.496e-3	7	2.164e-3	15	9.046e-3	11
258	min -0.163	11	-0.125	54	-0.159	32	-5.414e-3	32	-2.157e-3	24	-8.737e-3	20
259 N130B	max 0.146	20	0.024	33	0.171	7	4.548e-3	7	1.059e-3	10	6.801e-3	11
260	min -0.157	11	-0.175	70	-0.17	32	-4.392e-3	32	-9.926e-4	35	-6.461e-3	20
261 N131B	max 0.18	20	0.033	28	0.13	24	6.464e-3	24	9.587e-4	4	4.638e-3	28
262	min -0.184	11	-0.166	70	-0.131	15	-6.545e-3	15	-9.539e-4	12	-4.684e-3	3
263 N132C	max 0.159	20	0.014	22	0.166	7	4.992e-3	8	1.e-3	15	6.086e-3	11
264	min -0.165	11	-0.172	70	-0.164	32	-4.896e-3	33	-1.006e-3	7	-5.735e-3	20

Envelope AISC 15TH (360-16): LRFD Member Steel Code Checks

Member	Shape	Code	CheckLoc[in]	LC	Shear CheckLoc[in]	LC	CheckLoc[in]	DirL	Cphi*Pnc [lb]	phi*Pnt [lb]	phi*Mn y-y [k-ft]	phi*Mn z-z [k-ft]	Cb	Eqn
1 M2	HSS4X4X6	0.25	40	5	0.093	40	y	70	188250.474	197892	22.046	22.046	1.882	H1-1b
2 M3	L2x2x4	0.27	0	3	0.024	27.295	y	10	29527.562	42480	0.96	2.19	1.5	H2-1
3 M4	L2x2x4	0.261	0	4	0.024	27.295	z	12	29527.562	42480	0.96	2.19	1.5	H2-1
4 M5	PL6.5x0.375	0.312	21	18	0.103	36.312	y	70	3658.14	78975	0.617	7.866	1.399	H1-1b
5 M7	HSS4X4X6	0.269	40	16	0.094	23.75	y	70	188250.475	197892	22.046	22.046	1.915	H1-1b
6 M8	L2x2x4	0.296	0	13	0.025	0	y	5	29527.563	42480	0.96	2.19	1.5	H2-1
7 M9	L2x2x4	0.23	0	14	0.021	0	z	6	29527.563	42480	0.96	2.19	1.5	H2-1
8 M10	PL6.5x0.375	0.328	21	13	0.101	36.312	y	8	3658.14	78975	0.617	7.695	1.369	H1-1b

Envelope AISC 15TH (360-16): LRFD Member Steel Code Checks (Continued)

Member	Shape	Code CheckLoc[in]	LocShear CheckLoc[in]	DirL	Cphi*Pnc [lb]	phi*Pnt [lb]	y	70188250.475	197892	22.046	22.046	1.9	H1-1b	
9	M12	HSS4X4X6	0.268	40	11	0.092	40	y	70188250.475	197892	22.046	22.046	1.9	H1-1b
10	M13	L2x2x4	0.243	0	8	0.022	0	y	1629527.562	42480	0.96	2.19	1.5	H2-1
11	M14	L2x2x4	0.283	0	9	0.024	0	z	1729527.563	42480	0.96	2.19	1.5	H2-1
12	M15	PL6.5x0.375	0.313	21	9	0.102	36.312	y	3 3658.14	78975	0.617	7.517	1.337	H1-1b
13	M18	Pipe3.5x0.165	0.173	31	16	0.063	64	6	45873.009	71580.6	6.338	6.338	1.451	H1-1b
14	MP9	PIPE_2.5	0.144	42	7	0.075	42	5	33487.322	66654	4.727	4.727	1.947	H1-1b
15	MP7	PIPE_2.5	0.134	42	15	0.071	42	17	33487.322	66654	4.727	4.727	1.978	H1-1b
16	M25	PIPE_2.5	0.114	48	16	0.048	90	10	33487.322	66654	4.727	4.727	1.721	H1-1b
17	M28	L6.6x4.46x0.25	0.152	41.562	8	0.021	42	z	1751170.949	87561	2.465	7.125	1.136	H2-1
18	M29	L6.6x4.46x0.25	0.134	41.562	14	0.018	42	z	6 51170.949	87561	2.465	7.125	1.136	H2-1
19	M30	L6.6x4.46x0.25	0.145	0.437	30	0.021	0	z	1251170.949	87561	2.465	7.125	1.136	H2-1
20	M61A	C3.38x2.06x0.25	0.358	0	3	0.045	28.187	z	1147760.074	56700	2.203	5.752	1.629	H1-1b
21	M63A	C3.38x2.06x0.25	0.367	0	3	0.048	28.188	z	1147760.074	56700	2.203	5.752	1.628	H1-1b
22	M60A	C3.38x2.06x0.25	0.335	0	14	0.043	28.188	z	6 47760.074	56700	2.203	5.752	1.626	H1-1b
23	M61B	C3.38x2.06x0.25	0.375	0	14	0.05	28.188	z	6 47760.074	56700	2.203	5.752	1.629	H1-1b
24	M62A	C3.38x2.06x0.25	0.367	0	9	0.048	28.188	z	1747760.074	56700	2.203	5.752	1.634	H1-1b
25	M63B	C3.38x2.06x0.25	0.34	0	8	0.045	28.187	z	1647760.074	56700	2.203	5.752	1.626	H1-1b
26	M75	PL_2.375X0.5	0.398	1.5	5	0.213	0	y	6838256.871	38475	0.401	1.904	2.165	H1-1b
27	MP8	PIPE_2.5	0.251	42	15	0.096	84	7	33487.322	66654	4.727	4.727	1.718	H1-1b
28	M48	Pipe3.5x0.165	0.185	65	26	0.074	64	1645873.009	71580.6	6.338	6.338	1.655	H1-1b	
29	MP3	PIPE_2.5	0.154	42	18	0.064	60	1533487.322	66654	4.727	4.727	2.022	H1-1b	
30	MP1	PIPE_2.5	0.137	42	10	0.065	42	12	33487.322	66654	4.727	4.727	1.898	H1-1b
31	M51	PIPE_2.5	0.126	90	18	0.049	6	1133487.322	66654	4.727	4.727	1.816	H1-1b	
32	M62	Pipe3.5x0.165	0.187	31	30	0.071	32	5 45873.009	71580.6	6.338	6.338	1.724	H1-1b	
33	MP6	PIPE_2.5	0.145	42	12	0.069	42	10	33487.322	66654	4.727	4.727	1.916	H1-1b
34	MP4	PIPE_2.5	0.144	42	4	0.06	42	7	33487.322	66654	4.727	4.727	1.993	H1-1b
35	M65A	PIPE_2.5	0.134	6	4	0.046	90	1133487.322	66654	4.727	4.727	1.844	H1-1b	
36	MP2	PIPE_2.5	0.238	42	18	0.098	42	9	33487.322	66654	4.727	4.727	1.801	H1-1b
37	MP5	PIPE_2.5	0.238	42	4	0.098	42	13	33487.322	66654	4.727	4.727	1.801	H1-1b

Material Take-Off

Material	Size	Pieces	Length[in]	Weight[K]
1 General Members				
2 RIGID		29	35.1	0
3 Total General		29	35.1	0
4				
5 Hot Rolled Steel				
6 A1011 36 ksi	C3.38x2.06x0.25	6	198	0.098
7 A1011 36 ksi	PL6.5x0.375	3	126	0.087
8 A1011 36 ksi	L6.6x4.46x0.25	3	126	0.097
9 A36 Gr.36	PL_2.375X0.5	1	1.5	0.001
10 A500 GR.C	HSS4X4X6	3	120	0.163
11 A500 GR.C	Pipe3.5x0.165	3	288	0.141
12 A500 GR.C	PIPE_2.5	12	1152	0.526
13 A529 Gr. 50	L2x2x4	6	163.8	0.044
14 Total HR Steel		37	2175.3	1.156

Warning Log

Message

[1] There are members defined as member type: "Beam" that are vertical (or nearly vertical). For proper deflection optimization, change member type to "Column".