

KENNETH C. BALDWIN

280 Trumbull Street  
Hartford, CT 06103-3597  
Main (860) 275-8200  
Fax (860) 275-8299  
kbaldwin@rc.com  
Direct (860) 275-8345

Also admitted in Massachusetts  
and New York

October 14, 2021

*Via Electronic Mail*

Melanie A. Bachman, Esq.  
Executive Director/Staff Attorney  
Connecticut Siting Council  
10 Franklin Square  
New Britain, CT 06051

Re: **Notice of Exempt Modification – Facility Modification  
44 Rich Road (a/k/a 38 Rich Road), Thompson, Connecticut**

Dear Attorney Bachman:

Cellco Partnership d/b/a Verizon Wireless (“Cellco”) currently maintains an existing wireless telecommunications facility at the above-referenced property address (the “Property”). The facility consists of antennas and remote radio heads attached to a tower and associated equipment on the ground near the base of the tower. The tower and Cellco’s use of the tower were approved by the Siting Council (“Council”) in January of 2008 (Docket No. 344). A copy of the Docket No. 344 Decision and Order is included in [Attachment 1](#).

Cellco now intends to modify its facility by replacing twelve (12) existing antennas with three (3) new Samsung MT6407-77A antennas and six (6) MX06FRO660-03 antennas on Cellco’s existing antenna t-arm mounts. Cellco also intends to replace six (6) remote radio heads (“RRHs”) with six (6) new RRHs behind its antennas. A set of project plans showing Cellco’s proposed facility modifications and new antennas specifications are included in [Attachment 2](#).

Please accept this letter as notification pursuant to R.C.S.A. § 16-50j-73, for construction that constitutes an exempt modification pursuant to R.C.S.A. § 16-50j-72(b)(2). In accordance with R.C.S.A. § 16-50j-73, a copy of this letter is being sent to Thompson’s Chief Elected Official and Land Use Officer. The Town of Thompson is the owner of the Property.

Melanie A. Bachman, Esq.  
October 14, 2021  
Page 2

The planned modifications to the facility fall squarely within those activities explicitly provided for in R.C.S.A. § 16-50j-72(b)(2).

1. The proposed modifications will not result in an increase in the height of the existing tower. Cellco's replacement antennas will be installed on Cellco's existing t-arm antenna mounts.
2. The proposed modifications will not involve any change to ground-mounted equipment and, therefore, will not require the extension of the site boundary.
3. The proposed modifications will not increase noise levels at the facility by six decibels or more, or to levels that exceed state and local criteria.
4. The installation of Cellco's new antennas will not increase radio frequency (RF) emissions at the facility to a level at or above the Federal Communications Commission (FCC) safety standard. A cumulative General Power Density table for Cellco's modified facility is included in Attachment 3. The modified facility will be capable of providing Cellco's 5G wireless service.
5. The proposed modifications will not cause a change or alteration in the physical or environmental characteristics of the site.
6. According to the attached Structural Analysis ("SA") and Mount Analysis ("MA"), the existing tower, tower foundation and antenna platform can support Cellco's proposed modifications. Copies of the SA and MA are included in Attachment 4.

A copy of the parcel map and Property owner information is included in Attachment 5. A Certificate of Mailing verifying that this filing was sent to municipal officials is included in Attachment 6.

For the foregoing reasons, Cellco respectfully submits that the proposed modifications to the above-referenced telecommunications facility constitutes an exempt modification under R.C.S.A. § 16-50j-72(b)(2).

Melanie A. Bachman, Esq.  
October 14, 2021  
Page 3

Sincerely,

A handwritten signature in black ink, appearing to read "Kenneth C. Baldwin". The signature is fluid and cursive, with a long horizontal stroke at the end.

Kenneth C. Baldwin

Enclosures

Copy to:

Amy St. Onge, Thompson First Selectman  
Tyra Penn-Gesek, Director of Planning and Development  
Karla Hanna

# **ATTACHMENT 1**

**DOCKET NO. 344** - MCF Communications bg, Inc. and } Connecticut  
Omnipoint Communications, Inc. application for a Certificate of }  
Environmental Compatibility and Public Need for the } Siting  
construction, maintenance and operation of a telecommunications }  
facility located at Rich Road, Thompson, Connecticut. } Council

January 10, 2008

### **Decision and Order**

Pursuant to the foregoing Findings of Fact and Opinion, the Connecticut Siting Council (Council) finds that the effects associated with the construction, operation, and maintenance of a telecommunications facility including effects on the natural environment; ecological integrity and balance; public health and safety; scenic, historic, and recreational values; forests and parks; air and water purity; and fish and wildlife are not disproportionate either alone or cumulatively with other effects when compared to need, are not in conflict with the policies of the State concerning such effects, and are not sufficient reason to deny the application and therefore directs that a Certificate of Environmental Compatibility and Public Need, as provided by General Statutes § 16-50k, be issued to MCF Communications bg, Inc. for the construction, maintenance and operation of a wireless telecommunications facility to be located on Rich Road in Thompson, Connecticut.

The facility shall be constructed, operated, and maintained substantially as specified in the Council's record in this matter, and subject to the following conditions:

1. The tower shall be designed and constructed as a monopole no taller than 150 feet above ground level to provide telecommunications services to both public and private entities. Panel antennas to be installed on the tower shall be flush-mounted or attached to the tower using T-arm mounts.
2. The Certificate Holder shall prepare a Development and Management (D&M) Plan for this site in compliance with Sections 16-50j-75 through 16-50j-77 of the Regulations of Connecticut State Agencies. The D&M Plan shall be served on the Town of Thompson and all parties and intervenors, as listed in the service list, and submitted to and approved by the Council prior to the commencement of facility construction and shall include:
  - a) a final site plan(s) of site development to include specifications for the tower, tower foundation, antenna mountings, equipment building, access road, and utility line;
  - b) construction plans for site clearing, water drainage, and erosion and sedimentation control consistent with the 2002 Connecticut Guidelines for Soil Erosion and Sediment Control, as amended.

3. The Certificate Holder shall, prior to the commencement of operation, provide the Council worst-case modeling of the electromagnetic radio frequency power density of all proposed entities' antennas at the closest point of uncontrolled access to the tower base, consistent with Federal Communications Commission, Office of Engineering and Technology, Bulletin No. 65, August 1997. The Certificate Holder shall ensure a recalculated report of the electromagnetic radio frequency power density be submitted to the Council in the event other carriers locate at this facility or if circumstances in operation cause a change in power density above the levels calculated and provided pursuant to this Decision and Order.
4. Upon the establishment of any new state or federal radio frequency standards applicable to frequencies of this facility, the facility granted herein shall be brought into compliance with such standards.
5. The Certificate Holder shall permit public or private entities to share space on the proposed tower for fair consideration, or shall provide any requesting entity with specific legal, technical, environmental, or economic reasons precluding such tower sharing.
6. The Certificate Holder shall provide reasonable space on the tower for no compensation for any Town of Thompson public safety services (police, fire and medical services), provided such use can be accommodated and is compatible with the structural integrity of the tower.
7. Unless otherwise approved by the Council, if the facility authorized herein is not fully constructed and providing wireless services within eighteen months from the date of the mailing of the Council's Findings of Fact, Opinion, and Decision and Order (collectively called "Final Decision"), this Decision and Order shall be void, and the Certificate Holder shall dismantle the tower and remove all associated equipment or reapply for any continued or new use to the Council before any such use is made. The time between the filing and resolution of any appeals of the Council's Final Decision shall not be counted in calculating this deadline.
8. Any request for extension of the time period referred to in Condition 7 shall be filed with the Council not later than 60 days prior to the expiration date of this Certificate and shall be served on all parties and intervenors, as listed in the service list, and the Town of Thompson. Any proposed modifications to this Decision and Order shall likewise be so served.
9. If the facility ceases to provide wireless services for a period of one year, this Decision and Order shall be void, and the Certificate Holder shall dismantle the tower and remove all associated equipment or reapply for any continued or new use to the Council before any such use is made.
10. The Certificate Holder shall remove any nonfunctioning antenna, and associated antenna mounting equipment, within 60 days of the date the antenna ceased to function.

11. In accordance with Section 16-50j-77 of the Regulations of Connecticut State Agencies, the Certificate Holder shall provide the Council with written notice two weeks prior to the commencement of construction activities. In addition, the Certificate Holder shall provide the Council with written notice of the completion of site construction and the commencement of site operation.

Pursuant to General Statutes § 16-50p, we hereby direct that a copy of the Findings of Fact, Opinion, and Decision and Order be served on each person listed below, and notice of issuance shall be published in The Norwich Bulletin and The Thompson Villager.

By this Decision and Order, the Council disposes of the legal rights, duties, and privileges of each party named or admitted to the proceeding in accordance with Section 16-50j-17 of the Regulations of Connecticut State Agencies.

The parties and intervenors in this proceeding are:

<b>Status Granted</b>	<b>Status Holder (name, address &amp; phone number)</b>	<b>Representative (name, address &amp; phone number)</b>
<b>Applicant</b>	MCF Communications bg, Inc. and Omnipoint Communications, Inc.	Julie Kohler, Esq. Carrie Larson, Esq. Cohen and Wolf, P.C 1115 Broad Street Bridgeport, CT 06604 Tel: 203-368-0211 Fax: 203-394-9901 <a href="mailto:JKohler@cohenandwolf.com">JKohler@cohenandwolf.com</a> <a href="mailto:Clarson@cohenandwolf.com">Clarson@cohenandwolf.com</a>
<b>Intervenor Approved 08/29/07</b>	Cellco Partnership d/b/a Verizon Wireless	Kenneth C. Baldwin, Esq. Robinson & Cole LLP 280 Trumbull Street Hartford, CT 06103-3597 (860) 275-8200

# **ATTACHMENT 2**



# verizon

## THOMPSON\_NORTH\_CT

44 RICH ROAD  
 NORTH GROSVENORDALE, CT 06277  
 SBA SITE I.D.#: CT11559-A  
 LOCATION CODE (PSLC): 535838  
 FUZE ID: 16244622  
 EQUIPMENT UPGRADE PROJECT  
 RFDS DATE: 06/23/21


### PROJECT SUMMARY

SCOPE OF WORK: EXISTING TELECOMMUNICATIONS FACILITY EQUIPMENT ALTERATION  
 SITE NAME: THOMPSON\_NORTH\_CT  
 LOCATION CODE (PSLC): 535838  
 FUZE PROJECT ID: 16244622  
 SITE ADDRESS: 44 RICH ROAD  
 NORTH GROSVENORDALE, CT 06277  
 LATITUDE: 42.0115 N (RFDS)  
 LONGITUDE: -71.852028 W (RFDS)  
 FACILITY: SBA MONOPOLE  
 SITE I.D.#: CT11559-A  
 APPLICANT, LESSEE/LICENSEE, PROJECT OWNER: CELCOO PARTNERSHIP  
 d/b/a VERIZON WIRELESS  
 118 FLANDERS ROAD  
 THIRD FLOOR  
 WESTBOROUGH, MA 01581  
 SITE ENGINEER: PROTERRA DESIGN GROUP, LLC  
 4 BAY ROAD  
 BUILDING A, SUITE 200  
 HADLEY, MA 01035

### SHEET INDEX

SHT. NO.	DESCRIPTION	REV. NO.
T-1	TITLE SHEET	1
A-1	COMPOUND PLAN & ELEVATION	1
A-2	EXISTING AND PROPOSED ANTENNA PLAN	1
D-1	DETAIL	1
X-1	ANTENNA LAYOUT RENDERINGS (BY OTHERS)	1

### LOCATION MAP



### GENERAL NOTES

1. VERIFY COAX CONFIGURATION, ANTENNA CONFIGURATION, AND ANTENNA HEIGHT WITH LATEST RF DATA SHEET PRIOR TO INSTALLATION.
2. THE CONTRACTOR SHALL SCHEDULE AND SEQUENCE ALL REQUIRED WORK WITH THE OWNER'S REPRESENTATIVE AND CONSTRUCTION MANAGER.
3. REPAIR ANY DAMAGE DURING CONSTRUCTION TO MATCH EXISTING PRE-CONSTRUCTION CONDITIONS TO THE SATISFACTION OF THE CONSTRUCTION MANAGER
4. THE CONTRACTOR SHALL SUPERVISE AND DIRECT THE PROJECT DESCRIBED HEREIN. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES AND PROCEDURES FOR THE WORK.
5. ANTENNAS TO BE INSTALLED PER MANUFACTURER'S RECOMMENDATIONS, GLOBAL STRUCTURAL ANALYSIS, AND LOCAL ANTENNA MOUNT ANALYSIS INCLUDING ANTENNA MOUNT MODIFICATIONS AND STRUCTURAL AUGMENTS AS APPLICABLE.
6. REPLACE AND/OR REUSE (E) MOUNTING HARDWARE, INSPECT FOR DAMAGE, AND REPLACE AS NECESSARY TO THE SATISFACTION OF THE ENGINEER.
7. EQUIPMENT LOCATIONS AND CONDITIONS TO BE FIELD VERIFIED PRIOR TO COMMENCEMENT OF CONSTRUCTION. ENGINEER SHALL BE NOTIFIED OF ANY DISCREPANCIES OR BE RESPONSIBLE FOR THE SAME.
8. NORTH SHOWN IS APPROXIMATE, NOT ALL (E) OR (P) IMPROVEMENTS REQUIRED MAY BE SHOWN FOR CLARITY.
9. ANTENNA ELEVATIONS SHALL BE PER ZONING OR AS APPROVALS DICTATE.
10. THESE CONSTRUCTION DRAWINGS ARE CONTINGENT UPON A PASSING GLOBAL STRUCTURAL ANALYSIS INCLUDING THE INSTALLATION OF ANY REQUIRED MODIFICATIONS AND INSPECTION REPORTS AS A RESULT THEREIN.

### STRUCTURAL NOTES

GLOBAL TOWER STRUCTURAL ANALYSIS REPORT:  
**PASSING REPORT** - NO MODIFICATIONS REQUIRED BY TOWER ENGINEERING SOLUTIONS DATED 08/18/21.  
 LOCAL ANTENNA MOUNT ANALYSIS REPORT:  
**PASSING REPORT** - NO MODIFICATIONS REQUIRED BY MASER CONSULTING DATED 07/02/21.

### CONTRACTOR MOUNT POST MODIFICATION INSPECTION (PMI) REPORT REQUIREMENTS


PMI ONLINE ACCESS: <https://pmi.vzwsmart.com>  
 SMART TOOL VENDOR PROJECT NUMBER: 10081940  
 VZW LOCATION CODE (PSLC): 535838  
 \*\*\* PMI AND REQUIREMENTS ALSO EMBEDDED IN ANTENNA MOUNT ANALYSIS REPORT BY MASER CONSULTING DATED 07/02/21.  
 MOUNT MODIFICATIONS REQUIRED (Y/N): NO  
 VZW APPROVED SMART KIT VENDORS  
 REFER TO MOUNT MODIFICATION DRAWINGS PAGE FOR VZW SMART KIT APPROVED VENDORS



PREPARED BY:  
**ProTerra**  
 DESIGN GROUP, LLC  
 4 Bay Road, Bldg A  
 Suite 200  
 Hadley, MA 01035  
 Ph: (413)320-4918

### REVISIONS


REV#	DATE	DESCRIPTION	BY	CHK APP'D
0	07/09/21	PER RFDS DATED 06/23/21	TBO	JWS
1	08/27/21	PER RFDS DATED 08/23/21	TBO	JWS




THOMPSON NORTH CT  
 44 RICH ROAD  
 NORTH GROSVENORDALE,  
 CT 06277  
 FUZE PROJECT ID: 16244622  
 SBA SITE I.D.#: CT11559-A

**T-1**


Jesse Moreno, PE  
 Digitally signed by Jesse Moreno, PE  
 Date: 2021.08.27 13:09:52 -0400



**COMPOUND PLAN**  
SCALE: 1"=20' (11x17)



NOTE: AGL ELEVATIONS SHOWN HEREON FOR GENERAL REFERENCE ONLY, REFER TO LOCAL ANTENNA MOUNT ANALYSIS BY MASER CONSULTING AND SHEET X-1 FOR REQUIRED EQUIPMENT MOUNTING CONFIGURATION INCLUDING VERTICAL AND HORIZONTAL MOUNTING LOCATIONS LISTED IN TABLES. COORDINATE EQUIPMENT LOCATIONS AND ANY CONFLICTS WITH MASER CONSULTING.




**SOUTHWEST ELEVATION**  
SCALE: 1"=25' (11x17)



PREPARED BY:  
**ProTerra**  
DESIGN GROUP, LLC  
4 Bay Road, Bldg A  
Suite 200  
Hesley, MA 01035  
Ph: (413)320-4918

**REVISIONS**

REV.	DATE	DESCRIPTION	BY	CHK APP'D
0	07/09/21	PER RFDS DATED 06/23/21	TBO JWS	JAM
1	08/27/21	PER RFDS DATED 08/23/21	TBO JWS	JAM



THOMPSON NORTH, CT  
44 RICH ROAD  
NORTH GROSVEENORDALE,  
CT 06277  
FUZE PROJECT ID: 1624622  
SBA SITE ID: CT115994A

**A-1**


PREPARED BY:

REV	DATE	DESCRIPTION	BY	CHK APP'D
0	07/09/21	PER RFDS DATED 06/23/21	TBD JWS	JAM
1	08/27/21	PER RFDS DATED 08/23/21	TBD JWS	JAM




THOMPSON NORTH, CT  
44 RICH ROAD  
NORTH GROSVENORDALE,  
CT 06277  
FUZE PROJECT ID: 1624622  
SBA SITE ID: CT115994A

NOTE: AGL ELEVATIONS SHOWN HEREON FOR GENERAL REFERENCE ONLY, REFER TO LOCAL ANTENNA MOUNT ANALYSIS BY MASER CONSULTING AND SHEET X-1 FOR REQUIRED EQUIPMENT MOUNTING CONFIGURATION INCLUDING VERTICAL AND HORIZONTAL MOUNTING LOCATIONS LISTED IN TABLES. COORDINATE EQUIPMENT LOCATIONS AND ANY CONFLICTS WITH MASER CONSULTING.




**COMPOUND PLAN**  
SCALE: 1"=20' (11x17)

A GLOBAL TOWER STRUCTURAL ANALYSIS SHALL BE COMPLETED BY OTHERS PRIOR TO CONSTRUCTION TO CONFIRM CAPACITY.




**SOUTHWEST ELEVATION**  
SCALE: 1"=25' (11x17)

A GLOBAL TOWER STRUCTURAL ANALYSIS SHALL BE COMPLETED BY OTHERS PRIOR TO CONSTRUCTION TO CONFIRM CAPACITY.



**(E) ANTENNA PLAN**  
SCALE: 1"=4'  
1  
A-2



**(P) ANTENNA PLAN**  
SCALE: 1"=4'  
2  
A-2

NOTE: AT TIME OF PUBLICATION, THE DESIGN OF THE VERIZON MT6407-77A ANTENNA WAS NOT FINALIZED. BASED UPON DIRECTIVE BY VERIZON WIRELESS, FOR DESIGN PURPOSES THE PROPOSED EQUIPMENT HAS BEEN CONSIDERED TO BE A MAXIMUM SIZE NOT TO EXCEED 35.1"±H x 16.1"±W x 5.6"±D AND WEIGH APPROXIMATELY 87.1±LBS. IF ANY OF THESE PARAMETERS ARE EXCEEDED BY THE EQUIPMENT THE ENGINEER(S) SHALL BE NOTIFIED TO REVISE THE DRAWINGS, STRUCTURAL ANALYSIS, AND MOUNT ANALYSIS.



118 FLANDERS ROAD  
THIRD FLOOR  
WESTBOROUGH, MA 01581




4 Bay Road, Bldg A  
Suite 200  
Hedley, MA 01035  
Ph: (413)320-4918


PREPARED BY:

REV.	DATE	DESCRIPTION	CHK APP'D
0	07/09/21	PER REFS DATED 06/23/21	TBD JWS -JAM
1	08/27/21	PER REFS DATED 08/23/21	TBD JWS -JAM

**REVISIONS**



THOMPSON NORTH, CT  
44 RICH ROAD  
NORTH GROSVENORDALE,  
CT 06277  
FUZE PROJECT#R: 1624622  
SBA SITE ID#R: CT115994A




AWS 2100 LTE AND PCS 1900 LTE (B2/B66A RRH) DUAL-BAND RRH 97.5 lbs

**(P) AWS/PCS RRH MOUNTING DETAIL**

SCALE: NONE


1  
D-1



**(P) LARGE JUNCTION BOX MOUNTING DETAIL**

SCALE: NONE

3  
D-1



700 LTE AND 850 LTE (B5/B13 RRH) DUAL-BAND RRH 82.0 lbs

**(P) 700/850 RRH MOUNTING DETAIL**

SCALE: NONE

2  
D-1

**INSTALLATION NOTES:**

1. INSTALL ALL EQUIPMENT, MOUNTING BRACKETS, AND HARDWARE IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
2. GROUND DISTRIBUTION BOXES, MOUNTING PIPES, AND RRHS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
3. INSTALL EQUIPMENT AND MOUNTING BRACKETS TO PRESERVE CLIMBING ACCESS ON TOWER.
4. EQUIPMENT TO BE INSTALLED AT VERIZON RAD. CENTER IN ACCORDANCE WITH GLOBAL TOWER STRUCTURAL ANALYSIS AND MOUNT ANALYSIS (BY OTHERS).



118 FLANDERS ROAD  
THIRD FLOOR  
WESTBOROUGH, MA 01581




4 Bay Road, Bldg A  
Suite 200  
Hesley, MA 01035  
Ph: (413)320-4918

PREPARED BY:

REV	DATE	DESCRIPTION	CHK APP'D
0	07/09/21	PER RFD'S DATED 06/23/21	TBD JWS / JMK
1	08/27/21	PER RFD'S DATED 08/23/21	TBD JWS / JMK

**REVISIONS**





THOMPSON NORTH, CT  
44 RICH ROAD  
NORTH GROSVENORDALE,  
CT 06277  
FUZE PROJECT ID: 1024622  
SBA SITE ID: CT115994A

**D-1**

# ANTENNA LAYOUT SCHEMATIC RENDERINGS SHOWN HEREON PROVIDED BY OTHERS



REFER TO ANTENNA MOUNT ANALYSIS REPORT BY MASER CONSULTING DATED 07/02/21



TOP ANTENNA PIPE WORK POINT, TYP. ↑  
C.Ant. Frm.T\* ↓  
EQUIPMENT, TYP. ↓

\*NOTE: SEE TABLE BELOW AND IN MOUNT ANALYSIS FOR DISTANCE REQUIRED. COORDINATE EQUIPMENT LOCATIONS AND ANY MOUNTING CONFLICTS WITH MASER CONSULTING.



ALPHA



TOP ANTENNA PIPE WORK POINT, TYP. ↑  
C.Ant. Frm.T\* ↓  
EQUIPMENT, TYP. ↓

\*NOTE: SEE TABLE BELOW AND IN MOUNT ANALYSIS FOR DISTANCE REQUIRED. COORDINATE EQUIPMENT LOCATIONS AND ANY MOUNTING CONFLICTS WITH MASER CONSULTING.

BETA



TOP ANTENNA PIPE WORK POINT, TYP. ↑  
C.Ant. Frm.T\* ↓  
EQUIPMENT, TYP. ↓

\*NOTE: SEE TABLE BELOW AND IN MOUNT ANALYSIS FOR DISTANCE REQUIRED. COORDINATE EQUIPMENT LOCATIONS AND ANY MOUNTING CONFLICTS WITH MASER CONSULTING.

GAMMA

ALPHA

Ref#	Model	Height (in)	Width (in)	H Dist Frm L	Pipe #	Pipe Pos V	Ant Pos	C. Ant Frm T	Ant H Off	Status	Validation
A1	MX06FRO869-03	71.3	15.4	87.5	2	a	Front	36	8	Added	
A1	MX06FRO869-03	71.3	15.4	87.5	2	b	Front	36	-8	Added	
R5	B5/B13 RRH-BR04C	15	15	87.5	2	a	Behind	18	0	Added	
R2	MT6407-77A	35.1	16.1	48.5	3	a	Front	36	0	Added	
R4	B2/B66A RRH-BR049	15	15	48.5	3	a	Behind	18	0	Added	
A8	CHB826-43-2X	7.1	14.6	48.5	3	a	Behind	48	0	Added	

BETA

Ref#	Model	Height (in)	Width (in)	H Dist Frm L	Pipe #	Pipe Pos V	Ant Pos	C. Ant Frm T	Ant H Off	Status	Validation
A1	MX06FRO869-03	71.3	15.4	87.5	2	a	Front	36	8	Added	
A1	MX06FRO869-03	71.3	15.4	87.5	2	b	Front	36	-8	Added	
R5	B5/B13 RRH-BR04C	15	15	87.5	2	a	Behind	18	0	Added	
R2	MT6407-77A	35.1	16.1	48.5	3	a	Front	36	0	Added	
R4	B2/B66A RRH-BR049	15	15	48.5	3	a	Behind	18	0	Added	
A8	CHB826-43-2X	7.1	14.6	48.5	3	a	Behind	48	0	Added	

GAMMA

Ref#	Model	Height (in)	Width (in)	H Dist Frm L	Pipe #	Pipe Pos V	Ant Pos	C. Ant Frm T	Ant H Off	Status	Validation
A1	MX06FRO869-03	71.3	15.4	87.5	2	a	Front	36	8	Added	
A1	MX06FRO869-03	71.3	15.4	87.5	2	b	Front	36	-8	Added	
R5	B5/B13 RRH-BR04C	15	15	87.5	2	a	Behind	18	0	Added	
R2	MT6407-77A	35.1	16.1	48.5	3	a	Front	36	0	Added	
R4	B2/B66A RRH-BR049	15	15	48.5	3	a	Behind	18	0	Added	
A8	CHB826-43-2X	7.1	14.6	48.5	3	a	Behind	48	0	Added	

## CONTRACTOR MOUNT POST MODIFICATION INSPECTION (PMI) REPORT REQUIREMENTS

PMI ONLINE ACCESS: <https://pmi.vzwsmart.com>

SMART TOOL VENDOR PROJECT NUMBER: 10081940

V2W LOCATION CODE (PSLC): 535838

\*\*\* PMI AND REQUIREMENTS ALSO EMBEDDED IN ANTENNA MOUNT ANALYSIS REPORT BY MASER CONSULTING DATED 07/02/21.

MOUNT MODIFICATIONS REQUIRED (Y/N): NO

V2W APPROVED SMART KIT VENDORS

REFER TO MOUNT MODIFICATION DRAWINGS PAGE FOR V2W SMART KIT APPROVED VENDORS



PREPARED BY: ProTerra DESIGN GROUP, LLC

REV	DATE	DESCRIPTION	BY	CHK APP'D
0	07/09/21	PER REFS DATED 06/23/21	TBD	JWS / JMM
1	08/27/21	PER REFS DATED 08/23/21	TBD	JWS / JMM

RENDERINGS BY: MASER CONSULTING  
 MT, LAUREL OFFICE  
 2000 MIDLAND DRIVE - SUITE 100  
 MOUNT LAUREL, NJ 08054  
 Phone: 85627970412

THOMPSON NORTH, CT  
 44 RICH ROAD  
 NORTH GROSVENORDALE, CT 06277  
 FUZE PROJECT ID: 1624622  
 SBA SITE ID: CT115994A

X-1


# MX06FRO660-03

## NWAV™ X-Pol Hex-Port Antenna

**X-Pol Hex-Port 6 ft 60° Fast Roll Off antenna with independent tilt on 700 & 850 MHz:**

**2 ports 698-798, 824-894 MHz and 4 ports 1695-2180 MHz**

- Fast Roll Off (FRO™) azimuth beam pattern improves Intra- and Inter-cell SINR
- Compatible with dual band 700/850 MHz radios with independent low band EDT without external diplexers
- Fully integrated (iRETs) with independent RET control for low and high bands for ease of network optimization
- SON-Ready array spacing supports beamforming capabilities
- Suitable for LTE/CDMA/PCS/UMTS/GSM air interface technologies
- Integrated Smart Bias-Ts reduce leasing costs



NWAV™

### Fast Roll-Off antennas increase data throughput without compromising coverage


The horizontal beam produced by Fast Roll-Off (FRO) technology increases the Signal to Interference & Noise Ratio (SINR) by eliminating overlap between sectors.

#### Non-FRO antenna

Large traditional antenna pattern overlap creates harmful interference.


JMA's FRO antenna pattern minimizes overlap, thereby minimizing interference.

#### JMA FRO antenna



LTE throughput	SINR	Speed (bps/Hz)	Speed increase	CQI
Excellent	>18	>4.5	333+%	8-10
Good	15-18	3.3-4.5	277%	6-7
Fair	10-15	2-3.3	160%	4-6
Poor	<10	<2	0%	1-3


The LTE radio automatically selects the best throughput based on measured SINR.



Electrical specification (minimum/maximum)	Ports 1, 2		Ports 3, 4, 5, 6		
	Frequency bands, MHz	698-798	824-894	1695-1880	1850-1990
Polarization	± 45°		± 45°		
Average gain over all tilts, dBi	14.4	14.0	17.6	18.0	18.2
Horizontal beamwidth (HBW), degrees	60.5	53.0	55.0	55.0	55.5
Front-to-back ratio, co-polar power @180°± 30°, dB	>24	>24.0	>25.0	>25.0	>25.0
X-Pol discrimination (CPR) at boresight, dB	>15.0	>14.2	>18	>18	>15
Sector power ratio, percent	<3.5	<3.0	<3.7	<3.8	<3.6
Vertical beamwidth (VBW), degrees <sup>1</sup>	13.1	11.8	6.0	5.5	5.5
Electrical downtilt (EDT) range, degrees	2-14	2-14	0-9		
First upper side lobe (USLS) suppression, dB <sup>1</sup>	≤-15.0	≤-16.5	≤-16.0	≤-16.0	≤-16.0
Cross-polar isolation, port-to-port, dB <sup>1</sup>	25	25	25	25	25
Max VSWR / return loss, dB	1.5:1 / -14.0		1.5:1 / -14.0		
Max passive intermodulation (PIM), 2x20W carrier, dBc	-153		-153		
Max input power per any port, watts	300		250		
Total composite power all ports, watts	1500				

<sup>1</sup> Typical value over frequency and tilt

Mechanical specifications	
Dimensions height/width/depth, inches (mm)	71.3/ 15.4/ 10.7 (1811/ 392/ 273)
Shipping dimensions length/width/height, inches (mm)	82/ 20/ 15 (2083/ 508/ 381)
No. of RF input ports, connector type, and location	6 x 4.3-10 female, bottom
RF connector torque	96 lbf-in (10.85 N·m or 8 lbf-ft)
Net antenna weight, lb (kg)	60 (27.0)
Shipping weight, lb (kg)	90 (41.0)
Antenna mounting and downtilt kit included with antenna	91900318
Net weight of the mounting and downtilt kit, lb (kg)	18 (8.18)
Range of mechanical up/down tilt	-2° to 14°
Rated wind survival speed, mph (km/h)	150 (241)
Frontal, lateral, and rear wind loading @ 150 km/h, lbf (N)	154 (685), 73 (325), 158 (703)
Equivalent flat plate @ 100 mph and Cd=2, sq ft	2.6



Ordering information	
Antenna model	Description
MX06FRO660-03	6F X-Pol HEX FRO 60° independent tilt 700/850 RET, 4.3-10 & SBT
Optional accessories	
<a href="#">AISG cables</a>	M/F cables for AISG connections
<a href="#">PCU-1000 RET controller</a>	Stand-alone controller for RET control and configurations




Remote electrical tilt (RET 1000) information	
RET location	Integrated into antenna
RET interface connector type	8-pin AISG connector per IEC 60130-9
RET connector torque	Min 0.5 N·m to max 1.0 N·m (hand pressure & finger tight)
RET interface connector quantity	2 pairs of AISG male/female connectors
RET interface connector location	Bottom of the antenna
Total no. of internal RETs (low bands)	2
Total no. of internal RETs (high bands)	1
RET input operating voltage, vdc	10-30
RET max power consumption, idle state, W	≤ 2.0
RET max power consumption, normal operating conditions, W	≤ 13.0
RET communication protocol	AISG 2.0 / 3GPP

### RET and RF connector topology

Each RET device can be controlled either via the designated external AISG connector or RF port as shown below:

RET device	Band	RF port
R1	698-798	1-2
R2	824-894	1-2

RET device	Band	RF port
B1/B2	1695-2180	3-6



### Array topology

3 sets of radiating arrays R1/R2: 698-894 MHz B1: 1695-2180 MHz B2: 1695-2180 MHz	<table border="1"> <thead> <tr> <th>Band</th> <th>RF port</th> </tr> </thead> <tbody> <tr> <td>1695-2180</td> <td>3-4</td> </tr> <tr> <td>698-894</td> <td>1-2</td> </tr> <tr> <td>1695-2180</td> <td>5-6</td> </tr> </tbody> </table>	Band	RF port	1695-2180	3-4	698-894	1-2	1695-2180	5-6	
	Band	RF port								
1695-2180	3-4									
698-894	1-2									
1695-2180	5-6									

# SAMSUNG

## Dual-Band Radio Unit 700/850MHz (B13/B5) RFV01U-D2A

Samsung's RFV01U-D2A is a compact remote Radio Unit (RU) designed for deployments that require flexibility in installation and rapid onlining, without compromising on coverage, capacity or operational expenses.



The RFV01U-D2A RU targets dual-band support across Band 13 (700MHz) and Band 5 (850MHz), making it an ideal product for broad coverage footprints across multiple common low-end, long-range frequencies.

The RU handles all Radio Frequency (RF) processing in a single, compact unit, and is designed to interface via CPRI with Samsung's CDU baseband offerings, in both distributed- and central-RAN configurations.

In addition to its minimal footprint and ease of installation, the RU is also designed to reduce cost of ownership through its integrated spectrum analyzer, which allows for remote RF monitoring, greatly reducing the need for on-site maintenance visits.

### Features and Benefits

- Dual-band support for broad frequency coverage
- Minimal footprint reduces site costs
- Rapid, easy installation
- Flexibly deployable in any location
- Remote RF monitoring capability
- Convection cooled, silent operation

### Key Technical Specifications


Duplex Type: FDD  
Operating Frequencies:  
B13: DL(746-756MHz)/UL(777-787MHz)  
B5: DL(869-894MHz)/UL(824-849MHz)  
Instantaneous Bandwidth: 10MHz(B13) + 25MHz(B5)  
RF Chain: 4T4R/2T4R/2T2R  
Output Power: Total 320W  
DU-RU Interface: CPRI (10Gbps)  
Dimensions: 380 x 380 x 207mm (29.9L)  
Weight: 31.9kg  
Input Power: -48V DC  
Operating Temp.: -40 - 55°(w/o solar load)  
Cooling: Natural convection

## **SAMSUNG** C-Band 64T64R Massive MIMO Radio

for High Capacity and Wide Coverage

Samsung C-Band 64T64R Massive MIMO Radio enables mobile operators to increase coverage range, boost data speeds and ultimately offer enriched 5G experiences to users in the U.S..

Model Code : MT6407-77A




## Points of Differentiation

### Wide Bandwidth

With capability to support up to 2 CC carrier configuration, Samsung C-Band massive MIMO Radio supports 200 MHz bandwidth in the C-Band spectrum.

Samsung C-Band massive MIMO Radio covers the entire C-Band 280 MHz spectrum, so it can meet the operator's needs in current A block and future B/C blocks


C-Band spectrum supported by Massive MIMO Radio



### Future Proof Product

Samsung C-Band 64T64R Massive MIMO radio supports not only CPRI but also eCPRI as front-haul interface.

It enables operators can cut down on OPEX/CAPEX by reducing front-haul bandwidth through low layer split and using ethernet based higher efficient line.




### Enhanced Performance

C-Band massive MIMO Radio creates sharp beams and extends networks' coverage on the critical mid-band spectrum using a large number of antenna elements and high output power to boost data speeds.

This helps operators reduce their CAPEX as they now need less products to cover the same area than before.


Furthermore, as C-Band massive MIMO Radio supports MU-MIMO (Multi-user MIMO), it enables to increase user throughput by minimizing interference.



### Well Matched Design

Samsung C-Band Massive MIMO radio utilizes 64 antennas, supports up to 280MHz bandwidth, and delivers a 200W output power. despite the above advanced performance, the Radio has a compact size of 50.9L and 79.4lbs. This makes it easy to install the Radio.

It is designed to look solid and compact, with a low profile appearance so that, when installed, harmonizes well with the surrounding environment.



## Technical Specifications

Item	Specification
Tech	NR
Band	n77
Frequency Band	3700 - 3980 MHz
EIRP	78.5dBm (53.0 dBm+25.5 dBi)
IBW/OBW	280 MHz / 200 MHz
Installation	Pole/Wall
Size/Weight	16.06 x 35.06 x 5.51 inch (50.86L) / 79.4 lbs



# SAMSUNG



## **About Samsung Electronics Co., Ltd.**

Samsung inspires the world and shapes the future with transformative ideas and technologies. The company is redefining the worlds of TVs, smartphones, wearable devices, tablets, digital appliances, network systems, and memory, system LSI, foundry and LED solutions.

129 Samsung-ro, Yeongtong-gu, Suwon-si Gyeonggi-do, Korea

## **© 2021 Samsung Electronics Co., Ltd.**

All rights reserved. Information in this leaflet is proprietary to Samsung Electronics Co., Ltd. and is subject to change without notice. No information contained here may be copied, translated, transcribed or duplicated by any form without the prior written consent of Samsung Electronics.

# SAMSUNG

## Dual-Band Radio Unit AWS/PCS (B66/B2)

RFV01U-D1A

Samsung's RFV01U-D1A is a compact remote Radio Unit (RU) designed for deployments that require flexibility in installation and rapid onlining, without compromising on coverage, capacity or operational expenses.



The RFV01U-D1A RU targets dual-band support across Band 66 (AWS) and Band 2 (PCS), making it an ideal product for broad coverage footprints across multiple common mid-range frequencies.

The RU handles all Radio Frequency (RF) processing in a single, compact unit, and is designed to interface via CPRI with Samsung's CDU baseband offerings, in both distributed- and central-RAN configurations.

In addition to its minimal footprint and ease of installation, the RU is also designed to reduce cost of ownership through its integrated spectrum analyzer, which allows for remote RF monitoring, greatly reducing the need for on-site maintenance visits.

### Features and Benefits

- Dual-band support for broad frequency coverage
- Minimal footprint reduces site costs
- Rapid, easy installation
- Flexibly deployable in any location
- Remote RF monitoring capability
- Convection cooled, silent operation
- Built-in Broadcast Auxiliary Services (BAS) filter ensures compliant AWS operation without impacting footprint

### Key Technical Specifications

Duplex Type: FDD

Operating Frequencies:

B66: DL(2,110-2,180MHz)/UL(1,710-1,780MHz)

B2: DL(1,930-1,990MHz)/UL(1,850-1,910MHz)

Instantaneous Bandwidth:

70MHz(B66) + 60MHz(B2)

RF Chain: 4T4R/2T4R/2T2R

Output Power: Total 320W

DU-RU Interface: CPRI (10Gbps)

Dimensions: 380 x 380 x 255mm (36.8L)

Weight: 38.3kg

Input Power: -48V DC

Operating Temp.: -40 - 55°(w/o solar load)

Cooling: Natural convection

# **ATTACHMENT 3**

	General	Power	Density					
<b>Site Name: Thompson N</b>								
<b>Tower Height: Verizon @ 137ft</b>								
CARRIER	# OF CHAN.	WATTS ERP	HEIGHT	FREQ.	CALC. POWER DENS	MAX. PERMISS. EXP.	FRACTION MPE	Total
*T-Mobile	1	1556	148.7	1900	0.0275	1.0000	0.27%	
*T-Mobile	1	584	148.7	1900	0.0103	1.0000	0.10%	
*T-Mobile	1	1014	148.7	2100	0.0179	1.0000	0.18%	
*T-Mobile	2	2334	148.7	2100	0.0824	1.0000	0.82%	
*T-Mobile	2	789	148.7	600	0.0279	0.4000	0.70%	
*T-Mobile	2	433	148.7	700	0.0153	0.4667	0.33%	
*AT&T-UMTS	1	308	127	850	0.0076	0.5667	0.13%	
*AT&T-UMTS	1	1000	127	850	0.0246	0.5667	0.43%	
*AT&T-UMTS	1	1000	127	850	0.0246	0.5667	0.43%	
*AT&T-PCS-UMTS	1	1476	127	700	0.0363	0.4667	0.78%	
*AT&T-GSM	1	2951	127	700	0.0725	0.4667	1.55%	
*AT&T-LTE	2	3664	127	1900	0.1800	1.0000	1.80%	
*AT&T-PCS-LTE	1	3837	127	2100	0.0942	1.0000	0.94%	
<b>VZW 700</b>	<b>4</b>	<b>609</b>	<b>137</b>	<b>751</b>	<b>0.0047</b>	<b>0.5007</b>	<b>0.93%</b>	
<b>VZW CDMA</b>	<b>2</b>	<b>326</b>	<b>137</b>	<b>877.26</b>	<b>0.0012</b>	<b>0.5848</b>	<b>0.21%</b>	
<b>VZW Cellular</b>	<b>4</b>	<b>623</b>	<b>137</b>	<b>874</b>	<b>0.0048</b>	<b>0.5827</b>	<b>0.82%</b>	
<b>VZW PCS</b>	<b>4</b>	<b>1428</b>	<b>137</b>	<b>1975</b>	<b>0.0109</b>	<b>1.0000</b>	<b>1.09%</b>	
<b>VZW AWS</b>	<b>4</b>	<b>1530</b>	<b>137</b>	<b>2120</b>	<b>0.0117</b>	<b>1.0000</b>	<b>1.17%</b>	
<b>VZW CBAND</b>	<b>4</b>	<b>6531</b>	<b>137</b>	<b>3730.08</b>	<b>0.0501</b>	<b>1.0000</b>	<b>5.01%</b>	
								<b>17.70%</b>
* Source: Siting Council								



# **ATTACHMENT 4**



**Tower Engineering Solutions**

Phone (972) 483-0607, Fax (972) 975-9615  
1320 Greenway Drive, Suite 600, Irving, Texas 75038

---

**Structural Analysis Report**

**Existing 149 ft Nudd Corporation Monopole**

**Customer Name: SBA Communications Corp**

**Customer Site Number: CT11559-A**

**Customer Site Name: Thompson 1, CT**

**Carrier Name: Verizon (App#: 154487, V3)**

**Carrier Site ID / Name: 171757 / Thompson North CT**

**Site Location: 39 Rich Road**

**North Grosvenordale, Connecticut**

**Windham County**

**Latitude: 42.011550**

**Longitude: -71.851908**

**Analysis Result:**

**Max Structural Usage: 61.4% [Pass]**

**Max Foundation Usage: 67.0% [Pass]**

**Additional Usage Caused by Mount Modification: +0.0%**



**Report Prepared By: Younus Alkarawi**



**Tower Engineering Solutions**

Phone (972) 483-0607, Fax (972) 975-9615  
1320 Greenway Drive, Suite 600, Irving, Texas 75038

---

## **Structural Analysis Report**

**Existing 149 ft Nudd Corporation Monopole**

**Customer Name: SBA Communications Corp**

**Customer Site Number: CT11559-A**

**Customer Site Name: Thompson 1, CT**

**Carrier Name: Verizon (App#: 154487, V3)**

**Carrier Site ID / Name: 171757 / Thompson North CT**

**Site Location: 39 Rich Road**

**North Grosvenordale, Connecticut**

**Windham County**

**Latitude: 42.011550**

**Longitude: -71.851908**

### **Analysis Result:**

**Max Structural Usage: 61.4% [Pass]**

**Max Foundation Usage: 67.0% [Pass]**

**Additional Usage Caused by Mount Modification:**

**Report Prepared By: Younus Alkarawi**

## Introduction

The purpose of this report is to summarize the analysis results on the 149 ft Nudd Corporation Monopole to support the proposed antennas and transmission lines in addition to those currently installed. Any modification listed under Sources of Information was assumed completed and was included in this analysis.

## Sources of Information

<b>Tower Drawings</b>	Fred A. Nudd Corporation (Project No. 308-13019) original design drawings dated April 25, 2008.
<b>Foundation Drawing</b>	Fred A. Nudd Corporation (Project No. 308-13019) original design drawings dated April 25, 2008.
<b>Geotechnical Report</b>	
<b>Modification Drawings</b>	
<b>Mount Analysis</b>	Verizon MA by Maser Consulting Connecticut Project #: 21777328A (REV 1), dated

## Analysis Criteria

The rigorous analysis was performed in accordance with the requirements and stipulations of the TIA- In accordance with this standard, the structure was analyzed using **TESPoles**, a proprietary analysis software. The program considers the structure as an elastic 3-D model with second-order effects and temperature effects incorporated in the analysis. The analysis was performed using multiple wind directions.

<b>Wind Speed Used in the Analysis:</b>	Ultimate Design Wind Speed $V_{ult} = 130.0$ mph (3-Sec. Gust)/ Nominal Design Wind Speed $V_{asd} = 101.0$ mph (3-Sec. Gust)
<b>Wind Speed with Ice:</b>	50 mph (3-Sec. Gust) with 1" radial ice concurrent
<b>Operational Wind Speed:</b>	60 mph + 0" Radial ice
<b>Standard/Codes:</b>	TIA-222-G-2 / 2015 IBC / 2018 Connecticut State Building Code
<b>Exposure Category:</b>	
<b>Structure Class:</b>	
<b>Topographic Category:</b>	
<b>Crest Height:</b>	0 ft
<b>Seismic Parameters:</b>	

This structural analysis is based upon the tower being classified as a Structure Class II; however, if a different classification is required subsequent to the date hereof, the tower classification will be changed to meet such requirement and a new structural analysis will be run.

## Existing Antennas, Mounts and Transmission Lines

The table below summarizes the antennas, mounts and transmission lines that were considered in the analysis as existing on the tower.

Items	Elevation (ft)	Qty.	Antenna Descriptions	Mount Type & Qty.	Transmission Lines	Owner
			Ericsson Air 21 B2A/B4P	(3)T-Arms w/ (1) Metrosite Heavy Collar Mount Assembly: MS-H1436 (1) Metrosite Support rail kit:  braces: L2.5"x2.5"x1/4"	(2) 1 5/8" Fiber	T-Mobile
			Ericsson Air 21 B4A/B2P			
			Ericsson KRY 112 144/1			
			Ericsson Radio 4449 B71+B12			
			Antel/BXA-70063-6CF - Panel	(3) T-Arms	(1) 1 5/8" Fiber	Verizon
			Antel/BXA-171085-12BF - Panel			
			Antel/LPA-80080-6CF - Panel			
			Antel/LPA-4019 - Panel			
			ALU/RRH 2x40 AWS			
			RFS DB-T1-6Z-8AB-0Z Distribution			
			Powerwave 7770- Panel	(3) Modified T-Arms W/ (3) 2.38" Horizontal Pipe, (3) 2.38" Pipe Brace & (6) 2.88" Antenna Pipes	(1) 1/2" RET (3) 3/8" RET (1) 3" Conduit (2) 3" Conduit	
			Cci OPA65R-BU8DA- Panel			
			Cci DMP65R-BU8DA- Panel			
			Powerwave LGP21401 TMA			
			Powerwave LGP13519 Diplexer			
			Powerwave 860 10025			
			Ericsson RRUS 4478 B14			
			Ericsson RRUS 4449 B5/B12			
			Ericsson RRUS 8843 B2 B66A			
			Raycap DC6-48-60-18-8F			
			Raycap DC9-48-60-24-8C-EV			
			Powerwave 1001983- Bias T			

(Housing (2) 3/4" DC & (1) 7/16" fiber cables)

(Housing (1) 7/16" fiber, & (3) 1" DC power cables)

**Proposed Carrier’s Final Configuration of Antennas, Mounts and Transmission Lines**

Information pertaining to the proposed carrier’s final configuration of antennas and transmission lines was provided by SBA Communications Corp. The proposed antennas and lines are listed below.

Items	Elevation (ft)	Qty.	Antenna Descriptions	Mount Type & Qty.	Transmission Lines	Owner
		6	JMA Wireless MX06FRO660-03 - Panel	(3) Modified T-Arms W/ (3) JMA Wireless 91900314 (Mount Bracket)	Hybrid	Verizon
			Samsung MT6407-77A - Panel			
			Samsung RFV01U-D1A RRU			
			Samsung RFV01U-D2A RRU			
		3	Commscope CHB626-43-2X-Combiner			
			Raycap RCMDC-6627-PF-48-OVP			

See the attached coax layout for the line placement considered in the analysis.

## **Analysis Results**

The results of the structural analysis, performed for the wind and ice loading and antenna equipment as defined above, are summarized as the following:

	Pole shafts	Anchor Bolts	Base Plate
Max. Usage:			
Pass/Fail	<b>Pass</b>	<b>Pass</b>	<b>Pass</b>

## **Foundations**

	Moment (Kip-Ft)	Shear (Kips)
Original Design Reactions		
Analysis Reactions		
Factored Reactions*		
% of Design Reactions		

\* Per section 15.5.1 of the TIA-222-G standard, factored reactions were obtained by multiplying a 1.35 factor to the original design reactions.

The foundation has been investigated using the supplied documents and soils report and was found adequate. Therefore, no modification to the foundation will be required.

### **Operational Condition (Rigidity):**

Operational characteristics of the tower are found to be within the limits prescribed by TIA-222 for the installed antennas. The maximum twist/sway at the elevation of the proposed equipment is 0.9186 degrees under the operational wind speed as specified in the Analysis Criteria.

### **Conclusions**

Based on the analysis results, the existing structure and its foundation were found to be adequate to safely support the existing and proposed equipment and meet the minimum requirements per the TIA-222 Standard under the design basic wind speed as specified in the Analysis Criteria.



## Standard Conditions

This analysis was performed based on the information supplied to **Tower Engineering Solutions,** Verification of the information provided was not included in the Scope of Work for . The accuracy of the analysis is dependent on the accuracy of the information provided.

The structural analysis was performance based upon the evidence available at the time of this report. All information provided by the client is considered to be accurate.

The analyses will be performed based on the codes as specified by the client or based on the best knowledge of the engineering staff of . In the absence of information to the contrary, all work will be performed in accordance with the latest relevant revision of ANSI/TIA-222. If wind speed and/or ice loads are different from the minimum values recommended by the ANSI/TIA-222 standard or other codes, should be notified in writing and the applicable minimum values provided by the client.

The configuration of the existing mounts, antennas, coax and other appurtenances were supplied by the customer for the current structural analysis. has not visited the tower site to verify the adequacy of the information provided. If there is any discrepancy found in the report regarding the existing conditions, should be notified immediately to evaluate the effect of the discrepancy on the analysis results.

The client will assume responsibility for rework associated with the differences in initially provided information, including tower and foundation information, existing and/or proposed equipment and transmission lines.

If a feasibility analysis was performed, final acceptance of changed conditions shall be based upon a rigorous structural analysis.

# Usage Diagram - Max Ratio 60.90% at 25.0ft

**Structure:** CT11559-A-SBA  
**Site Name:** Thompson 1, CT  
**Height:** 149.00 (ft)  
**Base Elev:** 0.000 (ft)

**Code:** EIA/TIA-222-G  
**Exposure:** C  
**Gh:** 1.1


8/18/2021



Page: 1


**Dead Load Factor:** 1.20  
**Wind Load Factor:** 1.60

**Load Case : 1.2D + 1.6W 101 mph Wind**



**Iterations:** 22

*Copyright © 2021 by Tower Engineering Solutions, LLC. All rights reserved.*



## Structure: CT11559-A-SBA

**Type:** Tapered  
**Site Name:** Thompson 1, CT  
**Height:** 149.00 (ft)  
**Base Elev:** 0.00 (ft)

**Base Shape:** 18 Sided  
**Taper:** 0.23532

8/18/2021

Page: 2



### Shaft Properties


Seq	Length (ft)	Top (in)	Bottom (in)	Thick (in)	Joint Type	Taper	Grade (ksi)
1	25.00	53.18	59.06	0.438		0.23532	65
2	50.00	43.81	55.58	0.375	Slip	0.23532	65
3	50.00	34.08	45.85	0.313	Slip	0.23532	65
4	42.00	25.88	35.76	0.250	Slip	0.23532	65

### Discrete Appurtenances

Attach Elev (ft)	Force Elev (ft)	Qty	Description	Carrier
148.00	148.00	3	AIR21 B2A B4P	T-Mobile
148.00	148.00	3	AIR21 B2A B4P	T-Mobile
148.00	148.00	3	APXVAARR24_43-U-NA20	T-Mobile
148.00	148.00	3	Ericsson KRY112 144/1	T-Mobile
148.00	148.00	3	4449	T-Mobile
148.00	148.00	1	HRK12 (Handrail Kit)	T-Mobile
148.00	148.00	1	(3) Stabilizer Kit (4' FW)	T-Mobile
148.00	148.00	1	T-Arms	T-Mobile
137.00	137.00	3	T-Arms	Verizon
137.00	137.00	6	JMA Wireless	Verizon
137.00	137.00	3	Samsung MT6407-77A	Verizon
137.00	137.00	3	91900314	Verizon
137.00	137.00	3	Samsung RFV01U-D1A	Verizon
137.00	137.00	3	Samsung RFV01U-D2A	Verizon
137.00	137.00	3	Commscope	Verizon
137.00	137.00	1	RCMDC-6627-PF-48	Verizon
127.00	127.00	6	7770.00	AT&T
127.00	127.00	12	Powerwave LGP21401	AT&T
127.00	127.00	12	Kathrein 860 10025 RET	AT&T
127.00	127.00	6	Powerwave LGP13519	AT&T
127.00	127.00	1	Raycap DC6-48-60-18-8F	AT&T
127.00	127.00	3	Powerwave 1001983 Bias	AT&T
127.00	127.00	3	OPA65R-BU8DA	AT&T
127.00	127.00	3	DMP65R-BU8DA	AT&T
127.00	127.00	3	Horizontal Pipe	AT&T
127.00	127.00	3	RRUS 4478 B14	AT&T
127.00	127.00	3	4449 B5/B12	AT&T
127.00	127.00	3	RRUS 8843 B2 B66A	AT&T
127.00	127.00	1	DC9-48-60-24-8C-EV	AT&T
127.00	127.00	1	(3) Stabilizer Kit	AT&T
127.00	127.00	3	T-Arms	AT&T

### Linear Appurtenances

Elev From (ft)	Elev To (ft)	Placement	Description	Carrier
0.00	148.00	Inside	1 5/8" Coax	T-Mobile
0.00	148.00	Inside	1 5/8" Fiber	T-Mobile
0.00	137.00	Inside	1 5/8" Coax	Verizon
0.00	137.00	Inside	1 5/8" Hybrid	Verizon
0.00	127.00	Inside	1 5/8" Coax	AT&T
0.00	127.00	Inside	1" DC	AT&T
0.00	127.00	Inside	1/2" RET	AT&T
0.00	127.00	Inside	3" flex Conduit	AT&T
0.00	127.00	Inside	3/4" DC	AT&T
0.00	127.00	Inside	7/16" Fiber	AT&T



## Structure: CT11559-A-SBA

**Type:** Tapered  
**Site Name:** Thompson 1, CT  
**Height:** 149.00 (ft)  
**Base Elev:** 0.00 (ft)

**Base Shape:** 18 Sided  
**Taper:** 0.23532

8/18/2021

Page: 3



### Anchor Bolts

Qty	Specifications	Grade (ksi)	Arrangement
18	2.00" F1554 105	105.0	Radial

### Base Plate

Thickness (in)	Specifications (in)	Grade (ksi)	Geometry
2.7500	72.0	50.0	Round

### Reactions

Load Case	Moment (FT-Kips)	Shear (Kips)	Axial (Kips)
1.2D + 1.6W 101 mph Wind	3600.8	33.8	47.3
0.9D + 1.6W 101 mph Wind	3574.6	33.8	35.4
1.2D + 1.0Di + 1.0Wi 50 mph Wind	961.8	9.1	78.7
1.2D + 1.0E	194.2	1.7	47.3
0.9D + 1.0E	192.7	1.7	35.5
1.0D + 1.0W 60 mph Wind	790.9	7.5	39.4


# Structure: CT11559-A-SBA - Coax Line Placement

**Type:** Monopole  
**Site Name:** Thompson 1, CT  
**Height:** 149.00 (ft)

8/18/2021



Page: 4



## Shaft Properties

<b>Structure:</b> CT11559-A-SBA	<b>Code:</b> EIA/TIA-222-G	8/18/2021
<b>Site Name:</b> Thompson 1, CT	<b>Exposure:</b> C	
<b>Height:</b> 149.00 (ft)	<b>Crest Height:</b> 0.00	
<b>Base Elev:</b> 0.000 (ft)	<b>Site Class:</b> D - Stiff Soil	
<b>Gh:</b> 1.1	<b>Topography:</b> 1	<b>Struct Class:</b> II



Page: 5

Sec. No.	Shape	Length (ft)	Thick (in)	Fy (ksi)	Joint Type	Overlap (in)	Weight (lb)
1	18	25.000	0.4375	65		0.00	6,578
2	18	50.000	0.3750	65	Slip	84.00	9,987
3	18	50.000	0.3125	65	Slip	72.00	6,691
4	18	42.000	0.2500	65	Slip	60.00	3,466
<b>Total Shaft Weight:</b>							<b>26,722</b>

Bottom

Top

Sec. No.	Dia (in)	Elev (ft)	Area (sqin)	Ix (in^4)	W/t Ratio	D/t Ratio	Dia (in)	Elev (ft)	Area (sqin)	Ix (in^4)	W/t Ratio	D/t Ratio	Taper
1	59.06	0.00	81.41	35348.50	22.39	135.00	53.18	25.00	73.24	25739.0	20.02	121.5	0.235319
2	55.58	18.00	65.70	25294.99	24.72	148.20	43.81	68.00	51.70	12323.0	19.19	116.8	0.235319
3	45.85	62.00	45.16	11831.43	24.46	146.71	34.08	112.00	33.49	4825.70	17.82	109.0	0.235319
4	35.76	107.0	28.17	4488.25	23.81	143.03	25.88	149.00	20.33	1686.85	16.84	103.5	0.235319

## Load Summary

<b>Structure:</b> CT11559-A-SBA	<b>Code:</b> EIA/TIA-222-G	8/18/2021
<b>Site Name:</b> Thompson 1, CT	<b>Exposure:</b> C	
<b>Height:</b> 149.00 (ft)	<b>Crest Height:</b> 0.00	
<b>Base Elev:</b> 0.000 (ft)	<b>Site Class:</b> D - Stiff Soil	
<b>Gh:</b> 1.1	<b>Topography:</b> 1	<b>Struct Class:</b> II



Page: 6

### Discrete Appurtenances

No.	Elev (ft)	Description	Qty	No Ice			Ice			Hor. Ecc. (ft)	Vert Ecc (ft)
				Weight (lb)	CaAa (sf)	CaAa Factor	Weight (lb)	CaAa (sf)	CaAa Factor		
1	148.00	AIR21 B2A B4P	3	91.50	6.09	0.86	329.95	7.583	0.86	0.00	0.00
2	148.00	AIR21 B2A B4P	3	90.40	6.09	0.86	329.95	7.583	0.86	0.00	0.00
3	148.00	APXVAARR24_43-U-NA20	3	128.00	20.24	0.70	708.17	22.801	0.70	0.00	0.00
4	148.00	Ericsson KRY112 144/1 TMA	3	11.00	0.41	0.70	25.36	1.043	0.70	0.00	0.00
5	148.00	4449	3	70.00	1.65	0.67	168.83	2.392	0.67	0.00	0.00
6	148.00	HRK12 (Handrail Kit)	1	261.72	6.75	0.75	675.29	15.534	0.75	0.00	0.00
7	148.00	(3) Stabilizer Kit (4' FW)	1	140.00	3.70	0.75	374.24	8.859	0.75	0.00	0.00
8	148.00	T-Arms	1	500.00	15.00	0.75	1197.15	41.027	0.75	0.00	0.00
9	137.00	T-Arms	3	350.00	8.00	0.75	672.83	17.224	0.75	0.00	0.00
10	137.00	JMA Wireless MX06FRO660-03	6	60.00	9.87	0.87	433.08	11.720	0.87	0.00	0.00
11	137.00	Samsung MT6407-77A	3	87.10	4.69	0.70	255.91	5.960	0.70	0.00	0.00
12	137.00	91900314	3	28.00	0.00	1.00	53.83	0.000	1.00	0.00	0.00
13	137.00	Samsung RFV01U-D1A RRU	3	84.40	1.88	0.67	152.13	2.608	0.67	0.00	0.00
14	137.00	Samsung RFV01U-D2A RRU	3	70.30	1.88	0.67	134.56	2.608	0.67	0.00	0.00
15	137.00	Commscope CHB626-43-2X	3	19.40	1.33	0.50	59.82	2.471	0.50	0.00	0.00
16	137.00	RCMDC-6627-PF-48	1	32.00	4.06	1.00	182.53	5.146	1.00	0.00	0.00
17	127.00	7770.00	6	35.00	5.50	0.73	225.00	6.925	0.73	0.00	0.00
18	127.00	Powerwave LGP21401 TMAs	12	14.10	1.29	1.00	46.88	2.386	1.00	0.00	0.00
19	127.00	Kathrein 860 10025 RET	12	1.10	0.14	1.00	7.02	0.561	1.00	0.00	0.00
20	127.00	Powerwave LGP13519 Diplexer	6	5.30	0.34	1.00	17.75	0.935	1.00	0.00	0.00
21	127.00	Raycap DC6-48-60-18-8F	1	31.80	0.92	1.00	112.87	1.494	1.00	0.00	0.00
22	127.00	Powerwave 1001983 Bias T	3	4.40	0.21	1.00	11.69	0.684	1.00	0.00	0.00
23	127.00	OPA65R-BU8DA	3	76.50	18.09	0.73	462.99	21.617	0.74	0.00	0.00
24	127.00	DMP65R-BU8DA	3	95.70	17.87	0.73	561.24	20.569	0.75	0.00	0.00
25	127.00	Horizontal Pipe	3	45.75	2.97	0.75	104.38	7.861	0.75	0.00	0.00
26	127.00	RRUS 4478 B14	3	59.40	1.65	0.67	113.78	2.330	0.67	0.00	0.00
27	127.00	4449 B5/B12	3	71.00	1.97	0.67	141.00	2.688	0.67	0.00	0.00
28	127.00	RRUS 8843 B2 B66A	3	72.00	1.64	0.67	133.43	2.292	0.67	0.00	0.00
29	127.00	DC9-48-60-24-8C-EV	1	26.20	1.14	1.00	165.19	3.221	1.00	0.00	0.00
30	127.00	(3) Stabilizer Kit	1	180.00	6.10	0.75	476.60	14.476	0.75	0.00	0.00
31	127.00	T-Arms	3	350.00	8.00	0.75	670.40	17.154	0.75	0.00	0.00
<b>Totals:</b>			<b>106</b>	<b>7,370.47</b>			<b>23,156.39</b>				

### Linear Appurtenances

Bottom Elev. (ft)	Top Elev. (ft)	Description	Exposed Width	Exposed
0.00	148.00	(11) 1 5/8" Coax	0.00	Inside
0.00	148.00	(2) 1 5/8" Fiber	0.00	Inside
0.00	137.00	(11) 1 5/8" Coax	0.00	Inside
0.00	137.00	(1) 1 5/8" Hybrid	0.00	Inside
0.00	127.00	(6) 1 5/8" Coax	0.00	Inside
0.00	127.00	(1) 1" DC	0.00	Inside
0.00	127.00	(1) 1/2" RET	0.00	Inside
0.00	127.00	(3) 3" flex Conduit	0.00	Inside
0.00	127.00	(2) 3/4" DC	0.00	Inside
0.00	127.00	(2) 7/16" Fiber	0.00	Inside

## Discrete Appurtenances

No.	Elev (ft)	Description	Qty	No Ice			Ice			Hor. Ecc. (ft)	Vert Ecc (ft)
				Weight (lb)	CaAa (sf)	CaAa Factor	Weight (lb)	CaAa (sf)	CaAa Factor		



## Shaft Section Properties

<b>Structure:</b> CT11559-A-SBA	<b>Code:</b> EIA/TIA-222-G	8/18/2021
<b>Site Name:</b> Thompson 1, CT	<b>Exposure:</b> C	
<b>Height:</b> 149.00 (ft)	<b>Crest Height:</b> 0.00	
<b>Base Elev:</b> 0.000 (ft)	<b>Site Class:</b> D - Stiff Soil	
<b>Gh:</b> 1.1	<b>Topography:</b> 1	<b>Struct Class:</b> II



Page: 8

**Increment Length:** 5 (ft)

Elev (ft)	Description	Thick (in)	Dia (in)	Area (in <sup>2</sup> )	Ix (in <sup>4</sup> )	W/t Ratio	D/t Ratio	Fpy (ksi)	S (in <sup>3</sup> )	Weight (lb)
0.00		0.4375	59.063	81.405	35348.5	22.39	135.00	75.1	1178.	0.0
5.00		0.4375	57.886	79.771	33262.6	21.92	132.31	75.6	1131.	1371.1
10.00		0.4375	56.709	78.138	31260.4	21.45	129.62	76.2	1085.	1343.3
15.00		0.4375	55.533	76.504	29340.3	20.97	126.93	76.7	1040.	1315.5
18.00	Bot - Section 2	0.4375	54.827	75.524	28226.8	20.69	125.32	77.1	1014.	776.0
20.00		0.4375	54.356	74.870	27500.4	20.50	124.24	77.3	996.5	957.0
25.00	Top - Section 1	0.3750	53.930	63.741	23097.5	23.95	143.81	0.0	0.0	2356.3
30.00		0.3750	52.753	62.341	21608.3	23.39	140.67	73.9	806.8	1072.6
35.00		0.3750	51.576	60.940	20184.6	22.84	137.54	74.5	770.8	1048.7
40.00		0.3750	50.400	59.540	18824.8	22.29	134.40	75.2	735.7	1024.9
45.00		0.3750	49.223	58.139	17527.5	21.73	131.26	75.8	701.3	1001.1
50.00		0.3750	48.047	56.739	16291.2	21.18	128.12	76.5	667.8	977.3
55.00		0.3750	46.870	55.339	15114.5	20.63	124.99	77.1	635.2	953.4
60.00		0.3750	45.693	53.938	13995.8	20.07	121.85	77.8	603.3	929.6
62.00	Bot - Section 3	0.3750	45.223	53.378	13564.3	19.85	120.59	78.0	590.8	365.2
65.00		0.3750	44.517	52.538	12933.8	19.52	118.71	78.4	572.2	998.1
68.00	Top - Section 2	0.3125	44.436	43.763	10764.6	23.66	142.19	0.0	0.0	982.4
70.00		0.3125	43.965	43.296	10423.8	23.40	140.69	73.9	467.0	296.2
75.00		0.3125	42.789	42.129	9603.5	22.73	136.92	74.7	442.1	726.7
80.00		0.3125	41.612	40.962	8827.3	22.07	133.16	75.4	417.8	706.9
85.00		0.3125	40.435	39.795	8094.2	21.40	129.39	76.2	394.3	687.0
90.00		0.3125	39.259	38.628	7402.8	20.74	125.63	77.0	371.4	667.1
95.00		0.3125	38.082	37.461	6751.9	20.08	121.86	77.8	349.2	647.3
100.00		0.3125	36.906	36.294	6140.3	19.41	118.10	78.6	327.7	627.4
105.00		0.3125	35.729	35.128	5566.9	18.75	114.33	79.3	306.9	607.6
107.00	Bot - Section 4	0.3125	35.258	34.661	5347.9	18.48	112.83	79.7	298.7	237.5
110.00		0.3125	34.552	33.961	5030.3	18.09	110.57	80.1	286.7	635.0
112.00	Top - Section 3	0.2500	34.582	27.241	4056.7	22.98	138.33	0.0	0.0	416.2
115.00		0.2500	33.876	26.681	3811.6	22.48	135.50	75.0	221.6	275.2
120.00		0.2500	32.699	25.748	3425.3	21.65	130.80	75.9	206.3	446.0
125.00		0.2500	31.523	24.814	3066.0	20.82	126.09	76.9	191.6	430.1
127.00		0.2500	31.052	24.441	2929.7	20.49	124.21	77.3	185.8	167.6
130.00		0.2500	30.346	23.880	2732.8	19.99	121.38	77.9	177.4	246.6
135.00		0.2500	29.169	22.947	2424.7	19.16	116.68	78.9	163.7	398.4
137.00		0.2500	28.699	22.573	2308.2	18.83	114.80	79.3	158.4	154.9
140.00		0.2500	27.993	22.013	2140.6	18.33	111.97	79.8	150.6	227.6
145.00		0.2500	26.816	21.080	1879.6	17.50	107.27	80.8	138.1	366.6
148.00		0.2500	26.110	20.519	1733.7	17.01	104.44	81.4	130.8	212.3
149.00		0.2500	25.875	20.333	1686.8	16.84	103.50	81.6	128.4	69.5

**26722.3**

## Wind Loading - Shaft

<b>Structure:</b> CT11559-A-SBA	<b>Code:</b> EIA/TIA-222-G	8/18/2021
<b>Site Name:</b> Thompson 1, CT	<b>Exposure:</b> C	
<b>Height:</b> 149.00 (ft)	<b>Crest Height:</b> 0.00	
<b>Base Elev:</b> 0.000 (ft)	<b>Site Class:</b> D - Stiff Soil	
<b>Gh:</b> 1.1	<b>Topography:</b> 1	<b>Page:</b> 9
	<b>Struct Class:</b> II	




**Load Case:** 1.2D + 1.6W 101 mph Wind

**Iterations** 22

**Dead Load Factor** 1.20

**Wind Load Factor** 1.60



Elev (ft)	Description	Kzt	Kz	qz (psf)	qzGh (psf)	C (mph-ft)	Cf	Ice Thick (in)	Tributary (ft)	Aa (sf)	CfAa (sf)	Wind Force X (lb)	Dead Load Ice (lb)	Tot Dead Load (lb)
0.00		1.00	0.85	21.088	23.20	465.38	0.650	0.000	0.00	0.000	0.00	0.0	0.0	0.0
5.00		1.00	0.85	21.088	23.20	456.11	0.650	0.000	5.00	24.740	16.08	596.8	0.0	1645.3
10.00		1.00	0.85	21.088	23.20	446.84	0.650	0.000	5.00	24.242	15.76	584.8	0.0	1612.0
15.00		1.00	0.85	21.088	23.20	437.57	0.650	0.000	5.00	23.744	15.43	572.8	0.0	1578.6
18.00	Bot - Section 2	1.00	0.88	21.884	24.07	440.09	0.650	0.000	3.00	14.008	9.11	350.7	0.0	931.2
20.00		1.00	0.90	22.375	24.61	441.18	0.650	0.000	2.00	9.366	6.09	239.7	0.0	1148.4
25.00	Top - Section 1	1.00	0.95	23.451	25.80	441.89	0.650	0.000	5.00	23.066	14.99	618.8	0.0	2827.6
30.00		1.00	0.98	24.369	26.81	446.83	0.650	0.000	5.00	22.568	14.67	629.2	0.0	1287.1
35.00		1.00	1.01	25.172	27.69	444.02	0.650	0.000	5.00	22.071	14.35	635.6	0.0	1258.5
40.00		1.00	1.04	25.890	28.48	440.03	0.650	0.000	5.00	21.573	14.02	638.9	0.0	1229.9
45.00		1.00	1.07	26.540	29.19	435.12	0.650	0.000	5.00	21.075	13.70	639.9	0.0	1201.3
50.00		1.00	1.09	27.135	29.85	429.45	0.650	0.000	5.00	20.577	13.38	638.8	0.0	1172.7
55.00		1.00	1.12	27.685	30.45	423.16	0.650	0.000	5.00	20.079	13.05	636.0	0.0	1144.1
60.00		1.00	1.14	28.197	31.02	416.33	0.650	0.000	5.00	19.582	12.73	631.7	0.0	1115.5
62.00	Bot - Section 3	1.00	1.14	28.392	31.23	413.47	0.650	0.000	2.00	7.693	5.00	249.9	0.0	438.2
65.00		1.00	1.16	28.676	31.54	409.04	0.650	0.000	3.00	11.549	7.51	378.9	0.0	1197.7
68.00	Top - Section 2	1.00	1.17	28.950	31.84	404.47	0.650	0.000	3.00	11.370	7.39	376.6	0.0	1178.8
70.00		1.00	1.17	29.127	32.04	407.14	0.650	0.000	2.00	7.480	4.86	249.3	0.0	355.5
75.00		1.00	1.19	29.553	32.51	399.13	0.650	0.000	5.00	18.353	11.93	620.5	0.0	872.1
80.00		1.00	1.21	29.958	32.95	390.80	0.650	0.000	5.00	17.855	11.61	611.9	0.0	848.2
85.00		1.00	1.22	30.342	33.38	382.18	0.650	0.000	5.00	17.357	11.28	602.5	0.0	824.4
90.00		1.00	1.24	30.710	33.78	373.30	0.650	0.000	5.00	16.859	10.96	592.3	0.0	800.6
95.00		1.00	1.25	31.061	34.17	364.18	0.650	0.000	5.00	16.361	10.63	581.4	0.0	776.8
100.00		1.00	1.27	31.399	34.54	354.84	0.650	0.000	5.00	15.863	10.31	569.8	0.0	752.9
105.00		1.00	1.28	31.723	34.89	345.30	0.650	0.000	5.00	15.366	9.99	557.6	0.0	729.1
107.00	Bot - Section 4	1.00	1.28	31.849	35.03	341.43	0.650	0.000	2.00	6.007	3.90	218.9	0.0	285.0
110.00		1.00	1.29	32.035	35.24	335.56	0.650	0.000	3.00	8.988	5.84	329.4	0.0	762.0
112.00	Top - Section 3	1.00	1.30	32.157	35.37	331.62	0.650	0.000	2.00	5.892	3.83	216.8	0.0	499.4
115.00		1.00	1.30	32.336	35.57	330.54	0.650	0.000	3.00	8.689	5.65	321.4	0.0	330.3
120.00		1.00	1.32	32.627	35.89	320.49	0.650	0.000	5.00	14.084	9.15	525.7	0.0	535.2
125.00		1.00	1.33	32.909	36.20	310.29	0.650	0.000	5.00	13.586	8.83	511.5	0.0	516.1
127.00	Appurtenance(s)	1.00	1.33	33.019	36.32	306.17	0.650	0.000	2.00	5.295	3.44	200.0	0.0	201.1
130.00		1.00	1.34	33.182	36.50	299.94	0.650	0.000	3.00	7.793	5.07	295.8	0.0	296.0
135.00		1.00	1.35	33.446	36.79	289.46	0.650	0.000	5.00	12.590	8.18	481.7	0.0	478.0
137.00	Appurtenance(s)	1.00	1.35	33.550	36.90	285.23	0.650	0.000	2.00	4.897	3.18	187.9	0.0	185.9
140.00		1.00	1.36	33.703	37.07	278.85	0.650	0.000	3.00	7.196	4.68	277.4	0.0	273.1
145.00		1.00	1.37	33.953	37.35	268.12	0.650	0.000	5.00	11.595	7.54	450.4	0.0	439.9
148.00	Appurtenance(s)	1.00	1.37	34.100	37.51	261.62	0.650	0.000	3.00	6.718	4.37	262.1	0.0	254.8
149.00		1.00	1.38	34.148	37.56	259.45	0.650	0.000	1.00	2.199	1.43	85.9	0.0	83.4
<b>Totals:</b>									<b>149.00</b>			<b>17,169.1</b>		<b>32,066.8</b>

## Discrete Appurtenance Forces

<b>Structure:</b> CT11559-A-SBA	<b>Code:</b> EIA/TIA-222-G	8/18/2021
<b>Site Name:</b> Thompson 1, CT	<b>Exposure:</b> C	
<b>Height:</b> 149.00 (ft)	<b>Crest Height:</b> 0.00	
<b>Base Elev:</b> 0.000 (ft)	<b>Site Class:</b> D - Stiff Soil	
<b>Gh:</b> 1.1	<b>Topography:</b> 1	<b>Struct Class:</b> II




Page: 10

**Load Case:** 1.2D + 1.6W 101 mph Wind

**Dead Load Factor** 1.20

**Wind Load Factor** 1.60



**Iterations** 22

No.	Elev (ft)	Description	Qty	qz (psf)	qzGh (psf)	Orient Factor	x Ka	Ka	Total CaAa (sf)	Dead Load (lb)	Horiz Ecc (ft)	Vert Ecc (ft)	Wind FX (lb)	Mom Y (lb-ft)	Mom Z (lb-ft)
1	148.00	T-Arms	1	34.100	37.510	0.56	0.75	8.44	600.00	0.000	0.000	506.38	0.00	0.00	
2	148.00	4449	3	34.100	37.510	0.54	0.80	2.65	252.00	0.000	0.000	159.23	0.00	0.00	
3	148.00	HRK12 (Handrail Kit)	1	34.100	37.510	0.56	0.75	3.80	314.06	0.000	0.000	227.87	0.00	0.00	
4	148.00	(3) Stabilizer Kit (4' FW)	1	34.100	37.510	0.56	0.75	2.08	168.00	0.000	0.000	124.91	0.00	0.00	
5	148.00	Ericsson KRY112 144/1	3	34.100	37.510	0.56	0.80	0.69	39.60	0.000	0.000	41.34	0.00	0.00	
6	148.00	AIR21 B2A B4P	3	34.100	37.510	0.69	0.80	12.57	329.40	0.000	0.000	754.39	0.00	0.00	
7	148.00	AIR21 B2A B4P	3	34.100	37.510	0.69	0.80	12.57	325.44	0.000	0.000	754.39	0.00	0.00	
8	148.00	APXVAARR24_43-U-NA2	3	34.100	37.510	0.56	0.80	34.00	460.80	0.000	0.000	2040.73	0.00	0.00	
9	137.00	T-Arms	3	33.550	36.905	0.56	0.75	13.50	1260.00	0.000	0.000	797.15	0.00	0.00	
10	137.00	RCMDC-6627-PF-48	1	33.550	36.905	1.00	1.00	4.06	38.40	0.000	0.000	239.73	0.00	0.00	
11	137.00	Commscope	3	33.550	36.905	0.40	0.80	1.60	69.84	0.000	0.000	94.24	0.00	0.00	
12	137.00	Samsung RFV01U-D2A	3	33.550	36.905	0.54	0.80	3.02	253.08	0.000	0.000	178.50	0.00	0.00	
13	137.00	Samsung RFV01U-D1A	3	33.550	36.905	0.54	0.80	3.02	303.84	0.000	0.000	178.50	0.00	0.00	
14	137.00	91900314	3	33.550	36.905	1.00	1.00	0.00	100.80	0.000	0.000	0.00	0.00	0.00	
15	137.00	Samsung MT6407-77A	3	33.550	36.905	0.56	0.80	7.88	313.56	0.000	0.000	465.25	0.00	0.00	
16	137.00	JMA Wireless	6	33.550	36.905	0.70	0.80	41.22	432.00	0.000	0.000	2433.79	0.00	0.00	
17	127.00	T-Arms	3	33.019	36.321	0.56	0.75	13.50	1260.00	0.000	0.000	784.53	0.00	0.00	
18	127.00	7770.00	6	33.019	36.321	0.58	0.80	19.27	252.00	0.000	0.000	1119.96	0.00	0.00	
19	127.00	Powerwave LGP21401	12	33.019	36.321	0.80	0.80	12.38	203.04	0.000	0.000	719.67	0.00	0.00	
20	127.00	Kathrein 860 10025 RET	12	33.019	36.321	0.80	0.80	1.34	15.84	0.000	0.000	78.10	0.00	0.00	
21	127.00	Powerwave LGP13519	6	33.019	36.321	0.80	0.80	1.63	38.16	0.000	0.000	94.84	0.00	0.00	
22	127.00	Raycap DC6-48-60-18-8F	1	33.019	36.321	1.00	1.00	0.92	38.16	0.000	0.000	53.46	0.00	0.00	
23	127.00	Powerwave 1001983 Bias	3	33.019	36.321	0.80	0.80	0.50	15.84	0.000	0.000	29.29	0.00	0.00	
24	127.00	(3) Stabilizer Kit	1	33.019	36.321	0.56	0.75	3.43	216.00	0.000	0.000	199.40	0.00	0.00	
25	127.00	OPA65R-BU8DA	3	33.019	36.321	0.58	0.80	31.56	275.40	0.000	0.000	1834.25	0.00	0.00	
26	127.00	DMP65R-BU8DA	3	33.019	36.321	0.58	0.80	31.18	344.52	0.000	0.000	1811.95	0.00	0.00	
27	127.00	Horizontal Pipe	3	33.019	36.321	0.56	0.75	5.01	164.70	0.000	0.000	291.14	0.00	0.00	
28	127.00	RRUS 4478 B14	3	33.019	36.321	0.54	0.80	2.65	213.84	0.000	0.000	154.19	0.00	0.00	
29	127.00	4449 B5/B12	3	33.019	36.321	0.54	0.80	3.17	255.60	0.000	0.000	184.09	0.00	0.00	
30	127.00	RRUS 8843 B2 B66A	3	33.019	36.321	0.54	0.80	2.64	259.20	0.000	0.000	153.25	0.00	0.00	
31	127.00	DC9-48-60-24-8C-EV	1	33.019	36.321	1.00	1.00	1.14	31.44	0.000	0.000	66.25	0.00	0.00	

**Totals:** 8,844.56

**16,570.79**

## Total Applied Force Summary

<b>Structure:</b> CT11559-A-SBA	<b>Code:</b> EIA/TIA-222-G	8/18/2021
<b>Site Name:</b> Thompson 1, CT	<b>Exposure:</b> C	
<b>Height:</b> 149.00 (ft)	<b>Crest Height:</b> 0.00	
<b>Base Elev:</b> 0.000 (ft)	<b>Site Class:</b> D - Stiff Soil	
<b>Gh:</b> 1.1	<b>Topography:</b> 1	<b>Struct Class:</b> II




Page: 11

**Load Case:** 1.2D + 1.6W 101 mph Wind

**Dead Load Factor** 1.20

**Wind Load Factor** 1.60



**Iterations** 22

Elev (ft)	Description	Lateral FX (-) (lb)	Axial FY (-) (lb)	Torsion MY (lb-ft)	Moment MZ (lb-ft)
0.00		0.00	0.00	0.00	0.00
5.00		596.83	1877.96	0.00	0.00
10.00		584.82	1844.61	0.00	0.00
15.00		572.81	1811.25	0.00	0.00
18.00		350.69	1070.74	0.00	0.00
20.00		239.73	1241.43	0.00	0.00
25.00		618.82	3060.21	0.00	0.00
30.00		629.15	1519.70	0.00	0.00
35.00		635.57	1491.11	0.00	0.00
40.00		638.95	1462.52	0.00	0.00
45.00		639.87	1433.93	0.00	0.00
50.00		638.77	1405.34	0.00	0.00
55.00		635.95	1376.75	0.00	0.00
60.00		631.65	1348.15	0.00	0.00
62.00		249.88	531.26	0.00	0.00
65.00		378.88	1337.27	0.00	0.00
68.00		376.56	1318.40	0.00	0.00
70.00		249.26	448.54	0.00	0.00
75.00		620.48	1104.68	0.00	0.00
80.00		611.91	1080.85	0.00	0.00
85.00		602.49	1057.02	0.00	0.00
90.00		592.29	1033.20	0.00	0.00
95.00		581.38	1009.37	0.00	0.00
100.00		569.81	985.55	0.00	0.00
105.00		557.63	961.72	0.00	0.00
107.00		218.86	378.02	0.00	0.00
110.00		329.39	901.59	0.00	0.00
112.00		216.76	592.48	0.00	0.00
115.00		321.44	469.85	0.00	0.00
120.00		525.68	767.83	0.00	0.00
125.00		511.48	748.77	0.00	0.00
127.00	(63) attachments	7774.39	3877.91	0.00	0.00
130.00		295.83	390.21	0.00	0.00
135.00		481.74	635.11	0.00	0.00
137.00	(25) attachments	4575.11	3020.23	0.00	0.00
140.00		277.45	322.20	0.00	0.00
145.00		450.37	521.75	0.00	0.00
148.00	(18) attachments	4871.31	2793.20	0.00	0.00
149.00		85.92	83.41	0.00	0.00
	<b>Totals:</b>	<b>33,739.92</b>	<b>47,314.11</b>	<b>0.00</b>	<b>0.00</b>

## Calculated Forces

<b>Structure:</b> CT11559-A-SBA	<b>Code:</b> EIA/TIA-222-G	8/18/2021
<b>Site Name:</b> Thompson 1, CT	<b>Exposure:</b> C	
<b>Height:</b> 149.00 (ft)	<b>Crest Height:</b> 0.00	
<b>Base Elev:</b> 0.000 (ft)	<b>Site Class:</b> D - Stiff Soil	
<b>Gh:</b> 1.1	<b>Topography:</b> 1	<b>Struct Class:</b> II



Page: 12

**Load Case:** 1.2D + 1.6W 101 mph Wind

**Iterations** 22

**Dead Load Factor** 1.20  
**Wind Load Factor** 1.60



Seg Elev (ft)	Pu FY (-) (kips)	Vu FX (-) (kips)	Tu MY (-) (ft-kips)	Mu MZ (ft-kips)	Mu MX (ft-kips)	Resultant Moment (ft-kips)	phi Pn (kips)	phi Vn (kips)	phi Tn (ft-kips)	phi Mn (ft-kips)	Total Deflect (in)	Rotation Sway (deg)	Rotation Twist (deg)	Stress Ratio
0.00	-47.27	-33.80	0.00	-3600.8	0.00	3600.80	5499.39	2749.69	13252.7	6636.23	0.00	0.000	0.000	0.551
5.00	-45.31	-33.31	0.00	-3431.8	0.00	3431.80	5429.06	2714.53	12818.7	6418.90	0.08	-0.142	0.000	0.543
10.00	-43.39	-32.83	0.00	-3265.2	0.00	3265.24	5357.09	2678.54	12387.8	6203.11	0.30	-0.285	0.000	0.535
15.00	-41.51	-32.33	0.00	-3101.1	0.00	3101.10	5283.48	2641.74	11960.1	5988.97	0.68	-0.430	0.000	0.526
18.00	-40.40	-32.02	0.00	-3004.1	0.00	3004.11	5238.53	2619.26	11705.2	5861.33	0.98	-0.518	0.000	0.520
20.00	-39.11	-31.84	0.00	-2940.0	0.00	2940.06	5208.23	2604.11	11536.0	5776.60	1.21	-0.578	0.000	0.517
25.00	-35.97	-31.28	0.00	-2780.8	0.00	2780.85	4201.23	2100.61	9252.96	4633.35	1.89	-0.726	0.000	0.609
30.00	-34.38	-30.73	0.00	-2624.4	0.00	2624.44	4145.44	2072.72	8928.09	4470.68	2.73	-0.876	0.000	0.596
35.00	-32.81	-30.16	0.00	-2470.8	0.00	2470.81	4088.00	2044.00	8605.21	4309.00	3.74	-1.043	0.000	0.582
40.00	-31.27	-29.59	0.00	-2319.9	0.00	2319.99	4028.93	2014.47	8284.56	4148.44	4.93	-1.212	0.000	0.567
45.00	-29.77	-29.00	0.00	-2172.0	0.00	2172.05	3968.22	1984.11	7966.37	3989.11	6.29	-1.382	0.000	0.552
50.00	-28.29	-28.41	0.00	-2027.0	0.00	2027.03	3905.86	1952.93	7650.88	3831.13	7.83	-1.552	0.000	0.537
55.00	-26.85	-27.82	0.00	-1884.9	0.00	1884.96	3841.87	1920.93	7338.34	3674.63	9.54	-1.723	0.000	0.520
60.00	-25.47	-27.20	0.00	-1745.8	0.00	1745.86	3776.23	1888.12	7028.98	3519.72	11.44	-1.894	0.000	0.503
62.00	-24.90	-26.97	0.00	-1691.4	0.00	1691.47	3749.52	1874.76	6906.19	3458.23	12.25	-1.964	0.000	0.496
65.00	-23.53	-26.59	0.00	-1610.5	0.00	1610.56	3708.96	1854.48	6723.05	3366.52	13.52	-2.068	0.000	0.485
68.00	-22.19	-26.19	0.00	-1530.8	0.00	1530.80	2897.69	1448.84	5257.67	2632.74	14.85	-2.171	0.000	0.589
70.00	-21.69	-25.98	0.00	-1478.4	0.00	1478.42	2878.95	1439.48	5167.56	2587.62	15.77	-2.241	0.000	0.579
75.00	-20.53	-25.38	0.00	-1348.5	0.00	1348.53	2830.96	1415.48	4943.48	2475.42	18.23	-2.434	0.000	0.552
80.00	-19.39	-24.79	0.00	-1221.6	0.00	1221.62	2781.33	1390.66	4721.30	2364.16	20.88	-2.624	0.000	0.524
85.00	-18.29	-24.19	0.00	-1097.6	0.00	1097.68	2730.06	1365.03	4501.25	2253.97	23.73	-2.811	0.000	0.494
90.00	-17.21	-23.60	0.00	-976.71	0.00	976.71	2677.14	1338.57	4283.57	2144.97	26.77	-2.993	0.000	0.462
95.00	-16.17	-23.02	0.00	-858.69	0.00	858.69	2622.59	1311.30	4068.50	2037.27	30.00	-3.170	0.000	0.428
100.00	-15.15	-22.44	0.00	-743.60	0.00	743.60	2566.40	1283.20	3856.28	1931.01	33.41	-3.338	0.000	0.391
105.00	-14.18	-21.85	0.00	-631.42	0.00	631.42	2508.57	1254.28	3647.16	1826.29	36.99	-3.498	0.000	0.352
107.00	-13.79	-21.63	0.00	-587.72	0.00	587.72	2484.97	1242.49	3564.43	1784.86	38.47	-3.560	0.000	0.335
110.00	-12.89	-21.26	0.00	-522.84	0.00	522.84	2449.09	1224.55	3441.37	1723.24	40.73	-3.649	0.000	0.309
112.00	-12.28	-21.02	0.00	-480.32	0.00	480.32	1823.39	911.69	2573.73	1288.78	42.27	-3.705	0.000	0.380
115.00	-11.79	-20.69	0.00	-417.27	0.00	417.27	1799.96	899.98	2488.04	1245.87	44.63	-3.785	0.000	0.342
120.00	-11.02	-20.14	0.00	-313.83	0.00	313.83	1759.59	879.80	2346.51	1175.00	48.67	-3.921	0.000	0.274
125.00	-10.29	-19.59	0.00	-213.14	0.00	213.14	1717.59	858.79	2206.80	1105.04	52.83	-4.030	0.000	0.199
127.00	-6.96	-11.56	0.00	-173.97	0.00	173.97	1700.33	850.16	2151.49	1077.34	54.53	-4.066	0.000	0.166
130.00	-6.58	-11.25	0.00	-139.28	0.00	139.28	1673.94	836.97	2069.17	1036.12	57.10	-4.112	0.000	0.139
135.00	-5.97	-10.72	0.00	-83.05	0.00	83.05	1628.66	814.33	1933.84	968.36	61.43	-4.170	0.000	0.090
137.00	-3.29	-5.94	0.00	-61.60	0.00	61.60	1610.09	805.04	1880.41	941.60	63.18	-4.187	0.000	0.068
140.00	-2.99	-5.64	0.00	-43.77	0.00	43.77	1581.73	790.87	1801.05	901.87	65.82	-4.206	0.000	0.050
145.00	-2.50	-5.16	0.00	-15.56	0.00	15.56	1533.17	766.58	1671.06	836.77	70.23	-4.226	0.000	0.020
148.00	-0.08	-0.09	0.00	-0.09	0.00	0.09	1503.24	751.62	1594.49	798.43	72.89	-4.230	0.000	0.000
149.00	0.00	-0.09	0.00	0.00	0.00	0.00	1493.13	746.57	1569.22	785.78	73.77	-4.230	0.000	0.000


## Wind Loading - Shaft

<b>Structure:</b> CT11559-A-SBA	<b>Code:</b> EIA/TIA-222-G	8/18/2021
<b>Site Name:</b> Thompson 1, CT	<b>Exposure:</b> C	
<b>Height:</b> 149.00 (ft)	<b>Crest Height:</b> 0.00	
<b>Base Elev:</b> 0.000 (ft)	<b>Site Class:</b> D - Stiff Soil	
<b>Gh:</b> 1.1	<b>Topography:</b> 1	<b>Struct Class:</b> II



Page: 13

<b>Load Case:</b> 0.9D + 1.6W 101 mph Wind	<b>Iterations</b> 22
<b>Dead Load Factor</b> 0.90	
<b>Wind Load Factor</b> 1.60	



Elev (ft)	Description	Kzt	Kz	qz (psf)	qzGh (psf)	C (mph-ft)	Cf	Ice Thick (in)	Tributary (ft)	Aa (sf)	CfAa (sf)	Wind Force X (lb)	Dead Load Ice (lb)	Tot Dead Load (lb)
0.00		1.00	0.85	21.088	23.20	465.38	0.650	0.000	0.00	0.000	0.00	0.0	0.0	0.0
5.00		1.00	0.85	21.088	23.20	456.11	0.650	0.000	5.00	24.740	16.08	596.8	0.0	1234.0
10.00		1.00	0.85	21.088	23.20	446.84	0.650	0.000	5.00	24.242	15.76	584.8	0.0	1209.0
15.00		1.00	0.85	21.088	23.20	437.57	0.650	0.000	5.00	23.744	15.43	572.8	0.0	1184.0
18.00	Bot - Section 2	1.00	0.88	21.884	24.07	440.09	0.650	0.000	3.00	14.008	9.11	350.7	0.0	698.4
20.00		1.00	0.90	22.375	24.61	441.18	0.650	0.000	2.00	9.366	6.09	239.7	0.0	861.3
25.00	Top - Section 1	1.00	0.95	23.451	25.80	441.89	0.650	0.000	5.00	23.066	14.99	618.8	0.0	2120.7
30.00		1.00	0.98	24.369	26.81	446.83	0.650	0.000	5.00	22.568	14.67	629.2	0.0	965.3
35.00		1.00	1.01	25.172	27.69	444.02	0.650	0.000	5.00	22.071	14.35	635.6	0.0	943.9
40.00		1.00	1.04	25.890	28.48	440.03	0.650	0.000	5.00	21.573	14.02	638.9	0.0	922.4
45.00		1.00	1.07	26.540	29.19	435.12	0.650	0.000	5.00	21.075	13.70	639.9	0.0	901.0
50.00		1.00	1.09	27.135	29.85	429.45	0.650	0.000	5.00	20.577	13.38	638.8	0.0	879.5
55.00		1.00	1.12	27.685	30.45	423.16	0.650	0.000	5.00	20.079	13.05	636.0	0.0	858.1
60.00		1.00	1.14	28.197	31.02	416.33	0.650	0.000	5.00	19.582	12.73	631.7	0.0	836.7
62.00	Bot - Section 3	1.00	1.14	28.392	31.23	413.47	0.650	0.000	2.00	7.693	5.00	249.9	0.0	328.7
65.00		1.00	1.16	28.676	31.54	409.04	0.650	0.000	3.00	11.549	7.51	378.9	0.0	898.3
68.00	Top - Section 2	1.00	1.17	28.950	31.84	404.47	0.650	0.000	3.00	11.370	7.39	376.6	0.0	884.1
70.00		1.00	1.17	29.127	32.04	407.14	0.650	0.000	2.00	7.480	4.86	249.3	0.0	266.6
75.00		1.00	1.19	29.553	32.51	399.13	0.650	0.000	5.00	18.353	11.93	620.5	0.0	654.0
80.00		1.00	1.21	29.958	32.95	390.80	0.650	0.000	5.00	17.855	11.61	611.9	0.0	636.2
85.00		1.00	1.22	30.342	33.38	382.18	0.650	0.000	5.00	17.357	11.28	602.5	0.0	618.3
90.00		1.00	1.24	30.710	33.78	373.30	0.650	0.000	5.00	16.859	10.96	592.3	0.0	600.4
95.00		1.00	1.25	31.061	34.17	364.18	0.650	0.000	5.00	16.361	10.63	581.4	0.0	582.6
100.00		1.00	1.27	31.399	34.54	354.84	0.650	0.000	5.00	15.863	10.31	569.8	0.0	564.7
105.00		1.00	1.28	31.723	34.89	345.30	0.650	0.000	5.00	15.366	9.99	557.6	0.0	546.8
107.00	Bot - Section 4	1.00	1.28	31.849	35.03	341.43	0.650	0.000	2.00	6.007	3.90	218.9	0.0	213.7
110.00		1.00	1.29	32.035	35.24	335.56	0.650	0.000	3.00	8.988	5.84	329.4	0.0	571.5
112.00	Top - Section 3	1.00	1.30	32.157	35.37	331.62	0.650	0.000	2.00	5.892	3.83	216.8	0.0	374.6
115.00		1.00	1.30	32.336	35.57	330.54	0.650	0.000	3.00	8.689	5.65	321.4	0.0	247.7
120.00		1.00	1.32	32.627	35.89	320.49	0.650	0.000	5.00	14.084	9.15	525.7	0.0	401.4
125.00		1.00	1.33	32.909	36.20	310.29	0.650	0.000	5.00	13.586	8.83	511.5	0.0	387.1
127.00	Appurtenance(s)	1.00	1.33	33.019	36.32	306.17	0.650	0.000	2.00	5.295	3.44	200.0	0.0	150.8
130.00		1.00	1.34	33.182	36.50	299.94	0.650	0.000	3.00	7.793	5.07	295.8	0.0	222.0
135.00		1.00	1.35	33.446	36.79	289.46	0.650	0.000	5.00	12.590	8.18	481.7	0.0	358.5
137.00	Appurtenance(s)	1.00	1.35	33.550	36.90	285.23	0.650	0.000	2.00	4.897	3.18	187.9	0.0	139.4
140.00		1.00	1.36	33.703	37.07	278.85	0.650	0.000	3.00	7.196	4.68	277.4	0.0	204.8
145.00		1.00	1.37	33.953	37.35	268.12	0.650	0.000	5.00	11.595	7.54	450.4	0.0	329.9
148.00	Appurtenance(s)	1.00	1.37	34.100	37.51	261.62	0.650	0.000	3.00	6.718	4.37	262.1	0.0	191.1
149.00		1.00	1.38	34.148	37.56	259.45	0.650	0.000	1.00	2.199	1.43	85.9	0.0	62.6
<b>Totals:</b>									<b>149.00</b>			<b>17,169.1</b>		<b>24,050.1</b>

## Discrete Appurtenance Forces

<b>Structure:</b> CT11559-A-SBA	<b>Code:</b> EIA/TIA-222-G	8/18/2021
<b>Site Name:</b> Thompson 1, CT	<b>Exposure:</b> C	
<b>Height:</b> 149.00 (ft)	<b>Crest Height:</b> 0.00	
<b>Base Elev:</b> 0.000 (ft)	<b>Site Class:</b> D - Stiff Soil	
<b>Gh:</b> 1.1	<b>Topography:</b> 1	<b>Struct Class:</b> II




Page: 14

**Load Case:** 0.9D + 1.6W 101 mph Wind

**Dead Load Factor** 0.90

**Wind Load Factor** 1.60



**Iterations** 22

No.	Elev (ft)	Description	Qty	qz (psf)	qzGh (psf)	Orient Factor	x Ka	Ka	Total CaAa (sf)	Dead Load (lb)	Horiz Ecc (ft)	Vert Ecc (ft)	Wind FX (lb)	Mom Y (lb-ft)	Mom Z (lb-ft)
1	148.00	T-Arms	1	34.100	37.510	0.56	0.75	8.44	450.00	0.000	0.000	506.38	0.00	0.00	
2	148.00	4449	3	34.100	37.510	0.54	0.80	2.65	189.00	0.000	0.000	159.23	0.00	0.00	
3	148.00	HRK12 (Handrail Kit)	1	34.100	37.510	0.56	0.75	3.80	235.55	0.000	0.000	227.87	0.00	0.00	
4	148.00	(3) Stabilizer Kit (4' FW)	1	34.100	37.510	0.56	0.75	2.08	126.00	0.000	0.000	124.91	0.00	0.00	
5	148.00	Ericsson KRY112 144/1	3	34.100	37.510	0.56	0.80	0.69	29.70	0.000	0.000	41.34	0.00	0.00	
6	148.00	AIR21 B2A B4P	3	34.100	37.510	0.69	0.80	12.57	247.05	0.000	0.000	754.39	0.00	0.00	
7	148.00	AIR21 B2A B4P	3	34.100	37.510	0.69	0.80	12.57	244.08	0.000	0.000	754.39	0.00	0.00	
8	148.00	APXVAARR24_43-U-NA2	3	34.100	37.510	0.56	0.80	34.00	345.60	0.000	0.000	2040.73	0.00	0.00	
9	137.00	T-Arms	3	33.550	36.905	0.56	0.75	13.50	945.00	0.000	0.000	797.15	0.00	0.00	
10	137.00	RCMDC-6627-PF-48	1	33.550	36.905	1.00	1.00	4.06	28.80	0.000	0.000	239.73	0.00	0.00	
11	137.00	Commscope	3	33.550	36.905	0.40	0.80	1.60	52.38	0.000	0.000	94.24	0.00	0.00	
12	137.00	Samsung RFV01U-D2A	3	33.550	36.905	0.54	0.80	3.02	189.81	0.000	0.000	178.50	0.00	0.00	
13	137.00	Samsung RFV01U-D1A	3	33.550	36.905	0.54	0.80	3.02	227.88	0.000	0.000	178.50	0.00	0.00	
14	137.00	91900314	3	33.550	36.905	1.00	1.00	0.00	75.60	0.000	0.000	0.00	0.00	0.00	
15	137.00	Samsung MT6407-77A	3	33.550	36.905	0.56	0.80	7.88	235.17	0.000	0.000	465.25	0.00	0.00	
16	137.00	JMA Wireless	6	33.550	36.905	0.70	0.80	41.22	324.00	0.000	0.000	2433.79	0.00	0.00	
17	127.00	T-Arms	3	33.019	36.321	0.56	0.75	13.50	945.00	0.000	0.000	784.53	0.00	0.00	
18	127.00	7770.00	6	33.019	36.321	0.58	0.80	19.27	189.00	0.000	0.000	1119.96	0.00	0.00	
19	127.00	Powerwave LGP21401	12	33.019	36.321	0.80	0.80	12.38	152.28	0.000	0.000	719.67	0.00	0.00	
20	127.00	Kathrein 860 10025 RET	12	33.019	36.321	0.80	0.80	1.34	11.88	0.000	0.000	78.10	0.00	0.00	
21	127.00	Powerwave LGP13519	6	33.019	36.321	0.80	0.80	1.63	28.62	0.000	0.000	94.84	0.00	0.00	
22	127.00	Raycap DC6-48-60-18-8F	1	33.019	36.321	1.00	1.00	0.92	28.62	0.000	0.000	53.46	0.00	0.00	
23	127.00	Powerwave 1001983 Bias	3	33.019	36.321	0.80	0.80	0.50	11.88	0.000	0.000	29.29	0.00	0.00	
24	127.00	(3) Stabilizer Kit	1	33.019	36.321	0.56	0.75	3.43	162.00	0.000	0.000	199.40	0.00	0.00	
25	127.00	OPA65R-BU8DA	3	33.019	36.321	0.58	0.80	31.56	206.55	0.000	0.000	1834.25	0.00	0.00	
26	127.00	DMP65R-BU8DA	3	33.019	36.321	0.58	0.80	31.18	258.39	0.000	0.000	1811.95	0.00	0.00	
27	127.00	Horizontal Pipe	3	33.019	36.321	0.56	0.75	5.01	123.53	0.000	0.000	291.14	0.00	0.00	
28	127.00	RRUS 4478 B14	3	33.019	36.321	0.54	0.80	2.65	160.38	0.000	0.000	154.19	0.00	0.00	
29	127.00	4449 B5/B12	3	33.019	36.321	0.54	0.80	3.17	191.70	0.000	0.000	184.09	0.00	0.00	
30	127.00	RRUS 8843 B2 B66A	3	33.019	36.321	0.54	0.80	2.64	194.40	0.000	0.000	153.25	0.00	0.00	
31	127.00	DC9-48-60-24-8C-EV	1	33.019	36.321	1.00	1.00	1.14	23.58	0.000	0.000	66.25	0.00	0.00	

**Totals: 6,633.42 16,570.79**

## Total Applied Force Summary

<b>Structure:</b> CT11559-A-SBA	<b>Code:</b> EIA/TIA-222-G	8/18/2021
<b>Site Name:</b> Thompson 1, CT	<b>Exposure:</b> C	
<b>Height:</b> 149.00 (ft)	<b>Crest Height:</b> 0.00	
<b>Base Elev:</b> 0.000 (ft)	<b>Site Class:</b> D - Stiff Soil	
<b>Gh:</b> 1.1	<b>Topography:</b> 1	<b>Struct Class:</b> II




Page: 15

**Load Case:** 0.9D + 1.6W 101 mph Wind

**Dead Load Factor** 0.90

**Wind Load Factor** 1.60



**Iterations** 22

Elev (ft)	Description	Lateral FX (-) (lb)	Axial FY (-) (lb)	Torsion MY (lb-ft)	Moment MZ (lb-ft)
0.00		0.00	0.00	0.00	0.00
5.00		596.83	1408.47	0.00	0.00
10.00		584.82	1383.46	0.00	0.00
15.00		572.81	1358.44	0.00	0.00
18.00		350.69	803.05	0.00	0.00
20.00		239.73	931.07	0.00	0.00
25.00		618.82	2295.16	0.00	0.00
30.00		629.15	1139.78	0.00	0.00
35.00		635.57	1118.33	0.00	0.00
40.00		638.95	1096.89	0.00	0.00
45.00		639.87	1075.45	0.00	0.00
50.00		638.77	1054.00	0.00	0.00
55.00		635.95	1032.56	0.00	0.00
60.00		631.65	1011.12	0.00	0.00
62.00		249.88	398.44	0.00	0.00
65.00		378.88	1002.95	0.00	0.00
68.00		376.56	988.80	0.00	0.00
70.00		249.26	336.41	0.00	0.00
75.00		620.48	828.51	0.00	0.00
80.00		611.91	810.64	0.00	0.00
85.00		602.49	792.77	0.00	0.00
90.00		592.29	774.90	0.00	0.00
95.00		581.38	757.03	0.00	0.00
100.00		569.81	739.16	0.00	0.00
105.00		557.63	721.29	0.00	0.00
107.00		218.86	283.51	0.00	0.00
110.00		329.39	676.19	0.00	0.00
112.00		216.76	444.36	0.00	0.00
115.00		321.44	352.39	0.00	0.00
120.00		525.68	575.87	0.00	0.00
125.00		511.48	561.58	0.00	0.00
127.00	(63) attachments	7774.39	2908.43	0.00	0.00
130.00		295.83	292.66	0.00	0.00
135.00		481.74	476.33	0.00	0.00
137.00	(25) attachments	4575.11	2265.17	0.00	0.00
140.00		277.45	241.65	0.00	0.00
145.00		450.37	391.31	0.00	0.00
148.00	(18) attachments	4871.31	2094.90	0.00	0.00
149.00		85.92	62.55	0.00	0.00
	<b>Totals:</b>	<b>33,739.92</b>	<b>35,485.58</b>	<b>0.00</b>	<b>0.00</b>



## Calculated Forces

<b>Structure:</b> CT11559-A-SBA	<b>Code:</b> EIA/TIA-222-G	8/18/2021
<b>Site Name:</b> Thompson 1, CT	<b>Exposure:</b> C	
<b>Height:</b> 149.00 (ft)	<b>Crest Height:</b> 0.00	
<b>Base Elev:</b> 0.000 (ft)	<b>Site Class:</b> D - Stiff Soil	
<b>Gh:</b> 1.1	<b>Topography:</b> 1	<b>Struct Class:</b> II



Page: 16

**Load Case:** 0.9D + 1.6W 101 mph Wind

**Iterations** 22

**Dead Load Factor** 0.90  
**Wind Load Factor** 1.60



Seg Elev (ft)	Pu FY (-) (kips)	Vu FX (-) (kips)	Tu MY (-) (ft-kips)	Mu MZ (ft-kips)	Mu MX (ft-kips)	Resultant Moment (ft-kips)	phi Pn (kips)	phi Vn (kips)	phi Tn (ft-kips)	phi Mn (ft-kips)	Total Deflect (in)	Rotation Sway (deg)	Rotation Twist (deg)	Stress Ratio
0.00	-35.44	-33.78	0.00	-3574.6	0.00	3574.60	5499.39	2749.69	13252.7	6636.23	0.00	0.000	0.000	0.545
5.00	-33.95	-33.27	0.00	-3405.6	0.00	3405.69	5429.06	2714.53	12818.7	6418.90	0.08	-0.140	0.000	0.537
10.00	-32.49	-32.76	0.00	-3239.3	0.00	3239.35	5357.09	2678.54	12387.8	6203.11	0.30	-0.283	0.000	0.528
15.00	-31.07	-32.24	0.00	-3075.5	0.00	3075.55	5283.48	2641.74	11960.1	5988.97	0.67	-0.426	0.000	0.520
18.00	-30.23	-31.92	0.00	-2978.8	0.00	2978.82	5238.53	2619.26	11705.2	5861.33	0.97	-0.514	0.000	0.514
20.00	-29.24	-31.73	0.00	-2914.9	0.00	2914.98	5208.23	2604.11	11536.0	5776.60	1.20	-0.574	0.000	0.510
25.00	-26.88	-31.15	0.00	-2756.3	0.00	2756.34	4201.23	2100.61	9252.96	4633.35	1.88	-0.720	0.000	0.602
30.00	-25.66	-30.58	0.00	-2600.5	0.00	2600.59	4145.44	2072.72	8928.09	4470.68	2.71	-0.868	0.000	0.588
35.00	-24.47	-29.99	0.00	-2447.7	0.00	2447.70	4088.00	2044.00	8605.21	4309.00	3.71	-1.035	0.000	0.574
40.00	-23.30	-29.40	0.00	-2297.7	0.00	2297.73	4028.93	2014.47	8284.56	4148.44	4.89	-1.202	0.000	0.560
45.00	-22.15	-28.80	0.00	-2150.7	0.00	2150.71	3968.22	1984.11	7966.37	3989.11	6.24	-1.370	0.000	0.545
50.00	-21.03	-28.20	0.00	-2006.7	0.00	2006.70	3905.86	1952.93	7650.88	3831.13	7.76	-1.539	0.000	0.529
55.00	-19.93	-27.60	0.00	-1865.6	0.00	1865.69	3841.87	1920.93	7338.34	3674.63	9.46	-1.708	0.000	0.513
60.00	-18.89	-26.97	0.00	-1727.7	0.00	1727.72	3776.23	1888.12	7028.98	3519.72	11.34	-1.877	0.000	0.496
62.00	-18.46	-26.74	0.00	-1673.7	0.00	1673.78	3749.52	1874.76	6906.19	3458.23	12.14	-1.946	0.000	0.489
65.00	-17.42	-26.35	0.00	-1593.5	0.00	1593.57	3708.96	1854.48	6723.05	3366.52	13.40	-2.049	0.000	0.478
68.00	-16.41	-25.97	0.00	-1514.5	0.00	1514.51	2897.69	1448.84	5257.67	2632.74	14.72	-2.151	0.000	0.581
70.00	-16.02	-25.74	0.00	-1462.5	0.00	1462.58	2878.95	1439.48	5167.56	2587.62	15.64	-2.220	0.000	0.571
75.00	-15.14	-25.14	0.00	-1333.8	0.00	1333.88	2830.96	1415.48	4943.48	2475.42	18.07	-2.411	0.000	0.545
80.00	-14.27	-24.54	0.00	-1208.2	0.00	1208.20	2781.33	1390.66	4721.30	2364.16	20.69	-2.599	0.000	0.516
85.00	-13.43	-23.94	0.00	-1085.5	0.00	1085.52	2730.06	1365.03	4501.25	2253.97	23.51	-2.784	0.000	0.487
90.00	-12.62	-23.35	0.00	-965.81	0.00	965.81	2677.14	1338.57	4283.57	2144.97	26.53	-2.964	0.000	0.455
95.00	-11.82	-22.76	0.00	-849.07	0.00	849.07	2622.59	1311.30	4068.50	2037.27	29.72	-3.138	0.000	0.422
100.00	-11.06	-22.18	0.00	-735.25	0.00	735.25	2566.40	1283.20	3856.28	1931.01	33.10	-3.305	0.000	0.385
105.00	-10.33	-21.61	0.00	-624.33	0.00	624.33	2508.57	1254.28	3647.16	1826.29	36.65	-3.463	0.000	0.346
107.00	-10.03	-21.38	0.00	-581.12	0.00	581.12	2484.97	1242.49	3564.43	1784.86	38.11	-3.524	0.000	0.330
110.00	-9.35	-21.02	0.00	-516.97	0.00	516.97	2449.09	1224.55	3441.37	1723.24	40.35	-3.612	0.000	0.304
112.00	-8.90	-20.79	0.00	-474.92	0.00	474.92	1823.39	911.69	2573.73	1288.78	41.88	-3.668	0.000	0.374
115.00	-8.53	-20.46	0.00	-412.55	0.00	412.55	1799.96	899.98	2488.04	1245.87	44.21	-3.747	0.000	0.336
120.00	-7.94	-19.92	0.00	-310.24	0.00	310.24	1759.59	879.80	2346.51	1175.00	48.21	-3.882	0.000	0.269
125.00	-7.40	-19.38	0.00	-210.66	0.00	210.66	1717.59	858.79	2206.80	1105.04	52.33	-3.990	0.000	0.195
127.00	-5.03	-11.42	0.00	-171.91	0.00	171.91	1700.33	850.16	2151.49	1077.34	54.01	-4.025	0.000	0.163
130.00	-4.75	-11.11	0.00	-137.65	0.00	137.65	1673.94	836.97	2069.17	1036.12	56.55	-4.070	0.000	0.136
135.00	-4.30	-10.60	0.00	-82.10	0.00	82.10	1628.66	814.33	1933.84	968.36	60.85	-4.128	0.000	0.088
137.00	-2.37	-5.87	0.00	-60.90	0.00	60.90	1610.09	805.04	1880.41	941.60	62.58	-4.144	0.000	0.066
140.00	-2.15	-5.58	0.00	-43.29	0.00	43.29	1581.73	790.87	1801.05	901.87	65.19	-4.164	0.000	0.049
145.00	-1.79	-5.10	0.00	-15.39	0.00	15.39	1533.17	766.58	1671.06	836.77	69.56	-4.183	0.000	0.020
148.00	-0.06	-0.09	0.00	-0.09	0.00	0.09	1503.24	751.62	1594.49	798.43	72.18	-4.187	0.000	0.000
149.00	0.00	-0.09	0.00	0.00	0.00	0.00	1493.13	746.57	1569.22	785.78	73.06	-4.187	0.000	0.000

## Wind Loading - Shaft

<b>Structure:</b> CT11559-A-SBA	<b>Code:</b> EIA/TIA-222-G	8/18/2021
<b>Site Name:</b> Thompson 1, CT	<b>Exposure:</b> C	
<b>Height:</b> 149.00 (ft)	<b>Crest Height:</b> 0.00	
<b>Base Elev:</b> 0.000 (ft)	<b>Site Class:</b> D - Stiff Soil	
<b>Gh:</b> 1.1	<b>Topography:</b> 1	<b>Struct Class:</b> II



Page: 17

**Load Case:** 1.2D + 1.0Di + 1.0Wi 50 mph Wind

**Iterations** 22

**Dead Load Factor** 1.20

**Wind Load Factor** 1.00



Elev (ft)	Description	Kzt	Kz	qz (psf)	qzGh (psf)	C (mph-ft)	Cf	Ice Thick (in)	Tributary (ft)	Aa (sf)	CfAa (sf)	Wind Force X (lb)	Dead Load Ice (lb)	Tot Dead Load (lb)
0.00		1.00	0.85	5.168	5.68	0.00	1.200	0.000	0.00	0.000	0.00	0.0	0.0	0.0
5.00		1.00	0.85	5.168	5.68	0.00	1.200	1.656	5.00	26.120	31.34	178.2	617.7	2263.0
10.00		1.00	0.85	5.168	5.68	0.00	1.200	1.775	5.00	25.721	30.87	175.5	650.2	2262.2
15.00		1.00	0.85	5.168	5.68	0.00	1.200	1.848	5.00	25.285	30.34	172.5	664.3	2243.0
18.00	Bot - Section 2	1.00	0.88	5.363	5.90	0.00	1.200	1.882	3.00	14.949	17.94	105.8	401.2	1332.3
20.00		1.00	0.90	5.483	6.03	0.00	1.200	1.902	2.00	10.000	12.00	72.4	271.7	1420.1
25.00	Top - Section 1	1.00	0.95	5.747	6.32	0.00	1.200	1.945	5.00	24.687	29.62	187.3	680.8	3508.4
30.00		1.00	0.98	5.972	6.57	0.00	1.200	1.981	5.00	24.219	29.06	190.9	679.1	1966.2
35.00		1.00	1.01	6.169	6.79	0.00	1.200	2.012	5.00	23.747	28.50	193.4	675.2	1933.7
40.00		1.00	1.04	6.345	6.98	0.00	1.200	2.039	5.00	23.272	27.93	194.9	669.6	1899.5
45.00		1.00	1.07	6.504	7.15	0.00	1.200	2.063	5.00	22.794	27.35	195.7	662.6	1863.9
50.00		1.00	1.09	6.650	7.32	0.00	1.200	2.085	5.00	22.315	26.78	195.9	654.6	1827.3
55.00		1.00	1.12	6.785	7.46	0.00	1.200	2.105	5.00	21.833	26.20	195.5	645.6	1789.7
60.00		1.00	1.14	6.910	7.60	0.00	1.200	2.123	5.00	21.351	25.62	194.8	635.8	1751.3
62.00	Bot - Section 3	1.00	1.14	6.958	7.65	0.00	1.200	2.130	2.00	8.403	10.08	77.2	252.7	690.9
65.00		1.00	1.16	7.028	7.73	0.00	1.200	2.140	3.00	12.619	15.14	117.1	380.2	1577.9
68.00	Top - Section 2	1.00	1.17	7.095	7.80	0.00	1.200	2.150	3.00	12.445	14.93	116.5	376.3	1555.2
70.00		1.00	1.17	7.138	7.85	0.00	1.200	2.156	2.00	8.199	9.84	77.3	249.1	604.6
75.00		1.00	1.19	7.243	7.97	0.00	1.200	2.171	5.00	20.162	24.19	192.8	611.3	1483.3
80.00		1.00	1.21	7.342	8.08	0.00	1.200	2.185	5.00	19.676	23.61	190.7	599.3	1447.5
85.00		1.00	1.22	7.436	8.18	0.00	1.200	2.198	5.00	19.189	23.03	188.4	586.9	1411.3
90.00		1.00	1.24	7.526	8.28	0.00	1.200	2.211	5.00	18.702	22.44	185.8	574.1	1374.7
95.00		1.00	1.25	7.612	8.37	0.00	1.200	2.223	5.00	18.214	21.86	183.0	561.0	1337.8
100.00		1.00	1.27	7.695	8.46	0.00	1.200	2.234	5.00	17.726	21.27	180.0	547.6	1300.5
105.00		1.00	1.28	7.774	8.55	0.00	1.200	2.245	5.00	17.237	20.68	176.9	533.9	1263.0
107.00	Bot - Section 4	1.00	1.28	7.805	8.59	0.00	1.200	2.250	2.00	6.757	8.11	69.6	211.3	496.3
110.00		1.00	1.29	7.851	8.64	0.00	1.200	2.256	3.00	10.116	12.14	104.8	316.2	1078.2
112.00	Top - Section 3	1.00	1.30	7.881	8.67	0.00	1.200	2.260	2.00	6.646	7.97	69.1	208.5	707.9
115.00		1.00	1.30	7.925	8.72	0.00	1.200	2.266	3.00	9.822	11.79	102.7	307.6	637.9
120.00		1.00	1.32	7.996	8.80	0.00	1.200	2.276	5.00	15.980	19.18	168.7	498.3	1033.5
125.00		1.00	1.33	8.065	8.87	0.00	1.200	2.285	5.00	15.490	18.59	164.9	483.6	999.7
127.00	Appurtenance(s)	1.00	1.33	8.092	8.90	0.00	1.200	2.289	2.00	6.058	7.27	64.7	191.1	392.2
130.00		1.00	1.34	8.132	8.95	0.00	1.200	2.294	3.00	8.940	10.73	96.0	281.2	577.2
135.00		1.00	1.35	8.197	9.02	0.00	1.200	2.303	5.00	14.509	17.41	157.0	453.6	931.6
137.00	Appurtenance(s)	1.00	1.35	8.222	9.04	0.00	1.200	2.306	2.00	5.665	6.80	61.5	179.0	364.9
140.00		1.00	1.36	8.260	9.09	0.00	1.200	2.311	3.00	8.351	10.02	91.1	263.0	536.1
145.00		1.00	1.37	8.321	9.15	0.00	1.200	2.319	5.00	13.527	16.23	148.6	422.9	862.8
148.00	Appurtenance(s)	1.00	1.37	8.357	9.19	0.00	1.200	2.324	3.00	7.880	9.46	86.9	248.1	502.9
149.00		1.00	1.38	8.369	9.21	0.00	1.200	2.325	1.00	2.587	3.10	28.6	82.1	165.5
<b>Totals:</b>									<b>149.00</b>				<b>5,352.5</b>	<b>49,394.0</b>


## Discrete Appurtenance Forces

<b>Structure:</b> CT11559-A-SBA	<b>Code:</b> EIA/TIA-222-G	8/18/2021	
<b>Site Name:</b> Thompson 1, CT	<b>Exposure:</b> C		
<b>Height:</b> 149.00 (ft)	<b>Crest Height:</b> 0.00		
<b>Base Elev:</b> 0.000 (ft)	<b>Site Class:</b> D - Stiff Soil		
<b>Gh:</b> 1.1	<b>Topography:</b> 1	<b>Struct Class:</b> II	Page: 18



**Load Case:** 1.2D + 1.0Di + 1.0Wi 50 mph Wind

**Dead Load Factor** 1.20  
**Wind Load Factor** 1.00



**Iterations** 22

No.	Elev (ft)	Description	Qty	qz (psf)	qzGh (psf)	Orient Factor	x Ka	Ka	Total CaAa (sf)	Dead Load (lb)	Horiz Ecc (ft)	Vert Ecc (ft)	Wind FX (lb)	Mom Y (lb-ft)	Mom Z (lb-ft)
1	148.00	T-Arms	1	8.357	9.193	0.56	0.75	0.75	23.08	1147.15	0.000	0.000	212.15	0.00	0.00
2	148.00	4449	3	8.357	9.193	0.54	0.80	0.80	3.85	548.48	0.000	0.000	35.36	0.00	0.00
3	148.00	HRK12 (Handrail Kit)	1	8.357	9.193	0.56	0.75	0.75	8.74	314.06	0.000	0.000	80.33	0.00	0.00
4	148.00	(3) Stabilizer Kit (4' FW)	1	8.357	9.193	0.56	0.75	0.75	4.98	342.24	0.000	0.000	45.81	0.00	0.00
5	148.00	Ericsson KRY112 144/1	3	8.357	9.193	0.56	0.80	0.80	1.75	73.37	0.000	0.000	16.10	0.00	0.00
6	148.00	AIR21 B2A B4P	3	8.357	9.193	0.69	0.80	0.80	15.65	1048.04	0.000	0.000	143.88	0.00	0.00
7	148.00	AIR21 B2A B4P	3	8.357	9.193	0.69	0.80	0.80	15.65	1044.08	0.000	0.000	143.88	0.00	0.00
8	148.00	APXVAARR24_43-U-NA2	3	8.357	9.193	0.56	0.80	0.80	38.31	2201.32	0.000	0.000	352.14	0.00	0.00
9	137.00	T-Arms	3	8.222	9.044	0.56	0.75	0.75	29.07	2018.50	0.000	0.000	262.88	0.00	0.00
10	137.00	RCMDC-6627-PF-48	1	8.222	9.044	1.00	1.00	1.00	5.15	163.73	0.000	0.000	46.54	0.00	0.00
11	137.00	Commscope	3	8.222	9.044	0.40	0.80	0.80	2.97	153.61	0.000	0.000	26.82	0.00	0.00
12	137.00	Samsung RFV01U-D2A	3	8.222	9.044	0.54	0.80	0.80	4.19	411.06	0.000	0.000	37.93	0.00	0.00
13	137.00	Samsung RFV01U-D1A	3	8.222	9.044	0.54	0.80	0.80	4.19	401.43	0.000	0.000	37.93	0.00	0.00
14	137.00	91900314	3	8.222	9.044	1.00	1.00	1.00	0.00	182.78	0.000	0.000	0.00	0.00	0.00
15	137.00	Samsung MT6407-77A	3	8.222	9.044	0.56	0.80	0.80	10.01	819.99	0.000	0.000	90.57	0.00	0.00
16	137.00	JMA Wireless	6	8.222	9.044	0.70	0.80	0.80	48.94	2670.47	0.000	0.000	442.65	0.00	0.00
17	127.00	T-Arms	3	8.092	8.901	0.56	0.75	0.75	28.95	2011.19	0.000	0.000	257.67	0.00	0.00
18	127.00	7770.00	6	8.092	8.901	0.58	0.80	0.80	24.27	1392.01	0.000	0.000	216.00	0.00	0.00
19	127.00	Powerwave LGP21401	12	8.092	8.901	0.80	0.80	0.80	22.90	511.26	0.000	0.000	203.88	0.00	0.00
20	127.00	Kathrein 860 10025 RET	12	8.092	8.901	0.80	0.80	0.80	5.38	70.03	0.000	0.000	47.93	0.00	0.00
21	127.00	Powerwave LGP13519	6	8.092	8.901	0.80	0.80	0.80	4.49	96.69	0.000	0.000	39.97	0.00	0.00
22	127.00	Raycap DC6-48-60-18-8F	1	8.092	8.901	1.00	1.00	1.00	1.49	101.53	0.000	0.000	13.30	0.00	0.00
23	127.00	Powerwave 1001983 Bias	3	8.092	8.901	0.80	0.80	0.80	1.64	33.22	0.000	0.000	14.61	0.00	0.00
24	127.00	(3) Stabilizer Kit	1	8.092	8.901	0.56	0.75	0.75	8.14	442.60	0.000	0.000	72.48	0.00	0.00
25	127.00	OPA65R-BU8DA	3	8.092	8.901	0.60	0.80	0.80	38.65	1439.68	0.000	0.000	344.05	0.00	0.00
26	127.00	DMP65R-BU8DA	3	8.092	8.901	0.60	0.80	0.80	36.83	1588.13	0.000	0.000	327.81	0.00	0.00
27	127.00	Horizontal Pipe	3	8.092	8.901	0.56	0.75	0.75	13.26	297.85	0.000	0.000	118.07	0.00	0.00
28	127.00	RRUS 4478 B14	3	8.092	8.901	0.54	0.80	0.80	3.75	348.77	0.000	0.000	33.35	0.00	0.00
29	127.00	4449 B5/B12	3	8.092	8.901	0.54	0.80	0.80	4.32	424.80	0.000	0.000	38.47	0.00	0.00
30	127.00	RRUS 8843 B2 B66A	3	8.092	8.901	0.54	0.80	0.80	3.68	407.48	0.000	0.000	32.80	0.00	0.00
31	127.00	DC9-48-60-24-8C-EV	1	8.092	8.901	1.00	1.00	1.00	3.22	153.33	0.000	0.000	28.67	0.00	0.00
<b>Totals:</b>									<b>22,858.86</b>				<b>3,764.03</b>		

## Total Applied Force Summary

<b>Structure:</b> CT11559-A-SBA	<b>Code:</b> EIA/TIA-222-G	8/18/2021
<b>Site Name:</b> Thompson 1, CT	<b>Exposure:</b> C	
<b>Height:</b> 149.00 (ft)	<b>Crest Height:</b> 0.00	
<b>Base Elev:</b> 0.000 (ft)	<b>Site Class:</b> D - Stiff Soil	
<b>Gh:</b> 1.1	<b>Topography:</b> 1	<b>Struct Class:</b> II



Page: 19

**Load Case:** 1.2D + 1.0Di + 1.0Wi 50 mph Wind

**Dead Load Factor** 1.20

**Wind Load Factor** 1.00



**Iterations** 22

Elev (ft)	Description	Lateral FX (-) (lb)	Axial FY (-) (lb)	Torsion MY (lb-ft)	Moment MZ (lb-ft)
0.00		0.00	0.00	0.00	0.00
5.00		178.19	2495.63	0.00	0.00
10.00		175.47	2494.82	0.00	0.00
15.00		172.49	2475.57	0.00	0.00
18.00		105.83	1471.91	0.00	0.00
20.00		72.38	1513.13	0.00	0.00
25.00		187.29	3740.97	0.00	0.00
30.00		190.92	2198.82	0.00	0.00
35.00		193.38	2166.33	0.00	0.00
40.00		194.91	2132.12	0.00	0.00
45.00		195.70	2096.56	0.00	0.00
50.00		195.88	2059.89	0.00	0.00
55.00		195.54	2022.31	0.00	0.00
60.00		194.76	1983.95	0.00	0.00
62.00		77.18	783.93	0.00	0.00
65.00		117.07	1717.51	0.00	0.00
68.00		116.55	1694.73	0.00	0.00
70.00		77.26	697.64	0.00	0.00
75.00		192.76	1715.93	0.00	0.00
80.00		190.68	1680.14	0.00	0.00
85.00		188.35	1643.93	0.00	0.00
90.00		185.79	1607.34	0.00	0.00
95.00		183.02	1570.40	0.00	0.00
100.00		180.04	1533.14	0.00	0.00
105.00		176.89	1495.59	0.00	0.00
107.00		69.62	589.34	0.00	0.00
110.00		104.83	1217.75	0.00	0.00
112.00		69.13	800.99	0.00	0.00
115.00		102.75	777.48	0.00	0.00
120.00		168.67	1266.09	0.00	0.00
125.00		164.91	1232.35	0.00	0.00
127.00	(63) attachments	1853.77	9803.78	0.00	0.00
130.00		95.96	671.43	0.00	0.00
135.00		156.99	1088.72	0.00	0.00
137.00	(25) attachments	1006.81	7249.29	0.00	0.00
140.00		91.05	585.21	0.00	0.00
145.00		148.58	944.65	0.00	0.00
148.00	(18) attachments	1116.57	7270.78	0.00	0.00
149.00		28.58	165.49	0.00	0.00
Totals:		9,116.52	78,655.66	0.00	0.00

## Calculated Forces

<b>Structure:</b> CT11559-A-SBA	<b>Code:</b> EIA/TIA-222-G	8/18/2021
<b>Site Name:</b> Thompson 1, CT	<b>Exposure:</b> C	
<b>Height:</b> 149.00 (ft)	<b>Crest Height:</b> 0.00	
<b>Base Elev:</b> 0.000 (ft)	<b>Site Class:</b> D - Stiff Soil	
<b>Gh:</b> 1.1	<b>Topography:</b> 1	<b>Struct Class:</b> II




Page: 20

**Load Case:** 1.2D + 1.0Di + 1.0Wi 50 mph Wind

**Iterations** 22

**Dead Load Factor** 1.20  
**Wind Load Factor** 1.00



Seg Elev (ft)	Pu FY (-) (kips)	Vu FX (-) (kips)	Tu MY (-) (ft-kips)	Mu MZ (ft-kips)	Mu MX (ft-kips)	Resultant Moment (ft-kips)	phi Pn (kips)	phi Vn (kips)	phi Tn (ft-kips)	phi Mn (ft-kips)	Total Deflect (in)	Rotation Sway (deg)	Rotation Twist (deg)	Stress Ratio
0.00	-78.65	-9.14	0.00	-961.82	0.00	961.82	5499.39	2749.69	13252.7	6636.23	0.00	0.000	0.000	0.159
5.00	-76.15	-9.01	0.00	-916.10	0.00	916.10	5429.06	2714.53	12818.7	6418.90	0.02	-0.038	0.000	0.157
10.00	-73.65	-8.89	0.00	-871.03	0.00	871.03	5357.09	2678.54	12387.8	6203.11	0.08	-0.076	0.000	0.154
15.00	-71.17	-8.75	0.00	-826.61	0.00	826.61	5283.48	2641.74	11960.1	5988.97	0.18	-0.115	0.000	0.152
18.00	-69.70	-8.66	0.00	-800.36	0.00	800.36	5238.53	2619.26	11705.2	5861.33	0.26	-0.138	0.000	0.150
20.00	-68.18	-8.62	0.00	-783.04	0.00	783.04	5208.23	2604.11	11536.0	5776.60	0.32	-0.154	0.000	0.149
25.00	-64.43	-8.47	0.00	-739.94	0.00	739.94	4201.23	2100.61	9252.96	4633.35	0.51	-0.194	0.000	0.175
30.00	-62.23	-8.31	0.00	-697.62	0.00	697.62	4145.44	2072.72	8928.09	4470.68	0.73	-0.233	0.000	0.171
35.00	-60.06	-8.16	0.00	-656.06	0.00	656.06	4088.00	2044.00	8605.21	4309.00	1.00	-0.278	0.000	0.167
40.00	-57.92	-8.00	0.00	-615.28	0.00	615.28	4028.93	2014.47	8284.56	4148.44	1.31	-0.323	0.000	0.163
45.00	-55.82	-7.83	0.00	-575.30	0.00	575.30	3968.22	1984.11	7966.37	3989.11	1.68	-0.368	0.000	0.158
50.00	-53.75	-7.66	0.00	-536.15	0.00	536.15	3905.86	1952.93	7650.88	3831.13	2.08	-0.413	0.000	0.154
55.00	-51.73	-7.49	0.00	-497.84	0.00	497.84	3841.87	1920.93	7338.34	3674.63	2.54	-0.458	0.000	0.149
60.00	-49.74	-7.31	0.00	-460.37	0.00	460.37	3776.23	1888.12	7028.98	3519.72	3.05	-0.503	0.000	0.144
62.00	-48.95	-7.24	0.00	-445.75	0.00	445.75	3749.52	1874.76	6906.19	3458.23	3.26	-0.521	0.000	0.142
65.00	-47.23	-7.13	0.00	-424.02	0.00	424.02	3708.96	1854.48	6723.05	3366.52	3.60	-0.549	0.000	0.139
68.00	-45.54	-7.02	0.00	-402.62	0.00	402.62	2897.69	1448.84	5257.67	2632.74	3.95	-0.576	0.000	0.169
70.00	-44.84	-6.96	0.00	-388.58	0.00	388.58	2878.95	1439.48	5167.56	2587.62	4.20	-0.594	0.000	0.166
75.00	-43.12	-6.79	0.00	-353.78	0.00	353.78	2830.96	1415.48	4943.48	2475.42	4.85	-0.645	0.000	0.158
80.00	-41.43	-6.61	0.00	-319.84	0.00	319.84	2781.33	1390.66	4721.30	2364.16	5.55	-0.695	0.000	0.150
85.00	-39.79	-6.44	0.00	-286.77	0.00	286.77	2730.06	1365.03	4501.25	2253.97	6.30	-0.744	0.000	0.142
90.00	-38.18	-6.26	0.00	-254.58	0.00	254.58	2677.14	1338.57	4283.57	2144.97	7.11	-0.791	0.000	0.133
95.00	-36.60	-6.09	0.00	-223.27	0.00	223.27	2622.59	1311.30	4068.50	2037.27	7.96	-0.837	0.000	0.124
100.00	-35.07	-5.91	0.00	-192.85	0.00	192.85	2566.40	1283.20	3856.28	1931.01	8.86	-0.881	0.000	0.114
105.00	-33.57	-5.72	0.00	-163.31	0.00	163.31	2508.57	1254.28	3647.16	1826.29	9.81	-0.922	0.000	0.103
107.00	-32.98	-5.66	0.00	-151.86	0.00	151.86	2484.97	1242.49	3564.43	1784.86	10.20	-0.938	0.000	0.098
110.00	-31.77	-5.54	0.00	-134.89	0.00	134.89	2449.09	1224.55	3441.37	1723.24	10.80	-0.961	0.000	0.091
112.00	-30.97	-5.47	0.00	-123.81	0.00	123.81	1823.39	911.69	2573.73	1288.78	11.20	-0.976	0.000	0.113
115.00	-30.19	-5.37	0.00	-107.40	0.00	107.40	1799.96	899.98	2488.04	1245.87	11.82	-0.996	0.000	0.103
120.00	-28.92	-5.19	0.00	-80.57	0.00	80.57	1759.59	879.80	2346.51	1175.00	12.89	-1.032	0.000	0.085
125.00	-27.69	-5.01	0.00	-54.60	0.00	54.60	1717.59	858.79	2206.80	1105.04	13.98	-1.060	0.000	0.066
127.00	-17.92	-2.98	0.00	-44.58	0.00	44.58	1700.33	850.16	2151.49	1077.34	14.43	-1.069	0.000	0.052
130.00	-17.25	-2.88	0.00	-35.63	0.00	35.63	1673.94	836.97	2069.17	1036.12	15.10	-1.080	0.000	0.045
135.00	-16.17	-2.70	0.00	-21.25	0.00	21.25	1628.66	814.33	1933.84	968.36	16.24	-1.095	0.000	0.032
137.00	-8.94	-1.56	0.00	-15.85	0.00	15.85	1610.09	805.04	1880.41	941.60	16.70	-1.100	0.000	0.022
140.00	-8.35	-1.46	0.00	-11.18	0.00	11.18	1581.73	790.87	1801.05	901.87	17.40	-1.105	0.000	0.018
145.00	-7.41	-1.29	0.00	-3.90	0.00	3.90	1533.17	766.58	1671.06	836.77	18.56	-1.110	0.000	0.009
148.00	-0.16	-0.03	0.00	-0.03	0.00	0.03	1503.24	751.62	1594.49	798.43	19.25	-1.111	0.000	0.000
149.00	0.00	-0.03	0.00	0.00	0.00	0.00	1493.13	746.57	1569.22	785.78	19.49	-1.111	0.000	0.000


## Seismic Segment Forces (Factored)

<b>Structure:</b> CT11559-A-SBA	<b>Code:</b> EIA/TIA-222-G	8/18/2021
<b>Site Name:</b> Thompson 1, CT	<b>Exposure:</b> C	
<b>Height:</b> 149.00 (ft)	<b>Crest Height:</b> 0.00	
<b>Base Elev:</b> 0.000 (ft)	<b>Site Class:</b> D - Stiff Soil	
<b>Gh:</b> 1.1	<b>Topography:</b> 1	<b>Struct Class:</b> II



Page: 21

<b>Load Case:</b> 1.2D + 1.0E				<b>Iterations</b> 20
<b>Gust Response Factor</b>	1.10	<b>Sds</b>	0.18	<b>Ss</b> 0.17
<b>Dead Load Factor</b>	1.20	<b>Seismic Load Factor</b>	1.00	<b>S1</b> 0.06
<b>Wind Load Factor</b>	0.00	<b>Structure Frequency (f1)</b>	0.45	<b>SA</b> 0.05
				<b>Seismic Importance Factor</b> 1.00



Top Elev (ft)	Description	Wz (lb)	a	b	c	Lateral Fs (lb)	R: 1.50
0.00		0.00	0.00	0.00	0.00	0.00	
5.00		1371.1	0.00	0.03	0.02	19.86	
10.00		1343.3	0.01	0.05	0.03	29.20	
15.00		1315.5	0.02	0.06	0.04	33.57	
18.00	Bot - Section 2	775.97	0.03	0.07	0.04	20.85	
20.00		956.99	0.03	0.07	0.04	26.37	
25.00	Top - Section 1	2356.3	0.05	0.07	0.04	67.80	
30.00		1072.5	0.08	0.07	0.04	31.84	
35.00		1048.7	0.10	0.07	0.04	32.00	
40.00		1024.9	0.14	0.07	0.03	32.06	
45.00		1001.0	0.17	0.07	0.03	31.86	
50.00		977.26	0.21	0.06	0.02	31.12	
55.00		953.44	0.26	0.05	0.02	29.49	
60.00		929.61	0.31	0.04	0.01	26.57	
62.00	Bot - Section 3	365.17	0.33	0.04	0.01	9.91	
65.00		998.08	0.36	0.03	0.01	24.32	
68.00	Top - Section 2	982.36	0.39	0.02	0.01	20.44	
70.00		296.24	0.42	0.01	0.01	5.33	
75.00		726.71	0.48	-0.01	0.01	6.99	
80.00		706.86	0.54	-0.03	0.01	-0.02	
85.00		687.00	0.62	-0.06	0.02	-6.62	
90.00		667.15	0.69	-0.08	0.03	-11.76	
95.00		647.29	0.77	-0.11	0.05	-14.59	
100.00		627.44	0.85	-0.12	0.07	-14.66	
105.00		607.58	0.94	-0.12	0.10	-11.85	
107.00	Bot - Section 4	237.47	0.97	-0.12	0.12	-3.94	
110.00		635.01	1.03	-0.10	0.15	-6.79	
112.00	Top - Section 3	416.19	1.07	-0.09	0.17	-2.40	
115.00		275.23	1.13	-0.05	0.20	0.87	
120.00		446.01	1.23	0.03	0.27	9.85	
125.00		430.12	1.33	0.16	0.36	19.85	
127.00	Appurtenance(s)	3154.0	1.37	0.23	0.40	180.48	
130.00		246.64	1.44	0.36	0.47	18.59	
135.00		398.36	1.55	0.64	0.61	43.77	
137.00	Appurtenance(s)	2464.4	1.60	0.77	0.67	308.44	
140.00		227.58	1.67	1.01	0.77	34.06	
145.00		366.59	1.79	1.49	0.96	71.45	
148.00	Appurtenance(s)	2286.7	1.86	1.85	1.09	513.83	
149.00		69.51	1.89	1.98	1.14	16.34	
<b>Totals:</b>		<b>34,092.8</b>				<b>1,624.5</b>	<b>Total Wind: 33,739.9</b>

Seismic Base Shear is Less Than 50% of Wind Force - An Analysis is NOT Required


## Calculated Forces

<b>Structure:</b> CT11559-A-SBA	<b>Code:</b> EIA/TIA-222-G	8/18/2021
<b>Site Name:</b> Thompson 1, CT	<b>Exposure:</b> C	
<b>Height:</b> 149.00 (ft)	<b>Crest Height:</b> 0.00	
<b>Base Elev:</b> 0.000 (ft)	<b>Site Class:</b> D - Stiff Soil	
<b>Gh:</b> 1.1	<b>Topography:</b> 1	<b>Struct Class:</b> II



Page: 22

<b>Load Case:</b> 1.2D + 1.0E						<b>Iterations</b> 20
<b>Gust Response Factor</b>	1.10			<b>Sds</b>	0.18	<b>Ss</b> 0.17
<b>Dead Load Factor</b>	1.20	<b>Seismic Load Factor</b>	1.00	<b>Sd1</b>	0.10	<b>S1</b> 0.06
<b>Wind Load Factor</b>	0.00	<b>Structure Frequency (f1)</b>	0.45	<b>SA</b>	0.05	<b>Seismic Importance Factor</b> 1.00



Seg Elev (ft)	Pu FY (-) (kips)	Vu FX (-) (kips)	Tu MY (-) (ft-kips)	Mu MZ (ft-kips)	Mu MX (ft-kips)	Resultant Moment (ft-kips)	phi Pn (kips)	phi Vn (kips)	phi Tn (ft-kips)	phi Mn (ft-kips)	Total Deflect (in)	Rotation Sway (deg)	Rotation Twist (deg)	Stress Ratio
0.00	-47.31	-1.70	0.00	-194.21	0.00	194.21	5499.39	2749.69	13252.7	6636.23	0.00	0.00	0.00	0.038
5.00	-45.44	-1.69	0.00	-185.71	0.00	185.71	5429.06	2714.53	12818.7	6418.90	0.00	-0.01	0.037	
10.00	-43.59	-1.66	0.00	-177.28	0.00	177.28	5357.09	2678.54	12387.8	6203.11	0.02	-0.02	0.037	
15.00	-41.78	-1.63	0.00	-168.97	0.00	168.97	5283.48	2641.74	11960.1	5988.97	0.04	-0.02	0.036	
18.00	-40.71	-1.61	0.00	-164.08	0.00	164.08	5238.53	2619.26	11705.2	5861.33	0.05	-0.03	0.036	
20.00	-39.47	-1.59	0.00	-160.85	0.00	160.85	5208.23	2604.11	11536.0	5776.60	0.07	-0.03	0.035	
25.00	-36.41	-1.53	0.00	-152.89	0.00	152.89	4201.23	2100.61	9252.96	4633.35	0.10	-0.04	0.042	
30.00	-34.89	-1.50	0.00	-145.26	0.00	145.26	4145.44	2072.72	8928.09	4470.68	0.15	-0.05	0.041	
35.00	-33.40	-1.47	0.00	-137.77	0.00	137.77	4088.00	2044.00	8605.21	4309.00	0.20	-0.06	0.040	
40.00	-31.93	-1.44	0.00	-130.41	0.00	130.41	4028.93	2014.47	8284.56	4148.44	0.27	-0.07	0.039	
45.00	-30.50	-1.41	0.00	-123.20	0.00	123.20	3968.22	1984.11	7966.37	3989.11	0.34	-0.08	0.039	
50.00	-29.09	-1.39	0.00	-116.13	0.00	116.13	3905.86	1952.93	7650.88	3831.13	0.43	-0.09	0.038	
55.00	-27.72	-1.36	0.00	-109.20	0.00	109.20	3841.87	1920.93	7338.34	3674.63	0.52	-0.10	0.037	
60.00	-26.37	-1.33	0.00	-102.41	0.00	102.41	3776.23	1888.12	7028.98	3519.72	0.63	-0.11	0.036	
62.00	-25.84	-1.32	0.00	-99.74	0.00	99.74	3749.52	1874.76	6906.19	3458.23	0.67	-0.11	0.036	
65.00	-24.50	-1.30	0.00	-95.77	0.00	95.77	3708.96	1854.48	6723.05	3366.52	0.74	-0.12	0.035	
68.00	-23.18	-1.28	0.00	-91.87	0.00	91.87	2897.69	1448.84	5257.67	2632.74	0.82	-0.12	0.043	
70.00	-22.73	-1.28	0.00	-89.31	0.00	89.31	2878.95	1439.48	5167.56	2587.62	0.87	-0.13	0.042	
75.00	-21.63	-1.27	0.00	-82.93	0.00	82.93	2830.96	1415.48	4943.48	2475.42	1.01	-0.14	0.041	
80.00	-20.55	-1.27	0.00	-76.57	0.00	76.57	2781.33	1390.66	4721.30	2364.16	1.16	-0.15	0.040	
85.00	-19.49	-1.27	0.00	-70.21	0.00	70.21	2730.06	1365.03	4501.25	2253.97	1.32	-0.16	0.038	
90.00	-18.46	-1.27	0.00	-63.84	0.00	63.84	2677.14	1338.57	4283.57	2144.97	1.50	-0.17	0.037	
95.00	-17.45	-1.28	0.00	-57.46	0.00	57.46	2622.59	1311.30	4068.50	2037.27	1.69	-0.19	0.035	
100.00	-16.46	-1.28	0.00	-51.09	0.00	51.09	2566.40	1283.20	3856.28	1931.01	1.89	-0.20	0.033	
105.00	-15.50	-1.27	0.00	-44.71	0.00	44.71	2508.57	1254.28	3647.16	1826.29	2.10	-0.21	0.031	
107.00	-15.12	-1.27	0.00	-42.17	0.00	42.17	2484.97	1242.49	3564.43	1784.86	2.19	-0.21	0.030	
110.00	-14.22	-1.27	0.00	-38.35	0.00	38.35	2449.09	1224.55	3441.37	1723.24	2.32	-0.22	0.028	
112.00	-13.63	-1.27	0.00	-35.80	0.00	35.80	1823.39	911.69	2573.73	1288.78	2.42	-0.22	0.035	
115.00	-13.16	-1.27	0.00	-31.99	0.00	31.99	1799.96	899.98	2488.04	1245.87	2.56	-0.23	0.033	
120.00	-12.39	-1.26	0.00	-25.64	0.00	25.64	1759.59	879.80	2346.51	1175.00	2.80	-0.24	0.029	
125.00	-11.64	-1.24	0.00	-19.34	0.00	19.34	1717.59	858.79	2206.80	1105.04	3.06	-0.25	0.024	
127.00	-7.76	-1.04	0.00	-16.87	0.00	16.87	1700.33	850.16	2151.49	1077.34	3.16	-0.25	0.020	
130.00	-7.37	-1.02	0.00	-13.75	0.00	13.75	1673.94	836.97	2069.17	1036.12	3.32	-0.26	0.018	
135.00	-6.74	-0.97	0.00	-8.64	0.00	8.64	1628.66	814.33	1933.84	968.36	3.60	-0.26	0.013	
137.00	-3.72	-0.65	0.00	-6.69	0.00	6.69	1610.09	805.04	1880.41	941.60	3.71	-0.26	0.009	
140.00	-3.40	-0.62	0.00	-4.73	0.00	4.73	1581.73	790.87	1801.05	901.87	3.87	-0.27	0.007	
145.00	-2.87	-0.54	0.00	-1.65	0.00	1.65	1533.17	766.58	1671.06	836.77	4.15	-0.27	0.004	
148.00	-0.08	-0.02	0.00	-0.02	0.00	0.02	1503.24	751.62	1594.49	798.43	4.32	-0.27	0.000	
149.00	0.00	-0.02	0.00	0.00	0.00	0.00	1493.13	746.57	1569.22	785.78	4.38	-0.27	0.000	


## Seismic Segment Forces (Factored)

<b>Structure:</b> CT11559-A-SBA	<b>Code:</b> EIA/TIA-222-G	8/18/2021
<b>Site Name:</b> Thompson 1, CT	<b>Exposure:</b> C	
<b>Height:</b> 149.00 (ft)	<b>Crest Height:</b> 0.00	
<b>Base Elev:</b> 0.000 (ft)	<b>Site Class:</b> D - Stiff Soil	
<b>Gh:</b> 1.1	<b>Topography:</b> 1	<b>Struct Class:</b> II



Page: 23

<b>Load Case:</b> 0.9D + 1.0E				<b>Iterations</b> 20
<b>Gust Response Factor</b>	1.10	<b>Sds</b>	0.18	<b>Ss</b> 0.17
<b>Dead Load Factor</b>	0.90	<b>Seismic Load Factor</b>	1.00	<b>S1</b> 0.06
<b>Wind Load Factor</b>	0.00	<b>Structure Frequency (f1)</b>	0.45	<b>SA</b> 0.05
				<b>Seismic Importance Factor</b> 1.00



Top Elev (ft)	Description	Wz (lb)	a	b	c	Lateral Fs (lb)	R: 1.50
0.00		0.00	0.00	0.00	0.00	0.00	
5.00		1371.1	0.00	0.03	0.02	19.86	
10.00		1343.3	0.01	0.05	0.03	29.20	
15.00		1315.5	0.02	0.06	0.04	33.57	
18.00	Bot - Section 2	775.97	0.03	0.07	0.04	20.85	
20.00		956.99	0.03	0.07	0.04	26.37	
25.00	Top - Section 1	2356.3	0.05	0.07	0.04	67.80	
30.00		1072.5	0.08	0.07	0.04	31.84	
35.00		1048.7	0.10	0.07	0.04	32.00	
40.00		1024.9	0.14	0.07	0.03	32.06	
45.00		1001.0	0.17	0.07	0.03	31.86	
50.00		977.26	0.21	0.06	0.02	31.12	
55.00		953.44	0.26	0.05	0.02	29.49	
60.00		929.61	0.31	0.04	0.01	26.57	
62.00	Bot - Section 3	365.17	0.33	0.04	0.01	9.91	
65.00		998.08	0.36	0.03	0.01	24.32	
68.00	Top - Section 2	982.36	0.39	0.02	0.01	20.44	
70.00		296.24	0.42	0.01	0.01	5.33	
75.00		726.71	0.48	-0.01	0.01	6.99	
80.00		706.86	0.54	-0.03	0.01	-0.02	
85.00		687.00	0.62	-0.06	0.02	-6.62	
90.00		667.15	0.69	-0.08	0.03	-11.76	
95.00		647.29	0.77	-0.11	0.05	-14.59	
100.00		627.44	0.85	-0.12	0.07	-14.66	
105.00		607.58	0.94	-0.12	0.10	-11.85	
107.00	Bot - Section 4	237.47	0.97	-0.12	0.12	-3.94	
110.00		635.01	1.03	-0.10	0.15	-6.79	
112.00	Top - Section 3	416.19	1.07	-0.09	0.17	-2.40	
115.00		275.23	1.13	-0.05	0.20	0.87	
120.00		446.01	1.23	0.03	0.27	9.85	
125.00		430.12	1.33	0.16	0.36	19.85	
127.00	Appurtenance(s)	3154.0	1.37	0.23	0.40	180.48	
130.00		246.64	1.44	0.36	0.47	18.59	
135.00		398.36	1.55	0.64	0.61	43.77	
137.00	Appurtenance(s)	2464.4	1.60	0.77	0.67	308.44	
140.00		227.58	1.67	1.01	0.77	34.06	
145.00		366.59	1.79	1.49	0.96	71.45	
148.00	Appurtenance(s)	2286.7	1.86	1.85	1.09	513.83	
149.00		69.51	1.89	1.98	1.14	16.34	
<b>Totals:</b>		<b>34,092.8</b>				<b>1,624.5</b>	<b>Total Wind: 33,739.9</b>

Seismic Base Shear is Less Than 50% of Wind Force - An Analysis is NOT Required



## Calculated Forces

<b>Structure:</b> CT11559-A-SBA	<b>Code:</b> EIA/TIA-222-G	8/18/2021
<b>Site Name:</b> Thompson 1, CT	<b>Exposure:</b> C	
<b>Height:</b> 149.00 (ft)	<b>Crest Height:</b> 0.00	
<b>Base Elev:</b> 0.000 (ft)	<b>Site Class:</b> D - Stiff Soil	
<b>Gh:</b> 1.1	<b>Topography:</b> 1	<b>Struct Class:</b> II



Page: 24

<b>Load Case:</b> 0.9D + 1.0E						<b>Iterations</b> 20
<b>Gust Response Factor</b>	1.10		<b>Sds</b>	0.18		<b>Ss</b> 0.17
<b>Dead Load Factor</b>	0.90	<b>Seismic Load Factor</b>	1.00	<b>Sd1</b>	0.10	<b>S1</b> 0.06
<b>Wind Load Factor</b>	0.00	<b>Structure Frequency (f1)</b>	0.45	<b>SA</b>	0.05	<b>Seismic Importance Factor</b> 1.00



Seg Elev (ft)	Pu FY (-) (kips)	Vu FX (-) (kips)	Tu MY (-) (ft-kips)	Mu MZ (ft-kips)	Mu MX (ft-kips)	Resultant Moment (ft-kips)	phi Pn (kips)	phi Vn (kips)	phi Tn (ft-kips)	phi Mn (ft-kips)	Total Deflect (in)	Rotation Sway (deg)	Rotation Twist (deg)	Stress Ratio
0.00	-35.49	-1.70	0.00	-192.70	0.00	192.70	5499.39	2749.69	13252.7	6636.23	0.00	0.00	0.00	0.035
5.00	-34.08	-1.68	0.00	-184.21	0.00	184.21	5429.06	2714.53	12818.7	6418.90	0.00	-0.01	0.035	
10.00	-32.69	-1.66	0.00	-175.79	0.00	175.79	5357.09	2678.54	12387.8	6203.11	0.02	-0.02	0.034	
15.00	-31.33	-1.63	0.00	-167.50	0.00	167.50	5283.48	2641.74	11960.1	5988.97	0.04	-0.02	0.034	
18.00	-30.53	-1.61	0.00	-162.61	0.00	162.61	5238.53	2619.26	11705.2	5861.33	0.05	-0.03	0.034	
20.00	-29.60	-1.58	0.00	-159.40	0.00	159.40	5208.23	2604.11	11536.0	5776.60	0.06	-0.03	0.033	
25.00	-27.30	-1.52	0.00	-151.47	0.00	151.47	4201.23	2100.61	9252.96	4633.35	0.10	-0.04	0.039	
30.00	-26.16	-1.49	0.00	-143.88	0.00	143.88	4145.44	2072.72	8928.09	4470.68	0.15	-0.05	0.038	
35.00	-25.05	-1.46	0.00	-136.42	0.00	136.42	4088.00	2044.00	8605.21	4309.00	0.20	-0.06	0.038	
40.00	-23.95	-1.43	0.00	-129.12	0.00	129.12	4028.93	2014.47	8284.56	4148.44	0.27	-0.07	0.037	
45.00	-22.87	-1.40	0.00	-121.96	0.00	121.96	3968.22	1984.11	7966.37	3989.11	0.34	-0.08	0.036	
50.00	-21.82	-1.37	0.00	-114.94	0.00	114.94	3905.86	1952.93	7650.88	3831.13	0.42	-0.09	0.036	
55.00	-20.79	-1.35	0.00	-108.07	0.00	108.07	3841.87	1920.93	7338.34	3674.63	0.52	-0.09	0.035	
60.00	-19.78	-1.32	0.00	-101.34	0.00	101.34	3776.23	1888.12	7028.98	3519.72	0.62	-0.10	0.034	
62.00	-19.38	-1.31	0.00	-98.70	0.00	98.70	3749.52	1874.76	6906.19	3458.23	0.67	-0.11	0.034	
65.00	-18.37	-1.29	0.00	-94.76	0.00	94.76	3708.96	1854.48	6723.05	3366.52	0.74	-0.11	0.033	
68.00	-17.38	-1.27	0.00	-90.90	0.00	90.90	2897.69	1448.84	5257.67	2632.74	0.81	-0.12	0.041	
70.00	-17.05	-1.26	0.00	-88.37	0.00	88.37	2878.95	1439.48	5167.56	2587.62	0.86	-0.13	0.040	
75.00	-16.22	-1.26	0.00	-82.05	0.00	82.05	2830.96	1415.48	4943.48	2475.42	1.00	-0.14	0.039	
80.00	-15.41	-1.26	0.00	-75.77	0.00	75.77	2781.33	1390.66	4721.30	2364.16	1.15	-0.15	0.038	
85.00	-14.62	-1.26	0.00	-69.47	0.00	69.47	2730.06	1365.03	4501.25	2253.97	1.31	-0.16	0.036	
90.00	-13.84	-1.26	0.00	-63.18	0.00	63.18	2677.14	1338.57	4283.57	2144.97	1.49	-0.17	0.035	
95.00	-13.08	-1.26	0.00	-56.88	0.00	56.88	2622.59	1311.30	4068.50	2037.27	1.67	-0.18	0.033	
100.00	-12.34	-1.26	0.00	-50.58	0.00	50.58	2566.40	1283.20	3856.28	1931.01	1.87	-0.19	0.031	
105.00	-11.62	-1.26	0.00	-44.28	0.00	44.28	2508.57	1254.28	3647.16	1826.29	2.08	-0.21	0.029	
107.00	-11.34	-1.26	0.00	-41.76	0.00	41.76	2484.97	1242.49	3564.43	1784.86	2.17	-0.21	0.028	
110.00	-10.66	-1.26	0.00	-37.98	0.00	37.98	2449.09	1224.55	3441.37	1723.24	2.30	-0.22	0.026	
112.00	-10.22	-1.26	0.00	-35.47	0.00	35.47	1823.39	911.69	2573.73	1288.78	2.39	-0.22	0.033	
115.00	-9.87	-1.26	0.00	-31.70	0.00	31.70	1799.96	899.98	2488.04	1245.87	2.53	-0.23	0.031	
120.00	-9.29	-1.25	0.00	-25.42	0.00	25.42	1759.59	879.80	2346.51	1175.00	2.78	-0.24	0.027	
125.00	-8.73	-1.22	0.00	-19.19	0.00	19.19	1717.59	858.79	2206.80	1105.04	3.03	-0.25	0.022	
127.00	-8.82	-1.03	0.00	-16.74	0.00	16.74	1700.33	850.16	2151.49	1077.34	3.13	-0.25	0.019	
130.00	-5.53	-1.01	0.00	-13.64	0.00	13.64	1673.94	836.97	2069.17	1036.12	3.29	-0.25	0.016	
135.00	-5.05	-0.97	0.00	-8.58	0.00	8.58	1628.66	814.33	1933.84	968.36	3.56	-0.26	0.012	
137.00	-2.79	-0.65	0.00	-6.65	0.00	6.65	1610.09	805.04	1880.41	941.60	3.67	-0.26	0.009	
140.00	-2.55	-0.61	0.00	-4.70	0.00	4.70	1581.73	790.87	1801.05	901.87	3.84	-0.26	0.007	
145.00	-2.15	-0.54	0.00	-1.64	0.00	1.64	1533.17	766.58	1671.06	836.77	4.11	-0.27	0.003	
148.00	-0.06	-0.02	0.00	-0.02	0.00	0.02	1503.24	751.62	1594.49	798.43	4.28	-0.27	0.000	
149.00	0.00	-0.02	0.00	0.00	0.00	0.00	1493.13	746.57	1569.22	785.78	4.34	-0.27	0.000	

## Wind Loading - Shaft


<b>Structure:</b> CT11559-A-SBA	<b>Code:</b> EIA/TIA-222-G	8/18/2021
<b>Site Name:</b> Thompson 1, CT	<b>Exposure:</b> C	
<b>Height:</b> 149.00 (ft)	<b>Crest Height:</b> 0.00	
<b>Base Elev:</b> 0.000 (ft)	<b>Site Class:</b> D - Stiff Soil	
<b>Gh:</b> 1.1	<b>Topography:</b> 1	<b>Struct Class:</b> II



Page: 25

**Load Case:** 1.0D + 1.0W 60 mph Wind

**Dead Load Factor** 1.00  
**Wind Load Factor** 1.00



**Iterations** 21

Elev (ft)	Description	Kzt	Kz	qz (psf)	qzGh (psf)	C (mph-ft)	Cf	Ice Thick (in)	Tributary (ft)	Aa (sf)	CfAa (sf)	Wind Force X (lb)	Dead Load Ice (lb)	Tot Dead Load (lb)
0.00		1.00	0.85	7.442	8.19	276.46	0.650	0.000	0.00	0.000	0.00	0.0	0.0	0.0
5.00		1.00	0.85	7.442	8.19	270.96	0.650	0.000	5.00	24.740	16.08	131.6	0.0	1371.1
10.00		1.00	0.85	7.442	8.19	265.45	0.650	0.000	5.00	24.242	15.76	129.0	0.0	1343.3
15.00		1.00	0.85	7.442	8.19	259.94	0.650	0.000	5.00	23.744	15.43	126.3	0.0	1315.5
18.00	Bot - Section 2	1.00	0.88	7.723	8.50	261.44	0.650	0.000	3.00	14.008	9.11	77.3	0.0	776.0
20.00		1.00	0.90	7.896	8.69	262.09	0.650	0.000	2.00	9.366	6.09	52.9	0.0	957.0
25.00	Top - Section 1	1.00	0.95	8.276	9.10	262.51	0.650	0.000	5.00	23.066	14.99	136.5	0.0	2356.3
30.00		1.00	0.98	8.600	9.46	265.45	0.650	0.000	5.00	22.568	14.67	138.8	0.0	1072.6
35.00		1.00	1.01	8.883	9.77	263.77	0.650	0.000	5.00	22.071	14.35	140.2	0.0	1048.7
40.00		1.00	1.04	9.137	10.05	261.40	0.650	0.000	5.00	21.573	14.02	140.9	0.0	1024.9
45.00		1.00	1.07	9.366	10.30	258.49	0.650	0.000	5.00	21.075	13.70	141.1	0.0	1001.1
50.00		1.00	1.09	9.576	10.53	255.12	0.650	0.000	5.00	20.577	13.38	140.9	0.0	977.3
55.00		1.00	1.12	9.770	10.75	251.38	0.650	0.000	5.00	20.079	13.05	140.3	0.0	953.4
60.00		1.00	1.14	9.951	10.95	247.33	0.650	0.000	5.00	19.582	12.73	139.3	0.0	929.6
62.00	Bot - Section 3	1.00	1.14	10.020	11.02	245.63	0.650	0.000	2.00	7.693	5.00	55.1	0.0	365.2
65.00		1.00	1.16	10.120	11.13	243.00	0.650	0.000	3.00	11.549	7.51	83.6	0.0	998.1
68.00	Top - Section 2	1.00	1.17	10.217	11.24	240.28	0.650	0.000	3.00	11.370	7.39	83.1	0.0	982.4
70.00		1.00	1.17	10.279	11.31	241.87	0.650	0.000	2.00	7.480	4.86	55.0	0.0	296.2
75.00		1.00	1.19	10.430	11.47	237.11	0.650	0.000	5.00	18.353	11.93	136.9	0.0	726.7
80.00		1.00	1.21	10.572	11.63	232.16	0.650	0.000	5.00	17.855	11.61	135.0	0.0	706.9
85.00		1.00	1.22	10.708	11.78	227.04	0.650	0.000	5.00	17.357	11.28	132.9	0.0	687.0
90.00		1.00	1.24	10.838	11.92	221.76	0.650	0.000	5.00	16.859	10.96	130.6	0.0	667.1
95.00		1.00	1.25	10.962	12.06	216.35	0.650	0.000	5.00	16.361	10.63	128.2	0.0	647.3
100.00		1.00	1.27	11.081	12.19	210.80	0.650	0.000	5.00	15.863	10.31	125.7	0.0	627.4
105.00		1.00	1.28	11.195	12.31	205.13	0.650	0.000	5.00	15.366	9.99	123.0	0.0	607.6
107.00	Bot - Section 4	1.00	1.28	11.240	12.36	202.83	0.650	0.000	2.00	6.007	3.90	48.3	0.0	237.5
110.00		1.00	1.29	11.305	12.44	199.35	0.650	0.000	3.00	8.988	5.84	72.7	0.0	635.0
112.00	Top - Section 3	1.00	1.30	11.348	12.48	197.00	0.650	0.000	2.00	5.892	3.83	47.8	0.0	416.2
115.00		1.00	1.30	11.412	12.55	196.36	0.650	0.000	3.00	8.689	5.65	70.9	0.0	275.2
120.00		1.00	1.32	11.514	12.67	190.39	0.650	0.000	5.00	14.084	9.15	115.9	0.0	446.0
125.00		1.00	1.33	11.614	12.78	184.33	0.650	0.000	5.00	13.586	8.83	112.8	0.0	430.1
127.00	Appurtenance(s)	1.00	1.33	11.653	12.82	181.88	0.650	0.000	2.00	5.295	3.44	44.1	0.0	167.6
130.00		1.00	1.34	11.710	12.88	178.18	0.650	0.000	3.00	7.793	5.07	65.2	0.0	246.6
135.00		1.00	1.35	11.803	12.98	171.96	0.650	0.000	5.00	12.590	8.18	106.3	0.0	398.4
137.00	Appurtenance(s)	1.00	1.35	11.840	13.02	169.44	0.650	0.000	2.00	4.897	3.18	41.5	0.0	154.9
140.00		1.00	1.36	11.894	13.08	165.65	0.650	0.000	3.00	7.196	4.68	61.2	0.0	227.6
145.00		1.00	1.37	11.982	13.18	159.28	0.650	0.000	5.00	11.595	7.54	99.3	0.0	366.6
148.00	Appurtenance(s)	1.00	1.37	12.034	13.24	155.42	0.650	0.000	3.00	6.718	4.37	57.8	0.0	212.3
149.00		1.00	1.38	12.051	13.26	154.13	0.650	0.000	1.00	2.199	1.43	19.0	0.0	69.5
<b>Totals:</b>									<b>149.00</b>			<b>3,786.9</b>		<b>26,722.3</b>

## Discrete Appurtenance Forces

<b>Structure:</b> CT11559-A-SBA	<b>Code:</b> EIA/TIA-222-G	8/18/2021
<b>Site Name:</b> Thompson 1, CT	<b>Exposure:</b> C	
<b>Height:</b> 149.00 (ft)	<b>Crest Height:</b> 0.00	
<b>Base Elev:</b> 0.000 (ft)	<b>Site Class:</b> D - Stiff Soil	
<b>Gh:</b> 1.1	<b>Topography:</b> 1	<b>Struct Class:</b> II



Page: 26

**Load Case:** 1.0D + 1.0W 60 mph Wind

**Dead Load Factor** 1.00

**Wind Load Factor** 1.00



**Iterations** 21

No.	Elev (ft)	Description	Qty	qz (psf)	qzGh (psf)	Orient Factor	x Ka	Ka	Total CaAa (sf)	Dead Load (lb)	Horiz Ecc (ft)	Vert Ecc (ft)	Wind FX (lb)	Mom Y (lb-ft)	Mom Z (lb-ft)
1	148.00	T-Arms	1	12.034	13.238	0.56	0.75	8.44	500.00	0.000	0.000	111.69	0.00	0.00	
2	148.00	4449	3	12.034	13.238	0.54	0.80	2.65	210.00	0.000	0.000	35.12	0.00	0.00	
3	148.00	HRK12 (Handrail Kit)	1	12.034	13.238	0.56	0.75	3.80	261.72	0.000	0.000	50.26	0.00	0.00	
4	148.00	(3) Stabilizer Kit (4' FW)	1	12.034	13.238	0.56	0.75	2.08	140.00	0.000	0.000	27.55	0.00	0.00	
5	148.00	Ericsson KRY112 144/1	3	12.034	13.238	0.56	0.80	0.69	33.00	0.000	0.000	9.12	0.00	0.00	
6	148.00	AIR21 B2A B4P	3	12.034	13.238	0.69	0.80	12.57	274.50	0.000	0.000	166.39	0.00	0.00	
7	148.00	AIR21 B2A B4P	3	12.034	13.238	0.69	0.80	12.57	271.20	0.000	0.000	166.39	0.00	0.00	
8	148.00	APXVAARR24_43-U-NA2	3	12.034	13.238	0.56	0.80	34.00	384.00	0.000	0.000	450.12	0.00	0.00	
9	137.00	T-Arms	3	11.840	13.024	0.56	0.75	13.50	1050.00	0.000	0.000	175.82	0.00	0.00	
10	137.00	RCMDC-6627-PF-48	1	11.840	13.024	1.00	1.00	4.06	32.00	0.000	0.000	52.88	0.00	0.00	
11	137.00	Commscope	3	11.840	13.024	0.40	0.80	1.60	58.20	0.000	0.000	20.79	0.00	0.00	
12	137.00	Samsung RFV01U-D2A	3	11.840	13.024	0.54	0.80	3.02	210.90	0.000	0.000	39.37	0.00	0.00	
13	137.00	Samsung RFV01U-D1A	3	11.840	13.024	0.54	0.80	3.02	253.20	0.000	0.000	39.37	0.00	0.00	
14	137.00	91900314	3	11.840	13.024	1.00	1.00	0.00	84.00	0.000	0.000	0.00	0.00	0.00	
15	137.00	Samsung MT6407-77A	3	11.840	13.024	0.56	0.80	7.88	261.30	0.000	0.000	102.62	0.00	0.00	
16	137.00	JMA Wireless	6	11.840	13.024	0.70	0.80	41.22	360.00	0.000	0.000	536.81	0.00	0.00	
17	127.00	T-Arms	3	11.653	12.818	0.56	0.75	13.50	1050.00	0.000	0.000	173.04	0.00	0.00	
18	127.00	7770.00	6	11.653	12.818	0.58	0.80	19.27	210.00	0.000	0.000	247.03	0.00	0.00	
19	127.00	Powerwave LGP21401	12	11.653	12.818	0.80	0.80	12.38	169.20	0.000	0.000	158.74	0.00	0.00	
20	127.00	Kathrein 860 10025 RET	12	11.653	12.818	0.80	0.80	1.34	13.20	0.000	0.000	17.23	0.00	0.00	
21	127.00	Powerwave LGP13519	6	11.653	12.818	0.80	0.80	1.63	31.80	0.000	0.000	20.92	0.00	0.00	
22	127.00	Raycap DC6-48-60-18-8F	1	11.653	12.818	1.00	1.00	0.92	31.80	0.000	0.000	11.79	0.00	0.00	
23	127.00	Powerwave 1001983 Bias	3	11.653	12.818	0.80	0.80	0.50	13.20	0.000	0.000	6.46	0.00	0.00	
24	127.00	(3) Stabilizer Kit	1	11.653	12.818	0.56	0.75	3.43	180.00	0.000	0.000	43.98	0.00	0.00	
25	127.00	OPA65R-BU8DA	3	11.653	12.818	0.58	0.80	31.56	229.50	0.000	0.000	404.58	0.00	0.00	
26	127.00	DMP65R-BU8DA	3	11.653	12.818	0.58	0.80	31.18	287.10	0.000	0.000	399.66	0.00	0.00	
27	127.00	Horizontal Pipe	3	11.653	12.818	0.56	0.75	5.01	137.25	0.000	0.000	64.22	0.00	0.00	
28	127.00	RRUS 4478 B14	3	11.653	12.818	0.54	0.80	2.65	178.20	0.000	0.000	34.01	0.00	0.00	
29	127.00	4449 B5/B12	3	11.653	12.818	0.54	0.80	3.17	213.00	0.000	0.000	40.60	0.00	0.00	
30	127.00	RRUS 8843 B2 B66A	3	11.653	12.818	0.54	0.80	2.64	216.00	0.000	0.000	33.80	0.00	0.00	
31	127.00	DC9-48-60-24-8C-EV	1	11.653	12.818	1.00	1.00	1.14	26.20	0.000	0.000	14.61	0.00	0.00	

**Totals: 7,370.47**

**3,654.96**

## Total Applied Force Summary

<b>Structure:</b> CT11559-A-SBA	<b>Code:</b> EIA/TIA-222-G	8/18/2021
<b>Site Name:</b> Thompson 1, CT	<b>Exposure:</b> C	
<b>Height:</b> 149.00 (ft)	<b>Crest Height:</b> 0.00	
<b>Base Elev:</b> 0.000 (ft)	<b>Site Class:</b> D - Stiff Soil	
<b>Gh:</b> 1.1	<b>Topography:</b> 1	<b>Struct Class:</b> II



Page: 27

**Load Case:** 1.0D + 1.0W 60 mph Wind

**Dead Load Factor** 1.00

**Wind Load Factor** 1.00



**Iterations** 21

Elev (ft)	Description	Lateral FX (-) (lb)	Axial FY (-) (lb)	Torsion MY (lb-ft)	Moment MZ (lb-ft)
0.00		0.00	0.00	0.00	0.00
5.00		131.64	1564.97	0.00	0.00
10.00		128.99	1537.17	0.00	0.00
15.00		126.34	1509.38	0.00	0.00
18.00		77.35	892.28	0.00	0.00
20.00		52.88	1034.53	0.00	0.00
25.00		136.49	2550.18	0.00	0.00
30.00		138.77	1266.42	0.00	0.00
35.00		140.19	1242.59	0.00	0.00
40.00		140.93	1218.77	0.00	0.00
45.00		141.13	1194.94	0.00	0.00
50.00		140.89	1171.11	0.00	0.00
55.00		140.27	1147.29	0.00	0.00
60.00		139.32	1123.46	0.00	0.00
62.00		55.12	442.71	0.00	0.00
65.00		83.57	1114.39	0.00	0.00
68.00		83.06	1098.67	0.00	0.00
70.00		54.98	373.78	0.00	0.00
75.00		136.86	920.56	0.00	0.00
80.00		134.97	900.71	0.00	0.00
85.00		132.89	880.85	0.00	0.00
90.00		130.64	861.00	0.00	0.00
95.00		128.23	841.14	0.00	0.00
100.00		125.68	821.29	0.00	0.00
105.00		122.99	801.43	0.00	0.00
107.00		48.27	315.01	0.00	0.00
110.00		72.65	751.32	0.00	0.00
112.00		47.81	493.73	0.00	0.00
115.00		70.90	391.54	0.00	0.00
120.00		115.95	639.86	0.00	0.00
125.00		112.82	623.97	0.00	0.00
127.00	(63) attachments	1714.77	3231.59	0.00	0.00
130.00		65.25	325.18	0.00	0.00
135.00		106.26	529.26	0.00	0.00
137.00	(25) attachments	1009.12	2516.85	0.00	0.00
140.00		61.20	268.50	0.00	0.00
145.00		99.34	434.79	0.00	0.00
148.00	(18) attachments	1074.45	2327.67	0.00	0.00
149.00		18.95	69.51	0.00	0.00
	<b>Totals:</b>	<b>7,441.90</b>	<b>39,428.42</b>	<b>0.00</b>	<b>0.00</b>

## Calculated Forces


<b>Structure:</b> CT11559-A-SBA	<b>Code:</b> EIA/TIA-222-G	8/18/2021	
<b>Site Name:</b> Thompson 1, CT	<b>Exposure:</b> C		
<b>Height:</b> 149.00 (ft)	<b>Crest Height:</b> 0.00		
<b>Base Elev:</b> 0.000 (ft)	<b>Site Class:</b> D - Stiff Soil		
<b>Gh:</b> 1.1	<b>Topography:</b> 1	<b>Struct Class:</b> II	Page: 28



**Load Case:** 1.0D + 1.0W 60 mph Wind

**Iterations** 21

**Dead Load Factor** 1.00  
**Wind Load Factor** 1.00



Seg Elev (ft)	Pu FY (-) (kips)	Vu FX (-) (kips)	Tu MY (-) (ft-kips)	Mu MZ (ft-kips)	Mu MX (ft-kips)	Resultant Moment (ft-kips)	phi Pn (kips)	phi Vn (kips)	phi Tn (ft-kips)	phi Mn (ft-kips)	Total Deflect (in)	Rotation Sway (deg)	Rotation Twist (deg)	Stress Ratio
0.00	-39.43	-7.45	0.00	-790.91	0.00	790.91	5499.39	2749.69	13252.7	6636.23	0.00	0.000	0.000	0.126
5.00	-37.86	-7.34	0.00	-753.65	0.00	753.65	5429.06	2714.53	12818.7	6418.90	0.02	-0.031	0.000	0.124
10.00	-36.32	-7.23	0.00	-716.95	0.00	716.95	5357.09	2678.54	12387.8	6203.11	0.07	-0.063	0.000	0.122
15.00	-34.80	-7.12	0.00	-680.80	0.00	680.80	5283.48	2641.74	11960.1	5988.97	0.15	-0.094	0.000	0.120
18.00	-33.91	-7.05	0.00	-659.44	0.00	659.44	5238.53	2619.26	11705.2	5861.33	0.21	-0.114	0.000	0.119
20.00	-32.87	-7.01	0.00	-645.35	0.00	645.35	5208.23	2604.11	11536.0	5776.60	0.27	-0.127	0.000	0.118
25.00	-30.32	-6.88	0.00	-610.32	0.00	610.32	4201.23	2100.61	9252.96	4633.35	0.42	-0.159	0.000	0.139
30.00	-29.05	-6.76	0.00	-575.91	0.00	575.91	4145.44	2072.72	8928.09	4470.68	0.60	-0.192	0.000	0.136
35.00	-27.80	-6.63	0.00	-542.14	0.00	542.14	4088.00	2044.00	8605.21	4309.00	0.82	-0.229	0.000	0.133
40.00	-26.58	-6.50	0.00	-508.99	0.00	508.99	4028.93	2014.47	8284.56	4148.44	1.08	-0.266	0.000	0.129
45.00	-25.38	-6.37	0.00	-476.49	0.00	476.49	3968.22	1984.11	7966.37	3989.11	1.38	-0.303	0.000	0.126
50.00	-24.21	-6.24	0.00	-444.65	0.00	444.65	3905.86	1952.93	7650.88	3831.13	1.72	-0.341	0.000	0.122
55.00	-23.06	-6.11	0.00	-413.46	0.00	413.46	3841.87	1920.93	7338.34	3674.63	2.10	-0.378	0.000	0.119
60.00	-21.93	-5.97	0.00	-382.93	0.00	382.93	3776.23	1888.12	7028.98	3519.72	2.51	-0.416	0.000	0.115
62.00	-21.49	-5.92	0.00	-371.00	0.00	371.00	3749.52	1874.76	6906.19	3458.23	2.69	-0.431	0.000	0.113
65.00	-20.37	-5.83	0.00	-353.24	0.00	353.24	3708.96	1854.48	6723.05	3366.52	2.97	-0.454	0.000	0.110
68.00	-19.27	-5.75	0.00	-335.75	0.00	335.75	2897.69	1448.84	5257.67	2632.74	3.26	-0.476	0.000	0.134
70.00	-18.90	-5.70	0.00	-324.25	0.00	324.25	2878.95	1439.48	5167.56	2587.62	3.46	-0.492	0.000	0.132
75.00	-17.97	-5.57	0.00	-295.76	0.00	295.76	2830.96	1415.48	4943.48	2475.42	4.00	-0.534	0.000	0.126
80.00	-17.07	-5.44	0.00	-267.92	0.00	267.92	2781.33	1390.66	4721.30	2364.16	4.58	-0.576	0.000	0.119
85.00	-16.19	-5.31	0.00	-240.75	0.00	240.75	2730.06	1365.03	4501.25	2253.97	5.21	-0.617	0.000	0.113
90.00	-15.32	-5.18	0.00	-214.22	0.00	214.22	2677.14	1338.57	4283.57	2144.97	5.88	-0.657	0.000	0.106
95.00	-14.48	-5.05	0.00	-188.34	0.00	188.34	2622.59	1311.30	4068.50	2037.27	6.58	-0.695	0.000	0.098
100.00	-13.66	-4.92	0.00	-163.11	0.00	163.11	2566.40	1283.20	3856.28	1931.01	7.33	-0.732	0.000	0.090
105.00	-12.86	-4.79	0.00	-138.51	0.00	138.51	2508.57	1254.28	3647.16	1826.29	8.12	-0.767	0.000	0.081
107.00	-12.54	-4.74	0.00	-128.93	0.00	128.93	2484.97	1242.49	3564.43	1784.86	8.44	-0.781	0.000	0.077
110.00	-11.79	-4.66	0.00	-114.70	0.00	114.70	2449.09	1224.55	3441.37	1723.24	8.94	-0.800	0.000	0.071
112.00	-11.29	-4.61	0.00	-105.38	0.00	105.38	1823.39	911.69	2573.73	1288.78	9.28	-0.813	0.000	0.088
115.00	-10.90	-4.54	0.00	-91.55	0.00	91.55	1799.96	899.98	2488.04	1245.87	9.80	-0.830	0.000	0.080
120.00	-10.26	-4.42	0.00	-68.85	0.00	68.85	1759.59	879.80	2346.51	1175.00	10.68	-0.860	0.000	0.064
125.00	-9.64	-4.30	0.00	-46.76	0.00	46.76	1717.59	858.79	2206.80	1105.04	11.60	-0.884	0.000	0.048
127.00	-6.43	-2.54	0.00	-38.16	0.00	38.16	1700.33	850.16	2151.49	1077.34	11.97	-0.892	0.000	0.039
130.00	-6.11	-2.47	0.00	-30.55	0.00	30.55	1673.94	836.97	2069.17	1036.12	12.53	-0.902	0.000	0.033
135.00	-5.58	-2.35	0.00	-18.22	0.00	18.22	1628.66	814.33	1933.84	968.36	13.49	-0.915	0.000	0.022
137.00	-3.08	-1.30	0.00	-13.52	0.00	13.52	1610.09	805.04	1880.41	941.60	13.87	-0.919	0.000	0.016
140.00	-2.81	-1.24	0.00	-9.61	0.00	9.61	1581.73	790.87	1801.05	901.87	14.45	-0.923	0.000	0.012
145.00	-2.38	-1.13	0.00	-3.42	0.00	3.42	1533.17	766.58	1671.06	836.77	15.42	-0.927	0.000	0.006
148.00	-0.07	-0.02	0.00	-0.02	0.00	0.02	1503.24	751.62	1594.49	798.43	16.00	-0.928	0.000	0.000
149.00	0.00	-0.02	0.00	0.00	0.00	0.00	1493.13	746.57	1569.22	785.78	16.20	-0.928	0.000	0.000

## Final Analysis Summary

<b>Structure:</b> CT11559-A-SBA	<b>Code:</b> EIA/TIA-222-G	8/18/2021
<b>Site Name:</b> Thompson 1, CT	<b>Exposure:</b> C	
<b>Height:</b> 149.00 (ft)	<b>Crest Height:</b> 0.00	
<b>Base Elev:</b> 0.000 (ft)	<b>Site Class:</b> D - Stiff Soil	
<b>Gh:</b> 1.1	<b>Topography:</b> 1	<b>Struct Class:</b> II



Page: 29

### Reactions

Load Case	Shear FX (kips)	Shear FZ (kips)	Axial FY (kips)	Moment MX (ft-kips)	Moment MY (ft-kips)	Moment MZ (ft-kips)
1.2D + 1.6W 101 mph Wind	33.8	0.00	47.27	0.00	0.00	3600.80
0.9D + 1.6W 101 mph Wind	33.8	0.00	35.44	0.00	0.00	3574.60
1.2D + 1.0Di + 1.0Wi 50 mph Wind	9.1	0.00	78.65	0.00	0.00	961.82
1.2D + 1.0E	1.7	0.00	47.31	0.00	0.00	194.21
0.9D + 1.0E	1.7	0.00	35.49	0.00	0.00	192.70
1.0D + 1.0W 60 mph Wind	7.5	0.00	39.43	0.00	0.00	790.91

### Max Stresses

Load Case	Pu FY (-) (kips)	Vu FX (-) (kips)	Tu MY (-) (ft-kips)	Mu MZ (ft-kips)	Mu MX (ft-kips)	Resultant Moment (ft-kips)	phi Pn (kips)	phi Vn (kips)	phi Tn (ft-kips)	phi Mn (ft-kips)	Elev (ft)	Stress Ratio
1.2D + 1.6W 101 mph Wind	-35.97	-31.28	0.00	-2780.8	0.00	-2780.8	4201.23	2100.6	9252.96	4633.35	25.00	0.609
0.9D + 1.6W 101 mph Wind	-26.88	-31.15	0.00	-2756.3	0.00	-2756.3	4201.23	2100.6	9252.96	4633.35	25.00	0.602
1.2D + 1.0Di + 1.0Wi 50 mph Wind	-64.43	-8.47	0.00	-739.94	0.00	-739.94	4201.23	2100.6	9252.96	4633.35	25.00	0.175
1.2D + 1.0E	-23.18	-1.28	0.00	-91.87	0.00	-91.87	2897.69	1448.8	5257.67	2632.74	68.00	0.043
0.9D + 1.0E	-17.38	-1.27	0.00	-90.90	0.00	-90.90	2897.69	1448.8	5257.67	2632.74	68.00	0.041
1.0D + 1.0W 60 mph Wind	-30.32	-6.88	0.00	-610.32	0.00	-610.32	4201.23	2100.6	9252.96	4633.35	25.00	0.139

## Base Plate Summary

<b>Structure:</b> CT11559-A-SB	<b>Code:</b> EIA/TIA-222-G	8/18/2021
<b>Site Name:</b> Thompson 1, CT	<b>Exposure:</b> C	
<b>Height:</b> 149.00 (ft)	<b>Crest Height:</b> 0.00	
<b>Base Elev:</b> 0.000 (ft)	<b>Site Class:</b> D - Stiff Soil	
<b>Gh:</b> 1.1	<b>Topography:</b> 1	<b>Struct Class:</b> II



Page: 30

Reactions	Base Plate	Anchor Bolts
Original Design	<b>Yield (ksi):</b> 50.00	<b>Bolt Circle:</b> 66.00
<b>Moment (kip-ft):</b> 4056.00	<b>Width (in):</b> 72.00	<b>Number Bolts:</b> 18.00
<b>Axial (kip):</b> 38.00	<b>Style:</b> Round	<b>Bolt Type:</b> 2.00" F1554 105
<b>Shear (kip):</b> 36.00	<b>Polygon Sides:</b> 0.00	<b>Bolt Diameter (in):</b> 2.00
Analysis (1.2D + 1.6W)	<b>Clip Length (in):</b> 0.00	<b>Yield (ksi):</b> 105.00
<b>Moment (kip-ft):</b> 3600.80	<b>Effective Len (in):</b> 16.22	<b>Ultimate (ksi):</b> 125.00
<b>Axial (kip):</b> 47.27	<b>Moment (kip-in):</b> 519.81	<b>Arrangement:</b> Radial
<b>Shear (kip):</b> 33.80	<b>Allow Stress (ksi):</b> 67.50	<b>Cluster Dist (in):</b> 0.00
	<b>Applied Stress (ksi):</b> 25.65	<b>Start Angle (deg):</b> 0.00
	<b>Stress Ratio:</b> 0.38	Compression
		<b>Force (kip):</b> 149.86
		<b>Allowable (kip):</b> 250.00
		<b>Ratio:</b> 0.61
		Tension
		<b>Force (kip):</b> 141.12
		<b>Allowable (kip):</b> 250.00
		<b>Ratio:</b> 0.58



# Monopole Mat Foundation Design

Date

8/18/2021

<b>Customer Name:</b>	Verizon	<b>EIA/TIA Standard:</b>	EIA-222-G
<b>Site Name:</b>		<b>Structure Height (Ft.):</b>	149
<b>Site Number:</b>	CT11559-A-SBA	<b>Engineer Name:</b>	T. Alajaj
<b>Engr. Number:</b>	111975	<b>Engineer Login ID:</b>	

**Foundation Info Obtained from:**

Mapping Operation

**Structure Type:**

Monopole

**Analysis or Design?**

Analysis

**Base Reactions (Factored):**

Axial Load (Kips):	47.3	Shear Force (Kips):	33.8
Uplift Force (Kips):	0.0	Moment (Kips-ft):	3600.8

Allowable overstress %: 5.0%

**Foundation Geometries:**

		Mods required -Yes/No ?:	No
Diameter of Pier (ft.):	7.0	Depth of Base BG (ft.):	4.5
Pier Height A. G. (ft.):	1.00	Thickness of Pad (ft):	2.50
Length of Pad (ft.):	31	Width of Pad (ft.):	31

Final Length of pad (ft)	31.0	Final width of pad (ft):	31.0
--------------------------	------	--------------------------	------

**Material Properties and Rebar Info:**

Concrete Strength (psi):	3000	Steel Elastic Modulus:	29000	ksi
Vertical bar yield (ksi)	60	Tie steel yield (ksi):	60	
Vertical Rebar Size #:	9	Tie / Stirrup Size #:	5	
Qty. of Vertical Rebars:	56	Tie Spacing (in):	12.0	
Pad Rebar Yield (Ksi):	60	Pad Steel Rebar Size (#):	9	
Concrete Cover (in.):	3	Unit Weight of Concrete:	150.0	pcf

Rebar at the bottom of the concrete pad:

Qty. of Rebar in Pad (L):	30	Qty. of Rebar in Pad (W):	30
---------------------------	----	---------------------------	----


Rebar at the top of the concrete pad:

Qty. of Rebar in Pad (L):	30	Qty. of Rebar in Pad (W):	30
---------------------------	----	---------------------------	----

Apply 1.35 factor for e/w Per G: 1.35

**Soil Design Parameters:**

Soil Unit Weight (pcf):	120.0	Soil Buoyant Weight:	50.0	Pcf		
Water Table B.G.S. (ft):	4.5	Unit Weight of Water:	62.4	pcf	Angle from Top of Pad:	30
Ultimate Bearing Pressure (psf):	10400	Ultimate Skin Friction:	175	Psf	Angle from Bottm of Pad:	25
Consider Friction for O.T.M. (Y/N):	No	Consider Friction for bearing (Y/N):	No		Angle from Bottm of Pad:	25
Consider soil hor. resist. for OTM.:	No	Reduction factor on the maximum soil bearing pressure:	1.00			



**Foundation Analysis and Design:**

Uplift Strength Reduction Factor:	0.75	Compression Strength Reduction Factor:	0.75
Total Dry Soil Volume (cu. Ft.):	1845.03	Total Dry Soil Weight (Kips):	221.40
Total Buoyant Soil Volume (cu. Ft.):	0.00	Total Buoyant Soil Weight (Kips):	0.00
Total Effective Soil Weight (Kips):	221.40	Weight from the Concrete Block at Top (K):	0.00
Total Dry Concrete Volume (cu. Ft.):	2517.95	Total Dry Concrete Weight (Kips):	377.69
Total Buoyant Concrete Volume (cu. Ft.):	0.00	Total Buoyant Concrete Weight (Kips):	0.00
Total Effective Concrete Weight (Kips):	377.69	Total Vertical Load on Base (Kips):	646.40

**Check Soil Capacities:**

Calculated Maxium Net Soil Pressure under the base (psf):	1726	< Allowable Factored Soil Bearing (psf):	7800	0.22	OK!
Allowable Foundation Overturning Resistance (kips-ft.):	9090.5	> Design Factored Momont (kips-ft):	3787	0.42	OK!
Factor of Safety Against Overturning (O. R. Moment/Design Moment):	2.40				OK!

Load/  
Capacity  
Ratio



**Check the capacities of Reinforcing Concrete:**

Strength reduction factor (Flexure and axial tension):

Strength reduction factor (Axial compression):

(1) Concrete Pier:

- Vertical Steel Rebar Area (sq. in./each):
- Calculated Moment Capacity (Mn,Kips-Ft):
- Calculated Shear Capacity (Kips):
- Calculated Tension Capacity (Tn, Kips):
- Calculated Compression Capacity (Pn, Kips):
- Moment & Axial Strength Combination:
- Pier Reinforcement Ratio:

(2).Concrete Pad:

- One-Way Design Shear Capacity (L-Direction, Kips):
- One-Way Design Shear Capacity (W-Direction, Kips):
- One-Way Design Shear Capacity (Corner-Corner, Kips):
- Lower Steel Pad Reinforcement Ratio (L-Direct. ):
- Lower Steel Pad Moment Capacity (L-Direction, Kips-ft):
- Lower Steel Pad Moment Capacity (W-Direction, Kips-ft):
- Lower Steel Pad Moment Capacity (Corner-Corner, K-ft):
- Upper Steel Pad Reinforcement Ratio (L-Direct. ):
- Upper Steel Pad Moment Capacity (L-Direc. Kips-ft):
- Upper Steel Pad Moment Capacity (W-Direc. Kips-ft):
- Upper Steel Pad Moment Capacity (Corner-Corner, K-ft):

(3).Check Punching Shear Capacity due to Moment in the Pier:

- Moment transferred by punching shear:
- Max. factored shear stress  $v_{u,AB}$
- Max. factored shear stress  $v_u$

Strength reduction factor (Shear):

Wind Load Factor on Concrete Design:

- Tie / Stirrup Area (sq. in./each):
- > Design Factored Moment (Mu, Kips-
- > Design Factored Shear (Kips):
- > Design Factored Tension (Tu Kips):
- > Design Factored Axial Load (Pu Kips):

OK! Check Tie Spacing (Design/Required):  
Reinforcement Ratio is satisfied per ACI

ad  
Capacity  
Ratio

- One-Way Factored Shear (L-D, Kips): 334.5
- One-Way Factored Shear (W-D., Kips)
- One-Way Factored Shear (C-C, Kips): 319.3
- Lower Steel Pad Reinf. Ratio (W-Direc
- Moment at Bottom ( L-Dir. K-Ft):
- Moment at Bottom ( W-Dir. K-Ft):
- Moment at Bottom ( C-C Dir. K-Ft): 3251.0
- Upper Steel Reinf. Ratio (W-Dir. ):
- Moment at the top (L-Dir K-Ft):
- Moment at the top (W-Dir K-Ft):
- Moment at the top (C-C Dir. K-Ft):

1440.3

k-ft.

Max. factored shear stress  $v_{u,CD}$

Psi

Psi

Factored shear Strength  $\phi v_n$

Psi

Psi

Check Usage of Punching Shear Capacity:

OK!



Maser Consulting Connecticut  
2000 Midlantic Drive, Suite 100  
Mt. Laurel, NJ 08054  
(856) 797-0412  
peter.albano@colliersengineering.com

---

## Antenna Mount Analysis Report and PMI Requirements

### Mount Analysis

SMART Tool Project #: 10081940  
Maser Consulting Connecticut Project #: 21777328A (REV 1)

July 2, 2021

#### Site Information

Site ID: 535838-VZW / THOMPSON NORTH CT  
Site Name: THOMPSON NORTH CT  
Carrier Name: Verizon Wireless  
Address: 44 Rich Road  
North Grosvenordale, Connecticut 06277  
Windham County  
Latitude: 42.011500°  
Longitude: -71.852028°

#### Structure Information

Tower Type: 141-Ft Monopole  
Mount Type: 12.54-Ft T-Arm

**FUZE ID # 16244622**

#### Analysis Results

T-Arm: **96.2% Pass**

#### **\*\*\*Contractor PMI Requirements:**

**Included at the end of this MA report**


**Available & Submitted via portal at <https://pmi.vzwsmart.com>**

**Contractor - Please Review Specific Site PMI Requirements Upon Award**

**Requirements also Noted on Mount Modification Drawings**

**Requirements may also be Noted on A & E drawings**

Report Prepared By: Devin Castillo



07/02/2021

## **Executive Summary:**

The objective of this report is to determine the capacity of the antenna support mount at the subject facility for the final wireless telecommunications configuration, per the applicable codes and standards. Any modification listed under Sources of Information was assumed completed and was included in this analysis.

This analysis is inclusive of the mount structure only and does not address the structural capacity of the supporting structure. This mounting frame was not analyzed as an anchor attachment point for fall protection. All climbing activities are required to have a fall protection plan completed by a competent person.

## **Sources of Information:**

<b>Document Type</b>	<b>Remarks</b>
<i>Radio Frequency Data Sheet (RFDS)</i>	<i>Verizon RFDS, Site ID: 324966, dated June 23, 2021</i>
<i>Mount Mapping Report</i>	<i>Roaming Networks Inc., Site ID: 533838, dated April 26, 2021</i>

## **Analysis Criteria:**

Codes and Standards:	ANSI/TIA-222-H
Wind Parameters:	Basic Wind Speed (Ultimate 3-sec. Gust), $V_{ULT}$ : 120 mph Ice Wind Speed (3-sec. Gust): 50 mph Design Ice Thickness: 1.00 in Risk Category: II Exposure Category: C Topographic Category: 1 Topographic Feature Considered: N/A Topographic Method: N/A Ground Elevation Factor, $K_e$ : 0.978
Seismic Parameters:	$S_s$ : 0.187 $S_1$ : 0.056
Maintenance Parameters:	Wind Speed (3-sec. Gust): 30 mph Maintenance Live Load, $L_v$ : 250 lbs. Maintenance Live Load, $L_m$ : 500 lbs.
Analysis Software:	RISA-3D (V17)

**Final Loading Configuration:**

The following equipment has been considered for the analysis of the mounts:

Mount Elevation (ft)	Equipment Elevation (ft)	Quantity	Manufacturer	Model	Status
136.00	137.00	6	JMA Wireless	MX06FRO660-03	Added
		3	Samsung	MT6407-77A	
		1	Raycap	RVZDC-6627-PF-48	
		3	Samsung	B2/B66A RRH-BR049	
		3	Samsung	B5/B13 RRH-BR04C	
		3	Commscope	CHB626-43-2X	

It is acceptable to install up to any three (3) of the OVP model numbers listed below as required at any location other than the mount face without affecting the structural capacity of the mount. If OVP units are installed on the mount face, a mount re-analysis may be required unless replacing an existing OVP.

Model Number	Ports	AKA
DB-B1-6C-12AB-0Z	6	OVP-6
RVZDC-6627-PF-48	12	OVP-12

**Standard Conditions:**

1. All engineering services are performed on the basis that the information provided to Maser Consulting Connecticut and used in this analysis is current and correct. The existing equipment loading has been applied at locations determined from the supplied documentation and field observations. Any deviation from the loading locations specified in this report shall be communicated to Maser Consulting Connecticut to verify deviation will not adversely impact the analysis.
2. Mounts are assumed to have been properly fabricated, installed and maintained in good condition, twist free and plumb in accordance with its original design and manufacturer’s specifications.

Obvious safety and structural issues/deficiencies noticed at the time of the mount mapping and reported in the Mount Mapping Report are assumed to be corrected and documented as part of the PMI process and are not considered in the mount analysis.

The mount analysis and the mount mapping are not a condition assessment of the mount. Proper maintenance and condition assessments are still required post analysis.

3. For mount analyses completed from other data sources (including new replacement mounts) and not specifically mapped by Maser Consulting Connecticut, the mounts are assumed to have been properly fabricated, installed and maintained in good condition, twist free and plumb in accordance with its original design and manufacturer’s specifications.
4. All member connections are assumed to have been designed to meet or exceed the load carrying capacity of the connected member unless otherwise specified in this report.
5. The mount was checked up to, and including, the bolts that fasten it to the mount collar/attachment and threaded rod connections in collar members if applicable. Local deformation and interaction between the mount collar/attachment and the supporting tower structure are outside the scope of this analysis.

6. All services are performed, results obtained, and recommendations made in accordance with generally accepted engineering principles and practices. Maser Consulting Connecticut is not responsible for the conclusion, opinions, and recommendations made by others based on the information supplied.
7. Structural Steel Grades have been assumed as follows, if applicable, unless otherwise noted in this analysis:
  - o Channel, Solid Round, Angle, Plate      ASTM A36 (Gr. 36)
  - o HSS (Rectangular)                              ASTM 500 (Gr. B-46)
  - o Pipe    ASTM A53 (Gr. B-35)
  - o Threaded Rod                                      F1554 (Gr. 36)
  - o Bolts     ASTM A325

**Discrepancies between in-field conditions and the assumptions listed above may render this analysis invalid unless explicitly approved by Maser Consulting Connecticut.**

**Analysis Results:**

Component	Utilization %	Pass/Fail
Connection	96.2 %	Pass
Standoff	49.5 %	Pass
Face Horizontal	55.9 %	Pass
Mount Pipe	37.3 %	Pass

<b>Structure Rating – (Controlling Utilization of all Components)</b>	<b>96.2%</b>
---	--------------

The Mount has been found structurally adequate for all steel and external connection capacities. Serviceability in accordance with TIA-222-H section 4.9.11.3 has not been considered.

**Recommendation:**

The existing mounts are **SUFFICIENT** for the final loading configuration and does not require modifications.

ANSI/ASSP rigging plan review services compliant with the requirements of ANSI/TIA 322 are available for a Construction Class IV site or other, if required. Separate review fees will apply.

**Attachments:**

1. Mount Photos
2. Mount Mapping Report (for reference only)
3. Analysis Calculations
4. **Contractor Required Post Installation Inspection (PMI) Report Deliverables**
5. Antenna Placement Diagrams
6. TIA Adoption and Wind Speed Usage Letter






Mount Azimuth (Degree) for Each Sector		Tower Leg Azimuth (Degree) for Each Sector		Sector B																					
Sector A:	Deg	Leg A:	Deg	Ant																					
Sector B:	Deg	Leg B:	Deg	Ant <sub>1b</sub>																					
Sector C:	Deg	Leg C:	Deg	Ant <sub>1c</sub>																					
Sector D:	Deg	Leg D:	Deg	Ant																					
Climbing Facility Information				Ant <sub>2b</sub>																					
Location:	Deg	Sector A		Ant <sub>2c</sub>																					
Climbing Facility	Corrosion Type:			Ant <sub>3b</sub>	RRH2x40-AWS																				
	Access:	Climbing path was obstructed.		Ant <sub>3c</sub>																					
	Condition:	Loose hardware.		Ant																					
				Ant <sub>4b</sub>																					
				Ant <sub>4c</sub>																					
				Ant																					
				Ant <sub>5b</sub>																					
				Ant <sub>5c</sub>																					
				Ant on Standoff																					
				Ant on Standoff																					
				Ant on Tower																					
				Ant on Tower																					
				Sector C																					
				Ant																					
				Ant <sub>1b</sub>																					
				Ant <sub>1c</sub>																					
				Ant																					
				Ant <sub>2b</sub>																					
Ant <sub>2c</sub>																									
Ant																									
Ant <sub>3b</sub>	RRH2x40-AWS																								
Ant <sub>3c</sub>																									
Ant																									
Ant <sub>4b</sub>																									
Ant <sub>4c</sub>																									
Ant																									
Ant <sub>5b</sub>																									
Ant <sub>5c</sub>																									
Ant on Standoff																									
Ant on Standoff																									
Ant on Tower																									
Ant on Tower																									
Sector D																									
Ant																									
Ant <sub>1b</sub>																									
Ant <sub>1c</sub>																									
Ant																									
Ant <sub>2b</sub>																									
Ant <sub>2c</sub>																									
Ant																									
Ant <sub>3b</sub>																									
Ant <sub>3c</sub>																									
Ant																									
Ant <sub>4b</sub>																									
Ant <sub>4c</sub>																									
Ant																									
Ant <sub>5b</sub>																									
Ant <sub>5c</sub>																									
Ant on Standoff																									
Ant on Standoff																									
Ant on Tower																									
Ant on Tower																									


Observed Safety and Structural Issues During the Mount Mapping		
Issue #	Description of Issue	Photo #





	<b>Antenna Mount Mapping Form (PATENT PENDING)</b>			FCC #
				1261046
Tower Owner:	SBA	Mapping Date:	04.26.2021	
Site Name:	THOMPSON NORTH CT	Tower Type:	Monopole	
Site Number or ID:	533838	Tower Height (FT):	140.7	
Mapping Contractor:	Roaming Networks inc.	Mount Elevation (FT):	139.58	

This antenna mapping form is the property of TES and under PATENT PENDING. The formation contained herein is considered confidential in nature and is to be used only for the specific customer it was intended for. Reproduction, transmission, publication, modification or disclosure by any method is prohibited except by express written permission of TES. All means and methods are the responsibility of the contractor and the work shall be compliant with ANSI/ASSE A 10.48, OSHA, FCC, FAA and other safety requirements that may apply. TES is not warranting the usability of the safety climb as it must be assessed prior to each use in compliance with OSHA requirements.

**Please Insert Sketches of the Antenna Mount**







Ø2.40"x0.15"x72"

U PL 6"x2"x0.34"x8"  
U BOLTS Ø0.47"

Ø4.45"x0.24"x18"  
U PL 10"x2.5"x0.25"x15"  
BOLTS Ø0.48"  
U BOLTS Ø0.56"

HSS 4"x4"x0.232x35"

Ø3.52"x0.15"x150.5"



HSS 4"x4"x0.232"x35"



BOLTS Ø0.74"x35"

PL 11"x10"x0.51"  
BOLTS Ø0.61"

BENT PL 30"x10"x0.37"  
BOLTS Ø0.74"x35"

5.5"

04/24/2021 13:42:38  
THOMPSON NORTH CT




Envelope Only Solution


Maser Consulting
DC

Antenna Mount Analysis
------------------------

SK - 1
July 2, 2021 at 10:51 AM
535838-VZW_MT_LOT_A_H.r3d






Code Check ( Env )	
Black	No Calc
Red	> 1.0
Pink	.90-1.0
Green	.75-.90
Cyan	.50-.75
Blue	0-.50



Member Code Checks Displayed (Enveloped)  
Envelope Only Solution

Maser Consulting	Antenna Mount Analysis	SK - 2
DC		July 2, 2021 at 10:51 AM
		535838-VZW_MT_LOT_A_H.r3d



Member Shear Checks Displayed (Enveloped)  
Envelope Only Solution

Maser Consulting	Antenna Mount Analysis	SK - 3
DC		July 2, 2021 at 10:51 AM
		535838-VZW_MT_LOT_A_H.r3d



**Basic Load Cases**

	BLC Description	Category	X Gravity	Y Gravity	Z Gravity	Joint	Point	Distributed Area(Me...	Surface(P...
1	Antenna D	None					30		
2	Antenna Di	None					30		
3	Antenna Wo (0 Deg)	None					30		
4	Antenna Wo (30 Deg)	None					30		
5	Antenna Wo (60 Deg)	None					30		
6	Antenna Wo (90 Deg)	None					30		
7	Antenna Wo (120 Deg)	None					30		
8	Antenna Wo (150 Deg)	None					30		
9	Antenna Wo (180 Deg)	None					30		
10	Antenna Wo (210 Deg)	None					30		
11	Antenna Wo (240 Deg)	None					30		
12	Antenna Wo (270 Deg)	None					30		
13	Antenna Wo (300 Deg)	None					30		
14	Antenna Wo (330 Deg)	None					30		
15	Antenna Wi (0 Deg)	None					30		
16	Antenna Wi (30 Deg)	None					30		
17	Antenna Wi (60 Deg)	None					30		
18	Antenna Wi (90 Deg)	None					30		
19	Antenna Wi (120 Deg)	None					30		
20	Antenna Wi (150 Deg)	None					30		
21	Antenna Wi (180 Deg)	None					30		
22	Antenna Wi (210 Deg)	None					30		
23	Antenna Wi (240 Deg)	None					30		
24	Antenna Wi (270 Deg)	None					30		
25	Antenna Wi (300 Deg)	None					30		
26	Antenna Wi (330 Deg)	None					30		
27	Antenna Wm (0 Deg)	None					30		
28	Antenna Wm (30 Deg)	None					30		
29	Antenna Wm (60 Deg)	None					30		
30	Antenna Wm (90 Deg)	None					30		
31	Antenna Wm (120 Deg)	None					30		
32	Antenna Wm (150 Deg)	None					30		
33	Antenna Wm (180 Deg)	None					30		
34	Antenna Wm (210 Deg)	None					30		
35	Antenna Wm (240 Deg)	None					30		
36	Antenna Wm (270 Deg)	None					30		
37	Antenna Wm (300 Deg)	None					30		
38	Antenna Wm (330 Deg)	None					30		
39	Structure D	None		-1					
40	Structure Di	None						8	
41	Structure Wo (0 Deg)	None						16	
42	Structure Wo (30 Deg)	None						16	
43	Structure Wo (60 Deg)	None						16	
44	Structure Wo (90 Deg)	None						16	
45	Structure Wo (120 D...	None						16	
46	Structure Wo (150 D...	None						16	
47	Structure Wo (180 D...	None						16	
48	Structure Wo (210 D...	None						16	
49	Structure Wo (240 D...	None						16	
50	Structure Wo (270 D...	None						16	
51	Structure Wo (300 D...	None						16	
52	Structure Wo (330 D...	None						16	
53	Structure Wi (0 Deg)	None						16	
54	Structure Wi (30 Deg)	None						16	
55	Structure Wi (60 Deg)	None						16	
56	Structure Wi (90 Deg)	None						16	





**Basic Load Cases (Continued)**

	BLC Description	Category	X Gravity	Y Gravity	Z Gravity	Joint	Point	Distributed Area(Me...	Surface(P...
57	Structure Wi (120 De..	None						16	
58	Structure Wi (150 De..	None						16	
59	Structure Wi (180 De..	None						16	
60	Structure Wi (210 De..	None						16	
61	Structure Wi (240 De..	None						16	
62	Structure Wi (270 De..	None						16	
63	Structure Wi (300 De..	None						16	
64	Structure Wi (330 De..	None						16	
65	Structure Wm (0 Deg)	None						16	
66	Structure Wm (30 De..	None						16	
67	Structure Wm (60 De..	None						16	
68	Structure Wm (90 De..	None						16	
69	Structure Wm (120 D..	None						16	
70	Structure Wm (150 D..	None						16	
71	Structure Wm (180 D..	None						16	
72	Structure Wm (210 D..	None						16	
73	Structure Wm (240 D..	None						16	
74	Structure Wm (270 D..	None						16	
75	Structure Wm (300 D..	None						16	
76	Structure Wm (330 D..	None						16	
77	Lm1	None					1		
78	Lm2	None					1		
79	Lv1	None					1		
80	Lv2	None					1		

**Load Combinations**

	Description	Sol..	PD..	SR..	BLCFact..	BLCFact..	BLCFact..	BLCFact..	BLCFact..	BLCFact..	BLCFact..	BLCFact..	BLCFact..	BLCFact..	BLCFact..	BLCFact..	BLCFact..	BLCFact..	BLCFact..	BLCFact..	
1	1.2D+1.0Wo...Yes	Y			1	1.2	39	1.2	3	1	41	1									
2	1.2D+1.0Wo...Yes	Y			1	1.2	39	1.2	4	1	42	1									
3	1.2D+1.0Wo...Yes	Y			1	1.2	39	1.2	5	1	43	1									
4	1.2D+1.0Wo...Yes	Y			1	1.2	39	1.2	6	1	44	1									
5	1.2D+1.0Wo...Yes	Y			1	1.2	39	1.2	7	1	45	1									
6	1.2D+1.0Wo...Yes	Y			1	1.2	39	1.2	8	1	46	1									
7	1.2D+1.0Wo...Yes	Y			1	1.2	39	1.2	9	1	47	1									
8	1.2D+1.0Wo...Yes	Y			1	1.2	39	1.2	10	1	48	1									
9	1.2D+1.0Wo...Yes	Y			1	1.2	39	1.2	11	1	49	1									
10	1.2D+1.0Wo...Yes	Y			1	1.2	39	1.2	12	1	50	1									
11	1.2D+1.0Wo...Yes	Y			1	1.2	39	1.2	13	1	51	1									
12	1.2D+1.0Wo...Yes	Y			1	1.2	39	1.2	14	1	52	1									
13	1.2D + 1.0Di...Yes	Y			1	1.2	39	1.2	2	1	40	1	15	1	53	1					
14	1.2D + 1.0Di...Yes	Y			1	1.2	39	1.2	2	1	40	1	16	1	54	1					
15	1.2D + 1.0Di...Yes	Y			1	1.2	39	1.2	2	1	40	1	17	1	55	1					
16	1.2D + 1.0Di...Yes	Y			1	1.2	39	1.2	2	1	40	1	18	1	56	1					
17	1.2D + 1.0Di...Yes	Y			1	1.2	39	1.2	2	1	40	1	19	1	57	1					
18	1.2D + 1.0Di...Yes	Y			1	1.2	39	1.2	2	1	40	1	20	1	58	1					
19	1.2D + 1.0Di...Yes	Y			1	1.2	39	1.2	2	1	40	1	21	1	59	1					
20	1.2D + 1.0Di...Yes	Y			1	1.2	39	1.2	2	1	40	1	22	1	60	1					
21	1.2D + 1.0Di...Yes	Y			1	1.2	39	1.2	2	1	40	1	23	1	61	1					
22	1.2D + 1.0Di...Yes	Y			1	1.2	39	1.2	2	1	40	1	24	1	62	1					
23	1.2D + 1.0Di...Yes	Y			1	1.2	39	1.2	2	1	40	1	25	1	63	1					
24	1.2D + 1.0Di...Yes	Y			1	1.2	39	1.2	2	1	40	1	26	1	64	1					
25	1.2D + 1.5L... Yes	Y			1	1.2	39	1.2	77	1.5	27	1	65	1							
26	1.2D + 1.5L... Yes	Y			1	1.2	39	1.2	77	1.5	28	1	66	1							
27	1.2D + 1.5L... Yes	Y			1	1.2	39	1.2	77	1.5	29	1	67	1							
28	1.2D + 1.5L... Yes	Y			1	1.2	39	1.2	77	1.5	30	1	68	1							



**Load Combinations (Continued)**

	Description	Sol.	PD	SR	BLC Fact.	BLC Fact.	BLC Fact.	BLC Fact.	BLC Fact.	BLC Fact.	BLC Fact.	BLC Fact.	BLC Fact.	BLC Fact.	BLC Fact.
29	1.2D + 1.5L...	Yes	Y		1	1.2	39	1.2	77	1.5	31	1	69	1	
30	1.2D + 1.5L...	Yes	Y		1	1.2	39	1.2	77	1.5	32	1	70	1	
31	1.2D + 1.5L...	Yes	Y		1	1.2	39	1.2	77	1.5	33	1	71	1	
32	1.2D + 1.5L...	Yes	Y		1	1.2	39	1.2	77	1.5	34	1	72	1	
33	1.2D + 1.5L...	Yes	Y		1	1.2	39	1.2	77	1.5	35	1	73	1	
34	1.2D + 1.5L...	Yes	Y		1	1.2	39	1.2	77	1.5	36	1	74	1	
35	1.2D + 1.5L...	Yes	Y		1	1.2	39	1.2	77	1.5	37	1	75	1	
36	1.2D + 1.5L...	Yes	Y		1	1.2	39	1.2	77	1.5	38	1	76	1	
37	1.2D + 1.5L...	Yes	Y		1	1.2	39	1.2	78	1.5	27	1	65	1	
38	1.2D + 1.5L...	Yes	Y		1	1.2	39	1.2	78	1.5	28	1	66	1	
39	1.2D + 1.5L...	Yes	Y		1	1.2	39	1.2	78	1.5	29	1	67	1	
40	1.2D + 1.5L...	Yes	Y		1	1.2	39	1.2	78	1.5	30	1	68	1	
41	1.2D + 1.5L...	Yes	Y		1	1.2	39	1.2	78	1.5	31	1	69	1	
42	1.2D + 1.5L...	Yes	Y		1	1.2	39	1.2	78	1.5	32	1	70	1	
43	1.2D + 1.5L...	Yes	Y		1	1.2	39	1.2	78	1.5	33	1	71	1	
44	1.2D + 1.5L...	Yes	Y		1	1.2	39	1.2	78	1.5	34	1	72	1	
45	1.2D + 1.5L...	Yes	Y		1	1.2	39	1.2	78	1.5	35	1	73	1	
46	1.2D + 1.5L...	Yes	Y		1	1.2	39	1.2	78	1.5	36	1	74	1	
47	1.2D + 1.5L...	Yes	Y		1	1.2	39	1.2	78	1.5	37	1	75	1	
48	1.2D + 1.5L...	Yes	Y		1	1.2	39	1.2	78	1.5	38	1	76	1	
49	1.2D + 1.5Lv1	Yes	Y		1	1.2	39	1.2	79	1.5					
50	1.2D + 1.5Lv2	Yes	Y		1	1.2	39	1.2	80	1.5					
51	1.4D	Yes	Y		1	1.4	39	1.4							
52	Seismic Mass		Y		1	1	39	1							
53	1.2D + 1.0Ev...		Y		1	1.2	39	1.2	SX		SY	1	SZ	-1	
54	1.2D + 1.0Ev...		Y		1	1.2	39	1.2	SX	.5	SY	1	SZ	-.866	
55	1.2D + 1.0Ev...		Y		1	1.2	39	1.2	SX	.866	SY	1	SZ	-.5	
56	1.2D + 1.0Ev...		Y		1	1.2	39	1.2	SX	1	SY	1	SZ		
57	1.2D + 1.0Ev...		Y		1	1.2	39	1.2	SX	.866	SY	1	SZ	.5	
58	1.2D + 1.0Ev...		Y		1	1.2	39	1.2	SX	.5	SY	1	SZ	.866	
59	1.2D + 1.0Ev...		Y		1	1.2	39	1.2	SX		SY	1	SZ	1	
60	1.2D + 1.0Ev...		Y		1	1.2	39	1.2	SX	-.5	SY	1	SZ	.866	
61	1.2D + 1.0Ev...		Y		1	1.2	39	1.2	SX	-.866	SY	1	SZ	.5	
62	1.2D + 1.0Ev...		Y		1	1.2	39	1.2	SX	-1	SY	1	SZ		
63	1.2D + 1.0Ev...		Y		1	1.2	39	1.2	SX	-.866	SY	1	SZ	-.5	
64	1.2D + 1.0Ev...		Y		1	1.2	39	1.2	SX	-.5	SY	1	SZ	-.866	

**Joint Coordinates and Temperatures**

	Label	X [in]	Y [in]	Z [in]	Temp [F]	Detach From Diap...
1	N1	6.424983	0	0.562113	0	
2	N2	0	0	37.	0	
3	N3	0	9	37.	0	
4	N4	0	-9	37.	0	
5	N5	0	0	41.	0	
6	N6	75.25	0	41.	0	
7	N7	-75.25	0	41.	0	
8	N8	61.25	0	41.	0	
9	N9	61.25	0	44.	0	
10	N10	61.25	39	44.	0	
11	N11	61.25	-33	44.	0	
12	N12	12.25	0	41.	0	
13	N13	12.25	0	44.	0	
14	N14	12.25	39	44.	0	
15	N15	12.25	-33	44.	0	
16	N16	-26.75	0	41.	0	



### Joint Coordinates and Temperatures (Continued)

	Label	X [in]	Y [in]	Z [in]	Temp [F]	Detach From Diap...
17	N17	-26.75	0	44.	0	
18	N18	-26.75	39	44.	0	
19	N19	-26.75	-33	44.	0	
20	N20	-60.75	0	41.	0	
21	N21	-60.75	0	44.	0	
22	N22	-60.75	39	44.	0	
23	N23	-60.75	-33	44.	0	
24	N24	5.083778	0	25.182307	0	
25	N25	5.083778	30	25.182307	0	
26	N26	2.083778	0	25.182307	0	
27	N27	5.083778	-6	25.182307	0	

### Hot Rolled Steel Section Sets

	Label	Shape	Type	Design List	Material	Design R...	A [in2]	Iyy [in4]	Izz [in4]	J [in4]
1	Standoff	HSS4X4X4	Beam	Tube	A500 Gr. B 42	Typical	3.37	7.8	7.8	12.8
2	Mast Pipe	PIPE 4.0	Column	Pipe	A53 Gr. B	Typical	2.96	6.82	6.82	13.6
3	Face Horizontal	PIPE 3.0	Beam	Pipe	A53 Gr. B	Typical	2.07	2.85	2.85	5.69
4	Mount Pipe	PIPE 2.0	Column	Pipe	A53 Gr. B	Typical	1.02	.627	.627	1.25
5	Dual Antenna	PIPE 2.5	Column	Pipe	A53 Gr. B	Typical	1.61	1.45	1.45	2.89

### Hot Rolled Steel Properties

	Label	E [ksi]	G [ksi]	Nu	Therm (/1E...	Density[k/ft...	Yield[ksi]	Ry	Fu[ksi]	Rt
1	A36 Gr.36	29000	11154	.3	.65	.49	36	1.5	58	1.2
2	A53 Gr. B	29000	11154	.3	.65	.49	35	1.5	60	1.2
3	A572 Gr.50	29000	11154	.3	.65	.49	50	1.1	65	1.1
4	A992	29000	11154	.3	.65	.49	50	1.1	65	1.1
5	A500 Gr. B 42	29000	11154	.3	.65	.49	42	1.4	58	1.3
6	A500 Gr. B 46	29000	11154	.3	.65	.49	46	1.4	58	1.3

### Member Primary Data

	Label	I Joint	J Joint	K Joint	Rotate(deg)	Section/Shape	Type	Design List	Material	Design Rules
1	M1	N1	N2			Standoff	Beam	Tube	A500 Gr. ...	Typical
2	M2	N3	N4			Mast Pipe	Column	Pipe	A53 Gr. B	Typical
3	M3	N2	N5			RIGID	None	None	RIGID	Typical
4	M4	N7	N6			Face Horizontal	Beam	Pipe	A53 Gr. B	Typical
5	M5	N8	N9			RIGID	None	None	RIGID	Typical
6	MP1A	N10	N11			Mount Pipe	Column	Pipe	A53 Gr. B	Typical
7	M7	N12	N13			RIGID	None	None	RIGID	Typical
8	MP2A	N14	N15			Dual Antenna	Column	Pipe	A53 Gr. B	Typical
9	M9	N16	N17			RIGID	None	None	RIGID	Typical
10	MP3A	N18	N19			Mount Pipe	Column	Pipe	A53 Gr. B	Typical
11	M11	N20	N21			RIGID	None	None	RIGID	Typical
12	MP4A	N22	N23			Mount Pipe	Column	Pipe	A53 Gr. B	Typical
13	M13	N25	N27			Mount Pipe	Column	Pipe	A53 Gr. B	Typical
14	M14	N26	N24			RIGID	None	None	RIGID	Typical

### Member Advanced Data

	Label	I Release	J Release	I Offset[in]	J Offset[in]	T/C Only	Physical	Defl Rat...	Analysis ...	Inactive	Seismic...
1	M1						Yes				None
2	M2						Yes	** NA **			None
3	M3						Yes	** NA **			None



**Member Advanced Data (Continued)**

	Label	I Release	J Release	I Offset[in]	J Offset[in]	T/C Only	Physical	Defl Rat...	Analysis ...	Inactive	Seismic...
4	M4						Yes				None
5	M5						Yes	** NA **			None
6	MP1A						Yes	** NA **			None
7	M7						Yes	** NA **			None
8	MP2A						Yes	** NA **			None
9	M9						Yes	** NA **			None
10	MP3A						Yes	** NA **			None
11	M11						Yes	** NA **			None
12	MP4A						Yes	** NA **			None
13	M13						Yes	** NA **			None
14	M14						Yes	** NA **			None

**Member Point Loads (BLC 1 : Antenna D)**

	Member Label	Direction	Magnitude[lb,k-ft]	Location[in, %]
1	MP3A	Y	-19.4	48
2	MP3A	My	.01	48
3	MP3A	Mz	0	48
4	MP2A	Y	-23	6
5	MP2A	My	-.011	6
6	MP2A	Mz	.015	6
7	MP2A	Y	-23	66
8	MP2A	My	-.011	66
9	MP2A	Mz	.015	66
10	MP2A	Y	-23	6
11	MP2A	My	-.011	6
12	MP2A	Mz	-.015	6
13	MP2A	Y	-23	66
14	MP2A	My	-.011	66
15	MP2A	Mz	-.015	66
16	MP3A	Y	-43.55	24
17	MP3A	My	-.022	24
18	MP3A	Mz	0	24
19	MP3A	Y	-43.55	48
20	MP3A	My	-.022	48
21	MP3A	Mz	0	48
22	M13	Y	-32	12
23	M13	My	0	12
24	M13	Mz	0	12
25	MP3A	Y	-84.4	18
26	MP3A	My	.042	18
27	MP3A	Mz	0	18
28	MP2A	Y	-70.3	18
29	MP2A	My	.035	18
30	MP2A	Mz	0	18

**Member Point Loads (BLC 2 : Antenna Di)**

	Member Label	Direction	Magnitude[lb,k-ft]	Location[in, %]
1	MP3A	Y	-16.85	48
2	MP3A	My	.008	48
3	MP3A	Mz	0	48
4	MP2A	Y	-82.321	6
5	MP2A	My	-.041	6
6	MP2A	Mz	.055	6
7	MP2A	Y	-82.321	66
8	MP2A	My	-.041	66



**Member Point Loads (BLC 2 : Antenna Di) (Continued)**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
9	MP2A	Mz	.055	66
10	MP2A	Y	-82.321	6
11	MP2A	My	-.041	6
12	MP2A	Mz	-.055	6
13	MP2A	Y	-82.321	66
14	MP2A	My	-.041	66
15	MP2A	Mz	-.055	66
16	MP3A	Y	-35.549	24
17	MP3A	My	-.018	24
18	MP3A	Mz	0	24
19	MP3A	Y	-35.549	48
20	MP3A	My	-.018	48
21	MP3A	Mz	0	48
22	M13	Y	-75.814	12
23	M13	My	0	12
24	M13	Mz	0	12
25	MP3A	Y	-44.818	18
26	MP3A	My	.022	18
27	MP3A	Mz	0	18
28	MP2A	Y	-40.305	18
29	MP2A	My	.02	18
30	MP2A	Mz	0	18

**Member Point Loads (BLC 3 : Antenna Wo (0 Deg))**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	MP3A	X	0	48
2	MP3A	Z	-36.198	48
3	MP3A	Mx	0	48
4	MP2A	X	0	6
5	MP2A	Z	-205.33	6
6	MP2A	Mx	-.137	6
7	MP2A	X	0	66
8	MP2A	Z	-205.33	66
9	MP2A	Mx	-.137	66
10	MP2A	X	0	6
11	MP2A	Z	-205.33	6
12	MP2A	Mx	.137	6
13	MP2A	X	0	66
14	MP2A	Z	-205.33	66
15	MP2A	Mx	.137	66
16	MP3A	X	0	24
17	MP3A	Z	-97.776	24
18	MP3A	Mx	0	24
19	MP3A	X	0	48
20	MP3A	Z	-97.776	48
21	MP3A	Mx	0	48
22	M13	X	0	12
23	M13	Z	-144.362	12
24	M13	Mx	0	12
25	MP3A	X	0	18
26	MP3A	Z	-77.805	18
27	MP3A	Mx	0	18
28	MP2A	X	0	18
29	MP2A	Z	-77.805	18
30	MP2A	Mx	0	18



**Member Point Loads (BLC 4 : Antenna Wo (30 Deg))**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	MP3A	X	14.62	48
2	MP3A	Z	-25.323	48
3	MP3A	Mx	.007	48
4	MP2A	X	96.08	6
5	MP2A	Z	-166.416	6
6	MP2A	Mx	-.159	6
7	MP2A	X	96.08	66
8	MP2A	Z	-166.416	66
9	MP2A	Mx	-.159	66
10	MP2A	X	96.08	6
11	MP2A	Z	-166.416	6
12	MP2A	Mx	.063	6
13	MP2A	X	96.08	66
14	MP2A	Z	-166.416	66
15	MP2A	Mx	.063	66
16	MP3A	X	41.451	24
17	MP3A	Z	-71.795	24
18	MP3A	Mx	-.021	24
19	MP3A	X	41.451	48
20	MP3A	Z	-71.795	48
21	MP3A	Mx	-.021	48
22	M13	X	78.845	12
23	M13	Z	-136.563	12
24	M13	Mx	0	12
25	MP3A	X	35.678	18
26	MP3A	Z	-61.796	18
27	MP3A	Mx	.018	18
28	MP2A	X	34.443	18
29	MP2A	Z	-59.656	18
30	MP2A	Mx	.017	18

**Member Point Loads (BLC 5 : Antenna Wo (60 Deg))**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	MP3A	X	13.273	48
2	MP3A	Z	-7.663	48
3	MP3A	Mx	.007	48
4	MP2A	X	143.607	6
5	MP2A	Z	-82.912	6
6	MP2A	Mx	-.127	6
7	MP2A	X	143.607	66
8	MP2A	Z	-82.912	66
9	MP2A	Mx	-.127	66
10	MP2A	X	143.607	6
11	MP2A	Z	-82.912	6
12	MP2A	Mx	-.017	6
13	MP2A	X	143.607	66
14	MP2A	Z	-82.912	66
15	MP2A	Mx	-.017	66
16	MP3A	X	46.032	24
17	MP3A	Z	-26.577	24
18	MP3A	Mx	-.023	24
19	MP3A	X	46.032	48
20	MP3A	Z	-26.577	48
21	MP3A	Mx	-.023	48
22	M13	X	125.021	12
23	M13	Z	-72.181	12



**Member Point Loads (BLC 5 : Antenna Wo (60 Deg)) (Continued)**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
24	M13	Mx	0	12
25	MP3A	X	50.626	18
26	MP3A	Z	-29.229	18
27	MP3A	Mx	.025	18
28	MP2A	X	44.207	18
29	MP2A	Z	-25.523	18
30	MP2A	Mx	.022	18

**Member Point Loads (BLC 6 : Antenna Wo (90 Deg))**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	MP3A	X	8.37	48
2	MP3A	Z	0	48
3	MP3A	Mx	.004	48
4	MP2A	X	152.655	6
5	MP2A	Z	0	6
6	MP2A	Mx	-.076	6
7	MP2A	X	152.655	66
8	MP2A	Z	0	66
9	MP2A	Mx	-.076	66
10	MP2A	X	152.655	6
11	MP2A	Z	0	6
12	MP2A	Mx	-.076	6
13	MP2A	X	152.655	66
14	MP2A	Z	0	66
15	MP2A	Mx	-.076	66
16	MP3A	X	38.279	24
17	MP3A	Z	0	24
18	MP3A	Mx	-.019	24
19	MP3A	X	38.279	48
20	MP3A	Z	0	48
21	MP3A	Mx	-.019	48
22	M13	X	117.706	12
23	M13	Z	0	12
24	M13	Mx	0	12
25	MP3A	X	52.009	18
26	MP3A	Z	0	18
27	MP3A	Mx	.026	18
28	MP2A	X	42.127	18
29	MP2A	Z	0	18
30	MP2A	Mx	.021	18

**Member Point Loads (BLC 7 : Antenna Wo (120 Deg))**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	MP3A	X	13.273	48
2	MP3A	Z	7.663	48
3	MP3A	Mx	.007	48
4	MP2A	X	143.607	6
5	MP2A	Z	82.912	6
6	MP2A	Mx	-.017	6
7	MP2A	X	143.607	66
8	MP2A	Z	82.912	66
9	MP2A	Mx	-.017	66
10	MP2A	X	143.607	6
11	MP2A	Z	82.912	6
12	MP2A	Mx	-.127	6
13	MP2A	X	143.607	66

**Member Point Loads (BLC 7 : Antenna Wo (120 Deg)) (Continued)**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
14	MP2A	Z	82.912	66
15	MP2A	Mx	-.127	66
16	MP3A	X	46.032	24
17	MP3A	Z	26.577	24
18	MP3A	Mx	-.023	24
19	MP3A	X	46.032	48
20	MP3A	Z	26.577	48
21	MP3A	Mx	-.023	48
22	M13	X	90.394	12
23	M13	Z	52.189	12
24	M13	Mx	0	12
25	MP3A	X	50.626	18
26	MP3A	Z	29.229	18
27	MP3A	Mx	.025	18
28	MP2A	X	44.207	18
29	MP2A	Z	25.523	18
30	MP2A	Mx	.022	18

**Member Point Loads (BLC 8 : Antenna Wo (150 Deg))**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	MP3A	X	14.62	48
2	MP3A	Z	25.323	48
3	MP3A	Mx	.007	48
4	MP2A	X	96.08	6
5	MP2A	Z	166.416	6
6	MP2A	Mx	.063	6
7	MP2A	X	96.08	66
8	MP2A	Z	166.416	66
9	MP2A	Mx	.063	66
10	MP2A	X	96.08	6
11	MP2A	Z	166.416	6
12	MP2A	Mx	-.159	6
13	MP2A	X	96.08	66
14	MP2A	Z	166.416	66
15	MP2A	Mx	-.159	66
16	MP3A	X	41.451	24
17	MP3A	Z	71.795	24
18	MP3A	Mx	-.021	24
19	MP3A	X	41.451	48
20	MP3A	Z	71.795	48
21	MP3A	Mx	-.021	48
22	M13	X	58.853	12
23	M13	Z	101.937	12
24	M13	Mx	0	12
25	MP3A	X	35.678	18
26	MP3A	Z	61.796	18
27	MP3A	Mx	.018	18
28	MP2A	X	34.443	18
29	MP2A	Z	59.656	18
30	MP2A	Mx	.017	18

**Member Point Loads (BLC 9 : Antenna Wo (180 Deg))**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	MP3A	X	0	48
2	MP3A	Z	36.198	48
3	MP3A	Mx	0	48





**Member Point Loads (BLC 9 : Antenna Wo (180 Deg)) (Continued)**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
4	MP2A	X	0	6
5	MP2A	Z	205.33	6
6	MP2A	Mx	.137	6
7	MP2A	X	0	66
8	MP2A	Z	205.33	66
9	MP2A	Mx	.137	66
10	MP2A	X	0	6
11	MP2A	Z	205.33	6
12	MP2A	Mx	-.137	6
13	MP2A	X	0	66
14	MP2A	Z	205.33	66
15	MP2A	Mx	-.137	66
16	MP3A	X	0	24
17	MP3A	Z	97.776	24
18	MP3A	Mx	0	24
19	MP3A	X	0	48
20	MP3A	Z	97.776	48
21	MP3A	Mx	0	48
22	M13	X	0	12
23	M13	Z	144.362	12
24	M13	Mx	0	12
25	MP3A	X	0	18
26	MP3A	Z	77.805	18
27	MP3A	Mx	0	18
28	MP2A	X	0	18
29	MP2A	Z	77.805	18
30	MP2A	Mx	0	18

**Member Point Loads (BLC 10 : Antenna Wo (210 Deg))**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	MP3A	X	-14.62	48
2	MP3A	Z	25.323	48
3	MP3A	Mx	-.007	48
4	MP2A	X	-96.08	6
5	MP2A	Z	166.416	6
6	MP2A	Mx	.159	6
7	MP2A	X	-96.08	66
8	MP2A	Z	166.416	66
9	MP2A	Mx	.159	66
10	MP2A	X	-96.08	6
11	MP2A	Z	166.416	6
12	MP2A	Mx	-.063	6
13	MP2A	X	-96.08	66
14	MP2A	Z	166.416	66
15	MP2A	Mx	-.063	66
16	MP3A	X	-41.451	24
17	MP3A	Z	71.795	24
18	MP3A	Mx	.021	24
19	MP3A	X	-41.451	48
20	MP3A	Z	71.795	48
21	MP3A	Mx	.021	48
22	M13	X	-78.845	12
23	M13	Z	136.563	12
24	M13	Mx	0	12
25	MP3A	X	-35.678	18
26	MP3A	Z	61.796	18



**Member Point Loads (BLC 10 : Antenna Wo (210 Deg)) (Continued)**

	Member Label	Direction	Magnitude[lb,k-ft]	Location[in, %]
27	MP3A	Mx	-.018	18
28	MP2A	X	-34.443	18
29	MP2A	Z	59.656	18
30	MP2A	Mx	-.017	18

**Member Point Loads (BLC 11 : Antenna Wo (240 Deg))**

	Member Label	Direction	Magnitude[lb,k-ft]	Location[in, %]
1	MP3A	X	-13.273	48
2	MP3A	Z	7.663	48
3	MP3A	Mx	-.007	48
4	MP2A	X	-143.607	6
5	MP2A	Z	82.912	6
6	MP2A	Mx	.127	6
7	MP2A	X	-143.607	66
8	MP2A	Z	82.912	66
9	MP2A	Mx	.127	66
10	MP2A	X	-143.607	6
11	MP2A	Z	82.912	6
12	MP2A	Mx	.017	6
13	MP2A	X	-143.607	66
14	MP2A	Z	82.912	66
15	MP2A	Mx	.017	66
16	MP3A	X	-46.032	24
17	MP3A	Z	26.577	24
18	MP3A	Mx	.023	24
19	MP3A	X	-46.032	48
20	MP3A	Z	26.577	48
21	MP3A	Mx	.023	48
22	M13	X	-125.021	12
23	M13	Z	72.181	12
24	M13	Mx	0	12
25	MP3A	X	-50.626	18
26	MP3A	Z	29.229	18
27	MP3A	Mx	-.025	18
28	MP2A	X	-44.207	18
29	MP2A	Z	25.523	18
30	MP2A	Mx	-.022	18

**Member Point Loads (BLC 12 : Antenna Wo (270 Deg))**

	Member Label	Direction	Magnitude[lb,k-ft]	Location[in, %]
1	MP3A	X	-8.37	48
2	MP3A	Z	0	48
3	MP3A	Mx	-.004	48
4	MP2A	X	-152.655	6
5	MP2A	Z	0	6
6	MP2A	Mx	.076	6
7	MP2A	X	-152.655	66
8	MP2A	Z	0	66
9	MP2A	Mx	.076	66
10	MP2A	X	-152.655	6
11	MP2A	Z	0	6
12	MP2A	Mx	.076	6
13	MP2A	X	-152.655	66
14	MP2A	Z	0	66
15	MP2A	Mx	.076	66
16	MP3A	X	-38.279	24



**Member Point Loads (BLC 12 : Antenna Wo (270 Deg)) (Continued)**

	Member Label	Direction	Magnitude[lb,k-ft]	Location[in, %]
17	MP3A	Z	0	24
18	MP3A	Mx	.019	24
19	MP3A	X	-38.279	48
20	MP3A	Z	0	48
21	MP3A	Mx	.019	48
22	M13	X	-117.706	12
23	M13	Z	0	12
24	M13	Mx	0	12
25	MP3A	X	-52.009	18
26	MP3A	Z	0	18
27	MP3A	Mx	-.026	18
28	MP2A	X	-42.127	18
29	MP2A	Z	0	18
30	MP2A	Mx	-.021	18

**Member Point Loads (BLC 13 : Antenna Wo (300 Deg))**

	Member Label	Direction	Magnitude[lb,k-ft]	Location[in, %]
1	MP3A	X	-13.273	48
2	MP3A	Z	-7.663	48
3	MP3A	Mx	-.007	48
4	MP2A	X	-143.607	6
5	MP2A	Z	-82.912	6
6	MP2A	Mx	.017	6
7	MP2A	X	-143.607	66
8	MP2A	Z	-82.912	66
9	MP2A	Mx	.017	66
10	MP2A	X	-143.607	6
11	MP2A	Z	-82.912	6
12	MP2A	Mx	.127	6
13	MP2A	X	-143.607	66
14	MP2A	Z	-82.912	66
15	MP2A	Mx	.127	66
16	MP3A	X	-46.032	24
17	MP3A	Z	-26.577	24
18	MP3A	Mx	.023	24
19	MP3A	X	-46.032	48
20	MP3A	Z	-26.577	48
21	MP3A	Mx	.023	48
22	M13	X	-90.394	12
23	M13	Z	-52.189	12
24	M13	Mx	0	12
25	MP3A	X	-50.626	18
26	MP3A	Z	-29.229	18
27	MP3A	Mx	-.025	18
28	MP2A	X	-44.207	18
29	MP2A	Z	-25.523	18
30	MP2A	Mx	-.022	18

**Member Point Loads (BLC 14 : Antenna Wo (330 Deg))**

	Member Label	Direction	Magnitude[lb,k-ft]	Location[in, %]
1	MP3A	X	-14.62	48
2	MP3A	Z	-25.323	48
3	MP3A	Mx	-.007	48
4	MP2A	X	-96.08	6
5	MP2A	Z	-166.416	6
6	MP2A	Mx	-.063	6



**Member Point Loads (BLC 14 : Antenna Wo (330 Deg)) (Continued)**

	Member Label	Direction	Magnitude[lb,k-ft]	Location[in, %]
7	MP2A	X	-96.08	66
8	MP2A	Z	-166.416	66
9	MP2A	Mx	-.063	66
10	MP2A	X	-96.08	6
11	MP2A	Z	-166.416	6
12	MP2A	Mx	.159	6
13	MP2A	X	-96.08	66
14	MP2A	Z	-166.416	66
15	MP2A	Mx	.159	66
16	MP3A	X	-41.451	24
17	MP3A	Z	-71.795	24
18	MP3A	Mx	.021	24
19	MP3A	X	-41.451	48
20	MP3A	Z	-71.795	48
21	MP3A	Mx	.021	48
22	M13	X	-58.853	12
23	M13	Z	-101.937	12
24	M13	Mx	0	12
25	MP3A	X	-35.678	18
26	MP3A	Z	-61.796	18
27	MP3A	Mx	-.018	18
28	MP2A	X	-34.443	18
29	MP2A	Z	-59.656	18
30	MP2A	Mx	-.017	18

**Member Point Loads (BLC 15 : Antenna Wi (0 Deg))**

	Member Label	Direction	Magnitude[lb,k-ft]	Location[in, %]
1	MP3A	X	0	48
2	MP3A	Z	-8.182	48
3	MP3A	Mx	0	48
4	MP2A	X	0	6
5	MP2A	Z	-38.867	6
6	MP2A	Mx	-.026	6
7	MP2A	X	0	66
8	MP2A	Z	-38.867	66
9	MP2A	Mx	-.026	66
10	MP2A	X	0	6
11	MP2A	Z	-38.867	6
12	MP2A	Mx	.026	6
13	MP2A	X	0	66
14	MP2A	Z	-38.867	66
15	MP2A	Mx	.026	66
16	MP3A	X	0	24
17	MP3A	Z	-19.173	24
18	MP3A	Mx	0	24
19	MP3A	X	0	48
20	MP3A	Z	-19.173	48
21	MP3A	Mx	0	48
22	M13	X	0	12
23	M13	Z	-28.65	12
24	M13	Mx	0	12
25	MP3A	X	0	18
26	MP3A	Z	-16.158	18
27	MP3A	Mx	0	18
28	MP2A	X	0	18
29	MP2A	Z	-16.158	18



**Member Point Loads (BLC 15 : Antenna Wi (0 Deg)) (Continued)**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
30	MP2A	Mx	0	18

**Member Point Loads (BLC 16 : Antenna Wi (30 Deg))**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	MP3A	X	3.379	48
2	MP3A	Z	-5.853	48
3	MP3A	Mx	.002	48
4	MP2A	X	18.25	6
5	MP2A	Z	-31.61	6
6	MP2A	Mx	-.03	6
7	MP2A	X	18.25	66
8	MP2A	Z	-31.61	66
9	MP2A	Mx	-.03	66
10	MP2A	X	18.25	6
11	MP2A	Z	-31.61	6
12	MP2A	Mx	.012	6
13	MP2A	X	18.25	66
14	MP2A	Z	-31.61	66
15	MP2A	Mx	.012	66
16	MP3A	X	8.211	24
17	MP3A	Z	-14.221	24
18	MP3A	Mx	-.004	24
19	MP3A	X	8.211	48
20	MP3A	Z	-14.221	48
21	MP3A	Mx	-.004	48
22	M13	X	15.554	12
23	M13	Z	-26.94	12
24	M13	Mx	0	12
25	MP3A	X	7.464	18
26	MP3A	Z	-12.928	18
27	MP3A	Mx	.004	18
28	MP2A	X	7.23	18
29	MP2A	Z	-12.523	18
30	MP2A	Mx	.004	18

**Member Point Loads (BLC 17 : Antenna Wi (60 Deg))**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	MP3A	X	3.388	48
2	MP3A	Z	-1.956	48
3	MP3A	Mx	.002	48
4	MP2A	X	27.512	6
5	MP2A	Z	-15.884	6
6	MP2A	Mx	-.024	6
7	MP2A	X	27.512	66
8	MP2A	Z	-15.884	66
9	MP2A	Mx	-.024	66
10	MP2A	X	27.512	6
11	MP2A	Z	-15.884	6
12	MP2A	Mx	-.003	6
13	MP2A	X	27.512	66
14	MP2A	Z	-15.884	66
15	MP2A	Mx	-.003	66
16	MP3A	X	9.455	24
17	MP3A	Z	-5.459	24
18	MP3A	Mx	-.005	24
19	MP3A	X	9.455	48



Company : Maser Consulting  
 Designer : DC  
 Job Number :  
 Model Name : Antenna Mount Analysis

July 2, 2021  
 10:51 AM  
 Checked By: DX

**Member Point Loads (BLC 17 : Antenna Wi (60 Deg)) (Continued)**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
20	MP3A	Z	-5.459	48
21	MP3A	Mx	-.005	48
22	M13	X	24.811	12
23	M13	Z	-14.325	12
24	M13	Mx	0	12
25	MP3A	X	10.798	18
26	MP3A	Z	-6.234	18
27	MP3A	Mx	.005	18
28	MP2A	X	9.584	18
29	MP2A	Z	-5.533	18
30	MP2A	Mx	.005	18

**Member Point Loads (BLC 18 : Antenna Wi (90 Deg))**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	MP3A	X	2.489	48
2	MP3A	Z	0	48
3	MP3A	Mx	.001	48
4	MP2A	X	29.402	6
5	MP2A	Z	0	6
6	MP2A	Mx	-.015	6
7	MP2A	X	29.402	66
8	MP2A	Z	0	66
9	MP2A	Mx	-.015	66
10	MP2A	X	29.402	6
11	MP2A	Z	0	6
12	MP2A	Mx	-.015	6
13	MP2A	X	29.402	66
14	MP2A	Z	0	66
15	MP2A	Mx	-.015	66
16	MP3A	X	8.166	24
17	MP3A	Z	0	24
18	MP3A	Mx	-.004	24
19	MP3A	X	8.166	48
20	MP3A	Z	0	48
21	MP3A	Mx	-.004	48
22	M13	X	23.734	12
23	M13	Z	0	12
24	M13	Mx	0	12
25	MP3A	X	11.238	18
26	MP3A	Z	0	18
27	MP3A	Mx	.006	18
28	MP2A	X	9.369	18
29	MP2A	Z	0	18
30	MP2A	Mx	.005	18

**Member Point Loads (BLC 19 : Antenna Wi (120 Deg))**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	MP3A	X	3.388	48
2	MP3A	Z	1.956	48
3	MP3A	Mx	.002	48
4	MP2A	X	27.512	6
5	MP2A	Z	15.884	6
6	MP2A	Mx	-.003	6
7	MP2A	X	27.512	66
8	MP2A	Z	15.884	66
9	MP2A	Mx	-.003	66



**Member Point Loads (BLC 19 : Antenna Wi (120 Deg)) (Continued)**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
10	MP2A	X	27.512	6
11	MP2A	Z	15.884	6
12	MP2A	Mx	-.024	6
13	MP2A	X	27.512	66
14	MP2A	Z	15.884	66
15	MP2A	Mx	-.024	66
16	MP3A	X	9.455	24
17	MP3A	Z	5.459	24
18	MP3A	Mx	-.005	24
19	MP3A	X	9.455	48
20	MP3A	Z	5.459	48
21	MP3A	Mx	-.005	48
22	M13	X	18.426	12
23	M13	Z	10.638	12
24	M13	Mx	0	12
25	MP3A	X	10.798	18
26	MP3A	Z	6.234	18
27	MP3A	Mx	.005	18
28	MP2A	X	9.584	18
29	MP2A	Z	5.533	18
30	MP2A	Mx	.005	18

**Member Point Loads (BLC 20 : Antenna Wi (150 Deg))**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	MP3A	X	3.379	48
2	MP3A	Z	5.853	48
3	MP3A	Mx	.002	48
4	MP2A	X	18.25	6
5	MP2A	Z	31.61	6
6	MP2A	Mx	.012	6
7	MP2A	X	18.25	66
8	MP2A	Z	31.61	66
9	MP2A	Mx	.012	66
10	MP2A	X	18.25	6
11	MP2A	Z	31.61	6
12	MP2A	Mx	-.03	6
13	MP2A	X	18.25	66
14	MP2A	Z	31.61	66
15	MP2A	Mx	-.03	66
16	MP3A	X	8.211	24
17	MP3A	Z	14.221	24
18	MP3A	Mx	-.004	24
19	MP3A	X	8.211	48
20	MP3A	Z	14.221	48
21	MP3A	Mx	-.004	48
22	M13	X	11.867	12
23	M13	Z	20.554	12
24	M13	Mx	0	12
25	MP3A	X	7.464	18
26	MP3A	Z	12.928	18
27	MP3A	Mx	.004	18
28	MP2A	X	7.23	18
29	MP2A	Z	12.523	18
30	MP2A	Mx	.004	18



**Member Point Loads (BLC 21 : Antenna Wi (180 Deg))**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	MP3A	X	0	48
2	MP3A	Z	8.182	48
3	MP3A	Mx	0	48
4	MP2A	X	0	6
5	MP2A	Z	38.867	6
6	MP2A	Mx	.026	6
7	MP2A	X	0	66
8	MP2A	Z	38.867	66
9	MP2A	Mx	.026	66
10	MP2A	X	0	6
11	MP2A	Z	38.867	6
12	MP2A	Mx	-.026	6
13	MP2A	X	0	66
14	MP2A	Z	38.867	66
15	MP2A	Mx	-.026	66
16	MP3A	X	0	24
17	MP3A	Z	19.173	24
18	MP3A	Mx	0	24
19	MP3A	X	0	48
20	MP3A	Z	19.173	48
21	MP3A	Mx	0	48
22	M13	X	0	12
23	M13	Z	28.65	12
24	M13	Mx	0	12
25	MP3A	X	0	18
26	MP3A	Z	16.158	18
27	MP3A	Mx	0	18
28	MP2A	X	0	18
29	MP2A	Z	16.158	18
30	MP2A	Mx	0	18

**Member Point Loads (BLC 22 : Antenna Wi (210 Deg))**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	MP3A	X	-3.379	48
2	MP3A	Z	5.853	48
3	MP3A	Mx	-.002	48
4	MP2A	X	-18.25	6
5	MP2A	Z	31.61	6
6	MP2A	Mx	.03	6
7	MP2A	X	-18.25	66
8	MP2A	Z	31.61	66
9	MP2A	Mx	.03	66
10	MP2A	X	-18.25	6
11	MP2A	Z	31.61	6
12	MP2A	Mx	-.012	6
13	MP2A	X	-18.25	66
14	MP2A	Z	31.61	66
15	MP2A	Mx	-.012	66
16	MP3A	X	-8.211	24
17	MP3A	Z	14.221	24
18	MP3A	Mx	.004	24
19	MP3A	X	-8.211	48
20	MP3A	Z	14.221	48
21	MP3A	Mx	.004	48
22	M13	X	-15.554	12
23	M13	Z	26.94	12





**Member Point Loads (BLC 22 : Antenna Wi (210 Deg)) (Continued)**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
24	M13	Mx	0	12
25	MP3A	X	-7.464	18
26	MP3A	Z	12.928	18
27	MP3A	Mx	-.004	18
28	MP2A	X	-7.23	18
29	MP2A	Z	12.523	18
30	MP2A	Mx	-.004	18

**Member Point Loads (BLC 23 : Antenna Wi (240 Deg))**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	MP3A	X	-3.388	48
2	MP3A	Z	1.956	48
3	MP3A	Mx	-.002	48
4	MP2A	X	-27.512	6
5	MP2A	Z	15.884	6
6	MP2A	Mx	.024	6
7	MP2A	X	-27.512	66
8	MP2A	Z	15.884	66
9	MP2A	Mx	.024	66
10	MP2A	X	-27.512	6
11	MP2A	Z	15.884	6
12	MP2A	Mx	.003	6
13	MP2A	X	-27.512	66
14	MP2A	Z	15.884	66
15	MP2A	Mx	.003	66
16	MP3A	X	-9.455	24
17	MP3A	Z	5.459	24
18	MP3A	Mx	.005	24
19	MP3A	X	-9.455	48
20	MP3A	Z	5.459	48
21	MP3A	Mx	.005	48
22	M13	X	-24.811	12
23	M13	Z	14.325	12
24	M13	Mx	0	12
25	MP3A	X	-10.798	18
26	MP3A	Z	6.234	18
27	MP3A	Mx	-.005	18
28	MP2A	X	-9.584	18
29	MP2A	Z	5.533	18
30	MP2A	Mx	-.005	18

**Member Point Loads (BLC 24 : Antenna Wi (270 Deg))**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	MP3A	X	-2.489	48
2	MP3A	Z	0	48
3	MP3A	Mx	-.001	48
4	MP2A	X	-29.402	6
5	MP2A	Z	0	6
6	MP2A	Mx	.015	6
7	MP2A	X	-29.402	66
8	MP2A	Z	0	66
9	MP2A	Mx	.015	66
10	MP2A	X	-29.402	6
11	MP2A	Z	0	6
12	MP2A	Mx	.015	6
13	MP2A	X	-29.402	66

**Member Point Loads (BLC 24 : Antenna Wi (270 Deg)) (Continued)**

	Member Label	Direction	Magnitude[lb,k-ft]	Location[in, %]
14	MP2A	Z	0	66
15	MP2A	Mx	.015	66
16	MP3A	X	-8.166	24
17	MP3A	Z	0	24
18	MP3A	Mx	.004	24
19	MP3A	X	-8.166	48
20	MP3A	Z	0	48
21	MP3A	Mx	.004	48
22	M13	X	-23.734	12
23	M13	Z	0	12
24	M13	Mx	0	12
25	MP3A	X	-11.238	18
26	MP3A	Z	0	18
27	MP3A	Mx	-.006	18
28	MP2A	X	-9.369	18
29	MP2A	Z	0	18
30	MP2A	Mx	-.005	18

**Member Point Loads (BLC 25 : Antenna Wi (300 Deg))**

	Member Label	Direction	Magnitude[lb,k-ft]	Location[in, %]
1	MP3A	X	-3.388	48
2	MP3A	Z	-1.956	48
3	MP3A	Mx	-.002	48
4	MP2A	X	-27.512	6
5	MP2A	Z	-15.884	6
6	MP2A	Mx	.003	6
7	MP2A	X	-27.512	66
8	MP2A	Z	-15.884	66
9	MP2A	Mx	.003	66
10	MP2A	X	-27.512	6
11	MP2A	Z	-15.884	6
12	MP2A	Mx	.024	6
13	MP2A	X	-27.512	66
14	MP2A	Z	-15.884	66
15	MP2A	Mx	.024	66
16	MP3A	X	-9.455	24
17	MP3A	Z	-5.459	24
18	MP3A	Mx	.005	24
19	MP3A	X	-9.455	48
20	MP3A	Z	-5.459	48
21	MP3A	Mx	.005	48
22	M13	X	-18.426	12
23	M13	Z	-10.638	12
24	M13	Mx	0	12
25	MP3A	X	-10.798	18
26	MP3A	Z	-6.234	18
27	MP3A	Mx	-.005	18
28	MP2A	X	-9.584	18
29	MP2A	Z	-5.533	18
30	MP2A	Mx	-.005	18

**Member Point Loads (BLC 26 : Antenna Wi (330 Deg))**

	Member Label	Direction	Magnitude[lb,k-ft]	Location[in, %]
1	MP3A	X	-3.379	48
2	MP3A	Z	-5.853	48
3	MP3A	Mx	-.002	48



**Member Point Loads (BLC 26 : Antenna Wi (330 Deg)) (Continued)**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
4	MP2A	X	-18.25	6
5	MP2A	Z	-31.61	6
6	MP2A	Mx	-.012	6
7	MP2A	X	-18.25	66
8	MP2A	Z	-31.61	66
9	MP2A	Mx	-.012	66
10	MP2A	X	-18.25	6
11	MP2A	Z	-31.61	6
12	MP2A	Mx	.03	6
13	MP2A	X	-18.25	66
14	MP2A	Z	-31.61	66
15	MP2A	Mx	.03	66
16	MP3A	X	-8.211	24
17	MP3A	Z	-14.221	24
18	MP3A	Mx	.004	24
19	MP3A	X	-8.211	48
20	MP3A	Z	-14.221	48
21	MP3A	Mx	.004	48
22	M13	X	-11.867	12
23	M13	Z	-20.554	12
24	M13	Mx	0	12
25	MP3A	X	-7.464	18
26	MP3A	Z	-12.928	18
27	MP3A	Mx	-.004	18
28	MP2A	X	-7.23	18
29	MP2A	Z	-12.523	18
30	MP2A	Mx	-.004	18

**Member Point Loads (BLC 27 : Antenna Wm (0 Deg))**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	MP3A	X	0	48
2	MP3A	Z	-2.262	48
3	MP3A	Mx	0	48
4	MP2A	X	0	6
5	MP2A	Z	-12.833	6
6	MP2A	Mx	-.009	6
7	MP2A	X	0	66
8	MP2A	Z	-12.833	66
9	MP2A	Mx	-.009	66
10	MP2A	X	0	6
11	MP2A	Z	-12.833	6
12	MP2A	Mx	.009	6
13	MP2A	X	0	66
14	MP2A	Z	-12.833	66
15	MP2A	Mx	.009	66
16	MP3A	X	0	24
17	MP3A	Z	-6.111	24
18	MP3A	Mx	0	24
19	MP3A	X	0	48
20	MP3A	Z	-6.111	48
21	MP3A	Mx	0	48
22	M13	X	0	12
23	M13	Z	-9.023	12
24	M13	Mx	0	12
25	MP3A	X	0	18
26	MP3A	Z	-4.863	18



**Member Point Loads (BLC 27 : Antenna Wm (0 Deg)) (Continued)**

	Member Label	Direction	Magnitude[lb,k-ft]	Location[in, %]
27	MP3A	Mx	0	18
28	MP2A	X	0	18
29	MP2A	Z	-4.863	18
30	MP2A	Mx	0	18

**Member Point Loads (BLC 28 : Antenna Wm (30 Deg))**

	Member Label	Direction	Magnitude[lb,k-ft]	Location[in, %]
1	MP3A	X	.914	48
2	MP3A	Z	-1.583	48
3	MP3A	Mx	.000457	48
4	MP2A	X	6.005	6
5	MP2A	Z	-10.401	6
6	MP2A	Mx	-.01	6
7	MP2A	X	6.005	66
8	MP2A	Z	-10.401	66
9	MP2A	Mx	-.01	66
10	MP2A	X	6.005	6
11	MP2A	Z	-10.401	6
12	MP2A	Mx	.004	6
13	MP2A	X	6.005	66
14	MP2A	Z	-10.401	66
15	MP2A	Mx	.004	66
16	MP3A	X	2.591	24
17	MP3A	Z	-4.487	24
18	MP3A	Mx	-.001	24
19	MP3A	X	2.591	48
20	MP3A	Z	-4.487	48
21	MP3A	Mx	-.001	48
22	M13	X	4.928	12
23	M13	Z	-8.535	12
24	M13	Mx	0	12
25	MP3A	X	2.23	18
26	MP3A	Z	-3.862	18
27	MP3A	Mx	.001	18
28	MP2A	X	2.153	18
29	MP2A	Z	-3.729	18
30	MP2A	Mx	.001	18

**Member Point Loads (BLC 29 : Antenna Wm (60 Deg))**

	Member Label	Direction	Magnitude[lb,k-ft]	Location[in, %]
1	MP3A	X	.83	48
2	MP3A	Z	-.479	48
3	MP3A	Mx	.000415	48
4	MP2A	X	8.975	6
5	MP2A	Z	-5.182	6
6	MP2A	Mx	-.008	6
7	MP2A	X	8.975	66
8	MP2A	Z	-5.182	66
9	MP2A	Mx	-.008	66
10	MP2A	X	8.975	6
11	MP2A	Z	-5.182	6
12	MP2A	Mx	-.001	6
13	MP2A	X	8.975	66
14	MP2A	Z	-5.182	66
15	MP2A	Mx	-.001	66
16	MP3A	X	2.877	24



**Member Point Loads (BLC 29 : Antenna Wm (60 Deg)) (Continued)**

	Member Label	Direction	Magnitude[lb,k-ft]	Location[in, %]
17	MP3A	Z	-1.661	24
18	MP3A	Mx	-.001	24
19	MP3A	X	2.877	48
20	MP3A	Z	-1.661	48
21	MP3A	Mx	-.001	48
22	M13	X	7.814	12
23	M13	Z	-4.511	12
24	M13	Mx	0	12
25	MP3A	X	3.164	18
26	MP3A	Z	-1.827	18
27	MP3A	Mx	.002	18
28	MP2A	X	2.763	18
29	MP2A	Z	-1.595	18
30	MP2A	Mx	.001	18

**Member Point Loads (BLC 30 : Antenna Wm (90 Deg))**

	Member Label	Direction	Magnitude[lb,k-ft]	Location[in, %]
1	MP3A	X	.523	48
2	MP3A	Z	0	48
3	MP3A	Mx	.000262	48
4	MP2A	X	9.541	6
5	MP2A	Z	0	6
6	MP2A	Mx	-.005	6
7	MP2A	X	9.541	66
8	MP2A	Z	0	66
9	MP2A	Mx	-.005	66
10	MP2A	X	9.541	6
11	MP2A	Z	0	6
12	MP2A	Mx	-.005	6
13	MP2A	X	9.541	66
14	MP2A	Z	0	66
15	MP2A	Mx	-.005	66
16	MP3A	X	2.392	24
17	MP3A	Z	0	24
18	MP3A	Mx	-.001	24
19	MP3A	X	2.392	48
20	MP3A	Z	0	48
21	MP3A	Mx	-.001	48
22	M13	X	7.357	12
23	M13	Z	0	12
24	M13	Mx	0	12
25	MP3A	X	3.251	18
26	MP3A	Z	0	18
27	MP3A	Mx	.002	18
28	MP2A	X	2.633	18
29	MP2A	Z	0	18
30	MP2A	Mx	.001	18

**Member Point Loads (BLC 31 : Antenna Wm (120 Deg))**

	Member Label	Direction	Magnitude[lb,k-ft]	Location[in, %]
1	MP3A	X	.83	48
2	MP3A	Z	.479	48
3	MP3A	Mx	.000415	48
4	MP2A	X	8.975	6
5	MP2A	Z	5.182	6
6	MP2A	Mx	-.001	6



**Member Point Loads (BLC 31 : Antenna Wm (120 Deg)) (Continued)**

	Member Label	Direction	Magnitude[lb,k-ft]	Location[in, %]
7	MP2A	X	8.975	66
8	MP2A	Z	5.182	66
9	MP2A	Mx	-.001	66
10	MP2A	X	8.975	6
11	MP2A	Z	5.182	6
12	MP2A	Mx	-.008	6
13	MP2A	X	8.975	66
14	MP2A	Z	5.182	66
15	MP2A	Mx	-.008	66
16	MP3A	X	2.877	24
17	MP3A	Z	1.661	24
18	MP3A	Mx	-.001	24
19	MP3A	X	2.877	48
20	MP3A	Z	1.661	48
21	MP3A	Mx	-.001	48
22	M13	X	5.65	12
23	M13	Z	3.262	12
24	M13	Mx	0	12
25	MP3A	X	3.164	18
26	MP3A	Z	1.827	18
27	MP3A	Mx	.002	18
28	MP2A	X	2.763	18
29	MP2A	Z	1.595	18
30	MP2A	Mx	.001	18

**Member Point Loads (BLC 32 : Antenna Wm (150 Deg))**

	Member Label	Direction	Magnitude[lb,k-ft]	Location[in, %]
1	MP3A	X	.914	48
2	MP3A	Z	1.583	48
3	MP3A	Mx	.000457	48
4	MP2A	X	6.005	6
5	MP2A	Z	10.401	6
6	MP2A	Mx	.004	6
7	MP2A	X	6.005	66
8	MP2A	Z	10.401	66
9	MP2A	Mx	.004	66
10	MP2A	X	6.005	6
11	MP2A	Z	10.401	6
12	MP2A	Mx	-.01	6
13	MP2A	X	6.005	66
14	MP2A	Z	10.401	66
15	MP2A	Mx	-.01	66
16	MP3A	X	2.591	24
17	MP3A	Z	4.487	24
18	MP3A	Mx	-.001	24
19	MP3A	X	2.591	48
20	MP3A	Z	4.487	48
21	MP3A	Mx	-.001	48
22	M13	X	3.678	12
23	M13	Z	6.371	12
24	M13	Mx	0	12
25	MP3A	X	2.23	18
26	MP3A	Z	3.862	18
27	MP3A	Mx	.001	18
28	MP2A	X	2.153	18
29	MP2A	Z	3.729	18



Company : Maser Consulting  
 Designer : DC  
 Job Number :  
 Model Name : Antenna Mount Analysis

July 2, 2021  
 10:51 AM  
 Checked By: DX

**Member Point Loads (BLC 32 : Antenna Wm (150 Deg)) (Continued)**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
30	MP2A	Mx	.001	18

**Member Point Loads (BLC 33 : Antenna Wm (180 Deg))**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	MP3A	X	0	48
2	MP3A	Z	2.262	48
3	MP3A	Mx	0	48
4	MP2A	X	0	6
5	MP2A	Z	12.833	6
6	MP2A	Mx	.009	6
7	MP2A	X	0	66
8	MP2A	Z	12.833	66
9	MP2A	Mx	.009	66
10	MP2A	X	0	6
11	MP2A	Z	12.833	6
12	MP2A	Mx	-.009	6
13	MP2A	X	0	66
14	MP2A	Z	12.833	66
15	MP2A	Mx	-.009	66
16	MP3A	X	0	24
17	MP3A	Z	6.111	24
18	MP3A	Mx	0	24
19	MP3A	X	0	48
20	MP3A	Z	6.111	48
21	MP3A	Mx	0	48
22	M13	X	0	12
23	M13	Z	9.023	12
24	M13	Mx	0	12
25	MP3A	X	0	18
26	MP3A	Z	4.863	18
27	MP3A	Mx	0	18
28	MP2A	X	0	18
29	MP2A	Z	4.863	18
30	MP2A	Mx	0	18

**Member Point Loads (BLC 34 : Antenna Wm (210 Deg))**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	MP3A	X	-.914	48
2	MP3A	Z	1.583	48
3	MP3A	Mx	-.000457	48
4	MP2A	X	-6.005	6
5	MP2A	Z	10.401	6
6	MP2A	Mx	.01	6
7	MP2A	X	-6.005	66
8	MP2A	Z	10.401	66
9	MP2A	Mx	.01	66
10	MP2A	X	-6.005	6
11	MP2A	Z	10.401	6
12	MP2A	Mx	-.004	6
13	MP2A	X	-6.005	66
14	MP2A	Z	10.401	66
15	MP2A	Mx	-.004	66
16	MP3A	X	-2.591	24
17	MP3A	Z	4.487	24
18	MP3A	Mx	.001	24
19	MP3A	X	-2.591	48



Company : Maser Consulting  
 Designer : DC  
 Job Number :  
 Model Name : Antenna Mount Analysis

July 2, 2021  
 10:51 AM  
 Checked By: DX

**Member Point Loads (BLC 34 : Antenna Wm (210 Deg)) (Continued)**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
20	MP3A	Z	4.487	48
21	MP3A	Mx	.001	48
22	M13	X	-4.928	12
23	M13	Z	8.535	12
24	M13	Mx	0	12
25	MP3A	X	-2.23	18
26	MP3A	Z	3.862	18
27	MP3A	Mx	-.001	18
28	MP2A	X	-2.153	18
29	MP2A	Z	3.729	18
30	MP2A	Mx	-.001	18

**Member Point Loads (BLC 35 : Antenna Wm (240 Deg))**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	MP3A	X	-.83	48
2	MP3A	Z	.479	48
3	MP3A	Mx	-.000415	48
4	MP2A	X	-8.975	6
5	MP2A	Z	5.182	6
6	MP2A	Mx	.008	6
7	MP2A	X	-8.975	66
8	MP2A	Z	5.182	66
9	MP2A	Mx	.008	66
10	MP2A	X	-8.975	6
11	MP2A	Z	5.182	6
12	MP2A	Mx	.001	6
13	MP2A	X	-8.975	66
14	MP2A	Z	5.182	66
15	MP2A	Mx	.001	66
16	MP3A	X	-2.877	24
17	MP3A	Z	1.661	24
18	MP3A	Mx	.001	24
19	MP3A	X	-2.877	48
20	MP3A	Z	1.661	48
21	MP3A	Mx	.001	48
22	M13	X	-7.814	12
23	M13	Z	4.511	12
24	M13	Mx	0	12
25	MP3A	X	-3.164	18
26	MP3A	Z	1.827	18
27	MP3A	Mx	-.002	18
28	MP2A	X	-2.763	18
29	MP2A	Z	1.595	18
30	MP2A	Mx	-.001	18

**Member Point Loads (BLC 36 : Antenna Wm (270 Deg))**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	MP3A	X	-.523	48
2	MP3A	Z	0	48
3	MP3A	Mx	-.000262	48
4	MP2A	X	-9.541	6
5	MP2A	Z	0	6
6	MP2A	Mx	.005	6
7	MP2A	X	-9.541	66
8	MP2A	Z	0	66
9	MP2A	Mx	.005	66





**Member Point Loads (BLC 36 : Antenna Wm (270 Deg)) (Continued)**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
10	MP2A	X	-9.541	6
11	MP2A	Z	0	6
12	MP2A	Mx	.005	6
13	MP2A	X	-9.541	66
14	MP2A	Z	0	66
15	MP2A	Mx	.005	66
16	MP3A	X	-2.392	24
17	MP3A	Z	0	24
18	MP3A	Mx	.001	24
19	MP3A	X	-2.392	48
20	MP3A	Z	0	48
21	MP3A	Mx	.001	48
22	M13	X	-7.357	12
23	M13	Z	0	12
24	M13	Mx	0	12
25	MP3A	X	-3.251	18
26	MP3A	Z	0	18
27	MP3A	Mx	-.002	18
28	MP2A	X	-2.633	18
29	MP2A	Z	0	18
30	MP2A	Mx	-.001	18

**Member Point Loads (BLC 37 : Antenna Wm (300 Deg))**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	MP3A	X	-.83	48
2	MP3A	Z	-.479	48
3	MP3A	Mx	-.000415	48
4	MP2A	X	-8.975	6
5	MP2A	Z	-5.182	6
6	MP2A	Mx	.001	6
7	MP2A	X	-8.975	66
8	MP2A	Z	-5.182	66
9	MP2A	Mx	.001	66
10	MP2A	X	-8.975	6
11	MP2A	Z	-5.182	6
12	MP2A	Mx	.008	6
13	MP2A	X	-8.975	66
14	MP2A	Z	-5.182	66
15	MP2A	Mx	.008	66
16	MP3A	X	-2.877	24
17	MP3A	Z	-1.661	24
18	MP3A	Mx	.001	24
19	MP3A	X	-2.877	48
20	MP3A	Z	-1.661	48
21	MP3A	Mx	.001	48
22	M13	X	-5.65	12
23	M13	Z	-3.262	12
24	M13	Mx	0	12
25	MP3A	X	-3.164	18
26	MP3A	Z	-1.827	18
27	MP3A	Mx	-.002	18
28	MP2A	X	-2.763	18
29	MP2A	Z	-1.595	18
30	MP2A	Mx	-.001	18



**Member Point Loads (BLC 38 : Antenna Wm (330 Deg))**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	MP3A	X	-.914	48
2	MP3A	Z	-1.583	48
3	MP3A	Mx	-.000457	48
4	MP2A	X	-6.005	6
5	MP2A	Z	-10.401	6
6	MP2A	Mx	-.004	6
7	MP2A	X	-6.005	66
8	MP2A	Z	-10.401	66
9	MP2A	Mx	-.004	66
10	MP2A	X	-6.005	6
11	MP2A	Z	-10.401	6
12	MP2A	Mx	.01	6
13	MP2A	X	-6.005	66
14	MP2A	Z	-10.401	66
15	MP2A	Mx	.01	66
16	MP3A	X	-2.591	24
17	MP3A	Z	-4.487	24
18	MP3A	Mx	.001	24
19	MP3A	X	-2.591	48
20	MP3A	Z	-4.487	48
21	MP3A	Mx	.001	48
22	M13	X	-3.678	12
23	M13	Z	-6.371	12
24	M13	Mx	0	12
25	MP3A	X	-2.23	18
26	MP3A	Z	-3.862	18
27	MP3A	Mx	-.001	18
28	MP2A	X	-2.153	18
29	MP2A	Z	-3.729	18
30	MP2A	Mx	-.001	18

**Member Point Loads (BLC 77 : Lm1)**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	M4	Y	-500	%58

**Member Point Loads (BLC 78 : Lm2)**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	M4	Y	-500	%32

**Member Point Loads (BLC 79 : Lv1)**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	M4	Y	-250	0

**Member Point Loads (BLC 80 : Lv2)**

	Member Label	Direction	Magnitude[lb.k-ft]	Location[in.%]
1	M4	Y	-250	%50

**Member Distributed Loads (BLC 40 : Structure Di)**

	Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft.F...	Start Location[in.%]	End Location[in.%]
1	M1	Y	-9.584	-9.584	0	%100
2	M2	Y	-7.956	-7.956	0	%100
3	M4	Y	-6.548	-6.548	0	%100
4	MP1A	Y	-4.965	-4.965	0	%100



**Member Distributed Loads (BLC 40 : Structure Di) (Continued)**

	Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft.F...	Start Location[in.-%]	End Location[in.-%]
5	MP2A	Y	-4.965	-4.965	0	%100
6	MP3A	Y	-4.965	-4.965	0	%100
7	MP4A	Y	-4.965	-4.965	0	%100
8	M13	Y	-4.965	-4.965	0	%100

**Member Distributed Loads (BLC 41 : Structure Wo (0 Deg))**

	Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft.F...	Start Location[in.-%]	End Location[in.-%]
1	M1	X	0	0	0	%100
2	M1	Z	-.395	-.395	0	%100
3	M2	X	0	0	0	%100
4	M2	Z	-10.056	-10.056	0	%100
5	M4	X	0	0	0	%100
6	M4	Z	-14.123	-14.123	0	%100
7	MP1A	X	0	0	0	%100
8	MP1A	Z	-9.882	-9.882	0	%100
9	MP2A	X	0	0	0	%100
10	MP2A	Z	-9.882	-9.882	0	%100
11	MP3A	X	0	0	0	%100
12	MP3A	Z	-9.882	-9.882	0	%100
13	MP4A	X	0	0	0	%100
14	MP4A	Z	-9.882	-9.882	0	%100
15	M13	X	0	0	0	%100
16	M13	Z	-7.156	-7.156	0	%100

**Member Distributed Loads (BLC 42 : Structure Wo (30 Deg))**

	Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft.F...	Start Location[in.-%]	End Location[in.-%]
1	M1	X	.766	.766	0	%100
2	M1	Z	-1.326	-1.326	0	%100
3	M2	X	5.028	5.028	0	%100
4	M2	Z	-8.709	-8.709	0	%100
5	M4	X	5.296	5.296	0	%100
6	M4	Z	-9.173	-9.173	0	%100
7	MP1A	X	4.941	4.941	0	%100
8	MP1A	Z	-8.558	-8.558	0	%100
9	MP2A	X	4.941	4.941	0	%100
10	MP2A	Z	-8.558	-8.558	0	%100
11	MP3A	X	4.941	4.941	0	%100
12	MP3A	Z	-8.558	-8.558	0	%100
13	MP4A	X	4.941	4.941	0	%100
14	MP4A	Z	-8.558	-8.558	0	%100
15	M13	X	3.578	3.578	0	%100
16	M13	Z	-6.197	-6.197	0	%100

**Member Distributed Loads (BLC 43 : Structure Wo (60 Deg))**

	Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft.F...	Start Location[in.-%]	End Location[in.-%]
1	M1	X	6.652	6.652	0	%100
2	M1	Z	-3.84	-3.84	0	%100
3	M2	X	8.709	8.709	0	%100
4	M2	Z	-5.028	-5.028	0	%100
5	M4	X	3.058	3.058	0	%100
6	M4	Z	-1.765	-1.765	0	%100
7	MP1A	X	8.558	8.558	0	%100
8	MP1A	Z	-4.941	-4.941	0	%100
9	MP2A	X	8.558	8.558	0	%100
10	MP2A	Z	-4.941	-4.941	0	%100



**Member Distributed Loads (BLC 43 : Structure Wo (60 Deg)) (Continued)**

	Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft.F...	Start Location[in, %]	End Location[in, %]
11	MP3A	X	8.558	8.558	0	%100
12	MP3A	Z	-4.941	-4.941	0	%100
13	MP4A	X	8.558	8.558	0	%100
14	MP4A	Z	-4.941	-4.941	0	%100
15	M13	X	6.197	6.197	0	%100
16	M13	Z	-3.578	-3.578	0	%100

**Member Distributed Loads (BLC 44 : Structure Wo (90 Deg))**

	Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft.F...	Start Location[in, %]	End Location[in, %]
1	M1	X	12.694	12.694	0	%100
2	M1	Z	0	0	0	%100
3	M2	X	10.056	10.056	0	%100
4	M2	Z	0	0	0	%100
5	M4	X	0	0	0	%100
6	M4	Z	0	0	0	%100
7	MP1A	X	9.882	9.882	0	%100
8	MP1A	Z	0	0	0	%100
9	MP2A	X	9.882	9.882	0	%100
10	MP2A	Z	0	0	0	%100
11	MP3A	X	9.882	9.882	0	%100
12	MP3A	Z	0	0	0	%100
13	MP4A	X	9.882	9.882	0	%100
14	MP4A	Z	0	0	0	%100
15	M13	X	7.156	7.156	0	%100
16	M13	Z	0	0	0	%100

**Member Distributed Loads (BLC 45 : Structure Wo (120 Deg))**

	Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft.F...	Start Location[in, %]	End Location[in, %]
1	M1	X	10.009	10.009	0	%100
2	M1	Z	5.779	5.779	0	%100
3	M2	X	8.709	8.709	0	%100
4	M2	Z	5.028	5.028	0	%100
5	M4	X	3.058	3.058	0	%100
6	M4	Z	1.765	1.765	0	%100
7	MP1A	X	8.558	8.558	0	%100
8	MP1A	Z	4.941	4.941	0	%100
9	MP2A	X	8.558	8.558	0	%100
10	MP2A	Z	4.941	4.941	0	%100
11	MP3A	X	8.558	8.558	0	%100
12	MP3A	Z	4.941	4.941	0	%100
13	MP4A	X	8.558	8.558	0	%100
14	MP4A	Z	4.941	4.941	0	%100
15	M13	X	6.197	6.197	0	%100
16	M13	Z	3.578	3.578	0	%100

**Member Distributed Loads (BLC 46 : Structure Wo (150 Deg))**

	Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft.F...	Start Location[in, %]	End Location[in, %]
1	M1	X	2.704	2.704	0	%100
2	M1	Z	4.683	4.683	0	%100
3	M2	X	5.028	5.028	0	%100
4	M2	Z	8.709	8.709	0	%100
5	M4	X	5.296	5.296	0	%100
6	M4	Z	9.173	9.173	0	%100
7	MP1A	X	4.941	4.941	0	%100
8	MP1A	Z	8.558	8.558	0	%100



**Member Distributed Loads (BLC 46 : Structure Wo (150 Deg)) (Continued)**

	Member Label	Direction	Start Magnitude[lb/ft,...	End Magnitude[lb/ft,F...	Start Location[in, %]	End Location[in, %]
9	MP2A	X	4.941	4.941	0	%100
10	MP2A	Z	8.558	8.558	0	%100
11	MP3A	X	4.941	4.941	0	%100
12	MP3A	Z	8.558	8.558	0	%100
13	MP4A	X	4.941	4.941	0	%100
14	MP4A	Z	8.558	8.558	0	%100
15	M13	X	3.578	3.578	0	%100
16	M13	Z	6.197	6.197	0	%100

**Member Distributed Loads (BLC 47 : Structure Wo (180 Deg))**

	Member Label	Direction	Start Magnitude[lb/ft,...	End Magnitude[lb/ft,F...	Start Location[in, %]	End Location[in, %]
1	M1	X	0	0	0	%100
2	M1	Z	.395	.395	0	%100
3	M2	X	0	0	0	%100
4	M2	Z	10.056	10.056	0	%100
5	M4	X	0	0	0	%100
6	M4	Z	14.123	14.123	0	%100
7	MP1A	X	0	0	0	%100
8	MP1A	Z	9.882	9.882	0	%100
9	MP2A	X	0	0	0	%100
10	MP2A	Z	9.882	9.882	0	%100
11	MP3A	X	0	0	0	%100
12	MP3A	Z	9.882	9.882	0	%100
13	MP4A	X	0	0	0	%100
14	MP4A	Z	9.882	9.882	0	%100
15	M13	X	0	0	0	%100
16	M13	Z	7.156	7.156	0	%100

**Member Distributed Loads (BLC 48 : Structure Wo (210 Deg))**

	Member Label	Direction	Start Magnitude[lb/ft,...	End Magnitude[lb/ft,F...	Start Location[in, %]	End Location[in, %]
1	M1	X	-7.766	-7.766	0	%100
2	M1	Z	1.326	1.326	0	%100
3	M2	X	-5.028	-5.028	0	%100
4	M2	Z	8.709	8.709	0	%100
5	M4	X	-5.296	-5.296	0	%100
6	M4	Z	9.173	9.173	0	%100
7	MP1A	X	-4.941	-4.941	0	%100
8	MP1A	Z	8.558	8.558	0	%100
9	MP2A	X	-4.941	-4.941	0	%100
10	MP2A	Z	8.558	8.558	0	%100
11	MP3A	X	-4.941	-4.941	0	%100
12	MP3A	Z	8.558	8.558	0	%100
13	MP4A	X	-4.941	-4.941	0	%100
14	MP4A	Z	8.558	8.558	0	%100
15	M13	X	-3.578	-3.578	0	%100
16	M13	Z	6.197	6.197	0	%100

**Member Distributed Loads (BLC 49 : Structure Wo (240 Deg))**

	Member Label	Direction	Start Magnitude[lb/ft,...	End Magnitude[lb/ft,F...	Start Location[in, %]	End Location[in, %]
1	M1	X	-6.652	-6.652	0	%100
2	M1	Z	3.84	3.84	0	%100
3	M2	X	-8.709	-8.709	0	%100
4	M2	Z	5.028	5.028	0	%100
5	M4	X	-3.058	-3.058	0	%100
6	M4	Z	1.765	1.765	0	%100

**Member Distributed Loads (BLC 49 : Structure Wo (240 Deg)) (Continued)**

	Member Label	Direction	Start Magnitude[lb/ft,....	End Magnitude[lb/ft,F...	Start Location[in, %]	End Location[in, %]
7	MP1A	X	-8.558	-8.558	0	%100
8	MP1A	Z	4.941	4.941	0	%100
9	MP2A	X	-8.558	-8.558	0	%100
10	MP2A	Z	4.941	4.941	0	%100
11	MP3A	X	-8.558	-8.558	0	%100
12	MP3A	Z	4.941	4.941	0	%100
13	MP4A	X	-8.558	-8.558	0	%100
14	MP4A	Z	4.941	4.941	0	%100
15	M13	X	-6.197	-6.197	0	%100
16	M13	Z	3.578	3.578	0	%100

**Member Distributed Loads (BLC 50 : Structure Wo (270 Deg))**

	Member Label	Direction	Start Magnitude[lb/ft,....	End Magnitude[lb/ft,F...	Start Location[in, %]	End Location[in, %]
1	M1	X	-12.694	-12.694	0	%100
2	M1	Z	0	0	0	%100
3	M2	X	-10.056	-10.056	0	%100
4	M2	Z	0	0	0	%100
5	M4	X	0	0	0	%100
6	M4	Z	0	0	0	%100
7	MP1A	X	-9.882	-9.882	0	%100
8	MP1A	Z	0	0	0	%100
9	MP2A	X	-9.882	-9.882	0	%100
10	MP2A	Z	0	0	0	%100
11	MP3A	X	-9.882	-9.882	0	%100
12	MP3A	Z	0	0	0	%100
13	MP4A	X	-9.882	-9.882	0	%100
14	MP4A	Z	0	0	0	%100
15	M13	X	-7.156	-7.156	0	%100
16	M13	Z	0	0	0	%100

**Member Distributed Loads (BLC 51 : Structure Wo (300 Deg))**

	Member Label	Direction	Start Magnitude[lb/ft,....	End Magnitude[lb/ft,F...	Start Location[in, %]	End Location[in, %]
1	M1	X	-10.009	-10.009	0	%100
2	M1	Z	-5.779	-5.779	0	%100
3	M2	X	-8.709	-8.709	0	%100
4	M2	Z	-5.028	-5.028	0	%100
5	M4	X	-3.058	-3.058	0	%100
6	M4	Z	-1.765	-1.765	0	%100
7	MP1A	X	-8.558	-8.558	0	%100
8	MP1A	Z	-4.941	-4.941	0	%100
9	MP2A	X	-8.558	-8.558	0	%100
10	MP2A	Z	-4.941	-4.941	0	%100
11	MP3A	X	-8.558	-8.558	0	%100
12	MP3A	Z	-4.941	-4.941	0	%100
13	MP4A	X	-8.558	-8.558	0	%100
14	MP4A	Z	-4.941	-4.941	0	%100
15	M13	X	-6.197	-6.197	0	%100
16	M13	Z	-3.578	-3.578	0	%100

**Member Distributed Loads (BLC 52 : Structure Wo (330 Deg))**

	Member Label	Direction	Start Magnitude[lb/ft,....	End Magnitude[lb/ft,F...	Start Location[in, %]	End Location[in, %]
1	M1	X	-2.704	-2.704	0	%100
2	M1	Z	-4.683	-4.683	0	%100
3	M2	X	-5.028	-5.028	0	%100
4	M2	Z	-8.709	-8.709	0	%100



**Member Distributed Loads (BLC 52 : Structure Wo (330 Deg)) (Continued)**

	Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft,F...	Start Location[in, %]	End Location[in, %]
5	M4	X	-5.296	-5.296	0	%100
6	M4	Z	-9.173	-9.173	0	%100
7	MP1A	X	-4.941	-4.941	0	%100
8	MP1A	Z	-8.558	-8.558	0	%100
9	MP2A	X	-4.941	-4.941	0	%100
10	MP2A	Z	-8.558	-8.558	0	%100
11	MP3A	X	-4.941	-4.941	0	%100
12	MP3A	Z	-8.558	-8.558	0	%100
13	MP4A	X	-4.941	-4.941	0	%100
14	MP4A	Z	-8.558	-8.558	0	%100
15	M13	X	-3.578	-3.578	0	%100
16	M13	Z	-6.197	-6.197	0	%100

**Member Distributed Loads (BLC 53 : Structure Wi (0 Deg))**

	Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft,F...	Start Location[in, %]	End Location[in, %]
1	M1	X	0	0	0	%100
2	M1	Z	-.11	-.11	0	%100
3	M2	X	0	0	0	%100
4	M2	Z	-3.121	-3.121	0	%100
5	M4	X	0	0	0	%100
6	M4	Z	-4.193	-4.193	0	%100
7	MP1A	X	0	0	0	%100
8	MP1A	Z	-3.38	-3.38	0	%100
9	MP2A	X	0	0	0	%100
10	MP2A	Z	-3.38	-3.38	0	%100
11	MP3A	X	0	0	0	%100
12	MP3A	Z	-3.38	-3.38	0	%100
13	MP4A	X	0	0	0	%100
14	MP4A	Z	-3.38	-3.38	0	%100
15	M13	X	0	0	0	%100
16	M13	Z	-2.457	-2.457	0	%100

**Member Distributed Loads (BLC 54 : Structure Wi (30 Deg))**

	Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft,F...	Start Location[in, %]	End Location[in, %]
1	M1	X	.214	.214	0	%100
2	M1	Z	-.371	-.371	0	%100
3	M2	X	1.561	1.561	0	%100
4	M2	Z	-2.703	-2.703	0	%100
5	M4	X	1.572	1.572	0	%100
6	M4	Z	-2.723	-2.723	0	%100
7	MP1A	X	1.69	1.69	0	%100
8	MP1A	Z	-2.927	-2.927	0	%100
9	MP2A	X	1.69	1.69	0	%100
10	MP2A	Z	-2.927	-2.927	0	%100
11	MP3A	X	1.69	1.69	0	%100
12	MP3A	Z	-2.927	-2.927	0	%100
13	MP4A	X	1.69	1.69	0	%100
14	MP4A	Z	-2.927	-2.927	0	%100
15	M13	X	1.229	1.229	0	%100
16	M13	Z	-2.128	-2.128	0	%100

**Member Distributed Loads (BLC 55 : Structure Wi (60 Deg))**

	Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft,F...	Start Location[in, %]	End Location[in, %]
1	M1	X	1.861	1.861	0	%100
2	M1	Z	-1.074	-1.074	0	%100



**Member Distributed Loads (BLC 55 : Structure Wi (60 Deg)) (Continued)**

	Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft.F...	Start Location[in.%,]	End Location[in.%,]
3	M2	X	2.703	2.703	0	%100
4	M2	Z	-1.561	-1.561	0	%100
5	M4	X	.908	.908	0	%100
6	M4	Z	-.524	-.524	0	%100
7	MP1A	X	2.927	2.927	0	%100
8	MP1A	Z	-1.69	-1.69	0	%100
9	MP2A	X	2.927	2.927	0	%100
10	MP2A	Z	-1.69	-1.69	0	%100
11	MP3A	X	2.927	2.927	0	%100
12	MP3A	Z	-1.69	-1.69	0	%100
13	MP4A	X	2.927	2.927	0	%100
14	MP4A	Z	-1.69	-1.69	0	%100
15	M13	X	2.128	2.128	0	%100
16	M13	Z	-1.229	-1.229	0	%100

**Member Distributed Loads (BLC 56 : Structure Wi (90 Deg))**

	Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft.F...	Start Location[in.%,]	End Location[in.%,]
1	M1	X	3.551	3.551	0	%100
2	M1	Z	0	0	0	%100
3	M2	X	3.121	3.121	0	%100
4	M2	Z	0	0	0	%100
5	M4	X	0	0	0	%100
6	M4	Z	0	0	0	%100
7	MP1A	X	3.38	3.38	0	%100
8	MP1A	Z	0	0	0	%100
9	MP2A	X	3.38	3.38	0	%100
10	MP2A	Z	0	0	0	%100
11	MP3A	X	3.38	3.38	0	%100
12	MP3A	Z	0	0	0	%100
13	MP4A	X	3.38	3.38	0	%100
14	MP4A	Z	0	0	0	%100
15	M13	X	2.457	2.457	0	%100
16	M13	Z	0	0	0	%100

**Member Distributed Loads (BLC 57 : Structure Wi (120 Deg))**

	Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft.F...	Start Location[in.%,]	End Location[in.%,]
1	M1	X	2.8	2.8	0	%100
2	M1	Z	1.616	1.616	0	%100
3	M2	X	2.703	2.703	0	%100
4	M2	Z	1.561	1.561	0	%100
5	M4	X	.908	.908	0	%100
6	M4	Z	.524	.524	0	%100
7	MP1A	X	2.927	2.927	0	%100
8	MP1A	Z	1.69	1.69	0	%100
9	MP2A	X	2.927	2.927	0	%100
10	MP2A	Z	1.69	1.69	0	%100
11	MP3A	X	2.927	2.927	0	%100
12	MP3A	Z	1.69	1.69	0	%100
13	MP4A	X	2.927	2.927	0	%100
14	MP4A	Z	1.69	1.69	0	%100
15	M13	X	2.128	2.128	0	%100
16	M13	Z	1.229	1.229	0	%100

**Member Distributed Loads (BLC 58 : Structure Wi (150 Deg))**

Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft.F...	Start Location[in.%,]	End Location[in.%,]
--------------	-----------	---------------------------	--------------------------	-----------------------	---------------------





**Member Distributed Loads (BLC 58 : Structure Wi (150 Deg)) (Continued)**

	Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft.F...	Start Location[in,.%]	End Location[in,.%]
1	M1	X	.756	.756	0	%100
2	M1	Z	1.31	1.31	0	%100
3	M2	X	1.561	1.561	0	%100
4	M2	Z	2.703	2.703	0	%100
5	M4	X	1.572	1.572	0	%100
6	M4	Z	2.723	2.723	0	%100
7	MP1A	X	1.69	1.69	0	%100
8	MP1A	Z	2.927	2.927	0	%100
9	MP2A	X	1.69	1.69	0	%100
10	MP2A	Z	2.927	2.927	0	%100
11	MP3A	X	1.69	1.69	0	%100
12	MP3A	Z	2.927	2.927	0	%100
13	MP4A	X	1.69	1.69	0	%100
14	MP4A	Z	2.927	2.927	0	%100
15	M13	X	1.229	1.229	0	%100
16	M13	Z	2.128	2.128	0	%100

**Member Distributed Loads (BLC 59 : Structure Wi (180 Deg))**

	Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft.F...	Start Location[in,.%]	End Location[in,.%]
1	M1	X	0	0	0	%100
2	M1	Z	.11	.11	0	%100
3	M2	X	0	0	0	%100
4	M2	Z	3.121	3.121	0	%100
5	M4	X	0	0	0	%100
6	M4	Z	4.193	4.193	0	%100
7	MP1A	X	0	0	0	%100
8	MP1A	Z	3.38	3.38	0	%100
9	MP2A	X	0	0	0	%100
10	MP2A	Z	3.38	3.38	0	%100
11	MP3A	X	0	0	0	%100
12	MP3A	Z	3.38	3.38	0	%100
13	MP4A	X	0	0	0	%100
14	MP4A	Z	3.38	3.38	0	%100
15	M13	X	0	0	0	%100
16	M13	Z	2.457	2.457	0	%100

**Member Distributed Loads (BLC 60 : Structure Wi (210 Deg))**

	Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft.F...	Start Location[in,.%]	End Location[in,.%]
1	M1	X	-.214	-.214	0	%100
2	M1	Z	.371	.371	0	%100
3	M2	X	-1.561	-1.561	0	%100
4	M2	Z	2.703	2.703	0	%100
5	M4	X	-1.572	-1.572	0	%100
6	M4	Z	2.723	2.723	0	%100
7	MP1A	X	-1.69	-1.69	0	%100
8	MP1A	Z	2.927	2.927	0	%100
9	MP2A	X	-1.69	-1.69	0	%100
10	MP2A	Z	2.927	2.927	0	%100
11	MP3A	X	-1.69	-1.69	0	%100
12	MP3A	Z	2.927	2.927	0	%100
13	MP4A	X	-1.69	-1.69	0	%100
14	MP4A	Z	2.927	2.927	0	%100
15	M13	X	-1.229	-1.229	0	%100
16	M13	Z	2.128	2.128	0	%100

**Member Distributed Loads (BLC 61 : Structure Wi (240 Deg))**

Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft.F...	Start Location[in, %]	End Location[in, %]	
1	M1	X	-1.861	-1.861	0	%100
2	M1	Z	1.074	1.074	0	%100
3	M2	X	-2.703	-2.703	0	%100
4	M2	Z	1.561	1.561	0	%100
5	M4	X	-.908	-.908	0	%100
6	M4	Z	.524	.524	0	%100
7	MP1A	X	-2.927	-2.927	0	%100
8	MP1A	Z	1.69	1.69	0	%100
9	MP2A	X	-2.927	-2.927	0	%100
10	MP2A	Z	1.69	1.69	0	%100
11	MP3A	X	-2.927	-2.927	0	%100
12	MP3A	Z	1.69	1.69	0	%100
13	MP4A	X	-2.927	-2.927	0	%100
14	MP4A	Z	1.69	1.69	0	%100
15	M13	X	-2.128	-2.128	0	%100
16	M13	Z	1.229	1.229	0	%100

**Member Distributed Loads (BLC 62 : Structure Wi (270 Deg))**

Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft.F...	Start Location[in, %]	End Location[in, %]	
1	M1	X	-3.551	-3.551	0	%100
2	M1	Z	0	0	0	%100
3	M2	X	-3.121	-3.121	0	%100
4	M2	Z	0	0	0	%100
5	M4	X	0	0	0	%100
6	M4	Z	0	0	0	%100
7	MP1A	X	-3.38	-3.38	0	%100
8	MP1A	Z	0	0	0	%100
9	MP2A	X	-3.38	-3.38	0	%100
10	MP2A	Z	0	0	0	%100
11	MP3A	X	-3.38	-3.38	0	%100
12	MP3A	Z	0	0	0	%100
13	MP4A	X	-3.38	-3.38	0	%100
14	MP4A	Z	0	0	0	%100
15	M13	X	-2.457	-2.457	0	%100
16	M13	Z	0	0	0	%100

**Member Distributed Loads (BLC 63 : Structure Wi (300 Deg))**

Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft.F...	Start Location[in, %]	End Location[in, %]	
1	M1	X	-2.8	-2.8	0	%100
2	M1	Z	-1.616	-1.616	0	%100
3	M2	X	-2.703	-2.703	0	%100
4	M2	Z	-1.561	-1.561	0	%100
5	M4	X	-.908	-.908	0	%100
6	M4	Z	-.524	-.524	0	%100
7	MP1A	X	-2.927	-2.927	0	%100
8	MP1A	Z	-1.69	-1.69	0	%100
9	MP2A	X	-2.927	-2.927	0	%100
10	MP2A	Z	-1.69	-1.69	0	%100
11	MP3A	X	-2.927	-2.927	0	%100
12	MP3A	Z	-1.69	-1.69	0	%100
13	MP4A	X	-2.927	-2.927	0	%100
14	MP4A	Z	-1.69	-1.69	0	%100
15	M13	X	-2.128	-2.128	0	%100
16	M13	Z	-1.229	-1.229	0	%100



**Member Distributed Loads (BLC 67 : Structure Wm (60 Deg))**

	Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft.F...	Start Location[in.%,]	End Location[in.%,]
1	M1	X	.416	.416	0	%100
2	M1	Z	-.24	-.24	0	%100
3	M2	X	.544	.544	0	%100
4	M2	Z	-.314	-.314	0	%100
5	M4	X	.191	.191	0	%100
6	M4	Z	-.11	-.11	0	%100
7	MP1A	X	.535	.535	0	%100
8	MP1A	Z	-.309	-.309	0	%100
9	MP2A	X	.535	.535	0	%100
10	MP2A	Z	-.309	-.309	0	%100
11	MP3A	X	.535	.535	0	%100
12	MP3A	Z	-.309	-.309	0	%100
13	MP4A	X	.535	.535	0	%100
14	MP4A	Z	-.309	-.309	0	%100
15	M13	X	.387	.387	0	%100
16	M13	Z	-.224	-.224	0	%100

**Member Distributed Loads (BLC 68 : Structure Wm (90 Deg))**

	Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft.F...	Start Location[in.%,]	End Location[in.%,]
1	M1	X	.793	.793	0	%100
2	M1	Z	0	0	0	%100
3	M2	X	.629	.629	0	%100
4	M2	Z	0	0	0	%100
5	M4	X	0	0	0	%100
6	M4	Z	0	0	0	%100
7	MP1A	X	.618	.618	0	%100
8	MP1A	Z	0	0	0	%100
9	MP2A	X	.618	.618	0	%100
10	MP2A	Z	0	0	0	%100
11	MP3A	X	.618	.618	0	%100
12	MP3A	Z	0	0	0	%100
13	MP4A	X	.618	.618	0	%100
14	MP4A	Z	0	0	0	%100
15	M13	X	.447	.447	0	%100
16	M13	Z	0	0	0	%100

**Member Distributed Loads (BLC 69 : Structure Wm (120 Deg))**

	Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft.F...	Start Location[in.%,]	End Location[in.%,]
1	M1	X	.626	.626	0	%100
2	M1	Z	.361	.361	0	%100
3	M2	X	.544	.544	0	%100
4	M2	Z	.314	.314	0	%100
5	M4	X	.191	.191	0	%100
6	M4	Z	.11	.11	0	%100
7	MP1A	X	.535	.535	0	%100
8	MP1A	Z	.309	.309	0	%100
9	MP2A	X	.535	.535	0	%100
10	MP2A	Z	.309	.309	0	%100
11	MP3A	X	.535	.535	0	%100
12	MP3A	Z	.309	.309	0	%100
13	MP4A	X	.535	.535	0	%100
14	MP4A	Z	.309	.309	0	%100
15	M13	X	.387	.387	0	%100
16	M13	Z	.224	.224	0	%100





**Member Distributed Loads (BLC 73 : Structure Wm (240 Deg))**

	Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft.F...	Start Location[in, %]	End Location[in, %]
1	M1	X	- .416	- .416	0	%100
2	M1	Z	.24	.24	0	%100
3	M2	X	- .544	- .544	0	%100
4	M2	Z	.314	.314	0	%100
5	M4	X	- .191	- .191	0	%100
6	M4	Z	.11	.11	0	%100
7	MP1A	X	- .535	- .535	0	%100
8	MP1A	Z	.309	.309	0	%100
9	MP2A	X	- .535	- .535	0	%100
10	MP2A	Z	.309	.309	0	%100
11	MP3A	X	- .535	- .535	0	%100
12	MP3A	Z	.309	.309	0	%100
13	MP4A	X	- .535	- .535	0	%100
14	MP4A	Z	.309	.309	0	%100
15	M13	X	- .387	- .387	0	%100
16	M13	Z	.224	.224	0	%100

**Member Distributed Loads (BLC 74 : Structure Wm (270 Deg))**

	Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft.F...	Start Location[in, %]	End Location[in, %]
1	M1	X	- .793	- .793	0	%100
2	M1	Z	0	0	0	%100
3	M2	X	- .629	- .629	0	%100
4	M2	Z	0	0	0	%100
5	M4	X	0	0	0	%100
6	M4	Z	0	0	0	%100
7	MP1A	X	- .618	- .618	0	%100
8	MP1A	Z	0	0	0	%100
9	MP2A	X	- .618	- .618	0	%100
10	MP2A	Z	0	0	0	%100
11	MP3A	X	- .618	- .618	0	%100
12	MP3A	Z	0	0	0	%100
13	MP4A	X	- .618	- .618	0	%100
14	MP4A	Z	0	0	0	%100
15	M13	X	- .447	- .447	0	%100
16	M13	Z	0	0	0	%100

**Member Distributed Loads (BLC 75 : Structure Wm (300 Deg))**

	Member Label	Direction	Start Magnitude[lb/ft....	End Magnitude[lb/ft.F...	Start Location[in, %]	End Location[in, %]
1	M1	X	- .626	- .626	0	%100
2	M1	Z	- .361	- .361	0	%100
3	M2	X	- .544	- .544	0	%100
4	M2	Z	- .314	- .314	0	%100
5	M4	X	- .191	- .191	0	%100
6	M4	Z	- .11	- .11	0	%100
7	MP1A	X	- .535	- .535	0	%100
8	MP1A	Z	- .309	- .309	0	%100
9	MP2A	X	- .535	- .535	0	%100
10	MP2A	Z	- .309	- .309	0	%100
11	MP3A	X	- .535	- .535	0	%100
12	MP3A	Z	- .309	- .309	0	%100
13	MP4A	X	- .535	- .535	0	%100
14	MP4A	Z	- .309	- .309	0	%100
15	M13	X	- .387	- .387	0	%100
16	M13	Z	- .224	- .224	0	%100






## I. Mount-to-Tower Connection Check

### RISA Model Data

Nodes (labeled per RISA)	Orientation (per graphic of typical platform)
N1	60




TYPICAL PLATFORM

### Tower Connection Bolt Checks

Any moment resistance?:  
 Bolt Quantity per Reaction:  
 $d_x$  (in) (Delta X of typ. bolt config. sketch) :  
 $d_y$  (in) (Delta Y of typ. bolt config. sketch) :  
 Bolt Type:  
 Bolt Diameter (in):  
 Required Tensile Strength (kips):  
 Required Shear Strength (kips):  
 Tensile Strength / bolt (kips):  
 Shear Strength / bolt (kips):  
 Tensile Capacity Overall:  
 Shear Capacity Overall:

yes
4
7
7
A325N
0.625
20.1
9.3
20.7
12.4
<b>24.3%*</b>
<b>18.7%</b>



\*Note: Tension reduction not required if tension or shear capacity < 30%

### Tower Connection Plate and Weld Check

Connecting Standoff Member Shape:  
 Plate Width (in):  
 Plate Height (in):  
 $W_1$  (in):  
 $W_2$  (in):  
 $F_y$  (ksi, plate):  
 $t_{plate}$  (in):  
 Weld Size (1/16 in):  
 $\Phi * R_n$  (kip/in):  
 Required Weld Strength (kip/in):  
 Plate Bending Capacity:  
 Weld Capacity:

Rect
10
10
4
4
36
0.5
3
4.18
3.29
<b>96.2%</b>
<b>78.8%</b>

### Max Plate Bending Strengths

$M_{u_{xx}}$ (kip-in) :	8.4
$\Phi * M_{n_{xx}}$ (kip-in) :	20.3
$M_{u_{yy}}$ (kip-in) :	11.1
$\Phi * M_{n_{yy}}$ (kip-in) :	20.3



# Mount Desktop – Post Modification Inspection (PMI) Report Requirements

## Documents & Photos Required from Contractor – **Passing Mount Analysis**

---

**Purpose** – to provide Maser Consulting the proper documentation in order to complete the required Mount Desktop review of the Post Modification Inspection Report.

- Contractor is responsible for making certain the photos provided as noted below provide confirmation that the installation was completed in accordance with this Passing Mount Analysis.
- Contractor shall relay any data that can impact the performance of the mount, this includes safety issues.

### **Base Requirements:**


















- Any special photos outside of the standard requirements will be indicated on the passing MA
- Verification that loading is as communicated in the Passing Mount Analysis. NOTE If loading is different than what is conveyed contact Maser Consulting immediately.
- Each photo should be time and date stamped
- Photos should be high resolution and submitted in a Zip File and should be organized in the file structure as depicted in Schedule A attached.
- Contractor shall ensure that the safety climb wire rope is supported and not adversely impacted by the install of the modification components. This may involve the install of wire rope guides, or other items to protect the wire rope.
- The photos in the file structure should be uploaded to <https://pmi.vzsmart.com> as depicted on the drawings

### **Photo Requirements:**


- Base and “During Installation Photos”
  - Base pictures include
    - Photo of Gate Signs showing the tower owner, site name, and number
    - Photo of carrier shelter showing the carrier site name and number if available
    - Photos of the galvanizing compound and/or paint used (if applicable), clearly showing the label and name
  - “During Installation Photos if provided - must be placed only in this folder
- Photos taken at ground level
  - Overall tower structure before and after installation of the equipment modifications
  - Photos of the appropriate mount before and after installation of the modifications; if the mounts are at different rad elevations, pictures must be provided for all elevations that the modifications were installed
- Photos taken at Mount Elevation
  - Photos showing each individual sector before and also after installation of equipment. These photos should also certify that the placement and geometry of the equipment on the mount is as depicted on the sketch and table in the mount analysis




## **Schedule A – Photo & Document File Structure**

-  VzW Site Number / Name
  -  Base & “During Installation” Photos
  -  Pre-Installation Photos
    -  Alpha
    -  Beta
    -  Gamma
    -  Ground Level
    -  Tape Drop
  -  Post-Installation Photos
    -  Alpha
    -  Beta
    -  Gamma
    -  Ground Level
    -  Tape Drop
    -  Photos of climbing facility and safety climb – If Present
-  Certifications – Submission of this document including certifications
-  Specific Required Additional Photos

Plan View




Front View  
Looking at Structure




Ref#	Model	Height (in)	Width (in)	H Dist Frm L.	Pipe #	Pipe Pos V	Ant Pos	C. Ant Frm T.	Ant H Off	Status	Validation
A1	MX06FRO660-03	71.3	15.4	87.5	2	a	Front	36	8	Added	
A1	MX06FRO660-03	71.3	15.4	87.5	2	b	Front	36	-8	Added	
R5	B5/B13 RRH-BR04C	15	15	87.5	2	a	Behind	18	0	Added	
R2	MT6407-77A	35.1	16.1	48.5	3	a	Front	36	0	Added	
R4	B2/B66A RRH-BR049	15	15	48.5	3	a	Behind	18	0	Added	
A8	CHB626-43-2X	7.1	14.6	48.5	3	a	Behind	48	0	Added	

Plan View




Front View  
Looking at Structure




Ref#	Model	Height (in)	Width (in)	H Dist Frm L.	Pipe #	Pipe Pos V	Ant Pos	C. Ant Frm T.	Ant H Off	Status	Validation
A1	MX06FRO660-03	71.3	15.4	87.5	2	a	Front	36	8	Added	
A1	MX06FRO660-03	71.3	15.4	87.5	2	b	Front	36	-8	Added	
R5	B5/B13 RRH-BR04C	15	15	87.5	2	a	Behind	18	0	Added	
R2	MT6407-77A	35.1	16.1	48.5	3	a	Front	36	0	Added	
R4	B2/B66A RRH-BR049	15	15	48.5	3	a	Behind	18	0	Added	
A8	CHB626-43-2X	7.1	14.6	48.5	3	a	Behind	48	0	Added	

Plan View



Front View  
Looking at Structure



Ref#	Model	Height (in)	Width (in)	H Dist Frm L.	Pipe #	Pipe Pos V	Ant Pos	C. Ant Frm T.	Ant H Off	Status	Validation
A1	MX06FRO660-03	71.3	15.4	87.5	2	a	Front	36	8	Added	
A1	MX06FRO660-03	71.3	15.4	87.5	2	b	Front	36	-8	Added	
R5	B5/B13 RRH-BR04C	15	15	87.5	2	a	Behind	18	0	Added	
R2	MT6407-77A	35.1	16.1	48.5	3	a	Front	36	0	Added	
R4	B2/B66A RRH-BR049	15	15	48.5	3	a	Behind	18	0	Added	
A8	CHB626-43-2X	7.1	14.6	48.5	3	a	Behind	48	0	Added	

# Maser Consulting Connecticut

**Subject**

TIA-222-H Usage

**Site Information**

Site ID: 535838-VZW / THOMPSON NORTH CT  
Site Name: THOMPSON NORTH CT  
Carrier Name: Verizon Wireless  
Address: 44 Rich Road  
North Grosvenordal, Connecticut 06277  
Windham County  
Latitude: 42.0115°  
Longitude: -71.852028°

**Structure Information**

Tower Type: 141-Ft Monopole  
Mount Type: 12.54-Ft T-Arm

To Whom It May Concern,


We respectfully submit the above referenced Antenna Mount Structural Analysis report in conformance with ANSI/TIA-222-H, Structural Standard for Antenna Supporting Structures and Antennas and Small Wind Turbine Support Structures.

The 2015 International Building Code states that, in Section 3108, telecommunication towers shall be designed and constructed in accordance with the provisions of TIA-222. TIA-222-H is the latest revision of the TIA-222 Standard, effective as of January 01, 2018.

As with all ANSI standards and engineering best practice is to apply the most current revision of the standard. This ensures the engineer is applying all updates. As an example, the TIA-222-H Standard includes updates to bring it in line with the latest AISC and ACI standards and it also incorporates the latest wind speed maps by ASCE 7 based on updated studies of the wind data.

The TIA-222-H standard clarifies these specific requirements for the antenna mount analysis such as modeling methods, seismic analysis, 30-degree increment wind directions and maintenance loading. Therefore, it is our opinion that TIA-222-H is the most appropriate standard for antenna mount structural analysis and is acceptable for use at this site to ensure the engineer is taking into account the most current engineering standard available.

Sincerely,



Dejian Xu, PE  
Technical Manager

# **ATTACHMENT 5**





Rich Rd

Wilsonville Rd

Wilsonville Rd

Wilsonville Rd

Wilsonville Rd



THOMPSON,CT

38 RICH RD

**Location**

38 RICH RD

**Mblu**

97/ 28/ 7/ /

**Acct#**

005410

**Owner**

THOMPSON TOWN OF

**Assessment**

\$43,900

**Appraisal**

\$62,600

**PID**

2478

**Building Count**

1

Current Value

**Appraisal**

Valuation Year	Improvements	Land	Total
2019	\$0	\$62,600	\$62,600

---

**Assessment**

Valuation Year	Improvements	Land	Total
2019	\$0	\$43,900	\$43,900

**Owner of Record**

**Owner** THOMPSON TOWN OF

**Co-Owner**

**Address** PO BOX 899  
N GROSVENORDALE, CT 06255

**Sale Price** \$0

**Certificate**

**Book & Page** 0075/0087

**Sale Date** 02/10/1965

Ownership History

---

**Ownership History**

Owner	Sale Price	Certificate	Book & Page	Sale Date
THOMPSON TOWN OF	\$0		0075/0087	02/10/1965

Building Information

Building 1 : Section 1

**Year Built:**

**Living Area:** 0

**Replacement Cost:** \$0

**Building Percent Good:**

**Replacement Cost**

**Less Depreciation:** \$0

---

**Building Attributes**

Field	Description
Style	Vacant Land
Model	
Grade:	
Stories:	

Occupancy	
Exterior Wall 1	
Exterior Wall 2	
Roof Structure:	
Roof Cover	
Interior Wall 1	
Interior Wall 2	
Interior Flr 1	
Interior Flr 2	
Heat Fuel	
Heat Type:	
AC Type:	
Total Bedrooms:	
Total Bthrms:	
Total Half Baths:	
Total Xtra Fixtrs:	
Total Rooms:	
Bath Style:	
Kitchen Style:	



Building Photo

Building Layout

---

**Building Sub-Areas (sq ft) Legend**

No Data for Building Sub-Areas

Extra Features

---

**Extra Features Legend**

No Data for Extra Features

Land

Land Use

**Use Code** 9030

**Description** MUNICIPAL MDL-00

**Zone** R40

**Neighborhood**

**Alt Land Appr** No

**Category**

Land Line Valuation

**Size (Acres)** 8

**Frontage** 290

**Depth** 0

**Assessed Value** \$43,900

**Appraised Value** \$62,600

Outbuildings

**Outbuildings Legend**

No Data for Outbuildings

Valuation History

**Appraisal**

Valuation Year	Improvements	Land	Total
2018	\$0	\$213,500	\$213,500
2017	\$0	\$213,500	\$213,500
2016	\$0	\$213,500	\$213,500

**Assessment**

Valuation Year	Improvements	Land	Total
2018	\$0	\$149,500	\$149,500
2017	\$0	\$149,500	\$149,500
2016	\$0	\$149,500	\$149,500

(c) 2021 Vision Government Solutions, Inc. All rights reserved.

closecloseclose

# **ATTACHMENT 6**



**THOMPSON NORTH  
Certificate of Mailing — Firm**

Name and Address of Sender  Kenneth C. Baldwin, Esq. Robinson & Cole LLP 280 Trumbull Street Hartford, CT 06103	TOTAL NO. of Pieces Listed by Sender  2	TOTAL NO. of Pieces Received at Post Office™  2	Affix Stamp Here <i>Postmark with Date of Receipt.</i>			
	Postmaster, per (name of receiving employee)  <i>CR</i>					

USPS® Tracking Number Firm-specific Identifier	Address (Name, Street, City, State, and ZIP Code™)	Postage	Fee	Special Handling	Parcel Airlift
1.	Amy St. Onge, First Selectman Town of Thompson 815 Riverside Drive North Grosvenordale, CT 06255				
2.	Tyra Penn-Gesek, Director of Planning and Development Town of Thompson 815 Riverside Drive North Grosvenordale, CT 06255				
3.					
4.					
5.					
6.					