



10 Industrial Avenue, Suite 3
Mahwah NJ, 07430
Phone: (201)-951-3869
Tom Kincaid
Real Estate Consultant

August 1, 2014

Hand Delivered

Ms. Melanie A. Bachman
Acting Executive Director
Connecticut Siting Council
10 Franklin Square
New Britain, CT 06051

CC to Property Owner:
R L R Investments LLC
600 Gillan Rd Wilmington, OH 45177-9089

RE: Sprint Spectrum L.P. notice of intent to modify an existing telecommunications facility located at 90 N. Plains Industrial Road, Wallingford, CT 06492. Known to Sprint Spectrum L.P. as site CT43XC839.

Dear Ms. Bachman:

In order to accommodate technological changes, implement Code Division Multiple Access ("CDMA") and/or Long Term Evolution ("LTE") capabilities, and enhance system performance in the state of Connecticut, Sprint Spectrum L.P. plans to modify the equipment configurations at many of its existing cell sites. Please accept this letter and attachments as notification, pursuant to R.C.S.A. Section 16-50j-73, of construction which constitutes an exempt modification pursuant to R.C.S.A. Section 16-50j-72(b)(2). In compliance with R.C.S.A. Section 16-50j-73, a copy of this letter and its attachments is being sent to the chief elected official of the municipality in which affected cell site is located.

CDMA employs Spread-Spectrum technology and special coding scheme to allow multiple users to be multiplexed over the same physical channel.

LTE is a new high-performance air interface for cellular mobile communications. It is designed to increase the capacity and speed of mobile telephone networks.

Attached is a summary of the planned modifications, including power density calculations reflecting the change in Sprint's operations at the site. Also included is

documentation of the structural sufficiency of the tower to accommodate the revised antenna configuration.

The changes to the facility do not constitute modification as defined Connecticut General Statutes (“C.G.S.”) Section 16-50i(d) because the general physical characteristics of the facility will not be significantly changed or altered. Rather, the planned changes to the facility fall squarely within those activities explicitly provided for the R.C.S.A. Section 16-50j-72(b)(2).

1. The height of the overall structure will not be affected.
2. The proposed changes will not extend the site boundaries. There will be no effect on the site compound.
3. The proposed changes will not increase the noise level at the existing facility by 6 decibels or more.
4. Radio Frequency power density may increase due to the use of one or more CDMA transmissions. Moreover, LTE will utilize additional radio frequencies newly licensed by the FCC for cellular mobile communications. However, the changes will not increase the calculated “worst case” power density for the combined operations at the site to a level at or above the applicable standard for uncontrolled environments as calculated for a mixed frequency site.

For the foregoing reasons Sprint Spectrum L.P. respectfully submits that the proposed changes at the referenced site constitute exempt modifications under R.C.S.A. Section 16-50j-72(b)(2).

Please feel free to call me at (845) 499-4712 or email JNotaro@Transcendwireless.com with questions concerning this matter.
Thank you for your consideration.

Sincerely,

Jennifer Notaro
Real Estate Consultant

RADIO FREQUENCY FCC REGULATORY COMPLIANCE
MAXIMUM PERMISSIBLE EXPOSURE (MPE) ASSESSMENT

Sprint Existing Facility

Site ID: CT43XC839

Bilkay's Express

90 N. Plains Industrial Road
Wallingford, CT 06492

July 27, 2014

EBI Project Number: 62144044

July 27, 2014

Sprint
Attn: RF Engineering Manager
1 International Boulevard, Suite 800
Mahwah, NJ 07495

Re: Radio Frequency Maximum Permissible Exposure (MPE) Assessment for Site:
CT43XC839 - Bilkay's Express

Site Total: 53.76% - MPE% in full compliance

EBI Consulting was directed to analyze the proposed upgrades to the existing Sprint facility located at 90 N. Plains Industrial Road, Wallingford, CT, for the purpose of determining whether the radio frequency (RF) exposure levels from the proposed Sprint equipment upgrades on this property are within specified federal limits.

All information used in this report was analyzed as a percentage of current Maximum Permissible Exposure (% MPE) as listed in the FCC OET Bulletin 65 Edition 97-01 and ANSI/IEEE Std C95.1. The FCC regulates Maximum Permissible Exposure in units of microwatts per square centimeter ($\mu\text{W}/\text{cm}^2$). The number of $\mu\text{W}/\text{cm}^2$ calculated at each sample point is called the power density. The exposure limit for power density varies depending upon the frequencies being utilized. Wireless Carriers and Paging Services use different frequency bands each with different exposure limits, therefore it is necessary to report results and limits in terms of percent MPE rather than power density.

All results were compared to the FCC (Federal Communications Commission) radio frequency exposure rules, 47 CFR 1.1307(b)(1) – (b)(3), to determine compliance with the Maximum Permissible Exposure (MPE) limits for General Population/Uncontrolled environments as defined below.

General population/uncontrolled exposure limits apply to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Therefore, members of the general public would always be considered under this category when exposure is not employment related, for example, in the case of a telecommunications tower that exposes persons in a nearby residential area.

Public exposure to radio frequencies is regulated and enforced in units of microwatts per square centimeter ($\mu\text{W}/\text{cm}^2$). The general population exposure limit for the cellular band (850 MHz Band) is approximately $567 \mu\text{W}/\text{cm}^2$, and the general population exposure limit for the 1900 MHz and 2500 MHz bands is $1000 \mu\text{W}/\text{cm}^2$. Because each carrier will be using different frequency bands, and each frequency band has different exposure limits, it is necessary to report percent of MPE rather than power density.

Occupational/controlled exposure limits apply to situations in which persons are exposed as a consequence of their employment and in which those persons who are exposed have been made fully aware of the potential for exposure and can exercise control over their exposure. Occupational/controlled exposure limits also apply where exposure is of a transient nature as a result of incidental passage through a location where exposure levels may be above general population/uncontrolled limits (see below), as long as the exposed person has been made fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Additional details can be found in FCC OET 65.

CALCULATIONS

Calculations were done for the proposed upgrades to the existing Sprint Wireless antenna facility located at 90 N. Plains Industrial Road, Wallingford, CT, using the equipment information listed below. All calculations were performed per the specifications under FCC OET 65. All calculations were performed assuming a lobe representing the maximum gain of the antenna per the antenna manufactures supplied specifications, minus 10 dB, was focused at the base of the tower. For this report the sample point is the top of a 6 foot person standing at the base of the tower.

For all calculations, all emissions were calculated using the following assumptions:

- 1) 3 channels in the 1900 MHz Band were considered for each sector of the proposed installation.
- 2) 1 channel in the 800 MHz Band was considered for each sector of the proposed installation
- 3) 2 channels in the 2500 MHz Band were considered for each sector of the proposed installation.
- 4) All radios at the proposed installation were considered to be running at full power and were uncombined in their RF transmissions paths per carrier prescribed configuration. Per FCC OET Bulletin No. 65 - Edition 97-01 recommendations to achieve the maximum anticipated value at each sample point, all power levels emitting from the proposed antenna installation are increased by a factor of 2.56 to account for possible in-phase reflections from the surrounding environment. This is rarely the case, and if so, is never continuous.
- 5) For the following calculations the sample point was the top of a six foot person standing at the base of the tower. The maximum gain of the antenna per the antenna manufactures supplied specifications minus 10 dB was used in this direction. This value is a very conservative estimate as gain reductions for these particular antennas are typically much higher in this direction.

- 6) The antennas used in this modeling are the RFS APXVSPP18-C-A20 and the RFS APXVTM14-C-I20. This is based on feedback from the carrier with regards to anticipated antenna selection. The RFS APXVSPP18-C-A20 has a 15.9 dBd gain value at its main lobe at 1900 MHz and 13.4 dBd at its main lobe for 850 MHz. The RFS APXVTM14-C-I20 has a 15.9 dBd gain value at its main lobe at 2500 MHz. The maximum gain of the antenna per the antenna manufactures supplied specifications, minus 10 dB, was used for all calculations. This value is a very conservative estimate as gain reductions for these particular antennas are typically much higher in this direction.
- 7) The antenna mounting height centerline for the proposed antennas is **118 feet** above ground level (AGL).
- 8) Emissions values for additional carriers were taken from the Connecticut Siting Council active database. Values in this database are provided by the individual carriers themselves.

All calculation were done with respect to uncontrolled / general public threshold limits

| | |
|--------------|--|
| Site ID | CT43XC839 - Bilkay's Express |
| Site Address | 90 N. Plains Industrial Road, Wallingford, CT, 06492 |
| Site Type | Monopole |

Sector 1

| Antenna Number | Antenna Make | Antenna Model | Radio Type | Frequency Band | Technology | Power Out Per Channel (Watts) | Number of Channels | Composite Power | Antenna Gain (10 db reduction) | Antenna Height (ft) | analysis height | Cable Size | Cable Loss (dB) | Additional Loss (dB) | ERP | Power Density Percentage |
|-----------------------------------|--------------|-----------------|------------|----------------|------------|-------------------------------|--------------------|-----------------|--------------------------------|---------------------|-----------------|------------|-----------------|----------------------|--------|--------------------------|
| 1a | RFS | APXVSP18-C-A20 | RRH | 1900 MHz | CDMA / LTE | 20 | 3 | 60 | 5.9 | 118 | 112 | 1/2 " | 0.5 | 0 | 208.04 | 0.60% |
| 1a | RFS | APXVSP18-C-A20 | RRH | 850 MHz | CDMA / LTE | 20 | 1 | 20 | 3.4 | 118 | 112 | 1/2 " | 0.5 | 0 | 39.00 | 0.20% |
| 1B | RFS | APXVTMM14-C-120 | RRH | 2500 MHz | CDMA / LTE | 20 | 2 | 40 | 5.9 | 118 | 112 | 1/2 " | 0.5 | 0 | 138.69 | 0.70% |
| Sector total Power Density Value: | | | | | | | | | | | | | | | | 1.49% |

Sector 2

| Antenna Number | Antenna Make | Antenna Model | Radio Type | Frequency Band | Technology | Power Out Per Channel (Watts) | Number of Channels | Composite Power | Antenna Gain (10 db reduction) | Antenna Height (ft) | analysis height | Cable Size | Cable Loss (dB) | Additional Loss (dB) | ERP | Power Density Percentage |
|-----------------------------------|--------------|-----------------|------------|----------------|------------|-------------------------------|--------------------|-----------------|--------------------------------|---------------------|-----------------|------------|-----------------|----------------------|--------|--------------------------|
| 2a | RFS | APXVSP18-C-A20 | RRH | 1900 MHz | CDMA / LTE | 20 | 3 | 60 | 5.9 | 118 | 112 | 1/2 " | 0.5 | 0 | 208.04 | 0.60% |
| 2a | RFS | APXVSP18-C-A20 | RRH | 850 MHz | CDMA / LTE | 20 | 1 | 20 | 3.4 | 118 | 112 | 1/2 " | 0.5 | 0 | 39.00 | 0.20% |
| 2B | RFS | APXVTMM14-C-120 | RRH | 2500 MHz | CDMA / LTE | 20 | 2 | 40 | 5.9 | 118 | 112 | 1/2 " | 0.5 | 0 | 138.69 | 0.70% |
| Sector total Power Density Value: | | | | | | | | | | | | | | | | 1.49% |

Sector 3

| Antenna Number | Antenna Make | Antenna Model | Radio Type | Frequency Band | Technology | Power Out Per Channel (Watts) | Number of Channels | Composite Power | Antenna Gain (10 db reduction) | Antenna Height (ft) | analysis height | Cable Size | Cable Loss (dB) | Additional Loss (dB) | ERP | Power Density Percentage |
|-----------------------------------|--------------|-----------------|------------|----------------|------------|-------------------------------|--------------------|-----------------|--------------------------------|---------------------|-----------------|------------|-----------------|----------------------|--------|--------------------------|
| 3a | RFS | APXVSP18-C-A20 | RRH | 1900 MHz | CDMA / LTE | 20 | 3 | 60 | 5.9 | 118 | 112 | 1/2 " | 0.5 | 0 | 208.04 | 0.60% |
| 3a | RFS | APXVSP18-C-A20 | RRH | 850 MHz | CDMA / LTE | 20 | 1 | 20 | 3.4 | 118 | 112 | 1/2 " | 0.5 | 0 | 39.00 | 0.20% |
| 3B | RFS | APXVTMM14-C-120 | RRH | 2500 MHz | CDMA / LTE | 20 | 2 | 40 | 5.9 | 118 | 112 | 1/2 " | 0.5 | 0 | 138.69 | 0.70% |
| Sector total Power Density Value: | | | | | | | | | | | | | | | | 1.49% |

| Site Composite MPE % | |
|-------------------------|---------------|
| Carrier | MPE % |
| Sprint | 4.48% |
| Clearwire | 0.67% |
| MetroPCS | 7.42% |
| T-Mobile | 0.16% |
| XM Satellite Radio | 1.10% |
| AT&T | 6.01% |
| Verizon Wireless | 33.92% |
| Total Site MPE % | 53.76% |

Summary

All calculations performed for this analysis yielded results that were well within the allowable limits for general public Maximum Permissible Exposure (MPE) to radio frequency energy.

The anticipated Maximum Composite contributions from the Sprint facility are **4.48%** (**1.49% from sector 1, 1.49% from sector 2 and 1.49% from sector 3**) of the allowable FCC established general public limit considering all three sectors simultaneously sampled at the ground level.

The anticipated composite MPE value for this site assuming all carriers present is **53.76%** of the allowable FCC established general public limit sampled at 6 feet above ground level. This total composite site value is based upon MPE values listed in the Connecticut Siting Council database for existing carrier emissions.

FCC guidelines state that if a site is found to be out of compliance (over allowable thresholds), that carriers over a 5% contribution to the composite value will require measures to bring the site into compliance. For this facility, the composite values calculated were well within the allowable 100% threshold standard per the federal government.



Scott Heffernan
RF Engineering Director

EBI Consulting
21 B Street
Burlington, MA 01803



AMERICAN TOWER®
CORPORATION

Structural Analysis Report

Structure : 178.5 ft Monopole
ATC Site Name : Bilkays Express, CT
ATC Site Number : 302467
Engineering Number : 58996421
Proposed Carrier : Sprint Nextel
Carrier Site Name : Bilkays Express
Carrier Site Number : CT43XC839
Site Location : 90 North Plains Industrial Rd.
Wallingford, CT 06492-2334
41.480761,-72.817700
County : New Haven
Date : June 13, 2014
Max Usage : 81%
Result : Pass

Daniel Motter



Jun 13 2014 5:30 PM



Table of Contents

| | |
|--------------------------------------|----------|
| Introduction | 1 |
| Supporting Documents | 1 |
| Analysis | 1 |
| Conclusion..... | 1 |
| Existing and Reserved Equipment..... | 2 |
| Equipment to be Removed..... | 2 |
| Proposed Equipment | 3 |
| Structure Usages | 4 |
| Foundations | 4 |
| Deflection, Twist, and Sway..... | 4 |
| Standard Conditions | 5 |
| Calculations | Attached |



Introduction

The purpose of this report is to summarize results of a structural analysis performed on the 178.5 ft monopole to reflect the change in loading by Sprint Nextel.

Supporting Documents

| | |
|----------------------------|---|
| Tower Drawings | FWT Job #18357, dated March 19, 1999 |
| Foundation Drawing | FWT Job #18357, dated March 19, 1999 |
| Geotechnical Report | Tectonic Work Order #1170.C947C, dated March 11, 1999 |

Analysis

The tower was analyzed using American Tower Corporation's tower analysis software. This program considers an elastic three-dimensional model and second-order effects per ANSI/TIA-222.

| | |
|---------------------------------|---|
| Basic Wind Speed: | 110 mph (3-Second Gust) |
| Basic Wind Speed w/ Ice: | 50 mph (3-Second Gust) w/ 3/4" radial ice concurrent |
| Code: | ANSI/TIA-222-G / 2003 IBC w/ 2005 CT Supplement & 2009 CT Amendment |
| Structure Class: | II |
| Exposure Category: | B |
| Topographic Category: | 1 |

Conclusion

Based on the analysis results, the structure meets the requirements per the applicable codes listed above. The tower and foundation can support the equipment as described in this report.

If you have any questions or require additional information, please contact American Tower via email at Engineering@americantower.com. Please include the American Tower site name, site number, and engineering number in the subject line for any questions.



Existing and Reserved Equipment

| Elevation ¹ (ft) | | Qty | Antenna | Mount Type | Lines | Carrier |
|-----------------------------|--------------------|-----|--------------------------------|-----------------------|--|------------------|
| Mount | RAD | | | | | |
| 178.5 | 181.0 | 9 | 48" x 12" Panel | Low Profile Platform | (12) 1 5/8" Coax | Sprint Nextel |
| | | 3 | 72" x 12" Panel | | | |
| 171.0 | 171.0 | 2 | DragonWave Horizon Compact | Side Arms | (6) 5/16" Coax (2) 2" Conduit (2) 1/2" Coax | Clearwire |
| | | 3 | NextNet BTS-2500 | | | |
| | | 3 | Argus LLPX310R | | | |
| | | 1 | DragonWave A-ANT-11G-2-C | | | |
| | | 1 | DragonWave A-ANT-18G-2-C | | | |
| 160.0 | 160.0 | 3 | Powerwave 7020 | Platform w/ Handrails | (12) 1 5/8" Coax (1) 3" Conduit (6) 0.78" 8 AWG 6 (1) 0.39" Fiber Trunk | AT&T Mobility |
| | | 6 | 14" x 9" TTA | | | |
| | | 3 | Raycap DC6-48-60-18-8F | | | |
| | | 3 | CCI DTMABP7819VG12A | | | |
| | | 6 | Ericsson RRUS A2 Module | | | |
| | | 6 | Ericsson RRUS 11 (Band 7) | | | |
| | | 3 | Ericsson RRUS E2 B29 | | | |
| | | 6 | Ericsson RRUS-12 B2 | | | |
| | | 3 | Ericsson RRUS-32 | | | |
| | | 3 | Powerwave 7770.00 | | | |
| 9 | CCI HPA-65R-BUU-H6 | | | | | |
| 148.0 | 148.0 | 3 | Ericsson KRY 112 144/1 | T-Arm w/ Platforms | (12) 1 5/8" Coax (1) 1 1/4" Hybriflex Cable | T-Mobile |
| | | 3 | Ericsson AIR 21, 1.3 M, B2A B4 | | | |
| | | 3 | Ericsson AIR 21, 1.3M, B4A B2P | | | |
| 135.0 | 138.0 | 6 | RFS FD9R6004/2C-3L | Low Profile Platform | (18) 1 5/8" Coax (1) 1 5/8" Hybriflex | Verizon Wireless |
| | | 3 | Alcatel-Lucent RRH2x40 (700) | | | |
| | | 3 | Alcatel-Lucent RRH2x40-AWS | | | |
| | | 3 | Antel BXA-171063-8BF-EDIN-X | | | |
| | | 3 | Antel BXA-171063-12BF-EDIN | | | |
| | | 1 | RFS DB-T1-6Z-8AB-OZ | | | |
| | | 3 | Antel BXA-80063-6BF-EDIN-X | | | |
| | | 3 | Antel BXA-70063-6CF-EDIN-X | | | |
| 128.0 | 128.0 | 3 | RFS APXV18-206517S-C | Flush | (6) 1 5/8" Coax | Metro PCS |
| 116.0 | 118.0 | 3 | RFS APXVSP18-C-A20 | Low Profile Platform | (3) 1 1/4" Hybriflex Cable | Sprint Nextel |
| | 116.0 | 3 | Alcatel-Lucent 800MHz RRH | | | |
| | | 3 | Alcatel-Lucent 1900MHz 4x45 R | | | |
| 20.0 | 20.0 | 1 | PCTEL GPS-TMG-HR-26N | Standoff | (1) 1/2" Coax | |

Equipment to be Removed

| Elevation ¹ (ft) | | Qty | Antenna | Mount Type | Lines | Carrier |
|-----------------------------|-------|-----|---------------------|------------|-----------------|---------------|
| Mount | RAD | | | | | |
| 116.0 | 118.0 | 6 | Andrew DB980H90R-KL | - | (6) 1 1/4" Coax | Sprint Nextel |



Proposed Equipment

| Elevation ¹ (ft) | | Qty | Antenna | Mount Type | Lines | Carrier |
|-----------------------------|-------|-----|--------------------------------------|----------------------|----------------------|---------------|
| Mount | RAD | | | | | |
| 116.0 | 118.0 | 3 | RFS APXV9TM14-ALU-I20 | Low Profile Platform | (1) 1 1/4" Hybriflex | Sprint Nextel |
| | 116.0 | 3 | Alcatel-Lucent TD-RRH8x20-25 w/ S.S. | | | |

¹Mount elevation is defined as height above bottom of steel structure to the bottom of mount, RAD elevation is defined as center of antenna above ground level (AGL).

Install proposed coax outside the pole shaft. Stacking coax is not allowed.



Structure Usages

| Structural Component | Controlling Usage | Pass/Fail |
|----------------------|-------------------|-----------|
| Anchor Bolts | 81% | Pass |
| Shaft | 73% | Pass |
| Base Plate | 61% | Pass |

Foundations

| Reaction Component | Original Design Reactions | Factored Design Reactions* | Analysis Reactions | % of Design |
|--------------------|---------------------------|----------------------------|--------------------|-------------|
| Moment (Kips-Ft) | 5,025.0 | 6,783.8 | 6,514.5 | 96% |
| Shear (Kips) | 39.9 | 53.9 | 53.5 | 99% |

* The design reactions are factored by 1.35 per ANSI/TIA-222-G, Sec. 15.5.1

The structure base reactions resulting from this analysis are acceptable when compared to those shown on the original structure drawings, therefore no modification or reinforcement of the foundation will be required.

Deflection and Sway*

| Antenna Elevation (ft) | Deflection (ft) | Sway (Rotation) (°) |
|------------------------|-----------------|---------------------|
| 116.0 | 0.651 | 0.668 |

*Deflection and Sway was evaluated considering a design wind speed of 60 mph (3-Second Gust) per ANSI/TIA-222-G



Standard Conditions

All engineering services are performed on the basis that the information used is current and correct. This information may consist of, but is not necessary limited, to:

- Information supplied by the client regarding the structure itself, antenna, mounts and feed line loading on the structure and its components, or other relevant information.
- Information from drawings in the possession of American Tower Corporation, or generated by field inspections or measurements of the structure.

It is the responsibility of the client to ensure that the information provided to ATC Tower Services, Inc. and used in the performance of our engineering services is correct and complete. In the absence of information to the contrary, we assume that all structures were constructed in accordance with the drawings and specifications and that their capacity has not significantly changed from the "as new" condition.

Unless explicitly agreed by both the client and American Tower Corporation, all services will be performed in accordance with the current revision of ANSI/TIA -222. The design basic wind speed will be determined based on the minimum basic wind speed as prescribed in ANSI/TIA-222. Although every effort is taken to ensure that the loading considered is adequate to meet the requirements of all applicable regulatory entities, we can provide no assurance to meet any other local and state codes or requirements. If wind and ice loads or other relevant parameters are to be different from the minimum values recommended by the codes, the client shall specify the exact requirement.


All services are performed, results obtained, and recommendations made in accordance with generally accepted engineering principles and practices. ATC Tower Services, Inc. is not responsible for the conclusions, opinions and recommendations made by others based on the information we supply.


© 2007 - 2014 by ATC IP LLC. All rights reserved.

| Job Information | |
|-----------------|---------------------|
| Pole : | 302467 |
| Code : | ANSI/TIA-222 Rev G |
| Description : | 178.5' FWT Monopole |
| Client : | Sprint Nextel |
| Struct Class : | II |
| Location : | Bilkays Express, CT |
| Shape : | 18 Sides |
| Exposure : | B |
| Height : | 178.50 (ft) |
| Topo : | 1 |
| Base Elev (ft): | 0.00 |
| Taper: | 0.25140(in/ft) |

| Sections Properties | | | | | | | | |
|---------------------|-------------|------------------|---------------------|------------|------------|-------------|---------------|-------------------|
| Shaft Section | Length (ft) | Diameter (in) | | Thick (in) | Joint Type | Overlap | | Steel Grade (ksi) |
| | | Across Flats Top | Across Flats Bottom | | | Length (in) | Taper (in/ft) | |
| 1 | 53.000 | 58.67 | 72.00 | 0.438 | | 0.000 | 0.251401 | 65 |
| 2 | 53.000 | 48.11 | 61.43 | 0.375 | Slip Joint | 96.000 | 0.251401 | 65 |
| 3 | 53.000 | 37.06 | 50.39 | 0.313 | Slip Joint | 79.000 | 0.251401 | 65 |
| 4 | 39.167 | 29.00 | 38.84 | 0.250 | Slip Joint | 61.000 | 0.251401 | 65 |

| Discrete Appurtenance | | | | |
|-----------------------|-----------------|-----|--------------------------------|--|
| Attach Elev (ft) | Force Elev (ft) | Qty | Description | |
| 178.500 | 178.500 | 1 | Flat Low Profile Platform | |
| 178.500 | 181.000 | 9 | 48" x 12" Panel | |
| 178.500 | 181.000 | 3 | 72" x 12" Panel | |
| 171.000 | 171.000 | 1 | DragonWave A-ANT-11G-2-C | |
| 171.000 | 171.000 | 2 | DragonWave Horizon Compact | |
| 171.000 | 171.000 | 3 | Argus LLPX310R | |
| 171.000 | 171.000 | 3 | NextNet BTS-2500 | |
| 171.000 | 171.000 | 1 | DragonWave A-ANT-18G-2-C | |
| 171.000 | 171.000 | 1 | Side Arms | |
| 160.000 | 160.000 | 1 | Flat Platform w/ Handrails | |
| 160.000 | 160.000 | 9 | CCI HPA-65R-BUU-H6 | |
| 160.000 | 160.000 | 3 | Powerwave 7770.00 | |
| 160.000 | 160.000 | 3 | Ericsson RRUS-32 | |
| 160.000 | 160.000 | 3 | Ericsson RRUS E2 B29 | |
| 160.000 | 160.000 | 6 | Ericsson RRUS-12 B2 | |
| 160.000 | 160.000 | 6 | Ericsson RRUS 11 (Band 7) | |
| 160.000 | 160.000 | 6 | Ericsson RRUS A2 Module | |
| 160.000 | 160.000 | 3 | CCI DTMABP7819VG12A | |
| 160.000 | 160.000 | 3 | Raycap DC6-48-60-18-8F | |
| 160.000 | 160.000 | 6 | 14" x 9" TTA | |
| 160.000 | 160.000 | 3 | Powerwave 7020 | |
| 148.000 | 148.000 | 3 | Ericsson AIR 21, 1.3M, B4A B2P | |
| 148.000 | 148.000 | 3 | Ericsson AIR 21, 1.3 M, B2A B4 | |
| 148.000 | 148.000 | 3 | Ericsson KRY 112 144/1 | |
| 148.000 | 148.000 | 3 | T-Arm w/ Working Platform | |
| 135.000 | 138.000 | 3 | Alcatel-Lucent RRH2x40 (700) | |
| 135.000 | 138.000 | 1 | RFS DB-T1-6Z-8AB-0Z | |
| 135.000 | 138.000 | 3 | Alcatel-Lucent RRH2x40-AWS | |
| 135.000 | 138.000 | 3 | Antel BXA-171063-8BF-EDIN-X | |
| 135.000 | 138.000 | 3 | Antel BXA-80063-6BF-EDIN-X | |
| 135.000 | 138.000 | 6 | RFS FD9R6004/2C-3L | |
| 135.000 | 138.000 | 3 | Antel BXA-70063-6CF-EDIN-X | |
| 135.000 | 138.000 | 3 | Antel BXA-171063-12BF-EDIN | |
| 135.000 | 135.000 | 1 | Round Low Profile Platform | |
| 128.000 | 128.000 | 3 | RFS APXV18-206517S-C | |
| 116.000 | 118.000 | 3 | RFS APXV9TM14-ALU-I20 | |
| 116.000 | 116.000 | 3 | Alcatel-Lucent TD-RRH8x20-25 | |
| 116.000 | 118.000 | 3 | RFS APXVSP18-C-A20 | |
| 116.000 | 116.000 | 1 | Flat Low Profile Platform | |
| 116.000 | 116.000 | 3 | Alcatel-Lucent 1900 MHz 4x45 | |
| 116.000 | 116.000 | 3 | Alcatel-Lucent 800 MHz RRH | |
| 20.000 | 20.000 | 1 | Standoff | |
| 20.000 | 20.000 | 1 | PCTEL GPS-TMG-HR-26N | |






| Linear Appurtenance | | | |
|---------------------|--------|-------------------|-----------------|
| Elev (ft) | | Description | Exposed To Wind |
| From | To | | |
| 0.000 | 20.000 | 1/2" Coax | Yes |
| 0.000 | 116.0 | 1 1/4" Hybriflex | Yes |
| 0.000 | 116.0 | 1 1/4" Hybriflex | Yes |
| 0.000 | 128.0 | 1 5/8" Coax | Yes |
| 0.000 | 135.0 | 1 5/8" Coax | No |
| 0.000 | 135.0 | 1 5/8" Coax | Yes |
| 0.000 | 135.0 | 1 5/8" Hybriflex | No |
| 0.000 | 148.0 | 1 1/4" Hybriflex | No |
| 0.000 | 148.0 | 1 5/8" Coax | No |
| 0.000 | 148.0 | 1 5/8" Coax | Yes |
| 0.000 | 160.0 | 0.39" Fiber Trunk | No |
| 0.000 | 160.0 | 0.78" 8 AWG 6 | No |
| 0.000 | 160.0 | 1 5/8" Coax | No |
| 0.000 | 160.0 | 3" Conduit | No |
| 0.000 | 171.0 | 1/2" Coax | Yes |
| 0.000 | 171.0 | 2" Conduit | Yes |
| 0.000 | 171.0 | 5/16" Coax | No |
| 0.000 | 178.5 | 1 5/8" Coax | No |

| Load Cases | |
|----------------------|-------------------------------------|
| 1.2D + 1.6W | 110.00 mph with No Ice |
| 0.9D + 1.6W | 110.00 mph with No Ice (Reduced DL) |
| 1.2D + 1.0Di + 1.0Wi | 50.00 mph with 0.75 in Radial Ice |
| 1.2D + 1.0E | Dead Load with Seismic |
| 0.9D + 1.0E | Dead Load with Seismic (Reduced DL) |
| 1.0D + 1.0W | 60.00 mph Serviceability |


| Reactions | | | |
|----------------------|-----------------|-------------|-------------|
| Load Case | Moment (kip-ft) | Shear (kip) | Axial (kip) |
| 1.2D + 1.6W | 6514.47 | 53.48 | 75.62 |
| 0.9D + 1.6W | 6251.94 | 50.58 | 56.71 |
| 1.2D + 1.0Di + 1.0Wi | 1306.37 | 10.66 | 121.57 |
| 1.2D + 1.0E | 440.34 | 3.42 | 75.69 |
| 0.9D + 1.0E | 436.30 | 3.41 | 56.77 |
| 1.0D + 1.0W | 1166.70 | 9.41 | 63.07 |

| Dish Deflections | | | |
|------------------|------------------|-----------------|----------------|
| Load Case | Attach Elev (ft) | Deflection (in) | Rotation (deg) |
| 1.0D + 1.0W | 171.00 | 16.900 | 0.862 |
| 1.0D + 1.0W | 171.00 | 16.900 | 0.862 |



Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)



© 2007 - 2014 by ATC IP LLC. All rights reserved.

Shaft Section Properties

| Sect Info | Length (ft) | Thick (in) | Fy (ksi) | Joint Type | Joint Len (in) | Weight (lb) | Bottom | | | | | | Top | | | | | | | |
|--------------|-------------|------------|----------|------------|----------------|-------------|----------|-----------|-------------|-----------|-----------|-----------|----------|-----------|-------------|-----------|-----------|-----------|---------------|--|
| | | | | | | | Dia (in) | Elev (ft) | Area (sqin) | Ix (in^4) | W/t Ratio | D/t Ratio | Dia (in) | Elev (ft) | Area (sqin) | Ix (in^4) | W/t Ratio | D/t Ratio | Taper (in/ft) | |
| 1-18 | 53.000 | 0.4375 | 65 | | 0.00 | 16,253 | 72.00 | 0.00 | 99.37 | 64295.3 | 27.61 | 164.57 | 58.67 | 53.00 | 80.87 | 34653.6 | 22.24 | 134.12 | 0.251401 | |
| 2-18 | 53.000 | 0.3750 | 65 | Slip | 96.00 | 11,677 | 61.43 | 45.00 | 72.68 | 34236.3 | 27.48 | 163.83 | 48.11 | 98.00 | 56.82 | 16359.1 | 21.21 | 128.30 | 0.251401 | |
| 3-18 | 53.000 | 0.3125 | 65 | Slip | 79.00 | 7,766 | 50.39 | 91.42 | 49.67 | 15739.6 | 27.02 | 161.26 | 37.06 | 144.42 | 36.46 | 6222.7 | 19.51 | 118.62 | 0.251401 | |
| 4-18 | 39.167 | 0.2500 | 65 | Slip | 61.00 | 3,561 | 38.84 | 139.33 | 30.63 | 5764.1 | 25.99 | 155.39 | 29.00 | 178.50 | 22.81 | 2382.3 | 19.04 | 116.00 | 0.251401 | |
| Shaft Weight | | | | | | 39,257 | | | | | | | | | | | | | | |

Discrete Appurtenance Properties


| Attach Elev (ft) | Description | Qty | No Ice | | | Ice | | | Distance From Face (ft) | Vert Ecc (ft) |
|------------------|------------------------------|-----|-------------|-----------|--------------------|-------------|-----------|--------------------|-------------------------|---------------|
| | | | Weight (lb) | EPAA (sf) | Orientation Factor | Weight (lb) | EPAA (sf) | Orientation Factor | | |
| 178.50 | 48" x 12" Panel | 9 | 30.00 | 5.070 | 0.78 | 166.17 | 6.070 | 0.78 | 0.000 | 2.500 |
| 178.50 | 72" x 12" Panel | 3 | 45.00 | 8.130 | 0.79 | 240.70 | 9.454 | 0.79 | 0.000 | 2.500 |
| 178.50 | Flat Low Profile Platform | 1 | 1500.00 | 26.100 | 1.00 | 2,160.61 | 45.567 | 1.00 | 0.000 | 0.000 |
| 171.00 | Argus LLPX310R | 3 | 28.60 | 4.290 | 0.73 | 138.21 | 5.202 | 0.73 | 0.000 | 0.000 |
| 171.00 | DragonWave A-ANT-11G-2-C | 1 | 27.10 | 4.690 | 1.00 | 126.41 | 5.984 | 1.00 | 0.000 | 0.000 |
| 171.00 | DragonWave A-ANT-18G-2-C | 1 | 27.00 | 4.690 | 1.00 | 125.71 | 5.984 | 1.00 | 0.000 | 0.000 |
| 171.00 | DragonWave Horizon | 2 | 10.60 | 0.430 | 0.33 | 41.42 | 0.666 | 0.33 | 0.000 | 0.000 |
| 171.00 | NextNet BTS-2500 | 3 | 35.00 | 1.820 | 0.50 | 93.10 | 2.371 | 0.50 | 0.000 | 0.000 |
| 171.00 | Side Arms | 1 | 560.00 | 8.500 | 1.00 | 1,035.30 | 15.714 | 1.00 | 0.000 | 0.000 |
| 160.00 | 14" x 9" TTA | 6 | 10.00 | 1.050 | 0.33 | 47.02 | 1.503 | 0.33 | 0.000 | 0.000 |
| 160.00 | CCI DTMABP7819VG12A | 3 | 19.20 | 1.370 | 0.50 | 63.62 | 1.869 | 0.50 | 0.000 | 0.000 |
| 160.00 | CCI HPA-65R-BUU-H6 | 9 | 51.00 | 9.660 | 0.83 | 300.98 | 11.036 | 0.83 | 0.000 | 0.000 |
| 160.00 | Ericsson RRUS 11 (Band 7) | 6 | 50.70 | 2.790 | 0.67 | 137.81 | 3.474 | 0.67 | 0.000 | 0.000 |
| 160.00 | Ericsson RRUS A2 Module | 6 | 22.00 | 2.060 | 0.67 | 77.40 | 2.665 | 0.67 | 0.000 | 0.000 |
| 160.00 | Ericsson RRUS E2 B29 | 3 | 60.00 | 3.150 | 0.67 | 156.14 | 3.869 | 0.67 | 0.000 | 0.000 |
| 160.00 | Ericsson RRUS-12 B2 | 6 | 58.00 | 3.150 | 0.67 | 154.14 | 3.869 | 0.67 | 0.000 | 0.000 |
| 160.00 | Ericsson RRUS-32 | 3 | 77.00 | 3.310 | 0.67 | 191.42 | 4.109 | 0.67 | 0.000 | 0.000 |
| 160.00 | Flat Platform w/ Handrails | 1 | 2000.00 | 42.400 | 1.00 | 3,433.30 | 63.551 | 1.00 | 0.000 | 0.000 |
| 160.00 | Powerwave 7020 | 3 | 2.20 | 0.400 | 0.33 | 18.07 | 0.624 | 0.33 | 0.000 | 0.000 |
| 160.00 | Powerwave 7770.00 | 3 | 35.00 | 5.510 | 0.77 | 171.16 | 6.567 | 0.77 | 0.000 | 0.000 |
| 160.00 | Raycap DC6-48-60-18-8F | 3 | 20.00 | 1.110 | 1.00 | 101.17 | 2.526 | 1.00 | 0.000 | 0.000 |
| 148.00 | Ericsson AIR 21, 1.3 M, B2A | 3 | 83.00 | 6.050 | 0.86 | 251.77 | 7.147 | 0.86 | 0.000 | 0.000 |
| 148.00 | Ericsson AIR 21, 1.3M, B4A | 3 | 81.50 | 6.090 | 0.85 | 250.22 | 7.191 | 0.85 | 0.000 | 0.000 |
| 148.00 | Ericsson KRY 112 144/1 | 3 | 11.00 | 0.410 | 0.50 | 27.36 | 0.634 | 0.50 | 0.000 | 0.000 |
| 148.00 | T-Arm w/ Working Platform | 3 | 250.00 | 12.900 | 0.67 | 459.14 | 21.084 | 0.67 | 0.000 | 0.000 |
| 135.00 | Alcatel-Lucent RRH2x40 (700) | 3 | 50.00 | 2.120 | 0.67 | 135.98 | 2.736 | 0.67 | 0.000 | 3.000 |
| 135.00 | Alcatel-Lucent RRH2x40-AWS | 3 | 44.00 | 2.160 | 0.67 | 116.56 | 2.797 | 0.67 | 0.000 | 3.000 |
| 135.00 | Antel BXA-171063-12BF-EDIN | 3 | 15.00 | 4.730 | 0.88 | 132.75 | 5.942 | 0.88 | 0.000 | 3.000 |
| 135.00 | Antel BXA-171063-8BF-EDIN-X | 3 | 10.50 | 2.940 | 0.87 | 92.67 | 3.797 | 0.87 | 0.000 | 3.000 |
| 135.00 | Antel BXA-70063-6CF-EDIN-X | 3 | 17.00 | 7.570 | 0.77 | 188.79 | 8.805 | 0.77 | 0.000 | 3.000 |
| 135.00 | Antel BXA-80063-6BF-EDIN-X | 3 | 19.20 | 7.260 | 0.78 | 162.17 | 9.898 | 0.78 | 0.000 | 3.000 |
| 135.00 | RFS DB-T1-6Z-8AB-0Z | 1 | 44.00 | 4.800 | 1.00 | 185.96 | 5.664 | 1.00 | 0.000 | 3.000 |
| 135.00 | RFS FD9R6004/2C-3L | 6 | 2.60 | 0.370 | 0.50 | 15.50 | 0.576 | 0.50 | 0.000 | 3.000 |
| 135.00 | Round Low Profile Platform | 1 | 1500.00 | 21.700 | 1.00 | 2,142.42 | 40.737 | 1.00 | 0.000 | 0.000 |
| 128.00 | RFS APXV18-206517S-C | 3 | 26.40 | 5.170 | 0.80 | 141.66 | 6.388 | 0.80 | 0.000 | 0.000 |
| 116.00 | Alcatel-Lucent 1900 MHz | 3 | 60.00 | 2.320 | 0.67 | 152.23 | 2.974 | 0.67 | 0.000 | 0.000 |
| 116.00 | Alcatel-Lucent 800 MHz RRH | 3 | 53.00 | 2.130 | 0.67 | 137.70 | 2.729 | 0.67 | 0.000 | 0.000 |
| 116.00 | Alcatel-Lucent TD-RRH8x20- | 3 | 70.00 | 4.050 | 0.67 | 160.16 | 5.709 | 0.67 | 0.000 | 0.000 |
| 116.00 | Flat Low Profile Platform | 1 | 1500.00 | 26.100 | 1.00 | 2,132.74 | 44.746 | 1.00 | 0.000 | 0.000 |
| 116.00 | RFS APXV9TM14-ALU-I20 | 3 | 55.10 | 6.340 | 0.78 | 195.16 | 8.467 | 0.78 | 0.000 | 2.000 |
| 116.00 | RFS APXVSP18-C-A20 | 3 | 57.00 | 8.020 | 0.83 | 250.66 | 9.280 | 0.83 | 0.000 | 2.000 |
| 20.00 | PCTEL GPS-TMG-HR-26N | 1 | 0.60 | 0.090 | 1.00 | 8.27 | 0.231 | 1.00 | 0.000 | 0.000 |
| 20.00 | Standoff | 1 | 40.00 | 1.630 | 1.00 | 78.65 | 2.559 | 1.00 | 0.000 | 0.000 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)

6/13/2014 11:15:45 AM

Page: 2



© 2007 - 2014 by ATC IP LLC. All rights reserved.

Totals 135 12482.80

30,393.52


Number of Loadings : 43

Linear Appurtenance Properties

| Elev From (ft) | Elev To (ft) | Description | Exposed Width (in) | Exposed To Wind |
|----------------|--------------|--------------------------|--------------------|-----------------|
| 0.00 | 178.50 | (12) 1 5/8" Coax | 0.00 | N |
| 0.00 | 171.00 | (2) 1/2" Coax | 0.00 | Y |
| 0.00 | 171.00 | (2) 2" Conduit | 2.38 | Y |
| 0.00 | 171.00 | (6) 5/16" Coax | 0.00 | N |
| 0.00 | 160.00 | (1) 0.39" Fiber Trunk | 0.00 | N |
| 0.00 | 160.00 | (6) 0.78" 8 AWG6 | 0.00 | N |
| 0.00 | 160.00 | (12) 1 5/8" Coax | 0.00 | N |
| 0.00 | 160.00 | (1) 3" Conduit | 0.00 | N |
| 0.00 | 148.00 | (1) 1 1/4" Hybriflex Cab | 0.00 | N |
| 0.00 | 148.00 | (6) 1 5/8" Coax | 0.00 | N |
| 0.00 | 148.00 | (6) 1 5/8" Coax | 1.98 | Y |
| 0.00 | 135.00 | (15) 1 5/8" Coax | 0.00 | N |
| 0.00 | 135.00 | (3) 1 5/8" Coax | 0.00 | Y |
| 0.00 | 135.00 | (1) 1 5/8" Hybriflex | 0.00 | N |
| 0.00 | 128.00 | (6) 1 5/8" Coax | 1.98 | Y |
| 0.00 | 116.00 | (1) 1 1/4" Hybriflex | 1.54 | Y |
| 0.00 | 116.00 | (3) 1 1/4" Hybriflex | 1.55 | Y |
| 0.00 | 20.00 | (1) 1/2" Coax | 0.00 | Y |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)




© 2007 - 2014 by ATC IP LLC. All rights reserved.

Segment Properties (Max Len : 5 ft)

| Seg Top Elev (ft) | Description | Thick (in) | Flat Dia (in) | Area (in^2) | Ix (in^4) | W/t Ratio | D/t Ratio | Fy (ksi) | S (in3) | Weight (lb) |
|-------------------|-----------------|------------|---------------|-------------|-----------|-----------|-----------|----------|---------|-------------|
| 0.00 | | 0.4375 | 72.000 | 99.370 | 64,295.3 | 27.61 | 164.57 | 68.9 | 1758. | 0.0 |
| 5.00 | | 0.4375 | 70.743 | 97.624 | 60,966.4 | 27.10 | 161.70 | 69.5 | 1697. | 1,675.8 |
| 10.00 | | 0.4375 | 69.486 | 95.879 | 57,754.4 | 26.59 | 158.83 | 70.1 | 1637. | 1,646.1 |
| 15.00 | | 0.4375 | 68.229 | 94.134 | 54,657.3 | 26.09 | 155.95 | 70.7 | 1577. | 1,616.4 |
| 20.00 | | 0.4375 | 66.972 | 92.388 | 51,672.9 | 25.58 | 153.08 | 71.3 | 1519. | 1,586.7 |
| 25.00 | | 0.4375 | 65.715 | 90.643 | 48,799.2 | 25.07 | 150.21 | 71.9 | 1462. | 1,557.0 |
| 30.00 | | 0.4375 | 64.458 | 88.897 | 46,034.0 | 24.57 | 147.33 | 72.5 | 1406. | 1,527.3 |
| 35.00 | | 0.4375 | 63.201 | 87.152 | 43,375.4 | 24.06 | 144.46 | 73.1 | 1351. | 1,497.6 |
| 40.00 | | 0.4375 | 61.944 | 85.406 | 40,821.1 | 23.55 | 141.59 | 73.7 | 1298. | 1,467.9 |
| 45.00 | Bot - Section 2 | 0.4375 | 60.687 | 83.661 | 38,369.1 | 23.05 | 138.71 | 74.3 | 1245. | 1,438.2 |
| 50.00 | | 0.4375 | 59.430 | 81.915 | 36,017.4 | 22.54 | 135.84 | 74.9 | 1193. | 2,632.3 |
| 53.00 | Top - Section 1 | 0.3750 | 59.426 | 70.283 | 30,963.7 | 26.53 | 158.47 | 70.2 | 1026. | 1,552.9 |
| 55.00 | | 0.3750 | 58.923 | 69.684 | 30,179.4 | 26.30 | 157.13 | 70.5 | 1008. | 476.3 |
| 60.00 | | 0.3750 | 57.666 | 68.188 | 28,277.0 | 25.70 | 153.78 | 71.2 | 965.8 | 1,172.9 |
| 65.00 | | 0.3750 | 56.409 | 66.692 | 26,456.3 | 25.11 | 150.42 | 71.9 | 923.8 | 1,147.4 |
| 70.00 | | 0.3750 | 55.152 | 65.196 | 24,715.5 | 24.52 | 147.07 | 72.6 | 882.7 | 1,122.0 |
| 75.00 | | 0.3750 | 53.895 | 63.700 | 23,052.8 | 23.93 | 143.72 | 73.3 | 842.5 | 1,096.5 |
| 80.00 | | 0.3750 | 52.638 | 62.204 | 21,466.3 | 23.34 | 140.37 | 73.9 | 803.2 | 1,071.1 |
| 85.00 | | 0.3750 | 51.381 | 60.708 | 19,954.4 | 22.75 | 137.02 | 74.6 | 764.9 | 1,045.6 |
| 90.00 | | 0.3750 | 50.124 | 59.212 | 18,515.1 | 22.16 | 133.66 | 75.3 | 727.6 | 1,020.1 |
| 91.42 | Bot - Section 3 | 0.3750 | 49.768 | 58.788 | 18,120.3 | 21.99 | 132.71 | 75.5 | 717.1 | 284.4 |
| 95.00 | | 0.3750 | 48.867 | 57.715 | 17,146.8 | 21.57 | 130.31 | 76.0 | 691.1 | 1,310.5 |
| 98.00 | Top - Section 2 | 0.3125 | 48.738 | 48.030 | 14,230.2 | 26.09 | 155.96 | 70.7 | 575.1 | 1,078.7 |
| 100.0 | | 0.3125 | 48.235 | 47.531 | 13,791.5 | 25.81 | 154.35 | 71.0 | 563.2 | 325.2 |
| 105.0 | | 0.3125 | 46.978 | 46.285 | 12,734.5 | 25.10 | 150.33 | 71.9 | 533.9 | 798.1 |
| 110.0 | | 0.3125 | 45.721 | 45.038 | 11,732.9 | 24.39 | 146.31 | 72.7 | 505.4 | 776.9 |
| 115.0 | | 0.3125 | 44.464 | 43.791 | 10,785.2 | 23.68 | 142.28 | 73.6 | 477.8 | 755.7 |
| 116.0 | | 0.3125 | 44.213 | 43.542 | 10,602.0 | 23.54 | 141.48 | 73.7 | 472.3 | 148.6 |
| 120.0 | | 0.3125 | 43.207 | 42.544 | 9,890.0 | 22.97 | 138.26 | 74.4 | 450.8 | 585.9 |
| 125.0 | | 0.3125 | 41.950 | 41.298 | 9,045.8 | 22.26 | 134.24 | 75.2 | 424.7 | 713.2 |
| 128.0 | | 0.3125 | 41.196 | 40.550 | 8,563.1 | 21.83 | 131.83 | 75.7 | 409.4 | 417.8 |
| 130.0 | | 0.3125 | 40.693 | 40.051 | 8,251.0 | 21.55 | 130.22 | 76.1 | 399.4 | 274.3 |
| 135.0 | | 0.3125 | 39.436 | 38.804 | 7,504.2 | 20.84 | 126.19 | 76.9 | 374.8 | 670.8 |
| 139.3 | Bot - Section 4 | 0.3125 | 38.347 | 37.724 | 6,894.6 | 20.23 | 122.71 | 77.6 | 354.1 | 564.2 |
| 140.0 | | 0.3125 | 38.179 | 37.557 | 6,803.9 | 20.13 | 122.17 | 77.7 | 351.0 | 154.7 |
| 144.4 | Top - Section 3 | 0.2500 | 37.569 | 29.611 | 5,210.3 | 25.09 | 150.27 | 71.9 | 273.2 | 1,007.8 |
| 145.0 | | 0.2500 | 37.422 | 29.495 | 5,149.1 | 24.98 | 149.69 | 72.0 | 271.0 | 58.7 |
| 148.0 | | 0.2500 | 36.668 | 28.896 | 4,842.0 | 24.45 | 146.67 | 72.6 | 260.1 | 298.0 |
| 150.0 | | 0.2500 | 36.165 | 28.497 | 4,644.2 | 24.10 | 144.66 | 73.1 | 252.9 | 195.3 |
| 155.0 | | 0.2500 | 34.908 | 27.500 | 4,173.4 | 23.21 | 139.63 | 74.1 | 235.5 | 476.4 |
| 160.0 | | 0.2500 | 33.651 | 26.503 | 3,735.6 | 22.32 | 134.60 | 75.1 | 218.6 | 459.4 |
| 165.0 | | 0.2500 | 32.394 | 25.505 | 3,329.5 | 21.44 | 129.58 | 76.2 | 202.4 | 442.4 |
| 170.0 | | 0.2500 | 31.137 | 24.508 | 2,954.0 | 20.55 | 124.55 | 77.2 | 186.9 | 425.5 |
| 171.0 | | 0.2500 | 30.885 | 24.308 | 2,882.4 | 20.37 | 123.54 | 77.4 | 183.8 | 83.1 |
| 175.0 | | 0.2500 | 29.880 | 23.510 | 2,607.8 | 19.66 | 119.52 | 78.3 | 171.9 | 325.4 |
| 178.5 | | 0.2500 | 29.000 | 22.812 | 2,382.3 | 19.04 | 116.00 | 79.0 | 161.8 | 275.8 |
| | | | | | | | | | | 39,257.1 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)



6/13/2014 11:15:45 AM
 Page : 4

© 2007 - 2014 by ATC IP LLC. All rights reserved.

Load Case: 1.2D + 1.6W 110.00 mph with No Ice 23 Iterations

Gust Response Factor : 1.10 Wind Importance Factor : 1.00

Dead Load Factor : 1.20

Wind Load Factor : 1.60


Shaft Segment Forces (Factored)

| Seg Top Elev (ft) | Description | Kzt | Kz | qz (psf) | qzGh (psf) | C (mph-ft) | Cf | Ice Thick (in) | Tributary (ft) | Ap (sf) | EPAs (sf) | Wind Force X (lb) | Dead Load Ice (lb) | Tot Dead Load (lb) |
|-------------------|-----------------|------|------|----------|------------|------------|-------|----------------|----------------|---------|-----------|-------------------|--------------------|--------------------|
| 0.00 | | 1.00 | 0.70 | 20.599 | 22.65 | 560.71 | 0.650 | 0.000 | 0.00 | 0.000 | 0.00 | 0.0 | 0.0 | 0.0 |
| 5.00 | | 1.00 | 0.70 | 20.599 | 22.65 | 550.92 | 0.709 | * 0.000 | 5.00 | 30.197 | 21.40 | 775.9 | 0.0 | 2,011.0 |
| 10.00 | | 1.00 | 0.70 | 20.599 | 22.65 | 541.13 | 0.713 | * 0.000 | 5.00 | 29.665 | 21.16 | 767.1 | 0.0 | 1,975.3 |
| 15.00 | | 1.00 | 0.70 | 20.599 | 22.65 | 531.34 | 0.718 | * 0.000 | 5.00 | 29.133 | 20.92 | 758.3 | 0.0 | 1,939.7 |
| 20.00 | Appertunance(s) | 1.00 | 0.70 | 20.599 | 22.65 | 521.55 | 0.723 | * 0.000 | 5.00 | 28.601 | 20.68 | 749.6 | 0.0 | 1,904.1 |
| 25.00 | | 1.00 | 0.70 | 20.599 | 22.65 | 511.76 | 0.728 | * 0.000 | 5.00 | 28.070 | 20.43 | 740.8 | 0.0 | 1,868.4 |
| 30.00 | | 1.00 | 0.70 | 20.616 | 22.67 | 502.19 | 0.733 | * 0.000 | 5.00 | 27.538 | 20.19 | 732.6 | 0.0 | 1,832.8 |
| 35.00 | | 1.00 | 0.73 | 21.545 | 23.69 | 503.36 | 0.739 | * 0.000 | 5.00 | 27.006 | 19.95 | 756.5 | 0.0 | 1,797.2 |
| 40.00 | | 1.00 | 0.76 | 22.383 | 24.62 | 502.85 | 0.744 | * 0.000 | 5.00 | 26.474 | 19.71 | 776.3 | 0.0 | 1,761.5 |
| 45.00 | Bot - Section 2 | 1.00 | 0.78 | 23.149 | 25.46 | 501.00 | 0.750 | * 0.000 | 5.00 | 25.942 | 19.47 | 793.1 | 0.0 | 1,725.9 |
| 50.00 | | 1.00 | 0.81 | 23.856 | 26.24 | 498.07 | 0.757 | * 0.000 | 5.00 | 25.728 | 19.46 | 817.2 | 0.0 | 3,158.8 |
| 53.00 | Top - Section 1 | 1.00 | 0.82 | 24.257 | 26.68 | 495.86 | 0.762 | * 0.000 | 3.00 | 15.181 | 11.56 | 493.6 | 0.0 | 1,863.5 |
| 55.00 | | 1.00 | 0.83 | 24.515 | 26.96 | 500.59 | 0.761 | * 0.000 | 2.00 | 10.015 | 7.62 | 328.8 | 0.0 | 571.5 |
| 60.00 | | 1.00 | 0.85 | 25.132 | 27.64 | 496.03 | 0.766 | * 0.000 | 5.00 | 24.664 | 18.88 | 835.3 | 0.0 | 1,407.4 |
| 65.00 | | 1.00 | 0.87 | 25.713 | 28.28 | 490.80 | 0.772 | * 0.000 | 5.00 | 24.132 | 18.64 | 843.6 | 0.0 | 1,376.9 |
| 70.00 | | 1.00 | 0.89 | 26.263 | 28.89 | 484.97 | 0.780 | * 0.000 | 5.00 | 23.600 | 18.40 | 850.5 | 0.0 | 1,346.4 |
| 75.00 | | 1.00 | 0.91 | 26.786 | 29.46 | 478.61 | 0.787 | * 0.000 | 5.00 | 23.069 | 18.16 | 856.0 | 0.0 | 1,315.8 |
| 80.00 | | 1.00 | 0.92 | 27.285 | 30.01 | 471.78 | 0.795 | * 0.000 | 5.00 | 22.537 | 17.92 | 860.3 | 0.0 | 1,285.3 |
| 85.00 | | 1.00 | 0.94 | 27.761 | 30.53 | 464.52 | 0.803 | * 0.000 | 5.00 | 22.005 | 17.67 | 863.6 | 0.0 | 1,254.7 |
| 90.00 | | 1.00 | 0.95 | 28.219 | 31.04 | 456.87 | 0.812 | * 0.000 | 5.00 | 21.473 | 17.43 | 865.8 | 0.0 | 1,224.2 |
| 91.42 | Bot - Section 3 | 1.00 | 0.96 | 28.345 | 31.17 | 454.64 | 0.818 | * 0.000 | 1.42 | 5.987 | 4.90 | 244.2 | 0.0 | 341.3 |
| 95.00 | | 1.00 | 0.97 | 28.658 | 31.52 | 448.87 | 0.822 | * 0.000 | 3.58 | 15.143 | 12.45 | 628.0 | 0.0 | 1,572.6 |
| 98.00 | Top - Section 2 | 1.00 | 0.98 | 28.913 | 31.80 | 443.91 | 0.828 | * 0.000 | 3.00 | 12.468 | 10.33 | 525.6 | 0.0 | 1,294.5 |
| 100.0 | | 1.00 | 0.98 | 29.081 | 31.98 | 446.32 | 0.828 | * 0.000 | 2.00 | 8.206 | 6.80 | 348.0 | 0.0 | 390.2 |
| 105.0 | | 1.00 | 1.00 | 29.489 | 32.43 | 437.73 | 0.835 | * 0.000 | 5.00 | 20.142 | 16.83 | 873.3 | 0.0 | 957.7 |
| 110.0 | | 1.00 | 1.01 | 29.884 | 32.87 | 428.86 | 1.200 | * 0.000 | 5.00 | 19.610 | 23.53 | 1,237.7 | 0.0 | 932.3 |
| 115.0 | | 1.00 | 1.02 | 30.266 | 33.29 | 419.72 | 1.200 | * 0.000 | 5.00 | 19.078 | 22.89 | 1,219.5 | 0.0 | 906.8 |
| 116.0 | Appertunance(s) | 1.00 | 1.03 | 30.341 | 33.37 | 417.87 | 1.200 | * 0.000 | 1.00 | 3.752 | 4.50 | 240.4 | 0.0 | 178.3 |
| 120.0 | | 1.00 | 1.04 | 30.636 | 33.69 | 410.35 | 0.734 | * 0.000 | 4.00 | 14.795 | 10.85 | 585.2 | 0.0 | 703.0 |
| 125.0 | | 1.00 | 1.05 | 30.995 | 34.09 | 400.74 | 0.741 | * 0.000 | 5.00 | 18.015 | 13.35 | 728.2 | 0.0 | 855.9 |
| 128.0 | Appertunance(s) | 1.00 | 1.06 | 31.206 | 34.32 | 394.87 | 0.748 | * 0.000 | 3.00 | 10.554 | 7.89 | 433.5 | 0.0 | 501.3 |
| 130.0 | | 1.00 | 1.06 | 31.345 | 34.47 | 390.91 | 0.659 | * 0.000 | 2.00 | 6.929 | 4.57 | 252.1 | 0.0 | 329.1 |
| 135.0 | Appertunance(s) | 1.00 | 1.07 | 31.684 | 34.85 | 380.89 | 0.664 | * 0.000 | 5.00 | 16.951 | 11.26 | 627.6 | 0.0 | 805.0 |
| 139.3 | Bot - Section 4 | 1.00 | 1.08 | 31.972 | 35.16 | 372.04 | 0.670 | * 0.000 | 4.33 | 14.261 | 9.56 | 537.9 | 0.0 | 677.1 |
| 140.0 | | 1.00 | 1.08 | 32.015 | 35.21 | 370.67 | 0.674 | * 0.000 | 0.67 | 2.187 | 1.47 | 83.0 | 0.0 | 185.7 |
| 144.4 | Top - Section 3 | 1.00 | 1.09 | 32.301 | 35.53 | 361.49 | 0.678 | * 0.000 | 4.42 | 14.248 | 9.65 | 548.8 | 0.0 | 1,209.4 |
| 145.0 | | 1.00 | 1.09 | 32.338 | 35.57 | 365.14 | 0.678 | * 0.000 | 0.58 | 1.851 | 1.26 | 71.5 | 0.0 | 70.4 |
| 148.0 | Appertunance(s) | 1.00 | 1.10 | 32.528 | 35.78 | 358.83 | 0.681 | * 0.000 | 3.00 | 9.404 | 6.40 | 366.6 | 0.0 | 357.6 |
| 150.0 | | 1.00 | 1.11 | 32.653 | 35.91 | 354.59 | 0.650 | 0.000 | 2.00 | 6.163 | 4.01 | 230.2 | 0.0 | 234.4 |
| 155.0 | | 1.00 | 1.12 | 32.960 | 36.25 | 343.87 | 0.650 | 0.000 | 5.00 | 15.035 | 9.77 | 566.9 | 0.0 | 571.6 |
| 160.0 | Appertunance(s) | 1.00 | 1.13 | 33.260 | 36.58 | 333.00 | 0.650 | 0.000 | 5.00 | 14.503 | 9.43 | 551.9 | 0.0 | 551.3 |
| 165.0 | | 1.00 | 1.14 | 33.554 | 36.91 | 321.97 | 0.650 | 0.000 | 5.00 | 13.972 | 9.08 | 536.3 | 0.0 | 530.9 |
| 170.0 | | 1.00 | 1.15 | 33.842 | 37.22 | 310.80 | 0.650 | 0.000 | 5.00 | 13.440 | 8.74 | 520.3 | 0.0 | 510.6 |
| 171.0 | Appertunance(s) | 1.00 | 1.15 | 33.898 | 37.28 | 308.55 | 0.650 | 0.000 | 1.00 | 2.624 | 1.71 | 101.8 | 0.0 | 99.7 |
| 175.0 | | 1.00 | 1.16 | 34.123 | 37.53 | 299.49 | 0.650 | 0.000 | 4.00 | 10.284 | 6.68 | 401.4 | 0.0 | 390.5 |
| 178.5 | Appertunance(s) | 1.00 | 1.16 | 34.317 | 37.74 | 291.49 | 0.650 | 0.000 | 3.50 | 8.719 | 5.67 | 342.3 | 0.0 | 331.0 |
| | | | | | | | | Totals: | 178.50 | | | 27,267.3 | 0.0 | 47,108.5 |

* = Cf Adjusted By Linear Load Ra Effect

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)



© 2007 - 2014 by ATC IP LLC. All rights reserved.

Load Case: 1.2D + 1.6W 110.00 mph with No Ice 23 Iterations

Gust Response Factor : 1.10 Wind Importance Factor : 1.00

Dead Load Factor : 1.20


Wind Load Factor : 1.60

Discrete Appurtenance Segment Forces (Factored)

| Elev (ft) | Description | Qty | qz (psf) | qzGh (psf) | Orientation Factor | Ka | Total EPAa (sf) | Horiz Ecc (ft) | Vert Ecc (ft) | Wind FX (lb) | Mom Y (lb-ft) | Mom Z (lb-ft) | Dead Load (lb) |
|-----------|----------------------|-----|----------|------------|--------------------|------|-----------------|----------------|---------------|------------------|---------------|---------------|------------------|
| 20.00 | PCTEL GPS-TMG-HR- | 1 | 20.599 | 22.659 | 1.00 | 1.00 | 0.09 | 0.000 | 0.000 | 3.26 | 0.00 | 0.00 | 0.72 |
| 20.00 | Standoff | 1 | 20.599 | 22.659 | 1.00 | 1.00 | 1.63 | 0.000 | 0.000 | 59.09 | 0.00 | 0.00 | 48.00 |
| 116.0 | Alcatel-Lucent 800 M | 3 | 30.341 | 33.375 | 0.67 | 0.80 | 3.43 | 0.000 | 0.000 | 182.90 | 0.00 | 0.00 | 190.80 |
| 116.0 | Alcatel-Lucent 1900 | 3 | 30.341 | 33.375 | 0.67 | 0.80 | 3.73 | 0.000 | 0.000 | 199.21 | 0.00 | 0.00 | 216.00 |
| 116.0 | Flat Low Profile Pla | 1 | 30.341 | 33.375 | 1.00 | 1.00 | 26.10 | 0.000 | 0.000 | 1,393.73 | 0.00 | 0.00 | 1,800.00 |
| 116.0 | RFS APXVSP18-C- | 3 | 30.489 | 33.538 | 0.83 | 0.80 | 15.98 | 0.000 | 2.000 | 857.28 | 0.00 | 1,714.56 | 205.20 |
| 116.0 | Alcatel-Lucent TD-RR | 3 | 30.341 | 33.375 | 0.67 | 0.80 | 6.51 | 0.000 | 0.000 | 347.76 | 0.00 | 0.00 | 252.00 |
| 116.0 | RFS APXV9TM14-ALU- | 3 | 30.489 | 33.538 | 0.78 | 0.80 | 11.87 | 0.000 | 2.000 | 636.87 | 0.00 | 1,273.75 | 198.36 |
| 128.0 | RFS APXV18-206517S- | 3 | 31.206 | 34.327 | 0.80 | 1.00 | 12.41 | 0.000 | 0.000 | 681.48 | 0.00 | 0.00 | 95.04 |
| 135.0 | Round Low Profile PI | 1 | 31.684 | 34.853 | 1.00 | 1.00 | 21.70 | 0.000 | 0.000 | 1,210.09 | 0.00 | 0.00 | 1,800.00 |
| 135.0 | Antel BXA-171063-12B | 3 | 31.884 | 35.072 | 0.88 | 0.80 | 9.99 | 0.000 | 3.000 | 560.58 | 0.00 | 1,681.75 | 54.00 |
| 135.0 | Antel BXA-70063-6CF- | 3 | 31.884 | 35.072 | 0.77 | 0.80 | 13.99 | 0.000 | 3.000 | 785.03 | 0.00 | 2,355.08 | 61.20 |
| 135.0 | RFS FD9R6004/2C-3L | 6 | 31.884 | 35.072 | 0.50 | 0.80 | 0.89 | 0.000 | 3.000 | 49.83 | 0.00 | 149.49 | 18.72 |
| 135.0 | Antel BXA-80063-6BF- | 3 | 31.884 | 35.072 | 0.78 | 0.80 | 13.59 | 0.000 | 3.000 | 762.66 | 0.00 | 2,287.97 | 69.12 |
| 135.0 | Antel BXA-171063-8BF | 3 | 31.884 | 35.072 | 0.87 | 0.80 | 6.14 | 0.000 | 3.000 | 344.48 | 0.00 | 1,033.44 | 37.80 |
| 135.0 | Alcatel-Lucent RRH2x | 3 | 31.884 | 35.072 | 0.67 | 0.80 | 3.49 | 0.000 | 3.000 | 196.07 | 0.00 | 588.21 | 158.40 |
| 135.0 | RFS DB-T1-6Z-8AB-OZ | 1 | 31.884 | 35.072 | 1.00 | 0.80 | 3.84 | 0.000 | 3.000 | 215.48 | 0.00 | 646.45 | 52.80 |
| 135.0 | Alcatel-Lucent RRH2x | 3 | 31.884 | 35.072 | 0.67 | 0.80 | 3.41 | 0.000 | 3.000 | 191.30 | 0.00 | 573.89 | 180.00 |
| 148.0 | T-Arm w/ Working Pla | 3 | 32.528 | 35.780 | 0.67 | 0.75 | 19.45 | 0.000 | 0.000 | 1,113.30 | 0.00 | 0.00 | 900.00 |
| 148.0 | Ericsson KRY 112 144 | 3 | 32.528 | 35.780 | 0.50 | 0.80 | 0.49 | 0.000 | 0.000 | 28.17 | 0.00 | 0.00 | 39.60 |
| 148.0 | Ericsson AIR 21, 1,3 | 3 | 32.528 | 35.780 | 0.86 | 0.80 | 12.49 | 0.000 | 0.000 | 714.88 | 0.00 | 0.00 | 298.80 |
| 148.0 | Ericsson AIR 21, 1,3 | 3 | 32.528 | 35.780 | 0.85 | 0.80 | 12.42 | 0.000 | 0.000 | 711.24 | 0.00 | 0.00 | 293.40 |
| 160.0 | Powerwave 7020 | 3 | 33.260 | 36.586 | 0.33 | 0.75 | 0.30 | 0.000 | 0.000 | 17.39 | 0.00 | 0.00 | 7.92 |
| 160.0 | 14" x 9" TTA | 6 | 33.260 | 36.586 | 0.33 | 0.75 | 1.56 | 0.000 | 0.000 | 91.28 | 0.00 | 0.00 | 72.00 |
| 160.0 | Raycap DC6-48-60-18- | 3 | 33.260 | 36.586 | 1.00 | 0.75 | 2.50 | 0.000 | 0.000 | 146.20 | 0.00 | 0.00 | 72.00 |
| 160.0 | CCI | 3 | 33.260 | 36.586 | 0.50 | 0.75 | 1.54 | 0.000 | 0.000 | 90.22 | 0.00 | 0.00 | 69.12 |
| 160.0 | Ericsson RRUS A2 | 6 | 33.260 | 36.586 | 0.67 | 0.75 | 6.21 | 0.000 | 0.000 | 363.58 | 0.00 | 0.00 | 158.40 |
| 160.0 | Ericsson RRUS 11 (Ba | 6 | 33.260 | 36.586 | 0.67 | 0.75 | 8.41 | 0.000 | 0.000 | 492.42 | 0.00 | 0.00 | 365.04 |
| 160.0 | Ericsson RRUS-12 B2 | 6 | 33.260 | 36.586 | 0.67 | 0.75 | 9.50 | 0.000 | 0.000 | 555.95 | 0.00 | 0.00 | 417.60 |
| 160.0 | Ericsson RRUS E2 B29 | 3 | 33.260 | 36.586 | 0.67 | 0.75 | 4.75 | 0.000 | 0.000 | 277.98 | 0.00 | 0.00 | 216.00 |
| 160.0 | Ericsson RRUS-32 | 3 | 33.260 | 36.586 | 0.67 | 0.75 | 4.99 | 0.000 | 0.000 | 292.10 | 0.00 | 0.00 | 277.20 |
| 160.0 | Powerwave 7770.00 | 3 | 33.260 | 36.586 | 0.77 | 0.75 | 9.55 | 0.000 | 0.000 | 558.81 | 0.00 | 0.00 | 126.00 |
| 160.0 | CCI HPA-65R-BUU-H6 | 9 | 33.260 | 36.586 | 0.83 | 0.75 | 54.12 | 0.000 | 0.000 | 3,168.10 | 0.00 | 0.00 | 550.80 |
| 160.0 | Flat Platform w/ Han | 1 | 33.260 | 36.586 | 1.00 | 1.00 | 42.40 | 0.000 | 0.000 | 2,482.02 | 0.00 | 0.00 | 2,400.00 |
| 171.0 | Side Arms | 1 | 33.898 | 37.288 | 1.00 | 1.00 | 8.50 | 0.000 | 0.000 | 507.12 | 0.00 | 0.00 | 672.00 |
| 171.0 | DragonWave A-ANT- | 1 | 33.898 | 37.288 | 1.00 | 0.80 | 3.75 | 0.000 | 0.000 | 223.85 | 0.00 | 0.00 | 32.40 |
| 171.0 | NextNet BTS-2500 | 3 | 33.898 | 37.288 | 0.50 | 0.80 | 2.18 | 0.000 | 0.000 | 130.30 | 0.00 | 0.00 | 126.00 |
| 171.0 | Argus LLPX310R | 3 | 33.898 | 37.288 | 0.73 | 0.80 | 7.52 | 0.000 | 0.000 | 448.42 | 0.00 | 0.00 | 102.96 |
| 171.0 | DragonWave Horizon | 2 | 33.898 | 37.288 | 0.33 | 0.80 | 0.23 | 0.000 | 0.000 | 13.55 | 0.00 | 0.00 | 25.44 |
| 171.0 | DragonWave A-ANT- | 1 | 33.898 | 37.288 | 1.00 | 0.80 | 3.75 | 0.000 | 0.000 | 223.85 | 0.00 | 0.00 | 32.52 |
| 178.5 | 72" x 12" Panel | 3 | 34.453 | 37.899 | 0.79 | 0.80 | 15.41 | 0.000 | 2.500 | 934.70 | 0.00 | 2,336.75 | 162.00 |
| 178.5 | 48" x 12" Panel | 9 | 34.453 | 37.899 | 0.78 | 0.80 | 28.47 | 0.000 | 2.500 | 1,726.54 | 0.00 | 4,316.36 | 324.00 |
| 178.5 | Flat Low Profile Pla | 1 | 34.317 | 37.748 | 1.00 | 1.00 | 26.10 | 0.000 | 0.000 | 1,576.37 | 0.00 | 0.00 | 1,800.00 |
| | | | | | | | | | | 25,565.39 | | | 14,979.36 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)



Load Case: 1.2D + 1.6W

110.00 mph with No Ice

23 Iterations

Gust Response Factor : 1.10
 Dead Load Factor : 1.20
 Wind Load Factor : 1.60


Wind Importance Factor : 1.00

Linear Appurtenance Segment Forces (Factored)

| Seg Top Elev (ft) | Description | Exposed To Wind | Length (ft) | Ca | Exposed Width (in) | Area (sqft) | CaAa (sqft) | qz (psf) | Ra | Cf Adjust Factor | FX (lb) | Dead Load (lb) |
|-------------------|----------------------|-----------------|-------------|-------|--------------------|-------------|-------------|----------|-------|------------------|---------|----------------|
| 5.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.130 | 1.090 | 0.00 | 1.80 |
| 5.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 20.599 | 0.130 | 1.090 | 0.00 | 43.80 |
| 5.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 20.599 | 0.130 | 1.090 | 0.00 | 29.52 |
| 5.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.130 | 1.090 | 0.00 | 14.76 |
| 5.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 20.599 | 0.130 | 1.090 | 0.00 | 29.52 |
| 5.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 20.599 | 0.130 | 1.090 | 0.00 | 6.00 |
| 5.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 20.599 | 0.130 | 1.090 | 0.00 | 18.00 |
| 5.00 | (1) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.130 | 1.090 | 0.00 | 0.90 |
| 10.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.132 | 1.097 | 0.00 | 1.80 |
| 10.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 20.599 | 0.132 | 1.097 | 0.00 | 43.80 |
| 10.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 20.599 | 0.132 | 1.097 | 0.00 | 29.52 |
| 10.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.132 | 1.097 | 0.00 | 14.76 |
| 10.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 20.599 | 0.132 | 1.097 | 0.00 | 29.52 |
| 10.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 20.599 | 0.132 | 1.097 | 0.00 | 6.00 |
| 10.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 20.599 | 0.132 | 1.097 | 0.00 | 18.00 |
| 10.00 | (1) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.132 | 1.097 | 0.00 | 0.90 |
| 15.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.135 | 1.105 | 0.00 | 1.80 |
| 15.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 20.599 | 0.135 | 1.105 | 0.00 | 43.80 |
| 15.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 20.599 | 0.135 | 1.105 | 0.00 | 29.52 |
| 15.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.135 | 1.105 | 0.00 | 14.76 |
| 15.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 20.599 | 0.135 | 1.105 | 0.00 | 29.52 |
| 15.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 20.599 | 0.135 | 1.105 | 0.00 | 6.00 |
| 15.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 20.599 | 0.135 | 1.105 | 0.00 | 18.00 |
| 15.00 | (1) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.135 | 1.105 | 0.00 | 0.90 |
| 20.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.137 | 1.112 | 0.00 | 1.80 |
| 20.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 20.599 | 0.137 | 1.112 | 0.00 | 43.80 |
| 20.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 20.599 | 0.137 | 1.112 | 0.00 | 29.52 |
| 20.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.137 | 1.112 | 0.00 | 14.76 |
| 20.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 20.599 | 0.137 | 1.112 | 0.00 | 29.52 |
| 20.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 20.599 | 0.137 | 1.112 | 0.00 | 6.00 |
| 20.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 20.599 | 0.137 | 1.112 | 0.00 | 18.00 |
| 20.00 | (1) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.137 | 1.112 | 0.00 | 0.90 |
| 25.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.140 | 1.120 | 0.00 | 1.80 |
| 25.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 20.599 | 0.140 | 1.120 | 0.00 | 43.80 |
| 25.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 20.599 | 0.140 | 1.120 | 0.00 | 29.52 |
| 25.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.140 | 1.120 | 0.00 | 14.76 |
| 25.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 20.599 | 0.140 | 1.120 | 0.00 | 29.52 |
| 25.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 20.599 | 0.140 | 1.120 | 0.00 | 6.00 |
| 25.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 20.599 | 0.140 | 1.120 | 0.00 | 18.00 |
| 30.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.616 | 0.143 | 1.128 | 0.00 | 1.80 |
| 30.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 20.616 | 0.143 | 1.128 | 0.00 | 43.80 |
| 30.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 20.616 | 0.143 | 1.128 | 0.00 | 29.52 |
| 30.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.616 | 0.143 | 1.128 | 0.00 | 14.76 |
| 30.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 20.616 | 0.143 | 1.128 | 0.00 | 29.52 |
| 30.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 20.616 | 0.143 | 1.128 | 0.00 | 6.00 |
| 30.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 20.616 | 0.143 | 1.128 | 0.00 | 18.00 |
| 35.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 21.545 | 0.145 | 1.136 | 0.00 | 1.80 |
| 35.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 21.545 | 0.145 | 1.136 | 0.00 | 43.80 |
| 35.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 21.545 | 0.145 | 1.136 | 0.00 | 29.52 |
| 35.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 21.545 | 0.145 | 1.136 | 0.00 | 14.76 |
| 35.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 21.545 | 0.145 | 1.136 | 0.00 | 29.52 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)



6/13/2014 11:15:45 AM
 Page: 7

© 2007 - 2014 by ATC IP LLC. All rights reserved.

Load Case: 1.2D + 1.6W 110.00 mph with No Ice 23 Iterations

Gust Response Factor : 1.10 Wind Importance Factor : 1.00


Dead Load Factor : 1.20

Wind Load Factor : 1.60

| | | | | | | | | | | | | |
|-------|----------------------|-----|------|-------|------|------|------|--------|-------|-------|------|-------|
| 35.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 21.545 | 0.145 | 1.136 | 0.00 | 6.00 |
| 35.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 21.545 | 0.145 | 1.136 | 0.00 | 18.00 |
| 40.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 22.383 | 0.148 | 1.145 | 0.00 | 1.80 |
| 40.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 22.383 | 0.148 | 1.145 | 0.00 | 43.80 |
| 40.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 22.383 | 0.148 | 1.145 | 0.00 | 29.52 |
| 40.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 22.383 | 0.148 | 1.145 | 0.00 | 14.76 |
| 40.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 22.383 | 0.148 | 1.145 | 0.00 | 29.52 |
| 40.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 22.383 | 0.148 | 1.145 | 0.00 | 6.00 |
| 40.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 22.383 | 0.148 | 1.145 | 0.00 | 18.00 |
| 45.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 23.149 | 0.151 | 1.154 | 0.00 | 1.80 |
| 45.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 23.149 | 0.151 | 1.154 | 0.00 | 43.80 |
| 45.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 23.149 | 0.151 | 1.154 | 0.00 | 29.52 |
| 45.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 23.149 | 0.151 | 1.154 | 0.00 | 14.76 |
| 45.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 23.149 | 0.151 | 1.154 | 0.00 | 29.52 |
| 45.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 23.149 | 0.151 | 1.154 | 0.00 | 6.00 |
| 45.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 23.149 | 0.151 | 1.154 | 0.00 | 18.00 |
| 50.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 23.856 | 0.155 | 1.164 | 0.00 | 1.80 |
| 50.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 23.856 | 0.155 | 1.164 | 0.00 | 43.80 |
| 50.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 23.856 | 0.155 | 1.164 | 0.00 | 29.52 |
| 50.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 23.856 | 0.155 | 1.164 | 0.00 | 14.76 |
| 50.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 23.856 | 0.155 | 1.164 | 0.00 | 29.52 |
| 50.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 23.856 | 0.155 | 1.164 | 0.00 | 6.00 |
| 50.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 23.856 | 0.155 | 1.164 | 0.00 | 18.00 |
| 53.00 | (2) 1/2" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 24.257 | 0.157 | 1.172 | 0.00 | 1.08 |
| 53.00 | (2) 2" Conduit | Yes | 3.00 | 0.000 | 2.38 | 0.60 | 0.00 | 24.257 | 0.157 | 1.172 | 0.00 | 26.28 |
| 53.00 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 0.50 | 0.00 | 24.257 | 0.157 | 1.172 | 0.00 | 17.71 |
| 53.00 | (3) 1 5/8" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 24.257 | 0.157 | 1.172 | 0.00 | 8.85 |
| 53.00 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 0.50 | 0.00 | 24.257 | 0.157 | 1.172 | 0.00 | 17.71 |
| 53.00 | (1) 1 1/4" Hybriflex | Yes | 3.00 | 0.000 | 1.54 | 0.38 | 0.00 | 24.257 | 0.157 | 1.172 | 0.00 | 3.60 |
| 53.00 | (3) 1 1/4" Hybriflex | Yes | 3.00 | 0.000 | 1.55 | 0.39 | 0.00 | 24.257 | 0.157 | 1.172 | 0.00 | 10.80 |
| 55.00 | (2) 1/2" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 24.515 | 0.157 | 1.171 | 0.00 | 0.72 |
| 55.00 | (2) 2" Conduit | Yes | 2.00 | 0.000 | 2.38 | 0.40 | 0.00 | 24.515 | 0.157 | 1.171 | 0.00 | 17.52 |
| 55.00 | (6) 1 5/8" Coax | Yes | 2.00 | 0.000 | 1.98 | 0.33 | 0.00 | 24.515 | 0.157 | 1.171 | 0.00 | 11.81 |
| 55.00 | (3) 1 5/8" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 24.515 | 0.157 | 1.171 | 0.00 | 5.90 |
| 55.00 | (6) 1 5/8" Coax | Yes | 2.00 | 0.000 | 1.98 | 0.33 | 0.00 | 24.515 | 0.157 | 1.171 | 0.00 | 11.81 |
| 55.00 | (1) 1 1/4" Hybriflex | Yes | 2.00 | 0.000 | 1.54 | 0.26 | 0.00 | 24.515 | 0.157 | 1.171 | 0.00 | 2.40 |
| 55.00 | (3) 1 1/4" Hybriflex | Yes | 2.00 | 0.000 | 1.55 | 0.26 | 0.00 | 24.515 | 0.157 | 1.171 | 0.00 | 7.20 |
| 60.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 25.132 | 0.159 | 1.178 | 0.00 | 1.80 |
| 60.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 25.132 | 0.159 | 1.178 | 0.00 | 43.80 |
| 60.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 25.132 | 0.159 | 1.178 | 0.00 | 29.52 |
| 60.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 25.132 | 0.159 | 1.178 | 0.00 | 14.76 |
| 60.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 25.132 | 0.159 | 1.178 | 0.00 | 29.52 |
| 60.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 25.132 | 0.159 | 1.178 | 0.00 | 6.00 |
| 60.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 25.132 | 0.159 | 1.178 | 0.00 | 18.00 |
| 65.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 25.713 | 0.163 | 1.188 | 0.00 | 1.80 |
| 65.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 25.713 | 0.163 | 1.188 | 0.00 | 43.80 |
| 65.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 25.713 | 0.163 | 1.188 | 0.00 | 29.52 |
| 65.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 25.713 | 0.163 | 1.188 | 0.00 | 14.76 |
| 65.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 25.713 | 0.163 | 1.188 | 0.00 | 29.52 |
| 65.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 25.713 | 0.163 | 1.188 | 0.00 | 6.00 |
| 65.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 25.713 | 0.163 | 1.188 | 0.00 | 18.00 |
| 70.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 26.263 | 0.166 | 1.199 | 0.00 | 1.80 |
| 70.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 26.263 | 0.166 | 1.199 | 0.00 | 43.80 |
| 70.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 26.263 | 0.166 | 1.199 | 0.00 | 29.52 |
| 70.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 26.263 | 0.166 | 1.199 | 0.00 | 14.76 |
| 70.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 26.263 | 0.166 | 1.199 | 0.00 | 29.52 |
| 70.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 26.263 | 0.166 | 1.199 | 0.00 | 6.00 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)




| | | |
|-------------------------------|------------------------|-------------------------------|
| Load Case: 1.2D + 1.6W | 110.00 mph with No Ice | 23 Iterations |
| Gust Response Factor : 1.10 | | Wind Importance Factor : 1.00 |
| Dead Load Factor : 1.20 | | |
| Wind Load Factor : 1.60 | | |

| | | | | | | | | | | | | |
|-------|----------------------|-----|------|-------|------|------|------|--------|-------|-------|------|-------|
| 70.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 26.263 | 0.166 | 1.199 | 0.00 | 18.00 |
| 75.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 26.786 | 0.170 | 1.211 | 0.00 | 1.80 |
| 75.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 26.786 | 0.170 | 1.211 | 0.00 | 43.80 |
| 75.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 26.786 | 0.170 | 1.211 | 0.00 | 29.52 |
| 75.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 26.786 | 0.170 | 1.211 | 0.00 | 14.76 |
| 75.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 26.786 | 0.170 | 1.211 | 0.00 | 29.52 |
| 75.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 26.786 | 0.170 | 1.211 | 0.00 | 6.00 |
| 75.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 26.786 | 0.170 | 1.211 | 0.00 | 18.00 |
| 80.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 27.285 | 0.174 | 1.223 | 0.00 | 1.80 |
| 80.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 27.285 | 0.174 | 1.223 | 0.00 | 43.80 |
| 80.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 27.285 | 0.174 | 1.223 | 0.00 | 29.52 |
| 80.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 27.285 | 0.174 | 1.223 | 0.00 | 14.76 |
| 80.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 27.285 | 0.174 | 1.223 | 0.00 | 29.52 |
| 80.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 27.285 | 0.174 | 1.223 | 0.00 | 6.00 |
| 80.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 27.285 | 0.174 | 1.223 | 0.00 | 18.00 |
| 85.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 27.761 | 0.179 | 1.236 | 0.00 | 1.80 |
| 85.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 27.761 | 0.179 | 1.236 | 0.00 | 43.80 |
| 85.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 27.761 | 0.179 | 1.236 | 0.00 | 29.52 |
| 85.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 27.761 | 0.179 | 1.236 | 0.00 | 14.76 |
| 85.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 27.761 | 0.179 | 1.236 | 0.00 | 29.52 |
| 85.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 27.761 | 0.179 | 1.236 | 0.00 | 6.00 |
| 85.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 27.761 | 0.179 | 1.236 | 0.00 | 18.00 |
| 90.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 28.219 | 0.183 | 1.249 | 0.00 | 1.80 |
| 90.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 28.219 | 0.183 | 1.249 | 0.00 | 43.80 |
| 90.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 28.219 | 0.183 | 1.249 | 0.00 | 29.52 |
| 90.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 28.219 | 0.183 | 1.249 | 0.00 | 14.76 |
| 90.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 28.219 | 0.183 | 1.249 | 0.00 | 29.52 |
| 90.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 28.219 | 0.183 | 1.249 | 0.00 | 6.00 |
| 90.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 28.219 | 0.183 | 1.249 | 0.00 | 18.00 |
| 91.42 | (2) 1/2" Coax | Yes | 1.42 | 0.000 | 0.00 | 0.00 | 0.00 | 28.345 | 0.186 | 1.258 | 0.00 | 0.51 |
| 91.42 | (2) 2" Conduit | Yes | 1.42 | 0.000 | 2.38 | 0.28 | 0.00 | 28.345 | 0.186 | 1.258 | 0.00 | 12.41 |
| 91.42 | (6) 1 5/8" Coax | Yes | 1.42 | 0.000 | 1.98 | 0.23 | 0.00 | 28.345 | 0.186 | 1.258 | 0.00 | 8.36 |
| 91.42 | (3) 1 5/8" Coax | Yes | 1.42 | 0.000 | 0.00 | 0.00 | 0.00 | 28.345 | 0.186 | 1.258 | 0.00 | 4.18 |
| 91.42 | (6) 1 5/8" Coax | Yes | 1.42 | 0.000 | 1.98 | 0.23 | 0.00 | 28.345 | 0.186 | 1.258 | 0.00 | 8.36 |
| 91.42 | (1) 1 1/4" Hybriflex | Yes | 1.42 | 0.000 | 1.54 | 0.18 | 0.00 | 28.345 | 0.186 | 1.258 | 0.00 | 1.70 |
| 91.42 | (3) 1 1/4" Hybriflex | Yes | 1.42 | 0.000 | 1.55 | 0.18 | 0.00 | 28.345 | 0.186 | 1.258 | 0.00 | 5.10 |
| 95.00 | (2) 1/2" Coax | Yes | 3.58 | 0.000 | 0.00 | 0.00 | 0.00 | 28.658 | 0.188 | 1.265 | 0.00 | 1.29 |
| 95.00 | (2) 2" Conduit | Yes | 3.58 | 0.000 | 2.38 | 0.71 | 0.00 | 28.658 | 0.188 | 1.265 | 0.00 | 31.39 |
| 95.00 | (6) 1 5/8" Coax | Yes | 3.58 | 0.000 | 1.98 | 0.59 | 0.00 | 28.658 | 0.188 | 1.265 | 0.00 | 21.15 |
| 95.00 | (3) 1 5/8" Coax | Yes | 3.58 | 0.000 | 0.00 | 0.00 | 0.00 | 28.658 | 0.188 | 1.265 | 0.00 | 10.58 |
| 95.00 | (6) 1 5/8" Coax | Yes | 3.58 | 0.000 | 1.98 | 0.59 | 0.00 | 28.658 | 0.188 | 1.265 | 0.00 | 21.15 |
| 95.00 | (1) 1 1/4" Hybriflex | Yes | 3.58 | 0.000 | 1.54 | 0.46 | 0.00 | 28.658 | 0.188 | 1.265 | 0.00 | 4.30 |
| 95.00 | (3) 1 1/4" Hybriflex | Yes | 3.58 | 0.000 | 1.55 | 0.46 | 0.00 | 28.658 | 0.188 | 1.265 | 0.00 | 12.90 |
| 98.00 | (2) 1/2" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 28.913 | 0.192 | 1.275 | 0.00 | 1.08 |
| 98.00 | (2) 2" Conduit | Yes | 3.00 | 0.000 | 2.38 | 0.60 | 0.00 | 28.913 | 0.192 | 1.275 | 0.00 | 26.28 |
| 98.00 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 0.50 | 0.00 | 28.913 | 0.192 | 1.275 | 0.00 | 17.71 |
| 98.00 | (3) 1 5/8" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 28.913 | 0.192 | 1.275 | 0.00 | 8.85 |
| 98.00 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 0.50 | 0.00 | 28.913 | 0.192 | 1.275 | 0.00 | 17.71 |
| 98.00 | (1) 1 1/4" Hybriflex | Yes | 3.00 | 0.000 | 1.54 | 0.38 | 0.00 | 28.913 | 0.192 | 1.275 | 0.00 | 3.60 |
| 98.00 | (3) 1 1/4" Hybriflex | Yes | 3.00 | 0.000 | 1.55 | 0.39 | 0.00 | 28.913 | 0.192 | 1.275 | 0.00 | 10.80 |
| 100.0 | (2) 1/2" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 29.081 | 0.192 | 1.275 | 0.00 | 0.72 |
| 100.0 | (2) 2" Conduit | Yes | 2.00 | 0.000 | 2.38 | 0.40 | 0.00 | 29.081 | 0.192 | 1.275 | 0.00 | 17.52 |
| 100.0 | (6) 1 5/8" Coax | Yes | 2.00 | 0.000 | 1.98 | 0.33 | 0.00 | 29.081 | 0.192 | 1.275 | 0.00 | 11.81 |
| 100.0 | (3) 1 5/8" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 29.081 | 0.192 | 1.275 | 0.00 | 5.90 |
| 100.0 | (6) 1 5/8" Coax | Yes | 2.00 | 0.000 | 1.98 | 0.33 | 0.00 | 29.081 | 0.192 | 1.275 | 0.00 | 11.81 |
| 100.0 | (1) 1 1/4" Hybriflex | Yes | 2.00 | 0.000 | 1.54 | 0.26 | 0.00 | 29.081 | 0.192 | 1.275 | 0.00 | 2.40 |
| 100.0 | (3) 1 1/4" Hybriflex | Yes | 2.00 | 0.000 | 1.55 | 0.26 | 0.00 | 29.081 | 0.192 | 1.275 | 0.00 | 7.20 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)



© 2007 - 2014 by ATC IP LLC. All rights reserved.

Load Case: 1.2D + 1.6W 110.00 mph with No Ice 23 Iterations

Gust Response Factor : 1.10 Wind Importance Factor : 1.00

Dead Load Factor : 1.20

Wind Load Factor : 1.60


| | | | | | | | | | | | | |
|-------|----------------------|-----|------|-------|------|------|------|--------|-------|-------|-------|-------|
| 105.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 29.489 | 0.195 | 1.285 | 0.00 | 1.80 |
| 105.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 29.489 | 0.195 | 1.285 | 0.00 | 43.80 |
| 105.0 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 29.489 | 0.195 | 1.285 | 0.00 | 29.52 |
| 105.0 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 29.489 | 0.195 | 1.285 | 0.00 | 14.76 |
| 105.0 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 29.489 | 0.195 | 1.285 | 0.00 | 29.52 |
| 105.0 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 29.489 | 0.195 | 1.285 | 0.00 | 6.00 |
| 105.0 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 29.489 | 0.195 | 1.285 | 0.00 | 18.00 |
| 110.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 29.884 | 0.200 | 0.000 | 0.00 | 1.80 |
| 110.0 | (2) 2" Conduit | Yes | 5.00 | 1.200 | 2.38 | 0.99 | 1.19 | 29.884 | 0.200 | 0.000 | 62.59 | 43.80 |
| 110.0 | (6) 1 5/8" Coax | Yes | 5.00 | 1.200 | 1.98 | 0.82 | 0.99 | 29.884 | 0.200 | 0.000 | 52.07 | 29.52 |
| 110.0 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 29.884 | 0.200 | 0.000 | 0.00 | 14.76 |
| 110.0 | (6) 1 5/8" Coax | Yes | 5.00 | 1.200 | 1.98 | 0.82 | 0.99 | 29.884 | 0.200 | 0.000 | 52.07 | 29.52 |
| 110.0 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 1.200 | 1.54 | 0.64 | 0.77 | 29.884 | 0.200 | 0.000 | 40.50 | 6.00 |
| 110.0 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 1.200 | 1.55 | 0.65 | 0.77 | 29.884 | 0.200 | 0.000 | 40.76 | 18.00 |
| 115.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 30.266 | 0.206 | 0.000 | 0.00 | 1.80 |
| 115.0 | (2) 2" Conduit | Yes | 5.00 | 1.200 | 2.38 | 0.99 | 1.19 | 30.266 | 0.206 | 0.000 | 63.39 | 43.80 |
| 115.0 | (6) 1 5/8" Coax | Yes | 5.00 | 1.200 | 1.98 | 0.82 | 0.99 | 30.266 | 0.206 | 0.000 | 52.73 | 29.52 |
| 115.0 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 30.266 | 0.206 | 0.000 | 0.00 | 14.76 |
| 115.0 | (6) 1 5/8" Coax | Yes | 5.00 | 1.200 | 1.98 | 0.82 | 0.99 | 30.266 | 0.206 | 0.000 | 52.73 | 29.52 |
| 115.0 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 1.200 | 1.54 | 0.64 | 0.77 | 30.266 | 0.206 | 0.000 | 41.02 | 6.00 |
| 115.0 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 1.200 | 1.55 | 0.65 | 0.77 | 30.266 | 0.206 | 0.000 | 41.28 | 18.00 |
| 116.0 | (2) 1/2" Coax | Yes | 1.00 | 0.000 | 0.00 | 0.00 | 0.00 | 30.341 | 0.209 | 0.000 | 0.00 | 0.36 |
| 116.0 | (2) 2" Conduit | Yes | 1.00 | 1.200 | 2.38 | 0.20 | 0.24 | 30.341 | 0.209 | 0.000 | 12.71 | 8.76 |
| 116.0 | (6) 1 5/8" Coax | Yes | 1.00 | 1.200 | 1.98 | 0.17 | 0.20 | 30.341 | 0.209 | 0.000 | 10.57 | 5.90 |
| 116.0 | (3) 1 5/8" Coax | Yes | 1.00 | 0.000 | 0.00 | 0.00 | 0.00 | 30.341 | 0.209 | 0.000 | 0.00 | 2.95 |
| 116.0 | (6) 1 5/8" Coax | Yes | 1.00 | 1.200 | 1.98 | 0.17 | 0.20 | 30.341 | 0.209 | 0.000 | 10.57 | 5.90 |
| 116.0 | (1) 1 1/4" Hybriflex | Yes | 1.00 | 1.200 | 1.54 | 0.13 | 0.15 | 30.341 | 0.209 | 0.000 | 8.22 | 1.20 |
| 116.0 | (3) 1 1/4" Hybriflex | Yes | 1.00 | 1.200 | 1.55 | 0.13 | 0.16 | 30.341 | 0.209 | 0.000 | 8.28 | 3.60 |
| 120.0 | (2) 1/2" Coax | Yes | 4.00 | 0.000 | 0.00 | 0.00 | 0.00 | 30.636 | 0.143 | 1.129 | 0.00 | 1.44 |
| 120.0 | (2) 2" Conduit | Yes | 4.00 | 0.000 | 2.38 | 0.79 | 0.00 | 30.636 | 0.143 | 1.129 | 0.00 | 35.04 |
| 120.0 | (6) 1 5/8" Coax | Yes | 4.00 | 0.000 | 1.98 | 0.66 | 0.00 | 30.636 | 0.143 | 1.129 | 0.00 | 23.61 |
| 120.0 | (3) 1 5/8" Coax | Yes | 4.00 | 0.000 | 0.00 | 0.00 | 0.00 | 30.636 | 0.143 | 1.129 | 0.00 | 11.81 |
| 120.0 | (6) 1 5/8" Coax | Yes | 4.00 | 0.000 | 1.98 | 0.66 | 0.00 | 30.636 | 0.143 | 1.129 | 0.00 | 23.61 |
| 125.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 30.995 | 0.147 | 1.140 | 0.00 | 1.80 |
| 125.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 30.995 | 0.147 | 1.140 | 0.00 | 43.80 |
| 125.0 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 30.995 | 0.147 | 1.140 | 0.00 | 29.52 |
| 125.0 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 30.995 | 0.147 | 1.140 | 0.00 | 14.76 |
| 125.0 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 30.995 | 0.147 | 1.140 | 0.00 | 29.52 |
| 128.0 | (2) 1/2" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 31.206 | 0.150 | 1.151 | 0.00 | 1.08 |
| 128.0 | (2) 2" Conduit | Yes | 3.00 | 0.000 | 2.38 | 0.60 | 0.00 | 31.206 | 0.150 | 1.151 | 0.00 | 26.28 |
| 128.0 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 0.50 | 0.00 | 31.206 | 0.150 | 1.151 | 0.00 | 17.71 |
| 128.0 | (3) 1 5/8" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 31.206 | 0.150 | 1.151 | 0.00 | 8.85 |
| 128.0 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 0.50 | 0.00 | 31.206 | 0.150 | 1.151 | 0.00 | 17.71 |
| 130.0 | (2) 1/2" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 31.345 | 0.105 | 1.015 | 0.00 | 0.72 |
| 130.0 | (2) 2" Conduit | Yes | 2.00 | 0.000 | 2.38 | 0.40 | 0.00 | 31.345 | 0.105 | 1.015 | 0.00 | 17.52 |
| 130.0 | (6) 1 5/8" Coax | Yes | 2.00 | 0.000 | 1.98 | 0.33 | 0.00 | 31.345 | 0.105 | 1.015 | 0.00 | 11.81 |
| 130.0 | (3) 1 5/8" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 31.345 | 0.105 | 1.015 | 0.00 | 5.90 |
| 135.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 31.684 | 0.107 | 1.022 | 0.00 | 1.80 |
| 135.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 31.684 | 0.107 | 1.022 | 0.00 | 43.80 |
| 135.0 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 31.684 | 0.107 | 1.022 | 0.00 | 29.52 |
| 135.0 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 31.684 | 0.107 | 1.022 | 0.00 | 14.76 |
| 139.3 | (2) 1/2" Coax | Yes | 4.33 | 0.000 | 0.00 | 0.00 | 0.00 | 31.972 | 0.110 | 1.031 | 0.00 | 1.56 |
| 139.3 | (2) 2" Conduit | Yes | 4.33 | 0.000 | 2.38 | 0.86 | 0.00 | 31.972 | 0.110 | 1.031 | 0.00 | 37.96 |
| 139.3 | (6) 1 5/8" Coax | Yes | 4.33 | 0.000 | 1.98 | 0.72 | 0.00 | 31.972 | 0.110 | 1.031 | 0.00 | 25.58 |
| 140.0 | (2) 1/2" Coax | Yes | 0.67 | 0.000 | 0.00 | 0.00 | 0.00 | 32.015 | 0.112 | 1.037 | 0.00 | 0.24 |
| 140.0 | (2) 2" Conduit | Yes | 0.67 | 0.000 | 2.38 | 0.13 | 0.00 | 32.015 | 0.112 | 1.037 | 0.00 | 5.84 |
| 140.0 | (6) 1 5/8" Coax | Yes | 0.67 | 0.000 | 1.98 | 0.11 | 0.00 | 32.015 | 0.112 | 1.037 | 0.00 | 3.94 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev: 0.000 (ft)

6/13/2014 11:15:45 AM

Page: 10



© 2007 - 2014 by ATC IP LLC. All rights reserved.


Load Case: 1.2D + 1.6W 110.00 mph with No Ice 23 Iterations
 Gust Response Factor : 1.10 Wind Importance Factor : 1.00
 Dead Load Factor : 1.20
 Wind Load Factor : 1.60

| | | | | | | | | | | | | |
|----------------|-----------------|-----|------|-------|------|------|------|--------|-------|-------|---------------|-----------------|
| 144.4 | (2) 1/2" Coax | Yes | 4.42 | 0.000 | 0.00 | 0.00 | 0.00 | 32.301 | 0.114 | 1.042 | 0.00 | 1.59 |
| 144.4 | (2) 2" Conduit | Yes | 4.42 | 0.000 | 2.38 | 0.88 | 0.00 | 32.301 | 0.114 | 1.042 | 0.00 | 38.69 |
| 144.4 | (6) 1 5/8" Coax | Yes | 4.42 | 0.000 | 1.98 | 0.73 | 0.00 | 32.301 | 0.114 | 1.042 | 0.00 | 26.07 |
| 145.0 | (2) 1/2" Coax | Yes | 0.58 | 0.000 | 0.00 | 0.00 | 0.00 | 32.338 | 0.115 | 1.044 | 0.00 | 0.21 |
| 145.0 | (2) 2" Conduit | Yes | 0.58 | 0.000 | 2.38 | 0.12 | 0.00 | 32.338 | 0.115 | 1.044 | 0.00 | 5.11 |
| 145.0 | (6) 1 5/8" Coax | Yes | 0.58 | 0.000 | 1.98 | 0.10 | 0.00 | 32.338 | 0.115 | 1.044 | 0.00 | 3.44 |
| 148.0 | (2) 1/2" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 32.528 | 0.116 | 1.048 | 0.00 | 1.08 |
| 148.0 | (2) 2" Conduit | Yes | 3.00 | 0.000 | 2.38 | 0.60 | 0.00 | 32.528 | 0.116 | 1.048 | 0.00 | 26.28 |
| 148.0 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 0.50 | 0.00 | 32.528 | 0.116 | 1.048 | 0.00 | 17.71 |
| 150.0 | (2) 1/2" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 32.653 | 0.064 | 0.000 | 0.00 | 0.72 |
| 150.0 | (2) 2" Conduit | Yes | 2.00 | 0.000 | 2.38 | 0.40 | 0.00 | 32.653 | 0.064 | 0.000 | 0.00 | 17.52 |
| 155.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 32.960 | 0.066 | 0.000 | 0.00 | 1.80 |
| 155.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 32.960 | 0.066 | 0.000 | 0.00 | 43.80 |
| 160.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 33.260 | 0.068 | 0.000 | 0.00 | 1.80 |
| 160.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 33.260 | 0.068 | 0.000 | 0.00 | 43.80 |
| 165.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 33.554 | 0.071 | 0.000 | 0.00 | 1.80 |
| 165.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 33.554 | 0.071 | 0.000 | 0.00 | 43.80 |
| 170.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 33.842 | 0.074 | 0.000 | 0.00 | 1.80 |
| 170.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 33.842 | 0.074 | 0.000 | 0.00 | 43.80 |
| 171.0 | (2) 1/2" Coax | Yes | 1.00 | 0.000 | 0.00 | 0.00 | 0.00 | 33.898 | 0.076 | 0.000 | 0.00 | 0.36 |
| 171.0 | (2) 2" Conduit | Yes | 1.00 | 0.000 | 2.38 | 0.20 | 0.00 | 33.898 | 0.076 | 0.000 | 0.00 | 8.76 |
| Totals: | | | | | | | | | | | 549.50 | 4,147.70 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)

© 2007 - 2014 by ATC IP LLC. All rights reserved.



6/13/2014 11:15:46 AM
 Page: 11

Load Case: 1.2D + 1.6W 110.00 mph with No Ice 23 Iterations

Gust Response Factor : 1.10 Wind Importance Factor : 1.00

Dead Load Factor : 1.20


Wind Load Factor : 1.60

Applied Segment Forces Summary

| Seg Elev (ft) | Lateral FX (-) (lb) | Axial FY (-) (lb) | Torsion MY (lb-ft) | Moment MZ (lb-ft) |
|----------------|---------------------|-------------------|--------------------|-------------------|
| 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 5.00 | 775.89 | 2,459.22 | 0.00 | 0.00 |
| 10.00 | 767.12 | 2,423.59 | 0.00 | 0.00 |
| 15.00 | 758.35 | 2,387.95 | 0.00 | 0.00 |
| 20.00 | 811.93 | 2,401.03 | 0.00 | 0.00 |
| 25.00 | 740.80 | 2,315.78 | 0.00 | 0.00 |
| 30.00 | 732.65 | 2,280.14 | 0.00 | 0.00 |
| 35.00 | 756.46 | 2,244.51 | 0.00 | 0.00 |
| 40.00 | 776.35 | 2,208.87 | 0.00 | 0.00 |
| 45.00 | 793.06 | 2,173.23 | 0.00 | 0.00 |
| 50.00 | 817.22 | 3,606.13 | 0.00 | 0.00 |
| 53.00 | 493.64 | 2,131.91 | 0.00 | 0.00 |
| 55.00 | 328.83 | 750.47 | 0.00 | 0.00 |
| 60.00 | 835.27 | 1,854.79 | 0.00 | 0.00 |
| 65.00 | 843.65 | 1,824.24 | 0.00 | 0.00 |
| 70.00 | 850.51 | 1,793.69 | 0.00 | 0.00 |
| 75.00 | 856.04 | 1,763.15 | 0.00 | 0.00 |
| 80.00 | 860.35 | 1,732.60 | 0.00 | 0.00 |
| 85.00 | 863.56 | 1,702.06 | 0.00 | 0.00 |
| 90.00 | 865.76 | 1,671.51 | 0.00 | 0.00 |
| 91.42 | 244.20 | 468.04 | 0.00 | 0.00 |
| 95.00 | 627.99 | 1,893.18 | 0.00 | 0.00 |
| 98.00 | 525.64 | 1,562.87 | 0.00 | 0.00 |
| 100.0 | 347.96 | 569.14 | 0.00 | 0.00 |
| 105.0 | 873.31 | 1,405.04 | 0.00 | 0.00 |
| 110.0 | 1,485.67 | 1,379.59 | 0.00 | 0.00 |
| 115.0 | 1,470.66 | 1,354.13 | 0.00 | 0.00 |
| 116.0 | 3,908.51 | 3,130.13 | 0.00 | 2,988.30 |
| 120.0 | 585.16 | 1,041.71 | 0.00 | 0.00 |
| 125.0 | 728.15 | 1,279.23 | 0.00 | 0.00 |
| 128.0 | 1,114.96 | 850.36 | 0.00 | 0.00 |
| 130.0 | 252.10 | 486.65 | 0.00 | 0.00 |
| 135.0 | 4,943.15 | 3,630.84 | 0.00 | 9,316.28 |
| 139.3 | 537.88 | 934.87 | 0.00 | 0.00 |
| 140.0 | 83.02 | 225.31 | 0.00 | 0.00 |
| 144.4 | 548.81 | 1,472.15 | 0.00 | 0.00 |
| 145.0 | 71.45 | 105.10 | 0.00 | 0.00 |
| 148.0 | 2,934.22 | 2,067.93 | 0.00 | 0.00 |
| 150.0 | 230.22 | 327.33 | 0.00 | 0.00 |
| 155.0 | 566.92 | 804.08 | 0.00 | 0.00 |
| 160.0 | 9,087.88 | 5,515.80 | 0.00 | 0.00 |
| 165.0 | 536.31 | 637.17 | 0.00 | 0.00 |
| 170.0 | 520.32 | 616.81 | 0.00 | 0.00 |
| 171.0 | 1,648.84 | 1,112.24 | 0.00 | 0.00 |
| 175.0 | 401.45 | 437.75 | 0.00 | 0.00 |
| 178.5 | 4,579.91 | 2,658.34 | 0.00 | 6,653.11 |
| Totals: | 53,382.15 | 75,690.69 | 0.00 | 18,957.69 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)




Load Case: 1.2D + 1.6W 110.00 mph with No Ice 23 Iterations
 Gust Response Factor : 1.10 Wind Importance Factor : 1.00
 Dead Load Factor : 1.20
 Wind Load Factor : 1.60

Calculated Forces

| Seg Elev (ft) | Pu FY (-) (kips) | Vu FX (-) (kips) | Tu MY (ft-kips) | Mu MZ (ft-kips) | Mu MX (ft-kips) | Resultant Moment (ft-kips) | phi Pn (kips) | phi Vn (kips) | phi Tn (ft-kips) | phi Mn (ft-kips) | Total Deflect (in) | Rotation (deg) | Ratio |
|---------------------|------------------------|------------------------|-----------------------|-----------------------|-----------------------|----------------------------------|---------------------|---------------------|------------------------|------------------------|--------------------------|-------------------|-------|
| 0.00 | -75.62 | -53.48 | 0.00 | -6,514.47 | 0.00 | 6,514.47 | 6,164.54 | 3,082.27 | 18,158.3 | 9,092.69 | 0.00 | 0.00 | 0.729 |
| 5.00 | -73.03 | -52.88 | 0.00 | -6,247.09 | 0.00 | 6,247.09 | 6,108.61 | 3,054.31 | 17,675.6 | 8,850.97 | 0.08 | -0.14 | 0.718 |
| 10.00 | -70.48 | -52.28 | 0.00 | -5,982.69 | 0.00 | 5,982.69 | 6,050.81 | 3,025.41 | 17,193.4 | 8,609.50 | 0.30 | -0.28 | 0.707 |
| 15.00 | -67.97 | -51.68 | 0.00 | -5,721.30 | 0.00 | 5,721.30 | 5,991.14 | 2,995.57 | 16,712.0 | 8,368.43 | 0.68 | -0.43 | 0.695 |
| 20.00 | -65.44 | -51.01 | 0.00 | -5,462.91 | 0.00 | 5,462.91 | 5,929.59 | 2,964.80 | 16,231.6 | 8,127.91 | 1.20 | -0.57 | 0.683 |
| 25.00 | -63.01 | -50.41 | 0.00 | -5,207.84 | 0.00 | 5,207.84 | 5,866.18 | 2,933.09 | 15,752.7 | 7,888.07 | 1.89 | -0.72 | 0.671 |
| 30.00 | -60.61 | -49.80 | 0.00 | -4,955.81 | 0.00 | 4,955.81 | 5,800.89 | 2,900.44 | 15,275.4 | 7,649.08 | 2.72 | -0.87 | 0.659 |
| 35.00 | -58.25 | -49.16 | 0.00 | -4,706.80 | 0.00 | 4,706.80 | 5,733.73 | 2,866.86 | 14,800.1 | 7,411.07 | 3.71 | -1.02 | 0.646 |
| 40.00 | -55.93 | -48.49 | 0.00 | -4,461.00 | 0.00 | 4,461.00 | 5,664.70 | 2,832.35 | 14,327.0 | 7,174.19 | 4.86 | -1.17 | 0.632 |
| 45.00 | -53.65 | -47.79 | 0.00 | -4,218.55 | 0.00 | 4,218.55 | 5,593.79 | 2,796.90 | 13,856.5 | 6,938.58 | 6.16 | -1.32 | 0.618 |
| 50.00 | -49.96 | -46.99 | 0.00 | -3,979.60 | 0.00 | 3,979.60 | 5,521.02 | 2,760.51 | 13,388.9 | 6,704.40 | 7.63 | -1.47 | 0.603 |
| 53.00 | -47.78 | -46.51 | 0.00 | -3,838.62 | 0.00 | 3,838.62 | 4,440.13 | 2,220.06 | 10,789.7 | 5,402.88 | 8.58 | -1.56 | 0.722 |
| 55.00 | -46.94 | -46.26 | 0.00 | -3,745.60 | 0.00 | 3,745.60 | 4,419.76 | 2,209.88 | 10,648.2 | 5,332.01 | 9.25 | -1.63 | 0.714 |
| 60.00 | -44.98 | -45.50 | 0.00 | -3,514.33 | 0.00 | 3,514.33 | 4,367.53 | 2,183.77 | 10,295.0 | 5,155.16 | 11.05 | -1.80 | 0.692 |
| 65.00 | -43.05 | -44.72 | 0.00 | -3,286.84 | 0.00 | 3,286.84 | 4,313.43 | 2,156.72 | 9,942.96 | 4,978.87 | 13.02 | -1.97 | 0.671 |
| 70.00 | -41.16 | -43.93 | 0.00 | -3,063.22 | 0.00 | 3,063.22 | 4,257.46 | 2,128.73 | 9,592.32 | 4,803.29 | 15.18 | -2.14 | 0.648 |
| 75.00 | -39.30 | -43.13 | 0.00 | -2,843.56 | 0.00 | 2,843.56 | 4,199.61 | 2,099.81 | 9,243.38 | 4,628.56 | 17.51 | -2.31 | 0.624 |
| 80.00 | -37.48 | -42.30 | 0.00 | -2,627.94 | 0.00 | 2,627.94 | 4,139.90 | 2,069.95 | 8,896.44 | 4,454.83 | 20.02 | -2.48 | 0.599 |
| 85.00 | -35.70 | -41.47 | 0.00 | -2,416.43 | 0.00 | 2,416.43 | 4,078.31 | 2,039.15 | 8,551.80 | 4,282.26 | 22.70 | -2.65 | 0.573 |
| 90.00 | -34.00 | -40.59 | 0.00 | -2,209.09 | 0.00 | 2,209.09 | 4,014.84 | 2,007.42 | 8,209.74 | 4,110.97 | 25.56 | -2.81 | 0.546 |
| 91.42 | -33.49 | -40.37 | 0.00 | -2,151.59 | 0.00 | 2,151.59 | 3,996.52 | 1,998.26 | 8,113.33 | 4,062.70 | 26.41 | -2.86 | 0.538 |
| 95.00 | -31.55 | -39.70 | 0.00 | -2,006.95 | 0.00 | 2,006.95 | 3,949.51 | 1,974.76 | 7,870.56 | 3,941.13 | 28.60 | -2.97 | 0.518 |
| 98.00 | -29.96 | -39.14 | 0.00 | -1,887.84 | 0.00 | 1,887.84 | 3,056.80 | 1,528.40 | 6,090.92 | 3,049.99 | 30.50 | -3.07 | 0.629 |
| 100.00 | -29.33 | -38.82 | 0.00 | -1,809.57 | 0.00 | 1,809.57 | 3,039.33 | 1,519.67 | 5,992.84 | 3,000.87 | 31.80 | -3.14 | 0.613 |
| 105.00 | -27.86 | -37.96 | 0.00 | -1,615.46 | 0.00 | 1,615.46 | 2,994.36 | 1,497.18 | 5,748.30 | 2,878.42 | 35.18 | -3.31 | 0.571 |
| 110.00 | -26.47 | -36.47 | 0.00 | -1,425.69 | 0.00 | 1,425.69 | 2,947.52 | 1,473.76 | 5,504.94 | 2,756.56 | 38.74 | -3.48 | 0.527 |
| 115.00 | -25.15 | -34.96 | 0.00 | -1,243.35 | 0.00 | 1,243.35 | 2,898.80 | 1,449.40 | 5,263.06 | 2,635.44 | 42.47 | -3.64 | 0.481 |
| 116.00 | -22.24 | -30.89 | 0.00 | -1,205.41 | 0.00 | 1,205.41 | 2,888.83 | 1,444.42 | 5,214.89 | 2,611.32 | 43.24 | -3.68 | 0.470 |
| 120.00 | -21.16 | -30.28 | 0.00 | -1,081.86 | 0.00 | 1,081.86 | 2,848.21 | 1,424.11 | 5,022.95 | 2,515.21 | 46.37 | -3.80 | 0.438 |
| 125.00 | -19.88 | -29.51 | 0.00 | -930.44 | 0.00 | 930.44 | 2,795.75 | 1,397.88 | 4,784.90 | 2,396.01 | 50.42 | -3.94 | 0.396 |
| 128.00 | -19.07 | -28.36 | 0.00 | -841.91 | 0.00 | 841.91 | 2,763.38 | 1,381.69 | 4,643.19 | 2,325.05 | 52.93 | -4.03 | 0.369 |
| 130.00 | -18.56 | -28.11 | 0.00 | -785.18 | 0.00 | 785.18 | 2,741.42 | 1,370.71 | 4,549.21 | 2,277.99 | 54.63 | -4.08 | 0.352 |
| 135.00 | -15.25 | -22.94 | 0.00 | -635.34 | 0.00 | 635.34 | 2,685.21 | 1,342.61 | 4,316.17 | 2,161.29 | 58.97 | -4.20 | 0.300 |
| 139.33 | -14.34 | -22.35 | 0.00 | -535.92 | 0.00 | 535.92 | 2,634.99 | 1,317.49 | 4,116.57 | 2,061.34 | 62.83 | -4.30 | 0.266 |
| 140.00 | -14.10 | -22.26 | 0.00 | -521.02 | 0.00 | 521.02 | 2,627.14 | 1,313.57 | 4,086.07 | 2,046.07 | 63.43 | -4.32 | 0.260 |
| 144.42 | -12.66 | -21.61 | 0.00 | -422.69 | 0.00 | 422.69 | 1,915.99 | 957.99 | 2,941.41 | 1,472.89 | 67.46 | -4.40 | 0.294 |
| 145.00 | -12.54 | -21.54 | 0.00 | -410.09 | 0.00 | 410.09 | 1,911.69 | 955.84 | 2,923.20 | 1,463.77 | 68.00 | -4.41 | 0.287 |
| 148.00 | -10.69 | -18.47 | 0.00 | -345.45 | 0.00 | 345.45 | 1,889.17 | 944.59 | 2,829.77 | 1,416.99 | 70.79 | -4.48 | 0.250 |
| 150.00 | -10.37 | -18.22 | 0.00 | -308.52 | 0.00 | 308.52 | 1,873.79 | 936.89 | 2,767.71 | 1,385.91 | 72.67 | -4.51 | 0.229 |
| 155.00 | -9.59 | -17.61 | 0.00 | -217.41 | 0.00 | 217.41 | 1,834.01 | 917.01 | 2,613.49 | 1,308.69 | 77.44 | -4.60 | 0.172 |
| 160.00 | -4.82 | -8.11 | 0.00 | -129.38 | 0.00 | 129.38 | 1,792.37 | 896.18 | 2,460.85 | 1,232.25 | 82.29 | -4.65 | 0.108 |
| 165.00 | -4.22 | -7.52 | 0.00 | -88.85 | 0.00 | 88.85 | 1,748.85 | 874.42 | 2,310.07 | 1,156.75 | 87.18 | -4.70 | 0.079 |
| 170.00 | -3.65 | -6.95 | 0.00 | -51.23 | 0.00 | 51.23 | 1,703.46 | 851.73 | 2,161.44 | 1,082.33 | 92.11 | -4.73 | 0.050 |
| 171.00 | -2.67 | -5.22 | 0.00 | -44.28 | 0.00 | 44.28 | 1,694.16 | 847.08 | 2,132.00 | 1,067.58 | 93.10 | -4.73 | 0.043 |
| 175.00 | -2.27 | -4.78 | 0.00 | -23.40 | 0.00 | 23.40 | 1,656.20 | 828.10 | 2,015.26 | 1,009.13 | 97.06 | -4.74 | 0.025 |
| 178.50 | 0.00 | -4.58 | 0.00 | -6.65 | 0.00 | 6.65 | 1,622.00 | 811.00 | 1,914.55 | 958.70 | 100.54 | -4.75 | 0.007 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)



© 2007 - 2014 by ATC IP LLC. All rights reserved.

| | | |
|-------------------------------|-------------------------------------|-------------------------------|
| Load Case: 0.9D + 1.6W | 110.00 mph with No Ice (Reduced DL) | 23 Iterations |
| Gust Response Factor : 1.10 | | Wind Importance Factor : 1.00 |
| Dead Load Factor : 0.90 | | |
| Wind Load Factor : 1.60 | | |


Shaft Segment Forces (Factored)

| Seg Top Elev (ft) | Description | Kzt | Kz | qz (psf) | qzGh (psf) | C (mph-ft) | Cf | Ice Thick (in) | Tributary (ft) | Ap (sf) | EPAs (sf) | Wind Force X (lb) | Dead Load Ice (lb) | Tot Dead Load (lb) |
|-------------------|-----------------|------|------|----------|------------|------------|-------|----------------|----------------|---------|-----------|-------------------|--------------------|--------------------|
| 0.00 | | 1.00 | 0.70 | 20.599 | 22.65 | 560.71 | 0.650 | 0.000 | 0.00 | 0.000 | 0.00 | 0.0 | 0.0 | 0.0 |
| 5.00 | | 1.00 | 0.70 | 20.599 | 22.65 | 550.92 | 0.650 | * 0.000 | 5.00 | 30.197 | 19.63 | 711.6 | 0.0 | 1,508.2 |
| 10.00 | | 1.00 | 0.70 | 20.599 | 22.65 | 541.13 | 0.650 | * 0.000 | 5.00 | 29.665 | 19.28 | 699.1 | 0.0 | 1,481.5 |
| 15.00 | | 1.00 | 0.70 | 20.599 | 22.65 | 531.34 | 0.650 | * 0.000 | 5.00 | 29.133 | 18.94 | 686.5 | 0.0 | 1,454.8 |
| 20.00 | Appertunance(s) | 1.00 | 0.70 | 20.599 | 22.65 | 521.55 | 0.650 | * 0.000 | 5.00 | 28.601 | 18.59 | 674.0 | 0.0 | 1,428.1 |
| 25.00 | | 1.00 | 0.70 | 20.599 | 22.65 | 511.76 | 0.650 | * 0.000 | 5.00 | 28.070 | 18.25 | 661.5 | 0.0 | 1,401.3 |
| 30.00 | | 1.00 | 0.70 | 20.616 | 22.67 | 502.19 | 0.650 | * 0.000 | 5.00 | 27.538 | 17.90 | 649.5 | 0.0 | 1,374.6 |
| 35.00 | | 1.00 | 0.73 | 21.545 | 23.69 | 503.36 | 0.650 | * 0.000 | 5.00 | 27.006 | 17.55 | 665.6 | 0.0 | 1,347.9 |
| 40.00 | | 1.00 | 0.76 | 22.383 | 24.62 | 502.85 | 0.650 | * 0.000 | 5.00 | 26.474 | 17.21 | 677.9 | 0.0 | 1,321.1 |
| 45.00 | Bot - Section 2 | 1.00 | 0.78 | 23.149 | 25.46 | 501.00 | 0.650 | * 0.000 | 5.00 | 25.942 | 16.86 | 687.0 | 0.0 | 1,294.4 |
| 50.00 | | 1.00 | 0.81 | 23.856 | 26.24 | 498.07 | 0.650 | * 0.000 | 5.00 | 25.728 | 16.72 | 702.1 | 0.0 | 2,369.1 |
| 53.00 | Top - Section 1 | 1.00 | 0.82 | 24.257 | 26.68 | 495.86 | 0.650 | * 0.000 | 3.00 | 15.181 | 9.87 | 421.3 | 0.0 | 1,397.6 |
| 55.00 | | 1.00 | 0.83 | 24.515 | 26.96 | 500.59 | 0.650 | * 0.000 | 2.00 | 10.015 | 6.51 | 280.9 | 0.0 | 428.6 |
| 60.00 | | 1.00 | 0.85 | 25.132 | 27.64 | 496.03 | 0.650 | * 0.000 | 5.00 | 24.664 | 16.03 | 709.1 | 0.0 | 1,055.6 |
| 65.00 | | 1.00 | 0.87 | 25.713 | 28.28 | 490.80 | 0.650 | * 0.000 | 5.00 | 24.132 | 15.69 | 709.9 | 0.0 | 1,032.7 |
| 70.00 | | 1.00 | 0.89 | 26.263 | 28.89 | 484.97 | 0.650 | * 0.000 | 5.00 | 23.600 | 15.34 | 709.1 | 0.0 | 1,009.8 |
| 75.00 | | 1.00 | 0.91 | 26.786 | 29.46 | 478.61 | 0.650 | * 0.000 | 5.00 | 23.069 | 14.99 | 706.9 | 0.0 | 986.9 |
| 80.00 | | 1.00 | 0.92 | 27.285 | 30.01 | 471.78 | 0.650 | * 0.000 | 5.00 | 22.537 | 14.65 | 703.5 | 0.0 | 963.9 |
| 85.00 | | 1.00 | 0.94 | 27.761 | 30.53 | 464.52 | 0.650 | * 0.000 | 5.00 | 22.005 | 14.30 | 698.9 | 0.0 | 941.0 |
| 90.00 | | 1.00 | 0.95 | 28.219 | 31.04 | 456.87 | 0.650 | * 0.000 | 5.00 | 21.473 | 13.96 | 693.2 | 0.0 | 918.1 |
| 91.42 | Bot - Section 3 | 1.00 | 0.96 | 28.345 | 31.17 | 454.64 | 0.650 | * 0.000 | 1.42 | 5.987 | 3.89 | 194.1 | 0.0 | 256.0 |
| 95.00 | | 1.00 | 0.97 | 28.658 | 31.52 | 448.87 | 0.650 | * 0.000 | 3.58 | 15.143 | 9.84 | 496.5 | 0.0 | 1,179.4 |
| 98.00 | Top - Section 2 | 1.00 | 0.98 | 28.913 | 31.80 | 443.91 | 0.650 | * 0.000 | 3.00 | 12.468 | 8.10 | 412.4 | 0.0 | 970.8 |
| 100.0 | | 1.00 | 0.98 | 29.081 | 31.98 | 446.32 | 0.650 | * 0.000 | 2.00 | 8.206 | 5.33 | 273.0 | 0.0 | 292.7 |
| 105.0 | | 1.00 | 1.00 | 29.489 | 32.43 | 437.73 | 0.650 | * 0.000 | 5.00 | 20.142 | 13.09 | 679.5 | 0.0 | 718.3 |
| 110.0 | | 1.00 | 1.01 | 29.884 | 32.87 | 428.86 | 1.200 | * 0.000 | 5.00 | 19.610 | 23.53 | 1,237.7 | 0.0 | 699.2 |
| 115.0 | | 1.00 | 1.02 | 30.266 | 33.29 | 419.72 | 1.200 | * 0.000 | 5.00 | 19.078 | 22.89 | 1,219.5 | 0.0 | 680.1 |
| 116.0 | Appertunance(s) | 1.00 | 1.03 | 30.341 | 33.37 | 417.87 | 1.200 | * 0.000 | 1.00 | 3.752 | 4.50 | 240.4 | 0.0 | 133.7 |
| 120.0 | | 1.00 | 1.04 | 30.636 | 33.69 | 410.35 | 0.650 | * 0.000 | 4.00 | 14.795 | 9.62 | 518.5 | 0.0 | 527.3 |
| 125.0 | | 1.00 | 1.05 | 30.995 | 34.09 | 400.74 | 0.650 | * 0.000 | 5.00 | 18.015 | 11.71 | 638.8 | 0.0 | 641.9 |
| 128.0 | Appertunance(s) | 1.00 | 1.06 | 31.206 | 34.32 | 394.87 | 0.650 | * 0.000 | 3.00 | 10.554 | 6.86 | 376.8 | 0.0 | 376.0 |
| 130.0 | | 1.00 | 1.06 | 31.345 | 34.47 | 390.91 | 0.650 | * 0.000 | 2.00 | 6.929 | 4.50 | 248.5 | 0.0 | 246.8 |
| 135.0 | Appertunance(s) | 1.00 | 1.07 | 31.684 | 34.85 | 380.89 | 0.650 | * 0.000 | 5.00 | 16.951 | 11.02 | 614.4 | 0.0 | 603.7 |
| 139.3 | Bot - Section 4 | 1.00 | 1.08 | 31.972 | 35.16 | 372.04 | 0.650 | * 0.000 | 4.33 | 14.261 | 9.27 | 521.6 | 0.0 | 507.8 |
| 140.0 | | 1.00 | 1.08 | 32.015 | 35.21 | 370.67 | 0.650 | * 0.000 | 0.67 | 2.187 | 1.42 | 80.1 | 0.0 | 139.2 |
| 144.4 | Top - Section 3 | 1.00 | 1.09 | 32.301 | 35.53 | 361.49 | 0.650 | * 0.000 | 4.42 | 14.248 | 9.26 | 526.5 | 0.0 | 907.0 |
| 145.0 | | 1.00 | 1.09 | 32.338 | 35.57 | 365.14 | 0.650 | * 0.000 | 0.58 | 1.851 | 1.20 | 68.5 | 0.0 | 52.8 |
| 148.0 | Appertunance(s) | 1.00 | 1.10 | 32.528 | 35.78 | 358.83 | 0.650 | * 0.000 | 3.00 | 9.404 | 6.11 | 349.9 | 0.0 | 268.2 |
| 150.0 | | 1.00 | 1.11 | 32.653 | 35.91 | 354.59 | 0.650 | 0.000 | 2.00 | 6.163 | 4.01 | 230.2 | 0.0 | 175.8 |
| 155.0 | | 1.00 | 1.12 | 32.960 | 36.25 | 343.87 | 0.650 | 0.000 | 5.00 | 15.035 | 9.77 | 566.9 | 0.0 | 428.7 |
| 160.0 | Appertunance(s) | 1.00 | 1.13 | 33.260 | 36.58 | 333.00 | 0.650 | 0.000 | 5.00 | 14.503 | 9.43 | 551.9 | 0.0 | 413.5 |
| 165.0 | | 1.00 | 1.14 | 33.554 | 36.91 | 321.97 | 0.650 | 0.000 | 5.00 | 13.972 | 9.08 | 536.3 | 0.0 | 398.2 |
| 170.0 | | 1.00 | 1.15 | 33.842 | 37.22 | 310.80 | 0.650 | 0.000 | 5.00 | 13.440 | 8.74 | 520.3 | 0.0 | 382.9 |
| 171.0 | Appertunance(s) | 1.00 | 1.15 | 33.898 | 37.28 | 308.55 | 0.650 | 0.000 | 1.00 | 2.624 | 1.71 | 101.8 | 0.0 | 74.7 |
| 175.0 | | 1.00 | 1.16 | 34.123 | 37.53 | 299.49 | 0.650 | 0.000 | 4.00 | 10.284 | 6.68 | 401.4 | 0.0 | 292.9 |
| 178.5 | Appertunance(s) | 1.00 | 1.16 | 34.317 | 37.74 | 291.49 | 0.650 | 0.000 | 3.50 | 8.719 | 5.67 | 342.3 | 0.0 | 248.3 |
| | | | | | | | | Totals: | 178.50 | | | 24,395.2 | 0.0 | 35,331.4 |

* = Cf Adjusted By Linear Load Ra Effect

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)



© 2007 - 2014 by ATC IP LLC. All rights reserved.

Load Case: 0.9D + 1.6W 110.00 mph with No Ice (Reduced DL) 23 Iterations

Gust Response Factor : 1.10 Wind Importance Factor : 1.00

Dead Load Factor : 0.90


Wind Load Factor : 1.60

Discrete Appurtenance Segment Forces (Factored)

| Elev (ft) | Description | Qty | qz (psf) | qzGh (psf) | Orientation Factor | Ka | Total EPAa (sf) | Horiz Ecc (ft) | Vert Ecc (ft) | Wind FX (lb) | Mom Y (lb-ft) | Mom Z (lb-ft) | Dead Load (lb) |
|-----------|----------------------|-----|----------|------------|--------------------|------|-----------------|----------------|---------------|--------------|---------------|---------------|----------------|
| 20.00 | PCTEL GPS-TMG-HR- | 1 | 20.599 | 22.659 | 1.00 | 1.00 | 0.09 | 0.000 | 0.000 | 3.26 | 0.00 | 0.00 | 0.54 |
| 20.00 | Standoff | 1 | 20.599 | 22.659 | 1.00 | 1.00 | 1.63 | 0.000 | 0.000 | 59.09 | 0.00 | 0.00 | 36.00 |
| 116.0 | Alcatel-Lucent 800 M | 3 | 30.341 | 33.375 | 0.67 | 0.80 | 3.43 | 0.000 | 0.000 | 182.90 | 0.00 | 0.00 | 143.10 |
| 116.0 | Alcatel-Lucent 1900 | 3 | 30.341 | 33.375 | 0.67 | 0.80 | 3.73 | 0.000 | 0.000 | 199.21 | 0.00 | 0.00 | 162.00 |
| 116.0 | Flat Low Profile Pla | 1 | 30.341 | 33.375 | 1.00 | 1.00 | 26.10 | 0.000 | 0.000 | 1,393.73 | 0.00 | 0.00 | 1,350.00 |
| 116.0 | RFS APXVSP18-C- | 3 | 30.489 | 33.538 | 0.83 | 0.80 | 15.98 | 0.000 | 2.000 | 857.28 | 0.00 | 1,714.56 | 153.90 |
| 116.0 | Alcatel-Lucent TD-RR | 3 | 30.341 | 33.375 | 0.67 | 0.80 | 6.51 | 0.000 | 0.000 | 347.76 | 0.00 | 0.00 | 189.00 |
| 116.0 | RFS APXV9TM14-ALU- | 3 | 30.489 | 33.538 | 0.78 | 0.80 | 11.87 | 0.000 | 2.000 | 636.87 | 0.00 | 1,273.75 | 148.77 |
| 128.0 | RFS APXV18-206517S- | 3 | 31.206 | 34.327 | 0.80 | 1.00 | 12.41 | 0.000 | 0.000 | 681.48 | 0.00 | 0.00 | 71.28 |
| 135.0 | Round Low Profile PI | 1 | 31.684 | 34.853 | 1.00 | 1.00 | 21.70 | 0.000 | 0.000 | 1,210.09 | 0.00 | 0.00 | 1,350.00 |
| 135.0 | Antel BXA-171063-12B | 3 | 31.884 | 35.072 | 0.88 | 0.80 | 9.99 | 0.000 | 3.000 | 560.58 | 0.00 | 1,681.75 | 40.50 |
| 135.0 | Antel BXA-70063-6CF- | 3 | 31.884 | 35.072 | 0.77 | 0.80 | 13.99 | 0.000 | 3.000 | 785.03 | 0.00 | 2,355.08 | 45.90 |
| 135.0 | RFS FD9R6004/2C-3L | 6 | 31.884 | 35.072 | 0.50 | 0.80 | 0.89 | 0.000 | 3.000 | 49.83 | 0.00 | 149.49 | 14.04 |
| 135.0 | Antel BXA-80063-6BF- | 3 | 31.884 | 35.072 | 0.78 | 0.80 | 13.59 | 0.000 | 3.000 | 762.66 | 0.00 | 2,287.97 | 51.84 |
| 135.0 | Antel BXA-171063-8BF | 3 | 31.884 | 35.072 | 0.87 | 0.80 | 6.14 | 0.000 | 3.000 | 344.48 | 0.00 | 1,033.44 | 28.35 |
| 135.0 | Alcatel-Lucent RRH2x | 3 | 31.884 | 35.072 | 0.67 | 0.80 | 3.49 | 0.000 | 3.000 | 196.07 | 0.00 | 588.21 | 118.80 |
| 135.0 | RFS DB-T1-6Z-8AB-OZ | 1 | 31.884 | 35.072 | 1.00 | 0.80 | 3.84 | 0.000 | 3.000 | 215.48 | 0.00 | 646.45 | 39.60 |
| 135.0 | Alcatel-Lucent RRH2x | 3 | 31.884 | 35.072 | 0.67 | 0.80 | 3.41 | 0.000 | 3.000 | 191.30 | 0.00 | 573.89 | 135.00 |
| 148.0 | T-Arm w/ Working Pla | 3 | 32.528 | 35.780 | 0.67 | 0.75 | 19.45 | 0.000 | 0.000 | 1,113.30 | 0.00 | 0.00 | 675.00 |
| 148.0 | Ericsson KRY 112 144 | 3 | 32.528 | 35.780 | 0.50 | 0.80 | 0.49 | 0.000 | 0.000 | 28.17 | 0.00 | 0.00 | 29.70 |
| 148.0 | Ericsson AIR 21, 1,3 | 3 | 32.528 | 35.780 | 0.86 | 0.80 | 12.49 | 0.000 | 0.000 | 714.88 | 0.00 | 0.00 | 224.10 |
| 148.0 | Ericsson AIR 21, 1,3 | 3 | 32.528 | 35.780 | 0.85 | 0.80 | 12.42 | 0.000 | 0.000 | 711.24 | 0.00 | 0.00 | 220.05 |
| 160.0 | Powerwave 7020 | 3 | 33.260 | 36.586 | 0.33 | 0.75 | 0.30 | 0.000 | 0.000 | 17.39 | 0.00 | 0.00 | 5.94 |
| 160.0 | 14" x 9" TTA | 6 | 33.260 | 36.586 | 0.33 | 0.75 | 1.56 | 0.000 | 0.000 | 91.28 | 0.00 | 0.00 | 54.00 |
| 160.0 | Raycap DC6-48-60-18- | 3 | 33.260 | 36.586 | 1.00 | 0.75 | 2.50 | 0.000 | 0.000 | 146.20 | 0.00 | 0.00 | 54.00 |
| 160.0 | CCI | 3 | 33.260 | 36.586 | 0.50 | 0.75 | 1.54 | 0.000 | 0.000 | 90.22 | 0.00 | 0.00 | 51.84 |
| 160.0 | Ericsson RRUS A2 | 6 | 33.260 | 36.586 | 0.67 | 0.75 | 6.21 | 0.000 | 0.000 | 363.58 | 0.00 | 0.00 | 118.80 |
| 160.0 | Ericsson RRUS 11 (Ba | 6 | 33.260 | 36.586 | 0.67 | 0.75 | 8.41 | 0.000 | 0.000 | 492.42 | 0.00 | 0.00 | 273.78 |
| 160.0 | Ericsson RRUS-12 B2 | 6 | 33.260 | 36.586 | 0.67 | 0.75 | 9.50 | 0.000 | 0.000 | 555.95 | 0.00 | 0.00 | 313.20 |
| 160.0 | Ericsson RRUS E2 B29 | 3 | 33.260 | 36.586 | 0.67 | 0.75 | 4.75 | 0.000 | 0.000 | 277.98 | 0.00 | 0.00 | 162.00 |
| 160.0 | Ericsson RRUS-32 | 3 | 33.260 | 36.586 | 0.67 | 0.75 | 4.99 | 0.000 | 0.000 | 292.10 | 0.00 | 0.00 | 207.90 |
| 160.0 | Powerwave 7770.00 | 3 | 33.260 | 36.586 | 0.77 | 0.75 | 9.55 | 0.000 | 0.000 | 558.81 | 0.00 | 0.00 | 94.50 |
| 160.0 | CCI HPA-65R-BUU-H6 | 9 | 33.260 | 36.586 | 0.83 | 0.75 | 54.12 | 0.000 | 0.000 | 3,168.10 | 0.00 | 0.00 | 413.10 |
| 160.0 | Flat Platform w/ Han | 1 | 33.260 | 36.586 | 1.00 | 1.00 | 42.40 | 0.000 | 0.000 | 2,482.02 | 0.00 | 0.00 | 1,800.00 |
| 171.0 | Side Arms | 1 | 33.898 | 37.288 | 1.00 | 1.00 | 8.50 | 0.000 | 0.000 | 507.12 | 0.00 | 0.00 | 504.00 |
| 171.0 | DragonWave A-ANT- | 1 | 33.898 | 37.288 | 1.00 | 0.80 | 3.75 | 0.000 | 0.000 | 223.85 | 0.00 | 0.00 | 24.30 |
| 171.0 | NextNet BTS-2500 | 3 | 33.898 | 37.288 | 0.50 | 0.80 | 2.18 | 0.000 | 0.000 | 130.30 | 0.00 | 0.00 | 94.50 |
| 171.0 | Argus LLPX310R | 3 | 33.898 | 37.288 | 0.73 | 0.80 | 7.52 | 0.000 | 0.000 | 448.42 | 0.00 | 0.00 | 77.22 |
| 171.0 | DragonWave Horizon | 2 | 33.898 | 37.288 | 0.33 | 0.80 | 0.23 | 0.000 | 0.000 | 13.55 | 0.00 | 0.00 | 19.08 |
| 171.0 | DragonWave A-ANT- | 1 | 33.898 | 37.288 | 1.00 | 0.80 | 3.75 | 0.000 | 0.000 | 223.85 | 0.00 | 0.00 | 24.39 |
| 178.5 | 72" x 12" Panel | 3 | 34.453 | 37.899 | 0.79 | 0.80 | 15.41 | 0.000 | 2.500 | 934.70 | 0.00 | 2,336.75 | 121.50 |
| 178.5 | 48" x 12" Panel | 9 | 34.453 | 37.899 | 0.78 | 0.80 | 28.47 | 0.000 | 2.500 | 1,726.54 | 0.00 | 4,316.36 | 243.00 |
| 178.5 | Flat Low Profile Pla | 1 | 34.317 | 37.748 | 1.00 | 1.00 | 26.10 | 0.000 | 0.000 | 1,576.37 | 0.00 | 0.00 | 1,350.00 |
| | | | | | | | | | | 25,565.39 | | | 11,234.52 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)



© 2007 - 2014 by ATC IP LLC. All rights reserved.

Load Case: 0.9D + 1.6W 110.00 mph with No Ice (Reduced DL) 23 Iterations

Gust Response Factor : 1.10 Wind Importance Factor : 1.00

Dead Load Factor : 0.90


Wind Load Factor : 1.60

Linear Appurtenance Segment Forces (Factored)

| Seg Top Elev (ft) | Description | Exposed To Wind | Length (ft) | Ca | Exposed Width (in) | Area (sqft) | CaAa (sqft) | qz (psf) | Ra | Cf Adjust Factor | FX (lb) | Dead Load (lb) |
|-------------------|----------------------|-----------------|-------------|-------|--------------------|-------------|-------------|----------|-------|------------------|---------|----------------|
| 5.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.130 | 1.090 | 0.00 | 1.35 |
| 5.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 20.599 | 0.130 | 1.090 | 0.00 | 32.85 |
| 5.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 20.599 | 0.130 | 1.090 | 0.00 | 22.14 |
| 5.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.130 | 1.090 | 0.00 | 11.07 |
| 5.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 20.599 | 0.130 | 1.090 | 0.00 | 22.14 |
| 5.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 20.599 | 0.130 | 1.090 | 0.00 | 4.50 |
| 5.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 20.599 | 0.130 | 1.090 | 0.00 | 13.50 |
| 5.00 | (1) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.130 | 1.090 | 0.00 | 0.68 |
| 10.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.132 | 1.097 | 0.00 | 1.35 |
| 10.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 20.599 | 0.132 | 1.097 | 0.00 | 32.85 |
| 10.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 20.599 | 0.132 | 1.097 | 0.00 | 22.14 |
| 10.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.132 | 1.097 | 0.00 | 11.07 |
| 10.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 20.599 | 0.132 | 1.097 | 0.00 | 22.14 |
| 10.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 20.599 | 0.132 | 1.097 | 0.00 | 4.50 |
| 10.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 20.599 | 0.132 | 1.097 | 0.00 | 13.50 |
| 10.00 | (1) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.132 | 1.097 | 0.00 | 0.68 |
| 15.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.135 | 1.105 | 0.00 | 1.35 |
| 15.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 20.599 | 0.135 | 1.105 | 0.00 | 32.85 |
| 15.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 20.599 | 0.135 | 1.105 | 0.00 | 22.14 |
| 15.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.135 | 1.105 | 0.00 | 11.07 |
| 15.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 20.599 | 0.135 | 1.105 | 0.00 | 22.14 |
| 15.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 20.599 | 0.135 | 1.105 | 0.00 | 4.50 |
| 15.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 20.599 | 0.135 | 1.105 | 0.00 | 13.50 |
| 15.00 | (1) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.135 | 1.105 | 0.00 | 0.68 |
| 20.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.137 | 1.112 | 0.00 | 1.35 |
| 20.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 20.599 | 0.137 | 1.112 | 0.00 | 32.85 |
| 20.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 20.599 | 0.137 | 1.112 | 0.00 | 22.14 |
| 20.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.137 | 1.112 | 0.00 | 11.07 |
| 20.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 20.599 | 0.137 | 1.112 | 0.00 | 22.14 |
| 20.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 20.599 | 0.137 | 1.112 | 0.00 | 4.50 |
| 20.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 20.599 | 0.137 | 1.112 | 0.00 | 13.50 |
| 20.00 | (1) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.137 | 1.112 | 0.00 | 0.68 |
| 25.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.140 | 1.120 | 0.00 | 1.35 |
| 25.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 20.599 | 0.140 | 1.120 | 0.00 | 32.85 |
| 25.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 20.599 | 0.140 | 1.120 | 0.00 | 22.14 |
| 25.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.599 | 0.140 | 1.120 | 0.00 | 11.07 |
| 25.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 20.599 | 0.140 | 1.120 | 0.00 | 22.14 |
| 25.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 20.599 | 0.140 | 1.120 | 0.00 | 4.50 |
| 25.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 20.599 | 0.140 | 1.120 | 0.00 | 13.50 |
| 30.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.616 | 0.143 | 1.128 | 0.00 | 1.35 |
| 30.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 20.616 | 0.143 | 1.128 | 0.00 | 32.85 |
| 30.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 20.616 | 0.143 | 1.128 | 0.00 | 22.14 |
| 30.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 20.616 | 0.143 | 1.128 | 0.00 | 11.07 |
| 30.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 20.616 | 0.143 | 1.128 | 0.00 | 22.14 |
| 30.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 20.616 | 0.143 | 1.128 | 0.00 | 4.50 |
| 30.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 20.616 | 0.143 | 1.128 | 0.00 | 13.50 |
| 35.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 21.545 | 0.145 | 1.136 | 0.00 | 1.35 |
| 35.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 21.545 | 0.145 | 1.136 | 0.00 | 32.85 |
| 35.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 21.545 | 0.145 | 1.136 | 0.00 | 22.14 |
| 35.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 21.545 | 0.145 | 1.136 | 0.00 | 11.07 |
| 35.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 21.545 | 0.145 | 1.136 | 0.00 | 22.14 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)




| | | |
|-------------------------------|-------------------------------------|-------------------------------|
| Load Case: 0.9D + 1.6W | 110.00 mph with No Ice (Reduced DL) | 23 Iterations |
| Gust Response Factor : 1.10 | | Wind Importance Factor : 1.00 |
| Dead Load Factor : 0.90 | | |
| Wind Load Factor : 1.60 | | |

| | | | | | | | | | | | | |
|-------|----------------------|-----|------|-------|------|------|------|--------|-------|-------|------|-------|
| 35.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 21.545 | 0.145 | 1.136 | 0.00 | 4.50 |
| 35.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 21.545 | 0.145 | 1.136 | 0.00 | 13.50 |
| 40.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 22.383 | 0.148 | 1.145 | 0.00 | 1.35 |
| 40.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 22.383 | 0.148 | 1.145 | 0.00 | 32.85 |
| 40.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 22.383 | 0.148 | 1.145 | 0.00 | 22.14 |
| 40.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 22.383 | 0.148 | 1.145 | 0.00 | 11.07 |
| 40.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 22.383 | 0.148 | 1.145 | 0.00 | 22.14 |
| 40.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 22.383 | 0.148 | 1.145 | 0.00 | 4.50 |
| 40.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 22.383 | 0.148 | 1.145 | 0.00 | 13.50 |
| 45.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 23.149 | 0.151 | 1.154 | 0.00 | 1.35 |
| 45.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 23.149 | 0.151 | 1.154 | 0.00 | 32.85 |
| 45.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 23.149 | 0.151 | 1.154 | 0.00 | 22.14 |
| 45.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 23.149 | 0.151 | 1.154 | 0.00 | 11.07 |
| 45.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 23.149 | 0.151 | 1.154 | 0.00 | 22.14 |
| 45.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 23.149 | 0.151 | 1.154 | 0.00 | 4.50 |
| 45.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 23.149 | 0.151 | 1.154 | 0.00 | 13.50 |
| 50.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 23.856 | 0.155 | 1.164 | 0.00 | 1.35 |
| 50.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 23.856 | 0.155 | 1.164 | 0.00 | 32.85 |
| 50.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 23.856 | 0.155 | 1.164 | 0.00 | 22.14 |
| 50.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 23.856 | 0.155 | 1.164 | 0.00 | 11.07 |
| 50.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 23.856 | 0.155 | 1.164 | 0.00 | 22.14 |
| 50.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 23.856 | 0.155 | 1.164 | 0.00 | 4.50 |
| 50.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 23.856 | 0.155 | 1.164 | 0.00 | 13.50 |
| 53.00 | (2) 1/2" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 24.257 | 0.157 | 1.172 | 0.00 | 0.81 |
| 53.00 | (2) 2" Conduit | Yes | 3.00 | 0.000 | 2.38 | 0.60 | 0.00 | 24.257 | 0.157 | 1.172 | 0.00 | 19.71 |
| 53.00 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 0.50 | 0.00 | 24.257 | 0.157 | 1.172 | 0.00 | 13.28 |
| 53.00 | (3) 1 5/8" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 24.257 | 0.157 | 1.172 | 0.00 | 6.64 |
| 53.00 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 0.50 | 0.00 | 24.257 | 0.157 | 1.172 | 0.00 | 13.28 |
| 53.00 | (1) 1 1/4" Hybriflex | Yes | 3.00 | 0.000 | 1.54 | 0.38 | 0.00 | 24.257 | 0.157 | 1.172 | 0.00 | 2.70 |
| 53.00 | (3) 1 1/4" Hybriflex | Yes | 3.00 | 0.000 | 1.55 | 0.39 | 0.00 | 24.257 | 0.157 | 1.172 | 0.00 | 8.10 |
| 55.00 | (2) 1/2" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 24.515 | 0.157 | 1.171 | 0.00 | 0.54 |
| 55.00 | (2) 2" Conduit | Yes | 2.00 | 0.000 | 2.38 | 0.40 | 0.00 | 24.515 | 0.157 | 1.171 | 0.00 | 13.14 |
| 55.00 | (6) 1 5/8" Coax | Yes | 2.00 | 0.000 | 1.98 | 0.33 | 0.00 | 24.515 | 0.157 | 1.171 | 0.00 | 8.85 |
| 55.00 | (3) 1 5/8" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 24.515 | 0.157 | 1.171 | 0.00 | 4.43 |
| 55.00 | (6) 1 5/8" Coax | Yes | 2.00 | 0.000 | 1.98 | 0.33 | 0.00 | 24.515 | 0.157 | 1.171 | 0.00 | 8.85 |
| 55.00 | (1) 1 1/4" Hybriflex | Yes | 2.00 | 0.000 | 1.54 | 0.26 | 0.00 | 24.515 | 0.157 | 1.171 | 0.00 | 1.80 |
| 55.00 | (3) 1 1/4" Hybriflex | Yes | 2.00 | 0.000 | 1.55 | 0.26 | 0.00 | 24.515 | 0.157 | 1.171 | 0.00 | 5.40 |
| 60.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 25.132 | 0.159 | 1.178 | 0.00 | 1.35 |
| 60.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 25.132 | 0.159 | 1.178 | 0.00 | 32.85 |
| 60.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 25.132 | 0.159 | 1.178 | 0.00 | 22.14 |
| 60.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 25.132 | 0.159 | 1.178 | 0.00 | 11.07 |
| 60.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 25.132 | 0.159 | 1.178 | 0.00 | 22.14 |
| 60.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 25.132 | 0.159 | 1.178 | 0.00 | 4.50 |
| 60.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 25.132 | 0.159 | 1.178 | 0.00 | 13.50 |
| 65.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 25.713 | 0.163 | 1.188 | 0.00 | 1.35 |
| 65.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 25.713 | 0.163 | 1.188 | 0.00 | 32.85 |
| 65.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 25.713 | 0.163 | 1.188 | 0.00 | 22.14 |
| 65.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 25.713 | 0.163 | 1.188 | 0.00 | 11.07 |
| 65.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 25.713 | 0.163 | 1.188 | 0.00 | 22.14 |
| 65.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 25.713 | 0.163 | 1.188 | 0.00 | 4.50 |
| 65.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 25.713 | 0.163 | 1.188 | 0.00 | 13.50 |
| 70.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 26.263 | 0.166 | 1.199 | 0.00 | 1.35 |
| 70.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 26.263 | 0.166 | 1.199 | 0.00 | 32.85 |
| 70.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 26.263 | 0.166 | 1.199 | 0.00 | 22.14 |
| 70.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 26.263 | 0.166 | 1.199 | 0.00 | 11.07 |
| 70.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 26.263 | 0.166 | 1.199 | 0.00 | 22.14 |
| 70.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 26.263 | 0.166 | 1.199 | 0.00 | 4.50 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)



6/13/2014 11:15:46 AM

Page: 17

© 2007 - 2014 by ATC IP LLC. All rights reserved.


Load Case: 0.9D + 1.6W **110.00 mph with No Ice (Reduced DL)** **23 Iterations**

Gust Response Factor : 1.10 Wind Importance Factor : 1.00
 Dead Load Factor : 0.90
 Wind Load Factor : 1.60

| | | | | | | | | | | | | |
|-------|----------------------|-----|------|-------|------|------|------|--------|-------|-------|------|-------|
| 70.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 26.263 | 0.166 | 1.199 | 0.00 | 13.50 |
| 75.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 26.786 | 0.170 | 1.211 | 0.00 | 1.35 |
| 75.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 26.786 | 0.170 | 1.211 | 0.00 | 32.85 |
| 75.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 26.786 | 0.170 | 1.211 | 0.00 | 22.14 |
| 75.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 26.786 | 0.170 | 1.211 | 0.00 | 11.07 |
| 75.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 26.786 | 0.170 | 1.211 | 0.00 | 22.14 |
| 75.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 26.786 | 0.170 | 1.211 | 0.00 | 4.50 |
| 75.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 26.786 | 0.170 | 1.211 | 0.00 | 13.50 |
| 80.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 27.285 | 0.174 | 1.223 | 0.00 | 1.35 |
| 80.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 27.285 | 0.174 | 1.223 | 0.00 | 32.85 |
| 80.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 27.285 | 0.174 | 1.223 | 0.00 | 22.14 |
| 80.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 27.285 | 0.174 | 1.223 | 0.00 | 11.07 |
| 80.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 27.285 | 0.174 | 1.223 | 0.00 | 22.14 |
| 80.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 27.285 | 0.174 | 1.223 | 0.00 | 4.50 |
| 80.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 27.285 | 0.174 | 1.223 | 0.00 | 13.50 |
| 85.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 27.761 | 0.179 | 1.236 | 0.00 | 1.35 |
| 85.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 27.761 | 0.179 | 1.236 | 0.00 | 32.85 |
| 85.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 27.761 | 0.179 | 1.236 | 0.00 | 22.14 |
| 85.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 27.761 | 0.179 | 1.236 | 0.00 | 11.07 |
| 85.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 27.761 | 0.179 | 1.236 | 0.00 | 22.14 |
| 85.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 27.761 | 0.179 | 1.236 | 0.00 | 4.50 |
| 85.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 27.761 | 0.179 | 1.236 | 0.00 | 13.50 |
| 90.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 28.219 | 0.183 | 1.249 | 0.00 | 1.35 |
| 90.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 28.219 | 0.183 | 1.249 | 0.00 | 32.85 |
| 90.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 28.219 | 0.183 | 1.249 | 0.00 | 22.14 |
| 90.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 28.219 | 0.183 | 1.249 | 0.00 | 11.07 |
| 90.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 28.219 | 0.183 | 1.249 | 0.00 | 22.14 |
| 90.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 28.219 | 0.183 | 1.249 | 0.00 | 4.50 |
| 90.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 28.219 | 0.183 | 1.249 | 0.00 | 13.50 |
| 91.42 | (2) 1/2" Coax | Yes | 1.42 | 0.000 | 0.00 | 0.00 | 0.00 | 28.345 | 0.186 | 1.258 | 0.00 | 0.38 |
| 91.42 | (2) 2" Conduit | Yes | 1.42 | 0.000 | 2.38 | 0.28 | 0.00 | 28.345 | 0.186 | 1.258 | 0.00 | 9.31 |
| 91.42 | (6) 1 5/8" Coax | Yes | 1.42 | 0.000 | 1.98 | 0.23 | 0.00 | 28.345 | 0.186 | 1.258 | 0.00 | 6.27 |
| 91.42 | (3) 1 5/8" Coax | Yes | 1.42 | 0.000 | 0.00 | 0.00 | 0.00 | 28.345 | 0.186 | 1.258 | 0.00 | 3.14 |
| 91.42 | (6) 1 5/8" Coax | Yes | 1.42 | 0.000 | 1.98 | 0.23 | 0.00 | 28.345 | 0.186 | 1.258 | 0.00 | 6.27 |
| 91.42 | (1) 1 1/4" Hybriflex | Yes | 1.42 | 0.000 | 1.54 | 0.18 | 0.00 | 28.345 | 0.186 | 1.258 | 0.00 | 1.28 |
| 91.42 | (3) 1 1/4" Hybriflex | Yes | 1.42 | 0.000 | 1.55 | 0.18 | 0.00 | 28.345 | 0.186 | 1.258 | 0.00 | 3.83 |
| 95.00 | (2) 1/2" Coax | Yes | 3.58 | 0.000 | 0.00 | 0.00 | 0.00 | 28.658 | 0.188 | 1.265 | 0.00 | 0.97 |
| 95.00 | (2) 2" Conduit | Yes | 3.58 | 0.000 | 2.38 | 0.71 | 0.00 | 28.658 | 0.188 | 1.265 | 0.00 | 23.54 |
| 95.00 | (6) 1 5/8" Coax | Yes | 3.58 | 0.000 | 1.98 | 0.59 | 0.00 | 28.658 | 0.188 | 1.265 | 0.00 | 15.87 |
| 95.00 | (3) 1 5/8" Coax | Yes | 3.58 | 0.000 | 0.00 | 0.00 | 0.00 | 28.658 | 0.188 | 1.265 | 0.00 | 7.93 |
| 95.00 | (6) 1 5/8" Coax | Yes | 3.58 | 0.000 | 1.98 | 0.59 | 0.00 | 28.658 | 0.188 | 1.265 | 0.00 | 15.87 |
| 95.00 | (1) 1 1/4" Hybriflex | Yes | 3.58 | 0.000 | 1.54 | 0.46 | 0.00 | 28.658 | 0.188 | 1.265 | 0.00 | 3.22 |
| 95.00 | (3) 1 1/4" Hybriflex | Yes | 3.58 | 0.000 | 1.55 | 0.46 | 0.00 | 28.658 | 0.188 | 1.265 | 0.00 | 9.67 |
| 98.00 | (2) 1/2" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 28.913 | 0.192 | 1.275 | 0.00 | 0.81 |
| 98.00 | (2) 2" Conduit | Yes | 3.00 | 0.000 | 2.38 | 0.60 | 0.00 | 28.913 | 0.192 | 1.275 | 0.00 | 19.71 |
| 98.00 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 0.50 | 0.00 | 28.913 | 0.192 | 1.275 | 0.00 | 13.28 |
| 98.00 | (3) 1 5/8" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 28.913 | 0.192 | 1.275 | 0.00 | 6.64 |
| 98.00 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 0.50 | 0.00 | 28.913 | 0.192 | 1.275 | 0.00 | 13.28 |
| 98.00 | (1) 1 1/4" Hybriflex | Yes | 3.00 | 0.000 | 1.54 | 0.38 | 0.00 | 28.913 | 0.192 | 1.275 | 0.00 | 2.70 |
| 98.00 | (3) 1 1/4" Hybriflex | Yes | 3.00 | 0.000 | 1.55 | 0.39 | 0.00 | 28.913 | 0.192 | 1.275 | 0.00 | 8.10 |
| 100.0 | (2) 1/2" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 29.081 | 0.192 | 1.275 | 0.00 | 0.54 |
| 100.0 | (2) 2" Conduit | Yes | 2.00 | 0.000 | 2.38 | 0.40 | 0.00 | 29.081 | 0.192 | 1.275 | 0.00 | 13.14 |
| 100.0 | (6) 1 5/8" Coax | Yes | 2.00 | 0.000 | 1.98 | 0.33 | 0.00 | 29.081 | 0.192 | 1.275 | 0.00 | 8.85 |
| 100.0 | (3) 1 5/8" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 29.081 | 0.192 | 1.275 | 0.00 | 4.43 |
| 100.0 | (6) 1 5/8" Coax | Yes | 2.00 | 0.000 | 1.98 | 0.33 | 0.00 | 29.081 | 0.192 | 1.275 | 0.00 | 8.85 |
| 100.0 | (1) 1 1/4" Hybriflex | Yes | 2.00 | 0.000 | 1.54 | 0.26 | 0.00 | 29.081 | 0.192 | 1.275 | 0.00 | 1.80 |
| 100.0 | (3) 1 1/4" Hybriflex | Yes | 2.00 | 0.000 | 1.55 | 0.26 | 0.00 | 29.081 | 0.192 | 1.275 | 0.00 | 5.40 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)



Load Case: 0.9D + 1.6W 110.00 mph with No Ice (Reduced DL) 23 Iterations

Gust Response Factor : 1.10 Wind Importance Factor : 1.00


Dead Load Factor : 0.90

Wind Load Factor : 1.60

| | | | | | | | | | | | | |
|-------|----------------------|-----|------|-------|------|------|------|--------|-------|-------|-------|-------|
| 105.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 29.489 | 0.195 | 1.285 | 0.00 | 1.35 |
| 105.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 29.489 | 0.195 | 1.285 | 0.00 | 32.85 |
| 105.0 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 29.489 | 0.195 | 1.285 | 0.00 | 22.14 |
| 105.0 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 29.489 | 0.195 | 1.285 | 0.00 | 11.07 |
| 105.0 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 29.489 | 0.195 | 1.285 | 0.00 | 22.14 |
| 105.0 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 29.489 | 0.195 | 1.285 | 0.00 | 4.50 |
| 105.0 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 29.489 | 0.195 | 1.285 | 0.00 | 13.50 |
| 110.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 29.884 | 0.200 | 0.000 | 0.00 | 1.35 |
| 110.0 | (2) 2" Conduit | Yes | 5.00 | 1.200 | 2.38 | 0.99 | 1.19 | 29.884 | 0.200 | 0.000 | 62.59 | 32.85 |
| 110.0 | (6) 1 5/8" Coax | Yes | 5.00 | 1.200 | 1.98 | 0.82 | 0.99 | 29.884 | 0.200 | 0.000 | 52.07 | 22.14 |
| 110.0 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 29.884 | 0.200 | 0.000 | 0.00 | 11.07 |
| 110.0 | (6) 1 5/8" Coax | Yes | 5.00 | 1.200 | 1.98 | 0.82 | 0.99 | 29.884 | 0.200 | 0.000 | 52.07 | 22.14 |
| 110.0 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 1.200 | 1.54 | 0.64 | 0.77 | 29.884 | 0.200 | 0.000 | 40.50 | 4.50 |
| 110.0 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 1.200 | 1.55 | 0.65 | 0.77 | 29.884 | 0.200 | 0.000 | 40.76 | 13.50 |
| 115.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 30.266 | 0.206 | 0.000 | 0.00 | 1.35 |
| 115.0 | (2) 2" Conduit | Yes | 5.00 | 1.200 | 2.38 | 0.99 | 1.19 | 30.266 | 0.206 | 0.000 | 63.39 | 32.85 |
| 115.0 | (6) 1 5/8" Coax | Yes | 5.00 | 1.200 | 1.98 | 0.82 | 0.99 | 30.266 | 0.206 | 0.000 | 52.73 | 22.14 |
| 115.0 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 30.266 | 0.206 | 0.000 | 0.00 | 11.07 |
| 115.0 | (6) 1 5/8" Coax | Yes | 5.00 | 1.200 | 1.98 | 0.82 | 0.99 | 30.266 | 0.206 | 0.000 | 52.73 | 22.14 |
| 115.0 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 1.200 | 1.54 | 0.64 | 0.77 | 30.266 | 0.206 | 0.000 | 41.02 | 4.50 |
| 115.0 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 1.200 | 1.55 | 0.65 | 0.77 | 30.266 | 0.206 | 0.000 | 41.28 | 13.50 |
| 116.0 | (2) 1/2" Coax | Yes | 1.00 | 0.000 | 0.00 | 0.00 | 0.00 | 30.341 | 0.209 | 0.000 | 0.00 | 0.27 |
| 116.0 | (2) 2" Conduit | Yes | 1.00 | 1.200 | 2.38 | 0.20 | 0.24 | 30.341 | 0.209 | 0.000 | 12.71 | 6.57 |
| 116.0 | (6) 1 5/8" Coax | Yes | 1.00 | 1.200 | 1.98 | 0.17 | 0.20 | 30.341 | 0.209 | 0.000 | 10.57 | 4.43 |
| 116.0 | (3) 1 5/8" Coax | Yes | 1.00 | 0.000 | 0.00 | 0.00 | 0.00 | 30.341 | 0.209 | 0.000 | 0.00 | 2.21 |
| 116.0 | (6) 1 5/8" Coax | Yes | 1.00 | 1.200 | 1.98 | 0.17 | 0.20 | 30.341 | 0.209 | 0.000 | 10.57 | 4.43 |
| 116.0 | (1) 1 1/4" Hybriflex | Yes | 1.00 | 1.200 | 1.54 | 0.13 | 0.15 | 30.341 | 0.209 | 0.000 | 8.22 | 0.90 |
| 116.0 | (3) 1 1/4" Hybriflex | Yes | 1.00 | 1.200 | 1.55 | 0.13 | 0.16 | 30.341 | 0.209 | 0.000 | 8.28 | 2.70 |
| 120.0 | (2) 1/2" Coax | Yes | 4.00 | 0.000 | 0.00 | 0.00 | 0.00 | 30.636 | 0.143 | 1.129 | 0.00 | 1.08 |
| 120.0 | (2) 2" Conduit | Yes | 4.00 | 0.000 | 2.38 | 0.79 | 0.00 | 30.636 | 0.143 | 1.129 | 0.00 | 26.28 |
| 120.0 | (6) 1 5/8" Coax | Yes | 4.00 | 0.000 | 1.98 | 0.66 | 0.00 | 30.636 | 0.143 | 1.129 | 0.00 | 17.71 |
| 120.0 | (3) 1 5/8" Coax | Yes | 4.00 | 0.000 | 0.00 | 0.00 | 0.00 | 30.636 | 0.143 | 1.129 | 0.00 | 8.85 |
| 120.0 | (6) 1 5/8" Coax | Yes | 4.00 | 0.000 | 1.98 | 0.66 | 0.00 | 30.636 | 0.143 | 1.129 | 0.00 | 17.71 |
| 125.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 30.995 | 0.147 | 1.140 | 0.00 | 1.35 |
| 125.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 30.995 | 0.147 | 1.140 | 0.00 | 32.85 |
| 125.0 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 30.995 | 0.147 | 1.140 | 0.00 | 22.14 |
| 125.0 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 30.995 | 0.147 | 1.140 | 0.00 | 11.07 |
| 125.0 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 30.995 | 0.147 | 1.140 | 0.00 | 22.14 |
| 128.0 | (2) 1/2" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 31.206 | 0.150 | 1.151 | 0.00 | 0.81 |
| 128.0 | (2) 2" Conduit | Yes | 3.00 | 0.000 | 2.38 | 0.60 | 0.00 | 31.206 | 0.150 | 1.151 | 0.00 | 19.71 |
| 128.0 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 0.50 | 0.00 | 31.206 | 0.150 | 1.151 | 0.00 | 13.28 |
| 128.0 | (3) 1 5/8" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 31.206 | 0.150 | 1.151 | 0.00 | 6.64 |
| 128.0 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 0.50 | 0.00 | 31.206 | 0.150 | 1.151 | 0.00 | 13.28 |
| 130.0 | (2) 1/2" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 31.345 | 0.105 | 1.015 | 0.00 | 0.54 |
| 130.0 | (2) 2" Conduit | Yes | 2.00 | 0.000 | 2.38 | 0.40 | 0.00 | 31.345 | 0.105 | 1.015 | 0.00 | 13.14 |
| 130.0 | (6) 1 5/8" Coax | Yes | 2.00 | 0.000 | 1.98 | 0.33 | 0.00 | 31.345 | 0.105 | 1.015 | 0.00 | 8.85 |
| 130.0 | (3) 1 5/8" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 31.345 | 0.105 | 1.015 | 0.00 | 4.43 |
| 135.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 31.684 | 0.107 | 1.022 | 0.00 | 1.35 |
| 135.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 31.684 | 0.107 | 1.022 | 0.00 | 32.85 |
| 135.0 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 31.684 | 0.107 | 1.022 | 0.00 | 22.14 |
| 135.0 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 31.684 | 0.107 | 1.022 | 0.00 | 11.07 |
| 139.3 | (2) 1/2" Coax | Yes | 4.33 | 0.000 | 0.00 | 0.00 | 0.00 | 31.972 | 0.110 | 1.031 | 0.00 | 1.17 |
| 139.3 | (2) 2" Conduit | Yes | 4.33 | 0.000 | 2.38 | 0.86 | 0.00 | 31.972 | 0.110 | 1.031 | 0.00 | 28.47 |
| 139.3 | (6) 1 5/8" Coax | Yes | 4.33 | 0.000 | 1.98 | 0.72 | 0.00 | 31.972 | 0.110 | 1.031 | 0.00 | 19.19 |
| 140.0 | (2) 1/2" Coax | Yes | 0.67 | 0.000 | 0.00 | 0.00 | 0.00 | 32.015 | 0.112 | 1.037 | 0.00 | 0.18 |
| 140.0 | (2) 2" Conduit | Yes | 0.67 | 0.000 | 2.38 | 0.13 | 0.00 | 32.015 | 0.112 | 1.037 | 0.00 | 4.38 |
| 140.0 | (6) 1 5/8" Coax | Yes | 0.67 | 0.000 | 1.98 | 0.11 | 0.00 | 32.015 | 0.112 | 1.037 | 0.00 | 2.95 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev: 0.000 (ft)



© 2007 - 2014 by ATC IP LLC. All rights reserved.


| | | |
|-------------------------------|-------------------------------------|-------------------------------|
| Load Case: 0.9D + 1.6W | 110.00 mph with No Ice (Reduced DL) | 23 Iterations |
| Gust Response Factor : 1.10 | | Wind Importance Factor : 1.00 |
| Dead Load Factor : 0.90 | | |
| Wind Load Factor : 1.60 | | |

| | | | | | | | | | | | | |
|----------------|-----------------|-----|------|-------|------|------|------|--------|-------|-------|---------------|-----------------|
| 144.4 | (2) 1/2" Coax | Yes | 4.42 | 0.000 | 0.00 | 0.00 | 0.00 | 32.301 | 0.114 | 1.042 | 0.00 | 1.19 |
| 144.4 | (2) 2" Conduit | Yes | 4.42 | 0.000 | 2.38 | 0.88 | 0.00 | 32.301 | 0.114 | 1.042 | 0.00 | 29.02 |
| 144.4 | (6) 1 5/8" Coax | Yes | 4.42 | 0.000 | 1.98 | 0.73 | 0.00 | 32.301 | 0.114 | 1.042 | 0.00 | 19.55 |
| 145.0 | (2) 1/2" Coax | Yes | 0.58 | 0.000 | 0.00 | 0.00 | 0.00 | 32.338 | 0.115 | 1.044 | 0.00 | 0.16 |
| 145.0 | (2) 2" Conduit | Yes | 0.58 | 0.000 | 2.38 | 0.12 | 0.00 | 32.338 | 0.115 | 1.044 | 0.00 | 3.83 |
| 145.0 | (6) 1 5/8" Coax | Yes | 0.58 | 0.000 | 1.98 | 0.10 | 0.00 | 32.338 | 0.115 | 1.044 | 0.00 | 2.58 |
| 148.0 | (2) 1/2" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 32.528 | 0.116 | 1.048 | 0.00 | 0.81 |
| 148.0 | (2) 2" Conduit | Yes | 3.00 | 0.000 | 2.38 | 0.60 | 0.00 | 32.528 | 0.116 | 1.048 | 0.00 | 19.71 |
| 148.0 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 0.50 | 0.00 | 32.528 | 0.116 | 1.048 | 0.00 | 13.28 |
| 150.0 | (2) 1/2" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 32.653 | 0.064 | 0.000 | 0.00 | 0.54 |
| 150.0 | (2) 2" Conduit | Yes | 2.00 | 0.000 | 2.38 | 0.40 | 0.00 | 32.653 | 0.064 | 0.000 | 0.00 | 13.14 |
| 155.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 32.960 | 0.066 | 0.000 | 0.00 | 1.35 |
| 155.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 32.960 | 0.066 | 0.000 | 0.00 | 32.85 |
| 160.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 33.260 | 0.068 | 0.000 | 0.00 | 1.35 |
| 160.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 33.260 | 0.068 | 0.000 | 0.00 | 32.85 |
| 165.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 33.554 | 0.071 | 0.000 | 0.00 | 1.35 |
| 165.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 33.554 | 0.071 | 0.000 | 0.00 | 32.85 |
| 170.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 33.842 | 0.074 | 0.000 | 0.00 | 1.35 |
| 170.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 33.842 | 0.074 | 0.000 | 0.00 | 32.85 |
| 171.0 | (2) 1/2" Coax | Yes | 1.00 | 0.000 | 0.00 | 0.00 | 0.00 | 33.898 | 0.076 | 0.000 | 0.00 | 0.27 |
| 171.0 | (2) 2" Conduit | Yes | 1.00 | 0.000 | 2.38 | 0.20 | 0.00 | 33.898 | 0.076 | 0.000 | 0.00 | 6.57 |
| Totals: | | | | | | | | | | | 549.50 | 3,110.77 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)

6/13/2014 11:15:46 AM
 Page: 20



© 2007 - 2014 by ATC IP LLC. All rights reserved.

Load Case: 0.9D + 1.6W 110.00 mph with No Ice (Reduced DL) 23 Iterations

Gust Response Factor : 1.10 Wind Importance Factor : 1.00

Dead Load Factor : 0.90


Wind Load Factor : 1.60

Applied Segment Forces Summary

| Seg Elev (ft) | Lateral FX (-) (lb) | Axial FY (-) (lb) | Torsion MY (lb-ft) | Moment MZ (lb-ft) |
|----------------|---------------------|-------------------|--------------------|-------------------|
| 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 5.00 | 711.60 | 1,844.42 | 0.00 | 0.00 |
| 10.00 | 699.07 | 1,817.69 | 0.00 | 0.00 |
| 15.00 | 686.53 | 1,790.96 | 0.00 | 0.00 |
| 20.00 | 736.36 | 1,800.78 | 0.00 | 0.00 |
| 25.00 | 661.47 | 1,736.83 | 0.00 | 0.00 |
| 30.00 | 649.48 | 1,710.11 | 0.00 | 0.00 |
| 35.00 | 665.62 | 1,683.38 | 0.00 | 0.00 |
| 40.00 | 677.89 | 1,656.65 | 0.00 | 0.00 |
| 45.00 | 687.00 | 1,629.93 | 0.00 | 0.00 |
| 50.00 | 702.14 | 2,704.60 | 0.00 | 0.00 |
| 53.00 | 421.28 | 1,598.93 | 0.00 | 0.00 |
| 55.00 | 280.86 | 562.85 | 0.00 | 0.00 |
| 60.00 | 709.11 | 1,391.09 | 0.00 | 0.00 |
| 65.00 | 709.87 | 1,368.18 | 0.00 | 0.00 |
| 70.00 | 709.08 | 1,345.27 | 0.00 | 0.00 |
| 75.00 | 706.90 | 1,322.36 | 0.00 | 0.00 |
| 80.00 | 703.45 | 1,299.45 | 0.00 | 0.00 |
| 85.00 | 698.85 | 1,276.54 | 0.00 | 0.00 |
| 90.00 | 693.19 | 1,253.64 | 0.00 | 0.00 |
| 91.42 | 194.15 | 351.03 | 0.00 | 0.00 |
| 95.00 | 496.47 | 1,419.88 | 0.00 | 0.00 |
| 98.00 | 412.41 | 1,172.15 | 0.00 | 0.00 |
| 100.0 | 272.99 | 426.86 | 0.00 | 0.00 |
| 105.0 | 679.50 | 1,053.78 | 0.00 | 0.00 |
| 110.0 | 1,485.67 | 1,034.69 | 0.00 | 0.00 |
| 115.0 | 1,470.66 | 1,015.60 | 0.00 | 0.00 |
| 116.0 | 3,908.51 | 2,347.60 | 0.00 | 2,988.30 |
| 120.0 | 518.52 | 781.28 | 0.00 | 0.00 |
| 125.0 | 638.78 | 959.42 | 0.00 | 0.00 |
| 128.0 | 1,058.24 | 637.77 | 0.00 | 0.00 |
| 130.0 | 248.47 | 364.99 | 0.00 | 0.00 |
| 135.0 | 4,929.94 | 2,723.13 | 0.00 | 9,316.28 |
| 139.3 | 521.60 | 701.15 | 0.00 | 0.00 |
| 140.0 | 80.09 | 168.98 | 0.00 | 0.00 |
| 144.4 | 526.50 | 1,104.11 | 0.00 | 0.00 |
| 145.0 | 68.47 | 78.82 | 0.00 | 0.00 |
| 148.0 | 2,917.52 | 1,550.95 | 0.00 | 0.00 |
| 150.0 | 230.22 | 245.50 | 0.00 | 0.00 |
| 155.0 | 566.92 | 603.06 | 0.00 | 0.00 |
| 160.0 | 9,087.88 | 4,136.85 | 0.00 | 0.00 |
| 165.0 | 536.31 | 477.88 | 0.00 | 0.00 |
| 170.0 | 520.32 | 462.61 | 0.00 | 0.00 |
| 171.0 | 1,648.84 | 834.18 | 0.00 | 0.00 |
| 175.0 | 401.45 | 328.31 | 0.00 | 0.00 |
| 178.5 | 4,579.91 | 1,993.76 | 0.00 | 6,653.11 |
| Totals: | 50,510.07 | 56,768.01 | 0.00 | 18,957.69 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)



Load Case: 0.9D + 1.6W

110.00 mph with No Ice (Reduced DL)

23 Iterations

Gust Response Factor : 1.10
 Dead Load Factor : 0.90
 Wind Load Factor : 1.60


Wind Importance Factor : 1.00

Calculated Forces

| Seg Elev (ft) | Pu FY (-) (kips) | Vu FX (-) (kips) | Tu MY (ft-kips) | Mu MZ (ft-kips) | Mu MX (ft-kips) | Resultant Moment (ft-kips) | phi Pn (kips) | phi Vn (kips) | phi Tn (ft-kips) | phi Mn (ft-kips) | Total Deflect (in) | Rotation (deg) | Ratio |
|---------------|------------------|------------------|-----------------|-----------------|-----------------|----------------------------|---------------|---------------|------------------|------------------|--------------------|----------------|-------|
| 0.00 | -56.71 | -50.58 | 0.00 | -6,251.94 | 0.00 | 6,251.94 | 6,164.54 | 3,082.27 | 18,158.3 | 9,092.69 | 0.00 | 0.00 | 0.697 |
| 5.00 | -54.74 | -50.00 | 0.00 | -5,999.05 | 0.00 | 5,999.05 | 6,108.61 | 3,054.31 | 17,675.6 | 8,850.97 | 0.07 | -0.14 | 0.687 |
| 10.00 | -52.81 | -49.42 | 0.00 | -5,749.08 | 0.00 | 5,749.08 | 6,050.81 | 3,025.41 | 17,193.4 | 8,609.50 | 0.29 | -0.27 | 0.677 |
| 15.00 | -50.90 | -48.84 | 0.00 | -5,502.00 | 0.00 | 5,502.00 | 5,991.14 | 2,995.57 | 16,712.0 | 8,368.43 | 0.65 | -0.41 | 0.666 |
| 20.00 | -48.99 | -48.21 | 0.00 | -5,257.78 | 0.00 | 5,257.78 | 5,929.59 | 2,964.80 | 16,231.6 | 8,127.91 | 1.16 | -0.55 | 0.655 |
| 25.00 | -47.14 | -47.65 | 0.00 | -5,016.72 | 0.00 | 5,016.72 | 5,866.18 | 2,933.09 | 15,752.7 | 7,888.07 | 1.81 | -0.69 | 0.644 |
| 30.00 | -45.32 | -47.09 | 0.00 | -4,778.48 | 0.00 | 4,778.48 | 5,800.89 | 2,900.44 | 15,275.4 | 7,649.08 | 2.61 | -0.84 | 0.633 |
| 35.00 | -43.54 | -46.51 | 0.00 | -4,543.03 | 0.00 | 4,543.03 | 5,733.73 | 2,866.86 | 14,800.1 | 7,411.07 | 3.57 | -0.98 | 0.621 |
| 40.00 | -41.77 | -45.91 | 0.00 | -4,310.49 | 0.00 | 4,310.49 | 5,664.70 | 2,832.35 | 14,327.0 | 7,174.19 | 4.67 | -1.12 | 0.608 |
| 45.00 | -40.04 | -45.29 | 0.00 | -4,080.96 | 0.00 | 4,080.96 | 5,593.79 | 2,796.90 | 13,856.5 | 6,938.58 | 5.93 | -1.27 | 0.596 |
| 50.00 | -37.26 | -44.60 | 0.00 | -3,854.52 | 0.00 | 3,854.52 | 5,521.02 | 2,760.51 | 13,388.9 | 6,704.40 | 7.34 | -1.42 | 0.582 |
| 53.00 | -35.62 | -44.18 | 0.00 | -3,720.72 | 0.00 | 3,720.72 | 4,440.13 | 2,220.06 | 10,789.7 | 5,402.88 | 8.26 | -1.51 | 0.697 |
| 55.00 | -34.98 | -43.96 | 0.00 | -3,632.36 | 0.00 | 3,632.36 | 4,419.76 | 2,209.88 | 10,648.2 | 5,332.01 | 8.90 | -1.57 | 0.690 |
| 60.00 | -33.48 | -43.31 | 0.00 | -3,412.57 | 0.00 | 3,412.57 | 4,367.53 | 2,183.77 | 10,295.0 | 5,155.16 | 10.64 | -1.73 | 0.670 |
| 65.00 | -32.01 | -42.65 | 0.00 | -3,196.04 | 0.00 | 3,196.04 | 4,313.43 | 2,156.72 | 9,942.96 | 4,978.87 | 12.54 | -1.90 | 0.650 |
| 70.00 | -30.57 | -41.98 | 0.00 | -2,982.81 | 0.00 | 2,982.81 | 4,257.46 | 2,128.73 | 9,592.32 | 4,803.29 | 14.62 | -2.07 | 0.629 |
| 75.00 | -29.16 | -41.31 | 0.00 | -2,772.91 | 0.00 | 2,772.91 | 4,199.61 | 2,099.81 | 9,243.38 | 4,628.56 | 16.88 | -2.23 | 0.606 |
| 80.00 | -27.77 | -40.63 | 0.00 | -2,566.37 | 0.00 | 2,566.37 | 4,139.90 | 2,069.95 | 8,896.44 | 4,454.83 | 19.30 | -2.40 | 0.583 |
| 85.00 | -26.41 | -39.95 | 0.00 | -2,363.21 | 0.00 | 2,363.21 | 4,078.31 | 2,039.15 | 8,551.80 | 4,282.26 | 21.90 | -2.56 | 0.559 |
| 90.00 | -25.12 | -39.25 | 0.00 | -2,163.45 | 0.00 | 2,163.45 | 4,014.84 | 2,007.42 | 8,209.74 | 4,110.97 | 24.67 | -2.72 | 0.533 |
| 91.42 | -24.73 | -39.07 | 0.00 | -2,107.84 | 0.00 | 2,107.84 | 3,996.52 | 1,998.26 | 8,113.33 | 4,062.70 | 25.48 | -2.77 | 0.525 |
| 95.00 | -23.26 | -38.55 | 0.00 | -1,967.83 | 0.00 | 1,967.83 | 3,949.51 | 1,974.76 | 7,870.56 | 3,941.13 | 27.61 | -2.88 | 0.506 |
| 98.00 | -22.06 | -38.11 | 0.00 | -1,852.18 | 0.00 | 1,852.18 | 3,056.80 | 1,528.40 | 6,090.92 | 3,049.99 | 29.45 | -2.98 | 0.615 |
| 100.00 | -21.57 | -37.86 | 0.00 | -1,775.97 | 0.00 | 1,775.97 | 3,039.33 | 1,519.67 | 5,992.84 | 3,000.87 | 30.71 | -3.04 | 0.600 |
| 105.00 | -20.44 | -37.18 | 0.00 | -1,586.68 | 0.00 | 1,586.68 | 2,994.36 | 1,497.18 | 5,748.30 | 2,878.42 | 33.99 | -3.21 | 0.559 |
| 110.00 | -19.39 | -35.70 | 0.00 | -1,400.76 | 0.00 | 1,400.76 | 2,947.52 | 1,473.76 | 5,504.94 | 2,756.56 | 37.44 | -3.38 | 0.515 |
| 115.00 | -18.41 | -34.20 | 0.00 | -1,222.28 | 0.00 | 1,222.28 | 2,898.80 | 1,449.40 | 5,263.06 | 2,635.44 | 41.07 | -3.54 | 0.471 |
| 116.00 | -16.27 | -30.17 | 0.00 | -1,185.10 | 0.00 | 1,185.10 | 2,888.83 | 1,444.42 | 5,214.89 | 2,611.32 | 41.82 | -3.57 | 0.460 |
| 120.00 | -15.46 | -29.64 | 0.00 | -1,064.41 | 0.00 | 1,064.41 | 2,848.21 | 1,424.11 | 5,022.95 | 2,515.21 | 44.86 | -3.69 | 0.429 |
| 125.00 | -14.49 | -28.97 | 0.00 | -916.21 | 0.00 | 916.21 | 2,795.75 | 1,397.88 | 4,784.90 | 2,396.01 | 48.80 | -3.83 | 0.388 |
| 128.00 | -13.89 | -27.89 | 0.00 | -829.30 | 0.00 | 829.30 | 2,763.38 | 1,381.69 | 4,643.19 | 2,325.05 | 51.24 | -3.92 | 0.362 |
| 130.00 | -13.50 | -27.63 | 0.00 | -773.53 | 0.00 | 773.53 | 2,741.42 | 1,370.71 | 4,549.21 | 2,277.99 | 52.89 | -3.97 | 0.345 |
| 135.00 | -11.09 | -22.55 | 0.00 | -626.05 | 0.00 | 626.05 | 2,685.21 | 1,342.61 | 4,316.17 | 2,161.29 | 57.11 | -4.09 | 0.294 |
| 139.33 | -10.40 | -21.98 | 0.00 | -528.35 | 0.00 | 528.35 | 2,634.99 | 1,317.49 | 4,116.57 | 2,061.34 | 60.87 | -4.19 | 0.261 |
| 140.00 | -10.22 | -21.90 | 0.00 | -513.69 | 0.00 | 513.69 | 2,627.14 | 1,313.57 | 4,086.07 | 2,046.07 | 61.46 | -4.20 | 0.255 |
| 144.42 | -9.14 | -21.30 | 0.00 | -416.96 | 0.00 | 416.96 | 1,915.99 | 957.99 | 2,941.41 | 1,472.89 | 65.38 | -4.29 | 0.288 |
| 145.00 | -9.05 | -21.23 | 0.00 | -404.54 | 0.00 | 404.54 | 1,911.69 | 955.84 | 2,923.20 | 1,463.77 | 65.91 | -4.30 | 0.282 |
| 148.00 | -7.71 | -18.21 | 0.00 | -340.84 | 0.00 | 340.84 | 1,889.17 | 944.59 | 2,829.77 | 1,416.99 | 68.63 | -4.36 | 0.245 |
| 150.00 | -7.47 | -17.97 | 0.00 | -304.41 | 0.00 | 304.41 | 1,873.79 | 936.89 | 2,767.71 | 1,385.91 | 70.46 | -4.40 | 0.224 |
| 155.00 | -6.89 | -17.37 | 0.00 | -214.54 | 0.00 | 214.54 | 1,834.01 | 917.01 | 2,613.49 | 1,308.69 | 75.11 | -4.48 | 0.168 |
| 160.00 | -3.47 | -7.99 | 0.00 | -127.69 | 0.00 | 127.69 | 1,792.37 | 896.18 | 2,460.85 | 1,232.25 | 79.83 | -4.54 | 0.106 |
| 165.00 | -3.03 | -7.42 | 0.00 | -87.75 | 0.00 | 87.75 | 1,748.85 | 874.42 | 2,310.07 | 1,156.75 | 84.60 | -4.58 | 0.078 |
| 170.00 | -2.61 | -6.86 | 0.00 | -50.66 | 0.00 | 50.66 | 1,703.46 | 851.73 | 2,161.44 | 1,082.33 | 89.40 | -4.61 | 0.048 |
| 171.00 | -1.91 | -5.15 | 0.00 | -43.80 | 0.00 | 43.80 | 1,694.16 | 847.08 | 2,132.00 | 1,067.58 | 90.36 | -4.61 | 0.042 |
| 175.00 | -1.62 | -4.73 | 0.00 | -23.19 | 0.00 | 23.19 | 1,656.20 | 828.10 | 2,015.26 | 1,009.13 | 94.23 | -4.62 | 0.024 |
| 178.50 | 0.00 | -4.58 | 0.00 | -6.65 | 0.00 | 6.65 | 1,622.00 | 811.00 | 1,914.55 | 958.70 | 97.62 | -4.63 | 0.007 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)



© 2007 - 2014 by ATC IP LLC. All rights reserved.

Load Case: 1.2D + 1.0Di + 1.0Wi 50.00 mph with 0.75 in Radial Ice 22 Iterations

Gust Response Factor : 1.10 Ice Dead Load Factor : 1.00 Wind Importance Factor : 1.00
 Dead Load Factor : 1.20 Ice Importance Factor : 1.00
 Wind Load Factor : 1.00


Shaft Segment Forces (Factored)

| Seg Top Elev (ft) | Description | Kzt | Kz | qz (psf) | qzGh (psf) | C (mph-ft) | Cf | Ice Thick (in) | Tributary (ft) | Ap (sf) | EPAs (sf) | Wind Force X (lb) | Dead Load Ice (lb) | Tot Dead Load (lb) |
|-------------------|-----------------|------|------|----------|------------|------------|-------|----------------|----------------|---------|-----------|-------------------|--------------------|--------------------|
| 0.00 | | 1.00 | 0.70 | 4.256 | 4.682 | 0.000 | 1.200 | 0.000 | 0.00 | 0.000 | 0.00 | 0.0 | 0.0 | 0.0 |
| 5.00 | | 1.00 | 0.70 | 4.256 | 4.682 | 0.000 | 1.200 | * 1.242 | 5.00 | 31.232 | 37.48 | 175.5 | 560.1 | 2,571.1 |
| 10.00 | | 1.00 | 0.70 | 4.256 | 4.682 | 0.000 | 1.200 | * 1.331 | 5.00 | 30.774 | 36.93 | 172.9 | 590.6 | 2,565.9 |
| 15.00 | | 1.00 | 0.70 | 4.256 | 4.682 | 0.000 | 1.200 | * 1.386 | 5.00 | 30.288 | 36.35 | 170.2 | 604.6 | 2,544.3 |
| 20.00 | Appertunance(s) | 1.00 | 0.70 | 4.256 | 4.682 | 0.000 | 1.200 | * 1.427 | 5.00 | 29.790 | 35.75 | 167.4 | 611.3 | 2,515.4 |
| 25.00 | | 1.00 | 0.70 | 4.256 | 4.682 | 0.000 | 1.200 | * 1.459 | 5.00 | 29.285 | 35.14 | 164.5 | 613.9 | 2,482.4 |
| 30.00 | | 1.00 | 0.70 | 4.260 | 4.686 | 0.000 | 1.200 | * 1.486 | 5.00 | 28.776 | 34.53 | 161.8 | 613.8 | 2,446.6 |
| 35.00 | | 1.00 | 0.73 | 4.451 | 4.897 | 0.000 | 1.200 | * 1.509 | 5.00 | 28.263 | 33.92 | 166.1 | 611.6 | 2,408.8 |
| 40.00 | | 1.00 | 0.76 | 4.625 | 5.087 | 0.000 | 1.200 | * 1.529 | 5.00 | 27.748 | 33.30 | 169.4 | 608.0 | 2,369.5 |
| 45.00 | Bot - Section 2 | 1.00 | 0.78 | 4.783 | 5.261 | 0.000 | 1.200 | * 1.547 | 5.00 | 27.232 | 32.68 | 171.9 | 603.2 | 2,329.1 |
| 50.00 | | 1.00 | 0.81 | 4.929 | 5.422 | 0.000 | 1.200 | * 1.564 | 5.00 | 27.031 | 32.44 | 175.9 | 604.8 | 3,763.6 |
| 53.00 | Top - Section 1 | 1.00 | 0.82 | 5.012 | 5.513 | 0.000 | 1.200 | * 1.573 | 3.00 | 15.968 | 19.16 | 105.6 | 360.6 | 2,224.1 |
| 55.00 | | 1.00 | 0.83 | 5.065 | 5.572 | 0.000 | 1.200 | * 1.579 | 2.00 | 10.541 | 12.65 | 70.5 | 239.3 | 810.8 |
| 60.00 | | 1.00 | 0.85 | 5.193 | 5.712 | 0.000 | 1.200 | * 1.592 | 5.00 | 25.991 | 31.19 | 178.1 | 591.1 | 1,998.5 |
| 65.00 | | 1.00 | 0.87 | 5.313 | 5.844 | 0.000 | 1.200 | * 1.605 | 5.00 | 25.470 | 30.56 | 178.6 | 583.3 | 1,960.2 |
| 70.00 | | 1.00 | 0.89 | 5.426 | 5.969 | 0.000 | 1.200 | * 1.617 | 5.00 | 24.948 | 29.94 | 178.7 | 575.1 | 1,921.4 |
| 75.00 | | 1.00 | 0.91 | 5.534 | 6.088 | 0.000 | 1.200 | * 1.628 | 5.00 | 24.426 | 29.31 | 178.4 | 566.3 | 1,882.1 |
| 80.00 | | 1.00 | 0.92 | 5.637 | 6.201 | 0.000 | 1.200 | * 1.639 | 5.00 | 23.902 | 28.68 | 177.9 | 557.2 | 1,842.5 |
| 85.00 | | 1.00 | 0.94 | 5.736 | 6.309 | 0.000 | 1.200 | * 1.649 | 5.00 | 23.379 | 28.05 | 177.0 | 547.7 | 1,802.4 |
| 90.00 | | 1.00 | 0.95 | 5.830 | 6.413 | 0.000 | 1.200 | * 1.658 | 5.00 | 22.855 | 27.43 | 175.9 | 537.9 | 1,762.0 |
| 91.42 | Bot - Section 3 | 1.00 | 0.96 | 5.856 | 6.442 | 0.000 | 1.200 | * 1.661 | 1.42 | 6.380 | 7.66 | 49.3 | 151.6 | 492.9 |
| 95.00 | | 1.00 | 0.97 | 5.921 | 6.513 | 0.000 | 1.200 | * 1.667 | 3.58 | 16.139 | 19.37 | 126.1 | 382.9 | 1,955.5 |
| 98.00 | Top - Section 2 | 1.00 | 0.98 | 5.974 | 6.571 | 0.000 | 1.200 | * 1.672 | 3.00 | 13.304 | 15.97 | 104.9 | 316.8 | 1,611.3 |
| 100.0 | | 1.00 | 0.98 | 6.008 | 6.609 | 0.000 | 1.200 | * 1.676 | 2.00 | 8.764 | 10.52 | 69.5 | 209.6 | 599.8 |
| 105.0 | | 1.00 | 1.00 | 6.093 | 6.702 | 0.000 | 1.200 | * 1.684 | 5.00 | 21.545 | 25.85 | 173.3 | 513.3 | 1,471.0 |
| 110.0 | | 1.00 | 1.01 | 6.174 | 6.792 | 0.000 | 1.200 | * 1.692 | 5.00 | 21.020 | 25.22 | 171.3 | 502.4 | 1,434.7 |
| 115.0 | | 1.00 | 1.02 | 6.253 | 6.879 | 0.000 | 1.200 | * 1.699 | 5.00 | 20.495 | 24.59 | 169.2 | 491.4 | 1,398.2 |
| 116.0 | Appertunance(s) | 1.00 | 1.03 | 6.269 | 6.896 | 0.000 | 1.200 | * 1.701 | 1.00 | 4.035 | 4.84 | 33.4 | 97.8 | 276.1 |
| 120.0 | | 1.00 | 1.04 | 6.330 | 6.963 | 0.000 | 1.200 | * 1.707 | 4.00 | 15.932 | 19.12 | 133.1 | 384.1 | 1,087.1 |
| 125.0 | | 1.00 | 1.05 | 6.404 | 7.044 | 0.000 | 1.200 | * 1.714 | 5.00 | 19.443 | 23.33 | 164.4 | 468.6 | 1,324.5 |
| 128.0 | Appertunance(s) | 1.00 | 1.06 | 6.448 | 7.092 | 0.000 | 1.200 | * 1.718 | 3.00 | 11.412 | 13.69 | 97.1 | 277.0 | 778.3 |
| 130.0 | | 1.00 | 1.06 | 6.476 | 7.124 | 0.000 | 1.200 | * 1.720 | 2.00 | 7.503 | 9.00 | 64.1 | 182.8 | 511.9 |
| 135.0 | Appertunance(s) | 1.00 | 1.07 | 6.546 | 7.201 | 0.000 | 1.200 | * 1.727 | 5.00 | 18.390 | 22.07 | 158.9 | 445.2 | 1,250.2 |
| 139.3 | Bot - Section 4 | 1.00 | 1.08 | 6.606 | 7.266 | 0.000 | 1.200 | * 1.732 | 4.33 | 15.512 | 18.61 | 135.3 | 376.8 | 1,053.9 |
| 140.0 | | 1.00 | 1.08 | 6.615 | 7.276 | 0.000 | 1.200 | * 1.733 | 0.67 | 2.379 | 2.86 | 20.8 | 58.5 | 244.1 |
| 144.4 | Top - Section 3 | 1.00 | 1.09 | 6.674 | 7.341 | 0.000 | 1.200 | * 1.739 | 4.42 | 15.528 | 18.63 | 136.8 | 378.0 | 1,587.4 |
| 145.0 | | 1.00 | 1.09 | 6.681 | 7.350 | 0.000 | 1.200 | * 1.739 | 0.58 | 2.020 | 2.42 | 17.8 | 49.8 | 120.2 |
| 148.0 | Appertunance(s) | 1.00 | 1.10 | 6.721 | 7.393 | 0.000 | 1.200 | * 1.743 | 3.00 | 10.276 | 12.33 | 91.2 | 251.5 | 609.2 |
| 150.0 | | 1.00 | 1.11 | 6.746 | 7.421 | 0.000 | 1.200 | * 1.745 | 2.00 | 6.745 | 8.09 | 60.1 | 165.7 | 400.1 |
| 155.0 | | 1.00 | 1.12 | 6.810 | 7.491 | 0.000 | 1.200 | * 1.751 | 5.00 | 16.494 | 19.79 | 148.3 | 401.9 | 973.6 |
| 160.0 | Appertunance(s) | 1.00 | 1.13 | 6.872 | 7.559 | 0.000 | 1.200 | * 1.757 | 5.00 | 15.967 | 19.16 | 144.8 | 389.5 | 940.7 |
| 165.0 | | 1.00 | 1.14 | 6.933 | 7.626 | 0.000 | 1.200 | * 1.762 | 5.00 | 15.440 | 18.53 | 141.3 | 376.8 | 907.7 |
| 170.0 | | 1.00 | 1.15 | 6.992 | 7.691 | 0.000 | 1.200 | * 1.767 | 5.00 | 14.912 | 17.89 | 137.6 | 364.1 | 874.6 |
| 171.0 | Appertunance(s) | 1.00 | 1.15 | 7.004 | 7.704 | 0.000 | 1.200 | * 1.768 | 1.00 | 2.919 | 3.50 | 27.0 | 72.3 | 172.0 |
| 175.0 | | 1.00 | 1.16 | 7.050 | 7.755 | 0.000 | 1.200 | * 1.772 | 4.00 | 11.465 | 13.76 | 106.7 | 281.0 | 671.5 |
| 178.5 | Appertunance(s) | 1.00 | 1.16 | 7.090 | 7.799 | 0.000 | 1.200 | * 1.776 | 3.50 | 9.755 | 11.71 | 91.3 | 239.5 | 570.5 |
| | | | | | | | | Totals: | 178.50 | | | 5,889.7 | 18,409.5 | 65,518.0 |

* = Cf Adjusted By Linear Load Ra Effect

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)




| | | |
|--|-----------------------------------|-------------------------------|
| Load Case: 1.2D + 1.0Di + 1.0Wi | 50.00 mph with 0.75 in Radial Ice | 22 Iterations |
| Gust Response Factor : 1.10 | Ice Dead Load Factor : 1.00 | Wind Importance Factor : 1.00 |
| Dead Load Factor : 1.20 | | Ice Importance Factor : 1.00 |
| Wind Load Factor : 1.00 | | |

Discrete Appurtenance Segment Forces (Factored)

| Elev (ft) | Description | Qty | qz (psf) | qzGh (psf) | Orientation Factor | Ka | Total EPAa (sf) | Horiz Ecc (ft) | Vert Ecc (ft) | Wind FX (lb) | Mom Y (lb-ft) | Mom Z (lb-ft) | Dead Load (lb) |
|-----------|----------------------|-----|----------|------------|--------------------|------|-----------------|----------------|---------------|-----------------|---------------|---------------|------------------|
| 20.00 | PCTEL GPS-TMG-HR- | 1 | 4.256 | 4.682 | 1.00 | 1.00 | 0.23 | 0.000 | 0.000 | 1.08 | 0.00 | 0.00 | 8.39 |
| 20.00 | Standoff | 1 | 4.256 | 4.682 | 1.00 | 1.00 | 2.56 | 0.000 | 0.000 | 11.98 | 0.00 | 0.00 | 73.10 |
| 116.0 | Alcatel-Lucent 800 M | 3 | 6.269 | 6.896 | 0.67 | 0.80 | 4.39 | 0.000 | 0.000 | 30.26 | 0.00 | 0.00 | 444.89 |
| 116.0 | Alcatel-Lucent 1900 | 3 | 6.269 | 6.896 | 0.67 | 0.80 | 4.78 | 0.000 | 0.000 | 32.98 | 0.00 | 0.00 | 492.68 |
| 116.0 | Flat Low Profile Pla | 1 | 6.269 | 6.896 | 1.00 | 1.00 | 44.75 | 0.000 | 0.000 | 308.55 | 0.00 | 0.00 | 2,232.75 |
| 116.0 | RFS APXVSP18-C- | 3 | 6.299 | 6.929 | 0.83 | 0.80 | 18.49 | 0.000 | 2.000 | 128.09 | 0.00 | 256.18 | 786.19 |
| 116.0 | Alcatel-Lucent TD-RR | 3 | 6.269 | 6.896 | 0.67 | 0.80 | 9.18 | 0.000 | 0.000 | 63.30 | 0.00 | 0.00 | 484.37 |
| 116.0 | RFS APXV9TM14-ALU- | 3 | 6.299 | 6.929 | 0.78 | 0.80 | 15.85 | 0.000 | 2.000 | 109.83 | 0.00 | 219.65 | 506.63 |
| 128.0 | RFS APXV18-206517S- | 3 | 6.448 | 7.092 | 0.80 | 1.00 | 15.33 | 0.000 | 0.000 | 108.73 | 0.00 | 0.00 | 440.83 |
| 135.0 | Round Low Profile PI | 1 | 6.546 | 7.201 | 1.00 | 1.00 | 40.74 | 0.000 | 0.000 | 293.34 | 0.00 | 0.00 | 2,242.42 |
| 135.0 | Antel BXA-171063-12B | 3 | 6.588 | 7.246 | 0.88 | 0.80 | 12.55 | 0.000 | 3.000 | 90.94 | 0.00 | 272.83 | 407.24 |
| 135.0 | Antel BXA-70063-6CF- | 3 | 6.588 | 7.246 | 0.77 | 0.80 | 16.27 | 0.000 | 3.000 | 117.91 | 0.00 | 353.72 | 576.58 |
| 135.0 | RFS FD9R6004/2C-3L | 6 | 6.588 | 7.246 | 0.50 | 0.80 | 1.38 | 0.000 | 3.000 | 10.01 | 0.00 | 30.04 | 96.14 |
| 135.0 | Antel BXA-80063-6BF- | 3 | 6.588 | 7.246 | 0.78 | 0.80 | 18.53 | 0.000 | 3.000 | 134.27 | 0.00 | 402.80 | 389.26 |
| 135.0 | Antel BXA-171063-8BF | 3 | 6.588 | 7.246 | 0.87 | 0.80 | 7.93 | 0.000 | 3.000 | 57.46 | 0.00 | 172.38 | 284.31 |
| 135.0 | Alcatel-Lucent RRH2x | 3 | 6.588 | 7.246 | 0.67 | 0.80 | 4.52 | 0.000 | 3.000 | 32.78 | 0.00 | 98.35 | 376.08 |
| 135.0 | RFS DB-T1-6Z-8AB-OZ | 1 | 6.588 | 7.246 | 1.00 | 0.80 | 4.53 | 0.000 | 3.000 | 32.83 | 0.00 | 98.50 | 194.76 |
| 135.0 | Alcatel-Lucent RRH2x | 3 | 6.588 | 7.246 | 0.67 | 0.80 | 4.40 | 0.000 | 3.000 | 31.88 | 0.00 | 95.65 | 437.95 |
| 148.0 | T-Arm w/ Working Pla | 3 | 6.721 | 7.393 | 0.67 | 0.75 | 31.78 | 0.000 | 0.000 | 234.97 | 0.00 | 0.00 | 1,335.43 |
| 148.0 | Ericsson KRY 112 144 | 3 | 6.721 | 7.393 | 0.50 | 0.80 | 0.76 | 0.000 | 0.000 | 5.63 | 0.00 | 0.00 | 88.67 |
| 148.0 | Ericsson AIR 21, 1,3 | 3 | 6.721 | 7.393 | 0.86 | 0.80 | 14.75 | 0.000 | 0.000 | 109.05 | 0.00 | 0.00 | 805.11 |
| 148.0 | Ericsson AIR 21, 1,3 | 3 | 6.721 | 7.393 | 0.85 | 0.80 | 14.67 | 0.000 | 0.000 | 108.45 | 0.00 | 0.00 | 799.57 |
| 160.0 | Powerwave 7020 | 3 | 6.872 | 7.559 | 0.33 | 0.75 | 0.46 | 0.000 | 0.000 | 3.50 | 0.00 | 0.00 | 55.54 |
| 160.0 | 14" x 9" TTA | 6 | 6.872 | 7.559 | 0.33 | 0.75 | 2.23 | 0.000 | 0.000 | 16.87 | 0.00 | 0.00 | 294.13 |
| 160.0 | Raycap DC6-48-60-18- | 3 | 6.872 | 7.559 | 1.00 | 0.75 | 5.68 | 0.000 | 0.000 | 42.96 | 0.00 | 0.00 | 315.50 |
| 160.0 | CCI | 3 | 6.872 | 7.559 | 0.50 | 0.75 | 2.10 | 0.000 | 0.000 | 15.89 | 0.00 | 0.00 | 202.38 |
| 160.0 | Ericsson RRUS A2 | 6 | 6.872 | 7.559 | 0.67 | 0.75 | 8.03 | 0.000 | 0.000 | 60.73 | 0.00 | 0.00 | 490.82 |
| 160.0 | Ericsson RRUS 11 (Ba | 6 | 6.872 | 7.559 | 0.67 | 0.75 | 10.48 | 0.000 | 0.000 | 79.18 | 0.00 | 0.00 | 887.71 |
| 160.0 | Ericsson RRUS-12 B2 | 6 | 6.872 | 7.559 | 0.67 | 0.75 | 11.67 | 0.000 | 0.000 | 88.18 | 0.00 | 0.00 | 994.47 |
| 160.0 | Ericsson RRUS E2 B29 | 3 | 6.872 | 7.559 | 0.67 | 0.75 | 5.83 | 0.000 | 0.000 | 44.09 | 0.00 | 0.00 | 504.43 |
| 160.0 | Ericsson RRUS-32 | 3 | 6.872 | 7.559 | 0.67 | 0.75 | 6.19 | 0.000 | 0.000 | 46.82 | 0.00 | 0.00 | 620.46 |
| 160.0 | Powerwave 7770.00 | 3 | 6.872 | 7.559 | 0.77 | 0.75 | 11.38 | 0.000 | 0.000 | 86.01 | 0.00 | 0.00 | 534.48 |
| 160.0 | CCI HPA-65R-BUU-H6 | 9 | 6.872 | 7.559 | 0.83 | 0.75 | 61.83 | 0.000 | 0.000 | 467.37 | 0.00 | 0.00 | 2,800.58 |
| 160.0 | Flat Platform w/ Han | 1 | 6.872 | 7.559 | 1.00 | 1.00 | 63.55 | 0.000 | 0.000 | 480.39 | 0.00 | 0.00 | 3,383.30 |
| 171.0 | Side Arms | 1 | 7.004 | 7.704 | 1.00 | 1.00 | 15.71 | 0.000 | 0.000 | 121.07 | 0.00 | 0.00 | 1,027.30 |
| 171.0 | DragonWave A-ANT- | 1 | 7.004 | 7.704 | 1.00 | 0.80 | 4.79 | 0.000 | 0.000 | 36.88 | 0.00 | 0.00 | 103.01 |
| 171.0 | NextNet BTS-2500 | 3 | 7.004 | 7.704 | 0.50 | 0.80 | 2.84 | 0.000 | 0.000 | 21.92 | 0.00 | 0.00 | 300.29 |
| 171.0 | Argus LLPX310R | 3 | 7.004 | 7.704 | 0.73 | 0.80 | 9.11 | 0.000 | 0.000 | 70.22 | 0.00 | 0.00 | 431.79 |
| 171.0 | DragonWave Horizon | 2 | 7.004 | 7.704 | 0.33 | 0.80 | 0.35 | 0.000 | 0.000 | 2.71 | 0.00 | 0.00 | 87.08 |
| 171.0 | DragonWave A-ANT- | 1 | 7.004 | 7.704 | 1.00 | 0.80 | 4.79 | 0.000 | 0.000 | 36.88 | 0.00 | 0.00 | 103.83 |
| 178.5 | 72" x 12" Panel | 3 | 7.118 | 7.830 | 0.79 | 0.80 | 17.92 | 0.000 | 2.500 | 140.35 | 0.00 | 350.87 | 749.11 |
| 178.5 | 48" x 12" Panel | 9 | 7.118 | 7.830 | 0.78 | 0.80 | 34.09 | 0.000 | 2.500 | 266.95 | 0.00 | 667.37 | 1,549.50 |
| 178.5 | Flat Low Profile Pla | 1 | 7.090 | 7.799 | 1.00 | 1.00 | 45.57 | 0.000 | 0.000 | 355.39 | 0.00 | 0.00 | 2,260.61 |
| | | | | | | | | | | 4,538.68 | | | 31,199.66 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)



© 2007 - 2014 by ATC IP LLC. All rights reserved.

Load Case: 1.2D + 1.0Di + 1.0Wi 50.00 mph with 0.75 in Radial Ice 22 Iterations


Gust Response Factor : 1.10 Ice Dead Load Factor : 1.00 Wind Importance Factor : 1.00
 Dead Load Factor : 1.20 Ice Importance Factor : 1.00
 Wind Load Factor : 1.00

Linear Appurtenance Segment Forces (Factored)

| Seg Top Elev (ft) | Description | Exposed To Wind | Length (ft) | Ca | Exposed Width (in) | Area (sqft) | CaAa (sqft) | qz (psf) | Ra | Cf Adjust Factor | FX (lb) | Dead Load (lb) |
|-------------------|----------------------|-----------------|-------------|-------|--------------------|-------------|-------------|----------|-------|------------------|---------|----------------|
| 5.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 4.256 | 0.130 | 1.090 | 0.00 | 17.64 |
| 5.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 2.03 | 0.00 | 4.256 | 0.130 | 1.090 | 0.00 | 80.94 |
| 5.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 1.86 | 0.00 | 4.256 | 0.130 | 1.090 | 0.00 | 106.14 |
| 5.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 4.256 | 0.130 | 1.090 | 0.00 | 57.78 |
| 5.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 1.86 | 0.00 | 4.256 | 0.130 | 1.090 | 0.00 | 106.14 |
| 5.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 1.68 | 0.00 | 4.256 | 0.130 | 1.090 | 0.00 | 23.85 |
| 5.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 1.68 | 0.00 | 4.256 | 0.130 | 1.090 | 0.00 | 52.71 |
| 5.00 | (1) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 4.256 | 0.130 | 1.090 | 0.00 | 13.53 |
| 10.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 4.256 | 0.132 | 1.097 | 0.00 | 19.48 |
| 10.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 2.10 | 0.00 | 4.256 | 0.132 | 1.097 | 0.00 | 83.99 |
| 10.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 1.93 | 0.00 | 4.256 | 0.132 | 1.097 | 0.00 | 111.66 |
| 10.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 4.256 | 0.132 | 1.097 | 0.00 | 61.24 |
| 10.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 1.93 | 0.00 | 4.256 | 0.132 | 1.097 | 0.00 | 111.66 |
| 10.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 1.75 | 0.00 | 4.256 | 0.132 | 1.097 | 0.00 | 25.79 |
| 10.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 1.76 | 0.00 | 4.256 | 0.132 | 1.097 | 0.00 | 55.71 |
| 10.00 | (1) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 4.256 | 0.132 | 1.097 | 0.00 | 15.15 |
| 15.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 4.256 | 0.135 | 1.105 | 0.00 | 20.66 |
| 15.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 2.15 | 0.00 | 4.256 | 0.135 | 1.105 | 0.00 | 85.93 |
| 15.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 1.98 | 0.00 | 4.256 | 0.135 | 1.105 | 0.00 | 115.12 |
| 15.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 4.256 | 0.135 | 1.105 | 0.00 | 63.43 |
| 15.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 1.98 | 0.00 | 4.256 | 0.135 | 1.105 | 0.00 | 115.12 |
| 15.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 1.80 | 0.00 | 4.256 | 0.135 | 1.105 | 0.00 | 27.03 |
| 15.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 1.80 | 0.00 | 4.256 | 0.135 | 1.105 | 0.00 | 57.61 |
| 15.00 | (1) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 4.256 | 0.135 | 1.105 | 0.00 | 16.20 |
| 20.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 4.256 | 0.137 | 1.112 | 0.00 | 21.56 |
| 20.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 2.18 | 0.00 | 4.256 | 0.137 | 1.112 | 0.00 | 87.37 |
| 20.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.01 | 0.00 | 4.256 | 0.137 | 1.112 | 0.00 | 117.68 |
| 20.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 4.256 | 0.137 | 1.112 | 0.00 | 65.06 |
| 20.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.01 | 0.00 | 4.256 | 0.137 | 1.112 | 0.00 | 117.68 |
| 20.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 1.83 | 0.00 | 4.256 | 0.137 | 1.112 | 0.00 | 27.97 |
| 20.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 1.83 | 0.00 | 4.256 | 0.137 | 1.112 | 0.00 | 59.04 |
| 20.00 | (1) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 4.256 | 0.137 | 1.112 | 0.00 | 17.00 |
| 25.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 4.256 | 0.140 | 1.120 | 0.00 | 22.28 |
| 25.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 2.21 | 0.00 | 4.256 | 0.140 | 1.120 | 0.00 | 88.54 |
| 25.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.04 | 0.00 | 4.256 | 0.140 | 1.120 | 0.00 | 119.74 |
| 25.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 4.256 | 0.140 | 1.120 | 0.00 | 66.37 |
| 25.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.04 | 0.00 | 4.256 | 0.140 | 1.120 | 0.00 | 119.74 |
| 25.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 1.86 | 0.00 | 4.256 | 0.140 | 1.120 | 0.00 | 28.73 |
| 25.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 1.86 | 0.00 | 4.256 | 0.140 | 1.120 | 0.00 | 60.18 |
| 30.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 4.260 | 0.143 | 1.128 | 0.00 | 22.90 |
| 30.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 2.23 | 0.00 | 4.260 | 0.143 | 1.128 | 0.00 | 89.52 |
| 30.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.06 | 0.00 | 4.260 | 0.143 | 1.128 | 0.00 | 121.46 |
| 30.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 4.260 | 0.143 | 1.128 | 0.00 | 67.47 |
| 30.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.06 | 0.00 | 4.260 | 0.143 | 1.128 | 0.00 | 121.46 |
| 30.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 1.88 | 0.00 | 4.260 | 0.143 | 1.128 | 0.00 | 29.37 |
| 30.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 1.88 | 0.00 | 4.260 | 0.143 | 1.128 | 0.00 | 61.15 |
| 35.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 4.451 | 0.145 | 1.136 | 0.00 | 23.43 |
| 35.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 2.25 | 0.00 | 4.451 | 0.145 | 1.136 | 0.00 | 90.36 |
| 35.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.08 | 0.00 | 4.451 | 0.145 | 1.136 | 0.00 | 122.95 |
| 35.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 4.451 | 0.145 | 1.136 | 0.00 | 68.43 |
| 35.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.08 | 0.00 | 4.451 | 0.145 | 1.136 | 0.00 | 122.95 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)




| | | |
|--|-----------------------------------|-------------------------------|
| Load Case: 1.2D + 1.0Di + 1.0Wi | 50.00 mph with 0.75 in Radial Ice | 22 Iterations |
| Gust Response Factor : 1.10 | Ice Dead Load Factor : 1.00 | Wind Importance Factor : 1.00 |
| Dead Load Factor : 1.20 | | Ice Importance Factor : 1.00 |
| Wind Load Factor : 1.00 | | |

| | | | | | | | | | | | | |
|-------|----------------------|-----|------|-------|------|------|------|-------|-------|-------|------|--------|
| 35.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 1.90 | 0.00 | 4.451 | 0.145 | 1.136 | 0.00 | 29.93 |
| 35.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 1.90 | 0.00 | 4.451 | 0.145 | 1.136 | 0.00 | 61.99 |
| 40.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 4.625 | 0.148 | 1.145 | 0.00 | 23.91 |
| 40.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 2.27 | 0.00 | 4.625 | 0.148 | 1.145 | 0.00 | 91.12 |
| 40.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.10 | 0.00 | 4.625 | 0.148 | 1.145 | 0.00 | 124.26 |
| 40.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 4.625 | 0.148 | 1.145 | 0.00 | 69.27 |
| 40.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.10 | 0.00 | 4.625 | 0.148 | 1.145 | 0.00 | 124.26 |
| 40.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 1.92 | 0.00 | 4.625 | 0.148 | 1.145 | 0.00 | 30.43 |
| 40.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 1.92 | 0.00 | 4.625 | 0.148 | 1.145 | 0.00 | 62.73 |
| 45.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 4.783 | 0.151 | 1.154 | 0.00 | 24.34 |
| 45.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 2.28 | 0.00 | 4.783 | 0.151 | 1.154 | 0.00 | 91.79 |
| 45.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.11 | 0.00 | 4.783 | 0.151 | 1.154 | 0.00 | 125.44 |
| 45.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 4.783 | 0.151 | 1.154 | 0.00 | 70.03 |
| 45.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.11 | 0.00 | 4.783 | 0.151 | 1.154 | 0.00 | 125.44 |
| 45.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 1.93 | 0.00 | 4.783 | 0.151 | 1.154 | 0.00 | 30.88 |
| 45.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 1.94 | 0.00 | 4.783 | 0.151 | 1.154 | 0.00 | 63.39 |
| 50.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 4.929 | 0.155 | 1.164 | 0.00 | 24.73 |
| 50.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 2.29 | 0.00 | 4.929 | 0.155 | 1.164 | 0.00 | 92.41 |
| 50.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.13 | 0.00 | 4.929 | 0.155 | 1.164 | 0.00 | 126.51 |
| 50.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 4.929 | 0.155 | 1.164 | 0.00 | 70.72 |
| 50.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.13 | 0.00 | 4.929 | 0.155 | 1.164 | 0.00 | 126.51 |
| 50.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 1.94 | 0.00 | 4.929 | 0.155 | 1.164 | 0.00 | 31.29 |
| 50.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 1.95 | 0.00 | 4.929 | 0.155 | 1.164 | 0.00 | 64.00 |
| 53.00 | (2) 1/2" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 5.012 | 0.157 | 1.172 | 0.00 | 14.97 |
| 53.00 | (2) 2" Conduit | Yes | 3.00 | 0.000 | 2.38 | 1.38 | 0.00 | 5.012 | 0.157 | 1.172 | 0.00 | 55.65 |
| 53.00 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 1.28 | 0.00 | 5.012 | 0.157 | 1.172 | 0.00 | 76.26 |
| 53.00 | (3) 1 5/8" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 5.012 | 0.157 | 1.172 | 0.00 | 42.66 |
| 53.00 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 1.28 | 0.00 | 5.012 | 0.157 | 1.172 | 0.00 | 76.26 |
| 53.00 | (1) 1 1/4" Hybriflex | Yes | 3.00 | 0.000 | 1.54 | 1.17 | 0.00 | 5.012 | 0.157 | 1.172 | 0.00 | 18.91 |
| 53.00 | (3) 1 1/4" Hybriflex | Yes | 3.00 | 0.000 | 1.55 | 1.17 | 0.00 | 5.012 | 0.157 | 1.172 | 0.00 | 38.60 |
| 55.00 | (2) 1/2" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 5.065 | 0.157 | 1.171 | 0.00 | 10.04 |
| 55.00 | (2) 2" Conduit | Yes | 2.00 | 0.000 | 2.38 | 0.92 | 0.00 | 5.065 | 0.157 | 1.171 | 0.00 | 37.19 |
| 55.00 | (6) 1 5/8" Coax | Yes | 2.00 | 0.000 | 1.98 | 0.86 | 0.00 | 5.065 | 0.157 | 1.171 | 0.00 | 50.99 |
| 55.00 | (3) 1 5/8" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 5.065 | 0.157 | 1.171 | 0.00 | 28.54 |
| 55.00 | (6) 1 5/8" Coax | Yes | 2.00 | 0.000 | 1.98 | 0.86 | 0.00 | 5.065 | 0.157 | 1.171 | 0.00 | 50.99 |
| 55.00 | (1) 1 1/4" Hybriflex | Yes | 2.00 | 0.000 | 1.54 | 0.78 | 0.00 | 5.065 | 0.157 | 1.171 | 0.00 | 12.67 |
| 55.00 | (3) 1 1/4" Hybriflex | Yes | 2.00 | 0.000 | 1.55 | 0.78 | 0.00 | 5.065 | 0.157 | 1.171 | 0.00 | 25.82 |
| 60.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 5.193 | 0.159 | 1.178 | 0.00 | 25.42 |
| 60.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 2.32 | 0.00 | 5.193 | 0.159 | 1.178 | 0.00 | 93.49 |
| 60.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.15 | 0.00 | 5.193 | 0.159 | 1.178 | 0.00 | 128.39 |
| 60.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 5.193 | 0.159 | 1.178 | 0.00 | 71.94 |
| 60.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.15 | 0.00 | 5.193 | 0.159 | 1.178 | 0.00 | 128.39 |
| 60.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 1.97 | 0.00 | 5.193 | 0.159 | 1.178 | 0.00 | 32.02 |
| 60.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 1.97 | 0.00 | 5.193 | 0.159 | 1.178 | 0.00 | 65.07 |
| 65.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 5.313 | 0.163 | 1.188 | 0.00 | 25.74 |
| 65.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 2.33 | 0.00 | 5.313 | 0.163 | 1.188 | 0.00 | 93.98 |
| 65.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.16 | 0.00 | 5.313 | 0.163 | 1.188 | 0.00 | 129.23 |
| 65.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 5.313 | 0.163 | 1.188 | 0.00 | 72.49 |
| 65.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.16 | 0.00 | 5.313 | 0.163 | 1.188 | 0.00 | 129.23 |
| 65.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 1.98 | 0.00 | 5.313 | 0.163 | 1.188 | 0.00 | 32.34 |
| 65.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 1.98 | 0.00 | 5.313 | 0.163 | 1.188 | 0.00 | 65.55 |
| 70.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 5.426 | 0.166 | 1.199 | 0.00 | 26.03 |
| 70.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 2.34 | 0.00 | 5.426 | 0.166 | 1.199 | 0.00 | 94.44 |
| 70.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.17 | 0.00 | 5.426 | 0.166 | 1.199 | 0.00 | 130.02 |
| 70.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 5.426 | 0.166 | 1.199 | 0.00 | 73.00 |
| 70.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.17 | 0.00 | 5.426 | 0.166 | 1.199 | 0.00 | 130.02 |
| 70.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 1.99 | 0.00 | 5.426 | 0.166 | 1.199 | 0.00 | 32.65 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)




| | | |
|--|-----------------------------------|-------------------------------|
| Load Case: 1.2D + 1.0Di + 1.0Wi | 50.00 mph with 0.75 in Radial Ice | 22 Iterations |
| Gust Response Factor : 1.10 | Ice Dead Load Factor : 1.00 | Wind Importance Factor : 1.00 |
| Dead Load Factor : 1.20 | | Ice Importance Factor : 1.00 |
| Wind Load Factor : 1.00 | | |

| | | | | | | | | | | | | |
|-------|----------------------|-----|------|-------|------|------|------|-------|-------|-------|------|--------|
| 70.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 1.99 | 0.00 | 5.426 | 0.166 | 1.199 | 0.00 | 66.00 |
| 75.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 5.534 | 0.170 | 1.211 | 0.00 | 26.31 |
| 75.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 2.35 | 0.00 | 5.534 | 0.170 | 1.211 | 0.00 | 94.87 |
| 75.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.18 | 0.00 | 5.534 | 0.170 | 1.211 | 0.00 | 130.76 |
| 75.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 5.534 | 0.170 | 1.211 | 0.00 | 73.48 |
| 75.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.18 | 0.00 | 5.534 | 0.170 | 1.211 | 0.00 | 130.76 |
| 75.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 2.00 | 0.00 | 5.534 | 0.170 | 1.211 | 0.00 | 32.94 |
| 75.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 2.00 | 0.00 | 5.534 | 0.170 | 1.211 | 0.00 | 66.42 |
| 80.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 5.637 | 0.174 | 1.223 | 0.00 | 26.57 |
| 80.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 2.36 | 0.00 | 5.637 | 0.174 | 1.223 | 0.00 | 95.27 |
| 80.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.19 | 0.00 | 5.637 | 0.174 | 1.223 | 0.00 | 131.46 |
| 80.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 5.637 | 0.174 | 1.223 | 0.00 | 73.93 |
| 80.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.19 | 0.00 | 5.637 | 0.174 | 1.223 | 0.00 | 131.46 |
| 80.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 2.01 | 0.00 | 5.637 | 0.174 | 1.223 | 0.00 | 33.21 |
| 80.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 2.01 | 0.00 | 5.637 | 0.174 | 1.223 | 0.00 | 66.82 |
| 85.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 5.736 | 0.179 | 1.236 | 0.00 | 26.82 |
| 85.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 2.37 | 0.00 | 5.736 | 0.179 | 1.236 | 0.00 | 95.66 |
| 85.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.20 | 0.00 | 5.736 | 0.179 | 1.236 | 0.00 | 132.12 |
| 85.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 5.736 | 0.179 | 1.236 | 0.00 | 74.36 |
| 85.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.20 | 0.00 | 5.736 | 0.179 | 1.236 | 0.00 | 132.12 |
| 85.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 2.02 | 0.00 | 5.736 | 0.179 | 1.236 | 0.00 | 33.47 |
| 85.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 2.02 | 0.00 | 5.736 | 0.179 | 1.236 | 0.00 | 67.20 |
| 90.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 5.830 | 0.183 | 1.249 | 0.00 | 27.05 |
| 90.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 2.37 | 0.00 | 5.830 | 0.183 | 1.249 | 0.00 | 96.02 |
| 90.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.21 | 0.00 | 5.830 | 0.183 | 1.249 | 0.00 | 132.74 |
| 90.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 5.830 | 0.183 | 1.249 | 0.00 | 74.77 |
| 90.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.21 | 0.00 | 5.830 | 0.183 | 1.249 | 0.00 | 132.74 |
| 90.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 2.02 | 0.00 | 5.830 | 0.183 | 1.249 | 0.00 | 33.72 |
| 90.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 2.03 | 0.00 | 5.830 | 0.183 | 1.249 | 0.00 | 67.56 |
| 91.42 | (2) 1/2" Coax | Yes | 1.42 | 0.000 | 0.00 | 0.00 | 0.00 | 5.856 | 0.186 | 1.258 | 0.00 | 7.68 |
| 91.42 | (2) 2" Conduit | Yes | 1.42 | 0.000 | 2.38 | 0.67 | 0.00 | 5.856 | 0.186 | 1.258 | 0.00 | 27.24 |
| 91.42 | (6) 1 5/8" Coax | Yes | 1.42 | 0.000 | 1.98 | 0.63 | 0.00 | 5.856 | 0.186 | 1.258 | 0.00 | 37.66 |
| 91.42 | (3) 1 5/8" Coax | Yes | 1.42 | 0.000 | 0.00 | 0.00 | 0.00 | 5.856 | 0.186 | 1.258 | 0.00 | 21.22 |
| 91.42 | (6) 1 5/8" Coax | Yes | 1.42 | 0.000 | 1.98 | 0.63 | 0.00 | 5.856 | 0.186 | 1.258 | 0.00 | 37.66 |
| 91.42 | (1) 1 1/4" Hybriflex | Yes | 1.42 | 0.000 | 1.54 | 0.57 | 0.00 | 5.856 | 0.186 | 1.258 | 0.00 | 9.57 |
| 91.42 | (3) 1 1/4" Hybriflex | Yes | 1.42 | 0.000 | 1.55 | 0.58 | 0.00 | 5.856 | 0.186 | 1.258 | 0.00 | 19.17 |
| 95.00 | (2) 1/2" Coax | Yes | 3.58 | 0.000 | 0.00 | 0.00 | 0.00 | 5.921 | 0.188 | 1.265 | 0.00 | 19.55 |
| 95.00 | (2) 2" Conduit | Yes | 3.58 | 0.000 | 2.38 | 1.71 | 0.00 | 5.921 | 0.188 | 1.265 | 0.00 | 69.07 |
| 95.00 | (6) 1 5/8" Coax | Yes | 3.58 | 0.000 | 1.98 | 1.59 | 0.00 | 5.921 | 0.188 | 1.265 | 0.00 | 95.56 |
| 95.00 | (3) 1 5/8" Coax | Yes | 3.58 | 0.000 | 0.00 | 0.00 | 0.00 | 5.921 | 0.188 | 1.265 | 0.00 | 53.87 |
| 95.00 | (6) 1 5/8" Coax | Yes | 3.58 | 0.000 | 1.98 | 1.59 | 0.00 | 5.921 | 0.188 | 1.265 | 0.00 | 95.56 |
| 95.00 | (1) 1 1/4" Hybriflex | Yes | 3.58 | 0.000 | 1.54 | 1.46 | 0.00 | 5.921 | 0.188 | 1.265 | 0.00 | 24.34 |
| 95.00 | (3) 1 1/4" Hybriflex | Yes | 3.58 | 0.000 | 1.55 | 1.46 | 0.00 | 5.921 | 0.188 | 1.265 | 0.00 | 48.67 |
| 98.00 | (2) 1/2" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 5.974 | 0.192 | 1.275 | 0.00 | 16.45 |
| 98.00 | (2) 2" Conduit | Yes | 3.00 | 0.000 | 2.38 | 1.43 | 0.00 | 5.974 | 0.192 | 1.275 | 0.00 | 57.94 |
| 98.00 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 1.33 | 0.00 | 5.974 | 0.192 | 1.275 | 0.00 | 80.21 |
| 98.00 | (3) 1 5/8" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 5.974 | 0.192 | 1.275 | 0.00 | 45.23 |
| 98.00 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 1.33 | 0.00 | 5.974 | 0.192 | 1.275 | 0.00 | 80.21 |
| 98.00 | (1) 1 1/4" Hybriflex | Yes | 3.00 | 0.000 | 1.54 | 1.22 | 0.00 | 5.974 | 0.192 | 1.275 | 0.00 | 20.46 |
| 98.00 | (3) 1 1/4" Hybriflex | Yes | 3.00 | 0.000 | 1.55 | 1.22 | 0.00 | 5.974 | 0.192 | 1.275 | 0.00 | 40.86 |
| 100.0 | (2) 1/2" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.008 | 0.192 | 1.275 | 0.00 | 11.00 |
| 100.0 | (2) 2" Conduit | Yes | 2.00 | 0.000 | 2.38 | 0.96 | 0.00 | 6.008 | 0.192 | 1.275 | 0.00 | 38.68 |
| 100.0 | (6) 1 5/8" Coax | Yes | 2.00 | 0.000 | 1.98 | 0.89 | 0.00 | 6.008 | 0.192 | 1.275 | 0.00 | 53.57 |
| 100.0 | (3) 1 5/8" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.008 | 0.192 | 1.275 | 0.00 | 30.21 |
| 100.0 | (6) 1 5/8" Coax | Yes | 2.00 | 0.000 | 1.98 | 0.89 | 0.00 | 6.008 | 0.192 | 1.275 | 0.00 | 53.57 |
| 100.0 | (1) 1 1/4" Hybriflex | Yes | 2.00 | 0.000 | 1.54 | 0.82 | 0.00 | 6.008 | 0.192 | 1.275 | 0.00 | 13.67 |
| 100.0 | (3) 1 1/4" Hybriflex | Yes | 2.00 | 0.000 | 1.55 | 0.82 | 0.00 | 6.008 | 0.192 | 1.275 | 0.00 | 27.29 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)



6/13/2014 11:15:47 AM
 Page : 27

© 2007 - 2014 by ATC IP LLC. All rights reserved.

Load Case: 1.2D + 1.0Di + 1.0Wi 50.00 mph with 0.75 in Radial Ice 22 Iterations


Gust Response Factor : 1.10 Ice Dead Load Factor : 1.00 Wind Importance Factor : 1.00
 Dead Load Factor : 1.20 Ice Importance Factor : 1.00
 Wind Load Factor : 1.00

| | | | | | | | | | | | | |
|-------|----------------------|-----|------|-------|------|------|------|-------|-------|-------|-------|--------|
| 105.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.093 | 0.195 | 1.285 | 0.00 | 27.71 |
| 105.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 2.40 | 0.00 | 6.093 | 0.195 | 1.285 | 0.00 | 97.03 |
| 105.0 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.23 | 0.00 | 6.093 | 0.195 | 1.285 | 0.00 | 134.46 |
| 105.0 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.093 | 0.195 | 1.285 | 0.00 | 75.89 |
| 105.0 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.23 | 0.00 | 6.093 | 0.195 | 1.285 | 0.00 | 134.46 |
| 105.0 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 2.05 | 0.00 | 6.093 | 0.195 | 1.285 | 0.00 | 34.40 |
| 105.0 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 2.05 | 0.00 | 6.093 | 0.195 | 1.285 | 0.00 | 68.55 |
| 110.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.174 | 0.200 | 0.000 | 0.00 | 27.91 |
| 110.0 | (2) 2" Conduit | Yes | 5.00 | 1.200 | 2.38 | 2.40 | 2.88 | 6.174 | 0.200 | 0.000 | 19.57 | 97.33 |
| 110.0 | (6) 1 5/8" Coax | Yes | 5.00 | 1.200 | 1.98 | 2.23 | 2.68 | 6.174 | 0.200 | 0.000 | 18.21 | 134.98 |
| 110.0 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.174 | 0.200 | 0.000 | 0.00 | 76.24 |
| 110.0 | (6) 1 5/8" Coax | Yes | 5.00 | 1.200 | 1.98 | 2.23 | 2.68 | 6.174 | 0.200 | 0.000 | 18.21 | 134.98 |
| 110.0 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 1.200 | 1.54 | 2.05 | 2.46 | 6.174 | 0.200 | 0.000 | 16.72 | 34.61 |
| 110.0 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 1.200 | 1.55 | 2.06 | 2.47 | 6.174 | 0.200 | 0.000 | 16.75 | 68.85 |
| 115.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.253 | 0.206 | 0.000 | 0.00 | 28.10 |
| 115.0 | (2) 2" Conduit | Yes | 5.00 | 1.200 | 2.38 | 2.41 | 2.89 | 6.253 | 0.206 | 0.000 | 19.88 | 97.63 |
| 115.0 | (6) 1 5/8" Coax | Yes | 5.00 | 1.200 | 1.98 | 2.24 | 2.69 | 6.253 | 0.206 | 0.000 | 18.50 | 135.49 |
| 115.0 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.253 | 0.206 | 0.000 | 0.00 | 76.57 |
| 115.0 | (6) 1 5/8" Coax | Yes | 5.00 | 1.200 | 1.98 | 2.24 | 2.69 | 6.253 | 0.206 | 0.000 | 18.50 | 135.49 |
| 115.0 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 1.200 | 1.54 | 2.06 | 2.47 | 6.253 | 0.206 | 0.000 | 16.99 | 34.81 |
| 115.0 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 1.200 | 1.55 | 2.06 | 2.47 | 6.253 | 0.206 | 0.000 | 17.02 | 69.15 |
| 116.0 | (2) 1/2" Coax | Yes | 1.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.269 | 0.209 | 0.000 | 0.00 | 5.63 |
| 116.0 | (2) 2" Conduit | Yes | 1.00 | 1.200 | 2.38 | 0.48 | 0.58 | 6.269 | 0.209 | 0.000 | 3.99 | 19.54 |
| 116.0 | (6) 1 5/8" Coax | Yes | 1.00 | 1.200 | 1.98 | 0.45 | 0.54 | 6.269 | 0.209 | 0.000 | 3.71 | 27.12 |
| 116.0 | (3) 1 5/8" Coax | Yes | 1.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.269 | 0.209 | 0.000 | 0.00 | 15.33 |
| 116.0 | (6) 1 5/8" Coax | Yes | 1.00 | 1.200 | 1.98 | 0.45 | 0.54 | 6.269 | 0.209 | 0.000 | 3.71 | 27.12 |
| 116.0 | (1) 1 1/4" Hybriflex | Yes | 1.00 | 1.200 | 1.54 | 0.41 | 0.49 | 6.269 | 0.209 | 0.000 | 3.41 | 6.97 |
| 116.0 | (3) 1 1/4" Hybriflex | Yes | 1.00 | 1.200 | 1.55 | 0.41 | 0.50 | 6.269 | 0.209 | 0.000 | 3.41 | 13.84 |
| 120.0 | (2) 1/2" Coax | Yes | 4.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.330 | 0.143 | 1.129 | 0.00 | 22.63 |
| 120.0 | (2) 2" Conduit | Yes | 4.00 | 0.000 | 2.38 | 1.93 | 0.00 | 6.330 | 0.143 | 1.129 | 0.00 | 78.33 |
| 120.0 | (6) 1 5/8" Coax | Yes | 4.00 | 0.000 | 1.98 | 1.80 | 0.00 | 6.330 | 0.143 | 1.129 | 0.00 | 108.78 |
| 120.0 | (3) 1 5/8" Coax | Yes | 4.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.330 | 0.143 | 1.129 | 0.00 | 61.51 |
| 120.0 | (6) 1 5/8" Coax | Yes | 4.00 | 0.000 | 1.98 | 1.80 | 0.00 | 6.330 | 0.143 | 1.129 | 0.00 | 108.78 |
| 125.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.404 | 0.147 | 1.140 | 0.00 | 28.47 |
| 125.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 2.42 | 0.00 | 6.404 | 0.147 | 1.140 | 0.00 | 98.19 |
| 125.0 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.25 | 0.00 | 6.404 | 0.147 | 1.140 | 0.00 | 136.44 |
| 125.0 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.404 | 0.147 | 1.140 | 0.00 | 77.19 |
| 125.0 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.25 | 0.00 | 6.404 | 0.147 | 1.140 | 0.00 | 136.44 |
| 128.0 | (2) 1/2" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.448 | 0.150 | 1.151 | 0.00 | 17.14 |
| 128.0 | (2) 2" Conduit | Yes | 3.00 | 0.000 | 2.38 | 1.45 | 0.00 | 6.448 | 0.150 | 1.151 | 0.00 | 59.01 |
| 128.0 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 1.35 | 0.00 | 6.448 | 0.150 | 1.151 | 0.00 | 82.03 |
| 128.0 | (3) 1 5/8" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.448 | 0.150 | 1.151 | 0.00 | 46.42 |
| 128.0 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 1.35 | 0.00 | 6.448 | 0.150 | 1.151 | 0.00 | 82.03 |
| 130.0 | (2) 1/2" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.476 | 0.105 | 1.015 | 0.00 | 11.46 |
| 130.0 | (2) 2" Conduit | Yes | 2.00 | 0.000 | 2.38 | 0.97 | 0.00 | 6.476 | 0.105 | 1.015 | 0.00 | 39.38 |
| 130.0 | (6) 1 5/8" Coax | Yes | 2.00 | 0.000 | 1.98 | 0.90 | 0.00 | 6.476 | 0.105 | 1.015 | 0.00 | 54.76 |
| 130.0 | (3) 1 5/8" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.476 | 0.105 | 1.015 | 0.00 | 31.00 |
| 135.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.546 | 0.107 | 1.022 | 0.00 | 28.81 |
| 135.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 2.43 | 0.00 | 6.546 | 0.107 | 1.022 | 0.00 | 98.71 |
| 135.0 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 2.26 | 0.00 | 6.546 | 0.107 | 1.022 | 0.00 | 137.33 |
| 135.0 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.546 | 0.107 | 1.022 | 0.00 | 77.78 |
| 139.3 | (2) 1/2" Coax | Yes | 4.33 | 0.000 | 0.00 | 0.00 | 0.00 | 6.606 | 0.110 | 1.031 | 0.00 | 25.09 |
| 139.3 | (2) 2" Conduit | Yes | 4.33 | 0.000 | 2.38 | 2.11 | 0.00 | 6.606 | 0.110 | 1.031 | 0.00 | 85.74 |
| 139.3 | (6) 1 5/8" Coax | Yes | 4.33 | 0.000 | 1.98 | 1.97 | 0.00 | 6.606 | 0.110 | 1.031 | 0.00 | 119.34 |
| 140.0 | (2) 1/2" Coax | Yes | 0.67 | 0.000 | 0.00 | 0.00 | 0.00 | 6.615 | 0.112 | 1.037 | 0.00 | 3.86 |
| 140.0 | (2) 2" Conduit | Yes | 0.67 | 0.000 | 2.38 | 0.32 | 0.00 | 6.615 | 0.112 | 1.037 | 0.00 | 13.19 |
| 140.0 | (6) 1 5/8" Coax | Yes | 0.67 | 0.000 | 1.98 | 0.30 | 0.00 | 6.615 | 0.112 | 1.037 | 0.00 | 18.37 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev: 0.000 (ft)

6/13/2014 11:15:47 AM
 Page: 28



© 2007 - 2014 by ATC IP LLC. All rights reserved.

Load Case: 1.2D + 1.0Di + 1.0Wi 50.00 mph with 0.75 in Radial Ice 22 Iterations


Gust Response Factor : 1.10 Ice Dead Load Factor : 1.00 Wind Importance Factor : 1.00
 Dead Load Factor : 1.20 Ice Importance Factor : 1.00
 Wind Load Factor : 1.00

| | | | | | | | | | | | | |
|----------------|-----------------|-----|------|-------|------|------|------|-------|-------|-------|--------|-----------|
| 144.4 | (2) 1/2" Coax | Yes | 4.42 | 0.000 | 0.00 | 0.00 | 0.00 | 6.674 | 0.114 | 1.042 | 0.00 | 25.72 |
| 144.4 | (2) 2" Conduit | Yes | 4.42 | 0.000 | 2.38 | 2.16 | 0.00 | 6.674 | 0.114 | 1.042 | 0.00 | 87.61 |
| 144.4 | (6) 1 5/8" Coax | Yes | 4.42 | 0.000 | 1.98 | 2.01 | 0.00 | 6.674 | 0.114 | 1.042 | 0.00 | 122.01 |
| 145.0 | (2) 1/2" Coax | Yes | 0.58 | 0.000 | 0.00 | 0.00 | 0.00 | 6.681 | 0.115 | 1.044 | 0.00 | 3.40 |
| 145.0 | (2) 2" Conduit | Yes | 0.58 | 0.000 | 2.38 | 0.28 | 0.00 | 6.681 | 0.115 | 1.044 | 0.00 | 11.57 |
| 145.0 | (6) 1 5/8" Coax | Yes | 0.58 | 0.000 | 1.98 | 0.27 | 0.00 | 6.681 | 0.115 | 1.044 | 0.00 | 16.12 |
| 148.0 | (2) 1/2" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.721 | 0.116 | 1.048 | 0.00 | 17.54 |
| 148.0 | (2) 2" Conduit | Yes | 3.00 | 0.000 | 2.38 | 1.47 | 0.00 | 6.721 | 0.116 | 1.048 | 0.00 | 59.61 |
| 148.0 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 1.37 | 0.00 | 6.721 | 0.116 | 1.048 | 0.00 | 83.05 |
| 150.0 | (2) 1/2" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.746 | 0.064 | 0.000 | 0.00 | 11.71 |
| 150.0 | (2) 2" Conduit | Yes | 2.00 | 0.000 | 2.38 | 0.98 | 0.00 | 6.746 | 0.064 | 0.000 | 0.00 | 39.78 |
| 155.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.810 | 0.066 | 0.000 | 0.00 | 29.44 |
| 155.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 2.45 | 0.00 | 6.810 | 0.066 | 0.000 | 0.00 | 99.67 |
| 160.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.872 | 0.068 | 0.000 | 0.00 | 29.58 |
| 160.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 2.46 | 0.00 | 6.872 | 0.068 | 0.000 | 0.00 | 99.89 |
| 165.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.933 | 0.071 | 0.000 | 0.00 | 29.73 |
| 165.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 2.46 | 0.00 | 6.933 | 0.071 | 0.000 | 0.00 | 100.11 |
| 170.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.992 | 0.074 | 0.000 | 0.00 | 29.87 |
| 170.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 2.46 | 0.00 | 6.992 | 0.074 | 0.000 | 0.00 | 100.32 |
| 171.0 | (2) 1/2" Coax | Yes | 1.00 | 0.000 | 0.00 | 0.00 | 0.00 | 7.004 | 0.076 | 0.000 | 0.00 | 5.98 |
| 171.0 | (2) 2" Conduit | Yes | 1.00 | 0.000 | 2.38 | 0.49 | 0.00 | 7.004 | 0.076 | 0.000 | 0.00 | 20.07 |
| Totals: | | | | | | | | | | | 198.59 | 15,403.14 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)

6/13/2014 11:15:47 AM
 Page: 29



© 2007 - 2014 by ATC IP LLC. All rights reserved.


| | | |
|--|-----------------------------------|-------------------------------|
| Load Case: 1.2D + 1.0Di + 1.0Wi | 50.00 mph with 0.75 in Radial Ice | 22 Iterations |
| Gust Response Factor : 1.10 | Ice Dead Load Factor : 1.00 | Wind Importance Factor : 1.00 |
| Dead Load Factor : 1.20 | | Ice Importance Factor : 1.00 |
| Wind Load Factor : 1.00 | | |

Applied Segment Forces Summary

| Seg Elev (ft) | Lateral FX (-) (lb) | Axial FY (-) (lb) | Torsion MY (lb-ft) | Moment MZ (lb-ft) |
|----------------|---------------------|-------------------|--------------------|-------------------|
| 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 5.00 | 175.46 | 3,333.81 | 0.00 | 0.00 |
| 10.00 | 172.89 | 3,354.57 | 0.00 | 0.00 |
| 15.00 | 170.16 | 3,349.34 | 0.00 | 0.00 |
| 20.00 | 180.42 | 3,414.21 | 0.00 | 0.00 |
| 25.00 | 164.52 | 3,291.90 | 0.00 | 0.00 |
| 30.00 | 161.80 | 3,263.85 | 0.00 | 0.00 |
| 35.00 | 166.07 | 3,232.80 | 0.00 | 0.00 |
| 40.00 | 169.39 | 3,199.47 | 0.00 | 0.00 |
| 45.00 | 171.92 | 3,164.35 | 0.00 | 0.00 |
| 50.00 | 175.87 | 4,603.68 | 0.00 | 0.00 |
| 53.00 | 105.63 | 2,729.78 | 0.00 | 0.00 |
| 55.00 | 70.47 | 1,148.67 | 0.00 | 0.00 |
| 60.00 | 178.15 | 2,847.22 | 0.00 | 0.00 |
| 65.00 | 178.61 | 2,812.74 | 0.00 | 0.00 |
| 70.00 | 178.70 | 2,777.51 | 0.00 | 0.00 |
| 75.00 | 178.44 | 2,741.61 | 0.00 | 0.00 |
| 80.00 | 177.86 | 2,705.12 | 0.00 | 0.00 |
| 85.00 | 177.01 | 2,668.10 | 0.00 | 0.00 |
| 90.00 | 175.89 | 2,630.60 | 0.00 | 0.00 |
| 91.42 | 49.32 | 739.21 | 0.00 | 0.00 |
| 95.00 | 126.14 | 2,579.91 | 0.00 | 0.00 |
| 98.00 | 104.91 | 2,135.05 | 0.00 | 0.00 |
| 100.0 | 69.51 | 949.34 | 0.00 | 0.00 |
| 105.0 | 173.28 | 2,347.43 | 0.00 | 0.00 |
| 110.0 | 260.79 | 2,313.54 | 0.00 | 0.00 |
| 115.0 | 260.05 | 2,279.33 | 0.00 | 0.00 |
| 116.0 | 724.62 | 5,399.97 | 0.00 | 475.83 |
| 120.0 | 133.12 | 1,710.29 | 0.00 | 0.00 |
| 125.0 | 164.35 | 2,105.19 | 0.00 | 0.00 |
| 128.0 | 205.85 | 1,688.14 | 0.00 | 0.00 |
| 130.0 | 64.14 | 770.08 | 0.00 | 0.00 |
| 135.0 | 960.34 | 6,901.48 | 0.00 | 1,524.26 |
| 139.3 | 135.26 | 1,476.79 | 0.00 | 0.00 |
| 140.0 | 20.77 | 309.21 | 0.00 | 0.00 |
| 144.4 | 136.79 | 2,019.17 | 0.00 | 0.00 |
| 145.0 | 17.81 | 177.19 | 0.00 | 0.00 |
| 148.0 | 549.25 | 3,931.57 | 0.00 | 0.00 |
| 150.0 | 60.06 | 526.31 | 0.00 | 0.00 |
| 155.0 | 148.27 | 1,289.54 | 0.00 | 0.00 |
| 160.0 | 1,576.85 | 12,340.84 | 0.00 | 0.00 |
| 165.0 | 141.29 | 1,098.24 | 0.00 | 0.00 |
| 170.0 | 137.63 | 1,065.49 | 0.00 | 0.00 |
| 171.0 | 316.65 | 2,263.45 | 0.00 | 0.00 |
| 175.0 | 106.70 | 718.75 | 0.00 | 0.00 |
| 178.5 | 853.98 | 5,171.10 | 0.00 | 1,018.25 |
| Totals: | 10,627.02 | 121,575.9 | 0.00 | 3,018.34 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)



6/13/2014 11:15:47 AM
 Page : 30

© 2007 - 2014 by ATC IP LLC. All rights reserved.

| | | |
|--|-----------------------------------|-------------------------------|
| Load Case: 1.2D + 1.0Di + 1.0Wi | 50.00 mph with 0.75 in Radial Ice | 22 Iterations |
| Gust Response Factor : 1.10 | Ice Dead Load Factor : 1.00 | Wind Importance Factor : 1.00 |
| Dead Load Factor : 1.20 | | Ice Importance Factor : 1.00 |
| Wind Load Factor : 1.00 | | |


Calculated Forces

| Seg Elev (ft) | Pu FY (-) (kips) | Vu FX (-) (kips) | Tu MY (ft-kips) | Mu MZ (ft-kips) | Mu MX (ft-kips) | Resultant Moment (ft-kips) | phi Pn (kips) | phi Vn (kips) | phi Tn (ft-kips) | phi Mn (ft-kips) | Total Deflect (in) | Rotation (deg) | Ratio |
|---------------|------------------|------------------|-----------------|-----------------|-----------------|----------------------------|---------------|---------------|------------------|------------------|--------------------|----------------|-------|
| 0.00 | -121.57 | -10.66 | 0.00 | -1,306.37 | 0.00 | 1,306.37 | 6,164.54 | 3,082.27 | 18,158.3 | 9,092.69 | 0.00 | 0.00 | 0.163 |
| 5.00 | -118.23 | -10.54 | 0.00 | -1,253.08 | 0.00 | 1,253.08 | 6,108.61 | 3,054.31 | 17,675.6 | 8,850.97 | 0.02 | -0.03 | 0.161 |
| 10.00 | -114.87 | -10.42 | 0.00 | -1,200.39 | 0.00 | 1,200.39 | 6,050.81 | 3,025.41 | 17,193.4 | 8,609.50 | 0.06 | -0.06 | 0.158 |
| 15.00 | -111.52 | -10.30 | 0.00 | -1,148.28 | 0.00 | 1,148.28 | 5,991.14 | 2,995.57 | 16,712.0 | 8,368.43 | 0.14 | -0.09 | 0.156 |
| 20.00 | -108.10 | -10.17 | 0.00 | -1,096.76 | 0.00 | 1,096.76 | 5,929.59 | 2,964.80 | 16,231.6 | 8,127.91 | 0.24 | -0.12 | 0.153 |
| 25.00 | -104.80 | -10.06 | 0.00 | -1,045.89 | 0.00 | 1,045.89 | 5,866.18 | 2,933.09 | 15,752.7 | 7,888.07 | 0.38 | -0.14 | 0.150 |
| 30.00 | -101.54 | -9.94 | 0.00 | -995.62 | 0.00 | 995.62 | 5,800.89 | 2,900.44 | 15,275.4 | 7,649.08 | 0.55 | -0.17 | 0.148 |
| 35.00 | -98.30 | -9.81 | 0.00 | -945.93 | 0.00 | 945.93 | 5,733.73 | 2,866.86 | 14,800.1 | 7,411.07 | 0.74 | -0.20 | 0.145 |
| 40.00 | -95.09 | -9.68 | 0.00 | -896.87 | 0.00 | 896.87 | 5,664.70 | 2,832.35 | 14,327.0 | 7,174.19 | 0.97 | -0.23 | 0.142 |
| 45.00 | -91.93 | -9.54 | 0.00 | -848.46 | 0.00 | 848.46 | 5,593.79 | 2,796.90 | 13,856.5 | 6,938.58 | 1.24 | -0.26 | 0.139 |
| 50.00 | -87.32 | -9.38 | 0.00 | -800.74 | 0.00 | 800.74 | 5,521.02 | 2,760.51 | 13,388.9 | 6,704.40 | 1.53 | -0.30 | 0.135 |
| 53.00 | -84.59 | -9.29 | 0.00 | -772.59 | 0.00 | 772.59 | 4,440.13 | 2,220.06 | 10,789.7 | 5,402.88 | 1.72 | -0.31 | 0.162 |
| 55.00 | -83.44 | -9.24 | 0.00 | -754.02 | 0.00 | 754.02 | 4,419.76 | 2,209.88 | 10,648.2 | 5,332.01 | 1.86 | -0.33 | 0.160 |
| 60.00 | -80.58 | -9.10 | 0.00 | -707.81 | 0.00 | 707.81 | 4,367.53 | 2,183.77 | 10,295.0 | 5,155.16 | 2.22 | -0.36 | 0.156 |
| 65.00 | -77.77 | -8.95 | 0.00 | -662.32 | 0.00 | 662.32 | 4,313.43 | 2,156.72 | 9,942.96 | 4,978.87 | 2.62 | -0.40 | 0.151 |
| 70.00 | -74.99 | -8.79 | 0.00 | -617.59 | 0.00 | 617.59 | 4,257.46 | 2,128.73 | 9,592.32 | 4,803.29 | 3.05 | -0.43 | 0.146 |
| 75.00 | -72.24 | -8.64 | 0.00 | -573.63 | 0.00 | 573.63 | 4,199.61 | 2,099.81 | 9,243.38 | 4,628.56 | 3.52 | -0.46 | 0.141 |
| 80.00 | -69.53 | -8.48 | 0.00 | -530.45 | 0.00 | 530.45 | 4,139.90 | 2,069.95 | 8,896.44 | 4,454.83 | 4.02 | -0.50 | 0.136 |
| 85.00 | -66.86 | -8.31 | 0.00 | -488.07 | 0.00 | 488.07 | 4,078.31 | 2,039.15 | 8,551.80 | 4,282.26 | 4.56 | -0.53 | 0.130 |
| 90.00 | -64.23 | -8.14 | 0.00 | -446.50 | 0.00 | 446.50 | 4,014.84 | 2,007.42 | 8,209.74 | 4,110.97 | 5.14 | -0.57 | 0.125 |
| 91.42 | -63.49 | -8.10 | 0.00 | -434.97 | 0.00 | 434.97 | 3,996.52 | 1,998.26 | 8,113.33 | 4,062.70 | 5.31 | -0.58 | 0.123 |
| 95.00 | -60.91 | -7.97 | 0.00 | -405.95 | 0.00 | 405.95 | 3,949.51 | 1,974.76 | 7,870.56 | 3,941.13 | 5.75 | -0.60 | 0.118 |
| 98.00 | -58.77 | -7.86 | 0.00 | -382.04 | 0.00 | 382.04 | 3,056.80 | 1,528.40 | 6,090.92 | 3,049.99 | 6.13 | -0.62 | 0.145 |
| 100.00 | -57.82 | -7.80 | 0.00 | -366.32 | 0.00 | 366.32 | 3,039.33 | 1,519.67 | 5,992.84 | 3,000.87 | 6.39 | -0.63 | 0.141 |
| 105.00 | -55.47 | -7.64 | 0.00 | -327.31 | 0.00 | 327.31 | 2,994.36 | 1,497.18 | 5,748.30 | 2,878.42 | 7.07 | -0.67 | 0.132 |
| 110.00 | -53.15 | -7.38 | 0.00 | -289.12 | 0.00 | 289.12 | 2,947.52 | 1,473.76 | 5,504.94 | 2,756.56 | 7.79 | -0.70 | 0.123 |
| 115.00 | -50.88 | -7.11 | 0.00 | -252.21 | 0.00 | 252.21 | 2,898.80 | 1,449.40 | 5,263.06 | 2,635.44 | 8.54 | -0.73 | 0.113 |
| 116.00 | -45.48 | -6.33 | 0.00 | -244.63 | 0.00 | 244.63 | 2,888.83 | 1,444.42 | 5,214.89 | 2,611.32 | 8.70 | -0.74 | 0.109 |
| 120.00 | -43.77 | -6.19 | 0.00 | -219.32 | 0.00 | 219.32 | 2,848.21 | 1,424.11 | 5,022.95 | 2,515.21 | 9.33 | -0.77 | 0.103 |
| 125.00 | -41.67 | -6.02 | 0.00 | -188.35 | 0.00 | 188.35 | 2,795.75 | 1,397.88 | 4,784.90 | 2,396.01 | 10.15 | -0.80 | 0.094 |
| 128.00 | -39.98 | -5.80 | 0.00 | -170.31 | 0.00 | 170.31 | 2,763.38 | 1,381.69 | 4,643.19 | 2,325.05 | 10.65 | -0.81 | 0.088 |
| 130.00 | -39.21 | -5.73 | 0.00 | -158.71 | 0.00 | 158.71 | 2,741.42 | 1,370.71 | 4,549.21 | 2,277.99 | 11.00 | -0.82 | 0.084 |
| 135.00 | -32.32 | -4.69 | 0.00 | -128.52 | 0.00 | 128.52 | 2,685.21 | 1,342.61 | 4,316.17 | 2,161.29 | 11.87 | -0.85 | 0.072 |
| 139.33 | -30.85 | -4.53 | 0.00 | -108.21 | 0.00 | 108.21 | 2,634.99 | 1,317.49 | 4,116.57 | 2,061.34 | 12.65 | -0.87 | 0.064 |
| 140.00 | -30.54 | -4.51 | 0.00 | -105.19 | 0.00 | 105.19 | 2,627.14 | 1,313.57 | 4,086.07 | 2,046.07 | 12.77 | -0.87 | 0.063 |
| 144.42 | -28.52 | -4.35 | 0.00 | -85.25 | 0.00 | 85.25 | 1,915.99 | 957.99 | 2,941.41 | 1,472.89 | 13.59 | -0.89 | 0.073 |
| 145.00 | -28.34 | -4.33 | 0.00 | -82.72 | 0.00 | 82.72 | 1,911.69 | 955.84 | 2,923.20 | 1,463.77 | 13.70 | -0.89 | 0.071 |
| 148.00 | -24.42 | -3.73 | 0.00 | -69.71 | 0.00 | 69.71 | 1,889.17 | 944.59 | 2,829.77 | 1,416.99 | 14.26 | -0.90 | 0.062 |
| 150.00 | -23.89 | -3.67 | 0.00 | -62.26 | 0.00 | 62.26 | 1,873.79 | 936.89 | 2,767.71 | 1,385.91 | 14.64 | -0.91 | 0.058 |
| 155.00 | -22.60 | -3.50 | 0.00 | -43.93 | 0.00 | 43.93 | 1,834.01 | 917.01 | 2,613.49 | 1,308.69 | 15.60 | -0.93 | 0.046 |
| 160.00 | -10.29 | -1.73 | 0.00 | -26.42 | 0.00 | 26.42 | 1,792.37 | 896.18 | 2,460.85 | 1,232.25 | 16.58 | -0.94 | 0.027 |
| 165.00 | -9.19 | -1.57 | 0.00 | -17.79 | 0.00 | 17.79 | 1,748.85 | 874.42 | 2,310.07 | 1,156.75 | 17.57 | -0.95 | 0.021 |
| 170.00 | -8.13 | -1.41 | 0.00 | -9.96 | 0.00 | 9.96 | 1,703.46 | 851.73 | 2,161.44 | 1,082.33 | 18.56 | -0.95 | 0.014 |
| 171.00 | -5.87 | -1.06 | 0.00 | -8.54 | 0.00 | 8.54 | 1,694.16 | 847.08 | 2,132.00 | 1,067.58 | 18.76 | -0.95 | 0.011 |
| 175.00 | -5.16 | -0.94 | 0.00 | -4.31 | 0.00 | 4.31 | 1,656.20 | 828.10 | 2,015.26 | 1,009.13 | 19.56 | -0.96 | 0.007 |
| 178.50 | 0.00 | -0.85 | 0.00 | -1.02 | 0.00 | 1.02 | 1,622.00 | 811.00 | 1,914.55 | 958.70 | 20.26 | -0.96 | 0.001 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)

6/13/2014 11:15:47 AM
 Page : 31



© 2007 - 2014 by ATC IP LLC. All rights reserved.

| | | |
|-------------------------------|----------------------------------|---------------|
| Load Case: 1.2D + 1.0E | Dead Load with Seismic | 21 Iterations |
| Gust Response Factor : 1.10 | Sds : 0.26 | Ss : 0.24 |
| Dead Load Factor : 1.20 | Seismic Load Factor : 1.00 | Sd1 : 0.10 |
| Wind Load Factor : 0.00 | Structure Frequency : 0.3559 | SA : 0.04 |
| | Seismic Importance Factor : 1.00 | |

Total Segment Forces (Factored)

R : 1.50

| Seg Top Elev (ft) | Description | Wz (lb) | a | b | c | Lateral Fs (lb) |
|-------------------|-----------------|------------------|------|-------|------|-----------------|
| 0.00 | | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 5.00 | | 1675.82 | 0.00 | 0.03 | 0.02 | 43.95 |
| 10.00 | | 1646.12 | 0.01 | 0.05 | 0.03 | 62.38 |
| 15.00 | | 1616.43 | 0.01 | 0.06 | 0.03 | 71.04 |
| 20.00 | Appertunance(s) | 1991.73 | 0.02 | 0.07 | 0.04 | 94.10 |
| 25.00 | | 1557.03 | 0.04 | 0.07 | 0.04 | 76.51 |
| 30.00 | | 1527.34 | 0.05 | 0.07 | 0.04 | 76.97 |
| 35.00 | | 1497.64 | 0.07 | 0.07 | 0.04 | 77.05 |
| 40.00 | | 1467.94 | 0.09 | 0.07 | 0.04 | 77.08 |
| 45.00 | Bot - Section 2 | 1438.25 | 0.12 | 0.07 | 0.03 | 77.14 |
| 50.00 | | 2632.33 | 0.15 | 0.07 | 0.03 | 144.02 |
| 53.00 | Top - Section 1 | 1552.93 | 0.17 | 0.07 | 0.03 | 85.77 |
| 55.00 | | 476.28 | 0.18 | 0.07 | 0.03 | 26.42 |
| 60.00 | | 1172.87 | 0.21 | 0.06 | 0.02 | 65.11 |
| 65.00 | | 1147.42 | 0.25 | 0.06 | 0.02 | 62.17 |
| 70.00 | | 1121.96 | 0.29 | 0.05 | 0.01 | 56.87 |
| 75.00 | | 1096.51 | 0.33 | 0.04 | 0.01 | 48.31 |
| 80.00 | | 1071.05 | 0.38 | 0.02 | 0.01 | 35.79 |
| 85.00 | | 1045.60 | 0.43 | 0.01 | 0.01 | 19.26 |
| 90.00 | | 1020.15 | 0.48 | -0.01 | 0.01 | -0.03 |
| 91.42 | Bot - Section 3 | 284.41 | 0.50 | -0.01 | 0.01 | -1.59 |
| 95.00 | | 1310.49 | 0.54 | -0.03 | 0.01 | -25.65 |
| 98.00 | Top - Section 2 | 1078.72 | 0.57 | -0.04 | 0.01 | -32.98 |
| 100.0 | | 325.17 | 0.59 | -0.05 | 0.01 | -12.11 |
| 105.0 | | 798.09 | 0.65 | -0.07 | 0.02 | -40.48 |
| 110.0 | | 776.88 | 0.72 | -0.09 | 0.03 | -45.77 |
| 115.0 | | 755.66 | 0.78 | -0.11 | 0.05 | -46.60 |
| 116.0 | Appertunance(s) | 2745.59 | 0.80 | -0.11 | 0.05 | -169.08 |
| 120.0 | | 585.86 | 0.85 | -0.12 | 0.07 | -34.69 |
| 125.0 | | 713.24 | 0.93 | -0.12 | 0.10 | -36.99 |
| 128.0 | Appertunance(s) | 552.76 | 0.97 | -0.12 | 0.12 | -24.97 |
| 130.0 | | 274.27 | 1.00 | -0.11 | 0.13 | -10.92 |
| 135.0 | Appertunance(s) | 3401.92 | 1.08 | -0.08 | 0.18 | -78.79 |
| 139.3 | Bot - Section 4 | 564.22 | 1.15 | -0.04 | 0.22 | -2.85 |
| 140.0 | | 154.71 | 1.16 | -0.03 | 0.23 | -0.30 |
| 144.4 | Top - Section 3 | 1007.82 | 1.24 | 0.04 | 0.28 | 20.71 |
| 145.0 | | 58.66 | 1.25 | 0.05 | 0.29 | 1.40 |
| 148.0 | Appertunance(s) | 2763.04 | 1.30 | 0.12 | 0.34 | 114.59 |
| 150.0 | | 195.30 | 1.33 | 0.17 | 0.37 | 10.58 |
| 155.0 | | 476.37 | 1.43 | 0.33 | 0.46 | 42.55 |
| 160.0 | Appertunance(s) | 3317.10 | 1.52 | 0.55 | 0.57 | 428.80 |
| 165.0 | | 442.43 | 1.61 | 0.83 | 0.69 | 77.05 |
| 170.0 | | 425.46 | 1.71 | 1.18 | 0.84 | 95.34 |
| 171.0 | Appertunance(s) | 2680.06 | 1.73 | 1.26 | 0.87 | 629.00 |
| 175.0 | | 325.43 | 1.82 | 1.62 | 1.01 | 90.86 |
| 178.5 | Appertunance(s) | 2180.85 | 1.89 | 1.98 | 1.14 | 699.81 |
| Totals: | | 54,949.88 | | | | 2,846.81 |


Total Wind : 53,382.2

Seismic Base Shear Not Tested Due To User Override - Analysis Required

Pole : 302467
Location : Bilkays Express, CT
Height : 178.5 (ft)
Base Dia : 72.00 (in)
Top Dia : 29.00 (in)
Shape : 18 Sides
Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
Struct Class : II
Exposure Category : B
Topographic Category : 1
Base Elev : 0.000 (ft)

© 2007 - 2014 by ATC IP LLC. All rights reserved.



6/13/2014 11:15:47 AM

Page: 32

Load Case: 1.2D + 1.0E

Dead Load with Seismic

21 Iterations

Gust Response Factor : 1.10

Sds : 0.26

Ss : 0.24

Dead Load Factor : 1.20

Seismic Load Factor : 1.00

Sd1 : 0.10

S1 : 0.06

Wind Load Factor : 0.00


Structure Frequency : 0.3559

SA : 0.04

Seismic Importance Factor : 1.00

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)



© 2007 - 2014 by ATC IP LLC. All rights reserved.

| | | |
|-------------------------------|----------------------------------|---------------|
| Load Case: 1.2D + 1.0E | Dead Load with Seismic | 21 Iterations |
| Gust Response Factor : 1.10 | Sds : 0.26 | Ss : 0.24 |
| Dead Load Factor : 1.20 | Seismic Load Factor : 1.00 | Sd1 : 0.10 |
| Wind Load Factor : 0.00 | Structure Frequency : 0.3559 | SA : 0.04 |
| | Seismic Importance Factor : 1.00 | |


Calculated Forces

| Seg Elev (ft) | Pu FY (-) (kips) | Vu FX (-) (kips) | Tu MY (ft-kips) | Mu MZ (ft-kips) | Mu MX (ft-kips) | Resultant Moment (ft-kips) | phi Pn (kips) | phi Vn (kips) | phi Tn (ft-kips) | phi Mn (ft-kips) | Total Deflect (in) | Rotation (deg) | Ratio |
|---------------|------------------|------------------|-----------------|-----------------|-----------------|----------------------------|---------------|---------------|------------------|------------------|--------------------|----------------|-------|
| 0.00 | -75.69 | -3.42 | 0.00 | -440.34 | 0.00 | 440.34 | 6,164.54 | 3,082.27 | 18,158.3 | 9,092.69 | 0.00 | 0.00 | 0.061 |
| 5.00 | -73.23 | -3.38 | 0.00 | -423.26 | 0.00 | 423.26 | 6,108.61 | 3,054.31 | 17,675.6 | 8,850.97 | 0.01 | -0.01 | 0.060 |
| 10.00 | -70.81 | -3.33 | 0.00 | -406.34 | 0.00 | 406.34 | 6,050.81 | 3,025.41 | 17,193.4 | 8,609.50 | 0.02 | -0.02 | 0.059 |
| 15.00 | -68.42 | -3.27 | 0.00 | -389.67 | 0.00 | 389.67 | 5,991.14 | 2,995.57 | 16,712.0 | 8,368.43 | 0.05 | -0.03 | 0.058 |
| 20.00 | -66.02 | -3.19 | 0.00 | -373.30 | 0.00 | 373.30 | 5,929.59 | 2,964.80 | 16,231.6 | 8,127.91 | 0.08 | -0.04 | 0.057 |
| 25.00 | -63.70 | -3.12 | 0.00 | -357.36 | 0.00 | 357.36 | 5,866.18 | 2,933.09 | 15,752.7 | 7,888.07 | 0.13 | -0.05 | 0.056 |
| 30.00 | -61.42 | -3.05 | 0.00 | -341.75 | 0.00 | 341.75 | 5,800.89 | 2,900.44 | 15,275.4 | 7,649.08 | 0.18 | -0.06 | 0.055 |
| 35.00 | -59.17 | -2.99 | 0.00 | -326.48 | 0.00 | 326.48 | 5,733.73 | 2,866.86 | 14,800.1 | 7,411.07 | 0.25 | -0.07 | 0.054 |
| 40.00 | -56.97 | -2.92 | 0.00 | -311.55 | 0.00 | 311.55 | 5,664.70 | 2,832.35 | 14,327.0 | 7,174.19 | 0.33 | -0.08 | 0.053 |
| 45.00 | -54.79 | -2.85 | 0.00 | -296.97 | 0.00 | 296.97 | 5,593.79 | 2,796.90 | 13,856.5 | 6,938.58 | 0.42 | -0.09 | 0.053 |
| 50.00 | -51.19 | -2.70 | 0.00 | -282.74 | 0.00 | 282.74 | 5,521.02 | 2,760.51 | 13,388.9 | 6,704.40 | 0.52 | -0.10 | 0.051 |
| 53.00 | -49.05 | -2.62 | 0.00 | -274.63 | 0.00 | 274.63 | 4,440.13 | 2,220.06 | 10,789.7 | 5,402.88 | 0.59 | -0.11 | 0.062 |
| 55.00 | -48.30 | -2.60 | 0.00 | -269.40 | 0.00 | 269.40 | 4,419.76 | 2,209.88 | 10,648.2 | 5,332.01 | 0.63 | -0.11 | 0.061 |
| 60.00 | -46.45 | -2.54 | 0.00 | -256.41 | 0.00 | 256.41 | 4,367.53 | 2,183.77 | 10,295.0 | 5,155.16 | 0.76 | -0.12 | 0.060 |
| 65.00 | -44.62 | -2.48 | 0.00 | -243.71 | 0.00 | 243.71 | 4,313.43 | 2,156.72 | 9,942.96 | 4,978.87 | 0.89 | -0.14 | 0.059 |
| 70.00 | -42.83 | -2.43 | 0.00 | -231.30 | 0.00 | 231.30 | 4,257.46 | 2,128.73 | 9,592.32 | 4,803.29 | 1.05 | -0.15 | 0.058 |
| 75.00 | -41.07 | -2.39 | 0.00 | -219.15 | 0.00 | 219.15 | 4,199.61 | 2,099.81 | 9,243.38 | 4,628.56 | 1.21 | -0.16 | 0.057 |
| 80.00 | -39.33 | -2.36 | 0.00 | -207.22 | 0.00 | 207.22 | 4,139.90 | 2,069.95 | 8,896.44 | 4,454.83 | 1.39 | -0.18 | 0.056 |
| 85.00 | -37.63 | -2.34 | 0.00 | -195.44 | 0.00 | 195.44 | 4,078.31 | 2,039.15 | 8,551.80 | 4,282.26 | 1.58 | -0.19 | 0.055 |
| 90.00 | -35.96 | -2.34 | 0.00 | -183.74 | 0.00 | 183.74 | 4,014.84 | 2,007.42 | 8,209.74 | 4,110.97 | 1.79 | -0.20 | 0.054 |
| 91.42 | -35.49 | -2.34 | 0.00 | -180.43 | 0.00 | 180.43 | 3,996.52 | 1,998.26 | 8,113.33 | 4,062.70 | 1.85 | -0.21 | 0.053 |
| 95.00 | -33.60 | -2.34 | 0.00 | -172.04 | 0.00 | 172.04 | 3,949.51 | 1,974.76 | 7,870.56 | 3,941.13 | 2.01 | -0.22 | 0.052 |
| 98.00 | -32.03 | -2.34 | 0.00 | -165.02 | 0.00 | 165.02 | 3,056.80 | 1,528.40 | 6,090.92 | 3,049.99 | 2.14 | -0.23 | 0.065 |
| 100.00 | -31.46 | -2.34 | 0.00 | -160.35 | 0.00 | 160.35 | 3,039.33 | 1,519.67 | 5,992.84 | 3,000.87 | 2.24 | -0.23 | 0.064 |
| 105.00 | -30.06 | -2.34 | 0.00 | -148.64 | 0.00 | 148.64 | 2,994.36 | 1,497.18 | 5,748.30 | 2,878.42 | 2.49 | -0.25 | 0.062 |
| 110.00 | -28.68 | -2.35 | 0.00 | -136.92 | 0.00 | 136.92 | 2,947.52 | 1,473.76 | 5,504.94 | 2,756.56 | 2.76 | -0.26 | 0.059 |
| 115.00 | -27.32 | -2.34 | 0.00 | -125.19 | 0.00 | 125.19 | 2,898.80 | 1,449.40 | 5,263.06 | 2,635.44 | 3.04 | -0.28 | 0.057 |
| 116.00 | -24.19 | -2.33 | 0.00 | -122.85 | 0.00 | 122.85 | 2,888.83 | 1,444.42 | 5,214.89 | 2,611.32 | 3.10 | -0.28 | 0.055 |
| 120.00 | -23.15 | -2.33 | 0.00 | -113.52 | 0.00 | 113.52 | 2,848.21 | 1,424.11 | 5,022.95 | 2,515.21 | 3.34 | -0.29 | 0.053 |
| 125.00 | -21.87 | -2.33 | 0.00 | -101.85 | 0.00 | 101.85 | 2,795.75 | 1,397.88 | 4,784.90 | 2,396.01 | 3.66 | -0.31 | 0.050 |
| 128.00 | -21.02 | -2.33 | 0.00 | -94.86 | 0.00 | 94.86 | 2,763.38 | 1,381.69 | 4,643.19 | 2,325.05 | 3.86 | -0.32 | 0.048 |
| 130.00 | -20.53 | -2.33 | 0.00 | -90.21 | 0.00 | 90.21 | 2,741.42 | 1,370.71 | 4,549.21 | 2,277.99 | 3.99 | -0.33 | 0.047 |
| 135.00 | -16.90 | -2.31 | 0.00 | -78.56 | 0.00 | 78.56 | 2,685.21 | 1,342.61 | 4,316.17 | 2,161.29 | 4.34 | -0.34 | 0.043 |
| 139.33 | -15.97 | -2.31 | 0.00 | -68.54 | 0.00 | 68.54 | 2,634.99 | 1,317.49 | 4,116.57 | 2,061.34 | 4.66 | -0.35 | 0.039 |
| 140.00 | -15.74 | -2.31 | 0.00 | -67.00 | 0.00 | 67.00 | 2,627.14 | 1,313.57 | 4,086.07 | 2,046.07 | 4.71 | -0.35 | 0.039 |
| 144.42 | -14.27 | -2.28 | 0.00 | -56.80 | 0.00 | 56.80 | 1,915.99 | 957.99 | 2,941.41 | 1,472.89 | 5.04 | -0.37 | 0.046 |
| 145.00 | -14.16 | -2.28 | 0.00 | -55.47 | 0.00 | 55.47 | 1,911.69 | 955.84 | 2,923.20 | 1,463.77 | 5.08 | -0.37 | 0.045 |
| 148.00 | -12.10 | -2.15 | 0.00 | -48.63 | 0.00 | 48.63 | 1,889.17 | 944.59 | 2,829.77 | 1,416.99 | 5.32 | -0.38 | 0.041 |
| 150.00 | -11.77 | -2.14 | 0.00 | -44.32 | 0.00 | 44.32 | 1,873.79 | 936.89 | 2,767.71 | 1,385.91 | 5.48 | -0.38 | 0.038 |
| 155.00 | -10.96 | -2.10 | 0.00 | -33.60 | 0.00 | 33.60 | 1,834.01 | 917.01 | 2,613.49 | 1,308.69 | 5.88 | -0.39 | 0.032 |
| 160.00 | -5.45 | -1.63 | 0.00 | -23.12 | 0.00 | 23.12 | 1,792.37 | 896.18 | 2,460.85 | 1,232.25 | 6.30 | -0.40 | 0.022 |
| 165.00 | -4.81 | -1.55 | 0.00 | -14.97 | 0.00 | 14.97 | 1,748.85 | 874.42 | 2,310.07 | 1,156.75 | 6.73 | -0.41 | 0.016 |
| 170.00 | -4.20 | -1.45 | 0.00 | -7.22 | 0.00 | 7.22 | 1,703.46 | 851.73 | 2,161.44 | 1,082.33 | 7.16 | -0.41 | 0.009 |
| 171.00 | -3.09 | -0.81 | 0.00 | -5.77 | 0.00 | 5.77 | 1,694.16 | 847.08 | 2,132.00 | 1,067.58 | 7.25 | -0.42 | 0.007 |
| 175.00 | -2.65 | -0.72 | 0.00 | -2.52 | 0.00 | 2.52 | 1,656.20 | 828.10 | 2,015.26 | 1,009.13 | 7.60 | -0.42 | 0.004 |
| 178.50 | 0.00 | -0.70 | 0.00 | 0.00 | 0.00 | 0.00 | 1,622.00 | 811.00 | 1,914.55 | 958.70 | 7.90 | -0.42 | 0.000 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)

6/13/2014 11:15:47 AM
 Page : 34



© 2007 - 2014 by ATC IP LLC. All rights reserved.

| | | |
|-------------------------------|-------------------------------------|----------------------------------|
| Load Case: 0.9D + 1.0E | Dead Load with Seismic (Reduced DL) | 21 Iterations |
| Gust Response Factor : 1.10 | Sds : 0.26 | Ss : 0.24 |
| Dead Load Factor : 0.90 | Seismic Load Factor : 1.00 | Sd1 : 0.10 |
| Wind Load Factor : 0.00 | Structure Frequency : 0.3559 | SA : 0.04 |
| | | Seismic Importance Factor : 1.00 |

Total Segment Forces (Factored)

R : 1.50

| Seg Top Elev (ft) | Description | Wz (lb) | a | b | c | Lateral Fs (lb) |
|-------------------|-----------------|------------------|------|-------|------|-----------------|
| 0.00 | | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 5.00 | | 1675.82 | 0.00 | 0.03 | 0.02 | 43.95 |
| 10.00 | | 1646.12 | 0.01 | 0.05 | 0.03 | 62.38 |
| 15.00 | | 1616.43 | 0.01 | 0.06 | 0.03 | 71.04 |
| 20.00 | Appertunance(s) | 1991.73 | 0.02 | 0.07 | 0.04 | 94.10 |
| 25.00 | | 1557.03 | 0.04 | 0.07 | 0.04 | 76.51 |
| 30.00 | | 1527.34 | 0.05 | 0.07 | 0.04 | 76.97 |
| 35.00 | | 1497.64 | 0.07 | 0.07 | 0.04 | 77.05 |
| 40.00 | | 1467.94 | 0.09 | 0.07 | 0.04 | 77.08 |
| 45.00 | Bot - Section 2 | 1438.25 | 0.12 | 0.07 | 0.03 | 77.14 |
| 50.00 | | 2632.33 | 0.15 | 0.07 | 0.03 | 144.02 |
| 53.00 | Top - Section 1 | 1552.93 | 0.17 | 0.07 | 0.03 | 85.77 |
| 55.00 | | 476.28 | 0.18 | 0.07 | 0.03 | 26.42 |
| 60.00 | | 1172.87 | 0.21 | 0.06 | 0.02 | 65.11 |
| 65.00 | | 1147.42 | 0.25 | 0.06 | 0.02 | 62.17 |
| 70.00 | | 1121.96 | 0.29 | 0.05 | 0.01 | 56.87 |
| 75.00 | | 1096.51 | 0.33 | 0.04 | 0.01 | 48.31 |
| 80.00 | | 1071.05 | 0.38 | 0.02 | 0.01 | 35.79 |
| 85.00 | | 1045.60 | 0.43 | 0.01 | 0.01 | 19.26 |
| 90.00 | | 1020.15 | 0.48 | -0.01 | 0.01 | -0.03 |
| 91.42 | Bot - Section 3 | 284.41 | 0.50 | -0.01 | 0.01 | -1.59 |
| 95.00 | | 1310.49 | 0.54 | -0.03 | 0.01 | -25.65 |
| 98.00 | Top - Section 2 | 1078.72 | 0.57 | -0.04 | 0.01 | -32.98 |
| 100.0 | | 325.17 | 0.59 | -0.05 | 0.01 | -12.11 |
| 105.0 | | 798.09 | 0.65 | -0.07 | 0.02 | -40.48 |
| 110.0 | | 776.88 | 0.72 | -0.09 | 0.03 | -45.77 |
| 115.0 | | 755.66 | 0.78 | -0.11 | 0.05 | -46.60 |
| 116.0 | Appertunance(s) | 2745.59 | 0.80 | -0.11 | 0.05 | -169.08 |
| 120.0 | | 585.86 | 0.85 | -0.12 | 0.07 | -34.69 |
| 125.0 | | 713.24 | 0.93 | -0.12 | 0.10 | -36.99 |
| 128.0 | Appertunance(s) | 552.76 | 0.97 | -0.12 | 0.12 | -24.97 |
| 130.0 | | 274.27 | 1.00 | -0.11 | 0.13 | -10.92 |
| 135.0 | Appertunance(s) | 3401.92 | 1.08 | -0.08 | 0.18 | -78.79 |
| 139.3 | Bot - Section 4 | 564.22 | 1.15 | -0.04 | 0.22 | -2.85 |
| 140.0 | | 154.71 | 1.16 | -0.03 | 0.23 | -0.30 |
| 144.4 | Top - Section 3 | 1007.82 | 1.24 | 0.04 | 0.28 | 20.71 |
| 145.0 | | 58.66 | 1.25 | 0.05 | 0.29 | 1.40 |
| 148.0 | Appertunance(s) | 2763.04 | 1.30 | 0.12 | 0.34 | 114.59 |
| 150.0 | | 195.30 | 1.33 | 0.17 | 0.37 | 10.58 |
| 155.0 | | 476.37 | 1.43 | 0.33 | 0.46 | 42.55 |
| 160.0 | Appertunance(s) | 3317.10 | 1.52 | 0.55 | 0.57 | 428.80 |
| 165.0 | | 442.43 | 1.61 | 0.83 | 0.69 | 77.05 |
| 170.0 | | 425.46 | 1.71 | 1.18 | 0.84 | 95.34 |
| 171.0 | Appertunance(s) | 2680.06 | 1.73 | 1.26 | 0.87 | 629.00 |
| 175.0 | | 325.43 | 1.82 | 1.62 | 1.01 | 90.86 |
| 178.5 | Appertunance(s) | 2180.85 | 1.89 | 1.98 | 1.14 | 699.81 |
| Totals: | | 54,949.88 | | | | 2,846.81 |


Total Wind : 53,382.2

Seismic Base Shear Not Tested Due To User Override - Analysis Required

Pole : 302467
Location : Bilkays Express, CT
Height : 178.5 (ft)
Base Dia : 72.00 (in)
Top Dia : 29.00 (in)
Shape : 18 Sides
Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
Struct Class : II
Exposure Category : B
Topographic Category : 1
Base Elev : 0.000 (ft)

© 2007 - 2014 by ATC IP LLC. All rights reserved.



6/13/2014 11:15:48 AM

Page: 35

Load Case: 0.9D + 1.0E

Dead Load with Seismic (Reduced DL)

21 Iterations

Gust Response Factor : 1.10

Sds : 0.26

Ss : 0.24

Dead Load Factor : 0.90

Seismic Load Factor : 1.00

Sd1 : 0.10

S1 : 0.06

Wind Load Factor : 0.00


Structure Frequency : 0.3559

SA : 0.04

Seismic Importance Factor : 1.00

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)



© 2007 - 2014 by ATC IP LLC. All rights reserved.

Load Case: 0.9D + 1.0E

Dead Load with Seismic (Reduced DL)

21 Iterations

Gust Response Factor : 1.10
 Dead Load Factor : 0.90
 Wind Load Factor : 0.00

Sds : 0.26
 Sd1 : 0.10
 SA : 0.04
 Seismic Load Factor : 1.00
 Structure Frequency : 0.3559


Ss : 0.24
 S1 : 0.06
 Seismic Importance Factor : 1.00

Calculated Forces

| Seg Elev (ft) | Pu FY (-) (kips) | Vu FX (-) (kips) | Tu MY (ft-kips) | Mu MZ (ft-kips) | Mu MX (ft-kips) | Resultant Moment (ft-kips) | phi Pn (kips) | phi Vn (kips) | phi Tn (ft-kips) | phi Mn (ft-kips) | Total Deflect (in) | Rotation (deg) | Ratio |
|---------------|------------------|------------------|-----------------|-----------------|-----------------|----------------------------|---------------|---------------|------------------|------------------|--------------------|----------------|-------|
| 0.00 | -56.77 | -3.41 | 0.00 | -436.30 | 0.00 | 436.30 | 6,164.54 | 3,082.27 | 18,158.3 | 9,092.69 | 0.00 | 0.00 | 0.057 |
| 5.00 | -54.92 | -3.38 | 0.00 | -419.22 | 0.00 | 419.22 | 6,108.61 | 3,054.31 | 17,675.6 | 8,850.97 | 0.01 | -0.01 | 0.056 |
| 10.00 | -53.10 | -3.33 | 0.00 | -402.32 | 0.00 | 402.32 | 6,050.81 | 3,025.41 | 17,193.4 | 8,609.50 | 0.02 | -0.02 | 0.056 |
| 15.00 | -51.31 | -3.26 | 0.00 | -385.69 | 0.00 | 385.69 | 5,991.14 | 2,995.57 | 16,712.0 | 8,368.43 | 0.05 | -0.03 | 0.055 |
| 20.00 | -49.51 | -3.18 | 0.00 | -369.38 | 0.00 | 369.38 | 5,929.59 | 2,964.80 | 16,231.6 | 8,127.91 | 0.08 | -0.04 | 0.054 |
| 25.00 | -47.77 | -3.11 | 0.00 | -353.50 | 0.00 | 353.50 | 5,866.18 | 2,933.09 | 15,752.7 | 7,888.07 | 0.13 | -0.05 | 0.053 |
| 30.00 | -46.06 | -3.04 | 0.00 | -337.97 | 0.00 | 337.97 | 5,800.89 | 2,900.44 | 15,275.4 | 7,649.08 | 0.18 | -0.06 | 0.052 |
| 35.00 | -44.38 | -2.97 | 0.00 | -322.78 | 0.00 | 322.78 | 5,733.73 | 2,866.86 | 14,800.1 | 7,411.07 | 0.25 | -0.07 | 0.051 |
| 40.00 | -42.72 | -2.89 | 0.00 | -307.96 | 0.00 | 307.96 | 5,664.70 | 2,832.35 | 14,327.0 | 7,174.19 | 0.33 | -0.08 | 0.050 |
| 45.00 | -41.09 | -2.82 | 0.00 | -293.49 | 0.00 | 293.49 | 5,593.79 | 2,796.90 | 13,856.5 | 6,938.58 | 0.42 | -0.09 | 0.050 |
| 50.00 | -38.39 | -2.68 | 0.00 | -279.38 | 0.00 | 279.38 | 5,521.02 | 2,760.51 | 13,388.9 | 6,704.40 | 0.52 | -0.10 | 0.049 |
| 53.00 | -36.79 | -2.59 | 0.00 | -271.34 | 0.00 | 271.34 | 4,440.13 | 2,220.06 | 10,789.7 | 5,402.88 | 0.58 | -0.11 | 0.059 |
| 55.00 | -36.23 | -2.57 | 0.00 | -266.15 | 0.00 | 266.15 | 4,419.76 | 2,209.88 | 10,648.2 | 5,332.01 | 0.63 | -0.11 | 0.058 |
| 60.00 | -34.83 | -2.51 | 0.00 | -253.29 | 0.00 | 253.29 | 4,367.53 | 2,183.77 | 10,295.0 | 5,155.16 | 0.75 | -0.12 | 0.057 |
| 65.00 | -33.47 | -2.45 | 0.00 | -240.74 | 0.00 | 240.74 | 4,313.43 | 2,156.72 | 9,942.96 | 4,978.87 | 0.89 | -0.14 | 0.056 |
| 70.00 | -32.12 | -2.40 | 0.00 | -228.47 | 0.00 | 228.47 | 4,257.46 | 2,128.73 | 9,592.32 | 4,803.29 | 1.03 | -0.15 | 0.055 |
| 75.00 | -30.80 | -2.36 | 0.00 | -216.47 | 0.00 | 216.47 | 4,199.61 | 2,099.81 | 9,243.38 | 4,628.56 | 1.20 | -0.16 | 0.054 |
| 80.00 | -29.50 | -2.32 | 0.00 | -204.69 | 0.00 | 204.69 | 4,139.90 | 2,069.95 | 8,896.44 | 4,454.83 | 1.37 | -0.17 | 0.053 |
| 85.00 | -28.22 | -2.31 | 0.00 | -193.08 | 0.00 | 193.08 | 4,078.31 | 2,039.15 | 8,551.80 | 4,282.26 | 1.56 | -0.19 | 0.052 |
| 90.00 | -26.97 | -2.31 | 0.00 | -181.55 | 0.00 | 181.55 | 4,014.84 | 2,007.42 | 8,209.74 | 4,110.97 | 1.77 | -0.20 | 0.051 |
| 91.42 | -26.62 | -2.31 | 0.00 | -178.28 | 0.00 | 178.28 | 3,996.52 | 1,998.26 | 8,113.33 | 4,062.70 | 1.83 | -0.20 | 0.051 |
| 95.00 | -25.19 | -2.31 | 0.00 | -170.01 | 0.00 | 170.01 | 3,949.51 | 1,974.76 | 7,870.56 | 3,941.13 | 1.98 | -0.21 | 0.050 |
| 98.00 | -24.02 | -2.30 | 0.00 | -163.10 | 0.00 | 163.10 | 3,056.80 | 1,528.40 | 6,090.92 | 3,049.99 | 2.12 | -0.22 | 0.061 |
| 100.00 | -23.60 | -2.31 | 0.00 | -158.49 | 0.00 | 158.49 | 3,039.33 | 1,519.67 | 5,992.84 | 3,000.87 | 2.22 | -0.23 | 0.061 |
| 105.00 | -22.54 | -2.31 | 0.00 | -146.95 | 0.00 | 146.95 | 2,994.36 | 1,497.18 | 5,748.30 | 2,878.42 | 2.46 | -0.24 | 0.059 |
| 110.00 | -21.51 | -2.31 | 0.00 | -135.40 | 0.00 | 135.40 | 2,947.52 | 1,473.76 | 5,504.94 | 2,756.56 | 2.73 | -0.26 | 0.056 |
| 115.00 | -20.49 | -2.31 | 0.00 | -123.85 | 0.00 | 123.85 | 2,898.80 | 1,449.40 | 5,263.06 | 2,635.44 | 3.01 | -0.28 | 0.054 |
| 116.00 | -18.14 | -2.30 | 0.00 | -121.54 | 0.00 | 121.54 | 2,888.83 | 1,444.42 | 5,214.89 | 2,611.32 | 3.07 | -0.28 | 0.053 |
| 120.00 | -17.36 | -2.30 | 0.00 | -112.34 | 0.00 | 112.34 | 2,848.21 | 1,424.11 | 5,022.95 | 2,515.21 | 3.31 | -0.29 | 0.051 |
| 125.00 | -16.40 | -2.30 | 0.00 | -100.83 | 0.00 | 100.83 | 2,795.75 | 1,397.88 | 4,784.90 | 2,396.01 | 3.62 | -0.31 | 0.048 |
| 128.00 | -15.76 | -2.30 | 0.00 | -93.93 | 0.00 | 93.93 | 2,763.38 | 1,381.69 | 4,643.19 | 2,325.05 | 3.82 | -0.32 | 0.046 |
| 130.00 | -15.40 | -2.30 | 0.00 | -89.34 | 0.00 | 89.34 | 2,741.42 | 1,370.71 | 4,549.21 | 2,277.99 | 3.95 | -0.32 | 0.045 |
| 135.00 | -12.67 | -2.29 | 0.00 | -77.84 | 0.00 | 77.84 | 2,685.21 | 1,342.61 | 4,316.17 | 2,161.29 | 4.29 | -0.34 | 0.041 |
| 139.33 | -11.97 | -2.28 | 0.00 | -67.94 | 0.00 | 67.94 | 2,634.99 | 1,317.49 | 4,116.57 | 2,061.34 | 4.61 | -0.35 | 0.038 |
| 140.00 | -11.80 | -2.28 | 0.00 | -66.41 | 0.00 | 66.41 | 2,627.14 | 1,313.57 | 4,086.07 | 2,046.07 | 4.65 | -0.35 | 0.037 |
| 144.42 | -10.70 | -2.26 | 0.00 | -56.33 | 0.00 | 56.33 | 1,915.99 | 957.99 | 2,941.41 | 1,472.89 | 4.98 | -0.36 | 0.044 |
| 145.00 | -10.62 | -2.26 | 0.00 | -55.01 | 0.00 | 55.01 | 1,911.69 | 955.84 | 2,923.20 | 1,463.77 | 5.03 | -0.36 | 0.043 |
| 148.00 | -9.07 | -2.13 | 0.00 | -48.24 | 0.00 | 48.24 | 1,889.17 | 944.59 | 2,829.77 | 1,416.99 | 5.26 | -0.37 | 0.039 |
| 150.00 | -8.82 | -2.12 | 0.00 | -43.97 | 0.00 | 43.97 | 1,873.79 | 936.89 | 2,767.71 | 1,385.91 | 5.42 | -0.38 | 0.036 |
| 155.00 | -8.22 | -2.08 | 0.00 | -33.36 | 0.00 | 33.36 | 1,834.01 | 917.01 | 2,613.49 | 1,308.69 | 5.82 | -0.39 | 0.030 |
| 160.00 | -4.09 | -1.62 | 0.00 | -22.98 | 0.00 | 22.98 | 1,792.37 | 896.18 | 2,460.85 | 1,232.25 | 6.23 | -0.40 | 0.021 |
| 165.00 | -3.61 | -1.54 | 0.00 | -14.87 | 0.00 | 14.87 | 1,748.85 | 874.42 | 2,310.07 | 1,156.75 | 6.65 | -0.41 | 0.015 |
| 170.00 | -3.15 | -1.44 | 0.00 | -7.17 | 0.00 | 7.17 | 1,703.46 | 851.73 | 2,161.44 | 1,082.33 | 7.08 | -0.41 | 0.008 |
| 171.00 | -2.32 | -0.81 | 0.00 | -5.73 | 0.00 | 5.73 | 1,694.16 | 847.08 | 2,132.00 | 1,067.58 | 7.17 | -0.41 | 0.007 |
| 175.00 | -1.99 | -0.71 | 0.00 | -2.50 | 0.00 | 2.50 | 1,656.20 | 828.10 | 2,015.26 | 1,009.13 | 7.51 | -0.41 | 0.004 |
| 178.50 | 0.00 | -0.70 | 0.00 | 0.00 | 0.00 | 0.00 | 1,622.00 | 811.00 | 1,914.55 | 958.70 | 7.81 | -0.41 | 0.000 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)



© 2007 - 2014 by ATC IP LLC. All rights reserved.

| | | |
|-------------------------------|--------------------------|-------------------------------|
| Load Case: 1.0D + 1.0W | 60.00 mph Serviceability | 21 Iterations |
| Gust Response Factor : 1.10 | | Wind Importance Factor : 1.00 |
| Dead Load Factor : 1.00 | | |
| Wind Load Factor : 1.00 | | |


Shaft Segment Forces (Factored)

| Seg Top Elev (ft) | Description | Kzt | Kz | qz (psf) | qzGh (psf) | C (mph-ft) | Cf | Ice Thick (in) | Tributary (ft) | Ap (sf) | EPAs (sf) | Wind Force X (lb) | Dead Load Ice (lb) | Tot Dead Load (lb) | |
|-------------------|-----------------|------|------|----------|------------|------------|-------|----------------|----------------|---------|-----------|-------------------|--------------------|--------------------|------------------|
| 0.00 | | 1.00 | 0.70 | 6.129 | 6.742 | 305.84 | 0.650 | 0.000 | 0.00 | 0.000 | 0.00 | 0.0 | 0.0 | 0.0 | |
| 5.00 | | 1.00 | 0.70 | 6.129 | 6.742 | 300.50 | 0.650 | * 0.000 | 5.00 | 30.197 | 19.63 | 132.3 | 0.0 | 1,675.8 | |
| 10.00 | | 1.00 | 0.70 | 6.129 | 6.742 | 295.16 | 0.650 | * 0.000 | 5.00 | 29.665 | 19.28 | 130.0 | 0.0 | 1,646.1 | |
| 15.00 | | 1.00 | 0.70 | 6.129 | 6.742 | 289.82 | 0.650 | * 0.000 | 5.00 | 29.133 | 18.94 | 127.7 | 0.0 | 1,616.4 | |
| 20.00 | Appertunance(s) | 1.00 | 0.70 | 6.129 | 6.742 | 284.48 | 0.650 | * 0.000 | 5.00 | 28.601 | 18.59 | 125.3 | 0.0 | 1,586.7 | |
| 25.00 | | 1.00 | 0.70 | 6.129 | 6.742 | 279.14 | 0.650 | * 0.000 | 5.00 | 28.070 | 18.25 | 123.0 | 0.0 | 1,557.0 | |
| 30.00 | | 1.00 | 0.70 | 6.134 | 6.747 | 273.92 | 0.650 | * 0.000 | 5.00 | 27.538 | 17.90 | 120.8 | 0.0 | 1,527.3 | |
| 35.00 | | 1.00 | 0.73 | 6.410 | 7.051 | 274.56 | 0.650 | * 0.000 | 5.00 | 27.006 | 17.55 | 123.8 | 0.0 | 1,497.6 | |
| 40.00 | | 1.00 | 0.76 | 6.659 | 7.325 | 274.28 | 0.650 | * 0.000 | 5.00 | 26.474 | 17.21 | 126.1 | 0.0 | 1,467.9 | |
| 45.00 | Bot - Section 2 | 1.00 | 0.78 | 6.887 | 7.576 | 273.27 | 0.650 | * 0.000 | 5.00 | 25.942 | 16.86 | 127.7 | 0.0 | 1,438.2 | |
| 50.00 | | 1.00 | 0.81 | 7.098 | 7.807 | 271.67 | 0.650 | * 0.000 | 5.00 | 25.728 | 16.72 | 130.6 | 0.0 | 2,632.3 | |
| 53.00 | Top - Section 1 | 1.00 | 0.82 | 7.217 | 7.939 | 270.46 | 0.650 | * 0.000 | 3.00 | 15.181 | 9.87 | 78.3 | 0.0 | 1,552.9 | |
| 55.00 | | 1.00 | 0.83 | 7.294 | 8.023 | 273.04 | 0.650 | * 0.000 | 2.00 | 10.015 | 6.51 | 52.2 | 0.0 | 476.3 | |
| 60.00 | | 1.00 | 0.85 | 7.477 | 8.225 | 270.56 | 0.650 | * 0.000 | 5.00 | 24.664 | 16.03 | 131.9 | 0.0 | 1,172.9 | |
| 65.00 | | 1.00 | 0.87 | 7.650 | 8.415 | 267.71 | 0.650 | * 0.000 | 5.00 | 24.132 | 15.69 | 132.0 | 0.0 | 1,147.4 | |
| 70.00 | | 1.00 | 0.89 | 7.814 | 8.595 | 264.53 | 0.650 | * 0.000 | 5.00 | 23.600 | 15.34 | 131.9 | 0.0 | 1,122.0 | |
| 75.00 | | 1.00 | 0.91 | 7.969 | 8.766 | 261.06 | 0.650 | * 0.000 | 5.00 | 23.069 | 14.99 | 131.4 | 0.0 | 1,096.5 | |
| 80.00 | | 1.00 | 0.92 | 8.118 | 8.930 | 257.33 | 0.650 | * 0.000 | 5.00 | 22.537 | 14.65 | 130.8 | 0.0 | 1,071.1 | |
| 85.00 | | 1.00 | 0.94 | 8.260 | 9.086 | 253.37 | 0.650 | * 0.000 | 5.00 | 22.005 | 14.30 | 130.0 | 0.0 | 1,045.6 | |
| 90.00 | | 1.00 | 0.95 | 8.396 | 9.235 | 249.20 | 0.650 | * 0.000 | 5.00 | 21.473 | 13.96 | 128.9 | 0.0 | 1,020.1 | |
| 91.42 | Bot - Section 3 | 1.00 | 0.96 | 8.433 | 9.276 | 247.98 | 0.650 | * 0.000 | 1.42 | 5.987 | 3.89 | 36.1 | 0.0 | 284.4 | |
| 95.00 | | 1.00 | 0.97 | 8.526 | 9.379 | 244.83 | 0.650 | * 0.000 | 3.58 | 15.143 | 9.84 | 92.3 | 0.0 | 1,310.5 | |
| 98.00 | Top - Section 2 | 1.00 | 0.98 | 8.602 | 9.463 | 242.13 | 0.650 | * 0.000 | 3.00 | 12.468 | 8.10 | 76.7 | 0.0 | 1,078.7 | |
| 100.0 | | 1.00 | 0.98 | 8.652 | 9.517 | 243.45 | 0.650 | * 0.000 | 2.00 | 8.206 | 5.33 | 50.8 | 0.0 | 325.2 | |
| 105.0 | | 1.00 | 1.00 | 8.774 | 9.651 | 238.76 | 0.650 | * 0.000 | 5.00 | 20.142 | 13.09 | 126.4 | 0.0 | 798.1 | |
| 110.0 | | 1.00 | 1.01 | 8.891 | 9.780 | 233.92 | 1.200 | * 0.000 | 5.00 | 19.610 | 23.53 | 230.1 | 0.0 | 776.9 | |
| 115.0 | | 1.00 | 1.02 | 9.005 | 9.905 | 228.94 | 1.200 | * 0.000 | 5.00 | 19.078 | 22.89 | 226.8 | 0.0 | 755.7 | |
| 116.0 | Appertunance(s) | 1.00 | 1.03 | 9.027 | 9.930 | 227.93 | 1.200 | * 0.000 | 1.00 | 3.752 | 4.50 | 44.7 | 0.0 | 148.6 | |
| 120.0 | | 1.00 | 1.04 | 9.115 | 10.02 | 223.82 | 0.650 | * 0.000 | 4.00 | 14.795 | 9.62 | 96.4 | 0.0 | 585.9 | |
| 125.0 | | 1.00 | 1.05 | 9.222 | 10.14 | 218.58 | 0.650 | * 0.000 | 5.00 | 18.015 | 11.71 | 118.8 | 0.0 | 713.2 | |
| 128.0 | Appertunance(s) | 1.00 | 1.06 | 9.284 | 10.21 | 215.38 | 0.650 | * 0.000 | 3.00 | 10.554 | 6.86 | 70.1 | 0.0 | 417.8 | |
| 130.0 | | 1.00 | 1.06 | 9.326 | 10.25 | 213.22 | 0.650 | * 0.000 | 2.00 | 6.929 | 4.50 | 46.2 | 0.0 | 274.3 | |
| 135.0 | Appertunance(s) | 1.00 | 1.07 | 9.427 | 10.36 | 207.75 | 0.650 | * 0.000 | 5.00 | 16.951 | 11.02 | 114.3 | 0.0 | 670.8 | |
| 139.3 | Bot - Section 4 | 1.00 | 1.08 | 9.512 | 10.46 | 202.93 | 0.650 | * 0.000 | 4.33 | 14.261 | 9.27 | 97.0 | 0.0 | 564.2 | |
| 140.0 | | 1.00 | 1.08 | 9.525 | 10.47 | 202.18 | 0.650 | * 0.000 | 0.67 | 2.187 | 1.42 | 14.9 | 0.0 | 154.7 | |
| 144.4 | Top - Section 3 | 1.00 | 1.09 | 9.610 | 10.57 | 197.17 | 0.650 | * 0.000 | 4.42 | 14.248 | 9.26 | 97.9 | 0.0 | 1,007.8 | |
| 145.0 | | 1.00 | 1.09 | 9.621 | 10.58 | 199.17 | 0.650 | * 0.000 | 0.58 | 1.851 | 1.20 | 12.7 | 0.0 | 58.7 | |
| 148.0 | Appertunance(s) | 1.00 | 1.10 | 9.678 | 10.64 | 195.72 | 0.650 | * 0.000 | 3.00 | 9.404 | 6.11 | 65.1 | 0.0 | 298.0 | |
| 150.0 | | 1.00 | 1.11 | 9.715 | 10.68 | 193.41 | 0.650 | 0.000 | 2.00 | 6.163 | 4.01 | 42.8 | 0.0 | 195.3 | |
| 155.0 | | 1.00 | 1.12 | 9.806 | 10.78 | 187.56 | 0.650 | 0.000 | 5.00 | 15.035 | 9.77 | 105.4 | 0.0 | 476.4 | |
| 160.0 | Appertunance(s) | 1.00 | 1.13 | 9.896 | 10.88 | 181.63 | 0.650 | 0.000 | 5.00 | 14.503 | 9.43 | 102.6 | 0.0 | 459.4 | |
| 165.0 | | 1.00 | 1.14 | 9.983 | 10.98 | 175.62 | 0.650 | 0.000 | 5.00 | 13.972 | 9.08 | 99.7 | 0.0 | 442.4 | |
| 170.0 | | 1.00 | 1.15 | 10.069 | 11.07 | 169.52 | 0.650 | 0.000 | 5.00 | 13.440 | 8.74 | 96.8 | 0.0 | 425.5 | |
| 171.0 | Appertunance(s) | 1.00 | 1.15 | 10.085 | 11.09 | 168.30 | 0.650 | 0.000 | 1.00 | 2.624 | 1.71 | 18.9 | 0.0 | 83.1 | |
| 175.0 | | 1.00 | 1.16 | 10.152 | 11.16 | 163.36 | 0.650 | 0.000 | 4.00 | 10.284 | 6.68 | 74.6 | 0.0 | 325.4 | |
| 178.5 | Appertunance(s) | 1.00 | 1.16 | 10.210 | 11.23 | 158.99 | 0.650 | 0.000 | 3.50 | 8.719 | 5.67 | 63.7 | 0.0 | 275.8 | |
| | | | | | | | | Totals: | 535.50 | | | | 111,300.6 | 0.0 | 121,696.9 |

* = Cf Adjusted By Linear Load Ra Effect

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)



© 2007 - 2014 by ATC IP LLC. All rights reserved.

Load Case: 1.0D + 1.0W 60.00 mph Serviceability 21 Iterations

Gust Response Factor : 1.10 Wind Importance Factor : 1.00

Dead Load Factor : 1.00


Wind Load Factor : 1.00

Discrete Appurtenance Segment Forces (Factored)

| Elev (ft) | Description | Qty | qz (psf) | qzGh (psf) | Orientation Factor | Ka | Total EPAa (sf) | Horiz Ecc (ft) | Vert Ecc (ft) | Wind FX (lb) | Mom Y (lb-ft) | Mom Z (lb-ft) | Dead Load (lb) |
|-----------|----------------------|-----|----------|------------|--------------------|------|-----------------|----------------|---------------|--------------|---------------|---------------|----------------|
| 20.00 | PCTEL GPS-TMG-HR- | 1 | 6.129 | 6.742 | 1.00 | 1.00 | 0.09 | 0.000 | 0.000 | 0.61 | 0.00 | 0.00 | 0.60 |
| 20.00 | Standoff | 1 | 6.129 | 6.742 | 1.00 | 1.00 | 1.63 | 0.000 | 0.000 | 10.99 | 0.00 | 0.00 | 40.00 |
| 116.0 | Alcatel-Lucent 800 M | 3 | 9.027 | 9.930 | 0.67 | 0.80 | 3.43 | 0.000 | 0.000 | 34.01 | 0.00 | 0.00 | 159.00 |
| 116.0 | Alcatel-Lucent 1900 | 3 | 9.027 | 9.930 | 0.67 | 0.80 | 3.73 | 0.000 | 0.000 | 37.04 | 0.00 | 0.00 | 180.00 |
| 116.0 | Flat Low Profile Pla | 1 | 9.027 | 9.930 | 1.00 | 1.00 | 26.10 | 0.000 | 0.000 | 259.16 | 0.00 | 0.00 | 1,500.00 |
| 116.0 | RFS APXVSP18-C- | 3 | 9.071 | 9.978 | 0.83 | 0.80 | 15.98 | 0.000 | 2.000 | 159.41 | 0.00 | 318.82 | 171.00 |
| 116.0 | Alcatel-Lucent TD-RR | 3 | 9.027 | 9.930 | 0.67 | 0.80 | 6.51 | 0.000 | 0.000 | 64.67 | 0.00 | 0.00 | 210.00 |
| 116.0 | RFS APXV9TM14-ALU- | 3 | 9.071 | 9.978 | 0.78 | 0.80 | 11.87 | 0.000 | 2.000 | 118.43 | 0.00 | 236.85 | 165.30 |
| 128.0 | RFS APXV18-206517S- | 3 | 9.284 | 10.213 | 0.80 | 1.00 | 12.41 | 0.000 | 0.000 | 126.72 | 0.00 | 0.00 | 79.20 |
| 135.0 | Round Low Profile PI | 1 | 9.427 | 10.369 | 1.00 | 1.00 | 21.70 | 0.000 | 0.000 | 225.02 | 0.00 | 0.00 | 1,500.00 |
| 135.0 | Antel BXA-171063-12B | 3 | 9.486 | 10.435 | 0.88 | 0.80 | 9.99 | 0.000 | 3.000 | 104.24 | 0.00 | 312.72 | 45.00 |
| 135.0 | Antel BXA-70063-6CF- | 3 | 9.486 | 10.435 | 0.77 | 0.80 | 13.99 | 0.000 | 3.000 | 145.98 | 0.00 | 437.93 | 51.00 |
| 135.0 | RFS FD9R6004/2C-3L | 6 | 9.486 | 10.435 | 0.50 | 0.80 | 0.89 | 0.000 | 3.000 | 9.27 | 0.00 | 27.80 | 15.60 |
| 135.0 | Antel BXA-80063-6BF- | 3 | 9.486 | 10.435 | 0.78 | 0.80 | 13.59 | 0.000 | 3.000 | 141.82 | 0.00 | 425.45 | 57.60 |
| 135.0 | Antel BXA-171063-8BF | 3 | 9.486 | 10.435 | 0.87 | 0.80 | 6.14 | 0.000 | 3.000 | 64.06 | 0.00 | 192.17 | 31.50 |
| 135.0 | Alcatel-Lucent RRH2x | 3 | 9.486 | 10.435 | 0.67 | 0.80 | 3.49 | 0.000 | 3.000 | 36.46 | 0.00 | 109.38 | 132.00 |
| 135.0 | RFS DB-T1-6Z-8AB-OZ | 1 | 9.486 | 10.435 | 1.00 | 0.80 | 3.84 | 0.000 | 3.000 | 40.07 | 0.00 | 120.21 | 44.00 |
| 135.0 | Alcatel-Lucent RRH2x | 3 | 9.486 | 10.435 | 0.67 | 0.80 | 3.41 | 0.000 | 3.000 | 35.57 | 0.00 | 106.72 | 150.00 |
| 148.0 | T-Arm w/ Working Pla | 3 | 9.678 | 10.645 | 0.67 | 0.75 | 19.45 | 0.000 | 0.000 | 207.02 | 0.00 | 0.00 | 750.00 |
| 148.0 | Ericsson KRY 112 144 | 3 | 9.678 | 10.645 | 0.50 | 0.80 | 0.49 | 0.000 | 0.000 | 5.24 | 0.00 | 0.00 | 33.00 |
| 148.0 | Ericsson AIR 21, 1,3 | 3 | 9.678 | 10.645 | 0.86 | 0.80 | 12.49 | 0.000 | 0.000 | 132.93 | 0.00 | 0.00 | 249.00 |
| 148.0 | Ericsson AIR 21, 1,3 | 3 | 9.678 | 10.645 | 0.85 | 0.80 | 12.42 | 0.000 | 0.000 | 132.25 | 0.00 | 0.00 | 244.50 |
| 160.0 | Powerwave 7020 | 3 | 9.896 | 10.885 | 0.33 | 0.75 | 0.30 | 0.000 | 0.000 | 3.23 | 0.00 | 0.00 | 6.60 |
| 160.0 | 14" x 9" TTA | 6 | 9.896 | 10.885 | 0.33 | 0.75 | 1.56 | 0.000 | 0.000 | 16.97 | 0.00 | 0.00 | 60.00 |
| 160.0 | Raycap DC6-48-60-18- | 3 | 9.896 | 10.885 | 1.00 | 0.75 | 2.50 | 0.000 | 0.000 | 27.19 | 0.00 | 0.00 | 60.00 |
| 160.0 | CCI | 3 | 9.896 | 10.885 | 0.50 | 0.75 | 1.54 | 0.000 | 0.000 | 16.78 | 0.00 | 0.00 | 57.60 |
| 160.0 | Ericsson RRUS A2 | 6 | 9.896 | 10.885 | 0.67 | 0.75 | 6.21 | 0.000 | 0.000 | 67.61 | 0.00 | 0.00 | 132.00 |
| 160.0 | Ericsson RRUS 11 (Ba | 6 | 9.896 | 10.885 | 0.67 | 0.75 | 8.41 | 0.000 | 0.000 | 91.56 | 0.00 | 0.00 | 304.20 |
| 160.0 | Ericsson RRUS-12 B2 | 6 | 9.896 | 10.885 | 0.67 | 0.75 | 9.50 | 0.000 | 0.000 | 103.38 | 0.00 | 0.00 | 348.00 |
| 160.0 | Ericsson RRUS E2 B29 | 3 | 9.896 | 10.885 | 0.67 | 0.75 | 4.75 | 0.000 | 0.000 | 51.69 | 0.00 | 0.00 | 180.00 |
| 160.0 | Ericsson RRUS-32 | 3 | 9.896 | 10.885 | 0.67 | 0.75 | 4.99 | 0.000 | 0.000 | 54.32 | 0.00 | 0.00 | 231.00 |
| 160.0 | Powerwave 7770.00 | 3 | 9.896 | 10.885 | 0.77 | 0.75 | 9.55 | 0.000 | 0.000 | 103.91 | 0.00 | 0.00 | 105.00 |
| 160.0 | CCI HPA-65R-BUU-H6 | 9 | 9.896 | 10.885 | 0.83 | 0.75 | 54.12 | 0.000 | 0.000 | 589.11 | 0.00 | 0.00 | 459.00 |
| 160.0 | Flat Platform w/ Han | 1 | 9.896 | 10.885 | 1.00 | 1.00 | 42.40 | 0.000 | 0.000 | 461.53 | 0.00 | 0.00 | 2,000.00 |
| 171.0 | Side Arms | 1 | 10.085 | 11.094 | 1.00 | 1.00 | 8.50 | 0.000 | 0.000 | 94.30 | 0.00 | 0.00 | 560.00 |
| 171.0 | DragonWave A-ANT- | 1 | 10.085 | 11.094 | 1.00 | 0.80 | 3.75 | 0.000 | 0.000 | 41.62 | 0.00 | 0.00 | 27.00 |
| 171.0 | NextNet BTS-2500 | 3 | 10.085 | 11.094 | 0.50 | 0.80 | 2.18 | 0.000 | 0.000 | 24.23 | 0.00 | 0.00 | 105.00 |
| 171.0 | Argus LLPX310R | 3 | 10.085 | 11.094 | 0.73 | 0.80 | 7.52 | 0.000 | 0.000 | 83.38 | 0.00 | 0.00 | 85.80 |
| 171.0 | DragonWave Horizon | 2 | 10.085 | 11.094 | 0.33 | 0.80 | 0.23 | 0.000 | 0.000 | 2.52 | 0.00 | 0.00 | 21.20 |
| 171.0 | DragonWave A-ANT- | 1 | 10.085 | 11.094 | 1.00 | 0.80 | 3.75 | 0.000 | 0.000 | 41.62 | 0.00 | 0.00 | 27.00 |
| 178.5 | 72" x 12" Panel | 3 | 10.251 | 11.276 | 0.79 | 0.80 | 15.41 | 0.000 | 2.500 | 173.81 | 0.00 | 434.52 | 135.00 |
| 178.5 | 48" x 12" Panel | 9 | 10.251 | 11.276 | 0.78 | 0.80 | 28.47 | 0.000 | 2.500 | 321.05 | 0.00 | 802.63 | 270.00 |
| 178.5 | Flat Low Profile Pla | 1 | 10.210 | 11.231 | 1.00 | 1.00 | 26.10 | 0.000 | 0.000 | 293.13 | 0.00 | 0.00 | 1,500.00 |
| | | | | | | | | | | 4,753.89 | | | 38,696.68 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)



Load Case: 1.0D + 1.0W

60.00 mph Serviceability

21 Iterations

Gust Response Factor : 1.10
 Dead Load Factor : 1.00
 Wind Load Factor : 1.00


Wind Importance Factor : 1.00

Linear Appurtenance Segment Forces (Factored)

| Seg Top Elev (ft) | Description | Exposed To Wind | Length (ft) | Ca | Exposed Width (in) | Area (sqft) | CaAa (sqft) | qz (psf) | Ra | Cf Adjust Factor | FX (lb) | Dead Load (lb) |
|-------------------|----------------------|-----------------|-------------|-------|--------------------|-------------|-------------|----------|-------|------------------|---------|----------------|
| 5.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.129 | 0.130 | 1.090 | 0.00 | 1.50 |
| 5.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 6.129 | 0.130 | 1.090 | 0.00 | 36.50 |
| 5.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 6.129 | 0.130 | 1.090 | 0.00 | 24.60 |
| 5.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.129 | 0.130 | 1.090 | 0.00 | 12.30 |
| 5.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 6.129 | 0.130 | 1.090 | 0.00 | 24.60 |
| 5.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 6.129 | 0.130 | 1.090 | 0.00 | 5.00 |
| 5.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 6.129 | 0.130 | 1.090 | 0.00 | 15.00 |
| 5.00 | (1) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.129 | 0.130 | 1.090 | 0.00 | 0.75 |
| 10.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.129 | 0.132 | 1.097 | 0.00 | 1.50 |
| 10.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 6.129 | 0.132 | 1.097 | 0.00 | 36.50 |
| 10.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 6.129 | 0.132 | 1.097 | 0.00 | 24.60 |
| 10.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.129 | 0.132 | 1.097 | 0.00 | 12.30 |
| 10.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 6.129 | 0.132 | 1.097 | 0.00 | 24.60 |
| 10.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 6.129 | 0.132 | 1.097 | 0.00 | 5.00 |
| 10.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 6.129 | 0.132 | 1.097 | 0.00 | 15.00 |
| 10.00 | (1) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.129 | 0.132 | 1.097 | 0.00 | 0.75 |
| 15.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.129 | 0.135 | 1.105 | 0.00 | 1.50 |
| 15.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 6.129 | 0.135 | 1.105 | 0.00 | 36.50 |
| 15.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 6.129 | 0.135 | 1.105 | 0.00 | 24.60 |
| 15.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.129 | 0.135 | 1.105 | 0.00 | 12.30 |
| 15.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 6.129 | 0.135 | 1.105 | 0.00 | 24.60 |
| 15.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 6.129 | 0.135 | 1.105 | 0.00 | 5.00 |
| 15.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 6.129 | 0.135 | 1.105 | 0.00 | 15.00 |
| 15.00 | (1) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.129 | 0.135 | 1.105 | 0.00 | 0.75 |
| 20.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.129 | 0.137 | 1.112 | 0.00 | 1.50 |
| 20.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 6.129 | 0.137 | 1.112 | 0.00 | 36.50 |
| 20.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 6.129 | 0.137 | 1.112 | 0.00 | 24.60 |
| 20.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.129 | 0.137 | 1.112 | 0.00 | 12.30 |
| 20.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 6.129 | 0.137 | 1.112 | 0.00 | 24.60 |
| 20.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 6.129 | 0.137 | 1.112 | 0.00 | 5.00 |
| 20.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 6.129 | 0.137 | 1.112 | 0.00 | 15.00 |
| 20.00 | (1) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.129 | 0.137 | 1.112 | 0.00 | 0.75 |
| 25.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.129 | 0.140 | 1.120 | 0.00 | 1.50 |
| 25.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 6.129 | 0.140 | 1.120 | 0.00 | 36.50 |
| 25.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 6.129 | 0.140 | 1.120 | 0.00 | 24.60 |
| 25.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.129 | 0.140 | 1.120 | 0.00 | 12.30 |
| 25.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 6.129 | 0.140 | 1.120 | 0.00 | 24.60 |
| 25.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 6.129 | 0.140 | 1.120 | 0.00 | 5.00 |
| 25.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 6.129 | 0.140 | 1.120 | 0.00 | 15.00 |
| 30.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.134 | 0.143 | 1.128 | 0.00 | 1.50 |
| 30.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 6.134 | 0.143 | 1.128 | 0.00 | 36.50 |
| 30.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 6.134 | 0.143 | 1.128 | 0.00 | 24.60 |
| 30.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.134 | 0.143 | 1.128 | 0.00 | 12.30 |
| 30.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 6.134 | 0.143 | 1.128 | 0.00 | 24.60 |
| 30.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 6.134 | 0.143 | 1.128 | 0.00 | 5.00 |
| 30.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 6.134 | 0.143 | 1.128 | 0.00 | 15.00 |
| 35.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.410 | 0.145 | 1.136 | 0.00 | 1.50 |
| 35.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 6.410 | 0.145 | 1.136 | 0.00 | 36.50 |
| 35.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 6.410 | 0.145 | 1.136 | 0.00 | 24.60 |
| 35.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.410 | 0.145 | 1.136 | 0.00 | 12.30 |
| 35.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 6.410 | 0.145 | 1.136 | 0.00 | 24.60 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)



© 2007 - 2014 by ATC IP LLC. All rights reserved.

Load Case: 1.0D + 1.0W **60.00 mph Serviceability** **21 Iterations**

Gust Response Factor : 1.10 Wind Importance Factor : 1.00


Dead Load Factor : 1.00

Wind Load Factor : 1.00

| | | | | | | | | | | | | |
|-------|----------------------|-----|------|-------|------|------|------|-------|-------|-------|------|-------|
| 35.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 6.410 | 0.145 | 1.136 | 0.00 | 5.00 |
| 35.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 6.410 | 0.145 | 1.136 | 0.00 | 15.00 |
| 40.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.659 | 0.148 | 1.145 | 0.00 | 1.50 |
| 40.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 6.659 | 0.148 | 1.145 | 0.00 | 36.50 |
| 40.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 6.659 | 0.148 | 1.145 | 0.00 | 24.60 |
| 40.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.659 | 0.148 | 1.145 | 0.00 | 12.30 |
| 40.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 6.659 | 0.148 | 1.145 | 0.00 | 24.60 |
| 40.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 6.659 | 0.148 | 1.145 | 0.00 | 5.00 |
| 40.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 6.659 | 0.148 | 1.145 | 0.00 | 15.00 |
| 45.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.887 | 0.151 | 1.154 | 0.00 | 1.50 |
| 45.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 6.887 | 0.151 | 1.154 | 0.00 | 36.50 |
| 45.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 6.887 | 0.151 | 1.154 | 0.00 | 24.60 |
| 45.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 6.887 | 0.151 | 1.154 | 0.00 | 12.30 |
| 45.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 6.887 | 0.151 | 1.154 | 0.00 | 24.60 |
| 45.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 6.887 | 0.151 | 1.154 | 0.00 | 5.00 |
| 45.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 6.887 | 0.151 | 1.154 | 0.00 | 15.00 |
| 50.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 7.098 | 0.155 | 1.164 | 0.00 | 1.50 |
| 50.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 7.098 | 0.155 | 1.164 | 0.00 | 36.50 |
| 50.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 7.098 | 0.155 | 1.164 | 0.00 | 24.60 |
| 50.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 7.098 | 0.155 | 1.164 | 0.00 | 12.30 |
| 50.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 7.098 | 0.155 | 1.164 | 0.00 | 24.60 |
| 50.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 7.098 | 0.155 | 1.164 | 0.00 | 5.00 |
| 50.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 7.098 | 0.155 | 1.164 | 0.00 | 15.00 |
| 53.00 | (2) 1/2" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 7.217 | 0.157 | 1.172 | 0.00 | 0.90 |
| 53.00 | (2) 2" Conduit | Yes | 3.00 | 0.000 | 2.38 | 0.60 | 0.00 | 7.217 | 0.157 | 1.172 | 0.00 | 21.90 |
| 53.00 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 0.50 | 0.00 | 7.217 | 0.157 | 1.172 | 0.00 | 14.76 |
| 53.00 | (3) 1 5/8" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 7.217 | 0.157 | 1.172 | 0.00 | 7.38 |
| 53.00 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 0.50 | 0.00 | 7.217 | 0.157 | 1.172 | 0.00 | 14.76 |
| 53.00 | (1) 1 1/4" Hybriflex | Yes | 3.00 | 0.000 | 1.54 | 0.38 | 0.00 | 7.217 | 0.157 | 1.172 | 0.00 | 3.00 |
| 53.00 | (3) 1 1/4" Hybriflex | Yes | 3.00 | 0.000 | 1.55 | 0.39 | 0.00 | 7.217 | 0.157 | 1.172 | 0.00 | 9.00 |
| 55.00 | (2) 1/2" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 7.294 | 0.157 | 1.171 | 0.00 | 0.60 |
| 55.00 | (2) 2" Conduit | Yes | 2.00 | 0.000 | 2.38 | 0.40 | 0.00 | 7.294 | 0.157 | 1.171 | 0.00 | 14.60 |
| 55.00 | (6) 1 5/8" Coax | Yes | 2.00 | 0.000 | 1.98 | 0.33 | 0.00 | 7.294 | 0.157 | 1.171 | 0.00 | 9.84 |
| 55.00 | (3) 1 5/8" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 7.294 | 0.157 | 1.171 | 0.00 | 4.92 |
| 55.00 | (6) 1 5/8" Coax | Yes | 2.00 | 0.000 | 1.98 | 0.33 | 0.00 | 7.294 | 0.157 | 1.171 | 0.00 | 9.84 |
| 55.00 | (1) 1 1/4" Hybriflex | Yes | 2.00 | 0.000 | 1.54 | 0.26 | 0.00 | 7.294 | 0.157 | 1.171 | 0.00 | 2.00 |
| 55.00 | (3) 1 1/4" Hybriflex | Yes | 2.00 | 0.000 | 1.55 | 0.26 | 0.00 | 7.294 | 0.157 | 1.171 | 0.00 | 6.00 |
| 60.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 7.477 | 0.159 | 1.178 | 0.00 | 1.50 |
| 60.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 7.477 | 0.159 | 1.178 | 0.00 | 36.50 |
| 60.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 7.477 | 0.159 | 1.178 | 0.00 | 24.60 |
| 60.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 7.477 | 0.159 | 1.178 | 0.00 | 12.30 |
| 60.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 7.477 | 0.159 | 1.178 | 0.00 | 24.60 |
| 60.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 7.477 | 0.159 | 1.178 | 0.00 | 5.00 |
| 60.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 7.477 | 0.159 | 1.178 | 0.00 | 15.00 |
| 65.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 7.650 | 0.163 | 1.188 | 0.00 | 1.50 |
| 65.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 7.650 | 0.163 | 1.188 | 0.00 | 36.50 |
| 65.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 7.650 | 0.163 | 1.188 | 0.00 | 24.60 |
| 65.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 7.650 | 0.163 | 1.188 | 0.00 | 12.30 |
| 65.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 7.650 | 0.163 | 1.188 | 0.00 | 24.60 |
| 65.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 7.650 | 0.163 | 1.188 | 0.00 | 5.00 |
| 65.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 7.650 | 0.163 | 1.188 | 0.00 | 15.00 |
| 70.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 7.814 | 0.166 | 1.199 | 0.00 | 1.50 |
| 70.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 7.814 | 0.166 | 1.199 | 0.00 | 36.50 |
| 70.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 7.814 | 0.166 | 1.199 | 0.00 | 24.60 |
| 70.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 7.814 | 0.166 | 1.199 | 0.00 | 12.30 |
| 70.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 7.814 | 0.166 | 1.199 | 0.00 | 24.60 |
| 70.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 7.814 | 0.166 | 1.199 | 0.00 | 5.00 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)



© 2007 - 2014 by ATC IP LLC. All rights reserved.

Load Case: 1.0D + 1.0W **60.00 mph Serviceability** **21 Iterations**

Gust Response Factor : 1.10 **Wind Importance Factor : 1.00**


Dead Load Factor : 1.00

Wind Load Factor : 1.00

| | | | | | | | | | | | | |
|-------|----------------------|-----|------|-------|------|------|------|-------|-------|-------|------|-------|
| 70.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 7.814 | 0.166 | 1.199 | 0.00 | 15.00 |
| 75.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 7.969 | 0.170 | 1.211 | 0.00 | 1.50 |
| 75.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 7.969 | 0.170 | 1.211 | 0.00 | 36.50 |
| 75.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 7.969 | 0.170 | 1.211 | 0.00 | 24.60 |
| 75.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 7.969 | 0.170 | 1.211 | 0.00 | 12.30 |
| 75.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 7.969 | 0.170 | 1.211 | 0.00 | 24.60 |
| 75.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 7.969 | 0.170 | 1.211 | 0.00 | 5.00 |
| 75.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 7.969 | 0.170 | 1.211 | 0.00 | 15.00 |
| 80.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 8.118 | 0.174 | 1.223 | 0.00 | 1.50 |
| 80.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 8.118 | 0.174 | 1.223 | 0.00 | 36.50 |
| 80.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 8.118 | 0.174 | 1.223 | 0.00 | 24.60 |
| 80.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 8.118 | 0.174 | 1.223 | 0.00 | 12.30 |
| 80.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 8.118 | 0.174 | 1.223 | 0.00 | 24.60 |
| 80.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 8.118 | 0.174 | 1.223 | 0.00 | 5.00 |
| 80.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 8.118 | 0.174 | 1.223 | 0.00 | 15.00 |
| 85.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 8.260 | 0.179 | 1.236 | 0.00 | 1.50 |
| 85.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 8.260 | 0.179 | 1.236 | 0.00 | 36.50 |
| 85.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 8.260 | 0.179 | 1.236 | 0.00 | 24.60 |
| 85.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 8.260 | 0.179 | 1.236 | 0.00 | 12.30 |
| 85.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 8.260 | 0.179 | 1.236 | 0.00 | 24.60 |
| 85.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 8.260 | 0.179 | 1.236 | 0.00 | 5.00 |
| 85.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 8.260 | 0.179 | 1.236 | 0.00 | 15.00 |
| 90.00 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 8.396 | 0.183 | 1.249 | 0.00 | 1.50 |
| 90.00 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 8.396 | 0.183 | 1.249 | 0.00 | 36.50 |
| 90.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 8.396 | 0.183 | 1.249 | 0.00 | 24.60 |
| 90.00 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 8.396 | 0.183 | 1.249 | 0.00 | 12.30 |
| 90.00 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 8.396 | 0.183 | 1.249 | 0.00 | 24.60 |
| 90.00 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 8.396 | 0.183 | 1.249 | 0.00 | 5.00 |
| 90.00 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 8.396 | 0.183 | 1.249 | 0.00 | 15.00 |
| 91.42 | (2) 1/2" Coax | Yes | 1.42 | 0.000 | 0.00 | 0.00 | 0.00 | 8.433 | 0.186 | 1.258 | 0.00 | 0.43 |
| 91.42 | (2) 2" Conduit | Yes | 1.42 | 0.000 | 2.38 | 0.28 | 0.00 | 8.433 | 0.186 | 1.258 | 0.00 | 10.34 |
| 91.42 | (6) 1 5/8" Coax | Yes | 1.42 | 0.000 | 1.98 | 0.23 | 0.00 | 8.433 | 0.186 | 1.258 | 0.00 | 6.97 |
| 91.42 | (3) 1 5/8" Coax | Yes | 1.42 | 0.000 | 0.00 | 0.00 | 0.00 | 8.433 | 0.186 | 1.258 | 0.00 | 3.48 |
| 91.42 | (6) 1 5/8" Coax | Yes | 1.42 | 0.000 | 1.98 | 0.23 | 0.00 | 8.433 | 0.186 | 1.258 | 0.00 | 6.97 |
| 91.42 | (1) 1 1/4" Hybriflex | Yes | 1.42 | 0.000 | 1.54 | 0.18 | 0.00 | 8.433 | 0.186 | 1.258 | 0.00 | 1.42 |
| 91.42 | (3) 1 1/4" Hybriflex | Yes | 1.42 | 0.000 | 1.55 | 0.18 | 0.00 | 8.433 | 0.186 | 1.258 | 0.00 | 4.25 |
| 95.00 | (2) 1/2" Coax | Yes | 3.58 | 0.000 | 0.00 | 0.00 | 0.00 | 8.526 | 0.188 | 1.265 | 0.00 | 1.07 |
| 95.00 | (2) 2" Conduit | Yes | 3.58 | 0.000 | 2.38 | 0.71 | 0.00 | 8.526 | 0.188 | 1.265 | 0.00 | 26.16 |
| 95.00 | (6) 1 5/8" Coax | Yes | 3.58 | 0.000 | 1.98 | 0.59 | 0.00 | 8.526 | 0.188 | 1.265 | 0.00 | 17.63 |
| 95.00 | (3) 1 5/8" Coax | Yes | 3.58 | 0.000 | 0.00 | 0.00 | 0.00 | 8.526 | 0.188 | 1.265 | 0.00 | 8.81 |
| 95.00 | (6) 1 5/8" Coax | Yes | 3.58 | 0.000 | 1.98 | 0.59 | 0.00 | 8.526 | 0.188 | 1.265 | 0.00 | 17.63 |
| 95.00 | (1) 1 1/4" Hybriflex | Yes | 3.58 | 0.000 | 1.54 | 0.46 | 0.00 | 8.526 | 0.188 | 1.265 | 0.00 | 3.58 |
| 95.00 | (3) 1 1/4" Hybriflex | Yes | 3.58 | 0.000 | 1.55 | 0.46 | 0.00 | 8.526 | 0.188 | 1.265 | 0.00 | 10.75 |
| 98.00 | (2) 1/2" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 8.602 | 0.192 | 1.275 | 0.00 | 0.90 |
| 98.00 | (2) 2" Conduit | Yes | 3.00 | 0.000 | 2.38 | 0.60 | 0.00 | 8.602 | 0.192 | 1.275 | 0.00 | 21.90 |
| 98.00 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 0.50 | 0.00 | 8.602 | 0.192 | 1.275 | 0.00 | 14.76 |
| 98.00 | (3) 1 5/8" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 8.602 | 0.192 | 1.275 | 0.00 | 7.38 |
| 98.00 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 0.50 | 0.00 | 8.602 | 0.192 | 1.275 | 0.00 | 14.76 |
| 98.00 | (1) 1 1/4" Hybriflex | Yes | 3.00 | 0.000 | 1.54 | 0.38 | 0.00 | 8.602 | 0.192 | 1.275 | 0.00 | 3.00 |
| 98.00 | (3) 1 1/4" Hybriflex | Yes | 3.00 | 0.000 | 1.55 | 0.39 | 0.00 | 8.602 | 0.192 | 1.275 | 0.00 | 9.00 |
| 100.0 | (2) 1/2" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 8.652 | 0.192 | 1.275 | 0.00 | 0.60 |
| 100.0 | (2) 2" Conduit | Yes | 2.00 | 0.000 | 2.38 | 0.40 | 0.00 | 8.652 | 0.192 | 1.275 | 0.00 | 14.60 |
| 100.0 | (6) 1 5/8" Coax | Yes | 2.00 | 0.000 | 1.98 | 0.33 | 0.00 | 8.652 | 0.192 | 1.275 | 0.00 | 9.84 |
| 100.0 | (3) 1 5/8" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 8.652 | 0.192 | 1.275 | 0.00 | 4.92 |
| 100.0 | (6) 1 5/8" Coax | Yes | 2.00 | 0.000 | 1.98 | 0.33 | 0.00 | 8.652 | 0.192 | 1.275 | 0.00 | 9.84 |
| 100.0 | (1) 1 1/4" Hybriflex | Yes | 2.00 | 0.000 | 1.54 | 0.26 | 0.00 | 8.652 | 0.192 | 1.275 | 0.00 | 2.00 |
| 100.0 | (3) 1 1/4" Hybriflex | Yes | 2.00 | 0.000 | 1.55 | 0.26 | 0.00 | 8.652 | 0.192 | 1.275 | 0.00 | 6.00 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)



Load Case: 1.0D + 1.0W **60.00 mph Serviceability** **21 Iterations**

Gust Response Factor : 1.10 **Wind Importance Factor : 1.00**


Dead Load Factor : 1.00

Wind Load Factor : 1.00

| | | | | | | | | | | | | |
|-------|----------------------|-----|------|-------|------|------|------|-------|-------|-------|-------|-------|
| 105.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 8.774 | 0.195 | 1.285 | 0.00 | 1.50 |
| 105.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 8.774 | 0.195 | 1.285 | 0.00 | 36.50 |
| 105.0 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 8.774 | 0.195 | 1.285 | 0.00 | 24.60 |
| 105.0 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 8.774 | 0.195 | 1.285 | 0.00 | 12.30 |
| 105.0 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 8.774 | 0.195 | 1.285 | 0.00 | 24.60 |
| 105.0 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.54 | 0.64 | 0.00 | 8.774 | 0.195 | 1.285 | 0.00 | 5.00 |
| 105.0 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 0.000 | 1.55 | 0.65 | 0.00 | 8.774 | 0.195 | 1.285 | 0.00 | 15.00 |
| 110.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 8.891 | 0.200 | 0.000 | 0.00 | 1.50 |
| 110.0 | (2) 2" Conduit | Yes | 5.00 | 1.200 | 2.38 | 0.99 | 1.19 | 8.891 | 0.200 | 0.000 | 11.64 | 36.50 |
| 110.0 | (6) 1 5/8" Coax | Yes | 5.00 | 1.200 | 1.98 | 0.82 | 0.99 | 8.891 | 0.200 | 0.000 | 9.68 | 24.60 |
| 110.0 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 8.891 | 0.200 | 0.000 | 0.00 | 12.30 |
| 110.0 | (6) 1 5/8" Coax | Yes | 5.00 | 1.200 | 1.98 | 0.82 | 0.99 | 8.891 | 0.200 | 0.000 | 9.68 | 24.60 |
| 110.0 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 1.200 | 1.54 | 0.64 | 0.77 | 8.891 | 0.200 | 0.000 | 7.53 | 5.00 |
| 110.0 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 1.200 | 1.55 | 0.65 | 0.77 | 8.891 | 0.200 | 0.000 | 7.58 | 15.00 |
| 115.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 9.005 | 0.206 | 0.000 | 0.00 | 1.50 |
| 115.0 | (2) 2" Conduit | Yes | 5.00 | 1.200 | 2.38 | 0.99 | 1.19 | 9.005 | 0.206 | 0.000 | 11.79 | 36.50 |
| 115.0 | (6) 1 5/8" Coax | Yes | 5.00 | 1.200 | 1.98 | 0.82 | 0.99 | 9.005 | 0.206 | 0.000 | 9.81 | 24.60 |
| 115.0 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 9.005 | 0.206 | 0.000 | 0.00 | 12.30 |
| 115.0 | (6) 1 5/8" Coax | Yes | 5.00 | 1.200 | 1.98 | 0.82 | 0.99 | 9.005 | 0.206 | 0.000 | 9.81 | 24.60 |
| 115.0 | (1) 1 1/4" Hybriflex | Yes | 5.00 | 1.200 | 1.54 | 0.64 | 0.77 | 9.005 | 0.206 | 0.000 | 7.63 | 5.00 |
| 115.0 | (3) 1 1/4" Hybriflex | Yes | 5.00 | 1.200 | 1.55 | 0.65 | 0.77 | 9.005 | 0.206 | 0.000 | 7.68 | 15.00 |
| 116.0 | (2) 1/2" Coax | Yes | 1.00 | 0.000 | 0.00 | 0.00 | 0.00 | 9.027 | 0.209 | 0.000 | 0.00 | 0.30 |
| 116.0 | (2) 2" Conduit | Yes | 1.00 | 1.200 | 2.38 | 0.20 | 0.24 | 9.027 | 0.209 | 0.000 | 2.36 | 7.30 |
| 116.0 | (6) 1 5/8" Coax | Yes | 1.00 | 1.200 | 1.98 | 0.17 | 0.20 | 9.027 | 0.209 | 0.000 | 1.97 | 4.92 |
| 116.0 | (3) 1 5/8" Coax | Yes | 1.00 | 0.000 | 0.00 | 0.00 | 0.00 | 9.027 | 0.209 | 0.000 | 0.00 | 2.46 |
| 116.0 | (6) 1 5/8" Coax | Yes | 1.00 | 1.200 | 1.98 | 0.17 | 0.20 | 9.027 | 0.209 | 0.000 | 1.97 | 4.92 |
| 116.0 | (1) 1 1/4" Hybriflex | Yes | 1.00 | 1.200 | 1.54 | 0.13 | 0.15 | 9.027 | 0.209 | 0.000 | 1.53 | 1.00 |
| 116.0 | (3) 1 1/4" Hybriflex | Yes | 1.00 | 1.200 | 1.55 | 0.13 | 0.16 | 9.027 | 0.209 | 0.000 | 1.54 | 3.00 |
| 120.0 | (2) 1/2" Coax | Yes | 4.00 | 0.000 | 0.00 | 0.00 | 0.00 | 9.115 | 0.143 | 1.129 | 0.00 | 1.20 |
| 120.0 | (2) 2" Conduit | Yes | 4.00 | 0.000 | 2.38 | 0.79 | 0.00 | 9.115 | 0.143 | 1.129 | 0.00 | 29.20 |
| 120.0 | (6) 1 5/8" Coax | Yes | 4.00 | 0.000 | 1.98 | 0.66 | 0.00 | 9.115 | 0.143 | 1.129 | 0.00 | 19.68 |
| 120.0 | (3) 1 5/8" Coax | Yes | 4.00 | 0.000 | 0.00 | 0.00 | 0.00 | 9.115 | 0.143 | 1.129 | 0.00 | 9.84 |
| 120.0 | (6) 1 5/8" Coax | Yes | 4.00 | 0.000 | 1.98 | 0.66 | 0.00 | 9.115 | 0.143 | 1.129 | 0.00 | 19.68 |
| 125.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 9.222 | 0.147 | 1.140 | 0.00 | 1.50 |
| 125.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 9.222 | 0.147 | 1.140 | 0.00 | 36.50 |
| 125.0 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 9.222 | 0.147 | 1.140 | 0.00 | 24.60 |
| 125.0 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 9.222 | 0.147 | 1.140 | 0.00 | 12.30 |
| 125.0 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 9.222 | 0.147 | 1.140 | 0.00 | 24.60 |
| 128.0 | (2) 1/2" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 9.284 | 0.150 | 1.151 | 0.00 | 0.90 |
| 128.0 | (2) 2" Conduit | Yes | 3.00 | 0.000 | 2.38 | 0.60 | 0.00 | 9.284 | 0.150 | 1.151 | 0.00 | 21.90 |
| 128.0 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 0.50 | 0.00 | 9.284 | 0.150 | 1.151 | 0.00 | 14.76 |
| 128.0 | (3) 1 5/8" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 9.284 | 0.150 | 1.151 | 0.00 | 7.38 |
| 128.0 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 0.50 | 0.00 | 9.284 | 0.150 | 1.151 | 0.00 | 14.76 |
| 130.0 | (2) 1/2" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 9.326 | 0.105 | 1.015 | 0.00 | 0.60 |
| 130.0 | (2) 2" Conduit | Yes | 2.00 | 0.000 | 2.38 | 0.40 | 0.00 | 9.326 | 0.105 | 1.015 | 0.00 | 14.60 |
| 130.0 | (6) 1 5/8" Coax | Yes | 2.00 | 0.000 | 1.98 | 0.33 | 0.00 | 9.326 | 0.105 | 1.015 | 0.00 | 9.84 |
| 130.0 | (3) 1 5/8" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 9.326 | 0.105 | 1.015 | 0.00 | 4.92 |
| 135.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 9.427 | 0.107 | 1.022 | 0.00 | 1.50 |
| 135.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 9.427 | 0.107 | 1.022 | 0.00 | 36.50 |
| 135.0 | (6) 1 5/8" Coax | Yes | 5.00 | 0.000 | 1.98 | 0.82 | 0.00 | 9.427 | 0.107 | 1.022 | 0.00 | 24.60 |
| 135.0 | (3) 1 5/8" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 9.427 | 0.107 | 1.022 | 0.00 | 12.30 |
| 139.3 | (2) 1/2" Coax | Yes | 4.33 | 0.000 | 0.00 | 0.00 | 0.00 | 9.512 | 0.110 | 1.031 | 0.00 | 1.30 |
| 139.3 | (2) 2" Conduit | Yes | 4.33 | 0.000 | 2.38 | 0.86 | 0.00 | 9.512 | 0.110 | 1.031 | 0.00 | 31.63 |
| 139.3 | (6) 1 5/8" Coax | Yes | 4.33 | 0.000 | 1.98 | 0.72 | 0.00 | 9.512 | 0.110 | 1.031 | 0.00 | 21.32 |
| 140.0 | (2) 1/2" Coax | Yes | 0.67 | 0.000 | 0.00 | 0.00 | 0.00 | 9.525 | 0.112 | 1.037 | 0.00 | 0.20 |
| 140.0 | (2) 2" Conduit | Yes | 0.67 | 0.000 | 2.38 | 0.13 | 0.00 | 9.525 | 0.112 | 1.037 | 0.00 | 4.87 |
| 140.0 | (6) 1 5/8" Coax | Yes | 0.67 | 0.000 | 1.98 | 0.11 | 0.00 | 9.525 | 0.112 | 1.037 | 0.00 | 3.28 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev: 0.000 (ft)



6/13/2014 11:15:49 AM
 Page: 43


© 2007 - 2014 by ATC IP LLC. All rights reserved.

| Load Case: 1.0D + 1.0W | | 60.00 mph Serviceability | | | | | | | 21 Iterations | | | |
|------------------------------------|-----------------|---------------------------------|------|-------|------|------|------|--------|--------------------------------------|-------|---------------|------------------|
| Gust Response Factor : 1.10 | | | | | | | | | Wind Importance Factor : 1.00 | | | |
| Dead Load Factor : 1.00 | | | | | | | | | | | | |
| Wind Load Factor : 1.00 | | | | | | | | | | | | |
| 144.4 | (2) 1/2" Coax | Yes | 4.42 | 0.000 | 0.00 | 0.00 | 0.00 | 9.610 | 0.114 | 1.042 | 0.00 | 1.33 |
| 144.4 | (2) 2" Conduit | Yes | 4.42 | 0.000 | 2.38 | 0.88 | 0.00 | 9.610 | 0.114 | 1.042 | 0.00 | 32.24 |
| 144.4 | (6) 1 5/8" Coax | Yes | 4.42 | 0.000 | 1.98 | 0.73 | 0.00 | 9.610 | 0.114 | 1.042 | 0.00 | 21.73 |
| 145.0 | (2) 1/2" Coax | Yes | 0.58 | 0.000 | 0.00 | 0.00 | 0.00 | 9.621 | 0.115 | 1.044 | 0.00 | 0.17 |
| 145.0 | (2) 2" Conduit | Yes | 0.58 | 0.000 | 2.38 | 0.12 | 0.00 | 9.621 | 0.115 | 1.044 | 0.00 | 4.26 |
| 145.0 | (6) 1 5/8" Coax | Yes | 0.58 | 0.000 | 1.98 | 0.10 | 0.00 | 9.621 | 0.115 | 1.044 | 0.00 | 2.87 |
| 148.0 | (2) 1/2" Coax | Yes | 3.00 | 0.000 | 0.00 | 0.00 | 0.00 | 9.678 | 0.116 | 1.048 | 0.00 | 0.90 |
| 148.0 | (2) 2" Conduit | Yes | 3.00 | 0.000 | 2.38 | 0.60 | 0.00 | 9.678 | 0.116 | 1.048 | 0.00 | 21.90 |
| 148.0 | (6) 1 5/8" Coax | Yes | 3.00 | 0.000 | 1.98 | 0.50 | 0.00 | 9.678 | 0.116 | 1.048 | 0.00 | 14.76 |
| 150.0 | (2) 1/2" Coax | Yes | 2.00 | 0.000 | 0.00 | 0.00 | 0.00 | 9.715 | 0.064 | 0.000 | 0.00 | 0.60 |
| 150.0 | (2) 2" Conduit | Yes | 2.00 | 0.000 | 2.38 | 0.40 | 0.00 | 9.715 | 0.064 | 0.000 | 0.00 | 14.60 |
| 155.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 9.806 | 0.066 | 0.000 | 0.00 | 1.50 |
| 155.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 9.806 | 0.066 | 0.000 | 0.00 | 36.50 |
| 160.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 9.896 | 0.068 | 0.000 | 0.00 | 1.50 |
| 160.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 9.896 | 0.068 | 0.000 | 0.00 | 36.50 |
| 165.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 9.983 | 0.071 | 0.000 | 0.00 | 1.50 |
| 165.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 9.983 | 0.071 | 0.000 | 0.00 | 36.50 |
| 170.0 | (2) 1/2" Coax | Yes | 5.00 | 0.000 | 0.00 | 0.00 | 0.00 | 10.069 | 0.074 | 0.000 | 0.00 | 1.50 |
| 170.0 | (2) 2" Conduit | Yes | 5.00 | 0.000 | 2.38 | 0.99 | 0.00 | 10.069 | 0.074 | 0.000 | 0.00 | 36.50 |
| 171.0 | (2) 1/2" Coax | Yes | 1.00 | 0.000 | 0.00 | 0.00 | 0.00 | 10.085 | 0.076 | 0.000 | 0.00 | 0.30 |
| 171.0 | (2) 2" Conduit | Yes | 1.00 | 0.000 | 2.38 | 0.20 | 0.00 | 10.085 | 0.076 | 0.000 | 0.00 | 7.30 |
| Totals: | | | | | | | | | | | 102.18 | 10,714.88 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)

6/13/2014 11:15:49 AM
 Page: 44



© 2007 - 2014 by ATC IP LLC. All rights reserved.

| | | |
|-------------------------------|--------------------------|-------------------------------|
| Load Case: 1.0D + 1.0W | 60.00 mph Serviceability | 21 Iterations |
| Gust Response Factor : 1.10 | | Wind Importance Factor : 1.00 |
| Dead Load Factor : 1.00 | | |
| Wind Load Factor : 1.00 | | |


Applied Segment Forces Summary

| Seg Elev (ft) | Lateral FX (-) (lb) | Axial FY (-) (lb) | Torsion MY (lb-ft) | Moment MZ (lb-ft) |
|----------------|---------------------|-------------------|--------------------|-------------------|
| 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 5.00 | 132.32 | 2,049.35 | 0.00 | 0.00 |
| 10.00 | 129.99 | 2,019.66 | 0.00 | 0.00 |
| 15.00 | 127.66 | 1,989.96 | 0.00 | 0.00 |
| 20.00 | 136.93 | 2,000.86 | 0.00 | 0.00 |
| 25.00 | 123.00 | 1,929.81 | 0.00 | 0.00 |
| 30.00 | 120.77 | 1,900.12 | 0.00 | 0.00 |
| 35.00 | 123.77 | 1,870.42 | 0.00 | 0.00 |
| 40.00 | 126.05 | 1,840.72 | 0.00 | 0.00 |
| 45.00 | 127.75 | 1,811.03 | 0.00 | 0.00 |
| 50.00 | 130.56 | 3,005.11 | 0.00 | 0.00 |
| 53.00 | 78.34 | 1,776.59 | 0.00 | 0.00 |
| 55.00 | 52.23 | 625.39 | 0.00 | 0.00 |
| 60.00 | 131.86 | 1,545.65 | 0.00 | 0.00 |
| 65.00 | 132.00 | 1,520.20 | 0.00 | 0.00 |
| 70.00 | 131.85 | 1,494.75 | 0.00 | 0.00 |
| 75.00 | 131.45 | 1,469.29 | 0.00 | 0.00 |
| 80.00 | 130.81 | 1,443.84 | 0.00 | 0.00 |
| 85.00 | 129.95 | 1,418.38 | 0.00 | 0.00 |
| 90.00 | 128.90 | 1,392.93 | 0.00 | 0.00 |
| 91.42 | 36.10 | 390.04 | 0.00 | 0.00 |
| 95.00 | 92.32 | 1,577.65 | 0.00 | 0.00 |
| 98.00 | 76.69 | 1,302.39 | 0.00 | 0.00 |
| 100.0 | 50.76 | 474.29 | 0.00 | 0.00 |
| 105.0 | 126.35 | 1,170.87 | 0.00 | 0.00 |
| 110.0 | 276.26 | 1,149.66 | 0.00 | 0.00 |
| 115.0 | 273.47 | 1,128.45 | 0.00 | 0.00 |
| 116.0 | 726.79 | 2,608.44 | 0.00 | 555.68 |
| 120.0 | 96.42 | 868.09 | 0.00 | 0.00 |
| 125.0 | 118.78 | 1,066.02 | 0.00 | 0.00 |
| 128.0 | 196.78 | 708.63 | 0.00 | 0.00 |
| 130.0 | 46.20 | 405.54 | 0.00 | 0.00 |
| 135.0 | 916.72 | 3,025.70 | 0.00 | 1,732.37 |
| 139.3 | 96.99 | 779.06 | 0.00 | 0.00 |
| 140.0 | 14.89 | 187.76 | 0.00 | 0.00 |
| 144.4 | 97.90 | 1,226.79 | 0.00 | 0.00 |
| 145.0 | 12.73 | 87.58 | 0.00 | 0.00 |
| 148.0 | 542.51 | 1,723.28 | 0.00 | 0.00 |
| 150.0 | 42.81 | 272.78 | 0.00 | 0.00 |
| 155.0 | 105.42 | 670.07 | 0.00 | 0.00 |
| 160.0 | 1,689.90 | 4,596.50 | 0.00 | 0.00 |
| 165.0 | 99.73 | 530.98 | 0.00 | 0.00 |
| 170.0 | 96.75 | 514.01 | 0.00 | 0.00 |
| 171.0 | 306.60 | 926.87 | 0.00 | 0.00 |
| 175.0 | 74.65 | 364.79 | 0.00 | 0.00 |
| 178.5 | 851.64 | 2,215.29 | 0.00 | 1,237.15 |
| Totals: | 15,086.00 | 195,534.2 | 0.00 | 3,525.19 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)

6/13/2014 11:15:49 AM
 Page: 46



© 2007 - 2014 by ATC IP LLC. All rights reserved.


Analysis Summary

| Load Case | Reactions | | | | | | Max Usage | |
|----------------------|-----------------------|-----------------------|-----------------------|---------------------------|---------------------------|---------------------------|--------------|----------------------|
| | Shear FX (kips) | Shear FZ (kips) | Axial FY (kips) | Moment MX (ft-kips) | Moment MY (ft-kips) | Moment MZ (ft-kips) | Elev (ft) | Interaction Ratio |
| 1.2D + 1.6W | 53.48 | 0.00 | 75.62 | 0.00 | 0.00 | 6514.47 | 0.00 | 0.73 |
| 0.9D + 1.6W | 50.58 | 0.00 | 56.71 | 0.00 | 0.00 | 6251.94 | 53.00 | 0.70 |
| 1.2D + 1.0Di + 1.0Wi | 10.66 | 0.00 | 121.57 | 0.00 | 0.00 | 1306.37 | 0.00 | 0.16 |
| 1.2D + 1.0E | 3.42 | 0.00 | 75.69 | 0.00 | 0.00 | 440.34 | 98.00 | 0.06 |
| 0.9D + 1.0E | 3.41 | 0.00 | 56.77 | 0.00 | 0.00 | 436.30 | 98.00 | 0.06 |
| 1.0D + 1.0W | 9.41 | 0.00 | 63.07 | 0.00 | 0.00 | 1166.70 | 0.00 | 0.14 |

Pole : 302467
 Location : Bilkays Express, CT
 Height : 178.5 (ft)
 Base Dia : 72.00 (in)
 Top Dia : 29.00 (in)
 Shape : 18 Sides
 Taper : 0.251401 (in/ft)

Code: ANSI/TIA-222 Rev G
 Struct Class : II
 Exposure Category : B
 Topographic Category : 1
 Base Elev : 0.000 (ft)

6/13/2014 11:15:49 AM
 Page: 47



© 2007 - 2014 by ATC IP LLC. All rights reserved.

Base Summary

Reactions

| Original Design | | | Analysis | | | Moment Design % |
|-----------------|-------------|-------------|-----------------|-------------|-------------|-----------------|
| Moment (kip-ft) | Axial (kip) | Shear (kip) | Moment (kip-ft) | Axial (kip) | Shear (kip) | |
| 5,025.00 | 56.80 | 39.90 | 6,514.47 | 121.57 | 53.48 | 96.03 |

Base Plate

| Yield (ksi) | Thick (in) | Width (in) | Style | Poly Sides | Clip Len (in) | Effective Len (in) | Mu (kip-in) | Phi Mn (kip-in) | Ratio |
|-------------|------------|------------|-------|------------|---------------|--------------------|-------------|-----------------|-------|
| 60.0 | 2.750 | 85.000 | Round | 0 | 0.00 | 11.426 | 713.95 | 1166.52 | 0.61 |

Anchor Bolts

| Bolt Circle | Num Bolts | Bolt Type | Bolt Dia (in) | Yield (ksi) | Ultimate (ksi) | Arrange | Cluster Dist (in) | Start Angle (deg) | Compression | | | Tension | | |
|-------------|-----------|-----------|---------------|-------------|----------------|---------|-------------------|-------------------|-------------|-------------|-------|-------------|-------------|-------|
| | | | | | | | | | Force (kip) | Allow (kip) | Ratio | Force (kip) | Allow (kip) | Ratio |
| 79.00 | 20 | 2.25" 18J | 2.25 | 75.00 | 100.00 | Radial | 0.00 | 0.0 | 203.99 | 260.00 | 0.81 | 191.83 | 260.00 | 0.76 |

Sprint




AMERICAN TOWER CORPORATION

PROJECT: 2.5 EQUIPMENT DEPLOYMENT
 SITE NAME: BILKAYS EXPRESS
 SITE CASCADE: CT43XC839
 SITE NUMBER: 302467
 SITE ADDRESS: 90 N. PLAINS INDUSTRIAL RD.
 WALLINGFORD, CT 06492
 SITE TYPE: MONOPOLE TOWER
 MARKET: SOUTHERN CONNECTICUT

PLANS PREPARED FOR:
Sprint
 6580 Sprint Parkway
 Overland Park, Kansas 66251

PLANS PREPARED BY:
INFINIGY Design. Build. Deliver.
 1033 Watervliet Shaker Rd
 Albany, NY 12205
 Office # (518) 690-0790
 Fax # (518) 690-0793
 JOB NUMBER 340-000

MLA PARTNER:
AMERICAN TOWER CORPORATION
 10 PRESIDENTIAL WAY
 WOBURN, MA 01801



DRAWING NOTICE:
 THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF SPRINT AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPRINT.

| REVISIONS: | DESCRIPTION | DATE | BY | REV |
|------------|-------------------------|----------|-----|-----|
| | ISSUED FOR CONSTRUCTION | 07/15/14 | DJG | 2 |
| | REVISED PER COMMENTS | 07/10/14 | JLM | 1 |
| | ISSUED FOR PERMIT | 08/10/14 | DJG | 0 |
| | ISSUED FOR REVIEW | 05/27/14 | JLM | A |

SITE NAME:
BILKAYS EXPRESS

SITE CASCADE:
CT43XC839

SITE ADDRESS:
 90 N. PLAINS INDUSTRIAL RD.
 WALLINGFORD, CT 06492

SHEET DESCRIPTION:
TITLE SHEET & PROJECT DATA

SHEET NUMBER:
T-1

SITE INFORMATION

TOWER OWNER:
 AMERICAN TOWER CORPORATION
 10 PRESIDENTIAL WAY
 WOBURN, MA 01801

LATITUDE (NAD83):
 41° 28' 50.72" N
 41.480756°

LONGITUDE (NAD83):
 72° 49' 03.79" W
 -72.817719°

COUNTY:
 NEW HAVEN

ZONING JURISDICTION:
 CONNECTICUT SITING COUNCIL


ZONING DISTRICT:
 I-40

POWER COMPANY:
 CL&P
 (800) 286-2000

AAV PROVIDER:
 AT&T
 (800) 246-2020

SPRINT CM:
 GARY WOOD
 (860) 940-9168
 GARY.WOOD@SPRINT.COM

AREA MAP



LOCATION MAP



PROJECT DESCRIPTION

SPRINT PROPOSES TO MODIFY AN EXISTING UNMANNED TELECOMMUNICATIONS FACILITY.

- INSTALL 2.5 EQUIPMENT IN EXISTING NV MMBS CABINET
- INSTALL (3) PANEL ANTENNAS
- INSTALL (3) RRU'S TO TOWER
- INSTALL (27) JUMPER CABLES
- INSTALL (1) FIBER CABLE
- INSTALL (4) BATTERIES IN EXISTING BATTERY CABINET

THESE PLANS HAVE BEEN DEVELOPED FOR THE MODIFICATION OF AN EXISTING UNMANNED TELECOMMUNICATIONS FACILITY OWNED OR LEASED BY SPRINT IN ACCORDANCE WITH THE SCOPE OF WORK PROVIDED BY SPRINT. INFINIGY HAS INCORPORATED THIS SCOPE OF WORK IN THE PLANS. THESE PLANS ARE NOT FOR CONSTRUCTION UNLESS ACCOMPANIED BY A PASSING STRUCTURAL STABILITY ANALYSIS PREPARED BY A LICENSED STRUCTURAL ENGINEER. STRUCTURAL ANALYSIS MUST INCLUDE BOTH TOWER AND MOUNT.

APPLICABLE CODES

- ALL WORK SHALL BE PERFORMED AND MATERIALS INSTALL IN ACCORDANCE WITH THE CURRENT EDITIONS OF THE FOLLOWING CODES AS ADOPTED BY THE LOCAL GOVERNING AUTHORITIES. NOTHING IN THESE PLANS IS TO BE CONSTRUED TO PERMIT WORK NOT CONFORMING TO THESE CODES.
- INTERNATIONAL BUILDING CODE (2012 IBC)
 - TIA-EIA-222-G OR LATEST EDITION
 - NFPA 780 - LIGHTNING PROTECTION CODE
 - 2011 NATIONAL ELECTRIC CODE OR LATEST EDITION
 - ANY OTHER NATIONAL OR LOCAL APPLICABLE CODES, MOST RECENT EDITIONS
 - CT BUILDING CODE
 - LOCAL BUILDING CODE
 - CITY/COUNTY ORDINANCES

DRAWING INDEX

| SHEET NO. | SHEET TITLE | REV. |
|-----------|-----------------------------------|------|
| T-1 | TITLE SHEET & PROJECT DATA | 2 |
| SP-1 | SPRINT SPECIFICATIONS | 2 |
| SP-2 | SPRINT SPECIFICATIONS | 2 |
| SP-3 | SPRINT SPECIFICATIONS | 2 |
| A-1 | SITE PLAN | 2 |
| A-1A | EXISTING EQUIPMENT DETAILS | 2 |
| A-2 | TOWER ELEVATION & CABLE PLAN | 2 |
| A-3 | ANTENNA LAYOUT & MOUNTING DETAILS | 2 |
| A-4 | COLOR CODING & NOTES | 2 |
| A-5 | EQUIPMENT & MOUNTING DETAILS | 2 |
| A-6 | CIVIL DETAILS | 2 |
| A-7 | PLUMBING DIAGRAM | 2 |
| E-1 | ELECTRICAL & GROUNDING PLAN | 2 |
| E-2 | ELECTRICAL & GROUNDING DETAILS | 2 |



THESE OUTLINE SPECIFICATIONS IN CONJUNCTION WITH THE SPRINT STANDARD CONSTRUCTION SPECIFICATIONS, INCLUDING CONTRACT DOCUMENTS AND THE CONSTRUCTION DRAWINGS DESCRIBE THE WORK TO BE PERFORMED BY THE CONTRACTOR.

SECTION 01 100 - SCOPE OF WORK

PART 1 - GENERAL

- 1.1 THE WORK: THESE STANDARD CONSTRUCTION SPECIFICATIONS IN CONJUNCTION WITH THE SPRINT CONSTRUCTION STANDARDS FOR WIRELESS SITES, CONTRACT DOCUMENTS AND THE CONSTRUCTION DRAWINGS DESCRIBE THE WORK TO BE PERFORMED BY THE CONTRACTOR.
- 1.2 RELATED DOCUMENTS:
 - A. THE REQUIREMENTS OF THIS SECTION APPLY TO ALL SECTIONS IN THIS SPECIFICATION.
 - B. SPRINT "STANDARD CONSTRUCTION DETAILS FOR WIRELESS SITES" ARE INCLUDED IN AND MADE A PART OF THESE SPECIFICATIONS HERewith.
- 1.3 PRECEDENCE: SHOULD CONFLICTS OCCUR BETWEEN THE STANDARD CONSTRUCTION SPECIFICATIONS FOR WIRELESS SITES INCLUDING THE STANDARD CONSTRUCTION DETAILS FOR WIRELESS SITES AND THE CONSTRUCTION DRAWINGS, INFORMATION ON THE CONSTRUCTION DRAWINGS SHALL TAKE PRECEDENCE. NOTIFY SPRINT CONSTRUCTION MANAGER IF THIS OCCURS.
- 1.4 NATIONALLY RECOGNIZED CODES AND STANDARDS:
 - A. THE WORK SHALL COMPLY WITH APPLICABLE NATIONAL AND LOCAL CODES AND STANDARDS, LATEST EDITION, AND PORTIONS THEREOF, INCLUDED BUT NOT LIMITED TO THE FOLLOWING:
 - 1. GR-83-CORE NEBS REQUIREMENTS: PHYSICAL PROTECTION
 - 5. GR-78-CORE GENERIC REQUIREMENTS FOR THE PHYSICAL DESIGN AND MANUFACTURE OF TELECOMMUNICATIONS EQUIPMENT.
 - 3. GR-1089 CORE, ELECTROMAGNETIC COMPATIBILITY AND ELECTRICAL SAFETY -GENERIC CRITERIA FOR NETWORK TELECOMMUNICATIONS EQUIPMENT.
 - 4. NATIONAL FIRE PROTECTION ASSOCIATION CODES AND STANDARDS (NFPA) INCLUDING NFPA 70 (NATIONAL ELECTRICAL CODE - "NEC") AND NFPA 101 (LIFE SAFETY CODE).
 - 5. AMERICAN SOCIETY FOR TESTING OF MATERIALS (ASTM)
 - 6. INSTITUTE OF ELECTRONIC AND ELECTRICAL ENGINEERS (IEEE)
 - 7. AMERICAN CONCRETE INSTITUTE (ACI)
 - 8. AMERICAN WIRE PRODUCERS ASSOCIATION (AWPA)
 - 9. CONCRETE REINFORCING STEEL INSTITUTE (CRSI)
 - 10. AMERICAN ASSOCIATION OF STATE HIGHWAY AND TRANSPORTATION OFFICIALS (AASHTO)
 - 11. PORTLAND CEMENT ASSOCIATION (PCA)
 - 12. NATIONAL CONCRETE MASONRY ASSOCIATION (NCMA)
 - 13. BRICK INDUSTRY ASSOCIATION (BIA)
 - 14. AMERICAN WELDING SOCIETY (AWS)
 - 15. NATIONAL ROOFING CONTRACTORS ASSOCIATION (NRCA)
 - 16. SHEET METAL AND AIR CONDITIONING CONTRACTORS' NATIONAL ASSOCIATION (SMACNA)
 - 17. DOOR AND HARDWARE INSTITUTE (DHI)
 - 18. OCCUPATIONAL SAFETY AND HEALTH ACT (OSHA)
 - 19. APPLICABLE BUILDING CODES INCLUDING UNIFORM BUILDING CODE, SOUTHERN BUILDING CODE, BOCA, AND THE INTERNATIONAL BUILDING CODE.

1.5 DEFINITIONS:

- A. WORK: THE SUM OF TASKS AND RESPONSIBILITIES IDENTIFIED IN THE CONTRACT DOCUMENTS.
- B. COMPANY: SPRINT CORPORATION
- C. ENGINEER: SYNONYMOUS WITH ARCHITECT & ENGINEER AND "A&E". THE DESIGN PROFESSIONAL HAVING PROFESSIONAL RESPONSIBILITY FOR DESIGN OF THE PROJECT.
- D. CONTRACTOR: CONSTRUCTION CONTRACTOR; CONSTRUCTION VENDOR; INDIVIDUAL OR ENTITY WHO AFTER EXECUTION OF A CONTRACT IS BOUND TO ACCOMPLISH THE WORK.
- E. THIRD PARTY VENDOR OR AGENCY: A VENDOR OR AGENCY ENGAGED SEPARATELY BY THE COMPANY, A&E, OR CONTRACTOR TO PROVIDE MATERIALS OR TO ACCOMPLISH SPECIFIC TASKS RELATED TO BUT NOT INCLUDED IN THE WORK.
- F. OFC: OWNER FURNISHED, CONTRACTOR INSTALLED EQUIPMENT.
- G. CONSTRUCTION MANAGER - ALL PROJECTS RELATED COMMUNICATION TO FLOW THROUGH SPRINT REPRESENTATIVE IN CHARGE OF PROJECT...

- 1.6 SITE FAMILIARITY: CONTRACTOR SHALL BE RESPONSIBLE FOR FAMILIARIZING HIMSELF WITH ALL CONTRACT DOCUMENTS, FIELD CONDITIONS AND DIMENSIONS PRIOR TO PROCEEDING WITH CONSTRUCTION. ANY DISCREPANCIES SHALL BE BROUGHT TO THE ATTENTION OF THE SPRINT CONSTRUCTION MANAGER PRIOR TO THE COMMENCEMENT OF WORK. NO COMPENSATION WILL BE AWARDED BASED ON CLAIM OF LACK OF KNOWLEDGE OR FIELD CONDITIONS.
- 1.7 POINT OF CONTACT: COMMUNICATION BETWEEN SPRINT AND THE CONTRACTOR SHALL FLOW THROUGH THE SINGLE SPRINT CONSTRUCTION MANAGER APPOINTED TO MANAGE THE PROJECT FOR SPRINT.
- 1.8 ON-SITE SUPERVISION: THE CONTRACTOR SHALL SUPERVISE AND DIRECT THE WORK AND SHALL BE RESPONSIBLE FOR CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES, AND PROCEDURES IN ACCORDANCE WITH THE CONTRACT DOCUMENTS. THE CONTRACTOR SHALL EMPLOY A COMPETENT SUPERINTENDENT WHO SHALL BE IN ATTENDANCE AT THE SITE AT ALL TIMES DURING PERFORMANCE OF THE WORK.
- 1.9 DRAWINGS, SPECIFICATIONS AND DETAILS REQUIRED AT JOBSITE: THE CONSTRUCTION CONTRACTOR SHALL MAINTAIN A FULL SET OF THE CONSTRUCTION DRAWINGS, STANDARD CONSTRUCTION DETAILS FOR WIRELESS SITES AND THE STANDARD CONSTRUCTION SPECIFICATIONS FOR WIRELESS SITES AT THE JOBSITE FROM MOBILIZATION THROUGH CONSTRUCTION COMPLETION.

- A. THE JOBSITE DRAWINGS, SPECIFICATIONS AND DETAILS SHALL BE CLEARLY MARKED DAILY IN RED PENCIL WITH ANY CHANGES IN CONSTRUCTION OVER WHAT IS DEPICTED IN THE DOCUMENTS. AT CONSTRUCTION COMPLETION, THIS JOBSITE MARKUP SET SHALL BE DELIVERED TO THE COMPANY OR COMPANY'S DESIGNATED REPRESENTATIVE TO BE FORWARDED TO THE COMPANY'S A&E VENDOR FOR PRODUCTION OF "AS-BUILT" DRAWINGS.
- B. DETAILS ARE INTENDED TO SHOW DESIGN INTENT. MODIFICATIONS MAY BE REQUIRED TO SUIT JOB DIMENSIONS OR CONDITIONS, AND SUCH MODIFICATIONS SHALL BE INCLUDED AS PART OF THE WORK. CONTRACTOR SHALL NOTIFY SPRINT CONSTRUCTION MANAGER OF ANY VARIATIONS PRIOR TO PROCEEDING WITH THE WORK.
- C. DIMENSIONS SHOWN ARE TO FINISH SURFACES UNLESS NOTED OTHERWISE. SPACING BETWEEN EQUIPMENT IS THE REQUIRED CLEARANCE. SHOULD THERE BE ANY QUESTIONS REGARDING THE CONTRACT DOCUMENTS, EXISTING CONDITIONS AND/OR DESIGN INTENT, THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING A CLARIFICATION FROM THE SPRINT CONSTRUCTION MANAGER PRIOR TO PROCEEDING WITH THE WORK.

- 1.10 USE OF JOB SITE: THE CONTRACTOR SHALL CONFINE ALL CONSTRUCTION AND RELATED OPERATIONS INCLUDING STAGING AND STORAGE OF MATERIALS AND EQUIPMENT, PARKING, TEMPORARY FACILITIES, AND WASTE STORAGE TO THE LEASE PARCEL UNLESS OTHERWISE PERMITTED BY THE CONTRACT DOCUMENTS.
 - 1.11 UTILITIES SERVICES: WHERE NECESSARY TO CUT EXISTING PIPES, ELECTRICAL WIRES, CONDUITS, CABLES, ETC., OF UTILITY SERVICES, OR OF FIRE PROTECTION OR COMMUNICATIONS SYSTEMS, THEY SHALL BE CUT AND CAPPED AT SUITABLE PLACES OR WHERE SHOWN. ALL SUCH ACTIONS SHALL BE COORDINATED WITH THE UTILITY COMPANY INVOLVED.
 - 1.12 PERMITS / FEES: WHEN REQUIRED THAT A PERMIT OR CONNECTION FEE BE PAID TO A PUBLIC UTILITY PROVIDER FOR NEW SERVICE TO THE CONSTRUCTION PROJECT, PAYMENT OF SUCH FEE SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR.
 - 1.13 CONTRACTOR SHALL TAKE ALL MEASURES AND PROVIDE ALL MATERIAL NECESSARY FOR PROTECTING EXISTING EQUIPMENT AND PROPERTY.
 - 1.14 METHODS OF PROCEDURE (MOPS) FOR CONSTRUCTION: CONTRACTOR SHALL PERFORM WORK AS DESCRIBED IN THE FOLLOWING INSTALLATION AND COMMISSIONING MOPS.
- NOTE: IN SHORT-FORM SPECIFICATIONS ON THE DRAWINGS, A/E TO INSERT LIST OF APPLICABLE MOPS INCLUDING EN-2012-001, EN-2013-002, EL-0568, AND TS-0193
- 1.15 USE OF ELECTRONIC PROJECT MANAGEMENT SYSTEMS:

PART 2 - PRODUCTS (NOT USED)

PART 3 - EXECUTION

- 3.1 TEMPORARY UTILITIES AND FACILITIES: THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL TEMPORARY UTILITIES AND FACILITIES NECESSARY EXCEPT AS OTHERWISE INDICATED IN THE CONSTRUCTION DOCUMENTS. TEMPORARY UTILITIES AND FACILITIES INCLUDE POTABLE WATER, HEAT, HVAC, ELECTRICITY, SANITARY FACILITIES, WASTE DISPOSAL FACILITIES, AND TELEPHONE/COMMUNICATION SERVICES. PROVIDE TEMPORARY UTILITIES AND FACILITIES IN ACCORDANCE WITH OSHA AND THE AUTHORITY HAVING JURISDICTION. CONTRACTOR MAY UTILIZE THE COMPANY ELECTRICAL SERVICE IN THE COMPLETION OF THE WORK WHEN IT BECOMES AVAILABLE. USE OF THE LESSORS OR SITE OWNER'S UTILITIES OR FACILITIES IS EXPRESSLY FORBIDDEN EXCEPT AS OTHERWISE ALLOWED IN THE CONTRACT DOCUMENTS.
- 3.2 ACCESS TO WORK: THE CONTRACTOR SHALL PROVIDE ACCESS TO THE JOB SITE FOR AUTHORIZED COMPANY PERSONNEL AND AUTHORIZED REPRESENTATIVES OF THE ARCHITECT/ENGINEER DURING ALL PHASES OF THE WORK.
- 3.3 TESTING: REQUIREMENTS FOR TESTING BY THIS CONTRACTOR SHALL BE AS INDICATED HERewith, ON THE CONSTRUCTION DRAWINGS, AND IN THE INDIVIDUAL SECTIONS OF THESE SPECIFICATIONS. SHOULD COMPANY CHOOSE TO ENGAGE ANY THIRD-PARTY TO CONDUCT ADDITIONAL TESTING, THE CONTRACTOR SHALL COOPERATE WITH AND PROVIDE A WORK AREA FOR COMPANY'S TEST AGENCY.
- 3.4 DIMENSIONS: VERIFY DIMENSIONS INDICATED ON DRAWINGS WITH FIELD DIMENSIONS BEFORE FABRICATION OR ORDERING OF MATERIALS. DO NOT SCALE DRAWINGS.

- 3.5 EXISTING CONDITIONS: NOTIFY THE SPRINT CONSTRUCTION MANAGER OF EXISTING CONDITIONS DIFFERING FROM THOSE INDICATED ON THE DRAWINGS. DO NOT REMOVE OR ALTER STRUCTURAL COMPONENTS WITHOUT PRIOR WRITTEN APPROVAL FROM THE ARCHITECT AND ENGINEER.

SECTION 01 200 - COMPANY FURNISHED MATERIAL AND EQUIPMENT

PART 1 - GENERAL

- 1.1 THE WORK: THESE STANDARD CONSTRUCTION SPECIFICATIONS IN CONJUNCTION WITH THE OTHER CONTRACT DOCUMENTS AND THE CONSTRUCTION DRAWINGS DESCRIBE THE WORK TO BE PERFORMED BY THE CONTRACTOR.
- 1.2 RELATED DOCUMENTS:
 - A. THE REQUIREMENTS OF THIS SECTION APPLY TO ALL SECTIONS IN THIS SPECIFICATION.
 - B. SPRINT "STANDARD CONSTRUCTION DETAILS FOR WIRELESS SITES" ARE INCLUDED IN AND MADE A PART OF THESE SPECIFICATIONS HERewith.

PART 2 - PRODUCTS (NOT USED)

PART 3 - EXECUTION

- 3.1 RECEIPT OF MATERIAL AND EQUIPMENT:
 - A. A COMPANY FURNISHED MATERIAL AND EQUIPMENT IS IDENTIFIED ON THE RF DATA SHEET IN THE CONSTRUCTION DOCUMENTS.
 - B. THE CONTRACTOR IS RESPONSIBLE FOR SPRINT PROVIDED MATERIAL AND EQUIPMENT AND UPON RECEIPT SHALL:
 - 1. ACCEPT DELIVERIES AS SHIPPED AND TAKE RECEIPT.
 - 2. VERIFY COMPLETENESS AND CONDITION OF ALL DELIVERIES.
 - 3. TAKE RESPONSIBILITY FOR EQUIPMENT AND PROVIDE INSURANCE PROTECTION AS REQUIRED IN AGREEMENT.
 - 4. RECORD ANY DEFECTS OR DAMAGES AND WITHIN TWENTY-FOUR HOURS AFTER RECEIPT, REPORT TO SPRINT OR ITS DESIGNATED PROJECT REPRESENTATIVE OF SUCH.
 - 5. PROVIDE SECURE AND NECESSARY WEATHER PROTECTED WAREHOUSING.
 - 6. COORDINATE SAFE AND SECURE TRANSPORTATION OF MATERIAL AND EQUIPMENT, DELIVERING AND OFF-LOADING FROM CONTRACTOR'S WAREHOUSE TO SITE.
- 3.2 DELIVERABLES:
 - A. COMPLETE SHIPPING AND RECEIPT DOCUMENTATION IN ACCORDANCE WITH COMPANY PRACTICE.
 - B. IF APPLICABLE, COMPLETE LOST/STOLEN/DAMAGED DOCUMENTATION REPORT AS NECESSARY IN ACCORDANCE WITH COMPANY PRACTICE, AND AS DIRECTED BY COMPANY.
 - C. UPLOAD DOCUMENTATION INTO SPRINT SITE MANAGEMENT SYSTEM (SMS) AND/OR PROVIDE HARD COPY DOCUMENTATION AS REQUESTED.

SECTION 01 300 - CELL SITE CONSTRUCTION CO.

PART 1 - GENERAL

- 1.1 THE WORK: THESE STANDARD CONSTRUCTION SPECIFICATIONS IN CONJUNCTION WITH THE OTHER CONTRACT DOCUMENTS AND THE CONSTRUCTION DRAWINGS DESCRIBE THE WORK TO BE PERFORMED BY THE CONTRACTOR.
- 1.2 RELATED DOCUMENTS:
 - A. THE REQUIREMENTS OF THIS SECTION APPLY TO ALL SECTIONS IN THIS SPECIFICATION.
 - B. SPRINT "STANDARD CONSTRUCTION DETAILS FOR WIRELESS SITES" ARE INCLUDED IN AND MADE A PART OF THESE SPECIFICATIONS HERewith.
- 1.3 NOTICE TO PROCEED
 - A. NO WORK SHALL COMMENCE PRIOR TO COMPANY'S WRITTEN NOTICE TO PROCEED AND THE ISSUANCE OF THE WORK ORDER.
 - B. UPON RECEIVING NOTICE TO PROCEED, CONTRACTOR SHALL FULLY PERFORM ALL WORK NECESSARY TO PROVIDE SPRINT WITH AN OPERATIONAL WIRELESS FACILITY.

PART 2 - PRODUCTS (NOT USED)

PART 3 - EXECUTION


- 3.1 FUNCTIONAL REQUIREMENTS:
 - A. THE ACTIVITIES DESCRIBED IN THIS PARAGRAPH REPRESENT MINIMUM ACTIONS AND PROCESSES REQUIRED TO SUCCESSFULLY COMPLETE THE WORK. THE ACTIVITIES DESCRIBED ARE NOT EXHAUSTIVE, AND CONTRACTOR SHALL TAKE ANY AND ALL ACTIONS AS NECESSARY TO SUCCESSFULLY COMPLETE THE CONSTRUCTION OF A FULLY FUNCTIONING WIRELESS FACILITY AT THE SITE IN ACCORDANCE WITH COMPANY PROCESSES.
 - B. SUBMIT SPECIFIC DOCUMENTATION AS INDICATED HEREIN, AND OBTAIN REQUIRED APPROVALS WHILE THE WORK IS BEING PERFORMED.
 - C. MANAGE AND CONDUCT ALL FIELD CONSTRUCTION SERVICE RELATED ACTIVITIES
 - D. PROVIDE CONSTRUCTION ACTIVITIES TO THE EXTENT REQUIRED BY THE CONTRACT DOCUMENTS, INCLUDING BUT NOT LIMITED TO THE FOLLOWING:

PLANS PREPARED FOR:



6580 Sprint Parkway
Overland Park, Kansas 66251

PLANS PREPARED BY:



1033 Watervliet Shaker Rd
Albany, NY 12205
Office # (518) 690-0790
Fax # (518) 690-0793
JOB NUMBER 340-000

MLA PARTNER:



10 PRESIDENTIAL WAY
WOBURN, MA 01801

ENGINEERING LICENSE:



DRAWING NOTICE:
THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF SPRINT AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPRINT.

REVISIONS:

| DESCRIPTION | DATE | BY | REV |
|-------------------------|----------|-----|-----|
| ISSUED FOR CONSTRUCTION | 07/15/14 | DJG | 2 |
| REVISED PER COMMENTS | 07/10/14 | JJM | 1 |
| ISSUED FOR PERMIT | 06/10/14 | DJG | 0 |
| ISSUED FOR REVIEW | 05/27/14 | JJM | A |

SITE NAME:
BILKAYS EXPRESS

SITE CASCADE:
CT43XC839

SITE ADDRESS:
90 N. PLAINS INDUSTRIAL RD.
WALLINGFORD, CT 06492

SHEET DESCRIPTION:
SPRINT SPECIFICATIONS

SHEET NUMBER:
SP-1

CONTINUE FROM SP-1

1. PERFORM ANY REQUIRED SITE ENVIRONMENTAL MITIGATION.
2. PREPARE GROUND SITES; PROVIDE DE-GRUBBING; AND ROUGH AND FINAL GRADING, AND COMPOUND SURFACE TREATMENTS.
3. MANAGE AND CONDUCT ALL ACTIVITIES FOR INSTALLATION OF UTILITIES INCLUDING ELECTRICAL AND TELCO BACKHAUL.
4. INSTALL UNDERGROUND FACILITIES INCLUDING UNDERGROUND POWER AND COMMUNICATIONS CONDUITS, AND UNDERGROUND GROUNDING SYSTEM.
5. INSTALL ABOVE GROUND GROUNDING SYSTEMS.
6. PROVIDE NEW HVAC INSTALLATIONS AND MODIFICATIONS.
7. INSTALL "H-FRAMES", CABINETS AND SHELTERS AS INDICATED.
8. INSTALL ROADS, ACCESS WAYS, CURBS AND DRAINS AS INDICATED.
9. ACCOMPLISH REQUIRED MODIFICATION OF EXISTING FACILITIES.
10. PROVIDE ANTENNA SUPPORT STRUCTURE FOUNDATIONS.
11. PROVIDE SLABS AND EQUIPMENT PLATFORMS.
12. INSTALL COMPOUND FENCING, SIGHT SHIELDING, LANDSCAPING AND ACCESS BARRIERS.
13. PERFORM INSPECTION AND MATERIAL TESTING AS REQUIRED HEREINAFTER.
14. CONDUCT SITE RESISTANCE TO EARTH TESTING AS REQUIRED HEREINAFTER.
15. INSTALL FIXED GENERATOR SETS AND OTHER STANDBY POWER SOLUTIONS.
16. INSTALL TOWERS, ANTENNA SUPPORT STRUCTURES AND PLATFORMS ON EXISTING TOWERS AS REQUIRED.
17. INSTALL CELL SITE RADIOS, MICROWAVE, GPS, COAXIAL MAINLINE, ANTENNAS, CROSS BAND COUPLERS, TOWER TOP AMPLIFIERS, LOW NOISE AMPLIFIERS AND RELATED EQUIPMENT.
18. PERFORM, DOCUMENT, AND CLOSE OUT ANY CONSTRUCTION CONTROL DOCUMENTS THAT MAY BE REQUIRED BY GOVERNMENT AGENCIES AND LANDLORDS.
19. PERFORM ANTENNA AND COAX SWEEP TESTING AND MAKE ANY AND ALL NECESSARY CORRECTIONS.
20. REMAIN ON SITE MOBILIZED THROUGHOUT HAND-OFF AND INTEGRATION TO ASSIST AS NEEDED UNTIL SITE IS DEEMED SUBSTANTIALLY COMPLETE AND PLACED "ON AIR."

3.2 GENERAL REQUIREMENTS FOR CIVIL CONSTRUCTION:

- A. CONTRACTOR SHALL KEEP THE SITE FREE FROM ACCUMULATING WASTE MATERIAL, DEBRIS, AND TRASH. AT THE COMPLETION OF THE WORK, CONTRACTOR SHALL REMOVE FROM THE SITE ALL REMAINING RUBBISH, IMPLEMENTS, TEMPORARY FACILITIES, AND SURPLUS MATERIALS.
- B. EQUIPMENT ROOMS SHALL AT ALL TIMES BE MAINTAINED "BROOM CLEAN" AND CLEAR OF DEBRIS.
- C. CONTRACTOR SHALL TAKE ALL REASONABLE PRECAUTIONS TO DISCOVER AND LOCATE ANY HAZARDOUS CONDITION.
 1. IN THE EVENT CONTRACTOR ENCOUNTERS ANY HAZARDOUS CONDITION WHICH HAS NOT BEEN ABATED OR OTHERWISE MITIGATED, CONTRACTOR AND ALL OTHER PERSONS SHALL IMMEDIATELY STOP WORK IN THE AFFECTED AREA AND NOTIFY COMPANY IN WRITING. THE WORK IN THE AFFECTED AREA SHALL NOT BE RESUMED EXCEPT BY WRITTEN NOTIFICATION BY COMPANY.
 2. CONTRACTOR AGREES TO USE CARE WHILE ON THE SITE AND SHALL NOT TAKE ANY ACTION THAT WILL OR MAY RESULT IN OR CAUSE THE HAZARDOUS CONDITION TO BE FURTHER RELEASED IN THE ENVIRONMENT, OR TO FURTHER EXPOSE INDIVIDUALS TO THE HAZARD.
- D. CONTRACTOR'S ACTIVITIES SHALL BE RESTRICTED TO THE PROJECT LIMITS. SHOULD AREAS OUTSIDE THE PROJECT LIMITS BE AFFECTED BY CONTRACTOR'S ACTIVITIES, CONTRACTOR SHALL IMMEDIATELY RETURN THEM TO ORIGINAL CONDITION
- E. CONDUCT TESTING AS REQUIRED HEREIN.

3.3 DELIVERABLES:

- A. CONTRACTOR SHALL REVIEW, APPROVE, AND SUBMIT TO SPRINT SHOP DRAWINGS, PRODUCT DATA, SAMPLES, AND SIMILAR SUBMITTALS AS REQUIRED HEREINAFTER
- B. PROVIDE DOCUMENTATION INCLUDING, BUT NOT LIMITED TO, THE FOLLOWING. DOCUMENTATION SHALL BE FORWARDED IN ORIGINAL FORMAT AND/OR UPLOADED INTO SMS.
 1. ALL CORRESPONDENCE AND PRELIMINARY CONSTRUCTION REPORTS.
 2. PROJECT PROGRESS REPORTS.
 3. CIVIL CONSTRUCTION START DATE (POPULATE FIELD IN SMS AND/OR FORWARD NOTIFICATION).
 4. ELECTRICAL SERVICE COMPLETION DATE (POPULATE FIELD IN SMS AND/OR FORWARD NOTIFICATION).

5. LINES AND ANTENNA INSTALL DATE (POPULATE FIELD IN SMS AND/OR FORWARD NOTIFICATION).
6. POWER INSTALL DATE (POPULATE FIELD IN SMS AND/OR FORWARD NOTIFICATION).
7. TELCO READY DATE (POPULATE FIELD IN SMS AND/OR FORWARD NOTIFICATION).
8. PPC (OR SHELTER) INSTALL DATE (POPULATE FIELD IN SMS AND/OR FORWARD NOTIFICATION).
9. TOWER CONSTRUCTION START DATE (POPULATE FIELD IN SMS AND/OR FORWARD NOTIFICATION).
10. TOWER CONSTRUCTION COMPLETE DATE (POPULATE FIELD IN SMS AND/OR FORWARD NOTIFICATION).
11. BTS AND RADIO EQUIPMENT DELIVERED AT SITE DATE (POPULATE FIELD IN SMS AND/OR FORWARD NOTIFICATION).
12. NETWORK OPERATIONS HANDOFF CHECKLIST (HOC WALK) COMPLETE (UPLOAD FORM IN SMS)
13. CIVIL CONSTRUCTION COMPLETE DATE (POPULATE FIELD IN SMS AND/OR FORWARD NOTIFICATION).
14. SITE CONSTRUCTION PROGRESS PHOTOS UNLOADED INTO SMS.

SECTION 01 400 - SUBMITTALS & TESTS

PART 1 - GENERAL

- 1.1 THE WORK: THESE STANDARD CONSTRUCTION SPECIFICATIONS IN CONJUNCTION WITH THE OTHER CONTRACT DOCUMENTS AND THE CONSTRUCTION DRAWINGS DESCRIBE THE WORK TO BE PERFORMED BY THE CONTRACTOR.
- 1.2 RELATED DOCUMENTS:
 - A. THE REQUIREMENTS OF THIS SECTION APPLY TO ALL SECTIONS IN THIS SPECIFICATION.
 - B. SPRINT "STANDARD CONSTRUCTION DETAILS FOR WIRELESS SITES" ARE INCLUDED IN AND MADE A PART OF THESE SPECIFICATIONS HERewith.
- 1.3 SUBMITTALS:
 - A. THE WORK IN ALL ASPECTS SHALL COMPLY WITH THE CONSTRUCTION DRAWINGS AND THESE SPECIFICATIONS.
 - B. SUBMIT THE FOLLOWING TO COMPANY REPRESENTATIVE FOR APPROVAL.
 1. CONCRETE MIX-DESIGNS FOR TOWER FOUNDATIONS, ANCHORS PIERS, AND CONCRETE PAVING.
 2. CONCRETE BREAK TESTS AS SPECIFIED HEREIN.
 3. SPECIAL FINISHES FOR INTERIOR SPACES, IF ANY.
 4. ALL EQUIPMENT AND MATERIALS SO IDENTIFIED ON THE CONSTRUCTION DRAWINGS.
 5. CHEMICAL GROUNDING DESIGN
 - D. ALTERNATES: AT THE COMPANY'S REQUEST, ANY ALTERNATIVES TO THE MATERIALS OR METHODS SPECIFIED SHALL BE SUBMITTED TO SPRINT'S CONSTRUCTION MANAGER FOR APPROVAL PRIOR TO BEING SHIPPED TO SITE. SPRINT WILL REVIEW AND APPROVE ONLY THOSE REQUESTS MADE IN WRITING. NO VERBAL APPROVALS WILL BE CONSIDERED. SUBMITTAL FOR APPROVAL SHALL INCLUDE A STATEMENT OF COST REDUCTION PROPOSED FOR USE OF ALTERNATE PRODUCT.

1.4 TESTS AND INSPECTIONS:

- A. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL CONSTRUCTION TESTS, INSPECTIONS AND PROJECT DOCUMENTATION.
- B. CONTRACTOR SHALL ACCOMPLISH TESTING INCLUDING BUT NOT LIMITED TO THE FOLLOWING:
 1. COAX SWEEPS AND FIBER TESTS PER TS-0200 REV 4 ANTENNA LINE ACCEPTANCE STANDARDS.
 2. AGL, AZIMUTH AND DOWNTILT USING ELECTRONIC COMMERCIAL MADE-FOR-THE-PURPOSE ANTENNA ALIGNMENT TOOL.
 3. CONTRACTOR SHALL BE RESPONSIBLE FOR ANY AND ALL CORRECTIONS TO ANY WORK IDENTIFIED AS UNACCEPTABLE IN SITE INSPECTION ACTIVITIES AND/OR AS A RESULT OF TESTING.
- C. REQUIRED CLOSEOUT DOCUMENTATION INCLUDES, BUT IS NOT LIMITED TO THE FOLLOWING:
 1. AZIMUTH, DOWNTILT, AGL - UPLOAD REPORT FROM ANTENNA ALIGNMENT TOOL TO SITERRA TASK 465. INSTALLED AZIMUTH, DOWNTILT, AND AGL MUST CONFORM TO THE RF DATA SHEETS. SWEEP AND FIBER TESTS
 2. SCANABLE BARCODE PHOTOGRAPHS OF TOWER TOP AND INACCESSIBLE SERIALIZED EQUIPMENT
 3. ALL AVAILABLE JURISDICTIONAL INFORMATION
 4. PDF SCAN OF REDLINES PRODUCED IN FIELD

5. ELECTRONIC AS-BUILT DRAWINGS IN AUTOCAD AND PDF FORMATS. ANY FIELD CHANGE MUST BE REFLECTED BY MODIFYING THE PLANS, ELEVATIONS, AND DETAILS IN THE DRAWING SETS. GENERAL NOTES INDICATING MODIFICATIONS WILL NOT BE ACCEPTED. CHANGES SHALL BE HIGHLIGHTED AS "CLOUDS" IDENTIFIED AS THE "AS-BUILT" CONDITION.
6. LIEN WAIVERS
7. FINAL PAYMENT APPLICATION
8. REQUIRED FINAL CONSTRUCTION PHOTOS
9. CONSTRUCTION AND COMMISSIONING CHECKLIST COMPLETE WITH NO DEFICIENT ITEMS
10. ALL POST NTP TASKS INCLUDING DOCUMENT UPLOADS COMPLETED IN SITERRA (SPRINTS DOCUMENT REPOSITORY OF RECORD).

1.5 COMMISSIONING: PERFORM ALL COMMISSIONING AS REQUIRED BY APPLICABLE MOPs

1.6 INTEGRATION: PERFORM ALL INTEGRATION ACTIVITIES AS REQUIRED BY APPLICABLE MOPs

PART 2 - PRODUCTS (NOT USED)

PART 3 - EXECUTION

3.1 REQUIREMENTS FOR TESTING:

A. THIRD PARTY TESTING AGENCY:

1. WHEN THE USE OF A THIRD PARTY INDEPENDENT TESTING AGENCY IS REQUIRED, THE AGENCY THAT IS SELECTED MUST PERFORM SUCH WORK ON A REGULAR BASIS IN THE STATE WHERE THE PROJECT IS LOCATED AND HAVE A THOROUGH UNDERSTANDING OF LOCAL AVAILABLE MATERIALS, INCLUDING THE SOIL, ROCK, AND GROUNDWATER CONDITIONS.
2. THE THIRD PARTY TESTING AGENCY IS TO BE FAMILIAR WITH THE APPLICABLE REQUIREMENTS FOR THE TESTS TO BE DONE, EQUIPMENT TO BE USED, AND ASSOCIATED HEALTH AND SAFETY ISSUES.
3. EXPERIENCE IN SOILS, CONCRETE, MASONRY, AGGREGATE, AND ASPHALT TESTING USING ASTM, AASHTO, AND OTHER METHODS IS NEEDED.
4. EXPERIENCE IN SOILS, CONCRETE, MASONRY, AGGREGATE, AND ASPHALT TESTING USING ASTM, AASHTO, AND OTHER METHODS IS NEEDED.

3.2 REQUIRED TESTS:

A. CONTRACTOR SHALL ACCOMPLISH TESTING INCLUDING BUT NOT LIMITED TO THE FOLLOWING:

1. CONCRETE CYLINDER BREAK TESTS FOR THE TOWER AND ANCHOR FOUNDATIONS AS SPECIFIED IN SECTION: PORTLAND CEMENT CONCRETE PAVING.
2. ASPHALT ROADWAY COMPACTED THICKNESS, SURFACE SMOOTHNESS, AND COMPACTED DENSITY TESTING AS SPECIFIED IN SECTION: HOT MIX ASPHALT PAVING.
3. FIELD QUALITY CONTROL TESTING AS SPECIFIED IN SECTION: PORTLAND CEMENT CONCRETE PAVING.
4. TESTING REQUIRED UNDER SECTION: AGGREGATE BASE FOR ACCESS ROADS, PADS AND ANCHOR LOCATIONS
5. STRUCTURAL BACKFILL COMPACTION TESTS FOR THE TOWER FOUNDATION.
6. SITE RESISTANCE TO EARTH TESTING PER EXHIBIT: CELL SITE GROUNDING SYSTEM DESIGN.
7. ANTENNA AND COAX SWEEP TESTS PER EXHIBIT: ANTENNA TRANSMISSION LINE ACCEPTANCE STANDARDS.
8. GROUNDING AT ANTENNA MASTS FOR GPS AND ANTENNAS
9. ALL OTHER TESTS REQUIRED BY COMPANY OR JURISDICTION.

3.3 REQUIRED INSPECTIONS

A. SCHEDULE INSPECTIONS WITH COMPANY REPRESENTATIVE.

B. CONDUCT INSPECTIONS INCLUDING BUT NOT LIMITED TO THE FOLLOWING:

1. GROUNDING SYSTEM INSTALLATION PRIOR TO EARTH CONCEALMENT DOCUMENTED WITH DIGITAL PHOTOGRAPHS BY CONTRACTOR, APPROVED BY A&E OR SPRINT REPRESENTATIVE.
2. FORMING FOR CONCRETE AND REBAR PLACEMENT PRIOR TO POUR DOCUMENTED WITH DIGITAL PHOTOGRAPHS BY CONTRACTOR, APPROVED BY A&E OR SPRINT REPRESENTATIVE.
3. COMPACTION OF BACKFILL MATERIALS; AGGREGATE BASE FOR ROADS, PADS, AND ANCHORS; ASPHALT PAVING; AND SHAFT BACKFILL FOR CONCRETE AND WOOD POLES, BY INDEPENDENT THIRD PARTY AGENCY.
4. PRE- AND POST-CONSTRUCTION ROOFTOP AND STRUCTURAL INSPECTIONS ON EXISTING FACILITIES.
5. TOWER ERECTION SECTION STACKING AND PLATFORM ATTACHMENT DOCUMENTED BY DIGITAL PHOTOGRAPHS BY THIRD PARTY AGENCY.
6. ANTENNA AZIMUTH , DOWN TILT AND PER SUNLIGHT TOOL SUNSIGHT INSTRUMENTS - ANTENNALIGN ALIGNMENT TOOL (AAT)

PLANS PREPARED FOR:



PLANS PREPARED BY:



MLA PARTNER:



ENGINEERING LICENSE:



DRAWING NOTICE:

THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF SPRINT AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPRINT.

REVISIONS:

| DESCRIPTION | DATE | BY | REV |
|-------------------------|----------|-----|-----|
| ISSUED FOR CONSTRUCTION | 07/15/14 | DJG | 2 |
| REVISED PER COMMENTS | 07/10/14 | JLM | 1 |
| ISSUED FOR PERMIT | 06/10/14 | DJG | 0 |
| ISSUED FOR REVIEW | 05/27/14 | JLM | A |

SITE NAME:

BILKAYS EXPRESS

SITE CASCADE:

CT43XC839

SITE ADDRESS:

**90 N. PLAINS INDUSTRIAL RD.
WALLINGFORD, CT 06492**

SHEET DESCRIPTION:

SPRINT SPECIFICATIONS

SHEET NUMBER:

SP-2

CONTINUE FROM SP-2

7. VERIFICATION DOCUMENTED WITH THE ANTENNA CHECKLIST REPORT, BY A&E, SITE DEVELOPMENT REP, OR RF REP.
 8. FINAL INSPECTION CHECKLIST AND HANDOFF WALK (HOC). SIGNED FORM SHOWING ACCEPTANCE BY FIELD OPS IS TO BE UPLOADED INTO SMS.
 9. COAX SWEEP AND FIBER TESTING DOCUMENTS SUBMITTED VIA SMS FOR RF APPROVAL.
 10. SCAN-ABLE BARCODE PHOTOGRAPHS OF TOWER TOP AND INACCESSIBLE SERIALIZED EQUIPMENT
 11. ALL AVAILABLE JURISDICTIONAL INFORMATION
 12. PDF SCAN OF REDLINES PRODUCED IN FIELD
- C. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ANY AND ALL CORRECTIONS TO ANY WORK IDENTIFIED AS UNACCEPTABLE IN SITE INSPECTION ACTIVITIES AND/OR AS A RESULT OF TESTING.
- D. CONSTRUCTION INSPECTIONS AND CORRECTIVE MEASURES SHALL BE DOCUMENTED BY THE CONTRACTOR WITH WRITTEN REPORTS AND PHOTOGRAPHS. PHOTOGRAPHS MUST BE DIGITAL AND OF SUFFICIENT QUALITY TO CLEARLY SHOW THE SITE CONSTRUCTION. PHOTOGRAPHS MUST CLEARLY IDENTIFY THE PHOTOGRAPHED ITEM AND BE LABELED WITH THE SITE CASCADE NUMBER, SITE NAME, DESCRIPTION, AND DATE.
- 3.4 DELIVERABLES: TEST AND INSPECTION REPORTS AND CLOSEOUT DOCUMENTATION SHALL BE UPLOADED TO THE SMS AND/OR FORWARDED TO SPRINT FOR INCLUSION INTO THE PERMANENT SITE FILES.
- A. THE FOLLOWING TEST AND INSPECTION REPORTS SHALL BE PROVIDED AS APPLICABLE.
1. CONCRETE MIX AND CYLINDER BREAK REPORTS.
 2. STRUCTURAL BACKFILL COMPACTION REPORTS.
 3. SITE RESISTANCE TO EARTH TEST.
 4. ANTENNA AZIMUTH AND DOWN TILT VERIFICATION
 5. TOWER ERECTION INSPECTIONS AND MEASUREMENTS DOCUMENTING TOWER INSTALLED PER SUPPLIER'S REQUIREMENTS AND THE APPLICABLE SECTIONS HEREIN.
 6. COAX CABLE SWEEP TESTS PER COMPANY'S "ANTENNA LINE ACCEPTANCE STANDARDS".
- B. REQUIRED CLOSEOUT DOCUMENTATION INCLUDES THE FOLLOWING;
1. TEST WELLS AND TRENCHES: PHOTOGRAPHS OF ALL TEST WELLS; PHOTOGRAPHS SHOWING ALL OPEN EXCAVATIONS AND TRENCHING PRIOR TO BACKFILLING SHOWING A TAPE MEASURE VISIBLE IN THE EXCAVATIONS INDICATING DEPTH.
 2. CONDUITS, CONDUCTORS AND GROUNDING: PHOTOGRAPHS SHOWING TYPICAL INSTALLATION OF CONDUCTORS AND CONNECTORS; PHOTOGRAPHS SHOWING TYPICAL BEND RADIUS OF INSTALLED GROUND WIRES AND GROUND ROD SPACING;
 3. CONCRETE FORMS AND REINFORCING: CONCRETE FORMING AT TOWER AND EQUIPMENT/SHELTER PAD/FOUNDATIONS - PHOTOGRAPHS SHOWING ALL REINFORCING STEEL, UTILITY AND CONDUIT STUB OUTS; PHOTOGRAPHS SHOWING CONCRETE POUR OF SHELTER SLAB/FOUNDATION, TOWER FOUNDATION AND GUY ANCHORS WITH VIBRATOR IN USE; PHOTOGRAPHS SHOWING EACH ANCHOR ON GUYED TOWERS, BEFORE CONCRETE POUR.
 4. TOWER, ANTENNAS AND MAINLINE: INSPECTION AND PHOTOGRAPHS OF SECTION STACKING; INSPECTION AND PHOTOGRAPHS OF PLATFORM COMPONENT ATTACHMENT POINTS; PHOTOGRAPHS OF TOWER TOP GROUNDING; PHOTOS OF TOWER COAX LINE COLOR CODING AT THE TOP AND AT GROUND LEVEL; INSPECTION AND PHOTOGRAPHS OF OPERATIONAL OF TOWER LIGHTING, AND PLACEMENT OF FAA REGISTRATION SIGN; PHOTOGRAPHS SHOWING ADDITIONAL GROUNDING POINTS FOR TOWERS GREATER THAN 200 FEET.; PHOTOS OF ANTENNA GROUND BAR, EQUIPMENT GROUND BAR, AND MASTER GROUND BAR; PHOTOS OF GPS ANTENNA(S); PHOTOS OF EACH SECTOR OF ANTENNAS; ONE PHOTOGRAPH LOOKING AT THE SECTOR AND ONE FROM BEHIND SHOWING THE PROJECTED COVERAGE AREA; PHOTOS OF COAX WEATHERPROOFING - TOP AND BOTTOM; PHOTOS OF COAX GROUNDING--TOP AND BOTTOM; PHOTOS OF ANTENNA AND MAST GROUNDING; PHOTOS OF COAX CABLE ENTRY INTO SHELTER; PHOTOS OF PLATFORM MECHANICAL CONNECTIONS TO TOWER/MONOPOLE.
 5. ROOF TOPS: PRE-CONSTRUCTION AND POST-CONSTRUCTION VISUAL INSPECTION AND PHOTOGRAPHS OF THE ROOF AND INTERIOR TO DETERMINE AND DOCUMENT CONDITIONS; ROOF TOP CONSTRUCTION INSPECTIONS AS REQUIRED BY THE JURISDICTION; PHOTOGRAPHS OF CABLE TRAY AND/OR ICE BRIDGE; PHOTOGRAPHS OF DOGHOUSE/CABLE EXIT FROM ROOF;
 6. SITE LAYOUT - PHOTOGRAPHS OF THE OVERALL COMPOUND, INCLUDING EQUIPMENT PLATFORM FROM ALL FOUR CORNERS.
 7. FINISHED UTILITIES: CLOSE-UP PHOTOGRAPHS OF THE PPC BREAKER PANEL; CLOSE-UP PHOTOGRAPH OF THE INSIDE OF THE TELCO PANEL AND NIU; CLOSE-UP PHOTOGRAPH OF THE POWER METER AND DISCONNECT; PHOTOS OF POWER AND TELCO ENTRANCE TO COMPANY ENCLOSURE; PHOTOGRAPHS AT METER BOX AND/OR FACILITY DISTRIBUTION PANEL.
 8. REQUIRED MATERIALS CERTIFICATIONS: CONCRETE MIX DESIGNS; MILL CERTIFICATION FOR ALL REINFORCING AND STRUCTURAL STEEL; AND ASPHALT PAVING MIX DESIGN.
 9. ANY AND ALL SUBMITTALS BY THE JURISDICTION OR COMPANY.

SECTION 01 400 - SUBMITTALS & TESTS

PART 1 - GENERAL

- 1.1 THE WORK: THESE STANDARD CONSTRUCTION SPECIFICATIONS IN CONJUNCTION WITH THE OTHER CONTRACT DOCUMENTS AND THE CONSTRUCTION DRAWINGS DESCRIBE THE WORK TO BE PERFORMED BY THE CONTRACTOR.
- 1.2 RELATED DOCUMENTS:
 - A. THE REQUIREMENTS OF THIS SECTION APPLY TO ALL SECTIONS IN THIS SPECIFICATION.
 - B. SPRINT "STANDARD CONSTRUCTION DETAILS FOR WIRELESS SITES" ARE INCLUDED IN AND MADE A PART OF THESE SPECIFICATIONS HEREWITH.

PART 2 - PRODUCTS (NOT USED)

PART 3 - EXECUTION

- 3.1 WEEKLY REPORTS:
 - A. CONTRACTOR SHALL PROVIDE SPRINT WITH WEEKLY REPORTS SHOWING PROJECT STATUS. THIS STATUS REPORT FORMAT WILL BE PROVIDED TO THE CONTRACTOR BY SPRINT. THE REPORT WILL CONTAIN SITE ID NUMBER, THE MILESTONES FOR EACH SITE, INCLUDING THE BASELINE DATE, ESTIMATED COMPLETION DATE AND ACTUAL COMPLETION DATE.
 - B. REPORT INFORMATION WILL BE TRANSMITTED TO SPRINT VIA ELECTRONIC MEANS AS REQUIRED. THIS INFORMATION WILL PROVIDE A BASIS FOR PROGRESS MONITORING AND PAYMENT.
- 3.2 PROJECT CONFERENCE CALLS:
 - A. SPRINT MAY HOLD WEEKLY PROJECT CONFERENCE CALLS. CONTRACTOR WILL BE REQUIRED TO COMMUNICATE SITE STATUS, MILESTONE COMPLETIONS AND UPCOMING MILESTONE PROJECTIONS, AND ANSWER ANY OTHER SITE STATUS QUESTIONS AS NECESSARY.
- 3.3 PROJECT TRACKING IN SMS:
 - A. CONTRACTOR SHALL PROVIDE SCHEDULE UPDATES AND PROJECTIONS IN THE SMS SYSTEM ON A WEEKLY BASIS.
- 3.4 ADDITIONAL REPORTING:
 - A. ADDITIONAL OR ALTERNATE REPORTING REQUIREMENTS MAY BE ADDED TO THE REPORT AS DETERMINED TO BE REASONABLY NECESSARY BY COMPANY.
- 3.5 PROJECT PHOTOGRAPHS:
 - A. FILE DIGITAL PHOTOGRAPHS OF COMPLETED SITE IN JPEG FORMAT IN THE SMS PHOTO LIBRARY FOR THE RESPECTIVE SITE. PHOTOGRAPHS SHALL BE CLEARLY LABELED WITH SITE NUMBER, NAME AND DESCRIPTION, AND SHALL INCLUDE AT A MINIMUM THE FOLLOWING AS APPLICABLE:
 1. SHELTER AND TOWER OVERVIEW.
 2. TOWER FOUNDATION(S) - FORMS AND STEEL BEFORE POUR (EACH ANCHOR ON GUYED TOWERS).
 3. TOWER FOUNDATION(S) POUR WITH VIBRATOR IN USE (EACH ANCHOR ON GUYED TOWERS).
 4. TOWER STEEL AS BEING INSTALLED INTO HOLE (SHOW ANCHOR STEEL ON GUYED TOWERS).
 5. PHOTOS OF TOWER SECTION STACKING.
 6. CONCRETE TESTING / SAMPLES.
 7. PLACING OF ANCHOR BOLTS IN TOWER FOUNDATION.
 8. BUILDING/WATER TANK FROM ROAD FOR TENANT IMPROVEMENTS OR COMMENTS.
 9. SHELTER FOUNDATION--FORMS AND STEEL BEFORE POURING.
 10. SHELTER FOUNDATION POUR WITH VIBRATOR IN USE.
 11. COAX CABLE ENTRY INTO SHELTER.
 12. PLATFORM MECHANICAL CONNECTIONS TO TOWER/MONOPOLE.
 13. ROOFTOP PRE AND POST CONSTRUCTION PHOTOS TO INCLUDE PENETRATIONS AND INTERIOR CEILING.
 14. PHOTOS OF TOWER TOP COAX LINE COLOR CODING AND COLOR CODING AT GROUND LEVEL.
 15. PHOTOS OF ALL APPROPRIATE COMPANY OR REGULATORY SIGNAGE.
 16. PHOTOS OF EQUIPMENT BOLT DOWN INSIDE SHELTER.
 17. POWER AND TELCO ENTRANCE TO COMPANY ENCLOSURE AND POWER AND TELCO SUPPLY LOCATIONS INCLUDING METER/DISCONNECT.
 18. ELECTRICAL TRENCH(S) WITH ELECTRICAL / CONDUIT BEFORE BACKFILL.
 19. ELECTRICAL TRENCH(S) WITH FOIL-BACKED TAPE BEFORE FURTHER BACKFILL.
 20. TELCO TRENCH WITH TELEPHONE / CONDUIT BEFORE BACKFILL.
 21. TELCO TRENCH WITH FOIL-BACKED TAPE BEFORE FURTHER BACKFILL.
 22. SHELTER GROUND-RING TRENCH WITH GROUND-WIRE BEFORE BACKFILL (SHOW ALL CAD WELDS AND BEND RADII).
 23. TOWER GROUND-RING TRENCH WITH GROUND-WIRE BEFORE BACKFILL (SHOW ALL CAD WELDS AND BEND RADII).

24. FENCE GROUND-RING TRENCH WITH GROUND-WIRE BEFORE BACKFILL (SHOW ALL CAD WELDS AND BEND RADII).
 25. ALL BTS GROUND CONNECTIONS.
 26. ALL GROUND TEST WELLS.
 27. ANTENNA GROUND BAR AND EQUIPMENT GROUND BAR.
 28. ADDITIONAL GROUNDING POINTS ON TOWERS ABOVE 200'.
 29. HVAC UNITS INCLUDING CONDENSERS ON SPLIT SYSTEMS.
 30. GPS ANTENNAS.
 31. CABLE TRAY AND/OR WAVEGUIDE BRIDGE.
 32. DOGHOUSE/CABLE EXIT FROM ROOF.
 33. EACH SECTOR OF ANTENNAS; ONE PHOTOGRAPH LOOKING AT THE SECTOR AND ONE FROM BEHIND SHOWING THE PROJECTED COVERAGE AREA.
 34. MASTER BUS BAR.
 35. TELCO BOARD AND NIU.
 36. ELECTRICAL DISTRIBUTION WALL.
 37. CABLE ENTRY WITH SURGE SUPPRESSION.
 38. ENTRANCE TO EQUIPMENT ROOM.
 39. COAX WEATHERPROOFING--TOP AND BOTTOM OF TOWER.
 40. COAX GROUNDING --TOP AND BOTTOM OF TOWER.
 41. ANTENNA AND MAST GROUNDING.
 42. LANDSCAPING - WHERE APPLICABLE.
- 3.6 FINAL PROJECT ACCEPTANCE: COMPLETE ALL REQUIRED REPORTING TASKS PER CONTRACT, CONTRACT DOCUMENTS OR THE SPRINT INTEGRATED CONSTRUCTION STANDARDS FOR WIRELESS SITES AND UPLOAD INTO SITERRA.

PLANS PREPARED FOR:



6580 Sprint Parkway
Overland Park, Kansas 66251

PLANS PREPARED BY:




1033 Watervliet Shaker Rd
Albany, NY 12205
Office # (518) 690-0790
Fax # (518) 690-0793
JOB NUMBER 340-000

MLA PARTNER:



10 PRESIDENTIAL WAY
WOBBURN, MA 01801

ENGINEERING LICENSE:



DRAWING NOTICE:

THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF SPRINT AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPRINT.

REVISIONS:

| DESCRIPTION | DATE | BY | REV |
|-------------------------|----------|-----|-----|
| ISSUED FOR CONSTRUCTION | 07/15/14 | DJG | 2 |
| REVISED PER COMMENTS | 07/10/14 | JJM | 1 |
| ISSUED FOR PERMIT | 06/10/14 | DJG | 0 |
| ISSUED FOR REVIEW | 05/27/14 | JJM | A |

SITE NAME:

BILKAYS EXPRESS

SITE CASCADE:

CT43XC839

SITE ADDRESS:

90 N. PLAINS INDUSTRIAL RD.
WALLINGFORD, CT 06492


SHEET DESCRIPTION:

SPRINT SPECIFICATIONS

SHEET NUMBER:

SP-3


INFORMATION CONTAINED WITHIN DRAWINGS ARE BASED ON PROVIDED INFORMATION AND ARE NOT THE RESULT OF A FIELD SURVEY.



2.5' 0 2.5' 5' 10'
(IN FEET)
SCALE: 24"x36" SHEET 1" = 5'-0"
SCALE: 11"x17" SHEET 1" = 10'-0"

OVERALL SITE PLAN

SCALE: AS NOTED 1



1' 0 1' 2' 4'
(IN FEET)
SCALE: 24"x36" SHEET 1" = 2'-0"
SCALE: 11"x17" SHEET 1" = 4'-0"

SPRINT EQUIPMENT PLAN

SCALE: AS NOTED 2

PLANS PREPARED FOR:

6580 Sprint Parkway
Overland Park, Kansas 66251

PLANS PREPARED BY:

1033 Watervliet Shaker Rd
Albany, NY 12205
Office # (518) 690-0790
Fax # (518) 690-0793
JOB NUMBER 340-000

MLA PARTNER:

10 PRESIDENTIAL WAY
WOBURN, MA 01801

ENGINEERING LICENSE:

DRAWING NOTICE:

THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF SPRINT AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPRINT.

REVISIONS:

| DESCRIPTION | DATE | BY | REV |
|-------------------------|----------|-----|-----|
| ISSUED FOR CONSTRUCTION | 07/15/14 | DJG | 2 |
| REVISED PER COMMENTS | 07/10/14 | JLM | 1 |
| ISSUED FOR PERMIT | 06/10/14 | DJG | 0 |
| ISSUED FOR REVIEW | 05/27/14 | JLM | A |


SITE NAME:
BILKAYS EXPRESS

SITE CASCADE:
CT43XC839

SITE ADDRESS:
**90 N. PLAINS INDUSTRIAL RD.
WALLINGFORD, CT 06492**

SHEET DESCRIPTION:
SITE PLAN

SHEET NUMBER:
A-1




EXISTING SPRINT FIBER JUNCTION BOX
 EXISTING AAV EQUIPMENT
 EXISTING SPRINT PPC CABINET

EXISTING SPRINT 10'x14' CONCRETE EQUIPMENT PAD W/OVERHEAD ICE SHIELD CANOPY
 EXISTING SPRINT N.V. MMBS CABINET
 EXISTING SPRINT BATTERY CABINET

EXISTING CABINET LINE-UP

SCALE: AS NOTED 1




INSTALL (4) NEW BATTERIES IN EXISTING BATTERY CABINET

EXISTING BATTERY (TYP. OF (4) PER STRING)


EXISTING SPRINT BATTERY CABINET

EXISTING BATTERY CABINET

SCALE: AS NOTED 2




TOP VIEW




FRONT VIEW

MANUFACTURER: ALU
 MODEL: 9927

N.V. MMBS CABINET



TOP VIEW



REAR VIEW

MANUFACTURER: AVAYA
 MODEL: 60ECV2

BATTERY CABINET

INFORMATION SHOWN ABOVE BASED ON INFORMATION CONTAINED WITHIN SPRINT N.V DRAWING. CONTRACTOR TO VERIFY IN FIELD EXACT MAKE AND MODEL.

EXISTING CABINET DETAILS

SCALE: AS NOTED 3

PLANS PREPARED FOR:

6580 Sprint Parkway
 Overland Park, Kansas 66251

PLANS PREPARED BY:

Design. Build. Deliver.
 1033 Watervliet Shaker Rd
 Albany, NY 12205
 Office # (518) 690-0790
 Fax # (518) 690-0793
 JOB NUMBER 340-000

MLA PARTNER:

10 PRESIDENTIAL WAY
 WOBURN, MA 01801

ENGINEERING LICENSE:

DRAWING NOTICE:
 THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF SPRINT AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPRINT.

REVISIONS:

| DESCRIPTION | DATE | BY | REV |
|-------------------------|----------|-------|-----|
| ISSUED FOR CONSTRUCTION | 07/15/14 | D.J.G | 2 |
| REVISED PER COMMENTS | 07/10/14 | J.M | 1 |
| ISSUED FOR PERMIT | 06/10/14 | D.J.G | 0 |
| ISSUED FOR REVIEW | 05/27/14 | J.M | A |



SITE NAME:
BILKAYS EXPRESS

SITE CASCADE:
CT43XC839

SITE ADDRESS:
 90 N. PLAINS INDUSTRIAL RD.
 WALLINGFORD, CT 06492

SHEET DESCRIPTION:
EXISTING EQUIPMENT DETAILS

SHEET NUMBER:
A-1A



PLANS PREPARED FOR:

Sprint

6580 Sprint Parkway
Overland Park, Kansas 66251

PLANS PREPARED BY:

INFINIGY Design. Build. Deliver.

1033 Watervliet Shaker Rd
Albany, NY 12205
Office # (518) 680-0790
Fax # (518) 690-0793

JOB NUMBER 340-000

MLA PARTNER:

AMERICAN TOWER CORPORATION

10 PRESIDENTIAL WAY
WOBURN, MA 01801



DRAWING NOTICE:

THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF SPRINT AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPRINT.

REVISIONS:

| DESCRIPTION | DATE | BY | REV |
|-------------------------|----------|-----|-----|
| ISSUED FOR CONSTRUCTION | 07/15/14 | DJG | 2 |
| REVISED PER COMMENTS | 07/10/14 | JLM | 1 |
| ISSUED FOR PERMIT | 06/10/14 | DJG | 0 |
| ISSUED FOR REVIEW | 05/27/14 | JLM | A |

SITE NAME:

BILKAYS EXPRESS

SITE CASCADE:

CT43XC839

SITE ADDRESS:


90 N. PLAINS INDUSTRIAL RD.
WALLINGFORD, CT 06492

SHEET DESCRIPTION:

TOWER ELEVATION & CABLE PLAN

SHEET NUMBER:


A-2



NOTE:
EXISTING SPRINT ANTENNA PIPE MOUNT LOCATIONS AND SIZES ARE BASED ON A STRUCTURAL ANALYSIS COMPLETED BY: "AMERICAN TOWER CORPORATION.", TITLED: "STRUCTURAL ANALYSIS REPORT", ATC SITE NAME: "BILKAYS EXPRESS, CT" DATED "JUNE 13, 2014"

EXISTING ANTENNA & RRU LAYOUT

NO SCALE 1




NOTE:
EXISTING SPRINT ANTENNA PIPE MOUNT LOCATIONS AND SIZES ARE BASED ON A STRUCTURAL ANALYSIS COMPLETED BY: "AMERICAN TOWER CORPORATION.", TITLED: "STRUCTURAL ANALYSIS REPORT", ATC SITE NAME: "BILKAYS EXPRESS, CT" DATED "JUNE 13, 2014"

THE CONFIGURATION PLANS ARE BASED ON PROVIDED INFORMATION AND ARE FOR CONCEPTUAL PURPOSES ONLY. CONTRACTOR TO VERIFY FIELD CONDITIONS PRIOR TO CONSTRUCTION.

NOTE:
JUMPERS FROM 2.5 RRU TO THE 2.5 ANTENNA CANNOT EXCEED 15 FEET

FINAL ANTENNA LAYOUT

NO SCALE 2




NOTE:
CONTRACTOR TO POSITION RRU ON MOUNT BEHIND ANTENNA SUCH THAT THE RRU DOES NOT INTERFERE WITH THE EXISTING PLATFORM/T-ARM MOUNTING HARDWARE.

NOTE:
SPARE DC CABLES ARE COILED UP ON NV RRHS AT SPRINT ARRAY. THESE ARE TO BE USED TO POWER UP THE 2.5 RRHS AND TIED INTO EXISTING DC BREAKERS INSIDE THE FIBER JUNCTION BOX LOCATED AT EQUIPMENT.

NOTE:
THE DIAGRAM IS FOR CONCEPTUAL PURPOSES ONLY. CONTRACTOR IS TO REFER TO PASSING STRUCTURAL ANALYSIS FOR ANTENNA AND RRU MOUNTING DETAILS

DETAIL NOT USED

NO SCALE 3



TYPICAL ANTENNA & RRU MOUNTING DETAILS

NO SCALE 4

PLANS PREPARED FOR:

6580 Sprint Parkway
Overland Park, Kansas 66251

PLANS PREPARED BY:

Design. Build. Deliver.
1033 Watervliet Shaker Rd
Albany, NY 12205
Office # (518) 690-0790
Fax # (518) 690-0793
JOB NUMBER 340-000

MLA PARTNER:

10 PRESIDENTIAL WAY
WOBBURN, MA 01801

ENGINEERING LICENSE:

DRAWING NOTICE:
THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF SPRINT AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPRINT.

REVISIONS:

| DESCRIPTION | DATE | BY | REV |
|-------------------------|----------|-----|-----|
| ISSUED FOR CONSTRUCTION | 07/15/14 | DJG | 2 |
| REVISED PER COMMENTS | 07/10/14 | JJM | 1 |
| ISSUED FOR PERMIT | 06/10/14 | DJG | 0 |
| ISSUED FOR REVIEW | 05/27/14 | JJM | A |

SITE NAME:
BILKAYS EXPRESS

SITE CASCADE:
CT43XC839

SITE ADDRESS:
90 N. PLAINS INDUSTRIAL RD.
WALLINGFORD, CT 06492

SHEET DESCRIPTION:
ANTENNA LAYOUT & MOUNTING DETAILS


SHEET NUMBER:
A-3

| NV CABLES | | | | |
|-----------|-----------|------|-------|--|
| BAND | INDICATOR | PORT | COLOR | |
| 800-1 | YEL GRN | NV-1 | GRN | |
| 1900-1 | YEL RED | NV-2 | BLU | |
| 1900-2 | YEL BRN | NV-3 | BRN | |
| 1900-3 | YEL BLU | NV-4 | WHT | |
| 1900-4 | YEL SLT | NV-5 | RED | |
| 800-2 | YEL ORG | NV-6 | SLT | |
| SPARE | YEL WHT | NV-7 | PPL | |
| 2500 | YEL PPL | NV-8 | ORG | |

| HYBRID | |
|--------|-------|
| HYBRID | COLOR |
| 1 | GRN |
| 2 | BLU |
| 3 | BRN |
| 4 | WHT |
| 5 | RED |
| 6 | SLT |
| 7 | PPL |
| 8 | ORG |

| 2.5 Band | | |
|--------------|-------|--|
| 2500 Radio 1 | COLOR | |
| YEL WHT | GRN | |
| YEL WHT | BLU | |
| YEL WHT | BRN | |
| YEL WHT | WHT | |
| YEL WHT | RED | |
| YEL WHT | SLT | |
| YEL WHT | PPL | |
| YEL WHT | ORG | |

Figure 1: Antenna Orientation






NOTES:

- ALL CABLES SHALL BE MARKED WITH 2" WIDE, UV STABILIZED, UL APPROVED TAPE.
- THE FIRST RING SHALL BE CLOSEST TO THE END OF THE CABLE AND SPACED APPROXIMATELY 2" FROM THE END CONNECTOR, WEATHERPROOFING, OR BREAK-OUT CYLINDER. THERE SHALL BE A 1" SPACE BETWEEN EACH RING FOR THE CABLE IDENTIFIER, AND NO SPACES BETWEEN THE FREQUENCY BANDS.
- A 2" GAP SHALL SEPARATE THE CABLE COLOR CODE FROM THE FREQUENCY COLOR CODE. THE 2" COLOR RINGS FOR THE FREQUENCY CODE SHALL BE PLACED NEXT TO EACH OTHER WITH NO SPACES.
- THE 2" COLORED TAPE(S) SHALL EACH BE WRAPPED A MINIMUM OF 3 TIMES AROUND THE INDIVIDUAL CABLES, AND THE TAPE SHALL BE KEPT IN THE SAME LOCATION AS MUCH AS POSSIBLE.
- SITES WITH MORE THAN FOUR (4) SECTORS WILL REQUIRE ADDITIONAL RINGS FOR EACH SECTOR, FOLLOWING THE PATTERN. HIGH CAPACITY SITES WILL USE THE NEXT COLOR IN THE SEQUENCE FOR ADDITIONAL CABLES IN EACH SECTOR.
- HYBRID FIBER CABLE SHALL BE SECTOR IDENTIFIED INSIDE THE CABINET ON FREQUENCY BUNDLES, ON THE SEALTITE, ON THE MAIN LINE UPON EXIT OF SEALTITE, AND BEFORE AND AFTER THE BREAKOUT UNIT (MEDUSA), AS WELL AS BEFORE AND AFTER ANY ENTRANCE OR EXIT.
- HFC "MAIN TRUNK" WILL NOT BE MARKED WITH THE FREQUENCY CODES, AS IT CONTAINS ALL FREQUENCIES.
- INDIVIDUAL POWER PAIRS AND FIBER BUNDLES SHALL BE LABELED WITH BOTH THE CABLE AND FREQUENCY.

| Sector | Cable | First Ring | Second Ring | Third Ring |
|---------|-------|------------|-------------|------------|
| 1 Alpha | 1 | Green | No Tape | No Tape |
| | 2 | Green | No Tape | No Tape |
| | 3 | Brown | No Tape | No Tape |
| | 4 | White | No Tape | No Tape |
| | 5 | Red | No Tape | No Tape |
| | 6 | Grey | No Tape | No Tape |
| | 7 | Purple | No Tape | No Tape |
| | 8 | Orange | No Tape | No Tape |
| 2 Beta | 1 | Green | Green | No Tape |
| | 2 | Green | Green | No Tape |
| | 3 | Brown | Brown | No Tape |
| | 4 | White | White | No Tape |
| | 5 | Red | Red | No Tape |
| | 6 | Grey | Grey | No Tape |
| | 7 | Purple | Purple | No Tape |
| | 8 | Orange | Orange | No Tape |
| 3 Gamma | 1 | Green | Green | Green |
| | 2 | Green | Green | Green |
| | 3 | Brown | Brown | Brown |
| | 4 | White | White | White |
| | 5 | Red | Red | Red |
| | 6 | Grey | Grey | Grey |
| | 7 | Purple | Purple | Purple |
| | 8 | Orange | Orange | Orange |

| NV FREQUENCY | INDICATOR | ID |
|--------------|-----------|-----|
| 800-1 | YEL GRN | GRN |
| 1900-1 | YEL RED | RED |
| 1900-2 | YEL BRN | BRN |
| 1900-3 | YEL BLU | BLU |
| 1900-4 | YEL SLT | SLT |
| 800-1 | YEL ORG | ORG |
| RESERVED | YEL WHT | WHT |
| RESERVED | YEL PPL | PPL |

| 2.5 FREQUENCY | INDICATOR | ID |
|---------------|-----------|-----|
| 2500 -1 | YEL WHT | GRN |
| 2500 -2 | YEL WHT | RED |
| 2500 -3 | YEL WHT | BRN |
| 2500 -4 | YEL WHT | BLU |
| 2500 -5 | YEL WHT | SLT |
| 2500 -6 | YEL WHT | ORG |
| 2500 -7 | YEL WHT | WHT |
| 2500 -8 | YEL WHT | PPL |



PLANS PREPARED FOR:

6580 Sprint Parkway
Overland Park, Kansas 66251

PLANS PREPARED BY:

1033 Watervliet Shaker Rd
Albany, NY 12205
Office # (518) 690-0790
Fax # (518) 690-0793

JOB NUMBER 340-000

MLA PARTNER:

10 PRESIDENTIAL WAY
WOBURN, MA 01801

ENGINEERING LICENSE:

DRAWING NOTICE:

THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF SPRINT AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPRINT.

| REVISIONS: | DESCRIPTION | DATE | BY | REV |
|-------------------------|-------------|----------|-----|-----|
| ISSUED FOR CONSTRUCTION | | 07/15/14 | DJG | 2 |
| REVISED PER COMMENTS | | 07/10/14 | JLM | 1 |
| ISSUED FOR PERMIT | | 06/10/14 | DJG | 0 |
| ISSUED FOR REVIEW | | 05/27/14 | JLM | A |

SITE NAME:

BILKAYS EXPRESS

SITE CASCADE:

CT43XC839

SITE ADDRESS:

90 N. PLAINS INDUSTRIAL RD.
WALLINGFORD, CT 06492

SHEET DESCRIPTION:


COLOR CODING AND NOTES

SHEET NUMBER:

A-4

RRU: ALCATEL LUCENT TD-RRH8X20

COLOR: LIGHT GREY
WEIGHT: 70 LBS.



NOTES
COMPLY WITH MANUFACTURERS INSTRUCTIONS TO ENSURE THAT ALL RRU'S RECEIVE ELECTRICAL POWER WITHIN 24 HOURS OF BEING REMOVED FROM THE MANUFACTURER'S PACKAGING. DO NOT OPEN RRU PACKAGES IN THE RAIN.

2.5 RRU


NO SCALE

1

NEW EQUIPMENT IN EXISTING CABINET



NO SCALE

2



ANTENNA: RFS APXVTM14-C-120


RADOME MATERIAL: ASA
RADOME COLOR: LIGHT GREY
DIMENSIONS, HxWxD.in(mim): 56.3"x12.6"x6.3" (1430x320x160mm)
WEIGHT: 52.9 lbs
CONNECTORS: (8) 4.1/9.5 DIN FEMALE
(1) NF - CALIBRATION CONNECTOR



2.5 ANTENNA

NO SCALE

3



INFINIGY ESTIMATES

| * Riser Cable Length Estimate | | Units |
|-------------------------------|-----|-------|
| At Grade | 31 | Feet |
| Vertical Rise | 118 | Feet |
| At Sprint Centerline | 3 | Feet |
| Sub-Total | 152 | Feet |
| 15% Buffer | 23 | Feet |
| Total | 175 | Feet |

ABOVE LENGTH IS AN ESTIMATE AND SHOULD BE VERIFIED IN FIELD PRIOR TO ORDERING MATERIALS.

| ** Hybrid/Fiber Jumper Length Estimate | | Units |
|--|---|-------|
| From Connector To RRU | 8 | Feet |

ABOVE LENGTH IS AN ESTIMATE AND SHOULD BE VERIFIED IN FIELD PRIOR TO ORDERING MATERIALS.

| Coax Jumper Length Estimate | | Units |
|-----------------------------|---|-------|
| From RRU to Antenna | 5 | Feet |

ABOVE LENGTH IS AN ESTIMATE AND SHOULD BE VERIFIED IN FIELD PRIOR TO ORDERING MATERIALS.

NOTE:
* & **: REFERENCE SHEET A-6, DETAIL 1 FOR CORRESPONDING PART NUMBERS.

CABLE LENGTH NOTE:
APPROXIMATE LENGTH OF NEW CABLE IS SHOWN IN CHART ON THIS SHEET. CONTRACTOR TO CONFIRM EXACT CABLE LENGTH REQUIRED PRIOR TO ORDERING MATERIALS.

DETAIL NOT USED

NO SCALE

4

PLANS PREPARED FOR:

6580 Sprint Parkway
Overland Park, Kansas 66251

PLANS PREPARED BY:

1033 Watervliet Shaker Rd
Albany, NY 12205
Office # (518) 690-0790
Fax # (518) 690-0793

JOB NUMBER 340-000

MLA PARTNER:

10 PRESIDENTIAL WAY
WOBURN, MA 01801

ENGINEERING LICENSE:

DRAWING NOTICE:
THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF SPRINT AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPRINT.

REVISIONS:

| DESCRIPTION | DATE | BY | REV |
|-------------------------|----------|-----|-----|
| ISSUED FOR CONSTRUCTION | 07/15/14 | DJG | 2 |
| REVISED PER COMMENTS | 07/10/14 | JJM | 1 |
| ISSUED FOR PERMIT | 06/10/14 | DJG | 0 |
| ISSUED FOR REVIEW | 05/27/14 | JJM | A |

SITE NAME:
BILKAYS EXPRESS

SITE CASCADE:
CT43XC839

SITE ADDRESS:
90 N. PLAINS INDUSTRIAL RD.
WALLINGFORD, CT 06492

SHEET DESCRIPTION:
EQUIPMENT & MOUNTING DETAILS

SHEET NUMBER:
A-5




RFS HYBRIFLEX RISER CABLE SCHEDULE

| | | |
|-----------------------------------|---|--------|
| Fiber Only (Existing DC Power) | Hybrid cable MN: HB058-M12-050F 12x multi-mode fiber pairs, Top: Outdoor protected connectors, Bottom: LC Connectors, 5/8 cable, 50 ft | 50 ft |
| | MN: HB058-M12-075F | 75 ft |
| | MN: HB058-M12-100F | 100 ft |
| | MN: HB058-M12-125F | 125 ft |
| | MN: HB058-M12-150F | 150 ft |
| | MN: HB058-M12-175F | 175 ft |
| | MN: HB058-M12-200F | 200 ft |
| 8 AWG Power | Hybrid cable MN: HB114-08U3M12-050F 3x 8 AWG power pairs, 12x multi-mode fiber pairs, Outdoor rated connectors & LC Connectors, 1 1/4 cable, 50 ft | 50 ft |
| | MN: HB114-08U3M12-075F | 75 ft |
| | MN: HB114-08U3M12-100F | 100 ft |
| | MN: HB114-08U3M12-125F | 125 ft |
| | MN: HB114-08U3M12-150F | 150 ft |
| | MN: HB114-08U3M12-175F | 175 ft |
| | MN: HB114-08U3M12-200F | 200 ft |
| 6 AWG Power | Hybrid cable MN: HB114-13U3M12-225F 3x 6 AWG power pair, 12x multi-mode fiber pairs, Outdoor rated connectors & LC Connectors, 1 1/4 cable, 225 ft | 225 ft |
| | MN: HB114-13U3M12-250F | 250 ft |
| | MN: HB114-13U3M12-275F | 275 ft |
| | MN: HB114-13U3M12-300F | 300 ft |
| 4 AWG Power | Hybrid cable MN: HB114-21U3M12-325F 3x 4 AWG power pair, 12x multi-mode fiber pairs, Outdoor rated connectors & LC Connectors, 1 1/4 cable, 325 ft | 325 ft |
| | MN: HB114-21U3M12-350F | 350 ft |
| | MN: HB114-21U3M12-375F | 375 ft |

RFS HYBRIFLEX JUMPER CABLE SCHEDULE

| | | |
|-------------|---|-------|
| Fiber Only | Hybrid Jumper cable MN: HBF012-M3-5F1 5 ft, 3x multi-mode fiber pairs, Outdoor & LC connectors, 1/2 cable | 5 ft |
| | MN: HBF012-M3-10F1 | 10 ft |
| | MN: HBF012-M3-15F1 | 15 ft |
| | MN: HBF012-M3-20F1 | 20 ft |
| | MN: HBF012-M3-25F1 | 25 ft |
| | MN: HBF012-M3-30F1 | 30 ft |
| 8 AWG Power | Hybrid Jumper cable MN: HBF058-08U1M3-5F1 5 ft, 1x 8 AWG power pair, 3x multi-mode fiber pairs, Outdoor & LC Connectors, 5/8 cable | 5 ft |
| | MN: HBF058-08U1M3-10F1 | 10 ft |
| | MN: HBF058-08U1M3-15F1 | 15 ft |
| | MN: HBF058-08U1M3-20F1 | 20 ft |
| | MN: HBF058-08U1M3-25F1 | 25 ft |
| | MN: HBF058-08U1M3-30F1 | 30 ft |
| 6 AWG Power | Hybrid Jumper cable MN: HBF058-13U1M3-5F1 5 ft, 1x 6 AWG power pair, 3x multi-mode fiber pairs, Outdoor & LC Connectors, 5/8 cable | 5 ft |
| | MN: HBF058-13U1M3-10F1 | 10 ft |
| | MN: HBF058-13U1M3-15F1 | 15 ft |
| | MN: HBF058-13U1M3-20F1 | 20 ft |
| | MN: HBF058-13U1M3-25F1 | 25 ft |
| | MN: HBF058-13U1M3-30F1 | 30 ft |
| 4 AWG Power | Hybrid Jumper cable MN: HBF078-21U1M3-5F1 5 ft, 1x 4 AWG power pair, 3x multi-mode fiber pairs, Outdoor & LC Connectors, 7/8 cable | 5 ft |
| | MN: HBF078-21U1M3-10F1 | 10 ft |
| | MN: HBF078-21U1M3-15F1 | 15 ft |
| | MN: HBF078-21U1M3-20F1 | 20 ft |
| | MN: HBF078-21U1M3-25F1 | 25 ft |
| | MN: HBF078-21U1M3-30F1 | 30 ft |

NOTE:
SPRINT CM TO CONFIRM HYBRID OR FIBER RISER CABLE
AND HYBRID OR FIBER JUMPER CABLE MODEL NUMBERS IF
HYBRID CABLES ARE REQUIRED BEFORE PREPARING BOM.



FIBER ONLY

PLANS PREPARED FOR:

Sprint
6580 Sprint Parkway
Overland Park, Kansas 66251

PLANS PREPARED BY:

INFINIGY Design. Build. Deliver.

1033 Watervliet Shaker Rd
Albany, NY 12205
Office # (518) 690-0790
Fax # (518) 690-0793

JOB NUMBER 340-000

MLA PARTNER:

AMERICAN TOWER CORPORATION

10 PRESIDENTIAL WAY
WOBURN, MA 01801

ENGINEERING LICENSE:



DRAWING NOTICE:

THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF SPRINT AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPRINT.

REVISIONS:

| DESCRIPTION | DATE | BY | REV |
|-------------------------|----------|-----|-----|
| ISSUED FOR CONSTRUCTION | 07/15/14 | DJG | 2 |
| REVISED PER COMMENTS | 07/10/14 | JLM | 1 |
| ISSUED FOR PERMIT | 06/10/14 | DJG | 0 |
| ISSUED FOR REVIEW | 05/27/14 | JLM | A |

SITE NAME:

BILKAYS EXPRESS

SITE CASCADE:

CT43XC839

SITE ADDRESS:

90 N. PLAINS INDUSTRIAL RD.
WALLINGFORD, CT 06492

SHEET DESCRIPTION:

CIVIL DETAILS

SHEET NUMBER:

A-6



DRAWING NOTICE:
 THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF SPRINT AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPRINT.

REVISIONS:

| DESCRIPTION | DATE | BY | REV |
|-------------------------|----------|--------|-----|
| ISSUED FOR CONSTRUCTION | 07/15/14 | D.J.G. | 2 |
| REVISED PER COMMENTS | 07/10/14 | J.M. | 1 |
| ISSUED FOR PERMIT | 06/10/14 | D.J.G. | 0 |
| ISSUED FOR REVIEW | 05/27/14 | J.M. | A |


SITE NAME:
BILKAYS EXPRESS

SITE CASCADE:
CT43XC839


SITE ADDRESS:
 90 N. PLAINS INDUSTRIAL RD.
 WALLINGFORD, CT 06492

SHEET DESCRIPTION:
PLUMBING DIAGRAM


SHEET NUMBER:
A-7



ALU 2.5 ALU SCENARIO 1



RAN WIRING DIAGRAM




RF 2.5 ALU SCENARIO 1

PLAN NOT USED


NO SCALE 1

- LEGEND:**
- G — EXISTING GROUND RING
 - CADWELD CONNECTION (EXOTHERMIC WELD)
 - ▲ MECHANICAL CONNECTION
 - ⊗ GROUND ROD
 - CABLE GROUND KIT



TYPICAL ANTENNA GROUNDING PLAN

NO SCALE 2



TYPICAL EQUIPMENT GROUNDING PLAN (ELEVATION)

NO SCALE 3

DRAWING NOTICE:

THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF SPRINT AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPRINT.

REVISIONS:

| DESCRIPTION | DATE | BY | REV |
|-------------------------|----------|--------|-----|
| ISSUED FOR CONSTRUCTION | 07/15/14 | D.J.G. | 2 |
| REVISED PER COMMENTS | 07/10/14 | J.M. | 1 |
| ISSUED FOR PERMIT | 06/10/14 | D.J.G. | 0 |
| ISSUED FOR REVIEW | 05/27/14 | J.M. | A |

SITE NAME:

BILKAYS EXPRESS

SITE CASCADE:

CT43XC839

SITE ADDRESS:


90 N. PLAINS INDUSTRIAL RD.
WALLINGFORD, CT 06492

SHEET DESCRIPTION:

ELECTRICAL & GROUNDING PLAN

SHEET NUMBER:

E-1



DRAWING NOTICE:
 THESE DOCUMENTS ARE CONFIDENTIAL AND ARE THE SOLE PROPERTY OF SPRINT AND MAY NOT BE REPRODUCED, DISSEMINATED OR REDISTRIBUTED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPRINT.

REVISIONS:

| DESCRIPTION | DATE | BY | REV |
|-------------------------|----------|-------|-----|
| ISSUED FOT CONSTRUCTION | 07/15/14 | D.J.G | 2 |
| REVISED PER COMMENTS | 07/10/14 | J.M | 1 |
| ISSUED FOR PERMIT | 06/10/14 | D.J.G | 0 |
| ISSUED FOR REVIEW | 05/27/14 | J.M | A |

SITE NAME:
BILKAYS EXPRESS


SITE CASCADE:
CT43XC839

SITE ADDRESS:
 90 N. PLAINS INDUSTRIAL RD.
 WALLINGFORD, CT 06492

SHEET DESCRIPTION:
ELECTRICAL & GROUNDING DETAILS

SHEET NUMBER:
E-2

NOTES
 CG SHALL REFERENCE ALL SPECS FOR "CONNECTING THE POWER SUPPLY" OF THE NEW INSTALLATION DOCUMENTS, FOR ALL CONNECTION SPECIFICATIONS.




CIRCUIT SCHEDULE

| NO | FROM | TO | CONFIGURATION |
|----|------------------------|---------------------------------|---------------|
| ① | UTILITY SOURCE | METER/DISCONNECT | EXISTING |
| ② | METER/DISCONNECT | TRANSFER & LOAD CENTER | EXISTING |
| ③ | TRANSFER & LOAD CENTER | GENERATOR RECEPTACLE | EXISTING |
| ④ | TRANSFER & LOAD CENTER | EXISTING SPRINT BATTERY CABINET | EXISTING |
| ⑤ | TRANSFER & LOAD CENTER | EXISTING SPRINT MMBS CABINET | EXISTING |

ELECTRICAL ONE-LINE DIAGRAM


NO SCALE 1



NOTES
 1. APPLY NO-OX TO LUG AND BAR CONTACT SURFACE. DO NOT COAT INLINE LUG.
 2. IF STOLEN GROUND BARS ARE ENCOUNTERED, CONTACT SPRINT CM FOR REPLACEMENT THREADED ROD KIT.


INSTALLATION OF GROUNDING CONDUCTOR TO GROUNDING BAR

NO SCALE 2



TWO HOLE LUG

NO SCALE 3



GROUNDING RISER DIAGRAM

NO SCALE 4