



April 16, 2021

Melanie A. Bachman
Executive Director
Connecticut Siting Council
10 Franklin Square
New Britain, CT 06051

RE: **Notice of Exempt Modification for T-Mobile
Crown Site ID# 881534; T-Mobile Site ID# CTNH452A
670 Captain Neville Drive, Waterbury, CT 06705
Latitude: 41° 32' 3.60" / Longitude: -72° 58' 8.40"**

Dear Ms. Bachman:

T-Mobile currently maintains six (6) antennas at the 140-foot mount on the existing 150-foot Monopole Tower located at 670 Captain Neville Drive in Waterbury. The property is owned by MW Cell REIT 1, LLC (Crown Castle) and the Tower is owned by Crown Castle. T-Mobile now intends to replace six (6) existing antennas and add three (3) new antennas. This modification/proposal includes hardware that is both 4G(LTE) and 5G capable through remote software configuration and either or both services may be turned on or off at various times.

Planned Modifications:

Tower:

Remove and Replace:

(3) RFS – APXVTM14-ALU-120 Antennas (**REMOVE**) - (3) RFS – APX16DWV-16DWV-S-E-A20 Antennas (**REPLACE**)

(3) Commscope – NNVV-65B-R4 Antennas (**REMOVE**) – (3) RFS – APXVAALL24_43-U-NA20 Antennas (**REPLACE**)

(4) Alcatel Lucent - 800 MHz 2X50W RRH Radios (**REMOVE**) – (3) Ericsson – 4415 B66A Radios (**REPLACE**)

(3) Alcatel Lucent – TD-RRH8X20-25 Radios (**REMOVE**) – (3) Ericsson – 4449 B71+B85 Radios (**REPLACE**)

(3) Alcatel Lucent – PCS 1900MHz 4X45-65MHz Radios (**REMOVE**) – (3) Ericsson – 4424 B25 Radios (**REPLACE**)

Install New:

(3) AIR6449 B41 Antennas

(4) 1 5/8" feedlines

Ground:

Install New:

- (1) SSC 6160 cabinet
- (1) B160 battery cabinet
- (1) BB6648
- (3) BB6630
- (1) PSU 4813 voltage booster
- (1) DUG20
- (1) CSR IXRe router V2

The facility was approved by the City of Waterbury on December 20th, 1999. It was subsequently approved by the Siting Council on April 17th, 2000.

Please accept this letter as notification pursuant to Regulations of Connecticut State Agencies §16-50j-73, for construction that constitutes an exempt modification pursuant to R.C.S.A. § 16-50j-72(b)(2). In accordance with R.C.S.A. § 16-50j-73, a copy of this letter is being sent to The Honorable Neil M. O'Leary, Mayor of the City of Waterbury, as well as Robert Nerney, City Planner for the City of Waterbury.

1. The proposed modifications will not result in an increase in the height of the existing tower.
2. The proposed modifications will not require the extension of the site boundary.
3. The proposed modification will not increase noise levels at the facility by six decibels or more, or to levels that exceed state and local criteria.
4. The operation of the replacement antennas will not increase radio frequency emissions at the facility to a level at or above the Federal Communication Commission safety standard.
5. The proposed modifications will not cause a change or alteration in the physical or environmental characteristics of the site.
6. The existing structure and its foundation can support the proposed loading.

For the foregoing reasons, T-Mobile respectfully submits that the proposed modifications to the above-reference telecommunications facility constitutes an exempt modification under R.C.S.A. § 16-50j-72(b)(2).

Melanie A. Bachman

Page 3

Sincerely,

A handwritten signature in black ink, appearing to read "Richard Zajac". The signature is fluid and cursive, with the first name being more prominent than the last.

Richard Zajac
Site Acquisition Specialist
4545 East River Road, Suite 320
West Henrietta, NY
(585) 445-5896
Richard.zajac@crowncastle.com

cc:

The Honorable Neil M. O'Leary, Mayor
City of Waterbury
City Hall Building
235 Grand Street, 2nd floor
Waterbury, CT 06702
203-574-6712

Robert Nerny, City Planner (*via email only to rnerney@waterburyct.org*)
City of Waterbury
185 South Main Street, 5th floor
(1 Jefferson Square)
Waterbury, CT 06706
203-574-6817

(585) 445-5896

ORIGIN ID: ONHA
RICHARD ZAJAC
CROWN CASTLE
629 KAYLEIGH DR
WEBSTER, NY 14580
UNITED STATES US

SHIP DATE: 16APR21
ACT WGT: 1.00 LB
CAD: 112911364INET4340

BILL SENDER


TO **NEIL M. O'LEARY, MAYOR**

CITY OF WATERBURY
CITY HALL BUILDING

235 GRAND STREET, 2ND FLOOR
WATERBURY CT 06702

REF: 799001 7680
(203) 574-6712
INV/ PO: DEPT:

56D.J3/F9A6/FE4A




TRK# 7734 6536 6141
0201

MON - 19 APR 4:30P
STANDARD OVERNIGHT

XE BNHA

06702
CT-US BDL



After printing this label:

1. Use the 'Print' button on this page to print your label to your laser or inkjet printer.
2. Fold the printed page along the horizontal line.
3. Place label in shipping pouch and affix it to your shipment so that the barcode portion of the label can be read and scanned.

Warning: Use only the printed original label for shipping. Using a photocopy of this label for shipping purposes is fraudulent and could result in additional billing charges, along with the cancellation of your FedEx account number.

Use of this system constitutes your agreement to the service conditions in the current FedEx Service Guide, available on fedex.com. FedEx will not be responsible for any claim in excess of \$100 per package, whether the result of loss, damage, delay, non-delivery, misdelivery, or misinformation, unless you declare a higher value, pay an additional charge, document your actual loss and file a timely claim. Limitations found in the current FedEx Service Guide apply. Your right to recover from FedEx for any loss, including intrinsic value of the package, loss of sales, income interest, profit, attorney's fees, costs, and other forms of damage whether direct, incidental, consequential, or special is limited to the greater of \$100 or the authorized declared value. Recovery cannot exceed actual documented loss. Maximum for items of extraordinary value is \$1,000, e.g. jewelry, precious metals, negotiable instruments and other items listed in our Service Guide. Written claims must be filed within strict time limits, see current FedEx Service Guide.

Zajac, Richard

From: Zajac, Richard
Sent: Friday, April 16, 2021 1:33 PM
To: 'rnerney@waterburyct.org'
Subject: Connecticut Siting Council exempt modification application notification
Attachments: CSC Exempt Modification Application - 670 Captain Neville Dr.pdf

Good afternoon,

Please see the attached application to the Connecticut Siting Council regarding antenna work on the existing cell tower located at 670 Captain Neville Drive in Waterbury.

Should you have any questions/comments/concerns regarding this application, please do not hesitate to contact me.

Thank you,

RICH ZAJAC

Site Acquisition Specialist

T: (585) 445-5896 M: (607) 346-7212

F: (724) 416-4461

CROWN CASTLE

4545 East River Road, Suite 320

West Henrietta, NY 14586

Exhibit A

Original Facility Approval

BUILDING PERMIT

City of Waterbury

No. 9779 C

Location: 670 CAPTAIN MEVILLE DR

Use: CELLAR TOWER

Date: 12-20-99

BUILDING DEPT.
BY:

J. Steven O'Brien

MINIMUM OF THREE CALL INSPECTIONS
REQUIRED FOR ALL CONSTRUCTION
WORK:

1. FOUNDATIONS OR FOOTINGS.
2. PRIOR TO COVERING STRUCTURAL MEMBERS (READY TO LATH).
3. FINAL INSPECTION BEFORE OCCUPANCY.

APPROVED PLANS MUST BE RETAINED ON JOB AND THIS CARD KEPT POSTED UNTIL FINAL INSPECTION HAS BEEN MADE. WHERE A CERTIFICATE OF OCCUPANCY IS REQUIRED, SUCH BUILDING SHALL NOT BE OCCUPIED UNTIL FINAL INSPECTION HAS BEEN MADE.

WHERE APPLICABLE, SEPARATE PERMITS ARE REQUIRED FOR ELECTRICAL, PLUMBING AND MECHANICAL INSTALLATIONS.

POST THIS CARD SO IT IS VISIBLE FROM STREET

BUILDING INSPECTION APPROVALS	PLUMBING INSPECTION APPROVALS	ELECTRICAL INSPECTION APPROVALS
1	1	1
2	2	2
3	HEATING INSPECTION APPROVALS	REFRIGERATION INSPECTION APPROVALS
	1	1
OTHER	2	2

WORK SHALL NOT PROCEED UNTIL THE INSPECTOR HAS APPROVED THE VARIOUS STAGES OF CONSTRUCTION.

PERMIT WILL BECOME NULL AND VOID IF CONSTRUCTION IS NOT STARTED WITHIN SIX MONTHS OF DATE THE PERMIT IS ISSUED AS NOTED ABOVE.

INSPECTIONS INDICATED ON THIS CARD *CA* BE ARRANGED FOR BY TELEPHONE *C* WRITTEN NOTIFICATION.



STATE OF CONNECTICUT
CONNECTICUT SITING COUNCIL

Ten Franklin Square
New Britain, Connecticut 06051
Phone: (860) 827-2935
Fax: (860) 827-2950

April 17, 2000

Peter W. van Wilgen
Director-Real Estate Operations
Springwich Cellular Limited Partnership
500 Enterprise Drive
Rocky Hill, CT 06067

RE: TS-SCLP-151-000330 - Springwich Cellular Limited Partnership request for an order to approve tower sharing at an existing telecommunications facility located at Captain Neville Drive in Waterbury, Connecticut.

Dear Mr. van Wilgen:

At a public meeting held April 12, 2000, the Connecticut Siting Council (Council) ruled that the shared use of this existing tower site is technically, legally, environmentally, and economically feasible and meets public safety concerns, and therefore, in compliance with General Statutes § 16-50aa, the Council has ordered the shared use of this facility to avoid the unnecessary proliferation of tower structures. This facility has also been carefully modeled to ensure that radio frequency emissions are conservatively below State and federal standards applicable to the frequencies now used on this tower.

This decision is under the exclusive jurisdiction of the Council. Any additional change to this facility may require an explicit request to this agency pursuant to General Statutes § 16-50aa or notice pursuant to Regulations of Connecticut State Agencies Section 16-50j-73, as applicable. Such request or notice shall include all relevant information regarding the proposed change with cumulative worst-case modeling of radio frequency exposure at the closest point uncontrolled access to the tower base, consistent with Federal Communications Commission, Office of Engineering and Technology, Bulletin 65. Any deviation from this format may result in the Council implementing enforcement proceedings pursuant to General Statutes § 16-50u including, without limitation, imposition of expenses resulting from such failure and of civil penalties in an amount not less than one thousand dollars per day for each day of construction or operation in material violation.

This decision applies only to this request for tower sharing and is not applicable to any other request or construction.

The proposed shared use is to be implemented as specified in your letter dated March 29, 2000.

Thank you for your attention and cooperation.

Very truly yours,

A handwritten signature in black ink, appearing to read "Mortimer A. Gelston".

Mortimer A. Gelston
Chairman

MAG/RKE/rg

c: Honorable Philip A. Giordano, Mayor, City of Waterbury



500 Enterprise Drive
Rocky Hill, Connecticut 06067-3900
Phone: (860) 513-7730
Fax: (860) 513-7614

Springwich Cellular Limited Partnership

Peter W. van Wilgen
Director - Real Estate Operations

March 29, 2000

RECEIVED

MAR 30 2000

**CONNECTICUT
SITING COUNCIL**

Mr. Mortimer A. Gelston, Chairman
Connecticut Siting Council
10 Franklin Square
New Britain, Connecticut 06051

**Re: Springwich Cellular Limited Partnership Cellular Communications
Site – Captain Neville Drive, Waterbury, Connecticut**

Dear Chairman Gelston:

Springwich Cellular Limited Partnership (SCLP) plans to install cellular antennas and a related equipment building at the facility owned by Candid Communications of Waterbury, LLC (Candid Communications), of 110 Washington Avenue, 4th floor, North Haven, Connecticut 06473. Please accept this letter as our request to share the existing facility pursuant to C.G.S. Section 16-50aa. A copy of this letter is being sent to Philip A. Giordano, the Mayor of the City of Waterbury.

The tower proposed for use by SCLP is being constructed by Candid Communications. Candid Communications has received zoning approval from the City of Waterbury to construct a 150' monopole designed with four platforms for the purpose of tower sharing. SCLP is the first carrier to reach an agreement with the tower owner to use the tower and install radio equipment at the site. The tower will be located on Captain Neville Drive in the City of Waterbury and will be a 152' monopole with coordinates of Latitude 41° 32' 3" Longitude 72° 58' 8". The tower is presently under construction. Upon completion of the tower, SCLP plans to install up to twelve, four foot tall panel-type cellular antennas on the tower at the 150' foot level, as shown on the attached tower profile. SCLP will also install a single story, approximately 12' x 26' equipment building which will contain radio transmission equipment (See attached Site Plan).

Power Density Calculations.

The operation of SCLP's antennas will not increase the total radio frequency electromagnetic radiation power density, measured at the tower base, to a level at or above the ANSI standard. The following table shows the power density at the site from SCLP's proposed use in relation to the standard.

FREQUENCY	POWER DENSITY	HEIGHT	STANDARD LIMITS (mW/cm2)	% OF STANDARD
SNET Wireless 880 - 894	0.0332	150'	0.5867	5.66%
TOTAL	N/A		N/A	5.66%

As the table demonstrates, SCLP's proposed antennas would contribute 5.66% of the ANSI standard for the cellular frequency range as calculated for a single frequency site.

Statutory Considerations. C.G.S. §16-50aa provides that, upon written request for approval of a proposed shared use, "if the Council finds that the proposed shared use of the facility is technically, legally, environmentally and economically feasible and meets public safety concerns, the Council shall issue an order approving such shared use." (C.G.S. §16-50aa(c)(1).

The shared use of the tower satisfied the criteria stated in C.G.S. §16-50aa as follows:

- A. **Technical Feasibility.** The existing tower will be structurally sound and capable of supporting four wireless carriers, including the proposed antennas. The proposed shared use of this tower therefore is technically feasible.
- B. **Legal Feasibility.** Under C.G.S. §16-50aa, the Council has been authorized to issue an order approving the proposed shared use of an existing facility. (C.G.S. §16-50aa(c)(1).) This authority complements the Council's prior-existing authority under C.G.S. §16-50p to issue orders approving the construction of new towers that are subject to the Council's jurisdiction. C.G.S. §16-50x(a) directs the Council to "give such consideration to other state laws and municipal regulations as it shall deem appropriate" on ruling of requests for the shared use of tower facilities. Candid Communications has received local zoning approval for the construction of this tower. (See copy of Building Permit attached.) Under the authority vested in the Council by C.G.S. §16-50aa, order by the Council approving the shared use would permit the applicant to obtain a building permit for the proposed installations.
- C. **Environmental Feasibility.** The proposed shared use would have a minimal environmental effect, for the following reasons:
 - 1. The proposed antenna installation would have an insignificant incremental visual impact, and would not cause any significant change or alteration in the physical or environmental characteristics in or around the tower site. In particular, the proposed installation would not increase the height of the existing tower, and would not extend the boundaries of the tower site.

2. The proposed installation would not increase the noise levels at the existing facility by six decibels or more.
 3. Operations of antennas at this site would not exceed the total radio frequency electromagnetic radiation power density levels adopted by the State of Connecticut and the FCC as shown above. The "worst-case" exposure levels have also been calculated for ground level, which is an uncontrolled environment since it is generally accessible. The power density at ground level is only 5.66 % of both the ANSI and FCC standards for an uncontrolled environment. As such, the facility would be operated in full and complete compliance with the Federal Telecommunications Act of 1996.
 4. The proposed installation would not require any water or sanitary facilities, or general air emissions or discharges to water bodies. After construction is completed (approximately four weeks), the proposed installation would not generate any traffic other than periodic maintenance visits. The proposed use of the facility would therefore have a minimal environmental effect, and is environmentally feasible.
- D. **Economic Feasibility.** As previously stated, SCLP has entered into an agreement with the facility owner to share use of the existing facility on mutually agreed to terms. The proposed facility sharing is therefore economically feasible.
- E. **Public Safety Concerns.** As stated above, the tower is structurally capable of supporting the proposed antennas. The applicant is not aware of any other public safety issues relative to the proposed sharing of the tower. In fact, the provision of new or improved wireless coverage in the area is expected to enhance the safety and welfare of area residents. The public safety benefits of wireless service are further illustrated by the recent decision of local authorities elsewhere in Connecticut and in other parts of the country to provide mobile phones to residents to improve local public safety and enhance emergency communications. The proposed-shared use of this facility would likewise improve public safety in the City of Waterbury.

For the foregoing reasons, SCLP respectfully requests that the Council find the proposed shared use of this facility satisfies the criteria stated in C.G.S. Section 16-50aa and issue an order approving this proposed use.

Sincerely,




cc: Philip A. Giordano, Mayor

Exhibit B

Property Card

Location: 670 CAPT NEVILLE DR Owner: M B REALTY LLC



Property Information:

Map Block Lot:	0450-0490-0070	Acres:	8.88
Primary Use:	Light Industrial	Zone:	IP
Neighborhood:	85000-Industrial Park	Vol/Page:	3298
Mailing Address:	M B REALTY LLC 670 CAPTAIN NEVILLE DR WATERBURY CT 067050000		

Property Values:

	Appraised Value	Assessed Value (70%)
Building	2298424	1608900
Land	477464	334220
OutBuilding	48610	34030
Total	2824498	1977150

Building Information:

Bldg Style:		Living Area:	69700sq.ft
Construction:	Average	Year Built:	1990
Exterior Wall:	Concrete Precast Panel	Stories:	2

Roof Cover:		Heating:	Space Heater
Condition:	Good	Heat Fuel:	Gas
Rooms:	0	Bedrooms:	0
Full Baths:	0	Half Baths:	0
Outbuilding Information:			
Type	Area (sq.ft)	Year Built	Condition
Canopy Canopy	400sq.ft	2001	Average
Concrete Paving	340sq.ft	1996	Average
Concrete Block/Frame Shed	176sq.ft	1996	Average
Asphalt Paving	25452sq.ft	1996	Average
Special Features:			
Feature:	Sprinklers		

[Close](#)



Exhibit C

Construction Drawings

T-Mobile

CALL CONNECTICUT ONE CALL
(800) 922-4455 CBYD.COM
CALL 2 WORKING DAYS
BEFORE YOU DIG!

T-Mobile

35 GRIFFIN ROAD
BLOOMFIELD, CT 06002

CROWN CASTLE

1200 MACARTHUR BLVD, SUITE 200
MAHWAH, NJ 07430



TOWER
ENGINEERING
PROFESSIONALS

326 TRYON RD
RALEIGH, NC 27603
(919) 661-6351

TEP JOB #: 218162.502140

T-MOBILE SITE NUMBER: CTNH452A

T-MOBILE SITE NAME: CTNH452A

SITE TYPE: MONOPOLE

TOWER HEIGHT: 150'-0"

BUSINESS UNIT #: 881534

**SITE ADDRESS: 670 CAPTAIN NEVILLE DRIVE
WATERBURY, CT 06705**

COUNTY: NEW HAVEN

JURISDICTION: CITY OF WATERBURY

T-MOBILE SPRINT-RETAIN SITE CONFIGURATION: 67D5998C_1XAIR-1QP-1OP

SITE INFORMATION


CROWN CASTLE USA INC. WATERBURY TOWER
SITE NAME:
SITE ADDRESS: 670 CAPTAIN NEVILLE DRIVE
WATERBURY, CT 06705
COUNTY: NEW HAVEN
MAP/PARCEL #: 0450-0490-0070
AREA OF CONSTRUCTION: EXISTING
LATITUDE: 41° 32' 03.60" (41.534333)
LONGITUDE: -72° 58' 08.40" (-72.969000)
LAT/LONG TYPE: NAD83
GROUND ELEVATION: 756 FT
CURRENT ZONING: IP
JURISDICTION: CITY OF WATERBURY
OCCUPANCY CLASSIFICATION: U
TYPE OF CONSTRUCTION: IIB
A.D.A. COMPLIANCE: FACILITY IS UNMANNED AND NOT FOR HUMAN HABITATION
PROPERTY OWNER: MB REALTY LLC
670 CAPTAIN NEVILLE DR
WATERBURY, CT 06705
TOWER OWNER: CROWN CASTLE
1200 MACARTHUR BLVD, SUITE 200
MAHWAH, NJ 07430
CARRIER/APPLICANT: T-MOBILE
35 GRIFFIN ROAD
BLOOMFIELD, CT 06002
ELECTRIC PROVIDER: CONNECTICUT LIGHT & POWER CO
(800) 286-2000
TELCO PROVIDER: AT&T
(800) 288-2020

DRAWING INDEX

SHEET #	SHEET DESCRIPTION
T-1	TITLE SHEET
T-2	GENERAL NOTES
C-1.1	SITE PLAN
C-1.2	EXISTING & FINAL EQUIPMENT PLANS
C-2	FINAL ELEVATION & ANTENNA PLANS
C-3	EQUIPMENT DETAILS & COAX COLOR CODING
C-4	EQUIPMENT SPECS
C-5	CABINET SPECS
E-1	AC PANEL SCHEDULES & ONE LINE DIAGRAM
G-1	TYPICAL FINAL GROUNDING SCHEMATIC
G-2	GROUNDING DETAILS
G-3	GROUNDING DETAILS

ALL DRAWINGS CONTAINED HEREIN ARE FORMATTED FOR 22x34. CONTRACTOR SHALL VERIFY ALL PLANS AND EXISTING DIMENSIONS AND CONDITIONS ON THE JOB SITE AND SHALL IMMEDIATELY NOTIFY THE ENGINEER IN WRITING OF ANY DISCREPANCIES BEFORE PROCEEDING WITH THE WORK OR BE RESPONSIBLE FOR SAME.

LOCATION MAP



APPLICABLE CODES/REFERENCE DOCUMENTS

ALL WORK SHALL BE PERFORMED AND MATERIALS INSTALLED IN ACCORDANCE WITH THE CURRENT EDITIONS OF THE FOLLOWING CODES AS ADOPTED BY THE LOCAL GOVERNING AUTHORITIES. NOTHING IN THESE PLANS IS TO BE CONSTRUED TO PERMIT WORK NOT CONFORMING TO THESE CODES:

CODE TYPE	CODE
BUILDING	2018 CONNECTICUT STATE BUILDING CODE
MECHANICAL	2015 INTERNATIONAL MECHANICAL CODE
ELECTRICAL	2017 NEC

REFERENCE DOCUMENTS:
STRUCTURAL ANALYSIS: TOWER ENGINEERING PROFESSIONALS
DATED: 02/12/2021
MOUNT ANALYSIS: INFINIGY ENGINEERING, PLLC
DATED: 01/31/2021
ORDER ID: 538784 RFDS REVISION: 1
REVISION: 0 DATED: 01/11/2021

ANALYSIS CRITERIA:
APPLICABLE CODES: TIA-222-H / ASCE 7-16
WIND SPEED: V = 125 MPH (ULTIMATE 3 SECOND GUST)
EXPOSURE CATEGORY: C
RISK CATEGORY: II
TOPOGRAPHIC CATEGORY: 1
SEISMIC Ss: 0.187
SEISMIC S1: 0.064
SERVICE WIND SPEED: 60 MPH

APPROVALS

APPROVAL	SIGNATURE	DATE
RF	_____	_____
CONST.	_____	_____
FAA	_____	_____
OPS	_____	_____
RE	_____	_____
SR DEV MGR	_____	_____
REG DIR	_____	_____

THE PARTIES ABOVE HEREBY APPROVE AND ACCEPT THESE DOCUMENTS AND AUTHORIZE THE CONTRACTOR TO PROCEED WITH THE CONSTRUCTION DESCRIBED HEREIN. ALL CONSTRUCTION DOCUMENTS ARE SUBJECT TO REVIEW BY THE LOCAL BUILDING DEPARTMENT AND ANY CHANGES AND MODIFICATIONS THEY MAY IMPOSE.

PROJECT TEAM

A&E FIRM: TOWER ENGINEERING PROFESSIONALS
326 TRYON ROAD
RALEIGH, NC 27603
JOSEPH T. CRESS - PROJECT MANAGER
(919) 661-6351
GRAHAM M. ANDRES - CIVIL ENGINEER
(919) 661-6351
GRAHAM M. ANDRES - ELECTRICAL ENGINEER
(919) 661-6351
CROWN CASTLE USA INC. DISTRICT CONTACTS:
1500 CORPORATE DRIVE
CANONSBURG, PA 15317
NITSA CRENSHAW - A&E SPECIALIST
(212) 365-4734

PROJECT DESCRIPTION

THE PURPOSE OF THIS PROJECT IS TO ENHANCE BROADBAND CONNECTIVITY AND CAPACITY TO THE EXISTING ELIGIBLE WIRELESS FACILITY.

TOWER SCOPE OF WORK:
• REMOVE (6) ANTENNAS
• REMOVE (9) RRHs
• REMOVE (4) CABLES
• RELOCATE (1) MICROWAVE ANTENNA & (1) ODU
• REUSE (1) PLATFORM MOUNT W/ HANDRAIL
• REUSE (3) MICROWAVE DISHES & (2) ODU'S
• INSTALL (9) ANTENNAS
• INSTALL (9) RRHs
• INSTALL (4) HCS 6/24 4AWG 100M (1-5/8")
• INSTALL (6) BACK-TO-BACK RRH MOUNTS

GROUND SCOPE OF WORK:
• REMOVE SPRINT CABINET(S), AS NEEDED
• INSTALL (2) CABINETS
• INSTALL (3) BB 6630, (1) BB 6648, (1) DUG20, (1) CSR IXRE VE (GEN2) & (1) PSU 4813 BOOSTER
• REUSE EXISTING SPRINT PADS, ICE BRIDGE & UTILITY EQUIPMENT

T-MOBILE SITE NUMBER:
CTNH452A

BU #: 881534
WATERBURY TOWER

670 CAPTAIN NEVILLE DRIVE
WATERBURY, CT 06705

EXISTING 150'-0"
MONOPOLE

ISSUED FOR:

REV	DATE	DRWN	DESCRIPTION	DES/QA
A	03/01/21	ER	PRELIMINARY	JTC
B	03/16/21	BSE	PRELIMINARY	JTC
0	03/26/21	JW	CONSTRUCTION	JTC

SEAL:



03/26/21

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SHEET NUMBER:

T-1

REVISION:

0

CROWN CASTLE USA INC. SITE ACTIVITY REQUIREMENTS:

- 1. NOTICE TO PROCEED- NO WORK SHALL COMMENCE PRIOR TO CROWN CASTLE USA INC. WRITTEN NOTICE TO PROCEED (NTP) AND THE ISSUANCE OF A PURCHASE ORDER. PRIOR TO ACCESSING/ENTERING THE SITE YOU MUST CONTACT THE CROWN CASTLE USA INC. NOC AT 800-788-7011 & THE CROWN CASTLE USA INC. CONSTRUCTION MANAGER.
2. "LOOK UP" - CROWN CASTLE USA INC. SAFETY CLIMB REQUIREMENT: THE INTEGRITY OF THE SAFETY CLIMB AND ALL COMPONENTS OF THE CLIMBING FACILITY SHALL BE CONSIDERED DURING ALL STAGES OF DESIGN, INSTALLATION, AND INSPECTION. TOWER MODIFICATION, MOUNT REINFORCEMENTS, AND/OR EQUIPMENT INSTALLATIONS SHALL NOT COMPROMISE THE INTEGRITY OR FUNCTIONAL USE OF THE SAFETY CLIMB OR ANY COMPONENTS OF THE CLIMBING FACILITY ON THE STRUCTURE. THIS SHALL INCLUDE, BUT NOT BE LIMITED TO: PINCHING OF THE WIRE ROPE, BENDING OF THE WIRE ROPE FROM ITS SUPPORTS, DIRECT CONTACT OR CLOSE PROXIMITY TO THE WIRE ROPE WHICH MAY CAUSE FRICTIONAL WEAR, IMPACT TO THE ANCHORAGE POINTS IN ANY WAY, OR TO IMPEDE/BLOCK ITS INTENDED USE. ANY COMPROMISED SAFETY CLIMB, INCLUDING EXISTING CONDITIONS MUST BE TAGGED OUT AND REPORTED TO YOUR CROWN CASTLE USA INC. POC OR CALL THE NOC TO GENERATE A SAFETY CLIMB MAINTENANCE AND CONTRACTOR NOTICE TICKET.
3. PRIOR TO THE START OF CONSTRUCTION, ALL REQUIRED JURISDICTIONAL PERMITS SHALL BE OBTAINED. THIS INCLUDES, BUT IS NOT LIMITED TO, BUILDING, ELECTRICAL, MECHANICAL, FIRE, FLOOD ZONE, ENVIRONMENTAL, AND ZONING. AFTER ONSITE ACTIVITIES AND CONSTRUCTION ARE COMPLETED, ALL REQUIRED PERMITS SHALL BE SATISFIED AND CLOSED OUT ACCORDING TO LOCAL JURISDICTIONAL REQUIREMENTS.
4. ALL CONSTRUCTION MEANS AND METHODS; INCLUDING BUT NOT LIMITED TO, ERECTION PLANS, RIGGING PLANS, CLIMBING PLANS, AND RESCUE PLANS SHALL BE THE RESPONSIBILITY OF THE GENERAL CONTRACTOR RESPONSIBLE FOR THE EXECUTION OF THE WORK CONTAINED HEREIN, AND SHALL MEET ANSI/ASSE A10.48 (LATEST EDITION); FEDERAL, STATE, AND LOCAL REGULATIONS; AND ANY APPLICABLE INDUSTRY CONSENSUS STANDARDS RELATED TO THE CONSTRUCTION ACTIVITIES BEING PERFORMED. ALL RIGGING PLANS SHALL ADHERE TO ANSI/ASSE A10.48 (LATEST EDITION) AND CROWN CASTLE USA INC. STANDARD CED-STD-10253, INCLUDING THE REQUIRED INVOLVEMENT OF A QUALIFIED ENGINEER FOR CLASS IV CONSTRUCTION, TO CERTIFY THE SUPPORTING STRUCTURE(S) IN ACCORDANCE WITH ANSI/TIA-322 (LATEST EDITION).
5. ALL SITE WORK TO COMPLY WITH QAS-STD-10068 "INSTALLATION STANDARDS FOR CONSTRUCTION ACTIVITIES ON CROWN CASTLE USA INC. TOWER SITE," CED-STD-10294 "STANDARD FOR INSTALLATION OF MOUNTS AND APPURTENANCES," AND LATEST VERSION OF ANSI/TIA-1019-A-2012 "STANDARD FOR INSTALLATION, ALTERATION, AND MAINTENANCE OF ANTENNA SUPPORTING STRUCTURES AND ANTENNAS." IF THE SPECIFIED EQUIPMENT CAN NOT BE INSTALLED AS SHOWN ON THESE DRAWINGS, THE CONTRACTOR SHALL PROPOSE AN ALTERNATIVE INSTALLATION FOR APPROVAL BY CROWN CASTLE USA INC. PRIOR TO PROCEEDING WITH ANY SUCH CHANGE OF INSTALLATION.
7. ALL MATERIALS FURNISHED AND INSTALLED SHALL BE IN STRICT ACCORDANCE WITH ALL APPLICABLE CODES, REGULATIONS AND ORDINANCES. CONTRACTOR SHALL ISSUE ALL APPROPRIATE NOTICES AND COMPLY WITH ALL LAWS, ORDINANCES, RULES, REGULATIONS AND LAWFUL ORDERS OF ANY PUBLIC AUTHORITY REGARDING THE PERFORMANCE OF THE WORK. ALL WORK CARRIED OUT SHALL COMPLY WITH ALL APPLICABLE MUNICIPAL AND UTILITY COMPANY SPECIFICATIONS AND LOCAL JURISDICTIONAL CODES, ORDINANCES AND APPLICABLE REGULATIONS.
8. THE CONTRACTOR SHALL INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS UNLESS SPECIFICALLY STATED OTHERWISE.
9. THE CONTRACTOR SHALL CONTACT UTILITY LOCATING SERVICES PRIOR TO THE START OF CONSTRUCTION.
10. ALL EXISTING ACTIVE SEWER, WATER, GAS, ELECTRIC AND OTHER UTILITIES WHERE ENCOUNTERED IN THE WORK, SHALL BE PROTECTED AT ALL TIMES AND WHERE REQUIRED FOR THE PROPER EXECUTION OF THE WORK, SHALL BE RELOCATED AS DIRECTED BY CONTRACTOR. EXTREME CAUTION SHOULD BE USED BY THE CONTRACTOR WHEN EXCAVATING OR DRILLING PIERS AROUND OR NEAR UTILITIES. CONTRACTOR SHALL PROVIDE SAFETY TRAINING FOR THE WORKING CREW. THIS WILL INCLUDE BUT NOT BE LIMITED TO A) FALL PROTECTION B) CONFINED SPACE C) ELECTRICAL SAFETY D) TRENCHING AND EXCAVATION E) CONSTRUCTION SAFETY PROCEDURES.
11. ALL SITE WORK SHALL BE AS INDICATED ON THE STAMPED CONSTRUCTION DRAWINGS AND PROJECT SPECIFICATIONS. LATEST APPROVED REVISION.
12. CONTRACTOR SHALL KEEP THE SITE FREE FROM ACCUMULATING WASTE MATERIAL, DEBRIS, AND TRASH AT THE COMPLETION OF THE WORK. IF NECESSARY, RUBBISH, STUMPS, DEBRIS, STICKS, STONES AND OTHER REFUSE SHALL BE REMOVED FROM THE SITE AND DISPOSED OF LEGALLY.
13. ALL EXISTING INACTIVE SEWER, WATER, GAS, ELECTRIC AND OTHER UTILITIES, WHICH INTERFERE WITH THE EXECUTION OF THE WORK, SHALL BE REMOVED AND/OR CAPPED, PLUGGED OR OTHERWISE DISCONTINUED AT POINTS WHICH WILL NOT INTERFERE WITH THE EXECUTION OF THE WORK, SUBJECT TO THE APPROVAL OF CONTRACTOR, TOWER OWNER, CROWN CASTLE USA INC., AND/OR LOCAL UTILITIES.
14. THE CONTRACTOR SHALL PROVIDE SITE SIGNAGE IN ACCORDANCE WITH THE TECHNICAL SPECIFICATION FOR SITE SIGNAGE REQUIRED BY LOCAL JURISDICTION AND SIGNAGE REQUIRED ON INDIVIDUAL PIECES OF EQUIPMENT, ROOMS, AND SHELTERS.
15. THE SITE SHALL BE GRADED TO CAUSE SURFACE WATER TO FLOW AWAY FROM THE CARRIER'S EQUIPMENT AND TOWER AREAS.
16. THE SUB GRADE SHALL BE COMPACTED AND BROUGHT TO A SMOOTH UNIFORM GRADE PRIOR TO FINISHED SURFACE APPLICATION.
17. THE AREAS OF THE OWNERS PROPERTY DISTURBED BY THE WORK AND NOT COVERED BY THE TOWER, EQUIPMENT OR DRIVEWAY, SHALL BE GRADED TO A UNIFORM SLOPE, AND STABILIZED TO PREVENT EROSION AS SPECIFIED ON THE CONSTRUCTION DRAWINGS AND/OR PROJECT SPECIFICATIONS.
18. CONTRACTOR SHALL MINIMIZE DISTURBANCE TO EXISTING SITE DURING CONSTRUCTION. EROSION CONTROL MEASURES, IF REQUIRED DURING CONSTRUCTION, SHALL BE IN CONFORMANCE WITH THE LOCAL GUIDELINES FOR EROSION AND SEDIMENT CONTROL.
19. THE CONTRACTOR SHALL PROTECT EXISTING IMPROVEMENTS, PAVEMENTS, CURBS, LANDSCAPING AND STRUCTURES. ANY DAMAGED PART SHALL BE REPAIRED AT CONTRACTOR'S EXPENSE TO THE SATISFACTION OF OWNER.
20. CONTRACTOR SHALL LEGALLY AND PROPERLY DISPOSE OF ALL SCRAP MATERIALS SUCH AS COAXIAL CABLES AND OTHER ITEMS REMOVED FROM THE EXISTING FACILITY. ANTENNAS REMOVED SHALL BE RETURNED TO THE OWNER'S DESIGNATED LOCATION.
21. CONTRACTOR SHALL LEAVE PREMISES IN CLEAN CONDITION. TRASH AND DEBRIS SHOULD BE REMOVED FROM SITE ON A DAILY BASIS.
22. NO FILL OR EMBANKMENT MATERIAL SHALL BE PLACED ON FROZEN GROUND. FROZEN MATERIALS, SNOW OR ICE SHALL NOT BE PLACED IN ANY FILL OR EMBANKMENT.

GREENFIELD GROUNDING NOTES:

- 1. ALL GROUND ELECTRODE SYSTEMS (INCLUDING TELECOMMUNICATION, RADIO, LIGHTNING PROTECTION AND AC POWER GES'S) SHALL BE BONDED TOGETHER AT OR BELOW GRADE, BY TWO OR MORE COPPER BONDING CONDUCTORS IN ACCORDANCE WITH THE NEC.
2. THE CONTRACTOR SHALL PERFORM IEEE FALL-OFF-POTENTIAL RESISTANCE TO EARTH TESTING (PER IEEE 1100 AND 81) FOR GROUND ELECTRODE SYSTEMS, THE CONTRACTOR SHALL FURNISH AND INSTALL SUPPLEMENTAL GROUND ELECTRODES AS NEEDED TO ACHIEVE A TEST RESULT OF 5 OHMS OR LESS.
3. THE CONTRACTOR IS RESPONSIBLE FOR PROPERLY SEQUENCING GROUNDING AND UNDERGROUND CONDUIT INSTALLATION AS TO PREVENT ANY LOSS OF CONTINUITY IN THE GROUNDING SYSTEM OR DAMAGE TO THE CONDUIT AND PROVIDE TESTING RESULTS.
4. METAL CONDUIT AND TRAY SHALL BE GROUNDED AND MADE ELECTRICALLY CONTINUOUS WITH LISTED BONDING FITTINGS OR BY BONDING ACROSS THE DISCONTINUITY WITH #6 COPPER WIRE UL APPROVED GROUNDING TYPE CONDUIT CLAMPS.
5. METAL RACEWAY SHALL NOT BE USED AS THE NEC REQUIRED EQUIPMENT GROUND CONDUCTOR. STRANDED COPPER CONDUCTORS WITH GREEN INSULATION, SIZED IN ACCORDANCE WITH THE NEC, SHALL BE FURNISHED AND INSTALLED WITH THE POWER CIRCUITS TO BTS EQUIPMENT.
6. EACH CABINET FRAME SHALL BE DIRECTLY CONNECTED TO THE MASTER GROUND BAR WITH GREEN INSULATED SUPPLEMENTAL EQUIPMENT GROUND WIRES, #6 STRANDED COPPER OR LARGER FOR INDOOR BTS; #2 BARE SOLID TINNED COPPER FOR OUTDOOR BTS.
7. CONNECTIONS TO THE GROUND BUS SHALL NOT BE DOUBLED UP OR STACKED BACK TO BACK CONNECTIONS ON OPPOSITE SIDE OF THE GROUND BUS ARE PERMITTED.
8. ALL EXTERIOR GROUND CONDUCTORS BETWEEN EQUIPMENT/GROUND BARS AND THE GROUND RING SHALL BE #2 SOLID TINNED COPPER UNLESS OTHERWISE INDICATED.
9. ALUMINUM CONDUCTOR OR COPPER CLAD STEEL CONDUCTOR SHALL NOT BE USED FOR GROUNDING CONNECTIONS.
10. USE OF 90° BENDS IN THE PROTECTION GROUNDING CONDUCTORS SHALL BE AVOIDED WHEN 45° BENDS CAN BE ADEQUATELY SUPPORTED.
11. EXOTHERMIC WELDS SHALL BE USED FOR ALL GROUNDING CONNECTIONS BELOW GRADE.
12. ALL GROUND CONNECTIONS ABOVE GRADE (INTERIOR AND EXTERIOR) SHALL BE FORMED USING HIGH PRESS CRIMPS.
13. COMPRESSION GROUND CONNECTIONS MAY BE REPLACED BY EXOTHERMIC WELD CONNECTIONS.
14. ICE BRIDGE BONDING CONDUCTORS SHALL BE EXOTHERMICALLY BONDED OR BOLTED TO THE BRIDGE AND THE TOWER GROUND BAR.
15. APPROVED ANTI-OXIDANT COATINGS (I.E. CONDUCTIVE GEL OR PASTE) SHALL BE USED ON ALL COMPRESSION AND BOLTED GROUND CONNECTIONS.
16. ALL EXTERIOR GROUND CONNECTIONS SHALL BE COATED WITH A CORROSION RESISTANT MATERIAL.
17. MISCELLANEOUS ELECTRICAL AND NON-ELECTRICAL METAL BOXES, FRAMES AND SUPPORTS SHALL BE BONDED TO THE GROUND RING, IN ACCORDANCE WITH THE NEC.
18. BOND ALL METALLIC OBJECTS WITHIN 6 FT. OF MAIN GROUND RING WITH (1) #2 BARE SOLID TINNED COPPER GROUND CONDUCTOR.
19. GROUND CONDUCTORS USED FOR THE FACILITY GROUNDING AND LIGHTNING PROTECTION SYSTEMS SHALL NOT BE ROUTED THROUGH METALLIC OBJECTS THAT FORM A RING AROUND THE CONDUCTOR, SUCH AS METALLIC CONDUITS, METAL SUPPORT CLIPS OR SLEEVES THROUGH WALLS OR FLOORS. WHEN IT IS REQUIRED TO BE HOUSED IN CONDUIT TO MEET CODE REQUIREMENTS OR LOCAL CONDITIONS, NON-METALLIC MATERIAL SUCH AS PVC CONDUIT SHALL BE USED. WHERE USE OF METAL CONDUIT IS UNAVOIDABLE (I.E., NONMETALLIC CONDUIT PROHIBITED BY LOCAL CODE) THE GROUND CONDUCTOR SHALL BE BONDED TO EACH END OF THE METAL CONDUIT.
20. ALL GROUNDS THAT TRANSITION FROM BELOW GRADE TO ABOVE GRADE MUST BE #2 BARE SOLID TINNED COPPER IN 3/4" NON-METALLIC, FLEXIBLE CONDUIT FROM 24" BELOW GRADE TO WITHIN 3" TO 6" OF CAD-WELD TERMINATION POINT. THE EXPOSED END OF THE CONDUIT MUST BE SEALED WITH SILICONE CAULK. (ADD TRANSITIONING GROUND STANDARD DETAIL AS WELL).
21. BUILDINGS WHERE THE MAIN GROUNDING CONDUCTORS ARE REQUIRED TO BE ROUTED TO GRADE, THE CONTRACTOR SHALL ROUTE TWO GROUNDING CONDUCTORS FROM THE ROOFTOP, TOWERS, AND WATER TOWERS GROUNDING RING, TO THE EXISTING GROUNDING SYSTEM, THE GROUNDING CONDUCTORS SHALL NOT BE SMALLER THAN 2/O COPPER. ROOFTOP GROUNDING RING SHALL BE BONDED TO THE EXISTING GROUNDING SYSTEM, THE BUILDING STEEL COLUMNS, LIGHTNING PROTECTION SYSTEM, AND BUILDING MAIN WATER LINE (FERROUS OR NONFERROUS METAL PIPING ONLY).

GENERAL NOTES:

- 1. FOR THE PURPOSE OF CONSTRUCTION DRAWING, THE FOLLOWING DEFINITIONS SHALL APPLY: CONTRACTOR: GENERAL CONTRACTOR RESPONSIBLE FOR CONSTRUCTION CARRIER: T-MOBILE TOWER OWNER: CROWN CASTLE USA INC.
2. THESE DRAWINGS HAVE BEEN PREPARED USING STANDARDS OF PROFESSIONAL CARE AND COMPLETENESS NORMALLY EXERCISED UNDER SIMILAR CIRCUMSTANCES BY REPUTABLE ENGINEERS IN THIS OR SIMILAR LOCALITIES. IT IS ASSUMED THAT THE WORK DEPICTED WILL BE PERFORMED BY AN EXPERIENCED CONTRACTOR AND/OR WORKPEOPLE WHO HAVE A WORKING KNOWLEDGE OF THE APPLICABLE CODE STANDARDS AND REQUIREMENTS AND OF INDUSTRY ACCEPTED STANDARD GOOD PRACTICE. AS NOT EVERY CONDITION OR ELEMENT IS (OR CAN BE) EXPLICITLY SHOWN ON THESE DRAWINGS, THE CONTRACTOR SHALL USE INDUSTRY ACCEPTED STANDARD GOOD PRACTICE FOR MISCELLANEOUS WORK NOT EXPLICITLY SHOWN.
3. THESE DRAWINGS REPRESENT THE FINISHED STRUCTURE. THEY DO NOT INDICATE THE MEANS OR METHODS OF CONSTRUCTION. THE CONTRACTOR SHALL BE SOLELY RESPONSIBLE FOR THE CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES, AND PROCEDURES. THE CONTRACTOR SHALL PROVIDE ALL MEASURES NECESSARY FOR PROTECTION OF LIFE AND PROPERTY DURING CONSTRUCTION. SUCH MEASURES SHALL INCLUDE, BUT NOT BE LIMITED TO, BRACING, FORMWORK, SHORING, ETC. SITE VISITS BY THE ENGINEER OR HIS REPRESENTATIVE WILL NOT INCLUDE INSPECTION OF THESE ITEMS AND IS FOR STRUCTURAL OBSERVATION OF THE FINISHED STRUCTURE ONLY. NOTES AND DETAILS IN THE CONSTRUCTION DRAWINGS SHALL TAKE PRECEDENCE OVER GENERAL NOTES AND TYPICAL DETAILS. WHERE NO DETAILS ARE SHOWN, CONSTRUCTION SHALL CONFORM TO SIMILAR WORK ON THE PROJECT, AND/OR AS PROVIDED FOR IN THE CONTRACT DOCUMENTS. WHERE DISCREPANCIES OCCUR BETWEEN PLANS, DETAILS, GENERAL NOTES, AND SPECIFICATIONS, THE GREATER, MORE STRICT REQUIREMENTS, SHALL GOVERN. IF FURTHER CLARIFICATION IS REQUIRED CONTACT THE ENGINEER OF RECORD.
5. SUBSTANTIAL EFFORT HAS BEEN MADE TO PROVIDE ACCURATE DIMENSIONS AND MEASUREMENTS ON THE DRAWINGS TO ASSIST IN THE FABRICATION AND/OR PLACEMENT OF CONSTRUCTION ELEMENTS BUT IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO FIELD VERIFY THE DIMENSIONS, MEASUREMENTS, AND/OR CLEARANCES SHOWN IN THE CONSTRUCTION DRAWINGS PRIOR TO FABRICATION OR CUTTING OF ANY NEW OR EXISTING CONSTRUCTION ELEMENTS. IF IT IS DETERMINED THAT THERE ARE DISCREPANCIES AND/OR CONFLICTS WITH THE CONSTRUCTION DRAWINGS THE ENGINEER OF RECORD IS TO BE NOTIFIED AS SOON AS POSSIBLE.
6. PRIOR TO THE SUBMISSION OF BIDS, THE BIDDING CONTRACTOR SHALL VISIT THE CELL SITE TO FAMILIARIZE WITH THE EXISTING CONDITIONS AND TO CONFIRM THAT THE WORK CAN BE ACCOMPLISHED AS SHOWN ON THE CONSTRUCTION DRAWINGS. ANY DISCREPANCY FOUND SHALL BE BROUGHT TO THE ATTENTION OF CROWN CASTLE.
7. ALL MATERIALS FURNISHED AND INSTALLED SHALL BE IN STRICT ACCORDANCE WITH ALL APPLICABLE CODES, REGULATIONS AND ORDINANCES. CONTRACTOR SHALL ISSUE ALL APPROPRIATE NOTICES AND COMPLY WITH ALL LAWS, ORDINANCES, RULES, REGULATIONS AND LAWFUL ORDERS OF ANY PUBLIC AUTHORITY REGARDING THE PERFORMANCE OF THE WORK. ALL WORK CARRIED OUT SHALL COMPLY WITH ALL APPLICABLE MUNICIPAL AND UTILITY COMPANY SPECIFICATIONS AND LOCAL JURISDICTIONAL CODES, ORDINANCES AND APPLICABLE REGULATIONS.
8. UNLESS NOTED OTHERWISE, THE WORK SHALL INCLUDE FURNISHING MATERIALS, EQUIPMENT, APPURTENANCES AND LABOR NECESSARY TO COMPLETE ALL INSTALLATIONS AS INDICATED ON THE DRAWINGS.
9. THE CONTRACTOR SHALL INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS UNLESS SPECIFICALLY STATED OTHERWISE.
10. IF THE SPECIFIED EQUIPMENT CAN NOT BE INSTALLED AS SHOWN ON THESE DRAWINGS, THE CONTRACTOR SHALL PROPOSE AN ALTERNATIVE INSTALLATION FOR APPROVAL BY THE CARRIER AND CROWN CASTLE PRIOR TO PROCEEDING WITH ANY SUCH CHANGE OF INSTALLATION.
11. CONTRACTOR IS TO PERFORM A SITE INVESTIGATION AND IS TO DETERMINE THE BEST ROUTING OF ALL CONDUITS FOR POWER, AND TELCO AND FOR GROUNDING CABLES AS SHOWN IN THE POWER, TELCO, AND GROUNDING PLAN DRAWINGS.
12. THE CONTRACTOR SHALL PROTECT EXISTING IMPROVEMENTS, PAVEMENTS, CURBS, LANDSCAPING AND STRUCTURES. ANY DAMAGED PART SHALL BE REPAIRED AT CONTRACTOR'S EXPENSE TO THE SATISFACTION OF CROWN CASTLE USA INC. CONTRACTOR SHALL LEGALLY AND PROPERLY DISPOSE OF ALL SCRAP MATERIALS SUCH AS COAXIAL CABLES AND OTHER ITEMS REMOVED FROM THE EXISTING FACILITY. ANTENNAS REMOVED SHALL BE RETURNED TO THE OWNER'S DESIGNATED LOCATION.
14. CONTRACTOR SHALL LEAVE PREMISES IN CLEAN CONDITION. TRASH AND DEBRIS SHOULD BE REMOVED FROM SITE ON A DAILY BASIS.

CONCRETE, FOUNDATIONS, AND REINFORCING STEEL:

- 1. ALL CONCRETE WORK SHALL BE IN ACCORDANCE WITH THE ACI 301, ACI 318, ACI 336, ASTM A184, ASTM A185 AND THE DESIGN AND CONSTRUCTION SPECIFICATION FOR CAST-IN-PLACE CONCRETE.
2. UNLESS NOTED OTHERWISE, SOIL BEARING PRESSURE USED FOR DESIGN OF SLABS AND FOUNDATIONS IS ASSUMED TO BE 1000 psf.
3. ALL CONCRETE SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH (f'c) OF 3000 psi AT 28 DAYS, UNLESS NOTED OTHERWISE. NO MORE THAN 90 MINUTES SHALL ELAPSE FROM BATCH TIME TO TIME OF PLACEMENT UNLESS APPROVED BY THE ENGINEER OF RECORD. TEMPERATURE OF CONCRETE SHALL NOT EXCEED 90°F AT TIME OF PLACEMENT.
4. CONCRETE EXPOSED TO FREEZE-THAW CYCLES SHALL CONTAIN AIR ENTRAINING ADMIXTURES. AMOUNT OF AIR ENTRAINMENT TO BE BASED ON SIZE OF AGGREGATE AND F3 CLASS EXPOSURE (VERY SEVERE). CEMENT USED TO BE TYPE II PORTLAND CEMENT WITH A MAXIMUM WATER-TO-CEMENT RATIO (W/C) OF 0.45.
5. ALL STEEL REINFORCING SHALL CONFORM TO ASTM A615. ALL WELDED WIRE FABRIC (WWF) SHALL CONFORM TO ASTM A185. ALL SPLICES SHALL BE CLASS "B" TENSION SPLICES, UNLESS NOTED OTHERWISE. ALL HOOKS SHALL BE STANDARD 90 DEGREE HOOKS, UNLESS NOTED OTHERWISE. YIELD STRENGTH (Fy) OF STANDARD DEFORMED BARS ARE AS FOLLOWS: #4 BARS AND SMALLER.....40 ksi #5 BARS AND LARGER.....60 ksi
6. THE FOLLOWING MINIMUM CONCRETE COVER SHALL BE PROVIDED FOR REINFORCING STEEL UNLESS SHOWN OTHERWISE ON DRAWINGS: CONCRETE CAST AGAINST AND PERMANENTLY EXPOSED TO EARTH.....3" CONCRETE EXPOSED TO EARTH OR WEATHER: #6 BARS AND LARGER.....2" #5 BARS AND SMALLER.....1-1/2" CONCRETE NOT EXPOSED TO EARTH OR WEATHER: SLAB AND WALLS.....3/4" BEAMS AND COLUMNS.....1-1/2"
7. A TOOLED EDGE OR A 3/4" CHAMFER SHALL BE PROVIDED AT ALL EXPOSED EDGES OF CONCRETE, UNLESS NOTED OTHERWISE, IN ACCORDANCE WITH ACI 301 SECTION 4.2.4.

ELECTRICAL INSTALLATION NOTES:

- 1. ALL ELECTRICAL WORK SHALL BE PERFORMED IN ACCORDANCE WITH THE PROJECT SPECIFICATIONS, NEC AND ALL APPLICABLE FEDERAL, STATE, AND LOCAL CODES/ORDINANCES.
2. CONDUIT ROUTINGS ARE SCHEMATIC. CONTRACTOR SHALL INSTALL CONDUITS SO THAT ACCESS TO EQUIPMENT IS NOT BLOCKED AND TRIP HAZARDS ARE ELIMINATED.
3. WIRING, RACEWAY AND SUPPORT METHODS AND MATERIALS SHALL COMPLY WITH THE REQUIREMENTS OF THE NEC.
4. ALL CIRCUITS SHALL BE SEGREGATED AND MAINTAIN MINIMUM CABLE SEPARATION AS REQUIRED BY THE NEC.
4.1. ALL EQUIPMENT SHALL BEAR THE UNDERWRITERS LABORATORIES LABEL OF APPROVAL, AND SHALL CONFORM TO REQUIREMENT OF THE NATIONAL ELECTRICAL CODE.
4.2. ALL OVERCURRENT DEVICES SHALL HAVE AN INTERRUPTING CURRENT RATING THAT SHALL BE GREATER THAN THE SHORT CIRCUIT CURRENT TO WHICH THEY ARE SUBJECTED, 22,000 AIC MINIMUM. VERIFY AVAILABLE SHORT CIRCUIT CURRENT DOES NOT EXCEED THE RATING OF ELECTRICAL EQUIPMENT IN ACCORDANCE WITH ARTICLE 110.24 NEC OR THE MOST CURRENT ADOPTED CODE PRE THE GOVERNING JURISDICTION.
5. EACH END OF EVERY POWER PHASE CONDUCTOR, GROUNDING CONDUCTOR, AND TELCO CONDUCTOR OR CABLE SHALL BE LABELED WITH COLOR-CODED INSULATION OR ELECTRICAL TAPE (3M BRAND, 1/2" PLASTIC ELECTRICAL TAPE WITH UV PROTECTION, OR EQUAL). THE IDENTIFICATION METHOD SHALL CONFORM WITH NEC AND OSHA.
6. ALL ELECTRICAL COMPONENTS SHALL BE CLEARLY LABELED WITH LAMICOID TAGS SHOWING THEIR RATED VOLTAGE, PHASE CONFIGURATION, WIRE CONFIGURATION, POWER OR AMPACITY RATING AND BRANCH CIRCUIT ID NUMBERS (I.E. PANEL BOARD AND CIRCUIT ID'S).
7. PANEL BOARDS (ID NUMBERS) SHALL BE CLEARLY LABELED WITH PLASTIC LABELS.
8. ALL TIE WRAPS SHALL BE CUT FLUSH WITH APPROVED CUTTING TOOL TO REMOVE SHARP EDGES.
9. ALL POWER AND EQUIPMENT GROUND WIRING IN TUBING OR CONDUIT SHALL BE SINGLE COPPER CONDUCTOR (#14 OR LARGER) WITH TYPE THW, THN, THWN-2, XHHW, XHHW-2, THW, THW-2, RHW, OR RHW-2 INSULATION UNLESS OTHERWISE SPECIFIED.
10. SUPPLEMENTAL EQUIPMENT GROUND WIRING LOCATED INDOORS SHALL BE SINGLE COPPER CONDUCTOR (#6 OR LARGER) WITH TYPE THW, THWN, THWN-2, XHHW, XHHW-2, THW, THW-2, RHW, OR RHW-2 INSULATION UNLESS OTHERWISE SPECIFIED.
11. POWER AND CONTROL WIRING IN FLEXIBLE CORD SHALL BE MULTI-CONDUCTOR, TYPE SOOW CORD (#14 OR LARGER) UNLESS OTHERWISE SPECIFIED.
12. POWER AND CONTROL WIRING FOR USE IN CABLE TRAY SHALL BE MULTI-CONDUCTOR, TYPE TC CABLE (#14 OR LARGER), WITH TYPE THW, THWN, THWN-2, XHHW, XHHW-2, THW, THW-2, RHW, OR RHW-2 INSULATION UNLESS OTHERWISE SPECIFIED.
13. ALL POWER AND GROUNDING CONNECTIONS SHALL BE CRIMP-STYLE, COMPRESSION WIRE LUGS AND WIRE NUTS BY THOMAS AND BETTS (OR EQUAL). LUGS AND WIRE NUTS SHALL BE RATED FOR OPERATION NOT LESS THAN 75° C (90° C IF AVAILABLE).
14. RACEWAY AND CABLE TRAY SHALL BE LISTED OR LABELED FOR ELECTRICAL USE IN ACCORDANCE WITH NEMA, UL, ANSI/IEEC AND NEC.
15. ELECTRICAL METALLIC TUBING (EMT), INTERMEDIATE METAL CONDUIT (IMC), OR RIGID METAL CONDUIT (RMC) SHALL BE USED FOR EXPOSED INDOOR LOCATIONS.
16. ELECTRICAL METALLIC TUBING (EMT) OR METAL-CLAD CABLE (MC) SHALL BE USED FOR CONCEALED INDOOR LOCATIONS.
17. SCHEDULE 40 PVC UNDERGROUND ON STRAIGHTS AND SCHEDULE 80 PVC FOR ALL ELBOWS/90s AND ALL APPROVED ABOVE GRADE PVC CONDUIT.
18. LIQUID-TIGHT FLEXIBLE METALLIC CONDUIT (LIQUID-TITE FLEX) SHALL BE USED INDOORS AND OUTDOORS, WHERE VIBRATION OCCURS OR FLEXIBILITY IS NEEDED.
19. CONDUIT AND TUBING FITTINGS SHALL BE THREADED OR COMPRESSION-TYPE AND APPROVED FOR THE LOCATION USED. SET SNEW FITTINGS ARE NOT ACCEPTABLE.
20. CABINETS, BOXES AND WIRE WAYS SHALL BE LABELED FOR ELECTRICAL USE IN ACCORDANCE WITH NEMA, UL, ANSI/IEEC AND THE NEC.
21. WIREWAYS SHALL BE METAL WITH AN ENAMEL FINISH AND INCLUDE A HINGED COVER, DESIGNED TO SWING OPEN DOWNWARDS (WIREMOLD SPECMATE WIREWAY).
22. SLOTTED WIRING DUCT SHALL BE PVC AND INCLUDE COVER (PANDUIT TYPE E OR EQUAL).
23. CONDUITS SHALL BE FASTENED SECURELY IN PLACE WITH APPROVED NON-PERFORATED STRAPS AND HANGERS. EXPLOSIVE DEVICES (I.E. POWDER-ACTUATED) FOR ATTACHING HANGERS TO STRUCTURE WILL NOT BE PERMITTED. CLOSELY FOLLOW THE LINES OF THE STRUCTURE, MAINTAIN CLOSE PROXIMITY TO THE STRUCTURE AND KEEP CONDUITS IN TIGHT ENVELOPES. CHANGES IN DIRECTION TO ROUTE AROUND OBSTACLES SHALL BE MADE WITH CONDUIT OUTLET BODIES. CONDUIT SHALL BE INSTALLED IN A NEAT AND WORKMANLIKE MANNER, PARALLEL AND PERPENDICULAR TO STRUCTURE WALL AND CEILING LINES. ALL CONDUIT SHALL BE FISHED TO CLEAR OBSTRUCTIONS. ENDS OF CONDUITS SHALL BE TEMPORARILY CAPPED FLUSH TO FINISH GRADE TO PREVENT CONCRETE, PLASTER OR DIRT FROM ENTERING. CONDUITS SHALL BE RIGIDLY CLAMPED TO BOXES BY GALVANIZED MALLEABLE IRON BUSHING ON INSIDE AND GALVANIZED MALLEABLE IRON LOCKNUT ON OUTSIDE AND INSIDE. EQUIPMENT CABINETS, TERMINAL BOXES, JUNCTION BOXES AND PULL BOXES SHALL BE GALVANIZED OR EPOXY-COATED SHEET STEEL. SHALL MEET OR EXCEED UL 50 AND BE RATED NEMA 1 (OR BETTER) FOR INTERIOR LOCATIONS AND NEMA 3R (OR BETTER) FOR EXTERIOR LOCATIONS.
24. METAL RECEPTACLE, SWITCH AND DEVICE BOXES SHALL BE GALVANIZED, EPOXY-COATED OR NON-CORRODING; SHALL MEET OR EXCEED UL 514A AND NEMA OS 1 AND BE RATED NEMA 1 (OR BETTER) FOR INTERIOR LOCATIONS AND WEATHER PROTECTED (WP OR BETTER) FOR EXTERIOR LOCATIONS.
25. NONMETALLIC RECEPTACLE, SWITCH AND DEVICE BOXES SHALL MEET OR EXCEED NEMA OS 2 (NEWEST REVISION) AND BE RATED NEMA 1 (OR BETTER) FOR INTERIOR LOCATIONS AND WEATHER PROTECTED (WP OR BETTER) FOR EXTERIOR LOCATIONS.
26. THE CONTRACTOR SHALL NOTIFY AND OBTAIN NECESSARY AUTHORIZATION FROM THE CARRIER AND/OR CROWN CASTLE USA INC. BEFORE COMMENCING WORK ON THE AC POWER DISTRIBUTION PANELS.
27. THE CONTRACTOR SHALL PROVIDE NECESSARY TAGGING ON THE BREAKERS, CABLES AND DISTRIBUTION PANELS IN ACCORDANCE WITH THE APPLICABLE CODES AND STANDARDS TO SAFEGUARD LIFE AND PROPERTY.
28. INSTALL LAMICOID LABEL ON THE METER CENTER TO SHOW "T-MOBILE".
29. ALL EMPTY/SPARE CONDUITS THAT ARE INSTALLED ARE TO HAVE A METERED MULE TAPE PULL CORD INSTALLED.

Table with 3 columns: SYSTEM, CONDUCTOR, COLOR. Lists conductor color codes for various systems like 120/240V, 10, 120/208V, 30, 277/480V, 30, and DC VOLTAGE.

APWA UNIFORM COLOR CODE:

- WHITE PROPOSED EXCAVATION
PINK TEMPORARY SURVEY MARKINGS
RED ELECTRIC POWER LINES, CABLES, CONDUIT, AND LIGHTING CABLES
YELLOW GAS, OIL, STEAM, PETROLEUM, OR GASEOUS MATERIALS
ORANGE COMMUNICATION, ALARM OR SIGNAL LINES, CABLES, OR CONDUIT AND TRAFFIC LOOPS
BLUE POTABLE WATER
PURPLE RECLAIMED WATER, IRRIGATION, AND SLURRY LINES
GREEN SEWERS AND DRAIN LINES

* SEE NEC 210.5(C)(1) AND (2) ** POLARITY MARKED AT TERMINATION

ABBREVIATIONS:

- ANT ANTENNA
(E) EXISTING
FIF FACILITY INTERFACE FRAME
GEN GENERATOR
GPS GLOBAL POSITIONING SYSTEM
GSM GLOBAL SYSTEM FOR MOBILE
LTE LONG TERM EVOLUTION
MGB MASTER GROUND BAR
MW MICROWAVE
(N) NEW
NEC NATIONAL ELECTRIC CODE
(P) PROPOSED
PP POWER PLAN
QTY QUANTITY
RECT RECTIFIER
RBS RADIO BASE STATION
RETS REMOTE ELECTRIC TILT
RFDS RADIO FREQUENCY DATA SHEET
RRH REMOTE RADIO HEAD
RRU REMOTE RADIO UNIT
SIAD SMART INTEGRATED DEVICE
TMA TOWER MOUNTED AMPLIFIER
TYP TYPICAL
UMTS UNIVERSAL MOBILE TELECOMMUNICATIONS SYSTEM
W.P. WORK POINT

T-Mobile logo and address: 35 GRIFFIN ROAD, BLOOMFIELD, CT 06002

CROWN CASTLE logo and address: 1200 MACARTHUR BLVD, SUITE 200, MAHWAH, NJ 07430

TOWER ENGINEERING PROFESSIONALS logo and address: 326 TRYON RD, RALEIGH, NC 27603, (919) 661-6351

T-MOBILE SITE NUMBER: CTNH452A, BU #: 881534, WATERBURY TOWER, 670 CAPTAIN NEVILLE DRIVE, WATERBURY, CT 06705, EXISTING 150'-0" MONOPOLE

Table with 5 columns: REV, DATE, DRWN, DESCRIPTION, DES/QA. Shows revision history for the drawing.

ISSUED FOR:

Table with 5 columns: REV, DATE, DRWN, DESCRIPTION, DES/QA. Shows issued for information.


Professional Engineer seal for Daniel J. DeSantis, State of Connecticut, License No. 29338.

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SHEET NUMBER: T-2, REVISION: 0

NOTE:
 SITE PLAN SHOWN BELOW WAS REPRODUCED FROM INFORMATION PROVIDED BY CROWN CASTLE AND SITE WALK CONDUCTED BY TEP. CONTRACTOR TO VERIFY ALL EXISTING INFORMATION IS AS INDICATED ON SITE PLAN. CONTRACTOR IS TO ESTABLISH THE EXISTENCE AND LOCATION OF ALL EXISTING UNDERGROUND AND OVERHEAD UTILITIES. IMMEDIATELY NOTIFY THE CONSTRUCTION MANAGER OF ANY DISCREPANCIES.

FLOODPLAIN NOTE:
 THE TOWER IS LOCATED IN ZONE "X" AREAS DETERMINED TO BE OUTSIDE THE 0.2% ANNUAL CHANCE FLOODPLAIN ACCORDING TO FEMA COMMUNITY PANEL #09009C0137H, DATED 12/17/2010.



T-Mobile

35 GRIFFIN ROAD
 BLOOMFIELD, CT 06002

CROWN CASTLE

1200 MACARTHUR BLVD, SUITE 200
 MAHWAH, NJ 07430



TOWER ENGINEERING PROFESSIONALS

326 TRYON RD
 RALEIGH, NC 27603
 (919) 661-6351

TEP JOB #: 218162.502140

T-MOBILE SITE NUMBER:
CTNH452A

BU #: 881534
WATERBURY TOWER


670 CAPTAIN NEVILLE DRIVE
 WATERBURY, CT 06705

EXISTING 150'-0"
MONOPOLE

ISSUED FOR:

REV	DATE	DRWN	DESCRIPTION	DES./QA
A	03/01/21	ER	PRELIMINARY	JTC
B	03/16/21	BSE	PRELIMINARY	JTC
0	03/26/21	JW	CONSTRUCTION	JTC

SEAL:



03/26/21

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.


SHEET NUMBER:

C-1.1


REVISION:

0



1 SITE PLAN
 SCALE: 3/16"=1'-0" (FULL SIZE)
 3/32"=1'-0" (11x17)




FLOODPLAIN NOTE:
 THE TOWER IS LOCATED IN ZONE "X" AREAS
 DETERMINED TO BE OUTSIDE THE 0.2% ANNUAL
 CHANCE FLOODPLAIN ACCORDING TO FEMA COMMUNITY
 PANEL #09009C0137H, DATED 12/17/2010.



1 EXISTING EQUIPMENT PLAN
 SCALE: 3/8"=1'-0" (FULL SIZE)
 3/16"=1'-0" (11x17)



2 FINAL EQUIPMENT PLAN
 SCALE: 3/8"=1'-0" (FULL SIZE)
 3/16"=1'-0" (11x17)




T-Mobile

35 GRIFFIN ROAD
 BLOOMFIELD, CT 06002

CROWN CASTLE

1200 MACARTHUR BLVD, SUITE 200
 MAHWAH, NJ 07430



TOWER ENGINEERING PROFESSIONALS

326 TRYON RD
 RALEIGH, NC 27603
 (919) 661-6351

TEP JOB #: 218162.502140

T-MOBILE SITE NUMBER:
 CTNH452A

BU #: 881534
 WATERBURY TOWER

670 CAPTAIN NEVILLE DRIVE
 WATERBURY, CT 06705

EXISTING 150'-0"
 MONOPOLE

ISSUED FOR:

REV	DATE	DRWN	DESCRIPTION	DES./QA
A	03/01/21	ER	PRELIMINARY	JTC
B	03/16/21	BSE	PRELIMINARY	JTC
0	03/26/21	JW	CONSTRUCTION	JTC

SEAL:



03/26/21

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SHEET NUMBER:

C-1.2

REVISION:

0



T-MOBILE SITE NUMBER:
CTNH452A

BU #: **881534**
WATERBURY TOWER

670 CAPTAIN NEVILLE DRIVE
WATERBURY, CT 06705

EXISTING 150'-0"
MONOPOLE

ISSUED FOR:

REV	DATE	DRWN	DESCRIPTION	DES/QA
A	03/01/21	ER	PRELIMINARY	JTC
B	03/16/21	BSE	PRELIMINARY	JTC
0	03/26/21	JW	CONSTRUCTION	JTC

SEAL:



03/26/21


IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SHEET NUMBER:


C-2

REVISION:

0



1 FINAL ELEVATION
SCALE: NOT TO SCALE




2 EXISTING ANTENNA PLAN
SCALE: NOT TO SCALE

INSTALLER NOTE:
EXISTING AND PROPOSED ANTENNA/EQUIPMENT POSITIONING SHOWN PER RFS. FIELD CONDITIONS MAY VARY.

TIE-BACK ARM NOTE:
TIE-BACK ARMS SHOWN ARE FOR REFERENCE PURPOSES ONLY. TIE-BACK ARMS TO BE INSTALLED PER MOUNT MANUFACTURERS SPECIFICATIONS, ALSO ADHERING TO CROWN CASTLE CED-STD-10294 STANDARD FOR INSTALLATION OF MOUNTS AND APPURTENANCES.


TOWER ANALYSIS NOTES:
1. THE DESIGN DEPICTED IN THESE DRAWINGS IS VALID WHEN ACCOMPANIED BY A CORRESPONDING PASSING TOWER ANALYSIS.
2. CONSTRUCTION MANAGER / GENERAL CONTRACTOR SHALL REVIEW THE TOWER ANALYSIS FOR ANY CONDITIONS PRIOR TO INSTALLATION.
3. ANY REQUIRED TOWER MODIFICATION DESIGN OR TOWER REPLACEMENT SHALL BE APPROVED BY EOR.

MOUNT ANALYSIS NOTES:
1. THE DESIGN DEPICTED IN THESE DRAWINGS IS VALID WHEN ACCOMPANIED BY A CORRESPONDING PASSING MOUNT ANALYSIS.
2. CONSTRUCTION MANAGER / GENERAL CONTRACTOR SHALL REVIEW THE MOUNT ANALYSIS FOR ANY CONDITIONS PRIOR TO INSTALLATION.
3. ANY REQUIRED MOUNT MODIFICATION DESIGN OR MOUNT REPLACEMENT SHALL BE APPROVED BY EOR.



3 FINAL ANTENNA PLAN
SCALE: NOT TO SCALE

RRH NOTE:
CONTRACTOR TO ENSURE RRHs ARE INSTALLED MIN 8" AWAY FROM ANTENNA



TOWER ENGINEERING PROFESSIONALS

326 TRYON RD
RALEIGH, NC 27603
(919) 661-6351

TEP JOB #: 218162.502140

T-MOBILE SITE NUMBER:
CTNH452A

BU #: 881534
WATERBURY TOWER

670 CAPTAIN NEVILLE DRIVE
WATERBURY, CT 06705

EXISTING 150'-0"
MONOPOLE

ISSUED FOR:

REV	DATE	DRWN	DESCRIPTION	DES/QA
A	03/01/21	ER	PRELIMINARY	JTC
B	03/16/21	BSE	PRELIMINARY	JTC
0	03/26/21	JW	CONSTRUCTION	JTC

SEAL:



03/26/21

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SHEET NUMBER:
C-3

REVISION:
0

FINAL ANTENNA SCHEDULE

SECTOR	POS.	TECHNOLOGY	RAD CENTER	AZIMUTH	ANTENNA MANUFACTURER	ANTENNA MODEL	MECH. TILT	ELECT. TILT	TOWER MOUNTED EQUIPMENT	FEEDLINE TYPE
DISH	-	-	142'-0"	12'	ANDREW	VHLP2-11	-	-	(1) DRAGONWAVE/HORIZON COMPACT ODU	EUPEN - EC4-50 CABLE (1/2")
ALPHA	A1	L2100	140'-0"	30'	RFS	APX16DWV-16DWV-S-E-A20 (QUAD)	-	2'	(1) ERICSSON - 4415 B66A	(1) HCS 6/24 4AWG 100m
ALPHA	A2	L700, L600, N600, L1900, G1900	140'-0"	30'	RFS	APXVAALL24_43-U-NA20 (OCTO)	-	2'	(1) ERICSSON - 4449 B71+B85 (1) ERICSSON - 4415 B25	(1) HCS 6/24 4AWG 100m
ALPHA	A3	L2500, N2500	140'-0"	30'	ERICSSON	AIR6449 B41 (ACTIVE ANTENNA - MASSIVE MIMO)	-	2'	-	HYBRID (SHARED)
BETA	B1	L2100	140'-0"	150'	RFS	APX16DWV-16DWV-S-E-A20 (QUAD)	-	2'	(1) ERICSSON - 4415 B66A	HYBRID (SHARED)
BETA	B2	L700, L600, N600, L1900, G1900	140'-0"	150'	RFS	APXVAALL24_43-U-NA20 (OCTO)	-	2'	(1) ERICSSON - 4449 B71+B85 (1) ERICSSON - 4415 B25	(1) HCS 6/24 4AWG 100m
BETA	B3	L2500, N2500	140'-0"	150'	ERICSSON	AIR6449 B41 (ACTIVE ANTENNA - MASSIVE MIMO)	-	2'	-	HYBRID (SHARED)
DISH	-	-	142'-0"	203'	ANDREW	VHLP2-11	-	-	(1) DRAGONWAVE/HORIZON COMPACT ODU	EUPEN - EC4-50 CABLE (1/2")
DISH	-	-	142'-0"	270'	MOTOROLA	TIMING200	-	-	-	EUPEN - EC4-50 CABLE (1/2")
GAMMA	C1	L2100	140'-0"	270'	RFS	APX16DWV-16DWV-S-E-A20 (QUAD)	-	2'	(1) ERICSSON - 4415 B66A	HYBRID (SHARED)
GAMMA	C2	L700, L600, N600, L1900, G1900	140'-0"	270'	RFS	APXVAALL24_43-U-NA20 (OCTO)	-	2'	(1) ERICSSON - 4449 B71+B85 (1) ERICSSON - 4415 B25	(1) HCS 6/24 4AWG 100m
GAMMA	C3	L2500, N2500	140'-0"	270'	ERICSSON	AIR6449 B41 (ACTIVE ANTENNA - MASSIVE MIMO)	-	2'	-	HYBRID (SHARED)


PROPOSED ANTENNA/EQUIPMENT SHOWN IN BOLD

FINAL CABLE SCHEDULE


STATUS	CABLE TYPE	SIZE	QUANTITY
EXISTING	CABLE	1/2"	3
NEW	HCS	100m 4AWG	4
CABLE QUANTITY			7

NOTE:
(3) HYBRID SHARED BETWEEN APX/4415/4449/4424 PER SECTOR
(1) HYBRID SHARED BETWEEN 6449 ANTENNAS PER SECTOR

1 PROPOSED ANTENNA AND CABLE SCHEDULE
SCALE: NOT TO SCALE




2 HCS DETAIL
SCALE: NOT TO SCALE




1 ANTENNA MOUNTING DETAIL
SCALE: NOT TO SCALE

INSTALLER NOTES:

1. COMPLY WITH MANUFACTURERS INSTRUCTIONS TO ENSURE THAT ALL RRHs RECEIVE ELECTRICAL POWER WITHIN 24 HOURS OF BEING REMOVED FROM THE MANUFACTURER'S PACKAGING.
2. DO NOT OPEN RRH PACKAGES IN THE RAIN.
3. ALL PIPES, BRACKETS, AND MISCELLANEOUS HARDWARE TO BE GALVANIZED UNLESS NOTED OTHERWISE.




2 RRHs MOUNTING DETAIL
SCALE: NOT TO SCALE



ERICSSON - AIR6449 B41
WEIGHT: 104.0 LBS
SIZE (HxWxD): 33.10x20.60x8.60 IN.

3 ERICSSON - AIR6449 B41
SCALE: NOT TO SCALE



RFS/CELWAVE - APXVAALL24_43-U-NA20
WEIGHT (WITHOUT MOUNTING HARDWARE): 149.9 LBS
SIZE (HxWxD): 95.9x24.0x8.5 IN.

4 RFS/CELWAVE - APXVAALL24_43-U-NA20
SCALE: NOT TO SCALE

T-Mobile

35 GRIFFIN ROAD
BLOOMFIELD, CT 06002

CROWN CASTLE

1200 MACARTHUR BLVD, SUITE 200
MAHWAH, NJ 07430



TOWER ENGINEERING PROFESSIONALS

326 TRYON RD
RALEIGH, NC 27603
(919) 661-6351

TEP JOB #: 218162.502140

**T-MOBILE SITE NUMBER:
CTNH452A**

**BU #: 881534
WATERBURY TOWER**

670 CAPTAIN NEVILLE DRIVE
WATERBURY, CT 06705

**EXISTING 150'-0"
MONOPOLE**

ISSUED FOR:

REV	DATE	DRWN	DESCRIPTION	DES/QA
A	03/01/21	ER	PRELIMINARY	JTC
B	03/16/21	BSE	PRELIMINARY	JTC
0	03/26/21	JW	CONSTRUCTION	JTC

SEAL:



03/26/21


IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SHEET NUMBER:

C-4


REVISION:

0




RFS/CELWAVE - APX16DWV-16DWVS-E-A20
WEIGHT (WITHOUT MOUNTING HARDWARE): 40.70 LBS
SIZE (HxWxD): 55.9x13.3x3.15 IN.

5 RFS/CELWAVE - APX16DWV-16DWVS-E-A20
SCALE: NOT TO SCALE




ERICSSON - RADIO 4424 B25
WEIGHT: 86.0 LBS
SIZE (HxWxD): 17.10x14.4x11.30 IN.

6 ERICSSON - RADIO 4424 B25
SCALE: NOT TO SCALE



ERICSSON - RADIO 4449 B71/B85
WEIGHT: 73.21 LBS
SIZE (HxWxD): 17.91x13.2x10.63 IN.

7 ERICSSON - RADIO 4449 B71/B85
SCALE: NOT TO SCALE




ERICSSON - RADIO 4415 B66A
WEIGHT: 44.0 LBS
SIZE (HxWxD): 14.96x13.19x5.39 IN.

8 ERICSSON - RADIO 4415 B66A
SCALE: NOT TO SCALE

INSTALLER NOTES:

1. INFORMATION SHOWN PROVIDED BY T-MOBILE. CONTRACTOR TO REFERENCE CABINET MANUFACTURER'S SPECIFICATIONS FOR FURTHER DETAILS.
2. CONTRACTOR TO FOLLOW THE LATEST VERSION OF T-MOBILE REGIONAL CONSTRUCTION STANDARDS. CONTACT T-MOBILE FOR DETAILS.



Dimensions	
Width (A)	650 mm / 25.5906 in
Height (B)	1450 mm / 57.08661 in (without base frame) 1600 mm / 62.99213 in (with base frame)
Depth (C)	850 mm / 33.4646 in
Weight	
Empty enclosure	176 kg / 388.014 lb

1 ERICSSON 6160 CABINET DETAILS
SCALE: NOT TO SCALE



2 ERICSSON B160 CABINET DETAILS
SCALE: NOT TO SCALE

T-Mobile

35 GRIFFIN ROAD
BLOOMFIELD, CT 06002

CROWN CASTLE

1200 MACARTHUR BLVD, SUITE 200
MAHWAH, NJ 07430



TOWER ENGINEERING PROFESSIONALS

326 TRYON RD
RALEIGH, NC 27603
(919) 661-6351

TEP JOB #: 218162.502140

**T-MOBILE SITE NUMBER:
CTNH452A**

**BU #: 881534
WATERBURY TOWER**


670 CAPTAIN NEVILLE DRIVE
WATERBURY, CT 06705

**EXISTING 150'-0"
MONOPOLE**

ISSUED FOR:

REV	DATE	DRWN	DESCRIPTION	DES/QA
A	03/01/21	ER	PRELIMINARY	JTC
B	03/16/21	BSE	PRELIMINARY	JTC
0	03/26/21	JW	CONSTRUCTION	JTC

SEAL:



03/26/21

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SHEET NUMBER:

C-5

REVISION:

0


NOTE:
LOAD CALCULATIONS TAKEN FROM
INFORMATION PROVIDED BY CROWN
CASTLE & POWER ANALYSIS TOOL
BASED ON THE RFDS DATED
12/21/2020 V1.0. CONTRACTOR
TO VERIFY LOADS WITH
MANUFACTURER'S SPECIFICATIONS
PRIOR TO CONSTRUCTION.

EXISTING 200A M.C.B, 240/120 VAC, 1 ϕ , 3W PPC PANEL SCHEDULE											
LOAD SERVED	VOLT AMPERES (WATTS)		TRIP	CKT #	PHASE	CKT #	TRIP	VOLT AMPERES (WATTS)		LOAD SERVED	
	L1	L2						L1	L2		
SURGE PROTECTOR	100		20	1	A	2	15	180		TELCO GFI	
		100		3	B	4			9600	ELTEK CABINET	
HOFFMAN FAN	340		15	5	A	6	*100	9600			
SPARE				7	B	8				SPARE	
SPARE				9	A	10				SPARE	
SPARE				11	B	12				SPARE	
SPARE				13	A	14				SPARE	
SPARE				15	B	16				SPARE	
SPARE				17	A	18				SPARE	
SPARE				19	B	20				SPARE	
SPARE				21	A	22				SPARE	
SPARE				23	B	24				SPARE	
VOLT AMPS	440	100						9780	9600	VOLT AMPS	
L1 VOLT AMPERES				10220	9700		L2 VOLT AMPERES				
				10220			MAX VOLT AMPERES				
				85.2			MAX AMPS				
				106.5			MAX AMPS x 125%				

*NOTE - REUSE BREAKER FOR NEW CABINET INSTALL, NOTIFY TEP IF BREAKER IS TO REMAIN

PROPOSED 200A M.C.B, 240/120 VAC, 1 ϕ , 3W PPC PANEL SCHEDULE											
LOAD SERVED	VOLT AMPERES (WATTS)		TRIP	CKT #	PHASE	CKT #	TRIP	VOLT AMPERES (WATTS)		LOAD SERVED	
	L1	L2						L1	L2		
SURGE PROTECTOR	100		20	1	A	2	15	180		TELCO GFI	
		100		3	B	4			7405	6160 ENCLOSURE	
HOFFMAN FAN	340		15	5	A	6	*100	7405			
SPARE				7	B	8	20	180		GFCI INTERNAL IN 6160	
SPARE				9	A	10				SPARE	
SPARE				11	B	12				SPARE	
SPARE				13	A	14				SPARE	
SPARE				15	B	16				SPARE	
SPARE				17	A	18				SPARE	
SPARE				19	B	20				SPARE	
SPARE				21	A	22				SPARE	
SPARE				23	B	24				SPARE	
VOLT AMPS	440	100						7585	7585	VOLT AMPS	
L1 VOLT AMPERES				8025	7685		L2 VOLT AMPERES				
				8025			MAX VOLT AMPERES				
				66.9			MAX AMPS				
				83.6			MAX AMPS x 125%				

NOTE - PROPOSED BREAKER IN BOLD



GENERAL NOTES:

- ALL NEW CONDUCTORS TO BE INSTALLED SHALL BE COPPER. ALL CONDUCTORS SHALL BE THHW, THWN, THWN-2, XHHW, XHHW-2, THW, THW-2, RHW, OR RHW-2 UNLESS NOTED OTHERWISE.
- CONTRACTOR IS TO FIELD VERIFY ALL EXISTING ITEMS SHOWN ON THE ELECTRICAL ONE-LINE DIAGRAM AND NOTIFY THE ENGINEER OF ANY DISCREPANCIES.
- ALL GROUNDING AND BONDING PER THE NEC.

ONE-LINE DIAGRAM NOTES:

- ELECTRICAL SERVICE IS 200A, 120/240V, 1 ϕ , 3W.
- FOR COMPLETE INTERNAL WIRING AND ARRANGEMENT, REFER TO VENDOR PRINTS PROVIDED BY EQUIPMENT MANUFACTURER.

UTILITY NOTES:

- CONTRACTOR SHALL VERIFY AVAILABLE FAULT CURRENT WITH POWER COMPANY AND ENSURE ALL ELECTRICAL EQUIPMENT IS SUITABLE FOR AVAILABLE FAULT CURRENT.
- CONTRACTOR SHALL COORDINATE UTILITY SERVICES WITH LOCAL UTILITY COMPANIES. VERIFY ALL REQUIREMENTS WITH UTILITY COMPANY STANDARDS.
- ONE-LINE DIAGRAM IS FOR SCHEMATIC PURPOSES ONLY AND IS NOT INDICATIVE OF THE ACTUAL EQUIPMENT LAYOUT.
- ALL EQUIPMENT WILL HAVE A MINIMUM AIC OF 10 KA. CONTRACTOR TO DETERMINE AVAILABLE FAULT CURRENT BEFORE ENERGIZING EQUIPMENT. THE AMOUNT OF AVAILABLE FAULT CURRENT SHALL BE MARKED ON THE SERVICE EQUIPMENT PER NEC 110.24.
- CONTRACTOR SHALL NOTIFY UTILITY COMPANY OF CHANGES IN ELECTRICAL LOAD.
- CONTRACTOR TO VERIFY EXISTING CONDUIT(S) SIZE(S) PRIOR TO CONSTRUCTION AND MAY REUSE EXISTING CONDUIT(S) IF THEY MEET THE MINIMUM REQUIREMENTS PER NEC CODE.
- GROUNDING ELECTRODE CONDUCTOR IS SIZED FOR SINGLE 200A SERVICE ONLY. IF METER BANK SHARES A COMMON NEUTRAL/GROUND POINT, CONTRACTOR WILL INSTALL (1) 3/0 COPPER GEC INSTEAD.

UL NOTE:

ELECTRICAL MATERIALS, DEVICES, CONDUCTORS, APPLIANCES AND EQUIPMENT SHALL BE LABELED/LISTED BY UL OR ACCEPTED BY JURISDICTION (I.E.: LOCAL COUNTY OR STATE) APPROVED THIRD PARTY TESTING AGENCY

T-Mobile

35 GRIFFIN ROAD
BLOOMFIELD, CT 06002

CROWN CASTLE

1200 MACARTHUR BLVD, SUITE 200
MAHWAH, NJ 07430

TOWER ENGINEERING PROFESSIONALS

326 TRYON RD
RALEIGH, NC 27603
(919) 661-6351

TEP JOB #: 218162.502140

T-MOBILE SITE NUMBER:
CTNH452A

BU #: 881534
WATERBURY TOWER

670 CAPTAIN NEVILLE DRIVE
WATERBURY, CT 06705

EXISTING 150'-0"
MONOPOLE

ISSUED FOR:

REV	DATE	DRWN	DESCRIPTION	DES/QA
A	03/01/21	ER	PRELIMINARY	JTC
B	03/16/21	BSE	PRELIMINARY	JTC
0	03/26/21	JW	CONSTRUCTION	JTC

SEAL:



03/26/21

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SHEET NUMBER:

E-1

REVISION:

0

1 AC PANEL SCHEDULES
SCALE: NOT TO SCALE

2 ONE LINE DIAGRAM
SCALE: NOT TO SCALE

ALL GROUNDS MUST ROUTE DOWNHILL FOR ENTIRE DURATION OF ROUTE

PROVIDE LABOR, MATERIALS, INSPECTION, AND TESTING TO PROVIDE CODE COMPLIANCE FOR

#2 SOLID COPPER TINNED, EXOTHERMICALLY WELDED TO GROUND RING (BOTH ENDS), FINAL WELD COLD GALVANIZED, IN 1/2" NON-METALLIC SEAL TIGHT CONDUIT, SEALED WITH SILICONE, ANCHORED TO PAD/PLATFORM TO AVOID TRIP HAZARD USING HAMMER SET ANCHORS.

- #2 SOLID COPPER TINNED, 2 HOLE LUG WITH FLAT AND LOCK WASHER AT EQUIPMENT; EXOTHERMICALLY WELDED TO GROUND RING, FINAL WELD COLD GALVANIZED, IN 1/2" NON-METALLIC SEAL TIGHT CONDUIT, SEALED WITH SILICONE, ANCHORED TO PAD TO AVOID TRIP HAZARD USING HAMMER SET ANCHORS. EACH PART REQUIRES A SEPARATE DOWNLEAD, NO DAISY CHAINS.
- ALL COMPONENTS INSIDE FCOA CABINETS REQUIRE A DEDICATED GROUND.

#6 THHN STRANDED (GREEN JACKET), CONNECTED AT EQUIPMENT SIDE USING OVP TERMINAL BLOCK CONNECTION; MECHANICALLY CONNECTED TO GROUND REFERENCE AT MASTER BUSS BAR USING 2 HOLE LUG WITH FLAT AND LOCK WASHER, IN 1/2" NON-METALLIC SEAL TIGHT CONDUIT, SEALED WITH SILICONE, AND ANCHORED TO PAD/PLATFORM TO AVOID TRIP HAZARD.

- ALL VERTICAL MAST PIPES: #2 SOLID COPPER TINNED, EXOTHERMICALLY WELDED TO TOP OF PIPE (PIPE, DOWN MOLD), FINAL WELD COLD GALVANIZED, BONDED TO TOP BUSS BAR WITH 2 HOLE COPPER COMPRESSION LUG, FLAT AND LOCK WASHER.
- EXISTING/REUSED PIPES: #2 SOLID COPPER TINNED, BONDED WITH COLD WATER CLAMP TO TOP OF PIPE, BONDED TO TOP BUSS WITH 2 HOLE COPPER COMPRESSION LUG, FLAT AND LOCK WASHER

- #6 THHN, WITH PROPER COPPER COMPRESSION LUG, FLATS AND LOCK WASHERS
- ALL GROUND LUGS ON TMA MUST BE GROUNDED WITH SEPARATE DOWNLEAD TO BUSS BAR (NO DAISY CHAINS)

#2 SOLID COPPER TINNED, EXOTHERMICALLY WELDED (FLAT PLATE MOLD) TO OUTSIDE PERIMETER BEAMS IN FOUR (4) PLACES, FINAL WELD COLD GALVANIZED, BONDED DIRECTLY TO SUBGRADE GROUND RING.

- #2 SOLID COPPER TINNED, EXOTHERMICALLY WELDED (PIPE, DOWN MOLD) TO BOTTOM OF ALL VERTICAL SUPPORT POSTS, TYPICALLY FOUR (4) PIPES, FINAL WELD COLD GALVANIZED, BONDED DIRECTLY TO SUBGRADE GROUND RING.
- #2 SOLID COPPER TINNED, EXOTHERMICALLY WELDED (PIPE, UP MOLD) TO TOP OF ALL VERTICAL SUPPORT POSTS, TYPICALLY FOUR (4) PIPES, FINAL WELD COLD GALVANIZED, BONDED UP TO CANOPY GRIP-STRUT USING 2 HOLE COPPER COMPRESSION LUG, FLAT AND LOCK WASHER.

#6 THHN, WITH PROPER COPPER COMPRESSION LUG, ANTI-OXIDANT TO SECTOR BUSS BAR

#6 THHN WITH ONE HOLE LUG BONDED TO PREVIOUSLY GROUNDED FCOA, PLINTH OR BUSS BAR.

#6 THHN TO PREVIOUSLY GROUNDED BUSS BAR USING PROPER LUGS

- #6 THHN TO PREVIOUSLY GROUNDED BUSS BAR USING PROPER LUGS
- THROUGH BOLTS WITH FLAT, LOCK ON BRACKET


- PLATFORM / PAD BUSS BAR SHOULD BE MINIMUM 12" TINNED COPPER WITH INSULATORS, AND SHOULD HAVE TWO (2) EXOTHERMICALLY WELDED DOWN LEADS DIRECTLY TO GROUND RING USING #2 SOLID COPPER TINNED WIRE.
- SECTOR BUSS BAR SHOULD BE PROPERLY SIZED TO ACCOMMODATE NECESSARY GROUNDING FOR EQUIPMENT ON EACH MOUNT, AND MAY BE SOLID COPPER (TINNED NOT REQUIRED). DO NOT USE INSULATORS ON SECTOR BUSS BARS ATTACH DIRECTLY TO TOWER MOUNT STEEL.

- NO GROUND KITS ON HYBRID TRUNKS (TOP OR BOTTOM)
- NO GROUND KITS ON MICROWAVE IF CABLES (TOP OR BOTTOM)
- MICROWAVE SURGE SUPPRESSORS ARE NOT TO BE INSTALLED UPSTAIRS ON TOWER, DOWNSTAIRS ONLY (BULKHEAD PREFERRED)
- MICROWAVE ODU MUST BE GROUNDED TO TOWER TOP SECTOR OR COLLECTOR BUSS BAR
- ALL TMA'S AND DIPLEXERS MUST BE GROUNDED TO BUSS BAR. NO DAISY CHAIN ON TWIN/DUAL TMA
- ALL LUGS SHOULD BE PROPERLY SIZED FOR CONDUCTOR, BURNDY TINNED COPPER COMPRESSION STYLE
 - INDOOR (OR INSIDE CABINET) SHOULD HAVE WINDOW
 - OUTDOOR SHOULD NOT HAVE WINDOW
- CONTRACTOR TO VERIFY EXISTENCE AND LOCATION OF EXISTING SITE GROUND SYSTEM.
- CONTRACTOR SHALL VERIFY THAT GROUNDING ELECTRODES SHALL BE CONNECTED IN A RING USING #2 AWG BARE TINNED COPPER WIRE. THE TOP OF THE GROUND RODS AND THE RING CONDUCTOR SHALL BE 30" BELOW FINISHED GRADE, OR TO FROST DEPTH, WHICHEVER IS GREATER. GROUNDING ELECTRODES SHALL BE DRIVEN ON 10'-0" CENTERS (PROVIDE AND INSTALL AS REQUIRED, REQUIRED PER PLAN BELOW).
- GROUNDING CONDUCTORS SHALL BE OF EQUAL LENGTH, MATERIAL, AND BONDING TECHNIQUE.
- CONTRACTOR SHALL ENSURE GROUND RING IS WITHIN 12 TO 36 INCHES OF THE EQUIPMENT PAD. PROVIDE AND INSTALL GROUNDING CONNECTIONS SHOWN BELOW AS NEEDED PER EXISTING SITE GROUNDING SYSTEM. CONTRACTOR SHALL VERIFY ALL EXISTING SITE GROUNDING CONDITIONS BEFORE STARTING WORK OR PURCHASING EQUIPMENT.
- ALL DOWN CONDUCTORS MUST GO DOWN.

ALPHA

BETA


GAMMA



NOTE:
ALL NEW GROUNDS TO BE #6 STRANDED COPPER WITH GREEN INSULATION UNLESS NOTED OTHERWISE.
GROUNDING SHOWN TYPICAL PER SECTOR.

1 TYPICAL ANTENNA GROUNDING DIAGRAM
SCALE: NOT TO SCALE

NOTE:
CONTRACTOR TO REFERENCE SHEET C-1.1 & 1.2 FOR EXACT LOCATION AND ORIENTATION OF EQUIPMENT PAD



2 TYPICAL CABINET GROUNDING DIAGRAM
SCALE: NOT TO SCALE

T-Mobile
35 GRIFFIN ROAD
BLOOMFIELD, CT 06002

CROWN CASTLE
1200 MACARTHUR BLVD, SUITE 200
MAHWAH, NJ 07430

TOWER ENGINEERING PROFESSIONALS
326 TRYON RD
RALEIGH, NC 27603
(919) 661-6351
TEP JOB #: 218162.502140

T-MOBILE SITE NUMBER:
CTNH452A

BU #: **881534**
WATERBURY TOWER

670 CAPTAIN NEVILLE DRIVE
WATERBURY, CT 06705

EXISTING 150'-0"
MONOPOLE

ISSUED FOR:


REV	DATE	DRWN	DESCRIPTION	DES./QA
A	03/01/21	ER	PRELIMINARY	JTC
B	03/16/21	BSE	PRELIMINARY	JTC
0	03/26/21	JW	CONSTRUCTION	JTC

SEAL:

03/26/21

IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.


SHEET NUMBER: **G-1** REVISION: **0**



NOTES:

- DOUBLING UP "OR STACKING" OF CONNECTIONS IS NOT PERMITTED.
- EXTERIOR ANTIOXIDANT JOINT COMPOUND TO BE USED ON ALL EXTERIOR CONNECTIONS.
- GROUND BAR SHALL NOT BE ISOLATED FROM TOWER. MOUNT DIRECTLY TO ANTENNA MOUNT STEEL.


1 ANTENNA SECTOR GROUND BAR DETAIL
SCALE: NOT TO SCALE



NOTES:

- EXTERIOR ANTIOXIDANT JOINT COMPOUND TO BE USED ON ALL EXTERIOR CONNECTIONS.
- GROUND BAR SHALL NOT BE ISOLATED FROM TOWER. MOUNT DIRECTLY TO TOWER STEEL (TOWER ONLY).
- GROUND BAR SHALL BE ISOLATED FROM BUILDING OR SHELTER.


2 TOWER/SHELTER GROUND BAR DETAIL
SCALE: NOT TO SCALE



NOTES:

- GROUND ROD SHALL BE DRIVEN VERTICALLY, NOT TO EXCEED 45 DEGREES FROM THE VERTICAL
- GROUND WIRE SHALL BE MIN. 30" BELOW GRADE OR 6" BELOW FROST LINE. (WHICH EVER IS GREATER) AS PER N.E.C. ARTICLE 250-50(D)


3 INSPECTION WELL DETAIL
SCALE: NOT TO SCALE




NOTES:

- NUMBER OF GROUNDING BARS MAY VARY DEPENDING ON THE TYPE OF TOWER, ANTENNA LOCATIONS AND CONNECTION ORIENTATION. COAXIAL CABLES EXCEEDING 200 FEET ON THE TOWER SHALL HAVE GROUND KITS AT THE MIDPOINT. PROVIDE AS REQUIRED.
- ONLY MECHANICAL CONNECTIONS ARE ALLOWED TO BE MADE TO CROWN CASTLE USA INC. TOWERS. ALL MECHANICAL CONNECTIONS SHALL BE TREATED WITH AN ANTI-OXIDANT COATING.
- ALL TOWER GROUNDING SYSTEMS SHALL COMPLY WITH THE REQUIREMENTS OF THE RECOGNIZED EDITION OF ANSI/TIA 222 AND NFPA 780.


4 TYPICAL ANTENNA CABLE GROUNDING
SCALE: NOT TO SCALE



SINGLE CONNECTOR AT GROUND BARS




SINGLE CONNECTOR AT STEEL OBJECTS



SINGLE CONNECTOR AT METALLIC/STEEL OBJECTS

5 HARDWARE DETAIL FOR EXTERIOR CONNECTIONS
SCALE: NOT TO SCALE



NOTES:

- GROUND ROD SHALL BE DRIVEN VERTICALLY, NOT TO EXCEED 45 DEGREES FROM THE VERTICAL
- GROUND WIRE SHALL BE MIN. 30" BELOW GRADE OR 6" BELOW FROST LINE. (WHICH EVER IS GREATER) AS PER N.E.C. ARTICLE 250-50(D)

6 GROUND ROD DETAIL
SCALE: NOT TO SCALE

T-Mobile

35 GRIFFIN ROAD
BLOOMFIELD, CT 06002

CROWN CASTLE

1200 MACARTHUR BLVD, SUITE 200
MAHWAH, NJ 07430

TOWER ENGINEERING PROFESSIONALS
326 TRYON RD
RALEIGH, NC 27603
(919) 661-6351

TEP JOB #: 218162.502140

T-MOBILE SITE NUMBER:
CTNH452A

BU #: 881534
WATERBURY TOWER

670 CAPTAIN NEVILLE DRIVE
WATERBURY, CT 06705

EXISTING 150'-0"
MONOPOLE

ISSUED FOR:

REV	DATE	DRWN	DESCRIPTION	DES/QA
A	03/01/21	ER	PRELIMINARY	JTC
B	03/16/21	BSE	PRELIMINARY	JTC
0	03/26/21	JW	CONSTRUCTION	JTC

SEAL:



03/26/21


IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SHEET NUMBER:

G-2

REVISION:


0



NOTE:

1. ERICO EXOTHERMIC "MOLD TYPES" SHOWN HERE ARE EXAMPLES. CONSULT WITH CONSTRUCTION MANAGER FOR SPECIFIC MOLDS TO BE USED FOR THIS PROJECT.
2. MOLD TYPE ONLY TO BE USED BELOW GRADE WHEN CONNECTING GROUND RING TO GROUND ROD.


1 CADWELD GROUNDING CONNECTIONS
SCALE: NOT TO SCALE



NOTES:

1. DO NOT INSTALL CABLE GROUND KIT AT A BEND AND ALWAYS DIRECT GROUND WIRE DOWN TO GROUND BAR.
2. GROUNDING KIT SHALL BE TYPE AND PART NUMBER AS SUPPLIED OR RECOMMENDED BY CABLE MANUFACTURER.
3. WEATHER PROOFING SHALL BE TWO-PART TAPE KIT. COLD SHRINK SHALL NOT BE USED.


3 CABLE GROUND KIT CONNECTION
SCALE: NOT TO SCALE



NOTES:

1. DO NOT INSTALL CABLE GROUND KIT AT A BEND AND ALWAYS DIRECT GROUND WIRE DOWN TO ANTENNA GROUND BAR.
2. WEATHER PROOFING SHALL BE TWO-PART TAPE KIT. COLD SHRINK SHALL NOT BE USED.


4 GROUND CABLE CONNECTION
SCALE: NOT TO SCALE



NOTES:


1. DOWN LEAD (HOME RUN) CONDUCTORS ARE NOT TO BE INSTALLED ON CROWN CASTLE USA INC. TOWER, PER THE GROUNDING DOWN CONDUCTOR POLICY GAS-STD-10091. NO MODIFICATION OR DRILLING TO TOWER STEEL IS ALLOWED IN ANY FORM OR FASHION. CAD-WELDING ON THE TOWER AND/OR IN THE AIR ARE NOT PERMITTED.
2. OMIT INSULATOR WHEN MOUNTING TO TOWER STEEL OR PLATFORM STEEL. USE INSULATORS WHEN ATTACHING TO BUILDING OR SHELTERS.

6 GROUND BAR DETAIL
SCALE: NOT TO SCALE



7 LUG DETAIL
SCALE: NOT TO SCALE


WIRE SIZE	BURNDY LUG	BOLT SIZE
#6 AWG GREEN INSULATED	YA6C-2TC38	3/8" - 16 NC S 2 BOLT
#2 AWG SOLID TINNED	YA3C-2TC38	3/8" - 16 NC S 2 BOLT
#2 AWG STRANDED	YA2C-2TC38	3/8" - 16 NC S 2 BOLT
#2/0 AWG STRANDED	YA26-2TC38	3/8" - 16 NC S 2 BOLT
#4/0 AWG STRANDED	YA28-2N	1/2" - 16 NC S 2 BOLT




NOTES:

1. ALL GROUNDING LUGS ARE TO BE INSTALLED PER MANUFACTURER'S SPECIFICATIONS. ALL HARDWARE BOLTS, NUTS, LOCK WASHERS SHALL BE STAINLESS STEEL. ALL HARDWARE ARE TO BE AS FOLLOWS: BOLT, FLAT WASHER, GROUND BAR, GROUND LUG, FLAT WASHER AND NUT.


2 MECHANICAL LUG CONNECTION
SCALE: NOT TO SCALE



5 GROUNDWIRE INSTALLATION
SCALE: NOT TO SCALE



8 TRANSITIONING GROUND DETAIL
SCALE: NOT TO SCALE



T-MOBILE SITE NUMBER:
CTNH452A


BU #: 881534
WATERBURY TOWER

670 CAPTAIN NEVILLE DRIVE
WATERBURY, CT 06705

EXISTING 150'-0"
MONOPOLE

ISSUED FOR:

REV	DATE	DRWN	DESCRIPTION	DES./QA
A	03/01/21	ER	PRELIMINARY	JTC
B	03/16/21	BSE	PRELIMINARY	JTC
0	03/26/21	JW	CONSTRUCTION	JTC



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SHEET NUMBER: **G-3** REVISION: **0**

Exhibit D

Structural Analysis Report

Date: **February 12, 2021**



Tower Engineering Professionals
326 Tryon Road
Raleigh, NC 27603
(919) 661-6351

Subject: Structural Analysis Report

Carrier Designation: *Clearwire Corp Co-Locate*

Site Number: CTNH452A
Site Name: CTNH452A

Crown Castle Designation:

BU Number: 881534
Site Name: Waterbury Tower
JDE Job Number: 628860
Work Order Number: 1918937
Order Number: 538784 Rev. 1

Engineering Firm Designation:

TEP Project Number: 218162.496345

Site Data:

670 Captain Neville Drive, Waterbury, New Haven County, CT 06705
Latitude 41° 32' 3.60", Longitude -72° 58' 8.40"
150 Foot - Monopole Tower

Tower Engineering Professionals is pleased to submit this "**Structural Analysis Report**" to determine the structural integrity of the above-mentioned tower.

The purpose of the analysis is to determine acceptability of the tower stress level. Based on our analysis we have determined the tower stress level for the structure and foundation, under the following load case, to be:

LC5: Proposed Equipment Configuration

Sufficient Capacity

This analysis utilizes an ultimate 3-second gust wind speed of 125 mph as required by the 2018 Connecticut State Building Code. Applicable Standard references and design criteria are listed in Section 2 - Analysis Criteria.

Structural analysis prepared by: Samuel W. Poindexter / MBB

Respectfully submitted by:

Aaron T. Rucker, P.E.



Electronic Copy

02/12/2021

TABLE OF CONTENTS

1) INTRODUCTION

2) ANALYSIS CRITERIA

Table 1 - Proposed Equipment Configuration

Table 2 - Other Considered Equipment

3) ANALYSIS PROCEDURE

Table 3 - Documents Provided

3.1) Analysis Method

3.2) Assumptions

4) ANALYSIS RESULTS

Table 4 - Section Capacity (Summary)

Table 5 - Tower Component Stresses vs. Capacity

4.1) Recommendations

5) APPENDIX A

tnxTower Output

6) APPENDIX B

Base Level Drawing

7) APPENDIX C

Additional Calculations

1) INTRODUCTION

This tower is a 150-ft monopole tower designed by Engineered Endeavors, Inc.

2) ANALYSIS CRITERIA

TIA-222 Revision:	TIA-222-H
Risk Category:	II
Wind Speed:	125 mph
Exposure Category:	C
Topographic Factor:	1.0
Ice Thickness:	1.5 in
Wind Speed with Ice:	50 mph
Service Wind Speed:	60 mph

Table 1 - Proposed Equipment Configuration

Mounting Level (ft)	Center Line Elevation (ft)	Number of Antennas	Antenna Manufacturer	Antenna Model	Number of Feed Lines	Feed Line Size (in)
140.0	142.0	2	Andrew	VHLP2-11	3 4	1/2 1-5/8
		1	Motorola	Timing 2000		
	140.0	3	RFS Celwave	APX16DWV-16DWV-S-E-A20		
		3	RFS Celwave	APXVAALL24_43-U-NA20_TMO		
		3	Ericsson	AIR6449 B41_T-Mobile		
		3	Ericsson	Radio 4415 B66A_CCIV3		
		3	Ericsson	Radio 4424 B25_TMO		
		3	Ericsson	Radio 4449 B71 B85A_T-Mobile		
		2	Dragonwave	Horizon Compact		
		1	Tower Mounts	Platform Mount [LP 301-1_KCKR]		

Table 2 - Other Considered Equipment

Mounting Level (ft)	Center Line Elevation (ft)	Number of Antennas	Antenna Manufacturer	Antenna Model	Number of Feed Lines	Feed Line Size (in)
150.0	151.0	3	Kathrein	800 10121	12 6 2	1-5/8 3/4 3/8
		2	CCI Antennas	TPA-65R-LCUUUU-H8		
		1	CCI Antennas	OPA-65R-LCUU-H6		
		1	Quintel Technology	QS66512-2		
		3	Powerwave Technologies	LGP21401		
		3	Ericsson	RRUS A2 Module		
		3	Ericsson	RRUS 12 W/O Solar Shield		
		3	Ericsson	RRUS 11		
		2	Raycap	DC6-48-60-18-8F		
		3	Ericsson	RRUS 32		
	6	CCi Antennas	TPX-070821			
	150.0	2	Kathrein	80010966		
		2	CCI Antennas	OPA-65R-LCUU-H8		
		1	Kathrein	80010965K		
		3	Powerwave Technologies	LGP21401		
		3	Ericsson	RRUS 4426 B66		
		1	Raycap	DC6-48-60-18-8F		
		3	Ericsson	RRUS 4478 B14		
		3	Ericsson	RRUS 4478 B5		
		6	Kaelus	DBCT108F1V92-1		
1		Tower Mounts	Platform Mount [LP 301-1]			

3) ANALYSIS PROCEDURE

Table 3 - Documents Provided

Document	Reference	Source
Geotechnical Report	1405752	CCISites
Tower Foundation Drawings	1406237	CCISites
Tower Manufacturer Drawings	1405785	CCISites

3.1) Analysis Method

tnxTower (version 8.0.7.5), a commercially available analysis software package, was used to create a three-dimensional model of the tower and calculate member stresses for various loading cases. Selected output from the analysis is included in Appendix A. When applicable, Crown Castle has calculated and provided the effective area for panel antennas using approved methods following the intent of the TIA-222 Standard.

3.2) Assumptions

- 1) The tower and structures were maintained in accordance with the TIA-222 Standard.

- 2) The configuration of antennas, transmission cables, mounts and other appurtenances are as specified in Tables 1 and 2, and the referenced drawings.

This analysis may be affected if any assumptions are not valid or have been made in error. Tower Engineering Professionals should be notified to determine the effect on the structural integrity of the tower.

4) ANALYSIS RESULTS

Table 4 - Section Capacity (Summary)

Section No.	Elevation (ft)	Component Type	Size	Critical Element	P (lb)	ϕP_{allow} (lb)	% Capacity	Pass / Fail	
L1	150 - 123.29	Pole	TP23.17x17x0.1875	1	-8.81	772.63	74.7	Pass	
L2	123.29 - 87.79	Pole	TP30.86x22.005x0.3125	2	-14.11	1714.16	69.8	Pass	
L3	87.79 - 43.21	Pole	TP40.4x29.2294x0.375	3	-23.81	2698.35	68.1	Pass	
L4	43.21 - 0	Pole	TP49.5x38.3779x0.4375	4	-39.21	3985.57	61.6	Pass	
							Summary		
							Pole (L1)	74.7	Pass
							RATING =	74.7	Pass

Table 5 - Tower Component Stresses vs. Capacity - LC5

Notes	Component	Elevation (ft)	% Capacity	Pass / Fail
1,2	Anchor Rods	-	57.4	Pass
1,2	Base Plate	-	72.8	Pass
1,2	Base Foundation Soil Interaction	-	39.6	Pass
1,2	Base Foundation Structural	-	70.7	Pass

Structure Rating (max from all components) =	74.7%
---	--------------

Notes:


- 1) See additional documentation in "Appendix C - Additional Calculations" for calculations supporting the % capacity listed.
- 2) Rating per TIA-222-H Section 15.5

4.1) Recommendations

- 1) The tower and its foundation have sufficient capacity to carry the proposed load configuration. No modifications are required at this time.

APPENDIX A
TNXTOWER OUTPUT

Section	1	2	3	4
Length (ft)	26.71	38.92	49.00	48.79
Number of Sides	18	18	18	18
Thickness (in)	0.1875	0.3125	0.3750	0.4375
Socket Length (ft)	3.42	4.42	5.58	38.3779
Top Dia (in)	17.0000	22.0050	29.2294	38.3779
Bot Dia (in)	23.1700	30.8600	40.4000	49.5000
Grade			A572-65	
Weight (K)	1.1	3.4	6.8	10.0





MATERIAL STRENGTH

GRADE	Fy	Fu	GRADE	Fy	Fu
A572-65	65 ksi	80 ksi			

TOWER DESIGN NOTES

1. Tower is located in New Haven County, Connecticut.
2. Tower designed for Exposure C to the TIA-222-H Standard.
3. Tower designed for a 125 mph basic wind in accordance with the TIA-222-H Standard.
4. Tower is also designed for a 50 mph basic wind with 1.50 in ice. Ice is considered to increase in thickness with height.
5. Deflections are based upon a 60 mph wind.
6. Tower Risk Category II.
7. Topographic Category 1 with Crest Height of 0.00 ft
8. TOWER RATING: 74.7%



 Tower Engineering Professionals	Tower Engineering Professionals		Job: Waterbury Tower (BU 881534)		
	326 Tryon Rd. Raleigh, NC 27603		Project: TEP No. 218162.496345		
	Phone: (919) 661-6351		Client: Crown Castle	Drawn by: Sam Poindexter	App'd:
	FAX: (919) 661-6350		Code: TIA-222-H	Date: 02/12/21	Scale: NTS
			Path:		Dwg No. E-1

C:\Users\poindexter\Desktop\20191202_L-496345_881534_WATERBURY TOWER_Structural_Analysis\DrawTower\881534_191202_LCS.dwg

tnxTower Tower Engineering Professionals 326 Tryon Rd. Raleigh, NC 27603 Phone: (919) 661-6351 FAX: (919) 661-6350	Job Waterbury Tower (BU 881534)	Page 1 of 13
	Project TEP No. 218162.496345	Date 14:52:46 02/12/21
	Client Crown Castle	Designed by Sam Poindexter

Tower Input Data

The tower is a monopole.

This tower is designed using the TIA-222-H standard.

The following design criteria apply:

Tower is located in New Haven County, Connecticut.

Tower base elevation above sea level: 613.00 ft.

Basic wind speed of 125 mph.

Risk Category II.

Exposure Category C.

Simplified Topographic Factor Procedure for wind speed-up calculations is used.

Topographic Category: 1.

Crest Height: 0.00 ft.

Nominal ice thickness of 1.5000 in.

Ice thickness is considered to increase with height.

Ice density of 56 pcf.

A wind speed of 50 mph is used in combination with ice.

Temperature drop of 50 °F.

Deflections calculated using a wind speed of 60 mph.

A non-linear (P-delta) analysis was used.

Pressures are calculated at each section.

Stress ratio used in pole design is 1.

Tower analysis based on target reliabilities in accordance with Annex S.

Load Modification Factors used: $K_{es}(F_w) = 0.95$, $K_{es}(t_i) = 0.85$.

Local bending stresses due to climbing loads, feed line supports, and appurtenance mounts are not considered.

Options

<ul style="list-style-type: none"> Consider Moments - Legs Consider Moments - Horizontals Consider Moments - Diagonals Use Moment Magnification √ Use Code Stress Ratios √ Use Code Safety Factors - Guys Escalate Ice Always Use Max Kz Use Special Wind Profile Include Bolts In Member Capacity Leg Bolts Are At Top Of Section Secondary Horizontal Braces Leg Use Diamond Inner Bracing (4 Sided) SR Members Have Cut Ends SR Members Are Concentric 	<ul style="list-style-type: none"> Distribute Leg Loads As Uniform Assume Legs Pinned √ Assume Rigid Index Plate √ Use Clear Spans For Wind Area Use Clear Spans For KL/r Retension Guys To Initial Tension √ Bypass Mast Stability Checks √ Use Azimuth Dish Coefficients √ Project Wind Area of Appurt. Autocalc Torque Arm Areas Add IBC .6D+W Combination √ Sort Capacity Reports By Component Triangulate Diamond Inner Bracing Treat Feed Line Bundles As Cylinder Ignore KL/ry For 60 Deg. Angle Legs 	<ul style="list-style-type: none"> Use ASCE 10 X-Brace Ly Rules Calculate Redundant Bracing Forces Ignore Redundant Members in FEA SR Leg Bolts Resist Compression All Leg Panels Have Same Allowable Offset Girt At Foundation √ Consider Feed Line Torque Include Angle Block Shear Check Use TIA-222-H Bracing Resist. Exemption Use TIA-222-H Tension Splice Exemption <li style="text-align: center;">Poles √ Include Shear-Torsion Interaction Always Use Sub-Critical Flow Use Top Mounted Sockets √ Pole Without Linear Attachments Pole With Shroud Or No Appurtenances Outside and Inside Corner Radii Are Known
--	---	---

Tapered Pole Section Geometry

tnxTower Tower Engineering Professionals 326 Tryon Rd. Raleigh, NC 27603 Phone: (919) 661-6351 FAX: (919) 661-6350	Job	Waterbury Tower (BU 881534)	Page	2 of 13
	Project	TEP No. 218162.496345	Date	14:52:46 02/12/21
	Client	Crown Castle	Designed by	Sam Poindexter

Section	Elevation ft	Section Length ft	Splice Length ft	Number of Sides	Top Diameter in	Bottom Diameter in	Wall Thickness in	Bend Radius in	Pole Grade
L1	150.00-123.29	26.71	3.42	18	17.0000	23.1700	0.1875	0.7500	A572-65 (65 ksi)
L2	123.29-87.79	38.92	4.42	18	22.0050	30.8600	0.3125	1.2500	A572-65 (65 ksi)
L3	87.79-43.21	49.00	5.58	18	29.2294	40.4000	0.3750	1.5000	A572-65 (65 ksi)
L4	43.21-0.00	48.79		18	38.3779	49.5000	0.4375	1.7500	A572-65 (65 ksi)

Tapered Pole Properties

Section	Tip Dia. in	Area in ²	I in ⁴	r in	C in	I/C in ³	J in ⁴	It/Q in ²	w in	w/t
L1	17.2333	10.0055	357.3078	5.9684	8.6360	41.3742	715.0858	5.0037	2.6620	14.197
	23.4985	13.6775	912.7198	8.1588	11.7704	77.5439	1826.6405	6.8400	3.7479	19.989
L2	23.0864	21.5162	1279.1518	7.7008	11.1785	114.4293	2559.9867	10.7602	3.3229	10.633
	31.2879	30.2993	3572.0820	10.8444	15.6769	227.8567	7148.8642	15.1525	4.8814	15.62
L3	30.6456	34.3439	3612.5207	10.2433	14.8485	243.2916	7229.7948	17.1752	4.4844	11.958
	40.9654	47.6398	9642.0563	14.2089	20.5232	469.8125	19296.7998	23.8244	6.4504	17.201
L4	40.1941	52.6850	9581.3939	13.4688	19.4960	491.4548	19175.3953	26.3475	5.9845	13.679
	50.1961	68.1294	20719.1270	17.4172	25.1460	823.9532	41465.5167	34.0712	7.9420	18.153

Tower Elevation ft	Gusset Area (per face) ft ²	Gusset Thickness in	Gusset Grade	Adjust. Factor A _f	Adjust. Factor A _r	Weight Mult.	Double Angle Stitch Bolt Spacing Diagonals in	Double Angle Stitch Bolt Spacing Horizontal in	Double Angle Stitch Bolt Spacing Redundants in
L1 150.00-123.29				1	1	1			
L2 123.29-87.79				1	1	1			
L3 87.79-43.21				1	1	1			
L4 43.21-0.00				1	1	1			

Feed Line/Linear Appurtenances - Entered As Round Or Flat

Description	Face or Leg	Allow Shield	Exclude From Torque Calculation	Component Type	Placement ft	Total Number	Number Per Row	Clear Spacing in	Width or Diameter in	Perimeter in	Weight plf

Feed Line/Linear Appurtenances - Entered As Area

Description	Face or Leg	Allow Shield	Exclude From Torque Calculation	Component Type	Placement ft	Total Number	C _{AA}	Weight plf
							ft ² /ft	

tnxTower Tower Engineering Professionals 326 Tryon Rd. Raleigh, NC 27603 Phone: (919) 661-6351 FAX: (919) 661-6350	Job	Waterbury Tower (BU 881534)	Page	3 of 13
	Project	TEP No. 218162.496345	Date	14:52:46 02/12/21
	Client	Crown Castle	Designed by	Sam Poindexter

Description	Face or Leg	Allow Shield	Exclude From Torque Calculation	Component Type	Placement ft	Total Number	CAAA	Weight
							ft ² /ft	plf
CR 50 1873(1-5/8)	C	No	No	Inside Pole	150.00 - 0.00	12	No Ice 1/2" Ice 1" Ice 2" Ice	0.83 0.83 0.83 0.83
WR-VG86ST-BRD(3/4)	C	No	No	Inside Pole	150.00 - 0.00	6	No Ice 1/2" Ice 1" Ice 2" Ice	0.58 0.58 0.58 0.58
FB-L98B-034-XXX(3/8)	C	No	No	Inside Pole	150.00 - 0.00	2	No Ice 1/2" Ice 1" Ice 2" Ice	0.06 0.06 0.06 0.06
2" Flexible Conduit	C	No	No	Inside Pole	150.00 - 0.00	2	No Ice 1/2" Ice 1" Ice 2" Ice	0.34 0.34 0.34 0.34
** EC4-50(1/2)	C	No	No	Inside Pole	140.00 - 0.00	3	No Ice 1/2" Ice 1" Ice 2" Ice	0.16 0.16 0.16 0.16
HB158-21U6S24-xx M_TMO(1-5/8)	C	No	No	Inside Pole	140.00 - 0.00	4	No Ice 1/2" Ice 1" Ice 2" Ice	2.50 2.50 2.50 2.50
* Safety Line 3/8	C	No	No	CaAa (Out Of Face)	150.00 - 0.00	1	No Ice 1/2" Ice 1" Ice 2" Ice	0.22 0.75 1.28 2.34
Step Pegs (5/8" SR) 7-in. w/30" step	C	No	No	CaAa (Out Of Face)	150.00 - 0.00	1	No Ice 1/2" Ice 1" Ice 2" Ice	0.49 1.01 2.07 6.09

Feed Line/Linear Appurtenances Section Areas

Tower Section	Tower Elevation ft	Face	A _R ft ²	A _F ft ²	CAAA In Face ft ²	CAAA Out Face ft ²	Weight K
L1	150.00-123.29	A	0.000	0.000	0.000	0.000	0.00
		B	0.000	0.000	0.000	0.000	0.00
		C	0.000	0.000	0.000	1.936	0.57
L2	123.29-87.79	A	0.000	0.000	0.000	0.000	0.00
		B	0.000	0.000	0.000	0.000	0.00
		C	0.000	0.000	0.000	2.574	0.90
L3	87.79-43.21	A	0.000	0.000	0.000	0.000	0.00
		B	0.000	0.000	0.000	0.000	0.00
		C	0.000	0.000	0.000	3.232	1.13
L4	43.21-0.00	A	0.000	0.000	0.000	0.000	0.00
		B	0.000	0.000	0.000	0.000	0.00
		C	0.000	0.000	0.000	3.133	1.10

tnxTower Tower Engineering Professionals 326 Tryon Rd. Raleigh, NC 27603 Phone: (919) 661-6351 FAX: (919) 661-6350	Job Waterbury Tower (BU 881534)	Page 4 of 13
	Project TEP No. 218162.496345	Date 14:52:46 02/12/21
	Client Crown Castle	Designed by Sam Poindexter

Feed Line/Linear Appurtenances Section Areas - With Ice

Tower Section	Tower Elevation ft	Face or Leg	Ice Thickness in	A _R ft ²	A _F ft ²	C _A A _A In Face ft ²	C _A A _A Out Face ft ²	Weight K
L1	150.00-123.29	A	1.469	0.000	0.000	0.000	0.000	0.00
		B		0.000	0.000	0.000	0.000	0.00
		C		0.000	0.000	0.000	17.630	0.71
L2	123.29-87.79	A	1.431	0.000	0.000	0.000	0.000	0.00
		B		0.000	0.000	0.000	0.000	0.00
		C		0.000	0.000	0.000	23.432	1.08
L3	87.79-43.21	A	1.364	0.000	0.000	0.000	0.000	0.00
		B		0.000	0.000	0.000	0.000	0.00
		C		0.000	0.000	0.000	28.753	1.35
L4	43.21-0.00	A	1.222	0.000	0.000	0.000	0.000	0.00
		B		0.000	0.000	0.000	0.000	0.00
		C		0.000	0.000	0.000	26.709	1.29

Feed Line Center of Pressure

Section	Elevation ft	CP _X in	CP _Z in	CP _X Ice in	CP _Z Ice in
L1	150.00-123.29	-0.5523	0.3189	-2.0530	1.1853
L2	123.29-87.79	-0.5614	0.3241	-2.2451	1.2962
L3	87.79-43.21	-0.5679	0.3279	-2.3613	1.3633
L4	43.21-0.00	-0.5723	0.3304	-2.3933	1.3818

Note: For pole sections, center of pressure calculations do not consider feed line shielding.

Discrete Tower Loads

Description	Face or Leg	Offset Type	Offsets: Horz Lateral Vert ft ft ft	Azimuth Adjustment °	Placement ft	C _A A _A Front ft ²	C _A A _A Side ft ²	Weight K	
800 10121	A	From Centroid-Le g	4.00	0.0000	150.00	No Ice	3.74	2.17	0.05
			0.00			1/2" Ice	4.18	2.58	0.08
			1.00			1" Ice	4.63	3.00	0.12
						2" Ice	5.57	3.88	0.21
800 10121	B	From Centroid-Le g	4.00	0.0000	150.00	No Ice	3.74	2.17	0.05
			0.00			1/2" Ice	4.18	2.58	0.08
			1.00			1" Ice	4.63	3.00	0.12
						2" Ice	5.57	3.88	0.21
800 10121	C	From Centroid-Le g	4.00	0.0000	150.00	No Ice	3.74	2.17	0.05
			0.00			1/2" Ice	4.18	2.58	0.08
			1.00			1" Ice	4.63	3.00	0.12
						2" Ice	5.57	3.88	0.21

tnxTower Tower Engineering Professionals 326 Tryon Rd. Raleigh, NC 27603 Phone: (919) 661-6351 FAX: (919) 661-6350	Job	Waterbury Tower (BU 881534)	Page	5 of 13
	Project	TEP No. 218162.496345	Date	14:52:46 02/12/21
	Client	Crown Castle	Designed by	Sam Poindexter

<i>Description</i>	<i>Face or Leg</i>	<i>Offset Type</i>	<i>Offsets: Horz Lateral Vert</i> <i>ft ft ft</i>	<i>Azimuth Adjustment</i> <i>°</i>	<i>Placement</i> <i>ft</i>	<i>CAA Front</i> <i>ft²</i>	<i>CAA Side</i> <i>ft²</i>	<i>Weight</i> <i>K</i>	
80010966	A	From Centroid-Le g	4.00 0.00 0.00	0.0000	150.00	No Ice 1/2" Ice 1" Ice 2" Ice	14.59 15.46 16.35 18.16	5.04 5.81 6.59 8.21	0.13 0.22 0.32 0.54
80010966	B	From Centroid-Le g	4.00 0.00 0.00	0.0000	150.00	No Ice 1/2" Ice 1" Ice 2" Ice	14.59 15.46 16.35 18.16	5.04 5.81 6.59 8.21	0.13 0.22 0.32 0.54
TPA-65R-LCUUUU-H8	A	From Centroid-Le g	4.00 0.00 1.00	0.0000	150.00	No Ice 1/2" Ice 1" Ice 2" Ice	11.87 12.82 13.77 15.74	7.02 7.91 8.82 10.68	0.08 0.16 0.25 0.45
TPA-65R-LCUUUU-H8	B	From Centroid-Le g	4.00 0.00 1.00	0.0000	150.00	No Ice 1/2" Ice 1" Ice 2" Ice	11.87 12.82 13.77 15.74	7.02 7.91 8.82 10.68	0.08 0.16 0.25 0.45
OPA-65R-LCUU-H8	A	From Centroid-Le g	4.00 0.00 0.00	0.0000	150.00	No Ice 1/2" Ice 1" Ice 2" Ice	11.95 12.92 13.90 15.92	6.03 6.93 7.85 9.74	0.07 0.14 0.22 0.41
OPA-65R-LCUU-H8	B	From Centroid-Le g	4.00 0.00 0.00	0.0000	150.00	No Ice 1/2" Ice 1" Ice 2" Ice	11.95 12.92 13.90 15.92	6.03 6.93 7.85 9.74	0.07 0.14 0.22 0.41
80010965K	C	From Centroid-Le g	4.00 0.00 0.00	0.0000	150.00	No Ice 1/2" Ice 1" Ice 2" Ice	12.23 13.00 13.79 15.41	4.21 4.88 5.57 6.99	0.13 0.21 0.29 0.48
OPA-65R-LCUU-H6	C	From Centroid-Le g	4.00 0.00 1.00	0.0000	150.00	No Ice 1/2" Ice 1" Ice 2" Ice	9.20 9.97 10.76 12.39	4.63 5.34 6.07 7.57	0.08 0.14 0.20 0.35
QS66512-2	C	From Centroid-Le g	4.00 0.00 1.00	0.0000	150.00	No Ice 1/2" Ice 1" Ice 2" Ice	4.01 4.41 4.81 5.65	3.37 3.76 4.15 4.97	0.11 0.17 0.23 0.38
(3) LGP21401	B	From Centroid-Le g	4.00 0.00 0.00	0.0000	150.00	No Ice 1/2" Ice 1" Ice 2" Ice	1.10 1.24 1.38 1.69	0.21 0.27 0.35 0.52	0.01 0.02 0.03 0.05
LGP21401	A	From Centroid-Le g	4.00 0.00 1.00	0.0000	150.00	No Ice 1/2" Ice 1" Ice 2" Ice	1.10 1.24 1.38 1.69	0.21 0.27 0.35 0.52	0.01 0.02 0.03 0.05
LGP21401	B	From Centroid-Le g	4.00 0.00 1.00	0.0000	150.00	No Ice 1/2" Ice 1" Ice 2" Ice	1.10 1.24 1.38 1.69	0.21 0.27 0.35 0.52	0.01 0.02 0.03 0.05
LGP21401	C	From Centroid-Le g	4.00 0.00 1.00	0.0000	150.00	No Ice 1/2" Ice 1" Ice 2" Ice	1.10 1.24 1.38 1.69	0.21 0.27 0.35 0.52	0.01 0.02 0.03 0.05
RRUS 4426 B66	A	From Centroid-Le g	4.00 0.00 0.00	0.0000	150.00	No Ice 1/2" Ice 1" Ice 2" Ice	1.64 1.80 1.97 2.33	0.73 0.84 0.97 1.24	0.05 0.06 0.08 0.11
RRUS 4426 B66	B	From	4.00	0.0000	150.00	No Ice	1.64	0.73	0.05

tnxTower Tower Engineering Professionals 326 Tryon Rd. Raleigh, NC 27603 Phone: (919) 661-6351 FAX: (919) 661-6350	Job	Waterbury Tower (BU 881534)	Page	6 of 13
	Project	TEP No. 218162.496345	Date	14:52:46 02/12/21
	Client	Crown Castle	Designed by	Sam Poindexter

Description	Face or Leg	Offset Type	Offsets:		Azimuth Adjustment	Placement	CAAA Front	CAAA Side	Weight	
			Horz Lateral	Vert						°
RRUS 4426 B66	C	Centroid-Le g	0.00	0.00	0.0000	150.00	1/2" Ice	1.80	0.84	0.06
			4.00	0.00			1" Ice	1.97	0.97	0.08
			0.00	0.00			2" Ice	2.33	1.24	0.11
RRUS A2 MODULE	A	From Centroid-Le g	4.00	0.00	0.0000	150.00	No Ice	1.64	0.73	0.05
			0.00	0.00			1/2" Ice	1.80	0.84	0.06
			1.00	1.00			1" Ice	1.97	0.97	0.08
RRUS A2 MODULE	B	From Centroid-Le g	4.00	0.00	0.0000	150.00	2" Ice	2.33	1.24	0.11
			0.00	0.00			No Ice	1.60	0.38	0.02
			1.00	1.00			1/2" Ice	1.76	0.47	0.03
RRUS A2 MODULE	C	From Centroid-Le g	4.00	0.00	0.0000	150.00	1" Ice	1.92	0.57	0.04
			0.00	0.00			2" Ice	2.28	0.78	0.08
			1.00	1.00			No Ice	1.60	0.38	0.02
RRUS 12 W/O SOLAR SHIELD	A	From Centroid-Le g	4.00	0.00	0.0000	150.00	1/2" Ice	1.76	0.47	0.03
			0.00	0.00			1" Ice	1.92	0.57	0.04
			1.00	1.00			2" Ice	2.28	0.78	0.08
RRUS 12 W/O SOLAR SHIELD	B	From Centroid-Le g	4.00	0.00	0.0000	150.00	No Ice	1.60	0.38	0.02
			0.00	0.00			1/2" Ice	1.76	0.47	0.03
			1.00	1.00			1" Ice	1.92	0.57	0.04
RRUS 12 W/O SOLAR SHIELD	C	From Centroid-Le g	4.00	0.00	0.0000	150.00	2" Ice	2.28	0.78	0.08
			0.00	0.00			No Ice	1.60	0.38	0.02
			1.00	1.00			1/2" Ice	1.76	0.47	0.03
RRUS 11	A	From Centroid-Le g	4.00	0.00	0.0000	150.00	1" Ice	1.92	0.57	0.04
			0.00	0.00			2" Ice	2.28	0.78	0.08
			1.00	1.00			No Ice	1.60	0.38	0.02
RRUS 11	B	From Centroid-Le g	4.00	0.00	0.0000	150.00	1/2" Ice	1.76	0.47	0.03
			0.00	0.00			1" Ice	1.92	0.57	0.04
			1.00	1.00			2" Ice	2.28	0.78	0.08
RRUS 11	C	From Centroid-Le g	4.00	0.00	0.0000	150.00	No Ice	1.60	0.38	0.02
			0.00	0.00			1/2" Ice	1.76	0.47	0.03
			1.00	1.00			1" Ice	1.92	0.57	0.04
DC6-48-60-18-8F	C	From Centroid-Le g	4.00	0.00	0.0000	150.00	2" Ice	2.28	0.78	0.08
			0.00	0.00			No Ice	1.60	0.38	0.02
			1.00	1.00			1/2" Ice	1.76	0.47	0.03
DC6-48-60-18-8F	A	From Centroid-Le g	4.00	0.00	0.0000	150.00	1" Ice	1.92	0.57	0.04
			0.00	0.00			2" Ice	2.28	0.78	0.08
			0.00	0.00			No Ice	1.60	0.38	0.02
DC6-48-60-18-8F	B	From Centroid-Le g	4.00	0.00	0.0000	150.00	1/2" Ice	1.76	0.47	0.03
			0.00	0.00			1" Ice	1.92	0.57	0.04
			1.00	1.00			2" Ice	2.28	0.78	0.08
RRUS 32	A	From Centroid-Le g	4.00	0.00	0.0000	150.00	No Ice	1.60	0.38	0.02
			0.00	0.00			1/2" Ice	1.76	0.47	0.03
			0.00	0.00			1" Ice	1.92	0.57	0.04

tnxTower Tower Engineering Professionals 326 Tryon Rd. Raleigh, NC 27603 Phone: (919) 661-6351 FAX: (919) 661-6350	Job		Waterbury Tower (BU 881534)		Page		7 of 13	
	Project		TEP No. 218162.496345		Date		14:52:46 02/12/21	
	Client		Crown Castle		Designed by		Sam Poindexter	

Description	Face or Leg	Offset Type	Offsets:		Azimuth Adjustment	Placement	CAAA Front	CAAA Side	Weight
			Horz	Vert					
			ft	ft	°	ft	ft ²	ft ²	K
		g	1.00			1" Ice	3.32	2.17	0.10
						2" Ice	3.81	2.58	0.16
RRUS 32	B	From Centroid-Le	4.00	0.0000	150.00	No Ice	2.86	1.78	0.06
		g	0.00			1/2" Ice	3.08	1.97	0.08
			1.00			1" Ice	3.32	2.17	0.10
						2" Ice	3.81	2.58	0.16
RRUS 32	C	From Centroid-Le	4.00	0.0000	150.00	No Ice	2.86	1.78	0.06
		g	0.00			1/2" Ice	3.08	1.97	0.08
			1.00			1" Ice	3.32	2.17	0.10
						2" Ice	3.81	2.58	0.16
(3) RRUS 4478 B14	A	From Centroid-Le	4.00	0.0000	150.00	No Ice	1.84	1.06	0.06
		g	0.00			1/2" Ice	2.01	1.20	0.08
			0.00			1" Ice	2.19	1.34	0.09
						2" Ice	2.57	1.66	0.14
(2) TPX-070821	A	From Centroid-Le	4.00	0.0000	150.00	No Ice	0.47	0.10	0.01
		g	0.00			1/2" Ice	0.56	0.15	0.01
			1.00			1" Ice	0.66	0.20	0.02
						2" Ice	0.87	0.33	0.03
(4) TPX-070821	B	From Centroid-Le	4.00	0.0000	150.00	No Ice	0.47	0.10	0.01
		g	0.00			1/2" Ice	0.56	0.15	0.01
			1.00			1" Ice	0.66	0.20	0.02
						2" Ice	0.87	0.33	0.03
RRUS 4478 B5	A	From Centroid-Le	4.00	0.0000	150.00	No Ice	1.84	1.06	0.06
		g	0.00			1/2" Ice	2.01	1.20	0.08
			0.00			1" Ice	2.19	1.34	0.09
						2" Ice	2.57	1.66	0.14
RRUS 4478 B5	B	From Centroid-Le	4.00	0.0000	150.00	No Ice	1.84	1.06	0.06
		g	0.00			1/2" Ice	2.01	1.20	0.08
			0.00			1" Ice	2.19	1.34	0.09
						2" Ice	2.57	1.66	0.14
RRUS 4478 B5	C	From Centroid-Le	4.00	0.0000	150.00	No Ice	1.84	1.06	0.06
		g	0.00			1/2" Ice	2.01	1.20	0.08
			0.00			1" Ice	2.19	1.34	0.09
						2" Ice	2.57	1.66	0.14
(6) DBCT108F1V92-1	C	From Centroid-Le	4.00	0.0000	150.00	No Ice	0.64	0.60	0.03
		g	0.00			1/2" Ice	0.74	0.71	0.04
			0.00			1" Ice	0.85	0.81	0.04
						2" Ice	1.09	1.05	0.07
2.375" x 6' mount pipe	A	From Leg	0.00	0.0000	150.00	No Ice	1.43	1.43	0.02
			0.00			1/2" Ice	1.92	1.92	0.03
			0.00			1" Ice	2.29	2.29	0.05
						2" Ice	3.06	3.06	0.09
2.375" x 6' mount pipe	B	From Leg	0.00	0.0000	150.00	No Ice	1.43	1.43	0.02
			0.00			1/2" Ice	1.92	1.92	0.03
			0.00			1" Ice	2.29	2.29	0.05
						2" Ice	3.06	3.06	0.09
2.375" x 6' mount pipe	C	From Leg	0.00	0.0000	150.00	No Ice	1.43	1.43	0.02
			0.00			1/2" Ice	1.92	1.92	0.03
			0.00			1" Ice	2.29	2.29	0.05
						2" Ice	3.06	3.06	0.09
Platform Mount [LP 301-1]	C	None		0.0000	150.00	No Ice	23.81	23.81	1.59
						1/2" Ice	30.24	30.24	2.10
						1" Ice	36.33	36.33	2.73
						2" Ice	48.05	48.05	4.34
140									
TIMING 2000	C	From Centroid-Le	4.00	0.0000	140.00	No Ice	0.13	0.11	0.00
			0.00			1/2" Ice	0.18	0.15	0.00

tnxTower Tower Engineering Professionals 326 Tryon Rd. Raleigh, NC 27603 Phone: (919) 661-6351 FAX: (919) 661-6350	Job	Waterbury Tower (BU 881534)	Page	8 of 13
	Project	TEP No. 218162.496345	Date	14:52:46 02/12/21
	Client	Crown Castle	Designed by	Sam Poindexter

Description	Face or Leg	Offset Type	Offsets:		Azimuth Adjustment	Placement	CAAA Front	CAAA Side	Weight
			Horz Lateral	Vert					
		g	2.00						
APX16DWV-16DWV-S-E-A 20	A	From Centroid-Le g	4.00 0.00 0.00	0.0000	140.00	1" Ice 2" Ice No Ice 1/2" Ice 1" Ice 2" Ice	0.24 0.37 6.26 6.85 7.46 8.72	0.20 0.33 1.50 2.00 2.52 3.62	0.01 0.01 0.04 0.07 0.11 0.20
APX16DWV-16DWV-S-E-A 20	B	From Centroid-Le g	4.00 0.00 0.00	0.0000	140.00	No Ice 1/2" Ice 1" Ice 2" Ice	6.26 6.85 7.46 8.72	1.50 2.00 2.52 3.62	0.04 0.07 0.11 0.20
APX16DWV-16DWV-S-E-A 20	C	From Centroid-Le g	4.00 0.00 0.00	0.0000	140.00	No Ice 1/2" Ice 1" Ice 2" Ice	6.26 6.85 7.46 8.72	1.50 2.00 2.52 3.62	0.04 0.07 0.11 0.20
APXVAALL24_43-U-NA20 _TMO	A	From Centroid-Le g	4.00 0.00 0.00	0.0000	140.00	No Ice 1/2" Ice 1" Ice 2" Ice	14.67 15.43 16.21 17.81	5.32 5.99 6.68 8.08	0.15 0.26 0.38 0.65
APXVAALL24_43-U-NA20 _TMO	B	From Centroid-Le g	4.00 0.00 0.00	0.0000	140.00	No Ice 1/2" Ice 1" Ice 2" Ice	14.67 15.43 16.21 17.81	5.32 5.99 6.68 8.08	0.15 0.26 0.38 0.65
APXVAALL24_43-U-NA20 _TMO	C	From Centroid-Le g	4.00 0.00 0.00	0.0000	140.00	No Ice 1/2" Ice 1" Ice 2" Ice	14.67 15.43 16.21 17.81	5.32 5.99 6.68 8.08	0.15 0.26 0.38 0.65
AIR6449 B41_T-MOBILE	A	From Centroid-Le g	4.00 0.00 0.00	0.0000	140.00	No Ice 1/2" Ice 1" Ice 2" Ice	5.66 5.96 6.27 6.91	2.48 2.70 2.94 3.43	0.11 0.15 0.20 0.30
AIR6449 B41_T-MOBILE	B	From Centroid-Le g	4.00 0.00 0.00	0.0000	140.00	No Ice 1/2" Ice 1" Ice 2" Ice	5.66 5.96 6.27 6.91	2.48 2.70 2.94 3.43	0.11 0.15 0.20 0.30
AIR6449 B41_T-MOBILE	C	From Centroid-Le g	4.00 0.00 0.00	0.0000	140.00	No Ice 1/2" Ice 1" Ice 2" Ice	5.66 5.96 6.27 6.91	2.48 2.70 2.94 3.43	0.11 0.15 0.20 0.30
RADIO 4415 B66A_CCIV3	A	From Centroid-Le g	4.00 0.00 0.00	0.0000	140.00	No Ice 1/2" Ice 1" Ice 2" Ice	1.64 1.80 1.97 2.32	0.68 0.79 0.91 1.18	0.05 0.06 0.07 0.11
RADIO 4415 B66A_CCIV3	B	From Centroid-Le g	4.00 0.00 0.00	0.0000	140.00	No Ice 1/2" Ice 1" Ice 2" Ice	1.64 1.80 1.97 2.32	0.68 0.79 0.91 1.18	0.05 0.06 0.07 0.11
RADIO 4415 B66A_CCIV3	C	From Centroid-Le g	4.00 0.00 0.00	0.0000	140.00	No Ice 1/2" Ice 1" Ice 2" Ice	1.64 1.80 1.97 2.32	0.68 0.79 0.91 1.18	0.05 0.06 0.07 0.11
RADIO 4424 B25_TMO	A	From Centroid-Le g	4.00 0.00 0.00	0.0000	140.00	No Ice 1/2" Ice 1" Ice 2" Ice	2.05 2.23 2.42 2.81	1.61 1.77 1.94 2.30	0.09 0.11 0.13 0.19
RADIO 4424 B25_TMO	B	From Centroid-Le g	4.00 0.00 0.00	0.0000	140.00	No Ice 1/2" Ice 1" Ice	2.05 2.23 2.42	1.61 1.77 1.94	0.09 0.11 0.13

tnxTower Tower Engineering Professionals 326 Tryon Rd. Raleigh, NC 27603 Phone: (919) 661-6351 FAX: (919) 661-6350	Job Waterbury Tower (BU 881534)	Page 9 of 13
	Project TEP No. 218162.496345	Date 14:52:46 02/12/21
	Client Crown Castle	Designed by Sam Poindexter

Description	Face or Leg	Offset Type	Offsets:		Azimuth Adjustment	Placement	CAAA		Weight
			Horz Lateral	Vert			Front	Side	
			ft	ft	°	ft	ft ²	ft ²	K
RADIO 4424 B25_TMO	C	From Centroid-Le g	4.00	0.0000	140.00	2" Ice	2.81	2.30	0.19
			0.00	0.0000		No Ice	2.05	1.61	0.09
			0.00	0.0000		1/2" Ice	2.23	1.77	0.11
			0.00	0.0000		1" Ice	2.42	1.94	0.13
RADIO 4449 B71 B85A_T-MOBILE	A	From Centroid-Le g	4.00	0.0000	140.00	2" Ice	2.81	2.30	0.19
			0.00	0.0000		No Ice	1.97	1.59	0.07
			0.00	0.0000		1/2" Ice	2.15	1.75	0.09
			0.00	0.0000		1" Ice	2.33	1.92	0.12
RADIO 4449 B71 B85A_T-MOBILE	B	From Centroid-Le g	4.00	0.0000	140.00	2" Ice	2.72	2.28	0.17
			0.00	0.0000		No Ice	1.97	1.59	0.07
			0.00	0.0000		1/2" Ice	2.15	1.75	0.09
			0.00	0.0000		1" Ice	2.33	1.92	0.12
RADIO 4449 B71 B85A_T-MOBILE	C	From Centroid-Le g	4.00	0.0000	140.00	2" Ice	2.72	2.28	0.17
			0.00	0.0000		No Ice	1.97	1.59	0.07
			0.00	0.0000		1/2" Ice	2.15	1.75	0.09
			0.00	0.0000		1" Ice	2.33	1.92	0.12
HORIZON COMPACT	A	From Centroid-Le g	4.00	0.0000	140.00	2" Ice	2.72	2.28	0.17
			0.00	0.0000		No Ice	0.72	0.37	0.01
			0.00	0.0000		1/2" Ice	0.83	0.45	0.02
			0.00	0.0000		1" Ice	0.94	0.54	0.03
HORIZON COMPACT	B	From Centroid-Le g	4.00	0.0000	140.00	2" Ice	1.19	0.74	0.05
			0.00	0.0000		No Ice	0.72	0.37	0.01
			0.00	0.0000		1/2" Ice	0.83	0.45	0.02
			0.00	0.0000		1" Ice	0.94	0.54	0.03
Platform Mount [LP 301-1_KCKR]	C	None		0.0000	140.00	2" Ice	1.19	0.74	0.05
				0.0000		No Ice	35.03	35.03	1.86
				0.0000		1/2" Ice	44.46	44.46	2.52
				0.0000		1" Ice	53.72	53.72	3.33
						2" Ice	72.29	72.29	5.42

**

Dishes

Description	Face or Leg	Dish Type	Offset Type	Offsets:		Azimuth Adjustment	3 dB Beam Width	Elevation	Outside Diameter	Aperture Area	Weight
				Horz Lateral	Vert						
			ft	ft	°	°	ft	ft	ft ²	K	
VHLP2-11	A	Paraboloid w/Shroud (HP)	From Centroid	4.00	12.0000	140.00		2.17	No Ice	3.72	0.03
			-Leg	-6.00	1/2" Ice				4.01	0.05	
				2.00	1" Ice				4.30	0.07	
					2" Ice				4.88	0.11	
VHLP2-11	B	Paraboloid w/Shroud (HP)	From Centroid	4.00	83.0000	140.00		2.17	No Ice	3.72	0.03
			-Leg	6.00	1/2" Ice				4.01	0.05	
				2.00	1" Ice				4.30	0.07	
					2" Ice				4.88	0.11	

<p>tnxTower</p> <p><i>Tower Engineering Professionals</i> 326 Tryon Rd. Raleigh, NC 27603 Phone: (919) 661-6351 FAX: (919) 661-6350</p>	Job Waterbury Tower (BU 881534)	Page 10 of 13
	Project TEP No. 218162.496345	Date 14:52:46 02/12/21
	Client Crown Castle	Designed by Sam Poindexter

Load Combinations

Comb. No.	Description
1	Dead Only
2	1.2 Dead+1.0 Wind 0 deg - No Ice
3	0.9 Dead+1.0 Wind 0 deg - No Ice
4	1.2 Dead+1.0 Wind 30 deg - No Ice
5	0.9 Dead+1.0 Wind 30 deg - No Ice
6	1.2 Dead+1.0 Wind 60 deg - No Ice
7	0.9 Dead+1.0 Wind 60 deg - No Ice
8	1.2 Dead+1.0 Wind 90 deg - No Ice
9	0.9 Dead+1.0 Wind 90 deg - No Ice
10	1.2 Dead+1.0 Wind 120 deg - No Ice
11	0.9 Dead+1.0 Wind 120 deg - No Ice
12	1.2 Dead+1.0 Wind 150 deg - No Ice
13	0.9 Dead+1.0 Wind 150 deg - No Ice
14	1.2 Dead+1.0 Wind 180 deg - No Ice
15	0.9 Dead+1.0 Wind 180 deg - No Ice
16	1.2 Dead+1.0 Wind 210 deg - No Ice
17	0.9 Dead+1.0 Wind 210 deg - No Ice
18	1.2 Dead+1.0 Wind 240 deg - No Ice
19	0.9 Dead+1.0 Wind 240 deg - No Ice
20	1.2 Dead+1.0 Wind 270 deg - No Ice
21	0.9 Dead+1.0 Wind 270 deg - No Ice
22	1.2 Dead+1.0 Wind 300 deg - No Ice
23	0.9 Dead+1.0 Wind 300 deg - No Ice
24	1.2 Dead+1.0 Wind 330 deg - No Ice
25	0.9 Dead+1.0 Wind 330 deg - No Ice
26	1.2 Dead+1.0 Ice+1.0 Temp
27	1.2 Dead+1.0 Wind 0 deg+1.0 Ice+1.0 Temp
28	1.2 Dead+1.0 Wind 30 deg+1.0 Ice+1.0 Temp
29	1.2 Dead+1.0 Wind 60 deg+1.0 Ice+1.0 Temp
30	1.2 Dead+1.0 Wind 90 deg+1.0 Ice+1.0 Temp
31	1.2 Dead+1.0 Wind 120 deg+1.0 Ice+1.0 Temp
32	1.2 Dead+1.0 Wind 150 deg+1.0 Ice+1.0 Temp
33	1.2 Dead+1.0 Wind 180 deg+1.0 Ice+1.0 Temp
34	1.2 Dead+1.0 Wind 210 deg+1.0 Ice+1.0 Temp
35	1.2 Dead+1.0 Wind 240 deg+1.0 Ice+1.0 Temp
36	1.2 Dead+1.0 Wind 270 deg+1.0 Ice+1.0 Temp
37	1.2 Dead+1.0 Wind 300 deg+1.0 Ice+1.0 Temp
38	1.2 Dead+1.0 Wind 330 deg+1.0 Ice+1.0 Temp
39	Dead+Wind 0 deg - Service
40	Dead+Wind 30 deg - Service
41	Dead+Wind 60 deg - Service
42	Dead+Wind 90 deg - Service
43	Dead+Wind 120 deg - Service
44	Dead+Wind 150 deg - Service
45	Dead+Wind 180 deg - Service
46	Dead+Wind 210 deg - Service
47	Dead+Wind 240 deg - Service
48	Dead+Wind 270 deg - Service
49	Dead+Wind 300 deg - Service
50	Dead+Wind 330 deg - Service

Maximum Tower Deflections - Service Wind

Section No.	Elevation ft	Horz. Deflection in	Gov. Load Comb.	Tilt °	Twist °

tnxTower Tower Engineering Professionals 326 Tryon Rd. Raleigh, NC 27603 Phone: (919) 661-6351 FAX: (919) 661-6350	Job Waterbury Tower (BU 881534)	Page 11 of 13
	Project TEP No. 218162.496345	Date 14:52:46 02/12/21
	Client Crown Castle	Designed by Sam Poindexter

Section No.	Elevation ft	Horz. Deflection in	Gov. Load Comb.	Tilt °	Twist °
L1	150 - 123.29	27.656	50	1.9172	0.0050
L2	126.71 - 87.79	18.861	50	1.6032	0.0024
L3	92.21 - 43.21	9.213	50	1.0374	0.0010
L4	48.79 - 0	2.372	50	0.4595	0.0003

Critical Deflections and Radius of Curvature - Service Wind

Elevation ft	Appurtenance	Gov. Load Comb.	Deflection in	Tilt °	Twist °	Radius of Curvature ft
150.00	800 10121	50	27.656	1.9172	0.0050	13334
142.00	VHLP2-11	50	24.520	1.8146	0.0040	8333
140.00	TIMING 2000	50	23.747	1.7885	0.0038	6667

Maximum Tower Deflections - Design Wind

Section No.	Elevation ft	Horz. Deflection in	Gov. Load Comb.	Tilt °	Twist °
L1	150 - 123.29	127.789	24	8.8663	0.0226
L2	126.71 - 87.79	87.301	12	7.4318	0.0110
L3	92.21 - 43.21	42.715	12	4.8137	0.0045
L4	48.79 - 0	11.005	12	2.1325	0.0014

Critical Deflections and Radius of Curvature - Design Wind

Elevation ft	Appurtenance	Gov. Load Comb.	Deflection in	Tilt °	Twist °	Radius of Curvature ft
150.00	800 10121	24	127.789	8.8663	0.0226	3035
142.00	VHLP2-11	24	113.360	8.3990	0.0181	1896
140.00	TIMING 2000	24	109.801	8.2798	0.0171	1516

Compression Checks

Pole Design Data

Section No.	Elevation ft	Size	L ft	L _u ft	Kl/r	A in ²	P _u K	φP _n K	Ratio $\frac{P_u}{\phi P_n}$
L1	150 - 123.29 (1)	TP23.17x17x0.1875	26.71	0.00	0.0	13.2073	-8.81	772.63	0.011

tnxTower Tower Engineering Professionals 326 Tryon Rd. Raleigh, NC 27603 Phone: (919) 661-6351 FAX: (919) 661-6350	Job	Waterbury Tower (BU 881534)	Page	12 of 13
	Project	TEP No. 218162.496345	Date	14:52:46 02/12/21
	Client	Crown Castle	Designed by	Sam Poindexter

Section No.	Elevation ft	Size	L ft	L _u ft	Kl/r	A in ²	P _u K	φP _n K	Ratio $\frac{P_u}{\phi P_n}$
L2	123.29 - 87.79 (2)	TP30.86x22.005x0.3125	38.92	0.00	0.0	29.3018	-14.11	1714.16	0.008
L3	87.79 - 43.21 (3)	TP40.4x29.2294x0.375	49.00	0.00	0.0	46.1257	-23.81	2698.35	0.009
L4	43.21 - 0 (4)	TP49.5x38.3779x0.4375	48.79	0.00	0.0	68.1294	-39.21	3985.57	0.010

Pole Bending Design Data

Section No.	Elevation ft	Size	M _{ux} kip-ft	φM _{nx} kip-ft	Ratio $\frac{M_{ux}}{\phi M_{nx}}$	M _{uy} kip-ft	φM _{ny} kip-ft	Ratio $\frac{M_{uy}}{\phi M_{ny}}$
L1	150 - 123.29 (1)	TP23.17x17x0.1875	307.94	421.38	0.731	0.00	421.38	0.000
L2	123.29 - 87.79 (2)	TP30.86x22.005x0.3125	908.52	1318.91	0.689	0.00	1318.91	0.000
L3	87.79 - 43.21 (3)	TP40.4x29.2294x0.375	1793.23	2669.35	0.672	0.00	2669.35	0.000
L4	43.21 - 0 (4)	TP49.5x38.3779x0.4375	2957.53	4882.80	0.606	0.00	4882.80	0.000

Pole Shear Design Data

Section No.	Elevation ft	Size	Actual V _u K	φV _n K	Ratio $\frac{V_u}{\phi V_n}$	Actual T _u kip-ft	φT _n kip-ft	Ratio $\frac{T_u}{\phi T_n}$
L1	150 - 123.29 (1)	TP23.17x17x0.1875	16.17	231.79	0.070	0.04	450.48	0.000
L2	123.29 - 87.79 (2)	TP30.86x22.005x0.3125	18.66	514.25	0.036	0.17	1330.43	0.000
L3	87.79 - 43.21 (3)	TP40.4x29.2294x0.375	22.07	809.51	0.027	0.91	2747.28	0.000
L4	43.21 - 0 (4)	TP49.5x38.3779x0.4375	25.47	1195.67	0.021	1.14	5137.38	0.000

Pole Interaction Design Data


Section No.	Elevation ft	Ratio $\frac{P_u}{\phi P_n}$	Ratio $\frac{M_{ux}}{\phi M_{nx}}$	Ratio $\frac{M_{uy}}{\phi M_{ny}}$	Ratio $\frac{V_u}{\phi V_n}$	Ratio $\frac{T_u}{\phi T_n}$	Comb. Stress Ratio	Allow. Stress Ratio	Criteria
L1	150 - 123.29 (1)	0.011	0.731	0.000	0.070	0.000	0.747	1.000	4.8.2
L2	123.29 - 87.79 (2)	0.008	0.689	0.000	0.036	0.000	0.698	1.000	4.8.2
L3	87.79 - 43.21 (3)	0.009	0.672	0.000	0.027	0.000	0.681	1.000	4.8.2
L4	43.21 - 0 (4)	0.010	0.606	0.000	0.021	0.000	0.616	1.000	4.8.2

tnxTower Tower Engineering Professionals 326 Tryon Rd. Raleigh, NC 27603 Phone: (919) 661-6351 FAX: (919) 661-6350	Job Waterbury Tower (BU 881534)	Page 13 of 13
	Project TEP No. 218162.496345	Date 14:52:46 02/12/21
	Client Crown Castle	Designed by Sam Poindexter




Section Capacity Table

Section No.	Elevation ft	Component Type	Size	Critical Element	P K	ϕP_{allow} K	% Capacity	Pass Fail
L1	150 - 123.29	Pole	TP23.17x17x0.1875	1	-8.81	772.63	74.7	Pass
L2	123.29 - 87.79	Pole	TP30.86x22.005x0.3125	2	-14.11	1714.16	69.8	Pass
L3	87.79 - 43.21	Pole	TP40.4x29.2294x0.375	3	-23.81	2698.35	68.1	Pass
L4	43.21 - 0	Pole	TP49.5x38.3779x0.4375	4	-39.21	3985.57	61.6	Pass
Summary								
Pole (L1)							74.7	Pass
RATING =							74.7	Pass

APPENDIX B
BASE LEVEL DRAWING



(PROPOSED EQUIPMENT CONFIGURATION)
(3) 1/2" TO 140 FT LEVEL
(4) 1-5/8" TO 140 FT LEVEL



(OTHER CONSIDERED EQUIPMENT INSTALLED—IN
CONDUIT)
(2) 3/8" TO 150 FT LEVEL
(6) 3/4" TO 150 FT LEVEL
(OTHER CONSIDERED EQUIPMENT)
(12) 1-5/8" TO 150 FT LEVEL


APPENDIX C
ADDITIONAL CALCULATIONS

ASCE 7 Hazards Report

Address:
No Address at This Location

Standard: ASCE/SEI 7-10
Risk Category: II
Soil Class: D - Stiff Soil

Elevation: 612.55 ft (NAVD 88)
Latitude: 41.534333
Longitude: -72.969



Wind

Results:

Wind Speed:	122 Vmph
10-year MRI	76 Vmph
25-year MRI	86 Vmph
50-year MRI	92 Vmph
100-year MRI	99 Vmph

Wind Speed Updated Per Local Jurisdictional Requirements

Data Source: ASCE/SEI 7-10, Fig. 26.5-1A and Figs. CC-1–CC-4, incorporating errata of March 12, 2014

Date Accessed: Thu Feb 11 2021

Value provided is 3-second gust wind speeds at 33 ft above ground for Exposure C Category, based on linear interpolation between contours. Wind speeds are interpolated in accordance with the 7-10 Standard. Wind speeds correspond to approximately a 7% probability of exceedance in 50 years (annual exceedance probability = 0.00143, MRI = 700 years).

Site is in a hurricane-prone region as defined in ASCE/SEI 7-10 Section 26.2. Glazed openings need not be protected against wind-borne debris.



Mountainous terrain, gorges, ocean promontories, and special wind regions should be examined for unusual wind conditions.

Site Soil Class: D - Stiff Soil

Results:

S_s :	0.187	S_{DS} :	0.2
S_1 :	0.064	S_{D1} :	0.102
F_a :	1.6	T_L :	6
F_v :	2.4	PGA :	0.097
S_{MS} :	0.3	PGA _M :	0.155
S_{M1} :	0.153	F _{PGA} :	1.6
		I_e :	1

Seismic Design Category B



Data Accessed:

Thu Feb 11 2021

Date Source:

USGS Seismic Design Maps based on ASCE/SEI 7-10, incorporating Supplement 1 and errata of March 31, 2013, and ASCE/SEI 7-10 Table 1.5-2. Additional data for site-specific ground motion procedures in accordance with ASCE/SEI 7-10 Ch. 21 are available from USGS.

Ice

Results:

Ice Thickness: 0.75 in.

Concurrent Temperature: 15 F

Gust Speed: 50 mph

Data Source: Standard ASCE/SEI 7-10, Figs. 10-2 through 10-8

Date Accessed: Thu Feb 11 2021

Ice thicknesses on structures in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.

Values provided are equivalent radial ice thicknesses due to freezing rain with concurrent 3-second gust speeds, for a 50-year mean recurrence interval, and temperatures concurrent with ice thicknesses due to freezing rain. Thicknesses for ice accretions caused by other sources shall be obtained from local meteorological studies. Ice thicknesses in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.

The ASCE 7 Hazard Tool is provided for your convenience, for informational purposes only, and is provided “as is” and without warranties of any kind. The location data included herein has been obtained from information developed, produced, and maintained by third party providers; or has been extrapolated from maps incorporated in the ASCE 7 standard. While ASCE has made every effort to use data obtained from reliable sources or methodologies, ASCE does not make any representations or warranties as to the accuracy, completeness, reliability, currency, or quality of any data provided herein. Any third-party links provided by this Tool should not be construed as an endorsement, affiliation, relationship, or sponsorship of such third-party content by or from ASCE.

ASCE does not intend, nor should anyone interpret, the results provided by this Tool to replace the sound judgment of a competent professional, having knowledge and experience in the appropriate field(s) of practice, nor to substitute for the standard of care required of such professionals in interpreting and applying the contents of this Tool or the ASCE 7 standard.

In using this Tool, you expressly assume all risks associated with your use. Under no circumstances shall ASCE or its officers, directors, employees, members, affiliates, or agents be liable to you or any other person for any direct, indirect, special, incidental, or consequential damages arising from or related to your use of, or reliance on, the Tool or any information obtained therein. To the fullest extent permitted by law, you agree to release and hold harmless ASCE from any and all liability of any nature arising out of or resulting from any use of data provided by the ASCE 7 Hazard Tool.

Monopole Base Plate Connection




Site Info	
BU #	881534
Site Name	Waterbury Tower
Order #	538784 Rev. 1

Analysis Considerations	
TIA-222 Revision	H
Grout Considered:	No
l_{ar} (in)	3

Applied Loads	
Moment (kip-ft)	2957.52
Axial Force (kips)	39.21
Shear Force (kips)	25.47

*TIA-222-H Section 15.5 Applied



Connection Properties	Analysis Results
-----------------------	------------------

Anchor Rod Data
(16) 2-1/4" ϕ bolts (A615-75 N; $F_y=75$ ksi, $F_u=100$ ksi) on 58" BC
Base Plate Data
64" OD x 2" Plate (A572-60; $F_y=60$ ksi, $F_u=75$ ksi)
Stiffener Data
N/A
Pole Data
49.5" x 0.4375" 18-sided pole (A572-65; $F_y=65$ ksi, $F_u=80$ ksi)

Anchor Rod Summary	(units of kips, kip-in)	
$P_u_c = 155.33$	$\phi P_n_c = 268.39$	Stress Rating
$V_u = 1.59$	$\phi V_n = 120.77$	57.4%
$M_u = 3.1$	$\phi M_n = 128.14$	Pass
Base Plate Summary		
Max Stress (ksi):	41.26	(Flexural)
Allowable Stress (ksi):	54	
Stress Rating:	72.8%	Pass

Pier and Pad Foundation



BU #: 881534
 Site Name: Waterbury Tower
 App. Number: 538784 Rev. 1

TIA-222 Revision: H
 Tower Type: Monopole

Top & Bot. Pad Rein. Different?:
 Block Foundation?:
 Rectangular Pad?:

Superstructure Analysis Reactions		
Compression, P_{comp} :	39	kips
Base Shear, V_{u_comp} :	25	kips
Moment, M_u :	2958	ft-kips
Tower Height, H :	150	ft
BP Dist. Above Fdn, bp_{dist} :	5.25	in

Foundation Analysis Checks				
	Capacity	Demand	Rating*	Check
<i>Lateral (Sliding) (kips)</i>	544.89	25.00	4.4%	Pass
<i>Bearing Pressure (ksf)</i>	6.00	2.17	34.5%	Pass
<i>Overtuning (kip*ft)</i>	8058.55	3193.94	39.6%	Pass
<i>Pier Flexure (Comp.) (kip*ft)</i>	4135.04	3070.50	70.7%	Pass
<i>Pier Compression (kip)</i>	20168.46	73.22	0.3%	Pass
<i>Pad Flexure (kip*ft)</i>	6555.10	1103.89	16.0%	Pass
<i>Pad Shear - 1-way (kips)</i>	1273.66	135.72	10.1%	Pass
<i>Pad Shear - 2-way (Comp) (ksi)</i>	0.164	0.016	9.2%	Pass
<i>Flexural 2-way (Comp) (kip*ft)</i>	10105.26	1842.30	17.4%	Pass

Pier Properties		
Pier Shape:	Square	
Pier Diameter, $dpier$:	6.5	ft
Ext. Above Grade, E :	1	ft
Pier Rebar Size, S_c :	8	
Pier Rebar Quantity, mc :	36	
Pier Tie/Spiral Size, St :	5	
Pier Tie/Spiral Quantity, mt :	5	
Pier Reinforcement Type:	Tie	
Pier Clear Cover, cc_{pier} :	4	in

*Rating per TIA-222-H Section 15.5

Soil Rating*:	39.6%
Structural Rating*:	70.7%

Pad Properties		
Depth, D :	8	ft
Pad Width, W_1 :	26	ft
Pad Thickness, T :	4.5	ft
Pad Rebar Size (Bottom dir. 2), Sp_2 :	7	
Pad Rebar Quantity (Bottom dir. 2), mp_2 :	50	
Pad Clear Cover, cc_{pad} :	3	in

Material Properties		
Rebar Grade, F_y :	60	ksi
Concrete Compressive Strength, F'_c :	3	ksi
Dry Concrete Density, δ_c :	150	pcf

Soil Properties		
Total Soil Unit Weight, γ :	125	pcf
Ultimate Gross Bearing, Q_{ult} :	8.000	ksf
Cohesion, C_u :	0.000	ksf
Friction Angle, ϕ :	34	degrees
SPT Blow Count, N_{blows} :	126	
Base Friction, μ :	0.6	
Neglected Depth, N :	3.50	ft
Foundation Bearing on Rock?	No	
Groundwater Depth, gw :	N/A	ft

<--Toggle between Gross and Net

Exhibit E

Mount Analysis

Date: **January 31, 2021**

INFINIGY
FROM ZERO TO INFINIGY
the solutions are endless
Infinigy Engineering, PLLC
1033 Watervliet Shaker Road
Albany, NY 12205
518-690-0790
structural@infinigy.com

Darcy Tarr
Crown Castle
3530 Toringdon Way, Suite 300
Charlotte, NC 28277
(704) 405-6589

Subject: **Mount Analysis Report**

Carrier Designation: **Clearwire Corp Retain**
Carrier Site Number: CTNH452A
Carrier Site Name: CTNH452A

Crown Castle Designation: **Crown Castle BU Number:** 881534
Crown Castle Site Name: WATERBURY TOWER
Crown Castle JDE Job Number: 628860
Crown Castle Order Number: 538784 Rev. 0

Engineering Firm Designation: **Infinigy Engineering, PLLC Report Designation:** 1039-Z0001-B

Site Data: **670 Captain Neville Drive, Waterbury, New Haven County, CT, 06705**
Latitude 41°32'3.60", Longitude -72°58'8.40"

Structure Information: **Tower Height & Type:** **150.0 ft Monopole**
Mount Elevation: **140.0 ft**
Mount Type: **12.5 ft Platform**

Dear Darcy Tarr,

Infinigy Engineering, PLLC is pleased to submit this "**Mount Analysis Report**" to determine the structural integrity of Clearwire Corp's antenna mounting system with the proposed appurtenance and equipment addition on the abovementioned supporting tower structure. Analysis of the existing supporting tower structure is to be completed by others and therefore is not part of this analysis. Analysis of the antenna mounting system as a tie-off point for fall protection or rigging is not part of this document.

The purpose of the analysis is to determine acceptability of the mount stress level. Based on our analysis we have determined the mount stress level to be:

Platform

Sufficient - 54.3%

This analysis has been performed in accordance with the 2018 Connecticut State Building Code and Appendix N based upon an ultimate 3-second gust wind speed of 125 mph. Applicable Standard references and design criteria are listed in Section 2 - Analysis Criteria.

Mount analysis prepared by: Jacques S. Grimaldi, M.S., P.E.

Respectfully Submitted by:
Emmanuel Poulin, P.E.
518-690-0790
structural@infinigy.com
CT PE License No. 22947




TABLE OF CONTENTS

1) INTRODUCTION

2) ANALYSIS CRITERIA

Table 1 - Proposed Equipment Configuration

3) ANALYSIS PROCEDURE

Table 2 - Documents Provided

3.1) Analysis Method

3.2) Assumptions

4) ANALYSIS RESULTS

Table 3 - Mount Component Stresses vs. Capacity

4.1) Recommendations

5) APPENDIX A

Wire Frame and Rendered Models

6) APPENDIX B

Software Input Calculations

7) APPENDIX C

Software Analysis Output

8) APPENDIX D

Additional Calculations

1) INTRODUCTION

This is an existing 3 sector 12.5 ft Platform, designed by Site Pro 1.

2) ANALYSIS CRITERIA

Building Code:	2015 IBC / 2018 Connecticut State Building Code and Appendix N
TIA-222 Revision:	TIA-222-H
Risk Category:	II
Ultimate Wind Speed:	125 mph
Exposure Category:	B
Topographic Factor at Base:	1.0
Topographic Factor at Mount:	1.0
Ice Thickness:	1.5 in
Wind Speed with Ice:	50 mph
Seismic S_s:	0.189
Seismic S₁:	0.064
Live Loading Wind Speed:	30 mph
Man Live Load at Mid/End-Points:	250 lb
Man Live Load at Mount Pipes:	500 lb

Table 1 - Proposed Equipment Configuration

Mount Centerline (ft)	Antenna Centerline (ft)	Number of Antennas	Antenna Manufacturer	Antenna Model	Mount / Modification Details
140.0	142.0	2	Andrew	VHLP2-11	12.5 ft Platform
		1	Motorola	TIMING 2000	
	140.0	3	Ericsson	AIR6449 B41 T-MOBILE	
		3	RFS/Celwave	APX16DWV-16DWV-S-E-A20	
		3	RFS/Celwave	APXVAALL24 43-U-NA20 TMO	
		2	Dragonwave	HORIZON COMPACT	
		3	Ericsson	RADIO 4415 B66A CCIV3	
		3	Ericsson	RADIO 4424 B25 TMO	
		3	Ericsson	RADIO 4449 B71 B85A_ T-MOBILE	

3) ANALYSIS PROCEDURE

Table 2 - Documents Provided

Document	Remarks	Reference	Source
Crown Application	Clearwire Corp Application	538784 Rev. 0	CCI Sites
Loading Document	Clearwire Corp	RFDS Version: 1	TSA
Mount Manufacturer Drawings	Site Pro 1	Part No. RMQP-496-HK	Infinigy

3.1) Analysis Method

RISA-3D (Version 19.0.1), a commercially available analysis software package, was used to create a three-dimensional model of the antenna mounting system and calculate member stresses for various loading cases.

Infinigy Mount Analysis Tool V2.1.4, a tool internally developed by Infinigy, was used to calculate wind loading on all appurtenances, dishes and mount members for various loading cases. Selected output from the analysis is included in Appendix B "Software Input Calculations".

This analysis was performed in accordance with Crown Castle's ENG-SOW-10208 *Tower Mount Analysis* (Revision B).

3.2) Assumptions

- 1) The antenna mounting system was properly fabricated, installed and maintained in good condition in accordance with its original design and manufacturer's specifications.
- 2) The configuration of antennas, mounts, and other appurtenances are as specified in Table 1 and the referenced drawings.
- 3) All member connections are assumed to have been designed to meet or exceed the load carrying capacity of the connected member unless otherwise specified in this report.
- 4) The analysis will be required to be revised if the existing conditions in the field differ from those shown in the above-referenced documents or assumed in this analysis. No allowance was made for any damaged, missing, or rusted members.
- 5) Prior structural modifications to the tower mounting system are assumed to be installed as shown per available data.
- 6) Steel grades have been assumed as follows, unless noted otherwise:

Channel, Solid Round, Angle, Plate	Q345 (GR 36)
HSS (Rectangular)	Q235-GB (GR 35)
Pipe	Q235-GB (GR 35)
Connection Bolts	ASTM A325

This analysis may be affected if any assumptions are not valid or have been made in error. Infinigy Engineering, PLLC should be notified to determine the effect on the structural integrity of the antenna mounting system.

4) ANALYSIS RESULTS

Table 3 - Mount Component Stresses vs. Capacity (Platform, All Sectors)

Notes	Component	Critical Member	Centerline (ft)	% Capacity	Pass / Fail
1, 2	Mount Pipe(s)	MP3	140.0	54.3	Pass
	Horizontal(s)	M46		16.0	Pass
	Handrail(s)	M55		35.8	Pass
	Standoff(s)	M17		23.2	Pass
	Kicker(s)	M10		12.5	Pass
	Mount Connection(s)	-		16.4	Pass

Structure Rating (max from all components) =	54.3%
---	--------------


Notes:

- 1) See additional documentation in "Appendix C - Software Analysis Output" for calculations supporting the % capacity consumed.
- 2) See additional documentation in "Appendix D - Additional Calculations" for detailed mount connection calculations.

4.1) Recommendations

The mount has sufficient capacity to carry the proposed loading configuration. No modifications are required at this time.

APPENDIX A
WIRE FRAME AND RENDERED MODELS



Infinigy Engineering, PLLC

JG


1039-Z0001-B

881534

Render

Jan 31, 2021

881534_loaded.r3d



Infinigy Engineering, PLLC

881534

Wireframe

JG

Jan 31, 2021

1039-Z0001-B

881534_loaded.r3d

APPENDIX B
SOFTWARE INPUT CALCULATIONS

Program Inputs

PROJECT INFORMATION		
Client:	Crown Castle	
Carrier:	Clearwire Corp	
Engineer:	Jacques Grimaldi	

SITE INFORMATION		
Risk Category:	II	
Exposure Category:	B	
Topo Factor Procedure:	Method 1, Category 1	
Site Class:	D - Stiff Soil	
Ground Elevation:	612.55	ft *Rev H

MOUNT INFORMATION		
Mount Type:	Platform	
Num Sectors:	3	
Centerline AGL:	140.0	ft
Tower Height AGL:	150.0	ft

TOPOGRAPHIC DATA		
Topo Feature:	N/A	
Slope Distance:	N/A	ft
Crest Distance:	N/A	ft
Crest Height:	N/A	ft

FACTORS		
Directionality Fact. (K_d):	0.95	
Ground Ele. Factor (K_e):	0.98	*Rev H Only
Rooftop Speed-Up (K_s):	1.00	*Rev H Only
Topographic Factor (K_{zt}):	1.00	
Gust Effect Factor (G_H):	1.0	

CODE STANDARDS		
Building Code:	2015 IBC	
TIA Standard:	TIA-222-H	
ASCE Standard:	ASCE 7-10	

WIND AND ICE DATA		
Ultimate Wind (V_{ult}):	125	mph
Design Wind (V):	N/A	mph
Ice Wind (V_{ice}):	50	mph
Base Ice Thickness (t_i):	1.5	in
Flat Pressure:	80.87	psf
Round Pressure:	48.52	psf
Ice Wind Pressure:	7.76	psf

SEISMIC DATA		
Short-Period Accel. (S_s):	0.189	g
1-Second Accel. (S_1):	0.064	g
Short-Period Design (S_{DS}):	0.20	
1-Second Design (S_{D1}):	0.10	
Short-Period Coeff. (F_a):	1.60	
1-Second Coeff. (F_v):	2.40	
Amplification Factor (a_p):	1.00	
Response Mod. (R_p):	2.50	
Overstrength (Ω_o):	1.00	




Infinigy Load Calculator V2.1.4

ASCE 7 Hazards Report

Address:
No Address at This Location

Standard: ASCE/SEI 7-10
Risk Category: II
Soil Class: D - Stiff Soil

Elevation: 612.55 ft (NAVD 88)
Latitude: 41.534333
Longitude: -72.969



Wind

Results:

Wind Speed:	125 Vmph per 2018 Connecticut State Building Code and Appendix N
10-year MRI	76 Vmph
25-year MRI	86 Vmph
50-year MRI	92 Vmph
100-year MRI	99 Vmph

Data Source: ASCE/SEI 7-10, Fig. 26.5-1A and Figs. CC-1–CC-4, incorporating errata of March 12, 2014

Date Accessed: Sun Jan 31 2021

Value provided is 3-second gust wind speeds at 33 ft above ground for Exposure C Category, based on linear interpolation between contours. Wind speeds are interpolated in accordance with the 7-10 Standard. Wind speeds correspond to approximately a 7% probability of exceedance in 50 years (annual exceedance probability = 0.00143, MRI = 700 years).

Site is in a hurricane-prone region as defined in ASCE/SEI 7-10 Section 26.2. Glazed openings need not be protected against wind-borne debris.



Mountainous terrain, gorges, ocean promontories, and special wind regions should be examined for unusual wind conditions.

Site Soil Class: D - Stiff Soil

Results:

S_s :	0.189	S_{DS} :	0.2
S_1 :	0.064	S_{D1} :	0.102
F_a :	1.6	T_L :	6
F_v :	2.4	PGA :	0.097
S_{MS} :	0.3	PGA _M :	0.155
S_{M1} :	0.153	F _{PGA} :	1.6
		I_e :	1

Seismic Design Category B



Data Accessed:

Sun Jan 31 2021

Date Source:

USGS Seismic Design Maps based on ASCE/SEI 7-10, incorporating Supplement 1 and errata of March 31, 2013, and ASCE/SEI 7-10 Table 1.5-2. Additional data for site-specific ground motion procedures in accordance with ASCE/SEI 7-10 Ch. 21 are available from USGS.

Ice

Results:

Ice Thickness: 0.75 in.

Concurrent Temperature: 15 F

Gust Speed: 50 mph

Data Source: Standard ASCE/SEI 7-10, Figs. 10-2 through 10-8

Date Accessed: Sun Jan 31 2021

Ice thicknesses on structures in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.

Values provided are equivalent radial ice thicknesses due to freezing rain with concurrent 3-second gust speeds, for a 50-year mean recurrence interval, and temperatures concurrent with ice thicknesses due to freezing rain. Thicknesses for ice accretions caused by other sources shall be obtained from local meteorological studies. Ice thicknesses in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.

The ASCE 7 Hazard Tool is provided for your convenience, for informational purposes only, and is provided “as is” and without warranties of any kind. The location data included herein has been obtained from information developed, produced, and maintained by third party providers; or has been extrapolated from maps incorporated in the ASCE 7 standard. While ASCE has made every effort to use data obtained from reliable sources or methodologies, ASCE does not make any representations or warranties as to the accuracy, completeness, reliability, currency, or quality of any data provided herein. Any third-party links provided by this Tool should not be construed as an endorsement, affiliation, relationship, or sponsorship of such third-party content by or from ASCE.

ASCE does not intend, nor should anyone interpret, the results provided by this Tool to replace the sound judgment of a competent professional, having knowledge and experience in the appropriate field(s) of practice, nor to substitute for the standard of care required of such professionals in interpreting and applying the contents of this Tool or the ASCE 7 standard.

In using this Tool, you expressly assume all risks associated with your use. Under no circumstances shall ASCE or its officers, directors, employees, members, affiliates, or agents be liable to you or any other person for any direct, indirect, special, incidental, or consequential damages arising from or related to your use of, or reliance on, the Tool or any information obtained therein. To the fullest extent permitted by law, you agree to release and hold harmless ASCE from any and all liability of any nature arising out of or resulting from any use of data provided by the ASCE 7 Hazard Tool.

APPENDIX C
SOFTWARE ANALYSIS OUTPUT

Member Primary Data

	Label	I Node	J Node	Rotate(deg)	Section/Shape	Type	Design List	Material	Design Rule
1	M1	N4	N5		RIGID	None	None	RIGID	Typical
2	M2	N7	N6		RIGID	None	None	RIGID	Typical
3	M3	N8	N9		RIGID	None	None	RIGID	Typical
4	M4	N11	N10		RIGID	None	None	RIGID	Typical
5	M5	N12	N13		RIGID	None	None	RIGID	Typical
6	M6	N15	N14		RIGID	None	None	RIGID	Typical
7	M7	N26	N6	180	Kicker Angle	None	None	Q345	Typical
8	M8	N27	N26		RIGID	None	None	RIGID	Typical
9	M9	N27	N7	90	Kicker Angle	None	None	Q345	Typical
10	M10	N29	N10	180	Kicker Angle	None	None	Q345	Typical
11	M11	N30	N29		RIGID	None	None	RIGID	Typical
12	M12	N30	N11	90	Kicker Angle	None	None	Q345	Typical
13	M13	N32	N14	180	Kicker Angle	None	None	Q345	Typical
14	M14	N33	N32		RIGID	None	None	RIGID	Typical
15	M15	N33	N15	90	Kicker Angle	None	None	Q345	Typical
16	M16	N34	N35		Stand Off HSS	None	None	Q235-GB	Typical
17	M17	N36	N37		Corner Plate	None	None	Q345	Typical
18	M18	N36	N85		RIGID	None	None	RIGID	Typical
19	M19	N37	N72		RIGID	None	None	RIGID	Typical
20	M20	N38	N41		Stand Off HSS	None	None	Q235-GB	Typical
21	M21	N39	N44		Stand Off HSS	None	None	Q235-GB	Typical
22	M22	N42	N43		Corner Plate	None	None	Q345	Typical
23	M23	N42	N73		RIGID	None	None	RIGID	Typical
24	M24	N43	N78		RIGID	None	None	RIGID	Typical
25	M25	N45	N46		Corner Plate	None	None	Q345	Typical
26	M26	N45	N79		RIGID	None	None	RIGID	Typical
27	M27	N46	N84		RIGID	None	None	RIGID	Typical
28	M28	N48	N47		Face Horizontal	None	None	Q235-GB	Typical
29	M29	N52	N53		Stand Off HSS	None	None	Q235-GB	Typical
30	M30	N52	N86		RIGID	None	None	RIGID	Typical
31	M31	N53	N81		RIGID	None	None	RIGID	Typical
32	M32	N54	N55		Stand Off HSS	None	None	Q235-GB	Typical
33	M33	N54	N74		RIGID	None	None	RIGID	Typical
34	M34	N55	N87		RIGID	None	None	RIGID	Typical
35	M35	N56	N57		Stand Off HSS	None	None	Q235-GB	Typical
36	M36	N56	N80		RIGID	None	None	RIGID	Typical
37	M37	N57	N75		RIGID	None	None	RIGID	Typical
38	M38	N58	N61	270	Grating Support Angle	None	None	Q345	Typical
39	M39	N59	N60		Grating Support Angle	None	None	Q345	Typical
40	M40	N62	N65	270	Grating Support Angle	None	None	Q345	Typical
41	M41	N63	N64		Grating Support Angle	None	None	Q345	Typical
42	M42	N66	N69	270	Grating Support Angle	None	None	Q345	Typical
43	M43	N67	N68		Grating Support Angle	None	None	Q345	Typical
44	M44	N71	N70		RIGID	None	None	RIGID	Typical
45	M45	N77	N76		Face Horizontal	None	None	Q235-GB	Typical
46	M46	N83	N82		Face Horizontal	None	None	Q235-GB	Typical
47	M47	N88	N25		RIGID	None	None	RIGID	Typical
48	M48	N89	N28	240	RIGID	None	None	RIGID	Typical
49	M49	N90	N31	120	RIGID	None	None	RIGID	Typical

Member Primary Data (Continued)

	Label	I Node	J Node	Rotate(deg)	Section/Shape	Type	Design List	Material	Design Rule
50	M50	N108	N107		Support Rail	None	None	Q235-GB	Typical
51	M51	N110	N112	180	Support Rail Corner Angle	None	None	Q345	Typical
52	M52	N110	N117		RIGID	None	None	RIGID	Typical
53	M53	N111	N109		RIGID	None	None	RIGID	Typical
54	M54	N112	N126		RIGID	None	None	RIGID	Typical
55	M55	N113	N114	180	Support Rail Corner Angle	None	None	Q345	Typical
56	M56	N113	N121		RIGID	None	None	RIGID	Typical
57	M57	N114	N118		RIGID	None	None	RIGID	Typical
58	M58	N115	N116	180	Support Rail Corner Angle	None	None	Q345	Typical
59	M59	N115	N125		RIGID	None	None	RIGID	Typical
60	M60	N116	N122		RIGID	None	None	RIGID	Typical
61	M61	N120	N119		Support Rail	None	None	Q235-GB	Typical
62	M62	N124	N123		Support Rail	None	None	Q235-GB	Typical
63	MP4	N143	N16		Mount Pipe	None	None	Q235-GB	Typical
64	M64	N92	N91		RIGID	None	None	RIGID	Typical
65	M65	N128	N127		RIGID	None	None	RIGID	Typical
66	MP2	N144	N17		Mount Pipe	None	None	Q235-GB	Typical
67	M67	N94	N93		RIGID	None	None	RIGID	Typical
68	M68	N130	N129		RIGID	None	None	RIGID	Typical
69	MP1	N145	N18		Mount Pipe	None	None	Q235-GB	Typical
70	M70	N157	N156		RIGID	None	None	RIGID	Typical
71	M71	N159	N158		RIGID	None	None	RIGID	Typical
72	MP3	N160	N155		Mount Pipe	None	None	Q235-GB	Typical
73	M73	N151	N150		RIGID	None	None	RIGID	Typical
74	MP10	N146	N139		Mount Pipe	None	None	Q235-GB	Typical
75	M75	N135	N131		RIGID	None	None	RIGID	Typical
76	M76	N137	N136		RIGID	None	None	RIGID	Typical
77	MP12	N138	N134		Mount Pipe	None	None	Q235-GB	Typical
78	M78	N142	N141		RIGID	None	None	RIGID	Typical
79	M79	N140	N132		RIGID	None	None	RIGID	Typical
80	M80	N149	N148		RIGID	None	None	RIGID	Typical
81	MP11	N152	N147		Mount Pipe	None	None	Q235-GB	Typical
82	M82	N161	N154		RIGID	None	None	RIGID	Typical
83	M83	N163	N162		RIGID	None	None	RIGID	Typical
84	MP9	N133	N153		Mount Pipe	None	None	Q235-GB	Typical
85	M85	N181	N180		RIGID	None	None	RIGID	Typical
86	MP6	N176	N172		Mount Pipe	None	None	Q235-GB	Typical
87	M87	N168	N164		RIGID	None	None	RIGID	Typical
88	M88	N170	N169		RIGID	None	None	RIGID	Typical
89	MP8	N171	N167		Mount Pipe	None	None	Q235-GB	Typical
90	M90	N175	N174		RIGID	None	None	RIGID	Typical
91	M91	N173	N165		RIGID	None	None	RIGID	Typical
92	M92	N179	N178		RIGID	None	None	RIGID	Typical
93	MP7	N182	N177		Mount Pipe	None	None	Q235-GB	Typical
94	M94	N185	N184		RIGID	None	None	RIGID	Typical
95	M95	N187	N186		RIGID	None	None	RIGID	Typical
96	MP5	N166	N183		Mount Pipe	None	None	Q235-GB	Typical

Material Take-Off

	Material	Size	Pieces	Length[in]	Weight[LB]
1	General Members				
2	RIGID		54	144	0
3	Total General		54	144	0
4					
5	Hot Rolled Steel				
6	Q235-GB	HSS4X4X8	6	374.3	638.974
7	Q235-GB	PIPE 3.0	3	450	264.141
8	Q235-GB	PIPE 2.0	15	1602	463.356
9	Q345	6"x0.37" Plate	3	36	22.662
10	Q345	L2.5x2.5x3	9	344.8	88.102
11	Q345	L2x2x2	6	303.1	42.203
12	Total HR Steel		42	3110.3	1519.439

Basic Load Cases

	BLC Description	Category	X Gravity	Y Gravity	Z Gravity	Nodal	Point	Distributed	Area(Member)
1	Self Weight	DL		-1			46		3
2	Wind Load AZI 0	WLZ					92		
3	Wind Load AZI 30	None					92		
4	Wind Load AZI 60	None					92		
5	Wind Load AZI 90	WLX					92		
6	Wind Load AZI 120	None					92		
7	Wind Load AZI 150	None					92		
8	Wind Load AZI 180	None					92		
9	Wind Load AZI 210	None					92		
10	Wind Load AZI 240	None					92		
11	Wind Load AZI 270	None					92		
12	Wind Load AZI 300	None					92		
13	Wind Load AZI 330	None					92		
14	Distr. Wind Load Z	WLZ						96	
15	Distr. Wind Load X	WLX						96	
16	Ice Weight	OL1					46	96	3
17	Ice Wind Load AZI 0	OL2					92		
18	Ice Wind Load AZI 30	None					92		
19	Ice Wind Load AZI 60	None					92		
20	Ice Wind Load AZI 90	OL3					92		
21	Ice Wind Load AZI 120	None					92		
22	Ice Wind Load AZI 150	None					92		
23	Ice Wind Load AZI 180	None					92		
24	Ice Wind Load AZI 210	None					92		
25	Ice Wind Load AZI 240	None					92		
26	Ice Wind Load AZI 270	None					92		
27	Ice Wind Load AZI 300	None					92		
28	Ice Wind Load AZI 330	None					92		
29	Distr. Ice Wind Load Z	OL2						96	
30	Distr. Ice Wind Load X	OL3						96	
31	Seismic Load Z	ELZ			-0.101		46		
32	Seismic Load X	ELX	-0.101				46		
33	Service Live Loads	LL				1			



Basic Load Cases (Continued)

	BLC Description	Category	X Gravity	Y Gravity	Z Gravity	Nodal	Point	Distributed	Area(Member)
34	Maintenance Load 1	LL				1			
35	Maintenance Load 2	LL				1			
36	Maintenance Load 3	LL				1			
37	Maintenance Load 4	LL				1			
38	Maintenance Load 5	LL				1			
39	Maintenance Load 6	LL				1			
40	Maintenance Load 7	LL				1			
41	Maintenance Load 8	LL				1			
42	Maintenance Load 9	LL				1			
43	Maintenance Load 10	LL				1			
44	Maintenance Load 11	LL				1			
45	Maintenance Load 12	LL				1			
46	BLC 1 Transient Area Loads	None						60	
47	BLC 16 Transient Area Loads	None						60	

Load Combinations

	Description	Solve	P	Delta	BLC	Factor	BLC	Factor	BLC	Factor	BLC	Factor	BLC	Factor
1	1.4DL	Yes	Y	1	1.4									
2	1.2DL + 1WL AZI 0	Yes	Y	1	1.2	2	1	14	1	15				
3	1.2DL + 1WL AZI 30	Yes	Y	1	1.2	3	1	14	0.866	15	0.5			
4	1.2DL + 1WL AZI 60	Yes	Y	1	1.2	4	1	14	0.5	15	0.866			
5	1.2DL + 1WL AZI 90	Yes	Y	1	1.2	5	1	14		15	1			
6	1.2DL + 1WL AZI 120	Yes	Y	1	1.2	6	1	14	-0.5	15	0.866			
7	1.2DL + 1WL AZI 150	Yes	Y	1	1.2	7	1	14	-0.866	15	0.5			
8	1.2DL + 1WL AZI 180	Yes	Y	1	1.2	8	1	14	-1	15				
9	1.2DL + 1WL AZI 210	Yes	Y	1	1.2	9	1	14	-0.866	15	-0.5			
10	1.2DL + 1WL AZI 240	Yes	Y	1	1.2	10	1	14	-0.5	15	-0.866			
11	1.2DL + 1WL AZI 270	Yes	Y	1	1.2	11	1	14		15	-1			
12	1.2DL + 1WL AZI 300	Yes	Y	1	1.2	12	1	14	0.5	15	-0.866			
13	1.2DL + 1WL AZI 330	Yes	Y	1	1.2	13	1	14	0.866	15	-0.5			
14	0.9DL + 1WL AZI 0	Yes	Y	1	0.9	2	1	14	1	15				
15	0.9DL + 1WL AZI 30	Yes	Y	1	0.9	3	1	14	0.866	15	0.5			
16	0.9DL + 1WL AZI 60	Yes	Y	1	0.9	4	1	14	0.5	15	0.866			
17	0.9DL + 1WL AZI 90	Yes	Y	1	0.9	5	1	14		15	1			
18	0.9DL + 1WL AZI 120	Yes	Y	1	0.9	6	1	14	-0.5	15	0.866			
19	0.9DL + 1WL AZI 150	Yes	Y	1	0.9	7	1	14	-0.866	15	0.5			
20	0.9DL + 1WL AZI 180	Yes	Y	1	0.9	8	1	14	-1	15				
21	0.9DL + 1WL AZI 210	Yes	Y	1	0.9	9	1	14	-0.866	15	-0.5			
22	0.9DL + 1WL AZI 240	Yes	Y	1	0.9	10	1	14	-0.5	15	-0.866			
23	0.9DL + 1WL AZI 270	Yes	Y	1	0.9	11	1	14		15	-1			
24	0.9DL + 1WL AZI 300	Yes	Y	1	0.9	12	1	14	0.5	15	-0.866			
25	0.9DL + 1WL AZI 330	Yes	Y	1	0.9	13	1	14	0.866	15	-0.5			
26	1.2D + 1.0Di	Yes	Y	1	1.2	16	1							
27	1.2D + 1.0Di + 1.0Wi AZI 0	Yes	Y	1	1.2	16	1	17	1	29	1	30		
28	1.2D + 1.0Di + 1.0Wi AZI 30	Yes	Y	1	1.2	16	1	18	1	29	0.866	30	0.5	
29	1.2D + 1.0Di + 1.0Wi AZI 60	Yes	Y	1	1.2	16	1	19	1	29	0.5	30	0.866	
30	1.2D + 1.0Di + 1.0Wi AZI 90	Yes	Y	1	1.2	16	1	20	1	29		30	1	
31	1.2D + 1.0Di + 1.0Wi AZI 120	Yes	Y	1	1.2	16	1	21	1	29	-0.5	30	0.866	



Load Combinations (Continued)

	Description	Solve	P	Delta	BLCFactor	BLCFactor	BLCFactor	BLCFactor	BLCFactor	BLCFactor	BLCFactor	BLCFactor	BLCFactor
32	1.2D + 1.0Di + 1.0Wi AZI 150	Yes	Y	1	1.2	16	1	22	1	29	-0.866	30	0.5
33	1.2D + 1.0Di + 1.0Wi AZI 180	Yes	Y	1	1.2	16	1	23	1	29	-1	30	
34	1.2D + 1.0Di + 1.0Wi AZI 210	Yes	Y	1	1.2	16	1	24	1	29	-0.866	30	-0.5
35	1.2D + 1.0Di + 1.0Wi AZI 240	Yes	Y	1	1.2	16	1	25	1	29	-0.5	30	-0.866
36	1.2D + 1.0Di + 1.0Wi AZI 270	Yes	Y	1	1.2	16	1	26	1	29		30	-1
37	1.2D + 1.0Di + 1.0Wi AZI 300	Yes	Y	1	1.2	16	1	27	1	29	0.5	30	-0.866
38	1.2D + 1.0Di + 1.0Wi AZI 330	Yes	Y	1	1.2	16	1	28	1	29	0.866	30	-0.5
39	(1.2 + 0.2Sds)DL + 1.0E AZI 0	Yes	Y	1	1.24	31	1	32					
40	(1.2 + 0.2Sds)DL + 1.0E AZI 30	Yes	Y	1	1.24	31	0.866	32	0.5				
41	(1.2 + 0.2Sds)DL + 1.0E AZI 60	Yes	Y	1	1.24	31	0.5	32	0.866				
42	(1.2 + 0.2Sds)DL + 1.0E AZI 90	Yes	Y	1	1.24	31		32	1				
43	(1.2 + 0.2Sds)DL + 1.0E AZI 120	Yes	Y	1	1.24	31	-0.5	32	0.866				
44	(1.2 + 0.2Sds)DL + 1.0E AZI 150	Yes	Y	1	1.24	31	-0.866	32	0.5				
45	(1.2 + 0.2Sds)DL + 1.0E AZI 180	Yes	Y	1	1.24	31	-1	32					
46	(1.2 + 0.2Sds)DL + 1.0E AZI 210	Yes	Y	1	1.24	31	-0.866	32	-0.5				
47	(1.2 + 0.2Sds)DL + 1.0E AZI 240	Yes	Y	1	1.24	31	-0.5	32	-0.866				
48	(1.2 + 0.2Sds)DL + 1.0E AZI 270	Yes	Y	1	1.24	31		32	-1				
49	(1.2 + 0.2Sds)DL + 1.0E AZI 300	Yes	Y	1	1.24	31	0.5	32	-0.866				
50	(1.2 + 0.2Sds)DL + 1.0E AZI 330	Yes	Y	1	1.24	31	0.866	32	-0.5				
51	(0.9 - 0.2Sds)DL + 1.0E AZI 0	Yes	Y	1	0.86	31	1	32					
52	(0.9 - 0.2Sds)DL + 1.0E AZI 30	Yes	Y	1	0.86	31	0.866	32	0.5				
53	(0.9 - 0.2Sds)DL + 1.0E AZI 60	Yes	Y	1	0.86	31	0.5	32	0.866				
54	(0.9 - 0.2Sds)DL + 1.0E AZI 90	Yes	Y	1	0.86	31		32	1				
55	(0.9 - 0.2Sds)DL + 1.0E AZI 120	Yes	Y	1	0.86	31	-0.5	32	0.866				
56	(0.9 - 0.2Sds)DL + 1.0E AZI 150	Yes	Y	1	0.86	31	-0.866	32	0.5				
57	(0.9 - 0.2Sds)DL + 1.0E AZI 180	Yes	Y	1	0.86	31	-1	32					
58	(0.9 - 0.2Sds)DL + 1.0E AZI 210	Yes	Y	1	0.86	31	-0.866	32	-0.5				
59	(0.9 - 0.2Sds)DL + 1.0E AZI 240	Yes	Y	1	0.86	31	-0.5	32	-0.866				
60	(0.9 - 0.2Sds)DL + 1.0E AZI 270	Yes	Y	1	0.86	31		32	-1				
61	(0.9 - 0.2Sds)DL + 1.0E AZI 300	Yes	Y	1	0.86	31	0.5	32	-0.866				
62	(0.9 - 0.2Sds)DL + 1.0E AZI 330	Yes	Y	1	0.86	31	0.866	32	-0.5				
63	1.0DL + 1.5LL + 1.0SWL (60 mph) AZI 0	Yes	Y	1	1	2	0.23	14	0.23	15		33	1.5
64	1.0DL + 1.5LL + 1.0SWL (60 mph) AZI 30	Yes	Y	1	1	3	0.23	14	0.2	15	0.115	33	1.5
65	1.0DL + 1.5LL + 1.0SWL (60 mph) AZI 60	Yes	Y	1	1	4	0.23	14	0.115	15	0.2	33	1.5
66	1.0DL + 1.5LL + 1.0SWL (60 mph) AZI 90	Yes	Y	1	1	5	0.23	14		15	0.23	33	1.5
67	1.0DL + 1.5LL + 1.0SWL (60 mph) AZI 120	Yes	Y	1	1	6	0.23	14	-0.115	15	0.2	33	1.5
68	1.0DL + 1.5LL + 1.0SWL (60 mph) AZI 150	Yes	Y	1	1	7	0.23	14	-0.2	15	0.115	33	1.5
69	1.0DL + 1.5LL + 1.0SWL (60 mph) AZI 180	Yes	Y	1	1	8	0.23	14	-0.23	15		33	1.5
70	1.0DL + 1.5LL + 1.0SWL (60 mph) AZI 210	Yes	Y	1	1	9	0.23	14	-0.2	15	-0.115	33	1.5
71	1.0DL + 1.5LL + 1.0SWL (60 mph) AZI 240	Yes	Y	1	1	10	0.23	14	-0.115	15	-0.2	33	1.5
72	1.0DL + 1.5LL + 1.0SWL (60 mph) AZI 270	Yes	Y	1	1	11	0.23	14		15	-0.23	33	1.5
73	1.0DL + 1.5LL + 1.0SWL (60 mph) AZI 300	Yes	Y	1	1	12	0.23	14	0.115	15	-0.2	33	1.5
74	1.0DL + 1.5LL + 1.0SWL (60 mph) AZI 330	Yes	Y	1	1	13	0.23	14	0.2	15	-0.115	33	1.5
75	1.2DL + 1.5LL	Yes	Y	1	1.2	33	1.5						
76	1.2DL + 1.5LM-MP1 + 1SWL (30 mph) AZI 0	Yes	Y	1	1.2	34	1.5	2	0.058	14	0.058	15	
77	1.2DL + 1.5LM-MP1 + 1SWL (30 mph) AZI 30	Yes	Y	1	1.2	34	1.5	3	0.058	14	0.05	15	0.029
78	1.2DL + 1.5LM-MP1 + 1SWL (30 mph) AZI 60	Yes	Y	1	1.2	34	1.5	4	0.058	14	0.029	15	0.05
79	1.2DL + 1.5LM-MP1 + 1SWL (30 mph) AZI 90	Yes	Y	1	1.2	34	1.5	5	0.058	14		15	0.058
80	1.2DL + 1.5LM-MP1 + 1SWL (30 mph) AZI 120	Yes	Y	1	1.2	34	1.5	6	0.058	14	-0.029	15	0.05



Company : Infinigy Engineering, PLLC
 Designer : JG
 Job Number : 1039-Z0001-B
 Model Name : 881534

1/31/2021
 1:45:18 PM
 Checked By : _____

Load Combinations (Continued)

	Description	Solve	PDelta	BLCFactor	BLCFactor	BLCFactor	BLCFactor	BLCFactor	BLCFactor	BLCFactor	BLCFactor	BLCFactor	BLCFactor
81	1.2DL + 1.5LM-MP1 + 1SWL (30 mph) AZI 150	Yes	Y	1	1.2	34	1.5	7	0.058	14	-0.05	15	0.029
82	1.2DL + 1.5LM-MP1 + 1SWL (30 mph) AZI 180	Yes	Y	1	1.2	34	1.5	8	0.058	14	-0.058	15	
83	1.2DL + 1.5LM-MP1 + 1SWL (30 mph) AZI 210	Yes	Y	1	1.2	34	1.5	9	0.058	14	-0.05	15	-0.029
84	1.2DL + 1.5LM-MP1 + 1SWL (30 mph) AZI 240	Yes	Y	1	1.2	34	1.5	10	0.058	14	-0.029	15	-0.05
85	1.2DL + 1.5LM-MP1 + 1SWL (30 mph) AZI 270	Yes	Y	1	1.2	34	1.5	11	0.058	14		15	-0.058
86	1.2DL + 1.5LM-MP1 + 1SWL (30 mph) AZI 300	Yes	Y	1	1.2	34	1.5	12	0.058	14	0.029	15	-0.05
87	1.2DL + 1.5LM-MP1 + 1SWL (30 mph) AZI 330	Yes	Y	1	1.2	34	1.5	13	0.058	14	0.05	15	-0.029
88	1.2DL + 1.5LM-MP2 + 1SWL (30 mph) AZI 0	Yes	Y	1	1.2	35	1.5	2	0.058	14	0.058	15	
89	1.2DL + 1.5LM-MP2 + 1SWL (30 mph) AZI 30	Yes	Y	1	1.2	35	1.5	3	0.058	14	0.05	15	0.029
90	1.2DL + 1.5LM-MP2 + 1SWL (30 mph) AZI 60	Yes	Y	1	1.2	35	1.5	4	0.058	14	0.029	15	0.05
91	1.2DL + 1.5LM-MP2 + 1SWL (30 mph) AZI 90	Yes	Y	1	1.2	35	1.5	5	0.058	14		15	0.058
92	1.2DL + 1.5LM-MP2 + 1SWL (30 mph) AZI 120	Yes	Y	1	1.2	35	1.5	6	0.058	14	-0.029	15	0.05
93	1.2DL + 1.5LM-MP2 + 1SWL (30 mph) AZI 150	Yes	Y	1	1.2	35	1.5	7	0.058	14	-0.05	15	0.029
94	1.2DL + 1.5LM-MP2 + 1SWL (30 mph) AZI 180	Yes	Y	1	1.2	35	1.5	8	0.058	14	-0.058	15	
95	1.2DL + 1.5LM-MP2 + 1SWL (30 mph) AZI 210	Yes	Y	1	1.2	35	1.5	9	0.058	14	-0.05	15	-0.029
96	1.2DL + 1.5LM-MP2 + 1SWL (30 mph) AZI 240	Yes	Y	1	1.2	35	1.5	10	0.058	14	-0.029	15	-0.05
97	1.2DL + 1.5LM-MP2 + 1SWL (30 mph) AZI 270	Yes	Y	1	1.2	35	1.5	11	0.058	14		15	-0.058
98	1.2DL + 1.5LM-MP2 + 1SWL (30 mph) AZI 300	Yes	Y	1	1.2	35	1.5	12	0.058	14	0.029	15	-0.05
99	1.2DL + 1.5LM-MP2 + 1SWL (30 mph) AZI 330	Yes	Y	1	1.2	35	1.5	13	0.058	14	0.05	15	-0.029
100	1.2DL + 1.5LM-MP3 + 1SWL (30 mph) AZI 0	Yes	Y	1	1.2	36	1.5	2	0.058	14	0.058	15	
101	1.2DL + 1.5LM-MP3 + 1SWL (30 mph) AZI 30	Yes	Y	1	1.2	36	1.5	3	0.058	14	0.05	15	0.029
102	1.2DL + 1.5LM-MP3 + 1SWL (30 mph) AZI 60	Yes	Y	1	1.2	36	1.5	4	0.058	14	0.029	15	0.05
103	1.2DL + 1.5LM-MP3 + 1SWL (30 mph) AZI 90	Yes	Y	1	1.2	36	1.5	5	0.058	14		15	0.058
104	1.2DL + 1.5LM-MP3 + 1SWL (30 mph) AZI 120	Yes	Y	1	1.2	36	1.5	6	0.058	14	-0.029	15	0.05
105	1.2DL + 1.5LM-MP3 + 1SWL (30 mph) AZI 150	Yes	Y	1	1.2	36	1.5	7	0.058	14	-0.05	15	0.029
106	1.2DL + 1.5LM-MP3 + 1SWL (30 mph) AZI 180	Yes	Y	1	1.2	36	1.5	8	0.058	14	-0.058	15	
107	1.2DL + 1.5LM-MP3 + 1SWL (30 mph) AZI 210	Yes	Y	1	1.2	36	1.5	9	0.058	14	-0.05	15	-0.029
108	1.2DL + 1.5LM-MP3 + 1SWL (30 mph) AZI 240	Yes	Y	1	1.2	36	1.5	10	0.058	14	-0.029	15	-0.05
109	1.2DL + 1.5LM-MP3 + 1SWL (30 mph) AZI 270	Yes	Y	1	1.2	36	1.5	11	0.058	14		15	-0.058
110	1.2DL + 1.5LM-MP3 + 1SWL (30 mph) AZI 300	Yes	Y	1	1.2	36	1.5	12	0.058	14	0.029	15	-0.05
111	1.2DL + 1.5LM-MP3 + 1SWL (30 mph) AZI 330	Yes	Y	1	1.2	36	1.5	13	0.058	14	0.05	15	-0.029
112	1.2DL + 1.5LM-MP4 + 1SWL (30 mph) AZI 0	Yes	Y	1	1.2	37	1.5	2	0.058	14	0.058	15	
113	1.2DL + 1.5LM-MP4 + 1SWL (30 mph) AZI 30	Yes	Y	1	1.2	37	1.5	3	0.058	14	0.05	15	0.029
114	1.2DL + 1.5LM-MP4 + 1SWL (30 mph) AZI 60	Yes	Y	1	1.2	37	1.5	4	0.058	14	0.029	15	0.05
115	1.2DL + 1.5LM-MP4 + 1SWL (30 mph) AZI 90	Yes	Y	1	1.2	37	1.5	5	0.058	14		15	0.058
116	1.2DL + 1.5LM-MP4 + 1SWL (30 mph) AZI 120	Yes	Y	1	1.2	37	1.5	6	0.058	14	-0.029	15	0.05
117	1.2DL + 1.5LM-MP4 + 1SWL (30 mph) AZI 150	Yes	Y	1	1.2	37	1.5	7	0.058	14	-0.05	15	0.029
118	1.2DL + 1.5LM-MP4 + 1SWL (30 mph) AZI 180	Yes	Y	1	1.2	37	1.5	8	0.058	14	-0.058	15	
119	1.2DL + 1.5LM-MP4 + 1SWL (30 mph) AZI 210	Yes	Y	1	1.2	37	1.5	9	0.058	14	-0.05	15	-0.029
120	1.2DL + 1.5LM-MP4 + 1SWL (30 mph) AZI 240	Yes	Y	1	1.2	37	1.5	10	0.058	14	-0.029	15	-0.05
121	1.2DL + 1.5LM-MP4 + 1SWL (30 mph) AZI 270	Yes	Y	1	1.2	37	1.5	11	0.058	14		15	-0.058
122	1.2DL + 1.5LM-MP4 + 1SWL (30 mph) AZI 300	Yes	Y	1	1.2	37	1.5	12	0.058	14	0.029	15	-0.05
123	1.2DL + 1.5LM-MP4 + 1SWL (30 mph) AZI 330	Yes	Y	1	1.2	37	1.5	13	0.058	14	0.05	15	-0.029
124	1.2DL + 1.5LM-MP5 + 1SWL (30 mph) AZI 0	Yes	Y	1	1.2	38	1.5	2	0.058	14	0.058	15	
125	1.2DL + 1.5LM-MP5 + 1SWL (30 mph) AZI 30	Yes	Y	1	1.2	38	1.5	3	0.058	14	0.05	15	0.029
126	1.2DL + 1.5LM-MP5 + 1SWL (30 mph) AZI 60	Yes	Y	1	1.2	38	1.5	4	0.058	14	0.029	15	0.05
127	1.2DL + 1.5LM-MP5 + 1SWL (30 mph) AZI 90	Yes	Y	1	1.2	38	1.5	5	0.058	14		15	0.058
128	1.2DL + 1.5LM-MP5 + 1SWL (30 mph) AZI 120	Yes	Y	1	1.2	38	1.5	6	0.058	14	-0.029	15	0.05
129	1.2DL + 1.5LM-MP5 + 1SWL (30 mph) AZI 150	Yes	Y	1	1.2	38	1.5	7	0.058	14	-0.05	15	0.029

Load Combinations (Continued)

	Description	Solve	PDelta	BLCFactor	BLCFactor	BLCFactor	BLCFactor	BLCFactor	BLCFactor	BLCFactor	BLCFactor	BLCFactor	BLCFactor
130	1.2DL + 1.5LM-MP5 + 1SWL (30 mph) AZI 180	Yes	Y	1	1.2	38	1.5	8	0.058	14	-0.058	15	
131	1.2DL + 1.5LM-MP5 + 1SWL (30 mph) AZI 210	Yes	Y	1	1.2	38	1.5	9	0.058	14	-0.05	15	-0.029
132	1.2DL + 1.5LM-MP5 + 1SWL (30 mph) AZI 240	Yes	Y	1	1.2	38	1.5	10	0.058	14	-0.029	15	-0.05
133	1.2DL + 1.5LM-MP5 + 1SWL (30 mph) AZI 270	Yes	Y	1	1.2	38	1.5	11	0.058	14		15	-0.058
134	1.2DL + 1.5LM-MP5 + 1SWL (30 mph) AZI 300	Yes	Y	1	1.2	38	1.5	12	0.058	14	0.029	15	-0.05
135	1.2DL + 1.5LM-MP5 + 1SWL (30 mph) AZI 330	Yes	Y	1	1.2	38	1.5	13	0.058	14	0.05	15	-0.029
136	1.2DL + 1.5LM-MP6 + 1SWL (30 mph) AZI 0	Yes	Y	1	1.2	39	1.5	2	0.058	14	0.058	15	
137	1.2DL + 1.5LM-MP6 + 1SWL (30 mph) AZI 30	Yes	Y	1	1.2	39	1.5	3	0.058	14	0.05	15	0.029
138	1.2DL + 1.5LM-MP6 + 1SWL (30 mph) AZI 60	Yes	Y	1	1.2	39	1.5	4	0.058	14	0.029	15	0.05
139	1.2DL + 1.5LM-MP6 + 1SWL (30 mph) AZI 90	Yes	Y	1	1.2	39	1.5	5	0.058	14		15	0.058
140	1.2DL + 1.5LM-MP6 + 1SWL (30 mph) AZI 120	Yes	Y	1	1.2	39	1.5	6	0.058	14	-0.029	15	0.05
141	1.2DL + 1.5LM-MP6 + 1SWL (30 mph) AZI 150	Yes	Y	1	1.2	39	1.5	7	0.058	14	-0.05	15	0.029
142	1.2DL + 1.5LM-MP6 + 1SWL (30 mph) AZI 180	Yes	Y	1	1.2	39	1.5	8	0.058	14	-0.058	15	
143	1.2DL + 1.5LM-MP6 + 1SWL (30 mph) AZI 210	Yes	Y	1	1.2	39	1.5	9	0.058	14	-0.05	15	-0.029
144	1.2DL + 1.5LM-MP6 + 1SWL (30 mph) AZI 240	Yes	Y	1	1.2	39	1.5	10	0.058	14	-0.029	15	-0.05
145	1.2DL + 1.5LM-MP6 + 1SWL (30 mph) AZI 270	Yes	Y	1	1.2	39	1.5	11	0.058	14		15	-0.058
146	1.2DL + 1.5LM-MP6 + 1SWL (30 mph) AZI 300	Yes	Y	1	1.2	39	1.5	12	0.058	14	0.029	15	-0.05
147	1.2DL + 1.5LM-MP6 + 1SWL (30 mph) AZI 330	Yes	Y	1	1.2	39	1.5	13	0.058	14	0.05	15	-0.029
148	1.2DL + 1.5LM-MP7 + 1SWL (30 mph) AZI 0	Yes	Y	1	1.2	40	1.5	2	0.058	14	0.058	15	
149	1.2DL + 1.5LM-MP7 + 1SWL (30 mph) AZI 30	Yes	Y	1	1.2	40	1.5	3	0.058	14	0.05	15	0.029
150	1.2DL + 1.5LM-MP7 + 1SWL (30 mph) AZI 60	Yes	Y	1	1.2	40	1.5	4	0.058	14	0.029	15	0.05
151	1.2DL + 1.5LM-MP7 + 1SWL (30 mph) AZI 90	Yes	Y	1	1.2	40	1.5	5	0.058	14		15	0.058
152	1.2DL + 1.5LM-MP7 + 1SWL (30 mph) AZI 120	Yes	Y	1	1.2	40	1.5	6	0.058	14	-0.029	15	0.05
153	1.2DL + 1.5LM-MP7 + 1SWL (30 mph) AZI 150	Yes	Y	1	1.2	40	1.5	7	0.058	14	-0.05	15	0.029
154	1.2DL + 1.5LM-MP7 + 1SWL (30 mph) AZI 180	Yes	Y	1	1.2	40	1.5	8	0.058	14	-0.058	15	
155	1.2DL + 1.5LM-MP7 + 1SWL (30 mph) AZI 210	Yes	Y	1	1.2	40	1.5	9	0.058	14	-0.05	15	-0.029
156	1.2DL + 1.5LM-MP7 + 1SWL (30 mph) AZI 240	Yes	Y	1	1.2	40	1.5	10	0.058	14	-0.029	15	-0.05
157	1.2DL + 1.5LM-MP7 + 1SWL (30 mph) AZI 270	Yes	Y	1	1.2	40	1.5	11	0.058	14		15	-0.058
158	1.2DL + 1.5LM-MP7 + 1SWL (30 mph) AZI 300	Yes	Y	1	1.2	40	1.5	12	0.058	14	0.029	15	-0.05
159	1.2DL + 1.5LM-MP7 + 1SWL (30 mph) AZI 330	Yes	Y	1	1.2	40	1.5	13	0.058	14	0.05	15	-0.029
160	1.2DL + 1.5LM-MP8 + 1SWL (30 mph) AZI 0	Yes	Y	1	1.2	41	1.5	2	0.058	14	0.058	15	
161	1.2DL + 1.5LM-MP8 + 1SWL (30 mph) AZI 30	Yes	Y	1	1.2	41	1.5	3	0.058	14	0.05	15	0.029
162	1.2DL + 1.5LM-MP8 + 1SWL (30 mph) AZI 60	Yes	Y	1	1.2	41	1.5	4	0.058	14	0.029	15	0.05
163	1.2DL + 1.5LM-MP8 + 1SWL (30 mph) AZI 90	Yes	Y	1	1.2	41	1.5	5	0.058	14		15	0.058
164	1.2DL + 1.5LM-MP8 + 1SWL (30 mph) AZI 120	Yes	Y	1	1.2	41	1.5	6	0.058	14	-0.029	15	0.05
165	1.2DL + 1.5LM-MP8 + 1SWL (30 mph) AZI 150	Yes	Y	1	1.2	41	1.5	7	0.058	14	-0.05	15	0.029
166	1.2DL + 1.5LM-MP8 + 1SWL (30 mph) AZI 180	Yes	Y	1	1.2	41	1.5	8	0.058	14	-0.058	15	
167	1.2DL + 1.5LM-MP8 + 1SWL (30 mph) AZI 210	Yes	Y	1	1.2	41	1.5	9	0.058	14	-0.05	15	-0.029
168	1.2DL + 1.5LM-MP8 + 1SWL (30 mph) AZI 240	Yes	Y	1	1.2	41	1.5	10	0.058	14	-0.029	15	-0.05
169	1.2DL + 1.5LM-MP8 + 1SWL (30 mph) AZI 270	Yes	Y	1	1.2	41	1.5	11	0.058	14		15	-0.058
170	1.2DL + 1.5LM-MP8 + 1SWL (30 mph) AZI 300	Yes	Y	1	1.2	41	1.5	12	0.058	14	0.029	15	-0.05
171	1.2DL + 1.5LM-MP8 + 1SWL (30 mph) AZI 330	Yes	Y	1	1.2	41	1.5	13	0.058	14	0.05	15	-0.029
172	1.2DL + 1.5LM-MP9 + 1SWL (30 mph) AZI 0	Yes	Y	1	1.2	42	1.5	2	0.058	14	0.058	15	
173	1.2DL + 1.5LM-MP9 + 1SWL (30 mph) AZI 30	Yes	Y	1	1.2	42	1.5	3	0.058	14	0.05	15	0.029
174	1.2DL + 1.5LM-MP9 + 1SWL (30 mph) AZI 60	Yes	Y	1	1.2	42	1.5	4	0.058	14	0.029	15	0.05
175	1.2DL + 1.5LM-MP9 + 1SWL (30 mph) AZI 90	Yes	Y	1	1.2	42	1.5	5	0.058	14		15	0.058
176	1.2DL + 1.5LM-MP9 + 1SWL (30 mph) AZI 120	Yes	Y	1	1.2	42	1.5	6	0.058	14	-0.029	15	0.05
177	1.2DL + 1.5LM-MP9 + 1SWL (30 mph) AZI 150	Yes	Y	1	1.2	42	1.5	7	0.058	14	-0.05	15	0.029
178	1.2DL + 1.5LM-MP9 + 1SWL (30 mph) AZI 180	Yes	Y	1	1.2	42	1.5	8	0.058	14	-0.058	15	

Load Combinations (Continued)

	Description	Solve	PDelta	BLCFactor	BLCFactor	BLCFactor	BLCFactor	BLCFactor	BLCFactor	BLCFactor	BLCFactor	BLCFactor	BLCFactor
179	1.2DL + 1.5LM-MP9 + 1SWL (30 mph) AZI 210	Yes	Y	1	1.2	42	1.5	9	0.058	14	-0.05	15	-0.029
180	1.2DL + 1.5LM-MP9 + 1SWL (30 mph) AZI 240	Yes	Y	1	1.2	42	1.5	10	0.058	14	-0.029	15	-0.05
181	1.2DL + 1.5LM-MP9 + 1SWL (30 mph) AZI 270	Yes	Y	1	1.2	42	1.5	11	0.058	14		15	-0.058
182	1.2DL + 1.5LM-MP9 + 1SWL (30 mph) AZI 300	Yes	Y	1	1.2	42	1.5	12	0.058	14	0.029	15	-0.05
183	1.2DL + 1.5LM-MP9 + 1SWL (30 mph) AZI 330	Yes	Y	1	1.2	42	1.5	13	0.058	14	0.05	15	-0.029
184	1.2DL + 1.5LM-MP10 + 1SWL (30 mph) AZI 0	Yes	Y	1	1.2	43	1.5	2	0.058	14	0.058	15	
185	1.2DL + 1.5LM-MP10 + 1SWL (30 mph) AZI 30	Yes	Y	1	1.2	43	1.5	3	0.058	14	0.05	15	0.029
186	1.2DL + 1.5LM-MP10 + 1SWL (30 mph) AZI 60	Yes	Y	1	1.2	43	1.5	4	0.058	14	0.029	15	0.05
187	1.2DL + 1.5LM-MP10 + 1SWL (30 mph) AZI 90	Yes	Y	1	1.2	43	1.5	5	0.058	14		15	0.058
188	1.2DL + 1.5LM-MP10 + 1SWL (30 mph) AZI 120	Yes	Y	1	1.2	43	1.5	6	0.058	14	-0.029	15	0.05
189	1.2DL + 1.5LM-MP10 + 1SWL (30 mph) AZI 150	Yes	Y	1	1.2	43	1.5	7	0.058	14	-0.05	15	0.029
190	1.2DL + 1.5LM-MP10 + 1SWL (30 mph) AZI 180	Yes	Y	1	1.2	43	1.5	8	0.058	14	-0.058	15	
191	1.2DL + 1.5LM-MP10 + 1SWL (30 mph) AZI 210	Yes	Y	1	1.2	43	1.5	9	0.058	14	-0.05	15	-0.029
192	1.2DL + 1.5LM-MP10 + 1SWL (30 mph) AZI 240	Yes	Y	1	1.2	43	1.5	10	0.058	14	-0.029	15	-0.05
193	1.2DL + 1.5LM-MP10 + 1SWL (30 mph) AZI 270	Yes	Y	1	1.2	43	1.5	11	0.058	14		15	-0.058
194	1.2DL + 1.5LM-MP10 + 1SWL (30 mph) AZI 300	Yes	Y	1	1.2	43	1.5	12	0.058	14	0.029	15	-0.05
195	1.2DL + 1.5LM-MP10 + 1SWL (30 mph) AZI 330	Yes	Y	1	1.2	43	1.5	13	0.058	14	0.05	15	-0.029
196	1.2DL + 1.5LM-MP11 + 1SWL (30 mph) AZI 0	Yes	Y	1	1.2	44	1.5	2	0.058	14	0.058	15	
197	1.2DL + 1.5LM-MP11 + 1SWL (30 mph) AZI 30	Yes	Y	1	1.2	44	1.5	3	0.058	14	0.05	15	0.029
198	1.2DL + 1.5LM-MP11 + 1SWL (30 mph) AZI 60	Yes	Y	1	1.2	44	1.5	4	0.058	14	0.029	15	0.05
199	1.2DL + 1.5LM-MP11 + 1SWL (30 mph) AZI 90	Yes	Y	1	1.2	44	1.5	5	0.058	14		15	0.058
200	1.2DL + 1.5LM-MP11 + 1SWL (30 mph) AZI 120	Yes	Y	1	1.2	44	1.5	6	0.058	14	-0.029	15	0.05
201	1.2DL + 1.5LM-MP11 + 1SWL (30 mph) AZI 150	Yes	Y	1	1.2	44	1.5	7	0.058	14	-0.05	15	0.029
202	1.2DL + 1.5LM-MP11 + 1SWL (30 mph) AZI 180	Yes	Y	1	1.2	44	1.5	8	0.058	14	-0.058	15	
203	1.2DL + 1.5LM-MP11 + 1SWL (30 mph) AZI 210	Yes	Y	1	1.2	44	1.5	9	0.058	14	-0.05	15	-0.029
204	1.2DL + 1.5LM-MP11 + 1SWL (30 mph) AZI 240	Yes	Y	1	1.2	44	1.5	10	0.058	14	-0.029	15	-0.05
205	1.2DL + 1.5LM-MP11 + 1SWL (30 mph) AZI 270	Yes	Y	1	1.2	44	1.5	11	0.058	14		15	-0.058
206	1.2DL + 1.5LM-MP11 + 1SWL (30 mph) AZI 300	Yes	Y	1	1.2	44	1.5	12	0.058	14	0.029	15	-0.05
207	1.2DL + 1.5LM-MP11 + 1SWL (30 mph) AZI 330	Yes	Y	1	1.2	44	1.5	13	0.058	14	0.05	15	-0.029
208	1.2DL + 1.5LM-MP12 + 1SWL (30 mph) AZI 0	Yes	Y	1	1.2	45	1.5	2	0.058	14	0.058	15	
209	1.2DL + 1.5LM-MP12 + 1SWL (30 mph) AZI 30	Yes	Y	1	1.2	45	1.5	3	0.058	14	0.05	15	0.029
210	1.2DL + 1.5LM-MP12 + 1SWL (30 mph) AZI 60	Yes	Y	1	1.2	45	1.5	4	0.058	14	0.029	15	0.05
211	1.2DL + 1.5LM-MP12 + 1SWL (30 mph) AZI 90	Yes	Y	1	1.2	45	1.5	5	0.058	14		15	0.058
212	1.2DL + 1.5LM-MP12 + 1SWL (30 mph) AZI 120	Yes	Y	1	1.2	45	1.5	6	0.058	14	-0.029	15	0.05
213	1.2DL + 1.5LM-MP12 + 1SWL (30 mph) AZI 150	Yes	Y	1	1.2	45	1.5	7	0.058	14	-0.05	15	0.029
214	1.2DL + 1.5LM-MP12 + 1SWL (30 mph) AZI 180	Yes	Y	1	1.2	45	1.5	8	0.058	14	-0.058	15	
215	1.2DL + 1.5LM-MP12 + 1SWL (30 mph) AZI 210	Yes	Y	1	1.2	45	1.5	9	0.058	14	-0.05	15	-0.029
216	1.2DL + 1.5LM-MP12 + 1SWL (30 mph) AZI 240	Yes	Y	1	1.2	45	1.5	10	0.058	14	-0.029	15	-0.05
217	1.2DL + 1.5LM-MP12 + 1SWL (30 mph) AZI 270	Yes	Y	1	1.2	45	1.5	11	0.058	14		15	-0.058
218	1.2DL + 1.5LM-MP12 + 1SWL (30 mph) AZI 300	Yes	Y	1	1.2	45	1.5	12	0.058	14	0.029	15	-0.05

Envelope Node Reactions

Node Label		X [lb]	LC	Y [lb]	LC	Z [lb]	LC	MX [lb-ft]	LC	MY [lb-ft]	LC	MZ [lb-ft]	LC	
1	N39	max	1770.68	5	1584.505	38	4053.183	2	1847.895	27	2066.381	11	997.971	11
2		min	-1771.78	11	269.856	20	-2443.129	20	207.644	20	-2058.472	17	-886.89	17
3	N38	max	2015.493	16	1659.735	34	1659.475	14	518.346	25	1469.279	19	1365.812	37
4		min	-3317.541	10	278.183	15	-2406.744	8	-1336.868	32	-1469.649	13	-98.988	18
5	N34	max	3517.199	5	1729.78	30	1478.738	25	643.221	15	1988.284	15	127.693	22

Envelope Node Reactions (Continued)

Node Label	X [lb]	LC	Y [lb]	LC	Z [lb]	LC	MX [lb-ft]	LC	MY [lb-ft]	LC	MZ [lb-ft]	LC		
6	min	-2126.011	23	317.397	23	-2296.107	7	-1078.191	9	-1992.398	9	-1797.756	29	
7	N4	max	1.288	54	1841.983	27	586.767	20	517.913	27	58.123	11	37.557	11
8		min	-1.299	48	-362.383	20	-2840.195	27	-101.92	20	-53.256	17	-34.377	17
9	N8	max	523.365	24	1854.914	31	1430.414	31	59.175	24	59.31	3	87.145	24
10		min	-2477.067	31	-373.536	24	-302.024	24	-256.012	31	-51.113	21	-454.425	31
11	N12	max	2202.296	35	1652.675	35	1271.347	35	52.262	16	44.882	7	397.405	35
12		min	-533.763	16	-381.237	16	-308.172	16	-241.013	35	-36.024	25	-93.637	16
13	Totals:	max	4860.335	5	9697.074	28	4945.929	14						
14		min	-4860.335	11	2737.238	58	-4945.931	8						

Envelope AISC 15TH (360-16): LRFD Member Steel Code Checks

Member	Shape	Code Check	Loc[in]	LC	Shear	Check	Loc[in]	Dir	Cphi	Pnc [lb]	phi*Pnt [lb]	phi*Mn y-y [lb-ft]	phi*Mn z-z [lb-ft]	Cb	Eqn
1	MP3	PIPE 2.0	0.543	69	2	0.092	69	8	14916.096	32130	1871.625	1871.625	3	H1-1b	
2	MP7	PIPE 2.0	0.541	69	10	0.098	69	3	14916.096	32130	1871.625	1871.625	2.85	H1-1b	
3	MP6	PIPE 2.0	0.518	69	10	0.08	69	11	14916.096	32130	1871.625	1871.625	1.741	H1-1b	
4	MP10	PIPE 2.0	0.51	69	6	0.065	27	13	14916.096	32130	1871.625	1871.625	1.664	H1-1b	
5	MP2	PIPE 2.0	0.508	69	2	0.082	69	3	14916.096	32130	1871.625	1871.625	3	H1-1b	
6	MP11	PIPE 2.0	0.498	69	6	0.105	69	11	14916.096	32130	1871.625	1871.625	2.784	H1-1b	
7	M55	L2.5x2.5x3	0.358	0	8	0.121	0	y 13	27513.18	29192.4	872.574	1971.83	1.5	H2-1	
8	M51	L2.5x2.5x3	0.352	0	4	0.128	0	y 9	27513.18	29192.4	872.574	1971.83	1.5	H2-1	
9	MP8	PIPE 2.0	0.35	69	12	0.121	69	4	14916.096	32130	1871.625	1871.625	3	H1-1b	
10	MP4	PIPE 2.0	0.329	69	4	0.119	69	8	14916.096	32130	1871.625	1871.625	3	H1-1b	
11	MP5	PIPE 2.0	0.327	69	8	0.147	69	4	14916.096	32130	1871.625	1871.625	2.47	H1-1b	
12	M58	L2.5x2.5x3	0.327	0	12	0.127	0	y 5	27513.18	29192.4	872.574	1971.83	1.5	H2-1	
13	MP9	PIPE 2.0	0.314	69	5	0.142	69	12	14916.096	32130	1871.625	1871.625	2.654	H1-1b	
14	MP1	PIPE 2.0	0.294	69	10	0.148	27	8	14916.096	32130	1871.625	1871.625	3	H1-1b	
15	MP12	PIPE 2.0	0.29	69	8	0.1	69	12	14916.096	32130	1871.625	1871.625	2.17	H1-1b	
16	M61	PIPE 2.0	0.278	120.312	11	0.164	135.937	6	6295.422	32130	1871.625	1871.625	2.732	H1-1b	
17	M62	PIPE 2.0	0.276	120.312	4	0.177	118.75	5	6295.422	32130	1871.625	1871.625	2.455	H1-1b	
18	M50	PIPE 2.0	0.263	120.313	8	0.178	118.75	9	6295.422	32130	1871.625	1871.625	2.414	H1-1b	
19	M17	6"x0.37" Plate	0.232	6	5	0.269	4	y 4	36689.504	71928	553.5	8991	1.376	H1-1b	
20	M22	6"x0.37" Plate	0.221	6	9	0.258	4	y 8	36689.504	71928	553.5	8991	1.384	H1-1b	
21	M43	L2x2x2	0.221	0	5	0.009	0	y 30	10626.185	15908.4	402.563	720.708	1.5	H2-1	
22	M39	L2x2x2	0.214	0	9	0.009	0	y 34	10626.185	15908.4	402.563	720.708	1.5	H2-1	
23	M40	L2x2x2	0.213	0	3	0.01	0	z 28	10626.185	15908.4	402.563	720.708	1.5	H2-1	
24	M42	L2x2x2	0.212	0	7	0.01	0	z 32	10626.185	15908.4	402.563	720.708	1.5	H2-1	
25	M41	L2x2x2	0.208	0	13	0.011	0	y 38	10626.185	15908.4	402.563	720.708	1.5	H2-1	
26	M25	6"x0.37" Plate	0.203	6	2	0.273	4	y 12	36689.504	71928	553.5	8991	1.335	H1-1b	
27	M38	L2x2x2	0.201	0	11	0.01	0	z 36	10626.185	15908.4	402.563	720.708	1.5	H2-1	
28	M32	HSS4X4X8	0.16	31.26	30	0.045	31.26	y 8	186016.276	189630	20212.5	20212.5	1	H1-1b	
29	M46	PIPE 3.0	0.16	120.312	211	0.191	89.062	4	59302.836	65205	5748.75	5748.75	1	H1-1b	
30	M28	PIPE 3.0	0.159	120.313	107	0.186	62.5	8	59302.836	65205	5748.75	5748.75	1	H1-1b	
31	M35	HSS4X4X8	0.151	31.26	34	0.042	3.907	z 12	186016.276	189630	20212.5	20212.5	1	H1-1b	
32	M21	HSS4X4X8	0.145	0	11	0.093	0	z 11	184744.527	189630	20212.5	20212.5	1	H1-1b	
33	M29	HSS4X4X8	0.141	31.26	38	0.059	31.26	y 37	186016.276	189630	20212.5	20212.5	1	H1-1b	
34	M16	HSS4X4X8	0.14	0	3	0.1	0	z 3	184744.527	189630	20212.5	20212.5	1	H1-1b	
35	M45	PIPE 3.0	0.139	120.312	171	0.194	89.062	12	59302.836	65205	5748.75	5748.75	1	H1-1b	
36	M10	L2.5x2.5x3	0.125	25.762	30	0.003	50.472	y 4	16389.82	29192.4	872.574	1692.466	1.136	H2-1	



Company : Infinigy Engineering, PLLC
 Designer : JG
 Job Number : 1039-Z0001-B
 Model Name : 881534

1/31/2021
 1:45:18 PM
 Checked By : _____

Envelope AISC 15TH (360-16): LRFD Member Steel Code Checks (Continued)

Member	Shape	Code Check	Loc[in]	LC	Shear Check	Loc[in]	Dir	Lc	phi*Pnc [lb]	phi*Pnt [lb]	phi*Mn y-y [lb-ft]	phi*Mn z-z [lb-ft]	Cb	Eqn	
37	M7	L2.5x2.5x3	0.123	25.762	38	0.002	50.472	y	10	16389.82	29192.4	872.574	1692.466	1.136	H2-1
38	M9	L2.5x2.5x3	0.118	25.762	28	0.002	50.472	z	10	16389.82	29192.4	872.574	1692.466	1.136	H2-1
39	M12	L2.5x2.5x3	0.117	25.762	32	0.003	50.472	z	4	16389.82	29192.4	872.574	1692.466	1.136	H2-1
40	M13	L2.5x2.5x3	0.116	25.762	35	0.003	50.472	y	8	16389.82	29192.4	872.574	1692.466	1.136	H2-1
41	M20	HSS4X4X8	0.113	0	7	0.092	0	z	7	184744.527	189630	20212.5	20212.5	1	H1-1b
42	M15	L2.5x2.5x3	0.102	25.762	36	0.003	50.472	z	8	16389.82	29192.4	872.574	1692.466	1.136	H2-1

APPENDIX D
ADDITIONAL CALCUATIONS


Bolt Calculation Tool, V1.4

PROJECT DATA	
Site Name:	WATERBURY TOWER
Site Number:	881534
Job Code:	1039-Z0001-B
Connection Description:	Standoff to Collar

APPLIED LOADS		
Bolt Tension:	3344.58	lbs
Bolt Shear:	1039.45	lbs

BOLT PROPERTIES		
Bolt Type:	Bolt	-
Bolt Diameter:	0.625	in
Bolt Grade:	A325	-
# of Bolts:	4	-
Threads Excluded?	No	-

BOLT CHECK		
Tensile Strength	20340.15	
Shear Strength	13805.83	
Tensile Usage	16.4%	
Shear Usage	7.5%	
Interaction Check	0.03	≤1.05
Result	Pass	



Bolt Calculation Tool, V1.4

PROJECT DATA	
Site Name:	WATERBURY TOWER
Site Number:	881534
Job Code:	1039-Z0001-B
Connection Description:	Kicker to Collar

APPLIED LOADS		
Bolt Tension:	0.00	lbs
Bolt Shear:	466.49	lbs

BOLT PROPERTIES		
Bolt Type:	Bolt	-
Bolt Diameter:	0.625	in
Bolt Grade:	A325	-
# of Bolts:	4	-
Threads Excluded?	No	-

BOLT CHECK		
Tensile Strength	20340.15	
Shear Strength	13805.83	
Tensile Usage	0.0%	
Shear Usage	3.4%	
Interaction Check	0.00	≤1.05
Result	Pass	




Exhibit F

Power Density/RF Emissions Report

RADIO FREQUENCY EMISSIONS ANALYSIS REPORT
EVALUATION OF HUMAN EXPOSURE POTENTIAL
TO NON-IONIZING EMISSIONS

T-Mobile Existing Facility

Site ID: CTNH452A

670 Captain Neville Drive
Waterbury, Connecticut 06705

April 1, 2021

EBI Project Number: 6221001505

Site Compliance Summary	
Compliance Status:	COMPLIANT
Site total MPE% of FCC general population allowable limit:	14.97%

April 1, 2021

T-Mobile

Attn: Jason Overbey, RF Manager
35 Griffin Road South
Bloomfield, Connecticut 06002

Emissions Analysis for Site: CTNH452A

EBI Consulting was directed to analyze the proposed T-Mobile facility located at **670 Captain Neville Drive** in **Waterbury, Connecticut** for the purpose of determining whether the emissions from the Proposed T-Mobile Antenna Installation located on this property are within specified federal limits.

All information used in this report was analyzed as a percentage of current Maximum Permissible Exposure (% MPE) as listed in the FCC OET Bulletin 65 Edition 97-01 and ANSI/IEEE Std C95.1. The FCC regulates Maximum Permissible Exposure in units of microwatts per square centimeter ($\mu\text{W}/\text{cm}^2$). The number of $\mu\text{W}/\text{cm}^2$ calculated at each sample point is called the power density. The exposure limit for power density varies depending upon the frequencies being utilized. Wireless Carriers and Paging Services use different frequency bands each with different exposure limits; therefore, it is necessary to report results and limits in terms of percent MPE rather than power density.

All results were compared to the FCC (Federal Communications Commission) radio frequency exposure rules, 47 CFR 1.1307(b)(1) – (b)(3), to determine compliance with the Maximum Permissible Exposure (MPE) limits for General Population/Uncontrolled environments as defined below.

General population/uncontrolled exposure limits apply to situations in which the general population may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Therefore, members of the general population would always be considered under this category when exposure is not employment related, for example, in the case of a telecommunications tower that exposes persons in a nearby residential area.

Public exposure to radio frequencies is regulated and enforced in units of microwatts per square centimeter ($\mu\text{W}/\text{cm}^2$). The general population exposure limits for the 600 MHz and 700 MHz frequency bands are approximately $400 \mu\text{W}/\text{cm}^2$ and $467 \mu\text{W}/\text{cm}^2$, respectively. The general population exposure limit for the 1900 MHz (PCS), 2100 MHz (AWS) and 11 GHz frequency bands is $1000 \mu\text{W}/\text{cm}^2$. Because each carrier will be using different frequency bands, and each frequency band has different exposure limits, it is necessary to report percent of MPE rather than power density.

Occupational/controlled exposure limits apply to situations in which persons are exposed as a consequence of their employment and in which those persons who are exposed have been made fully aware of the potential for exposure and can exercise control over their exposure. Occupational/controlled exposure limits also apply where exposure is of a transient nature as a result of incidental passage through a location where exposure levels may be above general population/uncontrolled limits (see below), as long as the exposed person has been made fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Additional details can be found in FCC OET 65.

CALCULATIONS

Calculations were done for the proposed T-Mobile Wireless antenna facility located at 670 Captain Neville Drive in Waterbury, Connecticut using the equipment information listed below. All calculations were performed per the specifications under FCC OET 65. Since T-Mobile is proposing highly focused directional panel antennas, which project most of the emitted energy out toward the horizon, all calculations were performed assuming a lobe representing the maximum gain of the antenna per the antenna manufacturer's supplied specifications, minus 10 dB for directional panel antennas and 20 dB for highly focused parabolic microwave dishes, was focused at the base of the tower. For this report, the sample point is the top of a 6-foot person standing at the base of the tower. For power density calculations, the broadcast footprint of the AIR6449 antenna has been considered. Due to the beamforming nature of this antenna, the actual beam locations vary depending on demand and are narrow in nature. Using the broadcast footprint accounts for the potential location of beams at any given time.

For all calculations, all equipment was calculated using the following assumptions:

- 1) 2 LTE channels (600 MHz Band) were considered for each sector of the proposed installation. These Channels have a transmit power of 30 Watts per Channel.
- 2) 1 NR channel (600 MHz Band) was considered for each sector of the proposed installation. This Channel has a transmit power of 80 Watts.
- 3) 2 LTE channels (700 MHz Band) were considered for each sector of the proposed installation. These Channels have a transmit power of 30 Watts per Channel.
- 4) 4 GSM channels (PCS Band - 1900 MHz) were considered for each sector of the proposed installation. These Channels have a transmit power of 30 Watts per Channel.
- 5) 2 LTE channels (PCS Band - 1900 MHz) were considered for each sector of the proposed installation. These Channels have a transmit power of 60 Watts per Channel.

- 6) 2 LTE channels (AWS Band – 2100 MHz) were considered for each sector of the proposed installation. These Channels have a transmit power of 60 Watts per Channel.
- 7) 1 LTE channel (BRS Band - 2500 MHz) was considered for each sector of the proposed installation. This Channel has a transmit power of 120 Watts.
- 8) 1 NR channel (BRS Band - 2500 MHz) was considered for each sector of the proposed installation. This Channel has a transmit power of 120 Watts.
- 9) All radios at the proposed installation were considered to be running at full power and were uncombined in their RF transmissions paths per carrier prescribed configuration. Per FCC OET Bulletin No. 65 - Edition 97-01 recommendations to achieve the maximum anticipated value at each sample point, all power levels emitting from the proposed antenna installation are increased by a factor of 2.56 to account for possible in-phase reflections from the surrounding environment. This is rarely the case, and if so, is never continuous.
- 10) For the following calculations, the sample point was the top of a 6-foot person standing at the base of the tower. The maximum gain of the antenna per the antenna manufacturer's supplied specifications, minus 10 dB for directional panel antennas and 20 dB for highly focused parabolic microwave dishes, was used in this direction. This value is a very conservative estimate as gain reductions for these particular antennas are typically much higher in this direction.
- 11) The antennas used in this modeling are the RFS APX16DWV-16DWV-S-E-A20 for the 2100 MHz channel(s), the RFS APXVAALL24_43-U-NA20 for the 600 MHz / 600 MHz / 700 MHz / 1900 MHz / 1900 MHz channel(s), the Ericsson AIR 6449 for the 2500 MHz / 2500 MHz channel(s) in Sector A, the RFS APX16DWV-16DWV-S-E-A20 for the 2100 MHz channel(s), the RFS APXVAALL24_43-U-NA20 for the 600 MHz / 600 MHz / 700 MHz / 1900 MHz / 1900 MHz channel(s), the Ericsson AIR 6449 for the 2500 MHz / 2500 MHz channel(s) in Sector B, the RFS APX16DWV-16DWV-S-E-A20 for the 2100 MHz channel(s), the RFS APXVAALL24_43-U-NA20 for the 600 MHz / 600 MHz / 700 MHz / 1900 MHz / 1900 MHz channel(s), the Ericsson AIR 6449 for the 2500 MHz / 2500 MHz channel(s) in Sector C. This is based on feedback from the carrier with regard to anticipated antenna selection. All Antenna gain values and associated transmit power levels are shown in the Site Inventory and Power Data table below. The maximum gain of the antenna per the antenna manufacturer's supplied specifications, minus 10 dB for directional panel antennas and 20 dB for highly focused parabolic microwave dishes, was used for all calculations. This value is a very conservative estimate as gain reductions for these particular antennas are typically much higher in this direction.

- 12) The antenna mounting height centerline of the proposed antennas is 140 feet above ground level (AGL).
- 13) Emissions values for additional carriers were taken from the Connecticut Siting Council active database. Values in this database are provided by the individual carriers themselves.
- 14) All calculations were done with respect to uncontrolled / general population threshold limits.

T-Mobile Site Inventory and Power Data

Sector:	A	Sector:	B	Sector:	C
Antenna #:	1	Antenna #:	1	Antenna #:	1
Make / Model:	RFS APX16DWV-16DWV-S-E-A20	Make / Model:	RFS APX16DWV-16DWV-S-E-A20	Make / Model:	RFS APX16DWV-16DWV-S-E-A20
Frequency Bands:	2100 MHz	Frequency Bands:	2100 MHz	Frequency Bands:	2100 MHz
Gain:	15.9 dBd	Gain:	15.9 dBd	Gain:	15.9 dBd
Height (AGL):	140 feet	Height (AGL):	140 feet	Height (AGL):	140 feet
Channel Count:	2	Channel Count:	2	Channel Count:	2
Total TX Power (W):	120 Watts	Total TX Power (W):	120 Watts	Total TX Power (W):	120 Watts
ERP (W):	4,668.54	ERP (W):	4,668.54	ERP (W):	4,668.54
Antenna AI MPE %:	0.93%	Antenna BI MPE %:	0.93%	Antenna CI MPE %:	0.93%
Antenna #:	2	Antenna #:	2	Antenna #:	2
Make / Model:	RFS APXVAALL24_43-U-NA20	Make / Model:	RFS APXVAALL24_43-U-NA20	Make / Model:	RFS APXVAALL24_43-U-NA20
Frequency Bands:	600 MHz / 600 MHz / 700 MHz / 1900 MHz / 1900 MHz	Frequency Bands:	600 MHz / 600 MHz / 700 MHz / 1900 MHz / 1900 MHz	Frequency Bands:	600 MHz / 600 MHz / 700 MHz / 1900 MHz / 1900 MHz
Gain:	12.95 dBd / 12.95 dBd / 13.65 dBd / 15.45 dBd / 15.45 dBd	Gain:	12.95 dBd / 12.95 dBd / 13.65 dBd / 15.45 dBd / 15.45 dBd	Gain:	12.95 dBd / 12.95 dBd / 13.65 dBd / 15.45 dBd / 15.45 dBd
Height (AGL):	140 feet	Height (AGL):	140 feet	Height (AGL):	140 feet
Channel Count:	11	Channel Count:	11	Channel Count:	11
Total TX Power (W):	440 Watts	Total TX Power (W):	440 Watts	Total TX Power (W):	440 Watts
ERP (W):	12,569.87	ERP (W):	12,569.87	ERP (W):	12,569.87
Antenna A2 MPE %:	3.66%	Antenna B2 MPE %:	3.66%	Antenna C2 MPE %:	3.66%
Antenna #:	3	Antenna #:	3	Antenna #:	3
Make / Model:	Ericsson AIR 6449	Make / Model:	Ericsson AIR 6449	Make / Model:	Ericsson AIR 6449
Frequency Bands:	2500 MHz / 2500 MHz	Frequency Bands:	2500 MHz / 2500 MHz	Frequency Bands:	2500 MHz / 2500 MHz
Gain:	17.3 dBd / 17.3 dBd	Gain:	17.3 dBd / 17.3 dBd	Gain:	17.3 dBd / 17.3 dBd
Height (AGL):	140 feet	Height (AGL):	140 feet	Height (AGL):	140 feet
Channel Count:	2	Channel Count:	2	Channel Count:	2
Total TX Power (W):	240 Watts	Total TX Power (W):	240 Watts	Total TX Power (W):	240 Watts
ERP (W):	12,888.76	ERP (W):	12,888.76	ERP (W):	12,888.76
Antenna A3 MPE %:	2.58%	Antenna B3 MPE %:	2.58%	Antenna C3 MPE %:	2.58%

Site Composite MPE %	
Carrier	MPE %
T-Mobile (Max at Sector A):	7.18%
AT&T	3.93%
Sprint	3.76%
XM Sat Radio	0.1%
Site Total MPE % :	14.97%

T-Mobile MPE % Per Sector	
T-Mobile Sector A Total:	7.18%
T-Mobile Sector B Total:	7.18%
T-Mobile Sector C Total:	7.18%
Site Total MPE % :	14.97%

T-Mobile Maximum MPE Power Values (Sector A)							
T-Mobile Frequency Band / Technology (Sector A)	# Channels	Watts ERP (Per Channel)	Height (feet)	Total Power Density ($\mu\text{W}/\text{cm}^2$)	Frequency (MHz)	Allowable MPE ($\mu\text{W}/\text{cm}^2$)	Calculated % MPE
T-Mobile 2100 MHz LTE	2	2334.27	140.0	9.35	2100 MHz LTE	1000	0.93%
T-Mobile 600 MHz LTE	2	591.73	140.0	2.37	600 MHz LTE	400	0.59%
T-Mobile 600 MHz NR	1	1577.94	140.0	3.16	600 MHz NR	400	0.79%
T-Mobile 700 MHz LTE	2	695.22	140.0	2.78	700 MHz LTE	467	0.60%
T-Mobile 1900 MHz GSM	4	1052.26	140.0	8.43	1900 MHz GSM	1000	0.84%
T-Mobile 1900 MHz LTE	2	2104.51	140.0	8.43	1900 MHz LTE	1000	0.84%
T-Mobile 2500 MHz LTE	1	6444.38	140.0	12.90	2500 MHz LTE	1000	1.29%
T-Mobile 2500 MHz NR	1	6444.38	140.0	12.90	2500 MHz NR	1000	1.29%
						Total:	7.18%

• NOTE: Totals may vary by approximately 0.01% due to summation of remainders in calculations.

Summary

All calculations performed for this analysis yielded results that were **within** the allowable limits for general population exposure to RF Emissions.

The anticipated maximum composite contributions from the T-Mobile facility as well as the site composite emissions value with regards to compliance with FCC's allowable limits for general population exposure to RF Emissions are shown here:

T-Mobile Sector	Power Density Value (%)
Sector A:	7.18%
Sector B:	7.18%
Sector C:	7.18%
T-Mobile Maximum MPE % (Sector A):	7.18%
Site Total:	14.97%
Site Compliance Status:	COMPLIANT

The anticipated composite MPE value for this site assuming all carriers present is **14.97%** of the allowable FCC established general population limit sampled at the ground level. This is based upon values listed in the Connecticut Siting Council database for existing carrier emissions.

FCC guidelines state that if a site is found to be out of compliance (over allowable thresholds), that carriers over a 5% contribution to the composite value will require measures to bring the site into compliance. For this facility, the composite values calculated were well within the allowable 100% threshold standard per the federal government.