

Centerline Communications Ryan Clark 750 West Center Street, Floor 3 West Bridgewater, MA 02379 203-300-7310 rclark@clinellc.com

July 22, 2019

Members of the Siting Council Connecticut Siting Council Ten Franklin Square New Britain, CT 06051

Notice of Exempt Modification 1669 Thomaston Avenue Waterbury, CT 06704 Latitude: 41.58981 Longitude: -73.054228

T-Mobile Site#: CT11214D_L600

Dear Ms. Bachman:

T-Mobile currently maintains nine (3) antennas at the 130-foot level and (6) antennas at the 132-foot level of the existing 134-foot smokestack tower at 1669 Thomaston Avenue Waterbury, CT 06704. The 134-foot smokestack is owned by Landmark Dividend, LLC and the property is owned by 1669 Thomaston Ave, LLC. T-Mobile now intends to replace (3) three L600/L700 antennas at the 130-foot level. The existing antenna mounts can support the proposed antenna installations with the following modification: new Stiff-Arm Kits at Mount pipe location 4 @ 0'-9" about the Top Horizontal on all three sectors.

Planned Modifications:

Remove:

- (3) Coax Lines
- (3) Smart Bias-T's

Remove and Replace:

- (3) LNX 6515DS A1M Antennas (Remove) (3) LNX- APXVAARR24 600/700 MHz Antennas (Replace)
- (3) RRUS11 B12 radios (Remove at ground level) (3) RRU 4449 B71 B12 radios (Replace at antenna level)

Install New:

(2) Hybrid Lines

Existing to Remain:

- (3) AIR32 B66A B2A 1900 MHz/2100 MHz
- (3) LNX- APX16DWV 1900 MHz
- (15) Coax Lines
- (6) TMA's
- (1) Hybrid Line

This facility was approved on November 23, 1998 by the City of Waterbury BPD/ZD (File No. 87500). Approved by the City of Waterbury to install antenna to the existing smokestack with no conditions. Please see attached documentation.

Please accept this letter as notification pursuant to Regulations of Connecticut State Agencies § 16- SOj-73, for construction that constitutes an exempt modification pursuant to R.C.S.A. § 16-50j-72(b)(2). In accordance with R.C.SA. § 16-SOj-73, a copy of this letter is being sent to Mayor Neil M. O'Leary, City of Waterbury as chief elected official, Landmark Dividend, LLC as tower owner, 1669 Thomaston Ave, LLC as property owner, and the City of Waterbury Planning Department.

The planned modifications to the facility fall squarely within those activities explicitly provided for in R.C.S;A. § 16-50j-72(b)(2).

- 1. The proposed modifications will not result in an increase in the height of the existing structure.
- 2. The proposed modifications will not require the extension of the site boundary.
- 3. The proposed modifications will not increase noise levels at the facility by six decibels or more, or to levels that exceed state and local criteria.
- 4. The operation of the replacement antennas will not increase radio frequency emissions at the facility to a level at or above the Federal Communications Commission safety standard.
- 5. The proposed modifications will not cause a change or alteration in the physical or environmental characteristics of the site.
- 6. The existing structure and its foundation can support the proposed loading.

For the foregoing reasons, T-Mobile respectfully submits that the proposed modifications to the above referenced telecommunications facility constitute an exempt modification under R.C.S.A. § 16-50j-72(b)(2).

Respectfully submitted,

Ryan Clark

Ryan Clark

Mobile: 203-300-7310 Fax: 508-819-3017

Office: 117 Carol Street Danbury, CT 06810

Email: rclark@clinellc.com

Attachments

cc: Mayor Neil M. O'Leary, City of Waterbury as chief elected official Landmark Dividend, LLC as tower owner 1669 Thomaston Ave, LLC as property owner City of Waterbury Planning Department, Clifford C. Brammer III, Land Use Officer

Exhibit A

Original Facility Approval



BLDGAPP6

THE CITY OF WATERBURY

DEPARTMENT OF INSPECTIONS

235 Grand Street, Waterbury, CT 06702 (203) 574-6832

	Building Permit
PLEASE PRINT LEGIBLY (Shaded areas for Office Applicant:	use only!) Date: 6/25 , 2002
Company	
Name: URS Corporation DES	
Address: 795 Brook Street, Bldy 5	License No.
City: Rocky Hill State: CT Zip	Phone No. <u>860-529-8882</u>
Location Owner Location of Work:	Owner's Name: John Fzy Brownstein Real
Address: 1669 thomaston Avenue	Address: 1669 Thomaston Ave.
Waterbury, CT 06067	City: Water bury State: CT
	Architect:
I hereby certify that the proposed work is authorized by the owner of record and that I	Architect's Name: Ignacio C. Artaiz
have been authorized by the owner to make this application as an authorized agent and we	Address: U125 (orp. 795 Brook St. Blag 5
agree to conform to all applicable laws of this jurisdiction.	
	City: Rocky Hill State: CT
Print Name: Peter H. Maxwell	Signature:
(must check one) Proposed Use C Existing U	the second the control of the second
Commercial Restaurant Res	j 55 j attaon 1611
	sidential Temp. Structure her telecommunication Plan(s) on File? Yes ON
What are you building? Sprint PCS-teleco	Ommunication Cacility
What are you building? Spent PCS-teleco	ack, equipment cabinet platform on roo
st. Cost \$ 8 2,000 Start Work Date:	Zone: Continued on bac
REQUIRED? Department	
Was ONE TOWNS AND A	QUIRED? Department Yes O No HEALTH
	Yes O No HEALTHYes O No TRAFF
	YES O No DEL. TAX (allow 5 days)
Yes O No FIR MSH	Yes O No WATER
	Yes O No WASTE
EE: \$ /240.00 Fine: \$	CITY OF
ofO: \$ /5.00 Date Issued:	
2741 0 17/ C/ 1/2	
57 AL: \$ 106 8, 10 Title:	CONN.
12 j 3, 12 CK# 9689 x 9733	
0 LA 9KHY × 1/50	



THE CITY OF WATERBURY

DEPARTMENT OF INSPECTIONS

Certificate	No.
28307	

ficate of Use and Occupa

'Date:

This is to certif	fy that address	1669 Thomaston Ave		may be used for
		telecommunication facility		_ and is in compliance
with the provis	sions of the State	of Connecticut Basic Building Code.		
Use Group (in	accordance with	provisions of Article 3):		<i>(i, i, i</i>
Fire Grading	(as defined in Ta	ble 902):		par.
Maximum Liv	ve Load (as prese	eribed in Table 1106, p.s.f.): 1st2	nd	3rd
Permit No. 22	08D	Date: 7-12-02		
		·	Buildi	ng Official
REQUIRED?	O No.	Department		
Yes	O No	Department ZONING:		
Yes .:	O No - O No - O No - O No	Department ZONING: ENGINEERING:		
Yes	₽ No	Department ZONING:		
O Yes	=0-No .0-No	Department ZONING: ENGINEERING: CITY PLAN:		
O Yes O Yes	No No O No	Department ZONING: ENGINEERING: CITY PLAN: FIRE MARSHAL:		
O Yes O Yes O Yes O Yes	9 No 9 No 0 No 9 No	Department ZONING: ENGINEERING: CITY PLAN: FIRE MARSHAL: INLAND WETLANDS:		



THE CITY OF WATERBURY MEMORANDUM

DATE: JUNE 26,2002

FROM: KAREN MULCHAY, TAX COLLECTOR

TO: DEPT. OF BUILDING INSPECTIONS

SUBJECT: TAX CLEARANCE

AS OF THIS DATE, THE RECORDS IN THE TAX COLLECTOR'S OFFICE INDICATES THAT THE FOLLOWING IS NOT DELINQUENT.

BROWNSTEIN REALTY 1669 THOMASTON AVE. WATERBURY, CT

FOR: 1669 THOMASTON AVE

IF YOU HAVE ANY FURTHER QUESTIONS, DO NOT HESITATE TO CALL THE OFFICE AT 574-6935.

VERY TRULY YOURS,

KAREN MULCHAY TAX COLLECTOR

KM/dk



STATE OF CONNECTICUT

DEPARTMENT OF CONSUMER PROTECTION

165 CAPITOL AVE • HARTFORD CT 06106-1630

Be it known that

CONSTRUCTION SERVICES OF BRANFORD

63-3 NORTH BRANFORD ROAD BRANFORD, CT 06405

is certified by the Department of Consumer Protection as a registered

MAJOR CONTRACTOR

Registration Number: MCO.900576

Effective Date: 07/01/2001 Expiration Date: 06/30/2002

lames Fleming, Commissioner

r. uz P.06

FEB 13 2002 15:05 FR GBAC, INC 203 239 3843 TO 4811135

-48		6026500	TCATE OF LIABIL	ITY INSI	URANCE		02/	2/2002
8	CORU-	CERIII	ICAIE OF LIADIE	THE CENT	FICATE IS ISSU	ED AS A MATTER OF	INFO	RMATION MISICATE
700	ucer	NO IDANOE AC	203-985-9034	I ANIY AND	CUMPERO RE		reto (Nicola)	THE ROOM OF THE PERSON OF THE
		NSURANCE AG		ALTER THE	COVERAGE AL	TE DOES NOT AMEN FORDED BY THE PO	MOIR	BELVIOL
	2ND FLOOR 100 BROADW	/AY				Fording Coverag		
	NORTH HAVE	N, CT 08473						
Neu				INSURER AL U	NITED NATION	4L	A Administration	
	CONS	TRUCTION SEF	RVICES OF BRANFORD, LLC	production of	The state of the s			
	63-3 N	IORTH BRANFO	ORD RD.		IOYAL.			
	BRAN	FORD, CT 0540)5	ingurer D: 17	WILL.			
•••								NAME AND ADDRESS OF THE PARTY O
		ADLINANCO LIGISTE	DESCRIPTION OF ANY CONTRACT OR OTHER	RANGED AR	OVE FOR THE POL	JOS PERIOD INCICATED. I	MAY BE	IBBUED OR
af	IA MEGRINEWEN	(, I great un cont	AND DESCRIPTION OF THE PROPERTY OF THE PROPERT	EKEIN IS SUPPEZ	TO ALL THE TERM	18. Exclusions and co		ns of such
P(av pertain, the Micies. Aggrec	insurance affe Late limits show	M MAY HAVE BEEN REDUCED BY PAID	CLAIME.	YEAR OF THE BASSAN	, LAM	49 	
1		REVNANCE	MONEY NOTES	PATE TOTAL		EACH OCCURRENCE	8	1,000,000
	GENERAL LIABRIT	4		1/04/02	1/04/03	FIRE DAMAGE (ANY 644 (69)	3	50,000
A		GENERAL LUBILITY	L7158923	10 R da A C	110-11	MEN-ERT (MAY one person)	8	5,000
	l (HABE X COOLA			1	PERSONAL & ADV INJURY	1	1,000,000
	X GENERAL	AGGREG.]	GENERAL AGGREGATE	8	2,000,000
	100 - 0004				•	PRODUCTS - COMPANY #60	\$	2,000,000
	POLICY X	FROT LOC						
	AUTO HORILE LIAL		B101949A234	12/13/01	12/19/02	COMBINED SINGLE LIMIT	.8.	1,000,000
B	T WAS WILD					BODILY INJURY (Per persen)	\$	
	SCMEDVLED HIRED AUTOG					(Let despand) BODITA IMITALA	8	
	MON-OWNED	AUTOS				PROPERTY DAMAGE	s	
Estatograda						AUTO ONLY - EA ACCIDENT	8	
ĺ	DAYAUTO	¥	}			OTHER THAN EA ACC		· · · · · · · · · · · · · · · · · · ·
							September 1	10,000,000
	EXCEPT LIBBILITY	7			48487	EACH OCCURRENCE		10,000,000
D	X BOOUR	CLAIMB MADE	PHN016837	1/04/02	1/04/03	ACERECATE	18	10,000,000
							8	
	DEDUCTOR	68 888		l			6	
-	X RETENTION				-AM7100	是 公司 公司 公司 公司 公司 公司 公司 公司 公司 公司	4	
C	Workers Completed Liai		6858UB717X471	02/07/02	02/07/03	E.L. EACH ACCIDENT	\$	1,000,000
1	1					E.L. DISEASE - EA EMPLOYE		1,000,000
						B.L. DISEASE - POLICY LIMIT	[] [1,000,000
В	PROPERTY	OF OTHERS	QT-860-829X8931 ALL RISK BASIS	12/13/01	12/13/02	\$2,000,000		
			1	NUMBER AL BORLOTT	neg		<u>Squarence</u>	
PE	Cription of open Cardination	atoralocationem Sie eod comb	THICLERAFEICLUSIONS ADDED BY ENDORSEME REHENSIVE & COLLISION	M.1966. Ser Supame				
30.	OO MEDDOOUR	TE LOW OCINIL	INC. ITIABLAE & SASSIGIAL					
C	enticate ho	OLDER Y A	ODITIONAL INQUEED; INSURER LETTER: X	CANCELLA	LTION	- 100 to		n ties excensional
				- SKONFBYNZ	OF THE ALLOW DESCRIPTION	HER WILL CHORAVOR TO MA		MATTINE SYNT
1				DATO THERE	dy. The Issuind Dieu	es haves to the perty bri	الأستعمر م	E TO BO GO BYALL
		INT SPECTRUM		NOTICE TO TO	ne certykate iv/li 18legazzek og ligbi	Tem of the rest from the	المراجد . عواليان	B, 100-A025/58-50
			BLVD., SUITE 800	ACCRECATIVA			7	
	MAH	Wah, NJ 0749	5		ISPREASHTATIVE	JIMA	1	
						MAKA	L	OMEON 400
·A	5000 25-0-17E	· ·			()			



THE GITY OF WATERBURY

DEPARTMENT OF INSPECTIONS

235 Grand Street, Waterbury, CT 06702 (203) 574-6832

2208-0

Application for Building Permit

PLEASE PRINT LEG	IBLY (Shaded areas fo	r Office use only!)	Date: 6/25	, 2002
Applicant:				
Company Name: URS Corpe	oration AES		License No.	
Address: 795 Bro	ok Street, Bld	45		0-529-8882
city: Rocky H	State: C	<u> Zip: 06067</u>		
Location of Work:	Locatio	Owner: Owner's N	ame: John Fay/B	rownstein Realty
Address: 1669 T	nomeston Aven		1669 Thomast	/ 1
Waterbu	· y, CT 060	<u> </u>	eterbury	
I hereby certify that	the proposed work	Architect:		
authorized by the ow	ner of record and th	at I Architect's	Name: <u>lqneeio</u>	2. Artsiz
this application as an	authorized agent and	we Address:	125 (orp. 795 B	rookst. Bldq 5
agree to conform to a jurisdiction.	ii applicable laws of	UUS 📳	ly Hill	,
			1/4//	
Print Name: <u>Peter</u>	H. Maxwell	Signature:	1-201/h	man de la companya della companya de
(must check one) Pro	posed Use 🖸 Exi	sting Use F	Floodplain? O Yes O	No If yes, attach form.
☐ Commercial ☐	Restaurant	Residential		e
				The second secon
What are you building (Please describe in de	tail) existing smo	kestack, equ	ipment cabinet	platform on roof
st. Cost \$ <u>8 2,000</u>	Start Work Date:		Zone:	continued on back
REQUIRED? Department		REQUIRED?	Department	
Yes O No ZONING		_ O Yes O No	HEALTH	
O Yes O No ENG'G	· (1955年) - 中國語學 (1954年) (1954年) - 1957年 - 19	_ O Yes O No	TRAFF	
O Yes O No CITY PL		_ Yes O No	DEL. TAX (allow 5 days)	
Yes O No FIR MSH		_ O Yes O No	WATER	
O Yes O No IN/WET		_ O Yes O No	WASTE	· 政治企业自由的 基础程序 可可能的 "是是我们的,这种是是我们的。"
EE: \$	Fine: \$			STE CITY OF
ofO: \$	Date Issued			
d. Fee: \$	Issued by:_			A STATE OF THE SERVICE OF THE SERVIC
OTAL: \$	Title:			CONN



June 19, 2002

Mr. Brett Phair Sprint PCS 1 International Boulevard, 8th floor Mahwah, New Jersey 07492

Reference:

Proposed Telecommunications Facility

Sprint PCS Site No.: CT43XC845

1669 Thomaston Avenue Waterbury, Connecticut

F300002072.33

Dear Mr. Phair,

URS Corporation AES has been retained by Sprint PCS to provide contract documents for the installation of a telecommunications facility at 1669 Thomaston Avenue in Waterbury, Connecticut. The facility will consist of antennas to be mounted to the existing smokestack at the facility and equipment to be mounted on the roof of an existing structure.

The equipment will be installed on a steel platform designed to support 11,000 lbs of equipment cabinets. The steel platform is designed to be supported on the existing parapet wall supported by the bearing wall located directly below the parapet wall at one side and mounted to the existing masonry bearing wall on the other side. Construction documents have been prepared by URS for the installation of the proposed Sprint PCS facility. See drawings S-1 through S-3 dated 06/18/02 for structural details of the proposed steel platform.

The purpose of this letter is certify that the existing building structure supporting the Sprint PCS steel platform has sufficient structural capacity to support the proposed Sprint PCS installation. This analysis and design are based on requirements of the Connecticut State Building Code dated 1999 and the latest supplement and amendments.

Please call if there are any questions

Sincerely,

URS Corporation AES

Mohsén Sahirad, P.E. Senior Structural Engineer

cc:

A. Abadjian - URS
I. Artaiz, AIA - URS
D. Roberts, AIA - URS

CF/Book

CLIENT NAME:

Sprint PCS

SITE NAME:

Waterbury

SITE NUMBER:

CT43XC845

SITE ADDRESS:

1669 Thomaston Avenue

Waterbury, CT

SITE TYPE:

Rooftop / chimney-mounted antennas

SITE VISIT TYPE:

Structural inspection

PROJECT NO .:

F300002072.33 / F07

DATE OF VISIT:

9/26/02

ATTENDEES:

Ron Vaughn, McPhee Electric (ME)

Chris Taroli, Eastern Inc. (El)

Peter Maxwell, URS Corp. (URS)

WEATHER:

Light rain, 75° at 1:00

PREPARED BY:

Peter Maxwell

PROGRESS / ACTIVITIES: Structural steel attachment inspection

Steel attachment to masonry was in progress. The following was noted:

1. Beam: W8 on parapet was boited at location as shown on documents. Required grout space was provided.

2. Mounting plates: Wall attachment was per CD's, with flanges prepared for beam bolting. Beam locations have been raised to level with beam height at parapet.

Bolting: All locations encountered voids, and therefore were attached using Hilti HY-150 system.

ME will advise URS when masonry preparation is completed for re-pointing inspection.

G. Graveline, City of Waterbury 203-574-6854

L. Thoman, Sprint PCS 201-684-4170

D. Barker, McPhee Electric 674-9385

A. Abadjian, URS Corp.

DR, NA, MS, CF. Book

URS Corporation 500 Enterprise Drive, Suite 38 Rocky Hill. CT 06067 Tel: 860.529.8882 Fax: 860.529.3991

The state of the s		riggitöknasman (* Harrichististist		efektet 1. mai 1. 1843 (kolo e e e e e e e e e e e e e e e e e e



Thate: Chipatolip VMaxipeliburiba

DEPARTMENT OF INSPECTIONS

235 Grand Street, Waterbury, CT 06702 (203) 574-6832

Application for Building Reimit

)
	0-014-4538
Location of Work: Location Owner: Owner's Name: Browns	tein Kerlty
Address: 1669 Thomaston avenue Address: 1669 Tho	, , , , , , ,
Waterbury, CT 06710 City/State: Waterbury,	
I hereby certify that the proposed work is authorized	
by the owner of record and that I have been	·
authorized by the owner to make this application as an authorized agent and we agree to conform to all applicable laws of this jurisdiction.	
applicable laws of this jurisdiction. City/State:	
Print Name: MARIER BURBANK Signature: Marie C.	Bulanh
Commercial Restaurant Residential Temp. Str. Industrial Hospital Other Leonminication at Epis. What are you building? adding 3 fantennes and cabinet at experience of the property of the pro	ın(s) on File? ØYes O No
Est. Cost \$ 8,000 Start Work Date: 7/03 Zone: IC	
REQUIRED? Department // REQUIRED? Department	STANDARD COMMENCENTIAL CONTRACTOR OF THE STANDARD STANDAR
Yes O No ZONING MANAGER OYES O NO HEALTH	
OYes O No ENG'G O Yes O No TRAFF	
	(5)
O'Yes: O'No: CITY PL: Ø Yes: O'No DEL. TAX (allow 5 da	(5)
O Yes O No CITY PL	(5)
O Yes O No CITY PL	(5)
O Yes O No CITY PL Ø Yes O No DEL. TAX (allow 5 days) Ø Yes O No FIR MSH Ø Yes O No WATER D Yes O No IN/ WET O Yes O No WASTE	corrollar de la corrollar de l



CERTOFOL

THE CITY OF WATERBURY

DEPARTMENT OF INSPECTIONS

Certificate No.

29274

Certificate of Use and Occupancy

Date:

		1669 Thomaston Ave	may be used for
		3 antennaes and cabinet	and is in compliance
with the prov	isions of the Sta	ate of Connecticut Basic Building Code.	
Use Group (i	n accordance w	rith provisions of Article 3):	
ire Grading	; (as defined in	Table 902):	
vIaximum Li	ive Load (as pr	rescribed in Table 1106, p.s.f.): 1st 2nd	d 3rd
		3230 7-17-03	
سيداني والمارية		· ————————————————————————————————————	Building Official
REQUIRED?	Actoria de la companya del companya del companya de la companya de	Department	not september of the sector of
REQUIRED?	O No	Department ZONING:	
معانتظنان	O No	·	
O-Yes		ZONING:	<u> </u>
O Yes		ZONING:	
O Yes O Yes	@*No 	ZONING:ENGINEERING:	
O Yes O Yes O Yes O Yes O Yes		ZONING:	
O Yes O Yes O Yes		ZONING:	



				11	,		7/.2.762
A	CORD. CERTIF	ICATE OF LIAE	BILITY IN	ISU	RAN	CE COR NC	107/00/20
RODUK			THICCEPTI	FUCATR	K ISSUPIL	AS A MATTER OF INF	NOTAMATION
אטוטעה	210			יראובול <i>ב</i>	った かい ちんり	ATS TIPON THE CERTI	HUATE
ewb	oridge Coverage Corp.		HOLDER, TI	105 CER	TIPICATE	DOES NOT AMEND, EX ROED BY THE POLICI	POBELOW.
666	Newbridge Road		AL IER IHE	COAR	AUSC AFFC	MOLD BY THE PARTY.	
ort	th Bellmore NY 11710			INS	URERS AI	FORDING COVERAGE	
por	na:516-781-9000 Fax:	516-781-9172		- 1			
N SULPE	ם	-				lity Insurance	Corp
			INGURAR 6: I	Lart	ord Ins	urance Co.	
		- bul one More possess			and Pur		
	Costrotta Constr	aceron wanadem	INSURER D:	Ameri	can Int	ernational exp	up
	3188 Lawson Blyd Oceanside NY 115	72	INCURER S				
			, <u> </u>				, (
	PAGES	HAVE BEEN ISSUED TO THE INSURED NAM	ISO ABONG EOD THE PO	ICY PER	OO DIDICATE	DANDAMTRINTON C	
448.0	くのこうさんは、 さいこ はならなんなうこ 人ここのりにり ぎ	A THE BULKURU DESCRIBED HEREWIN IN THR	LECT TO ALL THE TERM	is, occup	ס מאג אמסק	HOLLE 40 EMOLLIQUE	a. · · ,
POL	ICIES. ACORECATE LIMITS SHOWN MAY F	IAVE BRAIN REDUCED BY PAID CLAIMS.					ND ()
MSR T	Type of Indurance	POLICY NUMBER	DATE MANDOM	PATE	INDON W	[JM]	
7	GENERAL LIABALITY			1))	BACH OCCURRENCE	12,000,00
A -	X COMMERCIAL GENERAL LIMBILITY	PGL76691	11/15/02	11)	15/03	PITE DAMAGE (ANY DIRE TO)	1100,000
A	CLAMB MADE X OCCUR					MED EXP (Any one person)	3
-				{		PERSONAL & ADVINJURY	\$1,000,00
<u> </u>				1	(GENERAL AGGREGATE	12,000,00
<u> </u>				1	1	PRODUCTS - DOMPICE AGG	1
	GENT ACGREGATE LIMIT APPLIES PER:			1 1	1	PRODUCTION DOMPTOR AGE	
	POLICY JECT LOG :			1			
	YTHRALI SINBONOTUA				}	COMBINED MHALE LIMIT	\$1,000,00
1.	X ANY ALITO	12URCU35566	11/20/02	11	20/03	(Ca accident)	
	ALL OWNED AUTOS					BOOKY INJURY	\$
}-				1	1	(plat becard)	
	SCHEDULED AUTOS	1		1		BOOKY INJURY	
-	HAED YOUR				<u>{</u> [(Let ecopous)	\$
}	NOTHOWNED ALTON						
]]	PROPERTY DAMAGE	2
1					1		
	GARAGE LIARILITY		,		1	YTLD ONTA . EY YCCIDENL	
Ì	. ANT NATO	CB		ĺ		OTHER THAN EA ACK	- -
ļ.				<u> </u>	1		
	EXCEAS LIABILITY				1	BACH OCCURRENCE	9 10, 8 DD ; X
D	X OCCUR CLIME HADE	REU3717138	11/15/02	: 11	15/03	AGGREGATE	\$ 10,000,4
"	X CCCA COMMENT	222072123		Ì			ds ·
		· ·		1			\$
	DEDUCTIBLE				1		8
<u></u> '	RETENTION \$				╫	TORY LIMITS B	H-
	WORKERS COMPENSATION AND			ه م		EL BACH ACCIDENT	* 1000000
B	EMMOVERS LIABILITY	12WECKR0681	09/05/02	3 0 5	105/03	EL DIFFENGE - EN BAIPLOY	
					.	51. DUPIGAGG - EA BANFLUT	EE & LUD MUDON
					4	NL DISEASE - POUCY LIM	TOO O COO
	OTHER			ĺ	1		· · · · · · · · · · · · · · · · · · ·
	Buildars Risk	MXI-97061576	02/26/03	3 0:	2/25/04	property	300,000
, –	THE PERSON OF TH						
i i		The state of the s		מאסונ			
DED	CRIPTION OF OPPRATIONAL OCATIONER	THICLES/EXCLUSIONS ADDED BY BHOOKS	iement/sphychal provi				
RJO NA	CEPTION OF OPERATIONAL OCATIONER Iditional Inburad: LI	Thickerecturious added by Brooks Thistop, Handen,	CT CT				
DER Ad	CAPTION OF OPERATIONAL OCATIONSA Iditional Insurad: LI	THICLESPECTURIONS ADDED BY BROOKS IN Thicavision, Hamden,	CI CI	÷		• .	
DER Ad	EMPTION OF OPPRATIONAL OCATIONER Iditional Insurad: LI	THICLESPECTURIONS ADDED BY BHOOMS IN TALAVISION, HAMDEN,	ementantical provi CT	·	<u> </u>	*	
DER Ad	EMPTION OF OPPRATIONAL OCATIONER Iditional Insurad: LI	THICLESPECTURIONS ADDED BY SHOOKS IN Thickness on, Hamden,	CI CI				
DER Ad	EMPTION OF OPPRATIONAL OCATIONER Iditional Insurad: LI	THICLESPECTURIONS ADDED BY BROOMS IN Thicknision, Hamden,	CT CT				
D68 Ad	PROPERTY OF OPERATIONAL CATEGORIA (CALLING)	THICLESPECTURIONS ADDED BY ENDORS IN TALAVISION, Hamden,	CT	· .			
Ad	Iditional Insurad: LI	THICLESPECTURIONS ADDED BY BROOKS IN THICKY ISLOD, HAMDED, THICKY ISLOD, HAMDED,	GANCELL	ATION			
Ad	Iditional Insurad: LI	n Talavísion, Hamden,	CANCELL	ATION Y OF THE	ASOVII DEBC	KIBED FOLICIES BE OANOSS.	LED DEFORM THE EX
Ad	Iditional Insurad: LI	N Talevision, Hamden,	CANCELLA SHOULD AND SH	ATION Y OF THE	REPURS INCH	rdr will endisavor to ma	IL 30 DAYRW
Ad	Iditional Insurad: LI	n Talavísion, Hamden,	CANCELLA SHOULD AND DATE THERE	ATION Y OF THE FOR, THE	TERCATE HOU	der will endsavor to ma Dur names to that left, bu	n falure to do s
Ad	Iditional Insurad: LI	n Talevision, Hamden, componer moures; mourer letter: A	CANCELLA SHOULD AND DATE THERE	ATION Y OF THE FOR, THE	TERCATE HOU	der will endsavor to ma Dur names to that left, bu	n falure to do
Ad	Iditional Insurad: LI RTIFICATE HOLDER Y A	N Talevision, Hamden, Componer moures; maures letter: A VOIC	CANCELLA SHOULD AND DATE THERE HOTICS TO IMPOSE NO	ATION YOF THE FOR, THE THE CERT	TERCATE HOU	rdr will endisavor to ma	n falure to do s
Ad	Iditional Insurad: LI	N Talevision, Hamden, Commonat Moures; Medrer Letter: A VOICE Teless	CANCELLA SHOULD AND DATE THERE NOTICE TO IMPOSE NO REPRESENT	ATION YOU THE FOR, THE THE CERT OULLISATIVES.	THEATE HOU	der will endsavor to ma Dur names to that left, bu	n falure to do s
Ad	RTIFICATE HOLDER Y A VolceStream Wi 100 Fillay Str	N Talevision, Hamden, Commonat Moures; Medrer Letter: A VOICE Teless	CANCELLA SHOULD AND DATE THERE HOTICS TO IMPOSE NO	ATION YOU THE FOR, THE THE CERT OULLISATIVES.	THEATE HOU	der will endsavor to ma Dur names to that left, bu	n failure to do si
Ad	RTIFICATE HOLDER Y A VolceStream Wi 100 Fillay Str	N Talevision, Hamden, Commonat Moures; Medrer Letter: A VOICE Teless	CANCELLA SHOULD AND DATE THERE NOTICE TO IMPOSE NO REPRESENT	ATION YOU THE FOR, THE THE CERT OULLISATIVES.	THEATE HOU	RER WILL SHOTSAVOR TO MA DER NAMED TO THE LEFT, BY THY OF ALLY KIND UPON THE	IL 30 DAYRM IT FAILURE TO DO SK
CE	RTIFICATE HOLDER Y A VolceStream Wi 100 Fillay Str	N Talevision, Hamden, Commonat Moures; Medrer Letter: A VOICE Teless	CANCELLA SHOULD AND DATE THERE NOTICE TO IMPOSE NO REPRESENT	ATION YOU THE FOR, THE THE CERT OULLISATIVES.	THEATE HOU	RER WILL SHOTSAVOR TO MA DER NAMED TO THE LEFT, BY THY OF ALLY KIND UPON THE	n failure to do sc
CE	VoiceStream Wind Stranger	N Talevision, Hamden, Commonat Moures; Medrer Letter: A VOICE Teless	CANCELLA SHOULD AND DATE THERE NOTICE TO IMPOSE NO REPRESENT	ATION YOU THE FOR, THE THE CERT OULLISATIVES.	THEATE HOU	RER WILL SHOTSAVOR TO MA DER NAMED TO THE LEFT, BY THY OF ALLY KIND UPON THE	IL SO DAYAMA

THE CITY OF WATERBURY MEMORANDUM

DATE: JULY 1, 2003

FROM: KAREN MULCAHY, TAX COLLECTOR

TO: DEPT. OF BUILDING INSPECTIONS

SUBJECT: TAX CLEARANCE

AS OF THIS DATE, THE RECORDS IN THE TAX COLLECTOR'S OFFICE INDICATES THAT THE FOLLOWING IS NOT DELINQUENT.

BROWNSTEIN REALTY, LLC 1669 THOMASTON AVE WATERBURY, CT 06704

FOR: 1669 THOMASTON AVE.

IF YOU HAVE ANY FURTHER QUESTIONS, DO NOT HESITATE TO CALL THE OFFICE AT 574-6935.

VERY TRULY YOURS

KAREN MULCAHÝ TAX COLLECTOR

KM/ps

	T.	
	'	
	·	



THE CITY OF WATERBURY

DEPARTMENT OF INSPECTIONS

235 Grand Street, Waterbury, CT 06702 (203) 574-6832

Application for Building Permit

PLEASE PRINT LEGIBLY (Shaded areas for Office us	se only!) Date: Nov C. 1978
Applicant: Omnipoint Communications Inc	
Company Name: Conti Enterprises, Inc.	License No. 00900869
Address: 3001 South Clinton Avenue	Phone No. (908) 561–8005
City:South Plainfield State: NJ Zip:	07080
Location Owner: Location of Work:	Owner's Name: Jack Browstein
Address: 1669 Thomaston Ave.	Brownstein Realty L.L.C. Address: 1669 Thomaston Avenue
Waterbury, CT	City: Waterbury State: CT_
	Architect:
I hereby certify that the proposed work is authorized by the owner of record and that I	Architect's Name: Archet Architects, Inc
have been authorized by the owner to make	670 North Beers Street
this application as an authorized agent and we agree to conform to all applicable laws of this	Address: Building 2
jurisdiction.	City: Holmdel State: NJ
Print Name: Scott Gustafson	Signature: Foot Charles on
(must check one) Proposed Use Existing Us	se Floodplain? O Yes O No If yes, attach form.
	idential Temp. Structure
	er Plan(s) on File? O Yes O No
What are you building? Wireless telecom	munication antennas attached to exisiting
(Please describe in detail) 150' Smokestack	with related equipment cabinet at base.
Est. Cost \$ 42,000 Start Work Date:	Zone: IG continued on back →
REQUIRED? Department// // //-2-3-576 REQ	QUIRED? Department
	Yes O No HEALTH
u	Yes O No TRAFF
	Yes O No DEL. TAX (allow 5 days)
	Yes O No WATER
	Yes O No WASTE
	WAVEL 1
EE: \$ <u>343.00</u> Fine: \$	THE CITY OF
CofO; \$ 5 00 Issued by: 6	
OTAL: \$ <u>348.09</u> Title: <u>A</u>	CONNICON

THE CITY OF WATERBURY MEMORANDUM

From: Debra DuBois, Delinquent Tax Collector Date: Nov. 20, 1998

To: Department of Building Inspections

Subject: Tax Clearance

As of this date, the records in the Tax Collector's Office indicate that the following is not delinquent.

Brownstein Realty LLC 1669 Thomaston Avenue Waterbury, CT

FOR: 1669 Thomaston Ave.

If you have any further questions, do not hesitate to call me at 574-6935.

Very truly yours,

Debra L. DuBois

Delinquent Tax Collector

C.C.M.C.

DLD/_{SCM}

Omnipoint Communications Inc. 25 Van Zant St, 4th Floor, Ste 18E East Norwalk, CT 06855



October 29, 1998

Town of Waterbury Planning and Zoning

To whom it may concern:

Omnipoint Communications is developing a system to provide PCS wireless technology to the state of Connecticut. The design of our system is based on what is known as a grid, in which each antenna site is spaced in a non-uniform pattern. Prior to obtaining any specific sites, this grid is designed by taking into consideration the topography of the land, population density, expected use levels, and, whenever possible, the location of existing structures. Next, a search "ring" is identified for each antenna site. The technology that Omnipoint is employing to develop this PCS system allows for some flexibility in base station placement but generally only within a search ring that is at most one-half mile in diameter. Specific sites are then obtained through the zoning and leasing processes. In order to maintain contiguous coverage between cell sites, as sites around a particular area become fixed, flexibility is lost for shifting sites in the remaining rings.

The candidate at 1669 Thomaston Avenue, Waterbury, CT has been selected to meet our coverage objective for adjacent portion of Route 8, Thomaston Avenue, the Bucks Hill and Waterville sections of Waterbury. This candidate fulfills our coverage objectives. We consider it important to provide a high quality service in Waterbury. High quality means; it is our goal to provide a dependable radio signal level allowing successful call completion and handover between adjacent sites. The location of a site with respect to the adjacent sites is of prime importance in the design of our system. Since the system works in continuity, the location of the sites are chosen such that they handoff to adjacent sites successfully. The candidate at 1669 Thomaston Avenue, Waterbury. will handover to adjacent northeast site in the 300 block of Garden Circle, Waterbury, the southeast site in the 100 block Todd Hollow Road, Waterbury, the southwest site at 1021 Straits Turnpike, Middlebury and the southern site at 65 Benedict Street, Waterbury.

Two other candidates considered for this ring, 1359 Thomaston Avenue, Waterbury and 266 Brookside Road, Waterbury. The owner of the candidate at 1359 Thomaston Avenue, Waterbury was not interested in negotiating with Omnipoint and the candidate at 266 Brookside Road, Waterbury would not provide adequate coverage for the area. Thus, the two candidates proved to not be viable options.

The cabinet chosen for the site is manufactured by Nortel which is a leader in the Telecommunication industry. The model number for the cabinet is S8000. This cabinet will support the tri-sectored antenna configuration . The dimensions of the cabinet (in inches) are $63^{\circ}H \times 53^{\circ}W \times 25^{\circ}D$. The cabinet will be located on the roof close to the penthouse and will be visible only from the roof of adjoining properties. The antenna chosen for this site is manufactured by EMS Wireless with model number RR90-17-02DP for each sector of the three. The dimensions for the antenna (in inches) are $56.0^{\circ}L \times 8.0^{\circ}W \times 2.75^{\circ}D$. The antenna cluster will consist of three sectors and there is one directional antenna proposed per sector to be used for both transmit and receive. These are high gain directional antennas which provide maximum coverage and increase the capacity of a site by three times. Since each antenna will

be transmitting a unique frequency, we can get three channels out of one site, whereas Omni-directional antennas would provide considerably less coverage than the proposed directional panel antennas. Moreover, Omni-directional antennas cannot resolve capacity issues since they transmit the same frequency in all directions (which means our capacity is reduced to one third). The other technological alternative would be the Micro cell design. However the antennas used for this design provide coverage to very small areas and would not at all be feasible to meet our coverage objective for this site.

The <u>maximum level</u> of RF energy associated with simultaneous and continuous operations of all transmitters will be <u>at least 2000 times below</u> the exposure limits of ANSI, IEEE, NCRP set at 1000 microwatts per square centimeter (μ W/cm²) and the limits of all states that regulate RF exposure. The emissions from Omnipoint Communications Inc. transmitters will be in the non-ionizing 1930-1945 Mhz frequency spectrum.

Please contact me if I can be of any further assistance.

Sincerely,

Michael Walker

Radio Frequency Engineer

on behalf of Omnipoint Communications

BROWNSTEIN REALTY, L.L.C.

1669 THOMASTON AVENUE WATERBURY, CONNECTICUT 06704 TELEPHONE: (203) 574-3811 FAX: (203) 575-0169

October 28, 1998

City of Waterbury Zoning Department 235 Grand Street Waterbury, Connecticut 06702

To Whom It May Concern:

This letter is to advise you that Omnipoint Communications, Inc. has my permission to apply to the City of Waterbury for any permits necessary to install their communications equipment on the smokestack located on my property at 1669 Thomaston Avenue.

Sincerely,

Jack Brownstein



The City of Waterbury

DEPARTMENT OF INSPECTIONS

Certificate No.

25158

Certificate of Use and Occupancy

Date:	11-1	<u></u>	1929
-------	------	---------	------

This Certificate Must be Signed Before Building Can be Occupied.

This is to cer	tify that address	1669 Thomaston Avenue may be used for
wireles	s telecom	munication antennas w/ equip. cab. and is in compliance
with the prov	visions of the Sta	te of Connecticut Basic Building Code.
Use Group (i	in accordance wi	ith provisions of Article 3):
Fire Grading	g (as defined in T	Γable 902):
Maximum L	ive Load (as pre	escribed in Table 1106, p.s.f.): 1st 2nd 3rd
Permit No	8750C	Date: 11/23/98
Special Build	ing Permit Stipu	lations and Conditions:
		Building Official
REQUIRED?		Department /
REQUIRED?	O No	Department ZONING: Meant liggeoner 11-10-99
4	O No ⊙∕No	
O Yes	نو	ZONING: ment liggeoner 11-10-99
© Yes	⊙√No	ZONING:
© Yes O Yes	≪No ≪No	ZONING:
© Yes O Yes O Yes	© No © No	ZONING:
O Yes O Yes O Yes O Yes O Yes	√No√No√No	ZONING:
O Yes O Yes O Yes O Yes O Yes O Yes	⊙No ⊙No ⊙No ⊙No	ZONING:
O Yes	ONO ONO ONO ONO	ZONING:



Exhibit B

Property Card

The Assessor's office is responsible for the maintenance of records on the ownership of properties. Assessments are computed at 70% of the estimated market value of real property at the time of the last revaluation which was 2017.

CITY OF WATERBURY

Information on the Property Records for the Municipality of Waterbury was last updated on 5/31/2019.

Parcel Information

Location:	1669 THOMASTON AVE	Property Use:	Industrial	Primary Use:	Light Industrial
Unique ID:	007409730005	Map Block Lot:	0074-0973-0005	Acres:	4.00
490 Acres:	0.00	Zone:	IL	Volume / Page:	7379/ 24
Developers Map / Lot:		Census:			

Value Information

	Appraised Value	Assessed Value
Land	554,880	388,420
Buildings	387,571	271,300
Detached Outbuildings	0	0
Total	942,451	659,720

Owner's Information


Owner's Data

1669 THOMASTON AVENUE LLC 1669 THOMASTON AVE WATERBURY CT 06704

Building 1



007409730005 04/11/2016



Category:	Industrial	Use:	Light Industrial	GLA:	212,578
Stories:	4.00	Construction:	Average	Year Built:	1900
Heating:	Forced Air	Fuel:		Cooling Percent:	0%

Siding:	Brick, Solid	Roof Material:	Beds/Units:	0
Sidilig.	Brick, Solid	Noor Plateriat.	Deasy offics.	o l

Special Features

Passenger Elevator	1
Passenger Elevator	1
Sprinklers	212578

Attached Components

Owner History - Sales

Owner Name	Volume	Page	Sale Date	Deed Type	Valid Sale	Sale Price
1669 THOMASTON AVENUE LLC	7379	24	08/07/2015	Additional Parcel	No	\$300,000

Building Permits

Permit Number	Permit Type	Date Opened	Date Closed	Permit Status	Reason
2018.2628	Electrical	09/19/2018		Open Permit	INSTALL A 15KW DIESEL DC GENERATOR TO BACKUP T-MOBILE EXISTING CABINET -NEW 4'X8' CONCRETE PAD ADDE
2016.2448	Electrical	08/19/2016		Closed	INSTALL 3 NEW ANTENNAS & RRU'S
2015.1093	Electrical	05/11/2015		Closed	INSTALL METER FOR SPRINT
2015.0143	Electrical	01/15/2015		Closed	REPLACE 3 EXISTING ANTENNAS ADD 3 RRU"S ON EXISTING STEEL PLATFORM
2015.0202	Electrical	01/15/2015		Closed	INTALL GROUNDING ELECTRO CONDUCTORS FOR SERVICE MARK AND PLACARD S
2014.1915	Electrical	07/21/2014		Expired Permit	UPGRADE, REPLACE & WIRE EQUIPMENT / TELECOMMUNICATION SITE

Permit Number	Permit Type	Date Opened	Date Closed	Permit Status	Reason
2012.2302	Comm Renovations	08/31/2012		Closed	BATHROOM/DEMISING WALL

Information Published With Permission From The Assessor




Exhibit C

Construction Drawings

SITE NAME: WATERBURY/RT 8 1

SITE NUMBER: CT11214D

SITE TYPE: **SMOKESTACK**

PROJECT TYPE: L600

δĭ

JURISDICTION: CITY OF WATERBURY

SITE ADDRESS: 1669 THOMASTON AVE WATERBURY, CT 06704

SHEET#

T-1

SP-1

SP-2

A-2

A-.3

A-4

A-5

A-6

F-1 G-1 TITLE SHEET

SPECIFICATIONS

SPECIFICATIONS

OVERALL SITE PLAN

ENLARGED SITE PLANS

ANTENNA DETAIL AND SPECIFICATIONS ANTENNA & RRU CONFIGURATION KEYS

PANEL SCHEDULE & ONE-LINE DIAGRAM

GROUNDING RISER DIAGRAM AND DETAILS

BUILDING FLEVATIONS

ANTENNA LAYOUTS

'•••Mobile•



SITE NUMBER: CT11214D

SITE NAME: WATERBURY/RT 8 1

SITE ADDRESS: 1669 THOMASTON AVE WATERBURY, CT 06704

PROJECT NO:	135648.003.01
CHECKED BY:	MDW

	ISSUED FOR:							
REV	DATE	DRWN	DESCRIPTION					
Α	7/15/19	JCO	PRELIMINARY REVIEW					
0	7/19/19	JCO	CONSTRUCTION					

B&T ENGINEERING, INC. Expires 2/10/20



SHEET NUMBER:

REVISION

PROJECT SUMMARY

SITE NAME: SITE NUMBER:

WATERBURY/RT 8_1 CT11214D

SITE ADDRESS: 1669 THOMASTON AVE WATERBURY, CT 06704

COUNTY: NEW HAVEN COUNTY JURISDICTION: CITY OF WATERBURY

41.589810° N LATITUDE LONGITUDE: 73.054228° W GROUND ELEVATION: 286' AMSL

CUSTOMER/APPLICANT:

35 GRIFFIN ROAD SOUTH BLOOMFIELD, CT 06002

(913) 402-6500

OCCUPANCY TYPE:

FACILITY IS UNMANNED AND NOT A.D.A. COMPLIANCE:

FOR HUMAN HABITATION

CONTACT INFORMATION

B&T ENGINEERING, INC. 1717 S. BOULDER, STE. 300 TULSA, OK 74119 CONTACT: MIKE OAKES (918) 587-4630

MANAGER:

(860) 550-5971

PROJECT

MARK RICHARD mark.richard64@t-mobile.com (860) 648-1116

BRIAN PAUL Brian.Paul14@t-mobile.com

T-MOBILE

DRIVING DIRECTIONS

Or Dr

DEPART BRADLEY INTERNATIONAL AIRPORT ON TERMINAL RD. ROAD NAME CHANGES TO BRADLEY FIELD CONNECTOR. ROAD NAME CHANGES TO CT-20 [BRADLEY FIELD CONNECTOR]. TAKE RAMP (RIGHT) ONTO I-91 [RICHARD P HORAN MEMORIAL AT EXIT 32A-32B, TURN RIGHT ONTO RAMP. TAKE RAMP ONTO I-84 [US-6]. AT EXIT 20, TAKE RAMP (RIGHT) CT-8. AT EXIT 36, KEEP RIGHT ONTO RAMP. TURN RIGHT ONTO HUNTINGDON AVE. TURN LEFT ONTO THOMASTON AVE. TURN LEFT ONTO CHAPEL ST. TURN RIGHT ONTO WELCH ST, THEN IMMEDIATELY TURN LEFT ONTO STEVENS ST. BEAR LEFT ONTO ACCESS RD AND ARRIVE AT WATERBURY-RT 8

CODE COMPLIANCE

ALL WORK SHALL BE PERFORMED AND MATERIALS INSTALLED IN ACCORDANCE WITH THE CURRENT EDITIONS OF THE FOLLOWING CODES AS ADOPTED BY THE LOCAL GOVERNING AUTHORITIES. NOTHING IN THESE PLANS IS TO BE CONSTRUED TO PERMIT WORK NOT CONFORMING TO

CODE TYPE BUILDING/DWELLING

2018 CONNECTICUT STATE BUILDING CODE 2018 CONNECTICUT STATE BUILDING CODE MECHANICAL 2018 CONNECTICUT STATE BUILDING CODE **ELECTRICAL**

PROJECT DESCRIPTION

NO SCALE

AREA MAP

WATERBURY-RT 8

THE PROPOSED PROJECT INCLUDES: REMOVE & REPLACE (3) ANTENNAS.

REMOVE (3) GROUND MOUNTED RRUS11 B12.

(2) DUS41 & (1) XMU. REMOVE

REMOVE (3) BIAS-T.
REMOVE (3) 1 5/8" COAX CABLES.

• INSTALL (3) 4449 B71+B12 RRH.

• INSTALL (2) BB6630 IN EXISTING RBS 6102 CABINET.

• INSTALL (2) 6x12 HCS.

DO NOT SCALE DRAWINGS

NO SCALE

LOCATION MAP

ALL DRAWINGS CONTAINED HEREIN ARE FORMATTED FOR 11X17. CONTRACTOR SHALL VERIFY ALL PLANS AND EXISTING DIMENSIONS AND CONDITIONS ON THE JOB SITE AND SHALL IMMEDIATELY NOTIFY THE ENGINEER IN WRITING OF ANY DISCREPANCIES BEFORE PROCEEDING WITH THE WORK OR BE RESPONSIBLE FOR SAME.

> SEE SHEETS SP-1 & SP-2 FOR ADDITIONAL CONSTRUCTION NOTES

A/E DOCUMENT REVIEW STATUS

DRAWING INDEX

SHEET DESCRIPTION

1116	SIGNATURE	DATE
T-MOBILE R.E. MGR.:		
T-MOBILE R.F. MGR.:		
T-MOBILE NetOps:		
T-MOBILE CONST. MGR.:		
INTERCONNECT:		
T-MOBILE SITE DEV. MGR.:		
PROPERTY OWNER:		
PLANNING:		

ACCEPTED: WITH OR NO COMMENTS, CONSTRUCTION MAY PROCEED

NOT ACCEPTED: RESOLVE COMMENTS AND RESUBMIT

ACCEPTANCE DOES NOT CONSTITUTE APPROVAL OF DESIGN, CALCULATIONS, ANALYSIS, TEST METHODS OF MATERIALS DEVELOPED OR SELECTED BY THE SUBCONTRACTOR AND DOES NOT RELIEVE SUBCONTRACTOR FROM FULL COMPLIANCE WITH CONTRACTUAL OBLIGATIONS.



CALL CONNECTICUT ONE CALL (800) 922-4455 **CALL 3 WORKING DAYS** BEFORE YOU DIG!

REV.#

0

0

0

0

0

Ω

0

0

0

0

1.1 INTENT:

- A. THESE SPECIFICATIONS AND CONSTRUCTION DRAWINGS DESCRIBE THE WORK TO BE DONE AND THE MATERIALS TO BE FURNISHED FOR CONSTRUCTION. PLANS ARE NOT TO BE SCALED.
- B. THE DRAWINGS AND SPECIFICATIONS ARE INTENDED TO BE FULLY EXPLANATORY AND SUPPLEMENTARY, HOWEVER, SHOULD ANYTHING BE SHOWN, INDICATED OR SPECIFIED ON ONE AND NOT THE OTHER, IT SHALL BE DONE THE SAME AS IF SHOWN, INDICATED OR SPECIFIED IN BOTH.
- C. THE INTENTION OF DOCUMENTS IS TO INCLUDE ALL LABOR AND MATERIALS REASONABLY NECESSARY FOR THE PROPER EXECUTION AND COMPLETION OF THE WORK AS STIPULATED IN THE CONTRACT.
- D. CONFLICTS: THE CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFICATION OF ALL MEASUREMENTS AT THE SITE BEFORE ORDERING MATERIAL OR DOING ANY WORK. NO COMPENSATION SHALL BE ALLOWED DUE TO DIFFERENCE BETWEEN ACTUAL DIMENSIONS AND THOSE ON THE DOCUMENTS. ANY DISCREPANCY SHALL BE REPORTED TO THE OWNER OR HIS AGENT FOR CONSIDERATION.

1.2 LICENSING REQUIREMENTS:

THE CONTRACTOR IS RESPONSIBLE FOR PROCUREMENT AND MAINTAINING OF ALL APPLICABLE LICENSES AND BONDS.

1.3 STORAGE

ALL MATERIALS MUST BE STORED IN A LEVEL AND DRY FASHION THAT DOES NOT OBSTRUCT THE FLOW OF OTHER WORK. ANY STORAGE METHOD MUST MEET ALL RECOMMENDATIONS OF THE ASSOCIATED MANUFACTURER.

1.4 CLEAN UP:

THE CONTRACTOR SHALL KEEP THE SITE FREE FROM ACCUMULATION OF WASTE MATERIALS OR RUBBISH AT ALL TIMES. TRASH MUST BE REMOVED DAILY.

1.5 QUALITY ASSURANCE:

ALL WORK SHALL BE IN ACCORDANCE WITH APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS.

PART 2 PRODUCTS - NOT APPLICABLE TO THIS SECTION

PART 3 EXECUTION - NOT APPLICABLE TO THIS SECTION

ELECTRICAL

PART 1 GENERAL

1.1 GENERAL CONDITIONS:

A. THE CONTRACTOR SHALL INSPECT THE SITE WHERE THIS WORK IS TO BE PERFORMED

AND FULLY FAMILIARIZE HIMSELF WITH ALL CONDITIONS RELATED TO THIS PROJECT.

THE CONTRACTOR SHALL OBTAIN AND PAY FOR ALL PERMITS AND LICENSES AND

SECTION 16000:

- SHALL MAKE ALL DEPOSITS AND PAY ALL FEES REQUIRED FOR THE PERFORMANCE OF WORK UNDER THIS SECTION.
- C. DRAWINGS SHOW THE GENERAL ARRANGEMENT OF ALL SYSTEMS AND COMPONENTS COVERED UNDER THIS SECTION. THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS. DRAWINGS SHALL NOT BE SCALED TO DETERMINE DIMENSIONS.

1.2 LAWS, REGULATIONS, ORDINANCES, STATUTES AND CODES

A. ALL WORK SHALL BE INSTALLED IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, AND ALL APPLICABLE LOCAL LAWS, REGULATIONS, ORDINANCES, STATUTES AND CODES

1.3 REFERENCES:

- A. THE PUBLICATIONS LISTED BELOW FORM PART OF THIS SPECIFICATION. EACH PUBLICATION SHALL BE THE LATEST REVISION AND ADDENDUM IN EFFECT ON THE DATE OF THIS SPECIFICATION IS ISSUED FOR CONSTRUCTION UNLESS OTHERWISE NOTED. EXCEPT AS MODIFIED BY THE REQUIREMENTS SPECIFIED HEREIN OR THE DETAILS OF THE DRAWINGS, WORK INCLUDED IN THIS SPECIFICATION SHALL CONFIRM TO THE APPLICABLE PROVISIONS OF THESE PUBLICATIONS.
- 1. ANSI/IEEE (AMERICAN NATIONAL STANDARDS INSTITUTE)
- 2. IEEE (INSTITUTE OF ELECTRICAL AND ELECTRONICS ENGINEERS)
- 3. ASTM (AMERICAN SOCIETY FOR TESTING AND MATERIALS)
- 4. ICEA (INSULATED CABLE ENGINEERS ASSOCIATION)
- 5. NEMA (NATIONAL ELECTRICAL MANUFACTURER'S ASSOCIATION)
- 6. NFPA (NATIONAL FIRE PROTECTION ASSOCIATION)
- 7. OSHA (OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION)
- 8. UL (UNDERWRITERS LABORATORIES, INC.)

1.4 SCOPE OF WORK:

- A. WORK UNDER THIS SECTION SHALL CONSIST OF FURNISHING ALL LABOR, MATERIAL AND ASSOCIATED SERVICES REQUIRED TO COMPLETELY CONSTRUCT AND LEAVE READY FOR OPERATION SYSTEMS AS SHOWN ON THE DRAWINGS AND HEREIN DESCRIBED.
- B. ALL ELECTRICAL EQUIPMENT UNDER THIS CONTRACT SHALL BE PROPERLY TESTED, ADJUSTED AND ALIGNED BY THE CONTRACTOR.
- C. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL EXCAVATING, DRAINING, TRENCHES, BACKFILLING, AND REMOVAL AND EXCESS DIRT.
- D. THE CONTRACTOR SHALL FURNISH TO THE OWNER, CERTIFICATES OF FINAL INSPECTION AND APPROVAL FROM THE INSPECTION AUTHORITIES HAVING JURISDICTION.

PART 2 PRODUCTS

2.1 GENERAL:

- A. ALL ITEMS OF MATERIALS AND EQUIPMENT SHALL BE NEW, FREE FROM DEFECTS AND OF THE BEST QUALITY NORMALLY USED FOR THE PURPOSE IN GOOD COMMERCIAL PRACTICE.
- B. ALL MATERIALS AND EQUIPMENT SHALL BE ACCEPTABLE TO THE AUTHORITY HAVING JURISDICTION AS SUITABLE FOR THE USE INTENDED.
- C. ALL EQUIPMENT SHALL BEAR THE UNDERWRITERS LABORATORIES LABEL OF APPROVAL, AND SHALL CONFORM TO THE REQUIREMENTS OF THE NATIONAL ELECTRICAL CODE.
- D. ALL OVERCURRENT DEVICES SHALL HAVE AN INTERRUPTING RATING EQUAL TO OR GREATER THAN THE SHORT CIRCUIT CURRENT TO WHICH THEY ARE SUBJECTED, 10,000 AIC MINIMUM. VERIFY AVAILABLE SHORT CIRCUIT CURRENT DOES NOT EXCEED THE RATING OF ELECTRICAL EQUIPMENT.

2.2 MATERIALS AND EQUIPMENT:

A. CONDUIT:

- RIGID GALVANIZED STEEL CONDUIT (RGS) SHALL BE HOT-DIP GALVANIZED INSIDE AND OUTSIDE INCLUDING ENDS AND THREADS AND ENAMELED OR LACQUERED INSIDE IN ADDITION TO GALVANIZING.
- FLEXIBLE METAL CONDUIT SHALL BE GALVANIZED, ZINC—COATED STEEL, PVC COATED FOR OUTDOOR APPLICATIONS.
- CONDUIT CLAMPS, STRAPS AND SUPPORTS SHALL BE STEEL OR MALLEABLE IRON. ALL FITTINGS SHALL BE COMPRESSION TYPE AND WATERTIGHT.
- 4. NON-METALLIC CONDUIT FITTINGS SHALL BE SCHEDULE 40 PVC, HEAVY-WALL RIGID WITH SOLVENT-CEMENT-TYPE JOINTS AS RECOMMENDED BY THE MANUFACTURER

B. WIRE AND CABLE:

- WIRE AND CABLE SHALL BE FLAME—RETARDANT, MOISTURE AND HEAT RESISTANT THERMOPLASTIC, SINGLE CONDUCTOR, COPPER, TYPE THHN/THWN, 600 VOLT, SIZES AS INDICATED, #12 AWG MINIMUM.
- 2. #10 AWG AND SMALLER CONDUCTORS SHALL BE SOLID AND #8 AWG AND LARGER CONDUCTORS SHALL BE STRANDED.
- 3. SOLDERLESS, PRESSURE—TYPE CONNECTORS CONSTRUCTED OF HIGH—STRENGTH, NON—CORRODIBLE, TIN—PLATED COPPER DESIGNED TO FURNISH HIGH—PULLOUT STRENGTH AND HIGH CONDUCTIVITY JOINTS SHALL BE USED.
- 4. SUPPORT GRIPS SHALL BE SINGLE WEAVE, CLOSED MESH, HIGH—GRADE, NON—MAGNETIC, TIN—COATED BRONZE, CAPABLE OF SUPPORTING TEN TIMES THE CABLE DEAD WEIGHT, HUBBELL KELLEMS OR APPROVED EQUAL.

C. DISCONNECT SWITCHES:

 DISCONNECT SWITCHES SHALL BE HEAVY DUTY, DEAD—FRONT, QUICK—MAKE, QUICK—BREAK, EXTERNALLY OPERABLE, HANDLE LOCKABLE AND INTERLOCKED WITH COVER IN CLOSED POSITION, RATING AS INDICATED, UL LABELED FURNISHED IN NEMA 3R ENCLOSURE, SQUARE D CLASS 3110 OR APPROVED EQUAL.

D. SYSTEM GROUNDING:

- GROUNDING CONDUCTOR SHALL BE BARE, SOLID TINNED COPPER, SIZE AS INDICATED, EXCEPT ABOVE GROUND GROUNDING CONDUCTORS SHALL BE INSULATED.
- 2. GROUND BUSSES SHALL BE BARE ANNEALED COPPER BARS OF RECTANGULAR CROSS SECTION.
- 3. CONNECTORS SHALL BE HIGH—CONDUCTIVITY, HEAVY DUTY, LISTED AND LABELED AS GROUNDING CONNECTORS FOR THE MATERIALS USED. USE TWO—HOLE COMPRESSION LUGS WITH HEAT SHRINK FOR MECHANICAL CONNECTIONS.
- 4. EXOTHERMIC WELDED CONNECTIONS SHALL BE PROVIDED IN KIT FORM AND SELECTED FOR THE SPECIFIC TYPES, SIZES, AND COMBINATIONS OF CONDUCTORS AND OTHER ITEMS TO BE CONNECTED.
- 5. GROUND RODS SHALL BE COPPER-CLAD STEEL WITH HIGH-STRENGTH STEEL CORE AND ELECTROLYTIC-GRADE COPPER OUTER SHEATH, MOLTEN WELDED TO CORE, 3/4"x10'-0".

E. OTHER MATERIALS:

 THE CONTRACTOR SHALL PROVIDE OTHER MATERIALS, THOUGH NOT SPECIFICALLY DESCRIBED, WHICH ARE REQUIRED FOR A COMPLETELY OPERATIONAL SYSTEM AND PROPER INSTALLATION OF THE WORK.



-T---Mobile-



SITE NUMBER: CT11214D

SITE NAME: WATERBURY/RT 8_1

SITE ADDRESS: 1669 THOMASTON AVE WATERBURY, CT 06704

PROJECT NO: 135648.003.01 CHECKED BY: MDW

	ISSUED FOR:			
Ш	REV	DATE	DRWN	DESCRIPTION
Ш	Α	7/15/19	JCO	PRELIMINARY REVIEW
Ш	0	7/19/19	JCO	CONSTRUCTION
Ш				
Ш				
Ш				

B&T ENGINEERING, INC. PEC.0001564 Expires 2/10/20



IT IS A VIOLATION OF LAW FOR ANY PERSON, JNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER,

SHEET NUMBER:

REVISION

3.1 GENERAL:

- A. ALL MATERIALS AND EQUIPMENT SHALL BE INSTALLED IN STRICT ACCORDANCE W/
 THE MANUFACTURER'S RECOMMENDATION
- B. EQUIPMENT SHALL BE TIGHTLY COVER AND PROTECTED AGAINST DIRT OR WATER, AND AGAINST CHEMICAL OR MECHANICAL INJURY DURING INSTALLATION AND CONSTRUCTION PERIODS.

3.2 LABOR AND WORK:

- A. ALL LABOR FOR THE INSTALLATION OF MATERIALS AND EQUIPMENT FURNISHED FOR THE ELECTRICAL SYSTEM SHALL BE DONE BY EXPERIENCED MECHANICS OF THE PROPER TRADES
- B. ALL ELECTRICAL EQUIPMENT FURNISHED SHALL BE ADJUSTED, ALIGNED AND TESTED BY THE CONTRACTOR AS REQUIRED TO PRODUCE THE INTENDED PERFORMANCE.
- C. UPON COMPLETION OF THE WORK, THE CONTRACTOR SHALL THOROUGHLY CLEAN ALL EXPOSED EQUIPMENT, REMOVE ALL LABELS AND ANY DEBRIS, CRATING OR CARTONS AND LEAVE THE INSTALLATION FINISHED AND READY FOR OPERATION.

3.3 COORDINATION:

A. THE CONTRACTOR SHALL COORDINATE THE INSTALLATION OF ELECTRICAL ITEMS WITH THE OWNER-FURNISHED EQUIPMENT DELIVERY SCHEDULE TO PREVENT UNNECESSARY DELAYS IN THE TOTAL WORK.

3.4 INSTALLATION:

A. CONDUIT

- 1. ALL ELECTRICAL WIRING SHALL BE INSTALLED IN CONDUIT AS HEREIN SPECIFIED. NO CONDUIT OR TUBING OF LESS THAN 3/4 INCH NOMINAL SIZE SHALL BE USED.
- 2. PROVIDE RGS CONDUIT FOR ALL EXPOSED, EXTERIOR CONDUIT.
- 3. PROVIDE SCHEDULE 40 PVC OR RGS CONDUIT BELOW GRADE, 1" MINIMUM, UNLESS NOTED OTHERWISE. ALL 90 DEGREE BENDS TO ABOVE GRADE SHALL BE RGS, MINIMUM BURIAL DEPTH SHALL BE 30" CLEAR TO TOP OF CONDUIT, UNLESS NOTED OTHERWISE.
- 4. USE GALVANIZED FLEXIBLE STEEL CONDUIT WHERE DIRECT CONNECTION IS NOT DESIRABLE FOR REASONS EQUIPMENT MOVEMENT, VIBRATION OR FOR EASE OF MAINTENANCE. USE LIQUIDTIGHT, PVC COATED FLEXIBLE METAL CONDUIT FOR OUTDOOR APPLICATIONS.
- 5. INSTALL GALVANIZED FLEXIBLE STEEL CONDUIT AT ALL POINTS OF CONNECTION TO EQUIPMENT MOUNTED ON SUPPORTS TO ALLOW FOR EXPANSION AND CONTRACTION
- 6. A RUN OF CONDUIT BETWEEN BOXES OR FITTINGS SHALL NOT CONTAIN MORE THE EQUIVALENT OF FOUR QURATER-BENDS INCLUDING THOSE BENDS LOCATED IMMEDIATELY AT THE BOX OR FITTING. THE RADIUS OF BENDS SHALL NEVER BE SHORTER THAN THAT OF THE CORRESPONDING TRADE ELBOW.
- 7. WHERE CONDUIT HAS TO BE CUT IN THE FIELD, IT SHALL BE CUT SQUARE WITH A PIPE CUTTER USING CUTTING KNIVES.
- ALL CONDUITS SHALL BE SWABBED CLEAN BY PULLING AN APPROPRIATE SIZE MANDREL THROUGH THE CONDUIT BEFORE INSTALLATION OF WIRE OR CABLE. CLEAR ALL BLOCKAGES AND REMOVE BURRS, DIRT AND DEBRIS.
- INSTALL MULE TAPE IN ALL EMPTY CONDUIT IDENTIFY PULL STRINGS AT EACH END WITH ITS DESTINATION.
- 10. PROVIDE INSULATED GROUNDING BUSHINGS OR ALL CONDUITS STUBBED INTO EQUIPMENT ENCLOSURES OR STUBBED OUT FOR FUTURE USE BY OTHERS.
- 11. CONTRACTOR IS RESPONSIBLE FOR PROTECTING ALL CONDUITS DURING CONSTRUCTION. TEMPORARY OPENINGS IN THE CONDUIT SYSTEM SHALL BE PLUGGED OR CAPPED TO PREVENT ENTRANCE OF MOISTURE OR FOREIGN MATTER. CONTRACTOR SHALL REPLACE ANY CONDUIT CONTAINING FOREIGN MATERIALS THAT CANNOT BE REMOVED.
- 12. INSTALL 3" RED METALLIC LOCATOR TAPE 12" ABOVE ALL UNDERGROUND CONDUIT AND WIRE.
- 13. CONDUITS SHALL BE INSTALLED IN SUCH A MANNER AS TO INSURE AGAINST COLLECTION OF TRAPPED CONDENSATION.

B. WIRE AND CABLE:

1. ALL POWER WIRING SHALL BE COLOR CODED AS FOLLOWS

DESCRIPTION PHASE A PHASE B PHASE C NEUTRAL GROUND	120/270V BLACK RED WHITE GREEN	RED BLUE WHITE	480Y/277V BROWN ORANGE YELLOW GRAY GREEN
GROUND	GREEN	GREEN	GREEN

- . SPLICES SHALL BE MADE ONLY AT OUTLETS, JUNCTION BOXES OR ACCESSIBLE RACEWAYS WITH PRESSURE—TYPE CONNECTORS.
- PULLING LUBRICANT SHALL BE SOAPSTONE POWDER, POWDERED TALC OR A
 COMMERCIAL PULLING COMPOUND. NO SOAP SUDS, SOAP FLAKES, OIL OR
 GREASE SHALL BE USED, AS THESE MAY BE HARMFUL TO CABLE INSULATION.
 CONTRACTOR SHALL USE NYLON OR HEMP ROPE FOR PULLING CABLE TO
 AVOID SCORING THE CONDUIT.
- 4. CABLES SHALL BE NEATLY TRAINED, WITHOUT INTERLACING, AND BE OF SUFFICIENT LENGTH IN ALL BOXES, EQUIPMENT. ETC. TO PERMIT MAKING A NEAT ARRANGEMENT. CABLES SHALL BE SECURED IN A MANNER TO AVOID TENSION ON CONDUCTORS OR TERMINALS AND SHALL BE PROTECTED FROM MECHANICAL INJURY AND FROM MOISTURE. SHARP BENDS OVER CONDUIT BUSHINGS ARE PROHIBITED. DAMAGED CABLES SHALL BE REMOVED AND REPLACE AT THE CONTRACTOR'S EXPENSE.

C. DISCONNECT SWITCHES:

 INSTALL DISCONNECT SWITCHED LEVEL AND PLUMB. CONNECT TO WIRING SYSTEM AND GROUND AS INDICATED.

D. GROUNDING:

- 1. ALL METALLIC PARTS OF ELECTRICAL EQUIPMENT WHICH DO NOT CARRY CURRENT SHALL BE GROUNDED IN ACCORDANCE WITH THE REQUIREMENTS OF ARTICLE 250 OF THE NATIONAL ELECTRIC CODE.
- PROVIDE ELECTRICAL GROUNDING AND BONDING SYSTEMS INDICATED WITH ASSEMBLY OF MATERIALS, INCLUDING GROUNDING ELECTRODES, BONDING JUMPERS AND ADDITIONAL ACCESSORIES AS REQUIRED FOR A COMPLETE INSTALLATION.
- 3. ROUTE GROUNDING CONNECTIONS AND CONDUCTORS TO GROUND IN THE SHORTEST AND STRAIGHTEST PATHS POSSIBLE TO MINIMIZE TRANSIENT VOLTAGE RISES
- 4. TIGHTEN GROUNDING AND BONDING CONNECTORS, INCLUDING SCREWS AND BOLTS, IN ACCORDANCE WITH MANUFACTURER'S PUBLISHED TORQUE TIGHTENING VALUES FOR CONNECTORS AND BOLTS. WHERE MANUFACTURE'S TORQUING REQUIREMENTS ARE NOT AVAILABLE, TIGHTEN CONNECTIONS TO COMPLY WITH TIGHTENING TORQUE VALUES SPECIFIED IN UL 486A TO ASSURE PERMANENT AND EFFECTIVE GROUNDING.
- 5. ALL UNDERGROUND GROUNDING CONNECTIONS SHALL BE MADE BY THE EXOTHERMIC WELD PROCESS AND INSTALL IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTION.
- 6. ALL GROUND CONNECTIONS SHALL BE INSPECTED FOR TIGHTNESS. EXOTHERMIC—WELDED CONNECTIONS SHALL BE APPROVED BY THE CONSTRUCTION INSPECTOR BEFORE BEING PERMANENTLY CONCEALED.
- APPLY CORROSION-RESISTANT FINISH TO FIELD CONNECTION AND PLACES WHERE FACTORY APPLIED PROTECTIVE COATING HAVE BEEN DESTROYED. USE COPPER-BASED "NO-OX" OR APPROVED EQUAL.
- 8. A SEPARATE, CONTINUOUS, INSULATED EQUIPMENT GROUNDING CONDUCTOR SHALL BE INSTALLED IN ALL FEEDER AND BRACH CIRCUITS.
- 9. BOND ALL INSULATED GROUNDING BUSHINGS WITH A BARE #6 AWG GROUNDING CONDUCTOR TO A GROUND BUS OR GROUNDING LUG IN ENCLOSURE.
- 10. DIRECT BURIED GROUND CONDUCTORS SHALL BE INSTALLED AT A NOMINAL DEPTH OF 30" BELOW GRADE, UNLESS NOTED OTHERWISE.
- 11. ALL GROUNDING CONDUCTORS EMBEDDED IN OR PENETRATING CONCRETE SHALL BE INSULATED OR INSTALLED IN PVC CONDUIT.
- 12. INSTALL ELECTROLYTIC GROUNDING SYSTEM IN STRICT ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS. REMOVE SEALING TAPE FROM LEACHING AND BREATHER HOLES, INSTALL PROTECTIVE BOX FLUSH WITH GRADE.
- 13. DRIVE GROUND RODS UNTIL TOPS ARE 30" BELOW FINAL GRADE
- 14. GROUNDING CONDUCTOR TO EQUIP[MENT GROUND LUGS:
 - BOLTED TO EQUIPMENT HOUSING WITH STAINLESS STEEL BOLTS AND LOCK WASHERS.
 -) ALL EQUIPMENT TO BE GROUNDED SHALL BE FREE OF PAINT OR ANY OTHER MATERIAL COVERING BARE METAL AT THE POINT OF CONNECTION.

3.5 ACCEPTANCE TESTING:

- 1. PROVIDE PERSONNEL AND EQUIPMENT, MAKE REQUIRED TESTS AND SUBMIT TEST REPORTS UPON COMPLETE OF TESTS.
- WHEN MATERIAL AND/OR WORKMANSHIP IS FOUND NOT TO COMPLY WITH THE SPECIFIED REQUIREMENTS, THE NON-COMPLYING ITEMS SHALL BE REMOVED FROM THE JOBSITE AND REPLACED WITH THE ITEMS COMPLYING WITH THE SPECIFIED REQUIREMENTS PROMPTLY AFTER RECEIPT OF NOTICE OF SUCH NON-COMPLIANCE.

A. TEST PROCEDURES:

- 1. ALL FEEDERS SHALL HAVE THEIR INSULATION TESTED AFTER INSTALLATION, BUT BEFORE CONNECTION TO DEVICES. THE CONDUCTORS SHALL TEST FREE FROM SHORT CIRCUITS AND GROUNDS. TESTING SHALL BE FOR ONE MINUTE, USING 1000V DC. INVESTIGATE ANY VALUES LESS THAN 50 MEGOHMS.
- PRIOR TO ENERGIZING CIRCUITRY, TEST WIRING DEVICES FOR ELECTRICAL CONTINUITY AND PROPER POLARITY CONNECTIONS.
- MEASURE AND RECORD VOLTAGES BETWEEN PHASES AN BETWEEN PHASE WIRE AND NEUTRALS. SUBMIT A REPORT OF MAXIMUM AND MINIMUM VOLTAGES.
- 4. PERFORM GROUND TEST TO MEASURE GROUND RESISTANCE OF GROUNDING SYSTEM USING THE IEEE STANDARD 3-POINT "FALL-OF-POTENTIAL" METHOD. PROVIDE PLOTTED TEST VALUES AND LOCATION SKETCH. NOTIFY THE ENGINEER IMMEDIATELY IF MEASURED VALUE IS OVER 5 OHMS.

END OF SECTION

END OF SPECIFICATION



-T---Mobile-



SITE NUMBER: CT11214D

SITE NAME: WATERBURY/RT 8_1

SITE ADDRESS: 1669 THOMASTON AVE WATERBURY, CT 06704

PROJECT NO: 135648.003.01 CHECKED BY: MDW

	ISSUED FOR:				
ſ	REV	DATE	DRWN	DESCRIPTION	
Γ	Α	7/15/19	JCO	PRELIMINARY REVIEW	
Γ	0	7/19/19	JCO	CONSTRUCTION	
[
[


B&T ENGINEERING, INC. PEC.0001564 Expires 2/10/20



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER,

SP-2

REVISION





T---Mobile-



SITE NUMBER: CT11214D

SITE NAME: WATERBURY/RT 8_1

SITE ADDRESS: 1669 THOMASTON AVE WATERBURY, CT 06704

PROJECT NO: 135648.003.01

ISSUED FOR:

1330ED FOR.			
REV	DATE	DRWN	DESCRIPTION
Α	7/15/19	JCO	PRELIMINARY REVIEW
0	7/19/19	JCO	CONSTRUCTION

B&T ENGINEERING, INC. PEC.0001564 Expires 2/10/20



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SHEET NUMBER: REVISION:



T Mobile



SITE NUMBER: CT11214D

SITE NAME: WATERBURY/RT 8_1

SITE ADDRESS: 1669 THOMASTON AVE WATERBURY, CT 06704

PROJECT NO: 135648.003.01


ISSUED FOR:				
REV	DATE	DRWN	DESCRIPTION	
Α	7/15/19	JCO	PRELIMINARY REVIEW	
0	7/19/19	JCO	CONSTRUCTION	

B&T ENGINEERING, INC. PEC.0001564 Expires 2/10/20



UNLESS THEY ARE ACTING UNDER THE DIRECTIC
OF A LICENSED PROFESSIONAL ENGINEER,
TO ALTER THIS DOCUMENT.

sheet number: Revision:





T Mobile



SITE NUMBER: CT11214D

SITE NAME: WATERBURY/RT 8_1

SITE ADDRESS: 1669 THOMASTON AVE WATERBURY, CT 06704

PROJECT NO: 135648.003.01

ISSUED FOR:				
REV	DATE	DRWN	DESCRIPTION	
Α	7/15/19	JCO	PRELIMINARY REVIEW	
0	7/19/19	JCO	CONSTRUCTION	

B&T ENGINEERING, INC. PEC.0001564 Expires 2/10/20



UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

A-3

REVISION



•T•••Mobile•



SITE NUMBER: CT11214D

SITE NAME: WATERBURY/RT 8_1

SITE ADDRESS: 1669 THOMASTON AVE WATERBURY, CT 06704

PROJECT NO: 135648.003.01

ISSUED FOR:

REV	DATE	DRWN	DESCRIPTION
Α	7/15/19	JCO	PRELIMINARY REVIEW
0	7/19/19	JCO	CONSTRUCTION


B&T ENGINEERING, INC. PEC.0001564 Expires 2/10/20



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SHEET NUMBER:

REVISION



ANTENNA SPECS								
MANUFACTURER	RFS							
MODEL #	APXVAARR24_43-U-NA20							
WIDTH	24.0"							
DEPTH	8.7"							
HEIGHT	95.9"							
WFIGHT	128.0 LBS							

RRH SPECS							
MANUFACTURER	ERICSSON						
MODEL #	4449 B71+B12						
WIDTH	13.2"						
DEPTH	9.4"						
HEIGHT	17.9"						
WEIGHT	70.5 LBS						



RRH DETAIL SCALE: N.T.S.



•T•••Mobile•



SITE NUMBER: CT11214D

SITE NAME: WATERBURY/RT 8_1

SITE ADDRESS: 1669 THOMASTON AVE WATERBURY, CT 06704

PROJECT NO: 135648.003.01 CHECKED BY:

ISSUED FOR:								
REV	DATE	DRWN	DESCRIPTION					
Α	7/15/19	JCO	PRELIMINARY REVIEW					
0	7/19/19	JCO	CONSTRUCTION					

B&T ENGINEERING, INC. PEC.0001564 Expires 2/10/20



SHEET NUMBER: REVISION:

ANTENNA NOTES:

- 1. ANTENNA CONTRACTOR SHALL INSURE THAT ALL ANTENNA MOUNTING PIPES ARE PLUMB.
- 2. COAXIAL FEEDER & FIBER LENGTHS INDICATED ARE APPROXIMATE.
- 3. ANTENNA COAXIAL FEEDERS & ANTENNA JUMPERS SHALL BE COLOR CODED PER T-MOBILE REQUIREMENTS. IN ADDITION TO THE COLOR CODE IN THE ANTENNA KEY THE FOLLOWING CHECKER STRIPE SHALL BE ADDED TO EACH ANTENNA COAXIAL FEEDER & ANTENNA JUMPER.

LTE L600 - WHITE-SOLID STRIPE LTE 700 - RED-BLACK CHECKER STRIPE LTE PCS - RED-GREEN CHECKER STRIPE LTE AWS - YELLOW-BLACK CHECKER STRIPE UMTS PCS - RED-WHITE CHECKER STRIPE UMTS AWS - GREEN-WHITE CHECKER STRIPE GSM PCS - BLACK-WHITE CHECKER STRIPE

- 4. UMTS AWS LINE 1 & 2 TO HAVE TMA, MOUNTED ON PIPE BEHIND ANTENNA POSITION #2.
- 5. MULTI-PORTS ANTENNAS: TERMINATE UNUSED ANTENNA PORTS WITH CONNECTOR CAP & WEATHERPROOF THOROUGHLY. JUMPERS FROM TMAS MUST TERMINATE TO OPPOSITE POLARIZATIONS IN EACH SECTOR,
- 6. CONTRACTOR MUST FOLLOW ALL MANUFACTURERS' RECOMMENDATIONS REGARDING THE INSTALLATION OF COAXIAL CABLES, CONNECTORS & ANTENNAS.
- 7. MINIMUM BEND RADIUS:

LDF4-50A (1/2" HARD LINE) = 5"FSJ4-50B (1/2" SUPER FLEX) = 1 1/4"AVA5-50A (7/8" HARD LINE) = 10"AVA7-50A (1 5/8 HARD LINE) = 15"LDF7-50A (1 5/8" HARD LINE) = 20"

- CONTRACTOR SHALL RECORD THE SERIAL, SECTOR & POSITION OF EACH ACTUATOR INSTALLED AT THE ANTENNAS AND FURNISH THE INFORMATION TO
- 9. WEATHERPROOF ALL ANTENNA CONNECTORS WITH SELF-AMALGAMATING TAPE.
- 10. ANTENNA CONTRACTOR SHALL PERFORM A "TAPE DROP" MEASUREMENT TO CONFIRM/VALIDATE ANTENNA CENTERLINE (ACL) HEIGHT. CONTRACTOR SHALL SUBMIT A COMPLETED HEIGHT VERIFICATION FORM TO THE CONSTRUCTION MANAGER.
- 11. ALL FIBER RUNS TO BE CONTAINED IN (1) NOKIA HYBRID DC-FIBER CABLE (P/N: ASU9325TYP01) FROM LOWER COVP TO UPPER COVP. HYBRID CABLE SHALL BE COLOR CODED PER T-MOBILE REQUIREMENTS.

						ANTENNA KEY										
SECTOR	STATUS	ANTENNA NUMBER	TYPE	COLOR CODE	ANTENNA	MODEL #	AZIMUTH	ELEC. TILT	MECH TILT	RAD CENTER	COAXIAL	FEEDER	HYBRID CABLE FE	EEDER		
SEC	SIAIUS	NUMBER	ITPE	COLOR CODE	VENDOR	MODEL #		TILT	TILT	RAD CENTER	SIZE	LENGTH	SIZE	LENGTH		
			L700	-				2°			_	_				
ALPHA	NEW	A-1	L600	-	RFS	APXVAARR24_43-U-NA20	70°	2*	0°	130'-0"	-	_	(1) 6x12 HCS	160'		
			L2100	-				2*			-	-	(1) 6x12 HCS			
	EXISTING	A-2	L1900	-	ERICSSON	AIR32 KRD901146-1_B66A_B2A	70°	2*	0°	133'-6"	-	-	(SHARED)	160'		
	EVICTINO	. 7	U1900 –		DE0	4DV46DV4/ 46DV4/ 6 5 400	70*	2*	0.	477' 0"	1 5/8"	145'-0"				
	EXISTING	A-3	G1900 U2100	-	RFS	APX16DWV-16DWV-S-E-A20	70°	2*	0°	133'-6"	1 5/8"	145'-0"	_	160'		
	NEW	B-1	L700	-	RFS	APXVAARR24_43-U-NA20	180°	2*	or	130'-0"	-	_	(1) 6x12 HCS	160'		
	11211	B-1	L600	-			,,,,	2*		150 -0	-	_		160		
BETA	EXISTING	B-2	L2100	.2100	ERICSSON	AIR32 KRD901146-1_B66A_B2A	70°	2*	0.	133'-6"	-	_	(1) 6x12 HCS (SHARED)	160'		
BE	LAISTING B-	B-2	L1900	-	Linioson		70	2*		133 -6	-	_		160		
	EXISTING	B-3	U1900 G1900	-	RFS	APX16DWV-16DWV-S-E-A20	70°	2*	0.	133'-6"	1 5/8"	145'-0"	-	160'		
	EXISTING	B-3	U2100	-	NF3		70	2*	U	133 -6	1 5/8"	145'-0"		160		
	NEW	G-1	L700	-					310°	2*		130'-0"	-	_	(4) 0 45 1155	
	NEW	G-1	L600	-	RFS	APXVAARR24_43-U-NA20	310	2°	O°	130 –0	-	_	(1) 6x12 HCS	160'		
GAMMA	EXISTING	G-2	L2100	-	ERICSSON	AIR32 KRD901146-1_B66A_B2A	70°	2*	0.	133'-6"	-	_	(1) 6x12 HCS (SHARED)	160'		
GAN	LAISTING	G-Z	L1900	-	LINICOSON	AITOZ MNDSOTTTO-T_DOOK_BZA		2*		133 -6	_	_				
	EXISTING	G-3	U1900 G1900	-	RFS	APX16DWV-16DWV-S-E-A20	70°	2*	0.	133'-6"	1 5/8"	145'-0"	_	160'		
	LAISTING	G-3	U2100	-	1(1.5	AI X 100WY - 100WY - 3-E-A20	70° 0°		133 -0	1 5/8"	145'-0"		160			

ANITENINIA VEV

RRU KEY — ON SMOKESTACK									
SECTOR	VENDOR	EQUIPMENT	MODEL #	ELEVATION	QUANTITY	STATUS			
MULTI	ERICSSON	RRU	4449 B71+B12	130'-0"	3	NEW			
MULTI	PCS	TMA	TWIN STYLE 1A	130'-0"	3	EXISTING			
MULTI	PCS	TMA	TWIN STYLE 1B	130'-0"	3	EXISTING			







SITE NUMBER: CT11214D

SITE NAME: WATERBURY/RT 8 1

SITE ADDRESS: 1669 THOMASTON AVE WATERBURY, CT 06704

PROJECT NO:	135648.003.01
CHECKED BY:	MDW

ISSUED FOR:								
REV	DATE	DRWN	DESCRIPTION					
Α	7/15/19	JCO	PRELIMINARY REVIEW					
0	7/19/19	JCO	CONSTRUCTION					

B&T ENGINEERING, INC. PEC.0001564 Expires 2/10/20



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

REVISION: SHEET NUMBER:

FINAL PANEL SCHEDULE									
LOAD	POLES	AMPS	BUS		AMPS	POLES	LOAD		
20/10	I OLLO	AMICS	L1	L2	7	, ollo	LOAD		
SPARE	1	20A	1	2	125A	2		RBS 6102	
AAV	1	20A	3	4	125A	2	KB2 6102		
			5	6	50A	2		UMTS	
			7	8	SUA	2		OMIS	
RATED VOLTAGE: ■120/240 □ 1	PHASE, 3	3 WIRE	BRANC	H POI	_ES: □12	□24 □3	30 ■42	APPROVED MF'RS	
RATED AMPS: □100 ■200 □400 □	RATED AMPS: □100 ■200 □400 □							NEMA □1 ■3R □4X	
□MAIN LUGS ONLY MAIN 200 AMPS ■BREAKER	SWITCH	■HINGED DOOR ■ KEYED DOOR LATCH					■KEYED DOOR LATCH		
□FUSED ■CIRCUIT BREAKER BRANCH DEVICE			TO E	BE GFCI B	REAKERS	FULL NEUTRAL BUS GROUND BAR			
ALL BREAKERS MUST BE RATED TO INTERRUPT	A SHORT	CIRCUIT IS	SC OF	10,00	O AMPS S	SYMMETRIC	AL		

EXISTING 100A BREAKER PANEL TO BE REPLACED W/ NEW 200A BREAKER PANEL. SQUARE D P/N: Q012040M200RB (OR APPROVED EQUAL/EMERSON JUICEBOX)
REPLACE EXISTING BREAKERS W/ NEW BREAKERS OF SAME AMPERAGE INSIDE NEW PANEL


PEDLACE EXISTING WIRES FOR EXISTING 6102 CARDINET WITH (3) 2/0 AWG THWN (CORPER) AND (1) #6C AWG MINIMUM CONDUIT SIZE TO BE 2"

REPLACE EXISTING WIRES FOR EXISTING 6102 CABINET WITH (3) 2/0 AWG THWN (COPPER) AND (1) #6G AWG. MINIMUM CONDUIT SIZE TO BE 2" UPGRADE FEEDER WIRES TO MEET AMPACITY.

FINAL PANEL DESIGN AND CALCULATIONS FOR WIRE SIZE WERE BASED OFF OF EXISTING PHOTOS FINAL T-MOBILE PANEL DETAIL

 $(1)^{\frac{F}{C}}$

SCALE: N.T.S.





-T---Mobile-



SITE NUMBER: CT11214D

SITE NAME: WATERBURY/RT 8_1

SITE ADDRESS: 1669 THOMASTON AVE WATERBURY, CT 06704

PROJECT NO: 135648.003.01 CHECKED BY: MDW

		ISSUED FOR:								
Ш	REV	DATE	DRWN	DESCRIPTION						
Ш	Α	7/15/19	JCO	PRELIMINARY REVIEW						
Ш	0	7/19/19	JCO	CONSTRUCTION						
Ш										
Ш										
Ш										

B&T ENGINEERING, INC. PEC.0001564 Expires 2/10/20





IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SHEET NUMBER:

REVISION:








EXISTING GROUND SYSTEM


ANTENNA GROUND DIAGRAM

SCALE: N.T.S.




NOTES:

- ALL HARDWARE BOLTS, NUTS, LOCK WASHERS SHALL BE STAINLESS STEEL. ALL HARDWARE ARE TO BE AS FOLLOWS: BOLT, FLAT WASHER, GROUND BAR, GROUND LUG, FLAT WASHER AND NUT.
- 2. COPPER SHIELD, ANTIOX, CR NO-OX OR APPROVED EQUAL SHALL BE PLACE WHERE ALL DISSIMILAR METALS CONNECT.
- 3. ALL LUGS ARE TO BE INSTALLED PER MANUFACTURER'S SPECIFICATIONS.



MECHANICAL LUG CONNECTION

SCALE: N.T.S.







-T---Mobile-



SITE NUMBER: CT11214D

SITE NAME: WATERBURY/RT 8 1

SITE ADDRESS: 1669 THOMASTON AVE WATERBURY, CT 06704

PROJECT NO: 135648.003.01 CHECKED BY: MDW

		ISSUED FOR:								
	REV	DATE	DRWN	DESCRIPTION						
	Α	7/15/19	JCO	PRELIMINARY REVIEW						
	0	7/19/19	JCO	CONSTRUCTION						
ı										

B&T ENGINEERING, INC. PEC.0001564 Expires 2/10/20



IT IS A VIOLATION OF LAW FOR ANY PERSON, UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMENT.

SHEET NUMBER:

REVISION

Exhibit D

Structural Analysis Report

July 19, 2019

Centerline Communications

Engineering Firm Designation:

95 Ryan Drive, Suite 1

Ravnham, MA 02767

(401) 835-2033

Peter Fales



B+T Group 1717 S. Boulder, Suite 300 Tulsa, OK 74119 (918) 587-4630 btwo@btgrp.com

Subject: Structural Analysis

CT11214D Carrier Designation: Site Number: Site Name: Waterbury/Rt 8 1

B+T Group Project Number:

Site Data: 1669 Thomaston Ave., Waterbury, CT 06704, New Haven County

Latitude 41.58981°, Longitude -73.05422°

Smokestack

(3) 13.5 ft. Stand-off Mounts

Dear Mr. Fales.

B+T Group is pleased to submit this "Structural Analysis" to determine the structural integrity of the above mentioned smokestack supported telecommunications site.

The purpose of the assessment is to determine acceptability of the smokestack to sufficiently support the telecommunications equipment presented in this report. Based on our professional opinion we have determined the suitability for the structure and foundation, under the following load case, to be:

Existing + Proposed Equipment Note: See Table 1 and Table 2 for the proposed and existing loading, respectively. **Sufficient Capacity** (Passing at 82.0%)

135648.004.01 REV B

The analysis has been performed in accordance with the ASCE 7 standard and the 2015 IBC based upon a wind speed of 125 mph 3-second gust (converted to an equivalent 97 mph nominal 3-second gust wind speed per Section 1609.3.1 for use with ANSI/TIA-222 G).

All equipment proposed in this report shall be installed in accordance with the drawings for the determined available structural capacity to be effective.

We at B+T Group appreciate the opportunity of providing our continuing professional services to you and NB+C. If you have any questions or need further assistance on this or any other projects please give us a call.

Structural Letter prepared by: Siva Tellakula, E.I.T.

Respectfully submitted by: B&T Engineering, Inc.

COA: PEC.0001564 Expires: 02/10/2020



TABLE OF CONTENTS

1) INTRODUCTION

2) ASSESSMENT CRITERIA

Table 1 - Proposed Antenna and Cable Information
Table 2 - Existing and Reserved Antenna and Cable Information

3) ASSESSMENT PROCEDURE

Table 3 - Documents Provided 3.1) Assessment Method

3.2) Assumptions

4) ASSESSMENT RESULTS

4.1) Recommendations

5) Appendix A

Calculations

1) INTRODUCTION

The proposed telecommunications equipment will be located on the smokestack at 1669 Thomaston Ave., Waterbury, CT 06704, New Haven County. There are existing telecommunications antennas mounted on the wall of the smokestack in three different sectors. The proposed loading consists of adding (3) antennas, (3) RRHs and (2) HCS to existing mount pipes.

2) ANALYSIS CRITERIA

The structural Analysis was performed for this structure in accordance with the 2015 International Building Code and the ASCE 7 Design Standard. The TIA-222-G apply to telecommunications towers. Although telecommunications equipment is present, this structure is primarily a smokestack and is more appropriately assessed with the ASCE 7 Standard. The design wind speed for this location is 97 mph 3-second gust.

Table 1 – Proposed and Existing Equipment Information

Loading	RAD Ctr. Elev. (ft.)	Position	Qty.	Manufacturer	Model / Type	Note					
		2	3	RFS	APXVAARR24_43-U-NA20	1					
Proposed (T-Mobile)	130		3	Ericsson	Radio 4449 B71+B12	2					
(1-Mobile)		-	2	Ericsson	6X12 HCS Fiber Cable						
	133.5	133.5					4	3	RFS	APX16DWV-16DWV-S-E-A20	3
			5	3	Ericsson	AIR32 KRD901146-1_B66A_B2A	3				
Existing (T-Mobile)			4	6	Ericsson	KRY 112 144/2					
(1 Woolic)								1	Ericsson	6X12 HCS Fiber Cable	
	-	-	15	-	1-5/8" Coax Cable	_					
F '			3	RFS	APPXVERR18-C						
Existing (Sprint)	120	-	3	Generic	Antenna	4					
(Opinit)			6	Ericsson	RRUS-11						

Note:

- (1) Proposed Antenna to be installed on the existing Mount Pipe.
- (2) Proposed Equipment to be installed directly behind the Antenna.
- (3) Existing Equipment installed on the Mount.
- (4) Sprint Equipment installed on the Smokestack.

3) ANALYSIS PROCEDURE

Table 3 - Documents Provided

Document	Remarks	Reference	Source
RFDS	Existing Loading Proposed Loading	Date: 04/16/2019	Centerline Communications.
Structural Analysis	Structural Detail	Date: 11/21/2014	Centerline Communications.

3.1) Analysis Method

This smokestack is a substantial structure designed and fabricated to support hundreds of pounds of material in addition to its own self weight. The nature and intended purpose of the structure is substantially greater than the addition of the telecommunication equipment. The proposed equipment will be mounted on existing mounts attached to the wall of the smokestack. The analysis of the mounts is not part of the scope of this report. Based on our calculations, the new antennas have insignificant effect on the seismic and wind load of the smokestack. Hence the Smokestack has adequate capacity to carry the existing and proposed loads.

3.2) Assumptions

- 1) The structure was built in accordance with the designer's specifications.
- 2) The structure has been maintained and is free of damage.
- 3) The configuration of antennas, transmission cables, mounts and other appurtenances are as specified in Tables 1 and 2 and the referenced drawings.
- 4) Existing loading was assumed based on final proposed loading.

This analysis may be affected if any assumptions are not valid or have been made in error. B+T Group should be notified to determine the effect on the structural integrity of the structure.

4) ANALYSIS RESULTS

4.1) Recommendations

1) The antennas shall be installed on the existing smokestack in accordance with the installation drawings.

APPENDIX A

(Calculations)

PROJECT	T 135648.002.01 - Waterbury/Rt 8_1 SP				
SUBJECT	Smokestack Calculations				
DATE	07/11/19 PAGE OF				



ASSESS IMPACT OF TELECOM EQUIPMENT ON WATER TOWER USING ASCE 7 - 05 STANDARD

WIND = 97 EXP = C Ht = 134

 $q = 0.00256 \text{ Kz Kzt Kd V}^2 \text{ I}$

 $\begin{array}{lll} I = & 1.0 & G = & 0.85 \\ K_d = & 0.95 & C_f = & 0.6 \\ K_{zt} = & 1.0 & Kz = 1.31 \end{array}$

 $q_z = 22.88 K_z$

 $p = q_z G C_f = 11.67 K_z$

Н	K_z	q_z	Р	W	Α	F		М
ft	-	psf	psf	ft	ft^2	lbs	ft	ft-lbs
134	1.35	30.80	15.71	12.00	201	3157	129.8125	409875
126	1.33	30.39	15.50	11.66	97.6525	1513	121.4375	183,770
117	1.31	29.95	15.27	11.36	95.14	1453	113.0625	164,290
109	1.29	29.48	15.04	11.03	92.37625	1389	104.6875	145,415
101	1.27	28.99	14.79	10.73	89.86375	1329	96.3125	127,969
92	1.24	28.46	14.52	10.39	87.01625	1263	87.9375	111,085
84	1.22	27.90	14.23	10.05	84.177125	1198	79.5625	95,295
75	1.19	27.29	13.92	9.75	81.65625	1136	71.1875	80,896
67	1.16	26.62	13.58	9.41	78.80875	1070	62.8125	67,202
59	1.13	25.88	13.20	9.07	75.96125	1003	54.4375	54,582
50	1.09	25.05	12.78	8.88	74.37	950	46.0625	43,773
42	1.05	24.11	12.30	8.44	70.685	869	37.6875	32,758
34	1.01	23.00	11.73	8.14	68.1725	800	29.3125	23,445
25	0.95	21.65	11.04	7.80	65.325	721	20.9375	15,104
17	0.87	19.88	10.14	7.47	62.56125	634	12.5625	7,969
8	0.75	17.18	8.76	7.16	59.965	525	4.1875	2,200
0	0.00	0.00	0.00	6.83	0	0	0	0

Total Moment 1,565,628 Ft-Lbs

Determine amount of moment generated by telecom equipment Note that equipment on the heaviest loaded sector is considered

Equipment	q_z	Α	C_f	F	М
-	psf	ft^2	-	lbs	ft-lbs
APXVAARR24_43-U-NA20	30.80	47.95	1.40	1757	231985
Radio 4449 B71+B12	30.80	4.10	1.40	150	19,836
6X12 HCS	30.80	3.10	1.40	114	14,998
APX16DWV-16DWV-S-E-A20	30.80	15.48	1.40	567	74,893
IR32 KRD901146-1_B66A_B2	30.80	15.88	1.40	582	76,828
KRY 112 144/2	30.80	1.20	1.40	44	5,796
APPXVERR18-C	30.70	59.10	1.40	2159	285,038
RRUS-11	30.70	13.92	1.40	509	67,145

 $K_z = 1.34$ Total Moment = 776,520 Ft-Lbs


 $q_z = 30.7$ psf H = 132 ft

Total Overturning Moment (M_o)= 2342.15 Ft-Kips





B+T Group		SK - 1
SP	Waterbury CT11214D	July 19, 2019 at 4:03 PM
135648.001.01- REV B		SMOKESTACK.r3d



The Smokestack dimensions and material properties were assumed based on the previous analysis by ATLANTIS Group (Dated November 21, 2014)

Height of Silo (H)=	134	ft.	
Top Diameter of Silo (D _t) =	9.75	ft.	
Top thickness of Silo (T_t) =	8	in	
Bottom Diameter of Silo (D _b) =	14.25	ft.	
Bottom Thickness of Silo (T _b) =	28	in	
Unit Weight of Bricks (Yprick) =	120	pcf	
Ultimate masonary strength (f' _m) =	432	kips/ft^2	3000 Psi
Area of Silo At top (A _t) =	19.02	Sq.ft.	
Area of Silo At bottom (A _b)=	87.35	Sq.ft.	
Average volume of Silo (V _a) =	6051.00	ft^3	$V_a = A_a \times H$
Weight of Silo (W)=	726.12	kips	$W=V_a \times y$ $brick$
Resisting Moment due to self weight (M _r)=	5173.61	ft-kips	$M_r = \frac{D_b}{2} \times W$
Easter of Softey (E.O.S.)-	2 21	No Overtur	nina
Factor of Saftey (F.O.S)=	2.21	ivo Overtur	
			$F.O.S = \frac{\cdot}{M_o}$

Compressive stress check of the bricks at the Critical section

As per Risa Output Critical section is at (H _c)=	75	ft.
Diameter of Silo at Critical section (D_c)=	12	ft.
Thickness of Silo at Critical section (T_c)=	18	in
Area of Silo Critical section (A _c)=	49.48	Sq.ft.
Moment of Inertia at critical section (I_c)=	695.81	ft^4
Radius of gyration at critical section (r_c)=	6.00	ft.

Compressive stresses due to axial loading and Bending

Makimum compressive stress due to axial load(f_a) =	14.67	kips/ft^2	$f_{\alpha} = \frac{W}{A_c}$
Allowable compressive stress due to axial load (F _a)=	107.14	kips/ft^2	$F_a = \frac{1}{4} f_m' (1 - (\frac{H_c}{140 r_c})^2)$

Compressive Stress in bending (f _b)=	2.52 kips/ft	$f_b = \frac{M_o T_c}{2 I_c}$
Allowable Compressive Stress in bending (F _b)=	144 kips/ft	$F_b = \frac{1}{3} f_m'$
Unity check =	0.15 OK	$\frac{f_a}{F_a} + \frac{f_b}{F_b} \le 1$

Flexural check at the base

Allowable flexural stresses on the tension Side at base

σ tension brick and concrete	30	psi
conn Stress due to Self Weight	57.7251	psi
Section Modulus Sx at Base	390480	in3

Moment capacity at base Mcap 2854574

Passing Percentage % = (Mo / Mcap)x100 82.049

lb.ft

Exhibit E

Mount Analysis

July 8, 2019

Peter Fales Centerline Communications 95 Ryan Drive, Suite 1 Raynham, MA 02767 (401) 835-2033



B+T Group 1717 S. Boulder, Suite 300 Tulsa, OK 74119 (918) 587-4630 btwo@btgrp.com

Subject: Appurtenance Mount Conditional Pass Report

Carrier Designation: Site Number: CT11214D

Site Name: Waterbury/Rt 8 1

Engineering Firm Designation: B+T Group Project Number: 135648.002.01

Site Data: 1669 Thomaston Ave., Waterbury, CT 06704, New Haven County

Latitude 41.58981°, Longitude -73.05422°

Smokestack

(3) 13.5 ft. Stand-off Mounts

Dear Mr. Fales,

B+T Group is pleased to submit this "**Appurtenance Mount Conditional Pass Report**" to determine the structural integrity of the antenna mount on the above-mentioned structure.

The purpose of the analysis is to determine acceptability of the mount's stress level. Based on our analysis we have determined the stress level for the mount under the following load case to be:

Existing + Proposed Equipment
Note: See Table 1 for the final loading configuration

Sufficient Capacity (Passing at 84.1 %)

*See Section 5.1 of this report for the structural modifications required in order for the mount to support the loading listed in Table 1

The analysis has been performed in accordance with the ANSI/TIA-222-G Standard. This analysis utilizes an ultimate 3-second gust wind speed of 125 mph (converted to an equivalent 97 mph nominal 3-second gust wind speed per Section 1609.3.1 for use with ANSI/TIA-222 G) as required by the 2015 International Building Code. Exposure Category C and Risk Category II were used in this analysis.

All the equipment proposed in this report shall be installed in accordance with the drawings for the determined available structural capacity to be effective.

We at *B+T Group* appreciate the opportunity of providing our continuing professional services to you and *Centerline Communications*. If you have any questions or need further assistance on this or any other projects, please give us a call.

Mount structural analysis prepared by: Prashanth Ghanta.

Respectfully submitted by: B&T Engineering, Inc. COA: PEC.0001564 Expires: 02/10/2020




TABLE OF CONTENTS

1) INTRODUCTION

2) ANALYSIS CRITERIA

Table 1 - Proposed and Existing Equipment Information

Table 2 - Documents Provided

3) ANALYSIS PROCEDURE

- 3.1) Analysis Method
- 3.2) Assumptions

4) ANALYSIS RESULTS

Table 3 - Mount Component Stresses vs. Capacity

5) RECOMMENDATIONS

6) APPENDIX A

RISA-3D Output

1) INTRODUCTION

The appurtenance mount consists of Stand-off mounts, at 131.5 ft., attached to smokestack at 1669 Thomaston Ave., Waterbury, CT 06704, New Haven County. The proposed antenna loading information was obtained from Centerline Communications. All information provided to B+T Group was assumed accurate and complete.

2) ANALYSIS CRITERIA

The structural analysis was performed for this mount in accordance with the ANSI/TIA-222-G-2-2005 Structural Standard for Antenna Supporting Structures and Antennas – Addendum 2 using a 3-second gust wind speed of 97 mph with no ice and 50 mph with 0.75-inch escalated ice thickness. Exposure Category C with top factor 1 and Risk Category II were used in this analysis. In addition, the standoff mounts have been analyzed for various live loading conditions consisting of a 250-lb man live load applied individually at the midpoint and cantilevered ends of horizontal members as well as a 500-pound man live load applied individually at mount pipe locations using a 3-second gust of 30mph. The mount was analyzed under 30° increments in the wind direction. The analyzed loading is detailed in Table 1.

Table 1 - Proposed and Existing Equipment Information

Table 1 1 Toposca and Existing Equipment information							
Loading	RAD Ctr. Elev. (ft.)	Position	Qty.	Manufacturer	Model / Type	Note	
		2	3	RFS	APXVAARR24_43-U-NA20	1	
Proposed	130		3	Ericsson	Radio 4449 B71+B12	2	
		-	2	Ericsson	6X12 HCS		
		4	3	RFS	APX16DWV-16DWV-S-E-A20	3	
Existing	133.5	5	3	Ericsson	AIR32 KRD901146-1_B66A_B2A	3	
		4	6	Ericsson	KRY 112 144/2		

Note:

- (1) Proposed Antenna to be installed on the existing Mount Pipe.
- (2) Proposed Equipment to be installed directly behind the Antenna.
- (3) Existing Equipment installed on the Mount.

Table 2 - Documents Provided

Documents	Remarks	Reference	Source
RFDS	Existing Loading Proposed Loading	Date: 04/16/2019	Centerline Communications.
Mount Mapping	B+T Group	Date: 06/26/2019	On file

3) ANALYSIS PROCEDURE

3.1) Analysis Method

RISA-3D (Version 17.0.2), a commercially available analysis software package, was used to create a three-dimensional model of the mount and calculate member stresses and deflections for various loading cases. Selected output from the analysis is included in Appendix A.

3.2) Assumptions

- 1. The mount was built in accordance with the manufacturer's specifications.
- 2. The mount has been maintained in accordance with the manufacturer's specifications and is free of damage.
- 3. The configuration of antennas and other appurtenances are as specified in Table 1.
- 4. All mount components have been assumed to be in sufficient condition to carry their full design capacity for the analysis.

- 5. Mount areas and weights are determined from field measurements, standard material properties, and/or manufacturer product data.
- 6. Serviceability with respect to antenna twist, tilt, roll or lateral translation is not checked and is left to the carrier or tower owner to ensure conformance.
- 7. All prior structural modifications, if any are assumed to be correctly installed and fully effective.
- 8. All member connections are assumed to have been designed to meet or exceed the load carrying capacity of the connected member unless otherwise specified in this report.
- 9. The following material grades were assumed (Unless Noted Otherwise):

a) Connection Bolts : ASTM A325

b) Steel Pipe : ASTM A53 (GR. 35) c) HSS (Round) : ASTM 500 (GR. B-42) d) HSS (Rectangular) : ASTM 500 (GR. B-46) e) Channel : ASTM A36 (GR. 36) Steel Solid Rod : ASTM A36 (GR. 36) g) Steel Plate : ASTM A36 (GR. 36) h) Steel Angle : ASTM A36 (GR. 36) UNISTRUT : ASTM A570 (GR. 33)

This analysis may be affected if any assumptions are not valid or have been made in error. B+T Group should be notified to determine the effect on the structural integrity of the antenna mounting system.

4) ANALYSIS RESULTS

Table 3- Mount Component Stresses vs. Capacity

Notes	Component	Elevation (ft.)	% Capacity	Pass / Fail
	Main Horizontals	131.5	74.4	Pass
	Mount Pipes	131.5	62.0	Pass
	Existing Tiebacks	131.5	16.3	Pass
	Connection Plates	131.5	72.8	Pass
	Vertical Connection Pipe	131.5	44.4	Pass
	Support Arms	131.5	84.1	Pass
	Additional Tiebacks	131.5	13.5	Pass

5) RECOMMENDATIONS

The sector mounts have sufficient capacity to carry the existing and proposed loads and is in compliance with the ANSI/TIA-222-H standard for the proposed, reserved and existing loading. (Refer to the RISA output for the specific members).


1. Install new Stiff-Arm Kits, Sitepro 1 **Part# STK-U** at Mount pipe location 4 @ 0'-9" above the Top Horizontal on all 3 sectors. (see Appendix A for the location of Additional Tie backs).

No structural modifications are required at this time, provided that the above-listed changes are implemented


APPENDIX A

(RISA-3D Output)






B+T Group		SK - 3
PG	CT11214D - Waterbury/Rt 8_1	July 8, 2019 at 2:53 PM
135648.002.01		135648_002_01_WaterburyRt 8_1









B+T Group		SK - 4
PG	CT11214D - Waterbury/Rt 8_1	July 8, 2019 at 2:53 PM
135648.002.01		135648_002_01_WaterburyRt 8_1





B+T Group		SK - 5
PG	CT11214D - Waterbury/Rt 8_1	July 8, 2019 at 2:53 PM
135648.002.01		135648_002_01_WaterburyRt 8_1





B+T Group		SK - 6
PG	CT11214D - Waterbury/Rt 8_1	July 8, 2019 at 2:53 PM
135648.002.01		135648_002_01_WaterburyRt 8_1

PROJECT	135648.002.01 - Waterbury/Rt 8_1, C PG Stand-off Mounts- Mount Analysis					
SUBJECT						
DATE	07/08/19	PAGE	1	OF	3	



INPUT [REF: ANSI/TIA-222-G2005]

Tower Type : ST
Tower Height : 134 ft

Mount Elevation : 131.5 ft

Antenna Elevation : 133.5 ft

Crest Height : 0 ft

Structure Class Π [Table 2-1] **Exposure Category** C [Sec. 2.6.5] Topography Category 1 [Sec. 2.6.6.2] Wind Velocity 97 [Annex B] mph [Annex B] Ice wind Velocity V_i : 50 mph Service Velocity V_s : 30 mph [Annex B] Base Ice thickness t_i : 0.75 in [Annex B]

ANTENNAS

	Manufacturer	Model	Height (in)	Front Width (in)	Side Width (in)	Weight (lbs)	Shape	Quantity	Location (%)
Mount I	Pipe M18	·		-					
	Ericsson	IR32 KRD901146-1_B66A_B2	59.25	12.87	8.66	143.00	Flat	0.5	5
	Ericsson	IR32 KRD901146-1_B66A_B2	59.25	12.87	8.66	143.00	Flat	0.5	70
Mount I	Pipe M17	-							
	RFS/Celwave	APX16DWV-16DWV-S-E-A20	55.90	13.30	3.15	40.70	Flat	0.5	10
	RFS/Celwave	APX16DWV-16DWV-S-E-A20	55.90	13.30	3.15	40.70	Flat	0.5	65
	Ericsson	KRY 112 144/2	8.65	6.65	3.19	9.70	Flat	1	20
Mount I									
	RFS/Celwave	APXVAARR24_43-U-NA20	95.90	24.00	8.70	128.00	Flat	0.5	15
	RFS/Celwave	APXVAARR24_43-U-NA20	95.90	24.00	8.70	128.00	Flat	0.5	75
	Ericsson	Radio 4449 B71+B12	14.95	13.19	9.25	75.00	Flat	1	50
Mount I	•								
	Ericsson	IR32 KRD901146-1_B66A_B2	59.25	12.87	8.66	143.00	Flat	0.5	5
	Ericsson	IR32 KRD901146-1_B66A_B2	59.25	12.87	8.66	143.00	Flat	0.5	70
Mount I	Pipe M59								
	RFS/Celwave	APX16DWV-16DWV-S-E-A20	55.90	13.30	3.15	40.70	Flat	0.5	10
	RFS/Celwave	APX16DWV-16DWV-S-E-A20	55.90	13.30	3.15	40.70	Flat	0.5	65
	Ericsson	KRY 112 144/2	8.65	6.65	3.19	9.70	Flat	1	20
Mount I		100//1000	05.00	2:00	0.70	100.00	-		
	RFS/Celwave	APXVAARR24_43-U-NA20	95.90	24.00	8.70	128.00	Flat	0.5	15
	RFS/Celwave	APXVAARR24_43-U-NA20	95.90	24.00	8.70	128.00	Flat	0.5	75
	Ericsson	Radio 4449 B71+B12	14.95	13.19	9.25	75.00	Flat	1	50
									L

PROJECT	135648.002.01 - Waterbury/Rt 8_1, C PG						
SUBJECT	Stand-off Mounts Mount Analysis						
DATE	07/08/19	PAGE	2	OF	3		



				٠.	LOIVE			
Nount Pipe M39 Ericsson	IR32 KRD901146-1_B66A_B2	59.25	12.87	8.66	143.00	Flat	0.5	5
Ericsson	IR32 KRD901146-1_B66A_B2	59.25	12.87	8.66	143.00	Flat	0.5	70
LIICSSOIT	INSERNOSOTI TO 1_BOOK_BE	33.23	12.07	0.00	115.00	riac	0.5	70
Nount Pipe M38								
RFS/Celwave	APX16DWV-16DWV-S-E-A20	55.90	13.30	3.15	40.70	Flat	0.5	10
RFS/Celwave	APX16DWV-16DWV-S-E-A20	55.90	13.30	3.15	40.70	Flat	0.5	65
Ericsson	KRY 112 144/2	8.65	6.65	3.19	9.70	Flat	1	20
Litesson	1001 112 111/2	0.00	0.00	5115	3170	riac		
Nount Pipe M29								
RFS/Celwave	APXVAARR24_43-U-NA20	95.90	24.00	8.70	128.00	Flat	0.5	15
RFS/Celwave	APXVAARR24_43-U-NA20	95.90	24.00	8.70	128.00	Flat	0.5	75
Ericsson	Radio 4449 B71+B12	14.95	13.19	9.25	75.00	Flat	1	50
Nount Pipe M6								
Ericsson	KRY 112 144/2	8.65	6.65	3.19	9.70	Flat	1	20
	,							
Mount Pipe M48							-	•
Ericsson	KRY 112 144/2	8.65	6.65	3.19	9.70	Flat	1	20
Mount Pipe M27								
Ericsson	KRY 112 144/2	8.65	6.65	3.19	9.70	Flat	1	20
Mount Pipe M2								
Ericsson	6X12 HCS	14.00	16.00	8.00	23.50	Flat	1	50
Mount Pipe M44								
Ericsson	6X12 HCS	14.00	16.00	8.00	23.50	Flat	1	50
Mount Pipe						_		

PROJECT	135648.002.01 - Waterbury/Rt 8_1, C PG					
SUBJECT	Stand-off Mounts Mount Analysis					
DATE	07/08/19	PAGE	3	OF	3	




INPUT [REF: ANSI/TIA-222-G2005]

Member Number	Section Set	Wind Projection (in)	Length (in)	Perimeter (in)	Shape	D _c (in)
M1	F1-CP1	0.38	3.19	21.25	Flat	10.26
M2	F1-S1	3.00	20.00	12.00	Flat	4.24
M3	F1-CP1	0.38	3.19	21.25	Flat	10.26
M4	F1-S1	3.00	20.00	12.00	Flat	4.24
M5	F1-P1	4.50	60.00	14.14	Round	4.50
M6	MF-H1	2.88	162.00	9.03	Round	2.88
M7	MF-H1	2.88	162.00	9.03	Round	2.88
M8	MF-P1	2.88	126.00	9.03	Round	2.88
M17	MF-P2	2.38	84.00	7.46	Round	2.38
M18	MF-P2	2.38	84.00	7.46	Round	2.38
M19	MF-P2	2.38	84.00	7.46	Round	2.38
M22	F1-CP1	0.38	3.19	21.25	Flat	10.26
M23	F1-S1	3.00	20.00	12.00	Flat	4.24
M24	F1-CP1	0.38	3.19	21.25	Flat	10.26
M25	F1-S1	3.00	20.00	12.00	Flat	4.24
M26	F1-P1	4.50	60.00	14.14	Round	4.50
M27	MF-H1	2.88	162.00	9.03	Round	2.88
M28	MF-H1	2.88	162.00	9.03	Round	2.88
M29	MF-P1	2.88	126.00	9.03	Round	2.88
M38	MF-P2	2.38	84.00	7.46	Round	2.38
M39	MF-P2	2.38	84.00	7.46	Round	2.38
M40	MF-P2	2.38	84.00	7.46	Round	2.38
M43	F1-CP1	0.38	3.19	21.25	Flat	10.26
M44	F1-S1	3.00	20.00	12.00	Flat	4.24
M45	F1-CP1	0.38	3.19	21.25	Flat	10.26
M46	F1-S1	3.00	20.00	12.00	Flat	4.24
M47	F1-P1	4.50	60.00	14.14	Round	4.50
M48	MF-H1	2.88	162.00	9.03	Round	2.88
M49	MF-H1	2.88	162.00	9.03	Round	2.88
M50	MF-P1	2.88	126.00	9.03	Round	2.88
M59	MF-P2	2.38	84.00	7.46	Round	2.38
M60	MF-P2	2.38	84.00	7.46	Round	2.38
M61	MF-P2	2.38	84.00	7.46	Round	2.38
M64	Tieback	1.90	115.91	5.97	Round	1.90
M65	Tieback	1.90	115.91	5.97	Round	1.90
M66	Tieback	1.90	115.91	5.97	Round	1.90
M67	Add Tieback	2.38	116.52	7.46	Round	2.38
M68	Add Tieback	2.38	116.52	7.46	Round	2.38
M69	Add Tieback	2.38	116.52	7.46	Round	2.38








Member Code Checks Displayed (Enveloped) Envelope Only Solution

B+T Group		SK - 1
PG	CT11214D - Waterbury/Rt 8_1	July 8, 2019 at 2:52 PM
135648.002.01		135648_002_01_WaterburyRt 8_1







Member Shear Checks Displayed (Enveloped) Envelope Only Solution

B+T Group		SK - 2
PG	CT11214D - Waterbury/Rt 8_1	July 8, 2019 at 2:53 PM
135648.002.01		135648_002_01_WaterburyRt 8_1

Company : B+T Group
Designer : PG
Job Number : 135648.002.01
Model Name : CT11214D - Waterbury/Rt 8_1

July 8, 2019 3:02 PM Checked By:_

Hot Rolled Steel Section Sets

	Label	Shape	Type	Design List	Material	Design Rul	A [in2]	lyy [in4]	Izz [in4]	J [in4]
1	MF-H1	PIPE 2.5	Beam	Pipe	A53 Gr.B	Typical	1.61	1.45	1.45	2.89
2	MF-P1	PIPE 2.5	Column	Pipe	A53 Gr.B	Typical	1.61	1.45	1.45	2.89
3	MF-P2	PIPE 2.0	Column	Pipe	A53 Gr.B	Typical	1.02	.627	.627	1.25
4	F1-S1	HSS3X3X3	Beam	Tube	A500 Gr.B	Typical	1.89	2.46	2.46	4.03
5	F1-P1	PIPE 4.0	Column	Pipe	A53 Gr.B	Typical	2.96	6.82	6.82	13.6
6	Tieback	PIPE 1.5	Beam	Pipe	A53 Gr.B	Typical	.749	.293	.293	.586
7	F1-CP1	PL 3/8X10.25	Beam	RECT	A36 Gr.36	Typical	3.844	.045	33.653	.176
8	Add Tieback	PIPE 2.0	Beam	Pipe	A53 Gr.B	Typical	1.02	.627	.627	1.25

Member Primary Data

	Label	I Joint	J Joint	K Joint		Section/Shape	Туре	Design List	Material	Design Rules
1	M1	N1	N2		90	F1-CP1	Beam	RECT	A36 Gr.36	Typical
2	M2	N2	N3			F1-S1	Beam	Tube	A500 Gr.B	Typical
3	M3	N4	N5		90	F1-CP1	Beam	RECT	A36 Gr.36	Typical
4	M4	N5	N6			F1-S1	Beam	Tube	A500 Gr.B	Typical
5	M5	N7	N8			F1-P1	Column	Pipe	A53 Gr.B	Typical
6	M6	N9	N10			MF-H1	Beam	Pipe	A53 Gr.B	Typical
7	M7	N11	N12			MF-H1	Beam	Pipe	A53 Gr.B	Typical
8	M8	N13	N14			MF-P1	Column	Pipe	A53 Gr.B	Typical
9	M9	N15	N16			RIGID	None	None	RIGID	Typical
10	M10	N17	N18			RIGID	None	None	RIGID	Typical
11	M11	N19	N20			RIGID	None	None	RIGID	Typical
12	M12	N21	N22			RIGID	None	None	RIGID	Typical
13	M13	N23	N24			RIGID	None	None	RIGID	Typical
14	M14	N25	N26			RIGID	None	None	RIGID	Typical
15	M15	N27	N28			RIGID	None	None	RIGID	Typical
16	M16	N29	N30			RIGID	None	None	RIGID	Typical
17	M17	N31	N32			MF-P2	Column	Pipe	A53 Gr.B	Typical
18	M18	N33	N34			MF-P2	Column	Pipe	A53 Gr.B	Typical
19	M19	N35	N36			MF-P2	Column	Pipe	A53 Gr.B	Typical
20	M20	N37	N38			RIGID	None	None	RIGID	Typical
21	M21	N39	N40			RIGID	None	None	RIGID	Typical
22	M22	N41	N42		90	F1-CP1	Beam	RECT	A36 Gr.36	Typical
23	M23	N42	N43			F1-S1	Beam	Tube	A500 Gr.B	Typical
24	M24	N44	N45		90	F1-CP1	Beam	RECT	A36 Gr.36	Typical
25	M25	N45	N46			F1-S1	Beam	Tube	A500 Gr.B	Typical
26	M26	N47	N48			F1-P1	Column	Pipe	A53 Gr.B	Typical
27	M27	N49	N50			MF-H1	Beam	Pipe	A53 Gr.B	Typical
28	M28	N51	N52			MF-H1	Beam	Pipe	A53 Gr.B	Typical
29	M29	N53	N54			MF-P1	Column	Pipe	A53 Gr.B	Typical
30	M30	N55	N56			RIGID	None	None	RIGID	Typical
31	M31	N57	N58			RIGID	None	None	RIGID	Typical
32	M32	N59	N60			RIGID	None	None	RIGID	Typical
33	M33	N61	N62			RIGID	None	None	RIGID	Typical
34	M34	N63	N64			RIGID	None	None	RIGID	Typical
35	M35	N65	N66			RIGID	None	None	RIGID	Typical
36	M36	N67	N68			RIGID	None	None	RIGID	Typical
37	M37	N69	N70			RIGID	None	None	RIGID	Typical
38	M38	N71	N72			MF-P2	Column	Pipe	A53 Gr.B	Typical
39	M39	N73	N74			MF-P2	Column	Pipe	A53 Gr.B	Typical
40	M40	N75	N76			MF-P2	Column	Pipe	A53 Gr.B	Typical
41	M41	N77	N78			RIGID	None	None	RIGID	Typical
42	M42	N79	N80			RIGID	None	None	RIGID	Typical
43	M43	N81	N82		90	F1-CP1	Beam	RECT	A36 Gr.36	Typical



Company : B+T Group
Designer : PG
Job Number : 135648.002.01
Model Name : CT11214D - Waterbury/Rt 8_1

July 8, 2019 3:02 PM Checked By:_

Member Primary Data (Continued)

	Label	I Joint	J Joint	K Joint	Rotate(deg)	Section/Shape	Туре	Design List	Material	Design Rules
44	M44	N82	N83			F1-S1	Beam	Tube	A500 Gr.B	Typical
45	M45	N84	N85		90	F1-CP1	Beam	RECT	A36 Gr.36	Typical
46	M46	N85	N86			F1-S1	Beam	Tube	A500 Gr.B	Typical
47	M47	N87	N88			F1-P1	Column	Pipe	A53 Gr.B	Typical
48	M48	N89	N90			MF-H1	Beam	Pipe	A53 Gr.B	
49	M49	N91	N92			MF-H1	Beam	Pipe	A53 Gr.B	
50	M50	N93	N94			MF-P1	Column	Pipe	A53 Gr.B	Typical
51	M51	N95	N96			RIGID	None	None	RIGID	Typical
52	M52	N97	N98			RIGID	None	None	RIGID	Typical
53	M53	N99	N100			RIGID	None	None	RIGID	Typical
54	M54	N101	N102			RIGID	None	None	RIGID	Typical
55	M55	N103	N104			RIGID	None	None	RIGID	Typical
56	M56	N105	N106			RIGID	None	None	RIGID	Typical
57	M57	N107	N108			RIGID	None	None	RIGID	Typical
58	M58	N109	N110			RIGID	None	None	RIGID	Typical
59	M59	N111	N112			MF-P2	Column	Pipe	A53 Gr.B	Typical
60	M60	N113	N114			MF-P2	Column	Pipe	A53 Gr.B	Typical
61	M61	N115	N116			MF-P2	Column	Pipe	A53 Gr.B	Typical
62	M62	N117	N118			RIGID	None	None	RIGID	Typical
63	M63	N119	N120			RIGID	None	None	RIGID	Typical
64	M64	N122	N123			Tieback	Beam	Pipe	A53 Gr.B	Typical
65	M65	N124	N125			Tieback	Beam	Pipe .	A53 Gr.B	
66	M66	N126	N127			Tieback	Beam	Pipe	A53 Gr.B	Typical
67	M67	N128	N82			Add Tieback	Beam	Pipe	A53 Gr.B	Typical
68	M68	N130	N2			Add Tieback		Pipe	A53 Gr.B	Typical
69	M69	N132	N42			Add Tieback		Pipe	A53 Gr.B	

Joint Coordinates and Temperatures

	Label	X [ft]	Y [ft]	Z [ft]	Temp [F]	Detach From Diap
1	N1	0.	0	4.5	0	·
2	N2	0.	0	4.76583	0	
3	N3	0.	0	6.432497	0	
4	N4	0.	-3.0416	4.5	0	
5	N5	0.	-3.0416	4.76583	0	
6	N6	0.	-3.0416	6.432497	0	
7	N7	0.	0.9792	6.432497	0	
8	N8	0.	-4.0208	6.432497	0	
9	N9	-6.75	.25	6.739997	0	
10	N10	6.75	.25	6.739997	0	
11	N11	-6.75	-2.75	6.739997	0	
12	N12	6.75	-2.75	6.739997	0	
13	N13	-6.5	3.58333	6.979997	0	
14	N14	-6.5	-6.91667	6.979997	0	
15	N15	-6.5	.25	6.739997	0	
16	N16	-6.5	.25	6.979997	0	
17	N17	-6.5	-2.75	6.739997	0	
18	N18	-6.5	-2.75	6.979997	0	
19	N19	-2	.25	6.739997	0	
20	N20	-2	.25	6.959157	0	
21	N21	-2	-2.75	6.739997	0	
22	N22	-2	-2.75	6.959157	0	
23	N23	2	.25	6.739997	0	
24	N24	2	.25	6.959157	0	
25	N25	2	-2.75	6.739997	0	
26	N26	2	-2.75	6.959157	0	



Company Designer Job Number Model Name

: B+T Group : PG : 135648.002.01

: CT11214D - Waterbury/Rt 8_1

July 8, 2019 3:02 PM Checked By:___

Joint Coordinates and Temperatures (Continued)

	Coordinates and Tem					
	Label	X [ft]	Y [ft]	Z [ft]	Temp [F]	Detach From Diap
27	N27	6.5	.25	6.739997	0	
28	N28	6.5	.25	6.959157	0	
29	N29	6.5	-2.75	6.739997	0	
30	N30	6.5	-2.75	6.959157	0	
31	N31	-2	2.916667	6.959157	0	
32	N32	-2	-4.083333	6.959157	0	
33	N33	2	2.916667	6.959157	0	
34	N34	2	-4.083333	6.959157	0	
35	N35	6.5	2.916667	6.959157	0	
36	N36	6.5	-4.083333	6.959157	0	
37	N37	0.	.25	6.432497	0	
38	N38	0.	.25	6.739997	0	
39	N39	0.	-2.75	6.739997	0	
40	N40	0.	-2.75	6.432497	0	
41	N41	3.897114	0	-2.25	0	
42	N42	4.12733	0	-2.382915	0	
43	N43	5.570706	0	-3.216248	0	
44	N44	3.897114	-3.0416	-2.25	0	
45	N45	4.12733	-3.0416	-2.382915	0	
46					0	
	N46 N47	5.570706	-3.0416	-3.216248		
47		5.570706	0.9792	-3.216248	0	
48	N48	5.570706	-4.0208	-3.216248	0	
49	N49	9.212008	.25	2.475673	0	
50	N50	2.462008	.25	-9.21567	0	
51	<u>N51</u>	9.212008	-2.75	2.475673	0	
52	N52	2.462008	-2.75	-9.21567	0	
53	N53	9.294854	3.58333	2.139167	0	
54	N54	9.294854	-6.91667	2.139167	0	
55	N55	9.087008	.25	2.259167	0	
56	N56	9.294854	.25	2.139167	0	
57	N57	9.087008	-2.75	2.259167	0	
58	N58	9.294854	-2.75	2.139167	0	
59	N59	6.837008	.25	-1.637948	0	
60	N60	7.026806	.25	-1.747528	0	
61	N61	6.837008	-2.75	-1.637948	0	
62	N62	7.026806	-2.75	-1.747528	0	
63	N63	4.837008	.25	-5.102049	0	
64	N64	5.026806	.25	-5.211629	0	
65	N65	4.837008	-2.75	-5.102049	0	
66	N66	5.026806	-2.75	-5.211629	0	
67	N67	2.587008	.25	-8.999163	0	
68	N68	2.776806	.25	-9.108743	0	
69	N69	2.587008	-2.75	-8.999163	0	
70	N70	2.776806	-2.75	-9.108743	0	
71	N71	7.026806	2.916667	-1.747528	0	
72	N72	7.026806	-4.083333	-1.747528	0	
73	N73	5.026806	2.916667	-5.211629	0	
74	N74	5.026806	-4.083333	-5.211629	0	
75	N75	2.776806	2.916667	-9.108743	0	
76	N76	2.776806	-4.083333	-9.108743	0	
77	N77	5.570706	.25	-3.216248	0	
78	N78	5.837008	.25	-3.369998	0	
79	N79	5.837008	-2.75	-3.369998	0	
80	N80	5.570706	-2.75	-3.216248	0	
81	N81	-3.897114	- <u>2.73</u> 4e-16	-2.25	0	
82	N82	-4.12733	4e-16	-2.382915	0	
83	N83	-4.12733 -5.570706	4e-16 4e-16	-3.216248	0	
UJ	LOO	-5.570700	45-10	-3.210240	U	



Company : B+T Group
Designer : PG
Job Number : 135648.002.01
Model Name : CT11214D - Waterbury/Rt 8_1

July 8, 2019 3:02 PM Checked By:_

Joint Coordinates and Temperatures (Continued)

	Label	X [ft]	Y [ft]	Z [ft]	Temp [F]	Detach From Diap
84	N84	-3.897114	-3.0416	-2.25	0	
85	N85	-4.12733	-3.0416	-2.382915	0	
86	N86	-5.570706	-3.0416	-3.216248	0	
87	N87	-5.570706	0.9792	-3.216248	0	
88	N88	-5.570706	-4.0208	-3.216248	0	
89	N89	-2.462008	.25	-9.21567	0	
90	N90	-9.212008	.25	2.475673	0	
91	N91	-2.462008	-2.75	-9.21567	0	
92	N92	-9.212008	-2.75	2.475673	0	
93	N93	-2.794854	3.58333	-9.119163	0	
94	N94	-2.794854	-6.91667	-9.119163	0	
95	N95	-2.587008	.25	-8.999163	0	
96	N96	-2.794854	.25	-9.119163	0	
97	N97	-2.587008	-2.75	-8.999163	0	
98	N98	-2.794854	-2.75	-9.119163	0	
99	N99	-4.837008	.25	-5.102049	0	
100	N100	-5.026806	.25	-5.211629	0	
101	N101	-4.837008	-2.75	-5.102049	0	
102	N102	-5.026806	-2.75	-5.211629	0	
103	N103	-6.837008	.25	-1.637948	0	
104	N104	-7.026806	.25	-1.747528	0	
105	N105	-6.837008	-2.75	-1.637948	0	
106	N106	-7.026806	-2.75	-1.747528	0	
107	N107	-9.087008	.25	2.259167	0	
108	N108	-9.276806	.25	2.149587	0	
109	N109	-9.087008	-2.75	2.259167	0	
110	N110	-9.276806	-2.75	2.149587	0	
111	N111	-5.026806	2.916667	-5.211629	0	
112	N112	-5.026806	-4.083333	-5.211629	0	
113	N113	-7.026806	2.916667	-1.747528	0	
114	N114	-7.026806	-4.083333	-1.747528	0	
115	N115	-9.276806	2.916667	2.149587	0	
116	N116	-9.276806	-4.083333	2.149587	0	
117	N117	-5.570706	.25	-3.216248	0	
118	N118	-5.837008	.25	-3.369998	0	
119	N119	-5.837008	-2.75	-3.369998	0	
120	N120	-5.570706	-2.75	-3.216248	0	
121	N121	0	0	0	0	
122	N122	6.5	-2.208334	6.959157	0	
123	N123	4.076528	-3.0416	-2.353584	0	
124	N124	2.776806	-2.208334	-9.108743	0	
125	N125	-4.076528	-3.0416	-2.353584	0	
126	N126	-9.276806	-2.208334	2.149587	0	
127	N127	0.	-3.0416	4.707169	0	
128	N128	-6.5	1.	6.979997	0	
129	N130	9.294854	0.999999	2.139167	0	
130	N132	-2.794854	1.	-9.119163	0	

Basic Load Cases

	BLC Description	Category	X Gravity	Y Gravity	Z Gravity	Joint	Point	Distributed	Area(Me	Surface(P
1	Dead	DĽ	_	-1			70		,	,
2	0 Wind - No Ice	WLZ					70	39		
3	90 Wind - No Ice	WLX					70	39		
4	0 Wind - Ice	WLZ					70	39		
5	90 Wind - Ice	WLX					70	39		



July 8, 2019 3:02 PM Checked By:_

Basic Load Cases (Continued)

	BLC Description	Category	X Gravity	Y Gravity	Z Gravity	Joint	Point	Distributed	Area(Me	Surface(P
6	0 Wind - Service	WLZ					70	39		
7	90 Wind - Service	WLX					70	39		
8	Ice	OL1					70	39		
9	Live Load a	LL				1				
10	Live Load b	LL				1				
11	Live Load c	LL				1				
12	Live Load d	LL				1				
13	Maint LL 1	LL					1			
14	Maint LL 2	LL					1			
15	Maint LL 3	LL					1			
16	Maint LL 4	LL					1			
17	Maint LL 5	LL					1			
18	Maint LL 6	LL					1			
19	Maint LL 7	LL					1			
20	Maint LL 8	LL					1			
21	Maint LL 9	LL					1			
22	Maint LL 10	LL					1			
23	Maint LL 11	LL					1			
24	Maint LL 12	LL					1			
25	Maint LL 13	LL								
26	Maint LL 14	LL								
27	Maint LL 15	LL								
28	Maint LL 16	LL								
29	Maint LL 17	LL								
30	Maint LL 18	LL								

Load Combinations

	Description	S P	. S	В	Fa	В	Fa	В	Fa	В	Fa	В	Fa	В	Fa	В	Fa	В	Fa	В	Fa	В	Fa
1	1.4 Dead	Yes Y		1	1.4																		
2	0.9 D + 1.6 - 0 W	Yes Y		1	.9	2	1.6																
3	0.9 D + 1.6 - 30 W	Yes Y		1	.9	2	1.3	3	.8														
4	0.9 D + 1.6 - 60 W	Yes Y		1	.9	3	1.3	2	.8														
5	0.9 D + 1.6 - 90 W	Yes Y		1	.9	3	1.6																
6	0.9 D + 1.6 - 120 W	Yes Y		1	.9	3	1.3	2	8														
7	0.9 D + 1.6 - 150 W	Yes Y		1	.9	2	-1	3	.8														
8	0.9 D + 1.6 - 180 W	Yes Y		1	.9	2	-1.6																
9	0.9 D + 1.6 - 210 W	Yes Y		1	.9	2	-1	3	8														
10	0.9 D + 1.6 - 240 W	Yes Y		1	.9	3	-1	2	8														
11	0.9 D + 1.6 - 270 W	Yes Y		1	.9	3	-1.6																
12	0.9 D + 1.6 - 300 W	Yes Y		1	.9	3	-1	2	.8														
13	0.9 D + 1.6 - 330 W	Yes Y		1	.9	2	1.3	3	8														
14	1.2 D + 1.6 - 0 W	Yes Y		1	1.2	2	1.6																
15	1.2 D + 1.6 - 30 W	Yes Y		1	1.2	2	1.3	3	.8														
16	1.2 D + 1.6 - 60 W	Yes Y		1	1.2	3	1.3	2	.8														
17	1.2 D + 1.6 - 90 W	Yes Y		1	1.2	3	1.6																
18	1.2 D + 1.6 - 120 W	Yes Y		1	1.2	3	1.3	2	8														
19	1.2 D + 1.6 - 150 W	Yes Y		1	1.2	2	-1	3	.8														
20	1.2 D + 1.6 - 180 W	Yes Y		1	1.2	2	-1.6																
21	1.2 D + 1.6 - 210 W	Yes Y		1	1.2	2	-1	3	8														
22	1.2 D + 1.6 - 240 W	Yes Y		1	1.2	3	-1	2	8														
23	1.2 D + 1.6 - 270 W	Yes Y		1	1.2		-1.6																
24	1.2 D + 1.6 - 300 W	Yes Y		1	1.2				.8														
25	1.2 D + 1.6 - 330 W	Yes Y		1	1.2		1.3		8														
26	0.9 D + 1.6 - 0 W/lce	Yes Y		1	.9	4	1.6			8	1												
27	0.9 D + 1.6 - 30 W/Ice			1	.9	4	1.3		.8		1												



: B+T Group : PG : 135648.002.01

July 8, 2019 3:02 PM Checked By:_

Load Combinations (Continued)

Description S	P S	B	Fa	В	Fa	B	Fa	В	Fa	В	Fa	В	Fa	R	Fa	В	Fa	В	Fa	В	Fa
28 0.9 D + 1.6 - 60 W/Ice Ye	s Y		1 .9		1.3			8		<u>ال</u>	. ı a	J	1 a	J	1 a	Τ	. i a	. D	1 a	J	a
29 0.9 D + 1.6 - 90 W/Ice Ye		_	1 .9					8	1												
30 0.9 D + 1.6 - 120 W/Ice Ye			1 .9		1.3		- 8		1												
31 0.9 D + 1.6 - 150 W/Ice Ye			1 .9		-1				1												
32 0.9 D + 1.6 - 180 W/Ice Ye	s V		1 .9		-1.6		.0	8	1												
33 0.9 D + 1.6 - 210 W/Ice Ye			1 .9	4			_ 8		1												
34 0.9 D + 1.6 - 240 W/Ice Ye			1 .9		-1				1												
35 0.9 D + 1.6 - 270 W/Ice Ye			1 .9	5			0	8	1												
36 0.9 D + 1.6 - 300 W/Ice Ye		_	1 .9		-1		.8		1												
37 0.9 D + 1.6 - 330 W/Ice Ye			1 .9		1.3				1												
38 1.2 D + 1.0 - 350 W/Ice Ye			1 1.2			5	0	8	1												
39 1.2 D + 1.0 - 30 W/Ice Ye		_	1 1.2			5	.5		1												
40 1.2 D + 1.0 - 60 W/Ice Ye			1 1.2		.866		.5		1												
41 1.2 D + 1.0 - 90 W/Ice Ye			1 1.2			4		8	1												
42 1.2 D + 1.0 - 120 W/Ice Ye			1 1.2			1	5		1												
43 1.2 D + 1.0 - 150 W/Ice Ye			1 1.2				.5		1												
44 1.2 D + 1.0 - 180 W/Ice Ye			1 1.2			J	.0	8	1												
45 1.2 D + 1.0 - 210 W/Ice Ye			1 1.2		866	5	5		1												
46 1.2 D + 1.0 - 240 W/Ice Ye			1 1.2		866		5		1												
47 1.2 D + 1.0 - 270 W/Ice Ye			1 1.2			7	.0	8	1												
48 1.2 D + 1.0 - 300 W/Ice Ye			1 1.2		866	4	.5		1												
49 1.2 D + 1.0 - 330 W/Ice Ye		_	1 1.2				5		1												
50 1.2 D + 1.5 LL a + Service Ye			1 1.2			<u> </u>	0	9													
51 1.2 D + 1.5 LL a + ServiceYe			1 1.2		.866	7	.5														
52 1.2 D + 1.5 LL a + Service Ye			1 1.2					9													
53 1.2 D + 1.5 LL a + Service Ye			1 1.2		1	U		9													
54 1.2 D + 1.5 LL a + Service Ye			1 1.2			6	- 5														
55 1.2 D + 1.5 LL a + Service Ye			1 1.2		866		.5		1.5												
56 1.2 D + 1.5 LL a + Service Ye		_	1 1.2				.0	9	1.5												
57 1.2 D + 1.5 LL a + Service Ye			1 1.2		866	7	- 5														
58 1.2 D + 1.5 LL a + Service Ye			1 1.2				5														
59 1.2 D + 1.5 LL a + Service Ye		_	1 1.2			0	0	9	1.5												
60 1.2 D + 1.5 LL a + Service Ye			1 1.2			6	.5														
61 1.2 D + 1.5 LL a + Service Ye			1 1.2																		
62 1.2 D + 1.5 LL b + Service Ye			1 1.2				5		1.5												
63 1.2 D + 1.5 LL b + Service Ye			1 1.2			7	5		1.5												
64 1.2 D + 1.5 LL b + Service Ye			1 1.2					10													
65 1.2 D + 1.5 LL b + Service Ye			1 1.2		1	U			1.5												
66 1.2 D + 1.5 LL b + Service Ye		_	1 1.2			6	5														
67 1.2 D + 1.5 LL b + Service Ye			1 1.2	_					1.5	_											
68 1.2 D + 1.5 LL b + Service Ye			1 1.2						1.5												
69 1.2 D + 1.5 LL b + Service Ye					866	7	- 5														
70 1.2 D + 1.5 LL b + ServiceYe			1 1.2		866																
71 1.2 D + 1.5 LL b + ServiceYe			1 1.2				0		1.5												
72 1.2 D + 1.5 LL b + Service Ye			1 1.2			6	5		1.5												
73 1.2 D + 1.5 LL b + Service Ye			1 1.2	_					1.5												
74 1.2 D + 1.5 LL c + ServiceYe			1 1.2				0		1.5												
75 1.2 D + 1.5 LL c + ServiceYe			1 1.2		.866	7	.5		1.5	_											
76 1.2 D + 1.5 LL c + ServiceYe			1 1.2						1.5												
77 1.2 D + 1.5 LL c + ServiceYe			1 1.2		1	U	.0		1.5												
78 1.2 D + 1.5 LL c + ServiceYe			1 1.2			6	- 5		1.5												
79 1.2 D + 1.5 LL c + ServiceYe		_	1 1.2		866		.5		1.5												
80 1.2 D + 1.5 LL c + ServiceYe			1 1.2						1.5												
81 1.2 D + 1.5 LL c + ServiceYe			1 1.2	_	866	7	_ 5		1.5												
82 1.2 D + 1.5 LL c + ServiceYe			1 1.2																		
83 1.2 D + 1.5 LL c + ServiceYe			1 1.2		-1	U	5		1.5												
84 1.2 D + 1.5 LL c + ServiceYe			1 1.2			6	.5		1.5												
04 1.2 D + 1.0 LL 0 + 061 10616	<u>ا</u> ا اِ		ı I.Z	1	UUU	U	.ວ	111	⊥1.ວ												



July 8, 2019 3:02 PM Checked By:_

Load Combinations (Continued)

Description	S P	S B	Fa	В	Fa	В	Fa	В	Fa	В	Fa	В	Fa	В	Fa	В	Fa	В	Fa	В	Fa
85 1.2 D + 1.5 LL c + Service	Yes Y	1	1.2	6	.866	7	5	11	1.5												
86 1.2 D + 1.5 LL d + Service	Yes Y	1	1.2	6	1				1.5												
87 1.2 D + 1.5 LL d + Service	Yes Y	1	1.2	6	.866	7	.5		1.5												
88 1.2 D + 1.5 LL d + Service	Yes Y	1	1.2	7	.866		.5		1.5												
89 1.2 D + 1.5 LL d + Service	Yes Y	1	1.2	7	1				1.5												
90 1.2 D + 1.5 LL d + Service	Yes Y	1	1.2	7	.866	6	5		1.5												
91 1.2 D + 1.5 LL d + Service		1	1.2	6	866	7	.5	12	1.5												
92 1.2 D + 1.5 LL d + Service	Yes Y	1	1.2	6	-1				1.5												
93 1.2 D + 1.5 LL d + Service	Yes Y	1	1.2	6	866	7	5	12	1.5												
94 1.2 D + 1.5 LL d + Service	Yes Y	1	1.2	7	866	6	5	12	1.5												
95 1.2 D + 1.5 LL d + Service	Yes Y	1	1.2	7	-1				1.5												
96 1.2 D + 1.5 LL d + Service	Yes Y	1	1.2	7	866	6	.5	12	1.5												
97 1.2 D + 1.5 LL d + Service	Yes Y	1	1.2	6	.866	7	5	12	1.5												
98 1.2 D + 1.5 LL Maint (1)Yes Y	1	1.2						1.5												
99 1.2 D + 1.5 LL Maint (2)Yes Y	1	1.2					14	1.5												
100 1.2 D + 1.5 LL Maint (3)Yes Y	1	1.2					15	1.5												
101 1.2 D + 1.5 LL Maint (4)Yes Y	1	1.2					16	1.5												
102 1.2 D + 1.5 LL Maint (5)Yes Y	1	1.2					17	1.5												
103 1.2 D + 1.5 LL Maint (1	1.2					18	1.5												
104 1.2 D + 1.5 LL Maint (1	1.2					19	1.5												
105 1.2 D + 1.5 LL Maint (8)Yes Y	1	1.2					20	1.5												
106 1.2 D + 1.5 LL Maint (9)Yes Y	1	1.2					21	1.5												
107 1.2 D + 1.5 LL Maint (10)		1	1.2					22	1.5												
108 1.2 D + 1.5 LL Maint (11)		1	1.2					23	1.5												
109 1.2 D + 1.5 LL Maint (12)		1	1.2					24	1.5												
110 1.2 D + 1.5 LL Maint (13)	Yes Y	1	1.2						1.5												
111 1.2 D + 1.5 LL Maint (14)		1	1.2						1.5												
112 1.2 D + 1.5 LL Maint (15)	Yes Y	1	1.2					27	1.5												
113 1.2 D + 1.5 LL Maint (16)	Yes Y	1	1.2					28	1.5												
114 1.2 D + 1.5 LL Maint (17)	Yes Y	1	1.2						1.5												
115 1.2 D + 1.5 LL Maint (18)	Yes Y	1	1.2					30	1.5												

Member Point Loads (BLC 1 : Dead)

	Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]
1	M18	Υ	071	%5
2	M18	Υ	071	%70
3	M18	Υ	0	0
4	M18	Υ	0	0
5	M18	Υ	0	0
6	M17	Υ	02	%10
7	M17	Υ	02	%65
8	M17	Υ	01	%20
9	M17	Υ	0	0
10	M17	Υ	0	0
11	M8	Υ	064	%15
12	M8	Υ	064	%75
13	M8	Υ	075	%50
14	M8	Υ	0	0
15	M8	Υ	0	0
16	M60	Υ	071	%5
17	M60	Υ	071	%70
18	M60	Υ	0	0
19	M60	Υ	0	0
20	M60	Υ	0	0
21	M59	Υ	02	%10



July 8, 2019 3:02 PM Checked By:_

Member Point Loads (BLC 1 : Dead) (Continued)

	Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]
22	M59	Υ	02	%65
23	M59	Υ	01	%20
24	M59	Υ	0	0
25	M59	Υ	0	0
26	M50	Υ	064	%15
27	M50	Υ	064	%75
28	M50	Υ	075	%50
29	M50	Υ	0	0
30	M50	Υ	0	0
31	M39	Υ	071	%5
32	M39	Υ	071	%70
33	M39	Υ	0	0
34	M39	Υ	0	0
35	M39	Υ	0	0
36	M38	Y	02	%10
37	M38	Ý	02	%65
38	M38	Ý	01	%20
39	M38	Y	0	0
40	M38	Y	0	0
41	M29	Ý	064	%15
42	M29	Ý	064	%75
43	M29	Y	075	%50
44	M29	Y	0	0
45	M29	Ý	0	0
46	M6	Y	01	%20
47	M6	Ý	0	0
48	M6	Υ	0	0
49	M6	Υ	0	0
50	M6	Υ	0	0
51	M48	Y	01	%20
52	M48	Y	0	0
53	M48	Υ	0	0
54	M48	Υ	0	0
55	M48	Υ	0	0
56	M27	Y	01	%20
57	M27	Ý	0	0
58	M27	Υ	0	0
59	M27	Y	0	0
60	M27	Y	0	0
61	M2	Y	024	%50
62	M2	Y	0	0
63	M2	Y	0	0
64	M2	Y	0	0
65	M2	Y	0	0
66	M44	Y	024	%50
67	M44	Ý	0	0
68	M44	Y	0	0
69	M44	Y	0	0
70	M44	Y	0	0

Member Point Loads (BLC 2: 0 Wind - No Ice)

	Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]
1	M18	Z	105	%5
2	M18	Z	105	%70
3	M18	Z	0	0
4	M18	Z	0	0



: B+T Group : PG : 135648.002.01

: CT11214D - Waterbury/Rt 8_1

July 8, 2019 3:02 PM Checked By:_

Member Point Loads (BLC 2: 0 Wind - No Ice) (Continued)

	Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]
5	M18	Z	0	0
6	M17	Z	101	%10
7	<u>M17</u>	Z	101	%65
8	M17	<u>Z</u>	015	%20
9	<u>M17</u>	Z	0	0
10	M17	Z	0	0
11	M8	Z	311	%15
12	<u>M8</u>	Z	311	%75
13	<u>M8</u>	Z	051	<u>%50</u>
14	<u>M8</u>	Z	0	0
15	<u>M8</u>	Z	0	0
16	M60	Z	105	%5
17	M60	Z	105	%70
18	M60	Z	0	0
19	M60	Z	0	0
20	M60	Z	0	0
21	M59	Z	101	%10
22	M59	Z	101	%65
23	M59	Z	015	%20
24	M59	Z	0	0
25	M59	Z	0	0
26	M50	Z	311	%15
27	M50	Z	311	%75
28	M50	Z	051	%50
29	M50	Z	0	0
30	M50	Z	0	0
31	M39	Z	105	%5
32	M39	Z	105	%70
33	M39	Z	0	0
34	M39	Z	0	0
35	M39	Z	0	0
36	M38	Z	101	%10
37	M38	Z	101	%65
38	M38	Z	015	%20
39	M38	Z	0	0
40	M38	Z	0	0
41	M29	Z	311	%15
42	M29	Z	311	%75
43	M29	Z	051	%50
44	M29	Z	0	0
45	M29	Z	0	0
46	<u>M6</u>	Z	015	%20
47	<u>M6</u>	Z	0	0
48	<u>M6</u>	Z	0	0
49	<u>M6</u>	Z	0	0
50	M6	Z	0	0
51	M48	Z Z	015	%20
52	M48		0	0
53	M48	Z	0	0
54	M48	Z	0	0
55	M48	Z	0	0
56	M27	Z	015	%20
57	M27	Z	0	0
58	M27	Z	0	0
59	M27	Z	0	0
60	M27	Z	0	0
61	M2	Z	058	%50



July 8, 2019 3:02 PM Checked By:_

Member Point Loads (BLC 2: 0 Wind - No Ice) (Continued)

	Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]
62	M2	Z	0	0
63	M2	Z	0	0
64	M2	Z	0	0
65	M2	Z	0	0
66	M44	Z	058	%50
67	M44	Z	0	0
68	M44	Z	0	0
69	M44	Z	0	0
70	M44	Z	0	0

Member Point Loads (BLC 3: 90 Wind - No Ice)

	Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]
1	M18	X	071	%5 ⁻
2	M18	X	071	%70
3	M18	X	0	0
4	M18	Χ	0	0
5	M18	Х	0	0
6	M17	X	024	%10
7	M17	X	024	%65
8	M17	X	007	%20
9	M17	X	0	0
10	M17	X	0	0
11	M8	X	113	%15
12	M8	X	113	%75
13	M8	X	035	%50
14	M8	X	0	0
15	M8	X	0	0
16	M60	X	071	%5
17	M60	X	071	%70
18	M60	X	0	0
19	M60	X	0	0
20	M60	X	0	0
21	M59	X	024	%10
22	M59	X	024	%65
23	M59	X	007	%20
24	M59	X	0	0
25	M59	X	0	0
26	M50	X	113	%15
27	M50	X	113	%75
28	M50	X	035	%50
29	M50	X	0	0
30	M50	X	0	0
31	M39	X	071	%5
32	M39	X	071	%70
33	M39	X	0	0
34	M39	X	0	0
35	M39	X	0	0
36	M38	X	024	%10
37	M38	X	024	%65
38	M38	X	007	%20
39	M38	X	0	0
40	M38	X	0	0
41	M29	X	113	%15
42	M29	X	113	%75
43	M29	X	035	%50
44	M29	X	0	0

: B+T Group : PG : 135648.002.01

: CT11214D - Waterbury/Rt 8_1

July 8, 2019 3:02 PM Checked By:___

Member Point Loads (BLC 3: 90 Wind - No Ice) (Continued)

	Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]
45	M29	X	0	0
46	M6	Х	007	%20
47	M6	Х	0	0
48	M6	Х	0	0
49	M6	X	0	0
50	M6	X	0	0
51	M48	Х	007	%20
52	M48	X	0	0
53	M48	Х	0	0
54	M48	Х	0	0
55	M48	X	0	0
56	M27	Χ	007	%20
57	M27	Χ	0	0
58	M27	X	0	0
59	M27	X	0	0
60	M27	X	0	0
61	M2	X	029	%50
62	M2	X	0	0
63	M2	X	0	0
64	M2	X	0	0
65	M2	X	0	0
66	M44	X	029	%50
67	M44	X	0	0
68	M44	X	0	0
69	M44	X	0	0
70	M44	Χ	0	0

Member Point Loads (BLC 4: 0 Wind - Ice)

	Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]
1	M18	Z	037	%5
2	M18	Z	037	%70
3	M18	Z	0	0
4	M18	Z	0	0
5	M18	Z	0	0
6	M17	Z	036	%10
7	M17	Z	036	%65
8	M17	Z	008	%20
9	M17	Z	0	0
10	M17	Z	0	0
11	M8	Z	097	%15
12	M8	Z	097	%75
13	M8	Z	021	%50
14	M8	Z	0	0
15	M8	Z	0	0
16	M60	Z	037	%5
17	M60	Z	037	%70
18	M60	Z	0	0
19	M60	Z	0	0
20	M60	Z	0	0
21	M59	Z	036	%10
22	M59	Z	036	%65
23	M59	Z	008	%20
24	M59	Z	0	0
25	M59	Z	0	0
26	M50	Z	097	%15
27	M50	Z	097	%75



: B+T Group : PG : 135648.002.01

: CT11214D - Waterbury/Rt 8_1

July 8, 2019 3:02 PM Checked By:_

Member Point Loads (BLC 4: 0 Wind - Ice) (Continued)

	Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]
28	M50	Z	021	%50
29	M50	Z	0	0
30	M50	Z	0	0
31	M39	Z	037	%5
32	M39	Z	037	%70
33	M39	Z	0	0
34	M39	Z	0	0
35	M39	Z	0	0
36	M38	Z	036	%10
37	M38		036	%65
38	M38	Z Z	008	%20
39	M38	Z	0	0
40	M38	Z	0	0
41	M29	Z	097	%15
42	M29	Z	097	%75
43	M29	Z	021	%50
44	M29	Z	0	0
45	M29	Z	0	0
46	M6	Z	008	%20
47	M6	Z	006	
48	NIO	Z	0	0
49	M6	Z	0	0
50	NIO	Z	0	0
51	M48	Z Z	008	%20
52	M48		0	0
53	M48	Z Z	0	0
54	M48		0	-
55	M48	Z	0	0
56	M27	Z	008	%20
57	M27	Z	0	0
58	M27	Z	0	0
59	M27	Z	0	0
60	M27	Z	0	0
61	<u>M2</u>	Z	023	%50
62	M2	Z	0	0
63	<u>M2</u>	Z	0	0
64	M2	Z	0	0
65	M2	Z	0	0
66	M44	Z	023	%50
67	M44	Z	0	0
68	M44	Z	0	0
69	M44	Z	0	0
70	M44	Z	0	0

Member Point Loads (BLC 5: 90 Wind - Ice)

	Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]
1	M18	X	028	%5 ⁻
2	M18	X	028	%70
3	M18	X	0	0
4	M18	X	0	0
5	M18	X	0	0
6	M17	X	014	%10
7	M17	X	014	%65
8	M17	X	005	%20
9	M17	X	0	0
10	M17	X	0	0



: B+T Group : PG : 135648.002.01

: CT11214D - Waterbury/Rt 8_1

July 8, 2019 3:02 PM Checked By:___

Member Point Loads (BLC 5: 90 Wind - Ice) (Continued)

	Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]
11	M8	X	043	%15
12	M8	X	043	%75
13	M8	X	016	%50
14	M8	X	0	0
15	<u>M8</u>	X	0	0
16	M60	X	028	%5
17	M60	X	028	%70
18	M60	X	0	0
19	M60	X	0	0
20	M60	X	0	0
21	M59	X	014	%10
22	M59	X	014	%65
23	M59	X	005	%20
24	M59	X	0	0
25	M59	X	0	0
26	M50	X	043	%15
27	M50	X	043	%75
28	M50	X	016	%50
29	M50	X	0	0
30	M50	X	0	0
31	M39	X	028	%5
32	M39	X	028	%70
33	M39	X	0	0
34	M39	X	0	0
35	M39	X	0	0
36	M38	X	014	%10
37	M38	X	014	%65
38	M38	X	005	%20
39	M38	X	0	0
40	M38	X	0	0
41	M29	X	043	%15
42	M29	X	043	%75
43	M29	X	016	%50
44	M29	X	0	0
45	M29	X	0	0
46	M6	X	005	%20
47	M6	X	0	0
48	M6	X	0	0
49	M6	X	0	0
50	M6	X	0	0
51	M48	X	005	%20
52	M48	X	0	0
53	M48	X	0	0
54	M48	X	0	0
55	M48	X	0	0
56	M27	X	005	%20
57	M27	X	0	0
58	M27	X	0	0
59	M27	X	0	0
60	M27	X	0	0
61	M2	X	014	%50
62	M2	X	0	0
63	M2	X	0	0
64	M2	X	0	0
65	M2	X	0	0
66	M44	X	014	%50
67	M44	X	0	0
	IVITT			



: B+T Group : PG : 135648.002.01

: CT11214D - Waterbury/Rt 8_1

July 8, 2019 3:02 PM Checked By:__

Member Point Loads (BLC 5: 90 Wind - Ice) (Continued)

	Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]
68	M44	X	0	0
69	M44	Χ	0	0
70	M44	X	0	0

Member Point Loads (BLC 6: 0 Wind - Service)

- III CITTLE	Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]
1	M18	Z	01	%5
2	M18	Z	01	%70
3	M18	Z	0	0
4	M18	Z	0	0
5	M18	Z	0	0
6	M17	Z	01	%10
7	M17	Z	01	%65
8	M17	Z	001	%20
9	M17	Z	0	0
10	M17	Z	0	0
11	M8	Z	029	%15
12	M8	Z	029	%75
13	M8	Z	005	%50
14	M8	Z	0	0
15	M8	Z	0	0
16	M60	Z	01	%5
17	M60	Z	01	%70
18	M60	Z	0	0
19	M60	Z	0	0
20	M60	Z	0	0
21	M59	Z	01	%10
22	M59	Z	01	%65
23	M59	Z	001	%20
24	M59	Z	0	0
25	M59	Z	0	0
26	M50	Z	029	%15
27	M50	Z	029	%75
28	M50	Z	005	%50
29	M50	Z	0	0
30	M50	Z	0	0
31	M39	Z	01	%5
32	M39	Z	01	%70
33	M39	Z	0	0
34	M39	Z	0	0
35	M39	Z	0	0
36	M38	Z	01	%10
37	M38	Z	01	%65
38	M38	Z	001	%20
39	M38	Z	0	0
40	M38	Z	0	0
41	M29	Z 	029	%15
42	M29		029	%75
43	M29	<u>Z</u> Z	005	%50
44	M29	<u>Z</u>	0	0
45	M29	Z	0	0
46	<u>M6</u>	Z	001	%20
47	<u>M6</u>	Z	0	0
48	<u>M6</u>	Z	0	0
49	<u>M6</u>	Z Z	0	0
50	M6	Z	0	0

: B+T Group : PG : 135648.002.01

: CT11214D - Waterbury/Rt 8_1

July 8, 2019 3:02 PM Checked By:____

Member Point Loads (BLC 6: 0 Wind - Service) (Continued)

	Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]
51	M48	Z	001	%20
52	M48	Z	0	0
53	M48	Z	0	0
54	M48	Z	0	0
55	M48	Z	0	0
56	M27	Z	001	%20
57	M27	Z	0	0
58	M27	Z	0	0
59	M27	Z	0	0
60	M27	Z	0	0
61	M2	Z	005	%50
62	M2	Z	0	0
63	M2	Z	0	0
64	M2	Z	0	0
65	M2	Z	0	0
66	M44	Z	005	%50
67	M44	Z	0	0
68	M44	Z	0	0
69	M44	Z	0	0
70	M44	Z	0	0

Member Point Loads (BLC 7: 90 Wind - Service)

	Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]
1	M18	X	007	%5
2	M18	X	007	%70
3	M18	X	0	0
4	M18	X	0	0
5	M18	X	0	0
6	M17	X	002	%10
7	M17	Χ	002	%65
8	M17	X	0007	%20
9	M17	X	0	0
10	M17	X	0	0
11	M8	Χ	011	%15
12	M8	Χ	011	%75
13	M8	X	003	%50
14	M8	X	0	0
15	M8	X	0	0
16	M60	X	007	%5
17	M60	X	007	%70
18	M60	X	0	0
19	M60	X	0	0
20	M60	X	0	0
21	M59	X	002	%10
22	M59	X	002	%65
23	M59	X	0007	%20
24	M59	X	0	0
25	M59	X	0	0
26	M50	X	011	%15
27	M50	X	011	%75
28	M50	X	003	%50
29	M50	X	0	0
30	M50	X	0	0
31	M39	X	007	%5
32	M39	X	007	%70
33	M39	X	0	0



July 8, 2019 3:02 PM Checked By:_

Member Point Loads (BLC 7: 90 Wind - Service) (Continued)

	Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]
34	M39	X	0	0
35	M39	X	0	0
36	M38	X	002	%10
37	M38	X	002	%65
38	M38	X	0007	%20
39	M38	X	0	0
40	M38	X	0	0
41	M29	X	011	%15
42	M29	X	011	%75
43	M29	X	003	%50
44	M29	X	0	0
45	M29	X	0	0
46	M6	X	0007	%20
47	M6	X	0	0
48	M6	X	0	0
49	M6	X	0	0
50	M6	X	0	0
51	M48	X	0007	%20
52	M48	X	0	0
53	M48	X	0	0
54	M48	X	0	0
55	M48	X	0	0
56	M27	X	0007	%20
57	M27	X	0	0
58	M27	X	0	0
59	M27	X	0	0
60	M27	X	0	0
61	M2	X	003	%50
62	M2	X	0	0
63	M2	X	0	0
64	M2	X	0	0
65	M2	X	0	0
66	M44	X	003	%50
67	M44	X	0	0
68	M44	X	0	0
69	M44	X	0	0
70	M44	X	0	0

Member Point Loads (BLC 8 : Ice)

	Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]
1	M18	Υ	09	%5
2	M18	Υ	09	%70
3	M18	Υ	0	0
4	M18	Υ	0	0
5	M18	Υ	0	0
6	M17	Υ	075	%10
7	M17	Υ	075	%65
8	M17	Υ	014	%20
9	M17	Υ	0	0
10	M17	Υ	0	0
11	M8	Υ	23	%15
12	M8	Υ	23	%75
13	M8	Υ	047	%50
14	M8	Υ	0	0
15	M8	Υ	0	0
16	M60	Υ	09	%5



: B+T Group : PG : 135648.002.01

: CT11214D - Waterbury/Rt 8_1

July 8, 2019 3:02 PM Checked By:_

Member Point Loads (BLC 8 : Ice) (Continued)

	Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]
17	M60	Υ	09	%70 °
18	M60	Υ	0	0
19	M60	Υ	0	0
20	M60	Υ	0	0
21	M59	Υ	075	%10
22	M59	Υ	075	%65
23	M59	Y	014	%20
24	M59	Υ	0	0
25	M59	Y	0	0
26	M50	Ý	23	%15
27	M50	Ý	23	%75
28	M50	Ý	047	%50
29	M50	Y	0	0
30	M50	Y	0	0
31	M39	Y	09	%5
32	M39	Y	09	%70
33	M39	Y	0	0
34	M39	Y	0	0
35	M39	Y	0	0
36	M38	Y	075	%10
37	M38	Y	075 075	%10 %65
		Y		%05 %20
38	M38	Y	014	
39	M38	Y	0	0
40	M38		0	0
41	M29	Y	23	%15
42	M29	Y	23	%75
43	<u>M29</u>	Y	047	<u>%50</u>
44	<u>M29</u>	Y	0	0
45	<u>M29</u>	Y	0	0
46	<u>M6</u>	Y	014	%20
47	<u>M6</u>	Y	0	0
48	M6	Y	0	0
49	M6	Y	0	0
50	M6	Y	0	0
51	M48	Y	014	%20
52	M48	Y	0	0
53	M48	Y	0	0
54	M48	Y	0	0
55	M48	Y	0	0
56	M27	Y	014	%20
57	M27	Y	0	0
58	M27	Υ	0	0
59	M27	Υ	0	0
60	M27	Υ	0	0
61	M2	Υ	048	%50
62	M2	Y	0	0
63	M2	Y	0	0
64	M2	Y	0	0
65	M2	Y	0	0
66	M44	Y	048	%50
67	M44	Y	0	0
68	M44	Y	0	0
69	M44	Y	0	0
70	M44	Y	0	0

Member Point Loads (BLC 13: Maint LL 1)



: B+T Group : PG : 135648.002.01 : CT11214D - Waterbury/Rt 8_1

July 8, 2019 3:02 PM Checked By:_

Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]			
1 M6	Υ	25	%5			
Member Point Loads (BL	C 14 · Maint I I 2)					
Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]			
1 M7	Υ	25	%5			
Member Point Loads (BL	C 15 : Maint LL 3)					
Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]			
1 M48	Y	25	<u>2004:101[11, 70]</u>			
Member Point Loads (BL	C 16 · Maint 4)					
Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]			
1 M49	Υ	25	%5			
Member Point Loads (BL	C 17 : Maint LL 5)					
Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]			
1 M27	Y	25	%5			
Member Point Loads (BL	C 18 · Maint 6)					
Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]			
1 M28	Y	25	%5			
Member Point Loads (BL	C 19 : Maint LL 7)					
Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]			
1 M2			%50			
Member Point Loads (BL	C 20 : Maint LL 8)					
Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]			
1 M4	Υ	25	%50			
Member Point Loads (BL	C 21 : Maint LL 9)					
Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]			
1 M44	Υ	25	%50			
Member Point Loads (BL	C 22 : Maint LL 10)					
Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]			
1 M46	Y	25	%50			
Member Point Loads (BL	C 23 : Maint LL 11)					
Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]			
1 M23	Y	25	%50			
Member Point Loads (BL	C 24 : Maint LL 12)					
Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]			
1 M25	Y	25	%50			
Member Distributed Loads (BLC 2 : 0 Wind - No Ice)						
	-		ocation[ft,%] End Location[ft,%			
Member Label						
1 M1 2 M2	Z00 Z01	1001	0 0			

: B+T Group : PG : 135648.002.01

: CT11214D - Waterbury/Rt 8_1

July 8, 2019 3:02 PM Checked By:__

Member Distributed Loads (BLC 2: 0 Wind - No Ice) (Continued)

	Member Label	Direction	Start Magnitude[k/ft,	End Magnitude[k/ft,F	Start Location[ft,%]	End Location[ft,%]
3	M3	Ζ	001	001	0	0
4	M4	Z	01	01	0	0
5	M5	Ζ	007	007	0	0
6	M6	Z	009	009	0	0
7	M7	Ζ	009	009	0	0
8	M8	Ζ	009	009	0	0
9	M17	Z	007	007	0	0
10	M18	Z	007	007	0	0
11	M19	Z	007	007	0	0
12	M22	Z	001	001	0	0
13	M23	Z	01	01	0	0
14	M24	Z	001	001	0	0
15	M25	Z	01	01	0	0
16	M26	Z	007	007	0	0
17	M27	Z	009	009	0	0
18	M28	Z	009	009	0	0
19	M29	Z	009	009	0	0
20	M38	Z	007	007	0	0
21	M39	Z	007	007	0	0
22	M40	Z	007	007	0	0
23	M43	Z	001	001	0	0
24	M44	Z	01	01	0	0
25	M45	Z	001	001	0	0
26	M46	Z	01	01	0	0
27	M47	Z	007	007	0	0
28	M48	Z	009	009	0	0
29	M49	Z	009	009	0	0
30	M50	Z	009	009	0	0
31	M59	Z	007	007	0	0
32	M60	Z	007	007	0	0
33	M61	Z	007	007	0	0
34	M64	Z	006	006	0	0
35	M65	Z	006	006	0	0
36	M66	Z	006	006	0	0
37	M67	Z	007	007	0	0
38	M68	Z	007	007	0	0
39	M69	Ζ	007	007	0	0

Member Distributed Loads (BLC 3 : 90 Wind - No Ice)

	DOI BIOGINDACOU EOC		, 00 ,,,,,a ,,,o,,			
	Member Label	Direction	Start Magnitude[k/ft,	End Magnitude[k/ft,F	Start Location[ft,%]	End Location[ft,%]
1	M1	X	001	001	0	0
2	M2	X	01	01	0	0
3	M3	X	001	001	0	0
4	M4	X	01	01	0	0
5	M5	X	007	007	0	0
6	M6	Χ	009	009	0	0
7	M7	X	009	009	0	0
8	M8	X	009	009	0	0
9	M17	X	007	007	0	0
10	M18	X	007	007	0	0
11	M19	X	007	007	0	0
12	M22	X	001	001	0	0
13	M23	X	01	01	0	0
14	M24	X	001	001	0	0
15	M25	X	01	01	0	0
16	M26	X	007	007	0	0

: B+T Group : PG : 135648.002.01

: CT11214D - Waterbury/Rt 8_1

July 8, 2019 3:02 PM Checked By:___

Member Distributed Loads (BLC 3: 90 Wind - No Ice) (Continued)

	Member Label	Direction	Start Magnitude[k/ft,	End Magnitude[k/ft,F	Start Location[ft,%]	End Location[ft,%]
17	M27	X	009	009	0	0
18	M28	X	009	009	0	0
19	M29	X	009	009	0	0
20	M38	X	007	007	0	0
21	M39	X	007	007	0	0
22	M40	X	007	007	0	0
23	M43	X	001	001	0	0
24	M44	X	01	01	0	0
25	M45	X	001	001	0	0
26	M46	X	01	01	0	0
27	M47	X	007	007	0	0
28	M48	X	009	009	0	0
29	M49	X	009	009	0	0
30	M50	X	009	009	0	0
31	M59	X	007	007	0	0
32	M60	X	007	007	0	0
33	M61	X	007	007	0	0
34	M64	X	006	006	0	0
35	M65	X	006	006	0	0
36	M66	X	006	006	0	0
37	M67	X	007	007	0	0
38	M68	X	007	007	0	0
39	M69	Χ	007	007	0	0

Member Distributed Loads (BLC 4: 0 Wind - Ice)

	Member Label	Direction	Start Magnitude[k/ft,	End Magnitude[k/ft,F	Start Location[ft,%]	End Location[ft,%]
1	M1	Ζ	008	008	0	0
2	M2	Ζ	007	007	0	0
3	M3	Ζ	008	008	0	0
4	M4	Ζ	007	007	0	0
5	M5	Ζ	003	003	0	0
6	M6	Z	003	003	0	0
7	M7	Z	003	003	0	0
8	M8	Ζ	003	003	0	0
9	M17	Z	003	003	0	0
10	M18	Z	003	003	0	0
11	M19	Ζ	003	003	0	0
12	M22	Ζ	008	008	0	0
13	M23	Z	007	007	0	0
14	M24	Z	008	008	0	0
15	M25	Z	007	007	0	0
16	M26	Z	003	003	0	0
17	M27	Z	003	003	0	0
18	M28	Z	003	003	0	0
19	M29	Z	003	003	0	0
20	M38	Ζ	003	003	0	0
21	M39	Z	003	003	0	0
22	M40	Z	003	003	0	0
23	M43	Z	008	008	0	0
24	M44	Z	007	007	0	0
25	M45	Z	008	008	0	0
26	M46	Z	007	007	0	0
27	M47	Z	003	003	0	0
28	M48	Z	003	003	0	0
29	M49	Ζ	003	003	0	0
30	M50	Z	003	003	0	0



Company Designer Job Number

: B+T Group : PG : 135648.002.01

Model Name : CT11214D - Waterbury/Rt 8_1

July 8, 2019 3:02 PM Checked By:__

Member Distributed Loads (BLC 4: 0 Wind - Ice) (Continued)

	Member Label	Direction	Start Magnitude[k/ft,	End Magnitude[k/ft,F	Start Location[ft,%]	End Location[ft,%]
31	M59	Z	003	003	0	0
32	M60	Ζ	003	003	0	0
33	M61	Ζ	003	003	0	0
34	M64	Ζ	002	002	0	0
35	M65	Ζ	002	002	0	0
36	M66	Z	002	002	0	0
37	M67	Ζ	002	002	0	0
38	M68	Z	002	002	0	0
39	M69	Z	002	002	0	0

Member Distributed Loads (BLC 5: 90 Wind - Ice)

	Member Label	Direction		End Magnitude[k/ft,F	Start Location[ft,%]	End Location[ft,%]
1	M1	X	008	008	0	0
2	M2	X	007	007	0	0
3	M3	X	008	008	0	0
4	M4	X	007	007	0	0
5	M5	X	003	003	0	0
6	M6	X	003	003	0	0
7	M7	Х	003	003	0	0
8	M8	X	003	003	0	0
9	M17	X	003	003	0	0
10	M18	X	003	003	0	0
11	M19	X	003	003	0	0
12	M22	X	008	008	0	0
13	M23	X	007	007	0	0
14	M24	X	008	008	0	0
15	M25	X	007	007	0	0
16	M26	X	003	003	0	0
17	M27	X	003	003	0	0
18	M28	X	003	003	0	0
19	M29	X	003	003	0	0
20	M38	X	003	003	0	0
21	M39	X	003	003	0	0
22	M40	X	003	003	0	0
23	M43	X	008	008	0	0
24	M44	X	007	007	0	0
25	M45	X	008	008	0	0
26	M46	X	007	007	0	0
27	M47	X	003	003	0	0
28	M48	X	003	003	0	0
29	M49	X	003	003	0	0
30	M50	X	003	003	0	0
31	M59	X	003	003	0	0
32	M60	X	003	003	0	0
33	M61	X	003	003	0	0
34	M64	X	002	002	0	0
35	M65	X	002	002	0	0
36	M66	X	002	002	0	0
37	M67	X	002	002	0	0
38	M68	X	002	002	0	0
39	M69	X	002	002	0	0
_ Jy	IVIUS	_	UU∠	002	U	U

Member Distributed Loads (BLC 6: 0 Wind - Service)

	Member Label	Direction	Start Magnitude[k/ft,	End Magnitude[k/ft,F	Start Location[ft,%]	End Location[ft,%]
1	M1	Z	0001	0001	0	0
2	M2	Z	001	001	0	0



: B+T Group : PG : 135648.002.01

: CT11214D - Waterbury/Rt 8_1

July 8, 2019 3:02 PM Checked By:___

Member Distributed Loads (BLC 6: 0 Wind - Service) (Continued)

	Member Label	Direction	Start Magnitude[k/ft,	End Magnitude[k/ft,F	Start Location[ft,%]	End Location[ft,%]
3	M3	Ζ	0001	0001	0	0
4	M4	Z	001	001	0	0
5	M5	Z	0006	0006	0	0
6	M6	Ζ	0004	0004	0	0
7	M7	Ζ	0004	0004	0	0
8	M8	Z	0004	0004	0	0
9	M17	Z	0003	0003	0	0
10	M18	Ζ	0003	0003	0	0
11	M19	Ζ	0003	0003	0	0
12	M22	Ζ	0001	0001	0	0
13	M23	Ζ	001	001	0	0
14	M24	Z	0001	0001	0	0
15	M25	Ζ	001	001	0	0
16	M26	Ζ	0006	0006	0	0
17	M27	Ζ	0004	0004	0	0
18	M28	Ζ	0004	0004	0	0
19	M29	Z	0004	0004	0	0
20	M38	Z	0003	0003	0	0
21	M39	Z	0003	0003	0	0
22	M40	Z	0003	0003	0	0
23	M43	Z	0001	0001	0	0
24	M44	Z	001	001	0	0
25	M45	Ζ	0001	0001	0	0
26	M46	Ζ	001	001	0	0
27	M47	Z	0006	0006	0	0
28	M48	Ζ	0004	0004	0	0
29	M49	Z	0004	0004	0	0
30	M50	Z	0004	0004	0	0
31	M59	Z	0003	0003	0	0
32	M60	Z	0003	0003	0	0
33	M61	Z	0003	0003	0	0
34	M64	Z	0003	0003	0	0
35	M65	Ζ	0003	0003	0	0
36	M66	Z	0003	0003	0	0
37	M67	Z	0003	0003	0	0
38	M68	Z	0003	0003	0	0
39	M69	Z	0003	0003	0	0

Member Distributed Loads (BLC 7 : 90 Wind - Service)

	Member Label	Direction	Start Magnitude[k/ft,	End Magnitude[k/ft,F	Start Location[ft,%]	End Location[ft,%]
1	M1	Χ	0001	0001	0	0
2	M2	X	001	001	0	0
3	M3	X	0001	0001	0	0
4	M4	X	001	001	0	0
5	M5	X	0006	0006	0	0
6	M6	X	0004	0004	0	0
7	M7	X	0004	0004	0	0
8	M8	X	0004	0004	0	0
9	M17	X	0003	0003	0	0
10	M18	X	0003	0003	0	0
11	M19	X	0003	0003	0	0
12	M22	Χ	0001	0001	0	0
13	M23	X	001	001	0	0
14	M24	X	0001	0001	0	0
15	M25	X	001	001	0	0
16	M26	X	0006	0006	0	0

: B+T Group : PG : 135648.002.01

: CT11214D - Waterbury/Rt 8_1

July 8, 2019 3:02 PM Checked By:___

Member Distributed Loads (BLC 7: 90 Wind - Service) (Continued)

	Member Label	Direction	Start Magnitude[k/ft,	End Magnitude[k/ft,F	Start Location[ft,%]	End Location[ft,%]
17	M27	X	0004	0004	0	0
18	M28	X	0004	0004	0	0
19	M29	X	0004	0004	0	0
20	M38	X	0003	0003	0	0
21	M39	X	0003	0003	0	0
22	M40	X	0003	0003	0	0
23	M43	X	0001	0001	0	0
24	M44	X	001	001	0	0
25	M45	X	0001	0001	0	0
26	M46	X	001	001	0	0
27	M47	X	0006	0006	0	0
28	M48	X	0004	0004	0	0
29	M49	X	0004	0004	0	0
30	M50	X	0004	0004	0	0
31	M59	X	0003	0003	0	0
32	M60	X	0003	0003	0	0
33	M61	X	0003	0003	0	0
34	M64	X	0003	0003	0	0
35	M65	X	0003	0003	0	0
36	M66	Χ	0003	0003	0	0
37	M67	X	0003	0003	0	0
38	M68	X	0003	0003	0	0
39	M69	Χ	0003	0003	0	0

Member Distributed Loads (BLC 8: Ice)

	Member Label	Direction	Start Magnitude[k/ft,	. End Magnitude[k/ft,F	Start Location[ft,%]	End Location[ft,%]
1	M1	Υ	025	025	0	0
2	M2	Υ	013	013	0	0
3	M3	Υ	025	025	0	0
4	M4	Υ	013	013	0	0
5	M5	Υ	013	013	0	0
6	M6	Υ	01	01	0	0
7	M7	Υ	01	01	0	0
8	M8	Υ	01	01	0	0
9	M17	Υ	009	009	0	0
10	M18	Υ	009	009	0	0
11	M19	Υ	009	009	0	0
12	M22	Υ	025	025	0	0
13	M23	Υ	013	013	0	0
14	M24	Υ	025	025	0	0
15	M25	Υ	013	013	0	0
16	M26	Υ	013	013	0	0
17	M27	Y	01	01	0	0
18	M28	Υ	01	01	0	0
19	M29	Υ	01	01	0	0
20	M38	Υ	009	009	0	0
21	M39	Υ	009	009	0	0
22	M40	Υ	009	009	0	0
23	M43	Υ	025	025	0	0
24	M44	Υ	013	013	0	0
25	M45	Υ	025	025	0	0
26	M46	Υ	013	013	0	0
27	M47	Υ	013	013	0	0
28	M48	Υ	01	01	0	0
29	M49	Υ	01	01	0	0
30	M50	Υ	01	01	0	0



Company : B+T Group Designer : PG Job Number : 135648.002.01

Model Name : CT11214D - Waterbury/Rt 8_1

July 8, 2019 3:02 PM Checked By:_

Member Distributed Loads (BLC 8 : Ice) (Continued)

	Member Label	Direction	Start Magnitude[k/ft,	End Magnitude[k/ft,F	Start Location[ft,%]	End Location[ft,%]
31	M59	Υ	009	009	0	0
32	M60	Υ	009	009	0	0
33	M61	Υ	009	009	0	0
34	M64	Υ	008	008	0	0
35	M65	Υ	008	008	0	0
36	M66	Υ	008	008	0	0
37	M67	Υ	009	009	0	0
38	M68	Υ	009	009	0	0
39	M69	Υ	009	009	0	0

Joint Loads and Enforced Displacements (BLC 9 : Live Load a)

	Joint Label	L,D,M	Direction	Magnitude[(k,k-ft), (in,rad), (k*s^2/f
1	N17	L	Υ	5

Joint Loads and Enforced Displacements (BLC 10 : Live Load b)

	Joint Label	L,D,M	Direction	Magnitude[(k,k-ft), (in,rad), (k*s^2/f
1	N21		Y	-5

Joint Loads and Enforced Displacements (BLC 11 : Live Load c)

	Joint Label	L,D,M	Direction	Magnitude[(k,k-ft), (in,rad), (k*s^2/f
1	N25	L	Υ	5

Joint Loads and Enforced Displacements (BLC 12 : Live Load d)

	Joint Label	L,D,M	Direction	Magnitude[(k,k-ft), (in,rad), (k*s^2/f
1	N29	L	Υ	5

Envelope Joint Reactions

	Joint		X [k]	LC	Y [k]	LC	Z [k]	LC	MX [k-ft]	LC	MY [k-ft]	LC	MZ [k-ft]	LC
1	N4	max	.887	87	1.454	43	2.067	39	06	2	0	115	.253	97
2		min	-1.794	57	.259	2	705	0	34	44	0	1	5	55
3	N1	max	2.357	18	1.384	44	.536	13	062	2	0	115	.26	97
4		min	-1.574	12	.191	2	-2.046	43	348	44	0	1	526	55
5	N81	max	1.05	18	1.379	39	3.914	14	.558	38	0	115	.023	2
6		min	449	12	.226	9	-2.667	8	01	8	0	1	102	20
7	N84	max	.758	5	1.455	39	036	13	.535	38	0	115	.017	2
8		min	-1.365	23	.257	9	-2.25	43	017	8	0	1	103	44
9	N41	max	1.167	4	1.32	48	1.672	3	.043	3	0	115	.506	46
10		min	-2.692	34	.253	6	-1.797	21	209	45	0	1	.076	4
11	N44	max	2.375	42	1.423	47	1.531	14	.039	3	0	115	.493	46
12		min	.1	12	.294	5	-1.407	8	191	45	0	1	.069	4
13	Totals:	max	5.599	17	8.259	49	8.819	2						
14		min	-5.599	11	2.265	7	-8.819	20						

Envelope AISC 13th(360-05): LRFD Steel Code Checks

	Member	Shape	Code Check	Loc[ft]	LC	Shear	Loc[ft]	Dir	LC	phi*Pnc	phi*Pnt	phi*Mn	.phi*MnCb Eqn
1	M1	PL 3/8X10	.366	0	44	.728	0	У	55	84.705	124.538	.973	26.594 1 H1-1b
2	M2	HSS3X3X3	.805	1.667	41	.177	0	Z	53	76.645	78.246	6.796	6.796 1 H1-1b
3	M3	PL 3/8X10	.359	0	43	.705	.266	У	55	84.705	124.538	.973	26.594 1 H1-1b
4	M4	HSS3X3X3	.794	1.667	47	.172	0	Z	58	76.645	78.246	6.796	6.796 1 H1-1b
5	M5	PIPE 4.0	.380	4.01	47	.440	4.01		59	86.074	93.24	10.631	10.631 1 H3-6
6	M6	PIPE 2.5	.455	6.75	41	.319	.281		21	12.482	50.715	3.596	3.596 1 H1-1b

July 8, 2019 3:02 PM Checked By:_

Envelope AISC 13th(360-05): LRFD Steel Code Checks (Continued)

	Member	Shape	Code Check	Loc[ft]	LC	Shear	Loc[ft]	Dir	LC	phi*Pncphi*Pntphi*Mnphi*MnCb Eqn
7	M7	PIPE 2.5	.640	6.75	21	.348	4.641		14	12.482 50.715 3.596 3.596 1 H3-6
8	M8	PIPE_2.5	.356	6.234	46	.248	3.391		21	20.573 50.715 3.596 3.596 3 H1-1b
9	M17	PIPE 2.0	.613	2.698	42	.258	5.615		21	17.855 32.13 1.872 1.872 1.H1-1b
10	M18	PIPE 2.0	.479	2.698	94	.091	2.698		96	17.855 32.13 1.872 1.872 1 H1-1b
11	M19	PIPE 2.0	.487	2.698	94	.087	5.177		95	17.855 32.13 1.872 1.872 1H1-1b
12	M22	PL 3/8X10	.353	0	48	.608	0	У	45	84.705 124.538 .973 26.594 1 H1-1b
13	M23	HSS3X3X3	.834	1.667	33	.165	0	Z	33	76.645 78.246 6.796 6.796 1 H1-1b
14	M24	PL 3/8X10	.352	0	47	.593	.266	У	46	84.705 124.538 .973 26.594 1 H1-1b
15	M25	HSS3X3X3	.804	1.667	39	.147	0	Z	38	76.645 78.246 6.796 6.796 1 H1-1b
16	M26	PIPE 4.0	.384	4.01	39	.444	.938		20	86.074 93.24 10.631 10.631 1 H3-6
17	M27	PIPE 2.5	.646	6.75	21	.310	.281		14	12.482 50.715 3.596 3.596 1 H1-1b
18	M28	PIPE 2.5	.744	6.75	14	.302	4.641		19	12.482 50.715 3.596 3.596 1 H1-1b
19	M29	PIPE 2.5	.366	6.234	38	.229	3.391		25	20.573 50.715 3.596 3.596 3 H1-1b
20	M38	PIPE 2.0	.616	2.698	45	.242	5.615		25	17.855 32.13 1.872 1.872 1H1-1b
21	M39	PIPE 2.0	.243	2.698	39	.087	5.615		22	17.855 32.13 1.872 1.872 1H1-1b
22	M40	PIPE 2.0	.186	5.104	21	.103	5.615		21	17.855 32.13 1.872 1.872 2H1-1b
23	M43	PL 3/8X10	.365	0	39	.624	0	У	38	84.705 124.538 .973 26.594 1 H1-1b
24	M44	HSS3X3X3	.841	1.667	37	.167	0	Z	37	76.645 78.246 6.796 6.796 1 H1-1b
25	M45	PL 3/8X10	.360	0	39	.606	.266	У	38	84.705 124.538 .973 26.594 1 H1-1b
26	M46	HSS3X3X3	.805	1.667	43	.145	0	Z	43	76.645 78.246 6.796 6.796 1 H1-1b
27	M47	PIPE 4.0	.387	4.01	43	.418	4.01		43	86.074 93.24 10.631 10.631 1 H3-6
28	M48	PIPE 2.5	.631	6.75	25	.188	.281		17	12.482 50.715 3.596 3.596 1H1-1b
29	M49	PIPE 2.5	.580	6.75	20	.195	4.641		16	12.482 50.715 3.596 3.596 1 H1-1b
30	M50	PIPE 2.5	.365	3.391	38	.146	3.391		17	20.573 50.715 3.596 3.596 2 H1-1b
31	M59	PIPE 2.0	.620	2.698	38	.160	5.615		17	17.855 32.13 1.872 1.872 1.H1-1b
32	M60	PIPE 2.0	.243	2.698	43	.099	5.615		14	17.855 32.13 1.872 1.872 1 H1-1b
33	M61	PIPE 2.0	.183	5.104	14	.094	5.177		20	17.855 32.13 1.872 1.872 2H1-1b
34	M64	PIPE 1.5	.141	4.829	23	.091	9.659		43	4.927 23.593 1.105 1.105 1 H1-1b
35	M65	PIPE 1.5	.163	4.829	15	.090	0		47	4.927 23.593 1.105 1.105 1 H1-1b
36	M66	PIPE 1.5	.157	4.829	20	.092	9.659		39	4.927 23.593 1.105 1.105 1 H1-1b
37	M67	PIPE 2.0	.135	9.71	14	.090	0		56	10.432 32.13 1.872 1.872 1H1-1b*
38	M68	PIPE 2.0	.132	4.855	20	.071	9.71		48	10.432 32.13 1.872 1.872 1H1-1b
39	M69	PIPE 2.0	.102	4.855	24	.074	0		39	10.432 32.13 1.872 1.872 1H1-1b

Exhibit F

Power Density/RF Emissions Report



RADIO FREQUENCY EMISSIONS ANALYSIS REPORT EVALUATION OF HUMAN EXPOSURE POTENTIAL TO NON-IONIZING EMISSIONS

T-Mobile Existing Facility

Site ID: CT11214D

Waterbury/Rt 8_I 1669 Thomaston Avenue Waterbury, Connecticut 06704

May 20, 2019

EBI Project Number: 5219001639

Site Compliance Summary					
Compliance Status:	COMPLIANT				
Site total MPE% of FCC general population allowable limit:	5.83%				



May 20, 2019

T-Mobile Attn: Jason Overbey, RF Manager 35 Griffin Road South Bloomfield, Connecticut 06002

Emissions Analysis for Site: CT11214D - Waterbury/Rt 8_1

EBI Consulting was directed to analyze the proposed T-Mobile facility located at **1669 Thomaston Avenue** in **Waterbury, Connecticut** for the purpose of determining whether the emissions from the Proposed T-Mobile Antenna Installation located on this property are within specified federal limits.

All information used in this report was analyzed as a percentage of current Maximum Permissible Exposure (% MPE) as listed in the FCC OET Bulletin 65 Edition 97-01 and ANSI/IEEE Std C95.1. The FCC regulates Maximum Permissible Exposure in units of microwatts per square centimeter (μ W/cm²). The number of μ W/cm² calculated at each sample point is called the power density. The exposure limit for power density varies depending upon the frequencies being utilized. Wireless Carriers and Paging Services use different frequency bands each with different exposure limits; therefore, it is necessary to report results and limits in terms of percent MPE rather than power density.

All results were compared to the FCC (Federal Communications Commission) radio frequency exposure rules, 47 CFR 1.1307(b)(1) - (b)(3), to determine compliance with the Maximum Permissible Exposure (MPE) limits for General Population/Uncontrolled environments as defined below.

General population/uncontrolled exposure limits apply to situations in which the general population may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Therefore, members of the general population would always be considered under this category when exposure is not employment related, for example, in the case of a telecommunications tower that exposes persons in a nearby residential area.

Public exposure to radio frequencies is regulated and enforced in units of microwatts per square centimeter (μ W/cm²). The general population exposure limits for the 600 MHz and 700 MHz frequency bands are approximately 400 μ W/cm² and 467 μ W/cm², respectively. The general population exposure limit for the 1900 MHz (PCS), 2100 MHz (AWS) and 11 GHz frequency bands is 1000 μ W/cm². Because each carrier will be using different frequency bands, and each frequency band has different exposure limits, it is necessary to report percent of MPE rather than power density.



Occupational/controlled exposure limits apply to situations in which persons are exposed as a consequence of their employment and in which those persons who are exposed have been made fully aware of the potential for exposure and can exercise control over their exposure. Occupational/controlled exposure limits also apply where exposure is of a transient nature as a result of incidental passage through a location where exposure levels may be above general population/uncontrolled limits (see below), as long as the exposed person has been made fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Additional details can be found in FCC OET 65.

CALCULATIONS

Calculations were done for the proposed T-Mobile Wireless antenna facility located at 1669 Thomaston Avenue in Waterbury, Connecticut using the equipment information listed below. All calculations were performed per the specifications under FCC OET 65. Since T-Mobile is proposing highly focused directional panel antennas, which project most of the emitted energy out toward the horizon, all calculations were performed assuming a lobe representing the maximum gain of the antenna per the antenna manufacturer's supplied specifications, minus 10 dB for directional panel antennas and 20 dB for highly focused parabolic microwave dishes, was focused at the base of the tower. For this report, the sample point is the top of a 6-foot person standing at the base of the tower.

For all calculations, all equipment was calculated using the following assumptions:

- 1) I LTE channel (600 MHz Band) was considered for each sector of the proposed installation. These Channels have a transmit power of 30 Watts per Channel.
- 2) 2 LTE channels (700 MHz Band) were considered for each sector of the proposed installation. These Channels have a transmit power of 30 Watts per Channel.
- 3) 4 GSM channels (PCS Band 1900 MHz) were considered for each sector of the proposed installation. These Channels have a transmit power of 30 Watts per Channel.
- 4) 2 LTE channels (PCS Band 1900 MHz) were considered for each sector of the proposed installation. These Channels have a transmit power of 60 Watts per Channel.
- 5) 2 UMTS channels (PCS Band 1900 MHz) were considered for each sector of the proposed installation. These Channels have a transmit power of 30 Watts per Channel.



- 6) 2 LTE channels (AWS Band 2100 MHz) were considered for each sector of the proposed installation. These Channels have a transmit power of 60 Watts per Channel.
- 7) 2 UMTS channels (AWS Band 2100 MHz) were considered for each sector of the proposed installation. These Channels have a transmit power of 30 Watts per Channel.
- 8) All radios at the proposed installation were considered to be running at full power and were uncombined in their RF transmissions paths per carrier prescribed configuration. Per FCC OET Bulletin No. 65 Edition 97-01 recommendations to achieve the maximum anticipated value at each sample point, all power levels emitting from the proposed antenna installation are increased by a factor of 2.56 to account for possible in-phase reflections from the surrounding environment. This is rarely the case, and if so, is never continuous.
- 9) For the following calculations, the sample point was the top of a 6-foot person standing at the base of the tower. The maximum gain of the antenna per the antenna manufacturer's supplied specifications, minus 10 dB for directional panel antennas and 20 dB for highly focused parabolic microwave dishes, was used in this direction. This value is a very conservative estimate as gain reductions for these particular antennas are typically much higher in this direction.
- 10) The antennas used in this modeling are the RFS APXVAARR24_43-U-NA20 for the 600 MHz / 700 MHz channel(s), the RFS APX16DWV-16DWVS-E-A20 for the 1900 MHz / 1900 MHz / 2100 MHz channel(s), the for the 1900 MHz / 2100 MHz channel(s) in Sector A, the RFS APXVAARR24_43-U-NA20 for the 600 MHz / 700 MHz channel(s), the RFS APX16DWV-16DWVS-E-A20 for the 1900 MHz / 1900 MHz / 2100 MHz channel(s), the Ericsson AIR 32 B66Aa/B2a for the 1900 MHz / 2100 MHz channel(s) in Sector B, the RFS APXVAARR24_43-U-NA20 for the 600 MHz / 700 MHz channel(s), the RFS APX16DWV-16DWVS-E-A20 for the 1900 MHz / 1900 MHz / 2100 MHz channel(s), the Ericsson AIR 32 B66Aa/B2a for the 1900 MHz / 2100 MHz channel(s) in Sector C.
- 11) All Antenna gain values and associated transmit power levels are shown in the Site Inventory and Power Data table below. The maximum gain of the antenna per the antenna manufacturer's supplied specifications, minus 10 dB for directional panel antennas and 20 dB for highly focused parabolic microwave dishes, was used for all calculations. This value is a very conservative estimate as gain reductions for these particular antennas are typically much higher in this direction.
- 12) The antenna mounting height centerlines of the proposed antennas are 130 feet and 132 feet above ground level (AGL).



- 13) Emissions values for additional carriers were taken from the Connecticut Siting Council active database. Values in this database are provided by the individual carriers themselves.
- 14) All calculations were done with respect to uncontrolled / general population threshold limits.



T-Mobile Site Inventory and Power Data

Sector:	Α	Sector:	В	Sector:	С
Antenna #:	ı	Antenna #:	ı	Antenna #:	ı
Make / Model:	RFS APXVAARR24_43-U- NA20	Make / Model:	RFS APXVAARR24_43-U- NA20	Make / Model:	RFS APXVAARR24_43-U- NA20
Frequency Bands:	600 MHz / 700 MHz	Frequency Bands:	600 MHz / 700 MHz	Frequency Bands:	600 MHz / 700 MHz
Gain:	12.95 dBd / 13.35 dBd	Gain:	12.95 dBd / 13.35 dBd	Gain:	12.95 dBd / 13.35 dBd
Height (AGL):	I30 feet	Height (AGL):	I 30 feet	Height (AGL):	I 30 feet
Channel Count:	3	Channel Count:	3	Channel Count:	3
Total TX Power (W):	90 Watts	Total TX Power (W):	90 Watts	Total TX Power (W):	90 Watts
ERP (W):	1,889.36	ERP (W):	1,889.36	ERP (W):	1,889.36
Antenna A1 MPE %:	0.91%	Antenna B1 MPE %:	0.91%	Antenna C1 MPE %:	0.91%
Antenna #:	2	Antenna #:	2	Antenna #:	2
Make / Model:	RFS APX16DWV-16DWVS- E-A20	Make / Model:	RFS APX16DWV-16DWVS- E-A20	Make / Model:	RFS APX16DWV-16DWVS- E-A20
Frequency Bands:	1900 MHz / 1900 MHz / 2100 MHz	Frequency Bands:	1900 MHz / 1900 MHz / 2100 MHz	Frequency Bands:	1900 MHz / 1900 MHz / 2100 MHz
Gain:	15.9 dBd / 15.9 dBd / 15.9 dBd	Gain:	15.9 dBd / 15.9 dBd / 15.9 dBd	Gain:	15.9 dBd / 15.9 dBd / 15.9 dBd
Height (AGL):	132 feet	Height (AGL):	I32 feet	Height (AGL):	I32 feet
Channel Count:	8	Channel Count:	8	Channel Count:	8
Total TX Power (W):	240 Watts	Total TX Power (W):	240 Watts	Total TX Power (W):	240 Watts
ERP (W):	9,337.08	ERP (W):	9,337.08	ERP (W):	9,337.08
Antenna A2 MPE %:	1.93%	Antenna B2 MPE %:	1.93%	Antenna C2 MPE %:	1.93%
Antenna #:	3	Antenna #:	3	Antenna #:	3
Make / Model:	Ericsson AIR 32 B66Aa/B2a	Make / Model:	Ericsson AIR 32 B66Aa/B2a	Make / Model:	Ericsson AIR 32 B66Aa/B2a
Frequency Bands:	1900 MHz / 2100 MHz	Frequency Bands:	1900 MHz / 2100 MHz	Frequency Bands:	1900 MHz / 2100 MHz
Gain:	15.35 dBd / 15.85 dBd	Gain:	15.35 dBd / 15.85 dBd	Gain:	15.35 dBd / 15.85 dBd
Height (AGL):	I 32 feet	Height (AGL):	I 32 feet	Height (AGL):	I 32 feet
Channel Count:	4	Channel Count:	4	Channel Count:	4
Total TX Power (W):	240 Watts	Total TX Power (W):	240 Watts	Total TX Power (W):	240 Watts
ERP (W):	8,728.31	ERP (W):	8,728.31	ERP (W):	8,728.31
Antenna A3 MPE %:	1.80%	Antenna B3 MPE %:	1.80%	Antenna C3 MPE %:	1.80%

Site Composite MPE %						
Carrier	MPE %					
T-Mobile (Max at Sector A):	4.63%					
Sprint	1.2%					
Site Total MPE %:	5.83%					

T-Mobile Sector A Total:	4.63%
T-Mobile Sector B Total:	4.63%
T-Mobile Sector C Total:	4.63%
Site Total:	5.83%

T-	T-Mobile Maximum MPE Power Values (Sector A)							
T-Mobile Frequency Band / Technology (Sector A)	# Channels	Watts ERP (Per Channel)	Height (feet)	Total Power Density (µW/cm²)	Frequency (MHz)	Allowable MPE (μW/cm²)	Calculated % MPE	
T-Mobile 600 MHz LTE	I	591.73	130.0	1.26	600 MHz LTE	400	0.32%	
T-Mobile 700 MHz LTE	2	648.82	130.0	2.76	700 MHz LTE	467	0.59%	
T-Mobile 1900 MHz GSM	4	1167.14	132.0	9.63	1900 MHz GSM	1000	0.96%	
T-Mobile 1900 MHz UMTS	2	1167.14	132.0	4.82	1900 MHz UMTS	1000	0.48%	
T-Mobile 2100 MHz UMTS	2	1167.14	132.0	4.82	2100 MHz UMTS	1000	0.48%	
T-Mobile 1900 MHz LTE	2	2056.61	132.0	8.49	1900 MHz LTE	1000	0.85%	
T-Mobile 2100 MHz LTE	2	2307.55	132.0	9.52	2100 MHz LTE	1000	0.95%	
	<u>'</u>			<u>'</u>		Total:	4.63%	



Summary

All calculations performed for this analysis yielded results that were **within** the allowable limits for general population exposure to RF Emissions.

The anticipated maximum composite contributions from the T-Mobile facility as well as the site composite emissions value with regards to compliance with FCC's allowable limits for general population exposure to RF Emissions are shown here:

T-Mobile Sector	Power Density Value (%)
Sector A:	4.63%
Sector B:	4.63%
Sector C:	4.63%
T-Mobile Maximum MPE % (Sector A):	4.63%
Site Total:	5.83%
Site Compliance Status:	COMPLIANT

The anticipated composite MPE value for this site assuming all carriers present is **5.83**% of the allowable FCC established general population limit sampled at the ground level. This is based upon values listed in the Connecticut Siting Council database for existing carrier emissions.

FCC guidelines state that if a site is found to be out of compliance (over allowable thresholds), that carriers over a 5% contribution to the composite value will require measures to bring the site into compliance. For this facility, the composite values calculated were well within the allowable 100% threshold standard per the federal government.

Exhibit G

Mailings Receipt/Proof of Notice

- 1. Ensure there are no other shipping or tracking labels attached to your package. Select the Print button on the print dialog box that appears. Note: If your browser does not support this function select Print from the File menu to print the label.
- 2. **Fold the printed label at the solid line below.** Place the label in a UPS Shipping Pouch. If you do not have a pouch, affix the folded label using clear plastic shipping tape over the entire label.

3. GETTING YOUR SHIPMENT TO UPS

Customers with a Daily Pickup

Your driver will pickup your shipment(s) as usual.


Customers without a Daily Pickup

Take your package to any location of The UPS Store®, UPS Access Point(TM) location, UPS Drop Box, UPS Customer Center, Staples® or Authorized Shipping Outlet near you. Items sent via UPS Return Services(SM) (including via Ground) are also accepted at Drop Boxes. To find the location nearest you, please visit the Resources area of CampusShip and select UPS Locations.

Schedule a same day or future day Pickup to have a UPS driver pickup all your CampusShip packages. Hand the package to any UPS driver in your area.

UPS Access PointTM TIENDA ECUADOR 72 LAKE AVE DANBURY ,CT 06810 UPS Access PointTM
THE UPS STORE
42 LAKE AVENUE EXT
DANBURY ,CT 06811

UPS Access PointTM
PAGUE MENOS SUPERMARKET
107 TRIANGLE ST
DANBURY ,CT 06810



- 1. Ensure there are no other shipping or tracking labels attached to your package. Select the Print button on the print dialog box that appears. Note: If your browser does not support this function select Print from the File menu to print the label.
- 2. **Fold the printed label at the solid line below.** Place the label in a UPS Shipping Pouch. If you do not have a pouch, affix the folded label using clear plastic shipping tape over the entire label.

3. GETTING YOUR SHIPMENT TO UPS

Customers with a Daily Pickup

Your driver will pickup your shipment(s) as usual.


Customers without a Daily Pickup

Take your package to any location of The UPS Store®, UPS Access Point(TM) location, UPS Drop Box, UPS Customer Center, Staples® or Authorized Shipping Outlet near you. Items sent via UPS Return Services(SM) (including via Ground) are also accepted at Drop Boxes. To find the location nearest you, please visit the Resources area of CampusShip and select UPS Locations.

Schedule a same day or future day Pickup to have a UPS driver pickup all your CampusShip packages. Hand the package to any UPS driver in your area.

UPS Access PointTM TIENDA ECUADOR 72 LAKE AVE DANBURY ,CT 06810 UPS Access PointTM
THE UPS STORE
42 LAKE AVENUE EXT
DANBURY ,CT 06811

UPS Access PointTM
PAGUE MENOS SUPERMARKET
107 TRIANGLE ST
DANBURY ,CT 06810



- 1. Ensure there are no other shipping or tracking labels attached to your package. Select the Print button on the print dialog box that appears. Note: If your browser does not support this function select Print from the File menu to print the label.
- 2. **Fold the printed label at the solid line below.** Place the label in a UPS Shipping Pouch. If you do not have a pouch, affix the folded label using clear plastic shipping tape over the entire label.

3. GETTING YOUR SHIPMENT TO UPS

Customers with a Daily Pickup

Your driver will pickup your shipment(s) as usual.

Customers without a Daily Pickup

Take your package to any location of The UPS Store®, UPS Access Point(TM) location, UPS Drop Box, UPS Customer Center, Staples® or Authorized Shipping Outlet near you. Items sent via UPS Return Services(SM) (including via Ground) are also accepted at Drop Boxes. To find the location nearest you, please visit the Resources area of CampusShip and select UPS Locations.

Schedule a same day or future day Pickup to have a UPS driver pickup all your CampusShip packages. Hand the package to any UPS driver in your area.

UPS Access PointTM TIENDA ECUADOR 72 LAKE AVE DANBURY ,CT 06810 UPS Access PointTM
THE UPS STORE
42 LAKE AVENUE EXT
DANBURY ,CT 06811

UPS Access PointTM
PAGUE MENOS SUPERMARKET
107 TRIANGLE ST
DANBURY ,CT 06810



- 1. Ensure there are no other shipping or tracking labels attached to your package. Select the Print button on the print dialog box that appears. Note: If your browser does not support this function select Print from the File menu to print the label.
- 2. **Fold the printed label at the solid line below.** Place the label in a UPS Shipping Pouch. If you do not have a pouch, affix the folded label using clear plastic shipping tape over the entire label.

3. GETTING YOUR SHIPMENT TO UPS

Customers with a Daily Pickup

Your driver will pickup your shipment(s) as usual.

Customers without a Daily Pickup

Take your package to any location of The UPS Store®, UPS Access Point(TM) location, UPS Drop Box, UPS Customer Center, Staples® or Authorized Shipping Outlet near you. Items sent via UPS Return Services(SM) (including via Ground) are also accepted at Drop Boxes. To find the location nearest you, please visit the Resources area of CampusShip and select UPS Locations.

Schedule a same day or future day Pickup to have a UPS driver pickup all your CampusShip packages. Hand the package to any UPS driver in your area.

UPS Access PointTM TIENDA ECUADOR 72 LAKE AVE DANBURY ,CT 06810 UPS Access PointTM
THE UPS STORE
42 LAKE AVENUE EXT
DANBURY ,CT 06811

UPS Access PointTM
PAGUE MENOS SUPERMARKET
107 TRIANGLE ST
DANBURY ,CT 06810

