

#### 9/19/2018

Melanie A. Bachman Executive Director Connecticut Siting Council 10 Franklin Square New Britain, CT 06051

Regarding: Notice of Exempt Modification – Antenna Swap Property Address: 125 South Main Street, West Hartford, MA 06107 AT&T Site: CTL01076 / FA: 10035052

Dear Ms. Bachman:

On behalf of AT&T, please accept this application as notification pursuant to R.C.S.A. §16-50j-73, for construction that constitutes an exempt modification pursuant to R.C.S.A. §16- 50j-72(b) (2).

AT&T currently maintains a wireless telecommunications facility on an existing monopole at the abovereferenced address. Crown Castle, owns said facility. The site consists of nine (9) wireless telecommunication antennas at an antenna centerline height of 107-feet on an existing 105 -foot monopole tower. AT&T now intends to remove (3) Powerwave 7770 panel antennas on position 4 all sectors, while retaining three (3) Powerwave 7770 panel antennas on positions 1, all sectors, and install three (3) new Quintel QS66512-2 panel antennas on position 4 all sectors (for a total of (9) panel antennas), at the 107-foot level. AT&T also intends to install three (3) RRU-32 B2 and (3) RRU-32 on the existing antenna masts.

Please accept this letter pursuant to Regulation of Connecticut State Agencies §16-50j-73, for construction that constitutes an exempt modification pursuant to R.C.S.A. § 16-510j-72(b) (2). In accordance with R.C.S.A., a copy of this letter is being sent to The Honorable Elinor Carbone, Mayor of Torrington, Zoning Enforcement Officer of the City of Torrington, Crown Castle tower owner and Lucille Lefebvre property owner.

The planned modifications to AT&T's facility fall squarely within those activities explicitly provided for in R.C.S.A. §16-50j-72(b) (2).

- 1. The proposed modifications will not result in an increase in the height of the existing tower. AT&T's replacement antennas will be installed at the 107-foot level of the 105-foot monopole.
- 2. The proposed modifications will not involve any changes to ground-mounted equipment and, therefore, will not require and extension of the site boundary.
- 3. The proposed modifications will not increase the noise levels at the facility by six decibels or more, or to levels that exceed state and local criteria.
- 4. The operation of the modified facility will not increase radio frequency (RF) emissions at the facility to a level at or above the Federal Communications Commission (FCC) safety standard. A



cumulative worst-case RF emissions calculation for AT&T's modified facility is provided in the RF Emissions Compliance Report, included,

- 5. The proposed modifications will not cause a change or alteration in the physical or environmental characteristics of the site.
- 6. The tower and its foundation can support AT&T's proposed modifications. (See Structural Analysis Report included).

For the foregoing reasons, AT&T respectfully submits that the proposed modifications to the above referenced telecommunications facility constitutes an exempt modification under R.C.S.A. §16-50j-72(b) (2).

Sincerely,

Kristen LeDuc Real Estate Specialist | Smartlink, LLC 85 Rangeway Road, Building 3, Suite 102 North Billerica, MA 01862

Enclosures

CC w/ enclosures:

The Honorable Shari Cantor, Mayor, Town of West Hartford

Matthew Hart, Town Manager, Town of West Hartford

Todd Dumais, Town Planner, Town of West Hartford

Southern New England Telephone Co. c/o Frontier Communications Tower/Property Owner

## **125 SOUTH MAIN STREET**

Location	125 SOUTH MAIN STREET	Mblu	F10/ 5095/ 125/ /
Parcel ID	5095 1 125 0001	Owner	SOUTHERN NEW ENGLAND TELEPHONE CO
Assessment	\$1,772,120	Appraisal	\$2,531,600
Vision Id #	17685	Building Count	1

#### **Current Value**

	Appraisal		
Valuation Year	Improvements	Land	Total
2016	\$1,212,600	\$1,319,000	\$2,531,600
	Assessment		
Valuation Year	Improvements	Land	Total
2016	\$848,820	\$923,300	\$1,772,120

#### Owner of Record

Owner	SOUTHERN NEW ENGLAND TELEPHONE CO	Sale Price	\$0
Co-Owner	C/O FRONTIER COMM	Certificate	1
Address	401 MERRITT 7 ATTN: TAX DEP	Book & Page	318/ 19
	NORWALK, CT 06851	Sale Date	
		Instrument	U

#### **Ownership History**

	Ownership	History			
Owner	Sale Price	Certificate	Book & Page	Instrument	Sale Date
SOUTHERN NEW ENGLAND TELEPHONE CO	\$0	1	318/ 19	U	

#### **Building Information**

## Building 1 : Section 1

Year Built: Living Area: Replacement Cost: Building Percent Good:	1962 28,098 \$3,539,789 32
Replacement Cost	1 122 700
Build	ling Attributes
Field	Description
STYLE	Telephone Exchange
MODEL	Ind/Comm
Grade	D 0.85
Stories:	2
Occupancy	
Exterior Wall 1	Concrete Block
Exterior Wall 2	
Roof Structure	Flat
Roof Cover	Built Up
Interior Wall 1	Typical
Interior Wall 2	
Floor Type	Reinf Concrete
Floor Cover	Asphalt
Heating Fuel	Typical
Heating Type	Forced Hot Air
АС Туре	Central - Zone
As Built Use	PHON
Bldg Use	Utility Building
# of Bedrooms	
Total Baths	
Туре	01
Wet Sprinkler	100
Dry Sprinkler	
1st Floor Use:	
Class	Class C
Frame Type	Rigid Steel
Plumbing	LIGHT
Ceiling	Acoustic Panel
Group	IND
Wall Height	12
Adjustment	

#### **Building Photo**



(http://images.vgsi.com/photos/WestHartfordCTPhotos //\00\01\66/43.JPG)

#### **Building Layout**



	Building Sub-Areas (sq f	t)	<u>Legend</u>
Code	Description	Gross Area	Living Area
PHN	TELEPHONE EXCHANGE	28,098	28,098
MUS	MULTI USE STORAGE	14,049	0
		42,147	28,098

#### Extra Features

Extra Features	Legend
No Data for Extra Features	

#### Land

Land Use		Land Line Valua	tion
Use Code Description	401 Utility Building	Size (Acres) Frontage	3.03
Zone	RM-1	Depth	
Neighborhood		Assessed Value	\$923,300
Alt Land Appr Category	No	Appraised Value	\$1,319,000

#### Outbuildings

	Outbuildings					Legend
Code	Description	Sub Code	Sub Description	Size	Value	Bldg #
CLP4	Paving, Asphalt			19000 SF	\$22,800	1
CPL6	Light Pole - Steel			20 SF	\$600	1
CFC5	Shed - Concrete Block			286 SF	\$3,900	1
C220	Elevator pass 2k lbs			1 UNIT	\$52,600	1

#### Valuation History

	Appraisal		
Valuation Year	Improvements	Land	Total
2017	\$1,212,600	\$1,319,000	\$2,531,600
2016	\$1,212,600	\$1,319,000	\$2,531,600
2015	\$1,102,400	\$1,319,000	\$2,421,400

	Assessment		
Valuation Year	Improvements	Land	Total
2017	\$848,820	\$923,300	\$1,772,120
2016	\$848,820	\$923,300	\$1,772,120
2015	\$771,680	\$923,300	\$1,694,980

(c) 2016 Vision Government Solutions, Inc. All rights reserved.

SITE SAFE



Smartlink on behalf of AT&T Mobility, LLC Site FA – 10035052 Site ID – CT1076 (MRCTB025383) USID – 59366 Site Name – WEST HARTFORD SBC CO

## 125 SOUTH MAIN STREET WEST HARTFORD, CT 06107

Latitude: N41-45-12.40 Longitude: W72-44-40.00 Structure Type: Monopole

R

Report generated date: July 17, 2018 Report by: Scott Broyles Customer Contact: Romina Kirchmaier

# AT&T Mobility, LLC will be compliant when the remediation recommended in Section 5.2 or other appropriate remediation is implemented.

Sitesafe logo is a registered trademark of Site Safe, LLC. All rights reserved.



## Table of Contents

1 GENERAL SITE SUMMARY	2
<ul> <li>1.1 Report Summary</li> <li>1.2 Signage Summary</li> <li>1.3 Fall Arrest Anchor Point Summary</li> </ul>	2 2 2
2 SCALE MAPS OF SITE	3
3 ANTENNA INVENTORY	5
4 EMISSION PREDICTIONS	6
5 SITE COMPLIANCE	9
<ul><li>5.1 Site Compliance Statement</li><li>5.2 Actions for Site Compliance</li></ul>	9 9
6 REVIEWER CERTIFICATION	10
APPENDIX A – STATEMENT OF LIMITING CONDITIONS	11
APPENDIX A – STATEMENT OF LIMITING CONDITIONS APPENDIX B – REGULATORY BACKGROUND INFORMATION	11 12
APPENDIX A – STATEMENT OF LIMITING CONDITIONS APPENDIX B – REGULATORY BACKGROUND INFORMATION FCC RULES AND REGULATIONS OSHA STATEMENT.	<b>11</b> <b>12</b> 12 13
APPENDIX A – STATEMENT OF LIMITING CONDITIONS APPENDIX B – REGULATORY BACKGROUND INFORMATION FCC RULES AND REGULATIONS OSHA STATEMENT APPENDIX C – SAFETY PLAN AND PROCEDURES	<b>11</b> <b>12</b> 12 13 <b>14</b>
APPENDIX A – STATEMENT OF LIMITING CONDITIONS APPENDIX B – REGULATORY BACKGROUND INFORMATION FCC RULES AND REGULATIONS OSHA STATEMENT APPENDIX C – SAFETY PLAN AND PROCEDURES APPENDIX D – RF EMISSIONS	11 12 13 13 14 15
APPENDIX A – STATEMENT OF LIMITING CONDITIONS APPENDIX B – REGULATORY BACKGROUND INFORMATION FCC RULES AND REGULATIONS OSHA STATEMENT APPENDIX C – SAFETY PLAN AND PROCEDURES APPENDIX D – RF EMISSIONS APPENDIX E – ASSUMPTIONS AND DEFINITIONS	11 12 12 13 13 14 15 16
APPENDIX A – STATEMENT OF LIMITING CONDITIONS APPENDIX B – REGULATORY BACKGROUND INFORMATION FCC RULES AND REGULATIONS OSHA STATEMENT. APPENDIX C – SAFETY PLAN AND PROCEDURES APPENDIX D – RF EMISSIONS APPENDIX D – RF EMISSIONS GENERAL MODEL ASSUMPTIONS AND DEFINITIONS USE OF GENERIC ANTENNAS. DEFINITIONS	11 12 12 13 13 14 16 16 16 16



#### 1 General Site Summary

#### 1.1 Report Summary

AT&T Mobility, LLC	Summary
Access to Antennas Locked?	No
Max Cumulative Simulated RFE Level on the Ground	<1% General Public Limit
FCC & AT&T Compliant?	Will Be Compliant
Optional AT&T Mitigation Items?	No

The following documents were provided by the client and were utilized to create this report:

**RFDS:** NEW-ENGLAND\_CONNECTICUT\_CTL01076\_2018-LTE-Multi-Carrier\_LTE\_sp656b\_2051A0D6QK\_10035052\_59366\_06-21-2017\_Final-RF-Approval\_v4.00

CD's: 10035052\_AE201\_171121\_CTL01076\_REV1

RF Powers Used: RFDS ABOVE

#### 1.2 Signage Summary

AT&T Signage Locations		INFORMATION	Notice	Notice	CAUTION	CAUTION	WARNING	VARNING Determine	M M
	Information 1	Information 2	Notice	Notice 2	Caution	Caution 2	Warning	Warning 2	Barriers
Access Point(s)	[#]	[#]	[#]	[#]	[#]	[#]	[#]	[#]	
Alpha	[#]	[#]	[#]	[#]	[#]	[#]	[#]	[#]	
Beta	[#]	[#]	[#]	[#]	[#]	[#]	[#]	[#]	
Gamma	[#]	[#]	[#]	[#]	[#]	[#]	[#]	[#]	

#### **1.3 Fall Arrest Anchor Point Summary**

Fall Arrest	Parapet Available	Parapet Height	Fall Arrest Anchor
Anchor &	(Y/N)	(inches)	Available (Y/N)
Parapet Info			
Roof Safety Info	N	N/A	Ν



#### 2 Scale Maps of Site

The following diagrams are included:

- Site Scale Map •
- RF Exposure Diagram •
- RF Exposure Diagram Elevation View •

## Site Scale Map For: WEST HARTFORD SBC CO



% of FCC Public Exposure Limit Spatial average 0' - 6'





#### 3 Antenna Inventory

The following antenna inventory was obtained by the customer and was utilized to create the site model diagrams:

				TX Freq	Δ7	Hor BW	Antlen	Ant Gain	3G UMTS	46	Total FRP			7
Ant ID	Operator	Antenna Make & Model	Туре	(MHz)	(Deg)	(Deg)	(ft)	(dBd)	Radio(s)	Radio(s)	(Watts)	х	Y	AGL
1	AT&T MOBILITY LLC	Powerwave 7770	Panel	850	25	82	4.6	11.51	1	0	401.5	151.3'	344'	104.7'
2	AT&T MOBILITY LLC	KMW AM-X-CD-16-65-00T	Panel	737	25	65	6	13.36	0	1	1475.7	156.8'	342.8'	104'
3	AT&T MOBILITY LLC (Proposed)	Quintel QS66512-2	Panel	1900	25	68	6	14.16	0	1	3664.4	166.7'	340.8'	104'
3	AT&T MOBILITY LLC (Proposed)	Quintel QS66512-2	Panel	2300	25	64	6	14.56	0	1	1285.3	166.7'	340.8'	104'
4	AT&T MOBILITY LLC	Powerwave 7770	Panel	850	144	82	4.6	11.51	1	0	401.5	167'	337.2'	104.7'
5	AT&T MOBILITY LLC	KMW AM-X-CD-16-65-00T	Panel	737	144	65	6	13.36	0	1	1475.7	163.7'	334.2'	104'
6	AT&T MOBILITY LLC (Proposed)	Quintel QS66512-2	Panel	1900	144	68	6	14.16	0	1	3664.4	155.7'	326'	104'
6	AT&T MOBILITY LLC (Proposed)	Quintel QS66512-2	Panel	2300	144	64	6	14.56	0	1	1285.3	155.7'	326'	104'
7	AT&T MOBILITY LLC	Powerwave 7770	Panel	850	267	82	4.6	11.51	1	0	401.5	153'	327.1'	104.7'
8	AT&T MOBILITY LLC	KMW AM-X-CD-16-65-00T	Panel	737	267	65	6	13.36	0	1	1475.7	152'	331.7'	104'
9	AT&T MOBILITY LLC (Proposed)	Quintel QS66512-2	Panel	1900	267	68	6	14.16	0	1	3664.4	149.6'	341.5'	104'
9	AT&T MOBILITY LLC (Proposed)	Quintel QS66512-2	Panel	2300	267	64	6	14.56	0	1	1285.3	149.6'	341.5'	104'

NOTE: X, Y and Z indicate relative position of the bottom of the antenna to the origin location on the site, displayed in the model results diagram. Specifically, the Z reference indicates the bottom of the antenna height above the main site level unless otherwise indicated. The distance to the bottom of the antenna is calculated by subtracting half of the length of the antenna from the antenna centerline. Effective Radiated Power (ERP) is provided by the operator or based on Sitesafe experience. The values used in the modeling may be greater than are currently deployed. For other operators at this site the use of "Generic" as an antenna model or "Unknown" for a wireless operator means the information with regard to operator, their FCC license and/or antenna information was not available nor could it be secured while on site. Other operator's equipment, antenna models and powers used for modeling are based on obtained information or Sitesafe experience.



## 4 Emission Predictions

In the RF Exposure Simulations below all heights are reflected with respect to main site level. In most rooftop cases this is the height of the main rooftop and in other cases this can be ground level. Each different height area, rooftop, or platform level is labeled with its height relative to the main site level. Emissions are calculated appropriately based on the relative height and location of that area to all antennas. The total analyzed elevations in the below RF Exposure Simulations are listed below.

- Ground = 0'
- Adjacent Building = 40' AGL

The Antenna Inventory heights are referenced to the same level.

## RF Exposure Simulation For: WEST HARTFORD SBC CO Composite View



% of FCC Public Exposure Limit Spatial average 0' - 6'



Sitesafe OET-65 Model Near Field Boundary: 1.5 \* Aperture Reflection Factor: 1 Spatially Averaged

## RF Exposure Simulation For: WEST HARTFORD SBC CO Elevation View



% of FCC Public Exposure Limit Spatial average 0' - 6'



Sitesafe OET-65 Model Near Field Boundary: 1.5 \* Aperture Reflection Factor: 1 Single Level (0)



#### 5 Site Compliance

#### 5.1 Site Compliance Statement

Upon evaluation of the cumulative RF emission levels from all operators at this site, RF hazard signage and antenna locations, Sitesafe has determined that:

AT&T Mobility, LLC will be compliant when the remediation recommended in Section 5.2 or other appropriate remediation is implemented.

The compliance determination is based on General Public RFE levels derived from theoretical modeling, RF signage placement, proposed antenna inventory and the level of restricted access to the antennas at the site. Any deviation from the AT&T Mobility, LLC's proposed deployment plan could result in the site being rendered non-compliant.

Modeling is used for determining compliance and the percentage of MPE contribution.

#### 5.2 Actions for Site Compliance

Based on FCC regulations, common industry practice, and our understanding of AT&T Mobility, LLC RF Safety Policy requirements, this section provides a statement of recommendations for site compliance. Recommendations have been proposed based on our understanding of existing access restrictions, signage, and an analysis of predicted RFE levels.

AT&T Mobility, LLC will be made compliant if the following changes are implemented:

#### Monopole Access Location

(1) Yellow Caution 2 sign(s) required at base of monopole.

#### Notes:

- This report's diagrams do not show the Access locations because the data provided did not include them.
- Data concerning all other carriers on site was unavailable and therefore not included in this report.
- Signage may already be in place. Sitesafe does not have record of any existing signage because there were no previous visits or data supplied regarding them. All remediation is based on a worst-case scenario.



#### 6 Reviewer Certification

The reviewer whose signature appears below hereby certifies and affirms:

That I am an employee of Sitesafe, LLC., in Vienna, Virginia, at which place the staff and I provide RF compliance services to clients in the wireless communications industry; and

That I am thoroughly familiar with the Rules and Regulations of the Federal Communications Commission (FCC) as well as the regulations of the Occupational Safety and Health Administration (OSHA), both in general and specifically as they apply to the FCC Guidelines for Human Exposure to Radio-frequency Radiation; and

That I have thoroughly reviewed this Site Compliance Report and believe it to be true and accurate to the best of my knowledge as assembled by and attested to by Scott Broyles.

<u>July 17, 2018</u>



## Appendix A - Statement of Limiting Conditions

Sitesafe has provided computer generated model(s) in this Site Compliance Report to show approximate dimensions of the site, and the model is included to assist the reader of the compliance report to visualize the site area, and to provide supporting documentation for Sitesafe's recommendations.

Sitesafe may note in the Site Compliance Report any adverse physical conditions, such as needed repairs, that Sitesafe became aware of during the normal research involved in creating this report. Sitesafe will not be responsible for any such conditions that do exist or for any engineering or testing that might be required to discover whether such conditions exist. Because Sitesafe is not an expert in the field of mechanical engineering or building maintenance, the Site Compliance Report must not be considered a structural or physical engineering report.

Sitesafe obtained information used in this Site Compliance Report from sources that Sitesafe considers reliable and believes them to be true and correct. Sitesafe does not assume any responsibility for the accuracy of such items that were furnished by other parties. When conflicts in information occur between data collected by Sitesafe provided by a second party and data collected by Sitesafe, the data will be used.



#### Appendix B - Regulatory Background Information

#### **FCC Rules and Regulations**

In 1996, the Federal Communications Commission (FCC) adopted regulations for the evaluating of the effects of RF emissions in 47 CFR § 1.1307 and 1.1310. The guideline from the FCC Office of Engineering and Technology is Bulletin 65 ("OET Bulletin 65"), *Evaluating Compliance with FCC Guidelines for Human Exposure to Radio Frequency Electromagnetic Fields*, Edition 97-01, published August 1997. Since 1996 the FCC periodically reviews these rules and regulations as per their congressional mandate.

FCC regulations define two separate tiers of exposure limits: Occupational or "Controlled environment" and General Public or "Uncontrolled environment". The General Public limits are generally five times more conservative or restrictive than the Occupational limit. These limits apply to *accessible* areas where workers or the general public may be exposed to Radio Frequency (RF) electromagnetic fields.

Occupational or Controlled limits apply in situations in which persons are exposed as a consequence of their employment and where those persons exposed have been made fully aware of the potential for exposure and can exercise control over their exposure.

An area is considered a Controlled environment when access is limited to these aware personnel. Typical criteria are restricted access (i.e. locked or alarmed doors, barriers, etc.) to the areas where antennas are located coupled with proper RF warning signage. A site with Controlled environments is evaluated with Occupational limits.

All other areas are considered Uncontrolled environments. If a site has no access controls or no RF warning signage it is evaluated with General Public limits.

The theoretical modeling of the RF electromagnetic fields has been performed in accordance with OET Bulletin 65. The Maximum Permissible Exposure (MPE) limits utilized in this analysis are outlined in the following diagram:



#### FCC Limits for Maximum Permissible Exposure (MPE) Plane-wave Equivalent Power Density



#### Limits for Occupational/Controlled Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm²)	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-			5	6
100,000				

#### Limits for General Population/Uncontrolled Exposure (MPE)

Frequency	Electric	Magnetic	Power	Averaging Time  E  <sup>2</sup> ,						
Range	Field	Field	Density (S)	H  <sup>2</sup> or S (minutes)						
(MHz)	Strength (E)	Strength	(mW/cm²)							
	(V/m)	(H) (A/m)								
0.3-1.34	614	1.63	(100)*	30						
1.34-30	824/f	2.19/f	(180/f²)*	30						
30-300	27.5	0.073	0.2	30						
300-1500			f/1500	30						
1500-			1.0	30						
100,000										
f = frequ	uency in MHz	*Plane-wave equivalent power density								

#### **OSHA** Statement

The General Duty clause of the OSHA Act (Section 5) outlines the occupational safety and health responsibilities of the employer and employee. The General Duty clause in Section 5 states:

(a) Each employer –

- shall furnish to each of his employees employment and a place of employment which are free from recognized hazards that are causing or are likely to cause death or serious physical harm to his employees;
- (2) shall comply with occupational safety and health standards promulgated under this Act.
- (b) Each employee shall comply with occupational safety and health standards and all rules, regulations, and orders issued pursuant to this Act which are applicable to his own actions and conduct.

OSHA has defined Radiofrequency and Microwave Radiation safety standards for workers who may enter hazardous RF areas. Regulation Standards 29 CFR § 1910.147 identify a generic Lock Out Tag Out procedure aimed to control the unexpected energization or start up of machines when maintenance or service is being performed.



#### Appendix C - Safety Plan and Procedures

The following items are general safety recommendations that should be administered on a site by site basis as needed by the carrier.

<u>General Maintenance Work</u>: Any maintenance personnel required to work immediately in front of antennas and / or in areas indicated as above 100% of the Occupational MPE limits should coordinate with the wireless operators to disable transmitters during their work activities.

Training and Qualification Verification: All personnel accessing areas indicated as exceeding the General Population MPE limits should have a basic understanding of EME awareness and RF Safety procedures when working around transmitting antennas. Awareness training increases a workers understanding to potential RF exposure scenarios. Awareness can be achieved in a number of ways (e.g. videos, formal classroom lecture or internet based courses).

**Physical Access Control:** Access restrictions to transmitting antennas locations is the primary element in a site safety plan. Examples of access restrictions are as follows:

- Locked door or gate
- Alarmed door
- Locked ladder access
- Restrictive Barrier at antenna (e.g. Chain link with posted RF Sign)

<u>**RF Signage:**</u> Everyone should obey all posted signs at all times. RF signs play an important role in properly warning a worker prior to entering into a potential RF Exposure area.

Assume all antennas are active: Due to the nature of telecommunications transmissions, an antenna transmits intermittently. Always assume an antenna is transmitting. Never stop in front of an antenna. If you have to pass by an antenna, move through as quickly and safely as possible thereby reducing any exposure to a minimum.

<u>Maintain a 3 foot clearance from all antennas</u>: There is a direct correlation between the strength of an EME field and the distance from the transmitting antenna. The further away from an antenna, the lower the corresponding EME field is.

Site RF Emissions Diagram: Section 4 of this report contains an RF Diagram that outlines various theoretical Maximum Permissible Exposure (MPE) areas at the site. The modeling is a worst case scenario assuming a duty cycle of 100% for each transmitting antenna at full power. This analysis is based on one of two access control criteria: General Public criteria means the access to the site is uncontrolled and anyone can gain access. Occupational criteria means the access is restricted and only properly trained individuals can gain access to the antenna locations.



## Appendix D – RF Emissions

The RF Emissions Simulation(s) in this report display theoretical spatially averaged percentage of the Maximum Permissible Exposure for all systems at the site unless otherwise noted. These diagrams use modeling as prescribed in OET Bulletin 65 and assumptions detailed in Appendix E.

The key at the bottom of each RF Emissions Simulation indicates percentages displayed referenced to FCC General Public Maximum Permissible Exposure (MPE) limits. Color coding on the diagram is as follows:

- Areas indicated as Gray are predicted to be below 5% of the MPE limits. Gray represents areas more than 20 times below the most conservative exposure limit.
- Green represents areas are predicted to be between 5% and 100% of the MPE limits. Green areas are accessible to anyone.
- Blue represents areas predicted to exceed the General Public MPE limits but are less than Occupational limits. Blue areas should be accessible only to RF trained workers.
- Yellow represents areas predicted to exceed Occupational MPE limits. Yellow areas should be accessible only to RF trained workers able to assess current exposure levels.
- Red represents areas predicted to have exposure more than 10 times the Occupational MPE limits. Red indicates that the RF levels must be reduced prior to access. An RF Safety Plan is required which outlines how to reduce the RF energy in these areas prior to access.



#### Appendix E - Assumptions and Definitions

#### **General Model Assumptions**

In this site compliance report, it is assumed that all antennas are operating at **full power at all times**. Software modeling was performed for all transmitting antennas located on the site. Sitesafe has further assumed a 100% duty cycle and maximum radiated power.

The modeling is based on recommendations from the FCC's OET-65 bulletin with the following variances per AT&T guidance. Reflection has not been considered in the modeling, i.e. the reflection factor is 1.0. The near / far field boundary has been set to 1.5 times the aperture height of the antenna and modeling beyond that point is the lesser of the near field cylindrical model and the far field model taking into account the gain of the antenna.

The site has been modeled with these assumptions to show the maximum RF energy density. Areas modeled with exposure greater than 100% of the General Public MPE level may not actually occur, but are shown as a prediction that could be realized. Sitesafe believes these areas to be safe for entry by occupationally trained personnel utilizing appropriate personal protective equipment (in most cases, a personal monitor).

#### **Use of Generic Antennas**

For the purposes of this report, the use of "Generic" as an antenna model, or "Unknown" for an operator means the information about a carrier, their FCC license and/or antenna information was not provided and could not be obtained while on site. In the event of unknown information, Sitesafe will use our industry specific knowledge of equipment, antenna models, and transmit power to model the site. If more specific information can be obtained for the unknown measurement criteria, Sitesafe recommends remodeling of the site utilizing the more complete and accurate data. Information about similar facilities is used when the service is identified and associated with a particular antenna. If no information is available regarding the transmitting service associated with an unidentified antenna, using the antenna manufacturer's published data regarding the antenna's physical characteristics makes more conservative assumptions.

Where the frequency is unknown, Sitesafe uses the closest frequency in the antenna's range that corresponds to the highest Maximum Permissible Exposure (MPE), resulting in a conservative analysis.



#### Definitions

5% Rule – The rules adopted by the FCC specify that, in general, at multiple transmitter sites actions necessary to bring the area into compliance with the guidelines are the shared responsibility of all licensees whose transmitters produce field strengths or power density levels at the area in question in excess of 5% of the exposure limits. In other words, any wireless operator that contributes 5% or greater of the MPE limit in an area that is identified to be greater than 100% of the MPE limit is responsible taking corrective actions to bring the site into compliance.

*Compliance* – The determination of whether a site is safe or not with regards to Human Exposure to Radio Frequency Radiation from transmitting antennas.

Decibel (dB) – A unit for measuring power or strength of a signal.

*Duty Cycle* – The percent of pulse duration to the pulse period of a periodic pulse train. Also, may be a measure of the temporal transmission characteristic of an intermittently transmitting RF source such as a paging antenna by dividing average transmission duration by the average period for transmission. A duty cycle of 100% corresponds to continuous operation.

*Effective (or Equivalent) Isotropic Radiated Power (EIRP)* – The product of the power supplied to the antenna and the antenna gain in a given direction relative to an isotropic antenna.

*Effective Radiated Power (ERP)* – In a given direction, the relative gain of a transmitting antenna with respect to the maximum directivity of a half wave dipole multiplied by the net power accepted by the antenna from the connecting transmitter.

*Gain (of an antenna)* – The ratio of the maximum intensity in a given direction to the maximum radiation in the same direction from an isotropic radiator. Gain is a measure of the relative efficiency of a directional antennas as compared to an omni directional antenna.

*General Population/Uncontrolled Environment* – Defined by the FCC, as an area where exposure to RF energy may occur to persons who are **unaware** of the potential for exposure and who have no control of their exposure. General Population is also referenced as General Public.

*Generic Antenna* – For the purposes of this report, the use of "Generic" as an antenna model means the antenna information was not provided and could not be obtained while on site. In the event of unknown information, Sitesafe will use our industry specific knowledge of antenna models to select a worst case scenario antenna to model the site.

*Isotropic Antenna* – An antenna that is completely non-directional. In other words, an antenna that radiates energy equally in all directions.

*Maximum Measurement* – This measurement represents the single largest measurement recorded when performing a spatial average measurement.

*Maximum Permissible Exposure (MPE)* – The maximum levels of RF exposure a person may be exposed to without harmful effect and with acceptable safety factor.

*Occupational/Controlled Environment* – Defined by the FCC, as an area where Radio Frequency Radiation (RFR) exposure may occur to persons who are **aware** of the



potential for exposure as a condition of employment or specific activity and can exercise control over their exposure.

*OET Bulletin 65* – Technical guideline developed by the FCC's Office of Engineering and Technology to determine the impact of Radio Frequency radiation on Humans. The guideline was published in August 1997.

**OSHA (Occupational Safety and Health Administration)** – Under the Occupational Safety and Health Act of 1970, employers are responsible for providing a safe and healthy workplace for their employees. OSHA's role is to promote the safety and health of America's working men and women by setting and enforcing standards; providing training, outreach and education; establishing partnerships; and encouraging continual process improvement in workplace safety and health. For more information, visit www.osha.gov.

*Radio Frequency (RF)* – The frequencies of electromagnetic waves which are used for radio communications. Approximately 3 kHz to 300 GHz.

*Radio Frequency Exposure (RFE)* – The amount of RF power density that a person is or might be exposed to.

Spatial Average Measurement – A technique used to average a minimum of ten (10) measurements taken in a ten (10) second interval from zero (0) to six (6) feet. This measurement is intended to model the average power density an average sized human will be exposed to at a location.

*Transmitter Power Output (TPO)* – The radio frequency output power of a transmitter's final radio frequency stage as measured at the output terminal while connected to a load.



#### Appendix F – References

The following references can be followed for further information about RF Health and Safety.

Sitesafe, LLC. http://www.sitesafe.com FCC Radio Frequency Safety http://www.fcc.gov/encyclopedia/radio-frequency-safety National Council on Radiation Protection and Measurements (NCRP) http://www.ncrponline.org Institute of Electrical and Electronics Engineers, Inc., (IEEE) http://www.ieee.org American National Standards Institute (ANSI) http://www.ansi.org Environmental Protection Agency (EPA) http://www.epa.gov/radtown/wireless-tech.html National Institutes of Health (NIH) http://www.niehs.nih.gov/health/topics/agents/emf/ Occupational Safety and Health Agency (OSHA) http://www.osha.gov/SLTC/radiofrequencyradiation/ International Commission on Non-Ionizing Radiation Protection (ICNIRP) http://www.icnirp.org World Health Organization (WHO) http://www.who.int/peh-emf/en/ National Cancer Institute http://www.cancer.gov/cancertopics/factsheet/Risk/cellphones American Cancer Society (ACS) http://www.cancer.org/docroot/PED/content/PED 1 3X Cellular Phone Towers.asp?sit earea=PED European Commission Scientific Committee on Emerging and Newly Identified Health Risks http://ec.europa.eu/health/ph risk/committees/04 scenihr/docs/scenihr o 022.pdf Fairfax County, Virginia Public School Survey http://www.fcps.edu/fts/safety-security/RFEESurvey/ UK Health Protection Agency Advisory Group on Non-ionising Radiation http://www.hpa.org.uk/webw/HPAweb&HPAwebStandard/HPAweb C/1317133826368 Norwegian Institute of Public Health http://www.fhi.no/dokumenter/545eea7147.pdf



PROJECT:	LTE 2C/3C
SITE NUMBER:	CTL01076
FA NUMBER:	10035052
PTN NUMBER:	2051A0D6QK / 2051A0D6PH
PACE NUMBER:	MRCTB025383 / MRCTB025396
SITE NAME:	WEST HARTFORD - SOUTH MAIN
SITE ADDRESS:	125 SOUTH MAIN STREET

WEST HARTFORD, CT 06107

	PROJECT INFORMATION	SCOPE OF WORK	APPLICABLE BUILDING CODES
<u>SITE_NAME:</u> <u>SITE_NUMBER:</u> <u>SITE_ADDRESS:</u>	WEST HARTFORD – SOUTH MAIN CTL01076 125 SOUTH MAIN STREET WEST HARTFORD, CT 06107	LTE 1900/WCS WILL BE 2C/3C AT THE SITE WITH BRONZE CONFIGURATION. PROPOSED 2C/3C PROJECT SCOPE HEREIN BASED ON RFDS ID # 1833299, VERSION 3.00 LAST UPDATED 11/06/17.	ALL WORK AND MATERIALS SHALL BE PERFORMED AND CURRENT EDITIONS OF THE FOLLOWING CODES AS ADD AUTHORITIES.
FA_NUMBER: <u>PTN_NUMBER:</u> <u>PACE_NUMBER:</u> <u>USID_NUMBER:</u>	10035052 2051A0D6QK / 2051A0D6PH MRCTB025383 / MRCTB025396 59366	<ul> <li>(3) NEW ANTENNAS TO REPLACE (3) EXISTING ANTENNAS</li> <li>(3) NEW RRUS-32 B2 UNITS</li> <li>(3) NEW RRUS-32 UNITS</li> <li>(1) NEW RAYCAP UNIT</li> </ul>	BUILDING CODE:         2012 INTERNATIONAL BUILDING C           2016 CONNECTICUT STATE BUILD           ELECTRICAL CODE:         2014 NATIONAL ELECTRIC CODE
APPLICANT:	AT&T WIRELESS 550 COCHITUATE ROAD SUITE 550 13 AND 14 FRAMINGHAM, MA 01701	<ul> <li>(1) FIBER CABLE AND (2) DC POWER CABLES</li> <li>UPGRADE DUS TO 5216</li> <li>(1) NEW XMU CARD</li> <li>CONTRACTOR SHALL FURNISH ALL MATERIAL WITH THE EXCEPTION OF AT%T SUDDUED MATERIAL</li> </ul>	FACILITY IS UNMANNED AND NOT FOR HUMAN HABI     ADA ACCESS REQUIREMENTS ARE NOT REQUIRED
OWNER:	FRONTIER – THE SOUTHERN NEW ENGLAND TELEPHONE CO 21 WEST AVENUE SPENCERPORT, NY 14559	ALL MATERIAL SHALL DEVISITIALLE MATERIAL WITH THE EACEF HOW OF AFAT SUFFELED WATERIAL.     ALL MATERIAL SHALL BE INSTALLED BY THE CONTRACTOR, UNLESS STATED OTHERWISE.     SITE I OCATION MAP	THIS FACILITY DOES NOT REQUIRE POTABLE WATER      DRAWING INDE
JURISDICTION: <u>COUNTY:</u> <u>SITE COORDINATES FROM</u> LATITUDE: LONGITUDE: <u>GROUND ELEV.:</u> <u>PROPOSED USE:</u> <u>AT&amp;T RF MANAGER:</u> PHONE: EMAIL: <u>PROJECT MANAGER:</u> ADDRESS: CONTACT: EMAIL: SITE ADUISITION:	HARTFORD COUNTY HARTFORD (RFDS) 41.7534439' -72.7444439' 115' TELECOMMUNICATIONS FACILITY DEEPAK RATHORE (860) 965–3068 dr701e@att.com PROJECT CONSULTANTS SMARTLINK 85 RANGEWAY ROAD, SUITE 102 NORTH BILLERICA, MA 01862 EDWARD WEISSMAN (917) 528–1857 Edward.Weissman@smartlinkllc.com	Port of the second seco	T1       TITLE SHEET         SP1       NOTES AND SPECIFICATIONS         SP2       NOTES AND SPECIFICATIONS         A1       COMPOUND PLAN         A2       EQUIPMENT PLAN         A3       ELEVATIONS         A4       ANTENNA PLANS         A5       EQUIPMENT DETAILS         A6       ANTENNA & CABLE CONFIGURATION         A7       CABLE NOTES AND COLOR CODING         A8       GROUNDING DETAILS
ADDRESS: CONTACT: EMGINEER/ARCHITECT: ADDRESS: CONTACT:	SMANTLINK 85 RANGEWAY ROAD, SUITE 102 NORTH BILLERICA, MA 01862 SHARON KEEFE (978) 930–3918 Sharon.Keefe@smartlinkllc.com FULLERTON ENGINEERING 1100 E. WOODFIELD ROAD, SUITE 500 SCHAUMBURG, IL 60173 MILLEN DIMITROV (842) 908–8439	DIRECTIONS SCAN QR CODE FOR LINK TO SITE LOCATION MAP	
EMAIL: <u>CONSTRUCTION:</u> ADDRESS: CONTACT: EMAIL:	MDimitrov@FullertonEngineering.com SMARTLINK 85 RANGEWAY ROAD, SUITE 102 NORTH BILLERICA, MA 01862 MARK DONNELLY (617) 515–2080 mark.donnelly@smartlinkllc.com		NOTE: DRAWING SCALES ARE FOR 11"X17" SHE

	550 COCHITUATE ROAD SUITE 550 13 AND 14 FRAMINGHAM, MA 01701
I	SMARTINK 1362 MELLON ROAD SUITE 140 HANOVER, MD 21076 FULLERTON ENGINEERING DESIGN
	I 100 E. WOODFIELD ROAD, SUITE 500 SCHAUMBURG, ILLINOIS 60173 TEL: 847-908-8400 COA# PEC.0001444 www.FullertonEngineering.com
INSTALLED IN ACCORDANCE WITH THE PTED BY THE LOCAL GOVERNING	REV         DATE         DESCRIPTION         BY           0         11/08/17         90% REVIEW         KC           4         44/04/17         FOR DEPLIY         ND
DDE NG CODE SUPPLEMENT	
FATION. AND WILL NOT PRODUCE ANY SEWAGE EX	PREPARED BY ME OR UNDER MY DIRECT SUPERVISION AND CONTROL, AND TO THE BEST OF MY KNOWLEDGE AND BELIEF COMPLY WITH THE REQUIREMENTS OF ALL APPLICABLE CODES.
	SITE NAME WEST HARTFORD - SOUTH MAIN
	SITE NUMBER: CTL01076
	SITE ADDRESS 125 SOUTH MAIN STREET WEST HARTFORD, CT 06107
811 u DIG	SHEET NAME TITLE SHEET
ETS UNLESS OTHERWISE NOTED	T1

#### GENERAL CONSTRUCTION

- 1. FOR THE PURPOSE OF CONSTRUCTION DRAWINGS, THE FOLLOWING DEFINITIONS SHALL APPLY: CONTRACTOR/CM – SMARTLINK OWNER – AT&T WIRELESS
- 2. ALL SITE WORK SHALL BE COMPLETED AS INDICATED ON THE DRAWINGS AND AT&T PROJECT SPECIFICATIONS.
- GENERAL CONTRACTOR SHALL VISIT THE SITE AND SHALL FAMILIARIZE HIMSELF WITH ALL CONDITIONS AFFECTING THE PROPOSED WORK AND SHALL MAKE PROVISIONS. GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR FAMILIARIZING HIMSELF WITH ALL CONTRACT DOCUMENTS, FIELD CONDITIONS, DIMENSIONS, AND CONFINING THAT THE WORK MAY BE ACCOMPLISHED AS SHOWN PRIOR TO PROCEEDING WITH CONSTRUCTION, ANY DISCREPANCIES SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER PRIOR TO THE COMMENCEMENT OF WORK. 3.
- 4. ALL MATERIALS FURNISHED AND INSTALLED SHALL BE IN STRICT ACCORDANCE WITH ALL APPLICABLE CODES, REGULATIONS, AND ORDINANCES. GENERAL CONTRACTOR SHALL ISSUE ALL APPROPRIATE NOTICES AND COMPLY WITH ALL LAWS, ORDINANCES, RULES, REGULATIONS, AND LAWFUL ORDERS OF ANY PUBLIC AUTHORITY REGARDING THE PERFORMANCE OF WORK.
- ALL WORK CARRIED OUT SHALL COMPLY WITH ALL APPLICABLE MUNICIPAL AND UTILITY COMPANY SPECIFICATIONS AND LOCAL JURISDICTIONAL CODES, ORDINANCES, AND 5. APPLICABLE REGULATIONS.
- UNLESS NOTED OTHERWISE, THE WORK SHALL INCLUDE FURNISHING MATERIALS, EQUIPMENT, APPURTENANCES, AND LABOR NECESSARY TO COMPLETE ALL INSTALLATIONS AS INDICATED ON THE DRAWINGS.
- PLANS ARE NOT TO BE SCALED. THESE PLANS ARE INTENDED TO BE A DIAGRAMMATIC OUTLINE ONLY UNLESS OTHERWISE NOTED. DIMENSIONS SHOWN ARE TO FINISH SURFACES UNLESS OTHERWISE NOTED. SPACING BETWEEN EQUIPMENT IS THE MINIMUM REQUIRED CLEARANCE. THEREFORE, IT IS CRITICAL TO FIELD VERIFY DIMENSIONS, SHOULD THERE BE ANY QUESTIONS REGARDING THE CONTRACT DOCUMENTS, THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING A CLARIFICATION FROM THE ENGINEER PRIOR TO PROCEEDING WITH THE WORK. DETAILS ARE INTENDED TO SHOW DESIGN INTENT. MODIFICATIONS MAY BE REQUIRED TO SUIT JOB DIMENSIONS OR CONDITIONS AND SUCH MODIFICATIONS SHALL BE INCLUDED AS PART OF WORK AND PREPARED BY THE ENGINEER PRIOR TO PROCEEDING WITH WORK.
- THE CONTRACTOR SHALL INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS UNLESS SPECIFICALLY STATED OTHERWISE.
- IF THE SPECIFIED EQUIPMENT CANNOT BE INSTALLED AS SHOWN ON THESE DRAWINGS, THE CONTRACTOR SHALL PROPOSE AN ALTERNATIVE INSTALLATION SPACE FOR APPROVAL BY THE ENGINEER PRIOR TO PROCEEDING.
- 10. GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR THE SAFETY OF WORK AREA, ADJACENT AREAS AND BUILDING OCCUPANTS THAT ARE LIKELY TO BE AFFECTED BY THE WORK UNDER THIS CONTRACT. WORK SHALL CONFIRM TO ALL OSHA REQUIREMENTS AND THE LOCAL JURISDICTION.
- 11. GENERAL CONTRACTOR SHALL COORDINATE WORK AND SCHEDULE WORK ACTIVITIES WITH OTHER DISCIPLINES.
- 12. ERECTION SHALL BE DONE IN A WORKMANLIKE MANNER BY COMPETENT EXPERIENCED WORKMAN IN ACCORDANCE WITH APPLICABLE CODES AND THE BEST ACCEPTED PRACTICE. ALL MEMBERS SHALL BE LAID PLUMB AND TRUE AS INDICATED THE DRAWINGS
- 13. SEAL PENETRATIONS THROUGH FIRE RATED AREAS WITH UL LISTED MATERIALS APPROVED BY LOCAL JURISDICTION. CONTRACTOR SHALL KEEP AREA CLEAN, HAZARD FREE, AND DISPOSE OF ALL DEBRIS.
- 14. WORK PREVIOUSLY COMPLETED IS REPRESENTED BY LIGHT SHADED LINES AND NOTES. THE SCOPE OF WORK FOR THIS PROJECT IS REPRESENTED BY DARK SHADED LINES AND NOTES. CONTRACTOR SHALL NOTIFY THE GENERAL CONTRACTOR OF ANY EXISTING CONDITIONS THAT DEVIATE FROM THE DRAWINGS PRIOR TO BEGINNING CONSTRUCTION. THIS
- 15. CONTRACTOR SHALL PROVIDE WRITTEN NOTICE TO THE CONSTRUCTION MANAGER 48 HOURS PRIOR TO COMMENCEMENT OF WORK.
- 16. THE CONTRACTOR SHALL PROTECT EXISTING IMPROVEMENTS, PAVEMENTS, CURBS, LANDSCAPING AND STRUCTURES. ANY DAMAGED PART SHALL BE REPAIRED AT CONTRACTOR'S EXPENSE TO THE SATISFACTION OF THE OWNER.
- 17. THE CONTRACTOR SHALL CONTACT UTILITY LOCATING SERVICES PRIOR TO THE START OF CONSTRUCTION.
- 18. GENERAL CONTRACTOR SHALL COORDINATE AND MAINTAIN ACCESS FOR ALL TRADES AND CONTRACTORS TO THE SITE AND/OR BUILDING.
- 19. THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR SECURITY OF THE SITE FOR THE DURATION OF CONSTRUCTION UNTIL JOB COMPLETION.

- 20. THE GENERAL CONTRACTOR SHALL MAINTAIN IN GOOD CONDITION ONE COMPLETE SET OF PLANS WITH ALL REVISIONS, ADDENDA, AND CHANGE ORDERS ON THE PREMISES AT ALL TIMES.
- 21. THE GENERAL CONTRACTOR SHALL PROVIDE PORTABLE FIRE EXTINGUISHERS WITH A RATING OF NOT LESS THAN 2-A OT 2-A:10-B:C AND SHALL BE WITHIN 25 FEET OF TRAVEL DISTANCE\_TO\_ALL\_PORTIONS\_OF\_WHERE THE WORK IS BEING COMPLETED DURING CONSTRUCTION
- 22. ALL EXISTING ACTIVE SEWER, WATER, GAS, ELECTRIC, AND OTHER UTILITIES SHALL BE PROTECTED AT ALL TIMES, AND WHERE REQUIRED FOR THE PROPER EXECUTION OF THE WORK, SHALL BE RELOCATED AS DIRECTED BY THE ENGINEER. EXTREME CAUTION SHOULD BE USED BY THE CONTRACTOR WHEN EXCAVATING OR DRILLING PIERS AROUND OR NEAR UTILITIES. CONTRACTOR SHALL PROVIDE SAFETY TRAINING FOR THE WORKING CREW. THIS SHALL INCLUDE BUT NOT PE WHITED TO ALL FAMILY DEPOTECTION BD CONFENSE BUT NOT BE LIMITED TO A) FALL PROTECTION, B) CONFINED SPACE, C) ELECTRICAL SAFETY, AND D) TRENCHING & EXCAVATION.
- 23. ALL EXISTING INACTIVE SEWER, WATER, GAS, ELECTRIC, AND OTHER UTILITIES, WHICH INTERFERE WITH THE EXECUTION OF THE WORK, SHALL BE REMOVED, CAPPED, PLUGGED OR OTHERWISE DISCONNECTED AT POINTS WHICH WILL NOT INTERFERE WITH THE EXECUTION OF THE WORK, AS DIRECTED BY THE RESPONSIBLE ENGINEER, AND SUBJECT TO THE ADDROVAL OF THE OWNER AND (OD LOCAL LETTING) THE APPROVAL OF THE OWNER AND/OR LOCAL UTILITIES.
- 24. THE AREAS OF THE OWNER'S PROPERTY DISTURBED BY THE WORK AND NOT COVERED BY THE TOWER, EQUIPMENT OR DRIVEWAY, SHALL BE GRADED TO A UNIFORM SLOPE, AND STABILIZED TO PREVENT EROSION.
- 25. CONTRACTOR SHALL MINIMIZE DISTURBANCE TO THE EXISTING SITE DURING CONSTRUCTION. EROSION CONTROL MEASURES, IF REQUIRED DURING CONSTRUCTION, SHALL BE IN CONFORMANCE WITH THE FEDERAL AND LOCAL JURISDICTION FOR EROSION AND SEDIMENT CONTROL.
- 26. NO FILL OR EMBANKMENT MATERIAL SHALL BE PLACED ON FROZEN GROUNDING. FROZEN MATERIALS, SNOW OR ICE SHALL NOT BE PLACED IN ANY FILL OR EMBANKMENT.
- 27. THE SUBGRADE SHALL BE BROUGHT TO A SMOOTH UNIFORM GRADE AND COMPACTED TO 95 PERCENT STANDARD PROCTOR DENSITY UNDER PAVEMENT AND STRUCTURES AND 80 PERCENT STANDARD PROCTOR DENSITY IN OPEN SPACE. ALL TRENCHES IN PUBLIC RIGHT OF WAY SHALL BE BACKFILLED WITH FLOWABLE FILL OR OTHER MATERIAL BDFC MALE DEV THE LOCAL HUBSINGTON PRE-APPROVED BY THE LOCAL JURISDICTION.
- 28. ALL NECESSARY RUBBISH, STUMPS, DEBRIS, STICKS, STONES, AND OTHER REFUSE SHALL BE REMOVED FROM THE SITE AND DISPOSED OF IN A LAWFUL MANNER.
- 29. ALL BROCHURES, OPERATING AND MAINTENANCE MANUALS, CATALOGS, SHOP DRAWINGS, AND OTHER DOCUMENTS SHALL BE TURNED OVER TO THE GENERAL CONTRACTOR AT COMPLETION OF CONSTRUCTION AND PRIOR TO PAYMENT.
- 30. CONTRACTOR SHALL SUBMIT A COMPLETE SET OF AS-BUILT REDLINES TO THE GENERAL CONTRACTOR UPON COMPLETION OF PROJECT AND PRIOR TO FINAL PAYMENT.
- 31. CONTRACTOR SHALL LEAVE PREMISES IN A CLEAN CONDITION.
- 32. THE PROPOSED FACILITY WILL BE UNMANNED AND DOES NOT REQUIRE POTABLE WATER OR SEWER SERVICE, AND IS NOT FOR HUMAN HABITAT (NO HANDICAP ACCESS REQUIRED).
- 33. OCCUPANCY IS LIMITED TO PERIODIC MAINTENANCE AND INSPECTION, APPROXIMATELY 2 TIMES PER MONTH, BY AT&T TECHNICIANS.
- 34. NO OUTDOOR STORAGE OR SOLID WASTE CONTAINERS ARE PROPOSED.
- 35. ALL MATERIAL SHALL BE FURNISHED AND WORK SHALL BE PERFORMED IN ACCORDANCE WITH THE LATEST REVISION AT&T MOBILITY GROUNDING STANDARD "TECHNICAL SPECIFICATION FOR CONSTRUCTION OF GSM/GPRS WIRELESS SPECIFICATION FOR CONSTRUCTION OF OWN OR WITCH STES" AND "TECHNICAL SPECIFICATION FOR FACILITY GROUNDING", IN CASE OF A CONFLICT BETWEEN THE CONSTRUCTION SPECIFICATION AND THE DRAWINGS, THE DRAWINGS SHALL GOVERN.
- 36. CONTRACTORS SHALL BE RESPONSIBLE FOR OBTAINING ALL PERMITS AND INSPECTIONS REQUIRED FOR CONSTRUCTION. IF CONTRACTOR CANNOT OBTAIN A PERMIT, THEY MUST NOTIFY THE GENERAL CONTRACTOR IMMEDIATELY.
- 37. CONTRACTOR SHALL REMOVE ALL TRASH AND DEBRIS FROM THE SITE ON A DAILY BASIS.
- 38. INFORMATION SHOWN ON THESE DRAWINGS WAS OBTAINED FROM SITE VISITS AND/OR DRAWINGS PROVIDED BY THE SITE OWNER. CONTRACTORS SHALL NOTIFY THE ENGINEER OF ANY DISCREPANCIES PRIOR TO ORDERING MATERIAL OR PROCEEDING WITH CONSTRUCTION.
- 39. NO WHITE STROBE LIGHTS ARE PERMITTED, LIGHTING IF REQUIRED, WILL MEET FAA STANDARDS AND REQUIREMENTS.
- ANTENNA MOUNTING
- 40. DESIGN AND CONSTRUCTION OF ANTENNA SUPPORTS SHALL CONFORM TO CURRENT ANSI/TIA-222 OR APPLICABLE LOCAL CODES

- 41. ALL STEEL MATERIALS SHALL BE GALVANIZED AFTER FABRICATION IN ACCORDANCE WITH ASTM A123 "ZINC (HOT-DIP GALVANIZED) COATINGS ON IRON AND STEEL PRODUCTS". UNLESS NOTED OTHERWISE.
- 42. ALL BOLTS, ANCHORS AND MISCELLANEOUS HARDWARE SHALL BE GALVANIZED IN ACCORDANCE WITH ASTM A153 "ZINC-COATING (HOT-DIP) ON IRON AND STEEL HARDWARE", UNLESS NOTED OTHERWISE.
- 43. DAMAGED GALVANIZED SURFACES SHALL BE REPAIRED BY COLD GALVANIZING IN ACCORDANCE WITH ASTM A780.
- 44. ALL ANTENNA MOUNTS SHALL BE INSTALLED WITH LOCK NUTS, DOUBLE NUTS AND SHALL BE TORQUED TO MANUFACTURER'S RECOMMENDATIONS
- 45. CONTRACTOR SHALL INSTALL ANTENNA PER MANUFACTURER'S RECOMMENDATION FOR INSTALLATION AND GROUNDING.
- 46. ALL UNUSED PORTS ON ANY ANTENNAS SHALL BE TERMINATED WITH A 50-OHM LOAD TO ENSURE ANTENNAS PERFORM AS DESIGNED.
- 47. PRIOR TO SETTING ANTENNA AZIMUTHS AND DOWNTILTS, ANTENNA CONTRACTOR SHALL CHECK THE ANTENNA MOUNT FOR TIGHTNESS AND ENSURE THAT THEY ARE PLUMB. ANTENNA AZIMUTHS SHALL BE SET FROM TRUE NORTH AND BE ORIENTED WITHIN +/-5% AS DEFINED BY THE RFDS. ANTENNA DOWNTILTS SHALL BE WITHIN +/-0.5% AS DEFINED BY THE RFDS. REFER TO ND-00246.
- 48. JUMPERS FROM THE TMA'S MUST TERMINATE TO OPPOSITE POLARIZATION'S IN EACH SECTOR.
- 49. CONTRACTOR SHALL RECORD THE SERIAL #, SECTOR, AND POSITION OF EACH ACTUATOR INSTALLED AT THE ANTENNAS AND PROVIDE THE INFORMATION TO AT&T.
- 50. TMA'S SHALL BE MOUNTED ON PIPE DIRECTLY BEHIND ANTENNAS AS CLOSE TO ANTENNA AS FEASIBLE IN A VERTICAL POSITION.

#### TORQUE REQUIREMENTS

- 51. ALL RF CONNECTIONS SHALL BE TIGHTENED BY A TORQUE
- 52. ALL RF CONNECTIONS, GROUNDING HARDWARE AND ANTENNA HARDWARE SHALL HAVE A TORQUE MARK INSTALLED IN A CONTINUOUS STRAIGHT LINE FROM BOTH SIDES OF THE CONNECTION.
  - ONNECTION. A. RF CONNECTION BOTH SIDES OF THE CONNECTOR. B. GROUNDING AND ANTENNA HAROWARE ON THE NUT SIDE STARTING FROM THE THREADS TO THE SOLID SURFACE. EXAMPLE OF SOLID SURFACE: GROUND BAR, ANTENNA BRACKET METAL.

#### FIBER & POWER CABLE MOUNTING

- 53. THE FIBER OPTIC TRUNK CABLES SHALL BE INSTALLED INTO CONDUITS, CHANNEL CABLE TRAYS, OR CABLE TRAY, WHEN INSTALLING FIBER OPTIC TRUNK CABLES INTO A CABLE TRAY SYSTEM, THEY SHALL BE INSTALLED INTO AN INTER DUCT AND A PARTITION BARRIER SHALL BE INSTALLED BETWEEN THE 600 VOLT CABLES AND THE INTER DUCT IN ORDER TO SEGREGATE CABLE TYPES. OPTIC FIBER TRUNK CABLES SHALL HAVE APPROVED CABLE RESTRAINTS EVERY (60) SIXTY FEET AND SECURELY FASTENED TO THE CABLE TRAY SYSTEM. NFPA 70 (NEC) ARTICLE 770 RULES SHALL APPLY.
- 54. THE TYPE TC-ER CABLES SHALL BE INSTALLED INTO CONDUITS, CHANNEL CABLE TRAYS, OR CABLE TRAY AND SHALL BE SECURED AT INTERVALS NOT EXCEEDING (6) SIX FEET. AN EXCEPTION; WHERE TYPE TC-ER CABLES ARE NOT SUBJECT TO PHYSICAL DAMAGE, CABLES SHALL BE PERMITTED TO MAKE A TRANSITION BETWEEN CONDUITS, CHANNEL CABLE TRAYS, OR CABLE TRAY WHICH ARE SERVING UTILIZATION EQUIPMENT OR DEVICES, A DISTANCE (6) SIX FEET SHALL NOT BE EXCEEDED WITHOUT CONTINUIOUS SUPPORTING. NEPA 70. (NEC) ARTICLES 336 CONTINUOUS SUPPORTING. NFPA 70 (NEC) ARTICLES 336 AND 392 RULES SHALL APPLY.
- 55. WHEN INSTALLING OPTIC FIBER TRUNK CABLES OR TYPE TC-ER CABLES INTO CONDUITS, NFPA 70 (NEC) ARTICLE 300 RULES SHALL APPLY.

#### COAXIAL CABLE NOTES

- 62. TYPES AND SIZES OF THE ANTENNA CABLE ARE BASED ON ESTIMATED LENGTHS. PRIOR TO
- ORDERING CABLE, CONTRACTOR SHALL VERIFY ACTUAL LENGTH BASED ON CONSTRUCTION LAYOUT AND NOTIFY THE PROJECT MANAGER IF ACTUAL LENGTHS EXCEED ESTIMATED
- 63. CONTRACTOR SHALL VERIFY THE DOWN-TILT OF EACH ANTENNA WITH A DIGITAL LEVEL.
- 64. CONTRACTOR SHALL CONFIRM COAX COLOR CODING PRIOR TO CONSTRUCTION.
- 65. ALL JUMPERS TO THE ANTENNAS FROM THE MAIN TRANSMISSION LINE SHALL BE 1/2" DIA. LDF AND SHALL NOT EXCEED 6'-0".

- DISTANCES NOT TO EXCEED 4'-0" OC.
- ANTENNAS, AND ALL OTHER EQUIPMENT.

- APPLICABLE.

#### GENERAL CABLE AND EQUIPMENT NOTES

- RECOMMENDATIONS.
- DISTRIBUTION/ROUTING.
- 75. IF REQUIRED TO PAINT ANTENNAS AND/OR COAX: A. TEMPERATURE SHALL BE ABOVE 50° F. B. PAINT COLOR MUST BE APPROVED BY BUILDING OWNER/LANDLORD.
  - IS REQUIRED. D. DO NOT PAINT OVER COLOR CODING OR ON EQUIPMENT MODEL NUMBERS
- 76. ALL CABLES SHALL BE GROUNDED WITH COAXIAL CABLE
- HORIZONTAL
- PORT. E. GROUNDING INSIDE THE EQUIPMENT SHELTER AT THE ENTRY PORT.

66. ALL COAXIAL CABLE SHALL BE SECURED TO THE DESIGNED SUPPORT STRUCTURE, IN AN APPROVED MANNER, AT

67. CONTRACTOR SHALL FOLLOW ALL MANUFACTURER'S RECOMMENDATIONS REGARDING BOTH THE INSTALLATION AND GROUNDING OF ALL COAXIAL CABLES, CONNECTORS,

68. CONTRACTOR SHALL GROUND ALL EQUIPMENT. INCLUDING ANTENNAS, RET MOTORS, TMA'S, COAX CABLES, AND RET CONTROL CABLES AS A COMPLETE SYSTEM. GROUNDING SHALL BE EXECUTED BY QUALIFIED WIREMEN IN COMPLIANCE WITH MANUFACTURER'S SPECIFICATION AND RECOMMENDATION.

69. CONTRACTOR SHALL PROVIDE STRAIN-RELIEF AND CABLE SUPPORTS FOR ALL CABLE ASSEMBLIES, COAX CABLES, AND RET CONTROL CABLES. CABLE STRAIN-RELIEFS AND CABLE SUPPORTS SHALL BE APROVED FOR THE PURPOSE. INSTALLATION SHALL BE IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS AND RECOMMENDATIONS.

70. CONTRACTOR TO VERIFY THAT EXISTING COAX HANGERS ARE STACKABLE SNAP IN HANGERS. IF EXISTING HANGERS ARE NOT STACKABLE SNAP IN HANGERS THE CONTRACTOR SHALL REPLACE EXISTING HANGERS WITH NEW SNAP IN HANGERS IF

71. CONTRACTOR SHALL BE RESPONSIBLE TO VERIFY ANTENNA, TMAS, DIPLEXERS, AND COAX CONFIGURATION, MAKE AND MODELS PRIOR TO INSTALLATION.

72. ALL CONNECTIONS FOR HANGERS, SUPPORTS, BRACING, ETC. SHALL BE INSTALLED PER TOWER MANUFACTURER'S

73. CONTRACTOR SHALL REFERENCE THE TOWER STRUCTURAL ANALYSIS/DESIGN DRAWINGS FOR DIRECTIONS ON CABLE

74. ALL OUTDOOR RF CONNECTORS/CONNECTIONS SHALL BE WEATHERPROOFED, EXCEPT THE RET CONNECTORS, USING BUTYL TAPE AFTER INSTALLATION AND FINAL CONNECTIONS ARE MADE. BUTYL TAPE SHALL HAVE A MINIMUM OF ONE-HALF TAPE WIDTH OVERLAP ON EACH TURN AND EACH LAYER SHALL BE WRAPPED THREE TIMES. WEATHERPROOFING SHALL BE SMOOTH WITHOUT BUCKLING. BUTYL BLEEDING IS NOT ALLOWED.

C. FOR REGULATED TOWERS, FAA/FCC APPROVED PAINT

ALL CABLES SHALL BE GROUNDED WITH COACAL CABLE GROUND KITS. FOLLOW THE MANUFACTURER'S RECOMMENDATIONS.
 A. GROUNDING AT THE ANTENNA LEVEL.
 B. GROUNDING AT MID LEVEL, TOWERS WHICH ARE OVER 200'-0", ADDITIONAL CABLE GROUNDING REQUIRED.
 C. GROUNDING AT BASE OF TOWER PRIOR TO TURNING HOPIZONTAL

GROUNDING OUTSIDE THE EQUIPMENT SHELTER AT ENTRY

77. ALL PROPOSED GROUND BAR DOWNLEADS ARE TO BE TERMINATED TO THE EXISTING ADJACENT GROUND BAR DOWNLEADS A MINIMUM DISTANCE OF 4'-0" BELOW GROUND BAR. TERMINATIONS MAY BE EXOTHERMIC OR COMPRESSION.



Beyond This Point you are entering a controlled area where RF emissions may exceed the FCC General Population Exposure Limits. Follow all posted signs and site guidelines	CAUTION Reyond This Point you are entering a controlled area where RF emissions may exceed the FCC Occupational Exposure Limits.	ALERTING SIGN (FOR CELL SITE BATTERIES)			ALERTING_SIGN (FOR_DIESEL_FUEL)			
for working in a RF environment.	for working in a RF environment.				GENER	AL SIGNAGE	GUIDELINES	6
ALERTIN	IG SIGNS	S	STRUCTURE TYPE	INFO SIGN #1	INFO SIGN #2	INFO SIGN #3	INFO SIGN #4	STRIPING
			TOWERS					
WARNING! DANGER DO NOT TOUCH TOWER!	ROPERTY OF AT&T		MONOPOLE/MONOPINE/MONOPALM	ENTRANCE GATES, SHELTER DOORS OR ON THE OUTDOOR CABINETS	CLIMBING SIDE OF THE TOWER	ON BACKSIDE OF ANTENNAS	ENTRANCE GATES, SHELTER DOORS OR ON THE OUTDOOR CABINETS	
SERIOUS "RF" BURN HAZARD! A MAINTAIN AN ADEQUATE CLEARANCE BETWEEN TOWER	UTHORIZED ERSONNEL ONLY	B	SEC TOWERS/TOWERS WITH HIGH VOLTAGE	ENTRANCE GATES, SHELTER DOORS OR ON THE OUTDOOR CABINETS	CLIMBING SIDE OF THE TOWER	ON BACKSIDE OF ANTENNAS	ENTRANCE GATES, SHELTER DOORS OR ON THE OUTDOOR CABINETS	
SUPPORTS AND GUY WIRES FAILURE TO ORFY ALL PORTED SIGNS AND STTE GUIDELINSE FOW WORKING IN A RADIO PREQUESCY EXVIRONMENT COULD RESULT IN SERIOLS INJURY. CONTACT CHREME THAP RELED (S) 4-1992 FOR CONTROLLED ENVIRONMENTS. C961992 FOR CONTROLLED ENVIRONMENTS.		C K	LIGHT POLES/FLAG POLES	ENTRANCE GATES, SHELTER DOORS OR ON THE OUTDOOR CABINETS	ON THE POLE, NO LESS THAN 3FT BELOW THE ANTENNA AND LESS THAN 9FT ABOVE GROLIND	ON BACKSIDE OF ANTENNAS	ENTRANCE GATES, SHELTER DOORS OR ON THE OUTDOOR CABINETS	
• e atst	IN CASE OF EMERGENCY, OR PRIOR TO PERFORMING MAINTENANCE ON THIS SITE, CALL 800-638-2822 AND REFERENCE CELL SITE NUMBER	3	UTILITY WOOD POLES (JPA)	ENTRANCE GATES, SHELTER DOORS OR ON THE OUTDOOR CABINETS	ON THE POLE, NO LESS THAN 3FT BELOW THE ANTENNA AND LESS THAN 9FT ABOVE GROUND	ON BACKSIDE OF ANTENNAS	ENTRANCE GATES, SHELTER DOORS OR ON THE OUTDOOR CABINETS	
ALERTING SIGN	INFO SIGN #4	F E	MICROCELLS MOUNTED ON NON-JPA POLES	ENTRANCE GATES, SHELTER DOORS OR ON THE OUTDOOR CABINETS	ON THE POLE, NO LESS THAN 3FT BELOW THE ANTENNA AND LESS THAN 9FT ABOVE	ON BACKSIDE OF ANTENNAS	ENTRANCE GATES, SHELTER DOORS OR ON THE OUTDOOR CABINETS	
			TOWERS		GROOND			
			AT ALL ACCESS POINTS TO THE ROOF	x			х	
			ON ANTENNAS	x		х	х	
			CONCEALED ANTENNAS	X	×		X	
			THE BUILDING	×	×		×	
			ANTENNAS ON SUPPORT STRUCTURE	×	×		×	
AT&T operates telecommunications antennas at this location. Remain at		M	ROUFVIEW GRAPH		ADJACENT TO FACH			
least 3 feet away from any antenna and obey all posted signs. Contact the owner(s) of the antenna(s) before working closer than 3 feet from the antenna			ANTENNA	×	ANTENNA		× *	DIAGONAL YELLOW
Contact AT&T at prior to performing any maintenance or repairs near AT&T antennas. This is Site#			RADIATION AREA IS BEYOND 3FT FROM ANTENNA	×	ADJACENT TO EACH		×	STRIPING AS TO ROOFVIEW GRAPH
Contact the management office if this door/hatch/gate is found unlocked.	ACTIVE ANTENNAS ARE MOUNTED		CHURCH STEEPLES	ACCESS TO STEEPLE	ANTENNAS IF ANTENNAS ARE CONCEALED	ON BACKSIDE OF ANTENNAS	ACCESS TO STEEPLE	
INFORMACION En esta propiedad se ubican antenas de telecomunicationes operadas por ATB.T.	BEHIND THIS PANEL     ON THIS STRUCTURE     STAV DACK A MINITUME		WATER STATIONS	ACCESS TO LADDER	ADJACENT TO ANTENNAS IF ANTENNAS ARE CONCEALED	ON BACKSIDE OF ANTENNAS	ACCESS TO LADDER	
but one progression assumma nanousos esperimento pre A (81).     Foror manterior na distancia de norme dos 2 gios visioses.     Comuniqueste con el completarios o los propietarios de las antensa attes de     trabajar o caminar a una distancia de nanona.     Comuniqueste con ATRTintes de realizar cualquier mantenimiento o     reparaciones cerce de la norma de ATRT:     Esta es la estación o base numero      Foror municane con la oficina de la administración del edificio si esta puerta o		N A	NOTES FOR ROOFTOP SITES: 1. EITHER NOTICE OR CAUTION SIGNS SECTOR	NEED TO BE POSTED	) AT EACH SECTOR A	S CLOSE AS POSSIBL	E TO: THE OUTER ED	GE OF THE STRIPED
ecomposerta se encuentra sin candido.	This is ATRCT sites	🥽 ətat	<ol> <li>IF ROOFVIEWS SHOWS: ONLY BLUE</li> <li>SHOULD THE REQUIRED STRIPING A MODIFY THE STRIPING AREA, PRIOR TO</li> </ol>	= NOTICE SIGN, BLU REAS INTERFERE WITH STARTING THE WORH	IE AND YELLOW = CA H ANY STRUCTURE OF <.	UTION SIGN, ONLY YE R EQUIPMENT (A/C, V	ELLOW = CAUTION SIC (ENTS, ROOF HATCH,	IN TO BE INSTALLED
INFO SIGN #1	INFO SIGN #2	INFO SIGN #3			c		INES CHART	
		<u> </u>			<u></u>	ISTAGE GUIDEI	LINES CHART	

4		550 COCHITUATE ROAD SUITE 550 13 AND 14 FRAMINGHAM, MA 01701						
ALERTING SIGN		Smartlink 1362 MELLON ROAD SUITE 140						
(FOR PROPANE)		HANOVER, MD 21076						
		ENGINEERING DESIGN						
NOTICE SIGN	CAUTION SIGN	I 100 E. WOODFIELD ROAD, SUITE 500 SCHAUMBURG, ILLINOIS 60173 TEL: 847-908-8400 COA# PEC.0001444 www.FullertonEngineering.com						
	AT THE HEIGHT OF THE FIRST CLIMBING STEP, MIN 9 FT ABOVE GROUND	REV         DATE         DESCRIPTION         BY           0         11/08/17         90%         REVIEW         KC           1         11/21/17         FOR         PERMIT         MD						
IF GP MAX VALUE C LEVEL IS: 0-99%; NO CAUTION SIGN AT NO I ANTENNA AND 9F NOTICE OR CAUTION S 9FT ABOVE GROU EXPOSURE EXCEEDS S PUBLIC EXPOSURE A ABOVE GROUND OR AT OF ADJACEN	OF MPE AT ANTENNA TICE SIGN; OVER 99%: LESS THAN 3FT BELOW T ABOVE GROUND IGN AT NO LESS THAN ND: ONLY IF THE 90% OF THE GENERAL T EXPOSURE AT 6FT OUTSIDE OF SURFACE IT BUILDING	I HEREBY CERTIFY THAT THESE DRAWINGS WERE PREPARED BY ME OR UNDER MY DIRECT SUPERVISION AND CONTROL, AND TO THE BEST OF MY KNOWLEDGE AND BELIEF COMPLY WITH THE REQUIREMENTS OF ALL APPLICABLE CODES. BELIEF CONNECTION BELIEF CONNECTION BELIEF CONNECTION SITE NAME WEST HARTFORD - SOUTH MAIN						
EITHER NOTICE OR CAU ROOFVIEW RESULTS) A	JTION SIGN (BASED ON AT ANTENNA /BARRIER	SITE NUMBER: CTL01076						
	CAUTION SIGN AT THE ANTENNAS	SITE ADDRESS						
	CAUTION SIGN BESIDE INFO SIGN #1, MIN. 9FT ABOVE GROUND	125 SOUTH MAIN STREET WEST HARTFORD, CT 06107						
OFF AREA OR THE OUTE ) INNAS, DISHES, ETC.). PL	ER ANTENNAS OF THE EASE NOTIFY AT&T TO	SHEET NAME NOTES AND SPECIFICATIONS SHEET NUMBER						
		SP2						





EQUIPMENT PLAN







- (6) EXISTING AT&T ANTENNAS
- (6) EXISTING TMA UNITS ON
- (1) EXISTING RAYCAP
- ON EXISTING MONOPOLE TO REMAIN





			FII SUPPLI	NAL ANTEN ED BY AT&	NA CONFIGURATION ANE T WIRELESS, FROM RF C	) CABLE ONFIG. I	SCHEDUI DATED (11	LE 1/06/17)													
SECTOR	ANTENNA	ANTENNA	ANTENNA	ANTENNA				CABLE FEEDE	R	RAYCAP											
SECTOR	NUMBER	& TYPE	MODEL NUMBER	VENDOR	IMA/ RKO UNII	AZIMUTH	GROUND	TYPE	LENGTH	UNIT											
	Δ-1	(E)	7770	POWERWAVE	(2) EXISTING TMA LINIT	144°	107'-0"	7/8"ø LDF5-50A	200'-0"												
		ANTENNA	,,,,,,,				107 -0	7/8"ø LDF5-50A	200'-0"												
	A-2	(E)	AM-X-CD-16-65-	KMW	(1) EXISTING RRUS-11 UNIT	25°	107'-0"	(1) EXISTING FIBER CABLE	200'-0"												
HP		ANTENNA	00T-RET			20	107 0	(2) EXISTING DC POWER CABLES	200'-0"												
ALF	A-3	_	-	_	-	_	_	-													
	A-4	(N) LTE2C/3C ANTENNA	QS66512-2	QUINTEL	(1) NEW RRUS-32 B2 UNIT (1) NEW RRUS-32 UNIT	25°	107'-0"	SEE ANTENNA B-4 FOR CABLE TYPE AND LENGTH													
	R_1	B-1 (E) UMTS 7770 POWERWAVE (2) EXISTIN		(2) EXISTING TMA LINIT	267°	107' 0"	7/8"ø LDF5-50A	200'-0"	<b>E</b>												
	В-1		(Z) EXISTING TMA ONIT	207	107 -0	7/8"ø LDF5-50A	200'-0"	N N N N													
AT	B-2	(E) LTE1C ANTENNA	AM-X-CD-16-65- OOT-RET	KMW	(1) EXISTING RRUS-11 UNIT	144°	107'-0"	SEE ANTENNA A–2 FOR CABLE TYPE AND LENGTH		-60-18-8											
BE	В-3	_	_	_	_	-	-	_		DC6-48- DC6-48-											
		(N)	0566512 2	0566512 2	0566512 2	0566512 2	0566512-2	0566512-2	0566512-2	0566512 2	0566512 2	0566512-2	0566512-2		(1) NEW RRUS-32 B2 UNIT	(1) NEW RRUS-32 B2 UNIT	1 4 4 9	107' 0"	(1) NEW FIBER CABLE	200'-0"	(E) (E)
	D-4	ANTENNA	Q300312-2	QUINTEL	(1) NEW RRUS-32 UNIT	144	107 -0	(2) NEW DC POWER CABLES	200'-0"	55											
	C-1	(E)	7770	POWERWAVE	(2) EXISTING TMA LINIT	25°	107'-0"	7/8"ø LDF5-50A	200'-0"												
		ANTENNA	,,,,,,	1 OWERWARE		20	107 0	7/8"ø LDF5-50A	200'-0"												
AMA	C-2	(E) LTE1C ANTENNA	AM-X-CD-16-65- OOT-RET	KMW	(1) EXISTING RRUS-11 UNIT	267°	107'-0"	SEE ANTENNA A– CABLE TYPE AND	2 FOR LENGTH												
GAN	C-3	_	_	-	_	-	_	_													
	C-4	(N) LTE2C/3C ANTENNA	QS66512-2	QUINTEL	(1) NEW RRUS-32 B2 UNIT (1) NEW RRUS-32 UNIT	267°	107'-0"	'-0" SEE ANTENNA B-4 FOR CABLE TYPE AND LENGTH													



1.	CONTRACTOR IS TO REFER TO AT&T'S MOST CURRENT RADIO FREQUENCY DATA SHEET (RFDS) PRICONSTRUCTION.	IOR TO		SECTC	IR ANTENNA
2.	THE SIZE, HEIGHT, AND DIRECTION OF THE ANTENNAS SHALL BE ADJUSTED TO ACHIEVE THE AZIM LIMIT SHADOWING AND TO MEET THE SYSTEM REQUIREMENTS.	UTHS SPECIFIED AND			
3.	CONTRACTOR SHALL VERIFY THE HEIGHT OF THE ANTENNA WITH THE AT&T WIRELESS PROJECT MA	NAGER.			
4.	VERIFY TYPE AND SIZE OF TOWER LEG PRIOR TO ORDERING ANY ANTENNA MOUNT.				UMPER CABLE (TYP.)
5.	UNLESS NOTED OTHERWISE THE CONTRACTOR MUST PROVIDE ALL MATERIAL NECESSARY.		(		· · ·
6.	ANTENNA AZIMUTHS ARE DEGREES OFF OF TRUE NORTH, BEARING CLOCKWISE, IN WHICH ANTENNA ALL ANTENNAS (AND SUPPORTING STRUCTURES AS PRACTICAL) SHALL BE ACCURATELY ORIENTED IN DIRECTION.	A FACE IS DIRECTED. IN THE SPECIFIED			
7.	CONTRACTOR SHALL VERIFY ALL RF INFORMATION PRIOR TO CONSTRUCTION.				
8.	SWEEP TEST SHALL BE PERFORMED BY GENERAL CONTRACTOR AND SUBMITTED TO AT&T WIRELESS SPECIALIST. TEST SHALL BE PERFORMED PER AT&T WIRELESS STANDARDS.	S CONSTRUCTION			
9.	CABLE LENGTHS WERE DETERMINED BASED ON THE DESIGN DRAWING. CONTRACTOR TO VERIFY ACT DURING PRE-CONSTRUCTION WALK.	TUAL LENGTH		JUMPE	R CABLE WHERE REQUIR
10.	CONTRACTOR TO USE ROSENBERGER FIBER LINE HANGER COMPONENTS (OR ENGINEER APPROVED	EQUAL).			
					ND KIT (TYP.)
ANTENN	A AND CABLING NOTES	SCALE: N.T.S. 1			
			(	2) 4	
	RF. DC. & COAX CABLE MARKING LOCATIONS TABLE				COAX, FIBER OR DC CAB
	1       EACH TOP-JUMPER SHALL BE COLOR CODED WITH (1) SET OF 3" WIDE BANDS.				
	2 EACH MAIN COAX SHALL BE COLOR CODED WITH (1) SET OF 3" WIDE BANDS NEAR THE TOP-JUMPER CONNECTION AND WITH (1) SET OF 3/4" WIDE COLOR			GROUN AND A	ID AT THE MIDPOINT OF S REQUIRED BY SCOPE
	Gamma Source       Gamma Source <td< td=""><td></td><td></td><td></td><td></td></td<>				
	4 ALL BOTTOM JUMPERS SHALL BE COLOR CODED WITH (1) SET OF 3/4" WIDE BANDS ON EACH END OF THE BOTTOM JUMPER.				TO EXTERIOR ENTRY P
	5 ALL BOTTOM JUMPERS SHALL BE COLOR CODED WITH (1) SET OF 3/4" WIDE BANDS ON EACH END OF THE BOTTOM JUMPER.				IDING BAR
		SCALE: N.T.S. 2			DE SHELTER
		-		INSIDE	. SHELIER
			(	3)	
1.	THE ANTENNA SYSTEM COAX SHALL BE LABELED WITH VINYL TAPE.				
2.	VIOLET. THESE TAPES MUST BE 3/4" WIDE & UV RESISTANT SUCH AS SCOTCH 35 VINYL ELECTRI TAPE AND SHOULD BE READILY AVAILABLE TO THE ELECTRICIAN OR CONTRACTOR ON SITE.	ICAL COLOR CODING			E SUPPRESSOR (TYP.)
3.	USING COLOR BANDS ON THE CABLES, MARK ALL RF CABLE BY SECTOR AND CABLE NUMBER AS COLOR CHART".	SHOWN ON "CABLE			· _ · · · · · · · · · · · · · · · · · ·
4.	WHEN AN EXISTING COAXIAL LINE THAT IS INTENDED TO BE A SHARED LINE BETWEEN TECHNOLOG ENCOUNTERED. THE CONTRACTOR SHALL REMOVE THE EXISTING COLOR CODING SCHEME AND REPI	IES IS LACE IT WITH THE			(ER AND/OR BIAS-T WH
	COLOR CODING STANDARD. IN THE ABSENCE OF AN EXISTING COLOR CODING AND TAGGING SCHEM INSTALLING PROPOSED COAXIAL CABLES, THIS GUIDELINE SHALL BE IMPLEMENTED AT THAT SITE RI	ME, OR WHEN EGARDLESS OF			
	TECHNOLOGY.				
5.	ALL COLOR CODE TAPE SHALL BE $3M-35$ and shall be installed using a minimum of (3) to tape and shall be neatly trimmed and smoothed out so as to avoid unraveling.	HREE WRAPS OF			VI USIVII EIX UADLE (ITF.)
6.	ALL COLOR BANDS INSTALLED AT THE TOP OF THE TOWER SHALL BE A MINIMUM OF $3$ " WIDE, AN MINIMUM OF $3/4$ " OF SPACE BETWEEN EACH COLOR.	ID SHALL HAVE A	(	5	
7.	ALL COLOR CODES SHALL BE INSTALLED SO AS TO ALIGN NEATLY WITH ONE ANOTHER FROM SIDE	E-TO-SIDE.			
8.	IF EXISTING CABLES AT THE SITE ALREADY HAVE A COLOR CODING SCHEME AND THEY ARE NOT II REUSED OR SHARED WITH THE NEW TECHNOLOGY. THE EXISTING COLOR CODING SCHEME SHALL F	NTENDED TO BE REMAIN UNTOUCHED.			
				EQUIPMENT	
	ARKING NOTES	SCALE: N.T.S. 3			

NG NOTES	SCALE: N.T.S.	
----------	---------------	--





