

STATE OF CONNECTICUT
CONNECTICUT SITING COUNCIL

IN RE: :
: :
A PETITION OF CELLCO PARTNERSHIP : SUB-PETITION NO. 1133
D/B/A VERIZON WIRELESS FOR : 541 BROADBRIDGE ROAD
MODIFICATIONS TO AN EXISTING : BRIDGEPORT, CT
WIRELESS TELECOMMUNICATIONS :
FACILITY AT 541 BROADBRIDGE ROAD :
IN BRIDGEPORT, CONNECTICUT : FEBRUARY 24, 2022

SUB-PETITION FOR DECLARATORY RULING:
ELIGIBLE FACILITIES REQUEST FOR MODIFICATIONS
THAT WILL NOT SUBSTANTIALLY CHANGE THE
PHYSICAL DIMENSIONS OF AN EXISTING BASE STATION

I. Introduction

Pursuant to Section 6409(a) of the Middle Class Tax Relief and Job Creation Act of 2012, codified at 47 U.S.C. § 1455(a) (“Section 6409(a)”) and the October 21, 2014 Report and Order (FCC-14-153) issued by the Federal Communications Commission (“FCC”) (the “FCC Order”), Cellco Partnership d/b/a Verizon Wireless (“Cellco”) hereby petitions the Connecticut Siting Council (the “Council”) for a declaratory ruling (“Sub-Petition”) that the installation of replacement antennas and related telecommunications equipment at the existing wireless telecommunications base station at 541 Broadbridge Road in Bridgeport, Connecticut (the “Property”) constitutes an Eligible Facilities Request (“EFR”) under the FCC Order. Cellco has designated this site as its “Bridgeport NE Facility”.

II. Factual Background

On August 31, 2017, the Council approved Cellco’s application for a Certificate of Environmental Compatibility and Public Need for the construction, maintenance and operation of a wireless telecommunications facility at the Property (Docket No 472). The approved facility

consists of a 100-foot flagpole tower within a fenced compound area. All antennas are located within an RF transparent screening shroud 36-inches in diameter. Equipment associated with the existing antennas is located on the ground adjacent to the flagpole tower.

III. Cellco's Proposed Facility Modifications

Cellco is licensed to provide wireless telecommunications services in the 700 MHz, 800 MHz, 1900 MHz, 2100 MHz and 3000 MHz frequency ranges in Bridgeport and throughout the State of Connecticut. Cellco intends to remove its six (6) existing antennas and install three (3) model NNH4-65B-R6 antennas at the 92-foot level and three (3) model MX08FIT265-01 antennas at the 82-foot level on the tower. Cellco will also install nine (9) remote radio heads ("RRHs") between the two levels of antennas. To accommodate Cellco's new antennas/RRHs the existing antenna screening shroud will need to be replaced with a larger (48" diameter) shroud. There will be no changes to Cellco's ground equipment.

Project Plans and Specifications for Cellco's antennas and RRHs for the Bridgeport NE Facility modifications are included in Attachment 1. According to the attached Structural Analysis ("SA") and Mount Analysis ("MA"), the existing tower, tower foundation, existing and new antenna mounts can support Cellco's proposed modifications. No modifications to Cellco's existing antenna mounts are required as part of this facility modification. The attached SA therefore, does not reference the MA provided. Copies of the SA and MA are included in Attachment 2.

IV. Discussion

A. The Proposed Modification Will Not Cause a Substantial Change to the Physical Dimensions of the Existing Base Station

Section 6409(a) provides, in relevant part, that "a State or local government may not deny, and shall approve, any eligible facilities request for a modification of an existing wireless

tower or base station that does not substantially change the physical dimensions of such tower or base station.” Pursuant to the FCC Order, the proposed modification does not substantially change the physical dimensions of the base station if the following criteria are satisfied.

1. *The proposed modified facility will not increase the height of the tower by more than ten (10) percent of the height.* Cellco does not intend to increase the height of the existing flagpole tower. Cellco’s antennas will be located at the same 92-foot and 82-foot levels within the existing 100-foot flagpole tower.

2. *The proposed facility modification will not protrude from the edge of the structure more than six (6) feet.* Cellco’s antennas and RRHs will be located inside the existing flagpole tower, therefore, will not protrude more than six (6) feet from the face of the tower.

3. *The proposed facility does not involve installation of more than the standard number of new equipment cabinets for the technology involved, but not to exceed four cabinets.* No changes in ground equipment are planned as part of these facility modifications.

4. *The proposed facility does not entail any excavation or deployment outside the current site of the base station.* Cellco’s proposed facility modifications will remain within the limits of the Property and the existing fenced compound.

5. *The proposed facility does not defeat the existing concealment elements of the base station.* The existing facility consists of a flagpole tower with stealth screening elements. To accommodate Cellco’s new antennas and RRHs, the flagpole antenna shroud will increase from 36-inch diameter to 48-inch diameter. All antennas will however remain concealed.

6. *The proposed facility complies with conditions associated with the prior approval of construction or modification of the base station.* Cellco’s proposed facility

modifications are consistent with the Siting Council's approval in Docket No. 472.

B. FCC Compliance

Included in Attachment 3 is a cumulative power density calculation table for Cellco's proposed modifications confirming that the facility will operate within the FCC safety standards for radio frequency emissions.

C. Notice to the City, Property Owner and Abutting Landowners

On February 24, 2022, a copy of this Sub-Petition was sent to Bridgeport's Mayor, Joseph Ganim and Dennis Buckley, Bridgeport's Zoning Administrator; and Beardsley Plaza Limited, the owner of the Property. Copies of the letters sent to Mayor Ganim, Dennis Buckley, and Beardsley Plaza Limited are included in Attachment 4. A copy of this Sub-Petition was also sent to the owners of land that abut the Property. A sample abutter's letter and the list of those abutting landowners who were sent notice and a copy of this filing is included in Attachment 5.

V. Conclusion

Based on the information provided above, Cellco respectfully submits that the proposed modification of the existing base station at the Property constitutes an "eligible facilities request" under Section 6409(a) and the FCC Order.


Respectfully submitted,

CELLCO PARTNERSHIP d/b/a VERIZON
WIRELESS

By 

Kenneth C. Baldwin, Esq.
Robinson & Cole LLP
280 Trumbull Street
Hartford, CT 06103-3597
(860) 275-8200
Its Attorneys

ATTACHMENT 1




PLUMBING DIAGRAM NOTES:

1. PORTS 1, 2, 3 & 4 ARE FOR LOW BAND (698-886 MHz).
2. PORTS 5, 6, 7, 8, 9, 10, 11 & 12 ARE FOR HIGH BAND (1685-2380 MHz).
3. SMART BIAS TEE (SBT) IS THROUGH ANTENNA PORTS 1 & 4 FOR LOW BAND AND 5, 7, 10 & 12 FOR HIGH BAND.
4. AISG CABLE IS ONLY NEEDED WHEN DRAWN IN THE DIAGRAMS BELOW. IF IT IS NOT DRAWN THEN SBT IS ENOUGH TO CONTROL ALL RET MOTORS.
5. NOT ALL SBT PORTS ARE NEEDED TO CONTROL RET, ONLY GREEN PORT CONNECTION TO GREEN PORT WILL CONTROL RET.

RET DC SIGNAL PASS FOR RET (PORT THAT WILL CONTROL RET)

PLUMBING DIAGRAM COMMENTS:

- A. DIAGRAMS SHOW ANTENNA PORT CONFIGURATIONS AS VIEWED FROM STANDING BEHIND THE ANTENNAS.
- B. ANTENNAS WILL BE INSTALLED IN THAT ORDER FROM LEFT TO RIGHT.
- C. CAP AND WEATHERPROOF UNUSED ANTENNA PORTS.
- D. ALL PLUMBING DIAGRAM COLORS ARE IRRELEVANT EXCEPT FOR AISG AND HYBRIFLEX CABLE. (FOR THE COAX COLORS, FOLLOW COAX COLORS GUIDE ABOVE)



NOTES:

1. INFORMATION SHOWN HEREIN IS FOR USE BY VERIZON WIRELESS EQUIPMENT OPERATIONS.
2. THIS B.O.M. DRAWING IS BASED ON FACILITY UPGRADE DESIGN DRAWINGS PREPARED BY CENTEK ENGINEERING (REV.0 DATED: 02/03/2022), & VERIZON WIRELESS RF ANTENNA EQUIPMENT RECOMMENDATION (DATED 11/19/2021).

BILL OF MATERIALS		
TECHNOLOGY	QUANTITY	ANTENNA
LTE 700		
LTE 850	3	COMMSCOPE ANTENNA MODEL: NNH4-65B-R6
LTE PCS 1900		
LTE AWS 2100		
5G	3	JMA ANTENNA MODEL: MX08FIT265-01

CABLES	QUANTITY	LENGTH EA	COMMENTS
HYBRID CABLE	1	±110 FT EA	6X12 HYBRID CABLE

RADIOS	QUANTITY	COMMENTS
LTE 700		
LTE 850 5G	3	SAMSUNG: B5/B13 RRH ORAN (RF4440d-13A)
LTE PCS 1900		
LTE AWS 2100	3	SAMSUNG: B2/B66A RRH ORAN (RF4439d-25A)
5G	3	SAMSUNG MODEL: RT-8808-77A

DIPLEXERS	QUANTITY	COMMENTS
QUADRUPLIFIER	12	CBC61923T-DS-43

OVP BOXES	QUANTITY	COMMENTS
OVP	1	OVP-6

PROFESSIONAL ENGINEER SEAL

verizon

CENTEK ENGINEERING
 2031 486-0390
 2031 486-8807 Fax
 632 North Branford Road
 Branford, CT 06405
 www.CentekEng.com


Cellco Partnership d/b/a Verizon Wireless
BRIDGEPORT NE CT
 541 BROADBRIDGE RD
 BRIDGEPORT, CT 06610

DATE: 11/18/21
 SCALE: AS NOTED
 JOB NO. 21007.69

RF BILL OF MATERIALS

B-1

Sheet No. 3 of 7




DATE:	11/16/21
SCALE:	AS NOTED
JOB NO.:	21007.69
PARTIAL SITE PLAN AND ELEVATION	
C-1	
Sheet No. 4 of 7	


Cellco Partnership d/b/a Verizon Wireless BRIDGEPORT NE CT 541 BROADBRIDGE RD BRIDGEPORT, CT 06610	PROFESSIONAL ENGINEER SEAL CENTEK ENGINEERING 2031 AVE 2500 2031 AVE 2500 F04 A2-2 North Branford Road Branford, CT 06405 www.CentekEng.com

REV.	DATE	BY	CHK'D BY	DESCRIPTION
1	11/16/21	DMD	ANC	CONSTRUCTION DRAWINGS - ISSUED FOR CONSTRUCTION
2	11/22/21	DMD	ANC	CONSTRUCTION DRAWINGS - REVISED FOR PERMITS DATED 11/19/2021
3	11/22/21	DMD	ANC	CONSTRUCTION DRAWINGS - ISSUED FOR PERMITS
4	11/22/21	DMD	ANC	CONSTRUCTION DRAWINGS - ISSUED FOR PERMITS

EXISTING ANTENNA CONFIGURATIONS




1 EXISTING SECTOR CONFIGURATION PLAN
SCALE: 3/4" = 1'-0"
82' + 92' ELEVATION



2 EXISTING SECTOR CONFIGURATION ELEVATION
SCALE: 3/8" = 1'-0"


ANTENNA MOUNT ANALYSIS REFERENCE NOTE

REFER TO PASSING VERIZON WIRELESS MOUNT ANALYSIS REPORT PREPARED BY CENTEK ENGINEERING, DATED 01/12/22 FOR ADDITIONAL INFORMATION. CENTEK PROJECT NUMBER 21007.09.




2A PROPOSED SECTOR CONFIGURATION ELEVATION
SCALE: 3/8" = 1'-0"


PROPOSED ANTENNA CONFIGURATIONS



3 PROPOSED SECTOR CONFIGURATION SECTIONS
SCALE: 3/4" = 1'-0"
82' ELEVATION 92' ELEVATION



4 ANTENNA REPLACEMENT MOUNT KIT DETAIL
SCALE: 1/2" = 1'
92' ELEVATION



5 PROPOSED REPLACEMENT ANTENNA MOUNT
SCALE: 1-1/2" = 1'-0"
82' ELEVATION

PROFESSIONAL ENGINEER SEAL

verizon

CENTEK ENGINEERING
Consistent Solutions™
2031 465-0090
432 North Branford Road
Branford, CT 06405
www.CentekEng.com

Cellco Partnership d/b/a Verizon Wireless
BRIDGEPORT NE CT
541 BROADBRIDGE RD
BRIDGEPORT, CT 06610

DATE: 11/18/21
SCALE: AS NOTED
JOB NO: 21007.09

ANTENNA SECTOR CONFIGURATION DETAILS

C-2
Sheet No. 5 of 7



DIPLEXER			
EQUIPMENT	DESCRIPTION	DIMENSIONS	WEIGHT
MAKE: COMMSCOPE MODEL: CBC61823T-DS-43	DIPLEXER 700MHz/850MHz/1900MHz	6.9"H x 7.8"W x 4.6"D	14.3 LBS. (W/MNTG HDWR)

NOTES:
1. CONTRACTOR TO COORDINATE FINAL EQUIPMENT MODEL SELECTION WITH VERIZON WIRELESS CONSTRUCTION MANAGER PRIOR TO ORDERING.

1 DIPLEXER DETAIL
C-3 NOT TO SCALE



ELEVATION

NH4-858-RE (BOTTOM VIEW)

12-PORT SECTOR ANTENNA		
EQUIPMENT	DIMENSIONS	WEIGHT
MAKE: COMMSCOPE MODEL: NH4-858-RE	72.0"L x 19.6"W x 7.8"D	83.1 LBS.

2 ANTENNA DETAIL
C-3 NOT TO SCALE



ELEVATION

MX08FT265-01 (BOTTOM VIEW)

8-PORT SECTOR ANTENNA		
EQUIPMENT	DIMENSIONS	WEIGHT
MAKE: JMA MODEL: MX08FT265-01	32.0"L x 11.6"W x 4.5"D	26.5 LBS.

3 ANTENNA DETAIL
C-3 NOT TO SCALE




RRH - ISOMETRIC RRH CLEARANCES

DUAL BAND RRU (REMOTE RADIO UNIT)			
EQUIPMENT	BANDS	DIMENSIONS	WEIGHT
MAKE: SAMSUNG MODEL: RF4438d-25A	B25: PCS (1900 MHz) B66: AWS (2100 MHz)	15.0"H x 15.0"W x 10.0"D	74.7 LBS.

NOTES:
1. CONTRACTOR TO COORDINATE FINAL EQUIPMENT MODEL SELECTION WITH VERIZON WIRELESS CONSTRUCTION MANAGER PRIOR TO ORDERING.

4 DUAL-BAND AWS/PCS MACRO RADIO UNIT DETAIL
C-3 NOT TO SCALE



RRH - ISOMETRIC RRH CLEARANCES

DUAL BAND RRU (REMOTE RADIO UNIT)			
EQUIPMENT	BANDS	DIMENSIONS	WEIGHT
MAKE: SAMSUNG MODEL: RF440d-13A	B5: 850 MHz B13: 700 MHz	15.0"H x 15.0"W x 9.0"D	70.3 LBS.

NOTES:
1. CONTRACTOR TO COORDINATE FINAL EQUIPMENT MODEL SELECTION WITH VERIZON WIRELESS CONSTRUCTION MANAGER PRIOR TO ORDERING.

5 DUAL-BAND 700/850 MHz MACRO RADIO UNIT DETAIL
C-3 NOT TO SCALE



RRH - ISOMETRIC

C BAND 8TR 320W RRU (REMOTE RADIO UNIT)			
EQUIPMENT	BANDS	DIMENSIONS	WEIGHT
MAKE: SAMSUNG MODEL: RT-8808-77A	N77: 3700 MHz	15.0"H x 15.0"W x 6.8"D	59.5 LBS.

NOTES:
1. CONTRACTOR TO COORDINATE FINAL EQUIPMENT MODEL SELECTION WITH VERIZON WIRELESS CONSTRUCTION MANAGER PRIOR TO ORDERING.

6 C-BAND 8TR 320W RADIO UNIT DETAIL
C-3 NOT TO SCALE

DATE: 11/18/21	SCALE: AS NOTED	JOB NO.: 2100789
RF DETAILS		
C-3		
Sheet No. 6 of 7		


Cellco Partnership d/b/a Verizon Wireless
BRIDGEPORT NE CT
541 BROADBRIDGE RD
BRIDGEPORT, CT 06610

CENITEK engineering
203-488-0890
488-8887 Fax
145
Branford, CT 06405
www.CenitekEng.com

PROFESSIONAL ENGINEER SEAL
VERIZON

CONSTRUCTION DRAWINGS - ISSUED FOR CONSTRUCTION
CONSTRUCTION DRAWINGS - REVISED FOR RFI'S DATED 11/19/2021
CONSTRUCTION DRAWINGS - ISSUED FOR CLIENT REVIEW

NO.	DATE	BY	DESCRIPTION
1	11/18/21	JLD	ISSUED FOR CLIENT REVIEW
2	11/18/21	ANC	ISSUED FOR RFI'S
3	11/18/21	ANC	ISSUED FOR CONSTRUCTION




NOTES:


- DO NOT INSTALL CABLE GROUND KIT AT A BEND AND ALWAYS DIRECT GROUND WIRE DOWN TO CIGBE.

1 CONNECTION OF GROUND WIRES TO GROUND BAR
E-1 NOT TO SCALE

EACH RRH CABINET SHALL BE GROUNDED IN THE FOLLOWING MANNER:
1. AT TOP OF THE CABINET
2. AT RIGHT SIDE OF THE CABINET.




2 RRH POLE MOUNT GROUNDING
E-1 NOT TO SCALE




NOTES:

- DO NOT INSTALL CABLE GROUND KIT AT A BEND AND ALWAYS DIRECT GROUND WIRE DOWN TO GROUND BAR.

3 ANTENNA CABLE GROUNDING DETAIL
E-1 NOT TO SCALE



4 TYPICAL ANTENNA GROUNDING DETAIL
E-1 NOT TO SCALE



NOTES

- TINNED COPPER GROUND BAR, 1/4" x 4" x 20", NEWTON INSTRUMENT CO. HOLE CENTERS TO MATCH NEMA DOUBLE LUG CONFIGURATION.
- INSULATORS, NEWTON INSTRUMENT CAT. NO. 3061-4.
- 5/8" LOCK WASHERS, NEWTON INSTRUMENT CO. CAT. NO. 3015-8.
- WALL MOUNTING BRACKET, NEWTON INSTRUMENT CO. CAT. NO. A-6055.
- 5/8-11 x 1" STAINLESS STEEL TRUSS SPANNER MACHINE SCREWS.

5 GROUND BAR DETAIL
E-1 NOT TO SCALE

ELECTRICAL SPECIFICATIONS

SECTION 16010

1.01. SCOPE OF WORK

A. WORK SHALL INCLUDE ALL LABOR, EQUIPMENT AND SERVICES REQUIRED TO COMPLETE (MAKE READY FOR OPERATION) ALL THE ELECTRICAL SERVICES INCLUDING, BUT NOT LIMITED TO, THE FOLLOWING:

- CELLULAR GROUNDING SYSTEMS CONSISTING OF ANTENNA GROUNDING, GROUND BARS, ETC.

1.02. GENERAL REQUIREMENTS

- THE ENTIRE ELECTRICAL INSTALLATION SHALL BE MADE IN STRICT ACCORDANCE WITH ALL LOCAL, STATE AND NATIONAL CODES AND REGULATIONS WHICH MAY APPLY AND NOTHING IN THE DRAWINGS OR SPECIFICATIONS SHALL BE INTERPRETED AS AN INFRINGEMENT OF SUCH CODES OR REGULATIONS.
- THE ELECTRICAL CONTRACTOR IS TO BE RESPONSIBLE FOR THE COMPLETE INSTALLATION AND COORDINATION OF THE ENTIRE ELECTRICAL SERVICE. ALL ACTIVITIES TO BE COORDINATED THROUGH OWNERS REPRESENTATIVE, DESIGN ENGINEER AND OTHER AUTHORITIES HAVING JURISDICTION OF TRADES.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL PERMITS AND PAY ALL FEES THAT MAY BE REQUIRED FOR THE ELECTRICAL WORK AND FOR SCHEDULING OF ALL INSPECTIONS THAT MAY BE REQUIRED BY THE LOCAL AUTHORITY.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATION WITH THE BUILDING OWNER FOR NEW AND/OR DEMOLITION WORK INVOLVED.
- NO MATERIAL OTHER THAN THAT CONTAINED IN THE "LATEST LIST OF ELECTRICAL FITTINGS" APPROVED BY THE UNDERWRITERS' LABORATORIES, SHALL BE USED IN ANY PART OF THE WORK. ALL MATERIAL FOR WHICH LABEL SERVICE HAS BEEN ESTABLISHED SHALL BEAR THE U.L. LABEL.
- THE CONTRACTOR SHALL GUARANTEE ALL NEW WORK FOR A PERIOD OF ONE YEAR FROM THE ACCEPTANCE DATE BY THE OWNER. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING WARRANTIES FROM ALL EQUIPMENT MANUFACTURERS FOR SUBMISSION TO THE OWNER.
- DRAWINGS INDICATE GENERAL ARRANGEMENT OF WORK INCLUDED IN CONTRACT. CONTRACTOR SHALL, WITHOUT EXTRA CHARGE, MAKE MODIFICATIONS TO THE LAYOUT OF THE WORK TO PREVENT CONFLICT WITH WORK OF OTHER TRADES AND FOR THE PROPER INSTALLATION OF WORK. CHECK ALL DRAWINGS AND VISIT JOB SITE TO VERIFY SPACE AND TYPE OF EXISTING CONDITIONS IN WHICH WORK WILL BE DONE, PRIOR TO SUBMITTAL OF BID.
- THE ELECTRICAL CONTRACTOR SHALL SUPPLY THREE (3) COMPLETE SETS OF APPROVED DRAWINGS, ENGINEERING DATA SHEETS, MAINTENANCE AND OPERATING INSTRUCTION MANUALS FOR ALL SYSTEMS AND THEIR RESPECTIVE EQUIPMENT. THESE MANUALS SHALL BE INSERTED IN VINYL COVERED 3-RING BINDERS AND TURNED OVER TO OWNER'S REPRESENTATIVE ONE (1) WEEK PRIOR TO FINAL PUNCH LIST.
- ALL WORK SHALL BE INSTALLED IN A NEAT AND WORKMAN LIKE MANNER AND WILL BE SUBJECT TO THE APPROVAL OF THE OWNER'S REPRESENTATIVE.
- ALL EQUIPMENT AND MATERIALS TO BE INSTALLED SHALL BE NEW, UNLESS OTHERWISE NOTED.
- BEFORE FINAL PAYMENT, THE CONTRACTOR SHALL PROVIDE A COMPLETE SET OF PRINTS (AS-BUILTS), LEGIBLY MARKED IN RED PENCIL TO SHOW ALL CHANGES FROM THE ORIGINAL PLANS.
- ENTIRE ELECTRICAL INSTALLATION SHALL BE IN ACCORDANCE WITH OWNER'S SPECIFICATIONS, AND REQUIREMENTS OF ALL LOCAL AUTHORITIES HAVING JURISDICTION. IT IS THE CONTRACTOR'S RESPONSIBILITY TO COORDINATE WITH APPROPRIATE INDIVIDUALS TO OBTAIN ALL SUCH SPECIFICATIONS AND REQUIREMENTS. NOTHING CONTAINED IN, OR OMITTED FROM, THESE DOCUMENTS SHALL RELIEVE CONTRACTOR FROM THIS OBLIGATION.

SECTION 16450

1.01. GROUNDING

- ALL NON-CURRENT CARRYING PARTS OF THE ELECTRICAL AND TELEPHONE CONDUIT SYSTEMS SHALL BE MECHANICALLY AND ELECTRICALLY CONNECTED TO PROVIDE AN INDEPENDENT RETURN PATH TO THE EQUIPMENT GROUNDING SOURCES.
- GROUNDING SYSTEM WILL BE IN ACCORDANCE WITH THE LATEST ACCEPTABLE EDITION OF THE NATIONAL ELECTRICAL CODE AND REQUIREMENTS PER LOCAL INSPECTOR HAVING JURISDICTION.
- EQUIPMENT GROUNDING CONDUCTOR:
 - EACH EQUIPMENT GROUND CONDUCTOR SHALL BE SIZED IN ACCORDANCE WITH THE N.E.C. ARTICLE 250-122.
 - THE MINIMUM SIZE OF EQUIPMENT GROUND CONDUCTOR SHALL BE #12 AWG COPPER.
- CELLULAR GROUNDING SYSTEM:

PROVIDE THE CELLULAR GROUNDING SYSTEM AS SPECIFIED ON DRAWINGS, INCLUDING, BUT NOT LIMITED TO:

 - GROUND BARS
 - ANTENNA GROUND CONNECTIONS AND PLATES.
- ALL EQUIPMENT SHALL BE BONDED TO GROUND AS REQUIRED BY N.E.C., MFG. SPECIFICATIONS, AND OWNER'S SPECIFICATIONS.

CONSTRUCTION DRAWINGS - ISSUED FOR CONSTRUCTION	DATE: 11/18/21
CONSTRUCTION DRAWINGS - REVISION FOR RFOS DATED 11/18/2021	SCALE: AS NOTED
CONSTRUCTION DRAWINGS - ISSUED FOR CLIENT REVIEW	JOB NO. 21007.09
DATE: 11/18/21	ELECTRICAL DETAILS AND SPECIFICATIONS
DATE: 11/18/21	
DATE: 11/18/21	E-1
DATE: 11/18/21	
DATE: 11/18/21	Sheet No. 1 of 1

Cellco Partnership d/b/a Verizon Wireless
BRIDGEPORT NE CT
541 BROADBRIDGE RD
BRIDGEPORT, CT 06610

CENITEK engineering
1203 #408-0889
1452 North Branford Road
Branford, CT 06405
www.CenitekEng.com

MX08FIT265-01

NWAV™ Panel Antenna

8-Port 32 in. FIT (Form in Tighter), 3700 - 4200 MHz

- 5G C-Band 8T8R beamforming antenna
- Optimized antenna array design for all C-Band beamforming combinations
- Excellent passive intermodulation (PIM) performance reduces harmful interference
- Integrated (internal RET) for remote electrical tilt control



NWAV™

Electrical specification (minimum/maximum)	Ports 1, 2, 3, 4, 5, 6, 7, 8
Frequency bands, MHz	3700-4200
Gain, dBi	17.1
Horizontal beamwidth (HBW), degrees	85
Horizontal beamwidth tolerance, degrees	±5
Front-to-back ratio, co-polar power @180°± 30°, dB	27
Vertical beamwidth (VBW), degrees ¹	5.5
Vertical beamwidth tolerance, degrees	±0.3
Remote electrical downtilt (EDT) range, degrees	2-12
First upper side lobe (USLS) suppression, dB ¹	15
Coupling level, Amp, Antenna port to Cal port, dB	26
Coupling level, max Amp Δ, Antenna port to Cal port, dB	±0.6
Coupler, max Amp Δ, Antenna port to Cal port, dB	0.65
Coupler, max Phase Δ, Antenna port to Cal port, degrees	4
Cross-polar isolation, port-to-port, dB ¹	25
Max VSWR / return loss, dB	1.5:1 / -14.0
Max passive intermodulation (PIM), 2x20W carrier, dBc	-145
Max input power per port at 50 °C, watts	75

¹ Typical value over frequency and tilt



MX08FIT265-01
NWAV™ Panel Antenna

Electrical specification, Broadcast 65°	Ports 1, 2, 3, 4, 5, 6, 7, 8
Frequency bands, MHz	3700-4200
Gain over all tilts, dBi	22.5
Horizontal beamwidth (HBW), degrees ¹	65
Horizontal beamwidth tolerance, degrees	±6
Vertical beamwidth (VBW), degrees ¹	5.5
Vertical beamwidth tolerance, degrees	±0.3
First upper side lobe (USLS) suppression, dB ¹	<-16

Electrical specification, Service Beam	Ports 1, 2, 3, 4, 5, 6, 7, 8
Frequency bands, MHz	3700-4200
Steered 0° gain, dBi	22.5
Steered 0° Gain tolerance, dBi	±0.6
Steered 0° Beamwidth, Horizontal, degrees	22
Steered 0° CPR at beampeak, dB	18
Steered 0° Horizontal Sidelobe, dB	12
Steered 30° Gain, dBi (max)	21.8
Steered 30° Gain tolerance, dBi	±0.6
Steered 30° Gain, dBi	21
Steered 30° Beamwidth, Horizontal, degree	22.2
Steered 30° CPR at beampeak, dB	18
Steered 30° Horizontal Sidelobe, dB	10

Electrical specification, Soft Split	Ports 1, 2, 3, 4, 5, 6, 7, 8
Frequency bands, MHz	3700-4200
Gain over all tilts, dBi	21.8
Horizontal beamwidth (HBW), degrees ¹	32
First upper side lobe (USLS) suppression, dB ¹	15


Beamforming weighting table available upon request



MX08FIT265-01

NWAV™ Panel Antenna

Mechanical specifications	
Dimensions height/width/depth, inches (mm)	32.0/ 11.6/ 4.53 (812.8/ 295/ 115)
Shipping dimensions length/width/height, inches (mm)	37.0/ 16.9/ 11.8 (939.8/ 430/ 300)
No. of RF input ports, connector type, and location	8 x 4.3-10 female, bottom
Calibration interface port, connector type, and location	1 x 4.3-10 female, bottom
RF connector torque	96 lbf-in (10.85 N·m or 8 lbf-ft)
Net antenna weight, lb (kg)	23.2 (10.52)
Weight with supplied pipe mount bracket, lb (kg)	26.5 (12.02)
Shipping weight, lb (kg)	49.1 (22.27)
Rated wind survival speed, mph (km/h)	150 (241)
Frontal wind loading @ 150 km/h, lbf (N)	56.9




Ordering information	
Antenna model	Description
MX08FIT265-01	32-inch 8T8R beamforming antenna, 3700-4200 MHz with RET
Mounting kit (included)	91900330 BRACKET KIT, range of mechanical up/down tilt -2° to 12°
Optional accessories	
AISG cables	M/F cables for AISG connections
PCU-1000 RET controller	Stand-alone controller for RET control and configurations

Remote electrical tilt (RET 1000) information

RET location	Integrated into antenna
RET interface connector type	8-pin AISG connector per IEC 60130-9 or RF port Bias-T
RET connector torque	Min 0.5 N·m to max 1.0 N·m (hand pressure & finger tight)
RET interface connector quantity	1 pair of AISG male/female connectors and 1 RF port Bias-T
RET interface connector location	Bottom of the antenna
Total no. of internal RETs	1
RET input operating voltage, vdc	10-30
RET max power consumption, idle state, W	≤ 2.0
RET max power consumption, normal operating conditions, W	≤ 13.0
RET communication protocol	AISG 2.0 / 3GPP

RET and RF connector topology

Each RET device can be controlled either via the designated external AISG connector or RF port as shown below:



Array topology

1 set of radiating arrays P1: 3700-4200 MHz	<table border="1"> <thead> <tr> <th>Band</th> <th>RF port</th> </tr> </thead> <tbody> <tr> <td>3700-4200</td> <td>1-8</td> </tr> </tbody> </table>	Band	RF port	3700-4200	1-8	
	Band	RF port				
3700-4200	1-8					

SAMSUNG

102 RRU
Product Specification

for RT8808-77A


Specifies hardware configuration, functions, specifications, components, ports, and LED information for the radio units.

Document Version 1.0
June 2021

Radio Access Network

Document Number: 2600-00T7PZGA2

Figure 1. Appearance



The RT8808-77A can be mounted on a wall or pole as displayed in the following installation scenario:

Specifications

The following table outlines the main specifications of RT8808-77A.

Table 2. Specifications (RT8808-77A)

Item	RT8808-77A
Radio Technology	5G NR
Operating Frequency	3700 to 3980 MHz
Channel Bandwidth	20/40/60/80/100 MHz
RF Chain	<ul style="list-style-type: none"> • 8T8R, 4T4R+4T4R Bi-sector • 2T2R+2T2R+2T2R Tri-sector • 4T8R+4T8R split mode
RF Output Power	Max. 320W (8 x 40W)
Capacity	Total Max 2C
CPRI interface	15km, 2 ports (25Gbps x 2), SFP28, single mode, Bi-di (Option: Duplex)
Input Voltage	-48 V DC (-38 V DC to -57 V DC)
Power Consumption (Max.)	1,192 W (100% load, 25°C) (w/o RET)
Operating Humidity	5% to 100%RH (Condensing, not to exceed 30g/m3 absolute humidity)
Operating Temperature	-40°C to 55°C (without solar load)
Dimension (in./mm)	14.96/380 (W) × 6.82/173.3(D) × 14.96/380 (H)
Weight (kg)	27 or less than
Cooling	Natural convection
Waterproof/Dustproof	IP65
Wind Resistance	Telcordia GR-487-CORE Issue5 <ul style="list-style-type: none"> • Wind Resistance (Section 3.36)
Earthquake Specification	Telcordia GR-63-CORE, Issue5, <ul style="list-style-type: none"> □ Earthquake (Section 4.4.1)
Vibration Specification	Telcordia GR-63-CORE, Issue5, <ul style="list-style-type: none"> • Office Vibration (Section 4.4.4) • Transportation Vibration (Section 4.4.5)
Altitude	Telcordia GR-63-CORE, Issue5, <ul style="list-style-type: none"> • Altitude (Section 4.1.3)
EMC	FCC Title 47 CFR Part 15
RF	FCC Title 47 CFR Part 27, 24
Safety	UL 62368-1, 2nd Edition
Installation	Pole, Wall, Tower



The power consumption is predicted with a simulation and the measured value is subject to change by ±10%

SAMSUNG

700/850MHZ MACRO RADIO

DUAL-BAND AND HIGH POWER FOR MACRO COVERAGE

Samsung's future proof dual-band radio is designed to help effectively increase the coverage areas in wireless networks. This 700/850MHz 4T4R dual-band radio has 4Tx/4Rx to 2Tx/2Rx RF chains options and a total output power of 320W, making it ideal for macro sites.

Model Code RF4440d-13A



Homepage
samsungnetworks.com




Youtube
www.youtube.com/samsung5g

Points of Differentiation

Continuous Migration

Samsung's 700/850MHz macro radio can support each incumbent CPRI interface as well as an advanced eCPRI interface. This feature provides installable options for both legacy LTE networks and added NR networks.



O-RAN Compliant

A standardized O-RAN radio can help when implementing cost-effective networks because it is capable of sending more data without compromising additional investments.

Samsung's state-of-the-art O-RAN technology will help accelerate the effort toward constructing a solid O-RAN ecosystem.



Optimum Spectrum Utilization

The number of required carriers varies according to site (region). The ability to support many carriers is essential for using all frequencies that the operator has available.


The new 700/850MHz dual-band radio can support up to 2 carriers in the B13 (700MHz) band and 3 carriers in the B5 (850MHz) band, respectively.



Secured Integrity

Access to sensitive data is allowed only to authorized software.

The Samsung radio's CPU can protect root of trust, which is credential information to verify SW integrity, and secure storage provides access control to sensitive data by using dedicated hardware (TPM).



Technical Specifications

Item	Specification
Tech	LTE / NR
Brand	B13(700MHz), B5(850MHz)
Frequency Band	DL: 746 – 756MHz, UL: 777 – 787MHz DL: 869 – 894MHz, UL: 824 – 849MHz
RF Power	(B13) 4 × 40W or 2 × 60W (B5) 4 × 40W or 2 × 60W
IBW/OBW	(B13) 10MHz / 10MHz (B5) 25MHz / 25MHz
Installation	Pole, Wall
Size/Weight	14.96 x 14.96 x 9.05inch (33.2L) / 70.33 lb

SAMSUNG

AWS/PCS MACRO RADIO

DUAL-BAND AND HIGH POWER FOR MACRO COVERAGE

Samsung's future proof dual-band radio is designed to help effectively increase the coverage areas in wireless networks. This AWS/PCS 4T4R dual-band radio has 4Tx/4Rx to 2Tx/2Rx RF chains options and a total output power of 320W, making it ideal for macro sites.

Model Code RF4439d-25A



Homepage
samsungnetworks.com




Youtube
www.youtube.com/samsungSg

Points of Differentiation

Continuous Migration


Samsung's AWS/PCS macro radio can support each incumbent CPRI interface as well as advanced eCPRI interfaces. This feature provides installable options for both legacy LTE networks and added NR networks.



O-RAN Compliant

A standardized O-RAN radio can help in implementing cost-effective networks, which are capable of sending more data without compromising additional investments.


Samsung's state-of-the-art O-RAN technology will help accelerate the effort toward constructing a solid O-RAN ecosystem.



Optimum Spectrum Utilization

The number of required carriers varies according to site (region). Supporting many carriers is essential for using all frequencies that the operator has available.

The new AWS/PCS dual-band radio can support up to 3 carriers in the PCS (1.9GHz) band and 4 carriers in the AWS (2.1GHz) band, respectively.



Brand New Features in a Compact Size

Samsung's AWS/PCS macro radio offers several features, such as dual connectivity for baseband for both CDU and vDU, O-RAN capability, more carriers and an enlarged PCS spectrum, combined into an incumbent radio volume of 36.8L.



Technical Specifications

Item	Specification
Tech	LTE / NR
Brand	B25(PCS), B66(AWS)
Frequency Band	DL: 1930 – 1995MHz, UL: 1850 – 1915MHz DL: 2110 – 2200MHz, UL: 1710 – 1780MHz
RF Power	(B25) 4 × 40W or 2 × 60W (B66) 4 × 60W or 2 × 80W
IBW/OBW	(B25) 65MHz / 30MHz (B66) DL 90MHz, UL 70MHz / 60MHz
Installation	Pole, Wall
Size/Weight	14.96 x 14.96 x 10.04inch (36.8L) / 74.7lb

4G LTE B6

Support Sector LTE 4x 698-896 MHz 8x 890-2362 MHz
 HBB 6x 2E22



- Flat broadband Low Band 980-900 MHz and High Band 950-900 MHz arrays for 4T4M 4X 100 capability for Band 4, AWS, CS and WCS applications
- Independent tilt for all arrays
- Array configuration provides capability for 4T4M 4X 100 on Low band and Dual 4T4M 4X 100 on High band
- Optimal SWR performance across all operating bands
- Excellent wind loading characteristics

General Specifications

Antenna Type	Sector
Band	Multi-band
Grounding Type	RF connector inner conductor and body grounded to reflector and mounting bracket
Performance Note	Indoor sag Wind loading figures are validated by independent test houses described in hit paper W-54E
Radome Material	Fiberglass, UV resistant
Radiator Material	Low loss circuit board
Reflector Material	Aluminum
RF Connector Interface	4mm F-conn
RF Connector Location	Bottom
RF Connector Quantity, high band	8
RF Connector Quantity, low band	4
RF Connector Quantity, total	12

Key Note Electric Tilt (ET) Performance

Hardware	Compliant ET
Interface	8-pin DII F-conn 8-pin DII 8-pin
Interface, quantity	1 f-conn 1 1 1
Input Voltage	10-12 Vdc
Internal	High band 4M Low band 4M
Power Consumption, idle state, maximum	1 W
Power Consumption, normal conditions, maximum	8 W

46B6

Protocol

MG AISG Multi ET

Dimensions

Width

498 mm (19.6 in)

Depth

90 mm (3.5 in)

Height

88 mm (3.47 in)

Net weight, without mounting kit

1.8 kg (3.96 lb)


Array Layout

Array	Freq (MHz)	Conns	RET (SRET)	AISG RET UID
R1	698-896	1-2	1	CPxxxxxxxxxxxxxxxxmm.1
R2	698-896	3-4	2	CPxxxxxxxxxxxxxxxxmm.2
Y1	1695-2360	5-6	3	CPxxxxxxxxxxxxxxxxmm.3
Y2	1695-2360	7-8	4	CPxxxxxxxxxxxxxxxxmm.4
Y3	1695-2360	9-10	5	CPxxxxxxxxxxxxxxxxmm.5
Y4	1695-2360	11-12	6	CPxxxxxxxxxxxxxxxxmm.6

Left Bottom Right Bottom (Sizes of colored boxes are not true depictions of array sizes)

Port Configuration

46B6



Electric Specificatio

Impedance	50 ohm
Operating Frequency Band	95 – 1000 MHz 98 – 890 MHz
Polarization	±45°
Maximum Input Power, maximum	90 W @ 50 °C

Electric Specificatio

Frequency Band, MHz	980	890	900-880	800-990	900-880	900-880
Gain, dBi	4	5	5	5	5	5
Beamwidth, Horizontal degrees	9	5	58	5	5	58
Beamwidth, Vertical degrees	5	5	5	5	9	8
Beam tilt, degrees	-4	-4	-4	-4	-4	-4
First lobe	5	8	8	9	9	5
Front-to-Ratio at 80, dB	8	5	5	8	5	5
Isolation, Cross Polarization, dB	5	5	5	5	5	5
Isolation, Interband, dB	5	5	5	5	5	5
Return Loss, dB	15	15	15	15	15	15

46B6

PIM, 1rd order, x dB, dBc	50	50	50	50	50	50
Input Power per Port at 100C, maximum, watts	100	100	50	50	50	100

Electric Specificity BA

Frequency Band, MHz	9880	8000-8900	9000-8800	8000-9900	9000-8000	00000000
Gain b/a Beam i/s, average, dBi	4	4	5	0	0	5
Gain b/a Beam i/s tolerance, dB	±5	±0	±0	±5	±4	±5
Gain b/a Beam i/s, average, dBi	4 4 4	4 4 4	5 5 5	0 0 0	0 0 0	5 5 5
Beamwidth, Horizontal tolerance, degrees	±0	±4	±5	±0	±0	±0
Beamwidth, Vertical tolerance, degrees	±0	±0	±0	±5	±0	±4
Beam, beampeak to beam above beam, dB	0	0	8	9	0	0
Front-to-Rear Power at 8000, dB	0	0	8	0	8	8
CP at Boresight, dB	0	4	5	0	0	0
CP at Sector, dB	0	5	9	8	0	9

Mechanical Specificity

Effective Projective Area, front	4 m ² 889 ft ²
Effective Projective Area, lateral	0 m ² 0 ft ²
Wind loading, excite, front	85 @ 5 k/h 54 lbf @ 5 k/h
Wind loading, excite, lateral	@ 5 k/h 5 lbf @ 5 k/h
Wind loading, excite, maximum	889 @ 5 k/h 99 lbf @ 5 k/h
Wind loading, excite, rear	54 @ 5 k/h 18 lbf @ 5 k/h
Wind speed, maximum	4 k/h 495 ph

Package Dimensions

Width, packed	8 in 200 in
Depth, packed	5 in 158 in
Length, packed	in 94 in
Weight, gross	5 kg 145 lb

46B6

Regulatory Compliance Certification

General

China HS

ISO 9001:2015

HS



Classification

Abolish the concentration value

Designed, manufactured and/or distributed under this quality management system

Compliant product

Included Product

BSA TM

- Wide profile Antenna Down tilt Mounting Kit for 4445 in 5555 D round bars
Kit contains one scissor top bracket set and one bottom bracket set

Footnote

Performance Note

Storage in iron metal conditions will degrade optical performance and

ATTACHMENT 2

Structural Analysis Report

98-ft Existing Flagpole

*Proposed Verizon
Antenna Upgrade*

Site Ref: Bridgeport NE CT

*541 Broadbridge Road
Bridgeport, CT*

Centek Project No. 21007.69

Date: November 19, 2021

Max Stress Ratio = 65%



Prepared for:
Verizon Wireless
20 Alexander Drive
Wallingford, CT 06492

Table of Contents

SECTION 1 - REPORT

- INTRODUCTION
- ANTENNA AND APPURTENANCE SUMMARY
- PRIMARY ASSUMPTIONS USED IN THE ANALYSIS
- ANALYSIS
- TOWER LOADING
- TOWER CAPACITY
- FOUNDATION AND ANCHORS
- CONCLUSION

SECTION 2 – CONDITIONS & SOFTWARE

- STANDARD ENGINEERING CONDITIONS
- GENERAL DESCRIPTION OF STRUCTURAL ANALYSIS PROGRAM

SECTION 3 – CALCULATIONS

- tnxTower INPUT/OUTPUT SUMMARY – FLAGPOLE
- tnxTower DETAILED OUTPUT – FLAGPOLE
- ANCHOR BOLT AND BASE PLATE ANALYSIS
- FOUNDATION ANALYSIS

SECTION 4 – REFERENCE MATERIAL

- RF DATA SHEET

Introduction

The purpose of this report is to summarize the results of the non-linear, P- Δ structural analysis of the antenna upgrade proposed by Verizon on the existing flagpole (tower) located in Bridgeport, Connecticut.

The host tower consists of three (3) 10-ft concealment canister sections supported on a 68.0-ft tall, two-section, eighteen sided, tapered monopole original designed by EEI jo no. 18280-D01 dated 02/20/2018. The tower geometry and structure member sizes were obtained the original design documents.

Antenna and appurtenance information were obtained from a previous structural analysis report prepared by Engineered Endeavors; dated February 19, 2018 and a Verizon RF data sheet.

The tower is made up of two (2) tapered vertical sections consisting of A572-65 sections. The vertical tower sections are slip joint connected. The diameter of the pole (flat-flat) is 35.5-in at the top and 45.00-in at the base.

Antenna and Appurtenance Summary

The existing, proposed and future loads considered in this analysis consist of the following:

- **VERIZON(EXISTING TO REMOVE):**
 - Antennas:** Six (6) Commscope SBJAHH-1D65B-DL panel antennas with rad center elevation of $\pm 92\&82$ -ft above grade level.
 - Appurtenances:** Three(3) Nokia B13 RRH 4x30 radio head units, three (3) Nokia B25 RRH 4x30 radio head units, three (3) Nokia B66A RRH 4x45 radio head units and twenty four (24) Kaelus QBC0002F1V51-1 Quadplexer.
- **VERIZON (Proposed):**
 - Antennas:** Three (3) Commscope NNH4-65B-R6 panel antennas and three (3) JMA MX08FIT265-01 panel antennas mounted within a concealment canister with rad center elevations of $\pm 92\&82$ -ft above grade level.
 - Appurtenances:** Three(3) Samsung RT-8808-77A radio head units, six (6) Commscope CBC61923T-DS-43 diplexers and one 6 OVP box.

Primary Assumptions Used in the Analysis

- The tower structure's theoretical capacity not including any assessment of the condition of the tower.
- The tower carries the horizontal and vertical loads due to the weight of antennas, ice load and wind.
- Tower is properly installed and maintained.
- Tower is in plumb condition.
- Tower loading for antennas and mounts as listed in this report.
- All bolts are appropriately tightened providing the necessary connection continuity.
- All welds are fabricated with ER-70S-6 electrodes.
- All members are assumed to be as specified in the original tower design documents or reinforcement drawings.
- All members are "hot dipped" galvanized in accordance with ASTM A123 and ASTM A153 Standards.
- All member protective coatings are in good condition.
- All tower members were properly designed, detailed, fabricated, installed and have been properly maintained since erection.
- Any deviation from the analyzed antenna loading will require a new analysis for verification of structural adequacy.
- All coax cables to be installed as indicated in this report.

Analysis

The existing tower was analyzed using a comprehensive computer program entitled tnxTower. The program analyzes the tower, considering the worst case loading condition. The tower is considered as loaded by concentric forces along the tower, and the model assumes that the tower members are subjected to bending, axial, and shear forces.

The existing tower was analyzed for the controlling basic wind speed (3-second gust) with no ice and the applicable wind and ice combination to determine stresses in members as per guidelines of TIA-222-G-2005 entitled "Structural Standard for Antenna Support Structures and Antennas", the American Institute of Steel Construction (AISC) and the Manual of Steel Construction; Load and Resistance Factor Design (LRFD).

The controlling wind speed is determined by evaluating the local available wind speed data as provided in Appendix N of the CSBC¹ and the wind speed data available in the TIA-222-G-2005 Standard.

Tower Loading

Tower loading was determined by the basic wind speed as applied to projected surface areas with modification factors per TIA-222-G-2005, gravity loads of the tower structure and its components, and the application of 0.75" radial ice on the tower structure and its components.

Basic Wind Speed:	Bridgeport; $v = 97$ mph (Vasd – Risk Cat II)	[Appendix N of the 2018 CT Building Code]
Load Cases:	<u>Load Case 1</u> ; 97 mph wind speed w/ no ice plus gravity load – used in calculation of tower stresses and rotation.	[Appendix N of the 2018 CT Building Code]
	<u>Load Case 2</u> ; 50 mph wind speed w/ 0.75" radial ice plus gravity load – used in calculation of tower stresses.	[Annex B of TIA-222-G-2005]

¹ The 2015 International Building Code as amended by the 2018 Connecticut State Building Code (CSBC).

Tower Capacity

- Calculated stresses were found to be within allowable limits.

Tower Section	Elevation (AGL)	Stress Ratio (percentage of capacity)	Result
Antenna Pole (Inside Canister – L3)	68.5' - 78.0'	64.7%	PASS
Pole Shaft (L6)	1.0' - 38.3'	35.7%	PASS

Foundation and Anchors

The existing foundation consists of a one (1) 6-ft Ø round x 18.75-ft tall pier. The existing foundation properties were obtained from the aforementioned design documents. The base of the tower is connected to the foundation by means of (6) 1.75"Ø, ASTM A615-75 anchor bolts embedded approximately 5.17-ft into the concrete foundation structure.

- The tower base reactions developed from the governing Load Case were used in the verification of the foundation and its anchors:

Location	Vector	Proposed Reactions
Base	Shear	11 kips
	Compression	15 kips
	Moment	683 kip-ft

- The foundation was found to be within allowable limits.

Foundation	Design Limit	Proposed Loading	Result
Reinforced Concrete Caisson	Moment Capacity	23.8%	PASS
	Lateral Deflection	0.27 in. ⁽¹⁾	PASS

(1) Lateral deflection limited to 0.75 in under service load combination per TIA-222-G section 9.5.

- The anchor bolts and base plate were found to be within allowable limits.

Tower Component	Design Limit	Stress Ratio (percentage of capacity)	Result
Anchor Bolts	Combined Axial and Bending	64.7%	PASS
Base Plate	Bending	61.5%	PASS

CEN TEK Engineering, Inc.
Structural Analysis – 98-ft Flagpole
Verizon Antenna Upgrade – Bridgeport NE CT
Bridgeport, CT
November 19, 2021

Conclusion

This analysis shows that the subject tower **is adequate** to support the proposed modified antenna configuration.

- Replacement of the top two (2) 10-ft concealment canisters with 10-ft x 48" diameter canisters (designed by others) is required to accommodate the proposed antennas.

The analysis is based, in part, on the information provided to this office by Verizon. If the existing conditions are different than the information in this report, Centek Engineering, Inc. must be contacted for resolution of any potential issues.

Please feel free to call with any questions or comments.

Respectfully Submitted by:



Timothy J. Lynn, PE
Structural Engineer



Prepared by:



Fernando J. Palacios
Engineer

CEN TEK Engineering, Inc.
Structural Analysis – 98-ft Flagpole
Verizon Antenna Upgrade – Bridgeport NE CT
Bridgeport, CT
November 19, 2021

*Standard Conditions for Furnishing of
Professional Engineering Services on
Existing Structures*

All engineering services are performed on the basis that the information used is current and correct. This information may consist of, but is not necessarily limited to:

- Information supplied by the client regarding the structure itself, its foundations, the soil conditions, the antenna and feed line loading on the structure and its components, or other relevant information.
- Information from the field and/or drawings in the possession of Centek Engineering, Inc. or generated by field inspections or measurements of the structure.
- It is the responsibility of the client to ensure that the information provided to Centek Engineering, Inc. and used in the performance of our engineering services is correct and complete. In the absence of information to the contrary, we assume that all structures were constructed in accordance with the drawings and specifications and are in an uncorroded condition and have not deteriorated. It is therefore assumed that its capacity has not significantly changed from the “as new” condition.
- All services will be performed to the codes specified by the client, and we do not imply to meet any other codes or requirements unless explicitly agreed in writing. If wind and ice loads or other relevant parameters are to be different from the minimum values recommended by the codes, the client shall specify the exact requirement. In the absence of information to the contrary, all work will be performed in accordance with the latest revision of ANSI/ASCE10 & ANSI/EIA-222
- All services performed, results obtained, and recommendations made are in accordance with generally accepted engineering principles and practices. Centek Engineering, Inc. is not responsible for the conclusions, opinions and recommendations made by others based on the information we supply.

CENTEK Engineering, Inc.
Structural Analysis – 98-ft Flagpole
Verizon Antenna Upgrade – Bridgeport NE CT
Bridgeport, CT
November 19, 2021

GENERAL DESCRIPTION OF STRUCTURAL ANALYSIS PROGRAM

tnxTower, is an integrated structural analysis and design software package for Designed specifically for the telecommunications industry, tnxTower, formerly ERITower, automates much of the tower analysis and design required by the TIA/EIA 222 Standard.

tnxTower Features:

- tnxTower can analyze and design 3- and 4-sided guyed towers, 3- and 4-sided self-supporting towers and either round or tapered ground mounted poles with or without guys.
- The program analyzes towers using the TIA-222-G (2005) standard or any of the previous TIA/EIA standards back to RS-222 (1959). Steel design is checked using the AISC ASD 9th Edition or the AISC LRFD specifications.
- Linear and non-linear (P-delta) analyses can be used in determining displacements and forces in the structure. Wind pressures and forces are automatically calculated.
- Extensive graphics plots include material take-off, shear-moment, leg compression, displacement, twist, feed line, guy anchor and stress plots.
- tnxTower contains unique features such as True Cable behavior, hog rod take-up, foundation stiffness and much more.

Section	6	5	4	3	2	1
Length (ft)	42.750	29.750	0.500	9.500	0.500	19.500
Number of Sides	18	18	1	1	1	1
Thickness (in)	0.250	0.250	0.465	0.465	0.465	0.465
Socket Length (ft)		5.500				
Top Dia (in)	38.684	35.500	10.750	10.750	8.625	8.625
Bot Dia (in)	45.000	40.020	35.500	10.750	10.750	8.625
Grade	A572-65	A500-42				
Weight (K)	4.8	3.0	0.1	0.5	0.0	0.8

98.0 ft

78.5 ft

68.5 ft

38.3 ft

1.0 ft

DESIGNED APPURTENANCE LOADING

TYPE	ELEVATION	TYPE	ELEVATION
10"x48" Canister	98 - 88	RRFDC-3315-PF-48 (Verizon - Proposed)	92
NNH4-65B-R6 (Verizon - Proposed)	92	10"x48" Canister	88 - 78
NNH4-65B-R6 (Verizon - Proposed)	92	RT-8808-77A (Verizon - Proposed)	82
NNH4-65B-R6 (Verizon - Proposed)	92	RT-8808-77A (Verizon - Proposed)	82
(2) CBC61923T-DS-43 - Diplexer (Verizon - Proposed)	92	RT-8808-77A (Verizon - Proposed)	82
(2) CBC61923T-DS-43 - Diplexer (Verizon - Proposed)	92	MX08FIT265-01 (Verizon - Proposed)	82
(2) CBC61923T-DS-43 - Diplexer (Verizon - Proposed)	92	MX08FIT265-01 (Verizon - Proposed)	82
(2) CBC61923T-DS-43 - Diplexer (Verizon - Proposed)	92	MX08FIT265-01 (Verizon - Proposed)	82
		10"x36" Canister	78 - 68



MATERIAL STRENGTH

GRADE	Fy	Fu	GRADE	Fy	Fu
A500-42	42 ksi	56 ksi	A572-65	65 ksi	80 ksi

TOWER DESIGN NOTES

1. Tower designed for Exposure C to the TIA-222-G Standard.
2. Tower designed for a 97 mph basic wind in accordance with the TIA-222-G Standard.
3. Tower is also designed for a 50 mph basic wind with 0.75 in ice. Ice is considered to increase in thickness with height.
4. Deflections are based upon a 60 mph wind.
5. Tower Structure Class II.
6. Topographic Category 1 with Crest Height of 0,000 ft
7. TOWER RATING: 64.7%

ALL REACTIONS ARE FACTORED



Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job: 21007.69 vZw Bridgeport NE CT	
	Project: 98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	
	Client: Verizon Wireless	
	Drawn by: TJL	
	App'd:	
Code: TIA-222-G	Date: 11/19/21	Scale: NTS
Path:	Dwg No: E-1	

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job 21007.69 vZw Bridgeport NE CT	Page 1 of 32
	Project 98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date 11:45:36 11/19/21
	Client Verizon Wireless	Designed by TJL

Tower Input Data

The tower is a monopole.

This tower is designed using the TIA-222-G standard.

The following design criteria apply:

Basic wind speed of 97 mph.

Structure Class II.

Exposure Category C.

Topographic Category 1.

Crest Height 0.000 ft.

Nominal ice thickness of 0.750 in.

Ice thickness is considered to increase with height.

Ice density of 56 pcf.

A wind speed of 50 mph is used in combination with ice.

Temperature drop of 50 °F.

Deflections calculated using a wind speed of 60 mph.

A non-linear (P-delta) analysis was used.

Pressures are calculated at each section.

Stress ratio used in pole design is 1.

Local bending stresses due to climbing loads, feed line supports, and appurtenance mounts are not considered.

Options

<ul style="list-style-type: none"> Consider Moments - Legs Consider Moments - Horizontals Consider Moments - Diagonals Use Moment Magnification √ Use Code Stress Ratios √ Use Code Safety Factors - Guys Escalate Ice Always Use Max Kz Use Special Wind Profile Include Bolts In Member Capacity Leg Bolts Are At Top Of Section Secondary Horizontal Braces Leg Use Diamond Inner Bracing (4 Sided) SR Members Have Cut Ends SR Members Are Concentric 	<ul style="list-style-type: none"> Distribute Leg Loads As Uniform Assume Legs Pinned √ Assume Rigid Index Plate Use Clear Spans For Wind Area Use Clear Spans For KL/r Retension Guys To Initial Tension √ Bypass Mast Stability Checks Use Azimuth Dish Coefficients √ Project Wind Area of Appurt. Autocalc Torque Arm Areas Add IBC .6D+W Combination √ Sort Capacity Reports By Component Triangulate Diamond Inner Bracing Treat Feed Line Bundles As Cylinder Ignore KL/ry For 60 Deg. Angle Legs 	<ul style="list-style-type: none"> Use ASCE 10 X-Brace Ly Rules Calculate Redundant Bracing Forces Ignore Redundant Members in FEA SR Leg Bolts Resist Compression All Leg Panels Have Same Allowable Offset Girt At Foundation √ Consider Feed Line Torque Include Angle Block Shear Check Use TIA-222-G Bracing Resist. Exemption Use TIA-222-G Tension Splice Exemption Poles √ Include Shear-Torsion Interaction Always Use Sub-Critical Flow Use Top Mounted Sockets Pole Without Linear Attachments Pole With Shroud Or No Appurtenances Outside and Inside Corner Radii Are Known
--	---	--

Tapered Pole Section Geometry

Section	Elevation ft	Section Length ft	Splice Length ft	Number of Sides	Top Diameter in	Bottom Diameter in	Wall Thickness in	Bend Radius in	Pole Grade
L1	98.000-78.500	19.500	0.000	Round	8.625	8.625	0.465		A500-42 (42 ksi)

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job 21007.69 vZw Bridgeport NE CT	Page 2 of 32
	Project 98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date 11:45:36 11/19/21
	Client Verizon Wireless	Designed by TJL

Section	Elevation ft	Section Length ft	Splice Length ft	Number of Sides	Top Diameter in	Bottom Diameter in	Wall Thickness in	Bend Radius in	Pole Grade
L2	78.500-78.000	0.500	0.000	Round	8.625	10.750	0.465		A500-42 (42 ksi)
L3	78.000-68.500	9.500	0.000	Round	10.750	10.750	0.465		A500-42 (42 ksi)
L4	68.500-68.000	0.500	0.000	Round	10.750	35.500	0.465		A500-42 (42 ksi)
L5	68.000-38.250	29.750	5.500	18	35.500	40.020	0.250	1.000	A572-65 (65 ksi)
L6	38.250-1.000	42.750		18	38.684	45.000	0.250	1.000	A572-65 (65 ksi)

Tapered Pole Properties

Section	Tip Dia. in	Area in ²	I in ⁴	r in	C in	I/C in ³	J in ⁴	It/Q in ²	w in	w/t
L1	8.625	11.920	99.539	2.890	4.313	23.081	199.077	5.957	0.000	0
L2	8.625	11.920	99.539	2.890	4.313	23.081	199.077	5.957	0.000	0
L3	10.750	15.025	199.073	3.640	5.375	37.037	398.146	7.508	0.000	0
L4	10.750	15.025	199.073	3.640	5.375	37.037	398.146	7.508	0.000	0
L5	35.500	51.181	7854.087	12.388	17.750	442.484	15708.174	25.575	0.000	0
L6	36.009	27.971	4390.983	12.514	18.034	243.484	8787.744	13.988	5.808	23.232
	40.599	31.557	6305.959	14.118	20.330	310.178	12620.216	15.782	6.604	26.414
	40.068	30.498	5691.722	13.644	19.652	289.631	11390.933	15.252	6.368	25.474
	45.656	35.509	8983.871	15.886	22.860	392.995	17979.563	17.758	7.480	29.92

Tower Elevation ft	Gusset Area (per face) ft ²	Gusset Thickness in	Gusset Grade	Adjust. Factor A _f	Adjust. Factor A _r	Weight Mult.	Double Angle Stitch Bolt Spacing Diagonals in	Double Angle Stitch Bolt Spacing Horizontals in	Double Angle Stitch Bolt Spacing Redundants in
L1 98.000-78.500				0	1	1			
L2 78.500-78.000				0	1	1			
L3 78.000-68.500				0	1	1			
L4 68.500-68.000				0	1	1			
L5 68.000-38.250				1	1	1			
L6 38.250-1.000				1	1	1			

Feed Line/Linear Appurtenances - Entered As Area

Description	Face or Leg	Allow Shield	Exclude From Torque Calculation	Component Type	Placement ft	Total Number	C _{AA} ft ² /ft	Weight klf
-------------	-------------------	-----------------	--	-------------------	-----------------	-----------------	--	---------------

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job 21007.69 vZw Bridgeport NE CT	Page 3 of 32
	Project 98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date 11:45:36 11/19/21
	Client Verizon Wireless	Designed by TJL

Description	Face or Leg	Allow Shield	Exclude From Torque Calculation	Component Type	Placement ft	Total Number		C _A A _A ft ² /ft	Weight klf
LDF5-50A (7/8 FOAM) (Verizon)	C	No	Yes	Inside Pole	93.000 - 5.000	18	No Ice	0.000	0.000
							1/2" Ice	0.000	0.000
							1" Ice	0.000	0.000
LDF5-50A (7/8 FOAM) (Verizon)	C	No	Yes	Inside Pole	83.000 - 5.000	18	No Ice	0.000	0.000
							1/2" Ice	0.000	0.000
							1" Ice	0.000	0.000
LDF5-50A (7/8 FOAM) (Verizon)	C	No	Yes	Inside Pole	73.000 - 5.000	18	No Ice	0.000	0.000
							1/2" Ice	0.000	0.000
							1" Ice	0.000	0.000

Feed Line/Linear Appurtenances Section Areas

Tower Section	Tower Elevation ft	Face	A _R ft ²	A _F ft ²	C _A A _A In Face ft ²	C _A A _A Out Face ft ²	Weight K
L1	98.000-78.500	A	0.000	0.000	0.000	0.000	0.000
		B	0.000	0.000	0.000	0.000	0.000
		C	0.000	0.000	0.000	0.000	0.113
L2	78.500-78.000	A	0.000	0.000	0.000	0.000	0.000
		B	0.000	0.000	0.000	0.000	0.000
		C	0.000	0.000	0.000	0.000	0.006
L3	78.000-68.500	A	0.000	0.000	0.000	0.000	0.000
		B	0.000	0.000	0.000	0.000	0.000
		C	0.000	0.000	0.000	0.000	0.140
L4	68.500-68.000	A	0.000	0.000	0.000	0.000	0.000
		B	0.000	0.000	0.000	0.000	0.000
		C	0.000	0.000	0.000	0.000	0.009
L5	68.000-38.250	A	0.000	0.000	0.000	0.000	0.000
		B	0.000	0.000	0.000	0.000	0.000
		C	0.000	0.000	0.000	0.000	0.530
L6	38.250-1.000	A	0.000	0.000	0.000	0.000	0.000
		B	0.000	0.000	0.000	0.000	0.000
		C	0.000	0.000	0.000	0.000	0.593

Feed Line/Linear Appurtenances Section Areas - With Ice

Tower Section	Tower Elevation ft	Face or Leg	Ice Thickness in	A _R ft ²	A _F ft ²	C _A A _A In Face ft ²	C _A A _A Out Face ft ²	Weight K
L1	98.000-78.500	A	1.655	0.000	0.000	0.000	0.000	0.000
		B		0.000	0.000	0.000	0.000	0.000
		C		0.000	0.000	0.000	0.000	0.113
L2	78.500-78.000	A	1.635	0.000	0.000	0.000	0.000	0.000
		B		0.000	0.000	0.000	0.000	0.000
		C		0.000	0.000	0.000	0.000	0.006
L3	78.000-68.500	A	1.625	0.000	0.000	0.000	0.000	0.000
		B		0.000	0.000	0.000	0.000	0.000
		C		0.000	0.000	0.000	0.000	0.140
L4	68.500-68.000	A	1.613	0.000	0.000	0.000	0.000	0.000
		B		0.000	0.000	0.000	0.000	0.000
		C		0.000	0.000	0.000	0.000	0.009

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job 21007.69 vZw Bridgeport NE CT	Page 4 of 32
	Project 98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date 11:45:36 11/19/21
	Client Verizon Wireless	Designed by TJL

Tower Section	Tower Elevation ft	Face or Leg	Ice Thickness in	A _R ft ²	A _F ft ²	C _{AA} In Face ft ²	C _{AA} Out Face ft ²	Weight K
L5	68.000-38.250	A	1.572	0.000	0.000	0.000	0.000	0.000
		B		0.000	0.000	0.000	0.000	0.000
		C		0.000	0.000	0.000	0.000	0.530
L6	38.250-1.000	A	1.426	0.000	0.000	0.000	0.000	0.000
		B		0.000	0.000	0.000	0.000	0.000
		C		0.000	0.000	0.000	0.000	0.593

Feed Line Center of Pressure

Section	Elevation ft	CP _X in	CP _Z in	CP _X Ice in	CP _Z Ice in
L1	98.000-78.500	0.000	0.000	0.000	0.000
L2	78.500-78.000	0.000	0.000	0.000	0.000
L3	78.000-68.500	0.000	0.000	0.000	0.000
L4	68.500-68.000	0.000	0.000	0.000	0.000
L5	68.000-38.250	0.000	0.000	0.000	0.000
L6	38.250-1.000	0.000	0.000	0.000	0.000

Note: For pole sections, center of pressure calculations do not consider feed line shielding.

Discrete Tower Loads

Description	Face or Leg	Offset Type	Offsets: Horz Lateral Vert ft ft ft	Azimuth Adjustment °	Placement ft	C _{AA} Front ft ²	C _{AA} Side ft ²	Weight K	
MX08FIT265-01 (Verizon - Proposed)	A	From Face	0.500	0.000	82.000	No Ice	3.123	1.411	0.027
			0.000			1/2" Ice	3.359	1.613	0.047
			0.000			1" Ice	3.603	1.821	0.070
MX08FIT265-01 (Verizon - Proposed)	B	From Face	0.500	0.000	82.000	No Ice	3.123	1.411	0.027
			0.000			1/2" Ice	3.359	1.613	0.047
			0.000			1" Ice	3.603	1.821	0.070
MX08FIT265-01 (Verizon - Proposed)	C	From Face	0.500	0.000	82.000	No Ice	3.123	1.411	0.027
			0.000			1/2" Ice	3.359	1.613	0.047
			0.000			1" Ice	3.603	1.821	0.070
NNH4-65B-R6 (Verizon - Proposed)	A	From Face	0.500	0.000	92.000	No Ice	12.268	5.721	0.083
			0.000			1/2" Ice	12.763	6.178	0.155
			0.000			1" Ice	13.265	6.642	0.234
NNH4-65B-R6 (Verizon - Proposed)	B	From Face	0.500	0.000	92.000	No Ice	12.268	5.721	0.083
			0.000			1/2" Ice	12.763	6.178	0.155
			0.000			1" Ice	13.265	6.642	0.234
NNH4-65B-R6 (Verizon - Proposed)	C	From Face	0.500	0.000	92.000	No Ice	12.268	5.721	0.083
			0.000			1/2" Ice	12.763	6.178	0.155
			0.000			1" Ice	13.265	6.642	0.234
(2) CBC61923T-DS-43 Diplexer (Verizon - Proposed)	A	From Face	0.500	0.000	92.000	No Ice	0.449	0.265	0.014
			0.000			1/2" Ice	0.534	0.332	0.019
			0.000			1" Ice	0.627	0.407	0.025

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job 21007.69 vZw Bridgeport NE CT	Page 5 of 32
	Project 98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date 11:45:36 11/19/21
	Client Verizon Wireless	Designed by TJL

Description	Face or Leg	Offset Type	Offsets: Horz Lateral Vert	Azimuth Adjustment	Placement	C _{AA} Front	C _{AA} Side	Weight	
			ft ft ft	°	ft	ft ²	ft ²	K	
(2) CBC61923T-DS-43 - Diplexer (Verizon - Proposed)	B	From Face	0.500 0.000 0.000	0.000	92.000	No Ice 1/2" Ice 1" Ice	0.449 0.534 0.627	0.265 0.332 0.407	0.014 0.019 0.025
(2) CBC61923T-DS-43 - Diplexer (Verizon - Proposed)	C	From Face	0.500 0.000 0.000	0.000	92.000	No Ice 1/2" Ice 1" Ice	0.449 0.534 0.627	0.265 0.332 0.407	0.014 0.019 0.025
RT-8808-77A (Verizon - Proposed)	A	From Face	0.500 0.000 0.000	0.000	82.000	No Ice 1/2" Ice 1" Ice	1.875 2.045 2.223	0.850 0.975 1.107	0.060 0.075 0.092
RT-8808-77A (Verizon - Proposed)	B	From Face	0.500 0.000 0.000	0.000	82.000	No Ice 1/2" Ice 1" Ice	1.875 2.045 2.223	0.850 0.975 1.107	0.060 0.075 0.092
RT-8808-77A (Verizon - Proposed)	C	From Face	0.500 0.000 0.000	0.000	82.000	No Ice 1/2" Ice 1" Ice	1.875 2.045 2.223	0.850 0.975 1.107	0.060 0.075 0.092
10'x48" Canister	C	From Face	0.000 0.000 0.000	0.000	98.000 - 88.000	No Ice 1/2" Ice 1" Ice	20.000 28.822 29.653	20.000 28.822 29.653	0.400 0.757 1.126
10'x48" Canister	C	From Face	0.000 0.000 0.000	0.000	88.000 - 78.000	No Ice 1/2" Ice 1" Ice	20.000 28.822 29.653	20.000 28.822 29.653	0.400 0.757 1.126
10'x36" Canister	C	From Face	0.000 0.000 0.000	0.000	78.000 - 68.000	No Ice 1/2" Ice 1" Ice	15.556 22.295 23.044	15.556 22.295 23.044	0.350 0.608 0.876
RRFDC-3315-PF-48 (Verizon - Proposed)	C	From Face	0.500 0.000 0.000	0.000	92.000	No Ice 1/2" Ice 1" Ice	3.015 3.234 3.460	1.965 2.153 2.349	0.025 0.051 0.081

Tower Pressures - No Ice

$G_H = 1.100$

Section Elevation	z	K _z	q _z	A _G	F _a	A _F	A _R	A _{leg}	Leg %	C _{AA} In Face	C _{AA} Out Face
ft	ft		ksf	ft ²	e	ft ²	ft ²	ft ²		ft ²	ft ²
L1 98.000-78.500	88.250	1.233	0.028	14.016	A B C	0.000 0.000 0.000	14.016 14.016 14.016	14.016	100.00 100.00 100.00	0.000 0.000 0.000	0.000 0.000 0.000
L2 78.500-78.000	78.241	1.202	0.028	0.404	A B C	0.000 0.000 0.000	0.404 0.404 0.404	0.404	100.00 100.00 100.00	0.000 0.000 0.000	0.000 0.000 0.000
L3 78.000-68.500	73.250	1.185	0.027	8.510	A B C	0.000 0.000 0.000	8.510 8.510 8.510	8.510	100.00 100.00 100.00	0.000 0.000 0.000	0.000 0.000 0.000
L4 68.500-68.000	68.205	1.168	0.027	0.964	A B C	0.000 0.000 0.000	0.964 0.964 0.964	0.964	100.00 100.00 100.00	0.000 0.000 0.000	0.000 0.000 0.000
L5 68.000-38.250	52.828	1.107	0.025	94.962	A B	0.000 0.000	94.962 94.962	94.962	100.00 100.00	0.000 0.000	0.000 0.000

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job 21007.69 vZw Bridgeport NE CT	Page 6 of 32
	Project 98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date 11:45:36 11/19/21
	Client Verizon Wireless	Designed by TJL

Section Elevation	z	K _Z	q _z	A _G	F a c e	A _F	A _R	A _{leg}	Leg %	C _{AA} In Face	C _{AA} Out Face
ft	ft		ksf	ft ²	e	ft ²	ft ²	ft ²		ft ²	ft ²
L6 38.250-1.000	19.854	0.9	0.021	133.050	C	0.000	94.962		100.00	0.000	0.000
					A	0.000	133.050	133.050	100.00	0.000	0.000
					B	0.000	133.050		100.00	0.000	0.000
					C	0.000	133.050		100.00	0.000	0.000

Tower Pressure - With Ice

$G_H = 1.100$

Section Elevation	z	K _Z	q _z	t _z	A _G	F a c e	A _F	A _R	A _{leg}	Leg %	C _{AA} In Face	C _{AA} Out Face
ft	ft		ksf	in	ft ²	e	ft ²	ft ²	ft ²		ft ²	ft ²
L1 98.000-78.500	88.250	1.233	0.007	1.655	19.395	A	0.000	19.395	19.395	100.00	0.000	0.000
						B	0.000	19.395		100.00	0.000	0.000
						C	0.000	19.395		100.00	0.000	0.000
L2 78.500-78.000	78.241	1.202	0.007	1.635	0.540	A	0.000	0.540	0.540	100.00	0.000	0.000
						B	0.000	0.540		100.00	0.000	0.000
						C	0.000	0.540		100.00	0.000	0.000
L3 78.000-68.500	73.250	1.185	0.007	1.625	11.083	A	0.000	11.083	11.083	100.00	0.000	0.000
						B	0.000	11.083		100.00	0.000	0.000
						C	0.000	11.083		100.00	0.000	0.000
L4 68.500-68.000	68.205	1.168	0.007	1.613	1.098	A	0.000	1.098	1.098	100.00	0.000	0.000
						B	0.000	1.098		100.00	0.000	0.000
						C	0.000	1.098		100.00	0.000	0.000
L5 68.000-38.250	52.828	1.107	0.007	1.572	102.758	A	0.000	102.758	102.758	100.00	0.000	0.000
						B	0.000	102.758		100.00	0.000	0.000
						C	0.000	102.758		100.00	0.000	0.000
L6 38.250-1.000	19.854	0.9	0.006	1.426	142.811	A	0.000	142.811	142.811	100.00	0.000	0.000
						B	0.000	142.811		100.00	0.000	0.000
						C	0.000	142.811		100.00	0.000	0.000

Tower Pressure - Service

$G_H = 1.100$

Section Elevation	z	K _Z	q _z	A _G	F a c e	A _F	A _R	A _{leg}	Leg %	C _{AA} In Face	C _{AA} Out Face
ft	ft		ksf	ft ²	e	ft ²	ft ²	ft ²		ft ²	ft ²
L1 98.000-78.500	88.250	1.233	0.010	14.016	A	0.000	14.016	14.016	100.00	0.000	0.000
					B	0.000	14.016		100.00	0.000	0.000
					C	0.000	14.016		100.00	0.000	0.000
L2 78.500-78.000	78.241	1.202	0.009	0.404	A	0.000	0.404	0.404	100.00	0.000	0.000
					B	0.000	0.404		100.00	0.000	0.000
					C	0.000	0.404		100.00	0.000	0.000
L3 78.000-68.500	73.250	1.185	0.009	8.510	A	0.000	8.510	8.510	100.00	0.000	0.000
					B	0.000	8.510		100.00	0.000	0.000
					C	0.000	8.510		100.00	0.000	0.000
L4 68.500-68.000	68.205	1.168	0.009	0.964	A	0.000	0.964	0.964	100.00	0.000	0.000
					B	0.000	0.964		100.00	0.000	0.000
					C	0.000	0.964		100.00	0.000	0.000

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job 21007.69 vZw Bridgeport NE CT	Page 7 of 32
	Project 98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date 11:45:36 11/19/21
	Client Verizon Wireless	Designed by TJL

Section Elevation	z	K _Z	q _z	A _G	F _a c e	A _F	A _R	A _{leg}	Leg %	C _{AA} In Face ft ²	C _{AA} Out Face ft ²
ft	ft		ksf	ft ²		ft ²	ft ²	ft ²			
L5 68.000-38.250	52.828	1.107	0.009	94.962	A	0.000	94.962	94.962	100.00	0.000	0.000
					B	0.000	94.962		100.00	0.000	0.000
					C	0.000	94.962		100.00	0.000	0.000
L6 38.250-1.000	19.854	0.9	0.007	133.050	A	0.000	133.050	133.050	100.00	0.000	0.000
					B	0.000	133.050		100.00	0.000	0.000
					C	0.000	133.050		100.00	0.000	0.000

Tower Forces - No Ice - Wind Normal To Face

Section Elevation	Add Weight	Self Weight	F _a c e	e	C _F	q _z	D _F	D _R	A _E	F	w	Ctrl. Face
ft	K	K				ksf			ft ²	K	klf	
L1 98.000-78.500	0.113	0.791	A	1	0.6	0.028	1	1	14.016	0.261	0.013	C
			B	1	0.6		1	1	14.016			
			C	1	0.6		1	1	14.016			
L2 78.500-78.000	0.006	0.023	A	1	0.6	0.028	1	1	0.404	0.007	0.015	C
			B	1	0.6		1	1	0.404			
			C	1	0.6		1	1	0.404			
L3 78.000-68.500	0.140	0.486	A	1	0.6	0.027	1	1	8.510	0.152	0.016	C
			B	1	0.6		1	1	8.510			
			C	1	0.6		1	1	8.510			
L4 68.500-68.000	0.009	0.056	A	1	0.6	0.027	1	1	0.964	0.017	0.034	C
			B	1	0.6		1	1	0.964			
			C	1	0.6		1	1	0.964			
L5 68.000-38.250	0.530	3.013	A	1	0.65	0.025	1	1	94.962	1.719	0.058	C
			B	1	0.65		1	1	94.962			
			C	1	0.65		1	1	94.962			
L6 38.250-1.000	0.593	4.801	A	1	0.65	0.021	1	1	133.050	1.981	0.053	C
			B	1	0.65		1	1	133.050			
			C	1	0.65		1	1	133.050			
Sum Weight:	1.390	9.170						OTM	161.934 kip-ft	4.138		

Tower Forces - No Ice - Wind 45 To Face

Section Elevation	Add Weight	Self Weight	F _a c e	e	C _F	q _z	D _F	D _R	A _E	F	w	Ctrl. Face
ft	K	K				ksf			ft ²	K	klf	
L1 98.000-78.500	0.113	0.791	A	1	0.6	0.028	1	1	14.016	0.261	0.013	C
			B	1	0.6		1	1	14.016			
			C	1	0.6		1	1	14.016			
L2 78.500-78.000	0.006	0.023	A	1	0.6	0.028	1	1	0.404	0.007	0.015	C
			B	1	0.6		1	1	0.404			
			C	1	0.6		1	1	0.404			
L3 78.000-68.500	0.140	0.486	A	1	0.6	0.027	1	1	8.510	0.152	0.016	C
			B	1	0.6		1	1	8.510			
			C	1	0.6		1	1	8.510			
L4 68.500-68.000	0.009	0.056	A	1	0.6	0.027	1	1	0.964	0.017	0.034	C
			B	1	0.6		1	1	0.964			

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job 21007.69 vZw Bridgeport NE CT	Page 8 of 32
	Project 98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date 11:45:36 11/19/21
	Client Verizon Wireless	Designed by T.JL

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	q _z	D _F	D _R	A _E	F	w	Ctrl. Face
ft	K	K	e			ksf			ft ²	K	klf	
L5 68.000-38.250	0.530	3.013	C	1	0.6	0.025	1	1	0.964	1.719	0.058	C
			A	1	0.65		1	1	94.962			
			B	1	0.65		1	1	94.962			
L6 38.250-1.000	0.593	4.801	C	1	0.65	0.021	1	1	94.962	1.981	0.053	C
			A	1	0.65		1	1	133.050			
			B	1	0.65		1	1	133.050			
Sum Weight:	1.390	9.170	C	1	0.65			1	133.050	4.138		
								OTM	161.934 kip-ft			

Tower Forces - No Ice - Wind 60 To Face

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	q _z	D _F	D _R	A _E	F	w	Ctrl. Face
ft	K	K	e			ksf			ft ²	K	klf	
L1 98.000-78.500	0.113	0.791	A	1	0.6	0.028	1	1	14.016	0.261	0.013	C
			B	1	0.6		1	1	14.016			
			C	1	0.6		1	1	14.016			
L2 78.500-78.000	0.006	0.023	A	1	0.6	0.028	1	1	0.404	0.007	0.015	C
			B	1	0.6		1	1	0.404			
			C	1	0.6		1	1	0.404			
L3 78.000-68.500	0.140	0.486	A	1	0.6	0.027	1	1	8.510	0.152	0.016	C
			B	1	0.6		1	1	8.510			
			C	1	0.6		1	1	8.510			
L4 68.500-68.000	0.009	0.056	A	1	0.6	0.027	1	1	0.964	0.017	0.034	C
			B	1	0.6		1	1	0.964			
			C	1	0.6		1	1	0.964			
L5 68.000-38.250	0.530	3.013	A	1	0.65	0.025	1	1	94.962	1.719	0.058	C
			B	1	0.65		1	1	94.962			
			C	1	0.65		1	1	94.962			
L6 38.250-1.000	0.593	4.801	A	1	0.65	0.021	1	1	133.050	1.981	0.053	C
			B	1	0.65		1	1	133.050			
			C	1	0.65		1	1	133.050			
Sum Weight:	1.390	9.170	C	1	0.65			1	161.934 kip-ft	4.138		
								OTM				

Tower Forces - No Ice - Wind 90 To Face

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	q _z	D _F	D _R	A _E	F	w	Ctrl. Face
ft	K	K	e			ksf			ft ²	K	klf	
L1 98.000-78.500	0.113	0.791	A	1	0.6	0.028	1	1	14.016	0.261	0.013	C
			B	1	0.6		1	1	14.016			
			C	1	0.6		1	1	14.016			
L2 78.500-78.000	0.006	0.023	A	1	0.6	0.028	1	1	0.404	0.007	0.015	C
			B	1	0.6		1	1	0.404			
			C	1	0.6		1	1	0.404			

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job 21007.69 vZw Bridgeport NE CT	Page 9 of 32
	Project 98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date 11:45:36 11/19/21
	Client Verizon Wireless	Designed by TJJ

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	q _z	D _F	D _R	A _E	F	w	Ctrl. Face
ft	K	K	e			ksf			ft ²	K	klf	
L3 78.000-68.500	0.140	0.486	A	1	0.6	0.027	1	1	8.510	0.152	0.016	C
			B	1	0.6		1	1	8.510			
			C	1	0.6		1	1	8.510			
L4 68.500-68.000	0.009	0.056	A	1	0.6	0.027	1	1	0.964	0.017	0.034	C
			B	1	0.6		1	1	0.964			
			C	1	0.6		1	1	0.964			
L5 68.000-38.250	0.530	3.013	A	1	0.65	0.025	1	1	94.962	1.719	0.058	C
			B	1	0.65		1	1	94.962			
			C	1	0.65		1	1	94.962			
L6 38.250-1.000	0.593	4.801	A	1	0.65	0.021	1	1	133.050	1.981	0.053	C
			B	1	0.65		1	1	133.050			
			C	1	0.65		1	1	133.050			
Sum Weight:	1.390	9.170						OTM	161.934 kip-ft	4.138		

Tower Forces - With Ice - Wind Normal To Face

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	q _z	D _F	D _R	A _E	F	w	Ctrl. Face
ft	K	K	e			ksf			ft ²	K	klf	
L1 98.000-78.500	0.113	1.196	A	1	1.2	0.007	1	1	19.395	0.192	0.010	C
			B	1	1.2		1	1	19.395			
			C	1	1.2		1	1	19.395			
L2 78.500-78.000	0.006	0.034	A	1	1.2	0.007	1	1	0.540	0.005	0.010	C
			B	1	1.2		1	1	0.540			
			C	1	1.2		1	1	0.540			
L3 78.000-68.500	0.140	0.719	A	1	1.2	0.007	1	1	11.083	0.105	0.011	C
			B	1	1.2		1	1	11.083			
			C	1	1.2		1	1	11.083			
L4 68.500-68.000	0.009	0.081	A	1	1.2	0.007	1	1	1.098	0.010	0.021	C
			B	1	1.2		1	1	1.098			
			C	1	1.2		1	1	1.098			
L5 68.000-38.250	0.530	5.284	A	1	1.2	0.007	1	1	102.758	0.913	0.031	C
			B	1	1.2		1	1	102.758			
			C	1	1.2		1	1	102.758			
L6 38.250-1.000	0.593	7.664	A	1	1.2	0.006	1	1	141.901	1.036	0.028	C
			B	1	1.2		1	1	141.901			
			C	1	1.2		1	1	141.901			
Sum Weight:	1.390	14.978						OTM	92.288 kip-ft	2.262		

Tower Forces - With Ice - Wind 45 To Face

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	q _z	D _F	D _R	A _E	F	w	Ctrl. Face
ft	K	K	e			ksf			ft ²	K	klf	
L1	0.113	1.196	A	1	1.2	0.007	1	1	19.395	0.192	0.010	C

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job	21007.69 vZw Bridgeport NE CT	Page	10 of 32	
	Project	98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610		Date	11:45:36 11/19/21
	Client	Verizon Wireless		Designed by	TJL

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	q _z	D _F	D _R	A _E	F	w	Ctrl. Face
ft	K	K				ksf			ft ²	K	klf	
98.000-78.500			B	1	1.2		1	1	19.395			
			C	1	1.2		1	1	19.395			
L2	0.006	0.034	A	1	1.2	0.007	1	1	0.540	0.005	0.010	C
78.500-78.000			B	1	1.2		1	1	0.540			
			C	1	1.2		1	1	0.540			
L3	0.140	0.719	A	1	1.2	0.007	1	1	11.083	0.105	0.011	C
78.000-68.500			B	1	1.2		1	1	11.083			
			C	1	1.2		1	1	11.083			
L4	0.009	0.081	A	1	1.2	0.007	1	1	1.098	0.010	0.021	C
68.500-68.000			B	1	1.2		1	1	1.098			
			C	1	1.2		1	1	1.098			
L5	0.530	5.284	A	1	1.2	0.007	1	1	102.758	0.913	0.031	C
68.000-38.250			B	1	1.2		1	1	102.758			
			C	1	1.2		1	1	102.758			
L6	0.593	7.664	A	1	1.2	0.006	1	1	141.901	1.036	0.028	C
38.250-1.000			B	1	1.2		1	1	141.901			
			C	1	1.2		1	1	141.901			
Sum Weight:	1.390	14.978						OTM	92.288 kip-ft	2.262		

Tower Forces - With Ice - Wind 60 To Face

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	q _z	D _F	D _R	A _E	F	w	Ctrl. Face
ft	K	K				ksf			ft ²	K	klf	
L1	0.113	1.196	A	1	1.2	0.007	1	1	19.395	0.192	0.010	C
98.000-78.500			B	1	1.2		1	1	19.395			
			C	1	1.2		1	1	19.395			
L2	0.006	0.034	A	1	1.2	0.007	1	1	0.540	0.005	0.010	C
78.500-78.000			B	1	1.2		1	1	0.540			
			C	1	1.2		1	1	0.540			
L3	0.140	0.719	A	1	1.2	0.007	1	1	11.083	0.105	0.011	C
78.000-68.500			B	1	1.2		1	1	11.083			
			C	1	1.2		1	1	11.083			
L4	0.009	0.081	A	1	1.2	0.007	1	1	1.098	0.010	0.021	C
68.500-68.000			B	1	1.2		1	1	1.098			
			C	1	1.2		1	1	1.098			
L5	0.530	5.284	A	1	1.2	0.007	1	1	102.758	0.913	0.031	C
68.000-38.250			B	1	1.2		1	1	102.758			
			C	1	1.2		1	1	102.758			
L6	0.593	7.664	A	1	1.2	0.006	1	1	141.901	1.036	0.028	C
38.250-1.000			B	1	1.2		1	1	141.901			
			C	1	1.2		1	1	141.901			
Sum Weight:	1.390	14.978						OTM	92.288 kip-ft	2.262		

Tower Forces - With Ice - Wind 90 To Face

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job 21007.69 vZw Bridgeport NE CT	Page 11 of 32
	Project 98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date 11:45:36 11/19/21
	Client Verizon Wireless	Designed by TJL

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	q _z	D _F	D _R	A _E	F	w	Ctrl. Face
ft	K	K				ksf			ft ²	K	klf	
L1	0.113	1.196	A	1	1.2	0.007	1	1	19.395	0.192	0.010	C
98.000-78.500			B	1	1.2		1	1	19.395			
			C	1	1.2		1	1	19.395			
L2	0.006	0.034	A	1	1.2	0.007	1	1	0.540	0.005	0.010	C
78.500-78.000			B	1	1.2		1	1	0.540			
			C	1	1.2		1	1	0.540			
L3	0.140	0.719	A	1	1.2	0.007	1	1	11.083	0.105	0.011	C
78.000-68.500			B	1	1.2		1	1	11.083			
			C	1	1.2		1	1	11.083			
L4	0.009	0.081	A	1	1.2	0.007	1	1	1.098	0.010	0.021	C
68.500-68.000			B	1	1.2		1	1	1.098			
			C	1	1.2		1	1	1.098			
L5	0.530	5.284	A	1	1.2	0.007	1	1	102.758	0.913	0.031	C
68.000-38.250			B	1	1.2		1	1	102.758			
			C	1	1.2		1	1	102.758			
L6	0.593	7.664	A	1	1.2	0.006	1	1	141.901	1.036	0.028	C
38.250-1.000			B	1	1.2		1	1	141.901			
			C	1	1.2		1	1	141.901			
Sum Weight:	1.390	14.978						OTM	92.288	2.262		
									kip-ft			

Tower Forces - Service - Wind Normal To Face

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	q _z	D _F	D _R	A _E	F	w	Ctrl. Face
ft	K	K				ksf			ft ²	K	klf	
L1	0.113	0.791	A	1	0.802	0.010	1	1	14.016	0.119	0.006	C
98.000-78.500			B	1	0.802		1	1	14.016			
			C	1	0.802		1	1	14.016			
L2	0.006	0.023	A	1	0.723	0.009	1	1	0.404	0.003	0.006	C
78.500-78.000			B	1	0.723		1	1	0.404			
			C	1	0.723		1	1	0.404			
L3	0.140	0.486	A	1	0.656	0.009	1	1	8.510	0.057	0.006	C
78.000-68.500			B	1	0.656		1	1	8.510			
			C	1	0.656		1	1	8.510			
L4	0.009	0.056	A	1	0.6	0.009	1	1	0.964	0.006	0.012	C
68.500-68.000			B	1	0.6		1	1	0.964			
			C	1	0.6		1	1	0.964			
L5	0.530	3.013	A	1	0.65	0.009	1	1	94.962	0.589	0.020	C
68.000-38.250			B	1	0.65		1	1	94.962			
			C	1	0.65		1	1	94.962			
L6	0.593	4.801	A	1	0.65	0.007	1	1	133.050	0.678	0.018	C
38.250-1.000			B	1	0.65		1	1	133.050			
			C	1	0.65		1	1	133.050			
Sum Weight:	1.390	9.170						OTM	58.452	1.452		
									kip-ft			

Tower Forces - Service - Wind 45 To Face

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job 21007.69 vZw Bridgeport NE CT	Page 12 of 32
	Project 98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date 11:45:36 11/19/21
	Client Verizon Wireless	Designed by TJJ

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	q _z	D _F	D _R	A _E	F	w	Ctrl. Face
ft	K	K				ksf			ft ²	K	klf	
L1 98.000-78.500	0.113	0.791	A	1	0.802	0.010	1	1	14.016	0.119	0.006	C
			B	1	0.802		1	1	14.016			
			C	1	0.802		1	1	14.016			
L2 78.500-78.000	0.006	0.023	A	1	0.723	0.009	1	1	0.404	0.003	0.006	C
			B	1	0.723		1	1	0.404			
			C	1	0.723		1	1	0.404			
L3 78.000-68.500	0.140	0.486	A	1	0.656	0.009	1	1	8.510	0.057	0.006	C
			B	1	0.656		1	1	8.510			
			C	1	0.656		1	1	8.510			
L4 68.500-68.000	0.009	0.056	A	1	0.6	0.009	1	1	0.964	0.006	0.012	C
			B	1	0.6		1	1	0.964			
			C	1	0.6		1	1	0.964			
L5 68.000-38.250	0.530	3.013	A	1	0.65	0.009	1	1	94.962	0.589	0.020	C
			B	1	0.65		1	1	94.962			
			C	1	0.65		1	1	94.962			
L6 38.250-1.000	0.593	4.801	A	1	0.65	0.007	1	1	133.050	0.678	0.018	C
			B	1	0.65		1	1	133.050			
			C	1	0.65		1	1	133.050			
Sum Weight:	1.390	9.170						OTM	58.452 kip-ft	1.452		

Tower Forces - Service - Wind 60 To Face

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	q _z	D _F	D _R	A _E	F	w	Ctrl. Face
ft	K	K				ksf			ft ²	K	klf	
L1 98.000-78.500	0.113	0.791	A	1	0.802	0.010	1	1	14.016	0.119	0.006	C
			B	1	0.802		1	1	14.016			
			C	1	0.802		1	1	14.016			
L2 78.500-78.000	0.006	0.023	A	1	0.723	0.009	1	1	0.404	0.003	0.006	C
			B	1	0.723		1	1	0.404			
			C	1	0.723		1	1	0.404			
L3 78.000-68.500	0.140	0.486	A	1	0.656	0.009	1	1	8.510	0.057	0.006	C
			B	1	0.656		1	1	8.510			
			C	1	0.656		1	1	8.510			
L4 68.500-68.000	0.009	0.056	A	1	0.6	0.009	1	1	0.964	0.006	0.012	C
			B	1	0.6		1	1	0.964			
			C	1	0.6		1	1	0.964			
L5 68.000-38.250	0.530	3.013	A	1	0.65	0.009	1	1	94.962	0.589	0.020	C
			B	1	0.65		1	1	94.962			
			C	1	0.65		1	1	94.962			
L6 38.250-1.000	0.593	4.801	A	1	0.65	0.007	1	1	133.050	0.678	0.018	C
			B	1	0.65		1	1	133.050			
			C	1	0.65		1	1	133.050			
Sum Weight:	1.390	9.170						OTM	58.452 kip-ft	1.452		

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job 21007.69 vZw Bridgeport NE CT	Page 13 of 32
	Project 98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date 11:45:36 11/19/21
	Client Verizon Wireless	Designed by TJL

Tower Forces - Service - Wind 90 To Face

Section Elevation	Add Weight	Self Weight	F a c e	e	C _F	q _z	D _F	D _R	A _E	F	w	Ctrl. Face
ft	K	K				ksf			ft ²	K	klf	
98.000-78.500	0.113	0.791	A	1	0.802	0.010	1	1	14.016	0.119	0.006	C
			B	1	0.802	1	1	14.016				
			C	1	0.802	1	1	14.016				
78.500-78.000	0.006	0.023	A	1	0.723	0.009	1	1	0.404	0.003	0.006	C
			B	1	0.723	1	1	0.404				
			C	1	0.723	1	1	0.404				
78.000-68.500	0.140	0.486	A	1	0.656	0.009	1	1	8.510	0.057	0.006	C
			B	1	0.656	1	1	8.510				
			C	1	0.656	1	1	8.510				
68.500-68.000	0.009	0.056	A	1	0.6	0.009	1	1	0.964	0.006	0.012	C
			B	1	0.6	1	1	0.964				
			C	1	0.6	1	1	0.964				
68.000-38.250	0.530	3.013	A	1	0.65	0.009	1	1	94.962	0.589	0.020	C
			B	1	0.65	1	1	94.962				
			C	1	0.65	1	1	94.962				
38.250-1.000	0.593	4.801	A	1	0.65	0.007	1	1	133.050	0.678	0.018	C
			B	1	0.65	1	1	133.050				
			C	1	0.65	1	1	133.050				
Sum Weight:	1.390	9.170					OTM	58.452	1.452			

Force Totals

Load Case	Vertical Forces	Sum of Forces X	Sum of Forces Z	Sum of Overturning Moments, M _x	Sum of Overturning Moments, M _z	Sum of Torques
	K	K	K	kip-ft	kip-ft	kip-ft
Leg Weight	9.170					
Bracing Weight	0.000					
Total Member Self-Weight	9.170			0.476	0.000	
Total Weight	12.329			0.476	0.000	
Wind 0 deg - No Ice		0.000	-7.180	-421.310	0.000	0.000
Wind 30 deg - No Ice		3.574	-6.218	-364.801	-209.397	0.360
Wind 45 deg - No Ice		5.054	-5.077	-297.772	-296.132	0.509
Wind 60 deg - No Ice		6.190	-3.590	-210.417	-362.686	0.623
Wind 90 deg - No Ice		7.147	0.000	0.476	-418.794	0.720
Wind 120 deg - No Ice		6.190	3.590	211.368	-362.686	0.623
Wind 135 deg - No Ice		5.054	5.077	298.723	-296.132	0.509
Wind 150 deg - No Ice		3.574	6.218	365.753	-209.397	0.360
Wind 180 deg - No Ice		0.000	7.180	422.261	0.000	0.000
Wind 210 deg - No Ice		-3.574	6.218	365.753	209.397	-0.360
Wind 225 deg - No Ice		-5.054	5.077	298.723	296.132	-0.509
Wind 240 deg - No Ice		-6.190	3.590	211.368	362.686	-0.623
Wind 270 deg - No Ice		-7.147	0.000	0.476	418.794	-0.720
Wind 300 deg - No Ice		-6.190	-3.590	-210.417	362.686	-0.623
Wind 315 deg - No Ice		-5.054	-5.077	-297.772	296.132	-0.509
Wind 330 deg - No Ice		-3.574	-6.218	-364.801	209.397	-0.360
Member Ice	5.808			1.867	0.000	
Total Weight Ice	22.939			1.867	0.000	
Wind 0 deg - Ice		0.000	-3.406	-187.749	0.000	0.000
Wind 30 deg - Ice		1.698	-2.950	-162.345	-94.372	0.146

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job 21007.69 vZw Bridgeport NE CT	Page 14 of 32
	Project 98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date 11:45:36 11/19/21
	Client Verizon Wireless	Designed by T.J.L

Load Case	Vertical Forces K	Sum of Forces X K	Sum of Forces Z K	Sum of Overturning Moments, M _x kip-ft	Sum of Overturning Moments, M _y kip-ft	Sum of Torques kip-ft
Wind 45 deg - Ice		2.402	-2.408	-132.212	-133.462	0.206
Wind 60 deg - Ice		2.941	-1.703	-92.941	-163.457	0.252
Wind 90 deg - Ice		3.396	0.000	1.867	-188.744	0.291
Wind 120 deg - Ice		2.941	1.703	96.675	-163.457	0.252
Wind 135 deg - Ice		2.402	2.408	135.945	-133.462	0.206
Wind 150 deg - Ice		1.698	2.950	166.079	-94.372	0.146
Wind 180 deg - Ice		0.000	3.406	191.482	0.000	0.000
Wind 210 deg - Ice		-1.698	2.950	166.079	94.372	-0.146
Wind 225 deg - Ice		-2.402	2.408	135.945	133.462	-0.206
Wind 240 deg - Ice		-2.941	1.703	96.675	163.457	-0.252
Wind 270 deg - Ice		-3.396	0.000	1.867	188.744	-0.291
Wind 300 deg - Ice		-2.941	-1.703	-92.941	163.457	-0.252
Wind 315 deg - Ice		-2.402	-2.408	-132.212	133.462	-0.206
Wind 330 deg - Ice		-1.698	-2.950	-162.345	94.372	-0.146
Total Weight	12.329			0.476	0.000	
Wind 0 deg - Service		0.000	-2.494	-146.934	0.000	0.000
Wind 30 deg - Service		1.241	-2.159	-127.185	-73.193	0.123
Wind 45 deg - Service		1.755	-1.763	-103.759	-103.510	0.174
Wind 60 deg - Service		2.150	-1.247	-73.229	-126.773	0.213
Wind 90 deg - Service		2.482	0.000	0.476	-146.385	0.246
Wind 120 deg - Service		2.150	1.247	74.180	-126.773	0.213
Wind 135 deg - Service		1.755	1.763	104.710	-103.510	0.174
Wind 150 deg - Service		1.241	2.159	128.136	-73.193	0.123
Wind 180 deg - Service		0.000	2.494	147.885	0.000	0.000
Wind 210 deg - Service		-1.241	2.159	128.136	73.193	-0.123
Wind 225 deg - Service		-1.755	1.763	104.710	103.510	-0.174
Wind 240 deg - Service		-2.150	1.247	74.180	126.773	-0.213
Wind 270 deg - Service		-2.482	0.000	0.476	146.385	-0.246
Wind 300 deg - Service		-2.150	-1.247	-73.229	126.773	-0.213
Wind 315 deg - Service		-1.755	-1.763	-103.759	103.510	-0.174
Wind 330 deg - Service		-1.241	-2.159	-127.185	73.193	-0.123

Load Combinations

Comb. No.	Description
1	Dead Only
2	1.2 Dead+1.6 Wind 0 deg - No Ice
3	0.9 Dead+1.6 Wind 0 deg - No Ice
4	1.2 Dead+1.6 Wind 30 deg - No Ice
5	0.9 Dead+1.6 Wind 30 deg - No Ice
6	1.2 Dead+1.6 Wind 45 deg - No Ice
7	0.9 Dead+1.6 Wind 45 deg - No Ice
8	1.2 Dead+1.6 Wind 60 deg - No Ice
9	0.9 Dead+1.6 Wind 60 deg - No Ice
10	1.2 Dead+1.6 Wind 90 deg - No Ice
11	0.9 Dead+1.6 Wind 90 deg - No Ice
12	1.2 Dead+1.6 Wind 120 deg - No Ice
13	0.9 Dead+1.6 Wind 120 deg - No Ice
14	1.2 Dead+1.6 Wind 135 deg - No Ice
15	0.9 Dead+1.6 Wind 135 deg - No Ice
16	1.2 Dead+1.6 Wind 150 deg - No Ice
17	0.9 Dead+1.6 Wind 150 deg - No Ice
18	1.2 Dead+1.6 Wind 180 deg - No Ice
19	0.9 Dead+1.6 Wind 180 deg - No Ice
20	1.2 Dead+1.6 Wind 210 deg - No Ice

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job 21007.69 vZw Bridgeport NE CT	Page 15 of 32
	Project 98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date 11:45:36 11/19/21
	Client Verizon Wireless	Designed by TJL

Comb. No.	Description
21	0.9 Dead+1.6 Wind 210 deg - No Ice
22	1.2 Dead+1.6 Wind 225 deg - No Ice
23	0.9 Dead+1.6 Wind 225 deg - No Ice
24	1.2 Dead+1.6 Wind 240 deg - No Ice
25	0.9 Dead+1.6 Wind 240 deg - No Ice
26	1.2 Dead+1.6 Wind 270 deg - No Ice
27	0.9 Dead+1.6 Wind 270 deg - No Ice
28	1.2 Dead+1.6 Wind 300 deg - No Ice
29	0.9 Dead+1.6 Wind 300 deg - No Ice
30	1.2 Dead+1.6 Wind 315 deg - No Ice
31	0.9 Dead+1.6 Wind 315 deg - No Ice
32	1.2 Dead+1.6 Wind 330 deg - No Ice
33	0.9 Dead+1.6 Wind 330 deg - No Ice
34	1.2 Dead+1.0 Ice+1.0 Temp
35	1.2 Dead+1.0 Wind 0 deg+1.0 Ice+1.0 Temp
36	1.2 Dead+1.0 Wind 30 deg+1.0 Ice+1.0 Temp
37	1.2 Dead+1.0 Wind 45 deg+1.0 Ice+1.0 Temp
38	1.2 Dead+1.0 Wind 60 deg+1.0 Ice+1.0 Temp
39	1.2 Dead+1.0 Wind 90 deg+1.0 Ice+1.0 Temp
40	1.2 Dead+1.0 Wind 120 deg+1.0 Ice+1.0 Temp
41	1.2 Dead+1.0 Wind 135 deg+1.0 Ice+1.0 Temp
42	1.2 Dead+1.0 Wind 150 deg+1.0 Ice+1.0 Temp
43	1.2 Dead+1.0 Wind 180 deg+1.0 Ice+1.0 Temp
44	1.2 Dead+1.0 Wind 210 deg+1.0 Ice+1.0 Temp
45	1.2 Dead+1.0 Wind 225 deg+1.0 Ice+1.0 Temp
46	1.2 Dead+1.0 Wind 240 deg+1.0 Ice+1.0 Temp
47	1.2 Dead+1.0 Wind 270 deg+1.0 Ice+1.0 Temp
48	1.2 Dead+1.0 Wind 300 deg+1.0 Ice+1.0 Temp
49	1.2 Dead+1.0 Wind 315 deg+1.0 Ice+1.0 Temp
50	1.2 Dead+1.0 Wind 330 deg+1.0 Ice+1.0 Temp
51	Dead+ Wind 0 deg - Service
52	Dead+ Wind 30 deg - Service
53	Dead+ Wind 45 deg - Service
54	Dead+ Wind 60 deg - Service
55	Dead+ Wind 90 deg - Service
56	Dead+ Wind 120 deg - Service
57	Dead+ Wind 135 deg - Service
58	Dead+ Wind 150 deg - Service
59	Dead+ Wind 180 deg - Service
60	Dead+ Wind 210 deg - Service
61	Dead+ Wind 225 deg - Service
62	Dead+ Wind 240 deg - Service
63	Dead+ Wind 270 deg - Service
64	Dead+ Wind 300 deg - Service
65	Dead+ Wind 315 deg - Service
66	Dead+ Wind 330 deg - Service

Maximum Member Forces

Section No.	Elevation ft	Component Type	Condition	Gov. Load Comb.	Axial K	Major Axis Moment kip-ft	Minor Axis Moment kip-ft
L1	98 - 78.5	Pole	Max Tension	35	0.000	0.000	-0.000
			Max. Compression	34	-7.031	0.000	-1.372
			Max. Mx	10	-2.604	-47.048	-0.359
			Max. My	18	-2.599	0.000	-48.139
			Max. Vy	10	4.537	-47.048	-0.359
			Max. Vx	18	4.591	0.000	-48.139
			Max. Torque	10			-0.779

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job 21007.69 vZw Bridgeport NE CT	Page 16 of 32
	Project 98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date 11:45:36 11/19/21
	Client Verizon Wireless	Designed by TJJ

Section No.	Elevation ft	Component Type	Condition	Gov. Load Comb.	Axial K	Major Axis Moment kip-ft	Minor Axis Moment kip-ft
L2	78.5 - 78	Pole	Max Tension	1	0.000	0.000	0.000
			Max. Compression	34	-7.162	0.000	-1.409
			Max. Mx	10	-2.667	-49.331	-0.368
			Max. My	18	-2.663	0.000	-50.458
			Max. Vy	10	4.596	-49.331	-0.368
			Max. Vx	18	4.650	0.000	-50.458
			Max. Torque	10			-0.799
L3	78 - 68.5	Pole	Max Tension	1	0.000	0.000	0.000
			Max. Compression	34	-9.380	0.000	-1.986
			Max. Mx	10	-3.873	-97.425	-0.547
			Max. My	18	-3.871	0.000	-99.241
			Max. Vy	10	5.521	-97.425	-0.547
			Max. Vx	18	5.575	0.000	-99.241
			Max. Torque	10			-1.114
L4	68.5 - 68	Pole	Max Tension	1	0.000	0.000	0.000
			Max. Compression	34	-9.547	0.000	-2.049
			Max. Mx	10	-3.979	-100.198	-0.567
			Max. My	18	-3.977	0.000	-102.061
			Max. Vy	10	5.582	-100.198	-0.567
			Max. Vx	18	5.636	0.000	-102.061
			Max. Torque	10			-1.149
L5	68 - 38.25	Pole	Max Tension	1	0.000	0.000	0.000
			Max. Compression	34	-14.831	0.000	-2.051
			Max. Mx	10	-7.406	-262.410	-0.578
			Max. My	18	-7.404	0.000	-265.569
			Max. Vy	10	7.827	-262.410	-0.578
			Max. Vx	18	7.881	0.000	-265.569
			Max. Torque	10			-1.149
L6	38.25 - 1	Pole	Max Tension	1	0.000	0.000	0.000
			Max. Compression	34	-25.828	0.000	-2.051
			Max. Mx	10	-14.791	-677.192	-0.585
			Max. My	18	-14.791	0.000	-682.626
			Max. Vy	10	11.441	-677.192	-0.585
			Max. Vx	18	11.494	0.000	-682.626
			Max. Torque	10			-1.149

Maximum Reactions

Location	Condition	Gov. Load Comb.	Vertical K	Horizontal, X K	Horizontal, Z K
Pole	Max. Vert	43	25.828	0.000	-3.406
	Max. H _x	27	11.096	11.436	0.000
	Max. H _z	2	14.795	0.000	11.489
	Max. M _x	2	681.455	0.000	11.489
	Max. M _z	10	677.192	-11.436	0.000
	Max. Torsion	26	1.149	11.436	0.000
	Min. Vert	7	11.096	-8.086	8.124
	Min. H _x	10	14.795	-11.436	0.000
	Min. H _z	18	14.795	0.000	-11.489
	Min. M _x	18	-682.626	0.000	-11.489
	Min. M _z	26	-677.192	11.436	0.000
	Min. Torsion	10	-1.149	-11.436	0.000

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job 21007.69 vZw Bridgeport NE CT	Page 17 of 32
	Project 98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date 11:45:36 11/19/21
	Client Verizon Wireless	Designed by TJL

Tower Mast Reaction Summary

Load Combination	Vertical	Shear _x	Shear _y	Overturing Moment, M _x	Overturing Moment, M _y	Torque
	K	K	K	kip-ft	kip-ft	kip-ft
Dead Only	12.329	0.000	0.000	0.481	0.000	0.000
1.2 Dead+1.6 Wind 0 deg - No Ice	14.795	0.000	-11.489	-681.455	0.000	0.000
0.9 Dead+1.6 Wind 0 deg - No Ice	11.096	0.000	-11.489	-679.766	0.000	0.000
1.2 Dead+1.6 Wind 30 deg - No Ice	14.795	5.718	-9.949	-590.080	-338.595	0.574
0.9 Dead+1.6 Wind 30 deg - No Ice	11.096	5.718	-9.949	-588.637	-337.684	0.574
1.2 Dead+1.6 Wind 45 deg - No Ice	14.795	8.086	-8.124	-481.691	-478.846	0.812
0.9 Dead+1.6 Wind 45 deg - No Ice	11.096	8.086	-8.124	-480.540	-477.557	0.812
1.2 Dead+1.6 Wind 60 deg - No Ice	14.795	9.904	-5.744	-340.436	-586.464	0.995
0.9 Dead+1.6 Wind 60 deg - No Ice	11.096	9.904	-5.744	-339.666	-584.886	0.995
1.2 Dead+1.6 Wind 90 deg - No Ice	14.795	11.436	0.000	0.585	-677.192	1.149
0.9 Dead+1.6 Wind 90 deg - No Ice	11.096	11.436	0.000	0.435	-675.369	1.149
1.2 Dead+1.6 Wind 120 deg - No Ice	14.795	9.904	5.744	341.606	-586.465	0.995
0.9 Dead+1.6 Wind 120 deg - No Ice	11.096	9.904	5.744	340.537	-584.887	0.995
1.2 Dead+1.6 Wind 135 deg - No Ice	14.795	8.086	8.124	482.861	-478.846	0.813
0.9 Dead+1.6 Wind 135 deg - No Ice	11.096	8.086	8.124	481.412	-477.558	0.812
1.2 Dead+1.6 Wind 150 deg - No Ice	14.795	5.718	9.949	591.250	-338.595	0.575
0.9 Dead+1.6 Wind 150 deg - No Ice	11.096	5.718	9.949	589.509	-337.684	0.575
1.2 Dead+1.6 Wind 180 deg - No Ice	14.795	0.000	11.489	682.626	0.000	0.000
0.9 Dead+1.6 Wind 180 deg - No Ice	11.096	0.000	11.489	680.638	0.000	0.000
1.2 Dead+1.6 Wind 210 deg - No Ice	14.795	-5.718	9.949	591.250	338.595	-0.575
0.9 Dead+1.6 Wind 210 deg - No Ice	11.096	-5.718	9.949	589.509	337.684	-0.575
1.2 Dead+1.6 Wind 225 deg - No Ice	14.795	-8.086	8.124	482.861	478.846	-0.813
0.9 Dead+1.6 Wind 225 deg - No Ice	11.096	-8.086	8.124	481.412	477.558	-0.812
1.2 Dead+1.6 Wind 240 deg - No Ice	14.795	-9.904	5.744	341.606	586.465	-0.995
0.9 Dead+1.6 Wind 240 deg - No Ice	11.096	-9.904	5.744	340.537	584.887	-0.995
1.2 Dead+1.6 Wind 270 deg - No Ice	14.795	-11.436	0.000	0.585	677.192	-1.149
0.9 Dead+1.6 Wind 270 deg - No Ice	11.096	-11.436	0.000	0.435	675.369	-1.149
1.2 Dead+1.6 Wind 300 deg - No Ice	14.795	-9.904	-5.744	-340.436	586.464	-0.995
0.9 Dead+1.6 Wind 300 deg - No Ice	11.096	-9.904	-5.744	-339.666	584.886	-0.995
1.2 Dead+1.6 Wind 315 deg - No Ice	14.795	-8.086	-8.124	-481.691	478.846	-0.812

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job 21007.69 vZw Bridgeport NE CT	Page 18 of 32
	Project 98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date 11:45:36 11/19/21
	Client Verizon Wireless	Designed by TJL

Load Combination	Vertical K	Shear _x K	Shear _y K	Overturning Moment, M _x kip-ft	Overturning Moment, M _y kip-ft	Torque kip-ft
No Ice						
0.9 Dead+1.6 Wind 315 deg - No Ice	11.096	-8.086	-8.124	-480.540	477.557	-0.812
1.2 Dead+1.6 Wind 330 deg - No Ice	14.795	-5.718	-9.949	-590.080	338.595	-0.574
0.9 Dead+1.6 Wind 330 deg - No Ice	11.096	-5.718	-9.949	-588.637	337.684	-0.574
1.2 Dead+1.0 Ice+1.0 Temp	25.828	0.000	0.000	2.051	0.000	0.000
1.2 Dead+1.0 Wind 0 deg+1.0 Ice+1.0 Temp	25.828	0.000	-3.406	-191.788	0.000	0.000
1.2 Dead+1.0 Wind 30 deg+1.0 Ice+1.0 Temp	25.828	1.698	-2.950	-165.813	-96.493	0.146
1.2 Dead+1.0 Wind 45 deg+1.0 Ice+1.0 Temp	25.828	2.402	-2.408	-135.001	-136.461	0.206
1.2 Dead+1.0 Wind 60 deg+1.0 Ice+1.0 Temp	25.828	2.941	-1.703	-94.847	-167.130	0.253
1.2 Dead+1.0 Wind 90 deg+1.0 Ice+1.0 Temp	25.828	3.396	0.000	2.095	-192.985	0.292
1.2 Dead+1.0 Wind 120 deg+1.0 Ice+1.0 Temp	25.828	2.941	1.703	99.036	-167.130	0.253
1.2 Dead+1.0 Wind 135 deg+1.0 Ice+1.0 Temp	25.828	2.402	2.408	139.191	-136.461	0.206
1.2 Dead+1.0 Wind 150 deg+1.0 Ice+1.0 Temp	25.828	1.698	2.950	170.003	-96.493	0.146
1.2 Dead+1.0 Wind 180 deg+1.0 Ice+1.0 Temp	25.828	0.000	3.406	195.978	0.000	0.000
1.2 Dead+1.0 Wind 210 deg+1.0 Ice+1.0 Temp	25.828	-1.698	2.950	170.003	96.493	-0.146
1.2 Dead+1.0 Wind 225 deg+1.0 Ice+1.0 Temp	25.828	-2.402	2.408	139.191	136.461	-0.206
1.2 Dead+1.0 Wind 240 deg+1.0 Ice+1.0 Temp	25.828	-2.941	1.703	99.036	167.130	-0.253
1.2 Dead+1.0 Wind 270 deg+1.0 Ice+1.0 Temp	25.828	-3.396	0.000	2.095	192.985	-0.292
1.2 Dead+1.0 Wind 300 deg+1.0 Ice+1.0 Temp	25.828	-2.941	-1.703	-94.847	167.130	-0.253
1.2 Dead+1.0 Wind 315 deg+1.0 Ice+1.0 Temp	25.828	-2.402	-2.408	-135.001	136.461	-0.206
1.2 Dead+1.0 Wind 330 deg+1.0 Ice+1.0 Temp	25.828	-1.698	-2.950	-165.813	96.493	-0.146
Dead+Wind 0 deg - Service	12.329	0.000	-2.494	-148.246	0.000	0.000
Dead+Wind 30 deg - Service	12.329	1.241	-2.159	-128.320	-73.848	0.123
Dead+Wind 45 deg - Service	12.329	1.755	-1.763	-104.683	-104.438	0.174
Dead+Wind 60 deg - Service	12.329	2.150	-1.247	-73.880	-127.909	0.213
Dead+Wind 90 deg - Service	12.329	2.482	0.000	0.487	-147.697	0.246
Dead+Wind 120 deg - Service	12.329	2.150	1.247	74.853	-127.909	0.213
Dead+Wind 135 deg - Service	12.329	1.755	1.763	105.657	-104.438	0.174
Dead+Wind 150 deg - Service	12.329	1.241	2.159	129.293	-73.849	0.123
Dead+Wind 180 deg - Service	12.329	0.000	2.494	149.219	0.000	0.000
Dead+Wind 210 deg - Service	12.329	-1.241	2.159	129.293	73.849	-0.123
Dead+Wind 225 deg - Service	12.329	-1.755	1.763	105.657	104.438	-0.174
Dead+Wind 240 deg - Service	12.329	-2.150	1.247	74.853	127.909	-0.213
Dead+Wind 270 deg - Service	12.329	-2.482	0.000	0.487	147.697	-0.246
Dead+Wind 300 deg - Service	12.329	-2.150	-1.247	-73.880	127.909	-0.213
Dead+Wind 315 deg - Service	12.329	-1.755	-1.763	-104.683	104.438	-0.174
Dead+Wind 330 deg - Service	12.329	-1.241	-2.159	-128.320	73.848	-0.123

Solution Summary

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job 21007.69 vZw Bridgeport NE CT	Page 19 of 32
	Project 98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date 11:45:36 11/19/21
	Client Verizon Wireless	Designed by T.J.L.

Load Comb.	Sum of Applied Forces			Sum of Reactions			% Error
	PX K	PY K	PZ K	PX K	PY K	PZ K	
1	0.000	-12.329	0.000	0.000	12.329	0.000	0.000%
2	0.000	-14.795	-11.489	0.000	14.795	11.489	0.000%
3	0.000	-11.096	-11.489	0.000	11.096	11.489	0.000%
4	5.718	-14.795	-9.949	-5.718	14.795	9.949	0.000%
5	5.718	-11.096	-9.949	-5.718	11.096	9.949	0.000%
6	8.086	-14.795	-8.124	-8.086	14.795	8.124	0.000%
7	8.086	-11.096	-8.124	-8.086	11.096	8.124	0.000%
8	9.904	-14.795	-5.744	-9.904	14.795	5.744	0.000%
9	9.904	-11.096	-5.744	-9.904	11.096	5.744	0.000%
10	11.436	-14.795	0.000	-11.436	14.795	0.000	0.000%
11	11.436	-11.096	0.000	-11.436	11.096	0.000	0.000%
12	9.904	-14.795	5.744	-9.904	14.795	-5.744	0.000%
13	9.904	-11.096	5.744	-9.904	11.096	-5.744	0.000%
14	8.086	-14.795	8.124	-8.086	14.795	-8.124	0.000%
15	8.086	-11.096	8.124	-8.086	11.096	-8.124	0.000%
16	5.718	-14.795	9.949	-5.718	14.795	-9.949	0.000%
17	5.718	-11.096	9.949	-5.718	11.096	-9.949	0.000%
18	0.000	-14.795	11.489	0.000	14.795	-11.489	0.000%
19	0.000	-11.096	11.489	0.000	11.096	-11.489	0.000%
20	-5.718	-14.795	9.949	5.718	14.795	-9.949	0.000%
21	-5.718	-11.096	9.949	5.718	11.096	-9.949	0.000%
22	-8.086	-14.795	8.124	8.086	14.795	-8.124	0.000%
23	-8.086	-11.096	8.124	8.086	11.096	-8.124	0.000%
24	-9.904	-14.795	5.744	9.904	14.795	-5.744	0.000%
25	-9.904	-11.096	5.744	9.904	11.096	-5.744	0.000%
26	-11.436	-14.795	0.000	11.436	14.795	0.000	0.000%
27	-11.436	-11.096	0.000	11.436	11.096	0.000	0.000%
28	-9.904	-14.795	-5.744	9.904	14.795	5.744	0.000%
29	-9.904	-11.096	-5.744	9.904	11.096	5.744	0.000%
30	-8.086	-14.795	-8.124	8.086	14.795	8.124	0.000%
31	-8.086	-11.096	-8.124	8.086	11.096	8.124	0.000%
32	-5.718	-14.795	-9.949	5.718	14.795	9.949	0.000%
33	-5.718	-11.096	-9.949	5.718	11.096	9.949	0.000%
34	0.000	-25.828	0.000	0.000	25.828	-0.000	0.000%
35	0.000	-25.828	-3.406	0.000	25.828	3.406	0.000%
36	1.698	-25.828	-2.950	-1.698	25.828	2.950	0.000%
37	2.402	-25.828	-2.408	-2.402	25.828	2.408	0.000%
38	2.941	-25.828	-1.703	-2.941	25.828	1.703	0.000%
39	3.396	-25.828	0.000	-3.396	25.828	-0.000	0.000%
40	2.941	-25.828	1.703	-2.941	25.828	-1.703	0.000%
41	2.402	-25.828	2.408	-2.402	25.828	-2.408	0.000%
42	1.698	-25.828	2.950	-1.698	25.828	-2.950	0.000%
43	0.000	-25.828	3.406	0.000	25.828	-3.406	0.000%
44	-1.698	-25.828	2.950	1.698	25.828	-2.950	0.000%
45	-2.402	-25.828	2.408	2.402	25.828	-2.408	0.000%
46	-2.941	-25.828	1.703	2.941	25.828	-1.703	0.000%
47	-3.396	-25.828	0.000	3.396	25.828	-0.000	0.000%
48	-2.941	-25.828	-1.703	2.941	25.828	1.703	0.000%
49	-2.402	-25.828	-2.408	2.402	25.828	2.408	0.000%
50	-1.698	-25.828	-2.950	1.698	25.828	2.950	0.000%
51	0.000	-12.329	-2.494	0.000	12.329	2.494	0.000%
52	1.241	-12.329	-2.159	-1.241	12.329	2.159	0.000%
53	1.755	-12.329	-1.763	-1.755	12.329	1.763	0.000%
54	2.150	-12.329	-1.247	-2.150	12.329	1.247	0.000%
55	2.482	-12.329	0.000	-2.482	12.329	0.000	0.000%
56	2.150	-12.329	1.247	-2.150	12.329	-1.247	0.000%
57	1.755	-12.329	1.763	-1.755	12.329	-1.763	0.000%
58	1.241	-12.329	2.159	-1.241	12.329	-2.159	0.000%
59	0.000	-12.329	2.494	0.000	12.329	-2.494	0.000%
60	-1.241	-12.329	2.159	1.241	12.329	-2.159	0.000%

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job 21007.69 vZw Bridgeport NE CT	Page 20 of 32
	Project 98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date 11:45:36 11/19/21
	Client Verizon Wireless	Designed by TJL

Load Comb.	Sum of Applied Forces			Sum of Reactions			% Error
	PX K	PY K	PZ K	PX K	PY K	PZ K	
61	-1.755	-12.329	1.763	1.755	12.329	-1.763	0.000%
62	-2.150	-12.329	1.247	2.150	12.329	-1.247	0.000%
63	-2.482	-12.329	0.000	2.482	12.329	0.000	0.000%
64	-2.150	-12.329	-1.247	2.150	12.329	1.247	0.000%
65	-1.755	-12.329	-1.763	1.755	12.329	1.763	0.000%
66	-1.241	-12.329	-2.159	1.241	12.329	2.159	0.000%

Non-Linear Convergence Results

Load Combination	Converged?	Number of Cycles	Displacement Tolerance	Force Tolerance
1	Yes	4	0.00000001	0.00000001
2	Yes	4	0.00000001	0.00001123
3	Yes	4	0.00000001	0.00000001
4	Yes	4	0.00000001	0.00055133
5	Yes	4	0.00000001	0.00034508
6	Yes	4	0.00000001	0.00057126
7	Yes	4	0.00000001	0.00035695
8	Yes	4	0.00000001	0.00040423
9	Yes	4	0.00000001	0.00025296
10	Yes	4	0.00000001	0.00030930
11	Yes	4	0.00000001	0.00019545
12	Yes	4	0.00000001	0.00063808
13	Yes	4	0.00000001	0.00040039
14	Yes	4	0.00000001	0.00057226
15	Yes	4	0.00000001	0.00035646
16	Yes	4	0.00000001	0.00040679
17	Yes	4	0.00000001	0.00025188
18	Yes	4	0.00000001	0.00001129
19	Yes	4	0.00000001	0.00000001
20	Yes	4	0.00000001	0.00040679
21	Yes	4	0.00000001	0.00025188
22	Yes	4	0.00000001	0.00057226
23	Yes	4	0.00000001	0.00035646
24	Yes	4	0.00000001	0.00063808
25	Yes	4	0.00000001	0.00040039
26	Yes	4	0.00000001	0.00030930
27	Yes	4	0.00000001	0.00019545
28	Yes	4	0.00000001	0.00040423
29	Yes	4	0.00000001	0.00025296
30	Yes	4	0.00000001	0.00057126
31	Yes	4	0.00000001	0.00035695
32	Yes	4	0.00000001	0.00055133
33	Yes	4	0.00000001	0.00034508
34	Yes	4	0.00000001	0.00006958
35	Yes	5	0.00000001	0.00004589
36	Yes	5	0.00000001	0.00004733
37	Yes	5	0.00000001	0.00004800
38	Yes	5	0.00000001	0.00004805
39	Yes	5	0.00000001	0.00004839
40	Yes	5	0.00000001	0.00005108
41	Yes	5	0.00000001	0.00005196
42	Yes	5	0.00000001	0.00005194
43	Yes	5	0.00000001	0.00005115
44	Yes	5	0.00000001	0.00005194
45	Yes	5	0.00000001	0.00005196

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job	21007.69 vZw Bridgeport NE CT	Page	21 of 32
	Project	98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date	11:45:36 11/19/21
	Client	Verizon Wireless	Designed by	TJL

46	Yes	5	0.00000001	0.00005108
47	Yes	5	0.00000001	0.00004839
48	Yes	5	0.00000001	0.00004805
49	Yes	5	0.00000001	0.00004800
50	Yes	5	0.00000001	0.00004733
51	Yes	4	0.00000001	0.00000001
52	Yes	4	0.00000001	0.00000001
53	Yes	4	0.00000001	0.00001453
54	Yes	4	0.00000001	0.00000001
55	Yes	4	0.00000001	0.00001720
56	Yes	4	0.00000001	0.00001892
57	Yes	4	0.00000001	0.00001479
58	Yes	4	0.00000001	0.00000001
59	Yes	4	0.00000001	0.00000001
60	Yes	4	0.00000001	0.00000001
61	Yes	4	0.00000001	0.00001479
62	Yes	4	0.00000001	0.00001892
63	Yes	4	0.00000001	0.00001720
64	Yes	4	0.00000001	0.00000001
65	Yes	4	0.00000001	0.00001453
66	Yes	4	0.00000001	0.00000001

Maximum Tower Deflections - Service Wind

Section No.	Elevation ft	Horz. Deflection in	Gov. Load Comb.	Tilt °	Twist °
L1	98 - 78.5	4.923	59	0.646	0.011
L2	78.5 - 78	2.485	59	0.444	0.005
L3	78 - 68.5	2.439	59	0.436	0.005
L4	68.5 - 68	1.771	59	0.211	0.001
L5	68 - 38.25	1.749	59	0.211	0.001
L6	43.75 - 1	0.799	59	0.158	0.001

Critical Deflections and Radius of Curvature - Service Wind

Elevation ft	Appurtenance	Gov. Load Comb.	Deflection in	Tilt °	Twist °	Radius of Curvature ft
98.000	10'x48" Canister	59	4.923	0.646	0.011	9595
93.000	10'x48" Canister	59	4.224	0.605	0.009	9595
92.000	NNH4-65B-R6	59	4.087	0.597	0.009	7996
88.000	10'x48" Canister	59	3.556	0.560	0.008	4797
83.000	10'x48" Canister	59	2.951	0.505	0.006	3200
82.000	MX08FIT265-01	59	2.840	0.493	0.006	3035
78.000	10'x48" Canister	59	2.439	0.436	0.005	2858
73.000	10'x36" Canister	59	2.033	0.299	0.002	2450
68.000	10'x36" Canister	59	1.749	0.211	0.001	4433

Maximum Tower Deflections - Design Wind

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job 21007.69 vZw Bridgeport NE CT	Page 22 of 32
	Project 98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date 11:45:36 11/19/21
	Client Verizon Wireless	Designed by TJL

Section No.	Elevation ft	Horz. Deflection in	Gov. Load Comb.	Tilt °	Twist °
L1	98 - 78.5	22.238	18	2.892	0.051
L2	78.5 - 78	11.304	18	2.002	0.022
L3	78 - 68.5	11.096	18	1.967	0.021
L4	68.5 - 68	8.075	18	0.960	0.004
L5	68 - 38.25	7.974	18	0.959	0.004
L6	43.75 - 1	3.646	18	0.721	0.002

Critical Deflections and Radius of Curvature - Design Wind

Elevation ft	Appurtenance	Gov. Load Comb.	Deflection in	Tilt °	Twist °	Radius of Curvature ft
98.000	10'x48" Canister	18	22.238	2.892	0.051	2176
93.000	10'x48" Canister	18	19.107	2.714	0.043	2176
92.000	NNH4-65B-R6	18	18.493	2.677	0.042	1813
88.000	10'x48" Canister	18	16.114	2.515	0.036	1088
83.000	10'x48" Canister	18	13.398	2.273	0.028	725
82.000	MX08FIT265-01	18	12.900	2.218	0.027	687
78.000	10'x48" Canister	18	11.096	1.967	0.021	644
73.000	10'x36" Canister	18	9.261	1.352	0.011	548
68.000	10'x36" Canister	18	7.974	0.959	0.004	991

Compression Checks

Pole Design Data

Section No.	Elevation ft	Size	L ft	L _u ft	Kl/r	A in ²	P _u K	φP _n K	Ratio P _u / φP _n
L1	98 - 96.9737	TP8.625x8.625x0.465	19.500	0.000	0.0	11.920	-0.254	450.593	0.001
	96.9737 - 95.9474					11.920	-0.200	450.593	0.000
	95.9474 - 94.9211					11.920	-0.300	450.593	0.001
	94.9211 - 93.8947					11.920	-0.400	450.593	0.001
	93.8947 - 92.8684					11.920	-0.500	450.593	0.001
	92.8684 - 91.8421					11.920	-0.948	450.593	0.002
	91.8421 - 90.8158					11.920	-1.048	450.593	0.002
	90.8158 - 89.7895					11.920	-1.149	450.593	0.003
	89.7895 - 88.7632					11.920	-1.250	450.593	0.003
	88.7632 - 87.7368					11.920	-1.352	450.593	0.003
	87.7368 - 86.7105					11.920	-1.454	450.593	0.003

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job 21007.69 vZw Bridgeport NE CT	Page 24 of 32
	Project 98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date 11:45:36 11/19/21
	Client Verizon Wireless	Designed by TJL

Section No.	Elevation ft	Size	L ft	L _u ft	Kl/r	A in ²	P _u K	φP _n K	Ratio $\frac{P_u}{\phi P_n}$
	50.1316 - 48.8553					30.279	-6.656	1953.010	0.003
	48.8553 - 47.5789					30.433	-6.841	1958.540	0.003
	47.5789 - 46.3026					30.587	-7.028	1964.020	0.004
	46.3026 - 45.0263					30.741	-7.216	1969.460	0.004
	45.0263 - 43.75					30.894	-7.404	1974.850	0.004
	43.75 - 38.25					31.558	-4.513	1997.580	0.002
L6	43.75 - 38.25	TP45x38.684x0.25	42.750	0.000	0.0	31.142	-4.399	1983.450	0.002
	38.25 - 36.2895					31.372	-9.203	1991.320	0.005
	36.2895 - 34.3289					31.602	-9.495	1999.080	0.005
	34.3289 - 32.3684					31.832	-9.789	2006.750	0.005
	32.3684 - 30.4079					32.062	-10.085	2014.320	0.005
	30.4079 - 28.4474					32.292	-10.384	2021.790	0.005
	28.4474 - 26.4868					32.521	-10.684	2029.160	0.005
	26.4868 - 24.5263					32.751	-10.987	2036.430	0.005
	24.5263 - 22.5658					32.981	-11.292	2043.600	0.006
	22.5658 - 20.6053					33.211	-11.599	2050.670	0.006
	20.6053 - 18.6447					33.441	-11.908	2057.650	0.006
	18.6447 - 16.6842					33.671	-12.220	2064.520	0.006
	16.6842 - 14.7237					33.900	-12.534	2071.300	0.006
	14.7237 - 12.7632					34.130	-12.849	2077.970	0.006
	12.7632 - 10.8026					34.360	-13.168	2084.550	0.006
	10.8026 - 8.84211					34.590	-13.488	2091.030	0.006
	8.84211 - 6.88158					34.820	-13.810	2097.400	0.007
	6.88158 - 4.92105					35.049	-14.135	2103.680	0.007
	4.92105 - 2.96053					35.279	-14.461	2109.860	0.007
	2.96053 - 1					35.509	-14.791	2115.940	0.007

Pole Bending Design Data

Section No.	Elevation ft	Size	M _{ux} kip-ft	φM _{ux} kip-ft	Ratio $\frac{M_{ux}}{\phi M_{ux}}$	M _{uy} kip-ft	φM _{uy} kip-ft	Ratio $\frac{M_{uy}}{\phi M_{uy}}$
LI	98 - 96.9737	TP8.625x8.625x0.465	0.084	97.637	0.001	0.000	97.637	0.000

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job	21007.69 vZw Bridgeport NE CT	Page	25 of 32
	Project	98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date	11:45:36 11/19/21
	Client	Verizon Wireless	Designed by	TJL

Section No.	Elevation ft	Size	M_{ux} kip-ft	ϕM_{ux} kip-ft	Ratio $\frac{M_{ux}}{\phi M_{ux}}$	M_{uy} kip-ft	ϕM_{uy} kip-ft	Ratio $\frac{M_{uy}}{\phi M_{uy}}$
	96.9737 - 95.9474		0.303	97.637	0.003	0.000	97.637	0.000
	95.9474 - 94.9211		0.654	97.637	0.007	0.000	97.637	0.000
	94.9211 - 93.8947		1.140	97.637	0.012	0.000	97.637	0.000
	93.8947 - 92.8684		1.759	97.637	0.018	0.000	97.637	0.000
	92.8684 - 91.8421		2.795	97.637	0.029	0.000	97.637	0.000
	91.8421 - 90.8158		5.353	97.637	0.055	0.000	97.637	0.000
	90.8158 - 89.7895		8.044	97.637	0.082	0.000	97.637	0.000
	89.7895 - 88.7632		10.869	97.637	0.111	0.000	97.637	0.000
	88.7632 - 87.7368		13.826	97.637	0.142	0.000	97.637	0.000
	87.7368 - 86.7105		16.914	97.637	0.173	0.000	97.637	0.000
	86.7105 - 85.6842		20.131	97.637	0.206	0.000	97.637	0.000
	85.6842 - 84.6579		23.478	97.637	0.240	0.000	97.637	0.000
	84.6579 - 83.6316		26.953	97.637	0.276	0.000	97.637	0.000
	83.6316 - 82.6053		30.556	97.637	0.313	0.000	97.637	0.000
	82.6053 - 81.5789		34.516	97.637	0.354	0.000	97.637	0.000
	81.5789 - 80.5526		38.932	97.637	0.399	0.000	97.637	0.000
	80.5526 - 79.5263		43.473	97.637	0.445	0.000	97.637	0.000
	79.5263 - 78.5		48.139	97.637	0.493	0.000	97.637	0.000
L2	78.5 - 78 (2)	TP10.75x8.625x0.465	48.139	97.637	0.493	0.000	97.637	0.000
L3	78 - 76.9444	TP10.75x10.75x0.465	55.441	155.048	0.358	0.000	155.048	0.000
	76.9444 - 75.8889		60.536	155.048	0.390	0.000	155.048	0.000
	75.8889 - 74.8333		65.742	155.048	0.424	0.000	155.048	0.000
	74.8333 - 73.7778		71.057	155.048	0.458	0.000	155.048	0.000
	73.7778 - 72.7222		76.480	155.048	0.493	0.000	155.048	0.000
	72.7222 - 71.6667		82.012	155.048	0.529	0.000	155.048	0.000
	71.6667 - 70.6111		87.650	155.048	0.565	0.000	155.048	0.000
	70.6111 - 69.5556		93.393	155.048	0.602	0.000	155.048	0.000
	69.5556 - 68.5		99.241	155.048	0.640	0.000	155.048	0.000
L4	68.5 - 68 (4)	TP35.5x10.75x0.465	99.241	155.048	0.640	0.000	155.048	0.000
L5	68 - 66.7237	TP40.02x35.5x0.25	109.327	1364.725	0.080	0.000	1364.725	0.000
	66.7237 - 65.4474		116.737	1376.758	0.085	0.000	1376.758	0.000
	65.4474 - 64.1711		124.293	1388.800	0.089	0.000	1388.800	0.000
	64.1711 - 62.8947		131.996	1400.867	0.094	0.000	1400.867	0.000

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job	21007.69 vZw Bridgeport NE CT	Page	26 of 32
	Project	98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date	11:45:36 11/19/21
	Client	Verizon Wireless	Designed by	TJL

Section No.	Elevation ft	Size	M_{ux} kip-ft	ϕM_{ux} kip-ft	Ratio $\frac{M_{ux}}{\phi M_{ux}}$	M_{uy} kip-ft	ϕM_{uy} kip-ft	Ratio $\frac{M_{uy}}{\phi M_{uy}}$
	62.8947 - 61.6184		139.846	1412.942	0.099	0.000	1412.942	0.000
	61.6184 - 60.3421		147.844	1425.033	0.104	0.000	1425.033	0.000
	60.3421 - 59.0658		155.991	1437.142	0.109	0.000	1437.142	0.000
	59.0658 - 57.7895		164.287	1449.267	0.113	0.000	1449.267	0.000
	57.7895 - 56.5132		172.732	1461.400	0.118	0.000	1461.400	0.000
	56.5132 - 55.2368		181.328	1473.542	0.123	0.000	1473.542	0.000
	55.2368 - 53.9605		190.076	1485.708	0.128	0.000	1485.708	0.000
	53.9605 - 52.6842		198.974	1497.875	0.133	0.000	1497.875	0.000
	52.6842 - 51.4079		208.026	1510.058	0.138	0.000	1510.058	0.000
	51.4079 - 50.1316		217.230	1522.250	0.143	0.000	1522.250	0.000
	50.1316 - 48.8553		226.588	1534.458	0.148	0.000	1534.458	0.000
	48.8553 - 47.5789		236.101	1546.667	0.153	0.000	1546.667	0.000
	47.5789 - 46.3026		245.768	1558.892	0.158	0.000	1558.892	0.000
	46.3026 - 45.0263		255.590	1571.125	0.163	0.000	1571.125	0.000
	45.0263 - 43.75		265.568	1583.358	0.168	0.000	1583.358	0.000
	43.75 - 38.25		158.369	1636.183	0.097	0.000	1636.183	0.000
L6	43.75 - 38.25	TP45x38.684x0.25	152.036	1603.100	0.095	0.000	1603.100	0.000
	38.25 - 36.2895		327.092	1621.417	0.202	0.000	1621.417	0.000
	36.2895 - 34.3289		344.115	1639.742	0.210	0.000	1639.742	0.000
	34.3289 - 32.3684		361.471	1658.075	0.218	0.000	1658.075	0.000
	32.3684 - 30.4079		379.157	1676.417	0.226	0.000	1676.417	0.000
	30.4079 - 28.4474		397.172	1694.767	0.234	0.000	1694.767	0.000
	28.4474 - 26.4868		415.513	1713.125	0.243	0.000	1713.125	0.000
	26.4868 - 24.5263		434.179	1731.492	0.251	0.000	1731.492	0.000
	24.5263 - 22.5658		453.167	1749.850	0.259	0.000	1749.850	0.000
	22.5658 - 20.6053		472.474	1768.217	0.267	0.000	1768.217	0.000
	20.6053 - 18.6447		492.099	1786.583	0.275	0.000	1786.583	0.000
	18.6447 - 16.6842		512.040	1804.942	0.284	0.000	1804.942	0.000
	16.6842 - 14.7237		532.293	1823.300	0.292	0.000	1823.300	0.000
	14.7237 - 12.7632		552.857	1841.650	0.300	0.000	1841.650	0.000
	12.7632 - 10.8026		573.728	1859.992	0.308	0.000	1859.992	0.000

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job 21007.69 vZw Bridgeport NE CT	Page 27 of 32
	Project 98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date 11:45:36 11/19/21
	Client Verizon Wireless	Designed by TJL

Section No.	Elevation ft	Size	M_{ux} kip-ft	ϕM_{nx} kip-ft	Ratio $\frac{M_{ux}}{\phi M_{nx}}$	M_{uy} kip-ft	ϕM_{ny} kip-ft	Ratio $\frac{M_{uy}}{\phi M_{ny}}$
	10.8026 - 8.84211		594.906	1878.317	0.317	0.000	1878.317	0.000
	8.84211 - 6.88158		616.388	1896.642	0.325	0.000	1896.642	0.000
	6.88158 - 4.92105		638.169	1914.942	0.333	0.000	1914.942	0.000
	4.92105 - 2.96053		660.250	1933.233	0.342	0.000	1933.233	0.000
	2.96053 - 1		682.627	1951.508	0.350	0.000	1951.508	0.000

Pole Shear Design Data

Section No.	Elevation ft	Size	Actual V_u K	ϕV_n K	Ratio $\frac{V_u}{\phi V_n}$	Actual T_u kip-ft	ϕT_n kip-ft	Ratio $\frac{T_u}{\phi T_n}$
L1	98 - 96.9737	TP8.625x8.625x0.465	0.040	225.297	0.000	0.000	145.412	0.000
	96.9737 - 95.9474		0.260	225.297	0.001	0.000	145.412	0.000
	95.9474 - 94.9211		0.391	225.297	0.002	0.000	145.412	0.000
	94.9211 - 93.8947		0.521	225.297	0.002	0.000	145.412	0.000
	93.8947 - 92.8684		0.651	225.297	0.003	0.000	145.412	0.000
	92.8684 - 91.8421		2.410	225.297	0.011	0.000	145.412	0.000
	91.8421 - 90.8158		2.540	225.297	0.011	0.000	145.412	0.000
	90.8158 - 89.7895		2.670	225.297	0.012	0.000	145.412	0.000
	89.7895 - 88.7632		2.800	225.297	0.012	0.000	145.412	0.000
	88.7632 - 87.7368		2.929	225.297	0.013	0.000	145.412	0.000
	87.7368 - 86.7105		3.055	225.297	0.014	0.000	145.412	0.000
	86.7105 - 85.6842		3.181	225.297	0.014	0.000	145.412	0.000
	85.6842 - 84.6579		3.307	225.297	0.015	0.000	145.412	0.000
	84.6579 - 83.6316		3.432	225.297	0.015	0.000	145.412	0.000
	83.6316 - 82.6053		3.557	225.297	0.016	0.000	145.412	0.000
	82.6053 - 81.5789		4.226	225.297	0.019	0.000	145.412	0.000
	81.5789 - 80.5526		4.349	225.297	0.019	0.000	145.412	0.000
	80.5526 - 79.5263		4.471	225.297	0.020	0.000	145.412	0.000
	79.5263 - 78.5		4.591	225.297	0.020	0.000	145.412	0.000
	L2		78.5 - 78 (2)	TP10.75x8.625x0.465	4.650	283.968	0.016	0.000
L3	78 - 76.9444	TP10.75x10.75x0.465	4.757	283.968	0.017	0.000	233.333	0.000
	76.9444 - 75.8889		4.863	283.968	0.017	0.000	233.333	0.000
	75.8889 -		4.967	283.968	0.017	0.000	233.333	0.000

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job	21007.69 vZw Bridgeport NE CT	Page	28 of 32
	Project	98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date	11:45:36 11/19/21
	Client	Verizon Wireless	Designed by	TJL

Section No.	Elevation ft	Size	Actual V_u K	ϕV_n K	Ratio $\frac{V_u}{\phi V_n}$	Actual T_u kip-ft	ϕT_n kip-ft	Ratio $\frac{T_u}{\phi T_n}$
	74.8333							
	74.8333 -		5.071	283.968	0.018	0.000	233.333	0.000
	73.7778							
	73.7778 -		5.174	283.968	0.018	0.000	233.333	0.000
	72.7222							
	72.7222 -		5.276	283.968	0.019	0.000	233.333	0.000
	71.6667							
	71.6667 -		5.377	283.968	0.019	0.000	233.333	0.000
	70.6111							
	70.6111 -		5.476	283.968	0.019	0.000	233.333	0.000
	69.5556							
	69.5556 - 68.5		5.575	283.968	0.020	0.000	233.333	0.000
L4	68.5 - 68 (4)	TP35.5x10.75x0.465	5.636	967.312	0.006	0.000	233.333	0.000
L5	68 - 66.7237	TP40.02x35.5x0.25	5.749	935.481	0.006	0.000	2735.708	0.000
	66.7237 -		5.864	938.555	0.006	0.000	2759.808	0.000
	65.4474							
	65.4474 -		5.978	941.608	0.006	0.000	2783.933	0.000
	64.1711							
	64.1711 -		6.093	944.638	0.006	0.000	2808.100	0.000
	62.8947							
	62.8947 -		6.209	947.646	0.007	0.000	2832.292	0.000
	61.6184							
	61.6184 -		6.325	950.632	0.007	0.000	2856.517	0.000
	60.3421							
	60.3421 -		6.442	953.596	0.007	0.000	2880.767	0.000
	59.0658							
	59.0658 -		6.559	956.537	0.007	0.000	2905.050	0.000
	57.7895							
	57.7895 -		6.677	959.457	0.007	0.000	2929.358	0.000
	56.5132							
	56.5132 -		6.795	962.353	0.007	0.000	2953.692	0.000
	55.2368							
	55.2368 -		6.914	965.228	0.007	0.000	2978.050	0.000
	53.9605							
	53.9605 -		7.033	968.081	0.007	0.000	3002.433	0.000
	52.6842							
	52.6842 -		7.152	970.911	0.007	0.000	3026.833	0.000
	51.4079							
	51.4079 -		7.273	973.719	0.007	0.000	3051.258	0.000
	50.1316							
	50.1316 -		7.393	976.505	0.008	0.000	3075.708	0.000
	48.8553							
	48.8553 -		7.514	979.268	0.008	0.000	3100.175	0.000
	47.5789							
	47.5789 -		7.636	982.009	0.008	0.000	3124.658	0.000
	46.3026							
	46.3026 -		7.758	984.728	0.008	0.000	3149.158	0.000
	45.0263							
	45.0263 -		7.881	987.425	0.008	0.000	3173.675	0.000
	43.75							
	43.75 - 38.25		4.429	998.792	0.004	0.000	3279.475	0.000
L6	43.75 - 38.25	TP45x38.684x0.25	4.000	991.725	0.004	0.000	3213.217	0.000
	38.25 -		8.600	995.658	0.009	0.000	3249.900	0.000
	36.2895							
	36.2895 -		8.770	999.542	0.009	0.000	3286.600	0.000
	34.3289							
	34.3289 -		8.940	1003.380	0.009	0.000	3323.325	0.000
	32.3684							
	32.3684 -		9.108	1007.160	0.009	0.000	3360.075	0.000
	30.4079							

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job 21007.69 vZw Bridgeport NE CT	Page 29 of 32
	Project 98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date 11:45:36 11/19/21
	Client Verizon Wireless	Designed by TJL

Section No.	Elevation ft	Size	Actual V_u K	ϕV_n K	Ratio $\frac{V_u}{\phi V_n}$	Actual T_u kip-ft	ϕT_n kip-ft	Ratio $\frac{T_u}{\phi T_n}$
	30.4079 - 28.4474		9.275	1010.890	0.009	0.000	3396.833	0.000
	28.4474 - 26.4868		9.441	1014.580	0.009	0.000	3433.608	0.000
	26.4868 - 24.5263		9.606	1018.210	0.009	0.000	3470.383	0.000
	24.5263 - 22.5658		9.770	1021.800	0.010	0.000	3507.175	0.000
	22.5658 - 20.6053		9.933	1025.340	0.010	0.000	3543.958	0.000
	20.6053 - 18.6447		10.094	1028.820	0.010	0.000	3580.742	0.000
	18.6447 - 16.6842		10.255	1032.260	0.010	0.000	3617.517	0.000
	16.6842 - 14.7237		10.414	1035.650	0.010	0.000	3654.292	0.000
	14.7237 - 12.7632		10.572	1038.990	0.010	0.000	3691.042	0.000
	12.7632 - 10.8026		10.729	1042.270	0.010	0.000	3727.783	0.000
	10.8026 - 8.84211		10.884	1045.510	0.010	0.000	3764.500	0.000
	8.84211 - 6.88158		11.039	1048.700	0.011	0.000	3801.192	0.000
	6.88158 - 4.92105		11.192	1051.840	0.011	0.000	3837.850	0.000
	4.92105 - 2.96053		11.344	1054.930	0.011	0.000	3874.492	0.000
	2.96053 - 1		11.494	1057.970	0.011	0.000	3911.083	0.000

Pole Interaction Design Data

Section No.	Elevation ft	Ratio P_u	Ratio M_{ux}	Ratio M_{uy}	Ratio V_u	Ratio T_u	Comb. Stress Ratio	Allow. Stress Ratio	Criteria
L1	98 - 96.9737	0.001	0.001	0.000	0.000	0.000	0.001	1.000	4.8.2 ✓
	96.9737 - 95.9474	0.000	0.003	0.000	0.001	0.000	0.004	1.000	4.8.2 ✓
	95.9474 - 94.9211	0.001	0.007	0.000	0.002	0.000	0.007	1.000	4.8.2 ✓
	94.9211 - 93.8947	0.001	0.012	0.000	0.002	0.000	0.013	1.000	4.8.2 ✓
	93.8947 - 92.8684	0.001	0.018	0.000	0.003	0.000	0.019	1.000	4.8.2 ✓
	92.8684 - 91.8421	0.002	0.029	0.000	0.011	0.000	0.031	1.000	4.8.2 ✓
	91.8421 - 90.8158	0.002	0.055	0.000	0.011	0.000	0.057	1.000	4.8.2 ✓
	90.8158 - 89.7895	0.003	0.082	0.000	0.012	0.000	0.085	1.000	4.8.2 ✓
	89.7895 - 1	0.003	0.111	0.000	0.012	0.000	0.114	1.000	4.8.2 ✓

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job 21007.69 vZw Bridgeport NE CT	Page 30 of 32
	Project 98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date 11:45:36 11/19/21
	Client Verizon Wireless	Designed by TJL

Section No.	Elevation ft	Ratio	Ratio	Ratio	Ratio	Ratio	Comb. Stress Ratio	Allow. Stress Ratio	Criteria
		P_u	M_{ux}	M_{uy}	V_u	T_u			
	88.7632						✓		
	88.7632 - 87.7368	0.003	0.142	0.000	0.013	0.000	0.145	1.000	4.8.2 ✓
	87.7368 - 86.7105	0.003	0.173	0.000	0.014	0.000	0.177	1.000	4.8.2 ✓
	86.7105 - 85.6842	0.003	0.206	0.000	0.014	0.000	0.210	1.000	4.8.2 ✓
	85.6842 - 84.6579	0.004	0.240	0.000	0.015	0.000	0.244	1.000	4.8.2 ✓
	84.6579 - 83.6316	0.004	0.276	0.000	0.015	0.000	0.280	1.000	4.8.2 ✓
	83.6316 - 82.6053	0.004	0.313	0.000	0.016	0.000	0.317	1.000	4.8.2 ✓
	82.6053 - 81.5789	0.005	0.354	0.000	0.019	0.000	0.359	1.000	4.8.2 ✓
	81.5789 - 80.5526	0.005	0.399	0.000	0.019	0.000	0.404	1.000	4.8.2 ✓
	80.5526 - 79.5263	0.006	0.445	0.000	0.020	0.000	0.451	1.000	4.8.2 ✓
	79.5263 - 78.5	0.006	0.493	0.000	0.020	0.000	0.499	1.000	4.8.2 ✓
L2	78.5 - 78 (2)	0.006	0.493	0.000	0.016	0.000	0.499	1.000	4.8.2 ✓
L3	78 - 76.9444	0.005	0.358	0.000	0.017	0.000	0.363	1.000	4.8.2 ✓
	76.9444 - 75.8889	0.005	0.390	0.000	0.017	0.000	0.396	1.000	4.8.2 ✓
	75.8889 - 74.8333	0.005	0.424	0.000	0.017	0.000	0.430	1.000	4.8.2 ✓
	74.8333 - 73.7778	0.006	0.458	0.000	0.018	0.000	0.464	1.000	4.8.2 ✓
	73.7778 - 72.7222	0.006	0.493	0.000	0.018	0.000	0.499	1.000	4.8.2 ✓
	72.7222 - 71.6667	0.006	0.529	0.000	0.019	0.000	0.535	1.000	4.8.2 ✓
	71.6667 - 70.6111	0.006	0.565	0.000	0.019	0.000	0.572	1.000	4.8.2 ✓
	70.6111 - 69.5556	0.007	0.602	0.000	0.019	0.000	0.609	1.000	4.8.2 ✓
	69.5556 - 68.5	0.007	0.640	0.000	0.020	0.000	0.647	1.000	4.8.2 ✓
L4	68.5 - 68 (4)	0.007	0.640	0.000	0.006	0.000	0.647	1.000	4.8.2 ✓
L5	68 - 66.7237	0.002	0.080	0.000	0.006	0.000	0.082	1.000	4.8.2 ✓
	66.7237 - 65.4474	0.002	0.085	0.000	0.006	0.000	0.087	1.000	4.8.2 ✓
	65.4474 - 64.1711	0.002	0.089	0.000	0.006	0.000	0.092	1.000	4.8.2 ✓
	64.1711 - 62.8947	0.002	0.094	0.000	0.006	0.000	0.097	1.000	4.8.2 ✓
	62.8947 -	0.003	0.099	0.000	0.007	0.000	0.102	1.000	4.8.2 ✓

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job 21007.69 vZw Bridgeport NE CT	Page 31 of 32
	Project 98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date 11:45:36 11/19/21
	Client Verizon Wireless	Designed by TJL

Section No.	Elevation ft	Ratio	Ratio	Ratio	Ratio	Ratio	Comb. Stress Ratio	Allow. Stress Ratio	Criteria
		P_u	M_{ux}	M_{uy}	V_u	T_u			
	61.6184						✓		
	61.6184 - 60.3421	0.003	0.104	0.000	0.007	0.000	0.106	1.000	4.8.2 ✓
	60.3421 - 59.0658	0.003	0.109	0.000	0.007	0.000	0.111	1.000	4.8.2 ✓
	59.0658 - 57.7895	0.003	0.113	0.000	0.007	0.000	0.116	1.000	4.8.2 ✓
	57.7895 - 56.5132	0.003	0.118	0.000	0.007	0.000	0.121	1.000	4.8.2 ✓
	56.5132 - 55.2368	0.003	0.123	0.000	0.007	0.000	0.126	1.000	4.8.2 ✓
	55.2368 - 53.9605	0.003	0.128	0.000	0.007	0.000	0.131	1.000	4.8.2 ✓
	53.9605 - 52.6842	0.003	0.133	0.000	0.007	0.000	0.136	1.000	4.8.2 ✓
	52.6842 - 51.4079	0.003	0.138	0.000	0.007	0.000	0.141	1.000	4.8.2 ✓
	51.4079 - 50.1316	0.003	0.143	0.000	0.007	0.000	0.146	1.000	4.8.2 ✓
	50.1316 - 48.8553	0.003	0.148	0.000	0.008	0.000	0.151	1.000	4.8.2 ✓
	48.8553 - 47.5789	0.003	0.153	0.000	0.008	0.000	0.156	1.000	4.8.2 ✓
	47.5789 - 46.3026	0.004	0.158	0.000	0.008	0.000	0.161	1.000	4.8.2 ✓
	46.3026 - 45.0263	0.004	0.163	0.000	0.008	0.000	0.166	1.000	4.8.2 ✓
	45.0263 - 43.75	0.004	0.168	0.000	0.008	0.000	0.172	1.000	4.8.2 ✓
	43.75 - 38.25	0.002	0.097	0.000	0.004	0.000	0.099	1.000	4.8.2 ✓
L6	43.75 - 38.25	0.002	0.095	0.000	0.004	0.000	0.097	1.000	4.8.2 ✓
	38.25 - 36.2895	0.005	0.202	0.000	0.009	0.000	0.206	1.000	4.8.2 ✓
	36.2895 - 34.3289	0.005	0.210	0.000	0.009	0.000	0.215	1.000	4.8.2 ✓
	34.3289 - 32.3684	0.005	0.218	0.000	0.009	0.000	0.223	1.000	4.8.2 ✓
	32.3684 - 30.4079	0.005	0.226	0.000	0.009	0.000	0.231	1.000	4.8.2 ✓
	30.4079 - 28.4474	0.005	0.234	0.000	0.009	0.000	0.240	1.000	4.8.2 ✓
	28.4474 - 26.4868	0.005	0.243	0.000	0.009	0.000	0.248	1.000	4.8.2 ✓
	26.4868 - 24.5263	0.005	0.251	0.000	0.009	0.000	0.256	1.000	4.8.2 ✓
	24.5263 - 22.5658	0.006	0.259	0.000	0.010	0.000	0.265	1.000	4.8.2 ✓
	22.5658 - 20.6053	0.006	0.267	0.000	0.010	0.000	0.273	1.000	4.8.2 ✓
	20.6053 -	0.006	0.275	0.000	0.010	0.000	0.281	1.000	4.8.2 ✓

tnxTower Centek Engineering Inc. 63-2 North Branford Rd. Branford, CT 06405 Phone: (203) 488-0580 FAX: (203) 488-8587	Job 21007.69 vZw Bridgeport NE CT	Page 32 of 32
	Project 98-ft Flag pole- 541 Broadbridge Road Bridgeport, CT 06610	Date 11:45:36 11/19/21
	Client Verizon Wireless	Designed by TJL

Section No.	Elevation ft	Ratio	Ratio	Ratio	Ratio	Ratio	Comb. Stress Ratio	Allow. Stress Ratio	Criteria
		ϕP_n	ϕM_{nx}	ϕM_{ny}	ϕV_n	ϕT_n			
	18.6447						✓		
	18.6447 - 16.6842	0.006	0.284	0.000	0.010	0.000	0.290	1.000	4.8.2 ✓
	16.6842 - 14.7237	0.006	0.292	0.000	0.010	0.000	0.298	1.000	4.8.2 ✓
	14.7237 - 12.7632	0.006	0.300	0.000	0.010	0.000	0.306	1.000	4.8.2 ✓
	12.7632 - 10.8026	0.006	0.308	0.000	0.010	0.000	0.315	1.000	4.8.2 ✓
	10.8026 - 8.84211	0.006	0.317	0.000	0.010	0.000	0.323	1.000	4.8.2 ✓
	8.84211 - 6.88158	0.007	0.325	0.000	0.011	0.000	0.332	1.000	4.8.2 ✓
	6.88158 - 4.92105	0.007	0.333	0.000	0.011	0.000	0.340	1.000	4.8.2 ✓
	4.92105 - 2.96053	0.007	0.342	0.000	0.011	0.000	0.348	1.000	4.8.2 ✓
	2.96053 - 1	0.007	0.350	0.000	0.011	0.000	0.357	1.000	4.8.2 ✓

Section Capacity Table

Section No.	Elevation ft	Component Type	Size	Critical Element	P K	ϕP_{allow} K	% Capacity	Pass Fail
L1	98 - 78.5	Pole	TP8.625x8.625x0.465	1	-2.599	450.593	49.9	Pass
L2	78.5 - 78	Pole	TP10.75x8.625x0.465	2	-2.634	450.593	49.9	Pass
L3	78 - 68.5	Pole	TP10.75x10.75x0.465	3	-3.871	567.935	64.7	Pass
L4	68.5 - 68	Pole	TP35.5x10.75x0.465	4	-3.928	567.935	64.7	Pass
L5	68 - 38.25	Pole	TP40.02x35.5x0.25	5	-7.404	1974.850	17.2	Pass
L6	38.25 - 1	Pole	TP45x38.684x0.25	6	-14.791	2115.940	35.7	Pass
Summary								
Pole (L3)							64.7	Pass
RATING =							64.7	Pass

Anchor Bolt and Base Plate Analysis:

Input Data:

Tower Reactions:

Overturning Moment = $M_U := 683\text{-ft-kips}$ (Input From trxDTower)
 Shear Force = $\text{Shear} := 11\text{-kips}$ (Input From trxDTower)
 Axial Force = $R_U := 15\text{-kips}$ (Input From trxDTower)

Anchor Bolt Data:

ASTMA615 Grade 75

Number of Anchor Bolts = $N := 6$ (User Input)
 Diameter of Bolt Circle = $D_{BC} := 51.25\text{-in}$ (User Input)
 Bolt "Column" Distance = $l := 3.0\text{-in}$ (User Input)
 Bolt Ultimate Strength = $F_U := 100\text{-ksi}$ (User Input)
 Bolt Yield Strength = $F_y := 75\text{-ksi}$ (User Input)
 Bolt Modulus = $E := 29000\text{-ksi}$ (User Input)
 Diameter of Anchor Bolts = $D := 1.75\text{-in}$ (User Input)
 Threads per Inch = $n := 5$ (User Input)
 Top of Concrete to Bot Leveling Nut = $l_{ar} := 2\text{-in}$ (User Input)
 Anchor Rod Force Correction Factor = $n_c := 1.1$

Base Plate Data:

UseASTMA572 Grade 50

Plate Yield Strength = $F_{yf} := 50\text{-ksi}$ (User Input)
 Base Plate Thickness = $t_{TP} := 1.75\text{-in}$ (User Input)
 Base Plate Diameter = $D_{OD} := 56.25\text{-in}$ (User Input)
 Outer Pole Diameter = $D_T := 45.5\text{-in}$ (User Input)
 Pole Wall Thickness = $t_T := 0.25\text{-in}$ (User Input)
 Pole Design Yield Strength = $F_{yp} := 65\text{-ksi}$ (User Input)
 $\eta := 0.5$ For UngROUTed Base Plate per TIA-222-G Section 4.9.9

Anchor Bolt Analysis:

GrossArea of Bolt = $A_g := \frac{\pi}{4} \cdot D^2 = 2.405 \cdot \text{in}^2$

NetArea of Bolt = $A_n := \frac{\pi}{4} \cdot \left(D - \frac{0.9743 \cdot \text{in}}{n} \right)^2 = 1.899 \cdot \text{in}^2$

Tensile Root Diameter = $d_{rt} := D - \frac{0.9743 \cdot \text{in}}{n} = 1.555 \cdot \text{in}$

Plastic Section Modulus = $Z := \frac{d_{rt}^3}{6} = 0.627 \cdot \text{in}^3$

Maximum Anchor Rod Force = $P_u := \frac{n_c \cdot \pi \cdot M_u}{N \cdot D_{BC}} + \frac{R_u}{N} = 94.6 \cdot \text{kips}$

Maximum Shear Force = $V_u := \frac{\text{Shear}}{N} = 1.8 \cdot \text{kips}$

Design Tensile Strength = $\Phi R_{nt} := 0.8 \cdot F_u \cdot A_n = 151.956 \cdot \text{k}$

Bolt % of Capacity = $\frac{\left(P_u + \frac{V_u}{\eta} \right)}{\Phi R_{nt}} \cdot 100 = 64.7$

Condition1 = $\text{Condition1} := \text{if} \left[\frac{\left(P_u + \frac{V_u}{\eta} \right)}{\Phi R_{nt}} \leq 1.00, \text{"OK"}, \text{"Overstressed"} \right]$

Condition1 = "OK"

Design Shear Strength = $\Phi R_{nv} := 0.75 \cdot 0.45 \cdot F_u \cdot A_g = 81.178 \cdot \text{k}$

Design Flexural Strength = $\Phi R_{nm} := 0.9 \cdot F_y \cdot Z = 42.312 \cdot \text{in} \cdot \text{k}$

$M_u := \begin{cases} 0 & \text{if } l_{ar} < D \\ 0.65 \cdot l_{ar} \cdot V_u & \text{otherwise} \end{cases} = 2.383 \cdot \text{in} \cdot \text{k}$

Bolt % of Capacity = $\left[\left(\frac{V_u}{\Phi R_{nv}} \right)^2 + \left(\frac{P_u}{\Phi R_{nt}} + \frac{M_u}{\Phi R_{nm}} \right)^2 \right] \cdot 100 = 46.1$

Condition2 = $\text{Condition2} := \text{if} \left[\left(\frac{V_u}{\Phi R_{nv}} \right)^2 + \left(\frac{P_u}{\Phi R_{nt}} + \frac{M_u}{\Phi R_{nm}} \right)^2 \leq 1.00, \text{"OK"}, \text{"Overstressed"} \right]$

Condition2 = "OK"

Base Plate Analysis:

Strength Resistance Factor for Yielding due to Bending =

$$\phi_b := 0.9$$

Strength Resistance Factor for Yielding due to Shear =

$$\phi_v := 1.0$$

Outside Fillet Horizontal Leg Dimension =

$$w_1 := 0.25\text{-in}$$

Effective Pole Outside Diameter =

$$D_e := D_T + w_1 = 45.75\text{-in}$$

Effective Base Plate Outside Diameter =

$$D_{oe} := \begin{cases} D_{OD} & \text{if } D_{OD} \leq (D_{BC} + 6 \cdot t_{TP}) \\ (D_{BC} + 6 \cdot t_{TP}) & \text{otherwise} \end{cases} = 56.25\text{-in}$$

Half-Angle Between Radial Lines Extending from Pole
 Centerline Through Midpoints Between Adjacent Anchor
 Rods =

$$\theta_1 := \frac{\pi}{N} = 0.524$$

Angle Defining Limiting Effective Base Plate Width
 Based on Plate Thickness =

$$\theta_2 := \text{asin}\left(\frac{12 \cdot t_{TP}}{D_{BC}}\right) = 0.422$$

Angle Defining Limiting Effective Base Plate Width
 Based on Distance Between Anchor Rod Bolt Circle and
 Effective Pole Outside Diameter =

$$\theta_3 := \text{acos}\left(\frac{D_{BC} + D_e}{2 D_{BC}}\right) = 0.329$$

Governing Angle Defining Effective Base Plate Width
 Resisting Bending =

$$\theta := \min(\theta_1, \theta_2, \theta_3) = 0.329$$

Effective Moment Arm of Anchor Rod Force =

$$x := 0.5 \cdot (D_{BC} - D_e) = 2.75\text{-in}$$

Effective Base Plate Width Resisting Bending from
 Transverse Bend Line =

$$B_{et} := D_{BC} \cdot \sin(\theta) = 16.562\text{-in}$$

Effective Base Plate Width Resisting Bending from
 Radial Bend Lines =

$$B_{er} := (D_{oe} - D_e) \cdot \sin(\theta) = 3.393\text{-in}$$

Total Effective Base Plate Width Resisting Bending =

$$B_{eff} := B_{et} + B_{er} = 19.956\text{-in}$$

Required Base Plate Thickness =

$$t_{TP,Req} := \sqrt{\frac{4 \cdot P_u \cdot x}{\phi_b \cdot F_{yf} \cdot B_{eff}}} = 1.077\text{-in}$$

Plate Bending Stress % of Capacity =

$$\frac{t_{TP,Req}}{t_{TP}} = 61.5\%$$

Condition2 =

$$\text{Condition3} := \text{if}\left(\frac{t_{TP,Req}}{t_{TP}} < 1.00, \text{"Ok"}, \text{"Overstressed"}\right)$$

Condition3 = "Ok"

Required Base Plate Thickness =

$$t_{TP,Req} := \frac{\phi_b \cdot t_T \cdot F_{yp}}{\phi_v \cdot 0.6 \cdot F_{yf}} = 0.488\text{-in}$$

Plate Bending Stress % of Capacity =

$$\frac{t_{TP,Req}}{t_{TP}} = 27.9\%$$

Condition2 =

$$\text{Condition4} := \text{if}\left(\frac{t_{TP,Req}}{t_{TP}} < 1.00, \text{"Ok"}, \text{"Overstressed"}\right)$$

Condition4 = "Ok"

Caisson Foundation:

Input Data:

Shear Force =	S := 11k	USER INPUT-FROM trnTower
Overturing Moment =	M := 683ft-k	USER INPUT-FROM trnTower
Applied Axial Load =	A1 := 15k	USER INPUT-FROM trnTower
Bending Moment =	Mu := 712ft-k	USER INPUT-FROM LPILE
Moment Capacity =	Mn := 3324ft-k	USER INPUT-FROM LPILE
Foundation Diameter =	d := 6ft	USER INPUT
Overall Length of Caisson =	Lc := 18.75ft	USER INPUT
Depth From Top of Caisson to Grade =	Lpag := 0.75ft	USER INPUT
Number of Rebar =	n := 26	USER INPUT
Area of Rebar =	Ar := 0.785in ²	USER INPUT
Rebar Yield Strength =	fy := 60ksi	USER INPUT
Concrete Comp Strength =	fc := 4ksi	USER INPUT

Check Moment Capacity:

Factor of Safety =	FS := $\frac{0.9Mn}{Mu} = 4.2$
Factor of Safety Required =	FS _{reqd} := 1
	FOSCheck := if(FS ≥ FS _{reqd} , "OK", "NO GOOD")
	FOSCheck = "OK"

=====

LPILE Plus for Windows, Version 5.0 (5.0.47)

Analysis of Individual Piles and Drilled Shafts
Subjected to Lateral Loading Using the p-y Method

(c) 1985-2010 by Ensoft, Inc.
All Rights Reserved

=====

This program is licensed to:

TJL
Centek Engineering

Files Used for Analysis

Path to file locations: J:\Jobs\2100700.WI\69_Bridgeport NE
CT\05_Structural\Backup Documentation\Calcs\LPile\
Name of input data file: Caisson.lpd
Name of output file: Caisson.lpo
Name of plot output file: Caisson.lpp
Name of runtime file: Caisson.lpr

Time and Date of Analysis

Date: November 19, 2021 Time: 12:09:44

Problem Title

21007.69 Bridgeport NE

Program Options

Units Used in Computations - US Customary Units: Inches, Pounds

Basic Program Options:

Analysis Type 3:

- Computation of Nonlinear Bending Stiffness and Ultimate Bending Moment Capacity with Pile Response Computed Using Nonlinear EI

Computation Options:

- Only internally-generated p-y curves used in analysis
- Analysis does not use p-y multipliers (individual pile or shaft action only)
- Analysis assumes no shear resistance at pile tip
- Analysis for fixed-length pile or shaft only
- No computation of foundation stiffness matrix elements
- Output summary table of values for pile-head deflection, maximum bending moment, and shear force only
- Analysis assumes no soil movements acting on pile
- No additional p-y curves to be computed at user-specified depths

Solution Control Parameters:

- Number of pile increments = 100
- Maximum number of iterations allowed = 100
- Deflection tolerance for convergence = 1.0000E-05 in
- Maximum allowable deflection = 1.0000E+02 in

Printing Options:

- Only summary tables of pile-head deflection, maximum bending moment, and maximum shear force are to be printed in output file.

Pile Structural Properties and Geometry

- Pile Length = 225.00 in
- Depth of ground surface below top of pile = 9.00 in
- Slope angle of ground surface = 0.00 deg.

Structural properties of pile defined using 2 points

Point No.	Point Depth in	Pile Diameter in	Moment of Inertia in**4	Pile Area Sq.in	Modulus of Elasticity lbs/Sq.in
1	0.0000	72.00000000	1319167.	4071.5000	3604996.
2	225.0000	72.00000000	1319167.	4071.5000	3604996.

Please note that because this analysis makes computations of ultimate moment capacity and pile response using nonlinear bending stiffness that the above values of moment of inertia and modulus of are not used for any computations other than total stress due to combined axial loading and bending.

Soil and Rock Layering Information

The soil profile is modelled using 2 layers

Layer 1 is sand, p-y criteria by Reese et al., 1974

Distance from top of pile to top of layer = 9.000 in
Distance from top of pile to bottom of layer = 210.000 in
p-y subgrade modulus k for top of soil layer = 0.000 lbs/in**3
p-y subgrade modulus k for bottom of layer = 0.000 lbs/in**3

NOTE: Internal default values for p-y subgrade modulus will be computed for the above soil layer.

Layer 2 is sand, p-y criteria by Reese et al., 1974

Distance from top of pile to top of layer = 210.000 in
Distance from top of pile to bottom of layer = 240.000 in
p-y subgrade modulus k for top of soil layer = 0.000 lbs/in**3
p-y subgrade modulus k for bottom of layer = 0.000 lbs/in**3

NOTE: Internal default values for p-y subgrade modulus will be computed for the above soil layer.

(Depth of lowest layer extends 15.00 in below pile tip)

Effective Unit Weight of Soil vs. Depth

Effective unit weight of soil with depth defined using 4 points

Point No.	Depth X in	Eff. Unit Weight lbs/in**3
1	9.00	0.07200
2	210.00	0.07200
3	210.00	0.08100
4	240.00	0.08100

Shear Strength of Soils

Shear strength parameters with depth defined using 4 points

Point No.	Depth X in	Cohesion c lbs/in**2	Angle of Friction Deg.	E50 or k_rm	RQD %
1	9.000	0.00000	32.00	-----	-----
2	210.000	0.00000	32.00	-----	-----
3	210.000	0.00000	40.00	-----	-----
4	240.000	0.00000	40.00	-----	-----

Notes:

- (1) Cohesion = uniaxial compressive strength for rock materials.
- (2) Values of E50 are reported for clay strata.
- (3) Default values will be generated for E50 when input values are 0.
- (4) RQD and k_rm are reported only for weak rock strata.

Loading Type

Static loading criteria was used for computation of p-y curves.

Pile-head Loading and Pile-head Fixity Conditions

Number of loads specified = 1

Load Case Number 1

Pile-head boundary conditions are Shear and Moment (BC Type 1)

Shear force at pile head = 11000.000 lbs
Bending moment at pile head = 8196000.000 in-lbs
Axial load at pile head = 15000.000 lbs

Non-zero moment at pile head for this load case indicates the pile-head may rotate under the applied pile-head loading, but is not a free-head (zero moment) condition.

Computations of Nominal Moment Capacity and Nonlinear Bending Stiffness

Number of sections = 1

Pile Section No. 1

The sectional shape is a circular drilled shaft (bored pile).

Outside Diameter = 72.0000 in

Material Properties:

Compressive Strength of Concrete = 4.000 kip/in**2
 Yield Stress of Reinforcement = 60. kip/in**2
 Modulus of Elasticity of Reinforcement = 29000. kip/in**2
 Number of Reinforcing Bars = 26
 Area of Single Bar = 0.79000 in**2
 Number of Rows of Reinforcing Bars = 13
 Area of Steel = 20.540 in**2
 Area of Shaft = 4071.504 in**2
 Percentage of Steel Reinforcement = 0.504 percent
 Cover Thickness (edge to bar center) = 3.000 in

Unfactored Axial Squash Load Capacity = 15005.68 kip

Distribution and Area of Steel Reinforcement

Row Number	Area of Reinforcement in**2	Distance to Centroidal Axis in
1	1.580	32.759
2	1.580	30.856
3	1.580	27.158
4	1.580	21.883
5	1.580	15.336
6	1.580	7.897
7	1.580	0.000
8	1.580	-7.897
9	1.580	-15.336
10	1.580	-21.883
11	1.580	-27.158
12	1.580	-30.856
13	1.580	-32.759

Axial Thrust Force = 15000.00 lbs

Bending Max. Steel Moment Stress in-lbs	Bending Stiffness lb-in2	Bending Curvature rad/in	Maximum Strain in/in	Neutral Axis Position inches	Max. Concrete Stress psi
---	--------------------------	--------------------------	----------------------	------------------------------	--------------------------

psi

4256323. 823.13148	5.107588E+12	8.333333E-07	0.00003108	37.30122006	110.31403
8469489. 1618.55057	5.081693E+12	0.00000167	0.00006121	36.72786033	215.44648
12638586. 2413.35040	5.055434E+12	0.00000250	0.00009132	36.52819884	318.79769
16763961. 3208.14016	5.029188E+12	0.00000333	0.00012143	36.42826402	420.44286
16763961. 6356.23117	4.023351E+12	0.00000417	0.00006732	16.15610039	231.62965
16763961. 7656.25284	3.352792E+12	0.00000500	0.00007979	15.95764911	273.51577
16763961. 8955.87206	2.873822E+12	0.00000583	0.00009227	15.81827724	315.17124
16763961. 10255.08679	2.514594E+12	0.00000667	0.00010477	15.71584046	356.59534
16763961. 11553.89394	2.235195E+12	0.00000750	0.00011729	15.63804138	397.78746
16763961. 12846.85350	2.011675E+12	0.00000833	0.00013000	15.59999907	439.38322
16763961. 14136.38339	1.828796E+12	0.00000917	0.00014283	15.58177507	481.08733
16763961. 15433.76294	1.676396E+12	0.00001000	0.00015540	15.53952062	521.58998
16763961. 16730.68243	1.547443E+12	0.00001083	0.00016797	15.50523126	561.86237
16763961. 18027.13936	1.436911E+12	0.00001167	0.00018057	15.47720754	601.90366
16763961. 19323.12985	1.341117E+12	0.00001250	0.00019318	15.45420706	641.71317
16763961. 20618.65145	1.257297E+12	0.00001333	0.00020580	15.43529427	681.29003
16763961. 21913.70137	1.183338E+12	0.00001417	0.00021845	15.41975462	720.63341
16763961. 23208.27494	1.117597E+12	0.00001500	0.00023111	15.40703666	759.74268
16763961. 24502.36957	1.058776E+12	0.00001583	0.00024378	15.39670050	798.61696
16763961. 25795.98059	1.005838E+12	0.00001667	0.00025647	15.38839853	837.25557
16763961. 27089.10753	9.579406E+11	0.00001750	0.00026918	15.38184106	875.65739
16763961. 28381.74371	9.143979E+11	0.00001833	0.00028191	15.37680280	913.82193
16763961. 29673.88751	8.746414E+11	0.00001917	0.00029465	15.37308848	951.74818
16763961. 30965.53505	8.381981E+11	0.00002000	0.00030741	15.37053931	989.43531

16763961.	8.046701E+11	0.00002083	0.00032019	15.36902010	1026.88241
32256.68353					
16763961.	7.737213E+11	0.00002167	0.00033298	15.36842144	1064.08885
33547.32704					
16763961.	7.450649E+11	0.00002250	0.00034579	15.36864460	1101.05363
34837.46323					
16999781.	7.285620E+11	0.00002333	0.00035862	15.36960590	1137.77579
36127.08917					
17587282.	7.277496E+11	0.00002417	0.00037147	15.37123668	1174.25462
37416.19944					
18174207.	7.269683E+11	0.00002500	0.00038434	15.37347257	1210.48901
38704.79220					
18760555.	7.262150E+11	0.00002583	0.00039722	15.37626421	1246.47837
39992.86053					
19346318.	7.254869E+11	0.00002667	0.00041012	15.37956011	1282.22144
41280.40398					
19931499.	7.247818E+11	0.00002750	0.00042304	15.38332379	1317.71765
42567.41507					
20516087.	7.240972E+11	0.00002833	0.00043598	15.38751447	1352.96570
43853.89340					
21100081.	7.234313E+11	0.00002917	0.00044894	15.39210212	1387.96480
45139.83340					
21683482.	7.227827E+11	0.00003000	0.00046191	15.39706099	1422.71420
46425.22871					
22266283.	7.221497E+11	0.00003083	0.00047491	15.40236318	1457.21273
47710.07736					
22848478.	7.215309E+11	0.00003167	0.00048792	15.40798509	1491.45931
48994.37612					
23430067.	7.209251E+11	0.00003250	0.00050095	15.41390955	1525.45322
50278.11800					
24591406.	7.197485E+11	0.00003417	0.00052708	15.42659104	1592.67859
52843.91779					
25750270.	7.186122E+11	0.00003583	0.00055328	15.44028318	1658.88068
55407.44146					
26906627.	7.175101E+11	0.00003750	0.00057956	15.45488513	1724.05120
57968.65215					
28014962.	7.152756E+11	0.00003917	0.00060556	15.46112072	1787.27995
60000.00000					
28870482.	7.070322E+11	0.00004083	0.00062963	15.41942203	1844.53322
60000.00000					
29586617.	6.961557E+11	0.00004250	0.00065261	15.35560048	1898.14445
60000.00000					
30196472.	6.836937E+11	0.00004417	0.00067472	15.27657831	1948.71572
60000.00000					
30717962.	6.702101E+11	0.00004583	0.00069608	15.18726289	1996.70381
60000.00000					
31238313.	6.576487E+11	0.00004750	0.00071749	15.10509288	2043.98088
60000.00000					
31676439.	6.442666E+11	0.00004917	0.00073812	15.01270473	2088.69522
60000.00000					
32034685.	6.301905E+11	0.00005083	0.00075800	14.91139448	2130.96863

60000.00000					
32392072.	6.169918E+11	0.00005250	0.00077790	14.81715882	2172.62311
60000.00000					
32748581.	6.045892E+11	0.00005417	0.00079784	14.72934544	2213.65501
60000.00000					
33104211.	5.929112E+11	0.00005583	0.00081781	14.64738572	2254.06137
60000.00000					
33374856.	5.804323E+11	0.00005750	0.00083681	14.55329812	2291.75347
60000.00000					
33606473.	5.679967E+11	0.00005917	0.00085539	14.45726216	2327.93962
60000.00000					
33941665.	5.579452E+11	0.00006083	0.00087600	14.40000021	2367.61443
60000.00000					
34094097.	5.455056E+11	0.00006250	0.00089674	14.34779370	2406.78708
60000.00000					
34319730.	5.348529E+11	0.00006417	0.00091482	14.25686896	2440.07204
60000.00000					
34544743.	5.247303E+11	0.00006583	0.00093292	14.17097604	2472.84324
60000.00000					
34769135.	5.150983E+11	0.00006750	0.00095106	14.08974588	2505.09832
60000.00000					
34992905.	5.059215E+11	0.00006917	0.00096922	14.01284587	2536.83502
60000.00000					
35132394.	4.959867E+11	0.00007083	0.00098601	13.92008436	2565.51460
60000.00000					
35268344.	4.864599E+11	0.00007250	0.00100276	13.83119595	2593.65934
60000.00000					
35403817.	4.773548E+11	0.00007417	0.00101954	13.74661410	2621.36150
60000.00000					
35538819.	4.686438E+11	0.00007583	0.00103634	13.66605985	2648.61960
60000.00000					
35673344.	4.603012E+11	0.00007750	0.00105317	13.58927357	2675.43151
60000.00000					
35807389.	4.523039E+11	0.00007917	0.00107002	13.51601923	2701.79529
60000.00000					
35940952.	4.446303E+11	0.00008083	0.00108689	13.44608009	2727.70901
60000.00000					
36074028.	4.372609E+11	0.00008250	0.00110379	13.37925661	2753.17062
60000.00000					
36206626.	4.301777E+11	0.00008417	0.00112071	13.31536853	2778.17855
60000.00000					
36338726.	4.233638E+11	0.00008583	0.00113766	13.25424206	2802.73017
60000.00000					
36338726.	4.152997E+11	0.00008750	0.00115500	13.19999921	2827.38227
60000.00000					
36545033.	4.098508E+11	0.00008917	0.00117700	13.19999921	2858.29423
60000.00000					
36759897.	4.046961E+11	0.00009083	0.00119566	13.16322291	2883.62507
60000.00000					
36831708.	3.981806E+11	0.00009250	0.00121065	13.08814466	2903.26734
60000.00000					

36903193. 60000.00000	3.918923E+11	0.00009417	0.00122567	13.01592886	2922.55503
36974352. 60000.00000	3.858193E+11	0.00009583	0.00124070	12.94642746	2941.48673
37045178. 60000.00000	3.799505E+11	0.00009750	0.00125575	12.87950099	2960.06081
37115678. 60000.00000	3.742757E+11	0.00009917	0.00127082	12.81502283	2978.27610
37255664. 60000.00000	3.634699E+11	0.00010250	0.00130103	12.69293082	3013.62345
37394308. 60000.00000	3.533320E+11	0.00010583	0.00133131	12.57928240	3047.51721
37531576. 60000.00000	3.438007E+11	0.00010917	0.00136167	12.47330725	3079.94462
37667474. 60000.00000	3.348220E+11	0.00011250	0.00139211	12.37433589	3110.89394
37801979. 60000.00000	3.263480E+11	0.00011583	0.00142264	12.28176963	3140.35235
37935064. 60000.00000	3.183362E+11	0.00011917	0.00145325	12.19507635	3168.30678
38066732. 60000.00000	3.107488E+11	0.00012250	0.00148394	12.11378825	3194.74471
38196961. 60000.00000	3.035520E+11	0.00012583	0.00151472	12.03748262	3219.65276
38489907. 60000.00000	2.979864E+11	0.00012917	0.00155000	12.00000036	3246.45226
38489907. 60000.00000	2.904899E+11	0.00013250	0.00158714	11.97838819	3272.40595
38496344. 60000.00000	2.834087E+11	0.00013583	0.00161406	11.88267195	3289.36218
38556543. 60000.00000	2.770530E+11	0.00013917	0.00164106	11.79202831	3305.15122
38615787. 60000.00000	2.709880E+11	0.00014250	0.00166812	11.70610964	3319.76384
38674056. 60000.00000	2.651935E+11	0.00014583	0.00169525	11.62459409	3333.19010
38731341. 60000.00000	2.596514E+11	0.00014917	0.00172246	11.54719198	3345.42022
38787638. 60000.00000	2.543452E+11	0.00015250	0.00174973	11.47363937	3356.44425
38842924. 60000.00000	2.492594E+11	0.00015583	0.00177708	11.40369165	3366.25185
38897202. 60000.00000	2.443803E+11	0.00015917	0.00180449	11.33712995	3374.83283
38950449. 60000.00000	2.396951E+11	0.00016250	0.00183198	11.27374828	3382.17653
39002664. 60000.00000	2.351919E+11	0.00016583	0.00185955	11.21336210	3388.27235
39053828. 60000.00000	2.308601E+11	0.00016917	0.00188719	11.15579760	3393.10930
39103939.	2.266895E+11	0.00017250	0.00191490	11.10089815	3396.67634

60000.00000						
39152976.	2.226710E+11	0.00017583	0.00194270	11.04851568	3398.96212	
60000.00000						
39200930.	2.187959E+11	0.00017917	0.00197057	10.99851501	3399.95511	
60000.00000						
39245176.	2.150421E+11	0.00018250	0.00199852	10.95077169	3394.94090	
60000.00000						
39288015.	2.114153E+11	0.00018583	0.00202654	10.90516984	3388.06345	
60000.00000						
39330457.	2.079143E+11	0.00018917	0.00205465	10.86160004	3381.16475	
60000.00000						
39372504.	2.045325E+11	0.00019250	0.00208284	10.81996357	3382.66262	
60000.00000						
39372504.	2.010511E+11	0.00019583	0.00211500	10.79999936	3388.78992	
60000.00000						
39372504.	1.976862E+11	0.00019917	0.00215100	10.79999936	3394.17923	
60000.00000						
39372504.	1.944321E+11	0.00020250	0.00218700	10.79999936	3397.81817	
60000.00000						
39559465.	1.921917E+11	0.00020583	0.00222300	10.79999936	3399.70674	
60000.00000						
39610701.	1.893739E+11	0.00020917	0.00225095	10.76151502	3398.78959	
60000.00000						
39622159.	1.864572E+11	0.00021250	0.00227579	10.70959175	3393.81200	
60000.00000						
39633517.	1.836302E+11	0.00021583	0.00230067	10.65949023	3388.82199	
60000.00000						
39644756.	1.808886E+11	0.00021917	0.00232560	10.61112463	3383.81970	
60000.00000						
39655896.	1.782287E+11	0.00022250	0.00235058	10.56442416	3378.80472	
60000.00000						
39666912.	1.756468E+11	0.00022583	0.00237561	10.51931155	3373.77725	
60000.00000						
39677825.	1.731396E+11	0.00022917	0.00240069	10.47572458	3376.12785	
60000.00000						
39688611.	1.707037E+11	0.00023250	0.00242581	10.43359458	3380.51401	
60000.00000						
39709844.	1.660342E+11	0.00023917	0.00247621	10.35348022	3387.98400	
60000.00000						
39730597.	1.616160E+11	0.00024583	0.00252680	10.27852857	3393.68856	
60000.00000						
39750857.	1.574291E+11	0.00025250	0.00257761	10.20834696	3397.59222	
60000.00000						
39770607.	1.534557E+11	0.00025917	0.00262862	10.14258349	3399.65826	
60000.00000						
39789302.	1.496776E+11	0.00026583	0.00268001	10.08155787	3396.65885	
60000.00000						
39806856.	1.460802E+11	0.00027250	0.00273181	10.02500403	3388.25646	
60000.00000						
39824183.	1.426538E+11	0.00027917	0.00278374	9.97160017	3379.82095	
60000.00000						

39841273.	1.393864E+11	0.00028583	0.00283579	9.92113173	3371.35189
60000.00000					
39858117.	1.362671E+11	0.00029250	0.00288797	9.87340343	3362.84885
60000.00000					
39874733.	1.332860E+11	0.00029917	0.00294028	9.82824361	3366.32702
60000.00000					
39891083.	1.304341E+11	0.00030583	0.00299273	9.78548491	3374.59268
60000.00000					
39907190.	1.277030E+11	0.00031250	0.00304531	9.74498570	3381.73249
60000.00000					
39923019.	1.250852E+11	0.00031917	0.00309803	9.70660651	3387.72708
60000.00000					
39932239.	1.225542E+11	0.00032583	0.00315298	9.67665589	3392.90944
60000.00000					
39939785.	1.201197E+11	0.00033250	0.00320854	9.64973938	3396.74797
60000.00000					
39946930.	1.177796E+11	0.00033917	0.00326430	9.62446225	3399.12072
60000.00000					
39953652.	1.155286E+11	0.00034583	0.00332026	9.60074294	3399.99576
60000.00000					
40062972.	1.136538E+11	0.00035250	0.00338400	9.60000050	3391.11370
60000.00000					
40171630.	1.118468E+11	0.00035917	0.00344800	9.60000050	3381.60139
60000.00000					
40276552.	1.100954E+11	0.00036583	0.00351200	9.60000050	3372.08908
60000.00000					
40377738.	1.083966E+11	0.00037250	0.00357600	9.60000050	3362.57678
60000.00000					
40475188.	1.067477E+11	0.00037917	0.00364000	9.60000050	3353.06447
60000.00000					
40568901.	1.051462E+11	0.00038583	0.00370400	9.60000050	3343.55216
60000.00000					
40658879.	1.035895E+11	0.00039250	0.00376800	9.60000050	3352.34735
60000.00000					
40745120.	1.020755E+11	0.00039917	0.00383200	9.60000050	3363.63978
60000.00000					

Unfactored (Nominal) Moment Capacity at Concrete Strain of 0.003 = 39893.31100
in-kip

 Computed Values of Load Distribution and Deflection
 for Lateral Loading for Load Case Number 1

Pile-head boundary conditions are Shear and Moment (Pile-head Condition Type 1)
 Specified shear force at pile head = 11000.000 lbs
 Specified moment at pile head = 8196000.000 in-lbs

Specified axial load at pile head = 15000.000 lbs

Output Verification:

Computed forces and moments are within specified convergence limits.


Summary of Pile Response(s)

Definition of Symbols for Pile-Head Loading Conditions:

Type 1 = Shear and Moment, y = pile-head displacement in
Type 2 = Shear and Slope, M = Pile-head Moment lbs-in
Type 3 = Shear and Rot. Stiffness, V = Pile-head Shear Force lbs
Type 4 = Deflection and Moment, S = Pile-head Slope, radians
Type 5 = Deflection and Slope, R = Rot. Stiffness of Pile-head in-lbs/rad

Load Type	Pile-Head Condition 1	Pile-Head Condition 2	Axial Load lbs	Pile-Head Deflection in	Maximum Moment in-lbs	Maximum Shear lbs
1	V= 11000.	M= 8.20E+06	15000.0000	0.2654159	8540881.	-73819.4214

The analysis ended normally.



Structural Analysis Report

Antenna Mount Analysis

*Proposed Verizon
Antenna Upgrade*

Site Ref: Bridgeport NE CT

*541 Broadbridge Road
Bridgeport, CT*

Centek Project No. 21007.69

Date: January 12, 2022

Max Stress Ratio = 1.3%



Prepared for:
Verizon Wireless
20 Alexander Drive
Wallingford, CT 06492

CEN TEK Engineering, Inc.
Structural Analysis – Mount Analysis
Verizon Antenna Upgrade – Bridgeport NE CT
Bridgeport, CT
January 12, 2022

Table of Contents

SECTION 1 – REPORT

- ANTENNA AND APPURTENANCE SUMMARY
- STRUCTURE LOADING
- CONCLUSION

SECTION 2 – CALCULATIONS

- GRAVITY AND ICE LOAD ON APPURTENANCES
- RISA3D OUTPUT REPORT
- PROPOSED CONNECTION TO HOST STRUCTURE

SECTION 3 – REFERENCE MATERIALS

- RF DATA SHEET, DATED 11/19/2021

January 12, 2022

Mr. Andrew Leone
Verizon Wireless
20 Alexander Drive
Wallingford, CT 06492

Re: *Structural Letter ~ Antenna Mount*
Verizon – Site Ref: Bridgeport NE CT
541 Broadbridge Road
Bridgeport, CT 06610

Centek Project No. 21007.69

Dear Mr. Leone,

Centek Engineering, Inc. has reviewed the Verizon antenna installation at the above-referenced site. The purpose of the review is to determine the structural adequacy of the proposed three (3) antenna masts, Pipe 2.0 STD X 8- FT and three (3) bend over plated as detailed on the Centek Engineering construction drawings entitled “Verizon, Bridgeport NE CT, 541 Broadbridge Road Bridgeport, CT” issued 11/22/2021 (Rev. B). The antennas are being proposed inside concealment canisters in an existing flagpole. The review considered the effects of dead load and ice load in accordance with the 2015 International Building Code as modified by the 2018 Connecticut State Building Code (CTBC), including ASCE 7-10 and ANSI/TIA-222-G *Structural Standards for Steel Antenna Towers and Supporting Structures*.

The loads considered in this analysis consist of the following:

- **Verizon:**
Antenna Masts: Three (3) Commscope NNH4-65B-R6 panel antennas, three (3) JMA MX08FIT265-01 panel antenna, three(3) Samsung RT-8808-77A RRU’s and three(3) Commscope CBC61923T-DS-43 diplexers the proposed antenna mounts inside concealments canisters with RAD center elevations of 92 ft +/- & 82 ft +/- AGL.

The antenna mount was analyzed per the requirements of the 2015 International Building Code as modified by the 2018 Connecticut State Building Code, considering a design ice thickness of 0.75-in Bridgeport as required in Annex B of the ANSI/TIA-222-G *Structural Standards for Steel Antenna Towers and Supporting Structures*.

Based on our review of the installation, it is our opinion that **the proposed antenna masts have sufficient capacity** to support the aforementioned antenna configuration. If there are any questions regarding this matter, please feel free to call.

Respectfully Submitted by:

Carlo F. Centore, PE
Principal ~ Structural Engineer



Prepared by:

Fernando J. Palacios
Engineer

*CENTEK Engineering, Inc.
Structural Analysis – Mount Analysis
Verizon Antenna Upgrade – Bridgeport NE CT
Bridgeport, CT
January 12, 2022*

Section 2 - Calculations

Development of Design Heights of Ice on Equipment Per TIA-222-G

Input

Structure Type =	Structure_Type := Pole	(User Input)
Structure Category =	SC := II	(User Input)
Height to Center of Antennas =	z := 92 ft	(User Input)
Radial Ice Thickness =	t _i := 0.75 in	(User Input per Annex B of TIA-222-G)
Radial Ice Density =	I _d := 56.00 pcf	(User Input)
Topographic Factor =	K _{zt} := 1.0	(User Input)

Output

Ice Importance factor=

$$I_{ice} := \begin{cases} \text{if } SC = 1 \\ 0 \\ \text{if } SC = 2 \\ 1.00 \\ \text{if } SC = 3 \\ 1.25 \end{cases} = 1 \quad \text{(TIA 222-G, Table 2-3)}$$

Height escalation factor for ice thickness=

$$K_{lz} := \left(\frac{z}{33} \right)^{0.1} = 1.108 \quad \text{(TIA 222-G, Sec, 2.6.8)}$$

Nominal thickness of radial glaze ice at height z=

$$t_{lz} := 2.0 \cdot t_i \cdot I_{ice} \cdot K_{lz} \cdot K_{zt}^{0.35} = 1.66 \text{ in} \quad \text{(TIA 222-G, Sec, 2.6.8)}$$

Development of Ice Load on Antennas

Antenna Data:

Antenna Model =	Commscope NNH4-65B-R6	
Antenna Shape =	Flat	(User Input)
Antenna Height =	$L_{ant} := 72.0$	in (User Input)
Antenna Width =	$W_{ant} := 19.6$	in (User Input)
Antenna Thickness =	$T_{ant} := 7.8$	in (User Input)
Antenna Weight =	$WT_{ant} := 83.1$	lbs (User Input)
Number of Antennas =	$N_{ant} := 1$	(User Input)
Antenna Aspect Ratio =	$Ar_{ant} := \frac{L_{ant}}{W_{ant}} = 3.7$	

Gravity Load (without ice)

Weight of All Antennas = $WT_{ant} \cdot N_{ant} = 83$ lbs

Gravity Loads (ice only)

Volume of Each Antenna =	$V_{ant} := L_{ant} \cdot W_{ant} \cdot T_{ant} = 1 \cdot 10^4$	cu in
Volume of Ice on Each Antenna =	$V_{ice} := (L_{ant} + 2 \cdot t_{iz}) \cdot (W_{ant} + 2 \cdot t_{iz}) \cdot (T_{ant} + 2 \cdot t_{iz}) - V_{ant} = 8200$	cu in
Weight of Ice on Each Antenna =	$W_{ICEant} := \frac{V_{ice}}{1728} \cdot Id = 266$	lbs
Weight of Ice on All Antennas =	$W_{ICEant} \cdot N_{ant} = 266$	lbs

Development of Ice Load on Antennas

Antenna Data:

Antenna Model =	JMA MX08FIT265-01	
Antenna Shape =	Flat	(User Input)
Antenna Height =	$L_{ant} := 33.1$	in (User Input)
Antenna Width =	$W_{ant} := 11.6$	in (User Input)
Antenna Thickness =	$T_{ant} := 4.5$	in (User Input)
Antenna Weight =	$WT_{ant} := 26.5$	lbs (User Input)
Number of Antennas =	$N_{ant} := 1$	(User Input)
Antenna Aspect Ratio =	$Ar_{ant} := \frac{L_{ant}}{W_{ant}} = 2.9$	

Gravity Load (without ice)

Weight of All Antennas = $WT_{ant} \cdot N_{ant} = 27$ lbs

Gravity Loads (ice only)

Volume of Each Antenna =	$V_{ant} := L_{ant} \cdot W_{ant} \cdot T_{ant} = 1728$	cu in
Volume of Ice on Each Antenna =	$V_{ice} := (L_{ant} + 2 \cdot t_{iz}) \cdot (W_{ant} + 2 \cdot t_{iz}) \cdot (T_{ant} + 2 \cdot t_{iz}) - V_{ant} = 2525$	cu in
Weight of Ice on Each Antenna =	$W_{ICEant} := \frac{V_{ice}}{1728} \cdot Id = 82$	lbs
Weight of Ice on All Antennas =	$W_{ICEant} \cdot N_{ant} = 82$	lbs

Development of Ice Load on RRUS's

RRUS Data:

RRUS Model =	Samsung RT-8808-77A	
RRUS Shape =	Flat	(User Input)
RRUS Height =	$L_{RRUS} := 15$	in (User Input)
RRUS Width =	$W_{RRUS} := 15$	in (User Input)
RRUS Thickness =	$T_{RRUS} := 6.8$	in (User Input)
RRUS Weight =	$WT_{RRUS} := 59.5$	lbs (User Input)
Number of RRUS's =	$N_{RRUS} := 1$	

Gravity Load (without ice)

Weight of All RRUSs = $WT_{RRUS} \cdot N_{RRUS} = 60$ lbs

Gravity Loads (ice only)

Volume of Each RRUS =	$V_{RRUS} := L_{RRUS} \cdot W_{RRUS} \cdot T_{RRUS} = 1530$	cu in
Volume of Ice on Each RRUS =	$V_{ice} := (L_{RRUS} + 2 \cdot t_{iz}) \cdot (W_{RRUS} + 2 \cdot t_{iz}) \cdot (T_{RRUS} + 2 \cdot t_{iz}) - V_{RRUS} = 1869$	cu in
Weight of Ice on Each RRUS =	$W_{ICERRUS} := \frac{V_{ice}}{1728} \cdot Id = 61$	lbs
Weight of Ice on All RRUSs =	$W_{ICERRUS} \cdot N_{RRUS} = 61$	lbs

Development of Ice Load on Diplexers

Diplexer Data:

Diplexer Model =	Commscope CBC61923T-DS-43	
Diplexer Shape =	Flat	(User Input)
Diplexer Height =	$L_{Dipl} := 6.9$	in (User Input)
Diplexer Width =	$W_{Dipl} := 7.8$	in (User Input)
Diplexer Thickness =	$T_{Dipl} := 4.6$	in (User Input)
Diplexer Weight =	$WT_{Dipl} := 14.3$	lbs (User Input)
Number of Diplexer =	$N_{Dipl} := 2$	(User Input)

Gravity Load (without ice)

Weight of All Diplexer = $WT_{Dipl} \cdot N_{Dipl} = 29$ lbs

Gravity Loads (ice only)

Volume of Each Diplexer =	$V_{Dipl} := L_{Dipl} \cdot W_{Dipl} \cdot T_{Dipl} = 248$	cu in
Volume of Ice on Each Diplexer =	$V_{ice} := (L_{Dipl} + 2 \cdot t_{iz}) \cdot (W_{Dipl} + 2 \cdot t_{iz}) \cdot (T_{Dipl} + 2 \cdot t_{iz}) - V_{Dipl} = 654$	cu in
Weight of Ice on Each Diplexer =	$W_{ICEDipl} := \frac{V_{ice}}{1728} \cdot Id = 21$	lbs
Weight of Ice on All Diplexer =	$W_{ICEDipl} \cdot N_{Dipl} = 42$	lbs



Envelope Only Solution

Centek Engineering
FJP
21007.69

Bridgeport NE CT - Mount
Member Framing

Jan 12, 2022 at 9:02 AM
Bridgeprt NE CT_AMA.r3d

(Global) Model Settings

Display Sections for Member Calcs	5
Max Internal Sections for Member Calcs	97
Include Shear Deformation?	Yes
Increase Nailing Capacity for Wind?	Yes
Include Warping?	Yes
Trans Load Btwn Intersecting Wood Wall?	Yes
Area Load Mesh (in^2)	144
Merge Tolerance (in)	.12
P-Delta Analysis Tolerance	0.50%
Include P-Delta for Walls?	Yes
Automatically Iterate Stiffness for Walls?	Yes
Max Iterations for Wall Stiffness	3
Gravity Acceleration (ft/sec^2)	32.2
Wall Mesh Size (in)	12
Eigensolution Convergence Tol. (1.E-)	4
Vertical Axis	Y
Global Member Orientation Plane	XZ
Static Solver	Sparse Accelerated
Dynamic Solver	Accelerated Solver

Hot Rolled Steel Code	AISC 14th(360-10): LRFD
Adjust Stiffness?	Yes(Iterative)
RISACconnection Code	AISC 14th(360-10): ASD
Cold Formed Steel Code	AISI S100-10: ASD
Wood Code	AWC NDS-12: ASD
Wood Temperature	< 100F
Concrete Code	ACI 318-11
Masonry Code	ACI 530-11: ASD
Aluminum Code	AA ADM1-10: ASD - Building
Stainless Steel Code	AISC 14th(360-10): ASD
Adjust Stiffness?	Yes(Iterative)

Number of Shear Regions	4
Region Spacing Increment (in)	4
Biaxial Column Method	Exact Integration
Parme Beta Factor (PCA)	.65
Concrete Stress Block	Rectangular
Use Cracked Sections?	Yes
Use Cracked Sections Slab?	No
Bad Framing Warnings?	No
Unused Force Warnings?	Yes
Min 1 Bar Diam. Spacing?	No
Concrete Rebar Set	REBAR_SET_ASTMA615
Min % Steel for Column	1
Max % Steel for Column	8

(Global) Model Settings, Continued

Seismic Code	ASCE 7-10
Seismic Base Elevation (ft)	Not Entered
Add Base Weight?	Yes
Ct X	.02
Ct Z	.02
T X (sec)	Not Entered
T Z (sec)	Not Entered
R X	3
R Z	3
Ct Exp. X	.75
Ct Exp. Z	.75
SD1	1
SDS	1
S1	1
TL (sec)	5
Risk Cat	I or II
Drift Cat	Other
Om Z	1
Om X	1
Cd Z	1
Cd X	1
Rho Z	1
Rho X	1

Hot Rolled Steel Properties

	Label	E [ksi]	G [ksi]	Nu	Therm (/1...	Density[k/ft^3]	Yield[ksi]	Ry	Fu[ksi]	Rt
1	A36 Gr.36	29000	11154	.3	.65	.49	36	1.5	58	1.2
2	A572 Gr.50	29000	11154	.3	.65	.49	50	1.1	58	1.2
3	A992	29000	11154	.3	.65	.49	50	1.1	58	1.2
4	A500 Gr.42	29000	11154	.3	.65	.49	42	1.3	58	1.1
5	A500 Gr.46	29000	11154	.3	.65	.49	46	1.2	58	1.1
6	A53 Grade B	29000	11154	.3	.65	.49	35	1.5	58	1.2

Hot Rolled Steel Section Sets

	Label	Shape	Type	Design Li...	Material	Design R...	A [in2]	Iyy [in4]	Izz [in4]	J [in4]
1	(P) Antenna Mast PIPE 2...	PIPE 2.0	Column	None	A53 Grade B	Typical	1.02	.627	.627	1.25
2	(P)Folded Plate	Folded Plate 7.75x...	Column	None	A36 Gr.36	Typical	2.626	5.835	26.377	.021

Hot Rolled Steel Design Parameters

	Label	Shape	Length[ft]	Lbyy[ft]	Lbzz[ft]	Lcomp top[...Lcomp bot[...L-torq...	Kyy	Kzz	Cb	Functi...
1	M1	(P) Antenn...	8			Lbyy				Lateral
2	M2	(P)Folded ...	3							Lateral

Member Primary Data

	Label	I Joint	J Joint	K Joint	Rotate(...)	Section/Shape	Type	Design List	Material	Design ...
1	M1	N12	N10			(P) Antenna Mast PIPE 2.0 STD	Colu...	None	A53 Gr..	Typical
2	M2	N6	N5			(P)Folded Plate	Colu...	None	A36 Gr..	Typical

Joint Coordinates and Temperatures

	Label	X [ft]	Y [ft]	Z [ft]	Temp [F]	Detach From Diaphragm
1	N10	0	-8	-0.	0	
2	N12	0	0	-0.	0	
3	N3	0	-1.5	-0.	0	
4	N4	0	-6.5	-0.	0	
5	N5	0	-13	-0.	0	
6	N6	0	-10	-0.	0	
7	N7	0	-10.666667	-0.	0	
8	N8	0	-12.333333	-0.	0	

Joint Boundary Conditions

	Joint Label	X [k/in]	Y [k/in]	Z [k/in]	X Rot.[k-ft/rad]	Y Rot.[k-ft/rad]	Z Rot.[k-ft/rad]
1	N3	Reaction	Reaction	Reaction		Reaction	
2	N4	Reaction	Reaction	Reaction		Reaction	
3	N7	Reaction	Reaction	Reaction		Reaction	
4	N8	Reaction	Reaction	Reaction		Reaction	

Member Point Loads (BLC 2 : Dead Load)

	Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]
1	M1	Y	-.042	1
2	M1	Y	-.042	7
3	M2	Y	-.014	.25
4	M2	Y	-.014	2.75

Member Point Loads (BLC 3 : Ice Load)

	Member Label	Direction	Magnitude[k,k-ft]	Location[ft,%]
1	M1	Y	-.134	1
2	M1	Y	-.134	7
3	M2	Y	-.041	.25
4	M2	Y	-.041	2.75

Member Distributed Loads

Member Label	Direction	Start Magnitude[k/ft,F,ksf]	End Magnitude[k/ft,F,ksf]	Start Location[f..End Location[ft..
No Data to Print ...				

Basic Load Cases

	BLC Description	Category	X Gravity	Y Gravity	Z Gravity	J...	Point	Distributed Area(Me...	Surface(...
1	Self Weight	None		-1					
2	Dead Load	None					4		
3	Ice Load	None					4		



Member Code Checks Displayed (Enveloped)
Envelope Only Solution

Centek Engineering
FJP
21007.69

Bridgeport NE CT - Mount
Member Unity Check

Jan 12, 2022 at 9:03 AM
Bridgeport NE CT_AMA.r3d

Proposed Connection to Host Structure for Mounts Supporting Antenna at 92 - ft Rad. Elevation

Bolts Grade	A325	
Number of Bolts =	$n_b := 2$	(User Input)
Bolt Diameter =	$d\phi := \frac{1}{2} \text{ in}$	(User Input)
Nominal Tensile Strength=	$F_{nt} := 90 \text{ ksi}$	(AISC, Steel construction manual 14th ed., Table J3.2)
Nominal Shear Strength=	$F_{nv} := 54 \text{ ksi}$	(AISC, Steel construction manual 14th ed., Table J3.2)
Safety Factor=	$\phi := 0.75$	(User Input)
Horizontal Spacing Between Bolts=	$S := 3 \text{ in}$	(User Input)

Reactions at Connection:

Shear X =	Shear _x := 0 · kip	(User Input)
Vertical=	Vertical := 0.201 kip	(User Input)
Shear Z =	Shear _z := 0 · kip	(User Input)
Moment X=	M _x := 0 · kip · ft	(User Input)
Moment Y=	M _y := 0 · kip · ft	(User Input)
Moment Z=	M _z := 0 kip · ft	(User Input)

Anchor Check:

Bolt Area=	$a_b := \pi \cdot \left(\frac{d\phi}{2}\right)^2 = 0.196 \text{ in}^2$	
Shear Strength=	$R_{nv} := F_{nv} \cdot a_b \cdot \phi = 7.952 \text{ kip}$	(AISC, Steel construction manual 14th ed., Formula J3-1)
Shear Stress per Bolt=	$V_{act} := \frac{\sqrt{\text{Shear}_x^2 + \text{Vertical}^2}}{n_b} + \frac{M_z}{S \cdot \frac{n_b}{2}} = 0.101 \text{ kip}$	
	Condition1 := if ($V_{act} \leq R_{nv}$, "OK", "Overstressed") = "OK"	$\frac{V_{act}}{R_{nv}} = 1.3\%$

Condition1 = "OK"

$$f_v := \frac{V_{act}}{a_b} = 0.512 \text{ ksi}$$

Tensile Stress Adjusted for Shear=	$F'_{nt} := \left\ \begin{array}{l} \text{if } \left(1.3 F_{nt} - \frac{F_{nt}}{\phi \cdot F_{nv}} \cdot f_v \right) \leq F_{nt} \\ 1.3 F_{nt} - \frac{F_{nt}}{\phi \cdot F_{nv}} \cdot f_v \\ \text{else} \\ F_{nt} \end{array} \right\ = 90 \text{ ksi}$	(AISC, Steel construction manual 14th ed., Formula J3-3A)
Tensile Strength=	$R_{nt} := F'_{nt} \cdot a_b \cdot \phi = 13.254 \text{ kip}$	(AISC, Steel construction manual 14th ed., Formula J3-2)

$$T_{act} := \frac{\text{Shear}_z}{n_b} + \frac{M_y}{S \cdot \frac{n_b}{2}} + \frac{M_x}{S \cdot \frac{n_b}{2}} = 0 \text{ kip}$$

$$f_t := \frac{T_{act}}{a_b} = 0 \text{ ksi}$$

Condition2 := if ($f_t \leq F'_{nt} \cdot \phi$, "OK", "Overstressed") = "OK"

Condition2 = "OK"

$$\frac{T_{act}}{R_{nt}} = 0$$

Proposed Connection to Host Structure for Mounts Supporting Antenna at 82 - ft Rad. Elevation

Bolts Grade	A325	
Number of Bolts =	$n_b := 2$	(User Input)
Bolt Diameter =	$d\phi := \frac{1}{2} \text{ in}$	(User Input)
Nominal Tensile Strength=	$F_{nt} := 90 \text{ ksi}$	(AISC, Steel construction manual 14th ed., Table J3.2)
Nominal Shear Strength=	$F_{nv} := 54 \text{ ksi}$	(AISC, Steel construction manual 14th ed., Table J3.2)
Safety Factor=	$\phi := 0.75$	(User Input)
Horizontal Spacing Between Bolts=	$S := 3 \text{ in}$	(User Input)

Reactions at Connection:

Shear X =	Shear _x := 0 · kip	(User Input)
Vertical=	Vertical := 0.074 kip	(User Input)
Shear Z =	Shear _z := 0 · kip	(User Input)
Moment X=	M _x := 0 · kip · ft	(User Input)
Moment Y=	M _y := 0 · kip · ft	(User Input)
Moment Z=	M _z := 0 kip · ft	(User Input)

Anchor Check:

Bolt Area=	$a_b := \pi \cdot \left(\frac{d\phi}{2}\right)^2 = 0.196 \text{ in}^2$	
Shear Strength=	$R_{nv} := F_{nv} \cdot a_b \cdot \phi = 7.952 \text{ kip}$	(AISC, Steel construction manual 14th ed., Formula J3-1)
Shear Stress per Bolt=	$V_{act} := \frac{\sqrt{\text{Shear}_z^2 + \text{Vertical}^2}}{n_b} + \frac{M_z}{S \cdot \frac{n_b}{2}} = 0.037 \text{ kip}$	
	Condition1 := if ($V_{act} \leq R_{nv}$, "OK", "Overstressed") = "OK"	$\frac{V_{act}}{R_{nv}} = 0.5\%$

Condition1 = "OK"

$$f_v := \frac{V_{act}}{a_b} = 0.188 \text{ ksi}$$

Tensile Stress Adjusted for Shear=	$F'_{nt} := \begin{cases} \text{if } \left(1.3 F_{nt} - \frac{F_{nt}}{\phi \cdot F_{nv}} \cdot f_v\right) \leq F_{nt} \\ 1.3 F_{nt} - \frac{F_{nt}}{\phi \cdot F_{nv}} \cdot f_v \\ \text{else} \\ F_{nt} \end{cases} = 90 \text{ ksi}$	(AISC, Steel construction manual 14th ed., Formula J3-3A)
------------------------------------	---	---

Tensile Strength= $R_{nt} := F'_{nt} \cdot a_b \cdot \phi = 13.254 \text{ kip}$ (AISC, Steel construction manual 14th ed., Formula J3-2)

Tension Force Each Bolt= $T_{act} := \frac{\text{Shear}_x}{n_b} + \frac{M_y}{S \cdot \frac{n_b}{2}} + \frac{M_x}{S \cdot \frac{n_b}{2}} = 0 \text{ kip}$

Tension Stress Each Bolt= $f_t := \frac{T_{act}}{a_b} = 0 \text{ ksi}$

Condition2 := if ($f_t \leq F'_{nt} \cdot \phi$, "OK", "Overstressed") = "OK"

Condition2 = "OK"

Flange Bolt and Flange Plate Analysis:

Input Data:

Tower Reactions:

Overturning Moment = $OM := 99.241 \cdot ft \cdot kips$ (Input From RisaTower)
 Shear Force = $Shear := 5.64 \cdot kips$ (Input From RisaTower)
 Axial Force = $Axial := 9.547 \cdot kips$ (Input From RisaTower)

Flange Bolt Data:

Use ASTM A325

Number of Flange Bolts = $N := 12$ (User Input)
 Diameter of Bolt Circle = $D_{bc} := 32 \cdot in$ (User Input)
 Bolt Minimum Tensile Strength = $F_{vb} := 120 \cdot ksi$ (User Input)
 Bolt Modulus = $E := 29000 \cdot ksi$ (User Input)
 Diameter of Flange Bolts = $D := 1.00 \cdot in$ (User Input)
 Threads per Inch = $n := 8$ (User Input)

Flange Plate Data:

Use ASTM A572 Grade 50

Plate Yield Strength = $F_{y_{bp}} := 50 \cdot ksi$ (User Input)
 Flange Plate Thickness = $t_{bp} := 1.25 \cdot in$ (User Input)
 Flange Plate Diameter = $D_{bp} := 35 \cdot in$ (User Input)
 Outer Pole Diameter = $D_{pole} := 10 \cdot in$ (User Input)

Geometric Layout Data:

Distance from Bolts to Centroid of Pole:

Radius of Bolt Circle = $R_{bc} := \frac{D_{bc}}{2} = 16 \text{ in}$

Distance to Bolts = $i := 1 \dots N$

$$d_i := \begin{cases} \theta \leftarrow 2 \cdot \pi \cdot \left(\frac{i}{N}\right) \\ d \leftarrow R_{bc} \cdot \sin(\theta) \end{cases}$$

$d_1 = 8.00 \text{ in}$	$d_7 = -8.00 \text{ in}$
$d_2 = 13.86 \text{ in}$	$d_8 = -13.86 \text{ in}$
$d_3 = 16.00 \text{ in}$	$d_9 = -16.00 \text{ in}$
$d_4 = 13.86 \text{ in}$	$d_{10} = -13.86 \text{ in}$
$d_5 = 8.00 \text{ in}$	$d_{11} = -8.00 \text{ in}$
$d_6 = 0.00 \text{ in}$	$d_{12} = 0.00 \text{ in}$

$$d = \begin{bmatrix} 0 \\ \vdots \end{bmatrix} \text{ in}$$

Critical Distances For Bending in Plate:

Outer Pole Radius = $R_{pole} := \frac{D_{pole}}{2} = 5 \text{ in}$

Moment Arms of Bolts about Neutral Axis = $MA_i := \text{if} \left(d_i \geq R_{pole}, d_i - R_{pole}, 0 \cdot \text{in} \right)$

$MA_1 = 3.00 \text{ in}$	$MA_7 = 0.00 \text{ in}$
$MA_2 = 8.86 \text{ in}$	$MA_8 = 0.00 \text{ in}$
$MA_3 = 11.00 \text{ in}$	$MA_9 = 0.00 \text{ in}$
$MA_4 = 8.86 \text{ in}$	$MA_{10} = 0.00 \text{ in}$
$MA_5 = 3.00 \text{ in}$	$MA_{11} = 0.00 \text{ in}$
$MA_6 = 0.00 \text{ in}$	$MA_{12} = 0.00 \text{ in}$

$$MA = \begin{bmatrix} 0 \\ \vdots \end{bmatrix} \text{ in}$$

Effective Width of Flange plate for Bending = $B_{eff} := 0.8 \cdot 2 \cdot \sqrt{\left(\frac{D_{bp}}{2}\right)^2 - \left(\frac{D_{pole}}{2}\right)^2} = 26.8 \text{ in}$

Flange Bolt Analysis:

Calculated Flange Bolt Properties:

Polar Moment of Inertia = $I_p := \sum_i (d_i)^2 = (1.536 \cdot 10^3) \text{ in}^2$

Gross Area of Bolt = $A_g := \frac{\pi}{4} \cdot D^2 = 0.785 \text{ in}^2$

Net Area of Bolt = $A_n := \frac{\pi}{4} \cdot \left(D - \frac{0.9743 \cdot \text{in}}{n} \right)^2 = 0.606 \text{ in}^2$

Net Diameter = $D_n := \frac{2 \cdot \sqrt{A_n}}{\sqrt{\pi}} = 0.878 \text{ in}$

Radius of Gyration of Bolt = $r := \frac{D_n}{4} = 0.22 \text{ in}$

Section Modulus of Bolt = $S_x := \frac{\pi \cdot D_n^3}{32} = 0.066 \text{ in}^3$

Check Flange Bolt Tension Force:

Maximum Tensile Force = $T_{Max} := OM \cdot \frac{R_{bc}}{I_p} - \frac{Axial}{N} = 11.6 \text{ kips}$

Maximum Shear Force = $V_{Max} := \frac{Shear}{N} = 0.47 \text{ kips}$

Design Tensile Strength = $\Phi R_{nt} := (0.75 \cdot F_{ub} \cdot 0.75 \cdot A_g) = 53 \text{ kips}$

Bolt Tension % of Capacity = $\frac{T_{Max}}{\Phi R_{nt}} = 21.90\%$

Condition1 = $Condition1 := \text{if} \left(\frac{T_{Max}}{\Phi R_{nt}} \leq 1.00, \text{"OK"}, \text{"Overstressed"} \right)$

Condition1 = "OK"

Design Shear Strength = $\Phi R_{nv} := (0.75 \cdot 0.45 \cdot F_{ub} \cdot A_g) = 31.8 \text{ kips}$

Bolt Tension % of Capacity = $\frac{V_{Max}}{\Phi R_{nv}} = 1.48\%$

Condition2 = $Condition2 := \text{if} \left(\left(\frac{V_{Max}}{\Phi R_{nv}} \right)^2 + \left(\frac{T_{Max}}{\Phi R_{nt}} \right)^2 \leq 1.00, \text{"OK"}, \text{"Overstressed"} \right) = \text{"OK"}$

Condition2 = "OK"

Flange Plate Analysis:

Force from Bolts =
$$C_i := \frac{OM \cdot d_i}{I_p} + \frac{Axial}{N}$$

$C_1 = 7.0 \text{ kips}$ $C_7 = -5.4 \text{ kips}$

$C_2 = 11.5 \text{ kips}$ $C_8 = -9.9 \text{ kips}$

$C_3 = 13.2 \text{ kips}$ $C_9 = -11.6 \text{ kips}$

$C_4 = 11.5 \text{ kips}$ $C_{10} = -9.9 \text{ kips}$ $C = \begin{bmatrix} 0 \\ \vdots \end{bmatrix} \text{ kips}$

$C_5 = 7.0 \text{ kips}$ $C_{11} = -5.4 \text{ kips}$

$C_6 = 0.8 \text{ kips}$ $C_{12} = 0.8 \text{ kips}$

Maximum Bending Stress in Plate =
$$f_{bp} := \sum_i \frac{4 \cdot C_i \cdot MA_i}{(E_{eff} \cdot t_{bp}^2)} = 37.4 \text{ ksi}$$

$F_{bp} := 0.9 \cdot F_{y_{bp}} = 45 \text{ ksi}$

Allowable Bending Stress in Plate =
$$\frac{f_{bp}}{F_{bp}} = 83.0\%$$

Plate Bending Stress % of Capacity =
$$Condition3 := \text{if} \left(\frac{f_{bp}}{F_{bp}} < 1.00, \text{"Ok"}, \text{"Overstressed"} \right)$$

Condition3 = $Condition3 = \text{"Ok"}$

ATTACHMENT 3

Site Name: **BRIDGEPORT NE CT**
 Cumulative Power Density

Operator	Operating Frequency (MHz)	Number of Trans.	ERP Per Trans. (watts)	Total ERP (watts)	Distance to Target (feet)	Calculated Power Density (mW/cm ²)	Maximum Permissible Exposure* (mW/cm ²)	Fraction of MPE (%)
VZW 700	751	4	510	2041	92	0.0087	0.5007	1.73%
VZW CDMA	876.03	2	0	0	92	0.0000	0.5840	0.00%
VZW Cellular	874	4	744	2978	92	0.0127	0.5827	2.17%
VZW PCS	1980	4	879	3514	92	0.0149	1.0000	1.49%
VZW AWS	2120	4	1016	4063	92	0.0173	1.0000	1.73%
VZW CBRS	3625	4	0	0	82	0.0000	1.0000	0.00%
VZW CBAND	3730.08	2	5493	10986	82	0.0588	1.0000	5.88%
Total Percentage of Maximum Permissible Exposure								13.06%

*Guidelines adopted by the FCC on August 1, 1996, 47 CFR Part 1 based on NCRP Report 86, 1986 and generally on ANSI/IEEE C95.1-1992

**Calculation includes a -10 dB Off Beam Antenna Pattern Adjustment pursuant to Attachments B and C of the Siting Council's November 10, 2015 Memorandum for Exempt Modification filings

MHz = Megahertz

mW/cm² = milliwatts per square centimeter

ERP = Effective Radiated Power

Absolute worst case maximum values used.

ATTACHMENT 4

February 24, 2022

Via Certificate of Mailing

Joseph Ganim, Mayor
City of Bridgeport
Margaret E. Morton Government Center
999 Broad Street
Bridgeport, CT 06604

Re: **Proposed Modifications to an Existing Telecommunications Facility at 541
Broadbridge Road in Bridgeport, Connecticut**

Dear Mayor Ganim:

This firm represents Cellco Partnership d/b/a Verizon Wireless (“Cellco”). Today, Cellco filed a Sub-Petition for Declaratory Ruling (“Sub-Petition”) with the Connecticut Siting Council (“Council”) seeking approval to modify its existing wireless telecommunications facility at 541 Broadbridge Road in Bridgeport, Connecticut (the “Property”). Cellco intends to install replace six (6) antennas with six (6) newer model antennas at the same levels within the flag pole tower and replace nine (9) remote radio heads (“RRHs”) with nine (9) newer model RRHs within the flag pole tower. In order to accommodate Cellco’s replacement antennas, the upper portions of the flag pole tower screening shroud will be widened from 36 inch diameter to 48 inch diameter. Equipment associated with Cellco’s antennas will not change as part of these facility modifications.

As presented in the Sub-Petition, the proposed facility modifications constitute an eligible facility request pursuant to Section 6409(a) of the Federal Middle Class Tax Relief and Job Creation act of 2012 (47 U.S.C. § 1455(a)) and the October 21, 2014 Order of the Federal Communications Commission (FCC-14-153). A copy of the full Sub-Petition is attached for your review. Landowners whose property abuts the Property were also sent notice of this filing along with a copy of the Sub-Petition.

24327913-v1

Robinson+Cole

Joseph Ganim, Mayor
February 24, 2022
Page 2

Pursuant to its decision in Petition No. 1133, comments or concerns regarding this proposal should be submitted to the Council within thirty (30) days of the date of the attached Sub-Petition.

Please contact me if you have any questions regarding this proposal.

Sincerely,

A handwritten signature in black ink, appearing to read "Kenneth C. Baldwin". The signature is fluid and cursive, with a long horizontal stroke at the end.

Kenneth C. Baldwin

Attachment

February 24, 2022

Via Certificate of Mailing

Dennis Buckley, Zoning Administrator
City of Bridgeport
45 Lyon Terrace
Bridgeport, CT 06604

Re: **Proposed Modifications to an Existing Telecommunications Facility at 541
Broadbridge Road in Bridgeport, Connecticut**

Dear Mr. Buckley:

This firm represents Cellco Partnership d/b/a Verizon Wireless (“Cellco”). Today, Cellco filed a Sub-Petition for Declaratory Ruling (“Sub-Petition”) with the Connecticut Siting Council (“Council”) seeking approval to modify its existing wireless telecommunications facility at 541 Broadbridge Road in Bridgeport, Connecticut (the “Property”). Cellco intends to install replace six (6) antennas with six (6) newer model antennas at the same levels within the flag pole tower and replace nine (9) remote radio heads (“RRHs”) with nine (9) newer model RRHs within the flag pole tower. In order to accommodate Cellco’s replacement antennas, the upper portions of the flag pole tower screening shroud will be widened from 36 inch diameter to 48 inch diameter. Equipment associated with Cellco’s antennas will not change as part of these facility modifications.

As presented in the Sub-Petition, the proposed facility modifications constitute an eligible facility request pursuant to Section 6409(a) of the Federal Middle Class Tax Relief and Job Creation act of 2012 (47 U.S.C. § 1455(a)) and the October 21, 2014 Order of the Federal Communications Commission (FCC-14-153). A copy of the full Sub-Petition is attached for your review. Landowners whose property abuts the Property were also sent notice of this filing along with a copy of the Sub-Petition.

24327954-v1

Robinson+Cole

Dennis Buckley, Zoning Administrator
February 24, 2022
Page 2

Pursuant to its decision in Petition No. 1133, comments or concerns regarding this proposal should be submitted to the Council within thirty (30) days of the date of the attached Sub-Petition.

Please contact me if you have any questions regarding this proposal.

Sincerely,

A handwritten signature in black ink, appearing to read "Kenneth C. Baldwin". The signature is fluid and cursive, with a long horizontal stroke at the end.

Kenneth C. Baldwin

Attachment

February 24, 2022

Via Certificate of Mailing

Beardsley Plaza Limited
P.O. Box 3580
Stamford, CT 06905

Re: **Proposed Modifications to an Existing Telecommunications Facility at 541
Broadbridge Road in Bridgeport, Connecticut**

Dear Sir or Madam:

This firm represents Cellco Partnership d/b/a Verizon Wireless (“Cellco”). Today, Cellco filed a Sub-Petition for Declaratory Ruling (“Sub-Petition”) with the Connecticut Siting Council (“Council”) seeking approval to modify its existing wireless telecommunications facility at 541 Broadbridge Road in Bridgeport, Connecticut (the “Property”). Cellco intends to install replace six (6) antennas with six (6) newer model antennas at the same levels within the flag pole tower and replace nine (9) remote radio heads (“RRHs”) with nine (9) newer model RRHs within the flag pole tower. In order to accommodate Cellco’s replacement antennas, the upper portions of the flag pole tower screening shroud will be widened from 36 inch diameter to 48 inch diameter. Equipment associated with Cellco’s antennas will not change as part of these facility modifications.

As presented in the Sub-Petition, the proposed facility modifications constitute an eligible facility request pursuant to Section 6409(a) of the Federal Middle Class Tax Relief and Job Creation act of 2012 (47 U.S.C. § 1455(a)) and the October 21, 2014 Order of the Federal Communications Commission (FCC-14-153). A copy of the full Sub-Petition is attached for your review. Landowners whose property abuts the Property were also sent notice of this filing along with a copy of the Sub-Petition.

24326432-v1

Robinson+Cole

Beardsley Plaza Limited
February 24, 2022
Page 2

Pursuant to its decision in Petition No. 1133, comments or concerns regarding this proposal should be submitted to the Council within thirty (30) days of the date of the attached Sub-Petition.

Please contact me if you have any questions regarding this proposal.

Sincerely,

A handwritten signature in black ink, appearing to read "Kenneth C. Baldwin". The signature is fluid and cursive, with a long horizontal stroke at the end.

Kenneth C. Baldwin

Attachment

ATTACHMENT 5

KENNETH C. BALDWIN

280 Trumbull Street
Hartford, CT 06103-3597
Main (860) 275-8200
Fax (860) 275-8299
kbaldwin@rc.com
Direct (860) 275-8345

Also admitted in Massachusetts
and New York

February 24, 2022

Via Certificate of Mailing

«Name_and_Address»

Re: Proposed Modifications to a Telecommunications Facility at 541 Broadbridge Road in Bridgeport, Connecticut

Dear «Salutation»:

This firm represents Cellco Partnership d/b/a Verizon Wireless (“Cellco”). Today, Cellco filed a Sub-Petition for Declaratory Ruling (“Sub-Petition”) with the Connecticut Siting Council (“Council”) seeking approval to modify its existing wireless telecommunications facility at 541 Broadbridge Road in Bridgeport, Connecticut (the “Property”). Cellco intends to install replace six (6) antennas with six (6) newer model antennas at the same levels within the flag pole tower and replace nine (9) remote radio heads (“RRHs”) with nine (9) newer model RRHs within the flag pole tower. In order to accommodate Cellco’s replacement antennas, the upper portions of the flag pole tower screening shroud will be expanded from 36 inch diameter to 48 inch diameter. Equipment associated with Cellco’s antennas will not change as part of these facility modifications.

As presented in the Sub-Petition, the proposed facility modifications constitute an eligible facility request pursuant to Section 6409(a) of the Federal Middle Class Tax Relief and Job Creation act of 2012 (47 U.S.C. § 1455(a)) and the October 21, 2014 Order of the Federal Communications Commission (FCC-14-153). A copy of the full Sub-Petition is attached for your review.

February 24, 2022

Page 2

Pursuant to its decision in Petition No. 1133, comments or concerns regarding this proposal should be submitted to the Council within thirty (30) days of the date of the attached Sub-Petition.

This notice is being sent to you because you are listed as an owner of land that abuts the Property. If you have any questions regarding the Sub-Petition, the Council's process for reviewing the Sub-Petition or the details of the filing itself, please feel free to contact me at the number listed above. You may also contact me or the Council directly at 860-827-2935.

Sincerely,

A handwritten signature in black ink, appearing to read "Kenneth C. Baldwin". The signature is fluid and cursive, with a long horizontal stroke at the end.

Kenneth C. Baldwin

Attachment

CELLCO PARTNERSHIP D/B/A VERIZON WIRELESS

ABUTTING PROPERTY OWNERS

**541 BROADBRIDGE ROAD
BRIDGEPORT, CONNECTICUT**

	Property Address	Owner's and Mailing Address
1.	1086 Huntington Turnpike	Johnny Zevallas, Jr. 805 93 rd Avenue North Naples, FL 34108
2.	29 Holland Road	Stephanie Ferreira 29 Holland Road Bridgeport, CT 06610
3.	559 Broadbridge Road	Beardsley Plaza Limited P.O. Box 3580 Stamford, CT 06905
4.	570 Broadbridge Road	Peter and Wilma Stevens and Luna Taylor 570 Broadbridge Road Bridgeport, CT 06610-1241
5.	495 Hooker Road	Rockman Ferrigno, Et Al 1000 Huntington Turnpike Bridgeport, CT 06610
6.	1000 Huntington Turnpike	Treelands Incorporated 1000 Huntington Turnpike Bridgeport, CT 06610
7.	1055 Huntington Turnpike	1055 Huntington Turnpike LLC 1425 Noble Avenue Bridgeport, CT 06606
8.	1077 Huntington Turnpike	Robert Discala 175 Hilltop Circle Trumbull, CT 06611