

July 23, 2021

Attn: Mr. Pat Hastings Dynamic Energy 1550 Liberty Ridge Drive, Suite 310 Wayne, PA 19087

(484) 318-8802

RE: STAG – Pepe Farms

Roof Framing Analysis 40 Pepes Farm Road Milford, CT 06460

SEI Project No.: 21355.00

Dear Mr. Hastings,

Structural Enginuity Inc. (SEI) has analyzed the existing building for a new roof solar array using the 2018 Connecticut State Building Code. Based on Dynamic Energy's site observations, the roof framing is understood to consist of a metal deck on 30" deep joists spaced 6'-2" apart and spanning between 36" deep joist girders. The building uses steel columns consisting of wide flange shapes.

The exiting roof has been analyzed to support a new solar array system. The building construction can support a new solar PV array with a maximum average load of 6.0 psf. These proposed loads and the analysis of the existing members can be seen in SEI's attached calculations. This weight is typically enough to accommodate a fully ballasted racking system. Therefore, it is SEI's professional opinion that the existing roof framing is structurally adequate to support the proposed solar array system. It should be noted that the proposed loading is assuming that the proposed solar array covers the entirety of the roof and the existing framing may be able to support a higher load for an array that is limited to only a portion of the roof surface. If a higher load is necessary, SEI would need to further analyze the detailed racking layout in order to determine if the framing is acceptable.

Please contact our office, at your convenience, should you have any further questions relating to this matter.

Sincerely,

Peter Martin Engineer III

pmartin@structuralenginuityinc.com

Allan T. Myket, P.E. President/Founder

amyket@structuralenginuityinc.com

7/23/2021

Structural Enginuity Inc.

Attachments:

- SEI Roof Structural Framing Analysis
- Dynamic Energy Drawings



Structural Enginuity, Inc.

1815 W. Diehl Rd, Ste 100 Naperville, IL 60563

(630) 219-1997

www.structuralenginuityinc.com

Project Name: STAG Industrial Holdings

Project No.: 21355.00

Client Name: Dynamic Energy

Date: 7/23/2021

Project Name: STAG INDUSTRIAL HOLDINGS

Roof Structural Analysis

40 Peper Farm Road

Milford, CT 06460

Project Client: Dynamic Energy[™]

1550 Liberty Ridge Drive, Suite 310

Wayne, PA 19087

(877) 809-8884

Client Contact: Pat Hastings

phastings@dynamicenergy.com

Design References: 2018 Connecticut State Building Code

ASCE 7-16

Scope of Work:

Provide structural engineering services required in the preparation of construction contract documents for the installation of solar panels at the address listed above. The racking system and proposed array layout, provided by client, will be used in conformance with the 2018 Connecticut State Building Code to determine if the existing structure has the capacity to support the addition of the array.

Existing Structure:

The storage facility Is approximately 642'-5" x 315'-4" with a flat roof. The roof is supported by 30" deep open web steel joists which run to 36" deep joist girders.



Loads



Structural Enginuity, Inc.

1815 W. Diehl Rd, Ste 100 Naperville, IL 60563 (630) 219-1997

www.structuralenginuityinc.com

Project Name: STAG Industrial Holdings

Project No.: 21355.00

Client Name: Dynamic Energy

Date: 7/23/2021

DEAD LOADS

Building Section: Roof 1

Building Section Description: Solar PV modules to be mounted on roof with a ballasted racking

system. The roof consists of a waterproofing membrane over rigid insulation and a metal deck. The deck is supported by open web

metal bar joists

Existing Dead Loads

Roof deck with foam insulation 3 psf

Metal Deck 3 psf

Steel Joists 3 psf

MEP & Misc 5 psf

14 psf

Proposed Dead Loads

Proposed Solar Array 6 psf

LIVE LOADS

Building Section: Main Roof

Proposed Live Loads

Roofs - Ordinary flat pitched, and curved roofs 20 psf IBC 2018 Table 1607.1

Note 1: Per IBC 2018 1607.13.5.1: Roof live loads need not be applied to the area covered by photovoltaic panels where the clear space between the panels and the roof surface is 24 inches or less.



Structural Enginuity, Inc.

1815 W. Diehl Rd, Ste 100 Naperville, IL 60563 (630) 219-1997

www.structuralenginuityinc.com

Project Name: STAG Industrial Holdings

Project No.: 21355.00

Client Name: Dynamic Energy

Date: 7/23/2021

SNOW LOADS

Controlling snow load

30 Ground snow load, pg psf CT BC 2018 Appendix N Exposure Factor, C_e 1 ASCE Table 7.3-1 Thermal Factor, C_t 1.2 ASCE Table 7.3-2 Importance Factor, I_s 1 ASCE Table 1.5-2 Flat roof snow load, $p_f = 0.7C_eC_tI_sp_g$ 25.2 psf ASCE Equation 7.3-1 **Building Section:** Main Roof **Roof Slope** 1.2 degrees 1 Roof Slopw Factor, C_s ASCE Fig 7.4-1 Minimum snow load for roofs with slopes less than 15 degrees $p_m = 20I_s$ psf ASCE 7.3.4

25.2

psf



Decking Check



Structural Enginuity, Inc. Project Name:

1815 W. Diehl Rd, Ste 100 Naperville, IL 60563 (630) 219-1997

www.structuralenginuityinc.com

Project Name: STAG Industrial Holdings

Project No.: 21355.00
Client Name: Dynamic Energy
Date: 7/23/2021

DECKING:

Assume Vulcraft 1.5B 22 Gauge roof deck 3 span condition

6'-2" ft span

Per inspection, existing metal deck is type 1.5B deck manufactured by Vulcraft.

Allowable loading

Roof loading

Dead Load

Psf

Vulcraft Deck Catalog

Psf

Vulcraft Deck Catalog

Roof Live Load 20 psf Snow Load 25.2 psf Proposed Solar Array 6 psf

Load combinations

D 14 psf D+Lr 34 psf

D+S+Solar 45.20 psf **CONTROLS**


D+0.75Lr 29 psf D+0.75S 32.9 psf

Controlling load combination 45.2 psf < Allowable load = 87 psf OK

Vulcraft 1.5B 22 Gauge deck OK



Framing Check



Results of Joist Analysis:

Original Design or Capacity Loads:

End Reactions:

RL = 6503.3 lbs. RR = 6503.3 lbs.

Minimum Design Web Member Shear:

Vw(min) = 1625.82 lbs. (25% of maximum end reaction for K-series and LH-series joists per SJI Spec's.)

Maximum Moments:

+Mx(max) =	62935.5	ft-lbs	@ x =	19.36	ft.
-Mx(max) =	0.0	ft-lbs	@ x =	0.00	ft.

*Maximum Deflections:

$-\Delta(\max) =$	-1.758	in.	@ x =	19.36	ft.
$+\Delta(max) =$	0.000	in.	@ x =	0.00	ft.
Λ (ratio) =	L/264		_		_

*Note: deflections shown above include a 15% increase above the values calculated using traditional "simple-beam" flexure in order to more closely match actual test results obtained by SJI.

New Design Loads:

End Reactions:

	-				
RL =	5394.9	lbs.	Rr =	5394.9	lbs.

Maximum Moments:

aximum Moments:

$$+Mx(max) = 52209.0$$
 ft-lbs @ $x = 19.36$ ft
 $-Mx(max) = 0.0$ ft-lbs @ $x = 0.00$ ft


*Maximum Deflections:

	• • • • • • • • • • • • • • • • • •	_	_		
$-\Delta(\max) =$	-1.459	in.	@ x =	19.36	ft.
$+\Delta(\max) =$	0.000	in.	@ x =	0.00	ft.
Λ (ratio) =	L/318		_		_

*Note: deflections shown above include a 15% increase above the values calculated using traditional "simple-beam" flexure in order to more closely match actual test results obtained by SJI.

Maximum Stress Ratios:

Comments:





Appendix A: DynamiC Energy Drawings

STAG INDUSTRIAL HOLDINGS

40 PEPES FARM ROAD MILFORD, CT 06460

SYSTEM DESCRIPTION

98.5%

TOTAL SYSTEM SIZE: 2160 kW DC STC TOTAL QUANTITY: 5400 MODULES TOTAL STRINGS: 156 STRINGS MODULES PER STRING TILT ANGLE: 10.0 DEGREES 143.544 DEGREES

MODULE DESCRIPTION:
MAXIMUM POWER (W)

OPEN CIRCUIT VOLTAGE (Voc): 49.8 V MAXIMUM POWER VOLTAGE (Vpm): SHORT CIRCUIT CURRENT (Isc): 10.36 A MAXIMUM POWER CURRENT (Ipm) 9.60 A EFFICIENCY (%): 19.88 % MAXIMUM SYSTEM VOLTAGE: 1500 VDC

INVERTER DESCRIPTION: CHINT POWER SYSTEMS TOTAL NUMBER OF INV:

MODEL NUMBER: CPS-SCA50KTL 1000*600*260mm CONTINUOUS POWER DC PEAK POWER TRACKING RANGE: 480-850V CEC PEAK EFFICIENCY

RACKING DESCRIPTION:
RACKING MANUFACTURER:

DOE SOLAR RACKING TYPE: BALLASTED

PROJECT CONTACTS

PROJECT MANAGER: MANOLI ALLEXOPOULOS 1550 LIBERTY RIDGE DR., STE 310 WAYNE, PA 19087

PHONE: (717) 951-0518

CONSTRUCTION MANAGER:

1550 LIBERTY RIDGE DR., STE 310

WAYNE, PA 19087 PHONE: (717) 951-0518

ELECTRICAL ENGINEER: HENDRIK BURGER

1550 LIBERTY RIDGE DR., STE 310 WAYNE, PA 19087

PHONE: (484) 323-1154

LICENCE#: 31153

STRUCTURAL ENGINEER

JAMES A MARX, P.E.


10 HIGH MOUNTAIN ROAD RINGWOOD, NJ 07456

ASCENT CONSULTING ENGINEERING

NORTH WINDS CENTER

LICENCE#: CT (NO. 17349)

1 AERIAL PHOTO
SCALE: N.T.S.



DRAWING LIST

COVER SHEET

SPECIFICATIONS:

GENERAL & CONSTRUCTION NOTES CONSTRUCTION NOTES (CONTINUED) CONSTRUCTION NOTES (CONTINUED)

STRUCTURAL:

BUILDING OVERVIEW

S101 **EXISTING STRUCTURAL LAYOUT & DETAILS** EXISTING STRUCTURAL LAYOUT & DETAILS (CONT.) S101.1

ELECTRICAL:

PV PANEL & EQUIPMENT LAYOUT E100 PV PANEL & RACKING LAYOUT E100.1 INVERTER, RACKING & CONDUIT DETAILS

E102 PV PANEL & PANELBOARD SUPPORT DETAILS

ONE-LINE DIAGRAM E200 E201

ONE-LINE LEGENDS & SETTINGS

E202 STRING LAYOUT & COMBINING ARCHITECTURE E202.1 STRING LAYOUT & COMBINING ARCHITECTURE CALCULATION & EQUIPMENT SCHEDULE E203

E204 TYPICAL PV-GROUNDING DIAGRAM E205 MONITORING DIAGRAM & PV SUBMETER DETAILS

CONDUCTOR SIZE CALCULATION TABLE F206 E400 **EQUIPMENT PLACARD LOCATIONS**

E401 **EQUIPMENT PLACARD LOCATIONS**

EQUIPMENT LABELS E402 F500 STAGING PLAN

DESIGN CRITERIA:

WIND SPEED: 123 MPH EXP.B GROUND SNOW LOAD: 30 PSF ROOF SNOW LOAD:

APPLICABLE CODES

2018 CONNECTICUT STATE BUILDING CODE

ELECTRICAL CODE NFPA 70, 2017 ED

STRUCTURAL ENGINUITY 1815 W. DIEHL RD SUITE 100


COVERSHEET


G001


Energy


Dynamic I

STAG INDUSTRIAL HOLDINGS
40 PEPES FARM ROAD
MILFORD, CT 06460









EX STEEL DETAIL
(PURLIN SECTION)

STRUCTURAL ENGINUITY 1815 W. DIEHL RD SUITE 100 NAPERSVILLE, IL 60563

SEAL

EXISTING STRUCTURAL LAYOUT & DETAILS

Dynamic Energy

STAG INDUSTRIAL HOLDINGS
40 PEPES FARM ROAD
MILFORD, CT 06460

S101.1

6/3/2021 2:18:40 PM