

PROPOSED SOLAR POWER SITE:

WINDSOR SOLAR ONE
41°54'2.27"N 72°39'49.60"W
445 RIVER STREET
WINDSOR, CT 06095

ARRAY LOCATION



PROJECT SITE

SHEET INDEX: FLEXTRACK S-SERIES

S1 PV MODULE SPECIFICATION SHEETS	●	●	
S2 1X75 RACK PLAN VIEW, ELEVATION, & NOTES	●	●	
S3 1X50 RACK PLAN VIEW, ELEVATION, & NOTES	●	●	
S4 TRACKER CONNECTIONS – DRIVE POST & SPLICE CONNECTION DETAILS	●	●	
S5 TRACKER CONNECTIONS – IDLER POST & VERTICAL RAIL CONNECTION DETAILS	●	●	
S6 TRACKER CONNECTIONS – DAMPER & PANEL CONNECTION DETAILS	●	●	
S7 TCU COMPONENT AND CONNECTION DETAILS	●	●	
S8 POST IDENTIFICATION DETAILS	●	●	
S7 TRACKER LAYOUT	●	●	
SIGN-OFF DEC. 23, 2024 IFP STAMPED SET APRIL 09, 2025			
ISSUANCE/REVISION			

LEGEND:
● ISSUED
○ REVISED, BUT NOT ISSUED

PREPARED FOR:

VEROGY
124 LASALLE ROAD
WEST HARTFORD, CT 06107

GENERAL NOTES:

1. CODES AND STANDARDS:

IBC 2021
NEC 2020
ASCE 360-16
AISI S100-20
ASCE 7-16

2. WIND DESIGN PARAMETERS:

ULTIMATE DESIGN WIND SPEED, V – 110 MPH
RISK CATEGORY – I
WIND EXPOSURE CATEGORY C, K_z – 1.00
TOPOGRAPHICAL FACTOR, K_{zt} – 1.00
WIND DIRECTIONALITY FACTOR, K_d – 0.85
GUST FACTOR & NET PRESSURE COEFFICIENT, GCN
–GCN COEFFICIENTS DETERMINED BASED ON WIND TUNNEL TESTING
–SEE SFR STRUCTURAL REPORT FOR PROJECT SPECIFIC GCN COEFFICIENTS

3. SNOW DESIGN PARAMETERS:

GROUND SNOW LOAD – 30 PSF
EXPOSURE CATEGORY, C_e – 0.90
SNOW THERMAL FACTOR, C_t – 1.20
SNOW IMPORTANCE FACTOR, I – 0.80
SNOW REDUCTION FACTOR SLIPPERY SURFACES, C_s

TILT ANGLE	C_s VALUE
0°-15°	1.00
20°	0.91
25°	0.82
30°	0.73
35°	0.64
40°	0.55
45°	0.46
50°	0.37
55°	0.28

4. EARTHQUAKE DESIGN PARAMETERS – EQUIVALENT LATERAL FORCE:

RISK CATEGORY – I
SITE CLASS – D
SEISMIC IMPORTANCE FACTOR, I_e – 1.0
RESPONSE MODIFICATION COEFFICIENT, R – 2
SPECTRAL RESPONSE ACCELERATION PARAMETERS

MAPPED	DESIGN
$S_g = 0.181g$	$S_{gs} = 0.193g$
$S_i = 0.055g$	$S_{gi} = 0.088g$

SEISMIC DESIGN CATEGORY – B
SEISMIC RESPONSE COEFFICIENT, C_s – 0.097

5. FOUNDATIONS:

FOUNDATION DESIGNED BY OTHERS.

6. APPLICABLE INSTALLATION TOLERANCES (PER SINGLE TRACKER):

N-S TRACKER SLOPE: 5%
A-FRAME N/S SPACING: $\pm 1 \frac{1}{2}$ "
TOP OF A-FRAME E-W ALIGNMENT: $\pm \frac{3}{4}$ "
TOP OF A-FRAME PLUMB: $\pm 1^{\circ}$
TOP OF A-FRAME TWIST: $\pm 3^{\circ}$
TOP OF A-FRAME(IDLER) OUT OF STRING-LINE: $\pm 1"$

TOP OF DRIVE A-FRAME IS 3" ABOVE IDLER A-FRAME.
MINIMUM RECOMMENDED CLEARANCE BETWEEN TRACKERS NO LESS THAN 12".
REFER TO APA DRAWINGS FOR A-FRAME INSTALLATION TOLERANCES.

PREPARED BY:

FLEXRACK BY QCELLS
23000 HARVARD RD., SUITE B
CLEVELAND, OH 44122

7. CONNECTIONS:

SEE SHEETS S4-S7 FOR TORQUE VALUES FOR EACH CONNECTION.

8. PV MODULE INFORMATION:

NAME/MODEL: FIRST SOLAR SERIES 7 535W
DIMENSIONS: 90.551" LONG X 47.874" WIDE X 2.205" TALL
WEIGHT: 87.5 LBS
VERSION: MPD-00903-07-US – JULY 2024

9. MATERIALS AND COATINGS:

- A. PILES:
 - i. W-SECTIONS: A992 STEEL HOT DIPPED GALVANIZED PER ASTM A123.
- B. HARDWARE:
 - ii. $\frac{3}{4}$ " ϕ TO BE F3125 GRADE A325 HOT DIPPED GALVANIZED PER ASTM A153.
 - iii. $\frac{5}{8}$ " ϕ TO BE F3125 GRADE A325 HOT DIPPED GALVANIZED PER ASTM A153.
 - iv. $\frac{1}{2}$ " ϕ TO BE A449 MECHANICAL GALVANIZED PER MAGNI 560.
 - v. $\frac{5}{16}$ " ϕ TO BE A449 MECHANICAL GALVANIZED PER MAGNI 560 OR STAINLESS STEEL.
 - vi. $\frac{1}{4}$ " ϕ TO BE A449 MECHANICAL GALVANIZED PER MAGNI 560 OR STAINLESS STEEL.

C. COLD FORMED STEEL:

- i. TORQUE TUBE TO BE A500 GRADE C PRE GALVANIZED PER ASTM A1057, ZT 60.
- ii. ALL COLD FORM STEEL TO BE PRE GALVANIZED PER A653 UNLESS OTHERWISE NOTED(G90 MINIMUM).

10. TRACKER STANDARDS:

- A. UL3703
- B. UL2703

11. STOW STRATEGY:

- A. STOW ANGLE: 55°
- B. TIME TO STOW: 2 MINUTES
- C. STOW TRIGGER WIND SPEED: 35 MPH
- D. WIND SPEED SENSOR INTERACTION: 3 SECOND GUST
- E. MANUAL STOW INSTRUCTION DOCUMENT: D001-NCU INSTALLATION & OPERATION MANUAL

ABBREVIATIONS

MIN	MINIMUM	BC	BEARING CRADLE
MAX	MAXIMUM	C-C	CENTER TO CENTER
OH	OVERHANG	CD	Critical Dimension
PAG	POST ABOVE GRADE	CTA	Central Tube Axis
REF	REFERENCE	DIM	Dimension
DIA	DIAMETER	EOP	End of Panel
TYP	TYPICAL	HORIZ	Horizontal
VERT	VERTICAL	HDG	Hot Dipped Galvanized
STD	STANDARD	PLN	Plain
RV	RECEIVER	SWG	Swaged
CP	CLAMP	EOT	End of Tub
S/C	STOCK CODE		

FLEXRACK
by qcells

23000 Harvard Road, Suite B
Cleveland, OH 44122

Copying in part or as a whole is prohibited. This is only to be used by the party described in the Title section. This is proprietary information of FlexRack by Qcells. © Copyright, FlexRack by Qcells All Rights Reserved.

REV	DESCRIPTION	CHG BY	DATE

STATE OF CONNECTICUT
SARAH M. FLICK
LICENCED PROFESSIONAL ENGINEER
13-M-2023
4/19/25


COVER SHEET

CUSTOMER:	VEROGY	SOFT	
DATE:	04/09/2025	JOB #:	19097
DRAWN BY:	ZC	CHECK BY:	JRD
PAGE:	1 of 1	SO:	S9



Series 7 TR1.

525-550 Watt Thin Film Solar Module



Series 7 TR1 modules combine First Solar's thin film technology with a larger form factor and an innovative new back rail mounting system to deliver improved efficiency, enhanced installation velocity, and unmatched lifetime energy performance for utility-scale PV projects.



More Lifetime Energy per Nameplate Watt

- Industry's best (0.3%) warranted degradation rate
- Superior temperature coefficient, spectral, and shading response
- No power loss from LID or LeTID
- Anti-reflective coated glass enhances energy production



Innovative Module Design

- Optimized back rail mount design enhances installation velocity
- Frameless design improves soiling and snow shedding
- Dual junction box design reduces wire management complexity and cost



Unmatched Quality and Reliability

- End-to-end manufacturing process for globally consistent quality
- Tested and certified to IEC standards and beyond
- Durable glass/glass construction
- Immune to and warranted against power loss from cell cracking
- 12-year Limited Product Warranty



Industry's Most Eco-efficient PV Solution

- Industry leading carbon footprint, water footprint and energy payback time
- Globally available PV module recycling services



America's Solar Company


- Designed, responsibly sourced, and manufactured in the USA

19.7%
HIGH BIN EFFICIENCY

30YR
LINEAR PERFORMANCE
WARRANTY

98%
WARRANTY START POINT

0.3%
WARRANTED ANNUAL
DEGRADATION RATE



Learn more about First Solar
and Series 7 TR1
at firstsolar.com/S7

Series 7 TR1.

Electrical Specifications

MODEL TYPES: FS-7XXXA-TR1 (XXX = NOMINAL POWER)

RATINGS AT STANDARD TEST CONDITIONS (1000W/m², AM 1.5, 25°C)²

Nominal Power ³ (-0/+5%)	P _{MAX} (W)	525	530	535	540	545	550
Efficiency (%)	%	18.8	19.0	19.1	19.3	19.5	19.7
Cell Efficiency (%)	%	19.7	19.9	20.1	20.3	20.4	20.6
Voltage at P _{MAX}	V _{MAX} (V)	186.0	186.9	187.8	188.7	189.6	190.4
Current at P _{MAX}	I _{MAX} (A)	2.82	2.84	2.85	2.86	2.88	2.89
Open Circuit Voltage	V _{OC} (V)	226.1	226.7	227.2	227.7	228.2	228.8
Short Circuit Current	I _{SC} (A)	3.04	3.05	3.06	3.06	3.07	3.08
Maximum System Voltage	V _{SYS} (V)			1500 ⁵			
Limiting Reverse Current	I _R (A)			5.0			
Maximum Series Fuse	I _{CF} (A)			5.0			


TEMPERATURE CHARACTERISTICS

Module Operating Temperature Range	(°C)	-40 to +85
Temperature Coefficient of P _{MAX}	T _K (P _{MAX})	-0.32%/°C [Temperature Range: 25°C to 75°C]
Temperature Coefficient of V _{OC}	T _K (V _{OC})	-0.28%/°C
Temperature Coefficient of I _{SC}	T _K (I _{SC})	+0.04%/°C
Nominal Operating Cell Temperature	(°C)	45

PACKAGING INFORMATION

Model Type	Modules Per Pack	Packs per 53' Container
FS-7XXXA-TR1	44 / 46	10 / 9

Mechanical Specifications



MECHANICAL DESCRIPTION

Length	2300mm
Width	1216mm
Area	2.80m ²
Module Weight	38.4 ⁷ / 39.7 kg
Leadwire ⁶	2.5mm ² , 650mm (+) & Bulkhead (-)
Connectors	TE Connectivity PV4-S or alternate
Junction Box	IP68 Rated
Bypass Diode	N/A
Cell Type	Thin film CdTe semiconductor, up to 268 cells
Back Rail Material	Galvanized steel
Front Glass	Heat strengthened
Back Glass	Heat strengthened
Encapsulation	Laminate material with edge seal
Frame to Glass Adhesive	Silicone
Load Rating	2400Pa

Certifications & Tests⁴

CERTIFICATIONS AND LISTINGS	EXTENDED DURABILITY TESTS	QUALITY & EHS
IEC 61215:2021 & IEC 61730-1:2016 ⁵ , CE	IEC TS 63209-1 Extended Stress Test	ISO 9001:2015
IEC 61701 Salt Mist Corrosion	Long-Term Sequential	ISO 14001:2015
IEC 60068-2-68 Dust and Sand Resistance	Thresher Test	ISO 45001:2018
IEC 62716 Ammonia Corrosion	PID Resistant	ISO 14064-3:2006
UL 1730 1500V Listed		EPEAT Silver Registered

Install in portrait only

- Limited power output and product warranties subject to warranty terms and conditions
- All ratings ±10%, unless specified otherwise. Specifications are subject to change
- Measurement uncertainty applies
- Testing Certifications/Lists pending
- IEC 61730-1: 2016 Class II
- Leadwire length from junction box exit to connector mating surface
- +/-130mm mounting location added to product variant


Disclaimer

All images shown are provided for illustrative purposes only and may not be an exact representation of the product. First Solar, Inc. reserves the right to change product images at any time without notice. The information included in this Module Datasheet is subject to change without notice and is provided for informational purposes only. No contractual rights are established or should be inferred because of user's reliance on the information contained in this Module Datasheet. Please refer to the appropriate Module User Guide and Module Product Specification document for more detailed technical information regarding module performance, installation and use.


First Solar, the First Solar logo, and Leading the World's Sustainable Energy Future are trademarks of First Solar, Inc., registered in the U.S. and other countries. America's Solar Company, Series 7 and Series 7 TR1 are trademarks of First Solar, Inc.

©2024

Copying in part or as a whole is prohibited. This is only to be used by the party described. This is a proprietary information of FlexRack by Qcells. © Copyright, FlexRack by Qcells All Rights Reserved.




VEROGY		WINDSOR SOLAR ONE
WINDSOR, CT 06095		19097
CUSTOMER:	DATE: 04/09/2025	PAGE: S1 of S9
DRAWN BY: ZC	JOB #: C7	URD
PV MODULE SPECIFICATION SHEETS		



FIRST SOLAR SERIES 7 535W
1X75 FLEXTRACK S-SERIES
TRACKER QUANTITY: 73


WINDSOR SOLAR ONE
WINDSOR, CT 06095
OB #: 19097

eet



DAMPER FRONT ELEVATION DETAIL

IDLER POST DAMPER SECTION VIEW - 0°



6 S2 DRIVE POST SECTION VIEW - 55°
SCALE: $\frac{3}{4}$ " = 1'-0"

5
S2

DRIVE POST FRONT ELEVATION VIEW

SCALE: $\frac{3}{4}'' = 1'-0''$




**23000 Harvard Road, Suite B
Cleveland, OH 44122**


**23000 Harvard Road, Suite B
Cleveland, OH 44122**

1

by the party described in the fine section. This is proprietary information of FlexRack by Qcells
© Copyright, FlexRack by Qcells All Rights Reserved.



S3

VEROGY
WINDSOR SOLAR ONE
WINDSOR, CT 06095FIRST SOLAR SERIES 7 535W
1X50 FLEXTRACK S-SERIES
TRACKER QUANTITY: 36FLEXRACK
by Qcells23000 Harvard Road, Suite B
Cleveland, OH 44122Copying in part or as a whole is prohibited. This is only to be used
by the party for whom it was intended. It is the property
of FlexRack by Qcells. All Rights Reserved.
© Copyright, FlexRack by Qcells All Rights Reserved.

FRONT ELEVATION
SCALE: 3/32" = 1'-0"

2 S3

3 S3

4 S3

5 S3

6 S3


7 S3

8 S3

9 S3

10 S3

11 S3



DRIVE POST SECTION VIEW - 55°
SCALE: 3/4" = 1'-0"

6 S3

5 S3

4 S3

3 S3

2 S3

1 S3

0 S3

-55 S3

-10 S3

-5 S3

0 S3

5 S3

10 S3

15 S3

20 S3

25 S3

30 S3

35 S3

40 S3

45 S3

50 S3

55 S3

60 S3

65 S3

70 S3

75 S3

80 S3

85 S3

90 S3

95 S3

100 S3

105 S3

110 S3

115 S3

120 S3

125 S3

130 S3

135 S3

140 S3

145 S3

150 S3

155 S3

160 S3

165 S3

170 S3

175 S3

180 S3

185 S3

190 S3

195 S3

200 S3

205 S3

210 S3

215 S3

220 S3

225 S3

230 S3

235 S3

240 S3

245 S3

250 S3

255 S3

260 S3

265 S3

270 S3

275 S3

280 S3

285 S3

290 S3

295 S3

300 S3

305 S3

310 S3

315 S3

320 S3

325 S3

330 S3

335 S3

340 S3

345 S3

350 S3

355 S3

360 S3

365 S3

370 S3

375 S3

380 S3

385 S3

390 S3

395 S3

400 S3

405 S3

410 S3

415 S3

420 S3

425 S3

430 S3

435 S3

440 S3

445 S3

450 S3

455 S3

460 S3

465 S3

470 S3

475 S3

480 S3

485 S3

490 S3

495 S3

500 S3

505 S3

510 S3

515 S3

520 S3

525 S3

530 S3

535 S3

540 S3

545 S3

550 S3

555 S3

560 S3

565 S3

570 S3

575 S3

580 S3

585 S3

590 S3

595 S3

600 S3

605 S3

610 S3

615 S3

620 S3

625 S3

630 S3

635 S3

640 S3

645 S3

650 S3

655 S3

660 S3

665 S3

670 S3

675 S3

680 S3

685 S3

690 S3

695 S3

700 S3

705 S3

710 S3

715 S3

720 S3

725 S3

730 S3

735 S3

740 S3

745 S3

750 S3

755 S3

760 S3

765 S3

770 S3

775 S3

780 S3

785 S3

790 S3

795 S3

800 S3

805 S3


810 S3

815 S3

820 S3


825 S3

8



3
S4 DRIVE POST SLEW DRIVE CONNECTION
SCALE: NTS

S4 SCALE: NTS
TORQUE VALUE:
100-120 FT-LBS FOR $\frac{5}{8}$ " BOLTS
175-200 FT-LBS FOR $\frac{3}{4}$ " BOLTS




1
S4

DRIVE POST ISOMETRIC VIEW


SCALE: NTS

SCALE: NTS



TORQUE TUBE SPLICE EXPLODED

TORQUE TUBE SPLICE MUST BE ORIENTED WITH THE BOLTS INSTALLED VERTICALLY.
TORQUE VALUE:
40-45 FT-LBS FOR $\frac{1}{2}$ " BOLTS
65-75 FT-LBS FOR $\frac{5}{8}$ " BOLTS





BEAM TO SLEW CONNECTION EXPLODED


SCALE: NTS
CONNECTION MUST BE ORIENTED WITH THE BOLTS INSTALLED VERTICALLY.
TORQUE VALUE: 100-120 FT-LBS FOR $\frac{5}{8}$ " BOLTS

© Copyright, FlexRack by Qcells All Rights Reserved.

Copying in part or as a whole is prohibited. This is only to be used
by the party described in the Title section. This is proprietary
information of FlexRack by Qcells
© Copyright, FlexRack by Qcells All Rights Reserved.



1 S5 IDLER POST ISOMETRIC VIEW
SCALE: NTS




2 S5 BEARING CRADLE ASSEMBLY EXPLODED
SCALE: NTS
SHOULDER OF BOLT MUST EXTEND THROUGH BOTH FACES OF THE SECTOR
CRADLE CHANNEL, SUCH THAT NO FORCE IS BEING EXERTED VERTICALLY ON THE
THREADS.


4 S5 IDLER POST TO BEARING ASSEMBLY EXPLODED
SCALE: NTS

TORQUE VALUE:
90-100 FT-LBS FOR $\frac{1}{2}$ -13 X $1\frac{1}{4}$ " BOLTS
25-30 FT-LBS FOR $\frac{1}{2}$ -13 X 5" CARRIAGE BOLTS

*SPRING PLATE TO BE INSTALLED IN TOP SET OF HOLES
*ALL PILES WITHIN THE CONNECTION SHALL BE PULLED INTO
FIRM CONTACT BY THE BOLTS IN THE JOINT



3 S5 IDLER BEARING ASSEMBLY EXPLODED
SCALE: NTS
TORQUE VALUE:
20-25 FT-LBS FOR $\frac{1}{8}$ -16 BOLTS



5 S5 VERT. RAIL TO TORQUE TUBE EXPLODED
SCALE: NTS
TORQUE VALUE:
20-25 FT-LBS FOR $\frac{1}{8}$ -16 BOLTS

VEROGY
WINDSOR SOLAR ONE
WINDSOR, CT 06095


CUSTOMER:
DRAWN BY: ZC
DATE: 04/09/2025
JOB #: 19097
PAGE: S6 of S9

DAMPER & PANEL
CONNECTION DETAILS

FLEXRACK
by Qcells


23000 Harvard Road, Suite B
Cleveland, OH 44122

Copying in part or as a whole is prohibited. This is only to be used
by the party described in the Title section. This is proprietary
information of FlexRack by Qcells
© Copyright, FlexRack by Qcells All Rights Reserved.





2 S6 DAMPER CONNECTION TO TUBE EXPLODED

SCALE: NTS
TORQUE VALUE:
10-12 FT-LBS FOR 3/16 SERRATED BOLTS
20-25 FT-LBS FOR 3/16 CARRIAGE BOLTS



4 S6 SOLAR PANEL TO VERT. RAIL CONN. EXPLODED




1 S6 DAMPER CONNECTION ISOMETRIC VIEW

3 S6 DAMPER CONNECTION TO POST EXPLODED


SCALE: NTS
TORQUE VALUE:
90-100 FT-LBS FOR 1/2" BOLTS
10-12 FT-LBS FOR 3/16 BOLTS

FIRST 3/16 NYLON LOCK NUT MUST BE TIGHTENED TO
SNUG TIGHT PRIOR TO THE INSTALLATION OF THE DAMPENER IN THE POST BRACKET.







Z RAIL TO PANEL CONNECTION



TCU TO PANEL CONNECTION




SELF POWERED PANEL TO TORQUE TUBE CONNECTION




BONDING STRAP CONNECTION ISOMETRIC VIEW


1
S7
SCALE: NTS
TORQUE VALUE:
5-6 FT-LBS FOR 3/8"-16 X 1" BOLT (BONDING STRAP HARDWARE)
20-25 FT-LBS FOR 3/8"-16 CARRIAGE BOLT
*BONDING STRAP MAY BE CONNECTED TO THE SELF POWERED Z RAILS ON EACH SIDE OF THE
SLEW DRIVE USING THE 3/8"-16 SERRATED FLANGEHEAD NUT




1
S8 PLAN VIEW 1X75 (EXTERIOR)
SCALE: NTS



2
S8 PLAN VIEW 1X75 (INTERIOR)
SCALE: NTS



3
S8 PLAN VIEW 1X50 (EXTERIOR)
SCALE: NTS



4
S8 PLAN VIEW 1X50 (INTERIOR)
SCALE: NTS

NOTES:

1. WORK THIS SHEET WITH SHEETS S2-S3, S9.

VEROGY		WINDSOR SOLAR ONE	
WINDSOR, CT 06095		19097	19097
CUSTOMER:		JOB #:	
DRAWN BY:	ZC	Check By:	JRD
DATE:	04/09/2025	Page:	S8 of S9
TCU COMPONENTS AND CONNECTION DETAILS			
FLEXRACK by Qcells 23000 Harvard Road, Suite B Cleveland, OH 44122			
Copying in part or as a whole is prohibited. This is only to be used by the party described in the Title section. This is proprietary information of FlexRack by Qcells © Copyright, FlexRack by Qcells All Rights Reserved.			
REV	DESCRIPTION	CHG. BY	DATE

VEROGY
WINDSOR SOLAR ONE
WINDSOR, CT 06095

Sheet
S9

FLEXRACK
by Qcells

23000 Harvard Road, Suite B
Cleveland, OH 44122

Copying in part or as a whole is prohibited. This is only to be used
by the party described in the Title section. This is proprietary
information of FlexRack by Qcells.
© Copyright, FlexRack by Qcells All Rights Reserved.




CUSTOMER:
DATE: 04/09/2025
DRAWN BY: ZC


JOB #: 19097
CHECK BY: JRD

PAGE: S9 of S9

PROJECT
NORTH



1
S9 TRACKER LAYOUT
SCALE: 1"=60'



NOTES:

1. WORK THIS SHEET WITH SHEETS S2-S3 & S8.
2. FINAL POST LOCATIONS ARE THE RESPONSIBILITY OF THE SURVEYOR OF RECORD (OTHERS).
3. INTERIOR AND EXTERIOR TRACKER LOCATIONS ARE BASED ON LAYOUT PROVIDED TO FLEXRACK BY CUSTOMER.
4. LOCATIONS INDICATED FOR EACH POST TYPE ARE BASED ON LAYOUT & TOPOGRAPHY PROVIDED TO FLEXRACK BY CUSTOMER.
5. FLEXRACK TO BE NOTIFIED IF ADDITIONAL SITE SURVEY IS COMPLETED.
6. FLEXRACK TO BE NOTIFIED OF ANY MODIFICATIONS TO THE LAYOUT AS SHOWN.
7. FLEXRACK IS NOT RESPONSIBLE FOR ANY LAYOUT MODIFICATIONS DONE DURING CONSTRUCTION.