

# FORGESOLAR GLARE ANALYSIS

Project: **Old Maids Lane, Portland**

4 MW AC project

Site configuration: **OML-temp-1**

Created 23 Jan, 2026

Updated 23 Jan, 2026

Time-step 1 minute

Timezone offset UTC-5

Minimum sun altitude 0.0 deg

DNI peaks at 1,000.0 W/m<sup>2</sup>

Category 1 MW to 5 MW

Site ID 169383.28215


Ocular transmission coefficient 0.5

Pupil diameter 0.002 m

Eye focal length 0.017 m

Sun subtended angle 9.3 mrad

PV analysis methodology V2



## Summary of Results No glare predicted

PV Array	Tilt	Orient	Annual Green Glare		Annual Yellow Glare		Energy kWh
			min	hr	min	hr	
PV array 1	SA tracking	SA tracking	0	0.0	0	0.0	-

*Total glare received by each receptor; may include duplicate times of glare from multiple reflective surfaces.*

Receptor	Annual Green Glare		Annual Yellow Glare	
	min	hr	min	hr
OP 1	0	0.0	0	0.0
OP 2	0	0.0	0	0.0
OP 3	0	0.0	0	0.0
OP 4	0	0.0	0	0.0
OP 5	0	0.0	0	0.0
OP 6	0	0.0	0	0.0
OP 7	0	0.0	0	0.0

# Component Data

## PV Arrays

**Name:** PV array 1  
**Description:** OML SAT  
**Axis tracking:** Single-axis rotation  
**Backtracking:** Shade  
**Tracking axis orientation:** 180.0°  
**Max tracking angle:** 52.0°  
**Resting angle:** 5.0°  
**Ground Coverage Ratio:** 0.45  
**Rated power:** -  
**Panel material:** Smooth glass without AR coating  
**Reflectivity:** Vary with sun  
**Slope error:** correlate with material



Vertex	Latitude (°)	Longitude (°)	Ground elevation (ft)	Height above ground (ft)	Total elevation (ft)
1	41.634190	-72.619486	144.76	10.00	154.76
2	41.633372	-72.619486	121.24	10.00	131.24
3	41.633372	-72.619161	119.84	10.00	129.84
4	41.633217	-72.618836	119.56	10.00	129.56
5	41.632881	-72.618836	110.97	10.00	120.97
6	41.632239	-72.618708	106.48	10.00	116.48
7	41.632317	-72.618025	117.61	10.00	127.61
8	41.633375	-72.618025	138.04	10.00	148.04
9	41.633428	-72.617633	169.92	10.00	179.92
10	41.633756	-72.617567	170.67	10.00	180.67
11	41.634342	-72.612156	207.01	10.00	217.01
12	41.635000	-72.612153	196.22	10.00	206.22

## Discrete Observation Point Receptors

Name	ID	Latitude (°)	Longitude (°)	Elevation (ft)	Height (ft)
OP 1	1	41.637439	-72.615093	168.57	0.00
OP 2	2	41.636627	-72.614182	167.05	0.00
OP 3	3	41.636278	-72.615786	164.70	0.00
OP 4	4	41.641147	-72.610164	173.62	0.00
OP 5	5	41.638870	-72.611468	170.72	0.00
OP 6	6	41.636148	-72.608903	162.69	0.00
OP 7	7	41.634794	-72.608961	163.45	0.00

# Glare Analysis Results

## Summary of Results No glare predicted

PV Array	Tilt	Orient	Annual Green Glare		Annual Yellow Glare		Energy
	°	°	min	hr	min	hr	kWh
PV array 1	SA tracking	SA tracking	0	0.0	0	0.0	-

Total glare received by each receptor; may include duplicate times of glare from multiple reflective surfaces.

Receptor	Annual Green Glare		Annual Yellow Glare	
	min	hr	min	hr
OP 1	0	0.0	0	0.0
OP 2	0	0.0	0	0.0
OP 3	0	0.0	0	0.0
OP 4	0	0.0	0	0.0
OP 5	0	0.0	0	0.0
OP 6	0	0.0	0	0.0
OP 7	0	0.0	0	0.0

## PV: PV array 1 no glare found

Receptor results ordered by category of glare

Receptor	Annual Green Glare		Annual Yellow Glare	
	min	hr	min	hr
OP 1	0	0.0	0	0.0
OP 2	0	0.0	0	0.0
OP 3	0	0.0	0	0.0
OP 4	0	0.0	0	0.0
OP 5	0	0.0	0	0.0
OP 6	0	0.0	0	0.0
OP 7	0	0.0	0	0.0

## PV array 1 and OP 1

No glare found

## PV array 1 and OP 2

No glare found

**PV array 1 and OP 3**

No glare found

**PV array 1 and OP 4**

No glare found

**PV array 1 and OP 5**

No glare found

**PV array 1 and OP 6**

No glare found

**PV array 1 and OP 7**

No glare found

# Assumptions

---

"Green" glare is glare with low potential to cause an after-image (flash blindness) when observed prior to a typical blink response time.

"Yellow" glare is glare with potential to cause an after-image (flash blindness) when observed prior to a typical blink response time.

Times associated with glare are denoted in Standard time. For Daylight Savings, add one hour.

The algorithm does not rigorously represent the detailed geometry of a system; detailed features such as gaps between modules, variable height of the PV array, and support structures may impact actual glare results. However, we have validated our models against several systems, including a PV array causing glare to the air-traffic control tower at Manchester-Boston Regional Airport and several sites in Albuquerque, and the tool accurately predicted the occurrence and intensity of glare at different times and days of the year.

Several V1 calculations utilize the PV array centroid, rather than the actual glare spot location, due to algorithm limitations. This may affect results for large PV footprints. Additional analyses of array sub-sections can provide additional information on expected glare. This primarily affects V1 analyses of path receptors.

Random number computations are utilized by various steps of the annual hazard analysis algorithm. Predicted minutes of glare can vary between runs as a result. This limitation primarily affects analyses of Observation Point receptors, including ATCTs. Note that the SGHAT/ForgeSolar methodology has always relied on an analytical, qualitative approach to accurately determine the overall hazard (i.e. green vs. yellow) of expected glare on an annual basis.

The analysis does not automatically consider obstacles (either man-made or natural) between the observation points and the prescribed solar installation that may obstruct observed glare, such as trees, hills, buildings, etc.

The subtended source angle (glare spot size) is constrained by the PV array footprint size. Partitioning large arrays into smaller sections will reduce the maximum potential subtended angle, potentially impacting results if actual glare spots are larger than the sub-array size. Additional analyses of the combined area of adjacent sub-arrays can provide more information on potential glare hazards. (See previous point on related limitations.)

The variable direct normal irradiance (DNI) feature (if selected) scales the user-prescribed peak DNI using a typical clear-day irradiance profile. This profile has a lower DNI in the mornings and evenings and a maximum at solar noon. The scaling uses a clear-day irradiance profile based on a normalized time relative to sunrise, solar noon, and sunset, which are prescribed by a sun-position algorithm and the latitude and longitude obtained from Google maps. The actual DNI on any given day can be affected by cloud cover, atmospheric attenuation, and other environmental factors.

The ocular hazard predicted by the tool depends on a number of environmental, optical, and human factors, which can be uncertain. We provide input fields and typical ranges of values for these factors so that the user can vary these parameters to see if they have an impact on the results.

The speed of SGHAT allows expedited sensitivity and parametric analyses.

The system output calculation is a DNI-based approximation that assumes clear, sunny skies year-round. It should not be used in place of more rigorous modeling methods.

Hazard zone boundaries shown in the Glare Hazard plot are an approximation and visual aid based on aggregated research data. Actual ocular impact outcomes encompass a continuous, not discrete, spectrum.

Glare locations displayed on receptor plots are approximate. Actual glare-spot locations may differ.

Refer to the Help page at [www.forgesolar.com/help/](http://www.forgesolar.com/help/) for assumptions and limitations not listed here.

Default glare analysis parameters and observer eye characteristics (for reference only):

- Analysis time interval: 1 minute
- Ocular transmission coefficient: 0.5
- Pupil diameter: 0.002 meters
- Eye focal length: 0.017 meters
- Sun subtended angle: 9.3 milliradians

© Sims Industries d/b/a ForgeSolar, All Rights Reserved.





Note: The image above is a panorama composition panning clockwise from southwest (left) to north (right).

**VIEWPOINT 1**  
Nayaug Elementary School (Old Maids Lane)

**LOCATION INFORMATION**

Municipality:	Portland
County:	Middlesex
Latitude:	41.63753° N
Longitude:	72.61459° W
Project Distance*:	996 feet



**PHOTOGRAPH INFORMATION**

Date:	January 21, 2026
Time:	4:07 PM
Camera:	Canon EOS 5D Mark IV
Camera Resolution:	30.4 Megapixels
Lens Focal Length (35 mm sensor equivalent):	51 mm
Camera Elevation:	189 feet
Field of View:	39 degrees
Direction of View:	South
Printed Size:	10 inches x 15 inches
Viewing Distance**:	21 inches

**NOTES**

\*Distance as measured from the viewpoint to the nearest PV panels within the simulated photograph's field of view

\*\*The simulation is at the correct perspective when printed on an 11-by-17 sheet at full scale, and viewed approximately 21 inches from the eye of the viewer.

**Old Maids Lane Solar**

Town of Portland, Middlesex County, Connecticut

EXISTING VIEW



This scale is to ensure the simulation images are printed at the intended size.

VIEWPOINT 1  
Nayaug Elementary School (Old Maids Lane)

Old Maids Lane Solar

Note: Printed at actual size, the existing view image is 15 inches wide by 10 inches high. At this size and focal length, the existing view should be viewed from a distance 21 inches from the eye of the viewer.

PROPOSED VIEW FOLLOWING INSTALLATION



This scale is to ensure the simulation images are printed at the intended size.

VIEWPOINT 1  
Nayaug Elementary School (Old Maids Lane)

Old Maids Lane Solar



Note: Printed at actual size, the resulting simulation image is 15 inches wide by 10 inches high. At this size and focal length, the simulation should be viewed from a distance 21 inches from the eye of the viewer.





Note: The image above is a panorama composition panning clockwise from southwest (left) to north (right).

**VIEWPOINT 1**  
Private Residence (Old Maids Lane)

**LOCATION INFORMATION**

Municipality:	Portland
County:	Middlesex
Latitude:	41.64118° N
Longitude:	72.61009° W
Project Distance*:	2,314 feet



**PHOTOGRAPH INFORMATION**

Date:	January 21, 2026
Time:	3:10 PM
Camera:	Canon EOS 5D Mark IV
Camera Resolution:	30.4 Megapixels
Lens Focal Length (35 mm sensor equivalent):	51 mm
Camera Elevation:	189 feet
Field of View:	39 degrees
Direction of View:	South - Southwest
Printed Size:	10 inches x 15 inches
Viewing Distance**:	21 inches

**NOTES**

\*Distance as measured from the viewpoint to the nearest PV panels within the simulated photograph's field of view

\*\*The simulation is at the correct perspective when printed on an 11-by-17 sheet at full scale, and viewed approximately 21 inches from the eye of the viewer.

**Old Maids Lane Solar**

Town of Portland, Middlesex County, Connecticut

EXISTING VIEW



Note: Printed at actual size, the existing view image is 15 inches wide by 10 inches high. At this size and focal length, the existing view should be viewed from a distance 21 inches from the eye of the viewer.



This scale is to ensure the simulation images are printed at the intended size.

VIEWPOINT 1

Private Residence (Old Maids Lane)

Old Maids Lane Solar



PROPOSED VIEW FOLLOWING INSTALLATION (PROJECT NOT VISIBLE)



Note: Printed at actual size, the resulting simulation image is 15 inches wide by 10 inches high. At this size and focal length, the simulation should be viewed from a distance 21 inches from the eye of the viewer.



This scale is to ensure the simulation images are printed at the intended size.

VIEWPOINT 1

Private Residence (Old Maids Lane)

Old Maids Lane Solar

