

Connecticut Department of Energy and Environmental Protection











National Emission Standards for Hazardous Air Pollutants for Reciprocating Internal Combustion Engines (RICE Rule)



40 CFR 63 Subpart ZZZZ Area Source Existing Non-Emergency Spark Ignition 4-Stroke Rich Burn Engine >500 Horsepower (≤24 hours/year)



Connecticut Department of Energy and Environmental Protection

To comply with this rule, you must meet the following equipment standards:

Every **500** hours of operation or annually, whichever comes first, you must:

- Change oil and filter
 - -Can utilize oil analysis program to extend specified oil change requirement
 - -Analysis must be performed every 500 hours of operation or annually, whichever comes first.
 - -Analysis must at a minimum analyze: Total Acid Number, viscosity, and percent water content.
 - -Condemning limits for these parameters are: Total Acid Number increases by >3.0 mg KOH/g from Total Acid Number of the oil when new; viscosity of the oil has changed by >20% from the viscosity of the oil when new; or percent water content (by volume) is >0.5.
 - -If all condemning limits are not exceeded you are not required to change the oil.
 - -If any limits are exceeded, change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results are received, change the oil within 2 days or before commencing operation, whichever is later.
 - -Keep records of parameters analyzed, results of the analysis, and oil changes.
 - -Analysis program must be part of the engine maintenance plan.



To comply with this rule, you must meet the following equipment standards:

Every **500** hours of operation or annually, whichever comes first, you must:

•Inspect all hoses and belts and replace as necessary

Every **1,000** hours of operation or annually, whichever comes first, you must:

Inspect spark plugs and replace as necessary

At all times you must operate/maintain all equipment in a manner consistent with safety and good air pollution control practices for minimizing emissions.



You must show continuous compliance by...

- •Operating and maintaining the engine according to the manufacturer's emission-related operation and maintenance instructions; or
- •Develop and follow your own maintenance plan which must provide to the extent practicable for the maintenance and operation of the engine in a manner consistent with good air pollution control practice for minimizing emissions



Monitoring Requirements



Photo credit: EPA

Minimize the engine's time spent at idle during startup and minimize startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes.



To demonstrate compliance with all rule requirements, you must keep records of:

•Maintenance conducted on the engine to demonstrate that you operated and maintained the engine and after-treatment control device (if any) according to your own maintenance plan.

•Keep records for 5 years from the date of creation.





By when must I comply with the rule?

October 19, 2013




Photo credit: EPA



Visit the EPA RICE Compliance Page

www.epa.gov/ttn/atw/icengines/

- Fact sheets
- Regulations
- Example notifications
- Announcements
- Q & A documents
- Testing advice
- Recorded webinars
- ...and more!





Take Aways

Engine Type:

•An existing non-emergency spark ignition 4-stroke rich burn engine at an area source with a site rating of greater than 500 HP which is operated 24 hours or less per calendar year

Standards:

- •Change oil/filter (can use oil analysis program) and inspect hoses and belts every 500 hours or annually and replace as needed
- •Inspect spark plugs and replace as necessary every 1,000 hours or annually

Monitoring:

•Operate/maintain engine according to manufacturer's instructions or develop maintenance plan



Take Aways

Recordkeeping:

- •Keep records of engine maintenance
- •Retain records for 5 years

Testing and Reporting:

None required

Compliance Date:

•October 19, 2013

