

# Connecticut Department of Energy and Environmental Protection











# National Emission Standards for Hazardous Air Pollutants for Reciprocating Internal Combustion Engines (RICE Rule)



# 40 CFR 63 Subpart ZZZZ Area Source Existing Non-Emergency Spark Ignition 4-Stroke Rich Burn Engine ≤500 Horsepower



## To comply with this rule, you must meet the following standards:

#### Every 1,440 hours of operation or annually, whichever comes first, you must:

- Change oil and filter
  - -Can utilize oil analysis program to extend specified oil change requirement.
    - Analysis must be performed every 1,440 hours or annually, whichever comes first.
    - Analysis program must at a minimum analyze: Total Acid Number, viscosity, and percent water content.
    - •Condemning limits for these parameters are: Total Acid Number increases by >3.0 mg KOH/g from Total Acid Number of the oil when new; viscosity of the oil has changed by >20% from the viscosity of the oil when new; or percent water content (by volume) is >0.5.
    - •If all condemning limits are not exceeded you are not required to change the oil.
    - •If any limits are exceeded, change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results are received, change the oil within 2 days or before commencing operation, whichever is later.
    - •Keep records of parameters analyzed, results of the analysis, and oil changes.
    - Analysis program must be part of the engine maintenance plan.



## To comply with this rule, you must meet the following standards:

Every 1,440 hours of operation or annually, whichever comes first, you must:

•Inspect spark plugs, hoses, and belts, and replace as necessary

At all times you must operate/maintain all equipment in a manner consistent with safety and good air pollution control practices for minimizing emissions.



## You must show continuous compliance by...

- •Operating and maintaining the engine according to the manufacturer's emission-related operation and maintenance instructions; or
- •Develop and follow your own maintenance plan which must provide to the extent practicable for the maintenance and operation of the engine in a manner consistent with good air pollution control practice for minimizing emissions



## Monitoring Requirements



Photo crodit: EDA

Minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes.



To demonstrate compliance with all rule requirements, keep records of:

- •Maintenance conducted on the engine to demonstrate that you operated and maintained the engine and after-treatment control device (if any) according to your own maintenance plan.
- •Keep records for 5 years from the date of creation.





# By when must I comply with the rule?

Your compliance date is: October 19, 2013




Photo credit: EPA



# Visit the EPA RICE Compliance Page

## www.epa.gov/ttn/atw/icengines/

- Fact sheets
- Regulations
- Example notifications
- Announcements
- Q & A documents
- Testing advice
- Recorded webinars
- ...and more!





# Take Aways

#### **Engine Type:**

•An existing non-emergency spark ignition 4-stroke rich burn engine at an area source with a site rating of less than or equal to 500 HP

#### Standards:

•Change oil and filter (can use oil analysis program) and inspect spark plugs, hoses, and belts every 1,440 hours or annually (replace as necessary)

#### Monitoring:

•Operate/maintain engine according to manufacturer's instructions or develop maintenance plan



# Take Aways

#### Recordkeeping:

- •Keep records of engine maintenance
- •Retain records for 5 years

### Testing and Reporting:

None required

#### **Compliance Date:**

•October 19, 2013

