

CONNECTICUT AND U.S. COAST GUARD MINIMUM REQUIREMENTS				
Equipment	Class A Less than 16 feet (less than 4.9 m)	Class 1 16 feet to less than 26 feet (4.9 to less than 7.9m)	Class 2 26 to less than 40 feet (7.9 to 12.2m)	Class 3 40 to less than 65 feet (12.2 to less than 19.8m)
Backfire Flame Arrestor	The device must be suitably attached to the air intake with a flametight connection and is required to be Coast Guard Approved or comply with SAEJ-1928 or UL1111 standards and marked accordingly.			
Ventilation Boats built before Aug. 1, 1980	At least two ventilator ducts, fitted with cowls or their equivalent, for the purpose of properly and effectively ventilating the bilges of every closed engine and fuel tank compartment of boats constructed or decked over after April 25, 1940, using gasoline as fuel.			
Ventilation Boats built on or after Aug. 1, 1980	At least two ventilator ducts for the purpose of efficiently ventilating every closed compartment that contains a gasoline engine and every closed compartment containing a gasoline tank, except those having permanently installed tanks which vent outside the boat and which contain no unprotected electrical devices. Also, engine compartments containing a gasoline engine having a cranking motor must be open to the atmosphere or contain power operated exhaust blowers which can be controlled from the instrument panel.			
Personal Flotation Devices	One approved Type I, II, III or V PFD for each person on board or being towed on waterskis, etc. Check label if using Type V.	One approved Type I, II, III or V PFD for each person on board or being towed on waterskis, etc.; and, in addition, one throwable Type IV device. (Type IV not required for canoes and kayaks.) Check label if using Type V.		
Sound- Producing Devices	Must carry approved visual distress signals for nighttime use when operating at night.	Must have some means of making an efficient sound signal.	Must have some means of making an efficient sound signal.	Must have a whistle audible for at least one-half mile.
Visual Distress Signals Required on coastal waters only	Must carry approved visual distress signals for nighttime use when operating at night.	Must carry visual distress signals approved for both daytime use and nighttime use.		

SAFETY EQUIPMENT

U.S. Coast Guard Fire Extinguisher Requirements

If your boat is less than 26' feet in length, uses an outboard engine, fuel is in a portable fuel tank, and there are no areas within the boat where fuel vapors can be trapped, the boat is not required to have a fire extinguisher.

Boat model year of 2018 and newer.		
NOTE - may carry only 5-B or 20-B rated fire extinguishers with date stamp		
Length (feet)	Minimum number of 5-B rated portable fire extinguishers required ¹	
	If no fixed fire extinguishing system in machinery space	If fixed fire extinguishing system in machinery space
Under 16	1	0
16 but less than 26	1	0
26 but less than 40	2	1
40 up to 65	3	2
¹ One 20-B, rated portable fire extinguisher may be substituted for two 5-B portable fire extinguishers. One 10-B is not a substitute for two 5-B.		

Boat model year between 1953 and 2017		
NOTE - may carry either 5-B, 20-B rated extinguishers with date stamp or B-I, B-II rated fire extinguishers		
Length (feet)	Minimum number of B-I/5-B, or B-II/20-B rated portable fire extinguishers required ¹	
	If no fixed fire extinguishing system in machinery space	If fixed fire extinguishing system in machinery space
Under 16	1	0
16 but less than 26	1	0
26 but less than 40	2	1
40 up to 65	3	2
¹ One 20-B/B-II, rated portable fire extinguisher may be substituted for two 5-B/B-I portable fire extinguishers. One 10-B is not a substitute for two 5-B.		