

State of Connecticut - Department of Public Health

LEAD AND HEALTHY HOMES PROGRAM REGISTRY OF AUTHORIZED ENCAPSULANT PRODUCTS



Encapsulants are coatings applied in liquid or cementitious form, that are made to be long-lasting barriers over lead paint. Conventional paint is not an encapsulant. Only the products listed on this Registry are authorized for use in Connecticut. Encapsulant use is prohibited on thresholds, window sashes, window parting beads, window stops, window wells, door jambs, door edges, or friction surfaces. Follow manufacturer's instructions/recommendations for product use. Please refer to the Encapsulant Product Fact Sheet and manufacturer's literature for more detailed information on each product. Authorizations followed by an asterisk (*) are valid for a one year period from the authorization date indicated.

Product Name	Manufacturer	Not Listed for Use on These Surfaces	Finished Product Thickness	Respiratory Protection Required	Occupancy During Application	Interior Use	Authorization Date
LeadLock™ - (Liquid)/ Your Last Coat™ (Liquid)	Global Encasement, Inc. 701 E. Santa Clara St. Ventura, CA 93001 (800) 266-3982	Friction surfaces, surfaces with chalking or calcimine must be properly prepared.	7 Mils - interior 16 Mils - exterior	For spray application use Molded Polymesh Shell Dust and Mist Respirator - MSHA/NIOSH Approval #TC-21C-287 or Equivalent.	No - During day of spray application. No - In work area if brush or roller used. Occupancy permitted in other areas if brush or roller used and adequate ventilation is provided for 24 hours after application.	Interior: YES Exterior: YES	04/17/96 Original 12/5/11 revision to Mil thickness
L-B-C™ Lead Barrier Compound Type I (Liquid)	Fiberlock Technologies Inc. 150 Dascomb Road Andover, MA 01810 (978) 623-9987 (800) 342-3755	Friction surfaces or surfaces with chalking or calcimine.	7 Mils	For spray application use Molded Polymesh Shell Dust and Mist Respirator - MSHA/NIOSH approval #TC-21C-287 or equivalent.	No - During day of spray application. No - In work area if brush or roller used. In other areas if brush or roller used and adequate ventilation is provided for 24 hours after application.	Interior: YES Exterior: NO	4/25/96

State of Connecticut - Department of Public Health

LEAD AND HEALTHY HOMES PROGRAM REGISTRY OF AUTHORIZED ENCAPSULANT PRODUCTS



Encapsulants are coatings applied in liquid or cementitious form, that are made to be long-lasting barriers over lead paint. Conventional paint is not an encapsulant. Only the products listed on this Registry are authorized for use in Connecticut. Encapsulant use is prohibited on thresholds, window sashes, window parting beads, window stops, window wells, door jambs, door edges, or friction surfaces. Follow manufacturer's instructions/recommendations for product use. Please refer to the Encapsulant Product Fact Sheet and manufacturer's literature for more detailed information on each product. Authorizations followed by an asterisk (*) are valid for a one year period from the authorization date indicated.

Product Name	Manufacturer	Not Listed for Use on These Surfaces	Finished Product Thickness	Respiratory Protection Required	Occupancy During Application	Interior Use	Authorization Date
L-B-C® Lead Barrier Compound Type III (Interior/Exterior)/ Child Guard (Interior/Exterior) (Liquid)	Fiberlock Technologies, Inc. 150 Dascomb Road Andover, MA 01810 02139-0802 (978) 623-9987 (800) 342-3755	Friction surfaces, impact surfaces, surfaces with calcimine paint, and radiators where temperature exceeds 212°F. Chalking surfaces must be adequately prepared.	7 Mils	For spray application use MSHA/NIOSH approved respirator.	Occupancy in adjacent room(s) permitted during brush or roller application. Occupancy during spray application is not permitted. Occupancy permitted once application has ceased and product is dry to the touch.	Interior: Yes Exterior: Yes	3/1/2000
Plaster -In-A-Roll (Cementitious) Gypsum Impregnated Jute Fabric	Flexi-Wall Systems 208 Carolina Drive P.O. Box 89 Liberty, South Carolina 29657-0089 (800) 843-5394	Not for use on interior surfaces other than walls and ceilings. Not recommended for use in areas where contact with moisture is likely.	35 Mils	Generally not required during normal use and handling of water based adhesive #500 as applied to Plaster-In-A-Roll.	Occupancy in adjacent room(s) permitted during application. Occupancy after application permitted after 24 hours.	Interior: YES Exterior: NO	9/16/96

State of Connecticut - Department of Public Health

LEAD AND HEALTHY HOMES PROGRAM REGISTRY OF AUTHORIZED ENCAPSULANT PRODUCTS



Encapsulants are coatings applied in liquid or cementitious form, that are made to be long-lasting barriers over lead paint. Conventional paint is not an encapsulant. Only the products listed on this Registry are authorized for use in Connecticut. Encapsulant use is prohibited on thresholds, window sashes, window parting beads, window stops, window wells, door jambs, door edges, or friction surfaces. Follow manufacturer's instructions/recommendations for product use. Please refer to the Encapsulant Product Fact Sheet and manufacturer's literature for more detailed information on each product. Authorizations followed by an asterisk (*) are valid for a one year period from the authorization date indicated.

Product Name	Manufacturer	Not Listed for Use on These Surfaces	Finished Product Thickness	Respiratory Protection Required	Occupancy During Application	Interior Use	Authorization Date
Faster Plaster Wall Liner (Cementitious) Gypsum Impregnated Jute Fabric	Flexi-Wall Systems 208 Carolina Drive P.O. Box 89 Liberty, South Carolina 29657-0089 (800) 843-5394	Not for use on interior surfaces other than walls and ceilings. Not recommended for use in areas where contact with moisture is likely.	50 Mils	Generally not required during normal use and handling of water based adhesive #500 as applied to Faster Plaster Wall Liner.	Occupancy in adjacent room(s) permitted during application. Occupancy after application permitted after 24 hours.	Interior: YES Exterior: NO	9/16/96
Encapsulating System: SE-110 Penetrating -- Stabilizer (Liquid) SE-120 Protective -- Skin (Liquid)	Safe Encasement Systems 450 Hillside Dr., Unit 405 Mesquite, NV 89027 (888) 277-8834	Friction surfaces, impact surfaces, traffic bearing surfaces, surfaces with calcimine paint.	SE-110 - 5 Mils SE-120 - 7 Mils	For spray, brush or roller applications use MSHA/NIOSH approved respirator suitable for organic vapors.	No - During spray, brush or roller application. Occupancy is restricted until the completion of application, cleanup is completed and the applied materials are dry to the touch and odors are no longer present. Continue ventilating the area for 48 hours after application.	Interior: YES Exterior: YES	04/30/01

State of Connecticut - Department of Public Health
LEAD AND HEALTHY HOMES PROGRAM
REGISTRY OF AUTHORIZED ENCAPSULANT PRODUCTS



Encapsulants are coatings applied in liquid or cementitious form, that are made to be long-lasting barriers over lead paint. Conventional paint is not an encapsulant. Only the products listed on this Registry are authorized for use in Connecticut. Encapsulant use is prohibited on thresholds, window sashes, window parting beads, window stops, window wells, door jambs, door edges, or friction surfaces. Follow manufacturer's instructions/recommendations for product use. Please refer to the Encapsulant Product Fact Sheet and manufacturer's literature for more detailed information on each product. Authorizations followed by an asterisk (*) are valid for a one year period from the authorization date indicated.

THIS IS VERSION 11-14 OF THE REGISTRY, DATED DECEMBER 6, 2011. IT WILL BE UPDATED PERIODICALLY. PLEASE CHECK WITH THE DEPARTMENT'S LEAD AND HEALTHY HOMES PROGRAM AT (860) 509-7299 FOR THE MOST RECENT VERSION. THE REGISTRY CAN ALSO BE FOUND ON THE DEPARTMENT'S WEB PAGE AT WWW.CT.GOV/DPH/LEAD.