



UTILITY INSTALLATIONS UNDER ENCROACHMENT PERMITS

Work performed within the Connecticut Department of Transportation’s right-of-way paved roadway should be in compliance with the Standard Specifications for Roads, Bridges, Facilities and Incidental Construction; including all supplements and revisions, Encroachment Permit-Pavement Repair Drawing and other applicable standards.

Bituminous Concrete: Section 4.06	3” HMA S0.5 TRAFFIC LEVEL 2, PLACED IN TWO EQUAL LIFTS OR AS DIRECTED BY THE PERMIT INSPECTOR
	6” HMA S1.0 TRAFFIC LEVEL 2, PLACED IN TWO EQUAL LIFTS OR MATCH EXISTING PAVEMENT OR PORTLAND CEMENT CONCRETE THICKNESS, WHICHEVER IS GREATER <i>Minimum of 92% Compaction</i>
Processed Aggregate Base: Section 3.04 Spec. M.05.01	10” PROCESSED AGGREGATE BASE MATERIAL COMPACTED IN 5” LIFTS <i>Minimum of 95% Compaction</i>
Compacted Granular Fill: Section 2.14 Spec. M.02.02	PLACE IN 8” LIFTS OR AS DIRECTED BY THE PERMIT INSPECTOR <i>Minimum of 95% Compaction</i>
Bedding Material: Spec. M.08.03	Apex 1 foot of Bedding Cover
	Bedding <div style="display: inline-block; border: 2px solid black; border-radius: 50%; width: 60px; height: 60px; background-color: black; color: white; text-align: center; vertical-align: middle; margin-left: 20px;"> MAIN </div>
	Bedding/Stone