Town of Ridgefield Train Station: -Branchville

CONNECTICUT COORDINATE	GRID	
	BIT CONCWALK BIT CONCWALK CONCWA	OI BRAN-CC-1 BRAN- BRAN- CANOPY OUT TOP I A. 74 OUTER GIRDEI BOX (1 CANO JUNCT FOR C.
	10. Dβ	32 ~
VIE REVISION DESCRIPTION	SIGNATURE/	

LASTED SAVED BY: tluy FILE NAME: C:\Users\tluy\State of Connecticut\0300-0215 - Design\F_Elect\Contract_Plans\Branch Lines\Danbury Branch\EL_CP_0300_0215_Branchville_Station_Camera_Layout_FCI-331.dgn PLOTTED DATE: 5/11/2023



BRANCHVILLE STATION CAMERA LAYOUT

SCALE: 1"=20'

GENERAL NOTES:

- 1. SEE DWG. G-002 FOR ELECTRICAL GENERAL NOTES.
- 2. SEE DWG. FCI-332 FOR CAMERA SCHEDULE.

- 7
- DETAIL 4/FCI-643 FOR BOLLARD.
- PER NEC.



PROJECT NUMBER: 0300-0215

PROJECT DESCRIPTION: NETWORK INFRASTRUCTURE UPGRADE FOR SECURITY - P TOWN(S): BRANCHVILLE

DRAWING TITLE: BRANCHVILLE STATION PLAN

RAILROAD SOUTH TO NEW HAVEN MAIN LINE

SEE DWG. G-003 FOR ELECTRICAL ABBREVIATIONS AND LEGEND.

3. SEE DWG. FCI-333 FOR DEVICE CONNECTIVITY DIAGRAM.

4. THE CONTRACTOR SHALL FURNISH AND INSTALL 20A-1P CIRCUIT BREAKER INSIDE EXISTING POWER PANEL, PP1, LOCATED IN MAIN ELECTRICAL CABINET. NEW CIRCUIT BREAKER SHALL MATCH EXISTING MANUFACTURER AND AIC RATING.

5. THE CONTRACTOR SHALL FURNISH AND INSTALL (2) #10 AWG + (1) #10 GND IN (1) 1" PVC COATED CONDUIT FROM EXISTING POWER PANEL "PP" LOCATED IN MAIN ELECTRICAL PAD MOUNT CABINET TO PROPOSED CCTV CABINET AS SHOWN ON THIS DRAWING. THE CONTRACTOR SHALL CORE DRILL THRU BOTTOM OF THE EXISTING ELECTICAL CABINET AND INSTALL PVC COATED CONDUIT ALONG WITH EXPANSION FIRRING. THE CONTRACTOR SHALL FURNISH AND INSTALL NEW JUCTION BOX ON BACK SIDE OF PLATFORM CONCRETE GIRDER AND INSTALL (1) 1" PVC COATED POWER CONDUIT TO NEW CCTV CABINET.

6. CCTV CABINET SHALL BE MOUNTED ON MIN. 48" THICK CONCRETE PAD. THE CONTRACTOR SHALL SUBMIT DETAILED SHOP DRAWING SHOWING NECESSARY REBARS FOR ENGINEER'S APPROVAL PRIOR TO PROCEED PAD INSTALLATION WORK. ALL INCOMING AND OUTGOING CONDUIT SHALL BE INSTALLED FROM BOTTOM OF THE CCTV CABINET AND RUN UNDERGROUND TO PLATFORM CONCRETE GIRDER MOUNTED JUNCTION BOX. ALL INCOMING, OUTGOING CONDUITS AND SPARE CONDUITS SHALL BE SEALED AT THE CCTV CABINET WALL AND AT THE OPENING BY USING APPROVED MATERIAL.

CONDUIT ON THIS SHEET SHALL BE MOUNTED ON BACK SIDE OF PLATFORM CONCRETE GIRDER. ALL ABOVE GROUND AND UNDERGROUND CONDUITS SHALL BE PVC COATED RGSC, UNLESS OTHERWISE NOTED. THE CONTRACTOR SHALL SUBMIT DETAIL CONDUIT INSTALLATION PLAN FOR ENGINEER'S APPROVAL PRIOR TO PROCEED CONDUIT INSTALLATION WORK.

8. THE CONTRACTOR SHALL FURNISH AND INSTALL PVC COATED CONDUITS FROM PLATFORM CONCRETE GIRDER MOUNTED JUNCTION BOX UP TO CANOPY CEILING. ROUTE CONDUIT ALONG CANOPY STEEL COLUMN TO CANOPY CEILING AND RUN HORIZONTALLY IN CANOPY STEEL BEAM TO PROPOSED CAMERA JUNCTION BOX.

9. THE CONTRACTOR SHALL INSTALL TWO (2) BOLLARDS IN FRONT OF NEW CCTV CABINET AS SHOWN IN THIS DRAWING, SEE

10. THE CONTRACTOR SHALL INSTALL JUNCTION BOX TO COMPLY NEC WIRE PULL REQUIREMENT. JUNCTION BOX SHALL BE SIZED

	DRAWING NO.
PHASE 4	FCI-331
	SHEET NO.
	1