



DEPARTMENT OF ADMINISTRATIVE SERVICES

PROPOSED CHANGE OF THE CONNECTICUT STATE  
BUILDING CODE AND FIRE SAFETY CODE

DATE SUBMITTED: April 2, 2024

**CODE INFORMATION**

Proposed change to: ☒ Building Code ☐ Fire Safety Code

Code section(s): INTERNATIONAL BUILDING CODE - (NEW) SECTION 2703.2 -

**PROPONENT INFORMATION**

Name: Leo Smith

Representing: DarkSky International

Telephone: 860-668-4000

Email: Leo@Smith.net

Address: 64 Boysenberry Court, Suffield, CT 06078  
Street Address Town State Zip Code

**PROPOSAL INFORMATION**

Description of change and reason for change (attach additional information as needed):

Add new section 2703.2 - Limits on Color Temperature of Exterior Lighting

Proposed text change, addition or deletion (attach additional information as needed):

See Attached

Supporting data and documents (attach additional information as needed) **The required use of a maximum 3000K CCT lamp will not impose any financial burden on commercial developers nor on building owners, while the**

**3000K maximum will significantly reduce the amount of light pollution. See Attached**

☒ **This Proposal is original material.** (Note: Original material is considered to be the submitter's own idea based on or as a result of his/her own experience, thought or research and, to the best of his/her knowledge, is not copied from another source.)

☐ **This Comment is not original material, its source (if known) is as follows:** (such as material / code development proposal from a prior development cycle or proposal submitted to model code committee etc.)

☒ **I would like to make an in-person presentation of my proposal.**

**Release**

I hereby grant the State of Connecticut full rights to the use of this material without benefit to me, including, but not limited to, publication and reproduction rights.

  
Proponent's Signature

Leo F Smith  
Printed Name

PLEASE EMAIL (PREFERRED) TO [DAS.CodesStandards@CT.GOV](mailto:DAS.CodesStandards@CT.GOV) OR MAIL OR FAX (SEE BELOW)

*Department of Administrative Services  
Office of the State Building Inspector  
450 Columbus Boulevard, Suite 1303  
Hartford, CT 06103  
Tel: 860-713-5900 Fax: 860-713-7410  
Affirmative Action/Equal Opportunity Employer*

12/29/16

**Proposed Change, Addition or Deletion to 2021 INTERNATIONAL BUILDING CODE -**

**CHAPTER 27 – ELECTRICAL - Section 2703.1 - Light Pollution Controls**

**Proposed Code Change: Add a NEW subsection 2703.2 Titled LIMIT ON CORRELATED COLOR TEMPERATURE OF EXTERIOR LIGHTING**

**Proposed Code Change Wording:**

**(NEW) 2703.2 Maximum Correlated Color Temperature. For any luminaire used to illuminate of any parking area, open sales lot, landscape, building facade or general area, the maximum Correlated Color Temperature (CCT) of the light source may not exceed 3000 Kelvin, as rated by the manufacturer.**

**REASON FOR ADDITION**

Historically, prior to LEDs, high pressure sodium lamps were often used for exterior lighting, with a correlated color temperature (CCT) rating of 2200K (Kelvin). Light pollution has significantly increased with LEDs. A primary reason for this increase in light pollution is the high CCT associated with many LEDs. CCT ratings for LEDs range from 2700K to 5000K CCT. The higher the CCT rating, the greater the emission of blue wavelength light. Higher levels of blue wavelength light directly cause significant increases of light pollution.

Over the past 10 years, research has shown that prolonged exposure to blue-spectrum light has serious health consequences for humans and the environment as well.

In 2016, the American Medical Association published guidance to reduce harm from high-intensity blue lighting from LEDs, citing evidence that nighttime exposure to blue-rich white light leads to increased risk for cancer, diabetes, and cardiovascular disease and that blue-rich LED streetlights are five times as disruptive to the human sleep cycle as conventional lighting (American Medical Association, "Human and Environmental Effects of Light Emitting Diode

(LED) Community Lighting," CSAPH Report 2-A-16, 2016). Excessive blue-spectrum light is environmentally disruptive for many classes of animals and plants, including migrating birds. Blue light has been shown to negatively affect plant greening, budburst, photoperiodic flowering, stomatal opening, and root development (see, for example, C.C. Brelsford and T.M. Robson, "Blue Light Advances Bud Burst in Branches of Three Deciduous Tree Species Under Short-day Conditions," *Trees*, 2018. 32(4): p. 1157–1164). In particular, scientists have highlighted the consequences of the increasingly widespread use of blue spectrum light-emitting diode technology for new lighting installations and retrofits (Gaston et al., "Environmental Impacts of Artificial Light at Night," *Annual Review of Environment and Resources* 2022.47:373-398).

Manufacturers offer 3000K CCT products in their general offerings, and do not add any up charge for a 3000K CCT lamp over what they charge for a 4000K or 5000K CCT lamp. Manufacturers reduce the blue wavelength light emissions by applying the light emitting diode with a phosphor coating.

Essentially, the requirement of a maximum 3000K CCT lamp will not impose any financial burden on commercial developers or building owners, while the 3000K maximum will significantly reduce the adverse effects from light pollution.

**FEASIBILITY:** 3000K CCT LED lights are widely available in the market for applications such as area, parking lot, facade and landscape lighting. 2700K CCT is the average produced by incandescent lighting, which was used universally for outdoor lighting in the 1930s, 40s and 50s, prior to high pressure sodium. The CCT for high pressure sodium averages 2200K.

**Fiscal Impact:** None - LED lights sold at different CCT values are not priced differently. A 3000K version costs the same as a 4000K or 5000K version. Yet the 3000K will substantially reduce the amount of light pollution generated by the LED luminaire.

## SUPPORTING DATA AND DOCUMENTATION

In 2016 the American Medical Association adopted a new policy advocating for the maximum of 3000K CCT for lighting. Following the below scientific studies finding harm from high CCT light is the AMA's 2016 Findings regarding LED lighting and its recommendation not to use outdoor lighting in excess of 3000K CCT.

---

2010, “**Visibility, Environmental, and Astronomical Issues Associated with Blue-Rich White Outdoor Lighting**,” detailing the hazards of blue-rich white light sources.  
<https://darksky.org/app/uploads/2016/12/IDA-Blue-Rich-Light-White-Paper.pdf>

2020, Harvard Health “**Blue light has a dark side**”, Effects of blue light and sleep  
[https://www.health.harvard.edu/staying-healthy/blue-light-has-a-dark-side#:~:text=Harvard%20researchers%20and%20their%20colleagues,as%20much%20\(3%20hours%20vs.](https://www.health.harvard.edu/staying-healthy/blue-light-has-a-dark-side#:~:text=Harvard%20researchers%20and%20their%20colleagues,as%20much%20(3%20hours%20vs.)

2016, Scientific Advances “**The new world atlas of artificial night sky brightness**” The map shows the forecast of the perceived sky brightness for a dark-adapted eye after a transition toward **4000K CCT LED technology**  
<https://www.science.org/doi/10.1126/sciadv.abl6891>

2023, The Washington Post “LED lights are meant to save energy. They're creating glaring problems: <https://www.washingtonpost.com/climate-environment/interactive/2023/glaring-problem-how-led-lights-worsen-light-pollution/>

2023, Science, “**Light pollution is skyrocketing**” This growth is difficult to discern with satellites now in operation because their detectors are blind to the blue light emitted by light-emitting diodes (LEDs), which are progressively replacing older lamps (such as high-intensity discharge). <https://www.science.org/doi/10.1126/science.adf4952>

2019, National Geographic, “**Light pollution is getting worse, and Earth is paying the price**” “...inexpensive white LEDs often found in street lights emit wavelengths of blue light that bounce around in the atmosphere” <https://www.nationalgeographic.com/science/article/nights-are-getting-brighter-earth-paying-the-price-light-pollution-dark-skies>

2023, LED Magazine “Lumileds aims to take back the night with low-blue LED offerings” “LED developer says NightScape technology delivers blue light levels below 2% to meet stringent outdoor lighting regulations.” <https://www.ledsmagazine.com/lighting-health-wellbeing/article/14296284/lumileds-aims-to-take-back-the-night-with-lowblue-led-offerings>



## Connecticut Medical Society Letter in Support of reducing CCT (2019)



127 Washington Avenue, East Building, 3rd Floor, North Haven, CT 06473  
Phone (203) 865-0587 Fax (203) 865-4997 [www.csms.org](http://www.csms.org)

August 15, 2019

Mr. Louis Free, Chairman  
Codes Amendment Subcommittee of the  
State Codes and Standards Committee  
Via Email to: [DAS.CodesStandards@CT.GOV](mailto:DAS.CodesStandards@CT.GOV) ; [louis.free@aecom.com](mailto:louis.free@aecom.com)

Re: Support for Proposed Code Amendment C302.3 - Limiting the Amount of Blue Wavelength Light from Exterior Lighting Fixtures - **Proposal # 190027**

Dear Members of the Codes Amendment Subcommittee:

The Connecticut State Medical Society (CSMS) respectfully requests approval of the proposed code change limiting the amount of blue wavelength emissions from LED outdoor lighting.

In June of 2016 the American Medical Association (AMA) released its report indicating potential harm from blue wavelength LED emissions. This potential harm from blue wavelength emissions applies to human health as well as to the ecology. In that report, the AMA urged the adoption of a limit to blue wavelength emissions – capping it at a maximum Correlated Color Temperature (CCT) of 3000K (Kelvin).

To the best of our knowledge, there is no cost differential between exterior LED light fixtures at 3000K CCT and those with higher blue wavelength emissions. The end user still is able to light the property using an LED with maximum 3000K CCT – at no increase in price – only an increase in benefits to human health, to a better ecology, and to a lower level of light pollution.

For the reasons stated above, CSMS respectfully urges the adoption of Proposal 190027 to limit exterior LEDs to a maximum of 3000K CCT in the best interest of a healthier environment for Connecticut's citizens and its ecology.

Respectfully submitted,

Matthew Katz  
EVP/CEO



REPORT OF THE COUNCIL ON SCIENCE AND PUBLIC HEALTH

CSAPH Report 2-A-16

Subject: Human and Environmental Effects of Light Emitting Diode (LED) Community Lighting

Presented by: Louis J. Kraus, MD, Chair

Referred to: Reference Committee E  
(Theodore Zanker, MD, Chair)

---

## INTRODUCTION

With the advent of highly efficient and bright light emitting diode (LED) lighting, strong economic arguments exist to overhaul the street lighting of U.S. roadways.<sup>1-3</sup> Valid and compelling reasons driving the conversion from conventional lighting include the inherent energy efficiency and longer lamp life of LED lighting, leading to savings in energy use and reduced operating costs, including taxes and maintenance, as well as lower air pollution burden from reduced reliance on fossil-based carbon fuels.

Not all LED light is optimal, however, when used as street lighting. Improper design of the lighting fixture can result in glare, creating a road hazard condition.<sup>4,5</sup> LED lighting also is available in various color correlated temperatures. Many early designs of white LED lighting generated a color spectrum with excessive blue wavelength. This feature further contributes to disability glare, i.e., visual impairment due to stray light, as blue wavelengths are associated with more scattering in the human eye, and sufficiently intense blue spectrum damages retinas.<sup>6,7</sup> The excessive blue spectrum also is environmentally disruptive for many nocturnal species. Accordingly, significant human and environmental concerns are associated with short wavelength (blue) LED emission. Currently, approximately 10% of existing U.S. street lighting has been converted to solid state LED technology, with efforts underway to accelerate this conversion. The Council is undertaking this report to assist in advising communities on selecting among LED lighting options in order to minimize potentially harmful human health and environmental effects.

## METHODS

English language reports published between 2005 and 2016 were selected from a search of the PubMed and Google Scholar databases using the MeSH terms “light,” “lighting methods,” “color,” “photostimulation,” and “adverse effects,” in combination with “circadian

rhythm/physiology/radiation effects,” “radiation dosage/effects,” “sleep/physiology,” “ecosystem,” “environment,” and “environmental monitoring.” Additional searches using the text terms “LED” and “community,” “street,” and “roadway lighting” were conducted. Additional information and perspective were supplied by recognized experts in the field.

## ADVANTAGES AND DISADVANTAGES OF LED STREET LIGHTS

The main reason for converting to LED street lighting is energy efficiency; LED lighting can reduce energy consumption by up to 50% compared with conventional high pressure sodium (HPS)



1 lighting. LED lighting has no warm up requirement with a rapid "turn on and off" at full intensity.  
2 In the event of a power outage, LED lights can turn on instantly when power is restored, as  
3 opposed to sodium-based lighting requiring prolonged warm up periods. LED lighting also has the  
4 inherent capability to be dimmed or tuned, so that during off peak usage times (e.g., 1 to 5 AM),  
5 further energy savings can be achieved by reducing illumination levels. LED lighting also has a  
6 much longer lifetime (15 to 20 years, or 50,000 hours), reducing maintenance costs by decreasing  
7 the frequency of fixture or bulb replacement. That lifespan exceeds that of conventional HPS  
8 lighting by 2-4 times. Also, LED lighting has no mercury or lead, and does not release any toxic  
9 substances if damaged, unlike mercury or HPS lighting. The light output is very consistent across  
10 cold or warm temperature gradients. LED lights also do not require any internal reflectors or glass  
11 covers, allowing higher efficiency as well, if designed properly.<sup>8,9</sup>

12  
13 Despite the benefits of LED lighting, some potential disadvantages are apparent. The initial cost is  
14 higher than conventional lighting; several years of energy savings may be required to recoup that  
15 initial expense.<sup>10</sup> The spectral characteristics of LED lighting also can be problematic. LED  
16 lighting is inherently narrow bandwidth, with "white" being obtained by adding phosphor coating  
17 layers to a high energy (such as blue) LED. These phosphor layers can wear with time leading to a  
18 higher spectral response than was designed or intended. Manufacturers address this problem with  
19 more resistant coatings, blocking filters, or use of lower color temperature LEDs. With proper  
20 design, higher spectral responses can be minimized. LED lighting does not tend to abruptly "burn  
21 out," rather it dims slowly over many years. An LED fixture generally needs to be replaced after it  
22 has dimmed by 30% from initial specifications, usually after about 15 to 20 years.<sup>1,11</sup>

23  
24 Depending on the design, a large amount of blue light is emitted from some LEDs that appear white  
25 to the naked eye. The excess blue and green emissions from some LEDs lead to increased light  
26 pollution, as these wavelengths scatter more within the eye and have detrimental environmental  
27 and glare effects. LED's light emissions are characterized by their correlated color temperature  
28 (CCT) index.<sup>12,13</sup> The first generation of LED outdoor lighting and units that are still widely being  
29 installed are "4000K" LED units. This nomenclature (Kelvin scale) reflects the equivalent color of  
30 a heated metal object to that temperature. The LEDs are cool to the touch and the nomenclature has  
31 nothing to do with the operating temperature of the LED itself. By comparison, the CCT associated  
32 with daylight light levels is equivalent to 6500K, and high pressure sodium lighting (the current  
33 standard) has a CCT of 2100K. Twenty-nine percent of the spectrum of 4000K LED lighting is  
34 emitted as blue light, which the human eye perceives as a harsh white color. Due to the point-  
35 source nature of LED lighting, studies have shown that this intense blue point source leads to  
36 discomfort and disability glare.<sup>14</sup>

37  
38 More recently engineered LED lighting is now available at 3000K or lower. At 3000K, the human  
39 eye still perceives the light as "white," but it is slightly warmer in tone, and has about 21% of its  
40 emission in the blue-appearing part of the spectrum. This emission is still very blue for the  
41 nighttime environment, but is a significant improvement over the 4000K lighting because it  
42 reduces discomfort and disability glare. Because of different coatings, the energy efficiency of  
43 3000K lighting is only 3% less than 4000K, but the light is more pleasing to humans and has less  
44 of an impact on wildlife.  
45



46 *Glare*

47  
48 Disability glare is defined by the Department of Transportation (DOT) as the following:

49  
50 “Disability glare occurs when the introduction of stray light into the eye reduces the ability to  
51 resolve spatial detail. It is an objective impairment in visual performance.”

---

CSAPH Rep. 2-A-16 -- page 3 of 8

1 Classic models of this type of glare attribute the deleterious effects to intraocular light scatter in the  
2 eye. Scattering produces a veiling luminance over the retina, which effectively reduces the contrast  
3 of stimulus images formed on the retina. The disabling effect of the veiling luminance has serious  
4 implications for nighttime driving visibility.<sup>15</sup>

5  
6 Although LED lighting is cost efficient and inherently directional, it paradoxically can lead to  
7 worse glare than conventional lighting. This glare can be greatly minimized by proper lighting  
8 design and engineering. Glare can be magnified by improper color temperature of the LED, such as  
9 blue-rich LED lighting. LEDs are very intense point sources that cause vision discomfort when  
10 viewed by the human eye, especially by older drivers. This effect is magnified by higher color  
11 temperature LEDs, because blue light scatters more within the human eye, leading to increased  
12 disability glare.<sup>16</sup>

13  
14 In addition to disability glare and its impact on drivers, many residents are unhappy with bright  
15 LED lights. In many localities where 4000K and higher lighting has been installed, community  
16 complaints of glare and a “prison atmosphere” by the high intensity blue-rich lighting are common.  
17 Residents in Seattle, WA have demanded shielding, complaining they need heavy drapes to be  
18 comfortable in their own homes at night.<sup>17</sup> Residents in Davis, CA demanded and succeeded in  
19 getting a complete replacement of the originally installed 4000K LED lights with the 3000K  
20 version throughout the town at great expense.<sup>18</sup> In Cambridge, MA, 4000K lighting with dimming  
21 controls was installed to mitigate the harsh blue-rich lighting late at night. Even in places with a  
22 high level of ambient nighttime lighting, such as Queens in New York City, many complaints were  
23 made about the harshness and glare from 4000K lighting.<sup>19</sup> In contrast, 3000K lighting has been  
24 much better received by citizens in general.



## *Unshielded LED Lighting*

Unshielded LED lighting causes significant discomfort from glare. A French government report published in 2013 stated that due to the point source nature of LED lighting, the luminance level of unshielded LED lighting is sufficiently high to cause visual discomfort regardless of the position, as long as it is in the field of vision. As the emission surfaces of LEDs are highly concentrated point sources, the luminance of each individual source easily exceeds the level of visual discomfort, in some cases by a factor of 1000.<sup>17</sup>

Discomfort and disability glare can decrease visual acuity, decreasing safety and creating a road hazard. Various testing measures have been devised to determine and quantify the level of glare and vision impairment by poorly designed LED lighting.<sup>20</sup> Lighting installations are typically tested by measuring foot-candles per square meter on the ground. This is useful for determining the efficiency and evenness of lighting installations. This method, however, does not take into account the human biological response to the point source. It is well known that unshielded light sources cause pupillary constriction, leading to worse nighttime vision between lighting fixtures and causing a “veil of illuminance” beyond the lighting fixture. This leads to worse vision than if the light never existed at all, defeating the purpose of the lighting fixture. Ideally LED lighting installations should be tested in real life scenarios with effects on visual acuity evaluated in order to ascertain the best designs for public safety.

## *Proper Shielding*

With any LED lighting, proper attention should be paid to the design and engineering features. LED lighting is inherently a bright point source and can cause eye fatigue and disability glare if it is allowed to directly shine into human eyes from roadway lighting. This is mitigated by proper

design, shielding and installation ensuring that no light shines above 80 degrees from the horizontal. Proper shielding also should be used to prevent light trespass into homes alongside the road, a common cause of citizen complaints. Unlike current HPS street lighting, LEDs have the ability to be controlled electronically and dimmed from a central location. Providing this additional control increases the installation cost, but may be worthwhile because it increases long term energy savings and minimizes detrimental human and environmental lighting effects. In environmentally sensitive or rural areas where wildlife can be especially affected (e.g., near national parks or bio-rich zones where nocturnal animals need such protection), strong consideration should be made for lower emission LEDs (e.g., 3000K or lower lighting with effective shielding). Strong consideration also should be given to the use of filters to block blue wavelengths (as used in Hawaii), or to the use of inherent amber LEDs, such as those deployed in Quebec. Blue light scatters more widely (the reason the daytime sky is “blue”), and unshielded blue-rich lighting that travels along the horizontal plane increases glare and dramatically increases the nighttime sky glow caused by excessive light pollution.



## POTENTIAL HEALTH EFFECTS OF “WHITE” LED STREET LIGHTING

Much has been learned over the past decade about the potential adverse health effects of electric light exposure, particularly at night.<sup>21-25</sup> The core concern is disruption of circadian rhythmicity. With waning ambient light, and in the absence of electric lighting, humans begin the transition to nighttime physiology at about dusk; melatonin blood concentrations rise, body temperature drops, sleepiness grows, and hunger abates, along with several other responses.

A number of controlled laboratory studies have shown delays in the normal transition to nighttime physiology from evening exposure to tablet computer screens, backlit e-readers, and room light typical of residential settings.<sup>26-28</sup> These effects are wavelength and intensity dependent, implicating bright, short wavelength (blue) electric light sources as disrupting transition. These effects are not seen with dimmer, longer wavelength light (as from wood fires or low wattage incandescent bulbs). In human studies, a short-term detriment in sleep quality has been observed after exposure to short wavelength light before bedtime. Although data are still emerging, some evidence supports a long-term increase in the risk for cancer, diabetes, cardiovascular disease and obesity from chronic sleep disruption or shiftwork and associated with exposure to brighter light sources in the evening or night.<sup>25,29</sup>

Electric lights differ in terms of their circadian impact.<sup>30</sup> Understanding the neuroscience of circadian light perception can help optimize the design of electric lighting to minimize circadian disruption and improve visual effectiveness. White LED streetlights are currently being marketed to cities and towns throughout the country in the name of energy efficiency and long term cost savings, but such lights have a spectrum containing a strong spike at the wavelength that most effectively suppresses melatonin during the night. It is estimated that a “white” LED lamp is at least 5 times more powerful in influencing circadian physiology than a high pressure sodium light based on melatonin suppression.<sup>31</sup> Recent large surveys found that brighter residential nighttime lighting is associated with reduced sleep time, dissatisfaction with sleep quality, nighttime awakenings, excessive sleepiness, impaired daytime functioning, and obesity.<sup>29,32</sup> Thus, white LED street lighting patterns also could contribute to the risk of chronic disease in the populations of cities in which they have been installed. Measurements at street level from white LED street lamps are needed to more accurately assess the potential circadian impact of evening/nighttime exposure to these lights.

---

CSAPH Rep. 2-A-16 -- page 5 of 8

---

## ENVIRONMENTAL EFFECTS OF LED LIGHTING

The detrimental effects of inefficient lighting are not limited to humans; 60% of animals are nocturnal and are potentially adversely affected by exposure to nighttime electrical lighting. Many birds navigate by the moon and star reflections at night; excessive nighttime lighting can lead to reflections on glass high rise towers and other objects, leading to confusion, collisions and death.<sup>33</sup> Many insects need a dark environment to procreate, the most obvious example being lightning bugs that cannot “see” each other when light pollution is pronounced. Other environmentally beneficial insects are attracted to blue-rich lighting, circling under them until they are exhausted and die.<sup>34,35</sup> Unshielded lighting on beach areas has led to a massive drop in turtle



populations as hatchlings are disoriented by electrical light and sky glow, preventing them from reaching the water safely.<sup>35-37</sup> Excessive outdoor lighting diverts the hatchlings inland to their demise. Even bridge lighting that is “too blue” has been shown to inhibit upstream migration of certain fish species such as salmon returning to spawn. One such overly lit bridge in Washington State now is shut off during salmon spawning season.

Recognizing the detrimental effects of light pollution on nocturnal species, U.S. national parks have adopted best lighting practices and now require minimal and shielded lighting. Light pollution along the borders of national parks leads to detrimental effects on the local bio-environment. For example, the glow of Miami, FL extends throughout the Everglades National Park. Proper shielding and proper color temperature of the lighting installations can greatly minimize these types of harmful effects on our environment.

## CONCLUSION

Current AMA Policy supports efforts to reduce light pollution. Specific to street lighting, Policy H-135.932 supports the implementation of technologies to reduce glare from roadway lighting. Thus, the Council recommends that communities considering conversion to energy efficient LED street lighting use lower CCT lights that will minimize potential health and environmental effects. The Council previously reviewed the adverse health effects of nighttime lighting, and concluded that pervasive use of nighttime lighting disrupts various biological processes, creating potentially harmful health effects related to disability glare and sleep disturbance.<sup>25</sup>

## RECOMMENDATIONS

The Council on Science and Public Health recommends that the following statements be adopted, and the remainder of the report filed.

1. That our American Medical Association (AMA) support the proper conversion to community-based Light Emitting Diode (LED) lighting, which reduces energy consumption and decreases the use of fossil fuels. (New HOD Policy)
2. That our AMA encourage minimizing and controlling blue-rich environmental lighting by using the lowest emission of blue light possible to reduce glare. (New HOD Policy)
3. That our AMA encourage the use of 3000K or lower lighting for outdoor installations such as roadways. All LED lighting should be properly shielded to minimize glare and detrimental human and environmental effects, and consideration should be given to utilize the ability of LED lighting to be dimmed for off-peak time periods. (New HOD Policy)

Fiscal Note: Less than \$500

## REFERENCES

1. Municipal Solid State Street Lighting Consortium. <http://www1.eere.energy.gov/buildings/ssl/consortium.html>. Accessed April 4, 2016.
2. Illuminating Engineering Society RP-8 – Guide to Roadway Lighting. <http://www.ies.org/> 2014. Accessed April 4, 2016.
3. LED Lighting Facts—A Program of the United States Department of Energy. <http://www.lightingfacts.com>. Accessed April 5, 2016.
4. Lin Y, Liu Y, Sun Y, Zhu X, Lai J, Heynderickx I. Model predicting discomfort glare caused by LED road lights. *Opt Express*. 2014;22(15):18056-71.
5. Gibbons RB, Edwards CJ. A review of disability and discomfort glare research and future direction. 18th Biennial TRB Visibility Symposium, College Station TX, United States, April 17-19, 2007.
6. Shang YM, Wang GS, Sliney D, Yang CH, Lee LL. White light-emitting diodes (LEDs) at domestic lighting levels and retinal injury in a rat model. *Environ Health Perspect*. 2014;122(3):269-76.
7. Lougheed T. Hidden blue hazard? LED lighting and retinal damage in rats, *Environ Health Perspect*. 2014;122(3):A81.
8. A Municipal Guide for Converting to LED Street Lighting, (<http://www1.eere.energy.gov/buildings/ssl/consortium.html>) 10/13/2013.
9. In depth: Advantages of LED Lighting. <http://energy.ltgovernors.com/in-depth-advantages-of-led-lighting.html>. Accessed April 5, 2016.
10. Silverman H. How LED Streetlights Work. HowStuffWorks.com. June 22, 2009. <http://science.howstuffworks.com/environmental/green-tech/sustainable/led-streetlight.htm>. Accessed April 7, 2016.
11. Jin H, Jin S, Chen L, Cen S, Yuan K. Research on the lighting performance of LED street lights with different color temperatures. *IEEE Photonics Journal*. 2015;24(6):975-78. <http://ieeexplore.ieee.org/stamp/stamp.jsp?arnumber=7328247>. Accessed April 7, 2016.
12. Morris N. LED there be light. Nick Morris predicts a bright future for LEDs. *Electrooptics.com*. <http://www.electrooptics.com/features/junjul06/junjul06leds.html>. Accessed April 7, 2016.
13. Mills MP. The LED illumination revolution. *Forbes Magazine*. February 27, 2008. [http://www.forbes.com/2008/02/27/incandescent-led-cfl-pf-guru\\_in\\_mm\\_0227energy\\_inl.html](http://www.forbes.com/2008/02/27/incandescent-led-cfl-pf-guru_in_mm_0227energy_inl.html). Accessed April 5, 2016.



14. Opinion of the French Agency for Food, Environmental and Occupational Health & Safety, October 19, 2010. <https://web.archive.org/web/20140429161553/http://www.anses.fr/Documents/AP2008sa0408EN.pdf>
15. U.S. Department of Transportation, Federal Highway Administration, 2005.
16. Sweater-Hickcox K, Narendran N, Bullough JD, Freyssinier JP. Effect of different coloured luminous surrounds on LED discomfort glare perception. *Lighting Research Technology*. 2013;45(4):464-75. <http://lrt.sagepub.com/content/45/4/464>. Accessed April 5, 2016.
17. Scigliano E. Seattle's new LED-lit streets Blinded by the lights. *Crosscut*. March 18, 2013. <http://crosscut.com/2013/03/streetlights-seattle-led/>. Accessed April 6, 2016.
18. Davis will spend \$350,000 to replace LED lights after neighbor complaints. CBS Local, Sacramento; October 21, 2014. <http://sacramento.suntimes.com/sac-news/7/138/6000/davis-will-spend-350000-to-replace-led-lights-after-neighbor-complaints>.
19. Chaban M. LED streetlights in Brooklyn are saving energy but exhausting residents. *NY Times*; March 23, 2015. [http://www.nytimes.com/2015/03/24/nyregion/new-led-streetlights-shine-too-brightly-for-some-in-brooklyn.html?\\_r=0](http://www.nytimes.com/2015/03/24/nyregion/new-led-streetlights-shine-too-brightly-for-some-in-brooklyn.html?_r=0). Accessed April 5, 2016.
20. Vos JJ. On the cause of disability glare and its dependence on glare angle, age and ocular pigmentation. *Clin Exp Optom*. 2003;86(6):363-70.
21. Stevens RG, Brainard GC, Blask DE, Lockley SW, Motta ME. Breast cancer and circadian disruption from electric lighting in the modern world. *CA Cancer J Clin*. 2014;64:207-18.
22. Evans JA, Davidson AJ. Health consequences of circadian disruption in humans and animal models. *Prog Mol Biol Transl Sci*. 2013;119:283-323.
23. Wright KP Jr, McHill AW, Birks BR, Griffin BR, Rusterholz T, Chinoy ED. Entrainment of the human circadian clock to the natural light-dark cycle. *Curr Biol*. 2013;23:1554-8.
24. Energy Savings Estimates of Light Emitting Diodes in Niche Lighting Applications. Building Technologies Program, Office of Energy Efficiency and Renewable Energy, U.S. Department of Energy. January 2011. [http://apps1.eere.energy.gov/buildings/publications/pdfs/ssl/nichefinalreport\\_january2011.pdf](http://apps1.eere.energy.gov/buildings/publications/pdfs/ssl/nichefinalreport_january2011.pdf) Accessed April 7, 2016.

25. Council on Science and Public Health Report 4. Light pollution. Adverse effects of nighttime lighting. American Medical Association, Annual Meeting, Chicago, IL. 2012.
  26. Cajochen C, Frey S, Anders D, et al. Evening exposure to a light-emitting diodes (LED)-backlit computer screen affects circadian physiology and cognitive performance. *J Appl Physiol*. 2011;110:1432-8.
  27. Chang AM, Aeschbach D, Duffy JF, Czeisler CA. Evening use of light-emitting eReaders negatively affects sleep, circadian timing, and next-morning alertness. *Proc Natl Acad Sci USA*. 2015;112:1232-7.
- 

CSAPH Rep. 2-A-16 -- page 8 of 8

28. Gooley JJ, Chamberlain K, Smith KA, et al. Exposure to room light before bedtime suppresses melatonin onset and shortens melatonin duration in humans. *J Clin Endocrinol Metab*. 2011;96:E463-72.
29. Koo YS, Song JY, Joo EY, et al. Outdoor artificial light at night, obesity, and sleep health: Cross-sectional analysis in the KoGES study. *Chronobiol Int*. 2016;33(3):301-14.
30. Lucas RJ, Peirson SN, Berson DM, et al. Measuring and using light in the melanopsin age. *Trends Neurosci*. 2014;37:1-9.
31. Falchi F, Cinzano P, Elvidge CD, Keith DM, Haim A. Limiting the impact of light pollution on human health, environment and stellar visibility. *J Environ Manage*. 2011;92:2714-22.
32. Ohayon M, Milesi C. Sleep deprivation/insomnia and exposure to street lights in the American general population. American Academy of Neurology Annual Meeting. April 15-21, 2016. Vancouver, BC.
33. Pawson SM, Bader MK. Led lighting increases the ecological impact of light pollution irrespective of color temperature. *Ecological Applications*. 2014;24:1561-68.
34. Gaston K, Davies T, Bennie J, Hopkins J. Reducing the ecological consequences of night-time light pollution: Options and developments. *J Appl Ecol*. 2012;49(6):1256-66.
35. Salmon M. Protecting sea turtles from artificial night lighting at Florida's oceanic beaches. In: Rich C, Longcore T (eds.). *Ecological Consequences of Artificial Night Lighting*. 2006:141-68. Island Press, Washington, DC.



36. Rusenko KW, Mann JL, Albury R, Moriarty JE, Carter HL. Is the wavelength of city glow getting shorter? Parks with no beachfront lights record adult aversion and hatchling disorientations in 2004. Kalb H, Rohde A, Gayheart K, Shanker, K, compilers. 2008. *Proceedings of the Twenty-fifth Annual Symposium on Sea Turtle Biology and Conservation*, NOAA Technical Memorandum NMFS-SEFSC-582, 204pp. <http://www.nmfs.noaa.gov/pr/pdfs/species/turtlesymposium2005.pdf>
37. Rusenko KW, Newman R, Mott C, et al. Using GIS to determine the effect of sky glow on nesting sea turtles over a ten year period. Jones TT, Wallace BP, compilers. 2012. *Proceedings of the Thirty-first Annual Symposium on Sea Turtle Biology and Conservation*. NOAA Technical Memorandum NOAA NMFS-SEFSC-631:32p.

Acknowledgement: The Council thanks George Brainard, PhD (Thomas Jefferson University); Richard Stevens, PhD (University Connecticut Health Center); and Mario Motta, MD (CSAPH, Tufts Medical School) for their contributions in preparing the initial draft of this report, and the commentary by Travis Longcore, PhD, on the ecological impact of nighttime electrical lighting.