

- PROTECTION OF UNDERGROUND FACILITIES**
- CONTRACTOR SHALL UNDERTAKE THE FOLLOWING STEPS PRIOR TO COMMENCING DRILLING OPERATIONS:
- CONTACT THE UTILITY LOCATION/NOTIFICATION SERVICE FOR THE CONSTRUCTION AREA.
 - POSITIVELY LOCATE AND STAKE ALL EXISTING UNDERGROUND FACILITIES. ANY FACILITIES LOCATED WITHIN 10 FEET OF THE DESIGNED DRILLED PATHS SHALL BE EXPOSED.
 - MODIFY DRILLING PRACTICES AND DOWNHOLE ASSEMBLIES AS NECESSARY TO PREVENT DAMAGE TO EXISTING FACILITIES.


- GENERAL NOTES**
- TOPOGRAPHIC SURVEY DATA PROVIDED BY BL COMPANIES, MERIDEN, CONNECTICUT.
 - NORTHINGS AND EASTINGS ARE IN U.S. SURVEY FEET REFERENCED TO CONNECTICUT STATE PLANE COORDINATES, NAD 83.
 - ELEVATIONS ARE IN FEET REFERENCED TO NAVD 88.
 - STATIONING IS IN FEET BY HORIZONTAL MEASUREMENT AND IS REFERENCED TO CONTROL ESTABLISHED FOR THE DRILLED SEGMENTS.
 - DRILLED PATH COORDINATES REFER TO CENTERLINE OF PIPE.

EXIT POINT @ 16°	P. T. 32° SAG BEND	WESTERN HDD ALIGNMENT	P. C. 32° SAG BEND	ENTRY POINT @ 16°
6+35.34, 10.51 N 616928.99, E 865632.64	5+60.72, -10.88	(ALL COORDINATES 25' RIGHT)	1+74.83, -10.88 RADIUS = 700'	0+98.36, 11.04 N 617306.54, E 866014.47
EXIT POINT @ 16°	P. T. 32° SAG BEND	EASTERN HDD ALIGNMENT	P. C. 32° SAG BEND	ENTRY POINT @ 16°
6+35.47, 10.55 N 616893.34, E 865667.70	5+60.72, -10.88	(ALL COORDINATES 25' LEFT)	1+74.83, -10.88 RADIUS = 700'	1+00.00, 10.57 N 617269.84, E 866048.46

PLAN
SCALE: 1" = 50'

- PILOT HOLE TOLERANCES**
- THE PILOT HOLES SHALL BE DRILLED TO THE TOLERANCES LISTED BELOW. HOWEVER, IN ALL CASES, RIGHT-OF-WAY RESTRICTIONS AND CONCERN FOR ADJACENT UTILITIES SHALL TAKE PRECEDENCE OVER THESE TOLERANCES.
- ELEVATION - PLUS 0 FEET, MINUS 10 FEET
 - ALIGNMENT - PLUS OR MINUS 5 FEET
 - ENTRY POINT - AT THE STAKED LOCATION
 - EXIT POINT - PLUS OR MINUS 5 FEET IN ALIGNMENT, PLUS OR MINUS 10 FEET IN LENGTH



- GEOTECHNICAL NOTES**
- GEOTECHNICAL DATA TAKEN FROM A MARCH 2006 GEOTECHNICAL EVALUATION REPORT PRODUCED BY GZA GEOTECHNICAL, INC., NORWOOD, MASSACHUSETTS. REFER TO THIS REPORT FOR MORE DETAILED SUBSURFACE INFORMATION.
 - THE LETTER "N" TO THE LEFT OF A SPLIT SPOON SAMPLE INDICATES THAT NO GRAVEL WAS OBSERVED IN THE SAMPLE. THE LETTERS "NT" INDICATE THAT GRAVEL WAS OBSERVED BUT NO GRADATION TESTS WERE PERFORMED.
 - THE GEOTECHNICAL DATA IS ONLY DESCRIPTIVE OF THE LOCATIONS ACTUALLY SAMPLED. EXTENSION OF THIS DATA OUTSIDE OF THE ORIGINAL BORINGS MAY BE DONE TO CHARACTERIZE THE SOIL CONDITIONS, HOWEVER, COMPANY DOES NOT GUARANTEE THESE CHARACTERIZATIONS TO BE ACCURATE. CONTRACTOR MUST USE HIS OWN EXPERIENCE AND JUDGEMENT IN INTERPRETING THIS DATA.




NOTE: BURIED UTILITIES ARE NOT SHOWN IN PROFILE. LOCATIONS TO BE CONFIRMED PRIOR TO COMMENCING HDD OPERATIONS.

ADDITIONAL GEOTECHNICAL NOTES

- DUE TO THE USE OF A 3-INCH SPLIT SPOON SAMPLER, PENETRATION RESISTANCE VALUES ASSOCIATED WITH BORINGS AC-2 & AC-4 MAY NOT CORRELATE WITH STANDARD PENETRATION TEST "N-VALUES" AS DEFINED BY ASTM D-1586.
- SUBSURFACE INFORMATION SHOWN ON THIS DRAWING HAS BEEN SIMPLIFIED FOR PRESENTATION PURPOSES. REFER TO THE PROJECT GEOTECHNICAL REPORT FOR MORE DETAILED INFORMATION.




- GENERAL LEGEND**
- DRILLED PATH ENTRY/EXIT POINT
- GEOTECHNICAL LEGEND**
- ⊕ BORING LOCATION
 - 2" O.D. SPLIT SPOON SAMPLE
 - 53.23 PENETRATION RESISTANCE IN BLOWS PER FOOT FOR A 140 POUND HAMMER FALLING 30 INCHES
 - PERCENTAGE OF GRAVEL BY WEIGHT FOR SAMPLES CONTAINING GRAVEL
 - 3" O.D. SPLIT SPOON SAMPLE
 - 53.23 PENETRATION RESISTANCE IN BLOWS PER FOOT FOR A 140 POUND HAMMER FALLING 30 INCHES
 - PERCENTAGE OF GRAVEL BY WEIGHT FOR SAMPLES CONTAINING GRAVEL
 - CORE BARREL SAMPLE
 - UCS 6,250 UNCONFINED COMPRESSIVE STRENGTH (PST)
 - 53.16 MOHS HARDNESS
 - ROCK QUALITY DESIGNATION (PERCENT)



PROFILE
SCALE: 1" = 50' HORIZONTAL
1" = 10' VERTICAL

COPYRIGHT © 2005 BURNS & MCDONNELL ENGINEERING COMPANY, INC.

<p>John D. Hair, P.E. Consulting Engineer</p>				<p>NORTHEAST UTILITIES SERVICE CO.</p>			
				<p>FOR THE CONNECTICUT LIGHT & POWER COMPANY</p>			
<p>date 01-04-07</p>				<p>TITLE MIDDLETOWN-NORWALK 345KV TRANSMISSION PROJECT</p>			
<p>designed JDH&A (RCR/JSP)</p>				<p>PLAN AND PROFILE CROSSING OF ASH CREEK BY HORIZONTAL DIRECTIONAL DRILLING TOWN OF FAIRFIELD & CITY OF BRIDGEPORT, CONNECTICUT</p>			
<p>checked JDH&A (DLB)</p>				<p>BY CHK APP DATE DATE DATE</p>			
<p>no. date revisions by chk</p>				<p>SCALE AS NOTED DWG. NO. 01224-16404 PG 001</p>			



SEE DRAWING NUMBER 24214-739
OF UNITED ILLUMINATING COMPANY
MIDDLETOWN-NORWALK PROJECT
DOUBLE CIRCUIT 345kV XLPE
UNDERGROUND TRANSMISSION LINE


VAULTS TO BE LOCATED AND OWNED
BY UNITED ILLUMINATING COMPANY

ISSUED UNDER UNDERGROUND CABLE
CROSSINGS OF WATERCOURSES AND
RAILROADS DEVELOPMENT AND
MANAGEMENT PLAN

SEE HORIZONTAL
DIRECTIONAL DRILL CROSSING
DWG. NO. 01223-16401 PG 001
FOR LAYOUT AND DETAILS
ISSUED UNDER UNDERGROUND
CABLE CROSSINGS OF
WATERCOURSES AND
RAILROADS DEVELOPMENT
AND MANAGEMENT PLAN



MATCHLINE SEE DWG NO.
01223-10001 PG 002

SEE DRAWING NUMBER 24214-739
OF UNITED ILLUMINATING COMPANY
MIDDLETOWN-NORWALK PROJECT
DOUBLE CIRCUIT 345kV XLPE
UNDERGROUND TRANSMISSION LINE



SEE HORIZONTAL
DIRECTIONAL DRILL CROSSING
DWG. NO. 01223-16401 PG 001
FOR LAYOUT AND DETAILS
ISSUED UNDER UNDERGROUND
CABLE CROSSINGS OF
WATERCOURSES AND
RAILROADS DEVELOPMENT
AND MANAGEMENT PLAN

ISSUED UNDER UNDERGROUND CABLE
CROSSINGS OF WATERCOURSES AND
RAILROADS DEVELOPMENT AND
MANAGEMENT PLAN



FOR REFERENCE ONLY
NOT FOR CONSTRUCTION

DOCKET No. 272

no.	date	revisions	by	chk
4	4/5/07	ISSUED CSC REVISED		CTC
3	2/26/07	ISSUED DOT/ MUNICIPALITY REVIEW		CTC
2	9/4/06	ISSUED CSC		CTC
1	6/1/06	ISSUED 60% PRELIMINARY		CTC



date 10/11/05
designed C. COURTRIGHT
detailed L. ROWSE
checked S. NEWLAND


MF	NO.	DATE	REVISIONS	BY	CHK	APP	APP

NORTHEAST UTILITIES SERVICE CO.

FOR THE CONNECTICUT LIGHT & POWER COMPANY
TITLE MIDDLETOWN-NORWALK 345kV TRANSMISSION PROJECT
TOWN OF STRATFORD
PLAN AND PROFILE Sta. 1000+00 to 1003+00


BY	SEN-BMCD	CHKD	APP	APP
DATE	10-11-05	DATE	DATE	DATE
SCALE	AS NOTED	DWG. NO.	01223-10001 PG 001	

COPYRIGHT © 2007 BURNS & MCDONNELL ENGINEERING COMPANY, INC.






SEE HORIZONTAL DIRECTIONAL DRILL CROSSING DWG. NO. 01223-16401 PG 001 FOR LAYOUT AND DETAILS ISSUED UNDER UNDERGROUND CABLE CROSSINGS OF WATERCOURSES AND RAILROADS DEVELOPMENT AND MANAGEMENT PLAN

MATCHLINE SEE DWG. NO. 01223-10001 PG 003



SEE HORIZONTAL DIRECTIONAL DRILL CROSSING DWG. NO. 01223-16401 PG 001 FOR LAYOUT AND DETAILS ISSUED UNDER UNDERGROUND CABLE CROSSINGS OF WATERCOURSES AND RAILROADS DEVELOPMENT AND MANAGEMENT PLAN



FOR REFERENCE ONLY
NOT FOR CONSTRUCTION

DOCKET No. 272








no.	date	revisions	by	chk
4	4/5/07	ISSUED CSC REVISED		
3	2/26/07	ISSUED DOT/ MUNICIPALITY REVIEW	CTC	
2	9/4/06	ISSUED CSC	CTC	
1	6/1/06	ISSUED 60% PRELIMINARY	CTC	

date 10/11/05
designed C. COURTRIGHT
detailed L. ROWSE
checked S. NEWLAND

MF	NO.	DATE	REVISIONS	BY	CHK	APP	APP

NORTHEAST UTILITIES SERVICE CO.			
FOR THE CONNECTICUT LIGHT & POWER COMPANY			
TITLE MIDDLETOWN-NORWALK 345KV TRANSMISSION PROJECT			
TOWN OF STRATFORD/CITY OF MILFORD PLAN AND PROFILE Sta. 1002+00 to 1010+50			
BY SEN-BMCD	CHKD	APP	APP
DATE 10-11-05	DATE	DATE	DATE
SCALE AS NOTED		DWG. NO. 01223-10001 PG 002	

COPYRIGHT © 2007 BURNS & MCDONNELL ENGINEERING COMPANY, INC.



FOR REFERENCE ONLY
NOT FOR CONSTRUCTION

DOCKET No. 272

no.	date	revisions	by	chk
4	4/5/07	ISSUED CSC REVISED		CTC
3	2/26/07	ISSUED DOT/ MUNICIPALITY REVIEW		CTC
2	9/4/06	ISSUED CSC		CTC
1	6/1/06	ISSUED 60% PRELIMINARY		CTC



date 10/11/05
designed C. COURTRIGHT
detailed L. ROWSE
checked S. NEWLAND

MF NO.	DATE	REVISIONS	BY	CHK	APP	APP


NORTHEAST UTILITIES SERVICE CO.

FOR THE CONNECTICUT LIGHT & POWER COMPANY

TITLE MIDDLETOWN-NORWALK 345KV TRANSMISSION PROJECT

CITY OF MILFORD
PLAN AND PROFILE Sta. 1010+00 to 1017+25

BY	SEN-BMCD	CHKD	APP	APP
DATE	10-11-05	DATE	DATE	DATE
SCALE	AS NOTED	D	DWG. NO.	01223-10001 PG 003



- PROTECTION OF UNDERGROUND FACILITIES**
- CONTRACTOR SHALL UNDERTAKE THE FOLLOWING STEPS PRIOR TO COMMENCING DRILLING OPERATIONS:
- CONTACT THE UTILITY LOCATION/NOTIFICATION SERVICE FOR THE CONSTRUCTION AREA.
 - POSITIVELY LOCATE AND STAKE ALL EXISTING UNDERGROUND FACILITIES. ANY FACILITIES LOCATED WITHIN 10 FEET OF THE DESIGNED DRILLED PATH SHALL BE EXPOSED.
 - MODIFY DRILLING PRACTICES AND DOWNHOLE ASSEMBLIES AS NECESSARY TO PREVENT DAMAGE TO EXISTING FACILITIES.

- GENERAL NOTES**
- TOPOGRAPHIC SURVEY DATA PROVIDED BY BL COMPANIES, MERIDEN, CONNECTICUT.
 - NORTHINGS AND EASTINGS ARE IN U.S. SURVEY FEET REFERENCED TO CONNECTICUT STATE PLANE COORDINATES, NAD 83.
 - ELEVATIONS ARE IN FEET REFERENCED TO NAVD 88.
 - STATIONING IS IN FEET BY HORIZONTAL MEASUREMENT AND IS REFERENCED TO CONTROL ESTABLISHED FOR THE DRILLED SEGMENTS.
 - DRILLED PATH COORDINATES REFER TO CENTERLINE OF PIPE.

PLAN

SCALE: 1" = 100'

ENTRY POINT @ 16' 11+00.00, 12.48
N 635168.24, E 900351.55
N 635149.52, E 900358.58


P.C. 19° SAG BEND 12+92.24, -42.65
RADIUS = 800'

P.T. 19° SAG BEND 15+54.62, -72.54

P.C. 7° SAG BEND 22+13.74, -38.00
RADIUS = 800'



P.T. 7° SAG BEND 23+10.79, -26.94

EXIT POINT @ 10' 25+00.00, 6.42
N 635659.76, E 901662.44
N 635641.03, E 901669.46



- PILOT HOLE TOLERANCES**
- THE PILOT HOLES SHALL BE DRILLED TO THE TOLERANCES LISTED BELOW. HOWEVER, IN ALL CASES, RIGHT-OF-WAY RESTRICTIONS AND CONCERN FOR ADJACENT UTILITIES SHALL TAKE PRECEDENCE OVER THESE TOLERANCES.
- ELEVATION - PLUS 0 FEET, MINUS 10 FEET
 - ALIGNMENT - PLUS OR MINUS 5 FEET BUT NO CLOSER THAN 15 FEET BETWEEN THE DRILLED PATHS
 - ENTRY POINT - AT THE STAKED LOCATION
 - EXIT POINT - PLUS OR MINUS 5 FEET IN ALIGNMENT, PLUS OR MINUS 10 FEET IN LENGTH

- GEOTECHNICAL NOTES**
- GEOTECHNICAL DATA TAKEN FROM A MARCH 2006 GEOTECHNICAL EVALUATION REPORT PRODUCED BY GEA GEOTECHNICAL, INC., NORWOOD, MASSACHUSETTS AND BORING LOGS INCLUDED IN APPENDIX 3 OF AN APRIL 2004 GEOPHYSICAL INVESTIGATION PRODUCED BY NDT CORPORATION, WORCESTER, MASSACHUSETTS. REFER TO THESE REPORTS FOR MORE DETAILED SUBSURFACE INFORMATION.
 - THE LETTER "N" TO THE LEFT OF A SPLIT SPOON SAMPLE INDICATES THAT NO GRAVEL WAS OBSERVED IN THE SAMPLE. THE LETTERS "NT" INDICATE THAT GRAVEL WAS OBSERVED BUT NO GRADATION TESTS WERE PERFORMED.
 - THE GEOTECHNICAL DATA IS ONLY DESCRIPTIVE OF THE LOCATIONS ACTUALLY SAMPLED. EXTENSION OF THIS DATA OUTSIDE OF THE ORIGINAL BORINGS MAY BE DONE TO CHARACTERIZE THE SOIL CONDITIONS, HOWEVER, COMPANY DOES NOT GUARANTEE THESE CHARACTERIZATIONS TO BE ACCURATE. CONTRACTOR MUST USE HIS OWN EXPERIENCE AND JUDGEMENT IN INTERPRETING THIS DATA.



ADDITIONAL GEOTECHNICAL NOTES


- DUE TO THE USE OF A 3-INCH SPLIT SPOON SAMPLER, PENETRATION RESISTANCE VALUES ASSOCIATED WITH BORINGS HR-1 AND HR-2 MAY NOT CORRELATE WITH STANDARD PENETRATION TEST "N-VALUES" AS DEFINED BY ASTM D-1586.
- DATA FROM BORINGS TTB-1, TTB-3, AND TTB-4 IS NOT SHOWN IN THE PROFILE VIEW DUE TO SPACE LIMITATIONS. REFER TO THE REFERENCED REPORTS FOR THE RESULTS OF THESE BORINGS.

GENERAL LEGEND

● DRILLED PATH ENTRY/EXIT POINT

GEOTECHNICAL LEGEND

- ⊙ BORING LOCATION
- 2" O.D. SPLIT SPOON SAMPLE
PENETRATION RESISTANCE IN BLOWS PER FOOT FOR A 140 POUND HAMMER FALLING 30 INCHES
PERCENTAGE OF GRAVEL BY WEIGHT FOR SAMPLES CONTAINING GRAVEL
- 3" O.D. SPLIT SPOON SAMPLE
PENETRATION RESISTANCE IN BLOWS PER FOOT FOR A 140 POUND HAMMER FALLING 30 INCHES
PERCENTAGE OF GRAVEL BY WEIGHT FOR SAMPLES CONTAINING GRAVEL
- CORE BARREL SAMPLE
UCS 6,250 UNCONFINED COMPRESSIVE STRENGTH (PST)
MHHS 6 MHHS HARDNESS
ROCK QUALITY DESIGNATION (PERCENT)



ISSUED FOR CONSTRUCTION

John D. Hair, P.E.
Consulting Engineer

date 09-01-06 detailed
designed JDH&A (JSP/DLB) checked JDH&A (JSP)






no.	date	revisions	by	chk
1	01/17/07	Modify rig side temporary workspace and add notes regarding access to boat ramps	DLB	JSP

NORTHEAST UTILITIES SERVICE CO.

FOR THE CONNECTICUT LIGHT & POWER COMPANY
TITLE MIDDLETOWN-NORWALK 345KV TRANSMISSION PROJECT
PLAN AND PROFILE
CROSSING OF THE HOUSATONIC RIVER
BY HORIZONTAL DIRECTIONAL DRILLING
MILFORD, CONNECTICUT

BY	CHKD	APP	APP
DATE	DATE	DATE	DATE
SCALE AS NOTED	D	DWG. NO.	01223-16401 PG 001

NOTE:
 1. SILT FENCE ON DOWNSLOPE SIDE OF CONSTRUCTION AREA, INCLUDING SPOIL PILES. WHEN AREAS ARE CURRENTLY PAVED USE CONNDOT APPROVED SEDIMENT CONTROL MEASURES.



**FOR REFERENCE ONLY
 NOT FOR CONSTRUCTION**

DOCKET No. 272

no.	date	revisions	by	chk
4	4/5/07	ISSUED CSC REVISED		
3	2/26/07	ISSUED DOT/ MUNICIPALITY REVIEW	CTC	
2	9/4/06	ISSUED CSC	CTC	
1	6/1/06	ISSUED 60% PRELIMINARY	CTC	




date 10/11/05
 designed C. COURTRIGHT
 detailed L. ROWSE
 checked S. NEWLAND

MF NO.	DATE	REVISIONS	BY	CHK	APP	APP

NORTHEAST UTILITIES SERVICE CO.
 FOR THE CONNECTICUT LIGHT & POWER COMPANY
 TITLE MIDDLETOWN-NORWALK 345KV TRANSMISSION PROJECT
 CITY OF MILFORD
 PLAN AND PROFILE Sta. 1017+25 to 1023+50

BY SEN-BMCD	CHKD	APP	APP
DATE 10-11-05	DATE	DATE	DATE
SCALE AS NOTED	D	DWG. NO. 01223-10001 PG 004	

COPYRIGHT © 2007 BURNS & MCDONNELL ENGINEERING COMPANY, INC.



PROTECTION OF UNDERGROUND FACILITIES

CONTRACTOR SHALL UNDERTAKE THE FOLLOWING STEPS PRIOR TO COMMENCING BORING OPERATIONS:

1. CONTACT THE UTILITY LOCATION/NOTIFICATION SERVICE FOR THE CONSTRUCTION AREA.
2. POSITIVELY LOCATE AND STAKE ALL EXISTING UNDERGROUND FACILITIES WITHIN 25 FEET OF THE BORE ALIGNMENT. LOCATIONS AND DEPTHS SHALL BE VERIFIED BY POT-Holing OR EXCAVATION.
3. UNDERGROUND FACILITIES LOCATED WITHIN 5 FEET OF THE DESIGNED BORE PATH SHALL BE EXPOSED.
4. MODIFY BORING PRACTICES AS NECESSARY TO PREVENT DAMAGE TO EXISTING FACILITIES.

GENERAL NOTES

1. TOPOGRAPHIC SURVEY DATA PROVIDED BY BL COMPANIES, MERIDEN, CONNECTICUT.
2. NORTHINGS AND EASTINGS ARE IN U.S. SURVEY FEET REFERENCED TO CONNECTICUT STATE PLANE COORDINATES, NAD 83.
3. ELEVATIONS ARE IN FEET REFERENCED TO NAVD 88.
4. STATIONING IS IN FEET BY HORIZONTAL MEASUREMENT.
5. HORIZONTAL BORE ENTRY AND EXIT COORDINATES REFER TO TOP OF PIPE.

LINE AND GRADE TOLERANCES

THE CASING SHALL BE INSTALLED TO THE LINE AND GRADE INDICATED ON THIS DRAWING WITHIN THE FOLLOWING TOLERANCES:

- ALIGNMENT. PLUS OR MINUS 3 FEET.
- ELEVATION. PLUS 0 FEET, MINUS 3 FEET.

HOWEVER, IN ALL CASES RIGHT-OF-WAY RESTRICTIONS AND CONCERN FOR ADJACENT FACILITIES SHALL TAKE PRECEDENCE OVER THE TOLERANCES LISTED.


GEOTECHNICAL NOTES

1. GEOTECHNICAL DATA TAKEN FROM DRAFT BORING LOGS PRODUCED BY GZA, GEOTECHNICAL, INC., NORWOOD, MASSACHUSETTS. REFER TO THE PROJECT GEOTECHNICAL REPORT FOR MORE DETAILED SUBSURFACE INFORMATION.
2. THE LETTER "N" TO THE LEFT OF A SPLIT SPOON SAMPLE INDICATES THAT NO GRAVEL WAS OBSERVED IN THE SAMPLE. THE LETTERS "NT" INDICATE THAT GRAVEL WAS OBSERVED BUT NO GRADATION TESTS WERE PERFORMED.
3. THE GEOTECHNICAL DATA IS ONLY DESCRIPTIVE OF THE LOCATIONS ACTUALLY SAMPLED. EXTENSION OF THIS DATA OUTSIDE OF THE ORIGINAL BORINGS MAY BE DONE TO CHARACTERIZE THE SOIL CONDITIONS. HOWEVER, COMPANY DOES NOT GUARANTEE THESE CHARACTERIZATIONS TO BE ACCURATE. CONTRACTOR MUST USE HIS OWN EXPERIENCE AND JUDGEMENT IN INTERPRETING THIS DATA.

GENERAL LEGEND

- HORIZONTAL BORE ENDPOINT
- ⊙ BORING LOCATION
- SPLIT SPOON SAMPLE
- 53.23 — PENETRATION RESISTANCE IN BLOWS PER FOOT FOR A 140 POUND HAMMER FALLING 30 INCHES
- PERCENTAGE OF GRAVEL BY WEIGHT FOR SAMPLES CONTAINING GRAVEL
- CORE BARREL SAMPLE
- UCS 6,250 — UNCONFINED COMPRESSIVE STRENGTH (PSI)
- 53.6 — MOHS HARDNESS
- ROCK QUALITY DESIGNATION (PERCENT)


PLAN
SCALE: 1" = 20'



ADDITIONAL GEOTECHNICAL NOTES

1. DUE TO THE USE OF A 3-INCH SPLIT SPOON SAMPLER, PENETRATION RESISTANCE VALUES ASSOCIATED WITH BORING MN-1 MAY NOT CORRELATE WITH STANDARD PENETRATION TEST "N-VALUES" AS DEFINED BY ASTM D-1586.
2. SUBSURFACE INFORMATION SHOWN ON THIS DRAWING HAS BEEN SIMPLIFIED FOR PRESENTATION PURPOSES. REFER TO THE PROJECT GEOTECHNICAL REPORT FOR MORE DETAILED INFORMATION.

PROFILE
SCALE: 1" = 20' HORIZONTAL
1" = 10' VERTICAL




**60% COMPLETION
PRELIMINARY**

John D. Hair, P.E.
Consulting Engineer



date 03-23-06
designed JDH&A (JSP)




detailed
checked 03-23-06

no.	date	revisions	by	chk

MF NO.	DATE	REVISIONS	BY	CHK	APP	APP
1	1/08/07	REVISE PIPE SPECIFICATION	DLB	JSP	JSP	

NORTHEAST UTILITIES SERVICE CO.			
FOR THE CONNECTICUT LIGHT & POWER COMPANY			
TITLE MIDDLETOWN-NORWALK 345KV TRANSMISSION PROJECT			
PLAN AND PROFILE CROSSING OF THE METRO NORTH RAILROAD BY HORIZONTAL BORING MILFORD, CONNECTICUT			
BY	CHKD	APP	APP
DATE	DATE	DATE	DATE
SCALE AS NOTED	DWG. NO. 01223-16402 PG 001		



PLAN

SCALE: 1" = 10'

PLAN NOTES

- TRACK ELEVATION SHOWN IS APPROXIMATE. CONTRACTOR SHALL VERIFY ELEVATION OF RAILROAD TRACK AT POINT OF MIN. VERTICAL CLEARANCE PRIOR TO START OF CONSTRUCTION. THE CONTRACTOR SHALL NOTIFY BL COMPANIES SHOULD THE ACTUAL TRACK ELEVATION BE HIGHER THAN SHOWN. BRIDGE ELEVATIONS SHALL BE ADJUSTED ACCORDINGLY TO MEET REQUIRED MIN. VERTICAL CLEARANCE.
- 4" OF CRUSHED STONE FOR SLOPE PROTECTION SHALL BE PROVIDED WITHIN THE LIMITS DEFINED IN THE 8' HIGH PROTECTIVE FENCE DETAILS. SEE DWG. No. 01224-16302 PG 013
- CRUSHED STONE FOR SLOPE PROTECTION SHALL BE INCLUDED IN THE PAY ITEM "8' CHAIN LINK FENCE".

DESIGN LOADS

- GRAVITY LOADS**
- A. MISCELLANEOUS DEAD LOAD = 126.5 PLF/BEAM
 - B. UTILITY DEAD LOAD = 92 PLF/BEAM
 - C. LIVE LOAD = 30 PSF
 - D. ROOF SNOW LOAD = 22.5 PSF
- LATERAL LOADS**
- A. BASIC WIND VELOCITY = 100 MPH
 - B. HORIZONTAL WIND PRESSURE = 50 PSF
 - C. VERTICAL WIND PRESSURE = 20 PSF
 - D. FOR ROOF & CLADDING - WIND PRESSURE ACCORDING SEI/ASCE STANDARD 7-02
- SEISMIC:**
- A. SEISMIC PERFORMANCE ZONE - 2 (PER AASHTO 3.10.4)

TABLE OF QUANTITIES		
ITEM	UNIT	QUANTITY
STRUCTURE EXCAVATION - EARTH (COMPLETE)	CY	30
STRUCTURE EXCAVATION - ROCK (COMPLETE)	CY	190
PERVIOUS STRUCTURE BACKFILL	CY	240
STEEL-LAMINATED ELASTOMERIC BEARINGS	EA	2
CLASS "A" CONCRETE	CY	260
DEFORMED STEEL BARS	LB	33800
ARCHITECTURAL CLADDING (SITE K)	SY	250
STRUCTURAL STEEL (GALVANIZED) (SITE K)	LB	57000
FIBERGLASS STRUCTURAL SHAPES (SITE K)	LB	5000
DAMPPOOFING	SY	190
8' CHAIN LINK FENCE	LF	230
5' CHAIN LINK FENCE (STRUCTURE)	LF	42
HEAT SHIELD	L.S.	1

GENERAL NOTES

SPECIFICATIONS: CONNECTICUT DEPARTMENT OF TRANSPORTATION FORM 816 (2004), SUPPLEMENTAL SPECIFICATIONS DATED JULY, 2005, AND SPECIAL PROVISIONS.

DESIGN SPECIFICATIONS: AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS, 3RD EDITION (2004); SEI/ASCE STANDARD 7-02, MINIMUM DESIGN LOADS FOR BUILDINGS AND OTHER STRUCTURES; AS SUPPLEMENTED BY THE CONNECTICUT DEPARTMENT OF TRANSPORTATION BRIDGE DESIGN MANUAL, 2003 EDITION, UP TO AND INCLUDING 2005 REVISIONS.

ALLOWABLE DESIGN STRESSES:

CLASS "A" CONCRETE	BASED ON	f'c = 3000 PSI
REINFORCEMENT	BASED ON	fy = 60,000 PSI
STRUCTURAL STEEL	BASED ON	Fy = 50,000 PSI
FIBERGLASS STRUCTURAL SHAPE	BASED ON	Fu = 33,000 PSI

STRUCTURAL STEEL: SEE STRUCTURAL STEEL NOTES FOR DESIGNATIONS AND REQUIREMENTS.

FOUNDATION PRESSURES: THE VARIOUS STRENGTH LIMITS NOTED ON THE SUBSTRUCTURE PLAN SHEETS REFER TO THE STRENGTH LIMITS AS SPECIFIED IN THE AASHTO LRFD BRIDGE DESIGN SPECIFICATION.

DIMENSIONS & ELEVATIONS: WHEN DIMENSIONS AND ELEVATIONS ARE GIVEN TO LESS THAN THREE DECIMAL PLACES, THE OMITTED DIGITS SHALL BE CONSIDERED TO BE ZEROS.

ALL ELEVATIONS ARE GIVEN IN DECIMAL FEET.

CONCRETE NOTES

CLASS "A" CONCRETE: CLASS "A" CONCRETE SHALL BE USED FOR THE ENTIRE SUBSTRUCTURES.

EXPOSED EDGES: EXPOSED EDGES OF CONCRETE SHALL BE BEVELED 1"x1", UNLESS OTHERWISE NOTED.


CONCRETE COVER: ALL REINFORCEMENT SHALL HAVE TWO INCHES CLEAR COVER, UNLESS OTHERWISE NOTED.

REINFORCEMENT: ALL REINFORCEMENT SHALL BE ASTM A615, GRADE 60.

CONSTRUCTION JOINTS: CONSTRUCTION JOINTS, OTHER THAN THOSE SHOWN ON THE PLANS, WILL NOT BE PERMITTED WITHOUT THE PRIOR APPROVAL OF THE ENGINEER.

BORING LEGEND

⊙ LOCATION OF BORING PERFORMED BY GZA GEO ENVIRONMENTAL, INC.




ELEVATION

SCALE: 1" = 10'

WORKING POINT COORDINATES		
WP	NORTHING	EASTING
WP-1	636431.4255	902321.1488
WP-2	636507.1003	902333.1752

TRANSPORTATION DIMENSIONS AND MASS DATA				
MEMBER	SHIPPING LENGTH	SHIPPING HEIGHT	SHIPPING WIDTH	SHIPPING WEIGHT
S1-S3	78' - 2"	4' - 3"	1' - 10"	18 000 LB.



TYPICAL SECTION

SCALE: 1/2" = 1'-0"

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATION BY THE BL COMPANIES AND IS IN NO WAY WARRANTED TO INDICATE THE TRUE CONDITIONS OF ACTUAL QUANTITIES OR DISTRIBUTION OF QUANTITIES OF WORK WHICH WILL BE REQUIRED.

NOTICE TO BRIDGE INSPECTORS

IT IS RECOMMENDED THAT AREMA, NESC, CONDOT AND MNR'S BRIDGE SAFETY PROCEDURES BE FOLLOWED WHEN INSPECTING AND MAINTAINING THIS BRIDGE FOR, BUT NOT LIMITED TO, ALL APPROPRIATE COMPONENTS INDICATED IN THE GOVERNING MANUALS FOR BRIDGE INSPECTION. ATTENTION MUST BE GIVEN TO INSPECTING THE FOLLOWING SPECIAL COMPONENTS AND DETAILS. (THE LISTING OF COMPONENTS FOR SPECIFIC ATTENTION SHALL NOT BE CONSTRUED TO REDUCE THE IMPORTANCE OF INSPECTION OF ANY OTHER COMPONENT OF THE STRUCTURE.) THE FREQUENCY OF INSPECTION OF THIS STRUCTURE SHALL BE IN ACCORDANCE WITH THE GOVERNING MANUALS FOR BRIDGE INSPECTION, UNLESS OTHERWISE DIRECTED BY NORTHEAST UTILITIES.

COMPONENT OR DETAIL	STRUCTURE SHEET REFERENCE
PLATE GIRDERS	01223-16301 PG 007
BEARINGS	01223-16301 PG 010

CONCRETE DISTRIBUTION		
SUBSTRUCTURE	C.Y.	0
SUBSTRUCTURE	C.Y.	205
FOOTINGS	C.Y.	45
TOTAL	C.Y.	250

INSPECTION OF FIELD WELDS		
METHOD	UNIT	QUANTITY
ULTRASONIC	inch	0
MAGNETIC PARTICLE	feet	0

**FOR REFERENCE ONLY
NOT FOR CONSTRUCTION**

no.	date	revisions	by	chk
7	4/5/07	ISSUED CSC REVISED		D.Q. B.K.
6	9/04/06	ISSUED CSC		D.Q. B.K.
5	6/01/06	ISSUED 60% PRELIMINARY		D.Q. B.K.
4	5/10/06	ISSUED SECOND REVIEW		D.Q. B.K.
3	1/31/06	ADDENDUM No.2		D.Q. B.K.
2	1/23/06	ISSUED TO BMD & N.U. FOR REVIEW		D.Q. B.K.
1	1/19/06	ISSUED CIVIL R.F.P.		D.Q. B.K.



ARCHITECTURE
ENGINEERING
PLANNING
LANDSCAPE ARCHITECTURE
LAND SURVEYING
ENVIRONMENTAL SCIENCES


355 Research Parkway
Meriden, CT 06450
PH: 203.237.0077
www.blcompanies.com

date 01/10/06 detailed
designed M. BEAULIEU checked C. CHUANG
D. QUINIT / B. KUTA

NORTHEAST UTILITIES SERVICE CO.


FOR	THE CONNECTICUT LIGHT & POWER COMPANY			
TITLE	MIDDLETOWN-NORWALK 345KV TRANSMISSION PROJECT			
	METRO NORTH SPURLINE GENERAL PLAN			
BY	CHKD	APP	APP	
DATE	DATE	DATE	DATE	
SCALE AS NOTED	D		DWG. NO.	01223-16301 PG 001

01-48335.PLT
04/04/2007
01:23:16:001 PG 001.dgn
K:\Jobs\05\05C1314\Drawn\Structures\01223-16301 PG 001.dgn




TYPICAL HORIZONTAL DIRECTIONAL DRILL DUCT BANK

SECTION NTS Y




REDUCED-HEIGHT HORIZONTAL DIRECTIONAL DRILL DUCT BANK

SECTION NTS Z




TYPICAL GROUNDING DUCT BANK

SECTION NTS AA




TYPICAL THERMAL COUPLE WIRE DUCT BANK

SECTION NTS BB



TYPICAL GAS UTILITY CROSSING

SECTION NTS M



15" PHASE-SPACING DUCT BANK

SECTION NTS N

- GENERAL NOTES:
- STANDARD TRENCH WITH PERMANENT PAVEMENT RESTORATION IN STATE HIGHWAY SHOWN. PAVEMENT RESTORATION REQUIREMENTS SHALL VARY DEPENDENT ON SPECIFIC EXISTING PAVEMENT CROSS SECTIONS AND MATERIALS.
 - ALL FIBERGLASS CONDUITS SHALL BE OF BULLET-RESISTANT GRADE OR APPROVED OTHER.
 - REFERENCE RESTORATION DRAWINGS FOR PROPOSED PAVEMENT SECTIONS.

DOCKET No. 272

FOR REFERENCE ONLY
NOT FOR CONSTRUCTION



date 11/09/05
designed C. COURTRIGHT
detailed L. ROWSE
checked S. NEWLAND

no.	date	revisions	by	chk
4	4/5/07	ISSUED CSC REVISED		CTC
3	2/26/07	ISSUED DOT/ MUNICIPALITY REVIEW		CTC
2	9/4/06	ISSUED CSC		CTC
1	6/1/06	ISSUED 60% PRLIMINARY		CTC


MF	NO.	DATE	REVISIONS	BY	CHK	APP	APP

NORTHEAST UTILITIES SERVICE CO.

FOR THE CONNECTICUT LIGHT & POWER COMPANY


TITLE MIDDLETOWN-NORWALK 345KV TRANSMISSION PROJECT
UTILITY BRIDGE DUCT BANK DETAILS
AND UTILITY CROSSING DETAIL

BY	SEN-BMCD	CHKD	APP	APP
DATE	11-09-05	DATE	DATE	DATE
SCALE	AS NOTED	DWG. NO.	01224-46003 PG 002	




TYPICAL HORIZONTAL DIRECTIONAL DRILL DUCT BANK

SECTION NTS Y




REDUCED-HEIGHT HORIZONTAL DIRECTIONAL DRILL DUCT BANK

SECTION NTS Z




TYPICAL GROUNDING DUCT BANK

SECTION NTS AA




TYPICAL THERMAL COUPLE WIRE DUCT BANK

SECTION NTS BB



TYPICAL GAS UTILITY CROSSING

SECTION NTS M



15" PHASE-SPACING DUCT BANK

SECTION NTS N

GENERAL NOTES:

- STANDARD TRENCH WITH PERMANENT PAVEMENT RESTORATION IN STATE HIGHWAY SHOWN. PAVEMENT RESTORATION REQUIREMENTS SHALL VARY DEPENDENT ON SPECIFIC EXISTING PAVEMENT CROSS SECTIONS AND MATERIALS.
- ALL FIBERGLASS CONDUITS SHALL BE OF BULLET-RESISTANT GRADE OR APPROVED OTHER.
- REFERENCE RESTORATION DRAWINGS FOR PROPOSED PAVEMENT SECTIONS.

DOCKET No. 272

FOR REFERENCE ONLY
NOT FOR CONSTRUCTION



date 11/09/05 detailed L. ROWSE
designed C. COURTRIGHT checked S. NEWLAND


no.	date	revisions	by	chk
4	4/5/07	ISSUED CSC REVISED	CTC	
3	2/26/07	ISSUED DOT/ MUNICIPALITY REVIEW	CTC	
2	9/4/06	ISSUED CSC	CTC	
1	6/1/06	ISSUED 60% PRELIMINARY	CTC	

MF	NO.	DATE	REVISIONS	BY	CHK	APP	APP

NORTHEAST UTILITIES SERVICE CO.


FOR THE CONNECTICUT LIGHT & POWER COMPANY
TITLE MIDDLETOWN-NORWALK 345KV TRANSMISSION PROJECT
UTILITY BRIDGE DUCT BANK DETAILS
AND UTILITY CROSSING DETAILS

BY	SEN-BMCD	CHKD	APP	APP
DATE	11-09-05	DATE	DATE	DATE
SCALE	AS NOTED	DWG. NO.	01223-46003 PG 002	




TYPICAL UTILITY BRIDGE DUCT BANK WITH SPARE

SECTION O
NTS




UTILITY BRIDGE SINGLE CIRCUIT WITH COMMUNICATIONS DUCT BANK AND SPARE

SECTION P
NTS



UTILITY BRIDGE SINGLE CIRCUIT DUCT BANK WITH SPARE

SECTION Q
NTS



UTILITY BRIDGE REDUCED-HEIGHT DUCT BANK WITH SPARE

SECTION R
NTS

GENERAL NOTES:

- STANDARD TRENCH WITH PERMANENT PAVEMENT RESTORATION IN STATE HIGHWAY SHOWN. PAVEMENT RESTORATION REQUIREMENTS SHALL VARY DEPENDENT ON SPECIFIC EXISTING PAVEMENT CROSS SECTIONS AND MATERIALS.
- OMITTED
- REFERENCE RESTORATION DRAWINGS FOR PROPOSED PAVEMENT SECTIONS.

FOR REFERENCE ONLY
NOT FOR CONSTRUCTION

DOCKET No. 272



date 11/09/05
designed C. COURTRIGHT
detailed L. ROWSE
checked S. NEWLAND

no.	date	revisions	by	chk
4	4/5/07	ISSUED CSC REVISED	CTC	
3	2/26/07	ISSUED DOT/ MUNICIPALITY REVIEW	CTC	
2	9/4/06	ISSUED CSC	CTC	
1	6/1/06	ISSUED 60% PRLIMINARY	CTC	

NORTHEAST UTILITIES SERVICE CO.


FOR THE CONNECTICUT LIGHT & POWER COMPANY

TITLE MIDDLETOWN-NORWALK 345KV TRANSMISSION PROJECT

UTILITY BRIDGE DUCT BANK DETAILS


BY	SEN-BMCD	CHKD	APP	APP
DATE	11-09-05	DATE	DATE	DATE

SCALE AS NOTED
DWG. NO. 01224-46003 PG 003




TYPICAL UTILITY BRIDGE DUCT BANK WITH SPARE

SECTION O
NTS




UTILITY BRIDGE SINGLE CIRCUIT WITH COMMUNICATIONS DUCT BANK AND SPARE

SECTION P
NTS



UTILITY BRIDGE SINGLE CIRCUIT DUCT BANK WITH SPARE

SECTION Q
NTS



UTILITY BRIDGE REDUCED-HEIGHT DUCT BANK WITH SPARE

SECTION R
NTS

GENERAL NOTES:

- STANDARD TRENCH WITH PERMANENT PAVEMENT RESTORATION IN STATE HIGHWAY SHOWN. PAVEMENT RESTORATION REQUIREMENTS SHALL VARY DEPENDENT ON SPECIFIC EXISTING PAVEMENT CROSS SECTIONS AND MATERIALS.
- OMITTED
- REFERENCE RESTORATION DRAWINGS FOR PROPOSED PAVEMENT SECTIONS.

FOR REFERENCE ONLY
NOT FOR CONSTRUCTION

DOCKET No. 272

no.	date	revisions	by	chk
4	4/5/07	ISSUED CSC REVISED	CTC	
3	2/26/07	ISSUED DOT/ MUNICIPALITY REVIEW	CTC	
2	9/4/06	ISSUED CSC	CTC	
1	6/1/06	ISSUED 60% PRELIMINARY	CTC	



date 11/09/05
designed C. COURTRIGHT
detailed L. ROWSE
checked S. NEWLAND

MF	NO.	DATE	REVISIONS	BY	CHK	APP	APP


NORTHEAST UTILITIES SERVICE CO.

FOR THE CONNECTICUT LIGHT & POWER COMPANY


TITLE MIDDLETOWN-NORWALK 345KV TRANSMISSION PROJECT
UTILITY BRIDGE DUCT BANK DETAILS

BY SEN-BMCD	CHKD	APP	APP
DATE 11-09-05	DATE	DATE	DATE


SCALE AS NOTED
D
DWG. NO. 01223-46003 PG 003




TYPICAL JACK AND BORE DUCT BANK




JACK AND BORE SINGLE CIRCUIT WITH COMMUNICATIONS DUCT BANK




JACK AND BORE SINGLE CIRCUIT DUCT BANK



HORIZONTAL DIRECTIONAL DRILL SINGLE CIRCUIT WITH COMMUNICATIONS DUCT BANK



HORIZONTAL DIRECTIONAL DRILL SINGLE CIRCUIT DUCT BANK



HORIZONTAL DIRECTIONAL DRILL COMMUNICATIONS DUCT BANK

GENERAL NOTES:

- STANDARD TRENCH WITH PERMANENT PAVEMENT RESTORATION IN STATE HIGHWAY SHOWN. PAVEMENT RESTORATION REQUIREMENTS SHALL VARY DEPENDENT ON SPECIFIC EXISTING PAVEMENT CROSS SECTIONS AND MATERIALS.
- REFERENCE RESTORATION DRAWINGS FOR PROPOSED PAVEMENT SECTIONS.

DOCKET No. 272

FOR REFERENCE ONLY
NOT FOR CONSTRUCTION

no.	date	revisions	by	chk
4	4/5/07	ISSUED CSC REVISED	CTC	
3	2/26/07	ISSUED DOT/ MUNICIPALITY REVIEW	CTC	
2	9/4/06	ISSUED CSC	CTC	
1	6/1/06	ISSUED 60% PRLIMINARY	CTC	



date 11/09/05
designed C. COURTRIGHT
detailed L. ROWSE
checked S. NEWLAND


MF	NO.	DATE	REVISIONS	BY	CHK	APP	APP

NORTHEAST UTILITIES SERVICE CO.


FOR THE CONNECTICUT LIGHT & POWER COMPANY

TITLE MIDDLETOWN-NORWALK 345KV TRANSMISSION PROJECT
JACK AND BORE AND HORIZONTAL DIRECTIONAL DRILL DUCT BANK DETAILS


BY	SEN-BMCD	CHKD	APP	APP
DATE	11-09-05	DATE	DATE	DATE
SCALE	AS NOTED	DWG. NO.	01224-46003 PG 004	




TYPICAL JACK AND BORE DUCT BANK




JACK AND BORE SINGLE CIRCUIT WITH COMMUNICATIONS DUCT BANK




JACK AND BORE SINGLE CIRCUIT DUCT BANK



HORIZONTAL DIRECTIONAL DRILL SINGLE CIRCUIT WITH COMMUNICATIONS DUCT BANK



HORIZONTAL DIRECTIONAL DRILL SINGLE CIRCUIT DUCT BANK



HORIZONTAL DIRECTIONAL DRILL COMMUNICATIONS DUCT BANK

- GENERAL NOTES:
- STANDARD TRENCH WITH PERMANENT PAVEMENT RESTORATION IN STATE HIGHWAY SHOWN. PAVEMENT RESTORATION REQUIREMENTS SHALL VARY DEPENDENT ON SPECIFIC EXISTING PAVEMENT CROSS SECTIONS AND MATERIALS.
 - REFERENCE RESTORATION DRAWINGS FOR PROPOSED PAVEMENT SECTIONS.

DOCKET No. 272

FOR REFERENCE ONLY
NOT FOR CONSTRUCTION


no.	date	revisions	by	chk
4	4/5/07	ISSUED CSC REVISED	CTC	
3	2/26/07	ISSUED DOT/ MUNICIPALITY REVIEW	CTC	
2	9/4/06	ISSUED CSC	CTC	
1	6/1/06	ISSUED 60% PRELIMINARY	CTC	



date 11/09/05
designed C. COURTRIGHT
detailed L. ROWSE
checked S. NEWLAND


MF	NO.	DATE	REVISIONS	BY	CHK	APP	APP

NORTHEAST UTILITIES SERVICE CO.			
FOR THE CONNECTICUT LIGHT & POWER COMPANY			
TITLE MIDDLETOWN-NORWALK 345KV TRANSMISSION PROJECT JACK AND BORE AND HORIZONTAL DIRECTIONAL DRILL DUCT BANK DETAILS			
BY SEN-BMCD	CHKD	APP	APP
DATE 11-09-05	DATE	DATE	DATE
SCALE AS NOTED	D	DWG. NO. 01223-46003	PG 004




CONSTRUCTION JOINT DETAIL

DETAIL 1
NTS




TYPICAL WARNING SIGN

DETAIL 2
NTS



THERMOCOUPLE TEMPERATURE DATA LOGGER

DETAIL 4
NTS



TEMPERATURE MONITORING STATION INSTALLATION

DETAIL 5
NTS

TEMPERATURE PROBES (OMEGA TC-PVC-T-24-180) SHALL BE MOUNTED AT THE 2:00 O'CLOCK POSITION ON C-PHASE OF CIRCUIT 3280 AND 10:00 O'CLOCK POSITION ON A-PHASE OF CIRCUIT 3921

COPYRIGHT © 2007 BURNS & McDONNELL ENGINEERING COMPANY, INC.

DOCKET No. 272

FOR REFERENCE ONLY
NOT FOR CONSTRUCTION

no.	date	revisions	by	chk
4	4/5/07	ISSUED CSC REVISED	CTC	
3	2/26/07	ISSUED DOT/ MUNICIPALITY REVIEW	CTC	
2	9/4/06	ISSUED CSC	CTC	
1	6/1/06	ISSUED 60% PRELIMINARY	CTC	

Burns & McDonnell
SINCE 1898

date 11/09/05 detailed L. ROWSE
designed C. COURTRIGHT checked S. NEWLAND

MF	NO.	DATE	REVISIONS	BY	CHK	APP	APP

NORTHEAST UTILITIES SERVICE CO.

FOR THE CONNECTICUT LIGHT & POWER COMPANY


TITLE MIDDLETOWN-NORWALK 345KV TRANSMISSION PROJECT
CROSSING AND TEMPERATURE MONITORING DETAILS

BY SEN-BMCD	CHKD	APP	APP
DATE 11-09-05	DATE	DATE	DATE
SCALE AS NOTED	D	DWG. NO. 01224-46003	PG 005

CONDUIT SIZE	MIN. DISTANCE
2 & 8	3.000
4 & 4	2.500
4 & 8	3.000
8 & 8	3.000

CTR TO CTR DISTANCE BETWEEN CONDUITS	MIN. DISTANCE
2 & 8	8.817
4 & 4	7.152
4 & 8	9.834
8 & 8	12.000

- NOTES:
1. USE ONE BORE SPACER FOR EVERY 5 FEET OF DUCT BANK.
 2. THE CASING ID MUST BE SMOOTH AND FREE FROM RIDGES, PROJECTIONS AND SEAMS THAT MIGHT IMPEDE THE ROLLING OF WHEELS.
 3. A TROUGH OR FEEDER BRIDGE SHOULD BE CONSTRUCTED AT THE LEADING END OF THE CASING TO SUPPORT SECTIONS OF DUCT BANK AS THEY ARE ASSEMBLED AND PULLED INTO THE CASING.
 4. THIS BORE SPACER IS DESIGNED FOR A CASING THAT IS STRAIGHT AND TRUE.
 5. IT IS POSSIBLE THAT THE DUCT BANK WILL ROTATE (CORKSCREW) AS IT IS PULLED THRU THE CASING UNLESS AN "OFF CENTER WEIGHT TECHNIQUE," "STABILIZATION CABLES" OR "L" ANGLE & SLOT TECHNIQUE IS USED.
 6. THIS BORE SPACER WILL ACCOMMODATE THE "SINGLE-END," "FLUSH COUPLED EXTRACTABLE INJECTION PIPE" OR "STATIONARY SACRIFICIAL INJECTION PIPE" METHODS OF GROUT FILLING. IT IS ESSENTIAL THAT THE BORE SPACERS ARE HELD IN PLACE RELATIVE TO THE CONDUIT. REASON: AS THE GROUT IS PUMPED INTO THE CASING, THE COMPARTMENTS FORMED BETWEEN THE BORE SPACERS ARE MORE OR LESS FILLED SEQUENTIALLY, PLACING A TEMPORARY THRUST LOAD ON EACH BORE SPACER.
 7. THE DUCT BANK MUST BE HELD IN POSITION AT BOTH ENDS TO ACCOMMODATE POSSIBLE UNEVEN THRUST LOADS THAT MAY BE GENERATED DURING THE GROUTING OPERATION.
 8. WHEN FILLING THE AREA BETWEEN THE CONDUITS AND CASING WITH GROUT, TAKE CARE NOT TO EXCEED THE HYDRAULIC COLLAPSE PRESSURE OF THE CONDUITS.
 9. DEPENDING ON THE GROUT SPECIFIC GRAVITY AND GROUT FLOW, IT IS POSSIBLE THAT THE DUCT BANK WILL FLOAT TO THE TOP OF THE CASING.
 10. ACTUAL QUANTITY OF GROUT USED SHOULD BE MEASURED AND RECORDED.



FASTENERS TO SECURE THE TWO WALLS OF BORE SPACER TOGETHER. SEE PAGE TWO OF THIS DRAWING FOR DETAILS. (TYPICAL OF 18 PLACES)

CORNER IS BROKEN .312 X 22.5" ON ONE SIDE OF BORE SPACER TO AID IN THE WITHDRAWAL OF GROUT INJECTION PIPE.

4.653 DIA HOLE THAT CAN BE USED FOR A GROUT INJECTION PIPE OR AS A FLOW HOLE.

CONTOURED FLOW HOLES (6 REQUIRED PER HALF)

FACTORY INSTALLED 3" DIAMETER POLYOLEFIN WHEEL ASSEMBLY. WHEELS ARE RATED AT 300 LBS PER WHEEL. (4 REQUIRED)


MATERIAL: .750 ±.075 THICK HIGH DENSITY POLYETHYLENE (HDPE) SHEETS ARE STRESS RELIEVED. COLOR: NATURAL WHITE. TENSILE STRENGTH: 3700 PSI, ELONGATION: 550%

DOUBLE WALL, FULL COMPLEMENT BORE SPACER With 8 Ea. 8", 2 Ea. 4" & 2 Ea. 2" RTRC-XHW (Bullet-Resistant, Extra Heavy Wall Fiberglass) Conduits Per NEMA TC-2002 In A 60,000 OD X 2.130 Min. Wall HOBAS (Centrifugally Cast Fiberglass Reinforced Polymer Mortar) Casing. See At Left: Alan Armstrong, B. Muehlenbeck, Don McCoy

7-7-06

1st Designed For BURNS & MCDONNELL Kansas City, MO - CHRIS COURTRIGHT - Phone: 816-333-9400

UNDERGROUND DEVICES, INC. 90-4150 NORTHBRIDG, ILLINOIS 60062 - PHONE: (847) 205-9000 PAGE 1 OF 3



DOUBLE WALL, FULL COMPLEMENT BORE SPACER With 8 Ea. 8", 2 Ea. 4" & 2 Ea. 2" RTRC-XHW (Bullet-Resistant, Extra Heavy Wall Fiberglass) Conduits Per NEMA TC-2002 In A 60,000 OD X 2.130 Min. Wall HOBAS (Centrifugally Cast Fiberglass Reinforced Polymer Mortar) Casing. See At Left: Alan Armstrong, B. Muehlenbeck, Don McCoy


7-7-06

1st Designed For BURNS & MCDONNELL Kansas City, MO - CHRIS COURTRIGHT - Phone: 816-333-9400

UNDERGROUND DEVICES, INC. 90-4150 NORTHBRIDG, ILLINOIS 60062 - PHONE: (847) 205-9000 PAGE 2 OF 3

UNDERGROUND DEVICES CATALOG NUMBER: BS4150W4

ITEM NUMBER	QTY REQ'D	DESCRIPTION
1	18	3/8-16 HEX NUT (GRADE 2, CENTERLOCK LOCKING NUT, ZINC PLATED STEEL)
2	36	3/8 FLAT WASHER (438 ID X 1.000 OD X .078 THK, USS STANDARD, ZINC PLATED STEEL)
3	2	UDI 90-4150 BLANK BORE SPACER
4	18	UDI 90-803 SPACER BUSHING (TYPE 1 PVC DARK GRAY)
5	18	3/8-16 X 6" LG HEX HEAD CAP SCREW (GRADE 2, ZINC PLATED LOW CARBON STEEL)



CONDUIT AND HOLE SIZES			
CONDUIT OD	FULL HOLE DIAMETER	PARTIAL HOLE DIAMETER	
NOMINAL	ACTUAL	BANDED	NON-BANDED
2"	2.500	---	2.620
4"	4.500	---	4.653
8"	8.900	9.015	8.920

DOUBLE WALL, FULL COMPLEMENT BORE SPACER With 8 Ea. 8", 2 Ea. 4" & 2 Ea. 2" RTRC-XHW (Bullet-Resistant, Extra Heavy Wall Fiberglass) Conduits Per NEMA TC-2002 In A 60,000 OD X 2.130 Min. Wall HOBAS (Centrifugally Cast Fiberglass Reinforced Polymer Mortar) Casing. See At Left: Alan Armstrong, B. Muehlenbeck, Don McCoy

7-7-06


1st Designed For BURNS & MCDONNELL Kansas City, MO - CHRIS COURTRIGHT - Phone: 816-333-9400

UNDERGROUND DEVICES, INC. 90-4150 NORTHBRIDG, ILLINOIS 60062 - PHONE: (847) 205-9000 PAGE 2 OF 3

UNDERGROUND DEVICES CATALOG NUMBER: BS4150W4

DETAIL No.1

SCALE: 4X




DOUBLE WALL, FULL COMPLEMENT BORE SPACER With 8 Ea. 8", 2 Ea. 4" & 2 Ea. 2" RTRC-XHW (Bullet-Resistant, Extra Heavy Wall Fiberglass) Conduits Per NEMA TC-2002 In A 60,000 OD X 2.130 Min. Wall HOBAS (Centrifugally Cast Fiberglass Reinforced Polymer Mortar) Casing. See At Left: Alan Armstrong, B. Muehlenbeck, Don McCoy

7-7-06


1st Designed For BURNS & MCDONNELL Kansas City, MO - CHRIS COURTRIGHT - Phone: 816-333-9400

UNDERGROUND DEVICES, INC. 90-4150 NORTHBRIDG, ILLINOIS 60062 - PHONE: (847) 205-9000 PAGE 3 OF 3

UNDERGROUND DEVICES CATALOG NUMBER: BS4150W4



HORIZONTAL DIRECTIONAL DRILL SECTION A NTS



JACK AND BORE SECTION B NTS

- NOTES:
1. ALL CASING SHALL BE COMPLETELY FILLED WITH A THERMALLY ACCEPTABLE GROUT. GROUT MIX DESIGN SHALL MEET PROJECT SPECIFICATIONS.
 2. GROUT SAMPLES SHALL BE SUBMITTED TO THE TEST COMPANY (CONTACT TEST COMPANY FOR APPROPRIATE SIZE & METHOD OF TRANSPORTATION) IN ACCORDANCE WITH THE SPECIFICATIONS.
 3. CONTRACTOR SHALL FURNISH AND INSTALL CASING PIPE SPACER. SPACERS SHALL BE INSTALLED A MAXIMUM DISTANCE OF 5 FEET APART. SPACERS SHALL BE INSTALLED PER MANUFACTURER'S RECOMMENDATIONS.
 4. CONTRACTOR SHALL SUBMIT DETAILED DESIGN OF EACH BORED CROSSING FOR REVIEW, INCLUDING AS A MINIMUM WORK PLAN, EQUIPMENT AND MATERIALS TO BE USED, WORK AREAS, BORE PIT SIZES AND LOCATIONS.
 5. BENTONITE SLURRY SAMPLES SHALL BE SUBMITTED TO THE TEST COMPANY (CONTACT TEST COMPANY FOR APPROPRIATE SIZE & METHOD OF TRANSPORTATION) IN ACCORDANCE WITH THE SPECIFICATIONS.

COPYRIGHT © 2007 BURNS & MCDONNELL ENGINEERING COMPANY, INC.

4 4/5/07 ISSUED CSC REVISED CTC

3 2/26/07 ISSUED DOT/ MUNICIPALITY REVIEW CTC

2 9/4/06 ISSUED CSC CTC

1 6/1/06 ISSUED 60% PRELIMINARY CTC

no. date revisions by chk

date 6/15/06 detailed L. ROWSE

designed C. COURTRIGHT checked S. NEWLAND

NORTHEAST UTILITIES SERVICE CO.

FOR THE CONNECTICUT LIGHT & POWER COMPANY


TITLE MIDDLETOWN-NORWALK 345KV TRANSMISSION PROJECT

HORIZONTAL DIRECTIONAL DRILL AND JACK AND BORE SECTIONS

BY SEN-BMCD	CHKD	APP	APP
DATE 6/15/06	DATE	DATE	DATE
SCALE AS NOTED	D	DWG. NO. 01223-46003	PG 006


DOCKET No. 272

FOR REFERENCE ONLY
NOT FOR CONSTRUCTION



PERMANENT FLEXIBLE PAVEMENT REPAIR (VAULT CONSTRUCTION)
DETAIL 1
 NTS

* SEE MILLING AND OVERLAY PLANS FOR LIMITS.




PERMANENT FLEXIBLE PAVEMENT REPAIR (DUCT BANK CONSTRUCTION)
DETAIL 2
 NTS

* SEE MILLING AND OVERLAY PLANS FOR LIMITS.

LEGEND FOR TYPICAL SECTIONS

- (A) STATE ROAD - 3" SUPERPAVE 0.5 INCH (PLACED IN TWO EQUAL LIFTS)
- LOCAL ROAD - 2" SUPERPAVE 0.5 INCH
- (B) STATE ROAD - 6" SUPERPAVE 1.5 INCH (PLACED IN TWO EQUAL LIFTS)
- LOCAL ROAD - 2" SUPERPAVE 0.375 INCH
- (C) 10" PROCESSED AGGREGATE SUBBASE
- (D) 1.5" SUPERPAVE 0.5 INCH
- (E) FORMATION OF SUBGRADE
- (F) CUT BITUMINOUS CONCRETE PAVEMENT
- (G) APPLY TACK COAT
- (H) TURF ESTABLISHMENT
- (I) MILL BITUMINOUS CONCRETE PAVEMENT (1.5")
- (J) CUT CONCRETE PAVEMENT
- (K) CONCRETE CURBING
- (L) CONCRETE SIDEWALK



RESET STONE CURBING/REPLACE CONC. CURBING
DETAIL 3
 NTS

* SEE MILLING AND OVERLAY PLANS FOR LIMITS.
 ** WHEN THE EXISTING CURBING IS DEEMED TO BE UNSUITABLE FOR REUSE BY THE ENGINEER, THE CONTRACTOR SHALL FURNISH AND INSTALL NEW CURBING OF THE SAME MATERIAL TO REPLACE IT.

NOTES:


- 1) THE LIMITS OF RESET STONE CURBING, CONCRETE CURBING AND CONCRETE SIDEWALK ARE SHOWN ON THE MILLING AND OVERLAY PLANS. THESE AREAS ARE APPROXIMATE AND MAY BE ADJUSTED BY THE ENGINEER TO RESTORE ADDITIONAL DISTURBED AREAS, IF ANY, DUE TO THE CONTRACTOR'S ACTIVITIES.
- 2) "MATERIAL FOR TACK COAT" SHALL BE APPLIED BETWEEN PAVEMENT COURSES AND TO ALL PAVEMENT JOINTS.
- 3) SEE TYPICAL DETAIL DRAWINGS FOR TEMPORARY PAVEMENT REPAIR DETAIL.
- 4) "PROCESSED AGGREGATE SUBBASE" SHALL BE USED IN PLACE OF "FLOWABLE FILL" AS THE ALTERNATE BACKFILL. "FLOWABLE FILL" AND "PROCESSED AGGREGATE SUBBASE" SHALL BE THERMALLY TESTED AND APPROVED BY THE ENGINEER PRIOR TO INSTALLATION. SEE TECHNICAL SPECIFICATIONS FOR DETAILS.

COPYRIGHT © 2007 BURNS & McDONNELL ENGINEERING COMPANY, INC.

DOCKET No. 272

FOR REFERENCE ONLY
NOT FOR CONSTRUCTION

no.	date	revisions	by	chk
4	4/5/07	ISSUED CSC REVISED	CTC	
3	2/26/07	ISSUED DOT/ MUNICIPALITY REVIEW	CTC	
2	9/4/06	ISSUED CSC	CTC	
1	6/1/06	ISSUED 60% PRELIMINARY	CTC	



Burns & McDonnell
SINCE 1898

date	6/15/06	detailed	BL COMPANIES
designed	BL COMPANIES	checked	S. NEWLAND

MF	NO.	DATE	REVISIONS	BY	CHK	APP	APP


NORTHEAST UTILITIES SERVICE CO.

FOR THE CONNECTICUT LIGHT & POWER COMPANY

TITLE MIDDLETOWN-NORWALK 345KV TRANSMISSION PROJECT



PAVEMENT RESTORATION DETAILS

BY SEN-BMCD	CHKD	APP	APP
DATE 6-15-06	DATE	DATE	DATE
SCALE AS NOTED	D	DWG. NO.	01224-71003 PG 001





- NOTES
- ①. 20 GPM TRASH PUMP DEWATERS FOUNDATION EXCAVATION
 - ②. MUDDY WATER DISCHARGES TO 1,250 GAL SEPTIC TANK (OR DET. OUTLET STRUCTURE)
 - ③. 4" TEE OUTLET WRAPPED W/ FILTER FABRIC
 - ④. 1,250 GAL CLEAR WELL
 - ⑤. 2ND 4" TEE OUTLET WRAPPED W/ FILTER FABRIC
 - ⑥. 2ND PUMP IN 55 GAL DRUM (OR GRAVITY HOSE) DRAINS SYSTEM
 - ⑦. TEMP. OUTLET TO CATCH BASIN IN STREET
 - ⑧. 2-1,250 GAL. TANKS = 2,500 GAL. CAPACITY TOTAL

PORTABLE SEDIMENT TANK
 DETAIL NTS ①




TEMPORARY SEDIMENT TRAP
 DETAIL NTS ②



RIPRAP TYPE	"T" (INCHES)
INTERMEDIATE	18
MODIFIED	12
STANDARD	36

LEVEL SPREADER
 DETAIL NTS ③



GUTTERBUDDY STORM DRAIN
 DETAIL NTS ④

FOR REFERENCE ONLY
 NOT FOR CONSTRUCTION

no.	date	revisions	by	chk
4	4/5/07	ISSUED CSC REVISED		CTC
3	2/26/07	ISSUED DOT/ MUNICIPALITY REVIEW		CTC
2	9/4/06	ISSUED CSC		CTC
1	6/1/06	ISSUED 60% PRELIMINARY		CTC



date 11/09/05
 detailed BL COMPANIES
 designed BL COMPANIES
 checked S. NEWLAND

MF	NO.	DATE	REVISIONS	BY	CHK	APP	APP

NORTHEAST UTILITIES SERVICE CO.			
FOR THE CONNECTICUT LIGHT & POWER COMPANY			
TITLE MIDDLETOWN-NORWALK 345KV TRANSMISSION PROJECT			
EROSION CONTROL DETAILS			
BY SEN-BMCD	CHKD	APP	APP
DATE 11-09-05	DATE	DATE	DATE
SCALE AS NOTED	D	DWG. NO. 01224-15003	PG 002