



STATE OF CONNECTICUT

CONNECTICUT SITING COUNCIL

Ten Franklin Square, New Britain, CT 06051

Phone: (860) 827-2935 Fax: (860) 827-2950

E-Mail: siting.council@ct.gov

www.ct.gov/csc

VIA ELECTRONIC MAIL

September 12, 2019

Anne Marie Zsamba
Real Estate Specialist
Crown Castle
3 Corporate Drive, Suite 101
Clifton Park, NY 12065

RE: **EM-T-MOBILE-030-190829** - T-Mobile notice of intent to modify an existing telecommunications facility located at 14 Thompson Hill Road, Columbia, Connecticut.

Dear Ms. Zsamba:

The Connecticut Siting Council (Council) is in receipt of your correspondence of September 11, 2019 submitted in response to the Council's September 9, 2019 notification of an incomplete request for exempt modification with regard to the above-referenced matter.

The submission renders the request for exempt modification complete and the Council will process the request in accordance with the Federal Communications Commission 60-day timeframe.

Thank you for your attention and cooperation.


Sincerely,

Melanie A. Bachman
Executive Director

MAB/MP/lm



Zsamba, Anne Marie



From: Zsamba, Anne Marie
Sent: Wednesday, September 11, 2019 8:52 AM
To: 'Mathews, Lisa A'
Cc: CSC-DL Siting Council
Subject: RE: Council Incomplete Letter for EM-T-MOBILE-030-190829 (14 Thompson Hill Road, Columbia)
Attachments: 876391_479837_Mount_T-Mobile_161ft.pdf; FCDS 876391.pdf

Good morning,

My most sincere apologies for the deficiencies noted in the Council's correspondence dated September 9, 2019.

Attached hereto please find a digitally signed MA as well as the correct set of drawings for this application. Hardcopies of the attached documents will arrive via Fedex delivery tomorrow, September 12. Please confirm this renders the exempt modification application complete.

Thank you.

Best,
Anne Marie

ANNE MARIE ZSAMBA
Real Estate Specialist
T: (201) 236-9224
F: (724) 416-6112

CROWN CASTLE
3 Corporate Park Drive, Suite 101,
Clifton Park, NY 12065
CrownCastle.com

From: Mathews, Lisa A <Lisa.A.Mathews@ct.gov>
Sent: Tuesday, September 10, 2019 3:39 PM
To: Zsamba, Anne Marie <AnneMarie.Zsamba@crowncastle.com>
Cc: CSC-DL Siting Council <Siting.Council@ct.gov>
Subject: Council Incomplete Letter for EM-T-MOBILE-030-190829 (14 Thompson Hill Road, Columbia)

CAUTION: This email originated from outside of the organization. Do not click links or open attachments unless you recognize the sender and know the content is safe.

Please see the attached correspondence.

Lisa A. Mathews
Office Assistant
Connecticut Siting Council
10 Franklin Square
New Britain, CT 06051
Lisa.A.Mathews@ct.gov

SCOPE OF WORK

ITEMS TO BE INSTALLED ON & REMOVED FROM EXISTING TOWER:

- REMOVE (3) ANTENNAS.
- REMOVE (3) RRUS.
- INSTALL PROPOSED MOUNT MODIFICATIONS.
- INSTALL (3) NEW ANTENNA PIPES.
- INSTALL T-MOBILE ANTENNA (APXVAARR24_43-U-NA20) (TYP. OF 1 PER SECTOR, TOTAL OF 3).
- INSTALL T-MOBILE RADIO (4449 B71+B12) (TYP. OF 1 PER SECTOR, TOTAL OF 3).
- INSTALL T-MOBILE ANTENNA (AIR32 KR0901146-1_B66A_B2A) (TYP. OF 1 PER SECTOR, TOTAL OF 3).
- INSTALL T-MOBILE COAX JUMPER CABLES (TYP. OF 4 PER SECTOR, TOTAL OF 12).
- INSTALL T-MOBILE FIBER JUMPER CABLES (TYP. OF 5 PER SECTOR, TOTAL OF 15).
- INSTALL T-MOBILE 6x12 HCS HYBRID CABLE (TOTAL OF 3).
- UPGRADE BREAKER TO 125A.

ITEMS TO BE INSTALLED ON & REMOVED FROM EXISTING EQUIPMENT PAD:

- REMOVE (1) XMU.
- REMOVE (1) DUS41.
- INSTALL (2) ERICSSON BASEBAND 6630 UNITS

ITEMS TO REMAIN:

- (3) ANTENNAS, (3) TMAS, (6) RU22, (1) DUW30, (1) DUG20, (6) COAX CABLES, (1) HYBRID CABLE.

SITE ADDRESS: 14 THOMPSON HILL ROAD
COLUMBIA, CT 06237

LATITUDE (NAD 83): N 41° 43' 3.44"

LONGITUDE (NAD 83): W 72° 17' 59.09"

COUNTY: TOLLAND

JURISDICTION: -

LANDLORD: CROWN CASTLE INTERNATIONAL
500 W. CUMMINGS PARK, STE 3600
WOBURN, MA 01801

STRUCTURE TYPE: MONOPOLE

STRUCTURE HEIGHT: 180'

RAD CENTER: 160'

CURRENT USE: TELECOMMUNICATIONS FACILITY

PROPOSED USE: TELECOMMUNICATIONS FACILITY

NOTE:
ALL CONSTRUCTION ACTIVITIES ARE TO BE COMPLETED DIRECTLY THROUGH CROWN. CONTRACTOR MUST HAVE CONSTRUCTION PO AND NTP FROM CROWN DIRECT IN ORDER TO BEGIN. PRE-APPROVAL TO ENTER THE PROPERTY MUST BE OBTAINED. FOR ACCESS AUTHORIZATION, PLEASE CONTACT CROWN.



L600 PROJECT

SITE NUMBER: CT11503A

SITE NAME: SPRINT COLUMBIA RT 6

CROWN SITE NAME: COLUMBIA / DEOJAY

BU#: 876391

T-MOBILE RAN TEMPLATE: 67D92DB OUTDOOR

T-Mobile
T-MOBILE NORTHEAST LLC
103 MONARCH DRIVE
LIVERPOOL, NY 13088

CROWN CASTLE
3 CORPORATE PARK DRIVE
SUITE 101
CLIFTON PARK, NY 12065

JACOBS
JACOBS ENGINEERING GROUP, INC.
120 ST. JAMES AVENUE, 5TH FLOOR
BOSTON, MA 02116



PROJECT NO: ERCC0004

DRAWN BY: AJM

CHECKED BY: CAT

SUBMITTALS		
NO.	DATE	DESCRIPTION
1	08/21/19	ISSUED FOR CONSTRUCTION
0	07/17/19	ISSUED FOR PERMITTING

THIS DOCUMENT IS THE CREATION, DESIGN, PROPERTY AND COPYRIGHTED WORK OF T-MOBILE. ANY DUPLICATION OR USE WITHOUT EXPRESS WRITTEN CONSENT IS STRICTLY PROHIBITED. DUPLICATION AND USE BY GOVERNMENT AGENCIES FOR THE PURPOSES OF CONDUCTING THEIR LAWFULLY AUTHORIZED REGULATORY AND ADMINISTRATIVE FUNCTIONS IS SPECIFICALLY ALLOWED.

SPRINT COLUMBIA RT 6
CT11503A
COLUMBIA / DEOJAY
876391
14 THOMPSON HILL ROAD
COLUMBIA, CT 06237

TITLE SHEET

T-1

DRAWING INDEX


SHEET NO:	SHEET TITLE
T-1	TITLE SHEET
GN-1	GENERAL NOTES
C-1	SITE PLAN
S-1	PROPOSED TOWER ELEVATION & ANTENNA LAYOUT PLAN
S-2	EQUIPMENT DETAILS
S-3	MOUNT DETAILS
S-4	MOUNT DETAILS
RF-1	ANTENNA INFORMATION CHART
RF-2	RF EQUIPMENT SCHEMATIC
E-1	ONE LINE DIAGRAM
G-1	GROUNDING RISER DIAGRAM

CROWN CASTLE SITE ID #: 876391
CROWN CASTLE SITE NAME: COLUMBIA / DEOJAY

ENGINEERING

2018 CONNECTICUT STATE BUILDING CODE
2018 AMENDMENT WITH 2015 INTERNATIONAL BUILDING CODE
2009 ICC/ANSI A117.1 ACCESSIBLE AND USABLE BUILDINGS AND FACILITIES
2015 INTERNATIONAL MECHANICAL CODE
2015 INTERNATIONAL ENERGY CONSERVATION CODE
2017 NATIONAL ELECTRICAL CODE (NFPA 70 2017)
ANSI/TIA-222-G


VICINITY MAP



384 TO ROUTE 6, TAKE RIGHT ON 66 WEST. GO TO TOP OF HILL AND TAKE HARD RIGHT ON MACHT ROAD. BEAR LEFT ON THOMPSON HILL ROAD, #14 ON LEFT. PULL INTO THE DRIVEWAY FOR #14 WITH CROWN YELLOW "CELL TOWER" SIGN ON MAILBOX AND PROCEED TO THE LEFT OF THE HOUSE. ACCESS ROAD CONTINUES UNTIL LOWER ACCESS GATE WITH CROWN BUSINESS SIGN ON IT. DO NOT DRIVE ON LANDLORDS PROPERTY - 4X4 VEHICLES ONLY. NO WINTER ACCESS, DO NOT PLOW. NOT SAFE TO ACCESS. - HOURS OF ACCESS: 8AM TO DARK. FOR ANY WORK AFTER DARK PLEASE CALL THE LANDOWNER TO ADVISE JOSHUA LANATI 860-716-5943 -ATTENTION VENDORS/CONTRACTORS: BE SURE TO HAVE COMPANY IDENTIFICATION WHEN ON SITE. CLEAN UP ALL TRASH & DEBRIS WHEN LEAVING THE SITE. **DO NOT OPEN ANY GATES THAT DO NOT HAVE CROWN SIGNAGE ON IT** *FOLLOW WRITTEN DIRECTIONS AND NOT GPS CORDS SOLELY* CHILDREN ON PROPERTY/DO NOT SPEED

GENERAL NOTES

1. THE FACILITY IS AN UNMANNED PRIVATE AND SECURED EQUIPMENT INSTALLATION. IT IS ONLY ACCESSED BY TRAINED TECHNICIANS FOR PERIODIC ROUTINE MAINTENANCE AND THEREFORE DOES NOT REQUIRE ANY WATER OR SANITARY SEWER SERVICE. THE FACILITY IS NOT GOVERNED BY REGULATIONS REQUIRING PUBLIC ACCESS PER ADA REQUIREMENTS.
2. CONTRACTOR SHALL VERIFY ALL PLANS AND EXISTING DIMENSIONS AND CONDITIONS ON THE JOB SITE AND SHALL IMMEDIATELY NOTIFY THE T-MOBILE REPRESENTATIVE IN WRITING OF DISCREPANCIES BEFORE PROCEEDING WITH THE WORK OR BE RESPONSIBLE FOR SAME.
3. HANDICAP REQUIREMENTS ARE NOT REQUIRED.
4. THIS FACILITY SHALL MEET OR EXCEED ALL FAA AND FCC REGULATORY REQUIREMENTS.
5. ALL NEW MATERIAL SHALL BE FURNISHED AND INSTALLED BY CONTRACTOR UNLESS NOTED OTHERWISE. EQUIPMENT, ANTENNAS/RADIOS AND CABLES FURNISHED BY OWNER AND INSTALLED BY CONTRACTOR.
6. NO COMMERCIAL SIGNAGE IS PROPOSED.



CALL CONNECTICUT ONE CALL
(800) 922-4455
CALL 3 WORKING DAYS
BEFORE YOU DIG!



CROWN CASTLE USA INC. SITE ACTIVITY REQUIREMENTS:

- NOTICE TO PROCEED- NO WORK SHALL COMMENCE PRIOR TO CROWN CASTLE USA INC. WRITTEN NOTICE TO PROCEED (NTP) AND THE ISSUANCE OF A PURCHASE ORDER. PRIOR TO ACCESSING/ENTERING THE SITE YOU MUST CONTACT THE CROWN CASTLE USA INC. NOC AT 800-788-7011 & THE CROWN CASTLE USA INC. CONSTRUCTION MANAGER.
- "LOOK UP" - CROWN CASTLE USA INC. SAFETY CLIMB REQUIREMENT:**
THE INTEGRITY OF THE SAFETY CLIMB AND ALL COMPONENTS OF THE CLIMBING FACILITY SHALL BE CONSIDERED DURING ALL STAGES OF DESIGN, INSTALLATION, AND INSPECTION. TOWER MODIFICATION, MOUNT REINFORCEMENTS, AND/OR EQUIPMENT INSTALLATIONS SHALL NOT COMPROMISE THE INTEGRITY OR FUNCTIONAL USE OF THE SAFETY CLIMB OR ANY COMPONENTS OF THE CLIMBING FACILITY ON THE STRUCTURE. THIS SHALL INCLUDE, BUT NOT BE LIMITED TO: PINCHING OF THE WIRE ROPE, BENDING OF THE WIRE ROPE FROM ITS SUPPORTS, DIRECT CONTACT OR CLOSE PROXIMITY TO THE WIRE ROPE WHICH MAY CAUSE FRICTIONAL WEAR, IMPACT TO THE ANCHORAGE POINTS IN ANY WAY, OR TO IMPED/BLOCK ITS INTENDED USE. ANY COMPROMISED SAFETY CLIMB, INCLUDING EXISTING CONDITIONS MUST BE TAGGED OUT AND REPORTED TO YOUR CROWN CASTLE USA INC. POC OR CALL THE NOC TO GENERATE A SAFETY CLIMB MAINTENANCE AND CONTRACTOR NOTICE TICKET.
- PRIOR TO THE START OF CONSTRUCTION, ALL REQUIRED JURISDICTIONAL PERMITS SHALL BE OBTAINED. THIS INCLUDES, BUT IS NOT LIMITED TO, BUILDING, ELECTRICAL, MECHANICAL, FIRE, FLOOD ZONE, ENVIRONMENTAL, AND ZONING. AFTER ONSITE ACTIVITIES AND CONSTRUCTION ARE COMPLETED, ALL REQUIRED PERMITS SHALL BE SATISFIED AND CLOSED OUT ACCORDING TO LOCAL JURISDICTIONAL REQUIREMENTS.
- ALL CONSTRUCTION MEANS AND METHODS; INCLUDING BUT NOT LIMITED TO, ERECTION PLANS, RIGGING PLANS, CLIMBING PLANS, AND RESCUE PLANS SHALL BE THE RESPONSIBILITY OF THE GENERAL CONTRACTOR RESPONSIBLE FOR THE EXECUTION OF THE WORK CONTAINED HEREIN, AND SHALL MEET ANSI/ASSE A10.48 (LATEST EDITION); FEDERAL, STATE, AND LOCAL REGULATIONS; AND ANY APPLICABLE INDUSTRY CONSENSUS STANDARDS RELATED TO THE CONSTRUCTION ACTIVITIES BEING PERFORMED. ALL RIGGING PLANS SHALL ADHERE TO ANSI/ASSE A10.48 (LATEST EDITION) AND CROWN CASTLE USA INC. STANDARD CED-STD-10253, INCLUDING THE REQUIRED INVOLVEMENT OF A QUALIFIED ENGINEER FOR CLASS IV CONSTRUCTION, TO CERTIFY THE SUPPORTING STRUCTURE(S) IN ACCORDANCE WITH ANS/ITIA-322 (LATEST EDITION).
- ALL SITE WORK TO COMPLY WITH OAS-STD-10068 "INSTALLATION STANDARDS FOR CONSTRUCTION ACTIVITIES ON CROWN CASTLE USA INC. TOWER SITE" AND LATEST VERSION OF ANS/ITIA-1019-A-2012 "STANDARD FOR INSTALLATION, ALTERATION, AND MAINTENANCE OF ANTENNA SUPPORTING STRUCTURES AND ANTENNAS".
- IF THE SPECIFIED EQUIPMENT CAN NOT BE INSTALLED AS SHOWN ON THESE DRAWINGS, THE CONTRACTOR SHALL PROPOSE AN ALTERNATIVE INSTALLATION FOR APPROVAL BY CROWN CASTLE USA INC. PRIOR TO PROCEEDING WITH ANY SUCH CHANGE OF INSTALLATION.
- ALL MATERIALS FURNISHED AND INSTALLED SHALL BE IN STRICT ACCORDANCE WITH ALL APPLICABLE CODES, REGULATIONS AND ORDINANCES. CONTRACTOR SHALL ISSUE ALL APPROPRIATE NOTICES AND COMPLY WITH ALL LAWS, ORDINANCES, RULES, REGULATIONS AND LAWFUL ORDERS OF ANY PUBLIC AUTHORITY REGARDING THE PERFORMANCE OF THE WORK. ALL WORK CARRIED OUT SHALL COMPLY WITH ALL APPLICABLE MUNICIPAL AND UTILITY COMPANY SPECIFICATIONS AND LOCAL JURISDICTIONAL CODES, ORDINANCES AND APPLICABLE REGULATIONS.
- THE CONTRACTOR SHALL INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS UNLESS SPECIFICALLY STATED OTHERWISE.
- THE CONTRACTOR SHALL CONTACT UTILITY LOCATING SERVICES PRIOR TO THE START OF CONSTRUCTION.
- ALL EXISTING ACTIVE SEWER, WATER, GAS, ELECTRIC AND OTHER UTILITIES WHERE ENCOUNTERED IN THE WORK, SHALL BE PROTECTED AT ALL TIMES AND WHERE REQUIRED FOR THE PROPER EXECUTION OF THE WORK, SHALL BE RELOCATED AS DIRECTED BY CONTRACTOR. EXTREME CAUTION SHOULD BE USED BY THE CONTRACTOR WHEN EXCAVATING OR DRILLING PIERS AROUND OR NEAR UTILITIES. CONTRACTOR SHALL PROVIDE SAFETY TRAINING FOR THE WORKING CREW. THIS WILL INCLUDE BUT NOT BE LIMITED TO A) FALL PROTECTION B) CONFINED SPACE C) ELECTRICAL SAFETY D) TRENCHING AND EXCAVATION E) CONSTRUCTION SAFETY PROCEDURES.
- ALL SITE WORK SHALL BE AS INDICATED ON THE STAMPED CONSTRUCTION DRAWINGS AND PROJECT SPECIFICATIONS, LATEST APPROVED REVISION.
- CONTRACTOR SHALL KEEP THE SITE FREE FROM ACCUMULATING WASTE MATERIAL, DEBRIS, AND TRASH AT THE COMPLETION OF THE WORK. IF NECESSARY, RUBBISH, STUMPS, DEBRIS, STICKS, STONES AND OTHER REFUSE SHALL BE REMOVED FROM THE SITE AND DISPOSED OF LEGALLY.
- ALL EXISTING INACTIVE SEWER, WATER, GAS, ELECTRIC AND OTHER UTILITIES, WHICH INTERFERE WITH THE EXECUTION OF THE WORK, SHALL BE REMOVED AND/OR CAPPED, PLUGGED OR OTHERWISE DISCONTINUED AT POINTS WHICH WILL NOT INTERFERE WITH THE EXECUTION OF THE WORK, SUBJECT TO THE APPROVAL OF CONTRACTOR, TOWER OWNER, CROWN CASTLE USA INC., AND/OR LOCAL UTILITIES.
- THE CONTRACTOR SHALL PROVIDE SITE SIGNAGE IN ACCORDANCE WITH THE TECHNICAL SPECIFICATION FOR SITE SIGNAGE REQUIRED BY LOCAL JURISDICTION AND SIGNAGE REQUIRED ON INDIVIDUAL PIECES OF EQUIPMENT, ROOMS, AND SHELTERS.
- THE SITE SHALL BE GRADED TO CAUSE SURFACE WATER TO FLOW AWAY FROM THE CARRIER'S EQUIPMENT AND TOWER AREAS.
- THE SUB GRADE SHALL BE COMPACTED AND BROUGHT TO A SMOOTH UNIFORM GRADE PRIOR TO FINISHED SURFACE APPLICATION.
- THE AREAS OF THE OWNERS PROPERTY DISTURBED BY THE WORK AND NOT COVERED BY THE TOWER, EQUIPMENT OR DRIVEWAY, SHALL BE GRADED TO A UNIFORM SLOPE, AND STABILIZED TO PREVENT EROSION AS SPECIFIED ON THE CONSTRUCTION DRAWINGS AND/OR PROJECT SPECIFICATIONS.
- CONTRACTOR SHALL MINIMIZE DISTURBANCE TO EXISTING SITE DURING CONSTRUCTION. EROSION CONTROL MEASURES, IF REQUIRED DURING CONSTRUCTION, SHALL BE IN CONFORMANCE WITH THE LOCAL GUIDELINES FOR EROSION AND SEDIMENT CONTROL.
- THE CONTRACTOR SHALL PROTECT EXISTING IMPROVEMENTS, PAVEMENTS, CURBS, LANDSCAPING AND STRUCTURES. ANY DAMAGED PART SHALL BE REPAIRED AT CONTRACTOR'S EXPENSE TO THE SATISFACTION OF OWNER.
- CONTRACTOR SHALL LEGALLY AND PROPERLY DISPOSE OF ALL SCRAP MATERIALS SUCH AS COAXIAL CABLES AND OTHER ITEMS REMOVED FROM THE EXISTING FACILITY. ANTENNAS REMOVED SHALL BE RETURNED TO THE OWNER'S DESIGNATED LOCATION.
- CONTRACTOR SHALL LEAVE PREMISES IN CLEAN CONDITION. TRASH AND DEBRIS SHOULD BE REMOVED FROM SITE ON A DAILY BASIS.
- NO FILL OR EMBANKMENT MATERIAL SHALL BE PLACED ON FROZEN GROUND. FROZEN MATERIALS, SNOW OR ICE SHALL NOT BE PLACED IN ANY FILL OR EMBANKMENT.

GROUNDING NOTES:

- ALL GROUND ELECTRODE SYSTEMS (INCLUDING TELECOMMUNICATION, RADIO, LIGHTNING PROTECTION AND AC POWER GES'S) SHALL BE BONDED TOGETHER AT OR BELOW GRADE, BY TWO OR MORE COPPER BONDING CONDUCTORS IN ACCORDANCE WITH THE NEC.
- THE CONTRACTOR SHALL PERFORM IEEE FALL-OF-POTENTIAL RESISTANCE TO EARTH TESTING (PER IEEE 1100 AND 81) FOR GROUND ELECTRODE SYSTEMS, THE CONTRACTOR SHALL FURNISH AND INSTALL SUPPLEMENTAL GROUND ELECTRODES AS NEEDED TO ACHIEVE A TEST RESULT OF 5 OHMS OR LESS.
- THE CONTRACTOR IS RESPONSIBLE FOR PROPERLY SEQUENCING GROUNDING AND UNDERGROUND CONDUIT INSTALLATION AS TO PREVENT ANY LOSS OF CONTINUITY IN THE GROUNDING SYSTEM OR DAMAGE TO THE CONDUIT AND PROVIDE TESTING RESULTS.
- METAL CONDUIT AND TRAY SHALL BE GROUNDED AND MADE ELECTRICALLY CONTINUOUS WITH LISTED BONDING FITTINGS OR BY BONDING ACROSS THE DISCONTINUITY WITH #6 COPPER WIRE UL APPROVED GROUNDING TYPE CONDUIT CLAMPS.
- METAL RACEWAY SHALL NOT BE USED AS THE NEC REQUIRED EQUIPMENT GROUND CONDUCTOR. STRANDED COPPER CONDUCTORS WITH GREEN INSULATION, SIZED IN ACCORDANCE WITH THE NEC, SHALL BE FURNISHED AND INSTALLED WITH THE POWER CIRCUITS TO BTS EQUIPMENT.
- EACH CABINET FRAME SHALL BE DIRECTLY CONNECTED TO THE MASTER GROUND BAR WITH GREEN INSULATED SUPPLEMENTAL EQUIPMENT GROUND WIRES, #6 STRANDED COPPER OR LARGER FOR INDOOR BTS; #2 BARE SOLID TINNED COPPER FOR OUTDOOR BTS.
- CONNECTIONS TO THE GROUND BUS SHALL NOT BE DOUBLED UP OR STACKED BACK TO BACK CONNECTIONS ON OPPOSITE SIDE OF THE GROUND BUS ARE PERMITTED.
- ALL EXTERIOR GROUND CONDUCTORS BETWEEN EQUIPMENT/GROUND BARS AND THE GROUND RING SHALL BE #2 SOLID TINNED COPPER UNLESS OTHERWISE INDICATED.
- ALUMINUM CONDUCTOR OR COPPER CLAD STEEL CONDUCTOR SHALL NOT BE USED FOR GROUNDING CONNECTIONS.
- USE OF 90° BENDS IN THE PROTECTION GROUNDING CONDUCTORS SHALL BE AVOIDED WHEN 45° BENDS CAN BE ADEQUATELY SUPPORTED.
- EXOTHERMIC WELDS SHALL BE USED FOR ALL GROUNDING CONNECTIONS BELOW GRADE.
- ALL GROUND CONNECTIONS ABOVE GRADE (INTERIOR AND EXTERIOR) SHALL BE FORMED USING HIGH PRESS CRIMPS.
- COMPRESSION GROUND CONNECTIONS MAY BE REPLACED BY EXOTHERMIC WELD CONNECTIONS.
- ICE BRIDGE BONDING CONDUCTORS SHALL BE EXOTHERMICALLY BONDED OR BOLTED TO THE BRIDGE AND THE TOWER GROUND BAR.
- APPROVED ANTIOXIDANT COATINGS (i.e. CONDUCTIVE GEL OR PASTE) SHALL BE USED ON ALL COMPRESSION AND BOLTED GROUND CONNECTIONS.
- ALL EXTERIOR GROUND CONNECTIONS SHALL BE COATED WITH A CORROSION RESISTANT MATERIAL.
- MISCELLANEOUS ELECTRICAL AND NON-ELECTRICAL METAL BOXES, FRAMES AND SUPPORTS SHALL BE BONDED TO THE GROUND RING, IN ACCORDANCE WITH THE NEC.
- BOND ALL METALLIC OBJECTS WITHIN 6 ft OF MAIN GROUND RING WITH (1) #2 BARE SOLID TINNED COPPER GROUND CONDUCTOR.
- GROUND CONDUCTORS USED FOR THE FACILITY GROUNDING AND LIGHTNING PROTECTION SYSTEMS SHALL NOT BE ROUTED THROUGH METALLIC OBJECTS THAT FORM A RING AROUND THE CONDUCTOR, SUCH AS METALLIC CONNECTIONS, METAL SUPPORT CLIPS OR SLEEVES THROUGH WALLS OR FLOORS. WHEN IT IS REQUIRED TO BE HOUSED IN CONDUIT TO MEET CODE REQUIREMENTS OR LOCAL CONDITIONS, NON-METALLIC MATERIAL SUCH AS PVC CONDUIT SHALL BE USED. WHERE USE OF METAL CONDUIT IS UNAVOIDABLE (i.e., NONMETALLIC CONDUIT PROHIBITED BY LOCAL CODE) THE GROUND CONDUCTOR SHALL BE BONDED TO EACH END OF THE METAL CONDUIT.
- ALL GROUNDS THAT TRANSITION FROM BELOW GRADE TO ABOVE GRADE MUST BE #2 BARE SOLID TINNED COPPER IN 3/4" NON-METALLIC, FLEXIBLE CONDUIT FROM 24" BELOW GRADE TO WITHIN 3" TO 6" OF CAD-WELD TERMINATION POINT. THE EXPOSED END OF THE CONDUIT MUST BE SEALED WITH SILICONE CAULK. (ADD TRANSITIONING GROUND STANDARD DETAIL AS WELL).
- BUILDINGS WHERE THE MAIN GROUNDING CONDUCTORS ARE REQUIRED TO BE ROUTED TO GRADE, THE CONTRACTOR SHALL ROUTE TWO GROUNDING CONDUCTORS FROM THE ROOFTOP, TOWERS, AND WATER TOWERS GROUNDING RING, TO THE EXISTING GROUNDING SYSTEM. THE GROUNDING CONDUCTORS SHALL NOT BE SMALLER THAN 2/0 COPPER. ROOFTOP GROUNDING RING SHALL BE BONDED TO THE EXISTING GROUNDING SYSTEM, THE BUILDING STEEL COLUMNS, LIGHTNING PROTECTION SYSTEM, AND BUILDING MAIN WATER LINE (FERROUS OR NONFERROUS METAL PIPING ONLY).

GENERAL NOTES:

- FOR THE PURPOSE OF CONSTRUCTION DRAWING, THE FOLLOWING DEFINITIONS SHALL APPLY:
CONTRACTOR: GENERAL CONTRACTOR RESPONSIBLE FOR CONSTRUCTION
CARRIER: T-MOBILE
TOWER OWNER: CROWN CASTLE USA INC.
- THESE DRAWINGS HAVE BEEN PREPARED USING STANDARDS OF PROFESSIONAL CARE AND COMPLETENESS NORMALLY EXERCISED UNDER SIMILAR CIRCUMSTANCES BY REPUTABLE ENGINEERS IN THIS OR SIMILAR LOCALITIES. IT IS ASSUMED THAT THE WORK DEPICTED WILL BE PERFORMED BY AN EXPERIENCED CONTRACTOR AND/OR WORKPEOPLE WHO HAVE A WORKING KNOWLEDGE OF THE APPLICABLE CODE STANDARDS AND REQUIREMENTS AND OF INDUSTRY ACCEPTED STANDARD GOOD PRACTICE. AS NOT EVERY CONDITION OR ELEMENT IS (OR CAN BE) EXPLICITLY SHOWN ON THESE DRAWINGS, THE CONTRACTOR SHALL USE INDUSTRY ACCEPTED STANDARD GOOD PRACTICE FOR MISCELLANEOUS WORK NOT EXPLICITLY SHOWN.
- THESE DRAWINGS REPRESENT THE FINISHED STRUCTURE. THEY DO NOT INDICATE THE MEANS OR METHODS OF CONSTRUCTION. THE CONTRACTOR SHALL BE SOLELY RESPONSIBLE FOR THE CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES, AND PROCEDURES. THE CONTRACTOR SHALL PROVIDE ALL MEASURES NECESSARY FOR PROTECTION OF LIFE AND PROPERTY DURING CONSTRUCTION. SUCH MEASURES SHALL INCLUDE, BUT NOT BE LIMITED TO, BRACING, FORMWORK, SHORING, ETC. SITE VISITS BY THE ENGINEER OR HIS REPRESENTATIVE WILL NOT INCLUDE INSPECTION OF THESE ITEMS AND IS FOR STRUCTURAL OBSERVATION OF THE FINISHED STRUCTURE ONLY.
- NOTES AND DETAILS IN THE CONSTRUCTION DRAWINGS SHALL TAKE PRECEDENCE OVER GENERAL NOTES AND TYPICAL DETAILS. WHERE NO DETAILS ARE SHOWN, CONSTRUCTION SHALL CONFORM TO SIMILAR WORK ON THE PROJECT, AND/OR AS PROVIDED FOR IN THE CONTRACT DOCUMENTS. WHERE DISCREPANCIES OCCUR BETWEEN PLANS, DETAILS, GENERAL NOTES, AND SPECIFICATIONS, THE GREATER, MORE STRICT REQUIREMENTS, SHALL GOVERN. IF FURTHER CLARIFICATION IS REQUIRED CONTACT THE ENGINEER OF RECORD.
- SUBSTANTIAL EFFORT HAS BEEN MADE TO PROVIDE ACCURATE DIMENSIONS AND MEASUREMENTS ON THE DRAWINGS TO ASSIST IN THE FABRICATION AND/OR PLACEMENT OF CONSTRUCTION ELEMENTS BUT IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO FIELD VERIFY THE DIMENSIONS, MEASUREMENTS, AND/OR CLEARANCES SHOWN IN THE CONSTRUCTION DRAWINGS PRIOR TO FABRICATION OR CUTTING OF ANY NEW OR EXISTING CONSTRUCTION ELEMENTS. IF IT IS DETERMINED THAT THERE ARE DISCREPANCIES AND/OR CONFLICTS WITH THE CONSTRUCTION DRAWINGS THE ENGINEER OF RECORD IS TO BE NOTIFIED AS SOON AS POSSIBLE.
- PRIOR TO THE SUBMISSION OF BIDS, THE BIDDING CONTRACTOR SHALL VISIT THE CELL SITE TO FAMILIARIZE WITH THE EXISTING CONDITIONS AND TO CONFIRM THAT THE WORK CAN BE ACCOMPLISHED AS SHOWN ON THE CONSTRUCTION DRAWINGS. ANY DISCREPANCY FOUND SHALL BE BROUGHT TO THE ATTENTION OF CROWN CASTLE.
- ALL MATERIALS FURNISHED AND INSTALLED SHALL BE IN STRICT ACCORDANCE WITH ALL APPLICABLE CODES, REGULATIONS AND ORDINANCES. CONTRACTOR SHALL ISSUE ALL APPROPRIATE NOTICES AND COMPLY WITH ALL LAWS, ORDINANCES, RULES, REGULATIONS AND LAWFUL ORDERS OF ANY PUBLIC AUTHORITY REGARDING THE PERFORMANCE OF THE WORK. ALL WORK CARRIED OUT SHALL COMPLY WITH ALL APPLICABLE MUNICIPAL AND UTILITY COMPANY SPECIFICATIONS AND LOCAL JURISDICTIONAL CODES, ORDINANCES AND APPLICABLE REGULATIONS.
- UNLESS NOTED OTHERWISE, THE WORK SHALL INCLUDE FURNISHING MATERIALS, EQUIPMENT, APPURTENANCES AND LABOR NECESSARY TO COMPLETE ALL INSTALLATIONS AS INDICATED ON THE DRAWINGS.
- THE CONTRACTOR SHALL INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS UNLESS SPECIFICALLY STATED OTHERWISE.
- IF THE SPECIFIED EQUIPMENT CAN NOT BE INSTALLED AS SHOWN ON THESE DRAWINGS, THE CONTRACTOR SHALL PROPOSE AN ALTERNATIVE INSTALLATION FOR APPROVAL BY THE CARRIER AND CROWN CASTLE PRIOR TO PROCEEDING WITH ANY SUCH CHANGE OF INSTALLATION.
- CONTRACTOR IS TO PERFORM A SITE INVESTIGATION AND IS TO DETERMINE THE BEST ROUTING OF ALL CONDUITS FOR POWER, AND TELCO AND FOR GROUNDING CABLES AS SHOWN IN THE POWER, TELCO, AND GROUNDING PLAN DRAWINGS.
- THE CONTRACTOR SHALL PROTECT EXISTING IMPROVEMENTS, PAVEMENTS, CURBS, LANDSCAPING AND STRUCTURES. ANY DAMAGED PART SHALL BE REPAIRED AT CONTRACTOR'S EXPENSE TO THE SATISFACTION OF CROWN CASTLE USA INC.
- CONTRACTOR SHALL LEGALLY AND PROPERLY DISPOSE OF ALL SCRAP MATERIALS SUCH AS COAXIAL CABLES AND OTHER ITEMS REMOVED FROM THE EXISTING FACILITY. ANTENNAS REMOVED SHALL BE RETURNED TO THE OWNER'S DESIGNATED LOCATION.
- CONTRACTOR SHALL LEAVE PREMISES IN CLEAN CONDITION. TRASH AND DEBRIS SHOULD BE REMOVED FROM SITE ON A DAILY BASIS.

ELECTRICAL INSTALLATION NOTES:

- ALL ELECTRICAL WORK SHALL BE PERFORMED IN ACCORDANCE WITH THE PROJECT SPECIFICATIONS, NEC AND ALL APPLICABLE FEDERAL, STATE, AND LOCAL CODES/ORDINANCES.
- CONDUIT ROUTINGS ARE SCHEMATIC. CONTRACTOR SHALL INSTALL CONDUITS SO THAT ACCESS TO EQUIPMENT IS NOT BLOCKED AND TRIP HAZARDS ARE ELIMINATED.
- WIRING, RACEWAY AND SUPPORT METHODS AND MATERIALS SHALL COMPLY WITH THE REQUIREMENTS OF THE NEC.
- ALL CIRCUITS SHALL BE SEGREGATED AND MAINTAIN MINIMUM CABLE SEPARATION AS REQUIRED BY THE NEC.
- ALL EQUIPMENT SHALL BEAR THE UNDERWRITERS LABORATORIES LABEL OF APPROVAL, AND SHALL CONFORM TO REQUIREMENT OF THE NATIONAL ELECTRICAL CODE.
- ALL OVERCURRENT DEVICES SHALL HAVE AN INTERRUPTING CURRENT RATING THAT SHALL BE GREATER THAN THE SHORT CIRCUIT CURRENT TO WHICH THEY ARE SUBJECTED, 20,000 AIC MINIMUM. VERIFY AVAILABLE SHORT CIRCUIT CURRENT DOES NOT EXCEED THE RATING OF ELECTRICAL EQUIPMENT IN ACCORDANCE WITH ARTICLE 110.24 NEC OR THE MOST CURRENT ADOPTED CODE PRE THE GOVERNING JURISDICTION.
- EACH END OF EVERY POWER PHASE CONDUCTOR, GROUNDING CONDUCTOR, AND TELCO CONDUCTOR OR CABLE SHALL BE LABELED WITH COLOR-CODED INSULATION OR ELECTRICAL TAPE (3M BRAND, 1/2" PLASTIC ELECTRICAL TAPE WITH UV PROTECTION, OR EQUAL). THE IDENTIFICATION METHOD SHALL CONFORM WITH NEC AND OSHA.
- ALL ELECTRICAL COMPONENTS SHALL BE CLEARLY LABELED WITH LAMICOID TAGS SHOWING THEIR RATED VOLTAGE, PHASE CONFIGURATION, WIRE CONFIGURATION, POWER OR AMPACITY RATING AND BRANCH CIRCUIT ID NUMBERS (i.e. PANEL BOARD AND CIRCUIT IDS).
- PANEL BOARDS (ID NUMBERS) SHALL BE CLEARLY LABELED WITH PLASTIC LABELS.
- ALL THE WRAPS SHALL BE CUT FLUSH WITH APPROVED CUTTING TOOL TO REMOVE SHARP EDGES.
- ALL POWER AND EQUIPMENT GROUND WIRING IN TUBING OR CONDUIT SHALL BE SINGLE COPPER CONDUCTOR (#14 OR LARGER) WITH TYPE THHW, THWN, THWN-2, XHHW, XHHW-2, THW, THW-2, RHW, OR RHW-2 INSULATION UNLESS OTHERWISE SPECIFIED.
- SUPPLEMENTAL EQUIPMENT GROUND WIRING LOCATED INDOORS SHALL BE SINGLE COPPER CONDUCTOR (#6 OR LARGER) WITH TYPE THHW, THWN, THWN-2, XHHW, XHHW-2, THW, THW-2, RHW, OR RHW-2 INSULATION UNLESS OTHERWISE SPECIFIED.
- POWER AND CONTROL WIRING IN FLEXIBLE CORD SHALL BE MULTI-CONDUCTOR, TYPE SOOW CORD (#14 OR LARGER) UNLESS OTHERWISE SPECIFIED.
- POWER AND CONTROL WIRING FOR IN CABLE TRAY SHALL BE MULTI-CONDUCTOR, TYPE TC CABLE (#14 OR LARGER), WITH TYPE THHW, THWN, THWN-2, XHHW, XHHW-2, THW, THW-2, RHW, OR RHW-2 INSULATION UNLESS OTHERWISE SPECIFIED.
- ALL POWER AND GROUNDING CONNECTIONS SHALL BE CRIMP-STYLE, COMPRESSION WIRE LUGS AND WIRE NUTS BY THOMAS AND BETTS (OR EQUAL). LUGS AND WIRE NUTS SHALL BE RATED FOR OPERATION NOT LESS THAN 75° C (90° C IF AVAILABLE).
- RACEWAY AND CABLE TRAY SHALL BE LISTED OR LABELED FOR ELECTRICAL USE IN ACCORDANCE WITH NEMA, UL, ANSII/IEEC AND NEC.
- ELECTRICAL METALLIC TUBING (EMT), INTERMEDIATE METAL CONDUIT (IMC), OR RIGID METAL CONDUIT (RMC) SHALL BE USED FOR EXPOSED INDOOR LOCATIONS.
- ELECTRICAL METALLIC TUBING (EMT) OR METAL-CLAD CABLE (MC) SHALL BE USED FOR CONCEALED INDOOR LOCATIONS.
- SCHEDULE 40 PVC UNDERGROUND ON STRAIGHTS AND SCHEDULE 80 PVC FOR ALL ELBOWS/90s AND ALL APPROVED ABOVE GRADE PVC CONDUIT.
- LIQUID-TIGHT FLEXIBLE METALLIC CONDUIT (LIQUID-TITE FLEX) SHALL BE USED INDOORS AND OUTDOORS, WHERE VIBRATION OCCURS OR FLEXIBILITY IS NEEDED.
- CONDUIT AND TUBING FITTINGS SHALL BE THREADED OR COMPRESSION-TYPE AND APPROVED FOR THE LOCATION USED. SET SCREW FITTINGS ARE NOT ACCEPTABLE.
- CABINETS, BOXES AND WIRE WAYS SHALL BE LABELED FOR ELECTRICAL USE IN ACCORDANCE WITH NEMA, UL, ANSII/IEEC AND THE NEC.
- WIREWAYS SHALL BE METAL WITH AN ENAMEL FINISH AND INCLUDE A HINGED COVER, DESIGNED TO SWING OPEN DOWNWARDS (WIREMOLD SPECIMATE WIREWAY).
- SLOTTED WIRING DUCT SHALL BE PVC AND INCLUDE COVER (PANDUIT TYPE E OR EQUAL).
- CONDUITS SHALL BE FASTENED SECURELY IN PLACE WITH APPROVED NON-PERFORATED STRAPS AND HANGERS. EXPLOSIVE DEVICES (i.e. POWDER-ACTUATED) FOR ATTACHING HANGERS TO STRUCTURE WILL NOT BE PERMITTED.
- CLOSELY FOLLOW THE LINES OF THE STRUCTURE. MAINTAIN CLOSE PROXIMITY TO THE STRUCTURE AND KEEP CONDUITS IN TIGHT ENVELOPES. CHANGES IN DIRECTION TO ROUTE AROUND OBSTACLES SHALL BE MADE WITH CONDUIT OUTLET BODIES. CONDUIT SHALL BE INSTALLED IN A NEAT AND WORKMANLIKE MANNER. PARALLEL AND PERPENDICULAR TO STRUCTURE WALL AND CEILING LINES. ALL CONDUIT SHALL BE FISHED TO CLEAR OBSTRUCTIONS. ENDS OF CONDUITS SHALL BE TEMPORARILY CAPPED FLUSH TO FINISH GRADE TO PREVENT CONCRETE, PLASTER OR DIRT FROM ENTERING. CONDUITS SHALL BE RIGIDLY CLAMPED TO BOXES BY GALVANIZED MALLEABLE IRON BUSHING ON INSIDE AND GALVANIZED MALLEABLE IRON LOCKNUT ON OUTSIDE AND INSIDE.
- EQUIPMENT CABINETS, TERMINAL BOXES, JUNCTION BOXES AND PULL BOXES SHALL BE GALVANIZED OR EPOXY-COATED SHEET STEEL. SHALL MEET OR EXCEED UL 50 AND BE RATED NEMA 1 (OR BETTER) FOR INTERIOR LOCATIONS AND NEMA 3R (OR BETTER) FOR EXTERIOR LOCATIONS.
- METAL RECEPTACLE, SWITCH AND DEVICE BOXES SHALL BE GALVANIZED, EPOXY-COATED OR NON-CORRODING; SHALL MEET OR EXCEED UL 514A AND NEMA OS 1 AND BE RATED NEMA 1 (OR BETTER) FOR INTERIOR LOCATIONS AND WEATHER PROTECTED (WP OR BETTER) FOR EXTERIOR LOCATIONS.
- NONMETALLIC RECEPTACLE, SWITCH AND DEVICE BOXES SHALL MEET OR EXCEED NEMA OS 2 (NEWEST REVISION) AND BE RATED NEMA 1 (OR BETTER) FOR INTERIOR LOCATIONS AND WEATHER PROTECTED (WP OR BETTER) FOR EXTERIOR LOCATIONS.
- THE CONTRACTOR SHALL NOTIFY AND OBTAIN NECESSARY AUTHORIZATION FROM THE CARRIER AND/OR CROWN CASTLE USA INC. BEFORE COMMENCING WORK ON THE AC POWER DISTRIBUTION PANELS.
- THE CONTRACTOR SHALL PROVIDE NECESSARY TAGGING ON THE BREAKERS, CABLES AND DISTRIBUTION PANELS IN ACCORDANCE WITH THE APPLICABLE CODES AND STANDARDS TO SAFEGUARD LIFE AND PROPERTY.
- INSTALL LAMICOID LABEL ON THE METER CENTER TO SHOW " CT 11503A".
- ALL EMPTY/SPARE CONDUITS THAT ARE INSTALLED ARE TO HAVE A METERED MULE TAPE PULL CORD INSTALLED.

CONDUCTOR COLOR CODE		
SYSTEM	CONDUCTOR	COLOR
120/240V, 1 Ø	A PHASE	BLACK
	B PHASE	RED
	NEUTRAL	WHITE
	GROUND	GREEN
120/208V, 3 Ø	A PHASE	BLACK
	B PHASE	RED
	C PHASE	BLUE
	NEUTRAL	WHITE
277/480V, 3 Ø	GROUND	GREEN
	A PHASE	BROWN
	B PHASE	ORANGE OR PURPLE
	C PHASE	YELLOW
	NEUTRAL	GREY
DC VOLTAGE	GROUND	GREEN
	POS (+)	RED**
	NEG (-)	BLACK**

* SEE NEC 210.5(C)(1) AND (2)
** POLARITY MARKED AT TERMINATION




T-MOBILE NORTHEAST LLC
103 MONARCH DRIVE
LIVERPOOL, NY 13088



3 CORPORATE PARK DRIVE
SUITE 101
CLIFTON PARK, NY 12065



JACOBS ENGINEERING GROUP, INC.
120 ST. JAMES AVENUE, 5TH FLOOR
BOSTON, MA 02116



PROJECT NO: ERCC0004

DRAWN BY: AJM

CHECKED BY: CAT



SUBMITTALS		
NO.	DATE	DESCRIPTION
1	08/21/19	ISSUED FOR CONSTRUCTION
0	07/17/19	ISSUED FOR PERMITTING

THIS DOCUMENT IS THE CREATION, DESIGN, PROPERTY AND COPYRIGHTED WORK OF T-MOBILE. ANY DUPLICATION OR USE WITHOUT EXPRESS WRITTEN CONSENT IS STRICTLY PROHIBITED. DUPLICATION AND USE BY GOVERNMENT AGENCIES FOR THE PURPOSES OF CONDUCTING THEIR LAWFULLY AUTHORIZED REGULATORY AND ADMINISTRATIVE FUNCTIONS IS SPECIFICALLY ALLOWED.

SPRINT COLUMBIA RT 6
CT11503A
COLUMBIA / DEOJAY
876391
14 THOMPSON HILL ROAD
COLUMBIA, CT 06237

GENERAL NOTES

GN-1



NOTES:

1. PLAN BASED ON AUTOCAD DRAWINGS ISSUED BY CROWN CASTLE ON 02/25/2019. CONTRACTOR TO FIELD VERIFY ALL DIMENSIONS AND LOCATION/ORIENTATION OF EXISTING EQUIPMENT.




T-MOBILE NORTHEAST LLC
103 MONARCH DRIVE
LIVERPOOL, NY 13088



3 CORPORATE PARK DRIVE
SUITE 101
CLIFTON PARK, NY 12065



120 ST. JAMES AVENUE, 5TH FLOOR
BOSTON, MA 02116



PROJECT NO: ERCC0004

DRAWN BY: AJM

CHECKED BY: CAT

SUBMITTALS		
1	08/21/19	ISSUED FOR CONSTRUCTION
0	07/17/19	ISSUED FOR PERMITTING

THIS DOCUMENT IS THE CREATION, DESIGN, PROPERTY AND COPYRIGHTED WORK OF T-MOBILE. ANY DUPLICATION OR USE WITHOUT EXPRESS WRITTEN CONSENT IS STRICTLY PROHIBITED. DUPLICATION AND USE BY GOVERNMENT AGENCIES FOR THE PURPOSES OF CONDUCTING THEIR LAWFULLY AUTHORIZED REGULATORY AND ADMINISTRATIVE FUNCTIONS IS SPECIFICALLY ALLOWED.


SPRINT COLUMBIA RT 6
CT11503A
COLUMBIA / DEOJAY
876391
14 THOMPSON HILL ROAD
COLUMBIA, CT 06237

SITE PLAN

C-1


NOTES:

- CONTRACTOR SHALL REFER TO THE STRUCTURAL ANALYSIS REPORT; SITE NUMBER: CT11503A; SITE NAME: SPRINT COLUMBIA RT 6; CROWN BU NUMBER: 876391; CROWN SITE NAME: COLUMBIA / DEOJAY; CROWN ORDER NUMBER: 479837; ISSUED BY AW SOLUTIONS INCORPORATED. DATED ON 06/26/19. PER THIS ANALYSIS NO MODIFICATIONS ARE REQUIRED. THE CONTRACTOR SHALL VERIFY ALL EXISTING MEMBERS AND HARDWARE ARE INSTALLED PROPERLY AS DESCRIBED IN THIS REPORT.




1 TOWER ELEVATION

SCALE: 3/32" = 1'-0"



2 EXISTING ANTENNA LAYOUT

SCALE: N.T.S.



3 PROPOSED ANTENNA LAYOUT

SCALE: N.T.S.

NOTES:

- CONTRACTOR SHALL REFER TO THE MOUNT MODIFICATION REPORT; SITE NUMBER: CT11503A; SITE NAME: SPRINT COLUMBIA RT 6; CROWN BU NUMBER: 876391; CROWN SITE NAME: COLUMBIA / DEOJAY; CROWN ORDER NUMBER: 479837; ISSUED BY PAUL J. FORD, DATED ON 06/19/19. THE MOUNT MODIFICATIONS MUST BE PERFORMED PRIOR TO THE INSTALLATION OF THE EQUIPMENT SHOWN ON THE DRAWINGS. CONTRACTOR SHALL REFER TO SHEETS 37 THROUGH 38 FOR DETAILS. THE CONTRACTOR SHALL VERIFY ALL EXISTING MEMBERS AND HARDWARE ARE INSTALLED PROPERLY AS DESCRIBED IN THIS REPORT.
 - INSTALL SITEPRO1 PRK-SFS-L PLATFORM REINFORCEMENT KIT OR EOR APPROVED EQUIVALENT AS INDICATED IN "APPENDIX D - SUPPLEMENTAL MODIFICATION INFORMATION" AND IN CONFORMANCE WITH THE ATTACHED MANUFACTURER DRAWINGS.
 - INSTALL RFS/CELWAVE APXVAARR24_43-U-NA20 ANTENNAS ON 8-FT LONG, P2.5 STD (2.88" O.D. X 0.189)
- MOUNT PIPES. SEE APPENDIX D DETAILS.
- CONTRACTOR TO VERIFY FINAL RF CONFIGURATION AND NOTIFY CARRIER AND ENGINEER W/ ANY DISCREPANCIES PRIOR TO THE INSTALLATION.
- CONTRACTOR SHALL NOT EXCEED MOUNTING MORE THAN (2) RRHS PER ANTENNA MOUNTING PIPE - RELOCATE TO AN ADJACENT ANTENNA MOUNTING PIPE AS NEEDED.




T-MOBILE NORTHEAST LLC
103 MONARCH DRIVE
LIVERPOOL, NY 13088



3 CORPORATE PARK DRIVE
SUITE 101
CLIFTON PARK, NY 12065



120 ST. JAMES AVENUE, 5TH FLOOR
BOSTON, MA 02116



PROJECT NO: ERCC0004

DRAWN BY: AJM

CHECKED BY: CAT

SUBMITTALS		
1	08/21/19	ISSUED FOR CONSTRUCTION
0	07/17/19	ISSUED FOR PERMITTING


THIS DOCUMENT IS THE CREATION, DESIGN, PROPERTY AND COPYRIGHTED WORK OF T-MOBILE. ANY DUPLICATION OR USE WITHOUT EXPRESS WRITTEN CONSENT IS STRICTLY PROHIBITED. DUPLICATION AND USE BY GOVERNMENT AGENCIES FOR THE PURPOSES OF CONDUCTING THEIR LAWFULLY AUTHORIZED REGULATORY AND ADMINISTRATIVE FUNCTIONS IS SPECIFICALLY ALLOWED.

SPRINT COLUMBIA RT 6
CT11503A
COLUMBIA / DEOJAY
876391
14 THOMPSON HILL ROAD
COLUMBIA, CT 06237



PROPOSED TOWER
ELEVATION &
ANTENNA LAYOUT
PLAN

S-1

MANUFACTURER: RFS
 MODEL NO.: APXVAARR24_43-U-NA20
 COLOR: LIGHT GRAY
 DIMENSIONS (LxWxD): 95.9" x 24" x 8.7"
 2436mm x 609mm x 222mm
 WEIGHT (lbs): 58
 CONNECTOR: 8 x 4-3-10 FEMALE AT BOTTOM +
 6 AISG CONNECTORS (3 MALE/3 FEMALE)
 SURVIVAL/RATED WIND VELOCITY (KM/H): 241 (150)



MANUFACTURER: ERICSSON
 MODEL NO.: 4449 B71+B12
 COLOR: LIGHT GRAY
 DIMENSIONS (LxWxD): 14.9" x 13.19" x 9.25"
 378mm x 335mm x 235mm
 WEIGHT (lbs): 74



NOTE
 MOUNTING OPTIONS ARE INCLUDED PRODUCTS WITH ANTENNA PURCHASE

T-Mobile
 T-MOBILE NORTHEAST LLC
 103 MONARCH DRIVE
 LIVERPOOL, NY 13088

CROWN CASTLE
 3 CORPORATE PARK DRIVE
 SUITE 101
 CLIFTON PARK, NY 12065

JACOBS
 JACOBS ENGINEERING GROUP, INC.
 120 ST. JAMES AVENUE, 5TH FLOOR
 BOSTON, MA 02116

1 ANTENNA SPECIFICATIONS


SCALE: N.T.S.

2 RRUS SPECIFICATIONS

SCALE: N.T.S.


3 TITLE

SCALE: N.T.S.



NOTE
 ANTENNA NOT SHOWN FOR CLARITY.

MANUFACTURER: ERICSSON
 MODEL NO.: AIR32 KRD901146-1_B66A_B2A
 COLOR: LIGHT GRAY
 DIMENSIONS (LxWxD): 59.25" x 12.87" x 8.66"
 1505mm x 327mm x 220mm
 WEIGHT (lbs): 153
 69.4kg
 CONNECTOR: 7/16 IEC-169-4 INSERT TYPE
 CABLE CONNECTOR: 7/16 INSERT-TYPE ON BOTH ENDS
 MAX. WIND LOAD: @ 42m/s 900 N



4 TITLE

SCALE: N.T.S.

5 ANTENNA SPECIFICATIONS

SCALE: N.T.S.

6 DETAIL NOT USED

SCALE: N.T.S.



PROJECT NO: ERCC0004
 DRAWN BY: AJM
 CHECKED BY: CAT

SUBMITTALS		
1	08/21/19	ISSUED FOR CONSTRUCTION
0	07/17/19	ISSUED FOR PERMITTING

THIS DOCUMENT IS THE CREATION, DESIGN, PROPERTY AND COPYRIGHTED WORK OF T-MOBILE. ANY DUPLICATION OR USE WITHOUT EXPRESS WRITTEN CONSENT IS STRICTLY PROHIBITED. DUPLICATION AND USE BY GOVERNMENT AGENCIES FOR THE PURPOSES OF CONDUCTING THEIR LAWFULLY AUTHORIZED REGULATORY AND ADMINISTRATIVE FUNCTIONS IS SPECIFICALLY ALLOWED.

SPRINT COLUMBIA RT 6
 CT11503A
 COLUMBIA / DEOJAY
 876391
 14 THOMPSON HILL ROAD
 COLUMBIA, CT 06237

EQUIPMENT DETAILS

S-2

7 DETAIL NOT USED


SCALE: N.T.S.

8 DETAIL NOT USED

SCALE: N.T.S.

9 DETAIL NOT USED

SCALE: N.T.S.



PROJECT NO: ERCC0004

DRAWN BY: AJM

CHECKED BY: CAT

SUBMITTALS		
NO.	DATE	DESCRIPTION
1	08/21/19	ISSUED FOR CONSTRUCTION
0	07/17/19	ISSUED FOR PERMITTING




THIS DOCUMENT IS THE CREATION, DESIGN, PROPERTY AND COPYRIGHTED WORK OF T-MOBILE. ANY DUPLICATION OR USE WITHOUT EXPRESS WRITTEN CONSENT IS STRICTLY PROHIBITED. DUPLICATION AND USE BY GOVERNMENT AGENCIES FOR THE PURPOSES OF CONDUCTING THEIR LAWFULLY AUTHORIZED REGULATORY AND ADMINISTRATIVE FUNCTIONS IS SPECIFICALLY ALLOWED.

SPRINT COLUMBIA RT 6
CT11503A
COLUMBIA / DEOJAY
876391
14 THOMPSON HILL ROAD
COLUMBIA, CT 06237

MOUNT
DETAILS

S-3

PARTS LIST						
ITEM	QTY	PART NO.	PART DESCRIPTION	LENGTH	UNIT WT.	NET WT.
1	3	X-LWRM	RING MOUNT WELDMENT		68.81	206.42
2	3	X-TBW	T-BRACKET WELDMENT		13.60	40.80
3	6	X-254924	DIAGONAL ANGLE - SITE PRO 1	72 in	19.71	118.24
4	12	X-STU	STIFF ARM CHANNEL BRACKET	8 1/2 in	1.37	16.46
5	6	SHCM-T	CHAIN MOUNT TIGHTENER BRACKET	3 in	1.86	11.15
6	12	G12112	1/2" x 1-1/2" HDG HEX BOLT GR5	1/2 in	0.15	1.77
7	3	G12212	1/2" x 2-1/2" HDG HEX BOLT GR5	2 1/2 in	0.20	0.61
8	12	G12065	1/2" x 6-1/2" HDG HEX BOLT GR5 FULL THREAD	6 1/2 in	0.41	4.91
9	24	G12FW	1/2" HDG USS FLATWASHER	3/32 in	0.03	0.82
10	27	G12LW	1/2" HDG LOCKWASHER	1/8 in	0.01	0.38
11	27	G12NUT	1/2" HDG HEAVY 2H HEX NUT		0.07	1.93
12	12	A582114	5/8" x 2-1/4" HDG A325 HEX BOLT	2 1/4 in	0.31	3.75
13	9	G58R-24	5/8" x 24" THREADED ROD (HDG.)	24 in	0.40	3.59
13	9	G58R-48	5/8" x 48" THREADED ROD (HDG.)	48 in	0.40	3.59
14	30	G58LW	5/8" HDG LOCKWASHER		0.03	0.78
15	30	G58NUT	5/8" HDG HEAVY 2H HEX NUT		0.13	3.90
					TOTAL WT. #	642.04



TOLERANCE NOTES

TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE:
SAWED, SHEARED AND GAS CUT EDGES ($\pm 0.030"$)
DRILLED AND GAS CUT HOLES ($\pm 0.030"$) - NO CONING OF HOLES
LASER CUT EDGES AND HOLES ($\pm 0.010"$) - NO CONING OF HOLES
BENDS ARE $\pm 1/2$ DEGREE
ALL OTHER MACHINING ($\pm 0.030"$)
ALL OTHER ASSEMBLY ($\pm 0.060"$)

PROPRIETARY NOTE:
THE DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT INDUSTRIES AND CONSIDERED A TRADE SECRET. ANY USE OR DISCLOSURE WITHOUT THE CONSENT OF VALMONT INDUSTRIES IS STRICTLY PROHIBITED.

DESCRIPTION
HANDRAIL REINFORCEMENT KIT (LONG)

SITE PRO 1
A valmont COMPANY
Engineering Support Team:
1-888-753-7446
Locations:
New York, NY
Atlanta, GA
Los Angeles, CA
Plymouth, IN
Salem, OR
Dallas, TX

REV	DESCRIPTION OF REVISIONS	CPD	BY	DATE
A	CHANGED MAX. DIA. FOR HANDRAIL CONNECTION	SP1	BC	10/25/2017

CPD NO. SP1	DRAWN BY CSL3 2/23/2017	ENG. APPROVAL 3RD PARTY
CLASS 81	SUB 02	DRAWING USAGE SHOP
CHECKED BY BMC 9/8/2017		DWG. NO. PRK-SFS-L

PART NO. PRK-SFS-L	PAGE 1 OF 3
DWG. NO. PRK-SFS-L	



PROJECT NO: ERCC0004

DRAWN BY: AJM

CHECKED BY: CAT

SUBMITTALS		
REV	DATE	DESCRIPTION
1	08/21/19	ISSUED FOR CONSTRUCTION
0	07/17/19	ISSUED FOR PERMITTING




THIS DOCUMENT IS THE CREATION, DESIGN, PROPERTY AND COPYRIGHTED WORK OF T-MOBILE. ANY DUPLICATION OR USE WITHOUT EXPRESS WRITTEN CONSENT IS STRICTLY PROHIBITED. DUPLICATION AND USE BY GOVERNMENT AGENCIES FOR THE PURPOSES OF CONDUCTING THEIR LAWFULLY AUTHORIZED REGULATORY AND ADMINISTRATIVE FUNCTIONS IS SPECIFICALLY ALLOWED.

SPRINT COLUMBIA RT 6
CT11503A
COLUMBIA / DEOJAY
876391
14 THOMPSON HILL ROAD
COLUMBIA, CT 06237

MOUNT
DETAILS

S-4

VERTICAL POSITION



TOLERANCE NOTES

TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE:
SAWED, SHEARED AND GAS CUT EDGES (± 0.030 "")
DRILLED AND GAS CUT HOLES (± 0.030 "") - NO CONING OF HOLES
LASER CUT EDGES AND HOLES (± 0.010 "") - NO CONING OF HOLES
BENDS ARE $\pm 1/2$ DEGREE
ALL OTHER MACHINING (± 0.030 "")
ALL OTHER ASSEMBLY (± 0.060 "")

PROPRIETARY NOTE:
THE DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT INDUSTRIES AND CONSIDERED A TRADE SECRET. ANY USE OR DISCLOSURE WITHOUT THE CONSENT OF VALMONT INDUSTRIES IS STRICTLY PROHIBITED.

DESCRIPTION
HANDRAIL REINFORCEMENT KIT (LONG)

SITE PRO 1
Engineering Support Team: 1-888-753-7446
Locations: New York, NY; Atlanta, GA; Los Angeles, CA; Plymouth, IN; Salem, OR; Dallas, TX

REV	DESCRIPTION OF REVISIONS	CPD	BY	DATE
A	CHANGED MAX. DIA. FOR HANDRAIL CONNECTION	SP1	BC	10/25/2017

REVISION HISTORY

CPD NO.	DRAWN BY	ENG. APPROVAL
SP1	CSL3 2/23/2017	3RD PARTY
CLASS	DRAWING USAGE	CHECKED BY
81	SHOP	BMC 9/8/2017

PART NO.	DWG. NO.
PRK-SFS-L	PRK-SFS-L

PAGE
2 OF 3


67D92DB OUTDOOR - TOWER TOP EQUIPMENT SCHEDULE (RE: CT11503A_P_RFDS_L600)													
ANTENNA NUMBER (FROM L TO R)	ANTENNA MODEL	ANTENNA AZIMUTH	MECH. TILT	ELEC. TILT	ANTENNA CENTERLINE FROM GROUND	TMA/RRUS MODEL	TMA/RRUS QUANTITY	COAX/HYBRID CABLE			JUMPERS		
								SIZE/TYPE	QUANTITY	LENGTH	TYPE	QTY	LENGTH
A1	AIR21 KRC118023-1_B2A_B4P	60°	0°	2°	160'	TWIN STYLE 3CX-PCS/AWS3+600/700BP TMA	1	1-5/8" COAX	2	240'	FIBER	2	10'
A2	APXVAARR24_43-U-NA20	60°	0°	2°	160'	RADIO 4449 B71+B12	1	6x12 HCS	1	240'	COAX FIBER	4 1	10' 10'
A3	AIR32 KRD901146-1_B66A_B2A	60°	0°	2°	160'	-	-	-	-	-	FIBER	2	10'
B1	AIR21 KRC118023-1_B2A_B4P	180°	0°	2°	160'	TWIN STYLE 3CX-PCS/AWS3+600/700BP TMA	1	1-5/8" COAX	2	240'	FIBER	2	10'
B2	APXVAARR24_43-U-NA20	180°	0°	2°	160'	RADIO 4449 B71+B12	1	6x12 HCS	1	240'	COAX FIBER	4 1	10' 10'
B3	AIR32 KRD901146-1_B66A_B2A	180°	0°	2°	160'	-	-	-	-	-	FIBER	2	10'
C1	AIR21 KRC118023-1_B2A_B4P	300°	0°	2°	160'	TWIN STYLE 3CX-PCS/AWS3+600/700BP TMA	1	1-5/8" COAX	2	240'	FIBER	2	10'
C2	APXVAARR24_43-U-NA20	300°	0°	2°	160'	RADIO 4449 B71+B12	1	6x12 HCS	1	240'	COAX FIBER	4 1	10' 10'
C3	AIR32 KRD901146-1_B66A_B2A	300°	0°	2°	160'	-	-	-	-	-	FIBER	2	10'

NOTES:

- EQUIPMENT LISTED IN **BOLD**, DELINEATES THAT THE EQUIPMENT IS PROPOSED

1 EQUIPMENT INFORMATION CHART

SCALE: NONE



EQUIPMENT NOTES:

- THE HYBRID CABLE LENGTH SHOW IS ONLY AN ESTIMATE AND SHOULD NOT BE USED FOR ORDERING MATERIALS. CONFIRM THE REQUIRED HYBRID CABLE LENGTH WITH T-MOBILE PRIOR TO ORDERING OR INSTALLATION.
- THE CONTRACTOR SHALL TEST THE OPTICAL FIBER AFTER INSTALLATION IN ACCORDANCE WITH T-MOBILE STANDARDS AND SUPPLY THE RESULTS TO T-MOBILE.
- THE CONTRACTOR SHALL CONFIRM THE TOWER TOP EQUIPMENT LIST ABOVE WITH THE FINAL T-MOBILE RFDS PRIOR TO INSTALLATION.
- ALL EXISTING AND PROPOSED ANTENNA CABLES SHALL BE COLOR CODED PER T-MOBILE STANDARDS.
- REFER TO EQUIPMENT INSTALLATION STANDARDS FOR ADDITIONAL INFORMATION.
- REFER TO EQUIPMENT MANUFACTURER'S SPECIFICATION SHEETS FOR ADDITIONAL INFORMATION NOT LISTED ABOVE.

67D92DB OUTDOOR - TOWER LOADING SUMMARY				
EQUIPMENT TYPE	EXISTING QUANTITY	QUANTITY REMOVED	QUANTITY ADDED	TOTAL QUANTITY
PANEL ANTENNA	6	3	6	9
COAX CABLE	6	0	0	6
HYBRID CABLE	1	0	3	4
FIBER JUMPER	0	0	15	15
COAX JUMPER	6	6	12	12
TMA	3	0	0	3
RADIO	3	3	3	3

2 ANTENNA KEY

SCALE: NONE

3 ANTENNA & CABLE SCHEDULE

SCALE: NONE



T-MOBILE NORTHEAST LLC
103 MONARCH DRIVE
LIVERPOOL, NY 13088



3 CORPORATE PARK DRIVE
SUITE 101
CLIFTON PARK, NY 12065



120 ST. JAMES AVENUE, 5TH FLOOR
BOSTON, MA 02116



PROJECT NO: ERCC0004

DRAWN BY: AJM

CHECKED BY: CAT

SUBMITTALS		
NO.	DATE	DESCRIPTION
1	08/21/19	ISSUED FOR CONSTRUCTION
0	07/17/19	ISSUED FOR PERMITTING


THIS DOCUMENT IS THE CREATION, DESIGN, PROPERTY AND COPYRIGHTED WORK OF T-MOBILE. ANY DUPLICATION OR USE WITHOUT EXPRESS WRITTEN CONSENT IS STRICTLY PROHIBITED. DUPLICATION AND USE BY GOVERNMENT AGENCIES FOR THE PURPOSES OF CONDUCTING THEIR LAWFULLY AUTHORIZED REGULATORY AND ADMINISTRATIVE FUNCTIONS IS SPECIFICALLY ALLOWED.

SPRINT COLUMBIA RT 6
CT11503A
COLUMBIA / DEOJAY
876391
14 THOMPSON HILL ROAD
COLUMBIA, CT 06237

ANTENNA
INFORMATION CHART

RF-1

SITE CONFIGURATION: 67D92DB OUTDOOR



T-MOBILE NORTHEAST LLC
103 MONARCH DRIVE
LIVERPOOL, NY 13088



3 CORPORATE PARK DRIVE
SUITE 101
CLIFTON PARK, NY 12065



120 ST. JAMES AVENUE, 5TH FLOOR
BOSTON, MA 02116



PROJECT NO: ERCC0004

DRAWN BY: AJM

CHECKED BY: CAT

SUBMITTALS		
NO.	DATE	DESCRIPTION
1	08/21/19	ISSUED FOR CONSTRUCTION
0	07/17/19	ISSUED FOR PERMITTING

THIS DOCUMENT IS THE CREATION, DESIGN, PROPERTY AND COPYRIGHTED WORK OF T-MOBILE. ANY DUPLICATION OR USE WITHOUT EXPRESS WRITTEN CONSENT IS STRICTLY PROHIBITED. DUPLICATION AND USE BY GOVERNMENT AGENCIES FOR THE PURPOSES OF CONDUCTING THEIR LAWFULLY AUTHORIZED REGULATORY AND ADMINISTRATIVE FUNCTIONS IS SPECIFICALLY ALLOWED.

SPRINT COLUMBIA RT 6
CT11503A
COLUMBIA / DEOJAY
876391
14 THOMPSON HILL ROAD
COLUMBIA, CT 06237

RF EQUIPMENT SCHEMATIC


RF-2

ONE LINE DIAGRAM NOTES:

1. ELECTRICAL SERVICE SHALL BE 200A, 240/120V, 1Ø, 3W
2. FOR COMPLETE INTERNAL WIRING AND ARRANGEMENT, REFER TO VENDOR PRINTS PROVIDED BY EQUIPMENT MANUFACTURER.

NOTES:

1. CONTRACTOR SHALL VERIFY AVAILABLE FAULT CURRENT WITH POWER COMPANY AND ENSURE ALL ELECTRICAL EQUIPMENT IS SUITABLE FOR AVAILABLE FAULT CURRENT.
2. CONTRACTOR SHALL COORDINATE UTILITY SERVICES WITH LOCAL UTILITY COMPANIES. VERIFY ALL REQUIREMENTS WITH UTILITY COMPANY STANDARDS.
3. ONE-LINE DIAGRAM IS SCHEMATIC ONLY AND NOT INDICATIVE OF ACTUAL EQUIPMENT LAYOUT.
4. CONTRACTOR SHALL LABEL METER SOCKET WITH SERVICE OWNER NAMEPLATE W/ 1/2" MINIMUM LETTERS.



T-MOBILE NORTHEAST LLC
103 MONARCH DRIVE
LIVERPOOL, NY 13088



3 CORPORATE PARK DRIVE
SUITE 101
CLIFTON PARK, NY 12065



JACOBS ENGINEERING GROUP, INC.
120 ST. JAMES AVENUE, 5TH FLOOR
BOSTON, MA 02116



PROJECT NO: ERCC0004

DRAWN BY: AJM

CHECKED BY: CAT


SUBMITTALS		
1	08/21/19	ISSUED FOR CONSTRUCTION
0	07/17/19	ISSUED FOR PERMITTING

THIS DOCUMENT IS THE CREATION, DESIGN, PROPERTY AND COPYRIGHTED WORK OF T-MOBILE. ANY DUPLICATION OR USE WITHOUT EXPRESS WRITTEN CONSENT IS STRICTLY PROHIBITED. DUPLICATION AND USE BY GOVERNMENT AGENCIES FOR THE PURPOSES OF CONDUCTING THEIR LAWFULLY AUTHORIZED REGULATORY AND ADMINISTRATIVE FUNCTIONS IS SPECIFICALLY ALLOWED.

SPRINT COLUMBIA RT 6
CT11503A
COLUMBIA / DEOJAY
876391
14 THOMPSON HILL ROAD
COLUMBIA, CT 06237

ONE LINE
DIAGRAM

E-1



- NOTES:**
1. ATTACH GROUND BAR DIRECTLY TO THE TOWER USING STANDARD ADAPTER.
 2. VERIFY NUMBER OF CABLES/TMAS PER T-MOBILE RF CONFIGURATION.

- GROUNDING NOTES:**
1. BELOW GROUND ALL GROUNDING CONDUCTORS TO BE #2 AWG SOLID TINNED BARE COPPER WIRE (BCW) U.O.N.
 2. ABOVE GROUND ALL GROUNDING CONDUCTORS TO BE #2 AWG STRANDED INSULATED COPPER WIRE U.O.N.
 3. PROVIDE BONDING AND GROUNDING CONDUCTORS WITH GREEN TYPE THWN INSULATION, U.O.N.
 4. LEAVE 4' EXCESS GROUND WIRE COILED UP ABOVE GRADE. SEAL/WEATHERPROOF CONDUIT.

T-Mobile
 T-MOBILE NORTHEAST LLC
 103 MONARCH DRIVE
 LIVERPOOL, NY 13088

CROWN CASTLE
 3 CORPORATE PARK DRIVE
 SUITE 101
 CLIFTON PARK, NY 12065

JACOBS
 JACOBS ENGINEERING GROUP, INC.
 120 ST. JAMES AVENUE, 5TH FLOOR
 BOSTON, MA 02116



PROJECT NO: ERCC0004
 DRAWN BY: AJM
 CHECKED BY: CAT

SUBMITTALS		
NO.	DATE	DESCRIPTION
1	08/21/19	ISSUED FOR CONSTRUCTION
0	07/17/19	ISSUED FOR PERMITTING

THIS DOCUMENT IS THE CREATION, DESIGN, PROPERTY AND COPYRIGHTED WORK OF T-MOBILE. ANY DUPLICATION OR USE WITHOUT EXPRESS WRITTEN CONSENT IS STRICTLY PROHIBITED. DUPLICATION AND USE BY GOVERNMENT AGENCIES FOR THE PURPOSES OF CONDUCTING THEIR LAWFULLY AUTHORIZED REGULATORY AND ADMINISTRATIVE FUNCTIONS IS SPECIFICALLY ALLOWED.

SPRINT COLUMBIA RT 6
 CT11503A
 COLUMBIA / DEOJAY
 876391
 14 THOMPSON HILL ROAD
 COLUMBIA, CT 06237

GROUNDING RISER
 DIAGRAM

G-1

TABLE OF CONTENTS

1) INTRODUCTION

2) ANALYSIS CRITERIA

Table 1 - Proposed Equipment Configuration

3) ANALYSIS PROCEDURE

Table 2 - Documents Provided

3.1) Analysis Method

3.2) Assumptions

4) ANALYSIS RESULTS

Table 3 - Mount Component Capacity

4.1) Recommendations

5) STANDARD CONDITIONS

6) APPENDIX A

WIRE FRAME AND RENDERED MODELS

7) APPENDIX B

SOFTWARE INPUT CALCULATIONS

8) APPENDIX C

SOFTWARE ANALYSIS OUTPUT

9) APPENDIX D

SUPPLEMENTAL MODIFICATION INFORMATION

10) APPENDIX E

MANUFACTURER DRAWINGS (FOR REFERENCE ONLY)

1) INTRODUCTION

The existing mount under consideration is (1) 12.5' Platform mount mapped by RKS on 04/01/2019.

2) ANALYSIS CRITERIA

TIA-222 Revision: TIA-222-H
Risk Category: II
Ultimate Wind Speed: 130 mph
Exposure Category: C
Topographic Factor at Base: 1.000
Topographic Factor at Mount: 1.000
Ice Thickness: 1.5 in
Wind Speed with Ice: 50 mph
Live Loading Wind Speed: 30 mph
Man Live Load at Mid/End-Points: 250 lb
Man Live Load at Mount Pipes: 500 lb

Table 1 - Proposed Equipment Configuration

Mount Centerline (ft)	Antenna Centerline (ft)	Number of Antennas	Antenna Manufacturer	Antenna Model	Mount / Modification Details
161	162	3	Ericsson	KRY 112 144/2	(1) 12.5' Platform
	161	3	Ericsson	AIR 32 B2A B66AA	
		3	Ericsson	ERICSSON AIR 21 B2A B4P	
		3	RFS/Celwave	APXVAARR24_43-U-NA20	
		3	Ericsson	RADIO 4449 B12/B71	

3) ANALYSIS PROCEDURE

Table 2 - Documents Provided

Document	Remarks	Reference	Source
Mount Mapping	876391 Dated: 04/22/2019	8352757	CCISites
Order	ID: 479837 Rev. 1 Dated: 04/15/2019	-	CCISites

3.1) Analysis Method

RISA-3D (version 17.0.2), a commercially available analysis software package, was used to create a three-dimensional model of the tower and calculate member stresses for various loading cases.

This analysis was performed in accordance with Crown Castle's ENG-SOW-10208 *Tower Mount Analysis* (Revision C).

3.2) Assumptions

- 1) *The analysis of the existing tower or the effect of the mount attachment to the tower is not within the current scope of work.*
- 2) *The antenna mounting system was properly fabricated, installed and maintained in good condition, twist free and plumb in accordance with its original design and manufacturer's specifications and all bolts are tightened as specified by the manufacturer and AISC requirements.*
- 3) *The configuration of antennas, mounts, and other appurtenances are as specified in Table 1.*
- 4) *All member connections have been designed to meet or exceed the load carrying capacity of the connected member unless otherwise specified in this report. All U-Bolt connections have been properly tightened. This analysis will be required to be revised if the existing conditions in the field differ from those shown in the above referenced documents or assumed in this analysis. No allowance was made for any damaged, missing, or rusted members.*
- 5) *Steel grades are as follows, unless noted otherwise:*

a) Channel, Solid Round, Angle, Plate, Unistrut	ASTM A36 (GR 36)
b) Pipe	ASTM A53 (GR 35)
c) HSS (Rectangular)	ASTM 500 (GR B-46)
d) HSS (Round)	ASTM 500 (GR B-42)
e) Threaded Rods	ASTM F1554 (GR 36)
f) Connection Bolts	ASTM A325
g) U-Bolts	SAE J429 (GR 2)
- 6) *Proposed equipment is to be installed in the locations specified in Appendix A. Any changes to the proposed equipment locations will render this report invalid.*
- 7) *Existing mount pipes will be replaced with 8-ft tall x P2.5 STD (2.88" O.D. x 0.189") pipes to accommodate the proposed antennas where required*

This analysis may be affected if any assumptions are not valid or have been made in error. Paul J Ford and Company should be notified to determine the effect on the structural integrity of the mount.

4) ANALYSIS RESULTS

Table 3- Mount Component Capacity

Notes	Component	Elevation (ft)	% Capacity	Pass / Fail
1	Face Horizontals	161	29.3	Pass
1	Bracing Members		31.1	Pass
1	Grating Support Members		26.0	Pass
1	Standoff Members		18.9	Pass
1	Ring Plate		Sufficient	
1	Corner Plates		46.0	Pass
1	Mount Pipes		54.9	Pass
1	Mount to Tower Connection		21.7	Pass

Mount Rating (max from all components) =	54.9%
---	--------------

Notes:

- 1) See additional documentation in "Appendix C – Software Analysis Output" for calculations supporting the % capacity consumed.

4.1) Recommendations

The mount has sufficient capacity to carry the proposed loading configuration. In order for the results of the analysis to be considered valid, the structural modifications listed below must be completed.

- Install SitePro1 PRK-SFS-L Platform Reinforcement Kit or EOR approved equivalent as indicated in "Appendix D – Supplemental Modification Information" and in conformance with the attached manufacturer drawings.
- Install RFS/Celwave APXVAARR24_43-U-NA20 antennas on 8-ft long, P2.5 STD (2.88" O.D. x 0.189) mount pipes. See Appendix D details.



Connection from the mount to the tower and local stresses on the tower are sufficient.

**STANDARD CONDITIONS FOR FURNISHING OF PROFESSIONAL ENGINEERING
SERVICES ON EXISTING MOUNTS BY PAUL J. FORD AND COMPANY**

- 1) It is the responsibility of the client to ensure that the information provided to Paul J. Ford and Company is accurate and complete. Paul J. Ford and Company will rely on the accuracy and completeness of such information in performing or furnishing services under this project.
- 2) If the existing conditions are not as represented on the referenced drawings and/or documents, Paul J. Ford and Company should be contacted immediately to evaluate the significance of the deviation.
- 3) The mount has been analyzed according to the minimum design loads recommended by the Reference Standard. If additional design loads are required, Paul J. Ford and Company should be made aware of this prior to the start of the project.
- 4) The standard of care for all Professional Engineering Services performed or furnished by Paul J. Ford and Company under this project will be the skill and care used by members of the Consultant's profession practicing under similar circumstances at the same time and in the same locality.
- 5) All Services are performed, results obtained, and recommendations made in accordance with generally accepted engineering principles and practices. Paul J. Ford and Company is not responsible for the conclusions, opinions and/or recommendations made by others based on the information supplied herein.

APPENDIX A

WIRE FRAME AND RENDERED MODELS



Proposed: (typical)
(1) Ericsson AIR 32 B2A B66AA
(1) Ericsson RADIO 4449 B12/B71

Proposed: (Typical)
(1) RFS/Celwave APXVAARR24_43-U-NA-20

Envelope Only Solution

Paul J. Ford & Company
SPC
37519-1593.003.7191

BU 876391 / Columbia/Deojay

SK - 2
June 18, 2019 at 11:10 AM
37519-1593.003.7191_WindLoad.r...

APPENDIX B


SOFTWARE INPUT CALCULATION

ASCE 7 Hazards Report

Address:
No Address at This Location

Standard: ASCE/SEI 7-10
Risk Category: II
Soil Class: D - Stiff Soil

Elevation: 560.51 ft (NAVD 88)
Latitude: 41.717622
Longitude: -72.299747



Wind

Results:

Wind Speed:	127 Vmph
10-year MRI	78 Vmph
25-year MRI	88 Vmph
50-year MRI	95 Vmph
100-year MRI	104 Vmph

Data Source: ASCE/SEI 7-10, Fig. 26.5-1A and Figs. CC-1–CC-4, incorporating errata of March 12, 2014

Date Accessed: Tue Apr 30 2019

Value provided is 3-second gust wind speeds at 33 ft above ground for Exposure C Category, based on linear interpolation between contours. Wind speeds are interpolated in accordance with the 7-10 Standard. Wind speeds correspond to approximately a 7% probability of exceedance in 50 years (annual exceedance probability = 0.00143, MRI = 700 years).

Site is in a hurricane-prone region as defined in ASCE/SEI 7-10 Section 26.2. Glazed openings need not be protected against wind-borne debris.



Mountainous terrain, gorges, ocean promontories, and special wind regions should be examined for unusual wind conditions.

Site Soil Class: D - Stiff Soil

Results:

S_s :	0.175	S_{DS} :	0.187
S_1 :	0.062	S_{D1} :	0.1
F_a :	1.6	T_L :	6
F_v :	2.4	PGA :	0.088
S_{MS} :	0.28	PGA _M :	0.14
S_{M1} :	0.15	F _{PGA} :	1.6
		I_e :	1

Seismic Design Category B



Data Accessed:

Tue Apr 30 2019

Date Source:

USGS Seismic Design Maps based on ASCE/SEI 7-10, incorporating Supplement 1 and errata of March 31, 2013, and ASCE/SEI 7-10 Table 1.5-2. Additional data for site-specific ground motion procedures in accordance with ASCE/SEI 7-10 Ch. 21 are available from USGS.

Ice

Results:

Ice Thickness: 0.75 in.

Concurrent Temperature: 5 F

Gust Speed: 50 mph

Data Source: Standard ASCE/SEI 7-10, Figs. 10-2 through 10-8

Date Accessed: Tue Apr 30 2019

Ice thicknesses on structures in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.

Values provided are equivalent radial ice thicknesses due to freezing rain with concurrent 3-second gust speeds, for a 50-year mean recurrence interval, and temperatures concurrent with ice thicknesses due to freezing rain. Thicknesses for ice accretions caused by other sources shall be obtained from local meteorological studies. Ice thicknesses in exposed locations at elevations higher than the surrounding terrain and in valleys and gorges may exceed the mapped values.




The ASCE 7 Hazard Tool is provided for your convenience, for informational purposes only, and is provided “as is” and without warranties of any kind. The location data included herein has been obtained from information developed, produced, and maintained by third party providers; or has been extrapolated from maps incorporated in the ASCE 7 standard. While ASCE has made every effort to use data obtained from reliable sources or methodologies, ASCE does not make any representations or warranties as to the accuracy, completeness, reliability, currency, or quality of any data provided herein. Any third-party links provided by this Tool should not be construed as an endorsement, affiliation, relationship, or sponsorship of such third-party content by or from ASCE.

ASCE does not intend, nor should anyone interpret, the results provided by this Tool to replace the sound judgment of a competent professional, having knowledge and experience in the appropriate field(s) of practice, nor to substitute for the standard of care required of such professionals in interpreting and applying the contents of this Tool or the ASCE 7 standard.

In using this Tool, you expressly assume all risks associated with your use. Under no circumstances shall ASCE or its officers, directors, employees, members, affiliates, or agents be liable to you or any other person for any direct, indirect, special, incidental, or consequential damages arising from or related to your use of, or reliance on, the Tool or any information obtained therein. To the fullest extent permitted by law, you agree to release and hold harmless ASCE from any and all liability of any nature arising out of or resulting from any use of data provided by the ASCE 7 Hazard Tool.



APPENDIX C

SOFTWARE ANALYSIS OUTPUT



Member Code Checks Displayed (Enveloped)
Envelope Only Solution

Paul J. Ford & Company	BU 876391 / Columbia/Deojay	SK - 3
SPC		June 18, 2019 at 11:18 AM
37519-1593.003.7191		37519-1593.003.7191_WindLoad.r...



Envelope Only Solution

Paul J. Ford & Company

SPC



37519-1593.003.7191

BU 876391 / Columbia/Deojay

SK - 5


June 18, 2019 at 11:20 AM

37519-1593.003.7191_WindLoad.r...



Loads: BLC 1, Dead
Envelope Only Solution

Paul J. Ford & Company	BU 876391 / Columbia/Deojay	SK - 7
SPC		June 18, 2019 at 11:22 AM
37519-1593.003.7191		37519-1593.003.7191_WindLoad.r...



Results for LC 25, 1.2 D + 1.0 Di + 1.0 Wi @ 300

Paul J. Ford & Company	BU 876391 / Columbia/Deojay	SK - 8
SPC		June 18, 2019 at 11:24 AM
37519-1593.003.7191		37519-1593.003.7191_WindLoad.r...

fl `cVUL'A cXY`GYH]b[g

Óä æ Á ^ & cā } • Á Á ^ { } á ^ Á Ó æ & •	Í Á
T æ Á Ó c } æ Á ^ & cā } • Á Á ^ { } á ^ Á Ó æ & •	J Í Á
Q & ~ á ^ Á Ú @ æ Á Ó ^ - { } æ á } N	Y ^ •
Q & ^ æ ^ Á æ á } * Á Ó æ æ á c Á Á Y á á N	Y ^ •
Q & ~ á ^ Á Y æ } á * N	Y ^ •
V æ • Á æ Á Ó c } Á Ó c • ^ & cā } * Á Y [[] á Á Y æ] N	Y ^ •
CE ^ æ S æ Á ^ • @ Á á C D	F I I
T ^ * ^ Á ^ æ } & ^ Á á D	É G
U É D cæ Á æ } • á Á ^ æ } &	É É É Á
Q & ~ á ^ Á U É D cæ Á Á Y æ } • N	Y ^ •
CE { } { } æ á æ ^ Á c æ Á Ú cā } ^ • • Á Á Y æ } • N	Y ^ •
T æ Á Ó æ á } • Á Á Y æ Á Ú cā } ^ • •	H
Ó æ á c Á Ó B & ^ ^ æ á } Á á D ^ & á C D	H Í É
Y æ Á ^ • @ Ú á ^ Á á D	G
Ó ä ^ } • { } cā } Á Ó } c ^ * ^ } & ^ Á É F É D É D	I
X ^ cæ á Á c á	Y
Ó [] á æ Á ^ { } á ^ Á Ú á } cæ á } Á Ú æ ^	Y Z
U cæ á Á c ^	U æ ^ Á Ó B & ^ ^ æ á
Ó ^ } æ á Á Ú c ^	Ó B & ^ ^ æ á Á Ú c ^

P [c Á á á Á Ú c ^ Á Ó á ^	Ó Ú Ó Á F I c @ H Í É É I D S U Ó
Ó ä b • Á Ú cā } ^ • • N	Y ^ • @ æ á ^ D
U Ó Ú Ó } } ^ & cā } Á Ó á ^	P [] ^
Ó [] á á Á { } ^ á á Á Ú c ^ Á Ó á ^	P [] ^
Y [[] á Á Ó á ^	P [] ^
Y [[] á Á ^ { }] ^ æ ^ ^	L F É É Ø
Ó } & ^ c Á Ó á ^	P [] ^
T æ [] ^ Á Ó á ^	P [] ^
Ó { } á ~ { } Á Ó á ^	P [] ^ Á Ó á á á *
U cæ á ^ • • Á Ú c ^ Á Ó á ^	Ó Ú Ó Á F I c @ H Í É É I D S U Ó
Ó ä b • Á Ú cā } ^ • • N	Y ^ • @ æ á ^ D

P ^ { } á ^ Á - Á Ú @ æ Á Ú ^ * á } •	I
U ^ * á } Á Ú æ á } * Á Ó & ^ { } ^ } c á D	I
Ó ä cæ á Á Ó { } } Á ^ c @ á	Ó cæ á Ó c ^ æ á }
U æ { } ^ Á Ó cæ á cæ á Á Ú Ó É D	É I
Ó [] } & ^ c Á Ú c ^ • • Á Ó [] &	U ^ & cæ } * æ
W ^ Á Ó æ á ^ á Á ^ & cā } • N	Y ^ •
W ^ Á Ó æ á ^ á Á ^ & cā } • Á Ú æ á N	Y ^ •
Ó ä á Á c á } á * Á Y æ } á * N	P []
W ^ • ^ á Á Ó & ^ Á Y æ } á * N	Y ^ •
T á F Á Ó c Á Ó æ á É Á Ú æ á } * N	P []
Ó [] } & ^ c Á Ú ^ á á Á Ú c	Ú Ó Ó É Ú ^ Ú Ó V ^ Ó É V T Ó É F I
T á Á Á Ú c ^ Á Á Ó { } }	F
T æ Á Á Á Ú c ^ Á Á Ó { } }	I

PJF PAUL J. FORD & COMPANY

250 E Broad St, Ste 600 • Columbus, OH 43215
 Phone 614.221.6679 www.pauljford.com

Project # **A37519-1593.003.7191**

By **SPC**

Date: 06/18/19

v0.1, Effective 07/10/18

MOUNT TO TOWER CONNECTION CHECKS

REACTIONS - LC9 N5840A

Px=	2.60792	Kip
Py=	0.26812	Kip
(Axial)Pz=	0.19607	Kip
Mx=	5.576	Kip-in
My=	31.586	Kip-in
(Torque)Mz=	4.618	Kip-in
Number of Bolts	=	4
Plate Size	b=	10 in
	d=	10 in
Edge distance for Bolts	=	1.5 in
Bolt group centroid y-coordinate, Yc		5 in
Bolt group centroid x-coordinate, Xc		5 in
Load eccentricity in x-direction, ex		0 in
Load eccentricity in y-direction, ey		0 in
Total Moment including load eccentricity ΣM_x =	5.576	Kips-in
Total Moment including load eccentricity ΣM_y =	31.586	Kips-in
Total Moment including load eccentricity ΣM_z =	4.618	Kips-in

BOLT CHECKS

Tension Reaction	2.70	kip
Shear Reaction	0.85	kip
Bolt Type	A325N	
Bolt Diameter	0.625	in
Tensile Strength	20.7	kips
Shear Strength	12.4	kips
Reduced Tensile Strength	-	kips
Tensile Capacity Used	13.1%	
Shear Capacity Used	6.8%	


Note: Tension reduction not required if tension or shear capacity < 30%

WELD CHECKS


Standoff Member Type	=	Square
Width	=	4 in
Depth (only for square members) =		4 in
Assumed Weld Size	=	0.3750
Total Forces in X direction =		0.434 kips
Total Forces in Y direction =		0.142 kips
Total Forces in Z direction =		1.75 kips
Resultant =		1.81 kips
$\Phi * F_w$ (Kip/in)/16" weld =		1.392
Capacity used		21.70%

APPENDIX D

SUPPLEMENTAL MODIFICATION INFORMATION



(3) 8' Long P2.5 STD
Mount Pipes (typical
1 per sector)



SitePro1 PRK-SFS-L

Envelope Only Solution

Paul J. Ford & Company

SPC


37519-1593.003.7191

BU 876391 / Columbia/Deojay

SK - 9

June 19, 2019 at 9:25 AM

37519-1593.003.7191_WindLoad.r...






Envelope Only Solution

Paul J. Ford & Company	BU 876391 / Columbia/Deojay	SK - 10
SPC		June 18, 2019 at 11:36 AM
37519-1593.003.7191		37519-1593.003.7191_WindLoad.r...

APPENDIX E

MANUFACTURER DRAWINGS (FOR REFERENCE ONLY)

PARTS LIST						
ITEM	QTY	PART NO.	PART DESCRIPTION	LENGTH	UNIT WT.	NET WT.
1	3	X-LWRM	RING MOUNT WELDMENT		68.81	206.42
2	3	X-TBW	T-BRACKET WELDMENT		13.60	40.80
3	6	X-254924	DIAGONAL ANGLE - SITE PRO 1	72 in	19.71	118.24
4	12	X-STU	STIFF ARM CHANNEL BRACKET	8 1/2 in	1.37	16.46
5	6	SHCM-T	CHAIN MOUNT TIGHTENER BRACKET	3 in	1.86	11.15
6	12	G12112	1/2" x 1-1/2" HDG HEX BOLT GR5	1/2 in	0.15	1.77
7	3	G12212	1/2" x 2-1/2" HDG HEX BOLT GR5	2 1/2 in	0.20	0.61
8	12	G12065	1/2" x 6-1/2" HDG HEX BOLT GR5 FULL THREAD	6 1/2 in	0.41	4.91
9	24	G12FW	1/2" HDG USS FLATWASHER	3/32 in	0.03	0.82
10	27	G12LW	1/2" HDG LOCKWASHER	1/8 in	0.01	0.38
11	27	G12NUT	1/2" HDG HEAVY 2H HEX NUT		0.07	1.93
12	12	A582114	5/8" x 2-1/4" HDG A325 HEX BOLT	2 1/4 in	0.31	3.75
13	9	G58R-24	5/8" x 24" THREADED ROD (HDG.)	24 in	0.40	3.59
13	9	G58R-48	5/8" x 48" THREADED ROD (HDG.)	48 in	0.40	3.59
14	30	G58LW	5/8" HDG LOCKWASHER		0.03	0.78
15	30	G58NUT	5/8" HDG HEAVY 2H HEX NUT		0.13	3.90
					TOTAL WT. #	642.04



REV	DESCRIPTION OF REVISIONS	CPD	BY	DATE
A	CHANGED MAX. DIA. FOR HANDRAIL CONNECTION	SP1	BC	10/25/2017

REVISION HISTORY


TOLERANCE NOTES

TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE:
 SAWED, SHEARED AND GAS CUT EDGES ($\pm 0.030''$)
 DRILLED AND GAS CUT HOLES ($\pm 0.030''$) - NO CONING OF HOLES
 LASER CUT EDGES AND HOLES ($\pm 0.010''$) - NO CONING OF HOLES
 BENDS ARE $\pm 1/2$ DEGREE
 ALL OTHER MACHINING ($\pm 0.030''$)
 ALL OTHER ASSEMBLY ($\pm 0.060''$)



PROPRIETARY NOTE:
 THE DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT INDUSTRIES AND CONSIDERED A TRADE SECRET. ANY USE OR DISCLOSURE WITHOUT THE CONSENT OF VALMONT INDUSTRIES IS STRICTLY PROHIBITED.

DESCRIPTION			
HANDRAIL REINFORCEMENT KIT (LONG)			
CPD NO.	DRAWN BY	ENG. APPROVAL	
SP1	CSL3 2/23/2017	3RD PARTY	
CLASS	SUB	DRAWING USAGE	CHECKED BY
81	02	SHOP	BMC 9/8/2017

 A valmont COMPANY	Engineering Support Team: 1-888-753-7446	Locations: New York, NY Atlanta, GA Los Angeles, CA Plymouth, IN Salem, OR Dallas, TX
	PART NO. PRK-SFS-L	
DWG. NO. PRK-SFS-L		1 OF 3 <small>PAGE</small>



VERTICAL POSITION




REV	DESCRIPTION OF REVISIONS	CPD	BY	DATE
A	CHANGED MAX. DIA. FOR HANDRAIL CONNECTION	SP1	BC	10/25/2017
REVISION HISTORY				

TOLERANCE NOTES

TOLERANCES ON DIMENSIONS, UNLESS OTHERWISE NOTED ARE:
 SAWED, SHEARED AND GAS CUT EDGES ($\pm 0.030"$)
 DRILLED AND GAS CUT HOLES ($\pm 0.030"$) - NO CONING OF HOLES
 LASER CUT EDGES AND HOLES ($\pm 0.010"$) - NO CONING OF HOLES
 BENDS ARE $\pm 1/2$ DEGREE
 ALL OTHER MACHINING ($\pm 0.030"$)
 ALL OTHER ASSEMBLY ($\pm 0.060"$)

PROPRIETARY NOTE:
 THE DATA AND TECHNIQUES CONTAINED IN THIS DRAWING ARE PROPRIETARY INFORMATION OF VALMONT INDUSTRIES AND CONSIDERED A TRADE SECRET. ANY USE OR DISCLOSURE WITHOUT THE CONSENT OF VALMONT INDUSTRIES IS STRICTLY PROHIBITED.

DESCRIPTION			
HANDRAIL REINFORCEMENT KIT (LONG)			
CPD NO.	DRAWN BY	ENG. APPROVAL	
SP1	CSL3 2/23/2017	3RD PARTY	
CLASS	SUB	DRAWING USAGE	CHECKED BY
81	02	SHOP	BMC 9/8/2017

 A valmont COMPANY	Engineering Support Team: 1-888-753-7446	Locations: New York, NY Atlanta, GA Los Angeles, CA Plymouth, IN Salem, OR Dallas, TX
	PART NO.	PRK-SFS-L
DWG. NO.	PRK-SFS-L	