

November 25, 2014

**VIA OVERNIGHT DELIVERY**

Hon. Robert Stein, Chairman  
and Members of the Connecticut Siting Council  
10 Franklin Square  
New Britain, CT 06051

Re: New Cingular Wireless PCS, LLC ("AT&T")  
Petition for a Declaratory Ruling  
200 Edgemark Acres, Meriden, Connecticut

Dear Chairman Stein and Members of the Council:

On behalf of New Cingular Wireless PCS, LLC (AT&T), we respectfully enclose an original and (15) fifteen copies of a Petition for a Declaratory Ruling that no Certificate of Environmental Compatibility and Public Need is required to add a wireless communications facility to an existing Connecticut Light & Power transmission tower at 200 Edgemark Acres, Meriden, Connecticut. The enclosed Petition is dated November 25, 2014. Also enclosed is a CD containing an electronic version of the Petition and attachments.

Accompanying the Petition please find four copies of the Structural Analysis prepared by Centek Engineering. A check payable to the "Connecticut Siting Council" in the amount of \$625.00, representing the filing fee is also enclosed.

Should the Council or Staff have any questions about this matter please do not hesitate to contact me.

Very truly yours,

  
Daniel M. Laub

cc: Mayor Manuel A. Santos, City of Meriden  
Dominick Caruso, City Planner, City of Meriden  
Michele Briggs, AT&T  
David Vivian, SAI  
Carlos Centore, Centek  
Michael Libertine, APT  
Christopher B. Fisher, Esq.

CONNECTICUT SITING COUNCIL

PETITION OF NEW CINGULAR )  
WIRELESS PCS, LLC ("AT&T") TO THE )  
CONNECTICUT SITING COUNCIL FOR ) PETITION NO. \_\_\_\_\_  
A DECLARATORY RULING THAT NO )  
CERTIFICATE OF ENVIRONMENTAL ) NOVEMBER 25, 2014  
COMPATIBILITY AND PUBLIC NEED IS )  
REQUIRED FOR A PROPOSED )  
INSTALLATION OF A WIRELESS )  
TELECOMMUNICATIONS FACILITY ON )  
AN EXISTING CL&P STRUCTURE )  
LOCATED AT 200 EDGEMARK ACRES, )  
MERIDEN, CONNECTICUT )

PETITION FOR DECLARATORY RULING TO  
INSTALL A WIRELESS TELECOMMUNICATIONS FACILITY  
ON A CL&P TRANSMISSION TOWER #783  
200 EDGEMARK ACRES, MERIDEN, CONNECTICUT

**I. Introduction**

New Cingular Wireless PCS, LLC ("AT&T"), the "Petitioner", hereby petitions the Connecticut Siting Council ("Council") pursuant to Sections 16-50j-38 and 16-50j-39 of the Regulations of Connecticut State Agencies ("R.C.S.A.") for a declaratory ruling that no Certificate of Environmental Compatibility and Public Need ("Certificate") is required pursuant to Section 16-50k of the Connecticut General Statutes ("C.G.S.") to add a wireless telecommunications facility to an existing Connecticut Light & Power ("CL&P") transmission tower structure #783 and located at 200 Edgemark Acres, Meriden, Connecticut (the "Site"). As set forth herein, but for a modest 12' tower extension, AT&T's collocation would satisfy all the other criteria for an exempt modification under

R.C.S.A. Section 16-50j-72 and tower sharing pursuant to Section 16-50aa of the Connecticut General Statutes.

## **II. Existing Facility**

The existing facility, CL&P structure #783, is located in the Town of Meriden and is part of a transmission line that runs northwest to Route 72 and beyond. Structure #783 is approximately 80 feet tall and is located in an existing CL&P easement. The underlying property is owned by Martorelli Realty Company.<sup>1</sup> The nearest municipal boundary is the Town of Cheshire located approximately 3,200' to the west of the existing CL&P structure. Other properties in the area include a residential uses and educational uses including H.C. Wilcox Technical High School and O.H. Platt High School.

## **III. Proposed AT&T Installation**

AT&T is licensed by the Federal Communications Commission ("FCC") to provide wireless services in this area of the State of Connecticut. AT&T proposes to install an antenna support structure to the existing 80' tall transmission pole, which will extend approximately 12' above the existing transmission pole. The extension would be able to support up to 12 panel antennas (9 antennas are currently proposed), along with 18 tower mounted amplifiers ("TMAs") at a centerline height of approximately 88' above grade level ("AGL"). A 12' x 24' equipment shelter with a pitched roof and clapboard siding will be placed at the base of the existing structure on a concrete foundation. A segmental retaining wall, approximately 24' by 34' is required to adequately support the equipment shelter to accommodate the grade of the property near the CL&P structure. Provisions for emergency backup power include a 50kW diesel fueled generator to be located inside the equipment shelter on the concrete foundation. The equipment shelter will be enclosed by a 6' tall chain link fence with privacy slats. Access to AT&T's proposed collocated facility is proposed from Edgemark Acres via an easement over the

---

<sup>1</sup> Documentation confirming AT&T's authority to file this petition from CL&P and the underlying property owner are included in Attachment H.

existing gravel driveway that currently serves the subject property. A small portion of the beginning of the gravel access driveway is on the subject property, but not within the CL&P easement. Utilities are proposed to extend underground from Edgemark Acres via the same utility/access easement on the underlying property to the facility.

Included as Attachment A are detailed construction drawings prepared by Centek Engineering, last revised November 20, 2014 which include an abutters map, topographic details, plans, elevations, site details, site utility plans and other aspects of proposed facility. Annexed hereto as Attachment B is a Structural Analysis report last revised October 6, 2014, also prepared by Centek Engineering, concluding that the existing utility pole and foundation with proposed reinforcements outlined therein can support AT&T's proposed facility.<sup>2</sup>

#### **IV. The Proposed Facility Will Not Have a Substantial Adverse Environmental Effect**

##### **A. Minimal Physical Impact**

A comparison of existing and proposed conditions reveals no substantial adverse environmental impacts associated with modifications to CL&P's transmission structure and AT&T's Facility. The new antenna mount and antennas will be added to the existing structure. The equipment compound will be constructed in an area already cleared in the CL&P right-of-way at the base of the pole. No tree clearing is required. No wetlands will be impacted. Grading and construction of a retaining wall is required for the proposed equipment area, which includes storm water design features. All erosion and sediment control measures will be installed in accordance with the "Connecticut Guidelines for Soil Erosion and Sediment Control" and amendments, as published by the Connecticut Council on Soil and Water Conservation. As

---

<sup>2</sup> Please note that due to its large size, the full structural report with calculations is being bulk filed along with this Petition.



such, AT&T respectfully submits that there are no significant environmental impacts associated with the proposed clearing and construction.

**B. Compliance with MPE Limits**

The operation of AT&T's antennas will not increase the total radio frequency electromagnetic power density at the site to a level at or above applicable standards. A power density report is included in Attachment C. The total radio frequency power density will be well within standards adopted by the Connecticut Department of Environmental Protection as set forth in Section 22a-162 of the Connecticut General Statutes and the MPE limits established by the Federal Communications Commission.

**C. Visibility**

As demonstrated in the visual materials included in Attachment D, the proposed AT&T installation will have a *de minimus* visual impact on the surrounding area which already has existing views of the transmission tower. The installation requires no FAA lighting or marking as per the TOWAIR and FAA report included in Attachment E. Additionally, AT&T's consultants determined as part of the field review for this project that there were no quantitative changes in areas of visibility and that AT&T's proposed installation would only be visible from areas that already have views of the CL&P towers. The attached visual materials demonstrate that the incremental change in height does not substantially change the existing viewshed, particularly considering that there are other adjacent CL&P structures that are taller and at higher elevations. As such, AT&T respectfully submits that the visibility of the CL&P transmission structure with AT&T's extension is neither significant nor adverse for purposes of the Council's regulatory considerations in ruling on this petition for a declaratory ruling.

**V. Public Need**

Annexed hereto in Attachment F are Radio Frequency plots depicting existing and planned coverage from the proposed facility at an antenna

centerline height of 88' AGL for AT&T's 4G LTE network in this area of the State depicting existing and proposed coverage in the 1900MHz and 700MHz spectrum bands. AT&T currently has gaps in reliable service in this area of the state and the proposed facility is needed to fill some of these existing coverage gaps within AT&T's network. As such, while the Council does not have to find a public need for the facility as part of a ruling on this Petition, it is respectfully submitted that the enclosed demonstrates the purpose for the installation of the proposed facility. This project is further consistent with state policy to avoid the proliferation of towers.


#### **VI. Notice**

Pursuant to R.C.S.A. Section 16-50j-40(a), notice of AT&T's intent to file this petition was sent to each person appearing of record as an owner of property that abuts the site, as well as the appropriate municipal officials and government agencies as listed in Section 16-50e of the C.G.S. Certification of such notice, a copy of the notice and the list of property owners and municipal officials and government agencies to whom the notice was sent are included in Attachment G.

#### **VII. Conclusion**

As set forth above, the proposed AT&T wireless facility and associated ground equipment are wholly consistent with legislative findings outlined in Section 16-50g and 16-50aa of the General Statutes of Connecticut that seek to avoid the unnecessary proliferation of towers in the State. Further, there are no known adverse environmental effects associated with the project. Therefore and for all the foregoing reasons, AT&T petitions the Connecticut Siting Council for a determination that the proposed wireless telecommunications facility does not require a Certificate of Environmental Compatibility and Public Need and that the Council issue an order approving same.

Respectfully Submitted,

A handwritten signature in black ink, appearing to read 'D. Laub', with a long horizontal flourish extending to the right.

Daniel M. Laub

On behalf of the Petitioner AT&T

cc: Mayor Manuel A. Santos, City of Meriden  
Dominick Caruso, City Planner, City of Meriden  
Michele Briggs, AT&T  
David Vivian, SAI  
Carlos Centore, Centek  
Michael Libertine, APT  
Christopher B. Fisher, Esq.

# ATTACHMENT A





# WIRELESS COMMUNICATIONS FACILITY CT2117 MERIDEN CL&P UTILITY STRUCTURE NO. 783 200 EDGEMARK ACRES MERIDEN, CT 06451

## GENERAL NOTES


- ALL WORK SHALL BE IN ACCORDANCE WITH THE 2003 INTERNATIONAL BUILDING CODE AS MODIFIED BY THE 2005 CONNECTICUT SUPPLEMENT AND 2009 AMENDMENTS, INCLUDING THE TIA/EIA-222 REVISION "F" "STRUCTURAL STANDARDS FOR STEEL ANTENNA TOWERS AND SUPPORTING STRUCTURES." 2005 CONNECTICUT FIRE SAFETY CODE AND 2009 AMENDMENTS, NATIONAL ELECTRICAL CODE AND LOCAL CODES.
- THE COMPOUND, TOWER, PRIMARY GROUND RING, ELECTRICAL SERVICE TO THE METER BANK AND TELEPHONE SERVICE TO THE DEMARCATION POINT ARE PROVIDED BY SITE OWNER. AS BUILT FIELD CONDITIONS REGARDING THESE ITEMS SHALL BE CONFIRMED BY THE CONTRACTOR. SHOULD ANY FIELD CONDITIONS PRECLUDE COMPLIANCE WITH THE DRAWINGS, THE CONTRACTOR SHALL IMMEDIATELY NOTIFY THE ENGINEER AND SHALL NOT PROCEED WITH ANY AFFECTED WORK.
- CONTRACTOR SHALL REVIEW ALL DRAWINGS AND SPECIFICATIONS IN THE CONTRACT DOCUMENT SET. CONTRACTOR SHALL COORDINATE ALL WORK SHOWN IN THE SET OF DRAWINGS. THE CONTRACTOR SHALL PROVIDE A COMPLETE SET OF DRAWINGS TO ALL SUBCONTRACTORS AND ALL RELATED PARTIES. THE SUBCONTRACTORS SHALL EXAMINE ALL THE DRAWINGS AND SPECIFICATIONS FOR THE INFORMATION THAT AFFECTS THEIR WORK.
- CONTRACTOR SHALL PROVIDE A COMPLETE BUILD-OUT WITH ALL FINISHES, STRUCTURAL, MECHANICAL, AND ELECTRICAL COMPONENTS AND PROVIDE ALL ITEMS AS SHOWN OR INDICATED ON THE DRAWINGS OR IN THE WRITTEN SPECIFICATIONS.
- CONTRACTOR SHALL FURNISH ALL MATERIAL, LABOR AND EQUIPMENT TO COMPLETE THE WORK AND FURNISH A COMPLETED JOB ALL IN ACCORDANCE WITH LOCAL AND STATE GOVERNING AUTHORITIES AND OTHER AUTHORITIES HAVING LAWFUL JURISDICTION OVER THE WORK.
- CONTRACTOR SHALL SECURE AND PAY FOR ALL PERMITS AND ALL INSPECTIONS REQUIRED AND SHALL ALSO PAY FEES REQUIRED FOR THE GENERAL CONSTRUCTION, PLUMBING, ELECTRICAL AND HVAC. PERMITS SHALL BE PAID FOR BY THE RESPECTIVE SUBCONTRACTORS. CONTRACTOR SHALL MAINTAIN A CURRENT SET OF DRAWINGS AND SPECIFICATIONS ON SITE AT ALL TIMES AND INSURE DISTRIBUTION OF NEW DRAWINGS TO SUBCONTRACTORS AND OTHER RELEVANT PARTIES AS SOON AS THEY ARE MADE AVAILABLE. ALL OLD DRAWINGS SHALL BE MARKED VOID AND REMOVED FROM THE CONTRACT AREA. THE CONTRACTOR SHALL FURNISH AN "AS-BUILT" SET OF DRAWINGS TO OWNER UPON COMPLETION OF PROJECT.  
LOCATION OF EQUIPMENT, AND WORK SUPPLIED BY OTHERS THAT IS DIAGRAMMATICALLY INDICATED ON THE DRAWINGS SHALL BE DETERMINED BY THE CONTRACTOR. THE CONTRACTOR SHALL DETERMINE LOCATIONS AND DIMENSIONS SUBJECT TO STRUCTURAL CONDITIONS AND WORK OF THE SUBCONTRACTORS.
- THE CONTRACTOR IS SOLELY RESPONSIBLE TO DETERMINE CONSTRUCTION PROCEDURE AND SEQUENCE, AND TO ENSURE THE SAFETY OF THE EXISTING STRUCTURES AND ITS COMPONENT PARTS DURING CONSTRUCTION. THIS INCLUDES THE ADDITION OF WHATEVER SHORING, BRACING, UNDERPINNING, ETC. THAT MAY BE NECESSARY. MAINTAIN EXISTING BUILDING'S/PROPERTY'S OPERATIONS, COORDINATE WORK WITH BUILDING/PROPERTY OWNER.
- DRAWINGS INDICATE THE MINIMUM STANDARDS, BUT IF ANY WORK SHOULD BE INDICATED TO BE SUBSTANDARD TO ANY ORDINANCES, LAWS, CODES, RULES, OR REGULATIONS BEARING ON THE WORK, THE CONTRACTOR SHALL INCLUDE IN HIS WORK AND SHALL EXECUTE THE WORK CORRECTLY IN ACCORDANCE WITH SUCH ORDINANCES, LAWS, CODES, RULES OR REGULATIONS WITH NO INCREASE IN COSTS.
- ALL UTILITY WORK SHALL BE IN ACCORDANCE WITH LOCAL UTILITY COMPANY REQUIREMENTS AND SPECIFICATIONS.
- ALL EQUIPMENT AND PRODUCTS PURCHASED ARE TO BE REVIEWED BY CONTRACTOR AND ALL APPLICABLE SUBCONTRACTORS FOR ANY CONDITION PER MFR.'S RECOMMENDATIONS. CONTRACTOR TO SUPPLY THESE ITEMS AT NO COST TO OWNER OR CONSTRUCTION MANAGER.
- ANY AND ALL ERRORS, DISCREPANCIES, AND "MISSED" ITEMS ARE TO BE BROUGHT TO THE ATTENTION OF THE AT&T CONSTRUCTION MANAGER DURING THE BIDDING PROCESS BY THE CONTRACTOR. ALL THESE ITEMS ARE TO BE INCLUDED IN THE BID. NO "EXTRA" WILL BE ALLOWED FOR MISSED ITEMS.
- CONTRACTOR SHALL BE RESPONSIBLE FOR ALL ON-SITE SAFETY FROM THE TIME THE JOB IS AWARDED UNTIL ALL WORK IS COMPLETE AND ACCEPTED BY THE OWNER.
- CONTRACTOR TO REVIEW ALL SHOP DRAWINGS AND SUBMIT COPY TO ENGINEER FOR APPROVAL. DRAWINGS MUST BEAR THE CHECKER'S INITIALS BEFORE SUBMITTING TO THE CONSTRUCTION MANAGER FOR REVIEW.
- THE CONTRACTOR SHALL FIELD VERIFY ALL DIMENSIONS, ELEVATIONS, ANGLES, AND EXISTING CONDITIONS AT THE SITE, PRIOR TO FABRICATION AND/OR INSTALLATION OF ANY WORK IN THE CONTRACT AREA.
- COORDINATION, LAYOUT, FURNISHING AND INSTALLATION OF CONDUIT AND ALL APPURTENANCES REQUIRED FOR PROPER INSTALLATION OF ELECTRICAL AND TELECOMMUNICATION SERVICE SHALL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR.
- ALL EQUIPMENT AND PRODUCTS PURCHASED ARE TO BE REVIEWED BY CONTRACTOR AND ALL APPLICABLE SUBCONTRACTORS FOR ANY CONDITION PER THE MANUFACTURER'S RECOMMENDATIONS. CONTRACTOR TO SUPPLY THESE ITEMS AT NO COST TO OWNER OR CONSTRUCTION MANAGER.
- ALL DAMAGE CAUSED TO ANY EXISTING STRUCTURE SHALL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR. THE CONTRACTOR WILL BE HELD LIABLE FOR ALL REPAIRS REQUIRED FOR EXISTING STRUCTURES IF DAMAGED DURING CONSTRUCTION ACTIVITIES.
- THE CONTRACTOR SHALL CONTACT "CALL BEFORE YOU DIG" AT LEAST 48 HOURS PRIOR TO ANY EXCAVATIONS AT 1-800-922-4455. ALL UTILITIES SHALL BE IDENTIFIED AND CLEARLY MARKED PRIOR TO ANY EXCAVATION WORK. CONTRACTOR SHALL MAINTAIN AND PROTECT MARKED UTILITIES THROUGHOUT PROJECT COMPLETION.
- CONTRACTOR SHALL COMPLY WITH OWNERS ENVIRONMENTAL ENGINEER ON ALL METHODS AND PROVISIONS FOR ALL EXCAVATION ACTIVITIES INCLUDING SOIL DISPOSAL. ALL BACKFILL MATERIALS TO BE PROVIDED BY THE CONTRACTOR.

## SITE DIRECTIONS

<b>FROM:</b> 500 ENTERPRISE DRIVE ROCKY HILL, CT	<b>TO:</b> 200 EDGEMARK ACRES MERIDEN, CT
1. HEAD NORTHEAST ON ENTERPRISE DRIVE TOWARD CAPITAL BLVD	0.3 MI
2. TURN LEFT ONTO CAPITOL BLVD	0.3 MI
3. TURN LEFT ONTO WEST ST	0.3 MI
4. TURN LEFT TO MERGE ONTO I-91 S TOWARD NEW HAVEN	0.3 MI
5. MERGE ONTO I-91 S	8.8 MI
6. TAKE EXIT 18 FOR I-691 W TOWARD MERIDEN/WATERBURY	0.2 MI
7. EXIT 18 TURNS SLIGHTLY RIGHT AND BECOMES I-691 W	2.2 MI
8. TAKE EXIT 6 FOR LEWIS AVE TOWARD CT-71	0.2 MI
9. TURN RIGHT ONTO LEWIS AVE	0.8 MI
10. TURN RIGHT ONTO W MAIN ST	0.8 MI
11. SLIGHT LEFT ONTO JOHNSON AVE	417 FT
12. TAKE THE 1ST LEFT ONTO ALLEN AVE	0.9 MI
13. TURN LEFT ONTO EDGEMARK ACRES, AND THE DESTINATION WILL BE ON THE LEFT	0.4 MI

## VICINITY MAP

SCALE: 1" = 1000'



## PROJECT SUMMARY

- THE GENERAL SCOPE OF WORK CONSISTS OF THE FOLLOWING:
  - INSTALLATION OF A PREFABRICATED 11'-6"x24'-0" EQUIPMENT SHELTER WITH SHELTER HOUSED 50KW DIESEL FUELED EMERGENCY POWER GENERATOR ON A CONCRETE FOUNDATION.
  - A TOTAL OF NINE (9) DIRECTIONAL PANEL ANTENNAS ARE TO BE MOUNTED TO A ANTENNA MAST ATTACHED TO THE EXISTING ±80.1' TALL CL&P STRUCTURE #783 AT A CENTERLINE ELEVATION OF ±88' ABOVE THE EXISTING TOWER BASE PLATE.
- POWER & TELCO UTILITIES WILL BE ROUTED UNDERGROUND FROM THE EXISTING UTILITY DEMARCS TO THE PROPOSED EQUIPMENT SHELTER. ALL UTILITY WORK AND ROUTING TO BE COORDINATED AND APPROVED BY THE LOCAL UTILITY COMPANIES AND LAND OWNER.

## PROJECT INFORMATION

AT&T SITE NUMBER:	CT2117
AT&T SITE NAME:	MERIDEN
SITE ADDRESS:	CL&P STRUCTURE NO. 783 200 EDGEMARK ACRES MERIDEN, CT 06451
LESSEE/APPLICANT:	AT&T MOBILITY 500 ENTERPRISE DRIVE, SUITE 3A MERIDEN, CT 06067
ENGINEER:	CENITEK ENGINEERING, INC. 63-2 NORTH BRANFORD RD. BRANFORD, CT. 06405
PROJECT COORDINATES:	LATITUDE: 41°-31'-51.713"N LONGITUDE: 72°-50'-33.622"W GROUND ELEVATION: ±360.0' A.M.S.L. COORDINATES AND GROUND ELEVATION BASED ON FAA 1-A SURVEY CERTIFICATION AS PREPARED BY MARTINEZ COUCH AND ASSOCIATES, DATED JUNE 27, 2014.

## SHEET INDEX

SHT. NO.	DESCRIPTION	REV.
T-1	TITLE SHEET	1
N-1	NOTES AND SPECIFICATIONS	1
C-1.0	ABUTTERS MAP	1
C-1.1	SITE/SITE SURVEY PLAN	1
C-2	COMPOUND PLAN, ELEVATION AND ANTENNA MOUNTING DETAILS	1
C-3	SITE DETAILS	1
C-4	SITE DETAILS	1
S-1	FOUNDATION PLAN, ROOF FRAMING PLAN AND DETAILS	1
E-1	SITE UTILITY PLAN	1
E-2	ELECTRICAL RISER DIAGRAM, NOTES AND LEGEND	1
E-3	ELECTRICAL GROUNDING SYSTEM	1
E-4	ELECTRICAL GROUNDING PLAN	1
E-5	N.U. GROUNDING PLAN, DETAILS AND NOTES	1
E-6	ELECTRICAL DETAILS	1
E-7	ELECTRICAL DETAILS	1
E-8	ELECTRICAL DETAILS	1
E-9	ELECTRICAL SPECIFICATIONS	1

CONSTRUCTION	DESCRIPTION	ISSUED FOR CLIENT REVIEW		
1	11/20/14	HJR	CFC	
0	11/10/14	HJR	CFC	
		DATE	DRAWN BY	CHK'D BY
		REV.		

PROFESSIONAL ENGINEER SEAL

**CENITEK** engineering  
Centered on Solutions  
(203) 498-0380  
(203) 498-3837 Fax  
632 North Branford Road  
Branford, CT 06405  
www.CenitekEng.com

AT&T MOBILITY  
WIRELESS COMMUNICATIONS FACILITY  
**MERIDEN**  
SITE NUMBER: CT2117  
200 EDGEMARK ACRES  
MERIDEN, CT 06451

DATE: 11/03/14  
SCALE: AS NOTED  
JOB NO. 13305.000

TITLE SHEET

**T-1**  
Sheet No. 1 of 17



**NOTES AND SPECIFICATIONS**

**DESIGN BASIS:**

- GOVERNING CODE: 2003 INTERNATIONAL BUILDING CODE AS MODIFIED BY THE 2005 CT STATE BUILDING CODE AND 2009 AMENDMENTS.
- TIA/EIA-222-F-1996, ASCE MANUAL NO. 72 - "DESIGN OF STEEL TRANSMISSION POLE STRUCTURES SECOND EDITION", NESC C2-2007 AND NORTHEAST UTILITIES DESIGN CRITERIA.
- DESIGN CRITERIA

WIND LOAD: (POWER MOUNT)

BASIC WIND SPEED (V) = 85 MPH (FASTEST MILE); BASED ON TIA/EIA-222F AND NU MAST DESIGN CRITERIA EXCEPTION 1.

WIND LOAD: (UTILITY POLE & FOUNDATION)

BASIC WIND SPEED (V) = 110 MPH (3-SECOND GUST) BASED ON NESC C2-2007, SECTION 25 RULE 250C.

**GENERAL NOTES:**

- ALL CONSTRUCTION SHALL BE IN COMPLIANCE WITH THE GOVERNING BUILDING CODE.
- DRAWINGS INDICATE THE MINIMUM STANDARDS, BUT IF ANY WORK SHOULD BE INDICATED TO BE SUBSTANDARD TO ANY ORDINANCES, LAWS, CODES, RULES, OR REGULATIONS BEARING ON THE WORK, THE CONTRACTOR SHALL INCLUDE IN HIS WORK AND SHALL EXECUTE THE WORK CORRECTLY IN ACCORDANCE WITH SUCH ORDINANCES, LAWS, CODES, RULES OR REGULATIONS WITH NO INCREASE IN COSTS.
- BEFORE BEGINNING THE WORK, THE CONTRACTOR IS RESPONSIBLE FOR MAKING SUCH INVESTIGATIONS CONCERNING PHYSICAL CONDITIONS (SURFACE AND SUBSURFACE) AT OR CONTIGUOUS TO THE SITE WHICH MAY AFFECT PERFORMANCE AND COST OF THE WORK.
- DIMENSIONS AND DETAILS SHALL BE CHECKED AGAINST THE PRE MANUFACTURED EQUIPMENT BUILDING SHOP DRAWINGS.
- THE CONTRACTOR SHALL VERIFY AND COORDINATE THE SIZE AND LOCATION OF ALL OPENINGS, SLEEVES AND ANCHOR BOLTS AS REQUIRED BY ALL TRADES.
- ALL DIMENSIONS, ELEVATIONS, AND OTHER REFERENCES TO EXISTING STRUCTURES, SURFACE AND SUBSURFACE CONDITIONS ARE APPROXIMATE. NO GUARANTEE IS MADE FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION SHOWN. THE CONTRACTOR SHALL VERIFY AND COORDINATE ALL DIMENSIONS, ELEVATIONS, ANGLES WITH EXISTING CONDITIONS AND WITH ARCHITECTURAL AND SITE DRAWINGS BEFORE PROCEEDING WITH ANY WORK.
- AS THE WORK PROGRESSES, THE CONTRACTOR SHALL NOTIFY THE OWNER OF ANY CONDITIONS WHICH ARE IN CONFLICT OR OTHERWISE NOT CONSISTENT WITH THE CONSTRUCTION DOCUMENTS AND SHALL NOT PROCEED WITH SUCH WORK UNTIL THE CONFLICT IS SATISFACTORILY RESOLVED.
- THE CONTRACTOR SHALL COMPLY WITH ALL APPLICABLE SAFETY CODES AND REGULATIONS DURING ALL PHASES OF CONSTRUCTION. THE CONTRACTOR IS SOLELY RESPONSIBLE FOR PROVIDING AND MAINTAINING ADEQUATE SHORING, BRACING, AND BARRICADES AS MAY BE REQUIRED FOR THE PROTECTION OF EXISTING PROPERTY, CONSTRUCTION WORKERS, AND FOR PUBLIC SAFETY.
- THE CONTRACTOR IS SOLELY RESPONSIBLE TO DETERMINE CONSTRUCTION PROCEDURE AND SEQUENCE, AND TO ENSURE THE SAFETY OF THE EXISTING STRUCTURES AND ITS COMPONENT PARTS DURING CONSTRUCTION. THIS INCLUDES THE ADDITION OF WHATEVER SHORING, BRACING, UNDERPINNING, ETC. THAT MAY BE NECESSARY. MAINTAIN EXISTING SITE OPERATIONS, COORDINATE WORK WITH NORTHEAST UTILITIES
- THE STRUCTURE IS DESIGNED TO BE SELF-SUPPORTING AND STABLE AFTER FOUNDATION REMEDIATION WORK IS COMPLETE. IT IS THE CONTRACTOR'S SOLE RESPONSIBILITY TO DETERMINE ERECTION PROCEDURE AND SEQUENCE AND TO ENSURE THE SAFETY OF THE STRUCTURE AND ITS COMPONENT PARTS DURING ERECTION. THIS INCLUDES THE ADDITION OF WHATEVER SHORING, TEMPORARY BRACING, GUYS OR TIEDOWNS, WHICH MIGHT BE NECESSARY.
- THE CONTRACTOR SHALL LIMIT THE DURATION OF ANY FOUNDATION MODIFICATION WORK. THE EXISTING FOUNDATION WITHIN THE SHOWN LIMITS IS STABLE FOR WIND SPEEDS LESS THAN 50MPH WITHOUT ICE LOADING. IF HIGHER WIND SPEED OR ICE EVENT IS EXPECTED, THE EXCAVATION AREA SHALL BE FILLED WITH COMPACT FILL MATERIAL.
- ALL DAMAGE CAUSED TO ANY EXISTING STRUCTURE SHALL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR. THE CONTRACTOR WILL BE HELD LIABLE FOR ALL REPAIRS REQUIRED FOR EXISTING STRUCTURES IF DAMAGED DURING CONSTRUCTION ACTIVITIES.
- SHOP DRAWINGS, CONCRETE MIX DESIGNS, TEST REPORTS, AND OTHER SUBMITTALS PERTAINING TO STRUCTURAL WORK SHALL BE FORWARDED TO THE OWNER FOR REVIEW BEFORE FABRICATION AND/OR INSTALLATION IS MADE. SHOP DRAWINGS SHALL INCLUDE ERECTION DRAWINGS AND COMPLETE DETAILS OF CONNECTIONS AS WELL AS MANUFACTURER'S SPECIFICATION DATA WHERE APPROPRIATE. SHOP DRAWINGS SHALL BE CHECKED BY THE CONTRACTOR AND BEAR THE CHECKER'S INITIALS BEFORE BEING SUBMITTED FOR REVIEW.
- NO DRILLING WELDING OR TAPING ON CL&P OWNED EQUIPMENT.
- REFER TO DRAWING T1 FOR ADDITIONAL NOTES AND REQUIREMENTS.

**SITE NOTES**

- THE CONTRACTOR SHALL CALL UTILITIES PRIOR TO THE START OF CONSTRUCTION.
- ACTIVE EXISTING UTILITIES, WHERE ENCOUNTERED IN THE WORK, SHALL BE PROTECTED AT ALL TIMES. THE ENGINEER SHALL BE NOTIFIED IMMEDIATELY, PRIOR TO PROCEEDING, SHOULD ANY UNCOVERED EXISTING UTILITY PRECLUDE COMPLETION OF THE WORK IN ACCORDANCE WITH THE CONTRACT DOCUMENTS.
- ALL RUBBISH, STUMPS, DEBRIS, STICKS, STONES AND OTHER REFUSE SHALL BE REMOVED OFF SITE AND BE LEGALLY DISPOSED, AT NO ADDITIONAL COST.
- THE SITE SHALL BE GRADED TO CAUSE SURFACE WATER TO FLOW AWAY FROM THE EQUIPMENT AND TOWER AREAS.
- NO FILL OR EMBANKMENT MATERIAL SHALL BE PLACED ON FROZEN GROUND. FROZEN MATERIALS, SNOW OR ICE SHALL NOT BE PLACED IN ANY FILL OR EMBANKMENT.
- THE SUBGRADE SHALL BE COMPACTED AND BROUGHT TO A SMOOTH UNIFORM GRADE PRIOR TO FINISHED SURFACE APPLICATION.
- THE AREAS OF THE COMPOUND DISTURBED BY THE WORK SHALL BE RETURNED TO THEIR ORIGINAL CONDITION.
- CONTRACTOR SHALL MINIMIZE DISTURBANCE TO EXISTING SITE DURING CONSTRUCTION. EROSION CONTROL MEASURES, SHALL BE IN CONFORMANCE WITH THE LOCAL GUIDELINES FOR EROSION AND SEDIMENT CONTROL.
- IF ANY FIELD CONDITIONS EXIST WHICH PRECLUDE COMPLIANCE WITH THE DRAWINGS, THE CONTRACTOR SHALL IMMEDIATELY NOTIFY THE ENGINEER AND SHALL PROCEED WITH AFFECTED WORK AFTER CONFLICT IS SATISFACTORILY RESOLVED.
- DIMENSIONS AND DETAILS SHALL BE CHECKED AGAINST THE PRE MANUFACTURED EQUIPMENT BUILDING SHOP DRAWINGS.
- THE CONTRACTOR SHALL VERIFY AND COORDINATE THE SIZE AND LOCATION OF ALL OPENINGS, SLEEVES AND ANCHOR BOLTS AS REQUIRED BY ALL TRADES.

**EARTHWORK NOTES**

- COMPACTED GRAVEL FILL SHALL BE FURNISHED AND PLACED AS A FOUNDATION FOR STRUCTURES, WHERE SHOWN ON THE CONTRACT DRAWINGS OR DIRECTED BY THE ENGINEER.
- CRUSHED STONE FILL SHALL BE PLACED IN 12" MAX. LIFTS AND CONSOLIDATED USING A HAND OPERATED VIBRATORY PLATE COMPACTOR WITH A MINIMUM OF 2 PASSES OF COMPACTOR PER LIFT.
- COMPACTED GRAVEL FILL TO BE WELL GRADED BANK RUN GRAVEL MEETING THE FOLLOWING GRADATION REQUIREMENTS:  
**SIEVE DESIGNATION                % PASSING**  
1 3/4"     100  
No. 4     40-70  
No. 100    5-20  
No. 200    4-8
- CRUSHED STONE TO BE UNIFORMLY GRADED, CLEAN, HARD PROCESS AGGREGATE MEETING THE FOLLOWING GRADATION REQUIREMENTS:  
**SIEVE DESIGNATION                % PASSING**  
1"     100  
3/4"    90-100  
3/8"    0-15  
1/2"    0-5
- SELECT BACKFILL FOR FOUNDATION WALLS SHALL BE FREE OF ORGANIC MATERIAL, TOPSOIL, DEBRIS AND BOULDERS LARGER THAN 6".
- GRAVEL AND GRANULAR FILL SHALL BE INSTALLED IN 10" MAX. LIFTS. COMPACTED TO 95% MIN. AT MAX. DRY DENSITY.
- NON WOVEN GEOTEXTILE FOR SEPARATION PURPOSES SHALL BE MIRAFI 140N, OR ENGINEER APPROVED EQUAL.

**FOUNDATION CONSTRUCTION NOTES**

- ALL FOOTINGS SHALL BE PLACED ON SUITABLE, COMPACTED SOIL HAVING ADEQUATE BEARING CAPACITY AND FREE OF ORGANIC CONTENT, CLAY, OR OTHER UNSUITABLE MATERIAL. ADDITIONAL EXCAVATION MAY BE REQUIRED BELOW FOOTING ELEVATIONS INDICATED IF UNSUITABLE MATERIAL IS ENCOUNTERED.
- SUBGRADE PREPARATION: IF UNSUITABLE SOIL IS ENCOUNTERED, REMOVE ALL UNSUITABLE MATERIALS FROM BELOW PROPOSED STRUCTURE FOUNDATIONS AND COMPACT EXPOSED SOIL SURFACES. PLACE AND COMPACT APPROVED GRAVEL FILL. PLACEMENT OF ALL COMPACTED FILL MUST BE UNDER SUPERVISION OF AN APPROVED TESTING LABORATORY. FILL SHALL BE COMPACTED IN LAYERS NOT TO EXCEED 10" BEFORE COMPACTION. DETERMINE MAXIMUM DRY DENSITY IN ACCORDANCE WITH ASTM D1557-70 AND MAKE ONE (1) FIELD DENSITY TEST IN ACCORDANCE WITH ASTM D2167-66 FOR EACH 50 CUBIC YARDS OF COMPACTED FILL, BUT NOT LESS THAN ONE (1) PER LAYER, TO INSURE COMPACTION TO 95% OF MAX. DRY DENSITY.
- ALL SOIL SURROUNDING AND UNDER ALL FOOTINGS SHALL BE KEPT REASONABLY DRY AND PROTECTED FROM FREEZING AND FROST ACTION DURING THE COURSE OF CONSTRUCTION.
- WHERE GROUNDWATER IS ENCOUNTERED, DEWATERING SHALL BE ACCOMPLISHED CONTINUOUSLY AND COMPLETELY DURING FOUNDATION CONSTRUCTION. PROVIDE CRUSHED STONE AS REQUIRED TO STABILIZE FOOTING SUBGRADE.
- ALL FOOTINGS ARE TO REST ON FIRM SOIL, REGARDLESS OF ELEVATIONS SHOWN ON THE DRAWINGS, BUT IN NO CASE MAY FOOTING ELEVATIONS BE HIGHER THAN INDICATED ON THE FOUNDATION PLAN, UNLESS SPECIFICALLY DIRECTED BY THE ENGINEER.
- FOUNDATION WATERPROOFING AND DAMPROOFING SHALL COMPLY WITH BUILDING CODE REQUIREMENTS UNLESS A MORE SUBSTANTIAL SYSTEM IS INDICATED OR SPECIFIED.

**CONCRETE CONSTRUCTION NOTES**

- CONCRETE CONSTRUCTION SHALL CONFORM TO THE FOLLOWING STANDARDS:  
ACI 211 - STANDARD PRACTICE FOR SELECTING PROPORTIONS FOR NORMAL AND HEAVYWEIGHT CONCRETE.  
ACI 301 - SPECIFICATIONS FOR STRUCTURAL CONCRETE FOR BUILDINGS.  
ACI 302 - GUIDE FOR CONCRETE FLOOR AND SLAB CONSTRUCTION  
ACI 304 - RECOMMENDED PRACTICE FOR MEASURING, MIXING, TRANSPORTING, AND PLACING CONCRETE.  
ACI 306.1 STANDARD SPECIFICATION FOR COLD WEATHER CONCRETING  
ACI 318 - BUILDING CODE REQUIREMENTS FOR REINFORCED CONCRETE.
- CONCRETE SHALL DEVELOP COMPRESSIVE STRENGTH IN 28 DAYS AS FOLLOWS:  
**SLABS ON GRADE                                 4,000 PSI**  
**ALL OTHER CONCRETE                             3,000 PSI**  
- PORTLAND CEMENT: ASTM C150, TYPE II, (540 LBS/CUBIC YARD)  
- AGGREGATE: ASTM C33, No. 67, TYPICAL  
- WATER: POTABLE WITH MAXIMUM WATER CEMENT RATIO OF .55  
- SLUMP: 3" TO 4"  
- ADMIXTURES: USE AIR ENTRAINING AGENT CONFORMING TO ASTM C260 WITH 4 TO 6% TOTAL AIR. USE WATER REDUCING AGENT CONFORMING TO ASTM C494, TYPE A, IN ALL CONCRETE. CALCIUM CHLORIDE MAY NOT BE USED TO ACCELERATE THE CONCRETE SETTING TIME.
- REINFORCING STEEL SHALL BE 60,000 PSI YIELD STRENGTH.
- WELDED WIRE FABRIC SHALL CONFORM TO ASTM-A-185.
- ALL DETAILING, FABRICATION, AND ERECTION OF REINFORCING BARS, UNLESS OTHERWISE NOTED, MUST FOLLOW THE LATEST ACI CODE AND LATEST ACI "MANUAL OF STANDARD PRACTICE FOR DETAILING REINFORCED CONCRETE STRUCTURES".
- CONCRETE COVER OVER REINFORCING SHALL CONFORM TO THE FOLLOWING, UNLESS OTHERWISE SHOWN:  
**CONCRETE CAST AGAINST & PERMANENTLY EXPOSED TO EARTH                                 3 INCHES**  
**CONCRETE EXPOSED TO EARTH OR WEATHER:     2 INCHES**  
**#6 THROUGH #18 BARS     1-1/2 INCHES**  
**#5 BAR, W31 OR D31 WIRE, AND SMALLER                             1-1/2 INCHES**  
**CONCRETE NOT EXPOSED TO WEATHER OR IN CONTACT WITH THE GROUND:     1-1/2 INCHES**  
**#14 THROUGH #18 BARS     3/4 INCHES**  
**#11 BAR AND SMALLER     3/4 INCHES**
- NO STEEL WIRE, METAL FORM TIES, OR ANY OTHER METAL SHALL REMAIN WITHIN THE REQUIRED COVER OF ANY CONCRETE SURFACE.
- ALL REINFORCEMENT SHALL BE CONTINUOUS UNLESS OTHERWISE NOTED. SPLICES SHALL BE WELL STAGGERED. ADDITIONAL BARS AND SPECIAL BENDING DETAILS ARE REQUIRED AT INTERSECTING WALLS AND AT JOINTS. SUCH DETAILS SHALL COMPLY WITH

- ACI 315 RECOMMENDATIONS UNLESS OTHERWISE SHOWN.
- NO TACK WELDING OF REINFORCING WILL BE PERMITTED.
  - NO CALCIUM CHLORIDE OR ADMIXTURES CONTAINING MORE THAN 1% CHLORIDE BY WEIGHT OF ADMIXTURE SHALL BE USED IN THE CONCRETE.
  - UNLESS OTHERWISE NOTED, ALL LAP SPLICES SHALL BE 48 BAR DIAMETERS.
  - SLAB ON GRADE FINISHES:  
EXTERIOR SLAB: NON-SLIP BROOM FINISH  
INTERIOR SLAB: STEEL TROWEL FINISH
  - INSPECTION AND TESTING OF CONCRETE WORK SHALL BE PERFORMED BY AN INDEPENDENT TESTING LABORATORY, PAID BY THE OWNER, AND APPROVED BY THE ENGINEER. THE INSPECTOR SHALL OBSERVE CONDITION OF SOILS AND FORMWORK BEFORE FOOTINGS ARE PLACED, SIZE, SPACING AND LOCATION OF REINFORCEMENT, AND PLACEMENT OF CONCRETE.
  - THE TESTING COMPANY SHALL ALSO OBTAIN A MINIMUM OF THREE (3) COMPRESSIVE STRENGTH TEST SPECIMENS FOR EACH CONCRETE MIX DESIGN. ONE SPECIMEN TESTED AT 7 DAYS, ONE AT 28 DAYS, AND ONE HELD IN RESERVE FOR FUTURE TESTING, IF NEEDED.
  - FOUR COPIES OF ALL INSPECTION TEST REPORTS SHALL BE SUBMITTED TO THE ENGINEER WITHIN TEN (10) WORKING DAYS OF THE DATE OF INSPECTION.

**STRUCTURAL STEEL**

- ALL STRUCTURAL STEEL IS DESIGNED BY ALLOWABLE STRESS DESIGN (ASD)  
A. STRUCTURAL STEEL (W SHAPES)---ASTM A992 (FY = 50 KSI)  
B. STRUCTURAL STEEL (OTHER SHAPES)---ASTM A36 (FY = 36 KSI)  
C. STRUCTURAL HSS (RECTANGULAR SHAPES)---ASTM A500 GRADE B, (FY = 46 KSI)  
D. STRUCTURAL HSS (ROUND SHAPES)---ASTM A500 GRADE B, (FY = 42 KSI)  
E. PIPE---ASTM A53 (FY = 35 KSI)  
F. CONNECTION BOLTS---ASTM A325-N  
G. U-BOLTS---ASTM A36  
H. ANCHOR RODS---ASTM F 1554  
I. WELDING ELECTRODE---ASTM E 70XX
- CONTRACTOR TO REVIEW ALL SHOP DRAWINGS AND SUBMIT COPY TO ENGINEER FOR APPROVAL. DRAWINGS MUST BEAR THE CHECKER'S INITIALS BEFORE SUBMITTING TO THE ENGINEER FOR REVIEW. SHOP DRAWINGS SHALL INCLUDE THE FOLLOWING: SECTION PROFILES, SIZES, CONNECTION ATTACHMENTS, REINFORCING, ANCHORAGE, SIZE AND TYPE OF FASTENERS AND ACCESSORIES. INCLUDE ERECTION DRAWINGS, ELEVATIONS AND DETAILS.
- STRUCTURAL STEEL SHALL BE DETAILED, FABRICATED AND ERECTED IN ACCORDANCE WITH THE LATEST PROVISIONS OF AISC MANUAL OF STEEL CONSTRUCTION.
- PROVIDE ALL PLATES, CLIP ANGLES, CLOSURE PIECES, STRAP ANCHORS, MISCELLANEOUS PIECES AND HOLES REQUIRED TO COMPLETE THE STRUCTURE.
- FIT AND SHOP ASSEMBLE FABRICATIONS IN THE LARGEST PRACTICAL SECTIONS FOR DELIVERY TO SITE.
- INSTALL FABRICATIONS PLUMB AND LEVEL, ACCURATELY FITTED, AND FREE FROM DISTORTIONS OR DEFECTS.
- AFTER ERECTION OF STRUCTURES, TOUCHUP ALL WELDS, ABRASIONS AND NON-GALVANIZED SURFACES WITH A 95% ORGANIC ZINC RICH PAINT IN ACCORDANCE WITH ASTM 780.
- ALL STEEL MATERIAL (EXPOSED TO WEATHER) SHALL BE GALVANIZED AFTER FABRICATION IN ACCORDANCE WITH ASTM A123 "ZINC (HOT DIPPED GALVANIZED) COATINGS" ON IRONS AND STEEL PRODUCTS.
- ALL BOLTS, ANCHORS AND MISCELLANEOUS HARDWARE SHALL BE GALVANIZED IN ACCORDANCE WITH ASTM A153 "ZINC COATING (HOT-DIP) ON IRON AND STEEL HARDWARE".
- CONTRACTOR SHALL COMPLY WITH AWS CODE FOR PROCEDURES APPEARANCE AND QUALITY OF WELDS, AND WELDING PROCESSES SHALL BE QUALIFIED IN ACCORDANCE WITH AWS "STANDARD QUALIFICATION PROCEDURES". ALL WELDING SHALL BE DONE USING E70XX ELECTRODES AND WELDING SHALL CONFORM TO AISC AND D1.1 WHERE FILLET WELD SIZES ARE NOT SHOWN, PROVIDE THE MINIMUM SIZE PER TABLE J2.4 IN THE AISC "MANUAL OF STEEL CONSTRUCTION" 9TH EDITION. AT THE COMPLETION OF WELDING, ALL DAMAGE TO GALVANIZED COATING SHALL BE REPAIRED.
- THE ENGINEER SHALL BE NOTIFIED OF ANY INCORRECTLY FABRICATED, DAMAGED OR OTHERWISE MISFITTING OR NON CONFORMING MATERIALS OR CONDITIONS TO REMEDIAL OR CORRECTIVE ACTION. ANY SUCH ACTION SHALL REQUIRE ENGINEER REVIEW.
- CONNECTION ANGLES SHALL HAVE A MINIMUM THICKNESS OF 1/4 INCHES.
- STRUCTURAL CONNECTION BOLTS SHALL CONFORM TO ASTM A325. ALL BOLTS SHALL BE 3/4" DIAMETER MINIMUM AND SHALL HAVE A MINIMUM OF TWO BOLTS, UNLESS OTHERWISE ON THE DRAWINGS.
- LOCK WASHER ARE NOT PERMITTED FOR A325 STEEL ASSEMBLIES.
- SHOP CONNECTIONS SHALL BE WELDED OR HIGH STRENGTH BOLTED.
- MILL BEARING ENDS OF COLUMNS, STIFFENERS, AND OTHER BEARING SURFACES TO TRANSFER LOAD OVER ENTIRE CROSS SECTION.
- FABRICATE BEAMS WITH MILL CAMBER UP.
- LEVEL AND PLUMB INDIVIDUAL MEMBERS OF THE STRUCTURE TO AN ACCURACY OF 1:500, BUT NOT TO EXCEED 1/4" IN THE FULL HEIGHT OF THE COLUMN.
- COMMENCEMENT OF STRUCTURAL STEEL WORK WITHOUT NOTIFYING THE ENGINEER OF ANY DISCREPANCIES WILL BE CONSIDERED ACCEPTANCE OF PRECEDING WORK.
- INSPECTION AND TESTING OF ALL WELDING AND HIGH STRENGTH BOLTING SHALL BE PERFORMED BY AN INDEPENDENT TESTING LABORATORY.
- FOUR COPIES OF ALL INSPECTION TEST REPORTS SHALL BE SUBMITTED TO THE ENGINEER WITHIN TEN (10) WORKING DAYS OF THE DATE OF INSPECTION.

**STRUCTURAL LUMBER CONSTRUCTION:**

- STRUCTURAL LUMBER USED FOR JOISTS, RAFTERS AND COLUMNS SHALL BE NO. 2 GRADE DOUGLAS FIR AND SHALL HAVE NOT LESS THAN THE FOLLOWING ALLOWABLE UNIT STRESSES, BEFORE ADJUSTMENT FOR DURATION FACTORS, BASED ON 1997 NDS SPECIFICATION:  
**EXTREME FIBER IN BENDING     Fb 875 PSI**  
**HORIZONTAL SHEAR     Fv 95 PSI**  
**TENSION PARALLEL TO GRAIN     Ft = 575 PSI**  
**COMPRESSION PERPENDICULAR TO GRAIN                           Fc 625 PSI**  
**COMPRESSION PARALLEL TO GRAIN                                   Fc = 1,350 PSI**  
**MODULUS OF ELASTICITY     E = 1,600,000 PSI**
- LIGHT FRAMING LUMBER USED FOR STUDS, PARTITIONS, AND MISCELLANEOUS FRAMING SHALL NOT BE LESS THAN STANDARD GRADE AND SHALL HAVE THE FOLLOWING MINIMUM ALLOWABLE UNIT STRESSES:  
**EXTREME FIBER IN BENDING     Fb 675 PSI**  
**TENSION PARALLEL TO GRAIN     Ft = 450 PSI**  
**COMPRESSION PARALLEL TO GRAIN                                   Fc 850 PSI**  
**MODULUS OF ELASTICITY     E = 1,400,000 PSI**
- MOISTURE CONTENT OF ALL FRAMING LUMBER WHEN DELIVERED TO THE PROJECT SITE SHALL NOT EXCEED 19%.
- EXCEPT WHERE STRICTER PROVISIONS ARE INDICATED, 2003 INTERNATIONAL RESIDENTIAL CODE SHALL GOVERN ALL WOOD CONSTRUCTION INCLUDING, BUT NOT LIMITED TO: MATERIALS, FASTENERS (TYPE, SIZE, SPACING, EMBEDMENT), SHOP AND FIELD FABRICATION, CONNECTIONS, AND INSTALLATION.
- NOT USED
- NAIL PENETRATION INTO WALL STUDS AND CORNER POSTS SHALL BE AT LEAST 1 3/4 INCHES.
- PROVIDE AND INSTALL TIMBER POSTS (6x6 OR BUILT UP 2x6 MEMBERS) AT ALL EXTERIOR CORNERS AND ANCHOR TO FOUNDATION WALLS, AND BETWEEN EACH FRAMING LEVEL TO RESIST UPLIFT FORCES. PROVIDE AND INSTALL SIMPSON HDU5--SDS2.5 (HOLD DOWN) ANCHORS WITH SSTB24 ANCHOR RODS OR EQUIVALENT AT FOUNDATION WALLS. PROVIDE AND INSTALL HDU2--SDS2.5 ANCHORS WITH SSB16 ANCHOR RODS AND POSTS EACH SIDE OF DOOR OPENINGS GREATER THAN 4'-0" IN EXTERIOR WALLS.
- HORIZONTAL (SLOPED) DIAPHRAGMS: THE FLOOR AND ROOF ARE DESIGNED AS DIAPHRAGMS TO RESIST LATERAL LOADS. FLOOR SHEATHING SHALL BE 3/4 INCH THICK APA RATED STURDI-FLOOR TONGUE AND GROOVE PLYWOOD. FLOOR SHEATHING SHALL BE ATTACHED TO FLOOR JOISTS WITH CONSTRUCTION ADHESIVE AND 80 NAILS. ROOF SHEATHING SHALL BE 5/8 INCH THICK CDX PLYWOOD. ROOF SHEATHING SHALL BE ATTACHED TO RAFTERS WITH 80 NAILS.  
  
MAXIMUM NAIL SPACING OF FLOOR AND ROOF SHEATHING SHALL BE 6" o.c. ALONG ALL EDGES. ALL EDGES SHALL BE SUPPORTED WITH SOLID BLOCKING. FIELD NAILING SHALL BE 12" o.c. NAIL PENETRATION INTO SUPPORTING MEMBER SHALL BE AT LEAST 1-1/2 INCHES.
- ALL DOUBLE TOP PLATES, RIM JOISTS, AND HEADERS IN EXTERIOR WALLS ARE USED AS DIAPHRAGM CHORD MEMBERS. SPLICES IN DOUBLE TOP PLATES SHALL BE STAGGERED AND METAL STRAPS PROVIDED TO CONNECT RIM JOISTS WITH HEADER AND LINTEL BEAMS.  
  
JOIST AND BEAM HANGERS AND OTHER FRAMING ANCHORS SHALL BE SIZED FOR REACTIONS SHOWN ON THE DRAWINGS UNLESS A SPECIFIC HANGER OR FRAMING ANCHOR IS INDICATED. SUBMIT SHOP DRAWINGS INDICATING PROPOSED HANGER SIZE AND TYPE.  
  
CONNECTION HARDWARE AND FASTENERS SHALL BE GALVANIZED OR STAINLESS STEEL. FRAMING ANCHORS AND FASTENERS THAT ARE NOT EXPOSED TO THE WEATHER SHALL BE G90 GALVANIZED. FRAMING ANCHORS AND FASTENERS THAT ARE EXPOSED TO THE WEATHER SHALL BE STAINLESS STEEL.
- ALL STRUCTURAL WOOD MEMBERS SHALL BE PROPERLY FIELD FABRICATED TO REQUIRED LENGTHS AND SPACING. PROVIDE SUITABLE CONNECTIONS, BEARING LENGTHS, STIFFENERS, BRIDGING, HEADERS, AND OTHER SPECIAL FRAMING AS INDICATED OR REQUIRED BY BUILDING CODE FOR COMPLETE INSTALLATION. ADDITIONAL JOISTS ARE REQUIRED AT FRAMED OPENINGS, AT CONCENTRATED LOADS, AND DIRECTLY BELOW PARTITIONS THAT ARE PARALLEL WITH JOISTS.
- ALL FRAMING (ROOF, FLOORS, WALLS) SHALL BE PROPERLY ANCHORED TO EACH OTHER AND TO CONCRETE FOUNDATIONS AGAINST UPLIFT BY ADEQUATELY SPLICED AND NAILED ROOF AND WALL SHEATHING, BY METAL STRAPS, HURRICANE ANCHORS, OR SIMILAR CONNECTION HARDWARE.
- PROVIDE HEAVY HEX NUTS AND WASHERS AT ALL ANCHOR BOLTS AND AT WOOD FRAME CONNECTIONS TO AVOID CRUSHING WOOD FIBERS.
- PRESSURE TREATED LUMBER SHALL BE USED FOR FOUNDATION SILLS AND FOR ALL LUMBER EXPOSED TO THE WEATHER AND IN DIRECT CONTACT WITH CONCRETE OR MASONRY FOUNDATIONS.
- PROVIDE SOLID BLOCKING BETWEEN ADJACENT FLOOR JOISTS AND ROOF RAFTERS, AT ALL SUPPORTS AND TOP FLANGE HANGERS, TO PREVENT MEMBER ROTATION. ALLOW SUFFICIENT CLEARANCE FOR CROSS VENTILATION AT ROOF.
- PROVIDE SOLID BLOCKING AND/OR MINIMUM 1"x3" DIAGONAL BRIDGING AT 7 FEET ON CENTER MAXIMUM AT ALL WOOD FRAMING. IF SOLID BLOCKING IS USED, IT SHALL EXCEED THE FULL DEPTH OF THE MEMBER IT IS Laterally Supporting, UNLESS OTHERWISE NOTD.
- EXTERIOR WALLS AND INTERIOR LOAD-BEARING WALLS SHALL BE FRAMED WITH 2x6 STUDS SPACED AT 16 INCHES ON CENTER AND SHALL HAVE DOUBLE TOP PLATES. INTERIOR NON-LOAD-BEARING PARTITIONS SHALL BE FRAMED WITH 2x4 STUDS SPACED AT 16 INCHES ON CENTER. UNLESS OTHERWISE INDICATED, BEARING WALLS AND PARTITIONS THAT ARE PARALLEL WITH FLOOR JOISTS SHALL BE FULLY SUPPORTED BY DOUBLE JOISTS. INSTALL SOLID FULL-DEPTH BLOCKING BETWEEN JOISTS DIRECTLY BELOW BEARING WALLS AND PARTITIONS THAT ARE PERPENDICULAR WITH FLOOR JOISTS.

PROFESSIONAL ENGINEER SEAL	DATE	11/03/14
	SCALE	AS NOTED
REVISIONS	NO.	DESCRIPTION
DRAWN BY	DATE	11/20/14



**CENTEK engineering**  
 Centek in Solutions  
 (203) 498-0380  
 (203) 498-9387 Fax  
 652 North Branch Road  
 Branford, CT 06405  
 www.CentekEng.com


**AT&T MOBILITY**  
 WIRELESS COMMUNICATIONS FACILITY  
**MERIDEN**  
 SITE NUMBER: CT2117  
 200 EDGE MARK ACRES  
 MERIDEN, CT 06451

DATE: 11/03/14  
 SCALE: AS NOTED  
 JOB NO. 13305.000  
**NOTES AND SPECIFICATIONS**  
**N-1**  
 Sheet No. 2 of 17




MISCELLANEOUS SITE INFORMATION	
DISTANCE TO NEAREST OFF SITE RESIDENCE*	= ±153'
NUMBER OF RESIDENTIAL STRUCTURES WITHIN 1000' OF TOWER	= ±42
DISTANCE TO NEAREST PROPERTY LINE*	= ±47'
DISTANCE TO NEARBY SCHOOLS AND CHILD DAY CARE CENTERS*:	
H.C. WILCOX HIGH SCHOOL	= ±0.63 mi
ORVILLE H. PLATT HIGH SCHOOL	= ±0.84 mi
LINCOLN MIDDLE SCHOOL	= ±1.03 mi
MERIDEN KINDERCARE	= ±1.11 mi
BENJAMIN FRANKLIN SCHOOL	= ±1.41 mi
CRUZ FAMILY DAYCARE	= ±1.78 mi


\* DISTANCES TAKEN FROM CENTER OF TOWER



**2** AERIAL PHOTO  
C-1.0 SCALE: 1" = 100'



**1** ABUTTERS MAP  
C-1.0 SCALE: 1" = 20'



REV.	DATE	BY	CHK'D BY	DESCRIPTION
1	11/20/14	HJR	CFC	CONSTRUCTION - ISSUED FOR CLIENT REVIEW
0	11/10/14	HJR	CFC	CONSTRUCTION

PROFESSIONAL ENGINEER SEAL



**CEN TEK** engineering  
Centered on Solutions  
(203) 488-0580  
(203) 488-3887 Fax  
632 North Branford Road  
Branford, CT 06405  
www.CenTekEng.com

AT&T MOBILITY  
WIRELESS COMMUNICATIONS FACILITY  
**MERIDEN**  
SITE NUMBER: CT2117  
200 EDMARK ACRES  
MERIDEN, CT 06451


DATE: 11/03/14  
SCALE: AS NOTED  
JOB NO. 13305.000

ABUTTERS MAP

**C-1.0**  
Sheet No. 3 of 17



SYMBOLS LEGEND	
---	PROPERTY LINE
- - -	EASEMENT LINE
---	DRIVE (EXISTING)
---650---	CONTOUR LINE
---	GRADING LINE
○	UTILITY POLE
○	EXISTING MANHOLE
-x-x-x-	FENCE LINE
X	PROPOSED SPOT GRADE
CB	EXISTING CATCH BASIN
WV	EXISTING WATER VALVE
GV	EXISTING GAS VALVE



NOTES	
USE OF METAL BASED TAPE MEASURES FOR PURPOSES OF TOWER AND ANTENNA HEIGHT MEASUREMENTS IS PROHIBITED WHEN THE HEIGHT OF THE TOWER/ANTENNA MAST IS GREATER THAN THE DISTANCE TO THE NEAREST POWER LINE.	
HEIGHT OF TOWER/ANTENNA MAST (A.G.L.)	= ±93'
DISTANCE TO NEAREST POWER LINE	= ±21'

**SURVEY NOTES**

THIS SURVEY AND MAP HAS BEEN PREPARED IN ACCORDANCE WITH SECTIONS 20-300B-1 THRU 20-300B-20 OF THE REGULATIONS OF CONNECTICUT STATE AGENCIES - "MINIMUM STANDARDS FOR SURVEYS AND MAPS IN THE STATE OF CONNECTICUT" AS ENDORSED BY THE CONNECTICUT ASSOCIATION OF LAND SURVEYORS, INC. ON SEPT. 26, 1996. THE LIMITED TOPOGRAPHIC SURVEY PORTION OF THIS PLAN CONFORMS TO A VERTICAL ACCURACY OF CLASS T-2 AND IS INTENDED TO BE USED TO DEPICT A PROPOSED TELECOMMUNICATION SITE.

THE PROPERTY/BOUNDARY LINES DEPICTED HEREON ARE COMPILED FROM OTHER MAPS, DEEDS AND LIMITED FIELD SURVEY. THESE LINES ARE NOT TO BE CONSTRUED AS A BOUNDARY OPINION AND ARE SUBJECT TO CHANGE AS AN ACCURATE FIELD SURVEY MAY DISCLOSE. PROPERTY MAY BE SUBJECT TO ENCUMBRANCES, EASEMENTS, RIGHTS OF WAY AS A TITLE SEARCH REPORT MAY DISCLOSE. PLANIMETRIC FEATURES SUCH AS PARKING AREAS, PAVED DRIVE ARE COMPILED FROM OTHER MAPS AND LIMITED FIELD SURVEY.

COORDINATES REFER TO NAD 83.

VERTICAL DATUM IS BASED ON NGVD 29.

PARCEL OWNER OF RECORD: MARTORELLI REALTY CO  
234 MIDDLE STREET  
MIDDLETOWN, CT 06457

PARCEL AREA = 0.83± ACRES.

PARCEL IS IN R-R ZONING DISTRICT.

PARCEL ID 0627-0225-004L-0043 ON THE MERIDEN ASSESSOR'S MAP.

SUBJECT PARCEL IS NOT IN A FLOOD ZONE AS SHOWN ON THE FLOOD INSURANCE RATE MAP, NEW HAVEN COUNTY, CONNECTICUT PANEL 164 OF 635, MAP NUMBER 09009C0164H, MAP EFFECTIVE DATE DECEMBER 17, 2010, BY FEDERAL EMERGENCY MANAGEMENT AGENCY.

REFERENCE IS MADE TO THE FOLLOWING MAPS:


1. SUBDIVISION, ROLLING HILLS PHASE II, MERIDEN, CT. SCALE 1"=100', DATED 5-6-88, REVISED THROUGH 12-6-90. RECORDED AS MAP #5119 OF THE MERIDEN LAND RECORDS.

NOT ALL IMPROVEMENTS SHOWN.

TO MY KNOWLEDGE AND BELIEF THIS MAP IS SUBSTANTIALLY CORRECT AS NOTED HEREON

THIS MAP IS NOT VALID WITHOUT A LIVE SIGNATURE AND SEAL

**1 SITE/SITE SURVEY PLAN**  
C-1 SCALE: 1" = 10'



A. RAFAEL MARTINEZ LLS #18833

DATE

1  
C-3 AT&T 20' WIDE ACCESS GATE.

1&2  
C-4 AT&T 6' TALL WOOD STOCKADE FENCE, TYP.

3  
C-3 AT&T GRAVEL COMPOUND SURFACE, TYP. (HATCHED AREA)


7  
C-3 AT&T SEGMENTAL RETAINING WALL.

EXTENT OF REINFORCED CONCRETE MAT FOUNDATION FOR SUBJECT TOWER.

EXISTING ±80.1' TALL CL&P TRANSMISSION TOWER #783.

EXISTING SPOT ELEVATION, TYP.

1  
C-1




PROFESSIONAL ENGINEER SEAL	
(203) 498-0380 (203) 498-3397 Fax 652 North Branford Road Branford, CT 06405 www.CentekEng.com	
<b>AT&amp;T MOBILITY</b> WIRELESS COMMUNICATIONS FACILITY <b>MERIDEN</b> SITE NUMBER: CT2117 200 EDMARK ACRES MERIDEN, CT 06451	
DATE:	11/03/14
SCALE:	AS NOTED
JOB NO.	13305.000
SITE/SITE SURVEY PLAN	
<b>C-11</b>	
Sheet No. 4 of 17	




### RF EQUIPMENT TABLE


SECTOR	PANEL ANTENNAS					FILTER	FROM TMA				TMA	FROM SHELTER			
	AZIMUTH	QTY.	MAKE: MODEL	RAD CENTER (AGL)	DOWNTILT		QTY.	JUMPER QTY.	JUMPER SIZE	JUMPER LENGTH		RET. QTY.	QTY.	MAKE & MODEL	COAX SIZE
ALPHA	0°	2	CCI: HPA-65R-BUU-H8	88.0'	0°M/0°E	0	20	1/2" Ø	15' ±	0	6	CCI TMABPDB7823VG12A	1-5/8"	36	120'±
		1	CCI: OPA-65R-LCUU-H8												
BETA	120°	2	CCI: HPA-65R-BUU-H8	88.0'	0°M/0°E	0	20	1/2" Ø	15' ±	0	6	CCI TMABPDB7823VG12A	1-5/8"	36	120'±
		1	CCI: OPA-65R-LCUU-H8												
GAMMA	240°	2	CCI: HPA-65R-BUU-H8	88.0'	0°M/0°E	0	20	1/2" Ø	15' ±	0	6	CCI TMABPDB7823VG12A	1-5/8"	36	120'±
		1	CCI: OPA-65R-LCUU-H8												



**3 ANTENNA MOUNTING CONFIGURATION DETAILS**  
SCALE: 1/4" = 1'




**2 COMPOUND PLAN**  
SCALE: 1" = 5'




**TOWER NOTES:**

- EXISTING 80.1' TALL CL&P STEEL TRANSMISSION STRUCTURE NO. 783.
- REFER TO STRUCTURAL ANALYSIS REPORT AND TOWER REINFORCEMENT DESIGN DRAWINGS PREPARED BY CENTEK ENGINEERING, INC., PROJECT NO. 13305, DATED 1/7/14, REVISED 10/6/14 (REV-4) FOR ADDITIONAL DETAILS AND REQUIREMENTS.
- ALL ANTENNAS AND COAX TO BE INSTALLED IN ACCORDANCE WITH STRUCTURAL ANALYSIS AND FINAL AT&T RF DATA SHEET.



**1 WESTERN ELEVATION**  
SCALE: 1" = 10'



PROFESSIONAL ENGINEER SEAL	CONSTRUCTION - ISSUED FOR CLIENT REVIEW
11/20/14	CFC
0	CFC
11/10/14	HHR
0	HHR
DATE	DRAWN BY
REV.	DESCRIPTION

at&t

SAI communications

CENTEK engineering  
Centered on Solutions  
203-488-0380  
203-488-3887 Fax  
652 North Branford Road  
Branford, CT 06405  
www.CenterEng.com

AT&T MOBILITY  
WIRELESS COMMUNICATIONS FACILITY  
MERIDEN  
SITE NUMBER: CT2117  
200 EDGE MARK ACRES  
MERIDEN, CT 06451


DATE: 11/03/14  
SCALE: AS NOTED  
JOB NO. 13305.000

COMPOUND PLAN, ELEVATION AND ANTENNA MOUNTING DETAILS

**C-2**

Sheet No. 5 of 17







**SEGMENTAL RETAINING WALL NOTES:**

- STRIP VEGETATION AND ORGANIC SOIL FROM WALL AND GEOSYNTHETIC ALIGNMENT.
- BENCH CUT ALL EXCAVATED SLOPES.
- DO NOT OVER EXCAVATE UNLESS DIRECTED BY SITE SOIL ENGINEER TO REMOVE UNSUITABLE SOIL.
- SITE SOIL ENGINEER SHALL VERIFY FOUNDATION SOILS AS BEING COMPETENT PER THE DESIGN STANDARDS AND PARAMETERS.
- BASE SHALL CONSIST OF COMPACTED GRAVEL, 6" THICK MIN.
- CONTRACTOR MAY OPT FOR A LEAN CONCRETE PAD. CONCRETE PAD SHALL BE UNREINFORCED, 4" THICK.
- MINIMUM EMBEDMENT OF WALL BELOW FINISH GRADE SHALL BE 2 COURSES OF BLOCK.
- FOLLOW APPLICABLE PROVISIONS OF THE MANUFACTURER'S INSTALLATION INSTRUCTIONS AND WRITTEN SPECIFICATIONS.
- NO. 8 CRUSHED STONE SHALL BE INSTALLED BEHIND THE WALL UP TO 18" FROM THE TOP OF THE WALL. CRUSHED STONE SHALL NOT EXTEND BELOW FINISHED GRADE IN FRONT OF WALL.
- WHERE DRAIN PIPE IS USED, PROVIDE OUTLETS @ MAX. 40 FT C-C.
- FOR UNITS TO BE EMBEDDED, COMPACT FILL IN FRONT OF UNITS AT THE SAME TIME BACKFILL BEHIND UNITS IS COMPACTED.
- COMPACTION TESTS SHALL BE TAKEN AS THE WALL IS INSTALLED. THE MINIMUM NUMBER OF TESTS SHALL BE DETERMINED BY THE ENGINEER.
- COMPACTION SHALL BE TO 95% OF MAXIMUM STANDARD PROCTOR DENSITY. (ASTM D-698)
- SEE SHOP DRAWINGS FOR GEOSYNTHETIC TYPE, LENGTH AND LOCATION REQUIRED.
- GEOSYNTHETIC SHALL BE THE TYPE AND LENGTH AS SHOWN ON SHOP DRAWINGS. PULL GEOSYNTHETIC TIGHT PRIOR TO BACKFILLING.
- GEOSYNTHETIC SHALL BE PLACED WITH STRONGEST DIRECTION PERPENDICULAR TO WALL FOLLOW GEOSYNTHETIC MANUFACTURER'S INSTALLATION INSTRUCTIONS AND WRITTEN SPECIFICATIONS.
- THE CONTRACTOR SHALL SUBMIT A SHOP DRAWING SHOWING THE COMPLETE WALL SYSTEM AND ALL DETAILS BASED ON THE ACTUAL SOILS IN THE FIELD THESE SHOP DRAWINGS SHALL BE SIGNED AND SEALED BY A PROFESSIONAL ENGINEER LICENSED IN THE STATE OF CONNECTICUT
- IF CONDITIONS ARE DIFFERENT THAN THOSE STATED IN THESE DRAWINGS AND SPECIFICATIONS, THE CONTRACTOR MUST CONTACT ENGINEER PRIOR TO PROCEEDING WITH THE CONSTRUCTION OF THE WALL.
- IF WALL LEVELING PAD REQUIRES FILL IT SHALL BE COMPACTED GRAVEL FROM BOTTOM OF EXCAVATION TO SUITABLE SOIL TO BOTTOM OF WALL.


**7 SEGMENTAL RETAINING WALL DETAIL**  
C-3 NOT TO SCALE




**6 BOLLARD DETAIL**  
C-3 NOT TO SCALE




**4 UTILITY SUPPORT FRAME (TYP)**  
C-3 NOT TO SCALE



**3 COMPOUND SURFACING DETAIL**  
C-3 NOT TO SCALE




**5 ICE BRIDGE DETAIL**  
C-3 NOT TO SCALE



**GPS ANTENNA MOUNTING BRACKET**

BILL OF MATERIALS		
ITEM	DESCRIPTION	QUANTITY
1	2-1/2" SCH. 40 x 8'-0" LG. MAX SS OR GALV. PIPE	1
2	UNIVERSAL CLAMP SET.	2




**A SECTION**  
C-3 NOT TO SCALE

**NOTES:**

- THE ELEVATION AND LOCATION OF THE GPS ANTENNA SHALL BE IN ACCORDANCE WITH THE FINAL RF REPORT.
- THE GPS ANTENNA MOUNT IS DESIGNED TO FASTEN TO A STANDARD 2-1/2" DIAMETER, SCHEDULE 40, GALVANIZED STEEL OR STAINLESS STEEL PIPE. THE PIPE MUST NOT BE THREADED AT THE ANTENNA MOUNT END. THE PIPE SHALL BE CUT TO THE REQUIRED LENGTH (MINIMUM OF 24 INCHES) USING A HAND OR ROTARY PIPE CUTTER TO ASSURE A SMOOTH AND PERPENDICULAR CUT. A HACK SAW SHALL NOT BE USED. THE CUT PIPE END SHALL BE DEBURRED AND SMOOTH IN ORDER TO SEAL AGAINST THE NEOPRENE GASKET ATTACHED TO THE ANTENNA MOUNT.
- ATTACH TO ICE BRIDGE POST NEAREST ANTENNA CABLE PORT AT EQUIPMENT.
- PRIOR TO INSTALLATION CONTRACTOR SHALL TEST GPS LOCATION WITH HAND HELD AND MOVE GPS ANTENNA TO OTHER ICE BRIDGE POSTS AS REQUIRED TO ACHIEVE ADEQUATE SIGNAL. FAILURE TO ACHIEVE ADEQUATE SIGNAL WITH A HAND HELD GPS SHALL BE REPORTED TO CONSTRUCTION MANAGER AND ENGINEER TO DETERMINE ALTERNATE INSTALLATION LOCATION FOR GPS ANTENNA.

**2 GPS GROUNDING/MOUNTING BRACKET DETAIL**  
C-3 NOT TO SCALE



**1 BARRIER GATE DETAIL**  
C-3 NOT TO SCALE

- BARRIER GATE CONSTRUCTION NOTES**
- GATE POST 3" SCHEDULE 40 FOR GATE WIDTHS UP THRU 6 FEET OR 12 FEET FOR DOUBLE SWING BARRIER GATE PER ASTM-F1083.
  - GATE FRAME: 2" SCHEDULE 40 PIPE PER ASTM-F1083.
  - CENTER UPRIGHT AND ANGLE BRACES: 1 5/8" SCHEDULE 40 PIPE PER ASTM-F1083.
  - HINGES: INDUSTRIAL OFFSET HINGES (I.O.H.).
  - INDUSTRIAL DROP ROD AND LATCH.
  - PROVIDE CAPS ON POSTS AND UPRIGHTS.

REV.	DATE	BY	CHK'D BY	DESCRIPTION
1	11/20/14	HJR	CFC	CONSTRUCTION - ISSUED FOR CLIENT REVIEW
0	11/10/14	HJR	CFC	CONSTRUCTION -

PROFESSIONAL ENGINEER SEAL



**CENITEK engineering**  
Centers on Solutions  
(203) 488-0380  
(203) 488-3887 Fax  
652 North Branford Road  
Branford, CT 06405  
www.CenitekEng.com


**AT&T MOBILITY**  
WIRELESS COMMUNICATIONS FACILITY  
**MERIDEN**  
SITE NUMBER: CT2117  
200 EDGE MARK ACRES  
MERIDEN, CT 06451

DATE: 11/03/14  
SCALE: AS NOTED  
JOB NO. 13305.000


SITE DETAILS

**C-3**







**SOUTHWEST ELEVATION**



**SOUTHEAST ELEVATION**




**NORTHEAST ELEVATION**




**NORTHWEST ELEVATION**


**3 EQUIPMENT SHELTER ELEVATIONS**  
C-4 SCALE: 3/16" = 1'-0"




**2 FENCE DETAIL**  
C-4 NOT TO SCALE



**1 FENCE GATE DETAIL**  
C-4 NOT TO SCALE



**1A UPPER POST SECTION**  
C-4 NOT TO SCALE



**1B UPPER POST SECTION**  
C-4 NOT TO SCALE

**FENCE & GATE NOTES:**

- ALL STEEL FENCE GATE COMPONENTS SHALL BE GALVANIZED. STEEL FENCE GATE MEMBERS SHALL BE SHOP WELDED AND GALV'D AFTER FABRICATION.
- ALL WOOD COMPONENTS SHALL BE WHITE CEDAR. DIMENSIONS SHOWN ARE NOMINAL.
- ALL METAL FENCE POSTS (OTHER THAN GATE) AND ASSOCIATED ACCESSORIES AND SCREWS ARE TO BE POST MASTER BY MASTER HALCO OR APPROVED EQUAL.
- ALL VERTICAL GATE FRAMING MEMBERS SHALL HAVE 1/4" WELDED END PLATE CAPS.

**WOOD FENCE COMPONENT FINISH:**

ALL WOOD COMPONENTS TO RECEIVE MINIMUM (2) COATS OF VALSPAR PREMIUM PENETRATING OIL DECK & SIDING TONER OR APPROVED EQUAL. FIRST COAT TO BE APPLIED PRIOR TO ASSEMBLY. APPLY COATING PER MANUFACTURER'S WRITTEN RECOMMENDATIONS.

**FASTENERS:**

- WOOD-TO-STEEL: 1 1/2" LNG #8-25 GA, FLUSH HEAD HILTI KWIK-PRO GALV'D SELF-DRILLING SCREWS (2 SCREWS AT EA. RAIL LOCATION, TYP.)
- WOOD-TO-WOOD: REFER TO POST MASTER BY HALCO FOR REQUIRED FASTENERS.

REV.	DATE	BY	CHK'D BY	DESCRIPTION
1	11/20/14	HJR	CFC	CONSTRUCTION - ISSUED FOR CLIENT REVIEW
0	11/10/14	HJR	CFC	CONSTRUCTION -

PROFESSIONAL ENGINEER SEAL




**CENTEK engineering**  
Centered on Solutions  
(203) 488-0380  
(203) 488-3837  
652 North Branford Road  
Branford, CT 06405  
www.CentekEng.com

**AT&T MOBILITY**  
WIRELESS COMMUNICATIONS FACILITY  
**MERIDEN**  
SITE NUMBER: CT2117  
200 EDGE MARK ACRES  
MERIDEN, CT 06451


DATE: 11/03/14  
SCALE: AS NOTED  
JOB NO. 13305.000

SITE DETAILS






**8 ROOF TRUSS SECTION - DESIGN SCHEMATIC**  
S-1 SCALE: 3/8" = 1'




**7 SOFFIT AND TRUSS CONNECTION DETAIL**  
S-1 SCALE: 1" = 1'




**6 ROOF FRAMING PLAN**  
S-1 SCALE: 1/4" = 1'


- ROOF FRAMING PLAN NOTES:**
1. CEILING JOISTS SHALL BE 2x6 D.F. #2 AT 16" O.C.
  2. ——— INDICATES SLOPING MEMBER
  3. REFER TO DRAWING N-1 FOR STRUCTURAL LUMBER REQUIREMENTS AND ADDITIONAL INFORMATION.




**9 FRAMING SECTION**  
S-1 SCALE: 3/4" = 1'



**3 BUILDING TIE DOWN**  
S-1 SCALE: 1" = 1'



**4 ENTRY STOOP DETAIL - ELEVATION**  
S-1 SCALE: 3/16" = 1'




**5 ENTRY STOOP DETAIL - SECTION**  
S-1 SCALE: 3/16" = 1'


**EQUIPMENT SHELTER BY CELLXION. VERIFY ALL SHELTER DIMENSIONS, EQUIPMENT DIMENSIONS, EQUIPMENT LOCATIONS AND UTILITY OPENINGS WITH BUILDING SHOP DRAWINGS PRIOR TO COMMENCEMENT OF WORK.**

**SLAB ON GRADE FOUNDATION DESIGN CONFORMS TO THE REQUIREMENTS OF THE 2003 INTERNATIONAL BUILDING CODE AS MODIFIED BY THE 2005 CONNECTICUT STATE BUILDING CODE SUPPLEMENT SECTION 1805.2.1 'FROST PROTECTION' AND SEI/ASCE STANDARD 32-01 SECTION 7.1 'SLAB ON GRADE CONSTRUCTION'.**

- FOUNDATION PLAN NOTES:**
1. BEARING SHIMS, TIE-DOWN PLATES AND ASSOCIATED INSTALLATION ANCHORS PROVIDED BY CELLXION. CONTRACTOR SHALL VERIFY ALL SHIM & TIE-DOWN QUANTITIES AND LOCATIONS WITH CELLXION PRIOR TO PERFORMING FOUNDATION WORK.
  2. SLAB/ TOP OF WALL TOLERANCE IS 1/4"±
  3. TOP 8" OF FOUNDATION SIDES MUST BE FORMED FLAT TO ACCEPT TIE-DOWN PLATES.
  4. REFER TO NOTES ON DWG. N-1 FOR ADDITIONAL REQUIREMENTS.
  5. PER NEC REQUIREMENTS, THE REBAR IN FOUNDATION AND FOOTING SHALL BE BONDED TO GROUND RING WITH A #2 AWG SOLID CONDUCTOR USING LISTED AND APPROVED METHODS.
  6. PROVIDE PVC SLEEVES FOR UTILITY CONDUIT PASSAGE THROUGH FOUNDATION OR CAST CONDUITS IN PLACE. REFER TO ELECTRICAL DRAWINGS FOR CONDUIT SIZES AND QUANTITIES.



**1 FOUNDATION PLAN**  
S-1 SCALE: 1/4" = 1' APPROX. GRID NORTH



**2 FOUNDATION PLAN SLAB ON GRADE**  
S-1 SCALE: 1/2" = 1'

REV.	DATE	BY	CHK'D BY	DESCRIPTION
1	11/20/14	HJR		CONSTRUCTION - ISSUED FOR CLIENT REVIEW
0	11/10/14	HJR		CONSTRUCTION -

PROFESSIONAL ENGINEER SEAL




**CENTEK engineering**  
Center on Solutions  
(203) 488-0380  
(203) 488-3887 Fax  
652 North Branford Road  
Branford, CT 06405  
www.CentekEng.com

**AT&T MOBILITY**  
WIRELESS COMMUNICATIONS FACILITY  
**MERIDEN**  
SITE NUMBER: CT2117  
200 EDGE MARK ACRES  
MERIDEN, CT 06451


DATE: 11/03/14  
SCALE: AS NOTED  
JOB NO. 13305.000

FOUNDATION PLAN, ROOF FRAMING PLAN AND DETAILS





**1** COMPOUND PLAN  
E-1 SCALE: 1" = 20'-0"




**ELECTRICAL LEGEND**


SYMBOL	DESCRIPTION
---	PROPERTY LINE
- - - - -	ACCESS/ UTILITY EASEMENT LINE (PROPOSED)
—E/T—	ELECTRICAL/TELCO CONDUIT RUN (UNDERGROUND)
—O/H—	UTILITY LINES (OVERHEAD BY UTILITY CO.)
○ □	UTILITY PULL BOX/SILO
◇	UTILITY POLE

**UTILITY NOTES**

- COORDINATE WITH OWNER FOR ALL EASEMENT DOCUMENTS.
- UTILITY ROUTING SHOWN ON THIS PLAN IS SCHEMATIC. CONTRACTOR SHALL COORDINATE FINAL ROUTING WITH RESPECTIVE UTILITY COMPANIES PRIOR TO PERFORMING ANY UTILITY TRENCH WORK. ALL UTILITY CONDUITS AND PULL BOXES SHALL BE LOCATED WITHIN THE EASEMENT AREA.
- UTILITY PULL BOXES/SILOS TO BE INSTALLED IN APPROXIMATE LOCATIONS SHOWN ON THIS PLAN. CONTRACTOR TO COORDINATE FINAL PULL BOX LOCATIONS WITH RESPECTIVE LOCAL UTILITY COMPANIES.
- ALL UTILITY EQUIPMENT SHALL BE LOCATED WITHIN THE EASEMENT AREA. PRIOR TO START OF CONSTRUCTION THE CONTRACTOR SHALL OBTAIN A VALID COPY OF THE EASEMENT MAP FROM THE OWNER.



**2** COMPOUND PLAN  
E-1 SCALE: 1" = 4'-0"



REV.	DATE	DRAWN BY	CHK'D BY	DESCRIPTION
1	11/20/14	TJB	CJD	CONSTRUCTION - ISSUED FOR CLIENT REVIEW
0	11/10/14	TJB	CJD	CONSTRUCTION

PROFESSIONAL ENGINEER SEAL



**CEN TEK** engineering  
Centered on Solutions™  
(203) 498-0390  
(203) 498-3897 Fax  
652 North Branford Road  
Branford, CT 06405  
www.CenTekEng.com

AT&T MOBILITY  
WIRELESS COMMUNICATIONS FACILITY  
**MERIDEN**  
SITE NUMBER: CT2117  
200 EDGE MARK ACRES  
MERIDEN, CT 06451

DATE: 11/03/14  
SCALE: AS NOTED  
JOB NO. 13305.000

SITE UTILITY PLAN

**E-1**

ELECTRICAL LEGEND	
SYMBOL	DESCRIPTION
---	GROUND RING
-T-----T-	UNDERGROUND COMMUNICATION CONDUIT
-E-----E-	UNDERGROUND ELECTRICAL CONDUIT AS INDICATED
⊕	GROUND BAR
○-----○	PERIMETER CHAIN LINK FENCE
⊗	5/8" DIAMETER x 10'-0" COPPER GROUND ROD OR 24"x24" GROUND PLATE ABOVE MATT FOUNDATION.
⊗	5/8" DIAMETER x 10'-0" COPPER GROUND ROD WITH ACCESS.
■	EXOTHERMIC WELD TYPE "TA"
●	MECHANICAL CONNECTION
⊕	GROUND WELL

### GENERAL NOTES

- REFER TO CIVIL DRAWINGS FOR ACTUAL LOCATIONS OF STRUCTURES ON SITE.
- COORDINATION, LAYOUT AND FURNISHING OF CONDUIT, CABLE AND ALL APPURTENANCES REQUIRED FOR PROPER INSTALLATION OF ELECTRICAL/TELECOMMUNICATIONS SERVICES SHALL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR.
- THE EXACT BUILDING FOUNDATION SIZE AND BUILDING WALL PENETRATIONS FOR UTILITIES SHALL BE CONFIRMED WITH THE BUILDING SPECIFICATIONS AND PLANS PRIOR TO LAYOUT.
- ALL UTILITY WORK SHALL BE IN ACCORDANCE WITH LOCAL UTILITY COMPANY REQUIREMENTS AND SPECIFICATIONS.
- PROVIDE CADWELD CONNECTION STYLES: THROUGH (CABLE TO CABLE) TYPE "TA" (CABLE TO SURFACE) TYPE "LA" OR "VS" (PIPE) (CABLE TO ROD) TYPE "GT" OR "NC" (CABLE TO CABLE) TYPE "SS"
- EXTEND UTILITY SERVICES TO UTILITY BACKBOARD IN PROPOSED OWNERS EQUIPMENT SHELTER. COORDINATE WITH SHELTER SHOP DRAWINGS FOR LOCATION. OWNER TO COORDINATE ALL UTILITY SERVICES TO NEW EQUIPMENT SHELTER.
- SEE CIVIL SHEETS FOR DETAILS OF FLOOR AND WALL PENETRATIONS.
- ALL CONDUITS SHALL BE PROPERLY ANCHORED ALONG ENTIRE ROUTE.

**VERIFY ALL SHELTER DIMENSIONS, EQUIPMENT DIMENSIONS, EQUIPMENT LOCATIONS AND UTILITY OPENINGS WITH BUILDING SHOP DRAWINGS PRIOR TO COMMENCEMENT OF WORK**

### NOTES


- CONTRACTOR TO VERIFY ALL CONDUIT ROUTING AND INSTALLATION REQUIREMENTS WITH LOCAL UTILITIES PRIOR TO INSTALLATION.
- ALL CONDUITS SHALL HAVE EXPANSION COUPLINGS WHERE EXTENDING ABOVE GRADE.
- ALL UTILITY SUPPLY CONDUITS, CONDUCTORS AND ASSOCIATED EQUIPMENT MUST BE LOCATED WITHIN THE LIMITS OF THE UTILITY EASEMENT. COORDINATE WITH OWNER FOR EASEMENT DOCUMENTATION.
- REFER TO SITE UTILITY PLAN.
- TELEPHONE EQUIPMENT SHOWN APPROXIMATE. COORDINATE WITH TELEPHONE UTILITY COMPANY AND PROVIDE ALL SPECIFIED EQUIPMENT.
- COORDINATE SERVICE EQUIPMENT INTERRUPTING RATING WITH AVAILABLE FAULT CURRENT FROM UTILITY COMPANY. EQUIPMENT SHALL NOT BE RATED LESS THAN 65 KAIC.
- ALL TELEPHONE AND ELECTRIC UTILITY WORK MUST BE COORDINATED WITH UTILITY COMPANY, AND ALL EQUIPMENT MUST BE UTILITY COMPANY APPROVED. CONTRACTOR SHALL PROVIDE ALL ELEMENTS NOT PROVIDED BY UTILITY COMPANIES.
- CONDUCTOR SIZES SHALL NOT BE REDUCED OR SUBSTITUTED WITHOUT ENGINEERS APPROVAL.
- INSTALL PULL ROPES IN ALL EMPTY CONDUITS.
- ALL CONDUCTORS AND CONDUCTOR TERMINATIONS SHALL BE RATED FOR 75°C OPERATION.
- COORDINATE WALL PENETRATIONS WITH SHELTER MANUFACTURER.

### ELECTRICAL ABBREVIATIONS

ABBREVIATION	DESCRIPTION
AFF	ABOVE FINISHED FLOOR
AIC	AMPERE INTERRUPTING CAPACITY
AWG	AMERICAN WIRE GAGE
C	CONDUIT
EGR	EXTERIOR GROUND RING
G - GRD	GROUND
GFCI	GROUND FAULT CIRCUIT INTERRUPTER
IGR	INTERIOR GROUND RING MOUNTED 9'-0" ABOVE FINISHED FLOOR
KWH	KILO-WATT-HOUR
MCCB	MOLDED CASE CIRCUIT BREAKER
MDP	MAIN DISTRIBUTION PANEL
NC	NORMALLY CLOSED
OC	ON CENTER
SA	SURGE ARRESTOR
VM	VOLTAGE MONITOR
WP	WEATHERPROOF
ER	EXISTING TO REMAIN
RR	REMOVE AND RELOCATE
RE	RELOCATED EXISTING
RGS	RIGID GALVANIZED STEEL

### NOTES

- EXISTING TRANSFORMER AND TELCO PEDESTAL TO BE USED. REFER TO SITE SURVEY AND UTILITY PLAN. COORDINATE WITH EACH UTILITY COMPANY.
- (1) 3" CONDUIT FOR PRIMARY ELECTRIC CONDUCTORS. CONDUCTORS PROVIDED BY UTILITY COMPANY FROM UTILITY POLE TO TRANSFORMER. PROVIDE ALL COUPLINGS, ADAPTERS, SWEEPS, AND ASSOCIATED HARDWARE. MATERIAL SHALL BE PER UTILITY COMPANY SPECIFICATIONS. PROVIDE CONCRETE ENCASEMENT (MIN. 3" COVER ALL AROUND) AS REQUIRED BY CL&P. REFER TO NEW SERVICE REQUEST # 229-7566.
- TRANSFORMER PROVIDED BY UTILITY COMPANY. TRANSFORMER VAULT, HOUSING, AND GROUND GRID BY ELECTRICAL CONTRACTOR, PER UTILITY COMPANY SPECIFICATIONS.
- PROVIDE TRANSFORMER GROUNDING PER NEC AND UTILITY COMPANY SPECIFICATIONS.
- TWO SETS OF: (3) 600 KCMIL, (1) 1/0 AWG GROUND, 4°C.
- TWO 4" CONDUITS WITH PULL ROPES FOR TELEPHONE COMPANY CONDUCTORS. CONDUCTORS PROVIDED BY TELEPHONE COMPANY FROM UTILITY POLE TO UTILITY BOARD. PROVIDE ALL COUPLINGS, ADAPTERS, SWEEPS, AND ASSOCIATED HARDWARE. MATERIAL SHALL BE PER TELEPHONE COMPANY SPECIFICATIONS. CONDUITS SHALL BE ENCASED IN CONCRETE WITH ELECTRICAL CONDUITS, PER AT&T AND U.I. SPECIFICATIONS. PROVIDE SEPARATION BETWEEN UTILITIES AS REQUIRED BY BOTH UTILITY COMPANIES.
- PROVIDE CONDUIT WITH PULL ROPE BETWEEN HANDHOLE AND PEDESTAL. EXPECT TWO 4" CONDUITS, BUT FINAL SIZE AND QUANTITY PER TELEPHONE COMPANY.
- TELEPHONE & ELECTRIC JUNCTION/SPLICE BOX. MUST BE TRAFFIC RATED. QUANTITY AND LOCATION PER EACH UTILITY COMPANY SPECIFICATIONS.
- TELEPHONE COMPANY HANDHOLE. INSTALL PER TELEPHONE COMPANY SPECIFICATIONS.
- TELEPHONE COMPANY PEDESTAL. INSTALL PER TELEPHONE COMPANY SPECIFICATIONS.
- UTILITY BACKBOARD. REFER TO CIVIL DRAWINGS.
- TWO 3'x4'x1' NEMA-3R TELEPHONE ENCLOSURES INSTALLED NEXT TO EACH OTHER ON UTILITY BACKBOARD. MAINTAIN APPROXIMATELY 1' SEPARATION BETWEEN AND INSTALL A SECTION OF 4" CONDUIT CONNECTING BOTH BOXES.
- PROVIDE DOUBLE DUPLEX, GFI RECEPTACLE IN WEATHERPROOF ENCLOSURE INSIDE OF TELEPHONE ENCLOSURE. CONNECT TO DEDICATED 20A/1P CIRCUIT IN OWNERS ELECTRIC PANEL IN SHELTER.
- PROVIDE GROUND BAR AS REQUIRED BY TELEPHONE COMPANY.
- #2 AWG GROUNDING CONDUCTOR IN 3/4" PVC CONDUIT, UNLESS OTHERWISE SPECIFIED BY TELEPHONE COMPANY. BOND TO GROUNDING TRIAD.
- 800A, 240/120V, 1P, 65 KAIC RATED, NEMA-3R, MAIN CIRCUIT BREAKER MODULE WITH 800A/2P MAIN CIRCUIT BREAKER. (SQUARE-D: EZM1800CBU OR APPROVED EQUIVALENT.) MUST BE UTILITY COMPANY APPROVED.
- 3-GANG MULTI-METER BRANCH DEVICES WITH 240V, 1P, 3W, 225A RATED METER SOCKETS. (SQUARE-D: EZML13225 OR APPROVED EQUIVALENT.) MUST BE UTILITY COMPANY APPROVED. (LEAVE ROOM FOR FUTURE 3-GANG MODULE.)
- UTILITY COMPANY APPROVED METER FOR AT&T IN AVAILABLE SOCKET. PROVIDE LABEL STATING "AT&T WIRELESS".
- 200A/2P MAIN CIRCUIT BREAKER IN AVAILABLE POSITION CORRESPONDING TO METER FOR OWNER.
- 3/0 AWG GROUNDING ELECTRODE CONDUCTOR IN 3/4" PVC CONDUIT BONDED TO GROUNDING TRIAD LOCATED AT UTILITY BACKBOARD. GROUNDING TRIAD SHALL BE BONDED TO COMPOUND GROUND RING WITH #2 AWG SOLID TINNED BARE COPPER WIRE.
- (3) #3/0 AWG, (1) #6 AWG GROUND, 2-1/2°C. FROM METER TO TRANSFER SWITCH IN SHELTER.
- (2) #12 AWG, #12 AWG GROUND, 3/4°C. FROM DEDICATED 20A/1P CIRCUIT BREAKER IN OWNERS POWER PANEL TO RECEPTACLE IN TELCO BOXES.
- EXPANSION COUPLING, TYPICAL.
- 4" PVC CONDUIT FOR TELEPHONE SERVICE. PROVIDE TELEPHONE CABLES AS REQUIRED BY TELEPHONE COMPANY AND OWNER. EXTEND TO OWNERS TELCO BOARD IN SHELTER.
- AT&T EQUIPMENT SHELTER.
- 4" PVC CONDUIT FROM HANDHOLE TO TELCO BOARD IN SHELTER. PROVIDE TELEPHONE CABLES AS REQUIRED BY TELEPHONE COMPANY AND OWNER.
- PROVIDE LABEL AT METER LISTING TYPE AND LOCATION OF ON SITE STANDBY GENERATOR.



**1 RISER DIAGRAM**  
E-2 SCALE: N.T.S.

REV.	DATE	BY	DESCRIPTION
1	11/20/14	TJB	CONSTRUCTION - ISSUED FOR CLIENT REVIEW
0	11/10/14	TJB	CONSTRUCTION - ISSUED FOR CLIENT REVIEW

PROFESSIONAL ENGINEER SEAL



**CEN TEK** engineering  
Centered on Solutions  
(203) 498-0380 Fax (203) 498-3387  
652 North Branford Road  
Branford, CT 06405  
www.CenTekEng.com


**AT&T MOBILITY**  
WIRELESS COMMUNICATIONS FACILITY  
**MERIDEN**  
SITE NUMBER: CT2117  
200 EDGE MARK ACRES  
MERIDEN, CT 06451

DATE: 11/03/14  
SCALE: AS NOTED  
JOB NO. 13305.000

ELECTRICAL  
RISER DIAGRAM,  
NOTES AND  
LEGEND

**E-2**





**1** SCHEMATIC DIAGRAM-GROUNDING SYSTEM  
E-3 NOT TO SCALE

**CELLULAR GROUNDING NOTES**

**OBJECTIVE**  
 PROVIDE A CELLULAR GROUNDING SYSTEM WITH MAXIMUM ALTERNATING CURRENT RESISTANCE OF 5 OHMS BETWEEN ANY POINT ON THE GROUNDING SYSTEM AND REFERENCE GROUND. PROVIDE EXTERIOR GROUNDING SCHEME WITH OWNERS APPROVAL AS REQUIRED TO ACHIEVE DESIRED MAXIMUM AC RESISTANCE TO GROUND. CONNECT

**TESTING**  
 CONTRACTOR TO PROVIDE AN INDEPENDENT TESTING CONTRACTOR TO DETERMINE THE GROUNDING SYSTEM RESISTANCE BY USE OF THE THREE POINT TEST AND AN AEMC MODEL 4500, OR APPROVED EQUAL. TEST TO BE PERFORMED PRIOR TO CONNECTION OF POWER SUPPLY TO THE CELL SITE AND CONNECTION OF THE GROUNDING SYSTEM TO THE WATER MAIN OR AC SUPPLY AS APPLICABLE.

**CONDUCTOR USED FOR CELLULAR GROUNDING SYSTEM**  
 EGR - #2 AWG ANNEALED SOLID TINNED BARE COPPER  
 IGR - #2 AWG ANNEALED STRANDED (7 STRAND) 'THW' GREEN COLORED INSULATION  
 INTER-BUS EXTENSION (FROM IGR TO EGR) - SEE DETAILS  
 EXTERNAL BOND CONNECTIONS TO EGR - #2 ANNEALED SOLID TINNED BARE COPPER  
 INTERIOR BOND CONNECTIONS TO IGR - #6 ANNEALED STRANDED (7 STRAND) 'THW' GREEN COLORED INSULATION

**MINIMUM BENDING RADIUS**  
 IGR #2 : 1'-0" NOMINAL AND 8" MINIMUM  
 EGR #2 : 2'-0" NOMINAL AND 8" MINIMUM  
 CELLULAR GROUNDING CONDUCTOR SHALL BE AS STRAIGHT AS POSSIBLE WITH MINIMUM 6" BENDING RADIUS.

**FASTENER FOR CELLULAR GROUNDING CONDUCTOR**  
 USE NON-METALLIC FASTENER AND STANDOFF 'CLIC' (AVAIL. FROM NEFCO 203-289-0285) TO SURFACE SUPPORT CONDUCTOR 3" AWAY FROM SURFACES.  
 SPACING OF FASTENERS: 2'-0" O.C. OUTSIDE BUILDING  
 3'-0" O.C. INSIDE BUILDING

**GROUNDING ELECTRODE**  
 GROUNDING ELECTRODE SHALL BE 5/8" DIA. x 10'-0" L. COPPER CLAD STEEL ROD. ADJUST LOCATION OF GROUNDING ELECTRODE IF SOIL CONDITION IS NOT CONDUCTIVE (GRAVEL, SANDY SOIL, ROCKS). SPACE GROUNDING ELECTRODES 8'-0" TO 10'-0" APART. ELECTRODES SHALL BE DRIVEN ONLY WITH PROPER DRIVER SLEEVE TO PREVENT MUSHROOMING TOP OF ROD. WHEN ROCK BOTTOM IS ENCOUNTERED, THE ELECTRODE SHALL BE DRIVEN AT AN OBLIQUE ANGLE NOT TO EXCEED 45° FROM THE VERTICAL AWAY FROM STRUCTURES. TOP OF GROUNDING ELECTRODE SHALL BE MIN. 3'-6" BELOW FINISH GRADE.

**CONNECTIONS ABOVE GRADE (MECHANICAL)**  
 COMPRESSION LUG CONNECTOR - 15 TON COMPRESSION, 2 HOLE, LONG BARREL, ELECTRO TINNED PLATED, HIGH CONDUCTIVITY, COPPER 600V RATED. USE 1/4" Ø BOLT, 3/4" SPACING LUGS TO BOND OBJECTS FROM THE IGR. (CONNECTOR SHALL BE BURNDY HYLUG SERIES OR EQUAL.)  
 EXOTHERMIC WELD LUG CONNECTOR - 2 HOLE, OFFSET, ELECTRO TINNED PLATED, HIGH CONDUCTIVITY, COPPER 600V. USE 1/2" Ø BOLT, 1-3/4" SPACING LUGS. CONNECTOR SHALL BE CADWELD CONNECTION STYLE (CABLE TO SURFACE) TYPE LA, LUG SIZE 1/8 x 1. EXOTHERMIC WELD TO LUG AS REQUIRED.  
 C-TAP COMPRESSION CONNECTOR - HIGH CONDUCTIVITY COPPER FOR MAIN TO BRANCH LINE TAPPING. (CONNECTOR SHALL BE BURNDY HYTAP SERIES OR EQUAL.)

**MECHANICAL CONNECTIONS**  
 USE MATCHING MANUFACTURER TOOL AND DIE FOR COMPRESSION CONNECTION.  
 APPLY ANTI-OXIDANT CONDUCTIVITY ENHANCER COMPOUND ON SURFACES THAT ARE COMPRESSED.  
 SURFACES INTENDED TO BE CONNECTED WITH MECHANICAL CONNECTORS SHALL BE BARE METAL TO BARE METAL. PRIME AND PAINT OVER BONDED AREA TO PREVENT CORROSION.

**WHEN BONDING #2 TO #2**  
 EXTERIOR OF BUILDING - USE EXOTHERMIC WELD CONNECTION  
 INTERIOR OF BUILDING - USE COMPRESSION CONNECTION ON STRANDED CONDUCTORS ONLY.  
 - USE EXOTHERMIC WELD CONNECTION ON SOLID CONDUCTOR.

**WHEN BONDING #2 TO FENCE POST**  
 USE EXOTHERMIC WELD 'CADWELD TYPE VS' CONNECTION TO FENCE POST STEEL SURFACE. TEST WELD FOR POSSIBLE BURN THRU. PATCH WELDED AREA WITH GALVANIZED COATING AS REQUIRED FOR PROPER WELDED PERMANENT BOND. REFER TO MANUFACTURER'S REQUIREMENTS FOR DETAILS

**GROUNDING SYSTEM INTERCONNECTION**  
 BOND THE EGR DOWN CONDUCTORS, AND/OR BURIED GROUND RING TO ANY METALLIC OBJECT OR EXISTING GROUNDING SYSTEM WITHIN 6".


**WHEN BONDING #2 TO TOWER GROUND PLATE**  
 TOWER GROUND PLATE SHALL BE 6" x 8" x 1/4" COPPER AND BE MADE AVAILABLE TO TOWER CONTRACTOR TO BE INSTALLED DURING TOWER CONSTRUCTION. USE EXOTHERMIC WELD 'CADWELD TYPE HS' TO TOWER GROUND PLATE TEST WELD FOR POSSIBLE BURN THRU. COORDINATE THE SIZE OF THE MOUNTING HOLE WITH TOWER CONTRACTOR.

**METALLIC CONDUITS**  
 BOND ALL STEEL CONDUITS TO PANELS AT POINT OF CONTACT WITH APPROVED GROUNDING BUSHING.

**GROUNDING SCHEMATIC NOTES**

- ① #2 AWG GREEN INSULATED
  - ② GROUND RING, #2 AWG BCW
  - ③ #2/0 GREEN INSULATED
  - ④ #6 AWG
  - ⑤ REFER TO RISER DIAGRAM FOR SPECIFICATIONS
  - ⑥ BOND ALL HALO GROUND RING TAILS TO GROUND RING. COORDINATE LOCATION AND QUANTITY WITH EQUIPMENT ROOM/SHELTER DRAWINGS
- GENERAL NOTES:**
1. ALL SURGE SUPPRESSION EQUIPMENT SHALL BE BONDED TO GROUND PER MANUFACTURER'S SPECIFICATIONS
  2. GROUND CONDUCTORS SHOWN SHALL BE #2 AWG SOLID TINNED BCW UNLESS OTHERWISE NOTED OR REQUIRED BY CODE.
  3. BOND CABLE TRAY AND ICE BRIDGE SECTIONS TOGETHER WITH #6 AWG STRANDED GREEN INSULATED JUMPERS.
  4. ALL SECTOR GROUND BARS SHALL BE BONDED TOGETHER WITH #2 AWG SOLID TINNED BCW.
  5. BOND ALL EQUIPMENT CABINETS AND BATTERY CABINETS TO GROUND PER MANUFACTURER'S SPECIFICATIONS.
  6. REFER TO GROUNDING PLAN FOR LOCATION OF GROUNDING DEVICES.
  7. REFER TO ALL ELECTRICAL AND GROUNDING DETAILS.
  8. COORDINATE ALL TOWER MOUNTED EQUIPMENT REQUIREMENTS WITH OWNER.
  9. ALL TOWER MOUNTED AMPLIFIERS AND ASSOCIATED EQUIPMENT SHALL BE BONDED TO THE SECTOR GROUND BAR PER MANUFACTURER'S SPECIFICATIONS.
  10. ALL GROUNDING SHALL BE IN ACCORDANCE WITH NEC AND OWNER'S REQUIREMENTS.
  11. ALL EXPOSED METAL OBJECTS IN SHELTER SHALL BE BONDED TO THE HALO GROUND WITHIN THAT ROOM.
  12. REFER TO RISER DIAGRAM FOR SPECIFICATIONS OF SERVICE GROUND AND TRANSFORMER GROUND.
  13. COORDINATE WITH CL&P TRANSMISSION DEPARTMENT REPRESENTATIVE TO DETERMINE ADDITIONAL GROUNDING REQUIREMENTS. PROVIDE ALL REQUIRED ELEMENTS TO MEET CL&P APPROVAL.
  14. COORDINATE WITH TOWER OWNER BEFORE INSTALLING ANY GROUNDING ELEMENTS ON TOWER OR BONDING TO EXISTING TOWER GROUND RING.

<p><b>AT&amp;T MOBILITY</b>          WIRELESS COMMUNICATIONS FACILITY  <b>MERIDEN</b>          SITE NUMBER: CT2117          200 EDGE MARK ACRES          MERIDEN, CT 06451</p>	<p>CONSTRUCTION - ISSUED FOR CLIENT REVIEW          CVD          CVD          CVD          TJB          TJB          TJB          DATE          11/20/14          11/10/14          0          REV.          1          0</p>
<p><b>at&amp;t</b></p> <p><b>SAI</b> communications</p>	<p>PROFESSIONAL ENGINEER SEAL</p> <p><b>CEN TEK</b> engineering          Center on Solutions          (203) 498-0380          (203) 498-3887 Fax          652 North Branford Road          Branford, CT 06405          www.CenTekEng.com</p>
<p>DATE: 11/03/14          SCALE: AS NOTED          JOB NO. 13305.000</p>	<p><b>ELECTRICAL GROUNDING SYSTEM</b></p> <p><b>E-3</b></p> <p>Sheet No. 11 of 17</p>



**GROUNDING PLAN NOTES**

- ① #2 SOLID TINNED BCW GROUND RING (TYP. 2'-0" FROM OUTSIDE EDGE OF EQUIPMENT SHELTER FOUNDATION) (TYP.).
- ② WAVEPORT GROUND BAR SEE DETAIL.
- ③ BOND HVAC UNITS TO GROUND RING.
- ④ GROUNDING ROD WITH ACCESS (TYP.) SEE DETAILS.
- ⑤ GROUNDING ROD (TYP.) SEE DETAILS.
- ⑥ TELEPHONE CABINET GROUNDING. (SEE RISER DIAGRAM).
- ⑦ CADCWELDED EQUIPMENT BUILDING TO GROUND RING (TYP.).
- ⑧ BOND SHELTER TAIL GROUND LEADS TO SHELTER GROUND RING (TYP. 6 PLACES).
- ⑨ BOND TO EXISTING TOWER GROUND RING. CONTRACTOR TO VERIFY LOCATION/CONFIGURATION IN FIELD. COORDINATE WITH TOWER OWNER. (TYP.)
- ⑩ BOND GROUNDING TRIAD TO GROUND RING.
- ⑪ UPPER TOWER MOUNTED SECTOR GROUND BAR.
- ⑫ LOWER TOWER MOUNTED GROUND BAR.
- ⑬ BOND UPPER TOWER MOUNTED GROUND BAR TO LOWER TOWER MOUNTED GROUND BAR (2 GROUND LEADS).
- ⑭ MAIN SERVICE GROUND. (SEE RISER DIAGRAM).
- ⑮ GROUNDING TRIAD (REFER TO DETAIL).
- ⑯ BOND UTILITY FRAME SUPPORT POSTS TO GROUNDING TRIAD.

**NOTES**

- 1. COORDINATE WITH RISER DIAGRAM, GROUNDING SYSTEM SCHEMATIC DIAGRAM, AND ALL GROUNDING DETAILS.
- 2. REFER TO ALL ELECTRICAL AND GROUNDING DETAILS.
- 3. ALL GROUNDING WORK MUST BE COORDINATED WITH, AND APPROVED BY TOWER OWNER PRIOR TO INSTALLATION.
- 4. PROVIDE ANY ADDITIONAL GROUNDING ELEMENTS REQUIRED BY TOWER OWNER.
- 5. SOME LANDSCAPING NOT SHOWN FOR CLARITY. REFER TO CIVIL DRAWINGS.

1 **GROUNDING PLAN**  
 E-4 SCALE: 1" = 4'  
 APPROX. NORTH

GRAPHIC SCALE  
 ( IN FEET )  
 1 inch = 4 ft.

REV.	DATE	BY	CHK'D BY	DESCRIPTION
1	11/20/14	TJB	CJD	CONSTRUCTION - ISSUED FOR CLIENT REVIEW
0	11/10/14	TJB	CJD	CONSTRUCTION

PROFESSIONAL ENGINEER SEAL



**CEN TEK** engineering  
 Centered on Solutions  
 (203) 488-0380  
 (203) 488-3887 Fax  
 652 North Branford Road  
 Branford, CT 06405  
 www.CenTekEng.com


**AT&T MOBILITY**  
 WIRELESS COMMUNICATIONS FACILITY  
**MERIDEN**  
 SITE NUMBER: CT2117  
 200 EDGE MARK ACRES  
 MERIDEN, CT 06451

DATE: 11/03/14  
 SCALE: AS NOTED  
 JOB NO. 13305.000

ELECTRICAL  
 GROUNDING PLAN



**NORTHEAST UTILITIES - TOWER GROUNDING SYSTEM NOTES**



**1 NU TOWER GROUNDING DETAIL**  
E-5 NOT TO SCALE

**NU TOWER GROUNDING NOTES:**

**(NORTHEAST UTILITIES REQUIREMENTS)**

- (A)** STEEL HYBRID POLE.
- (B)** CONCRETE CAISSON TYPE FOUNDATION.
- (C)** STRANDED COPPERWELD SPOKE FROM POLE GROUND TO GRADING RING. SPOKES ARE A CONTINUATION OF STRANDED COPPERWELD COUNTERPOISE CONNECTING GRADING RING TO POLE GROUND. SPOKES TO SLOPE ON STRAIGHT LINE FROM GROND LEVEL TO GRADING RING.
- (D)** PARALLEL GROVE CONNECTOR, NU SC190052.
- (E)** GRADING RING Ø 18" MINIMUM BELOW GRADE AND 24" TO 30" FROM TOWER FOUNDATION. GRADING RING TO BE 3 NO. 8 STRANDED ANEALED COPPERWELD.
- (F)** COUNTERPOISE, 3 NO. 8 STRANDED ANEALED COPPERWELD (TYPICAL).
- (G)** COPPERWELD POLE GROUND.

GENERAL NOTES:  
 1. THE INFORMATION ON THIS SHEET REPRESENTS TYPICAL NORTHEAST UTILITIES GROUNDING REQUIREMENTS. CONTRACTOR MUST COORDINATE WITH NORTHEAST UTILITIES SITE MANAGER FOR SPECIFIC (AND CURRENT) GROUNDING REQUIREMENTS AT THIS SITE.

- GENERAL-**
1. THE OWNER WILL FURNISH THE WIRE, CONNECTORS, AND MISCELLANEOUS MATERIAL ASSOCIATED WITH THE COUNTERPOISE GROUNDING SYSTEM.
  2. THE CONTRACTOR SHALL FURNISH ALL LABOR, MATERIALS AND EQUIPMENT NECESSARY TO INSTALL THE GROUNDING SYSTEM AND TO REHABILITATE THE RIGHT-OF-WAY AS CLOSE AS POSSIBLE TO ITS ORIGINAL CONDITION.
  3. THE CONTRACTOR SHALL HANDLE AND TRANSPORT THE OWNER SUPPLIED MATERIAL FROM THE OWNER'S STOREROOMS AND YARDS TO THE JOB SITE AND SHALL RETURN SURPLUS MATERIAL AND EMPTY REELS TO DESIGNATED STOREROOMS AND YARDS UPON COMPLETION OF THE CONTRACT.
  4. NORTHEAST UTILITIES WILL BE RESPONSIBLE FOR PERFORMING TESTS FOR SURGE IMPEDANCE AND WAVE IMPEDENCE.

- INSTALLATION-**
1. UNLESS OTHERWISE DURECTED BY THE OWNER'S REPRESENTATIVE, COUNTERPOISE SHALL BE BURIED A MINIMUM OF 24" IN CULTIVATED AREAS AND 18" IN WOODED OR OTHER AREAS. FOR ROCKY AREAS OR WHERE OBSTRUCTIONS ARE ENCOUNTERED, THE COUNTERPOISE SHALL BE DIVERTED AROUND SUCH OBSTRUCTIONS. ALL INSTALLATIONS SHALL INCLUDE CONNECTIONS TO EXISTING OR PROPOSED STRUCTURES, AND SUCH CONNECTIONS SHALL BE MADE BELOW GROUND USING BOLTED PARALLEL GROVE CONNECTORS.
  2. WHERE MULTIPLE STUCTURE GROUNDS EXIST AT MULTI POLE STRUCTURES, THEY SHALL BE CONNECTED TOGETHER WITH BURIED COPPERWELD WIRE, BUT ONLY IF SUCH GROUNDS HAVE METALLIC CONNECTIONS UP THE POLES TO THE SHIELD WIRE(S). AT STRUCTURES THAT HAVE PALE GROUNDS AND ALSO POLE GUY GROUNDS, CONNECTIONS SHALL BE MADE ONLY TO THE POLE GROUNDS, AND THE MINIMUM SPACING BETWEEN THE COUNTERPOISE AND ANCHOR RODS SHALL BE 10'. AT WOOD POLE STRUCTURES WHERE NO SUCH POLE GROUND EXISTS, COUNTERPOISE CONNECTIONS SHALL BE MADE TO THE POLE TOP GUYS.
  3. FOR SINGLE CONTINUOUS (TYPE A) AND SINGLE BROKEN (TYPE B) COUNTERPOISE, THE WIRE SHALL IN GENERAL BE LAYED AT THE CENTERLINE OF THE TRANSMISSION LINE. FOR DOUBLE CONTINUOUS (TYPE C) AND DOUBLE BROKEN (TYPE D) COUNTERPOISE, THE WIRES SHALL IN GENERAL SHALL BE LAYED UNDER THE OUTSIDE PHASE WIRES OF THE TRANSMISSION LINE. COUNTERPOISE SHALL NOT BE INSTALLED ACROSS BROOKS, RIVERS, HIGHWAYS, RAILROADS, OR IN THE VICINITY OF TELEPHONE CABLES OR PIPELINES.
  4. AT STEEL POLE STRUCTURES, A BURIED GRADING RING AND SPOKES SHALL ALSO BE INSTALLED AROUND THE STRUCTURE UNLESS THE STRUCTURE HAS A PAD AND PIER FOUNDATION OR UNLESS A RING ALREADY EXISTS. COUNTERPOISE WIRE SHALL BE CONNECTED AT TWO PLACES TO EACH RING, AND COPPERWELD SPOKES SHALL SLOPE LINEARLY UP TO THE STRUCTURE GROUND.
  5. AT WOOD POLE STRUCTURES, AN 8' LENGTH OF PLASTIC MOULDING SHALL BE STAPLED OVER THE BOTTOM WITH 8' OF DOWNLEAD.

- GROUND RODS-**
1. WHERE GROUND RODS ARE REQUIRED, THEY SHALL BE SINGLE OR SECTIONAL WITH THE LENGTH SPECIFIED. THEY SHALL BE DRIVEN VERTICALLY INTO THE GROUND TO A DEPTH WHICH WILL LEAVE THE TOP OF THE ROD AT LEAST 12" BELOW GRADE. ALL RODS SHALL BE CONNECTED TO COUNTERPOISE OR TO POLE GROUNDS USING BOLTED CONNECTORS.

- REHABILITATION-**
1. SELECTIVE CLEARING PROCEDURES WERE USED IN THE DEVELOPMENT OF THE RIGHT-OF-WAY, AND GROWTH OF SELECTED SPECIES HAS BEEN SAVED. THE CONTRACTOR SHALL NOT VIOLATE THE OWNER'S INTENT TO SAVE SELECTIVE SPECIES AND IMPOSE THE MINIMUM ENVIRONMENTAL IMPACT ON THE RIGHT OF WAY DURING THE EXECUTION OF THE WORK. THE CONTRACTOR SHALL REVIEW THE ROUTING OF EACH SECTION OF COUNTERPOISE WITH THE OWNER'S REPRESENTATIVE PRIOR TO ITS FIELD SPECIFIED LOCATION. THE CONTRACTOR IS RESPONSIBLE TO THE OWNER FOR DAMAGES TO THE RIGHT-OF-WAY IN OTHER THAN THE FIELD SPECIFIED LOCATIONS.
  2. ANY BRUSH ALONG THE FIELD SPECIFIED COUNTERPOISE ROUTES WHICH IS LEFT IN AN UNSIGHTLY CONDITION BY THE INSTALLATION WORK WILL BE CUT TO THE GROUND BY THE CONTRACTOR AND LEFT IN SMALL, NEAT PILES IN PLACE WHERE CUT.
  3. IN LOCATIONS WHERE EXCAVATION FOR THE INSTALLATION OF COUNTERPOISE BRINGS TO THE SURFACE ANY SMALL BOULDERS, THEY WILL BE BACKFILLED BELOW GRADE OR DIPERSED ON THE RIGHT-OF-WAY AS THE OWNER'S REPRESENTATIVE MAY DIRECT. INSTALLATION OF THE COUNTERPOISE SHALL NOT RESULT IN A PATH OF SMALL BOULDERS ON THE FINISHED SURFACE.
  4. THE OWNER ANTICIPATES THAT SEASONAL CONDITIONS MAY NOT ALLOW PERMANENT REHABILITATION OF WORK SITES AND THE RIGHT-OF-WAY UPON COMPLETION OF THE INSTALLATION OF THE COUNTERPOISE. WHERE TEMPORARY REHABILITATION HAS BEEN COMPLETED IN ADVERSE SEASON, THE CONTRACTOR SHALL TAKE THE FOLLOWING STEPS:
    - A. WATERBARS WILL BE CONSTRUCTED ON ACCESS ROADS AND TRENCH LINES TO SHUNT WATER OFF THIS LINE OF DISTURBED SURFACES AND CONTROL EROSION ALONG THE DISTURBED SURFACE.
    - B. ALL DISTURBED SURFACES OF FOUNDATION SITES OR ALONG TRENCH LINES OR ACCESS ROADS SHALL BE GRADED AND COVERED WITH HAY MULCH. SUCH DISTURBED SURFACES ON SLOPES GREATER THAN ONE (VERTICAL) ON FOUR (HORIZONTAL) SHALL BE COVERED WITH WOOD CHIPS.

5. AS DRYING CONDITIONS PERMIT IN THE SPRING, FOLLOWING COMPLETION OF THE INSTALLATION OF COUNTERPOISE, PERMANENT REHABILITATION OF ALL DISTURBED OR ERODED SURFACES SHALL BE ACCOMPLISHED AS FOLLOWS:
  - A. LAWN, GOLF COURSES, CEMETARIES AND OTHER SIMILAR OCCUPANCIES SHALL BE LOAMED, GRADED, FERTILIZED, SEEDED AND WHERE APPROPRIATE, MULCHED, TO ESTABLISH A REHABILITATION CONSISTANT WITH THE USE ESTABLISHED BY THE OCCUPANT.
  - B. GARDENS, OTHER CULTIVATED AREAS AND PASTURES, SHALL BE GRADED AND TOPSOILED TO RESTORE THE DEPTH OF FERTILE SOIL COMMON TO THE ADJACENT GROUND. WHERE APPROPRIATE, SEEDING SHALL BE DONE IN ACCORDANCE WITH STEP C BELOW.
  - C. THE CONTRACTOR SHALL SEED ALL DISTURBED AREAS ALONG THE NEW COUNTERPOISE ROUTES. SEED SHALL BE SPREAD AT THE RATE OF 100 LBS. PER ACRE AND SHALL BE AS FOLLOWS OR APPROVED EQUAL:

	<b>% BY WEIGHT</b>	<b>% BY GERMINATION</b>	<b>% BY PURITY</b>
CREeping RED FESCUE	30	85	98
DOMESTIC RYE	20	90	98
KENTUCKY TALL FESCUE	50	--	--
	100		

- D. ALL OTHER DISTURBED AREAS INCLUDING REMAINING FOUNDATION SITES, ACCESS ROADS, AND REPAIR OF EROSION OF SITUATION SHALL BE SEEDED WITH MIXED SPECIFICATION ABOVE. IN REMOTE AREAS, A CONSERVATION MIX, AS USED BY THE CONNECTICUT STATE PARKS AND FOREST COMMISSION MAY BE SUBSTITUTED. ALL AREAS WHICH EXPERIENCED EROSION DAMAGE AND ALL SLOPES OVER ONE (VERTICAL) AND FOUR (HORIZONTAL) WHERE TEMPORARY REHABILITATION WORK HAS BEEN DONE SHALL BE REMULCHED.
6. IT IS IMPERATIVE THAT PERMANENT REHABILITATION BE ACCOMPLISHED IN GOOD TIME, WHICH WILL ALLOW THE OCCUPANT FULL AND UNDISTURBED USE OF THE SITE IN THE SUCCEEDING SEASON, AND TO PREVENT UNNECESSARY AND UNREASONABLE SPREADING OF CONTINUATION OF DISTURBED SURFACES.
7. ANY BRUSH ALONG THE ACCESS ROADS WHICH IS LEFT IN AN UNSIGHTLY CONDITION BY THE WORK CONDUCTED, SHALL BE CUT TO THE GROUND BY THE CONTRACTOR AND LEFT IN SMALL NEAT PILES IN PLACE WHERE CUT.

NO.	DATE	BY	DESCRIPTION
1	11/20/14	TJB	
0	11/10/14	TJB	

PROFESSIONAL ENGINEER SEAL




**CENTEK** engineering  
 Centek on Solutions  
 (203) 498-0390  
 (203) 498-3597 Fax  
 652 North Branford Road  
 Branford, CT 06405  
 www.CentekEng.com

AT&T MOBILITY  
 WIRELESS COMMUNICATIONS FACILITY  
**MERIDEN**  
 SITE NUMBER: CT2117  
 200 EDGE MARK ACRES  
 MERIDEN, CT 06451


DATE: 11/03/14  
 SCALE: AS NOTED  
 JOB NO. 13305.000

N.U. GROUNDING  
 PLAN, DETAILS  
 AND NOTES







**1 GROUND TRIAD DETAIL**  
E-6 NOT TO SCALE




**2 RRH POLE MOUNT GROUNDING**  
E-6 NOT TO SCALE



**3 CABLEPORT GROUND BAR LUG CONNECTION**  
E-6 NOT TO SCALE



**4 EQUIPMENT GROUND BAR DETAIL**  
E-6 NOT TO SCALE



- NOTES**
- ① TINNED COPPER GROUND BAR, 1/4" x 4" x 20", NEWTON INSTRUMENT CO. HOLE CENTERS TO MATCH NEMA DOUBLE LUG CONFIGURATION.
  - ② INSULATORS, NEWTON INSTRUMENT CAT. NO. 3061-4.
  - ③ 5/8" LOCK WASHERS, NEWTON INSTRUMENT CO. CAT. NO. 3015-8.
  - ④ WALL MOUNTING BRACKET, NEWTON INSTRUMENT CO. CAT NO. A-6056.
  - ⑤ 5/8-11 x 1" STAINLESS STEEL TRUSS SPANNER MACHINE SCREWS.

**5 GROUND BAR DETAIL**  
E-6 NOT TO SCALE

**WARNING**

ARC FLASH & SHOCK HAZARD  
APPROPRIATE PPE REQUIRED

MAXIMUM AVAILABLE FAULT  
CURRENT:  
**XX,XXX AMPS**

DATE: MM/DD/YYYY

- NOTES:**
1. REFER TO SPECIFICATIONS FOR FOR ADDITIONAL NAMEPLATE REQUIREMENTS.
  2. PROVIDE WARNING LABEL ON ALL SERVICE EQUIPMENT IN ACCORDANCE WITH 2011 NEC 110.24.

**6 DETAIL OF TYPICAL FAULT CURRENT SIGN**  
E-6 NOT TO SCALE


**DANGER**

ARC FLASH AND SHOCK HAZARD.

APPROPRIATE PPE REQUIRED.


- NOTES:**
1. REFER TO SPECIFICATIONS FOR FOR ADDITIONAL NAMEPLATE REQUIREMENTS.
  2. PROVIDE WARNING LABEL ON ALL SWITCHBOARDS, DISTRIBUTION PANELS, PANELBOARDS IN ACCORDANCE WITH 2005 NEC 110.16.

**7 DETAIL OF TYPICAL FLASH PROTECTION WARNING SIGN**  
E-6 NOT TO SCALE




- NOTE:**
1. DO NOT INSTALL CABLE GROUND KIT AT A BEND AND ALWAYS DIRECT GROUND WIRE DOWN TO GROUND BAR.

**8 ANTENNA CABLE GROUNDING DETAIL**  
E-6 NOT TO SCALE




- NOTE:**
1. GROUND PLATE DETAIL TO BE USED ONLY IF 10 FT. GROUND ROD DEPTH CANNOT BE ACHIEVED DUE TO LEDGE CONDITION OR IF EXISTING TOWER FOUNDATION IS ENCOUNTERED.

**8A GROUND PLATE DETAIL**  
E-6 NOT TO SCALE



- NOTE:**
1. USE GROUND PLATE DETAIL IF 10 FT. GROUND ROD DEPTH CANNOT BE ACHIEVED DUE TO LEDGE CONDITION OR IF EXISTING TOWER FOUNDATION IS ENCOUNTERED.

**9 GROUND ROD DETAIL**  
E-6 NOT TO SCALE



- NOTE:**
1. INSPECTION HAND HOLE MAY BE CONCRETE OR PVC AND SHALL BE A MINIMUM OF 12" DIA x 18" DEEP.

**10 GROUND ROD WITH ACCESS DETAIL**  
E-6 NOT TO SCALE

REV.	DATE	BY	CHK'D BY	DESCRIPTION
1	11/20/14	TJB		CONSTRUCTION - ISSUED FOR CLIENT REVIEW
0	11/10/14	TJB		CONSTRUCTION -

PROFESSIONAL ENGINEER SEAL




**CEN TEK engineering**  
Center on Solutions  
(203) 498-0390  
(203) 498-3397 Fax  
652 North Branford Road  
Branford, CT 06405  
www.CenTekEng.com

**AT&T MOBILITY**  
WIRELESS COMMUNICATIONS FACILITY  
**MERIDEN**  
SITE NUMBER: CT2117  
200 EDGE MARK ACRES  
MERIDEN, CT 06451

DATE: 11/03/14  
SCALE: AS NOTED  
JOB NO. 13305.000

ELECTRICAL  
DETAILS






**NOTES:**

- ENGINEER SHALL INSPECT PLACEMENT OF EGR CONDUCTOR PRIOR TO BACKFILLING.
- MAINTAIN MIN. 2'-0" LINEAR CLEARANCE BETWEEN BACKFILL AND THE FOLLOWING: FOUNDATION, UNDERGROUND PIPING/CONDUIT, UNDERGROUND SERVICES. IN THE CLEARANCE AREAS, USE EARTH BACKFILL INSTEAD.
- EXERCISE HANDLING AND USE PRECAUTION OF BACKFILL MATERIAL PER MFR'S REQUIREMENTS.
- FOR LOCATIONS WHERE ROCK BOTTOM DEPTH IS LESS THAN 12" CONDUCTIVE CONCRETE SHALL BE USED INSTEAD OF CONDUCTIVE BACKFILL.
- PROVIDE MIN 2" CLEARANCE ON ALL SIDES OF GROUND PLATE.


**1 GROUND PLATE TRENCH/BACKFILL DETAIL (SHALLOW TOPSOIL)**  
E-7 NOT TO SCALE



**NOTES:**

- ENGINEER SHALL INSPECT PLACEMENT OF EGR CONDUCTOR PRIOR TO BACKFILLING.
- MAINTAIN MIN. 2'-0" LINEAR CLEARANCE BETWEEN BACKFILL AND THE FOLLOWING: FOUNDATION, UNDERGROUND PIPING/CONDUIT, UNDERGROUND SERVICES. IN THE CLEARANCE AREAS, USE EARTH BACKFILL INSTEAD.
- EXERCISE HANDLING AND USE PRECAUTION OF BACKFILL MATERIAL PER MFR'S REQUIREMENTS.
- FOR LOCATIONS WHERE ROCK BOTTOM DEPTH IS LESS THAN 12" CONDUCTIVE CONCRETE SHALL BE USED INSTEAD OF CONDUCTIVE BACKFILL.


**2 EGR TRENCH/BACKFILL DETAIL (SHALLOW TOPSOIL)**  
E-7 NOT TO SCALE




**NOTES:**

- ENGINEER SHALL INSPECT PLACEMENT OF EGR CONDUCTOR PRIOR TO BACKFILLING.
- MAINTAIN MIN. 2'-0" LINEAR CLEARANCE BETWEEN NATURAL CLAY BACKFILL AND THE FOLLOWING: FOUNDATION, UNDERGROUND PIPING/CONDUIT, UNDERGROUND SERVICES. IN THE CLEARANCE AREAS, USE EARTH BACKFILL INSTEAD.
- EXERCISE HANDLING AND USE PRECAUTION OF BACKFILL MATERIAL PER MFR'S REQUIREMENTS.

**3 EGR TRENCH/BACKFILL DETAIL**  
E-7 NOT TO SCALE




- NOTES**
- HIGH CONDUCTIVITY TINNED COPPER BAR 1'-8" Lx4"Wx1/4"D.
  - RED COLORED STANDOFF INSULATOR PLASTIC #1872-1A.
  - STAINLESS STEEL TRUSS SPANNER MACHINE SCREWS, SPLIT LOCKWASHER AND FLAT WASHER.
  - 1"Wx1/8"T STAINLESS STEEL TYPE 304 BRACKET.
  - STAINLESS STEEL TYPE 304 HARDWARE - 3/8" EXPANSION BOLT FOR CONCRETE.



**TYPICAL GROUND BAR - DIMENSIONS**  
N.T.S.


**4 MASTER/EQUIPMENT GROUND BAR DETAILS**  
E-7 N.T.S.



**NOTE:**

- DO NOT INSTALL CABLE GROUND KIT AT A BEND AND ALWAYS DIRECT GROUND WIRE DOWN TO CIGBE

**5 CONNECTION OF GROUND WIRES TO GROUND BAR**  
E-7 NOT TO SCALE



**NOTE:**

- NUMBER OF GROUND BARS MAY VARY DEPENDING ON THE TYPE OF TOWER, LOCATION AND CONNECTION ORIENTATION. PROVIDE AS REQUIRED.

**6 ANTENNA CABLE GROUNDING - LATTICE TOWER**  
E-7 NOT TO SCALE

CONSTRUCTION	ISSUED FOR CLIENT REVIEW
CONSTRUCTION	DESCRIPTION
CD	CHK'D BY
TJB	DATE
1	11/20/14
0	11/10/14
REV.	

PROFESSIONAL ENGINEER SEAL



**CENITEK engineering**  
Centered on Solutions  
(203) 498-0380  
(203) 498-3887 Fax  
652 North Branford Road  
Branford, CT 06405  
www.CenitekEng.com


**AT&T MOBILITY**  
WIRELESS COMMUNICATIONS FACILITY  
**MERIDEN**  
SITE NUMBER: CT2117  
200 EDGE MARK ACRES  
MERIDEN, CT 06451

DATE: 11/03/14  
SCALE: AS NOTED  
JOB NO. 13305.000


ELECTRICAL DETAILS

**E-7**







**1 CELLULAR GROUNDING CONDUCTOR SECURED ON WALL**  
E-8 N.T.S.



**2 ICE BRIDGE BONDING DETAIL**  
E-8 NOT TO SCALE



**3 TYPICAL EXTERIOR/INTERIOR GROUNDING CONNECTION**  
E-8 NOT TO SCALE



**BILL OF MATERIALS**



ITEM	DESCRIPTION	QUANTITY
1	2-1/2" SCH. 40 x 8'-0" LG. MAX SS OR GALV. PIPE	1
2	UNIVERSAL CLAMP SET.	2

**4 GPS ANTENNA MOUNTING BRACKET DETAIL**  
E-8 NOT TO SCALE


**NOTES**

1 THE ELEVATION AND LOCATION OF THE GPS ANTENNA SHALL BE IN ACCORDANCE WITH THE FINAL RF REPORT.

2 THE GPS ANTENNA MOUNT IS DESIGNED TO FASTEN TO A STANDARD 2-1/2" DIAMETER, SCHEDULE 40, GALVANIZED STEEL OR STAINLESS STEEL PIPE. THE PIPE MUST NOT BE THREADED AT THE ANTENNA MOUNT END. THE PIPE SHALL BE CUT TO THE REQUIRED LENGTH (MINIMUM OF 24 INCHES) USING A HAND OR ROTARY PIPE CUTTER TO ASSURE A SMOOTH AND PERPENDICULAR CUT. A HACK SAW SHALL NOT BE USED. THE CUT PIPE END SHALL BE DEBURRED AND SMOOTH IN ORDER TO SEAL AGAINST THE NEOPRENE GASKET ATTACHED TO THE ANTENNA MOUNT.



**5 MASTER/EQUIPMENT GROUND BAR DETAILS**  
E-8 N.T.S.



**6 TYPICAL ANTENNA GROUNDING DETAIL**  
E-8 NOT TO SCALE

REV.	DATE	DRAWN BY	CHECKED BY	CONSTRUCTION -	ISSUED FOR CLIENT REVIEW
1	11/20/14	TJB	CJD	CONSTRUCTION	
0	11/10/14	TJB	CJD	CONSTRUCTION	

PROFESSIONAL ENGINEER SEAL



**CEN TEK engineering**  
Centered on Solutions™  
(203) 488-0380  
(203) 488-3387 Fax  
652 North Branford Road  
Branford, CT 06405  
www.CenTekEng.com

AT&T MOBILITY  
WIRELESS COMMUNICATIONS FACILITY  
**MERIDEN**  
SITE NUMBER: CT2117  
200 EDGE MARK ACRES  
MERIDEN, CT 06451

DATE: 11/03/14  
SCALE: AS NOTED  
JOB NO. 13305.000

ELECTRICAL DETAILS







# ATTACHMENT B

**Structural Design of**  
**Antenna Frame and Analysis**  
**of CL&P Tower**

*AT&T Mobility Site Ref: CT2117*

*CL&P Structure No. 783*  
*78' Electric Transmission Lattice Tower*

*200 Edgemark Acres*  
*Meriden, CT*

*CEN TEK Project No. 13305*

*~~Date: January 7, 2014~~*  
*Rev 4: October 6, 2014*



**Prepared for:**  
**AT&T Mobility**  
**500 Enterprise Drive, Suite 3A**  
**Rocky Hill, CT 06067**

# **Table of Contents**

## **SECTION 1 - REPORT**

- INTRODUCTION
- PRIMARY ASSUMPTIONS USED IN THE ANALYSIS
- ANALYSIS
- DESIGN BASIS
- RESULTS
- CONCLUSION

## **SECTION 2 - CONDITIONS & SOFTWARE**

- STANDARD ENGINEERING CONDITIONS
- GENERAL DESCRIPTION OF STRUCTURAL ANALYSIS PROGRAMS
  - RISA 3-D
  - PLS TOWER

## **SECTION 3 - DESIGN CRITERIA**

- CRITERIA FOR DESIGN OF PCS FACILITIES ON OR EXTENDING ABOVE METAL ELECTRIC TRANSMISSION TOWERS
- NU DESIGN CRITERIA TABLE
- PCS SHAPE FACTOR CRITERIA
- WIRE LOADS SHEET

## **SECTION 4 - DRAWINGS**

- T-1 TITLE SHEET
- N-1 DESIGN BASIS AND GENERAL NOTES
- N-2 EARTHWORK AND FOUNDATION CONSTRUCTION NOTES
- N-3 CONCRETE CONSTRUCTION NOTES
- N-4 STRUCTURAL STEEL NOTES
- MI-1 MODIFICATION INSPECTION REQUIREMENTS
- S-1 TOWER ELEVATION AND FEEDLINE PLAN
- S-2 FOUNDATION REINFORCEMENT DETAILS
- S-3 TOWER REINFORCEMENT DETAILS
- S-4 ANTENNA FRAME ELEVATIONS
- S-5 ANTENNA FRAME PLAN AND DETAILS



**SECTION 5 - EIA/TIA-222-F LOAD CALCULATIONS FOR ANTENNA FRAME**

- ANTENNA FRAME WIND & ICE LOAD

**SECTION 6 - ANTENNA FRAME DESIGN PER EIA/TIA-222F**

- LOAD CASES AND COMBINATIONS (TIA/EIA LOADING)
- RISA 3-D ANALYSIS REPORT
- MAST CONNECTION ANALYSIS

**SECTION 7 - NECS/NU LOAD CALCULATIONS FOR OBTAINING REACTIONS APPLIED TO UTILITY STRUCTURE**

- ANTENNA FRAME WIND LOAD

**SECTION 8 – ANTENNA FRAME ANALYSIS PER NESC/NU FOR OBTAINING REACTIONS APPLIED TO UTILITY STRUCTURE**

- LOAD CASES AND COMBINATIONS (NESC/NU LOADING)
- RISA 3-D ANALYSIS REPORT

**SECTION 9 - PLS TOWER RESULTS FROM ANTENNA FRAME REACTIONS CALCULATED IN RISA WITH NESC/NU CRITERIA**

- COAX CABLE LOAD ON CL&P TOWER CALCULATION
- PLS REPORT
- LOCAL STRESS CHECK – UNREINFORCED SECTION
- LOCAL STRESS CHECK – REINFORCED SECTION
- FOUNDATION ANALYSIS

**SECTION 10 - REFERENCE MATERIAL**

- RFDS SHEET
- EQUIPMENT CUT SHEETS

## *I n t r o d u c t i o n*

The purpose of this report is to design a proposed antenna mast and analyze the existing 78' CL&P tower located at 200 Edgemark Acres in Meriden, CT for the proposed AT&T Mobility antenna installation.

The proposed loads consist of the following:

- **AT&T MOBILITY (Proposed):**  
**Antennas:** Six (6) Andrew CCI HPA-65R-BUU-H8 panel antennas, three (3) Andrew CCI OPA-65R-LCUU-H8 panel antennas and eighteen (18) CCI BPDB7823VG12A TMA's mounted on a Site-Pro Ultra-Low Profile Platform p/n ULP12-496 with a RAD center elevation of 88-ft above grade.  
**Coax Cables:** Thirty-six (36) 1-5/8" Ø coax cables running on two (2) legs of the existing tower as indicated in section 4 of this report.

## *P r i m a r y a s s u m p t i o n s u s e d i n t h e a n a l y s i s*

- Allowable steel stresses are defined by AISC-ASD 9<sup>th</sup> edition for design of the ANTENNA Mast and antenna supporting elements.
- ASCE Manual No. 10-97, "Design of Latticed Steel Transmission Structures", defines allowable steel stresses for evaluation of the CL&P utility tower.
- All utility tower members are adequately protected to prevent corrosion of steel members.
- All proposed antenna mounts are modeled as listed above.
- All coaxial cable will be installed as indicated in Section 4 of this report.
- ANTENNA Mast will be properly installed and maintained.
- No residual stresses exist due to incorrect tower erection.
- All bolts are appropriately tightened providing the necessary connection continuity.
- All welds conform to the requirements of AWS D1.1.
- ANTENNA Mast and utility tower will be in plumb condition.
- Utility tower was properly installed and maintained and all members were properly designed, detailed, fabricated, and installed and have been properly maintained since erection.
- Any deviation from the analyzed loading will require a new analysis for verification of structural adequacy.

## A n a l y s i s

Structural design of the antenna frame was independently completed using the current version of RISA-3D computer program licensed to CENTEK Engineering, Inc.

The antenna mast consisting of a HSS12.5"x0.625" conforming to ASTM A500 Grade 42 ( $F_y = 42\text{ksi}$ ) mounted on a 18'-6" antenna frame connected at eight points to the existing tower was analyzed for its ability to resist loads prescribed by the TIA/EIA standard. Section 5 of this report details these gravity and lateral wind loads. NESC prescribed loads were also applied to the antenna mast in order to obtain reactions needed for analyzing the CL&P tower structure. These loads are developed in Section 7 of this report. Load cases and combinations used in RISA-3D for TIA/EIA loading and for NESC/NU loading are listed in report Sections 6 and 8, respectively.

An envelope solution was first made to determine maximum and minimum forces, stresses, and deflections to confirm the selected section as adequate. Additional analyses were then made to determine the NESC forces to be applied to the CL&P tower structure.

The RISA-3D program contains a library of all AISC shapes and corresponding section properties are computed and applied directly within the program. The program's Steel Code Check option was also utilized. The forces calculated in RISA-3D using NESC guidelines were then applied to the CL&P tower using PLS-Tower. Maximum usage for the tower was calculated considering the additional forces from the mast and associated appurtenances.

## D e s i g n B a s i s

Our analysis was performed in accordance with EIA-222-F-1996, ASCE Manual No. 10-97, "Design of Latticed Steel Transmission Structures", NESC C2-2007 and Northeast Utilities Design Criteria.

The CL&P tower structure, considering existing and future conductor and shield wire loading, with the proposed antenna mast was analyzed under two conditions:

- **UTILITY TOWER ANALYSIS**

The purpose of this analysis is to determine the adequacy of the existing utility structure to support the proposed antenna loads. The loading and design requirements were analyzed in accordance with the NU Design Criteria Table, NESC C2-2007 ~ Construction Grade B, and ASCE Manual No. 10-97, "Design of Latticed Steel Transmission Structures".

Load cases considered:

Load Case 1: NESC Heavy

Wind Pressure.....	4.0 psf
Radial Ice Thickness.....	0.5"
Vertical Overload Capacity Factor.....	1.50
Wind Overload Capacity Factor.....	2.50
Wire Tension Overload Capacity Factor.....	1.65

Load Case 2: NESC Extreme

Wind Speed.....	110 mph <sup>(1)</sup>
Radial Ice Thickness.....	0"

Note 1: NESC C2-2007, Section 25, Rule 250C: Extreme Wind Loading, 1.25 x Gust Response Factor (wind speed: 3-second gust)

▪ ANTENNA FRAME ANALYSIS

ANTENNA mast, appurtenances and connections to the utility tower were analyzed and designed in accordance with the NU Design Criteria Table, TIA/EIA-222-F, and AISC-ASD standards.

Load cases considered:

Load Case 1:

Wind Speed..... 85 mph <sup>(2)</sup>  
 Radial Ice Thickness..... 0"

Load Case 2:

Wind Pressure..... 75% of 85 mph wind pressure  
 Radial Ice Thickness..... 0.5"

| Note 2: Per NU Mast Design Criteria Exception 1.

R e s u l t s

▪ ANTENNA FRAME ASSEMBLY

The antenna frame was determined to be structurally adequate.

Member	Stress Ratio (% of capacity)	Result
HSS12.5"x0.625" Mast	44.2%	<b>PASS</b>
HSS 6x6x3/8 Brace	89.0%	<b>PASS</b>
Mast Connection to CL&P Tower	81.6% <sup>(1)</sup>	<b>PASS</b>

Note 1 – 1/3 increase in allowable stress not used for connection to tower per OTRM 059.

▪ UTILITY TOWER

This analysis finds that the subject utility structure is adequate to support the existing ANTENNA mast and related appurtenances. The tower stresses meet the requirements set forth by the ASCE Manual No. 10-97, "Design of Latticed Steel Transmission Structures", for the applied NESC Heavy and Hi-Wind load cases. The detailed analysis results are provided in Section 9 of this report. The analysis results are summarized as follows:

**With the proposed tower reinforcements detailed in Section 4 of this report** a maximum usage of **96.54%** occurs in the utility tower under the **NESC Extreme** loading condition.

TOWER SECTION:

The utility structure **with the proposed tower reinforcements detailed in Section 4 of this report** was found to be within allowable limits.

Tower Member	Stress Ratio (% of capacity)	Result
Angle Leg13X	96.54%	<b>PASS</b>

▪ FOUNDATION AND ANCHORS

The existing foundation consists of four (4) 16-inx25-in tapering to 28-inx25-in x 6.25-ft long reinforced concrete piers on four (4) 4-ft-6-in square x 2-ft thick reinforced concrete pads. The base of the tower is connected to the foundation by one (1) anchor stub per leg. Foundation information was obtained from a foundation exploration conducted on May 5, 2014.

**BASE REACTIONS:**

From PLS-Tower analysis of CL&P tower based on NESC/NU prescribed loads.

Load Case	Shear	Uplift	Compression
NESC Heavy Wind	25.29 kips	26.19 kips	80.81 kips
NESC Extreme Wind	60.66 kips	1113.12 kips	130.05 kips

Note 1 – 10% increase to be applied to the above tower base reactions for foundation verification per OTRM 051  
 Note 1 – Reactions are combined leg reactions.

**FOUNDATION:**

The foundation **with the proposed reinforcements detailed in Section 4 of this report** was found to be within allowable limits.

Foundation	Design Limit	Allowable Limit	Proposed Loading <sup>(2)</sup>	Result
Reinforced Conc. Pad and Pier	Overturing	1.0 FS <sup>(1)</sup>	1.66 FS <sup>(1)</sup>	<b>PASS</b>

Note 1: FS denotes Factor of Safety

Note 2: 10% increase to PLS base reactions used in foundation analysis per OTRM 051.

**Conclusions and Recommendations**

This analysis shows that the subject utility tower **with the proposed reinforcements outlined below and detailed in Section 4 of this report is adequate** to support the proposed AT&T equipment installaiton.

- Replacement of sixteen (8) L1-3/4x1-3/4x3/16 diagonal members with L2x2x5/16.
- Replacement of two (2) L2x2x3/16 horizontal members with L2x2x1/4.
- Installation of one (1) 27'x27'x3.5' reinforced concrete mat.

The analysis is based, in part on the information provided to this office by Northeast Utilities and AT&T Mobility. If the existing conditions are different than the information in this report, CENTEK engineering, Inc. must be contacted for resolution of any potential issues.

Please feel free to call with any questions or comments.

Respectfully Submitted by:



Timothy J. Lynn, PE  
 Structural Engineer



# ATTACHMENT C



**New Cingular Wireless  
PCS, LLC**  
500 Enterprise Drive  
Rocky Hill, Connecticut  
06067

**Radu Alecsandru**  
RF Engineer  
at&t mobility

<b>Transmission Mode</b>	<b>00000 Centerline Ht (feet)</b>	<b>Frequency (MHz)</b>	<b>00000000 Number of Channels</b>	<b>Power Per Channel (Watts)</b>	<b>Power Density (mW/cm<sup>2</sup>)</b>	<b>Standard Limits (mW/cm<sup>2</sup>)</b>	<b>Percent of Limit</b>
AT&T UMTS	88	800 Band	2	500	0.0464	0.5867	7.91
AT&T UMTS	88	1900 Band	1	500	0.0232	1.0000	2.32
AT&T LTE	88	700 Band	1	500	0.0232	0.4667	4.97
AT&T LTE	88	1900 Band	1	500	0.0232	1.0000	2.32
AT&T LTE	88	2300 Band	1	500	0.0232	1.0000	2.32
<b>Total</b>							<b>19.9%</b>

# ATTACHMENT D



# Visibility Analysis

CTSR2117  
MERIDEN  
CL&P UTILITY STRUCTURE NO. 783  
200 EDGEMARK ACRES  
MERIDEN, CT 06451

*Prepared in February 2014 by:*  
All-Points Technology Corporation, P.C.  
3 Saddlebrook Drive  
Killingworth, CT 06141

New Cingular Wireless PCS, LLC dba AT&T







**DOCUMENTATION**

PHOTO	LOCATION	ORIENTATION	DISTANCE TO SITE
1	EDGEMARK ACRES (24mm Focal Length)	EAST	+/- 0.04 MILE





**SIMULATION**

PHOTO

1

LOCATION

**EDGEMARK ACRES (24mm Focal Length)**

ORIENTATION

**EAST**

DISTANCE TO SITE

**+/- 0.04 MILE**





## DOCUMENTATION

PHOTO

2

LOCATION

RIVERSIDE DRIVE

ORIENTATION

NORTHEAST

DISTANCE TO SITE

+/- 0.08 MILE







**SIMULATION**

PHOTO

2

LOCATION

**RIVERSIDE DRIVE**

ORIENTATION

**NORTHEAST**

DISTANCE TO SITE

**+/- 0.08 MILE**







**DOCUMENTATION**

PHOTO

3

LOCATION

OLD GATE ROAD

ORIENTATION

SOUTHEAST

DISTANCE TO SITE

+/- 0.29 MILE







**SIMULATION**

PHOTO

3

LOCATION

**OLD GATE ROAD**

ORIENTATION

**SOUTHEAST**

DISTANCE TO SITE

**+/- 0.29 MILE**







**SIMULATION**

PHOTO

3

LOCATION

**OLD GATE ROAD**

ORIENTATION

**SOUTHEAST**

DISTANCE TO SITE

**+/- 0.29 MILE**





# ATTACHMENT E

# TOWAIR Determination Results

[? HELP](#)

[New Search](#) [Printable Page](#)

## \*\*\* NOTICE \*\*\*

TOWAIR's findings are not definitive or binding, and we cannot guarantee that the data in TOWAIR are fully current and accurate. In some instances, TOWAIR may yield results that differ from application of the criteria set out in 47 C.F.R. Section 17.7 and 14 C.F.R. Section 77.13. A positive finding by TOWAIR recommending notification should be given considerable weight. On the other hand, a finding by TOWAIR recommending either for or against notification is not conclusive. It is the responsibility of each ASR participant to exercise due diligence to determine if it must coordinate its structure with the FAA. TOWAIR is only one tool designed to assist ASR participants in exercising this due diligence, and further investigation may be necessary to determine if FAA coordination is appropriate.

<b>DETERMINATION Results</b>	
<b>Structure does not require registration. The structure meets the 6.10-meter (20-foot) Rule criteria.</b>	
<b>Your Specifications</b>	
<b>NAD83 Coordinates</b>	
Latitude	41-31-51.7 north
Longitude	072-50-33.7 west
<b>Measurements (Meters)</b>	
Overall Structure Height (AGL)	28
Support Structure Height (AGL)	24.4
Site Elevation (AMSL)	109.7
<b>Structure Type</b>	
UPOLE - Utility Pole/Tower used to provide service (Electric, Telephone, etc)	

### [Tower Construction Notifications](#)

Notify Tribes and Historic Preservation Officers of your plans to build a tower.



**AIRSPACE®****Federal Aviation Regulations Part 77 Sub-Part C  
Obstruction Analysis Report**


---

New Cingular Wireless PCS  
David A Vivian  
500 Enterprise Drive, Suite 3A  
Rocky Hill, CT 06067

E-mail: David.Vivian@SAI-Comm.com  
Phone: 4132185042 Fax:2079678436

---

**Site Identification:** 200\_EDGEMARK\_ACRES  
**Nearest City:** Meriden, CT

## Site Information (Coordinate Datum - NAD83)

<b>Latitude:</b> 41° - 31' - 51.74"	<b>Decimal Degrees:</b> 41.5310388888889°
<b>Longitude:</b> 72° - 50' - 33.65"	<b>Decimal Degrees:</b> 72.8426805555555°
<b>Ground Elevation:</b> 360 feet AMSL	
<b>Structure Height:</b> 93 feet AGL	
<b>Overall Height:</b> 453 feet AMSL	

**FAA Number:** Null  
**Airspace Study #:** 2013-APS-1276-OE

Analyzed on: 12/6/2013. Using Airspace® 13.11.211. Airspace® Data Date: 11/15/2013

This Airspace Analysis was completed under all obstacle evaluation rules specified in Federal Aviation Regulations (FAR) Part 77 sub-Part C.

Approved,

---

Justin J Pittman, Airspace Specialist  
Federal Airways & Airspace®  
1423 S. Patrick Dr  
Satellite Beach, FL 32937  
(321)777-1266

---

Clyde J Pittman, Aerospace Engineer

Date Printed: 12-02-2013

AIRSPACE® and TERPS® are registered ® trademarks of Federal Airways & Airspace®  
Copyright © 1989 - 2013 Federal Airways & Airspace®

## AIRSPACE®

**Site ID Number:** 200\_EDGEMARK\_ACRES

### AERONAUTICAL RECOMMENDATIONS

Notice to the FAA is not required for the proposed antenna which will increase the height of an existing structure by less than 20 feet. This exemption is described in CFR Part 77.9(e)(4).

TERPS® analysis has been completed for the proposed site. The maximum allowable height identified is 487 feet AMSL based upon MMK RWY 18 Departure ICA.

The height of the existing structure will exceed obstruction standards. The FAA would require an extended study to determine the aeronautical impacts. The maximum not to exceed height to avoid an extended study by the FAA is 253 feet AMSL.

Marking and Lighting are not normally required for structures 200 feet or less. However, it may become a requirement based upon the outcome of the aeronautical study conducted by the FAA. It will then become part of the determination and a requirement of the determination.

No adverse impact to low altitude federal airways are identified.

Possible VFR Traffic Pattern operations impact.

No Potential FCC Licensed AM Broadcast Station interference identified.

No impact to an Air Navigation Facility has been identified.

#### Executive Summary

This study evaluated a proposed antenna tower which would be located upon an existing T-L utility structure that would increase the overall height of the existing structure by no more than 15 feet. Title 14 CFR Part 77.9(e)(4) exempts the requirement for notice of the proposed antenna to the FAA,

"Any antenna structure of 20 feet or less in height except one that would increase the height of another antenna structure."

The existing structure does exceed obstruction standards by exceeding the IFR horizontal and VFR conical surfaces. The existing structure does not exceed any instrument or departure procedure. If the existing T-L structure was to be submitted to the FAA, the structure would likely be approved with the condition of marking and/or lighting. Application of 77.9(e)(4) would except the proposed antenna tower from requiring notice to the FAA.

Information has also been provided by the Client that the existing T-L structure is located less than 150 feet from another existing T-L structure that is of greater height and obstruction lighted. AC70/7460-1K Paragraph 55, "Group of Obstructions," provides guidance for structures grouped together.

"When individual objects, except wind turbines, within a group of obstructions are not the same height

Date Printed: 12-02-2013

AIRSPACE® and TERPS® are registered ® trademarks of Federal Airways & Airspace®  
Copyright © 1989 - 2013 Federal Airways & Airspace®



## AIRSPACE®

Site ID Number: 200\_EDGEMARK\_ACRES

### LANDING FACILITY INFORMATION

The nearest public use landing facility to the proposed location is:  
MERIDEN MARKHA (Ident: MMK)

The distance to the nearest runway of this landing facility is 33244 feet or 6.3 statute miles. The true bearing is 156.08° to this landing facility.

Private landing facilities are exempt from review by the FAA under FAR Part 77. However, locating near a private landing facility may affect aircraft operations during take-off and landing.

The nearest private landing facility is: ME87: GOOD  
The existing structure is located 11119 feet or 2.1 statute miles.  
The true bearing to this landing facility is 116 degrees.

The existing structure is within 3 nautical miles (3.45 statute miles) of a private landing facility. This landing facility and supporters are likely to resist this proposal during the local zoning board hearing.

### FAA NOTICE REQUIREMENTS

Notice to the FAA would be required for the following reasons listed below unless proposed tower meets one or more exemption criteria described within CFR

The existing structure exceeds a slope beginning at the runway and extending towards the existing structure. The airport runway elevation, the structure's total elevation above mean sea level (AMSL), the distance between the runway and the existing structure and the airport slope (100:1 or 50:1) are the factors considered during the calculations. This requirement is specified in FAR Part 77.9(b). The maximum height permitted by this FAR is 1832 feet AMSL.

**The proposed antenna tower meets the exemption criteria described in CFR Part 77.9(e)(4) and does not require notice to the FAA.**

## AIRSPACE®

Site ID Number: 200\_EDGEMARK\_ACRES

### AERONAUTICAL IMPACT

#### FAR Part 77 Subpart-C Obstruction Standards

The height of the existing structure will exceed obstruction standards as defined by FAR Part 77.17(a)(1), 77.17(a)(2) or 77.19.

#### Terminal Instrument Procedure Standards - FAR Part 77.17(a)(3)

No adverse impact with a US Terminal Approach or Departure Procedure has been identified.

#### Minimum Obstacle Clearance Altitude (MOCA) - FAR Part 77.17(a)(4)

The proposed structure is not located within a low altitude airway area and will not impact aircraft using any airway.

#### VFR Traffic Pattern Airspace

The proposed structure is located within a VFR Traffic Pattern Airspace. The maximum allowable height is 361 ft AMSL based upon the VFR Conical Surface.

#### FCC Licensed AM Broadcast Station Proof-of-Performance

The proposed structure is not located within the specified range of an FCC Licensed AM radio and will not require Proof-of-Performance analysis.

Date Printed: 12-02-2013

AIRSPACE® and TERPS® are registered ® trademarks of Federal Airways & Airspace®  
Copyright © 1989 - 2013 Federal Airways & Airspace®



\*\*\*\*\*  
\* Federal Airways & Airspace \*  
\* Summary Report: Alteration Of Existing Structure \*  
\* Non-Antenna Structure \*  
\*\*\*\*\*

Airspace User: Justin Pittman

File: 200\_EDGE MARK\_ACRES

Location: Meriden, CT  
Distance: 2.5 Statute Miles  
Direction: 81° (true bearing)

Latitude: 41°-31'-51.74" Longitude: 72°-50'-33.65"

SITE ELEVATION AMSL.....360 ft.  
STRUCTURE HEIGHT..... 93 ft.  
OVERALL HEIGHT AMSL.....453 ft.

NOTICE CRITERIA

- FAR 77.9(a): NNR (DNE 200 ft AGL)
- FAR 77.9(b): NR (Exceeds Notice Slope, Maximum: 250 ft.)
- FAR 77.9(c): NNR (Not a Traverse Way)
- FAR 77.9: NNR FAR 77.9 IFR Straight-In Notice Criteria for MMK
- FAR 77.9: NNR FAR 77.9 IFR Straight-In Notice Criteria for 4B8
- FAR 77.9(d): NNR (Off Airport Construction)

NR = Notice Required  
NNR = Notice Not Required  
PNR = Possible Notice Required (depends upon actual IFR procedure)  
For new construction review Air Navigation Facilities at bottom of this report.

If the proposed construction is an alteration to an existing structure, notice requirements may be superceded by the item exemptions listed below.

The location and analysis were based upon an existing structure. However, no existing aeronautical study number was identified. **If the 'existing' structure penetrates an obstruction surface defined by CFR 77.17, 77.19, 77.21 or 77.23 (see below) it is recommended the FAA be notified of the 'existing' structure to determine obstruction marking or lighting requirements.** It is not uncommon for the FAA to issue a Determination of No Hazard (DNH) for an existing structure and modify the airspace to accommodate the structure, should that be required. If the FAA issues a DNH enter the aeronautical study number (ASN) in the space provided on the Airspace Analysis Window Form and re-run Airspace.

The FAA Co-Location policy does not apply unless the existing structure has been previously studied by the FAA and has a valid ASN with a DNH ruling. To take advantage of co-locating an antenna systems on an 'existing' structure it is recommended that 'only' notice on the existing structure be filed with the FAA. Once the DNH is received rerun Airspace and enter the ASN in the space provided.

Title 14 CFR Part 77.9(e), Notice Criteria Exception:  
The location and analysis were based upon an existing structure with the alteration limited to the addition of an antenna with a height no greater than 20 feet. **Title 14 CFR Part 77.9(e)(4) exempts the requirement for notice to the FAA; "Any antenna structure of 20 feet or less in height except one that would increase the height of another antenna structure."** If the addition

of an antenna of 20 feet or less to an existing structure increase the height of the structure to exceed 200 feet AGL or penetrate an obstruction surface defined by Title 14 CFR 77.17, 77.19, 77.21 or 77.23 notice is recommend. This will allow the FAA to determine the level of obstruction lighting required and any aeronautical impacts, if any, to aircraft operations. Notice of an existing structure almost always receives a No Hazard Determination. Please see Summary Report below plus the Airport and Part 77 Reports for application of the above listed CFRs.

OBSTRUCTION STANDARDS

- FAR 77.17(a) (1): DNE 499 ft AGL
- FAR 77.17(a) (2): DNE - Airport Surface
- FAR 77.19(a): Exceeds - Horizontal Surface Maximum 253 ft AMSL
- FAR 77.19(b): DNE - Conical Surface
- FAR 77.19(c): DNE - Primary Surface
- FAR 77.19(d): DNE - Approach Surface
- FAR 77.19(e): DNE - Transitional Surface

VFR TRAFFIC PATTERN AIRSPACE FOR: MMK: MERIDEN MARKHAM MUNI

- Type: A RD: 7360.773 RE: 103
- FAR 77.17(a) (1): DNE
- FAR 77.17(a) (2): Does Not Apply.
- VFR Horizontal Surface: DNE
- VFR Conical Surface: Exceeds - Maximum allowable height is 361 ft AMSL.
- VFR Approach Slope: DNE
- VFR Transitional Slope: DNE

The structure is within VFR - Traffic Pattern Airspace Climb/Descent Area. Structures exceeding the greater of 350' AAE, 77.17(a) (2), or VFR horizontal and conical surfaces will receive a hazard determination from the FAA. Maximum AMSL of Climb/Descent Area is 453 feet.

VFR TRAFFIC PATTERN AIRSPACE FOR: 4B8: ROBERTSON FIELD

- Type: A RD: 56198.98 RE: 200
- FAR 77.17(a) (1): DNE
- FAR 77.17(a) (2): DNE - Greater Than 5.99 NM.
- VFR Horizontal Surface: DNE
- VFR Conical Surface: DNE
- VFR Approach Slope: DNE
- VFR Transitional Slope: DNE

TERPS DEPARTURE PROCEDURE (FAA Order 8260.3, Volume 4)

- FAR 77.17(a) (3) Departure Surface Criteria (40:1)
- The Maximum Height Permitted is 287 ft AMSL

MINIMUM OBSTACLE CLEARANCE ALTITUDE (MOCA)

- FAR 77.17(a) (4) MOCA Altitude Enroute Criteria
- The Maximum Height Permitted is 1500 ft AMSL

PRIVATE LANDING FACILITIES

FACIL	BEARING	RANGE	DELTA ARP	FAA
IDENT TYP NAME	To FACIL	IN NM	ELEVATION	IFR
CT95 HEL MERIDEN-WALLINGFORD HOSPITAL	84.7	1.49	+308	
No Impact to Private Landing Facility Structure is beyond notice limit by 4053 feet.				
CT21 HEL C N FLAGG	113.25	3.54	+120	
No Impact to Private Landing Facility Structure is beyond notice limit by 16509 feet.				



OCT1 HEL BRISTOL-MYERS SQUIBB COMPANY 125.47 4.79 +103  
 No Impact to Private Landing Facility  
 Structure is beyond notice limit by 24105 feet.

AIR NAVIGATION ELECTRONIC FACILITIES

FAC IDNT	TYPE	ST AT	FREQ	VECTOR	DIST (ft)	DELTA ELEVA	ST LOCATION	GRND ANGLE	APCH BEAR
MMK	CO	Y	134.92	152.2	7362	+297	CT MERIDEN	2.31	
Notice Required. Unless exempt under FAA/FCC co-location policy or Title 14 CFR Part 77.9(e).									
MAD	VOR/DME	R	110.4	152.5	89262	+233	CT MADISON	.15	
HFD	VOR/DME	R	114.9	63.5	90183	-396	CT HARTFORD	-.25	
HVN	VOR/DME	R	109.8	186.78	98609	+447	CT NEW HAVEN	.26	
BDL	RADAR	ON		16.36	154800	+217	CT BRADLEY INTL	.08	
BDR	VOR/DME	R	108.8	209.74	155560	+444	CT BRIDGEPORT	.16	
QVH	RADAR ARSR	Y	1326.9	169.85	241503	+102	NY RIVERHEAD	.02	
OKX	RADAR WXL	Y		181.37	242553	+232	NY BRENTWOOD	.05	

FCC AM PROOF-OF-PERFORMANCE

NOT REQUIRED: Structure is not near a FCC licensed AM radio station Proof-of-Performance is not required. Please review AM Station Report for details.

Nearest AM Station: WMMW @ 4243 meters.

Airspace® Summary Version 13.11.336

AIRSPACE® and TERPS® are registered ® trademarks of Federal Airways & Airspace®  
 Copyright © 1989 - 2013

12-02-2013  
 10:11:24

\*\*\*\*\*  
\* F.A.R. 77 OBSTRUCTION ANALYSIS \*  
\*\*\*\*\*

Airspace User: Justin Pittman

FILE: 200\_EDGEMARK\_ACRES

LATITUDE: 41°-31'-51.74" LONGITUDE: 72°-50'-33.65"

SITE ELEVATION AMSL..... 360 ft.  
STRUCTURE HEIGHT..... 93 ft.  
OVERALL HEIGHT AMSL..... 453 ft.

77.17(a) (1) A height more than 499 ft. Above Ground Level (AGL) .

\*\*\*\*\* DOES NOT EXCEED \*\*\*\*\*

THE MAXIMUM ALLOWABLE HEIGHT IS:..... 859 ft. AMSL  
THE GROUND ELEVATION AT THE SITE IS:... 360 ft. AMSL  
THE OVERALL CASE ELEVATION IS:..... 453 ft. AMSL  
THE CASE IS BELOW THE ALLOWABLE BY:.... 406 ft.

\*\*\*\*\*  
BEGIN AIRPORT ANALYSIS FOR MMK  
\*\*\*\*\*

77.17(a) (2) A height AGL or airport elevation, whichever is higher.

\*\*\*\*\* DOES NOT EXCEED \*\*\*\*\*

BECAUSE: Airport does not have a runway longer than 3200 feet.  
THE REFERENCE AIRPORT IDENT IS:..... MMK  
THE AIRPORT ELEVATION IS:..... 103 ft. AMSL  
THE DISTANCE FROM THE CASE TO ARP IS:.. 1.4713 NAUTICAL MILES  
THE BEARING AIRPORT TO CASE IS:..... 336.084 DEGREES  
THE CASE HEIGHT AGL IS:..... 93 ft.  
ALLOWABLE HEIGHT..... 560 ft. AMSL

77.19 (a) A height exceeding a horizontal surface 150 ft. above  
airport elevation within a radius of >> MMK <<.

\*\*\*\*\* EXCEEDS HORIZONTAL SURFACE \*\*\*\*\*

MAXIMUM ALLOWABLE HEIGHT IS:..... 253 ft AMSL.  
THE AIRPORT ELEVATION IS:..... 103 ft. AMSL  
THE CASE EXCEEDS THE ALLOWABLE BY:.... 200 ft.



77.19(b) A height exceeding a conical surface (a slope outward 4000 ft. from the horizontal surface at 20/1 ratio).

\*\*\*\*\* DOES NOT EXCEED \*\*\*\*\*

NOT WITHIN SPECIFIED CONICAL SURFACE AREA

\*\*\*\*\*  
\* BEGIN RUNWAY ANALYSIS \*  
\*\*\*\*\*

EXISTING RUNWAY 18/36

77.19(c) A height exceeding runway primary surface.

\*\*\*\*\* DOES NOT EXCEED \*\*\*\*\*

NOT WITHIN SPECIFIED RUNWAY PRIMARY SURFACE

77.19(d) A height exceeding an approach surface of RUNWAY 18.

THE BEARING TO THE CASE FROM THE THRESHOLD IS..... 334.663 degrees

THE ABEAM BEARING TO THE CENTERLINE IS..... 251.68 degrees

THE CENTERLINE OUTBOUND TRUE BEARING IS..... 341.68 degrees

THE ABEAM DISTANCE TO CENTERLINE FROM CASE IS..... 875.1 ft.

THE RUNWAY THRESHOLD ELEVATION IS..... 103 ft. AMSL

THE DISTANCE FROM THRESHOLD + 200' TO THE CASE IS... 7162.231 ft.

THE DISTANCE FROM THRESHOLD + 200' TO NB IS..... 7108.51 ft.

THE CRITICAL WIDTH OF HALF THE APPROACH IS..... 783.135 ft.

THE TRANSITIONAL SURFACE HEIGHT IS 471' AMSL. HOWEVER, THE CASE IS IN AN AREA WHERE THE TRANSITIONAL SURFACE IS LIMITED BY THE HORIZONTAL SURFACE (253' AMSL). See FAR 77.19(a) for this runway.

THE SLOPE OF RUNWAY 18 IS: 20 TO 1.

The FAA has defined this runway as a utility runway. It has a visual approach. The obstacle surface extends 5000 feet (20:1 Slope) symmetrically centered along the runway centerline extended. This airport may have a circling approach. Please review the US Terminal Procedures volume associated with this airport. If a procedure for this airport and/or this runway exist, use Terps® Professional software to determine the height limits (if any) the procedure will have on the proposed structure. A circling approach to the airport or any runway can extend out up to 4.5 NM from every runway end.

\*\*\*\*\*  
BEGIN AIRPORT ANALYSIS FOR 4B8  
\*\*\*\*\*

77.17(a) (2) A height AGL or airport elevation, whichever is higher.

\*\*\*\*\* DOES NOT EXCEED \*\*\*\*\*  
BECAUSE: Location studied is further than 5.99 NM from ARP.  
THE REFERENCE AIRPORT IDENT IS:..... 4B8  
THE AIRPORT ELEVATION IS:..... 202 ft. AMSL  
THE DISTANCE FROM THE CASE TO ARP IS:... 9.5512 NAUTICAL MILES  
THE BEARING AIRPORT TO CASE IS:..... 174.045 DEGREES  
THE CASE HEIGHT AGL IS:..... 93 ft.  
ALLOWABLE HEIGHT..... 1215 ft. AMSL

77.19 (a) A height exceeding a horizontal surface 150 ft. above airport elevation within a radius of >> 4B8 <<.

\*\*\*\*\* DOES NOT EXCEED \*\*\*\*\*  
NOT WITHIN SPECIFIED HORIZONTAL SURFACE AREA

77.19(b) A height exceeding a conical surface (a slope outward 4000 ft. from the horizontal surface at 20/1 ratio).

\*\*\*\*\* DOES NOT EXCEED \*\*\*\*\*  
NOT WITHIN SPECIFIED CONICAL SURFACE AREA

\*\*\*\*\*  
\* BEGIN RUNWAY ANALYSIS \*  
\*\*\*\*\*

EXISTING RUNWAY 02/20

77.19(c) A height exceeding runway primary surface.

\*\*\*\*\* DOES NOT EXCEED \*\*\*\*\*  
NOT WITHIN SPECIFIED RUNWAY PRIMARY SURFACE

77.19(d) A height exceeding an approach surface of RUNWAY 02.

THE BEARING TO THE CASE FROM THE THRESHOLD IS..... 173.64 degrees  
THE ABEAM BEARING TO THE CENTERLINE IS..... 95.35 degrees  
THE CENTERLINE OUTBOUND TRUE BEARING IS..... 185.35 degrees  
THE ABEAM DISTANCE TO CENTERLINE FROM CASE IS..... 11382.2 ft.  
\*\*\*\*\* DOES NOT EXCEED \*\*\*\*\*

CASE MEETS ANGULAR CRITERIA BUT IS LOCATED  
GREATER THAN 50,000 ft. FROM THE START OF



ANY APPROACH TYPE, OUT BY 4839.5 feet

\*\*\*\*\*  
\* BEGIN RUNWAY ANALYSIS \*  
\*\*\*\*\*

PROPOSED RUNWAY 02/20

77.19(c) A height exceeding runway primary surface.

\*\*\*\*\* DOES NOT EXCEED \*\*\*\*\*

NOT WITHIN SPECIFIED RUNWAY PRIMARY SURFACE

77.19(d) A height exceeding an approach surface of RUNWAY 02.

THE BEARING TO THE CASE FROM THE THRESHOLD IS..... 173.64 degrees

THE ABEAM BEARING TO THE CENTERLINE IS..... 95.35 degrees

THE CENTERLINE OUTBOUND TRUE BEARING IS..... 185.35 degrees

THE ABEAM DISTANCE TO CENTERLINE FROM CASE IS..... 11381.7 ft.


\*\*\*\*\* DOES NOT EXCEED \*\*\*\*\*

CASE MEETS ANGULAR CRITERIA BUT IS LOCATED  
GREATER THAN 50,000 ft. FROM THE START OF  
ANY APPROACH TYPE, OUT BY 4837.4 feet


Airspace® Version 13.11.336


AIRSPACE® and TERPS® are registered ® trademarks of Federal Airways & Airspace®  
Copyright © 1989 - 2013

12-02-2013  
10:10:44



























Departure Runway 36

\*\*\* 200\_EDGEMARK\_ACR \*\*\*

MERIDEN MARKHAM MUNI - Runway: 36

Date: 12-02-2013 Time: 09:42:20

STUDY OBJECT DATA

Study Latitude: 41° 31' 51.74" N  
Study Longitude: 72° 50' 33.65" W  
Ground Elevation: 360' AMSL ft.  
AGL Height: 93' AGL ft.  
Overall Elevation: 453' AMSL ft.

INSTRUMENT DEPARTURE ANALYSIS

Initial Climb Area (ICA): Max Hgt ICA: 487 ft

Diverse Departure A Not in Diverse A - DNE Diverse A


Diverse Departure B Not in Diverse B - DNE Diverse B

The above analysis is in accordance with FAA Order 8260.3B Change 19. This analysis used a 420 ft/NM climb gradient (CG) and an Obstacle Clearance Surface (OCS) that provides 100 feet of obstacle clearance at 1 NM from the Departure End of Runway (DER). Some runways have published climb gradients greater than 200 ft/NM. A specified climb gradient greater than standard (200 ft/NM) is sometimes necessary to allow acceptable obstacle clearance. Should your location exceed the value indicated above you may need to determine if there is a published CG and conduct additional calculations to determine if the CG will provide proper clearance for your proposed structure.

Terps® Version 13.11.433

Airspace® and Terps® are registered ® trademarks of Federal Airways and Airspace®. Copyright © 1989 - 2013

The mathematical algorithms used by this program are derived directly from Federal Aviation Administration (FAA) Orders on Instrument Flight Procedures.





Circling Approach Area Analysis

\*\*\* 200\_EDGEMARK\_ACR \*\*\*

MERIDEN MARKHAM MUNI

Date: 12-02-2013 Time: 09:46:38

STUDY OBJECT DATA

Study Latitude: 41° 31' 51.74" N  
Study Longitude: 72° 50' 33.65" W  
Ground Elevation: 360' AMSL ft.  
AGL Height: 93' AGL ft.  
Overall Elevation: 453' AMSL ft.

INSTRUMENT APPROACH PROCEDURE (IAP) ANALYSIS GPS

Distance: 7361 ft.  
Aircraft Category: B  
Circling MDA: 780  
Vkias: 120 knots  
Vktas: 125.1191 knots  
Bank Angle: 25°  
Straight Segment: 0.4 NM  
Expanded CAA: True  
Turn Radius: 1.7 NM  
  
Maximum AMSL: 480

Terps® Version 13.11.433

Airspace® and Terps® are registered ® trademarks of Federal Airways  
and Airspace®. Copyright © 1989 - 2013

The mathematical algorithms used by this program are derived directly  
from Federal Aviation Administration (FAA) Orders on Instrument Flight  
Procedures.

## **SITE GROUND ELEVATION**

### **USGS GROUND ELEVATION POINT DATA North American Datum 1983 - NAD83 North American Vertical Datum 1988 - NAVD88**

**2013-APS-1276-OE**

**Latitude:** 41° - 31' - 51.74" N    **Decimal Degrees:** 41.5310388888889°  
**Longitude:** 72° - 50' - 33.65" W    **Decimal Degrees:** -72.8426805555555°

**Ground Elevation: 351.92 feet AMSL**

This certifies the above elevation data value for the specified latitude/longitude point was obtained from the United States Geological Survey Seamless Elevation data located at the EROS data center. The elevation value meets vertical accuracy criteria as specified by FAA Order 8260.19C, Appendix 2, Obstacle Accuracy Standards, Codes And Sources, paragraph 101 for Code 'C'. The elevation value for the specified latitude/longitude is accurate to within ±20 feet vertically.


Date Printed: 12-02-2013

AIRSPACE® and TERPS® are registered ® trademarks of Federal Airways & Airspace®  
Copyright © 1989 - 2006 Federal Airways & Airspace®



# ATTACHMENT F

CT2117  
 200 Edgemark Acres  
 Meriden, CT 06451  
 41-31-51.7 N  
 072-50-33.7 W  
 Antenna Ht: 88' AGL  
 GE: 360' AMSL



**Symbol Key**

- ★ 1900 MHz LTE Site
- ★ Proposed Site Location
- ★ Planned Site Location

**Coverage Key**

- $\geq -86$  dBm
- $< -86$  dBm &  $\geq -96$  dBm
- $< -96$  dBm

1900 MHz LTE  
 Coverage of CT2117

Meriden, CT


200 Edgemark Acres  
 Meriden, CT 06451



PREPARED ON  
 DATE: 11/19/2014

REV  
 0





CT2117  
 200 Edgemark Acres  
 Meriden, CT 06451  
 41-31-51.7 N  
 072-50-33.7 W  
 Antenna Ht: 88' AGL  
 GE: 360' AMSL

**Symbol Key**

- ★ 700 MHz LTE Site
- ★ Proposed Site Location
- ★ Planned Site Location

**Coverage Key**

- $\geq -83$  dBm
- $< -83$  dBm &  $\geq -93$  dBm
- $< -93$  dBm

700 MHz LTE  
 Coverage of CT2117

**Meriden, CT**

200 Edgemark Acres  
 Meriden, CT 06451



PREPARED ON \_\_\_\_\_  
 DATE: 11/19/2014  
 REV 0

# ATTACHMENT G

## NOTICE

Notice is hereby given, pursuant to Section 16-50j-40(a) of the Regulations of Connecticut State Agencies of a Petition to be filed with the Connecticut Siting Council (“Siting Council”) on or after November 25, 2014 by New Cingular Wireless PCS, LLC (“AT&T” or the “Petitioner”). AT&T will seek a declaratory ruling that no certificate of environmental compatibility and public need is required to collocate a wireless telecommunications facility on an existing Connecticut Light & Power (“CL&P”) transmission structure located at 200 Edgemark Acres, Meriden, Connecticut (the “Site”).

The existing facility, CL&P structure number 783, is located in an existing CL&P right-of-way occupied by the existing transmission lines. It is situated on property located at 200 Edgemark Acres (the “subject parcel”), owned by Martorelli Realty Company.

AT&T’s proposed facility consists of attaching an approximately 12’ tall antenna support structure at the top of the existing 80’ tall transmission pole to support up to 12 panel antennas and other equipment at a centerline height of approximately 88’ above grade level. A 12’ x 24’ associated unmanned equipment shelter will be located at grade at the base of the existing transmission pole. The equipment shelter will be completely secured by a 6’ tall chain link fence. Provisions for emergency backup power include a 50kW diesel generator to be located inside the proposed equipment shelter. Access to AT&T’s facility is proposed from Edgemark Acres via an easement over the existing gravel driveway that currently serves the subject property. A small portion of the beginning of the gravel access driveway is on the subject property, but is not within the CL&P easement. Utility connections to the facility are proposed to extend to Edgemark Acres via underground utility conduits.

The facility is being proposed to allow AT&T to provide service in this area of the State. The Petition will provide details of the facility and explain why Petitioner submits that the proposed co-located wireless facility presents no significant adverse environmental effects. The location, height and other features of the facility are subject to review and potential change under provisions of the Connecticut General Statutes Sections 16-50g et. seq.

Copies of the Petition will be available for review during normal business hours on or after November 26, 2014 at the Connecticut Siting Council:

Connecticut Siting Council  
10 Franklin Square  
New Britain, Connecticut 06051

or the offices of the undersigned. All inquiries should be addressed to the Connecticut Siting Council or to the undersigned.


Daniel M. Laub, Esq.  
Christopher B. Fisher, Esq.  
Cuddy & Feder LLP  
445 Hamilton Ave, 14th Floor  
White Plains, New York 10601  
(914) 761-1300  
Attorneys for the Petitioner



**CERTIFICATION OF SERVICE**

I hereby certify that on the 24<sup>th</sup> of November 2014, a copy of the foregoing notice was mailed by certified mail, return receipt requested to each of the abutting properties owners on the accompanying list.

11/24/14  
Date



Daniel M. Laub  
Cuddy & Feder LLP  
445 Hamilton Avenue, 14<sup>th</sup> Floor  
White Plains, New York 10601

Attorneys for:  
New Cingular Wireless PCS, LLC ("AT&T")


ADJACENT PROPERTY OWNERS  
200 Edgemark Acres, Meriden, CT

Gennaro Martorelli Trustee 234 Middle Street Middletown, CT 06457	Justin W. & Kelly L. Trella 268 Edgemark Acres Meriden, CT 06451
Deutsche Bank National Trust Company Tr c/o New Century Equite Loan Tr 1761 E St Andrew Pl Santa Ana, CA 92705	Gloria Martorelli 175 Edgemark Acres Meriden, CT 06451

**CERTIFICATION OF SERVICE**

I hereby certify that on the 24th day of November 2014, notice of the intent to file a petition for declaratory ruling regarding the herein proposed telecommunications Facility in Meriden were sent by certified mail, return receipt requested, to the following:

Dated: 11/24/14



Cuddy & Feder LLP  
445 Hamilton Avenue, 14<sup>th</sup> Floor  
White Plains, N.Y. 10601  
Attorneys for:  
New Cingular Wireless PCS LLC ("AT&T")

**State and Regional**

The Honorable George Jepsen Attorney General Office of the Attorney General 55 Elm Street Hartford, CT 06106	Department of Economic and Community Development Catherine H. Smith 505 Hudson Street Hartford, CT 06106-7106
Department of Public Health Dr. Jewel Mullen, Commissioner 410 Capitol Avenue PO Box 340308 Hartford, CT 06134	Department of Transportation James P. Redeker, Commissioner 2800 Berlin Turnpike Newington, CT 06111
Council on Environmental Quality Susan D. Merrow, Chair 79 Elm Street Hartford, CT 06106	Department of Agriculture Steven K. Reviczky, Commissioner 165 Capitol Avenue Hartford, CT 06106
Office of Policy and Management Benjamin Barnes, Secretary 450 Capitol Avenue Hartford, CT 06106-1308	State Senator-District S13 Dante Bartolomeo Legislative Office Building Room 3200 Hartford, CT 06106



<p>Department of Energy &amp; Environmental Protection-Public Utilities Regulatory Authority  Chairman Arthur House  Ten Franklin Square  New Britain, CT 06051</p>	<p>South Central Regional Council of Governments  Carl Amento, Executive Director  127 Washington Ave. -4<sup>th</sup> Floor West  North Haven, CT 06473</p>
<p>Connecticut Department of Emergency Services and Public Protection  Division of Emergency Management and Homeland Security  Dora B. Schriro, Commissioner  1111 Country Club Road  Middletown, CT 06457</p>	<p>Department of Economic and Community Development  Offices of Culture and Tourism  Daniel T. Forrest, State Historic Preservation Officer  One Constitution Plaza, 2<sup>nd</sup> Floor  Hartford, CT 06103</p>
<p>Department of Energy &amp; Environmental Protection  Rob Klee, Commissioner  79 Elm Street  Hartford, CT 06106</p>	<p>State House Representative  83<sup>rd</sup> District  Catherine F. Abercrombie  Legislative Office Building, Room 2704  Hartford, CT 06106</p>

**Federal**

<p>Federal Communications Commission  445 12<sup>th</sup> Street SW  Washington, D.C. 20554</p>	<p>Federal Aviation Administration  800 Independence Avenue, SW  Washington, DC 20591</p>
<p>U.S. Congresswoman Elizabeth Esty  5<sup>th</sup> District  114 West Main Street  Post Office Plaza, LLC  New Britain, CT 06051</p>	<p>U.S. Senator Richard Blumenthal  90 State House Square, 10th Floor  Hartford, CT 06103</p>
<p>U.S. Senator Christopher Murphy  One Constitution Plaza, 7<sup>th</sup> Floor  Hartford, CT 06103</p>	

### City of Meriden

<p>Mayor Manuel A. Santos  City of Meriden  142 East Main Street  Meriden, CT 06450</p>	<p>City of Meriden  Planning Commission  Enrico Buccilli, Chairman  142 East Main Street  Meriden, CT 06450</p>
<p>City of Meriden  Irene Masse, City Clerk  142 East Main Street  Meriden, CT 06450</p>	<p>City of Meriden  Inland Wetlands Commission  Robert C. Burns, Chairman  142 East Main Street  Meriden, CT 06450</p>
<p>City of Meriden  Dominick Caruso, City Planner  142 East Main Street  Meriden, CT 06450</p>	<p>City of Meriden  Lawrence Kendzior, City Manager  142 East Main Street  Meriden, CT 06450</p>
<p>City of Meriden  Conservation Commission  Maryellen Mordarski, Chairwoman  142 East Main Street  Meriden, CT 06450</p>	

# ATTACHMENT H





Northeast  
Utilities System

56 Prospect Street, Hartford, CT 06103

Northeast Utilities Service Company  
P.O. Box 270  
Hartford, CT 06141-0270  
(203) 665-5000

November 21, 2014


Mr. Tim Burks  
AT&T Wireless.  
500 Enterprise Drive  
Rocky Hill, CT 06067

RE: AT&T Antenna Site, CT-2117 200 Edgemark Acres, Meriden CT, CL&P structure 783.

Dear Mr. Burks:

Based on our reviews of the site drawings, the structural and foundation analysis provided by Centek Engineering and, along with a third party review performed by Paul J. Ford we have reviewed for acceptance this modification.

Since there are no outstanding structural issues to resolve at this time please contact Mr. Green (860-665-6933) to resolve any lease issues; once the lease amendment is secured you may contact Mr. John Landry directly (860-665-5425) to begin these arrangements.

Sincerely,  
  
Robert Gray  
Transmission Line Engineering

ref: 13305.000 CT2117 Meriden - CD Rev1 14.11.20.pdf  
13305.000 - CT2117 Structural Analysis Rev4 14-10-06.pdf



**Northeast  
Utilities**

107 Selden Street, Berlin, CT 06037

Northeast Utilities  
P.O. Box 270  
Hartford, CT 06141-0270  
(860) 665-5000  
www.nu.com

November 24, 2014

Mr. Tim Burks  
Site Acquisition Manager- New England  
SAI Communications, Consultant for  
AT&T Mobility (a/k/a New Cingular Wireless  
500 Enterprise Drive  
Rocky Hill, CT 06067

Re: Site Permitting Authorization  
200 Edgemark Acres, Meriden, CT  
Telecommunications Site

Dear Mr. Burks:

Authorization is hereby given to New Cingular Wireless PCS, LLC (New Cingular), its employees and its duly authorized agents and independent contractors (hereinafter collectively referred to as "New Cingular"), to apply for any and all local municipal, state and federal licenses, permits and approvals, including but not limited to Connecticut Siting Council, building permits, zoning variances, zoning special exceptions, site plan and subdivision approvals, driveway, wetlands and terrain alteration permits, which are or may be necessary or required for New Cingular to construct, operate and maintain a wireless communications system (PCS System), and/or antenna site on the following property over which The Connecticut Light & Power Company (CL&P) has easement rights:

CL&P Structure #783, FAA #10126684  
200 Edgemark Acres  
Meriden, Connecticut

The foregoing authorization is given subject to the following conditions:

1. This authorization shall be nonexclusive. Nothing herein shall prevent or restrict CL&P from authorizing any other person or entity to apply for any similar licenses, permits or approvals to construct, operate and maintain any other communication system or facility of any type on the property at any time.
2. This authorization shall not obligate CL&P to pay for or reimburse any costs or expenses or to provide any assistance of any kind in connection with any applications, or bind or obligate CL&P to agree or be responsible for any on-site or off-site improvements, development restrictions, impact fees or assessments, capital improvement charges, bonds or other security, or any other fee, assessment, charge or expense imposed or required as a condition of any

license, permit or approval. New Cingular shall be solely and fully responsible for all fees, charges costs and expenses of any kind in connection with any applications. CL&P agrees to reasonably cooperate with New Cingular in signing such applications or other similar documents as may be required in order for New Cingular to apply for any license, permit or approval.

3. This authorization shall not be deemed or construed to grant or transfer to New Cingular any interest in the property, whatsoever, and shall not in any respect obligate or require CL&P to sell, lease or license the Property to New Cingular or otherwise allow New Cingular to use or occupy the property for any purpose, regardless of whether any licenses, permits and approvals applied for by New Cingular for the property are granted. New Cingular understands and acknowledges that any and all applications filed by New Cingular for the property at New Cingular's sole risk and without any enforceable expectation that the property will be made available for New Cingular's use.
4. New Cingular shall be required to supply to CL&P, free of charge and contemporaneous with New Cingular's filing of same, a complete copy of any and all applications, plans, reports and other public filings made by New Cingular with any local, municipal, state or federal governmental or regulatory officer, agency board, bureau, commission or other person or body for any licenses, permits or approvals for the property, and to keep CL&P fully informed on a regular basis of the status of New Cingular's applications.
5. This authorization shall automatically expire six (6) months after the date of this letter, unless extended in writing by mutual agreement of CL&P and New Cingular.

Very truly yours,



Michael J. Green, Senior Real Estate Analyst  
T & D ROW & Survey Engineering

**AGREED TO ON BEHALF OF New Cingular Wireless PCS, LLC**

By:  Its Agent  
Duly Authorized

Date: 11/24/14



Market: Connecticut  
Cell Site Number: SR 2117  
Cell Site Name: Meriden – Edgemark Acres (NU)  
Fixed Asset Number: 10126684

## ADDITIONAL GROUND SPACE LEASE AGREEMENT

THIS ADDITIONAL GROUND SPACE LEASE AGREEMENT ("**Agreement**"), dated as of the latter of the signature dates below (the "**Effective Date**"), is entered into by Martorelli Realty Company, a Connecticut partnership, having a mailing address of 234 Middle Street, Middletown, CT 06457 ("**Landlord**") and New Cingular Wireless PCS, LLC, a Delaware limited liability company, having a mailing address of 575 Morosgo Drive, 13-F West Tower, Atlanta, GA 30324 ("**Tenant**").

### BACKGROUND

Landlord owns or controls that certain plot, parcel or tract of land, as described on **Exhibit 1**, together with all rights and privileges arising in connection therewith, located at 200 Edgemark Acres, Meriden, in the County of New Haven, State of Connecticut (collectively, the "**Property**"). Tenant desires to use a portion of the Property in connection with its federally licensed communications business to provide space for certain of Tenant's equipment necessary or advisable for the operation of its antennas and associated communications fixtures and equipment installed or to be installed on an antenna structure owned by a third party ("**Antenna Landlord**"), which antenna structure is located on the Property or adjacent property. Landlord desires to grant to Tenant the right to use a portion of the Property in accordance with this Agreement.


The parties agree as follows:

- 1. LEASE OF PREMISES.** Landlord hereby leases to Tenant a certain portion of the Property containing approximately 702 square feet including the air space above such ground space, as described on attached **Exhibit 1** (the "**Premises**") for the placement of Tenant's Communication Facility and grants such easements as are necessary for installation of all equipment required or advisable to connect Tenant's antennas located on the antenna structure owned by Antenna Landlord with the Communication Facility (as such term is defined in Paragraph 2 below).
- 2. PERMITTED USE.** Tenant may use the Premises for the transmission and reception of communications signals and the installation, construction, maintenance, operation, repair, replacement and upgrade of its communications fixtures and related equipment, cables, accessories and improvements, which may include a suitable support structure, equipment shelters or cabinets and fencing and any other items necessary to the successful and secure use of the Premises (collectively, the "**Communication Facility**"), as well as the right to test, survey and review title on the Property; Tenant further has the right but not the obligation to add, modify and/or replace equipment in order to be in compliance with any current or future federal, state or local mandated application, including, but not limited to, emergency 911 communication services, at no additional cost to Tenant or Landlord (collectively, the "**Permitted Use**"). Landlord and Tenant agree that any portion of the Communication Facility that may be conceptually described on **Exhibit 1** will not be deemed to limit Tenant's Permitted Use. If **Exhibit 1** includes drawings of the initial installation of the Communication Facility, Landlord's execution of this Agreement will signify Landlord's approval of **Exhibit 1**. For a period of ninety (90) days following the start of construction, Landlord grants Tenant, its subtenants, licensees and sublicensees, the right to use such portions of Landlord's contiguous, adjoining or surrounding property (the "**Surrounding Property**") as may reasonably be required during construction and installation of the Communication Facility. Tenant has the right to install and operate transmission cables from the equipment shelter or cabinet to the antenna structure which is located on the Property or adjacent property, electric lines from the main feed to the equipment shelter or cabinet and communication lines from the Property's main entry point to the equipment shelter or cabinet, and to make other improvements, alterations, upgrades or additions appropriate for Tenant's Permitted Use, including the right to construct a fence around the Premises and undertake any other appropriate means to secure the Premises at

IN WITNESS WHEREOF, the parties have caused this Agreement to be effective as of the last date written below.

**"LANDLORD"**


Martorelli Realty Company

By:   
Print Name: Gennaro Martorelli  
Its: A partner  
Date: 1/8/14

**"TENANT"**

New Cingular Wireless PCS, LLC,  
a Delaware limited liability company

By: AT&T Mobility Corporation  
Its: Manager

By:   
Print Name: Kevin L. Mason  
Its: Area Manager – Construction & Engineering  
Site Acquisition for the New England Market  
Date: 1-14-2014


[ACKNOWLEDGMENTS APPEAR ON THE NEXT PAGE]


**TENANT ACKNOWLEDGMENT**

State of Massachusetts  
County of Middlesex

On this the 14 day of January, 2014 before me Kevin L. Mason the undersigned officer, personally appeared Kevin L. Mason who acknowledged himself to be the Area Manager-Construction & Engineering, Site Acquisition for the New England Market of AT&T Mobility Corporation, manager of New Cingular Wireless PCS, LLC, a (member managed or manager managed) limited liability company, and that he, as such Area Manager, being authorized so to do, executed the foregoing instrument for the purposes therein contained, by signing the name of the limited liability company by himself as Area Manager-Construction & Engineering, Site Acquisition for the New England Market.

In witness whereof I hereunto set my hand.





Notary Public

Print Name: Kathleen E Burns


My Commission Expires: 11/13/20

**LANDLORD ACKNOWLEDGMENT**

State of CT  
County of Middlesex

On this the 8th day of January, 2014 before me, Andrea P. Atkins the undersigned officer, personally appeared Andrea Martorelli who acknowledged himself to be the partner of Martorelli Realty Company, a partnership, and that he, as such partner, being authorized so to do, executed the foregoing instrument for the purposes therein contained, by signing the name of the partnership by himself as a partner.

In witness whereof I hereunto set my hand.

  
Andrea P. Atkins  
Notary Public

Print Name: \_\_\_\_\_

My Commission Expires: 6/30/14